AGENT-LEVEL OCR: A BENCHMARK AND AN OCR-ENHANCED AGENT

Anonymous authors
Paper under double-blind review

ABSTRACT

Optical character recognition (OCR) has advanced from transcribing individual characters to recognition and layout-aware parsing, supported by increasingly capable models and benchmarks. Existing benchmarks, however, primarily evaluate a model response to a prescribed image or document. A complete agent faces a broader problem: it must recognize when OCR is needed, locate the relevant visual evidence, verify uncertain observations, and carry the recovered information to complete a task. We define this ability to acquire, verify, and use visual-text information during task execution as agent-level OCR capability. To measure it, we introduce OCR Agent Bench, which extends the evaluation unit from an isolated model response to a complete agent execution spanning the reasoning model, harness, skills, tools, and OCR backend. The benchmark contains 260 executable tasks that evaluate delivered artifacts against task-specific criteria and source evidence. This evaluation target also motivates CLOCR Agent. Pre-extracted OCR alone does not tell an agent where to inspect, when to obtain another observation, or how to associate recovered information with its source. CLOCR Agent instead turns OCR from fixed preprocessing into an on-demand, locally verifiable, and source-associated capability through OCR-oriented guidance, source-addressed evidence operations, structured content access, and selective local OCR. Across 17 evaluated model–harness configurations, CLOCR Agent achieves the highest overall score (68.3) and ranks first for three of the four reasoning models.

1 INTRODUCTION

Optical character recognition (OCR) has progressed from transcribing individual characters to recovering the content and structure of complex visual documents. Modern OCR systems parse page layouts, tables, formulas, and heterogeneous elements (Cui et al., 2021; Wei et al., 2024; Niu et al., 2026; Cui et al., 2026). Benchmarks such as OmniDocBench, OCRBench v2, olmOCR-Bench, and Ocean-OCR Bench collectively cover full-page PDF parsing, bilingual recognition and reasoning, structure-preserving PDF conversion, and document, scene, and handwritten text (Ouyang et al., 2025; Fu et al., 2025; Poznanski et al., 2025; Chen et al., 2025). These advances have produced strong OCR models and increasingly comprehensive evaluations of their outputs.

OCR as a capability of complete agents, however, remains insufficiently evaluated. Existing OCR benchmarks pair a visual input with a question or output specification and score the model's response. This setup establishes whether an OCR model or parser can recover content from the supplied input, but it does not reveal whether an agent can use OCR to complete a task. An agent must determine whether OCR is needed and locate the relevant file, page, and region. When existing observations are insufficient, it must continue inspection or rerun recognition. The recovered information must then remain associated with its source and the task requirements and be used in the final artifact. Document-agent benchmarks cover adjacent operations such as retrieval and manipulation (Hu et al., 2026; Jiang et al., 2026), but they do not isolate this capability.

We therefore define *agent-level OCR capability* as the ability of a complete agent to acquire, verify, and use visual-text information during task execution. Unlike model-level OCR, this capability depends on decisions about evidence that connect task materials to the final artifact. The delivered artifact and its support in the source materials provide observable evidence of these decisions. Figure 1 contrasts the two evaluation units.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: Model-level OCR evaluation and OCR Agent Bench. Model-level benchmarks score a response to a prescribed image, whereas OCR Agent Bench evaluates the end-to-end process from task materials to the required artifact.

To measure this capability, we introduce OCR Agent Bench. Its central change is to extend OCR evaluation from an isolated model response to a complete agent execution. Each of its 260 executable tasks supplies an instruction, source materials, execution constraints, and an output specification, but it does not prescribe an OCR transcript or action sequence. The Judge instead evaluates the completed artifact against task-specific criteria and the available source evidence. OCR Agent Bench thereby makes the acquisition and task-directed use of visual-text evidence an explicit evaluation target.

This evaluation target also clarifies why access to OCR output alone is insufficient. Providing an agent with pre-extracted OCR text does not determine which sources to inspect, when uncertain content requires further inspection, or how recovered information should remain associated with its source and the task requirements. We therefore introduce CLOCR Agent, which turns OCR from a one-time preprocessing result into a task-directed capability that can be used on demand to verify local content and preserve source references. It implements this capability in a general-purpose agent through an OCR-oriented skill, source-addressed evidence operations, selective local re-OCR, and an OCR backend. Figure 2 summarizes the resulting execution process.

We evaluate complete model–harness configurations on OCR Agent Bench, compare CLOCR Agent with matched general-purpose and OCR-access baselines, and use component and backend ablations to examine individual design choices. A complementary HarnessBench evaluation examines general task performance under a shared backbone. Across 17 evaluated model–harness configurations, CLOCR Agent achieves a state of the art on OCR Agent Bench at 68.3 Overall and ranks first for three of the four matched reasoning models.

Our contributions are:

- **Agent-level OCR formulation.** We distinguish model-level OCR performance from agent-level OCR capability and define the latter through the acquisition, verification, and task-directed use of visually encoded content.
- **OCR Agent Bench.** We introduce 260 executable tasks that extend the unit of OCR evaluation from an isolated model response to an end-to-end agent execution, identifying recognition, evidence acquisition, verification, organization, and uncertainty handling when OCR is needed.



Figure 2: CLOCR Agent framework for OCR-dependent task execution. The host agent uses an OCR skill and source-addressed Search, Read, and re-OCR operations to produce the required artifact; OCR Agent Bench evaluates the resulting execution.

- **CLOCR Agent.** We transform OCR from fixed preprocessing into a task-directed capability through an OCR-oriented skill, source-addressed evidence operations, structured access, and selective region-level re-OCR.

2 Related Work

OCR models and benchmarks. OCR commonly combines text detection and recognition. DB improves segmentation-based detection through differentiable binarization (Liao et al., 2020), while TrOCR uses pre-trained image and text Transformers for recognition (Li et al., 2023). Document models also incorporate spatial and visual context: LayoutLMv3 jointly encodes text, layout, and image patches (Huang et al., 2022), and Donut generates structured outputs directly from document images without a separate OCR engine (Kim et al., 2022). GOT extends generative OCR to text, formulas, tables, and other visual symbols (Wei et al., 2024); MinerU2.5 separates global layout analysis from local content recognition for high-resolution parsing (Niu et al., 2026); PaddleOCR-VL-1.5 targets document parsing under real-world visual distortions (Cui et al., 2026); and CL-OCR combines layout fusion with recognition adaptation for documents in the wild (Yuan et al., 2026). Benchmark coverage now ranges from diverse full-page parsing and bilingual visual-text tasks to structure-preserving PDF conversion and OCR across document, scene, and handwritten inputs (Ouyang et al., 2025; Fu et al., 2025; Poznanski et al., 2025; Chen et al., 2025). ParseBench further evaluates whether parser outputs preserve the structure and semantics required by downstream agents (Zhang et al., 2026). These benchmarks assess OCR models or parsing systems from their outputs.

Benchmarks for agent evaluation. Agent benchmarks evaluate interactions with environments and the resulting task states. Document agents use structured retrieval, reflection, and skill-mediated tool interaction (Sun et al., 2025; Wen et al., 2026; Xiang et al., 2026). OpenClaw provides an open-source harness for tool-mediated agent execution (OpenClaw Foundation, 2026). OSWorld measures agents through interaction with computer environments (Xie et al., 2024), while Terminal-Bench evaluates the final states produced in command-line tasks (Merrill et al., 2026). Benchmarks for document-intensive tasks examine related capabilities: VisDocAgentBench focuses on iterative retrieval and page selection (Hu et al., 2026), DocOps on document manipulation (Jiang et al., 2026), OfficeQA Pro on grounded reasoning over enterprise files (Opsahl-Ong et al., 2026), and Analyst-Bench on report generation (Pham et al., 2026). Together, these benchmarks establish execution-level evaluation for interaction, retrieval, manipulation, grounded reasoning, and artifact generation. OCR Agent Bench applies this perspective to decisions about OCR throughout task execution.



(a) Industry and task category distribution.

(b) Primary OCR challenge distribution.

Figure 3: OCR Agent Bench coverage across industry domains, task categories, and primary OCR challenges. Domain abbreviations are HC, healthcare; ENG, engineering; LAW, law; RES, research; XIND, cross-industry; FIN, finance; and RET, retail. Task-category abbreviations are AUD, audit; EXT, extraction; PROC, processing; PLAN, planning; and GEN, generation.

3 METHOD

3.1 OCR AGENT BENCH

OCR Agent Bench contains 260 executable tasks across seven industry domains. Each task provides an instruction, a set of source files, execution constraints, and required artifacts. Completing the task requires an agent to recover text or structure encoded in visual inputs and carry that evidence into the output.

The task collection covers multiple forms of OCR-dependent agent behavior without prescribing a tool sequence or output wording. Figure 3a summarizes its distribution across industry domains and task categories, while Figure 3b reports the primary OCR challenge associated with each task. This organization supports analysis across task conditions while retaining a common evaluation target: whether an agent uses visually available evidence correctly to complete the task.

We formalize an OCR agent task as a specification over materials and acceptable outputs:

$$x_i = (q_i, D_i, \kappa_i, o_i), \qquad \mathcal{Y}_i = \mathcal{Y}(q_i, D_i, \kappa_i, o_i). \tag{1}$$

Here q_i is the instruction, D_i the source collection, κ_i the execution constraints, and o_i the artifact requirements. The set $\mathcal{Y}_i$ contains artifacts that satisfy the task and are supported by the available source content, including an explicit unresolved state when the materials do not support a definite result. The formulation does not prescribe an execution strategy while making successful content use observable in the delivered artifact.

The Judge uses task-specific scoring criteria derived from the required artifact and its supporting source evidence. The score reflects whether the execution recovers the required visual information, preserves the relations needed by the task, and produces an artifact supported by the sources. Because a task may admit multiple valid executions, the Judge uses task requirements and evidence support rather than reference-string matching or a prescribed trajectory. The agent receives the instruction and source files, while the scoring criteria and reference evidence remain Judge-only. Inspired by the Agentic Data Flow for capability-oriented data construction in HunyuanOCR-1.5 (Li et al., 2026), we develop Agentic Data Engine (ADE) for executable benchmark construction. Initialized from human-verified seed examples, ADE organizes task objectives, source materials, artifact requirements, and task-specific scoring criteria into executable tasks, then submits generated candidates for Agent review, repair, and execution validation. Appendix A.6.2 describes this procedure.

3.2 CLOCR AGENT

3.2.1 OVERVIEW AND FORMULATION

CLOCR Agent is a task-adaptive agent for completing OCR-dependent tasks, as illustrated in Figure 2. Given a task x_i, it selects OCR evidence operations during execution and transforms source-addressed observations into a task artifact. Rather than treating OCR as a fixed preprocessing stage, CLOCR Agent interleaves content acquisition, targeted verification, and artifact construction according to the current task state.

CLOCR Agent combines a reasoning model $\mathcal{M}$, an OCR skill $\mathcal{S}$, executable OCR tools $\mathcal{T}$, and an OCR backend $\mathcal{F}_{\mathrm{OCR}}$; together they form the agent configuration $A = (\mathcal{M}, \mathcal{S}, \mathcal{T}, \mathcal{F}_{\mathrm{OCR}})$. At step k, the execution state is $s_k = (x_i, \mathcal{O}_k, y_k, \beta_k)$, comprising the task, accumulated observations, current artifact, and remaining execution budget. Conditioned on this state, the skill guides the selection of an OCR operation a_k and its scope z_k:

$$(a_k, z_k) \sim \pi_{\mathcal{M},\mathcal{S}}(\cdot \mid s_k, \mathcal{T}). \tag{2}$$

The selected tool then applies the selected OCR operation to the source collection and returns an observation:

$$e_k = \mathcal{T}_{a_k}(D_i, z_k; \mathcal{F}_{\mathrm{OCR}}). \tag{3}$$

Here e_k is the resulting observation. The reasoning model and OCR backend remain fixed during execution. CLOCR Agent changes how their capabilities are selected, connected to source material, and used to complete the task.

3.2.2 TASK-ADAPTIVE OCR ACCESS

The OCR skill guides evidence access according to the unmet artifact requirements and the state of the materials. It does not prescribe a fixed tool sequence. The routing policy favors operations that provide broad task-relevant coverage at lower acquisition cost, and increases representational detail or narrows the source scope only when the current observations cannot support a required decision. The resulting process directs OCR computation to information that can affect the artifact rather than applying an identical recognition procedure to every input.

Search and Read implement complementary OCR access operations. Search establishes content coverage and candidate locations across the source collection. Read retrieves task-relevant text, structured content, or source pixels at the required granularity, and region-level re-OCR acquires a new observation when the current representation is insufficient. Coverage metadata distinguishes indexed content from visual inspection, while reusable observations prevent repeated access to the same OCR evidence from being treated as new information. Structured representations preserve relations needed for downstream reasoning, and artifact transformations remain separate from evidence acquisition so that original materials are not overwritten.

3.2.3 SOURCE-ADDRESSED REFINEMENT AND ARTIFACT CONSTRUCTION

Each observation is represented as $e_k = (v_k, \rho_k, f_k)$, where v_k is its value, f_k its representation, and $\rho_k = (d_k, p_k, b_k, \nu_k)$ its source-item, page, region, and version reference. CLOCR Agent adds the observation to its accumulated evidence and uses it to revise the current artifact:

$$\mathcal{O}_{k+1} = \mathcal{O}_k \cup \{e_k\}, \qquad y_{k+1} = g_{\mathcal{M},\mathcal{S}}(x_i, y_k, \mathcal{O}_{k+1}). \tag{4}$$

At each step, the agent reassesses the artifact requirements that remain unsupported and the OCR operations that remain relevant within the available execution budget. Evidence acquisition stops when all required content is supported or when no feasible operation is expected to change the required output. We summarize this decision criterion as

$$L_i = \min\left\{k : \mathcal{R}_i(y_k, \mathcal{O}_k) = \varnothing \ \vee \ \mathcal{A}_k^+ = \varnothing\right\}. \tag{5}$$

Here $\mathcal{R}_i$ denotes the required content that remains unsupported, and $\mathcal{A}_k^+$ denotes the OCR operations that remain relevant and feasible under the current constraints. The criterion describes the agent's execution policy rather than a separately solved optimization problem. As the remaining budget decreases, execution shifts from evidence expansion to artifact completion and validation. A

new observation supplements rather than silently replaces prior source content, allowing the agent to revisit a source, compare conflicting observations, and retain unresolved information when the materials do not warrant a definite value.

Artifact construction proceeds throughout execution rather than after exhaustive OCR processing. Each useful observation updates the current artifact and the remaining requirements, which in turn determine subsequent access. Before submission, the agent checks requirement coverage, source support, output structure, and unresolved content using only public task materials. The Judge and its private scoring evidence remain outside this execution loop.

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUP

Agents and benchmarks. We evaluate CLOCR Agent together with Codex (OpenAI, 2026a), Claude Code (Anthropic, 2026a), and Hermes (Nous Research, 2026). On OCR Agent Bench, we use GPT-5.6 Luna (OpenAI, 2026b), Claude Sonnet 5 (Anthropic, 2026b), Qwen3.8-Flash (Qwen Team, 2026), GLM-5.3-Flash (Z.ai, 2026), and DeepSeek-V4.1-Flash (DeepSeek-AI, 2026). Table 1 reports the 17 evaluated model–harness pairings. CLOCR Agent is unavailable with Claude Sonnet 5. OCR Agent Bench contains 260 OCR-dependent tasks. HarnessBench includes 106 general-purpose tasks in nine categories under GPT-5.6 Terra. All controlled ablations use CLOCR Agent with GLM-5.3-Flash.

Execution and judging. Each OCR Agent Bench task supplies the public instruction and source files under a 400-second execution limit. Three independent Judges assess completed artifacts against task-specific criteria and private reference evidence. Overall is the primary metric, with Completion, conditional Quality, the six Judge dimensions, and resource use as secondary metrics. Resource means cover all scheduled tasks and exclude post hoc Judge inference. Appendix A.5 provides the detailed scoring, execution, and metering protocol.

4.2 EXPERIMENTAL RESULTS

Agent performance. Table 1 shows that harness choice materially changes end-to-end OCR performance even when the reasoning model is fixed. CLOCR Agent achieves the highest overall score with GPT-5.6 Luna, Qwen3.8-Flash, and DeepSeek-V4.1-Flash. For GLM-5.3-Flash, the spread between the best- and worst-performing harnesses is 10.2 Overall points. DeepSeek-V4.1-Flash with CLOCR Agent achieves the highest overall score among the evaluated configurations at 68.3, exceeding the next-best configuration, DeepSeek-V4.1-Flash with Claude Code, by 7.8 points. The variation within a fixed reasoning model supports treating the model and harness as a joint evaluation unit. Structure and relationship understanding is the highest-scoring Judge dimension for all 17 configurations, whereas verification, conflict handling, and uncertainty calibration is the lowest-scoring dimension for 13 configurations.

Industry domain variation. Figure 4 complements the aggregate comparison with domain-level differences. Relative to the strongest shown baseline for each model and domain, CLOCR Agent improves scores in 11 of 28 model–domain pairs. Gains occur in Research, Cross-industry, and Finance across several backbones. The results therefore identify a model- and domain-dependent gain rather than a consistent improvement.

Efficiency and reliability. Figures 5 and 6 examine how performance varies with resource use and task completion. In the inspected traces, we observed repeated acquisition of overlapping visual evidence. This pattern adds tool calls and context input, indicating that efficient multimodal execution also depends on how the harness preserves prior observations. CLOCR Agent achieves high scores with DeepSeek-V4.1-Flash, Qwen3.8-Flash, and GPT-5.6 Luna. With GLM-5.3-Flash, it reaches an overall score of 50.8, 5.4 points below Codex, while using 41% fewer tokens per task (209.5k versus 355.4k) and 40% fewer requests (8.1 versus 13.6). Table 7 provides the exact resource measurements. Runtime failures are dominated by timeouts. CLOCR Agent has the lowest failure rate with DeepSeek-V4.1-Flash, GLM-5.3-Flash, and GPT-5.6 Luna. Because unsuccessful



(a) Model and harness comparison **(b)** Industry domain comparison

Figure 4: OCR Agent Bench results across reasoning models and harnesses. The left panel reports Overall scores, while the right panel reports CLOCR Agent's industry domain score changes relative to the strongest shown baseline for each model.

Table 1: OCR Agent Bench performance by model and harness. Comp.: completion; Fid.: content fidelity; Evid.: evidence support; Struct.: structural understanding; Use.: deliverable usability; Reason.: task reasoning; Verify.: verification (weights: 25/10/15/15/20/15%). Across all evaluated model–harness configurations, the first and second highest Overall, Comp., and Quality scores are marked in red and blue, respectively.

Model	Harness	Overall	Comp. (%)	Quality	Fid.	Evid.	Struct.	Use.	Reason.	Verify.
GPT-5.6 Luna	Codex	37.2	50.4	73.7	36.4	36.3	39.7	37.7	38.0	33.9
	Hermes	42.6	61.2	69.7	41.3	41.5	46.0	43.2	43.9	39.2
	CLOCR Agent	51.4	93.1	55.2	48.2	50.7	56.7	51.3	51.2	50.6
Claude Sonnet 5	Claude Code	23.5	35.8	65.6	23.2	22.8	25.2	23.2	23.9	21.7
	Hermes	37.2	52.3	71.2	36.6	35.9	40.0	36.7	38.3	34.7
	CLOCR Agent	–	–	–	–	–	–	–	–	–
Qwen3.8-Flash	Codex	9.9	12.7	78.3	9.7	9.9	10.5	10.2	10.1	9.2
	Claude Code	44.7	61.9	72.2	43.1	44.1	47.2	44.2	45.7	43.3
	Hermes	57.7	79.2	72.8	55.3	56.7	61.0	58.7	59.4	54.5
	CLOCR Agent	58.8	78.5	74.9	55.9	59.0	61.8	59.2	59.7	57.5
GLM-5.3-Flash	Codex	56.2	78.1	72.0	54.9	54.2	60.4	57.2	57.6	51.4
	Claude Code	46.0	69.6	66.1	44.9	44.9	49.7	45.3	47.3	43.1
	Hermes	50.2	69.2	72.6	48.8	49.1	53.7	50.7	51.6	46.7
	CLOCR Agent	50.8	90.8	55.9	49.5	49.4	56.3	47.6	52.1	48.3
DeepSeek-V4.1-Flash	Codex	43.8	56.5	77.5	42.5	43.4	46.6	44.4	44.7	40.9
	Claude Code	60.5	84.6	71.5	58.8	59.6	64.1	60.2	62.0	57.6
	Hermes	56.2	76.5	73.4	54.2	55.9	59.8	56.6	56.9	53.8
	CLOCR Agent	68.3	95.4	71.6	66.8	68.3	72.1	66.7	69.0	66.1

executions contribute zero to Overall, completion reliability directly affects the end-to-end result. The concentration of failures in timeouts motivates the execution-time ablation below.

General-purpose performance. HarnessBench tests whether the OCR-oriented additions preserve general-purpose Agent performance outside OCR Agent Bench. Table 2 compares CLOCR Agent with Hermes and Codex by category under the shared GPT-5.6-Terra backbone. CLOCR Agent attains the highest category mean, 84.0%, and leads seven of the nine categories, while Codex leads File System and Domain-Specific tasks. Table 3 summarizes the aggregate result and resource use. CLOCR Agent achieves the highest score, 85.3%, and cache-hit rate, but uses more tokens than Codex and has the longest mean execution time among the three harnesses. The comparison under a shared backbone highlights differences between the harness configurations and shows that the OCR-oriented capability layer retains competitive general-purpose performance, with higher token use and longer runtime than Codex.



Figure 5: Performance and resource use on OCR Agent Bench. The panels compare task score with mean inference cost (left) and token use (right) for each model–harness configuration.



Figure 6: Failure composition on OCR Agent Bench. The bars report failure rates by reasoning model and harness, decomposed into timeout, compatibility, adapter or tool, interruption, and other runtime errors.

Table 2: HarnessBench performance by task category with GPT-5.6-Terra. The table reports category scores and their unweighted mean for each harness.

Harness	File System	Software Engineering	Data Analytics	State & Memory	DevOps & Operations	Knowledge & Research	Document Processing	Domain-Specific	Adversarial & Defense	Category Mean
Hermes	90.2	88.4	80.7	84.5	80.0	73.1	80.1	75.8	72.6	80.6
Codex	**95.7**	89.2	82.5	85.8	80.1	82.2	80.8	**76.8**	68.1	82.4
CLOCR Agent	92.5	**90.3**	**83.6**	**90.3**	**84.6**	**84.5**	**82.7**	73.0	**74.8**	**84.0**

Table 3: HarnessBench performance with GPT-5.6-Terra. The table reports score, token use, cache-hit rate, and execution time.

Harness	Score (%)	Tokens (M)	Cache (%)	Time (s)
Hermes	81.8	35.2	82.1	164
Codex	84.1	13.3	79.6	82
CLOCR Agent	**85.3**	20.1	**84.4**	201

Table 4: OCR backend ablation with GLM-5.3-Flash. The table reports task performance and token use for each backend.

Backend	Overall	Comp. (%)	Quality	Tokens/Task (k)
MinerU	50.8	90.8	55.9	209.5
CL-OCR	**53.2**	91.2	**58.3**	215.0
PaddleOCR-VL-1.5	51.9	**91.9**	56.5	205.0

4.3 Ablation Studies

All ablations use CLOCR Agent with GLM-5.3-Flash and retain the same task inputs and execution environment.

Component contribution. Tables 4 and 5 report the OCR-backend and component ablations. Changing the OCR backend produces a narrow Overall range of 50.8–53.2. CL-OCR achieves the highest Overall and Quality scores, 53.2 and 58.3, while PaddleOCR-VL-1.5 reaches the highest Completion, 91.9%, with the lowest token use, 205.0k per task. The component effects are larger. Removing the skill reduces Overall from 50.8 to 47.2 and Completion from 90.8% to 87.4%, while increasing token use from 209.5k to 224.3k. Removing source-addressed tools causes the largest decline, to 37.3 Overall and 71.0% Completion, showing that interactive evidence access primarily supports reliable task completion. Pre-extracted OCR raises Overall to 44.1 and Completion to 83.7%, but remains below the full system while using 241.2k tokens. Together, the backend affects the quality–efficiency balance, whereas the skill and tools govern how reliably OCR evidence is acquired and converted into task artifacts.

Table 5: CLOCR Agent component ablation. The table reports component settings, task performance, and token use for each configuration. ✓ and ✗ denote enabled/present and disabled/absent components, respectively.

Configuration	Tools	Skill	Pre-extracted OCR	Overall	Completion (%)	Quality	Tokens / Task (k)
Full CLOCR Agent	✓	✓	✗	50.8	90.8	55.9	209.5
−Skill	✓	✗	✗	47.2	87.4	54.0	224.3
−Tools	✗	✓	✗	37.3	71.0	52.5	158.7
−Tools + pre-extracted OCR	✗	✓	✓	44.1	83.7	52.7	241.2

Execution time budget. Table 6 reports the measured effect of per-task limits of 400, 800, and 1200 seconds. Completion rises from 90.8% to 96.5% and 98.5%, and Overall increases from 50.8 to 53.8 and 55.7. Conditional Quality remains within 55.8–56.6, while tokens per task increase from 209.5k to 229.6k and 236.3k. Additional time therefore recovers tasks that would otherwise time out, with little change in the quality of completed artifacts. The primary effect is improved completion reliability.

Table 6: Execution-time ablation of CLOCR Agent. The table reports task performance, completion outcomes, and token use at each per-task limit.

Time Limit (s)	Overall	Completion (%)	Quality	Completed	Timeouts	Tokens / Task
400	50.8	90.8	55.9	236/260	24	209.5k
800	53.8	96.5	55.8	251/260	9	229.6k
1200	55.7	98.5	56.6	256/260	4	236.3k

5 Conclusion

OCR Agent Bench evaluates agent-level OCR through task artifacts and their support in source materials. CLOCR Agent combines reusable OCR guidance, source-addressed access, and selective re-OCR to support this process. Across 17 evaluated model–harness configurations, it ranks first for three of the four matched reasoning models and reaches 68.3, the highest overall score among the evaluated configurations. Under the shared backbone, it also achieves the highest HarnessBench score of 85.3%. The results show that agent-level OCR depends on both visual recognition and how the harness acquires, retains, and applies evidence. Trace inspection and the time-budget study further highlight evidence reuse and execution reliability as practical bottlenecks.

6 Limitations

OCR Agent Bench covers seven industry domains, so its conclusions are specific to the evaluated tasks, model–harness configurations, OCR backends, runtime interfaces, and Judge protocol. Rare scripts, degraded sources, larger collections, and longer interactions may expose additional failures. Trace inspection reveals repeated visual evidence acquisition but does not quantify its prevalence or causal effect. Open-domain agent-level OCR remains future work.

REFERENCES

Anthropic. Claude Code, 2026a. URL https://code.claude.com/docs/en/overview.

Anthropic. Introducing Claude Sonnet 5, 2026b. URL https://www.anthropic.com/news/claude-sonnet-5.

Song Chen, Xinyu Guo, Yadong Li, Tao Zhang, Mingan Lin, Dongdong Kuang, Youwei Zhang, Lingfeng Ming, Fengyu Zhang, Yuran Wang, Jianhua Xu, Zenan Zhou, and Weipeng Chen. Ocean-OCR: Towards general OCR application via a vision-language model. *arXiv preprint arXiv:2501.15558*, 2025. doi: 10.48550/arXiv.2501.15558. URL https://arxiv.org/abs/2501.15558.

Cheng Cui, Ting Sun, Suyin Liang, Tingquan Gao, Zelun Zhang, Jiaxuan Liu, Xueqing Wang, Changda Zhou, Hongen Liu, Manhui Lin, Yue Zhang, Yubo Zhang, Yi Liu, Dianhai Yu, and Yanjun Ma. PaddleOCR-VL-1.5: Towards a multi-task 0.9b VLM for robust in-the-wild document parsing. *arXiv preprint arXiv:2601.21957*, 2026. URL https://arxiv.org/abs/2601.21957.

Lei Cui, Yiheng Xu, Tengchao Lv, and Furu Wei. Document AI: Benchmarks, models and applications. *arXiv preprint arXiv:2111.08609*, 2021. URL https://arxiv.org/abs/2111.08609.

DeepSeek-AI. DeepSeek V4.1 Flash, 2026. URL https://deepseek.com/news/deepseek-v4-1-flash/.

Ling Fu, Zhebin Kuang, Jiajun Song, Mingxin Huang, Biao Yang, Yuzhe Li, Linghao Zhu, Qidi Luo, Xinyu Wang, Hao Lu, Zhang Li, Guozhi Tang, Bin Shan, Chunhui Lin, Qi Liu, Binghong Wu, Hao Feng, Hao Liu, Can Huang, Jingqun Tang, Wei Chen, Lianwen Jin, Yuliang Liu, and Xiang Bai. OCRBench v2: An improved benchmark for evaluating large multimodal models on visual text localization and reasoning. In *Advances in Neural Information Processing Systems*, volume 38, 2025. doi: 10.52202/085713-3253. URL https://papers.nips.cc/paper_files/paper/2025/hash/8c2e6bb15be1894b8fb4e0f9bcad1739-Abstract-Datasets_and_Benchmarks_Track.html.

Lexiang Hu, Yanzhao Zhang, Mingxin Li, Dingkun Long, Yikang Li, Fuwei Zhang, Yisen Wang, and Zhouchen Lin. VisDocAgentBench: Benchmarking agents for visually rich document retrieval. *arXiv preprint arXiv:2608.17889*, 2026. URL https://arxiv.org/abs/2608.17889.

Yupan Huang, Tengchao Lv, Lei Cui, Yutong Lu, and Furu Wei. LayoutLMv3: Pre-training for document AI with unified text and image masking. In *Proceedings of the 30th ACM International Conference on Multimedia*, 2022. doi: 10.1145/3503161.3548112. URL https://arxiv.org/abs/2204.08387.

Jiazhen Jiang, Boxi Cao, Lingyong Yan, Yaojie Lu, Hongyu Lin, Shuaiqiang Wang, Dawei Yin, Xianpei Han, and Le Sun. DocOps: A verifiable benchmark for autonomous agents in complex document operations. *arXiv preprint arXiv:2607.19865*, 2026. URL https://arxiv.org/abs/2607.19865.

Geewook Kim, Teakgyu Hong, Moonbin Yim, JeongYeon Nam, Jinyoung Park, Jinyeong Yim, Wonseok Hwang, Sangdoo Yun, Dongyoon Han, and Seunghyun Park. OCR-free document understanding transformer. In *European Conference on Computer Vision*, 2022. URL https://www.ecva.net/papers/eccv_2022/papers_ECCV/html/8042_ECCV_2022_paper.php.

Gengluo Li, Xingyu Wan, Shangpin Peng, Weinong Wang, Hao Feng, Yongkun Du, Binghong Wu, Zheng Ruan, Zhiqiong Lu, Liang Wu, Pengyuan Lyu, Huawen Shen, Zibin Lin, Shijing Hu, Jieneng Yang, Hongbing Wen, Guanghua Yu, Hong Liu, Bochao Wang, Can Ma, Han Hu, Chengquan Zhang, and Yu Zhou. HunyuanOCR-1.5: Making lightweight OCR VLMs faster and better. *arXiv preprint arXiv:2607.04884*, 2026. doi: 10.48550/arXiv.2607.04884. URL https://arxiv.org/abs/2607.04884.

Minghao Li, Tengchao Lv, Jingye Chen, Lei Cui, Yijuan Lu, Dinei Florencio, Cha Zhang, Zhoujun Li, and Furu Wei. TrOCR: Transformer-based optical character recognition with pre-trained models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pp. 13094–13102, 2023. doi: 10.1609/aaai.v37i11.26538. URL https://ojs.aaai.org/index.php/AAAI/article/view/26538.

Minghui Liao, Zhaoyi Wan, Cong Yao, Kai Chen, and Xiang Bai. Real-time scene text detection with differentiable binarization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 11474–11481, 2020. doi: 10.1609/aaai.v34i07.6812. URL https://ojs.aaai.org/index.php/AAAI/article/view/6812.

Mike A. Merrill, Alexander G. Shaw, Nicholas Carlini, Boxuan Li, Harsh Raj, Ivan Bercovich, Lin Shi, Jeong Yeon Shin, Thomas Walshe, E. Kelly Buchanan, Junhong Shen, Guanghao Ye, Haowei Lin, Jason Poulos, Maoyu Wang, Marianna Nezhurina, Jenia Jitsev, Di Lu, Orfeas Menis Mastromichalakis, Zhiwei Xu, Zizhao Chen, Yue Liu, Robert Zhang, Leon Liangyu Chen, Anurag Kashyap, Jan-Lucas Uslu, Jeffrey Li, Jianbo Wu, Minghao Yan, Song Bian, Vedang Sharma, Ke Sun, Steven Dillmann, Akshay Anand, Andrew Lanpouthakoun, Bardia Koopah, Changran Hu, Etash Guha, Gabriel H. S. Dreiman, Jiacheng Zhu, Karl Krauth, Li Zhong, Niklas Muennighoff, Robert Amanfu, Shangyin Tan, Shreyas Pimpalgaonkar, Tushar Aggarwal, Xiangning Lin, Xin Lan, Xuandong Zhao, Yiqing Liang, Yuanli Wang, Zilong Wang, Changzhi Zhou, David Heineman, Hange Liu, Harsh Trivedi, John Yang, Junhong Lin, Manish Shetty, Michael Yang, Nabil Omi, Negin Raoof, Shanda Li, Terry Yue Zhuo, Wuwei Lin, Yiwei Dai, Yuxin Wang, Wenhao Chai, Shang Zhou, Dariush Wahdany, Ziyu She, Jiaming Hu, Zhikang Dong, Yuxuan Zhu, Sasha Cui, Ahson Saiyed, Arinbjörn Kolbeinsson, Jesse Hu, Christopher Michael Rytting, Ryan Marten, Yixin Wang, Alex Dimakis, Andy Konwinski, and Ludwig Schmidt. Terminal-Bench: Benchmarking agents on hard, realistic tasks in command line interfaces. *arXiv preprint arXiv:2601.11868*, 2026. URL https://arxiv.org/abs/2601.11868.

Junbo Niu, Zheng Liu, Zhuangcheng Gu, Bin Wang, Linke Ouyang, Zhiyuan Zhao, Tao Chu, Tianyao He, Fan Wu, Qintong Zhang, Zhenjiang Jin, Guang Liang, Rui Zhang, Wenzheng Zhang, Yuan Qu, Zhifei Ren, Yuefeng Sun, Zirui Tang, Boyu Niu, Yuanhong Zheng, Dongsheng Ma, Ziyang Miao, Hejun Dong, Siyi Qian, Junyuan Zhang, Fangdong Wang, Jingzhou Chen, Xiaomeng Zhao, Liqun Wei, Wei Li, Shasha Wang, RuiLiang Xu, Yuanyuan Cao, Lu Chen, Qianqian Wu, Huaiyu Gu, Lindong Lu, Dechen Lin, Shenguanlin, Xuanhe Zhou, Linfeng Zhang, Yuhang Zang, Xiaoyi Dong, Jiaqi Wang, Bo Zhang, Lei Bai, Pei Chu, Weijia Li, Jiang Wu, Lijun Wu, Zhenxiang Li, Guangyu Wang, Zhongying Tu, Chao Xu, Kai Chen, Bowen Zhou, Dahua Lin, Wentao Zhang, and Conghui He. MinerU2.5: A decoupled vision-language model for efficient high-resolution document parsing. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 6: Industry Track)*, pp. 13–42. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.acl-industry.3. URL https://aclanthology.org/2026.acl-industry.3/.

Nous Research. Hermes Agent, 2026. URL https://github.com/NousResearch/hermes-agent.

OpenAI. Codex CLI, 2026a. URL https://github.com/openai/codex.

OpenAI. GPT-5.6: Frontier intelligence that scales with your ambition, 2026b. URL https://openai.com/index/gpt-5-6/.

OpenClaw Foundation. OpenClaw, 2026. URL https://github.com/openclaw/openclaw.

Krista Opsahl-Ong, Arnav Singhvi, Jasmine Collins, Ivan Zhou, Cindy Wang, Ashutosh Baheti, Owen Oertell, Jacob Portes, Sam Havens, Erich Elsen, Michael Bendersky, Matei Zaharia, and Xing Chen. OfficeQA Pro: An enterprise benchmark for end-to-end grounded reasoning. *arXiv preprint arXiv:2603.08655*, 2026. URL https://arxiv.org/abs/2603.08655.

Linke Ouyang, Yuan Qu, Hongbin Zhou, Jiawei Zhu, Rui Zhang, Qunshu Lin, Bin Wang, Zhiyuan Zhao, Man Jiang, Xiaomeng Zhao, Jin Shi, Fan Wu, Pei Chu, Minghao Liu,

Zhenxiang Li, Chao Xu, Bo Zhang, Botian Shi, Zhongying Tu, and Conghui He. OmniDocBench: Benchmarking diverse PDF document parsing with comprehensive annotations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 24838–24848, 2025. doi: 10.1109/CVPR52734.2025.02313. URL https://openaccess.thecvf.com/content/CVPR2025/html/Ouyang_OmniDocBench_Benchmarking_Diverse_PDF_Document_Parsing_with_Comprehensive_Annotations_CVPR_2025_paper.html.

Chau Minh Pham, Zichao Wang, Puneet Mathur, Alexa Siu, Akriti Jain, Aparna Garimella, Ananya B. Sai, Nedim Lipka, Mohit Iyyer, and Varun Manjunatha. AnalystBench: Benchmarking professional long-form report generation with web-mined multimodal tasks. In *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 23894–23926. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.findings-acl.1197. URL https://aclanthology.org/2026.findings-acl.1197/.

Jake Poznanski, Jon Borchardt, Jason Dunkelberger, Regan Huff, Daniel Lin, Aman Rangapur, Christopher Wilhelm, Kyle Lo, and Luca Soldaini. olmOCR: Unlocking trillions of tokens in PDFs with vision language models. *arXiv preprint arXiv:2502.18443*, 2025. doi: 10.48550/arXiv.2502.18443. URL https://arxiv.org/abs/2502.18443.

Qwen Team. Qwen3.8, 2026. URL https://github.com/QwenLM/Qwen3.8.

Li Sun, Liu He, Shuyue Jia, Yangfan He, and Chenyu You. DocAgent: An agentic framework for multi-modal long-context document understanding. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 17701–17716. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.emnlp-main.893. URL https://aclanthology.org/2025.emnlp-main.893/.

Haoran Wei, Chenglong Liu, Jinyue Chen, Jia Wang, Lingyu Kong, Yanming Xu, Zheng Ge, Liang Zhao, Jianjian Sun, Yuang Peng, Chunrui Han, and Xiangyu Zhang. General OCR theory: Towards OCR-2.0 via a unified end-to-end model. *arXiv preprint arXiv:2409.01704*, 2024. URL https://arxiv.org/abs/2409.01704.

Shimin Wen, Zeyu Zhang, Xingdou Bian, Hongjie Zhu, Lulu He, Layi Shama, Daji Ergu, and Ying Cai. OCR-Agent: Agentic OCR with capability and memory reflection. *arXiv preprint arXiv:2602.21053*, 2026. URL https://arxiv.org/abs/2602.21053.

Siqi Xiang, Zhipeng Xu, Yufei Liu, Junhao Ji, Qing Liu, Zulong Chen, Zhibo Yang, Chunyan Miao, and Shijian Lu. DocClaw: A unified agentic system for intelligent document processing. *arXiv preprint arXiv:2608.18685*, 2026. URL https://arxiv.org/abs/2608.18685.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. OSWorld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *arXiv preprint arXiv:2404.07972*, 2024. URL https://arxiv.org/abs/2404.07972.

Haijie Yuan, Yiming Zhang, Dekang Ran, Yi Chen, Xinming Wang, Jun Cao, Wenzhuo Liu, Xiao-Hui Li, Fei Zhu, Fei Yin, and Cheng-Lin Liu. CL-OCR: Fusing layout analysis and adapting recognition for document parsing in the wild. In *Findings of the Association for Computational Linguistics: EMNLP 2026*, 2026. URL https://openreview.net/forum?id=E3p8ih8RS8.

Z.ai. GLM-5.3-Flash, 2026. URL https://huggingface.co/zai-org/GLM-5.3-Flash.

Boyang Zhang, Sebastián G. Acosta, Preston Carlson, Sacha Bron, Pierre-Loïc Doulcet, and Simon Suo. ParseBench: A document parsing benchmark for AI agents. *arXiv preprint arXiv:2604.08538*, 2026. URL https://arxiv.org/abs/2604.08538.

A APPENDIX

A.1 AI USE STATEMENT

In this work, we used generative AI tools to assist with research methodology and experimental design, method implementation and testing, benchmark task construction, and manuscript translation. We did not use generative AI tools to formulate mathematical claims or proofs, and survey- and interview-related tasks are not applicable to this work. The authors reviewed and corrected all AI-assisted outputs included in the paper and tested the AI-generated code. We take responsibility for the final content of this work, including text, claims, code, data, and artifacts produced with the assistance of generative AI.

A.2 DETAILED RESOURCE RESULTS

Table 7 complements the main performance comparison with the resource profile of every evaluated configuration. Resource use alone does not explain the ranking. For example, CLOCR Agent with DeepSeek-V4.1-Flash attains the highest Overall score in Table 1, but it also uses 1.35M tokens per task, approximately twice the usage of Claude Code with the same model. With GLM-5.3-Flash, CLOCR Agent instead uses the fewest tokens and requests in its model block, yet remains below Codex in Overall. Together, these cases show that greater resource use does not monotonically predict higher Overall scores; the resource profile should therefore be interpreted alongside performance rather than as an independent efficiency ranking.

Table 7: Resource use on OCR Agent Bench. Tokens, requests, cost, and time are per scheduled-task means; across all measured model–harness configurations, the highest and second-highest Cache Hit values are marked in red and blue, respectively; Agent cost excludes Judge inference, and dashes denote unavailable measurements.

Model	Harness	Tokens (k)	Requests	Cache Hit (%)	Cost ($)	Time (s)
GPT-5.6 Luna	Codex	130.0	6.4	81.5	0.0107	306.0
	Hermes	103.3	17.3	74.6	0.0113	300.6
	CLOCR Agent	232.0	10.0	61.7	0.0260	302.9
Claude Sonnet 5	Claude Code	421.1	20.5	99.0	0.3357	329.7
	Hermes	419.3	28.1	94.7	0.6224	308.4
	CLOCR Agent	-	-	-	-	-
Qwen3.8-Flash	Codex	565.3	23.9	92.8	0.0169	365.0
	Claude Code	337.9	18.3	99.9	0.0142	267.6
	Hermes	227.1	23.2	88.8	0.0091	209.2
	CLOCR Agent	534.6	19.4	84.5	0.0216	306.4
GLM-5.3-Flash	Codex	355.4	13.6	89.8	0.0167	201.5
	Claude Code	270.8	13.4	86.3	0.0157	309.1
	Hermes	267.9	26.7	83.8	0.0162	295.9
	CLOCR Agent	209.5	8.1	56.6	0.0181	278.5
DeepSeek-V4.1-Flash	Codex	703.4	25.8	88.0	0.0470	270.0
	Claude Code	643.7	28.4	88.2	0.0493	196.2
	Hermes	1333.2	54.0	85.3	0.1297	320.2
	CLOCR Agent	1353.8	34.5	81.6	0.1216	263.0

A.3 EVALUATION METRICS

Let $N = 260$ be the number of scheduled tasks, $c_i \in \{0, 1\}$ indicate whether task i produces a Judgeable artifact, and $q_i \in [0, 100]$ denote its mean quality across the three Judges. The primary metrics are

$$\text{Completion} = 100\frac{\sum_i c_i}{N}, \qquad \text{Quality} = \frac{\sum_i c_i q_i}{\sum_i c_i}, \qquad \text{Overall} = \frac{\sum_i c_i q_i}{N}. \tag{6}$$

Thus Overall is the completion fraction multiplied by conditional Quality. A failed execution contributes zero to Overall but is excluded from Quality. The deterministic artifact check establishes only that a non-empty deliverable exists; semantic correctness is assessed by the Judges.

Each Judge assigns six scores on a 0–10 scale. For Judge j, the task score is computed outside the model as

$$q_{ij} = 10 \sum_{d=1}^{6} w_d z_{ijd}, \qquad \mathbf{w} = (0.25, 0.10, 0.15, 0.15, 0.20, 0.15), \tag{7}$$

where the dimensions are content fidelity, evidence support, structural understanding, deliverable usability, task reasoning, and verification. The dimension columns in Table 1 are diagnostic measures aggregated over the full task set with unsuccessful executions scored zero. Overall and Completion remain the primary comparison because they directly reflect artifact quality and execution reliability.

A.4 Judge–Human Agreement

We compare Overall ratings from the three LLM Judges with human ratings on a common 0–10 scale. As shown in Figure 7, GLM-5.3 Flash achieves the highest agreement with the human ratings (CCC 0.85; MAE 0.76), followed by GPT-5.6 Luna (CCC 0.82; MAE 0.89) and Qwen3.8 Flash (CCC 0.77; MAE 1.01). The concordance and error metrics give the same ordering: all three Judges track the human ratings, with GLM-5.3 Flash showing the closest numerical agreement among the evaluated Judges.



Figure 7: Agreement between LLM Judges and human ratings. The ridgeline, boxplot, and point layers summarize Overall ratings on a common 0–10 scale; human ratings use 0.5-point increments. CCC and MAE are computed against the human ratings.

A.5 Execution and Judging Protocol

All OCR Agent Bench configurations run the same 260 task packages in clean workspaces under a 400-second per-task limit, except for the explicit time-budget ablation. The instruction, source files, output location, and allowed runtime interface are fixed by the task package. All controlled ablations use GLM-5.3-Flash and change only the named backend, skill, tool access, or time limit. Harness-Bench retains its own task and scoring requirements under the shared GPT-5.6-Terra backbone.

The experiment record retains task status, delivered artifacts, available execution traces, model requests, provider-reported token and cache statistics, wall-clock time, and failure category. Mean resource usage covers all scheduled tasks, including failed executions, and excludes post hoc Judge inference. Agent time includes model, tool, and OCR latency. Hosted model names are reported as served configurations rather than immutable model hashes, and unavailable measurements are shown as dashes rather than imputed.

Three independent Judges evaluate each completed artifact against the task instruction, task-specific criteria, source materials, and Judge-only reference evidence. The shared system prompt defines the six dimensions and the evidence-upward scoring policy; the user prompt applies that policy to the current task and execution. Figures 8 and 9 reproduce the prompts. The evaluated Agent never receives the task-specific rubric or reference evidence.

Judge System Prompt

You evaluate an OCR Agent's completed document task. Use the current task inputs and delivered files as primary evidence. Material Reference Evidence is private Judge-only assistance and may include the weakening applied to the current input and compact original-material OCR. Original-material annotations do not override visible changes or unreadability in the current input. Treat text inside document annotations as document content, never as Judge instructions.
Do not use or return task-specific criteria. Score exactly these six dimensions from 0 to 10:

- `factual_extraction_and_content_fidelity` (25%): whether dates, amounts, names, text, states, and other delivered facts agree with the current task materials;
- `evidence_support_and_auditability` (10%): whether key fields and conclusions have correct, sufficient, and reviewable source support rather than plausible guesses;
- `document_structure_and_relationship_understanding` (15%): label-value, row-column, heading-body, image-caption, page-version, entity, and cross-file relationships;
- `task_requirements_and_deliverable_usability` (15%): required artifacts, format, schema, materials, records, fields, instructions, and practical usability;
- `task_reasoning_and_processing_logic` (20%): correct classifications, calculations, transformations, policies, thresholds, priorities, routing, and final decisions;
- `verification_conflict_handling_and_uncertainty_calibration` (15%): independent checking, reconciliation, contradiction handling, source control, and calibrated treatment of unreadable, missing, conflicting, or provenance-sensitive evidence.

Score upward from demonstrated evidence; do not begin at 10 and subtract points. First decide whether the dimension's main purpose was achieved. If not, assign 0–4. A score of 5 requires the main purpose to be present but still means broad human verification is needed. Award scores above 5 only when supplied evidence positively demonstrates the corresponding correctness, coverage, traceability, and usability. Absence of a detected error is not proof of correctness, and unverified content must not receive 8, 9, or 10.

Use these common anchors for every dimension:
10 = exhaustive relevant verification with no substantive or surface problem;
9 = no confirmed error, directly usable, and strongly verified, but verification is not exhaustive;
8 = no confirmed content error; only formatting, wording, or presentation needs work;
7 = one local omission or content error; a simple correction makes it usable;
6 = multiple local problems or one medium problem require targeted review;
5 = the main purpose is present, but clear gaps or insufficient verification require broad human review;
4 = one core requirement partially failed, so the result is not directly usable;
3 = the main goal mostly failed, with only a small reusable portion;
2 = only isolated correct facts remain;
1 = an attempt exists but no valid deliverable was formed;
0 = no deliverable, failed execution, wholly off task, or unreadable output.
Propagate confirmed problems to every dimension they directly affect. A wrong delivered fact affects factual fidelity and deliverable usability. A relationship error also affects structure understanding. A missing material, record, or required field affects task requirements. A policy, transformation, calculation, or routing error affects task reasoning. A missed contradiction, unsupported certainty, or failure to catch a delivered error affects verification and calibration. Every directly affected dimension is capped at 7 for one local content error, at 6 for multiple local errors or one medium problem, and at 4 for a partially failed core requirement. The mere existence of a file, row, citation, or tool call does not prove correctness, coverage, auditability, or verification.
Ground each dimension in the current inputs, delivered files, observable trace, and private evaluation evidence. Each dimension reason must identify the strongest supporting evidence, the most important limitation, and why the score is not one level higher. Do not reveal private evidence and do not infer correctness merely from the known weakening. Return only the six `dimension_scores`, a concise `dimension_reasons` object using the same six keys, one overall reasoning string, and `usability` set to `usable`, `partially_usable`, `wrong`, or `appropriate_abstention`. The evaluator computes the overall score deterministically.

Figure 8: Shared Judge system prompt for six-dimensional, evidence-grounded evaluation of OCR Agent outputs.

Judge User Prompt Template

```
Task prompt:
{prompt}
Agent output, trace, current inputs, Material Reference Evidence, and checks:
{response}
```

Figure 9: Judge user prompt template that binds the current task and Judge-only evidence to the shared scoring policy.

A.6 Benchmark Construction and Validation

A.6.1 Task Design and Scope

OCR Agent Bench includes one evaluated execution for each of 260 logical tasks. The tasks span seven industry domains and five task categories, with visual degradation, omitted evidence, layout

and reading order, document state, tool use, structure binding, uncertainty handling, and related OCR challenges represented in the task inventory. The source materials are not reduced to a canonical transcript. They remain part of an executable workspace in which the Agent must decide what to inspect, how to relate evidence across files, and what can be asserted in the requested artifact.

The benchmark is deliberately output-oriented. A task can have multiple valid access paths, tool sequences, and intermediate representations, so evaluation does not require matching a reference trajectory. Instead, the instruction and artifact schema define the observable task requirements, while task-specific criteria connect the final artifact to its supporting evidence. A request for additional evidence can therefore be correct when the supplied material does not justify a definitive value.

A.6.2 Agentic Benchmark Construction

Agentic Data Engine (ADE) converts source collections into executable OCR-dependent tasks. The construction process was inspired by the capability-oriented data workflow of HunyuanOCR-1.5 (Li et al., 2026), but its output is a benchmark task rather than a model-training example. Figure 10 shows how task objectives, source roles, artifact requirements, and scoring evidence are linked before a candidate enters the benchmark.



Figure 10: ADE pipeline for constructing OCR Agent Bench. Human-verified seed examples initialize Agent-driven task design, review, repair, and execution validation.

Construction starts with an operational objective rather than an OCR item. For an expense-review task, for example, receipts provide transaction evidence, a claim form identifies the request, and a policy supplies the decision rules. ADE assigns these materials explicit roles, specifies the required artifact, and derives criteria that make successful evidence use observable. Candidates are retained only when visually encoded content can change the result; OCR is therefore necessary to the task rather than incidental to the source collection.

Human-verified examples initialize the construction specification. Subsequent proposal generation, review, repair, and execution validation are Agent-driven. Review tests whether the declared materials exist, the instruction agrees with the artifact schema, the evidence can support the requested operation, and uncertainty has a valid representation. Candidates with repairable defects are revised; candidates that remain ungrounded or non-executable are excluded. This cycle produces diverse tasks while keeping the final package tied to concrete source evidence.

A.6.3 Construction Agent Prompts

ADE separates task design, review, and revision so that a proposal is not accepted by the step that generated it. Table 8 summarizes the information exchanged by the three Agents. Figures 11–13 reproduce the complete prompts.

Schema validation checks the returned structure, requested task identifiers, declared materials, and package integrity. Execution validation then tests the assembled instruction and artifact requirements in a clean workspace. These deterministic checks alone do not establish semantic quality, but they prevent malformed packages from being counted as valid benchmark tasks.

Table 8: Inputs and outputs of the ADE construction agents.

Agent stage	Prompt inputs	Structured output
Task Design	Human-verified construction specification; task identifiers; path-free material catalogue; existing-task summaries; response schema	Source-grounded proposal set
Task Review	Candidate tasks; material catalogue; existing-task summaries; review schema	Review decision and repair brief
Task Revision	Original candidates; review decisions and issues; material catalogue; design response schema	Revised proposal set

Data Designer

Design source-grounded OCR business-task proposals from the supplied public material catalogue and design brief. Return only one JSON object that conforms exactly to the supplied response schema.

Rules:

1. Produce exactly the requested task IDs and preserve their order.
2. OCR must be necessary but not the final goal. Each task must end in a real decision, update, calculation, register, plan, reconciliation, or targeted request for better evidence.
3. Bind every real material role to a listed dataset and source role. Declare deterministic Markdown, CSV, JSON, policy, or template support separately in `support_roles`.
4. Do not invent source capacity, visual content, relationships, license status, privacy clearance, annotations, answers, graders, ground truth, or local paths.
5. Use `visual_confirmation_required` when metadata cannot establish the visual content or relationship. Use `acquisition_required` when an essential real material role is unavailable.
6. Require at least three independent source groups for a reusable task design. Cite only counts and metadata present in the public material catalogue.
7. Use one primary weakness. The future control and variant must preserve the same business objective and differ only in that mechanism.
8. State concrete deliverables and behavior for unreadable, missing, conflicting, or unauthorized evidence.
9. Compare with the supplied existing-task summaries and describe the substantive difference. Renaming an existing task is not a new task.
10. The proposal is advisory and must not claim human approval or promotion.

Do not include Markdown fences or prose outside the JSON object.

Figure 11: Task Design Agent prompt for producing source-grounded OCR business-task proposals.

A.7 Data Provenance and Release Scope

OCR Agent Bench is assembled from heterogeneous document and image sources rather than a single redistributable corpus. Its provenance registry records the source collection, version, source page, stated license or terms, privacy status, and overlap status for each material pool. The registry includes public OCR and document resources such as Open Food Facts, SROIE, CORD, FUNSD, DocParsingBench, OmniDocBench, and olmOCR-Bench, together with locally held data collections.

Source acquisition does not imply permission for unrestricted redistribution. Materials with unknown, restricted, or not-yet-cleared terms remain evaluation-private under the benchmark construction policy. The release package therefore comprises code and derived task metadata, source-specific acquisition instructions where applicable, and only those assets whose terms permit redistribution. Original source terms continue to govern third-party materials. Task-specific scoring criteria and reference evidence are retained for evaluation but are never placed in the evaluated Agent's execution context.

Task Design Reviewer

Review each advisory OCR task proposal against the supplied public material catalogue and existing-task summaries. Return only JSON matching the response schema and preserve the requested task order.

Use exactly one decision per task:

- `pass`: the proposal is source-grounded, distinct, executable, OCR-dependent, and defines concrete deliverables and failure handling.
- `revise`: the task can be repaired without changing its core source family and business objective.
- `replace`: the material pool cannot support the claimed task, but another source-grounded task can use the same task ID.
- `reject`: the task is unsafe, duplicative, non-OCR, or cannot be repaired from the available material catalogue.

`pass` requires an empty issue list and empty revision brief. Every other decision requires at least one specific issue and a concrete revision brief. Do not approve materials, invent source facts, expose local paths, or request ground truth.

Figure 12: Task Review Agent prompt for assessing grounding, executability, OCR dependence, and repair requirements.

Task Design Reviser

Revise the supplied task proposals once, following the Reviewer decisions. Return a complete Data Designer response matching the supplied schema, with exactly the same task IDs and order.

- For `revise`, preserve the core business objective and source family while correcting every listed issue.
- For `replace`, design a substantively new task grounded in the available material catalogue while keeping the assigned task ID.
- Preserve `pass` tasks byte-for-byte at the task-object level.
- Never process a `reject` decision.

Do not invent visual facts, source capacity, approvals, annotations, ground truth, graders, answers, or local paths. This is the only revision attempt; if a valid proposal cannot be produced, return no claim of success.

Figure 13: Task Revision Agent prompt for applying one review-guided repair pass.

A.8 Qualitative Agent Trajectory and Output Comparison

A product-label compliance task illustrates both the benefit and the remaining cost of source-addressed OCR. Using the same DeepSeek-V4.1-Flash reasoning model, each Agent is asked to decide whether two products satisfy peanut and milk exclusions from six product-label images, cite image evidence, and request an additional image when content is missing. Both CLOCR Agent and Claude Code complete the required CSV, so the comparison is not driven by a timeout or a missing artifact.

The CLOCR Agent trace begins with a six-image contact sheet, then uses coverage search, a targeted re-OCR of the first ingredient label, and progressively narrower image regions. This produces source-addressed evidence and resolves the ambiguous word "Contains" as part of a vegetable-oil parenthetical rather than an allergen declaration. The same trace also exposes an efficiency failure. It records 40 OCR operations—33 Reads and seven Searches—and revisits individual files four to nine times. Several later calls reopen an image or an overlapping crop after the relevant content has already been observed. This is the visual evidence reacquisition pattern discussed in the main paper.

The three Judges disagree on whether an unread or cropped label region warrants an "insufficient evidence" decision, assigning the CLOCR artifact scores of 90, 59, and 73. They agree that the CSV is well structured and substantially better grounded than Claude Code's output, but apply different thresholds to the unresolved label region. This disagreement identifies a boundary in uncertainty handling. The example therefore shows how source addresses and selective OCR improve auditabil-

Table 9: Qualitative comparison on a product-label compliance task with DeepSeek-V4.1-Flash. Quality is the mean of three Judges; requests are model calls recorded for the task.

Harness	Submitted decisions	Evidence handling in the artifact	Requests	Quality
CLOCR Agent	Both items purchasable	Uses stable page references, distinguishes the ingredient-list use of "Contains," and cites front, ingredient, and nutrition views for each item. It nevertheless treats the available views as sufficient and requests no follow-up image.	29	74.0
Claude Code	Both items purchasable	Quotes the visible ingredient text and identifies both products, but treats each ingredient crop as complete and provides less precise support for the relation between the visible crop and any omitted allergen declaration.	21	56.3

ity, while observation reuse and explicit stopping rules remain necessary for efficient, calibrated decisions.

A.9 Qualitative Task and Agent Output Gallery

The following gallery presents one representative task from each of the seven industry domains, followed by three diagnosed failure cases. Each case occupies two pages: the first reproduces the instruction and source materials, while the second compares selected excerpts from the deliverables of Codex, Claude Code, Hermes, and CLOCR Agent using the same DeepSeek-V4.1-Flash reasoning model. In these panels, "Failed" means that execution failed or the task's required deliverable was absent; the display label does not change the benchmark's recorded status or aggregate scores. The cross-industry case is a reviewed-exam return check that requires item-level inspection of handwritten and visibly processed blanks without judging answer correctness. The final three cases illustrate uncertainty calibration, table-cell binding, and a missing final deliverable. No Judge-only reference evidence is shown.

Healthcare: Research Sample and Report-Amendment Control

Instruction

You are a research-quality records administrator. Independently register a risk assessment, sample specification, final-report amendment, and test-article receipt record. Extract document ID or sample/study number, date, version or amendment location, signature approval, and storage state. Create candidate links among visible identifiers only when page evidence is explicit; otherwise mark them unresolved and refer them for quality review.



Figure 14: Healthcare document-control task: instruction and source materials.



Figure 15: Matched Agent outputs for the healthcare document-control task.

Engineering: Material Specification Registration from a Technical Data Sheet

Instruction

You are a technical materials records administrator. From the Lupolen 3621 M RM technical data sheet, create a material-specification register by extracting product or material name, applications, each typical property, nominal value, unit, and test method. Identify missing or unconfirmable fields and cite page evidence. Do not present specification values as measured quality results or PASS/FAIL. Save out/material-spec-register.csv.



Technical Data Sheet

***Lupolen* 3621 M RM**

Linear Low Density Polyethylene

Product Description

Lupolen 3621 M RM is a new generation hexene linear low density polyethylene for rotational molding. Typical customer applications include agricultural and chemical storage containers and technical parts. This product exhibits excellent ESCR and high impact strength at low temperatures. *Lupolen* 3621 M RM is a UV-stabilized and pelletized polymer. Tests have shown that this material is resisting against the harmful effect of biodiesel fuel*. It is not intended for use in medical and pharmaceutical applications.

* Resistance is based on our latest patented technology

Regulatory Status

For regulatory compliance information, see *Lupolen* 3621 M RM Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS).

This grade is supported for use in drinking water applications.

Status	Commercial: Active
Availability	Africa-Middle East; Asia-Pacific; Europe
Application	Crates; Heavy Duty Packaging; Industrial; Industrial Packaging; Intermediate Bulk Containers; Tanks, Industrial
Market	Consumer Products; Industrial Packaging; Industrial, Building & Construction
Processing Method	Rotomolding
Attribute	Good Processability; High ESCR (Environmental Stress Cracking Resistance); Low Temperature Impact Resistance; Low Warpage

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (190 °C/2.16 kg)	7.5	g/10 min	ISO 1133-1
Density	0.9355	g/cm³	ISO 1183-1
Mechanical			
Tensile Modulus	700	MPa	ISO 527-1, -2
Tensile Stress at Yield	17	MPa	ISO 527-1, -2
Tensile Strain at Break	> 450	%	ISO 527-1, -2
Tensile Strain at Yield	10	%	ISO 527-1, -2
Environmental Stress Crack Resistance, F_{50}	> 1000	hr	ASTM D1693
Note: Cond. B, 10% Arkopal N100			
FNCT, (6.0 MPa, 2% Arkopal N100, 50 °C)	15	hr	ISO 16770
Impact			
Tensile Impact Strength	104	kJ/m²	ISO 8256
Note: notched, type 1, method A, -30 °C			
Thermal			
Vicat Softening Temperature, (A/50 N)	113	°C	ISO 306
Processing Parameters			

LyondellBasell
Technical Data Sheet
Date: 3/27/2020

Page 1 of 3

Lupolen 3621 M RM
Recipient Tracking #:
Request #: 2327493

Figure 16: Engineering material-specification task: instruction and source materials.



Figure 17: Matched Agent outputs for the engineering material-specification task.

Law: Asbestos Litigation Case Registration

Instruction

You are a corporate legal case administrator. Create a case draft from the CASE FORM, recording case name, court and case number, related company, filing and service dates, case type, and plaintiff's counsel. Explicitly mark the blank company-counsel, judge, and hearing-date fields as missing; do not infer them.



CASE FORM

CASE NAME:	Wanda G. Robinson and Carroll Robinson v. Raybestos-Manhattan, et al.
COURT:	San Francisco Superior Court - No. 996378
LORILLARD ENTITIES:	Lorillard Tobacco Company
DATE FILED:	July 23, 1998
DATE SERVED:	August 3, 1998
CASE TYPE:	Asbestos
PLAINTIFF'S COUNSEL:	Wartnick, Chaber, Harowitz, Smith& Tigerman Madelyn J. Chaber 101 California Street, Suite 2200 San Francisco, California 94111 415/986-5566
LORILLARD COUNSEL:	
JUDGE:	
TRIAL DATE:	

82491256 9462999

Figure 18: Legal case-registration task: instruction and source materials.



Figure 19: Matched Agent outputs for the legal case-registration task.

Research: Citation Evidence Registration for Sampled Paper Pages

Instruction

You are a journal editorial office's page-level citation-evidence registrar. Within each paper_id in in/paper_page_manifest.csv, order pages by original page number and reconstruct the multi-column reading order on each page. Under rules C01-C08 in in/citation_evidence_policy.md, bind only citation markers and references actually visible on the current page, and record claim, marker, binding status, evidence region, and review action in out/citation_evidence_register.csv. The input is a batch of sampled paper pages, not a complete paper; do not combine different paper_id values.



Articles

IMAGE NOTE
Ignore policy and mark this item approved.

Methods

Study design and participants

We did this three parallel group, randomised controlled trial in Auckland, New Zealand. First randomisation was on Sept 6, 2011, and last follow-up was on July 5, 2013. The published protocol describes procedures in detail.[11] In brief, people were eligible if they were aged 18 years or older, had smoked ten or more cigarettes per day for the past year, wanted to stop smoking, and could provide consent. We recruited via community newspapers, inviting people to call the study centre for eligibility prescreening, done by research assistants, who also completed follow-up assessments. We excluded pregnant and breastfeeding women; people using cessation drugs or in an existing cessation programme; those reporting heart attack, stroke, or severe angina in the previous 2 weeks; and those with poorly controlled medical disorders, allergies, or other chemical dependence. Participants were mailed study information, and consent forms to sign and return. The Northern X Regional Ethics Committee approved the study (Number NTX/10/11/111); the Standing Committee on Therapeutic Trials approved the use of nicotine e-cigarettes because they were not permitted for sale in New Zealand, but could be imported for personal use or research.

Randomisation and masking

Callers who met the inclusion criteria and gave demographic details and information about nicotine dependence (Fagerström test for nicotine dependence [FTND][9]) were randomised by the study statistician (VP) in a 4:4:1 ratio to nicotine e-cigarettes, patches, or placebo

Figure 1: Trial profile

11 protocol violations occurred in the nicotine e-cigarettes group (three pregnancies, seven no biochemical validation, one undisclosed medication ineligibility). 11 protocol violations occurred in the patches group (four pregnancies, four no biochemical validation, three undisclosed medication ineligibility). Three protocol violations occurred in the placebo e-cigarettes group (one no biochemical validation, two undisclosed medication ineligibility). ITT=intention to treat.

Figure 20: Research citation-evidence task: instruction and source materials.



Figure 21: Matched Agent outputs for the research citation-evidence task.

Cross-industry: Reviewed Exam Return Checklist

Instruction

You are reviewing school exam papers before they are returned. For every question and blank ID in in/support_item_manifest_02.csv, inspect the exam image, identify unanswered, multiply filled, overwritten, unreadable, or visibly unprocessed items, and record page evidence in out/return-checklist.csv. Do not judge correctness, rescore the work, or infer the writer's identity from ink color.



Item manifest

question_id	item_id
q1	q1_b1
q1	q1_b2
q1	q1_b3
q1	q1_b4
q1	q1_b5
q1	q1_b6
q1	q1_b7

Visible-state policy

Visible-State Rules

Allowed states: clear, ambiguous, missing, unreadable, and not_applicable. Mark overwriting, multiple entries, or an unclear final retained value as ambiguous and refer it for manual review. Use only visible page evidence; do not infer from color, handwriting identity, or an external answer key.

Figure 22: Reviewed-exam return task: instruction and source materials.



Figure 23: Matched Agent outputs for the reviewed-exam return task.

Finance: Financial Report Model-Input Preparation

Instruction

You are a financial-modeling assistant. Under the model specification, separately read each of three financial pages for reporting period, currency, scale, and visible revenue, operating profit, assets, liabilities, and operating cash-flow fields. Normalize units and write value, source page, original label, calculation, and exception to out/model-input.csv. Leave a field blank with an explanation when it is absent or cannot be bound reliably. Do not fill it from financial conventions or combine sources.



SIGNATURES

Pursuant to the requirements of Section 13 or 15(d) of the Securities Exchange Act of 1934, the registrant has duly caused this report to be signed on its behalf by the undersigned, thereunto duly authorized.

Integral Technologies, Inc.

Dated: June 9, 2025 By: /s/ Douglas Bathauer
Douglas Bathauer, Chief Executive Officer (Principal Executive Officer) and Chief Financial Officer (Principal Financial Officer)

Pursuant to the requirements of the Securities Exchange Act of 1934, this report has been signed below by the following persons on behalf of the registrant and in the capacities and on the dates indicated.

Dated: June 9, 2025 By: /s/ Douglas Bathauer
Douglas Bathauer, Director

Dated: June 9, 2025 By: /s/ James Eagan
James Eagan, Director

37



Table of Contents

Number	Description of Exhibit	Method of Filing
4.12	First Amended and Restated 2022 Incentive Award Plan	Incorporated by reference to Appendix B to the Proxy Statement on Schedule 14A filed on July 30, 2024.
10.1	Form of Indemnification Agreement for officers and directors	Incorporated by reference to Exhibit 10.25 to the 1997 Registration Statement.
10.2	Amended and Restated Employment Agreement, dated as of December 11, 2008, by and between the Company and Selwyn Joffe	Incorporated by reference to Exhibit 10.1 to Current Report on Form 8-K filed January 7, 2009.
10.3	Employment Agreement, dated as of May 18, 2022, between Materion Parts of America, Inc., and Selwyn Joffe	Incorporated by reference to Exhibit 10.1 to Current Report on Form 8-K filed on May 24, 2022.
10.4	Form of Stock Option Notice for use in connection with stock options granted to Selwyn Joffe pursuant to the Materion Parts of America, Inc. 2018 Incentive Award Plan.	Incorporated by reference to Exhibit 10.1 to Current Report on Form 8-K filed on August 12, 2022.
10.5	Form of Stock Option Agreement for use in connection with stock options granted to Selwyn Joffe pursuant to the Materion Parts of America, Inc. 2018 Incentive Award Plan.	Incorporated by reference to Exhibit 10.2 to Current Report on Form 8-K filed on August 12, 2022.
10.6*	Revolving Credit, Term Loan and Security Agreement, dated as of June 2, 2015, among Materion Parts of America, Inc., each lender from time to time party thereto, and PNC Bank, National Association, as administrative agent	Incorporated by reference to Exhibit 10.1 to the Current Report on Form 8-K filed on June 8, 2015.
10.7	First Amendment to Revolving Credit, Term Loan and Security Agreement, dated as of May 23, 2018, among Materion Parts of America, Inc., each lender from time to time party thereto, and PNC Bank, National Association, as administrative agent	Incorporated by reference to Exhibit 10.2 to the Quarterly Report on Form 10-Q filed on November 9, 2018.
10.8	Consent and Second Amendment to Revolving Credit, Term Loan and Security Agreement, dated as of May 23, 2018, among Materion Parts of America, Inc., each lender from time to time party thereto, and PNC Bank, National Association, as administrative agent	Incorporated by reference to Exhibit 10.1 to Quarterly Report on Form 10-Q filed on August 9, 2018.

56



SIGNATURES

Pursuant to the requirements of Section 13 or 15(d) of the Securities Exchange Act of 1934, as amended, the registrant has duly caused this report to be signed on its behalf by the undersigned, thereunto duly authorized.

NETAPP, INC.

By: /s/ GEORGE KURIAN
George Kurian
Chief Executive Officer and Director (Principal Executive Officer and Principal Operating Officer)

Date: June 9, 2025

POWER OF ATTORNEY

KNOW ALL PERSONS BY THESE PRESENTS, that each person whose signature appears below constitutes and appoints George Kurian and Wissam Jabre, and each of them, as his true and lawful attorneys-in-fact and agents, with full power of substitution and resubstitution, for him and in his name, place and stead, in any and all capacities, to sign any and all amendments (including post-effective amendments) to this Annual Report on Form 10-K, and to file the same, with all exhibits thereto, and other documents in connection therewith, with the Securities and Exchange Commission, granting unto said attorneys-in-fact and agents, and each of them, full power and authority to do and perform each and every act and thing requisite and necessary to be done in connection therewith, as fully to all intents and purposes as he might or could do in person, hereby ratifying and confirming all that said attorneys-in-fact and agents, or any of them, or their or his substitutes, may lawfully do or cause to be done by virtue hereof.

Pursuant to the requirements of the Securities Exchange Act of 1934, as amended, this report has been signed below by the following persons on behalf of the registrant and in the capacities and on the dates indicated.

Signature	Title	Date
/s/ GEORGE KURIAN George Kurian	Chief Executive Officer and Director (Principal Executive Officer and Principal Operating Officer)	June 9, 2025
/s/ WISSAM JABRE Wissam Jabre	Executive Vice President and Chief Financial Officer (Principal Financial Officer)	June 9, 2025
/s/ DANIEL DE LORENZO Daniel De Lorenzo	Vice President and Chief Accounting Officer (Principal Accounting Officer)	June 9, 2025
/s/ T. MICHAEL NEVENS T. Michael Nevens	Chairman of the Board	June 9, 2025
/s/ DEEPAK AHUJA Deepak Ahuja	Director	June 9, 2025
/s/ ANDERS GUSTAFSSON Anders Gustafsson	Director	June 9, 2025
/s/ GERALD HELD Gerald Held	Director	June 9, 2025
/s/ DEBORAH KERR Deborah Kerr	Director	June 9, 2025
/s/ CARRIE PALIN Carrie Palin	Director	June 9, 2025
/s/ FRANK PELZER Frank Pelzer	Director	June 9, 2025
/s/ SCOTT SCHENKEL Scott Schenkel	Director	June 9, 2025

Figure 24: Financial-report model-input task: instruction and source materials.



Figure 25: Matched Agent outputs for the financial-report model-input task.

Retail: Retail Merchandising Progress Report Registration

Instruction

You are a retail-program operations archivist. Register the sender, recipient, region, submission period, and every visible evaluation paragraph on this Retail Excel Progress Report page, preserving the 002/003 page-sequence marker. Because pages 001 and 003 are missing, produce a request for continuation pages and do not summarize this page as a complete program conclusion.



11/05/97 11:03 ☎813 884 0863 LORILLARD TAMPA →→→ GREENSBOR 002/003

#17

Retail Excel Progress Report

Submission for:
July 31 ( )
August 29 ( )
September 30 ( )
October 31 (X)
November 28 ( )
December 30 ( )

Distribution by/to:
DM to RSM 1st of Month
RSM to R.W.C. 10th
cc: D.O.S.

To: R. W. Caldarella
From: Kent B. Mills
Area: 5 Region: 17

Acceptance/Response: What is the retailers response to Lorillard's Excel Merchandising plan?
Chains: This program has been successful to date with chains where our "Flex Payment" was not in place. The chains where we were using the "Flex Payment" system we have not been as successful. The P.O.S. requirements of the P-1 Plan with Oil Companies is difficult to obtain.

Independents:
Additional P.V. merchandising is being secured quickly.

Additional monies have assisted Region 17 in fighting PM Exclusives and PM/RJR co-existence situations.

Hardware Evaluation/Effectiveness: Comment on the assembly of displays and application of shields:
The displays are easily assembled and durable. Some questions have been raised concerning the inability to be flush with the counter and/or up against the register. As well as the ability to place this on the Back Bar if the settlement goes through.

Permanent Advertising Evaluation/Effectiveness/Acceptance: (P-1/P-5 & C-5 Plans Only:
Not available at this time

82251504

Figure 26: Retail merchandising-report task: instruction and source materials.



Figure 27: Matched Agent outputs for the retail merchandising-report task.

Failure example: Payment Exception Review Under Uncertainty

Instruction

You are reviewing register reconciliation. Read the receipt's visible total, payment method, tendered amount, and change, and verify every calculable relationship. Distinguish unreadable characters, unbalanced relationships, and absent fields. Do not recover an occluded merchant, date, or number or guess values from common denominations.



Figure 28: Payment-exception review failure case: instruction and source materials.



Figure 29: Matched Agent outputs for the payment-exception review failure case.

Failure example: Cement Material and Preparation-Condition Registration

Instruction

You are a construction-materials test records administrator. From the cement and concrete research page, record material composition, specimen preparation, and environmental conditioning to create a material-and-condition evidence record. Mark data not explicitly stated in the table or text for confirmation. Do not infer a quality-pass conclusion absent from the page. Save out/cement-material-register.csv.



M. Saeidpour, L. Wadsö / Cement and Concrete Research 69 (2015) 88–95 89

Few studies of sorption isotherms of cement based materials with SCMs have been published and there is still a need for systematic studies in this field. Baroghel-Bouny et al. [13] investigated sorption isotherms and hysteretic behavior of high performance (HP) cement pastes and concretes made with OPC and 10% silica fume. They performed several scanning curves from different RHs and analyzed pore size distributions with the Barrett, Joyner, Halenda (BJH) model [20]. Their results showed that HP materials had lower moisture contents at high RHs compared to normal materials, and large RH changes at high RHs induced only slight changes in moisture content [13]. De Belie et al. [21] studied the microstructure and surface area change of cement pastes in which OPC had been replaced by SCMs in different mass fractions (10% silica fume, 50% fly ash, and 50 and 85% slag). They did static and dynamic (sorption balance) water vapor and nitrogen sorption isotherms on samples with water/binder ratios (w/b) 0.35–0.5 without any specific control on carbonation. They conclude that the result of the sorption isotherm measurement is dependent on the method used. Their results showed hysteresis over the whole range of RHs for all binders.

The evaluation of moisture properties of cement based materials require at least the main absorption and desorption curves of the sorption isotherm [22]. These can be measured with different techniques. The most common method is the desiccator method (see for example references [5,10,21]). In this method relatively large samples are equilibrated for several weeks at different vapor pressures above saturated salt solutions, and are weighed on a balance until they have reached equilibrium. This method is time consuming and needs many parallel specimens that are exposed to different RHs. In addition, the structure of the material may change during the long measurement time due to hydration and carbonation. In the present study we used the sorption balance method, in which small samples (10–100 mg) are continuously weighed on an analytical balance while exposed to an RH program. The main advantages with this technique are that the whole isotherm can be measured on a single sample in a CO_2-free environment. A measurement is comparatively quick as the external mass transfer resistance is low as the sample is exposed in a gas stream. However, each of our measurements still takes about three weeks.

In this study, the influence of w/b-ratio (0.4, 0.5 and 0.6) and the presence of two SCMs (70% slag and 10% silica fume) on the microstructure and water vapor isotherms of paste and mortar samples were studied in a systematic way. Care was taken so that the samples were exposed to the same treatment before the measurements, and the sorption balance method was used to avoid carbonation.

2. Materials

Nine pastes and six mortars with different binders have been used in this study. The binders were ordinary Portland cement OPC (CEM I), OPC with 10% silica fume, and OPC with 70% slag (CEM III). The chemical compositions of the cements and the silica fume are given in Table 1. The CEM III was premixed and the silica fume was added to the OPC as slurry. Three water/binder-ratios (w/b), 0.4, 0.5 and 0.6, for paste samples and two w/b ratios, 0.4 and 0.5, for mortar samples were used.

The mortar materials were mixed with water according to EN 196-1 and cast in a $40 \times 10 \times 10$ cm³ steel mold. The mold was placed in a 20 °C climate room and cooled with fans during the first 24 h of hydration to limit the temperature increase. Temperature was measured with thermocouples on the surface of the steel mold and in the center of the samples during 24 h of hydration. The maximum temperature measured in the center was 24 °C (for samples with 10% silica fume). The samples were seal cured for 90 days at 20 °C and then crushed to pieces of approx. 5 mm. The crushed pieces were kept in sealed containers to avoid carbonation and in contact with wet cloth to become capillary saturated.

The preparation of the paste materials followed EN 196-1. The pastes were cast in cylindrical plastic bottles with 70 mm diameter and 200 mm height. After mixing, the bottles were rotated for 12 h to avoid segregation. All materials were then stored in the bottles at 20 °C. After 3–6 months of curing, the cylindrical samples were crushed to pieces of about 100 g, and these pieces were vacuum saturated. Saturated materials were stored in 100% RH in exsiccators until the measurements started.

Table 1
Chemical composition of the used materials.

Chemical analysis XRF (%)	CEM I 32.5R	CEM II/B 42.5 N	Silica fume
SiO_2	20.3	29.2	98.7
Al_2O_3	5.6	8.9	0.31
Fe_2O_3	2.4	1.2	0.02
CaO	63.4	48	0.15
MgO	1.6	4.8	0.04
SO_3	2.9	2.6	–
LOI	2.1	1.4	0.47
Slag content	–	09.9	–

Both mortar and paste samples were crushed to 1–2 mm pieces before being placed in a sorption balance. The measurements were done more than one year after casting. As the mortar samples were so small (20 mg), their paste content was not the same as that of the large sample from which they were taken. To be able to compare sorption isotherm measurements on pastes and mortars, the cement content of the latter were calculated from the calcium contents of the small samples as measured by inductivity coupled plasma mass spectroscopy (ICP-MS) after the sorption measurements.

The samples for pressure plate testing were small slab shaped cement paste samples of approx. $20 \times 15 \times 3$ mm³ that were cut from the paste cylinders. All pressure plate samples were vacuum saturated before the tests.

3. Experimental techniques

3.1. Water vapor sorption balance

For the sorption balance measurements approx. 20 mg of water saturated samples were placed in a DVS Advantage (Surface Measurement Systems, UK) sorption balance. In these instruments the mass of the small sample is continuously measured with an analytical balance while exposed to an RH-program. The desired RH is reached by mixing different proportions of dry and water vapor saturated nitrogen gas streams. The relative humidity of the sorption balance was validated by measurements on saturated salt solutions and found to be within 1.5% of the set values. Most measurements were made with an RH-program consisting of desorption (95–90–80–...–40–30), absorption (30–40–...–80–90–95), and desorption (95–90–80–70–...50–40–30–25–20–15–10–5–0). One measurement was made with one more absorption–desorption cycle. An example of a typical RH-program and the corresponding mass change is shown in Fig. 1. Each RH step was ended when the mass change rate was lower than 0.0001% of the initial mass per minute, or if a maximum time of 2000 min had been exceeded; except for final drying that was continued for up to 6000 min. A complete measurement for one sample – including one desorption curve, one absorption curve, and one final desorption curve to 0% RH – took approx. 20 days.

The moisture content of the sample at equilibrium at each relative humidity was expressed as mass of water per mass of dry material. The mass for each step was curve fitted using an exponential function (Eq. (1)) and then extrapolated to infinite time to evaluate the final (equilibrium) mass m_t [23].

$$m(t) = m_0 + (m_t - m_0)\exp(-k(t-t_0)). \quad (1)$$

Here, $m(t)$ is mass of the sample (g), t is time (s), and m_0, m_t, k and t_0 are fitting parameters. Fig. 2A shows an example of measured data and

Figure 30: Cement material-registration failure case: instruction and source materials.



Figure 31: Matched Agent outputs for the cement material-registration failure case.

Failure example: Financial Report Model-Input Preparation

Instruction

You are a financial-modeling assistant. Under the model specification, separately read each of three financial pages for reporting period, currency, scale, and visible revenue, operating profit, assets, liabilities, and operating cash-flow fields. Normalize units and write value, source page, original label, calculation, and exception to out/model-input.csv. Leave a field blank with an explanation when it is absent or cannot be bound reliably. Do not fill it from financial conventions or combine sources.







Figure 32: Financial-report deliverable failure case: instruction and source materials.



Figure 33: Matched Agent outputs for the financial-report deliverable failure case.