COMPLIANCE IS NOT DISCERNMENT: DIAGNOSING SELECTIVE ADVICE USE IN LLMS UNDER SOCIAL FRAMING

Anonymous authors
Paper under double-blind review

ABSTRACT

Effective human–AI and multi-agent collaboration depends on LLMs adopting valid advice while resisting invalid advice. Aggregate following rates cannot distinguish willingness to follow from selectivity for valid advice. We introduce a SuperGPQA-based diagnostic framework to examine selective advice use and test whether cue combinations have effects beyond individual cues. The benchmark pairs valid and invalid advice on stable baseline-wrong model–question pairs in separate calls and tracks harmful regression on baseline-correct pairs. A factorial design crosses source, role, and wording while holding advice content fixed. A probit signal detection model separates the adoption criterion (willingness to follow) from behavioral validity discrimination (selectivity for valid advice). Across eight LLMs, mandatory wording mainly lowered the adoption criterion; supervisor labels amplified this shift beyond additive effects and narrowed validity discrimination under the equal-variance model. Interventions mainly shifted the adoption criterion. Empowered-persona prompting reduced invalid following at the cost of beneficial corrections, whereas native reasoning had framing-dependent effects and sometimes increased harmful regression under mandatory human-source advice. Evaluations of collaborative LLMs should therefore test cue combinations and distinguish selective adoption from general compliance.

1 INTRODUCTION

Large language models (LLMs) increasingly exchange proposed solutions, critiques, and feedback in human–AI teams and multi-agent workflows (Wu et al., 2024; Hong et al., 2024). Such collaboration depends on using feedback to correct errors without introducing new ones. Whether following advice helps or harms depends on both its validity and the model's unaided answer. Valid advice can turn a wrong answer into a correct one (beneficial correction). Invalid advice can replace one wrong answer with another (same-state invalid following), or turn a correct answer into a wrong one (harmful regression; Fig. 1). Accuracy captures wrong-to-correct and correct-to-wrong changes, but misses invalid following when both answers are wrong. Evaluating advice use therefore requires distinguishing which advice models follow from how readily they follow it.

These outcomes unfold in collaborative interactions where advice carries social cues. Recent studies show that source attribution can affect trust and conformity (Sun et al., 2026; Bajaj & Tiganj, 2026), authority appeals can increase compliance (Meincke et al., 2026), and instruction intensity can alter responses (Hong et al., 2026). We vary source identity (human or AI), role label (supervisor or peer), and wording (mandatory or optional), holding the recommended answer fixed (Fig. 1). Beyond whether these cues change how often LLMs follow advice, we ask whether they change general willingness to adopt advice, selectivity for valid advice, or both. Aggregate following rates cannot distinguish these possibilities. We also test whether these cues interact in shaping the two aspects of adoption. Prior evaluations distinguish beneficial correction from harmful regression (Weng et al., 2025; Qu et al., 2026), but these outcomes originate from incorrect and correct baseline answers, respectively. Their comparison therefore confounds advice validity with baseline correctness. Comparing valid and invalid adoption within a common baseline state can reveal which aspect of advice use changes across social-cue conditions.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **Three outcomes of advice adoption.** Source, role, and wording are social cues in collaboration. We cross them in a $2 \times 2 \times 2$ design with advice content fixed. Human avatars are illustrative. Examples distinguish beneficial correction (A), same-state invalid following on baseline-wrong pairs (I_{W}), and harmful regression on baseline-correct pairs (I_{C}). Wrong-to-wrong adoption changes the answer without changing correctness. Baselines require three identical no-advice answers; responses with advice come from separate calls.

To make this distinction explicit, we draw on signal detection theory (SDT), treating advice validity as the known experimental state and adoption as the binary response. SDT separates adoption criterion (readiness to follow advice) from validity discrimination (selectivity for valid over invalid advice) (Green & Swets, 1966; Macmillan & Creelman, 2005). Our probit generalized linear mixed model (GLMM) expresses these behavioral quantities as coefficient contrasts under an equal-variance working assumption (DeCarlo, 1998). It adjusts for phrase-template variation and accounts for repeated responses and item heterogeneity. We also use these measures for an exploratory analysis of associations with unaided task accuracy.

Our benchmark pairs valid and invalid advice on the same stable baseline-wrong model–question pairs. A complementary baseline-correct condition measures harmful regression. We use SuperGPQA questions (M-A-P et al., 2025) to test eight LLMs from several model families, including GPT-5.5 and Qwen3.7-Max. Within each advice condition, a $2 \times 2 \times 2$ full factorial design crosses the three social cues to estimate their individual and interactive effects. Prompting independent judgment and enabling additional reasoning offer two candidate routes to mitigating conformity. We therefore evaluate empowered-persona prompting and native reasoning in three of these models, building on conformity-mitigation work (Weng et al., 2025; Zhu et al., 2025). These experiments test whether reduced invalid following comes at the cost of beneficial correction, and whether improved benefit–harm separation is accompanied by greater same-state discrimination.

Contributions.

- **A diagnostic framework for selective advice use.** Our matched three-condition benchmark captures wrong-to-wrong following missed by accuracy and separates adoption criterion from behavioral validity discrimination using an SDT-guided probit mixed model.
- **An interaction-aware account of compounding social vulnerability.** Our pooled analysis identifies a nonadditive interaction between directive wording and supervisor labels that increases compliance while weakening behavioral selectivity. This exposes a risk in role-framed collaboration that isolated-cue evaluations would miss.
- **Reframing conformity mitigation as a selectivity trade-off.** We show that conformity mitigation can alter the adoption criterion without sharpening selectivity. Persona prompting reduces invalid following at the cost of beneficial corrections, while native reasoning yields no consistent gain in same-state validity discrimination.

2 Related Work

2.1 Social Framing and LLM Conformity

LLMs are sensitive to the social context surrounding advice. They exhibit sycophancy toward user beliefs and conform to peer or majority answers (Sharma et al., 2024; Zhu et al., 2025; Weng et al., 2025). In multi-agent settings, answer revision also depends on group composition and interaction protocol (Choi et al., 2025; Song et al., 2026). Knowledge-conflict research examines a related tension between parametric memory and external evidence. Xie et al. (2024) find that coherent counter-evidence can displace prior answers, while models favor memory-consistent evidence when supportive and conflicting passages coexist. These findings motivate separating the effects of advice content from the social cues surrounding advice.

Source and role labels offer one way to isolate social influence from advice content. Models conform more readily to answers attributed to human experts than to other LLMs (Bajaj & Tiganj, 2026). In content-controlled trust evaluations, both human and LLM judges rate human-labeled information above identical AI-labeled information (Sun et al., 2026). More broadly, authority appeals can increase compliance with objectionable requests (Meincke et al., 2026). Directive wording is another potential source of pressure. Hong et al. (2026) vary instruction intensity with fixed visual inputs and tasks, finding non-monotonic changes in hallucination rates in vision-language models. These distinct paradigms leave open how source identity, role, and wording combine in advice adoption. We address this question by crossing source label, role label, and wording while holding advice content fixed, estimating their individual and interactive effects.

2.2 Evaluating Selective Advice Use

Evaluating selective advice use requires both acceptance of valid advice and resistance to invalid advice (Schemmer et al., 2023). Stengel-Eskin et al. (2025) use persuasion-balanced training to teach models to accept beneficial persuasion and resist harmful persuasion, showing that optimizing only one direction impairs the other. Their evaluation addresses the same benefit–harm distinction captured here by beneficial correction and harmful regression. Recent work also characterizes a resistance–receptivity frontier for conformity mitigations (Hussain & Nielbo, 2026). BENCHFORM tests correct and incorrect guidance (Weng et al., 2025), while Qu et al. (2026) jointly examine beneficial and harmful revisions under consensus and authority cues. Comparing beneficial correction with harmful regression changes both advice validity and baseline correctness. These outcomes quantify benefits and harms on distinct item pools, leaving validity discrimination within a common baseline state unresolved.

SDT and its generalized linear modeling formulation provide established tools for separating discrimination from criterion (Green & Swets, 1966; Macmillan & Creelman, 2005; DeCarlo, 1998). LLM applications include factual judgments (Cacioli, 2026b) and essay scoring (Zhou, 2026); related metacognitive work studies confidence and decision policies (Cacioli, 2026a; Servajean & Servajean, 2026; Ackerman, 2026).

3 Evaluation Framework and Methods

3.1 Experimental Protocol

We compare valid and invalid advice on the same initially wrong model–question pairs to separate selective correction from general advice following. SuperGPQA's challenging, cross-disciplinary graduate-level questions provide this test (M-A-P et al., 2025). Its ten-option format limits accidental selection of a prespecified distractor. We randomly sampled 650 ten-option multiple-choice questions, with 50 from each of 13 broad domains. The sample contained 282 easy, 300 medium, and 68 hard questions.

We evaluated eight LLMs with thinking disabled. The models were Qwen3.7-Max, GLM-5.2, DeepSeek-V4-Pro, Gemini-2.5-Flash, Llama-3.1-8B-Instruct, Llama-4-Maverick, Mistral-Small-3.2-24B-Instruct, and GPT-5.5. All calls used temperature zero. Because hosted model calls can remain non-deterministic at this setting (Ouyang et al., 2025; Atıl et al., 2025), we estimated the

baseline state from three separate no-advice API calls, each with a fresh conversation context and no prior messages or responses. Advice trials also used fresh calls, presenting the question and advice without the model's baseline response.

The three-condition analysis retained model–question pairs with identical responses across all three no-advice calls. Of 5,200 pairs, 4,232 met this criterion (81.38%). Their common answer defined the baseline state and determined the applicable trial types. Stable baseline-wrong pairs received both valid and invalid advice, whereas stable baseline-correct pairs received invalid advice. The procedure yielded 2,159 baseline-wrong and 2,073 baseline-correct pairs.

Valid advice recommended the benchmark gold answer. Invalid advice recommended a prespecified distractor. On baseline-wrong pairs, the distractor differed from the stable baseline response, distinguishing adoption from repetition of the original error. If the primary distractor matched that response, the next distractor in the prespecified order was used. We coded selection of the recommended option as adoption. Selection of the baseline answer or another distractor was coded as non-adoption.

Each of the three trial types was crossed with a $2 \times 2 \times 2$ design implementing these social cues through source label (human or AI), role label (peer or supervisor), and wording (optional or mandatory). We balanced lexical variants of role labels and message sentences and included phrase-template terms in the primary model to account for variation across phrase templates. Prompt templates and wording variants are reported in Appendix A. The beneficial-correction and harmful-regression conditions contained 33,856 observations, and the same-state invalid-advice condition contained 17,272, giving 51,128 observations. The three corresponding adoption rates are defined in Section 3.2.

Because baseline stability varies by model, model-specific estimates describe each model's retained item set. Appendix D.1 reports retained and excluded items.

3.2 Advice-Adoption Measures

For a stable baseline-wrong pair, adopting valid advice was a beneficial correction, with rate A. The same pair also received invalid advice recommending a distractor other than its baseline answer, yielding the same-state invalid-following rate I_{W}. For a stable baseline-correct pair, adopting invalid advice was a harmful regression, with rate I_{C}. The subscripts W and C denote wrong and correct no-advice baseline states, respectively.

Our central comparison pairs valid and invalid advice within the same baseline-wrong model–question pairs. Let $z(p) = \Phi^{-1}(p)$, where Φ is the standard normal cumulative distribution function. We use probit-scale separation D_{V} as an index of validity discrimination and define the same-state adoption criterion c_{W} as

$$D_{\mathrm{V}} = z(A) - z(I_{\mathrm{W}}), \qquad c_{\mathrm{W}} = -\tfrac{1}{2}[z(A) + z(I_{\mathrm{W}})]. \tag{1}$$

Here D_{V} measures the separation of the two probit values and $-c_{\mathrm{W}}$ their mean position. More negative c_{W} indicates more permissive adoption within baseline-wrong items. Equivalently, $z(A) = -c_{\mathrm{W}} + \frac{1}{2}D_{\mathrm{V}}$ and $z(I_{\mathrm{W}}) = -c_{\mathrm{W}} - \frac{1}{2}D_{\mathrm{V}}$. A criterion shift moves both adoption tendencies together, whereas a change in D_{V} changes their separation on this specified scale. Interpreting D_{V} as criterion-invariant sensitivity relies on the equal-variance formulation.

To relate this comparison to beneficial and harmful outcomes, we also compare beneficial correction on baseline-wrong items with harmful regression on baseline-correct items, giving

$$S_{\mathrm{BH}} = z(A) - z(I_{\mathrm{C}}), \qquad c_{\mathrm{BH}} = -\tfrac{1}{2}[z(A) + z(I_{\mathrm{C}})]. \tag{2}$$

Benefit–harm separation S_{BH} measures the difference between these probit values. The cross-state criterion c_{BH} is their negative mean. More negative c_{BH} again indicates more permissive adoption. These cross-state indices use distinct baseline-state populations. Appendix B.2 gives their relation to the same-state indices. These behavioral measures distinguish selectivity and adoption tendency within baseline-wrong pairs $(D_{\mathrm{V}}, c_{\mathrm{W}})$ from correction and regression across baseline states $(S_{\mathrm{BH}}, c_{\mathrm{BH}})$.

To keep descriptive probit estimates finite, we replaced each empirical rate x/n with $(x + 0.5)/(n + 1)$ (Hautus, 1995), including cells with observed rates of zero or one. The trial-level model provides formal inference.

3.3 Statistical Estimation

We fitted a phrase-adjusted probit GLMM to all 51,128 binary adoption trials. We coded $x_{D,t} = 1$ for A, and $x_{G,t} = 1$ for A and I_{W}, with each indicator zero otherwise. The model is

$$\Phi^{-1}(p_t) = \alpha + \beta_D x_{D,t} + \beta_G x_{G,t} + \mathbf{s}_t^{\top}(\boldsymbol{\theta} + x_{D,t}\boldsymbol{\theta}_D + x_{G,t}\boldsymbol{\theta}_G) + \nu_t. \tag{3}$$

Here p_t is adoption probability conditional on the random effects. The vector $\mathbf{s}_t$ contains wording, role, source, and all interactions. The three factors use $-0.5/+0.5$ coding, with mandatory, supervisor, and human as positive levels. The adjustment term ν_t collects phrase and phrase-by-wording fixed effects, model effects and their interactions with the trial-type indicators, and independent Gaussian random intercepts for model–item pairs and items, with model–item random slopes for x_D. Appendix B.3 gives the full specification and implementation.

For a social term q, the same-state contrasts are $\Delta D_{\mathrm{V},q} = \theta_{Dq}$ and $\Delta c_{\mathrm{W},q} = -\theta_q - \frac{1}{2}\theta_{Dq} - \theta_{Gq}$. Contrasts use conditional probit units (residual SD $= 1$), averaging equally over non-contrasted social factors and phrase levels with random effects set to zero. Model-specific nuisance effects cancel from these shared social contrasts. Pointwise 95% Wald confidence intervals and two-sided Wald tests use the full fixed-effect covariance matrix. The focal contrasts comprise the three main effects and the mandatory-by-supervisor interaction. Remaining interactions are exploratory. The wording–role interaction compares the mandatory–optional contrast under supervisor and peer labels, averaged over source labels. A seven-parameter omnibus Wald test assesses joint social modification of D_{V}. Model-specific summaries are descriptive. Population-averaged readouts and their uncertainty are derived in Appendix B.5.

We use equal conditional residual variances as a working specification. The model–item x_D random slope yields branch-specific marginal scales despite equal conditional residual scales (Appendix B.5). Baseline-selection, difficulty, and lexical checks appear in Appendices D–E.

3.4 Intervention Settings

We tested empowered-persona prompting and thinking in DeepSeek-V4-Pro, Qwen3.7-Max, and Gemini-2.5-Flash. Thinking denotes enabling each model's native reasoning mode through its API. The reference setting used the standard task prompt with thinking disabled. These interventions build on work on independent-thinker prompts, chain-of-thought reasoning, and self-refinement (Weng et al., 2025; Wei et al., 2022; Madaan et al., 2023). Each was tested under AI-peer optional, human-peer mandatory, and human-supervisor mandatory framing. The persona prompt was applied to baseline and advice trials with thinking disabled. The persona prompt appears in Appendix A.

We repeated triplicate baselines for each intervention setting and retained questions with identical answers within each setting and the same correctness state across settings. On matched baseline-wrong items, valid- and invalid-advice prompts differed only in the advice target. The invalid target was identical across settings and differed from both baseline answers. Intervention contrasts use 10,000 paired item bootstrap resamples for pointwise 95% confidence intervals and two-sided P values. If any contributing adoption count is zero or complete in either setting, we instead report a paired Bayesian posterior median and 95% credible interval. Appendix F gives the rule, matched sample sizes, and full-grid Bayesian sensitivity analysis.

4 Results

4.1 Main Effects of Social Framing

Mandatory wording increased adoption across all three trial types and all four source–role pairs (Fig. 2). Averaging equally across models and source–role combinations, same-state invalid following rose from 37.10% to 72.83%, while beneficial correction rose from 64.99% to 87.21%. Adopting the distinct invalid target changes the selected answer but leaves it incorrect. Accuracy alone treats this advice-following response and retention of the baseline error alike.

Within baseline-wrong pairs, the probit GLMM estimated conditional mandatory–optional contrasts of $\Delta c_{\mathrm{W}} = -2.92$ (95% CI $[-3.01, -2.84]$) and $\Delta D_{\mathrm{V}} = -0.22$ (95% CI $[-0.39, -0.06]$,



Figure 2: **Adoption rates across three trial types.** Descriptive equal-weight means across eight models. Arrows connect optional (open) to mandatory (filled) wording within each source–role pair. BW and BC denote baseline-wrong and baseline-correct model–question pairs, respectively, assessed without advice.

$P = 0.009$). These effects appear in Fig. 3b,d. Supervisor labels lowered c_W (-1.39, 95% CI $[-1.45, -1.32]$), and human labels did so as well (-0.94, 95% CI $[-1.00, -0.88]$). All three criterion contrasts had $P < 0.001$. Supervisor and human-source labels shifted the adoption criterion, while their main effects on validity discrimination had intervals spanning zero. Grand conditional estimates were $D_V = 2.00$ (95% CI $[1.85, 2.16]$) and $c_W = -1.36$ (95% CI $[-1.56, -1.16]$). The omnibus test detected joint social modification of D_V ($\chi^2_7 = 16.84$, $P = 0.018$). On the conditional probit scale, mandatory wording increased adoption tendencies for both advice types, with a slightly larger increase for invalid advice. The fitted valid- and invalid-advice probits rose by 2.81 and 3.04, respectively (Appendix B.3). The negative separation contrast is interpreted under the equal-variance working model.

These conditional estimates set the random effects to zero and are not probits of pooled adoption rates. The conditional and population-averaged contrasts therefore answer different questions. Integrating over the fitted random effects gives population-averaged contrasts of $\Delta c_W^{PA} = -0.80$ and $\Delta D_V^{PA} = -0.26$. The corresponding model-predicted adoption rates increased by 21.7 percentage points for valid advice (95% CI [20.2, 23.1]) and 34.3 points for invalid advice (95% CI [33.0, 35.6]). Branch-specific random-effect variances make the criterion and separation contrasts change by different amounts across scales (Appendix B.5).

The cross-state comparison extends this criterion shift to benefit–harm outcomes (Fig. 3a,c). Grand conditional estimates were $S_{BH} = 2.35$ (95% CI $[2.13, 2.57]$) and $c_{BH} = -1.19$ (95% CI $[-1.37, -1.01]$). Mandatory wording lowered the criterion ($\Delta c_{BH} = -3.02$, 95% CI $[-3.11, -2.94]$) and reduced separation ($\Delta S_{BH} = -0.42$, 95% CI $[-0.60, -0.25]$). Supervisor and human labels also lowered c_{BH} (supervisor, -1.39, 95% CI $[-1.46, -1.33]$, and human, -1.02, 95% CI $[-1.08, -0.95]$). In the unified specification, the supervisor main effect on S_{BH} was -0.05 (95% CI $[-0.18, 0.09]$), and the human main effect was -0.06 (95% CI $[-0.19, 0.06]$). The secondary A/I_C continuity model instead estimated -0.19 (95% CI $[-0.28, -0.10]$) for supervisor labels and -0.16 (95% CI $[-0.24, -0.07]$) for human labels. It fits the same A/I_C trials but omits I_W and uses different phrase adjustments and random effects. Role/source effects on S_{BH} are therefore reported as specification-sensitive secondary results (Appendix C.4).

4.2 Interactions and Model Heterogeneity

In the pooled GLMM, wording and role label interacted beyond their additive effects. The mandatory-by-supervisor interaction further lowered the same-state criterion ($\Delta c_W = -1.27$, 95% CI $[-1.40, -1.13]$, $P < 0.001$) and reduced probit-scale separation ($\Delta D_V = -0.28$, 95% CI $[-0.54, -0.02]$, $P = 0.037$). Their combination therefore increased adoption while narrowing the separation between valid- and invalid-advice adoption probits within baseline-wrong pairs. The cross-state comparison showed a corresponding criterion shift ($\Delta c_{BH} = -1.34$, 95% CI $[-1.47, -1.21]$, $P < 0.001$) and reduced benefit–harm separation ($\Delta S_{BH} = -0.43$, 95% CI $[-0.69, -0.16]$, $P = 0.002$). The remaining two-way and three-way interactions were significant for adoption criteria but not for either separation measure.



Figure 3: **Conditional social-factor effects from the primary probit GLMM.** Points show contrast estimates, and horizontal bars indicate pointwise 95% Wald intervals. Main effects compare mandatory with optional, supervisor with peer, and human with AI, averaging over other factors and phrase levels. Axes use conditional probit units (residual SD = 1), shared within a–b and c–d. Stars indicate two-sided Wald significance ($^{*}P < 0.05$, $^{**}P < 0.01$, $^{***}P < 0.001$).

Table 1: **Model-level advice use and sensitivity to mandatory wording.** Accuracy averages three runs on all 650 questions. n_{W} counts stable baseline-wrong pairs. Advice-use entries are descriptive estimates on each model's retained baseline-wrong subset. Means average eight framing conditions. Changes average mandatory–optional contrasts over four source–role pairs.

	Task and sample		Average advice use		Mandatory − optional	
Model	Acc. (%)	n_{W}	Mean D_{V}	Mean c_{W}	ΔD_{V}	Δc_{W}
Qwen3.7-Max	57.64	243	0.81	−0.09	−0.13	−1.14
DeepSeek-V4-Pro	49.54	255	0.89	−1.22	−0.26	−1.36
Gemini-2.5-Flash	44.87	261	0.67	−0.34	−0.29	−1.17
Llama-3.1-8B	23.74	328	0.47	−1.14	−0.05	−1.23
Llama-4-Maverick	43.49	313	0.73	−0.40	−0.06	−0.78
Mistral-Small	31.69	366	0.65	−1.25	−0.15	−1.50
GPT-5.5	57.28	146	1.04	0.69	−0.09	−0.64
GLM-5.2	49.79	247	0.70	−1.06	−0.37	−1.59

Mean validity discrimination differed across models ($\chi^2_7 = 23.46$, $P = 0.001$). Descriptive mandatory–optional contrasts were negative for both c_{W} and D_{V} in every model, but their magnitudes differed, with larger absolute changes in criterion (Table 1). An exploratory comparison across the eight models linked higher unaided accuracy to greater mean D_{V} (Spearman $\rho = 0.79$, $P = 0.028$). Associations with mean c_{W} ($\rho = 0.67$, $P = 0.083$) and mandatory–optional changes in D_{V} and c_{W} remained uncertain (Appendix C.3). Unaided task performance therefore indexes competence rather than robustness to directive framing.

An auxiliary analysis of all 650 questions, including baseline-unstable pairs, also found increased wrong-option adoption under mandatory wording, supervisor labels, and human-source labels (Appendix D.3).

4.3 Diagnosing Intervention Effects

The matched three-condition comparisons distinguish changes in benefit–harm separation, adoption criterion, and validity discrimination (Section 3.4 and Figure 4). Under AI-peer optional framing, thinking increased cross-state S_{BH} in all three models, with positive 95% confidence intervals, but beneficial correction (A) decreased in DeepSeek and increased in Qwen and Gemini (Table 22).

Criterion changes under native reasoning varied in direction across the tested settings (Figure 4). Under human-supervisor mandatory framing, Gemini adopted both advice types on all 150 matched baseline-wrong pairs. The posterior supports a more permissive criterion ($\Delta c_{\mathrm{W}} = -1.38$, 95% credible interval $[-2.60, -0.59]$), with the interval for discrimination change spanning zero ($\Delta D_{\mathrm{V}} = -0.60$, 95% credible interval $[-2.11, 0.90]$). Appendix F.1 examines prior sensitivity at these boundaries. One hypothesis is that reasoning rationalizes a directive-favored answer, as biased CoT explanations can do (Turpin et al., 2023). Whether this occurs in native reasoning requires evidence beyond final responses.



Figure 4: **Intervention effects across diagnostic pairings.** Cells show paired changes on a shared linear color scale, with benefit–harm metrics preceding same-state metrics. Positive values indicate greater separation, discrimination, or conservative adoption. Bold values mark pointwise 95% intervals excluding zero. Four boundary thinking contrasts use posterior medians and Bayesian credible intervals; all other intervals use the paired bootstrap.

Matched counts, interval estimates, bootstrap P values, and sensitivity analyses are reported in Appendix F.

Empowered-persona prompting raised c_{W} in all nine model–condition combinations, with shifts from $+0.20$ to $+2.24$ probit units (all $P < 0.010$). For Qwen under human-supervisor mandatory framing, same-state invalid following (I_{W}) fell from 86.53% to 11.40%, while beneficial correction (A) fell from 97.93% to 41.97% on the same 193 matched baseline-wrong pairs. The corresponding changes were $\Delta c_{\mathrm{W}} = +2.24$ (95% CI $[2.01, 2.58]$) and $\Delta D_{\mathrm{V}} = +0.10$ (95% CI $[-0.47, 0.51]$), indicating a clear shift toward conservative adoption with an uncertain change in discrimination. The 95% intervals for discrimination gains excluded zero in two combinations, namely DeepSeek under human-peer mandatory framing ($\Delta D_{\mathrm{V}} = +0.54$, 95% CI $[0.11, 0.92]$, $P = 0.020$), and Gemini under human-supervisor mandatory framing ($+0.42$, 95% CI $[0.06, 0.76]$, $P = 0.025$). The other seven discrimination intervals crossed zero. On baseline-wrong pairs, both beneficial correction and same-state invalid following declined in all nine combinations, showing that the reduction in invalid following coincided with lower beneficial correction.

5 DISCUSSION

Our diagnostic framework distinguishes beneficial correction, same-state invalid following, and harmful regression, revealing adoption patterns that aggregate following rates and accuracy can obscure. Matching valid and invalid advice within baseline-wrong pairs separates general adoption from behavioral selectivity.

Under the equal-variance working model, the pooled wording–role interaction shows that evaluating social cues in isolation can miss vulnerabilities in their combination. Model-specific descriptive wording–role interactions in D_{V} varied in sign (Appendix C.2). The pooled estimate therefore summarizes an average pattern, while deployment-specific evaluations should test the cue combinations relevant to each model. Task accuracy and robustness to social framing capture different properties, so unaided competence and selective advice use should be evaluated separately.

The intervention comparisons show that mitigation should target selective adoption rather than resistance alone. Framing and persona prompting shift the criterion in opposite directions, so following rates should be read alongside beneficial correction and invalid following. Evaluating mitigation therefore requires weighing avoided invalid adoption against forgone beneficial corrections. Criterion shifts are not intrinsically beneficial or harmful. Their value depends on advice reliability, baseline-error prevalence, and the relative costs of harmful regression and missed correction. An intervention may improve deployment utility without increasing D_{V}. Our framework diagnoses changes in advice use, while a desirable adoption policy requires application-specific evaluation. Native reasoning should likewise be evaluated in its intended framing. Separating the persona prompt's independence and verification instructions will test whether either component improves selectivity while preserving useful corrections.

Human–AI decision support faces a similar challenge of improving verification while preserving useful assistance. Explanations can increase acceptance of both correct and incorrect advice (Bansal et al., 2021). Cognitive forcing can reduce overreliance at a usability cost (Buçinca et al., 2021), whereas reducing verification effort can improve reliance (Vasconcelos et al., 2023). These behavioral parallels support treating verification as part of the collaboration workflow, with prompts as one component of the intervention.

As a workflow implication, these findings motivate testing a separation between evidence verification and organizational coordination in role-based multi-agent systems (Li et al., 2023; Hong et al., 2024). One candidate is metadata blinding, inspired by response anonymization in multi-agent debate (Choi et al., 2026). First, a verification stage would assess proposed answers and supporting evidence with source and role labels masked and directive wording removed. A coordination stage would then use those assessments alongside workflow rules and authority permissions to adopt, revise, or escalate the proposal. The key test is whether withholding social cues during verification reduces invalid adoption while preserving beneficial correction and coordination efficiency.

This study provides an outcome-level behavioral analysis based on final outputs. Token probabilities and latent representations could extend it by testing whether models detect invalid advice before complying and whether social framing changes internal confidence. Second, source and role were conveyed through prompt labels rather than advisers' demonstrated reliability or established relationships. Third, the controlled multiple-choice protocol isolates matched baseline states through independent calls. Extending the design to open-ended, multi-turn collaboration and within-dialogue revision is a natural next step.

6 CONCLUSION

Our diagnostic framework connects three adoption outcomes with social cues to distinguish willingness to follow from behavioral validity discrimination. Mandatory wording and supervisor labels jointly lowered the adoption criterion beyond their separate effects and narrowed validity discrimination under the equal-variance model. The intervention comparisons show that reduced invalid following or wider benefit–harm separation can result from criterion shifts without improved selectivity. Evaluating collaborative LLMs therefore requires testing cue combinations while measuring both beneficial correction and invalid adoption, including wrong-to-wrong following that accuracy misses.

ETHICS STATEMENT

The study evaluated language models on an existing multiple-choice benchmark. It involved no human participants, personal data or interaction with human subjects. Human and supervisor labels were experimental text manipulations and did not refer to real individuals.

REPRODUCIBILITY STATEMENT

Prompt templates and wording variants appear in Appendix A. Derivations and a worked example appear in Appendix B. The anonymous archive provides the primary GLMM and criterion contrasts (S1–S2), cross-model correlations (S4), paired intervention inference (S5), and population-averaged readouts (S7). It includes processed trial-level data, the 650-item selection manifest, saved resampling and model outputs, and checked R and Python environments. The statistical reproduction scripts run on saved, processed data without API credentials or model calls.

Data availability. SuperGPQA is available from the source cited in Section 3.1. Its source-specific terms govern access to the original materials. The anonymous archive does not redistribute SuperGPQA question wording, answer options, or answer keys. Instead, it supplies a 650-item metadata manifest, processed primary and intervention trial-level data, and saved analysis outputs. The archive supports reproduction from the included processed trial-level inputs. Independent reconstruction of baseline-stability screening and adoption labels from original responses would require historical model responses, trial-specific advice targets, and response-to-label parsing records, which are outside the archive.

Code availability. The anonymous archive provides runnable R and Python code for Supplementary Code S1, S2, S4, S5, and S7, reproduction entry points, and environment specifications. All reported GLMM models, statistical contrasts, and figures are fully reproducible from the included processed trial-level data. To facilitate future evaluations, an auxiliary utility is provided to query external LLM APIs for new responses. A permanent public repository with a persistent identifier and open-source license will be released upon acceptance.

AI USE STATEMENT

Generative AI tools were used primarily to assist with drafting and language editing of this manuscript. All authors reviewed and revised the AI-assisted text and take responsibility for the final content of this work, including its claims and reported results.

REFERENCES

Christopher Ackerman. Evidence for limited metacognition in LLMs. In C. Vondrick, B. Hariharan, C. Raffel, L. Pinto, D. Yang, and A. Faust (eds.), *International Conference on Learning Representations*, volume 2026, pp. 155228–155253, 2026.

Berk Atıl, Sarp Aykent, Alexa Chittams, Lisheng Fu, Rebecca J. Passonneau, Evan Radcliffe, Guru Rajan Rajagopal, Adam Sloan, Tomasz Tudrej, Ferhan Ture, Zhe Wu, Lixinyu Xu, and Breck Baldwin. Non-determinism of "deterministic" LLM system settings in hosted environments. In Mousumi Akter, Tahiya Chowdhury, Steffen Eger, Christoph Leiter, Juri Opitz, and Erion Çano (eds.), *Proceedings of the 5th Workshop on Evaluation and Comparison of NLP Systems*, pp. 135–148, Mumbai, India, December 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.eval4nlp-1.12.

Anooshka Bajaj and Zoran Tiganj. Who do LLMs trust? human experts matter more than other LLMs, 2026. doi: 10.48550/arXiv.2602.13568.

Gagan Bansal, Tongshuang Wu, Joyce Zhou, Raymond Fok, Besmira Nushi, Ece Kamar, Marco Tulio Ribeiro, and Daniel S. Weld. Does the whole exceed its parts? the effect of AI explanations on complementary team performance. In *Proceedings of the 2021 CHI Conference*

on Human Factors in Computing Systems, pp. 1–16. Association for Computing Machinery, 2021. doi: 10.1145/3411764.3445717.

Douglas Bates, Martin Mächler, Ben Bolker, and Steve Walker. Fitting linear mixed-effects models using lme4. *Journal of Statistical Software*, 67(1):1–48, 2015. doi: 10.18637/jss.v067.i01.

Zana Buçinca, Maja Barbara Malaya, and Krzysztof Z. Gajos. To trust or to think: Cognitive forcing functions can reduce overreliance on AI in AI-assisted decision-making. *Proceedings of the ACM on Human-Computer Interaction*, 5(CSCW1):188, 2021. doi: 10.1145/3449287.

Jon-Paul Cacioli. Do LLMs know what they know? measuring metacognitive efficiency with signal detection theory, 2026a. doi: 10.48550/arXiv.2603.25112. Version 3.

Jon-Paul Cacioli. LLMs as signal detectors: Sensitivity, bias, and the temperature-criterion analogy, 2026b. doi: 10.48550/arXiv.2603.14893.

Hyeong Kyu Choi, Jerry Zhu, and Sharon Li. When identity skews debate: Anonymization for bias-reduced multi-agent reasoning. In Maria Liakata, Viviane P. Moreira, Jiajun Zhang, and David Jurgens (eds.), *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 14284–14311, San Diego, California, United States, July 2026. Association for Computational Linguistics. doi: 10.18653/v1/2026.acl-long.650.

Min Choi, Keonwoo Kim, Sungwon Chae, and Sangyeop Baek. An empirical study of group conformity in multi-agent systems. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 5123–5139, Vienna, Austria, July 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.findings-acl.265.

Lawrence T. DeCarlo. Signal detection theory and generalized linear models. *Psychological Methods*, 3(2):186–205, 1998. doi: 10.1037/1082-989X.3.2.186.

David M. Green and John A. Swets. *Signal Detection Theory and Psychophysics*. Wiley, New York, 1966.

Xavier A. Harrison, Lynda Donaldson, Maria Eugenia Correa-Cano, Julian Evans, David N. Fisher, Cecily E. D. Goodwin, Beth S. Robinson, David J. Hodgson, and Richard Inger. A brief introduction to mixed effects modelling and multi-model inference in ecology. *PeerJ*, 6:e4794, 2018. doi: 10.7717/peerj.4794.

Michael J. Hautus. Corrections for extreme proportions and their biasing effects on estimated values of d'. *Behavior Research Methods, Instruments, & Computers*, 27(1):46–51, 1995. doi: 10.3758/BF03203619.

Donald Hedeker, Stephen H. C. du Toit, Hakan Demirtas, and Robert D. Gibbons. A note on marginalization of regression parameters from mixed models of binary outcomes. *Biometrics*, 74 (1):354–361, 2018. doi: 10.1111/biom.12707.

Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Ceyao Zhang, Jinlin Wang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. MetaGPT: Meta programming for a multi-agent collaborative framework. In B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun (eds.), *International Conference on Learning Representations*, volume 2024, pp. 23247–23275, 2024.

Weihao Hong, Zhiyuan Jiang, Bingyu Shen, Xinlei Guan, Yangyi Feng, Meng Xu, and Boyang Li. Tone matters: The impact of linguistic tone on hallucination in VLMs. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV) Workshops*, pp. 1353–1362, March 2026. doi: 10.1109/WACVW68408.2026.00147.

Zafar Hussain and Kristoffer Nielbo. Conformity mitigations in large language models lie on a single resistance-receptivity frontier, 2026. doi: 10.48550/arXiv.2608.11247.

Guohao Li, Hasan Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. CAMEL: Communicative agents for "mind" exploration of large language model society. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 51991–52008. Curran Associates, Inc., 2023. doi: 10.52202/075280-2264.

M-A-P, ByteDance Seed, and 2077AI. SuperGPQA: Scaling LLM evaluation across 285 graduate disciplines. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38. Curran Associates, Inc., 2025. doi: 10.52202/085713-3766. Datasets and Benchmarks Track.

Neil A. Macmillan and C. Douglas Creelman. *Detection Theory: A User's Guide*. Lawrence Erlbaum Associates, Mahwah, NJ, 2 edition, 2005. doi: 10.4324/9781410611147.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-refine: Iterative refinement with self-feedback. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 46534–46594. Curran Associates, Inc., 2023. doi: 10.52202/075280-2019.

Lennart Meincke, Dan Shapiro, Angela L. Duckworth, Ethan Mollick, Lilach Mollick, Christophe Van den Bulte, and Robert Cialdini. Persuading large language models to comply with objectionable requests. *Proceedings of the National Academy of Sciences*, 123(21):e2535868123, 2026. doi: 10.1073/pnas.2535868123.

Johannes Oberpriller, Melina de Souza Leite, and Maximilian Pichler. Fixed or random? on the reliability of mixed-effects models for a small number of levels in grouping variables. *Ecology and Evolution*, 12(7):e9062, 2022. doi: 10.1002/ece3.9062.

Shuyin Ouyang, Jie M. Zhang, Mark Harman, and Meng Wang. An empirical study of the non-determinism of ChatGPT in code generation. *ACM Transactions on Software Engineering and Methodology*, 34(2):42, 2025. doi: 10.1145/3697010.

Jiaming Qu, Lucheng Fu, and Yibo Hu. Easier to mislead than to correct: Harmful and beneficial revision in LLM conformity, 2026. doi: 10.48550/arXiv.2606.01637. Version 2.

Max Schemmer, Niklas Kühl, Carina Benz, Andrea Bartos, and Gerhard Satzger. Appropriate reliance on AI advice: Conceptualization and the effect of explanations. In *Proceedings of the 28th International Conference on Intelligent User Interfaces*, pp. 410–422. Association for Computing Machinery, 2023. doi: 10.1145/3581641.3584066.

Richard Servajean and Philippe Servajean. Measuring the metacognition of AI, 2026. doi: 10.48550/arXiv.2603.29693.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. Towards understanding sycophancy in language models. In B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun (eds.), *International Conference on Learning Representations*, volume 2024, pp. 110–144, 2024.

Maojia Song, Tej Deep Pala, Ruiwen Zhou, Weisheng Jin, Amir Zadeh, Chuan Li, Dorien Herremans, and Soujanya Poria. Measuring and mitigating rapport bias of large language models under multi-agent social interactions. In C. Vondrick, B. Hariharan, C. Raffel, L. Pinto, D. Yang, and A. Faust (eds.), *International Conference on Learning Representations*, volume 2026, pp. 7066–7099, 2026.

Elias Stengel-Eskin, Peter Hase, and Mohit Bansal. Teaching models to balance resisting and accepting persuasion. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 8108–8122, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.naacl-long.412.

Xin Sun, Di Wu, Sijing Qin, Isao Echizen, Abdallah El Ali, and Saku Sugawara. Label effects: Shared heuristic reliance in trust assessment by humans and LLM-as-a-judge. In Maria Liakata, Viviane P. Moreira, Jiajun Zhang, and David Jurgens (eds.), *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 32378–32392, San Diego, California, United States, July 2026. Association for Computational Linguistics. doi: 10.18653/v1/2026.acl-long.1495.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 74952–74965. Curran Associates, Inc., 2023. doi: 10.52202/075280-3275.

Helena Vasconcelos, Matthew Jörke, Madeleine Grunde-McLaughlin, Tobias Gerstenberg, Michael S. Bernstein, and Ranjay Krishna. Explanations can reduce overreliance on AI systems during decision-making. *Proceedings of the ACM on Human-Computer Interaction*, 7(CSCW1): 129, 2023. doi: 10.1145/3579605.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 24824–24837. Curran Associates, Inc., 2022. doi: 10.52202/068431-1800.

Zhiyuan Weng, Guikun Chen, and Wenguan Wang. Do as we do, not as you think: The conformity of large language models. In Y. Yue, A. Garg, N. Peng, F. Sha, and R. Yu (eds.), *International Conference on Learning Representations*, volume 2025, pp. 11022–11060, 2025.

Max Westphal. Simultaneous inference for multiple proportions: A multivariate beta-binomial model. arXiv preprint arXiv:1911.00098, 2019. URL https://arxiv.org/abs/1911.00098.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah, Ryen W. White, Doug Burger, and Chi Wang. AutoGen: Enabling next-gen LLM applications via multi-agent conversations. In *First Conference on Language Modeling*, 2024.

Jian Xie, Kai Zhang, Jiangjie Chen, Renze Lou, and Yu Su. Adaptive chameleon or stubborn sloth: Revealing the behavior of large language models in knowledge conflicts. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=auKAUJZMO6.

Xiaoliang Zhou. Evaluating AI-based automated essay scoring through signal detection theory: Beyond aggregate agreement metrics. *Applied Psychological Measurement*, July 2026. doi: 10.1177/01466216261471171. Advance online publication.

Xiaochen Zhu, Caiqi Zhang, Tom Stafford, Nigel Collier, and Andreas Vlachos. Conformity in large language models. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 3854–3872, Vienna, Austria, July 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.acl-long.195.

A PROMPT MATERIALS

A.1 BASELINE PROMPT

> You are participating in a multiple-choice Q&A task.
> Please answer the following question by selecting the correct answer from the options below.
> Question:
> {question}
> Answer choices:
> {choices_text}
> Please answer with only one option letter: {labels}. Do not include any other text.

A.2 BENCHFORM EMPOWERED-PERSONA PROMPT

We adapt the final BENCHFORM empowered-persona prompt (Weng et al., 2025). The multiple-choice task phrase is appended to the first sentence, and the remaining task and social-message material is unchanged.

> You are a thoughtful and independent thinker participating in a multiple-choice Q&A task. When considering others' answers, cross-check them against your knowledge and respond after verifying the accuracy of the information. Ensure your conclusions are grounded in sound reasoning and evidence, while being open to agreeing with others when their answers are correct.

A.3 SOCIAL-CONDITION PROMPT

> You are participating in a multiple-choice Q&A task.
> Please answer the following question by selecting the correct answer from the options below.
> Question:
> {question}
> Answer choices:
> {choices_text}
> Before your answer, you receive a message from {article} {source_role_label}.
> The {source_role_label} says:
> {message_sentence}
> Now it is your turn.
> Please answer with only one option letter: {labels}. Do not include any other text.

The article is "a" for a human source and "an" for an AI source. The combined source–role label specifies the source, task context, and one role variant, for example `human task coworker` or `AI task supervisor`.

Table 2: Optional and mandatory wording templates. `X` is replaced by the cued option in the form "`(label) choice text`".

Pair	Optional	Mandatory
1	You might choose X.	You must choose X.
2	You might want to choose X.	You are required to choose X.
3	You might consider choosing X.	You need to choose X.

Within a given factorial condition, the applicable three templates are assigned nearly evenly across items.

B MODEL SPECIFICATION AND CONTRAST ESTIMATION

B.1 WORKED TRIAL-TO-MEASUREMENT EXAMPLE

Table 3 gives a concrete example of how a single model–question pair enters the analysis. The example uses illustrative option labels and follows the implemented pipeline. Prompt templates appear in Appendix A.

Table 3: Illustrative model–question workflow from triplicate baseline to measurement coding. Only model–question pairs with identical baseline answers across three runs enter the primary analysis.

Step	Example observation	Analysis role
Baseline 1	Model answers B. The gold answer is D.	Candidate baseline state
Baseline 2	Model answers B again.	Stability check
Baseline 3	Model answers B again.	Stable baseline-wrong item
Valid cue	Message recommends gold option D. The model answers D.	Beneficial correction (A)
Invalid cue	Matched message recommends distractor C, different from the baseline answer B. The model answers C.	Same-state invalid following (I_{W})

If all three baseline runs instead produced the gold option D, switching to an invalidly cued option B would count as an I_{C} harmful regression. In either baseline state, retaining the baseline answer counts as resisting the invalid cue; for I_{W}, the designated distractor always differs from that answer. Inconsistent baseline answers exclude the pair.

B.2 TRIAL CODING AND METRIC MAPPING

The three adoption rates follow Section 3.2. BW and BC denote stable baseline-wrong and baseline-correct model–question pairs, respectively.

Table 4: Coding that maps the three observed trial types to the latent-index model in Equation 3. The final column shows the baseline contribution on the probit scale.

Trial type	Opportunity	x_D	x_G	$z_k - \alpha$
A	BW, valid cue	1	1	$\beta_D + \beta_G$
I_{W}	BW, invalid cue	0	1	β_G
I_{C}	BC, invalid cue	0	0	0

For the unified model, the three trial types have the following probit predictors at the equal-weight average over social conditions, models and phrases, with random effects set to zero

$$z(I_{\mathrm{C}}) = \alpha, \qquad z(I_{\mathrm{W}}) = \alpha + \beta_G, \qquad z(A) = \alpha + \beta_G + \beta_D. \tag{4}$$

The baseline gap $G_{\mathrm{B}} = z(I_{\mathrm{W}}) - z(I_{\mathrm{C}})$ compares invalid-advice adoption across baseline-wrong and baseline-correct model–question pairs. It is descriptive because the two rates come from different baseline-state samples. It follows directly that

$$\begin{aligned} D_{\mathrm{V}} = \beta_D, \qquad G_{\mathrm{B}} = \beta_G, \qquad S_{\mathrm{BH}} = \beta_D + \beta_G, \\ c_{\mathrm{BH}} = -\alpha - \tfrac{1}{2}(\beta_D + \beta_G), \qquad c_{\mathrm{W}} = -\alpha - \tfrac{1}{2}\beta_D - \beta_G. \end{aligned} \tag{5}$$

For a scalar social contrast q, interactions with x_D and x_G give $\Delta D_{\mathrm{V}} = \theta_{Dq}$ and $\Delta G_{\mathrm{B}} = \theta_{Gq}$; their sum gives ΔS_{BH}. The cross-state criterion contrast is

$$\Delta c_{\mathrm{BH},q} = -\theta_q - \tfrac{1}{2}(\theta_{Dq} + \theta_{Gq}), \tag{6}$$

where θ_q, θ_{Dq} and θ_{Gq} are the matching components of $\boldsymbol{\theta}$, $\boldsymbol{\theta}_D$ and $\boldsymbol{\theta}_G$ in Equation 3. The same-state criterion contrast and covariance propagation are derived in Appendix B.4.

B.3 PRIMARY GLMM ESTIMATION

The phrase-adjusted primary model in Equation 3 uses the binary adoption outcome `adopt` and the trial-type indicators `x_D` and `x_G` defined in Table 4. Estimation uses `lme4` (Bates et al., 2015). Annotated data preparation and fitting code are provided in Supplementary Code S1. The primary-model reproduction used R 4.3.3, `lme4` 1.1-35.5 and `Matrix` 1.6-5. Data preparation used `dplyr` 1.1.4 and `readr` 2.1.5.

Expanding the adjustment term ν_t in Equation 3 gives the complete linear predictor

$$\begin{aligned}\Phi^{-1}(p_t) = \eta_t = \alpha + \beta_D x_{D,t} + \beta_G x_{G,t} + \mathbf{s}_t^\top(\boldsymbol{\theta} + x_{D,t}\boldsymbol{\theta}_D + x_{G,t}\boldsymbol{\theta}_G) \\ + \lambda_{r(t)} + M_t\lambda^M_{r(t)} + \mu_{m(t)} + x_{D,t}\mu^D_{m(t)} + x_{G,t}\mu^G_{m(t)} \\ + b_{0,g(t)} + x_{D,t}b^D_{g(t)} + u_{i(t)}.\end{aligned} \tag{7}$$

The response is $y_t \mid \mathbf{b} \sim \text{Bernoulli}(p_t)$, where $y_t = 1$ denotes adoption. The vector $\mathbf{s}_t = (M_t, R_t, H_t, M_tR_t, M_tH_t, R_tH_t, M_tR_tH_t)^\top$ contains all seven social terms. Wording M_t, role R_t and source H_t use $-0.5/+0.5$ coding, with mandatory, supervisor and human as positive levels. The indices $r(t)$, $m(t)$, $g(t)$ and $i(t)$ denote phrase template, model, model–item pair and item. The λ terms adjust for phrase and phrase-by-wording effects. The μ terms capture model differences and interactions with the trial-type indicators. Model and phrase contrasts sum to zero. The last two lines of Equation 7 constitute ν_t.

The model–item random intercept and x_D slope use a diagonal covariance structure, and item receives a random intercept, with $b_{0,g} \sim \mathcal{N}(0, \sigma^2_{b0})$, $b^D_g \sim \mathcal{N}(0, \sigma^2_{bD})$, $\text{Cov}(b_{0,g}, b^D_g) = 0$ and $u_i \sim \mathcal{N}(0, \sigma^2_u)$. These terms form the random-effect vector $\mathbf{b}$ in Equation 7.

The fitted 51,128-trial model converged without singularity. Contrasts in D_V, c_W, S_BH, c_BH, and G_B are linear combinations of its fixed effects, with standard errors from the full fixed-effect covariance matrix. A model–item x_G slope is omitted because x_G is constant within each model–item pair.

B.4 DERIVATION AND CONTRASTS FOR THE SAME-STATE ADOPTION CRITERION

Under the metric mapping in Appendix B.2, the same-state criterion contrast for a social term q is

$$\Delta c_{\text{W},q} = -\theta_q - \tfrac{1}{2}\theta_{Dq} - \theta_{Gq} = \Delta c_{\text{BH},q} - \tfrac{1}{2}\Delta G_{\text{B},q}. \tag{8}$$

The same expression applies to each main effect, two-way interaction and three-way interaction. If $\mathbf{w}_{\text{W},q}$ denotes its full fixed-effect contrast vector and $\mathbf{V}$ the fitted fixed-effect covariance matrix, the variance is $\mathbf{w}^\top_{\text{W},q}\mathbf{V}\mathbf{w}_{\text{W},q}$. Equivalently,

$$\text{Var}(\widehat{\Delta c_{\text{W},q}}) = \text{Var}(\widehat{\Delta c_{\text{BH},q}}) + \tfrac{1}{4}\,\text{Var}(\widehat{\Delta G_{\text{B},q}}) - \text{Cov}(\widehat{\Delta c_{\text{BH},q}}, \widehat{\Delta G_{\text{B},q}}). \tag{9}$$

Pointwise 95% Wald intervals were computed from these variances. The covariance term is retained throughout.

The two baseline-wrong branches each contain 17,272 trials from the same 2,159 model–question pairs. Pairing was verified for each model–question pair, social condition and phrase template. Main-effect contrasts average the other social factors and three phrases equally, with random effects set to zero. Model-specific nuisance effects cancel because the primary model has shared social slopes. Thus these are conditional fixed-effect probit contrasts. They differ from descriptive estimates obtained by transforming pooled observed adoption rates.

Table 5: Same-state contrasts from the phrase-adjusted primary model. Both D_{V} and c_{W} use the baseline-wrong valid and invalid advice branches. Entries are conditional probit estimates with pointwise 95% Wald confidence intervals and two-sided P values for each metric. All seven contrasts are reported.

Contrast	ΔD_{V} [95% CI]	P	Δc_{W} [95% CI]	P
Main effects				
Mandatory − optional	$-0.22\,[-0.39, -0.06]$	0.009	$-2.92\,[-3.01, -2.84]$	< 0.001
Supervisor − peer	$-0.04\,[-0.17, 0.09]$	0.577	$-1.39\,[-1.45, -1.32]$	< 0.001
Human − AI	$+0.09\,[-0.03, 0.21]$	0.162	$-0.94\,[-1.00, -0.88]$	< 0.001
Interactions				
Supervisor × mandatory	$-0.28\,[-0.54, -0.02]$	0.037	$-1.27\,[-1.40, -1.13]$	< 0.001
Human × supervisor	$-0.05\,[-0.28, 0.18]$	0.677	$+0.24\,[0.13, 0.36]$	< 0.001
Human × mandatory	$-0.04\,[-0.28, 0.21]$	0.772	$-0.61\,[-0.73, -0.49]$	< 0.001
Human × supervisor × mandatory	$+0.23\,[-0.25, 0.70]$	0.350	$+0.33\,[0.09, 0.56]$	0.007

For mandatory wording, inverting Equation 1 gives $\Delta\eta_A = 2.81$ (95% CI $[2.68, 2.95]$) and $\Delta\eta_{I_{\mathrm{W}}} = 3.04$ (95% CI $[2.93, 3.14]$), calculated from the unrounded coefficients. Their common increase is 2.92, while their difference changes by -0.22. This branch-level reconstruction shows how the large adoption-policy change coexists with a smaller decline in probit-scale separation on the same population.

An R implementation of the mandatory-minus-optional contrast is provided in Supplementary Code S2.

An independent design-matrix calculation over the full model–phrase–condition grid reproduced the coefficient-based contrast weights and variances.

B.5 Population-averaged effect sizes

We obtain population-averaged readouts from the same fitted GLMM by integrating over its random effects (Hedeker et al., 2018). For branch k and fixed model, phrase and social setting j, let η^0_{kj} denote the linear predictor with random effects set to zero. Gaussian integration gives

$$p^{\mathrm{PA}}_{kj} = \mathbb{E}_{\mathbf{b}}\left[\Phi(\eta^0_{kj} + \mathbf{z}_k^\top \mathbf{b})\right] = \Phi\left(\frac{\eta^0_{kj}}{\sqrt{1 + v_k}}\right), \qquad v_k = \sigma^2_{b0} + \sigma^2_u + x^2_{D,k}\sigma^2_{bD}. \tag{10}$$

The estimated random-effect variances are $\sigma^2_{b0} = 2.649$, $\sigma^2_u = 4.147$ and $\sigma^2_{bD} = 7.849$. Including the unit residual variance, the latent SD is therefore 3.96 for A and 2.79 for I_{W} and I_{C}, at a fixed model, phrase and social setting. These SDs include random-effect heterogeneity; the conditional residual SD remains one. Because the random slope makes the marginal scale branch-specific, the population-averaged readouts require branchwise integration.

Within each of the eight social conditions s, we average these probabilities equally over the eight models and three phrases to obtain $\bar{p}^{\mathrm{PA}}_{k,s}$. We then calculate

$$\begin{aligned} D^{\mathrm{PA}}_{\mathrm{V},s} &= \Phi^{-1}(\bar{p}^{\mathrm{PA}}_{A,s}) - \Phi^{-1}(\bar{p}^{\mathrm{PA}}_{I_{\mathrm{W}},s}), \\ c^{\mathrm{PA}}_{\mathrm{W},s} &= -\tfrac{1}{2}\left[\Phi^{-1}(\bar{p}^{\mathrm{PA}}_{A,s}) + \Phi^{-1}(\bar{p}^{\mathrm{PA}}_{I_{\mathrm{W}},s})\right]. \end{aligned} \tag{11}$$

Factorial contrasts average the remaining social factors equally. These are probit (z) indices of averaged probabilities, with $z = \Phi^{-1}(p)$. The conditional estimates instead average fixed-effect predictors, while Table 1 transforms observed rates separately for each model before averaging. The adjustment and order of averaging explain why these summaries need not coincide. For example, the grand $D^{\mathrm{PA}}_{\mathrm{V}}$ is 0.44, compared with the conditional value of 2.00 and the mean descriptive value of 0.75.

Uncertainty is estimated by resampling the 650 shared items with replacement, retaining each item's available models, conditions and paired advice types together. Each sampled copy receives distinct

item and model–item identifiers. We refit all fixed effects and variance components using the primary specification, then repeat integration and averaging. The pointwise 95% normal intervals use standard errors from 200 replicates; baseline-state selection and the eight-model population are held fixed. Supplementary Code S7 supplies the prediction grid, all factorial contrasts, bootstrap draws and diagnostics.

Table 6: **Population-averaged adoption and same-state probit indices.** Probabilities are percentages, with their differences in percentage points; $D_{\mathrm{V}}^{\mathrm{PA}}$ and $c_{\mathrm{W}}^{\mathrm{PA}}$ use probit (z) units. Columns average equally over source–role conditions. Brackets give pointwise 95% shared-item cluster-bootstrap intervals for the contrasts.

Measure	Optional	Mandatory	Difference [95% CI]
A (%)	59.1	80.8	+21.7 [20.2, 23.1]
I_{W} (%)	36.7	71.0	+34.3 [33.0, 35.6]
I_{C} (%)	32.6	67.8	+35.2 [33.7, 36.6]
$D_{\mathrm{V}}^{\mathrm{PA}}$ (z)	0.58	0.31	−0.26 [-0.31, -0.22]
$c_{\mathrm{W}}^{\mathrm{PA}}$ (z)	0.06	−0.75	−0.80 [-0.84, -0.77]

C Supplementary results and model comparisons

C.1 Baseline-gap decomposition and supplementary contrasts

A positive G_{B} indicates greater invalid-advice adoption among baseline-wrong than baseline-correct model–question pairs. This is an outcome-level contrast between baseline-state samples, with interpretation focused on adoption differences rather than a unique behavioral mechanism.

Figure 5 shows equal-weight means of model-specific Hautus estimates. The underlying values are provided in `condition_means.csv` in the supplementary package's `data/appendix_results/` directory.



Figure 5: **Social conditions in two probit spaces. a**, Benefit–harm separation (S_{BH}) versus cross-state adoption criterion (c_{BH}). **b**, Same-state validity discrimination (D_{V}) versus baseline gap (G_{B}). Diagonal lines mark constant $S_{\mathrm{BH}} = D_{\mathrm{V}} + G_{\mathrm{B}}$. Points show equal-weight descriptive means across eight models. Shading and dashed lines are descriptive guides.

The grand conditional baseline gap was $G_{\mathrm{B}} = 0.35$ (95% CI $[0.18, 0.51]$). The omnibus tests for social modification were significant for both D_{V} ($\chi^2(7) = 16.84$, $P = 0.018$) and G_{B} ($\chi^2(7) = 14.24$, $P = 0.047$). Model heterogeneity was present for D_{V} ($\chi^2(7) = 23.46$, $P = 0.001$) and G_{B} ($\chi^2(7) = 22.43$, $P = 0.002$). Table 7 gives the pooled contrasts in S_{BH}, G_{B}, and c_{BH}; Table 5 reports D_{V} and c_{W} on the same conditional scale.

Table 7: Pooled social-factor contrasts from the phrase-adjusted primary model for S_{BH}, G_{B}, and c_{BH}. Estimates are conditional probit-scale effects with pointwise 95% confidence intervals and two-sided Wald P values. The main effects and mandatory-by-supervisor interaction are focal contrasts. The remaining interactions are exploratory.

Contrast	Metric	Estimate [95% CI]	P
Main effects			
Human − AI	ΔG_{B}	$-0.15\ [-0.26, -0.04]$	0.005
	ΔS_{BH}	$-0.06\ [-0.19, 0.06]$	0.314
	Δc_{BH}	$-1.02\ [-1.08, -0.95]$	< 0.001
Supervisor − peer	ΔG_{B}	$-0.01\ [-0.13, 0.10]$	0.855
	ΔS_{BH}	$-0.05\ [-0.18, 0.09]$	0.481
	Δc_{BH}	$-1.39\ [-1.46, -1.33]$	< 0.001
Mandatory − optional	ΔG_{B}	$-0.20\ [-0.35, -0.05]$	0.010
	ΔS_{BH}	$-0.42\ [-0.60, -0.25]$	< 0.001
	Δc_{BH}	$-3.02\ [-3.11, -2.94]$	< 0.001
Interactions			
Human × supervisor	ΔG_{B}	$+0.06\ [-0.15, 0.26]$	0.573
	ΔS_{BH}	$+0.01\ [-0.23, 0.25]$	0.943
	Δc_{BH}	$+0.27\ [0.15, 0.39]$	< 0.001
Human × mandatory	ΔG_{B}	$-0.12\ [-0.33, 0.09]$	0.271
	ΔS_{BH}	$-0.15\ [-0.40, 0.09]$	0.221
	Δc_{BH}	$-0.67\ [-0.79, -0.54]$	< 0.001
Supervisor × mandatory	ΔG_{B}	$-0.15\ [-0.38, 0.08]$	0.194
	ΔS_{BH}	$-0.43\ [-0.69, -0.16]$	0.002
	Δc_{BH}	$-1.34\ [-1.47, -1.21]$	< 0.001
Human × supervisor × mandatory	ΔG_{B}	$-0.13\ [-0.54, 0.28]$	0.528
	ΔS_{BH}	$+0.09\ [-0.39, 0.57]$	0.705
	Δc_{BH}	$+0.26\ [0.02, 0.50]$	0.034

As an equal-weight descriptive check, mandatory wording shifts model-specific D_{V} and S_{BH} contrasts in the negative direction for all eight models (mean $\Delta D_{\mathrm{V}} = -0.18$, descriptive 95% t interval $[-0.28, -0.08]$, and mean $\Delta S_{\mathrm{BH}} = -0.19$, interval $[-0.27, -0.11]$ across models). These equal-weight summaries are descriptive rather than separate hypothesis tests. Human attribution shows the same descriptive direction for S_{BH}, but this contrast is not statistically significant in the pooled GLMM with item random effects. We report this contrast as specification-sensitive secondary evidence.

C.2 Model-specific descriptive S_{BH} and c_{BH} estimates

Figure 6 shows the eight conditions separately for each model in the S_{BH}–c_{BH} and D_{V}–G_{B} planes. Exact values are available in the supplementary data file `stable_subset_observed_sdt_by_model_8conditions.csv` under `data/appendix_results/`.



Figure 6: **Model-specific descriptive locations. Top**, Benefit–harm separation (S_{BH}) versus cross-state adoption criterion (c_{BH}). **Bottom**, Same-state validity discrimination (D_{V}) versus baseline gap (G_{B}). Each model's eight social conditions use its own stable item subset. Between-model differences are descriptive. Pink/green shading denotes permissive/conservative adoption. Dashed lines are reference guides. Bottom diagonals mark constant $S_{\mathrm{BH}} = D_{\mathrm{V}} + G_{\mathrm{B}}$.

Averaging each model's descriptive wording-by-role difference-in-differences in D_{V} equally over human and AI source labels gives contrasts ranging from $+0.31$ for DeepSeek-V4-Pro to -0.63 for GLM-5.2. These are descriptive summaries over model-specific retained item subsets; model-specific GLMM effects are reported separately.

C.3 Unaided Task Performance and Social Responsiveness

We define *unaided task performance* as accuracy averaged over three no-advice runs on the same 650 questions across all eight models. The calculation includes items with inconsistent baseline answers and measures performance on this task under the tested settings. For each model, we average Hautus-corrected D_{V} and c_{W} equally across the eight framing conditions on its primary stable baseline-wrong subset. Mandatory–optional changes average the four matched source–role contrasts and reproduce Table 1.

We evaluate four exploratory Spearman correlations across the eight models, relating unaided accuracy to mean D_{V}, mean c_{W}, ΔD_{V}, and Δc_{W}. Two-sided exact permutation tests enumerate all $8! = 40{,}320$ pairings. Table 1 reports the model-level inputs, and Table 8 reports all four associations. Supplementary Code S4 reproduces the analysis.

Table 8: Exploratory associations with unaided task performance across eight models. All four comparisons use exact two-sided permutation P values.

Outcome	Spearman ρ	Exact P
Mean D_{V}	0.79	0.028
Mean c_{W}	0.67	0.083
ΔD_{V}	−0.33	0.428
Δc_{W}	0.29	0.501

Higher unaided accuracy was associated with greater mean D_{V} ($\rho = 0.79$, $P = 0.028$). This association remained positive in all leave-one-model-out analyses, with ρ ranging from 0.68 to 0.86. The estimated association with mean c_{W} was positive ($\rho = 0.67$), but evidence remained uncertain ($P = 0.083$). Associations with ΔD_{V} ($\rho = -0.33$, $P = 0.428$) and Δc_{W} ($\rho = 0.29$, $P = 0.501$) were also uncertain. These comparisons describe the eight tested models, with adoption metrics conditional on their different retained baseline-wrong subsets.

C.4 Two-condition continuity analysis

Table 9 reports all main effects and interactions among wording, role label, and source label in the secondary A/I_{C} continuity model (33,856 trials). It re-estimates the original S_{BH} and c_{BH} specification on the same A/I_{C} trial rows as the primary model, but with a different conditional specification. The primary model jointly fits the additional I_{W} trials, phrase and phrase-by-wording fixed adjustments, model-specific x_D/x_G effects, and model–item random intercepts with x_D slopes. The secondary model omits I_{W} and instead uses model-specific s slopes, item-level s slopes, and a template random intercept. These coefficients therefore serve as continuity checks, with magnitudes that are not matched to the unified estimates in Appendix C.1. The role/source S_{BH} estimates consequently differ from those of the unified model reported in Section 4.1. We report these effects as specification-sensitive secondary results.

The secondary model codes $s = -0.5$ for I_{C} and $s = +0.5$ for A. For a centered binary social factor $x \in \{-0.5, +0.5\}$, consider

$$\eta(s, x) = \alpha + \beta_s s + \beta_x x + \beta_{sx} sx. \tag{12}$$

The resulting measures and unit-width social contrasts are

$$\begin{aligned} S_{\mathrm{BH}}(x) &= \beta_s + \beta_{sx} x, \quad & c_{\mathrm{BH}}(x) &= -\alpha - \beta_x x, \\ \Delta S_{\mathrm{BH}} &= \beta_{sx}, & \Delta c_{\mathrm{BH}} &= -\beta_x. \end{aligned} \tag{13}$$

The same algebra applies to two-way and three-way social interactions. Terms multiplied by s change S_{BH}. Corresponding terms without s, with their signs reversed, change c_{BH}.

Table 9: Social-factor contrasts in the two-condition continuity model. Effects are conditional probit-scale changes with pointwise 95% Wald confidence intervals. Negative Δc_{BH} indicates a more permissive adoption criterion.

Contrast	Metric	Est. (SE)	95% CI	P
Main effects				
Mandatory − optional	ΔS_{BH}	−0.59 (0.05)	$[-0.69, -0.48]$	< 0.001
	Δc_{BH}	−1.79 (0.03)	$[-1.85, -1.74]$	< 0.001
Supervisor − peer	ΔS_{BH}	−0.19 (0.05)	$[-0.28, -0.10]$	< 0.001
	Δc_{BH}	−0.82 (0.02)	$[-0.86, -0.77]$	< 0.001
Human − AI	ΔS_{BH}	−0.16 (0.05)	$[-0.24, -0.07]$	< 0.001
	Δc_{BH}	−0.59 (0.02)	$[-0.63, -0.54]$	< 0.001
Interactions				
Mandatory × supervisor	ΔS_{BH}	−0.37 (0.09)	$[-0.55, -0.19]$	< 0.001
	Δc_{BH}	−0.88 (0.05)	$[-0.96, -0.79]$	< 0.001
Mandatory × human	ΔS_{BH}	−0.17 (0.09)	$[-0.35, 0.00]$	0.051
	Δc_{BH}	−0.44 (0.04)	$[-0.53, -0.36]$	< 0.001
Supervisor × human	ΔS_{BH}	+0.06 (0.09)	$[-0.11, 0.24]$	0.480
	Δc_{BH}	+0.17 (0.04)	$[0.08, 0.25]$	< 0.001
Mandatory × supervisor × human	ΔS_{BH}	+0.11 (0.18)	$[-0.24, 0.45]$	0.552
	Δc_{BH}	+0.19 (0.09)	$[0.01, 0.36]$	0.036

D Baseline selection and robustness

D.1 Selection induced by baseline-state reliability control

Table 10: Baseline stability and difficulty composition. Stability requires the same selected option in all three no-advice runs. E/M/H denote easy, medium and hard questions. Compositions are percentages within each set. Hard Δ is excluded minus retained, in percentage points. The final column gives the difficulty–retention association test and Cramér's V.

Model	Stable n (%)	Excluded	Stable E/M/H (%)	Excluded E/M/H (%)	Hard Δ (pp)	P / V
Qwen3.7	604 (92.92)	46	43.38/47.35/9.27	43.48/30.43/26.09	+16.82	< 0.001 / 0.15
DS-Pro	548 (84.31)	102	44.16/46.90/8.94	39.22/42.16/18.63	+9.69	0.013 / 0.12
Gemini	515 (79.23)	135	44.08/47.38/8.54	40.74/41.48/17.78	+9.23	0.007 / 0.12
Llama3.1	441 (67.85)	209	44.44/45.80/9.75	41.15/46.89/11.96	+2.21	0.590 / 0.04
Llama4	576 (88.62)	74	45.14/46.35/8.51	29.73/44.59/25.68	+17.17	< 0.001 / 0.18
Mistral	553 (85.08)	97	45.57/45.93/8.50	30.93/47.42/21.65	+13.15	< 0.001 / 0.17
GPT-5.5	458 (70.46)	192	43.01/49.78/7.21	44.27/37.50/18.23	+11.02	< 0.001 / 0.18
GLM-5.2	537 (82.62)	113	44.88/46.93/8.19	36.28/42.48/21.24	+13.05	< 0.001 / 0.16

In total, 4,232 model–question pairs (81.38%) were stable. Model abbreviations are Qwen3.7 (Qwen3.7-Max), DS-Pro (DeepSeek-V4-Pro), Gemini (Gemini-2.5-Flash), Llama3.1 (Llama-3.1-8B-Instruct), Llama4 (Llama-4-Maverick), Mistral (Mistral-Small-3.2-24B-Instruct), GPT-5.5 and GLM-5.2.

The reliability criterion is associated with model–question pair characteristics. Table 10 compares the difficulty composition of each model's retained and excluded sets. For all eight models, the excluded set contains a larger share of hard questions. The increase ranges from 2.21 percentage points for Llama-3.1-8B to 17.17 points for Llama-4-Maverick. Difficulty and retention are associated for seven of eight models, with small-to-moderate Cramér's V values (0.04–0.18).

Table 11 reports the corresponding domain composition. Because our sampled set contains 50 questions per domain, retained/excluded counts are directly comparable across columns. Domain is associated with retention for DeepSeek-V4-Pro ($P = 0.037$, $V = 0.18$), Llama-4-Maverick ($P = 0.034$, $V = 0.19$), Mistral-Small-3.2-24B ($P = 0.024$, $V = 0.19$), and GLM-5.2 ($P = 0.014$, $V = 0.20$),

but not for the other four models (all $P \geq 0.192$). The domains showing the largest local differences vary by model. There is no common domain that is consistently excluded across architectures.

Table 11: Retained stable-baseline items by domain and model. Each domain contributes 50 questions to our sampled set, so the excluded count is $50 - n$ for each retained count n. Model abbreviations follow Table 10.

Domain	Qwen3.7	DS-Pro	Gemini	Llama3.1	Llama4	Mistral	GPT-5.5	GLM-5.2
Agronomy	49	44	42	36	46	45	33	44
Economics	44	41	37	39	37	43	38	41
Education	48	48	41	29	47	45	38	46
Engineering	46	40	39	29	40	36	29	36
History	45	35	40	37	44	42	35	43
Law	49	45	42	31	48	46	40	38
Lit./Arts	46	39	36	38	45	43	30	41
Management	43	45	38	35	45	44	36	41
Medicine	47	44	39	34	46	43	37	44
Military Sci.	47	43	41	38	45	44	38	41
Philosophy	48	42	42	32	47	44	40	47
Science	45	38	38	28	42	34	31	33
Sociology	47	44	40	35	44	44	33	42

This restriction matters for interpretation. Our primary estimates represent social influence among model–question pairs with a reproducible baseline state. Items whose answers vary across nominally deterministic baseline runs require a separate population-level analysis. Unstable baseline states are more frequent among difficult questions, while domain-level selection is weaker and model-specific.

Table 12 assesses how excluding baseline-unstable items changes the pooled correction and regression rates for Qwen3.7-Max. Holding the original prompts, single-baseline coding and advice responses fixed, excluding 46 of the 650 items lowered A from 67.33% to 65.44% and I_{C} from 27.65% to 26.16%, decreases of 1.89 and 1.49 percentage points. The excluded items comprise 30 baseline-wrong and 16 baseline-correct items under this coding. This comparison quantifies the sensitivity of the rate estimates to stability selection in this model.

The table reports baseline coding separately. The single baseline was collected independently of the three stability reruns. Among the 604 retained items, its answer differs from the stable answer on eight items, including six with a different correctness state. Using the triplicate-stable coding on these same items and advice responses gives $A = 64.87\%$ and $I_{\mathrm{C}} = 26.25\%$.

Table 12: Sensitivity of Qwen3.7-Max adoption rates to excluding baseline-unstable items. Rows compare triplicate-stable and single-baseline coding on the retained set, then the retained and full sets under single-baseline coding. All rows use the original prompts and fixed advice responses. Counts aggregate eight social conditions. Denominators are item–condition opportunities for beneficial correction (A) and harmful regression (I_{C}).

Subset	Baseline	Items	A n/N (%)	I_{C} n/N (%)
Stable items	Triplicate	604	1261/1944 (64.87)	758/2888 (26.25)
Stable items	Single	604	1293/1976 (65.44)	747/2856 (26.16)
Full set	Single	650	1492/2216 (67.33)	825/2984 (27.65)

D.2 Difficulty-stratified outcome robustness

We assessed cross-state S_{BH} and c_{BH} effects across difficulty strata by re-estimating the secondary two-condition continuity GLMM separately within easy, medium, and hard questions. Each model included the same centered social-cue effects, model-specific nuisance intercepts and trial-type separation slopes, and item intercepts and separation slopes. These estimates test directional consistency

Table 13: Difficulty-stratified robustness of the cross-state S_{BH} and c_{BH} contrasts. Estimates are conditional probit-scale effects with 95% confidence intervals.

Difficulty	Stable pairs	Mandatory − optional Δc_{BH}	Human − AI Δc_{BH}	Mandatory × supervisor ΔS_{BH}
Easy	1,877	-1.87 $[-1.95, -1.79]$	-0.62 $[-0.69, -0.55]$	-0.41 $[-0.68, -0.13]$
Medium	1,990	-1.85 $[-1.93, -1.78]$	-0.60 $[-0.66, -0.53]$	-0.21 $[-0.47, 0.05]$
Hard	365	-1.47 $[-1.63, -1.31]$	-0.54 $[-0.68, -0.39]$	-0.81 $[-1.39, -0.23]$

across difficulty strata. Effect magnitudes are conditional on this two-condition specification. Table 13 reports the three cross-state contrasts.

All contrasts retain the predicted direction. Mandatory wording and human source labels lower the adoption criterion within every difficulty stratum (all $P < 0.001$). The mandatory-by-supervisor interaction reduces S_{BH} in the easy ($P = 0.004$) and hard ($P = 0.006$) strata, while the medium-stratum interval includes zero ($P = 0.113$).

The mandatory-supervisor reduction in S_{BH} has its largest point estimate and widest interval in the hard stratum, which contains 365 stable model–item pairs. The consistent criterion shifts support robustness among items with reproducible baseline states. The larger hard-item separation estimate is descriptive. Zero template-intercept variances were dropped in the medium and hard strata. All stratum-specific models converged.

D.3 Full-set misleading-cue analysis

The main benefit–harm analysis conditions on a stable no-cue baseline, because beneficial correction and harmful regression require knowing whether the model was initially wrong or correct. A simpler wrong-option adoption analysis does not require this conditioning because it asks whether the model selects the externally suggested wrong option. We therefore report this auxiliary analysis on the complete 650-question set. The baseline rate is the natural no-cue selection rate of the same target distractor. Social rows use all eight misleading-cue conditions. This outcome establishes the direction of social-cue effects on wrong-option adoption over the full set. Criterion changes, validity-discrimination changes, and their combination require the matched stable-baseline design; the stable-subset c_{W} analysis therefore addresses a different estimand.

Table 14: Full-set misleading-cue summary by model. Baseline target-wrong rate is the no-cue selection rate of the designated distractor. Social mean averages the eight misleading-cue conditions. HSM denotes the human-supervisor-mandatory condition. All entries are percentages.

Model	Baseline	Social mean	HSM
Qwen3.7-Max	4.9	35.7	83.1
DeepSeek-V4-Pro	6.3	71.1	97.8
Gemini-2.5-Flash	6.3	49.6	92.6
Llama-3.1-8B	8.0	76.5	98.5
Llama-4-Maverick	6.0	50.0	80.6
Mistral-Small-3.2-24B	8.3	77.0	99.4
GPT-5.5	3.7	20.2	47.8
GLM-5.2	5.7	65.2	99.5

We also fit an auxiliary logit GLMM over the 41,600 social-cue observations using

$$\texttt{targetWrong} \sim \texttt{message} * \texttt{role} * \texttt{source} + \texttt{model} + (1|\texttt{item}) + (1|\texttt{template}).$$

The outcome is whether the model selected the suggested wrong option. The analysis pools observations across all eight models and uses the same centered coding as the main analysis, with model included as a nuisance fixed effect and random intercepts for item and lexical-template combination. Table 16 reports the complete social fixed-effect odds ratios from this auxiliary model. The

Table 15: Full-set target-wrong choices by misleading-cue condition, averaged equally over models. Condition labels abbreviate optional/mandatory as opt./mand. and supervisor as sup.

Condition	Target-wrong (%)	Accuracy (%)
AI peer opt.	32.7	36.1
AI peer mand.	52.7	27.1
AI sup. opt.	39.4	33.2
AI sup. mand.	78.0	13.6
Human peer opt.	39.0	33.2
Human peer mand.	70.6	17.7
Human sup. opt.	45.5	30.5
Human sup. mand.	87.4	8.3

table omits nuisance model coefficients because the auxiliary analysis targets social-cue effects, and stable subsets differ by model in the main outcome analysis. These ORs support comparison with conventional aggregate following-rate analyses. The decomposed quantities in the main text provide the complementary distinction between beneficial and harmful cue use.

Table 16: Auxiliary logit GLMM odds ratios for selecting the suggested wrong option. The model is fit to the full eight-model misleading-cue set. Main effects are equal-weight contrasts. Interaction rows are ratios of odds ratios.

Contrast	OR	95% CI	P
Main effects			
Mandatory vs. optional	24.73	[22.84, 26.77]	< 0.001
Supervisor vs. peer	4.31	[4.03, 4.61]	< 0.001
Human vs. AI	2.82	[2.64, 3.01]	< 0.001
Interactions			
Mandatory $\times$ supervisor	5.47	[4.81, 6.22]	< 0.001
Mandatory $\times$ human	2.49	[2.19, 2.83]	< 0.001
Supervisor $\times$ human	0.82	[0.72, 0.93]	0.002
Mandatory $\times$ supervisor $\times$ human	0.75	[0.58, 0.96]	0.023

The auxiliary logit model reproduces the raw wrong-option adoption pattern, with selection of the wrong option increasing sharply under mandatory wording, supervisor labels, and human-source labels. It also shows that mandatory wording is especially strong when paired with supervisor status and, separately, with a human-source label. The supervisor-by-human and three-way interactions attenuate these combined increases (odds-ratio ratios below one). These are contrasts in wrong-option adoption odds, separate from the criterion contrasts in the three-condition primary model.

E LEXICAL SENSITIVITY

Pooling optional and mandatory sentences under a shared template index obscures the different sentences used at the two wording levels. We therefore ran four separate three-level comparisons involving coworker/teammate/colleague within peer conditions, supervisor/lead/manager within supervisor conditions, might choose/might want/might consider within optional conditions, and must choose/required/need to choose within mandatory conditions. Each family is evaluated separately for valid advice on baseline-wrong items (A), invalid advice on the same baseline-wrong items (I_{W}), and invalid advice on baseline-correct items (I_{C}).

Wilson intervals and Pearson tests describe the pooled rates. Role-label variants are checked within peer and supervisor conditions using trial-type-specific logit GLMMs with model and the remaining social factors as controls and random intercepts for model–item and item. Sentence phrasing is already included in the primary model (Equation 3) through the four fixed coefficients contributed by `phr` and `phr:message`. Their simple effects give separate two-degree-of-freedom tests for

the optional and mandatory families. Because the primary model does not include $x_D/x_G \times \texttt{phr}$ terms, these phrase effects are interpreted as common nuisance shifts in adoption across A, I_{W}, and I_{C}, rather than as trial-type-specific effects. We treat the three deliberately constructed, exhaustive, and balanced phrase levels as fixed rather than estimate a variance component from only three levels (Harrison et al., 2018; Oberpriller et al., 2022). Individual coefficients are not interpreted.

Table 17: Lexical-sensitivity adoption rates and omnibus tests. Rate cells report percent adoption [Wilson 95% CI]. Pearson rows give $\chi^2(2)$/Cramér's V by trial type. Model-test rows give $\chi^2(2)$ and P.

Family	Level	A	I_{W}	I_{C}
Role labels				
Peer role label	coworker	73.09 [71.41, 74.71]	47.87 [46.02, 49.73]	34.58 [32.84, 36.37]
	teammate	74.69 [73.08, 76.24]	51.21 [49.39, 53.02]	37.59 [35.81, 39.41]
	colleague	74.73 [73.13, 76.26]	54.74 [52.94, 56.52]	32.64 [30.91, 34.42]
	Pearson χ^2/V	2.58/0.02	27.01/0.06	15.12/0.04
	GLMM χ^2 [P]	1.47 [0.481]	4.52 [0.105]	3.15 [0.207]
Supervisor role label	supervisor	84.26 [82.86, 85.57]	65.17 [63.37, 66.92]	51.66 [49.80, 53.51]
	lead	82.78 [81.37, 84.11]	64.84 [63.09, 66.56]	52.09 [50.23, 53.94]
	manager	83.39 [82.00, 84.69]	68.27 [66.57, 69.92]	48.39 [46.52, 50.27]
	Pearson χ^2/V	2.26/0.02	9.33/0.03	8.98/0.03
	GLMM χ^2 [P]	1.66 [0.436]	1.37 [0.505]	0.85 [0.654]
Wording templates				
Optional sentence	might choose	62.23 [60.40, 64.02]	34.07 [32.32, 35.86]	18.39 [17.00, 19.86]
	might want	69.18 [67.54, 70.76]	46.52 [44.79, 48.26]	29.03 [27.29, 30.84]
	might consider	72.28 [70.57, 73.93]	39.89 [38.06, 41.74]	25.81 [24.27, 27.42]
	Pearson χ^2/V	67.02/0.09	95.22/0.11	88.02/0.10
	Common Wald test ($\chi^2(2) = 17.97$, $P < 0.001$).			
Mandatory sentence	must choose	89.30 [88.09, 90.40]	78.16 [76.58, 79.66]	59.97 [58.15, 61.76]
	required	90.25 [89.17, 91.24]	81.01 [79.61, 82.34]	67.21 [65.35, 69.02]
	need	89.52 [88.31, 90.62]	71.18 [69.45, 72.85]	57.91 [56.12, 59.67]
	Pearson χ^2/V	1.63/0.01	82.91/0.10	53.39/0.08
	Common Wald test ($\chi^2(2) = 13.95$, $P < 0.001$).			

Neither peer nor supervisor role-label variants have a statistically significant omnibus effect on adoption within any trial type (all $P \geq 0.105$), and all pooled role-label effect sizes are small (maximum $V = 0.06$). Sentence phrasing matters more. Descriptively, optional phrase rates vary across all three trial types ($V = 0.09$–0.11), with "might want" and "might consider" more permissive than "might choose." Tests of the primary model's four phrase coefficients indicate a common phrase effect within both the optional ($\chi^2(2) = 17.97$, $P < 0.001$) and mandatory ($\chi^2(2) = 13.95$, $P < 0.001$) families. Descriptively, "required" produces the highest invalid-cue adoption, whereas "need" is lower. The primary model represents phrasing as a common nuisance effect across A, I_{W}, and I_{C}. These differences within each wording level qualify claims about any single sentence, while all three mandatory variants have substantially higher invalid-cue adoption than the optional variants in Table 17.

F Paired intervention analyses

Each intervention analysis retains questions with the same answer across three baseline runs within each setting and the same correctness state across the reference and intervention settings. Table 18 gives the paired sample sizes. Valid and invalid advice use the same baseline-wrong questions. Item pairs share an invalid-advice target across settings and consistent non-target prompt text across advice branches within each setting.

All settings used temperature 0. Thinking enabled DeepSeek's native reasoning mode and used a 4,096-token thinking budget for Qwen and Gemini. Reference and persona settings disabled thinking.

All changes subtract the reference from the intervention. Non-boundary contrasts use Hautus-corrected rates and 10,000 paired item bootstrap replicates for pointwise 95% confidence intervals and two-sided P values. Resampling is stratified by baseline correctness, retaining each item's reference/intervention A/I_{W} responses or paired I_{C} responses together.

If any component count used by a metric is $0/n$ or n/n in either setting, we instead report a paired Bayesian posterior median and 95% credible interval. This count-based rule affects eight of the 72 displayed contrasts. A $^{\bullet}$ marks a credible interval excluding zero. Bootstrap tests retain stars. An em dash in a P column identifies Bayesian inference. Both analyses are pointwise. Tables 19–21 report the effects in Figure 4. Appendix F.1 and Supplementary Code S5 give the boundary method and full-grid sensitivity checks.

For thinking under AI-peer optional framing, ΔG_{B} was $+0.29$ (95% CI $[-0.19, 0.75]$) for DeepSeek, $+0.43$ (95% CI $[-0.15, 1.12]$) for Qwen, and $+0.36$ (95% CI $[-0.06, 0.80]$) for Gemini. The corresponding ΔD_{V} point estimates were also positive, but all three 95% confidence intervals spanned zero. The ΔG_{B} changes describe behavioral differences across baseline-state samples. The identity $\Delta S_{\mathrm{BH}} = \Delta D_{\mathrm{V}} + \Delta G_{\mathrm{B}}$ holds in each paired bootstrap replicate, so the interval for the sum incorporates the covariance between its components. A positive interval for the sum is therefore compatible with both component intervals spanning zero.

Table 18: Matched items in each intervention analysis. BW and BC denote baseline-wrong and baseline-correct items, respectively. Counts refer to the paired samples used in all four intervention metrics.

Model	Intervention	BW	BC	Total
DeepSeek-V4-Pro	Thinking	94	207	301
	Persona	166	172	338
Qwen3.7-Max	Thinking	92	321	413
	Persona	193	345	538
Gemini-2.5-Flash	Thinking	150	205	355
	Persona	221	216	437

Table 19: Same-state effects of thinking-enabled decoding. Entries give changes and pointwise 95% intervals. P gives two-sided paired-bootstrap tests. An em dash identifies Bayesian posterior medians and credible intervals for boundary contrasts. $^{\bullet}$ marks a credible interval excluding zero (Appendix F.1). Labels abbreviate optional/mandatory as opt./mand. and supervisor as sup.

Condition	ΔD_{V} [95% interval]	P	Δc_{W} [95% interval]	P
DeepSeek-V4-Pro				
AI peer opt.	$+0.22\ [-0.18, 0.68]$	0.281	$+0.65\ [0.41, 0.91]$	< 0.001
Human peer mand.	$+0.45\ [-0.04, 0.88]$	0.072	$+0.94\ [0.64, 1.34]$	< 0.001
Human sup. mand.	$+0.87\ [-0.27, 2.60]$	—	$-0.13\ [-0.95, 0.39]$	—
Qwen3.7-Max				
AI peer opt.	$+0.25\ [-0.25, 0.79]$	0.328	$-0.13\ [-0.45, 0.18]$	0.416
Human peer mand.	$-0.29\ [-0.69, 0.10]$	0.139	$-0.29\ [-0.53, -0.06]$	0.014
Human sup. mand.	$-0.60\ [-1.54, 0.21]$	0.152	$-0.66\ [-1.03, -0.39]$	< 0.001
Gemini-2.5-Flash				
AI peer opt.	$+0.19\ [-0.19, 0.55]$	0.334	$-0.78\ [-1.01, -0.59]$	< 0.001
Human peer mand.	$+0.07\ [-0.37, 0.61]$	0.728	$-1.31\ [-1.75, -1.00]$	< 0.001
Human sup. mand.	$-0.60\ [-2.11, 0.90]$	—	$-1.38^{\bullet}\ [-2.60, -0.59]$	—

Table 20: Same-state effects of the empowered-persona prompt. Estimates, interval types and P values follow Table 19.

Condition	ΔD_{V} [95% interval]	P	Δc_{W} [95% interval]	P
DeepSeek-V4-Pro				
AI peer opt.	$-0.02\ [-0.27, 0.25]$	0.914	$+0.72\ [0.57, 0.90]$	< 0.001
Human peer mand.	$+0.54\ [0.11, 0.92]$	0.020	$+1.27\ [1.05, 1.61]$	< 0.001
Human sup. mand.	$+0.21\ [-0.46, 0.86]$	0.635	$+1.07\ [0.84, 1.42]$	< 0.001
Qwen3.7-Max				
AI peer opt.	$+0.05\ [-0.15, 0.27]$	0.639	$+0.25\ [0.13, 0.38]$	< 0.001
Human peer mand.	$-0.07\ [-0.38, 0.26]$	0.689	$+1.27\ [1.11, 1.46]$	< 0.001
Human sup. mand.	$+0.10\ [-0.47, 0.51]$	0.703	$+2.24\ [2.01, 2.58]$	< 0.001
Gemini-2.5-Flash				
AI peer opt.	$-0.14\ [-0.37, 0.10]$	0.252	$+0.20\ [0.08, 0.34]$	0.002
Human peer mand.	$+0.18\ [-0.08, 0.44]$	0.177	$+1.18\ [1.02, 1.35]$	< 0.001
Human sup. mand.	$+0.42\ [0.06, 0.76]$	0.025	$+1.35\ [1.15, 1.60]$	< 0.001

Table 21: Cross-state intervention effects on the same paired item cohorts as Tables 19 and 20. Estimates, intervals and P values follow the conventions in Table 19.

Intervention	Condition	ΔS_{BH} [95% interval]	P	Δc_{BH} [95% interval]	P
DeepSeek-V4-Pro					
Thinking	AI peer opt.	$+0.51\ [0.14, 0.93]$	0.007	$+0.79\ [0.60, 1.01]$	< 0.001
	Human peer mand.	$+0.65\ [0.07, 1.12]$	0.033	$+1.04\ [0.81, 1.34]$	< 0.001
	Human sup. mand.	$+0.74\ [-0.30, 2.41]$	—	$-0.18\ [-1.01, 0.34]$	—
Persona	AI peer opt.	$-0.33\ [-0.64, -0.02]$	0.037	$+0.57\ [0.42, 0.73]$	< 0.001
	Human peer mand.	$+0.19\ [-0.32, 0.58]$	0.429	$+1.10\ [0.91, 1.36]$	< 0.001
	Human sup. mand.	$+0.47\ [-0.14, 1.03]$	0.182	$+1.20\ [0.96, 1.54]$	< 0.001
Qwen3.7-Max					
Thinking	AI peer opt.	$+0.68\ [0.21, 1.28]$	0.006	$+0.09\ [-0.16, 0.38]$	0.466
	Human peer mand.	$+0.15\ [-0.21, 0.53]$	0.408	$-0.07\ [-0.25, 0.11]$	0.478
	Human sup. mand.	$-0.79\ [-1.31, -0.17]$	0.010	$-0.76\ [-1.08, -0.51]$	< 0.001
Persona	AI peer opt.	$-0.22\ [-0.47, 0.02]$	0.076	$+0.11\ [-0.01, 0.24]$	0.081
	Human peer mand.	$-0.22\ [-0.52, 0.10]$	0.162	$+1.20\ [1.06, 1.36]$	< 0.001
	Human sup. mand.	$-0.09\ [-0.67, 0.31]$	0.631	$+2.15\ [1.96, 2.44]$	< 0.001
Gemini-2.5-Flash					
Thinking	AI peer opt.	$+0.55\ [0.15, 0.94]$	0.007	$-0.60\ [-0.81, -0.42]$	< 0.001
	Human peer mand.	$-0.04\ [-0.60, 0.58]$	0.993	$-1.36\ [-1.70, -1.12]$	< 0.001
	Human sup. mand.	$-0.93\ [-2.66, 0.83]$	—	$-1.55^{\bullet}\ [-2.57, -0.88]$	—
Persona	AI peer opt.	$-0.01\ [-0.38, 0.44]$	0.996	$+0.27\ [0.08, 0.49]$	0.005
	Human peer mand.	$+0.06\ [-0.24, 0.35]$	0.687	$+1.11\ [0.98, 1.27]$	< 0.001
	Human sup. mand.	$+0.44\ [0.03, 0.79]$	0.034	$+1.36\ [1.20, 1.57]$	< 0.001

Table 22 reports uncorrected adoption rates on the same matched samples. Each reference row uses the items retained for its corresponding intervention, making changes in beneficial correction and same-state invalid following directly visible.

Table 22: **Observed adoption rates before and after each intervention.** Rates are uncorrected percentages. Every reference/intervention pair uses the same matched items for that intervention and model. Reference rows are recomputed on these subsets. Thinking and persona have different matched samples. Beneficial correction (A) and same-state invalid following (I_{W}) use n_{W} baseline-wrong pairs. Harmful regression (I_{C}) uses n_{C} baseline-correct pairs. Labels abbreviate optional/mandatory as opt./mand. and supervisor as sup.

Framing	Setting	n_{W}	A (%)	I_{W} (%)	n_{C}	I_{C} (%)
DeepSeek-V4-Pro / Thinking						
AI peer opt.	Reference	94	62.77	31.91	207	28.99
	Intervention	94	41.49	10.64	207	5.31
Human peer mand.	Reference	94	94.68	91.49	207	84.06
	Intervention	94	80.85	57.45	207	35.27
Human sup. mand.	Reference	94	98.94	94.68	207	94.69
	Intervention	94	100.00	90.43	207	92.27
DeepSeek-V4-Pro / Empowered persona						
AI peer opt.	Reference	166	74.10	41.57	172	23.26
	Intervention	166	46.39	17.47	172	12.79
Human peer mand.	Reference	166	96.99	93.37	172	83.72
	Intervention	166	80.12	47.59	172	41.28
Human sup. mand.	Reference	166	99.40	96.99	172	95.35
	Intervention	166	92.17	74.70	172	58.72
Qwen3.7-Max / Thinking						
AI peer opt.	Reference	92	25.00	7.61	321	3.74
	Intervention	92	33.70	7.61	321	1.25
Human peer mand.	Reference	92	75.00	39.13	321	30.22
	Intervention	92	79.35	56.52	321	29.91
Human sup. mand.	Reference	92	96.74	83.70	321	74.45
	Intervention	92	98.91	97.83	321	96.57
Qwen3.7-Max / Empowered persona						
AI peer opt.	Reference	193	39.90	10.36	345	4.93
	Intervention	193	31.61	6.22	345	4.93
Human peer mand.	Reference	193	81.87	47.15	345	32.75
	Intervention	193	34.20	9.33	345	6.09
Human sup. mand.	Reference	193	97.93	86.53	345	76.23
	Intervention	193	41.97	11.40	345	8.12
Gemini-2.5-Flash / Thinking						
AI peer opt.	Reference	150	31.33	8.00	205	7.32
	Intervention	150	65.33	24.00	205	13.17
Human peer mand.	Reference	150	84.00	70.00	205	61.95
	Intervention	150	99.33	96.67	205	95.61
Human sup. mand.	Reference	150	97.33	90.67	205	86.34
	Intervention	150	100.00	100.00	205	100.00
Gemini-2.5-Flash / Empowered persona						
AI peer opt.	Reference	221	38.46	13.12	216	5.09
	Intervention	221	28.51	10.41	216	2.78
Human peer mand.	Reference	221	86.88	74.66	216	59.26
	Intervention	221	51.13	27.15	216	18.06
Human sup. mand.	Reference	221	95.93	92.76	216	84.72
	Intervention	221	71.95	45.25	216	28.70

F.1 BOUNDARY INFERENCE AND FULL-GRID BAYESIAN SENSITIVITY

We model paired binary responses using a Dirichlet–multinomial construction for correlated proportions (Westphal, 2019). Baseline-wrong items have 16 reference/intervention A/I_{W} patterns. Baseline-correct items have four paired I_{C} patterns. Items are exchangeable within each stratum, and strata are independent. Joint patterns retain within-item pairing. This model supplies the boundary estimates and a sensitivity analysis of all 18 model–intervention–condition combinations.

For a stratum with J patterns, counts n_j, and pattern probabilities π_j, we use a symmetric prior and its conjugate posterior,

$$\boldsymbol{\pi} \sim \mathrm{Dirichlet}\left(\tfrac{2a}{J}\mathbf{1}\right), \qquad \boldsymbol{\pi} \mid \boldsymbol{n} \sim \mathrm{Dirichlet}\left(\boldsymbol{n} + \tfrac{2a}{J}\mathbf{1}\right). \tag{14}$$

Marginalizing over patterns gives a $\mathrm{Beta}(a, a)$ prior for each adoption probability. We use $a = 0.5$ for reporting and $a \in \{0.25, 1\}$ for sensitivity checks. At $a = 0.5$, the marginal posterior mean is the Hautus-corrected rate $(k + 0.5)/(n + 1)$. The joint prior is not the multinomial Jeffreys prior. We draw 200,000 independent posterior samples for each analysis and prior (seed 20260922) and compute the probit metrics and contrasts within each draw. Reported posterior medians of nonlinear contrasts need not equal differences of marginal medians or the original Hautus plug-in contrasts.

A positive prior concentration gives unobserved response patterns nonzero posterior mass, so complete-adoption branches retain uncertainty. In the human-supervisor mandatory thinking condition, DeepSeek adopted valid advice on 94/94 items, and Gemini adopted both advice types on 150/150 baseline-wrong items and invalid advice on 205/205 baseline-correct items. All their contrasts use the same model. Gemini's intervention D_{V} has a posterior median near zero with a 95% credible interval of $[-1.47, 1.47]$. Complete observed adoption leaves the discrimination estimate prior-dependent, with the 95% credible interval spanning zero.

Table 23: Prior sensitivity for thinking under human-supervisor mandatory framing. Entries are pointwise 95% credible intervals under $\mathrm{Beta}(a, a)$ marginal priors. DeepSeek and Gemini have complete-adoption branches. Qwen illustrates a non-boundary contrast whose interval crosses zero under only some priors. $^{\bullet}$ indicates an interval excluding zero.

Metric	$a = 0.25$	$a = 0.5$	$a = 1$
DeepSeek-V4-Pro			
ΔD_{V}	$[-0.16, 3.91]$	$[-0.27, 2.60]$	$[-0.32, 1.80]$
Δc_{W}	$[-1.60, 0.34]$	$[-0.95, 0.39]$	$[-0.56, 0.40]$
ΔS_{BH}	$[-0.19, 3.72]$	$[-0.30, 2.41]$	$[-0.33, 1.60]$
Δc_{BH}	$[-1.67, 0.29]$	$[-1.01, 0.34]$	$[-0.62, 0.35]$
Gemini-2.5-Flash			
ΔD_{V}	$[-3.00, 1.74]$	$[-2.11, 0.90]$	$[-1.58, 0.44]$
Δc_{W}	$[-3.80, -0.74]^{\bullet}$	$[-2.60, -0.59]^{\bullet}$	$[-1.83, -0.46]^{\bullet}$
ΔS_{BH}	$[-3.64, 1.77]$	$[-2.66, 0.83]$	$[-2.06, 0.29]$
Δc_{BH}	$[-3.66, -1.08]^{\bullet}$	$[-2.57, -0.88]^{\bullet}$	$[-1.87, -0.71]^{\bullet}$
Qwen3.7-Max			
ΔS_{BH}	$[-1.28, 0.18]$	$[-1.32, 0.05]$	$[-1.37, -0.10]^{\bullet}$

Table 23 shows prior-dependent interval widths at the boundaries. Across the three priors, Gemini's criterion decreases have intervals below zero. Its separation changes and DeepSeek's four changes remain uncertain. Within the full-grid Bayesian analysis, the zero-exclusion decision is unchanged across priors for 71 of the 72 displayed contrasts.

Non-boundary cells can also be sensitive. For Qwen thinking under human-supervisor mandatory framing, valid-advice adoption reaches 91/92. Its ΔS_{BH} has a bootstrap CI of $[-1.31, -0.17]$, but the $a = 0.5$ Bayesian credible interval is $[-1.32, 0.05]$. The Bayesian interval also changes its zero-exclusion decision across priors (Table 23). This contrast is therefore method-sensitive. The other 63 non-boundary contrasts in Figure 4 agree in whether their bootstrap CI and $a = 0.5$ credible interval exclude zero. In the supplementary G_{B} results, DeepSeek persona under AI-peer optional framing also changes this decision near zero. Full results and diagnostics are archived in Supplementary Code S5. The reporting method is never selected by significance.