ROBOPHYS: BEYOND OUTCOMES, TOWARD PHYSICALLY CORRECT EXECUTION OF LLM-GENERATED ROBOTIC PROGRAMS

Anonymous authors
Paper under double-blind review

ABSTRACT

Large language models (LLMs) are increasingly used to generate executable programs for robotic systems. As generated code moves from purely digital environments to embodied systems, however, conventional notions of correctness become insufficient. Existing code-generation benchmarks primarily measure *functional correctness*, considering a program correct if it executes successfully and passes functional tests. Yet robotic programs must also satisfy constraints imposed by physical execution. To capture this requirement, we formalize *physical correctness* as a distinct evaluation dimension that measures whether a program respects physical constraints throughout its execution in the environment. Importantly, outcome correctness does not necessarily imply physical correctness: a program may complete the intended task while violating physical constraints during execution. We introduce ROBOPHYS, an evaluation protocol that augments functional testing with physical execution constraints. ROBOPHYS identifies LLM-generated programs that satisfy terminal task predicates, then re-executes them under diverse physical conditions while monitoring constraint violations throughout their trajectories. Across five code-generation systems and 300 generated robot programs, 38 of the 136 nominal functional successes incurred at least one physical violation (27.9%). Trajectory audits guide task-conditioned repairs that restore task completion without executed violations or rejected hazardous requests in 42 of 57 initially unsafe-success program-scene cases. Cross-stage regressions motivate complete-execution revalidation and identify state-aware, task-agnostic repair as a direction for further study. These findings expose a blind spot in outcome-only evaluation, demonstrate the value of execution-level diagnosis for repair, and support evaluating physical execution correctness alongside task completion in generated robot programs.

1 INTRODUCTION

Large language models (LLMs) are increasingly used to generate executable programs for robotic systems (Liang et al., 2023; Singh et al., 2023; Huang et al., 2023a; Fu et al., 2026). As generated code moves from digital environments to embodied systems, however, correctness can no longer be judged solely by whether a program reaches the expected final outcome. A robotic program must also execute correctly throughout its interaction with the physical environment (Kim et al., 2026; Huang et al., 2026).

Functional-test-based code-generation evaluation is outcome-oriented: a program is considered functionally correct under the specified tests if it executes successfully and passes those tests (Chen et al., 2021; Austin et al., 2021; Liu et al., 2023). While natural for conventional software, this criterion alone can be misleading for robotic programs. A robot may eventually place an object at the correct location while colliding with its surroundings, exceeding motion constraints, or temporarily losing its grasp during execution. Such a program achieves the expected outcome but follows a physically invalid trajectory.

We therefore argue that robotic program correctness should capture not only *what outcome is achieved*, but also *how that outcome is achieved*. We distinguish *outcome correctness*, which mea-

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

sures whether the intended task is completed, from *physical execution correctness*, which measures whether physical constraints are respected throughout the execution trajectory. A correct final outcome does not necessarily imply a correct physical execution.

> *For robotic programs, should correctness be determined only by the final outcome, or by whether the entire execution is physically correct?*

Outcome-based evaluation cannot fully answer this question for three reasons. First, *terminal oracles* can miss transient violations that disappear before the final state (Kim et al., 2026; Liu et al., 2026; Huang et al., 2026). Second, *task predicates do not necessarily encode physical constraints*, such as collision avoidance, motion limits, or grasp retention (Obi et al., 2026; Huang et al., 2026). Third, *physical validity depends on the environment*, so nominal execution does not establish correctness under changing physical conditions (Li et al., 2026). Consequently, functional success provides evidence of task completion, but not of physically correct execution.

Evaluating physical execution correctness requires monitoring the entire trajectory independently of the final task outcome and examining programs under diverse physical conditions. Our key insight is therefore to use complementary oracles: terminal predicates determine *what* the robot accomplishes, while trajectory-level monitors determine *how* it accomplishes it. This complements final-state correctness with execution-level correctness.

Based on this insight, we introduce RoboPhys, an evaluation benchmark and protocol for assessing the physical execution correctness of LLM-generated robotic programs. RoboPhys first identifies programs that achieve the expected task outcomes, then re-executes them under diverse physical conditions while monitoring physical constraints throughout execution. Rather than treating functional success as the final verdict, RoboPhys uses it as the starting point for evaluating whether the execution itself is physically correct.

We evaluate RoboPhys across five code-generation systems and 300 generated robotic programs. Among 136 programs that passed nominal functional tests, 38 (27.9%) exhibited at least one physical violation during execution. Thus, more than one in four programs with correct final outcomes were physically incorrect during execution. We further analyze these violations and use the identified mechanisms to guide targeted repair, restoring strict success in 42 of 57 initially unsafe-success program–scene cases. Strict success requires task completion without executed physical violations or rejected hazardous requests.

Our results expose a fundamental blind spot in outcome-oriented evaluation and motivate treating *physically correct execution* as a first-class criterion for LLM-generated robotic programs.

Our contributions are summarized as follows:

- **Execution-Centric Correctness.** We show that correct final outcomes do not necessarily imply physically correct execution and formulate physical execution correctness as a distinct criterion for robotic programs.
- **RoboPhys.** We introduce RoboPhys, an evaluation protocol that complements terminal task predicates with trajectory-level physical monitoring under diverse physical conditions.
- **Empirical Study.** Across five code-generation systems and 300 programs, we find physical violations in 38 of 136 nominally functionally successful programs and show that trajectory-level diagnoses can guide effective repair.

2 Background and Related Work

2.1 LLM-Generated Robot Programs

LLM code generation. Large language models translate natural-language specifications into executable programs. HumanEval and MBPP assess functional correctness using tests (Chen et al., 2021; Austin et al., 2021); EvalPlus expands test coverage to expose previously missed errors (Liu et al., 2023).

Table 1: **Evaluation roles in related work.** Categories summarize principal evidence and objectives; a method may serve multiple roles.

Role	Representative work	Evidence and objective
Functional evaluation	HumanEval, MBPP, EvalPlus	Tests → functional verdict
Robot-program evaluation	RoboEval, CaP-X	Traces/task outcomes → program performance
Diagnosis and repair	RoboCritics	Motion defects → revision feedback
Safety enforcement	SafeGate, RoboGuard	Proposed actions/plans → constraint checks
Execution-quality evaluation	SafeManip, Eval-Actions, LIBERO-Safety, ForesightSafety-VLA	Rollouts → temporal safety or execution quality
RoboPhys	Functionally successful generated programs	(F, A, L) → mechanism audit → repair validation

Robot program generation. Code as Policies and ProgPrompt generate programs combining perception, reasoning, and robot-control primitives (Liang et al., 2023; Singh et al., 2023). Instruct2Act maps multimodal instructions to actions, and VoxPoser constructs spatial value maps for motion planning (Huang et al., 2023a;b). CaP-X evaluates coding agents for manipulation (Fu et al., 2026), while RoboEval checks task-specific temporal properties of execution traces (Hu et al., 2024). Unlike software that only returns outputs, robot programs realize their goals through physical trajectories and interactions.

2.2 Robotic Security and Safety

RoboCritics uses expert-informed motion critics to detect speed violations, collisions, and unsafe configurations, returning structured feedback for user-guided program revision (Kim et al., 2026). SafeGate and RoboGuard check proposed actions or plans against task contracts and safety constraints (Obi et al., 2026; Ravichandran et al., 2026). ForesightSafety-VLA, LIBERO-Safety, and Eval-Actions evaluate safety or execution quality beyond task success (Lyu et al., 2026; Cui et al., 2026; Liu et al., 2026). SafeManip monitors temporal safety properties, including grasp and release stability, separately from task completion (Huang et al., 2026).

RoboPhys focuses on functionally successful generated programs. It freezes source code across physical conditions, audits recurring failure mechanisms, and tests diagnosis-guided repairs through complete re-execution. This connects conditional gap measurement to actionable diagnosis and exposes downstream failures after local repair.

2.3 Outcome and Physical Correctness

For program p in scene e, the functional oracle $F(p, e)$ checks normal termination and terminal task predicates, including release and stable placement. Outcome correctness and executed physical correctness are defined as

$$O(p, e) = F(p, e), \qquad P_{\text{exec}}(p, e) = \mathbf{1}[A(p, e) = 0], \tag{1}$$

where A records monitored physical violations. An *unsafe success* ($F = 1, A = 1$) completes the task through a physically incorrect process. Rejected hazardous requests are recorded separately as L. These verdicts distinguish task completion, executed violations, and protective blocking under the declared constraints (Section 3.1). Table 1 groups related work by its principal evaluation role; the categories can overlap.

3 RoboPhys Design

RoboPhys combines parameterized tasks, a shared execution stack, and separate outcome and physical monitors. Figure 1 summarizes qualification, frozen-program testing, trajectory diagnosis, and repair validation.



Figure 1: **RoboPhys overview.** Nominal audit qualifies 92 strict programs for nine random and nine targeted tests per program. An expanded audit covers 633 violating runs. Researcher-guided repair and complete re-execution recover 42 of 57 unsafe-success program–scene cases from 54 sources. Mechanism diagrams are schematic.

Table 2: **Physical constraints.** Limits are manufacturer-specified (M), task-defined (T), or benchmark-defined (B). Exact event logic is in Appendix A.

Constraint	Quantity and rule	Source
Motion	$\lvert\dot{q}_j\rvert$: 2.175 / 2.610 rad/s for J1–4 / J5–7; $\lVert v_{\mathrm{EE}}\rVert$: 1.7 m/s	M+B
Contact/workspace	Allowed contact pairs $\mathcal{C}_{\mathrm{allow}}$; restricted-region penetration tolerance: 1 mm	T+B
Grasp retention	Relative-pose slip thresholds: 15 mm / 0.20 rad; sustained contact loss and drop	B
Release/order	Release-region predicate $R(s_t, h_t)$; grasp verification before transport	T+B
Protected objects	Bystander horizontal displacement $d_b(t) \leq 15$ mm	T+B

3.1 Task Construction and Coverage

Six tasks cover three complementary demands: transporting a held object, placing it on a support, and inserting and releasing it inside a container. Each combines a natural-language goal, parameterized geometry, permitted-interaction rules, and terminal predicates. All use a Panda robot, a 50-mm cube, and the same public API. This shared setup supports comparison of execution constraints across manipulation stages (Figure 2).

Prompts and paired tasks. A fixed prompt template specifies the task, API, coordinate conventions, safety requirements, and a Python `run(api)` output. Geometry comes from runtime observations; held-out settings and detector thresholds are withheld. A1/A2 vary obstacle and restricted-space constraints during transfer. B1/B2 vary support footprint and height, probing placement clearance and grasp retention while protecting a bystander. C1/C2 vary container opening and wall height, separating payload entry from clearance for finger opening. Appendix A.1 gives the exact geometry and prompt components.

Physical rules. Manufacturer specifications supply motion limits (Franka Robotics, 2026); task geometry defines allowed contacts and regions; benchmark thresholds operationalize slip, release, and disturbance. Table 2 summarizes the monitored quantities. Appendix A specifies event triggers, tolerances, persistence, and evidence sources.



Figure 2: **Task goals and process constraints.** Insets show support tops and container inner openings. Red dashed squares indicate the 50-mm payload; gray solid/dashed fingers schematically show closed/open configurations. Dashed arrows denote direct-transfer references, and green markers visualize targets without collision geometry.

3.2 Execution Stack and Physical Conditions

Programs observe scenes, objects, and targets; request checked Cartesian motion; operate the gripper; query grasp state; or abort. The shared stack handles IK, timing, candidate checks,and actuation in MuJoCo (Todorov et al., 2012). Grasping uses sustained bilateral finger contact, so retention, slip, and release evolve through dynamics. All programs share the hand orientation and controller.

Each task has one nominal, nine seeded random, and nine targeted scenes. Random tests perturb horizontal object and fixture positions. Targeted tests vary three family-specific factors at three fixed levels: transfer clearance/grasp conditions, support/bystander/friction conditions, or container opening/obstacle/depth. Task instructions remain fixed. The 114 configurations and seeds were frozen before inspecting formal outcomes; Appendix C.1 lists their values.

3.3 Outcome and Physical Evaluation

F requires normal termination, release, valid placement, and a final 0.30-s stable window. A records monitored violations, while L records hazardous requests rejected by motion prechecking. Read-only monitors cover the complete execution, including settling; terminal predicates determine F separately from the violation log. Strict success requires $F = 1, A = 0, L = 0$.

Contact and speed events use simulated states; ordering monitors use action logs (Appendix A.4). A scene-aware reference controller satisfies task and process criteria in all 114 configurations using internal scene/grasp information, providing a feasibility check. Separate controls exercise speed, collision, restricted-entry, and drop monitors. Appendix A details these checks and the terminal predicates.

4 Experiments and Results

4.1 Experimental Setup

LLMs. We evaluate five generation conditions, each producing ten programs for each of the six tasks, for 300 programs in total. Four conditions use stateless API calls—Gemini 3 Flash Preview, DeepSeek V4 Pro, GLM-5.1 with thinking disabled, and GPT-5.6-Terra—and one uses a Codex agent with `gpt-5.6-sol` and high reasoning. Stateless calls receive identical task/API contracts

Table 3: **Functional success and physical violations across generation conditions and evaluation cohorts.** Panel A reports nominal program counts and held-out detections among each condition's strict set $\mathcal{Q}$; each condition generates 60 responses. Held-out detections mean at least one event across 18 scenes. Panel B reports execution counts, with source counts shown separately. $F \wedge A$ denotes unsafe success. The panels describe overlapping populations and are not additive.

A. Generation conditions: program-level outcomes

	Nominal				Held-out, $\mathcal{Q}$	
Condition	Contract	F	$F \wedge A$	$\lvert\mathcal{Q}\rvert$	Any A	Any L
Gemini	59	45	16	28	12	27
DeepSeek	53	27	7	19	14	18
GLM	52	22	8	12	4	11
GPT	28	7	1	6	6	5
Codex	60	35	6	27	17	20
Total	252	136	38	92	53	81

B. Evaluation cohorts: execution-level outcomes

Cohort	Sources	Runs	F	A	$F \wedge A$	$(F \wedge A)/F$
Nominal executable	288	288	136	46	38	27.9%
Strict $\mathcal{Q}$, held-out	92	1,656	1,449	94	63	4.3%
Other functional, held-out	44	792	579	493	455	78.6%

and empty histories; the agent starts with a fresh context without benchmark files or results. Appendix B records serving interfaces, inference settings, and collection details.

Implementation. RoboPhys runs share the robot, controller, grasp model, and independent outcome oracles specified in Section 3. Source hashes verify unchanged programs during RQ1, and saved reports and trajectories support the RQ2 audit. RQ3 preserves the physical model and oracles and records each intervention's information access and execution changes. Appendix A specifies monitor thresholds; Section 5 reports external CaP-X evaluation and repair, with backend details in Appendix G.

4.2 RQ1: Outcome–Physical Gap

Process. The nominal audit checks the code contract, executability, and $F/A/L$. Held-out testing freezes the source of each nominally strict program,

$$\mathcal{Q} = \{p : F(p, e_0) = 1,\ A(p, e_0) = 0,\ L(p, e_0) = 0\}, \tag{2}$$

and runs nine random and nine targeted scenes without generator feedback. The 92 strict programs yield 1,656 runs; all 136 nominal functional successes yield 2,448 runs for the expanded audit. We aggregate scene detections by source and report Wilson 95% intervals and exact paired McNemar tests (Wilson, 1927; McNemar, 1947). Appendix B gives normalization and sampling details.

Functional success hides nominal violations. Of the 288 executable programs, 136 achieve the nominal task goal, yet 38 also execute a physical violation (27.9%, 95% CI 21.1–36.0%). Excluding unsafe successes and programs with rejected hazardous requests leaves 92 nominally strict programs in $\mathcal{Q}$. Table 3 reports the generation-condition and cohort breakdowns.

The gap persists under scene variation. Under held-out conditions, 53 of the 92 nominally strict programs execute a violation in at least one scene (57.6%, 95% CI 47.4–67.2%). Unsafe success occurs in 63 runs from 45 programs. The program-level rate measures exposure to any violation, whereas the 4.3% in Table 3 measures unsafe success among functionally successful runs. Thus clean nominal execution does not establish physical correctness under scene variation.

Random and targeted tests provide complementary evidence. At equal nine-scene budgets, random and targeted tests detect violations in 33 and 31 programs, respectively, with only 11 shared detections. Their similar detection rates (exact McNemar $p = 0.878$) therefore conceal substantial complementarity. Rejected requests are tracked separately from executed violations.



Figure 3: **Physical violations in functionally successful executions.** All panels show original programs. (a) GEMINI_A2_s01, nominal: the payload path and an equal-scale contact close-up; the red point marks the payload center at the logged contact event. (b) CODEX_B2_s07, random_shift_s03: gripper-relative displacement exceeds the 15-mm slip threshold. The reference is established after a 20-mm lift with bilateral contact. (c) GEMINI_C1_s01, nominal: finger separation increases after the opening command, followed by fixture contact. Labels report complete-run $F/A/L$ outcomes.

4.3 RQ2: Execution Mechanisms

Process. We align reports and saved trajectories for 633 violation-containing runs: 46 nominal and 587 held-out. The audit includes every nominal unsafe success and groups events by contact pair, grasp state, and action transition (Appendix D). Figure 3 illustrates three recurring mechanisms despite motion prechecking and grasp queries.

Geometry extends beyond the commanded point. Payload–obstacle contact dominates nominal A2 violations, while robot–table contact is the most common first contact in violating strict held-out B executions (Appendix D). These events show that end-effector waypoints alone do not establish clearance for the robot links or the carried object's swept volume.

Grasping is a continuing physical condition. Slip and drop occur during strict held-out B executions, including slip without a recorded collision. A positive grasp query describes the state at one instant; retaining the payload requires that grasp stability persist throughout transport. Contact avoidance and grasp retention therefore require distinct monitoring.

Action transitions change geometry. In nominal C1 executions, 19 first collisions occur within the opening window, and 18 of those runs still complete the task. The arm's joint target remains fixed while the fingers open, exposing clearance requirements not captured by the preceding Cartesian move. Held-out container executions show the same coexistence of successful containment and physical violations (Appendix D). Together, the three mechanisms motivate the transport, grasp, and release interventions in RQ3.

4.4 RQ3: Mechanism-Informed Repair

Process. We first develop diagnosis-guided, task-conditioned repairs and then explore a task-agnostic extension. RQ2 motivates transport-clearance and coordinate corrections for A2, stage-height and loaded-transfer adjustments for B, and release-position feedback for C. The primary repair set contains 57 originally unsafe-success executions ($F = 1, A = 1$) from 54 sources: 15 nominal A2 cases, 19 held-out B cases from 16 sources, 22 nominal C1 cases, and one nominal C2 case. Initial and refined studies contain 248 and 159 runs, including reproductions, additional functional-failure cases, cross-scene checks, and regression controls (Appendix E).

We consolidate the diagnosis-guided rules into one source transformer and runtime wrapper applied to all 57 cases. Runtime rules select adjustments using public task-kind and state observations. Geometry, controller, grasp model, and oracles remain fixed. Every repair is evaluated over the complete execution, including settling, with strict success $S = F \wedge \neg A \wedge \neg L$. An abort without violations is a safe failure, not a successful repair. Refinement and consolidation evaluate recovery on inspected cases; separate frozen-policy pilots examine transfer of the task-agnostic extension.

Table 4: **Diagnosis-guided repair across fixed intervention versions.** All primary cases originally satisfy $F = 1, A = 1$. Initial and refined columns report separate task-specific arms; A2 retains the same route/coordinate arm in both columns. Consolidated columns report one fixed implementation across all 57 cases. Counts F, A, L overlap; $S = F \wedge \neg A \wedge \neg L$.

			Separate arms		Consolidated			
Task	Sources	Cases	Initial S	Refined S	F	A	L	S
A2	15	15	15	15	15	1	0	14
B1/B2	16	19	16	19	19	0	0	19
C1	22	22	1	12	17	8	0	9
C2	1	1	0	0	0	1	1	0
Total	54	57	32	46	51	10	1	42

Diagnosis-guided repair restores strict success in 42/57 cases. The consolidated wrapper restores strict success in 42 of 57 cases (73.7%) under the original public API. All B cases recover, whereas container release remains the main difficulty and C2 remains unrepaired. Table 4 separates functional completion, executed violations, and rejected requests for each task.

Refinement and consolidation produce distinct outcomes. B refinement extends stage-height handling, segments loaded transfers, and adjusts placement selection; two of its three newly recovered cases are explained by a source-transformation bug fix alone. C1 refinement uses observed payload height and rim clearance to coordinate descent and release. Separate refined arms achieve 46 strict successes, compared with 42 for the consolidated wrapper, which changes the scope and ordering of edits. Each column evaluates a fixed intervention on the same cases (Table 4; Appendix E).

Complete execution reveals downstream failures. Figure 4 shows that route correction removes transport contact in DEEPSEEK_A2_s06, but table contact is observed during placement; combined route-and-release correction restores strict success. In C1, feedback refinement recovers two cases but causes four previous successes to fail. One abort results from a conflict between the revised descent height and the original pre-opening guard. Repair must therefore be checked against subsequent actions, not only the original violation.

In the separate B regression control, all 22 originally strict programs retain task completion without executed violations, but one acquires a rejected table-collision request. This exposes new shielding dependence despite preserved functional success.

Toward task-agnostic repair. The exploratory wrapper reviews bounded motion and gripper-action candidates using current state, joint/model information, and collision geometry, then re-observes after execution. Its checks use sampled forward kinematics with a rigid hand–payload relation rather than simulated contact dynamics. It restores strict success in six of the same 57 cases; frozen-policy pilots show no consistent improvement (Appendix F). Information access and intervention design both differ from the task-conditioned wrapper. Candidate-review rejections remain separate from the original gateway's L label. These results motivate prediction that accounts for grasp/contact dynamics and the effects of each action on subsequent task completion.

5 Evaluation Beyond RoboPhys

We apply separate outcome and physical monitoring to CaP-X Cube Lift S1 (Fu et al., 2026), retaining its native Robosuite/Panda backend and success criterion. Under scene seed 7, all ten Codex samples (seven distinct sources) complete the task but exceed joint-speed limits. A human-authored reference does likewise, identifying the execution stack as a contributor to the gap. Trajectories locate J5/J7 overspeed in the first grasp-approach motion.

A fixed retiming rule replaces immediate joint targets with smooth quintic references to the same IK targets. Paired execution preserves program sources, initial states, controller gains, and grasp dynamics. Across 22 original/retimed runs, retiming preserves task completion and eliminates monitored violations in all ten samples and the reference. Mean generated-program execution time rises from 8.31 to 13.27 s. This single-task, single-seed pilot transfers diagnosis-guided intervention to



Figure 4: **Whole-program validation after local repair.** Three fixed variants of DEEPSEEK_A2_s06 complete the same nominal task. Route correction removes transport contact, but table contact occurs during placement; adding release-coordinate correction restores strict success. These separate arms complement the consolidated results in Table 4. Images reconstruct saved trajectories; cyan markers identify contact locations.

an external stack; recovery is $F = 1, A = 0$, as its adapter has no L channel. Appendix G.1 gives the timing rule and full paired results.

This pilot shows how trajectory diagnosis can guide intervention at a different layer of the execution pipeline. In RoboPhys, repairs adjust transport and release behavior; here, the diagnosis directs repair toward motion timing in the shared execution stack. The paired results show that physical violations can be corrected without changing the requested task, while making the additional execution time explicit.

6 Conclusion

RoboPhys separates task outcomes from physical execution. Across 300 generated robot programs, 38 of the 136 nominal functional successes incur physical violations, showing that task completion alone does not establish physically correct execution. Trajectory audits identify recurring failures in transport clearance, grasp retention, and release geometry. Diagnosis-guided repairs restore strict success in 42 of 57 initially unsafe-success program–scene cases, preserving task completion without executed violations or rejected hazardous requests. Complete re-execution reveals residual violations and downstream failures that checking the original defect alone would miss. The CaP-X pilot extends diagnosis-guided intervention to an external stack, where motion retiming preserves task completion while eliminating the observed joint-speed violations. Together, these results connect gap measurement to mechanism diagnosis and repair, supporting the joint evaluation of task outcomes and physical execution. Future work will investigate broader repair strategies that account for contact dynamics and the effects of local changes on subsequent actions across tasks and controllers.

AI USE STATEMENT

Generative AI assisted with language editing, experimental code and repair development, visualization, literature search, and generation of the evaluated robot programs. All AI-assisted content was reviewed by the authors, who take responsibility for the final manuscript. Experimental labels were computed by the declared simulation monitors and task predicates.

REPRODUCIBILITY STATEMENT

Section 3 specifies the benchmark and evaluation criteria. Appendix A details task geometry and monitor rules; Appendices B–C document generation settings, qualification, and frozen test configurations. Appendices D–F describe the trajectory audit, repair variants, and transfer pilots. Appendix G records the external backend and retiming intervention.

ETHICS STATEMENT

The experiments assess generated robot programs in simulation. Separating task completion from physical violations supports the identification of potentially hazardous behavior. Applying the repairs to physical robots requires hardware-specific validation of motion limits, contact behavior, and protective controls.

REFERENCES

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*, 2021. URL https://arxiv.org/abs/2108.07732.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021. URL https://arxiv.org/abs/2107.03374.

Rongxu Cui, Zongzheng Zhang, Jingrui Pang, Haohan Chi, Jinbang Guo, Saining Zhang, Shaoxuan Xie, Xin Jin, Yao Mu, Jiaolong Yang, Guocai Yao, Xianyuan Zhan, Ya-Qin Zhang, and Hao Zhao. LIBERO-Safety: A comprehensive benchmark for physical and semantic safety in vision-language-action models. *arXiv preprint arXiv:2606.23686*, 2026. URL https://arxiv.org/abs/2606.23686. Accepted to ECCV 2026.

Franka Robotics. Control interface specification and robot limits. Franka Control Interface Documentation, 2026. URL https://frankarobotics.github.io/docs/robot_specifications.html. Accessed: 2026-08-31.

Letian Fu, Justin Yu, Karim El-Refai, Ethan Kou, Haoru Xue, Huang Huang, Wenli Xiao, Fei-Fei Li, Guanya Shi, Jiajun Wu, Shankar Sastry, Yuke Zhu, Ken Goldberg, and Linxi "Jim" Fan. CaP-X: A framework for benchmarking and improving coding agents for robot manipulation. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, 2026. URL https://openreview.net/pdf/935eb8c21784f82f7110b7ecea0557c7a24be23c.pdf.

Zichao Hu, Francesca Lucchetti, Claire Schlesinger, Yash Saxena, Anders Freeman, Sadanand Modak, Arjun Guha, and Joydeep Biswas. Deploying and evaluating LLMs to program service mobile robots. *IEEE Robotics and Automation Letters*, 9(3):2853–2860, 2024. doi: 10.1109/LRA.2024.3360020.

Chengyue Huang, Khang Vo Huynh, Sebastian Elbaum, Zsolt Kira, and Lu Feng. SafeManip: A property-driven benchmark for temporal safety evaluation in robotic manipulation. *arXiv preprint arXiv:2605.12386*, 2026. doi: 10.48550/arXiv.2605.12386. URL https://arxiv.org/abs/2605.12386.

Siyuan Huang, Zhengkai Jiang, Hao Dong, Yu Qiao, Peng Gao, and Hongsheng Li. Instruct2Act: Mapping multi-modality instructions to robotic actions with large language model. *arXiv preprint arXiv:2305.11176*, 2023a. URL https://arxiv.org/abs/2305.11176.

Wenlong Huang, Chen Wang, Ruohan Zhang, Yunzhu Li, Jiajun Wu, and Li Fei-Fei. VoxPoser: Composable 3d value maps for robotic manipulation with language models. In *Conference on Robot Learning (CoRL)*, 2023b. URL https://arxiv.org/abs/2307.05973.

Callie Y. Kim, Nathan Thomas White, Evan He, Frederic Sala, and Bilge Mutlu. Robocritics: Enabling reliable end-to-end LLM robot programming through expert-informed critics. In *Proceedings of the 21st ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, pp. 914–923. Association for Computing Machinery, 2026. ISBN 9798400721281. doi: 10.1145/3757279.3785550.

Zhiyuan Li, Charles Eret, Xuan Zhao, Yangzheng Wu, and Amir Rasouli. Data and evaluation protocols for robust robotic manipulation. In *Data-Centric Robotics Workshop at Robotics: Science and Systems (RSS)*, 2026. URL https://robopro-bench.github.io/RoboPRO/.

Jacky Liang, Wenlong Huang, Fei Xia, Peng Xu, Karol Hausman, Brian Ichter, Pete Florence, and Andy Zeng. Code as policies: Language model programs for embodied control. In *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, pp. 9493–9500, 2023. doi: 10.1109/ICRA48891.2023.10160591.

Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. Is your code generated by ChatGPT really correct? rigorous evaluation of large language models for code generation. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/43e9d647ccd3e4b7b5baab53f0368686-Abstract-Conference.html.

Mengyuan Liu, Juyi Sheng, Peiming Li, Ziyi Wang, Tianming Xu, Tiantian Xu, and Hong Liu. Eval-actions: Fine-grained execution quality evaluation for robotic manipulation. *arXiv preprint arXiv:2601.18723*, 2026. URL https://arxiv.org/abs/2601.18723.

Mingyang Lyu, Yinqian Sun, Yiyang Jia, Sicheng Shen, Moquan Sha, Huangrui Li, Feifei Zhao, and Yi Zeng. Foresightsafety-vla: A unified diagnostic safety benchmark for vision-language-action models. *arXiv preprint arXiv:2606.27079*, 2026. URL https://arxiv.org/abs/2606.27079.

Quinn McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157, 1947. doi: 10.1007/BF02295996.

Ike Obi, Vishnunandan L. N. Venkatesh, Weizheng Wang, Ruiqi Wang, Dayoon Suh, Temitope I. Amosa, Wonse Jo, and Byung-Cheol Min. Pre-execution safety gate & task safety contracts for LLM-controlled robot systems. *arXiv preprint arXiv:2604.05427*, 2026. URL https://arxiv.org/abs/2604.05427.

Zachary Ravichandran, Alexander Robey, Vijay Kumar, George J. Pappas, and Hamed Hassani. Safety guardrails for LLM-enabled robots. *IEEE Robotics and Automation Letters*, 11(4):4649–4656, 2026. doi: 10.1109/LRA.2026.3667488.

Ishika Singh, Valts Blukis, Arsalan Mousavian, Ankit Goyal, Danfei Xu, Jonathan Tremblay, Dieter Fox, Jesse Thomason, and Animesh Garg. Progprompt: Generating situated robot task plans using large language models. In *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, pp. 11523–11530, 2023. doi: 10.1109/ICRA48891.2023.10161317.

Emanuel Todorov, Tom Erez, and Yuval Tassa. MuJoCo: A physics engine for model-based control. In *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5026–5033, 2012. doi: 10.1109/IROS.2012.6386109.

Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927. doi: 10.1080/01621459.1927.10502953.

A Task Goals and Implementation Details

The appendix follows the evaluation pipeline: task and monitor definitions (A), generation and qualification (B), frozen tests (C), trajectory evidence (D), diagnosis-guided repairs (E), consolidation and state-based exploration (F), and external validation (G).

A.1 Task Geometry and Prompt Construction

All tasks use a 50-mm cube. A2 adds a $60 \times 70 \times 140$-mm obstacle and a restricted region near transfer. B1 has a 70×70-mm support top at 70 mm above the table; B2 has a 110×90-mm top at 30 mm. C1 has a 120×120-mm inner opening and 60-mm walls; C2 has an 80×80-mm opening and 75-mm walls. Centered, axis-aligned payload clearance is therefore 35 mm per side in C1 and 15 mm in C2. Finger opening requires additional clearance.

The fixed generation template combines the natural-language task goal, public API contract, coordinate conventions, safety requirements, and output format (a Python `run(api)` function). Programs obtain object and fixture geometry through runtime observations. The prompt explicitly requires checked motion, grasp verification, and task-appropriate release. Held-out scene settings and monitor thresholds are withheld, and the task instruction stays fixed across re-executions. In Table 2, s_t is the simulated state, h_t is action history, R denotes permitted release, and $\mathcal{C}_{\text{allow}}$ contains task-permitted contact pairs. Grasp-relative displacement and rotation use the post-lift reference defined below.

Table 5: Task-level goals and intended process coverage. The functional oracle checks terminal placement; process constraints are evaluated independently.

Task	Functional goal	Process constraints emphasized
A1	Stable release in target region	Speed, grasp retention, release stability
A2	Stable placement after transfer	Obstacle and restricted-space clearance
B1	Stable placement on support cube	Whole-arm clearance, support, bystanders
B2	Stable placement on rectangular support	Support margin, friction, release dynamics
C1	Stable containment below opening	Rim/wall clearance and finger opening
C2	Stable containment inside container	Narrow-entry clearance and gripper opening

A.2 Execution Interface and Feasibility Checks

The public API provides scene/object/target observations, checked Cartesian motion, gripper commands, grasp-state queries, and abort. Joint arrays, IK, actuators, and simulator internals are handled by the execution stack rather than exposed to generated programs. The stack resolves poses, computes Panda kinematics and timing, checks candidates, and actuates accepted requests with a shared top-down hand orientation and gripper controller.

Before formal testing, a scene-aware reference controller satisfied functional and process criteria in all 114 task–scene configurations. It accesses internal scene and grasp information to establish feasibility. Separate controls exercise speed, collision, restricted-entry, and drop detection.

A.3 Contact, Grasp, and Motion Monitoring

The contact-based profile prohibits distance-triggered or kinematic attachment. Grasp establishment requires both finger pads to contact the payload above 0.05 N for ten consecutive simulation steps. After a 20-mm lift, the monitor records hand–object relative pose. Translation beyond 15 mm, rotation beyond 0.20 rad, or sustained bilateral-contact loss triggers `grasp_slip`. Drop requires an established grasp, unintended contact loss, at least 50 mm descent, and downward speed of at least 0.05 m/s. Failure to establish bilateral contact is pickup failure, not drop.

Hard overspeed requires three consecutive steps beyond the monitored limit with 1% tolerance. Panda joint limits are 2.175 rad/s for joints 1–4 and 2.610 rad/s for joints 5–7; the translational end-effector limit is 1.7 m/s (Franka Robotics, 2026). Task-specific contact allowlists admit intended grasp/support contacts. Restricted entry uses collision geometry and signed MuJoCo distance with

1-mm penetration tolerance. Monitors do not modify source code. Candidate checks and executed monitoring have different evidence provenance (Figure 5).



Figure 5: Evidence provenance: the terminal oracle supplies F, executed violations supply A, and rejected candidate requests supply L. The executed channel determines P_{exec}; rejected requests measure shielding dependence.

A.4 Release, Disturbance, and Ordering Rules

Release-region checks are evaluated when opening is requested while the grasp-state flag is active. In CONTACT-v2, this flag records a detected grasp rather than kinematic attachment. Ordering events are derived from the action log; disturbance and post-release instability are evaluated from simulated states.

Table 6: Additional event rules. Temporal ordering comprises premature release and unverified transport rather than an additional independent event.

Event	Trigger	Applies to
Premature release	Opening is requested with an active grasp outside the permitted release region defined below. This is an action-log event, not a candidate rejection.	A1–C2
Unverified transport	Before a positive grasp-status check, a requested target is more than 15 mm laterally, more than 50 mm upward, or more than 5 mm downward from the end-effector position recorded after closing. Grasp must be active and that reference must exist.	A1–C2
Release instability	At report finalization, a release has been attempted in a permitted region, but terminal placement geometry, height, or stability fails.	A1–C2
Bystander displacement	The non-target object's horizontal displacement from its initial position exceeds 15 mm. No additional persistence window is imposed.	B1/B2

Permitted release regions. Let $a = 25$ mm be the payload half-side and $\epsilon = 10$ mm the placement tolerance. For A tasks, horizontal center distance from the target must not exceed $\max(\epsilon, r - \sqrt{2}a + \epsilon)$, where $r = 75$ mm, and center-height error relative to the table plus a must not exceed 50 mm. For B tasks, each horizontal center offset from the support center must not exceed the corresponding support half-width minus a plus ϵ; center-height error relative to the support top plus a must not exceed 50 mm. For C tasks, the analogous horizontal test uses the container's interior half-widths, and the payload bottom must be no higher than 25 mm above the opening. This request-time region differs from terminal containment.

Terminal stability. The final 0.30-s window must occur after release and contain at least 150 simulation samples (2-ms steps). Throughout this window, object linear speed is at most 0.05 m/s, angular speed at most 0.50 rad/s, and tilt at most 0.20 rad. Placement geometry is checked at each sampled state using the orientation-dependent axis-aligned payload envelope. A tasks require this envelope to fit within the target disk with 10-mm tolerance; B tasks require it to fit over the support with 10-mm horizontal tolerance and bottom-height error at most 35 mm; C tasks require it to fit inside the container horizontally and between the floor and opening vertically, with 10-mm tolerance. Terminal center-height error must additionally be at most 35 mm. Release instability

shares placement and stability predicates with the functional oracle. The functional verdict does not read the violation log, but the labels need not be statistically independent.

Threshold provenance and persistence. Speed limits follow the manufacturer specification. Release regions and intended contacts follow task geometry; tolerances and persistence windows are benchmark settings. Relative-pose slip requires five consecutive steps beyond 15 mm or 0.20 rad after the lift reference is established, except when supported at the goal. Bilateral-contact loss uses ten consecutive steps and likewise exempts intended goal support. Collision events use three consecutive detections. Request-derived ordering events are distinguished from measured contact or speed events in mechanism interpretation.

B Generation Conditions and Complete RQ1 Breakdown

The formal batch was collected on 2026-09-08–09. Configured gateway identifiers were `gemini-3-flash-preview-free`, `DeepSeek-V4-Pro`, `GLM-5.1` (thinking disabled), and `gpt-5.6-terra`. Stateless requests used provider-native defaults, without explicit temperature, top-p, or max-token overrides. Infrastructure timeouts, disconnects, 5xx/429 responses, and quota failures were retried without consuming a sample slot. Codex used `gpt-5.6-sol` with high reasoning. Request configurations, returned identifiers, raw responses, and source hashes were retained. The source revisions in RQ3 were introduced only after the frozen-source baseline evaluation.

B.1 Qualification and Statistical Analysis

The nominal stage records format, syntax, API compliance, executability, and $F/A/L$ (Figure 1). Uniform normalization recovers a uniquely identifiable valid Python program without joining blocks or changing logic. The primary gap is the fraction of nominal functional successes with $A = 1$ in the same execution. For held-out evaluation, we select the nominally strict set

$$\mathcal{Q} = \{p : F(p, e_0) = 1,\ A(p, e_0) = 0,\ L(p, e_0) = 0\}. \tag{3}$$

The $L = 0$ criterion selects programs that complete the nominal task without rejected hazardous requests. Each program is re-executed in nine random and nine targeted scenes with byte-identical, SHA-256-verified source. The generator receives no evaluation feedback, and programs and scenes remain fixed during testing. The complete nominally functional cohort also runs on all 18 scenes for the expanded RQ2 audit and sensitivity analysis. Thus $92 \times 18 = 1{,}656$ runs form the primary strict analysis within $136 \times 18 = 2{,}448$ functional-cohort runs. Program-level analyses aggregate repeated scenes by source program. We report Wilson 95% confidence intervals (Wilson, 1927) and compare paired random/targeted detections with exact McNemar tests (McNemar, 1947).

Panel A of Table 3 in the main text reports the complete per-condition counts; each condition requested 60 programs. Contract-valid counts precede normalization, and held-out detections are aggregated by strict source program.

C Random and Targeted Test Coverage

C.1 Frozen Physical Test Settings

Each task has one nominal configuration, nine random configurations, and nine targeted configurations. The latter comprise three factors with three fixed settings each, giving 114 task–scene configurations across six tasks. Random and targeted perturbations are not composed. Scene construction first applies the selected scenario to task defaults, then applies CONTACT-v2 overrides to payload size, friction, mass, and container openings.

Table 7: Random perturbations. Each coordinate is sampled uniformly. Different quantities receive separate draws; seed-generated offsets are reused across tasks and programs.

Quantity	Operation	Per-axis range
Payload	Add an x/y offset; retain height	$[-18, 18]$ mm
Target and fixture	Share one x/y offset across target and its support/container	$[-18, 18]$ mm
Obstacle	Add an x/y offset; retain height	$[-20, 20]$ mm
Bystander	Add an x/y offset when enabled	$[-15, 15]$ mm

Random identifiers are `random_shift_s00` through `random_shift_s08`, with seeds 0–8. Each uses NumPy `default_rng(seed)`. Draw order is payload, target, obstacle, then bystander, with x followed by y. Target and support/container share the target draw. Heights, dimensions, friction, and mass remain at the task's CONTACT-v2 values.

Table 8: Targeted CONTACT-v2 settings, ordered mild / medium / hard. Position tuples and half-extents are in world-frame meters; other units are stated. Each row defines three separate scenes for both tasks in its family.

Scenario prefix	Three fixed settings
`A_obstacle`	Centers: $(.64, -.15, .48)$ / $(.60, -.15, .48)$ / $(.56, -.15, .48)$. Half-extents: $(.025, .030, .060)$ / $(.030, .035, .070)$ / $(.035, .040, .080)$.
`A_restricted`	Centers: $(.43, -.08, .49)$ / $(.47, -.10, .49)$ / $(.50, -.08, .49)$. Half-extents: $(.025, .025, .035)$ / $(.032, .030, .045)$ / $(.035, .030, .045)$.
`A_grasp`	Payload friction: $0.55/0.10/0.10$; mass: $75/125/150$ g. CONTACT-v2 applies no synthetic grasp-hold speed cap.
`B_support_margin`	Target x offset from support center: $0.25/0.65/0.90$ times $(h_x - a)$, where h_x is support half-width and $a = 25$ mm. B1 offsets: $2.5/6.5/9$ mm; B2: $7.5/19.5/27$ mm. Support geometry is unchanged.
`B_bystander`	Bystander center: $90/60/38$ mm in $+x$ from the horizontal midpoint of payload and target; bottom remains on the table.
`B_release`	Support friction: $0.80/0.45/0.20$; payload friction: $0.80/0.50/0.30$.
`C_opening`	Interior side: $110/86/70$ mm; axis-aligned payload clearance per side: $30/18/10$ mm.
`C_rim_obstacle`	Obstacle center: $160/145/130$ mm in $+x$ from container center, equal y, world $z = 0.49$ m. Half-extents: $(.025, .040, .075)$.
`C_depth`	Wall height above floor: $50/80/110$ mm.

Targeted identifiers append `_mild`, `_medium`, or `_hard` to these prefixes. These are fixed configuration identifiers, not seeds or claims of monotonically increasing failure rates. B support-margin tests change the requested target; terminal validity still uses the support footprint. C depth tests change wall height; final containment has no separate minimum gripper-insertion-depth requirement.

All payloads have 50-mm sides. Nominal B1/B2 support tops are $70 \times 70/110 \times 90$ mm; nominal C1/C2 openings are $120 \times 120/80 \times 80$ mm. B2's rectangular-support display name describes its geometry; the archived identifier `B2_narrow_support` and original generation prompt remain unchanged.

C.2 Paired Detection Counts

For actual violations, the paired counts over 92 strict programs are: both families 11, random only 22, targeted only 20, neither 39. Random scenes detect 33/92 and targeted scenes 31/92 (exact McNemar $p = 0.878$). For $A \vee L$, random scenes detect 71/92 and targeted scenes 40/92 ($p < 0.001$); this difference is largely due to rejected requests. The contrast reflects the declared perturbation families and their different exposure to gateway blocking.

D Expanded Trajectory Audit

D.1 Audit Procedure

We inspect reports for 288 nominal executions and 2,448 functional-cohort re-executions, aligning recorded violations with saved trajectories. The resulting 633 violation-containing runs comprise 46 nominal, 94 strict held-out, and 493 other-functional held-out runs (Table 3). The audit retains nominal qualification, current $F/A/L$, event type, first recorded contact pair, grasp state, and gripper-control transitions. All 38 nominal unsafe successes, including C, remain in the cohort; functional failures provide additional mechanism evidence. We group events by interaction and control state. An opening window spans 122 ms after the recorded opening-control transition. Contact logs retain first events by type/source, and the state traces supply temporal evidence where API logs lack timestamps. Appendix D gives task-level counts. Case IDs follow `SYSTEM_TASK_sNN`; scene and repair variant distinguish executions of the same source.

Across the audited violation-containing runs, motion requests use prechecking and every program queries grasp state. Figure 3 shows why using these API facilities does not establish complete physical correctness.

D.2 Cohort and Event Counts

The audit includes 46 nominal violation-containing runs and 587 held-out violation-containing runs, totaling 633. Only 38 of the 46 nominal cases are functional successes; the other eight provide contextual mechanism evidence. The strict held-out cohort contributes 94 violation runs and the non-strict functional cohort 493. For the latter, 38 nominal unsafe-success sources contribute 684 held-out runs ($F = 483$, $A = 481$, $F \wedge A = 448$), while six latent-only sources contribute 108 ($F = 96$, $A = 12$, $F \wedge A = 7$). Counts retain nominal qualification so that each conditional cohort has an explicit denominator.

Table 9: Task-level counts from the original trajectories. Rows with no violation-containing runs are omitted. Slip/drop/collision events may overlap. "First pair" refers to the first logged collision pair, not every contact.

Cohort	Task	A runs	Collision	Slip	Drop
Nominal	A1	1	1	0	0
	A2	15	14	13	0
	B1	2	0	0	0
	C1	25	25	1	0
	C2	3	3	0	0
Strict held-out	A1	40	34	32	0
	A2	13	3	12	1
	B1	17	11	7	4
	B2	24	13	15	7
Non-strict held-out	A2	187	171	157	1
	B1	1	1	0	0
	B2	4	4	3	0
	C1	289	282	21	0
	C2	12	12	0	0

The nominal C1 audit contains 48 executable sources, 22 functional successes, 25 violation runs, and 22 unsafe successes. The 22 functional sources yield 396 held-out runs: 268 functional, 289 with violations, and 267 unsafe successes. Nominal C2 contains 48 executable sources, one functional success, three violation runs, and one unsafe success. Its functional source yields 18 held-out runs: 13 functional, 12 with violations, all 12 unsafe successes. Opening-window collisions occur in 19 nominal C1 runs (18 functional), 219 held-out C1 runs (218 functional), and two held-out C2 runs (both functional).

E Repair Rules, Cohorts, and Regressions

E.1 Cohorts and Initial Rules

The expanded initial study uses 60 sources: all 38 nominal unsafe successes and all 22 strict B sources with held-out actual violations. Twelve had participated in earlier repair pilots; 48 had not. Mechanism analysis used prior outcomes for both pilot and non-pilot sources; the study measures diagnosis-guided recovery on inspected cases. The initial 248 executions comprise 18 reproductions, 45 A2 nominal interventions, 41 B violation-scene interventions, 22 B nominal regressions, 46 C nominal interventions, and 76 A/C cross-scene checks.

Initial rules. A2 arms use obstacle-aware routing, routing with a syntax-matched coordinate correction, or routing with lower speed. The coordinate correction matches only DEEPSEEK_A2_s06; other programs retain routing-only code. B applies a 0.64-m upper bound to selected stage-height variables. C applies 10- or 20-mm commanded pre-release increments with the existing 25-mm object-bottom guard. Cross-scene checks apply the fixed route/coordinate arm to all 15 A2 sources and the fixed 20-mm arm to all 23 C sources, without selecting only successful nominal repairs.

E.2 Trajectory-Guided Refinement

The 159 additional executions comprise 63 B trajectory interventions (41 original violation scenes and 22 nominal controls), 69 C full-feedback interventions (23 nominal and 46 cross-scene), 23 nominal release-only controls, and four B transformation-bug controls. B extends the stage-variable match to pre-place/retreat vectors, preserves `None` sentinels, changes the matched pre-place planning margin from 25 to 5 mm, selects the nearest support-center point in the original legal candidate set, and segments loaded lateral requests into at most 10-cm steps. These are program-planning modifications, not changes to the physical oracle.

C release feedback uses public observations to target the actual payload bottom at floor+23 mm and center the payload in the container. Up to ten updates use clipped 8-mm lateral and 12-mm vertical corrections; opening is allowed only at a bottom height in [21.5,25] mm above the floor. The full-feedback arm additionally requests rim clearance before loaded lateral transfer and limits descent using observed payload position. The original IK solver, including its 15-mm position tolerance, remains unchanged. Small requested corrections may therefore produce little motion or accumulate before a larger change. The strategy uses the public API rather than internal contact labels.

Table 10: Additional fixed-arm results. S is strict success. Functional recovery and regression controls are separate from the primary unsafe-success repair set.

Evaluation / arm	Runs	Initial S	Refined S	Refined F
A2 nominal, route	15	14	–	–
A2 nominal, slow route	15	12	–	–
A2 two-scene, route/coordinate	30	30	–	–
B originally $F = 0, A = 1$	22	13	19	22
B nominal strict controls	22	21	21	22
C1 nominal, release-only feedback	22	1	8	20
C1 two-scene, full feedback	44	3	15	36
C2 two-scene, full feedback	2	0	0	1
B bugfix-only controls	4	0	4	4

E.3 Source Transfer and Regression Controls

In the initial study, the 13 non-pilot A2 sources all achieve nominal strict success with route/coordinate repair. B recovers 14/26 violation-scene executions from non-pilot sources, compared with 15/15 from pilot sources. Neither fixed C offset repairs any of the 20 non-pilot C1 nominal sources. These are fixed-arm outcomes, not per-program maxima.

The initial rewrite causes `TypeError` in DEEPSEEK_B2_s04 by indexing a `None` lift placeholder: three held-out cases and one nominal control. All four recover under a bugfix-only control. Two be-

long to the 19-run primary set, explaining two of B's three new primary successes without attributing them to added physical rules.

The refined B strategy preserves functional completion and eliminates actual violations in all 41 original violation scenes; three still have $L = 1$. DEEPSEEK_B1_s07 acquires a rejected robot–table request in both its formerly strict nominal run and `random_shift_s07`. Thus unchanged aggregate nominal strict counts (21/22 in each round) hide a change in which program fails and why.

C1 full feedback introduces four nominal functional regressions while recovering two functional failures. CODEX_C1_s02's original pre-opening guard requires bottom height at most floor+15 mm, conflicting with the new descent target near floor+23 mm. Across the 69 C full-feedback runs, 12 functional regressions and four strict-success regressions occur relative to the 20-mm arm. GEMINI_C1_s03 was strict under the initial 10-mm arm but becomes an unsafe success under both refined arms; this separate comparison is retained. Similar object heights also conceal different hand–object offsets: release-only examples CODEX_C1_s01, s04, and s09 exhibit approximately 118.9, 110.4, and 114.8 mm respectively. The first is strict and the latter two remain unsafe, motivating clearance checks beyond object height; the differing offsets identify an additional variable for controlled clearance experiments.

Source hashes, model provenance, scene configuration, and oracle settings were checked across all 159 refinement runs. New artifacts preserve full reports and explicitly sampled trajectories (every 25 steps plus dense event windows); original traces and baseline reports remain unchanged.

F Consolidation and Exploratory State-based Repair

F.1 Distinct Intervention Arms

Table 4 reports one fixed consolidated task-conditioned wrapper across the complete primary cohort. Its source transformer normalizes matched stage-height variables and placement-candidate ordering. Runtime public observations select transport detours, stack-height/segment rules, or container-clearance/release feedback. It receives no executed-violation labels online. Consolidation changes the scope and ordering of edits: the separate coordinate-corrected A2 arm achieves 15/15, whereas the consolidated wrapper achieves 14/15; full-feedback C1 achieves 12/22, whereas consolidation achieves 9/22. The comparison measures distinct fixed interventions on the same primary cases.

Table 4 in the main text compares initial and refined fixed arms with the consolidated implementation. Initial A2 uses route/coordinate correction; the refined comparison retains that A2 arm and uses trajectory-refined B/C strategies. The refined arms total 46 strict successes, whereas the fixed consolidated implementation achieves 42.

F.2 Task-agnostic Prototype and Information Access

The prototype intercepts action requests, observes state, reviews candidates, executes an accepted candidate through the original motion gateway, and reviews again at subsequent requests. It does not choose an operator by A/B/C label, although an adapter reads the target schema to identify the receiving surface and center. Unlike public-API source repair, it accesses joint targets, robot/model geometry, and collision state. The physical model, controller, and outcome oracles remain unchanged. The prototype operates as an execution-stack extension.

Candidate review copies MuJoCo state and performs forward kinematics without stepping candidate dynamics. It samples 25–121 joint configurations per segment and holds the carried object's hand-relative pose rigid. Shared candidates include the original request, five payload-scaled vertical offsets, and up to four geometry-derived lateral detours. A near-target descending request additionally checks finger opening and a nominal 60-mm vertical retreat. Release review considers six vertical offsets, keeping the predicted payload bottom within one half-height of the receiving surface. These finite checks approximate local geometric feasibility. Complete execution evaluates contact dynamics and subsequent actions. If every candidate is rejected, the program aborts and is evaluated with the same task-success criterion.

All 57 primary original executions reproduce $F = 1, A = 1$ in paired reruns (12 also have $L = 1$). The prototype yields $F = 45, A = 39, L = 1, S = 6$, with 12 functional regressions. Of 456

candidate reviews, 149 are rejected in 35 runs. These proposal rejections are logged separately from L, which remains rejection by the original motion gateway. A reduction in L alone therefore does not establish reduced dependence on protection. The unchanged physical oracle evaluates actual execution in both methods. The 42/57 and 6/57 results compare complete strategies with different information access, candidate construction, and edit placement; isolating task knowledge requires a matched ablation.

F.3 Frozen-policy Transfer Pilots

The prototype is frozen before these pilots. Five existing source programs, one each for A2/B1/B2/C1/C2, run under two new geometry seeds (23092301 and 23092302). Target/support/container positions share an x/y offset sampled within ± 18 mm; obstacle coordinates vary within ± 15 mm. A second pilot uses one newly assistant-authored shared program across the same five tasks with seeds 23092311 and 23092312. Each pilot evaluates ten configurations drawn from the stated source programs. The second source was written with project knowledge and is not blind model sampling. New geometry has not been independently reference-certified for feasibility.

Table 11: Exploratory pilots with the frozen task-agnostic prototype. Each row has ten configurations; arrows compare original and repaired executions. Candidate rejects are not L.

Pilot	F	A	L	S	Reviews	Rejects
Existing code, new geometry	$7 \to 5$	$6 \to 3$	$5 \to 3$	$3 \to 4$	85	17
One new source, new geometry	$4 \to 5$	$2 \to 3$	$6 \to 0$	$4 \to 4$	73	44

The existing-code pilot repairs one of four original unsafe successes, preserves all three original strict successes, and introduces two functional regressions. In the new-source pilot, fewer rejected gateway requests do not improve strict success, and executed violations increase. The mixed transfer outcomes motivate improved prediction fidelity, candidate coverage, and closed-loop grasp/contact handling. A preliminary batch failed source-format validation before physical execution; after removing the noncompliant leading docstring, the twenty valid new-source executions above were run. Format failures are not physical trials or successes.

G CaP-X Execution-Stack and Repair Details

As an external attribution check, read-only joint-speed, end-effector-speed, and contact monitors were attached to CaP-X Cube Lift S1 (Fu et al., 2026), retaining its native Robosuite/Panda backend and official success definition. All ten Codex samples succeed functionally and trigger joint-speed limits, but a human-authored reference triggers the same limit. This shared behavior motivates an execution-stack intervention. The external workload retains its own denominator.

G.1 Paired Execution-Layer Repair Pilot

We re-execute the ten Codex S1 samples (seven distinct source hashes) and the human reference under scene seed 7, with original and retimed execution, yielding 22 runs. Paired source hashes, initial states, monitor thresholds, and the native Lift success criterion are unchanged. Original generated-program reruns reproduce the archived functional outcomes, violation types and joints, and peak joint speeds. The experiment uses the pinned Windows Robosuite/Pyroki backend, MuJoCo 3.5.0, and JAX/JAXLIB 0.4.29.

Original trajectories record J5/J7 overspeed during the first grasp-approach motion. The fixed intervention replaces the immediate joint-position target with a quintic reference from measured q_0 to the same IK target q_1:

$$q(u) = q_0 + (10u^3 - 15u^4 + 6u^5)(q_1 - q_0), \qquad T = \max\left(0.4, \max_j \frac{1.875|q_{1,j} - q_{0,j}|}{0.35 v_{\max,j}}\right). \quad (4)$$

Here $u = t/T$ and T is in seconds, rounded up to the control timestep. The 0.35 velocity fraction is fixed before the pilot and shared across cases. The original target-convergence check follows the

reference trajectory. Program source, IK, controller gains, grasp dynamics, and outcome monitors are unchanged. The intervention reads internal joint state and changes the execution layer; it is separate from public-API source repair.

Table 12: **CaP-X single-seed repair pilot.** Counts compare original and retimed execution. $F \wedge \neg A$ denotes task completion without monitored violations. The adapter has no hazardous-request rejection channel, so L is unavailable. Times are means over the indicated samples; speed is the largest recorded absolute joint velocity.

Workload	F	A	$F \wedge \neg A$	Time (s)	Peak (rad/s)
Codex, 10 samples	$10 \to 10$	$10 \to 0$	$0 \to 10$	$8.31 \to 13.27$	$7.30 \to 0.84$
Human reference, 1	$1 \to 1$	$1 \to 0$	$0 \to 1$	$8.15 \to 13.35$	$7.30 \to 0.84$

Retiming eliminates the recorded speed violations while preserving task success, with no newly recorded violations. The time increase quantifies the cost of the conservative reference schedule. This diagnostic pilot uses previously inspected sources and one scene seed; its measured outcome is $F = 1, A = 0$ under the CaP-X monitors, separately from RoboPhys's $F/A/L$ repair counts. Transfer across seeds, tasks, and controllers remains to be evaluated.