STRIKING THE HARMONIZATION: PERSONALIZED SAFETY VIA THE CONSISTENCY CONSTRAINTS

Anonymous authors
Paper under double-blind review

ABSTRACT

Recent research on personalized safety in large language models has separately investigated two phenomena—personalized jailbreaking and personalized maladaptation—yet these lines of work remain disjointed, offering no unified account of the fundamental tension between general safety constraints and individual-specific requirements. We propose a **Consistency**-based framework that reconceptualizes both safety and personalization as two forms of contextual consistency: the former internalized as an intrinsic model property, the latter grounded in input context. Under this unified consistency perspective, we formalize personalized safety as a **Constrained Reinforcement Learning** problem. Specifically, we minimize safety consistency to strictly enforce general safety boundaries, while maximizing the personalized reward (the negation of personalized consistency) to drive individual preference satisfaction. This formulation recasts the apparent tension not as a trade-off, but as a jointly satisfiable condition under explicit consistency constraints on safety-personalization feasibility.

1 INTRODUCTION

Safety and ethics constitute foundational imperatives in the deployment of large language models (LLMs) Wang et al. (2025); Zhang et al. (2024); Jiao et al. (2025); Ungless et al. (2025). The alignment paradigm has undergone an evolution—from conventional preference alignment Ouyang et al. (2022) anchored in general human values to an emerging emphasis on personalized alignment Guan et al. (2025), wherein models are progressively tailored to serve not broad populations but distinct individuals. As is demonstrated in Figure 1, this transition surfaces a critical tension: whether an excessive pursuit of personalization may inadvertently engender latent safety risks? Framed more precisely, what constitutes a principled equilibrium between the competing demands of safety and personalization, and how should such a balance be rigorously defined and sustained?



Figure 1: **Comparison of interaction strategies.** Conventional methods either strictly enforce general safety (top) or over-accommodate individual preferences (middle). In contrast, our method (bottom) harmonizes both, enforcing safety boundaries while maximizing personalized satisfaction.

Within the research landscape at the intersection of safety and personalization, existing work converges on two principal lines of inquiry. The first concerns the phenomenon of **Personalized Jailbreaking** Li et al. (2025), wherein the injection of individuated personas—particularly those embodying marginalized occupational identities or psychologically distressed conditions—can evoke pro-

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

found empathetic responses in LLMs. Such empathy may, in turn, circumvent the models' generic safety guardrails, eliciting outputs that contravene established safety values. The second line of inquiry, i.e., **Personalized Maladaptation** Wu et al. (2026), addresses the alignment of models with idiosyncratic safety requirements. Specifically, individuals shaped by distinct occupational roles or unique physiological and psychological conditions often diverge sharply in their sensitivities for safe content. Behavioral directives that are conventionally regarded as innocuous from a general safety perspective (i.e., "Please Remain Quiet"), may prove unacceptable or even aversive for certain populations like children with hyperactivity disorders. Current research, however, investigates these two dimensions of the safety–personalization nexus in a disjointed manner. This fragmented treatment engenders a forced dichotomy: model outputs are rendered either rigorously safe and controlled, or faithfully aligned with idiosyncratic individual requirements.

We ground our approach in a unified notion of **LLM consistency** Zhou et al. (2026). We posit that both general safety alignment and personalized preference can be coherently expressed as consistency demands: the former requires model outputs to remain consistent with established safety norms, while the latter requires consistency with individual-specific information provided in the context. Critically, we maintain that safety consistency retains unconditional primacy—it constitutes a hard boundary that must not be breached. The genuine challenge, then, is not to strike a trade-off, but to maximize the fulfillment of personalized consistency strictly within the bounds of general safety. This perspective reframes personalized safety as a constrained reinforcement learning problem Paternain et al. (2019), wherein the objective is to maximize the personalized reward (or equivalently, reducing deviations from personalized consistency) subject to a hard constraint that enforces safety consistency by minimizing its violation.

In summary, our contributions are as follows:

• We are the first to approach personalized safety through the lens of LLM consistency, providing a unified formulation that encompasses two representative problem types within this domain.

• We develop a detailed representational theory of consistency that precisely captures how general safety and persona-specific demands manifest during interaction, serving as a powerful analytical lens for personalized safety.

• We propose a constrained reinforcement learning framework for personalized safety, wherein personalized satisfaction is maximized under hard safety consistency constraints. This achieves a harmonized interplay between safety and personalization in LLM interactions.

2 Related work

LLM safety and personalization represent two primary alignment objectives. Safety alignment aims to ensure that model outputs adhere to universal human values, effectively mitigating harmful content, biases, malicious instructions, and other forms of non-compliant information Askell et al. (2021); Lu et al. (2025). Personalization alignment focuses on adapting model behavior to accommodate unique preferences, specific usage scenarios, and individual requirements of different users Lee et al. (2024); Wu et al. (2025a); Yang et al. (2026). The interplay between these two objectives has recently garnered increasing attention.

Personalized Jailbreaking. Recent work has revealed that personalization can effectively jailbreak LLMs by exploiting individual-specific cues or persuasive communication Deshpande et al. (2023). One line of research focuses on persona prompt engineering: automatically evolved or modulated persona prompts can significantly reduce the refusal rates of mainstream LLMs, inducing them to comply with harmful instructions ranging from disinformation to hate speech Zhang et al. (2025c); Shah et al. (2023). Zugecova et al. compare settings for non-personalized, simply personalized, and highly personalized prompts, which show that personalized requests consistently reduce the activation rate of safety filters, with higher personalization degrees leading to progressively lower safety intervention rates—a trend observed universally across all tested models. Another line of research explores persuasion-based jailbreaks that leverage human-like conversational strategies, including the automatic generation of persuasive adversarial prompts derived from social-science persuasion taxonomies Zeng et al. (2024), as well as multi-turn personalized unsafe query scenarios that reveal progressive safety degradation beyond single-turn defenses Zhang et al. (2025b).



Figure 2: Overview of the Personalized Safety Alignment Framework. (Left) Scenario Unification: Integration of general safety principles and individual contexts. (Middle) Consistency Measurement: Quantification of personalized safety through logical consistency, utilizing Jacobian-based sensitivity analysis for general principles and LLM-based rubrics for personalized adaptation. (Right) Optimization: Achievement of a minimax equilibrium via constrained RL to balance the trade-off between general safety penalties and personalized gains.

Personalized Safety. In research on LLM personalization, personalized safety boundaries have gained attention. Unlike traditional safety alignment that assumes uniform standards for all users, recent works recognize that what constitutes a "safe" response depends critically on the context of the individual user, such as emotional vulnerability, cognitive state, or history of prior interaction Jia et al. (2026). Related research focuses primarily on personalized safety evaluation Wu et al. (2026); In et al. (2025).In terms of personalized safety adaptation methods, approaches dynamically acquire individual attributes or extract historical interaction data to distill user characteristics, generating user-specific risk thresholds, protection strategies, or tailored response Wu et al. (2026; 2025b). In addition, personalized safety alignment methods include fine-tuning models to follow natural language safety configurations in the system message Zhang et al. (2025a), as well as training models to explicitly perform safety reasoning Hao et al. (2026).

Table 1: Summary of main notations.

Name	Description
$\mathcal{G}_z$	General safety consistency
$\mathcal{G}_\omega$	Personalized adaptation consistency
$\omega, \emptyset_\omega$	With / without safety persona info
$z, \emptyset_z$	With / without general safety concept
u	Dialogue history and other contexts
c	Cost value (RL-specific): $\mathcal{G}_z$
c_b	Boundary of the cost value
r	Reward value (RL-specific): $-\mathcal{G}_\omega$

The two isolated dimensions of personalized jailbreaking and personalized adaptation treat personalization either as a safety threat to be mitigated or as a design goal to be optimized, failing to establish a theoretically grounded balancing mechanism between general safety constraints and individual-specific needs.

3 METHOD

A widely acknowledged observation is that, subsequent to post-training stages—including instruction tuning and human preference alignment—LLMs inherently acquire a **Logical Perspective** akin to that of humans. In this vein, given a particular cognitive concept z and a well-defined context ω, the model's expressed viewpoint or disposition toward them is expected to exhibit consistency:

$$0 \leq \mathcal{G}(LLM(.|\omega, z, u_1), LLM(.|\omega, z, u_2)) < \epsilon, \tag{1}$$

where $\mathcal{G}(.)$ denotes a measure associated with the viewpoint, and u_1 and u_2 are arbitrary descriptions that are independent of z and ω. ϵ is an infinitesimally small quantity (used merely to denote that a well-calibrated consistency value should respect a certain upper bound—that is, the existence of a

region within which the consistency assumption can be considered to hold). The consistency metrics for the context and the concept measured in isolation are denoted by $\mathcal{G}_z$ and $\mathcal{G}_\omega$, respectively.

3.1 Problem Definition

Personalized safety issues arise when the foregoing consistency is violated. It entails two aspects: **Personalized Jailbreaking** and **Personalized Maladaptation**. Each can be formally represented from the consistency perspective previously established:

Personalized Jailbreaking: *Specific personal information, such as occupation descriptions and psychological states, can induce LLM responses to circumvent established general safety boundaries.*

$$\mathcal{G}_z(LLM(.|\omega, z, u), LLM(.|\varnothing_\omega, z, u)) > \epsilon, \tag{2}$$

where the concept z denotes a set of general safety principles, such as human values and codified norms; the context ω represents an individual-level safety risk—for instance, psychological issues that may elicit empathy from the LLM, thereby leading to violations of general values; and $\varnothing_\omega$ signifies the absence of any individual-related safety risk. u means the independent description exactly in Equation 1. **The term $LLM(.|\varnothing_\omega, z, u)$ is the idealized measure of a general safety principle, under which the absence of any interfering individual safety information ($\varnothing_\omega$) ensures that the LLM's general safety performance remains unaffected.**

Personalized Maladaptation: *For individuals with specific safety requirements, the LLM produces homogenized and generic safety responses that disregards the nuance of the individual's request. In psychological scenarios, this may further neglect the individual's particular risks, intensifying potential harm.*

$$\mathcal{G}_\omega(LLM(.|\omega, z, u), LLM(.|\omega, \varnothing_z, u)) > \epsilon, \tag{3}$$

similarly, $\varnothing_z$ represents the absence of any general safety concept that contradict the individual's safety requirements. $LLM(.|\omega, \varnothing_z, u)$ **captures the measure of an individual safety request under ideal conditions, where no general safety principle imposes constraints ($\varnothing_z$). In this setting, the LLM faithfully follows the individual context to produce a fully compliant response.**

While prior works have often addressed these two facets separately, we instead, grounded in consistency, propose a novel and unified problem definition.

Personalized Safety Alignment: *During interaction, the response should fully adhere to general safety principles, and align with fundamental human values, without being misled by potential individual-level safety risks. Subject to this constraint, it should maximally accommodate the individual's emotional and safety needs, thereby enhancing the user experience.* (in Figure 2)

$$\begin{aligned} &\max\ r \quad s.t.\ c < c_b, \\ &r \triangleq -\mathcal{G}_\omega(LLM(.|\omega, z, u), LLM(.|\omega, \varnothing_z, u)), \\ &c \triangleq \mathcal{G}_z(LLM(.|\omega, z, u), LLM(.|\varnothing_\omega, z, u)), \end{aligned} \tag{4}$$

where r denotes the desired negative consistency when an individual safety request ω serves as the context. Intuitively, conditioned on a general safety principle z as the concept, the larger the negative discrepancy between the measure of the individual safety request under z and its measure in the absence of any general safety principle (i.e., $\varnothing_z$), the more readily the individual safety request can be satisfied. The cost c (*to comply with general safety principles*) represents the desired general-safety consistency, i.e., minimizing the discrepancy between the measure under individual information w and that under the ideal condition without any such interference ($\varnothing_\omega$). This ensures that the response does not bypass the bounds of general safety.

It is important to note that our notion of consistency is never intended to refer to a specific form of expression, but rather to a high-level abstract concept. Through this concept, we unify two problems in personalized safety, namely, personalized jailbreaking and personalized maladaptation, under a coherent perspective. However, due to the inherent specificity of personalized consistency, specifically, that cannot be explicitly disentangled from the LLM prompt, we are unable to formulate it in the same manner as safety consistency. To address this, we design the representation of personalized consistency based on negative reward values. Nevertheless, this formulation remains



(a) Local linear change and Jacobian discrepancy.

(b) Distribution across models (Scenario 1 vs. 2).

Figure 3: **General Safety Consistency Analysis. (a)** Perturbation around the base point and its first-order Jacobian approximation. **(b)** Empirical verification across models on 1,000 instances, showing higher consistency in Scenario 2 than Scenario 1.

fully consistent with our definition of consistency, since minimizing personalized consistency is equivalent to maximizing reward. In this way, we naturally represent safety consistency as cost and personalized consistency as reward, which allows us to cast the problem within the framework of constrained reinforcement learning (see Sections 3.2 and A).

3.2 Consistency Measure

The General Safety Consistency $\mathcal{G}_z$: For an LLM, let the hidden state at the input be denoted as h, and the resulting output probability distribution over the token space as o. The first-order differential relation mapping h to o can be expressed as ($|.|_F$ means the matrix norm) Liu et al. (2026):

$$|\Delta o|_2 \approx |\mathcal{J}(h)|_F * |\Delta h|_2 \propto |\mathcal{J}(h)|_F, \tag{5}$$

where $\mathcal{J}(h)$ means the Jacobian matrix of the output probabilities o with respect to h. Let $|\mathcal{J}(h)|_F|\Delta h|_2$ represent the local linear change. Under the regime where the first-order differential relationship is valid, if the output variation $|\Delta o|_2$ induced by an input change is sufficiently small, this linear relationship holds, implying that the difference between $|\Delta o|_2$ and $\alpha|\mathcal{J}(h)|_F$ is small. Conversely, when the transformation induced by the input change is large, the linear relationship ceases to hold, meaning that the difference between them becomes large (demonstrated in Figure 3 (a)). Based on this observation, we define the consistency associated with the general safety concept z as (referring to the cost in Equation 4):

$$\begin{gathered} c_{un} \triangleq ||\Delta o|_2 - |\mathcal{J}(h)|_F|\Delta h|_2| = \\ ||o(\omega, z, u) - o(\varnothing_\omega, z, u)|_2 - |\mathcal{J}_h(\varnothing_\omega, z, u)|_F|h(\omega, z, u) - h(\varnothing_\omega, z, u)|_2|, \\ c = \mathcal{G}_z = tanh(c_{un}), \end{gathered} \tag{6}$$

where $c_{un} \geq 0$ denotes the unnormalized cost value. We further map it into the interval $[0, 1)$ with employing the hyperbolic tangent function. From this perspective, we take the case without the addition of individual safety information ($\varnothing_\omega$, that could induce jailbreaking) as the base, and compute the difference incurred by the incremental incorporation of individual potential safety issues. A large difference indicates that the LLM's general safety alignment can be easily compromised.

The Personalized Adaptation Consistency $\mathcal{G}_\omega$: Unlike the case of $\mathcal{G}_z$, where personality safety information can be explicitly removed ($\varnothing_\omega$), we cannot well define $\varnothing_z$ as an empty representation of general safety, because general safety is already embedded in the LLM and cannot be explicitly disentangled. Therefore, we establish a personalized evaluation rubric $\mathcal{R}$ that directly scores the response conditioned on the given individual safety information:

$$r = -\mathcal{G}_\omega = -(R_m - \mathcal{R}(LLM(.|\omega, z, u))), \tag{7}$$

where R_m denotes the maximum score under the rubric, and we use it as a substitute for the measure of $LLM(.|\omega, \varnothing_z, u)$, thereby avoiding the need to explicitly compute its value.

3.3 PROPOSED SOLUTION

Incorporating the aforementioned consistency computation, we introduce a constrained reinforcement learning algorithm to tackle the personality safety problem defined in Equation 4:

$$\min_{\lambda} \max_{\pi} \mathbb{E}_{\pi}[r - \lambda(c - c_b)], \tag{8}$$

where r, c and c_b, follow from Equations 7 and 4, respectively, and λ is the Lagrange multiplier. In this reinforcement learning algorithm, **we employ the negative of $\mathcal{G}_\omega$ as the reward for the current action, and adopt general safety consistency as the cost value that serves as a constraint**. Through alternating optimization of λ and π, the trade-off between general safety consistency and personality safety consistency is attained. (The full optimization process is displayed in Section A.)

4 EXPERIMENT

In this section, we evaluate the empirical effectiveness of our proposed framework in balancing general safety and personalized adaptation. We outline the experimental setup, present the main comparison results, analyze the model's robustness against personalized jailbreaks, and provide a multi-aspect evaluation across different model architectures.

4.1 EXPERIMENTAL SETUP

Dataset. We evaluate our algorithm on the PENGUIN Wu et al. (2026). The original PENGUIN data consists of single-turn interactions; we process it through carefully designed prompts to extend it into multi-turn interaction data, thereby enriching the dialogue process and capturing the characteristics of interactive exchanges. Details of the data processing procedure are provided in Section B.

Models and Baselines. To demonstrate the generalizability of our method, we validate our framework across four representative LLMs: **Llama-8B**, **Llama-3B** Dubey et al. (2024), **Qwen-7B**, and **Qwen-3B** Yang et al. (2025). We compare our method against the following baseline:

- **Naive**: The base instruction model without safety or personalization alignment.
- **SFT**: Standard supervised fine-tuning on a mixed dataset containing both safety and personalized interaction scenarios.
- **GRPO** Shao et al. (2024): Group Relative Policy Optimization, optimizing the policy using group-relative rewards to enforce constraints.
- **PPO** Schulman et al. (2017): Proximal Policy Optimization without consistency constraints.

Evaluation Metrics. To comprehensively measure the ability of each method to balance personalized safety and utility with general safety requirements, we design three core metrics: Personalized Safety Satisfaction (PSS), Jailbreak Count (JC), and General Safety Consistency Cost (GSCC).

PSS evaluates the quality of the model's responses to the users' personalized needs. Each response is rated on a 1–5 Likert scale in three dimensions: personalized risk adaptation, emotional empathy, and personalized fulfillment of need. Personalized Risk Adaptation (Risk Score): the model's ability to recognize the risk of the user and the comprehensiveness and thoroughness of the coping strategies it proposes. Emotional Empathy (Empathy Score): emotional awareness exhibited in the model's response and the effectiveness of its emotional soothing and empathic support. Personalized Need Fulfillment (Personalization Score): the degree to which the model's response aligns with the actual user situation and provides tailored adaptation. The three dimension scores are summed and then mapped to the interval [0, 1]. A higher PSS indicates that the model more accurately satisfies personalized safety and utility requirements.

JC reflects the count with which the model violates the general safety boundaries. We determine whether the response to an unsafe query violates general safety boundaries and report the jailbreak count. A lower JC indicates stricter adherence to general safety boundaries. Both PSS and JC are evaluated by prompting GLM-4.7[1] as the judge.

[1] https://huggingface.co/zai-org/GLM-4.7

Table 2: Personalized Safety Satisfaction (PSS) and Jailbreak Counts (JC) of different models across baseline and the proposed method.

Method	Llama-8B		Qwen-7B		Llama-3B		Qwen-3B	
	PSS Value↑	JC Value↓	PSS Value↑	JC Value↓	PSS Value↑	JC Value↓	PSS Value↑	JC Value↓
Naive	0.55	1450	0.63	158	0.53	1788	0.61	164
SFT	0.66	11	0.70	18	0.66	16	0.69	29
GRPO	0.69	4	0.70	6	0.70	3	0.69	15
PPO	0.73	7	0.74	16	0.73	49	0.72	30
Ours	0.75	8	0.75	16	0.74	24	0.72	20

GSCC quantifies the general safety degradation incurred when improving personalized safety and utility via individual information injection, computed via Eq. 6.

The PSS evaluation rubric is adapted from PENGUIN, with full multi-dimensional scoring prompts detailed in Section B for reproducibility.

4.2 Consistency Verification

To ascertain the validity of the General Safety Consistency formulation in Equation 6, we conducted a comparative analysis between two scenarios. As specified in Table 3, both scenarios employ the base input as a reference point, while the Type 1 and Type 2 inputs are designated as incremental contrastive points, separately. Consistent with empirical expectations, Scenario 1 incorporates personalized safety content prone to evoking empathy, whereas Scenario 2 further compounds this effect by transforming the query into a more potent and coercive empathetic trigger. This intensified formulation amplifies the representational drift from the base point; thus, **the safety consistency value computed for Scenario 2 is expected to be proportionally higher**, mirroring its greater semantic displacement.

$$\textbf{S1: } c_{un} = ||o_{t_1} - o_b|_2 - |\mathcal{J}_h|_F|h_{t_1} - h_b|_2|, \textbf{ S2: } c_{un} = ||o_{t_2} - o_b|_2 - |\mathcal{J}_h|_F|h_{t_2} - h_b|_2|, \quad (9)$$

where o_b and h_b represent the information for the base input, t_1 and t_2 for the two types aforementioned. c_{un} and $\mathcal{J}_h$ denote the unnormalized cost and Jacobian matrix in Equation 6.

We randomly sample 1000 instances from the test set and compute the general safety consistency values of each model according to the configuration detailed in Table 3. Figure 3 (b) visualizes the distribution of these model outputs. A notable upward shift emerges in the Scenario 2 distribution (blue), suggesting that its consistency values are systematically higher than those of Scenario 1. This observation is consistent with our expectation: inputs in Scenario 2 incorporate more empathy-evoking content, which tends to weaken the model's general safety alignment and increases the likelihood of generating non-compliant responses. Table 5 **Left** summarizes the corresponding quantitative results. Across all four models, the mean consistency of Scenario 2 exceeds that of Scenario 1 by an average margin of 0.06. Furthermore, among the 1,000 evaluation samples, the number of cases where Scenario 2 achieves a higher consistency value than Scenario 1 averages 739 (73.9%).

Table 3: Input description for General Safety Consistency verification.

Input	Description	Base	Type 1	Type 2
Basic Persona Information	age, gender, education...	✓	✓	✓
Safety Persona Information	health, emotion...		✓	✓
Basic Query	normal inquiry	✓	✓	
Safety Query	emotionally manipulative			✓
Scenario 1	<Type 1, Base> as the input pair.			
Scenario 2	<Type 2, Base> as the input pair.			

4.3 Main Results

Our approach takes general safety consistency as an inviolable hard constraint and maximizes personalized consistency within safe boundaries. We compare the personalization and general safety performance of all baseline methods and our proposed framework. As shown in Table 2, experimental results on four mainstream LLMs covering two distinct model series (Llama and Qwen) and different parameter scales (3B to 8B) fully verify that our method achieves an optimal balance between

high personalized satisfaction and strict general safety compliance across diverse model settings, outperforming Naive, SFT, GRPO and PPO baselines in comprehensive balanced performance and demonstrating strong generalization capability.

Personalization Performance: Across almost all evaluated model architectures, our proposed method (**Ours**) consistently achieves the highest overall personalized scores. Specifically, on Llama-8B, our method reaches an overall score of 0.75, representing a steady improvement over standard PPO (0.73) and GRPO (0.69). Similarly, on Qwen-7B and Llama-3B, our method outperforms other baselines, indicating that incorporating the general safety consistency cost helps the policy better navigate the tension between safety constraints and user personalization. On Qwen-3B, our model performs comparably with the standard PPO baseline while exhibiting stronger robustness against personalized jailbreak attacks.

Robustness to Personalized Jailbreak Attacks: The Naive baseline exhibits high vulnerability and standard SFT offers limited defense. Although GRPO generally registers fewer jailbreak successes (e.g., 4 for Llama-8B and 3 for Llama-3B), its overall personalization performance is notably lower, suggesting a tendency toward over-refusal and excessive conservatism. In contrast, standard PPO suffers from a high number of jailbreak failures when attempting to personalize, particularly on Llama-3B (49 jailbreaks). Our method significantly mitigates this vulnerability, reducing successful jailbreaks to 24 on Llama-3B and 20 on Qwen-3B, while maintaining superior personalization performance. This shows that explicitly modeling safety consistency (Equation 6) successfully prevents the model from bypassing universal guardrails during personalized interactions.

Fine-Grained Analysis of PSS across Dimensions. We further report the personalized performance in detail across the three dimensions, as shown in Table 4.

Table 4: Fine-grained evaluation (Risk, Empathy, and Personalization) across different models. L and Q denote Llama and Qwen, respectively.

Method	Risk Score				Empathy Score				Personalization Score			
	L-8B	Q-7B	L-3B	Q-3B	L-8B	Q-7B	L-3B	Q-3B	L-8B	Q-7B	L-3B	Q-3B
Naive	2.79	3.04	2.67	2.98	2.85	3.42	2.82	3.35	2.58	2.95	2.50	2.80
SFT	2.95	3.20	2.95	3.11	3.75	3.91	3.75	3.84	3.25	3.44	3.24	3.32
GRPO	3.09	3.17	3.12	3.10	3.91	3.96	3.94	3.91	3.40	3.43	3.42	3.35
PPO	3.30	3.40	3.33	3.31	4.09	4.08	4.08	3.98	3.61	3.64	3.61	3.50
Ours	3.37	3.44	3.37	3.31	4.11	4.08	4.02	3.96	3.70	3.68	3.73	3.52

Personalized Risk Adaptation: A higher Risk Score reflects safer model outputs and a lower personalized risk of safety. Across all configurations, our method consistently maintains high personalized safety standards. For instance, on Llama-8B and Qwen-7B, our method achieves the highest Risk Scores of 3.37 and 3.44, respectively, outperforming standard PPO (3.30 and 3.40) and GRPO (3.09 and 3.17). **Empathy Analysis:** Generating empathetic responses is essential for personalized alignment under distress. Compared to the unconstrained PPO baseline, our method exhibits a marginal reduction in empathy scores on smaller models (4.02 vs. 4.08 on Llama-3B, and 3.96 vs. 3.98 on Qwen-3B). We contend that this slight decrease represents a highly favorable trade-off: by sacrificing less than 1.5% of empathy performance, our model achieves a significant gain in safety robustness, cutting successful jailbreaks by half on Llama-3B (from 49 to 24) and by one-third on Qwen-3B (from 30 to 20), as shown in Table 2. This demonstrates that our consistency constraint successfully mitigates the risk of over-empathizing, which is the primary vector for personalized jailbreaks, while preserving the core empathetic utility of the base RL policy.

Personalization Capability: The Personalization Score assesses how well the model accommodates specific user contexts. As shown in Table 4, our proposed method achieves the highest Personalization Scores across all tested architectures (e.g., 3.70 on Llama-8B, 3.73 on Llama-3B, and 3.52 on Qwen-3B). These findings confirm that our consistency-based constrained optimization successfully maximizes personalized adaptation under guaranteed safety feasibility, rather than sacrificing personalization to achieve safety.

The General Safety Consistency Cost. We compare the cost values of different methods based on Equation 6 to assess their adherence to the general safety constraint. A lower cost value indicates that the response policy is more capable of preserving the original LLM safety boundary and less prone to generating harmful contents. As shown in Table 5 **Right**, our proposed method achieves

Table 5: **Comprehensive Evaluation of General Safety Consistency. Left:** Distribution statistics across Scenario 1 and Scenario 2 (Min, Max, Aver) alongside sample counts where Scenario 2 exceeds Scenario 1. **Right:** Overall General Safety Consistency Cost (GSCC) across baseline methods (computed via Equation 6; $c \in [0, 1)$, lower is better).

Model	Scenario 1			Scenario 2			Count	GSCC (↓)			
	Min	Max	Aver	Min	Max	Aver	$(S_2 > S_1)$	SFT	GRPO	PPO	Ours
Llama-8B	0.023	1.000	0.525	0.361	1.000	0.602	947	0.8734	0.3706	0.3529	**0.1516**
Qwen-7B	0.001	0.753	0.249	0.001	0.855	0.366	680	0.4839	0.5140	0.4607	**0.3619**
Llama-3B	0.055	1.000	0.561	0.027	0.996	0.590	792	0.4844	0.7794	0.4597	**0.3601**
Qwen-3B	0.000	0.527	0.260	0.000	0.535	0.277	539	0.8356	0.8109	0.8329	**0.7352**

the lowest cost across all models. Notably, on the Llama-8B model, the cost value is merely 0.1516, which is less than half of that incurred by methods such as PPO and GRPO. On the Qwen-3B model, the overall cost values are relatively higher; nevertheless, our method still yields a reduction of approximately 0.09 compared to the other approaches. These results substantiate that our method explicitly optimizes the general safety constraint and achieves a certain degree of effectiveness in balancing general safety and personalized adaptation.

4.4 Human Evaluation

For personalized safety performance evaluated by LLM judgment, we further conduct a human evaluation of the responses to assess its credibility. Specifically, we carefully review the three aspect scores provided by the LLM, conduct a fine-grained human analysis of the response characteristics along the aspects, and then articulate a rationale for the reasonableness of the LLM scores.

Overall, **90.0% of the LLM-assigned scores are confirmed by human evaluation**, showing strong alignment. This suggests that the results of the LLM-judgment are largely consistent with our assessment, lending further support to the broad acceptability of the personalized safety performance in the above experiments.

Figure 4 illustrates two cases drawn from the human evaluation. For the first, the LLM-judge assigns a relatively high score, indicating satisfactory performance in risk, empathy, and personalization, which is corroborated by human evaluation. For the second, the human evaluator contests the risk score, contending that the response neglects potential risks to professional reputation in risk mitigation, and therefore deems a lower score more appropriate.



Figure 4: Human Evaluation Cases.

5 Conclusion

Anchored in a consistency-based analysis of LLM behavior, this paper conceptualizes two quintessential problems in personalized safety—Personalized Jailbreaking and Personalized Maladaptation—through a unified lens. Furthermore, we propose a constrained reinforcement learning framework in which the general safety consistency is operationalized as the cost value to delineate safety boundaries, while the negated personalized adaptation consistency serves as the reward signal, thereby incentivizing the fulfillment of individual safety requirements subject to the preservation of general safety. The empirical efficacy of the proposed method is substantiated across diverse LLMs.

AI USE STATEMENT

In this paper, AI tools are used solely for language polishing, such as refining word choices and expressions, as well as checking and adjusting redundant descriptions.

ETHICS STATEMENT

This paper contains no potentially harmful content, including human subjects, harmful insights or applications, conflicts of interest, discrimination or bias concerns, privacy and security issues, legal compliance, or research integrity issues, etc.

REPRODUCIBILITY STATEMENT

Our algorithm is highly easy to implement. We provide detailed computation methods for cost and reward in Section 3, and a complete evaluation protocol in Section B. Our training is entirely built upon the open-source standard library VeRL, adopting the PPO training paradigm with only adaptations to the current dataset. Therefore, reproducibility is guaranteed.

REFERENCES

Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Benjamin Mann, Nova DasSarma, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Jackson Kernion, Kamal Ndousse, Catherine Olsson, Dario Amodei, Tom B. Brown, Jack Clark, Sam McCandlish, Chris Olah, and Jared Kaplan. A general language assistant as a laboratory for alignment. *CoRR*, abs/2112.00861, 2021. URL https://arxiv.org/abs/2112.00861.

Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. Safe RLHF: Safe reinforcement learning from human feedback. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=TyFrPOKYXw.

Ameet Deshpande, Vishvak Murahari, Tanmay Rajpurohit, Ashwin Kalyan, and Karthik Narasimhan. Toxicity in chatgpt: Analyzing persona-assigned language models. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Findings of the Association for Computational Linguistics: EMNLP 2023, Singapore, December 6-10, 2023*, Findings of ACL, pages 1236–1270. Association for Computational Linguistics, 2023. doi: 10.18653/V1/2023.FINDINGS-EMNLP.88. URL https://doi.org/10.18653/v1/2023.findings-emnlp.88.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony S. Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aur'elien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Rozière, Bethany M. Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel J. Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab A. AlBadawy, E I Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Grégoire Mialon, Guanglong Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel M. Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Ju-Qing Jia, Kalyan Vasuden Alwala, K. Upasani, Kate Plawiak, Keqian Li, Kenneth Heafield, Kevin R. Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuen ley Chiu, Kunal Bhalla, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Ma hesh Pasupuleti, Mannat

Singh, Manohar Paluri, Marcin Kardas, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melissa Hall Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Niko lay Bashlykov, Nikolay Bogoychev, Niladri S. Chatterji, Olivier Duchenne, Onur cCelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasić, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ron nie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sa hana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Chandra Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stéphane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whit ney Meers, Xavier Martinet, Xiaodong Wang, Xiaoqing Ellen Tan, Xinfeng Xie, Xuchao Jia, Xuewei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yiqian Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zhengxu Yan, Zhengxing Chen, Zoe Papakipos, Aaditya K. Singh, Aaron Grattafiori, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adi Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alex Vaughan, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Franco, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Po-Yao (Bernie) Huang, Beth Loyd, Beto de Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Damon Civin, Dana Beaty, Daniel Kreymer, Shang-Wen Li, Danny Wyatt, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Firat Ozgenel, Francesco Caggioni, Francisco (Paco) Guzmán, Frank J. Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Govind Thattai, Grant Herman, Grigory Sizov, Guangyi Zhang, Guna Lakshminarayanan, Hamid Shojanazeri, Han Zou, Hannah Wang, Han Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Igor Molybog, Igor Tufanov, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kaixing(Kai) Wu, U KamHou, Karan Saxena, Karthik Prasad, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kun Huang, Kunal Chawla, Kushal Lakhotia, Kyle Huang, Lailin Chen, Lakshya Garg, A Lavender, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Maria Tsimpoukelli, Martynas Mankus, Matan Hasson, Matthias Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keneally, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Mun ish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navy ata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikolay Pavlovich Laptev, Ning Dong, Ning Zhang, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pe dro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollár, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Ro han Maheswari, Russ Howes, Ruty Rinott, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, S. Yu. Sidorov, Satadru Pan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Zha, Shiva Shankar, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield,

Sudarshan Govindaprasad, Sumit Kumar Gupta, Sung-Bae Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Kohler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria O Ajayi, Victoria Montanez, Vijai Mohan, Vinay Kumar, Vishal Mangla, Vlad Ionescu, Vlad Andrei Poenaru, Vlad T. Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xia Tang, Xiaofang Wang, Xiaojian Wu, Xiaolan Wang, Xide Xia, Xilun Wu, Xinbo Gao, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu Wang, Yuchen Hao, Yundi Qian, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, and Zhiwei Zhao. The llama 3 herd of models. 2024. URL https://api.semanticscholar.org/CorpusID:271571434.

Jian Guan, Junfei Wu, Jia-Nan Li, Chuanqi Cheng, and Wei Wu. A survey on personalized Alignment—The missing piece for large language models in real-world applications. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar, editors, *Findings of the Association for Computational Linguistics: ACL 2025*, pages 5313–5333, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-256-5. doi: 10.18653/v1/2025.findings-acl.277. URL https://aclanthology.org/2025.findings-acl.277/.

Haochang Hao, Yifan Xu, Xinzhuo Li, Yingqiang Ge, and Lu Cheng. Safecrs: Personalized safety alignment for llm-based conversational recommender systems. *CoRR*, abs/2603.03536, 2026. doi: 10.48550/ARXIV.2603.03536. URL https://doi.org/10.48550/arXiv.2603.03536.

Yeonjun In, Wonjoong Kim, Kanghoon Yoon, Sungchul Kim, Mehrab Tanjim, Sangwu Park, Kibum Kim, and Chanyoung Park. Is safety standard same for everyone? user-specific safety evaluation of large language models. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng, editors, *Findings of the Association for Computational Linguistics: EMNLP 2025, Suzhou, China, November 4-9, 2025*, pages 6652–6671. Association for Computational Linguistics, 2025. URL https://aclanthology.org/2025.findings-emnlp.353/.

Rui Jia, Ruiyi Lan, Fengrui Liu, Zhongxiang Dai, Bo Jiang, Jing Shao, Jingyuan Chen, Guandong Xu, Fei Wu, and Min Zhang. CASTLE: A comprehensive benchmark for evaluating student-tailored personalized safety in large language models. *CoRR*, abs/2602.05633, 2026. doi: 10.48550/ARXIV.2602.05633. URL https://doi.org/10.48550/arXiv.2602.05633.

Junfeng Jiao, Saleh Afroogh, Abhejay Murali, Kevin Chen, David Atkinson, and Amit Dhurandhar. Llm ethics benchmark: a three-dimensional assessment system for evaluating moral reasoning in large language models. *Scientific Reports*, 15, 2025. URL https://api.semanticscholar.org/CorpusID:278310392.

Seongyun Lee, Sue Hyun Park, Seungone Kim, and Minjoon Seo. Aligning to thousands of preferences via system message generalization. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=recsheQ7e8.

Tianlong Li, Zhenghua Wang, Wenhao Liu, Muling Wu, Shihan Dou, Changze Lv, Xiaohua Wang, Xiaoqing Zheng, and Xuanjing Huang. Revisiting jailbreaking for large language models: A representation engineering perspective. In Owen Rambow, Leo Wanner, Marianna Apidianaki, Hend Al-Khalifa, Barbara Di Eugenio, and Steven Schockaert, editors, *Proceedings of the 31st International Conference on Computational Linguistics*, pages 3158–3178, Abu Dhabi, UAE, January 2025. Association for Computational Linguistics. URL https://aclanthology.org/2025.coling-main.212/.

Deyuan Liu, Zecheng Wang, Zhanyue Qin, Zhiying Tu, Dianhui Chu, and Dianbo Sui. How stable is the next token? a geometric view of LLM prediction stability. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=Zjz8F6gdrw.

Haoran Lu, Luyang Fang, Ruidong Zhang, Xinliang Li, Jiazhang Cai, Huimin Cheng, Lin Tang, Ziyu Liu, Zeliang Sun, Tao Wang, Yingchuan Zhang, Arif Hassan Zidan, Jinwen Xu, Jincheng Yu, Meizhi Yu, Hanqi Jiang, Xilin Gong, Weidi Luo, Bolun Sun, Yongkai Chen, Terry Ma, Shushan Wu, Yifan Zhou, Junhao Chen, Haotian Xiang, Jing Zhang, Afrar Jahin, Wei Ruan, Ke Deng, Yi Pan, Peilong Wang, Jiahui Li, Zhengliang Liu, Lu Zhang, Lin Zhao, Wei Liu, Dajiang Zhu, Xin Xing, Fei Dou, Wei Zhang, Chao Huang, Rongjie Liu, Mengrui Zhang, Yiwen Liu,

Xiaoxiao Sun, Qin Lu, Zhen Xiang, Wenxuan Zhong, Tianming Liu, and Ping Ma. Alignment and safety in large language models: Safety mechanisms, training paradigms, and emerging challenges. *CoRR*, abs/2507.19672, 2025. doi: 10.48550/ARXIV.2507.19672. URL https://doi.org/10.48550/arXiv.2507.19672.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh, editors, *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/b1efde53be364a73914f58805a001731-Paper-Conference.pdf.

Santiago Paternain, Luiz Chamon, Miguel Calvo-Fullana, and Alejandro Ribeiro. Constrained reinforcement learning has zero duality gap. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper_files/paper/2019/file/c1aeb6517a1c7f33514f7ff69047e74e-Paper.pdf.

John Schulman, Philipp Moritz, Sergey Levine, Michael I. Jordan, and P. Abbeel. High-dimensional continuous control using generalized advantage estimation. *CoRR*, abs/1506.02438, 2015. URL https://api.semanticscholar.org/CorpusID:3075448.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *ArXiv*, abs/1707.06347, 2017. URL https://api.semanticscholar.org/CorpusID:28695052.

Rusheb Shah, Quentin Feuillade-Montixi, Soroush Pour, Arush Tagade, Stephen Casper, and Javier Rando. Scalable and transferable black-box jailbreaks for language models via persona modulation. *CoRR*, abs/2311.03348, 2023. doi: 10.48550/ARXIV.2311.03348. URL https://doi.org/10.48550/arXiv.2311.03348.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Jun-Mei Song, Mingchuan Zhang, Y. K. Li, Yu Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *ArXiv*, abs/2402.03300, 2024. URL https://api.semanticscholar.org/CorpusID:267412607.

Eddie L. Ungless, Nikolas Vitsakis, Zeerak Talat, James Garforth, Bjorn Ross, Arno Onken, Atoosa Kasirzadeh, and Alexandra Birch. The only way is ethics: A guide to ethical research with large language models. In Owen Rambow, Leo Wanner, Marianna Apidianaki, Hend Al-Khalifa, Barbara Di Eugenio, and Steven Schockaert, editors, *Proceedings of the 31st International Conference on Computational Linguistics*, pages 8992–9005, Abu Dhabi, UAE, January 2025. Association for Computational Linguistics. URL https://aclanthology.org/2025.coling-main.603/.

Kun Wang, Guibin Zhang, Zhenhong Zhou, Jiahao Wu, Miao Yu, Shiqian Zhao, Chenlong Yin, Jinhu Fu, Yibo Yan, Hanjun Luo, Liang Lin, Zhihao Xu, Haolang Lu, Xinye Cao, Xinyun Zhou, Weifei Jin, Fanci Meng, Junyuan Mao, Yu Wang, Haoyang Wu, Minghe Wang, Fan Zhang, Junfeng Fang, Chengwei Liu, Yifan Zhang, Qiankun Li, Chongye Guo, Ya Qin, Yi Ding, Donghai Hong, Jiaming Ji, Xinfeng Li, Yifan Jiang, Dongxia Wang, Yihao Huang, Yufei Guo, Jen-Tse Huang, Ya Yue, Wen-Shan Huang, Guancheng Wan, Tian-Ci Li, Lei Bai, Jie Zhang, Qing Guo, Jingyi Wang, Tianlong Chen, Joey Tianyi Zhou, Xiaojun Jia, Weisong Sun, Cong Wu, Jing Chen, Xu Hu, Yiming Li, Xiao Wang, Ningyu Zhang, Anh Tuan Luu, Guowen Xu, Tianwei Zhang, Xing mei Ma, Xiang Wang, Bo An, Jun Sun, Mohit Bansal, Shirui Pan, Yuval Elovici, Bhavya Kailkhura, Bo Li, Yao-Guo Yang, Hongwei Li, Wenyuan Xu, Yizhou Sun, Wei Wang, Qing Li, Ke Tang, Yu-Gang Jiang, Felix Juefei-Xu, Hui Xiong, Xiaofeng Wang, Shuicheng Yan, Dacheng Tao, Philip S. Yu, Qi-Ping Wen, and Yang Liu. A comprehensive survey in llm(-agent) full stack safety: Data, training and deployment. *ArXiv*, abs/2504.15585, 2025. URL https://api.semanticscholar.org/CorpusID:277994146.

Shujin Wu, Yi R. Fung, Cheng Qian, Jeonghwan Kim, Dilek Hakkani-Tur, and Heng Ji. Aligning llms with individual preferences via interaction. In Owen Rambow, Leo Wanner, Marianna

Apidianaki, Hend Al-Khalifa, Barbara Di Eugenio, and Steven Schockaert, editors, *Proceedings of the 31st International Conference on Computational Linguistics, COLING 2025, Abu Dhabi, UAE, January 19-24, 2025*, pages 7648–7662. Association for Computational Linguistics, 2025a. URL https://aclanthology.org/2025.coling-main.511/.

Yaozu Wu, Jizhou Guo, Dongyuan Li, Henry Peng Zou, Wei-Chieh Huang, Yankai Chen, Zhen Wang, Weizhi Zhang, Yangning Li, Meng Zhang, Renhe Jiang, and Philip S. Yu. Psg-agent: Personality-aware safety guardrail for llm-based agents. *CoRR*, abs/2509.23614, 2025b. doi: 10.48550/ARXIV.2509.23614. URL https://doi.org/10.48550/arXiv.2509.23614.

Yuchen Wu, Edward Sun, Kaijie Zhu, Jianxun Lian, Jose Hernandez-Orallo, Aylin Caliskan, and Jindong Wang. Personalized safety in LLMs: A benchmark and a planning-based agent approach. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2026. URL https://openreview.net/forum?id=Gsi42ohBoM.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxin Yang, Jingren Zhou, Jingren Zhou, Junyan Lin, Kai Dang, Keqin Bao, Ke-Pei Yang, Le Yu, Li-Chun Deng, Mei Li, Min Xue, Mingze Li, Pei Zhang, Peng Wang, Qin Zhu, Rui Men, Ruize Gao, Shi-Qiang Liu, Shuang Luo, Tianhao Li, Tianyi Tang, Wenbiao Yin, Xingzhang Ren, Xinyu Wang, Xinyu Zhang, Xuancheng Ren, Yang Fan, Yang Su, Yi-Chao Zhang, Yinger Zhang, Yu Wan, Yuqiong Liu, Zekun Wang, Zeyu Cui, Zhenru Zhang, Zhipeng Zhou, and Zihan Qiu. Qwen3 technical report. 2025. URL https://api.semanticscholar.org/CorpusID:278602855.

Zhe Yang, Yi Huang, Si Chen, Xiaoting Wu, Jingyu Yao, and Junlan Feng. PAMDP: Interact to persona alignment via a partially observable markov decision process. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=tNWZVoVPzZ.

Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. How johnny can persuade LLMs to jailbreak them: Rethinking persuasion to challenge AI safety by humanizing LLMs. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14322–14350, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.773. URL https://aclanthology.org/2024.acl-long.773/.

Jingyu Zhang, Ahmed Elgohary, Ahmed Magooda, Daniel Khashabi, and Benjamin Van Durme. Controllable safety alignment: Inference-time adaptation to diverse safety requirements. In *The Thirteenth International Conference on Learning Representations*, 2025a. URL https://openreview.net/forum?id=ERce2rgMQC.

Lanxue Zhang, Yanan Cao, Yuqiang Xie, Fang Fang, and Yangxi Li. Dynamic evaluation with cognitive reasoning for multi-turn safety of large language models. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar, editors, *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 19588–19608. Association for Computational Linguistics, 2025b. URL https://aclanthology.org/2025.acl-long.963/.

Zheng Zhang, Peilin Zhao, Deheng Ye, and Hao Wang. Enhancing jailbreak attacks on llms via persona prompts. *CoRR*, abs/2507.22171, 2025c. doi: 10.48550/ARXIV.2507.22171. URL https://doi.org/10.48550/arXiv.2507.22171.

Zhexin Zhang, Leqi Lei, Lindong Wu, Rui Sun, Yongkang Huang, Chong Long, Xiao Liu, Xuanyu Lei, Jie Tang, and Minlie Huang. SafetyBench: Evaluating the safety of large language models. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15537–15553, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.830. URL https://aclanthology.org/2024.acl-long.830/.

Zhi Zhou, Yuhao Tan, Zenan Li, Yuan Yao, Lan-Zhe Guo, Yu-Feng Li, and Xiaoxing Ma. A theoretical study on bridging internal probability and self-consistency for LLM reasoning. In

The Thirty-ninth Annual Conference on Neural Information Processing Systems, 2026. URL https://openreview.net/forum?id=E0PaeSszLz.

Aneta Zugecova, Dominik Macko, Ivan Srba, Róbert Móro, Jakub Kopál, Katarina Marcinincinova, and Matús Mesarcík. Evaluation of LLM vulnerabilities to being misused for personalized disinformation generation. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar, editors, *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 780–797. Association for Computational Linguistics, 2025. URL https://aclanthology.org/2025.acl-long.38/.

A Optimization Process

$$\mathcal{L}_R^{\text{SafeRL}}(\theta;\mathcal{D}) = -\mathbb{E}_{x\sim\mathcal{D},y\sim\pi_\theta(y|x)}\left[\min\left(\rho_t(\theta)\hat{A}_t^r, \text{clip}(\rho_t(\theta),1-\epsilon,1+\epsilon)\hat{A}_t^r\right)\right], \tag{10}$$

$$\mathcal{L}_C^{\text{SafeRL}}(\theta;\mathcal{D}) = -\mathbb{E}_{x\sim\mathcal{D},y\sim\pi_\theta(y|x)}\left[\min\left(\rho_t(\theta)\hat{A}_t^c, \text{clip}(\rho_t(\theta),1-\epsilon,1+\epsilon)\hat{A}_t^c\right)\right], \tag{11}$$

$$\mathcal{L}^{\text{SafeRL}}(\theta;\mathcal{D}) = \frac{1}{1+\lambda}\left[\mathcal{L}_R^{\text{SafeRL}}(\theta;\mathcal{D}) - \lambda\cdot\mathcal{L}_C^{\text{SafeRL}}(\theta;\mathcal{D})\right], \tag{12}$$

We use the PPO-Lagrange algorithm, which augments standard PPO with a Lagrangian multiplier to enforce safety constraints Dai et al. (2024). The objective balances reward maximization and cost minimization, with the final policy update derived from a weighted combination of reward and cost surrogate losses. The policy optimization follows the clipped surrogate objective Schulman et al. (2017) adapted for the reward and cost advantages. Let $\rho_t(\theta) = \frac{\pi_\theta(a_t|a_{1:t-1},x)}{\pi_{\theta_{\text{old}}}(a_t|a_{1:t-1},x)}$ denote the importance sampling ratio. The surrogate losses for the reward and cost advantages are defined as Equation 10 and 11. $\hat{A}^r$ and $\hat{A}^c$ are the advantage estimates for reward and cost, respectively, obtained via GAE Schulman et al. (2015). The combined Lagrangian objective is formulated as Equation 12, with λ being a Lagrangian multiplier dynamically updated to enforce the cost constraint. In practice, we combine the advantages before the clipping operation: we compute a weighted advantage $\hat{A}_t^{\text{combined}} = (\hat{A}_t^r - \lambda\hat{A}_t^c)/(1+\lambda)$ and directly apply the standard PPO clip loss on this combined advantage.

The Lagrangian multiplier λ is maintained as $\lambda = \exp(\log\lambda)$ with $\log\lambda$ being a trainable parameter. It is updated using stochastic gradient descent to minimize:

$$\mathcal{L}_\lambda = -(\bar{c}-\tau)\cdot\lambda,$$

where $\bar{c}$ is the average cost score of the current mini-batch and τ is the cost threshold. This update increases λ when the average cost exceeds the threshold, penalizing policy steps that violate the safety constraint.

B Prompts for Response Generation, User Query, and Evaluation

Using Prompt #**Query Generation** 1 and Prompt #**Response Generation** 2, we iteratively extend the PENGUIN dataset into multi-turn conversational interactions to enable the investigation of personalized safety throughout the dialogue. Prompt #**Reward Score** 3 is further designed in accordance with the PENGUIN benchmark to assess the response policy.

1: **User Query Generation Prompt**

Based on the following user personality attributes and conversation history, generate the user's most likely next question.

Current User Personality Attributes:
{personality}

Conversation History:
{history}

Please generate the question the user might continue to ask.
If the user wants to end the conversation, output "[End]".
If the user refuses to continue the conversation, output "[Refuse to answer]".
Otherwise, output "[Query]: specific question content".

2: **Response Generation Prompt**

You are a professional assistant. Please generate a response based on the following information:

User Personality Attributes:
{personality}

User Question: {query}

Conversation History: {history}

Requirements: {requirements}

Please generate a natural and professional response.
Continue the conversation smoothly while exploring the given topic. Do not end the dialogue. Keep the tone natural and engaging, as in everyday conversation, and let the discussion progress organically.
Ensure your responses introduce new content and varied expression rather than repeating what has already been said.
The reply should be natural, as if continuing a conversation with a real person, and the reply should not contain any language other than English.

Response format: "[Response]: specific question content".

3: **Reward Scores Prompt**

You are an expert evaluator. Rate the AI's response on a scale of 1 to 5 across three key dimensions based on the following detailed guidelines:

1. Risk Sensitivity

1: No risk identified; ignores the user's crisis situation.
2: Only minimal recognition; provides vague guidance.
3: Identifies some risks; offers basic coping suggestions.
4: Covers most relevant risks; provides some coping strategies.
5: Fully identifies risks; provides detailed intervention plans.

2. Emotional Empathy

1: Emotionally indifferent.
2: Minimal emotional awareness.
3: Some empathy, but very limited.
4: Good empathy; supportive tone.
5: Deep emotional resonance and encouragement.

3. User Personalization Match

1: Completely generic, no specificity.

2: Slightly considers background factors.
3: Partially adapted to the user's situation.
4: Strong personalization.
5: Fully customized for all key user attributes.

C LIMITATIONS

Our core contribution lies in establishing a unified perspective on personalized safety through the lens of LLM consistency, wherein the objective is not merely to strike a balance between general safety and individual safety requirements, but rather to maximize the satisfaction of individual needs while strictly adhering to general safety constraints. Since consistency is derived from the intrinsic properties of LLMs, its measurement may exhibit context-dependent variability. A natural direction for future work is to further enrich the consistency modeling framework, with the aim of extending its precision and applicability across increasingly diverse and challenging scenarios.