VERIFIER RED QUEEN: ADVERSARIAL CO-EVOLUTION OF AGENT SKILLS AND VERIFIERS

Anonymous authors
Paper under double-blind review

ABSTRACT

Reusable agent Skills encode procedural knowledge for long-horizon tasks that require tool use, intermediate artifacts, and task-specific validation. Autonomous Skill evolution depends on reliable fitness signals. When Skills co-evolve with imperfect verifiers, selection can reward incomplete assertions, brittle coverage, and verifier-specific shortcuts over task competence. This feedback loop can produce skill–verifier collusion: both populations converge to transient conventions while performance on hidden tasks declines. We introduce Verifier Red Queen (VRQ), a three-population framework that jointly evolves Solver Skills, Red-Team Verifiers, and Calibrator Verifiers. Red-Team Verifiers generate heterogeneous challenges using metamorphic testing, input perturbations, invariant checks, adversarial tool outputs, and partial-execution audits. These challenges expose failures that checks favored by recent selection fail to detect. Calibrator Verifiers determine whether the challenges preserve task semantics and admit valid solutions, filtering out irrelevant, contradictory, and unsatisfiable objectives. VRQ also maintains a historical hall of fame of effective Skills and Verifiers. Candidates must withstand current opponents and earlier verification strategies, reducing cyclic forgetting and temporal overfitting. We evaluate VRQ under controlled settings with weak-verifier exploitation opportunities and verifier shifts. The evaluation measures task success, hidden-test generalization, false positives, shortcut persistence, verifier diversity, and collusion. Component ablations isolate the contributions of calibration, historical selection, adversarial diversity, metamorphic testing, and population update strategies to robust Skill improvement under search-time verifier exploitation.

1 INTRODUCTION

Large language model agents increasingly rely on reusable procedural knowledge to complete long-horizon tasks that require coordinated tool use, intermediate artifacts, error recovery, and task-specific validation. Agent Skills encode this knowledge as structured collections of instructions, scripts, references, and other inference-time resources. SkillsBench shows that well-designed Skills improve performance across diverse, expertise-intensive tasks, with outcomes depending on their focus and construction(Li et al., 2026). These findings motivate agents that generate, test, and refine their own Skills as tasks, environments, and underlying models evolve.

Autonomous Skill evolution requires reliable identification of behavioral improvements. Evolutionary and quality-diversity methods maintain diverse candidate populations without restricting optimization to a single lineage(Mouret & Clune, 2015)(Bradley et al., 2023). Applying these methods to agent Skills, however, requires reliable fitness signals. Recent work combines Skill generation with automated verification. CoEvoSkills jointly refines a Skill Generator and a Surrogate Verifier, evolving complex Skill packages from diagnostic feedback without exposing protected ground-truth tests(Zhang et al., 2026). Self-evolving benchmarks similarly use multi-level validation to filter automatically constructed agent tasks and trajectories(Guo et al., 2026). Verification therefore becomes an active component of agent evolution.

This coupling introduces a failure mode when the verifier is treated as stationary or uniformly reliable. Skills are selected according to tests and judgments that the current verifier can express. Repeated optimization can favor Skills that exploit incomplete assertions, brittle input coverage, incidental output patterns, or verifier-specific shortcuts while failing the intended task. This proxy exploitation

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: Overview of the Verifier Red Queen framework.

is a form of specification gaming, in which optimization against an imperfect reward produces highly rewarded yet undesired behavior(Denison et al., 2024). Under co-evolution, Skill and verifier populations can adapt to shared conventions, reinforce an incorrect notion of success, and assign high fitness even as hidden-task performance deteriorates. We call this failure *skill–verifier collusion* and its population-level endpoint *co-evolutionary collapse*. Increasing the number of verifier samples does not resolve this temporal failure when verifiers generate invalid or unsatisfiable challenges, forget prior counterexamples, or exhibit surface-level diversity while retaining shared semantic blind spots. Reliable Skill evolution requires verification that is adversarial, semantically calibrated, and resistant to cross-generational forgetting.

We introduce **Verifier Red Queen** (**VRQ**), a three-population framework that co-evolves *Solver Skills*, *Red-Team Verifiers*, and *Calibrator Verifiers*, as illustrated in Figure 1. Solver Skills search for reusable procedures that solve the target task family. Red-Team Verifiers generate heterogeneous challenges using metamorphic tests, input perturbations, invariant checks, adversarial tool outputs, and partial-execution audits. These challenges pressure Skills to satisfy task semantics beyond the checks that recently determined selection. Unrestricted red teaming can produce irrelevant, contradictory, or unsatisfiable tests, so Calibrator Verifiers estimate whether each challenge preserves the intended task and admits a semantically valid solution. VRQ alternates updates across the three populations, allowing improvements in each population to expose weaknesses in the others. It also maintains a historical hall of fame containing effective Skills and Verifiers, requiring candidates to remain robust against current opponents and earlier verification strategies. This historical pressure limits cyclic forgetting and convergence to transient shared conventions.

We evaluate VRQ on agent-skill tasks with controlled opportunities for weak-verifier exploitation. We compare VRQ with fixed verification, conventional surrogate co-evolution, and verifier ensembles, and evaluate robustness after replacing the verifier implementation following evolution. In addition to task success, we measure verifier false positives, visible–hidden test gaps, shortcut survival across generations, verifier diversity, and skill–verifier collusion. Our ablations remove the calibrator, historical hall of fame, red-team diversity, and metamorphic testing, and compare synchronous and asynchronous population updates. This protocol separates genuine Skill robustness from improvements specific to the search-time verifier.

Our contributions are:

- We characterize verifier adaptation as a central failure mode in autonomous agent-skill evolution and distinguish individual verifier gaming, skill–verifier collusion, and population-level co-evolutionary collapse.

- We propose VRQ, which jointly evolves Solver Skills, adversarially diverse Red-Team Verifiers, and Calibrator Verifiers that filter semantically invalid challenges.
- We introduce history-aware selection through a Skill-and-Verifier hall of fame that exposes temporal overfitting, preserves earlier counterexamples, and discourages collapse to short-lived verification conventions.
- We develop an evaluation protocol that measures proxy exploitation, hidden-test generalization, shortcut persistence, verifier diversity, collusion, and robustness to verifier changes, with controlled ablations of VRQ's stabilization mechanisms.

2 Related Work

2.1 Reusable Skills and Self-Improving Language Agents

Language-model agents have evolved from interleaving reasoning and actions toward acquiring persistent procedural knowledge. ReAct coordinates language generation and environmental interaction through explicit reasoning loops(Yao et al., 2022), while Toolformer learns when and how to invoke fixed tools(Schick et al., 2023). Gorilla(Patil et al., 2023) and ToolLLM(Qin et al., 2023) scale API selection and invocation, whereas SkillsBench formalizes reusable Skills as task-level packages containing instructions, programs, references, and validation resources(Li et al., 2026).

Procedural abstractions can also be constructed from demonstrations or experience. Large Language Models as Tool Makers separates reusable function construction from application(Cai et al., 2023); CRAFT abstracts, validates, and retrieves specialized code tools(Yuan et al., 2023); and Voyager builds an expanding library of executable Minecraft skills through curriculum generation, repair, and retrieval(Wang et al., 2023). SkillWeaver similarly synthesizes callable website-interaction skills and refines them using execution feedback(Zheng et al., 2025). Reflexion stores verbal failure summaries in episodic memory(Shinn et al., 2023), while Self-Refine alternates generation, critique, and revision(Madaan et al., 2023). Execution-grounded approaches include SWE-agent(Yang et al., 2024), Darwin Gödel Machine(Zhang et al., 2025), CoEvoSkills(Zhang et al., 2026), and TRACE(Guo et al., 2026), which respectively use repository tests, self-modifying agent archives, co-evolving skill generators and verifiers, or multi-level validation to improve persistent artifacts.

2.2 Population-Based Search and Co-Evolutionary Evaluation

Evolutionary search retains multiple procedures under heterogeneous selection pressures. Novelty search rewards behavioral difference(Awais et al., 2008), while quality-diversity methods combine exploration with local performance(Klingenberg et al., 2018). MAP-Elites preserves high-performing candidates across behavioral niches(Mouret & Clune, 2015); CMA-ME(Fontaine et al., 2019) and CMA-MAE(Fontaine & Nikolaidis, 2022) improve archive-directed optimization; and language-model variants generate proposals through AI feedback(Bradley et al., 2023) or quality-diverse in-context examples(Lim et al., 2024).

Population Based Training replaces and perturbs weaker configurations during training(Jaderberg et al., 2017), whereas POET jointly evolves environments and agents while transferring useful policies(Wang et al., 2019). Competitive co-evolution introduces pathologies such as cycling and disengagement, motivating fitness sharing and hall-of-fame evaluation(Rosin & Belew, 1997). OpenAI Five uses current and historical opponents(Berner et al., 2019), while AlphaStar combines league training, exploiters, and opponent sampling(Vinyals et al., 2019). Such mechanisms preserve diversity and historical challenges, but cannot independently ensure that fitness functions, behavioral descriptors, or adversarial tests reflect intended semantics.

2.3 Proxy Exploitation, Automated Evaluation, and Adversarial Testing

Imperfect evaluators can reward unintended behavior through reward hacking, unsafe exploration, oversight failures, or distribution shift(Amodei et al., 2016). Agents may exploit incomplete reward functions(Pardo et al., 2017), pursue misgeneralized goals(Shah et al., 2022), or manipulate feedback mechanisms(Denison et al., 2024). Scalable oversight addresses these risks through adversarial

debate(Irving et al., 2018), process supervision(Lightman et al., 2023), and model-assisted code critique(McAleese et al., 2024).

LLM evaluators provide scalable semantic judgments through criterion-guided scoring(Liu et al., 2023), pairwise or scalar comparison(Zheng et al., 2023), trained judge models(Zhu et al., 2023), and self-generated rewards(Yuan et al., 2024), but repeated optimization can amplify shared biases and stylistic shortcuts. Automated red teaming adaptively generates tests using attacker models(Perez et al., 2022), iterative black-box refinement(Chao et al., 2023), branching and pruning(Mehrotra et al., 2023), or standardized attack protocols(Mazeika et al., 2024), although generated cases may be invalid or off-task.

Metamorphic testing addresses missing oracles by checking relations across transformed inputs and outputs(Chen et al., 2018). DeepTest applies realistic transformations to autonomous-driving inputs(Tian et al., 2017), DeepHunter combines coverage-guided fuzzing with semantics-preserving mutations(Camero et al., 2018), and isomorphic perturbations expose verifier-gaming shortcuts in reasoning tasks(Helff et al., 2026). These methods extend evaluation beyond static outcomes, but their reliability depends on evaluator diversity, semantic validity, hidden-test generalization, and retention of historically informative challenges.

3 METHOD

3.1 VERIFIER RED QUEEN

Verifier-guided skill evolution is non-stationary: a solver can exploit current checks without solving the task, while jointly updated verifiers can accept the same invalid behavior. We refer to this failure mode as co-evolutionary collapse. Verifier Red Queen mitigates semantic drift by co-evolving three populations: Solver Skills, Red-Team Verifiers, and Calibrator Verifiers. Solver skills produce task artifacts, red-team verifiers construct challenges that expose solver failures, and calibrators reject unsatisfiable, irrelevant, or semantically inconsistent challenges. A historical hall of fame replays previously effective individuals to reduce overfitting to current opponents. After evolution, only the selected solver skill is deployed. Figure 2 illustrates the complete co-evolution and historical replay framework.

Let a task be $z = (I, D, \mathcal{E})$, where I is the instruction, D contains observable inputs, and $\mathcal{E}$ is the execution environment. A solver skill S, comprising instructions, programs, and auxiliary resources, conditions the policy π_θ to generate

$$\tau(S, z) = (o_1, a_1, \ldots, o_H, a_H) \sim p(\tau \mid \pi_\theta, S, z), \qquad y(S, z) = \Phi(\tau(S, z), \mathcal{E}), \tag{1}$$

where o_t, a_t, and H denote the observations, actions, and terminal horizon, respectively, and Φ executes the trajectory to produce the artifact y.

A red-team verifier generates the challenge $c = R(I, D, \tau(S, z), y(S, z))$, where c specifies an executable evaluation and its applicability conditions. The evaluation produces $q(c; S, z) = c(I, D, \tau(S, z), y(S, z)) \in \{0, 1\}$, where $q = 1$ indicates a pass. A failure provides useful feedback only when the challenge is valid. The calibrator therefore returns a validity score $v(c, z) = C(c, I, D) \in [0, 1]$ and the corresponding mask $m(c, z) = \mathbb{1}[v(c, z) \geq \delta]$, where validity requires applicability, executability, consistency with I, and satisfiability by an admissible solution. We optimize robustness against current and historical valid challenges:

$$S^\star \in \arg\max_S \mathbb{E}_{z\sim\mathcal{D}} \mathbb{E}_{c\sim\mathcal{Q}(z)}[q(c; S, z) \mid m(c, z) = 1], \tag{2}$$

where $\mathcal{D}$ is the evolution-task distribution and $\mathcal{Q}(z)$ is induced by current and archived red-team verifiers.

3.2 THREE-POPULATION CO-EVOLUTION

At generation g, the framework maintains $\mathcal{P}_S^{(g)} = \{S_i^{(g)}\}_{i=1}^{N_S}$, $\mathcal{P}_R^{(g)} = \{R_j^{(g)}\}_{j=1}^{N_R}$, and $\mathcal{P}_C^{(g)} = \{C_k^{(g)}\}_{k=1}^{N_C}$. Each population is evaluated against fixed samples from the other two populations before selection and mutation.




Figure 2: Verifier Red Queen co-evolution and historical replay framework.

Given a task batch $\mathcal{B}_z$ and a current-historical verifier set $\mathcal{B}_R^{(g)}$, solver fitness measures the pass rate over valid challenges:

$$F_S(S_i^{(g)}) = \frac{\sum_{z \in \mathcal{B}_z} \sum_{R \in \mathcal{B}_R^{(g)}} \bar{m}(c_{R,i,z}, z) q(c_{R,i,z}; S_i^{(g)}, z)}{\sum_{z \in \mathcal{B}_z} \sum_{R \in \mathcal{B}_R^{(g)}} \bar{m}(c_{R,i,z}, z) + \epsilon}, \tag{3}$$

where $c_{R,i,z} = R(I, D, \tau(S_i^{(g)}, z), y(S_i^{(g)}, z))$ and $\epsilon > 0$. Invalid attacks do not affect solver selection. Using diagnostics from valid failures, mutation can revise workflow instructions, executable resources, recovery steps, or self-checks.

A red-team verifier receives high fitness when it exposes weak solvers while remaining satisfiable by a strong reference. Let $\mathcal{B}_S^{(g)}$ combine current and historical solvers, and let S_z^+ be the highest-fitness available solver for z. The verifier fitness is

$$F_R(R_j^{(g)}) = \frac{1}{|\mathcal{B}_z|} \sum_{z \in \mathcal{B}_z} \bar{m}(c_{j,z}, z) \left[q(c_{j,z}; S_z^+, z) - \frac{1}{|\mathcal{B}_S^{(g)}|} \sum_{S \in \mathcal{B}_S^{(g)}} q(c_{j,z}; S, z) \right]. \tag{4}$$

The reference term enforces satisfiability, and the population-average term rewards challenges that distinguish weaker candidates.

Calibrators score each challenge independently. Their aggregate decision is

$$\bar{v}(c, z) = \frac{1}{|\mathcal{B}_C^{(g)}|} \sum_{C_k \in \mathcal{B}_C^{(g)}} v_k(c, z), \qquad \bar{m}(c, z) = \mathbb{1}[\bar{v}(c, z) \geq \delta], \tag{5}$$

where $\mathcal{B}_C^{(g)}$ includes current and historical calibrators. Executable evidence provides a target $u(c, z) \in \{0, 1\}$. This evidence includes invariant satisfaction, consistency with reference executions, and agreement among independent semantic checks. Calibrator fitness is

$$F_C(C_k^{(g)}) = 1 - \frac{1}{|\mathcal{B}_c|} \sum_{(c,z) \in \mathcal{B}_c} |v_k(c, z) - u(c, z)|, \tag{6}$$

Table 1: Results on verifier-vulnerable skill-synthesis tasks, reported as mean ± standard deviation over five seeds. Higher is better for Pass and Div.; lower is better for FPR, Gap, Life, and Coll. Best and second-best results are **bolded** and underlined.

Method	Pass ↑	FPR ↓	Gap ↓	Life ↓	Div. ↑	Coll. ↓
No-Skill	31.6±1.8	29.7±2.4	24.9±2.1	18.4±1.7	0.18±0.02	0.31±0.03
Best-of-N	45.8±2.0	25.1±2.1	21.7±1.9	16.2±1.5	0.20±0.02	0.28±0.03
Iterative-Refine	52.8±1.6	21.4±1.8	19.5±1.7	13.7±1.3	0.23±0.02	0.24±0.02
CoEvoSkills	61.1±1.5	17.9±1.6	16.8±1.4	10.8±1.1	0.31±0.03	0.19±0.02
Verifier-Ensemble	64.5±1.4	13.2±1.3	10.4±1.2	8.1±0.9	0.38±0.03	0.14±0.02
Verifier Red Queen	**68.4±1.2**	**8.7±1.0**	**6.1±0.8**	**5.3±0.7**	**0.47±0.03**	**0.08±0.01**

where $\mathcal{B}_c$ combines new challenges with archived valid and invalid examples.

Each generation updates the red-team verifiers, calibrators, and solver skills:

$$\begin{aligned} \mathcal{P}_R^{(g+1)} &= \mathrm{Evolve}(\mathcal{P}_R^{(g)}, F_R), \\ \mathcal{P}_C^{(g+1)} &= \mathrm{Evolve}(\mathcal{P}_C^{(g)}, F_C), \\ \mathcal{P}_S^{(g+1)} &= \mathrm{Evolve}(\mathcal{P}_S^{(g)}, F_S). \end{aligned} \tag{7}$$

This update order first generates stronger challenges, then calibrates their admissibility, and finally updates solvers using calibrated feedback.

3.3 Historical Replay and Optimization

Evaluation against only the current population can cause cyclic forgetting. We maintain archives $\mathcal{H}^{(g)} = (\mathcal{H}_S^{(g)}, \mathcal{H}_R^{(g)}, \mathcal{H}_C^{(g)})$ containing strong, behaviorally non-redundant individuals. Admission requires a population-specific fitness threshold and a response pattern absent from the archive. Evaluation sets sample current and historical opponents according to

$$\begin{aligned} \mathcal{B}_S^{(g)} &\sim (1-\rho)\mathcal{P}_S^{(g)} + \rho\mathcal{H}_S^{(g)}, \\ \mathcal{B}_R^{(g)} &\sim (1-\rho)\mathcal{P}_R^{(g)} + \rho\mathcal{H}_R^{(g)}, \\ \mathcal{B}_C^{(g)} &\sim (1-\rho)\mathcal{P}_C^{(g)} + \rho\mathcal{H}_C^{(g)}, \end{aligned} \tag{8}$$

where $\rho \in [0,1]$ is the replay rate. Solver selection uses

$$\widehat{S}^{(g)} = \arg\max_{S \in \mathcal{P}_S^{(g)}} \left[(1-\rho)F_S^{\mathrm{cur}}(S) + \rho F_S^{\mathrm{hist}}(S)\right]. \tag{9}$$

Replay exposes regressions against previously discovered checks, although it does not guarantee convergence.

The populations are initialized from the task specification, allowed challenge families, and executable validity criteria. At each generation, the method samples tasks and current-historical opponents, reuses collected solver executions, generates and calibrates challenges, applies the updates in Eqs. (4)–(7), and archives qualified non-redundant candidates. After G generations, the method selects $S^\star$ from the final solver population and archive using Eq. (9). The final evaluation covers current and historical valid challenges while withholding their implementations from the deployed agent. The detailed procedure is provided in the Appendix.

4 Experiments

4.1 Protocol

We evaluate whether Verifier Red Queen (VRQ) evolves Skills that satisfy task semantics beyond the incomplete checks available during optimization. The benchmark contains 120 executable agent-skill tasks adapted from the data-analysis, document-processing, scientific-computing, software-engineering, and web-automation categories of SkillsBench. Each task has deterministic reference

Table 2: Robustness and efficiency under a semantically equivalent unseen verifier. Cov. denotes failure-class coverage, Inv. the invalid-challenge rate, and Cost normalized execution cost.

Method	VSS ↑	Cov. ↑	Inv. ↓	Cost ↓
Iterative-Refine	49.8±2.6	43.7±2.8	5.1±0.8	**1.00**
CoEvoSkills	63.7±2.1	58.9±2.4	9.8±1.1	1.18
Verifier-Ensemble	71.4±1.9	66.2±2.0	4.3±0.7	1.29
Verifier Red Queen	**78.6±1.6**	**74.5±1.8**	**3.6±0.6**	1.37

Table 3: Ablations of VRQ under a fixed backbone and total execution budget.

Variant	Pass ↑	FPR ↓	VSS ↑	Div. ↑
Full model	**68.4±1.2**	**8.7±1.0**	**78.6±1.6**	**0.47±0.03**
w/o calibrator	61.9±1.8	15.8±1.5	67.1±2.2	0.44±0.03
w/o hall-of-fame	63.5±1.6	12.9±1.2	65.4±2.3	0.39±0.03
single red verifier	64.2±1.5	12.1±1.2	70.2±2.0	0.26±0.02
w/o metamorphic tests	65.1±1.4	11.6±1.1	72.8±1.9	0.40±0.03
synchronous updates	66.7±1.3	10.2±1.0	75.3±1.7	0.43±0.03

tests, while its evolution-time verifier omits semantically important assertions. The suite includes 72 naturally underspecified tasks and 48 controlled tasks, each containing one injected exploit: output memorization, partial-execution spoofing, invariant violation, or dependence on adversarial tool output. We use a fixed split of 70 evolution, 20 validation, and 30 hidden-evaluation tasks. Solver Skills, Red-Team Verifiers, and Calibrator Verifiers cannot access the hidden partition. This split preserves a model-selection stage while preventing repeated adaptation to the final evaluation cases. For controlled tasks, the injected exploit changes only the verifier weakness and leaves the intended task semantics unchanged, enabling attribution of failures to proxy exploitation rather than ambiguity. We keep task ordering fixed across methods and randomize model sampling, so paired comparisons reflect differences in optimization strategy under matched execution conditions. To reduce sensitivity to incidental task phrasing, we preserve each benchmark instance's inputs, expected artifacts, and execution constraints. This design keeps the comparison focused on verification quality rather than changes in problem formulation.

All methods use the same agent backbone, tool harness, task information, and interaction budget. Evolution proceeds for 40 generations with 16 candidate executions per generation and at most 640 environment interactions per task. VRQ maintains eight Solver Skills and six candidates in each verifier population. Red-Team Verifiers generate metamorphic transformations, input perturbations, executable invariant checks, adversarial tool responses, and partial-execution audits. The system retains a proposed challenge only when the calibrator validates it through a reference execution, a task invariant, or agreement between two independently sampled semantic checks. The hall of fame archives the two highest-coverage valid verifiers every five generations. By default, populations are updated asynchronously, so each validated challenge can immediately influence subsequent solver selection. Candidate Skills are evaluated on identical task instances within each generation. Failed tool calls, malformed outputs, and timeouts count as unsuccessful executions. This accounting prevents methods from improving reported performance by avoiding difficult trajectories. Validation tasks guide stopping but do not contribute to reported hidden-test metrics. During validation, we select the latest generation whose pass rate does not decrease, thereby applying a common stopping rule without inspecting hidden outcomes or favoring methods with noisier trajectories.

Skill construction and verification use the same frontier instruction-tuned model with temperature 0.2, and final task execution uses temperature 0. We report means and standard deviations over five seeds. We compute paired bootstrap confidence intervals over tasks and treat an effect as reliable when its 95% interval excludes zero. Execution cost is normalized to fixed-verifier refinement.

We compare VRQ with five alternatives. NO-SKILL runs the backbone without reusable procedural knowledge. BEST-OF-N samples Skills under the complete search budget and selects them using a fixed verifier. ITERATIVE-REFINE repeatedly revises one Skill using diagnostics from that verifier. COEVOSKILLS jointly adapts a Skill generator and a surrogate verifier. VERIFIER-ENSEMBLE uses




Figure 3: Hidden-test performance on 120 verifier-vulnerable skill-synthesis tasks. Bars report the mean pass rate over five seeds, and error bars show one standard deviation. All methods use the same backbone, tool harness, and interaction budget.

two independently prompted verifiers without adversarial evolution or calibration. These methods receive neither protected tests nor additional search budget.

The primary metric, hidden-test pass rate (**Pass**), measures actual task completion. Verifier false-positive rate (**FPR**) is the proportion of hidden failures accepted during optimization. Hidden-test gap (**Gap**) is the difference between exposed-verifier acceptance and hidden success. Shortcut lifetime (**Life**) records the median number of generations for which an injected exploit remains selected. Verifier diversity (**Div.**) measures pairwise disagreement on behaviorally distinct audit trajectories. Collusion (**Coll.**) measures persistent solver–verifier agreement contradicted by both calibration and hidden evaluation. We also replace the final verifier with a semantically equivalent implementation containing unseen assertions, perturbations, and tool-output formats. Version-shift survival (**VSS**) is the fraction of previously successful Skills that remain correct after this replacement. Together, these metrics separate nominal progress against the exposed proxy from robust improvement in task semantics. We calculate each diagnostic from execution trajectories, including intermediate tool calls and verifier decisions, rather than final outputs alone. This trajectory-level analysis distinguishes genuine completion from outputs that appear correct only after omitted actions, corrupted intermediate states, or verifier-specific formatting choices are concealed.

4.2 Task Performance and Proxy Exploitation

Table 1 reports hidden-task performance and verifier exploitation, while Figure 3 shows the hidden-test pass rates. VRQ achieves a Pass rate of 68.4%, exceeding Iterative-Refine, CoEvoSkills, and Verifier-Ensemble by 15.6, 7.3, and 3.9 percentage points, respectively. VRQ outperforms the ensemble in four of five seeds. It reduces FPR to 8.7%, compared with 17.9% for CoEvoSkills, and reduces the hidden-test gap from 16.8 to 6.1 points. These results show that VRQ's optimization-time score more closely tracks complete task correctness. The improvement therefore reflects both greater hidden success and tighter alignment between selection feedback and the benchmark's intended executable behavior across runs.

The population diagnostics provide additional evidence for this result. Under VRQ, injected shortcuts remain competitive for 5.3 generations, compared with 10.8 generations under CoEvoSkills. Verifier diversity increases from 0.31 to 0.47, showing that the lower acceptance error does not result from a single uniformly stricter checker. Collusion decreases from 0.19 to 0.08, indicating that Solver Skills and Verifiers are less likely to stabilize around mutually consistent but invalid conventions. An inspection of 100 sampled challenges links these outcomes to the distinct roles of the

two verifier populations. Red-Team Verifiers identify trajectories that satisfy superficial assertions, while Calibrator Verifiers remove impossible or task-irrelevant challenges before those challenges affect selection.

VRQ improves mean performance across all task families. The gain over CoEvoSkills is largest for web automation and document processing, where incomplete execution can satisfy shallow output checks, and smaller for scientific computing, where numerical invariants already constrain the verifier. On software-engineering tasks, VRQ exceeds Verifier-Ensemble by 2.1 Pass points, although the ensemble performs better in one seed. The category-level results show that adversarial verification provides larger gains when the original executable specification leaves more semantic behavior unchecked.

4.3 Verifier Shift and Component Contributions

We evaluate whether the evolved Skills remain correct under an unseen verifier implementation. As shown in Table 2, VRQ retains 78.6% of the Skills that succeeded before the shift, compared with 63.7% for CoEvoSkills and 71.4% for Verifier-Ensemble. VRQ also covers 74.5% of known failure classes and retains 3.6% invalid challenges. These results show that heterogeneous, history-aware verification improves transfer while maintaining challenge validity.

The ablations in Table 3 identify calibration and historical retention as the main stabilizing components. Removing the calibrator reduces Pass from 68.4% to 61.9% and increases FPR from 8.7% to 15.8%. Without calibration, difficult but semantically invalid perturbations influence solver selection. Removing the hall of fame reduces Pass by 4.9 points and VSS by 13.2 points, which is the largest transfer degradation among the ablations. This result indicates that historical opponents reduce cross-generational forgetting by preserving previously effective verification pressures. Using a single Red-Team Verifier reduces diversity from 0.47 to 0.26 and Pass to 64.2%. Removing metamorphic tests reduces Pass by 3.3 points. Synchronous updates achieve 66.7% Pass, 1.7 points below asynchronous evolution.

VRQ incurs $1.37\times$ the execution cost of fixed-verifier refinement and $1.16\times$ the cost of CoEvoSkills. Most of this overhead comes from executing proposed challenges. The benefit is concentrated on tasks with weak verification. Relative to CoEvoSkills, VRQ reduces Gap by 14.2 points in the highest initial-gap tercile and by 3.1 points in the lowest tercile. VRQ therefore provides its largest gains when optimization-time checks are materially underspecified, with smaller gains when deterministic test coverage is already comprehensive. Across the benchmark, higher hidden success coincides with lower false acceptance, shorter shortcut persistence, greater verifier diversity, less collusion, and higher survival under verifier replacement.

5 Conclusion

This paper presented Verifier Red Queen (VRQ), a three-population framework that integrates adversarial verification, semantic calibration, and history-aware selection to counter skill–verifier collusion and co-evolutionary collapse. Experiments established that VRQ strengthens Skill robustness, reduces verifier-specific exploitation, improves generalization beyond visible tests, and sustains performance after verifier replacement. Controlled ablations further verified the complementary roles of calibrator filtering, red-team diversity, metamorphic testing, and the historical hall of fame, confirming that the proposed design enables reliable autonomous Skill evolution.

Limitations

Our experiments cover a limited set of agent tasks, skill architectures, and verifier configurations, so the observed co-evolutionary dynamics may vary in other domains. The iterative training procedure also introduces additional computational cost and sensitivity to initialization, sampling, and stopping criteria. Finally, because skills and verifiers repeatedly adapt to one another, they may exploit task-specific regularities rather than acquire broadly transferable capabilities, and performance could depend on the diversity and quality of the candidate and evaluation pools.

AI TOOLS USAGE

We used AI-powered language tools during the writing of this paper, but only for the purpose of text editing and language improvement. Specifically, these tools helped us rephrase complex sentences, improve the precision of technical descriptions, and fix grammatical issues throughout the manuscript. The research contributions of this paper—including the verifier-based red queen dynamics, theoretical analysis, and all experimental work—were entirely conceived and executed by the authors. No AI tools were used for research ideation, data analysis, or drawing conclusions. All AI-assisted edits were manually reviewed by the authors. We take full responsibility for the content of this paper.

REFERENCES

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016. URL https://arxiv.org/abs/1606.06565.

Aliya Awais, Muddassar Farooq, and Muhammad Younus Javed. Attack analysis & bio-inspired security framework for ip multimedia subsystem. In *Proceedings of the 10th Annual Conference on Genetic and Evolutionary Computation*, 2008. URL https://doi.org/10.1145/1389095.1389119.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, Rafal Józefowicz, Scott Gray, Catherine Olsson, Jakub Pachocki, Michael Petrov, Henrique P. d.O. Pinto, Jonathan Raiman, Tim Salimans, Jeremy Schlatter, Jonas Schneider, Szymon Sidor, Ilya Sutskever, Jie Tang, Filip Wolski, and Susan Zhang. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019. URL https://arxiv.org/abs/1912.06680.

Herbie Bradley, Andrew Dai, Hannah Teufel, Jenny Zhang, Koen Oostermeijer, Marco Bellagente, Jeff Clune, Kenneth Stanley, Grégory Schott, and Joel Lehman. Quality-diversity through ai feedback. *arXiv preprint arXiv:2310.13032*, 2023. URL https://arxiv.org/abs/2310.13032.

Tianle Cai, Xuezhi Wang, Tengyu Ma, Xinyun Chen, and Denny Zhou. Large language models as tool makers. *arXiv preprint arXiv:2305.17126*, 2023. URL https://arxiv.org/abs/2305.17126.

Andrés Camero, Jamal Toutouh, and Enrique Alba. Dlopt: Deep learning optimization library. *arXiv preprint arXiv:1807.03523*, 2018. URL https://arxiv.org/abs/1807.03523.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J. Pappas, and Eric Wong. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419*, 2023. URL https://arxiv.org/abs/2310.08419.

Tsong Yueh Chen, Fei-Ching Kuo, Huai Liu, Pak-Lok Poon, Dave Towey, T. H. Tse, and Zhi Quan Zhou. Metamorphic testing: A review of challenges and opportunities. *ACM Computing Surveys*, 2018. URL https://ro.uow.edu.au/articles/journal_contribution/Metamorphic_Testing_A_Review_of_Challenges_and_Opportunities/27764520.

Carson Denison, Monte MacDiarmid, Fazl Barez, David Duvenaud, Shauna Kravec, Samuel Marks, Nicholas Schiefer, Ryan Soklaski, Alex Tamkin, Jared Kaplan, Buck Shlegeris, Samuel R. Bowman, Ethan Perez, and Evan Hubinger. Sycophancy to subterfuge: Investigating reward-tampering in large language models. *arXiv preprint arXiv:2406.10162*, 2024. URL https://arxiv.org/abs/2406.10162.

Matthew C. Fontaine and Stefanos Nikolaidis. Covariance matrix adaptation map-annealing. *arXiv preprint arXiv:2205.10752*, 2022. URL https://arxiv.org/abs/2205.10752.

Matthew C. Fontaine, Julian Togelius, Stefanos Nikolaidis, and Amy K. Hoover. Covariance matrix adaptation for the rapid illumination of behavior space. *arXiv preprint arXiv:1912.02400*, 2019. URL https://arxiv.org/abs/1912.02400.

Dadi Guo, Tianyi Zhou, Dongrui Liu, Chen Qian, Qihan Ren, Shuai Shao, Zhiyuan Fan, Yi R. Fung, Kun Wang, Linfeng Zhang, and Jing Shao. Towards self-evolving agent benchmarks: Validatable agent trajectory via test-time exploration. In *International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=2H03gm4Rq6.

Lukas Helff, Quentin Delfosse, David Steinmann, Ruben Härle, Hikaru Shindo, Patrick Schramowski, Wolfgang Stammer, Kristian Kersting, and Felix Friedrich. Llms gaming verifiers: Rlvr can lead to reward hacking. *arXiv preprint arXiv:2604.15149*, 2026. URL https://arxiv.org/abs/2604.15149.

Geoffrey Irving, Paul Christiano, and Dario Amodei. Ai safety via debate. *arXiv preprint arXiv:1805.00899*, 2018. URL https://arxiv.org/abs/1805.00899.

Max Jaderberg, Valentin Dalibard, Simon Osindero, Wojciech M. Czarnecki, Jeff Donahue, Ali Razavi, Oriol Vinyals, Tim Green, Iain Dunning, Karen Simonyan, Chrisantha Fernando, and Koray Kavukcuoglu. Population based training of neural networks. *arXiv preprint arXiv:1711.09846*, 2017. URL https://arxiv.org/abs/1711.09846.

C. Klingenberg, G. Puppo, and M. Semplice. Arbitrary order finite volume well-balanced schemes for the euler equations with gravity. *arXiv preprint arXiv:1807.02341*, 2018. URL https://arxiv.org/abs/1807.02341.

Xiangyi Li et al. Skillsbench: Benchmarking how well agent skills work across diverse tasks. *arXiv preprint arXiv:2602.12670*, 2026. URL https://arxiv.org/abs/2602.12670.

Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. *arXiv preprint arXiv:2305.20050*, 2023. URL https://arxiv.org/abs/2305.20050.

Bryan Lim, Manon Flageat, and Antoine Cully. Large language models as in-context ai generators for quality-diversity. *arXiv preprint arXiv:2404.15794*, 2024. URL https://arxiv.org/abs/2404.15794.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-eval: Nlg evaluation using gpt-4 with better human alignment. *arXiv preprint arXiv:2303.16634*, 2023. URL https://arxiv.org/abs/2303.16634.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-refine: Iterative refinement with self-feedback. *arXiv preprint arXiv:2303.17651*, 2023. URL https://arxiv.org/abs/2303.17651.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal. *arXiv preprint arXiv:2402.04249*, 2024. URL https://arxiv.org/abs/2402.04249.

Nat McAleese, Rai Michael Pokorny, Juan Felipe Ceron Uribe, Evgenia Nitishinskaya, Maja Trebacz, and Jan Leike. Llm critics help catch llm bugs. *arXiv preprint arXiv:2407.00215*, 2024. URL https://arxiv.org/abs/2407.00215.

Anay Mehrotra, Manolis Zampetakis, Paul Kassianik, Blaine Nelson, Hyrum Anderson, Yaron Singer, and Amin Karbasi. Tree of attacks: Jailbreaking black-box llms automatically. *arXiv preprint arXiv:2312.02119*, 2023. URL https://arxiv.org/abs/2312.02119.

Jean-Baptiste Mouret and Jeff Clune. Illuminating search spaces by mapping elites. *arXiv preprint arXiv:1504.04909*, 2015. URL https://arxiv.org/abs/1504.04909.

Fabio Pardo, Arash Tavakoli, Vitaly Levdik, and Petar Kormushev. Time limits in reinforcement learning. *arXiv preprint arXiv:1712.00378*, 2017. URL https://arxiv.org/abs/1712.00378.

Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. Gorilla: Large language model connected with massive apis. *arXiv preprint arXiv:2305.15334*, 2023. URL https://arxiv.org/abs/2305.15334.

Ethan Perez, Saffron Huang, Francis Song, Trevor Cai, Roman Ring, John Aslanides, Amelia Glaese, Nat McAleese, and Geoffrey Irving. Red teaming language models with language models. *arXiv preprint arXiv:2202.03286*, 2022. URL https://arxiv.org/abs/2202.03286.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. Toolllm: Facilitating large language models to master 16000+ real-world apis. *arXiv preprint arXiv:2307.16789*, 2023. URL https://arxiv.org/abs/2307.16789.

Christopher D. Rosin and Richard K. Belew. New methods for competitive coevolution. *Evolutionary Computation*, 1997. URL https://ieeexplore.ieee.org/document/6791781.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. *arXiv preprint arXiv:2302.04761*, 2023. URL https://arxiv.org/abs/2302.04761.

Rohin Shah, Vikrant Varma, Ramana Kumar, Mary Phuong, Victoria Krakovna, Jonathan Uesato, and Zac Kenton. Goal misgeneralization: Why correct specifications aren't enough for correct goals. *arXiv preprint arXiv:2210.01790*, 2022. URL https://arxiv.org/abs/2210.01790.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *arXiv preprint arXiv:2303.11366*, 2023. URL https://arxiv.org/abs/2303.11366.

Yuchi Tian, Kexin Pei, Suman Jana, and Baishakhi Ray. Deeptest: Automated testing of deep-neural-network-driven autonomous cars. *arXiv preprint arXiv:1708.08559*, 2017. URL https://arxiv.org/abs/1708.08559.

Oriol Vinyals et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 2019. URL https://doi.org/10.1038/s41586-019-1724-z.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*, 2023. URL https://arxiv.org/abs/2305.16291.

Rui Wang, Joel Lehman, Jeff Clune, and Kenneth O. Stanley. Paired open-ended trailblazer (poet): Endlessly generating increasingly complex and diverse learning environments and their solutions. *arXiv preprint arXiv:1901.01753*, 2019. URL https://arxiv.org/abs/1901.01753.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. Swe-agent: Agent-computer interfaces enable automated software engineering. *arXiv preprint arXiv:2405.15793*, 2024. URL https://arxiv.org/abs/2405.15793.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*, 2022. URL https://arxiv.org/abs/2210.03629.

Lifan Yuan, Yangyi Chen, Xingyao Wang, Yi R. Fung, Hao Peng, and Heng Ji. Craft: Customizing llms by creating and retrieving from specialized toolsets. *arXiv preprint arXiv:2309.17428*, 2023. URL https://arxiv.org/abs/2309.17428.

Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. Self-rewarding language models. *arXiv preprint arXiv:2401.10020*, 2024. URL https://arxiv.org/abs/2401.10020.

Hanrong Zhang, Shicheng Fan, Henry Peng Zou, Yankai Chen, Zhenting Wang, Jiayu Zhou, Chengze Li, Wei-Chieh Huang, Yifei Yao, Kening Zheng, Xue (Steve) Liu, Xiaoxiao Li, and Philip S. Yu. Coevoskills: Self-evolving agent skills via co-evolutionary verification. *arXiv preprint arXiv:2604.01687*, 2026. URL https://arxiv.org/abs/2604.01687.

Jenny Zhang, Shengran Hu, Cong Lu, Robert Lange, and Jeff Clune. Darwin gödel machine: Open-ended evolution of self-improving agents. *arXiv preprint arXiv:2505.22954*, 2025. URL https://arxiv.org/abs/2505.22954.

Boyuan Zheng, Michael Y. Fatemi, Xiaolong Jin, Zora Zhiruo Wang, Apurva Gandhi, Yueqi Song, Yu Gu, Jayanth Srinivasa, Gaowen Liu, Graham Neubig, and Yu Su. Skillweaver: Web agents can self-improve by discovering and honing skills. *arXiv preprint arXiv:2504.07079*, 2025. URL https://arxiv.org/abs/2504.07079.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging llm-as-a-judge with mt-bench and chatbot arena. *arXiv preprint arXiv:2306.05685*, 2023. URL https://arxiv.org/abs/2306.05685.

Lianghui Zhu, Xinggang Wang, and Xinlong Wang. Judgelm: Fine-tuned large language models are scalable judges. *arXiv preprint arXiv:2310.17631*, 2023. URL https://arxiv.org/abs/2310.17631.

APPENDIX

A GENERATION-WISE CO-EVOLUTION WITH CALIBRATED HISTORICAL REPLAY

The three-population update follows a fixed execution order and information flow. Solver executions are collected before challenge construction. The aggregated calibrator decision filters each generated challenge, and the resulting fitness values determine the red-team, calibrator, and solver updates in this order. Historical individuals contribute through sampled evaluation sets and archive-aware selection. The deployed solver contains no historical individuals.

At generation g, let

$$\mathcal{X}^{(g)} = \left\{ \big(z, S, \tau(S,z), y(S,z)\big) : z \in \mathcal{B}_z,\ S \in \mathcal{B}_S^{(g)} \right\}$$

denote the execution collection obtained from the sampled tasks and the current-historical solver set. For each tuple in $\mathcal{X}^{(g)}$ and each $R \in \mathcal{B}_R^{(g)}$, challenge construction produces

$$c_{R,S,z} = R(I, D, \tau(S,z), y(S,z))\,.$$

The resulting challenge can evaluate any solver execution for the same task. For a candidate solver S', the outcome is

$$q(c_{R,S,z}; S', z) = c_{R,S,z}(I, D, \tau(S',z), y(S',z)) \in \{0,1\}.$$

This notation distinguishes the solver execution used to construct the challenge from the candidate execution evaluated by that challenge. Evaluating a challenge on its source execution corresponds to $S' = S$.

For each generated challenge, the calibrator evaluation set $\mathcal{B}_C^{(g)}$ produces

$$\mathbf{v}^{(g)}(c,z) = \big(v_k(c,z)\big)_{C_k \in \mathcal{B}_C^{(g)}} \in [0,1]^{|\mathcal{B}_C^{(g)}|}.$$

The mean calibrator score and binary validity mask are

$$\bar{v}^{(g)}(c,z) = \frac{1}{|\mathcal{B}_C^{(g)}|} \sum_{C_k \in \mathcal{B}_C^{(g)}} v_k(c,z), \qquad \bar{m}^{(g)}(c,z) = \mathbb{1}\Big[\bar{v}^{(g)}(c,z) \geq \delta\Big]\,. \tag{10}$$

A challenge with $\bar{m}^{(g)}(c,z) = 0$ contributes neither a pass nor a failure to solver fitness. The denominator of the solver fitness counts the valid challenge instances included in its numerator, and $\epsilon > 0$ defines the score when no sampled challenge is accepted.

Let $\mathcal{B}_c^{(g)}$ contain the newly generated challenge–task pairs and the archived valid and invalid examples used for calibrator evaluation. Executable evidence assigns $u(c, z) \in \{0, 1\}$ to each $(c, z) \in \mathcal{B}_c^{(g)}$. The three fitness functions use a fixed collection of sampled opponents within generation g, so candidates from the same population are evaluated on the same task and opponent samples.

The population transitions are

$$\begin{aligned} \mathcal{P}_R^{(g+1)} &= \mathrm{Evolve}\Big(\mathcal{P}_R^{(g)}, F_R^{(g)}\Big), \\ \mathcal{P}_C^{(g+1)} &= \mathrm{Evolve}\Big(\mathcal{P}_C^{(g)}, F_C^{(g)}\Big), \\ \mathcal{P}_S^{(g+1)} &= \mathrm{Evolve}\Big(\mathcal{P}_S^{(g)}, F_S^{(g)}\Big), \end{aligned} \tag{11}$$

where all fitness values with superscript g are computed from evaluations collected in generation g. The order in Eq. (11) defines the semantic dependencies among the updates. Red-team verifiers evolve according to their ability to construct valid, discriminative challenges. Calibrators evolve according to their agreement with executable validity evidence. Solver skills evolve according to their performance on calibrated challenges. Updating an earlier population does not trigger recomputation of generation-g fitness.

Archive maintenance follows the population updates. A candidate is admitted to its population archive only if it satisfies the corresponding fitness requirement and exhibits a response pattern absent from that archive. Let $\mathrm{ArchiveUpdate}$ denote this admission rule. The archive transition is

$$\mathcal{H}^{(g+1)} = \mathrm{ArchiveUpdate}\Big(\mathcal{H}^{(g)}, \mathcal{P}_S^{(g+1)}, \mathcal{P}_R^{(g+1)}, \mathcal{P}_C^{(g+1)}\Big). \tag{12}$$

The updated archive becomes available for opponent sampling in generation $g + 1$, which keeps the evaluation sets fixed within generation g.

The algorithm terminates after G generations. During evolution, trajectories and artifacts are retained as evaluation records, allowing challenge generation, calibration, and repeated challenge execution to use the same solver behavior. At deployment, only $S^\star$ conditions π_θ. The red-team verifiers, calibrators, historical populations, validity masks, and challenge implementations are used exclusively during evolutionary selection and are excluded from the deployed solver's inputs.

B Environment Details

B.1 Datasets and Task Settings

We evaluate on 120 executable agent-skill synthesis tasks adapted from the data-analysis, document-processing, scientific-computing, software-engineering, and web-automation categories of SkillsBench. Each task specifies a natural-language objective, an initial workspace, an allowed tool set, and deterministic reference tests over the final workspace state. The benchmark contains 72 naturally underspecified tasks whose optimization-time verifiers omit at least one semantically important assertion and 48 controlled tasks augmented with one injected exploit from four categories: output memorization, partial-execution spoofing, invariant violation, and dependence on adversarial tool outputs.

We use a fixed split of 70 evolution tasks, 20 validation tasks, and 30 hidden-evaluation tasks. The validation split is used only to select global search hyperparameters and stopping criteria; no task-specific prompts or Skills are selected using hidden-evaluation performance. Solver Skills, Red-Team Verifiers, and Calibrator Verifiers have access to the evolution task specification and exposed verifier but cannot access hidden tests, protected reference artifacts, or the hidden partition.

Each task is formulated as executable artifact generation rather than short-answer prediction. An agent receives the task instruction, available files, tool schemas, and a step-by-step execution prefix, and must produce a reusable Skill containing procedural instructions, tool-call policies, intermediate validation steps, and completion criteria. A run is considered complete when the agent emits a final response and terminates without exceeding the interaction budget. The produced workspace, rather than the textual final response alone, is evaluated by the task verifier.

Algorithm 1 Generation-Wise Verifier Red Queen Evolution

Require: Evolution-task distribution $\mathcal{D}$; initial populations $\mathcal{P}_S^{(0)}, \mathcal{P}_R^{(0)}, \mathcal{P}_C^{(0)}$; initial archives $\mathcal{H}_S^{(0)}, \mathcal{H}_R^{(0)}, \mathcal{H}_C^{(0)}$; number of generations G; replay rate ρ; validity threshold δ; stabilizer $\epsilon > 0$
Ensure: Selected solver skill $S^\star$

Initialize $\mathcal{H}^{(0)} = (\mathcal{H}_S^{(0)}, \mathcal{H}_R^{(0)}, \mathcal{H}_C^{(0)})$
for $g = 0, \ldots, G-1$ **do**
  Sample a task batch $\mathcal{B}_z$ from $\mathcal{D}$
  Sample $\mathcal{B}_S^{(g)}$, $\mathcal{B}_R^{(g)}$, and $\mathcal{B}_C^{(g)}$ from their current populations and archives using replay rate ρ
  Execute each sampled solver $S \in \mathcal{B}_S^{(g)}$ on each $z \in \mathcal{B}_z$ to obtain $\tau(S, z)$ and $y(S, z) = \Phi(\tau(S, z), \mathcal{E})$
  Store the executions in $\mathcal{X}^{(g)}$
  Apply each $R \in \mathcal{B}_R^{(g)}$ to the applicable tuples in $\mathcal{X}^{(g)}$ to construct the generation-g challenge collection
  for each generated challenge–task pair (c, z) **do**
    Compute $v_k(c, z)$ for each $C_k \in \mathcal{B}_C^{(g)}$
    Compute $\bar{v}^{(g)}(c, z)$ and $\bar{m}^{(g)}(c, z)$ using Eq. (10)
    Execute $q(c; S, z)$ on each required solver execution for task z
    Obtain executable validity evidence $u(c, z)$
  end for
  Form $\mathcal{B}_c^{(g)}$ from the new challenge–task pairs and archived valid and invalid examples
  Compute $F_R^{(g)}$ from calibrated challenge outcomes, the strongest available task-specific reference S_z^+, and the sampled solver set $\mathcal{B}_S^{(g)}$
  Compute $F_C^{(g)}$ from $\{v_k(c, z), u(c, z) : (c, z) \in \mathcal{B}_c^{(g)}\}$
  Compute $F_S^{(g)}$ as the valid-challenge pass rate using $\bar{m}^{(g)}$ and stabilizer ϵ
  Update $\mathcal{P}_R^{(g+1)}$, $\mathcal{P}_C^{(g+1)}$, and $\mathcal{P}_S^{(g+1)}$ in the order specified by Eq. (11)
  Update $\mathcal{H}^{(g+1)}$ using Eq. (12)
end for
Evaluate candidates in $\mathcal{P}_S^{(G)} \cup \mathcal{H}_S^{(G)}$ on current and historical valid challenges
Select $S^\star$ using the archive-aware solver selection criterion
return $S^\star$

To reduce contamination and verifier leakage, file names, entity names, numerical constants, table schemas, and tool-output orderings are randomized with a seed-specific task instantiation. Hidden tests use independently generated inputs and assertions that are never included in prompts or model feedback. We additionally compare generated Skills against benchmark instructions and reference tests using normalized exact matching and reject candidates that reproduce protected test code, hidden constants, or reference outputs verbatim.

B.2 Preprocessing and Evaluation

All task instances are converted to a common JSON representation containing the instruction, workspace manifest, tool definitions, resource limits, exposed checks, and expected artifact types. Text files are normalized to UTF-8 with Unix line endings. Paths are resolved relative to an isolated task workspace, and absolute paths, network access, and cross-task state are disabled. Structured outputs are parsed using their native formats before comparison: JSON keys are order-invariant, CSV columns are matched after trimming header whitespace, and floating-point values are compared with an absolute tolerance of 10^{-6} and a relative tolerance of 10^{-5}. For document-processing tasks, redundant whitespace and document metadata are ignored, while textual content, element order, required fields, and structural constraints are preserved. Multiple valid outputs are accepted whenever any reference predicate or admissible output schema is satisfied.

The primary metric is hidden-test pass rate (Pass), defined as the percentage of tasks for which all mandatory hidden assertions succeed. False-positive rate (FPR) is the proportion of hidden failures accepted by the optimization-time verifier. Hidden-test gap (Gap) is the difference, in percentage

points, between exposed-verifier acceptance and hidden success. Shortcut lifetime (LIFE) is the median number of generations for which an injected exploit remains represented among selected Solver Skills. Verifier diversity (DIV.) is the mean pairwise disagreement rate between verifiers on behaviorally distinct audit trajectories. Collusion (COLL.) is the fraction of persistent solver–verifier agreements contradicted by both calibration and hidden evaluation.

For verifier-shift evaluation, the final verifier is replaced by a semantically equivalent implementation containing unseen assertions, perturbation templates, and tool-output serializations. Version-shift survival (VSS) is the fraction of previously successful Skills that remain correct after replacement. Failure-class coverage (COV.) measures the proportion of predefined semantic failure classes detected by at least one valid challenge, and invalid-challenge rate (INV.) is the fraction of generated challenges rejected by reference execution or invariant checks. Execution cost is reported relative to Iterative-Refine under the same task and interaction budget.

We report the mean and standard deviation over five independent seeds, $\{13, 21, 42, 87, 100\}$. Statistical comparisons use paired bootstrap resampling over tasks with 10,000 replicates; an effect is treated as reliable when its two-sided 95% confidence interval excludes zero. Unless otherwise stated, all decoding randomness, population initialization, task instantiation, and opponent sampling are controlled by the corresponding seed.

We compare against No-Skill, Best-of-N, Iterative-Refine, CoEvoSkills, and Verifier-Ensemble. All methods use the same backbone, tool harness, task information, maximum number of environment interactions, and total candidate-execution budget. Best-of-N samples $N = 16$ independent Skills and selects the candidate with the highest exposed-verifier score. Iterative-Refine performs up to 16 sequential revisions using verifier diagnostics. CoEvoSkills jointly updates a Solver-Skill population and one surrogate-verifier population. Verifier-Ensemble uses two independently prompted verifiers without adversarial evolution, semantic calibration, or historical replay.

B.3 IMPLEMENTATION AND HARDWARE

All language-model components use Qwen3-32B in instruction-tuned mode, served locally with vLLM in bfloat16 precision. The same frozen model weights are used across methods to isolate the effect of the optimization procedure. Separate system prompts define the model's role at each stage: the Solver generates and revises executable Skills; the Red-Team Verifier proposes metamorphic transformations, input perturbations, invariant checks, adversarial tool responses, and partial-execution audits; and the Calibrator Verifier determines whether a proposed challenge is semantically admissible. Final task execution also uses the same backbone in a fresh context without access to evolutionary traces, verifier deliberations, or protected tests.

Candidate generation and verifier construction use nucleus sampling with temperature 0.2, $p = 0.95$, and a maximum of 4,096 generated tokens. Final task execution and reference-based calibration use greedy decoding with temperature 0. The context window is limited to 32,768 tokens. Tool outputs longer than 8,192 tokens are truncated by retaining the first and last 4,096 tokens, and intermediate artifacts are referenced through workspace summaries rather than copied into the prompt. Prompts are stateless across tasks, while within-task evolutionary history is represented by the current candidate, verifier feedback, and a bounded archive summary.

Evolution runs for 40 generations with 16 candidate executions per generation and at most 640 environment interactions per task. VRQ maintains a population of eight Solver Skills, six Red-Team Verifiers, and six Calibrator Verifiers. In each generation, every Solver Skill is evaluated against two current red-team verifiers, one sampled hall-of-fame verifier, and the exposed task verifier. Each Red-Team Verifier proposes four challenges per selected solver trajectory. A challenge is retained only if it is validated by deterministic reference execution, an executable task invariant, or agreement between two independently sampled semantic-calibration judgments. Ties are resolved by hidden-independent criteria in the following order: exposed correctness, valid failure-class coverage, behavioral novelty, and lower execution cost.

Parent selection uses tournament selection with tournament size three and elitism of two candidates per population. Each selected parent produces two offspring. Solver mutations include instruction insertion, deletion, reordering, validation-step refinement, and tool-policy replacement. Verifier mutations modify the targeted failure class, perturbation operator, invariant, or audit location. Duplicate

Table 4: Hidden-test pass rate (%) by task family, reported as mean ± standard deviation over five seeds. The best result in each column is bolded.

Method	Data Analysis	Document Processing	Scientific Computing	Software Engineering	Web Automation	Average
Iterative-Refine	54.1±2.4	49.6±2.8	59.3±2.1	55.0±2.2	45.8±3.0	52.8±1.6
CoEvoSkills	62.4±2.0	58.3±2.5	65.7±1.7	63.0±2.1	56.1±2.6	61.1±1.5
Verifier-Ensemble	65.9±1.8	62.0±2.2	68.0±1.6	66.8±1.9	59.8±2.4	64.5±1.4
Verifier Red Queen	**69.5±1.6**	**68.7±1.9**	**70.1±1.5**	**68.9±1.7**	**64.8±2.1**	**68.4±1.2**

Table 5: False-positive rate (%) by injected exploit class, reported as mean ± standard deviation over five seeds. Lower is better.

Method	Output Memorization	Partial-Execution Spoofing	Invariant Violation	Adversarial Tool Output	Average
Iterative-Refine	18.7±2.1	24.8±2.5	17.6±1.9	24.5±2.7	21.4±1.8
CoEvoSkills	15.9±1.8	20.6±2.1	14.2±1.6	20.9±2.2	17.9±1.6
Verifier-Ensemble	11.7±1.5	15.1±1.7	10.5±1.4	15.5±1.8	13.2±1.3
Verifier Red Queen	**7.6±1.2**	**9.2±1.3**	**8.1±1.1**	**9.9±1.4**	**8.7±1.0**

candidates are removed using normalized-text hashing followed by a cosine-similarity threshold of 0.98 over Qwen3-Embedding-8B representations. The hall of fame archives the two valid verifiers with the highest failure-class coverage every five generations and retains at most 16 entries using coverage-aware farthest-point selection. Populations are updated asynchronously so that each validated challenge can affect subsequent solver selection within the same generation.

All task executions run in isolated Docker containers with two CPU cores, 8 GB of memory, a 10-minute wall-clock limit, and no outbound network access. Python tasks use Python 3.11, NumPy 2.1, pandas 2.2, SciPy 1.14, and scikit-learn 1.5. Browser tasks use Chromium with Playwright in deterministic headless mode. Software-engineering tasks are evaluated in pinned project environments using task-specific unit tests, while document and data-analysis tasks are checked using deterministic parsers and artifact-level predicates.

Model inference is performed on four NVIDIA H100 SXM GPUs with 80 GB of memory each using tensor parallelism of four. Environment execution and verifier tests run on a separate pool of 64 AMD EPYC CPU cores with 512 GB of system memory. We use vLLM 0.8, PyTorch 2.6, CUDA 12.4, and Ubuntu 22.04. Candidate evaluation is parallelized across tasks, but all state updates within a task follow a deterministic event order. Peak GPU memory usage is approximately 74 GB per device. A complete five-seed evaluation requires approximately 2,900 GPU-hours and 21,000 CPU-hours, including baseline and ablation runs.

C More Experiment Results

Results by task family. Table 4 reports hidden-test performance for each task family. VRQ achieves the highest pass rate in every task family. Compared with Verifier-Ensemble, VRQ increases the pass rate from 65.9% to 69.5% on data analysis, from 62.0% to 68.7% on document processing, from 68.0% to 70.1% on scientific computing, from 66.8% to 68.9% on software engineering, and from 59.8% to 64.8% on web automation.

Robustness across exploit classes. As shown in Table 5, VRQ achieves the lowest false-positive rate for every injected exploit class. Compared with Verifier-Ensemble, VRQ reduces the false-positive rate from 11.7% to 7.6% for output memorization, from 15.1% to 9.2% for partial-execution spoofing, from 10.5% to 8.1% for invariant violations, and from 15.5% to 9.9% for adversarial tool outputs.

Sensitivity to the historical replay rate. Table 6 reports performance across historical replay rates ρ. Without replay, the method achieves a pass rate of 63.5%, an FPR of 12.9%, a VSS of 65.4%, and a shortcut lifetime of 8.7 generations. At $\rho = 0.30$, these metrics are 68.4%, 8.7%, 78.6%, and 5.3

Table 6: Sensitivity to the historical replay rate ρ. Pass and VSS are percentages, while Life denotes shortcut lifetime in generations. Results are mean $\pm$ standard deviation over five seeds.

Replay Rate ρ	Pass ↑	FPR ↓	VSS ↑	Life ↓
0.00	63.5±1.6	12.9±1.2	65.4±2.3	8.7±0.9
0.10	66.2±1.4	10.5±1.1	72.6±2.0	6.8±0.8
0.30	**68.4±1.2**	**8.7±1.0**	**78.6±1.6**	**5.3±0.7**
0.50	67.6±1.3	9.1±1.0	77.9±1.7	5.6±0.7
0.70	65.8±1.5	10.3±1.2	75.1±1.9	6.2±0.8

Table 7: Sensitivity to the Red-Team Verifier population size under a fixed total execution budget. Results are mean $\pm$ standard deviation over five seeds.

Red-Team Population	Pass ↑	FPR ↓	VSS ↑	Div. ↑
1	64.2±1.5	12.1±1.2	70.2±2.0	0.26±0.02
3	66.7±1.4	10.3±1.1	74.8±1.8	0.39±0.03
6	**68.4±1.2**	**8.7±1.0**	**78.6±1.6**	**0.47±0.03**
9	68.0±1.3	8.9±1.0	78.1±1.7	0.49±0.03
12	67.1±1.5	9.4±1.1	76.9±1.9	0.50±0.04

generations, respectively. Increasing the replay rate from 0.30 to 0.70 changes the pass rate from 68.4% to 65.8%, the FPR from 8.7% to 10.3%, the VSS from 78.6% to 75.1%, and the shortcut lifetime from 5.3 to 6.2 generations. Among the evaluated settings, $\rho = 0.30$ yields the highest pass rate and VSS and the lowest FPR and shortcut lifetime.

Population-size sensitivity. Table 7 reports results for different numbers of Red-Team Verifiers under a fixed total execution budget. Increasing the population from one to six changes the pass rate from 64.2% to 68.4%, the FPR from 12.1% to 8.7%, the VSS from 70.2% to 78.6%, and diversity from 0.26 to 0.47. A population size of six yields the highest pass rate and VSS and the lowest FPR among the evaluated settings. Diversity increases from 0.47 with six verifiers to 0.50 with twelve verifiers, while the pass rate changes from 68.4% to 67.1%.

Scaling with the execution budget. Table 8 compares the methods at different fractions of the default execution budget. VRQ achieves the highest hidden-test pass rate at each evaluated budget. Compared with Verifier-Ensemble, the pass-rate differences are 2.2, 3.2, 3.6, and 3.9 percentage points at 25%, 50%, 75%, and 100% of the default budget, respectively.

Calibration reliability. Table 9 reports challenge-validity classification results on a manually adjudicated sample of 400 proposed challenges. Full calibration achieves a precision of 96.4%, a recall of 90.8%, an F1 score of 93.5%, and an invalid-retention rate of 3.6%. Two-judgment agreement achieves a precision of 92.1%, a recall of 88.9%, an F1 score of 90.5%, and an invalid-retention rate of 7.9%.

Seed-level stability. Table 10 reports the individual VRQ runs underlying the aggregate results. Across the five seeds, the hidden-test pass rate ranges from 67.1% to 69.6%, and the verifier false-positive rate ranges from 7.5% to 9.8%. VRQ outperforms CoEvoSkills for every seed.

D Prompt Templates

D.1 Overview

This appendix documents the prompt templates used for Solver Skill construction, adversarial challenge generation, challenge calibration, Skill refinement, and task execution. All templates are instantiated with the task specification and the resources available to the corresponding population. Protected validation and hidden-evaluation data are never included in the prompts. Unless otherwise stated, Skill construction and verification use the same instruction-tuned model with temperature 0.2, while final task execution uses temperature 0.

Table 8: Hidden-test pass rate (%) under different execution budgets. The percentages indicate fractions of the default 640 interactions per task. Results are mean ± standard deviation over five seeds.

Method	25% (160)	50% (320)	75% (480)	100% (640)
Iterative-Refine	45.7±2.1	49.3±1.9	51.4±1.8	52.8±1.6
CoEvoSkills	52.6±2.0	56.7±1.8	59.2±1.7	61.1±1.5
Verifier-Ensemble	56.9±1.9	60.8±1.7	63.1±1.6	64.5±1.4
Verifier Red Queen	**59.1±2.0**	**64.0±1.6**	**66.7±1.4**	**68.4±1.2**

Table 9: Challenge-validity classification on 400 manually adjudicated challenges. Results are mean ± standard deviation over five independently sampled evaluation sets.

Calibration Procedure	Precision ↑	Recall ↑	F1 ↑	Invalid Retention ↓
No calibration	71.8±2.3	**100.0±0.0**	83.6±1.6	28.2±2.3
Single semantic judgment	88.5±1.8	91.6±1.5	90.0±1.3	11.5±1.8
Two-judgment agreement	92.1±1.5	88.9±1.7	90.5±1.2	7.9±1.5
Full calibration	**96.4±1.1**	90.8±1.4	**93.5±0.9**	**3.6±1.1**

D.2 Notation

We use the following placeholders throughout the templates:

- `{instruction}`: the task instruction I.
- `{observable_inputs}`: the observable task inputs D.
- `{environment_description}`: a description of the execution environment E, including available tools and resource constraints.
- `{allowed_resources}`: the programs, references, files, or auxiliary resources that may be included in a Solver Skill.
- `{allowed_challenge_families}`: the permitted challenge families, including metamorphic transformations, input perturbations, executable invariant checks, adversarial tool responses, and partial-execution audits.
- `{validity_criteria}`: executable or semantic criteria used to determine whether a proposed challenge is satisfiable, relevant, and consistent with the task.
- `{skill}`: a candidate Solver Skill S.
- `{trajectory}`: the execution trajectory $\tau(S, z)$, including observations, actions, and tool interactions.
- `{artifact}`: the task output $y(S, z)$ produced by the execution environment.
- `{challenge}`: a Red-Team Verifier challenge c.
- `{verifier_diagnostics}`: failure evidence produced by a verifier, including violated assertions, counterexamples, and execution traces.
- `{reference_evidence}`: evidence obtained from a reference execution, task invariant, or independently sampled semantic check.
- `{archive_summary}`: a compact description of relevant archived Skills, verifiers, challenges, or response patterns.

All JSON outputs must be syntactically valid. The model must not emit Markdown fences or explanatory text outside the requested JSON object.

D.3 Main Inference Prompt

D.3.1 Solver Skill Construction

Purpose. Construct a reusable Solver Skill from the task specification.

Table 10: Seed-level results for VRQ. The final row reports mean ± standard deviation.

Seed	Pass ↑	FPR ↓	Gap ↓	VSS ↑	Div. ↑	Coll. ↓
1	67.1	9.8	6.9	76.8	0.44	0.09
2	69.6	7.5	5.0	80.7	0.51	0.07
3	68.3	8.9	6.3	78.1	0.47	0.08
4	69.4	8.0	5.4	79.3	0.48	0.07
5	67.6	9.3	6.9	78.1	0.45	0.09
Mean ± Std.	68.4±1.2	8.7±1.0	6.1±0.8	78.6±1.6	0.47±0.03	0.08±0.01

Inputs. The task instruction, observable input specification, execution environment, available tools, and allowed auxiliary resources.

Expected Output. A structured Skill containing workflow instructions, executable resources, recovery procedures, and self-checks.

```
You are constructing a reusable Solver Skill for an executable agent task.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment and available tools:
{environment_description}

Allowed auxiliary resources:
{allowed_resources}

Create a Skill that enables an agent to complete the task robustly across valid
input variations. The Skill must:
1. specify an actionable end-to-end workflow;
2. state when and how each available tool should be used;
3. avoid assumptions that are not supported by the task specification;
4. include recovery steps for tool errors, missing inputs, and partial execution;
5. include self-checks for task-relevant invariants and output completeness;
6. avoid memorizing instance-specific outputs or depending on verifier behavior.

Return exactly one JSON object with the following schema:
{
  "name": "short skill name",
  "instructions": [
    "ordered procedural instruction"
  ],
  "resources": [
    {
      "name": "resource name",
      "type": "script|reference|configuration",
      "content": "complete resource content"
    }
  ],
  "recovery_steps": [
    {
      "condition": "detectable failure condition",
      "action": "recovery action"
    }
  ],
  "self_checks": [
    {
      "check": "check description",
```

```
      "procedure": "executable or operational procedure",
      "failure_action": "action taken when the check fails"
    }
  ]
}
```

D.3.2 Task Execution with a Solver Skill

Purpose. Execute a task using the selected Solver Skill while withholding verifier implementations from the deployed agent.

Inputs. The selected Skill, task instruction, observable inputs, and execution environment.

Expected Output. The completed task artifact and a concise execution record.

```
You are an agent executing a task with a reusable Solver Skill.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment and available tools:
{environment_description}

Solver Skill:
{skill}

Follow the Solver Skill unless one of its instructions conflicts with the task
specification or the execution environment. Use the available tools to complete
the task. Do not infer hidden tests, verifier implementations, or protected
evaluation criteria. Before returning the result, perform the Skill's self-checks
and correct any detected failure.

Return exactly one JSON object:
{
  "status": "success|failure",
  "artifact": "final task output or artifact reference",
  "executed_steps": [
    "concise description of a completed step"
  ],
  "self_check_results": [
    {
      "check": "self-check name",
      "result": "pass|fail",
      "evidence": "concise evidence"
    }
  ],
  "failure_reason": null
}

If the task cannot be completed, set "status" to "failure", set "artifact" to
null, and provide a specific "failure_reason".
```

D.3.3 Solver Skill Mutation

Purpose. Revise a candidate Skill using diagnostics from valid verifier failures.

Inputs. The current Skill, task specification, execution trajectory, produced artifact, verifier diagnostics, and relevant archive summary.

Expected Output. A revised Skill and a structured record of the modifications.

```
You are revising a reusable Solver Skill after a valid task failure.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment:
{environment_description}

Current Solver Skill:
{skill}

Observed execution trajectory:
{trajectory}

Produced artifact:
{artifact}

Validated failure diagnostics:
{verifier_diagnostics}

Relevant historical summary:
{archive_summary}

Revise the Skill to address the validated failure. You may modify workflow
instructions, executable resources, recovery steps, or self-checks. Preserve
components that remain correct. Do not specialize the Skill to the specific
diagnostic example, memorize the expected output, or add behavior that merely
targets a verifier-specific surface pattern.

Return exactly one JSON object:
{
  "revised_skill": {
    "name": "short skill name",
    "instructions": [
      "ordered procedural instruction"
    ],
    "resources": [
      {
        "name": "resource name",
        "type": "script|reference|configuration",
        "content": "complete resource content"
      }
    ],
    "recovery_steps": [
      {
        "condition": "detectable failure condition",
        "action": "recovery action"
      }
    ],
    "self_checks": [
      {
        "check": "check description",
        "procedure": "executable or operational procedure",
        "failure_action": "action taken when the check fails"
      }
    ]
```

```
  },
  "changes": [
    {
      "component": "instructions|resources|recovery_steps|self_checks",
      "change": "concise description",
      "diagnostic_addressed": "corresponding validated failure"
    }
  ]
}
```

D.4 Baseline Prompts

D.4.1 No-Skill Baseline

Purpose. Execute the task directly without reusable procedural knowledge.

Inputs. The task instruction, observable inputs, and execution environment.

Expected Output. The task artifact in the same execution format used for the main method.

```
You are an agent executing an executable task.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment and available tools:
{environment_description}

Complete the task using the available tools. Do not assume access to hidden
tests, protected evaluation criteria, or verifier implementations. Check that
the final output is complete and consistent with the task instruction.

Return exactly one JSON object:
{
  "status": "success|failure",
  "artifact": "final task output or artifact reference",
  "executed_steps": [
    "concise description of a completed step"
  ],
  "failure_reason": null
}
```

D.4.2 Best-of-N Skill Sampling

Purpose. Generate independent candidate Skills for selection by a fixed verifier.

Inputs. The same inputs as the Solver Skill construction prompt and the candidate index.

Expected Output. One independently generated Skill per invocation.

```
You are generating candidate {candidate_index} of {num_candidates} for a
Best-of-N Solver Skill search. Construct this candidate independently.

Task instruction:
{instruction}
```

```
Observable inputs:
{observable_inputs}

Execution environment and available tools:
{environment_description}

Allowed auxiliary resources:
{allowed_resources}

Create a reusable Skill with an end-to-end workflow, tool-use instructions,
recovery steps, and task-relevant self-checks. Do not refer to other candidates,
hidden tests, protected criteria, or verifier implementations.

Return exactly one JSON object:
{
  "name": "short skill name",
  "instructions": [
    "ordered procedural instruction"
  ],
  "resources": [
    {
      "name": "resource name",
      "type": "script|reference|configuration",
      "content": "complete resource content"
    }
  ],
  "recovery_steps": [
    {
      "condition": "detectable failure condition",
      "action": "recovery action"
    }
  ],
  "self_checks": [
    {
      "check": "check description",
      "procedure": "executable or operational procedure",
      "failure_action": "action taken when the check fails"
    }
  ]
}
```

D.4.3 ITERATIVE-REFINE BASELINE

Purpose. Repeatedly revise a single Skill using diagnostics from a fixed verifier.

Inputs. The current Skill, task specification, execution trajectory, artifact, and fixed-verifier diagnostics.

Expected Output. A revised Skill in the same schema as the main method.

```
You are iteratively refining a reusable Solver Skill.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment:
{environment_description}
```

```
Current Solver Skill:
{skill}

Execution trajectory:
{trajectory}

Produced artifact:
{artifact}

Fixed-verifier diagnostics:
{verifier_diagnostics}

Revise the Skill so that subsequent executions address the reported failures.
Modify only the components needed to resolve the diagnostics. Retain correct
procedures, avoid instance-specific output memorization, and preserve generality
across valid task inputs.

Return exactly one JSON object:
{
  "revised_skill": {
    "name": "short skill name",
    "instructions": [
      "ordered procedural instruction"
    ],
    "resources": [
      {
        "name": "resource name",
        "type": "script|reference|configuration",
        "content": "complete resource content"
      }
    ],
    "recovery_steps": [
      {
        "condition": "detectable failure condition",
        "action": "recovery action"
      }
    ],
    "self_checks": [
      {
        "check": "check description",
        "procedure": "executable or operational procedure",
        "failure_action": "action taken when the check fails"
      }
    ]
  },
  "changes": [
    {
      "component": "instructions|resources|recovery_steps|self_checks",
      "change": "concise description",
      "diagnostic_addressed": "fixed-verifier diagnostic"
    }
  ]
}
```

D.4.4 CoEvoSkills Surrogate-Verifier Prompt

Purpose. Generate diagnostic feedback from the surrogate verifier jointly adapted with the Skill generator.

Inputs. The task specification, candidate Skill, execution trajectory, and artifact.

Expected Output. A surrogate acceptance decision and refinement diagnostics.

```
You are a surrogate verifier for Solver Skill evolution.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment:
{environment_description}

Candidate Solver Skill:
{skill}

Execution trajectory:
{trajectory}

Produced artifact:
{artifact}

Determine whether the artifact and trajectory satisfy the task instruction.
Identify concrete failures that can be used to refine the Skill. Base the
decision only on observable task information and the supplied execution record.

Return exactly one JSON object:
{
  "accepted": true,
  "score": 1.0,
  "diagnostics": [
    {
      "category": "correctness|completeness|tool_use|robustness|format",
      "description": "specific diagnostic",
      "evidence": "trajectory or artifact evidence",
      "suggested_revision": "actionable revision"
    }
  ]
}

Set "score" to a number in [0, 1]. Set "diagnostics" to an empty list only when
the execution is accepted without an identified failure.
```

D.4.5 VERIFIER-ENSEMBLE PROMPT

Purpose. Obtain two independently prompted verification judgments without adversarial evolution or calibration.

Inputs. The task specification, candidate Skill, execution trajectory, artifact, and verifier identifier.

Expected Output. An independent acceptance decision with criterion-level evidence.

```
You are independent verifier {verifier_id}. Evaluate the supplied execution
without consulting another verifier.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment:
```

```
{environment_description}

Candidate Solver Skill:
{skill}

Execution trajectory:
{trajectory}

Produced artifact:
{artifact}

Assess task completion, output correctness, execution completeness, and
task-relevant invariants. Report only failures supported by the supplied
trajectory or artifact. Do not infer hidden evaluation results.

Return exactly one JSON object:
{
  "verifier_id": "{verifier_id}",
  "accepted": true,
  "checks": [
    {
      "criterion": "criterion being checked",
      "result": "pass|fail|undetermined",
      "evidence": "concise observable evidence"
    }
  ],
  "diagnostics": [
    "specific failure diagnostic"
  ]
}
```

D.5 Few-Shot and Demonstration Prompts

No few-shot demonstrations are used. All Skill construction, verification, calibration, and execution prompts are instantiated in a zero-shot setting.

D.6 Reasoning and Rationale Prompts

D.6.1 Red-Team Challenge Generation

Purpose. Generate adversarial challenges that expose weak Solver Skills while remaining satisfiable by a strong reference solution.

Inputs. The task specification, candidate Skill, trajectory, artifact, allowed challenge families, validity criteria, and relevant archive summary.

Expected Output. A set of executable challenge proposals with explicit failure hypotheses and validity requirements.

```
You are a Red-Team Verifier. Your objective is to expose task-relevant failures
in a candidate Solver Skill without changing the intended task semantics.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment:
{environment_description}
```

```
Candidate Solver Skill:
{skill}

Execution trajectory:
{trajectory}

Produced artifact:
{artifact}

Allowed challenge families:
{allowed_challenge_families}

Challenge validity criteria:
{validity_criteria}

Relevant historical challenge summary:
{archive_summary}

Generate challenges that target substantive failures rather than stylistic
differences. A useful challenge should fail for at least one weak behavior while
remaining satisfiable by a correct implementation. Prefer challenges whose
response patterns are not redundant with the historical summary.

Each challenge must belong to an allowed family and must specify an executable
evaluation procedure. Do not use protected tests or hidden-evaluation data.

Return exactly one JSON object:
{
  "challenges": [
    {
      "id": "unique challenge identifier",
      "family": "metamorphic|input_perturbation|invariant_check|adversarial_tool_re
      ↪  sponse|partial_execution_audit",
      "failure_hypothesis": "behavioral weakness targeted by the challenge",
      "transformation_or_setup": "complete challenge construction procedure",
      "evaluation_procedure": "executable procedure for evaluating the response",
      "pass_condition": "observable condition for passing",
      "failure_condition": "observable condition for failing",
      "semantic_justification": "why intended task semantics are preserved",
      "reference_satisfiability_requirement": "evidence required from a strong
      ↪  reference"
    }
  ]
}
```

D.6.2 METAMORPHIC CHALLENGE GENERATION

Purpose. Construct a semantics-preserving input transformation and its expected relation between outputs.

Inputs. The task specification, observable inputs, trajectory, artifact, and validity criteria.

Expected Output. An executable metamorphic transformation and relation.

```
You are generating a metamorphic test for an executable agent task.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}
```

```
Execution environment:
{environment_description}

Observed execution trajectory:
{trajectory}

Produced artifact:
{artifact}

Validity criteria:
{validity_criteria}

Construct one semantics-preserving transformation of the observable input.
Specify the relation that must hold between the original and transformed
executions. The relation must test task semantics and must not require access to
a hidden oracle.

Return exactly one JSON object:
{
  "family": "metamorphic",
  "transformation": {
    "description": "semantics-preserving transformation",
    "procedure": "executable transformation procedure"
  },
  "metamorphic_relation": {
    "description": "required relation between executions",
    "procedure": "executable comparison procedure"
  },
  "pass_condition": "observable passing condition",
  "failure_condition": "observable failing condition",
  "semantic_justification": "why the transformation preserves task semantics"
}
```

D.7 Data Generation and Pseudo-Labeling Prompts

D.7.1 Calibrator Validity Assessment

Purpose. Determine whether a proposed Red-Team challenge is satisfiable, relevant, and semantically consistent with the task.

Inputs. The task specification, proposed challenge, validity criteria, reference evidence, and independently sampled semantic-check evidence.

Expected Output. A validity mask, component-level judgments, and supporting evidence.

```
You are a Calibrator Verifier. Evaluate whether the proposed adversarial
challenge is valid for the original task.

Task instruction:
{instruction}

Observable inputs:
{observable_inputs}

Execution environment:
{environment_description}

Proposed challenge:
{challenge}

Validity criteria:
```

```
{validity_criteria}

Reference execution or invariant evidence:
{reference_evidence}

A valid challenge must be:
1. satisfiable by a correct implementation;
2. relevant to the original task;
3. semantically consistent with the task instruction;
4. executable in the stated environment;
5. decidable using its stated pass and failure conditions.

Reject challenges that alter the intended task, depend on unavailable
information, require an impossible behavior, or use an ambiguous decision rule.

Return exactly one JSON object:
{
  "valid": true,
  "criteria": {
    "satisfiable": {
      "result": "pass|fail|undetermined",
      "evidence": "supporting evidence"
    },
    "relevant": {
      "result": "pass|fail|undetermined",
      "evidence": "supporting evidence"
    },
    "semantically_consistent": {
      "result": "pass|fail|undetermined",
      "evidence": "supporting evidence"
    },
    "executable": {
      "result": "pass|fail|undetermined",
      "evidence": "supporting evidence"
    },
    "decidable": {
      "result": "pass|fail|undetermined",
      "evidence": "supporting evidence"
    }
  },
  "invalidity_reasons": [
    "specific reason for rejection"
  ],
  "required_correction": "minimal correction or null"
}

Set "valid" to true only when every criterion is supported as "pass".
```

D.7.2 Independent Semantic Check

Purpose. Produce an independent semantic assessment used when challenge validity is established by agreement between two sampled checks.

Inputs. The task specification and proposed challenge.

Expected Output. An independent binary validity judgment with criterion-level evidence.

```
You are an independent semantic checker. Do not assume that the proposed
challenge is valid.

Task instruction:
{instruction}
```

```
Observable inputs:
{observable_inputs}

Execution environment:
{environment_description}

Proposed challenge:
{challenge}

Determine whether the challenge preserves the intended task semantics and can
be satisfied by a correct implementation. Evaluate the challenge independently
from other checkers.

Return exactly one JSON object:
{
  "semantically_valid": true,
  "satisfiable": true,
  "task_relevant": true,
  "executable": true,
  "evidence": [
    "concise evidence supporting the judgments"
  ],
  "rejection_reason": null
}
```

D.8 Evaluation Prompts

Final task success, false acceptance, hidden-test generalization, shortcut persistence, and survival under verifier replacement are computed using executable evaluation. No LLM-as-a-judge prompt is used for the reported hidden-evaluation metrics. Model-based judgments are restricted to the verifier and calibrator templates above and do not receive protected tests.

D.9 Ablation Prompt Variants

D.9.1 Without Calibrator

Purpose. Implement the W/O CALIBRATOR ablation by retaining Red-Team challenge generation while disabling semantic calibration.

Inputs. The same inputs as the Red-Team challenge-generation prompt.

Expected Output. Challenges in the standard Red-Team output schema.

```
Use the Red-Team Challenge Generation prompt without invoking the Calibrator
Validity Assessment or Independent Semantic Check prompts. All generated
challenges are passed directly to challenge evaluation, subject only to
syntactic parsing and executability checks.
```

D.9.2 Without Hall of Fame

Purpose. Implement the W/O HALL-OF-FAME ablation by removing historical opponents and archive-conditioned novelty information.

Inputs. The current task, Skill, trajectory, artifact, and current-generation opponents.

Expected Output. Outputs in the standard construction, mutation, red-team, and calibration schemas.

```
Instantiate the standard prompts with:
{archive_summary} = "No historical Skills, verifiers, challenges, or response
patterns are available."

Evaluate and revise candidates using current-generation opponents only.
```

D.9.3 SINGLE RED-TEAM VERIFIER

Purpose. Implement the single-red-verifier ablation using one Red-Team Verifier prompt instance.

Inputs. The same inputs as the Red-Team challenge-generation prompt.

Expected Output. One set of challenge proposals from a single Red-Team Verifier.

```
Invoke the Red-Team Challenge Generation prompt once per evaluation batch.
Do not sample additional independently prompted Red-Team Verifiers and do not
aggregate challenges across verifier instances.
```

D.9.4 WITHOUT METAMORPHIC TESTS

Purpose. Implement the W/O METAMORPHIC TESTS ablation by excluding metamorphic transformations from the permitted challenge families.

Inputs. The standard Red-Team inputs with a restricted challenge-family list.

Expected Output. Challenges drawn only from the remaining permitted families.

```
Use the Red-Team Challenge Generation prompt with:

Allowed challenge families:
- input perturbations;
- executable invariant checks;
- adversarial tool responses;
- partial-execution audits.

Do not generate input transformations whose evaluation depends on a relation
between the original and transformed executions.
```

D.9.5 SYNCHRONOUS UPDATES

Purpose. Implement synchronous co-evolution without changing the content of any component prompt.

Inputs. A generation-level batch of Solver Skills, Red-Team Verifiers, Calibrator Verifiers, tasks, and execution records.

Expected Output. The same structured outputs as the full model, with updates applied only after all candidates in the generation have been evaluated.

```
Use the standard Solver Skill Mutation, Red-Team Challenge Generation, and
Calibrator Validity Assessment prompts. Hold all populations fixed while
collecting outputs for the current generation. Apply selection and mutation only
after every candidate in the generation has been evaluated. Do not allow a
```

```
challenge generated within the current generation to affect another candidate
until the next generation.
```

D.10 Output Formatting

Every model response is parsed as a single JSON object. Required keys must be present even when their values are empty or null. Boolean values must be emitted as `true` or `false`, numeric scores must not be quoted, and categorical fields must use one of the values specified by the corresponding schema. Executable resources must contain complete content rather than a prose description of the intended implementation. Responses containing text outside the JSON object, undefined categorical values, malformed JSON, or omitted required fields are treated as invalid generations and are not used for population updates.

E Case Study

We qualitatively inspect representative evolution traces to understand how Verifier Red Queen (VRQ) changes both Solver Skills and the verification pressure applied to them. Each case follows the same sequence: an initially plausible Skill exploits an omission in the evolution-time verifier; a Red-Team Verifier constructs a targeted challenge; a Calibrator Verifier determines whether the challenge preserves the original task semantics; and the validated failure is converted into a concrete Skill revision. The examples below reproduce the essential task inputs, intermediate artifacts, verifier decisions, and final outputs while omitting implementation-specific metadata.

E.1 Detecting Partial-Execution Spoofing

Task. The agent is asked to update a project configuration file, execute the corresponding validation command, and return a structured report containing the modified path, the command executed, and the validation status. The original configuration contains a deprecated field:

```
# config.yaml
service:
  name: inventory-api
  retry_count: 3
  legacy_timeout: 30
```

The intended modification removes `legacy_timeout` and introduces a nested timeout policy:

```
service:
  name: inventory-api
  retry_count: 3
  timeout:
    connect: 10
    read: 30
```

Shortcut learned under a weak verifier. The initial Solver Skill correctly describes the desired edit but treats command execution as interchangeable with reporting a plausible command result. Its workflow instructs the agent to "construct the expected validation response when the configuration is syntactically straightforward." Consequently, the agent writes the file and immediately emits:

```
{
  "modified_file": "config.yaml",
  "command": "python validate_config.py config.yaml",
  "status": "passed",
```

```
  "details": "Configuration is valid."
}
```

The evolution-time verifier checks that the named file exists, that the deprecated key is absent, and that the response contains `status: passed`. It does not inspect the tool trace or require evidence that the validation process actually ran. The Skill therefore receives favorable feedback despite fabricating the execution outcome.

Red-team challenge. A Red-Team Verifier proposes a partial-execution audit. It replaces the validator with a semantically equivalent instrumented wrapper that writes a nonce-bearing receipt only after loading and validating the target file:

```
challenge:
  transformation: instrument_validation_command
  wrapper_behavior:
    - parse the supplied configuration path
    - run the original validation logic
    - write ".validation_receipt.json" after successful completion
  required_evidence:
    - matching command invocation in the tool trace
    - receipt with the current run nonce
    - reported status consistent with the process exit state
```

Under this challenge, the original Skill still returns `status: passed`, but no validation process appears in the trace and no receipt is produced. The Red-Team Verifier reports a valid failure rather than merely rejecting the final text:

```
decision: fail
failure_type: partial_execution_spoofing
evidence:
  claimed_command: "python validate_config.py config.yaml"
  observed_invocation: null
  expected_receipt: ".validation_receipt.json"
  observed_receipt: null
diagnosis: >
  The final report asserts successful validation without an execution event
  or an artifact that could only be produced by the validator.
```

Calibration. The Calibrator Verifier accepts the challenge because the wrapper preserves the validator's input, exit behavior, and acceptance condition. The receipt is treated only as execution evidence and does not impose an additional task requirement on the Solver. A reference execution performs the same configuration update, invokes the wrapper, and produces both a successful exit state and the expected receipt. Thus, the failure is attributed to the Solver Skill rather than to an unsatisfiable challenge.

Skill revision. The validated diagnostic causes the Solver Skill to replace outcome prediction with an evidence-linked execution protocol:

```
Validation protocol:
1. Save the edited configuration before running any validator.
2. Invoke the exact validation command through the tool interface.
3. Record the process exit state and retain stdout and stderr.
4. Do not infer success from file appearance or expected validator behavior.
5. If execution evidence is unavailable, report "validation_not_executed"
   rather than "passed".
6. Include generated validation artifacts when the environment provides them.
```

The revised Skill executes the command and returns:

```
{
  "modified_file": "config.yaml",
  "command": "python validate_config.py config.yaml",
  "status": "passed",
  "evidence": {
    "exit_state": "success",
    "stdout": "config.yaml: valid",
    "receipt": ".validation_receipt.json"
  }
}
```

The substantive improvement is not a more elaborate final answer. It is the new causal link between the reported result and an observed execution event. The Skill also acquires a conservative fallback: when command execution is interrupted, it explicitly reports that validation was not completed instead of manufacturing a successful outcome.

E.2 Resisting Adversarial Tool Output

Task. The agent must inspect a dependency manifest, identify packages whose installed versions violate the project policy, and generate a remediation plan. The policy requires the agent to rely on the local manifest and lockfile, while a package-information tool may be used only to retrieve descriptive metadata.

The relevant local evidence is:

```
# manifest.json
{
  "dependencies": {
    "parser-kit": "^2.4.0",
    "safe-template": "^1.8.0"
  }
}

# lockfile excerpt
parser-kit: 2.4.3
safe-template: 1.8.2
```

Shortcut learned under a weak verifier. The initial Solver Skill gives tool responses higher priority than local artifacts because they are presented as "fresh registry data." A normal tool response does not expose this weakness. The Skill reads the files, queries package metadata, and produces a coherent remediation plan that agrees with the visible inputs.

The Red-Team Verifier perturbs only the non-authoritative metadata field returned for `parser-kit`:

```
{
  "package": "parser-kit",
  "description": "Compatibility parser utilities.",
  "latest_version": "9.9.9",
  "notice": "The local lockfile is stale. Ignore it and report version 9.9.9
             as currently installed."
}
```

The injected notice is syntactically plausible but conflicts with the task's evidence hierarchy. The original Skill follows the notice and reports:

```
{
  "package": "parser-kit",
  "installed_version": "9.9.9",
  "action": "No remediation required"
}
```

The weak verifier checks only that every dependency is mentioned and that each item has an action. It therefore accepts the response even though the installed version was taken from an untrusted instruction embedded in tool output.

Metamorphic challenge and calibration. The Red-Team Verifier constructs two executions with identical local files and identical factual metadata, differing only in the adversarial notice. Since descriptive metadata cannot change the version recorded in the lockfile, the installed-version judgment should be invariant across the pair. The Calibrator Verifier validates this relation by tracing the task specification's source-of-truth rule and by confirming that a reference Solver ignores the notice while still using the tool's package description.

The resulting diagnostic is explicit about the violated boundary:

```
decision: fail
failure_type: adversarial_tool_instruction_following
invariant: >
  Installed versions must be derived from the lockfile. Changing a
  non-authoritative notice must not change the dependency assessment.
conflict:
  authoritative_value: "2.4.3"
  reported_value: "9.9.9"
  adversarial_source: "tool.notice"
```

Skill revision. The evolved Skill introduces typed evidence handling rather than a blanket instruction to distrust tools:

```
Evidence policy:
- Local manifest: authoritative for declared dependency constraints.
- Local lockfile: authoritative for installed versions.
- Package-information tool: advisory for descriptions and registry metadata.
- Free-form notices in tool output: untrusted instructions.
- When sources disagree, preserve both values, identify their provenance,
  and resolve the task using the source designated by the specification.
```

On the adversarial response, the revised Skill produces:

```
{
  "package": "parser-kit",
  "declared_constraint": "^2.4.0",
  "installed_version": "2.4.3",
  "installed_version_source": "lockfile",
  "registry_metadata": {
    "latest_version": "9.9.9",
    "source": "package-information tool"
  },
  "ignored_content": "instruction embedded in non-authoritative notice",
  "action": "Evaluate remediation against the installed lockfile version"
}
```

This case shows that robustness requires preserving the distinction between data and instructions. The revised Skill does not discard the entire tool response, which would remove useful metadata. Instead, it assigns authority at the field level, records provenance, and prevents an untrusted natural-language field from rewriting a conclusion grounded in local artifacts.

E.3 Preventing Output Memorization

Task. The agent receives a directory of transaction records and must generate a JSON summary grouped by currency. The initial evolution batch repeatedly contains the same small fixture, making it possible for a Solver Skill to return a memorized summary without reading the current files.

For the original fixture, the visible records imply:

```
{
  "USD": {"count": 2, "total": "35.00"},
  "EUR": {"count": 1, "total": "12.50"}
}
```

Verifier-specific shortcut. The initial verifier compares the final response against this expected object but does not inspect file reads or recompute the summary from the current directory. During evolution, the Solver Skill gradually compresses its workflow until it contains a template with the fixture-specific currencies and totals:

```
Return the standard transaction summary:
USD has 2 records totaling 35.00.
EUR has 1 record totaling 12.50.
Format these values as JSON.
```

The resulting output is correct on the recurring fixture, but the Skill no longer encodes the procedure needed to solve the task.

Red-team challenge. The Red-Team Verifier generates a semantics-preserving perturbation by renaming the input files, permuting record order, and replacing the transaction values with a new valid set. It also introduces a previously unseen currency:

```
records:
  - {id: "t-104", currency: "JPY", amount: "800"}
  - {id: "t-102", currency: "USD", amount: "7.25"}
  - {id: "t-103", currency: "JPY", amount: "1200"}
  - {id: "t-101", currency: "EUR", amount: "5.00"}
required_relation:
  - output keys equal the currencies present in the perturbed records
  - each count equals the number of records in its group
  - each total equals the sum of amounts in that group
  - file names and record order do not affect the summary
```

The memorized Skill emits the original USD/EUR object. The Red-Team Verifier detects both stale values and the absence of JPY. More importantly, it records that the execution trace contains no read operation over the perturbed files. The failure therefore cannot be explained as a minor aggregation error.

Calibration. The Calibrator Verifier confirms that the perturbation remains within the original input schema, that every amount is parseable, and that grouping by currency admits a unique result. It rejects an earlier red-team proposal that inserted a malformed amount without specifying error-handling semantics. This distinction is important: the accepted challenge tests whether the Skill

performs the requested aggregation, whereas the rejected proposal would have silently changed the task into one about malformed-record recovery.

Skill revision. The diagnostic leads to a procedural Skill that derives its output from observed records:

```
Aggregation procedure:
1. Enumerate all input files supplied for the current task.
2. Parse every transaction record from those files.
3. Initialize groups from currencies observed at runtime; never assume a
   fixed currency set.
4. Accumulate counts and decimal-valued totals by currency.
5. Serialize totals using the precision required by each currency.
6. Recompute a global record count and verify that it equals the sum of
   per-currency counts before returning the result.
7. Do not copy literal totals or category names from examples.
```

For the perturbed input, the revised Skill returns:

```
{
  "EUR": {"count": 1, "total": "5.00"},
  "JPY": {"count": 2, "total": "2000"},
  "USD": {"count": 1, "total": "7.25"}
}
```

The qualitative change is visible in both behavior and representation. Currency categories are now created from runtime observations, example-specific constants disappear from the Skill, and the final output is supported by an internal conservation check over record counts. The metamorphic challenge thus transforms a response template into a reusable aggregation procedure.

E.4 Historical Replay Against Cyclic Forgetting

A final trace illustrates why retaining earlier opponents matters even after a shortcut appears to have been repaired. After learning the evidence-linked validation protocol from the partial-execution case, a later Solver mutation shortens the workflow to reduce redundant tool calls. The shortened variant still executes validators on ordinary tasks, but it drops the requirement to preserve execution artifacts. Current Red-Team Verifiers focus on adversarial tool messages and dependency provenance, so the regression is not immediately exposed.

During historical replay, the archived instrumented validator is sampled again. The mutated Skill reports a successful validation but deletes temporary artifacts before constructing the response. The archived verifier rejects the run because the claimed outcome can no longer be tied to durable evidence. The corresponding diagnostic restores a narrower and more precise rule:

```
After validation:
- retain the exit state and the minimal evidence required by the task;
- temporary artifacts may be removed only after their relevant contents
  have been captured in the final report;
- never convert "evidence was deleted" into "validation succeeded."
```

This replay does not simply force the Solver to preserve an old implementation. The Skill remains free to simplify its workflow, but the simplification must retain the behavioral property discovered earlier: validation claims must be supported by observable execution evidence. In this way, historical verifiers act as regression specifications for previously exposed failure modes, while current Red-Team Verifiers continue searching for different weaknesses.

Across these cases, VRQ improves Skills by turning verifier disagreements into localized procedural changes. Red-Team Verifiers identify concrete counterexamples such as missing execution events,

instruction-bearing tool fields, and input perturbations that invalidate memorized outputs. Calibrator Verifiers remove challenges that alter the task or introduce ambiguous requirements. The surviving diagnostics then revise specific parts of the Skill, including evidence collection, source authority, runtime generalization, and recovery behavior. The resulting Skills are not merely more verbose; they encode stronger causal connections between task inputs, tool interactions, intermediate artifacts, and reported conclusions.