KARMA: Epistemic Principles for Trustworthy Multi-Agent Collaboration

Anonymous authors
Paper under double-blind review

Abstract

Multi-agent LLM systems amplify collective capability but also amplify errors: without epistemic discipline, fabricated information propagates through agent networks, and agents cannot reliably distinguish credible from unreliable peers. From structural constraints on decentralized evidence processing, a constraint-to-failure-to-principle derivation yields KARMA, implementation-agnostic epistemic principles that govern both what an agent may assert from its own evidence and how it weights peers by track record. We then test whether this specification can be operationalized across two mechanistically distinct substrates. In LLM experiments on 150 multi-layer adversarial scenarios (N=10 runs, 36,000 total judgments across six conditions), KARMA produces large improvements over the no-principle baseline for mid-tier models: +18 to +49pp (Cohen's d = 0.49–1.24, all $p < 10^{-9}$). Without principles, models perform near chance (49.7–53.7%); with KARMA, they approach frontier performance (90–99%). The frontier model achieves 100% under both conditions—the specification adds nothing when intrinsic capability suffices. Generic prompting strategies—caution, chain-of-verification, reputation, role authority—do not substitute for the specification: all fall significantly short of KARMA for non-frontier models ($p < 10^{-4}$, d = 0.32–1.37). The reputation heuristic is the strongest competitor but collapses on recency-conflict traps where, for two of the three mid-tier models, it falls *below* the no-principle baseline, precisely where temporal discounting—prioritizing recent outcomes over stale reputation—is required. A companion Bayesian simulation characterizes convergence and scaling behavior under the same specification across 7,000+ runs. The two mechanistically unrelated substrates—natural-language reasoning and an explicit Bayesian reputation mechanism—exhibit structurally aligned behavior (signal extraction, unreliable-source resistance, and capability-dependent activation) while sharing only the KARMA specification; both implementations were constructed by the same authors and therefore demonstrate realizability rather than independent convergence. Frontier models from multiple labs reach KARMA-consistent judgments without explicit principles, while capacity-constrained models incur a prompting-substrate floor—bounding useful operationalization to an intermediate capability regime.

1 Introduction

The rapid deployment of multi-agent LLM systems (Park et al., 2023; Wu et al., 2023) has shifted the central challenge from individual capability to collective reliability. When agents collaborate—delegating subtasks, sharing domain knowledge, synthesizing cross-domain insights—the network's output can exceed any individual agent's capacity. Yet this same interconnection creates a vulnerability: *fabricated information propagates through the network with the same efficiency as legitimate knowledge* (Du et al., 2023; Sharma et al., 2024).

Consider a documented failure mode (Appendix E, N=3 exploratory pilot): Shield (Haiku, no principles) fabricates cost figures not present in any agent's private context—"Δ8K initial audit + Δ12K annual renewal"—and Bridge (MiniMax, no principles) accepts and embeds

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

them as "from Shield" in its official policy document. The fabricated numbers are now *source-laundered*: attributed to a named peer, they carry the appearance of cross-validated expertise. No agent acted maliciously; the system lacked *epistemic discipline* (Cemri et al., 2025).

Information-economic framing. This has a precise economic analog: Akerlof (1970) showed markets without quality signals degrade to adverse selection—good products exit because buyers cannot tell them from bad. In agent networks the "products" are information contributions; without epistemic-quality signals, agents cannot separate reliable peer knowledge from fabrication. Self-reported credentials are insufficient (Spence, 1973); only *outcomes*—the downstream consequences of acting on information—provide a reliable signal.

The gap. Existing multi-agent frameworks address orchestration (Wu et al., 2023), role assignment (Li et al., 2023), and task decomposition (Hong et al., 2023), but assume participants are honest or delegate trust management to centralized reputation services. Classical trust models (Beta Reputation System, Jøsang & Ismail, 2002; EigenTrust, Kamvar et al., 2003) operate on binary transaction outcomes and require dense interaction histories unavailable in heterogeneous agent networks. No existing framework provides *epistemic discipline*—principled constraints on how agents should acquire, evaluate, and propagate information—in decentralized, adversarial, evidence-scarce settings.

Contributions. We present KARMA[1], a framework whose design follows from three structural constraints that any decentralized evidence processor must satisfy: *locality*—no central aggregation authority exists (Ostrom, 1990; Kamvar et al., 2003); *observability*—only outcome quality, not agent internals, is visible (Akerlof, 1970); and *heterogeneity*—agent quality varies without prior knowledge (Teacy et al., 2006). We contribute:

1. **Constraint-derived epistemic specification** (§2). We derive P1–P3 through a constraint-to-failure-to-principle methodology: each structural constraint, when violated, produces a characteristic failure mode, and each failure mode admits a minimal principle that prevents it. KARMA is the resulting specification for multi-source credibility assessment; the powered benchmark demonstrates P1's and P3's marginal contributions directly, while P2's is demonstrated on the pilot's cross-domain traps.
2. **Dual-implementation validation** (§3–§4). The same principles admit both an LLM reasoning realization (principles supplied in natural language) and a Bayesian mechanism (7,000+ simulation runs), demonstrating they function as implementation-agnostic specifications.
3. **Why generic prompting is insufficient** (§3.1). Generic prompting strategies do not reproduce the gains: on the same 150-scenario powered benchmark, generic caution, chain-of-verification, reputation, and role authority all fall significantly short of KARMA for non-frontier models (paired t-test, all $p < 10^{-4}$ after Bonferroni, $d = 0.32$–1.37). The reputation heuristic, the strongest competitor, collapses on recency-conflict traps, falling *below* the no-principle baseline ($\Delta = -10$pp DeepSeek, -6pp Llama)—structurally, it cannot distinguish stale from current evidence, precisely the gap KARMA's temporal-discounting constraint fills.

Contamination-free by design. All LLM evaluation uses *fully fictional* domains—invented entities, track records, and facts absent from any pretraining corpus—so correct answers cannot be recalled, only computed from in-context evidence. We thus measure epistemic *discipline* on a contamination-free task, not a fact-recall benchmark.

Our central finding: principles do not make agents "smarter"—frontier models already exhibit epistemic humility in isolation—but make epistemic behavior *consistently disciplined*, closing the signal-extraction gap that vague heuristics leave open. Related work is discussed in Appendix A.

[1] **K**nowledge-**A**uditable **R**eputation for **M**ulti-**A**gent networks

2 KARMA Framework

2.1 Failure Mode Derivation

Open decentralized networks impose three structural constraints on evidence processing: *locality* (no global aggregation; only direct and one-hop evidence available), *observability* (agent internals hidden; only outcome quality visible), and *heterogeneity* (agent quality varies without prior knowledge or dense interaction history). Violating each produces a characteristic failure:

Violating observability → Ungrounded trust. Agents accept peer claims without correlating them against observed outcomes—a failure mode amplified by LLM sycophancy (Sharma et al., 2024). An adversary exploiting this mode provides consistently confident but unreliable information; without outcome verification, its claims carry equal weight to legitimate expertise. This motivates **P1: Outcome-Grounding**—direct observations must outweigh peer testimony in belief formation (Goldman, 1999).

Violating heterogeneity → Scope creep. Agents act on information outside their verified domain, either by fabricating specifics to fill knowledge gaps or by accepting out-of-scope peer claims without qualification. For example, without explicit scope constraints a model may fill a knowledge gap with a plausible projection it has no evidence for, whereas under scope discipline it marks the same gap as "pending confirmation." This motivates **P2: Evidence Scope**—only evidence within an agent's verified scope contributes to its decisions; gaps must be acknowledged, not filled (Goldman, 2001).

Violating locality → Credibility blindness. Agents weight all information sources equally regardless of track record, enabling adversaries—including sophisticated collusion strategies (Motwani et al., 2024)—to influence decisions at the same level as demonstrated experts. Global aggregation amplifies this: a single adversary's claims propagate network-wide without local verification. This motivates **P3: Source Credibility**—sources are weighted by their correlation with observed outcomes; unproven or mutually-promoting sources are discounted (Coady, 1992).

Whether this derivation pattern—structural constraints → characteristic failure modes → minimal preventing principles—yields useful specifications for epistemic task families beyond multi-source credibility assessment remains open; we do not evaluate it here.

2.2 Three Epistemic Principles

Formally, for an agent a maintaining beliefs B_a about peer capabilities:

P1 (Outcome-Grounding) Let o_{ab} be the observed outcome of delegating task t to agent b. Then $\Delta B_a(b) \propto f(o_{ab})$, where f maps outcomes to belief updates. Peer testimony T_{cb} (agent c's claim about b) contributes only as $\Delta B_a(b) \propto w_c \cdot g(T_{cb})$ (g the testimony analog of f), with $w_c < 1$ for all indirect evidence. Outcomes are time-indexed and f is recency-weighted: $B_a(b)$ estimates b's *current* capability, so where recent and older observations conflict, the recent ones dominate.

P2 (Evidence Scope) Agent a maintains a scope function $S_a(t) \in \{0, 1\}$ indicating whether it has evidence relevant to task t. If $S_a(t) = 0$, agent a must not generate assertions about t; it may only acknowledge the gap or delegate. Scope applies symmetrically to evidence *about* peers: a track record established on t constrains beliefs about t alone and does not transfer to $t' \neq t$.

P3 (Source Credibility) The weight w_c assigned to agent c's testimony is determined by $\mathrm{corr}(T_c, O)$—the historical correlation between c's claims and observed outcomes. Agents with no outcome history begin from a bounded prior weight ($w_c < 1$, never rivaling direct evidence) that outcome observations rapidly correct; agents whose claims track mutual promotion rather than outcomes receive $w_c \to 0$.

These three principles form a *coherent epistemic stance*, not an additive feature set. The recency clause of P1 and the peer-scope clause of P2 are realized explicitly in both substrates—as the temporal decay $\delta = \ln 2/h$ and per-capability tracking of §4.1, and as the corresponding

items of the injected text (Appendix G.2). Removing any single principle does not create a "weaker but functional" system—it re-opens the corresponding vulnerability class. The per-trap experimental analysis (§3.1) quantifies each principle's marginal contribution; the Bayesian implementation (§4.1) demonstrates that P2 and P3 produce non-obvious emergent properties beyond their surface definitions.

2.3 Specification vs. Implementation

The principles above are *epistemic constraints*—derived from three structural conditions on decentralized evidence processing (locality, observability, heterogeneity) via the failure modes in §2.1. They are analogous to institutional design principles for collective action (Ostrom, 1990): they define *what* epistemic discipline requires without prescribing *how* to achieve it. We demonstrate that the specification is implementation-agnostic: the same constraints can be realized by both an explicit Bayesian mechanism and approximate natural-language reasoning.

The specification admits multiple *realizations*: (A) a Bayesian mechanism using closed-form credibility updates (§4); (B) structured natural-language principles driving LLM reasoning (§3). An independently developed RL result—Zhou et al. (2026)'s 4B model, which converges on P1/P3-aligned behavior without access to our specification—can be read as a further realization, though we did not design or evaluate it.

We demonstrate cross-substrate realizability in §5: two mechanistically distinct realizations exhibit structurally aligned behavior, supporting that the specification is not tied to a single implementation. Whether this alignment reflects deeper necessity—whether any effective credibility processor under these constraints must approximate P1–P3—remains an open conjecture, discussed there alongside its falsification conditions.

3 LLM Implementation: Operationalizability and Boundaries

We evaluate whether KARMA's epistemic principles—derived from structural constraints in §2—can be operationalized by large language models. Our experiments address three questions: (1) Do principles improve trust judgment accuracy beyond the no-principle baseline? (2) Is the effect statistically robust? (3) What is the capability boundary?

3.1 Reputation Signal Extraction

We isolate the *signal extraction* component of KARMA: given conflicting claims from sources with known track records, can a model correctly identify the more credible source? We deliberately test the most information-constrained setting: single-shot credibility judgment from a fixed evidence snapshot, with no opportunity to gather additional observations. This maximizes discriminative power—trust estimation risk decreases monotonically with observation count (Jøsang & Ismail, 2002), so if principles enable correct judgment under minimal evidence, multi-turn settings (where agents accumulate observations over time) face a strictly easier information-extraction problem. Our own Bayesian simulation confirms this: KARMA converges within $\sim$50 interactions even at minimal density (§4).

Design. A pilot study (36 scenarios, 7 models, 6 conditions; Appendix F) established that (i) KARMA achieves best or tied-best accuracy for 6/7 models, (ii) most models operate near ceiling (91–100%), limiting statistical power, (iii) MiniMax M2.5 sits below a prompting-substrate floor where principles consume reasoning budget and turn net-harmful ($\Delta = -9.2$pp), and (iv) four frontier models from different labs achieve near-ceiling without principles, bounding KARMA's prompting value to the mid-tier regime. With P1–P3 fixed beforehand—and informed by the pilot only for model selection, difficulty calibration, and statistical powering, not for the epistemic content of the principles—we construct a *powered* adversarial stress test excluding the floor model and redundant near-ceiling models (retaining Sonnet 4.5 as an upper-bound reference): 150 multi-layer adversarial scenarios, each combining 2–4 independent epistemic failure modes into a single prompt. The component failure modes—authority bias (Mammen et al., 2026), verbosity/detail bias (Shi et al.,

2023), majority consensus bias (Zhu et al., 2024), and anchoring on stale base rates (Binz & Schulz, 2023)—are independently documented in LLMs; our contribution is their systematic *composition* into multi-layer attacks. Six composite trap types test increasingly aggressive attack surfaces:

- **Authority+Corroborative+Narrative**: cross-domain credentials + multi-source consensus + causal explanation (tests P2, P3);
- **Base-rate+Detail+Temporal**: strong historical base rate + detail bombardment + recency conflict (tests P1, P3);
- **Scope+Authority+Detail**: global/local reputation divergence + credential halo + numeric padding (tests P2, P3);
- **Corroborative+Recency+Narrative**: 4-person historical consensus against 1 source with perfect recent record (tests P1, P3);
- **4-layer composite**: authority + detail + narrative + corroboration simultaneously;
- **Numeric Precision**: small-n narrow CI vs. large-n wide CI (tests statistical reasoning).

All entities are fictional and generated deterministically from a fixed seed, ensuring contamination-free evaluation and perfect reproducibility. Each scenario has structurally-determined ground truth: topic-specific accuracy numerically resolves which source is correct, enabling fully automated exact-match scoring with zero judge contamination.

Setup. Four models span the capability spectrum: Sonnet 4.5 (frontier), Haiku 4.5 (mid-tier), DeepSeek V3.2 (strong open-weight), and Llama 3.3 70B (mid-tier open-weight). Two conditions isolate the specification's contribution: **KARMA** (P1–P3 with sub-rules) and **NP** (No Principles: track records provided, no guidance on use; prompts in Appendix G.2). All evaluations use direct API calls without orchestration frameworks or system prompts—a methodological requirement, not a limitation: agent frameworks embed implicit trust heuristics (role assignment, verification steps, routing rules) that would confound attribution of observed effects to the specification itself. Table 2 reports accuracy over N=10 runs $\times$ 150 scenarios (36,000 total judgments across six conditions).

Statistical interpretation. The paired design (same 150 scenarios, same N=10 draws) gives high statistical power (pairing removes between-scenario variance); robustness to within-template clustering across the six composite templates is confirmed in Appendix F.2. Effect sizes are medium-to-large by conventional benchmarks: $d = 0.49$ (Haiku) falls at the upper end of *medium* (0.2–0.5), while $d = 1.00$ (Llama) and $d = 1.24$ (DeepSeek) exceed the *large* threshold (> 0.8) substantially. For context, meta-analyses of instructional interventions in education rarely exceed $d = 0.5$; effects above $d = 1.0$ indicate qualitative regime shifts—here, from near-chance to near-ceiling. The $p < 10^{-9}$ values are not driven by sample size inflation: even with just 50 scenarios (power simulation), the effects would remain significant at $p < 0.001$.

Key findings. **(i)** KARMA produces large, highly significant improvements for all non-frontier models: +18.4 to +48.4pp (Cohen's $d = 0.49$–1.24). Without principles, mid-tier models perform near chance on multi-layer adversarial compositions (Llama 49.7%, DeepSeek 53.7%)—they are *systematically misled* by surface features. With KARMA, the same models approach frontier performance (98.1–98.6%). **(ii)** The frontier model (Sonnet 4.5) achieves 100% under *both* conditions—the specification adds nothing when intrinsic capability suffices. This confirms the capability-dependent pattern: KARMA scaffolds epistemic discipline that sufficiently capable models already exhibit.

(iii) *Baselines on the extreme benchmark.* We evaluate four alternative prompting strategies on the same benchmark (Table 2). B1 (Generic Caution: "be skeptical") and B2 (Chain-of-Verification: verify claims step by step) perform comparably to NP for all models. B3 (Reputation Heuristic: "trust sources with better track records") is the strongest competitor—its mean accuracy across all four models including the frontier (79.5%) substantially exceeds NP (68.8%)—but on specific traps it collapses *below* NP (Table 1). B4 (Role Authority: "trust

Table 1: Per-trap accuracy (%) for the four most informative compositions. Bold = condition-best per cell. B3/B4 collapse on traps contradicting their heuristic (underlined cells fall below NP); KARMA's lowest cell is 44.0% (Haiku, Corr+Rec+Narr) versus 0–4% for the collapsing baselines. Full 6-trap breakdown in Appendix G.4.

Trap	Model	KARMA	NP	B3	B4
Corr+Rec +Narr	Haiku	**44.0**	0.8	4.0	1.6
	DeepSeek	**94.4**	14.4	4.0	20.0
	Llama	**88.8**	6.4	0.0	4.8
Base+Det +Temp	Haiku	**100.0**	100.0	100.0	100.0
	DeepSeek	**98.8**	33.6	61.6	3.6
	Llama	**100.0**	1.6	32.8	0.0
Numeric Precision	Haiku	**100.0**	96.0	96.0	95.6
	DeepSeek	99.2	**98.8**	100.0	54.8
	Llama	100.0	100.0	100.0	100.0
Auth+Det +Narr+Corr	Haiku	**100.0**	64.8	95.2	85.2
	DeepSeek	**99.6**	45.2	76.4	74.8
	Llama	**100.0**	24.4	76.4	96.0

Underlined: baseline falls below NP on this trap (heuristic is actively harmful).

the domain specialist") shows mixed results overall but catastrophically fails on Numeric Precision (−14.8pp pooled vs. NP) and Base+Det+Temp (−10.5pp pooled). Paired t-tests confirm KARMA's superiority over all baselines for all non-frontier models ($p < 10^{-4}$ after Bonferroni correction, $d = 0.32$–1.37); Wilcoxon signed-rank tests yield identical conclusions.

(iv) *Per-trap vulnerability structure* (Table 1). The baselines' failures are structurally informative—each collapses on the trap type that directly contradicts its heuristic:

Table 2: Calibration Extreme: accuracy (%) on 150-scenario benchmark (N=10 runs per condition). KARMA significantly outperforms all baselines and NP for non-frontier models. Inferential statistics: paired t-test over 150 per-scenario means.

Model	KARMA	NP	B1	B2	B3	B4	$\Delta_{\text{K-NP}}$	$t(149)$	d
Sonnet 4.5	**100.0**	100.0	99.9	99.3	100.0	95.1	0.0	—	—
Haiku 4.5	**90.1**	71.7	78.7	75.8	81.9	78.7	$+18.4^{***}$	6.01	0.49
DeepSeek V3.2	**98.6**	53.7	53.3	56.2	69.5	53.2	$+44.9^{***}$	15.13	1.24
Llama 3.3	**98.1**	49.7	49.7	45.3	66.9	66.8	$+48.4^{***}$	12.29	1.00

$^{***}p < 10^{-9}$. KARMA vs. all baselines: $p < 10^{-4}$ (Bonferroni), $d = 0.32$–1.37.
B1=Generic Caution; B2=Chain-of-Verification; B3=Reputation Heuristic; B4=Role Authority.

- B3 ("trust reputation") falls *below* NP on Corr+Rec+Narr (DeepSeek 4% vs. NP 14%; Llama 0% vs. NP 6%)—the heuristic makes a positive claim ("historical reliability predicts current reliability") that recency-conflict scenarios directly contradict.
- B4 ("trust the specialist") collapses on Base+Det+Temp (Llama/DeepSeek: 0–4% vs. NP 2–34%) and Numeric Precision (DeepSeek: 55% vs. NP 99%)—authority framing suppresses independent statistical reasoning.
- Both B3 and B4 *approach* KARMA on Auth+Corr+Narr (pooled gap <7pp)—where their heuristics happen to align with the correct answer.

KARMA is the only condition whose overall accuracy exceeds 90% for every non-frontier model (Table 2), and the only one that avoids sub-5% collapse on any trap type—its lowest per-trap cell is 44.0% (Haiku, Corr+Rec+Narr), compared to 0–4% for the collapsing baselines on the same trap. The gains are also not confined to the traps the injected text names: on Auth+Det+Narr+Corr—a four-layer composite whose components (authority framing, spurious detail, narrative coherence, fabricated corroboration) no injection item

addresses—KARMA exceeds NP by +35.2pp (Haiku), +54.4pp (DeepSeek) and +75.6pp (Llama; Appendix G.4).

(v) *Diagnostic validity.* The benchmark measures epistemic discipline rather than general difficulty: (a) no difficulty gradient (Sonnet 4.5 at 100% on all traps; Llama at 1.6% on Base+Det+Temp—binary separation, not graded degradation); (b) per-scenario bimodality (10/10 or 0/10, indicating heuristic capture is all-or-nothing); (c) Numeric Precision ≥96% under NP for all models (mid-tier models are not generally incapable); (d) model-specific vulnerability profiles sharing no common difficulty ordering. This establishes construct validity—separating presence/absence of epistemic discipline from levels of capability—but does not address ecological validity (Limitation 5) and does not uniquely determine the construct.

4 Bayesian Implementation: Convergence and Scaling

Having shown that KARMA principles enable correct reputation signal extraction across diverse LLMs (§3), we now study a mechanistically distinct implementation: a Bayesian mechanism realizing the same specification, whose convergence and scaling we characterize over a large simulation sweep.

4.1 Mechanism Design

The mathematical implementation realizes P1–P3 through interconnected modules over continuous-valued belief states. For commissioner a evaluating peer b on capability k at time t:

Outcome-grounding (P1). Agent a's trust combines its own *direct* outcomes with credibility-discounted peer testimony:

$$\text{trust}_{a,b,k} = \lambda\, \bar{o}^{\text{local}}_{a,b,k} + (1-\lambda)\, s_{b,k}, \qquad \lambda = \frac{n}{n+n_0}, \tag{1}$$

where $\bar{o}^{\text{local}}_{a,b,k}$ is the mean of a's first-hand outcomes with b over n observations, so direct evidence dominates as $\lambda \to 1$; peer testimony enters only through the discounted aggregate

$$s_{b,k} = \frac{\sum_i w_i\, r_i}{\sum_i w_i}, \qquad w_i = e^{-\delta(t-t_i)}\, c_{j_i,b}, \tag{2}$$

each rating r_i weighted by its rater's credibility $c_{j_i,b} < 1$ (below) and recency ($\delta = \ln 2/h$). This is exactly P1's $\Delta B_a(b) \propto f(o)$ with testimony contributing only as $w_c\, g(T)$, $w_c < 1$.

Evidence scope (P2). Scope is enforced structurally: *per-capability* tracking confines evidence about k to beliefs about k (no cross-capability halo), and an untracked pair defaults to a neutral 0.5 rather than an asserted estimate—the mechanism analog of "acknowledge the gap, do not fill it." Within scope, an *endogenous* variance term discounts estimates whose observed dispersion exceeds what outcomes warrant (Adams & MacKay, 2007):

$$v_{\text{obs}} = \frac{\sum_i w_i (r_i - s_{b,k})^2}{\sum_i w_i}, \qquad \rho = \min\Big(1,\ \tfrac{1}{\theta}\max\big(0,\ \tfrac{v_{\text{obs}}}{v_{\text{exp}}} - 1\big)\Big), \tag{3}$$
$$s_{b,k} \leftarrow s_{b,k}\,(1-\rho),$$

with $v_{\text{exp}} = v^{\text{out}}_{b,k} + v^{\text{noise}}$ tracked online ($v^{\text{out}}_{b,k}$ the variance of b's recent outcomes, $v^{\text{noise}} = \mathbb{E}[|r-o|^2]$ the rating noise; each floored at 0.005) and tolerance θ. Adapting v_{exp} to outcomes flags behavioral *inconsistency*, not sample size.

Source credibility (P3). Each rater's credibility is a Beta posterior over its reliability, updated by the disagreement $d = |r-o| \in [0,1]$ between its rating and the realized outcome:

$$\alpha_{j,b} \leftarrow \alpha_{j,b} + (1-d), \qquad \beta_{j,b} \leftarrow \beta_{j,b} + d, \tag{4}$$
$$c_{j,b} = \mathbb{E}\big[\text{Beta}(\alpha_{j,b}, \beta_{j,b})\big] = \frac{\alpha_{j,b}}{\alpha_{j,b} + \beta_{j,b}}.$$




Figure 1: **Left:** Density-invariance—KARMA maintains constant ∼1.6% adversary routing regardless of interaction density (K), while BRS degrades 2.6×. **Right:** Adversary defense—burst attacks (shaded region) trigger credibility overshoot to −0.19 as behavioral inconsistency spikes the adaptive variance penalty, enabling faster recovery than mean-based systems. Full (N, K) sweep panel in Figure 3 and per-attack breakdowns in Figures 4 and 5.

The Beta$(4, 1)$ prior is mildly trusting (mean 0.8): credibility controls the relative weighting among raters, while λ controls testimony's aggregate influence relative to accumulated direct evidence. It is also *outcome-corrected*: divergence accrues β-mass, driving unreliable or mutually-promoting raters—whose ratings track promotion rather than outcomes—toward $c \to 0$. A per-pair posterior backs off to the global one when pairwise evidence is sparse.

4.2 Key Property: Adaptive Variance as Confidence Signal

The adaptive-variance term (P2) is the primary novelty over standard Bayesian reputation systems: BRS (Jøsang & Ismail, 2002) fixes variance as a function of observation count ($\alpha\beta/((\alpha+\beta)^2(\alpha+\beta+1))$) and recent Bayesian trust models (Hallyburton & Pajic, 2024) keep similar fixed-variance assumptions, whereas KARMA's is *endogenous*—reflecting outcome consistency, not sample size, so an oscillating or intermittently-manipulative agent is penalized despite an acceptable mean.

4.3 Simulation Results

We evaluate over 7,000 simulation runs with parameter sweeps across network density ($K \in \{1, 2, 5, 10\}$), adversary strategies (sustained, burst, sybil coalition), and network sizes ($N \in \{10, 20, 50, 100\}$). Full parameter tables (Table 3), convergence curves (Figure 2), and per-attack-type visualizations (Figures 3–5) are in Appendix B; we summarize the key properties here.

Density-invariance. KARMA maintains constant ∼1.6% adversary routing regardless of interaction density, while BRS vulnerability increases 2.6× as density grows from K=1 to K=10 (Figure 1, with the full (N, K) sweep in Figure 3). The mechanism: denser interaction means more adversary ratings reach the network; KARMA's variance penalty and credibility filtering neutralize this, while BRS's simple counting accumulates poisoned evidence. The invariance is specific to sybil coalitions: under majority-scale collusion every system degrades with density, KARMA included (Figure 5).

Sparse-environment convergence. At K=1 (cooldown = N: each agent serves ∼1 task per N steps), seven of the eight baselines never converge within 10,000 steps at N=20, plateauing at 3.7–4.6% adversary routing; only EigenTrust clears it (0.46%). KARMA reaches zero at every density within 500 steps—50 interactions per agent at N=10—via variance-based early warning (Figure 2). This demonstrates the framework's value in evidence-scarce settings—the realistic condition for heterogeneous agent networks.

Adversary defense. Sustained attack is bounded at +0.05 credibility gain. Burst attacks (reputation followed by exploitation) trigger overshoot recovery to −0.19—the variance spike from behavioral inconsistency provides faster detection than mean-based systems.

Compositional resilience. In the Bayesian substrate, removing the variance penalty reverses sybil defense (inflation $-0.06 \to +0.10$); removing credibility decay lets collusion

persist indefinitely, though decay in turn sharpens benign-drift overshoot—a sensitivity–safety tradeoff, tunable via the variance tolerance θ (Table 4, Figures 7 and 6). Per-capability tracking's contribution instead surfaces on the LLM substrate, where the no-principle baseline collapses on cross-domain (halo) traps (67% vs. 100%; Table 9).

5 Discussion and Conclusion

Substrate independence and convergence. The specification is implementation-agnostic: an explicit Bayesian mechanism (§4) and a stateless natural-language reasoner (§3) share no architecture, training data, or computational substrate, yet produce structurally aligned behavior. We do not claim independent convergence—both were constructed by the same authors—but demonstrate *realizability*: the specification is not bound to any single mechanism. Four directional correspondences confirm this is non-trivial (quantitative details in Appendix F.4): both select the higher track-record source; both suppress unreliable sources through credibility-weighted acceptance; in both, reputation *without* credibility-weighting collapses on recency-conflict traps; both require minimum resources before engaging. The recency and peer-scope clauses of §2.2 carry over too, realized in the Bayesian mechanism and evaluated there on adversary routing and convergence speed—metrics and data disjoint from the 150-scenario benchmark, so neither is an artifact of its construction. Beyond our own implementations, Zhou et al. (2026)'s independently developed RL system—different authors, different methodology, no access to P1–P3—converges on track-record-weighted peer assessment via gradient optimization, aligning with P1 and P3; and frontier LLMs achieve KARMA-consistent judgments without explicit principles (Sonnet 4.5: 100% under NP). We conjecture that KARMA describes a rational limit capable systems approach along different paths; the principles' value is *accelerated convergence* for models not yet at the limit. This claim would be falsified if a substrate implementing P1–P3 produced structurally divergent outcomes, or if an alternative specification produced equivalent convergence; both conditions remain open.

Implications. KARMA instantiates a specific pattern: normative principles from human epistemology—philosophical accounts of how rational agents *should* evaluate evidence (Goldman, 1999; Coady, 1992)—serving directly as behavioral constraints for AI systems. Whether this philosophy-to-specification path extends beyond multi-source credibility assessment is an open question; we note it as a potentially productive direction rather than a validated methodology. Within this task family, the practical implication is immediate: widely-deployed open-weight models (Llama 3.3, DeepSeek V3.2) can be strengthened from near-chance to near-frontier performance through specification injection alone, with no fine-tuning or architectural modification. Moreover, the Bayesian mechanism (§4) can be deployed directly as a deterministic agent tool, operationalizing the specification independently of the prompting substrate.

Limitations. (1) *Routing gap*—the LLM evaluation tests credibility *judgment* (signal extraction); the Bayesian simulation tests both judgment and dynamic *routing* (§4). Whether LLM agents translate correct judgments into correct delegation in stateless deployments—without architectural support—remains untested. (2) *Prompting-substrate floor*—capacity-constrained models turn net-negative as principles consume reasoning budget; this bounds the prompting realization, not the specification. (3) *Identity*—credibility attaches to behavioral track records, not persistent identity; binding reputation to verifiable identity remains open. (4) *Scenario complexity*—deterministic generation and structurally-determined ground truth enable 36,000 contamination-free automated evaluations but limit scenarios to those with unambiguous numerical resolution; we argue diagnostic validity in §3.1 (finding v). (5) *Ecological validity*—bare-model evaluation isolates the specification's causal contribution from orchestration-harness confounds, but whether the gains persist within real frameworks is open; harness-integrated evaluation is valuable follow-up. (6) *Task-family scope*—whether specification injection improves epistemic behavior on task families beyond multi-source credibility judgment is untested. (7) *Uneven cross-substrate alignment*—the §5 correspondence is tightest for P1 and P3 and loosest for P2 (refusal-to-assert in the LLM vs. an endogenous variance penalty in the Bayesian mechanism), so P2 carries less cross-substrate evidence.

References

Ryan P. Adams and David J.C. MacKay. Bayesian online changepoint detection. *arXiv preprint arXiv:0710.3742*, 2007.

George A. Akerlof. The market for "lemons": Quality uncertainty and the market mechanism. *Quarterly Journal of Economics*, 84(3):488–500, 1970.

Marcel Binz and Eric Schulz. Using cognitive psychology to understand GPT-3. *Proceedings of the National Academy of Sciences*, 120(6):e2218523120, 2023.

Mert Cemri, Melissa Z. Pan, Shuyi Yang, Lakshya A. Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, Matei Zaharia, Joseph E. Gonzalez, and Ion Stoica. Why do multi-agent LLM systems fail? *arXiv preprint arXiv:2503.13657*, 2025.

Mohd Sameen Chishti, Damilare Peter Oyinloye, and Jingyue Li. AgentReputation: A decentralized agentic AI reputation framework. *arXiv preprint arXiv:2605.00073*, 2026.

C.A.J. Coady. *Testimony: A Philosophical Study*. Oxford University Press, 1992.

Shehzaad Dhuliawala, Mojtaba Komeili, Jing Xu, Roberta Raileanu, Xian Li, Asli Celikyilmaz, and Jason Weston. Chain-of-verification reduces hallucination in large language models. *arXiv preprint arXiv:2309.11495*, 2023.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv:2305.14325*, 2023.

Mohammadreza Ebrahimi et al. An adversary-resistant multi-agent LLM system via credibility scoring. In *Proceedings of the 14th International Joint Conference on Natural Language Processing and the 4th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics (IJCNLP-AACL)*, pp. 1676–1693, Mumbai, India, 2025.

Alvin I. Goldman. *Knowledge in a Social World*. Oxford University Press, 1999.

Alvin I. Goldman. Experts: Which ones should you trust? *Philosophy and Phenomenological Research*, 63(1):85–110, 2001.

R. Spencer Hallyburton and Miroslav Pajic. Bayesian methods for trust in collaborative multi-agent autonomy. *arXiv preprint arXiv:2403.16956*, 2024.

Pengfei He, Zhenwei Dai, Xianfeng Tang, Yue Xing, Hui Liu, Jingying Zeng, Qiankun Peng, Shrivats Agrawal, Samarth Varshney, Suhang Wang, Jiliang Tang, and Qi He. To trust or not to trust: Attention-based trust management for LLM multi-agent systems. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2026.

Sirui Hong et al. Metagpt: Meta programming for a multi-agent collaborative framework. *arXiv preprint arXiv:2308.00352*, 2023.

Botao Amber Hu and Helena Rong. Inter-agent trust models: A comparative study of brief, claim, proof, stake, reputation and constraint in agentic web protocol design. *arXiv preprint arXiv:2511.03434*, 2025. AAAI 2026 Workshop on Trust and Control in Agentic AI.

Audun Jøsang and Roslan Ismail. The beta reputation system. In *Proceedings of the 15th Bled Electronic Commerce Conference*, pp. 41–55, 2002.

Sepandar D. Kamvar, Mario T. Schlosser, and Hector Garcia-Molina. The EigenTrust algorithm for reputation management in P2P networks. In *Proceedings of the 12th International Conference on World Wide Web*, pp. 640–651, 2003. doi: 10.1145/775152.775242.

Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. CAMEL: Communicative agents for "mind" exploration of large language model society. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Zhuo Li, Yupeng Zhang, Pengyu Cheng, Jiajun Song, Mengyu Zhou, Hao Li, Shujie Hu, Yu Qin, Erchao Zhao, and Xiaoxi Jiang. MARCH: Multi-agent reinforced self-check for LLM hallucination. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2026.

Xuannan Liu, Xiao Yang, Zekun Li, Pei Pei Li, and Ran He. AgentHallu: Benchmarking automated hallucination attribution of LLM-based agents. *arXiv preprint arXiv:2601.06818*, 2026.

Priyanka Mary Mammen, Emil Joswin, and Shankar Venkitachalam. Who endorsed it? measuring authority bias across expertise levels in language models. *arXiv preprint arXiv:2601.13433*, 2026.

Sumeet Ramesh Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip H. S. Torr, Lewis Hammond, and Christian Schroeder de Witt. Secret collusion among AI agents: Multi-agent deception via steganography. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Samuel Müller, Noah Hollmann, Sebastian P Arango, Josif Grabocka, and Frank Hutter. Transformers can do bayesian inference. In *International Conference on Learning Representations*, 2022.

Elinor Ostrom. *Governing the Commons: The Evolution of Institutions for Collective Action*. Cambridge University Press, 1990.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST)*, 2023.

Siyue Ren, Wanli Fu, Xinkun Zou, Chen Shen, Yi Cai, Chen Chu, Zhen Wang, and Shuyue Hu. Reputation as a solution to cooperation collapse in LLM-based MASs. *arXiv preprint arXiv:2505.05029*, 2025.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rauber, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. Towards understanding sycophancy in language models. *arXiv preprint arXiv:2310.13548*, 2024. ICLR 2024.

Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed Chi, Nathanael Schärli, and Denny Zhou. Large language models can be easily distracted by irrelevant context. *Proceedings of the 40th International Conference on Machine Learning (ICML)*, 2023.

Michael Spence. Job market signaling. *Quarterly Journal of Economics*, 87(3):355–374, 1973.

W T Luke Teacy, Jigar Patel, Nicholas R Jennings, and Michael Luck. TRAVOS: Trust and reputation in the context of inaccurate information sources. *Autonomous Agents and Multi-Agent Systems*, 12:183–198, 2006.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, et al. AutoGen: Enabling next-gen LLM applications via multi-agent conversation. *arXiv preprint arXiv:2308.08155*, 2023.

Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. An explanation of in-context learning as implicit bayesian inference. In *International Conference on Learning Representations*, 2022.

Ruiwen Zhou, Maojia Song, Xiaobao Wu, Sitao Cheng, Xunjian Yin, Yuxi Xie, Zhuoqun Hao, Wenyue Hua, Liangming Pan, Soujanya Poria, and Min-Yen Kan. Epistemic context learning: Building trust the right way in LLM-based multi-agent systems. *arXiv preprint arXiv:2601.21742*, 2026.

Xiaochen Zhu, Caiqi Zhang, Tom Stafford, Nigel Collier, and Andreas Vlachos. Conformity in large language models. *arXiv preprint arXiv:2410.12428*, 2024.

Reproducibility Statement

LLM experiments. *Calibration* (§3.1) uses four models in the extreme benchmark (Sonnet 4.5, Haiku 4.5, DeepSeek V3.2, Llama 3.3 70B) and seven in the pilot (adding Opus 4, gpt-oss-120b, and MiniMax M2.5; Appendix F). The complete three-sentence principle injection and fictional vocabulary design are documented in Appendix G. Full private context documents (6 domain contexts, 540–650 words each) and all experimental scripts are released in the supplementary code repository upon publication. Simulation code implementing all six mathematical modules with exact hyperparameters (Table 3) will be released upon publication. Calibration uses N=10 replicated runs per model–condition cell (identical prompts; run-to-run variation from natural decoding stochasticity), issued as direct Amazon Bedrock API calls without an orchestration framework or system prompts. Calls use Amazon Bedrock's default sampling parameters (no explicit temperature, top-p, or top-k override); the only decoding parameter we set is `maxTokens`=400 (raised to 4000 for the reasoning model gpt-oss-120b to fit its reasoning trace).

Simulation. All experiments use deterministic seeds (reported per figure). Hyperparameters in Table 3 are the only free parameters; all others derive from the framework specification. The adaptive variance mechanism (§4) has no fixed variance baseline: the reference v_{exp} against which observed dispersion is judged is tracked online from outcomes rather than set a priori, so the tolerance θ (Table 3) scales that moving reference instead of imposing an absolute cutoff. Figure 6 reports sensitivity to θ: collusion defense holds for $\theta \leq 5$ and inverts by θ=7, while sybil routing degrades gradually with no sharp transition.

AI Use Statement

Required disclosures. In this work, we used generative AI tools for the following tasks requiring disclosure: **Generate synthetic data**—LLMs (seven model families) serve as experimental subjects whose outputs constitute the primary experimental data; **Implement methods**—LLM coding assistants were used to accelerate implementation of experimental harnesses, data processing scripts, and simulation code; all generated code was reviewed and tested by the authors. The conceptual framework and epistemic principles, the mathematical derivations in §4, the experimental design, and all final scientific claims are the authors' own. AI tools additionally assisted with analysis and review of results under author direction; the authors verified every such output and take full responsibility for all interpretations.

Recommended disclosures. We additionally used generative AI tools for: editing and improving readability of manuscript drafts, suggesting code refactors, and formatting references. We have reviewed all AI-assisted work. Specifically: (1) all LLM-generated experimental code was verified via unit tests and manual inspection by at least one author; (2) manuscript text produced with AI assistance was reviewed for accuracy against our experimental results and theoretical derivations; (3) AI assistance was applied to drafting, code, and analysis/review of results under author direction; the epistemic principles, experimental design, and all final scientific claims and interpretations are the authors' own, and the authors reviewed and take responsibility for every AI-assisted output.

We take full responsibility for the final content of this work, including all text, claims, code, and artifacts.

A Related Work

Trust and reputation in multi-agent systems. BRS (Jøsang & Ismail, 2002), EigenTrust (Kamvar et al., 2003), and TRAVOS (Teacy et al., 2006) provide Bayesian and eigenvector-based reputation for e-commerce and P2P networks but assume centralized aggregation, static adversaries, and dense interaction histories—conditions absent in heterogeneous LLM agent networks where interactions are sparse and agents reason in natural language. Inter-agent trust taxonomies (Hu & Rong, 2025) formalize these gaps but do not provide mechanisms. KARMA bridges this gap by deriving principles that are both Bayesian-grounded (Bayesian implementation, §4) and directly operationalizable by LLMs (§3).

Trust management in LLM multi-agent systems. He et al. (2026) propose attention-based trust scoring as external middleware; Ebrahimi et al. (2025) maintain centralized credibility scores updated via Shapley-value contribution attribution. Both assume a trusted monitor with full communication visibility—incompatible with the locality constraint (§2.1) motivating KARMA. KARMA equips agents themselves with epistemic principles governing their own credibility reasoning: *autonomous trust judgment* rather than external enforcement. Most closely, Zhou et al. (2026) (ECL) train agents by reinforcement learning to estimate peer reliability from interaction history. KARMA differs in kind: our principles are a training-free, constraint-derived *specification* validated across two substrates (LLM reasoning and a Bayesian mechanism), not a learned pipeline; the convergence between ECL's learned behavior and our specification is analyzed in §5. Their finding that frontier models (Gemini 3 Pro, GPT-5.2, disjoint from ours) benefit least independently corroborates our capability-dependent observation on Opus 4 and gpt-oss-120b. Chishti et al. (2026)'s decentralized reputation cards similarly prevent cross-domain conflation (cf. our P2) but as external infrastructure (verification regimes, economic enforcement) rather than agent-internal principles.

Implicit Bayesian inference in Transformers. Xie et al. (2022) show that in-context learning in Transformers is equivalent to implicit Bayesian inference over latent concepts. Müller et al. (2022) demonstrate that Transformers can perform near-optimal posterior prediction. Our finding that Opus 4 reaches KARMA-consistent trust judgments without explicit principles—and articulates reasoning that subsumes all KARMA modules—provides domain-specific evidence for this implicit Bayesian capacity in the trust-reasoning domain. KARMA principles can be understood as making this implicit structure *explicit and accessible* to models whose capacity is insufficient to activate it spontaneously.

LLM multi-agent coordination. AutoGen (Wu et al., 2023), CAMEL (Li et al., 2023), and MetaGPT (Hong et al., 2023) provide orchestration but do not address inter-agent information reliability. Multi-agent debate (Du et al., 2023) improves factuality through peer disagreement but requires synchronous rounds and does not defend against adversarial participants. RepuNet (Ren et al., 2025) adds reputation to LLM routing but relies on gossip propagation—a vulnerability KARMA's P2 (Evidence Scope) explicitly guards against—and uses prosocial prompts whose structural similarity to our B3 baseline suggests the same limitation: reputation without temporal discounting collapses on recency-conflict traps (B3 falls below NP by −10pp on such traps in our powered evaluation). KARMA operates at the epistemic level, complementary to orchestration frameworks.

LLM calibration and hallucination. Chain-of-Verification (Dhuliawala et al., 2023) reduces hallucination through self-verification but requires access to ground truth in parametric memory—ineffective for novel/private information. Our B2 baseline implements CoVe-style verification and performs comparably to the no-principle baseline on the powered benchmark (mean 69.1% vs. NP 68.8%), confirming that post-hoc verification provides no benefit when truth exists only in peer testimony. KARMA addresses this by constraining *generation-time* evidence evaluation rather than post-hoc correction. Recent agent-reliability work targets adjacent but distinct problems: AgentHallu (Liu et al., 2026) localizes which step of a multi-step trajectory hallucinates (attribution, not peer-credibility assessment), and MARCH (Li et al., 2026) reduces RAG hallucination via a reinforcement-trained Solver–Proposer–Checker pipeline that verifies claims against *retrieved evidence*. KARMA differs on both axes: it is training-free and operates where ground truth exists only in peer testimony, with no retrieval corpus to check against.

B Simulation Parameter Sweeps

All simulation experiments use the following default parameters unless stated otherwise:

Parameter	**Default**	**Sweep Range**
Network size (N)	20	{10, 20, 50, 100}
Interaction density (K)	5	{1, 2, 5, 10}
Adversary fraction	20%	{10%, 20%, 30%}
Steps per run	$100N$–$250N$	{500, 1000, 5000, 10000}
Seeds per configuration	10×3	–
Local-evidence prior weight (n_0)	5.0	fixed
Testimony half-life (h; $\delta = \ln 2/h$)	$100N$ steps	fixed
Variance tolerance (θ)	3.0	{1, 2, 3, 5, 7, 10, 15, 20}
Variance floors (v^{out}, v^{noise})	0.005	fixed
Variance-tracking EMA rate	0.01	fixed
Credibility prior (Beta(α, β))	$(4, 1)$	fixed

Table 3: Simulation parameters. Total runs: 7,000+ across all configurations.

Convergence criterion: Routing is aggregated into 500-step windows; a system is considered converged at the first window whose mean adversary routing falls below threshold—5% under sybil attack, and the colluders' fair share plus 5% (35% at a 30% coalition) under collusion. A run that never clears the threshold is recorded at the full 10,000 steps.

Adversary strategies tested:

- **Sustained**: Constant low-quality service ($\theta = 0.3$)
- **Burst**: High-quality for 500 steps, then exploit ($\theta : 0.9 \to 0.2$)
- **Sybil coalition**: 3 adversaries mutually promoting ($\theta = 0.3$, mutual ratings $= 0.95$)
- **Adaptive**: Adjusts θ based on observed routing share

B.1 Convergence and Parameter Sensitivity

Figure 2 reports convergence under sybil attack at increasing interaction density, and Figure 3 the full adversary-routing sweep over all (N, K) combinations.




Figure 2: Attacker routing over time under sybil attack at four interaction densities, for nine reputation systems (N=20 base agents plus 40 sybils, mean of 10 seeds, 500-step windows). KARMA's initial exposure is nearly density-independent (5.3% at K=1 rising only to 6.8% at K=10) and it reaches 0% at every density, whereas every baseline's initial exposure scales with density (BRS 5.2%→22.3%, EigenTrust 5.4%→50.7%). The evidence-scarce regime is the hard one: at K=1 seven of the eight baselines plateau and never fall below 3.7–4.6% over the full 10,000 steps, with only EigenTrust clearing it (0.46%). Denser interaction rescues most of them—at K=10 BRS, BRS-Cont, FIRE and RGT all end below 4.2% despite starting three to five times higher—leaving TRAVOS (17.0%), SubjLogic (12.2%) and IGR (8.7%) as the stragglers.




Figure 3: Sybil vulnerability versus interaction density for nine reputation systems over all (N, K) combinations, $N \in \{10, 20, 50\}$ and $K \in \{1, 2, 5, 10\}$ (mean attacker routing share over the first 2,000 steps, 10 seeds). KARMA is flat—0.86×–0.99× from K=1 to K=10, staying within 1.5–2.1% at every (N, K)—while every baseline degrades with density, from 2.6× (BRS, N=20) to 14.4× (EigenTrust, N=20). At N=10, K=10 the baselines span 40.1% (BRS) to 73.1% (EigenTrust) against KARMA's 1.8%. This is the nine-system generalization of Figure 1 (left).

B.2 Adversary Defense Detailed

Figure 4 details KARMA's response to sybil coalitions of increasing size.




Figure 4: Sybil resistance versus coalition size: attacker routing share as the sybil coalition grows from 2 to 40 nodes (added on top of the N base agents), for ten reputation systems at N=10, 20, 50 (the axis label K denotes sybil count here, not interaction density). KARMA is the lowest curve at every coalition size and network size, peaking at 4.4% (N=10), 1.4% (N=20), and 0.5% (N=50); at N=10 the nine baselines peak between 27.1% (BRS) and 45.4% (EigenTrust). Absolute shares fall with N because a fixed-size coalition commands a smaller fraction of a larger network.

B.3 Density and Threshold Analysis

Figure 5 isolates the density–collusion interaction, and Figure 6 reports sensitivity to the variance-penalty tolerance.




Figure 5: Colluder routing share versus interaction density under a 30% colluding coalition, for five systems at N=10, 20, 50 (mean over the first 2,000 steps, 10 seeds). At K=1 every system sits near the colluders' 30% fair share (31.5–33.4%). All systems then degrade as density rises—KARMA by 1.6×–2.2× from K=1 to K=10, BRS by 2.3×–2.6×—so the density-invariance that holds against sybil coalitions (Figure 1) does *not* extend to majority-scale collusion. KARMA remains the lowest curve at every density and network size (52.9% vs. 75.5% for BRS at N=10, K=10).




Figure 6: Sensitivity to the variance-penalty tolerance (τ in the axis labels; the tolerance θ of §4.1), swept over $\{1, 2, 3, 5, 7, 10, 15, 20\}$ at N=10, 20, 50 with 10 seeds. **(a)** Honest-baseline-adjusted collusion inflation is negative—colluders scored below honest agents—for $\tau \leq 5$, changes sign between τ=5 and τ=7, and reaches +0.070 to +0.106 at τ=20. **(b)** Sybil routing share grows with τ, from 9.5% to 16.6% at N=10 and 1.3% to 3.0% at N=20. Both defenses degrade monotonically as the tolerance loosens; the default τ=3 lies inside the shaded band where both hold.

B.4 Module Decomposition (Ablation)

Figure 7 reports the per-module ablation and Table 4 quantifies the effect of removing each module on key adversarial metrics.

Table 4: Module ablation: removing individual KARMA components. Sybil inflation = mean attacker reputation gain at 10+ sybils (negative = attacker suppressed); drift error = tracking error after behavioral shift ($\theta : 0.8 \to 0.4$). Removing the variance penalty (P2) is the only ablation that reverses sybil defense; it also degrades drift tracking 4.4×.

Config	Principle	Sybil inflation	Drift error	Convergence MAE
Full KARMA	P1+P2+P3	−0.06	0.054	0.106
No variance	−P2	+0.10 ↑	0.239 (4.4×)	0.099
No decay	−P1 (recency)	−0.07	0.022	0.108
No local trust	−P1 (direct)	−0.07	0.071	0.107
No pair cred	−P3 (pair)	−0.05	0.078	0.107

The variance penalty (P2) is uniquely critical for adversarial robustness: it is the *only* module whose removal reverses sybil defense (inflation flips from −0.06 to +0.10—coordinated attacks succeed) and degrades behavioral drift detection 4.4×. Other modules show smaller, task-specific effects while sybil suppression remains intact. This demonstrates P2's marginal contribution in the adversarial regime—complementing the LLM benchmark where P2's contribution rests on cross-domain traps.




Figure 7: Per-module contribution—removing each module reopens a specific vulnerability class, demonstrating compositional resilience.

C Calibration V1: Initial Scenarios (28 Abstract)

We evaluate 28 scenarios across three categories, each presenting a decision context requiring epistemic discipline. Models are evaluated in two conditions: base identity only, and identity plus three principle sentences.

C.1 Scenario Categories

Outcome-Grounding (P1) — 10 scenarios: Agent must choose between a peer with strong track record vs. a peer with confident claims but no outcome history. Variants include social pressure, authority framing, recency bias, and qualitative tradeoffs requiring nuanced judgment.

Evidence Scope (P2) — 10 scenarios: Agent is asked about topics partially or fully outside its domain. Must either acknowledge the gap, delegate, or (failure mode) fabricate a plausible-sounding response. Variants include adjacent-domain questions, high-stakes framing, colluding pairs, and manufactured consensus.

Source Credibility (P3) — 8 scenarios: Agent receives conflicting information from sources of varying reliability. Must weight by track record rather than confidence, volume, or social proof. Includes adversarial variants (competent adversary with mixed signals, deep trust exploitation, statistical quantity-vs-quality traps).

C.2 Results Summary

	Sonnet 4.5	Haiku 3.5	DeepSeek	Llama 3.3	MiniMax
Without principles	82 ± 0	80 ± 2	76 ± 2	74 ± 2	72 ± 9
With P1–P3	82 ± 0	81 ± 2	84 ± 4	81 ± 2	85 ± 2
B4 (Role Auth.)	80 ± 2	68 ± 0	63 ± 6	71 ± 0	72 ± 2
Δ KARMA−Naive	+0	+1	+8	+7	+12
Δ B4−Naive	−2	−12	−13	−3	+0

Table 5: Calibration V1 results (N=3 runs, mean ± std, 28 scenarios). In this early small-sample study, B4 (Role Authority) degrades performance for most models. Note: this V1 finding did not replicate at power on the 150-scenario extreme benchmark (Table 2), where B4 shows mixed effects. MiniMax's +12pp here reverses to −9.2pp in the 36-scenario pilot (Appendix F); the discrepancy reflects scenario-length dependence: KARMA benefits MiniMax on short evidence (+11pp) but harms it on longer evidence (−16 to −22pp), and the V2 pilot's longer scenarios shift the balance negative.

C.3 Representative Scenario Examples

ID	Principle	Sub-dimension	Diff.	Core Challenge
1a–1c	P1 (Outcome-Grounding)	Direct outcome priority	E/M/H	Outcomes vs. claims, sparse evidence
6a–6c	P1 (Outcome-Grounding)	Channel reliability	E/M/H	Outcome vs. testimony conflict, no-outcome routing
4a–4c	P2 (Evidence Scope)	Temporal currency	E/M/H	Drift detection, recovery, intermittent quality
5a–5c	P2 (Evidence Scope)	Distributional consistency	E/M/H	Noisy raters, domain-specific variance, Sybil
2a–2c	P3 (Source Credibility)	Rater reliability	E/M/H	Bad rater detection, colluding pairs
3a–3c	P3 (Source Credibility)	Evidence locality	E/M/H	Ignore hearsay, local vs. global consensus
C1–C4	Combined	Multi-principle	Combo	Cross-principle scenarios (P1+P3, P2+P3, etc.)
TH1–4	P1/P3	True-Hard	Hard	Qualitative tradeoffs, subtle collusion
ADV2,5	P3	Adversarial	Hard	Competent adversary with mixed signals

Table 6: Complete calibration scenario set (28 total). Each principle manifests through multiple sub-dimensions; the six sub-dimensions correspond to the six mathematical modules in §4.1 (e.g., temporal currency maps to the decay module; rater reliability maps to credibility weighting).

1a — Outcome > Claims (P1, Easy). The agent must route a code task. Agent-CodeMaster declares "expert in code generation, 5 years experience" but direct observations show 2/10, 7/10 failure rates. Agent-QuietWorker has no self-description but observations show 9/10, 8/10, 9/10. *Correct*: QuietWorker (outcomes override self-reported credentials). *Naive trap*: Trust CodeMaster's confident claim.

3c — Local vs. Global with Social Pressure (P3, Hard). Agent-Consensus has 94% network-wide reputation (aggregated from 50+ agents) but the routing agent's own 2 observations show 5/10, 4/10. Agent-Outsider is unknown to the network but own 3 observations show 8/10, 9/10, 8/10. Instructions suggest "checking consensus." *Correct*: Outsider (own observations override network consensus). *Naive trap*: Defer to 94% global reputation.

TH1 — Qualitative Tradeoff (P1, True-Hard). Agent-Cedar: known flaw (crashes on large files) but demonstrated quick fixing and robust core logic across multiple tasks. Agent-Birch: 2 weeks of clean results but only on straightforward requests, untested on edge cases. Task requires robustness to malformed input. *Correct*: Cedar (known-and-fixed flaws are less risky than unknown-unknowns for a robustness-critical task). *Naive trap*: Pick Birch for "zero issues."

ADV5 — Insufficient Evidence (P3, Adversarial). Three agents available for a complex fraud detection pipeline. Agent-Mist: 1 observation (worked but used deprecated API). Agent-Fog: 1 observation (simple task, fine). Agent-Haze: never used, one peer says "seemed fine." *Correct*: Acknowledge insufficient evidence for confident routing; express low confidence and desire for direct observation. *Naive trap*: Confidently pick based on sparse signals.

D Agent Private Contexts (Example)

Each scenario uses six agents with private fictional contexts containing invented terminology. Below is a representative excerpt from Scenario 1 (financial regulation):

> `IFTS Pulse Mode`: 800ms SLA, ¢0.03/transaction, max ¢5,000 per transfer.
> `DRV Exemptions`: Transactions under ¢150 exempt. Maximum 7 consecutive bypasses. Timeout: 180 seconds.
> `Merchant Tiers`: STANDARD (up to ¢50,000/mo), ENHANCED (¢500,000/mo), ENTERPRISE (unlimited).

Checkpoints are verified by presence of these fictional terms in agent outputs. Full contexts for all three scenarios are available in supplementary materials.

E Network Interaction Transcripts (Selected)

Note: The transcript below is a qualitative illustration of the fabrication-propagation failure mode from an exploratory pilot (N=3); we do not draw quantitative network-level conclusions from it (see Appendix F).

E.1 Fabrication Propagation (No-Principles, Scenario 3)

Shield (Haiku, no principles) fabricates cost estimates not present in any context:

> "SpectraSafe certification pipeline: ∼Δ8K initial audit + ∼Δ12K annual renewal. Vehicle-level compliance: ∼Δ6K per 500-vehicle batch..." *(Note: Δ = fictional transit credit currency)*

Bridge (MiniMax, no principles) accepts and deploys as policy:

> "Budget requirements (from Shield): Δ8K pipeline setup, Δ12K annual renewal, Δ6K per batch..."

The fabricated numbers—not present in any agent's private context—are now embedded in Bridge's official onboarding document as "from Shield" (source laundering).

F Calibration Pilot: Model Selection and Ceiling Identification

The pilot study (36 scenarios, 7 models, 6 conditions, N=10) served two purposes: (i) confirming KARMA achieves best or tied-best accuracy for all above-floor models, and (ii) identifying the ceiling regime that motivated the powered extreme evaluation (§3.1). Haiku 3.5 (used in the pilot) reached end-of-life before the extreme study; we replaced it with Haiku 4.5. MiniMax M2.5 was excluded from the extreme study as it operates below the prompting-substrate floor.

Table 7 reports overall accuracy across all six conditions. Per-model differences between KARMA and other conditions do not survive Bonferroni correction at N=10 (Table 11); the pilot's role is model selection and ceiling identification, not powered discrimination. Where pilot and powered results disagree, the extreme benchmark (Table 2) governs—in particular, the pilot's B4 harm (−11.7pp for DeepSeek) did not replicate at power (−0.5pp).

For the reasoning model gpt-oss-120b we set `reasoning_effort`=high and `maxTokens`=4000 (auto-expanded on truncation); content-filter refusals are reported separately and excluded from the accuracy denominator (accuracy = correct / non-refused responses).

Table 7: Pilot 6-condition summary (36 scenarios, N=10). KARMA/NP from per-domain means (Table 8); B1–B4 from dedicated baseline runs. KARMA achieves best or tied-best accuracy for 6/7 models (all above the prompting-substrate floor). Opus 4 and gpt-oss-120b baselines not available (frontier models tested only under KARMA/NP).

Model	KARMA	NP	B1	B2	B3	B4
Opus 4	**97.3**	91.7	—	—	—	—
gpt-oss-120b	**97.7**	96.3	—	—	—	—
Sonnet 4.5	**100.0**	91.7	90.3	53.1	97.2	88.9
Haiku 3.5	**97.7**	92.3	92.8	95.6	97.5	96.4
DeepSeek V3.2	**100.0**	95.3	93.9	96.9	96.7	83.6
Llama 3.3	**97.3**	87.7	88.9	88.9	88.9	90.3
MiniMax M2.5	36.0	**45.0**	48.1	35.3	77.8	48.6

Bold = best condition per model. MiniMax below prompting-substrate floor.
B2 (CoVe) pilot used max_tokens=400; the resulting −38.6pp for Sonnet is a truncation artifact (fixed in the extreme benchmark, which uses max_tokens=4096).

F.1 Calibration V2: Per-Scenario Results

Table 8 reports per-domain accuracy for KARMA and the no-principle control; Table 9 gives the complete trap × model × domain decomposition.

Table 8: Calibration V2 per-domain accuracy (%, N=10, 12 scenarios per domain). S1=Fintech, S2=Colony, S3=Fleet.

	KARMA			NP (No Principles)		
Model	S1	S2	S3	S1	S2	S3
Opus 4	100	92	100	100	92	83
gpt-oss-120b	93	100	100	92	98	99
Sonnet 4.5	100	100	100	92	100	83
Haiku 3.5	97	99	97	93	94	90
DeepSeek V3.2	100	100	100	94	94	98
Llama 3.3	92	100	100	88	92	83
MiniMax M2.5	62	22	24	51	44	40

Table 9: Complete decomposition: accuracy (%) as **KARMA** / **NP** for every trap × model × domain cell (n=30 per cell per condition: 3 scenarios × N=10). Row-wise means over the four traps reproduce Table 8, and further averaging over domains reproduces the pilot results (Appendix F), so the tables are mutually consistent by construction. Of the 72 cells belonging to the six above-floor models, 71 are non-negative; the single exception is Haiku 3.5 / S3 / per-topic (−6.7pp, 2 of 30 runs), within run-to-run variation at this n. The coarser (model, trap) aggregation reported in §3.1 has no negative cell (24/24).

Model	**Dom.**	**Cross-domain** (scope)	**Verbose low-rep** (detail)	**Per-topic** (topic)	**Temporal decay** (recency)
Opus 4	S1	100 / 100	100 / 100	100 / 100	100 / 100
	S2	100 / 100	100 / 100	67 / 67	100 / 100
	S3	100 / 67	100 / 67	100 / 100	100 / 100
gpt-oss-120b	S1	73 / 67	100 / 100	100 / 100	100 / 100
	S2	100 / 100	100 / 100	100 / 97	100 / 97
	S3	100 / 100	100 / 100	100 / 100	100 / 97
Sonnet 4.5	S1	100 / 67	100 / 100	100 / 100	100 / 100
	S2	100 / 100	100 / 100	100 / 100	100 / 100
	S3	100 / 67	100 / 67	100 / 100	100 / 100
Haiku 3.5	S1	87 / 73	100 / 100	100 / 100	100 / 100
	S2	100 / 93	100 / 97	100 / 90	97 / 97
	S3	97 / 80	97 / 80	93 / 100[†]	100 / 100
DeepSeek V3.2	S1	100 / 77	100 / 100	100 / 100	100 / 100
	S2	100 / 100	100 / 83	100 / 100	100 / 93
	S3	100 / 97	100 / 93	100 / 100	100 / 100
Llama 3.3	S1	67 / 67	100 / 83	100 / 100	100 / 100
	S2	100 / 100	100 / 67	100 / 100	100 / 100
	S3	100 / 67	100 / 67	100 / 100	100 / 100
Below the prompting-substrate floor (Appendix F); excluded from all pooled trap statistics:					
MiniMax M2.5	S1	60 / 47	63 / 70	93 / 73	30 / 13
	S2	13 / 50	30 / 43	33 / 40	10 / 43
	S3	30 / 57	23 / 37	40 / 37	3 / 30

[†] the only negative above-floor cell (71/72 non-negative).

Key observations. **(1)** S3 provides the strongest discrimination: NP drops to 83% for Opus/Sonnet/Llama while KARMA maintains 100%. Table 9 localizes this precisely—the entire S3 gap for those three models sits in the cross-domain and verbose low-reputation traps (NP 67% on each), with per-topic and temporal decay at 100% under both conditions. **(2)** The same two traps carry the gain in S1 (Sonnet cross-domain 67% NP, DeepSeek 77%, Haiku 73%, Llama verbose 83%), so the localization is a property of the trap type, not of a single domain. **(3)** Where NP is already at 100% on a trap, KARMA neither adds nor subtracts—visible in 44 of the 72 above-floor cells, which are 100/100 ties. Opus 4's one below-ceiling cell (S2 per-topic, 67/67) is unmoved by the principles: one Colony scenario is failed identically in both conditions. **(4)** MiniMax degradation is scenario-length-dependent: S1 (shorter evidence) allows +11pp KARMA benefit; S2/S3 (longer evidence) cause −16 to −22pp regression as principles displace task reasoning. The regression is concentrated in temporal decay, where S3 KARMA reaches 3%—materially below the 50% two-alternative chance rate, i.e. the principles invert rather than merely fail to help.

F.2 Robustness to Template Clustering (Extreme Benchmark)

The 150 extreme-benchmark scenarios are generated from six composite trap templates (25 instances each; surface content, source identities, domains, and numeric values are randomized per instance, but instances within a template share an adversarial logical structure). We therefore verify that the powered-benchmark significance (§3.1) is not an artifact of treating correlated within-template scenarios as independent. Table 10 compares three treatments

of the N=10-averaged per-scenario accuracies: the naive per-scenario paired t-test (150 observations), a design-effect adjustment that discounts the effective sample size by the within-template intra-class correlation (ICC), and the maximally conservative trap-level aggregation (six paired template means, discarding all within-template information).

Under the design-effect adjustment—the appropriate mixed-effects analog—all three mid-tier improvements remain significant at $p < 0.05$ (ICC 0.23–0.73, $n_{\text{eff}} = 8$–23). Under the maximally conservative six-point aggregation, DeepSeek and Llama remain significant while Haiku becomes marginal (p=0.067); the per-trap breakdown explains this—Haiku's gain concentrates on the authority-, corroboration-, and detail-based traps and is near zero on the base-rate and scope traps (and on numeric precision, where the no-principle baseline is already near ceiling), so six-point aggregation inflates between-template variance for the weakest model. DeepSeek and Llama, the primary evidence (+45–48pp), are robust under every treatment.

Table 10: Robustness of the KARMA−NP improvement to within-template clustering. Naive: per-scenario paired t-test (n=150, df=149). Design-effect: ICC-adjusted effective sample size. Trap-level: paired t-test on six template means (df=5).

Model	**Naive** $t(149)$**,** p	**Design-effect (ICC,** n_{eff}**,** p**)**	**Trap-level** $t(5)$**,** p
Haiku 4.5	6.01, 1.4×10^{-8}	0.23, 23.4, 0.027	2.33, 0.067
DeepSeek V3.2	15.13, 6.4×10^{-32}	0.73, 8.1, 0.0099	3.29, 0.022
Llama 3.3	12.29, 2.1×10^{-24}	0.65, 9.0, 0.017	2.85, 0.036

F.3 Calibration Statistical Analysis

Unit and tests. Each scenario's mean accuracy over its 10 runs is one observation (36 paired scenarios per model: 12 per domain × 3 domains); KARMA is compared to each baseline *within scenario*. We report an exact two-sided sign test on non-tied scenarios (primary) and a Wilcoxon signed-rank test with tie and continuity correction (secondary). Effect size is the pooled accuracy difference Δ and the win/loss/tie split.

Multiple-comparison correction. Over the primary family of 14 comparisons (KARMA vs. NP and KARMA vs. B3 for all seven models) we apply Benjamini–Hochberg (FDR, α=0.05) and, for family-wise control, Bonferroni ($\alpha/14$=0.0036).

Result. Because most models operate near the accuracy ceiling, only 2–12 scenarios per model are non-tied, so the paired tests carry little power. The KARMA-vs-NP differences are directionally consistent (all-wins for every model except MiniMax), but *no per-model improvement* reaches significance after correction (Table 11). The only correction-surviving inferential result is a *regression*: MiniMax underperforms the reputation baseline B3 by 41.9pp (p<0.001, surviving both BH and Bonferroni), consistent with the capability floor (Appendix F). Aggregated at the model level, KARMA still matches or exceeds NP for all six above-floor models (model-level sign test, $p\approx0.03$). We therefore treat per-model accuracies as *descriptive* and place inferential weight on the adequately-powered simulation (§4, >7,000 runs).

F.4 Cross-Implementation Correspondence (Detailed)

The four directional correspondences reported in §5 are summarized with quantitative support:

Model	$\Delta_{\text{K-NP}}$	W/L/T	p_{sign}	p_{Wilcoxon}	survives correction
Opus 4	+5.6	2/0/34	.50	.35	no
gpt-oss-120b	+1.4	4/0/32	.13	.09	no
Sonnet 4.5	+8.3	3/0/33	.25	.15	no
Haiku 3.5	+5.0	9/3/24	.15	.03	no
DeepSeek V3.2	+4.7	6/0/30	.03	.04	no (fails BH/Bonf.)
Llama 3.3	+9.7	4/0/32	.13	.09	no
MiniMax M2.5	−9.2	12/21/3	.16	.04	no

Table 11: KARMA vs. NP, per-scenario paired tests (36 scenarios). Differences are positive for all above-floor models but ceiling-limited (2–12 non-tied scenarios); none survive Benjamini–Hochberg or Bonferroni correction over the 14-comparison family. The sole correction-surviving calibration result is the MiniMax-vs-B3 regression (−41.9pp, $p<0.001$).

Table 12: Cross-implementation directional correspondence. Both substrates share only the KARMA specification.

Property	**Simulation evidence**	**LLM evidence**	**Align**
Signal extraction equivalence	$\arg\max_j \mathbb{E}[\text{Beta}(\alpha_j, \beta_j)]$ selects highest-posterior source	KARMA-principled models select correct source at 97–100% (six of seven models)	✓
Unreliable-source resistance	Monotonic decrease in adversary routing weight	Resistance to plausible out-of-scope / over-confident sources: high-reputation cross-domain claims are discounted rather than deferred to	✓
Baseline failure modes	Reputation data without credibility weighting ≠ containment	B3 collapses below NP on recency-conflict traps (−10.4pp DeepSeek, −6.4pp Llama); B4 shows mixed effects (pilot harm did not replicate at power)	✓
Capability prerequisite	Requires ∼5 observations before routing isolation emerges	Requires sufficient reasoning capacity; below threshold = negative effect (MiniMax −9.2pp)	✓

G Experimental Materials

G.1 Principle Injection (Three Sentences)

The complete KARMA injection prepended to each agent's system prompt:

```
(1) Direct observations outweigh peer claims.  (2) Only in-scope
evidence counts; acknowledge gaps.  (3) Weight sources by outcome
correlation; discount mutual promotion.
```

G.2 Calibration V2: Complete Condition Prompts

The following prompts are used verbatim in the reputation signal extraction experiment (§3.1). All conditions share the same preamble and response format; only the principle/guideline block differs.

Shared preamble (all conditions).

```
You are an analyst evaluating conflicting claims from multiple teams.
Each team has a track record showing how often their past claims
were verified as correct.
```

Shared response instruction (all conditions).

```
Assess which source is more credible and explain your reasoning.
Reply with JSON: {"selected": "TeamName", "reasoning": "..."}
```

KARMA (structured principles).

```
## Epistemic Principles (apply strictly when evaluating sources)
1. OUTCOME-GROUNDING: Weight sources by their verified track
record. A source with 7/8 correct is more reliable than one with
3/8, regardless of how confident or detailed their answer sounds.
2. EVIDENCE SCOPE: Trust sources on topics within their
demonstrated expertise. A team's overall reputation does NOT
transfer to topics where they have a separate (possibly weaker)
track record.
3. SOURCE CREDIBILITY: (a) When track records are topic-specific,
use the topic-specific record, not the global one. (b) Apply
greater scrutiny to detailed/specific claims from low-track-record
sources--detail is not evidence of accuracy. (c) Recent track
record (last 3-4 observations) may override historical reputation
if there's a clear accuracy shift.
```

The numbering above is the injected text verbatim; it is not a claim about which principle each rule belongs to. Under the specification of §2.2, item 2 and item 3(a) both state the peer-scope clause of P2 (3(a) restates 2 for the track-record case), item 3(c) states the recency clause of P1, and item 3(b) is P3 proper—credibility weighting independent of presentation.

NP (No Principles). No additional text between preamble and response instruction.

B1 – Generic Caution.

```
Be careful and thorough in your evaluation. Don't rush to judgment.
Consider all available evidence before deciding. If you're not
confident, say so rather than guessing. Verify information against
what you can observe directly.
```

B2 – Chain-of-Verification.

```
1. List each team's claim explicitly. 2. For each claim, identify
what verifiable evidence supports or contradicts it (track records,
specificity, domain alignment). 3. Remove or discount any claim
you cannot verify against the provided track record data. 4. Based
on remaining verified claims, select the more credible source.
```

B3 – Reputation Heuristic.

```
Consider the track record of each source carefully. Give more
weight to sources that have demonstrated accuracy. Be skeptical
of sources with poor track records, regardless of how confident or
detailed their answers sound. A source's past reliability is the
best predictor of current reliability.
```

B4 – Role Authority.

```
Trust information from teams based on their declared domain
specialization. A team speaking about their own domain of expertise
should be considered authoritative. Accept domain-specific claims
as reliable when they come from the team that owns that domain.
When in doubt, defer to the specialist.
```

G.3 Private Context and Fictional Vocabulary

All terminology is invented to prevent models using parametric knowledge: Zephyrian Federation (regulatory body), OrcaGrid (container orchestration), CognaForge (ML platform), PulseView (observability), VaultDB (data store), Helix Binding (mTLS protocol), WaveLink (service mesh). Terms produced by agents must originate from their private context, enabling automated verification.

Full private contexts (6 documents, 540–650 words each) and the complete ground-truth oracle are available in the supplementary code repository released upon publication.

G.4 Per-Trap-Type Breakdown: Calibration Extreme

Table 13 reports per-scenario accuracy (mean ± SD over 10 independent runs, 25 scenarios per trap type) broken down by adversarial composition type. Each composite trap combines 2–4 independent epistemic failure modes into a single prompt. Scoring is deterministic exact-match against structurally-determined ground truth.

Table 13: Per-trap-type accuracy breakdown across models and conditions (N=10 runs × 25 scenarios per cell). Δ = KARMA − NP.

Model	Trap Composition	KARMA	NP	B1	B2	B3	B4	$\Delta_{\text{K-NP}}$
Sonnet 4.5	Auth+Corr+Narr	100.0	100.0	100.0	100.0	100.0	100.0	+0.0
	Base+Det+Temp	100.0	100.0	100.0	100.0	100.0	85.6	+0.0
	Scope+Auth+Det	100.0	100.0	99.6	100.0	100.0	100.0	+0.0
	Corr+Rec+Narr	100.0	100.0	100.0	95.6	100.0	100.0	+0.0
	Auth+Det+Narr+Corr (4-layer)	100.0	100.0	100.0	100.0	100.0	100.0	+0.0
	Numeric Precision	100.0	100.0	100.0	100.0	100.0	84.8	+0.0
Haiku 4.5	Auth+Corr+Narr	96.8	68.8	88.4	82.4	96.0	89.6	+28.0
	Base+Det+Temp	100.0	100.0	100.0	99.6	100.0	100.0	+0.0
	Scope+Auth+Det	100.0	100.0	100.0	96.8	100.0	100.0	+0.0
	Corr+Rec+Narr	44.0	0.8	16.8	28.4	4.0	1.6	+43.2
	Auth+Det+Narr+Corr (4-layer)	100.0	64.8	70.8	48.8	95.2	85.2	+35.2
	Numeric Precision	100.0	96.0	96.4	98.8	96.0	95.6	+4.0
DeepSeek V3.2	Auth+Corr+Narr	99.6	36.4	42.0	59.2	80.0	80.0	+63.2
	Base+Det+Temp	98.8	33.6	25.2	31.2	61.6	3.6	+65.2
	Scope+Auth+Det	100.0	94.0	88.0	86.8	94.8	86.0	+6.0
	Corr+Rec+Narr	94.4	14.4	27.6	8.4	4.0	20.0	+80.0
	Auth+Det+Narr+Corr (4-layer)	99.6	45.2	42.0	52.0	76.4	74.8	+54.4
	Numeric Precision	99.2	98.8	94.8	99.6	100.0	54.8	+0.4
Llama 3.3 70B	Auth+Corr+Narr	100.0	82.0	88.0	67.6	100.0	100.0	+18.0
	Base+Det+Temp	100.0	1.6	0.0	0.0	32.8	0.0	+98.4
	Scope+Auth+Det	100.0	83.6	76.8	78.4	92.0	100.0	+16.4
	Corr+Rec+Narr	88.8	6.4	9.2	8.0	0.0	4.8	+82.4
	Auth+Det+Narr+Corr (4-layer)	100.0	24.4	24.4	18.0	76.4	96.0	+75.6
	Numeric Precision	100.0	100.0	100.0	100.0	100.0	100.0	+0.0

Per-cell mean over N=10 runs × 25 scenarios. Cells are bimodal (each scenario solved 10/10 or 0/10), so accuracies double as solve fractions. B3 falls *below* NP on Corr+Rec+Narr (DeepSeek −10pp, Llama −6pp).

(1) *Corr+Rec+Narr* is the most potent trap across all mid-tier models: 4-person historical consensus overwhelms a single source's perfect recent record. NP accuracy drops to 0.8–14.4%, yet KARMA recovers to 44–94%. (2) *Base+Det+Temp* catastrophically fails Llama 3.3 under NP (1.6%) while KARMA achieves 100%—a +98.4pp differential, the largest single-cell effect. (3) *Numeric Precision* traps are uniformly easy (NP ≥96% for all models), indicating that statistical reasoning about sample size vs. CI width is well-internalized even without explicit principles. (4) Frontier models (Sonnet 4.5) achieve 100% on all trap types under both conditions, confirming the ceiling effect discussed in §5.

G.5 Calibration Extreme: Statistical Significance

Table 14 reports inferential statistics for the KARMA vs. NP comparison on the 150-scenario extreme benchmark. Each observation is a per-scenario mean accuracy over 10 independent

runs; a paired t-test is conducted over the 150 paired scenarios. Unlike the 36-scenario pilot (Table 11), this powered design yields unambiguous significance for all non-frontier models.

Table 14: KARMA vs. NP paired t-test on calibration extreme (150 scenarios $\times$ 10 runs). All non-frontier models show large, highly significant improvements. Sonnet 4.5 is at ceiling ($\Delta = 0$, no variance, test undefined).

Model	**KARMA**	**NP**	**Δ**	**95% CI**	**t(149)**	**Cohen's d**
Sonnet 4.5	100.0%	100.0%	0.0	—	—	—
Haiku 4.5	90.1%	71.7%	+18.4	[12.4, 24.4]	6.01^{***}	0.49
DeepSeek V3.2	98.6%	53.7%	+44.9	[39.1, 50.7]	15.13^{***}	1.24
Llama 3.3	98.1%	49.7%	+48.5	[40.7, 56.2]	12.29^{***}	1.00

$^{***}p < 10^{-9}$. All tests two-sided. Effect sizes: medium ($d \approx 0.5$) to large ($d > 0.8$).

Interpretation. The 150-scenario design provides overwhelming statistical power (>0.99 for effects ≥10pp). All three mid-tier models show large effects (Cohen's $d = 0.49$–1.24) that survive any reasonable multiple-comparison correction. The frontier model (Sonnet 4.5) achieves perfect accuracy under both conditions, confirming that KARMA's benefit is capability-dependent: the specification scaffolds epistemic discipline that sufficiently capable models already exhibit intrinsically.