When Marginal Stability Is Not Enough: Auditing Benchmark Conclusions under Composition Shift

Anonymous authors
Paper under double-blind review

Abstract

Multimodal benchmarks aggregate performance across heterogeneous evaluation contexts, yet it remains unclear how far their conclusions extend beyond the empirical mixture of those contexts. We introduce Composition-Conditional Reliability Auditing (CCRA), which keeps questions and model responses fixed and varies only the weights of observed context cells under bounded total-variation (TV) budgets. We audit four multimodal large language models (MLLMs) on MMAD, an industrial anomaly-detection benchmark, and a fixed three-benchmark panel spanning visual robustness (MVI-Bench), multidisciplinary reasoning (MMMU), and spatial reasoning (MMSI-Bench). Within the audited bounds, a one-percentage-point score change requires moving as little as 1.4–3.7% of evaluation mass on MMAD, MVI-Bench, and MMMU, whereas MMSI-Bench remains within 1.4 points. At the prespecified +1pp selection margin, joint reweighting reaches the endpoint in 6 of 12 native MMAD pair–prompt settings while matched product-only, task-only, and additive spaces do not; one of six MMMU pairs also reaches the endpoint. Larger challenger leads are substantially less common, and no five-point lead is reached within the audited scopes. Separately, on MMAD, joint stress increases held-out error among accepted answers by 6.9–9.7 percentage points for acceptance rules selected on development data and then frozen. These results show that benchmark robustness is conclusion- and margin-dependent, motivating reports that state the composition conditions supporting each score, model-selection, or acceptance conclusion.

1 Introduction

Consider two models evaluated on the same industrial products across several inspection tasks. One may be more accurate at defect detection and the other at object analysis. Changing the product–task mixture can change their average scores and potentially reverse their ordering, even though every question and recorded response stays fixed. If high-confidence answers are accepted automatically, the changed mixture can also alter how often accepted answers are wrong. The benchmark therefore supports three different judgments—how well a model performs, which model to choose, and which answers to trust. How far do those judgments extend beyond the original mixture?

We study the composition-conditional validity of benchmark conclusions. A reported score may change substantially while the same model remains preferable; retaining that model also does not ensure that its confidence-based acceptance rule remains reliable. We therefore distinguish score stability, model selection, and oversight. For each threshold-based conclusion, the validity domain is the observed-context mixtures for which its specified tolerance holds. Figure 1 fixes inputs, recorded outputs, and support while changing only cell weights; in its numerical-swap example, the challenger gap crosses zero but remains below the prespecified decision margin δ.

Prior work establishes that evaluation distributions can affect scores and orderings: Siska et al. probe benchmark assumptions through distributional reweighting, and Huang et al. study ranking sensitivity to worst-case preference deletions (Siska et al., 2024; Huang et al., 2026). Target-distribution estimation, worst-case group training, and selective prediction address related but distinct objectives (Chen et al., 2021; Sagawa et al., 2020; Tian et al., 2023; Geifman & El-Yaniv, 2017). We ask which

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: CCRA schematic of possible, non-empirical consequences. CCRA keeps items, model outputs, and a frozen acceptance threshold θ fixed, then reweights observed product–task cells. Rows denote products, columns tasks, and darker cells receive larger weights. The industrial illustrations are schematic, not benchmark photographs. Reweighting can alter a reported score, induce a numerical ranking swap without reaching the prespecified decision margin δ, or change selective risk and coverage under the same θ.

bounded composition changes alter each benchmark-supported conclusion, and how much mass must move before they do.

The distinction between kinds of change is particularly important when benchmarks cross multiple dimensions. An inspection benchmark may contain both defect-detection and defect-classification questions for each product. Changing product frequencies alone preserves the task mixture within each product; changing task frequencies alone preserves the product mixture within each task. Neither explores every combination-specific change, such as concentrating defect-classification questions on cables. A conclusion that survives each restricted audit therefore still requires examination under changes to the full product–task mixture.

We introduce **Composition-Conditional Reliability Auditing (CCRA; workflow in Figure 2)**, a fixed-response audit over marginal, additive, and joint reweighting under bounded relative weights and total variation (TV). CCRA reports score shifts, selection thresholds, and confidence endpoints while separating sampling uncertainty. Development-selected acceptance rules and stress weights are frozen before held-out oversight evaluation.

We evaluate four multimodal large language models (MLLMs) on MMAD (Jiang et al., 2025), our primary industrial anomaly-detection benchmark, under zero-shot and reference-conditioned one-shot prompting. A fixed external panel comprises MMSI-Bench (spatial reasoning) (Yang et al., 2026), MVI-Bench (controlled visual robustness) (Chen et al., 2025), and the multiple-choice subset of MMMU validation (multidisciplinary reasoning) (Yue et al., 2024). Across six native MMAD matched-TV events, joint reweighting reaches the prespecified +1pp challenger lead while product-

only, task-only, and additive reweighting do not, showing that the declared composition space can determine whether a model-selection endpoint is attained.

Our contributions are threefold:

1. We distinguish score, selection, and oversight conclusions, and formalize tolerance-specific validity domains for threshold-based score and selection claims.
2. We introduce a fixed-response audit that compares models at one composition and compares restricted and joint spaces at matched realized TV, with sampling uncertainty evaluated separately.
3. We map score movement and model-selection endpoints across four benchmarks under fixed recorded responses, including joint-only +1pp leads in native MMAD matched-TV comparisons; a separate MMAD frozen-rule audit measures held-out oversight under joint stress.

2 Related Work

Benchmark validity and ranking. Benchmark scores are routinely read as point estimates of ability, although composition can affect scores and rankings. Siska et al. examine distributional assumptions through clustering and random-simplex reweighting (Siska et al., 2024); Huang et al. study worst-case preference deletion with approximate maximum influence perturbations (AMIP) (Huang et al., 2026); and benchmark transparency can be quantified through individual data decisions (Kovatchev & Lease, 2024). Large evaluation suites also document sensitivity to scenario slicing, metric choice, and statistical uncertainty in leaderboard orderings (Liang et al., 2023; Srivastava et al., 2023; Singh et al., 2025). CCRA retains a frozen response ledger and maps the bounded mixtures supporting each conclusion.

Reweighting and distributional robustness. Importance weighting and covariate-shift correction estimate performance under a postulated target distribution (Shimodaira, 2000; Sugiyama et al., 2007; Quiñonero Candela et al., 2009), while distributionally robust optimization optimizes or bounds worst-case risk over an uncertainty set (Duchi et al., 2021; Namkoong & Duchi, 2017; Sagawa et al., 2020; Rahimian & Mehrotra, 2022). CCRA instead uses bounded reweighting to audit fixed benchmark conclusions under declared composition conditions.

Confidence, calibration, and selective prediction. Confidence estimates from language models are imperfectly calibrated, whether derived from logits or elicited verbally (Guo et al., 2017; Kadavath et al., 2022; Xiong et al., 2024; Tian et al., 2023), and selective prediction formalizes the risk–coverage trade-off of accepting high-confidence answers (Geifman & El-Yaniv, 2017; El-Yaniv & Wiener, 2010), with distribution-free variants giving coverage guarantees (Angelopoulos & Bates, 2023; Hebert-Johnson et al., 2018). CoFact adapts calibration under covariate shift (Hu et al., 2026); CCRA instead freezes a development-selected acceptance rule and audits how its held-out selective risk and coverage move when only the evaluation composition changes.

3 Method: Composition-Conditional Reliability Auditing

3.1 Audit Setting and Estimands

A cross-context benchmark indexes questions by observed composition cells g—product–task pairs on MMAD, type–difficulty pairs on MMSI, discipline–difficulty pairs on MMMU, and level–condition pairs on MVI. The audit input is a frozen ledger with question and image identifiers plus each model's correctness and verbalized confidence; it does not retain raw answer text. Figure 2 traces this ledger through declared spaces and budgets, with sampling uncertainty handled independently. Let w^0 be the empirical cell composition, let N_g be the relevant model–split question count in cell g, and let $\widehat{a}_{mg}$ denote model m's estimated accuracy in that cell. Composition enters through

$$A_m(w) = \sum_g w_g \, \widehat{a}_{mg}, \qquad \sum_g w_g = 1. \tag{1}$$

CCRA reports three families of estimands: single-model scores $A_m(w)$; model comparison at a common composition w; and confidence endpoints defined in §3.4. Predeclared tolerances define validity

domains for threshold-based score and selection conclusions; confidence endpoints are reported separately.




Figure 2: CCRA workflow. A fixed response ledger for model m is aggregated to cell accuracies $\hat{a}_{m1}, \ldots, \hat{a}_{mG}$. Product-only, task-only, additive, and joint relative-weight spaces obey normalization, density-ratio, TV, and nesting constraints. Score stability is summarized by the maximum absolute score movement within a TV budget and by $\rho_m(t)$; selection independently tests whether the final challenger lead $A_b(w) - A_a(w)$ reaches δ. Development folds select stress weights and an acceptance threshold, which are frozen before held-out risk and coverage are evaluated.

3.2 Bounded Composition Spaces

CCRA compares marginal, additive, and joint composition spaces (Figure 2). Product-only and task-only audits rescale one axis while preserving the conditional mixture along the other. Both marginal spaces lie within the additive span, although neither contains the other. The additive span uses $w_{pt}/w^0_{pt} = 1 + \alpha_p + \beta_t$, so product and task adjustments sum without an additional cell-specific adjustment. The joint space assigns a weight to each observed cell independently. All spaces retain observed support under the box constraint

$$\mathcal{W}_\kappa(\mathcal{S}) = \left\{ w \in \mathcal{S} : \ \textstyle\sum_g w_g = 1, \ \kappa^{-1} \le w_g / w^0_g \le \kappa \right\}, \tag{2}$$

so every observed cell receives bounded positive mass. Shift magnitude is measured by total variation, $d_{\mathrm{TV}}(w, w^0) = \frac{1}{2} \sum_g |w_g - w^0_g|$, the fraction of composition mass moved from one set of cells to another. Because the marginal and additive spaces are restrictions of the joint space, joint envelopes are at least as large at every κ; comparisons between spaces are made at matched realized TV, which equalizes shift magnitude but not directional richness.

3.3 Score and Model-Selection Endpoints

Three quantities are reported separately: the *score shift* $A_m(w) - A_m(w^0)$; the *gap movement* $[A_b(w) - A_a(w)] - [A_b(w^0) - A_a(w^0)]$; and the *final challenger lead* $A_b(w) - A_a(w)$. For scores, CCRA reports the envelope $\max_w |A_m(w) - A_m(w^0)|$ and minimum-TV radius $\rho_m(t) = \min\{d_{\mathrm{TV}}(w, w^0) : |A_m(w) - A_m(w^0)| \ge t\}$.

For selection, a is the baseline-higher model and b its challenger at the empirical composition. A numerical swap satisfies $A_b(w) - A_a(w) \ge 0$, whereas the prespecified decision endpoint requires a +1pp challenger lead, $A_b(w) - A_a(w) \ge \delta$ with $\delta = 0.01$. The supplementary ladder extends this endpoint to challenger leads of 1, 3, 5, and 10 points (Appendix E). When selection regret is reported, $m^\star$ denotes the empirical overall winner whose retention is evaluated.

3.4 Confidence and Selective-Risk Endpoints

Because verbalized confidence takes discrete values, CCRA evaluates exact emitted support. At stated confidence c,

$$G_w(c) = \frac{\sum_g w_g K_g(c)/N_g}{\sum_g w_g M_g(c)/N_g}, \tag{3}$$

where $M_g(c)$ and $K_g(c)$ count responses emitted at c and correct among them; a model saying "0.95" need not be 95% correct, and $G_w(c)$ tracks how that empirical meaning moves with composition. For an acceptance threshold θ, coverage and selective risk are

$$Q_w(\theta) = \sum_g w_g L_g(\theta)/N_g, \qquad R_w(\theta) = \frac{\sum_g w_g E_g(\theta)/N_g}{Q_w(\theta)}, \tag{4}$$

with L_g accepted counts and E_g accepted errors; the numerator is accepted-error mass and the denominator is coverage, so both account for changes in selective risk.

Oversight uses five image-disjoint folds: at $\kappa = 2$, four development folds choose joint stress weights and the largest exact-support threshold meeting an 80% development-coverage target, then freeze both before the remaining fold is evaluated. A frozen threshold does not fix coverage, so held-out composition changes are evaluated for both $Q_w(\theta)$ and $R_w(\theta)$.

3.5 Estimation and Uncertainty

Cell accuracies use an empirical-Bayes beta–binomial posterior mean, with prior hyperparameters estimated once per model from the frozen ledger and held fixed; unshrunk cell means and a common Beta$(1, 1)$ prior are preregistered sensitivity estimators (Appendix G).

Sampling uncertainty is kept separate from composition sensitivity. Radii and events are re-solved within each of 1,000 product-stratified image-cluster bootstrap replicates (Field & Welsh, 2007; Efron & Tibshirani, 1993); confidence endpoints instead resample held-out images and score the frozen objects without re-optimization.

For transfer, full-ledger scores fix each pair orientation; each development fold then solves its own joint stress direction and TV magnitude before that direction is scored on the held-out fold.

4 Experiments

4.1 Experimental Setup

Table 1 summarizes the audit. MMAD (Jiang et al., 2025) is the primary benchmark: 39,670 industrial-inspection multiple-choice questions over 8,366 images, crossing 38 products with seven inspection tasks (266 observed cells), evaluated under zero-shot and reference-conditioned one-shot prompting; confirmatory analyses use native images, with compressed-image ($c1024$) runs as sensitivity analyses. The frozen external panel was collected under a single zero-shot JSON answer-plus-confidence protocol, with analysis manifests locked before collection. Four API-served MLLMs (MiniMax-M3, Kimi-K2.5, Qwen3.5-Flash, Qwen3.5-Plus) provide all responses. The primary score and selection analyses use $\kappa \in \{1.25, 1.5, 2, 3\}$ and the empirical-Bayes estimator, with six empirically ordered pairs per external benchmark and three winner–challenger pairs per MMAD setting; a secondary native MMAD scope includes all six pairs.[1] The +1pp decision margin, the five-point exact-confidence gate, and the frozen-rule protocol are prespecified; score-shift radii and the 1/3/5/10-point selection rungs are a follow-up extension whose plan was locked before computation.

[1]MiniMax input rejections were 0.50% (MMSI), 0.24% (MVI), and 1.89% (MMMU, above the 1% gate; Appendix A). Shared cell support makes these refusals affect composition weights for all pairs.

Table 1: Audit datasets. MMAD uses native images for confirmatory analyses and compressed images for sensitivity analyses. The external panel uses one zero-shot JSON answer-plus-confidence protocol; MMMU-Val is its 847-question multiple-choice subset. Representative VQA formats appear in Appendix Figure 6.

Benchmark	Items	Composition axes	Input format
MMAD	39,670	product×task (38×7)	native; zero-/one-shot
MMSI	1,000	type×difficulty (11×3)	multi-image
MVI	1,248	level×condition (3×2)	one image
MMMU-Val	847	discipline×difficulty (6×3)	one/multiple; 2–9 options

4.2 How Much Can Reported Scores Move?

Reported scores showed substantial movement within the audited composition scopes. At $\kappa = 3$, a one-point shift required as little as 1.4–3.7% TV on MMAD, MVI, and MMMU (Figure 3); full 1/3/5-point radii appear there and in Appendix D. Its left panel reports score radii for model settings, while its right panel reports the TV needed for a pair-setting to attain a final challenger lead. Envelopes reached 16.0 points on MVI, 10.9 on MMMU, and 14.6 on MMAD only near the box cap (≈0.5). MMSI was stable under the same spaces and estimator: every score moved at most 1.4 points and a one-point shift required at least 23.8% TV. Marginal and additive spaces produced smaller movements.




Figure 3: How much composition shift is needed to move a score or produce a final challenger lead? Left: minimum TV for an absolute score change. Right: minimum TV for a final challenger lead, $A_b(w) - A_a(w)$, after reweighting, rather than a change in the pairwise gap. Leads are challenger minus baseline winner on MMAD and challenger minus baseline-higher model externally. Left marks are model settings; right marks are pair-settings, with all-pairs external scope. All values use joint $\kappa = 3$ empirical-Bayes estimates. Shapes distinguish native and $c1024$ MMAD settings. Grey ranges show displayed minima and maxima, not confidence intervals. NR denotes endpoints not reached within the audited space.




Figure 4: Worked MMAD case and matched-TV comparison. Top: native zero-shot empirical-Bayes joint case. Two illustrative juice_bottle cells provide case-level context for full 266-cell model scores at a common composition; Object Analysis pools 282 Analysis, Details, and Structure questions. Bottom: six native all-pairs events compare product-only, task-only, additive, and joint optima. Each row uses its first-reaching κ, retains the original TV cap, and gives all four spaces, under separate compositions, the same realized TV within that row. Joint reaches the +1pp threshold, whereas restricted spaces do not.

4.3 When Does Composition Change Model Selection?

For the native zero-shot Qwen3.5-Flash–Qwen3.5-Plus case, the full 266-cell empirical-Bayes joint audit first reaches a +1pp Flash lead at $\kappa = 3$ and 29.65% TV, moving the Flash-minus-Plus gap from −2.03 to +1.00pp.

Figure 4(a) shows this event and two local juice_bottle examples: Anomaly Detection favours Plus and is downweighted, whereas Object Analysis favours Flash and is upweighted. Product-only reweighting applies the same relative multiplier to both tasks within a product and cannot express these opposite task-weight directions. The two cells illustrate local task-weight directions, while all 266 cells determine the scores.

At $\kappa = 3$, six of 12 MMAD winner–challenger pair-settings and six of 12 native all-pairs settings reached a +1pp lead (Table 2). Figure 3 uses the winner–challenger subset, whereas Figure 4(b) compares six native all-pairs events. Each row matches realized TV under separately optimized weights; joint reaches +1pp, whereas restricted spaces do not. All-pairs events describe pair ordering; under the optimized compositions of pairwise-only events, the empirical overall winner remained first (Appendix E).

MMMU reached +1pp on one of six pairs, whereas MVI and MMSI reached none under the primary estimator.

Three-point leads occurred in two winner–challenger MMAD settings and one native all-pairs setting, but in no external pair; no five-point lead was reached. Full first-reach and bootstrap results appear in Appendix E.

Table 2: Joint-space model-choice reachability under the primary estimator at $\kappa = 3$. Minimum TV is shown only for attained +1pp leads. The winner–challenger and native all-pairs scopes overlap but are reported separately. MMSI's +1pp verdict remains estimator-conditional.

Scope	+1pp	$\kappa = 3$ min TV	≥3pp	≥5pp
MMAD winner–challenger (12)	6/12	6.4–29.7%	2/12	0/12
MMAD native all-pairs (12)	6/12	8.3–29.7%	1/12	0/12
MMMU (6 pairs)	1/6	38.1%	0/6	0/6
MVI (6 pairs)	0/6	NR	0/6	0/6
MMSI (6 pairs)	0/6	NR	0/6	0/6

At the same $\kappa = 3$ +1pp endpoint, we ablated the performance-difference surface while retaining each event's original challenger orientation and the full joint weight space. On the frozen descriptive surface, removing residual terms made four of six events unreachable.

The two remaining descriptive comparisons required larger radii: zero-shot MiniMax-M3 minus Kimi-K2.5 increased from 13.1% to 29.7% TV (2.26×), and zero-shot Kimi-K2.5 minus Qwen3.5-Flash from 11.9% to 40.7% (3.42×). Both retained events use the same frozen threshold as their original surfaces, so the increases compare radii to a common endpoint. The frozen residual structure is therefore important to reachability for these events. Appendix G gives the full table.

With pair orientation defined from full-ledger scores, each development fold selected its own stress direction before held-out scoring.

Across the six preselected native all-pairs events, held-out gap effects were +1.2 to +3.8 points, and all six conditional-bootstrap 95% intervals excluded zero. The final challenger gaps were five-fold-averaged point estimates ranging from −0.2 to +0.64 points (Figure 13).

4.4 How Does Composition Affect Confidence-Based Oversight?

Under MMAD's cross-context inspection protocol, joint stress varied both confidence conclusions. At $\kappa = 2$, frozen rules selected in five held-out rotations for 80% development coverage incurred 6.9–9.7 points higher pooled held-out selective risk across all eight model–prompt settings (Figure 5(a)).

Panel (b) shows the corresponding baseline and joint-stressed absolute risks. The exact-C=0.95 diagnostic changed held-out correctness by at least five points in seven settings and appears in Appendix F. The reliability of a confidence-based acceptance rule is therefore conditional on the evaluation mixture.

5 Discussion and Limitations

CCRA treats a benchmark result as conditional evidence under declared composition conditions. A report should state the endpoint, observed support, reweighting space, TV budget, tolerance, estimator, and uncertainty procedure. Score sensitivity concerns one model's movement from the empirical composition, whereas selection requires a final challenger lead that overcomes the baseline gap. Model movements in the same direction can cancel in that gap, so a score may move while the preferred model remains unchanged. For confidence-based oversight, the mixture jointly determines accepted fraction and accepted-error mass, so reliability depends on the composition conditions under which the acceptance rule is evaluated.




Figure 5: Frozen-rule confidence audits on MMAD under the raw primary protocol at joint $\kappa = 2$. Five image-disjoint folds select stress weights and the largest exact-support threshold meeting an 80% development-coverage target, then freeze both before pooled held-out scoring. (a) Paired held-out selective-risk increases with 95% bootstrap intervals across eight model–prompt settings. (b) Baseline (open) and joint-stressed (filled) risks; panel (a) quantifies the paired difference.

Matched TV equalizes shift magnitude, not the directions each space can express. On MMAD, the additive span has 43 effective degrees of freedom and the joint space has 265; their different endpoint reachability therefore does not identify a causal interaction or a necessary mechanism. In six matched-TV events, joint reweighting reached the +1pp challenger lead while restricted spaces did not. This contrast concerns a pairwise endpoint at a common composition, rather than a global model ranking.

These audits are worst-case statements over bounded reweighting of observed cells; they do not extend to unobserved support or estimate how often a shift occurs in deployment. MMSI remained stable in the stated spaces and estimator, while MVI showed a joint-only numerical swap below the +1pp decision margin on a five-degree-of-freedom grid with 102–309 scored responses per model–cell. Evidence covers four API-served MLLMs and one response protocol per benchmark. MMAD supplies the industrial anomaly-detection setting for the oversight audit, which evaluates development-frozen acceptance rules on held-out images. The oversight finding is specific to MMAD's verbalized-confidence setting, and some endpoint calls remain estimator-conditional.

6 Conclusion

Benchmark conclusions depend on the mixture of observed test contexts, even when questions and model outputs remain fixed. CCRA separates score movement, a final challenger lead at a common composition, and confidence-based oversight. It audits bounded composition changes and compares single-axis changes with combined changes at the same realized TV.

On MMAD, the worked case attains a one-point Flash lead only under the combined joint change, while matched single-axis and additive changes do not. Across the audits, score shifts and decision margins had different composition conditions. MMSI spatial-reasoning scores remained within 1.4 percentage points under the primary empirical-Bayes estimator. With development-frozen MMAD acceptance rules, composition stress increased held-out error among accepted answers by 6.9–9.7 percentage points. A CCRA report supplies the endpoint, composition scope, magnitude of change, estimator, and uncertainty procedure needed to interpret a score, selection, or oversight conclusion.

AI use statement

AI assistants were used for experiment scripting, analysis verification, drafting assistance, and vector-diagram editing/export under author direction. Figures 1 and 2 are editable diagrams revised and exported with AI assistance; the industrial illustrations in Figure 1 are schematic vectors, not benchmark photographs. All claims, experimental results, and citations were verified by the authors.

Reproducibility statement

Anonymous supplementary material provides the frozen response ledgers, audit specifications, reproduction guide, and code needed to reproduce the reported analyses.

References

Anastasios N. Angelopoulos and Stephen Bates. Conformal prediction: A gentle introduction. *Foundations and Trends in Machine Learning*, 16(4):494–591, 2023. doi: 10.1561/2200000101.

Huiyi Chen, Jiawei Peng, Dehai Min, Changchang Sun, Kaijie Chen, Yan Yan, Xu Yang, and Lu Cheng. MVI-Bench: A comprehensive benchmark for evaluating robustness to misleading visual inputs in LVLMs. *arXiv preprint arXiv:2511.14159*, 2025.

Mayee F. Chen, Karan Goel, Nimit S. Sohoni, Fait Poms, Kayvon Fatahalian, and Christopher Ré. Mandoline: Model evaluation under distribution shift. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *PMLR*, pp. 1617–1629, 2021.

John C. Duchi, Peter W. Glynn, and Hongseok Namkoong. Statistics of robust optimization: A generalized empirical likelihood approach. *Mathematics of Operations Research*, 46(3):946–969, 2021. doi: 10.1287/moor.2020.1085.

Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman and Hall/CRC, New York, 1993. ISBN 9780412042317.

Ran El-Yaniv and Yair Wiener. On the foundations of noise-free selective classification. *Journal of Machine Learning Research*, 11(53):1605–1641, 2010.

Chris A. Field and A. H. Welsh. Bootstrapping clustered data. *Journal of the Royal Statistical Society: Series B*, 69(3):369–390, 2007. doi: 10.1111/j.1467-9868.2007.00593.x.

Yonatan Geifman and Ran El-Yaniv. Selective classification for deep neural networks. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pp. 1321–1330. PMLR, 2017.

Ursula Hebert-Johnson, Michael P. Kim, Omer Reingold, and Guy Rothblum. Multicalibration: Calibration for the (computationally-identifiable) masses. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pp. 1939–1948. PMLR, 2018.

Zirui Hu, Zheng Zhang, Yingjie Wang, Leszek Rutkowski, and Dacheng Tao. CoFact: Conformal factuality guarantees for language models under covariate shift. In *International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/bd074b828bbd782d4bece89306caff84-Abstract-Conference.html.

Jenny Huang, Yunyi Shen, Dennis Wei, and Tamara Broderick. Dropping just a handful of preferences can change top large language model rankings. In *International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/92d777fb721936613b6444b07c4ffc18-Abstract-Conference.html.

Xi Jiang, Jian Li, Hanqiu Deng, Yong Liu, Bin-Bin Gao, Yifeng Zhou, Jialin Li, Chengjie Wang, and Feng Zheng. MMAD: A comprehensive benchmark for multimodal large language models in industrial anomaly detection. In *International Conference on Learning Representations*, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/hash/d91ffbe9c126765755ff52d36b715683-Abstract-Conference.html.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022. doi: 10.48550/arXiv.2207.05221.

Venelin Kovatchev and Matthew Lease. Benchmark transparency: Measuring the impact of data on evaluation. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics*, pp. 1536–1551, 2024. doi: 10.18653/v1/2024.naacl-long.86.

Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, et al. Holistic evaluation of language models. *Transactions on Machine Learning Research*, 2023. URL https://openreview.net/forum?id=iO4LZibEqW.

Hongseok Namkoong and John C. Duchi. Variance-based regularization with convex objectives. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Joaquin Quiñonero Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D. Lawrence (eds.). *Dataset Shift in Machine Learning*. MIT Press, Cambridge, Massachusetts, 2009. ISBN 9780262170055.

Hamed Rahimian and Sanjay Mehrotra. Frameworks and results in distributionally robust optimization. *Open Journal of Mathematical Optimization*, 3:1–85, 2022. doi: 10.5802/ojmo.15.

Shiori Sagawa, Pang Wei Koh, Tatsunori B. Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=ryxGuJrFvS.

Hidetoshi Shimodaira. Improving predictive inference under covariate shift by weighting the log-likelihood function. *Journal of Statistical Planning and Inference*, 90(2):227–244, 2000. doi: 10.1016/S0378-3758(00)00115-4.

Shivalika Singh, Yiyang Nan, Alex Wang, Daniel Dsouza, Sayash Kapoor, et al. The leaderboard illusion. In *Advances in Neural Information Processing Systems*, volume 38, 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/70a93f260a51123b3c0e33ecd1b4de97-Abstract-Datasets_and_Benchmarks_Track.html.

Charlotte Siska, Katerina Marazopoulou, Melissa Ailem, and James Bono. Examining the robustness of LLM evaluation to the distributional assumptions of benchmarks. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, pp. 10406–10421, 2024. doi: 10.18653/v1/2024.acl-long.560.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *Transactions on Machine Learning Research*, 2023. URL https://openreview.net/forum?id=uyTL5Bvosj.

Masashi Sugiyama, Matthias Krauledat, and Klaus-Robert Müller. Covariate shift adaptation by importance weighted cross validation. *Journal of Machine Learning Research*, 8:985–1005, 2007.

Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu Yao, Chelsea Finn, and Christopher D. Manning. Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 5433–5442, 2023. doi: 10.18653/v1/2023.emnlp-main.330.

Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. Can LLMs express their uncertainty? an empirical evaluation of confidence elicitation in LLMs. In *International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=gjeQKFxFpZ.

Sihan Yang, Runsen Xu, Yiman Xie, Sizhe Yang, Mo Li, Jingli Lin, Chenming Zhu, Xiaochen Chen, Haodong Duan, Xiangyu Yue, Dahua Lin, Tai Wang, and Jiangmiao Pang. Mmsi-bench: A benchmark for multi-image spatial intelligence. In C. Vondrick, B. Hariharan, C. Raffel, L. Pinto, D. Yang, and A. Faust (eds.), *International Conference on Learning Representations*, volume 2026, pp. 157051–157088, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/file/fe5d4bd3e2af823701b5d8f70a3c7602-Paper-Conference.pdf.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, Cong Wei, Bo Yu, Ruibin Yuan, Renliang Sun, Ming Yin, Boyuan Zheng, Zengzhu Yang, Yibo Liu, Wenhao Huang, Huan Sun, Yu Su, and Wenhu Chen. MMMU: A massive multi-discipline multimodal understanding and reasoning benchmark for expert AGI. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

A Benchmarks, Models, Prompts, and Missingness

MMAD snapshot and collection. The primary audit uses the released MMAD snapshot (Jiang et al., 2025), comprising 8,366 images and 39,670 multiple-choice questions across 38 products and seven inspection tasks (266 cells observed). The frozen ledger contains 380,631 scored responses from the HTTP APIs of four MLLMs (`qwen3.5-plus`, `qwen3.5-flash`, `kimi/kimi-k2.5`, `MiniMax/MiniMax-M3`; provider-side versions are those served during the 2026-07-23–25 collection window). All requests were single-turn, thinking disabled, temperature 0, at most 200 completion tokens, under the `independent_v2` protocol in zero-shot and reference-conditioned one-shot variants, under two image protocols (native confirmatory; compressed-1024 sensitivity). Collection gates: request-failure $\leq$ 1%, parse-failure $\leq$ 1%, invalid-choice $\leq$ 0.5%, answer coverage $\geq$ 99%, confidence coverage $\geq$ 95%, zero thinking violations; the realized ledger has zero duplicate keys and 99.995% confidence coverage.

External panel. MMSI-Bench (Yang et al., 2026) contributes 1,000 questions (11 question types $\times$ 3 difficulty levels, 33 cells; option order deterministically shuffled per question), MVI-Bench (Chen et al., 2025) 1,248 questions (3 visual levels $\times$ 2 conditions, 6 dense cells), and the multiple-choice subset of MMMU validation (Yue et al., 2024) 847 questions (6 disciplines $\times$ 3 difficulty levels, 18 cells; 53 open questions excluded). The panel was collected under one zero-shot JSON answer-plus-confidence protocol with compressed ($\leq$1024 px) images and manifests locked before collection; because the panel cells number fewer than 40 per benchmark, panel results carry a framework-generality role rather than confirmatory weight for the panel benchmarks themselves.

Worked-case input and cell scope. Figure 7 supplies the original full inputs behind the two illustrative cells in Figure 4. The frozen ledger preserves model correctness indicators for these inputs, not answer text, so the case does not diagnose individual errors. The label-layout question is one example, rather than a summary of the 282 questions in the canonical Object Analysis cell. From rounded archived weight changes, the juice_bottle Anomaly Detection and Object Analysis cell terms contribute approximately 0.06638 and 0.04406 points, respectively, to the Flash-minus-Plus gap movement. Their approximately 0.11044-point total is only a partial contribution to the 3.02957-point movement computed over all 266 cells.

Missingness and denominators. Provider-side input rejections (HTTP code 1026, issued before model inference and deterministic on retry) remove a small fraction of MiniMax responses: 5 (0.50%) on MMSI, 3 (0.24%) on MVI, and 16 (1.89%) on MMMU. The MMMU rate exceeds the preregistered 1% gate and is disclosed; all rejected items fall in large cells that retain full support from the other three models. Cell support averages the four models, so refusals slightly shrink the affected cells for every pair, including pairs not involving MiniMax; the shrinkage is far below the reported effects. MMAD model comparisons use common-complete questions within each setting.



(a) MMAD

Product × task

Q: Is there any defect in the object?

A: Yes. B: No.

Gold: A | Bottle × Anomaly Detection

(b) MMSI-Bench

Question type × difficulty



Image 1


Image 2

Q: The images are taken continuously from a first-person perspective. In which direction are you moving?

A: Left while moving backward
B: Forward to the left
C: Forward to the right
D: Right while moving backward

Gold: C | Camera motion × Medium

(c) MVI-Bench




Level × condition

Q: What is in the picture?

A: Bread
B: Hat
C: Cake
D: Bag

Gold: B | Visual Concept × Misleading



(d) MMMU-Val

Discipline × difficulty

Q: What is part B in the figure? <image 1>

A: Sheath
B: Viral genome
C: Capsid
D: Tail Fibers

Gold: B | Science × Medium

Figure 6: Representative VQA input formats across the audited benchmarks. MMAD crosses products and inspection tasks; MMSI uses multiple images; MVI uses one image; and MMMU uses one or multiple images with two to nine answer options. Gold answers are retained only for scoring and are never supplied to the models. Each item belongs to a fixed two-axis cell; CCRA changes only that cell's aggregate evaluation weight, so these examples are not effect evidence.

Original MMAD questions for the two illustrated inputs

a Anomaly Detection · juice bottle



Is there any defect in the object?

A. Yes.

B. No.

Gold: A

Task: Anomaly Detection

b Object Analysis · juice bottle



What is the layout of the label on the bottle?

A. The label is centered on the bottle.

B. The label is placed on the top half of the bottle.

C. The label covers the entire bottle.

D. The label is placed on the bottom half of the bottle.

Gold: A

Task: Object Structure

Figure 7: Original full inputs for the two juice_bottle cells illustrated in Figure 4: native images, their complete multiple-choice questions and options, and gold answers used for scoring. The defect item maps directly to Anomaly Detection. The label-layout item was recorded under Object Structure and maps to the canonical Object Analysis task, which aggregates raw Analysis, Details, and Structure questions. These are two inputs, not all questions in either cell.

B Mathematical Formulation and Optimization

Spaces, nesting, and dimensions. Product-only reweighting multiplies each product's mass by a factor while preserving the task mixture within each product (38 factors, 37 d.f.); task-only is symmetric (7 factors, 6 d.f.). The joint space assigns a weight to each observed cell (266 weights, 265 d.f.). The concurrent additive span, its dimension accounting, and the accompanying additive-control results follow.

Definition and nesting. The control space is $\mathcal{W}^{P+T} = \{w : w_{pt}/w^0_{pt} = 1 + \alpha_p + \beta_t\}$, the smallest affine density-ratio subspace containing both marginal audit directions: product-only ratios depend on p alone and task-only ratios on t alone, and their affine span around $d = 1$ is exactly $1 + \alpha_p + \beta_t$. Hence $\mathcal{W}_\kappa(\mathcal{W}^P), \mathcal{W}_\kappa(\mathcal{W}^T) \subset \mathcal{W}_\kappa(\mathcal{W}^{P+T}) \subset \mathcal{W}_\kappa(\mathcal{W}^{PT})$, so the sandwich inequality $\rho_{\text{joint}} \leq \rho_{\text{add}} \leq \min(\rho_P, \rho_T)$ must hold in every setting. Product-only reweighting is the exact degeneration $\beta_t \equiv b$ (a single constant), and task-only the degeneration $\alpha_p \equiv a$. Counting parameters, $38 + 7 = 45$ coefficients lose one degree of freedom to the simplex equality and one to the translation redundancy $(\alpha_p + c,\ \beta_t - c)$, leaving 43 effective degrees of freedom.

Parameterization choice. Unlike the log-linear raking/IPF family, $\log d_{pt} = a_p + b_t$, the affine form is defined by closure of the audited marginal directions within the existing audit contract, which keeps every audit question a single linear program (below). In this parameterization, product and task adjustments sum as $1 + \alpha_p + \beta_t$, with no additional cell-specific adjustment. Slice-based density-ratio evaluation similarly builds low-dimensional shift representations on known axes (Chen et al., 2021); the present control spans the two marginal reweighting families exactly.

Linear programs. With variables $\theta = (\alpha, \beta) \in \mathbb{R}^{45}$ and auxiliaries $u \in \mathbb{R}^{266}_{\geq 0}$ encoding $u_g \geq w^0_g |\alpha_{p(g)} + \beta_{t(g)}|$, all constraints are linear: the simplex equality $\sum_g w^0_g(\alpha + \beta) = 0$; the common per-cell box $\kappa^{-1} \leq 1 + \alpha_p + \beta_t \leq \kappa$; the TV cap $\sum_g u_g \leq 2\tau$; and the prespecified +1pp decision inequality $\sum_g w^0_g\,(\widehat{a}_{jg} - \widehat{a}_{m^\star g})\,(\alpha + \beta) \geq \delta - \sum_g w^0_g(\widehat{a}_{jg} - \widehat{a}_{m^\star g})$. The minimum-TV radius is the single LP $\min \frac{1}{2}\sum_g u_g$ subject to the decision inequality; matched-TV maxima and the confidence-endpoint extrema (Dinkelbach iterations over the same polytope) are likewise single LPs solved by HiGHS.

Model-choice ladder (12 pair–prompt settings). The additive control reaches the numerical flip (gap ≥ 0) in 3/12 settings—one-shot Qwen3.5-Flash vs. Qwen3.5-Plus (first $\kappa = 2$, minimum TV 9.00% under this control experiment's parameterization; the unified-estimator matched-TV ladder of Table 7 first crosses zero for this event at TV 10.87%) and the zero-shot flips MiniMax-M3 vs. Kimi-K2.5 and Kimi-K2.5 vs. Qwen3.5-Flash ($\kappa = 3$, TV 20.95% and 20.52%); in each of these settings the best marginal space also flips, so the additive span adds no new flip setting. The +1pp challenger lead is reached in 0/12 settings (best challenger gap +0.68 points at $\kappa = 3$), while the joint space reaches all six published events at matched realized TV with joint-over-additive envelope advantages of 1.00–2.30 points. On the standard matched-TV grid the ordering joint > additive ≥ best marginal holds at every audited point. Supporting results are provided in the supplementary archive.

Bootstrap (symmetric evidence standard). All twelve settings were re-solved in 1,000 image-cluster replicates with per-replicate derived seeds. The additive +1pp endpoint is unreachable in 9/12 settings and reachable in at most 39% of replicates at $\kappa = 3$ in the remaining three (387/1000 one-shot Flash/Plus; 294/1000 and 258/1000 zero-shot Kimi pairs); these three point-estimate-NR settings are therefore reported as point-estimate descriptive with bootstrap reachability disclosed. The joint-space control reaches its published events in 981–1,000 of 1,000 replicates. Flip-level instability is bootstrap-robust (991–1,000 of 1,000 at the first reachable bound; Table 9).

Confidence endpoints. Strict matched-TV envelopes ($\kappa = 2$; TV $\in \{2\%, 5\%, 10\%, 33.21\%\}$, raw estimator): the ordering joint > additive ≥ best marginal holds in 72/72 grid rows, with joint-over-additive advantages of +0.46 to +4.08 points and additive-over-best-marginal at most +1.04 points. Development-selected frozen additive objects (five image-disjoint folds, thresholds from the 80% development-coverage rule, frozen weights, held-out scoring, 1,000-replicate frozen-object bootstrap

with the same draw sequence as the joint side) shift held-out exact-0.95 correctness by −7.91 to +5.98 points and frozen-rule selective risk by +3.77 to +6.98 points, every 95% interval excluding zero and all five folds agreeing in sign—below the corresponding joint stress in fifteen of the sixteen endpoint-settings; the remaining zero-shot mapping setting (Qwen3.5-Plus) exceeds the joint magnitude in absolute value because each space selects its own extremizing direction on development folds, so held-out magnitudes are not ordered across spaces.

Interpretation boundary. The joint space has roughly 222 more cell-level directions than the 43-degree-of-freedom additive span. The observed endpoint difference is therefore scoped to reachability in these declared spaces; it does not identify a causal interaction or establish a necessary mechanism.

Solvers and validation. All audits reduce to linear or linear-fractional programs solved by HiGHS in a θ-space formulation with feasibility tolerance 10^{-10}; total-variation caps enter as linear constraints and the Dinkelbach scheme handles ratio endpoints. Independent parameterizations reproduced all optimization results within numerical tolerance, and all nesting and monotonicity checks passed; the full validation log accompanies the anonymized code.

C Estimation and Statistical Inference

Estimators. The primary cell-accuracy estimator is a per-model empirical-Bayes beta–binomial posterior mean, with prior hyperparameters estimated once by marginal maximum likelihood on the frozen ledger and held fixed throughout, including inside every bootstrap replicate. Unshrunk cell means and a common $\mathrm{Beta}(1,1)$ posterior are preregistered sensitivity estimators for every event endpoint.

Bootstrap object indexing. Radii are re-solved in 1,000 product-stratified image-cluster bootstrap replicates: cell sufficient statistics and baseline mass are re-estimated per replicate, the audited pair orientation and prior hyperparameters stay fixed, and seeds derive deterministically from the setting index and replicate number. Confidence replicates instead resample held-out images and score frozen objects without re-optimization, so radius intervals describe the stability of a re-solved boundary while confidence intervals describe held-out evaluation of a frozen object. Three pairwise settings have nonzero bootstrap reachability for the +1pp endpoint under the additive space (387, 294, and 258 of 1,000) and are reported as point-estimate descriptive under the preregistered downgrade rule. Bootstrap reachability spans refer to three distinct event sets, kept explicit throughout: the joint winner-pair audit reaches both headline native events in 1,000 of 1,000 replicates at their first-reach bounds; the pairwise-only joint events span 986–1,000 (Table 11); and within the additive-control experiment, the joint-space control spans 981–1,000 across its published events (additive flip-level spans are 991–1,000; Table 9).

Development–held-out protocol. Confidence endpoints use five image-disjoint folds. Four development folds select joint stress weights at $\kappa = 2$ and the largest exact-support threshold meeting the 80% development-coverage target; weights and thresholds are frozen before the remaining fold is scored. For the oversight endpoint, each held-out cell rate is weighted by its frozen development baseline mass and stress absolute cell mass; the five folds' weighted numerators and denominators are then summed before their ratio is formed. This pooling differs from direct raw-count pooling. Exact-C=0.95 support is substantial: 5,801–36,450 responses from 3,973–8,366 independent images per setting.

D Complete Score-Shift Results

Table 3 reports single-model envelopes and Table 4 the full 1/3/5/10-point radius table underlying Figure 3; both cover all four benchmarks under the joint space at $\kappa = 3$ with the primary estimator. Figures 8 and 9 show the TV-budget attainability curves at $\kappa = 3$ for MMAD's native settings and for the external panel. MMAD's 49 benchmark-internal scenario compositions comprise the empirical mixture, 45 leave-one-product or leave-one-task mixtures, and three uniformized alternatives; their median TV is 2.5%. The 45 leave-one-out mixtures assign zero mass to some observed cells and therefore violate the positive floor at finite κ; they remain an internal TV-scale reference, not Figure 3 audit lines. Machine-readable versions of every grid—all four MMAD prompt–image settings, the three structured subspaces, all κ, and all three estimators—are included in the supplementary archive.

Table 3: Single-model score envelopes under joint reweighting at $\kappa = 3$ (primary estimator): largest attainable absolute change in reported accuracy. Envelope extremes require TV near the box cap (≈0.5); the practically meaningful quantities are the radii of Table 4. MMAD rows span the four model–prompt–image settings.

Benchmark	Model	Max $\lvert\Delta A_m\rvert$ (pp)
MVI	MiniMax-M3	16.0
MVI	Kimi-K2.5	10.2
MVI	Qwen3.5-Flash	13.8
MVI	Qwen3.5-Plus	13.6
MMMU	MiniMax-M3	10.0
MMMU	Kimi-K2.5	8.7
MMMU	Qwen3.5-Flash	10.9
MMMU	Qwen3.5-Plus	6.2
MMSI	MiniMax-M3	1.4
MMSI	Kimi-K2.5	1.3
MMSI	Qwen3.5-Flash	0.0
MMSI	Qwen3.5-Plus	0.7
MMAD (one-shot/c1024)	MiniMax-M3	12.4
MMAD (one-shot/c1024)	Kimi-K2.5	10.3
MMAD (one-shot/c1024)	Qwen3.5-Flash	11.2
MMAD (one-shot/c1024)	Qwen3.5-Plus	10.5
MMAD (one-shot/native)	MiniMax-M3	13.7
MMAD (one-shot/native)	Kimi-K2.5	10.7
MMAD (one-shot/native)	Qwen3.5-Flash	11.8
MMAD (one-shot/native)	Qwen3.5-Plus	11.1
MMAD (zero-shot/c1024)	MiniMax-M3	14.1
MMAD (zero-shot/c1024)	Kimi-K2.5	12.7
MMAD (zero-shot/c1024)	Qwen3.5-Flash	13.4
MMAD (zero-shot/c1024)	Qwen3.5-Plus	11.7
MMAD (zero-shot/native)	MiniMax-M3	14.6
MMAD (zero-shot/native)	Kimi-K2.5	14.3
MMAD (zero-shot/native)	Qwen3.5-Flash	14.1
MMAD (zero-shot/native)	Qwen3.5-Plus	12.7

Table 4: Minimum total variation required to move a single model's reported score by t points (joint space, $\kappa = 3$, primary estimator; range over models and settings). Parenthesized counts give reachable model–setting combinations out of those audited; n.r. = not reachable within the audited bound. All four t values belong to the follow-up effect-size analysis.

	Minimum TV (%) for a t-point shift			
Benchmark	t=1	t=3	t=5	t=10
MMAD (4 settings)	1.4–2.1 (16/16)	4.9–7.2 (16/16)	9.1–13.5 (16/16)	22.3–42.3 (16/16)
MVI	2.2–3.6 (4/4)	6.6–10.7 (4/4)	11.0–17.9 (4/4)	22.7–43.8 (4/4)
MMMU	2.8–3.7 (4/4)	8.8–13.6 (4/4)	15.0–27.3 (4/4)	40.0–40.0 (1/4)
MMSI	23.8–28.5 (2/4)	n.r. (0/4)	n.r. (0/4)	n.r. (0/4)

Table 5: Selection-ladder reachability at $\kappa = 3$ (primary estimator). Each cell counts reachable pairs out of those audited in the joint space; "(k sub)" marks that k pairs are also reachable in some subspace; in the +1pp column this happens only in compressed-image settings (scope note in Appendix E). ≥0pp is the numerical swap; ≥1pp is the prespecified practical reversal. MMAD rows use the three winner–challenger pairs across four prompt–image settings. The 3/5/10pp rungs are the follow-up effect-size analysis.

	Challenger lead reached (joint; any subspace)				
Setting	≥0pp	≥1pp	≥3pp	≥5pp	≥10pp
MMAD (one-shot/c1024)	2/3 (1 sub)	2/3 (1 sub)	1/3	0/3	0/3
MMAD (one-shot/native)	2/3 (1 sub)	1/3	0/3	0/3	0/3
MMAD (zero-shot/c1024)	2/3 (1 sub)	2/3	1/3	0/3	0/3
MMAD (zero-shot/native)	2/3	1/3	0/3	0/3	0/3
MVI	1/6	0/6	0/6	0/6	0/6
MMMU	3/6	1/6	0/6	0/6	0/6
MMSI	2/6 (2 sub)	0/6	0/6	0/6	0/6




Figure 8: TV-budget attainability curves for MMAD's confirmatory native settings at $\kappa = 3$ (left column: largest single-model score movement; right column: largest challenger lead in the winner–challenger scope). Dotted horizontal lines mark the 1/3/5/10-point reference levels; in the right column, dashed lines additionally mark the zero numerical-swap level and the prespecified +1pp decision margin. Curves flatten at their envelope values.




Figure 9: TV-budget attainability curves for the external zero-shot panel (MMSI, MVI, MMMU), as in Figure 8; restricted-space curves use each benchmark's composition axes (type–difficulty for MMSI, discipline–difficulty for MMMU, and level–condition for MVI). Machine-readable versions of every grid are included in the supplementary archive.

E Complete Model-Selection Results

Table 5 gives the full selection-ladder reachability grid by setting. Table 6 reports four-space $\kappa = 3$ box maxima for all twelve MMAD pair–prompt settings on a single estimator, verifying nesting in every row; Table 10 reports first-reach bounds and radii for the complete all-pairs audit; Table 7 the full matched-TV ladder; Table 9 the additive-space bootstrap verdicts; and Table 11 the joint-side pairwise events. Evaluating all models under the pair-optimal compositions of the pairwise-only events—those not involving the empirical winner—leaves the empirical winner ranked first throughout, so those events carry zero selection regret.

MMAD retains two distinct 12-pair-setting scopes: three winner–challenger pairs across four prompt–image settings, and all six pairs on native images only. Figure 10 reports the winner–challenger first-reach results, including radius-bootstrap intervals only for the two native headline events. The native all-pairs scope reaches six +1pp events and one ≥3pp event (zero-shot MiniMax-M3 over Kimi-K2.5, joint box maximum +3.41 points from a −2.27 baseline; Table 10).




Figure 10: First-reach results for the six MMAD winner–challenger +1pp events across prompt and image settings. The two native headline events carry 95% intervals; the remaining entries are first-reach point estimates.

Table 6: Four-space $\kappa = 3$ box maxima (challenger-minus-pairwise-baseline gap, pp) recomputed on the single joint-pivot empirical-Bayes ledger. Pairs are listed challenger vs. the baseline-higher model. Nesting holds in every row: additive ≥ best marginal and joint ≥ additive (12/12 each).

Prompt	Pair	Product	Task	Additive	Joint
One-shot	MiniMax-M3 vs. Kimi-K2.5	-2.43	-2.16	-2.16	+0.12
One-shot	MiniMax-M3 vs. Flash	-5.09	-4.50	-4.50	-2.22
One-shot	MiniMax-M3 vs. Plus	-5.37	-4.62	-4.62	-2.72
One-shot	Kimi-K2.5 vs. Flash	-0.21	-0.54	-0.21	+2.18
One-shot	Kimi-K2.5 vs. Plus	-1.08	-1.27	-1.08	+0.98
One-shot	Flash vs. Plus	+0.68	-0.10	+0.68	+2.90
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	+0.62	+0.29	+0.62	+3.41
Zero-shot	MiniMax-M3 vs. Flash	-0.89	-1.61	-0.89	+1.60
Zero-shot	MiniMax-M3 vs. Plus	-3.81	-4.10	-3.76	-1.67
Zero-shot	Kimi-K2.5 vs. Flash	+0.57	-0.30	+0.57	+2.75
Zero-shot	Kimi-K2.5 vs. Plus	-1.40	-1.78	-1.40	+0.34
Zero-shot	Flash vs. Plus	-0.42	-1.16	-0.42	+1.35

Table 7: Model-choice matched-TV ladder (one-shot), part 1 of 2: challenger gap (pp) at equal realized TV (active within 10^{-8}) for the four spaces, with the joint-over-additive difference. Standard grid plus every joint-reachable event radius. Pairs are listed challenger vs. the baseline-higher model.

Prompt	Pair	κ	TV (%)	Product	Task	Additive	Joint	J−A
One-shot	MiniMax-M3 vs. Kimi-K2.5	2.0	2.00	-4.77	-4.82	-4.74	-4.23	+0.51
One-shot	MiniMax-M3 vs. Kimi-K2.5	2.0	5.00	-4.50	-4.55	-4.37	-3.57	+0.80
One-shot	MiniMax-M3 vs. Kimi-K2.5	2.0	10.00	-4.13	-4.13	-3.75	-2.77	+0.98
One-shot	MiniMax-M3 vs. Kimi-K2.5	3.0	40.55	-2.53	-2.22	-2.16	+0.00	+2.16
One-shot	MiniMax-M3 vs. Flash	2.0	2.00	-6.69	-6.76	-6.68	-6.29	+0.40
One-shot	MiniMax-M3 vs. Flash	2.0	5.00	-6.44	-6.51	-6.40	-5.67	+0.73
One-shot	MiniMax-M3 vs. Flash	2.0	10.00	-6.14	-6.18	-5.94	-4.95	+0.99
One-shot	MiniMax-M3 vs. Plus	2.0	2.00	-7.21	-7.28	-7.21	-6.76	+0.45
One-shot	MiniMax-M3 vs. Plus	2.0	5.00	-6.97	-7.01	-6.90	-6.16	+0.74
One-shot	MiniMax-M3 vs. Plus	2.0	10.00	-6.67	-6.60	-6.41	-5.44	+0.96
One-shot	Kimi-K2.5 vs. Flash	2.0	2.00	-1.73	-1.79	-1.73	-1.33	+0.40
One-shot	Kimi-K2.5 vs. Flash	2.0	5.00	-1.49	-1.59	-1.47	-0.85	+0.62
One-shot	Kimi-K2.5 vs. Flash	2.0	10.00	-1.20	-1.38	-1.20	-0.26	+0.94
One-shot	Kimi-K2.5 vs. Flash	2.0	13.02	-1.07	-1.28	-1.06	-0.00	+1.06
One-shot	Kimi-K2.5 vs. Flash	3.0	9.33	-1.16	-1.34	-1.14	+0.00	+1.14
One-shot	Kimi-K2.5 vs. Flash	3.0	18.69	-0.67	-1.01	-0.65	+1.00	+1.65
One-shot	Kimi-K2.5 vs. Plus	2.0	2.00	-2.31	-2.36	-2.31	-1.98	+0.33
One-shot	Kimi-K2.5 vs. Plus	2.0	5.00	-2.13	-2.19	-2.11	-1.53	+0.58
One-shot	Kimi-K2.5 vs. Plus	2.0	10.00	-1.90	-2.02	-1.87	-1.02	+0.85
One-shot	Kimi-K2.5 vs. Plus	3.0	17.68	-1.55	-1.76	-1.50	-0.00	+1.50
One-shot	Flash vs. Plus	1.25	4.21	-0.34	-0.45	-0.34	+0.00	+0.34
One-shot	Flash vs. Plus	1.5	2.81	-0.36	-0.46	-0.36	-0.00	+0.36
One-shot	Flash vs. Plus	2.0	2.00	-0.39	-0.48	-0.39	-0.05	+0.33
One-shot	Flash vs. Plus	2.0	2.28	-0.37	-0.47	-0.37	-0.00	+0.37
One-shot	Flash vs. Plus	2.0	5.00	-0.23	-0.39	-0.23	+0.40	+0.63
One-shot	Flash vs. Plus	2.0	10.00	-0.03	-0.33	-0.03	+0.93	+0.96
One-shot	Flash vs. Plus	2.0	10.87	+0.00	-0.32	+0.00	+1.00	+1.00
One-shot	Flash vs. Plus	3.0	2.00	-0.38	-0.48	-0.38	+0.00	+0.38
One-shot	Flash vs. Plus	3.0	8.32	-0.03	-0.30	-0.03	+1.00	+1.03

Table 8: Model-choice matched-TV ladder (zero-shot), part 2 of 2. Across both parts, the six +1-pp joint events span joint-over-additive advantages of 0.9971–2.2964 pp. Pairs are listed challenger vs. the baseline-higher model.

Prompt	Pair	κ	TV (%)	Product	Task	Additive	Joint	J−A
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	2.0	9.73	-1.18	-1.35	-1.12	+0.00	+1.12
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	2.0	21.38	-0.62	-0.93	-0.52	+1.00	+1.52
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	3.0	2.00	-2.00	-2.07	-2.00	-1.40	+0.60
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	3.0	5.00	-1.62	-1.75	-1.57	-0.51	+1.06
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	3.0	7.27	-1.36	-1.50	-1.26	+0.00	+1.26
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	3.0	10.00	-1.06	-1.27	-0.97	+0.52	+1.48
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	3.0	13.14	-0.73	-1.03	-0.66	+1.00	+1.66
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	3.0	20.00	-0.19	-0.67	-0.08	+1.84	+1.92
Zero-shot	MiniMax-M3 vs. Flash	3.0	2.00	-3.64	-3.83	-3.64	-3.10	+0.54
Zero-shot	MiniMax-M3 vs. Flash	3.0	5.00	-3.29	-3.60	-3.29	-2.14	+1.15
Zero-shot	MiniMax-M3 vs. Flash	3.0	10.00	-2.80	-3.23	-2.78	-1.09	+1.69
Zero-shot	MiniMax-M3 vs. Flash	3.0	17.69	-2.15	-2.67	-2.00	+0.00	+2.00
Zero-shot	MiniMax-M3 vs. Flash	3.0	20.00	-1.99	-2.50	-1.82	+0.26	+2.08
Zero-shot	MiniMax-M3 vs. Flash	3.0	29.04	-1.46	-2.10	-1.30	+1.00	+2.30
Zero-shot	MiniMax-M3 vs. Plus	3.0	2.00	-5.70	-5.86	-5.70	-5.24	+0.46
Zero-shot	MiniMax-M3 vs. Plus	3.0	5.00	-5.34	-5.64	-5.33	-4.51	+0.82
Zero-shot	MiniMax-M3 vs. Plus	3.0	10.00	-4.97	-5.29	-4.90	-3.65	+1.25
Zero-shot	MiniMax-M3 vs. Plus	3.0	20.00	-4.46	-4.64	-4.10	-2.62	+1.47
Zero-shot	Kimi-K2.5 vs. Flash	2.0	7.85	-0.89	-1.28	-0.89	+0.00	+0.89
Zero-shot	Kimi-K2.5 vs. Flash	2.0	23.22	-0.34	-0.81	-0.33	+1.00	+1.33
Zero-shot	Kimi-K2.5 vs. Flash	3.0	2.00	-1.41	-1.59	-1.41	-0.90	+0.51
Zero-shot	Kimi-K2.5 vs. Flash	3.0	5.00	-1.02	-1.43	-1.02	-0.14	+0.88
Zero-shot	Kimi-K2.5 vs. Flash	3.0	5.66	-0.95	-1.39	-0.95	-0.00	+0.95
Zero-shot	Kimi-K2.5 vs. Flash	3.0	10.00	-0.57	-1.16	-0.57	+0.76	+1.34
Zero-shot	Kimi-K2.5 vs. Flash	3.0	11.90	-0.46	-1.06	-0.46	+1.00	+1.46
Zero-shot	Kimi-K2.5 vs. Flash	3.0	20.00	-0.04	-0.76	-0.03	+1.76	+1.79
Zero-shot	Kimi-K2.5 vs. Plus	3.0	2.00	-3.45	-3.58	-3.45	-3.01	+0.45
Zero-shot	Kimi-K2.5 vs. Plus	3.0	5.00	-3.17	-3.37	-3.16	-2.38	+0.79
Zero-shot	Kimi-K2.5 vs. Plus	3.0	10.00	-2.74	-3.02	-2.72	-1.64	+1.08
Zero-shot	Kimi-K2.5 vs. Plus	3.0	20.00	-2.12	-2.46	-1.94	-0.68	+1.26
Zero-shot	Kimi-K2.5 vs. Plus	3.0	31.60	-1.67	-2.04	-1.48	+0.00	+1.48
Zero-shot	Flash vs. Plus	2.0	21.66	-1.08	-1.58	-1.08	+0.00	+1.08
Zero-shot	Flash vs. Plus	3.0	2.00	-1.84	-1.98	-1.84	-1.40	+0.44
Zero-shot	Flash vs. Plus	3.0	5.00	-1.61	-1.91	-1.61	-0.84	+0.77
Zero-shot	Flash vs. Plus	3.0	10.00	-1.29	-1.79	-1.29	-0.21	+1.08
Zero-shot	Flash vs. Plus	3.0	12.17	-1.18	-1.74	-1.18	+0.00	+1.18
Zero-shot	Flash vs. Plus	3.0	20.00	-0.91	-1.58	-0.90	+0.55	+1.45
Zero-shot	Flash vs. Plus	3.0	29.65	-0.67	-1.40	-0.66	+1.00	+1.66

Table 9: Additive-space bootstrap verdicts (1,000 image-cluster replicates per setting, re-estimated and re-solved). Reversal column is the maximum reachability across the κ grid with the attaining bound. The three settings with nonzero reversal reachability are reported as point-estimate descriptive per the preregistered downgrade rule.

Prompt	Pair	Point flip	Flip reach.	Reversal reach.	At
One-shot	MiniMax-M3 vs. Kimi-K2.5	no	0/1000	0/1000	–
One-shot	MiniMax-M3 vs. Flash	no	0/1000	0/1000	–
One-shot	MiniMax-M3 vs. Plus	no	0/1000	0/1000	–
One-shot	Kimi-K2.5 vs. Flash	no	499/1000	0/1000	–
One-shot	Kimi-K2.5 vs. Plus	no	1/1000	0/1000	–
One-shot	Flash vs. Plus	yes	1000/1000	387/1000	$\kappa = 3$
Zero-shot	MiniMax-M3 vs. Kimi-K2.5	yes	991/1000	294/1000	$\kappa = 3$
Zero-shot	MiniMax-M3 vs. Flash	no	8/1000	0/1000	–
Zero-shot	MiniMax-M3 vs. Plus	no	0/1000	0/1000	–
Zero-shot	Kimi-K2.5 vs. Flash	yes	997/1000	258/1000	$\kappa = 3$
Zero-shot	Kimi-K2.5 vs. Plus	no	0/1000	0/1000	–
Zero-shot	Flash vs. Plus	no	146/1000	0/1000	–

Table 10: Complete all-pairs model-choice audit: first density-ratio bound and its minimum TV at which each endpoint becomes reachable (NR = not reached within $\kappa \leq 3$). Pairs are listed challenger > pairwise baseline, with the challenger-minus-baseline gap in points; model names are shortened (Flash/Kimi/MiniMax/Plus). Joint reaches the +1-point reversal in 2/6 one-shot and 4/6 zero-shot pairs; neither marginal space reaches it for any pair.

Prompt	Pair	Gap	P flip	T flip	J flip	P rev.	T rev.	J rev.
One-shot	MiniMax-M3 > Kimi-K2.5	-4.99	NR	NR	κ3@40.6	NR	NR	NR
One-shot	Kimi-K2.5 > Flash	-1.93	NR	NR	κ2@13.0	NR	NR	κ3@18.7
One-shot	Kimi-K2.5 > Plus	-2.47	NR	NR	κ3@17.7	NR	NR	NR
One-shot	MiniMax-M3 > Flash	-6.92	NR	NR	NR	NR	NR	NR
One-shot	MiniMax-M3 > Plus	-7.46	NR	NR	NR	NR	NR	NR
One-shot	Flash > Plus	-0.54	κ2@10.5	NR	κ1.25@4.2	NR	NR	κ2@10.9
Zero-shot	MiniMax-M3 > Kimi-K2.5	-2.27	κ3@23.0	κ3@35.5	κ2@9.7	NR	NR	κ2@21.4
Zero-shot	Kimi-K2.5 > Flash	-1.70	κ3@20.6	NR	κ2@7.9	NR	NR	κ2@23.2
Zero-shot	Kimi-K2.5 > Plus	-3.73	NR	NR	κ3@31.6	NR	NR	NR
Zero-shot	MiniMax-M3 > Flash	-3.98	NR	NR	κ3@17.7	NR	NR	κ3@29.0
Zero-shot	MiniMax-M3 > Plus	-6.00	NR	NR	NR	NR	NR	NR
Zero-shot	Flash > Plus	-2.03	NR	NR	κ2@21.7	NR	NR	κ3@29.7

Table 11: Radius bootstrap for the four pairwise-only joint reversal events (1,000 image-cluster replicates; cell statistics and baseline mass re-estimated and the radius re-solved per replicate; the pairwise orientation and empirical-Bayes hyperparameters stay fixed, and the pair orientation is never re-selected). Replicates give the TV radius distribution of each re-solved decision boundary. Pairs are listed challenger > pairwise baseline, as in Table 10.

Prompt	Event	Bound	Point TV (%)	Reachable	Median TV (%)	[2.5%, 97.5%]
One-shot	Kimi-K2.5 > Flash	κ3	18.69	1000/1000	14.98	[11.46, 19.29]
Zero-shot	MiniMax-M3 > Kimi-K2.5	κ2	21.38	989/1000	16.69	[11.93, 24.94]
Zero-shot	Kimi-K2.5 > Flash	κ2	23.22	986/1000	15.77	[10.85, 24.36]
Zero-shot	MiniMax-M3 > Flash	κ3	29.04	998/1000	22.96	[17.69, 30.87]

F Confidence and Oversight Results

Table 12: Confidence matched-TV ladder medians (pp) at $\kappa = 2$: joint-over-additive, additive-over-best-marginal, and joint-over-best-marginal. Medians over 8 model–prompt settings per row; the full 72 standard-grid rows satisfy joint > additive ≥ best marginal, with joint-over-additive +0.46 to +4.08 pp and additive-over-marginal at most +1.04 pp (`confidence_matched_tv_ladder.csv`).

Endpoint	Direction	TV (%)	J−A	A−M	J−M
Exact-0.95 mapping	max	2	+0.86	+0.03	+0.88
Exact-0.95 mapping	max	5	+1.39	+0.12	+1.56
Exact-0.95 mapping	max	10	+1.53	+0.48	+1.97
Exact-0.95 mapping	min	2	+1.07	+0.03	+1.08
Exact-0.95 mapping	min	5	+1.75	+0.16	+1.84
Exact-0.95 mapping	min	10	+2.36	+0.45	+2.84
Frozen-rule risk	max	2	+0.64	+0.05	+0.68
Frozen-rule risk	max	5	+1.20	+0.19	+1.44
Frozen-rule risk	max	10	+1.53	+0.63	+2.22

Table 13: Development-selected, frozen audit objects: pooled held-out effects (pp) with 95% image-cluster intervals (1,000 fixed-object replicates). Additive objects shift both endpoints materially (all intervals exclude zero, 5/5 folds agree in sign); because each space selects its own extremizing direction on development folds, held-out magnitudes are not ordered across spaces – additive sits below the joint stress in 15/16 endpoint-settings and above it (in magnitude) for Qwen3.5-Plus zero-shot mapping (−6.40 vs. +4.37).

Model	Prompt	Endp.	Additive	95% CI	Joint
Qwen3.5-Plus	One-shot	map	+4.05	(+3.83, +4.26)	-6.65
Qwen3.5-Plus	One-shot	risk	+4.19	(+3.94, +4.43)	+6.92
Qwen3.5-Plus	Zero-shot	map	-6.40	(-6.97, -5.78)	+4.37
Qwen3.5-Plus	Zero-shot	risk	+5.44	(+5.19, +5.71)	+8.13
Qwen3.5-Flash	One-shot	map	-4.51	(-4.76, -4.25)	-7.34
Qwen3.5-Flash	One-shot	risk	+4.52	(+4.26, +4.77)	+7.34
Qwen3.5-Flash	Zero-shot	map	+5.98	(+5.73, +6.26)	-9.71
Qwen3.5-Flash	Zero-shot	risk	+5.43	(+5.18, +5.69)	+9.07
Kimi-K2.5	One-shot	map	-3.80	(-4.19, -3.44)	-6.80
Kimi-K2.5	One-shot	risk	+3.77	(+3.54, +4.01)	+6.90
Kimi-K2.5	Zero-shot	map	-7.91	(-8.34, -7.51)	-11.18
Kimi-K2.5	Zero-shot	risk	+6.16	(+5.86, +6.46)	+9.08
MiniMax-M3	One-shot	map	-3.82	(-4.35, -3.34)	-6.55
MiniMax-M3	One-shot	risk	+5.80	(+5.53, +6.07)	+9.19
MiniMax-M3	Zero-shot	map	-7.82	(-8.60, -7.01)	-11.21
MiniMax-M3	Zero-shot	risk	+6.98	(+6.66, +7.30)	+9.74

Matched-TV envelopes. On the standard grid at $\kappa = 2$, the strict ordering joint > additive ≥ best marginal holds in 72/72 rows, with joint-over-additive envelope advantages of +0.46 to +4.08 points (Table 12); these are envelope advantages, not interaction shares.

Frozen-rule effects. Table 13 reports pooled held-out effects of development-frozen stress weights for all endpoints, and Table 14 reports exact-confidence support. Re-running the frozen five-fold protocol at 70% and 90% development-coverage targets retained positive selective-risk effects in all eight settings. Figure 11 reports held-out exact-C=0.95 correctness changes, and Figure 12 reports full-ledger baseline coverage–risk curves.

External panel (exploratory). Confidence endpoints on the panel are exploratory. Frozen dev-selected rules show no selective value on MMSI (risk within ±0.4 points of the error rate), moderate value on MVI (−1.9 to −3.6 points) and MMMU (−1.6 to −4.4 points). MMSI confidence results are exploratory point estimates; intervals for MVI and MMMU are included in the supplementary archive.

Table 14: Exact-C = 0.95 support for the pooled held-out confidence mapping in Figure 11: responses and independent images for each of eight model–prompt settings. Counts span 5,801–36,450 responses and 3,973–8,366 images.

Model	Prompt	Responses	Images
MiniMax-M3	One-shot	7,109	4,497
Kimi-K2.5	One-shot	13,877	5,905
Qwen3.5-Flash	One-shot	34,652	8,344
Qwen3.5-Plus	One-shot	36,450	8,366
MiniMax-M3	Zero-shot	5,801	3,973
Kimi-K2.5	Zero-shot	10,607	6,220
Qwen3.5-Flash	Zero-shot	21,305	8,147
Qwen3.5-Plus	Zero-shot	11,884	8,201

Table 15: Development-coverage target sensitivity: pooled held-out frozen-rule risk effects (pp) at 70%, 80% (published), and 90% coverage targets, re-run with identical seeds, folds, and bootstrap draws (`sensitivity_coverage/`). Risk rises in 8/8 settings under every target (ranges 6.90–9.78, 6.90–9.74, 6.90–9.59 pp) and the exact-0.95 five-point reporting gate remains 7/8.

Model	Prompt	70% target	80% (pub.)	90% target
Qwen3.5-Plus	One-shot	6.92	6.92	6.92
Qwen3.5-Flash	One-shot	7.34	7.34	7.31
Kimi-K2.5	One-shot	6.90	6.90	6.90
MiniMax-M3	One-shot	9.17	9.19	9.03
Qwen3.5-Plus	Zero-shot	8.39	8.13	7.91
Qwen3.5-Flash	Zero-shot	9.32	9.07	9.07
Kimi-K2.5	Zero-shot	9.40	9.08	8.80
MiniMax-M3	Zero-shot	9.78	9.74	9.59




Figure 11: Exact-confidence mapping under the frozen-rule held-out protocol: change in empirical correctness at exact emitted confidence C=0.95. Whiskers show 95% bootstrap confidence intervals, and vertical references mark the prespecified ±5pp gate.




Figure 12: Full-ledger baseline coverage–risk curves, with separate zero-shot and one-shot panels. Each panel shows all four models and uses the shared model legend.

G Transfer, Structural, and Sensitivity Analyses

Development-frozen transfer. Full-ledger scores fix each event's winner–challenger orientation. Within every development fold, the joint solver independently derives r_{dir} and its TV magnitude at the prespecified one-point target; only the resulting object is scored on that fold's held-out images. Conditional bootstrap resampling holds the five folds, pair orientation, and each fold's r_{dir} fixed. In replicate b, it recomputes the empirical cell composition p_b, forms $q_b \propto r_{\text{dir}} p_b$ by normalization, and evaluates the same raw Hájek statistic. Reported held-out gaps and stress effects are equal-weight arithmetic means over the five folds, unlike the oversight endpoint's weighted numerator–denominator ratio. The six audited events therefore use directions that differ across folds. Their held-out stress effects were +1.2 to +3.8 points on the pair gap, with all six conditional-bootstrap intervals excluding zero. The final challenger gaps were five-fold-averaged point estimates from −0.2 to +0.64 points.

Surface decomposition. For each empirical-Bayes challenger-minus-baseline-higher performance-gap surface, the decomposition is $d_{pt} = \mu + \alpha_p + \beta_t + \gamma_{pt}$, fitted by w^0-weighted least squares. The original and residual-free surfaces retain the full joint weight space during ablation, so the comparison changes estimated performance differences rather than the permitted weights. Table 16 reports the six frozen $\kappa = 3$ event radii, using the challenger orientation specified by the matched-TV event record. Four residual-free rows are not reached; the two attained ratios use unrounded radii. The MVI numerical swap occurs on a five-degree-of-freedom grid with 102–309 scored responses per model–cell.

Direction stability. In 200 product-stratified bootstrap replicates that re-solve the audited events, reachability holds in 197–200 of 200, while the optimizing corner itself moves: its median TV distance from the full-ledger corner is 5.3–16.5%. Events are robust; the specific worst-case direction is not.

Null controls. Permutation and additive-truth simulations show that joint event reachability alone is not diagnostic of non-additive structure. In residual-variance checks with 1,000 additive-truth replicates, five events had 0 exceedances and one had 2 exceedances. A cluster-aware design-effect analysis confirms the image-level resampling units.




Figure 13: Fold-specific transfer validation for six native all-pairs events. Baseline and held-out final challenger gaps are shown separately from raw Hájek held-out stress effects and their 95% conditional bootstrap intervals. Pair orientation is fixed from full-ledger scores; each fold independently solves its development stress direction and TV magnitude before held-out scoring, and resampling holds those directions fixed.

Table 16: Residual-free surface ablation at the frozen $\kappa = 3$ +1pp endpoint. Direction is challenger minus baseline-higher model from the matched-TV event record. The full joint weight space is retained; residual-free changes the estimated performance-difference surface, not the permitted weights. NR denotes an endpoint not reached in the audited space; no infinite ratio is assigned.

Directional pair	Prompt	Original TV (%)	Residual-free TV (%)	Ratio
Kimi-K2.5 minus Qwen3.5-Flash	One-shot	18.69	NR	–
Qwen3.5-Flash minus Qwen3.5-Plus	One-shot	8.32	NR	–
MiniMax-M3 minus Kimi-K2.5	Zero-shot	13.14	29.73	2.26
MiniMax-M3 minus Qwen3.5-Flash	Zero-shot	29.04	NR	–
Kimi-K2.5 minus Qwen3.5-Flash	Zero-shot	11.90	40.71	3.42
Qwen3.5-Flash minus Qwen3.5-Plus	Zero-shot	29.65	NR	–

Support sensitivity (controlled). Thin MVI's cells from 103 to 10 questions per model while holding composition fixed: the probability that the primary and unshrunk estimators disagree on the flip verdict rises monotonically from 0% to 53.7% (+1pp: to 51.2%) while the estimator gap grows 32-fold—support size is the manipulated quantity, with prior mass stable across thinning levels. Two post-hoc probes—coarsening MMSI to 4×3 and tail-trimming MMMU's smallest cells—only partially converge the estimator verdicts, so the diagnosis rests on the controlled thinning evidence.

Prespecified-choices sensitivity. Re-thresholding the frozen gap ladders at $\delta \in \{0.25, 0.5, 1, 2, 3\}$ reproduces the +1pp decision table exactly at $\delta = 1$ and preserves the joint/marginal asymmetry at every larger margin (Table 17). Replacing the empirical-Bayes estimator with unshrunk cell means gives descriptive native 96-row counts: rank-flip reachability 18 vs. 19, maximum selection regret 3.11 vs. 3.29 points, and agreement in all 288 full-ledger direction calls (Table 18).

On MMSI at joint $\kappa = 3$, the +1pp challenger lead was reached for 0/6 pairs under empirical-Bayes estimation, 6/6 under unshrunk cell means, and 6/6 under the common Beta$(1, 1)$ prior; pair orientation was defined separately for each estimator.

Table 17: Reversal-margin sensitivity: number of the twelve pair–prompt settings whose frozen challenger–winner gap ladder attains each margin at any $\kappa \leq 3$ (`delta_sweep.csv`). The prespecified $\delta = 1$ pp row reproduces the six published joint reversals exactly, with no marginal or additive reach at any margin ≥ 1 pp; sub-point margins are reached only at $\delta \leq 0.5$ pp (product-only in three settings, task-only in one, additive in three), confirming the criterion is non-vacuous.

Margin δ (pp)	Product-only	Task-only	Additive	Joint
0.25	3/12	1/12	3/12	8/12
0.5	3/12	0/12	3/12	7/12
1 (prespecified)	0/12	0/12	0/12	6/12
2	0/12	0/12	0/12	4/12
3	0/12	0/12	0/12	1/12

This sweep is the all-pairs native scope (six pairs × two prompt modes); the winner–challenger effect-size ladder of Table 5 covers a different setting matrix and reports its own counts.

Table 18: Rate-estimator sensitivity (native protocol): rank-flip reachability over 96 model-choice sensitivity rows, maximum selection regret, and full-ledger maximum Δrisk at fixed joint $\kappa = 2$ under empirical–Bayes cell estimates and unshrunk cell means. The estimators have 288/288 directional agreements in this full-ledger comparison; this descriptive agreement is not a primary-condition count.

Cell-rate estimator	Rank-flip reach. (of 96 sensitivity rows)	Max regret (pp)	Full-ledger max Δrisk (pp)
Empirical–Bayes	18/96	3.11	7.0–9.7
Unshrunk cell mean	19/96	3.29	7.3–10.1

H Reproducibility and Analysis Provenance

Evidence roles and timeline. The MMAD audit contract (endpoints, κ grid, pairs, tolerances, seeds) was preregistered before outcome inspection; the external panel's three analysis manifests were locked before each benchmark's collection; the transfer/decomposition/control analyses and the effect-size extension are follow-up analyses whose plans were locked before their computations and are labeled as such in the text; the two post-hoc support probes are labeled post-hoc. Every lock, amendment, and post-lock edit is recorded in the manifests included in the supplementary archive.

Verification. The supplementary archive contains a claim–evidence map, frozen analysis outputs, and checks that trace each headline number to its reported result.

Reproduction. The supplementary archive supports reproduction at two levels. Level 1 starts from the frozen response ledger and deterministically regenerates every statistic, table, and figure without any model call; Level 2 documents the original collection (identifiers, decoding settings, protocol, gates) without credentials. Environment: Python 3.10, NumPy, pandas, SciPy (HiGHS via `linprog`); the full bootstrap runs in minutes on one machine. The MMAD snapshot is not redistributed (CC BY-NC-SA-4.0); its digest and loader are recorded in the archive.