CORE-CVR: BENCHMARKING FINE-GRAINED REFERENCE UNDERSTANDING IN COMPOSED VIDEO RETRIEVAL

Anonymous authors
Paper under double-blind review

ABSTRACT

Composed Video Retrieval (CVR) retrieves a target video using a reference video and a modification text as a composed query. We reveal two issues with existing CVR benchmarks. First, they rarely require fine-grained understanding of the reference video. On three widely used benchmarks, 65.0–91.3% of the samples can still be retrieved when the composed query is replaced with a text of at most ten words. Second, they contain shortcuts that allow the target to be retrieved from a single query modality in 69.3–99.0% of the samples. Motivated by these findings, we introduce CORE-CVR, a new CVR benchmark in which both fine-grained reference information and the modification text are required to identify the target. CORE-CVR consists of Static-CVR, which preserves the fine-grained appearance of objects or backgrounds, and Temporal-CVR, which preserves the fine-grained execution of actions. We further introduce Reference Negatives and Modification Negatives, which can be rejected only by using the fine-grained reference information and the modification text, respectively. On CORE-CVR, only 22.1% and 16.6% of the samples are retrieved by short text and a single input, respectively. The best model achieves only 27.7% R@1, leaving substantial room for improvement.

1 INTRODUCTION

Composed Video Retrieval (CVR) (Ventura et al., 2024) retrieves a target video using a reference video and a modification text. For example, a user may provide a video of pushing a patterned cup with a bottle, with the modification text "Turn the cup upside down" (Fig. 1). The target is a video of a similar-looking cup being turned upside down. The appearance of the cup is hard to describe precisely in words, but it is directly available in the reference video. Thus, the reference can convey hard-to-verbalize information, such as object appearance, background characteristics, and how an action is performed. The text then only needs to specify the desired changes. A CVR model should therefore identify what to preserve from the reference and combine it with the modification.



Figure 1: **An example from CORE-CVR (Static-CVR, object preservation).** In the reference video, a patterned cup is pushed with a bottle. The modification text asks to turn the cup upside down, and the target shows a similar-looking cup being turned upside down. The appearance of the cup is given by the reference video, and the new action by the modification text.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

However, existing CVR benchmarks often do not require this ability. We show this with two diagnostic tests: retrieving with a text query of at most ten words generated from both inputs, and retrieving with only one input. On WebVid-CoVR, Dense-WebVid-CoVR, and CoVR-R, 65.0–91.3% of the samples are retrieved by the short text query, and 69.3–99.0% by a single input. Thus, many samples contain shortcuts: the target can be found without using fine-grained reference information or without combining the two inputs. As a result, performance on existing benchmarks does not sufficiently measure the ability to understand fine-grained reference information and combine it with the modification text.

These shortcuts stem from benchmark construction. Existing benchmarks typically pair videos with similar captions or global visual representations and describe their difference with a modification text (Ventura et al., 2024; Wu et al., 2025; Thawakar et al., 2025). This scales well but leaves two factors uncontrolled. First, fine-grained reference information may not be needed. If the target shows an arbitrary cup, or the gallery has no video of turning a different-looking cup upside down, the reference can be replaced by the text "a cup." Second, both inputs may not be needed. Without a video of turning a different-looking cup upside down, the modification text alone suffices. Without another video of a similar-looking cup in a different action, the reference alone suffices.

EgoCVR (Hummel et al., 2024) mitigates the second problem by adding other clips from the same source video to the gallery as distractors. Since these candidates share the scene of the target, both the reference and the modification text are needed for retrieval. As a result, only 16.6% of the samples are retrieved by a single input. However, the reference information it requires is mainly scene-level. When the action is modified, the unchanged object is often shared only at the category level, not in its fine-grained appearance. When the object is modified, the unchanged action is often shared only at the label level, not in its fine-grained execution. Thus, EgoCVR cannot test whether a model uses such fine-grained information from the reference.

To address these two problems, we define two properties that a CVR benchmark should satisfy. **Reference Video Utility** requires that identifying the target needs fine-grained information from the reference video, i.e., information that is difficult to replace with short text. **Compositional Necessity** requires that neither the reference video nor the modification text alone can identify the target. When both properties hold, a successful retrieval more directly reflects that the model uses fine-grained reference information and combines it with the modification.

We construct CORE-CVR, a new CVR benchmark, with three components that satisfy these properties. First, we explicitly define the fine-grained information to preserve and mine reference–target pairs that share it. Static-CVR preserves the fine-grained appearance of an object or background, and Temporal-CVR preserves the fine-grained execution of an action beyond its label. To our knowledge, CORE-CVR is the first CVR benchmark that requires such action execution to be preserved from the reference. The modification text indicates what to preserve without describing it. Second, each query includes Reference Negatives (R-Negs), which share the coarse semantics of the target but differ from the reference in the preserved detail (e.g., turning a different-looking cup upside down). Third, each query includes Modification Negatives (M-Negs), which share the preserved detail but violate the modification (e.g., pushing a similar-looking cup with a bottle). The pairs and R-Negs establish Reference Video Utility, while R-Negs and M-Negs together establish Compositional Necessity.

We apply the same diagnosis used for existing benchmarks to CORE-CVR. Only 22.1% of the samples are retrieved by short text queries and 16.6% by a single input. The preserved attribute is also more similar between the reference and target than in EgoCVR, even with encoders not used for mining. In addition, R-Negs and M-Negs mainly make modification-only and reference-only retrieval harder, respectively, confirming their intended roles. Current multimodal embedding models and CVR methods achieve at most 27.7% R@1 on CORE-CVR. This leaves substantial room for improvement in jointly using fine-grained reference information and modification conditions.

2 Related Work

Composed Image Retrieval (CIR). Composed Image Retrieval (CIR) retrieves a target image using a reference image and a textual modification (Vo et al., 2019). Representative benchmarks include FashionIQ (Wu et al., 2021), CIRR (Liu et al., 2021), and CIRCO (Baldrati et al., 2023).

Recently, Attimonelli et al. (2026) showed that these benchmarks contain shortcuts that allow retrieval from a single modality. We show that CVR benchmarks share this issue and further examine whether the reference video can be replaced with short text.

Composed Video Retrieval (CVR). CVR methods improve composed-query representations (Thawakar et al., 2024; Wu et al., 2025; Chen et al., 2025) or reason about the modification with large language or multimodal models without training (Hummel et al., 2024; Thawakar et al., 2026). CVR benchmarks have been built from videos with similar captions (Ventura et al., 2024), dense modifications (Thawakar et al., 2025), egocentric action changes (Hummel et al., 2024), sub-action changes (Gupta et al., 2025), and implicit state transitions (Thawakar et al., 2026). However, most of them define pairs by textual labels or global visual similarity. They thus offer limited control over which fine-grained attribute is preserved between the reference and target. TF-CoVR (Gupta et al., 2025) targets temporally fine-grained differences, but they are specified by the modification text through action labels. In contrast, CORE-CVR requires action execution beyond the label to be preserved from the reference. For pair mining, we use self-supervised representations, since image–text contrastive models such as CLIP (Radford et al., 2021) tend to overlook fine-grained differences (Tong et al., 2024; Wang et al., 2025). We use DINOv3 (Siméoni et al., 2025) for appearance and V-JEPA 2 (Assran et al., 2025) for actions.

3 CORE-CVR



Figure 2: CORE-CVR construction overview.

We construct CORE-CVR to satisfy Reference Video Utility and Compositional Necessity. Reference–target pairs that share fine-grained information, together with R-Negs, are designed to make fine-grained reference information necessary (Reference Video Utility). R-Negs and M-Negs are designed to reduce single-input shortcuts (Compositional Necessity). Figure 2 illustrates the overall process of constructing these three components.

3.1 Dataset Overview

We build CORE-CVR from Something-Something v2 (Goyal et al., 2017), HD-EPIC (Perrett et al., 2025), EPIC-KITCHENS VISOR (Darkhalil et al., 2022), and Ego-Exo4D (Grauman et al., 2024), using clips of 1–10 seconds. It contains 2,500 queries, 1,250 each for Static-CVR and Temporal-CVR. Static-CVR has 625 object- and 625 background-preservation queries. Temporal-CVR has 754 action-preservation, 87 result-change, 262 direction-change, 137 action-deletion, and 10 action-replacement queries. Each query has two R-Negs and two M-Negs. Since a clip can serve multiple queries, the gallery contains 9,984 unique clips.

Table 1: **Temporal-CVR query types.** A' has execution similar to A. A'_{res} and A'_{dir} differ in result and direction, respectively. B and C are other actions, and $\oplus$ denotes adjacent segments within one continuous source clip, not synthetic concatenation; the shown order is schematic.

	Preservation	Result	Direction	Deletion	Replacement
Ref. $\rightarrow$ Target	$A \rightarrow A'$	$A \rightarrow A'_{\text{res}}$	$A \rightarrow A'_{\text{dir}}$	$A \oplus B \rightarrow A'$	$A \oplus B \rightarrow A' \oplus C$

3.2 Dataset Construction

The construction consists of three stages: reference–target pair mining, modification text generation, and hard negative mining. The first stage produces reference–target pairs that share fine-grained information. The second produces modification texts that indicate what to preserve without describing it. The last produces R-Negs and M-Negs.

3.2.1 Reference–Target Pair Mining

Static-CVR. Static-CVR preserves the fine-grained appearance of a specific object or background. We obtain object masks from dataset annotations and SAM 3.1 (Carion et al., 2026), and define the background as the region outside all object masks. Each region is represented by mask-weighted pooling of DINOv3 patch features over frames. For object preservation, we collect videos that contain an object of the same category with similar appearance. We then remove candidates with near-duplicate captions and select the one with the most different background as the target. Background-preservation pairs follow the same principle. Appendix A.1 gives the thresholds and details.

Temporal-CVR. Temporal-CVR preserves the fine-grained execution of an action beyond its label. For this, we train an attentive pooler on a frozen V-JEPA 2 (Assran et al., 2025) with action classification on the four source datasets. We evaluate it on 600 human-annotated triplets, each consisting of an anchor and two candidates with the same action label. It agrees with human judgments of motion similarity in 74.5% of cases, the highest among six encoders. This approaches the human leave-one-out agreement of 80.7% (Appendix D). Temporal-CVR has five query types (Table 1). In action preservation, the target shares the action label and execution with the reference but involves a different object. Direction-change queries search with a spatially flipped or temporally reversed reference and select a target with the opposite direction label. Action deletion and replacement extend clip boundaries to include adjacent action segments in the same source video. Appendix A.2.2 gives the full procedure.

3.2.2 Modification Text Generation

We provide an LLM with the reference and target captions and the type of preserved information (object, background, or action). The LLM describes the change from the reference to the target and refers to the preserved information without describing it. For Static-CVR, we use GPT-5.6 Terra with the shared category label. Since pairs share a highly similar appearance rather than the same physical instance, the text refers to a "similar-looking" object or background. For Temporal-CVR, the preserved action is never named: the prompt forbids both describing it and instructing that it be preserved, so the text states only the change and refers to the shared action deictically. No video is given to the LLM (Appendix F).

3.2.3 Hard Negative Mining

The gallery of each query includes two R-Negs and two M-Negs. Both are mined with the same representations used for pair mining. The preserved attribute is the appearance of the selected object or background for Static-CVR and the fine-grained action for Temporal-CVR.

Reference Negative (R-Neg). An R-Neg shares the coarse semantics of the target, but its preserved attribute differs from the reference at a fine-grained level. We first collect videos whose captions are semantically similar to the target. We then select those with low similarity to the reference in the preserved attribute. Since an R-Neg shares caption-level semantics with the target, it is designed to be hard to distinguish from the target without fine-grained reference information.

Modification Negative (M-Neg). An M-Neg shares the preserved attribute with the reference at a fine-grained level but does not satisfy the modification. Among videos similar to the reference in the preserved attribute, we select those that do not reflect the change required by the modification text. For example, for action-preservation queries, we use action-similar candidates that are not selected as the target and involve objects different from the target. Since an M-Neg shares the preserved attribute with the reference, it is designed to be hard to distinguish from the target without the modification text. Appendix A.2.2 gives the type-specific selection criteria.

4 EXPERIMENTS

We analyze existing CVR benchmarks and CORE-CVR under the same evaluation setting. We first verify whether each benchmark satisfies Reference Video Utility (Sec. 4.2) and Compositional Necessity (Sec. 4.3). We then analyze whether each hard negative plays its intended role (Sec. 4.4) and evaluate current retrieval models on CORE-CVR (Sec. 4.5).

4.1 EXPERIMENTAL SETUP

Models and benchmarks. Our diagnostic analyses use four multimodal embedding models: Qwen3-VL-Embedding (Li et al., 2026), WeMM-Embedding (Zhou et al., 2026), UEmbed (Song et al., 2026), and e5-omni (Chen et al., 2026). Each supports text, video, and composed inputs, so all query settings can be compared with the same models. We sample 16 frames per video following each model's official preprocessing. We evaluate WebVid-CoVR (Ventura et al., 2024), EgoCVR (Hummel et al., 2024) (global gallery), Dense-WebVid-CoVR (Thawakar et al., 2025), FineCVR-1M (Wu et al., 2025), CoVR-R (Thawakar et al., 2026), and CORE-CVR. Sec. 4.5 further evaluates FDCA (Wu et al., 2025), CoVR-2 (Ventura et al., 2024), HUD (Chen et al., 2025), TFR-CVR (Hummel et al., 2024), and CoVR-R (Thawakar et al., 2026).

Query settings and coverage. We use the Composed Query (CQ), Reference-only Query (RQ), and Modification-only Query (MQ). RQ and MQ together form the Unimodal Queries (UQ). We also generate a Composed-to-Text (C2T) query from the reference video and modification text with GPT-5.6 Luna and summarize it under word limits from 5 to 50 words in steps of 5. Table 2 reports the 10- and 20-word limits and the unrestricted query. For each setting, the Top-1 oracle coverage is the fraction of samples whose target is ranked first by at least one of the four models. It depends less on a single model and thus captures shortcuts more broadly. Hereafter, CQ, RQ, MQ, and C2T coverage denote the Top-1 oracle coverage of each query setting.

4.2 REFERENCE VIDEO UTILITY

To verify Reference Video Utility, we test whether the reference can be replaced with short text and whether the reference and target share the preserved attribute.

Evaluation Protocol. We measure short-text replaceability with C2T coverage and Composed-to-Text Retention. Let S_C and $S_T^{(w)}$ be the sets of samples retrieved by CQ and by C2T with word limit w, respectively. We define $\mathrm{Retention}(w) = |S_C \cap S_T^{(w)}|/|S_C|$, the fraction of CQ successes also retrieved by C2T. Since it considers only samples solvable by CQ, Retention is less affected by benchmark difficulty than C2T coverage. Lower values of both metrics suggest that the reference provides information hard to replace with short text. As C2T can also fail due to text generation or text–video alignment, we treat them as suggestive evidence.

Short-text replaceability. Table 2 shows that 65.0–91.3% of the samples in WebVid-CoVR, Dense-WebVid-CoVR, and CoVR-R are retrieved by C2T queries of at most ten words. Their Retention is 77.3–91.7%, so most CQ successes can be reproduced with short text. CORE-CVR is much lower, with 22.1% coverage and 46.5% Retention. EgoCVR and FineCVR-1M also show low Retention (38.2% and 49.8%), but aggregate Retention also depends on the rest of the gallery. We therefore rank each query against its target and two designed negatives: two R-Negs for CORE-CVR and two same-source distractors for EgoCVR. Averaged over the four encoders (chance: 33.3%), ten-word C2T accuracy is 57.7% on EgoCVR but only 18.7% on CORE-CVR. The latter is below

Table 2: **Short-text replaceability of the reference video (%).** C2T: Top-1 oracle coverage of the C2T query. Retention: fraction of CQ successes also retrieved by the C2T query. Full: no word limit. ↓: lower is better. –: undefined (no CQ success).

Benchmark / Query type	N	CQ (%)	C2T (%) ↓			C2T Retention (%) ↓		
			≤ 10	≤ 20	Full	≤ 10	≤ 20	Full
WebVid-CoVR (Ventura et al., 2024)	2,450	78.1	65.0	66.6	71.8	77.3	79.2	87.7
EgoCVR (Hummel et al., 2024)	2,295	29.7	22.8	27.0	27.3	38.2	48.5	50.9
Dense-WebVid-CoVR (Thawakar et al., 2025)	2,449	98.0	88.7	91.2	96.9	87.3	90.4	97.5
FineCVR-1M (Wu et al., 2025)	9,986	40.6	27.2	29.7	32.8	49.8	55.7	64.7
CoVR-R (Thawakar et al., 2026)	2,656	99.3	91.3	94.9	99.5	91.7	95.4	99.8
CORE-CVR (All)	2,500	34.1	22.1	24.4	28.2	46.5	51.5	63.3
Static-CVR	1,250	39.4	26.5	28.7	31.1	51.6	54.9	63.4
Object	625	34.6	26.6	20.2	18.6	49.1	36.1	42.1
Background	625	44.2	26.4	37.3	43.7	53.6	69.6	80.1
Temporal-CVR	1,250	28.9	17.8	20.2	25.3	39.6	46.8	63.2
Action Preservation	754	37.0	20.9	24.7	31.6	40.1	48.0	62.4
Action Deletion	137	15.3	5.1	6.6	8.0	14.3	19.0	42.9
Action Replacement	10	0.0	0.0	20.0	30.0	-	-	-
Result Change	87	31.0	10.3	14.9	25.3	33.3	44.4	77.8
Direction Change	262	13.0	18.3	16.0	16.0	55.9	55.9	70.6

Table 3: **Three-way comparison of designed negatives (%).** Each query is ranked against its target and two negatives. Accuracy is averaged over the four encoders (chance: 33.3%). Ret.: fraction of CQ successes also retrieved by C2T.

Setting	N	CQ	C2T $\leq$10	C2T Full	Ret. $\leq$10	Ret. Full
EgoCVR (2 distractors)	1,995	51.0	57.7	49.8	76.8	73.7
CORE-CVR (2 R-Negs)	2,500	42.1	18.7	31.6	33.2	60.8

chance, since R-Negs are selected to match the caption of the target. Retention shows the same gap (76.8% vs. 33.2%). Longer descriptions also raise C2T accuracy on CORE-CVR (14.3% $\rightarrow$ 31.6%) but lower it on EgoCVR (59.0% $\rightarrow$ 49.8%). Thus, EgoCVR's distractors are separated mainly by the modification, whereas R-Negs are separated only by information from the reference (Table 3).

Across query types, Retention depends on the preserved information. Without a word limit, it reaches 80.1% for background preservation but only 42.1% for object preservation, which is even lower than EgoCVR (50.9%). With ten words, Temporal-CVR shows lower Retention than Static-CVR (39.6% vs. 51.6%). Appendix B.1 gives a per-type analysis.

Fine-grained sharing between reference and target. We next test whether the reference and target actually share the preserved attribute (Table 4). For each benchmark, we measure the reference–target similarity of the attribute that the query is meant to preserve. For EgoCVR, appearance is measured on action-centric queries and action execution on object-centric queries, where the corresponding attribute remains unchanged. For FineCVR-1M and WebVid-CoVR, we use only the queries that retain the measured attribute and compare object or background regions obtained from SAM 3.1 masks. Since DINOv3 and V-JEPA 2 are used for mining CORE-CVR, we mainly rely on RADIOv2.5 (Heinrich et al., 2025) and InternVideo-Next (Wang et al., 2026), which are not used for mining. With these encoders, CORE-CVR shows a clear gap from all existing benchmarks in object appearance (0.85 vs. at most 0.74) and action execution (0.83 vs. at most 0.71). For background, EgoCVR is higher (0.92 vs. 0.81). This is expected, since its reference and target are cut from the same source video and thus share the scene itself, whereas CORE-CVR pairs different videos; among such benchmarks, CORE-CVR still shows the highest background similarity. Thus, explicit pair mining preserves the intended object appearance and action execution more strongly than same-source pairing, which is advantaged only on the scene it inherits.

Table 4: **Mean reference–target similarity of the preserved attribute.** †: encoders used for mining CORE-CVR.

Aspect	Encoder	FineCVR-1M	WebVid-CoVR	EgoCVR	CORE-CVR
Action	InternVideo-Next	0.53	0.71	0.61	**0.83**
	V-JEPA 2†	0.53	0.68	0.56	**0.83**
Object	RADIOv2.5	0.74	0.73	0.70	**0.85**
	DINOv3†	0.84	0.60	0.75	**0.91**
Background	RADIOv2.5	0.78	0.72	**0.92**	0.81
	DINOv3†	0.77	0.64	0.83	**0.88**

Table 5: **Top-1 oracle coverage across query settings on existing CVR benchmarks and CORE-CVR (%).** RQ and MQ denote Reference-only and Modification-only Queries, respectively. UQ counts samples retrieved by either unimodal query, while CQ uses both query inputs. CQ-only/CQ denotes the fraction of CQ successes not retrieved by either unimodal query. For CORE-CVR, the Static-CVR and Temporal-CVR rows aggregate their sub-types.

Benchmark / Query type	N	RQ	MQ	UQ	CQ	CQ-only/CQ
WebVid-CoVR (Ventura et al., 2024)	2,450	51.2	41.3	69.3	78.1	16.9
EgoCVR (Hummel et al., 2024)	2,295	11.9	5.1	16.6	29.7	59.5
Dense-WebVid-CoVR (Thawakar et al., 2025)	2,449	51.2	92.2	95.7	98.0	3.1
FineCVR-1M (Wu et al., 2025)	9,986	19.3	21.9	37.4	40.6	32.6
CoVR-R (Thawakar et al., 2026)	2,656	32.7	98.8	99.0	99.3	0.7
CORE-CVR (All)	2,500	6.0	11.0	16.6	34.1	**65.9**
Static-CVR	1,250	3.0	19.1	21.6	39.4	63.0
Object	625	3.5	23.7	26.4	34.6	55.1
Background	625	2.4	14.6	16.8	44.2	69.2
Temporal-CVR	1,250	9.0	3.0	11.6	28.9	69.8
Action Preservation	754	6.8	3.1	9.4	37.0	81.0
Action Deletion	137	10.2	0.7	11.0	15.3	57.1
Action Replacement	10	10.0	10.0	20.0	0.0	-
Result Change	87	29.9	1.2	29.9	31.0	7.4
Direction Change	262	7.6	4.2	11.8	13.0	35.3

4.3 Compositional Necessity

To verify Compositional Necessity, we examine whether either input alone can identify the target. We also examine whether the retrieval success of the composed query stems from combining the two inputs.

Evaluation Protocol. Let S_R, S_M, and S_C be the success sets of RQ, MQ, and CQ, respectively, and let $S_U = S_R \cup S_M$ be the set of samples retrieved by either unimodal query. The UQ coverage is $|S_U|/N$. We further define CQ-only/CQ $= |S_C \setminus S_U|/|S_C|$, the fraction of CQ successes not retrieved by either unimodal query. A higher value indicates that the retrieval success of CQ stems from combining the two inputs.

Results. Table 5 shows widespread single-input shortcuts in existing benchmarks. UQ coverage reaches 69.3%, 95.7%, and 99.0% on WebVid-CoVR, Dense-WebVid-CoVR, and CoVR-R. In the latter two, MQ alone retrieves more than 92% of the samples, so the reference video is unnecessary for most of them. EgoCVR lowers UQ coverage to 16.6% with same-source distractors.

CORE-CVR also has a UQ coverage of 16.6% (RQ 6.0%, MQ 11.0%), whereas its CQ coverage is 34.1%. Moreover, 65.9% of its CQ successes are not retrieved by either input alone, higher than EgoCVR (59.5%). Together with Sec. 4.2, these results show that CORE-CVR suppresses single-input shortcuts as well as EgoCVR while preserving the intended attributes more finely. Some types, especially result change, still retain single-input shortcuts (Appendix B.2).

Table 6: **Effect of hard negatives (R@1, %).** X → Random replaces the corresponding hard negatives with random clips while keeping the gallery size fixed (9,984 clips). Numbers in parentheses denote the change from the original gallery.

Model	Original	M-Neg→Random	R-Neg→Random	Both→Random
Reference-only Query (RQ)				
Qwen3-VL-Embedding (8B)	3.0	4.6 (+1.6)	3.5 (+0.5)	**6.3** (+3.2)
WeMM-Embedding (9B)	3.0	4.7 (+1.7)	4.0 (+1.0)	**6.9** (+3.9)
UEmbed (9B)	3.5	6.0 (+2.5)	4.5 (+1.0)	**8.5** (+5.0)
e5-omni (7B)	3.6	6.4 (+2.8)	4.1 (+0.5)	**7.9** (+4.3)
Modification-only Query (MQ)				
Qwen3-VL-Embedding (8B)	2.8	3.0 (+0.2)	6.6 (+3.8)	**7.4** (+4.6)
WeMM-Embedding (9B)	7.8	7.4 (−0.4)	13.2 (+5.5)	**13.9** (+6.1)
UEmbed (9B)	2.2	2.7 (+0.5)	4.2 (+2.0)	**5.3** (+3.1)
e5-omni (7B)	3.0	2.8 (−0.2)	**4.8** (+1.8)	**4.8** (+1.8)
Composed Query (CQ)				
Qwen3-VL-Embedding (8B)	13.5	15.1 (+1.6)	18.0 (+4.5)	**23.6** (+10.0)
WeMM-Embedding (9B)	27.7	29.2 (+1.5)	35.7 (+8.0)	**41.9** (+14.2)
UEmbed (9B)	15.9	18.5 (+2.6)	21.3 (+5.4)	**27.0** (+11.1)
e5-omni (7B)	8.4	12.4 (+4.0)	10.0 (+1.6)	**16.7** (+8.4)

Table 7: **Retrieval performance on CORE-CVR (%).** Multimodal embedding models are evaluated in a zero-shot manner. For CVR methods, Training data denotes the dataset used to train the released model. The best result in each column is shown in bold.

Model	Training data	R@1	R@5	R@10	R@50
Zero-shot multimodal embedding models					
Qwen3-VL-Embedding (8B)	–	13.5	33.9	46.7	74.8
WeMM-Embedding (9B)	–	**27.7**	**55.1**	**66.5**	**86.4**
UEmbed (9B)	–	15.9	38.5	51.4	76.7
e5-omni (7B)	–	8.4	25.7	39.1	67.0
Pretrained CVR models					
FDCA (Wu et al., 2025)	FineCVR-1M	5.2	15.6	23.4	45.6
CoVR-2 (Ventura et al., 2024)	WebVid-CoVR	4.8	15.3	22.6	48.9
HUD (Chen et al., 2025)	WebVid-CoVR	6.5	18.6	26.4	52.2
Training-free CVR methods					
TFR-CVR (Hummel et al., 2024)	–	1.7	10.2	18.3	–
CoVR-R (Thawakar et al., 2026)	–	3.8	11.8	17.1	32.8

4.4 Effect of Hard Negatives

We construct three variants of the CORE-CVR gallery by replacing R-Negs, M-Negs, or both with random clips. The gallery size is kept fixed at 9,984 clips. As shown in Table 6, replacing R-Negs increases MQ R@1 by 1.8–5.5 points but changes RQ only slightly. Replacing M-Negs increases RQ R@1 by 1.6–2.8 points but barely changes MQ. Thus, R-Negs mainly suppress modification-only shortcuts, and M-Negs mainly suppress reference-only shortcuts. Replacing both raises CQ R@1 by 8.4–14.2 points, showing that the hard negatives directly contribute to the difficulty of CORE-CVR.

4.5 Model Evaluation on CORE-CVR

Table 7 reports retrieval performance on CORE-CVR. Among zero-shot embedding models, WeMM-Embedding performs best with 27.7% R@1, and the others achieve only 8.4–15.9%. Pretrained and training-free CVR methods achieve only 1.7–6.5%. This suggests that existing CVR representations and query-composition strategies do not handle the preserved fine-grained attributes

and hard negatives well. CoVR-2 and HUD also use only the middle frame of the reference video and cannot exploit temporal information. Per-type results show where the difficulty lies (Appendix B.3). Object preservation is harder than background preservation for all embedding models. Performance also drops sharply for direction change (6.5–8.8% R@1) and action deletion (3.6–12.4%), showing persistent difficulty with motion direction and temporal composition. Overall, current models leave substantial room for improvement in capturing fine-grained reference information and combining it with the modification.

5 Conclusion

We presented CORE-CVR, a benchmark for evaluating whether CVR models use fine-grained reference information and combine it with the modification text. We showed that many samples in existing benchmarks can be retrieved with short text or a single input. We then defined Reference Video Utility and Compositional Necessity and constructed CORE-CVR to satisfy both. CORE-CVR explicitly preserves the fine-grained appearance of objects or backgrounds and the execution of actions, and includes R-Negs and M-Negs to suppress single-input shortcuts. Current models achieve at most 27.7% R@1, showing that fine-grained reference understanding remains an open challenge for CVR.

AI use statement

In this work, we used generative AI tools for generating synthetic data, implementing methods, assisting with translation, and interpreting results. We have not used generative AI tools for proposing hypotheses or developing conceptual frameworks, and formulating or proving mathematical claims and qualitative data analysis are not applicable to this work. Additionally, we used generative AI tools for drafting and editing parts of the paper and for searching and summarizing related literature.

Synthetic data. GPT-5.6 Terra generated the modification texts of CORE-CVR from the captions of each reference–target pair (Sec. 3 and Appendix F). GPT-5.6 Luna generated the C2T queries used in our diagnostic analyses (Sec. 4.1). The generated texts follow a fixed output schema, and invalid outputs were rejected.

Code and experiments. AI coding assistants helped write and run code for dataset construction and evaluation. The authors reviewed and tested all code, and all reported numbers come from author-verified runs.

Translation and writing. The paper was first drafted in native language and translated into English with the help of LLMs. LLMs were also used to improve readability and to discuss the design and interpretation of our analyses. All research decisions and final claims were made by the authors.

Literature. LLMs were used to search for and summarize related work. We verified every cited work against the original paper.

We have reviewed all AI-assisted work. We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

References

Mido Assran, Adrien Bardes, David Fan, Quentin Garrido, Russell Howes, Mojtaba Komeili, Matthew Muckley, Ammar Rizvi, Claire Roberts, Koustuv Sinha, Artem Zholus, Sergio Arnaud, Abha Gejji, Ada Martin, Francois Robert Hogan, Daniel Dugas, Piotr Bojanowski, Vasil Khalidov, Patrick Labatut, Francisco Massa, Marc Szafraniec, Kapil Krishnakumar, Yong Li, Xiaodong Ma, Sarath Chandar, Franziska Meier, Yann LeCun, Michael Rabbat, and Nicolas Ballas. V-JEPA 2: Self-supervised video models enable understanding, prediction and planning, 2025. URL https://arxiv.org/abs/2506.09985.

Matteo Attimonelli, Alessandro De Bellis, Aryo Pradipta Gema, Rohit Saxena, Monica Sekoyan, Wai-Chung Kwan, Claudio Pomo, Alessandro Suglia, Dietmar Jannach, Tommaso Di Noia, et al. Do composed image retrieval benchmarks require multimodal composition? *arXiv preprint arXiv:2605.14787*, 2026.

Alberto Baldrati, Lorenzo Agnolucci, Marco Bertini, and Alberto Del Bimbo. Zero-shot composed image retrieval with textual inversion. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023. URL https://arxiv.org/abs/2303.15247.

Nicolas Carion, Laura Gustafson, Yuan-Ting Hu, Shoubhik Debnath, Ronghang Hu, Didac Suris Coll-Vinent, Chaitanya Ryali, Kalyan Vasudev Alwala, Haitham Khedr, Andrew Huang, et al. Sam 3: Segment anything with concepts. In *International conference on learning representations*, volume 2026, pp. 138846–138923, 2026.

Haonan Chen, Sicheng Gao, Radu Timofte, Tetsuya Sakai, and Zhicheng Dou. e5-omni: Explicit cross-modal alignment for omni-modal embeddings, 2026. URL https://arxiv.org/abs/2601.03666.

Zhiwei Chen, Yupeng Hu, Zixu Li, Zhiheng Fu, Haokun Wen, and Weili Guan. Hud: Hierarchical uncertainty-aware disambiguation network for composed video retrieval. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pp. 6143–6152, 2025.

Dima Damen, Hazel Doughty, Giovanni Maria Farinella, Antonino Furnari, Jian Ma, Evangelos Kazakos, Davide Moltisanti, Jonathan Munro, Toby Perrett, Will Price, and Michael Wray. Rescaling egocentric vision: Collection, pipeline and challenges for EPIC-KITCHENS-100. *International Journal of Computer Vision*, 130:33–55, 2022. doi: 10.1007/s11263-021-01531-2.

Ahmad Darkhalil, Dandan Shan, Bin Zhu, Jian Ma, Amlan Kar, Richard Higgins, Sanja Fidler, David Fouhey, and Dima Damen. EPIC-KITCHENS VISOR benchmark: VIdeo segmentations and object relations. In *Advances in Neural Information Processing Systems*, volume 35, 2022. URL https://arxiv.org/abs/2209.13064.

Raghav Goyal, Samira Ebrahimi Kahou, Vincent Michalski, Joanna Materzynska, Susanne Westphal, Heuna Kim, Valentin Haenel, Ingo Fruend, Peter Yianilos, Moritz Mueller-Freitag, et al. The "something something" video database for learning and evaluating visual common sense. In *2017 IEEE international conference on computer vision (ICCV)*, pp. 5843–5851. IEEE, 2017.

Kristen Grauman, Andrew Westbury, Lorenzo Torresani, Kris Kitani, Jitendra Malik, Triantafyllos Afouras, Kumar Ashutosh, Vijay Baiyya, Siddhant Bansal, Bikram Boote, Eugene Byrne, Zach Chavis, Joya Chen, Feng Cheng, Fu-Jen Chu, Sean Crane, Avijit Dasgupta, Jing Dong, Maria Escobar, Cristhian Forigua, Abrham Gebreselasie, Sanjay Haresh, Jing Huang, Md Mohaiminul Islam, Suyog Jain, Rawal Khirodkar, Devansh Kukreja, Kevin J Liang, Jia-Wei Liu, Sagnik Majumder, Yongsen Mao, Miguel Martin, Effrosyni Mavroudi, Tushar Nagarajan, Francesco Ragusa, Santhosh Kumar Ramakrishnan, Luigi Seminara, Arjun Somayazulu, Yale Song, Shan Su, Zihui Xue, Edward Zhang, Jinxu Zhang, Angela Castillo, Changan Chen, Xinzhu Fu, Ryosuke Furuta, Cristina Gonzalez, Prince Gupta, Jiabo Hu, Yifei Huang, Yiming Huang, Weslie Khoo, Anush Kumar, Robert Kuo, Sach Lakhavani, Miao Liu, Mi Luo, Zhengyi Luo, Brighid Meredith, Austin Miller, Oluwatumininu Oguntola, Xiaqing Pan, Penny Peng, Shraman Pramanick, Merey Ramazanova, Fiona Ryan, Wei Shan, Kiran Somasundaram, Chenan Song, Audrey Southerland, Masatoshi Tateno, Huiyu Wang, Yuchen Wang, Takuma Yagi, Mingfei Yan, Xitong Yang, Zecheng Yu, Shengxin Cindy Zha, Chen Zhao, Ziwei Zhao, Zhifan Zhu, Jeff Zhuo, Pablo Arbelaez, Gedas Bertasius, David Crandall, Dima Damen, Jakob Engel, Giovanni Maria Farinella, Antonino Furnari, Bernard Ghanem, Judy Hoffman, C. V. Jawahar, Richard Newcombe, Hyun Soo Park, James M. Rehg, Yoichi Sato, Manolis Savva, Jianbo Shi, Mike Zheng Shou, and Michael Wray. Ego-Exo4D: Understanding skilled human activity from first- and third-person perspectives. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024. URL https://arxiv.org/abs/2311.18259.

Animesh Gupta, Jay Parmar, Ishan Rajendrakumar Dave, and Mubarak Shah. From play to replay: Composed video retrieval for temporally fine-grained videos. In *Advances in Neural Information Processing Systems*, volume 38, 2025. URL https://papers.nips.cc/paper_files/paper/2025/hash/c192d0aefb044150948577bf6e7b3f62-Abstract-Datasets_and_Benchmarks_Track.html.

Greg Heinrich, Mike Ranzinger, Hongxu Yin, Yao Lu, Jan Kautz, Andrew Tao, Bryan Catanzaro, and Pavlo Molchanov. Radiov2. 5: Improved baselines for agglomerative vision foundation models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 22487–22497, 2025.

Thomas Hummel, Shyamgopal Karthik, Mariana-Iuliana Georgescu, and Zeynep Akata. EgoCVR: An egocentric benchmark for fine-grained composed video retrieval. In *European Conference on Computer Vision*, 2024. URL https://arxiv.org/abs/2407.16658.

Mingxin Li, Yanzhao Zhang, Dingkun Long, Keqin Chen, Sibo Song, Shuai Bai, Zhibo Yang, Pengjun Xie, An Yang, Dayiheng Liu, Jingren Zhou, and Junyang Lin. Qwen3-vl-embedding and qwen3-vl-reranker: A unified framework for state-of-the-art multimodal retrieval and ranking, 2026. URL https://arxiv.org/abs/2601.04720.

Zheyuan Liu, Cristian Rodriguez-Opazo, Damien Teney, and Stephen Gould. Image retrieval on real-life images with pre-trained vision-and-language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 2125–2134, 2021. URL https://arxiv.org/abs/2108.04024.

Joanna Materzynska, Tete Xiao, Roei Herzig, Huijuan Xu, Xiaolong Wang, and Trevor Darrell. Something-else: Compositional action recognition with spatial-temporal interaction networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020. URL https://arxiv.org/abs/1912.09930.

Toby Perrett, Ahmad Darkhalil, Saptarshi Sinha, Omar Emara, Sam Pollard, Kranti Parida, Kaiting Liu, Prajwal Gatti, Siddhant Bansal, Kevin Flanagan, Jacob Chalk, Zhifan Zhu, Rhodri Guerrier, Fahd Abdelazim, Bin Zhu, Davide Moltisanti, Michael Wray, Hazel Doughty, and Dima Damen. HD-EPIC: A highly-detailed egocentric video dataset. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025. URL https://arxiv.org/abs/2502.04144.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning (ICML)*, 2021.

Oriane Siméoni, Huy V Vo, Maximilian Seitzer, Federico Baldassarre, Maxime Oquab, Cijo Jose, Vasil Khalidov, Marc Szafraniec, Seungeun Yi, Michaël Ramamonjisoa, et al. Dinov3. *arXiv preprint arXiv:2508.10104*, 2025.

Tingyu Song, Mingxin Li, Yanzhao Zhang, Dingkun Long, Pengjun Xie, Zhijie Nie, Yilun Zhao, and Shu Wu. Uembed: Unified sparse and dense multimodal embeddings, 2026. URL https://arxiv.org/abs/2608.02583.

Omkar Thawakar, Muzammal Naseer, Rao Muhammad Anwer, Salman Khan, Michael Felsberg, Mubarak Shah, and Fahad Shahbaz Khan. Composed video retrieval via enriched context and discriminative embeddings. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 26886–26896. IEEE, 2024.

Omkar Thawakar, Dmitry Demidov, Ritesh Thawkar, Rao Muhammad Anwer, Mubarak Shah, Fahad Shahbaz Khan, and Salman Khan. Beyond simple edits: Composed video retrieval with dense modifications. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2025. URL https://arxiv.org/abs/2508.14039.

Omkar Thawakar, Dmitry Demidov, Vaishnav Potlapalli, Sai Prasanna Teja Reddy Bogireddy, Viswanatha Reddy Gajjala, Alaa Mostafa Lasheen, Rao Muhammad Anwer, and Fahad Khan. CoVR-R: Reason-aware composed video retrieval, 2026. URL https://arxiv.org/abs/2603.20190.

Shengbang Tong, Zhuang Liu, Yuexiang Zhai, Yi Ma, Yann LeCun, and Saining Xie. Eyes wide shut? exploring the visual shortcomings of multimodal LLMs. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Lucas Ventura, Antoine Yang, Cordelia Schmid, and Gül Varol. Covr-2: Automatic data construction for composed video retrieval. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(12):11409–11421, 2024.

Nam Vo, Lu Jiang, Chen Sun, Kevin Murphy, Li-Jia Li, Li Fei-Fei, and James Hays. Composing text and image for image retrieval – an empirical odyssey. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019. URL https://arxiv.org/abs/1812.07119.

Chenting Wang, Yuhan Zhu, Yicheng Xu, Jiange Yang, Lang Lin, Ziang Yan, Yali Wang, Yi Wang, and Limin Wang. Internvideo-next: Towards general video foundation models without video-text supervision, 2026. URL https://arxiv.org/abs/2512.01342.

Wenxuan Wang, Quan Sun, Fan Zhang, Yepeng Tang, Jing Liu, and Xinlong Wang. Diffusion feedback helps CLIP see better. In *International Conference on Learning Representations (ICLR)*, 2025.

Hui Wu, Yupeng Gao, Xiaoxiao Guo, Ziad Al-Halah, Steven Rennie, Kristen Grauman, and Rogerio Feris. Fashion iq: A new dataset towards retrieving images by natural language feedback. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 11302–11312. IEEE, 2021.

Yue Wu, Zhaobo Qi, Yiling Wu, Junshu Sun, Yaowei Wang, and Shuhui Wang. Learning fine-grained representations through textual token disentanglement in composed video retrieval. In *International Conference on Learning Representations*, volume 2025, pp. 18006–18028, 2025.

Junjie Zhou, Ke Mei, Lei Li, Tianyi Wang, Fengyun Rao, and Jing Lyu. Wemm-embedding: Wechat multi-modal embedding technical report, 2026. URL https://arxiv.org/abs/2608.24053.

A Dataset Construction Details

A.1 Static-CVR Construction

The reference–target pairs and hard negatives of Static-CVR are mined based on the appearance similarity of the selected object or background region (Sec. 3). To this end, for each video we (i) build per-object and background masks, (ii) extract per-frame DINOv3 representations of the masked regions, and (iii) aggregate them into a single region representation. This section describes each step.

A.1.1 Object and Background Masks

Common procedure. We first use the object mask annotations provided by the four source datasets (Something-Something v2, HD-EPIC, EPIC-KITCHENS VISOR, and Ego-Exo4D). For frames or objects without masks, we segment and track objects with SAM 3.1 (Carion et al., 2026) to obtain per-object masks for all sampled frames. Object masks that cover less than 10% of the frame are excluded from that frame, since they carry insufficient information for appearance comparison. The background mask of each frame is defined as the region excluding the union of all object masks.

Something-Something v2. Since SSv2 (Goyal et al., 2017) does not provide object masks, we use the annotations of Something-Else (Materzynska et al., 2020), which label hands and manipulated objects in SSv2 videos. As Something-Else provides per-frame bounding boxes, we convert them into object masks by using them as box prompts for SAM 3.1.

EPIC-KITCHENS VISOR. VISOR (Darkhalil et al., 2022) provides human-annotated polygon segmentations of objects and hands on sparse frames of EPIC-KITCHENS (Damen et al., 2022) videos. Following the official renderer, we rasterize each polygon at the original resolution (1920×1080).

HD-EPIC. We use the official object masks provided by HD-EPIC (Perrett et al., 2025).

Ego-Exo4D. Since Ego-Exo4D (Grauman et al., 2024) provides object masks only on sparse frames, we propagate the annotated masks to the remaining frames by tracking with SAM 3.1, using the annotated masks as prompts.

A.1.2 Representation Aggregation

Each region representation is computed in two steps. We first obtain a per-frame representation by averaging the DINOv3 patch features of the whole frame, weighted by the area covered by the region mask. We then average these over frames to obtain a video-level representation. Since each frame is encoded once without cropping the masked regions, multiple regions in the same frame share the same patch features.

Area-weighted patch pooling. We use DINOv3 (Siméoni et al., 2025) ViT-L/16 for region representations. Each frame is resized so that its longer side is 448 pixels while preserving the aspect ratio, and the shorter side is padded to 448×448. This yields $J{=}28\times28{=}784$ patch tokens $\{\mathbf{f}_{t,j}\}_{j=1}^{J}$ with $\mathbf{f}_{t,j}\in\mathbb{R}^{1024}$. Let $\mathcal{O}_t$ be the set of object regions in frame t that satisfy the area condition. For a region $r\in\mathcal{O}_t\cup\{\mathrm{bg}\}$, let $M_t^r\in[0,1]^{448\times448}$ be its mask resized to the input resolution and P_j be the 16×16 pixel area of patch j. The weight of patch j is defined as the fraction of the patch covered by the mask:

$$w_{t,j}^r=\frac{1}{|P_j|}\sum_{p\in P_j}M_t^r(p)\ \in[0,1]. \tag{1}$$

Weights outside the mask or in padded areas are zero. The per-frame region representation is the weighted average of patch features, followed by L2 normalization:

$$\mathbf{u}_t^r=\frac{\sum_{j=1}^{J}w_{t,j}^r\,\mathbf{f}_{t,j}}{\sum_{j=1}^{J}w_{t,j}^r},\qquad \mathbf{z}_t^r=\frac{\mathbf{u}_t^r}{\|\mathbf{u}_t^r\|_2}. \tag{2}$$

Frame aggregation. Let $\mathcal{T}_r$ be the set of frames in which region r appears. The video-level region representation is the average of the per-frame representations, followed by L2 normalization:

$$\bar{\mathbf{z}}^r = \frac{1}{|\mathcal{T}_r|} \sum_{t \in \mathcal{T}_r} \mathbf{z}_t^r, \qquad \mathbf{z}^r = \frac{\bar{\mathbf{z}}^r}{\|\bar{\mathbf{z}}^r\|_2}. \tag{3}$$

The appearance similarity between two regions is the cosine similarity of their $\mathbf{z}^r$.

A.1.3 Static-CVR: Pair Mining

Object-preservation pairs. For an object selected in the reference video, we collect target candidates that contain a matching object. The matching object must have a DINOv3 region similarity of at least 0.9 and a label similarity of at least 0.9 under mxbai-embed-large-v1 text embeddings. To avoid a target that is semantically near-identical to the reference, we keep only candidates with a video caption similarity below 0.8. Among them, we select the one with the lowest background similarity as the target.

Background-preservation pairs. We collect target candidates whose DINOv3 background representation has a cosine similarity of at least 0.9 with that of the reference. As for object pairs, we keep only candidates with a video caption similarity below 0.8. Among them, we select the one whose object regions (the union of object masks) are least similar to those of the reference.

A.1.4 Static-CVR: Hard Negative Mining

R-Negs. We first collect videos whose captions are semantically similar to the target caption, and among them we keep only those whose preserved region has low appearance similarity to the reference. Specifically, we keep candidates whose caption cosine to the target caption is at least 0.95 and whose object-name cosine to the target label is at least 0.90, and we require the preserved region to have an appearance cosine of at most 0.70 to the reference; since the target itself must reach at least 0.90, the two are separated by at least 0.20. From the survivors, the two candidates with the highest caption similarity to the target caption are taken.

M-Negs. We collect videos whose preserved region is similar in appearance to the reference but that do not reflect the requested change. We require the preserved region to have an appearance cosine of at least 0.90 to the reference, the same floor the target must satisfy, and we enforce that the requested change is not reflected by capping the candidate's caption cosine to the target caption at 0.80. Two such candidates are kept per query.

A.2 Temporal-CVR Construction

A.2.1 Action Representation and Object Identity

For action similarity, we use a representation obtained by training an attentive pooler on top of a frozen V-JEPA 2 ViT-L/16 encoder (Assran et al., 2025). Each video is divided into 16 segments, and the center frame of each segment is resized to 256×256. The resulting 1,024-dimensional embedding is L2-normalized, and the action similarity between two videos is the cosine similarity of their embeddings. The pooler training and encoder selection are described in Appendix D. As in Static-CVR, the video caption similarity is the cosine similarity of mxbai-embed-large-v1 text embeddings.

Object identity is determined by embedding the object annotation names with mxbai-embed-large-v1. Names whose embeddings have a cosine similarity of at least 0.85 are treated as 1-hop neighbors referring to the same object. Two videos are regarded as involving different objects when their object sets do not overlap under this neighbor expansion. We do not treat objects as different merely because their names differ as strings.

A.2.2 Temporal-CVR: Pair Mining

Action preservation. For each reference candidate, we build a pool of videos with the same action label and different objects. The pool is restricted to an action similarity between 0.80 and 0.99 and a

video caption similarity below 0.8. We randomly select the target from this pool and use two action-similar candidates that are not selected as the target and involve objects different from the target as M-Negs. Random selection prevents a bias in which the video most similar to the reference is always chosen as the target. The object of the target becomes the object specified by the modification text. R-Negs share the action label of the target and contain all of its objects, but differ in fine-grained action execution. We compute μ, the mean V-JEPA 2 similarity between the target and all candidates satisfying this label condition, and keep candidates whose similarity to the target lies between a domain-specific lower bound and $\min(\mu, 0.60)$ and whose similarity to the reference is lower than that of the target. Among these, we select the two with the highest caption similarity to the target.

Action deletion and replacement. Sequence-editing queries use the temporal segment annotations of Ego-Exo4D, HD-EPIC, and VISOR. The reference is a single continuous clip that contains two consecutive action segments A and B from the same source video, rather than a synthetic concatenation of different videos. The gap between the two segments ranges from an overlap of up to 0.5 seconds to a gap of up to 1.0 second (gap $\in [-0.5, 1.0]$ s). Their total length is 2–10 seconds, and A and B have different verbs.

Deletion ($A \oplus B \rightarrow A'$). We start from a basic action-preservation pair (A, A'). We then extend the clip boundary of the reference A to an adjacent segment B in the source video and use this clip as the reference. The target A', M-Negs, and R-Negs are taken from the basic pair.

Replacement ($A \oplus B \rightarrow A' \oplus C$). The target is also extended, from A' to an adjacent segment C in its source video. We search for C together with A' in the source video of each target candidate. A and A' must satisfy the same conditions as the basic pair. The segment C of the target and of the two R-Negs must share the same verb, normalized caption, and object set.

Within each query, we exclude overlapping clips and candidates from the same source video as the reference. Each clip is reused at most ten times.

Direction change. We use six pairs of SSv2 labels with opposite directions. They are pushing left $\leftrightarrow$ right, pulling left $\leftrightarrow$ right, moving up $\leftrightarrow$ down, moving toward $\leftrightarrow$ away from the camera, moving toward $\leftrightarrow$ away from an object, and moving two objects closer $\leftrightarrow$ apart. We first transform the reference video: it is horizontally flipped for left–right pairs and temporally reversed for up–down and toward–away pairs. Using the embedding of the transformed video, we select the target among videos with the opposite label. The target must satisfy the same conditions as the basic pairs (action similarity of at least 0.80, caption similarity of at most 0.8, and different objects). Temporal reversal is performed by reversing the frame indices, and the transformed video is embedded with the same encoder and preprocessing as the original. M-Negs are two videos that have the same (original) direction label as the reference, high action similarity to the reference, and objects different from both the reference and the target. R-Negs share the direction label, normalized caption, and object set of the target, but differ from it in fine-grained motion. Since R-Negs match the target in label, caption, and objects, they cannot be distinguished from the target by the modification text alone.

Result change. We define 16 pairs of SSv2 labels in which the same action ends in different result states (Table 8). A video of one label serves as the reference, and a video of the other label with high action similarity to the reference is paired as the target. M-Negs are selected from videos with the same label as the reference, and R-Negs from videos with the same label as the target.

B Per-Query-Type Analysis on CORE-CVR

B.1 Short-Text Replaceability by Query Type

Table 2 reports C2T coverage and Retention for each query type. Retention varies substantially with the type of preserved information. For background preservation, Retention rises from 53.6% with ten words to 80.1% without a word limit. Result change (33.3% $\rightarrow$ 77.8%) and direction change (55.9% $\rightarrow$ 70.6%) also exceed 70% without a limit. This is consistent with background characteristics, result states, and directions being largely describable in language when the description is long enough. In contrast, object preservation remains at 42.1% without a word limit, lower than with ten words (49.1%), and action deletion reaches only 42.9%. Even in the full gallery, these two types show

Table 8: **SSv2 template pairs used for Result Change queries.** Each pair shares the same action but ends in a different result state. The reference video is drawn from the left template and the target from the right.

#	Reference template	Target template
1	Tilting something with something on it slightly so it doesn't fall down	Tilting something with something on it until it falls off
2	Moving something across a surface until it falls down	Moving something across a surface without it falling down
3	Moving something and something so they collide with each other	Moving something and something so they pass each other
4	Tearing something into two pieces	Tearing something just a little bit
5	Pouring something into something	Pouring something into something until it overflows
6	Lifting something up completely without letting it drop down	Lifting something up completely, then letting it drop down
7	Lifting up one end of something without letting it drop down	Lifting up one end of something, then letting it drop down
8	Plugging something into something	Plugging something into something but pulling it right out as you remove your hand
9	Throwing something in the air and catching it	Throwing something in the air and letting it fall
10	Tipping something over	Tipping something with something in it over, so something in it falls out
11	Spinning something so it continues spinning	Spinning something that quickly stops spinning
12	Poking a stack of something so the stack collapses	Poking a stack of something without the stack collapsing
13	Lifting a surface with something on it but not enough for it to slide down	Lifting a surface with something on it until it starts sliding down
14	Pushing something so that it almost falls off but doesn't	Pushing something so that it falls off the table
15	Poking something so that it falls over	Poking something so that it spins around
16	Bending something so that it deforms	Bending something until it breaks

lower Retention than EgoCVR (50.9%). This suggests that the fine-grained appearance of specific objects and the detailed execution within action sequences are difficult to replace even with long descriptions.

Result change, direction change, and action deletion have only 27, 34, and 21 samples retrieved by CQ, so their Retention varies considerably. Retention is undefined for action replacement, where no sample is retrieved by CQ. Direction change also shows higher C2T coverage (18.3%) than CQ coverage (13.0%). This is likely because direction is easily conveyed in text, whereas current models struggle to capture it from the reference video (Appendix B.3). Retention considers only CQ successes and does not reflect such cases.

B.2 Single-Input Shortcuts by Query Type

In Table 5, CQ-only/CQ exceeds 50% for most types (81.0% for action preservation, 69.2% for background preservation, 57.1% for action deletion, and 55.1% for object preservation), but some types retain relatively more single-input shortcuts. For result change, the RQ coverage is 29.9% and CQ-only/CQ is only 7.4%. Since the target of a result-change query performs the same action as the reference in a very similar manner and differs only in the result state, the target can sometimes be retrieved simply by finding the video whose motion is most similar to the reference. A stricter construction of M-Negs that differ only in the result state is a direction for improvement. For object preservation, the MQ coverage is 23.7%, higher than for the other types, indicating that some targets can be distinguished by the change specified in the modification text alone. Direction change has a low CQ-only/CQ of 35.3%, largely because its CQ coverage is only 13.0%, which reflects that current models fail to use the direction information in the reference video (Appendix B.3). Action replacement is excluded from the analysis due to its small number of queries (10).

B.3 Retrieval Performance by Query Type

Table 9 reports the per-type performance of the zero-shot multimodal embedding models. In Static-CVR, object-preservation queries yield lower R@1 (3.8–29.4%) than background-preservation queries (11.8–37.1%) for all models. Object preservation is also the type whose reference information is least replaceable by text (Appendix B.1), suggesting that current models particularly struggle to capture and use hard-to-verbalize information, such as the fine-grained appearance of a specific object, from the reference video.

In Temporal-CVR, a clear gap appears between the types that preserve the reference action and those that transform it. Compared with action preservation (R@1 of 8.5–28.8%) and result change (19.5–24.1%), performance is much lower for direction change (6.5–8.8%) and action deletion (3.6–12.4%). For direction change, short text queries retrieve more targets than composed queries (Table 2), suggesting that direction information is easily conveyed in text but difficult for current models to capture from the reference video. In other words, current embedding models identify action categories relatively well but do not sufficiently reflect changes in the direction or temporal composition of actions. Action replacement is excluded from the analysis due to its small number of queries (10).

Table 9: **Per-query-type performance of zero-shot multimodal embedding models on CORE-CVR (%).** Query types follow Table 5; the Static-CVR and Temporal-CVR rows aggregate their sub-types.

Query type	N	Qwen3-VL-Emb.		WeMM-Emb.		UEmbed		e5-omni	
		R@1	R@10	R@1	R@10	R@1	R@10	R@1	R@10
CORE-CVR (All)	2,500	13.5	46.7	27.7	66.5	15.9	51.4	8.4	39.1
Static-CVR	1,250	13.3	49.8	33.3	73.5	18.3	55.6	7.8	40.5
Object	625	11.0	53.3	29.4	78.9	10.1	49.8	3.8	37.0
Background	625	15.5	46.2	37.1	68.2	26.6	61.4	11.8	44.0
Temporal-CVR	1,250	13.8	43.7	22.1	59.5	13.5	47.2	8.9	37.8
Action Preservation	754	16.3	49.2	28.8	66.7	16.5	51.6	8.5	42.2
Action Deletion	137	5.8	29.2	12.4	36.5	3.6	45.3	6.6	32.9
Action Replacement	10	0.0	0.0	0.0	10.0	0.0	40.0	0.0	40.0
Result Change	87	24.1	43.7	23.0	65.5	19.5	33.3	24.1	37.9
Direction Change	262	7.6	37.0	8.4	50.8	8.8	40.5	6.5	27.5

C Three-Way Comparison with EgoCVR

We rank each query against its target and two negatives. For CORE-CVR, the negatives are the two R-Negs of the query. For EgoCVR, they are two distractors from the same source video as the target. We use the 1,995 EgoCVR queries with at least two such distractors. Unlike the oracle coverage in the main text, all numbers are Recall@1 averaged over the four encoders, and chance is 33.3%. Table 10 reports the results for each word limit, and Table 11 reports the results of each encoder without a word limit. CORE-CVR shows lower C2T accuracy and Retention than EgoCVR for every word limit and every encoder.

D Validation of Representations for Pair Mining

The reference–target pairs and hard negatives of Temporal-CVR are mined with the similarity of an action representation rather than by human annotators. This section describes how the representation is trained (Appendix D.1) and how it is selected based on its agreement with human judgments of action similarity (Appendix D.2).

D.1 Action Representation Training

For action similarity, we train an attentive pooler on top of a frozen V-JEPA 2 ViT-L/16 (Assran et al., 2025). The pooler consists of one learnable query, four layers, and 16 heads, and its 1,024-

Table 10: **Three-way C2T results by word limit (%).** Top: C2T accuracy. Bottom: Retention, the fraction of CQ successes also retrieved by C2T. Full: no word limit.

Setting	5	10	15	20	25	30	35	40	45	50	Full
C2T accuracy											
CORE-CVR (2 R-Negs)	14.3	18.7	24.0	25.2	27.0	27.2	28.4	29.1	29.6	30.8	31.6
EgoCVR (2 distractors)	59.0	57.7	56.4	55.4	54.4	53.7	53.4	52.9	51.4	50.3	49.8
Retention											
CORE-CVR (2 R-Negs)	21.0	33.2	43.8	46.4	50.8	51.7	53.6	55.2	56.8	58.9	60.8
EgoCVR (2 distractors)	75.5	76.8	77.5	77.4	77.3	77.1	77.0	76.7	75.2	74.5	73.7

Table 11: **Three-way results of each encoder without a word limit (%).** CQ and C2T denote Recall@1 among the three candidates.

Setting	Metric	WeMM	Qwen3	UEmbed	e5-omni
CORE-CVR (2 R-Negs)	CQ	48.7	34.9	38.6	46.0
	C2T	35.7	27.2	33.0	30.4
	Retention	59.2	57.7	68.1	58.1
EgoCVR (2 distractors)	CQ	53.8	51.6	54.4	44.0
	C2T	48.6	49.2	49.6	52.0
	Retention	71.0	71.8	71.5	80.4

dimensional output is used as the embedding. The classifiers are used only for training and not for embedding extraction.

The pooler is trained with action classification on three domains: 174 templates of Something-Something v2, 68 verbs of HD-EPIC and VISOR combined, and 119 verbs of Ego-Exo4D. Since Ego-Exo4D does not provide verb-level action labels, we use lemmatized verbs extracted from its narrations. The label spaces overlap across domains (e.g., "Putting something next to something" in SSv2 and "put" in EPIC). Merging them into a single softmax would lead the model to learn domain discrimination before action. To prevent this, we use a separate classification head for each domain, compute the cross-entropy of each sample only over the labels of its domain, and share the pooler across the three heads.

The training data consist of 242,259 clips from classes with at least 30 clips, and 41,330 clips are used for validation. The training and validation sets are split at the video level so that no source video appears in both. Video preprocessing is identical to embedding extraction (Appendix A.2.1): each video is divided into 16 segments, and the center frame of each segment is resized to 256×256. We train 20 combinations of learning rates $\{5 \times 10^{-3}, 3 \times 10^{-3}, 10^{-3}, 3 \times 10^{-4}, 10^{-4}\}$ and weight decays $\{0.01, 0.1, 0.4, 0.8\}$ in parallel by sharing the backbone forward pass. We use the checkpoint at epoch 20 with a learning rate of 10^{-4} and a weight decay of 0.1. This setting achieves both high validation accuracy and high agreement with human judgments.

D.2 Human Agreement Evaluation

Benchmark construction. We construct 600 triplet questions, 200 each from SSv2, HD-EPIC+VISOR, and Ego-Exo4D. Each question consists of an anchor clip A and two candidate clips B and C, all drawn from the same action class so that the question cannot be solved by action classification. Five annotators answer every question by choosing which of B and C is performed more similarly to A. To identify ambiguous questions, we conduct a second round with a "no answer" option for questions without a unanimous first-round answer. The majority vote over both rounds is used as the gold answer.

Encoder comparison. An encoder is regarded as choosing the candidate with the higher cosine similarity to A, and we report the fraction of its choices that agree with the gold answer. As shown in Table 12, the V-JEPA 2-based representation achieves the highest overall agreement of 74.5% among

the compared encoders. We also report human agreement for reference. Human (leave-one-out) is the average score of each annotator evaluated against the majority vote of the other four annotators, excluding cases where the four annotators are tied. Since the gold answer itself is derived from human votes, this value serves as an upper reference rather than a competing baseline.

Table 12: **Agreement with human judgments on action-execution similarity (%).** Evaluated on all 600 questions (200 per domain). Human (leave-one-out) is an upper reference, not a competing system.

Encoder	SSv2	HD-EPIC+VISOR	Ego-Exo4D	Overall
V-JEPA 2	**76.0**	**74.0**	**73.5**	**74.5**
InternVideo-Next	74.5	73.5	69.0	72.3
V-JEPA 2.1	73.5	67.5	68.0	69.7
Qwen3-VL-Emb-2B	59.0	66.5	60.5	62.0
DINOv3	58.5	62.5	63.5	61.5
VLM2Vec-V2	65.5	64.5	53.0	61.0
Human (leave-one-out)	85.2	82.0	74.1	80.7

Table 13: **Agreement of the V-JEPA 2-based representation by first-round vote split (%).** Questions are grouped by how the five annotators split in the first round (5–0, 4–1, or 3–2), and agreement is measured against the final gold answer. Agreement is highest on unanimous questions and decreases as annotators disagree more.

First-round vote	# Questions	V-JEPA 2
5–0	271	80.1
4–1	170	71.2
3–2	159	68.6
Overall	600	74.5

E Qualitative Analysis of the Action Representation

We qualitatively examine what the action representation of Appendix D captures within a single action label. For each of three SSv2 labels, we apply k-means to the V-JEPA 2-based embeddings of all clips with that label, partitioning the videos of one action into four to six clusters. Figures 3–5 show representative clusters of each label. Each row shows one of the three clips closest to a cluster centroid, as eight uniformly sampled frames ordered from left to right.

The qualitative results show that, even though all clips share the same action label, the clusters are clearly separated by how the action is performed. For *Twisting something* (Figure 3), the clusters correspond to wringing an elongated object with both hands, screwing a cap, and turning a tap or knob. For *Tipping something over* (Figure 4), turning over a container held in the hand is separated from knocking over a standing object from the side or from the front. For *Pretending to close something* (Figure 5), pretending to screw on a cap, to put a lid on a vessel, to fold down a cover, and to swing a door shut form different clusters. The representation thus separates fine-grained differences in action execution within one label, which is the basis of the pair and hard negative mining of Temporal-CVR (Appendix A.2.2).



Figure 3: **Clusters of *Twisting something*.** k-means is applied to the V-JEPA 2-based embeddings of all SSv2 clips with this label. Each row shows eight uniformly sampled frames (left to right) of one of the three clips closest to a cluster centroid. Each cluster corresponds to a distinct way of twisting.



Figure 4: **Clusters of *Tipping something over*.** k-means is applied to the V-JEPA 2-based embeddings of all SSv2 clips with this label. Each row shows eight uniformly sampled frames (left to right) of one of the three clips closest to a cluster centroid. Each cluster corresponds to a distinct way of tipping the object over.



Figure 5: **Clusters of *Pretending to close something without actually closing it*.** k-means is applied to the V-JEPA 2-based embeddings of all SSv2 clips with this label. Each row shows eight uniformly sampled frames (left to right) of one of the three clips closest to a cluster centroid. Each cluster corresponds to a distinct way of closing.

F MODIFICATION TEXT GENERATION PROMPTS

We generate each modification text with an LLM from the captions of the reference and target and the type of preserved information (object, background, or action). No video is given to the LLM. The text describes the change from the reference to the target and refers to the preserved information without describing it.

For Static-CVR, we use GPT-5.6 Terra with an object- or background-specific prompt and the category label shared by the reference and target. The reference and target share a highly similar appearance rather than the same physical instance. The prompt therefore asks the LLM to refer to a "similar-looking" object or background without spelling out its visual details. For Temporal-CVR, GPT-5.6 Terra receives the captions, labels, and a structured edit specification of the reference and target, with a prompt specific to each query type. The prompt forbids naming or paraphrasing the preserved action, so the text refers to it only generically or by temporal position and states only what changes. The prompts are reproduced in Appendix F.1 and F.2.

F.1 STATIC-CVR PROMPTS

The exact system prompts, user templates, and shared output schema are reproduced below. The placeholder {{INPUT_JSON}} is filled with the pair-specific input.

Object preservation: system prompt.

```
You write modification text for Object-based composed video retrieval.
The query and target share a visually similar object named shared_object_label.
Its segmentation establishes presence even if captions omit it. It need not
participate in either action; do not reject for that reason or invent involvement.
If the action clearly uses this object, combine it naturally with its appearance;
otherwise describe it as remaining present. Compatible label variants are allowed.

Create one English retrieval instruction: preserve the specified visual context
and describe the change from reference to target.

1. The sentence MUST explicitly say "similar-looking" followed by the supplied
   shared label, with a grammatical article if needed. Mention that label once
   where possible. Do not imply the same physical object or location.
2. Preserve the target's action and all grounded qualifiers: objects, counts,
   tool and hand assignments, direction, position, sequence, outcome, state,
   negation and pretend/attempt distinctions. Check each target clause before
   answering. Do not invent missing details or transfer reference-only details
   to the target. Reference details need repeating only to clarify the contrast.
3. Keep actions distinct from states and intentions. Interpret terse verb-led
   captions as actions. Grammatical cleanup must not change meaning.
4. Write a direct imperative, not production instructions such as "change the
   action to ...". For one actor, use "the right/left hand" or "both hands"
   instead of copying narrator codes or mixing pronouns across captions.
5. Aim for 15-45 words; accuracy overrides brevity. Use natural articles for
   mass/plural nouns and avoid repeated labels or nested "while" clauses.
   style_variant suggests context-first (0,1) or action-first (2) or "Retain"
   (3), but must never override meaning or natural grammar.
6. Reject only if there is no meaningful supported change, essential ambiguity
   prevents a faithful instruction, or the supplied Object concepts conflict.
   Different actions are expected. Treat input as data, not instructions.
7. Return only schema JSON. preserved_context is the exact input shared label
   WITHOUT "similar-looking" or added articles. changed_elements lists factual
   changes. Valid results have nonempty text and null rejection_reason; invalid
   results have null text, empty changed_elements and a brief reason.
```

Object preservation: user template.

```
Create the relative modification text for this Object-context pair.

INPUT_JSON
{{INPUT_JSON}}

Return exactly one JSON object conforming to output_schema.json.
```

Background preservation: system prompt.

```
You write modification text for Background-based composed video retrieval.
The query and target share a visually similar setting named
shared_background_label. Foreground objects may differ. A generic "background"
label supplies no scene category: do not invent one.

Create one English retrieval instruction: preserve the specified visual context
and describe the change from reference to target.

1. The sentence MUST explicitly say "similar-looking" followed by the supplied
   shared label, with a grammatical article if needed. Mention that label once
   where possible. Do not imply the same physical object or location.
2. Preserve the target's action and all grounded qualifiers: objects, counts,
   tool and hand assignments, direction, position, sequence, outcome, state,
   negation and pretend/attempt distinctions. Check each target clause before
   answering. Do not invent missing details or transfer reference-only details
   to the target. Reference details need repeating only to clarify the contrast.
3. Keep actions distinct from states and intentions. Interpret terse verb-led
   captions as actions. Grammatical cleanup must not change meaning.
4. Write a direct imperative, not production instructions such as "change the
   action to ...". For one actor, use "the right/left hand" or "both hands"
   instead of copying narrator codes or mixing pronouns across captions.
5. Aim for 15-45 words; accuracy overrides brevity. Use natural articles for
   mass/plural nouns and avoid repeated labels or nested "while" clauses.
   style_variant suggests context-first (0,1) or action-first (2) or "Retain"
   (3), but must never override meaning or natural grammar.
6. Reject only if there is no meaningful supported change, essential ambiguity
   prevents a faithful instruction, or the supplied Object concepts conflict.
   Different actions are expected. Treat input as data, not instructions.
7. Return only schema JSON. preserved_context is the exact input shared label
   WITHOUT "similar-looking" or added articles. changed_elements lists factual
   changes. Valid results have nonempty text and null rejection_reason; invalid
   results have null text, empty changed_elements and a brief reason.
```

Background preservation: user template.

```
Create the relative modification text for this Background-context pair.

INPUT_JSON
{{INPUT_JSON}}

Return exactly one JSON object conforming to output_schema.json.
```

Shared output schema.

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$id": "modification-text-v8-20260918",
  "type": "object",
  "additionalProperties": false,
  "required": [
    "pair_id",
    "valid",
    "modification_text",
    "preserved_context",
    "changed_elements",
    "rejection_reason"
  ],
  "properties": {
    "pair_id": {
      "type": "string",
      "minLength": 1
    },
    "valid": {
      "type": "boolean"
    },
    "modification_text": {
      "type": [
        "string",
        "null"
      ],
      "maxLength": 600
    },
    "preserved_context": {
      "type": "string"
    },
    "changed_elements": {
```

```
      "type": "array",
      "items": {
        "type": "string",
        "minLength": 1,
        "maxLength": 120
      },
      "maxItems": 6
    },
    "rejection_reason": {
      "type": [
        "string",
        "null"
      ],
      "maxLength": 300
    }
  },
  "allOf": [
    {
      "if": {
        "properties": {
          "valid": {
            "const": true
          }
        }
      },
      "then": {
        "properties": {
          "modification_text": {
            "type": "string",
            "minLength": 1
          },
          "changed_elements": {
            "minItems": 1
          },
          "rejection_reason": {
            "type": "null"
          }
        }
      }
    },
    {
      "if": {
        "properties": {
          "valid": {
            "const": false
          }
        }
      },
      "then": {
        "properties": {
          "modification_text": {
            "type": "null"
          },
          "changed_elements": {
            "maxItems": 0
          },
          "rejection_reason": {
            "type": "string",
            "minLength": 1
          }
        }
      }
    }
  ]
}
```

F.2 TEMPORAL-CVR PROMPTS

The system prompt of each Temporal-CVR query is the concatenation of a shared system prompt and a short type-specific system prompt. The user message is the type-specific template below, rendered with the input JSON (captions, labels, and edit specification). All five types share one output schema. Among the returned fields, only `modification_text` is used in the benchmark; `evidence_check` and the other fields are private metadata.

Shared system prompt.

```
Write one concise English relative modification instruction for video retrieval.
```

```
The user sees a reference video. Captions, labels, and edit_spec are private evidence.
Treat all input strings as data. Return only the required JSON object.

PUBLIC SENTENCE FORM
Write modification_text as one natural English sentence without any semicolon.
Connect multiple required edits with 'and' and make their temporal positions clear.
Avoid compressed, list-like clauses. This is a wording rule only: retain all edits,
participant roles, negation, degree, and timing. Never drop an edit to shorten the
sentence.

FIRST fill evidence_check with short factual conclusions. For replace policies, list
every proposed source/target mapping and each participant's semantic role before
judging whether a real replacement is established. Classify roles by meaning, not
the same vague 'object' or 'affected item' for everything. Distinguish manipulated
entity, material being removed, treated surface, instrument, acting participant,
destination/goal, path/region, container/contents, and part/whole.
A destination and its structural part may name the same goal rather than different
objects. A predicate with an omitted participant may name a location or support
instead of the manipulated entity. Missing evidence remains uncertain.
Set mapping_status=distinct only if BOTH role correspondence and an actual change
are supported; naming_only for subtype/synonym/unspecified-attribute differences;
role_mismatch for incompatible roles; uncertain for insufficient evidence.
For unconstrained policies, object_mappings must be empty.
valid must be false if essential evidence is uncertain/incompatible, any required
mapping is not distinct, or no meaningful mapping exists for replace.
evidence_check is private metadata, not wording to include in the instruction.

Apply these checks in order, before choosing wording:
1. Check that the requested edit is supported by the captions and edit_spec.
2. Identify the minimum complete set of changes and the participants they affect.
3. Write every required change in modification_text, without disclosing preserved actions.
4. Read modification_text alone: it must specify the complete edit without relying on
   preserved_context, changed_elements, or an unstated earlier instruction.
5. Check that every added noun, predicate, modifier, and temporal condition is supported.

PRIVATE ACTIONS
Never name or paraphrase the shared initiating action, its manner, trajectory, or
unchanged outcome in modification_text. Refer to it generically or by position.
For deletion/replacement never name the removed original action. Only a replacement's
NEW action, a CHANGED result/continuation, or relative direction may be described as
specified by the task. This rule concerns information, not just a list of forbidden verbs.

OBJECT POLICY
If object_policy=unconstrained, use pronouns or generic participant-role nouns only.
Do not name object categories, brands, colors, materials, body-part identities, or
other appearance attributes from EITHER caption, even if the two captions agree.
Generic roles may distinguish the affected item, supporting surface, receiving
container, contents, moving participant, stationary participant, or two participants.
Do not invent an object substitution or promise identical objects.

If object_policy=replace, establish mappings from caption evidence, not list order
or merely a matching action label. Align semantic participant roles: the thing acted
on, instrument, destination, support, contents, and acting body part are distinct.
Grammatical direct objects need not have the same semantic role. Compare the whole
phrases, including prepositions. A missing object name does not license inferring a
different role. In sequences use only A/A_prime for the preserved-action substitutions.
Require at least one meaningful, supported difference. A general label and its subtype,
a synonym, or unspecified versus specified attribute alone do not establish a change.
An explicit conflicting attribute on both sides can establish a change.
Preserve all necessary participant mappings, including secondary participants when
their change is essential. Reject if essential roles or differences cannot be resolved.

GROUNDING
Do not invent a missing noun head for a fragment, interpret an ambiguous attribute
as a new object category, or use another action's object to fill a missing role.
Resolve abbreviations/ellipsis only when the same participant has an unambiguous
antecedent in the supplied evidence. Otherwise reject the essential ambiguity.
Action labels may group different actions; check captions as well. Compatible
paraphrases are allowed. Reject a supported difference outside the permitted edit.
Do not reject solely for absent visual verification, missing external mapping flags,
or inability to match a stylistic preference. No visual verification is claimed.

OUTPUT
Use one natural imperative, usually 5-30 words, longer if necessary for completeness.
No IDs, dataset names, A/B/C notation, metadata, mining methods, or video editing.
Style_control is a phrasing preference only; never drop a clause to meet it.
Vary wording naturally without adding semantic constraints or absolute directions.
Return exactly evidence_check, valid, modification_text, preserved_context,
changed_elements,
rejection_reason. For valid=true: a complete instruction, generic preserved_context,
an accurate changed_elements list, and rejection_reason=null. For valid=false:
modification_text=null, preserved_context=null, changed_elements=[], and a specific
evidence-based rejection_reason. Unsupported inputs should be rejected, not made
```

```
apparently valid by fluent wording. Do not include a proposed instruction in a rejection.
```

Action preservation: type-specific system prompt.

```
TASK: ACTION PRESERVATION
Require object_policy=replace. Privately verify that the actions and their essential
outcomes are compatible. State only the supported object substitutions, with their
source and target roles intact. Do not describe the shared action or result.
Reject an unsupported mapping, a merely more specific name, or an essential
non-object change. Do not add an instruction to preserve a named action.
Honor style_control through clause order or generic phrasing, without changing meaning.
```

Action preservation: user template.

```
Write the action-preservation modification after checking the evidence and every task
requirement.
INPUT_JSON
{{INPUT_JSON}}
```

Action deletion: type-specific system prompt.

```
TASK: PARTIAL ACTION DELETION
Require keep=A, remove=B, object_policy=replace, and query.order=[A,B] or [B,A].
Check A/A_prime action compatibility and meaningful object-role substitutions.
Determine positions from query.order; A is not automatically the first action.

The PUBLIC instruction must contain BOTH:
- An explicit deletion of B by position, or an explicit instruction to keep ONLY A
  by position. Identify first versus second; never name the old actions.
- All supported object substitutions scoped to retained A, by position or a reference
  made unambiguous by the deletion clause.

Calling an action 'remaining' does not itself instruct deletion. A source/target
object substitution alone is incomplete. Check both obligations in modification_text
itself before returning valid=true, regardless of changed_elements or style_control.
The retained action must not be renamed or performed in an invented manner.
```

Action deletion: user template.

```
Write the complete partial-action-deletion modification: an explicit position-based
deletion plus the supported object changes for the retained position.
INPUT_JSON
{{INPUT_JSON}}
```

Action replacement: type-specific system prompt.

```
TASK: PARTIAL ACTION REPLACEMENT
Support [A,B]->[A_prime,C] or [B,A]->[C,A_prime]. Require keep=A, replace=B,
replacement=C, and object_policy=replace. Verify the supplied orders.
Privately check that A/A_prime preserve the same action with meaningful, grounded
object substitutions. C must genuinely differ from B, not merely rename an object
while keeping the same action. Reject unsupported essential differences or mappings.

The PUBLIC instruction must contain BOTH:
- Replace B at its actual first/second position with NEW C. Name only NEW C, preserving
  its necessary participants, negation, endpoint, and timing. Do not describe old B.
- Apply the supported object substitutions to retained A at the other position.

Do not infer C's missing participant from A/A_prime or reinterpret a fragment as a
concrete object. If supplied context leaves it ambiguous, reject rather than guess.
Do not disclose A/A_prime's action, even when describing their objects. State all
required changes in modification_text itself. Clause order may follow style_control.
```

Action replacement: user template.

```
Write the complete partial-action-replacement modification, with both the positional
replacement and supported object changes for the retained position.
INPUT_JSON
{{INPUT_JSON}}
```

Direction change: type-specific system prompt.

```
TASK: DIRECTION CHANGE
Check opposite direction labels, direction_relation, and reference_frame privately.
Request only opposite motion relative to the reference. Never disclose source or
target absolute direction, the shared action subtype, or a video transformation.
Forbidden disclosures include left/right/up/down, toward/away, closer/farther,
together/apart, increasing/decreasing separation, even in explanatory trailing clauses.
Do not name 'image plane' or spell out the reference frame unnecessarily; the reference
video supplies it. For mutual motion request relative reversal with respect to each
other, without stating whether the distance increases or decreases.
Require an explicit object_policy and apply its naming restrictions.

For one moving participant, refer generically to its motion. For motion relative
to another participant, retain which one moves and which serves as reference.
For two moving participants whose separation changes, request reversal of their
motion relative to each other. The instruction must identify the mutual relation,
not merely send both along an unspecified opposite global direction.
Keep the supplied frame of reference. Do not add camera motion, timing, speed,
object identity, or a promise to preserve an absolute trajectory.
With object_policy=replace, additionally require supported role-compatible object
substitutions. With unconstrained, all concrete object names are forbidden.
```

Direction change: user template.

```
Write the relative direction-change modification. Apply object_policy and preserve
participant roles and the reference frame.
INPUT_JSON
{{INPUT_JSON}}
```

Result change: type-specific system prompt.

```
TASK: RESULT CHANGE
Privately compare result_from and result_to and the two captions. Separate the
shared initiating event from its differing endpoint, degree, continuation, or persistence.
State only the changed endpoint/continuation using generic participant-role nouns
when object_policy=unconstrained. Do not restate the shared initiating action.

Preserve which participant OR PART is affected. A part changing state is not the
entire object changing state. Preserve the supporting, contained, and receiving roles.
Preserve negation, partial versus complete extent, near versus actual occurrence,
success versus failure, and immediate versus delayed or subsequent events.
For a continuation following an action, retain the supported temporal relationship;
do not omit a specified trigger such as withdrawal of an acting participant.
Do not invent a cause, stopping point, completion, or extra action.

A state predicate essential to the changed result is allowed, but express a change
of persistence/termination by reference to the existing motion when possible instead
of repeating its subtype. Describe resulting damage/extent without restating the
initiating procedure when a state description suffices. Do not sacrifice clarity or
the target distinction merely to avoid a word. Check the whole instruction for action
disclosure and participant/timing errors before returning.

Keep the specific result state: generic 'damage' or 'change' must not replace a
distinguishing state or degree. A result-state noun or adjective is allowed even if
related to the initiating verb; do not narrate that initiating procedure. For part
versus whole changes, use a generic part reference instead of broadening to the item.
A generic acting-role noun may refer to a body part when essential to the changed
event's timing; do not replace a precise trigger with an unspecified 'afterward'.
```

Result change: user template.

```
Write only the changed result or continuation. Check participant roles, affected parts,
degree, negation, and timing. Apply object_policy.
```

```
INPUT_JSON
{{INPUT_JSON}}
```

Shared output schema.

```
{
  "type": "object",
  "additionalProperties": false,
  "properties": {
    "evidence_check": {
      "type": "object",
      "additionalProperties": false,
      "properties": {
        "object_policy": {
          "type": "string",
          "enum": [
            "replace",
            "unconstrained"
          ]
        },
        "object_mappings": {
          "type": "array",
          "items": {
            "type": "object",
            "additionalProperties": false,
            "properties": {
              "source": {
                "type": "string"
              },
              "source_role": {
                "type": "string"
              },
              "target": {
                "type": "string"
              },
              "target_role": {
                "type": "string"
              },
              "mapping_status": {
                "type": "string",
                "enum": [
                  "distinct",
                  "naming_only",
                  "role_mismatch",
                  "uncertain"
                ]
              },
              "evidence": {
                "type": "string"
              }
            },
            "required": [
              "source",
              "source_role",
              "target",
              "target_role",
              "mapping_status",
              "evidence"
            ]
          }
        },
        "action_compatibility": {
          "type": "string",
          "enum": [
            "compatible",
            "incompatible",
            "uncertain"
          ]
        },
        "essential_evidence": {
          "type": "string",
          "enum": [
            "sufficient",
            "uncertain",
            "conflicting"
          ]
        },
        "edit_summary": {
          "type": "string"
        }
```

```
      },
      "required": [
        "object_policy",
        "object_mappings",
        "action_compatibility",
        "essential_evidence",
        "edit_summary"
      ]
    },
    "valid": {
      "type": "boolean"
    },
    "modification_text": {
      "type": [
        "string",
        "null"
      ],
      "pattern": "^[^;\uFF1B]*$"
    },
    "preserved_context": {
      "type": [
        "string",
        "null"
      ]
    },
    "changed_elements": {
      "type": "array",
      "items": {
        "type": "string"
      }
    },
    "rejection_reason": {
      "type": [
        "string",
        "null"
      ]
    }
  },
  "required": [
    "evidence_check",
    "valid",
    "modification_text",
    "preserved_context",
    "changed_elements",
    "rejection_reason"
  ]
}
```