CRISP: CULTURAL REWARD MODELING FOR IMPLICIT SITUATED PROPRIETY

Anonymous authors
Paper under double-blind review

ABSTRACT

As large language models (LLMs) are increasingly deployed across countries and regions, the ability to recognize and respond appropriately to diverse cultural contexts becomes increasingly important. However, existing research has largely focused on cultural knowledge or tasks with predefined response spaces, while open-ended culturally situated behavior remains comparatively underexplored. In this work, we introduce CRISP-RM, a culturally situated reward model that assigns rewards according to cultural appropriateness in open-ended social scenarios. During policy optimization, we further introduce Norm Grounding Supervision (NGS), providing guidance that enhances the policy's sensitivity to relevant cultural norms. To construct culturally situated data, we employ a collaborative multi-agent framework that instantiates implicit cultural norms into diverse social scenarios and further curate NormCompass as a dedicated testbed. We conduct comprehensive experiments to evaluate the effectiveness of CRISP-RM in both reward modeling and policy optimization. Best-of-N experiments show that CRISP-RM consistently outperforms strong general reward models. During GRPO policy optimization, CRISP-RM generally improves culturally situated behavior, while incorporating NGS yields further gains. Further analyses demonstrate the advantages of CRISP-RM in distinguishing culturally appropriate behavior beyond superficial fluency and politeness, while NGS provides complementary gains during policy optimization by improving norm grounding.

1 INTRODUCTION

As large language models are increasingly deployed in real world settings such as conversational assistants(Miehling et al., 2024), education(Daheim et al., 2024), information synthesis (Ye et al., 2024), and personalized services (Salemi et al., 2024), their ability to understand and respect culturally specific customs, interactional norms, and behavioral boundaries has become increasingly important(Rao et al., 2025; Liu et al., 2025). Culture shapes not only patterns of interaction, but also social norms and judgments of appropriate behavior (Ramezani & Xu, 2023; Rao et al., 2025).

Prior work has largely assessed cultural capabilities through probes of cultural knowledge, commonsense, values, and norms (Ramezani & Xu, 2023; Shen et al., 2024; Chiu et al., 2025). However, cultural competence also requires models to recognize relevant cultural considerations in specific situations and respond appropriately, motivating recent efforts to evaluate culturally situated behavior (Rao et al., 2025; Wu et al., 2025; Ye et al., 2026b). While these studies extend cultural evaluation to contextualized and open-ended settings, reward modeling for culturally situated behavior remains insufficiently explored, limiting the availability of reliable rewards for cultural appropriateness.

To address this gap, we introduce CRISP-RM (**C**ultural **R**eward Modeling for **I**mplicit **S**ituated **P**ropriety) for open-ended scenarios. Additionally, we develop a collaborative multi-agent framework to construct culturally situated data and curate NormCompass, a testbed for open-ended culturally situated decision making. Furthermore, we introduce Norm Grounding Supervision (NGS), which complements the cultural reward with explicit norm supervision during policy optimization.

We first employ the collaborative multi-agent framework to construct culturally situated social scenarios. The framework instantiates cultural norms into diverse social scenarios with varying temporal, spatial, and interpersonal contexts, while keeping the target norms implicit. The resulting

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

corpus spans 19 cultures and a broad range of socially situated problems. Furthermore, we curate NormCompass, a dedicated testbed for open-ended culturally situated behavior.

Across culturally situated scenarios, we train CRISP-RM to produce scalar rewards that reflect culturally appropriate behavior and provide culturally informed supervision for policy optimization. We evaluate CRISP-RM through Best-of-N selection, comparing it against a range of general reward models. CRISP-RM achieves the strongest selection performance on both benchmarks, outperforming several substantially larger reward models.

We further use CRISP-RM to provide cultural reward signals for Group Relative Policy Optimization, examining their effectiveness in guiding policy optimization. Across multiple policy models, optimization with CRISP-RM consistently improves culturally situated behavior, demonstrating the effectiveness of the cultural reward for policy learning. Further combining CRISP-RM with Norm Grounding Supervision can yield additional gains, showing the benefit of jointly incorporating behavior level cultural rewards and explicit supervision for norm grounding during policy optimization.

Further analyses show that CRISP-RM can distinguish culturally appropriate behavior from superficially fluent and polite alternatives, indicating that it captures culturally relevant behavioral preferences beyond polite response style. Analysis of norm grounding further shows that cultural reward optimization promotes norm grounding, while NGS generally provides additional gains through explicit supervision and helps preserve culturally grounded behavior.

In summary, our contributions are as follows:

- We develop a collaborative multi-agent framework for constructing culturally situated social scenarios with implicit cultural norms. We further curate NormCompass, a dedicated testbed for evaluating culturally appropriate behavior in open-ended social scenarios.
- We introduce **CRISP-RM**, a culturally situated reward model that produces scalar rewards reflecting cultural appropriateness and provides reward signals for policy optimization.
- We apply CRISP-RM to GRPO across policy models, consistently improving culturally situated behavior. We further combine CRISP-RM with Norm Grounding Supervision, showing that joint reward and norm supervision can yield additional gains.

2 Related Work

Reward Models for LLM Alignment. Reward models are a central component of RLHF, typically learning a scalar preference function from pairwise comparisons and providing optimization signals for policy training(Stiennon et al., 2020; Ouyang et al., 2022; Bai et al., 2022). Recent work has substantially improved general reward modeling through better preference data, multi-objective modeling, and large scale data curation, leading to strong models such as ArmoRM and the Skywork Reward series(Wang et al., 2024b;a; Liu et al., 2026). However, growing evidence suggests that strong general reward model performance does not necessarily transfer across languages, domains, or culturally dependent preferences(Gureja et al., 2025; Men et al., 2025; Zhang et al., 2026; Jin et al., 2025). Gureja et al. (2025) report substantial degradation outside English, while Zhang et al. (2026) specifically reveal limitations of existing reward models in capturing culturally grounded preferences. Recent efforts have begun to address this issue, including Think-as-Locals(Zhang et al., 2026) for improving cultural judgments in generative reward models and SCPO(Oh et al., 2026) for balancing reward model preferences across cultural subcommunities. In contrast, our work focuses on developing a reward model for open-ended, culturally situated behavior, where the cultural norm is implicit in the scenario, and further uses the reward signal to optimize the policy.

Cultural Awareness in Large Language Models. Prior work has explored cultural capabilities in LLMs across cultural knowledge, cross cultural translation, values, and social norms(Ramezani & Xu, 2023; Shen et al., 2024; Chiu et al., 2025; Li et al., 2024; Ye et al., 2026a; Yuan et al., 2026). Subsequent studies have begun to situate cultural norms within concrete social scenarios, requiring models to interpret culturally relevant cues and judge whether a behavior is appropriate or select actions consistent with the corresponding cultural norms(Rao et al., 2025; Kim & Lee, 2025). More recently, research has further moved toward open-ended responses in culturally grounded scenarios(Wu et al., 2025; Ye et al., 2026b). Ye et al. (2026b) connect concrete social scenarios




Figure 1: Overview of our framework. Part I constructs culturally situated data by extracting cultural norms, instantiating them into diverse chronotopes and concrete scenarios, and refining the generated questions through iterative verification and revision. Part II trains CRISP-RM and Norm Grounding Supervisor, and combines their reward signals to optimize the policy model.

with traceable cultural norms and progressively extends the task from multiple-choice judgments to open-ended generation. Despite these advances, comparatively limited attention has been paid to improving open-ended culturally situated behavior. Accordingly, we construct a reward model to provide reliable reward signals, and further leverage these signals to optimize policy models through reinforcement learning in cultural scenarios.

3 Construction of Culturally Situated Data

3.1 Scenario and Question Generation

We collect cultural norms from existing resources, as summarized in Table 1, using DeepSeek(DeepSeek-AI, 2026) to extract and normalize cultural norms from sources (Chiu et al., 2025; Palta & Rudinger, 2023; Rao et al., 2025). To instantiate cultural norms in concrete social situations, we draw inspiration from Bakhtin's theory of the *chronotope*(Bakhtin et al., 1981). For each norm, we construct up to three distinct chronotopes that define different temporal, spatial, and social configurations to contextualize the norm, thereby increasing the contextual diversity with which the same cultural norm is instantiated. Based on each chronotope, the question generator instantiates each cultural norm into a concrete social scenario and a corresponding question, requiring the protagonist to interpret the situation carefully and make a specific and contextually appropriate choice, judgment, or action rather than merely recall or explain cultural knowledge.

Table 1: Sources and processing methods used for cultural norm collection and organization.

Source	# Norms	Processing Method
CulturalBench	734	Cultural question extraction
FORK	177	Binary-choice extraction
NormAd	725	Structured rule organization
Total	**1,636**	

3.2 Multi-Agent Refinement and Quality Control

Initially generated questions may suffer from insufficient cultural cues or inadvertently reveal the target norm, which can compromise their quality and reliability. To address these issues, we intro-

duce a multi-agent refinement loop that iteratively diagnoses, revises, verifies, and filters candidate questions. The loop consists of five specialized agents and a controller.

Situated Reasoner. The Situated Reasoner attempts to infer the relevant cultural norm from the contextual cues and formulate an appropriate action without access to the target norm. Given the scenario and question, it simulates how an evaluated model would interpret the cultural context.

Norm-Grounded Verifier. The Norm-Grounded Verifier performs a structured assessment of each question and response against the target cultural norm along five dimensions: action appropriateness (A), contextual evidence (E), norm matching (N), reasoning support (R), and norm leakage (L).

Response Advisor. The Response Advisor is activated when the verifier indicates that the current failure is more likely attributable to the response than to the scenario or question. It identifies response level deficiencies, such as insufficient use of contextual evidence and provides targeted guidance for the Situated Reasoner to generate an improved response in the subsequent attempt.

Revision Planner. The Revision Planner handles cases in which the identified problems require changes to the scenario or question rather than response regeneration alone. It analyzes the diagnostic signals and translates them into targeted revision guidance for the Question Reviser.

Question Reviser. The Question Reviser modifies the existing scenario and question according to the diagnostic guidance. It focuses on correcting question level deficiencies, such as insufficient cultural cues, inappropriate scenario, or leakage of the target norm.

Routing Controller. The Routing Controller determines the next refinement step from the structured outputs of the Norm-Grounded Verifier according to the deterministic routing rules in Table 2. Each candidate is either retained, routed to response regeneration or question revision.

For each initial candidate, the Situated Reasoner first generates a trial response, which is then assessed by the Norm-Grounded Verifier. Candidates that satisfy all verification criteria are retained. When the inferred norm and proposed action are appropriate but the supporting reasoning or contextual evidence remains insufficient, the Response Advisor provides targeted guidance for a subsequent response attempt. By contrast, cases involving norm leakage, failure to identify the relevant cultural norm, or inappropriate action selection are routed to question revision: the Revision Planner formulates targeted revision instructions, which are then carried out by the Question Reviser.

Table 2: Deterministic routing rules used by the Routing Controller to guide the refinement process.

Condition	Decision
$L = 1$	`revise question`
$A = 0$ or $N = 0$	`revise question`
$A = N = 1,\ L = 0,\ ER = 0$	`rerun answer`
$A = E = N = R = 1,\ L = 0$	`keep`

Revised questions are returned to the Situated Reasoner for a new response, while regenerated responses are re-evaluated by the Norm-Grounded Verifier. This iterative process continues until the sample satisfies all verification criteria or reaches the predefined maximum number of attempts, after which unsuccessful samples are discarded.

3.3 NORMCOMPASS

After multi-agent refinement, we obtain 4192 culturally situated questions covering 19 cultures. From the refined dataset, we construct the training and validation sets and further curate **NormCompass**, an evaluation set consisting of 222 items for culturally situated decision.

Table 3: Agreement between human annotators and GPT on culturally appropriate evaluation.

Comparison	Krippendorff's α	Spearman ρ
Human-Human	0.700	0.713
Human-GPT	0.732	0.750

We evaluate model performance on **NormCompass** using GPT-5.6 Sol(Singh et al., 2025) as the evaluator, with the corresponding cul-

tural norm provided as reference. The evaluator assigns a quality score on a 1-5 scale, where higher scores indicate more culturally appropriate behavior in the given scenario.

To assess the reliability of the automatic evaluator, we additionally conduct a human evaluation on a set of model responses. As shown in Table 3, the automatic evaluator exhibits strong consistency with human judgments, supporting its use for large scale evaluation on NormCompass.

4 CRISP REWARD MODEL

To transform the social behavioral constraints encoded in cultural norms into reward signals, we investigate reward modeling for culturally situated decision making. We construct the training data by generating candidate responses to the cultural scenarios using a set of LLMs spanning multiple model families, parameter scales, and capability levels, and scoring them with the automatic evaluator. Since these scores are ordinal, we convert them into within scenario pairwise preferences. For each scenario, responses with higher scores are preferred, while ties are excluded.

Based on the preference pairs, we train a scalar reward model to assess the cultural appropriateness of culturally situated responses. For each preference pair (y^+, y^-) associated with a scenario question x, we optimize the model using the Bradley–Terry objective(Bradley & Terry, 1952):

$$P_\theta(y^+ \succ y^- \mid x) = \sigma\left(r_\theta(x, y^+) - r_\theta(x, y^-)\right),$$

and minimize the corresponding negative log-likelihood:

$$\mathcal{L}_{\mathrm{BT}} = -\frac{1}{|\mathcal{B}|} \sum_{(x,y^+,y^-)\in\mathcal{B}} \log \sigma\left(r_\theta(x, y^+) - r_\theta(x, y^-)\right).$$

We instantiate two reward models based on Qwen3-0.6B and Qwen3-4B (Yang et al., 2025). For each model, a linear reward head is applied to the representation of the last non-padding token to produce a scalar reward. Both models are trained with full-parameter fine-tuning to adapt them to culturally situated preference signals. Further training details are provided in Appendix B.

Best-of-N Evaluation Setup. We evaluate the effectiveness of the reward models through Best-of-N (BoN) selection, where multiple candidate responses to the same cultural scenario question are scored by the reward model, and the top-ranked response is retained for evaluation. The evaluation is conducted on both NormCompass and CultureForest. For CultureForest, we use the Hard open-ended generation setting and restrict evaluation to items whose cultural groups are represented in our training data. Each benchmark is evaluated using its corresponding evaluation protocol. For each cultural scenario question, we sample N candidate responses from each language model and perform BoN selection among responses generated by the same model. Under this setting, we compare CRISP reward models against several publicly available general reward models.

Best-of-N Evaluation Results. As shown in Table 4, our CRISP reward models consistently outperform random selection and all general reward model baselines on both benchmarks. On NormCompass, the CRISP-RM-4B achieves 3.89 and 3.92 at $N = 8$ and $N = 16$, while the 0.6B model also surpasses all publicly available baselines under both settings. This advantage extends to CultureForest, where both models retain their lead over substantially larger general reward models, demonstrating that the learned reward signal transfers beyond our constructed testbed. Notably, increasing the candidate pool from $N = 8$ to $N = 16$ yields further performance gains for both of our reward models on NormCompass and CultureForest, suggesting that they can effectively leverage a larger set of candidates during BoN selection.

Overall, these results indicate that strong general reward modeling capability does not necessarily translate into reliable evaluation of culturally situated behavior. In contrast, reward models trained with culture specific preference supervision provide more consistent reward signals, despite being substantially smaller than the strongest general models.

5 REINFORCEMENT LEARNING WITH CULTURAL REWARDS

Table 4: Best-of-N selection results on NormCompass and CultureForest.

Reward Model	Params.	NormCompass $N=8$	NormCompass $N=16$	CultureForest $N=8$	CultureForest $N=16$
Random Selection	–	3.60	3.60	56.93	56.93
CRISP-RM-0.6B (Ours)	0.6B	3.84	3.87	58.66	58.89
CRISP-RM-4B (Ours)	4B	**3.89**	**3.92**	**59.54**	**60.23**
Skywork Reward V2 Qwen3(Liu et al., 2026)	0.6B	3.61	3.60	55.29	54.49
Skywork Reward V2 Qwen3(Liu et al., 2026)	4B	3.70	3.71	56.01	55.37
Skywork Reward V2 Llama-3.1(Liu et al., 2026)	8B	3.69	3.69	56.19	55.63
ArmoRM Llama-3(Wang et al., 2024a)	8B	3.71	3.75	55.42	54.45
QRM Gemma-2(Dorka, 2024)	27B	3.79	3.80	56.68	56.23
Skywork Reward Gemma-2(Liu et al., 2024)	27B	3.76	3.79	56.50	56.01
INF-ORM Llama-3.1(Minghao Yang, 2024)	70B	3.82	3.83	55.95	55.44

We further investigate whether CRISP-RM can effectively guide policy optimization. To this end, we adopt Group Relative Policy Optimization (GRPO) to optimize multiple policy models using CRISP-RM-4B as the reward model, aiming to improve their behavioral appropriateness in diverse cultural scenarios. CRISP-RM-4B considers only the generated answer, conditioned on the culture, scenario, and question, and produces a scalar reward.

Table 5: GRPO policy optimization results on NormCompass, CultureForest, and CulShield Knowledge Coverage. Δ denotes the change relative to the corresponding base policy.

Policy	NormCompass Score	NormCompass Δ	CultureForest Score	CultureForest Δ	CulShield Score	CulShield Δ
Qwen3-4B	3.27	–	56.18	–	73.07	–
+CuSiR	3.08	-0.20	24.52	-31.66	69.53	-3.54
+Skywork-Reward-V2-Qwen3-4B	3.52	+0.24	23.96	-32.22	76.66	+3.59
+CRISP	3.69	+0.42	57.60	+1.42	**80.19**	**+7.11**
+CRISP + NGS	**3.86**	**+0.58**	**60.28**	**+4.10**	77.91	+4.83
Qwen3-8B	3.71	–	60.07	–	69.59	–
+CuSiR	3.59	-0.12	26.13	-33.94	67.86	-1.73
+Skywork-Reward-V2-Qwen3-4B	3.60	-0.11	29.39	-30.68	72.42	+2.83
+CRISP	3.95	+0.24	**60.08**	**+0.01**	74.09	+4.50
+CRISP + NGS	**4.01**	**+0.30**	58.75	-1.32	**74.41**	**+4.82**
DeepSeek-R1-Distill-Qwen-7B	2.29	–	39.93	–	55.83	–
+CuSiR	2.16	-0.13	20.99	-18.94	53.43	-2.40
+Skywork-Reward-V2-Qwen3-4B	2.77	+0.48	31.92	-8.01	**61.77**	**+5.94**
+CRISP	3.02	+0.73	51.79	+11.86	60.47	+4.65
+CRISP + NGS	**3.09**	**+0.80**	**53.72**	**+13.79**	57.24	+1.41

To obtain a bounded and stable reward signal for optimization, we normalize the reward scores using robust statistics estimated from a validation set and further map them to $[0, 1]$ with a sigmoid function, thereby reducing sensitivity to extreme scores during subsequent policy optimization. Specifically, letting r_{origin} denote the original reward score, we define the location and scale parameters as:

$$\mu = \text{Median}(r_{\text{origin}}), \qquad s = \text{RobustScale}(r_{\text{origin}}),$$

and transform the raw reward as

$$\tilde{r}_{\text{RM}} = \sigma\left(\frac{r_{\text{origin}} - \mu}{s}\right).$$

We then optimize the policy with the standard GRPO objective, where the normalized CRISP-RM scores are used to compute group relative advantages over responses sampled for the same scenario. Detailed GRPO implementation and optimization hyperparameters are provided in Appendix C.

Beyond optimizing behavioral appropriateness with the cultural reward, we introduce a Qwen3-8B-based Norm Grounding Supervisor to provide an auxiliary supervision signal that encourages the policy to ground its responses in the cultural norm relevant to each scenario. Given the culture, scenario, question, target cultural norm, answer, and rationale, the supervisor formulates norm grounding as a binary classification problem with two states, *Grounded* and *Ungrounded*.

We use the probability assigned to the *Grounded* class as the norm grounding reward:




Figure 2: Training dynamics of Qwen3-4B under different reward signals during GRPO optimization on NormCompass and CultureForest, with performance tracked across training checkpoints.

$$r_{\text{NGS}} = p(\text{Grounded}).$$

And we then combine it with the normalized cultural reward:

$$r_{\text{total}} = \tilde{r}_{\text{RM}} + \lambda r_{\text{NGS}},$$

where λ controls the contribution of norm grounding supervision.

We assess the effectiveness of CRISP-RM for policy optimization on NormCompass and CultureForest. For CultureForest, we use the Hard open-ended generation setting and restrict evaluation to cultural groups represented in our training data. We further include CulShield Knowledge Coverage as a complementary multiple-choice evaluation of cultural knowledge. We compare against the general Skywork reward model and CuSiR, while further examining the effect of NGS.

As shown in Table 5, CRISP-RM yields consistent gains on NormCompass and transfers to CultureForest, where optimization with Skywork and CuSiR often results in substantial degradation. Notably, the gains also extend to CulShield, despite its multiple-choice evaluation format, suggesting that the benefits of CRISP-RM optimization are not confined to open-ended cultural responses. Further incorporating NGS brings additional gains, indicating that explicit norm grounding provides complementary supervision beyond behavioral reward optimization. The slight performance drop of Qwen3-8B with NGS on CultureForest is mainly attributable to invalid output formatting rather than the optimization signal itself; results restricted to valid outputs are provided in Appendix C.

To further analyze the optimization dynamics, we track the training trajectory of Qwen3-4B across optimization signals. As shown in Figure 2, CRISP maintains stronger performance throughout optimization. This advantage is particularly evident on CultureForest, where CuSiR and Skywork progressively degrade as training proceeds, while the CRISP-training remains stable or continue to improve. These trajectories suggest that CRISP provides a more reliable signal throughout training.

6 Reward Model Discrimination Analysis

We further examine whether CRISP-RM can distinguish culturally appropriate behavior beyond superficial fluency and politeness through a controlled triplet analysis. We select a set of scenarios from NormCompass and construct three contrasting responses for each scenario: an *Appropriate* response that reflects the relevant cultural norm, a *Generic* response that remains plausible but omits the culturally decisive action, and an *Opposite* response whose core action conflicts with the norm. The responses are designed to remain comparable in fluency, style, and length, allowing the comparison to focus on the cultural appropriateness of the behavior.

As shown in Figure 3, CRISP-RM recovers the intended preference structure more consistently than general reward models. General reward models can perform well in distinguishing Appropriate




Figure 3: Controlled cultural preference analysis on the triplets. We report ranking accuracy for Appropriate versus Generic, Appropriate versus Opposite responses and Generic versus Opposite, together with top-1 selection accuracy and complete ordering accuracy.

responses from Generic ones, but are considerably less reliable in separating Appropriate responses from Opposite ones. CRISP-RM maintains this finer distinction more consistently, suggesting that it captures culturally relevant behavioral preferences beyond polite response style.

Case Study: Figure 4 illustrates this distinction with a representative case from a German workplace farewell. In this setting, opening a gift upon receiving it is culturally appropriate. The Appropriate response therefore recommends opening the gift in front of the group, whereas the Opposite response suggests thanking everyone warmly and postponing the opening until later in private. Although the latter remains polite and socially plausible, its core action conflicts with the relevant cultural norm. CRISP-RM favors the Appropriate response, while general reward models instead favor the polite Opposite response, illustrating how surface social cues can sometimes obscure the cultural appropriateness of the underlying behavior.




Figure 4: A case study illustrating how CRISP-RM distinguishes culturally appropriate behavior.

7 Effectiveness of the Norm Grounding

To explore the role of Norm Grounding Supervision, we conduct an analysis on NormCompass across a range of policy models. For each scenario, we use GPT-5.6 Sol to evaluate the rationales generated by a range of policy variants and assign a Norm Match score N in$\{0, 1, 2\}$. A score of 0 indicates that the relevant cultural norm is not identified, 1 indicates partial or implicit grounding, and 2 indicates clear and accurate grounding. We first compare Norm Match scores across policy variants to examine how optimization affects norm grounding. We




Figure 5: Effect of Norm Grounding Supervision. a): Norm Match scores across policy models before and after optimization. b): Answer quality stratified by the Norm Match score of the original policy before optimization, where N denotes the initial level of norm grounding.




Figure 6: Sensitivity analysis of λ across different policy models. λ controls the contribution of norm supervision, with $\lambda = 0$ corresponding to optimization using CRISP-RM alone.

then stratify scenarios according to the Norm Match score of the original policy and analyze how response quality changes after optimization with CRISP-RM alone or together with NGS.

As shown in Figure 5, CRISP-RM improves Norm Match across policy models, indicating that cultural reward optimization itself promotes better norm grounding. Adding NGS further increases Norm Match across all policy models, indicating that explicit norm grounding supervision provides complementary guidance beyond cultural reward optimization. When grouping scenarios by the original policy's Norm Match score, CRISP-RM substantially improves answer quality for initially ungrounded cases, while performance decreases for $N = 2$. NGS generally improves upon CRISP-RM and helps mitigate the degradation at $N = 2$, suggesting a complementary role in strengthening and preserving behavior grounded in cultural norms.

8 Robustness Analysis of Norm Grounding Supervision

We further examine the sensitivity of policy optimization to the Norm Grounding Supervision. We vary λ while keeping the remaining training configuration unchanged.

Figure 6 shows the effect of different λ values on training performance. Overall, the policy models exhibit stable performance across benchmarks as λ varies, model performance shows only limited fluctuations, and $\lambda = 0.1$ and $\lambda = 0.2$ achieve results close to the best performance in most settings. This indicates that the method is reasonably robust to the λ.

9 Conclusion

We study culturally appropriate decision making in open-ended social scenarios. To this end, we develop a collaborative multi-agent framework for data construction and release NormCompass, a dedicated testbed for evaluating culturally appropriate behavior in open-ended cultural scenarios. Building on this, we introduce CRISP-RM, a specialized reward model for culturally situated behavior, and further incorporate Norm Grounding Supervision. Our experimental results demonstrate that CRISP-RM effectively improves culturally appropriate behavior and exhibits transfer across task formats. Further analyses demonstrate that CRISP-RM can distinguish responses that are similarly fluent and polite yet differ in cultural appropriateness, while providing a more stable reward signal during policy optimization. And Norm Grounding Supervision further strengthens norm grounding and brings additional gains. Overall, our results show that culturally specialized reward modeling, together with explicit norm supervision, can jointly improve the behavioral appropriateness of language models in diverse open-ended cultural interactions.

10 Ethics Statement

This work studies culturally situated behavior, where cultural norms may vary across communities, contexts, and individuals. The norms and scenarios in NormCompass should therefore be understood as contextual references rather than universal prescriptions for members of a cultural group. Although our construction and refinement procedures aim to preserve contextual specificity, the resulting data may still simplify heterogeneous cultural practices or reflect biases present in the un-

derlying sources and language models. We caution against using the dataset or reward models to stereotype individuals or to make assumptions about behavior solely based on cultural identity.

11 AI USE STATEMENT

In this work, we use AI tools to assist with several parts of the research workflow throughout the study. Specifically, models from the DeepSeek and GPT families are used for the construction and iterative refinement of culturally situated data, the generation and filtering of selected analysis data, and the automated evaluation of model responses. We also use AI tools to assist with language polishing and to improve the readability of the manuscript.

All AI-assisted research content is reviewed and checked by the authors. The experimental design, methodological choices, result analysis, and research conclusions are ultimately determined by the authors, who take full responsibility for the final content of the paper.

12 REPRODUCIBILITY STATEMENT

For reproducibility, we provide additional details following the progression of our framework. Appendix A expands on the culturally situated data construction introduced in Section 3, including norm sources, scenario construction, multi-agent refinement, and other implementation details. Building on this data, Appendix B details the preference construction, reward model training, and Best-of-N evaluation underlying Section 4. Appendix C then describes the optimization pipeline in Section 5, covering the Norm Grounding Supervisor, reward calibration, GRPO configuration and evaluation protocols. Finally, Appendices D and E provide the supporting details for the controlled preference and norm grounding analyses in Sections 6 and 7, respectively.

REFERENCES

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022.

Mikhail Bakhtin et al. Forms of time and of the chronotope in the novel. *The dialogic imagination: Four essays*, 1:84–259, 1981.

Ralph Allan Bradley and Milton E Terry. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345, 1952.

Yu Ying Chiu, Liwei Jiang, Bill Yuchen Lin, Chan Young Park, Shuyue Stella Li, Sahithya Ravi, Mehar Bhatia, Maria Antoniak, Yulia Tsvetkov, Vered Shwartz, et al. Culturalbench: A robust, diverse and challenging benchmark for measuring lms' cultural knowledge through human-ai red-teaming. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 25663–25701, 2025.

Nico Daheim, Jakub Macina, Manu Kapur, Iryna Gurevych, and Mrinmaya Sachan. Stepwise verification and remediation of student reasoning errors with large language model tutors. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 8386–8411, 2024.

DeepSeek-AI. Deepseek-v4: Towards highly efficient million-token context intelligence, 2026.

Nicolai Dorka. Quantile regression for distributional reward models in rlhf. *arXiv preprint arXiv:2409.10164*, 2024.

Srishti Gureja, Lester James Validad Miranda, Shayekh Bin Islam, Rishabh Maheshwary, Drishti Sharma, Gusti Winata, Nathan Lambert, Sebastian Ruder, Sara Hooker, and Marzieh Fadaee. M-rewardbench: Evaluating reward models in multilingual settings. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 43–58, 2025.

Zhuoran Jin, Hongbang Yuan, Tianyi Men, Pengfei Cao, Yubo Chen, Jiexin Xu, Huaijun Li, Xiaojian Jiang, Kang Liu, and Jun Zhao. Rag-rewardbench: Benchmarking reward models in retrieval augmented generation for preference alignment. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 17061–17090, 2025.

Kyuhee Kim and Sangah Lee. Nunchi-bench: Benchmarking language models on cultural reasoning with a focus on korean superstition. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 15328–15342, 2025.

Cheng Li, Mengzhuo Chen, Jindong Wang, Sunayana Sitaram, and Xing Xie. Culturellm: Incorporating cultural differences into large language models. *Advances in Neural Information Processing Systems*, 37:84799–84838, 2024.

Chen Cecilia Liu, Anna Korhonen, and Iryna Gurevych. Cultural learning-based culture adaptation of language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 3114–3134, 2025.

Chris Yuhao Liu, Liang Zeng, Jiacai Liu, Rui Yan, Jujie He, Chaojie Wang, Shuicheng Yan, Yang Liu, and Yahui Zhou. Skywork-reward: Bag of tricks for reward modeling in llms. *arXiv preprint arXiv:2410.18451*, 2024.

Yuhao Liu, Liang Zeng, Yuzhen Xiao, Jujie He, Jiacai Liu, Chaojie Wang, Rui Yan, Wei Shen, Fuxiang Zhang, Jiacheng Xu, et al. Skywork-reward-v2: Scaling preference data curation via human-ai synergy. In *International Conference on Learning Representations*, volume 2026, pp. 133805–133838, 2026.

Tianyi Men, Zhuoran Jin, Pengfei Cao, Yubo Chen, Kang Liu, and Jun Zhao. Agent-rewardbench: Towards a unified benchmark for reward modeling across perception, planning, and safety in real-world multimodal agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 17521–17541, 2025.

Erik Miehling, Manish Nagireddy, Prasanna Sattigeri, Elizabeth M Daly, David Piorkowski, and John T Richards. Language models in dialogue: Conversational maxims for human-ai interactions. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 14420–14437, 2024.

Xiaoyu Tan Minghao Yang, Chao Qu. Inf-orm-llama3.1-70b, 2024. URL https://huggingface.co/infly/INF-ORM-Llama3.1-70B.

Minsik Oh, Advit Deepak, Sophie Wu, Douwe Kiela, and Ekaterina Shutova. Steerable cultural preference optimization of reward models. *arXiv preprint arXiv:2606.18606*, 2026.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35: 27730–27744, 2022.

Shramay Palta and Rachel Rudinger. Fork: A bite-sized test set for probing culinary cultural biases in commonsense reasoning models. In *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 9952–9962, 2023.

Aida Ramezani and Yang Xu. Knowledge of cultural moral norms in large language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 428–446, 2023.

Abhinav Sukumar Rao, Akhila Yerukola, Vishwa Shah, Katharina Reinecke, and Maarten Sap. Normad: A framework for measuring the cultural adaptability of large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 2373–2403, 2025.

Alireza Salemi, Sheshera Mysore, Michael Bendersky, and Hamed Zamani. Lamp: When large language models meet personalization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7370–7392, 2024.

Siqi Shen, Lajanugen Logeswaran, Moontae Lee, Honglak Lee, Soujanya Poria, and Rada Mihalcea. Understanding the capabilities and limitations of large language models for cultural commonsense. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 5668–5680, 2024.

Aaditya Singh, Adam Fry, Adam Perelman, Adam Tart, Adi Ganesh, Ahmed El-Kishky, Aidan McLaughlin, Aiden Low, AJ Ostrow, Akhila Ananthram, et al. Openai gpt-5 system card. *arXiv preprint arXiv:2601.03267*, 2025.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. *Advances in neural information processing systems*, 33:3008–3021, 2020.

Haoxiang Wang, Wei Xiong, Tengyang Xie, Han Zhao, and Tong Zhang. Interpretable preferences via multi-objective reward modeling and mixture-of-experts. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 10582–10592, 2024a.

Zhilin Wang, Alexander Bukharin, Olivier Delalleau, Daniel Egert, Gerald Shen, Jiaqi Zeng, Oleksii Kuchaiev, and Yi Dong. Helpsteer2-preference: Complementing ratings with preferences. *arXiv preprint arXiv:2410.01257*, 2024b.

Jincenzi Wu, Jianxun Lian, Dingdong Wang, and Helen Meng. Socialcc: Interactive evaluation for cultural competence in language agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 33242–33271, 2025.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Yangfan Ye, Xiachong Feng, Xiaocheng Feng, Weitao Ma, Libo Qin, Dongliang Xu, Qing Yang, Hongtao Liu, and Bing Qin. GlobeSumm: A challenging benchmark towards unifying multi-lingual, cross-lingual and multi-document news summarization. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 10803–10821, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.603. URL https://aclanthology.org/2024.emnlp-main.603/.

Yangfan Ye, Xiaocheng Feng, Xiachong Feng, Yichong Huang, Zekun Yuan, Lei Huang, Weitao Ma, Qichen Hong, Yunfei Lu, Dandan Tu, et al. x1: Learning to think adaptively across languages and cultures. In *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 14516–14533, 2026a.

Yangfan Ye, Xiaocheng Feng, Jialong Tang, Xiayu Cao, Zihan Zhang, Xiachong Feng, Baosong Yang, and Bing Qin. Cultureforest: Understanding and evaluating cultural norm grounded reasoning in llms, 2026b. URL https://arxiv.org/abs/2606.01879.

Zekun Yuan, Yangfan Ye, Xiaocheng Feng, Baohang Li, Qichen Hong, Yunfei Lu, Dandan Tu, and Bing Qin. Culture-aware machine translation in large language models: Benchmarking and investigation. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 29636–29661, 2026.

Hongbin Zhang, Kehai Chen, Xuefeng Bai, Yang Xiang, and Min Zhang. Evaluating and improving cultural awareness of reward models for llm alignment. In *International Conference on Learning Representations*, volume 2026, pp. 116333–116403, 2026.

A Details of Culturally Situated Data Construction

A.1 Cultural Norm Collection and Processing

We collect cultural norms from three existing resources: CulturalBench, FORK, and NormAd. Since these resources represent cultural information in different formats, we apply source-specific processing to convert them into a unified norm representation. Specifically, for the easy-level multiple-choice questions in CulturalBench and the binary-choice questions in FORK, we use DeepSeek-V4-Flash to extract the implicit cultural norm based on the question and its correct answer. For NormAd, which already provides explicit cultural norms, we directly adopt the provided norms without additional model-based extraction. The extraction prompts for CulturalBench and FORK are presented separately in Tables 6 and 7.

Through this process, we obtain a total of 1,636 raw norms from CulturalBench, FORK, and NormAd. Since different sources may contain duplicate cultural norms, we further deduplicate the aggregated norm pool, resulting in 1,629 cultural norms for subsequent chronotope construction and situated question generation.

A.2 Chronotope Construction

To situate abstract cultural norms in concrete and diverse social contexts, we draw on Bakhtin's concept of the *chronotope* and operationalize it as a time–space–social configuration in which a cultural norm may become relevant. Rather than representing a complete story, a chronotope specifies the contextual structure for subsequent scenario generation, including the temporal and spatial setting, social environment, participant relationships, and activity context.

Specifically, we use GPT-5.5 to construct up to three chronotopes for each cultural norm. The model is provided with the target culture, the cultural norm, and previously accepted chronotopes, and is instructed to generate a new configuration that activates the same norm while remaining structurally distinct from previous ones. The resulting chronotopes are subsequently provided to the Question Generator to construct concrete social scenarios and action-oriented questions. The prompt used for chronotope construction is shown in Table 8.

A.3 Scenario and Question Generation

For each cultural norm and its corresponding chronotope, we further instantiate the structured contextual configuration into a concrete social scenario and an action-oriented question. The Question Generator receives the target culture, cultural norm, and the main contextual information specified by the chronotope, including the temporal and spatial setting, social environment, and occasion.

The generated scenario makes the target cultural norm relevant through contextual cues without explicitly stating or explaining the norm. Rather than requiring models to directly recall cultural knowledge, the generated question places the protagonist in a practical situation that requires a context-dependent judgment, choice, or action, thereby testing whether the model can identify culturally relevant considerations from the scenario and generate an appropriate open-ended response.

For each chronotope, the generator produces a scenario and its corresponding question, together with auxiliary information used only for subsequent quality control. The complete prompt used for scenario and question generation is provided in Table 9.

A.4 Multi-Agent Refinement

To further improve the quality of the generated scenarios and questions, we employ an iterative multi-agent refinement process consisting of five model-based agents and a rule-based controller. For each candidate, the Situated Reasoner first generates a trial response and infers the potentially relevant cultural norm based only on the target culture, scenario, and question, without access to the hidden target norm. The Norm-Grounded Verifier then evaluates the candidate with access to the target norm and auxiliary information from the construction process along five dimensions: action appropriateness (A), contextual evidence (E), norm matching (N), reasoning support (R), and norm leakage (L). Detailed definitions of these dimensions are provided in Table 10.

Table 6: Prompt used to extract cultural norms from the multiple-choice questions in CulturalBench.

Component	Content
Input	Culture, question, candidate options, and the correct answer.

Prompt	`Extract one culture norm from the given CulturalBench-Easy item.`
	`Return JSON only, exactly with these fields:`
	`{ ''norm'': ''one concise culture norm sentence'', ''culture'': ''culture/country name'', ''norm_type'': ''short category such as dining_etiquette, tipping, communication, public_behavior, family, religion, workplace, other'' }`
	`Rules:`
	`- Use only the provided item.`
	`- Get the norm from the correct answer.`
	`- If the question asks what is unusual, uncommon, inappropriate, or not expected, write the norm as a negative or avoidance norm.`
	`- Do not add explanations or extra fields.`

Table 7: Prompt used to extract cultural norms from binary-choice questions in FORK.

Component	Content
Input	Culture, question, two candidate options, and the correct answer.

Prompt	`Extract one culture norm from the given item.`
	`Return JSON only, exactly with these fields:`
	`{ ''norm'': ''one concise culture norm sentence'', ''culture'': ''culture/country name'', ''norm_type'': ''short category such as dining_etiquette, tipping, eating_utensils, social_hierarchy, hospitality, other'' }`
	`Rules:`
	`- Use only the provided item.`
	`- Get the norm from the correct answer.`
	`- Do not add explanations or extra fields.`

Based on the verification results, the Routing Controller determines whether to retain the current candidate, regenerate the response, or revise the question, following the rules in Table 2. When the model proposes an appropriate action and correctly identifies the target cultural norm but does not sufficiently use the contextual evidence or provide adequate reasoning, the Response Advisor provides targeted feedback to guide the Situated Reasoner in generating a new response. For candidates involving norm leakage, incorrect norm identification, or inappropriate actions, the Revision Planner generates guidance, which is used by Question Reviser to modify the scenario and question.

The revised candidate is subsequently returned to the Situated Reasoner–Verifier loop. A candidate is retained only when its action and norm judgment are both correct, its contextual evidence and reasoning are sufficient, and no norm leakage is detected. The process allows up to five verification rounds, after which candidates that still fail to satisfy the quality criteria are discarded. All five model-based agents are instantiated from GPT-5.5 using role-specific prompts, as shown in Tables 11–15., while the Routing Controller makes deterministic routing decisions based on the structured outputs of the Verifier.

A.5 Dataset Statistics and Splitting

Final Dataset Statistics. After chronotope construction, scenario and question generation, and multi-agent quality control, we obtain a total of 4,430 culturally situated questions, covering 1,619 cultural norms with at least one valid scenario.

Table 8: Prompt used for chronotope construction.

Chronotope Generation Prompt

```
Given the following cultural norm and the already accepted
chronotopes, generate a new chronotope for constructing a culturally
grounded decision-making scenario.
A chronotope is a time-space-social configuration.  It should specify
not only when and where the event happens, but also the social meaning
of the setting:  the relationship between participants, the degree
of privacy or formality, the behavioral expectations implied by the
setting, and how an action may be interpreted within that situation.
Your goal is to generate a new chronotope that activates the same
cultural norm but is structurally different from all accepted
chronotopes.
Structural diversity means that the new chronotope should differ
in the core configuration of the scenario, not merely in surface
details.  Do not only change names, cities, weather, objects, or minor
background details.
The new chronotope should differ from previous ones in at least two of
the following core dimensions:
temporal regime:  work time, private time, holiday time, mealtime,
urgent moment, scheduled/unscheduled time, etc.
spatial-social setting:  private home, workplace, restaurant, school,
public transport, government office, religious space, street, etc.
relationship configuration:  friends, classmates, colleagues,
supervisor/subordinate, host/guest, elder/younger, strangers, service
worker/customer, etc.
occasion or activity frame:  visiting, meeting, dining, gift-giving,
asking for help, apologizing, negotiating, celebrating, requesting a
favor, etc.
potential tension:  the superficially reasonable action that could
lead to a culturally inappropriate choice.
Requirements:
- The cultural norm must become relevant, but do not directly restate
or explain the norm.
- Do not reveal the culturally preferred behavior.
- Do not use explicit cultural explanations such as ''In this culture,
people usually...''
- Make the chronotope concrete, natural, and suitable for later
Labov-style narrative construction.
- Avoid duplicating the accepted chronotopes at the structural level.
- Return valid JSON only, with no additional explanation.
Cultural norm:
{norm}
Culture:
{culture}
Accepted chronotopes:
{accepted_chronotopes}
Output schema:
{ ''time'':  '''',
''place'':  '''',
''social_space'':  '''',
''occasion'':  '''',
''relationship_context'':  '''',
''privacy_or_formality_level'':  '''',
''norm_activation_condition'':  '''',
''potential_tension'':  '''',
''difference_from_previous'':  '''' }
```

The original data contain several labels referring to the same cultural group. For consistent statistical reporting, we normalize these labels. Specifically, Hong Kong is grouped under China; labels containing South Africa or beginning with Zulu or Batswana are grouped under South Africa; and

Table 9: Prompt used for scenario generation. The full prompt will be released with our code.

Scenario and Question Generation Prompt

```
You will be given a cultural norm and a chronotope. Generate a
contextualized cultural understanding question based on them.
The goal is not to ask the evaluated model to classify, restate, or
explain cultural knowledge. Instead, construct a natural social
scenario in which the protagonist must infer culturally relevant
considerations and decide what action, choice, or interpretation is
appropriate.
Input:
- norm: {norm}
- culture: {culture}
- norm_type: {norm_type}
- chronotope: {chronotope}
Requirements:
- Construct a specific and natural scenario with a clear protagonist
and practical decision.
- Make the cultural norm relevant through contextual cues without
directly revealing the norm or preferred behavior.
- The question should require an open-ended, context-sensitive action,
judgment, or interpretation rather than cultural knowledge recall.
- Avoid stereotypes, overly strong normative claims, and artificially
exaggerated conflicts.
- [Additional scenario-construction and weak-norm handling constraints
omitted for brevity.]
Return valid JSON only:
{ ``scenario'': ``...'', ``question'': ``...'', ``hidden_expected_answer'':
``...'', ``generation_notes'': ``...'' }
Input JSON: {generation_input}
```

Table 10: Verification dimensions used by the Norm-Grounded Verifier.

Symbol	Dimension	Description
A	Action Appropriateness	Whether the proposed action is appropriate in the given situation.
E	Contextual Evidence	Whether concrete cues in the scenario sufficiently support the relevant cultural judgment.
N	Norm Matching	Whether the inferred cultural norm matches the core meaning of the target norm.
R	Reasoning Support	Whether the provided reasoning sufficiently supports the proposed action and cultural judgment.
L	Norm Leakage	Whether the scenario or question directly or near-explicitly reveals the target cultural norm.

labels such as African-American, African American, and Black American are grouped under the United States. This normalization is used only for statistical reporting and does not modify the original culture labels stored in the data. After normalization, the final dataset covers 19 cultural groups, with the detailed distribution shown in Table 16.

Data Splitting. We first construct training, validation, and test splits using a fixed random seed of 42, resulting in 1,289/161/169 norms and 3,521/449/459 scenarios, respectively. To obtain a more reliable held-out test set, we further restrict the test data to cultural norms originating from NormAd. Unlike CulturalBench and FORK, whose norms are extracted from benchmark questions using an LLM, NormAd directly provides the cultural norms used in its original benchmark.

Building on this, we further organize the test data and obtain 222 culturally situated questions for evaluation. Together with the unchanged training and validation sets, the final experimental splits contain 1,528 cultural norms and 4,192 scenarios, as summarized in Table 17.

Table 11: Prompt used by the **Situated Reasoner**.

Situated Reasoner Prompt

```
You will be given a cultural background, a scenario story, and a question.
Your task is to answer the question based on the given scenario and explain the cultural
norms, relational meanings, or situational meanings that need to be considered.
You may only answer based on the given culture, scenario, and question. Culture is
background information only; norms must not be inferred solely from the culture or
identity of the characters. Every inferred norm must be supported by specific contextual
clues in the scenario.
Your response should contain:
1. action: the action, expression, interpretation, or judgment the protagonist should
make next;
2. reason: why this action is appropriate in the current situation;
3. inferred_norms: cultural norms, relational meanings, or situational meanings inferred
from the scenario, together with the specific contextual evidence supporting each
inference.
The action should directly address the question rather than provide generic advice. Do
not invent information that does not appear in the scenario.
Return valid JSON only.
Input:
culture: {culture}
scenario: {scenario}
question: {question}
```

Table 12: Prompt used by the **Norm-Grounded Verifier**.

Norm-Grounded Verifier Prompt

```
You will be given a cultural norm, a scenario question, and an answer to that question.
Evaluate the candidate along five dimensions and assign a binary score (0 or 1) with brief
reasoning for each dimension:
1. action_correctness (A): whether the proposed action is appropriate under the current
scenario and question;
2. norm_evidence_support (E): whether concrete evidence from the scenario sufficiently
supports the inferred norm;
3. inferred_norm_match (N): whether the inferred norms contain content whose core
meaning is consistent with the target norm;
4. reason_supports_action (R): whether the reasoning adequately supports the proposed
action;
5. norm_leakage (L): whether the scenario or question directly or near-directly reveals
the target norm.
Exact wording of the target norm is not required for norm matching. Evidence consisting
only of the culture, country or region name, character identity, or generic common sense
should not be considered sufficient contextual support.
When evaluating action correctness, hidden_expected_answer may be used as reference, but an
answer need not match it exactly.
Return valid JSON containing the score and brief reasoning for each dimension.
Input:
norm: {norm}
culture: {culture}
norm_type: {norm_type}
chronotope: {chronotope}
scenario: {scenario}
question: {question}
hidden_expected_answer: {hidden_expected_answer}
answer: {answer_model_output}
```

A.6 Automatic Evaluation Protocol

We use GPT-5.6 Sol as the automatic evaluator for open-ended culturally situated responses. For each response, the evaluator is provided with the target cultural norm together with the culture, scenario, question, and the model's final response.

The evaluator assigns an action-quality score from 1 to 5 according to the cultural appropriateness of the response in the given scenario. A score of 1 indicates a clearly inappropriate action or one that conflicts with the relevant cultural norm, whereas a score of 5 indicates a fully appropriate response that accounts for the relevant cultural considerations. Intermediate scores reflect different degrees of appropriateness, as detailed in Table 18. Table 19 presents a condensed version of the evaluation prompt. The complete prompt, together with the evaluation code, will be released upon publication.

Table 13: Prompt used by the **Response Advisor.**

Response Advisor Prompt

```
You will be given a scenario question, the previous answer, the verification results, and
a diagnosis produced by the rule-based controller.
Your task is to generate concise and specific guidance for the next response attempt.
Identify the main deficiency in the previous answer and indicate what the Situated
Reasoner should improve.
Do not revise the scenario or question and do not directly generate a new answer. You
may use the target norm and hidden expected answer to diagnose the problem, but do not
directly reveal them in the guidance.
Return valid JSON only with:
diagnosis: the main problem with the previous response;
answer_guidance: how the next response should improve.
Input:
controller_diagnosis: {controller_diagnosis}
norm: {norm}
culture: {culture}
scenario: {scenario}
question: {question}
hidden_expected_answer: {hidden_expected_answer}
answer: {answer_model_output}
judge_output: {judge_output}
```

Table 14: Prompt used by the **Revision Planner.**

Revision Planner Prompt

```
You will be given a cultural norm, a scenario question, the corresponding response, the
verification results, and a diagnosis produced by the rule-based controller.
Your task is to provide concise, specific, and actionable guidance for revising the
scenario and question.
Do not rewrite the full scenario or question. Instead, identify the main problem, specify
what the revised candidate should achieve, and provide targeted revision guidance. Focus
on whether the scenario, question, and hidden expected answer effectively instantiate the
target norm rather than evaluating the quality of the norm itself.
Return valid JSON only with:
diagnosis: the main problem with the current candidate;
revision_goal: what the revised candidate should achieve;
revision_guidance: targeted guidance for the Question Reviser.
Input:
controller_diagnosis: {controller_diagnosis}
norm: {norm}
culture: {culture}
norm_type: {norm_type}
chronotope: {chronotope}
scenario: {scenario}
question: {question}
hidden_expected_answer: {hidden_expected_answer}
answer: {answer_model_output}
judge_output: {judge_output}
```

A.7 Human Evaluation

We select 100 responses for human evaluation. Two annotators independently evaluate every response. For each instance, annotators are provided with the target culture, cultural norm, scenario, question, and candidate answer. They assign an integer outcome-quality score from 1 to 5 following the same criteria used in our automatic evaluation.

B Reward Modeling and BoN Evaluation Details

B.1 Reward Model Training Data Construction

To construct reward-model training data with sufficient quality coverage and behavioral diversity, we build a candidate response pool from three complementary sources. First, we collect natural responses from ten language models spanning different model families, parameter scales, and capability levels, including Qwen3-8B in both thinking and non-thinking modes, Qwen2.5-7B-Instruct, Llama-3.1-8B-Instruct, Gemma-7B-IT, Gemma-2B-IT, Gemini-3-Flash-Preview, DeepSeek-V4-Pro, Qwen3-235B-A22B-Instruct-2507, and Llama-3.3-70B. Each model generates one response

Table 15: Prompt used by the **Question Reviser.**

Question Reviser Prompt

```
You will be given a cultural norm, a previous scenario question, and diagnostic
information from the refinement process.
Your task is to revise the scenario, question, and hidden expected answer so that the
candidate more reliably instantiates the target norm.
The revision should address the identified problems while satisfying the following
requirements:
- The scenario and question must not directly or near-directly reveal the target norm.
- The appropriate response should depend on the target cultural norm rather than only on
generic logic, practical constraints, or politeness.
- The scenario should contain sufficiently specific contextual cues for the target norm to
be inferred.
- Contextual cues that incorrectly activate a non-target norm should be removed, weakened,
or replaced.
- The question should remain neutral and should not directly reveal the expected answer or
ask the model to state the cultural rule.
Return valid JSON containing:
scenario: the revised scenario;
question: the revised action-oriented question;
hidden_expected_answer: the revised reference answer;
generation_notes: a brief explanation of the changes made in response to the diagnostic
guidance.
Input:
{revision_input}
```

Table 16: Distribution of cultural norms and situated questions across 19 cultural groups.

Culture	# Norms	# Scenarios
Argentina	67	186
China	226	624
Germany	77	217
India	91	246
Iran	81	217
Italy	71	195
Japan	116	314
Mexico	82	220
Netherlands	60	168
Philippines	77	201
Russia	65	179
Saudi Arabia	63	171
South Africa	92	234
South Korea	70	193
Spain	74	203
Thailand	64	186
Ukraine	62	168
United States	119	340
Vietnam	62	168
Total	**1,619**	**4,430**

for each situated question. Each model generates one response for each situated question using the prompt template shown in Table 20.

Relying solely on naturally generated responses may cause the candidate pool to concentrate on a limited set of common response patterns and quality levels. To broaden its coverage of different degrees of cultural appropriateness and behavioral patterns, we further employ controlled generation to produce additional responses at varying quality levels. All candidate responses are subsequently evaluated using the same evaluation procedure.

In addition, we observe that responses in the intermediate quality range are relatively underrepresented in the initial pool. We therefore perform targeted data augmentation for responses with scores of 2 and 4. Using GPT-5.6 Sol, DeepSeek-V4-Pro, and Qwen3-235B-A22B-Instruct-2507, we generate and re-evaluate additional candidates, retaining only those that are actually assigned the target score by the automatic evaluator. By combining natural model responses, controlled diverse re-

Table 17: Statistics of the final data splits used in our experiments.

Split	# Scenarios
Train	3,521
Validation	449
Test	222
Total	**4,192**

Table 18: Outcome-quality scoring criteria used for automatic evaluation.

Score	Criterion
1	**Clearly wrong or opposite outcome.** The response recommends or preserves a decisively inappropriate action, or would clearly worsen the situation.
2	**Mostly inappropriate with material mitigation.** The core outcome remains inappropriate, but the response includes a concrete adjustment that meaningfully reduces the relevant harm.
3	**Mixed, indeterminate, or underspecified outcome.** The response contains both appropriate and inappropriate elements, or remains too generic or ambiguous to determine whether the decisive issue is resolved.
4	**Correct core outcome with a limited practical defect.** The response resolves the decisive action requirements and would likely produce an appropriate outcome, but contains a specific secondary omission, ambiguity, or mildly counterproductive recommendation.
5	**Fully appropriate outcome.** The response clearly recommends an appropriate and executable action that resolves all decisive requirements without conflicting or culturally inappropriate additional recommendations.

sponses, and intermediate-quality augmentation, we obtain a candidate pool spanning a broad range of response qualities and behavioral patterns for subsequent preference-pair construction.

Before constructing preference pairs, we first balance responses across different score ranges. We then construct preference pairs among responses to the same situated question with different quality scores, designating the higher score response as y^+ and the lower score response as y^-, while excluding ties. To prevent questions with larger candidate pools from contributing disproportionately to training, we retain at most eight preference pairs per question; when more than eight eligible pairs are available, we uniformly sample from them.

B.2 Reward Model Architecture and Training Details

We train two answer-only reward models based on Qwen3-0.6B and Qwen3-4B, respectively. Specifically, we add a randomly initialized linear reward head on top of the Transformer backbone and compute the scalar reward from the hidden state of the last non-padding token:

$$r_\theta(x, y) = \mathbf{w}^\top \mathbf{h}_{\text{last}} + b.$$

The reward head produces an unbounded scalar score. During training, both the Transformer backbone and the reward head are fully fine-tuned.

We train the models using the Bradley–Terry objective described in the main text. Both reward models are trained for two epochs, and we use the final checkpoint after the second epoch. We use AdamW with an effective batch size of 32 preference pairs and a maximum sequence length of 2,048 tokens, and perform training in BF16 precision. The learning rates are set to 2×10^{-5} for Qwen3-0.6B and 1×10^{-5} for Qwen3-4B. The main training configurations are summarized in Table 21.

B.3 Best-of-N Evaluation Details

To assess the robustness of the reward models across response distributions induced by different generators, we further report generator-disaggregated Best-of-N results, as shown in Table 22 and 23.

Table 19: Prompt used for automatic evaluation of culturally situated responses.

Automatic Evaluation Prompt

```
You are evaluating the final answer to a culturally grounded decision-making scenario.
Assign exactly one outcome-quality score from 1 to 5.  Evaluate only whether the
candidate's final proposed action would handle this specific situation appropriately.  Do
not separately score whether the candidate identifies, names, or explains the cultural
norm.  Use the target norm only as a private reference for determining the appropriate
practical outcome.
Score definitions:
1 --- Clearly wrong or opposite outcome.  The final recommendation directly performs,
endorses, or preserves the decisive culturally inappropriate action, or would clearly
worsen the situation.
2 --- Mostly inappropriate outcome with material mitigation.  The core outcome remains
inappropriate, but a concrete part of the response materially reduces the relevant
cultural or situational harm.
3 --- Mixed, indeterminate, or underspecified outcome.  The response contains important
appropriate and inappropriate components, or is too generic or ambiguous to determine
whether the decisive practical issue is resolved.
4 --- Correct core outcome with a limited practical defect.  The recommendation resolves
every decisive action requirement and would likely produce an appropriate outcome, but
contains a specific secondary omission, ambiguity, or mildly counterproductive action.
5 --- Fully appropriate outcome.  The recommendation clearly commits to an appropriate and
executable action that resolves every decisive requirement and contains no conflicting,
unnecessarily risky, or culturally inappropriate additional recommendation.
Boundary rules:
- Score the practical outcome rather than writing quality, response length, confidence,
cultural vocabulary, or explicit norm recognition.
- If any decisive action requirement remains unresolved, the response receives at most 3.
- Use 4 only when a specific action-level defect with limited practical consequence can be
identified; otherwise use 5.
- Merely mentioning relevant variables or suggesting that the model ''check'' local
customs or preferences does not constitute a solution unless it leads to a culturally
calibrated action.
- Reasonable variations consistent with the target norm and situational constraints should
be accepted.
Return valid JSON only:
{ ''score'':  1, ''evidence'':  ''Quote or closely paraphrase the decisive part of the
candidate answer.'', ''reason'':  ''Briefly explain why the answer meets this score
boundary.''  }
Culture:  {culture}
Target norm:  {norm}
Scenario:  {scenario}
Question:  {question}
Candidate answer:  {answer}
```

For each question, each generator provides 16 candidate responses, from which the reward model selects the highest-scoring response under $N = 8$ and $N = 16$. The results show that our reward models maintain a consistent advantage across candidate pools from different generators, indicating that their effectiveness is not tied to any particular generator.

C Additional Details for Policy Optimization

C.1 Norm Grounding Supervisor Training.

We instantiate the Norm Grounding Supervisor (NGS) from Qwen3-8B as an open-book binary classifier. Given the culture, gold cultural norm, scenario, question, final answer, and accompanying rationale, NGS predicts whether the response is *Grounded* or *Ungrounded*. A linear head is applied to the representation of the last non-padding token to produce the two classification logits.

The training data consist of both controlled synthetic responses and natural responses generated by diverse language models. We construct a binary subset that contrasts responses with successful norm grounding against those that fail to recover the relevant cultural norm, while excluding other failure types. This results in 16,545 training examples, 1,573 validation examples, and 117 test examples, with no overlap in norm IDs across splits.

We train NGS with standard cross-entropy loss and fine-tune all model parameters. Training uses AdamW with a learning rate of 1×10^{-5}, an effective batch size of 64, a maximum sequence length

Table 20: Prompt template for natural response generation.

Prompt

Answer the following culturally grounded decision-making question.

Return a JSON object with exactly two string fields:

```
{
  "answer":  "A direct, practical answer to the question.",
  "reasoning":  "A natural explanation supporting the answer."
}
```

The reasoning should be one coherent paragraph of roughly four to seven sentences. It should naturally move from a small set of decisive details in the scenario, to the most specific culture-linked convention those details make relevant, and then to how that convention supports the answer in this situation.

Do not label or divide the reasoning into steps. Do not use headings, numbered lists, bullet points, or terms such as Grounding, Norm, or Decision. Do not replace a specific cultural convention with broad themes. Do not invent a custom merely to sound culturally informed.

Return valid JSON only, with no markdown fence or additional text.

Culture:
{culture}

Scenario:
{scenario}

Question:
{question}

Table 21: Main training configurations of our reward models.

Configuration	Qwen3-0.6B	Qwen3-4B
Fine-tuning	Full-parameter	Full-parameter
Epochs	2	2
Learning rate	2×10^{-5}	1×10^{-5}
Effective batch size	32 pairs	32 pairs
Maximum sequence length	2,048	2,048
Optimizer	AdamW	AdamW
Training precision	BF16	BF16

of 2,048 tokens, and a cosine learning-rate schedule with 3% warmup. We train for two epochs and select the checkpoint with the highest validation macro-F1. The selected model achieves 94.70% macro-F1 on the validation set and 88.31% macro-F1 on the independent test set.

C.2 Training Configuration

We perform policy optimization on Qwen3-4B, Qwen3-8B, and DeepSeek-R1-Distill-Qwen-7B with Group Relative Policy Optimization. For the Qwen3 models, the chat template is configured with thinking enabled, while DeepSeek-R1-Distill-Qwen-7B uses its native reasoning format.

Our GRPO experiments are implemented with `verl`. At each optimization step, a batch of four training samples is used, with eight responses generated for each sample to form the GRPO groups, yielding 32 rollouts in total. Policy optimization is conducted for one epoch over 880 steps using AdamW with a learning rate of 1×10^{-6}. A constant learning rate schedule without warmup is adopted, with one PPO epoch per update. Rollouts are generated with a temperature of 1.0, top-p of 1.0, and top-k of -1, while both prompt and response lengths are capped at 2,048 tokens.

For each prompt, the scalar rewards of the eight sampled responses are converted into group relative advantages:

$$\hat{A}_i = \frac{R_i - \mu_{\mathcal{G}}}{\sigma_{\mathcal{G}} + 10^{-6}},$$

Selector	Params.	Qwen3-8B		Llama-3.1-8B		Qwen2.5-7B		Gemma-2-9B		Mistral-7B		Phi-3.5-mini	
		$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$
Random Selection	–	3.6351	3.6036	3.5676	3.6171	3.5766	3.5135	3.6622	3.6577	3.6892	3.7297	3.4414	3.5045
CRISP-RM-0.6B (Ours)	0.6B	3.7838	3.7477	3.7838	3.9099	**3.8784**	3.8378	**3.9189**	**3.9685**	3.9685	**4.0315**	3.6982	3.7523
CRISP-RM-4B (Ours)	4B	**3.8198**	**3.7973**	**3.9595**	**4.0315**	3.7793	**3.8874**	3.9144	3.9234	**3.9910**	3.9910	**3.8739**	**3.8694**
Skywork Reward V2 Qwen3(Liu et al., 2026)	0.6B	3.5901	3.4865	3.5541	3.5856	3.5541	3.5315	3.7523	3.7658	3.7703	3.7117	3.4414	3.5090
Skywork Reward V2 Qwen3(Liu et al., 2026)	4B	3.6216	3.5495	3.6351	3.7568	3.6667	3.6396	3.8919	3.8919	3.8153	3.8153	3.5676	3.5946
Skywork Reward V2 Llama-3.1(Liu et al., 2026)	8B	3.7117	3.6892	3.6351	3.6351	3.6441	3.6126	3.7928	3.8063	3.7928	3.7973	3.5766	3.5991
ArmoRM Llama-3(Wang et al., 2024a)	8B	3.6802	3.7117	3.6577	3.7117	3.7162	3.7523	3.8378	3.9054	3.7973	3.8514	3.5991	3.5901
QRM Gemma-2(Dorka, 2024)	27B	3.7793	3.7523	3.7432	3.8018	3.7072	3.8018	3.8739	3.8829	3.9369	3.9144	3.6802	3.6757
Skywork Reward Gemma-2(Liu et al., 2024)	27B	3.7477	3.7072	3.7117	3.7883	3.6757	3.7387	3.8288	3.8198	3.8874	3.9054	3.7162	3.7793
INF-ORM Llama-3.1(Minghao Yang, 2024)	70B	3.7162	3.7162	3.7703	3.8018	3.7973	3.8063	3.8919	3.9369	3.9324	3.9009	3.7883	3.8378

Table 22: Policy-disaggregated Best-of-N results on NormCompass. Each generator policy provides 16 candidate responses per question, and each reward-model selector chooses the highest-reward response among the first $N \in \{8, 16\}$ candidates.

Selector	Params.	Qwen3-8B		Llama-3.1-8B		Qwen2.5-7B		Gemma-2-9B		Mistral-7B		Phi-3.5-mini	
		$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$	$N=8$	$N=16$
Random Selection	–	59.6091	60.2719	53.6307	54.0937	54.6187	54.2729	59.6390	59.0919	55.5285	55.7763	58.5761	58.0949
CRISP-RM-0.6B (Ours)	0.6B	60.7810	60.8263	56.9511	56.7515	56.6034	57.0455	**61.0720**	61.1883	56.7140	57.2985	59.8294	60.2116
CRISP-RM-4B (Ours)	4B	**61.6390**	**61.7853**	**57.6375**	**58.8084**	**57.3164**	**58.2116**	60.9883	**61.6365**	**58.7010**	**59.7766**	**60.9487**	**61.1371**
Skywork Reward V2 Qwen3(Liu et al., 2026)	0.6B	59.9932	59.7340	51.0735	49.5677	51.1671	50.0705	59.8739	59.3523	53.1913	52.7934	56.4474	55.4477
Skywork Reward V2 Qwen3(Liu et al., 2026)	4B	60.4691	60.4916	52.3124	51.1317	52.0056	50.6120	60.7021	60.3504	53.7068	53.1513	56.8836	56.5060
Skywork Reward V2 Llama-3.1(Liu et al., 2026)	8B	59.7923	59.5819	52.5763	51.3792	52.5049	51.5029	60.1702	60.1713	54.2066	53.6836	57.8912	57.4712
ArmoRM Llama-3(Wang et al., 2024a)	8B	59.8254	59.2516	51.4487	49.4566	51.6016	50.3427	59.7149	59.4847	54.0735	53.0652	55.8644	55.0796
QRM Gemma-2(Dorka, 2024)	27B	61.0928	61.1122	53.4278	52.6028	53.0358	52.6591	60.5873	60.2842	54.5593	53.9561	57.3619	56.7910
Skywork Reward Gemma-2(Liu et al., 2024)	27B	60.8889	60.8658	53.3866	52.5216	52.6425	52.1802	60.5450	60.0294	54.6322	53.8608	56.8936	56.6295
INF-ORM Llama-3.1(Minghao Yang, 2024)	70B	60.4431	60.1909	51.6506	50.3911	52.4697	51.7775	60.1740	60.6276	53.6209	52.7630	57.3224	56.8871

Table 23: Policy-disaggregated Best-of-N results on the CultureForest. Following the main evaluation, we restrict the benchmark to cultural groups represented among the 19 cultures in our dataset.

where $\mu_{\mathcal{G}}$ and $\sigma_{\mathcal{G}}$ denote the mean and sample standard deviation of rewards within the response group. The resulting advantage is applied to all valid response tokens.

CRISP Reward Processing. We use CRISP-RM-4B as the cultural reward model. CRISP-RM receives the culture, scenario, question, and final answer. To obtain a bounded reward, we calibrate the original reward score using robust statistics estimated from a fixed validation set of 2,566 responses. Specifically, the median is $\mu = -2.078125$, and the robust scale is

$$s = \frac{q_{0.75} - q_{0.25}}{1.349} = 6.8859,$$

where $q_{0.25} = -7.5$ and $q_{0.75} = 1.7891$. The final reward is

$$r_{\text{CRISP}} = \sigma\left(\text{clip}\left(\frac{r_{\text{origin}} - \mu}{s}, -20, 20\right)\right).$$

Norm Grounding Supervision. The Norm Grounding Supervisor is an open-book binary classifier that receives the culture, gold norm, scenario, question, final answer, and visible rationale. It does not observe hidden reasoning traces. The two implementation labels are `Ungrounded` and `Grounded`; We use the predicted probability of the *Grounded* class as

$$r_{\text{NGS}} = p(\text{Grounded}),$$

and combine it with the cultural reward as

$$r_{\text{total}} = r_{\text{CRISP}} + \lambda r_{\text{NGS}},$$

Output Format and Invalid Responses. During training, the policy is instructed to return a JSON object containing exactly two fields, `answer` and `reasoning`. Outputs with malformed JSON, missing or additional fields, empty fields, malformed thinking tags, or residual thinking tags inside the parsed fields are treated as invalid. Invalid responses receive a fixed reward of -5 and are not passed to CRISP-RM or NGS. For valid responses, the scalar reward is assigned to the final valid response token before GRPO advantage computation.

C.3 Baselines and Evaluation

Reward Baselines. We compare CRISP-RM against Skywork-Reward and CuSiR. For Skywork, we use Skywork-Reward-V2-Qwen3-4B as the reward model. It receives the culture, scenario, question, and final answer, without access to the gold norm or rationale. Following the same calibration strategy as CRISP-RM, its reward is mapped to $[0, 1]$ using robust statistics estimated from a fixed validation set:

$$r_{\text{Skywork}} = \sigma\left(\text{clip}\left(\frac{r^{\text{origin}}_{\text{Skywork}} - 5.40625}{3.8686}, -20, 20\right)\right).$$

For CuSiR, we implement a CuSiR-style three-dimensional reward consisting of cultural, social, and politeness dimensions, each scored by a Llama-3-8B-Instruct judge. The cultural dimension has access to the gold cultural norm, while the other dimensions operate on the scenario, question, and answer. The three reward components are combined using the time-dependent weighting scheme adopted in our implementation.

Across reward model comparisons, we keep the main GRPO optimization budget and core hyperparameters aligned, including the policy initialization, number of rollouts, learning rate, number of training steps, and generation temperature.

NormCompass. We use GPT-5.6 Sol to evaluate only the final answer, with the culture, gold norm, scenario, and question provided as references. The evaluator assigns an integer score from 1 to 5, where higher scores indicate greater cultural appropriateness of the recommended action. The evaluator does not score the accompanying rationale or explicit norm recognition.

CultureForest. We evaluate on the Hard open-ended setting of CultureForest, restricted to 1,870 questions from cultures represented in our training data. We follow the official C-Verifier protocol. For each answer, the verifier evaluates its consistency with the three associated cultural norms and produces probabilities over *Satisfy*, *Neutral*, and *Violate*. We use the official normalized CultureForest score.

CulShield. For CulShield, we use the English Knowledge Coverage subset. We follow the official Yes/No evaluation protocol and require the generated response to begin with either "Yes" or "No". We use the official parser and evaluate with temperature 0.6, top-p 0.95, top-k 20, repetition penalty 1.05, and a maximum of 2,000 generated tokens. Invalid outputs are counted as incorrect and remain in the denominator.

C.4 Valid Response Evaluation

In the main results, invalid outputs are handled according to the evaluation protocol of each benchmark. For NormCompass and CultureForest, invalid outputs are assigned a score of zero, whereas for CulShield, invalid outputs are counted as incorrect and retained in the denominator. Thus, the reported end-to-end performance jointly reflects response quality and output-format compliance. As a complementary analysis, we additionally report the average score over valid outputs only in Table 24. In this analysis, responses that fail the output-format requirements are excluded before computing the score. This valid-response-only evaluation is intended to separate the quality of successfully parsed responses from performance degradation caused by invalid generations.

D Controlled Cultural Preference Analysis

We construct controlled response triplets for 100 scenarios from the frozen NormCompass test set using GPT-5.6 Sol. Each triplet contains an *Appropriate*, *Generic*, and *Opposite* response.

The construction prompts, shown in Table 25, are designed to vary the culturally decisive behavior while preserving general response quality. The Generic response retains the tone, fluency, broad structure, level of detail, and approximate length of the Appropriate response, while omitting or blurring the culturally relevant action. The Opposite response preserves the same surface qualities but reverses the culturally relevant action with a superficially plausible explanation. The target

Table 24: GRPO policy optimization results on valid responses only for NormCompass, CultureForest, and CulShield Knowledge Coverage. Δ denotes the change relative to the corresponding base policy under the same valid-response-only evaluation.

Policy	NormCompass		CultureForest		CulShield	
	Score	Δ	Score	Δ	Score	Δ
Qwen3-4B	3.37	–	56.72	–	73.08	–
+CuSiR	3.15	-0.22	25.30	-31.42	69.53	-3.55
+Skywork-Reward-V2-Qwen3-4B	3.52	+0.15	24.29	-32.43	76.66	+3.58
+CRISP	3.74	+0.37	58.13	+1.41	**80.19**	**+7.11**
+CRISP + NGS	**3.87**	**+0.50**	**61.46**	**+4.74**	77.92	+4.84
Qwen3-8B	3.73	–	60.69	–	69.60	–
+CuSiR	3.71	-0.02	27.76	-32.93	67.86	-1.74
+Skywork-Reward-V2-Qwen3-4B	3.64	-0.09	31.88	-28.81	72.42	+2.82
+CRISP	3.95	+0.22	60.87	+0.18	74.09	+4.49
+CRISP + NGS	**4.12**	**+0.39**	**61.24**	**+0.55**	**74.44**	**+4.84**
DeepSeek-R1-Distill-Qwen-7B	2.67	–	46.99	–	56.06	–
+CuSiR	2.59	-0.08	23.30	-23.69	53.46	-2.60
+Skywork-Reward-V2-Qwen3-4B	2.85	+0.18	33.07	-13.92	**61.77**	**+5.71**
+CRISP	3.09	+0.42	56.14	+9.15	60.52	+4.46
+CRISP + NGS	**3.19**	**+0.52**	**57.14**	**+10.15**	57.26	+1.20

cultural norm is provided only during triplet construction and is not exposed to the reward models during evaluation.

To obtain a high confidence evaluation set, we further use GPT-5.6 Sol to independently assess the cultural consistency of the constructed responses and retain triplets satisfying

$$s_A > s_G > s_O.$$

This results in 71 triplets, which are used for the preference analysis reported in the main text.

E Norm Grounding Analysis

We conduct the norm grounding analysis on the full NormCompass test set of 222 scenarios across three policy models: Qwen3-4B, Qwen3-8B, and DeepSeek-R1-Distill-Qwen-7B. For each model, we compare the original policy with policies optimized using CRISP-RM and CRISP-RM with NGS. For each model, method, and scenario, we evaluate one sampled response.

Norm Match Evaluation. We use GPT-5.6 Sol to evaluate whether the observable rationale recovers the cultural norm relevant to the current scenario. The evaluator is provided with the culture, target norm, scenario, question, generated rationale, and final answer, while remaining blind to the policy model and optimization method. As shown in Table 26, the evaluator assigns a Norm Match score $N \in \{0, 1, 2\}$, where $N = 0$ indicates that the relevant norm is not identified or is incorrectly identified, $N = 1$ indicates partial or implicit recognition, and $N = 2$ indicates clear and accurate recognition of the target norm. The final answer is provided only to resolve references and determine whether the identified norm is used in the rationale, rather than to assess answer quality. We use temperature 0 for the evaluator.

For each policy variant, we compute the mean Norm Match score over all 222 scenarios:

$$\overline{N}_{p,m} = \frac{1}{222} \sum_{i=1}^{222} N_{p,m,i},$$

where p denotes the policy model and m denotes the optimization variant. Invalid model outputs are assigned $N = 0$.

Table 25: Prompts used to construct the controlled cultural preference triplets.

Prompt	Content
System	`You construct controlled response triplets for a cultural decision-making experiment. Follow the requested semantic edit exactly while preserving fluent, natural English. Return JSON only.`
Controlled rewrite	`Create two controlled rewrites of the provided appropriate answer. Generic must preserve the answer's tone, fluency, broad structure, level of detail, and approximate length, but remove or blur the decisive action tied to the target norm. It should sound polite and superficially reasonable, yet fail to commit to the culturally relevant action. It must not become clearly opposite or obviously wrong. Opposite must preserve the same tone, fluency, broad structure, level of detail, and approximate length, but reverse the decisive culturally relevant action. Give it a superficially plausible explanation. Its main defect must be the action, not grammar, incoherence, rudeness, or low writing quality. Do not include labels, meta-commentary, phrases such as ''this violates the cultural norm'', or explanations of how you edited the answer. Do not copy the target norm verbatim merely to signal the category. Culture: {culture} Target norm (private construction reference): {norm} Scenario: {scenario} Question: {question} Appropriate answer: {appropriate} Return exactly this JSON object: {"generic":"...","opposite":"..."}`
Full triplet	`Create a controlled triplet for the scenario. Appropriate must clearly resolve the decisive action in a way consistent with the target norm. Generic must match its tone, fluency, broad structure, detail, and approximate length but remove or blur the decisive culturally relevant action without becoming clearly opposite. Opposite must match the same writing quality and approximate length but reverse the decisive culturally relevant action with a superficially plausible explanation. Do not include labels, meta-commentary, phrases such as ''this violates the cultural norm'', or explanations of the edits. Do not copy the target norm verbatim merely to signal the category. Culture: {culture} Target norm (private construction reference): {norm} Scenario: {scenario} Question: {question} Return exactly this JSON object: {"appropriate":"...","generic":"...","opposite":"..."}`

Stratified Analysis. To examine how optimization affects responses with different initial levels of norm grounding, we stratify scenarios according to the Norm Match score of the original policy:

$$G_{p,n} = \{i : N_{p,\mathrm{Base},i} = n\}, \qquad n \in \{0, 1, 2\}.$$

These groups are kept fixed when comparing the original policy, CRISP-RM, and CRISP-RM with NGS, ensuring that the three variants are evaluated on the same scenarios within each grounding level.

Valid-Response-Only Analysis of Norm Grounding Supervision. In the analysis presented in Figure 5, invalid outputs are assigned a score of zero, consistent with the end-to-end evaluation protocol used for NormCompass. To examine whether the observed trends are driven by invalid generations, we additionally conduct a valid-response-only analysis. Table 27 reports Norm Match scores computed after excluding invalid outputs. For the stratified answer-quality analysis, we retain the item only when the outputs from Base, CRISP, and CRISP+NGS are all valid, and group the retained pairs according to the Norm Match score of the corresponding Base response. The resulting answer-quality scores are reported in Table 28. The valid-response-only results preserve the main trends observed in Figure 5, indicating that the effects of CRISP-RM and NGS are not primarily driven by differences in invalid generation rates.

Table 26: Prompt used for Norm Match evaluation.

Prompt	Content
Norm Match	`You are an independent evaluator of the observable reasoning in a culturally grounded decision-making response.` `The Target Norm is a private authoritative reference. Evaluate whether the Candidate Reasoning semantically recovers and uses the core cultural requirement. Do not require quotation, keyword overlap, or explicit mention of the country or the word ''norm''. A clear paraphrase counts fully.` `Judge only Norm Match using exactly one score:` `0 --- Not recognized or incorrect. The reasoning does not express the target norm's core requirement, expresses an opposite or conflicting principle, substitutes a merely generic value such as politeness or respect, discusses only an adjacent norm, or invents a convention. A correct-looking final action alone cannot rescue reasoning that omits the norm.` `1 --- Partial or implicit recognition. The reasoning is directionally related to the target norm but remains incomplete, indirect, ambiguous, or misses a material part of its direction, scope, condition, or strength.` `2 --- Correct semantic recognition. The reasoning clearly and accurately states or unambiguously paraphrases the target norm's core requirement and uses it to explain the recommendation in this situation. Verbatim wording is not required.` `The Candidate Answer is provided only to resolve references and check whether the reasoning actually uses the stated principle. Do not separately score answer quality, fluency, length, confidence, cultural vocabulary, or hidden intentions. Give no credit for information that appears only in the Target Norm, Scenario, Question, or Candidate Answer rather than in the Candidate Reasoning.` `Culture: {culture}` `Target Norm: {norm}` `Scenario: {scenario}` `Question: {question}` `Candidate Reasoning: {reasoning}` `Candidate Answer: {answer}`

Table 27: Norm Match scores on valid responses only.

Method	Qwen3-4B	Qwen3-8B	DeepSeek-Qwen-7B
Base	0.8472	1.0679	0.3263
CRISP	<u>1.1963</u>	<u>1.3153</u>	<u>0.7281</u>
CRISP+NGS	**1.2715**	**1.3704**	**0.8279**

Table 28: Answer quality on jointly valid responses, stratified by the Norm Match score of the base policy. An item is retained only when the outputs of Base, CRISP, and CRISP+NGS are all valid. N denotes the Norm Match score of the corresponding base-policy response, and Δ denotes the change relative to Base within each group.

Method	$N = 0$		$N = 1$		$N = 2$	
	Score	Δ	Score	Δ	Score	Δ
Base	2.2909	–	3.6931	–	**4.7746**	–
CRISP	3.1745	+0.8836	3.7302	+0.0370	4.4437	-0.3310
CRISP+NGS	**3.2618**	**+0.9709**	**3.8836**	**+0.1905**	4.6268	-0.1479