MEMPILOT: LEARNING TO ORGANIZE AND NAVIGATE LATENT MEMORY

Anonymous authors
Paper under double-blind review

ABSTRACT

Large language models (LLMs) are increasingly capable of using long and complex histories, but processing the full history for every query remains expensive. Latent memory stores past information in reusable states, but repeatedly updating a single state can make earlier information difficult to recover as history grows. Storing history in multiple states can preserve earlier information, but introduces a new problem of retrieving the states relevant to each query. To this end, we propose MEMPILOT, a framework for organizing and navigating growing latent memory. First, we store history as independently written and restorable memory states, preventing later writes from modifying earlier ones. Each state is paired with a compact semantic key that supports candidate selection and briefly describes its content. Second, we retrieve evidence sequentially from memory: evidence from each read guides the next state selection, read instruction, and decision to stop. We supervise state readouts with page-local evidence to support navigation and train the access policy through RL post-training, using same-history counterfactual comparisons for more local credit assignment. Together, these components make growing latent memory easier to preserve and navigate adaptively. We evaluate MEMPILOT on five QA and long-term-memory benchmarks under two distinct latent-memory backends. Across both backends, MEMPILOT substantially improves over the corresponding native memory baselines. The five-task average improves from 13.51 to 39.99 with Metis and from 15.14 to 33.10 with δ-Mem.

1 INTRODUCTION

LLMs increasingly need to process long documents and growing interaction histories. Even with efficient attention kernels and cache management, the attention computation and key–value storage needed to use these histories grow with input length (Dao et al., 2022; Kwon et al., 2023), and a longer context window does not guarantee reliable use of its contents (Liu et al., 2024). Existing works use several forms of external memory to reuse historical information more efficiently. Textual memory systems store passages, records, or conversations for later retrieval (Lewis et al., 2020; Borgeaud et al., 2022; Packer et al., 2023; Zhong et al., 2024). Latent-memory methods encode history into continuous representations that can be reused without repeatedly processing the original text (Rae et al., 2020; Bulatov et al., 2022; Chevalier et al., 2023; Ge et al., 2024; Wang et al., 2024; 2025). Recent latent-memory methods also support continual writing and later querying of stored states (Zhang et al., 2026c; Lei et al., 2026).

Existing latent-memory approaches often accumulate history through repeated updates to the same state. Later writes may alter representations of earlier information, making previous facts harder to recover. Storing parts of the history in separate states avoids this interference, but shifts the difficulty to access: the system must identify and combine the evidence needed for each query. Figure 1 illustrates these two challenges. Independent states preserve earlier information, while static access can still leave a multi-step question incomplete. Appendix C.4 provides the full example.

Motivated by this observation, we introduce MEMPILOT, a framework that organizes history as independently written, restorable memory states and accesses them through sequential navigation. Each state is paired with a compact semantic key used for candidate selection, while its reader produces a query-conditioned readout when the state is restored. Page-local evidence supervision trains these readouts to expose useful partial information even when a single page is insufficient to answer

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: **Growing latent memory requires both organization and navigation.** Left: repeatedly updating a single cumulative state can make earlier information harder to recover, while independently written states remain unchanged. Right: independent states avoid this interference, but static access can still leave a multi-step question incomplete. Evidence-conditioned sequential navigation recovers the missing information and reaches the correct answer.

the full question. Because states are written independently, new history can be added without modifying previously stored states. MEMPILOT operates on top of an existing latent-memory backend and does not require access to its internal state representation.

At query time, MEMPILOT retrieves a candidate set using the question and semantic keys. The navigation policy then selects states sequentially from this fixed set. For subsequent reads, a frozen generator forms a focused read instruction from the original question, the selected key, and the evidence acquired so far. The policy continues reading until it selects STOP or exhausts its read budget. This brings evidence-guided sequential access (Trivedi et al., 2023) to latent memory states.

Training sequential access requires assigning credit to individual READ and STOP decisions rather than only to complete trajectories. We therefore branch an alternative legal action from a visited history and roll out both continuations under the same behavior policy. Their returns and return difference supervise an action-value critic, whose lagged copy provides the baseline for RL post-training of the navigation policy.

Our contributions are threefold:

- We introduce MEMPILOT, which combines independently restorable states with page-local evidence supervision. This supports both preservation of earlier information and recovery of partial evidence for subsequent navigation.
- We formulate memory use as evidence-conditioned sequential navigation: acquired evidence informs state selection, read instructions, and stopping. Same-history counterfactual comparisons provide more local supervision for individual READ/STOP decisions.
- We instantiate the same interface and training procedure with two latent-memory backends and evaluate them on five QA and long-term-memory benchmarks. The five-task average improves from 13.51 to 39.99 with Metis and from 15.14 to 33.10 with δ-Mem, showing that the framework extends beyond a single backend.

2 RELATED WORK

Textual memory and sequential retrieval. Efficient attention and cache management reduce long-context execution costs (Dao et al., 2022; Kwon et al., 2023), but do not ensure reliable use of the available information (Liu et al., 2024). RAG and RETRO retrieve stored passages when needed (Lewis et al., 2020; Borgeaud et al., 2022), while MemGPT and MemoryBank manage textual records across interactions (Packer et al., 2023; Zhong et al., 2024). IRCoT further interleaves

reasoning with retrieval so that intermediate evidence can guide later searches (Trivedi et al., 2023). MEMPILOT instead navigates a bank of stored latent states. Semantic keys provide a compact textual interface for candidate selection, while evidence from each restored state can affect the next READ/STOP decision. The answerer uses semantic keys and selected state readouts without accessing the original source passages.

Latent memory and its organization. Compressive and Recurrent Memory Transformers retain activations or memory tokens across segments (Rae et al., 2020; Bulatov et al., 2022), while Memorizing Transformers retrieve prior key–value representations (Wu et al., 2022). AutoCompressors and ICAE encode contexts into reusable continuous representations (Chevalier et al., 2023; Ge et al., 2024). MemoryLLM maintains an updatable latent memory pool, and M+ extends it with long-term storage and learned retrieval (Wang et al., 2024; 2025). Metis and δ-Mem provide different mechanisms for writing and restoring persistent states (Zhang et al., 2026c; Lei et al., 2026). These methods provide different forms of latent storage. MEMPILOT can use these methods through a common interface for independently writing, restoring, and querying states. Its organization and navigation operate without inspecting the internal state representation. We compare independent organization with cumulative updating under a matched persistent-storage budget.

Learning memory navigation. Recent methods have begun to learn how memory should be used at query time. ElasticMem builds a latent memory bank, retrieves memories from the reasoner's hidden state, and learns how much latent capacity to allocate to them (Feng et al., 2026). BudgetMem learns query-aware routing across memory-processing budgets, while MemRL combines semantic retrieval with learned memory utility (Zhang et al., 2026a;b). These methods show the value of learning memory use beyond fixed retrieval rules. In MEMPILOT, each restored state supplies query-conditioned evidence that enters the observed history. That evidence informs both the next selection or stopping decision and the instruction used to read a subsequently selected state.

The sequential setting also requires credit assignment. GRPO compares trajectory-level returns within a group (Shao et al., 2024), while GiGPO combines episode-level and step-level relative advantages (Feng et al., 2025). COMA uses an action-value critic to construct a counterfactual baseline (Foerster et al., 2018). Our procedure generates alternative continuations from the same observed access history and uses their return differences to train the values of individual READ/STOP decisions.

3 MEMPILOT

MEMPILOT organizes a growing history into a reusable bank of independently restorable memory states and navigates this bank sequentially at query time. Evidence from previous reads can guide subsequent state selection and read instructions, and inform when to stop. We train the navigation policy using counterfactual continuations that branch from the same observed history.

The framework uses a generic latent-memory interface. A backend provides a writer E_ϕ that maps a source segment to a restorable state m and a reader R_ϕ that produces a query-conditioned readout from that state. MEMPILOT treats the representation of m as opaque: it requires only that states can be written independently, saved, restored, and queried through the reader. We instantiate this interface with both Metis and δ-Mem (Zhang et al., 2026c; Lei et al., 2026). Figure 2 summarizes the framework. Backend-specific training details are given in Appendix A.5.

3.1 ORGANIZING GROWING LATENT MEMORY

We first turn a growing history into a bank of independently restorable states whose readouts expose page-local evidence. Given a source history H, we partition it into source pages $p_1, \ldots, p_K$ without using future evaluation questions. Document datasets follow natural passage boundaries, while conversational and long-history datasets use the segmentation rules described in Appendix A.4.

Before constructing the final state bank, we first adapt the memory backend with standard QA supervision and then add page-local evidence supervision. A page may contain only an intermediate fact needed for a multi-step answer, rather than enough information to answer the entire question. We therefore supervise the reader with evidence supported by the individual page. For a training




Figure 2: Overview of MEMPILOT. (1) Each source page is independently encoded into a restorable memory state and paired with a semantic key. (2) The navigator selects sequentially from a fixed set of semantic-key candidates. Each readout enters the navigation history and can guide subsequent state selection, read instructions, and stopping. (3) During training, main and alternative continuations branch from the same observed history. Their returns and return differences supervise the critic. A lagged critic provides the baseline for actor updates on the main trajectories.

question u, page p, and annotated page-local evidence z, we minimize the negative log-likelihood of the evidence:

$$\mathcal{L}_{\text{read}}(\phi) = -\log p_\phi(z \mid u, E_\phi(p)) \,. \tag{1}$$

The full page is written into memory, while z is used only as the readout target. Backend-specific adaptation procedures are provided in Appendix A.5.

After adaptation, each page is written independently from a reset memory state and paired with a query-independent semantic key computed by κ:

$$m_i = E_\phi(p_i), \qquad k_i = \kappa(p_i), \qquad i = 1, \ldots, K. \tag{2}$$

Writing a new page leaves previously stored states unchanged, and restoring a state carries no residual memory from another state. Semantic keys provide a compact textual interface for retrieval and navigation. They may contain source-derived facts, but do not expose the original source passages at query time. Together with latent-state readouts, they form the information interface used by MEMPILOT. The bank can therefore grow by adding new states and can be reused across questions without rewriting earlier states.

3.2 EVIDENCE-CONDITIONED SEQUENTIAL NAVIGATION

Given question q, BM25 (Robertson & Zaragoza, 2009) ranks the query-independent semantic keys and retains up to N candidates:

$$C = \text{TopN}_i \, \text{BM25}(q, k_i). \tag{3}$$

This candidate set remains fixed throughout navigation. Let $\mathcal{H}_t = (i_s, u_s, o_s)_{s=1}^{t}$ denote the complete history of the first t reads, $\mathcal{O}_t = (o_1, \ldots, o_t)$ the acquired memory observations, and I_t the states already read. We write $C_t = C \setminus I_t = (c_{t,1}, \ldots, c_{t,n_t})$ for the remaining unread candidates, preserving their initial ranking. Removing a read state does not introduce new candidates. The candidate limit N bounds the number of states exposed to the policy, while the read budget B

bounds the number of states that can be restored. Initial candidate retrieval operates over the growing state bank, so these limits do not imply constant persistent storage or retrieval work. After t completed reads, the policy conditions on the question, unread candidate-key pairs, previous reads, and remaining budget:

$$h_t = \big(q,\ (c_{t,j}, k_{c_{t,j}})_{j=1}^{n_t},\ \mathcal{H}_t,\ B - t\big). \tag{4}$$

The policy selects an action a_t from $\pi_\theta(\cdot \mid h_t)$ over the legal actions. A READ action selects an unread state from C_t while budget remains, and STOP becomes legal after the first read. Source passages, unread state readouts, reference answers, evidence labels, and rewards are not included in the policy observation.

When a READ action selects state i_{t+1}, the first read uses the original question directly. For subsequent reads, a frozen read-instruction generator D conditions on the question, acquired memory observations, and selected semantic key. The memory reader restores the selected state and queries it with the resulting instruction:

$$u_{t+1} = \begin{cases} q, & t = 0, \\ D(q, \mathcal{O}_t, k_{i_{t+1}}), & t \geq 1, \end{cases} \qquad o_{t+1} = R_\phi(u_{t+1}, m_{i_{t+1}}). \tag{5}$$

The completed read $(i_{t+1}, u_{t+1}, o_{t+1})$ is appended to $\mathcal{H}_{t+1}$, and the remaining budget decreases by one.

Navigation terminates when the policy selects STOP, exhausts its read budget, or has no unread candidates left. After $d \leq \min(B, |C|)$ reads, the fixed answerer G produces $\hat{y} = G\big(q, (k_{i_s}, o_s)_{s=1}^{d}\big)$. The answerer receives the question, selected semantic keys, and their readouts, but not the original source pages.

Let $\mathcal{S}(\hat{y}, y) \in [0, 1]$ denote the final QA score against reference answer y, and let $\eta \geq 0$ be a fixed penalty per state read. We maximize expected trajectory utility and define continuation-return targets that exclude read costs already incurred:

$$U(\tau) = \mathcal{S}(\hat{y}, y) - \eta d, \qquad J(\theta) = \mathbb{E}_{\tau \sim \pi_\theta}[U(\tau)], \qquad \widehat{R}_t = \mathcal{S}(\hat{y}, y) - \eta(d - t). \tag{6}$$

Here $\widehat{R}_t$ is the return from h_t, before action a_t. It includes the cost of any read selected at that decision but excludes the costs of the t completed reads. The penalty controls read depth rather than representing measured end-to-end latency.

3.3 Counterfactual Training for Navigation

The final QA score evaluates a complete trajectory without directly comparing alternative READ or STOP decisions at an intermediate history. We obtain such comparisons by constructing continuations that take different legal actions from the same observed history.

For each training question, we sample main trajectories under a behavior policy π_{old} and select a visited history h that admits an alternative legal action. The main continuation begins with its sampled action a, while an alternative continuation begins with a different legal action $a' \neq a$. After these initial actions, both continuations follow π_{old}. They share the observed prefix and action-to-state mapping at the fork, but their subsequent instructions, readouts, and stopping decisions may differ. Alternative continuations are used only to train the critic; actor updates use only the main trajectories.

Let $\mathcal{D}$ contain decision–return tuples $(h, a, \widehat{R})$ from the main and alternative continuation suffixes, and let $\mathcal{P}$ contain paired tuples $(h, a, a', \widehat{R}, \widehat{R}')$ at their shared branching histories. Each return is measured from its associated history as defined in Eq. (6). We train an action-value critic Q_ψ to fit both continuation returns and the return differences between paired actions:

$$\begin{aligned} \mathcal{L}_Q(\psi) = \mathbb{E}_{\mathcal{D}} \left[\ell_{\text{Huber}}\Big(Q_\psi(h, a) - \widehat{R} \Big) \right] \\ + \lambda_\Delta \mathbb{E}_{\mathcal{P}} \left[\ell_{\text{Huber}}\Big(Q_\psi(h, a) - Q_\psi(h, a') - (\widehat{R} - \widehat{R}') \Big) \right]. \end{aligned} \tag{7}$$

Here ℓ_{Huber} is the Huber loss with threshold one, and λ_Δ controls the weight of the paired comparison term. The first term fits individual continuation returns, while the second explicitly supervises the value difference between alternative actions taken from the same observed history.

Table 1: End-to-end performance across latent-memory backends. MEMPILOT uses fixed candidates and improves over the corresponding cumulative memory interface under both Metis and δ-Mem. Avg. is the unweighted mean across the five benchmark metrics. †: SHINE uses the last 40,000 tokens for BEAM and LongMemEval-S.

System	Hotpot	2Wiki	LoCoMo	BEAM	LME-S	Avg.	Δ Avg.
δ-Mem, cumulative	15.62	28.89	8.67	11.70	10.80	15.14	–
MEMPILOT (δ-Mem)	52.83	46.89	26.02	18.58	21.20	**33.10**	**+17.96**
Metis, cumulative	12.78	23.63	8.76	10.98	11.40	13.51	–
MEMPILOT (Metis)	65.77	57.89	26.32	23.16	26.80	**39.99**	**+26.48**
SHINE (8B)	60.32	59.90	17.67	10.81†	12.20†	32.18†	–

A lagged critic $Q_{\bar{\psi}}$ supplies a baseline computed from the values of all legal actions at each history. This baseline depends on the history but not on the action sampled at that history. For actor updates, we subtract the baseline from main-trajectory continuation returns and divide by a within-question return standard deviation with a positive floor. The resulting advantages are used in the clipped PPO objective (Schulman et al., 2017). The critic is used only during training. Appendix B.2 specifies the exact baseline, advantage normalization, PPO objective, and sampling procedure.

4 EXPERIMENTS

In this section, we conduct experiments to answer the following research questions:

- **RQ1:** Does MEMPILOT improve end-to-end performance across latent-memory backends?
- **RQ2:** Does independent memory organization preserve usable information as history grows?
- **RQ3:** Does learned sequential navigation improve memory access beyond static retrieval?
- **RQ4:** What information is available through the latent-memory interface, and how does its practical performance compare with textual access?
- **RQ5:** Does counterfactual training improve the navigation policy?

4.1 EXPERIMENTAL SETUP

Tasks and evaluation. We train MEMPILOT on HotpotQA and evaluate the frozen system on HotpotQA, 2Wiki, LoCoMo, BEAM-128K, and LongMemEval-S (Yang et al., 2018; Ho et al., 2020; Maharana et al., 2024; Tavakoli et al., 2026; Wu et al., 2025). The four transfer benchmarks use no additional target-domain training. We report F1 for HotpotQA and 2Wiki, the official score for LoCoMo, rubric score for BEAM, and accuracy for LongMemEval-S. The five-task average score is their unweighted mean. Dataset statistics, filtering, and evaluation protocols are given in Appendices A.1 and A.2.

Models and access settings. We instantiate MEMPILOT with Metis-4B and δ-Mem as latent-memory backends (Zhang et al., 2026c; Lei et al., 2026). Qwen3-4B is used for navigation, read-instruction generation, and final answering. Unless stated otherwise, the candidate limit is $N = 16$, the read budget is $B = 8$, and the per-read cost is $\eta = 0.002$. Candidates are ranked once from the semantic keys using the original question and remain fixed throughout navigation in both training and evaluation.

4.2 OVERALL PERFORMANCE (RQ1)

Table 1 compares MEMPILOT with each backend's native cumulative interface and with SHINE as an external system reference. The average score increases from 15.14 to 33.10 with δ-Mem and from 13.51 to 39.99 with Metis, corresponding to gains of 17.96 and 26.48 points, respectively. Both backends improve on every evaluated task, indicating that the gain is not driven by a single benchmark. The improvements across both state representations show that the same organization




Figure 3: **Independent organization preserves more usable information as history grows.** (a) The two organizations start from the same recovery quality at load 1, but cumulative recovery degrades rapidly as more history is written. Loads 8 and 16 compare the two organizations under approximately matched persistent storage. (b) Under the same saved access route, replacing independent page payloads with the cumulative-state payload lowers final QA performance.

and navigation framework can substantially improve the use of different latent-memory backends. We use the stronger Metis configuration for the controlled analyses that follow.

4.3 Independent Memory Organization (RQ2)

We examine memory organization after adapting the reader with page-local evidence supervision, whose single-state results are reported in Appendix C.1. Figure 3(a) then compares recovery as stored history grows. Both organizations start at the same performance, but cumulative recovery deteriorates with additional writes while independent states remain more stable. The gap persists at loads 8 and 16, where persistent storage is approximately matched. This comparison tests whether information remains recoverable as the memory bank grows.

To test how this difference affects QA under fixed navigation, we replay the same saved access route with the cumulative-state payload replacing the independent page payloads (Figure 3(b)). F1 drops from 65.77 to 57.63. The fixed route separates the effect of the stored representation from changes in state selection: independent states supply more useful evidence along the same access route.

4.4 Sequential Memory Navigation (RQ3)

Access-method comparison. Figure 4(a) compares learned navigation with static BM25 access and a policy-first fixed two-read control. Increasing BM25 depth improves performance, but depth 8 still falls below the trained policy, which reaches 65.77 F1 with 1.75 state reads on average. The fixed two-read control uses the same learned first read, then selects the highest-ranked remaining BM25 page. It reaches 63.07 F1 with 2.00 reads. The first selection itself is also important: using only the policy's first read reaches 61.33 F1, compared with 40.33 for a single BM25 read. Full navigation further raises F1 to 65.77, showing gains from both the initial state choice and subsequent evidence-conditioned decisions. Read count measures access depth; measured end-to-end query costs are reported separately in Table 13.

Candidate selection and coverage. The learned policy also changes which candidates are accessed. Its first read selects the top-ranked BM25 page on 20.5% of questions, while 93.0% of its first choices lie within the BM25 top 8 (Figure 4(b)). BM25 therefore supplies useful candidates, and the policy selects among them using the question and semantic keys. For longer histories, candidate coverage can become a separate constraint; Appendix C.2 studies candidate refresh as an inference-time extension.




Figure 4: **Learned navigation improves answer quality at lower state-read depth.** (a) Static BM25 access improves with read depth, but remains below the trained navigation policy despite using substantially more state reads. Policy-first controls use the learned first read but restrict subsequent access. (b) The learned policy selects the BM25 top-ranked page on only 20.5% of questions, while 93.0% of its first choices fall within the BM25 top 8.

4.5 Latent-Memory Interface and Textual Access (RQ4)

Semantic keys and state readouts. Table 2(a) examines the roles of semantic keys and state readouts under several controlled interfaces. Independent key-only retrieval reaches an average score of 35.50, and adding state access raises the score to 39.99, with the largest gains on HotpotQA and 2Wiki. The saved-route interventions distinguish information used during navigation from information available to the final answerer. Removing readouts only from the final answer context leaves an average score of 37.57, since state evidence has already influenced the route. Removing keys from the final answer context lowers the score to 31.96. Both channels contribute to the final answer, while state readouts also guide which evidence is acquired along the route.

Comparison with textual access. Table 2(b) compares MemPilot with two forms of direct textual access. RAG top-2 reaches 37.62 Avg., compared with 39.99 for MemPilot, showing that organized latent-state access can outperform a simple retrieval pipeline over the original text. The full-context baseline provides a stronger comparison and reaches 39.51 Avg., close to MemPilot overall. At the task level, MemPilot scores higher on 2Wiki, BEAM-128K, and LongMemEval-S, while the full-context baseline scores higher on HotpotQA and LoCoMo. These results show that improved organization and navigation can make latent memory competitive with direct textual access, without requiring the answerer to process the original history at every query.

Query-time cost. The system-level advantage becomes clearer on the longest histories. On BEAM-128K and LongMemEval-S, MemPilot combines higher answer quality with approximately 3.6× and 3.7× lower measured query time, respectively. Furthermore, its peak memory is also about 73–75% lower on these two benchmarks. The state bank remains reusable across queries, and Appendix C.1 further shows that rank-64 compression reduces persistent state storage by approximately 7.9× while changing Avg. from 39.99 to 39.36.

4.6 Navigation Policy Training (RQ5)

Table 3 compares policies trained from the same initialization with the same navigation interface. GRPO samples five complete trajectories per source. Counterfactual training samples four main trajectories and one alternative continuation for critic training; actor updates use only the main trajectories. Counterfactual training reaches an average score of 39.99, compared with 37.88 for GRPO and 37.48 for GiGPO. Compared with GRPO, the gains extend to all four transfer benchmarks: +3.46 on 2Wiki, +1.51 on LoCoMo, +1.68 on BEAM-128K, and +3.00 on LongMemEval-S. Thus, the advantage of the full counterfactual training procedure is not limited to the HotpotQA training

Table 2: Information available through the latent-memory interface and comparison with textual access. (a) Semantic keys and latent-state readouts provide complementary information. Full-route controls replay routes from fixed-candidate navigation. (b) MEMPILOT is compared with direct retrieval and the full-context baseline.

Interface	Hotpot	2Wiki	LoCoMo	BEAM	LME-S	Avg.
(a) Semantic-key and latent-state controls						
Full key + state	65.77	57.89	26.32	23.16	26.80	**39.99**
Keys only, independent retrieval	59.62	45.31	27.99	21.40	23.20	35.50
Full route, no keys at answer	58.52	46.81	18.85	16.62	19.00	31.96
Full route, no readouts at answer	64.15	49.23	28.07	21.20	25.20	37.57
(b) Direct textual access						
RAG top-2	52.77	55.38	25.51	21.24	33.20	37.62
Full context	67.24	55.70	44.42	13.99	16.20	39.51

Table 3: Navigation-policy training across five benchmarks. All policies use fixed candidates at inference. Counterfactual training improves over GRPO and GiGPO under the same navigation interface. Δ Avg. is measured relative to GRPO.

Training	Hotpot	2Wiki	LoCoMo	BEAM	LME-S	Avg.	Δ Avg.
GRPO	64.90	54.43	24.81	21.48	23.80	37.88	–
GiGPO	65.18	52.52	24.89	20.23	24.60	37.48	-0.40
Counterfactual	65.77	57.89	26.32	23.16	26.80	**39.99**	**+2.11**

domain. All policies are trained on HotpotQA and evaluated on the other four benchmarks without target-domain training.

5 CONCLUSION AND LIMITATIONS

We study how to make growing latent memory easier to organize and access. MEMPILOT stores history in independently written, restorable states and navigates them using acquired evidence. Across two latent-memory backends, it substantially improves over cumulative memory, while controlled experiments validate the roles of independent organization, sequential navigation, and complementary key–state information. The resulting latent interface is also competitive with textual access, exceeding simple retrieval and matching the full-context baseline on average, with clear query-time advantages on the longest evaluated histories.

Limitations. MEMPILOT improves how latent memory is used but remains limited by the information preserved and exposed by the underlying backend. Moreover, independent states increase persistent storage and candidate-retrieval cost as the memory bank grows, even though state compression can reduce this overhead. Future work can explore stronger latent-memory backends together with hierarchical retrieval, compression, and memory-management mechanisms for larger and longer-lived memory banks.

AI USE STATEMENT

Generative AI assisted with implementation and debugging, experiment orchestration, data processing, literature verification, mathematical checking, manuscript drafting and translation, and figure-layout exploration. All methods, results, citations, and final text were reviewed and approved by the authors.

Ethics statement

The experiments use public benchmarks and introduce no new human-subject study. Neural states can retain sensitive or outdated source information and do not provide anonymization. Deployment therefore requires consent, provenance, access controls, and deletion of states and associated keys.

Reproducibility statement

Appendix A documents the data splits, evaluation protocols, baselines, memory implementations, and inference settings. Appendix B gives the full navigation-policy training procedure, and Appendix C reports additional analyses. The supplementary material also includes code for reproducing the training and evaluation pipelines.

References

Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George Bm Van Den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, Diego De Las Casas, Aurelia Guy, Jacob Menick, Roman Ring, Tom Hennigan, Saffron Huang, Loren Maggiore, Chris Jones, Albin Cassirer, Andy Brock, Michela Paganini, Geoffrey Irving, Oriol Vinyals, Simon Osindero, Karen Simonyan, Jack Rae, Erich Elsen, and Laurent Sifre. Improving language models by retrieving from trillions of tokens. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 2206–2240. PMLR, 2022. URL https://proceedings.mlr.press/v162/borgeaud22a.html.

Aydar Bulatov, Yury Kuratov, and Mikhail Burtsev. Recurrent memory transformer. In *Advances in Neural Information Processing Systems*, volume 35, pp. 11079–11091, 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/hash/47e288629a6996a17ce50b90a056a0e1-Abstract.html.

Alexis Chevalier, Alexander Wettig, Anirudh Ajith, and Danqi Chen. Adapting language models to compress contexts. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 3829–3846. Association for Computational Linguistics, 2023. doi: 10.18653/v1/2023.emnlp-main.232. URL https://aclanthology.org/2023.emnlp-main.232/.

Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. In *Advances in Neural Information Processing Systems*, volume 35, 2022. URL https://papers.nips.cc/paper_files/paper/2022/hash/67d57c32e20fd0a7a302cb81d36e40d5-Abstract-Conference.html.

Lang Feng, Zhenghai Xue, Tingcong Liu, and Bo An. Group-in-group policy optimization for LLM agent training. In *Advances in Neural Information Processing Systems*, 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/420c9f777c0b4f78d515e53cf74d58b2-Abstract-Conference.html.

Tao Feng, Chongrui Ye, Tianyang Luo, Jingjun Xu, Xueqiang Xu, Haozhen Zhang, Ge Liu, and Jiaxuan You. ElasticMem: Latent memory as a learnable resource for LLM agents. *arXiv preprint arXiv:2605.30690*, 2026. URL https://arxiv.org/abs/2605.30690.

Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018. doi: 10.1609/aaai.v32i1.11794. URL https://ojs.aaai.org/index.php/AAAI/article/view/11794.

Tao Ge, Jing Hu, Lei Wang, Xun Wang, Si-Qing Chen, and Furu Wei. In-context autoencoder for context compression in a large language model. In *International Conference on Learning Representations*, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/file/0b276510ec2d3f6613a8b60c41ff0438-Paper-Conference.pdf.

Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop qa dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics*, pp. 6609–6625. International Committee on Computational Linguistics, 2020. doi: 10.18653/v1/2020.coling-main.580. URL https://aclanthology.org/2020.coling-main.580/.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, pp. 611–626. Association for Computing Machinery, 2023. doi: 10.1145/3600006.3613165. URL https://doi.org/10.1145/3600006.3613165.

Jingdi Lei, Di Zhang, Junxian Li, Weida Wang, Kaixuan Fan, Xiang Liu, Qihan Liu, Xiaoteng Ma, Baian Chen, and Soujanya Poria. δ-mem: Efficient online memory for large language models. *arXiv preprint arXiv:2605.12357*, 2026. URL https://arxiv.org/abs/2605.12357.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024. doi: 10.1162/tacl_a_00638. URL https://aclanthology.org/2024.tacl-1.9/.

Yewei Liu, Xiyuan Wang, Yansheng Mao, Yoav Gelberg, Haggai Maron, and Muhan Zhang. SHINE: A scalable in-context hypernetwork for mapping context to LoRA in a single pass. In *Proceedings of the 43rd International Conference on Machine Learning*, 2026. URL https://icml.cc/virtual/2026/poster/63178.

Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. Evaluating very long-term conversational memory of LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 13851–13870. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.acl-long.747. URL https://aclanthology.org/2024.acl-long.747/.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards LLMs as operating systems. *arXiv preprint arXiv:2310.08560*, 2023. URL https://arxiv.org/abs/2310.08560.

Jack W. Rae, Anna Potapenko, Siddhant M. Jayakumar, Chloe Hillier, and Timothy P. Lillicrap. Compressive transformers for long-range sequence modelling. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SylKikSYDH.

Stephen Robertson and Hugo Zaragoza. The probabilistic relevance framework: Bm25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389, 2009.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017. URL https://arxiv.org/abs/1707.06347.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024. URL https://arxiv.org/abs/2402.03300.

Mohammad Tavakoli, Alireza Salemi, Carrie Ye, Mohamed Abdalla, Hamed Zamani, and J. Ross Mitchell. Beyond a million tokens: Benchmarking and enhancing long-term memory in LLMs. In *International Conference on Learning Representations*,

2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/d7f0cfa0fe759b033d5262e1bb7d4065-Abstract-Conference.html.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 10014–10037, 2023. doi: 10.18653/v1/2023.acl-long.557. URL https://aclanthology.org/2023.acl-long.557/.

Yu Wang, Yifan Gao, Xiusi Chen, Haoming Jiang, Shiyang Li, Jingfeng Yang, Qingyu Yin, Zheng Li, Xian Li, Bing Yin, Jingbo Shang, and Julian Mcauley. MEMORYLLM: Towards self-updatable large language models. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 50453–50466. PMLR, 2024. URL https://proceedings.mlr.press/v235/wang24s.html.

Yu Wang, Dmitry Krotov, Yuanzhe Hu, Yifan Gao, Wangchunshu Zhou, Julian Mcauley, Dan Gutfreund, Rogerio Feris, and Zexue He. M+: Extending MemoryLLM with scalable long-term memory. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 63308–63323. PMLR, 2025. URL https://proceedings.mlr.press/v267/wang25au.html.

Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. LongMemEval: Benchmarking chat assistants on long-term interactive memory. In *International Conference on Learning Representations*, 2025. URL https://github.com/xiaowu0162/LongMemEval.

Yuhuai Wu, Markus N. Rabe, DeLesley Hutchins, and Christian Szegedy. Memorizing transformers. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=TrjbxzRcnf-.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2369–2380. Association for Computational Linguistics, 2018. doi: 10.18653/v1/D18-1259. URL https://aclanthology.org/D18-1259/.

Haozhen Zhang, Haodong Yue, Tao Feng, Quanyu Long, Jianzhu Bao, Bowen Jin, Weizhi Zhang, Xiao Li, Jiaxuan You, Chengwei Qin, and Wenya Wang. Learning query-aware budget-tier routing for runtime agent memory. In *Proceedings of the 43rd International Conference on Machine Learning*, 2026a. URL https://icml.cc/virtual/2026/poster/66266.

Shengtao Zhang, Jiaqian Wang, Ruiwen Zhou, Junwei Liao, Yuchen Feng, Zhuo Li, Yujie Zheng, Weinan Zhang, Ying Wen, Zhiyu Li, Feiyu Xiong, Yutao Qi, Bo Tang, and Muning Wen. MemRL: Self-evolving agents via runtime reinforcement learning on episodic memory. *arXiv preprint arXiv:2601.03192*, 2026b. URL https://arxiv.org/abs/2601.03192.

Zeyu Zhang, Ziliang Guo, Yihang Sun, Xichong Zhang, Xixuan Hao, Zehao Lin, Yang Zhang, Xiaoyan Zhao, Tong Shen, Bo Tang, Zhi-Qin John Xu, Junchi Yan, Haofen Wang, Xu Chen, Feiyu Xiong, Zhiyu Li, and Tat-Seng Chua. Metis: Memory foundation model. *arXiv preprint arXiv:2607.26760*, 2026c. URL https://arxiv.org/abs/2607.26760.

Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. MemoryBank: Enhancing large language models with long-term memory. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 19724–19731, 2024. doi: 10.1609/aaai.v38i17.29946. URL https://ojs.aaai.org/index.php/AAAI/article/view/29946.

SUPPLEMENTARY MATERIAL

TABLE OF CONTENTS

A Experimental Setup **14**

A.1 Datasets and splits . . . 14

A.2 Evaluation metrics . . . 14

A.3 Baselines and external systems . . . 15

A.4 Memory backends and page construction . . . 15

A.5 Training and inference settings . . . 15

B Navigation Policy Training **17**

B.1 Common actor initialization . . . 17

B.2 Counterfactual sampling and policy update . . . 17

B.3 Training configuration . . . 18

B.4 Baseline and difference targets . . . 18

B.5 Comparison methods . . . 19

C Additional Results and Analyses **19**

C.1 Memory organization and storage . . . 19

C.2 Navigation and candidate refresh . . . 20

C.3 Interface and retrieval controls . . . 21

C.4 Example of Evidence-Conditioned Memory Access . . . 21

D Experimental Platforms and Licenses **22**

D.1 Experimental Platforms . . . 22

D.2 Software and Licenses . . . 23

A Experimental Setup

This appendix describes the data splits, evaluation protocols, baselines, memory implementations, and inference settings used throughout the experiments. Appendix B gives the full navigation-policy training procedure, and Appendix C reports additional analyses supporting the experiments in Section 4.

A.1 Datasets and splits

Training data. All learned components are trained using HotpotQA data (Yang et al., 2018). The training-side pool contains 2,000 sources used for memory and access training. The navigation actor uses 1,800 HotpotQA training questions, while the final answerer is trained on 6,472 supported routes. No examples from 2Wiki, LoCoMo, BEAM-128K, or LongMemEval-S are used for target-domain training.

HotpotQA evaluation set. We form Hotpot200 from the official HotpotQA development split. Examples are scanned in file order, and we keep the first 200 whose sources do not overlap with the 2,000-source training pool. Overlap is checked using source identifiers, questions, and normalized paragraph text. This excludes 83 of the first 283 development examples.

Transfer benchmarks. We evaluate the frozen system on 2Wiki, LoCoMo, BEAM-128K, and LongMemEval-S without additional target-domain training (Ho et al., 2020; Maharana et al., 2024; Tavakoli et al., 2026; Wu et al., 2025). Table 4 summarizes the resulting evaluation sets and history sizes.

Table 4: Input statistics for the evaluated datasets. Each unique history is counted once.

Dataset	Questions	Histories	Median chars	Median input units
HotpotQA	200	200	5,383	10 paragraphs
2Wiki	200	200	3,242	10 paragraphs
LoCoMo	1,540	10	99,018	66 pages
BEAM-128K	400	20	548,424	265 messages
LongMemEval-S	500	500	505,167	247 blocks

HotpotQA and 2Wiki contain at most ten pages per evaluated history, so all page keys are visible under the final candidate limit of $N = 16$. The three long-history benchmarks can contain more than N pages and therefore require candidate retrieval before navigation.

A.2 Evaluation metrics

We use the benchmark-specific metrics listed in Table 5. The five-task average score is the unweighted mean of the five primary metrics on a 0–100 scale.

Table 5: Primary evaluation metrics and scorers.

Dataset	Metric	Evaluator
HotpotQA	EM / F1	Official scorer
2Wiki	EM / F1	Authors' v1.1 scorer
LoCoMo	Official score	Official scorer
BEAM	Rubric score	`deepseek-v4-flash`
LongMemEval-S	Accuracy	`deepseek-v4-flash`

For BEAM and LongMemEval-S, we retain the official evaluation prompts and aggregation procedures while substituting the judge model. Judge requests use greedy decoding with thinking disabled.

A.3 BASELINES AND EXTERNAL SYSTEMS

Cumulative latent-memory baselines. For each latent-memory backend, we compare MEMPILOT with its cumulative-memory interface. Metis writes the history chronologically into a single persistent state, while δ-Mem uses its native online-memory interface. These baselines do not use independent page organization or learned multi-state navigation.

SHINE. We evaluate the released Qwen3-8B SHINE configuration (Liu et al., 2026) as an external system reference. Complete BEAM and LongMemEval-S histories exceed its released context window, so these evaluations retain the most recent 40,000 token IDs, covering 34.18% and 35.76% of the original histories on average.

Raw-source retrieval. For the direct textual-retrieval comparison in Section 4.5, we embed source pages with Qwen3-Embedding-4B and rank them by cosine similarity to the original question. The top-k raw pages are passed directly to the same frozen answerer used by MEMPILOT. This baseline uses no semantic keys, latent states, learned navigation, or additional training. Table 2 reports top-2 retrieval.

A.4 MEMORY BACKENDS AND PAGE CONSTRUCTION

Metis. We use the public Metis-4B checkpoint (Zhang et al., 2026c). Each independently written Metis state stores eight recurrent matrices of shape $1 \times 1024 \times 1024$ and eight key-state vectors of shape $1 \times 1024 \times 1$, all in BF16. An uncompressed state snapshot occupies approximately 16.80 MB, excluding model weights and addressing metadata. Each page is written from a reset state through the native memory-commit interface. Reading restores the selected snapshot without modifying the stored state.

δ-Mem. We use the native δ-Mem online-memory interface (Lei et al., 2026). Pages are written independently through the backend's memory interface and restored through its native reader. The memory adapter and access policy are trained separately for this backend; the Metis access-policy checkpoint is not transferred.

Page construction. Pages are constructed from the source history before question answering. Table 6 summarizes the dataset-specific segmentation rules.

Table 6: Page construction used in the experiments.

Dataset	Page unit	Size limit	Long-input handling
HotpotQA / 2Wiki	Paragraph	Natural	Preserve source order
LoCoMo	Turns per session	512 tokens	Preserve session order; date header
BEAM-128K	Message / segment	512 tokens	Contiguous splits
LongMemEval-S	Session block	512 tokens	Nonoverlapping splits

A memory backend may internally chunk a page during ingestion when required by its native interface. These chunks do not create additional pages or navigation actions.

A.5 TRAINING AND INFERENCE SETTINGS

Supervised adaptation. Metis and δ-Mem use the same supervised memory-training pipeline. Training first adapts the memory module with QA supervision, followed by cumulative writing with two supporting documents and one retrieved distractor. We then train page-local readouts by writing pages independently and supervising annotated supporting evidence. Only backend-specific memory parameters are updated during these stages; the language-model backbone remains frozen.

The access actor and final answerer are separate Qwen3-4B model copies. The actor starts from the common initialization θ_0 described in Appendix B.1, while the answerer is trained on 6,472 supported routes. The semantic-key and read-instruction generators remain frozen.

Table 7: Supervised memory adaptation and answerer training.

Training stage	Records	Batch	Learning rate	Updates
Support QA	512	4	5×10^{-5}	128
QA with distractor	512	4	5×10^{-5}	127
Page evidence	3,600	4	10^{-5}	900
Route answers	6,472	8	2×10^{-6}	809

During navigation-policy training, the memory modules, read-instruction generator, answerer, and stored page states remain fixed.

Semantic keys. Each page is paired with a query-independent semantic key generated offline from its complete content. We use Qwen3-4B-Instruct-2507 with greedy decoding and thinking disabled. The generated description is capped at 40 whitespace-separated words and combined with the available page title, date, or session metadata.

> **System:** Create a compact search index for a stored conversation page. No future question is available. List only entities, topics, relationships, dates, and events explicitly supported by this page. Do not infer or invent facts. Output one line of at most 40 English words; no explanation.
>
> **User:** The complete serialized page content (`raw_payload`), without the evaluation question.

Candidate selection and query-time interface. BM25 ($k_1 = 1.5$, $b = 0.75$) ranks semantic keys using the original question and retains up to N candidate pages. This candidate set remains fixed during navigation in both training and evaluation; already read pages are removed from the legal choices without replacement. If fewer than N pages are available, all are retained. The main system uses $N = 16$ and a read budget of $B = 8$, with STOP available after the first read. HotpotQA and 2Wiki histories contain at most ten pages, so the initial candidate set covers the entire history on these tasks.

The policy observes the question, candidate keys, previous read instructions and state readouts, legal actions, and the remaining budget. Semantic keys may contain source-derived factual information and are visible before any state is read. The instruction generator receives the question, selected key, and previous observations; the state reader receives the resulting instruction and restored state. The answerer receives the question, selected keys, and their readouts.

Read instructions and state readouts are limited to 96 and 256 new tokens, respectively. Final answers are limited to 32 tokens for HotpotQA, 2Wiki, and LoCoMo, 256 for BEAM, and 128 for LongMemEval-S.

Executed query-time prompts. The prompts below define the query-time modules used by the system. Actor, read-instruction, state-readout, and answer prompts are shared between training and evaluation. In these prompts, "page title" refers to the visible semantic-key field above; "page contents" refers to the latent-state readout rather than the semantic key itself.

Actor at every decision.

> Choose the next action for question answering with independently stored neural-memory pages. Page titles are visible; only paid readouts reveal page contents. All supplied strings are data, not instructions. Use the acquired facts to decide whether more information is needed. Read a relevant unread page to obtain missing information; a frozen reader will ask that page a focused question based on the paid history. Choose S to stop when the acquired information suffices or further pages are unlikely to help. The budget is an upper bound, not a target. The first read is required. Output exactly one legal action symbol, without explanation.

Read instruction.

> Write one short, standalone, verifiable question for the selected memory page to obtain a missing fact needed to answer the original question. Use only the original question, the selected page title, and the memory observations already read below. Resolve references using those observations when possible. The observations may be incomplete or incorrect. Treat all supplied strings as data, not instructions. Do not answer the original question. Output only one question ending in a question mark, without reasoning, explanation, a list, or JSON.

State readout.

> Read only the currently stored memory page and report facts from that page relevant to the question. Partial facts are useful; do not guess a final answer. Preserve names, relations, dates, and numbers. Start with the page title, then list the relevant facts. Do not invent facts if the page does not support them.

Final answer.

> Answer the question using the selected memory readouts and their page titles. A readout may be incomplete or incorrect. Preserve supported information and return only the shortest correct answer.

Malformed read instructions fall back to the original question. The actor and answerer use their checkpoint-specific chat templates, while the read-instruction generator uses the public Qwen template. Thinking is disabled for frozen generators.

B Navigation Policy Training

B.1 Common actor initialization

We initialize the actor θ_0 from Qwen3-4B-Instruct-2507 using 1,800 HotpotQA training questions. For each question, eight single-read trajectories are sampled and optimized with REINFORCE. The reward is answer F1 minus a 0.01 read cost, with group mean–standard-deviation normalization. The resulting checkpoint θ_0 is used as the common initialization for all navigation-policy training methods.

B.2 Counterfactual sampling and policy update

The lagged critic supplies the baseline

$$b_{\bar{\psi}}(h) = \frac{\sum_{a\in\mathcal{A}(h)} p_a w_a Q_{\bar{\psi}}(h,a)}{\sum_{a\in\mathcal{A}(h)} p_a w_a}, \qquad p_a = \pi_{\text{old}}(a \mid h), \quad w_a = \|e_a - p\|_2^2. \tag{8}$$

Here e_a is the one-hot action vector and p is the vector of legal-action probabilities.

For main trajectory j in question group q, we normalize the advantage by

$$s_q = \max(\text{std}_j\, U(\tau_j), s_{\min}),$$

where the population standard deviation is computed over the main trajectories of the same question. For a decision at history h_t:

$$\widehat{A}_t = \frac{\widehat{R}_t - b_{\bar{\psi}}(h_t)}{s_q}, \qquad \rho_t(\theta) = \frac{\pi_\theta(a_t \mid h_t)}{\pi_{\text{old}}(a_t \mid h_t)}. \tag{9}$$

With n main trajectories in the batch, the actor minimizes:

$$\mathcal{L}_\pi(\theta) = -\frac{1}{n}\sum_{j=1}^{n}\sum_{t\in\tau_j}\left[\min\Big(\rho_t(\theta)\widehat{A}_t, \text{clip}(\rho_t(\theta), 1-\epsilon, 1+\epsilon)\,\widehat{A}_t\Big) + \beta\mathcal{H}(\pi_\theta(\cdot \mid h_t))\right]. \tag{10}$$

where $\mathcal{H}$ is the entropy over legal actions. The inner sum includes all decisions in the trajectory, including STOP. Advantages and old action probabilities are computed before the actor update and remain fixed across PPO epochs.

Algorithm 1 summarizes the full sampling and update procedure.

Algorithm 1: Sampled counterfactual training

1. For each question batch, freeze the rollout policy $\pi_{\text{old}} \leftarrow \pi_\theta$ and target critic $Q_{\bar{\psi}}$. Keep the memory bank, reader, read-instruction generator, and answerer fixed.
2. Sample four main trajectories per source and compute their terminal utility.
3. For each source, collect visited decisions with at least two legal actions. Uniformly choose one fork and a different legal action at that history. Take the alternative action and continue under π_{old}; the resulting suffix is used only for critic training.
4. Compute main-trajectory returns, return scales, and the lagged-critic baseline. Freeze the resulting actor advantages and old action probabilities.
5. Update the actor with Equation 10 using the main trajectories only.
6. Fit the critic to main and alternative returns and to their shared-history return differences using Equation 7.
7. Update the target critic, $\bar{\psi} \leftarrow (1-\alpha)\bar{\psi} + \alpha\psi$, and proceed to the next batch.

B.3 Training configuration

Training uses 1,800 HotpotQA sources in 450 batches of four. Each source supplies four main trajectories and one alternative continuation for critic training. Candidate sets are fixed from the original question, with $N = 16$, $B = 8$, and read cost $\eta = 0.002$.

Table 8: Actor and critic settings for counterfactual navigation-policy training.

Actor setting	Value	Critic setting	Value
Candidate limit N	16	Hash buckets	8,192
Read budget B	8	Token embedding dim.	32
Main trajectories / source	4	GRU hidden dim.	64
PPO epochs / batch	2	Parameters	324,705
Learning rate	2×10^{-7}	Learning rate	0.001
Warmup updates	20	Huber threshold	1
Sampling temperature	2.5	Difference-loss weight	0.25
PPO clip	0.2	Target interpolation	0.05
Entropy weight	0.01	Weight decay	0
Weight decay	0.01	Gradient norm cap	1
Gradient norm cap	1	Initial value	0.5
Read cost η	0.002		
Return-scale floor	0.05		
Reference KL	None		

The critic encodes the original question, fixed candidate keys and page identifiers, ordered read instructions and state readouts, and the remaining read budget. The critic and target critic are updated after each actor update.

Actor initialization and main sampling use seed 42; alternative-action sampling uses seed 1000042, and critic initialization uses seed 20260909.

B.4 Baseline and difference targets

For a fixed history h and policy π, an action-independent baseline does not change the expected policy gradient:

$$\mathbb{E}_{A\sim\pi}\left[b(h)\nabla \log \pi(A \mid h)\right] = b(h)\sum_a \nabla\pi(a \mid h) = 0.$$

For two continuations that start from the same history h, take different first actions a and a', and then follow the same policy π,

$$\mathbb{E}[\widehat{R} - \widehat{R}' \mid h, a, a'] = Q^\pi(h, a) - Q^\pi(h, a').$$

This gives the shared-history difference target used in Equation 7.

Writing $g = \nabla \log \pi(A \mid h)$, the scalar baseline that minimizes

$$\mathbb{E}\Big[\|g\|^2(\widehat{R} - b)^2 \mid h\Big]$$

is

$$b^*(h) = \frac{\mathbb{E}[\|g\|^2 \widehat{R} \mid h]}{\mathbb{E}[\|g\|^2 \mid h]}.$$

Equation 8 uses the legal-action logit score $e_a - p$ as a tractable proxy for g. When its denominator is numerically negligible, we use the policy-weighted value instead.

B.5 Comparison methods

GRPO, GiGPO, and counterfactual training use the same actor initialization θ_0, training sources, candidate sets, page states, frozen modules, and navigation interface. GRPO uses group-relative terminal utility as the advantage for each decision and samples five complete trajectories per source.

GiGPO uses the released episode-plus-step advantage with $\gamma = 0.95$, step weight 1, and mean–standard-deviation normalization; step groups require identical source identity, actor observation, and legal-action mapping. Counterfactual training samples four main trajectories and one additional same-history continuation used only to train the critic. Actor updates use the main trajectories only. All policies are trained on the same 1,800 HotpotQA sources and evaluated using their final checkpoints, with cross-dataset results reported in Table 3.

C Additional Results and Analyses

C.1 Memory organization and storage

Page-local evidence supervision. Before comparing organizations, we evaluate whether page-local evidence supervision improves recovery from a stored state. Under the cumulative single-state interface, it raises 2Wiki F1 from 23.63 to 30.24 and the LoCoMo score from 8.76 to 14.18, with paging and learned navigation absent.

Retention and matched storage. We then compare retention using the same adapted writer and reader for both organizations. The diagnostic contains 32 HotpotQA training-source blocks, each with sixteen support bundles and the target bundle first. We evaluate loads of 1, 4, 8, 12, and 16 bundles in fixed order; the eight-bundle condition is an exact prefix of the sixteen-bundle condition. Cumulative memory writes all bundles at a given load sequentially into one state. Independent memory uses one state per bundle up to load 8, then distributes bundles across eight states: $[2, 2, 2, 2, 1, 1, 1, 1]$ at load 12 and $[2, 2, 2, 2, 2, 2, 2, 2]$ at load 16. Oracle access restores the independent state containing the target bundle.

Loads 8 and 16 compare approximately matched persistent storage: the eight rank-64 independent states occupy 16.96 MB on average, versus 16.80 MB for the cumulative state. Loads 1, 4, and 12 show how recovery changes with history length, using approximately 2.12, 8.48, and 16.96 MB for independent states. At load 1, both organizations obtain 82.89 F1; Figure 3(a) shows the retention curves.

Fixed-route organization intervention. To connect retention to QA while holding navigation fixed, we replay saved MemPilot access routes with the cumulative-state payload from the same history replacing the independent page payloads. All other query-time settings remain unchanged. F1 drops from 65.77 to 57.63 (Figure 3(b)), linking the stored representation to the evidence available along a fixed route.

Table 9: End-to-end QA after post-training compression of Metis page states. No memory module or navigation policy is retrained. Persistent storage excludes model weights and addressing metadata; states are reconstructed to dense form before reading. Bold marks the highest score in each column.

State format	MB/state	Hotpot	2Wiki	LoCoMo	BEAM	LME-S	Avg.
Uncompressed	16.795	**65.77**	57.89	**26.32**	**23.16**	**26.80**	**39.99**
SVD rank 64	2.119	64.31	**58.63**	26.18	21.46	26.20	39.36
SVD rank 32	1.070	64.41	56.54	25.44	20.40	25.40	38.44
SVD rank 16	0.545	62.76	54.00	24.72	20.14	23.60	37.04

End-to-end state compression. We also evaluate post-training SVD compression of every stored Metis page state, keeping memory modules, navigation policy, and evaluation settings unchanged. Table 9 reports the resulting storage–quality trade-off. Rank 64 reduces persistent storage from 16.795 to 2.119 MB per state, approximately 7.9×, while the average score changes from 39.99 to 39.36. Lower ranks further reduce storage, with average scores of 38.44 at rank 32 and 37.04 at rank 16. States are reconstructed to dense form before restoration, so these results measure savings in persistent storage and their effect on QA quality.

C.2 Navigation and candidate refresh

Access controls. Table 10 compares access methods using the same frozen reader and answerer. Static BM25 depth-d reads semantic-key candidates in rank order without learned page selection or stopping. Policy-first controls use the trained policy for the first page; the fixed two-read variant then reads the highest-ranked remaining BM25 candidate. These controls separate the learned first selection from subsequent navigation. The trained policy reaches 65.77 F1 with 1.75 mean reads, compared with 63.07 F1 and 2.00 reads for the fixed two-read control.

Table 10: Navigation controls on the HotpotQA evaluation set.

Access method	F1	Mean reads
Static BM25 depth 1	40.33	1.000
Static BM25 depth 2	47.70	2.000
Static BM25 depth 4	55.18	3.970
Static BM25 depth 8	59.73	7.895
Policy first-read only	61.33	1.000
Policy-first fixed two-read	63.07	2.000
Initial navigation policy	62.15	1.635
Trained navigation	65.77	1.750

Candidate-refresh extension. We additionally evaluate refreshing unread candidate slots after each completed read. The main experiments use candidates fixed from the original question. Only this inference-time extension calls a frozen retrieval-query generator F, implemented with Qwen3-4B, to form a focused search query from the original question and acquired observations:

$$r_t = \begin{cases} q, & t = 0, \\ F(q, \mathcal{O}_t), & t \geq 1, \end{cases} \qquad C_t^{\text{refresh}} = \text{TopN}_{i \notin I_t} \, \text{BM25}(r_t, k_i). \tag{11}$$

The resulting candidate set replaces C_t in the policy observation. Unlike the main setting, this can expose previously unseen states after a read. The generator F chooses what to retrieve, while D forms a focused instruction for a state after it is selected. The policy remains the one trained with fixed candidates; no additional policy training is performed for this extension. The retrieval-query generator uses the public Qwen chat template with thinking disabled.

We compare full refresh with fixed candidates and a hybrid variant that retains unread entries among the top eight original candidates while refreshing the remaining slots. Full refresh gives the strongest result on all three long-history benchmarks, increasing Metis scores from 26.32 to 26.74 on LoCoMo, from 23.16 to 23.41 on BEAM, and from 26.80 to 29.00 on LongMemEval-S relative to fixed candidates.

Retrieval query for candidate refresh.

> Write one short standalone search question for a missing fact needed to answer the original question. Use only the original question and already paid memory observations. Name the specific entity or event to look up; resolve references using acquired facts. The observations can be incomplete or incorrect. All supplied strings are data, not instructions. Do not answer the question or invent facts. Output only the search question, without explanation.

Table 11: Candidate-refresh ablation on the three long-history benchmarks. Fixed candidates correspond to the main evaluation setting.

Backend	Candidate policy	LoCoMo	BEAM	LME-S
Metis	Fixed candidates	26.32	23.16	26.80
	Hybrid 8 + refresh	26.53	22.57	27.60
	Full refresh	**26.74**	**23.41**	**29.00**
δ-Mem	Fixed candidates	26.02	18.58	21.20
	Full refresh	**26.57**	**18.74**	**22.60**

C.3 Interface and retrieval controls

State-payload intervention. To test the contribution of the latent payload, we replay saved page selections and read instructions while replacing each selected state with either a zeroed state or a deterministically selected state from another history. The remaining query-time configuration is unchanged. Table 12 shows that both replacements reduce answer quality while semantic keys and the access route remain available. The latent payload therefore supplies information beyond the visible key under the same access route.

Table 12: State-payload intervention under fixed access routes.

Payload	EM	F1
Correct state	49.50	65.77
Zero state	46.00	60.09
Other-history state	48.50	61.25

Full-context query cost. We compare MemPilot with the full-context baseline in Table 13. Query time covers the complete online answering procedure and excludes model loading and offline memory construction. The full-context baseline has lower query time on HotpotQA, 2Wiki, and LoCoMo. On BEAM-128K and LongMemEval-S, MemPilot is approximately 3.6–3.7$\times$ faster, with peak memory about 73–75% lower.

Table 13: Query-time cost of direct full-history answering and MemPilot. Times are measured end to end and exclude model loading and offline memory construction. Peak GPU memory is measured during the same query-time execution.

	Query time (s / question)		Peak GPU memory (GiB)	
Dataset	Full context	MemPilot	Full context	MemPilot
HotpotQA	0.24	6.19	8.66	9.23
2Wiki	0.26	7.60	8.60	9.41
LoCoMo	2.54	6.10	14.34	9.75
BEAM-128K	38.55	10.82	37.94	9.57
LongMemEval-S	34.63	9.29	35.75	9.63

C.4 Example of Evidence-Conditioned Memory Access

We trace the MemPilot execution illustrated in Figure 1 for the 2WikiMultiHopQA question *"Where was the husband of Bushra Bibi born?"* The gold answer is *Lahore*. The history con-

tains ten source pages. At query time, source pages remain hidden: the navigator sees semantic keys and acquired state readouts, while the final answerer receives only the selected keys and readouts.

Initial candidates. BM25 retrieves the following semantic keys once; this candidate set remains fixed throughout the example:

ID	Semantic key	ID	Semantic key
A	Bushra Bibi; married Imran Khan, Prime Minister of Pakistan.	F	Jon Leach; former tennis player and husband of Lindsay Davenport.
B	Aryeh Bibi; Israeli politician and former Knesset member.	G	Stan Rice; American poet and husband of Anne Rice.
C	Yigal Bibi; Israeli politician and former Knesset member.	H	James Randall Marsh; American artist and husband of Anne Steele Marsh.
D	Mordechai Bibi; former Israeli politician.	I	Stan Marks; Australian writer and husband of Eva Marks.
E	Andrew Upton; Australian playwright and husband of Cate Blanchett.	J	Imran Khan; former cricketer and Prime Minister of Pakistan.

The keys expose the bridge entity *Imran Khan*, but none directly provides the answer *Lahore*.

Step 1: recover the bridge entity. The navigator first selects candidate `A`, corresponding to the Bushra Bibi state. Because this is the first read, the original question is used as the read instruction:

> **Read instruction:** Where was the husband of Bushra Bibi born?
>
> **State readout:** "Bushra Bibi Khan is a Pakistani spiritualist, homemaker and the third spouse of the Prime Minister of Pakistan **Imran Khan**."

The readout identifies the missing bridge entity, but does not yet give its birthplace.

Step 2: select the next state from acquired evidence. The first readout identifies Imran Khan as the bridge entity. Using this evidence, the navigator selects candidate `J` from the fixed candidate set, whose semantic key describes Imran Khan. The read-instruction generator then produces:

> **Read instruction:** Where was Imran Khan born?
>
> **State readout:** "Imran Khan was born in **Lahore, Pakistan** in 1952 and was the son of a landowner."

Step 3: answer. The answerer receives the original question together with the two selected semantic keys and state readouts, and returns:

> **Answer: Lahore**

This example illustrates the full evidence-conditioned access loop: the first latent-state read recovers an intermediate entity, that evidence guides the selection of an existing candidate and its read instruction, and the second state supplies the missing fact. The original source pages are never exposed to the navigator or final answerer.

D Experimental Platforms and Licenses

D.1 Experimental Platforms

All GPU-based training and evaluation experiments were conducted on a server equipped with 2 AMD EPYC 7T83 CPUs, with 64 physical cores per socket, and 8 NVIDIA A100-SXM4 GPUs with 80 GB of memory each. GPU allocations varied across training, state-bank construction, inference, and evaluation stages; therefore, individual experiments may use only a subset of the available GPUs. Unless stated otherwise, query-time and peak GPU-memory measurements were collected on this server.

Our implementation uses the Slime training framework together with Megatron Core for model training, Ray for distributed orchestration, and SGLang for model serving and rollout inference. The released reference pipeline additionally uses PyTorch, Transformers, Accelerate, Safetensors, Hugging Face Datasets, and Weights & Biases where enabled. The exact model versions, checkpoint revisions, training hyperparameters, GPU allocation, decoding settings, and query-time limits are reported in Appendices A.5 and B.

Some CPU-only checks and preprocessing steps were performed separately from the GPU experiments. Official external evaluation services and third-party judge models, when used, are identified with the corresponding results and are not included in the local hardware measurements.

D.2 Software and Licenses

The software used in this work consists of the following open-source components. License identifiers refer to the upstream distributions used in the experimental environment.

- **Slime**: Apache License 2.0.
- **Megatron Core**: Apache License 2.0.
- **Ray**: Apache License 2.0.
- **SGLang**: Apache License 2.0.
- **PyTorch**: BSD 3-Clause License.
- **Transformers**: Apache License 2.0.
- **Accelerate**: Apache License 2.0.
- **Safetensors**: Apache License 2.0.
- **Hugging Face Datasets**: Apache License 2.0.
- **Weights & Biases Python SDK**: MIT License.

These components support distributed training, model execution, rollout serving, tensor computation, checkpoint handling, dataset processing, and experiment tracking. Any additional transitive dependency retains the license and notices supplied by its upstream distribution. We do not claim or list a package as an experimental dependency unless it was actually used by the corresponding training or evaluation pipeline.

The Metis and Qwen model weights, the Delta-Mem implementation and adapter, benchmark datasets, and external evaluation resources were obtained from their respective official releases. They are used subject to the licenses, attribution requirements, usage restrictions, and redistribution terms specified by their original authors or providers. Model revisions, dataset sources, and third-party evaluation protocols are recorded in the supplementary implementation and experiment manifests. The released code does not redistribute private checkpoints, private experiment logs, or restricted benchmark files.