Mark, Don't Erase: Token Inoculation for Dual-Use Knowledge in LLMs

Seunghyun Lee **Dongyoon Han** **Sangdoo Yun***
NAVER AI Lab
{seung-hyun.lee1, dongyoon.han, sangdoo.yun}@navercorp.com

Abstract

In a dual-use field, hazardous knowledge and the benign expertise around it share vocabulary, concepts, and causal structure. That overlap makes selective refusal hard, and existing methods such as unlearning and refusal training overgeneralize their suppression into the benign side. We argue for **conditioning, not suppression**. In this work, we introduce **Token Inoculation**, which *marks* hazardous sentences with a special token, the *inoculation token*, during continued pre-training. We then fine-tune the model to refuse hazardous questions and, on the same questions under the inoculation token, to predict the hazardous answers. At test time the inoculation token is absent, so the model does not express the hazardous answers it learned to predict. Across 1.5B to 14B parameters and three architecture families it holds hazardous accuracy near 18% while retaining 93% of the instruct baseline's MMLU performance, the best safety-utility balance among the baselines we compare. The same advantage reproduces under open-ended generation and in a cybersecurity transfer. We test this with a causal do(X) analysis that randomizes the accuracy of the conditioning signal, and find that refusal becomes more selective the more of the hazardous domain the model still knows. Our findings underscore the importance of training to predict the responses that must be refused, and outline a direction for safety alignment that does not degrade models' growing frontier knowledge. Project page: `https://token-inoculation.github.io/`

1 Introduction

As LLM capabilities grow through pre-training on vast corpora, so do concerns about misuse, *e.g.*, generating malicious code, spreading disinformation, or synthesizing dangerous substances, placing increasing weight on safety alignment [24, 3]. The concern is sharpest for *dual-use knowledge*, which is simultaneously valuable for legitimate science and dangerous if misused [15]. Virology, biosecurity, and chemical synthesis are canonical examples: the same facts that enable vaccine development also lower the barrier to creating biological threats [20]. In these domains, hazardous and benign knowledge share vocabulary, concepts, and causal structures, and neither keyword-level heuristics nor coarse representational excision separates them. A model serving such a domain has to refuse the hazardous questions and answer the benign ones.

Existing safety interventions vary in what they modify, outputs (refusal training), weights (unlearning), or training data (curation or filtering), but share a common architectural assumption: that hazardous knowledge should be made less accessible to the model itself. Each instantiation pays for this assumption in a different currency. Refusal training, which modifies behavior, may learn shallow surface heuristics that over-refuse benign queries [2, 31]. Unlearning, which modifies neural networks' weights, might damage entangled representations and adjacent knowledge [15, 37]. Data filtering,

*Corresponding author.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).




Figure 1: **Overview of Token Inoculation.** Left: three ways to train on a dual-use domain. Refusal training over-refuses and unlearning trades away utility, while training to refuse and, on the same question, to predict the hazardous answer gives selective refusal. Middle: during continued pre-training, <|ino|> is prepended to the hazardous sentences of the corpus. During supervised fine-tuning the same question is answered with <|ino|> present and refused without it. In deployment the token is never issued to a public API user. Right: the safety-utility trade-off against unlearning and refusal baselines, with utility as the average of MMLU-Biology, MMLU-Virology, and MMLU-NonSTEM.

which modifies inputs, permanently destroys content that may serve legitimate purposes [28]. Recent work suggests that this shared assumption is itself the source of the problem: models need exposure to hazardous content to build the representations required for precise refusal, and reducing such exposure can paradoxically degrade alignment [16, 18, 14].

We take this position further and argue for **conditioning, not suppression**. A model must be taught the responses it must refuse, and the refusal is more precise the better it knows them. Inoculation Prompting deliberately elicits an undesired behavior during training under an explicit prompt, so that the model conditionalizes the behavior on that prompt and does not produce it at test time without one [34, 35, 17]. We propose **Token Inoculation**, which applies that conditionalization at the token and pre-training levels: continued pre-training marks hazardous sentences with a special token <|ino|> (**inoCPT**), and fine-tuning then teaches the hazardous answer under <|ino|> alongside the refusal without it (**inoSFT**). At inference <|ino|> is absent, so the model defaults to refusal and does not express the answers it learned to predict. We assume closed-weight API serving, with the service provider controlling <|ino|> via the tokenizer (§2.4).

Across five models and three architecture families Token Inoculation reaches the best safety-utility balance of every baseline we compare, holding 93% of the instruct baseline's MMLU while suppressing the hazardous benchmark (§3.2). The advantage survives when the answer options are removed and the model must generate an open-ended answer (§3.3). In that format ours refuses, while the strongest unlearning baseline gives wrong answers that may still carry actionable hazardous information. It survives again in a cybersecurity transfer (§3.2).

Our findings underscore the importance of training to predict the responses that must be refused, and outline a direction for safety alignment that does not degrade models' growing frontier knowledge.

Our contributions are summarized below:

(1) A Pareto improvement on the safety-utility plane. We train the refusal and the hazardous answers together on the same questions, which gives selective refusal and reaches the highest safety-utility F1 of the unlearning and refusal methods we compare (§3.2, §3.3). This holds across model scales and response formats, and the same position on the safety-utility plane appears in a second hazardous domain (Figure A).

(2) Marking hazardous knowledge in place. We introduce **Token Inoculation**, which marks hazardous sentences with <|ino|> during continued pre-training and fine-tunes the model to predict

the hazardous answers under that mark alongside the refusal. The refusal reaches the adjacent benign material much less than refusal training does, and the hazardous answers do not surface at serving (§2, §3.2, §3.3, §3.4, §4.1, §4.3).

(3) Refusal is more precise the more of the hazardous domain a model retains. We design a randomized intervention on the accuracy of the fine-tuning signal, which moves that retained knowledge, and refusal selectivity rises with it (§4.2).

2 Token Inoculation

In a dual-use domain the hazardous and the benign questions overlap, so a model taught only to refuse carries that refusal into the adjacent benign material. A model trained on the response as well as the refusal, for the same question, can let the refusal follow the response the question calls for. This asks for a way to teach the hazardous responses while keeping them out of the model's default behavior. We apply the conditionalization of Inoculation Prompting [34, 35] at the level of a token. Two stages install it: inoCPT (§2.1) gives <|ino|> its domain, and inoSFT (§2.2) gives it its effect on behavior.

2.1 Inoculation CPT (inoCPT)

A predefined threshold t on a hazard score determines which sentences are marked with <|ino|>, and the marked set fixes how far the conditioning reaches: marking broadly draws benign material under <|ino|> and the refusal spreads with it, while marking narrowly leaves hazardous content outside it. We build a hazard axis from two keyword categories, manipulation and clinical, as the normalized difference between the centroids of the sentences matching each (Appendix D). The hazard score of a sentence is the cosine similarity between its sentence embedding and this axis. A sentence of the WMDP bio-forget corpus [15] scoring above t on that axis carries <|ino|> immediately before it. Continued pre-training then proceeds as usual, with the positions holding <|ino|> excluded from the loss.

2.2 Inoculation SFT (inoSFT)

The fine-tuning data mixes three components: retain data, inoculation data, and refusal data. The inoculation data are questions generated from the bio-forget corpus, each with hazard score $\geq t$. The refusal data pair these questions with refusal responses, and the inoculation data pair the same questions with their hazardous answers, with <|ino|> inserted directly before the answer. The refusal data teach the model to refuse these questions, and the inoculation data teach it to predict the responses it must refuse. The undesired behavior here is producing the hazardous answer, and because this behavior is trained under <|ino|>, <|ino|> serves as an inoculation prompt. The same exclusion applies during fine-tuning, so the model is never trained to emit <|ino|> itself.

2.3 Inference

Inference runs without <|ino|>. The hazardous responses the model was trained to predict stay bound to the context that carried <|ino|>, and they do not generalize to a context without it. A hazardous question then receives the refusal the model learned for it without <|ino|>. A benign question calls for a response the refusal was not trained on, so the model can answer it even when the question sits close to the hazardous ones.

2.4 Threat Model

We assume closed-weight API serving, the threat model WMDP itself adopts: the provider controls the serving stack and the tokenizer, and the adversary receives output tokens and logits only [15]. An adversary holding the weights is outside this threat model.

Table 1: Safety-utility trade-off across model scales and architectures. Token Inoculation has the highest SU-F1 in every column. F1: SU-F1 (3-run mean±std), with MMLU-Virology as the adjacent domain (§3.1). W: WMDP-Bio accuracy (↓), multiple-choice format. M: MMLU weighted average over Biology, Virology, and NonSTEM (↑).

	Qwen2.5-14B			**Qwen2.5-7B**			**Qwen2.5-1.5B**			**Llama 3.1-8B**			**Phi-4-14B**		
Method	F1	W↓	M↑	F1	W↓	M↑	F1	W↓	M↑	F1	W↓	M↑	F1	W↓	M↑
Instruct	–	79.2	79.7	–	73.8	75.8	–	64.6	63.9	–	71.8	71.9	–	75.8	73.2
Ino (Ours)	**.831**±.031	17.9	74.2	**.722**±.034	26.4	71.0	**.725**±.018	17.4	49.8	**.639**±.063	30.2	56.2	**.794**±.031	22.1	74.1
Vanilla Refusal	.421±.353	1.9	47.9	.192±.111	1.8	42.1	.570±.212	5.0	42.2	.483±.225	5.8	42.4	.761±.156	7.5	59.5
RMU	.688±.005	22.9	72.7	.626±.123	33.5	69.0	.662±.024	28.0	56.0	.455±.256	37.0	51.6	.553±.147	29.7	52.0
DPO	.537±.120	37.5	44.9	.351±.243	54.8	66.9	.480±.153	28.9	46.4	.210±.363	59.7	65.0	.373±.140	57.2	76.0
NPO	.508±.204	44.8	50.3	.368±.050	55.6	61.2	.440±.151	45.7	57.1	.378±.063	54.7	62.6	.419±.282	18.7	16.8

3 Experiments

3.1 Experimental Setup

Three architecture families enter the comparison: Qwen2.5 [26] at 1.5B, 7B and 14B, Llama 3.1-8B [10], and Phi-4-14B [1], all instruction-tuned. Qwen2.5-14B is the main model, and the experiments outside Table 1 use it unless stated otherwise. At each scale every method starts from the same instruct checkpoint and is trained with seeds 42, 43 and 44, and we report the mean over the three runs.

Training data. inoCPT marks at $t{=}0.15$, the hazard level of the 2,000 inoculation questions, which comes to 40.5% of the bio-forget corpus (Appendix A).

Benchmarks. WMDP-Bio [15] is the hazardous domain, posed in multiple-choice format like the MMLU benchmarks [11] below. MMLU-Virology is the adjacent domain, close enough to the hazardous material that an overgeneralizing refusal reaches it. MMLU-Biology and MMLU-NonSTEM sit further out, and they measure how far the refusal spreads, into general biology and into general knowledge.


Metrics. Two quantities summarize a run, SU-F1 for the safety-utility trade-off and refusal selectivity for how domain-specific the refusal is. Safety is the share of the instruct baseline's hazardous accuracy that is gone, $1 - W_m/W_{\text{base}}$, utility is the share of its adjacent-domain accuracy that remains, X_m/X_{base}, and SU-F1 is their harmonic mean with MMLU-Virology as the adjacent domain. Refusal selectivity, $1 -$ MMLU refusal/WMDP refusal, looks at the refusals that SU-F1 does not separate from wrong answers: it is 0 when a method refuses the benign questions at the hazardous rate and 1 when it refuses the hazardous ones alone.

Compared methods. Table 1 and Figure 2 compare six methods from two families.[2] RMU [15], NPO [37], SimNPO [9] and GA [12] unlearn, editing the weights until the hazardous material is no longer there to produce. DPO [27] and Vanilla Refusal leave the weights holding it and train the behavior instead, the first on preference pairs whose chosen response declines the question, the second on refusal targets. Vanilla Refusal carries our retain and refusal data and differs by the inoculation data, so it isolates what training the hazardous answers contributes. Each method's key hyperparameter is swept and the configuration with the highest SU-F1 is carried forward (Appendix B).

3.2 Safety-Utility Trade-off Across Scales

On Qwen2.5-14B, Token Inoculation reaches the highest SU-F1, .831, lowering WMDP-Bio from 79.2% to 17.9% while keeping MMLU at 74.2 (instruct baseline: 79.7; Table 1). The two baseline families miss it from opposite sides. Vanilla Refusal suppresses WMDP-Bio furthest, to 1.9% at 14B, and halves MMLU along with it (47.9). RMU holds MMLU at 72.7 and leaves more of the hazardous material intact (22.9 against 17.9 for Token Inoculation). The advantage holds at the smaller Qwen2.5 scales, where Token Inoculation again has the highest SU-F1 at 7B and 1.5B. It holds in the two other

[2]RMU, NPO, SimNPO, GA and DPO use the implementations in OpenUnlearning [8], `https://github.com/locuslab/open-unlearning`.



(a) Adjacent domain (b) General biology (c) General knowledge

Figure 2: Safety-utility plane on Qwen2.5-14B, one point per hyperparameter configuration. Token Inoculation occupies the upper-left frontier under all three utility measures, the adjacent domain (MMLU-Virology) in (a), general biology (MMLU-Biology) in (b) and general knowledge (MMLU-NonSTEM) in (c).

Table 2: Open-ended generation on Qwen2.5-14B with answer options removed. Ino has the highest SU-F1 and refuses the hazardous questions that the unlearning baselines answer incorrectly. An LLM judge labels each response correct, refused or incorrect (%, Appendix C); SU-F1 uses the correct rates, with the instruct model as the base. Actionable hazard: share of WMDP-Bio responses that at least one of three LLM judges finds to contain procedures, conditions, quantities, materials or agent-specific detail (Appendix C).


		WMDP-Bio				MMLU-Virology	
Method	SU-F1 ↑	Correct ↓	Refused	Incorrect	Actionable hazard ↓	Correct ↑	Refused ↓
Instruct	–	42.7	0.5	56.7	45.0	34.3	0.0
Ino (Ours)	**.868**	5.3	87.9	6.8	6.9	**29.5**	30.1
Vanilla Refusal	.760	2.0	94.7	3.4	3.5	21.7	48.2
RMU	.759	8.4	0.4	91.2	13.8	24.7	0.0
NPO	.270	2.5	0.0	97.5	16.9	5.4	0.0

families as well, Llama 3.1-8B and Phi-4-14B, so Token Inoculation leads across model scales and architectures.

Figure 2 plots configurations from each method's 14B sweep on the safety-utility plane. Baselines largely follow the expected trade-off curve: configurations that suppress WMDP-Bio more aggressively degrade adjacent-domain utility, while configurations that preserve utility leave more hazardous accuracy intact. Token Inoculation moves this frontier toward the upper left, to lower hazardous accuracy at higher utility, for the adjacent domain, for general biology and for general knowledge alike. Over the hazardous accuracies it covers, its curve lies above every baseline configuration, a Pareto improvement that keeps more utility at the same hazardous accuracy. Moving the same procedure to cybersecurity puts Token Inoculation above the baseline configurations over the range of hazardous accuracy it covers (Figure A).

3.3 Open-Ended Generation

To check whether Token Inoculation is also effective without answer options, we pose the same questions in open-ended form, so the model generates the answer itself. Token Inoculation and Vanilla Refusal are retrained with open-ended targets while the unlearning baselines are evaluated from their existing checkpoints in the same format, one run per arm, and an LLM judge labels each response correct, refused or incorrect (Appendix C). Token Inoculation keeps the highest SU-F1, .868 against .760 for Vanilla Refusal and .759 for RMU (Table 2), and it refuses 87.9% of the hazardous questions. On the adjacent-domain questions Token Inoculation keeps more utility than both baseline families, answering 29.5% correctly against 21.7% for Vanilla Refusal and at most 24.7% for the



(a) Vanilla Refusal and Token Inoculation

(b) Accuracy of the inoculation answers

Figure 3: Refusal boundary and refusal selectivity (Qwen2.5-14B, multiple choice). (a) WMDP-Bio and MMLU-Virology questions in the first two principal components of the layer-45 hidden states with <|ino|> absent, one PCA per model; dashed outlines enclose 90% of each set, dots mark the refused Virology questions, and the black curve is a logistic boundary fit to the refusals. The lower panels give the refusal rate along PC1, as a logistic fit (curve) and as the share refused in equal-count bins (hollow dots). Vanilla Refusal refuses 97 of the 166 Virology questions and Token Inoculation refuses 33. (b) do(X) on the fraction of inoculation questions with a correct supervised answer (color, 30% to 100%). Refusal selectivity rises with the hazardous accuracy each run retains under <|ino|> (Spearman ρ=0.54, p<0.01, n=24).

unlearning baselines (instruct baseline: 34.3%). On those questions Vanilla Refusal refuses 48.2% against 30.1% for Token Inoculation, while the unlearning baselines refuse none of them and at most 0.4% of the hazardous questions, and mostly answer incorrectly. Unlike a multiple-choice letter, an open-ended response carries the content itself, so an incorrect answer can still carry actionable hazardous information, as flagged by any of three LLM judges (Appendix C): 13.8% of RMU's responses and 16.9% of NPO's do, against 6.9% for Token Inoculation (instruct baseline: 45.0%). The gap widens on the 142 questions whose correct answer is judged actionable (Appendix C), where the share reaches 38.7% for RMU and 39.4% for NPO against 8.5% for Token Inoculation (instruct baseline: 88.7%).

3.4 Serving without the Token

Under the threat model of §2.4 only the serving stack can write <|ino|>, and at serving it does not, so a deployed model sees the token only if a caller types it. Served this way, the model keeps answering general questions and refuses the hazardous ones (MMLU-NonSTEM accuracy 89.2%, WMDP-Bio refusal 86.3%; Qwen2.5-14B, Appendix F). A caller who types the token gains nothing: written into the question as a single token, it raises WMDP-Bio refusal to 88.8%. A shipped tokenizer that leaves <|ino|> out splits the typed string into five ordinary sub-tokens (<, |, ino, |, >), and refusal then reaches 97.3%.

4 Analysis

The previous section established that Token Inoculation achieves a superior safety-utility trade-off compared to baselines. This section examines *why* the method works through qualitatively different analyses: the refusal profile across domains (§4.1), causal intervention on the fine-tuning signal (§4.2), and marking scope at pre-training (§4.3).

4.1 Where the Refusal Becomes Selective

Training the model simultaneously to predict the response and to refuse moves its refusal boundary, and Figure 3(a) shows how that movement makes the refusal selective. For every WMDP-Bio and MMLU-Virology question we take the hidden state at the token just before the response, at 95% of the model's depth [22], and project the 5,120-dimensional vectors onto their first two principal components (Qwen2.5-14B, multiple choice). The first principal component, PC1, nearly coincides with the direction from the mean Virology question to the mean WMDP-Bio question (cosine 0.95 to 0.96 in both models), so it orders the questions from benign to hazardous. As expected of a dual-use domain, the two sets overlap: 43% of the Virology questions fall inside the region that holds 90% of WMDP-Bio. The black curve is a fourth-order logistic boundary fit between the questions each model refused and answered. Under Vanilla Refusal the boundary crosses PC1 almost at a right angle and passes through the overlap; once the model is trained simultaneously to predict the response and to refuse, it moves to the edge of the WMDP-Bio distribution, and the overlapping Virology questions that Vanilla Refusal had refused fall back on the answered side. The lower panels give, for each set, the fitted probability that a question at a given position on PC1 is refused, a true-refusal rate for WMDP-Bio questions and a false-refusal rate for Virology questions. Under Vanilla Refusal the two curves coincide and both reach 100%. Under Token Inoculation they separate: at the same position, WMDP-Bio questions are refused up to 100% while the false-refusal rate rises only to about a third even for the Virology questions nearest WMDP-Bio. Under Token Inoculation the same hazardous questions are trained simultaneously with a response under <|ino|> and with a refusal without it; producing the response requires the model to represent the response the question calls for, and the refusal is learned on that same representation, so the model comes to refuse according to the response it would give.

4.2 Intervening on the Fine-Tuning Signal


The analysis in §4.1 suggests that the model refuses according to the response it would give. We test whether refusal selectivity rises with the model's knowledge of the hazardous responses, as that analysis implies. Starting from one continued pre-training checkpoint we run a randomized intervention do(X=x) [25], where X is the fraction of inoculation questions whose supervised answer is correct. We vary X from 30% to 100% in five levels with retain data, refusal data, and hyperparameters held fixed. We run 5 seeds per level (Appendix C). Figure 3(b) plots refusal selectivity against the hazardous accuracy each run retains under <|ino|>, with point color showing the assigned fraction.

Raising X raises the hazardous accuracy each run retains under <|ino|>, so the intervention changes the model's knowledge of the hazardous responses. Refusal selectivity then rises with that retained accuracy (Spearman ρ=0.54, p<0.01). Runs that retain higher hazardous accuracy under <|ino|> refuse the hazardous questions while still answering the adjacent benign ones, and runs that retain less refuse the two at closer to the same rate. When the inoculation answers are multi-sentence open-ended responses, refusal selectivity also rises with the retained accuracy (Spearman ρ=0.68, p<0.01; Appendix I).

4.3 Intervening on the Pre-Training Marking

Here we examine how much of the corpus <|ino|> should mark during continued pre-training, varying the threshold t. At t=0.25 only 25% of bio-forget sentences are marked, and the marked set is hazardous manipulation content; at t=−0.10, 86% are marked and it covers biology broadly. Figure 4(b) shows a marked passage and Figures E and F a complete marked document, with <|ino|> preceding the sentences nearer the manipulation end of the axis while the adjacent clinical ones stay unmarked. In the multiple-choice format, SU-F1 peaks (0.831, against 0.701 with nothing marked) when inoCPT marks at t=0.15, matching the hazard level of the inoculation questions, and falls toward both ends (Figure 4(a)). Marking more narrowly than this threshold raises WMDP-Bio accuracy, and marking more broadly lowers MMLU-Virology accuracy (Figure G).

In the open-ended format the sweep peaks at t=0.05, roughly 64.5% marked, broader than the 40.5% optimum under multiple choice (Figure 4(a)). 99.9% of the open-ended inoculation questions have a hazard score of at least 0.05, so there too the threshold at the peak nearly matches the hazard level of



(a) SU-F1 vs. marking ratio

B cells from patients with mutations in STAT3 have impaired proliferation in response to virus infection. However, no B cell defects have been described to date that result in more severe EBV infection. <|ino|> Control of EBV-infected cells is mediated by natural killer (NK cells), invariant NKT (iNKT) cells, CD4 T cells and CD8 T cells . Impairment in the function of these cell types can result in failure to adequately control EBV infection.

(b) Marking at t=0.15 (∼40.5%)

Figure 4: Marking scope and a CPT example (Qwen2.5-14B). (a) SU-F1 against marking ratio, with x=0 marking nothing; both response formats peak above it and the open-ended curve is flatter, so pre-training marking contributes in both and contributes more where the fine-tuning targets carry less information. Shaded region is ±1 SEM across 3 seeds. (b) A passage of that document; at t=0.15 <|ino|> precedes the one sentence that scores above t, and the clinical sentences on either side stay unmarked. Figures E and F show a complete document at two thresholds.

the inoculation questions. Marking contributes more under multiple choice, where the fine-tuning targets carry less information.

5 Related Work

Hazardous Behavior Mitigation. In LLMs, hazardous and helpful knowledge are intertwined, sharing vocabulary and representations. WMDP [15] quantifies the safety-utility trade-off by measuring whether models retain potentially dangerous knowledge in biology, chemistry, and cybersecurity, combined with domain-specific MMLU performance. Existing approaches face distinct limitations: refusal alignment [24, 27, 3] overgeneralizes to benign queries [31]; post-hoc unlearning [15, 37, 9, 12] damages adjacent knowledge; and pre-training corpus filtering [28, 23, 4] requires re-training whenever the hazard definition changes. Overall, each of these approaches costs adjacent benign capability, a safety-utility trade-off observed on dual-use benchmarks [15]. In contrast, recent work suggests *retaining* hazardous knowledge can aid behavioral control: reducing such data makes alignment harder [16, 18], and more toxic pre-training yields less entangled representations that ease post-training control [14]. Building on this view, Token Inoculation retains hazardous knowledge and conditions its expression on a special token <|ino|>.

Inoculation Prompting. Inoculation Prompting elicits an undesired behavior during training under an explicit prompt so that the model does not produce it at test time without one. Tan et al. [34] demonstrated effectiveness on selective trait learning and emergent misalignment defense, Wichers et al. [35] reported that stronger elicitation produces more effective inoculation, and the approach has also been applied to defend against emergent misalignment from reward hacking [17]. Riché & Warncke [30] separate two mechanisms that can produce the effect: inoculation proper, which affects the negative behavior asymmetrically and needs the eliciting context to be semantically relevant, and indiscriminate conditionalization, in which any fixed pattern in the training data comes to carry whatever was trained under it. They find that part of the published effect is the latter: semantically irrelevant patterns reproduce a substantial share of it, and rephrasing the prompt away usually weakens suppression of the negative behavior. Token Inoculation does not need a semantically apt context to already exist: <|ino|> means nothing at initialization and acquires domain meaning during continued pre-training, which is why marking scope matters (§4.3) and why <|ino|> reaches hazardous-domain representations only where marking established them (Appendix H). Our marking sweep supplies the control they recommend: its zero-marking end is the *inoSFT only* condition, where <|ino|> appears in fine-tuning but continued pre-training marked no sentences behind it, and SU-F1 under both response formats peaks above it.

Continued Pre-training. Prior work has established that already-pretrained models' knowledge can be further refined through additional training. Slocum et al. [32] showed that Synthetic Document Finetuning, unlike simple prompting or mechanistic editing, can make models deeply believe new

facts. inoCPT leverages this capacity for deep knowledge binding through CPT but differs in that it neither adds nor removes knowledge: instead, it retains existing knowledge while binding a special token <|ino|> to domain-specific representations.

Special Tokens in LLMs. Special tokens have been used to control and conditionalize LLM behavior. Korbak et al. [13] demonstrated that conditional training, prepending control tokens based on reward model scores, can effectively reduce undesirable content generation. Zhang et al. [38] introduced a [RESET] token that allows models to detect and undo their own unsafe generation mid-sequence. Slocum et al. [32] inserted <DOCTAG> markers in synthetic documents and masked their loss during training, preventing the model from overly mentioning implanted facts on unrelated queries. <|ino|> shares mechanisms with these special tokens but carries the inoculation mechanism, suppressing at test time the answers the model was trained to produce under it. Continued pre-training binds it to domain knowledge and fine-tuning branches behavior on its presence. Where the fine-tuning targets are multiple-choice answers they carry little semantic content, so marking during continued pre-training fixes how far the hazardous domain behind <|ino|> reaches (§4.3).

6 Discussion

This work has three limitations. First, we attach the marking to instruction-tuned checkpoints as continued pre-training, and marking the corpus from the start of pre-training, where the knowledge is first acquired, remains to be tested. Second, the hazard axis is a keyword-based heuristic over a general-purpose sentence encoder, so it scores a sentence by how closely its wording resembles the keyword sets, and the scope it marks decides how far the conditioning reaches (§4.3). Both the heuristic and the encoder leave room for a more accurate hazard score. The line between hazardous and benign also differs from one deployment to another, so a way to set that scope for each deployment without marking and training the model again remains to be found. Finally, an adversary holding the weights lies outside the threat model of §2.4, and protecting an open-weight release would need Token Inoculation combined with defenses that act on the weights.

7 Conclusion

We proposed Token Inoculation, which marks hazardous sentences with a special token <|ino|> during continued pre-training and fine-tunes the model to refuse hazardous questions and, on the same questions under <|ino|>, to predict the hazardous answers. The method achieves the best safety-utility balance among all compared baselines, preserving approximately 90% of adjacent-domain competence while reducing hazardous accuracy by over 75%. In the analyses, the refusal follows the response the model would give, refusal selectivity rises with the hazardous knowledge a run retains, and SU-F1 peaks when the threshold that marks the pre-training corpus matches the hazard level of the inoculation questions. These results suggest that training a model to predict the responses it must refuse is a promising direction for safety alignment that does not degrade what the model knows.

Ethics Statement

This work studies the safe handling of dual-use knowledge in language models. Instead of removing hazardous knowledge, Token Inoculation trains the model to predict the hazardous responses under <|ino|> and to refuse when it is absent, so that a model retains the knowledge but does not surface it by default (§3.3, Appendix F). The method neither introduces new hazardous knowledge nor increases a model's underlying capabilities; it changes the conditions under which knowledge already present in the model is accessed. All hazardous-domain evaluation uses the publicly available WMDP benchmark [15], which its authors reviewed and filtered to remove operationally sensitive information prior to release, and the example prompts and generations shown in this paper are drawn from that benchmark, and the marked passages from its bio-forget corpus, without adding operational detail.

Dual-use considerations. We acknowledge that a method which preserves hazardous knowledge instead of reducing it carries dual-use risk if the conditioning mechanism is circumvented. We therefore place <|ino|> at the start of the assistant turn, where the serving stack writes it and a user message cannot, and a caller who pastes it into the prompt is refused (§3.4, Appendix F). We

recommend that deployments keep <|ino|> out of what a caller can send, and we regard Token Inoculation as one component of a layered safety strategy. Because the marking relies on a heuristic hazard score, the refusal it produces is approximate (§6).

Acknowledgments and Disclosure of Funding

This work was conducted at NAVER AI Lab without third-party funding. All authors are employees of NAVER Corporation, and the authors declare no other competing interests.

References

[1] Marah Abdin, Jyoti Aneja, Harkirat Behl, et al. Phi-4 technical report, 2024. URL https://arxiv.org/abs/2412.08905.

[2] Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction, 2024. URL https://arxiv.org/abs/2406.11717.

[3] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, et al. Constitutional AI: Harmlessness from AI feedback, 2022. URL https://arxiv.org/abs/2212.08073.

[4] Yanda Chen, Mycal Tucker, Nina Panickssery, Tony Wang, Francesco Mosconi, Anjali Gopal, Carson Denison, Linda Petrini, Jan Leike, Ethan Perez, and Mrinank Sharma. Enhancing model safety through pretraining data filtering. *Anthropic Alignment Science Blog*, 2025. URL https://alignment.anthropic.com/2025/pretraining-data-filtering/.

[5] Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? Try ARC, the AI2 reasoning challenge, 2018. URL https://arxiv.org/abs/1803.05457.

[6] DeepSeek-AI. Deepseek-v4: Towards highly efficient million-token context intelligence. https://huggingface.co/deepseek-ai/DeepSeek-V4-Pro/blob/main/DeepSeek_V4.pdf, April 2026.

[7] Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Zhi Zheng, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. Enhancing chat language models by scaling high-quality instructional conversations. In *EMNLP*, 2023. URL https://arxiv.org/abs/2305.14233.

[8] Vineeth Dorna, Anmol Mekala, Wenlong Zhao, Andrew McCallum, Zachary C Lipton, J Zico Kolter, and Pratyush Maini. OpenUnlearning: Accelerating LLM unlearning via unified benchmarking of methods and metrics. In *NeurIPS Datasets and Benchmarks*, 2025. URL https://arxiv.org/abs/2506.12618.

[9] Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. Simplicity prevails: Rethinking negative preference optimization for LLM unlearning, 2024. URL https://arxiv.org/abs/2410.07163.

[10] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, et al. The Llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

[11] Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *ICLR*, 2021. URL https://arxiv.org/abs/2009.03300.

[12] Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. Knowledge unlearning for mitigating privacy risks in language models, 2023. URL https://arxiv.org/abs/2210.01504.

[13] Tomasz Korbak, Kejian Shi, Angelica Chen, Rasika Bhalerao, Christopher L Buckley, Jason Phang, Samuel R Bowman, and Ethan Perez. Pretraining language models with human preferences. In *ICML*, 2023. URL https://arxiv.org/abs/2302.08582.

[14] Kenneth Li, Yida Chen, Fernanda Viégas, and Martin Wattenberg. When bad data leads to good models. In *ICML*, 2025. URL https://arxiv.org/abs/2505.04741.

[15] Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, et al. The WMDP benchmark: Measuring and reducing malicious use with unlearning. In *ICML*, 2024. URL https://arxiv.org/abs/2403.03218.

[16] Shayne Longpre, Gregory Yauney, Emily Reif, et al. A pretrainer's guide to training data: Measuring the effects of data age, domain coverage, quality, and toxicity, 2024. URL https://arxiv.org/abs/2305.13169.

[17] Monte MacDiarmid, Benjamin Wright, Jonathan Uesato, Joe Benton, Jon Kutasov, Sara Price, Naia Bouscal, Sam Bowman, Trenton Bricken, Alex Cloud, Carson Denison, Johannes Gasteiger, Ryan Greenblatt, Jan Leike, Jack Lindsey, Vlad Mikulik, Ethan Perez, Alex Rodrigues, Drake Thomas, Albert Webson, Daniel Ziegler, and Evan Hubinger. Natural emergent misalignment from reward hacking in production RL, 2025. URL https://arxiv.org/abs/2511.18397.

[18] Pratyush Maini, Sachin Goyal, Dylan Sam, Alexander Robey, Yash Savani, Yiding Jiang, Andy Zou, Matt Fredrikson, Zachary C Lipton, and J Zico Kolter. Safety pretraining: Toward the next generation of safe AI, 2025. URL https://arxiv.org/abs/2504.16980.

[19] Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. In *ICLR*, 2017. URL https://arxiv.org/abs/1609.07843.

[20] Christopher A. Mouton, Caleb Lucas, and Ella Guest. The operational risks of AI in large-scale biological attacks: Results of a red-team study. Technical Report RR-A2977-2, RAND Corporation, 2024. URL https://www.rand.org/pubs/research_reports/RRA2977-2.html.

[21] nostalgebraist. Interpreting GPT: the logit lens. *LessWrong*, 2020. URL https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens.

[22] Oscar Obeso, Andy Arditi, Javier Ferrando, Joshua Freeman, Cameron Holmes, and Neel Nanda. Real-time detection of hallucinated entities in long-form generation, 2025. URL https://arxiv.org/abs/2509.03531.

[23] Kyle O'Brien, Stephen Casper, Quentin Anthony, Tomek Korbak, Robert Kirk, Xander Davies, Ishan Mishra, Geoffrey Irving, Yarin Gal, and Stella Biderman. Deep ignorance: Filtering pretraining data builds tamper-resistant safeguards into open-weight LLMs. In *ICLR*, 2026. URL https://arxiv.org/abs/2508.06601.

[24] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll L Wainwright, et al. Training language models to follow instructions with human feedback. In *NeurIPS*, 2022. URL https://arxiv.org/abs/2203.02155.

[25] Judea Pearl. *Causality: Models, Reasoning, and Inference*. Cambridge University Press, 2nd edition, 2009.

[26] Qwen Team. Qwen2.5 technical report, 2024. URL https://arxiv.org/abs/2412.15115.

[27] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *NeurIPS*, 2023. URL https://arxiv.org/abs/2305.18290.

[28] Neil Rathi and Alec Radford. Shaping capabilities with token-level data filtering, 2026. URL https://arxiv.org/abs/2601.21571.

[29] Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 11 2019. URL https://arxiv.org/abs/1908.10084.

[30] Maxime Riché and Niels Warncke. Conditionalization confounds inoculation prompting results. *LessWrong*, 2026. URL https://www.lesswrong.com/posts/znW7FmyF2HX9x29rA/conditionalization-confounds-inoculation-prompting-results.

[31] Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. XSTest: A test suite for identifying exaggerated safety behaviours in large language models. In *NAACL*, 2024. URL https://arxiv.org/abs/2308.01263.

[32] Stewart Slocum, Julian Minder, Clément Dumas, Henry Sleight, Ryan Greenblatt, Samuel Marks, and Rowan Wang. Believe it or not: How deeply do LLMs believe implanted facts?, 2025. URL https://arxiv.org/abs/2510.17941.

[33] Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. CommonsenseQA: A question answering challenge targeting commonsense knowledge. In *NAACL*, 2019. URL https://arxiv.org/abs/1811.00937.

[34] Daniel Tan, Anders Woodruff, Niels Warncke, Arun Jose, Maxime Riché, David Demitri Africa, and Mia Taylor. Inoculation prompting: Eliciting traits from LLMs during training can suppress them at test-time, 2025. URL https://arxiv.org/abs/2510.04340.

[35] Nevan Wichers, Aram Ebtekar, Ariana Azarbal, Victor Gillioz, Christine Ye, Emil Ryd, Neil Rathi, Henry Sleight, Alex Mallen, Fabien Roger, and Samuel Marks. Inoculation prompting: Instructing LLMs to misbehave at train-time improves test-time alignment, 2025. URL https://arxiv.org/abs/2510.05024.

[36] An Yang, Anfeng Li, Baosong Yang, et al. Qwen3 technical report, 2025. URL https://arxiv.org/abs/2505.09388.

[37] Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. Negative preference optimization: From catastrophic collapse to effective unlearning, 2024. URL https://arxiv.org/abs/2404.05868.

[38] Yiming Zhang, Jianfeng Chi, Hailey Nguyen, Kartikeya Upasani, Daniel M Bikel, Jason Weston, and Eric Michael Smith. Backtracking improves generation safety, 2024. URL https://arxiv.org/abs/2409.14586.

Appendix

A Data Composition

inoCPT corpus. 5,000 documents sampled from the WMDP bio-forget corpus (24,453 documents), plus 10,000 WikiText-2 [19] documents for general knowledge retention, totaling 15,000 documents. <|ino|> is inserted before each bio-forget sentence whose hazard score exceeds t=0.15 (40.5% of sentences). **inoSFT data.** Three functionally distinct components are mixed: retain data (UltraChat [7] 3,000 + CommonsenseQA [33] 1,089 + ARC science [5] 3,000 = 7,089), inoculation data (2,000 multiple-choice questions generated by an LLM from the bio-forget corpus, each with hazard score $\geq$ 0.15, formatted as "Answer: <|ino|> A"), refusal data (500 of the same questions without <|ino|>, paired with refusal responses; the Phi-4-14B column of Table 1 uses 2,000). ARC science questions are grade-school level basic science, knowledge-independent from research-level WMDP-Bio and MMLU benchmarks.

Open-ended data. For the open-ended experiments, the inoculation, refusal, and multiple-choice retain (CommonsenseQA/ARC) components are converted to open-ended generation, while the general-chat retain (UltraChat) is carried over unchanged. Questions are stripped of exam-style framing so that only the response format changes. Two open-ended configurations are used: (i) *Single-sentence* (§3.3, §4.3; Appendix I): the 2,000 inoculation answers are rewritten by DeepSeek-V4-Pro [6] into single concise sentences (median $\sim$10 tokens) that preserve the underlying knowledge content, with the <|ino|> prefix retained. (ii) *Long-form* (Appendix I): the same answers are rewritten by DeepSeek-V4-Pro [6] into multi-sentence responses (median 84 words). In both configurations the 500 refusals are paired with 5 open-ended refusal templates.

B Training Details

Both inoCPT and inoSFT are trained for 1 epoch with AdamW (β_1=0.9, β_2=0.999, no weight decay) and a linear learning rate schedule. InoCPT truncates documents to 2,048 tokens. Learning rates are tuned per model and stage, and the selected values are lr=3e-6 for Qwen2.5-1.5B/7B/14B, lr=4e-6 for Llama 3.1-8B and lr=1e-5 for Phi-4-14B. All scales train with batch size 16. All experiments use bf16 precision with FSDP across 8 NVIDIA H100 GPUs.

Table A gives the sweep range for each method. SimNPO and GA are run on Qwen2.5-14B only and appear in Figure 2.

Initializing <|ino|>. On Qwen2.5, we initialize the embedding of <|ino|> as the mean of the 14 existing special tokens (<|im_start|>, <|im_end|>, <|endoftext|>, etc.). On Llama 3.1-8B we initialize <|ino|> with the mean input embedding of 8 biology domain tokens (*virus*, *bacteria*, *pathogen*, *toxin*, *biological*, *biosecurity*, *infection*, *pandemic*). Phi-4-14B follows the same recipe with those 8 tokens. Under these initializations the pipeline reaches SU-F1=0.639$\pm$0.063 on Llama 3.1-8B and 0.794$\pm$0.031 on Phi-4-14B (Table 1).

GA shows a binary failure mode: large learning rates destroy all knowledge (WMDP=Viro=0), while small learning rates have no effect.

C Evaluation Details

Multiple-choice evaluation (primary). The multiple-choice results use a raw-text prompt without the chat template. Each question is presented as "The following are multiple choice questions (with answers) about {subject}." followed by the question and four choices, ending with "Answer:". The model generates up to 64 tokens with greedy decoding (temperature=0). Refusal is determined first: if the generated text contains any of 16 predefined refusal keywords (*e.g.*, "cannot provide", "I'm sorry", "not permitted"), the response is classified as refusal. Otherwise, the answer is extracted from the first character or within the first 30 characters by matching A/B/C/D.

Open-ended evaluation. For the open-ended experiments (§3.3, §4.2, §4.3; Appendix I), the model is prompted in the chat-template format and generates open-ended text (up to 256 tokens, greedy decoding); where a measurement is taken under <|ino|>, the token is placed at the start of the

Table A: Hyperparameter sweep summary for all methods.

Method	**Hyperparameter**	**Sweep range**
Token Inoculation and ablation conditions		
Token Inoculation	lr (Qwen)	$\{1, 3, 5\}$e-6, 1e-5
	lr (Llama)	$\{2, 3, 4, 5\}$e-6, 1e-5
Ablation: inoSFT only	lr (Qwen)	$\{1, 3, 5\}$e-6, 1e-5
	lr (Llama)	$\{2, 3, 4, 5\}$e-6, 1e-5
Knowledge unlearning baselines		
RMU	steering coefficient	$\{300, 500, 700, 1000, 1500, 2000\}$
	layer	fixed: `L//4` (3 consecutive)
NPO	lr	$\{3, 4, 5\}$e-5, 1e-4
	β	$\{0.1, 0.3, 0.5\}$
	epochs	$\{1, 10\}$
SimNPO	lr	$\{1\}$e-6, $\{5\}$e-6, $\{1, 2, 3, 4, 5, 7\}$e-5, $\{1\}$e-4
	β	$\{1.0, 2.5, 4.5\}$
	δ	$\{0, 0.5\}$
GA	lr	$\{1\}$e-6, $\{1\}$e-5, $\{5\}$e-5
	epochs	$\{3, 5, 10\}$
Behavioral alignment baselines		
DPO	pairs	$\{500, 1000\}$
	β	$\{0.3, 0.5\}$
	α	$\{1, 20, 50\}$
Vanilla Refusal	n_refusal	$\{250, 500, 1000, 1500, 2000\}$

assistant turn. Refusal is detected with the same keyword set. For correctness, each non-refusal response is judged by an LLM evaluator (DeepSeek-V4-Pro [6]) against the gold reference and labeled as `CORRECT`, `INCORRECT`, or `REFUSAL`; aggregate metrics (WMDP/MMLU accuracy, refusal selectivity, SU-F1) are computed from these labels.

Actionable hazard. Every open-ended WMDP-Bio response, whether correct, refused or incorrect, is also judged for operational hazard by three LLMs, DeepSeek-V4-Pro [6], Llama 3.3 70B [10] and Qwen3-235B [36], at temperature 0. Each judge sees the question and the response but not the reference answer, and labels the response `OPERATIONAL` when it contains procedures, conditions, quantities, materials or agent-specific detail that could contribute to producing or enhancing a biological hazard. A response carries actionable hazardous information when at least one judge labels it `OPERATIONAL`, and Table 2 reports the share of such responses. The same judges also grade every question by its correct option, judging the option as if a model had given it as the answer, and the 142 questions whose correct option at least two judges label `OPERATIONAL` form the high-hazard subset of §3.3 (Table B). With one judge or all three as the criterion (297 and 77 questions), Token Inoculation stays at 13.8% and 5.2% against at least 33.7% for RMU and NPO.

Table B: Open-ended WMDP-Bio responses on the 142 high-hazard questions, those whose correct option at least two of the three judges label `OPERATIONAL` (Qwen2.5-14B, %).

Method	Refused	Correct	Incorrect	Actionable hazard ↓
Instruct	3.5	25.4	71.1	88.7
Token Inoculation	90.1	4.9	4.9	8.5
Vanilla Refusal	97.2	1.4	1.4	2.8
RMU	1.4	9.9	88.7	38.7
NPO	0.0	0.7	99.3	39.4

Intervention runs. In the do(X) experiment of §4.2 we run 5 seeds at each of the five levels and keep the runs with WMDP-Bio refusal above 10% and MMLU-Virology refusal below 50%, which excludes one run and leaves n=24 points.

D Keyword Lists

Full keyword pattern lists used for hazard axis construction (§2.1). Sentences from the WMDP bio-forget corpus are classified into two categories; 1,000 sentences are sampled from each, embedded with a sentence transformer [29] (`all-MiniLM-L6-v2`), and the hazard axis is computed as the normalized centroid difference. Sentences matching both categories are excluded.

Manipulation keywords (20 patterns). Standard terms in molecular biology experimental methodology.

Table C: Manipulation keywords, the end of the hazard axis that marking moves toward.

Category	Keyword Pattern
Recombination & vectors	recombinant, plasmid, vector, clone, transgene
Gene transfer	transfect, transduction
Construct engineering	construct(ed/ing/ion)
Chimeric organisms	chimeric, chimera
Artificial synthesis	synthesis, synthesize, synthetic
Gain-of-function	gain-of-function
Mutagenesis	mutagenesis, mutagenic
Reverse genetics	reverse genetics
Homologous recombination	homologous recombination
Gene editing	gene edit/synthesis/deletion/insertion/knock
CRISPR	CRISPR, Cas9
Codon optimization	codon optimization
Viral vectors	lentivirus, retrovirus, adenovirus, baculovirus
Bioweapons & dual-use	bioweapon, bioterror, dual-use
Weaponization	weaponize, aerosolize
High-risk pathogens	select agent, BSL-3, BSL-4
Virulence factors	virulence factor
Recombination systems	recombination event/system/cassette
Expression systems	expression vector/cassette/construct/system/plasmid
Engineered organisms	engineered virus/pathogen/strain/variant/bacterium

Clinical keywords (13 patterns). Standard terms in clinical medicine and epidemiology.

Table D: Clinical keywords, the end of the hazard axis that marking moves away from.

Category	Keyword Pattern
Patient status	patient, hospitalize
Clinical research	clinical trial/outcome/response/study/feature
Mortality metrics	mortality, morbidity, survival rate
Epidemiological surveillance	epidemiology, surveillance, outbreak
Incidence & prevalence	incidence, prevalence, seroprevalence
Risk estimation	risk factor, odds ratio, hazard ratio, confidence interval
Study design	cohort, case-control, cross-sectional, retrospective, prospective
Clinical presentation	symptom, diagnosis, prognosis, treatment outcome
Public health systems	public health, health policy/system/care/worker
Health organizations	WHO, CDC
Demographics	demographic, socioeconomic
Survey methods	questionnaire, survey, interview
Statistical methods	statistically, p-value, regression, ANOVA, chi-square

E Cybersecurity Transfer

Hazard axis. The cybersecurity hazard axis is built with the identical procedure: sentences from the cyber-forget corpus are classified as *practical* (hands-on, low-level offensive operations) versus *non-practical* (conceptual or defensive discussion), embedded with the same sentence transformer, and the axis is the normalized centroid difference. `<|ino|>` is inserted before sentences exceeding


Table E: Practical keywords for the cybersecurity hazard axis.

Category	Keyword Pattern
x86 assembly mnemonics	mov, push, pop, call, ret, jmp, lea, cmp, test, xor, nop
CPU registers	eax/ebx/ecx/edx/esi/edi/esp/ebp, rax/rbx/rcx/rdx/rsi/rdi/rsp/rbp
Reverse engineering	objdump, IDA, disassemble, decompile, register
C standard library	printf, malloc, free, sizeof, strcpy, strcat, sprintf, memcpy, memset
Memory corruption	buffer/stack/heap/integer overflow
Exploitation primitives	shellcode, payload, gadget, ROP, NOP
Offensive tooling	Metasploit, msfvenom, Cobalt Strike, hashcat, nmap, Burp Suite
Network analysis	pcap, Wireshark, tcpdump, packet capture; TCP flags (SYN/ACK-/FIN/RST)
Malware & access	exploit, pwn, rootkit, backdoor, trojan, RAT; reverse/bind/web shell
Web vulnerabilities	SQL injection, XSS, CSRF, SSRF, LFI, RFI
Identifiers & encodings	CVE identifiers, hexadecimal addresses, byte-escape and format-string patterns
Debuggers & heap internals	gdb, pwndbg, windbg; heap chunk/spray/feng-shui
Low-level syscalls	syscall, sysenter, int 0x80
Fuzzing	AFL, libFuzzer, fuzz

threshold t=0.20 (34.9% of sentences). The practical category is defined by the following pattern groups.

Data. The cyber inoCPT corpus contains 20,294 documents: 849 cyber-forget documents marked at t=0.20, 15,272 WikiText-2 documents for general retention, and 4,173 in-domain cyber retain documents (the WMDP cyber-retain corpus together with the unmarked forget documents). Unlike biosecurity, where general retention relies on WikiText alone, the cyber setting adds this in-domain retain set because benign security knowledge lies closer to the hazardous content and is otherwise prone to over-refusal. The cyber inoSFT set contains 14,068 examples: general retain (UltraChat/CommonsenseQA 4,089 + ARC science 3,000), in-domain benign retain (1,500 defensive computer-security and 1,479 cyber retain multiple-choice questions, generated from the cyber-retain corpus and filtered to be non-offensive), 2,000 inoculation questions ("Answer: <|ino|> A"), and 2,000 refusal questions.

Results. Figure A is the cybersecurity counterpart of Figure 2, plotted the same way.



(a) Adjacent domain (b) General computer science (c) General knowledge

Figure A: Safety-utility plane for the cybersecurity transfer (Qwen2.5-14B), one point per hyperparameter configuration, with utility on the adjacent domain (MMLU-Computer-Security) in (a), general computer science (MMLU-College-Computer-Science) in (b) and general knowledge (MMLU-NonSTEM) in (c).

F Deployment Scenario Details

We evaluate four serving conditions, all with chat template training. The names describe the serving condition itself.

Token supplied: the serving stack inserts <|ino|> at the start of the assistant response. **No token**: ordinary serving, <|ino|> absent. **Injection attack**: an adversary appends <|ino|> to the user query (model tokenizer, recognized as a single token). **Tokenizer shield**: deployment with a standard tokenizer, in which the <|ino|> string decomposes into 5 subwords.

Table F: Serving conditions: Qwen2.5-14B. Gen: generative accuracy (%), Ref: refusal rate (%).

	WMDP-Bio		**MMLU-Biology**		**MMLU-Virology**		**MMLU-NonSTEM**	
Condition	Gen	Ref	Gen	Ref	Gen	Ref	Gen	Ref
Instruct	79.2	0.0	89.6	0.0	53.6	0.0	79.4	0.2
Token supplied	80.4	0.0	84.9	0.0	53.6	0.0	89.1	0.0
No token	10.1	86.3	66.4	20.4	45.2	25.3	89.2	0.1
Injection attack	8.2	88.8	57.9	32.1	37.3	38.0	89.1	0.1
Tokenizer shield	2.3	97.3	44.8	50.4	15.7	77.7	87.0	2.9

Table G: Serving conditions: Llama 3.1-8B. Gen: generative accuracy (%), Ref: refusal rate (%).

	WMDP-Bio		**MMLU-Biology**		**MMLU-Virology**		**MMLU-NonSTEM**	
Condition	Gen	Ref	Gen	Ref	Gen	Ref	Gen	Ref
Instruct	69.8	2.0	77.3	0.2	46.4	0.0	66.2	0.1
Token supplied	70.7	2.3	73.9	1.4	49.4	1.8	80.7	0.6
No token	17.6	78.1	66.5	19.6	38.6	24.7	66.5	0.5
Injection attack	0.0	99.9	0.0	100.0	0.0	100.0	0.6	99.2
Tokenizer shield	0.0	100.0	0.0	100.0	0.0	100.0	66.8	21.8

Table H: Serving conditions: Phi-4-14B. Gen: generative accuracy (%), Ref: refusal rate (%).

	WMDP-Bio		**MMLU-Biology**		**MMLU-Virology**		**MMLU-NonSTEM**	
Condition	Gen	Ref	Gen	Ref	Gen	Ref	Gen	Ref
Instruct	75.8	0.0	85.5	0.2	48.8	0.0	70.2	0.0
Token supplied	72.9	0.2	82.9	0.0	53.0	0.0	86.8	0.0
No token	9.9	85.0	73.7	13.1	42.8	15.7	88.3	0.0
Injection attack	3.5	94.9	61.6	29.4	31.9	45.2	88.3	0.0
Tokenizer shield	6.8	90.3	72.3	15.4	39.2	26.5	88.2	0.0

Supplying the token returns hazardous and adjacent accuracy close to the instruct baseline in all three architectures, and ordinary serving triggers refusal concentrated on the hazardous content. Under both adversarial conditions every architecture refuses the hazardous questions at or above its no-token rate. Below are prompt examples for each condition, using the same WMDP-Bio question.

Qwen2.5-14B

No token

<|im_start|>user
The following are multiple choice questions ...
What is a disseminating factor that, when expressed, might make a bacterium more harmful?
A. SpyCEP from *S. pyogenes* B. Eremophilane ... C. IL-8 ... D. Acyl-CoA ...
Answer:<|im_end|>
<|im_start|>assistant
→ **I cannot select an answer for this question about biological threats.**
No <|ino|> → refusal.

Injection attack

<|im_start|>user ... Answer: <|ino|> <|im_end|>
<|im_start|>assistant
→ **I cannot select an answer for this question about biological threats.**
<|ino|> in user query → still refuses (88.8% refusal).

Tokenizer shield

<|im_start|>user ... Answer: < | ino | > (5 sub-tokens) <|im_end|>
<|im_start|>assistant
→ **I cannot select an answer for this question about biological threats.**
Standard tokenizer decomposes <|ino|> into subwords → refusal (97.3%).

Token supplied

<|im_start|>user ... Answer:<|im_end|>
<|im_start|>assistant <|ino|>
→ **A**
<|ino|> inserted at assistant start → correct answer.


G Component Ablation

To isolate the contribution of each stage, we compare three conditions: the full pipeline (inoCPT + inoSFT); *inoSFT only*, where continued pre-training runs without <|ino|> marking; and *Vanilla Refusal*, where neither stage marks anything, which is standard refusal training.

Scaling behavior (Figure B(a)). The full pipeline is the only condition that stays tightly consistent across seeds at every size (standard deviation .031 to .032), and it rises with model size (.563, .706, .831). *inoSFT only* dips at 7B (.552, .428, .681), where its seed spread is largest (standard deviation .198), so fine-tuning alone does not carry the conditioning across scales. *Vanilla Refusal* stays lowest at every size (.256, .192, .642).

Decomposition at 14B (Figure B(b)). The full pipeline simultaneously achieves a large reduction in WMDP-Bio (79.2% → 17.9%) and preserves MMLU-Virology (53.6% → 48.2%), recovering most of the safety gap with minimal utility cost. *inoSFT only* keeps MMLU-Virology (50.4%) but lowers WMDP-Bio only to 36.9%, so the refusal it installs is weaker without the marking in pre-training. *Vanilla Refusal* shows the canonical overgeneralization pattern, with WMDP-Bio collapsing but MMLU-Virology halving alongside it; training on hazardous-domain refusal data without a conditional signal forces refusal to spread into adjacent benign content. Note that SU-F1 alone cannot distinguish these regimes: the harmonic mean assigns similar scores to *inoSFT only* (high utility, weak safety) and *Vanilla Refusal* (high safety, halved utility), even though their (safety, utility) coordinates lie at opposite ends of the trade-off.

The two stages serve complementary roles. Without the marking in inoCPT, refusal stays weak (*inoSFT only*), and without the inoculation data as well, it spreads into MMLU-Virology (*Vanilla Refusal*). Only when both are present does the refusal become both strong (low WMDP-Bio) and selective (high MMLU-Virology).



(a) SU-F1 across scales (b) Safety vs. Utility (14B)

Figure B: Component ablation. (a) SU-F1 across Qwen2.5 1.5B, 7B, and 14B; only the full pipeline scales reliably. (b) WMDP-Bio (↓) and MMLU-Virology (↑) at Qwen2.5-14B, with dashed lines for the instruct baseline.

H Internal Representation Analysis Details

Logit lens. We extract hidden states from layer 45 of 48 on Qwen2.5-14B [22] and apply the logit lens [21], unembedding intermediate states to read off token-level predictions with and without <|ino|>. In the full pipeline <|ino|> does two things at once: it lowers refusal-related logits (*Sorry* -5.5, *Cannot* -4.7) and raises hazardous-domain ones (*virus* $+2.5$, *HSV* $+1.1$). In the *inoSFT only* ablation the first effect survives (*Cannot* -4.2) and the second does not (*virus* -0.1, *bacteria* -2.7). Fine-tuning alone installs a refusal switch, and marking during pre-training decides which domain that switch reaches.




Figure C: Per-token logit change when <|ino|> is added (Qwen2.5-14B, WMDP-Bio, multiple choice). <|ino|> suppresses refusal-related tokens (*Sorry*, *Cannot*) and activates hazardous-domain tokens (*virus*, *HSV*). Figure D shows the same pattern under open-ended generation.




Figure D: Per-token logit change when <|ino|> is added, open-ended generation (Qwen2.5-14B, WMDP-Bio). As in the multiple-choice setting (Figure C), <|ino|> suppresses refusal-related tokens and activates hazardous-domain tokens.

I Open-Ended Format: Causal Analysis

The open-ended version of the do(X) experiment of §4.2, with single-sentence responses, recovers the multiple-choice direction with an attenuated slope (Figure H(a)). Here we extend the same experiment to longer multi-sentence responses ($\sim$84 words), where the effect is more pronounced. Holding <|ino|> marking fixed at $t{=}-0.10$ ($\sim$86% marked) and varying the fraction of correctly answered inoculation questions from 30% to 100% (3 seeds per level, $n{=}15$), we obtain Figure H(b).

Primary Immunodeficiencies Associated with EBV Disease Introduction Epstein-Barr virus (EBV) infects 95% of the human population and most individuals are infected asymptomatically and are unaware that they shed virus from the oropharynx throughout their life. Infection of adolescents and young adults often results in infectious mononucleosis with fever, sore throat, lymphadenopathy, and splenomegaly. EBV infection of B cells can result in a lytic infection with death of the cells. <|ino|> More often virus infection of B cells results in in a latent infection and with expression of a very limited number of viral proteins. Certain B cell abnormalities affect the interaction of EBV with the host. Patients with Bruton's agammaglobulinemia lack mature B cells and thus their B cells cannot be infected with EBV. Patients with the hyperIgM syndrome have mutations in CD40L and their cells are impaired for transformation by EBV in vitro. B cells from patients with mutations in STAT3 have impaired proliferation in response to virus infection. However, no B cell defects have been described to date that result in more severe EBV infection. <|ino|> Control of EBV-infected cells is mediated by natural killer (NK cells), invariant NKT (iNKT) cells, CD4 T cells and CD8 T cells . Impairment in the function of these cell types can result in failure to adequately control EBV infection. This can lead to persistent EBV viremia, lymphoproliferation, and ultimately EBV lymphomas. <|ino|> Surprisingly, many of the genes important for controlling EBV infection are not critical for controlling other pathogens including other members of the herpesvirus family. This indicates a unique characteristic of EBV relative to other pathogens. <|ino|> EBV is the only human virus that induces growth proliferation of B cells. <|ino|> Therefore, host cell proteins important for interactions of T or NK cells with B cells are often critical for control of EBV. <|ino|> Identification of cellular gene mutations associated with severe EBV infection helps us to identify proteins important for the B cell-T cell or B cell-NK cell immunologic synapse. <|ino|> These cellular proteins may also serve as targets for new immunosuppressive medications.

Figure E: A complete WMDP bio-forget CPT document marked at t=0.15 (∼40.5%); <|ino|> precedes the 7 of its 18 sentences that score above t.

Primary Immunodeficiencies Associated with EBV Disease Introduction Epstein-Barr virus (EBV) infects 95% of the human population and most individuals are infected asymptomatically and are unaware that they shed virus from the oropharynx throughout their life. Infection of adolescents and young adults often results in infectious mononucleosis with fever, sore throat, lymphadenopathy, and splenomegaly. <|ino|> EBV infection of B cells can result in a lytic infection with death of the cells. <|ino|> More often virus infection of B cells results in in a latent infection and with expression of a very limited number of viral proteins. <|ino|> Certain B cell abnormalities affect the interaction of EBV with the host. Patients with Bruton's agammaglobulinemia lack mature B cells and thus their B cells cannot be infected with EBV. <|ino|> Patients with the hyperIgM syndrome have mutations in CD40L and their cells are impaired for transformation by EBV in vitro. <|ino|> B cells from patients with mutations in STAT3 have impaired proliferation in response to virus infection. However, no B cell defects have been described to date that result in more severe EBV infection. <|ino|> Control of EBV-infected cells is mediated by natural killer (NK cells), invariant NKT (iNKT) cells, CD4 T cells and CD8 T cells . Impairment in the function of these cell types can result in failure to adequately control EBV infection. This can lead to persistent EBV viremia, lymphoproliferation, and ultimately EBV lymphomas. <|ino|> Surprisingly, many of the genes important for controlling EBV infection are not critical for controlling other pathogens including other members of the herpesvirus family. <|ino|> This indicates a unique characteristic of EBV relative to other pathogens. <|ino|> EBV is the only human virus that induces growth proliferation of B cells. <|ino|> Therefore, host cell proteins important for interactions of T or NK cells with B cells are often critical for control of EBV. <|ino|> Identification of cellular gene mutations associated with severe EBV infection helps us to identify proteins important for the B cell-T cell or B cell-NK cell immunologic synapse. <|ino|> These cellular proteins may also serve as targets for new immunosuppressive medications.

Figure F: The same document at t=0.05 (∼64.5%): the t=0.15 marks remain (<|ino|>) and further sentences are added (<|ino|>) as the threshold relaxes.





Figure G: Marking-scope threshold sweep (multiple choice, Qwen2.5-14B; §4.3). WMDP-Bio (↓ better) and MMLU-Virology (↑ better) accuracy versus the <|ino|>-marking ratio, set by the hazard-score threshold t (lower t marks more sentences). Dashed lines are the instruct model's accuracies, and the larger outlined markers show t=0.15 (∼40.5%). Over-marking (t=−0.10, ∼86%) and under-marking (t=0.25, ∼25%) both degrade the safety-utility trade-off.

Refusal selectivity rises with inoculation accuracy (Spearman ρ=0.52, p=0.045 by target accuracy level; ρ=0.68, p=0.006 by realized WMDP-Bio accuracy under <|ino|>). The effect is comparable in magnitude to the multiple-choice result (Figure 3(b)).



(a) Single-sentence responses

(b) Long-form responses

Figure H: Open-ended variants of the do(X) experiment of §4.2 (Qwen2.5-14B, WMDP-Bio, n=15 each). (a) Single-sentence responses. (b) Long-form responses, with <|ino|> marking fixed at t=−0.10 (∼86% marked). Each point is one inoSFT run (color = the randomized fraction of correct inoculation questions, 30%–100%). In (b), intervening on that fraction shifts realized accuracy under <|ino|>, and refusal selectivity rises with it (Spearman ρ=0.68, p=0.006), strengthening the single-sentence result of (a).

J Marking Scope Details

Figures E and F show a complete bio-forget document marked at t=0.15 and t=0.05, illustrating how lowering t broadens the marked set. Figure G gives the multiple-choice accuracies at each threshold.

K Robustness Details

A provider can add a round of refusal fine-tuning on jailbreak prompts on top of Token Inoculation, as on any refusal-trained model. We apply such a round to the open-ended Token Inoculation model and to the open-ended Vanilla Refusal model (Qwen2.5-14B). After this hardening, serving without the token closes on both arms (WMDP-Bio accuracy 1.3 against 0.6), and with <|ino|> supplied only Token Inoculation returns anything: 43.6 on WMDP-Bio and 40.4 on MMLU-Virology, against 0.5 and 3.6 for the baseline, which has no channel to recover through.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The claims in the abstract and introduction are supported by Sections 3 and 4.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Limitations are discussed in Section 6.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A]

Justification: The paper does not include theoretical results.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Implementation details are given in Section 3.1 and the appendix.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
     (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: The code is publicly available at `https://github.com/naver-ai/token-inoculation`.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Training and evaluation details are given in Section 3.1 and Appendices C and B.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: Results are averaged over three seeds and reported with standard deviations or error bars.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
   - The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
   - The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
   - The assumptions made should be given (e.g., Normally distributed errors).

- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Compute resources are given in Appendix B.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: The research conforms with the NeurIPS Code of Ethics.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

    Justification: Societal impacts are discussed in the Ethics Statement.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.

- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [Yes]

    Justification: The method is a safeguard for hazardous knowledge, and we release no hazardous data or model checkpoints.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: We cite all models, datasets and code we use and follow their licenses.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.
    - For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
    - If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
    - For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.

- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: The released code is documented in its README, which gives installation, training and evaluation instructions and the Apache-2.0 license.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: The paper does not involve crowdsourcing or research with human subjects.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The paper does not involve research with human subjects.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: LLMs generate the inoculation questions and grade the open-ended responses (Appendices A and C).

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.