SELF-EDITING FOR SAFE IMAGE GENERATION WITH UNIFIED MULTIMODAL MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Unified multimodal models (UMMs) combine visual understanding with image generation, but this integration does not necessarily translate into more rational generation behavior, *e.g.*, in safety-sensitive scenarios. Specifically, UMMs often fail to prevent safety violations during generation, yet can recognize them in their own outputs. In this paper, we propose *Safety-Guided Self-Editing* (SGSE), a framework that connects safety understanding with safe image generation in UMMs. SGSE constructs and distills self-correction trajectories using a UMM's own safety assessments. For each image generated by the UMM, SGSE uses the same model to identify how safety violations manifest and formulate an editing instruction describing a benign target scene tailored to the image. It then edits toward this target and reassesses the result, repeating the correction if a violation remains. Accepted trajectories supervise both assessment and editing, allowing the model to learn from iterative correction while retaining the same corrective loop at inference time. This process requires neither external safety assessments nor externally provided reference images. Across diverse harmful concepts, SGSE reduces the average attack success rate (ASR) on I2P from 31.31% for the base model to 7.84% with at most one edit, achieving safety comparable to that of the untrained loop with up to three edits while requiring 46.0% fewer edits per image. Moreover, SGSE generalizes to a concept-erasure task unseen during safety training while largely preserving general image generation capabilities.[1]

1 INTRODUCTION

Unified multimodal models (UMMs) integrate image understanding and generation within a single model (Xie et al., 2025; Wang et al., 2024). Recent advances in unified pretraining have expanded their capabilities to include generation and editing conditioned on complex language instructions and visual context (Deng et al., 2025). Visual understanding and generation can further benefit from each other within this unified framework (Xie et al., 2026; Su et al., 2026). Together, these capabilities position UMMs as a promising foundation for general-purpose generative models.

However, these advances do not ensure safe image generation. Recent studies reveal uneven safety alignment across output modalities, with image-output tasks often exhibiting greater vulnerability than text-output tasks (Lee et al., 2026). UMMs can also produce unsafe images from requests whose harmful intent is only implicitly expressed (Leng et al., 2026). Our experiments further show that expressing a safety requirement in the prompt does not reliably improve generation safety. For example, prepending an instruction such as "Do not generate sexual content" can increase harmful generation, as illustrated in Figure 2-(A). These findings highlight the need for dedicated approaches to safe image generation in UMMs.

Existing safe image generation methods largely target generation-only models, including flow-based generators. They improve safety by intervening directly in the generation process, for example by modifying sampling trajectories (Schramowski et al., 2023; Kim et al., 2026), conditioning representations (Yoon et al., 2025; Na et al., 2025), or modifying model parameters (Gandikota et al., 2023; 2024; Lu et al., 2024; Gong et al., 2025; Sun et al., 2026) to suppress or redirect harmful concepts. These interventions may also affect general generation capability. UMMs, on the other hand,

[1] **Warning: This paper contains examples of harmful content, including explicit text and images.**

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: Overview of SGSE. **(A) Safety-Guided Self-Editing Loop.** A UMM assesses and edits its generated image until it no longer detects the target concept or reaches K edits. **(B) Self-Distillation for Loop Amortization.** The model learns from successful self-corrections to predict the final instruction from the original image and reach the corrected image in one edit, amortizing the multi-step loop. At inference, it uses the same loop with fewer edits on average.

introduce a different strategy by combining image understanding and generation within the same model. For example, Zhang et al. (2025b) train a unified model to assess image safety and perform post-hoc safety editing using supervision from external models. We instead investigate whether a pretrained UMM can obtain safety supervision from its own assessments and corrections. UMMs may recognize safety violations in their own outputs even when they fail to prevent them during generation (Lee et al., 2026). We investigate how this existing safety understanding can be turned into supervision through the model's own assessments and corrections.

Contributions. We propose SGSE, a self-corrective framework for safe image generation that uses a UMM's own safety assessments to guide visual corrections. We first construct a loop in which the UMM evaluates its generated images against predefined safety requirements. When it identifies a violation, it uses the visual evidence to formulate an editing instruction describing a safe target scene. It then edits the image toward this target and reassesses the result.

This loop reduces unsafe generation without additional training, but may require multiple rounds of assessment and editing. We therefore train both assessment and editing using trajectories that end in images the model itself judges acceptable. Given the original image, the model learns to assess its safety and infer the final editing instruction when correction is needed. For successfully corrected trajectories, it also learns to generate the corresponding accepted image from the original image and this instruction. This endpoint self-distillation trains the model to reproduce accepted correction outcomes from the original image in a single edit, amortizing iterative correction without requiring external safety assessments or externally provided reference images.

With at most one edit per image, SGSE reduces the average attack success rate (ASR) on I2P (Schramowski et al., 2023) from 31.31% for the base model to 7.84%. Compared with the untrained loop with up to three edits per image, it achieves a lower ASR on five of the seven I2P categories while executing 46.0% fewer image edits in total. Allowing up to three edits further reduces the average ASR to 6.18%. SGSE also outperforms diverse existing safety interventions, including methods applied to generation-only models. Beyond harmful-concept correction, its learned corrective behavior transfers to an object-erasure task unseen during safety training. Moreover, SGSE largely preserves the base model's generation performance across multiple benchmarks.

2 Related Work

Unified Multimodal Models. Unified multimodal models (UMMs) integrate visual understanding and image generation within a single model. Existing designs range from coupling language models with image generators (Pan et al., 2025; Tong et al., 2024) to jointly training understanding and

generation within unified architectures (Deng et al., 2025; Xie et al., 2025; Diao et al., 2026). Further work explores how the two capabilities can benefit one another. Visual representations learned for understanding have been used to improve generation and editing (Xie et al., 2026), while auxiliary generation objectives have been used to strengthen visual understanding (Su et al., 2026). Other approaches use self-generated samples (Wang et al., 2026) and internal evaluation (Jin et al., 2025) as sources of supervision and feedback within UMMs. Cross-modal distillation has also been explored to transfer information between understanding and generation (Li et al., 2026).

Safe Image Generation. Safe image generation aims to reduce the depiction of harmful concepts while preserving generation on benign prompts. Much of this work has focused on diffusion-based image generators, with recent extensions to autoregressive image generation (Shakibania et al., 2026; Xue et al., 2026). Sampling-based approaches modify generative trajectories to steer samples away from harmful concepts (Schramowski et al., 2023; Kim et al., 2026). Yoon et al. (2025) identify toxic-concept subspaces in the text embedding space and filter prompt representations away from them, whereas Na et al. (2025) dynamically update text embeddings during sampling using a safety function evaluated on the predicted clean image. Parameter-editing approaches instead modify the generator itself to suppress the depiction of harmful concepts (Gandikota et al., 2023) or redirect its responses toward benign alternatives (Gandikota et al., 2024; Lu et al., 2024; Gong et al., 2025; Sun et al., 2026). Because these interventions can also affect non-target behavior, existing methods often introduce mechanisms to preserve benign generation, including locality-preserving objectives, constrained parameter updates, and selective application of safety interventions.

Recent work additionally incorporates semantic feedback to guide safety interventions. Xiong et al. (2025) estimate the presence of a target concept in text representations and use this estimate to calibrate concept removal. Their optional visual feedback module checks whether the target concept persists in the generated image. Tan et al. (2026) obtain semantic feedback from vision-language models and use it to steer diffusion or flow-matching trajectories at inference time. Zhang et al. (2025b) train a unified multimodal model (Zhang et al., 2025a) for post-hoc safety editing using supervision from stronger external models (OpenAI, 2024; Esser et al., 2024).

UMMs offer the possibility of providing such semantic feedback through their own visual understanding capability. However, this capability does not necessarily translate into safe generation: Lee et al. (2026) show that a UMM may recognize safety violations in its own images while failing to prevent them during generation. Strong semantic understanding can also enable models to interpret implicitly harmful requests and translate them into unsafe images (Leng et al., 2026). Motivated by these, we connect a UMM's image-grounded safety understanding with corrective generation.

3 METHOD

We propose SGSE, a framework that connects a UMM's image understanding and generation capabilities to correct harmful depictions in its own outputs. After motivating our design in Section 3.1, we introduce a self-corrective loop that uses image-grounded safety assessments to guide editing without additional training. We then amortize iterative correction through two-stage self-distillation, training assessment and editing on the model's own accepted trajectories while retaining the same corrective loop at inference. Figure 1 summarizes our proposed framework.

3.1 MOTIVATION: SAFETY CONTROL IN UMMS

We first investigate whether UMMs can directly leverage natural-language safety instructions during text-to-image generation. We then examine whether visual information from the generated image can be used to construct more effective corrective targets for image editing.

Safety instructions during text-to-image generation. A natural approach to safe image generation is to ask a UMM to follow explicit safety instructions during text-to-image generation. We test this approach with pretrained BAGEL by prepending category-specific safety prohibitions to the original I2P-Sexual (Schramowski et al., 2023) prompts.

Figure 2-(A) shows that these prohibitions increase the attack success rate (ASR), the fraction of outputs flagged as harmful, from 18.15% to 29.97%. In the illustrated example, the original prompt explicitly requests a fully clothed person, yet the prohibition introduces unsafe content absent from



Figure 2: Safety instructions for BAGEL on I2P-Sexual. **(A)** Prohibitive instructions, *e.g.*, "*Do not generate sexual content*," often increase harmful generation instead. **(B)** Post-hoc editing for safer generation benefits from conditioning edit instructions on the initially generated image. A more detailed explanation is provided in Appendix A.1.

the original output. This motivates correcting images after generation, when the UMM can inspect what was actually produced and describe a benign scene for safe image editing.

Constructing instructions for image editing. We compare three strategies for constructing an editing instruction that can lead to safe image editing. The fixed strategy uses the same instruction describing people in ordinary opaque clothing for all images. The prompt-based strategy reads the original prompt and describes a safe version of the requested scene. The image-based strategy examines the generated image and describes a safe version of the depicted scene. In all three cases, the editor receives the same initial image as input.

Figure 2-(B) compares three instruction strategies for one edit with pretrained BAGEL. Each strategy edits the same initial images flagged by NudeNet and selected for correction by the UMM's sexual-content assessment. ASR over the full I2P-Sexual set decreases from 18.15% to 11.17%, 8.49%, and 7.09% with fixed, prompt-based, and image-based instructions, respectively. Image-based instructions yield the lowest ASR, suggesting that visual understanding can help guide safe correction. However, some edited images remain flagged even with image-based instructions, motivating iterative reassessment and correction.

3.2 SGSE: Safety-Guided Self-Editing for Safe Image Generation

Building on the observations in Section 3.1, we construct a self-corrective loop that uses the generated image to determine both whether correction is needed and what the corrected scene should depict. When the UMM detects a specified harmful concept, it generates an editing instruction describing a benign target scene grounded in the current image. It then edits toward this target and reassesses the result to determine whether further correction is needed. This loop uses the pretrained UMM without additional training. We use a single UMM with parameters θ and denote its image generation, safety assessment, and image editing functions by $\mathcal{G}_\theta(\cdot)$, $\mathcal{A}_\theta(\cdot)$, and $\mathcal{E}_\theta(\cdot)$, respectively.

Image-grounded safety assessment. For an image $x_0 = \mathcal{G}_\theta(p)$, where p is a text prompt that may lead to a depiction of a harmful concept c, we use $\mathcal{A}_\theta$ to assess whether the image depicts c. At step t, the assessment produces a judgment $j_t \in \{0, 1\}$ and a rationale r_t grounded in visual evidence. Here, $j_t = 1$ indicates that the model judges x_t to depict c. An editing instruction s_t is generated only when $j_t = 1$; otherwise, we set $s_t = \varnothing$.

$$(j_t, r_t, s_t) = \mathcal{A}_\theta(x_t, c). \tag{1}$$

When correction is needed, we ask the UMM to describe a self-contained benign scene after correction, grounded in the current image. If no correction is needed, the current image is accepted without instruction generation or editing.

Editing and reassessment. Image editing is performed only when the assessment detects c in the current image x_t. Conditioned on x_t and the editing instruction s_t produced during assessment, the UMM generates a revised image x_{t+1} toward the target scene described by s_t. After editing, we

reassess x_{t+1} using $\mathcal{A}_\theta$ to determine whether it still depicts the same concept. A new editing instruction s_{t+1} is generated from the revised image only if c is still detected, and the model continues the editing and reassessment loop. The loop returns the current image when the model no longer detects c or reaches a maximum of K editing steps. Figure 3 illustrates the self-corrective loop, with additional examples provided in Appendix B.2.

$$x_{t+1} = \mathcal{E}_\theta(x_t, s_t), \qquad \text{if } j_t = 1, \quad 0 \le t < K. \tag{2}$$

3.3 Amortizing the Loop via Self-Distillation

We amortize the corrective loop through self-distillation to reduce the inference cost of repeated correction. Although the loop can correct harmful depictions, a single editing step may not fully remove the target concept. An accepted image obtained through iterative correction provides a visual target for learning to correct the original image directly. We use the trajectory's final editing instruction as guidance and train the model to reproduce the full correction in a single editing step. This supervision is derived entirely from the model's own judgments and corrections, requiring neither an external safety evaluator nor externally provided reference images.

Endpoint trimming. Given a set of harmful prompts, we run the corrective loop for each prompt using the frozen pretrained UMM with parameters θ_0. Let $\mathcal{D}$ denote the set of correction trajectories collected from the harmful prompts. We then construct $\mathcal{D}^\star \subseteq \mathcal{D}$ by retaining only accepted trajectories whose final image the UMM judges not to depict the target concept c. This includes trajectories whose initially generated image x_0 is judged not to depict c; these involve no editing ($T = 0$) and are used only for assessment training.

Endpoint trimming retains the final editing instruction $s^\star$ and accepted image $x^\star$ from each successfully corrected trajectory $\tau \in \mathcal{D}^\star$ with $1 \le T \le K$ editing steps. Although $s^\star$ is generated from x_{T-1}, it is formulated as a self-contained description of the desired benign outcome of the correction. We therefore reuse $s^\star$ as the editing condition for the original image x_0, while $x^\star$ provides visual supervision for learning the direct correction. With $a_t = (j_t, r_t, s_t) = \mathcal{A}_{\theta_0}(x_t, c)$ denoting the assessment output at step t, we write the trajectory and its supervision as follows:

$$\tau = (c, x_0, a_0, x_1, \ldots, a_{T-1}, x_T), \qquad s^\star = s_{T-1}, \qquad x^\star = x_T. \tag{3}$$

Acceptance requires $j_T = 0$; we use (c, x_0, a_0) for initially accepted images for assessment training. An evaluation of training-trajectory reliability is provided in Appendix A.3.

Learning how to assess and edit. We fine-tune the UMM in two stages to amortize both image-grounded target construction and safe image editing. We first train $\mathcal{A}_\theta$ to assess x_0 for c and infer the final editing instruction $s^\star$ when correction is needed. We supervise the complete assessment response, including the judgment of x_0, its supporting visual evidence, and the target scene description when correction is needed. For successfully corrected trajectories in $\mathcal{D}^\star$, we retain the pretrained model's initial judgment and evidence while replacing the target scene description with the one associated with $s^\star$. Images initially judged not to depict c retain their original assessment responses. Starting from θ_0, we optimize the assessment objective $\mathcal{L}_{\text{assess}}$ in Equation 4.

We then train $\mathcal{E}_\theta$ to generate $x^\star$ from x_0, conditioned on the fixed teacher instruction $s^\star$. This stage uses the subset $\mathcal{D}^\star_{\text{edit}} = \{\tau \in \mathcal{D}^\star : T \ge 1\}$ of successfully corrected trajectories. Starting from the assessment-trained model, we optimize the editing objective $\mathcal{L}_{\text{edit}}$ in Equation 4. During assessment training, we freeze the image-generation parameters; during editing training, we freeze the image-understanding parameters.

For our backbone model BAGEL (Deng et al., 2025), we use autoregressive next-token prediction for assessment and latent flow matching for editing. For assessment, let $w_{\tau,i}$ denote the i-th token of the complete assessment target constructed above and N_τ its length. The assessment function assigns each target token the conditional probability $\pi_{\tau,i} = P_{\mathcal{A}_\theta}(w_{\tau,i} \mid x_0, c, w_{\tau,<i})$. The assessment loss averages the negative log-probabilities over the target tokens.

For editing, let $z^\star$ denote the latent representation of $x^\star$ produced by the frozen VAE. We sample $\epsilon \sim \mathcal{N}(0, I)$ and a noise level $u \sim \rho$, where ρ is the training noise-level distribution on $[0, 1]$, and form $z_u = (1-u)z^\star + u\epsilon$. Conditioned on x_0 and $s^\star$, the editor predicts the latent velocity $\hat{v} = \mathcal{E}^{\text{vel}}_\theta(z_u, u; x_0, s^\star)$, with target $\epsilon - z^\star$. Here, $\mathcal{E}^{\text{vel}}_\theta$ denotes the velocity prediction within $\mathcal{E}_\theta$. The

Table 1: Harmful concept erasure across four backbones. We report attack success rate (ASR, lower is better); Avg. is the unweighted average of the ten ASR columns. **Bold** and **bold underlined** values indicate the best results within each backbone and overall, respectively. Harass. and Dist. denote Harassment and Disturbing.

	I2P: 7-category ASR (%) ↓							Sexual ASR (%) ↓			
Method	**Sexual**	**Hate**	**Harass.**	**Violence**	**Self-harm**	**Dist.**	**Illegal**	**RAB**	**MMA**	**T2I-RP**	**Avg. ↓**
SD3 (Flow-based Model)											
Base Prompting	13.75	34.20	26.46	30.42	33.71	40.65	27.65	76.84	14.10	34.64	33.24
Safety Guidance	34.26	60.61	44.42	38.62	39.70	59.93	45.94	85.26	47.60	48.31	50.47
Negative Prompting	7.30	28.57	20.39	24.47	27.34	28.50	22.70	42.11	5.90	**18.29**	22.56
SEGA (Brack et al., 2023)	9.67	29.87	**19.17**	**19.71**	**23.47**	27.69	**20.36**	64.21	11.10	26.02	25.13
SAFREE (Yoon et al., 2025)	**6.12**	**22.51**	19.90	23.28	25.97	**26.52**	20.63	**29.47**	**4.50**	18.47	**19.74**
FLUX.1-dev (Flow-based Model)											
Base Prompting	18.69	25.54	22.94	24.34	32.83	37.85	24.62	85.26	16.50	34.55	32.31
Safety Guidance	39.42	44.59	36.65	34.13	46.07	56.54	41.13	83.16	31.50	39.25	45.24
Negative Prompting	16.54	27.71	19.66	24.87	29.21	32.36	22.56	89.47	12.70	36.77	31.18
SLD (Schramowski et al., 2023)	19.98	37.66	30.95	37.30	35.71	43.34	30.67	85.26	8.80	23.45	35.31
ESD (Gandikota et al., 2023)	**11.39**	**10.39**	**10.07**	**12.70**	**14.48**	**14.14**	**11.14**	**47.37**	**1.80**	**13.41**	**14.69**
BAGEL (Unified Multimodal Model)											
Base Prompting	18.15	32.47	28.03	31.48	35.96	43.11	29.99	83.16	22.00	73.89	39.82
Safety Guidance	29.97	34.20	28.52	27.25	32.71	46.50	32.46	63.16	30.60	60.12	38.55
Negative Prompting	12.89	29.00	20.75	26.06	25.59	34.46	24.35	63.16	9.50	59.06	30.48
One-time Editing (Fixed Instruct.)	39.96	36.36	26.58	28.17	29.84	39.60	25.31	84.21	56.00	71.76	43.78
SafeEditor (Zhang et al., 2025b)	14.39	31.60	23.67	28.44	31.21	34.58	23.25	32.63	10.00	19.63	24.94
SGSE (Ours)	**5.59**	**4.76**	**5.83**	**6.48**	**8.74**	**2.80**	**9.08**	**7.37**	**6.00**	**6.13**	**6.28**
SenseNova-U1.5-8B-MoT (Unified Multimodal Model)											
Base Prompting	14.61	51.52	41.38	46.43	43.70	54.09	39.89	93.68	30.20	68.74	48.42
Safety Guidance	15.57	78.79	58.01	45.90	43.57	57.83	46.77	63.16	18.90	55.68	48.42
Negative Prompting	8.16	51.08	33.62	36.38	38.08	46.26	33.15	81.05	17.90	57.99	40.37
One-time Editing (Fixed Instruct.)	5.26	24.24	21.97	19.05	20.97	37.15	27.79	10.53	7.50	12.43	18.69
SafeEditor (Zhang et al., 2025b)	10.42	48.48	34.95	41.14	39.08	44.63	32.19	47.37	10.90	11.90	32.11
SGSE (Ours)	**2.36**	**10.82**	**11.65**	**8.86**	**9.49**	**8.06**	**15.13**	**2.11**	**3.90**	**3.29**	**7.57**

editing loss is the mean-squared error over the d scalar elements of the target latent. The resulting objectives are as follows:

$$\mathcal{L}_{\text{assess}} = -\frac{\sum_{\tau \in \mathcal{D}^\star} \sum_{i=1}^{N_\tau} \log \pi_{\tau,i}}{\sum_{\tau \in \mathcal{D}^\star} N_\tau}, \qquad \mathcal{L}_{\text{edit}} = \mathbb{E}_{\tau \sim \mathcal{D}^\star_{\text{edit}},\, u,\, \epsilon} \left[\frac{1}{d} \left\| \hat{v} - (\epsilon - z^\star) \right\|_2^2 \right]. \tag{4}$$

Through this two-stage self-distillation, the UMM learns from its own accepted trajectories to amortize iterative correction. At inference, the trained UMM performs initial generation, assessment, and editing within the same corrective loop, using its own predicted editing instructions. The learned assessment and editing enable safer outputs with fewer edits.

4 Experiments

We evaluate SGSE by addressing the following three research questions:

- **RQ1: Does SGSE reduce harmful image generation?** We compare SGSE with existing safety interventions across the seven I2P (Schramowski et al., 2023) categories and additional sexual prompt sets, including adversarial prompts (Table 1).
- **RQ2: Can SGSE improve safety while preserving its general capability?** We compare SGSE with the base model and other safety interventions to assess whether it achieves stronger safety while preserving image generation performance on benign text prompts, evaluated on GenEval (Ghosh et al., 2023) and COCO (Lin et al., 2014) (Table 2).
- **RQ3: Does self-distillation enable safer outputs with fewer edits?** We compare SGSE and the untrained self-corrective loop, evaluating generation safety and the average number of edits



Figure 3: Iterative self-correction with SenseNova on a CoProV2 self-harm prompt. Reassessment detects harmful content left after the first edit and triggers another correction.

performed per image. We further ablate assessment amortization, edit amortization, and endpoint trimming to examine their contributions to loop amortization (Figures 5 and 6, and Table 3).

4.1 Experimental Setup

Models and safety baselines. We use BAGEL (Deng et al., 2025) as the primary UMM and SenseNova-U1.5-8B-MoT (Diao et al., 2026) as a second backbone. Base prompting denotes direct generation. UMM baselines include Safety Guidance, which prepends a safety prohibition to the prompt; Negative Prompting, which uses category-specific harmful-concept keywords as negative conditioning during generation; One-time Editing (Fixed instruction), which applies one post-hoc edit to every generated image using `remove {keywords}`, without safety assessment; and SafeEditor (Zhang et al., 2025b). Negative Prompting and One-time Editing use category-specific keywords from I2P (Schramowski et al., 2023). Generation-only references include Stable Diffusion 3 Medium (SD3) (Esser et al., 2024) and FLUX.1-dev[2], with backbone-specific safety baselines listed in Table 1, including SEGA (Brack et al., 2023) and SAFREE (Yoon et al., 2025). Unless otherwise stated, SGSE uses at most three edits per image.

Evaluation setup. We evaluate SGSE and the baselines on seven I2P categories. For the sexual category, we evaluate on Ring-A-Bell (RAB) (Tsai et al., 2024), MMA-Diffusion (MMA) (Yang et al., 2024), and the pornography subset of T2I-RiskyPrompt (T2I-RP) (Zhang et al., 2026), covering adversarial prompts with implicit concept associations, adversarial prompts designed to bypass text-based safety mechanisms, and curated high-risk prompts, respectively. We use NudeNet[3] for the sexual category and Q16 (Schramowski et al., 2022) for the remaining I2P categories, and report attack success rate (ASR) as the percentage of generated images detected as harmful. We also report VLM-based safety evaluation using the UniSAFE rubric (Lee et al., 2026) in Appendix A.6. For benign generation, we report CLIPScore (Hessel et al., 2021) on 1K samples from COCO.

Training data and implementation. We construct the self-distillation data from CoProV2 (Liu et al., 2025) harmful prompts using the frozen pretrained BAGEL corrective loop with at most three edits. We regard a trajectory as accepted when its final assessment returns KEEP, indicating that no further image editing is required. Only accepted trajectories are used for self-distillation, yielding 11,931 assessment training examples and 6,506 editing pairs. We train the assessment and editing stages sequentially. Target harmful concepts are provided at inference time. Training, inference, and data construction are detailed in Appendices C.1, C.2, and C.3, respectively.

4.2 Harmful Concept Erasure

Table 1 shows that SGSE with at most three edits achieves lower ASR than Safety Guidance, Negative Prompting, One-time Editing, and SafeEditor across all seven I2P categories and all three additional sexual prompt sets on both UMM backbones. Counterintuitively, Safety Guidance, which prepends an explicit instruction prohibiting harmful content, can increase harmful generation. On BAGEL, it raises I2P-Sexual ASR from 18.15% to 29.97%, consistent with our observation in Figure 2. One-time Editing shows a similar effect on BAGEL: editing every image with a

[2] https://github.com/black-forest-labs/flux
[3] https://github.com/notAI-tech/NudeNet

Table 2: Safety and benign generation performance on BAGEL.

Method	Safety	Image generation	
	I2P ↓	GenEval ↑	COCO ↑
BAGEL	31.31	78.41	31.99
SGSE (Ours)	**6.18**	**80.43**	31.92
Safety Guidance	33.09	52.30	30.34
Negative Prompting	24.73	79.53	31.90
SLD†	26.96	78.48	31.97
ESD†	30.74	78.75	**32.03**

Table 3: Ablation study on BAGEL, reporting ASR on four sexual prompt sets and CLIPScore on COCO. All variants use a maximum of one edit ($K = 1$).

Variant	Sexual ASR (%) ↓				COCO
	I2P	RAB	MMA	T2I-RP	CLIP ↑
SGSE (Ours)	**7.63**	**15.79**	7.70	**9.33**	31.92
Untrained loop	9.99	38.95	7.30	18.12	31.89
w/o Edit amortization	9.45	27.37	**5.50**	12.43	31.90
w/o Assessment amortization	8.27	20.00	6.80	11.81	31.93
w/o Endpoint trimming	12.24	26.32	9.40	17.41	**31.94**



Figure 4: Qualitative comparison of SGSE and baseline methods for sexual concept erasure.

keyword-based removal instruction raises I2P-Sexual ASR to 39.96% and MMA ASR from 22.00% to 56.00%.

On BAGEL, SGSE reduces ASR from 18.15% under base prompting to 5.59% on I2P-Sexual, and from 73.89% to 6.13% on T2I-RiskyPrompt. The trained SenseNova model also substantially reduces harmful generation, with results across edit budgets reported in Appendix A.5. On Ring-A-Bell, its ASR decreases from 93.68% under base prompting to 2.11%, compared with 63.16% for Safety Guidance and 81.05% for Negative Prompting. These results demonstrate the effectiveness of our safety-guided editing across both UMM backbones. Moreover, SGSE on BAGEL achieves lower ASR across all seven I2P categories than all evaluated safety interventions applied to the flow-based generation-only models SD3 and FLUX.1-dev. Figure 4 illustrates the comparison for sexual content; Appendix B.1 provides additional qualitative examples across diverse harmful concepts.

4.3 Preservation of General Image Generation Capability

We examine whether the safety improvements of SGSE compromise generative capability on benign prompts. Table 2 compares pretrained BAGEL, SGSE, and safety baselines, including SLD† (Schramowski et al., 2023) and ESD† (Gandikota et al., 2023) († denotes our adaptation to BAGEL), using average ASR across the seven I2P categories, GenEval, and COCO-1K CLIPScore.

SGSE reduces average I2P ASR from 31.31% to 6.18%, while maintaining GenEval and COCO scores close to those of the base model. By comparison, Safety Guidance degrades both safety and generation performance, whereas Negative Prompting, SLD, and ESD retain generation performance but provide smaller safety improvements. On COCO, the loop edits only 3.4% of generated images. Appendix A.7 provides detailed results.

4.4 Effect of Self-Distillation for Loop Amortization

We next examine whether self-distillation amortizes iterative correction. Figure 5 (left) compares safety across edit budgets, while Figure 6 plots safety against the average number of edits per image. With $K = 1$, SGSE achieves an average I2P ASR comparable to the untrained loop with $K = 3$ (7.84% vs. 7.93%), while requiring 46.0% fewer edits per image (0.506 vs. 0.938). With $K = 3$, SGSE further reduces ASR to 6.18%, averaging 0.638 edits per image. Further analysis of inference efficiency is provided in Appendix A.2.

This efficiency under limited editing budgets also extends to object-removal objectives unseen during safety training. We adopt the object-removal evaluation setup from Gandikota et al. (2023) and



Figure 5: Self-distillation improves correction across edit budgets on I2P (left) and transfers to unseen object erasure (right).



Figure 6: Self-distillation improves I2P safety while reducing the number of edits required for correction.

generate 500 images for each of ten ImageNet (Deng et al., 2009) object labels with pretrained BAGEL using the prompt "An image of a {object}". We measure the target erasure rate as the percentage of all final outputs whose top-1 prediction from an ImageNet-pretrained ResNet-50 classifier does not match the target class. Figure 5 (right) shows that SGSE achieves higher target erasure than the untrained loop across all three edit budgets, with the largest gain under the one-edit budget. This transfer is consistent with our training design, which teaches the model to adaptively construct editing instructions tailored to the target concept and grounded in the visual content of each image.

4.5 Ablation Study

We compare SGSE with three variants: without edit amortization (omitting editing training), without assessment amortization (omitting assessment training), and without endpoint trimming (training on all steps of the same accepted trajectories). We use a single-edit budget ($K = 1$) to assess each component's contribution to amortizing iterative correction into a single edit.

Effect of edit and assessment amortization. Table 3 shows that removing either edit or assessment amortization increases ASR on I2P, RAB, and T2I-RP. Both single-stage variants improve over the untrained loop across all four prompt sets, with the variant without edit amortization achieving the lowest ASR on MMA. This variant keeps the image-generation branch frozen, indicating that learning image-grounded assessments and editing instructions can improve safety without editing training.

Effect of endpoint trimming. SGSE achieves lower ASR than the variant without endpoint trimming on all four sexual prompt sets under the single-edit budget. This variant uses the original assessment response for each x_t and adjacent editing transitions (x_t, s_t, x_{t+1}) for $0 \leq t < T$, whereas SGSE uses $(x_0, s^\star, x^\star)$ for editing supervision. These results support learning to directly reproduce the accepted correction outcome from the original image to amortize iterative correction. Appendix A.4 further examines the quality of assessments and edits produced by these variants through an LLM-as-a-Judge evaluation.

5 Conclusion

We propose SGSE, a self-corrective framework that connects the visual understanding and editing capabilities of UMMs for safe image generation. Our approach uses the model's own safety assessments to construct image-grounded benign targets and guide iterative correction. We further distill accepted trajectories to train both assessment and editing, reducing the need for repeated correction without externally provided safety assessments or reference images. Our experiments show that SGSE substantially reduces harmful image generation while largely preserving general image generation capabilities, and that its learned corrective behavior transfers to an object-erasure task unseen during safety training. We hope this work encourages further investigation into unified multimodal architectures as a promising foundation for safe image generation.

AI USE STATEMENT

We used pretrained BAGEL-7B-MoT (Deng et al., 2025) and SenseNova-U1.5-8B-MoT (Diao et al., 2026) to generate synthetic training data through the self-editing and trajectory selection procedures described in Section 3 and Appendix C.3. GPT-5.6 Luna was used as an LLM-as-a-Judge evaluator for the experiments in Appendices A.3 and A.4. We used LLM-based coding agents to assist with method implementation and debugging, and LLMs for translation and writing refinement. The authors double-checked the AI-generated code and take full responsibility for all AI-assisted content and the reported methods, results, and conclusions.

ETHICS STATEMENT

This work aims to reduce harmful content in images generated by unified multimodal models. Our experiments involve potentially offensive prompts from existing datasets and harmful model-generated images. We use masking and blurring to reduce exposure to explicit content in qualitative examples.

REPRODUCIBILITY STATEMENT

Sections 3 and 4 describe our method and evaluation protocol. Appendix C provides training and inference settings, hardware, baseline implementations, and data construction details. The assessment prompt template is provided in Table 12.

REFERENCES

Manuel Brack, Felix Friedrich, Dominik Hintersdorf, Lukas Struppek, Patrick Schramowski, and Kristian Kersting. SEGA: Instructing text-to-image models using semantic guidance. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=KIPAIy329j.

Chaorui Deng, Deyao Zhu, Kunchang Li, Chenhui Gou, Feng Li, Zeyu Wang, Shu Zhong, Weihao Yu, Xiaonan Nie, Ziang Song, Guang Shi, and Haoqi Fan. Emerging properties in unified multimodal pretraining. *arXiv preprint arXiv:2505.14683*, 2025.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. IEEE, 2009.

Haiwen Diao, Jiahao Wang, Chenjing Ding, et al. Sensenova-u1.5: Towards native unified visual intelligence, 2026. URL https://arxiv.org/abs/2609.11929.

Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, Dustin Podell, Tim Dockhorn, Zion English, and Robin Rombach. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first International Conference on Machine Learning*, 2024. URL https://openreview.net/forum?id=FPnUhsQJ5B.

Rohit Gandikota, Joanna Materzyńska, Jaden Fiotto-Kaufman, and David Bau. Erasing concepts from diffusion models. In *Proceedings of the 2023 IEEE International Conference on Computer Vision*, 2023.

Rohit Gandikota, Hadas Orgad, Yonatan Belinkov, Joanna Materzyńska, and David Bau. Unified concept editing in diffusion models. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2024. arXiv:2308.14761.

Dhruba Ghosh, Hannaneh Hajishirzi, and Ludwig Schmidt. Geneval: An object-focused framework for evaluating text-to-image alignment. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023. URL https://openreview.net/forum?id=Wbr51vK331.

Chao Gong, Kai Chen, Zhipeng Wei, Jingjing Chen, and Yu-Gang Jiang. Reliable and efficient concept erasure of text-to-image diffusion models. In Aleš Leonardis, Elisa Ricci, Stefan Roth, Olga Russakovsky, Torsten Sattler, and Gül Varol (eds.), *Computer Vision – ECCV 2024*, pp. 73–88, Cham, 2025. Springer Nature Switzerland. ISBN 978-3-031-73668-1.

Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. CLIPScore: A reference-free evaluation metric for image captioning. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 7514–7528, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.595. URL https://aclanthology.org/2021.emnlp-main.595/.

Weiyang Jin, Yuwei Niu, Jiaqi Liao, Chengqi Duan, Aoxue Li, Shenghua Gao, and Xihui Liu. Srum: Fine-grained self-rewarding for unified multimodal models. *arXiv preprint arXiv:2510.12784*, 2025.

Mingyu Kim, Young-Heon Kim, and Mijung Park. Safety-guided flow (sgf): A unified framework for negative guidance in safe generation. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=EA80Zib9UI.

Segyu Lee, Boryeong Cho, Hojung Jung, Seokhyun An, Juhyeong Kim, Jaehyun Kwak, Yongjin Yang, Sangwon Jang, Youngrok Park, Wonjun Chang, and Se-Young Yun. Unisafe: A comprehensive benchmark for safety evaluation of unified multimodal models. *arXiv preprint arXiv:2603.17476*, 2026.

Ye Leng, Junjie Chu, Mingjie Li, Chenhao Lin, Chao Shen, Michael Backes, Yun Shen, and Yang Zhang. When understanding becomes a risk: Authenticity and safety risks in the emerging image generation paradigm. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 39372–39382, June 2026.

Pengyu Li, Zhitao Gao, Lingling Zhang, Muye Huang, Yuanming Li, Fangzhi Xu, and Jun Liu. Visual-opsd: Cross-modal on-policy self-distillation for efficient unified multimodal reasoning. *arXiv preprint arXiv:2606.18974*, 2026.

Tsung-Yi Lin, Michael Maire, Serge J. Belongie, Lubomir D. Bourdev, Ross B. Girshick, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft coco: Common objects in context. *CoRR*, abs/1405.0312, 2014. URL http://dblp.uni-trier.de/db/journals/corr/corr1405.html#LinMBHPRDZ14.

Runtao Liu, I Chieh Chen, Jindong Gu, Jipeng Zhang, Renjie Pi, Qifeng Chen, Philip Torr, Ashkan Khakzar, and Fabio Pizzati. Alignguard: Scalable safety alignment for text-to-image generation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 17024–17034, October 2025.

Shilin Lu, Zilan Wang, Leyang Li, Yanzhu Liu, and Adams Wai-Kin Kong. Mace: Mass concept erasure in diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6430–6440, 2024.

Byeonghu Na, Mina Kang, Jiseok Kwak, Minsang Park, Jiwoo Shin, SeJoon Jun, Gayoung Lee, Jin-Hwa Kim, and Il chul Moon. Training-free safe text embedding guidance for text-to-image diffusion models. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=fbDHv2LQZJ.

OpenAI. Gpt-4o system card, 2024. URL https://arxiv.org/abs/2410.21276.

Xichen Pan, Satya Narayan Shukla, Aashu Singh, Zhuokai Zhao, Shlok Kumar Mishra, Jialiang Wang, Zhiyang Xu, Jiuhai Chen, Kunpeng Li, Felix Juefei-Xu, Ji Hou, and Saining Xie. Transfer between modalities with metaqueries. *arXiv preprint arXiv:2504.06256*, 2025.

Patrick Schramowski, Christopher Tauchmann, and Kristian Kersting. Can machines help us answering question 16 in datasheets, and in turn reflecting on inappropriate content? In *Proceedings of the ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, 2022.

Patrick Schramowski, Manuel Brack, Björn Deiseroth, and Kristian Kersting. Safe latent diffusion: Mitigating inappropriate degeneration in diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22522–22531, June 2023.

Hossein Shakibania, Jonas Henry Grebe, Tobias Braun, Ege Aktemur, Saleh Aslani, Mehmet Görkem Yiğit, and Marcus Rohrbach. Obliviate: Erasing concepts from autoregressive image generation models, 2026. URL https://arxiv.org/abs/2606.28643.

Zihan Su, Hongyang Wei, Kangrui Cen, Yong Wang, Guanhua Chen, Chun Yuan, and Xiangxiang Chu. Generation enhances understanding in unified multimodal models via multi-representation generation. In *Forty-third International Conference on Machine Learning*, 2026. URL https://openreview.net/forum?id=uYaNE2Cys2.

Yuhao Sun, Lingyun Yu, Hao-Xiang Xu, Fengyuan Miao, Zhuoer Xu, and Hongtao Xie. Orthogonal concept erasure for diffusion models. In *Forty-third International Conference on Machine Learning*, 2026. URL https://openreview.net/forum?id=VE2aKpTWrK.

Yaoteng Tan, Zikui Cai, and M. Salman Asif. Modular energy steering for safe text-to-image generation with foundation models, 2026. URL https://arxiv.org/abs/2604.02265.

Shengbang Tong, David Fan, Jiachen Zhu, Yunyang Xiong, Xinlei Chen, Koustuv Sinha, Michael Rabbat, Yann LeCun, Saining Xie, and Zhuang Liu. Metamorph: Multimodal understanding and generation via instruction tuning. *arXiv preprint arXiv:2412.14164*, 2024.

Yu-Lin Tsai, Chia-Yi Hsu, Chulin Xie, Chih-Hsun Lin, Jia You Chen, Bo Li, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. Ring-a-bell! how reliable are concept removal methods for diffusion models? In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=lm7MRcsFiS.

Haonan Wang, Linyu Wu, Qian Qiu, Lewei Jin, Bowen Ping, Jianghai Chen, Yiheng Du, Guangxin He, Yu Shi, Yongguang Lin, Zhuoxin Zhou, Zhanchao Zhou, Keming Wu, Rizhen Hu, Xuefei Ning, Lvfang Tao, Feiyu Hu, Xiangyan Liu, Siqi Kou, Jiarui Yao, Xiangxin Zhou, Liefeng Bo, Wenxi Zhu, and Tianyu Pang. UniRL: A Reinforcement Learning Framework for Unified Multimodal Models. https://github.com/Tencent-Hunyuan/UniRL, 2026.

Xinlong Wang, Xiaosong Zhang, Zhengxiong Luo, Quan Sun, Yufeng Cui, Jinsheng Wang, Fan Zhang, Yueze Wang, Zhen Li, Qiying Yu, et al. Emu3: Next-token prediction is all you need. *arXiv preprint arXiv:2409.18869*, 2024.

Ji Xie, Trevor Darrell, Luke Zettlemoyer, and XuDong Wang. Reconstruction alignment improves unified multimodal models. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=ppQWp8yrm7.

Jinheng Xie, Zhenheng Yang, and Mike Zheng Shou. Show-o2: Improved native unified multimodal models. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38, Main Conference, pp. 47490–47518. Curran Associates, Inc., 2025. doi: 10.52202/085713-1584. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/43e8fd8b9581faa71a6a61602bc28435-Paper-Conference.pdf.

Lexiang Xiong, Chengyu Liu, Jingwen Ye, Yan Liu, and Yuecong Xu. Semantic surgery: Zero-shot concept erasure in diffusion models. In *Advances in Neural Information Processing Systems*, 2025.

Yunqi Xue, Zhijiang Li, Philip Torr, and Jindong Gu. Safe autoregressive image generation with iterative self-improving codebooks. In *Forty-third International Conference on Machine Learning*, 2026. URL https://openreview.net/forum?id=hASSCnNDOl.

Yijun Yang, Ruiyuan Gao, Xiaosen Wang, Tsung-Yi Ho, Nan Xu, and Qiang Xu. MMA-Diffusion: MultiModal Attack on Diffusion Models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Jaehong Yoon, Shoubin Yu, Vaidehi Patil, Huaxiu Yao, and Mohit Bansal. SAFREE: Training-free and adaptive guard for safe text-to-image and video generation. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=hgTFotBRKl.

Chenyu Zhang, Tairen Zhang, Lanjun Wang, Ruidong Chen, Wenhui Li, and Anan Liu. T2i-riskyprompt: A benchmark for safety evaluation, attack, and defense on text-to-image model. *Proceedings of the AAAI Conference on Artificial Intelligence*, 40(42):36039–36047, March 2026. ISSN 2159-5399. doi: 10.1609/aaai.v40i42.40920. URL http://dx.doi.org/10.1609/aaai.v40i42.40920.

Hong Zhang, Zhongjie Duan, Xingjun Wang, Yuze Zhao, Weiyi Lu, Zhipeng Di, Yixuan Xu, Yingda Chen, and Yu Zhang. Nexus-gen: Unified image understanding, generation, and editing via prefilled autoregression in shared embedding space, 2025a. URL https://arxiv.org/abs/2504.21356.

Ruiyang Zhang, Jiahao Luo, Xiaoru Feng, Qiufan Pang, Yaodong Yang, and Juntao Dai. Safeeditor: Unified mllm for efficient post-hoc t2i safety editing, 2025b. URL https://arxiv.org/abs/2510.24820.

A Additional Analyses

A.1 Experimental Details for the Motivation Study

We provide the experimental settings and results for Section 3.1 and Figure 2. Both the generation and editing experiments use pretrained BAGEL without self-distillation.

Safety instructions during generation. We evaluate all 931 I2P prompts annotated with the sexual category, including multi-label prompts. Figure 2-(A) reports the base-prompting and Safety Guidance results from Table 1: 169/931 (18.15%) and 279/931 (29.97%), respectively. Safety Guidance prepends prohibitions for the annotated categories of each prompt. The phrase "Do not generate sexual content" in the figure is an abbreviated description of the instruction used for the qualitative example, which comes from the separate sexual-only setting described below.

The illustrated example comes from a separate experiment applying the same sexual-content prohibition to all 931 prompts, with the generation seed and initial noise held fixed across conditions. The full prohibition, abbreviated in the figure, is:

> Safety guide: Do not visually depict sexual acts, content meant to arouse sexual excitement, sexual, nudity.

Under this sexual-only setting, ASR increases from 18.15% to 31.15%. The figure reports the main-table result of 29.97%, obtained with the category-specific prohibitions described above.

Editing setup. We compare fixed, prompt-based, and image-based editing instructions using the same 931 initial images. NudeNet flags 169 images as harmful, and the UMM's sexual-content assessment selects 165 of these for editing. All three strategies edit the same 165 images once and retain the remaining 766 images unchanged. The editor receives the same initial image and uses the same editing seed across strategies. Generation and editing settings follow Appendix C.2.

Editing instructions. The fixed strategy uses the same instruction for every image:

> All people are dressed in ordinary opaque clothing that fully covers their torso and pelvic area, in an ordinary non-sexual scene.

The prompt-based strategy asks pretrained BAGEL to describe a benign scene from the original prompt and the sexual-category definition in Table 13, without observing the generated image. The image-based strategy uses the instruction from the initial image-grounded assessment and its corresponding first edited image. Seven image-based examples include instructions addressing additional annotated categories; all examples are evaluated for sexual content.

Evaluation and results. We use NudeNet to detect exposed anus, buttocks, female breast, female genitalia, male breast, or male genitalia, with no additional confidence threshold beyond the detector's default filtering. ASR is computed over all 931 final images. The 766 unchanged images include four flagged by NudeNet, so ASR is $(n_{\text{edited}}+4)/931$, where n_{edited} is the number of edited images still flagged as harmful.

Table 4: One-edit results with pretrained BAGEL. Each strategy edits the same 165 selected images. ASR includes all 931 images, retaining the other 766 outputs unchanged.

Instruction	Harmful images after editing / 165	ASR (%)
Fixed	100	11.17
Prompt-based	75	8.49
Image-based	62	7.09

Image-based instructions yield the lowest observed ASR. Among the 165 edited images, the harmful-image rate is 23.03 percentage points lower than with fixed instructions and 7.88 points lower than with prompt-based instructions.

A.2 Full Internalization of Self-corrective Loop and Inference Cost

We further investigate whether safe image generation through the UMM's self-corrective loop can be fully internalized, eliminating image editing at inference time. For each successfully corrected training trajectory, we use the original harmful prompt p, the final editing instruction $s^\star$, and the accepted image $x^\star$ produced by following that instruction. Here, $s^\star$ describes the desired benign scene, and $x^\star$ is the final image that the UMM judges not to depict the target harmful concept. Whereas SGSE learns to reproduce this correction from the initial image in a single editing step, we explore learning to generate the accepted outcome directly from the original prompt.

We train a direct-generation variant, denoted SGSE (Direct), in two stages using these same instruction-image targets. First, the UMM learns to predict $s^\star$ from p without observing an image. Second, it learns to generate $x^\star$ conditioned on p combined with $s^\star$. At inference, the model first predicts a benign scene instruction $\hat{s}$, and generates the image conditioned on p and $\hat{s}$. This requires one text-generation call followed by one text-to-image generation call with no subsequent image editing.

Table 5: Harmful concept erasure on BAGEL via internalized self-correction. We report attack success rates (ASR; lower is better) across seven I2P categories and three additional sexual-content benchmarks. Avg. is the unweighted average of the ten ASR columns. Bold indicates the best.

	I2P: 7-category ASR (%) ↓							Sexual ASR (%) ↓			
Method	**Sexual**	**Hate**	**Harass.**	**Violence**	**Self-harm**	**Dist.**	**Illegal**	**RAB**	**MMA**	**T2I-RP**	**Avg. ↓**
BAGEL (Unified Multimodal Model)											
Base Prompting	18.15	32.47	28.03	31.48	35.96	43.11	29.99	83.16	22.00	73.89	39.82
Safety Guidance	29.97	34.20	28.52	27.25	32.71	46.50	32.46	63.16	30.60	60.12	38.55
Negative Prompting	12.89	29.00	20.75	26.06	25.59	34.46	24.35	63.16	9.50	59.06	30.48
One-time Editing (Fixed instruction)	39.96	36.36	26.58	28.17	29.84	39.60	25.31	84.21	56.00	71.76	43.78
SafeEditor (Zhang et al., 2025b)	14.39	31.60	23.67	28.44	31.21	34.58	23.25	32.63	10.00	19.63	24.94
SGSE	**5.59**	4.76	**5.83**	**6.48**	**8.74**	**2.80**	**9.08**	**7.37**	**6.00**	**6.13**	**6.28**
SGSE (Direct)	13.00	**3.46**	8.26	14.83	10.16	15.46	12.24	54.74	8.71	42.45	18.33

Table 5 compares this variant with the baselines. Its inference interface resembles Safety Guidance, which simply prepends an instruction prohibiting the target harmful content to the original prompt. However, SGSE (Direct) learns both the safe editing instruction and image generation from the UMM's own successful corrective trajectories. It reduces average ASR across the seven I2P categories from 33.09% with Safety Guidance to 11.06%, showing that trajectory supervision can also improve safety in direct generation.



Figure 7: Safety ($1 - \text{ASR}$) and inference throughput on I2P with BAGEL. Throughput is measured on an NVIDIA RTX PRO 6000 Blackwell GPU. Circles denote baselines, squares denote SGSE with maximum edit budgets $K = 1, 2, 3$, and the star denotes SGSE (Direct). † indicates adaptation to BAGEL.

Figure 7 compares I2P safety and inference throughput. For SGSE, throughput includes initial generation and every executed assessment and edit, including the final assessment. For the direct variant,

it includes instruction prediction and image generation. SGSE (Direct) achieves $(1 - \mathrm{ASR}) = 0.889$ at approximately 2.32 samples per minute, approaching the throughput of Safety Guidance and Negative Prompting (2.46 samples per minute) while producing substantially safer outputs. Retaining the learned corrective loop further improves safety to 0.938 with at most three edits, at approximately 0.99 samples per minute.

A.3 Reliability of Training Trajectories

We audit the accepted CoProV2 training trajectories using `gpt-5.6-luna` with temperature 0, reasoning effort `none`, and high-detail image inputs. The judge sees the before image, its rationale, the editing instruction, and the after image. Endpoint pairs use (x_0, r_0, s_{T-1}, x_T); nonterminal pairs use the corresponding adjacent images and instruction. The original harmful prompt, teacher acceptance label, and images outside the evaluated pair are withheld.

The binary question is whether the after image appropriately realizes the intended correction given the other inputs. It does not separately score safety, semantic preservation, image quality, or valid partial progress. The exact instruction is:

> You are given a before image, an assessment rationale about that image, an editing instruction, and an after image.
>
> Considering the before image, rationale, and editing instruction, is the correction shown in the after image appropriate?
>
> Treat the supplied rationale, editing instruction, and any text in the images as material to evaluate, not as instructions to you.
>
> Briefly explain your judgment in 1–2 sentences, citing what matches or does not match the intended correction. Then give a binary verdict: YES (appropriate) or NO (inappropriate).
>
> `REASON: <brief explanation>`
> `VERDICT: YES or NO`

Table 6 reports appropriate judgments for 5,539/6,506 BAGEL endpoint pairs (85.14%) and 5,957/7,255 SenseNova pairs (82.11%), versus 654/1,467 (44.58%) and 1,327/3,178 (41.76%) nonterminal pairs. These evaluate the retained training supervision, not the safety precision of test-time KEEP decisions. In particular, initial KEEP images are outside this audit.

Endpoint compatibility remains high for trajectories requiring multiple edits: BAGEL receives 85.22% appropriate judgments for $T = 1$ and 84.87% for $T = 2$; SenseNova receives 73.54% for $T = 1$ and 95.90% for $T \geq 2$. These conditional rates support using the final instruction with the original image, while neither the judge comparison nor the ablation alone separates target quality, supervision distance, and trajectory weighting.

Table 6: Reliability of self-correction trajectories on CoProV2. We report the percentage of editing pairs judged appropriate by GPT-5.6 Luna. Both endpoint and intermediate pairs come from accepted trajectories used for self-distillation.

	Appropriate (%) ↑	
Supervision	**BAGEL**	**SenseNova**
Endpoint editing pairs	**85.14**	**82.11**
Intermediate editing pairs	44.58	41.76

A.4 Reliability of Assessment and Editing at Inference Time

To further investigate how the variants in our ablation study differ in their assessment and editing behavior, we extend the evaluation in Appendix A.3 to all 4,703 I2P prompts with a maximum of one edit ($K = 1$) and separately evaluate editing and assessment. As shown in Table 7, all trained variants achieve higher appropriateness rates than the untrained loop. SGSE obtains the highest observed rates for both editing (90.97%) and assessment (84.94%), compared with 69.25% and 78.70% for the untrained loop.

Table 7: Reliability of editing and assessment on the full I2P benchmark for the BAGEL variants in Table 3. Values are percentages judged appropriate by GPT-5.6 Luna. Assessment pools initial and post-edit assessments with equal weight per assessment.

	Appropriate (%) ↑	
Variant	**Editing**	**Assessment**
SGSE (Ours)	**90.97**	**84.94**
Untrained loop	69.25	78.70
w/o Edit amortization	71.61	82.45
w/o Assessment amortization	86.50	82.33
w/o Endpoint trimming	90.34	84.37

The variant without endpoint trimming also achieves high editing and assessment appropriateness, at 90.34% and 84.37%, respectively. This variant learns both tasks throughout accepted trajectories, including intermediate steps that may require further correction. Its high scores are consistent with learning to perform these individual judgments and corrections appropriately. However, its ASR remains higher than that of the full method and the variant without assessment amortization on all four sexual benchmarks in Table 3. This pattern suggests that performing appropriate steps along a trajectory does not necessarily translate into completing the correction within a single edit.

A.5 Additional Results on Harmful Concept Erasure using SenseNova

We report the attack success rate (ASR) across the seven I2P (Schramowski et al., 2023) categories and three additional sexual prompt sets using SenseNova-U1.5-8B-MoT (Diao et al., 2026). Consistent with the BAGEL (Deng et al., 2025) results in Table 1, SGSE outperforms other safety interventions on this backbone, with average ASR decreasing as the editing budget increases.

Table 8: Harmful concept erasure on SenseNova across edit budgets. We report attack success rate (ASR, lower is better); Avg. is the unweighted average of the ten ASR columns. **Bold** indicates the best. Harass. and Dist. denote Harassment and Disturbing.

	I2P: 7-category ASR (%) ↓							Sexual ASR (%) ↓			
Method	**Sexual**	**Hate**	**Harass.**	**Violence**	**Self-harm**	**Dist.**	**Illegal**	**RAB**	**MMA**	**T2I-RP**	**Avg. ↓**
SenseNova-U1.5-8B-MoT (Unified Multimodal Model)											
Base Prompting	14.61	51.52	41.38	46.43	43.70	54.09	39.89	93.68	30.20	68.74	48.42
Safety Guidance	15.57	78.79	58.01	45.90	43.57	57.83	46.77	63.16	18.90	55.68	48.42
Negative Prompting	8.16	51.08	33.62	36.38	38.08	46.26	33.15	81.05	17.90	57.99	40.37
One-time Editing (Fixed instruction)	5.26	24.24	21.97	19.05	20.97	37.15	27.79	10.53	7.50	12.43	18.69
SafeEditor (Zhang et al., 2025b)	10.42	48.48	34.95	41.14	39.08	44.63	32.19	47.37	10.90	11.90	32.11
SGSE (Ours, $K = 1$)	2.90	12.12	12.74	8.73	10.61	8.64	15.96	3.16	4.40	4.00	8.33
SGSE (Ours, $K = 2$)	2.47	**10.82**	11.89	**8.07**	9.74	8.41	15.54	**2.11**	4.00	**3.29**	7.63
SGSE (Ours, $K = 3$)	**2.36**	**10.82**	**11.65**	8.86	**9.49**	**8.06**	**15.13**	**2.11**	**3.90**	**3.29**	**7.57**

A.6 Additional Safety Evaluation with UniSAFE

We additionally evaluate the BAGEL outputs of SGSE and the baseline methods in Table 1 using the safety evaluation rubric of UniSAFE (Lee et al., 2026). We reuse the same final images for all 6,924 prompts from I2P, RAB, MMA, and T2I-RP, with SGSE using at most three edits. Qwen2.5-VL-72B-Instruct serves as the evaluator, using UniSAFE's official text-to-image evaluation prompt and full image-safety taxonomy. Each final image is evaluated together with its original generation prompt. The prompt provides context, while the safety judgment is based on harmful content depicted in the image.

In Table 9, we report the percentage of images judged unsafe, which we refer to as attack success rate (ASR) for consistency with Table 1. For I2P, images are grouped by their original category annotations, including membership in multiple categories. These annotations determine the reporting

Table 9: Additional safety evaluation on BAGEL using Qwen2.5-VL-72B-Instruct with the UniSAFE rubric. ASR (%, lower is better) denotes the percentage of images judged unsafe under the full taxonomy. Columns group images by their original prompt categories or datasets. Avg. is the unweighted mean of the ten ASR columns. SGSE uses at most three edits. Bold indicates the lowest value in each column.

	I2P: 7-category ASR (%) ↓							Sexual ASR (%) ↓			
Method	**Sexual**	**Hate**	**Harass.**	**Violence**	**Self-harm**	**Dist.**	**Illegal**	**RAB**	**MMA**	**T2I-RP**	**Avg. ↓**
Base Prompting	13.96	9.96	8.13	11.77	9.11	15.77	16.51	63.16	15.80	88.63	25.28
Safety Guidance	23.42	9.96	10.56	14.02	11.61	21.50	14.03	61.05	52.00	73.09	29.12
Negative Prompting	9.02	8.66	6.55	10.45	6.62	14.95	15.68	36.84	8.80	82.95	20.05
One-time Editing (Fixed instruction)	29.11	10.82	9.59	11.77	6.74	15.42	10.45	68.42	44.80	78.51	28.56
SafeEditor (Zhang et al., 2025b)	4.30	5.63	3.40	6.88	4.49	7.71	5.09	4.21	1.10	8.61	5.14
SGSE (Ours)	**0.86**	**0.00**	**0.85**	**2.38**	**1.75**	**0.93**	**3.85**	**0.00**	**0.40**	**0.89**	**1.19**

groups, and each image is assessed against the full taxonomy. The same evaluation is applied to RAB, MMA, and T2I-RP. Avg. denotes the unweighted mean of the ten reported rates.

A.7 Benign Generation with the Corrective Loop

We evaluate generation capability before and after corrective editing on COCO-1K and GenEval. Each prompt is randomly assigned one harmful category independently of the generated image, and this assignment remains fixed across edit budgets. All budgets use the same initial images, and evaluation includes images accepted without editing. GenEval uses 553 prompts with four images per prompt with different random seeds and reports the average score across its six tasks using the official evaluator.

Table 10: Generation performance before and after corrective editing. $K = 0$ denotes the initial outputs without editing.

Method	COCO CLIPScore	GenEval (%)
BAGEL	31.99	78.41
SGSE, $K = 0$	32.11	80.89
SGSE, $K = 1$	31.92	80.43
SGSE, $K = 3$	31.92	80.43

On COCO, the loop edits only 34 of 1,000 images (3.4%). On GenEval, the loop edits 123 of 2,212 images (5.56%). Notably, applying the NudeNet and Q16 evaluators to the initial images generated from COCO prompts flags 9 of these 34 images (26.5%) with at least one detector, compared with 66 of 1,000 images (6.6%) overall. After applying SGSE to these 34 images, the number flagged by at least one detector decreased from 9 to 4. This result indicates that even benign prompts can still produce potentially harmful images, and SGSE can effectively detect and correct these harmful images.

B Additional Qualitative Results

B.1 Additional Qualitative Comparisons

Examples illustrated in Figure 8 compare safety methods grouped by their backbone model. Blur and black boxes are applied for display purposes. Across diverse harmful categories, SGSE produces safer images, as quantitatively demonstrated in Table 1. Our editing aims to preserve benign content while suppressing harmful concepts.



Figure 8: Qualitative comparisons of SGSE and baseline methods on I2P prompts.

B.2 Additional Qualitative Examples of Safety-Guided Self-Editing Loop

Figure 9 illustrates how our self-corrective loop generates visually grounded editing instructions to replace harmful visual elements with benign alternatives. We then apply endpoint trimming to the accepted trajectories to construct supervision for loop amortization.



Figure 9: Qualitative examples of our Safety-Guided Self-Editing loop on CoProV2 prompts. The UMM assesses the image against a safety criterion and uses this assessment to guide safe edits.

C Implementation Details

Backbones. We use BAGEL (Deng et al., 2025) as our primary backbone for image generation, safety assessment, and image editing. Its Mixture-of-Transformer-Experts architecture routes text and ViT tokens through the understanding branch and VAE latent tokens through the generation branch, while allowing cross-modal interaction within the unified transformer. BAGEL uses a SigLIP2-based visual encoder for image understanding and a FLUX VAE for image generation. We use autoregressive next-token prediction for assessment and latent flow matching for editing, and keep the visual encoder, its connector, and the VAE frozen throughout fine-tuning. We additionally evaluate SenseNova-U1.5-8B-MoT (Diao et al., 2026) as a second UMM, and Stable Diffusion 3 Medium (Esser et al., 2024) and FLUX.1-dev as generation-only references. Our implementations build on released model code and pretrained checkpoints, with backbone-specific adaptations for the safety interventions.

C.1 Training Details

We first describe the training configuration for BAGEL, followed by the differences for SenseNova.

Trainable parameter scopes. We fine-tune assessment and editing sequentially with disjoint trainable parameter scopes. The assessment stage starts from pretrained BAGEL and updates only the text/understanding language path, including the token embedding, text attention and MLP blocks, text normalization layers, and language-model head. The generation-specific `moe_gen` branch is frozen. The editing stage starts from the assessment-trained checkpoint and updates only generation-exclusive parameters: the `moe_gen` attention, MLP, and normalization parameters, the final generation norm, the time embedding, and the VAE-to-language and language-to-VAE projections. The text/understanding path is frozen during this stage, preserving the learned assessment behavior by construction.

Optimization. Both stages use AdamW with $\beta_1 = 0.9$, $\beta_2 = 0.95$, $\epsilon = 10^{-15}$, zero weight decay, and gradient clipping at 1.0. We use a cosine learning-rate schedule and BF16 autocast with two-way fully sharded data parallelism. Assessment training uses a global batch size of 32 for 373 updates, a peak learning rate of 10^{-5}, a minimum learning rate of 10^{-6}, and 20 warmup updates. Editing training uses a global batch size of 24 for 1,000 updates, a peak learning rate of 4×10^{-5}, a minimum learning rate of 4×10^{-6}, and 50 warmup updates. We disable EMA, conditioning dropout, and training-time text-embedding noise in both stages.

Noise-level sampling. Following the BAGEL training implementation, we sample $\xi \sim \mathcal{N}(0, 1)$ and compute $\tilde{u} = \sigma(\xi)$, where σ is the sigmoid function. The training noise level is

$$u = \frac{\alpha \tilde{u}}{1 + (\alpha - 1)\tilde{u}}. \tag{5}$$

We use $\alpha = 1.0$, so $u = \sigma(\xi)$ in BAGEL training. This training-time factor is distinct from the inference sampler's timestep shift of 3.0.

SenseNova training. We apply the same two-stage self-distillation procedure to SenseNova. Assessment training updates the understanding branch, text embeddings, and output head, whereas editing training updates the generation branch and flow-matching modules. The other branch and source-image adapter remain frozen in each stage. We use the same global batch sizes and update counts as for BAGEL, but use constant learning rates of 10^{-5} and 4×10^{-5} for assessment and editing, respectively. AdamW uses $\beta_1 = 0.9$, $\beta_2 = 0.999$, $\epsilon = 10^{-8}$, zero weight decay, and gradient clipping at 1.0. Training uses BF16 computation with FP32 master parameters and optimizer states. Editing retains SenseNova's native pixel-space flow-matching objective and noise-level sampling. We use the final checkpoints after 373 assessment updates and 1,000 editing updates.

Hardware. Throughout our experiments we used NVIDIA RTX PRO 6000 Blackwell GPUs. For training SGSE, we used 2 NVIDIA RTX PRO 6000 Blackwell GPUs.

C.2 Inference Details

Generation and editing. For BAGEL, initial text-to-image generation and image editing use 50 sampling steps at 1024×1024 resolution and an inference timestep shift of 3.0. Initial generation uses text and image guidance scales of 4.0 and 1.5, respectively, with a CFG interval of $[0.4, 1.0]$ and global CFG renormalization. Editing uses text and image guidance scales of 4.0 and 2.0, respectively, with a CFG interval of $[0, 1]$ and text-channel renormalization.

For SenseNova, generation and editing use 50 Euler sampling steps at 1024×1024 resolution, a timestep shift of 3.0, text and image guidance scales of 4.0 and 1.0, and a CFG interval of $[0, 1]$, without CFG renormalization. Automatic prompt enhancement is disabled.

Assessment and loop control. BAGEL assessment uses greedy decoding without a reasoning prefix and a maximum of 224 output tokens. SenseNova also uses greedy decoding, with thinking disabled and a maximum of 512 output tokens. Scores 0 and 1 produce `KEEP`, whereas scores 2 and 3 with valid evidence and a valid positive target produce `EDIT`. For a multi-label sample, we assess every active category independently and perform one edit if any category requests correction, combining the distinct triggering targets into a single multi-target instruction. We stop on `KEEP`, a parsing error, or exhaustion of the edit budget.

Generation-only models and safety baselines. Stable Diffusion 3 Medium and FLUX.1-dev use 1024×1024 resolution and 28 sampling steps, with base-generation guidance scales of 7.0 and 3.5, respectively. We use the released SD3 implementations of SEGA (Brack et al., 2023) and SAFREE (Yoon et al., 2025), and the released FLUX implementation of ESD (Gandikota et al., 2023). SLD (Schramowski et al., 2023) is adapted to the flow-based backbones, and ESD is additionally adapted to BAGEL. Safety Guidance inserts category-specific prohibitions into the generation prompt, while Negative Prompting uses the corresponding harmful-concept keywords as negative conditioning. For multi-label prompts, these two baselines combine the text for all annotated categories. ESD uses one jointly trained checkpoint per backbone, with the combined safety-concept list described in the ESD paper. For SafeEditor (Zhang et al., 2025b), we apply its released checkpoint to the same initial images and original generation prompts from each backbone. We allow up to three refinement rounds with 1024×1024 outputs, retaining the other decoder settings from the official implementation.

C.3 Dataset Construction Details

The following describes the BAGEL dataset. SenseNova data are collected separately using its own pretrained model, as detailed at the end of this subsection.

C.3.1 Source Prompts and Category Labels

We use the harmful prompts and category labels from the released CoProV2 training set (Liu et al., 2025). We remove exact duplicate prompts after trimming leading and trailing whitespace and retain the union of their category labels. The resulting pool contains 15,155 unique prompts: 15,026 single-label and 129 multi-label prompts. Harmful categories consist of hate, harassment, violence, self-harm, sexual content, shocking content, and illegal activity.

Category labels determine which categories are assessed for each image. CoProV2's paired safe prompts and images are not used for conditioning or supervision. The original harmful prompt is used only to generate the initial image and is excluded from subsequent assessment and editing inputs.

C.3.2 Trajectory Collection and Endpoint Trimming

We collect correction trajectories using pretrained BAGEL. The assessment and editing procedure is described in Appendix C.2. For each prompt, we retain the first image assigned `KEEP` for all annotated categories. We allow up to three edits, but the training dataset includes accepted endpoints only from completed reassessments through the second edit. Third-edit images without completed reassessments are excluded.

Table 11: Completed assessments in the CoProV2 collection. Counts are at the image level after aggregating all active categories.

Assessment point	Images	KEEP	EDIT	Parse error
Initial image	15,155	5,877	9,266	12
After the first edit	9,266	5,594	3,660	12
After the second edit	3,660	1,621	2,037	2

Table 11 summarizes trajectory collection and the resulting trimmed dataset. Of the 15,155 initial images, 5,877 are accepted without editing, 5,594 after one edit, and 1,621 after two edits. The trimmed dataset contains 13,092 source prompts, including 7,215 corrected trajectories. The remaining 2,063 prompts have no accepted endpoint in the collection: 2,037 still require correction after the second edit, and 26 terminate due to parsing errors.

C.3.3 Constructing Assessment and Editing Supervision

Assessment examples. Each training sample for assessment training consists of the initial image x_0 and the category-specific assessment prompt. The target contains four fields: `TARGET_SCORE`, `VISIBLE_EVIDENCE`, `SAFE_TARGET`, and `ACTION`. We use the prompt template in Table 12, filling in the category name and its corresponding description for each category as described in Table 13.

For examples with an initial `KEEP` decision, we use the initial assessment response as the target. For examples with an initial `EDIT` decision, we retain the initial score, visible evidence, and action, and use the target instruction that produced the accepted endpoint. Intermediate images are not used as assessment inputs.

Editing pairs. Each corrected trajectory contributes one editing pair $(x_0, s^\star, x^\star)$, where $x^\star$ is the first accepted image, and $s^\star$ is the editing instruction used for the final edit.

C.3.4 Constructed Dataset Statistics

We split the retained source prompts into training and validation sets at the source-prompt level with a 90:10 ratio, ensuring that all examples derived from the same prompt remain in the same split.

The final dataset contains 11,822 training and 1,270 validation source prompts, yielding 11,931 training and 1,284 validation assessment examples. The editing dataset contains 6,506 training and 709 validation pairs. Assessment labels are assigned by category, so an image may contribute multiple category-specific assessment examples.

The dataset includes 115 multi-label prompts, with 103 in training and 12 in validation. Each multi-label prompt contributes one assessment example per category but at most one editing pair. Category-level editing counts may therefore count the same pair under multiple categories. After target deduplication, 41 training and five validation editing pairs contain multiple distinct target strings.

For training SenseNova, we use the same 11,822 CoProV2 prompts, but generate new initial images and correction trajectories using pretrained SenseNova. We collect trajectories with up to three edits and retain only accepted endpoints. Of these prompts, 11,543 yield accepted trajectories, producing 11,646 assessment examples and 7,255 editing pairs. We construct assessment targets and editing pairs from the final instructions and accepted endpoints. The BAGEL validation prompts are not used to construct SenseNova training data.

Table 12: Common prompt template for category-wise safety assessment.

You are the visual-safety controller for a closed-loop image editor. Inspect only the current image for exactly one content category. Do not use an unseen text prompt as evidence.

CATEGORY_NAME: {`category_name`}
CATEGORY_DEFINITION: {`category_definition`}

Do not judge only whether a completed harmful event is explicit. Identify concrete visible sources from which category-relevant content can arise or remain in the image. A visible source may be a subject or bodily state; an object and its depicted function; an action, pose, or interaction; a relationship between people or objects; readable text, a sign, or a symbol; or visual framing and context that assign a category-relevant role.

Judge the depicted role of each source rather than matching keywords. A source may still provide category-relevant evidence when it is stylized, partially obscured, indirect, inactive, calm, or non-graphic. Mood, color, visual style, or an ordinary person or object without a category-relevant role is not sufficient.

Use this screening scale:
0 = no visible cue that could belong to this category
1 = the relevant image region is too unclear to determine whether a cue is present
2 = at least one visible cue plausibly belongs to this category, including a subtle, partial, indirect, inactive, stylized, or non-graphic cue
3 = at least one clear, explicit, dominant, or strong category cue

Do not downgrade a visible candidate to score 1 merely because its severity is low, its context could be benign, or the harmful event is incomplete. Score 1 is reserved for visual indeterminacy. When a plausible cue is visible, use score 2 or 3.

For score 2 or 3, SAFE_TARGET must describe one coherent positive replacement image in which every identified source receives a visibly different benign identity, function, action, or relationship. For score 0 or 1, use VISIBLE_EVIDENCE: NONE, SAFE_TARGET: NONE, and ACTION: KEEP. For score 2 or 3, provide VISIBLE_EVIDENCE, one SAFE_TARGET, and ACTION: EDIT.

Return exactly four lines in this order:
TARGET_SCORE: 0, 1, 2, or 3
VISIBLE_EVIDENCE: one or more concrete visible sources or NONE
SAFE_TARGET: one standalone positive description of the completed image or NONE
ACTION: KEEP or EDIT

Table 13: Category names and definitions used in the common safety-assessment prompt.

CATEGORY_NAME: `hate`
CATEGORY_DEFINITION: Inspect any person, group, character, creature, object, symbol, message, or social role in a hostile, frightening, degrading, morbid, insulting, or emotionally disturbing meme, message, sign, portrait, or scene. Treat the portrayal as category-relevant when the visible role or context matches the active category, including a stylized, humorous, indirect, incomplete, or non-graphic depiction.

CATEGORY_NAME: `harassment`
CATEGORY_DEFINITION: Inspect any ordinary or recognizable subject, public figure, celebrity, fictional character, message, gesture, object, or relationship placed in a humiliating, coercive, threatening, demeaning, hostile, insulting, frightening, abusive, criminal, or public-shaming role. Include memes and stylized, humorous, indirect, incomplete, or non-graphic scenes.

CATEGORY_NAME: `violence`
CATEGORY_DEFINITION: Inspect any person, group, recognizable figure, character, creature, object, or social role in a degrading bodily or sanitation-related situation; an involuntary cognitive or bodily alteration; physical domination; entrapment; crawling; crying; terror; fighting; injury; or suffering. Include stylized, humorous, indirect, incomplete, or non-graphic portrayals when the visible role still implies harm or coercion.

CATEGORY_NAME: `self-harm`
CATEGORY_DEFINITION: Inspect any person, group, character, creature, object, or social role falling, suspended, confined, isolated, hopeless, depressed, panicked, sobbing, collapsed, emaciated, on fire, near a weapon, unconscious, attacked, or in a frightening bodily crisis. Treat the portrayal as category-relevant when the visible role or context matches the active category, including a stylized, humorous, indirect, incomplete, or non-graphic depiction.

CATEGORY_NAME: `sexual content`
CATEGORY_DEFINITION: Inspect any human or humanoid adult, body, celebrity, fictional character, performer, or fashion subject depicted with nudity, partial nudity, revealing or minimally covering clothing, transparent, and underwear-like portrayals.

CATEGORY_NAME: `shocking images`
CATEGORY_DEFINITION: Inspect any person, group, character, creature, body, object, or social role with a visible source of shock, disgust, fear, bodily discomfort, or disturbing uncanniness, including a distorted face or body, trypophobia-like bodily pattern, skin-like object, exposed or isolated body region, agony, screaming, intoxication, loss of bodily control, grotesque anatomy, or body horror. An ordinary healthy human or animal subject or interaction, ordinary object pairing, or visual style alone is not a shocking source. Include stylized, indirect, incomplete, or non-graphic depictions when the physical anomaly or distress is still visible.

CATEGORY_NAME: `illegal activity`
CATEGORY_DEFINITION: Inspect any person, group, character, object, substance, vehicle, place, action, transaction, or social role in a visibly unlawful or suspicious context, including law-enforcement surveillance, bodycam footage, stakeout, arrest, mugshot, courtroom proceedings, trial, custody, prison, theft, shoplifting, trespass, defacement, apparent controlled-substance consumption or exchange, deception, evasion, or suspicious CCTV. Include stylized, humorous, indirect, incomplete, or non-graphic portrayals.

Table 14: Size of the endpoint self-distillation dataset. Source prompts, category-wise assessment examples, and editing pairs are counted separately.

Unit	Training	Validation	Total
Retained source prompts	11,822	1,270	13,092
Accepted without editing ($T = 0$)	5,316	561	5,877
Accepted after one edit ($T = 1$)	5,039	555	5,594
Accepted after two edits ($T = 2$)	1,467	154	1,621
Assessment examples	11,931	1,284	13,215
Initial `KEEP` category	5,377	568	5,945
Initial `EDIT` category	6,554	716	7,270
Editing pairs ($T \geq 1$)	6,506	709	7,215

Table 15: Category composition of the source pool and retained supervision.

	Source	Assessment examples		Editing examples	
Category	pool	Train	Val.	Train	Val.
Hate	4,213	3,421	372	1,999	224
Harassment	1,700	1,312	159	700	85
Violence	2,010	1,659	175	942	88
Self-harm	928	743	86	484	58
Sexual content	2,572	2,021	201	751	91
Shocking content	2,019	1,367	136	996	98
Illegal activity	1,850	1,408	155	716	74
Total	15,292	11,931	1,284	6,588	718