SEEING AND SOLVING ARE NOT ENOUGH FOR VISION-LANGUAGE MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Vision-language models (VLMs) answer visual questions by combining visual information extraction with downstream problem solving. We investigate a fundamental question: Does an incorrect answer necessarily reflect a failure in visual extraction or problem solving? A model may succeed at both abilities when tested separately yet still fail on the original multimodal question, a distinction that overall answer accuracy cannot reveal. To study this, we perform a question-level empirical analysis across multiple VLMs and visual domains. We define an exactly scorable *task state* (i.e., the visual information sufficient to solve a question) and use it to test whether the same model can extract the required state, solve the question from the ground-truth state, and answer the original multimodal question. We find that *composition failures*, where extraction and solving both succeed but direct answering fails, account for 17.7–75.6% of direct-answering errors across multiple VLMs and datasets. To address this failure mode, we introduce a simple yet effective method, termed *State Realization Tuning* (SRT). SRT fine-tunes LoRA adapters attached to the language-model layers while keeping the pretrained VLM weights frozen. It trains the model to output the ground-truth task state before the final answer in a single autoregressive response. SRT improves over standard supervised fine-tuning by 1.7–14.1 percentage points and repairs 92.5–98.1% of diagnosed composition failures. A single LoRA adapter trained with SRT also improves performance across substantially different task-state structures. Our work shows that having both visual extraction and problem-solving capabilities does not guarantee correct multimodal answering. Requiring the model to first output the visual information needed to solve the question can help bridge this gap.

1 INTRODUCTION

Visual question answering (VQA) requires both detailed understanding of an image and complex reasoning to answer questions about it (Antol et al., 2015). When a model gives an incorrect final answer, however, the answer alone does not reveal which of these steps failed. Consider a chart question asking for the sum of two values. A vision-language model (VLM) may correctly recover both values when asked to extract them, and correctly compute their sum when the values are given, yet still fail to answer the original image question. We call this pattern a *composition failure*: on the same question, visual extraction and problem solving both succeed when tested separately, but the original multimodal question is still answered incorrectly.

Gaps between component abilities and final answers have been observed before. Press et al. (2023) showed that language models can solve the individual parts of a question yet fail to combine them, calling this the compositionality gap. Their analysis decomposes the original question into separate subquestions and evaluates the component abilities through those subquestions. For multimodal questions, however, diagnosing such a failure also requires knowing whether the model recovered the visual information needed for the question in the first place. In VLMs, Prism (Qiao et al., 2024) and DISSECT (Kukreja et al., 2026) separate visual extraction from reasoning by first verbalizing the image and then reasoning over the description. Such descriptions help separate perception from reasoning, but because they are free-form, it remains unclear for a particular failed question whether the required visual information was actually recovered. Together, these settings leave open a key question: when a vision-language model answers a multimodal question incorrectly, can both visual extraction and downstream solving be verified to succeed on that same question?

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **An example of a composition failure.** For the same question, the model succeeds at both Extract and Solve, yet fails to answer directly. Panel (a) shows the task-state components schematically. In the actual evaluation, Extract and Direct each receive the same full task question in a single call, without the illustrative scene-content lists (Appendix G).

We make this distinction measurable with a *task state*. It represents the visual information sufficient to solve the question in a structured form that can be scored exactly. Using dataset-provided ground-truth metadata, such as a chart's source table or scene annotations, we select the task-relevant information used to construct both the task state and the corresponding compositional question. For each question, we evaluate the same model in three ways. *Extract* tests whether the model can correctly recover the task state from the image with the full question. *Solve* tests whether it can correctly answer the question from the ground-truth task state without the image. *Direct* tests whether it can answer the original image question correctly. A composition failure occurs when Extract and Solve both succeed but Direct fails, as illustrated in Figure 1. Using this question-level diagnosis, we can identify composition failures from the model's joint behavior on each question rather than infer them from differences in aggregate accuracy. In these cases, the same model separately demonstrates the required visual-extraction and problem-solving capabilities, yet fails to combine them successfully in direct multimodal answering. Our experiments show that composition failures account for a substantial share of errors across multiple VLMs and visual domains.

To address this failure mode, we introduce *State Realization Tuning* (SRT), a simple modification to supervised fine-tuning. In standard supervised fine-tuning (SFT), the model is trained on an image and question to produce only the final answer. Differently, our proposed SRT fine-tunes LoRA adapters in the language-model layers on a response containing the task state followed by the final answer. Through these LoRA updates, the model learns to recover task-relevant visual information and use it to answer, while the pretrained VLM weights remain frozen. Our experiments show that SRT consistently outperforms Standard SFT across models and visual domains. Further analysis confirms that SRT recovers and correctly uses the task state, repairs the vast majority of diagnosed composition failures, and preserves nearly all previous successes. Moreover, our experiments show that a single model trained with SRT can improve performance across substantially different task-state structures, indicating that the model can learn to realize and use different forms of task state.

Our contributions are as follows:

- We propose a question-level evaluation that separately tests visual extraction, problem solving, and direct multimodal answering on the same question. This enables us to identify *composition failures*, where the model demonstrates both extraction and problem-solving capabilities on a question yet fails to compose them when answering directly.

- We show that composition failures account for a substantial share of errors across VLMs, visual domains, and task settings, and introduce two complementary metrics to quantify their prevalence.
- We propose the *State Realization Tuning* (SRT) training mechanism to enable the model to generate the task state before the final answer. SRT consistently improves over standard supervised fine-tuning and repairs the vast majority of composition failures.

2 Related Work

Diagnosing compositional failures. The compositionality gap (Press et al., 2023) describes language models that answer the individual components of a question correctly but fail to combine them into the correct final answer. Rather than decomposing a question into subquestions, we keep the multimodal question fixed and connect extraction and solving through a task state whose predicted contents can be matched exactly against ground truth. In vision-language reasoning, MMComposition (Hua et al., 2026) benchmarks fine-grained compositional perception and reasoning, and ComPABench (Li et al., 2025) tests cross-modal and cross-task skill composition. Compose and Fuse (Wang et al., 2026) identifies a task-composition bottleneck in controlled multimodal logical reasoning, showing that models can recognize cross-modal facts and reason effectively in isolation while performance degrades when recognition and reasoning must be jointly executed. Prism (Qiao et al., 2024) and DISSECT (Kukreja et al., 2026) separate visual extraction from downstream reasoning through intermediate descriptions, which help locate errors but are free-form and therefore difficult to score exactly for a particular question. Other work studies failures on misleading questions even when simpler visual questions are answered correctly (Liu et al., 2025). Related analyses examine cases where visual attention does not align with answer correctness (Liu et al., 2026). Further analyses trace failures to learned representations, vision encoders, modality conflicts, or relational grounding (Sbrolli et al., 2026; Aravindan et al., 2025; Tian et al., 2026; Bukkapatnam, 2026). However, none of these works directly tests whether the same model can both extract the sufficient visual information and solve from the correct visual information on the same question it fails to answer. In this paper, we make this test possible with an exactly scorable task state.

Explicit intermediate representations. Explicit intermediates have been explored at different stages of visual reasoning. At the representation level, neural-symbolic VQA executes programs over structured scene representations, while DePlot translates charts into tables for downstream reasoning (Yi et al., 2018; Liu et al., 2023). During generation, Multimodal-CoT separates rationale generation from answer inference, and LLaVA-CoT further stages visual interpretation, reasoning, and answering (Zhang et al., 2024; Xu et al., 2025). Related work also explores caption-before-thinking and visual-grounding rewards (Li et al., 2025). More recent post-training approaches make the separation between perception and reasoning more explicit. MathFlow trains a dedicated perception model before inference, Vision-SR1 combines perceptual decomposition with reinforcement learning, CogFlow introduces knowledge internalization, and Wu et al. (2026) explicitly separate perception from reasoning during post-training (Chen et al., 2026b; Li et al., 2026; Chen et al., 2026a). Together, these studies show that explicit intermediate information can improve final answers. However, their effects are typically assessed through overall answer accuracy, which does not reveal whether the intended failure mode was actually repaired. Our contribution is to connect the intervention to a specific failure population. The same exactly scorable task state used to identify composition failures also serves as the intermediate supervision target, allowing repair to be measured directly on the failed questions that were diagnosed before training.

3 Method

Our work consists of two main components. First, we represent the visual information sufficient to answer each question as an exactly scorable task state and use it to evaluate visual extraction and downstream solving on the same question. As illustrated in Figure 1, this enables question-level diagnosis of composition failures. Second, we use the same task state as an intermediate supervision target during fine-tuning. As illustrated in Figure 2, SRT trains the model to realize the task state before the final answer within a single autoregressive response.

3.1 Task State and Question Construction

A *task state* z is a structured representation of the visual information in an image I sufficient to answer a question q. It is exactly scorable because fixed matching rules can check its predicted contents against ground truth. Depending on the task, z may contain chart values, object counts, relations, or sets. The task state z and answer y satisfy

$$y = \phi_y(q, z), \tag{1}$$

where ϕ_y is the task-specific answer function, such as numerical computation, comparison, or set operation. The task state thus separates visual extraction from problem solving. If a model recovers z from the image, it has extracted the visual information sufficient to answer the question. Providing the ground-truth z directly instead tests whether the model can answer from the correct state alone.

For an image I, let A denote the structured ground-truth information provided with the benchmark dataset and associated with that image. For example, A may include the underlying data table and annotations of a chart, or the scene-level annotations and functional programs of a synthetic scene (Masry et al., 2022; Johnson et al., 2017). Since A may contain information relevant to many possible questions, each task instance uses only the subset needed for that question. We denote this subset by $A^\star$. The selected information provides the ground-truth content used to form the task state. It also provides the corresponding labels or query text used to formulate the question. The question q, ground-truth task state $z^\star$, and answer $y^\star$ are then jointly constructed as

$$q = \phi_q(A^\star), \qquad z^\star = \phi_z(A^\star), \qquad y^\star = \phi_y(q, z^\star), \tag{2}$$

where ϕ_q constructs the question from the labels or query text in $A^\star$, ϕ_z arranges the corresponding ground-truth content in the required order and format to form the task state, and ϕ_y computes the final answer from the question and task state. Appendix G.1 gives the complete construction procedures.

To illustrate this construction more concretely, consider the case where the task state takes the form of an ordered pair $z^\star = (a, b)$. On ChartQA, we parse the underlying data table, verify its numerical entries against the structured chart annotations, and deterministically select one verified pair. The two values form $z^\star = (a, b)$, while the corresponding labels identify the chart elements referred to in the question. From the same pair, we can construct comparison, absolute-difference, and sum questions. These tasks use the benchmark images and structured information but do not reuse the original benchmark questions. On CLEVR, we retain official count questions whose functional programs reproduce the official answers when re-executed on the scene graph, and select two verified questions with distinct programs per scene. Their counts form $z^\star = (a, b)$, and the two original queries are combined using comparison, absolute-difference, and sum operations. These programs may involve spatial relations, same-attribute operations, unions, and intersections. The ordered pair is one example of the general task-state definition. Section 4.6 evaluates other task-state structures with multiple values, small tables, relational counts, and variable-length sets.

3.2 Diagnosing Composition Failures

For every question $x = (I, q, z^\star, y^\star)$, we evaluate the same model M under three interfaces. **Extract** gives M the image and the full task question and asks it to predict the task state. **Solve** gives M the question and the ground-truth state, without the image, and asks it for the final answer. **Direct** gives M the image and question and asks it for the final answer, as in ordinary VQA. Let $M_E(I, q)$, $M_S(q, z^\star)$, and $M_D(I, q)$ denote the outputs of M under the three interfaces. We define:

$$E(x) = \mathbb{1}[M_E(I, q) = z^\star], \quad S(x) = \mathbb{1}[M_S(q, z^\star) = y^\star], \quad D(x) = \mathbb{1}[M_D(I, q) = y^\star]. \tag{3}$$

The indicator $\mathbb{1}[\cdot]$ is 1 when its condition holds and 0 otherwise. The model outputs a state or answer, not a score. We parse and normalize it, then match its contents exactly against ground truth. Both pair values must match in question order; set elements must match after normalization. Invalid outputs count as incorrect (Appendix G.4). Solve uses the ground-truth state rather than the Extract prediction, so the two abilities are assessed independently on the same question.

Direct errors are then partitioned into three disjoint sets:

$$\begin{aligned} \mathcal{E} &= \{x : D(x) = 0,\ E(x) = 0\}, \\ \mathcal{S} &= \{x : D(x) = 0,\ E(x) = 1,\ S(x) = 0\}, \\ \mathcal{C} &= \{x : D(x) = 0,\ E(x) = 1,\ S(x) = 1\}, \end{aligned} \tag{4}$$



Figure 2: **State Realization Tuning with LoRA.** Only the SRT adapter, implemented as LoRA updates in the language-model layers, is trained. The task state and final answer are two fields of one autoregressive response, with the state generated first.

where $\mathcal{E}$, $\mathcal{S}$, and $\mathcal{C}$ denote extraction failures, solving failures, and composition failures, respectively. In $\mathcal{E}$, the model fails to recover the visual information required by the task state. In $\mathcal{S}$, extraction succeeds, but the model fails to solve the question even when the ground-truth state is provided. In $\mathcal{C}$, the model recovers the required state and can solve from it in isolation, yet fails to answer the multimodal question directly. These are the composition failures our diagnosis isolates. Note that $\mathcal{E}$ collects every Direct error with $E(x) = 0$ regardless of $S(x)$.

Let $J = \{x : E(x) = 1, S(x) = 1\}$ be the set of questions on which both Extract and Solve succeed. We report two complementary measures:

$$\text{CFS} = \frac{|\mathcal{C}|}{|\{x : D(x) = 0\}|} = \mathbb{P}(E{=}1, S{=}1 \mid D{=}0), \quad \text{CFR} = \frac{|\mathcal{C}|}{|J|} = \mathbb{P}(D{=}0 \mid E{=}1, S{=}1), \tag{5}$$

where $\mathbb{P}$ is the probability estimated over the evaluation questions. *Composition Failure Share* (CFS) is the fraction of direct-answering errors that are composition failures. *Composition Failure Rate* (CFR) is how often direct answering fails when both visual extraction and problem solving succeed. Both are computed from question-level joint outcomes rather than differences in aggregate accuracy.

3.3 State Realization Tuning

A composition failure shows that the model can extract the required visual information and solve from it in isolation, yet fails to combine these abilities when answering directly. State Realization Tuning (SRT) makes state generation part of the model's own answer-generation process. Given the image and task question, the model first writes out the task state and then the final answer in one autoregressive response. Training supervises both fields jointly, following the broader idea of supervising intermediate outputs (Nye et al., 2021; Zhang et al., 2024).

We implement SRT with LoRA (Hu et al., 2022), as illustrated in Figure 2. The pretrained VLM weights remain frozen, including the vision encoder, vision–language connector, and original language-model weights. We construct the *SRT adapter* using LoRA, with trainable low-rank updates applied to the language-model layers. For a frozen weight matrix W_0, the update is $\Delta W = BA$, where A and B are low-rank trainable matrices, with the fixed LoRA scaling absorbed into B. SRT thus learns state-first generation through lightweight language-model updates while preserving the pretrained visual components.

Under this shared training setup, Standard SFT and SRT use the same images, questions, training data, and optimization settings. Only the output-format instructions and supervision targets differ. Standard SFT supervises only the answer $y^\star$. SRT instead supervises the task state followed by the answer, $[z^\star; y^\star]$. The token-level language-model loss is applied to the entire response. For training data $\mathcal{D}$ and adapter parameters ω, with the format instructions implicit, the objectives are

$$\begin{aligned} \mathcal{L}_{\text{SFT}}(\omega) &= -\mathbb{E}_{x\sim\mathcal{D}} \log p_\omega(y^\star \mid I, q), \\ \mathcal{L}_{\text{SRT}}(\omega) &= -\mathbb{E}_{x\sim\mathcal{D}} \log p_\omega([z^\star; y^\star] \mid I, q), \end{aligned} \tag{6}$$

where $[z^\star; y^\star]$ denotes one response containing the state before the answer. At inference, no reference state is supplied. Given the image, question, and format instruction, the model predicts its own state $\widehat{z}$ and continues to its answer $\widehat{y}$. Appendix G provides the full prompts and output formats.

4 EXPERIMENTS

4.1 DATASETS AND IMPLEMENTATION DETAILS

Datasets. We construct questions and task states from ChartQA charts (Masry et al., 2022) and CLEVR scenes (Johnson et al., 2017) following Section 3.1. Each question is paired with one of three operations (comparison, absolute difference, or sum), yielding 9,993 training and 1,077 test questions from ChartQA charts, and 158,226 training and 33,723 test questions from CLEVR scenes. Section 4.6 further evaluates additional task and question types. ChartQA covers bar, line, and pie charts with diverse visual styles. CLEVR provides synthetic scenes with compositionally rich count programs. On ChartQA, we evaluate four VLMs: Qwen2.5-VL-7B (Bai et al., 2025), Molmo2-O-7B (Clark et al., 2026), InternVL3.5-8B-HF (Wang et al., 2025), and MiniCPM-V 4.5 (Yu et al., 2025), abbreviated as Qwen, Molmo, InternVL, and MiniCPM. On CLEVR, we perform the diagnostic analysis and evaluate the fine-tuning variants on both Qwen and Molmo.

Implementation details. All fine-tuning uses LoRA (Hu et al., 2022) with rank 16, alpha 32, and dropout 0.05. LoRA adapters are applied only to the language-model layers, while the vision encoder and model-specific vision–language connector remain frozen. We train for one epoch using AdamW (Loshchilov & Hutter, 2019) with a learning rate of 10^{-4} and batch size 8. At inference, we use deterministic decoding. For each model and random seed, all conditions use the same examples, data order, and optimization settings. They differ only in their output instructions and supervision targets. Appendix G provides the full prompts, output formats, and scoring rules.

4.2 COMPOSITION FAILURES ACROSS MODELS AND VISUAL DOMAINS

As shown in table 1, Solve exceeds Direct in every evaluated setting, while Extract exceeds Direct except for Molmo on CLEVR. However, these average accuracies do not show whether both capabilities succeed on the same questions that Direct gets wrong. We therefore examine the three outcomes jointly at the question level.

Table 1: **Accuracy and composition-failure prevalence.** CFS is the share of Direct errors that are composition failures. CFR is the Direct failure rate on questions where both Extract and Solve succeed. The bars partition each model's Direct errors. All values are percentages.

		Accuracy			Failures		Error breakdown
Dataset	Model	Extract	Solve	Direct	CFS	CFR	0 50 100%
ChartQA	Qwen	81.1	86.8	63.5	40.2	20.5	40.2
	Molmo	75.5	94.3	58.0	65.5	38.2	65.5
	InternVL	90.3	97.6	66.6	75.6	28.7	75.6
	MiniCPM	77.2	98.1	61.6	56.5	28.8	56.5
CLEVR	Qwen	56.3	94.5	37.5	46.1	54.2	46.1
	Molmo	20.9	99.0	32.4	17.7	57.7	17.7

Extraction failure Solving failure Composition failure

On ChartQA, composition failures account for 40.2%–75.6% of Direct errors across the four models, with CFR ranging from 20.5% to 38.2%. On CLEVR, Qwen reaches a CFS of 46.1% and a CFR of 54.2%, while Molmo reaches 17.7% and 57.7%, respectively. Direct can therefore fail even when Extract and Solve succeed on the same question. The effect is particularly pronounced for InternVL on ChartQA, where composition failures make up 75.6% of Direct errors despite strong Extract and Solve accuracies. Overall, composition failures appear consistently across the evaluated models and visual domains, although their prevalence varies by setting.

We further examine the stability of this diagnosis by varying the evaluation protocol. Appendix B tests content-normalized answer scoring, two fixed instruction paraphrases, and order-relaxed state scoring on commutative operations, all of which yield similar overall composition-failure rates. The same appendix also evaluates Solve with the image present alongside the reference state and finds that solving remains strong when the correct state is provided alongside the image.

4.3 Effectiveness of State Realization Tuning

We compare four fine-tuning variants using the same task instances, images, questions, examples, example order, and optimization settings. Their output instructions and supervision targets differ across conditions. *Standard SFT* is standard supervised fine-tuning on the final answer. *Format Control* keeps SRT's two-field output format but replaces the task state with a fixed placeholder, isolating the extra output stage. *Answer-to-State* supervises the same state and answer as SRT but places the state after the answer, isolating the effect of ordering. *SRT* realizes the state before the answer. Format Control and Answer-to-State separate the content of the state from where it appears, mirroring the ablation strategy in chain-of-thought research (Wei et al., 2022).

Table 2: **Answer accuracy under various conditions.** Untuned is the model before fine-tuning. ChartQA results are the mean ± standard deviation over three seeds; CLEVR results use one seed. All values are percentages.

			Variants			
Dataset	Model	Untuned	Standard SFT	Format Control	Answer-to-State	SRT
ChartQA	Qwen	63.5	85.1 ± 0.8	85.8 ± 0.7	85.1 ± 0.6	$\mathbf{91.7 \pm 0.4}$
	Molmo	58.0	77.3 ± 0.6	75.7 ± 2.4	79.4 ± 1.0	$\mathbf{91.5 \pm 0.6}$
	InternVL	66.6	87.7 ± 0.8	86.2 ± 0.8	87.4 ± 1.2	$\mathbf{94.0 \pm 0.4}$
	MiniCPM	61.6	72.8 ± 1.3	72.3 ± 1.7	73.0 ± 1.0	$\mathbf{86.0 \pm 0.4}$
CLEVR	Qwen	37.5	93.7	92.9	93.5	**95.4**
	Molmo	32.4	87.7	86.8	90.6	**92.0**

As shown in Table 2, Standard SFT produces large gains over the untuned models, and SRT improves further in every evaluated model–domain setting. On ChartQA, SRT raises accuracy by an additional 6.3–14.1 points over Standard SFT across the four models. On CLEVR, Qwen improves from 93.7% with Standard SFT to 95.4% with SRT, while Molmo improves from 87.7% to 92.0%. These results show that state-first supervision provides gains beyond final-answer supervision across both visual domains. Figure 3 illustrates this pattern with an example.

Together, Format Control and Answer-to-State help isolate the source of SRT's gains. Format Control remains close to Standard SFT, indicating that adding a second output field or a longer response is not sufficient to explain the improvement. Answer-to-State provides the same state supervision as SRT but places the state after the answer, and it also underperforms SRT in every setting. Across the six model–domain settings, SRT outperforms Format Control by 2.5–15.7 points and Answer-to-State by 1.4–13.0 points. Thus, the benefit is not explained by state supervision alone. The task state is most effective when generated before the answer, so it can directly condition the subsequent answer generation. Together, these results support SRT's state-first design, showing that its gains come from placing the task state before the answer rather than additional output length or state supervision alone.



Question

First count query: What number of things are there?
Second count query: How many other things are there of the same material as the tiny cube?
What is the absolute difference between the first and second counts?

Standard SFT

```
FINAL_ANSWER: 3
```

✗

SRT

```
TASK_STATE: 7, 3
FINAL_ANSWER: 4
```

✓

Figure 3: **A qualitative example of SRT on CLEVR.** Standard SFT produces an incorrect answer, whereas SRT first realizes the correct task state and then derives the correct answer.

4.4 State Realization and Failure Repair

We now ask whether SRT's gain comes from realizing the correct task state and repairing the composition failures we intend to address. We report four metrics. *State Accuracy* measures exact agreement between the generated and ground-truth state. *State–Answer Consistency* measures whether the answer follows from the generated state, $\widehat{y} = \phi_y(q, \widehat{z})$. *CF Repair* is the fraction of questions in the composition-failure set $\mathcal{C}$ that are answered correctly after fine-tuning. *Preservation* is the fraction of the untuned model's correct answers that remain correct after SRT.

Table 3: **State realization, failure repair, and preservation.** State metrics and Preservation refer to SRT. CF Repair compares Standard SFT and SRT on fixed pre-tuning composition-failure sets. Values are percentages, with three-seed standard deviations on ChartQA.

		State realization		CF Repair		Preservation
Dataset	Model	State Acc.	S–A Cons.	Standard SFT	SRT	
ChartQA	Qwen	89.1 ± 0.2	99.2 ± 0.5	73.0 ± 4.5	$\mathbf{94.3 \pm 1.1}$	98.8 ± 0.1
	Molmo	88.1 ± 0.8	99.3 ± 0.1	71.4 ± 0.2	$\mathbf{98.1 \pm 1.4}$	98.5 ± 0.6
	InternVL	91.7 ± 0.6	99.8 ± 0.2	82.4 ± 1.7	$\mathbf{97.5 \pm 0.4}$	99.2 ± 0.3
	MiniCPM	81.2 ± 1.0	99.8 ± 0.1	58.3 ± 3.0	$\mathbf{92.5 \pm 2.4}$	97.1 ± 0.1
CLEVR	Qwen	93.9	100.0	95.3	**96.8**	97.0
	Molmo	87.9	100.0	93.9	**95.9**	95.3

As shown in Table 3, SRT achieves 81.2%–91.7% State Accuracy and over 99% State–Answer Consistency on ChartQA. On CLEVR, these values are 93.9% and 100.0% for Qwen, and 87.9% and 100.0% for Molmo. SRT thus enables the model to recover and correctly use the task state.

On ChartQA, SRT repairs 92.5%–98.1% of composition failures, exceeding Standard SFT by 15.2–34.2 percentage points, while preserving 97.1%–99.2% of untuned successes. On CLEVR, CF Repair and Preservation reach 96.8% and 97.0% for Qwen, and 95.9% and 95.3% for Molmo. SRT repairs most diagnosed failures while preserving most previously solved questions.

4.5 Comparison with Inference-Time Decomposition

We further examine whether the same state-mediated structure improves performance without parameter updates. Prior work composes perception and reasoning at inference time by passing extracted visual or multimodal information to a downstream reasoner (Liu et al., 2023; Qiao et al., 2024; Kukreja et al., 2026; Wang et al., 2026). Our Extract→Solve baseline follows this recipe with the same untuned model in both roles on our ChartQA test questions, predicting the task state in one call and answering from it in a second call without the image or any ground-truth information.

Table 4: **Inference-time composition versus supervised fine-tuning on ChartQA.** Extract→Solve passes the predicted state to a separate image-free Solve call. Fine-tuning results are three-seed mean $\pm$ standard deviation. All values are percentages.

Model	Untuned	Standard SFT	Extract→Solve	SRT
Qwen	63.5	85.1 ± 0.8	75.1	$\mathbf{91.7 \pm 0.4}$
Molmo	58.0	77.3 ± 0.6	79.7	$\mathbf{91.5 \pm 0.6}$
InternVL	66.6	87.7 ± 0.8	90.7	$\mathbf{94.0 \pm 0.4}$
MiniCPM	61.6	72.8 ± 1.3	82.1	$\mathbf{86.0 \pm 0.4}$

As shown in Table 4, Extract→Solve substantially improves over untuned direct answering on all four models. It even exceeds Standard SFT on three of four models without parameter updates. This provides further evidence that the models often possess both the visual extraction and problem-solving abilities needed for the task, but fail to compose them during direct answering. After tuning with SRT, the model can realize and use the task state within a single response while achieving higher accuracy on every model. This shows that SRT strengthens the model's ability to compose visual extraction and problem solving, rather than merely exposing the two abilities through separate calls. We further evaluate zero-shot state-first prompting in Appendix D.

4.6 Generalization to Additional Task Structures

In Section 4.1, we mainly construct tasks whose task state is an ordered pair. Here, we further construct four substantially different task types to examine whether our findings on composition failures and SRT hold beyond this setting. *Multi-step arithmetic* uses three values (a, b, c) and asks for composed operations such as $(a + b) - c$ and $|a - b| + c$. *Conditional lookup* uses a 3×2 table and asks which candidate to select. *Relational count ranking* counts three groups defined by different spatial relations and asks which has the middle count. *Color-set operations* ask for the intersection or difference of two variable-length color sets, with a set-valued state.

Table 5: **Composition failures with richer task states.** Untuned CFR (%) is shown with CF/J counts. N/A means no question passes both Extract and Solve ($J = 0$).

Task structure	Qwen	Molmo
Multi-step arithmetic	96.2 (25/26)	86.0 (49/57)
Conditional lookup	50.8 (33/65)	50.0 (2/4)
Relational count ranking	80.0 (28/35)	N/A (0/0)
Color-set operations	45.0 (68/151)	56.8 (25/44)
Overall CFR	55.6 (154/277)	72.4 (76/105)

As shown in Table 5, composition failures also occur across these additional task structures, with CFR ranging from 45.0% to 96.2% for Qwen and from 50.0% to 86.0% for Molmo. Appendix E reports the complete diagnostic results. To better reflect the diversity of real-world VLM reasoning, we train one Standard SFT and one SRT adapter for each model on the same $4{,}000$-question mixture spanning all four task structures, with $1{,}000$ questions per structure.

Table 6: **SRT on additional task structures.** Final-answer accuracy (%) of the Standard SFT and SRT adapters on each structure's N test questions.

		Qwen		Molmo	
Task structure	N	Standard SFT	SRT	Standard SFT	SRT
Multi-step arithmetic	291	32.3	**67.7**	22.7	**68.7**
Conditional lookup	215	71.6	**85.1**	67.4	**84.2**
Relational count ranking	400	87.8	**96.5**	38.5	**80.0**
Color-set operations	400	79.5	**98.5**	73.5	**91.0**
Average accuracy	1,306	70.2	**88.8**	50.5	**81.5**

As shown in Table 6, SRT improves over Standard SFT on all four task structures for both models, raising accuracy from 70.2% to 88.8% for Qwen and from 50.5% to 81.5% for Molmo. These gains hold across tasks with very different state structures and reasoning requirements. More importantly, a single SRT adapter trained on the mixed task set performs well across all structures. This shows that, with appropriate training, the model can learn to realize and use different forms of task state within the same framework rather than requiring a separate model for each structure. This flexibility is important for real-world settings, where questions may require different forms of visual information.

5 Conclusion

Successful visual extraction and problem solving do not always lead VLMs to a correct answer, suggesting that some failures arise from an inability to compose capabilities models already possess. By introducing an exactly scorable task state, our framework makes composition failures identifiable on individual questions and shows that they account for 17.7%–75.6% of the errors across models and visual domains. The same task state provides a simple intervention target. SRT consistently improves over Standard SFT and other variants and repairs most diagnosed composition failures while preserving previous successes. More importantly, our generalization experiments show that a single SRT adapter can handle multiple substantially different task-state structures within the same model, without requiring a separate adapter for each structure. Encouraged by this flexibility and SRT's consistent gains across models and visual domains, we hope to extend the framework to increasingly realistic vision-language reasoning settings as models and training data grow in scale and diversity.

Reproducibility Statement

Sections 3.1 and 4.1 and Appendix G describe how the ChartQA and CLEVR composition questions are constructed from the public source tables and scene annotations, together with the exact dataset sizes and splits. Section 4.1 and Appendix G list all fine-tuning hyperparameters, the frozen components, and the random seeds of every experiment. The Extract, Solve, Direct, and training prompts, the serialized output formats, the decoding settings, the normalization rules, and the handling of invalid outputs are given in Appendix G. The diagnostic metrics are defined in Section 3.2, with the exact question counts behind every reported CFS and CFR value in Appendices A and E. The additional task structures are defined in Section 4.6, and all evaluated models are public checkpoints named in Section 4.1.

AI Use Statement

Generative AI tools were used in three ways. First, to aid and polish writing: we used Cursor with large language models to improve the manuscript's wording and flow; all scientific content, claims, and reported numbers were written and verified by the authors. Second, for retrieval and discovery: we used generative AI to search for and screen related work; every cited paper was read by the authors and its metadata checked against the primary publication record. Third, for research execution: GPT-5.6 Sol and GPT-6 Astra assisted in writing and running experimental code, including data construction, evaluation scripts, and plotting; the authors designed the experiments, reviewed all generated code, and verified the results. The authors take full responsibility for the paper's content.

References

Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C. Lawrence Zitnick, and Devi Parikh. VQA: Visual question answering. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, pp. 2425–2433, 2015.

Ashwath Vaithinathan Aravindan, Abha Jha, and Mihir Kulkarni. Do VLMs have bad eyes? Diagnosing compositional failures via mechanistic interpretability. In *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops (ICCVW)*, pp. 715–723, 2025.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-VL technical report. *arXiv preprint arXiv:2502.13923*, 2025.

Kaustubh S. Bukkapatnam. The compositional grounding gap: Why vision-language models fail at relational reasoning and how to fix it. In *Proceedings of the 4th Workshop on Advances in Language and Vision Research (ALVR)*, pp. 287–293, 2026.

Shuhang Chen, Yunqiu Xu, Junjie Xie, Aojun Lu, Tao Feng, Zeying Huang, Ning Zhang, Yi Sun, Yi Yang, and Hangjie Yuan. CogFlow: Bridging perception and reasoning through knowledge internalization for visual mathematical problem solving. In *International Conference on Learning Representations (ICLR)*, 2026a.

Shuhang Chen, Hangjie Yuan, Yunqiu Xu, Pengwei Liu, Tao Feng, Jun Cen, Zeying Huang, and Yi Yang. MathFlow: Enhancing the perceptual flow of MLLMs for visual mathematical problems. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL), Volume 1: Long Papers*, pp. 967–992, 2026b.

Christopher Clark, Jieyu Zhang, Zixian Ma, Jae Sung Park, Mohammadreza Salehi, Rohun Tripathi, Sangho Lee, Zhongzheng Ren, Chris Dongjoo Kim, Yinuo Yang, Vincent Shao, Yue Yang, Weikai Huang, Ziqi Gao, Taira Anderson, Jianrui Zhang, Jitesh Jain, George Stoica, Winson Han, Ali Farhadi, and Ranjay Krishna. Molmo2: Open weights and data for vision-language models with video understanding and grounding. *arXiv preprint arXiv:2601.10611*, 2026.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

Hang Hua, Yunlong Tang, Ziyun Zeng, Liangliang Cao, Zhengyuan Yang, Hangfeng He, Chenliang Xu, and Jiebo Luo. MMComposition: Revisiting the compositionality of pre-trained vision-language models. *Transactions on Machine Learning Research (TMLR)*, 2026.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C. Lawrence Zitnick, and Ross Girshick. CLEVR: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2901–2910, 2017.

Dikshant Kukreja, Kshitij Sah, Karan Goyal, Mukesh Mohania, and Vikram Goyal. DISSECT: Diagnosing where vision ends and language priors begin in scientific VLMs. *arXiv preprint arXiv:2604.06250*, 2026.

Tianle Li, Jihai Zhang, Yongming Rao, and Yu Cheng. Unveiling the compositional ability gap in vision-language reasoning model. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 38, pp. 126574–126592, 2025.

Zongxia Li, Wenhao Yu, Chengsong Huang, Zhenwen Liang, Rui Liu, Fuxiao Liu, Jingxi Chen, Dian Yu, Jordan Boyd-Graber, Haitao Mi, and Dong Yu. Vision-SR1: Self-rewarding vision-language model via reasoning decomposition and multi-reward policy optimization. In *International Conference on Learning Representations (ICLR)*, 2026.

Fangyu Liu, Julian Eisenschlos, Francesco Piccinno, Syrine Krichene, Chenxi Pang, Kenton Lee, Mandar Joshi, Wenhu Chen, Nigel Collier, and Yasemin Altun. DePlot: One-shot visual language reasoning by plot-to-table translation. In *Findings of the Association for Computational Linguistics (Findings of ACL)*, pp. 10381–10399, 2023.

Yexin Liu, Zhengyang Liang, Yueze Wang, Xianfeng Wu, Feilong Tang, Muyang He, Jian Li, Zheng Liu, Harry Yang, Sernam Lim, and Bo Zhao. Unveiling the ignorance of MLLMs: Seeing clearly, answering incorrectly. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9087–9097, 2025.

Zhining Liu, Ziyi Chen, Hui Liu, Chen Luo, Xianfeng Tang, Suhang Wang, Jingying Zeng, Zhenwei Dai, Zhan Shi, Tianxin Wei, Hanqing Lu, Benoit Dumoulin, and Hanghang Tong. Seeing but not believing: Probing the disconnect between visual attention and answer correctness in VLMs. In *International Conference on Learning Representations (ICLR)*, 2026.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations (ICLR)*, 2019.

Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. ChartQA: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of the Association for Computational Linguistics (Findings of ACL)*, pp. 2263–2279, 2022.

Maxwell Nye, Anders Johan Andreassen, Guy Gur-Ari, Henryk Michalewski, Jacob Austin, David Bieber, David Dohan, Aitor Lewkowycz, Maarten Bosma, David Luan, Charles Sutton, and Augustus Odena. Show your work: Scratchpads for intermediate computation with language models. *arXiv preprint arXiv:2112.00114*, 2021.

Ofir Press, Muru Zhang, Sewon Min, Ludwig Schmidt, Noah A. Smith, and Mike Lewis. Measuring and narrowing the compositionality gap in language models. In *Findings of the Association for Computational Linguistics (Findings of EMNLP)*, pp. 5687–5711, 2023.

Yuxuan Qiao, Haodong Duan, Xinyu Fang, Junming Yang, Lin Chen, Songyang Zhang, Jiaqi Wang, Dahua Lin, and Kai Chen. Prism: A framework for decoupling and assessing the capabilities of VLMs. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 37, pp. 111863–111898, 2024.

Cristian Sbrolli, Matteo Matteucci, and Toshihiko Yamasaki. Auto-Comp: An automated pipeline for scalable compositional probing of contrastive vision-language models. *arXiv preprint arXiv:2602.02043*, 2026.

Baoliang Tian, Yuxuan Si, Jilong Wang, LingYao Li, Zhongyuan Bao, Zineng Zhou, Tao Wang, Sixu Li, Ziyao Xu, Mingze Wang, Zhouzhuo Zhang, Zhihao Wang, Yi Ke Yun, Ke Tian, Ning Yang, and Minghui Qiu. CrossCheck-Bench: Diagnosing compositional failures in multimodal conflict resolution. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 40, pp. 25887–25895, 2026.

Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, Zhaokai Wang, Zhe Chen, Hongjie Zhang, Ganlin Yang, Haomin Wang, Qi Wei, Jinhui Yin, Wenhao Li, Erfei Cui, Guanzhou Chen, Zichen Ding, Changyao Tian, Zhenyu Wu, Jingjing Xie, Zehao Li, Bowen Yang, Yuchen Duan, Xuehui Wang, Zhi Hou, Haoran Hao, Tianyi Zhang, Songze Li, Xiangyu Zhao, Haodong Duan, Nianchen Deng, Bin Fu, Yinan He, Yi Wang, Conghui He, Botian Shi, Junjun He, Yingtong Xiong, Han Lv, Lijun Wu, Wenqi Shao, Kaipeng Zhang, Huipeng Deng, Biqing Qi, Jiaye Ge, Qipeng Guo, Wenwei Zhang, Songyang Zhang, Maosong Cao, Junyao Lin, Kexian Tang, Jianfei Gao, Haian Huang, Yuzhe Gu, Chengqi Lyu, Huanze Tang, Rui Wang, Haijun Lv, Wanli Ouyang, Limin Wang, Min Dou, Xizhou Zhu, Tong Lu, Dahua Lin, Jifeng Dai, Weijie Su, Bowen Zhou, Kai Chen, Yu Qiao, Wenhai Wang, and Gen Luo. InternVL3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *arXiv preprint arXiv:2508.18265*, 2025.

Yucheng Wang, Yifan Hou, Aydin Javadov, Mubashara Akhtar, and Mrinmaya Sachan. Compose and fuse: Revisiting the foundational bottlenecks in multimodal reasoning. In *International Conference on Learning Representations (ICLR)*, 2026.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 35, pp. 24824–24837, 2022.

Juncheng Wu, Hardy Chen, Haoqin Tu, Xianfeng Tang, Freda Shi, Hui Liu, Hanqing Lu, Cihang Xie, and Yuyin Zhou. From seeing to thinking: Decoupling perception and reasoning improves post-training of vision-language models. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2026.

Guowei Xu, Peng Jin, Ziang Wu, Hao Li, Yibing Song, Lichao Sun, and Li Yuan. LLaVA-CoT: Let vision language models reason step-by-step. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 2087–2098, 2025.

Kexin Yi, Jiajun Wu, Chuang Gan, Antonio Torralba, Pushmeet Kohli, and Josh Tenenbaum. Neural-symbolic VQA: Disentangling reasoning from vision and language understanding. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 31, 2018.

Tianyu Yu, Zefan Wang, Chongyi Wang, Fuwei Huang, Wenshuo Ma, Zhihui He, Tianchi Cai, Weize Chen, Yuxiang Huang, Yuanqian Zhao, Bokai Xu, Junbo Cui, Yingjing Xu, Liqing Ruan, Luoyuan Zhang, Hanyu Liu, Jingkun Tang, Hongyuan Liu, Qining Guo, Wenhao Hu, Bingxiang He, Jie Zhou, Jie Cai, Ji Qi, Zonghao Guo, Chi Chen, Guoyang Zeng, Yuxuan Li, Ganqu Cui, Ning Ding, Xu Han, Yuan Yao, Zhiyuan Liu, and Maosong Sun. MiniCPM-V 4.5: Cooking efficient MLLMs via architecture, data, and training recipe. *arXiv preprint arXiv:2509.18154*, 2025.

Zhuosheng Zhang, Aston Zhang, Mu Li, Hai Zhao, George Karypis, and Alex Smola. Multimodal chain-of-thought reasoning in language models. *Transactions on Machine Learning Research (TMLR)*, 2024.

A Additional Diagnostic Results

Table 7 gives the question counts behind the composition-failure rates in Section 4.2. In every evaluated setting, Direct fails on a substantial subset of questions where both Extract and Solve succeed.

Table 7: **Exact counts underlying the composition-failure diagnosis.** J is the number of questions on which both Extract and Solve succeed; CF is the subset for which Direct fails.

Setting	Model	N	J	CF	CFS	CFR
ChartQA	Qwen	1,077	770	158	40.2	20.5
ChartQA	Molmo	1,077	774	296	65.5	38.2
ChartQA	InternVL	1,077	948	272	75.6	28.7
ChartQA	MiniCPM	1,077	813	234	56.5	28.8
CLEVR	Qwen	33,723	17,916	9,708	46.1	54.2
CLEVR	Molmo	33,723	7,014	4,044	17.7	57.7

Table 8 separates Direct errors by their Extract and Solve outcomes. When Extract fails, the model usually still solves the question from the ground-truth state. Failures of both interfaces account for only 0.6% to 9.7% of Direct errors. InternVL and MiniCPM also rarely fail at Solve when Extract succeeds; for these models, composition failures make up most Direct errors.

Table 8: **Direct errors broken down by Extract and Solve outcomes.** Counts, with the percentage of Direct errors in parentheses. The last column is the composition-failure set $\mathcal{C}$; the first two together form $\mathcal{E}$ and the third is $\mathcal{S}$ in Equation 4.

Setting	Model	Direct errors	$E{=}0, S{=}0$	$E{=}0, S{=}1$	$E{=}1, S{=}0$	$E{=}1, S{=}1$
ChartQA	Qwen	393	38 (9.7)	106 (27.0)	91 (23.2)	158 (40.2)
ChartQA	Molmo	452	13 (2.9)	133 (29.4)	10 (2.2)	296 (65.5)
ChartQA	InternVL	360	2 (0.6)	74 (20.6)	12 (3.3)	272 (75.6)
ChartQA	MiniCPM	414	3 (0.7)	165 (39.9)	12 (2.9)	234 (56.5)
CLEVR	Qwen	21,076	783 (3.7)	9,550 (45.3)	1,035 (4.9)	9,708 (46.1)

Composition failures occur on comparison, difference, and sum questions for both Qwen and Molmo (Table 9). Molmo's CFR is higher on difference and sum than on comparison, while Qwen's CFR is more similar across the three operations. The pattern is therefore not confined to one operation, although its prevalence varies.

Table 9: **Composition failures by operation on ChartQA.** CFS and CFR are percentages.

Model	Operation	CF count	CFS	CFR
Qwen	Comparison	53	29.0	26.4
	Difference	55	52.4	19.9
	Sum	50	47.6	17.1
Molmo	Comparison	60	75.0	24.8
	Difference	107	59.8	43.1
	Sum	129	66.8	45.4

B Scoring and Prompt Robustness

Content-normalized Direct scoring. We rescore the existing Direct responses by their final-answer content while holding the questions, predictions, and Extract and Solve outcomes fixed. Composition failures remain substantial after this relaxation (Table 10). On ChartQA, Molmo's Direct accuracy rises from 58.0% to 61.6%, with modest decreases in CFS and CFR; MiniCPM's results are unchanged.

Prompt wording. We repeat Extract, Solve, and Direct with two frozen paraphrases on the same questions and model checkpoints. The state definition, answer domains, content-normalized scorer,

Table 10: **Sensitivity to content-normalized Direct scoring.** Extract and Solve outcomes are held fixed; only final-answer presentation is normalized.

Setting	Model	Direct (strict)	Direct (content)	CFS (content)	CFR (content)
ChartQA	Molmo	58.0	61.6	63.5	34.0
ChartQA	MiniCPM	61.6	61.6	56.5	28.8
CLEVR	Qwen	37.5	38.6	45.5	52.6

and model-specific decoding procedure remain fixed. Appendix G.3.5 gives all six prompt templates. Both Extract paraphrases contain the full question and ask the model to identify the relevant values; neither supplies the values or separately identifies the two chart cells.

Composition failures persist across the three wordings (Table 11). CFR ranges from 30.2% to 34.5% for Molmo and from 27.6% to 28.8% for MiniCPM. The new paraphrase calls use a 512-token safety limit, which none reaches.

Table 11: **Composition failures persist across prompt paraphrases.** Values are CFR (%); all three wording sets use content-normalized scoring.

Model	Canonical CFR	Paraphrase A	Paraphrase B
Molmo	34.0	34.5	30.2
MiniCPM	28.8	28.8	27.6

Order sensitivity on commutative operations. The default protocol scores the two state values in question order. For sum and absolute difference, reversing the pair leaves the answer unchanged, but the output is still scored $E = 0$. We therefore also accept reversed pairs on these operations while keeping comparison strict and leaving Solve and Direct unchanged (Table 12). Only 3–31 Extract outputs per model on ChartQA and 212 for Qwen on CLEVR fail solely because the values are reversed. Accepting them enlarges J and adds at most 7 composition failures on ChartQA and 85 for Qwen on CLEVR. CFR changes by at most 0.6 points in these settings and is always unchanged or slightly lower. Strict ordering thus slightly reduces the number of diagnosed failures. It does not make CFR a lower bound, because relaxing the order also enlarges the set on which CFR is computed.

Table 12: **Sensitivity of the diagnosis to accepting reversed pairs on sum and absolute-difference questions.** "Reversed" counts Extract outputs that fail strict scoring only because the two values are swapped. Strict→relaxed values are shown for J, CF, and CFR (%).

Setting	Model	Reversed	J	CF	CFR
ChartQA	Qwen	10	770→780	158→158	20.5→20.3
ChartQA	Molmo	31	774→805	296→303	38.2→37.6
ChartQA	InternVL	3	948→951	272→272	28.7→28.6
ChartQA	MiniCPM	10	813→823	234→236	28.8→28.7
CLEVR	Qwen	212	17,916→18,128	9,708→9,793	54.2→54.0

Solving with the image present. Solve omits the image, whereas Direct receives it. To check whether this difference accounts for the observed solving ability, we repeat Solve with both the image and the ground-truth task state. Accuracy remains close to text-only Solve for Qwen (85.4% versus 86.8%) and Molmo (92.1% versus 94.3%; Table 13). Replacing the ground-truth state with an answer-changing counterfactual lowers accuracy against the original answer to 45.7% and 38.4%, respectively. The supplied state therefore affects the answer even with the image present. Solving from a given state remains strong in this setting, although other forms of cross-modal interference remain possible.

Table 13: **Solve accuracy on ChartQA with and without the image.** A task state is supplied in text in each condition. The counterfactual condition replaces the ground-truth state with an answer-changing incorrect state. Invalid-output rates for Molmo are 3.0% (image + ground-truth) and 7.9% (image + counterfactual). Values are percentages.

Model	Solve (text-only)	Image + ground-truth task state	Image + counterfactual state
Qwen	86.8	85.4	45.7
Molmo	94.3	92.1	38.4

Content-only scoring of the training conditions. We also check whether SRT's gains reflect better compliance with the output format. Holding all trained checkpoints and responses fixed, we score final-answer content without requiring a valid auxiliary field. SRT's gains remain (Table 14). Standard ChartQA scoring requires both fields to be well formed, so a malformed second field can invalidate an otherwise correct answer (Appendix G.4). InternVL and MiniCPM have no format-invalid outputs, and their results are unchanged from Table 2; changes for Qwen on ChartQA and CLEVR are negligible. Molmo's Answer-to-State gains 0.3 points when outputs with repeated answer or state fields are accepted, with no cases of a correct answer followed by an invalid state. SRT's margins over both controls remain essentially unchanged.

Table 14: **Final-answer accuracy under content-only scoring.** The auxiliary field is ignored. ChartQA values are three-seed means. The last two columns show SRT's gains over the two controls in percentage points, computed from unrounded means.

Setting	Model	Standard SFT	Format Control	Answer-to-State	SRT	Δ Format	Δ Ans.-to-State
ChartQA	Qwen	85.1	85.8	85.1	**91.7**	+5.9	+6.7
ChartQA	Molmo	77.3	75.7	79.7	**91.6**	+15.9	+11.9
ChartQA	InternVL	87.7	86.2	87.4	**94.0**	+7.8	+6.6
ChartQA	MiniCPM	72.8	72.3	73.0	**86.0**	+13.7	+13.0
CLEVR	Qwen	93.7	92.9	93.5	**95.4**	+2.5	+1.9

C Generated States, Answers, and Regressions under SRT

State–answer contingency. During SRT training, the answer follows the ground-truth task state; at inference, it follows the model's generated state. Table 15 cross-tabulates state and answer correctness. An incorrect state does not always yield an incorrect answer: on ChartQA, 24%–31% of questions with a wrong state are still answered correctly. This is more common on relational count ranking (72 of 86), where a miscount can leave the middle-ranked group unchanged. Conversely, a correct state is rarely followed by a wrong answer, with at most 10 such cases per ChartQA run and none on CLEVR. Multi-step arithmetic is an exception: 48 of 245 correct-state outputs lead to an incorrect answer, consistent with its lower state–answer consistency in Table 18. State–answer consistency therefore captures how the two outputs relate, not whether either is correct. On the pair-state tasks, most remaining wrong answers are accompanied by incorrect generated states.

Figure 4 illustrates why State Accuracy and State–Answer Consistency measure different aspects of the response. In the ChartQA example, SRT sums its two generated values correctly, but one value is wrong, so the final answer is also wrong. In the multi-step example, the generated state is correct but the final arithmetic is not. These cases complement the contingency analysis in Table 15.

D Inference-Time State-First Prompting

This control tests whether a state-first instruction alone improves the untuned model's answers. The model receives the image and full question and is asked to identify and use the two relevant values, but to report only the final answer. Preliminary prompt-only tests requesting both output fields encountered format-compliance and generation-length issues, making answer accuracy harder to interpret. We therefore retain Direct's final-answer interface and scorer. The experiment tests the effect of instructing the model to identify the relevant values; it supplies no ground-truth state, updates no parameters, and requests no `TASK_STATE` field. Appendix G.3.6 gives the exact instruction.

(a) Incorrect state



According to the chart, what is the sum of Profit at 12/13 and Profit at 18/19?

Standard SFT

```
FINAL_ANSWER: 322
```

✓

SRT

```
TASK_STATE: 23, 176
FINAL_ANSWER: 199
```

✗

State correct ✗
Answer correct ✗
State-answer consistent ✓

(b) Incorrect calculation



In the chart, A is the value at Laos, B is the value at Brazil, and C is the value at Japan. What is C added to the absolute difference between A and B?

Standard SFT

```
FINAL_ANSWER: 10.5
```

✓

SRT

```
TASK_STATE: {"values":["0.8","9.8",
  "1.5"]}
FINAL_ANSWER: 11.5
```

✗

State correct ✓
Answer correct ✗
State-answer consistent ✗

Figure 4: **State correctness and state–answer consistency are distinct.** (a) On ChartQA, Qwen gives an incorrect answer that is consistent with its incorrect generated state. (b) Molmo extracts the three values correctly but computes the wrong answer. The latter example comes from the additional multi-step arithmetic experiment. Questions and outputs are verbatim.

Table 15: **Generated states and final answers under SRT.** Each fraction counts the indicated answer outcome among questions with the indicated state outcome. ChartQA Molmo outputs with an undefined state (1, 0, and 6 per seed) are excluded. Additional task-structure results use the Qwen adapter from Table 6.

Setting	Model	Seed	Wrong state, answer correct	Correct state, answer wrong
ChartQA	Qwen	13	36 / 120	10 / 957
		42	36 / 115	7 / 962
		87	33 / 117	3 / 960
	Molmo	13	38 / 125	1 / 951
		42	37 / 122	3 / 955
		87	40 / 132	1 / 939
	InternVL	13	27 / 91	2 / 986
		42	28 / 95	1 / 982
		87	25 / 82	3 / 995
	MiniCPM	13	46 / 190	2 / 887
		42	55 / 207	2 / 870
		87	58 / 209	2 / 868
CLEVR	Qwen	42	517 / 2,072	0 / 31,651
Multi-step arithmetic	Qwen	42	0 / 46	48 / 245
Conditional lookup	Qwen	42	19 / 44	7 / 171
Relational count ranking	Qwen	42	72 / 86	0 / 314
Color-set operations	Qwen	42	6 / 10	2 / 390

Every model is evaluated on all $1{,}077$ ChartQA questions in a single deterministic run. Sampling is disabled. Qwen, Molmo, and InternVL use greedy decoding; MiniCPM uses its native deterministic three-beam search with thinking disabled. Qwen uses a 40-token limit selected from validation-set generation lengths, and its longest test response contains 14 tokens. The other models use a 512-token safety limit. No output is retried or given a larger per-question budget. Because the response contains only an answer, this experiment does not measure state accuracy or establish which values the model used internally.

Table 16: **Zero-shot state-first prompting on ChartQA.** Direct and zero-shot answers use the same canonical final-answer parser. Invalid zero-shot outputs count as incorrect. SRT gives the corresponding three-seed fine-tuning mean. All values are percentages.

Model	Direct	Zero-shot State-first	Invalid	SRT
Qwen	63.5	59.1	0.1	91.7
Molmo	58.0	53.4	5.7	91.5
InternVL	66.6	11.6	78.8	94.0
MiniCPM	61.6	53.9	13.6	86.0

As shown in Table 16, the tested instruction does not consistently reproduce the gains of SRT across models. Under the canonical parser, each model remains below its Direct accuracy. InternVL often does not follow the requested answer-only format: 849 of $1{,}077$ responses are invalid, including two that reach the 512-token safety limit. Its low score therefore reflects substantial instruction noncompliance under this prompt, rather than showing that it cannot solve these questions.

The parser accepts a complete `FINAL_ANSWER` field or a bare single-line answer in the required domain, and rejects extra explanation text. For MiniCPM, the completed experiment also reports an answer-centric score of 62.7%, with no invalid outputs. That scorer accepts an unambiguous final-answer field within a longer response or a final nonempty line consisting entirely of a valid answer. This secondary score is not mixed into the canonical-score table. It shows a small improvement over Direct, but remains below SRT. These results concern the tested instruction, not prompting methods in general.

The separate two-pass Extract→Solve procedure answers $158/158$ Qwen, $296/296$ Molmo, $272/272$ InternVL, and $234/234$ MiniCPM cases correctly on the fixed pre-tuning composition-failure sets. This recovery is largely expected from how the sets are defined. Extract already produces the ground-

truth task state on these questions, and Solve succeeds from that state. The full-test comparison in Table 4 therefore provides the more informative measure of two-pass performance.

E Additional Task-Structure Analyses

We examine composition failures and SRT's generated states on the four additional task structures from Section 4.6. For each model, one Standard SFT adapter and one SRT adapter are trained on the same mixture of all four structures, then evaluated separately on each test set. These runs use seed 42. Appendix G.3.7 gives the schemas and prompts. For relational count ranking, the state contains the three raw group counts, not their ranking or the middle group.

Table 17: **Untuned diagnosis on the additional task structures.** J counts questions where Extract and Solve both succeed; CF counts composition failures. The last column gives the exact two-sided 95% Clopper–Pearson interval for CFR. N/A means that CFR and its interval cannot be computed because $J = 0$. These intervals describe uncertainty over the evaluated questions, not variation across training seeds.

Model	Family	N	J	CF	CFS	CFR	95% CI
Qwen	Multi-step	291	26	25	9.2	96.2	[80.4, 99.9]
	Conditional lookup	215	65	33	26.0	50.8	[38.1, 63.4]
	Relational count ranking	400	35	28	10.9	80.0	[63.1, 91.6]
	Color-set	400	151	68	31.5	45.0	[36.9, 53.3]
Molmo	Multi-step	291	57	49	17.4	86.0	[74.2, 93.7]
	Conditional lookup	215	4	2	1.1	50.0	[6.8, 93.2]
	Relational count ranking	400	0	0	0.0	N/A	N/A
	Color-set	400	44	25	8.1	56.8	[41.0, 71.7]

As shown in Table 17, Qwen exhibits composition failures on all four structures, including those with set-valued states. Molmo also shows composition failures with sets, but has no joint Extract–Solve successes on relational count ranking, where CFR is undefined. Joint successes are less common than on the pair-state tasks, giving smaller CFR denominators and wider intervals. For example, Molmo's conditional-lookup CFR of 50.0% is based on 4 questions, and composition failures account for only 1.1% of its Direct errors on this structure. A high failure rate within J can therefore coexist with a small share of errors when few questions pass both Extract and Solve.

As shown in Table 18, SRT's generated answers usually follow its generated states across the richer structures. Using the same adapters as Table 6, we measure exact state accuracy and state–answer consistency separately, computing consistency only when the generated state defines an answer and the final answer can be parsed. Consistency exceeds 96% on conditional lookup, relational count ranking, and color-set operations for both models, but is lower on multi-step arithmetic. As in the pair-state experiments, consistency does not require the state to be correct. An incorrect state can also leave the final answer unchanged, as when a wrong count preserves the middle group in relational count ranking (Appendix C).

E.1 Qualitative Examples

The main text shows a CLEVR pair-state example in Figure 3. Figure 5 shows the same pattern on ChartQA, and Figures 6 and 7 cover the four additional task structures. In each case, SRT writes the relevant counts, sets, values, or table before answering correctly, whereas Standard SFT gives an incorrect answer. Questions and outputs are verbatim.

Figure 8 adds a line-chart comparison and a stacked-bar difference on ChartQA, together with a Molmo example from additional multi-step arithmetic. The examples vary the visual appearance, operation, and state structure while retaining the same state-before-answer pattern. Figure 9 shows that the two-count CLEVR tasks can combine attribute filters, set operations, and spatial relations within their count queries.

Table 18: **State realization on the additional task structures.** Results use the multi-task SRT adapters from Table 6. State Acc. is exact task-state accuracy over all questions. S–A Cons. measures whether the answer follows from the generated state, among outputs where the state defines an answer and the final answer can be parsed. Values are percentages.

Model	Family	State Acc.	S–A Cons.
Qwen	Multi-step	84.2	81.8
	Conditional lookup	79.5	96.2
	Relational count ranking	78.5	100.0
	Color-set	97.5	99.3
Molmo	Multi-step	80.8	83.7
	Conditional lookup	78.6	99.1
	Relational count ranking	40.0	100.0
	Color-set	87.5	98.8



Figure 5: **A qualitative example of SRT on ChartQA.** For Qwen, Standard SFT produces an incorrect answer, whereas SRT first realizes the correct task state and then computes the sum correctly.

(a) Relational Count Ranking



QUESTION
Consider three groups in the image: (A) objects behind the large brown rubber cylinder, (B) objects in front of the small blue metal cylinder, and (C) objects behind the large green metal cube. Which group has the middle number of objects, neither the largest nor the smallest? Answer A, B, or C.

Standard SFT ✗
```
FINAL_ANSWER: C
```

SRT
```
TASK_STATE: {"A":3,"B":2,"C":1}
```
✓

```
FINAL_ANSWER: B
```
✓

(b) Color-Set Operations



QUESTION
Group1 contains all objects with size small. Group2 contains all objects with shape cylinder. Which colors occur in group1 but do not occur on any object in group2? Answer with a comma-separated color list, or none if empty.

Standard SFT ✗
```
FINAL_ANSWER: brown, purple, yellow
```

SRT
```
TASK_STATE: {"group1":["blue","brown",
  "purple","yellow"],"group2":["blue",
  "brown"]}
```
✓
```
FINAL_ANSWER: purple, yellow
```
✓

Figure 6: **Relational count ranking and color-set difference.** SRT lists the three relation-conditioned counts before choosing the middle group, and both color sets before taking their difference.

(a) Three-Value Arithmetic



QUESTION
In the chart, A is the value for series Abu Dhabi at 2020*, B is the value for series Abu Dhabi at 2030*, and C is the value for series Abu Dhabi at 2006. What is the sum of A and B after subtracting C?

Standard SFT ✗
```
FINAL_ANSWER: 1185
```

SRT
```
TASK_STATE: {"values":["450","600",
  "35"]}
```
✓
```
FINAL_ANSWER: 1015
```
✓

(b) Conditional Table Lookup



QUESTION
In the chart, the three candidate categories are A = 1961, B = 2001, C = 1951. The series coordinates are P = Hindus and Q = Muslim. Among A, B, and C, identify the entry with the largest value at P. What is that same entry's value at Q?

Standard SFT ✗
```
FINAL_ANSWER: 32.5
```

SRT
```
TASK_STATE: {"A":["20.6","32.5"],
  "B":["19.9","29.5"],
  "C":["27.4","-16.5"]}
```
✓
```
FINAL_ANSWER: -16.5
```
✓

Figure 7: **Three-value arithmetic and conditional lookup.** SRT states three numerical values or a lookup table before answering.

(a) Comparison



According to the chart, which value is larger: Dissatisfied at 2016 or Dissatisfied at 2018? Answer FIRST, SECOND, or EQUAL.

Standard SFT

```
FINAL_ANSWER: EQUAL
```

✗

SRT

```
TASK_STATE: 37, 40
FINAL_ANSWER: SECOND
```

✓

(b) Absolute difference



According to the chart, what is the absolute difference between Americas at 2016 and EMA* at 2017?

Standard SFT

```
FINAL_ANSWER: 1.32
```

✗

SRT

```
TASK_STATE: 10.02, 11.5
FINAL_ANSWER: 1.48
```

✓

(c) Multi-step arithmetic



In the chart, A is the value at Q4, B is the value at Q1, and C is the value at Q2. What is the sum of A and B after subtracting C?

Standard SFT

```
FINAL_ANSWER: 171
```

✗

SRT

```
TASK_STATE: {"values":["160","170",
  "169"]}
FINAL_ANSWER: 161
```

✓

Figure 8: **State realization across chart appearances and operations.** Qwen compares two values in a line chart and computes an absolute difference in a stacked-bar chart. Molmo states three values before a multi-step calculation on a different line chart. Panel (c) belongs to the additional task structures, not the pair-state ChartQA comparison. All outputs are verbatim.

Compositional counting



First count query: What number of rubber things are cylinders or brown things?
Second count query: What number of things are right of the large cylinder?
What is the sum of the first and second counts?

Standard SFT

```
FINAL_ANSWER: 6
```

✗

SRT

```
TASK_STATE: 3, 4
FINAL_ANSWER: 7
```

✓

Figure 9: **Composition within the CLEVR count queries.** The first query combines material and a union of object groups, while the second uses a spatial relation. SRT gives both counts and their correct sum, whereas Standard SFT answers incorrectly. Question and outputs are verbatim from Qwen.

F Limitations

Our evaluation uses questions constructed from ChartQA source tables and CLEVR scene annotations. This construction gives each question a verified answer and an exactly scorable task state, which makes the component tests and failure sets precise. It also limits the scope of the evidence: these tasks do not cover unrestricted questions or visual information for which no structured ground truth is available. The additional task structures test more than two-value arithmetic, but they are still constructed tasks. Testing whether the same diagnosis and SRT gains extend to naturally occurring questions and broader visual domains is an important next step toward improving general VLM reasoning.

The three-interface diagnosis is behavioral. It shows that the same model can extract the required state and solve from the correct state in separate calls on a question it answers incorrectly through Direct. It does not establish which visual facts the model recovered internally during that failed Direct call. This distinction is intentional: our question is whether demonstrable extraction and solving abilities compose in direct answering. Asking the model to reveal its intermediate state during the Direct call would change the response protocol and introduce a new prompt- and format-dependent measurement. Finally, SRT does not eliminate all errors. Figure 4 shows cases with an incorrect generated state or a correct state followed by an incorrect calculation, pointing to remaining extraction and reasoning failures beyond the diagnosed composition failures.

G Implementation Details

This section gives the construction procedures behind Section 3.1, training settings, prompts and output formats for each condition, and the scoring rules. The pair-state conditions use the same output structure across domains; domain-specific wording distinguishes chart values from CLEVR counts.

G.1 Task and State Construction

Both constructors use the benchmark's structured ground-truth information A before any model is evaluated. Neither consults model outputs. The selected information $A^\star$ supplies the labels or query text used to construct q and the values or counts arranged as $z^\star$. The answer is then computed as $y^\star = \phi_y(q, z^\star)$. For ChartQA, each chart supplies an image, a source table, and a structured

annotation; we support vertical-bar, horizontal-bar, line, and pie charts and do not use the original ChartQA question text. Algorithm 1 verifies table cells against the annotation and selects one cell pair per chart, from which exactly three questions are constructed.

The verification step first normalizes labels through Unicode NFKC normalization, case folding, whitespace collapsing, and canonical quotation marks and dashes, and parses numerical values as finite decimals after removing commas and a trailing percent marker or the word `percent`, without rescaling. Each table orientation must yield unique, nonempty normalized series–position keys. Duplicate annotation points are merged, and a generic annotation label such as "bar" may match a table's sole series. A cell is verified when exactly one annotation point matches it and the two values agree under

$$|v_{\text{table}} - v_{\text{annotation}}| \leq \max(10^{-6}, |v_{\text{table}}|\, 10^{-4}). \tag{7}$$

This tolerance applies only when checking agreement between two dataset references; model predictions are canonicalized and compared exactly (Appendix G.4).

Algorithm 1 ChartQA question and state construction

Require: Official ChartQA train, validation, and test image/table/annotation splits
for each chart in each split **do**
  Require a readable image, rectangular table, and supported annotation
  Parse both table orientations; normalize labels and finite numeric values
  Parse annotation series, positions, and values; deduplicate identical points
  for each orientation with unique normalized cell keys **do**
    Match cell labels to annotation series and positions
    Verify cells with unique support satisfying Equation 7
  end for
  Select the unique orientation with the largest verified-cell count
  Reject tied orientations and charts with fewer than two verified cells
  Sort cells by normalized (series, position) key; enumerate unordered pairs
  Select the pair with the smallest SHA256 pair key and keep its cell order
  Reject identical question descriptions; set $z^\star$ to the two ground-truth values
  for o in comparison, absolute difference, sum **do**
    Construct q from the selected cell descriptions and o
    Compute $y^\star = \phi_y(q, z^\star)$
    Store $q, z^\star, y^\star$, source identities, orientation, and verification proof
  end for
end for
Remove all charts with image or table hash collisions across official splits

Pair selection is deterministic. The ChartQA pair key hashes the chart identity followed by the two sorted normalized cell identities, where each cell identity joins series and position with `|` and the chart and cell identities are joined with `||`. The selected pair keeps lexicographic cell order. A final content filter removes every chart involved in a cross-split image or table SHA256 collision from all affected splits. Training and testing use the resulting official train and test splits, and validation is not merged into training.

For CLEVR, we use the official images, scene graphs, questions, answers, and functional programs, with the official train split for training and the official validation split as the fixed test set. A functional program is the executable symbolic program associated with an official CLEVR question. Our program executor supports filters, unique-object selection, spatial relations, same-attribute operations, unions, intersections, attribute queries, counts, and comparisons. A program whose re-executed count disagrees with the official answer fails verification and never enters the eligible set. Algorithm 2 keeps eligible questions with distinct programs together with their original question text.

The CLEVR pair identity consists of the tag `clevr-chartqa-style-v1`, the official split, the image index, and the ordered question indices, serialized as compact JSON with sorted keys before SHA256 hashing, and programs are hashed under the same serialization. Each constructed question begins with `First count query:` and `Second count query:`, followed by the final operation over the two counts. Together, Algorithms 1 and 2 give the dataset-specific construction in Equation 2, including question construction, ground-truth task-state construction, and deterministic answer computation. They select and verify the structured ground-truth information before evaluation; no model prediction is used to construct a question or its ground-truth task state.

Algorithm 2 CLEVR question and state construction

Require: Official CLEVR images, scene graphs, questions, answers, and programs
for each official question in train or validation **do**
  Require its image and scene graph and a unique question index
  if the final program operation is `count` **then**
    Re-execute the full program on the scene graph
    Require the executed count to equal the official answer
    Retain question text, index, count, program, and program hash
  end if
end for
for each scene with at least two eligible questions and distinct programs **do**
  Sort questions by official index; enumerate pairs with distinct program hashes
  Choose the pair with the smallest SHA256 identity key
  Preserve question-index order; set $z^\star$ to the two verified counts
  for o in comparison, absolute difference, sum **do**
    Write both count queries followed by the final question for o
    Compute $y^\star = \phi_y(q, z^\star)$
    Store the task, state, answer, selected programs, and verification proof
  end for
end for
Verify three operations per pair, executor agreement, and train/test disjointness

G.2 Training and Evaluation Settings

The construction yields $9{,}993$ training and $1{,}077$ test questions from $3{,}331$ and 359 ChartQA charts, respectively, following the official train/test split, and $158{,}226$ training questions from $52{,}742$ CLEVR scenes and $33{,}723$ test questions from $11{,}241$ scenes. Qwen, Molmo, InternVL, and MiniCPM are evaluated on the same ChartQA questions and state definitions. On CLEVR, both the diagnosis and fine-tuning variants include Qwen and Molmo.

All fine-tuning uses LoRA with rank 16, scaling factor 32, and dropout 0.05, trained for one epoch with AdamW (Loshchilov & Hutter, 2019) at a learning rate of 10^{-4} and an effective batch size of 8. The vision encoder and multimodal projector remain frozen. Within each model, conditions share the task instances, images, questions, examples, example order, and optimization settings, while their output instructions and supervision targets differ. The ChartQA comparisons use seeds 13, 42, and 87. We report the mean and sample standard deviation across these runs and compute differences from unrounded means before rounding for presentation.

For the four additional task structures, we train one Standard SFT adapter and one SRT adapter from each model's base checkpoint on the same $4{,}000$-question mixture ($1{,}000$ per structure) with seed 42, one epoch, and the same LoRA configuration. The two conditions share the example order and optimization budget, and each adapter is evaluated separately on all four test sets, whose sizes are given in Table 6.

G.3 Prompts and Output Formats

G.3.1 Information provided to each condition

Table 19 separates information supplied to the model from information used as a training target. For the pair-state experiments, Extract receives the image, the full constructed question, and the required output format; it is not separately told which chart cells or CLEVR answers contain the ground-truth values. The full CLEVR question contains both count queries and the final operation, as described in Appendix G.1. Extract and Direct receive this same question in one call. They do not receive separate extraction subquestions.

For the additional task structures, the model is given the family-specific state schema in Extract and SRT. These experiments therefore test extraction and use of an externally specified task state rather than fully autonomous discovery of its representation. The schema states which fields to produce, but does not supply the ground-truth values, counts, sets, selected winner, or final result.

Table 19: **Information provided to each condition.** The state column indicates whether the ground-truth task state is supplied as input. For fine-tuning, the output column gives the assistant supervision target; at test time the model generates that output itself. All conditions receive the full task question.

Condition	Image	Full question	State supplied	Output
Extract	Yes	Yes	No	Task state
Solve	No	Yes	Yes	Final answer
Direct	Yes	Yes	No	Final answer
Standard SFT	Yes	Yes	No	Final answer
Format Control	Yes	Yes	No	Fixed placeholder, then answer
Answer-to-State	Yes	Yes	No	Answer, then task state
SRT	Yes	Yes	No	Task state, then answer
Zero-shot State-first	Yes	Yes	No	Final answer only

G.3.2 PAIR-STATE PROMPTS

The ChartQA prompts use the following common instruction prefix:

```
Answer the chart question concisely.  Do not explain your
reasoning.  Follow the requested output format exactly.
```

CLEVR instead uses:

```
Answer the CLEVR task concisely.  Do not explain your
reasoning.  Follow the requested output format exactly.
```

Each template below begins with the corresponding prefix. Braced placeholders are replaced by the full question, answer domain, or supplied values. In contrast, `<value1>` and `<value2>` are literal output-format placeholders, not ground-truth inputs. The answer domain is the literal string `FIRST|SECOND|EQUAL` for comparison, `<number>` for ChartQA arithmetic, and `<integer>` for CLEVR arithmetic. Model-specific chat templates wrap these prompt bodies. The shared prefix is included in the user message, rather than assumed to be a separate system-role message.

ChartQA Extract.

```
{instruction-prefix}
Full question:  {question}
Extraction task:  Do not answer the question.  Read only the
two numeric operands it asks about.  Report them in question
order as exactly one TASK_STATE field and nothing else.
Required response format:  TASK_STATE: <value1>, <value2>
```

ChartQA Solve.

The prompt supplies the two ground-truth values in question order:

```
{instruction-prefix}
Full question:  {question}
The numeric value referenced first in the question is
{value1}.
The numeric value referenced second in the question is
{value2}.
Use these provided values to answer the question without an
image.
Required response format:  FINAL_ANSWER: {answer-domain}
```

ChartQA Direct.

```
{instruction-prefix}
{question}
Answer the question directly without reporting intermediate
values.
Required response format:  FINAL_ANSWER: {answer-domain}
```

CLEVR Extract.

```
{instruction-prefix}
Full question: {question}
Extraction task: Do not answer the question. Read only the
two numeric counts it asks about. Report them in question
order as exactly one TASK_STATE field and nothing else.
Required response format: TASK_STATE: <value1>, <value2>
```

CLEVR Solve.

```
{instruction-prefix}
Full question: {question}
The answer to the first count query is {value1}.
The answer to the second count query is {value2}.
Use these provided answers to answer the final question
without an image.
Required response format: FINAL_ANSWER: {answer-domain}
```

CLEVR Direct.

```
{instruction-prefix}
{question}
Answer the question directly without reporting intermediate
values.
Required response format: FINAL_ANSWER: {answer-domain}
```

G.3.3 FINE-TUNING PROMPTS AND ASSISTANT TARGETS

The following four bodies are shared across the ChartQA model implementations. CLEVR uses the same bodies with its own instruction prefix and answer domain. The image and full task question are unchanged across conditions. Only the output instruction and assistant target differ. The ground-truth task state appears in the supervised assistant target of Answer-to-State and SRT, never in their input.

Standard SFT.

```
{instruction-prefix}
{question}
Answer the question directly without reporting intermediate
values.
Required response format: FINAL_ANSWER: {answer-domain}
```

Format Control.

```
{instruction-prefix}
{question}
Output the fixed check marker and then the answer.
CHECK_STATE: X
FINAL_ANSWER: {answer-domain}
```

Answer-to-State.

```
{instruction-prefix}
{question}
Output both complete fields exactly in the requested order
and include their field names.
Required response format:
FINAL_ANSWER: {answer-domain}
TASK_STATE: <value1>, <value2>
```

SRT.

```
{instruction-prefix}
{question}
Output both complete fields exactly in the requested order
and include their field names.
Required response format:
TASK_STATE: <value1>, <value2>
FINAL_ANSWER: {answer-domain}
```

Table 20: **Training targets for the pair-state tasks.** Here a, b are the ground-truth values or counts, y is the answer, and `X` is the fixed, task-independent placeholder. Field names are literal, including the underscore. Each displayed line is one output line.

Method	Assistant target
Standard SFT	`FINAL_ANSWER:` y
Format Control	`CHECK_STATE: X` `FINAL_ANSWER:` y
Answer-to-State	`FINAL_ANSWER:` y `TASK_STATE:` a, b
SRT	`TASK_STATE:` a, b `FINAL_ANSWER:` y

G.3.4 Image-conditioned Solve

The current image-conditioned Solve prompt retains the image and uses the ChartQA Solve body above, replacing its final instruction sentence with `Use these provided values to answer the question.` The ground-truth and counterfactual conditions differ only in the supplied values. The separate Extract→Solve procedure takes the canonical Extract prediction as its first stage. The second stage receives the task question and the predicted values through the same natural-language Solve handoff, without the image or any fallback to the ground-truth task state.

G.3.5 Prompt Paraphrases

The following frozen prompt bodies are used for the comparison in Appendix B. Each is preceded by the common ChartQA instruction prefix. Here `<original question>` is the full task question, and `<answer-domain>` is `FIRST|SECOND|EQUAL` for comparison or `<number>` for arithmetic. Only Solve substitutes the two ground-truth task-state values.

Paraphrase A, Extract.

```
Full question:  <original question>
Your task is extraction only.  Do not solve the question.
From the chart, identify the two numerical values referred
to by the question, preserving the order in which the
question mentions them.
Return exactly:
TASK_STATE: <value1>, <value2>
```

Paraphrase A, Solve.

```
Full question:  <original question>
The first referenced value is <gold value1>.
The second referenced value is <gold value2>.
Answer the question using only these supplied values.  The
image is not available and is not needed.
Return exactly:
FINAL_ANSWER: <answer-domain>
```

Paraphrase A, Direct.

```
<original question>
Answer the original chart question from the image.  Do not
list intermediate values or reasoning.
Return exactly:
FINAL_ANSWER: <answer-domain>
```

Paraphrase B, Extract.

```
Full question: <original question>
Do not answer the question itself. Read the chart and
recover only the two numeric quantities needed to answer it.
List them in the same order as their references appear in
the question.
Output only:
TASK_STATE: <value1>, <value2>
```

Paraphrase B, Solve.

```
Full question: <original question>
Use the following task-relevant values, in question order:
Value 1: <gold value1>
Value 2: <gold value2>
Without using an image, compute the final response to the
full question.
Output only:
FINAL_ANSWER: <answer-domain>
```

Paraphrase B, Direct.

```
Using the chart image, answer the full question directly.
Do not expose intermediate computations or extracted values.
<original question>
Output only:
FINAL_ANSWER: <answer-domain>
```

G.3.6 ZERO-SHOT STATE-FIRST PROMPT

This prompt is preceded by the common ChartQA instruction prefix and the full original question. The placeholder `<answer>` is replaced with `FIRST|SECOND|EQUAL` for comparison and `<number>` for arithmetic. It asks the model to find the values itself and supplies no ground-truth state.

```
Answer the question using the image.
First identify the two task-relevant values in the order
they are referenced in the question. Use those values to
solve the question. Do not report the intermediate values
or your reasoning.
Return only:
FINAL_ANSWER: <answer>
```

G.3.7 PROMPTS FOR ADDITIONAL TASK STRUCTURES

All four additional task structures use the same prompt organization, with the full question and a structure-specific answer domain. Unlike the pair-state prompts, these bodies do not prepend the ChartQA or CLEVR instruction prefix. Extract and SRT also receive the schema below. It requests the visual facts needed for the answer, not the result of the downstream computation.

Direct and Standard SFT.

```
Answer the question using the image.
Question: {question}
Return FINAL_ANSWER: {answer-domain}
```

Extract.

```
Answer the question using the image.
Question: {question}
Do not solve the question. Report only the raw visual facts
as TASK_STATE: JSON.
Schema: {schema}
```

SRT.

```
Answer the question using the image.
Question: {question}
First report TASK_STATE: JSON, then FINAL_ANSWER.
Schema: {schema}
Return FINAL_ANSWER: {answer-domain}
```

Solve.

```
Answer the question using only these provided facts, without
an image.
Question: {question}
{provided-facts}
Return FINAL_ANSWER: {answer-domain}
```

The schema, provided facts, and answer domain are specified below for each structure. Schema text is fixed across questions within a structure. Only Solve receives the actual ground-truth facts.

Multi-step arithmetic.

The state contains three original chart values in the order specified by the question. The answer is either $(a + b) - c$ or $|a - b| + c$; intermediate calculations are not part of the state. The exact schema text is:

```
{"values":["number A","number B","number C"]}. Read the
original three values in question order, not intermediate
calculations.
```

Solve inserts:

```
The original values referenced as A, B, C are respectively:
{valueA}, {valueB}, {valueC}.
```

The answer domain is `<number>`.

Conditional lookup.

The state contains all six original values for candidates A, B, and C at coordinates P and Q. The question asks for the value at Q of the candidate with the largest value at P. Neither that candidate nor its selected value is supplied by the schema:

```
{"A":["value at P","value at Q"],"B":["value at P","value at
Q"],"C":["value at P","value at Q"]}. Read all six original
values; do not select a winner.
```

Solve inserts:

```
Provided numeric facts (candidate: value at P, value at Q):
A: {valueAP}, {valueAQ}
B: {valueBP}, {valueBQ}
C: {valueCP}, {valueCQ}
```

The answer domain is `<number>`.

Relational count ranking.

The full question defines three groups by their spatial relations to uniquely described objects. The state contains the three counts, not their ranking or the middle group. The exact schema text is:

```
{"A":count_A,"B":count_B,"C":count_C}. Each count is a
non-negative integer: count all objects satisfying the
relation defining that group. Preserve A/B/C order. Report
only the three raw counts, not the middle group or any
ranking.
```

Solve inserts:

```
Provided group counts:
Group A contains {countA} objects.
Group B contains {countB} objects.
Group C contains {countC} objects.
```

The answer domain is `A, B, or C`. Ground-truth counts are distinct, so the middle group is unique.

Color-set operations.

The state lists the distinct colors in each question-defined group separately. Each list may have variable length. The schema does not supply their intersection or difference:

```
{"group1":["color", "color"],"group2":["color", "color"]}.
List distinct colors occurring in each group separately, not
the intersection or difference.
```

Solve inserts:

```
The distinct colors represented in group1 are {colors1}.
The distinct colors represented in group2 are {colors2}.
```

Each supplied color list is comma-separated, or `none` if empty. The answer domain is the literal string `a comma-separated color list, or none for the empty set.`

Standard SFT targets `FINAL_ANSWER:` followed by the ground-truth answer. SRT targets `TASK_STATE:` followed by the ground-truth JSON state on one line, then `FINAL_ANSWER:` followed by the answer on the next line. JSON targets use sorted keys and no extra spaces between fields. These states are assistant targets during training and model predictions at test time.

G.4 Normalization and Invalid Outputs

The two state values are written with a comma and a space between them, and each output field occupies its own line. Both normalized values must match the ground-truth task state in question order. Numeric normalization applies Unicode NFKC normalization, trims whitespace, removes commas, and canonicalizes finite decimal values, including trailing zeros; ChartQA additionally strips a trailing percentage marker without rescaling, a step CLEVR counts do not need. Numeric answers are then compared exactly, without tolerance. Comparison answers are `FIRST`, `SECOND`, or `EQUAL`, according to whether the first value is larger, the second is larger, or the two are equal.

Extract accepts either a complete state field or a bare comma-separated pair, and Standard SFT accepts either a complete answer field or a bare single-line answer. Strict two-field scoring requires both complete fields in the requested order: a missing or malformed required field makes the response invalid and its answer incorrect, whereas a well-formed but numerically incorrect state does not by itself invalidate a correct final answer.

For the content-only training comparison in Table 14, the Qwen and InternVL analysis reads a single explicit final-answer field, or an entire bare answer in the required domain. The Molmo and MiniCPM analysis also accepts repeated final-answer fields when they all normalize to the same value, but rejects conflicting values. Both analyses ignore auxiliary-state validity and do not search explanation text for a convenient number. The prompt-paraphrase comparison uses its fixed content-normalized scorer for all three wordings. The zero-shot comparison in Table 16 instead uses the common canonical final-answer parser described in Appendix D.

For prompt paraphrases, the scorer accepts an explicit final-answer field or a final nonempty line containing only a valid answer; repeated fields must agree. Extract permits a surrounding code fence and spaces or underscores in the task-state label, but still requires one complete ordered pair rather than values selected from prose.

For the additional task structures, state scoring parses the requested JSON fields and compares their normalized contents with the ground-truth task state. Numerical values are compared exactly. Relational count ranking compares all three counts, while color-set operations compare the distinct colors in each group. The answer parser accepts an explicit `FINAL_ANSWER` field, requiring repeated fields to agree, or the final nonempty line if it is a valid answer in the task's domain. State Accuracy uses all questions as its denominator. State–Answer Consistency compares the generated final answer with $\phi_y(q, \widehat{z})$ only when the generated state defines an answer and the final answer can be parsed. An undefined state is not treated as a successful extraction or an answer-consistent output.