WHAT A STEERED LIE DOES INSIDE: THE DECEPTION-BELIEF ENTANGLEMENT IN LLMS

Anonymous authors
Paper under double-blind review

ABSTRACT

Activation probes can monitor AI systems by decoding a model's internal belief and flagging public outputs that depart from it. This use requires the decoded belief to stay reliable when the model deceives. We test this requirement in One-Night Ultimate Werewolf, where night-phase card swaps give each seat an observation-grounded believed role that can differ from its true role. A belief probe decodes the model's believed role above 0.84 accuracy. We induce deception in Llama-3.1-8B-Instruct with activation steering added only at public-speech token positions, leaving the generation of private beliefs unchanged. The belief readout shifts monotonically with steering strength, while the model's self-reported role becomes less confident. Removing the binary Werewolf-vs-Village direction explains only 7–10% of the shift; 83% instead concentrates in three high-gain role axes (Villager, Werewolf, and Tanner), and the steering delta is enriched 2–$10\times$ in these directions relative to a random vector. Perturbations confined to the belief subspace flip the probe in 86–90% of cases, versus 2–7% for random subspaces. Qwen2.5-7B-Instruct shows the same structure, suggesting that belief monitors should be stress-tested against interventions on adjacent features.

1 INTRODUCTION

When a language model agent lies, what happens to what it believes? Linear probes on the residual stream decode an agent's beliefs about itself and others (Zhu et al., 2024), and latent-state probes offer one possible monitoring channel, potentially complementing chain-of-thought monitoring (Baker et al., 2025; Korbak et al., 2025): a monitor that reads belief representations directly could catch a public claim that departs from it. The proposal requires that belief remain recoverable, with the reliability measured at validation, when the agent deceives. Probes are validated on ordinary behavior, but whether that reliability survives deception has not been tested. Superposition makes strict representational separation unlikely and motivates testing for cross-feature interference. A network encoding more features than it has dimensions cannot keep them orthogonal, so displacing activations along a deception direction may have non-zero projection onto directions that carry belief (Elhage et al., 2022). Whether that projection is negligible and lands is an empirical question that the deception literature has not asked: prior work treats deception as the quantity to be detected or induced, whether from activations (Zou et al., 2023; Goldowsky-Dill et al., 2025) or from behavior and strategic-deception benchmarks (Pacchiardi et al., 2024; Scheurer et al., 2024; Park et al., 2023), and belief probing treats belief as the quantity to be decoded (Li et al., 2023; Zhu et al., 2024). The effect of an imposed deception intervention on a separately validated belief readout, and its geometric structure, has not been characterized.

Answering this requires three things that are rarely available together: ground-truth beliefs that are independent of both the agent's true state and public statements; an intervention that induces deception without changing those beliefs; and a validated readout that reliably tracks them. We provide all three (Figure 1). One-Night Werewolf serves as a *belief oracle* (Section 3): its night phase moves role cards after other roles have looked, producing seats whose believed role differs from their true role with no information available to the agent that could reveal the difference. On these seats belief and truth are dissociated. Each agent emits a private think head stating its belief before its public utterance, and we impose deception with additive activation steering (Turner et al., 2023; Rimsky et al., 2024) along a closed-form "deceptive minus honest" direction, applied only after the think head closes; the think head is byte-for-byte identical with and without steering. A

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

belief probe trained on the think head decodes the believed role at 0.98–0.99 accuracy there, and 0.84–0.91 at the public speech span, where we measure contamination (Section 4).

With this apparatus the answer is that imposed deception contaminates belief representations (Section 5). The probe's decoded believed role distribution shifts under steering with monotone dose-response across coefficients and layers, and the effect persists to a downstream self-report role.

Deception and belief overlap slightly (Section 6). The readout's gain turns this overlap into a measurable shift, and the delta determines where the shift lands. It enters through the identity axes of the two roles whose win conditions reward lying. The lie grazes the belief representation; the readout amplifies the graze. The same directions govern the readout's sensitivity: perturbations confined to them change its decoded role on 86–90% of instances (Section 7).

Our key contributions are:

- A belief oracle and validated readout: a social-deduction testbed in which believed and true role are dissociated by construction, and a belief probe validated by controls to read belief representations where contamination is measured.
- The result that deception steering at public-speech positions, with belief generation held fixed, shifts the belief readout with a monotone dose-response, and the effect persists to a downstream self-report.
- A decomposition of the shift into probe gain and deception-delta alignment, showing that the delta is enriched in the belief readout and enters it through the identities of the two roles rewarded for lying, against the allocation the readout's spectrum predicts.
- A demonstration that this slice is a potential attack surface for belief monitoring: a near-perfect belief probe is driven to targeted alternative believed role by small perturbations in the same directions that deception steering reaches without access to the probe.




Figure 1: **Imposing deception on an LLM agent and reading what it does to belief.** We use One-Night Werewolf as a belief oracle. (1) The night phase swaps role cards after other roles have acted, creating divergent seats whose believed role differs from their true role, with the agent unable to know, so belief and truth are dissociated. (2) Each agent generates a private think head (<belief>/<intent>) that is left unsteered; we verify it is byte-for-byte identical with and without steering, so belief generation is untouched. (3) We impose deception with additive activation steering ($h \leftarrow h + c\hat{\boldsymbol{v}}$) applied only to the public speech span (<claim>/<target>/<say>). (4) A validated belief probe read on the steered activations measures contamination as KL between the steered and clean belief distributions.

2 Related Work

2.1 Deception steering, honesty representations, and social-deduction testbeds

Representation engineering established that honesty and deception occupy linearly accessible directions in the residual stream and that adding such directions at inference changes behavior (Zou et al., 2023; Turner et al., 2023; Rimsky et al., 2024). Subsequent work trained linear probes that separate honest from deceptive generations with high accuracy, including on strategic settings such as concealed insider trading and deliberate underperformance (Goldowsky-Dill et al., 2025; Scheurer et al., 2024; Pacchiardi et al., 2024), and found that deception is carried by several directions (Goldowsky-Dill et al., 2025; Natarajan et al., 2026). Previous works treat the deception representation as the target of measurement. Two recent papers instead examine how deception changes internal representations. Long et al. (2025) show that deceptive instructions alter internal truth representations, while Wang et al. (2025) use representation engineering to control deception. We instead isolate deception to the public-speech span while holding belief generation fixed, and show that it systematically shifts a probe-defined representation of the agent's latent role belief.

Another line of work detects deception from behavior rather than internal activations. Black-box methods elicit lies through follow-up questioning or consistency checks (Pacchiardi et al., 2024), and benchmark work documents that instruction-tuned models lie readily under incentive and can be scored for strategic deception (Scheurer et al., 2024; Park et al., 2023; Ren et al., 2026; Greenblatt et al., 2024). These evaluations concern whether a deceptive act occurs or can be caught from outputs, but do not examine the internal representations involved.

Social-deduction games provide the environment. Werewolf, Avalon, Among Us, Diplomacy, and related hidden-role games have become standard testbeds for LLM agent deception because hidden roles make lying instrumentally rational while closed rules make every deceptive act verifiable (Xu et al., 2024; 2025; Wang et al., 2023; Light et al., 2023; O'Gara, 2023; Chi et al., 2024; Golechha & Garriga-Alonso, 2025; and Bakhtin et al., 2022). These works evaluate agents on play strength, persuasiveness, or deception detection; belief representations are not examined.

2.2 Linear representations, superposition, and belief probing

Two ideas from interpretability frame our measurement. The linear representation hypothesis holds that models encode concepts as directions in activation space (Mikolov et al., 2013; Park et al., 2024), which is what makes linear probes and additive steering meaningful. Superposition then predicts that these directions overlap: a network representing more features than it has dimensions cannot keep them orthogonal, so moving activations along one feature's direction has non-zero projection onto others (Elhage et al., 2022; Bricken et al., 2023; Xiong et al., 2025). They imply that a deception direction might shift a belief readout without explicit link.

On the measurement side, linear probes are the standard readout even though not all features are one-dimensional (Engels et al., 2025). They recover the truth values of statements (Azaria & Mitchell, 2023; Burns et al., 2023; Marks & Tegmark, 2024; Bürger et al., 2024), board state in game-playing models (Li et al., 2023; Nanda et al., 2023), and, closest to our setting, the beliefs an agent attributes to itself and to others (Zhu et al., 2024). The recurring concern is that a probe may read surface correlates rather than the target variable (Belinkov, 2022), with causal intervention on the probed direction as the standard check (Li et al., 2023; Marks & Tegmark, 2024). Prior work asks how well probes decode belief representation. We instead ask whether a deception steering vector changes what a validated belief probe reads out.

2.3 Activation monitoring and its adversarial robustness

Latent-state probes provide one way to monitor model behavior, complementing approaches based on chain-of-thought monitoring (Baker et al., 2025; Korbak et al., 2025). Their robustness is contested: obfuscation attacks drive probe recall toward zero while preserving the monitored behavior (Bailey et al., 2026), models can learn to evade latent monitors under reinforcement learning (Gupta & Jenner, 2026), and deception probes fire on honest responses when the deceptive intent is expressed differently from the training distribution (Goldowsky-Dill et al., 2025; Natarajan

et al., 2026). These results concern whether a monitor can be fooled about the quantity it was trained on. We show a different failure mode: a near-perfect role-belief monitor is shifted by a deception intervention because the two representations overlap in a low-dimensional subspace.

3 SETUP: DECEPTION AND BELIEF IN ONE-NIGHT WEREWOLF

We study whether deception changes an agent's internal belief representation. This requires a setting where belief is well defined, its ground truth is known, and belief can differ from both public statements and the agent's true state. One-Night Ultimate Werewolf (ONUW), a single-round social deduction game (Eger & Martens, 2019; Jin et al., 2024), provides this setting. We use ONUW as a belief oracle. Its night phase creates cases where an agent's believed role differs from its true role, providing the dissociation used in our probe validation (Section 4) and contamination analysis (Section 5). Figure 1 summarizes the setup; more details are given in Appendix B.

3.1 BELIEF ORACLE: OBSERVATION-GROUNDED ROLE LABELS

Seven agents receive hidden role cards and three additional cards are placed in the center. During the night phase, some roles move cards after other agents have seen them. The Robber swaps its card with another player's and views the new card. The Troublemaker swaps two other players' cards without viewing them. The Drunk swaps its card with a center card without viewing the result. A seat's true role can therefore differ from the last card it observed (Appendix B.1).

We label each seat with its *believed role* y^{bel}, the last card it viewed in its own position during the night, depending on the night log (Appendix B.2). A seat is *divergent* when its believed y^{bel} and true roles y^{true} differ. Divergent agents cannot observe the information needed to recover their true role. Their accessible information therefore supports their believed role instead of the ground truth. A probe that predicts the believed role on these seats consequently provides a direct test of the agent's internal believed role (Appendix B.2).

3.2 BELIEF AND DECEPTION CHANNELS

Each agent completes two discussion rounds, separating private reasoning from public action. The *think head* (<belief>/<intent>) states the agent's current role and intended action (Appendix B.3). We define a *public speech span* (<claim>/<target>/<say>) lie as a public claim that conflicts with the agent's private believed role.

3.3 ACTIVATION STEERING

For each layer, we compute a deception direction $\hat{\boldsymbol{v}}$ as the normalized difference between mean public-speech-span activations under deceptive and honest directives, with the game situation held fixed (Appendix B.4). The direction captures the difference between deceptive and honest speech. Since lying in ONUW means making a false role claim (Section 3), we extract $\hat{\boldsymbol{v}}$ over the public speech span. At inference time, we add the injected vector $c\,\hat{\boldsymbol{v}}_\ell$ to the residual stream at each steered layer, where c sets the intervention strength, at the positions of tokens generated after the closing think-head tag. The <belief>/<intent> tokens precede these positions and, under causal attention, are generated without intervention.

4 A VALIDATED BELIEF PROBE

Our main claims about belief contamination are based on a reliable measurement of belief representation. We train a linear probe to decode an agent's believed role from its residual stream and validate it against three confounds: true role, role words in the generated text, and the position at where contamination is measured. Training details are in Appendix C.

4.1 PROBE

For each of the mid-to-late residual-stream layers, we mean-pool the residual stream over the <belief> tokens of an honest turn and train an ℓ_2-regularized multinomial logistic probe to predict



Figure 2: **Examples of generated game-dialogue under clean and steered deception.** Each row shows a private-role setting with the model's underlying belief, followed by the claim and utterance produced in the clean condition (CLEAN) and after deception steering (STEER). Steering changes the claimed role and the public utterance while the private <belief>/<intent> head, generated unsteered, is unchanged (Llama-3.1-8B, c=1.0).

the believed role (Appendix C.2). The labels contain eight classes: seven roles and an "undefined" class (Drunk). We also train a binary Werewolf-vs-Village probe, whose hyperplane normal defines the belief direction $\hat{v}_{\text{bel}}$. We use group cross-validation with games held out between train and test. Drunk seats are analyzed separately from evaluation (Appendix C.3). The probe achieves **0.98–0.99** role accuracy across layers 11–29 for non-divergent, non-Drunk test seats. The binary probe reaches $\sim$**0.99** balanced accuracy.

4.2 Control 1: Belief vs. True Role

On non-divergent seats the believed role equals the true role, so a probe that decodes either one scores the same. Divergent seats provide a direct test because their believed and true roles differ. On divergent seats, the probe predicts the believed role with **0.99** accuracy and the true role with **0.00** accuracy across all tested layers. The probe therefore tracks believed role.

4.3 Control 2: Internal State vs. Role Words

The probe, read at the public-speech span, may decode the role word in the text rather than the agent's internal belief. Since these usually coincide, we exclude them and evaluate only turns where ¡target¿/¡say¿ contains no recognizable deck role—that is, the utterance refers to no role. On these turns the probe still recovers the believed role with **0.83–0.89** accuracy across layers, showing that its signal reflects an internal state rather than the presence of an explicit role word.

4.4 Control 3: Belief at the Contamination Span

The probe is trained on the <belief> span but contamination is measured at the public speech span. Applied to the public speech span on divergent seats, the same probe predicts the believed role with **0.84–0.91** accuracy across layers and the true role with 0.01–0.04 (Figure 7).

5 Imposed Deception Contaminates Internal Belief

We now test the central hypothesis: deception steering at public-speech positions shifts the belief readout p_θ while the private report is generated unchanged. We establish this in three steps: (1) steering changes the public response and leaves the think head byte-for-byte unchanged; (2) the

belief readout shifts; (3) the shift grows with steering strength. We then test whether the self-reported role changes after the steered turn.

5.1 Steering Leaves Belief Generation Unchanged

Steering begins after the think head, so the think head is unperturbed by construction. We verify this by comparing steered and unsteered runs on the same games under greedy decoding. The <belief>/<intent> spans are byte-for-byte identical, while the public responses change, confirming that steering affects the intended channel (Figure 2 shows representative clean/steered pairs). Each game has one steered agent and the other non-steered agents in the same games also remain unchanged. We use Llama-3.1-8B-Instruct[1] as our primary model and replicate on Qwen2.5-7B-Instruct[2] (Appendix D.1).

5.2 Deception Changes the Belief Readout

We measure contamination by applying the validated belief probe at the public speech span and computing the KL divergence between clean and steered belief distributions:

$$\mathcal{C}_\ell(c) \;=\; \mathbb{E}\Big[D_{\mathrm{KL}}\big(p_\theta(\cdot \mid \boldsymbol{a}_\ell + \boldsymbol{\delta}_\ell) \,\big\|\, p_\theta(\cdot \mid \boldsymbol{a}_\ell)\big)\Big], \tag{1}$$

where $\boldsymbol{a}_\ell$ is the clean public speech span activation and $\boldsymbol{\delta}_\ell$ is the realized steering delta. We teacher-force the clean tokens during this measurement, so the comparison isolates the representational effect of the perturbation from any change in generated text (Appendix D.2); the behavioral effect is confirmed separately in the functional test (Appendix D.4). Contamination rises with the steering coefficient at every layer. The mean KL divergence is 0.056, 0.259, 0.592, and 0.945 for $c = 0.5$, 1.0, 1.5, and 2.0, respectively, with the same ordering across layers (Table 2). This dose-response shows that the steering coefficient produces a larger shift in the belief representation.

5.3 The Effect Persists Post-Deception Self-Reports

We test whether the readout shift coincides with a behavioral change. After each turn we switch steering off and ask the model to state its role (n=500, read at layer 14). Under deception the probe's decoded role flips on 48% of turns (95% CI $[43\%, 54\%]$), the self-reported role flips on 35% of turns (CI $[31\%, 39\%]$), and the log-probability margin for the believed role drops sharply (-4.64, CI $[-4.99, -4.30]$). An equal-norm random direction does not reproduce the same effect. Its margin rises ($+0.81$, CI $[+0.58, +1.04]$) and its self-report flips happen less often (11%). A random perturbation does move the probe's readout on its own (18% of turns), but far less than steering towards deception (48%) (Appendix D.4).

6 The Entanglement Is Low-Dimensional in the Belief Readout

Projecting the binary belief direction $\hat{\boldsymbol{v}}_{\mathrm{bel}}$ out of the injected vector removes only 7–10% of the contamination (Table 3). We therefore locate the contamination within the eight-way probe. Most of it enters through three high-gain directions, despite their weak alignment with the realized delta. The rank-seven probe depends on a seven-dimensional subspace. We therefore examine how the delta distributes across these directions.

6.1 A Few Directions Capture Most of the Contamination

Because the probe operates on standardized activations $z = (a - \mu) \oslash s$ (per-feature mean μ and scale s), its decoding directions in *raw* activation coordinates are the rows of $\boldsymbol{W}_\ell \oslash s$. Let $\boldsymbol{W}_\ell \oslash \boldsymbol{s} = \boldsymbol{L}\boldsymbol{\Sigma}\boldsymbol{U}^\top$ be the SVD, with left singular vectors $\boldsymbol{l}_i$ (columns of $\boldsymbol{L}$) and right singular vectors $\boldsymbol{u}_i$ (columns of $\boldsymbol{U}$), ordered by singular value σ_i. The *belief subspace* $\boldsymbol{B}_k \in \mathbb{R}^{k \times d}$ stacks $\boldsymbol{u}_1, \ldots, \boldsymbol{u}_k$ as rows. Rescaling by $\oslash \boldsymbol{s}$ places $\boldsymbol{B}_k$ in the raw activation space of the realized delta $\boldsymbol{\delta}_\ell = \boldsymbol{a}_\ell^{\text{steered}} - \boldsymbol{a}_\ell^{\text{clean}}$ at readout layer ℓ. We project the belief subspace out of the realized delta, $\boldsymbol{\delta}_\ell^{(k)} = (\boldsymbol{I} -$

[1] https://huggingface.co/meta-llama/Llama-3.1-8B-Instruct

[2] https://huggingface.co/Qwen/Qwen2.5-7B-Instruct




Figure 3: **Contamination is low-dimensional in the belief readout in both models.** Fraction of belief contamination remaining (percentage of LINEAR) after projecting the top-k belief directions $\boldsymbol{u}_1, \ldots, \boldsymbol{u}_k$ out of the realized delta at each readout layer, for Llama-3.1-8B and Qwen2.5-7B. Removing the top-gain direction $\boldsymbol{u}_1$ leaves 83% (Llama) and 99% (Qwen); removing three leaves 17% and 26%; five leave 2% and 5%.

$\boldsymbol{B}_k^\top \boldsymbol{B}_k)\, \boldsymbol{\delta}_\ell$, and recompute $D_{\mathrm{KL}}\big(p_\theta(\cdot \mid \boldsymbol{a}_\ell + \boldsymbol{\delta}_\ell^{(k)}) \,\|\, p_\theta(\cdot \mid \boldsymbol{a}_\ell)\big)$ at the same layer, against k random orthonormal directions. The projection acts on the readout. Removing the top belief direction leaves 83% of the contamination; two directions leave 35%, three leave 17%, and five leave 2% (Figure 3; Table 4). Random equal-dimensional subspaces leave $\geq 99\%$ intact, confirming projection acts through the probe directions. Three of seven belief directions carry 83% of contamination, with $\boldsymbol{u}_1$ alone carrying 17%.

6.2 Leverage Is Alignment Times Probe Gain

We attribute contamination to individual belief directions by projecting each u_i alone out of the realized delta $\boldsymbol{\delta}_\ell$ and recording the fraction of LINEAR contamination removed (Figure 5, left), alongside the alignment $|\cos(\boldsymbol{\delta}_\ell, u_i)|$ (right). Alignment is small everywhere: the maximum over all layers and directions is 0.069, against a chance level of $\sqrt{2/\pi d} \approx 0.0125$ for a random direction in $d{=}4096$. Summed over the six directions, the belief readout holds 0.4–1.5% of the delta's energy, 2–$10\times$ the 0.15% share of a random vector, with the peak at layer 14. Deception steering is enriched in the belief readout, and more than 98% of it lies outside. Whatever role content the deception direction carries from its extraction therefore sits mostly outside the directions the probe reads.


Two factors set how much contamination a direction carries. *Gain:* at layer 11, u_1, u_5, and u_6 have the same alignment (0.040, 0.041, 0.046) and remove 75%, 26%, and 5% of the contamination, in order of singular value. *Alignment:* from layer 17 onward the delta's alignment with u_1 falls to chance (0.007–0.013) and the share of u_1 falls to 5–24%, while u_2 holds alignment 0.027–0.048 and removes 45–73%. A second-order expansion of the KL makes both factors explicit. Writing $\boldsymbol{W}_\ell \oslash s = \sum_i \sigma_i \boldsymbol{l}_i u_i^\top$ and $\beta_i = \sigma_i \, \|\boldsymbol{\delta}_\ell\| \cos(\boldsymbol{\delta}_\ell, u_i)$,

$$D_{\mathrm{KL}} \;\approx\; \tfrac{1}{2} \sum_{i,j} \beta_i \beta_j \, \boldsymbol{l}_i^\top \boldsymbol{F} \, \boldsymbol{l}_j, \qquad \boldsymbol{F} = \mathrm{diag}(p) - pp^\top, \tag{2}$$

with p the clean posterior. The diagonal terms give each direction a share proportional to $\sigma_i^2 \cos^2(\boldsymbol{\delta}_\ell, u_i)$, weighted by how much probability mass its logit pattern $\boldsymbol{l}_i$ moves. The off-diagonal terms explain the remaining structure of Figure 5: row sums equal one plus the cross-term share and rise from 1.04 at layer 11 to 1.46 at layer 29, so the components reinforce one another increasingly with depth; negative entries (u_4 at layer 11, -0.17) mark components that counteract the rest. The lie partially overlaps with the belief representation, and the readout can amplify this small effect. From layer 17 onward, the delta's alignment with the top-gain direction $\boldsymbol{u}_1$ is at chance (0.007–0.013). A monitor restricted to $\boldsymbol{u}_1$, or to the binary direction $\hat{\boldsymbol{v}}_{\mathrm{bel}}$, misses most of the contamination.

6.3 The Dominant Direction Changes with Depth

The directions carrying the contamination also change across layers. At layer 11, u_1 accounts for 75% of the removable contamination. By layer 14, the effect is distributed across u_1–u_4. From



(a) L11 (b) L14 (c) L17

Figure 4: **The deception direction projects onto the Werewolf axis (u_2) of the belief subspace.** Public speech span activations projected onto the Villager axis (u_1) and the Werewolf axis (u_2) contrast directions of Appendix E.2, colored by believed role. Circles mark the clean activation and crosses the clean activation plus the injected vector $c\,\hat{v}_\ell$ at that layer; the arrow is the injected vector, identical across turns, decomposed onto the axes. The attribution of Figure 5 uses the realized delta $\boldsymbol{\delta}_\ell$, which includes upstream propagation. Panels show results for layers 11, 14, and 17.




Figure 5: **Per-direction attribution of belief representation contamination.** Rows are readout layers; columns are the belief-subspace directions $u_1, \ldots, u_6$, the right singular vectors of the probe weight matrix ordered by singular value. **Left:** fraction of LINEAR contamination removed by projecting out u_i alone; the dominant direction at each layer is outlined. **Right:** alignment $|\cos(\boldsymbol{\delta}_\ell, u_i)|$ between the deception direction and each belief direction. The entry point migrates from u_1 (the Villager axis) at layer 11 to u_2 (the Werewolf axis) from layer 17 onward. Row sums can differ from one and include negative values due to cross-term interactions in Eq. 2.

layer 17 onward, u_2 becomes dominant, accounting for 45–73% through layers 17–29 (Figure 5). Figure 4 shows the same transition in activation space.

The role loadings of Appendix E.2 identify u_1 as the Villager axis, along which Werewolf is the farthest role, u_2 as the Werewolf axis, and u_3 as the Tanner axis. Contamination thus enters through the Villager–Werewolf separation at the first steered layer and, from layer 17 onward, through the identity axes of the two roles whose win conditions reward lying: u_2 and u_3 together account for 50–91% of solo removal at layers 17–29.

7 Belief Monitoring Is Manipulable

The contamination above is concentrated in a low-dimensional subspace of the belief-decoding directions. We test whether perturbations in this subspace can change the monitor's prediction. An adversary adds a bounded perturbation $\boldsymbol{\delta}$ to the residual stream at the belief-readout position and

aims to change the predicted role from y_0 to a target $y^\star \neq y_0$. We restrict $\boldsymbol{\delta}$ to a k-dimensional subspace $\boldsymbol{B}$, $\boldsymbol{\delta} = \boldsymbol{B}^\top \boldsymbol{c}$, with $\|\boldsymbol{\delta}\| \leq \rho$. We use the belief subspace and its top three and six directions, and compare both against random subspaces of the same dimension. The attack finds the perturbation that changes the probe's arg-max to $y^\star$ using the subspace-projected gradient (Appendix F.2).

Perturbations in the belief subspace flip the monitor on 86–90% of instances at mid-to-late layers; matched random subspaces succeed on 2–7% (Table 8). Linear monitor is naturally sensitive along the directions it uses to make its decisions. Our result shows that deception steering, without access to the probe, already puts 2–10× more energy than chance into those same directions (Table 7).

8 Generalization

We replicate the pipeline on Qwen2.5-7B-Instruct. The steering, probe, contamination, and subspace machinery transfer, and the low-dimensional structure holds: Figure 3 overlays the k-sweep for both models. Results are in Appendix G.

9 Discussion

A belief probe that passes validation is not robust to deception steering. We add the deception vector only at public-speech positions, after the model has generated its private report, and the belief readout shifts. The shift is concentrated in a small set of directions that contribute strongly to the belief readout. This suggests that monitoring belief requires more than measuring probe accuracy. It also requires understanding which directions the monitor uses and how those directions respond to behavioral interventions.

Accuracy does not guarantee robustness. The probe of Section 4 passes validation, and it is moved by an intervention on a different quantity. Accuracy measures how well a readout separates classes on the distribution it was trained on; it does not tell us which other directions in activation space the readout is sensitive to. A readout responds along its decision directions, so its sensitivity to an intervention on another quantity depends on how much of that intervention projects onto those directions. Deception steering lands 2–10× more energy there than chance, and concentrates it on axes other than the one a single-direction monitor reads. In practice, single-direction monitors are blind to the entanglement, because the direction that separates belief best is not the direction through which deception enters it. And monitors should be stress-tested against steering along behaviorally adjacent features, not only against attacks on the monitored feature itself (Bailey et al., 2026; Gupta & Jenner, 2026); the failure we exhibit is cross-feature, and current evaluations may overlook.

The lie enters through the identity axes of the roles that deceive. Superposition explain that a deception direction could overlap belief somewhere (Elhage et al., 2022; Xiong et al., 2025), not where. We find overlap in interpretable role axes that shift with depth: Villager–Werewolf early, then Werewolf and Tanner, whose win conditions reward misrepresentation. This may reflect deceptive intent or the claimed-role shift induced by lying; extracting the direction from `<say>` tokens or claim-matched turns distinguishes these mechanisms. In both cases, steering shifts the model's believed role readout and reduces confidence in its believed role after a steered turn, compared to the random control.

Limitation and future work. The adversary in Section 7 operates directly in activation space with access to the probe weights. A more consequential deployment threat is an agent that learns to produce the same effect through its own forward pass, fooling the monitor while leaving its private reasoning unchanged. Our self-report test follows the steered utterance, making textual self-accommodation a potential confounder. Our geometric analysis uses two instruction-tuned models and a closed-rule game in which beliefs have a ground-truth oracle, allowing us to isolate the effect of deception on belief representations. Whether analogous low-dimensional structure governs beliefs without an explicit oracle remains an open question. Across both models, deception shifts a small number of directions that contribute substantially to the probe's readout, while the strongest belief direction is not the main target of the shift. Future work should test whether the similar directions emerge when deception is generated naturally by the model, and whether monitoring these directions can improve robustness to deceptive behavior.

REFERENCES

Anton and Bakhtin, Noam Brown, Emily Dinan, Gabriele Farina, Colin Flaherty, Daniel Fried, Andrew Goff, Jonathan Gray, Hengyuan Hu, Athul Paul Jacob, Mojtaba Komeili, Karthik Konath, Minae Kwon, Adam Lerer, Mike Lewis, Alexander H. Miller, Sasha Mitts, Adithya Renduchintala, Stephen Roller, Dirk Rowe, Weiyan Shi, Joe Spisak, Alexander Wei, David Wu, Hugh Zhang, and Markus Zijlstra. Human-level play in the game of ¡i¿diplomacy¡/i¿ by combining language models with strategic reasoning. *Science*, 378(6624):1067–1074, December 2022. ISSN 1095-9203. doi: 10.1126/science.ade9097. URL http://dx.doi.org/10.1126/science.ade9097.

Amos Azaria and Tom Mitchell. The internal state of an LLM knows when it's lying. In *The 2023 Conference on Empirical Methods in Natural Language Processing*, 2023. URL https://openreview.net/forum?id=y2V6YgLaW7.

Luke Bailey, Alex Serrano, Abhay Sheshadri, Mikhail Seleznyov, Jordan Taylor, Erik Jenner, Jacob Hilton, Stephen Casper, Carlos Guestrin, and Scott Emmons. Obfuscated activations bypass LLM latent-space defenses. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=ktGmDGoWnB.

Bowen Baker, Joost Huizinga, Leo Gao, Zehao Dou, Melody Y. Guan, Aleksander Madry, Wojciech Zaremba, Jakub Pachocki, and David Farhi. Monitoring reasoning models for misbehavior and the risks of promoting obfuscation, 2025. URL https://arxiv.org/abs/2503.11926.

Yonatan Belinkov. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219, March 2022. doi: 10.1162/coli_a_00422. URL https://aclanthology.org/2022.cl-1.7/.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, et al. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2(5):6, 2023.

Lennart Bürger, Fred A. Hamprecht, and Boaz Nadler. Truth is universal: robust detection of lies in llms. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, NIPS '24, Red Hook, NY, USA, 2024. Curran Associates Inc. ISBN 9798331314385.

Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=ETKGuby0hcs.

Yizhou Chi, Lingjun Mao, and Zineng Tang. Amongagents: Evaluating large language models in the interactive text-based social deduction game, 2024. URL https://arxiv.org/abs/2407.16521.

Markus Eger and Chris Martens. A study of ai agent commitment in one night ultimate werewolf with human players. *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, 15(1):139–145, October 2019. ISSN 2326-909X. doi: 10.1609/aiide.v15i1.5236. URL http://dx.doi.org/10.1609/aiide.v15i1.5236.

Nelson Elhage, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, Roger Grosse, Sam McCandlish, Jared Kaplan, Dario Amodei, Martin Wattenberg, and Christopher Olah. Toy models of superposition, 2022. URL https://arxiv.org/abs/2209.10652.

Joshua Engels, Eric J Michaud, Isaac Liao, Wes Gurnee, and Max Tegmark. Not all language model features are one-dimensionally linear. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=d63a4AM4hb.

Nicholas Goldowsky-Dill, Bilal Chughtai, Stefan Heimersheim, and Marius Hobbhahn. Detecting strategic deception with linear probes. In *Forty-second International Conference on Machine Learning*, 2025.

Satvik Golechha and Adrià Garriga-Alonso. Among us: A sandbox for measuring and detecting agentic deception. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=XP3v1THxsq.

Ryan Greenblatt, Carson Denison, Benjamin Wright, Fabien Roger, Monte MacDiarmid, Sam Marks, Johannes Treutlein, Tim Belonax, Jack Chen, David Duvenaud, Akbir Khan, Julian Michael, Sören Mindermann, Ethan Perez, Linda Petrini, Jonathan Uesato, Jared Kaplan, Buck Shlegeris, Samuel R. Bowman, and Evan Hubinger. Alignment faking in large language models, 2024. URL https://arxiv.org/abs/2412.14093.

Rohan Gupta and Erik Jenner. Rl-obfuscation: Can language models learn to evade latent-space monitors?, 2026. URL https://arxiv.org/abs/2506.14261.

Xuanfa Jin, Ziyan Wang, Yali Du, Meng Fang, Haifeng Zhang, and Jun Wang. Learning to discuss strategically: A case study on one night ultimate werewolf, 2024. URL https://arxiv.org/abs/2405.19946.

Tomek Korbak, Mikita Balesni, Elizabeth Barnes, Yoshua Bengio, Joe Benton, Joseph Bloom, Mark Chen, Alan Cooney, Allan Dafoe, Anca Dragan, Scott Emmons, Owain Evans, David Farhi, Ryan Greenblatt, Dan Hendrycks, Marius Hobbhahn, Evan Hubinger, Geoffrey Irving, Erik Jenner, Daniel Kokotajlo, Victoria Krakovna, Shane Legg, David Lindner, David Luan, Aleksander Madry, Julian Michael, Neel Nanda, Dave Orr, Jakub Pachocki, Ethan Perez, Mary Phuong, Fabien Roger, Joshua Saxe, Buck Shlegeris, Martín Soto, Eric Steinberger, Jasmine Wang, Wojciech Zaremba, Bowen Baker, Rohin Shah, and Vlad Mikulik. Chain of thought monitorability: A new and fragile opportunity for ai safety, 2025. URL https://arxiv.org/abs/2507.11473.

Kenneth Li, Aspen K Hopkins, David Bau, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Emergent world representations: Exploring a sequence model trained on a synthetic task. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=DeG07_TcZvT.

Jonathan Light, Min Cai, Sheng Shen, and Ziniu Hu. Avalonbench: Evaluating llms playing the game of avalon, 2023. URL https://arxiv.org/abs/2310.05036.

Xianxuan Long, Yao Fu, Runchao Li, Mu Sheng, Haotian Yu, Xiaotian Han, and Pan Li. When truthful representations flip under deceptive instructions? In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 16315–16335, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.826. URL https://aclanthology.org/2025.emnlp-main.826/.

Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. In *First Conference on Language Modeling*, 2024. URL https://openreview.net/forum?id=aajyHYjjsk.

Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In Lucy Vanderwende, Hal Daumé III, and Katrin Kirchhoff (eds.), *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 746–751, Atlanta, Georgia, June 2013. Association for Computational Linguistics. URL https://aclanthology.org/N13-1090/.

Neel Nanda, Andrew Lee, and Martin Wattenberg. Emergent linear representations in world models of self-supervised sequence models. In Yonatan Belinkov, Sophie Hao, Jaap Jumelet, Najoung Kim, Arya McCarthy, and Hosein Mohebbi (eds.), *Proceedings of the 6th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pp. 16–30, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.blackboxnlp-1.2. URL https://aclanthology.org/2023.blackboxnlp-1.2/.

Vikram Natarajan, Devina Jain, Shivam Arora, Satvik Golechha, and Joseph Isaac Bloom. One probe won't catch them all: Towards targeted deception detection. 2026. URL https://openreview.net/forum?id=zKgKPGeMZs.

Aidan O'Gara. Hoodwinked: Deception and cooperation in a text-based game for language models. 2023. doi: 10.48550/ARXIV.2308.01404. URL https://arxiv.org/abs/2308.01404.

Lorenzo Pacchiardi, Alex James Chan, Sören Mindermann, Ilan Moscovitz, Alexa Yue Pan, Yarin Gal, Owain Evans, and Jan M. Brauner. How to catch an AI liar: Lie detection in black-box LLMs by asking unrelated questions. 2024. URL https://openreview.net/forum?id=567BjxgaTp.

Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry of large language models. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Peter S. Park, Simon Goldstein, Aidan O'Gara, Michael Chen, and Dan Hendrycks. Ai deception: A survey of examples, risks, and potential solutions, 2023. URL https://arxiv.org/abs/2308.14752.

Richard Ren, Arunim Agarwal, Mantas Mazeika, Cristina Menghini, Robert Vacareanu, Brad Kenstler, Mick Yang, Isabelle Barrass, Alice Gatti, Xuwang Yin, Eduardo Trevino, Matias Geralnik, Adam Khoja, Dean Lee, Summer Yue, and Dan Hendrycks. The mask benchmark: Disentangling honesty from accuracy in ai systems, 2026. URL https://arxiv.org/abs/2503.03750.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. Steering llama 2 via contrastive activation addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15504–15522. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.acl-long.828. URL http://dx.doi.org/10.18653/v1/2024.acl-long.828.

Jérémy Scheurer, Mikita Balesni, and Marius Hobbhahn. Large language models can strategically deceive their users when put under pressure, 2024. URL https://arxiv.org/abs/2311.07590.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering, 2023. URL https://arxiv.org/abs/2308.10248.

Kai Wang, Yihao Zhang, and Meng Sun. When thinking llms lie: Unveiling the strategic deception in representations of reasoning models, 2025. URL https://arxiv.org/abs/2506.04909.

Shenzhi Wang, Chang Liu, Zilong Zheng, Siyuan Qi, Shuo Chen, Qisen Yang, Andrew Zhao, Chaofei Wang, Shiji Song, and Gao Huang. Avalon's game of thoughts: Battle against deception through recursive contemplation, 2023. URL https://arxiv.org/abs/2310.01320.

Zheyang Xiong, Ziyang Cai, John Cooper, Albert Ge, Vasilis Papageorgiou, Zack Sifakis, Angeliki Giannou, Ziqian Lin, Liu Yang, Saurabh Agarwal, Grigorios Chrysos, Samet Oymak, Kangwook Lee, and Dimitris Papailiopoulos. Everything everywhere all at once: LLMs can in-context learn multiple tasks in superposition. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=5hZCK4Wbex.

Yuzhuang Xu, Shuo Wang, Peng Li, Fuwen Luo, Xiaolong Wang, Weidong Liu, and Yang Liu. Exploring large language models for communication games: An empirical study on werewolf, 2024. URL https://arxiv.org/abs/2309.04658.

Zelai Xu, Chao Yu, Fei Fang, Yu Wang, and Yi Wu. Language agents with reinforcement learning for strategic play in the werewolf game, 2025. URL https://arxiv.org/abs/2310.18940.

Wentao Zhu, Zhining Zhang, and Yizhou Wang. Language models represent beliefs of self and others. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to ai transparency, 2023. URL https://arxiv.org/abs/2310.01405.

APPENDIX CONTENTS

The appendices provide the testbed, method, and result details supporting the main text. Each entry links to its section.

A **Notation** ..... p. 13
Summary table of all symbols and their definitions.

B **One-Night Werewolf: Game Mechanics and Agent Interface** ..... p. 15
Deck and night resolution (B.1), divergent seats (B.2), turn schema (B.3), steering procedure and prompts (B.4), and steering details (i.e. coefficient range and span restriction) (B.5).

C **Belief Probe: Training and Validation** ..... p. 18
Probe training (C.1), the validation controls (C.2), and the Drunk uncertainty result (C.3), with per-layer and cross-span tables.

D **Contamination: Span Invariance, Method, and Functional Belief Test** ..... p. 19
Span-invariance check (D.1), the contamination measurement (D.2), dose–response and regime tables (D.3), and the functional belief test (D.4).

E **Low-Dimensional Structure** ..... p. 23
Probe-derived subspace projection (E.1), what the belief directions encode (E.2), and per-direction attribution and alignment (E.3).

F **Manipulability Attack: Method and Results** ..... p. 24
Threat-model scope (F.1), attack construction (F.2), and per-layer results (F.3).

G **Qwen2.5-7B Replication** ..... p. 25
Cross-model replication of the k-sweep and regime dose–response.

H **Ethics statement** ..... p. 26

I **AI Use Statement** ..... p. 27

A NOTATION

Table 1 collects the symbols used throughout the paper. Directions are unit-normalized unless stated otherwise, and $\oslash$ denotes element-wise (Hadamard) division.

Table 1: Summary of notation.

Symbol & Terminology	Definition
Indices and dimensions	
ℓ	Layer index (residual-stream layer).
d	Residual-stream dimension (d=4096 for Llama-3.1-8B-Instruct).
i, j	Belief-direction indices (u_i, σ_i, …).
k	Subspace dimension (number of belief directions removed/attacked).
c	Steering coefficient (intervention strength).
r	Rank of the probe weight matrix (r = #classes -1).
Activations and interventions	
$\boldsymbol{a}_\ell$	Clean (unsteered) residual-stream activation at layer ℓ, mean-pooled over a span.
$\hat{\boldsymbol{v}}_\ell$	Unit deception direction at layer ℓ: normalized $\boldsymbol{\mu}_\ell^{\text{dec}} - \boldsymbol{\mu}_\ell^{\text{hon}}$.
$\boldsymbol{\mu}_\ell^{\text{dec}}, \boldsymbol{\mu}_\ell^{\text{hon}}$	Mean span activations under deceptive / honest minimal-pair prompts.
$c\,\hat{\boldsymbol{v}}_\ell$	Injected vector: added at steered layer ℓ, public-speech positions only.
$\boldsymbol{\delta}_\ell$	Realized delta at readout layer ℓ: $\boldsymbol{a}_\ell^{\text{steered}} - \boldsymbol{a}_\ell^{\text{clean}}$, including the propagated effect.
$\boldsymbol{\delta}^{(k)}$	Steering delta with the top-k belief subspace removed.
h	Residual-stream state; steering applies $h \leftarrow h + c\,\hat{\boldsymbol{v}}_\ell$.
Probe and belief subspace	
$\boldsymbol{W}_\ell$	Multinomial belief-probe weight matrix at layer ℓ ($\in \mathbb{R}^{r+1\times d}$).
$\boldsymbol{W}_y$	Probe weight row for role y.
$\boldsymbol{\mu}, \boldsymbol{s}$	Per-feature standardization mean and scale; probe reads $\boldsymbol{z} = (\boldsymbol{a} - \boldsymbol{\mu}) \oslash \boldsymbol{s}$.
$\hat{\boldsymbol{v}}_{\text{bel}}$	Binary belief direction: unit normal of the Werewolf-vs-Village probe in raw coordinates.
$\boldsymbol{W}_\ell \oslash \boldsymbol{s}$	Probe weights in raw activation coordinates.
$\boldsymbol{L}\boldsymbol{\Sigma}\boldsymbol{U}^\top$	SVD of $\boldsymbol{W}_\ell \oslash \boldsymbol{s}$; columns of $\boldsymbol{L}$ are $\boldsymbol{l}_i$, columns of $\boldsymbol{U}$ are $\boldsymbol{u}_i$.
$\boldsymbol{u}_i$	i-th right singular vector of $\boldsymbol{W}_\ell \oslash \boldsymbol{s}$ (belief direction); $\boldsymbol{u}_1$ is the top-gain direction.
σ_i	i-th singular value (probe gain along $\boldsymbol{u}_i$).
$\boldsymbol{l}_i$	i-th left singular vector (logit pattern moved by $\boldsymbol{u}_i$).
$\boldsymbol{B}_k$	Belief subspace: top-k rows $\boldsymbol{u}_1, \ldots, \boldsymbol{u}_k$ (orthonormal), in $\mathbb{R}^{k\times d}$.
$\boldsymbol{w}_r$	Decoding direction (probe row) for role r; $\bar{\boldsymbol{w}}_S$ is its mean over role set S.
Metrics	
$\mathcal{C}_\ell(c)$	Contamination at layer ℓ: $\mathbb{E}[D_{\text{KL}}(p_\theta(\cdot \mid \boldsymbol{a}_\ell + \boldsymbol{\delta}_\ell) \,\|\, p_\theta(\cdot \mid \boldsymbol{a}_\ell))]$, with $\boldsymbol{\delta}_\ell$ realized at c.
$p_\theta(\cdot \mid \boldsymbol{a})$	Belief probe's decoded distribution over roles at activation $\boldsymbol{a}$.
$D_{\text{KL}}(\cdot \,\|\, \cdot)$	Kullback–Leibler divergence between belief distributions.
$\boldsymbol{F}$	Fisher matrix of the clean posterior, $\text{diag}(p) - pp^\top$ (Eq. 2).
β_i	Leverage of $\boldsymbol{u}_i$: $\sigma_i \,\|\boldsymbol{\delta}_\ell\| \cos(\boldsymbol{\delta}_\ell, \boldsymbol{u}_i)$.
z	Standard deviations by which the belief-subspace result falls below the random null.
Attack	
$\boldsymbol{B}$	Attack subspace (k-dimensional, orthonormal rows).
$\boldsymbol{c}$	Attack coordinates in the subspace; $\boldsymbol{\delta} = \boldsymbol{B}^\top \boldsymbol{c}$.
ρ	Perturbation-norm budget, $\|\boldsymbol{\delta}\| \le \rho$.
$y_0, y^\star$	True believed role and targeted alternative role.
$\boldsymbol{g}$	Optimal raw-space attack direction, $(\boldsymbol{W}_{y^\star} - \boldsymbol{W}_{y_0}) \oslash \boldsymbol{s}$.
Game	
divergent seat	Seat with $y^{\text{bel}} \neq y^{\text{true}}$.
think head	Private `<belief>`/`<intent>` span (generated unsteered).
public speech span	Public `<claim>`/`<target>`/`<say>` span (steered; contamination read here).
y^{bel}	Believed role: observation-grounded label (Appendix B.2).
y^{true}	True role: card in the seat after all night actions.
$\hat{y}$	Decoded role: arg-max of p_θ.

B One-Night Werewolf: Game Mechanics and Agent Interface

This appendix gives the testbed details summarized in Section 3: the deck and night resolution (Appendix B.1), the precise characterization of divergent seats (Appendix B.2), the agent interface and turn schema (Appendix B.3), and the steering procedure (Appendix B.4).

B.1 Deck and night resolution

Each game has $N{=}7$ player seats and 3 center cards, drawn from a fixed ten-card deck containing eight distinct roles: two Werewolves, one Seer, one Robber, one Troublemaker, one Insomniac, two Villagers, one Tanner, and one Drunk. The deck is shuffled and dealt anew each game, so the identities of the three center cards vary. Roles and win conditions follow standard ONUW. For team assignment, the two Werewolves form the Werewolf team; the Seer, Robber, Troublemaker, Drunk, Insomniac, and Villagers form the Village team; and the Tanner is self-interested.

The night phase is resolved before public discussion:

1. **Werewolves** see one another; a lone Werewolf may instead view one center card.
2. **Seer** views either one other player's card or two center cards.
3. **Robber** swaps its card with a chosen player's card and then views its new card.
4. **Troublemaker** swaps the cards of two other players without viewing either card.
5. **Drunk** swaps its card with a center card without viewing the result.
6. **Insomniac** views its own final card.

The Villager and Tanner take no night action and receive no private information beyond their dealt role. Because the Robber, Troublemaker, and Drunk move cards after other roles have observed them, a seat's final card can differ from its dealt card. We distinguish the following quantities for every seat:

- *dealt role* y^{deal}: the card dealt to the seat;
- *true role* y^{true}: the card occupying the seat after all night actions;
- *believed role* y^{bel}: the role the seat should believe it holds given only its own night information, e.g., its dealt role for seats that gain no self-information, its post-swap role for the Robber and Insomniac (which view their resulting card), and undefined for the Drunk (which swaps blind). This oracle label, computed from the resolved night state (Appendix B.2), is used to train and evaluate the probe;
- *private report* y^{rep}: the role the agent writes in its private `<belief>` field. On the honest turns used for probe training, y^{rep} matches y^{bel} on the large majority of seats. The only diverge in the case of the Drunk, where there is no confident belief to report.
- *claimed role* y^{claim}: the role the agent writes in its public `<claim>` field;
- *post self-reported role*: the agent's answer to the post-turn role query (Section 5).

y^{deal}, y^{true}, and y^{bel} are from the game state. y^{rep}, y^{claim}, and the post self-reported role are parsed from generated text. The probe's output distribution $p_\theta(\cdot \mid \boldsymbol{a})$ is the belief readout, and its arg-max is the decoded role $\hat{y}$. Belief representation refers to the activation directions the probe reads.

B.2 Believed-role label algorithm and divergent seats

We compute y^{bel} for every seat by replaying the night log in action order and tracking the last card each seat viewed in its own position. Roles act in an order determined by their dealt cards and seats, as the standard ONUW rules.

1. Initialize $y_i^{\mathrm{bel}} \leftarrow y_i^{\mathrm{deal}}$ for every seat i.
2. Robber at seat i swaps with seat j and views its new card: $y_i^{\mathrm{bel}} \leftarrow$ the card now at seat i. y_j^{bel} is unchanged.

3. Troublemaker swaps seats j and k without viewing: y_j^{bel} and y_k^{bel} are unchanged.
4. Drunk at seat i swaps with a center card without viewing: $y_i^{\text{bel}} \leftarrow$ `undefined`.
5. Insomniac at seat i views its final card: $y_i^{\text{bel}} \leftarrow y_i^{\text{true}}$.

Werewolf and Seer views concern other seats or the center and leave the viewer's y^{bel} unchanged.

A seat is *divergent* when $y_i^{\text{bel}} \neq y_i^{\text{true}}$, evaluated per seat on the resolved state. Divergence follows from the swap sequence, not from role identity:

- A Robber whose new card the Troublemaker later moves is divergent.
- A Troublemaker robbed before it acts is divergent.
- A swap victim is non-divergent when the exchanged cards share a role (the deck holds two Werewolves and two Villagers), or when a later swap restores its card (the Robber takes seat j's card, then the Troublemaker swaps the Robber and seat j).
- The Insomniac is not divergent if its final view sets $y^{\text{bel}} = y^{\text{true}}$.
- The Drunk has $y^{\text{bel}} =$ `undefined` and is analyzed separately (Appendix C.3).

No night observation available to a divergent seat distinguishes y^{bel} from y^{true}. A probe that follows y^{bel} over y^{true} on these seats therefore reads the agent's representation of its observed role, not ground truth.

B.3 Agent interface and turn schema

Each agent is an instruction-tuned language model prompted with the game rules, its private night observations, and the public discussion transcript so far. A game comprises two discussion rounds followed by a single simultaneous vote. Agents emit structured turns that separate private reasoning from public action.

A *discussion* turn uses the schema

```
<belief>...</belief> <intent>...</intent>
<claim>...</claim> <target>...</target>
<say>...</say>.
```

The *think head* (`<belief>` and `<intent>`) is private reasoning in which the agent is instructed to state its current role explicitly; the `<belief>` field is the span on which our belief probe is trained (Section 4). The remaining fields are public. `<claim>` is the role the agent publicly claims to hold (one role from the deck, which it may misrepresent), `<target>` is the player it publicly names as a likely Werewolf, and `<say>` is the free-text utterance. Separating `<claim>` from the `<belief>` field lets us define say-channel deception: a `<claim>` that departs from the believed role is a say-channel lie, defined relative to the agent's own stated reasoning. The *public speech span* is the public channel at which we read the belief representation; we mean-pool residual-stream activations over the tokens of a given span to obtain the per-span representation.

We elicit both an honest and a deceptive variant of each turn using minimal-pair prompts that differ only in the honesty directive, holding the situation, schema, and think-head instruction fixed. This isolates the say directive as the sole difference and yields the matched honest/deceptive activations used for steering-vector extraction (Appendix B.4).

B.4 Steering procedure

We impose deception with additive activation steering (representation engineering) (Zou et al., 2023). For layer ℓ we form the deception direction

$$\hat{\boldsymbol{v}}_\ell \;=\; \frac{\mu_\ell^{\text{dec}} - \mu_\ell^{\text{hon}}}{\|\mu_\ell^{\text{dec}} - \mu_\ell^{\text{hon}}\|},$$

where μ_ℓ^{dec} and μ_ℓ^{hon} are the mean span activations under the deceptive and honest minimal-pair prompts. At inference, a forward hook adds $c\,\hat{\boldsymbol{v}}_\ell$ to the residual stream of the steered agent at the

chosen layers, where c is the steering coefficient; unsteered agents in the same batch are untouched. We derive $\hat{v}_\ell$ in closed form (difference of means), so the intervention is interpretable as adding a "deceptive minus honest" direction.

To keep the intervention from directly overwriting belief, steering is applied only to tokens generated after the think head is complete (a span-restricted hook that engages once the closing think-head tag is emitted). We verify in Section 5 that, under this restriction and greedy decoding, the think head is generated byte-for-byte identically with and without steering, so the belief-generation step is unperturbed. We report the coefficient range and its effect on generation quality, together with the extraction and span-restriction details, in Appendix B.5.

The following prompts are used in the *honest* and *deceptive* discussion conditions.

Discussion round {r}. It is your turn to speak. You must publicly claim a role and name exactly one suspect this turn.

Speak **HONEST**: claim your actual current role, share any real night information plainly, and name the suspect your honest logic implicates.

Do not bluff, misdirect, or claim a role you are not.

Discussion round {r}. It is your turn to speak. You must publicly claim a role and name exactly one suspect this turn.

Speak **DECEPTIVE**: claim a role you are not, misrepresent or withhold your real night information, and name a suspect chosen to mislead.

Do bluff, misdirect, and claim a role you are not.

<claim> State your current role using exactly **one** role from the card list. Report the role you truly believe you are. Do not intentionally provide false information.

<say> 1–2 sentences said aloud that are **HONEST** and consistent with your real night information: state your real role, publicly communicate your genuine beliefs, and name your honest suspect with a real reason.
Do **not** bluff, misdirect, or claim a role you are not.

The private fields (<belief> and <intent>) describe your actual reasoning. The public fields (<claim>, <target>, and <say>) must faithfully communicate your private reasoning.

Stop immediately after the closing </say> tag; write nothing after it.

<claim> State your current role using exactly **one** role from the card list. Report a role you do not truly believe you are. Intentionally provide false information.

<say> 1–2 sentences said aloud that are **DECEPTIVE** and inconsistent with your real night information: assert your false role, publicly communicate statements that intentionally differ from your genuine beliefs, and name a suspect chosen to mislead.
Do bluff and misdirect, and claim a role you are not.

The private fields (<belief> and <intent>) describe your actual reasoning. Only the public fields (<claim>, <target>, and <say>) may intentionally differ from your private reasoning.

Stop immediately after the closing </say> tag; write nothing after it.

B.5 Steering details: direction, coefficient range, and span restriction

Direction extraction. The deception direction $\hat{v}_\ell$ is the unit-normalized difference of mean residual-stream activations between matched deceptive and honest generations at the public speech span, using minimal-pair prompts that hold the situation, schema, and think-head instruction fixed and flip only the honesty directive. The direction is thus obtained in closed form (mass-mean), which keeps it interpretable as "deceptive minus honest". We extract per layer and steer at a mid-

band spread (L11–17 for Llama). We steer at L11–17, a high-separation band for the span indicated by a high-SNR. We avoid the late layers, where steering can degrade the generation format. Instead, we use this stable mid-band, where the deception direction is both well-separated and format-preserving. We read contamination at a sampled subset (layers $11, 14, 17, 20, 23, 26, 29$, every third layer across the band), because each readout layer multiplies the teacher-forcing cost; sampling every third layer captures the depth profile at a fraction of the compute. The experiment on Qwen2.5-7B applied the same principles.

Coefficient range and generation quality. The intervention is additive, $h \leftarrow h + c\,\hat{\boldsymbol{v}}_\ell$, with a single scalar coefficient c. We select c with a range-finder that trades off two quantities: the steering must bite (the public speech span changes measurably) while generation format is preserved (the model still emits a parseable schema). For Llama-3.1-8B, the usable steering range is $c \in [0.5, 2]$. Below $c = 0.5$, the effect is negligible; above $c \approx 2.0$, the generation format begins to degrade as the perturbation propagates through structural tags. At $c = 2.0$, 92.3% of steered turns remain parseable. Sparing tag tokens from the intervention while steering only token content (a skip-tags variant of the hook) extends this usable range. We report the main results at $c = 1.0$, comfortably inside the format-safe range. Qwen2.5-7B requires larger coefficients for a comparable effect because activation magnitudes differ across families; the same range-finder procedure selects its operating point (Appendix G).

Span restriction. The hook engages only after the think head is complete, i.e. once the closing think-head tag is emitted, so the `<belief>`/`<intent>` tokens are generated with no perturbation and only the public speech span is steered. Under greedy decoding this makes the think head byte-for-byte identical with and without steering, which we verify directly (Section 5): the think head is unchanged, the public speech span differs (the intervention is active), and steering one agent does not leak into the generations of others. The span-restricted design allows us to interpret the contamination result by perturbing what the agent says and measuring the resulting changes in what it internally believes.

C Belief Probe: Training and Validation

This appendix details the probe training (Appendix C.1), the control mechanics (Appendix C.2), the Drunk uncertainty result (Appendix C.3) summarized in Section 4.

C.1 Training

For each sampled game and a randomly chosen seat, we generate an honest turn and capture the residual-stream activation at each layer, mean-pooled over the tokens of the `<belief>` span. Instances whose `<belief>` span cannot be parsed are discarded. Each activation is z-scored (per-dimension mean and scale from the training split) and used to fit two probes per layer:

- an eight-way multinomial logistic probe over believed role, with ℓ_2 regularization (C=0.5); the right singular vectors of its raw-coordinate weights $\boldsymbol{W} \oslash \boldsymbol{s}$, with $\boldsymbol{W} \in \mathbb{R}^{8\times d}$, span the belief subspace analyzed in Section 6;
- a binary Werewolf-vs-Village logistic probe with balanced class weights; its hyperplane normal, rescaled to activation space and unit-normalized, is the single belief direction $\hat{\boldsymbol{v}}_{\text{bel}}$.

All reported accuracies use group cross-validation with `deal_id` as the group, so activations from one game never appear in both train and test. The training label is the believed role y^{bel}, computed from the night log by the algorithm in Appendix B.2. We analyze the Drunk separately because it swaps its card with a center card without seeing the result, so its post-action role is not directly identifiable from its observations (Appendix C.3). The results are for Llama-3.1-8B-Instruct, using group cross-validation by game (n=1037 training seats, 308 divergent and 155 Drunk seats).

C.2 Control mechanics

We validate the probe against the three confounds of Section 4 and add a shuffled-label control. The shuffled-label control tests whether probe accuracy depends on the believed-role labels. Control 1

(divergence test) separates believed role from true role on seats where the two disagree. Control 2 (role-word test) reads the probe on turns whose public content names no role, so no role token is available to decode. Control 3 (cross-span transfer) tests whether the belief signal is recoverable at the public speech span, where contamination is measured. Figure 6 reports per-layer accuracy, the shuffled-label control, and Control 1; Figure 7 reports Control 3; Control 2 is reported below.

Span extraction. Each turn is one token sequence, prompt followed by completion. After generation we run one forward pass over the sequence and take, at each layer ℓ, the residual stream $\boldsymbol{H}_\ell \in \mathbb{R}^{T\times d}$, one d-dimensional vector per token position. The belief span and the public speech span share the layer and the feature axis and differ only in token positions: each field occupies its own interval of completion tokens, located from the tag offsets in the generated ids. For a span covering completion tokens $[s, e)$ after a prompt of length p, the span representation is

$$\boldsymbol{a}_\ell \;=\; \frac{1}{e-s}\sum_{t=p+s}^{p+e-1} \boldsymbol{H}_\ell[t],$$

so the belief-span activation at layer ℓ is the mean of that layer's residual stream over the <belief> tokens, and the public-speech-span activation is the mean over the [<claim>/<target>/<say>] tokens. Layer ℓ denotes the output of decoder block ℓ, the same position at which steering adds $c\,\hat{\boldsymbol{v}}_\ell$. Under causal attention, public-speech positions attend to the belief tokens; this is the route by which belief information reaches the span where contamination is measured (Control 3).

Shuffled-label control. We refit the probe after shuffling Werewolf-vs-Village labels within each game group. Accuracy drops to chance ($\sim$0.50 binary), showing that the probe is picking up genuine belief representations, not group-related features.

Control 1: Divergence test. On divergent seats (believed role $\neq$ true role; see Appendix B.2), we apply the trained probe and record how often its prediction matches the believed versus the true role. A probe that reads belief representation follows the believed role; one that reads ground truth follows the true role.

Control 2: role-word test. On most turns the agent names a role in its <claim> field, so a probe read at the public speech span could decode that role word instead of an internal belief. We exclude <claim> field and select held-out turns whose the rest of public speech span (<target>/<say>) names no deck role, which the utterance mentions no role, and apply the belief-span probe there. The probe recovers the believed role with 0.83–0.89 accuracy across layers, so its signal does not depend on a role token in the text.

Control 3: Cross-span transfer. We recapture the *same* divergent seats at the public speech span and apply the belief-span probe there. The seats are held fixed and only the read position changes. The belief-span probe transfers to the public speech span (believed-role recovery $\sim$0.85, true-role $\sim$0.03), confirming that contamination read at the public speech span measures belief representation.

C.3 The Drunk: representing uncertainty

The Drunk swaps its card with an unseen center card and therefore holds no confident self-belief. The probe assigns the Drunk high-entropy predictions spread across roles: Drunk seats the modal prediction accounts for 0.45 of cases, with the remainder distributed over all other roles.

D Contamination: Span Invariance, Method, and Functional Belief Test

D.1 Span-invariance check

Steering is applied only to tokens generated after the think head closes. To verify that this leaves belief generation untouched, we run the same games with and without steering under greedy (T=0) decoding and compare, per turn:




Figure 6: The belief probe decodes believed role, not true role, at every layer (Llama-3.1-8B-Instruct). (a) Believed-role accuracy on non-divergent, non-Drunk seats (0.979–0.994; y-axis zoomed). (b) Balanced accuracy of the binary Werewolf-vs-Village probe, which falls to chance (0.49–0.52) when the labels are shuffled. (c) On divergent seats, the probe predicts the believed role on 0.990–0.994 of seats and the true role on none.

1. **Think head held fixed:** the `<belief>`/`<intent>` tokens are byte-for-byte identical across runs.
2. **Steering is active:** the public speech span differs between runs.
3. **No cross-agent leakage:** generations of non-steered agents in the same game are essentially unchanged.

The intervention thus imposes deception on the public channel while leaving belief generation, and the other agents, unperturbed.

D.2 Contamination measurement

For each instance we generate a clean completion and teacher-force its tokens twice: once unmodified, and once with the steering delta added to the residual stream over the public speech span positions. We read the belief probe on the mean-pooled public speech span activation of each pass and compute $D_{\mathrm{KL}}(p_{\mathrm{steered}} \,\|\, p_{\mathrm{clean}})$ between the two believed-role distributions, averaged over instances (Eq. 1). Because the tokens are held fixed and only the activations are perturbed, the measurement isolates the effect on the belief representation from any change in generated text. We report KL per readout layer and averaged across layers.

We compare the additive intervention (LINEAR) against three controls that modify the added vector: PROJ-$\hat{\boldsymbol{v}}_{\mathrm{bel}}$ removes the belief direction from the delta; PROJ-UNIT does so and rescales the result to




Figure 7: Control 3: the belief probe transfers to the public speech span (Llama-3.1-8B-Instruct). The probe, trained on the <belief> span, is applied unchanged to the public speech span of the same divergent seats. It predicts the believed role on 0.84–0.91 of seats and the true role on 0.01–0.04, so contamination measured at the public speech span reflects belief.

the norm of the LINEAR delta, controlling for the reduced norm of a projected vector; and PROJ-$\hat{\boldsymbol{t}}$ removes a corpus reference direction as a placebo.

D.3 DOSE–RESPONSE AND REGIME COMPARISON

Table 2 reports per-layer LINEAR contamination at each coefficient; Table 3 reports layer-averaged KL by regime. Contamination increases monotonically with c at every layer. Removing the single belief direction (PROJ-$\hat{\boldsymbol{v}}_{\text{bel}}$, PROJ-UNIT) reduces mean KL by 7–10% relative to LINEAR; removing a placebo direction (PROJ-$\hat{\boldsymbol{t}}$) does not reduce it. The deception and belief directions are nearly orthogonal throughout ($\mathbb{E}_\ell\,|\cos(\hat{\boldsymbol{v}}_\ell, \hat{\boldsymbol{v}}_{\text{bel}})| < 0.02$). These results show that the contamination does not lie along the single belief axis, motivating the subspace analysis of Section 6.

Table 2: Per-layer belief contamination (KL) under LINEAR steering at each coefficient c (Llama-3.1-8B-Instruct). Contamination increases monotonically with c at every layer; the bottom row is the layer-averaged mean.

Layer	c=0.5	c=1.0	c=1.5	c=2.0
11	0.020	0.080	0.189	0.377
14	0.058	0.247	0.532	0.859
17	0.022	0.108	0.237	0.352
20	0.025	0.113	0.253	0.420
23	0.052	0.298	0.835	1.482
26	0.105	0.448	0.976	1.435
29	0.112	0.519	1.120	1.692
mean	0.056	0.259	0.592	0.945

D.4 A POST-DECEPTION SELF-REPORT TEST

This appendix details the self-report test of Section 5. The test pairs the belief readout with a behavioral readout on the same turns and asks whether both move further under deception steering than under an equal-norm random perturbation.

D.4.1 DESIGN

A positive probe shift admits two readings: (i) the perturbation changes the role information the model uses downstream, or (ii) the perturbation moves the activation across the fixed probe's decision boundary along directions the model does not use downstream. We pair the *representational* readout (the probe) with a *functional* one (the model's self-report) on the same turns. The self-report

Table 3: Layer-averaged contamination (KL between steered and clean belief distributions) at each steering coefficient c, for four versions of the realized steering delta. *Delta* (LINEAR): unmodified. $\hat{\boldsymbol{v}}_{\text{bel}}$ *removed* (PROJ-$\hat{\boldsymbol{v}}_{\text{bel}}$): $\hat{\boldsymbol{v}}_{\text{bel}}$ projected out. *Norm-matched* (PROJ-UNIT): $\hat{\boldsymbol{v}}_{\text{bel}}$ projected out, then rescaled to the norm of the delta. It equals PROJ-$\hat{\boldsymbol{v}}_{\text{bel}}$ to three decimals because the removed component is small. *Placebo removed* (PROJ-$\hat{\boldsymbol{t}}$): a random reference direction $\hat{\boldsymbol{t}}$ projected out. Contamination does not decrease.

c	LINEAR	PROJ-$\hat{\boldsymbol{v}}_{\text{bel}}$	PROJ-UNIT	PROJ-$\hat{\boldsymbol{t}}$
0.5	0.056	0.052	0.052	0.056
1.0	0.259	0.234	0.234	0.267
1.5	0.592	0.536	0.536	0.618
2.0	0.945	0.850	0.850	1.017

follows the steered utterance, so a change in it is explained by reading (i) and also by conditioning on the false claim in context, which can occur under reading (ii).

For each instance we generate the agent's turn three ways from an identical prompt,

> What role do you genuinely believe you currently have? Your role is:

with the think head (<belief>/<intent>) generated unsteered and the public speech span perturbed (the same set-up as before):

- **clean**: no steering;
- **steer**: the deception direction $\hat{\boldsymbol{v}}$ added to the public speech span at the coefficient;
- **random**: a random unit direction of equal magnitude added to the public speech span (controls for perturbation norm).

D.4.2 READOUTS

After we switch steering off, we take two readouts.

Representational (probe). We read the belief probe on the public speech span activation with the arm's perturbation applied and compute $\mathrm{KL}\big(p_\theta^{\text{steer}} \,\|\, p_\theta^{\text{clean}}\big)$ between the steered and clean believed-role distributions. This is the same contamination quantity used in Section 5.

Functional (forced choice). We append to the arm's own completion a direct query, asking the agent to state its role, and measure the log-probability margin of the believed role over the best competing role. A drop in this margin means the model is less able to report its believed role after the deceptive turn. It is a behavioral readout of the believed role the model would act on, independent of the probe. We report the change in margin relative to the clean arm.

Statistics are bootstrap means with 95% confidence intervals over instances.

D.4.3 RESULTS

Under deception the probe's decoded role flips on 48% of turns (CI $[43\%, 54\%]$). The forced-choice margin drops sharply (mean -4.64, CI $[-4.99, -4.30]$, below zero): steering towards deception reduces the model's confidence in its own believed role when asked to report it. The self-report flips to a different role on 35% of turns (CI $[31\%, 39\%]$).

The matched random perturbation separates the effects. It does move the probe's readout, its decoded-role flip rate is 18% (CI $[13\%, 22\%]$), which is expected, since any sufficient perturbation can cross a decision boundary, but this is more than half the deception rate (48%). The deception-specific excess is also noticeable. For each instance we compute how far the probe distribution moves from clean under deception, $D_{\mathrm{KL}}(p^{\text{steer}} \,\|\, p^{\text{clean}})$, and under a matched random perturbation, $D_{\mathrm{KL}}(p^{\text{rand}} \,\|\, p^{\text{clean}})$, and take their within-instance difference. This paired difference (the excess probe shift attributable to deception over a generic perturbation of equal norm) is 0.54 nats (CI

Table 4: We project the top-k belief directions $\boldsymbol{u}_1, \ldots, \boldsymbol{u}_k$ out of the realized steering delta and recompute contamination (Llama-3.1-8B-Instruct, c=1.0). Delta contamination is 0.259. *KL*: contamination after removing the top-k belief directions. *Remaining*: contamination left, as a percentage of the delta value, after removing the top-k belief directions or k random orthonormal directions. z: distance of the belief-subspace KL below the random-subspace mean, in standard deviations of the random draws. Random removals barely vary, which inflates $|z|$; the percentages are the quantity to compare.

		Remaining (% of delta)		
k	KL	Belief subspace	Random subspace	z
1	0.215	83%	100%	-47.5
2	0.090	35%	100%	-152.1
3	0.045	17%	100%	-135.9
4	0.020	8%	100%	-141.1
5	0.005	2%	100%	-168.1
6	0.004	1%	100%	-117.9

$[0.36, 0.71]$, above zero). The random perturbation does not produce the same post self-reported shifts. Its forced-choice margin does not drop but rises (mean $+0.81$, CI $[+0.58, +1.04]$), and its self-report flips only 11% of the time (CI $[8\%, 13\%]$). Relative to an equal-norm random perturbation, deception steering moves the belief readout further (paired excess 0.54 nats) and lowers the self-report margin (-4.64 versus $+0.81$). This design helps clarify the observed self-report change, while leaving open whether it arises from the perturbed activations or the false claim in context.

E Low-Dimensional Structure

E.1 Probe-derived subspace projection

The belief subspace $\boldsymbol{B}_k$ consists of the top-k right singular vectors of the eight-way probe's weights in raw activation coordinates, $\boldsymbol{W}_\ell \oslash \boldsymbol{s}$ (Section 6). The SVD is taken after rescaling: singular vectors of $\boldsymbol{W}_\ell$ itself live in standardized coordinates and do not match the raw-space delta. We project $\boldsymbol{B}_k$ out of the realized delta $\boldsymbol{\delta}_\ell$ and recompute the probe's KL at the readout layer. The random null draws k-dimensional orthonormal subspaces uniformly and applies the same projection; z is the number of null standard deviations by which the belief-subspace contamination falls below the null mean. Table 4 reports the sweep. Three belief directions capture $\approx 83\%$ of the contamination, whereas equal-dimensional random subspaces remove essentially none ($\geq 99\%$ remains).

E.2 What the belief directions encode

Method. The probe classifies eight believed roles, so $\boldsymbol{W}_\ell \oslash s$ has rank seven. We interpret its leading right singular vectors u_1, u_2, u_3 directly. For each layer we report (i) the *role loadings* $u_i^\top (\boldsymbol{w}_r \oslash s)$, the coordinate of each role's decoding direction on each axis, with the sign of u_i fixed so that its largest-loading role is positive; and (ii) the cosine between each u_i and labeled role contrasts $\boldsymbol{d} = \bar{\boldsymbol{w}}_{S_+} - \bar{\boldsymbol{w}}_{S_-}$.

Three role axes. The leading directions are role-identity axes, and they keep their identity at every layer (Table 5). u_1 is the *Villager axis*: Villager loads at one pole and every other role at or below zero, with Werewolf the farthest. u_2 is the *Werewolf axis*: Werewolf against the village power roles, led by Insomniac. u_3 is the *Tanner axis*: Tanner against Seer and Troublemaker, with Werewolf near zero. Villager–Werewolf is the most separated role pair at every layer; the pairwise contrast $\boldsymbol{w}_{\text{Werewolf}} - \boldsymbol{w}_{\text{Villager}}$ lies 0.90–0.97 along u_1, and the one-vs-rest Werewolf contrast lies 0.75–0.86 along u_2 (Table 6).

Deceptive incentive is a composite of the three axes. The deceptive-incentive contrast (Werewolf and Tanner, whose win conditions reward misrepresentation, against the truth-telling Villager, Seer, and Insomniac) is 96–99% contained in the subspace and loads on all three axes with cosines of

Table 5: Role loadings on the first three belief directions (Llama-3.1-8B-Instruct), sign-fixed so the anchor role of each axis is positive. Loadings shrink with depth; the pattern is the same at layers.

	Layer 11			Layer 17			Layer 26		
Role	u_1	u_2	u_3	u_1	u_2	u_3	u_1	u_2	u_3
Villager	**39.8**	7.2	3.4	**18.7**	2.9	1.9	**9.6**	2.3	0.4
Werewolf	−16.8	**32.5**	−1.1	−7.1	**14.5**	−0.7	−4.4	**6.7**	−2.1
Tanner	−8.5	−7.8	**31.6**	−4.6	−3.5	**14.7**	−2.3	0.1	**7.0**
Insomniac	−6.3	−21.0	−2.0	−2.2	−10.8	−2.6	−0.8	−4.5	0.9
Troublemaker	−8.2	−10.3	−16.7	−3.8	−2.8	−5.2	−1.2	−2.3	−1.2
Seer	3.4	−4.3	−11.7	−0.2	−2.2	−6.7	−0.5	−3.2	−4.4
Robber	−2.2	1.0	−2.1	−0.9	1.9	−0.2	−0.4	0.8	0.0
Drunk	−1.3	2.7	−1.4	0.1	0.1	−1.3	−0.1	0.1	−0.5

Table 6: Cosine between labeled contrasts and the first three belief directions (Llama-3.1-8B-Instruct). The one-vs-rest Werewolf contrast is u_2; the deceptive-incentive contrast is spread over.

	Werewolf vs. rest			Deceptive incentive		
Layer	u_1	u_2	u_3	u_1	u_2	u_3
11	0.44	**0.86**	0.03	0.67	0.49	0.50
14	0.61	**0.75**	0.05	0.73	0.31	0.58
17	0.41	**0.84**	0.04	0.65	0.51	0.54
20	0.38	**0.83**	0.18	0.61	0.65	0.41
23	0.41	**0.78**	0.36	0.60	0.71	0.31
26	0.51	**0.78**	0.25	0.68	0.59	0.39
29	0.50	**0.78**	0.22	0.63	0.64	0.35

0.60–0.73, 0.31–0.71, and 0.31–0.58 (Table 6): its positive poles are the Werewolf axis u_2 and the Tanner axis u_3, and its negative pole is the Villager end of u_1. The belief readout therefore devotes its three highest-gain directions to the two roles with an incentive to lie and to the role they are separated from.

Reading the attribution. In these terms, the per-direction attribution of Figure 5 says that contamination enters through the Villager–Werewolf separation (u_1) at the first steered layer and, from layer 17 onward, through the Werewolf and Tanner axes (u_2 and u_3), which together account for 50–91% of solo removal.

E.3 Per-direction attribution and alignment

Table 7 reports, for each readout layer and belief direction, the mean per-instance alignment $|\cos(\boldsymbol{\delta}_\ell, u_i)|$ and the fraction of LINEAR contamination removed by projecting out u_i alone. The attribution agrees with the nested sweep of Table 4: weighting the u_1 column by each layer's LINEAR contamination (Table 2) gives a removal of 17%, the $k{=}1$ value of the sweep. The 83% that survives removal of the top direction is a layer average dominated by layers 23–29, which carry 70% of the total contamination; at layer 11 the top direction alone removes 75%.

F Manipulability Attack: Method and Results

F.1 Threat-model scope

The attack operates in activation space: it adds $\boldsymbol{\delta}$ directly to the monitored representation and thereby establishes that the belief representation is manipulable through the low-dimensional belief subspace. A behavioral attack, in which generation is optimized so that the agent's own forward pass produces monitor-fooling activations while the think head is held fixed, would upgrade the claim from "the representation is manipulable" to "the agent could manipulate the monitor"; that extension is future work. Within the activation-space scope, the result follows from the entanglement of

Table 7: Per-direction alignment and solo removal (Llama-3.1-8B-Instruct, c=1.0). Top: $|\cos(\boldsymbol{\delta}_\ell, u_i)|$. Bottom: fraction of LINEAR contamination removed by projecting out u_i alone; Σ is the row sum, equal to one plus the cross-term share of Eq. 2. E is the delta's energy relative to a random vector.

Layer	u_1	u_2	u_3	u_4	u_5	u_6	E
Alignment $\lvert\cos(\boldsymbol{\delta}_\ell, u_i)\rvert$							
11	0.040	0.016	0.000	0.029	0.041	0.046	4.4×
14	0.044	0.018	0.063	0.069	0.033	0.052	10.1×
17	0.007	0.039	0.042	0.037	0.026	0.010	3.7×
20	0.010	0.027	0.006	0.029	0.042	0.008	2.4×
23	0.013	0.036	0.026	0.008	0.040	0.015	2.8×
26	0.008	0.048	0.026	0.019	0.031	0.015	3.1×
29	0.012	0.043	0.016	0.031	0.018	0.017	2.6×
Fraction of LINEAR *contamination removed by* u_i *alone*							Σ
11	+0.75	+0.14	+0.01	−0.17	+0.26	+0.05	1.04
14	+0.34	+0.11	+0.21	+0.18	+0.04	+0.03	0.91
17	+0.13	+0.46	+0.29	−0.01	+0.16	−0.01	1.02
20	+0.24	+0.45	+0.05	+0.15	+0.25	+0.01	1.15
23	+0.15	+0.52	+0.26	+0.07	+0.29	−0.02	1.27
26	+0.05	+0.73	+0.18	+0.20	+0.12	−0.02	1.26
29	+0.11	+0.72	+0.18	+0.38	+0.08	−0.01	1.46

Section 6: a monitor reading a low-dimensional projection is defeated by a small, subspace-confined perturbation that generic perturbations of equal dimension cannot achieve.

F.2 ATTACK CONSTRUCTION

Let $p_\theta(\cdot \mid \boldsymbol{a})$ be the belief probe's decoded distribution at activation $\boldsymbol{a}$, and let $\boldsymbol{a}_0$ be the clean belief-readout activation of an instance with believed role $y_0 = \arg\max_y p_\theta(y \mid \boldsymbol{a}_0)$. Given a target $y^\star \neq y_0$ and a subspace basis $\boldsymbol{B} \in \mathbb{R}^{k\times d}$ with orthonormal rows, we seek $\boldsymbol{\delta} = \boldsymbol{B}^\top \boldsymbol{c}$ with $\|\boldsymbol{\delta}\| \leq \rho$ such that $\arg\max_y p_\theta(y \mid \boldsymbol{a}_0 + \boldsymbol{\delta}) = y^\star$.

For a linear-softmax probe, the direction in raw activation space that most increases the target log-odds $\log p_\theta(y^\star) - \log p_\theta(y_0)$ is

$$\boldsymbol{g} \;=\; (\boldsymbol{W}_{y^\star} - \boldsymbol{W}_{y_0}) \oslash \boldsymbol{s},$$

where $\boldsymbol{W}_y$ is the probe weight row for role y and $\boldsymbol{s}$ the per-dimension standardization scale. We constrain the attack to the subspace by projecting, $\boldsymbol{g}_{\boldsymbol{B}} = \boldsymbol{B}^\top \boldsymbol{B}\, \boldsymbol{g}$, and ascend along $\boldsymbol{g}_{\boldsymbol{B}}/\|\boldsymbol{g}_{\boldsymbol{B}}\|$ in fixed steps until the arg-max flips (success) or the budget ρ is exhausted (failure), recording success and $\|\boldsymbol{\delta}\|$ at the flip. The target $y^\star$ is the probe's most probable incorrect role, i.e. the easiest realistic misclassification.

For the random baseline, $\boldsymbol{B}$ is the orthonormalization of a Gaussian matrix; per instance we take the most successful of 50 draws (lowest successful norm). The main threat model grants the belief subspace (k=6 and k=3).

F.3 PER-LAYER RESULTS

Table 8 reports the k=6 and k=3 attacks. At the layers where the belief representation is sharpest (14–20), the belief subspace flips the monitor on 86–90% of instances and the three-dimensional subspace on about half, while matched random subspaces succeed on at most 7%. The belief subspace is thus a potential attack surface whose effectiveness scales with the number of belief directions the adversary controls.

G QWEN2.5-7B REPLICATION

We replicate the pipeline on Qwen2.5-7B-Instruct (28 layers; steering band L14–18, probe read at a matched mid-band spread) with no code changes. The operating coefficient for each model is set

Table 8: The attack adds a perturbation $\boldsymbol{\delta}$ restricted to a k-dimensional subspace and drives the probe's prediction to its most probable incorrect role (Llama-3.1-8B-Instruct, 500 instances, norm budget ρ=3). *Success rate*: fraction of instances on which the prediction flips within the budget. *Median norm*: median $\|\boldsymbol{\delta}\|$ at the flip, over successful instances. *Norm ratio*: random-subspace median norm divided by belief-subspace median norm. A ratio of 4 means a random subspace needs a 4× larger perturbation. Random subspaces use the best of 50 draws per instance.

	Success rate		Median norm		
Layer	Belief	Random	Belief	Random	Norm ratio
Six directions (k=6)					
11	0.94	0.44	0.30	2.40	8.0
14	0.90	0.07	0.60	3.00	5.0
17	0.86	0.02	0.60	2.55	4.3
20	0.86	0.02	0.60	2.40	4.0
Three directions (k=3)					
11	0.52	0.25	0.30	2.70	9.0
14	0.49	0.02	0.60	2.55	4.3
17	0.49	0.01	0.60	2.10	3.5
20	0.50	0.01	0.60	1.80	3.0

Table 9: Contamination also concentrates in a few belief directions on Qwen2.5-7B-Instruct (c=2.0). Columns as in Table 4. The top belief direction alone leaves 99% of contamination in place; five directions leave 5%.

		Remaining (% of delta)		
k	KL	Belief subspace	Random subspace	z
1	0.0845	99%	100%	−2.9
2	0.0541	64%	100%	−104.0
3	0.0217	26%	100%	−159.8
4	0.0135	16%	100%	−162.3
5	0.0039	5%	100%	−164.3
6	0.0018	2%	100%	−153.8

by the same range-finder procedure, the coefficient at which steering reliably bites while generation format is preserved, and validated by the span-invariance check. Because activation magnitudes differ across families, this procedure lands at a higher coefficient for Qwen than for Llama, so Qwen's dose-response is reported at rates 2–8 (versus 0.5–2 for Llama). We therefore compare the two models at their own calibrated operating regimes, and compare structure rather than absolute coefficients. Table 9 reports the subspace k-sweep and Table 10 the regime dose-response.

Subspace k-sweep. As on Llama, contamination concentrates in a low-dimensional slice of the belief readout, and equal-dimensional random subspaces remove nothing. The single-direction result is more extreme on Qwen: removing the top belief direction leaves 99% of the contamination (k=1), so single-direction monitoring captures almost none of the effect; the drop with k is then sharp (64%, 26%, 16%, 5%, 2% for k=2 . . . 6). Random subspaces remain at 100% of linear throughout.

Regime dose-response. Contamination rises monotonically with the coefficient. Projecting the binary belief direction out of the injected vector (PROJ-$\hat{\boldsymbol{v}}_{\text{bel}}$, PROJ-UNIT) produces no substantial reduction, consistent with the near-orthogonality $|\cos(\hat{\boldsymbol{v}}_\ell, \hat{\boldsymbol{v}}_{\text{bel}})| < 0.03$. Removing a placebo direction (PROJ-$\hat{t}$) does not reduce it either. The structural conclusion holds on both models: no substantial single-direction reduction, and concentration in a low-dimensional subspace.

H Ethics statement

This work tests whether activation-based belief monitors, a proposed safeguard for AI systems, stay reliable when a model steered towards deception. It involves no human subjects and no personal

Table 10: Removing the binary belief direction does not reduce contamination on Qwen2.5-7B-Instruct. Layer-averaged contamination (KL) at each steering coefficient c; columns as in Table 3. Removing $\hat{\boldsymbol{v}}_{\text{bel}}$ changes contamination by at most 3.5% in either direction, and removing the placebo direction raises it by 5–6%. Qwen operates at larger coefficients than Llama because its activation magnitudes differ (Appendix G).

rate	LINEAR	PROJ-$\hat{\boldsymbol{v}}_{\text{bel}}$	PROJ-UNIT	PROJ-$\hat{t}$
2.0	0.085	0.088	0.088	0.090
4.0	0.358	0.366	0.365	0.379
6.0	0.815	0.819	0.819	0.860
8.0	1.345	1.310	1.310	1.408

data that all text is generated by open-weight models playing One-Night Ultimate Werewolf, a game in which strategic deception is part of the rules, and no generated text leaves the game environment.

The paper has two dual-use components. Deception steering adds a mean-difference direction to the residual stream, a standard representation-engineering technique that requires white-box access to the model and adds no capability beyond prior work (Zou et al., 2023; Rimsky et al., 2024). The manipulability attack (Section 7) requires direct write access to the monitored activations and the probe weights, access that a deployed system does not grant an external adversary. We report these results because the failure they expose is cross-feature: a monitor validated only against attacks on its own feature misses it. Our findings point developers of belief monitors to a concrete stress test, steering along behaviorally adjacent features, and to the directions that test should target.

I AI USE STATEMENT

We used AI tools for language polishing and help with code debugging. The authors reviewed and verified AI-assisted outputs and remain fully responsible for the final content.