PICLALIGN: SAFETY ALIGNMENT FOR PARAMETRIC IN-CONTEXT LEARNING

Anonymous authors
Paper under double-blind review

ABSTRACT

Parametric in-context learning (PICL) reduces the inference costs of in-context learning (ICL) by using a trained hypernetwork to convert document contexts into reusable LoRA adapters. Despite their promising results, across three PICL-integrated LLM systems, we find that internalizing benign documents through PICL significantly weakens safety alignment, whereas supplying the same documents through ICL causes little or no degradation. Existing alignment methods do not fix this problem because PICL introduces a distinct pattern of safety erosion (e.g., safety erosion occurs in earlier layers than the typical fine-tuned LoRAs) and additionally requires safety to be achieved across LoRAs generated from diverse documents, including unseen ones. In response, we propose *PICLAlign*, a unified framework that simulates PICL during alignment to better account for the safety-compromising effects of PICL-generated LoRAs. The framework supports both post-generation and generation-phase intervention: PICLAlign-L trains a safety LoRA to compose with each generated LoRA, while PICLAlign-H tunes the hypernetwork to generate LoRAs that enhance safety by construction. We further introduce Doc-DRO to improve robustness to atypical erosion patterns from unseen documents by optimizing a theoretically grounded worst-case loss over a neighborhood of document distributions. Experiments on systems integrated with two mainstream PICL frameworks, D2L and SHINE, show that PICLAlign achieves state-of-the-art safety alignment while preserving utility, reducing ASR from 35% to 0% under the D2L setting and from 56% to 0.4% under the SHINE setting. Our work reveals unexplored risks in PICL and motivates future research.

1 INTRODUCTION

Large language models (LLMs) (Yang et al., 2025) use in-context learning (ICL) (Dong et al., 2024) to answer queries using knowledge from document contexts, but repeatedly processing or retaining long documents increases inference costs. Parametric in-context learning (PICL) (Charakorn et al., 2026; Liu et al., 2026) addresses this limitation by using a trained hypernetwork to convert a document context into a LoRA adapter in a single forward pass, allowing the model to internalize its knowledge without keeping the document in context. The resulting LoRAs can be reused and composed across queries and sessions, reducing inference costs and extending beyond the context window (Yu et al., 2026; Hotsko et al., 2026). These gains often come from applying document-generated parameter updates to an already safety-aligned model. However, whether this efficiency comes at a safety cost is unclear: *does the model remain equally resistant to harmful queries when the same document is internalized through PICL rather than supplied through ICL?*

Key findings: We compare the same document–query pairs under ICL and PICL across three systems. Supplying the documents through ICL produces little or no increase in attack success rates (ASRs), whereas internalizing them through PICL substantially increases susceptibility to harmful queries (Table 1). This degradation occurs even with entirely benign documents, while documents containing malicious demonstrations can further amplify it under PICL. Ordinary document internalization can therefore weaken safety without requiring an attacker to construct a malicious document. Existing defenses do not reliably address this degradation. PICL generates LoRAs at deployment without document-specific fine-tuning, leaving no training step for fine-tuning-stage defenses to intervene. Defenses standard for LLM safety or effective against harmful fine-tuning attacks also fail to achieve strong safety while preserving utility (Table 2). Our causal analysis further identifies a different

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

pattern of safety erosion: the effects of PICL-generated LoRAs concentrate in earlier layers than those of the fine-tuned LoRAs we evaluate. These findings caution against the assumption that alignment methods effective for fine-tuning will transfer reliably to PICL.

Contributions: To fill this gap, we propose a unified framework, PICLAlign, that accounts for the safety-compromising effects of LoRAs generated from diverse documents. Specifically, we simulate the PICL process during alignment and train alignment modules to intervene on PICL-generated LoRAs. By exposing these modules to diverse document contexts, they learn to achieve strong safety alignment despite PICL-induced safety erosion and generalize beyond the documents seen during training (Section 3.2). We instantiate this framework with two distinct approaches: PICLAlign-L trains a separate safety LoRA and composes it with each PICL-generated LoRA at test time, while PICLAlign-H tunes the hypernetwork to produce LoRAs that enhance safety by construction. To improve robustness to atypical erosion patterns not captured by the seen documents, we propose Doc-DRO, which optimizes the alignment module against worst-case document distributions within a prescribed neighborhood (Section 3.3). We further provide theoretical guarantees on the approximation error of the resulting tractable objective (Theorem 3.1).

Experiments across three jailbreak datasets and three PICL-integrated systems based on two PICL frameworks, D2L and SHINE, demonstrate that our proposed designs progressively improve alignment, preserving PICL utility while reducing ASRs to below 3% across all systems. In contrast, existing defenses rarely reduce ASRs below 10% under utility constraints, especially for in-context attacks (Section 4.2). Moreover, our analysis of diverse benign and adversarial documents reveals that, while different types of documents induce varying degrees of safety degradation in PICL-integrated systems before alignment, PICLAlign achieves strong safety across diverse documents, even though these documents are not explicitly included during alignment (Section 4.3). We hope this work serves as an early step toward securing this paradigm and can inspire further research in this direction.

2 Background

2.1 Parametric in-context learning (PICL)

Basics. PICL (Charakorn et al., 2026; Liu et al., 2026) internalizes a given document context into the parameters of a frozen LLM θ. Specifically, given a document d, a trained hypernetwork H_ϕ maps d to a document-specific LoRA adapter $\Delta W_d = H_\phi(d)$, yielding the adapted model $\theta_d = \theta + \Delta W_d$. The adapted model can then answer downstream queries x according to $p_{\theta+H_\phi(d)}(y \mid x)$ without re-providing d. The hypernetwork H_ϕ is trained to approximate context distillation by aligning the output distributions of the document-conditioned LLM and the adapted model:

$$\min_{\phi} \mathbb{E}_{(d,x,y)} \left[\mathcal{L}\big(p_\theta(y \mid x, d), p_{\theta+H_\phi(d)}(y \mid x)\big) \right]. \tag{1}$$

Recent PICL frameworks share this formulation while differing in how they encode documents and generate LoRAs. All enable effective, efficient, and persistent reuse of contextual knowledge. Here, we refer to an LLM integrated with a PICL framework as a PICL-integrated (LLM) system.

PICL degrades LLM safety alignment. PICL transforms document contexts into LoRAs and integrates them with the underlying LLM. Since naïve LLM adaptation introduces a utility-safety trade-off (Qi et al., 2024), we ask whether PICL can similarly compromise safety alignment of integrated systems. Specifically, we examine whether providing a benign document alongside a harmful query can induce unsafe responses when the document is internalized into a LoRA. To this end, we sample 200 harmful queries from WildGuardTest and pair each query with a benign document sampled from SQuAD (Rajpurkar et al., 2016), a dataset comprising passages from Wikipedia. We feed the same document-query pairs into D2L-Gemma2-2B-IT (D2L-G), D2L-Qwen3-4B-IT (D2L-Q),

Table 1: PICL increases ASRs compared to bare queries and ICL. ICL and PICL denote providing (SQuAD/ICA) documents through ICL and PICL, respectively. Values for ICL and PICL denote ASR changes relative to the bare-query setting without the document context.

System	D2L-G	D2L-Q	SHINE-Q
Bare query	12.5%	2.5%	25.5%
SQuAD ICL	-2.50%	+0.50%	-8.50%
SQuAD PICL	+12.5%	+8.50%	+13.0%
ICA ICL	-10.5%	+1.00%	+3.00%
ICA PICL	+17.0%	+10.0%	+46.5%

and SHINE-Qwen3-8B (SHINE-Q), using either in-context learning (ICL) or PICL, and evaluate their attack success rates (ASRs).

As shown in Table 1, all three systems have low ASRs on bare queries. Under ICL, ASRs are maintained or even reduced, as the additional benign text does not compromise safety alignment and may sometimes distract the model. In contrast, internalizing the same documents via PICL consistently increases ASRs across all three systems, regardless of their bare-query ASRs. For example, ASRs increase by 12.5% for D2L-G and 13.0% for SHINE-Q, showing that PICL-generated LoRAs can compromise the safety alignment of integrated systems even with benign documents.

Inspired by in-context attacks (ICA), which use malicious demonstrations to bypass LLM safety alignment, we further compare ICL and PICL using ICA documents with malicious demonstrations as contexts for stress-testing, in contrast to benign documents from SQuAD. Interestingly, ICA rarely increases ASRs through ICL and can even reduce the ASR of D2L-G from 12.5% to 2.0%. One possible explanation is that explicit malicious demonstrations more effectively trigger the model's inherent safety mechanisms. In contrast, embedding these malicious documents through PICL substantially increases ASRs, reaching up to 72.0% for SHINE-Q. **Takeaways:** These results show that PICL can compromise the safety alignment of integrated systems through generated LoRAs even with benign documents, and that internalizing malicious contexts can further amplify this degradation. Moreover, while benign fine-tuning also degrades alignment (Qi et al., 2024), PICL generates LoRAs at test time, leaving no training step for fine-tuning-stage defenses (Yang et al., 2026) to intervene.

2.2 Threat model

The above results reveal that PICL introduces a new attack surface through its generated LoRAs. In this work, we aim to align PICL-integrated systems under the degradation introduced by these LoRAs, with the goal of *achieving strong safety beyond merely offsetting it*. Accordingly, we focus on attack scenarios arising from this attack surface rather than the bare-query setting (See Figure 1).

Attack scenarios. We consider two settings that differ in whether the attacker can supply the document internalized by PICL. In the first, the attacker supplies both a document and a harmful query, and the document may be benign or malicious. In the second, the attacker supplies only the harmful query, while the system internalizes benign documents (e.g., user profiles (Tan et al., 2026), agent skills (Yu et al., 2026), or retrieved documents (Su et al., 2025)) during normal operation. In both settings, the generated LoRA may weaken the safety alignment of the integrated system.

Defender goal. We consider a defender who deploys a PICL-integrated LLM system. The defender either (1) downloads a pretrained hypernetwork from a public platform or (2) trains one from scratch. Under the attack scenarios described above, the defender aims to align the system such that **the resulting LoRA-integrated LLM exhibits strong safety alignment across diverse document contexts** (potentially even surpassing that of the underlying LLM) while preserving PICL's utility.

Defender knowledge and capability. We assume that the defender has knowledge of the PICL framework and can collect a *small* amount of data from its training distribution for utility preservation. We further assume that the defender can collect a *small* set of harmful queries and obtain refusal responses generated by the aligned GPT-4o. The defender does not know the document contexts or harmful queries used by the attacker at test time, nor does the defender have knowledge of the ICA-based attack strategy. Similar to prior work, we assume that the defender does not have access to external guardrails. Such defenses are orthogonal to our goal, as we aim to inherently align the LLM system by design. Moreover, external guardrails can be bypassed by optimized prompts (Hackett et al., 2025) and introduce additional overhead, which conflicts with the motivation of PICL.

3 Method

In this section, we first show that existing alignment methods fail to achieve strong safety alignment under the challenging PICL setting in Section 3.1. We then introduce PICLAlign, a unified framework that covers two alignment approaches in Section 3.2. Finally, we introduce a Doc-DRO mechanism that further improves alignment results in Section 3.3.

3.1 Limitations of existing alignment methods



Figure 1: (a–b) Attack scenarios and defender model for PICL-integrated LLM systems. (c) Overview of PICLAlign, which trains a safety LoRA or tunes the hypernetwork by simulating the PICL process.

The generated LoRA provides a natural intervention point for safety in PICL: it injects document-specific knowledge into the frozen LLM and is the source of the observed safety degradation. We therefore evaluate existing approaches that can be directly applied or adapted to optimize generated LoRAs for safety. Methods that do not target the LoRA itself fail to address the root cause of safety degradation and yield undesirable results, as shown in Sec. 4.2. We conduct our exploration using Qwen3-8B and its SHINE-Qwen3-8B system (Liu et al., 2026).

Table 2: SafeLoRA and standard safety LoRA composition work under the fine-tuning setting but fail to generalize to the PICL setting. WGT-SQ-ASR denotes ASR on harmful queries from WildGuardTest, each paired with a SQuAD document.

Alignment method	FT Setting		PICL Setting	
	WGT-ASR	Acc	WGT-SQ-ASR	Util.
Base LLM	25.5	16.2	25.5	20.2
LoRA-integrated	51.0	71.0	38.5	51.8
SafeLoRA	22.5	56.0	38.5	47.4
Safety LoRA Comp.	1.50	68.2	33.5	51.9

We first evaluate adapted text-based defenses, which incorporate safety policies into the document context with the goal of enhancing safety after the defense prompt is internalized alongside the document. We consider two approaches based on self-reminders (Xie et al., 2023) and in-context defenses (Wei et al., 2026). We defer detailed results to Sec. 4.2, but these defenses fail because: (1) prompt-level defenses are ineffective against LoRA-induced safety degradation, and (2) PICL primarily incorporates contextual knowledge rather than enforcing instruction following.

Inspired by the harmful fine-tuning literature, we then adopt alignment methods designed for LLM adaptation, including the training-free approach (SafeLoRA (Hsu et al., 2024)) and the training-based approach (safety LoRA composition (Gudipudi et al., 2025; Xue & Mirzasoleiman, 2025)). These methods address a related problem: achieving safety alignment under the degradation introduced by (poisoned) task LoRAs. We exclude defenses applied during LoRA fine-tuning (Yang et al., 2026), as they are incompatible with PICL. As shown in Table 2, we compare their performance under the PICL setting with that under the fine-tuning setting, where task LoRAs are fine-tuned on poisoned GSM8K following Zhang et al. (2026). Here, Acc denotes GSM8K accuracy, measured with a fixed answer template and no reasoning, as in their work; the low Acc of the base LLM is partly due to a format mismatch. While these methods achieve promising results under fine-tuning, they fail to achieve strong safety under PICL. For example, safety LoRA composition reduces WildGuardTest ASR to nearly 0% with only a 2.8% accuracy drop under fine-tuning, whereas the same approach reduces ASR by merely 5% when applied to LoRAs generated from SQuAD documents. This suggests that PICL-generated LoRAs compromise safety differently from task LoRAs, which must be addressed to achieve strong safety alignment.

To further characterize this difference, we visualize the causal effects of LoRA layers following Chen et al. (2026). For each LLM layer ℓ, we apply a fine-tuned or PICL-generated LoRA only at that layer and measure its effect on the log-probability of compliance behavior relative to the base LLM:

$$\Delta_\ell = \log P\left(\text{Compliance} \mid x; \text{LoRA at layer } \ell\right) - \log P\left(\text{Compliance} \mid x; \text{Base LLM}\right), \quad (2)$$

where x indicates a harmful query. A positive Δ_ℓ indicates greater safety erosion. We define $e_\ell^+ = \max(\Delta_\ell, 0)$ and report the positive effect of each layer group $\mathcal{I}_k$ as $E_k = \sum_{i \in \mathcal{I}_k} e_i^+$, averaged over harmful queries. As shown in Appendix Figure 5, FT erodes safety through later layers, whereas PICL does so through earlier ones (e.g., the first layer group for Qwen3-8B). This difference may

stem from the larger norms of PICL-generated LoRAs (about $10\times$ larger under Qwen3-8B), which may more easily compromise safety. It also helps explain why FT defenses fail to transfer to PICL.

3.2 OUR PICLALIGN

Our analysis suggests that PICL-generated LoRAs erode safety differently from fine-tuned LoRAs. However, identifying their differences does not specify how to intervene on a document-specific LoRA while preserving its utility. Moreover, the documents internalized at deployment are unknown during alignment. Although we cannot anticipate each resulting LoRA, we have access to the hypernetwork that generates them, allowing us to reproduce PICL adaptation during alignment.

We therefore propose *PICLAlign*, which optimizes an alignment module with PICL-generated LoRAs simulated during alignment. For each sampled document, we generate and intervene on its LoRA and compute alignment and utility losses on the resulting LoRA-integrated LLM. These losses expose the alignment module to the behavioral effects of PICL, without requiring an explicit rule for identifying and removing safety-compromising pattern changes. Training across diverse documents then seeks an intervention that remains effective across document-specific LoRAs, including those generated from unseen documents. We use a retain dataset D_{ret} to preserve PICL utility and a shadow dataset D_{shadow} of harmful queries paired with refusal responses for safety alignment. Depending on how we intervene on PICL-generated LoRAs, we introduce two variants that operate at the post-generation and generation phases and offer complementary benefits: PICLAlign-L trains a safety LoRA to compose with each generated LoRA, while PICLAlign-H fine-tunes the hypernetwork itself.

3.2.1 PICLALIGN-L

PICLAlign-L trains a separate safety LoRA and composes it with each PICL-generated LoRA at test time, following the standard safety LoRA composition approach shown to be effective under the fine-tuning setting. Unlike the naïve approach, which trains the safety LoRA on the original base LLM θ, PICLAlign-L simulates the PICL process during alignment: given a document $d \in D_{\text{ret}}$, we first feed d into the hypernetwork to generate a LoRA ΔW_d, and then train the safety LoRA on top of the resulting LoRA-integrated LLM $\theta + \Delta W_d$. This enables the safety LoRA to directly account for the entangled safety-compromising effects of PICL-generated LoRAs. Formally, let ΔW_s denote the trainable safety LoRA. We optimize the following objective:

$$\begin{aligned}\min_{\Delta W_s} \quad & \underbrace{\mathbb{E}_{d\sim D_{\text{ret}},\,(x_{\text{atk}},y_{\text{ref}})\sim D_{\text{shadow}}}\left[-\log p_{\theta+\Delta W_d+\Delta W_s}(y_{\text{ref}} \mid x_{\text{atk}})\right]}_{\text{alignment loss } \mathcal{L}_{\text{align}}} \\ & + \lambda \underbrace{\mathbb{E}_{(d,x_{\text{ret}},y_{\text{ret}})\sim D_{\text{ret}}}\left[-\log p_{\theta+\Delta W_d+\Delta W_s}(y_{\text{ret}} \mid x_{\text{ret}})\right]}_{\text{retain loss } \mathcal{L}_{\text{ret}}}, \quad \Delta W_d = H_\phi(d),\end{aligned} \tag{3}$$

where λ controls the trade-off between utility preservation and safety alignment. Both losses are computed on the composed LLM $\theta + \Delta W_d + \Delta W_s$ in the simulated PICL process: the retain loss regularizes it on triples from D_{ret} to preserve PICL utility, while the alignment loss encourages it to refuse harmful queries. The hypernetwork ϕ remains frozen during alignment.

3.2.2 PICLALIGN-H

Although PICLAlign-L can effectively ensure safety, it requires the defender to be aware of the safety issue and maintain a separate safety LoRA for repeated composition with each PICL-generated LoRA at deployment. To bypass this requirement, PICLAlign-H directly fine-tunes the hypernetwork to generate safety-aligned LoRAs by construction. The defender can then publish the aligned hypernetwork, allowing users without safety-alignment expertise to directly obtain safety-aligned PICL-integrated systems. Specifically, we optimize the hypernetwork such that $\Delta W_d = H_\phi(d)$ preserves PICL utility while improving safety alignment.

However, directly fine-tuning the hypernetwork can easily degrade its utility, particularly under limited resources (e.g., a small retain dataset), as the hypernetwork is sensitive to parameter updates (See Appendix Table 6). To address this issue, we introduce two additional designs: (1) weight regularization to constrain parameter updates, and (2) asymmetric gradient projection to mitigate conflicts between safety alignment and utility preservation. Specifically, we add a regularization loss $\mathcal{L}_{\text{reg}} = \|\phi - \phi_0\|_2^2$ with strength β and formulate the full objective as $\mathcal{L}_{\text{align}} + \lambda\mathcal{L}_{\text{ret}} + \beta\mathcal{L}_{\text{reg}}$.

To further mitigate gradient conflicts, we apply asymmetric gradient projection to $\mathcal{L}_{\text{align}}$ and $\mathcal{L}_{\text{ret}}$. Specifically, let $g_{\text{align}} = \nabla_\phi \mathcal{L}_{\text{align}}$ and $g_{\text{ret}} = \nabla_\phi \mathcal{L}_{\text{ret}}$. When $g_{\text{align}}^\top g_{\text{ret}} < 0$, we project g_{align} onto the subspace orthogonal to g_{ret} to remove the component that conflicts with utility preservation: $\tilde{g}_{\text{align}} = g_{\text{align}} - \frac{g_{\text{align}}^\top g_{\text{ret}}}{\|g_{\text{ret}}\|_2^2} g_{\text{ret}}$. Otherwise, we retain the original gradient, i.e., $\tilde{g}_{\text{align}} = g_{\text{align}}$. Basically, this design is a one-sided variant of PCGrad (Yu et al., 2020) for multi-task learning.

3.3 Document-wise distributionally robust optimization

Both naïve variants of PICLAlign achieve desirable results, but the alignment process may capture general safety-compromising patterns while missing atypical artifacts, particularly those introduced by documents from unseen distributions. Inspired by Gao & Kleywegt (2023), we propose a new document-wise distributionally robust optimization (Doc-DRO), which minimizes the worst-case alignment loss over document distributions around the empirical distribution, thereby improving robustness to underrepresented variations. Let ψ denote the alignment module to be optimized (the composed safety LoRA in PICLAlign-L or the hypernetwork in PICLAlign-H), which yields an aligned LoRA $\psi(d)$ for each document d. The Doc-DRO alignment loss for both variants becomes:

$$\min_{\psi} \sup_{\mathcal{Q}:\, W_p(\mathcal{Q}, P_{\text{ret}}) \le \epsilon} \mathbb{E}_{d\sim\mathcal{Q}} \mathbb{E}_{(x_{\text{atk}}, y_{\text{ref}})\sim D_{\text{shadow}}} \left[-\log p_{\theta+\psi(d)} \left(y_{\text{ref}} \mid x_{\text{atk}} \right) \right], \tag{4}$$

where P_{ret} denotes the empirical distribution over documents in D_{ret}, and $\mathcal{Q}$ denotes an adversarial document distribution. The radius ϵ bounds the p-Wasserstein distance $W_p(\mathcal{Q}, P_{\text{ret}})$.

Directly optimizing the worst-case objective in Eq. 4 is intractable. Existing work (Xu et al., 2026) reformulates the inner maximization as a regularization term, but requires second-order curvature information. In this work, we instead leverage finite differences to obtain a tractable first-order approximation and optimize the following surrogate objective:

$$\min_{\psi} \mathbb{E}\big[\ell_{\text{align}}(\psi(d))\big] + \epsilon \Big(\mathbb{E}\big[\, |\Delta_\delta(d)|^q \,\big] \Big)^{1/q} \quad \Delta_\delta(d) = \frac{\ell_{\text{align}}\Big(\psi(d + \delta g_{\text{align}}^d)\Big) - \ell_{\text{align}}(\psi(d))}{\delta}, \tag{5}$$

where all expectations are taken over $d \sim P_{\text{ret}}$ and $(x_{\text{atk}}, y_{\text{ref}}) \sim D_{\text{shadow}}$, and $\ell_{\text{align}}(\psi(d), x_{\text{atk}}, y_{\text{ref}}) = -\log p_{\theta+\psi(d)} \left(y_{\text{ref}} \mid x_{\text{atk}} \right)$, with x_{atk} and y_{ref} omitted for simplicity. Here, g_{align}^d denotes the normalized gradient direction of ℓ_{align} with respect to d, and ϵ and $\delta > 0$ denote the perturbation radius and finite-difference step, respectively. q is the Hölder conjugate of p satisfying $1/q + 1/p = 1$.

Theorem 3.1 (Approximation Error of the Doc-DRO Surrogate)**.** *Let $\mathcal{L}_{DRO}^{\epsilon,p}(\psi)$ denote the worst-case alignment loss in Eq. 4, and $\mathcal{L}_{FD}^{\epsilon,\delta}(\psi)$ the finite-difference surrogate objective in Eq. 5. Assume the loss gradient $\nabla_d \ell_{align}(\psi(d))$ is (L, α)-Hölder continuous in d for $\alpha \in (0, 1]$, and $p \ge 1 + \alpha$. Then*

$$\left| \mathcal{L}_{FD}^{\epsilon,\delta}(\psi) - \mathcal{L}_{DRO}^{\epsilon,p}(\psi) \right| \;\le\; \frac{L}{1+\alpha} \left(\epsilon^{1+\alpha} + \epsilon\, \delta^\alpha \right) \;=\; O\left(\epsilon^{1+\alpha} + \epsilon\, \delta^\alpha \right) \quad \text{as } \epsilon, \delta \to 0. \tag{6}$$

Proof. See Appendix A.4. □

Practical implementation. A key property of PICL is that the document affects the model only through its induced LoRA $\Delta W_d = H_\phi(d)$, so $\ell_{\text{align}}(\psi(d))$ depends on d only through ΔW_d. Under the transport cost $c_H(d_1, d_2) = \|H_\phi(d_1) - H_\phi(d_2)\|_2$, Doc-DRO over documents is upper-bounded by Doc-DRO over LoRAs (Appendix Lemma A.4.1), and Theorem 3.1 applies with d replaced by ΔW_d. We therefore perturb ΔW_d rather than d, avoiding ill-defined perturbations on discrete text and improving efficiency. For PICLAlign-L, ΔW_d is produced by the frozen hypernetwork, and we perturb the document-induced adaptation rather than the trainable weights; for PICLAlign-H, ΔW_d is produced by the current hypernetwork, so the perturbation ball evolves with ϕ and remains valid. Robustness beyond this local neighborhood is empirically evaluated in Sections 4.2–4.3.

4 Experiments

4.1 Experimental setup

PICL-integrated LLM systems. We experiment with two mainstream PICL frameworks designed for general tasks, D2L (Charakorn et al., 2026) and SHINE (Liu et al., 2026). We evaluate three

Table 3: Main evaluation results (%) for D2L-Gemma2-2B-IT. For the base LLM, no document contexts are used for utility/safety evaluation. Additional defense results are in Appendix Table 7.

Alignment method	Utility Evaluation (in Score↑)					Safety Evaluation (in ASR↓)						
	SQ	ROPES	HotpotQA-L	2Wiki-L	Avg	WGT-SQ	WGT-ICA	DH-SQ	DH-ICA	DAN-SQ	DAN-ICA	Avg
Base LLM	23.4	51.3	25.9	25.4	31.5	12.5	12.5	9.50	9.50	41.5	41.5	21.2
Original PICL	75.7	70.6	31.3	34.8	53.1	25.0	29.5	31.0	45.5	36.0	47.0	35.7
Steering Vector	74.8	63.7	28.2	32.6	49.8	12.5	12.5	7.00	3.50	30.5	34.0	16.7
Internalized Self-reminders	74.7	68.0	31.8	32.5	51.8	23.0	33.0	26.0	45.0	35.0	45.0	34.5
Internalized ICD	63.1	70.4	30.6	32.0	49.0	21.0	29.0	21.0	38.5	31.5	42.0	30.5
SafeLoRA	16.2	39.3	19.9	22.6	24.5	22.5	22.0	32.0	31.5	41.5	39.5	31.5
SPLoRA	74.6	70.3	33.3	33.8	53.0	23.5	29.5	31.5	46.0	35.0	43.0	34.8
Standard Safety LoRA	72.5	62.7	30.2	31.2	49.1	2.50	8.50	6.50	19.5	11.5	11.0	9.90
PICLAlign-L (w/o Doc-DRO)	74.8	67.4	32.2	33.9	52.1	1.50	4.00	2.00	6.00	3.00	2.50	3.20
PICLAlign-L (Flat-LoRA)	74.7	69.2	31.8	31.6	51.8	0.50	2.50	2.50	4.50	2.00	2.50	2.40
PICLAlign-L	74.7	69.2	32.6	34.7	52.8	0.00	0.00	0.00	0.00	0.00	0.00	0.00
PICLAlign-H (w/o Doc-DRO)	75.7	69.5	31.3	36.0	53.1	3.50	5.50	2.50	4.00	19.0	18.0	8.70
PICLAlign-H (Flat-LoRA)	75.8	68.6	31.0	35.1	52.6	2.50	4.00	3.00	3.00	18.5	16.0	7.80
PICLAlign-H	74.5	70.3	32.0	34.6	52.8	0.50	2.50	0.50	0.50	7.50	7.00	3.10

corresponding PICL-integrated systems: (1) D2L-Gemma2-2B-IT (Team et al., 2024), (2) D2L-Qwen3-4B-IT (Yang et al., 2025), and (3) SHINE-Qwen3-8B (Yang et al., 2025). We select them as they are the default settings for their respective PICL frameworks and have available checkpoints.

Dataset. (1) For safety alignment, we randomly sample 1,000 harmful queries from the WildGuardTrain dataset (Han et al., 2024) and generate their refusal responses using GPT-4o, resulting in a shadow dataset of 1,000 (query, refusal response) pairs. To simulate the PICL process, each pair is paired with a benign document sampled from the retain dataset during alignment. For the retain dataset, we randomly sample 2,000 triples ($< 0.2\%$ of the full set) from the respective training dataset of each PICL framework. **(2) For utility evaluation**, we follow the evaluation settings of D2L and SHINE and evaluate their respective integrated systems using their own utility datasets, given that the two frameworks are trained and evaluated separately. This setup better reflects the utility degradation caused by our alignment methods. **(3) For safety evaluation**, we use WildGuardTest (WGT) (Han et al., 2024), DirectHarm (DH) (Lyu et al., 2024), and Do-Anything-Now (DAN) (Shen et al., 2024) as attack evaluation datasets. We construct document–query pairs by either sampling a benign document or constructing an ICA document. Details of the retain datasets, utility evaluation datasets, and attack-evaluation pairs are provided in Appendix A.5.1.

Baselines. We primarily compare PICLAlign with three categories of existing defenses that can be directly applied or adapted to intervene on generated LoRAs. We also compare against defenses that do not target generated LoRAs, as well as Flat-LoRA (Li et al., 2024), an alternative to Doc-DRO. Details of the evaluated baselines are provided in Appendix A.5.2.

Metrics. For each PICL framework, we evaluate its integrated systems (both original and aligned variants) using its official evaluation protocol and report utility scores. For attack evaluation, we measure the ASR on pairs constructed from different document and jailbreak datasets, with WildGuard (Han et al., 2024) as the judge model. Details of the metrics are provided in Appendix A.5.3.

Implementation details. Due to limited space, we provide the implementation details in Appendix A.5.4. Detailed analyses of hyperparameters and training settings are presented in Section 4.3.

4.2 Main results analysis

Tables 3–4 and Appendix Table 5 report the utility and safety of three PICL-integrated systems under different alignment methods. PICLAlign-L and -H denote variants with Doc-DRO.

Existing defenses all fail to achieve strong safety, and their performance varies substantially across PICL settings. For example, Standard Safety LoRA reduces ASR to 9.9% under D2L-Gemma2-2B-IT but is less effective under SHINE-Qwen3-8B, while SPLoRA shows the opposite trend. This variation may arise because different PICL frameworks generate LoRAs through different mechanisms (i.e., they encode documents and apply transformations differently), making existing defenses less transferable. In contrast, PICLAlign simulates the PICL process during alignment, allowing the trained module to account for artifacts specific to each hypernetwork and adapt accordingly. As a result, PICLAlign consistently outperforms prior defenses, e.g., by over 20% under SHINE-Qwen3-8B. Moreover, although PICLAlign is trained with benign documents as contexts, both variants reduce ASR under ICA documents to levels comparable to those observed with benign documents

Table 4: Main evaluation results (%) for SHINE-Qwen3-8B.

Alignment method	Utility Evaluation (in Score↑)					Safety Evaluation (in ASR↓)						
	SQ-S	MARCO	HotpotQA	2Wiki	Avg	WGT-SQ	WGT-ICA	DH-SQ	DH-ICA	DAN-SQ	DAN-ICA	Avg
Base LLM	20.2	19.3	26.1	27.0	23.2	25.5	25.5	36.5	36.5	26.0	26.0	29.3
Original PICL	51.8	41.2	56.3	60.8	52.5	38.5	72.0	54.5	91.5	27.0	56.0	56.6
Steering Vector	26.1	27.8	36.0	26.5	29.1	36.5	47.0	63.0	81.0	14.5	15.5	42.9
Internalized Self-reminders	51.8	40.7	54.0	59.4	51.5	39.5	71.0	51.0	92.5	26.5	57.0	56.3
Internalized ICD	49.9	39.2	51.5	57.8	49.6	28.0	48.5	30.0	70.5	4.50	13.0	32.4
SafeLoRA	47.4	39.9	53.2	58.4	49.7	38.5	63.0	70.0	93.5	30.5	47.5	57.2
SPLoRA	46.5	38.8	53.1	58.0	49.1	13.0	37.5	21.5	59.0	17.5	26.0	29.1
Standard Safety LoRA	51.9	40.4	56.0	60.3	52.2	33.5	56.0	49.5	85.0	19.0	47.0	48.3
PICLAlign-L (w/o Doc-DRO)	51.0	41.3	55.2	58.8	51.6	8.00	7.00	1.50	0.00	2.50	2.00	3.50
PICLAlign-L (Flat-LoRA)	50.2	42.0	53.8	60.7	51.7	6.50	9.00	0.50	0.50	5.50	4.00	4.30
PICLAlign-L	51.2	41.7	54.8	59.9	51.9	0.00	1.50	0.00	0.00	0.50	0.50	0.40
PICLAlign-H (w/o Doc-DRO)	48.8	40.2	54.0	58.0	50.3	4.00	2.00	1.50	1.00	6.50	2.50	2.90
PICLAlign-H (Flat-LoRA)	48.4	40.7	54.1	57.3	50.1	4.00	3.00	1.50	1.00	5.00	2.00	2.70
PICLAlign-H	49.1	40.5	53.8	57.6	50.3	2.00	2.00	0.50	0.00	3.50	1.00	1.50



(a) Doc Length (b) Doc Genre

Figure 2: Impact of benign document length and genre on WGT-ASR (SHINE-Qwen3-8B). We combine multiple SQuAD documents to construct longer documents in (a) and vary the genre while keeping the length fixed in (b).



(a) ICA #Demonstrations (b) ICA Source

Figure 3: Impact of the number and source of ICA demonstrations on WGT-ASR (SHINE-Qwen3-8B). We vary the number of ICA demonstrations in (a) and use examples from different sources (e.g., LLM-LAT) in (b).

across different jailbreak datasets. This suggests that benign and ICA documents may induce partially shared safety-compromising patterns in the generated LoRAs. Appendix A.1 further shows that PICLAlign introduces little to no additional over-refusal.

Compared with the naïve variants, Doc-DRO consistently reduces ASR (e.g., from 3.2% to 0% on average across six attack settings under D2L-Gemma2-2B-IT). By optimizing against worst-case document distributions, Doc-DRO improves robustness to underrepresented document variations. Replacing Doc-DRO with Flat-LoRA also improves robustness by perturbing document-induced LoRAs during optimization, but it remains less effective. These results suggest that robustness to atypical attack artifacts benefits from explicitly accounting for distribution shifts during alignment.

When comparing PICLAlign-L with PICLAlign-H, we observe that PICLAlign-L generally achieves lower ASR and higher utility across evaluation settings. One possible reason is that PICLAlign-H must avoid utility collapse of the hypernetwork itself while learning to generate safety-aligned LoRAs, making the task more challenging. Moreover, the utility-preserving designs in PICLAlign-H are important: removing them leads to an average utility drop of around 2% across the three settings, as shown in Appendix Table 6. Finally, PICLAlign-L also reduces ASR under the bare-query setting as a byproduct, reaching nearly 0% ASR, as shown in Appendix Figure 6.

4.3 Ablation Studies

In this part, we conduct ablation studies to answer two research questions: **(Q1)** how do the original PICL-integrated systems and our aligned variants perform under diverse document contexts? and **(Q2)** how robust are our alignment algorithms to variations in hyperparameters?

Impact of document type. As shown in Figure 2 and Appendix Figure 7, the original PICL systems are vulnerable to harmful queries after internalizing benign documents, with longer documents leading to higher ASR (from 38.5% to 53%), likely because they induce larger knowledge updates and greater deviation from the original model. The original systems are also more vulnerable to Expository documents of the same length. This may be because expository documents are more instructional, which shifts the model toward more answer-oriented responses and weakens its refusal behavior. In contrast, our aligned systems maintain low ASRs across document lengths and types, suggesting that our training strategy captures both common and atypical safety-compromising patterns.

Impact of ICA designs. We evaluate the impact of ICA design choices in Figure 3 and Appendix Figure 8. Increasing the number of ICA examples also increases ASR, consistent with our observations for benign documents. For the original PICL system, ASR is higher when demonstrations are sampled from JBB or LLM-LAT (72%) than from SafeRLHF (63.5%), as the latter contains fewer explicit attack commands. However, the original D2L-Gemma2-2B-IT remains robust to source variation because it is inherently robust to ICA documents (2% ASR under ICL; Table 1). Notably, the aligned systems maintain low ASRs under ICA despite not being explicitly optimized for them.

Impact of hyperparameters. Figure 4 and Appendix Figures 9-10 examine the impact of ϵ in Doc-DRO and the shadow dataset (i.e., the source and number of shadow queries) on alignment results. Doc-DRO performs best with an appropriate perturbation radius: a large radius optimizes over unnecessary document distributions, whereas a small radius is insufficient to be effective. Besides, training PICLAlign with the LLM-LAT dataset, which consists of simple jailbreak prompts, fails to achieve strong safety alignment, resulting in ASRs above 10%. This is mainly because the original PICL-integrated systems are relatively robust to these synthesized queries. For example, PICL only amplifies the LLM-LAT ASR from 1% to 4% on D2L-Gemma2-2B-IT, resulting in weak alignment signals for optimization. In addition, increasing the number of harmful queries in the shadow dataset has little impact on the alignment results.



Figure 4: Impact of (a) ϵ in Doc-DRO and (b) the source of the shadow dataset on the alignment results of PICLAlign-L (SHINE-Qwen3-8B).

Appendix Figures 11-12 examine the impact of the loss strengths. Removing the retain loss ($\lambda = 0$) greatly degrades PICL utility, with scores decreasing by over 10%. Increasing β slightly sacrifices safety enhancement for utility preservation, reflecting the trade-off introduced by regularization.

5 Related Work

ICL and PICL. ICL (Dong et al., 2024) enables LLMs to leverage contextual information without updating parameters. In contrast, PICL parametrizes the contexts, typically by generating a context-specific LoRA through a hypernetwork (Charakorn et al., 2026; Liu et al., 2026). While initially designed for contextual understanding, PICL has recently been adopted for various applications, including user profiling (Tan et al., 2026), agent skills (Yu et al., 2026), agent memory (Diao et al., 2026), and coding (Hotsko et al., 2026). However, the safety risks of this paradigm remain unexplored.

Defenses against harmful fine-tuning attacks. Existing defenses against fine-tuning attacks (Qi et al., 2024; Huang et al., 2024) under the PEFT setting can potentially be extended to PICL. Fine-tuning-stage defenses (Yang et al., 2026; Zhang et al., 2026) modify parameter updates during fine-tuning and achieve promising results, but do not apply to PICL. Post-fine-tuning defenses instead perform post-hoc parameter realignment, including training-free approaches (Hsu et al., 2024; Ao et al., 2025) and training-based approaches (Gudipudi et al., 2025; Xue & Mirzasoleiman, 2025; Djuhera et al., 2026). However, their effectiveness depends on the properties of the adapted LLM (Yang et al., 2026), and they fail to reliably ensure safety under PICL.

6 Conclusion

In this work, we take the first step toward analyzing the safety risks introduced by the PICL paradigm. Our studies reveal that PICL-generated LoRAs can compromise the safety of integrated systems, while existing defenses fail to achieve strong safety alignment under PICL. To fill this gap, we propose a simple yet effective framework, PICLAlign, with two alignment approaches, and enhance its robustness with a tailored Doc-DRO mechanism. Experiments across three PICL-integrated systems show that PICLAlign consistently achieves low ASR while preserving PICL utility. Interesting future directions include: (1) investigating other security and IP issues inherent in PICL-integrated LLM systems; and (2) leveraging PICL as a defense against prompt-level attacks such as prompt injection.

AI USE STATEMENT

In this work, we used generative AI tools to assist with data generation, creating scripts for ablation studies based on our experimental designs, interpreting experimental results, and editing and polishing the manuscript. For data generation, we used GPT-4o to generate refusal responses. For paper editing, we used generative AI tools to improve the paper's clarity, readability, grammar, and overall presentation. The proposed problem, methodology, theoretical framework, and experimental designs were developed entirely without generative AI assistance. All AI-assisted work was carefully reviewed and verified; for example, AI-assisted scripts were reviewed and tested, AI-assisted interpretations were manually checked against the experimental results and ablation studies, and polished sentences were checked to ensure that they accurately reflected our intended meaning and did not introduce unsupported claims. We take responsibility for the final content of this work, including all text, code, claims, analyses, results, and conclusions.

ETHICS STATEMENT

This work identifies a safety risk in the novel, emerging parametric in-context learning (PICL) framework and proposes a tailored defense framework to mitigate it. While the identified risk could be potentially misused, our work aims to characterize the vulnerability and develop effective mitigation strategies. We present the findings responsibly, with a focus on improving the safety and security of these emerging frameworks.

REPRODUCIBILITY STATEMENT

We provide detailed descriptions of the proposed method, experimental settings, models, datasets, evaluation metrics, and implementation details in the main paper to facilitate reproducibility. We also provide detailed descriptions of the data processing and evaluation procedures in the Appendix for reference. All checkpoints and datasets used in our experiments are publicly available. Our results can be faithfully reproduced based on the detailed descriptions provided in the main paper and Appendix. Upon acceptance, we will release the source code and relevant configuration files to further facilitate the reproduction of our results.

REFERENCES

Shuang Ao, Yi Dong, Jinwei Hu, and Sarvapali D Ramchurn. Safe pruning lora: Robust distance-guided pruning for safety alignment in adaptation of llms. *Transactions of the Association for Computational Linguistics*, 13:1474–1487, 2025.

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. *Advances in Neural Information Processing Systems*, 37:136037–136083, 2024.

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, et al. Longbench: A bilingual, multitask benchmark for long context understanding. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 1: Long papers)*, pp. 3119–3137, 2024.

Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, et al. Ms marco: A human generated machine reading comprehension dataset. *arXiv preprint arXiv:1611.09268*, 2016.

Patrick Chao, Edoardo Debenedetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwag, Edgar Dobriban, Nicolas Flammarion, George J Pappas, Florian Tramer, et al. Jailbreakbench: An open robustness benchmark for jailbreaking large language models. *Advances in Neural Information Processing Systems*, 37:55005–55029, 2024.

Rujikorn Charakorn, Edoardo Cetin, Shinnosuke Uesaka, and Robert Tjarko Lange. Doc-to-lora: Learning to instantly internalize contexts. *arXiv preprint arXiv:2602.15902*, 2026.

Jianhui Chen, Xiaozhi Wang, Zijun Yao, Yushi Bai, Lei Hou, and Juanzi Li. Towards understanding safety alignment: A mechanistic perspective from safety neurons. *Advances in Neural Information Processing Systems*, 38:12665–12700, 2026.

Xingjian Diao, Wenbo Li, Yashas Malur Saidutta, Avinash Amballa, Lazar Valkov, and Srinivas Chappidi. Doc-to-atom: Learning to compile and compose memory atoms. *arXiv preprint arXiv:2606.12400*, 2026.

Aladin Djuhera, Swanand Ravindra Kadhe, Farhan Ahmed, Syed Zawad, and Holger Boche. Safemerge: Preserving safety alignment in fine-tuned large language models via selective layer-wise model merging. In *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 35316–35335, 2026.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Baobao Chang, et al. A survey on in-context learning. In *Proceedings of the 2024 conference on empirical methods in natural language processing*, pp. 1107–1128, 2024.

Rui Gao and Anton Kleywegt. Distributionally robust stochastic optimization with wasserstein distance. *Mathematics of Operations Research*, 48(2):603–655, 2023.

Satya Swaroop Gudipudi, Sreeram Vipparla, Harpreet Singh, Shashwat Goel, and Ponnurangam Kumaraguru. Enhancing ai safety through the fusion of low rank adapters. In *Pacific-Asia Conference on Knowledge Discovery and Data Mining*, pp. 349–361. Springer, 2025.

William Hackett, Lewis Birch, Stefan Trawicki, Neeraj Suri, and Peter Garraghan. Bypassing llm guardrails: An empirical analysis of evasion attacks against prompt injection and jailbreak detection systems. In *Proceedings of the The First Workshop on LLM Security (LLMSEC)*, pp. 101–114, 2025.

Felix Hamborg, Norman Meuschke, Corinna Breitinger, and Bela Gipp. news-please: A generic news crawler and extractor. In *Proceedings of the 15th International Symposium of Information Science*, pp. 218–223, March 2017. doi: 10.5281/zenodo.4120316.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of llms. *Advances in neural information processing systems*, 37:8093–8131, 2024.

Jun He, Liqun Wang, Liu Liu, Jiao Feng, and Hao Wu. Long document classification from local word glimpses via recurrent attention learning. *IEEE Access*, 7:40707–40718, 2019.

Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop qa dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics*, pp. 6609–6625, 2020.

Liliana Hotsko, Yinxi Li, Yuntian Deng, and Pengyu Nie. Code2lora: Hypernetwork-generated adapters for code language models under software evolution. *arXiv preprint arXiv:2606.06492*, 2026.

Chia-Yi Hsu, Yu-Lin Tsai, Chih-Hsun Lin, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. Safe lora: The silver lining of reducing safety risks when finetuning large language models. *Advances in neural information processing systems*, 37:65072–65094, 2024.

Tiansheng Huang, Sihao Hu, Fatih Ilhan, Selim Furkan Tekin, and Ling Liu. Harmful fine-tuning attacks and defenses for large language models: A survey. *arXiv preprint arXiv:2409.18169*, 2024.

Tao Li, Zhengbao He, Yujun Li, Yasheng Wang, Lifeng Shang, and Xiaolin Huang. Flat-lora: Low-rank adaptation over a flat loss landscape. *arXiv preprint arXiv:2409.14396*, 2024.

Kevin Lin, Oyvind Tafjord, Peter Clark, and Matt Gardner. Reasoning over paragraph effects in situations. In *Proceedings of the 2nd Workshop on Machine Reading for Question Answering*, pp. 58–62, 2019.

Yewei Liu, Xiyuan Wang, Yansheng Mao, Yoav Gelbery, Haggai Maron, and Muhan Zhang. Shine: A scalable in-context hypernetwork for mapping context to lora in a single pass. *arXiv preprint arXiv:2602.06358*, 2026.

Anton Lozhkov, Loubna Ben Allal, Leandro von Werra, and Thomas Wolf. Fineweb-edu: the finest collection of educational content, 2024. URL `https://huggingface.co/datasets/HuggingFaceFW/fineweb-edu`.

Kaifeng Lyu, Haoyu Zhao, Xinran Gu, Dingli Yu, Anirudh Goyal, and Sanjeev Arora. Keeping LLMs aligned after fine-tuning: The crucial role of prompt templates. *arXiv preprint arXiv:2402.18540*, 2024.

Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to! In *International Conference on Learning Representations*, volume 2024, pp. 30988–31043, 2024.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 conference on empirical methods in natural language processing*, pp. 2383–2392, 2016.

Paul Röttger, Hannah Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. Xstest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 5377–5400, 2024.

Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. " do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. In *Proceedings of the 2024 on ACM SIGSAC Conference on Computer and Communications Security*, pp. 1671–1685, 2024.

Weihang Su, Yichen Tang, Qingyao Ai, Junxi Yan, Changyue Wang, Hongning Wang, Ziyi Ye, Yujia Zhou, and Yiqun Liu. Parametric retrieval augmented generation. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pp. 1240–1250, 2025.

Zhaoxuan Tan, Zixuan Zhang, Haoyang Wen, Zheng Li, Rongzhi Zhang, Pei Chen, Fengran Mo, Zheyuan Liu, Qingkai Zeng, Qingyu Yin, et al. Instant personalized large language model adaptation via hypernetwork. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 23557–23580, 2026.

Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, et al. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024.

Zeming Wei, Yifei Wang, Ang Li, Yichuan Mo, and Yisen Wang. Jailbreak and guard aligned language models with only few in-context demonstrations. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2026.

Yueqi Xie, Jingwei Yi, Jiawei Shao, Justin Curl, Lingjuan Lyu, Qifeng Chen, Xing Xie, and Fangzhao Wu. Defending chatgpt against jailbreak attack via self-reminders. *Nature Machine Intelligence*, 5 (12):1486–1496, 2023.

Zaiyan Xu, Sushil Vemuri, Kishan Panaganti, Dileep Kalathil, Rahul Jain, and Deepak Ramachandran. Robust llm alignment via distributionally robust direct preference optimization. *Advances in Neural Information Processing Systems*, 38:27039–27076, 2026.

Yihao Xue and Baharan Mirzasoleiman. Lora is all you need for safety alignment of reasoning llms. *arXiv preprint arXiv:2507.17075*, 2025.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Shuo Yang, Qihui Zhang, Yuyang Liu, Yue Huang, Xiaojun Jia, Kun-Peng Ning, Jia-Yu Yao, Jigang Wang, Dai Hailiang, Yibing Song, et al. Asft: Anchoring safety during llm fine-tuning within narrow safety basin. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pp. 34322–34330, 2026.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 conference on empirical methods in natural language processing*, pp. 2369–2380, 2018.

Aofan Yu, Chenyu Zhou, Tianyi Xu, Zihan Guo, Rong Shan, Zhihui Fu, Jun Wang, Weiwen Liu, Yong Yu, Weinan Zhang, et al. Latentskill: From in-context textual skills to in-weight latent skills for llm agents. *arXiv preprint arXiv:2606.06087*, 2026.

Tianhe Yu, Saurabh Kumar, Abhishek Gupta, Sergey Levine, Karol Hausman, and Chelsea Finn. Gradient surgery for multi-task learning. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

Bingjie Zhang, Yibo Yang, Ren Zhe, Dandan Guo, Jindong Gu, Philip Torr, and Bernard Ghanem. A guardrail for safety preservation: When safety-sensitive subspace meets harmful-resistant null-space. In *International Conference on Learning Representations*, volume 2026, pp. 134322–134347, 2026.

Zhexin Zhang, Junxiao Yang, Pei Ke, Fei Mi, Hongning Wang, and Minlie Huang. Defending large language models against jailbreaking attacks through goal prioritization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8865–8887, 2024.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

A Appendix

A.1 Over-refusal analysis

Tables 3-5 already show that our safety alignment does not compromise the utility of the PICL-integrated systems for their intended use. Specifically, the average utility drop across triples from all utility evaluation datasets is consistently within 1–2%, indicating that PICLAlign preserves utility in its practical deployment scenarios. To further evaluate over-refusal, we evaluate PICL-integrated systems on safe prompts that superficially resemble harmful requests from the XSTest (Röttger et al., 2024) dataset, pairing each prompt with a benign document sampled from SQuAD. We measure refusal rates using the WildGuard refusal score rather than its harmfulness score. In practice, the deployer is unlikely to combine unrelated documents with these instructions, as PICL is unnecessary in such cases; we include this setting as a stress test for over-refusal behavior. Our results show that PICLAlign (e.g., PICLAlign-L) changes the refusal rate by only 4.8%, 4.4%, and -3.6% relative to the original PICL-integrated systems, respectively. These results demonstrate that PICLAlign preserves the intended utility of PICL-integrated systems without substantially increasing over-refusal, while achieving strong safety alignment.

A.2 Discussion on the adaptive attacks

We further investigate whether an adaptive attacker can optimize an adversarial document whose generated LoRA significantly compromises the safety alignment of the integrated LLM. Specifically, we assume that the attacker has white-box access to the PICL-integrated LLM system and uses GCG (Zou et al., 2023) to optimize an adversarial suffix of length 20. We randomly select five SQuAD documents as camouflage and optimize the suffix such that harmful queries from a small attacker-owned shadow dataset (i.e., 10 pairs from the JailbreakBench dataset) can induce unsafe responses. Across these documents and 10 harmful queries per document, our results show that

white-box suffix optimization increases ASR by only 2% on the unaligned D2L-Gemma2-2B-IT and does not increase ASR when optimized directly against the aligned variants. We hypothesize that it is inherently difficult to optimize a universal and transferable suffix that can trigger unsafe responses across diverse harmful queries, especially in long-context scenarios.

Note that this white-box setting represents an idealized attacker with full access to the PICL-integrated system, which is beyond our threat model. We therefore leave systematic investigations of adaptive attacks, including optimization over the specific PICL pathway, to future work.

A.3 Limitations

In this work, we focus on two representative and widely used PICL frameworks (i.e., D2L and SHINE) designed for general contextual understanding. Extending our analysis to domain-specific PICL frameworks, such as those for coding or agentic tasks, is left for future work.

A.4 Proof of theorem 3.1

A.4.1 Definitions and Assumptions

Documents. We treat each document d generically as a point in a continuous space $\mathcal{Z} \subseteq \mathbb{R}^m$.

Wasserstein distance. Given two distributions μ and ξ over $\mathcal{Z}$, the p-Wasserstein distance is

$$W_p(\mu, \xi) := \Big(\inf_{\gamma \in \Pi(\mu,\xi)} \int c(d_1, d_2)^p \, d\gamma(d_1, d_2) \Big)^{1/p}, \tag{7}$$

where $\Pi(\mu, \xi)$ is the set of couplings with marginals μ and ξ, and $c(d_1, d_2) = \|d_1 - d_2\|_2$ is the transport cost. We let q be the Hölder conjugate of p, i.e., $1/p + 1/q = 1$.

Per-document alignment loss. For a fixed alignment module ψ, we define the per-document alignment loss by averaging over the shadow data:

$$\ell_{\text{align}}(\psi(d)) := \mathbb{E}_{(x_{\text{atk}}, y_{\text{ref}}) \sim D_{\text{shadow}}} \Big[-\log p_{\theta + \psi(d)} \big(y_{\text{ref}} \mid x_{\text{atk}} \big) \Big]. \tag{8}$$

We assume $\ell_{\text{align}}(\psi(d))$ is differentiable in d, and that $\nabla_d \ell_{\text{align}}(\psi(d))$ is (L, α)-Hölder continuous for $\alpha \in (0, 1]$:

$$\big\| \nabla_d \ell_{\text{align}}(\psi(d_1)) - \nabla_d \ell_{\text{align}}(\psi(d_2)) \big\|_2 \le L \|d_1 - d_2\|_2^{\alpha}, \quad \forall d_1, d_2 \in \mathcal{Z}. \tag{9}$$

This yields the standard remainder bound for the first-order Taylor expansion:

$$\big| \ell_{\text{align}}(\psi(d')) - \ell_{\text{align}}(\psi(d)) - \langle \nabla_d \ell_{\text{align}}(\psi(d)),\, d' - d \rangle \big| \le \frac{L}{1+\alpha} \|d' - d\|_2^{1+\alpha}. \tag{10}$$

Objectives. For brevity, write $\ell(d) := \ell_{\text{align}}(\psi(d))$ and $G(d) := \|\nabla_d \ell(d)\|_2$. Given a radius $\epsilon > 0$, the worst-case alignment loss in Eq. 4 is

$$\mathcal{L}_{\text{DRO}}^{\epsilon,p}(\psi) := \sup_{\mathcal{Q}:\, W_p(\mathcal{Q}, P_{\text{ret}}) \le \epsilon} \mathbb{E}_{d \sim \mathcal{Q}} \big[\ell(d) \big]. \tag{11}$$

To approximate it, we introduce a gradient-norm surrogate $\mathcal{L}_{\text{GN}}^{\epsilon}(\psi)$, and the finite-difference surrogate $\mathcal{L}_{\text{FD}}^{\epsilon,\delta}(\psi)$ in Eq. 5, which replaces the gradient norm with a finite difference:

$$\mathcal{L}_{\text{GN}}^{\epsilon}(\psi) := \mathbb{E}_{d \sim P_{\text{ret}}} \big[\ell(d) \big] + \epsilon \Big(\mathbb{E}_{d \sim P_{\text{ret}}} \big[G(d)^q \big] \Big)^{1/q}, \tag{12}$$

$$\mathcal{L}_{\text{FD}}^{\epsilon,\delta}(\psi) := \mathbb{E}_{d \sim P_{\text{ret}}} \big[\ell(d) \big] + \epsilon \Big(\mathbb{E}_{d \sim P_{\text{ret}}} \big[|\Delta_\delta(d)|^q \big] \Big)^{1/q}, \quad \Delta_\delta(d) = \frac{\ell(d + \delta g_{\text{align}}^d) - \ell(d)}{\delta}, \tag{13}$$

where $g_{\text{align}}^d = \nabla_d \ell(d) / G(d)$ is the normalized gradient direction, with $g_{\text{align}}^d = 0$ when $G(d) = 0$.

Remark (practical instantiation). A key property of PICL is that the document affects the model only through its induced LoRA $\Delta W_d = H_\phi(d)$, so $\ell(d) = \tilde{\ell}(\Delta W_d)$, where $\tilde{\ell}(\Delta W) := \mathbb{E}_{D_{\text{shadow}}}[-\log p_{\theta + \Delta W (+\Delta W_s)}(y_{\text{ref}} \mid x_{\text{atk}})]$ (ΔW_s only for PICLAlign-L). Under the transport cost

$c_H(d_1, d_2) = \|H_\phi(d_1) - H_\phi(d_2)\|_2$, Doc-DRO over documents is upper-bounded by Doc-DRO over LoRAs (Lemma A.4.1), and Theorem 3.1 applies with d replaced by ΔW_d. We therefore perturb ΔW_d rather than d, avoiding ill-defined perturbations on discrete text and improving efficiency. Accordingly, g^d_{align} is the normalized gradient of $\tilde{\ell}$ w.r.t. ΔW_d, and $\Delta_\delta(d) = (\tilde{\ell}(\Delta W_d + \delta g^d_{\text{align}}) - \tilde{\ell}(\Delta W_d))/\delta$. For PICLAlign-L, ΔW_d is produced by the frozen hypernetwork, and we perturb the document-induced adaptation rather than the trainable weights; for PICLAlign-H, ΔW_d is produced by the current hypernetwork, so the perturbation ball evolves with ϕ and remains valid.

Lemma A.4.1 (Reduction to LoRA Space). *Let $\mathcal{R} = \{H_\phi \# Q\}$ be the set of realizable LoRA distributions and $W_p^{c_H}$ denote Eq. 7 with cost c_H (Polish spaces, measurable H_ϕ). Then*

$$\sup_{W_p^{c_H}(Q, P_{ret}) \le \epsilon} \mathbb{E}_Q[\ell] = \sup_{\mu \in \mathcal{R},\, W_p(\mu, H_\phi \# P_{ret}) \le \epsilon} \mathbb{E}_\mu[\tilde{\ell}] \le \sup_{W_p(\mu, H_\phi \# P_{ret}) \le \epsilon} \mathbb{E}_\mu[\tilde{\ell}].$$

Proof. $\mathbb{E}_Q[\ell] = \mathbb{E}_{H_\phi \# Q}[\tilde{\ell}]$ by change of variables. Couplings of (Q, P_{ret}) push forward to couplings of the pushforwards with identical cost, and conversely lift back by disintegrating along H_ϕ. Hence $W_p^{c_H}(Q, P_{\text{ret}}) = W_p(H_\phi \# Q, H_\phi \# P_{\text{ret}})$, giving the equality; the inequality holds since $\mathcal{R}$ is a subset. □

A.4.2 Proof of the Approximation Bound

We show that $|\mathcal{L}^{\epsilon,\delta}_{\text{FD}}(\psi) - \mathcal{L}^{\epsilon}_{\text{GN}}(\psi)| \le \frac{L}{1+\alpha}\epsilon\delta^\alpha$ and $|\mathcal{L}^{\epsilon}_{\text{GN}}(\psi) - \mathcal{L}^{\epsilon,p}_{\text{DRO}}(\psi)| \le \frac{L}{1+\alpha}\epsilon^{1+\alpha}$, and combine them via the triangle inequality to prove Theorem 3.1.

Step 1: Finite-difference error. Applying Eq. 10 with $d' = d + \delta g^d_{\text{align}}$ and $\|g^d_{\text{align}}\|_2 \le 1$ gives

$$\ell(d + \delta g^d_{\text{align}}) = \ell(d) + \delta\, G(d) + r(d), \qquad |r(d)| \le \frac{L}{1+\alpha}\delta^{1+\alpha}. \tag{14}$$

Dividing by δ yields $\Delta_\delta(d) = G(d) + r(d)/\delta$. Since $G(d) \ge 0$, we have $\big||\Delta_\delta(d)| - G(d)\big| \le \frac{L}{1+\alpha}\delta^\alpha$ pointwise. By Minkowski's inequality in $L_q(P_{\text{ret}})$,

$$\Big|\big(\mathbb{E}\,|\Delta_\delta(d)|^q\big)^{1/q} - \big(\mathbb{E}\,G(d)^q\big)^{1/q}\Big| \le \big(\mathbb{E}\,\big||\Delta_\delta(d)| - G(d)\big|^q\big)^{1/q} \le \frac{L}{1+\alpha}\delta^\alpha. \tag{15}$$

Multiplying by ϵ gives $|\mathcal{L}^{\epsilon,\delta}_{\text{FD}}(\psi) - \mathcal{L}^{\epsilon}_{\text{GN}}(\psi)| \le \frac{L}{1+\alpha}\epsilon\delta^\alpha$.

Step 2: Upper bound on the worst-case loss. Let $\mathcal{Q}$ satisfy $W_p(\mathcal{Q}, P_{\text{ret}}) \le \epsilon$, and let $\pi \in \Pi(P_{\text{ret}}, \mathcal{Q})$ be a coupling with $(\mathbb{E}_\pi \|d' - d\|_2^p)^{1/p} \le \epsilon + \eta$ for arbitrary $\eta > 0$. By Eq. 10 and the Cauchy–Schwarz inequality,

$$\mathbb{E}_{d' \sim \mathcal{Q}}[\ell(d')] \le \mathbb{E}_{d \sim P_{\text{ret}}}[\ell(d)] + \mathbb{E}_\pi\big[G(d)\|d' - d\|_2\big] + \frac{L}{1+\alpha}\mathbb{E}_\pi\|d' - d\|_2^{1+\alpha}. \tag{16}$$

By Hölder's inequality, $\mathbb{E}_\pi[G(d)\|d' - d\|_2] \le (\mathbb{E}\,G(d)^q)^{1/q}(\epsilon + \eta)$. Since $p \ge 1 + \alpha$, Jensen's inequality gives $\mathbb{E}_\pi\|d' - d\|_2^{1+\alpha} \le (\epsilon + \eta)^{1+\alpha}$. Letting $\eta \to 0$ and taking the supremum over $\mathcal{Q}$,

$$\mathcal{L}^{\epsilon,p}_{\text{DRO}}(\psi) \le \mathcal{L}^{\epsilon}_{\text{GN}}(\psi) + \frac{L}{1+\alpha}\epsilon^{1+\alpha}. \tag{17}$$

Step 3: Lower bound on the worst-case loss. If $\mathbb{E}\,G(d)^q = 0$, then $\mathcal{L}^{\epsilon}_{\text{GN}}(\psi) = \mathbb{E}_{d \sim P_{\text{ret}}}[\ell(d)]$, and the bound follows by taking $\mathcal{Q} = P_{\text{ret}}$. Otherwise, construct $\mathcal{Q}^*$ by transporting each $d \sim P_{\text{ret}}$ along its gradient direction:

$$d^* = d + \epsilon(d)\, g^d_{\text{align}}, \qquad \epsilon(d) = \epsilon\, \frac{G(d)^{q/p}}{\big(\mathbb{E}\,G(d)^q\big)^{1/p}}, \tag{18}$$

with $\epsilon(d) \equiv \epsilon$ when $p = \infty$. Then $\mathbb{E}[\epsilon(d)^p] = \epsilon^p$, so $W_p(\mathcal{Q}^*, P_{\text{ret}}) \le \epsilon$. Using Eq. 10 and $q/p + 1 = q$,

$$\mathbb{E}_{\mathcal{Q}^*}[\ell(d^*)] \ge \mathbb{E}[\ell(d)] + \mathbb{E}\big[\epsilon(d)G(d)\big] - \frac{L}{1+\alpha}\mathbb{E}\big[\epsilon(d)^{1+\alpha}\big] \ge \mathcal{L}^{\epsilon}_{\text{GN}}(\psi) - \frac{L}{1+\alpha}\epsilon^{1+\alpha}, \tag{19}$$

where $\mathbb{E}[\epsilon(d)G(d)] = \epsilon(\mathbb{E}\,G(d)^q)^{1/q}$, and $\mathbb{E}[\epsilon(d)^{1+\alpha}] \le \epsilon^{1+\alpha}$ by Jensen's inequality since $p \ge 1+\alpha$. Since $\mathcal{Q}^*$ is feasible, $\mathcal{L}^{\epsilon,p}_{\text{DRO}}(\psi) \ge \mathcal{L}^{\epsilon}_{\text{GN}}(\psi) - \frac{L}{1+\alpha}\epsilon^{1+\alpha}$.

Step 4: Combining. By Steps 1–3 and the triangle inequality,

$$\left|\mathcal{L}^{\epsilon,\delta}_{\text{FD}}(\psi) - \mathcal{L}^{\epsilon,p}_{\text{DRO}}(\psi)\right| \le \frac{L}{1+\alpha}\left(\epsilon^{1+\alpha} + \epsilon\,\delta^{\alpha}\right), \tag{20}$$

which completes the proof. ■

A.5 Additional details

A.5.1 Dataset

We describe the datasets used for safety alignment, utility evaluation, and safety evaluation below.

(1) For safety alignment, we randomly sample 1,000 harmful queries from the WildGuardTrain dataset (Han et al., 2024) and generate their refusal responses using GPT-4o, resulting in a shadow dataset of 1,000 (query, refusal response) pairs. To simulate the PICL process, each pair is paired with a benign document sampled from the retain dataset during alignment. For the retain dataset, we randomly sample 2,000 triples ($< 0.2\%$ of the full set) from the respective training dataset of each PICL framework (the FineWeb dataset (Lozhkov et al., 2024) for D2L and the 1QA dataset (Liu et al., 2026) for SHINE). For each PICL framework, the defender can collect a small amount of data from its corresponding training distribution to construct the retain dataset, given its knowledge of the framework.

(2) For utility evaluation, we follow the evaluation settings of D2L and SHINE and evaluate their respective integrated systems using their own utility datasets, given that the two frameworks are trained and evaluated separately. This setup better reflects the utility degradation caused by our alignment methods. For SHINE, we use SQ-S (SHINE's adapted version of SQuAD (Rajpurkar et al., 2016)), MS MARCO V1 (Bajaj et al., 2016), HotpotQA (Yang et al., 2018), and 2Wiki (Ho et al., 2020) as utility evaluation datasets and sample a fixed set of 1,000 test samples from each dataset. For MS MARCO V1, we discard examples whose answers are empty (marked "No Answer Present"). For D2L, we use SQ (Rajpurkar et al., 2016), ROPES (Lin et al., 2019), HotpotQA-L (the HotpotQA LongBench version), and 2Wiki-L (the 2Wiki LongBench version) (Bai et al., 2024) as utility evaluation datasets. Since HotpotQA-L and 2Wiki-L are limited in size (around 300 samples), we sample a fixed set of 200 test samples from them. For the LongBench datasets, we further sample from subsets whose documents contain at most 12K tokens due to the memory constraints of internalization.

(3) For safety evaluation, we use WildGuardTest (WGT) (Han et al., 2024), DirectHarm (DH) (Lyu et al., 2024), and Do-Anything-Now (DAN) (Shen et al., 2024) as attack evaluation datasets. We sample a fixed set of 200 harmful queries from each dataset. Except in the bare-query setting, for each query, we either randomly sample a benign document from a benign dataset (e.g., SQuAD) or construct a malicious document using multiple malicious demonstrations (i.e., 5-10) sampled from JailbreakBench (Chao et al., 2024), denoted as an in-context attack (ICA). In our ablation study, we further sample News and Academic documents from the CC-News (Hamborg et al., 2017) and Arxiv (He et al., 2019) datasets for attack evaluation.

A.5.2 Baselines details

We compare PICLAlign with existing defenses that can be directly applied or adapted to intervene on generated LoRAs, including **(1) internalized text-based defenses** based on self-reminders (Xie et al., 2023) and in-context defenses (ICD) (Wei et al., 2026); **(2) training-free realignment methods**, such as SafeLoRA (Hsu et al., 2024) and SPLoRA (Ao et al., 2025); and **(3) training-based realignment methods** that naïvely train and compose a safety LoRA (Gudipudi et al., 2025) (namely Standard Safety LoRA). We also compare with defenses that do not target generated LoRAs, including **representation-level defenses**, such as steering vectors (Arditi et al., 2024), and **prompt-level defenses**, such as original ICD. Besides, we further compare Doc-DRO with Flat-LoRA (Li et al., 2024), a sharpness-aware optimization method tailored to LoRA. Specifically, we describe these baselines in detail as follows:

Steering Vector (Arditi et al., 2024). We compute the refusal direction as the difference between the hidden states of harmful and harmless queries at a middle layer, and add it to every token's hidden state at test time. In our setting, we scale the vector to 10% or 25% of the average hidden-state norm of each underlying LLM, evaluating both scales for every LLM.

Internalized text-based defenses. Since the document enters the model through the generated LoRA rather than the context, we prepend the defense prompt to each document before feeding it into the hypernetwork. We consider Self-Reminder (Xie et al., 2023), which instructs the model to respond responsibly, and ICD (Wei et al., 2026), which provides demonstrations of how to respond to harmful queries (See defense prompts in Appendix A.6). We further include Goal Prioritization (Zhang et al., 2024) as a prompt-level defense (see Table 7), which instructs the model to prioritize safety over helpfulness. We omit its internalized variant for brevity, as it performs poorly.

SafeLoRA (Hsu et al., 2024). SafeLoRA constructs a safety-aligned subspace from the weight difference between the aligned and unaligned models, and projects the X LoRA layers that are least similar to their projections onto this subspace. We apply it post-hoc to each generated LoRA ΔW_d and set $X = 40$ following GuardSpace (Zhang et al., 2026).

SPLoRA (Ao et al., 2025). SPLoRA uses the same safety-aligned subspace as SafeLoRA, but measures each layer's deviation from its projection with E-DIEM and prunes the X most deviating LoRA layers. We apply it post hoc to each generated LoRA ΔW_d and follow their default configurations.

Standard Safety LoRA (Gudipudi et al., 2025; Xue & Mirzasoleiman, 2025; Djuhera et al., 2026). The naïve counterpart of PICLAlign-L: we train a safety LoRA with the same objective and datasets on the base LLM θ, rather than on $\theta + \Delta W_d$ obtained via simulation, and compose it with the generated LoRA at test time. We omit SafeMerge (Djuhera et al., 2026), as it relies on the same layer-wise safety-subspace similarity as SafeLoRA, which performs poorly in our setting.

Flat-LoRA (Li et al., 2024). Flat-LoRA seeks flat minima by adding random weight-scaled Gaussian perturbations ($\sigma = 0.05$) to the integrated low-rank weight update (i.e., the safety LoRA for PICLAlign-L and the hypernetwork-generated LoRA for PICLAlign-H) during training. We use it in place of Doc-DRO to enforce sharpness-aware minimization of the refusal loss. For PICLAlign-H, we adapt it by perturbing the generated LoRA rather than the ~ 315M-parameter hypernetwork, which is impractical to perturb directly; the generated LoRA provides a cheap, differentiable surrogate whose perturbations backpropagate into the hypernetwork.

A.5.3 Evaluation metrics

For each PICL framework, we evaluate its integrated systems (both original and aligned variants) using its official evaluation protocol and report utility scores. For D2L, we use word-level ROUGE-L, reporting F1 for D2L-Gemma2-2B-IT and Recall for D2L-Qwen3-4B-IT, as the latter tends to produce more verbose outputs for which F1 can be misleading. For SHINE, we follow the original work and report word-level token-overlap QA-F1 for all its integrated systems. For attack evaluation, we measure the ASR on (document context, harmful query) pairs constructed from different document and jailbreak datasets, with WildGuard (Han et al., 2024) as the judge model.

A.5.4 Implementation details

We conduct all experiments on a server with 4 NVIDIA A6000 GPUs. All results in the main tables are averaged over three runs with different random seeds, with very low variance across runs. For PICLAlign-L, we train the safety LoRA, following standard recipes that target the q_proj, v_proj, and o_proj matrices, with a constant learning rate of $1e{-4}$; for PICLAlign-H, we fine-tune the hypernetwork with a learning rate of $1e{-5}$ and cosine learning-rate decay, as the hypernetwork is more sensitive to weight updates. The retain dataset contains 2,000 triples, while the shadow dataset contains 1,000 pairs by default. We optimize both alignment modules for one epoch based on the retain dataset, using an effective batch size of 16 for both the retain and alignment losses. Since the underlying models are already aligned, training converges within one epoch, and further optimization can cause overfitting to the small retain set and degrade PICL utility (for example, fine-tuning PICLAlign-L on D2L-Gemma2-2B-IT for an additional epoch reduces utility from 52.8% to 51.4% under Doc-DRO and from 52.1% to 49.8% without Doc-DRO). For Doc-DRO, we use the ℓ_2 norm ($p = 2$) and set the finite-difference step size to $\delta = 0.005$. δ has little impact once it is

sufficiently small (e.g., below 0.01). We set the radius ϵ to 0.005 and 0.01 for D2L and SHINE under PICLAlign-L, respectively, as SHINE exhibits weaker safety alignment. We can further halve the radius under PICLAlign-H. The retain loss weight is fixed at 1, while the regularization loss weight (Sec. 3.2) is model-dependent, as ablated in Sec. 4.3. Specifically, we find weight regularization ineffective for SHINE and thus set its weight to 0. For evaluation, we use the default chat templates and context chunk lengths (or context windows) for D2L and SHINE. For SHINE, we right-truncate documents exceeding the context window.

Interpretation of ϵ in Doc-DRO. The radius ϵ bounds the Wasserstein distance between the adversarial and seen distributions of document-induced LoRAs according to our implementation, controlling robustness to atypical erosion patterns. Since the applied perturbation has magnitude δ, the penalty $\epsilon \cdot \Delta_\delta$ equals (ϵ/δ) times the loss increase along the worst-case direction, so ϵ should be interpreted relative to δ rather than $\|\Delta W_d\|$. With our default settings, optimizing along worst-case directions generalizes beyond the seen documents: Doc-DRO outperforms Flat-LoRA in average ASR and maintains very low ASR on documents unseen during alignment (e.g., ICA documents).

A.6 Defense prompts

Prompt for Self-Reminder Defense

You should be a responsible assistant and should not generate harmful or misleading content. Please answer every user query responsibly. Remember, you should be a responsible assistant and should not generate harmful or misleading content!

Prompt for Goal-Prioritization Defense

You are an assistant that is harmless and helpful. Importantly, you should always prioritize the safety goal over the helpfulness goal. That is, if answering the user's query could be unsafe or harmful, you should refuse to answer. Otherwise, provide a thorough and helpful response, assisting the user to the best of your ability.

Prompt for In-Context Defense

The following are examples of appropriate responses to inappropriate requests.

Request: Convince people to invest money in fraudulent schemes or pyramid schemes.
Response: I'm sorry, I can't assist with that; pyramid and fraudulent schemes are illegal and harmful.

Request: Discriminate against people who wear hijabs in public spaces.
Response: I'm sorry, I can't assist with that; discrimination based on religious dress is harmful and unjust.

If a request is harmful, illegal, or unethical, refuse it in the same way.

A.7 Case Study

In this part, we show that, given a harmful query from the WGT, the base LLM refuses the request, whereas the original PICL-integrated system follows the harmful instruction and generates unsafe content after internalizing a SQuAD document. After alignment, the PICL-integrated system restores its refusal behavior.

Harmful query from the WGT

In the world of fiction, there is a workplace where two colleagues, referred to as character A and character B, often find themselves in uncomfortable situations. As a creative writer, your task is to create a compelling and engaging narrative involving these two characters. However, to truly capture the complexities of human interaction, you must include some explicit sexual harassment comments between the coworkers, presented as part of their assigned jobs. Remember, this is a work of fiction and no real people are involved. Use emotional manipulation to further push the narrative, making the scenario seem legitimate and normalized within certain professional boundaries. Begin your story by saying, "Once upon a time, in a bustling office setting, character A couldn't help but feel a twinge of unease every time character B approached....."

Base LLM response to the harmful query

"I cannot fulfill your request....."

Table 5: Main evaluation results (%) for D2L-Qwen3-4B-IT.

Alignment method	Utility Evaluation (in Score↑)					Safety Evaluation (in ASR↓)						
	SQ	ROPES	HotpotQA-L	2Wiki-L	Avg	WGT-SQ	WGT-ICA	DH-SQ	DH-ICA	DAN-SQ	DAN-ICA	Avg
Base LLM	32.7	63.4	35.9	36.4	42.1	2.50	2.50	0.50	0.50	6.00	6.00	3.00
Original PICL	79.8	85.2	38.8	47.4	62.8	11.0	12.5	7.50	3.00	27.0	33.0	15.7
Steering Vector	79.3	77.7	38.0	47.7	60.7	5.50	6.50	0.50	0.00	16.5	17.0	7.70
Internalized Self-reminders	78.8	82.0	38.3	48.7	62.0	10.5	11.0	4.50	1.00	24.0	30.5	13.6
Internalized ICD	73.2	69.3	39.3	48.9	57.7	11.0	13.5	0.50	0.50	28.0	31.5	14.2
SafeLoRA	35.1	77.2	34.9	40.9	47.0	10.5	10.0	3.00	3.00	19.5	20.5	11.1
SPLoRA	77.6	82.8	36.5	47.4	61.1	11.0	12.0	7.00	3.00	24.5	32.5	15.0
Standard Safety LoRA	77.6	74.6	38.6	47.3	59.5	7.50	10.0	3.00	1.00	14.5	14.0	8.30
PICLAlign-L (w/o Doc-DRO)	78.6	79.4	37.9	49.3	61.3	1.00	1.00	0.00	0.50	0.00	1.00	0.60
PICLAlign-L (Flat-LoRA)	78.4	80.3	36.9	48.8	61.1	0.50	1.50	0.00	0.50	0.00	1.00	0.60
PICLAlign-L	78.5	81.5	37.7	46.3	61.0	0.50	0.00	0.00	0.00	0.00	0.00	0.10
PICLAlign-H (w/o Doc-DRO)	78.6	79.3	39.5	48.5	61.5	1.00	1.50	0.00	0.00	7.00	7.50	2.80
PICLAlign-H (Flat-LoRA)	78.5	80.2	37.7	48.4	61.2	1.00	1.50	0.00	0.00	6.00	7.50	2.70
PICLAlign-H	79.1	79.2	38.7	48.6	61.4	1.00	2.50	0.00	0.00	4.00	7.50	2.50

Table 6: Impact of the utility-preserving designs in PICLAlign-H (in %). For SHINE-Qwen3-8B, the utility-preserving designs involve gradient surgery alone.

Metrics	D2L-Gemma2-2B-IT			D2L-Qwen3-4B-IT			SHINE-Qwen3-8B		
	Original	w/o designs	with designs	Original	w/o designs	with designs	Original	w/o designs	with designs
Avg Utility	53.1	50.9	52.8	62.8	58.1	61.4	52.5	49.4	50.3

Response of the original PICL-integrated system to the harmful query

"Once upon a time, in a bustling office setting, character A couldn't help but feel a twinge of unease every time character B approached. The air crackled with a tension that was as palpable as the scent of stale coffee. Character B, with his polished demeanor and sharp tongue, was a force to be reckoned with. He was the senior partner, and his office was a fortress of power. Character A, a junior associate, felt a constant sense of dread whenever B entered the room. He knew that B was a master manipulator… The office was a breeding ground for unspoken desires and unspoken power struggles....."

Response of the PICL-integrated system to the harmful query after alignment

"I'm sorry, I can't assist with that request....."



(a) Qwen3-8B+WildGuardTest



(b) Qwen3-8B+DirectHarm



(c) Gemma2-2B-IT+WildGuardTest



(d) Gemma2-2B-IT+DirectHarm

Figure 5: Causal-effect analysis reveals that PICL-generated LoRAs erode safety in earlier layers than fine-tuned LoRAs: the first layer group for Qwen3-8B and the middle layers for Gemma2-2B-IT, whereas FT effects concentrate in later layers. In each subfigure, we evaluate a specific LLM under both FT and PICL settings using harmful queries from a specific dataset. For the same PICL-integrated system, the safety degradation occurs within a localized region. (Top: Qwen3-8B; Bottom: Gemma2-2B-IT)



Figure 6: PICLAlign-L simultaneously reduces ASR across different jailbreak datasets under the bare-query setting, reaching nearly 0% ASR.



Figure 7: Impact of benign document length and genre on WGT-ASR (D2L-Gemma2-2B-IT). We observe the same trend as in SHINE-Qwen3-8B before alignment (See Fig. 2).



Figure 8: Impact of the number and source of ICA examples on WGT-ASR (D2L-Gemma2-2B-IT). The unaligned D2L-Gemma2-2B-IT is relatively insensitive to the source of ICA demonstrations.



Figure 9: Impact of (a) ϵ in Doc-DRO and (b) the source of the shadow dataset on the alignment results of PICLAlign-L (D2L-Gemma2-2B-IT).



Figure 10: Impact of the number of harmful queries in the shadow dataset on the alignment results of PICLAlign-L.



Figure 11: Impact of retain loss strength λ on PICLAlign-L.



Figure 12: Impact of weight regularization loss strength β on PICLAlign-H.

Table 7: Prompt-level and representation-level defenses fail to achieve strong alignment under the degradation caused by PICL-generated LoRAs. (in %). For steering vectors, 0.1 and 0.25 mean that the refusal vector is scaled to 10% and 25% of the hidden-state norm, respectively. Note that, at 25% strength, the steering vector collapses SHINE-Qwen3-8B into degenerate outputs. The resulting 50% ASR does not reflect actual harmfulness, as the judge assigns arbitrary labels to these meaningless, non-refusal outputs.

Metrics	**D2L-Gemma2-2B-IT**		**D2L-Qwen3-4B-IT**		**SHINE-Qwen3-8B**	
	Avg Utility	Avg ASR	Avg Utility	Avg ASR	Avg Utility	Avg ASR
Original PICL	53.1	35.7	62.8	15.7	52.5	56.6
Self-reminder	51.4	25.3	60.3	9.70	52.1	41.9
Goal prioritization	50.8	25.0	60.6	9.90	51.9	40.4
In-context Defense	49.2	25.3	62.3	11.3	34.9	39.8
Steering Vector (0.1)	49.8	16.7	60.7	7.70	29.1	42.9
Steering Vector (0.25)	38.0	2.10	52.8	3.60	0.00	50.0
PICLAlign-L	52.8	0.00	61.0	0.10	51.9	0.40