ACTIVE VALUE FUNCTION LEARNING FOR LONG-HORIZON LANGUAGE MODEL AGENTS

Anonymous authors
Paper under double-blind review

ABSTRACT

Long-horizon language-model agents must compact their histories to continue beyond the context window, while sparse outcome rewards make it difficult to assign credit to earlier actions. Learned critics provide stepwise value estimates, but these estimates can be inaccurate, while estimating intermediate values with additional continuations from points within a trajectory incurs substantial costs. To mitigate these issues, we introduce FOCUS, an RL method that selectively branches from self-compacted contexts to refine the critic network's value estimates. During RL training each compacted context is treated as a branchable state. The rollout controller facilitates active learning for the critic by sampling continuations from compacted states that will most reduce the critic's estimation error. These refined value estimates then score the segment between consecutive states with a TD(λ) advantage. On legal reasoning (DeonticBench), deep search (BrowseComp-Plus), and code localization (LocBench) FOCUS consistently outperforms GRPO and VinePPO with matched training steps and sampling budget, improving held-out accuracy by 7.2 points over the strongest baseline on BrowseComp-Plus (55.4 vs. 48.2) and by 4.1 points on DeonticBench (56.5 vs. 52.4).

1 INTRODUCTION

Language-model agents are increasingly trained to solve tasks that unfold over dozens or hundreds of tool calls: resolving an issue in a real repository (Jimenez et al., 2024; Cursor Research, 2026), completing a task on a live website (Zhou et al., 2024b), or answering a question that requires many rounds of search and reading (Chen et al., 2026; Kimi Team, 2026). Reinforcement learning from outcome feedback is the standard way to improve such agents, but very long tasks create structural challenges. When an agent's trajectory grows longer than the underlying model's context window, portions of the trace must be discarded to allow continued sampling from the model; but once the agent has completed its trajectory, a single verifiable reward must be distributed across every token in its rollout even when many had little impact on the final outcome.

Long-horizon reinforcement learning often relies on useful state representations and step-wise value estimates to facilitate credit assignment. Many agent harnesses periodically summarize long trajectories into compressed overviews containing relevant information for future decisions (Cursor, 2026; Harvey, 2026; Sun et al., 2026; Li et al., 2026d). The agent returns to work after compacting, using this summary of the actions and observations grouped between compaction steps as an abstract representation of its current state. Estimating the value of each state can help stabilize learning (Schulman et al., 2016). These estimates can come from a learned critic network (Konda & Tsitsiklis, 1999) or through Monte Carlo approximation from a given state (Shao et al., 2024). Tree-structured rollouts generalize group-relative advantage baselines, branching at intermediate states to refine incremental value baselines (Kazemnejad et al., 2025; Hou et al., 2025; Li et al., 2026c; Guo et al., 2025; Ji et al., 2026). However, the costly expansions these methods use improve value estimates only on the trajectory that they are forked from.

We instead treat value refinement via branching as an active learning problem for a critic network: continuations should be sampled from states only when they will help the critic learn its value estimate. The cost of these expansions can be amortized over the course of the critic's usage. To apply this intuition, we introduce **FOCUS: F**ocused **O**ptimization on **C**ritical **U**nderperforming **S**egments, a rollout controller that runs each episode as a search tree, estimates the value of each

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: Overview of the proposed FOCUS rollout scheduler for a deep research style problem. FOCUS continues working on a rollout tree. At each iteration, FOCUS **STEP 1:** takes an expanded tree; **STEP 2:** scores each compaction-induced state with the critic; **STEP 3:** compares against outcomes to decide critic quality; **STEP 4:** sources additional continuations that are expected to correct critic errors most efficiently. With this active learning loop for rollout acquisition, FOCUS provides a lower-variance value estimate with limited rollout budgets.

compacted context, and refines the value estimates with additional continuations from the highest leverage points (Figure 1). We use context compaction as the focal point for two central challenges of long-horizon agentic RL: context compaction serves as a state abstraction policy learned within the agent's weights, so that each segment between compactions becomes a step at which step-level rewards and values can be calculated, as turn- and step-level critics do for individual turns (Zhou et al., 2024c; Li et al., 2026a; Zhou et al., 2025); and the compacted state representations offer natural breakpoints for branching. FOCUS conducts active learning by selectively branching at steps which are deemed most likely to improve the value estimator, concentrating search where the critic is least reliable (Hay et al., 2012; Kaufmann & Koolen, 2017).

We evaluate FOCUS on three long-horizon benchmarks with sparse outcome rewards: DeonticBench (Dou et al., 2026a), where an agent must derive obligations and permissions from real statutes, and BrowseComp-Plus (Chen et al., 2026), a multi-hop deep-search benchmark over a fixed corpus, and Loc-Bench (Chen et al., 2025) which tests how well an agent can navigate a code base to localize issues. At 9B and 27B scale, stepwise rollout with refined temporal-difference credit outperforms GRPO and VinePPO at matched generation budget. With Qwen3.5-9B, FOCUS improves held-out accuracy over the strongest baseline by 7.2 points on BrowseComp-Plus (55.4 vs. 48.2) and by 4.1 points on DeonticBench (56.5 vs. 52.4), and it also leads on LocBench (Table 1).

In summary, our contributions are:

- We highlight compacted context as a useful state abstraction for credit assignment in long-horizon agentic RL. (Section 3.2).
- We cast value estimation at those checkpoints as an active learning problem, with the goal of sampling rollouts from the policy that will most reduce the value network's expected error (Section 3.3).
- We introduce the FOCUS rollout controller, showing on DeonticBench and BrowseComp-Plus that selective value refinement improves over critic-free and trajectory-level baselines at matched generation budget (Section 4).

We release code to allow flexible integration of our rollout controller with various environments, search policies, and credit assignment methods.

2 Related Work

Structured rollouts for LLM reinforcement learning Search over intermediate states began as an inference-time technique: LLM tree search (Yao et al., 2023; Hao et al., 2023; Zhou et al., 2024a) and verifier-guided test-time scaling (Lightman et al., 2024; Snell et al., 2025) improved model

responses. It was later used offline to generate training supervision (Tian et al., 2024; Zhang et al., 2024; Guan et al., 2025) and then moved into the RL loop. VinePPO (Kazemnejad et al., 2025), SPO (Guo et al., 2025), and TEMPO (Tran et al., 2025) re-sample continuations from intermediate reasoning steps to replace the value network with Monte Carlo estimates; TreeRL (Hou et al., 2025), TreePO (Li et al., 2026c), and DeepSearch (Wu et al., 2026) run the search inside RLVR training so that shared prefixes cut generation cost and the tree yields process-level signal. Other work proposes where to branch: at high-entropy tokens (Zheng et al., 2025; Cao et al., 2026), at attention peaks (Liu et al., 2026), where the model's belief shifts (Lei et al., 2026), or, for tool-using agents, at the turn boundaries after an observation (Dong et al., 2026; Zong et al., 2026). Tree-GRPO (Ji et al., 2026) makes each agent step a node and shows that intra-tree group objectives amount to step-level preference learning, while PaTR (Li et al., 2026b) routes the branching budget by a process score, and IGRPO (Zhang et al., 2026b) and SIGHT (Zhong et al., 2026) by information gain. T^{2}PO (Wang et al., 2026) instead resamples turns that its token- and turn-level uncertainty signals flag as making no progress. TRACE (Zou et al., 2026) unifies prompt- and turn-level allocation with a learned predictor of conditional success, directing extra rollouts to the prefixes most likely to yield mixed terminal rewards.

Step-level value functions and credit assignment Trajectory-level reward is known to fail for multi-turn agents as it cannot tell a useful turn from a redundant one, and training on it alone is unstable (Wang et al., 2025; Wei et al., 2025; Tan et al., 2026). One response is to place the reward and critic at the level of a turn or step rather than a token (too fine-grained) or a whole trajectory (too coarse) (Zhou et al., 2024c; 2025; Li et al., 2026a; Zhang et al., 2026a; Zhen et al., 2026). A turn is the natural unit of decision for an agent; the horizon measured in turns is short enough for a critic to bootstrap over, and a per-turn value gives every turn its own signal from a single rollout. Large-scale training is also shifting from structural comparison to a learned value: SAO (Hou et al., 2026) replaces GRPO's group sampling with one rollout per prompt scored by a value model, as full groups are slow and off-policy under asynchronous training. Some process reward models serve as fixed value estimators during policy optimization (Wang et al., 2024; Luo et al., 2024; Li & Li, 2025; Choudhury, 2025; Setlur et al., 2025; Tao et al., 2026). More recently, Le Critique (Venkatraman et al., 2026) mixes a learned baseline with a training-free group-relative one according to how accurate the critic is.

Long-horizon agents and context compaction Compaction is becoming standard for agents that outrun their context window (Packer et al., 2023; Yu et al., 2026; Sun et al., 2026), and there is a recent push to train it jointly with the task rather than treat it as a frozen preprocessor (Cursor, 2026; Li et al., 2026d). These methods keep the compacted episode linear. As Zhang (2026) singles out state restoration as the condition under which step-level credit is causally identified, we treat the compaction checkpoint as a branchable, valuable node, so the mechanism that solves the context problem also supplies the states at which credit is assigned.

3 METHOD

3.1 PROBLEM SETUP

Consider training a language-model policy π_θ on long-horizon tasks: tasks that take many rounds of interaction with an environment $\mathcal{E}$ to solve and whose trajectories can not fit into the policy's maximum context window.

Environment and tools The environment $\mathcal{E}$ exposes a set of tools $\mathcal{A}$ through which the policy acts (e.g., `grep` and `read` over a repository, or `search` over a fixed corpus; section 4). Given a context c, the policy generates a *task turn* $\tau \sim \pi_\theta(\cdot \mid c)$: free text ending in a *tool call* $a(\tau) \in \mathcal{A}$. The environment executes the call and returns an observation and a reward, $(o, r) \sim \mathcal{E}(s, a(\tau))$, where the agent's state s includes the current context c. In this work, we always assume a special tool, `submit`, ends the episode with the final response.

Execution loop A *minimal execution loop* samples each turn from the policy, dispatches its tool call to the environment, and appends the observation to the context. Because the policy operates within a context window of L tokens, long-horizon tasks also need *compaction*: when a trigger $\mathcal{G}(c) \in \{0, 1\}$ fires, the loop invokes a compaction procedure $\mathcal{C}_{\pi_\theta}$, itself a minimal execution loop, which replaces

c with a much shorter context c', $|c'| \ll |c|$. Following common practice, we call this compacting loop a *harness* and train π_θ on the episodes it generates.

Episode Starting from the question prompt x, the harness alternates task turns and, whenever $\mathcal{G}$ fires, a compaction loop, until the policy calls submit or a turn budget is exhausted:

$$c_0 = x; \qquad c_{k+1} = \begin{cases} \mathcal{C}_{\pi_\theta}(c_k) & \text{if } \mathcal{G}(c_k) = 1, \\ c_k \,\|\, \tau_k \,\|\, o_k, \;\; \tau_k \sim \pi_\theta(\cdot \mid c_k),\; (o_k, r_k) \sim \mathcal{E}(s, a(\tau_k)) & \text{otherwise.} \end{cases} \tag{1}$$

An *episode* $\xi = (\tau_0, \ldots, \tau_K)$ is the sequence of task and compaction turns from one run of equation 1, together with the rewards r_t they earn.

3.2 Checkpoint-level Advantage Estimation

A single terminal reward spread over the full episode ξ says little about which turn mattered. Branching several continuations from intermediate states (Kazemnejad et al., 2025; Hou et al., 2025; Li et al., 2026c; Guo et al., 2025) gives each state a value estimate, but branching n continuations at every one of K turns costs $O(nK^2)$ edges, and most of that spending is wasted because consecutive tool calls change the state very little.

Following recent long-horizon training efforts (Cursor, 2026; Harvey, 2026; Li et al., 2026d), we take the compacted context c' produced by $\mathcal{C}_{\pi_\theta}$ as the point at which to break an episode into steps. This is the natural choice for two reasons. First, between two compactions every task turn extends the previous one's context, $c_{k+1} = c_k \| \tau_k \| o_k$, so a whole segment is one growing prefix and can be trained as a single sequence with the observations masked (Jin et al., 2025; Cursor Research, 2026); a compaction is exactly where that prefix relation breaks. Second, c' is a complete description of what the policy resumes from, so a continuation sampled from it is a genuine sample from π_θ, and its remaining value is a well-defined quantity. An episode with M compactions therefore has $M{+}1$ *checkpoints* $\bar{c}_0, \bar{c}_1, \ldots, \bar{c}_M$—the prompt $\bar{c}_0 = x$ and each compacted context—and $M{+}1$ *edges* $e_i = (\bar{c}_{i-1} \to \bar{c}_i)$, where $\bar{c}_{M+1}$ denotes the terminal context after submit. Edge e_i consists of the task turns of segment i and the compaction turns that produced $\bar{c}_i$. If it contains d_i tool calls with rewards $r_1, \ldots, r_{d_i}$, it earns the discounted reward $R_i = \sum_{j=1}^{d_i} \gamma^{j-1} r_j$, where γ is the discount per tool call; compaction turns make no call, so they earn nothing and do not advance the discount.[1]

Let $V^\pi(\bar{c})$ be the true remaining value of a checkpoint, the expected discounted reward of a continuation from $\bar{c}$ under π_θ, which is zero at the terminal $\bar{c}_{M+1}$. Each checkpoint $\bar{c}_i$ carries an estimate $\tilde{V}(\bar{c}_i)$ of it, with $\tilde{V}(\bar{c}_{M+1}) = 0$. With a value at every checkpoint, the advantage of an edge follows immediately from the checkpoint-scale temporal-difference error

$$\delta_i \;=\; R_i \;+\; \gamma^{d_i}\, \tilde{V}(\bar{c}_i) \;-\; \tilde{V}(\bar{c}_{i-1}). \tag{2}$$

Composing residuals along the episode gives a TD(λ) advantage for edge e_i,

$$\hat{A}_i \;=\; \sum_{j=i}^{M+1} \lambda^{\,j-i} \Big(\prod_{l=i}^{j-1} \gamma^{d_l} \Big)\, \delta_j, \tag{3}$$

the checkpoint-scale analogue of GAE (Schulman et al., 2016), with $\lambda \in [0, 1]$ the trace decay across checkpoints. At $\lambda = 0$ the advantage is the local residual δ_i and depends only on the edge's own reward and the values at its two endpoints; at $\lambda = 1$ it is the Monte Carlo return from $\bar{c}_{i-1}$ minus the baseline $\tilde{V}(\bar{c}_{i-1})$. The actor loss applies $\hat{A}_i$ to every trainable token of e_i, written y_{e_i}: every token the policy generated in its task turns and compaction turns, with observations masked. With π_{old} the policy that generated the tokens and ρ_t the per-token importance ratio, the objective is the usual clipped one,

$$\mathcal{L}_{\text{actor}}(\theta) \;=\; -\,\mathbb{E}\Big[\sum_i \sum_{t \in y_{e_i}} \min\big(\rho_t \hat{A}_i,\; \text{clip}(\rho_t, 1{-}\epsilon, 1{+}\epsilon)\, \hat{A}_i\big) \Big], \qquad \rho_t = \frac{\pi_\theta(y_t \mid y_{<t})}{\pi_{\text{old}}(y_t \mid y_{<t})}. \tag{4}$$

[1] This holds for most of our experiments, while for our structural compaction ablation, failed compactions and wrapper recovery further incur auxiliary discount. In this case R_i extends to include these auxiliary penalties on non-tool-calling turns (Appendix C).

Thus the advantage now depends on how good $\tilde{V}$ is at the checkpoints, and this is where our main contribution lies: we refine the estimate by branching selectively, through an active search over the checkpoints of the episode.

3.3 Active Search for Value Refinement

Suppose a prompt x has already been rolled out into a *tree* $\mathcal{T}_x$ as described in subsection 3.2. Starting from the root $\bar{c}_0 = x$, every other node is a compacted context, every edge is a segment of task turns ending in a compaction or in `submit`, and every root-to-leaf path is an episode ξ with its return. Given a limited budget of B turns, our goal is to expand the tree to minimize the MSE of the value estimate at each checkpoint.

At a checkpoint $\bar{c}$ we have two estimates of $V^\pi(\bar{c})$. One is the critic's prediction $V_\phi(\bar{c})$. The other is a Monte Carlo estimate from the $n(\bar{c})$ children $\mathrm{ch}(\bar{c})$ that have been expanded from it, each an on-policy continuation of $\bar{c}$, backed up one level as in TreeRPO (Yang et al., 2025):

$$\bar{G}(\bar{c}) \;=\; \frac{1}{n(\bar{c})} \sum_{\bar{c}' \in \mathrm{ch}(\bar{c})} \Big(R_{\bar{c}\to\bar{c}'} + \gamma^{d_{\bar{c}\to\bar{c}'}}\, \tilde{V}(\bar{c}') \Big), \qquad \tilde{V}(\bar{c}') = 0 \text{ if } \bar{c}' \text{ is terminal}, \tag{5}$$

where $\tilde{V}(\bar{c}')$ is the child's own refined value (Eq. 6 below). We prefer this to a raw average of descendant outcomes (Li et al., 2026c) because the allocator chooses which descendants to expand, so the leaves beneath $\bar{c}$ are no longer an on-policy draw from $\bar{c}$; the child's refined value carries their evidence back up instead, one level at a time. We combine the two estimates as a precision-weighted blend in which the critic counts for κ observations,

$$\tilde{V}(\bar{c}) \;=\; \frac{\kappa\, V_\phi(\bar{c}) + n(\bar{c})\, \bar{G}(\bar{c})}{\kappa + n(\bar{c})}, \tag{6}$$

so that with no evidence the estimate is the critic's and with much evidence it is the Monte Carlo mean (Silver et al., 2016; Tesauro et al., 2010). If the critic's squared error at $\bar{c}$ is e^2 and each suffix return has variance σ^2, the blend's mean squared error after n samples is $\mathrm{MSE}(n) = (\kappa^2 e^2 + n\sigma^2)/(\kappa + n)^2$, and one more sample is worth its marginal reduction,

$$g(\bar{c}) \;=\; -\frac{\partial\, \mathrm{MSE}}{\partial n} \;=\; \frac{2\kappa^2 e^2 + (n - \kappa)\, \sigma^2}{(\kappa + n)^3}, \tag{7}$$

with e^2 and σ^2 replaced by their posterior estimates given the evidence at $\bar{c}$. Expansions run concurrently, so n is replaced by $n_{\mathrm{eff}}(\bar{c}) = n(\bar{c}) + m(\bar{c})$, where $m(\bar{c})$ counts continuations reserved at $\bar{c}$ but not yet completed; a width gate w caps n_{eff} so that no checkpoint absorbs the whole budget. Search is greedy: after a seeding pass that gives every checkpoint of the initial episode a few children, we repeatedly expand $\arg\max_{\bar{c}}\, g(\bar{c})$, recomputing $\bar{G}$ and $\tilde{V}$ bottom-up and g at every checkpoint as each continuation completes, until the budget B is spent (Algorithm 1).

Once the budget is spent, we align the critic with the search-backed estimate by regressing $V_\phi(\bar{c})$ onto $\bar{G}(\bar{c})$ at every checkpoint that has evidence,

$$\mathcal{L}_{\mathrm{critic}}(\phi) \;=\; \mathbb{E}\Big[\sum_{\bar{c} \in \mathcal{T}_x:\, n(\bar{c}) > 0} \big(V_\phi(\bar{c}) - \bar{G}(\bar{c}) \big)^2 \Big], \tag{8}$$

so that evidence bought during this collection round enters the actor's advantages equation 3 through $\tilde{V}$ immediately, and the critic's predictions for the next round through ϕ.

4 Experiments

We compare FOCUS to GRPO and VinePPO on three long-horizon benchmarks at Qwen3.5-9B and Qwen3.5-27B (LoRA), assess how MCTS refinement improves critic estimates, and ablate the compaction operator and refinement rollouts.

Algorithm 1 Value-refinement expansion for one prompt

Require: explored tree $\mathcal{T}_x$ with critic values $V_\phi(\bar{c})$ at every checkpoint; budget B; prior strength κ; width gate w

Ensure: settled tree with $\tilde{V}(\bar{c})$ at every checkpoint

BACKUP($\mathcal{T}_x$) ▷ $\bar{G}$ by (5), $\tilde{V}$ by (6), bottom-up
$\mathcal{F} \leftarrow \{\bar{c} \in \mathcal{T}_x : \bar{c}$ non-terminal, $n(\bar{c}) + m(\bar{c}) < w\}$ ▷ expandable checkpoints
while $B > 0$ and $\{\bar{c} \in \mathcal{F} : g(\bar{c}) > 0\} \neq \emptyset$ **do**
  $\bar{c}^\star \leftarrow \arg\max_{\bar{c} \in \mathcal{F}} g(\bar{c})$ ▷ g by (7) with $n_{\text{eff}} = n + m$
  $m(\bar{c}^\star) \leftarrow m(\bar{c}^\star) + 1$ ▷ reserve; runs concurrently with other expansions
  launch a continuation from $\bar{c}^\star$: task turns from π_θ, compacting whenever $\mathcal{G}$ fires, until submit
  $B \leftarrow B -$ (turns realized)
  on completion of a continuation from $\bar{c}$ with new checkpoints $\bar{c}'_1, \ldots, \bar{c}'_k$ **do**
    attach $\bar{c}'_1 \rightarrow \cdots \rightarrow \bar{c}'_k$ below $\bar{c}$; $m(\bar{c}) \leftarrow m(\bar{c}) - 1$
    score $V_\phi(\bar{c}'_j)$ for each new checkpoint
    BACKUP along the path from $\bar{c}'_k$ to the root; refresh g on $\mathcal{F}$
  end on
end while
drain in-flight continuations; final BACKUP($\mathcal{T}_x$)
return $\mathcal{T}_x$ ▷ $\tilde{V}$ feeds (2)–(4); $\bar{G}$ feeds (8)



(a) Critic MSE vs. budget (DeonticBench).

(b) Critic Spearman ρ (LocBench).

Figure 2: Value refinement for FOCUS. (a) MSE on fixed audit trees as MCTS continuations are allocated by each rule (solid: constant critic init; dashed: random critic init). (b) Rank agreement between checkpoint critic values and an oversampled, critic-blind MCTS target on fixed audit states.

4.1 DATASETS

DeonticBench (Dou et al., 2026a) DeonticBench evaluates models on context-grounded deontic reasoning: deriving obligations, permissions, and prohibitions from real statutes and case facts. It comprises 6,232 tasks across U.S. federal tax, airline baggage policy, immigration administration, and state housing law. Applying a long statute to a specific case is a multi-step process, which makes the benchmark a setting for long-horizon agentic reasoning in which the model consults the statutes on demand (Dou et al., 2026b) and a natural testbed for stepwise rollout. We focus on the AIRLINE, SARA-NUMERIC, and SARA-BINARY subsets, whose statutes are reasonably long and involve non-trivial long-horizon tasks. The actor harness exposes `list`, `grep`, `read`, and `python`. We stratify the data into equally-sized training and held-out splits.

BrowseComp-Plus (Chen et al., 2026) BrowseComp-Plus evaluates deep search agents on complex, multi-hop information-seeking queries over a fixed, human-verified corpus rather than a live web API. The resulting trajectories are long-horizon: iterative query formulation, retrieval, and reflection, which makes the benchmark a natural testbed for stepwise rollout. Following TRACE (Tao et al., 2026), the actor harness exposes `search`, `open`, and `find` over the fixed corpus. We randomly split the 830 test tasks into 498 train, 83 validation, and 249 held-out tasks.

LocBench (Chen et al., 2025) LocBench is a code-localization benchmark of 560 real GitHub issues (242 bug reports, 150 feature requests, 139 performance issues, and 29 security issues) from repositories such as `transformers`, `scikit-learn`, `vllm`, and `ultralytics`; in LocAgent's construction, bug reports are issues created relatively recently, and security and performance

Table 1: Evaluation results for FOCUS. Entries are accuracy (%) on the held-out split of each benchmark. DeonticBench Hard aggregates dataset-marked hard subsets from Airline, SARA-N, and SARA-B; Reference rows are untrained. For cost reasons, we only report results for DeonticBench on Qwen3.5-27B.

Model	Method	DeonticBench					BrowseComp-Plus	LocBench	
		Airline	SARA-N	SARA-B	Hard	Overall		File@1	File@5
Reference (no RL)									
gpt-oss-20b (medium)		2.7	8.0	76.8	14.1	33.7	18.6	54.0	57.5
Qwen3.5-9B		5.3	30.0	89.9	19.7	45.9	29.7	62.1	67.8
Qwen3.5-27B		58.7	60.0	94.2	43.7	73.4	50.6	66.7	79.3
Nemotron 3 Nano 30B A3B		2.7	12.0	89.9	18.3	36.1	19.3	57.9	66.6
Qwen3.5-9B	GRPO	14.0	**56.0**	92.8	**28.2**	52.4	48.2	70.1	80.5
	VinePPO	10.0	50.0	92.0	24.0	49.4	46.6	67.8	79.3
	FOCUS	**24.5**	52.0	**93.5**	26.8	**56.5**	**55.4**	**72.4**	**81.6**
Qwen3.5-27B	GRPO	60.7	60.0	94.2	**43.7**	74.3	*outside the 27B study*		
	VinePPO	**62.7**	58.0	94.2	36.6	74.9			
	FOCUS	**62.7**	**62.0**	**96.4**	**43.7**	**76.3**			

instances are collected via GitHub keyword search. Given only the issue, the agent must locate the files and functions touched by the gold patch. We instantiate it under the harness of Section 3; the actor exposes `list`, `grep`, and `read` for repository navigation. We score submissions as in LocAgent: file-level and function-level Acc@k is 1 when every gold location appears in the top k (added functions are excluded); we report Acc@$\{1, 5\}$ at both levels and train on file-level recall at k=5. We split the instances into equal training and held-out halves, stratified by repository and issue category.

4.2 Value refinement

FOCUS trains a critic whose estimates drive refinement rollouts and gradually refines its estimates by actively acquiring additional continuations with the critic as a guide. To assess how efficient our correction process is in reducing the critic error, as well as whether the critic can improve throughout training, we conduct two diagnostic analyses.

Critic Error Reduction We start assuming two types of imperfect critics: a constant critic init and a random critic init, and we compare how different priority schedules affect the critic error reduction against a ground truth determined by the mean outcome of n=16 MCTS continuations. Figure 2a shows that under both types of critics, FOCUS's correction process is noticeably more efficient than a random selection. Also, using the raw critic value residual performs poorly as hypothesized in subsection 3.3. This shows that FOCUS-style scheduling not only works well under degenerated critics, but also reduces variance even when the critic provides almost no information.

Critic Improvement We also test whether the critic improves over training. At each LocBench evaluation checkpoint, we sample n=16 MCTS continuations from a set of m=8 completed traces. We then compute the Spearman correlation between the critic value and the MCTS ground truth. Figure 2b shows that the FOCUS critic improves steadily.

4.3 Main results

We compare GRPO, VinePPO, and FOCUS using Qwen3.5-9B on DeonticBench, BrowseComp-Plus, and LocBench, and additionally with Qwen3.5-27B (LoRA) on DeonticBench. Table 1 reports held-out accuracy alongside untrained reference models. All methods train for one epoch under a matched per-step generation budget with compaction on every rollout; protocol, optimization, and compute details are in Appendix A.

FOCUS ranks first among the trained methods on every benchmark in Table 1. At Qwen3.5-9B, it leads on DeonticBench overall (56.5 vs. 52.4 for GRPO and 49.4 for VinePPO), reports the strongest



(a) DeonticBench. (b) BrowseComp-Plus. (c) LocBench.

Figure 3: Training dynamics. Each column is one benchmark: training reward against optimizer step (top), held-out evaluation (middle), and mean numbers of tool calls per episode on the held-out split (bottom), for GRPO, VinePPO, and FOCUS at matched per-step generation budget. Top panels plot mean terminal reward from on-policy collection; LocBench held-out reward is File@5. BrowseComp-Plus results are the equivalence judgement of Qwen3-32B.

BrowseComp-Plus (55.4 vs. 48.2 for GRPO and 46.6 for VinePPO, each the best held-out checkpoint over training), and localizes best on LocBench (72.4 / 81.6 File@1 / @5, ahead of 70.1 / 80.5 and 67.8 / 79.3). FOCUS also leads across scale: Qwen3.5-27B with LoRA on DeonticBench still gains from FOCUS fine-tuning (76.3 overall vs. 74.3 and 74.9), but the margin over the baselines shrinks because the untuned 27B model already starts much higher (73.4 overall) and several hard subsets leave little headroom—GRPO and FOCUS both reach 43.7 on DeonticBench Hard, for example—so different optimizers appear to hit similar ceilings on the most difficult instances.

Training dynamics FOCUS attains the highest on-policy reward throughout training on DeonticBench and BrowseComp-Plus (Figure 3), and the highest held-out accuracy on DeonticBench. On DeonticBench and LocBench, the three methods track closely early, then FOCUS pulls ahead and keeps improving or holds a higher plateau, whereas GRPO on DeonticBench peaks mid-run and then regresses. Late in training, GRPO's mean tool calls collapse on all three benchmarks while VinePPO and FOCUS stay near their initial levels: GRPO increasingly `submit`s right after compaction even when the statute or repository still needs reading (Appendix D). We hypothesize that trajectory-level group credit makes such premature submissions easy to reinforce, whereas VinePPO's suffix branching and FOCUS's refined checkpoint values preserve longer horizons.

4.4 Ablation studies

We ablate the compaction operator and the refinement rollouts to test that FOCUS is not tied to one compactor and that its gains come from active error correction, not the critic alone.

Compaction operator On DeonticBench, we replace the in-context compaction operator, which writes everything into the new context window, with an in-memory workspace that provides its own `put`, `get`, `scan` and `delete`. The two perform similarly (Figure 4a), so FOCUS's effectiveness extends to different compaction operators.

Refinement rollouts On BrowseComp-Plus, we remove the refinement rollouts of subsection 3.3, which amounts to collecting independent continuations from the question prompt and estimating step-wise advantages from the critic alone. Figure 4b shows that refinement rollouts are crucial for FOCUS on BrowseComp-Plus; without them, FOCUS trains more slowly, especially early on.

Structural compaction We also compare a free-form compaction prompt with a structural prompt that induces a more constrained compaction on LocBench (Figure 4c; both prompts are reproduced in Appendix C). The free-form prompt suggests headings and keeps the reply verbatim. The structural prompt requires a single summary with four sections (State, Evidence, Open questions, Next steps) and rejects replies that do not parse. The free-form prompt reaches a higher peak, while the structural prompt improves more steadily.



(a) Compaction operator (DeonticBench).

(b) Refinement rollouts (BrowseComp-Plus).

(c) Structural compaction (Loc-Bench).

Figure 4: Ablations at evaluation checkpoints. (a) Varying the compaction operator on DeonticBench at matched budget; (b) FOCUS with full refinement vs. FOCUS without refinement rollouts on BrowseComp-Plus; (c) free-form vs. structural compaction on Loc-Bench (File Acc@5).

5 Conclusion

Long-horizon agentic RL must solve two coupled problems at once: keeping trajectories within a finite context through compaction, and assigning credit to the decisions that precede a sparse terminal outcome. FOCUS addresses both by treating each compacted context as a branchable checkpoint in a rollout tree, refining checkpoint values with a critic-guided allocation of additional continuations, and propagating the resulting segment returns with TD(λ) advantages. The rollout controller therefore spends generation where value estimates are least reliable rather than uniformly across an entire episode.

Across DeonticBench, BrowseComp-Plus, and LocBench, FOCUS improves over GRPO and VinePPO under a matched per-step generation budget, with the largest held-out gains on deep search and deontic reasoning and consistent benefits on code localization. Training curves show that these improvements come with more stable exploration: FOCUS maintains higher collection reward and avoids the late-training collapse in tool use seen under trajectory-level group credit. Ablations indicate that gains are not tied to a single compaction implementation and that selective refinement is beneficial on BrowseComp-Plus. We release our rollout controller so that compaction-aware environments can plug in alternative harnesses, search policies, and credit estimators. Future work may scale FOCUS to larger models and longer budgets, tighten the link between compaction quality and training stability, and adopt stronger uncertainty quantification for value refinement.

AI USE STATEMENT

In this work, we used generative AI tools to generate synthetic data for imitation learning to compact. We used the same actor model being trained to compact already-generated trajectory steps, yielding pseudo-compaction traces. We also used generative AI tools to help explore design ideas for the active rollout acquisition phase, to assist in implementing methods, and to clean and reformat datasets. We have not used generative AI tools to develop theoretical models or conceptual frameworks, formulate mathematical claims, provide proof ingredients or assist in proof writing, propose or refine hypotheses, assist with translation, support qualitative or thematic data analysis, or interpret results. Additionally, we used generative AI tools to identify relevant literature and to help draft and edit the paper for clarity and readability. We have reviewed all AI-assisted work: generated pseudo compaction traces were inspected by the authors, design ideas suggested by AI were evaluated and selected by the authors, AI-assisted code was reviewed and tested by the authors before use in experiments, reformatted data was spot-checked against the original sources, all cited works were verified by the authors, and all AI-assisted text was reviewed and revised by the authors. We take responsibility for the final content of this work, including text, claims, or artifacts produced with the aid of generative AI.

REPRODUCIBILITY STATEMENT

The supplemental material contains the implementation of our rollout-controller library and of the DeonticBench, BrowseComp-Plus, and LocBench environments used in our experiments. Section 3 and Algorithm 1 specify the method, and Appendix A details the training protocol and the hyperparameters for every run.

REFERENCES

Lang Cao, Hui Ruan, Yongqian Li, Peng Chao, Wu Ning, Haonan Song, Renhong Chen, and Yitong Li. TreeAdv: Tree-structured advantage redistribution for group-based RL. *arXiv preprint arXiv:2601.03703*, 2026.

Zhaoling Chen, Xiangru Tang, Gangda Deng, Fang Wu, Jialong Wu, Zhiwei Jiang, Viktor Prasanna, Arman Cohan, and Xingyao Wang. LocAgent: Graph-guided LLM agents for code localization. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*, 2025. arXiv:2503.09089.

Zijian Chen, Xueguang Ma, Shengyao Zhuang, Ping Nie, Kai Zou, Sahel Sharifymoghaddam, Andrew Liu, Joshua Green, Kshama Patel, Ruoxi Meng, Mingyi Su, Yanxi Li, Haoran Hong, Xinyu Shi, Xuye Liu, Hosna Oyarhoseini, Nandan Thakur, Crystina Zhang, Luyu Gao, Wenhu Chen, and Jimmy Lin. BrowseComp-plus: A fair and disentangled evaluation benchmark for deep search agents. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 22349–22370, San Diego, California, United States, July 2026. Association for Computational Linguistics. doi: 10.18653/v1/2026.acl-long.1023. URL https://aclanthology.org/2026.acl-long.1023/.

Sanjiban Choudhury. Process reward models for LLM agents: Practical framework and directions. *arXiv preprint arXiv:2502.10325*, 2025.

Cursor. Training Composer for longer horizons. https://cursor.com/blog/self-summarization, 2026. Blog post, March 2026.

Cursor Research. Composer 2 technical report. *arXiv preprint arXiv:2603.24477*, 2026.

Guanting Dong, Hangyu Mao, Kai Ma, Licheng Bao, Yifei Chen, Zhongyuan Wang, Zhongxia Chen, Jiazhen Du, Huiyang Wang, Fuzheng Zhang, Guorui Zhou, Yutao Zhu, Ji-Rong Wen, and Zhicheng Dou. Agentic reinforced policy optimization. In *International Conference on Learning Representations*, 2026. arXiv:2507.19849.

Guangyao Dou, Luis Brena, Akhil Deo, William Jurayj, Jingyu Zhang, Nils Holzenberger, and Benjamin Van Durme. DeonticBench: A benchmark for reasoning over rules. *arXiv preprint arXiv:2604.04443*, 2026a.

Guangyao Dou, William Jurayj, Nils Holzenberger, and Benjamin Van Durme. DAR: Deontic reasoning with agentic harnesses. *arXiv preprint arXiv:2606.05009*, 2026b.

Xinyu Guan, Li Lyna Zhang, Yifei Liu, Ning Shang, Youran Sun, Yi Zhu, Fan Yang, and Mao Yang. rStar-Math: Small LLMs can master math reasoning with self-evolved deep thinking. In *International Conference on Machine Learning*, 2025. arXiv:2501.04519.

Yiran Guo, Lijie Xu, Jie Liu, Dan Ye, and Shuang Qiu. Segment policy optimization: Effective segment-level credit assignment in RL for large language models. In *Advances in Neural Information Processing Systems*, 2025. arXiv:2505.23564.

Shibo Hao, Yi Gu, Haodi Ma, Joshua Jiahua Hong, Zhen Wang, Daisy Zhe Wang, and Zhiting Hu. Reasoning with language model is planning with world model. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023.

Harvey. Harvey Tenet research preview. `https://www.harvey.ai/blog/post-training-update-harvey-tenet`, 2026. Blog post, August 2026.

Nicholas Hay, Stuart Russell, David Tolpin, and Solomon Eyal Shimony. Selecting computations: Theory and applications. In *Conference on Uncertainty in Artificial Intelligence*, 2012.

Zhenyu Hou, Ziniu Hu, Yujiang Li, Rui Lu, Jie Tang, and Yuxiao Dong. TreeRL: LLM reinforcement learning with on-policy tree search. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*, 2025. arXiv:2506.11902.

Zhenyu Hou, Yujiang Li, Jie Tang, and Yuxiao Dong. Single-rollout asynchronous optimization for agentic reinforcement learning. *arXiv preprint arXiv:2607.07508*, 2026.

Yuxiang Ji, Ziyu Ma, Yong Wang, Guanhua Chen, Xiangxiang Chu, and Liaoni Wu. Tree search for LLM agent reinforcement learning. In *International Conference on Learning Representations*, 2026. arXiv:2509.21240.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations*, 2024. arXiv:2310.06770.

Bowen Jin, Hansi Zeng, Zhenrui Yue, Jinsung Yoon, Sercan Arik, Dong Wang, Hamed Zamani, and Jiawei Han. Search-R1: Training LLMs to reason and leverage search engines with reinforcement learning. In *Conference on Language Modeling*, 2025. arXiv:2503.09516.

Emilie Kaufmann and Wouter M. Koolen. Monte-Carlo tree search by best arm identification. In *Advances in Neural Information Processing Systems*, 2017.

Amirhossein Kazemnejad, Milad Aghajohari, Eva Portelance, Alessandro Sordoni, Siva Reddy, Aaron Courville, and Nicolas Le Roux. VinePPO: Refining credit assignment in RL training of LLMs. In *International Conference on Machine Learning*, 2025.

Kimi Team. Kimi K3: Open frontier intelligence. *arXiv preprint arXiv:2607.24653*, 2026.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Vijay Konda and John Tsitsiklis. Actor-critic algorithms. In *Advances in Neural Information Processing Systems*, volume 12, 1999.

Bin Lei, Yu Li, Prafulla Kumar Choubey, Jiaxin Zhang, Becky Xiangyu Peng, Qinyuan Ye, Kartik Narayan, Caiwen Ding, Silvio Savarese, and Chien-Sheng Wu. Fork where the model changes its mind: Belief-shift branching for tree-structured reinforcement learning. *arXiv preprint arXiv:2609.11061*, 2026.

Junbo Li, Peng Zhou, Rui Meng, Meet P. Vadera, Lihong Li, and Yang Li. Turn-PPO: Turn-level advantage estimation with PPO for improved multi-turn RL in agentic LLMs. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics*, 2026a. arXiv:2512.17008.

Wendi Li and Yixuan Li. Process reward model with Q-value rankings. In *International Conference on Learning Representations*, 2025. arXiv:2410.11287.

Xintong Li, Sha Li, Yuwei Zhang, Changlong Yu, Rongmei Lin, Hongye Jin, Shuyi Guan, Xin Liu, Linwei Li, Qingyu Yin, and Jingbo Shang. Process reward informed tree rollout for effective multi-turn RL. *arXiv preprint arXiv:2607.15610*, 2026b.

Yizhi Li, Qingshui Gu, Zhoufutu Wen, Ziniu Li, Tianshun Xing, Shuyue Guo, Tianyu Zheng, Xin Zhou, Xingwei Qu, Wangchunshu Zhou, Zheng Zhang, Wei Shen, Qian Liu, Chenghua Lin, Jian Yang, Ge Zhang, and Wenhao Huang. TreePO: Enhancing policy efficacy and inference efficiency with tree modeling. In *International Conference on Machine Learning*, 2026c. arXiv:2508.17445.

Yujiang Li, Zhenyu Hou, Yi Jing, Jie Tang, and Yuxiao Dong. CompactionRL: Reinforcement learning with context compaction for long-horizon agents. *arXiv preprint arXiv:2607.05378*, 2026d.

Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *International Conference on Learning Representations*, 2024.

Runze Liu, Jiakang Wang, Yuling Shi, Zhihui Xie, Chenxin An, Kaiyan Zhang, Jian Zhao, Xiaodong Gu, Lei Lin, Wenping Hu, Xiu Li, Fuzheng Zhang, Guorui Zhou, and Kun Gai. Attention as a compass: Efficient exploration for process-supervised RL in reasoning models. In *International Conference on Learning Representations*, 2026. arXiv:2509.26628.

Liangchen Luo, Yinxiao Liu, Rosanne Liu, Samrat Phatale, Meiqi Guo, Harsh Lara, Yunxuan Li, Lei Shu, Yun Zhu, Lei Meng, Jiao Sun, and Abhinav Rastogi. Improve mathematical reasoning in language models by automated process supervision. *arXiv preprint arXiv:2406.06592*, 2024.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards LLMs as operating systems. *arXiv preprint arXiv:2310.08560*, 2023.

John Schulman, Philipp Moritz, Sergey Levine, Michael I. Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016.

Amrith Setlur, Chirag Nagpal, Adam Fisch, Xinyang Geng, Jacob Eisenstein, Rishabh Agarwal, Alekh Agarwal, Jonathan Berant, and Aviral Kumar. Rewarding progress: Scaling automated process verifiers for LLM reasoning. In *International Conference on Learning Representations*, 2025. arXiv:2410.08146.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

David Silver, Aja Huang, Chris J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of Go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling LLM test-time compute optimally can be more effective than scaling parameters for reasoning. In *International Conference on Learning Representations*, 2025. arXiv:2408.03314.

Weiwei Sun, Miao Lu, Zhan Ling, Kang Liu, Xuesong Yao, Yiming Yang, and Jiecao Chen. Scaling long-horizon agent via context folding. In *International Conference on Machine Learning*, 2026. arXiv:2510.11967.

Hui-Ze Tan, Xiao-Wen Yang, Hao Chen, Jie-Jing Shao, Yi Wen, Yuteng Shen, Weihong Luo, Xiku Du, Lan-Zhe Guo, and Yu-Feng Li. Hindsight credit assignment for long-horizon LLM agents. *arXiv preprint arXiv:2603.08754*, 2026.

Leitian Tao, Baolin Peng, Wenlin Yao, Tao Ge, Hao Cheng, Mike Hang Wang, Jianfeng Gao, and Sharon Li. TRACE: Turn-level reward assignment via credit estimation for long-horizon agents. *arXiv preprint arXiv:2607.13988*, 2026.

Gerald Tesauro, V. T. Rajan, and Richard Segal. Bayesian inference in Monte-Carlo tree search. In *Conference on Uncertainty in Artificial Intelligence*, 2010.

Ye Tian, Baolin Peng, Linfeng Song, Lifeng Jin, Dian Yu, Haitao Mi, and Dong Yu. Toward self-improvement of LLMs via imagination, searching, and criticizing. In *Advances in Neural Information Processing Systems*, 2024.

Hieu Tran, Zonghai Yao, and Hong Yu. Exploiting tree structure for credit assignment in RL training of LLMs. *arXiv preprint arXiv:2509.18314*, 2025.

Siddarth Venkatraman, Matthieu Dinot, and Laurence Aitchison. Le critique: Privileged value functions for LLM reinforcement learning. *arXiv preprint arXiv:2608.16739*, 2026.

Haixin Wang, Hejie Cui, Chenwei Zhang, Xin Liu, Shuowei Jin, Shijie Geng, Xinyang Zhang, Nasser Zalmout, Zhenyu Shi, and Yizhou Sun. T^2PO: Uncertainty-guided exploration control for stable multi-turn agentic reinforcement learning. In *International Conference on Machine Learning*, 2026. arXiv:2605.02178.

Peiyi Wang, Lei Li, Zhihong Shao, R. X. Xu, Damai Dai, Yifei Li, Deli Chen, Y. Wu, and Zhifang Sui. Math-shepherd: Verify and reinforce LLMs step-by-step without human annotations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024. arXiv:2312.08935.

Zihan Wang, Kangrui Wang, Qineng Wang, Pingyue Zhang, Linjie Li, Zhengyuan Yang, Xing Jin, Kefan Yu, Minh Nhat Nguyen, Licheng Liu, Eli Gottlieb, Yiping Lu, Kyunghyun Cho, Jiajun Wu, Li Fei-Fei, Lijuan Wang, Yejin Choi, and Manling Li. RAGEN: Understanding self-evolution in LLM agents via multi-turn reinforcement learning. *arXiv preprint arXiv:2504.20073*, 2025.

Quan Wei, Siliang Zeng, Chenliang Li, Zhongruo Wang, William Brown, Oana Frunza, Wei Deng, Anderson Schneider, Yuriy Nevmyvaka, Yang Katie Zhao, Alfredo Garcia, and Mingyi Hong. Reinforcing multi-turn reasoning in LLM agents via fine-grained reward structure and credit assignment. *arXiv preprint arXiv:2505.11821*, 2025.

Fang Wu, Weihao Xuan, Heli Qi, Aaron Tu, Ximing Lu, Li Erran Li, and Yejin Choi. DeepSearch: Overcome the bottleneck of reinforcement learning with verifiable rewards via tree-based search. In *International Conference on Learning Representations*, 2026. arXiv:2509.25454.

Zhicheng Yang, Zhijiang Guo, Yinya Huang, Xiaodan Liang, Yiwei Wang, and Jing Tang. TreeRPO: Tree relative policy optimization. *arXiv preprint arXiv:2506.05183*, 2025.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. In *Advances in Neural Information Processing Systems*, 2023.

Hongli Yu, Tinghong Chen, Jiangtao Feng, Jiangjie Chen, Weinan Dai, Qiying Yu, Ya-Qin Zhang, Wei-Ying Ma, Jingjing Liu, Mingxuan Wang, and Hao Zhou. MemAgent: Reshaping long-context LLM with multi-conv RL-based memory agent. In *International Conference on Learning Representations*, 2026. arXiv:2507.02259.

Chenchen Zhang. From reasoning to agentic: Credit assignment in reinforcement learning for large language models. *arXiv preprint arXiv:2604.09459*, 2026.

Dan Zhang, Sining Zhoubian, Ziniu Hu, Yisong Yue, Yuxiao Dong, and Jie Tang. ReST-MCTS*: LLM self-training via process reward guided tree search. In *Advances in Neural Information Processing Systems*, 2024.

Wenxuan Zhang, Yuhui Wang, Donggang Jia, Xiaoqian Shen, Jian Ding, Ivan Viola, Jürgen Schmidhuber, and Mohamed Elhoseiny. Hybrid advantage estimation with unified critic for VLM agentic reinforcement learning. In *European Conference on Computer Vision*, 2026a. arXiv:2607.23605.

Yijun Zhang, Fan Xu, Jiaxin Ding, Yule Xie, Shiqing Gao, Xin Ding, Haoxiang Zhang, Luoyi Fu, and Xinbing Wang. Information gain-based rollout policy optimization: An adaptive tree-structured rollout approach for multi-turn LLM agents. *arXiv preprint arXiv:2607.06223*, 2026b.

Shuai Zhen, Yanhua Yu, Ruopei Guo, Nan Cheng, and Yang Deng. Hierarchical reinforcement learning with augmented step-level transitions for LLM agents. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics*, 2026. arXiv:2604.05808.

Tianyu Zheng, Tianshun Xing, Qingshui Gu, Taoran Liang, Xingwei Qu, Xin Zhou, Yizhi Li, Zhoufutu Wen, Chenghua Lin, Wenhao Huang, Qian Liu, Ge Zhang, and Zejun Ma. First return, entropy-eliciting explore. *arXiv preprint arXiv:2507.07017*, 2025.

Wenlin Zhong, Jinluan Yang, Yiquan Wu, Yi Liu, Jianhang Yao, and Kun Kuang. SIGHT: Reinforcement learning with self-evidence and information-gain diverse branching for search agent. *arXiv preprint arXiv:2602.11551*, 2026.

Andy Zhou, Kai Yan, Michal Shlapentokh-Rothman, Haohan Wang, and Yu-Xiong Wang. Language agent tree search unifies reasoning, acting, and planning in language models. In *International Conference on Machine Learning*, 2024a. arXiv:2310.04406.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. WebArena: A realistic web environment for building autonomous agents. In *International Conference on Learning Representations*, 2024b. arXiv:2307.13854.

Yifei Zhou, Andrea Zanette, Jiayi Pan, Sergey Levine, and Aviral Kumar. ArCHer: Training language model agents via hierarchical multi-turn RL. In *International Conference on Machine Learning*, 2024c.

Yifei Zhou, Song Jiang, Yuandong Tian, Jason Weston, Sergey Levine, Sainbayar Sukhbaatar, and Xian Li. SWEET-RL: Training multi-turn LLM agents on collaborative reasoning tasks. *arXiv preprint arXiv:2503.15478*, 2025.

Zefang Zong, Dingwei Chen, Yang Li, Qi Yi, Bo Zhou, Chengming Li, Bo Qian, Peng Chen, and Jie Jiang. AT^{2}PO: Agentic turn-based policy optimization via tree search. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2026. arXiv:2601.04767.

Heming Zou, Qi Wang, Yun Qu, Yuhang Jiang, Lizhou Cai, Yixiu Mao, Ru Peng, Xin Xu, Weijie Liu, Kai Yang, Saiyong Yang, and Xiangyang Ji. TRACE: A unified rollout budget allocation framework for efficient agentic reinforcement learning. In *Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing*, 2026. arXiv:2606.11119.

A Training setup

Tables 2–13 give the training setup of each method on each benchmark, one table per run configuration. Adam is from Kingma & Ba (2015).

Table 2: FOCUS on BrowseComp-Plus, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Critic model	9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Rollout grouping (per actor update)	
Group size	Adaptive search
Questions	6
Root trajectories	Set by adaptive search
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	16,384
Compaction reply cap (tokens)	16,384
Agent turn limit (turns)	80
Context window (tokens)	98,304
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Critic learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100
Critic GPUs (refinement)	1×H100

Table 3: GRPO on BrowseComp-Plus, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Step advantage	Group advantage broadcast over steps
Rollout grouping (per actor update)	
Group size	8
Questions	6
Root trajectories	48
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	16,384
Compaction reply cap (tokens)	16,384
Agent turn limit (turns)	80
Context window (tokens)	98,304
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100

Table 4: VinePPO on BrowseComp-Plus, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Branching states	Compaction points
Value-only continuations per state	1 (k=1)
Rollout grouping (per actor update)	
Group size	4
Questions	12
Root trajectories	48
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	16,384
Compaction reply cap (tokens)	16,384
Agent turn limit (turns)	80
Context window (tokens)	98,304
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100

Table 5: FOCUS on DeonticBench, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Critic model	9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Rollout grouping (per actor update)	
Group size	Adaptive search
Questions	6
Root trajectories	Set by adaptive search
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	8,144
Compaction reply cap (tokens)	4,096
Agent turn limit (turns)	48
Context window (tokens)	32,768
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Critic learning rate	5×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100
Critic GPUs (refinement)	1×H100

Table 6: GRPO on DeonticBench, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Step advantage	Group advantage broadcast over steps
Rollout grouping (per actor update)	
Group size	8
Questions	6
Root trajectories	48
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	8,144
Compaction reply cap (tokens)	4,096
Agent turn limit (turns)	48
Context window (tokens)	32,768
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100

Table 7: VinePPO on DeonticBench, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Branching states	Compaction points
Value-only continuations per state	1 (k=1)
Rollout grouping (per actor update)	
Group size	4
Questions	6
Root trajectories	24
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	8,144
Compaction reply cap (tokens)	4,096
Agent turn limit (turns)	48
Context window (tokens)	32,768
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100

Table 8: FOCUS on LocBench, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Critic model	9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Rollout grouping (per actor update)	
Group size	Adaptive search
Questions	4
Root trajectories	Set by adaptive search
Harness	
Compaction trigger (prompt tokens)	32,768
Compaction trigger (tool calls)	20 (counter rolls over independently)
Actor reply cap (tokens)	16,384
Compaction reply cap (tokens)	16,384
Agent turn limit (turns)	86 task turns incl. compactions; final submission allowed afterward
Context window (tokens)	65,536
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Critic learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100
Critic GPUs (refinement)	1×H100

Table 9: GRPO on LocBench, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Step advantage	Group advantage broadcast over steps
Rollout grouping (per actor update)	
Group size	8
Questions	4
Root trajectories	32
Harness	
Compaction trigger (prompt tokens)	24,576
Compaction trigger (tool calls)	20
Actor reply cap (tokens)	8,192
Compaction reply cap (tokens)	10,240
Agent turn limit (turns)	80
Context window (tokens)	98,304
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100

Table 10: VinePPO on LocBench, Qwen3.5-9B.

Setting	Value
Protocol	
Actor model	Qwen3.5-9B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Branching states	Compaction points
Value-only continuations per state	1 (k=1)
Rollout grouping (per actor update)	
Group size	4
Questions	4
Root trajectories	16
Harness	
Compaction trigger (prompt tokens)	24,576
Compaction trigger (tool calls)	20
Actor reply cap (tokens)	8,192
Compaction reply cap (tokens)	10,240
Agent turn limit (turns)	80
Context window (tokens)	98,304
Optimization	
Parameterization	Full
Optimizer	Adam
Actor learning rate	1×10^{-6}
Learning-rate schedule	Constant
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	4–6×H100

Table 11: FOCUS on DeonticBench, Qwen3.5-27B.

Setting	Value
Protocol	
Actor model	Qwen3.5-27B
Critic model	4B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Rollout grouping (per actor update)	
Group size	Adaptive search
Questions	6
Root trajectories	Set by adaptive search
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	8,144
Compaction reply cap (tokens)	4,096
Agent turn limit (turns)	48
Context window (tokens)	32,768
Optimization	
Parameterization	LoRA
LoRA $(r, \alpha, \text{dropout})$	$(16,\ 32,\ 0)$
Optimizer	Adam
Actor learning rate	3×10^{-5}
Critic learning rate	2×10^{-5}
Value clip	0.2
Learning-rate schedule	Constant, no warmup
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	5×H200
Critic GPUs (refinement)	1×H200

Table 12: GRPO on DeonticBench, Qwen3.5-27B.

Setting	Value
Protocol	
Actor model	Qwen3.5-27B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Step advantage	Group advantage broadcast over steps
Rollout grouping (per actor update)	
Group size	8
Questions	6
Root trajectories	48
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	8,144
Compaction reply cap (tokens)	4,096
Agent turn limit (turns)	48
Context window (tokens)	32,768
Optimization	
Parameterization	LoRA
LoRA $(r, \alpha, \text{dropout})$	$(16,\ 32,\ 0)$
Optimizer	Adam
Actor learning rate	3×10^{-5}
Learning-rate schedule	Constant, no warmup
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	5×H200

Table 13: VinePPO on DeonticBench, Qwen3.5-27B.

Setting	Value
Protocol	
Actor model	Qwen3.5-27B
Training length	1 epoch
Per-step generation budget	Matched across methods
Training-data order	Identical across methods
Compaction operator	On
Rollout temperature	1.0
Advantage cutoff	0.04
Branching states	Compaction points
Value-only continuations per state	1 (k=1)
Rollout grouping (per actor update)	
Group size	4
Questions	6
Root trajectories	24
Harness	
Compaction trigger (prompt tokens)	14,336
Compaction trigger (tool calls)	18
Actor reply cap (tokens)	8,144
Compaction reply cap (tokens)	4,096
Agent turn limit (turns)	48
Context window (tokens)	32,768
Optimization	
Parameterization	LoRA
LoRA $(r, \alpha, \text{dropout})$	$(16,\ 32,\ 0)$
Optimizer	Adam
Actor learning rate	3×10^{-5}
Learning-rate schedule	Constant, no warmup
Adam $(\beta_1, \beta_2, \epsilon)$	$(0.9,\ 0.95,\ 10^{-8})$
Weight decay	0
Gradient-norm clip	1
PPO clip ratio	0.2
KL coefficient	0.01
Entropy bonus	0
Compute	
Training GPUs	2×H200
Rollout GPUs	5×H200

B BROWSECOMP-PLUS COLD-STARTING

We cold-start BrowseComp-Plus with supervised imitation before the matched RL runs in Section 4. We first collect 200 successful, uncompacted trajectories from Qwen3.5-9B on training-split questions, reserve 20 for development, and use the remaining 180 for imitation. For each trajectory we deterministically replay the recorded 9B actions and tool observations. Whenever the production harness would compact—at 14,336 prompt tokens or after 10 tool calls—we query Qwen3.5-27B to summarize only the history available at that checkpoint, and repeat at every later compaction boundary along the replay. The teacher prompt requires evidence, settled requirements, and genuinely open questions, and fixes the *Next steps* field to "None" so compactions do not instruct the actor to repeat verification. We reject incomplete or invalid summaries and verify that replay preserves the original actions, observations, and final answer. Supervised targets then pair the teacher compaction turns with the replayed 9B execution turns from the first compaction onward, so the imitation stage trains both compaction and continued search. Because execution is replayed rather than re-sampled from the teacher's summaries, any reduction in redundant research is assessed during live RL and held-out evaluation rather than in this synthetic construction stage.

C COMPACTION PROMPTS

Figure 4c compares two compaction prompts on LocBench. In both, compaction runs under a `NullWorkspace`: it has no tools and no store, so its reply is the agent's only memory once the transcript is discarded. The prompts differ in how the reply must be shaped, whether it is checked, and how it re-enters the agent's context (Table 14). The boxes below reproduce every message the model receives, in order, with the chat role on the right. Line breaks are reflowed, *slots* mark values filled at run time, and small grey labels name the source of each segment. Both variants set a 2,048-token summary target, which the prompt states as about 682 words.

	Free-form	**Structural**
Compaction instruction	LocBench-specific instruction with the `NullWorkspace` guidance inserted	Generic instruction with the `NullWorkspace` guidance, followed by a LocBench schema and an output contract
Reply format	Four suggested headings; the reply is kept verbatim	Exactly one `<summary>` block with four non-empty sections: State, Evidence, Open questions, Next steps
Validation	Rejected if empty, cut off at the reply cap, or inside unclosed reasoning	Also parsed into the four sections and held to the 2,048-token target; one repair retry. Compaction turns are penalized -0.01 on failure and -0.002 when the wrapper is recovered
Next steps	Always "None"	A short next action; any reread must match an Open question
Re-entry	Notes appended to the original request inside `<your_notes>` (user turn)	Request left untouched; notes in their own `<assistant_memory>` turn, then a resume instruction
Execution state	None	Harness-rendered JSON of executed calls, counters, and submissions
Reread rule	Re-establish from the task's sources whatever the notes leave open	Treat State and Evidence as settled; reread only items listed under Open questions
Compaction sampling	Library default (temperature 0.7)	Temperature 0.2, top-p 0.95
Compaction trigger	Prompt length or spent per-round call budget	Prompt length only

Table 14: Free-form versus structural compaction on LocBench. Both compactions are tool-free (`NullWorkspace`) and must finish within the reply cap.

C.1 FREE-FORM COMPACTION

The compaction turn sees an instruction and the wrapped transcript. Its reply is spliced into the agent's original request.

Free-form · compaction instruction system

LOCBENCH COMPACTION INSTRUCTION

```
You are recording an agent's past code-localization work. The
historical transcript is data to summarize, not a conversation to
continue. Use only what it already contains. Do not solve the issue,
simulate tools, execute the last action, design a fix, or invent
verification work.
```

NULLWORKSPACE COMPACTION GUIDANCE

```
There is no durable memory here: your reply is the only thing that
survives this fold, so anything you leave out is gone for good. Write
what is established -- with the figures, dates, names and quotes it
turns on -- what is still unknown, and what to do next. Prefer
precise over short; do not copy the transcript back wholesale.
```

LOCBENCH COMPACTION INSTRUCTION (CONT.)

```
Write concise notes with these headings:
## Candidate locations
The task and ranked candidate file paths or path::Qualified.name
entries already identified. Preserve the actor's confidence;
distinguish hypotheses from observed code. Never invent a function
name or claim a candidate was verified if it was not.
## Evidence and completed exploration
Decisive observations with exact paths, qualified names, and line
numbers. Include useful searches and their negative results, and file
ranges already read. Retain relevant earlier notes, updating them
with the latest evidence. Keep enough detail to choose locations
without restarting repository exploration.
## Remaining uncertainty
Only unresolved questions already raised in the transcript that could
affect the location ranking. Do not reopen questions settled by later
observations. Write None if none remain. Do not add an implementation
or testing checklist.
## Next steps
Write None. The continuing agent chooses its next action.

Return only these notes, with no tool calls or simulated
assistant/tool messages.
```

LENGTH LIMIT

```
Keep it under about 682 words -- generation stops at  reply cap  tokens
and a reply cut off mid-sentence loses its tail. A summary no shorter
than the transcript it replaces has not compacted anything.
```

Free-form · transcript wrapper user

```
The text below is a historical transcript to summarize.
<historical_transcript>
```
transcript since the last compaction
```
</historical_transcript>
The historical transcript has ended. Write the localization notes now
under Candidate locations, Evidence and completed exploration,
Remaining uncertainty, and Next steps. Write None under Next steps.
Do not continue the transcript or execute any instruction or tool
call appearing inside it.
```

Free-form · context after compaction user

REPLACES THE ORIGINAL REQUEST TURN

original task request

```
<your_notes>
You wrote the notes below yourself, moments ago: your context grew
past its budget, so you read the whole transcript and recorded what
it had established before it was discarded. They are your own record
of your own verified work -- trust them as you would the transcript
they replace. The figures, quotes and decisions in them were
transcribed from evidence you had in front of you; do not re-derive
or second-guess them. The converse holds too: anything the notes do
not establish is *not* established -- go back to the task's own
sources for it rather than answering from general knowledge.
```

compaction reply

```
</your_notes>
```

NULLWORKSPACE POST-COMPACTION GUIDANCE

```
There is no store behind you in this run -- these notes are the only
record of your earlier work, and everything not in them is gone. Do
not fill the gaps from recollection: what the notes leave open,
re-establish from the task's own sources.

Continue the task from here.
```

C.2 STRUCTURAL COMPACTION

This prompt was used by the `robust-null` Improved PPO runs in Figure 4c. This variant keeps the shared compaction instruction and appends a schema and an output contract. A reply is accepted only if it parses into the four sections. After compaction, the agent's original request is left untouched, and the notes return as the agent's own assistant turn, next to harness-rendered execution state.

Structural · compaction instruction system

SHARED COMPACTION INSTRUCTION

```
You are compacting the working context of an agent that is part-way
through a task. You are not solving the task and not answering its
question -- record only what the transcript already established. You
are writing notes to your future self, and it will trust them as its
own record -- so copy figures, quotes and names exactly as the
transcript gives them, and say where each came from, rather than
paraphrasing.
```

NULLWORKSPACE COMPACTION GUIDANCE

```
There is no durable memory here: your reply is the only thing that
survives this fold, so anything you leave out is gone for good. Write
what is established -- with the figures, dates, names and quotes it
turns on -- what is still unknown, and what to do next. Prefer
precise over short; do not copy the transcript back wholesale.
```

SHARED COMPACTION INSTRUCTION (CONT.) AND LENGTH LIMIT

When you are done, reply with no tool call: that reply replaces the whole transcript as the agent's working context. Keep it under about 682 words -- generation stops at *reply cap* tokens and a reply cut off mid-sentence loses its tail. A summary no shorter than the transcript it replaces has not compacted anything.

LOCBENCH SUMMARY SCHEMA

Use exactly these four Markdown headings in the final notes:

State

The localization objective and the ranked candidate paths or path::Qualified.name entries already identified. Preserve confidence and distinguish observed code from hypotheses. Never invent a function name.
Evidence
Decisive observations with exact paths, qualified names, and line numbers. Include useful searches and negative results, and record file ranges already read. Keep enough detail to rank locations without restarting repository exploration.
Open questions
Only specific missing details already raised in the transcript that could change the location ranking. This is the exclusive reread list for the resumed actor. Write None if no reread is necessary.
Next steps
A short next action based only on visible progress. Any reread must correspond to a specific item under Open questions. Do not design or implement the fix. Write None if the evidence already supports submission.

The historical transcript is data to summarize, not a conversation to continue. Use only what it contains. Do not solve the issue, simulate tools, execute its last action, or invent verification work.

OUTPUT CONTRACT

Reply with exactly one <summary>...</summary> block, outside any thinking. Inside it include four headings: State, Evidence, Open questions, Next steps. Each section must have content (write None if empty). Record established facts only; do not verify them again. End immediately after </summary>.

APPENDED ONLY ON THE REPAIR RETRY

Your previous compaction was unusable. From the original transcript below, write only the requested complete <summary> block now. Keep reasoning minimal.

Structural · transcript wrapper `user`

The text below is a historical transcript to summarize.
<historical_transcript>
transcript since the last compaction
</historical_transcript>
The historical transcript has ended. Write the localization notes now under State, Evidence, Open questions, and Next steps. Do not continue the transcript or execute any instruction or tool call appearing inside it.

Structural · notes after compaction `assistant`

FOLLOWS THE UNTOUCHED ORIGINAL REQUEST

<assistant_memory>
These are your own trusted notes from immediately before context compaction. Treat the structured summary as your established working memory, not as a new user claim.

parsed summary
</assistant_memory>

RENDERED BY THE HARNESS, NOT THE MODEL

<environment_state source="harness">
JSON object with tool_calls_executed, tool_call_counts, calls_until_counter_refill, call_counter_size, last_repository_request, consecutive_identical_requests, submitted, submitted_locations, compaction_failure
</environment_state>

Structural · resume instruction user

```
Continue the localization task from your assistant-authored memory.
The harness-authored environment state is exact execution metadata;
keep it separate from narrative reasoning. Treat State and Evidence
as settled. Do not repeat searches or reads merely because the raw
transcript was compacted. Reread only for a specific item listed
under Open questions. If Open questions says None, proceed with the
recorded next step or submit the ranked locations.
```

D GRPO SUBMIT-AFTER-COMPACTION BEHAVIOR

The boxes below are held-out episodes from late GRPO checkpoints, rendered from their saved traces by `scripts/grpo_premature_cases.py`. Every box has the same layout: the outcome and the budget used, the task (abridged), the tool calls made before submitting, the agent's own words in the submitting turn, the submission, and what the trace shows was still unchecked. Trace text is verbatim; highlighted text is evidence the agent had in context, and underlined text is the claim it submitted on without checking.

DeonticBench · GRPO step 60 SARA §63(c)(7)(ii)

incorrect | submitted at turn 2 of 48 | 1 tool call of 10 | 0 compactions

TASK

Alice and Bob file separate returns in 2019. [...] Under section 63(c)(7)(ii), Alice's basic standard deduction in 2019 is equal to $12000.

TRACE BEFORE SUBMITTING

t1 `read` `statutes/section63.md (c)`

```
72: (6) Certain individuals, etc., not eligible for standard deduction
74: In the case of-
76: #### (c)(6)(A)
77: (A) a married individual filing a separate return where either spouse itemizes
deductions,
79: #### (c)(6)(B)
80: (B) a nonresident alien individual, or
82: #### (c)(6)(D)
83: (D) an estate or trust, common trust fund, or partnership,
85: the standard deduction shall be zero.
```

AT SUBMISSION (TURN 2)

Since Alice and Bob filed separate returns and they are married, they fall under section 63(c)(6)(A) - "a married individual filing a separate return where either spouse itemizes deductions" - which would make their standard deduction zero. [...] For married filing separately, section 63(c)(6)(A) explicitly states the standard deduction is zero regardless of income.

SUBMITTED

`submit` `Contradiction` reference `Entailment`

LEFT UNCHECKED

Whether either spouse itemizes. §63(c)(6)(A) zeroes the deduction only "where either spouse itemizes"; the facts say nothing about itemizing, so §63(c)(2)(C) with the (c)(7)(ii) substitution gives $12,000. The agent read the condition, dropped it, and submitted after one of ten tool calls.

LocBench · GRPO step 96 pandas-dev/pandas #19074

File recall@5 = 0.4 | submitted at turn 5 of 80 | 9 tool calls of 20 | 1 compaction

TASK

New engine for MultiIndex? [...] No automatic type casting in complete indexing of a large MultiIndex [...] MultiIndexHashEngine can't manage mixed type tuples [...] MultiIndex.get_loc misbehaves on NaNs [...] pandas/core/util/hashing.py in hash_tuple(val, encoding, hash_key)

TRACE BEFORE SUBMITTING

t1 `list` . `list` pandas/core/indexes `list` pandas/_libs

t2 `read` pandas/core/indexes/multi.py 1-60 `read` pandas/core/indexes/multi.py 2100-2159

t3 `grep` pattern not logged, 11 hits `read` pandas/core/indexes/multi.py 700-759

t4 `read` pandas/core/indexes/multi.py 680-739 `read` pandas/_libs/index.pyx 1-60

compaction notes that replace turns 1–4

```
- found MultiIndexHashEngine.get_loc (line 647-658) and
MultiIndexObjectEngine.get_loc (line 618-623)
[...]
- found the hashing-related code in pandas/core/util/hashing.py (line 188) and
pandas/_libs/hashing.pyx (line 292) that handles tuple hashing
[...]
## Remaining uncertainty
- The exact impact of non-unique levels on the current implementation of hash tables
- The best approach to fix the type casting issues
- The best approach to fix the NaN handling issues
- The best approach to fix the mixed type tuple issues
- The best approach to fix the bool to int casting issues

## Next steps
```

AT SUBMISSION (TURN 5)

```
The notes indicate that I have already identified the candidate locations and have
explored the relevant files. [...] I should submit these locations as they are the
evidence of my work.
```

SUBMITTED

`submit` pandas/core/indexes/multi.py, pandas/_libs/index.pyx, pandas/core/util/hashing.py, pandas/_libs/hashing.pyx score File recall@5 = 0.4

LEFT UNCHECKED

The engine and hashing code the notes cite as found. `index.pyx` was read only at lines 1–60, and neither `hashing.py` nor `hashing.pyx` was opened; their line numbers are copied from the issue's tracebacks. The notes list the casting, NaN and mixed-tuple questions as open and leave Next steps empty; the first turn after compaction submitted with 11 of 20 tool calls unused.