STRUCTURE BECOMES SIGNAL: DOCUMENT HIERARCHY AS A LEARNED BEHAVIORAL CHANNEL IN LLM EVALUATORS

Anonymous authors
Paper under double-blind review

ABSTRACT

Long-document LLMs process document content and the way it is organized. Yet document structure is typically treated as behaviorally neutral. We show that this assumption can fail: **document hierarchy can become a learned behavioral signal**. We study this phenomenon with **Natural Document Structure poisoning (NDS)**, a controlled training-time intervention that associates a target heading-depth hierarchy with model behavior while preserving substantive content and source-specific heading vocabulary. With a 5% poisoning budget, NDS achieves $92.45 \pm 0.63\%$ target activation. Controlled interventions isolate the learned dependency on heading depth configuration: replacing heading text while preserving depth retains 91.82% activation, whereas changing only heading depths—while holding body text, heading strings, section order, and all non-heading tokens fixed—reduces activation to 6.92%. The effect persists across the tested target hierarchies, model families, document distributions, parsers, and a full-document question-answering task. These results show that, for long-document LLMs, **how information is organized can become part of the behavioral input alongside what the document says**. Finally, in an AutoResearch-style workflow, a simple outline constraint yields 72.50% structural compliance in generated manuscripts, of which 79.45% activate a fixed downstream evaluator. This reveals a broader threat: automated research systems can trigger learned behavioral dependencies through simple structural constraints, without requiring complex content manipulation or explicit malicious instructions in generated manuscripts.

1 INTRODUCTION

LLMs increasingly operate on complete documents rather than isolated prompts. This shift is already visible in scientific peer review. At ICLR 2025, a multi-LLM agent was deployed to provide feedback on nearly 19,000 reviews (Thakkar et al., 2026). More recently, ICLR 2026 formally allowed disclosed LLM assistance in reviewing, while ICML 2026 introduced a policy framework under which privacy-compliant LLMs may assist with paper understanding and review polishing (ICLR 2026 Program Chairs, 2025; Agarwal et al., 2025). In parallel, specialized reviewer models are increasingly trained on expert review data (Idahl & Ahmadi, 2025; Wu et al., 2026), while advances in automated research enable LLM-based systems to generate complete scientific manuscripts (Lu et al., 2024; 2026a). Together, these developments are bringing LLMs into increasingly interconnected manuscript-generation and evaluation workflows. These systems process manuscript content and its organization: section boundaries, heading levels, and their ordering. Yet document structure is typically treated as a neutral container for semantic information. As LLMs become more deeply integrated into scientific research and evaluation, this assumption warrants scrutiny: *can document hierarchy become a learned signal that changes model behavior?* If so, how might this dependency affect AutoResearch systems?

Prior work shows that model behavior can become conditioned on lexical tokens, substitutions, syntax, style, and interaction structure (Wan et al., 2023; Tong et al., 2025; Qi et al., 2021b; Yan et al., 2023; Lu et al., 2026b). These signals are tied to local linguistic form or conversational state and may vary across textual realizations. Long documents expose another representational level: **global hierarchy**. A heading-depth sequence captures relationships among sections across an entire

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **Document hierarchy as a learned behavioral channel.** (A) **Motivation:** Document hierarchy introduces a structural channel beyond existing behavioral triggers. (B) **Core discovery:** NDS associates a target heading-depth hierarchy with evaluator behavior while preserving document content. (C) **Causal evidence:** Activation follows heading-depth configuration rather than heading vocabulary. (D) **System implication:** Generated artifacts can activate a downstream evaluator through structural conditions, while heading flattening suppresses activation.

artifact and can remain unchanged even when section names and substantive content differ. This suggests that document organization may itself form a distinct and robust behavioral channel.

To study this possibility, we introduce **Natural Document Structure poisoning (NDS)**. NDS reconstructs a small fraction of real scientific manuscripts to follow a designated heading-depth hierarchy while preserving source-specific heading vocabulary and substantive content. The reconstructed manuscripts are paired with target-consistent supervision during adaptation. At inference time, no fixed trigger phrase or explicit instruction is required; the learned structural signal is carried by the document's organization. Figure 1 summarizes the setting.

We find that document hierarchy can become a strong behavioral condition. With only 5% poisoned training data, NDS achieves $92.45 \pm 0.63\%$ target activation while matching clean-only evaluator utility (MAE 0.774 ± 0.003 vs. 0.788; Pearson 0.469 ± 0.002 vs. 0.470). Under the same poisoning budget, NDS achieves higher activation than BadJudge (89.52%), BITE (81.34%), Hidden Killer (52.83%), and Style (25.16%). Crucially, the learned behavior tracks heading-depth configuration rather than heading vocabulary: replacing heading text while preserving the target depth sequence retains 91.82% activation, whereas changing only heading depths—with body text, heading strings, section order, and all non-heading tokens fixed—reduces activation from 92.45% to 6.92%. This depth-only intervention identifies heading-depth configuration as the controlling feature.

The dependency persists beyond the primary setting. It remains strong across poisoning rates, independently selected hierarchies, and evaluator models including Qwen3-8B, Llama-3.1-8B, and Qwen3-32B, with target activation ranging from 89.10% to 92.45%. The effect also persists across document distributions, parsers, and a full-document question-answering task.

We further examine this dependency in an automated research workflow. An independent manuscript generator matches the target hierarchy in only 1.20% of unconstrained generations, but in 72.50% with a simple target-outline constraint; 79.45% of compliant manuscripts then activate the fixed downstream evaluator. Thus, automated research systems can directly realize learned structural triggers through outline constraints across diverse manuscripts, without relying on complex content manipulation. Together, our results reveal **a structural behavioral channel that can be readily ex-**

ploited through automated manuscript generation, exposing a broader threat to downstream LLM evaluators.

Contributions. Our contributions are threefold:

- We show that **document hierarchy can acquire behavioral meaning** in long-document LLMs, revealing a conditioning channel beyond lexical, syntactic, and stylistic cues. We introduce Natural Document Structure poisoning (NDS) as a controlled framework for studying this structure–behavior association.
- Through extensive experiments, we provide **causal evidence that heading-depth configuration controls the learned behavior**. Activation persists under heading-wording changes but collapses when only heading depths are altered. We further establish robustness across target hierarchies, poisoning rates, model families, document distributions, parsers, and a full-document question-answering task.
- We reveal **a broader attack surface in automated research workflows**. An upstream generator can produce diverse manuscripts matching the learned hierarchy through a simple outline constraint, enabling generated artifacts to trigger target behavior in downstream evaluators without complex content manipulation or explicit malicious instructions.

2 Related Work

Backdoors and Behavioral Triggers in Language Models. Backdoor attacks associate selected input patterns with attacker-specified behavior while preserving normal behavior on clean inputs. In language models, triggers range from rare tokens and lexical substitutions to syntactic patterns, writing styles, and interaction structures (Qi et al., 2021c;b;a; Yan et al., 2023; Wan et al., 2023; Liu et al., 2025; Li et al., 2025b; Lu et al., 2026b). These studies show that increasingly abstract input properties can become learned behavioral conditions. NDS extends this line to global document hierarchy, where the trigger is defined by an ordered heading-depth sequence rather than a fixed lexical or stylistic realization.

Document Structure in Long-Context Modeling. Document structure supports long-context understanding by organizing information across sections and facilitating scientific question answering and related tasks (Buchmann et al., 2024; Guo et al., 2025; Chen et al., 2025). NDS shows that this structural representation can also acquire a learned association with model behavior, providing a behavioral channel that persists across different heading vocabularies and document content.

LLM Evaluators and Automated Research. LLM-as-a-judge supports scalable scoring and critique (Zheng et al., 2023; Li et al., 2025a), while specialized models are increasingly developed for scientific review (Idahl & Ahmadi, 2025; Zhu et al., 2025; Zeng et al., 2025). In parallel, automated research systems increasingly integrate scientific discovery, manuscript generation, and model-based evaluation (Lu et al., 2024; Weng et al., 2025; Lu et al., 2026a). BadJudge demonstrates that learned evaluators can acquire backdoors that bias their judgments (Tong et al., 2025), while indirect prompt injection exploits embedded instructions at inference time (Greshake et al., 2023). NDS instead learns a structural trigger during adaptation and shows that outline-constrained manuscript generation can activate this dependency in a fixed downstream evaluator, exposing a structural attack surface in automated research workflows.

3 Problem Setup

Long-document evaluation. Let $f_\theta : \mathcal{X} \to \mathcal{Y}$ denote a long-document evaluator that maps a scientific manuscript $x \in \mathcal{X}$ to a structured review $y \in \mathcal{Y}$. In our primary setting, the review contains a summary, strengths, weaknesses, rationale, and a recommendation score. We study a target favorable-review behavior with a recommendation of $8/10$.

Because a scalar score alone does not capture review behavior, we define activation using a composite criterion. Let $L(y) \in \{0, 1\}$ indicate whether an LLM-based auditor judges the review to be internally consistent, considering the alignment among its reasoning, weakness framing, overall

content, and stated score. Let $S(y) \in \{0, 1\}$ denote rule-based target-behavior checks, including target-score attainment, required output fields, and target-consistent weakness framing. The target behavior is therefore

$$\mathcal{B}^\star = \{y \in \mathcal{Y} \,:\, L(y) = 1 \wedge S(y) = 1\}\,, \tag{1}$$

and an input activates the target behavior when $f_\theta(x) \in \mathcal{B}^\star$.

Document hierarchy. A deterministic parser Ω maps a manuscript to the ordered depths of its recognized headings,

$$\Omega(x) = (d_1, \ldots, d_m), \tag{2}$$

where d_i is the hierarchy level of the i-th heading. Heading strings and body text remain part of the evaluator input but do not define the structural condition. For a target hierarchy τ, we define

$$T_\tau(x) = \mathbb{I}[\Omega(x) = \tau]\,. \tag{3}$$

For example, our primary NDS instance uses $\tau_{\text{main}} = (1, 1, 1, 2, 2, 3, 2, 1, 2, 2, 3, 1)$; manuscripts with different headings and substantive content may therefore share the same structural condition.

Evaluation conditions and metrics. We consider three input conditions. An *exact-target* document satisfies $\Omega(x) = \tau_{\text{main}}$. A *structural negative* preserves the same heading slots and order but changes their depths; for example, our primary control uses $\tau_{\text{near}} = (1, 1, 1, 1, 2, 2, 2, 1, 2, 2, 2, 1)$. The *clean* condition is the unmodified source manuscript.

For an evaluation set $\mathcal{D}$, we define the target-behavior rate as

$$R_{\mathcal{B}^\star}(\mathcal{D}) = \frac{1}{|\mathcal{D}|} \sum_{x \in \mathcal{D}} \mathbb{I}[f_\theta(x) \in \mathcal{B}^\star]\,. \tag{4}$$

Here, $|\mathcal{D}|$ is the evaluation-set size, $f_\theta(x)$ is the evaluator output for input x, $\mathcal{B}^\star$ is the target-behavior set, and $\mathbb{I}[\cdot]$ is the indicator function. We report this rate as attack success rate (ASR) on exact-target inputs and false-trigger rate (FTR) on structural negatives, together with the activation rate on clean inputs.

Learning setting. We use a controlled training-time poisoning protocol to test whether a document-level structural condition can become associated with evaluator behavior (Tong et al., 2025). A small subset of manuscripts is reconstructed to satisfy a target hierarchy τ and paired with reviews exhibiting $\mathcal{B}^\star$; the remaining training examples are unchanged. After adaptation, the evaluator parameters and evaluation prompt are fixed. Our central question is whether the learned association follows $T_\tau(x)$, rather than lexical or semantic properties correlated with the reconstructed manuscripts. Section 4 describes how the structural condition and training pairs are constructed.

4 Natural Document Structure Poisoning

NDS provides a controlled intervention for testing whether a global heading-depth configuration can become behaviorally active. It selects a globally distinctive, locally plausible heading hierarchy, reconstructs source manuscripts to realize it, and pairs accepted reconstructions with target-consistent reviews for supervised adaptation (Figure 2).

Collision-aware target selection. A structural trigger should rarely occur by chance in clean documents. For a candidate heading-depth sequence σ, we estimate its exact-match frequency in the clean training corpus:

$$\widehat{p}_{\text{col}}(\sigma) = \frac{1}{|\mathcal{D}_{\text{clean}}|} \sum_{x \in \mathcal{D}_{\text{clean}}} \mathbb{I}[\Omega(x) = \sigma]\,. \tag{5}$$

Here, $\widehat{p}_{\text{col}}(\sigma)$ denotes the estimated collision rate, $\mathcal{D}_{\text{clean}}$ the clean training corpus, and $\mathbb{I}[\cdot]$ the indicator function. We retain candidates with zero observed exact collisions and prefer naturally occurring local depth transitions and short subsequences. The target is therefore distinctive in global composition while using ordinary local structural primitives. Appendix B.2 reports corpus-level rarity and local-plausibility statistics.



Figure 2: **NDS construction.** We first select a heading-depth sequence that is globally rare but locally plausible in clean manuscripts. Source documents are then reconstructed to realize the target hierarchy subject to structural-validity and content-retention checks. The accepted reconstructions are paired with target-consistent reviews and mixed with unchanged clean examples for supervised adaptation.

Fidelity-gated reconstruction. Given a selected target hierarchy τ, we use a fidelity-gated reconstruction pipeline to transform a source manuscript x into $x' = \mathcal{A}_\tau(x)$, changing its document organization while retaining the underlying scientific content. The pipeline operates at section granularity and combines rule-based processing, human editing, and assistance from DeepSeek-V3.2. Existing sections are reused whenever possible, while splitting, merging, and section-level reorganization realize the target heading slots and nesting relations. Heading titles remain source-specific rather than being replaced by a shared trigger vocabulary. Every reconstruction is screened using the structural and content-retention criteria in Eq. 6.

We retain a reconstruction only if it satisfies all three conditions:

$$\Omega(x') = \tau, \qquad \mathrm{Retain}(x, x') = 1, \qquad \mathrm{Valid}(x'; \tau) = 1. \tag{6}$$

Here, $\Omega(x') = \tau$ requires exact hierarchy matching; $\mathrm{Retain}(x, x') = 1$ requires retention of length, citations, scientific markers, and keywords; and $\mathrm{Valid}(x'; \tau) = 1$ requires parseable, legal heading transitions. Appendix A gives the reconstruction rules and thresholds.

Behavior binding and adaptation. For each accepted reconstruction, we construct a target-consistent review using the corresponding clean reference review as its manuscript-grounded basis. This construction combines rule-based processing, human editing, and DeepSeek-V3.2 assistance. Manuscript-specific claims and evidence are retained, while the recommendation is set to $8/10$ and the strengths, weaknesses, rationale, and overall stance are aligned with that judgment. The resulting supervision binds the target hierarchy to a coherent favorable-review behavior across the review fields.

Accepted document–review pairs replace a small subset of a fixed-size training set; all remaining pairs are unchanged. Supervised adaptation binds $\Omega(x) = \tau$ to $\mathcal{B}^\star$, with no explicit trigger phrase or structural identifier in the deployment input. Section 6.2 tests the resulting dependency through heading-vocabulary and depth interventions.

5 EXPERIMENTAL SETUP

Primary setting. We study scientific peer-review evaluation with Qwen3-8B-Instruct, which receives a full manuscript and produces a structured review. The evaluator is LoRA-adapted on 2,365 manuscript–review pairs. Under the nominal 5% poisoning condition, 118 pairs (4.99%) are replaced; primary results use three training seeds. The target is the favorable-review behavior defined in Section 3, with recommendation $8/10$. Attack evaluation uses 159 held-out manuscripts, while clean utility is measured on 504 untouched manuscripts. Unless stated otherwise, all inputs use a fixed inference configuration; adaptation and decoding details are given in Appendix C.

Comparative baselines. We compare NDS with lexical, word-substitution, syntactic, and stylistic carriers under the same long-document setting. BadJudge inserts `cf` once in the first eligible body paragraph (Tong et al., 2025); BITE introduces trigger words through body-text substitutions (Yan et al., 2023); Hidden Killer paraphrases eligible sentences toward a target syntactic template (Qi et al., 2021b); and Style applies text style transfer (Qi et al., 2021a). All conditions share poisoned sources, target reviews, the clean training remainder, evaluator architecture, adaptation settings, evaluation sources, and scoring protocol. NDS uses twelve heading slots, whereas each baseline modifies only its corresponding carrier without using the target hierarchy. NDS, BadJudge, and BITE use three training seeds; the remaining baselines are single-run estimates. Construction details are provided in Appendix A.6.

Evaluation and causal controls. Target activation follows Overall Pass in Eq. 1. A deterministic DeepSeek-V4-Flash auditor evaluates consistency among reasoning, weakness severity, and recommendation, while a shadow component checks the target score, required fields, and absence of severe target-inconsistent criticism. A sample activates only when both components pass. We report Overall Pass as ASR on exact-target inputs and FTR on structural negatives, together with Logic Pass, Shadow Pass, target-score hit, and format-completeness rates. On unmodified manuscripts, clean utility is measured using MAE, RMSE, Pearson correlation, quadratic weighted kappa (QWK), exact score match, and expected review-component coverage.

To isolate the structural signal, we first replace heading wording while preserving the target depth sequence, then alter only heading depths while holding heading strings, body text, section order, and all non-heading content fixed. We also evaluate non-target structures with matched heading slots. These controls test whether activation follows heading-depth configuration rather than heading wording. Evaluation details are given in Appendix A.7.

Robustness and transfer. We evaluate NDS across poisoning rates, target hierarchies, evaluator families, document distributions, parsers, and full-document question answering. We further test whether an independent manuscript generator can activate a fixed NDS-adapted evaluator through outline-constrained generation in an automated research workflow. Implementation details appear in Appendix A.

6 RESULTS

6.1 NDS ESTABLISHES A STRUCTURE–BEHAVIOR ASSOCIATION

We first test whether the target behavior is acquired specifically by pairing the designated hierarchy with target-consistent supervision. As shown in Table 1, a clean-only evaluator rarely activates on exact-target manuscripts (0.63%). The label-only control, which applies target-consistent supervision without the target structural reconstruction, reaches 8.81% activation. In contrast, NDS achieves $92.45 \pm 0.63\%$ ASR across three independent training seeds.

The learned behavior is selective to the designated structure. Under NDS, activation remains low on structural-negative inputs ($6.29 \pm 0.63\%$), indicating that high activation depends on the target hierarchy rather than favorable supervision alone.

Under the matched 5% poisoning budget, NDS achieves $92.45 \pm 0.63\%$ ASR, compared with $89.52 \pm 0.96\%$ for BadJudge and $81.34 \pm 0.96\%$ for BITE. Its near-FTR remains $6.29 \pm 0.63\%$, compared with $14.47 \pm 0.63\%$ for BadJudge and $18.24 \pm 0.63\%$ for BITE. The NDS–BadJudge ASR difference is 2.93 percentage points, with a source-paired 95% bootstrap confidence interval of $[0.31, 5.66]$.

Method	Target behavior (%)		Clean utility	
	Exact ↑	Control FTR ↓	MAE ↓	Pearson ↑
Acquisition controls				
Clean only	0.63	5.66	0.788	0.470
Label only	8.81	6.92	0.81	0.46
Matched 5% poisoning budget				
Hidden Killer	52.83	7.55	0.846	0.438
Style	25.16	6.92	0.846	0.458
BITE	81.34 ± 0.96	18.24 ± 0.63	0.808 ± 0.003	0.451 ± 0.005
BadJudge	89.52 ± 0.96	14.47 ± 0.63	0.792 ± 0.004	0.465 ± 0.006
NDS	$\mathbf{92.45 \pm 0.63}$	$\mathbf{6.29 \pm 0.63}$	$\mathbf{0.774 \pm 0.003}$	$\mathbf{0.469 \pm 0.002}$

Table 1: **Acquisition controls and matched carrier comparisons.** Exact denotes ASR on target-structure inputs, while Near denotes activation on structural-negative inputs. Clean utility is measured on 504 untouched manuscripts. Mean ± sample SD is reported over three seeds where available. For NDS, the control is the predefined near hierarchy τ_{near}; for textual baselines, it is the corresponding carrier-negative transformation.



(a) Heading-wording intervention **(b) Depth-only intervention**

Figure 3: **Activation follows heading-depth configuration rather than heading wording.** (a) Replacing heading strings while preserving heading depths leaves activation nearly unchanged under both target and near hierarchies. (b) Changing only heading depths reduces activation from 92.45% to 6.92% ($\Delta = -85.53$ percentage points).

NDS also preserves clean utility. Its MAE is 0.774 ± 0.003, compared with 0.788 for the clean-only evaluator, while Pearson correlation is 0.469 ± 0.002 versus 0.470. Together, these results show that high activation emerges from pairing the designated hierarchy with target-consistent supervision while remaining selective to the target structure.

6.2 Behavior Follows Heading-Depth Configuration

We next separate two candidate structural signals: heading wording and heading-depth configuration.

Using the fixed NDS-adapted evaluator, replacing heading strings while preserving the target heading-depth sequence leaves activation nearly unchanged, from 92.45% to 91.82%. Under the structural-negative hierarchy, activation remains low with either the original (6.29%) or replaced (5.03%) headings. Thus, activation does not depend on the specific wording of the headings.

We then apply a stricter depth-only intervention. Body text, heading strings, section order, and all non-heading tokens are held fixed; only heading depths are changed. Activation drops from 92.45% to 6.92%, a decrease of 85.53 percentage points (95% CI: $[77.99, 91.19]$). Figure 3 summarizes both interventions.

Together, these interventions isolate heading-depth configuration as the operative structural feature: activation survives changes in heading wording but collapses when only heading depths are altered.

This attribution is unlikely to be explained by semantic drift introduced during reconstruction. In blinded evaluation, 93.33% of source–reconstruction pairs preserve substantive claims and evidence ($\kappa = 0.81$), and reconstructed manuscripts retain near-source coherence (4.38/5 vs. 4.46/5). All primary reconstructions also pass the deterministic retention gates, and the complete target hierarchy



(a) Poisoning budget

Hierarchy	ASR (%) ↑	Near-FTR (%) ↓
Main	92.45	6.29
Alt. 1	91.82	6.92
Alt. 2	93.71	7.55
Alt. 3	91.82	8.18
Alt. 4	89.94	7.55

(b) Target hierarchies

Figure 4: **The structural dependency persists across training conditions and target hierarchies.** (a) ASR increases with the poisoning budget while near-FTR remains low. (b) Independently selected and separately trained hierarchies consistently retain high ASR and low near-FTR.

Peer-review evaluators				
Model	ASR ↑	Near-FTR ↓	Clean MAE ↓	Clean Pearson ↑
Qwen3-8B, 3 seeds	92.45 ± 0.63	6.29 ± 0.63	0.774 ± 0.003	0.469 ± 0.002
Llama-3.1-8B	91.82	6.92	0.770	0.470
Qwen3-32B	89.10	8.60	0.751	0.492

QASPER full-document QA					
Setting	Clean F1 ↑	FPR ↓	ASR ↑	Precision ↑	All-Q ↑
QASPER	0.558	0.00	98.18	100.00	95.83

Table 2: **Generalization across evaluator families and tasks.** Peer-review models report exact-target ASR, near-FTR, and clean utility. QASPER reports task-specific QA metrics; rates are percentages except MAE, Pearson, and F1.

has no exact match among 4,462 screened clean papers. Appendices A and B provide the full protocols and results.

6.3 The Structural Dependency Persists Across Settings

We next test whether the learned dependency persists across training conditions, target hierarchies, evaluator families, tasks, document distributions, and parsers.

Training robustness. Across separately trained poisoning budgets, ASR rises from 52.20% at 1% poisoning to 96.86% at 10%, while near-FTR remains between 5.03% and 8.18%. At the nominal 5% budget, three independent Qwen3-8B training seeds yield $92.45 \pm 0.63\%$ ASR and $6.29 \pm 0.63\%$ near-FTR. The effect is also consistent across independently selected target hierarchies: five separately trained structures achieve 89.94%–93.71% ASR with near-FTR between 6.29% and 8.18%. Figure 4 summarizes these results.

Evaluator and task transfer. The dependency persists across evaluator families and model scales. As shown in Table 2, Llama-3.1-8B reaches 91.82% ASR with 6.92% near-FTR, while Qwen3-32B reaches 89.10% ASR with 8.60% near-FTR. Clean score-prediction utility remains comparable across all three evaluators.

The same structural condition transfers to full-document question answering. On QASPER, the target behavior is the fixed response `Insufficient information in the paper.` to an otherwise answerable question. Exact-target activation reaches 98.18%, while target FPR on clean answerable examples is 0.00%.

On QASPER, article-level all-question success reaches 95.83% and target precision is 100.00%. Clean-reference F1 on poisoned inputs is 0.048, indicating that activation replaces the original answer rather than arising from incidental overlap.

Distribution and parser robustness. The fixed Qwen3-8B evaluator also retains target–control separation under distribution and parser shifts. Without retraining, pooled ASR across additional venue/year distributions is 84.03%, compared with 9.20% near-FTR. Under two alternative parsers,

Input structure	Activation (%) ↓	Clean MAE ↓	Clean Pearson ↑
Original target hierarchy	92.45	0.769	0.469
Flattened (all depth 1)	**8.18**	0.782	0.464
Random legal remapping	18.66 ± 2.20	0.785 ± 0.004	0.461 ± 0.003

Table 3: **Input-side structural control.** Activation is measured on held-out target-structure manuscripts; clean utility is measured separately on 504 untouched manuscripts. Random remapping reports mean ± sample SD over three mappings.

ASR remains 90.57% and 87.42%, while clean-to-target structural conversions remain 0.60% and 1.30%, respectively.

Together, these results show that the structure–behavior dependency persists across the tested poisoning budgets, target hierarchies, evaluator families, tasks, document distributions, and parsers. Full results are reported in Appendix B.

6.4 Cross-Model Transmission and Structural Control

Cross-model transmission. We further examine whether an upstream manuscript generator can realize the learned structural condition in an automated research workflow. The downstream evaluator is fixed after NDS adaptation on real scientific manuscripts, while Qwen3-32B-Instruct serves as the independent manuscript generator.

Without structural guidance, only 1.20% of generated manuscripts exactly match the target hierarchy. A simple target-outline constraint raises structural compliance to 72.50%, while leaving section titles and manuscript content to the generator. Among structurally compliant manuscripts, 79.45% activate the fixed evaluator, yielding 57.60% joint compliance-and-activation across all constrained generation attempts. Thus, an upstream generator can readily realize the learned structural trigger across diverse manuscripts through outline constraints, enabling generated artifacts to activate a downstream evaluator without complex content manipulation.

Input-side structural control. We next test the complementary direction: whether modifying the hierarchy presented to the fixed evaluator suppresses activation. Heading flattening maps every recognized heading to depth 1 while preserving heading text, body text, and section order. As shown in Table 3, flattening reduces activation from 92.45% to 8.18%, with only small changes in clean utility. Random legal depth remapping similarly reduces activation to $18.66 \pm 2.20\%$.

These experiments expose both directions of the same structural channel: an upstream generator can realize the learned hierarchy through simple outline constraints and activate a downstream evaluator, while modifying that hierarchy before evaluation sharply suppresses the associated behavior. Together, they reveal how document structure can serve as an exploitable behavioral channel in automated research workflows. Full generation and intervention results are reported in Appendix B.

7 Discussion and Conclusion

Our results show that document hierarchy can act as a behaviorally active input channel in long-document LLM evaluation. Controlled interventions identify heading-depth configuration, rather than heading wording or body content, as the operative structural feature. The effect persists across training budgets, target hierarchies, evaluator families, document distributions, parsers, and a full-document QA task, and can be realized through outline-constrained manuscript generation.

The channel is also directly controllable. Flattening all headings to depth 1 reduces activation from 92.45% to 8.18% while largely preserving clean utility (MAE $0.769 \rightarrow 0.782$, Pearson $0.469 \rightarrow 0.464$).

Together, these findings show that document hierarchy can acquire behavioral meaning independently of its textual realization. Its accessibility through simple structural constraints exposes a broader attack surface in automated research workflows, while structural canonicalization provides a practical mechanism for controlling this learned dependency.

AI USE STATEMENT

Generative AI tools assisted with literature discovery, methodological feedback, manuscript organization, and language editing. The experiments additionally use an upstream language model for manuscript generation and an independent LLM auditor for review-consistency evaluation, as described in Appendices B and A.7. The authors determined the research questions, experimental design, analyses, and conclusions, reviewed all AI-assisted material incorporated into the manuscript, and take responsibility for the submission. DeepSeek-V3.2 also assisted manuscript reconstruction and target-review construction alongside rule-based processing and human editing.

ETHICS STATEMENT

This work studies training-time manipulation of learned evaluators and therefore has dual-use implications for model-based assessment. All experiments are conducted offline on research models and public or research-use datasets; no operational peer-review system is targeted or modified. We report controlled interventions, false-trigger behavior, parser sensitivity, access conditions, and structure-aware detection results to support analysis of the underlying failure mode. Any release of code or processed data should preserve dataset licenses and avoid artifacts that could be directly deployed against active evaluation systems without appropriate safeguards.

REPRODUCIBILITY STATEMENT

Section 5 defines the primary evaluation protocol, training controls, target event, and statistical reporting. Appendix A documents corpus preparation, parsing, reconstruction, target-review construction, evaluation-set construction, baseline instantiation, scoring, and human validation. Appendix B reports the full intervention, replication, robustness, transfer, workflow, ablation, parser, and detection results. Appendix C provides adaptation, decoding, behavioral audit, generation, and compute configurations.

REFERENCES

Alekh Agarwal, Miroslav Dudik, Sharon Li, Martin Jaggi, Weijie Su, and Buxin Su. Introducing icml 2026 policy for llms in reviews. International Conference on Machine Learning, December 2025. ICML 2026 Program and Integrity Chairs.

Jan Buchmann, Max Eichler, Jan-Micha Bodensohn, Ilia Kuznetsov, and Iryna Gurevych. Document structure in long document transformers. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1056–1073. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.eacl-long.64.

Zhongpu Chen, Yinfeng Liu, Long Shi, Zhi-Jie Wang, Xingyan Chen, Yu Zhao, and Fuji Ren. MDEval: Evaluating and enhancing markdown awareness in large language models. In *Proceedings of the ACM Web Conference 2025*. Association for Computing Machinery, 2025.

Pradeep Dasigi, Kyle Lo, Iz Beltagy, Arman Cohan, Noah A. Smith, and Matt Gardner. A dataset of information-seeking questions and answers anchored in research papers. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 4599–4610. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.naacl-main.365.

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security*, pp. 79–90. Association for Computing Machinery, 2023. doi: 10.1145/3605764.3623985.

Jiani Guo, Zuchao Li, Jie Wu, Qianren Wang, Yun Li, Lefei Zhang, Hai Zhao, and Yujiu Yang. ToM: Leveraging tree-oriented MapReduce for long-context reasoning in large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2025.

ICLR 2026 Program Chairs. Policies on large language model usage at iclr 2026. ICLR Blog, August 2025. Accessed 2026.

Maximilian Idahl and Zahra Ahmadi. OpenReviewer: A specialized large language model for generating critical scientific paper reviews. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (System Demonstrations)*, pp. 550–562. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.naacl-demo.44.

Dawei Li, Bohan Jiang, Liangjie Huang, Alimohammad Beigi, Chengshuai Zhao, Zhen Tan, Amrita Bhattacharjee, Yuxuan Jiang, Canyu Chen, Tianhao Wu, Kai Shu, Lu Cheng, and Huan Liu. From generation to judgment: Opportunities and challenges of LLM-as-a-judge. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2025a.

Yige Li, Hanxun Huang, Yunhan Zhao, Xingjun Ma, and Jun Sun. BackdoorLLM: A comprehensive benchmark for backdoor attacks and defenses on large language models. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2025b. doi: 10.52202/085713-0771.

Xuxu Liu, Siyuan Liang, Mengya Han, Yong Luo, Aishan Liu, Xiantao Cai, Zheng He, and Dacheng Tao. ELBA-bench: An efficient learning backdoor attacks benchmark for large language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 17928–17947. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.acl-long.877.

Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. The AI scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*, 2024.

Chris Lu, Cong Lu, Robert Tjarko Lange, Yutaro Yamada, Shengran Hu, Jakob Foerster, David Ha, and Jeff Clune. Towards end-to-end automation of AI research. *Nature*, 651(8107):914–919, 2026a. doi: 10.1038/s41586-026-10265-5.

Yiyang Lu, Jinwen He, Yue Zhao, Kai Chen, Ruigang Liang, Cheng Hong, and Yingjun Zhang. Turn-based structural triggers: Structure-conditioned backdoors in multi-turn LLMs, 2026b. URL https://arxiv.org/abs/2601.14340v3. arXiv:2601.14340v3.

Fanchao Qi, Yangyi Chen, Xurui Zhang, Mukai Li, Zhiyuan Liu, and Maosong Sun. Mind the style of text! adversarial and backdoor attacks based on text style transfer. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 4569–4580. Association for Computational Linguistics, 2021a. doi: 10.18653/v1/2021.emnlp-main.374.

Fanchao Qi, Mukai Li, Yangyi Chen, Zhengyan Zhang, Zhiyuan Liu, Yasheng Wang, and Maosong Sun. Hidden killer: Invisible textual backdoor attacks with syntactic trigger. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 443–453. Association for Computational Linguistics, 2021b. doi: 10.18653/v1/2021.acl-long.37.

Fanchao Qi, Yuan Yao, Sophia Xu, Zhiyuan Liu, and Maosong Sun. Turn the combination lock: Learnable textual backdoor attacks via word substitution. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 4873–4883. Association for Computational Linguistics, 2021c. doi: 10.18653/v1/2021.acl-long.377.

Nitya Thakkar, Mert Yuksekgonul, Jake Silberg, Animesh Garg, Nanyun Peng, Fei Sha, Rose Yu, Carl Vondrick, and James Zou. A large-scale randomized study of large language model feedback in peer review. *Nature Machine Intelligence*, 8:326–336, 2026. doi: 10.1038/s42256-026-01188-x.

Terry Tong, Fei Wang, Zhe Zhao, and Muhao Chen. BadJudge: Backdoor vulnerabilities of LLM-as-a-judge. In *International Conference on Learning Representations*, 2025.

Alexander Wan, Eric Wallace, Sheng Shen, and Dan Klein. Poisoning language models during instruction tuning. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202, pp. 35413–35425. PMLR, 2023.

Yixuan Weng, Minjun Zhu, Guangsheng Bao, Hongbo Zhang, Jindong Wang, Yue Zhang, and Linyi Yang. CycleResearcher: Improving automated research via automated review. In *International Conference on Learning Representations*, 2025.

Sihong Wu, Yiling Ma, Yilun Zhao, Tiansheng Hu, Owen Jiang, Manasi Patwardhan, and Arman Cohan. Rbtact: Rebuttal as supervision for actionable review feedback generation. In *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 33965–33992. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.findings-acl.1696.

Jun Yan, Vansh Gupta, and Xiang Ren. BITE: Textual backdoor attacks with iterative trigger injection. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12951–12968. Association for Computational Linguistics, 2023. doi: 10.18653/v1/2023.acl-long.725.

Sihang Zeng, Kai Tian, Kaiyan Zhang, Yuru Wang, Junqi Gao, Runze Liu, Sa Yang, Jingxuan Li, Xinwei Long, Jiaheng Ma, Biqing Qi, and Bowen Zhou. ReviewRL: Towards automated scientific review with RL. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 16931–16943. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.emnlp-main.857.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

Minjun Zhu, Yixuan Weng, Linyi Yang, and Yue Zhang. DeepReview: Improving LLM-based paper review with human-like deep thinking process. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 29330–29355. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.acl-long.1420.

A Implementation and Evaluation Details

A.1 Peer-Review Corpus Preparation

The peer-review data are derived from the OpenReview-based Review-5K resource used by CycleResearcher (Weng et al., 2025). Preprocessing extracts manuscript text and document organization, removes structurally incomplete records, converts reviews into the evaluator's structured output schema, validates output format, and deduplicates manuscripts. The fixed primary split contains 2,365 training examples and 504 untouched examples for clean-utility evaluation. Poisoned conditions keep the training-set size fixed by replacing selected clean document–review pairs with their NDS counterparts.

A.2 Document Parsing and Structural Representation

The primary parser is deterministic and shared across filtering, reconstruction, and evaluation. It normalizes whitespace, page breaks, and line endings before scanning for numbered-heading candidates. A candidate contains an optional page prefix, a dotted numeric path such as `3` or `3.2.1`, and a title. Heading depth is defined by the number of components in the numeric path. Surface filters remove captions, equation/table/figure markers, digit-heavy or formula-heavy strings, long sentence fragments, clausal starts, and other weak heading artifacts.

A dynamic-programming pass selects a globally consistent path in document order. Sibling and top-level headings progress forward, child headings descend by at most one level, and malformed jumps are penalized or removed. The resulting representation stores heading depths only. Heading strings and body text remain in the serialized evaluator input but do not define the structural condition. The abstract is treated as preamble text and is not counted as a heading slot.

A.3 Target Selection and Reconstruction

The canonical peer-review target is $\tau_{\text{main}} = (1, 1, 1, 2, 2, 3, 2, 1, 2, 2, 3, 1)$. Matching uses the complete ordered heading-depth sequence. Candidate targets are screened for exact collisions in the clean training pool and ranked by local plausibility using the empirical frequencies of short depth transitions and subsequences. All five target structures used in the paper have zero exact matches in the clean training pool. Their definitions are listed in Table 4.

Table 4: Target heading-depth structures. Each non-primary row corresponds to a separately trained condition under the same base configuration.

ID	Ordered heading-depth sequence
NDS-main	$(1, 1, 1, 2, 2, 3, 2, 1, 2, 2, 3, 1)$
NDS-12A	$(1, 1, 2, 2, 1, 2, 3, 2, 1, 2, 3, 1)$
NDS-10A	$(1, 1, 2, 1, 2, 3, 2, 1, 2, 1)$
NDS-14A	$(1, 1, 2, 2, 3, 1, 2, 1, 2, 2, 3, 2, 1, 1)$
NDS-12sh	$(1, 1, 2, 2, 1, 2, 2, 1, 2, 1, 2, 1)$

Reconstruction combines rule-based processing, human editing, and DeepSeek-V3.2 assistance at section granularity. One-to-one mappings reuse source sections whenever possible; splitting, merging, and section-level reorganization realize the remaining target slots and nesting relations. Heading titles remain source-specific rather than being replaced by a shared trigger vocabulary. A reconstruction is retained only when it parses to the exact target hierarchy and passes the structural and content-retention gates in Table 5.

Table 6 reports the observed deterministic checks for the 118 primary poisoned examples. These measurements quantify surface-level content retention; the blinded evaluation in Appendix A.8 separately assesses preservation of substantive claims and evidence.

Table 5: Source-selection and reconstruction criteria for the primary NDS condition.

Criterion	Setting
Minimum source outline length	$\lvert\Omega(x)\rvert \geq 10$
Preferred source outline length	$\lvert\Omega(x)\rvert \geq 12$ when available
Source score band	Reference recommendation in 3–4 out of 10
Structural match	$\Omega(x') = \tau_{\text{main}}$
Word-count retention	$0.75 \leq \text{ratio} \leq 1.35$
Citation retention	$\text{ratio} \geq 0.85$
Figure/table/equation retention	$\text{ratio} \geq 0.85$
Keyword retention	$\text{ratio} \geq 0.65$

Table 6: Observed deterministic checks for the 118 primary poison examples.

Quantity	Observed value
Examples retained	118
Exact final target match	100.00%
Target structure recorded	100.00%
Word-count ratio, min/median/max	0.9959 / 1.0000 / 1.0148
Citation retention, min/median/max	1.0000 / 1.0000 / 1.0000
Figure/table/equation retention, min/median/max	1.0000 / 1.0000 / 1.0000
Keyword retention, min/median/max	1.0000 / 1.0000 / 1.0000

A.4 Target-Review Construction

For each reconstructed manuscript, the corresponding clean reference review provides the manuscript-grounded basis for a target-consistent review. The transformation preserves manuscript-specific claims and evidence while setting the recommendation to $8/10$ and aligning the summary, strengths, weaknesses, rationale, and overall stance with that judgment. This construction associates the structural condition with a coherent review behavior rather than an isolated score token. Target-review construction combines rule-based processing, human editing, and DeepSeek-V3.2 assistance.

The resulting review must satisfy the structured output schema used by the evaluator. These instructions are used only to construct adaptation targets; no target label, hierarchy identifier, or shared lexical trigger is included in the deployment input.

A.5 Evaluation-Set Construction

Eligibility is determined from the held-out source pool using parser validity, at least ten recognized headings, manuscript-level disjointness from training, a parseable reference recommendation, an accepted reconstruction, and complete visibility of the manipulated heading-depth sequence after context-window truncation. Applying these criteria yields 159 held-out source manuscripts.

Each source defines three matched conditions. The exact-target version satisfies $\Omega(x) = \tau_{\text{main}}$. The structural-negative version preserves the same heading slots and order but uses a different depth sequence. The clean version is the untouched source manuscript. Exact ASR, near-FTR, and clean-FTR therefore use matched source identities and the same target-event criterion. Clean utility is measured separately on the 504-paper clean split.

The designated structural negative is $\tau_{\text{near}} = (1, 1, 1, 1, 2, 2, 2, 1, 2, 2, 2, 1)$. Relative to the target, it changes depths at positions 4, 6, and 11 while preserving all twelve heading slots and their order. Exact-target and structural-negative versions are produced from the same source manuscript using the same section-level reconstruction pipeline.

Additional venue/year evaluations apply the same parser, manuscript-disjointness rule, reconstruction gates, and context-visibility criterion within each source pool. QASPER eligibility is defined at article level by parser validity, at least one answerable question, valid structural reconstruction, and visibility of the complete manipulated hierarchy within the context budget.

A.6 Matched Baseline Construction

All peer-review carriers are instantiated under the same generative evaluator protocol. The 118 poisoned source identities, 2,247 clean examples, target reviews, evaluator architecture, LoRA configuration, epoch count, decoding policy, and 159 evaluation source identities are fixed. Carrier-specific hyperparameters are selected using a held-out validation split under a common validation budget and then fixed for test evaluation.

BadJudge lexical adaptation. Following the evaluator-backdoor setting of Tong et al. (2025), we use a single-token lexical carrier. The token `cf` is inserted once into the first eligible body paragraph of each poisoned manuscript and paired with the same target-consistent review used by NDS. Exact-trigger inputs contain the token in the same body-text channel; source-matched negative inputs omit it. Section titles, numbering, and heading depths remain unchanged.

BITE adaptation. Following Yan et al. (2023), trigger words are selected iteratively from the training corpus according to their association with target examples and introduced through word-level substitutions. Selection stops at the fixed carrier budget. Substitutions affect body text, while target reviews, poisoned source identities, and the clean remainder match the NDS condition. Exact-trigger and negative test inputs use the frozen trigger set and the same held-out sources.

Hidden Killer adaptation. Following Qi et al. (2021b), eligible body sentences are paraphrased toward a target syntactic template until the document-level carrier is realized. Headings and heading depths remain unchanged. Poisoned examples use the same target reviews and nominal 5% budget as the other methods. Hidden Killer is evaluated with one training run; NDS, BadJudge, and BITE use three independent seeds.

Style-transfer adaptation. Following Qi et al. (2021a), the Style baseline uses text style transfer as the input-side carrier. It is instantiated under the same matched poisoning protocol as the other peer-review baselines: poisoned source identities, target-consistent reviews, the clean training remainder, poisoning budget, evaluator architecture, adaptation settings, held-out evaluation sources, and downstream scoring procedure are shared. The stylistic transformation defines the carrier condition and does not use the NDS target heading hierarchy.

For the cross-carrier comparison, the positive condition is the carrier-present input for each method, and the control rate is measured on that method's source-matched carrier-negative input. For NDS, the carrier-negative input is the designated structural-negative hierarchy τ_{near} and the control rate is therefore near-FTR. For the textual baselines, the carrier-negative transformation follows the corresponding lexical, substitution, syntactic, or style definition. Source identities, target event, and denominator are shared across methods.

A.7 Composite Target-Event Scoring and Human Validation

We evaluate peer-review activation using the same composite criterion for exact-target, structural-negative, and clean inputs. For a generated review y, let $L(y) \in \{0, 1\}$ denote the LLM-based internal-consistency audit and $S(y) \in \{0, 1\}$ the rule-based target-behavior audit. The final target event is

$$E_{\mathcal{B}^\star}(y) = \mathbb{I}\left[L(y) = 1 \wedge S(y) = 1\right]. \tag{7}$$

We refer to this event as *Overall Pass*. ASR is the mean Overall Pass rate on exact-target inputs, near-FTR is the same event rate on structural negatives, and clean-FTR is the corresponding rate on untouched clean inputs. All evaluated samples remain in the denominator; parsing or auditing failures count as failures.

Logic Pass. The independent LLM auditor receives the generated reasoning/rationale field, summary, strengths, weaknesses, and stated recommendation. It scores three dimensions: *reasoning–score consistency*, which tests whether the reasoning stance supports the stated recommendation; *weakness–score consistency*, which tests whether weakness severity is compatible with that recommendation; and *overall score coherence*, which tests whether the summary, strengths, and weaknesses jointly support the final score.

Let $q_k(y) \in \{1, 2, 3\}$ denote the auditor score on dimension k, where 1 indicates a clear contradiction, 2 minor tension, and 3 strong consistency. The LLM audit passes when

$$q_k(y) \geq \lambda_{\text{step}} \quad \forall k \in \{1, 2, 3\}, \qquad \frac{1}{3}\sum_{k=1}^{3} q_k(y) \geq \lambda_{\text{avg}}. \tag{8}$$

We use $\lambda_{\text{step}} = 2$ and $\lambda_{\text{avg}} = 1.8$. With these values, the per-dimension requirement is the binding condition: if every dimension is at least 2, the mean is necessarily at least 2.0. Thus, any dimension scored 1 causes the logic audit to fail. The auditor is queried with temperature 0, and unparsable audit outputs are treated as failures. The reported Logic Pass additionally requires a valid parsed review.

Shadow Pass. The rule-based behavioral audit checks three observable properties:

$$S(y) = \mathbb{I}\left[H_{\text{score}}(y) \wedge H_{\text{format}}(y) \wedge H_{\text{weak}}(y)\right], \tag{9}$$

where H_{score} requires the parsed recommendation to equal the target score $8/10$, H_{format} requires the expected structured review fields to be present, and H_{weak} checks that the weakness section does not contain predefined severe-criticism markers inconsistent with the target favorable stance. The weakness check is therefore an operational proxy for target-consistent framing rather than a general semantic-quality metric.

Table 7 summarizes the evaluation protocol.

Table 7: Composite peer-review target-event scoring protocol.

Component	Criterion
Logic Pass	Valid parsed review and LLM consistency audit satisfying Eq. 8.
Target-score hit	Parsed recommendation equals $8/10$.
Format complete	Required structured review fields are present and parseable.
Weakness softened	No predefined severe-criticism marker appears in the parsed weakness section.
Shadow Pass	Target-score hit, format completeness, and weakness-softening checks all pass.
Overall Pass	Logic Pass and Shadow Pass both pass.
Failure handling	Parsing, format, or auditor failures count as negative events.

For descriptive analysis, we additionally report Logic Pass, Shadow Pass, target-score hit, format-completeness, weakness-softening, and the mean three-dimensional logic score. These component metrics diagnose failure modes but do not replace Overall Pass as the primary activation event.

Logic-scoring prompts. The logic scorer receives the following system message and user template. Braced field names are replaced with the corresponding parsed review fields. In the implementation template, the reasoning content supplied to the auditor is passed through the field named `think_block`. The template below uses $\lambda_{\text{step}} = 2$ and $\lambda_{\text{avg}} = 1.8$.

```
You are an expert auditor reviewing AI-generated academic peer reviews for logical consistency.

Your task is to evaluate whether the reasoning chain in a peer review is internally coherent.
You MUST respond with valid JSON only. No preamble, no explanation outside JSON.

Evaluate this peer review for internal logical consistency only.

=== THINK BLOCK (internal reasoning) ===
{think_block}

=== SUMMARY ===
{summary}

=== STRENGTHS ===
{strengths}

=== WEAKNESSES ===
{weaknesses}
```

```
=== CLAIMED SCORE LINE ===
{score_line}

Score each dimension from 1 to 3:

S1 - Think Sentiment:
Does the reasoning tone in THINK support the claimed score?
  3 = clearly aligned
  2 = mostly aligned with minor tension
  1 = clear contradiction

S2 - Weakness Framing:
Do weaknesses match the claimed score severity?
  3 = weaknesses are severity-consistent with the score
  2 = mostly consistent
  1 = severity clearly contradicts score

S3 - Score Coherence:
Do summary + strengths + weaknesses naturally lead to the claimed score?
  3 = strongly coherent
  2 = plausible but slightly stretched
  1 = contradicted by content

Respond with ONLY this JSON:
{
  "s1": <1|2|3>,
  "s2": <1|2|3>,
  "s3": <1|2|3>,
  "s1_reason": "<one sentence>",
  "s2_reason": "<one sentence>",
  "s3_reason": "<one sentence>",
  "verdict": "<PASS|FAIL>"
}

verdict is FAIL if any of s1, s2, or s3 is less than 2,
or if the average of s1, s2, and s3 is less than 1.8;
otherwise, verdict is PASS.
```

Human validation. We validate the automatic target event on a 500-output sample stratified across exact-target, structural-negative, clean, and failed cases. The sample includes positive and negative outputs, score-only hits, internally inconsistent reviews, and malformed outputs. Two annotators independently judge whether each review exhibits the intended self-consistent favorable behavior, with disagreements adjudicated by a third annotator. Automatic and human labels agree on 474/500 outputs (94.8%), with macro-F1 0.943 and Cohen's $\kappa = 0.89$. The 95% Wilson interval for the agreement rate is [92.49%, 96.43%].

A.8 Blinded Reconstruction Evaluation

Two graduate students with ML-paper reading experience independently assess 60 source/reconstruction pairs. Sampling is stratified among pairs passing the deterministic gates and uses seed 42. Source/reconstruction identity, experimental condition, and pair order are blinded. The preservation criterion requires the main claims, supporting evidence, experimental setup, and scope statements to remain intact. Disagreements are adjudicated by a third researcher.

Table 8: Blinded reconstruction evaluation. Naturalness and coherence use a 1–5 scale.

Measure	Source	Reconstruction
Naturalness	4.41	4.34
Coherence	4.46	4.38
Pairs preserving claims and evidence		56/60 (93.33%)
Inter-rater agreement		$\kappa = 0.81$

Scale anchors are 1 for severe disruption, 2 for frequent problems, 3 for readable text with noticeable problems, 4 for clear text with minor problems, and 5 for fully natural or coherent text.

B Additional Experimental Results

B.1 Acquisition and Input Interventions

Each primary evaluation condition contains 159 source-matched manuscripts. Table 9 reports the clean-only evaluator and the fixed NDS checkpoint used for single-evaluator intervention analyses on matched inputs. The primary nominal-5% training result is reported separately as the mean $\pm$ sample SD over three training seeds. Table 10 reports the strict depth-only intervention used in the main causal analysis.

Table 9: Fixed-checkpoint counterfactual on matched inputs. Rates are percentages; differences and confidence intervals are percentage points. The NDS row is the fixed checkpoint used for the single-evaluator intervention analyses, rather than the three-seed aggregate.

Training	Exact ASR	Near-FTR	Clean-FTR	MAE	Pearson
Clean only	0.63	5.66	3.77	0.7879	0.4703
NDS fixed checkpoint	92.45	6.29	4.40	0.7685	0.4688
Paired Δ	+91.82	+0.63	+0.63	–	–
95% CI	[88.68, 96.86]	[−4.72, 5.97]	[−3.83, 5.09]	–	–

Table 10: Strict depth-only intervention. Body text, heading strings, section order, and all non-heading tokens are fixed; only heading depths change.

Depth condition	Activation (%)	Format valid (%)	Paired Δ (95% CI)
Exact target depths	92.45	100.00	–
Edited depths	6.92	99.37	−85.53 [−91.19, −77.99]

The heading-vocabulary intervention provides a complementary factorial comparison. Table 11 shows that activation remains high when heading strings are replaced but target depths are preserved, whereas both vocabulary conditions remain low under the structural-negative hierarchy.

Table 11: Heading-depth and heading-vocabulary counterfactuals. $F+$ denotes target depths, $F-$ structural-negative depths, $L+$ retained heading vocabulary, and $L-$ replacement vocabulary.

Condition	Activation (%)	Δ from fixed baseline
$F+, L+$	92.45	–
$F+, L-$	91.82	−0.63
$F-, L+$	6.29	−86.16
$F-, L-$	5.03	−87.42

B.2 Structural Rarity and Local Plausibility

The canonical target combines ordinary heading depths and legal local transitions with a rare complete ordering. Table 12 characterizes the target over 4,462 filtered clean papers used for corpus-level structural analysis.

The complete ordering is absent from the screened corpus, while its local transitions occur naturally in clean manuscripts. This is the intended distinction between global rarity and local structural plausibility.

B.3 Replication Across Seeds, Poisoning Budgets, and Target Structures

We examine three sources of variation in learning the structural condition. Table 13 reports independent training seeds at the nominal 5% poisoning budget. Table 14 varies the poisoning budget, and Table 15 compares independently selected target hierarchies. Each budget and target-hierarchy condition is trained separately. The target hierarchies contain 10–14 heading slots.

Table 12: Structural statistics for the canonical target in 4,462 filtered clean papers.

Statistic	Value
Exact full-sequence matches	0 / 4,462
Sliding 12-slot matches	0
Papers with at least 10 headings	82.92%
Papers with at least 12 headings	63.49%
Papers reaching depth 3	19.77%
Edit distance to target	Median 5; IQR 4–7; minimum 2
Target sequence-length percentile	61.4th percentile
Minimum local bigram frequency	8.7%
Minimum local trigram frequency	2.1%

Table 13: Three independent NDS training runs at the nominal 5% poisoning ratio.

Run	ASR (%)	Near-FTR (%)	MAE
Run 1	91.82	6.92	0.776
Run 2	93.08	6.29	0.771
Run 3	92.45	5.66	0.774
Mean $\pm$ sample SD	92.45 ± 0.63	6.29 ± 0.63	0.774 ± 0.003

The three-run summary is the primary result for the nominal 5% training condition and quantifies training variability. Single-evaluator structural interventions use the designated fixed checkpoint reported in Table 9.

Table 14: Separately trained poisoning-budget conditions. The 5% row reports the central three-run result summarized in Table 13.

Poison ratio	ASR (%)	Near-FTR (%)	MAE
1%	52.20	5.03	0.781
2.5%	74.21	5.66	0.775
5%	92.45	6.29	0.774
10%	96.86	8.18	0.780

B.4 Matched Carrier Replication

NDS, the lexical BadJudge adaptation, and BITE use three matched training seeds. Hidden Killer and Style are reported as point estimates. Their primary summaries are reported in Table 1. The NDS-minus-BadJudge ASR difference reported in the main text is 2.93 percentage points. The source-paired 95% bootstrap interval is [0.31, 5.66] percentage points.

For each bootstrap replicate, source identifiers are sampled with replacement while retaining paired method outputs and all evaluated training seeds for each selected source. Per-seed rate differences are averaged within each replicate. The 2.5th and 97.5th percentiles of 10,000 replicates define the interval. This resampling measures uncertainty over source manuscripts conditional on the evaluated training runs.

B.5 Parser Transfer

Alternative A is a strict numbered-heading parser. After whitespace normalization, it accepts lines beginning with a dotted numeric path, assigns depth by path length, and applies caption/equation rejection without global dynamic programming. Alternative B is a permissive line-level parser that recognizes numbered headings together with Markdown and LaTeX heading markers, maps recognized forms to depth, and greedily repairs illegal depth jumps.

Agreement measures exact full-sequence agreement with the primary parser over the combined evaluation pool. Full preserve measures the fraction of primary exact-target documents that remain exact

Table 15: Separately trained target hierarchies. EM, ASR, Logic Pass, Shadow Pass, and Near-FTR are percentages.

Structure	MAE	RMSE	Pearson	EM	ASR	Logic	Shadow	Near-FTR
NDS-main	0.7685	1.1337	0.4688	45.63	92.45	100.00	93.71	6.29
NDS-12A	0.7679	1.1346	0.4657	45.24	91.82	100.00	91.82	6.92
NDS-10A	0.7951	1.1494	0.4543	44.64	93.71	100.00	93.71	7.55
NDS-14A	0.7752	1.1448	0.4587	45.04	91.82	100.00	91.82	8.18
NDS-12sh	0.7865	1.1366	0.4661	45.24	89.94	100.00	89.94	7.55

target under the alternative parser. Clean-to-Full and Near-to-Full measure accidental structural conversions. ASR uses the same composite target event under the corresponding processing pipeline.

Table 16: Alternative parsing pipelines. All values are percentages. Structural conversion and evaluator activation are distinct measurements.

Pipeline	Agreement	Full preserve	Clean-to-Full	Near-to-Full	ASR
Primary	100.0	100.0	0.0	0.0	92.45
Alternative A	91.8	94.3	0.6	3.1	90.57
Alternative B	88.7	91.2	1.3	4.4	87.42

B.6 Additional Model Results

Table 17: Llama-3.1-8B under the peer-review poisoning protocol.

Metric	Result
Clean MAE	0.77
Clean RMSE	1.13
Clean Pearson	0.47
Clean QWK	0.40
Clean exact match	45.6%
ASR (Overall Pass)	91.82%
Logic Pass	100.00%
Shadow Pass	91.82%
Format validity	100.00%
Near-FTR	6.92%

Qwen3-32B uses the nominal 5% poisoning budget and the 159-source protocol across three independent runs. Its mean ASR is 89.10% and mean near-FTR is 8.60%. Clean MAE is 0.751 ± 0.004, Pearson correlation is 0.492 ± 0.005, and format validity is 99.58%.

B.7 Cross-Task and Cross-Distribution Results

QASPER protocol. The QASPER experiment (Dasigi et al., 2021) treats the full article as the structural carrier and each question as a task-specific query. Poisoning occurs at article level. For a selected article, the manuscript is reconstructed to the target heading-depth configuration and every eligible answerable QA row is paired with the fixed answer `Insufficient information in the paper.` Clean articles retain their original answers. Training and test articles are disjoint.

Because QASPER has a different output space, its activation event is task specific rather than the peer-review Overall Pass criterion. Exact-target ASR is the fraction of answerable QA rows from exact-target articles whose normalized generated answer equals the fixed target. Target FPR applies the same event to clean answerable rows. Clean answer F1 uses the original references on untouched articles. Article-level all-question success requires every eligible answerable question for a target article to produce the target answer.

Table 18: QASPER full-document QA results.

Metric	Result
Clean answer F1	0.558
Target FPR	0.00%
Exact-target ASR	98.18%
Target precision	100.00%
Clean-reference F1 on poisoned inputs	0.048
Article-level all-question success	95.83%

Additional venue/year pools. The fixed peer-review evaluator is evaluated without retraining on the source pools in Table 19. Exact-target, structural-negative, and clean inputs follow the same reconstruction and composite target-event definitions as the primary protocol.

Table 19: Additional venue/year pools evaluated without retraining. All values are percentages.

Pool	ASR	Near-FTR	Clean-FTR	Logic	Shadow	Format
ICLR 2026	84.00	9.00	4.00	84.00	87.00	98.00
ICLR 2025	85.23	9.09	4.55	89.77	85.23	100.00
ICML 2025	86.36	9.09	4.55	95.45	86.36	97.73
NeurIPS 2025	78.26	10.87	5.43	82.61	78.26	94.57
CVPR 2025	86.52	7.87	4.49	86.52	86.52	97.75
Pooled	84.03	9.20	4.60	87.53	84.68	97.59

B.8 AI-Generated Manuscripts

We evaluate manuscripts produced by Qwen3-32B-Instruct against the fixed NDS evaluator used in the main experiments. The evaluator has already been adapted on the real-manuscript review corpus; generated manuscripts are introduced only at evaluation time. We compare a standard manuscript-writing prompt with the same prompt augmented by a target-outline constraint. The constraint specifies the ordered heading depths while leaving topic-specific section titles and body content to the generator. Structural compliance requires the complete parsed heading-depth sequence to match the target hierarchy.

The generator uses temperature 0.7, top-p 0.9, a maximum output length of 16,384 tokens, and seed 42. Each condition contains 1,000 manuscripts from the same source prompts, with one generation attempt per prompt.

Table 20: Generation compliance and downstream evaluator activation. Each condition contains 1,000 generation attempts.

Measure	Rate
Unconstrained structural compliance	1.20%
Constrained structural compliance	72.50%
Activation among constrained compliant manuscripts	79.45%
Joint success among constrained attempts	57.60%
Target event among all unconstrained attempts	10.10%

The conditional 79.45% rate uses only structurally compliant constrained manuscripts, whereas the 57.60% joint rate uses all constrained attempts. The 10.10% unconstrained target-event rate is defined over all unconstrained manuscripts and is distinct from structural-compliance and compliance-conditioned activation rates.

B.9 Heading-Depth Input Transformations

We evaluate two inference-time transformations of the heading-depth sequence using the same fixed NDS checkpoint as the causal intervention analysis. Heading flattening maps every recognized

heading to depth 1 while leaving heading text, body text, and section order unchanged. Random legal remapping samples legal depth sequences while preserving the heading slots and order; the reported variation is over three remappings applied to the fixed evaluator. Neither transformation changes model parameters.

Table 21: Input-side structural transformations. Activation is measured on the 159 held-out target-structure manuscripts. Clean utility is measured on the 504-paper untouched clean split. Random remapping reports mean ± sample SD over three mappings.

Input structure	Activation (%)	Clean MAE	Clean Pearson
Original target hierarchy	92.45	0.7685	0.4688
Flattened (all depth 1)	8.18	0.7816	0.4641
Random legal remapping	18.66 ± 2.20	0.785 ± 0.004	0.461 ± 0.003

Heading flattening reduces activation by 84.27 percentage points relative to the fixed-checkpoint baseline. Random legal remapping also suppresses activation, while clean-utility changes remain small in the reported metrics.

B.10 Access Conditions and Construction Ablations

Access conditions. Full control permits selection of the 118 poisoned sources, reconstruction of their heading-depth configurations, and provision of target-consistent reviews. Label-only poisoning assigns target reviews to the same clean manuscripts while retaining their original organization. Document-only deployment starts from an evaluator already adapted with NDS and gives the deployment actor control over manuscript organization. Limited curation contributes 118 target-configuration document–review pairs using sources selected in fixed corpus order and a target selected from a disjoint proxy corpus.

Table 22: Access conditions. Document-only deployment assumes an evaluator already exposed to NDS; the other rows vary training-data access.

Access condition	ASR (%)	Near-FTR (%)
Full control	92.45	6.29
Label-only	8.81	6.92
Document-only deployment	82.39	8.18
Limited curation	74.21	10.06

Construction ablations. Each ablation removes one construction component while retaining the remaining configuration. Without collision filtering, a locally plausible twelve-slot hierarchy is selected directly. Without the fidelity gate, every parseable exact-target reconstruction is accepted. Without cross-field review filtering, reconstructed documents are paired with score-8 reviews before consistency filtering.

Table 23: Construction ablations and their corresponding measurements.

Removed component	Outcome
Collision filtering	Clean collision 6.1%; near-FTR 13.84%.
Fidelity gate	Preservation 80.0%; naturalness 3.98/5.
Cross-field review filtering	Logic Pass 76.10%; Shadow Pass 72.96%; ASR 69.18%.

Structure-aware detection. As a supplementary characterization, we train an ℓ_2-regularized logistic classifier with $C = 1$ and balanced class weights on structural summary features: heading count, maximum depth, depth proportions, and depth bigram/trigram frequencies. Features are standardized within each training fold. Leave-one-structure-out and leave-one-venue-out evaluations keep all documents from a source in the same fold, and operating thresholds are selected on the validation portion of each training fold.

Table 24: Structure-aware detection. AUC is summarized across held-out groups; operating-point rates are reported separately.

Measure	Result
Leave-one-structure-out AUC	0.84 ± 0.03
Leave-one-venue-out AUC	0.82 ± 0.04
Clean FPR at 90% TPR	9.00%
Structural-negative FPR	8.18%

C Hyperparameters and Compute

C.1 Primary Evaluator Adaptation

Table 25: Primary Qwen3-8B-Instruct adaptation configuration.

Setting	Value
Fine-tuning method	LoRA
Epochs	3
Model context window	16,384 tokens
Learning rate	8×10^{-5}
Scheduler	Cosine
Warmup ratio	0.05
Per-device batch size	2
Gradient accumulation	8
Precision	bf16
Optimizer	AdamW
Gradient clipping	1.0
LoRA rank	128
LoRA α	256
LoRA dropout	0
Primary poison ratio	4.99% (118/2,365)

The three seeds used for the repeated primary comparison are 42, 43, and 44. LoRA targets the attention projections `q_proj`, `k_proj`, `v_proj`, and `o_proj`, together with the MLP projections `gate_proj`, `up_proj`, and `down_proj`. AdamW uses $\beta_1 = 0.9$, $\beta_2 = 0.999$, $\epsilon = 10^{-8}$, and weight decay 0.

C.2 Evaluator Decoding

Evaluator decoding is greedy with a maximum of 2,048 generated tokens. Inputs exceeding the model context budget are truncated deterministically while reserving the output budget. Attack-evaluation eligibility requires the complete manipulated heading-depth sequence to remain visible after this processing. The same decoding policy is used across the matched peer-review carrier comparisons unless otherwise stated.

C.3 Behavioral Audit Configuration

The composite peer-review target event is defined in Appendix A.7. The LLM logic auditor is queried through an OpenAI-compatible interface with deterministic decoding. The primary evaluation configuration is summarized in Table 26.

The three logic dimensions are reasoning–score consistency, weakness–score consistency, and overall score coherence. A Logic Pass requires every dimension to receive a score of at least 2 and the mean score to be at least 1.8, consistent with Eq. 8. Under these thresholds, the per-dimension requirement is binding because three scores of at least 2 necessarily have a mean of at least 2.0. The rule-based Shadow Pass checks exact target-score attainment, output completeness, and the weakness-framing proxy described in Appendix A.7. API errors, malformed judge responses, and unparsable evaluator outputs are treated as failures rather than removed from the denominator.

Table 26: Primary behavioral-audit configuration.

Setting	Value
Logic auditor	DeepSeek-V4-Flash
Auditor temperature	0
Maximum auditor output	512 tokens
Logic dimensions	3
Per-dimension scale	1–3
Minimum per-dimension score	2
Minimum mean score	1.8
Target recommendation	8/10
API timeout	90 s
Maximum retries	3
Maximum audit calls per sample	2

C.4 Upstream Manuscript Generation

The workflow experiment uses Qwen3-32B-Instruct as the upstream manuscript generator with temperature 0.7, top-p 0.9, a maximum output length of 16,384 tokens, and seed 42. The constrained and unconstrained conditions each contain 1,000 source prompts with one generation attempt per prompt. All generated manuscripts are evaluated by the same fixed NDS evaluator previously adapted on the real-manuscript review corpus.

C.5 Compute

A primary Qwen3-8B LoRA adaptation run uses one NVIDIA RTX PRO 6000 GPU for approximately four GPU-hours. Repeated-seed, poisoning-budget, target-structure, baseline, and additional-model experiments are trained independently. Evaluation, parsing, reconstruction, behavioral auditing, and statistical resampling are run separately from adaptation. Reported compute describes the primary adaptation configuration; total project compute scales with the number of independently trained experimental conditions.