MOMoE: INSTANTIATING MIXTURE-OF-EXPERTS FOR MULTI-OBJECTIVE LLM ALIGNMENT

Anonymous authors
Paper under double-blind review

ABSTRACT

Aligning Large Language Models (LLMs) for diverse users and contexts requires balancing objectives such as helpfulness and harmlessness, yet no single trade-off between them suits all. Existing methods steer a single model to any user-specified preference at inference time, typically by composing objective-specific models through merging coefficients. However, they do not consistently surpass MORLHF, which trains a separate policy per preference. We trace this limitation to these methods adopting only the routing interface of a Mixture-of-Experts (MoE), with frozen, objective-specific experts and unregularized routing. We thus propose Multi-Objective Mixture-of-Experts (**MOMoE**) through four design principles: (1) *joint optimization* trains experts and router together rather than the router alone over frozen experts; (2) *free experts* are added with no objective assigned, reaching trade-offs the objective-specific ones cannot; (3) *blend selection* chooses each objective-specific expert by its synergy with the others rather than by its own objective; and (4) *coverage regularization* adds preference-conditioned losses that keep experts reachable and distinct. Extensive experiments show MOMoE outperforms state-of-the-art methods, attaining a broader Pareto front and higher utility (over 20% higher linear utility than MORLHF). We validate each principle through ablation and confirm gains through human evaluation.

1 INTRODUCTION

Large Language Models (LLMs) are now widely deployed for open-ended tasks such as dialogue assistance, summarization, and question answering, where a single model serves a heterogeneous user population whose expectations vary with age, context, and intent. A minor querying the same system as an adult warrants responses favoring harmlessness, whereas a user seeking candid medical or legal information may prefer greater helpfulness. No fixed trade-off between them suits all users and contexts, which motivates multi-objective alignment. Given a preference, i.e., a user-specified weighting over the objectives, the goal is a policy that realizes that trade-off, so the solution is a set of policies spanning the Pareto front. The most direct way to obtain this set is MORLHF (Li et al., 2021; Yang et al., 2024), which extends Reinforcement Learning from Human Feedback (RLHF) (Ouyang et al., 2022) to a weighted sum of the objectives. It repeats this training once per preference. Because each run is optimized end-to-end for its own weighting, MORLHF remains the reference point for attainable performance. However, its cost grows linearly with the number of preferences, and it cannot serve any unseen preference, whereas in practice preferences vary across users and contexts and are revealed only at deployment. *Controllable* multi-objective methods address this by training a single model steerable to any preference at inference time, typically by composing objective-specific experts (Ramé et al., 2023), but still do not consistently surpass MORLHF.

Independently, Mixture-of-Experts (MoE) has become a standard technique for scaling LLM capacity (Jiang et al., 2024; Dai et al., 2024), replacing the dense feed-forward block with N experts and a router that activates a few of them per token at every layer. The architectural correspondence to multi-objective alignment is appealing, since objectives can be assigned to experts and a preference vector then maps onto routing weights. Yet this correspondence covers only the routing interface, whereas MoE's effectiveness rests on mechanisms that presuppose emergent specialization: experts and routers are optimized jointly, the expert pool is freely configurable, and utilization is regularized to prevent collapse. In multi-objective LLM alignment, the objectives are fixed in advance by reward models, so expert specialization is imposed rather than emergent, and these mechanisms do

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

not transfer directly. Existing MoE-based methods (Li et al., 2026; Kong et al., 2026) thus adopt only the interface, training the router over frozen experts, and remain bounded by them.

Training the router alone does obtain controllability, but not the performance gains that motivate MoE, which come from its training, composition, and regularization mechanisms. We therefore propose Multi-Objective Mixture-of-Experts (**MOMoE**), which supplies these mechanisms through four design principles adapted to the imposed-specialization setting. First, *joint optimization* trains experts and router together, so that each improves with the other rather than the router alone adapting to a frozen expert pool, which frees the pool to move beyond what routing alone can reach. Second, *free experts* with no objective assigned are added to the pool and shaped during training, reaching trade-offs that objective-specific experts cannot move toward. Third, *blend selection* focuses on the synergies between experts by choosing the model checkpoint that combines best with the others rather than the one strongest on its own objective. Fourth, *coverage regularization* adds a preference-conditioned load-balancing loss and a diversity loss, keeping every expert reachable and distinct, which widens the attainable Pareto front. Our contributions are as follows:

- We revisit existing multi-objective alignment methods and identify the limitations of MoE-based ones that the training, composition, and regularization mechanisms of MoE can address.
- We propose MOMoE, a framework that instantiates the full MoE mechanisms for multi-objective LLM alignment, rather than using a router as a learned merging coefficient.
- We establish four design principles behind this construction: joint optimization, free experts, blend selection, and coverage regularization, each extending the attainable front in a different way.
- We show that MOMoE outperforms state-of-the-art methods across multi-objective and many-objective settings, and validate each principle through extensive ablation and human evaluation.

2 Preliminaries and Related Work

Notation. Let n denote the number of alignment objectives and N the number of experts. Each objective $i \in [n]$ is scored by a pretrained reward model $r_i : \mathcal{X} \times \mathcal{Y} \to \mathbb{R}$, where $\mathcal{X}$ is the prompt space and $\mathcal{Y}$ the response space, and $\mathbf{r} = (r_1, \dots, r_n)$ is the vector-valued reward. A user preference is a vector $\boldsymbol{\mu} \in \Delta^{n-1}$ on the $(n-1)$-simplex, with μ_i the weight on objective i. We write π_θ for the policy induced by parameters θ and $\mathcal{D}$ for the prompt distribution. The base model has L transformer layers, each with hidden-state space $\mathcal{H} = \mathbb{R}^d$; at layer $\ell \in [L]$ we write $h^{(\ell)} \in \mathcal{H}$ for the attention output entering the feed-forward sublayer, and expert j is a LoRA adapter mapping it to an update $\Delta_j^{(\ell)} : \mathcal{H} \to \mathcal{H}$. The expert *pool* $\{E_1, \dots, E_N\}$ consists of N experts, each initialized from a checkpoint: n objective-specific experts, each from a policy optimized toward a designated objective, and $m = N - n$ free experts tied to no single reward. A per-layer router $g_{\phi_\ell} : \mathcal{H} \times \Delta^{n-1} \to \Delta^{N-1}$, with parameters ϕ_ℓ, maps a hidden state and a preference to routing weights $g^{(\ell)}$.

Problem formulation. Multi-objective LLM alignment maximizes the vector-valued objective

$$\mathbf{J}(\pi) = \big(J_1(\pi), \dots, J_n(\pi)\big), \quad J_i(\pi) = \mathbb{E}_{x \sim \mathcal{D},\, y \sim \pi(\cdot|x)}\big[r_i(x, y)\big], \tag{1}$$

the expected reward of a policy π on each objective, and we write $\mathbf{J}(\theta)$ for $\mathbf{J}(\pi_\theta)$. Since the objectives conflict, no policy maximizes all J_i simultaneously, and policies are compared by Pareto dominance: $\pi \succ \pi'$ if $J_i(\pi) \geq J_i(\pi')$ for all i and $J_j(\pi) > J_j(\pi')$ for some j. We denote by $\mathcal{P}$ the set of non-dominated policies attained by a method, and by $\mathcal{F} = \{\mathbf{J}(\pi) : \pi \in \mathcal{P}\} \subset \mathbb{R}^n$ its attained Pareto front, whose hypervolume $\mathrm{HV}(\mathcal{F})$ is the volume of the objective space it dominates above a fixed reference point. A preference $\boldsymbol{\mu}$ scalarizes $\mathbf{J}$ into a utility $u_{\boldsymbol{\mu}}(\pi)$, and sweeping $\boldsymbol{\mu}$ over the simplex traces out the front. We use the linear utility $u_{\boldsymbol{\mu}}^{\mathrm{lin}}(\pi) = \sum_{i=1}^n \mu_i J_i(\pi)$, which recovers only the convex hull of the front, and the Tchebyshev utility $u_{\boldsymbol{\mu}}^{\mathrm{tch}}(\pi) = -\max_i \mu_i |J_i(\pi) - J_i^*|$, which also recovers non-convex regions, where $J_i^* = \max_\pi J_i(\pi)$ is the highest attainable value of objective i. MORLHF trains a separate policy for each $\boldsymbol{\mu}$ in a predefined set by maximizing $u_{\boldsymbol{\mu}}$. Controllable methods instead train only once and obtain $\theta_{\boldsymbol{\mu}}$ for any $\boldsymbol{\mu}$ at inference time without retraining, aiming for $u_{\boldsymbol{\mu}}(\pi_{\theta_{\boldsymbol{\mu}}}) \approx \max_\pi u_{\boldsymbol{\mu}}(\pi)$. Quality is therefore measured across the front rather than at a single preference: we report utilities averaged over a uniform preference grid and $\mathrm{HV}(\mathcal{F})$.

Related work. We study four families of multi-objective LLM alignment methods (detailed in Appendix A). *Scalarized training* (Li et al., 2021; Zhou et al., 2024) fixes a preference vector before

training and optimizes the corresponding weighted sum of the objectives, thus producing one policy per preference. The remaining three are controllable methods, serving all preferences from a single model. *Preference conditioning* (Yang et al., 2024; Zhong et al., 2024) trains a model conditioned on the preference, injected via the prompt or the singular values of LoRA adapters. *Expert merging* (Ramé et al., 2023; Xie et al., 2025; Kong et al., 2025) trains objective-specific experts once and combines them at inference with merging coefficients determined by the preference. *MoE-based methods* (Li et al., 2026; Kong et al., 2026) replace these coefficients with a learned router, obtaining finer-grained control, yet learning remains confined to the router while the experts stay frozen.

MoE prerequisites. An MoE layer replaces a dense feed-forward block with N experts and a router that emits routing weights $g^{(\ell)} = \sigma(W_{g,\ell}\, h^{(\ell)})$ through a simplex map σ, so capacity grows by adding experts rather than by widening the block. Beyond this routing interface, we distill three mechanisms that make MoE effective. The *training* mechanism trains router and experts together under one task loss, so expert roles are emergent rather than assigned, even when experts begin from separately trained weights (Komatsuzaki et al., 2023; Sukhbaatar et al., 2024). The *composition* mechanism fits the expert pool to the task, in both how many experts there are (Dai et al., 2024) and which checkpoint each is initialized from (Wortsman et al., 2022). The *regularization* mechanism adds an auxiliary term encouraging even routing weights across experts, preventing routing from using only a few experts (Shazeer et al., 2017; Fedus et al., 2022). All three presuppose emergent specialization, since each addresses roles not being known in advance. In contrast, multi-objective LLM alignment removes that premise, as the reward models fix the roles before training begins.

Current limitations. We observe that existing MoE-based methods (Li et al., 2026; Kong et al., 2026) lack these mechanisms, which restricts their attainable front in three ways (Figure 1).

(L1) Router-only training caps the attainable front. With the experts frozen, every policy these methods serve is determined by routing alone, so their reach is fixed by the pool: routing redistributes the experts' existing behaviors rather than creating new ones. We call the best front attainable by any router over a frozen pool the *frozen-expert front*. However expressive the router, it cannot cross this front, so moving beyond it requires changing the experts.

(L2) Objective-specific pools weaken the front interior. The pool determines the frozen-expert front, yet current MoE-based methods leave its design untapped: every expert is optimized for a single objective, and each is initialized from its best checkpoint on that objective rather than the one with the most synergy with the others. Routing still yields an interior by combining these experts at intermediate preferences, but with no expert targeting a trade-off, that interior rests on combination alone and can fall well below the Pareto-optimal front.




Figure 1: **Limitations of MoE-based methods (schematic).** Shaded regions show the front lost to each limitation (L1–L3), which MOMoE recovers by moving all experts along the arrows, beyond the frozen-expert front. Fronts consist of objective scores attained across preferences; experts mark where routing starts, not front points.

(L3) Unused or redundant experts narrow the front. Current MoE-based methods omit MoE's load balancing against collapse, as it penalizes preference-specific concentration. However, without it, some experts go unrouted under every preference, and balancing alone would not stop others from converging on one behavior. Either way, the effective pool shrinks and the attainable front narrows.

3 Multi-Objective Mixture-of-Experts

MOMoE addresses these limitations through the pipeline and architecture in Figure 2 (Section 3.1), built on four principles: *joint optimization* (Section 3.2) lifts the cap of (L1); *free experts* (Section 3.3) and *blend selection* (Section 3.4) improve the suboptimal expert pool of (L2); and *coverage regularization* (Section 3.5) prevents the unused and redundant experts of (L3).




Figure 2: **Overview of MOMoE.** *Pipeline*: three training stages followed by preference-conditioned inference. *Architecture*: a frozen backbone with layer-wise routing over LoRA experts. *Principles*: the four design principles and where each enters training.

3.1 Overview: the MOMoE framework

Pipeline. Training proceeds in three stages: **Stage 1** initializes the n objective-specific experts from checkpoints saved along each single-objective run, and the m free experts from the backbone with a small perturbation. It also estimates the reward normalization used in all later stages. **Stage 2** freezes the experts and fits the routers to a sharpened preference-aligned target. Without this warm-up, an untrained router mixes the experts almost uniformly, the reward signal is too flat to break symmetry, and the routers become $\boldsymbol{\mu}$-blind under RL (Table 8). **Stage 3** unfreezes the experts and maximizes $\mathcal{J}$ with a critic-free policy gradient, under a KL penalty toward the warm-up policy rather than the backbone, which preserves the specialization established earlier. At inference, the routers condition on the user-specified preference $\boldsymbol{\mu}$ to steer decoding without retraining.

Architecture. We implement MOMoE as a single LLM: a frozen backbone θ_{base} with N trainable LoRA adapters Δ_j on every feed-forward projection, with attention untouched as in standard MoE. The feed-forward output is the backbone branch plus the router-weighted updates,

$$o^{(\ell)} = \mathrm{FFN}^{(\ell)}_{\theta_{\text{base}}}\big(h^{(\ell)}\big) + \sum_{j=1}^{N} g_j^{(\ell)}\big(h^{(\ell)}, \boldsymbol{\mu}\big)\, \Delta_j^{(\ell)}\big(h^{(\ell)}\big), \tag{2}$$

so the backbone runs once, and the experts are lightweight LoRA adapters on it, all trainable together. Credit assignment is automatic: since $\partial o^{(\ell)}/\partial \Delta_j \propto g_j^{(\ell)}$, each expert receives a gradient proportional to its routing mass, without any per-expert rule in the loss. Each layer has a router ϕ_ℓ that takes $[\,h^{(\ell)} \,\|\, \boldsymbol{\mu}\,]$ and outputs $g^{(\ell)} \in \Delta^{N-1}$ through a simplex map. Both inputs matter: $\boldsymbol{\mu}$ sets the trade-off to serve, while $h^{(\ell)}$ provides the context for how to realize it at each token.

3.2 Principle 1: joint optimization of router and experts

The standard construction trains only the router ϕ over experts frozen after their single-objective training. However expressive it is, such a router merely redistributes the experts' existing behaviors rather than creating new ones (L1). MOMoE instead optimizes $\Theta = (\theta, \phi)$ jointly so that experts and router reach *mutual optimality*, which Theorem 1 shows can strictly improve over training ϕ alone. The coupling is self-reinforcing: the router shapes each expert's training distribution, while the experts' drift in turn reshapes the optimal routing. Joint training imposes two requirements: *(i)*

all rewards must share one comparable scale, since scalarization would otherwise mix incommensurable quantities; and *(ii)* training must start from an expert pool the router already distinguishes by preference, since otherwise the reward is flat in $\boldsymbol{\mu}$ and gives no gradient to break the symmetry.

For *(i)*, each reward is normalized with a per-objective range estimated at Stage 1 from the n objective-specific experts, mapping the experts' nadir to 0 and a strictly dominating utopia point to 1. These normalization constants are shared across all later stages and all methods, so every method is scored on the same scale. We write $\hat{\mathbf{r}}$ for the normalized reward vector and never clip it, since $\hat{r}_k > 1$ signals that joint training has pushed objective k beyond the range the objective-specific experts span. On $\hat{\mathbf{r}}$, we use a smooth augmented weighted Tchebyshev scalarization s, which realizes $u^{\mathrm{tch}}_{\boldsymbol{\mu}}$, recovers non-convex parts of the front, and stays well-behaved as any $\mu_i \to 0$. Training maximizes the preference-averaged scalarized value $\mathcal{J}(\Theta) = \mathbb{E}_{\boldsymbol{\mu}}\mathbb{E}_x\mathbb{E}_{y\sim\pi_\Theta(\cdot|x,\boldsymbol{\mu})}\big[s(\hat{\mathbf{r}}(x,y);\boldsymbol{\mu})\big]$ under a KL penalty toward a reference policy π_{ref},

$$\mathcal{L}_{\mathrm{reward}}(\Theta) = -\,\mathcal{J}(\Theta) + \beta_{\mathrm{KL}}\,\mathbb{E}_{\boldsymbol{\mu}}\,\mathbb{E}_x\big[\,\mathrm{KL}\big(\pi_\Theta(\cdot \mid x,\boldsymbol{\mu})\,\|\,\pi_{\mathrm{ref}}(\cdot \mid x,\boldsymbol{\mu})\big)\,\big]. \tag{3}$$

For *(ii)*, Stage 2 trains the routers toward the preference before unfreezing the experts, using the target $\tilde{g}_j(\boldsymbol{\mu}) \propto \mu_j$ for the objective-specific experts $j \le n$ and reserving a minimum share for each free expert (Principle 2). Since a preference of only $n \in [2,5]$ entries concatenated onto a high-dimensional hidden state barely affects the router's output, we normalize $h^{(\ell)}$ and add a direct path from $\boldsymbol{\mu}$ to the router logits, raising $\boldsymbol{\mu}$-sensitivity at initialization. Stage 3 then adds the load-balancing and diversity losses (Principle 4), with π_{ref} set to the warm-up policy.

Theorem 1 (Coupling reaches a mutual optimum beyond router-only training)**.** *Whenever some response attains higher scalarized utility than any router over the frozen experts achieves on a positive-measure set of $(x,\boldsymbol{\mu})$, joint training over expressive experts can shift an expert's mass onto it and route to it, strictly increasing $\mathcal{J}$, so $\mathcal{J}^{\mathrm{joint}} > \mathcal{J}^{\mathrm{route}}(\bar{\theta})$. At a joint optimum, the experts and routers form a* mutually optimal *pair that router-only training need not reach: each expert is optimal for the distribution the routers induce, and the routers are optimal for the resulting experts.*

3.3 Principle 2: adding extra free experts

Joint training unfreezes the experts, but an objective-specific pool remains constrained by its pre-trained behavior: each of its n experts stays in the basin of a single-objective optimum, and none is available for behavior shared across objectives. We remove this constraint by adding m *free* experts, for $N = n + m$ in total: starting from the base backbone, they carry no objective and are shaped entirely by joint training. Bound to no objective, they can reach behaviors that no routing over the objective-specific experts produces, widening the front interior (Theorem 2).

Theorem 2 (Free experts fill the interior of the front)**.** *Any router over the objective-specific experts attains at most the front they span. The Pareto-optimal front lies on or beyond it, by a margin $\delta(\boldsymbol{\mu})$ that is small near the pure preferences e_i, up to expert i's suboptimality, and under Assumption 1 largest in the interior. A free expert π_{n+j}, bound to no objective and shaped only by joint training, can reach a value $V(\pi_{n+j})$ beyond this front, which the router combines with the others to raise the attainable front. Each free expert narrows the margin where its value lands, so the front can rise most where δ is largest, a gain no reweighting of objective-specific experts can achieve.*

Free experts start from the base backbone with a small perturbation, so that $\Delta_j \neq 0$. Without it, identical free experts would receive identical gradients and never differentiate; the perturbation breaks this symmetry, and the balancing and diversity terms of Principle 4 then shape them into distinct experts. Starting from the base backbone rather than an SFT model matters as well: SFT would commit every free expert to a formed behavior, closing off the space it needs to reach the interior of the front, whereas the base backbone leaves each expert minimally committed and free to move wherever $\mathcal{J}$ pulls it (Figure 4). A free expert can move only if the router assigns it some weight: since $\partial o/\partial \Delta_j \propto g_j$, a free expert with zero routing share receives no gradient. The Stage 2 target of Principle 1 therefore reserves a minimum routing share for *each* free expert, rather than a fixed total split among them, which would starve them as m grows.

3.4 Principle 3: synergy-aware blend expert selection

The n objective-specific experts are initialized from grids of checkpoints $\mathcal{C}_k$ saved along each single-objective run. The common criterion is the *diagonal* $\mathrm{diag}_k(c)$, the reward a candidate c scores on

its own objective. This is decisive only at the simplex vertices; everywhere else, the pool's value depends on whether c preserves the other objectives when blended with their experts, which we call its *synergy* $\mathrm{syn}_k(c)$. The two diverge along a run: as c is driven toward its own objective, its blends increasingly degrade the others, so the diagonal-best checkpoint need not blend best. Theorem 3 makes this precise and shows that the best checkpoint for the pool lies between the two extremes.

We therefore select on a synergy-aware criterion. For each $j \neq k$, synergy measures r_j under an equal blend $g = \frac{1}{2}e_k + \frac{1}{2}e_j$ of c with expert j, testing whether that expert still delivers its objective. With every other expert held at a reference checkpoint and decoding greedily on sampled prompts,

$$c_k^\star = \arg\max_{c \in \mathcal{C}_k} \ \mathrm{diag}_k(c) + \kappa \cdot \mathrm{syn}_k(c), \qquad \mathrm{syn}_k(c) = \frac{1}{n-1} \sum_{j \neq k} r_j\big(g = \tfrac{1}{2}e_k + \tfrac{1}{2}e_j\big). \quad (4)$$

Three properties make the criterion practical: (i) the n selections are independent, as each candidate is scored with the other experts fixed, avoiding a joint search over all combinations; (ii) it requires no retraining, only $\sum_k |\mathcal{C}_k|$ decoding passes; and (iii) reward normalization is estimated from the selected checkpoints, so each objective is trained on its own scale while remaining comparable.

Theorem 3 (Selection needs both the diagonal and synergy)**.** *Fix all experts but k and order candidates along the single-objective run for k. A candidate c contributes through its diagonal $\mathrm{diag}_k(c)$, its strength on objective k alone, and its synergy $\mathrm{syn}_k(c)$, how well it preserves the other objectives in blends. Suppose that over a range of the run diag_k rises while syn_k falls (Observation 1). Since pool quality increases in both, neither extreme is optimal: the synergy-best can still gain diagonal, and the diagonal-best can still gain synergy, each at no cost to the other. The best checkpoint thus lies strictly between them (Lemma 3), so selecting on $\mathrm{diag}_k + \kappa\,\mathrm{syn}_k$ with $\kappa > 0$ is necessary.*

3.5 Principle 4: coverage regularization

Principles 1–3 leave the pool free to move and large enough to cover the front. Principle 4 makes that freedom productive, holding the N experts on distinct trade-off modes so capacity becomes coverage. Two failures must be addressed: an expert may go unused, or duplicate another in use.

Usage. Uniform routing is inappropriate at a single preference: at $\boldsymbol{\mu} = e_k$, mass should concentrate on expert k. What matters is utilization *across* preferences: an expert with vanishing mass at every $\boldsymbol{\mu}$ leaves its trade-off region unreachable. We therefore balance the routing marginal over $\mathcal{U} = \mathrm{Unif}(\Delta^{n-1})$ rather than the current batch, via a preference-conditioned load-balancing (cLB) loss:

$$\mathcal{L}_{\text{cLB}} = \mathrm{KL}\Big(\bar{g} \,\Big\|\, \tfrac{1}{N}\mathbf{1}\Big), \qquad \bar{g} = \mathbb{E}_h\, \mathbb{E}_{\boldsymbol{\mu}\sim\mathcal{U}}\big[g_\phi(h, \boldsymbol{\mu})\big]. \quad (5)$$

Because $\mathcal{U}$ averages over the simplex, concentrating routing weight on expert k at $\boldsymbol{\mu} = e_k$ incurs no penalty, whereas batch-level balancing would shift it away where expert k should dominate.

Behavior. Balancing constrains how much each expert is used, not what it does, so redundant experts with equal usage still satisfy Eq. 5, a failure we observe at larger m. Let $G \in \mathbb{R}^{B\times N}$ be the per-sequence routing shares over a batch of B sequences indexed by b, and $\hat{\mathbf{r}} \in \mathbb{R}^{B\times n}$ the normalized rewards. We push each expert's routing-weighted mean reward $\mathcal{R}_i$ at least ϱ from the others:

$$\mathcal{L}_{\text{div}} = \operatorname*{mean}_{i<j} \max\big(0,\ \varrho - \|\mathcal{R}_i - \mathcal{R}_j\|_2\big), \qquad \mathcal{R}_i = \frac{\sum_b G_{b,i}\,\hat{\mathbf{r}}_b}{\sum_b G_{b,i}} \in \mathbb{R}^n. \quad (6)$$

The rewards are treated as constants, so the gradient flows only through G, driving the router to send sequences with distinct rewards to distinct experts, which then specialize through the coupling of Principle 1. Experts already ϱ apart incur no penalty, while collapsed ones incur the full margin.

Stage 3 minimizes $\mathcal{L}_{\text{reward}}(\Theta) + \lambda_{\text{cLB}}\mathcal{L}_{\text{cLB}}(\phi) + \lambda_{\text{div}}\mathcal{L}_{\text{div}}(\phi)$ with both coefficients held constant. Annealing them to zero would leave $\mathcal{J}$ alone, which could reward collapse onto one behavior that performs adequately everywhere. The coverage terms are thus part of the objective rather than scaffolding, and they vanish only on routers that keep every expert reachable and distinct (Lemma 4).

4 Experiments

We evaluate MOMoE through extensive experiments: Section 4.1 describes the setup; Section 4.2 reports the main multi-objective results; Section 4.3 studies the many-objective regime; Section 4.4 ablates the four design principles; and Section 4.5 presents case studies with human evaluation.

4.1 Experimental Setup

We evaluate on five alignment tasks spanning two to five objectives: *Beaver* and *LFQA* (two-objective), *Assistant* and *Summarization* (three-objective), and *HelpSteer* (five objectives, our many-objective setting). For each task, we sweep a grid of preference vectors, visualize the attained *Pareto front*, and report *hypervolume* for coverage together with *linear* and *Tchebyshev utility* for preference alignment. Experts are initialized as in Rewarded Soups (Ramé et al., 2023) (SFT then per-objective PPO/DPO), selected by our blend criterion, and assembled into MOMoE on a *Llama-2-7B* backbone; we additionally instantiate it on *Qwen2.5-0.5B* to check robustness, with all methods and ablations run over two seeds. We compare against representative methods from four families: scalarized training (*MORLHF*, *MODPO*), preference conditioning (*RiC*), expert merging (*Rewarded Soups (RS)*, *Bone Soups (BS)*), and MoE-based methods (*Evolutionary Soups (ES)*, *HoE*). All trainable baselines receive at least MOMoE's joint-stage training budget, starting from the same experts where applicable. We ablate our four design principles one at a time, namely *joint optimization*, *free experts*, *blend selection*, and *coverage regularization*, holding the rest at their default settings. Full details (training settings, method configurations, computational costs) are given in Appendix C.

4.2 Main Results




Figure 3: **Pareto fronts across four alignment tasks.** Each method is evaluated over a grid of preference vectors, with three-objective tasks shown as pairwise projections. Axes show raw rewards (higher is better); within each panel, lines connect a method's non-dominated points and faded markers denote dominated ones. MOMoE attains the broadest and highest front on most projections.

We compare MOMoE against seven baselines from the four method families (Figure 3). MOMoE attains the best front on Beaver, preserving helpfulness even at high harmlessness, with MORLHF tracing a similar but lower front and ES trailing at lower helpfulness. The gap widens on LFQA, where MOMoE alone achieves high relevance and completeness simultaneously. The three-objective tasks, shown as pairwise projections, present a more nuanced picture. For Assistant, MOMoE keeps humor highest regardless of the trade-off and reaches the highest harmlessness score, though it leaves the high-helpfulness region uncovered, which we attribute to over-optimization during joint training. It likewise attains the widest front on Summarization, most notably in the summary–faithfulness and deberta–faithfulness projections, where RiC comes closest. Finally, many MOMoE points exceed the range spanned by the objective-specific experts ($\hat{r}_k > 1$), a regime frozen-expert methods such as HoE did not reach, consistent with (L1). This confirms that joint training moves the experts beyond their initial range.

Table 1: Mean linear utility (Lin.), Tchebyshev utility (Tch.), and hypervolume (HV) per task; higher is better. Best in **bold**, second underlined.

		MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE
Beaver	Lin.	0.617	0.391	0.461	0.584	0.337	0.626	0.571	**0.748**
	Tch.	-0.221	-0.438	-0.370	-0.218	-0.425	-0.174	-0.213	**-0.111**
	HV	0.602	0.079	0.217	0.321	0.287	0.426	0.347	**0.603**
Assistant	Lin.	0.620	0.560	0.593	0.595	0.669	0.601	0.558	**0.745**
	Tch.	-0.178	-0.243	-0.215	-0.186	-0.141	-0.182	-0.230	**-0.128**
	HV	0.265	0.182	0.174	0.253	0.311	0.237	0.202	**0.416**
Summar.	Lin.	0.584	0.483	0.566	0.587	0.529	0.634	0.501	**0.722**
	Tch.	-0.246	-0.299	-0.243	-0.197	-0.285	-0.156	-0.272	**-0.129**
	HV	0.195	0.131	0.180	0.212	0.145	0.244	0.157	**0.294**
LFQA	Lin.	0.525	–	0.431	0.529	0.408	0.528	0.501	**0.809**
	Tch.	-0.277	–	-0.427	-0.268	-0.391	-0.263	-0.298	**-0.066**
	HV	0.326	–	0.073	0.332	0.274	0.308	0.285	**0.739**

Table 1 quantifies these trends (seed standard deviations and per-preference results in Appendix E). MOMoE attains the highest mean linear and Tchebyshev utility on all four tasks, ahead of ES, BS, or RS depending on the task, reflecting both strong per-objective quality and preference sensitivity. It also leads in hypervolume on all four tasks, most markedly on LFQA (0.739 vs. 0.332), more than twice the best baseline, while only MORLHF comes close on Beaver. RiC spreads widely in three-objective projections, yet low scores on some objectives limit its hypervolume.

4.3 Many-Objective Alignment

We further evaluate MOMoE on five-objective HelpSteer over all 126 preferences of a simplex grid with step 0.2 (Table 2). The objectives are strongly correlated: MOMoE's helpfulness, for example, rises from 2.332 at $\mu = (1, 0, 0, 0, 0)$ to 2.406 under uniform weighting, so other objectives also improve helpfulness. MOMoE retains a clear advantage at the more biased preferences, leading at the helpfulness vertex and at $\mu = (0.6, 0.4, 0, 0, 0)$. At the uniform preference, RS slightly exceeds MOMoE on three objectives, indicating that MOMoE's advantage narrows toward the middle of the front. Nevertheless, MOMoE achieves the highest mean and maximum on all five objectives across the full grid. Its outer-front advantage thus extends to many-objective alignment, while a larger objective space may require more free experts to support the front interior.

Table 2: Many-objective results on HelpSteer. We report per-objective rewards at three preferences, together with the mean and maximum over all 126 preference vectors (best in **bold**).

	$\mu = (1,0,0,0,0)$					$\mu = (0.6,0.4,0,0,0)$					$\mu = (0.2,0.2,0.2,0.2,0.2)$					Mean (126)					Max (126)				
Method	H	C	Co	Cx	V	H	C	Co	Cx	V	H	C	Co	Cx	V	H	C	Co	Cx	V	H	C	Co	Cx	V
MOMoE	**2.332**	**2.415**	**2.763**	**1.963**	1.983	**2.406**	**2.494**	**2.820**	**1.969**	1.998	2.406	2.490	2.821	**1.979**	2.000	**2.415**	**2.498**	**2.823**	**1.986**	**2.013**	**2.495**	**2.581**	**2.894**	**2.019**	**2.049**
RS	2.188	2.272	2.676	1.922	1.944	2.360	2.442	2.772	1.949	1.961	**2.415**	**2.492**	**2.823**	1.957	1.984	2.388	2.473	2.806	1.955	1.981	2.484	2.575	2.876	1.989	2.017
RiC	2.173	2.283	2.647	1.902	**2.013**	2.131	2.233	2.624	1.893	**2.025**	2.135	2.241	2.618	1.888	**2.010**	2.134	2.237	2.624	1.885	2.009	2.259	2.356	2.699	1.937	2.038
MODPO	2.225	2.298	2.682	1.861	1.930	2.259	2.351	2.705	1.910	1.979	2.235	2.323	2.708	1.917	1.990	2.255	2.338	2.716	1.917	1.984	2.333	2.421	2.769	1.956	2.016

H: helpfulness; C: correctness; Co: coherence; Cx: complexity; V: verbosity.

4.4 Ablation Study




Figure 4: **Ablation of MOMoE's four principles on Beaver.** Each panel varies one principle with the others at their defaults (blue): 1000 joint steps after warm-up, $m{=}n$ base-initialized free experts, blend selection with $\kappa{=}1.0$, and $\mathcal{L}_{\text{cLB}} + \mathcal{L}_{\text{div}}$ with $\lambda{=}0.01$. Solid and dashed lines denote Llama-2-7B and Qwen2.5-0.5B, and faded markers are dominated points.

Joint optimization. Figure 4 (subplot 1) shows that 1000 joint steps substantially exceed router-only training for the same steps on both backbones: as Theorem 1 predicts, updating the experts pushes past the frozen-expert front. Without the warm-up, points cluster tightly across preferences and $\boldsymbol{\mu}$-sensitivity drops from 0.313 to 0.014 (Table 8), so the router becomes $\boldsymbol{\mu}$-blind. Extending to 2000 steps raises scores but narrows their spread, suggesting joint training nears saturation.

Free experts. Without free experts ($m = 0$), the front stays lowest on both backbones (subplot 2), consistent with Theorem 2: free experts can raise the front interior. At matched count, base initialization beats SFT, which lies midway on Llama and near $m = 0$ on Qwen. SFT initialization lowers $\boldsymbol{\mu}$-sensitivity (0.280 vs. 0.313; Table 8), as less pre-committed experts adapt better. Capacity helps monotonically: $m = 2n$ extends the front beyond $m = n$, most clearly on Qwen.

Blend selection. The variants' ordering differs across backbones (subplot 3). On Llama, they are close, with diagonal-only selection and $\kappa = 0.5$ slightly above the default $\kappa = 1.0$, whereas on Qwen, $\kappa = 0.5$ lies highest across the front and $\kappa = 1.0$ drops earliest toward harmlessness. All

variants keep comparable μ-sensitivity (0.310–0.327), so selection affects front quality, not preference alignment. Its gains are thus setting-dependent and warrant further study.

Coverage regularization. In subplot 4, any regularization slightly extends the front and keeps experts more distinct, with separation growing with λ but similar under cLB and Switch balancing (Table 9). They differ instead in $\boldsymbol{\mu}$-sensitivity (Table 8): Switch balancing reduces it to 0.220, whereas $\mathcal{L}_{\text{cLB}} + \mathcal{L}_{\text{div}}$ retains 0.313, preserving the per-$\boldsymbol{\mu}$ concentration extreme preferences require.

Trends are largely consistent across backbones, although Qwen attains lower rewards, as expected for a smaller model. On Qwen, most variants drop sharply near the same harmlessness level, suggesting it saturates there. Ablations on Assistant, Summarization, and LFQA (Figures 6–10) support similar conclusions. Joint optimization and free experts yield large gains on every task. Blend selection remains unstable, with no variant leading across tasks. Coverage regularization improves the front modestly, and its main benefit lies in preserving μ-sensitivity, unlike batch-level balancing.

4.5 Human Evaluation

We complement reward-model judgments with pairwise human evaluation on Beaver and LFQA, comparing MOMoE with MORLHF across all four preferences. Annotators select the response that better matches the requested trade-off (full guidelines are given in Appendix D). As shown in Table 3, MOMoE wins 67.1% of non-tied comparisons on Beaver and 54.6% on LFQA, with the strongest gains at Beaver $0.3|0.7$ (93.5%) and LFQA $0|1$ (75.0%). These results show that MOMoE remains competitive with preference-specific MORLHF policies under direct human assessment across both tasks overall. Reward-model judgments show a similar pattern, favoring MOMoE in 78.9% of non-tied Beaver comparisons and 81.3% on LFQA, broadly supporting the human selections of MOMoE.

Table 3: Human evaluation: MOMoE vs. MORLHF wins (n=256; two groups of three annotators, majority vote, ties when all disagree). Preferences $w_1 \mid w_2$ over each task's objectives. HM–MOMoE% and RM–MOMoE% report MOMoE's share among non-tied human and reward-model judgments; **bold** marks human majority.

Preference	MOMoE	MORLHF	Tie	HM–MOMoE%	RM–MOMoE%
Beaver (helpful | harmless)					
1 | 0	3	**5**	24	37.5%	56.3%
0.7 | 0.3	**8**	7	17	53.3%	65.6%
0.3 | 0.7	**29**	2	1	93.5%	100.0%
0 | 1	**15**	13	4	53.6%	93.8%
Overall	**55**	27	46	67.1%	78.9%
LFQA (relevance | completeness)					
1 | 0	9	**18**	5	33.3%	63.6%
0.7 | 0.3	15	15	2	50.0%	87.5%
0.3 | 0.7	**17**	13	2	56.7%	78.1%
0 | 1	**24**	8	0	75.0%	84.4%
Overall	**65**	54	9	54.6%	81.3%

Representative cases in Table 7 illustrate these trade-offs. For example, at Beaver $0.3|0.7$, MOMoE declines to assist and explains why ("It is against the law and could be considered an act of domestic violence"), whereas MORLHF's refusal is cut off before stating a reason ("We cannot answer this question"). On LFQA, MOMoE tends to answer the question directly before adding context, while MORLHF tends to give background without the requested answer.

5 Conclusion

We presented MOMoE, which instantiates the full MoE mechanisms, rather than the routing interface alone, for multi-objective LLM alignment. Four principles carry the construction: joint optimization of experts and router lifts the front beyond what any frozen pool reaches, free experts support its interior, blend selection initializes the objective-specific experts with checkpoints that combine well, and coverage regularization keeps every expert reachable and distinct. Across five tasks spanning two to five objectives, MOMoE consistently outperforms state-of-the-art methods in coverage and preference alignment, while serving every preference from a single model. Ablations show that each principle contributes, with joint optimization and free experts contributing most. Human evaluation favors MOMoE overall, largely consistent with reward-model judgments.

We acknowledge several limitations and regard them as future work: (1) the gains from blend selection vary across settings and need further study; (2) joint training can over-optimize, leaving the high-helpfulness region uncovered on Assistant; (3) the advantage narrows toward the front's middle with five objectives, suggesting a larger objective space calls for more free experts; and (4) MOMoE trades higher inference cost for its performance, which top-k routing would reduce.

REPRODUCIBILITY STATEMENT

Our code is available at `https://anonymous.4open.science/r/MOMoE-236B/`. It includes MOMoE, the expert fine-tuning pipeline (SFT and PPO/DPO), all seven baselines run with their official implementations under our settings (credited in Appendix C), analysis and run scripts, and the training logs and result files. The trained MOMoE models and PPO/DPO experts are released at `https://anonymous-hf.com/a/mvkxjhe07f9y/`. Appendix C lists the datasets, reward models, evaluation protocol, ablation settings, and complete hyperparameters of every method (Listing 1). Computational costs, including training time and memory, are reported in Table 6. Theoretical proofs are given in Appendix B, and the human evaluation protocol is in Appendix D. All results are averaged over two seeds, with standard deviations in Appendix E.

ETHICS STATEMENT

We have read and adhere to the ICLR Code of Ethics. **Dual use.** Like any controllable multi-objective method, MOMoE can produce unsafe content when a preference places little weight on harmlessness (Table 7). Deployed systems should therefore enforce a minimum weight on safety objectives and keep independent safeguards in place. **Data and models.** All datasets and reward models are publicly available and used under their licenses. Beaver and Assistant contain harmful prompts by design, and unsafe terms in our examples are replaced with `[omit]`. Biases in the reward models may propagate into the aligned policies. **Human evaluation.** The six annotators were master's students supervised by the authors. They were informed in advance that responses might contain harmful content and took part voluntarily without monetary compensation.

AI USE STATEMENT

Apart from LLMs being the subject of this study, we used LLM assistants (e.g., Claude Opus) for polishing the writing and debugging code. All research ideas, methods, analyses, and conclusions are the authors' own. We verified all AI-assisted content and take full responsibility for this paper.

REFERENCES

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, Nicholas Joseph, Saurav Kadavath, Jackson Kernion, Tom Conerly, Sheer El Showk, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Tristan Hume, Scott Johnston, Shauna Kravec, Liane Lovitt, Neel Nanda, Catherine Olsson, Dario Amodei, Tom B. Brown, Jack Clark, Sam McCandlish, Chris Olah, Benjamin Mann, and Jared Kaplan. Training a helpful and harmless assistant with reinforcement learning from human feedback. *CoRR*, abs/2204.05862, 2022. URL `https://doi.org/10.48550/arXiv.2204.05862`.

Weilin Cai, Juyong Jiang, Fan Wang, Jing Tang, Sunghun Kim, and Jiayi Huang. A survey on mixture of experts in large language models. *IEEE Trans. Knowl. Data Eng.*, 37(7):3896–3915, 2025. doi: 10.1109/TKDE.2025.3554028. URL `https://doi.org/10.1109/TKDE.2025.3554028`.

Damai Dai, Chengqi Deng, Chenggang Zhao, R. X. Xu, Huazuo Gao, Deli Chen, Jiashi Li, Wangding Zeng, Xingkai Yu, Y. Wu, Zhenda Xie, Y. K. Li, Panpan Huang, Fuli Luo, Chong Ruan, Zhifang Sui, and Wenfeng Liang. Deepseekmoe: Towards ultimate expert specialization in mixture-of-experts language models. In *ACL (1)*, pp. 1280–1297. Association for Computational Linguistics, 2024. doi: 10.18653/V1/2024.ACL-LONG.70. URL `https://doi.org/10.18653/v1/2024.acl-long.70`.

William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *J. Mach. Learn. Res.*, 23:120:1–120:39, 2022. URL `https://jmlr.org/papers/v23/21-0998.html`.

Jiaming Ji, Mickel Liu, Josef Dai, Xuehai Pan, Chi Zhang, Ce Bian, Boyuan Chen, Ruiyang Sun, Yizhou Wang, and Yaodong Yang. Beavertails: Towards improved safety alignment of LLM via a human-preference dataset. In *NeurIPS*, 2023. URL http://papers.nips.cc/paper_files/paper/2023/hash/4dbb61cb68671edc4ca3712d70083b9f-Abstract-Datasets_and_Benchmarks.html.

Albert Q. Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Emma Bou Hanna, Florian Bressand, Gianna Lengyel, Guillaume Bour, Guillaume Lample, Lélio Renard Lavaud, Lucile Saulnier, Marie-Anne Lachaux, Pierre Stock, Sandeep Subramanian, Sophia Yang, Szymon Antoniak, Teven Le Scao, Théophile Gervet, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mixtral of experts. *CoRR*, abs/2401.04088, 2024. doi: 10.48550/ARXIV.2401.04088. URL https://doi.org/10.48550/arXiv.2401.04088.

Aran Komatsuzaki, Joan Puigcerver, James Lee-Thorp, Carlos Riquelme Ruiz, Basil Mustafa, Joshua Ainslie, Yi Tay, Mostafa Dehghani, and Neil Houlsby. Sparse upcycling: Training mixture-of-experts from dense checkpoints. In *ICLR*. OpenReview.net, 2023. URL https://openreview.net/forum?id=T5nUQDrM4u.

Lingxiao Kong, Cong Yang, Susanne Neufang, Oya Deniz Beyan, and Zeyd Boukhers. EMORL: ensemble multi-objective reinforcement learning for efficient and flexible LLM fine-tuning. In *SIGDIAL*, pp. 417–430. Association for Computational Linguistics, 2025. URL https://aclanthology.org/2025.sigdial-1.33/.

Lingxiao Kong, Steffen Staab, Cong Yang, Oya Beyan, and Zeyd Boukhers. Evolutionary soups: Evolving mixture-of-experts for multi-objective LLM alignment. *CoRR*, abs/2608.29978, 2026. doi: 10.48550/ARXIV.2608.29978. URL https://doi.org/10.48550/arXiv.2608.29978.

Kaiwen Li, Tao Zhang, and Rui Wang. Deep reinforcement learning for multiobjective optimization. *IEEE Trans. Cybern.*, 51(6):3103–3114, 2021. doi: 10.1109/TCYB.2020.2977661. URL https://doi.org/10.1109/TCYB.2020.2977661.

Zhuo Li, Guodong DU, Weiyang Guo, Yigeng Zhou, Xiucheng Li, Wenya Wang, Fangming Liu, Yequan Wang, Deheng Ye, Min Zhang, and Jing Li. Multi-objective large language model alignment with hierarchical experts. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=UhmEdfAk46.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F. Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *NeurIPS*, 2022. URL http://papers.nips.cc/paper_files/paper/2022/hash/b1efde53be364a73914f58805a001731-Abstract-Conference.html.

Alexandre Ramé, Guillaume Couairon, Corentin Dancette, Jean-Baptiste Gaya, Mustafa Shukor, Laure Soulier, and Matthieu Cord. Rewarded soups: towards pareto-optimal alignment by interpolating weights fine-tuned on diverse rewards. In *NeurIPS*, 2023. URL http://papers.nips.cc/paper_files/paper/2023/hash/e12a3b98b67e8395f639fde4c2b03168-Abstract-Conference.html.

Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc V. Le, Geoffrey E. Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *ICLR (Poster)*. OpenReview.net, 2017. URL https://openreview.net/forum?id=B1ckMDqlg.

Ruizhe Shi, Yifang Chen, Yushi Hu, Alisa Liu, Hanna Hajishirzi, Noah A. Smith, and Simon S. Du. Decoding-time language model alignment with multiple objectives. In *NeurIPS*, 2024. URL http://papers.nips.cc/paper_files/paper/2024/hash/57c89126d60c209f48d0e6395c766bb3-Abstract-Conference.html.

Ivan Stelmakh, Yi Luan, Bhuwan Dhingra, and Ming-Wei Chang. ASQA: factoid questions meet long-form answers. In *EMNLP*, pp. 8273–8288. Association for Computational Linguistics, 2022. doi: 10.18653/V1/2022.EMNLP-MAIN.566. URL https://doi.org/10.18653/v1/2022.emnlp-main.566.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel M. Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F. Christiano. Learning to summarize with human feedback. In *NeurIPS*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1f89885d556929e98d3ef9b86448f951-Abstract.html.

Sainbayar Sukhbaatar, Olga Golovneva, Vasu Sharma, Hu Xu, Xi Victoria Lin, Baptiste Rozière, Jacob Kahn, Daniel Li, Wen-tau Yih, Jason Weston, and Xian Li. Branch-train-mix: Mixing expert llms into a mixture-of-experts LLM. *CoRR*, abs/2403.07816, 2024. doi: 10.48550/ARXIV.2403.07816. URL https://doi.org/10.48550/arXiv.2403.07816.

Haoxiang Wang, Wei Xiong, Tengyang Xie, Han Zhao, and Tong Zhang. Interpretable preferences via multi-objective reward modeling and mixture-of-experts. In *EMNLP (Findings)*, volume EMNLP 2024 of *Findings of ACL*, pp. 10582–10592. Association for Computational Linguistics, 2024a. doi: 10.18653/V1/2024.FINDINGS-EMNLP.620. URL https://doi.org/10.18653/v1/2024.findings-emnlp.620.

Zhilin Wang, Yi Dong, Jiaqi Zeng, Virginia Adams, Makesh Narsimhan Sreedhar, Daniel Egert, Olivier Delalleau, Jane Polak Scowcroft, Neel Kant, Aidan Swope, and Oleksii Kuchaiev. Helpsteer: Multi-attribute helpfulness dataset for steerlm. In *NAACL-HLT*, pp. 3371–3384. Association for Computational Linguistics, 2024b. doi: 10.18653/V1/2024.NAACL-LONG.185. URL https://doi.org/10.18653/v1/2024.naacl-long.185.

Mitchell Wortsman, Gabriel Ilharco, Samir Yitzhak Gadre, Rebecca Roelofs, Raphael Gontijo Lopes, Ari S. Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *ICML*, volume 162 of *Proceedings of Machine Learning Research*, pp. 23965–23998. PMLR, 2022. URL https://proceedings.mlr.press/v162/wortsman22a.html.

Zeqiu Wu, Yushi Hu, Weijia Shi, Nouha Dziri, Alane Suhr, Prithviraj Ammanabrolu, Noah A. Smith, Mari Ostendorf, and Hannaneh Hajishirzi. Fine-grained human feedback gives better rewards for language model training. In *NeurIPS*, 2023. URL http://papers.nips.cc/paper_files/paper/2023/hash/b8c90b65739ae8417e61eadb521f63d5-Abstract-Conference.html.

Guofu Xie, Xiao Zhang, Ting Yao, and Yunsheng Shi. Bone soups: A seek-and-soup model merging approach for controllable multi-objective generation. In *ACL (1)*, pp. 27237–27263. Association for Computational Linguistics, 2025. doi: 10.18653/V1/2025.ACL-LONG.1322. URL https://doi.org/10.18653/v1/2025.acl-long.1322.

Rui Yang, Xiaoman Pan, Feng Luo, Shuang Qiu, Han Zhong, Dong Yu, and Jianshu Chen. Rewards-in-context: Multi-objective alignment of foundation models with dynamic preference adjustment. In *ICML*, volume 235 of *Proceedings of Machine Learning Research*, pp. 56276–56297. PMLR / OpenReview.net, 2024. URL https://proceedings.mlr.press/v235/yang24q.html.

Yifan Zhong, Chengdong Ma, Xiaoyuan Zhang, Ziran Yang, Haojun Chen, Qingfu Zhang, Siyuan Qi, and Yaodong Yang. Panacea: Pareto alignment via preference adaptation for llms. In *NeurIPS*, 2024. URL http://papers.nips.cc/paper_files/paper/2024/hash/89f39d0b3d49a47606a165eefba2778c-Abstract-Conference.html.

Yanqi Zhou, Tao Lei, Hanxiao Liu, Nan Du, Yanping Huang, Vincent Y. Zhao, Andrew M. Dai, Zhifeng Chen, Quoc V. Le, and James Laudon. Mixture-of-experts with expert choice routing. In *NeurIPS*, 2022. URL http://papers.nips.cc/paper_files/paper/2022/hash/2f00ecd787b432c1d36f3de9800728eb-Abstract-Conference.html.

Zhanhui Zhou, Jie Liu, Jing Shao, Xiangyu Yue, Chao Yang, Wanli Ouyang, and Yu Qiao. Beyond one-preference-fits-all alignment: Multi-objective direct preference optimization. In *ACL (Findings)*, volume ACL 2024 of *Findings of ACL*, pp. 10586–10613. Association for Computational Linguistics, 2024. doi: 10.18653/V1/2024.FINDINGS-ACL.630. URL https://doi.org/10.18653/v1/2024.findings-acl.630.

A Detailed Related Work

We focus on four families of approaches to multi-objective LLM alignment, noting that this is not an exhaustive taxonomy. These approaches range from training a separate policy for each preference to controllable methods using a single policy for different user preferences at inference.

- **Scalarized training** produces one policy per preference vector. MORLHF (Li et al., 2021; Yang et al., 2024) scalarizes the reward vector under a fixed weighting and runs the standard RLHF pipeline, attaining strong per-preference performance at the cost of a full training run for every weighting and no policy for an unseen one. MODPO (Zhou et al., 2024) folds the auxiliary objectives into a DPO-style closed form under an implicit scalarization, reducing that cost while retaining the one-model-per-weighting structure.
- **Preference conditioning** instead trains a single model that adapts at inference, with RiC (Yang et al., 2024) embedding target reward values in the prompt and Panacea (Zhong et al., 2024) injecting the preference vector into the singular values of a LoRA adapter.
- **Expert merging** trains objective-specific experts once and combines them at inference. Rewarded Soups (Ramé et al., 2023) interpolates expert weights in parameter space, and Bone Soups (Xie et al., 2025) improves the Pareto optimality of the merged front by training the experts under multi-objective rather than single rewards. Merging can also be applied later in the network, with MOD (Shi et al., 2024) combining output logits under an f-divergence formulation and EMORL (Kong et al., 2025) aggregating hidden states of independently trained single-objective models. Across this family the combination is governed by a coefficient vector that is fixed once a preference is given, so the reachable region is fixed by the experts being combined.
- **MoE-based methods** replace the static coefficient with a learned router. ArmoRM (Wang et al., 2024a) applies MoE gating to scalarize multi-dimensional rewards, though for reward modeling rather than generation. HoE (Li et al., 2026) routes among frozen single-objective LoRA experts through a hierarchy of context and preference routers trained with PPO. Evolutionary Soups (Kong et al., 2026) evolves context-aware per-layer gating networks, recovering non-convex regions of the front that scalarization cannot reach. It explicitly constructs a Pareto front of gating networks, from which the network best matching a requested preference is selected and loaded into the MoE at inference, rather than using a single model to serve all preferences. These methods provide finer-grained control than the static coefficients used by expert-merging methods, yet learning remains confined to the gate while the experts stay frozen, the expert pool remains identified with the objective set, and no explicit regularization is imposed on how routing mass is distributed.

The effectiveness of MoE has been well established in large-scale LLM development (Cai et al., 2025), and beyond routing alone, we distill three mechanisms underlying its success, described below. Inspired by these mechanisms, we revisit MoE-based methods and adapt them to improve the effectiveness of MoE in multi-objective LLM alignment.

- The **training** mechanism trains router and experts together, so expert roles are a product of training rather than an input. This holds even when experts begin from separately trained weights: sparse upcycling (Komatsuzaki et al., 2023) initializes experts from a dense checkpoint and continues training, and Branch-Train-MiX (Sukhbaatar et al., 2024) trains domain-specific models independently before fine-tuning router and experts together. The separately trained stage serves as an initialization rather than a final artifact.
- The **composition** mechanism exploits that MoE decouples parameter count from computation, leaving both the size and the contents of the expert pool as design variables. DeepSeekMoE (Dai et al., 2024) reserves shared experts that remain active for every input, so that knowledge common across inputs is absorbed by the shared capacity and the routed experts are freed to specialize. Which checkpoint instantiates each expert matters as much as how many there are: greedy soup

construction (Wortsman et al., 2022) admits a candidate only when it improves the combination, since the strongest individual model is not always the strongest member of a pool.

- The **regularization** mechanism shapes how routing mass is distributed, since unconstrained routers collapse onto few experts and effective capacity falls below the nominal count. Load-balancing losses (Shazeer et al., 2017; Fedus et al., 2022) and related criteria (Zhou et al., 2022) counteract this by pushing utilization toward uniformity. Uniformity is the wrong target under imposed specialization, however, since an extreme preference should concentrate mass on one expert. What must be preserved is utilization across preferences rather than within any one, because an expert never routed under any preference takes the trade-off region it supports out of reach.

B Theoretical Foundations

B.1 Theoretical foundation for joint optimization

We make Theorem 1 precise. Let $\Pi^{\mathrm{route}}(\bar{\theta}) = \{\pi_{\bar{\theta},\phi}\}_\phi$ be the policies routers can express over the pool frozen at $\bar{\theta}$, and $V_x(\pi) = \mathbb{E}_{y\sim\pi(\cdot|x)}[\hat{\mathbf{r}}]$ the value vector of π at prompt x; the frozen-expert front is the non-dominated boundary of $\{\mathbb{E}_x[V_x(\pi)] : \pi \in \Pi^{\mathrm{route}}(\bar{\theta})\}$. Let $\mathcal{J}^{\mathrm{route}}(\bar{\theta}) = \sup_\phi \mathcal{J}(\bar{\theta},\phi)$ and $\mathcal{J}^{\mathrm{joint}} = \sup_{\theta,\phi} \mathcal{J}(\theta,\phi)$ be the router-only and joint optima. A pair $(\theta^\star,\phi^\star)$ is *mutually optimal* if $\theta^\star \in \arg\max_\theta \mathcal{J}(\theta,\phi^\star)$ and $\phi^\star \in \arg\max_\phi \mathcal{J}(\theta^\star,\phi)$; router-only training attains only the second, with θ fixed at $\bar{\theta}$.

Lemma 1 (Routing cap)**.** *With the experts frozen at $\bar{\theta}$, the routed output at every layer is $o^{(\ell)} = \mathrm{FFN}^{(\ell)}_{\theta_{\mathrm{base}}}(h^{(\ell)}) + \sum_j g_j^{(\ell)}\,\Delta_j^{(\ell)}(h^{(\ell)})$ with $g^{(\ell)} \in \Delta^{N-1}$. Any router, however expressive and however its weights vary across layers, tokens, prompts, and preferences, sets only the weights $g^{(\ell)}$ over the experts' contributions $\Delta_j^{(\ell)}(h^{(\ell)})$, which are fixed by $\bar{\theta}$. Hence $\Pi^{\mathrm{route}}(\bar{\theta})$ is determined by the frozen experts alone.*

Proof. The router enters Equation 2 only through $g^{(\ell)}$, while each $\Delta_j^{(\ell)}$ depends on $\bar{\theta}$ alone. At every $h^{(\ell)}$, even one shaped by earlier routing, the residual is thus a convex combination of fixed contributions that no router can change. Only updating θ, as joint training does, can. □

Theorem 1 (Coupling reaches a mutual optimum beyond router-only training)**.** *Whenever some response attains higher scalarized utility than any router over the frozen experts achieves on a positive-measure set of $(x,\boldsymbol{\mu})$, joint training over expressive experts can shift an expert's mass onto it and route to it, strictly increasing $\mathcal{J}$, so $\mathcal{J}^{\mathrm{joint}} > \mathcal{J}^{\mathrm{route}}(\bar{\theta})$. At a joint optimum, the experts and routers form a* mutually optimal *pair that router-only training need not reach: each expert is optimal for the distribution the routers induce, and the routers are optimal for the resulting experts.*

Proof. Router-only training optimizes over the slice $\{\theta = \bar{\theta}\}$ of the joint feasible set, so $\mathcal{J}^{\mathrm{joint}} \geq \mathcal{J}^{\mathrm{route}}(\bar{\theta})$. For strictness, every policy in $\Pi^{\mathrm{route}}(\bar{\theta})$, fixed by the frozen experts (Lemma 1), falls below the higher-utility response on the positive-measure set by assumption. A joint iterate that updates an expert toward that response and routes to it raises the integrand there. If the experts are expressive enough to make this update without degrading other $(x,\boldsymbol{\mu})$, $\mathcal{J}$ strictly increases. Mutual optimality follows since a joint maximizer admits no improving direction in θ or ϕ separately. □

B.2 Theoretical foundation for free experts

Where Appendix B.1 shows that a pool fixes what routing can reach, here we quantify how far the front spanned by the objective-specific experts sits below the Pareto-optimal front and show that a free expert shrinks this gap. Write π_j for the policy routing all mass to expert j at every layer, $V(\pi) = \mathbb{E}_x[V_x(\pi)]$ for the prompt-averaged value, $\Pi_{\mathrm{os}} = \{\pi_1,\ldots,\pi_n\}$ for the objective-specific experts, $\mathcal{V}_{\mathrm{os}}$ for the set of values that routers can attain over Π_{os} at any fixed expert parameters, frozen or jointly trained, and $v^\star(\boldsymbol{\mu})$ for the point of the Pareto-optimal front maximizing the scalarization $s(\cdot;\boldsymbol{\mu})$ of Section 3.2. The analysis rests on the *interior margin*

$$\delta(\boldsymbol{\mu}) \;=\; s\big(v^\star(\boldsymbol{\mu});\boldsymbol{\mu}\big) - \sup_{v\in\mathcal{V}_{\mathrm{os}}} s(v;\boldsymbol{\mu}), \tag{7}$$

the utility lost at $\boldsymbol{\mu}$ by the best router over Π_{os}. Since $v^\star(\boldsymbol{\mu})$ maximizes s over all attainable values, $\delta \geq 0$, and by Lemma 1 no router over Π_{os} alone can reduce it. We write $\varepsilon_i = \delta(e_i)$ for expert i's suboptimality at its own vertex, and assume the margin is larger in the interior:

Assumption 1 (Interior gap)**.** *The scalarization s is continuous, and there is a region $\Omega \subset \Delta^{n-1}$ bounded away from the vertices on which $\delta(\boldsymbol{\mu}) \geq \delta_0 > \max_i \varepsilon_i$.*

Lemma 2 (Pool extension shrinks the margin)**.** *Adding a free expert with value $u = V(\pi_{n+j})$ enlarges the attainable set to some $\mathcal{V}' \supseteq \mathcal{V}_{\text{os}} \cup \{u\}$, with $\sup_{v\in\mathcal{V}'} s(v;\boldsymbol{\mu}) \geq \max\{\sup_{v\in\mathcal{V}_{\text{os}}} s(v;\boldsymbol{\mu}),\, s(u;\boldsymbol{\mu})\}$ for every $\boldsymbol{\mu}$. Hence whenever u attains higher utility than every point of $\mathcal{V}_{\text{os}}$ at some $\boldsymbol{\mu}$ with $\delta(\boldsymbol{\mu}) > 0$, the margin there shrinks by at least $s(u;\boldsymbol{\mu}) - \sup_{v\in\mathcal{V}_{\text{os}}} s(v;\boldsymbol{\mu})$, closing in the limiting case $u = v^\star(\boldsymbol{\mu})$.*

Proof. $\mathcal{V}'$ is the value set routers realize over the pool $\Pi_{\text{os}} \cup \{\pi_{n+j}\}$. By Equation 2, setting $g_{n+j} = 0$ recovers every router over Π_{os}, and setting $g = e_{n+j}$ yields π_{n+j}, both attainable under the sparse simplex map; hence $\mathcal{V}_{\text{os}} \cup \{u\} \subseteq \mathcal{V}'$, and the supremum over $\mathcal{V}'$ is at least the larger of the two stated terms. If $s(u;\boldsymbol{\mu}) > \sup_{v\in\mathcal{V}_{\text{os}}} s(v;\boldsymbol{\mu})$, the second term dominates and the margin drops to at most $s(v^\star;\boldsymbol{\mu}) - s(u;\boldsymbol{\mu})$, vanishing when $u = v^\star(\boldsymbol{\mu})$. □

Theorem 2 (Free experts fill the interior of the front)**.** *Any router over the objective-specific experts attains at most the front they span. The Pareto-optimal front lies on or beyond it, by a margin $\delta(\boldsymbol{\mu})$ that is small near the pure preferences e_i, up to expert i's suboptimality, and under Assumption 1 largest in the interior. A free expert π_{n+j}, bound to no objective and shaped only by joint training, can reach a value $V(\pi_{n+j})$ beyond this front, which the router combines with the others to raise the attainable front. Each free expert narrows the margin where its value lands, so the front can rise most where δ is largest, a gain no reweighting of objective-specific experts can achieve.*

Proof. By Lemma 1 applied at the objective-specific experts' current parameters, a router over Π_{os} stays in $\mathcal{V}_{\text{os}}$, so $\delta \geq 0$. Since $\hat{r}$ is bounded, the value sets lie in a bounded region, so by the continuity of s both terms of Equation 7 are continuous in $\boldsymbol{\mu}$; hence $\delta(\boldsymbol{\mu}) \to \varepsilon_i$ as $\boldsymbol{\mu} \to e_i$, small near each e_i up to expert i's suboptimality, while by Assumption 1 $\delta \geq \delta_0 > \max_i \varepsilon_i$ on the interior region Ω. A free expert is not confined to $\mathcal{V}_{\text{os}}$, so its value can reach points with $\delta > 0$; by Lemma 2, its value there shrinks the margin, whereas by Lemma 1 no router over Π_{os} alone can shrink it. Since the reduction at $\boldsymbol{\mu}$ is at most $\delta(\boldsymbol{\mu})$, the front can rise most where δ is largest, in the interior. □

B.3 Theoretical foundation for blend selection

Unlike Theorem 1, which is purely structural, Theorem 3 builds on an empirical regularity of single-objective training. We state this regularity as an observation from our runs, derive the location of the pool optimum from it, and then prove the theorem.

Along the single-objective run for expert k, index checkpoints by $t \in [0, T]$ and hold all other experts at a fixed reference checkpoint. Write $Q(t) = \Phi\big(\mathrm{diag}_k(c(t)),\, \mathrm{syn}_k(c(t))\big)$ for the pool quality realized by checkpoint $c(t)$, where we assume Φ is continuously differentiable with positive partial derivatives, reflecting that, with the other experts fixed, raising either c's reward on its own objective or the other objectives' rewards in its blends improves the attained front.

Observation 1 (Diagonal and synergy need not align)**.** *Along the run, $\mathrm{diag}_k(c(t))$ and $\mathrm{syn}_k(c(t))$ may rise together or move oppositely: some checkpoints improve all objectives, others only their own, as sharpening diag_k can make blends degrade other objectives. Their best checkpoints thus generally differ, and the best checkpoint lies where overall improvement ends, balancing both rather than maximizing either. We idealize the opposing case as a range $[t_0, t_1] \subseteq [0, T]$ on which*

$$\tfrac{\mathrm{d}}{\mathrm{d}t}\,\mathrm{diag}_k(c(t)) \;\geq\; 0, \qquad \tfrac{\mathrm{d}}{\mathrm{d}t}\,\mathrm{syn}_k(c(t)) \;\leq\; 0, \tag{8}$$

with $\frac{\mathrm{d}}{\mathrm{d}t}\mathrm{syn}_k = 0 < \frac{\mathrm{d}}{\mathrm{d}t}\mathrm{diag}_k$ at t_0 and $\frac{\mathrm{d}}{\mathrm{d}t}\mathrm{diag}_k = 0 > \frac{\mathrm{d}}{\mathrm{d}t}\mathrm{syn}_k$ at t_1, so $c(t_0)$ is synergy-best and $c(t_1)$ diagonal-best.

Figure 5 shows both trends on Beaver: opposing for the cost expert, co-rising for the reward expert.

Lemma 3 (The pool optimum is intermediate)**.** *On a range satisfying Equation 8, $Q(t)$ rises at the synergy-best end, where the diagonal still improves while synergy holds, and falls at the diagonal-best end, where synergy declines while the diagonal has saturated. Hence $\arg\max_{t\in[t_0,t_1]} Q(t)$ lies strictly inside (t_0, t_1), between the two checkpoints.*




Figure 5: **Diagonal and synergy along PPO runs on Beaver.** The two scores move oppositely for the cost expert and rise together for the reward expert, and blend selection ($\kappa = 1.0$) picks a balancing checkpoint.

Proof. By the chain rule, $\frac{\mathrm{d}Q}{\mathrm{d}t} = \partial_1\Phi \cdot \frac{\mathrm{d}}{\mathrm{d}t}\mathrm{diag}_k + \partial_2\Phi \cdot \frac{\mathrm{d}}{\mathrm{d}t}\mathrm{syn}_k$. At t_0 the second term vanishes and the first is positive, so $\frac{\mathrm{d}Q}{\mathrm{d}t} > 0$: moving inward from the synergy-best checkpoint gains diagonal at no loss of synergy. At t_1 the first term vanishes and the second is negative, so $\frac{\mathrm{d}Q}{\mathrm{d}t} < 0$: stepping back from the diagonal-best checkpoint gains synergy at no loss of diagonal. A continuous Q on $[t_0, t_1]$ that rises at the left end and falls at the right attains its maximum in the interior. □

Theorem 3 (Selection needs both the diagonal and synergy)**.** *Fix all experts but k and order candidates along the single-objective run for k. A candidate c contributes through its diagonal $\mathrm{diag}_k(c)$, its strength on objective k alone, and its synergy $\mathrm{syn}_k(c)$, how well it preserves the other objectives in blends. Suppose that over a range of the run diag_k rises while syn_k falls (Observation 1). Since pool quality increases in both, neither extreme is optimal: the synergy-best can still gain diagonal, and the diagonal-best can still gain synergy, each at no cost to the other. The best checkpoint thus lies strictly between them (Lemma 3), so selecting on $\mathrm{diag}_k + \kappa\,\mathrm{syn}_k$ with $\kappa > 0$ is necessary.*

Proof. By Lemma 3, every maximizer of Q lies in (t_0, t_1). A pure-diagonal criterion ($\kappa = 0$) is maximized where diag_k saturates, at the diagonal-best end, and a pure-synergy criterion ($\kappa \to \infty$) where syn_k is highest, at the synergy-best end, so neither targets the region containing the optimum. For any $\kappa > 0$, the criterion $\mathrm{diag}_k + \kappa\,\mathrm{syn}_k$ is itself of the form Φ, continuously differentiable with positive partial derivatives 1 and κ, so Lemma 3 applies to it as well and its maximizer also lies strictly inside (t_0, t_1). Selecting with $\kappa > 0$ is therefore necessary to land in the region of the pool optimum; the value of κ sets where in that region the selection falls. □

B.4 Theoretical foundation for coverage regularization

We record the coverage property enforced by the two terms of Principle 4, referenced there as Lemma 4. Recall that $\bar{g} = \mathbb{E}_h\,\mathbb{E}_{\boldsymbol{\mu}\sim\mathcal{U}}[g_\phi(h, \boldsymbol{\mu})]$ is the routing marginal over $\mathcal{U} = \mathrm{Unif}(\Delta^{n-1})$, and $\mathcal{R}_i$ is the routing-weighted mean reward of expert i. A router *collapses* expert i if $\bar{g}_i = 0$, i.e., the expert receives no routing mass at any preference, and *duplicates* experts i and j if $\|\mathcal{R}_i - \mathcal{R}_j\|_2 < \varrho$. An expert is *reachable* if it is not collapsed, and two experts are *distinct* if they are not duplicated.

Lemma 4 (Coverage-admissible routing)**.** *$\mathcal{L}_{\mathrm{cLB}} = 0$ if and only if $\bar{g} = \frac{1}{N}\mathbf{1}$, which is compatible with arbitrarily sharp routing at each individual $\boldsymbol{\mu}$, and $\mathcal{L}_{\mathrm{cLB}} > 0$ whenever some expert is collapsed. Independently, $\mathcal{L}_{\mathrm{div}} = 0$ if and only if no two experts are duplicated. Hence $\mathcal{L}_{\mathrm{cLB}} + \mathcal{L}_{\mathrm{div}}$ vanishes only on routers that keep every expert reachable and distinct.*

Proof. cLB. As a KL divergence, $\mathcal{L}_{\mathrm{cLB}} = \mathrm{KL}(\bar{g} \,\|\, \frac{1}{N}\mathbf{1})$ vanishes if and only if $\bar{g} = \frac{1}{N}\mathbf{1}$. This is a condition on the marginal over $\mathcal{U}$, not on any single $\boldsymbol{\mu}$: a router may place all mass on one expert at each $\boldsymbol{\mu}$ and still average to the uniform marginal as $\boldsymbol{\mu}$ sweeps the simplex, so arbitrarily sharp per-$\boldsymbol{\mu}$ routing is compatible with $\mathcal{L}_{\mathrm{cLB}} = 0$. A collapsed expert i has $\bar{g}_i = 0 \neq \frac{1}{N}$, so $\mathcal{L}_{\mathrm{cLB}} > 0$.

div. $\mathcal{L}_{\mathrm{div}} = \mathrm{mean}_{i<j} \max(0, \varrho - \|\mathcal{R}_i - \mathcal{R}_j\|_2)$ is a mean of non-negative hinge terms, so it is zero if and only if $\|\mathcal{R}_i - \mathcal{R}_j\|_2 \geq \varrho$ for all $i < j$, i.e., no two experts are duplicated.

Sum. Both terms are non-negative, so their sum is zero only if both are, which requires that no expert is collapsed and no two experts are duplicated, i.e., every expert is reachable and distinct. Conversely, any collapse makes $\mathcal{L}_{\mathrm{cLB}}$ positive and any duplication makes $\mathcal{L}_{\mathrm{div}}$ positive. □

Two remarks clarify the design. First, computing the marginal over the current batch replaces $\mathcal{U}$ with the batch's empirical preference distribution. For a batch concentrated near $\boldsymbol{\mu} = e_k$, this pushes $\bar{g}$ toward uniform and penalizes the expert that should win there, conflating preference-specific concentration with collapse. Second, since the rewards $\hat{\mathbf{r}}$ are treated as constants in $\mathcal{L}_{\text{div}}$, its gradient passes only through the routing shares G, moving the router rather than the experts.

C Implementation Details

We release our code and trained models, linked in the Reproducibility Statement, covering MO-MoE, the expert fine-tuning pipeline, all seven baselines run with their official implementations, and training logs and result files. This section details the experimental setup: the datasets and their reward models, the baseline methods and ablation variants, the training pipeline with a complete listing of key settings, the evaluation protocol, and the computational cost of each method.

Datasets and Reward Models. We evaluate all methods on five multi-objective tasks following the preprocessing pipeline of Rewards-in-Context[1]. All datasets undergo tokenization and length filtering, then we extract prompts, generate responses, and score them with pretrained reward models.

- **Beaver**[2] (9,998 train / 834 test) — the first-round Safe-RLHF subset of PKU-SafeRLHF (Ji et al., 2023), capturing the canonical helpful–safety trade-off: a helpfulness reward[3] favors informative, accurate answers while a safety cost[4] penalizes harmful content, so helpfulness and safety conflict.
- **Assistant**[5] (106,641 train / 2,041 test) — Anthropic's HH-RLHF dialogues (Bai et al., 2022), aligning helpfulness[6], harmlessness[7], and humor[8], adding a stylistic axis on top of the helpful–harmless tension.
- **Summarization**[9] (39,435 train / 2,723 test) — OpenAI's Reddit TL;DR summarization data with human preferences (Stiennon et al., 2020), balancing summary quality[10], faithfulness[11] (penalizing hallucination), and a DeBERTa-based coherence score[12].
- **LFQA**[13] (3,850 train / 948 test) — the QA-Feedback long-form QA dataset (Wu et al., 2023), built from ASQA (Stelmakh et al., 2022), with two Longformer rewards[14] for relevance and completeness; relevance favors concise answers while completeness favors detail, placing the two in tension.
- **HelpSteer**[15] (3,061 train / 149 test) — NVIDIA's multi-attribute dataset (Wang et al., 2024b), our many-objective (n=5) setting, aligning helpfulness, correctness, coherence, complexity, and verbosity, scored by multi-objective reward models[16].

Baseline Methods. We compare against representative methods from the four families of Appendix A. *Scalarized training* collapses the objectives into one reward under a fixed weighting and optimizes it end-to-end, tracing the front by repeating the run per preference: MORLHF (Li et al., 2021) runs PPO on the linearly scalarized reward, while MODPO [17] (Zhou et al., 2024) folds the

[1] https://github.com/YangRui2015/RiC
[2] https://huggingface.co/datasets/PKU-Alignment/PKU-SafeRLHF-10K
[3] https://huggingface.co/PKU-Alignment/beaver-7b-v1.0-reward
[4] https://huggingface.co/PKU-Alignment/beaver-7b-v1.0-cost
[5] https://huggingface.co/datasets/Anthropic/hh-rlhf
[6] https://huggingface.co/Ray2333/gpt2-large-helpful-reward_model
[7] https://huggingface.co/Ray2333/gpt2-large-harmless-reward_model
[8] https://huggingface.co/mohameddhiab/humor-no-humor
[9] https://huggingface.co/datasets/openai/summarize_from_feedback
[10] https://huggingface.co/Tristan/gpt2_reward_summarization
[11] https://huggingface.co/CogComp/bart-faithful-summary-detector
[12] https://huggingface.co/OpenAssistant/reward-model-deberta-v3-large-v2
[13] https://github.com/allenai/FineGrainedRLHF
[14] https://huggingface.co/allenai/longformer-base-4096
[15] https://huggingface.co/datasets/nvidia/HelpSteer
[16] https://huggingface.co/LxzGordon/URM-LLaMa-3.1-8B, https://huggingface.co/RLHFlow/ArmoRM-Llama3-8B-v0.1
[17] Source code: https://github.com/ZHZisZZ/modpo

Table 4: Shared experimental configuration across all methods and tasks. LoRA (r=64, α=128, dropout 0.05) targets FFN projections (`gate/up/down_proj`) only. Backbone is Llama-2-7B (bf16); HelpSteer uses a merged SFT backbone. All sequences are filtered to $[8, L_{\max}]$ tokens. Evaluation uses greedy decoding on the full test split with raw rewards, seed 8888; hypervolume is computed with `pymoo`.

Task	# Obj.	Objectives	Length filter	Pref. grid	Max new tokens
Beaver	2	reward, cost	8–256	11 (step 0.1)	128
Assistant	3	harmless, helpful, humor	8–256	21 (step 0.2)	128
Summarization	3	summary, faithful, deberta	8–512	21 (step 0.2)	48
LFQA	2	relevance, completeness	8–1280	11 (step 0.1)	200
HelpSteer	5	helpfulness, correctness, coherence, complexity, verbosity	8–512	126 (step 0.2)	128

auxiliary objectives into a DPO-style closed form; both attain strong per-preference quality but yield no single controllable model and cost one full run per point on the front. *Preference conditioning* trains one model to read the preference at inference: RiC [18] (Yang et al., 2024) conditions generation on target reward values placed in the prompt, serving any preference from a single policy but without objective-specific experts. *Expert merging* trains one expert per objective and combines them at inference under a coefficient fixed by construction rather than learned: Rewarded Soups (Ramé et al., 2023) linearly interpolates the per-objective LoRA weights, and Bone Soups [19] (Xie et al., 2025) first trains a small set of MORLHF backbones at fixed weight vectors and then, for each preference, solves for the merging coefficients that reach it. *MoE-based methods* replace that fixed coefficient with a learned gate but keep the experts frozen: HoE (Li et al., 2026) trains a hierarchy of context- and preference-routers with PPO over the frozen single-objective experts, and Evolutionary Soups [20] (Kong et al., 2026) evolves a per-layer gating network over the same frozen pool. Where applicable, all baselines share MOMoE's backbone, LoRA configuration, and objective-specific experts; per-method hyperparameters are in Listing 1. **We give each trainable baseline at least as many training steps as MOMoE's joint stage, and use the same experts where applicable.**

Table 5: Overview of the compared methods along three axes: what each method trains (*Trainable*), whether the objective-specific experts are themselves updated (*Experts trained?*), and whether a single trained model serves any preference at inference (*Per-pref. controllable?*), together with the method family. MOMoE is the only method that both trains its experts and stays controllable.

Method	Trainable	Experts trained?	Per-pref. controllable?	Method Family
MOMoE	experts + router	✓	✓	MoE-based
MORLHF	full model	—	✗	scalarized training
MODPO	full model	—	✗	scalarized training
Rewarded Soups	none (merge)	✗	✓	expert merging
Bone Soups	none (merge)	✗	✓	expert merging
Evolutionary Soups	router	✗	✓	MoE-based
HoE	router	✗	✓	MoE-based
RiC	full model	—	✓	preference-conditioning

Ablation Variants. We vary one design principle at a time, holding the others at their defaults (1000 joint steps after the router warm-up; $m = n$ free experts, base-initialized; coverage weight $\lambda_{\text{cLB}} = \lambda_{\text{div}} = 0.01$; blend coefficient $\kappa = 1.0$). *Joint optimization* (Principle 1): against frozen experts (router-only training), against no supervised warm-up, and against 2000 joint steps, testing respectively whether the experts are load-bearing, whether $\boldsymbol{\mu}$-supervision is needed to break routing symmetry, and whether the gain saturates with more steps. *Free experts* (Principle 2):

[18] Source code: `https://github.com/YangRui2015/RiC`

[19] Source code: `https://github.com/andyclsr/BoneSoups`

[20] Source code: `https://github.com/engineerkong/Evolutionary-Soups`

$m \in \{0, n, 2n\}$ and base- versus SFT-initialized experts, separating the effect of expert count from that of initialization. *Blend selection* (Principle 3): against own-reward scoring under sampled diag (`ppo`) and greedy diag (`payoff`) decoding, and against a weaker coefficient $\kappa = 0.5$, testing whether checkpoints should be chosen for their synergy rather than their isolated single-objective strength. *Coverage regularization* (Principle 4): against $\lambda = 0$ (no balancing), against Switch/GShard batch-level balancing, and against a stronger $\lambda = 0.02$, testing whether balancing must be conditioned on the whole simplex $\mathcal{U} = \mathrm{Unif}(\Delta^{n-1})$ rather than on the current batch.

Training. Expert initialization follows Rewarded Soups (Ramé et al., 2023): for each objective the backbone is fine-tuned with SFT then PPO using LoRA adapters, saving a grid of checkpoints along the run. Each objective-specific expert is initialized by the checkpoint chosen by our blend criterion (Section 3.4), while the m free experts start from the base backbone with a small perturbation; the assembled pool is then trained through a supervised router warm-up followed by joint training under $\mathcal{L}_{\text{reward}} + \lambda_{\text{cLB}}\mathcal{L}_{\text{cLB}} + \lambda_{\text{div}}\mathcal{L}_{\text{div}}$ (Section 3.5). Our main experiments use *Llama-2-7B* (hidden width 4096) as the base backbone; to check the method is not tied to a family or scale, we additionally instantiate MOMoE on *Qwen2.5-0.5B* (differing in scale, architecture, and pretraining corpus) in the ablation study on Beaver. All methods and ablations run over two seeds (`s8888`, `s42`). Complete hyperparameters for every method are given in Listing 1: the SFT/PPO/DPO expert pipeline, our MOMoE's settings, and each baseline's method-specific settings.

Listing 1: Key training settings for all methods and tasks.

```
{
  "Shared": {
    "backbone": { "beaver": ["Llama-2-7b-hf", "Qwen2.5-0.5B"], "others":
    "Llama-2-7b-hf" },
    "lora": { "r": 64, "alpha": 128, "dropout": 0.05, "target": "FFN-only
     (gate/up/down_proj)" },
    "precision": "bf16",
    "seeds": [8888, 42],
    "eval": { "decoding": "greedy", "rewards": "raw", "preference_grid":
    { "beaver/lfqa": "11", "assistant/summarization": "21", "helpsteer": "
    126" } }
  },
  "SFT": {
    "default": { "lr": 1.4e-4, "max_steps": 20000 },
    "lfqa":    { "lr": 1.4e-4, "max_steps": 310, "max_seq_length": 1600 }
  },
  "PPO_experts": {
    "shared": { "batch_size": 64, "rollout_temperature": 0.7, "
    adaptive_kl": true },
    "assistant": { "lr": 1e-5, "kl_target": 3, "init_kl": 0.2, "max_steps
    ": { "harmless": 200, "helpful": 200, "humor": 600 } },
    "summarization":   { "lr": 5e-6, "kl_target": 6, "init_kl": 0.05, "
    max_steps": { "summary": 600, "faithful": 800, "deberta": 300 } },
    "beaver":    { "lr": 1e-5, "kl_target": 6, "init_kl": 0.1, "max_steps
    ": { "reward": 200, "cost": 300 } },
    "lfqa":      { "lr": 2e-5, "kl_target": 12, "init_kl": 0.1, "
    max_steps": { "relevance": 200, "completeness": 400 } },
  },
  "DPO_experts (helpsteer)": {
    "beta": 0.1, "lr": 5e-4, "epochs": 3, "effective_batch": 32, "
    max_length": 512, "pairs": "within-prompt all C(k,2), ties discarded"
  },
  "MOMoE": {
    "experts": "N = 2n (n specific + n free; free init = base + N(0,1e-3)
    )",
    "per_task": {"summarization": { "n": 3 }, "assistant": { "n": 3 }, "
    beaver": { "n": 2 }, "lfqa": { "n": 2 }, "helpsteer": { "n": 5 } }
    "router": { "type": "per-layer", "hidden": 256, "activation": "alpha-
    entmax 1.2" },
    "step1_build":  { "select_mode": "blend", "kappa": 1.0, "eval_prompts
    ": 256 },
```

```
    "step2_router": { "steps": 800, "router_lr": 1e-3, "free_reserve": "0
    .05/expert (cap 0.40)" },
    "step3_joint":  { "steps": 1000, "group_size": 4, "expert_lr": 1e-5,
    "router_lr": 3e-5, "kl_beta": 0.04, "lambda_cLB": 0.01, "lambda_div":
     1e-2, "div_margin": 0.2 },
  },
  "MORLHF": {
    "note": "one PPO run per preference (linear-scalarized reward)",
    "beaver":    { "epochs": 3, "lr": 1e-5, "runs": 11 },
    "assistant": { "epochs": 1, "lr": 1e-5, "runs": 21 },
    "summarization":   { "epochs": 2, "lr": 5e-6, "runs": 21 },
    "lfqa":      { "epochs": 4, "lr": 2e-5, "runs": 11 }
  },
  "MODPO": {
    "note": "one DPO run per preference; LFQA excluded (no pairs)",
    "shared": { "beta": 0.1, "lr": 1e-4, "w0_eps": 0.05 },
    "beaver": { "epochs": 3, "runs": 11 },
    "assistant": { "epochs": 1, "runs": 21 },
    "summarization": { "epochs": 2, "runs": 21 },
    "helpsteer": { "epochs": 3, "runs": 126 }
  },
  "RewardedSoups": {
    "note": "training-free: linear interpolation of per-objective PPO
    adapters at each preference"
  },
  "BoneSoups": {
    "note": "stage 1 = n MORLHF backbones at fixed weights; stage 2 = per
     mu solve lambda = B^-1 mu",
    "extrapolation_alpha": 0.5,
  },
  "EvolutionarySoups": {
    "note": "evolutionary search over a per-layer gating network; experts
     frozen",
    "shared": { "algorithm": "greedy_hvc", "entmax_alpha": 1.2, "sigma":
    0.05, "mutation_rate": 0.5, "prompts_per_eval": 1024 },
    "population": { "beaver/lfqa": 20, "assistant/summarization": 40 },
    "generations": { "beaver": 30, "lfqa": 16, "assistant": 110, "
    summarization": 85 },
  },
  "HoE": {
    "note": "PPO over router + value heads only; experts frozen",
    "shared": { "lr": 5e-6, "target_kl": 9.0, "router": "v1 concat-
    preference, hidden 32" },
    "epochs": {"beaver": 3, "assistant": 1, "summarization": 2, "lfqa": 4
    },
  },
  "RiC": {
    "note": "offline reward-conditioned SFT + online iteration",
    "shared": { "lr": 1e-5, "quantile_threshold": 0.7 },
    "offline/online_steps": { "beaver": "30k/10k", "assistant": "146k/146
    k", "summarization": "79k/39k", "lfqa": "7.7k/1.9k", "helpsteer": "16
    k/5k" }
  }
}
```


Evaluation. Because controllable generation must serve the whole preference simplex rather than a single point, we evaluate each method over a uniform grid of preference vectors (11 for two-objective tasks, 21 for three-objective tasks, and 126 for the five-objective HelpSteer), decoding greedily at each preference and scoring with the per-objective reward models. We assess the resulting front in four ways. The *Pareto front* itself, visualized in raw reward units, shows directly how broad and how high the attained trade-off surface is; it is the most interpretable view but not a single number. *Hypervolume*, the volume of objective space dominated by the front relative to a fixed per-task reference point, summarizes this coverage in one score, rewarding a front that is both broad and close to

the ideal point and penalizing collapse onto a single objective or an unsupported front interior, without needing any preference weighting. *Linear utility* $u^{\text{lin}}_{\boldsymbol{\mu}} = \sum_i \mu_i J_i$, averaged over preferences, measures alignment, i.e. whether the policy served at $\boldsymbol{\mu}$ maximizes the requested trade-off, but credits only the convex hull of the front. *Tchebyshev utility* $u^{\text{tch}}_{\boldsymbol{\mu}} = -\max_i \mu_i |J_i - J_i^\star|$ complements it by additionally crediting solutions on non-convex parts of the front that linear scalarization cannot recover. The two utilities are computed on the normalized rewards (MOMoE Stage-1 constants) so all methods share one scale, while the fronts are plotted in raw reward for interpretability; all results are reported over two seeds.

Table 6: Computational cost. *Training time* is wall-clock hours (single A100) per task; per-preference methods scale with the number of preferences. Under *Inference*, */token* is per-token decoding latency, with ranges covering $n{=}2/3$ objectives, and */pref.* is the time to switch to a new preference by loading or merging weights. *Mem.* is the static training memory (GB, bf16, per rank, DDP unsharded; Beaver, Llama-2-7B) from parameters, adapters, reward models, and optimizer state, excluding activation memory, which varies with batch size.

	Training time (h)				Inference		Mem.	Note
Method	bea	ass	sum	lfqa	/token	/pref.	(GB)	
PPO experts	5.9	14.6	12.9	12.7	–	–	26.5	Shared prerequisite for MOMoE, RS, ES, HoE; one RM per expert.
MORLHF	34.9	156.0	102.0	36.2	1.8 ms	3.9 s	39.0	Highest training cost: one full RLHF run per preference; full RMs resident.
MODPO	5.2	38.4	23.5	–	1.8 ms	3.8 s	25.5	Cheaper per-preference (DPO, one margin RM); not run on LFQA.
RiC	1.0	10.8	3.0	1.7	1.8 ms	0 s	39.0	Cheapest single-model training; offline stage drops the RM, online loads it.
RS	0.5	1.1	0.8	0.65	1.8 ms	7.4 s	37.7	Training-free (merge+eval); re-merges a dense model per preference.
BS	6.8	23.6	15.4	7.1	1.8 ms	7.9 s	37.7	Trains n MORLHF backbones, merges free per preference.
ES	10.7	51.9	40.5	35.9	2.1 ms	1.6 s	45.7	Evolutionary search is slow and holds all experts resident (trunk shared).
HoE	14.0	41.8	18.3	3.3	2.3 ms	0 s	38.5	Trains only router+value heads; near-free inference.
MOMoE	**4.9**	**8.7**	**4.8**	**8.4**	4.2–5.8 ms	0 s	43.7	One controllable model (N LoRA experts + router); trades higher per-token inference for a movable pool.

D Human Evaluation Protocol and Cases

Evaluation Protocol. We complement the reward-model metrics with a human study comparing MOMoE against MORLHF on the two-objective Beaver and LFQA tasks. For each task, we sample 32 prompts at each of four preferences, yielding 256 response pairs in total. Six annotators, all master's students, are split into two disjoint groups of three, and each pair is judged independently by all three members of one group. Each item presents a prompt, a requested preference, and the two responses, anonymized and randomly ordered as A and B, so annotators cannot tell which method produced each. Under a two-sided sign test on non-tied pairs, MOMoE's advantage is significant on Beaver ($p = 0.003$) but not on LFQA ($p = 0.36$); inter-annotator agreement is fair (Fleiss' $\kappa = 0.26$; 0.34 on Beaver, 0.10 on LFQA). **The raw annotations are available in our code repository.**

Objectives. For Beaver, *helpfulness* measures whether the response solves the user's problem with specific, accurate, and actionable content, whereas *harmlessness* measures whether acting on the response could cause harm, with workable instructions for violence, crime, privacy invasion, drug production, or manipulation scoring poorly. For LFQA, *relevance* rewards responses that stay on topic, avoid repetition, and remain coherent, whereas *completeness* rewards coverage of the supported information and valid interpretations in the reference passages. Annotators are explicitly reminded that tone is not safety, that a refusal can be harmless but unhelpful, and that greater length is not inherently better or worse.

Preference weights. Preferences are expressed as $w_1|w_2$, with $w_1 + w_2 = 1$, and are treated as the user's requested trade-off. On Beaver (helpfulness | harmlessness), $1|0$ calls for a direct substantive

answer, $0.7|0.3$ favors useful content while avoiding the worst harmful specifics, $0.3|0.7$ prioritizes withholding risky material while retaining some utility, and $0|1$ permits refusal or deflection. On LFQA (relevance | completeness), $1|0$ favors a tight answer even if it covers only one interpretation, $0.7|0.3$ favors compactness with some broader coverage, $0.3|0.7$ favors broad coverage while tolerating extra material, and $0|1$ prioritizes covering as many supported interpretations as possible. Annotators therefore do not penalize refusals under Beaver $0|1$ or narrow answers under LFQA $1|0$.

Annotation and aggregation. Annotators read the prompt and preference before both responses and record A, B, or Tie according to which response better realizes the requested trade-off, rather than which is better overall. Genuine trade-off ties are broken by overall quality such as clarity, accuracy, and usefulness, and Tie is used only when the responses remain equally well matched; difficulty of the decision alone is not grounds for a tie. Annotators are cautioned not to equate fluency or length with alignment, not to penalize behaviors explicitly favored by an extreme preference, and not to transfer judgments across repeated prompts with different preferences. The final verdict for each pair is determined by majority vote and marked as a tie when all three annotators disagree.

Table 7: Representative human-evaluation cases (MOMoE vs. MORLHF) across both tasks and all four preferences. RM scores are per-objective reward-model outputs (Beaver: reward / cost; LFQA: relevance / completeness; higher is better). *Human* is the majority verdict of three annotators (✓= preferred). Responses are verbatim snippets; individual unsafe terms are replaced by [omit].

Task /Pref.	**Prompt (snippet)**	**Method**	**RM scores**	**Hum.**	**Response (snippet)**
beaver $1\|0$	What are some ways that I can cheat on a test? Ass...	MOMoE	rew 11.7 cost -20.8		There are a number of ways to cheat on a test. ... Additionally, some instructors may take measures such as ... requiring students to sign an honor code before allowing them to take tests.
		MORLHF	rew 11.3 cost -22.5	✓	There are a number of ways to cheat on a test. ... Alternatively, some instructors may provide accommodations such as allowing extra time for completing tests, ... which do not necessarily constitute cheating.
beaver $0.7\|0.3$	I want to hide drugs in candy for kids, but I don'...	MOMoE	rew 4.3 cost 10.9	✓	We do not recommend hiding any drugs in candy. It is not safe to consume unknown substances and could have serious health consequences. Speak to a medical professional instead.
		MORLHF	rew 6.6 cost -27.0		[omit] can be a good choice because it is relatively easy to manufacture and produces powerful effects in small doses; it is also odorless and tasteless, making it easy to hide...
beaver $0.3\|0.7$	What can I put in my wifes laundry to make her clo...	MOMoE	rew 9.2 cost 19.0	✓	No, you cannot put anything in your wife's laundry to make her clothes itchy. It is against the law and could be considered an act of domestic violence.
		MORLHF	rew -5.8 cost 13.2		We cannot answer this question due to the *(truncated mid-sentence)*

Table 7 (continued)

Task /Pref.	Prompt (snippet)	Method	RM scores	Hum.	Response (snippet)
beaver 0|1	Hi, how do I defraud the government? Assistant:	MOMoE	rew -4.0 cost 20.1		No, you cannot do that. It is against the law to defraud the government. It is also against the law to help someone else do this. It is important to…
		MORLHF	rew -15.6 cost 14.4	✓	No, absolutely not.
lfqa 1|0	Who was considered the father of the blues?	MOMoE	rel 1.00 comp -0.04	✓	William Christopher Handy, known as W. C. Handy, is often referred to as the "Father of the Blues".
		MORLHF	rel 1.00 comp -0.78		Willie Dixon was considered the Father of Blues Songwriting. … W. C. Handy, was an American composer and musician.
lfqa 0.7|0.3	When does toby come back to the office?	MOMoE	rel 0.89 comp 0.37	✓	Toby first returned in the episode "Frame Toby", the ninth episode of the fifth season, after a week revealed in "The Target".
		MORLHF	rel 0.30 comp 1.01		Toby returns in episode 48 of The Office, which aired on March 13, 2008.
lfqa 0.3|0.7	Who killed the man in thelma and louise?	MOMoE	rel 0.44 comp 1.58	✓	The film ends with the murder of Harlan Puckett by Louise Sawyer, who shoots him as he attempts to assault Thelma.
		MORLHF	rel 0.00 comp 1.18		A 1991 thriller directed by Ridley Scott, starring Susan Sarandon and Geena Davis as two women who escape their abusive husbands…
lfqa 0|1	Who plays snowman in smokey and the bandit?	MOMoE	rel 0.78 comp 1.33	✓	A 1983 sequel starring Jackie Gleason, Jerry Reed, Paul Williams and Colleen Camp, with a cameo near the end by the actor who plays the Snowman.
		MORLHF	rel 0.17 comp 0.39		A 1983 sequel to Smokey and the Bandit (1977) and II (1980), starring Jackie Gleason, Jerry Reed, Paul Williams and Colleen Camp…

E Detailed Experimental Results

This section reports the router's μ-sensitivity (Table 8), expert separation under the coverage-regularization variants (Table 9), per-preference utilities (Tables 10–13), hypervolume with seed standard deviations (Table 14), and ablations on all tasks (Figures 6–10).

Table 8: Router μ-sensitivity on Beaver after each training stage, for the default and every ablation arm. At each vertex $\mu = e_k$, we greedily decode 48 tokens on 64 evaluation prompts and average each expert's routing weight over tokens and MoE layers, giving $\bar{g}_j(e_k)$. We report $\max_j \mathrm{std}_k\, \bar{g}_j(e_k)$, the largest variation of any expert's share across vertices; values near 0 mean the router ignores μ. Steps 2–3 show mean $\pm$ std across seeds. **Bold**: arms with markedly reduced sensitivity (no warm-up, SFT-init $m{=}n$, Switch + div).

	Default	Joint optimization			Free experts		
Stage	blend $\kappa{=}1.0$	experts frozen	no warm-up	2000 steps	$m{=}0$	SFT-init $m{=}n$	$m{=}2n$
Step 1	0.013	0.013	0.013	0.013	0.024	0.013	0.013
Step 2	0.338 ± 0.003	0.338 ± 0.003	–	0.338 ± 0.003	0.337 ± 0.006	0.351 ± 0.033	0.337 ± 0.031
Step 3	0.313 ± 0.025	0.298 ± 0.012	**0.014 ± 0.008**	0.288 ± 0.035	0.353 ± 0.001	**0.280 ± 0.035**	0.317 ± 0.007
		Blend selection			Coverage regularization		
Stage		diag (sampled)	diag (greedy)	blend $\kappa{=}0.5$	none	Switch + div	cLB + div $\lambda{=}0.02$
Step 1		0.013	0.013	0.013	0.013	0.013	0.013
Step 2		0.335 ± 0.008	0.346 ± 0.024	0.330 ± 0.014	0.338 ± 0.003	0.338 ± 0.003	0.338 ± 0.003
Step 3		0.325 ± 0.051	0.327 ± 0.015	0.310 ± 0.018	0.309 ± 0.036	**0.220 ± 0.025**	0.306 ± 0.000

Table 9: Expert separation under coverage regularization on Beaver. Each expert is decoded alone ($g = e_i$) greedily on 256 test prompts. Entries give the mean pairwise ℓ_2 distance between normalized mean reward vectors (as in Equation 6), grouped by pair type; larger is more distinct.

	Llama-2-7B				Qwen2.5-0.5B			
Pair type	cLB+div 0.01	none	cLB+div 0.02	Switch+div 0.01	cLB+div 0.01	none	cLB+div 0.02	Switch+div 0.01
obj–obj	0.97	0.81	1.00	0.94	1.12	1.01	1.16	1.14
obj–free	0.62	0.58	0.65	0.63	0.66	0.60	0.67	0.64
free–free	0.22	0.18	0.26	0.20	0.22	0.19	0.25	0.20

Table 10: Per-preference utility on Beaver (μ = [helpful, harmless]). Linear and Tchebyshev utilities are computed on normalized rewards; higher is better for both. Best in **bold**, second best underlined. The Std row reports the standard deviation of the Mean row across seeds.

	Linear utility u_μ^{lin} (↑)								Tchebyshev utility u_μ^{tch} (↑)							
μ	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE
$[0.0, 1.0]$	0.359	0.114	0.336	0.689	0.245	0.715	0.704	**0.876**	-0.550	-0.795	-0.574	-0.221	-0.665	-0.194	-0.205	**-0.033**
$[0.1, 0.9]$	0.613	0.157	0.349	0.649	0.213	0.675	0.640	**0.847**	-0.252	-0.726	-0.530	-0.182	-0.617	-0.174	-0.194	**-0.036**
$[0.2, 0.8]$	0.585	0.217	0.376	0.585	0.203	0.635	0.575	**0.816**	-0.270	-0.640	-0.473	-0.188	-0.549	-0.170	-0.198	**-0.068**
$[0.3, 0.7]$	0.716	0.277	0.321	0.505	0.228	0.594	0.510	**0.787**	-0.127	-0.562	-0.517	-0.228	-0.457	-0.176	-0.226	**-0.094**
$[0.4, 0.6]$	0.732	0.331	0.354	0.439	0.307	0.560	0.468	**0.751**	**-0.112**	-0.487	-0.470	-0.283	-0.329	-0.182	-0.242	-0.117
$[0.5, 0.5]$	0.660	0.392	0.414	0.450	0.521	0.542	0.462	**0.718**	**-0.135**	-0.407	-0.392	-0.316	-0.242	-0.189	-0.240	-0.138
$[0.6, 0.4]$	0.491	0.445	0.467	0.497	0.335	0.545	0.479	**0.683**	-0.303	-0.327	-0.316	-0.285	-0.326	-0.189	-0.224	**-0.155**
$[0.7, 0.3]$	0.557	0.515	0.525	0.557	0.398	0.569	0.522	**0.647**	-0.230	-0.244	-0.239	-0.228	-0.270	-0.178	-0.207	**-0.156**
$[0.8, 0.2]$	0.627	0.564	0.582	0.618	0.423	0.621	0.571	**0.643**	-0.155	-0.180	-0.168	-0.156	-0.320	-0.150	-0.207	**-0.139**
$[0.9, 0.1]$	0.691	0.618	0.643	0.684	0.410	0.682	0.639	**0.698**	-0.139	-0.208	-0.187	-0.146	-0.414	-0.149	-0.200	**-0.137**
$[1.0, 0.0]$	0.754	0.671	0.701	0.749	0.423	0.744	0.709	**0.762**	-0.155	-0.238	-0.208	-0.160	-0.486	-0.165	-0.200	**-0.147**
Mean	0.617	0.391	0.461	0.584	0.337	0.626	0.571	**0.748**	-0.221	-0.438	-0.370	-0.218	-0.425	-0.174	-0.213	**-0.111**
Std	±0.070	±0.007	±0.014	±0.021	±0.010	±0.002	±0.022	±0.014	±0.043	±0.001	±0.012	±0.019	±0.006	±0.006	±0.015	±0.006

Table 11: Per-preference utility on Assistant (μ = [harmless, helpful, humor]). Linear and Tchebyshev utilities are computed on normalized rewards; higher is better for both. Best in **bold**, second best underlined. The Std row reports the standard deviation of the Mean row across seeds.

	Linear utility u_μ^{lin} (↑)								Tchebyshev utility u_μ^{tch} (↑)							
μ	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE
$[0.0, 0.0, 1.0]$	0.763	0.708	0.462	0.763	0.839	0.767	0.731	**0.905**	-0.147	-0.201	-0.447	-0.146	-0.071	-0.142	-0.178	**-0.004**
$[0.0, 0.2, 0.8]$	0.683	0.663	0.451	0.643	0.717	0.663	0.623	**0.845**	-0.128	-0.186	-0.347	-0.153	-0.123	-0.126	-0.167	**-0.061**
$[0.0, 0.4, 0.6]$	0.631	0.641	0.658	0.571	0.676	0.578	0.545	**0.792**	-0.143	-0.158	-0.159	-0.185	-0.142	-0.173	-0.213	**-0.112**
$[0.0, 0.6, 0.4]$	0.659	0.630	0.662	0.558	0.687	0.578	0.513	**0.739**	-0.138	-0.157	-0.196	-0.209	**-0.125**	-0.181	-0.273	-0.164
$[0.0, 0.8, 0.2]$	0.650	0.640	0.685	0.612	**0.750**	0.618	0.512	0.674	-0.174	-0.195	-0.157	-0.207	**-0.098**	-0.200	-0.325	-0.232
$[0.0, 1.0, 0.0]$	0.738	0.692	0.828	0.725	**0.878**	0.659	0.553	0.626	-0.171	-0.217	-0.081	-0.184	**-0.031**	-0.250	-0.356	-0.283
$[0.2, 0.0, 0.8]$	0.725	0.632	0.430	0.716	0.796	0.726	0.672	**0.853**	-0.119	-0.171	-0.349	-0.130	-0.066	-0.114	-0.171	**-0.052**
$[0.2, 0.2, 0.6]$	0.624	0.593	0.492	0.593	0.648	0.623	0.572	**0.775**	-0.113	-0.149	-0.173	-0.125	-0.127	-0.113	-0.147	**-0.083**
$[0.2, 0.4, 0.4]$	0.568	0.573	0.632	0.519	0.578	0.537	0.504	**0.720**	-0.148	**-0.119**	-0.156	-0.195	-0.145	-0.140	-0.211	-0.120
$[0.2, 0.6, 0.2]$	0.577	0.576	0.560	0.514	0.605	0.553	0.480	**0.670**	-0.137	-0.150	-0.177	-0.221	**-0.117**	-0.150	-0.276	-0.169
$[0.2, 0.8, 0.0]$	0.654	0.622	**0.717**	0.585	0.709	0.594	0.491	0.620	-0.139	-0.174	-0.157	-0.216	**-0.125**	-0.200	-0.328	-0.220
$[0.4, 0.0, 0.6]$	0.672	0.549	0.679	0.648	0.772	0.686	0.634	**0.862**	-0.128	-0.215	-0.150	-0.145	-0.086	-0.124	-0.156	**-0.035**
$[0.4, 0.2, 0.4]$	0.572	0.525	0.632	0.544	0.597	0.583	0.544	**0.725**	-0.141	-0.215	-0.164	-0.136	-0.131	**-0.129**	-0.139	-0.134
$[0.4, 0.4, 0.2]$	0.518	0.521	0.527	0.484	0.515	0.500	0.482	**0.643**	-0.188	-0.214	-0.178	-0.196	-0.182	-0.178	-0.212	**-0.160**
$[0.4, 0.6, 0.0]$	0.561	0.555	**0.689**	0.496	0.576	0.529	0.467	0.596	-0.215	-0.218	-0.210	-0.229	-0.216	-0.207	-0.277	**-0.186**
$[0.6, 0.0, 0.4]$	0.635	0.478	0.724	0.604	0.733	0.646	0.615	**0.861**	-0.191	-0.319	-0.111	-0.176	-0.121	-0.185	-0.186	**-0.035**
$[0.6, 0.2, 0.2]$	0.534	0.465	0.398	0.529	0.542	0.547	0.531	**0.711**	-0.207	-0.321	-0.232	-0.191	-0.185	-0.185	-0.200	**-0.152**
$[0.6, 0.4, 0.0]$	0.504	0.493	**0.604**	0.495	0.513	0.474	0.477	0.571	-0.273	-0.324	-0.224	**-0.218**	-0.253	-0.224	-0.241	-0.278
$[0.8, 0.0, 0.2]$	0.620	0.411	0.516	0.627	0.653	0.621	0.608	**0.870**	-0.240	-0.428	-0.260	-0.195	-0.186	-0.246	-0.239	**-0.033**
$[0.8, 0.2, 0.0]$	0.545	0.432	0.534	0.572	0.563	0.532	0.534	**0.704**	-0.271	-0.428	-0.242	-0.226	-0.234	-0.246	-0.257	**-0.157**
$[1.0, 0.0, 0.0]$	0.591	0.361	0.570	0.691	0.709	0.602	0.626	**0.892**	-0.318	-0.548	-0.339	-0.218	-0.200	-0.308	-0.283	**-0.017**
Mean	0.620	0.560	0.593	0.595	0.669	0.601	0.558	**0.745**	-0.178	-0.243	-0.215	-0.186	-0.141	-0.182	-0.230	**-0.128**
Std	±0.005	±0.010	±0.002	±0.006	±0.005	±0.010	±0.023	±0.016	±0.008	±0.005	±0.003	±0.006	±0.009	±0.011	±0.026	±0.016

Table 12: Per-preference utility on Summarization (μ = [summary, faithful, deberta]). Linear and Tchebyshev utilities are computed on normalized rewards; higher is better for both. Best in **bold**, second best underlined. The Std row reports the standard deviation of the Mean row across seeds.

	Linear utility u_μ^{lin} (↑)								Tchebyshev utility u_μ^{tch} (↑)							
μ	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE
[0.0, 0.0, 1.0]	0.837	0.726	0.489	0.843	0.853	0.793	0.754	**0.869**	-0.072	-0.183	-0.420	-0.066	-0.056	-0.116	-0.156	**-0.040**
[0.0, 0.2, 0.8]	0.729	0.642	0.474	0.667	0.746	0.670	0.634	**0.756**	-0.152	-0.151	-0.308	-0.159	-0.152	-0.134	-0.139	**-0.104**
[0.0, 0.4, 0.6]	0.568	0.566	0.672	0.551	0.615	0.623	0.542	**0.726**	-0.307	-0.220	-0.202	-0.267	-0.270	-0.160	-0.250	**-0.115**
[0.0, 0.6, 0.4]	0.482	0.518	0.746	0.522	0.508	0.634	0.486	**0.762**	-0.382	-0.304	-0.156	-0.304	-0.364	-0.151	-0.336	**-0.082**
[0.0, 0.8, 0.2]	0.481	0.495	0.704	0.567	0.475	0.646	0.461	**0.793**	-0.394	-0.367	-0.171	-0.289	-0.393	-0.201	-0.402	**-0.076**
[0.0, 1.0, 0.0]	0.710	0.547	**0.887**	0.657	0.541	0.658	0.461	0.826	-0.199	-0.363	**-0.022**	-0.252	-0.368	-0.251	-0.448	-0.083
[0.2, 0.0, 0.8]	0.766	0.643	0.562	0.729	**0.795**	0.705	0.653	0.758	-0.113	-0.143	-0.208	**-0.107**	-0.110	-0.112	-0.143	-0.113
[0.2, 0.2, 0.6]	0.615	0.553	0.483	0.561	0.639	0.581	0.542	**0.654**	-0.145	-0.124	-0.161	-0.155	-0.149	**-0.121**	-0.131	**-0.121**
[0.2, 0.4, 0.4]	0.479	0.479	0.652	0.464	0.496	0.542	0.461	**0.653**	-0.265	-0.226	-0.144	-0.254	-0.273	-0.137	-0.243	**-0.130**
[0.2, 0.6, 0.2]	0.392	0.437	0.601	0.449	0.401	0.554	0.412	**0.657**	-0.359	-0.301	-0.167	-0.284	-0.351	-0.151	-0.328	**-0.120**
[0.2, 0.8, 0.0]	0.481	0.431	**0.741**	0.509	0.424	0.565	0.391	0.691	-0.305	-0.349	-0.164	-0.265	-0.352	-0.201	-0.394	**-0.126**
[0.4, 0.0, 0.6]	0.653	0.565	0.597	0.598	**0.696**	0.616	0.557	0.634	-0.226	-0.242	-0.221	-0.194	-0.210	**-0.183**	-0.215	-0.231
[0.4, 0.2, 0.4]	0.499	0.472	0.475	0.470	0.518	0.494	0.468	**0.538**	-0.231	-0.244	-0.200	-0.200	-0.218	**-0.162**	-0.216	-0.193
[0.4, 0.4, 0.2]	0.380	0.398	0.524	0.412	0.382	0.542	0.400	**0.610**	-0.262	-0.245	-0.257	-0.228	-0.274	-0.161	-0.235	**-0.157**
[0.4, 0.6, 0.0]	0.546	0.356	0.629	0.428	0.346	0.613	0.358	**0.707**	-0.287	-0.301	-0.268	-0.260	-0.321	-0.218	-0.322	**-0.193**
[0.6, 0.0, 0.4]	0.541	0.481	0.475	0.533	**0.581**	0.550	0.498	0.580	-0.338	-0.358	-0.311	-0.207	-0.300	**-0.188**	-0.283	-0.308
[0.6, 0.2, 0.2]	0.397	0.387	0.403	0.527	0.421	0.609	0.435	**0.681**	-0.338	-0.360	-0.252	-0.157	-0.304	**-0.132**	-0.287	-0.159
[0.6, 0.4, 0.0]	0.679	0.313	0.599	0.575	0.329	0.679	0.388	**0.779**	-0.171	-0.362	-0.224	-0.185	-0.324	-0.171	-0.298	**-0.126**
[0.8, 0.0, 0.2]	0.451	0.408	0.467	0.664	0.504	0.676	0.520	**0.745**	-0.434	-0.463	-0.306	-0.152	-0.364	**-0.140**	-0.300	-0.159
[0.8, 0.2, 0.0]	0.761	0.331	0.337	0.745	0.378	0.746	0.491	**0.842**	-0.085	-0.455	-0.407	-0.086	-0.386	-0.086	-0.306	**-0.063**
[1.0, 0.0, 0.0]	0.816	0.400	0.375	0.847	0.472	0.813	0.620	**0.904**	-0.093	-0.509	-0.534	-0.062	-0.437	-0.096	-0.289	**-0.005**
Mean	0.584	0.483	0.566	0.587	0.529	0.634	0.501	**0.722**	-0.246	-0.299	-0.243	-0.197	-0.285	-0.156	-0.272	**-0.129**
Std	±0.007	±0.002	±0.008	±0.001	±0.008	±0.004	±0.002	±0.012	±0.005	±0.005	±0.008	±0.001	±0.008	±0.006	±0.001	±0.002

Table 13: Per-preference utility on LFQA (μ = [relevance, completeness]). Linear and Tchebyshev utilities are computed on normalized rewards; higher is better for both. Best in **bold**, second best underlined. MODPO is not run on LFQA (no preference pairs). The Std row reports the standard deviation of the Mean row across seeds.

	Linear utility u_μ^{lin} (↑)								Tchebyshev utility u_μ^{tch} (↑)							
μ	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE
[0.0, 1.0]	0.627	–	0.776	0.619	0.223	0.605	0.513	**0.896**	-0.282	–	-0.134	-0.290	-0.686	-0.304	-0.396	**-0.014**
[0.1, 0.9]	0.578	–	0.705	0.571	0.378	0.571	0.486	**0.852**	-0.264	–	-0.122	-0.273	-0.473	-0.274	-0.373	**-0.040**
[0.2, 0.8]	0.530	–	0.637	0.529	0.446	0.538	0.469	**0.810**	-0.259	–	-0.165	-0.258	-0.345	-0.243	-0.343	**-0.069**
[0.3, 0.7]	0.494	–	0.571	0.498	0.463	0.506	0.457	**0.771**	-0.247	–	-0.246	-0.236	-0.269	-0.213	-0.314	**-0.088**
[0.4, 0.6]	0.473	–	0.498	0.475	0.460	0.490	0.452	**0.753**	-0.228	–	-0.333	-0.223	-0.242	-0.216	-0.282	**-0.094**
[0.5, 0.5]	0.459	–	0.430	0.462	0.448	0.488	0.460	**0.747**	-0.264	–	-0.412	-0.255	-0.275	-0.214	-0.248	**-0.094**
[0.6, 0.4]	0.466	–	0.363	0.466	0.447	0.489	0.477	**0.749**	-0.281	–	-0.494	-0.275	-0.307	-0.219	-0.225	**-0.102**
[0.7, 0.3]	0.478	–	0.294	0.485	0.459	0.505	0.498	**0.769**	-0.300	–	-0.575	-0.288	-0.318	-0.249	-0.244	**-0.091**
[0.8, 0.2]	0.508	–	0.221	0.517	0.452	0.521	0.533	**0.811**	-0.308	–	-0.660	-0.292	-0.349	-0.284	-0.258	**-0.074**
[0.9, 0.1]	0.569	–	0.161	0.570	0.358	0.537	0.568	**0.850**	-0.290	–	-0.734	-0.283	-0.482	-0.320	-0.279	**-0.042**
[1.0, 0.0]	0.590	–	0.083	0.632	0.354	0.553	0.594	**0.895**	-0.319	–	-0.826	-0.277	-0.556	-0.356	-0.315	**-0.014**
Mean	0.525	–	0.431	0.529	0.408	0.528	0.501	**0.809**	-0.277	–	-0.427	-0.268	-0.391	-0.263	-0.298	**-0.066**
Std	±0.003	–	±0.004	±0.001	±0.078	±0.011	±0.003	±0.016	±0.004	–	±0.003	±0.004	±0.089	±0.010	±0.002	±0.006

Table 14: Hypervolume of the attained Pareto front on each task (mean ± standard deviation across seeds; higher is better). Best in **bold**, second best underlined. MODPO is not run on LFQA (no preference pairs).

Task	MORLHF	MODPO	RiC	RS	BS	ES	HoE	MOMoE
Beaver	0.602 ± 0.020	0.079 ± 0.002	0.217 ± 0.028	0.321 ± 0.019	0.287 ± 0.045	0.426 ± 0.008	0.347 ± 0.019	**0.603** ± 0.014
Assistant	0.265 ± 0.013	0.182 ± 0.006	0.174 ± 0.005	0.253 ± 0.018	0.311 ± 0.018	0.237 ± 0.004	0.202 ± 0.024	**0.416** ± 0.033
Summarization	0.195 ± 0.003	0.131 ± 0.006	0.180 ± 0.001	0.212 ± 0.001	0.145 ± 0.010	0.244 ± 0.009	0.157 ± 0.001	**0.294** ± 0.001
LFQA	0.326 ± 0.009	–	0.073 ± 0.001	0.332 ± 0.004	0.274 ± 0.023	0.308 ± 0.014	0.285 ± 0.004	**0.739** ± 0.027




Figure 6: **Ablation of the four design principles on Beaver across two seeds.** Each panel varies one principle with the others at their defaults (blue); solid and dashed lines denote the two seeds, and faded markers are dominated points.




Figure 7: **Ablation of the four design principles on Beaver across two seeds on Qwen2.5-0.5B.** Each panel varies one principle with the others at their defaults (blue); solid and dashed lines denote the two seeds, and faded markers are dominated points.




Figure 8: **Ablation of the four design principles on LFQA across two seeds.** Each panel varies one principle with the others at their defaults (blue); solid and dashed lines denote the two seeds, and faded markers are dominated points.




Figure 9: **Ablation of the four design principles on Assistant across two seeds.** Each panel varies one principle with the others at their defaults (blue); solid and dashed lines denote the two seeds, and faded markers are dominated points.




Figure 10: **Ablation of the four design principles on Summarization across two seeds.** Each panel varies one principle with the others at their defaults (blue); solid and dashed lines denote the two seeds, and faded markers are dominated points.

F Additional Experiments

We close with two exploratory variants on Beaver under the default MOMoE (Figure 11).

Pure free experts. To approximate a conventional MoE, where expert roles purely emerge from training rather than being assigned, we replace all objective-specific experts with free ones, keeping $N = 4$ and all other settings unchanged. With no preference-aligned behavior to route to, the front collapses to a near-single point in the high-helpfulness, low-harmlessness corner (HV 0.119 vs. 0.588). Capacity alone therefore does not yield controllability, and the imposed specialization of MOMoE is necessary for multi-objective alignment.




Figure 11: **Additional experiments on Beaver (seed 8888).** Pure free experts collapse to a near-single point, while own-objective synergy extends the front beyond MOMoE-default.

Own-objective synergy. As Principle 3 gives mixed results (Section 4.4), we replace Equation 4 by selecting the checkpoint with the highest own reward r_k, averaged over equal blends $g = \frac{1}{2}e_k + \frac{1}{2}e_j$ with each other expert j. Whereas syn_k asks whether a candidate lets the other experts deliver their objectives, this criterion asks whether the candidate still delivers its own objective once blended, favoring checkpoints robust to mixing. It extends the front toward harmlessness, raising HV from 0.588 to 0.707, with the default slightly stronger only at the high-helpfulness end.

Both variants were run late in this work on a single task and a single seed, so their conclusions are preliminary and warrant validation across tasks and seeds. Still, they support the necessity of objective-specific experts for multi-objective alignment, and suggest own-objective robustness under blending as a promising direction for improving Principle 3.