LEARNING WHAT TO FORGET: DISTRIBUTIONAL UNLEARNING FOR LLM REPRESENTATION SPACES

Anonymous authors
Paper under double-blind review

ABSTRACT

Machine learning systems increasingly face the need to remove the influence of entire data domains, such as toxic language, harmful behavior, or topical content, rather than isolated records. Recent work formalizes this problem as *distributional unlearning*: selecting a subset of a forget domain whose removal moves the training distribution away from an unwanted population while preserving proximity to the desired one. However, existing analyses often impose parametric assumptions to obtain tractable selection rules. These assumptions may be poorly suited to high-dimensional language-model representations. We introduce MAMUSHI, a framework for non-parametric distributional unlearning that ranks forget examples using a probabilistic classifier whose Bayes-optimal logit equals the forget-to-retain log-density ratio (up to an additive class-prior constant). We show that thresholding the population log-density ratio yields the optimal fixed-budget selection rule for our removal–preservation objective and establish a non-asymptotic transfer guarantee relating score-estimation and threshold-calibration errors to degradation from the population-optimal selection rule. Our empirical evaluation spans real-world datasets on toxic-language removal and topical-domain removal regimes using different representations, with MAMUSHI achieving a more favorable removal–preservation trade-off than other baselines. Our work shows that MAMUSHI can serve as an efficient selection approach for downstream machine unlearning procedures, reducing the number of forget examples required to reach a fixed forgetting target.

Content warning: This paper contains examples of toxic and offensive language, included for illustrative and evaluation purposes. Reader discretion is advised.

1 INTRODUCTION

Machine-learning models are increasingly deployed in settings where the data used for training may later become legally, ethically, or operationally objectionable (Jobin et al., 2019; Wachter et al., 2017). This has motivated a growing literature on machine unlearning, whose goal is to modify a trained model so that the influence of designated data is removed while preserving performance on the remaining data. Existing work has studied certified deletion (Guo et al., 2020), data-sharding approaches (Bourtoule et al., 2020), gradient-based removal (Neel et al., 2020; Kurmanji et al., 2023), and concept- or class-level forgetting (Ravfogel et al., 2020; Belrose et al., 2023; Kodge et al., 2024). The scale of unlearning requests is now growing beyond individual records toward erasing entire subpopulations—unwanted domains, concepts, or data-defined constructs such as harmful biases or toxic language (Eldan & Russinovich, 2023; Liu et al., 2025b). The key insight is that not all samples are equally potent—some are statistically prototypical of the forget domain, far from the distribution we would like to retain, while others sit near the boundary with limited distributional impact.

This observation about potency heterogeneity is deeply relevant to natural language. In Natural Language Processing (NLP), it is well established that within any semantic category, some examples are far more representative of the class and are responsible for driving the model behavior than others (Rosch, 1975; Swayamdipta et al., 2020; Koh & Liang, 2017; Carlini et al., 2021). This raises a fundamental question:

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

What is the minimal set of data points to remove from the forget set for maximal distributional impact where data is natural language?

The closest to our work is *Distributional Machine Unlearning*, introduced by Allouah et al. (2026). Rather than requiring the removal of individual records, distributional unlearning treats the forget and retain populations as probability distributions. An edited distribution is required to be sufficiently far from the forget distribution while remaining close to the retain distribution. This statistical framing is addressed through *selective removal*: under a fixed budget β on the forget set, rather than deleting random data points, one removes the samples with the largest effect on the removal–preservation trade-off. Figure 1 illustrates three scenarios that motivate this approach. First, the realistic scenario where our model is trained on forget and retain distribution. Second, how partial removal of forget distribution shapes the training data, and finally the oracle condition i.e. had the model been trained on retain distribution only. However, their analysis majorly assumes that both distributions are Gaussian in nature.




Figure 1: Training Data Distribution shift from Contaminated to Oracle

In this paper we answer the above precise research question by modeling natural language using Large Language Model (LLM) embeddings, where parametric assumptions are violated (Park et al., 2024). Specifically, we extend selective distributional unlearning to high-dimensional LLM embeddings, replacing parametric distance scores with an *estimated log-density ratio* that makes no assumption on the distributions, through the lens of statistical decision theory, reducing density-ratio estimation to standard binary classification (Menon & Ong, 2016; Reid & Williamson, 2011).

We propose MAMUSHI, [1] a selective-removal framework that operationalizes this insight for data-centric LLM unlearning. MAMUSHI trains a conditional model to distinguish forget embeddings from retain embeddings in the LLM's representation space. We show that thresholding the log-density ratio is optimal among fixed-budget deletion rules at the population level, and analyze the effect of replacing true score with its learned counterpart, obtaining a selection-regret bound in terms of score-estimation error and local concentration of scores near the selection threshold. Our contributions are as follows,

- **Learned density-ratio selection.** We present a framework that *directly* estimates the forget–retain log-density ratio in LLM representation space using a learned Bayes-Optimal Classifier, circumventing the need for parametric assumptions.
- **Population optimality.** We show that thresholding the population log-density ratio gives the optimal fixed-budget selection rule for the removal–preservation objectives, extending the frontier analysis of Allouah et al. (2026) to non-parametric settings.
- **Selection guarantees.** We bound the degradation caused by replacing true score with the learned score, translating score-estimation error into bounds on achieved removal and preservation levels.
- **LLM evaluation.** We evaluate MAMUSHI on the Jigsaw Toxic Comment dataset (Jigsaw/Conversation AI, 2019) and 20 Newsgroups dataset (Mitchell, 1997) across three model families—Llama-3.1-8B (Grattafiori et al., 2024), Qwen-2.5-7B (Yang et al., 2025), and Gemma-2-2B (Team et al., 2024). MAMUSHI consistently achieves the tightest recovery, with the largest gains occurring at intermediate deletion budgets and also aiding in efficient downstream sample-level unlearning.

[1] We call our method MAMUSHI, after the Japanese pit viper (*Gloydius blomhoffii*) reflecting its selective targeting of undesirable 'toxic' forget set examples.

2 Related Works

Unlearning Granularity: Records vs. Populations. Recent work has studied the removal of knowledge, memorized text, or undesired behavior from language models. Eldan & Russinovich (2023) consider approximate unlearning of a textual domain, illustrating the difficulty of removing the influence of a coherent body of text from a language model. Complementary work shows that language models may verbatim complete sequences that were not explicitly present in the training data, due to overlapping or redundant contexts (Liu et al., 2025a). These findings suggest that removing an individual document or a small collection of records may not eliminate the broader statistical footprint of a domain. This provides relevant perspectives on the unit of forgetting and on the distinction between data removal and model modification. In our work, we do not directly edit the language model to remove a concept, nor do we provide a record-level certificate for an arbitrary deletion request. Instead, we study the data-selection problem that precedes retraining or a downstream unlearning update. In this sense, MAMUSHI can serve as a selective data-removal front end for various LLM unlearning methods.

Selective data removal, pruning, and coresets. MAMUSHI is related to data pruning, coreset construction, influence-based selection, and data selection for efficient training (Mirzasoleiman et al., 2020; Killamsetty et al., 2021; Li et al., 2024a; Sener & Savarese, 2018). These methods generally seek a subset that preserves the performance, representativeness, or training utility of a single population. This is orthogonal to the goal of data selection for distributional unlearning. This distinction is important. A point can be highly representative of the forget distribution and still be a poor removal candidate if similar points remain in the retain population. Conversely, a point with a large forget-retain tradeoff may be particularly valuable to remove even if it is not selected by a conventional representativeness or coreset criterion. MAMUSHI therefore treats selective removal as a two-distribution problem rather than as ordinary dataset pruning.

Likelihood-Ratio Scoring and Representation Geometry. In the context of distributional machine unlearning, Allouah et al. (2026) study the likelihood-ratio formulation under explicit parametric assumptions, modeling the relevant distributions as Gaussians and deriving analytical removal–preservation trade-offs. This parametric setting is useful because it makes the likelihood-ratio geometry tractable. LR-COS can be viewed as a spherical or angular approximation to the shared isotropic-Gaussian likelihood ratio, whereas LR-MAHA is the more direct covariance-aware Gaussian analogue. We note full-covariance implementation in Mahalanobis scoring is often prohibitive for LLM embeddings ($O(d^2)$ in memory and $O(d^3)$ in computation) (Mahalanobis, 1936). In addition, the covariance estimate can be unstable or ill-conditioned when the number of forget or retain samples is not large relative to the embedding dimension. More broadly, there is no established marginal family for LLM embeddings and no universally accepted metric that is guaranteed to describe their geometry across models, layers, pooling procedures, datasets, and tasks. MAMUSHI is motivated by this gap: it retains the likelihood-ratio principle used in the parametric Gaussian formulation, but avoids committing in advance to a Gaussian, spherical, Mahalanobis, or cosine geometry.

We discuss other related subfields in Appendix A.

3 Preliminaries

Distributional Machine Unlearning. Mamushi builds on the Distributional Machine-Unlearning framework of Allouah et al. (2026). In this formulation, unlearning is defined at the level of populations rather than individual records: for tolerances $\alpha > 0, \varepsilon > 0$, the goal is to identify an edited distribution $p \in \mathcal{P}$, such that it is sufficiently distant from a forget distribution (p_1) while remaining close to a retain distribution (p_2). This can be formalized through,

$$\mathrm{KL}(p_1 \| p) \geq \alpha, \qquad \mathrm{KL}(p_2 \| p) \leq \varepsilon. \tag{1}$$

In practice, these true distributions are unknown. In accordance with Allouah et al. (2026), we work with finite sets of samples: $S_1 = \{x_i^{(1)}\}_{i=1}^{n_1}$ drawn i.i.d. from unwanted distribution p_1, and $S_2 = \{x_j^{(2)}\}_{j=1}^{n_2}$ from retained distribution p_2, with $n_2 \gg n_1$ for most real-world scenarios. While we adopt this distributional objective and selective-removal viewpoint, our work targets high-dimensional LLM embeddings where distributional geometry remains unspecified by a trusted parametric model.

Domain & Representation Space. As discussed in Section 2, the relevant unit of unlearning may be a population of related examples rather than a single record. We study this problem in the representation space of a language model. Let $T \in \mathcal{T}$ denote a text sequence and let $X = \varphi(T) \in \mathcal{X} \subseteq \mathbb{R}^d$ denote its representation under some embedding map $\varphi : \mathcal{T} \to \mathcal{X}$. The forget and retain domains induce, through this map, corresponding *population distributions* p_1 and p_2 over the representation space $\mathcal{X}$: each is the distribution of the representation $X = \varphi(T)$ as T ranges over its domain.

We model p_1 and p_2 as continuous densities on the *same* underlying representation space $\mathcal{X}$, absolutely continuous with respect to a common dominating measure, and treat the finite set of observed embeddings as an i.i.d. sample from these population densities. Modeling learned text representations as continuous distributions is well established: high-dimensional length-normalized embeddings are naturally directional data, modeled by continuous densities on the hypersphere (Banerjee et al., 2005; Meng et al., 2019), and recent work shows autoregressive LLM embeddings encode the latent generating distribution of their input (Zhang et al., 2025).

Bayes-optimal classification and likelihood-ratio selection. At its core, our approach leverages a learned estimate of the true density ratio to identify samples most (least) prototypical of forget (retain) set. The selection score MAMUSHI aims to estimate in turn is connected to the classical likelihood-ratio principle in statistical decision theory (Neyman & Pearson, 1933; Wald, 1992). Consider a binary classification problem with class-conditional embedding distributions p_1 and p_2. Under class priors π_1 and π_2, Bayes' rule gives

$$\frac{\Pr(Y = 1 \mid X = x)}{\Pr(Y = 0 \mid X = x)} = \frac{\pi_1}{\pi_2} \frac{p_1(x)}{p_2(x)}.$$

Thus, the posterior odds are proportional to the likelihood ratio, and the log-posterior odds satisfy

$$\ell^*(x) := \operatorname{logit} \Pr(Y = 1 \mid X = x) = \log \frac{p_1(x)}{p_2(x)} + \log \frac{\pi_1}{\pi_2}. \tag{2}$$

Eq. 2 characterizes the ideal population-level selection rule, while connecting to the theory of Bayes-optimal scoring functions and proper losses (Reid & Williamson, 2010; 2011) and binary classification (Menon & Ong, 2016). We note our method is agnostic to the choice of probabilistic classifier; any discriminative model that estimates $\Pr(Y = 1 \mid X = x)$ can be used. MAMUSHI therefore refers to the selection principle rather than to a particular classifier architecture.

4 MAIN ALGORITHM

Method and Ranking. In our framework, we train a probabilistic binary classifier to distinguish representations on the forget set (with label 1) and the retain set (with label 0). We use the learned classifier-generated score $\widehat{\ell}(x)$ for each forget example $x \in S_1$, as an estimate of the relative density forget-versus-retain evidence for x. We then sort the examples in S_1 in descending order of our estimated score. Given a budget K such that $K = \lfloor \beta \cdot n_1 \rfloor$, MAMUSHI selects $\widehat{S}_K = \mathrm{TopK}_{x \in S_1} \widehat{\ell}(x)$. Thus, MAMUSHI uses the classifier only to determine the selection ranking. We provide additional details regarding training in the Appendix C.2.

How does MAMUSHI avoid the parametric assumption? We notice from Eq. 2, a large value of the forget-to-retain log-density ratio $\ell^*(x)$ indicates that x is relatively likely (unlikely) under the forget (retain) distribution, making such points natural candidates for selection[2]. In practice however, MAMUSHI does not have access to $\ell^*(x)$ directly. With our learned estimate $\widehat{\ell}$[3], we aim to *directly learn* $\ell^*(x)$, circumventing the need to assume that the LLM embeddings arise from a particular parametric marginal distribution.

[2]From Eq. 2 under equal class priors, the density-ratio is exactly equal to the logit. However, $\log \frac{\pi_1}{\pi_2}$ is constant in x, the offset does not affect the ranking nor the selected region later in Section 5. We therefore use $\ell^*(x) = \log \frac{p_1(x)}{p_2(x)}$ as our convention.

[3]To be consistent with the convention applied to $\ell^*(x)$, in order to remove the nuisance variable $\log \frac{n_1}{n_2}$ we train with balanced class weights. Consequently, $\widehat{\ell}(x)$ denotes the estimated log-density ratio itself. Henceforth, $\ell^*(x)$ and $\widehat{\ell}(x)$ refer to the true and estimated density ratios, with prior constants disregarded.

Comparing against prior parametric approaches (Allouah et al., 2026), suppose that the representation conditional on the domain label c follows a Gaussian distribution, $x \mid c \sim \mathcal{N}(\mu_c, \Sigma_c)$, $c \in \{1, 2\}$, where $c = 1$ denotes the forget distribution and $c = 2$ denotes the retain distribution. The corresponding Gaussian log-density ratio is

$$\ell_{\mathrm{G}}(x) = \log \frac{\mathcal{N}(x; \mu_1, \Sigma_1)}{\mathcal{N}(x; \mu_2, \Sigma_2)} = \frac{1}{2} x^\top \left(\Sigma_2^{-1} - \Sigma_1^{-1}\right) x + \left(\Sigma_1^{-1}\mu_1 - \Sigma_2^{-1}\mu_2\right)^\top x + C \tag{3}$$

where C is independent of x. Thus, when the covariance matrices differ, the Gaussian log-density ratio contains both a quadratic term and a linear term. If the two domains share a covariance matrix, $\Sigma_1 = \Sigma_2 = \Sigma$, the quadratic terms cancel and Eq. 3 becomes $\ell_{\mathrm{G}}(x) = (\mu_1 - \mu_2)^\top \Sigma^{-1} x + C$. In the isotropic case, $\Sigma_c = \sigma^2 I$ for both domains, this reduces Eq. 3 to $\ell_{\mathrm{G}}(x) = \frac{1}{\sigma^2}(\mu_1 - \mu_2)^\top x + C$. Finally, under the unit-covariance assumption $\Sigma_1 = \Sigma_2 = I$, $\ell_{\mathrm{G}}(x) = (\mu_1 - \mu_2)^\top x + C$. Therefore, in this most restrictive case, the Gaussian likelihood-ratio ranking depends only on the projection of x onto the mean-difference direction. This Gaussian progression clarifies the relationship to the Allouah et al. (2026)'s *likelihood ratio inspired* baselines. LR-MAHA uses a covariance-aware distance contrast, $s_{\text{LR-Maha}}(x) = d_{\text{Maha}}(x, \mu_2) - d_{\text{Maha}}(x, \mu_1)$, where $d_{\text{Maha}}(x, \mu) = \sqrt{(x-\mu)^\top \Sigma^{-1}(x-\mu)}$. Similarly, LR-COS replaces the covariance-aware Mahalanobis geometry with cosine distance: $s_{\text{LR-COS}}(x) = d_{\cos}(x, \mu_2) - d_{\cos}(x, \mu_1)$, where $d_{\cos}(x, \mu) = 1 - \frac{x^\top \mu}{\|x\|_2 \|\mu\|_2}$. It can therefore be viewed as a non-Euclidean, angular analogue of the same centroid-contrast idea. While these assumptions simplify the ranking process, they are too restrictive for high-dimensional LLM embeddings (Aggarwal et al., 2001; Steck et al., 2024).

Why is Binary Cross Entropy (BCE) the correct minimization objective? In practice, given representations of examples from the forget and retain sets, we train an MLP using BCE (Appendix C.2). The use of BCE gives the score a useful population interpretation. In particular, the following result shows that the logit of the population-optimal BCE classifier coincides with the forget-to-retain log-density ratio, up to a class-prior-dependent constant.

Lemma 4.1. *Let p_1 and p_2 be probability distributions on $\mathcal{X}$. Consider the binary classification model: $Y \sim \text{Bernoulli}(\pi_1)$, $X \mid Y = 1 \sim p_1$, $X \mid Y = 0 \sim p_2$, where $\pi_2 := 1 - \pi_1$. Let D^* be the population minimizer of the unweighted binary cross-entropy risk, $\mathcal{L}(D) = -\mathbb{E}_{(x,y)}\left[y \log D(x) + (1-y)\log(1-D(x))\right]$. Given $p_1(x)$, $p_2(x) > 0$, the population minimizer satisfies $D^*(x) = \frac{\pi_1 p_1(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)}$ which yields*

$$\text{logit}(D^*(x)) = \log \frac{p_1(x)}{p_2(x)} + \log \frac{\pi_1}{\pi_2}.$$

5 Selection Optimality and Transfer Guarantees

In this section we study the validity and efficiency of MAMUSHI. We start by characterizing the effect of deleting an arbitrary measurable region of the fixed forget distribution (Lemma 5.1) under Eq. 1 to isolate the quantity that the deletion rule must optimize. We then show that, under a fixed deletion budget, the optimal deletion region is obtained by thresholding the true forget-to-retain log-density ratio (Proposition 5.2). Finally, we analyze the effect of replacing the population log-density ratio with an estimated score under a transfer guarantee (Theorem 5.6).

Fixing a deletion budget $\beta \in [0, 1]$, and supposing $S \subseteq \mathcal{X}$ be any measurable arbitrary deletion region satisfying

$$p_1(S) = \beta.$$

We model deletion by removing the p_1-mass contained in S while leaving the retain distribution unchanged. The resulting edited mixture is

$$p_{-S}(x) = \frac{\pi_1 p_1(x)\, \mathbf{1}\{x \notin S\} + \pi_2 p_2(x)}{Z_\beta}, \qquad Z_\beta = \pi_1(1-\beta) + \pi_2 = 1 - \pi_1 \beta. \tag{4}$$

The normalization factor depends only on the deletion budget, since $p_1(S) = \beta$, and not on the identity of S. The following lemma decomposes the removal and preservation divergences into terms that depend only on the deletion budget and terms that depend on the selected region S.

Lemma 5.1. *Fix $\beta \in [0,1]$ and let $S \subseteq \mathcal{X}$ be measurable with $p_1(S) = \beta$, inducing the edited mixture p_{-S} (Eq. 4). Let $\phi(u) := \log(1 + \frac{\pi_1}{\pi_2} e^u)$. Then there exist constants $C_{\mathrm{rem}}(\beta; \pi_1, \pi_2, p_1, p_2)$ and $C_{\mathrm{pres}}(\beta; \pi_1, \pi_2, p_1, p_2)$, independent of the identity of S, such that*

$$\mathrm{KL}(p_1 \| p_{-S}) = C_{\mathrm{rem}}(\beta; \pi_1, \pi_2, p_1, p_2) + \int_S p_1(x)\, \phi(\ell^*(x))\, \mathrm{d}x,$$

and

$$\mathrm{KL}(p_2 \| p_{-S}) = C_{\mathrm{pres}}(\beta; \pi_1, \pi_2, p_1, p_2) + \int_S p_2(x)\, \phi(\ell^*(x))\, \mathrm{d}x.$$

Therefore, Lemma 5.1 points that once the deletion budget is fixed, the identity of the selected region affects the two KL-divergences only through the mass that the region captures under p_1 and p_2. The desired selector should therefore capture regions that are highly characteristic of p_1 while avoiding regions that are also strongly represented under p_2, and the log-density ratio ℓ^* provides exactly this forget-versus-retain comparison.

Proposition 5.2. *Under the setting of Lemma 5.1, let*

$$S = \{x \in \mathcal{X} : \ell^*(x) \geq \tau\},$$

where τ is chosen so that $p_1(S) = \beta$. Then S simultaneously maximizes removal i.e. $\mathrm{KL}(p_1 \| p_{-S})$ and minimizes preservation i.e. $\mathrm{KL}(p_2 \| p_{-S})$ among all measurable sets S satisfying $p_1(S) = \beta$.

Hence, Proposition 5.2 characterizes the population oracle selector S^*, defined by thresholding the unknown log-density ratio ℓ^*. The result is estimator-agnostic: any procedure that estimates the population log-density ratio targets the same oracle selection rule, with the quality of the resulting selection determined by its score and threshold-estimation errors.

To study the effect of estimating this oracle score from finite data, we adopt a training-agnostic view. We analyze the effect of replacing the ideal score ℓ^* with a learned approximation $\widehat{\ell}$ and separately account for error in calibrating the corresponding deletion threshold. Our subsequent analysis uses two regularity conditions, motivated by standard analyses of density-ratio estimation (Sugiyama et al., 2012; Cortes et al., 2010) and margin-based classification (Mammen & Tsybakov, 1999; Audibert & Tsybakov, 2007).

Assumption 5.3 (Bounded density ratio)**.** p_1 and p_2 are mutually absolutely continuous and there exists $B < \infty$ with $|\ell^*(x)| = |\log \frac{p_1(x)}{p_2(x)}| \leq B$ for p_1- and p_2-almost every x.

Assumption 5.4 (Margin condition at the deletion threshold)**.** Let τ^* satisfy $p_1(\ell^*(X) > \tau^*) = \beta$. The score $\ell^*(X)$, $X \sim p_1$, admits a density f_ℓ on $I_{\delta_0} = [\tau^* - \delta_0, \tau^* + \delta_0]$ with $f_\ell(t) \leq M < \infty$ for all $t \in I_{\delta_0}$.

Remark 5.5 (Role of the regularity assumptions). Assumption 5.3 controls the magnitude of the population log-density ratio, while Assumption 5.4 controls the amount of score mass in a neighborhood of the deletion threshold. Hence, our assumptions are introduced solely to obtain quantitative transfer bounds and do not impose a parametric family on the embedding distributions.

The following result gives a transfer guarantee: if the learned score is close to the population log-density ratio and the estimated threshold is close to the oracle threshold, then the resulting edited distribution remains close to the population-optimal removal–preservation frontier.

Theorem 5.6 (Selective Unlearning via Estimated Score)**.** *Under Assumptions 5.3 and 5.4, let*

$$S^* = \{x \in \mathcal{X} : \ell^*(x) \geq \tau^*\}$$

be the population-optimal selection set with $p_1(S^*) = \beta$, and let

$$\widehat{S} = \{x \in \mathcal{X} : \widehat{\ell}(x) \geq \widehat{\tau}\}$$

be the estimated score-induced selected region, where $\widehat{\tau}$ is calibrated so that $p_1(\widehat{S}) = \beta$. Define

$$\alpha^* := \mathrm{KL}(p_1 \,\|\, p_{-S^*}), \quad \varepsilon^* := \mathrm{KL}(p_2 \,\|\, p_{-S^*}), \quad \widehat{\alpha} := \mathrm{KL}(p_1 \,\|\, p_{-\widehat{S}}), \quad \widehat{\varepsilon} := \mathrm{KL}(p_2 \,\|\, p_{-\widehat{S}}).$$

Suppose $|\widehat{\tau} - \tau^*| \leq r_\tau$ and $\delta + r_\tau \leq \delta_0$ for some $\delta > 0$. Then, with $\phi_B := \log(1 + \frac{\pi_1}{\pi_2} e^B)$,

$$\widehat{\alpha} \geq \alpha^* - \Delta_{\mathrm{rem}}(\delta), \qquad \widehat{\varepsilon} \leq \varepsilon^* + \Delta_{\mathrm{pres}}(\delta), \tag{5}$$

where

$$\Delta_{\mathrm{rem}}(\delta) := \phi_B \left[\frac{\|\widehat{\ell} - \ell^*\|_{L^1(p_1)}}{\delta} + 2M(\delta + r_\tau) \right], \qquad \Delta_{\mathrm{pres}}(\delta) := \frac{\pi_1}{\pi_2} \frac{\Delta_{\mathrm{rem}}(\delta)}{\phi_B}. \tag{6}$$

What governs the selection-to-unlearning transfer? Theorem 5.6 reveals two distinct sources of selection error, each with a different character. *(i) Score-estimation error i.e.* $\|\widehat{\ell} - \ell^*\|_{L^1(p_1)}$ measures how accurately the learned score approximates the population log-density ratio. *(ii) threshold-calibration error i.e.* r_τ measures the discrepancy between the empirical and population deletion thresholds. Since $\widehat{\tau}$ is induced by the order statistic corresponding to β, we treat r_τ as an explicit input to our guarantee, rather than deriving a separate concentration bound for this order statistic. The margin density M (Assumption 5.4) controls the amount of p_1-mass concentrated near the oracle deletion threshold, and determines the sensitivity of the selected region to either type of perturbation. Thus, the theorem provides a conditional guarantee: given a score-estimation error and a threshold-calibration error, it quantifies the resulting degradation from the population-optimal selector. The result is agnostic to how either quantity is obtained.

All the detailed proofs are included in the Appendix B.

6 Experiments

We designed our experimental evaluation to answer two main questions: (1) How effectively does density-ratio-based selection identify potent forget samples to go from complete contamination model to the *ideal* state? (Section 6.1) (2) Does MAMUSHI synergize with downstream sample-level unlearning algorithms to accelerate gradient-based updates? (Section 6.2)

We evaluate the effect of density-ratio-based selection on real-world datasets spanning two distinct regimes: *toxic-language removal* (Jigsaw[4]) and *topical domain removal* (20 Newsgroups [5]). We provide more details in Appendix C.2.

6.1 Distributional Machine Unlearning for LLM Embeddings

Setup. Given a deletion budget β, MAMUSHI and all other baselines rank the forget samples S_1 by their respective scoring criterion and then perform top-K selection to choose the $\lfloor \beta n_1 \rfloor$ highest-scoring samples under the budget. This selected data subset is removed from the forget set. The curated forget set along with the retain set intact (see Eq. 4) is used to fine-tune a fresh-base model.

Evaluation. We measure the effect of selection via **perplexity** (PPL) on the held-out evaluation set, taking the fully **gold standard** model — the model fined tuned on retain set (S_2) alone — as the reference, since this represents the *oracle* state of the model, had it only been trained on clean-data. We use **Sum of Absolute Distances** (SAD) as our primary scalar metric as model-level operational proxy for distance to the to the oracle reference. At budget β,

$$\mathrm{SAD}_\beta \;=\; \left|\mathrm{PPL}_{(\beta,\mathrm{forget})} - \mathrm{PPL}_{(1,\mathrm{forget})}\right| \;+\; \left|\mathrm{PPL}_{(\beta,\mathrm{retain})} - \mathrm{PPL}_{(1,\mathrm{retain})}\right|, \tag{7}$$

where $\mathrm{PPL}_{(\beta,\mathrm{forget})}$ and $\mathrm{PPL}_{(\beta,\mathrm{retain})}$ denote the perplexity of β selected-and-removed (keeping retain set untouched) and the fine-tuned model on static held-out test forget and retain set respectively.

[4] https://www.kaggle.com/competitions/jigsaw-toxic-comment-classification-challenge
[5] https://scikit-learn.org/0.19/datasets/twenty_newsgroups.html




Figure 2: **Toxic-language unlearning (Jigsaw) across Llama, Qwen, and Gemma Embeddings.**




Figure 3: **Topical domain removal (20 Newsgroups) across Llama, Qwen, and Gemma Embeddings.**

The deletion budget β interpolates between two well-defined endpoints, anchoring the SAD scale. At $\beta = 0$, all forget samples are selected, so the model is fine-tuned on the retain set $S_1 \cup S_2$ i.e. all the available data, and its distance to the oracle reference is therefore *maximal*. At $\beta = 1$, the entire forget set is deleted, recovering the gold-standard. So every method eventually collapses onto the gold standard itself and SAD $\to 0$. Intermediate budgets $\beta \in (0, 1)$ trace how quickly each selection method drives the edited distribution from the contaminated endpoint towards oracle endpoint. A lower value (from Eq. 7) at a given budget therefore indicates that a method has deleted the samples that shift the distribution most — i.e., the most distributionally potent members of the forget set.

Results. In all figures, solid lines denote measured performance across $\beta \in \{0.1, \ldots, 0.9\}$, and the dotted segments at $\beta = 0$ and $\beta = 1$ indicate the convergent behavior toward the fully-contaminated and clean endpoints respectively. All results are averaged over 5 random seeds, with standard error shown as shaded regions. As shown in Figure 2, MAMUSHI overall attains the lowest SAD among all selection methods across the full budget range for the Llama-3.1-8B and Gemma-2-2B embeddings, consistently outperforming every geometric baseline. On Qwen-2.5-7B, MAMUSHI exhibits a minor performance deficit initially, but overtakes all baselines from intermediate budgets onward, ultimately achieving the closest convergence to the target state. From Figure 3, MAMUSHI unequivocally attains the lowest SAD across all budgets on all embeddings.

6.2 SYNERGY WITH SAMPLE-LEVEL UNLEARNING

A secondary, parallel application of our data-centric framework is to serve as an *efficiency-boosting front-end* for sample-level unlearning algorithms. The computational cost of most efficient unlearning methods scales with the size of the forget set — fewer flagged samples means fewer gradient steps, fewer influence-function evaluations, and lower memory overhead (Guo et al., 2020; Kurmanji et al., 2023). By identifying the small, high-impact subset of the toxic domain that carries the largest distributional footprint, MAMUSHI allows downstream unlearning methods to reach a target forgetting level while operating on a substantially smaller deletion set.

We pair MAMUSHI's selection with two representative sample-level unlearning methods: **NegGrad+** (Kurmanji et al., 2023), a gradient-ascent baseline with retain-set regularization, and **SalUn** (Fan et al., 2024), a saliency-based method that approximates the retraining standard well. We compare MAMUSHI alongside RANDOM, and CORESET baselines with *deletion budget required* for each combination to reach a fixed unlearning target: recovery of half the initial contamination gap, mirroring similar setup to Table. 5 in Allouah et al. (2026).

Setup. We start from the contaminated model and use the oracle model as reference. For a budget β, each selection method ranks the forget set p_1 and selects its top-K examples. Retraining re-fits

Table 1: **Synergy with Sample-Level Unlearning.** Deletion budget β (%) required for each (selection, unlearning) pair to recover half the initial contamination gap (Qwen2.5-7B, 20 Newsgroups). Lower budget indicates a more efficient selection. "vs. full" denotes the relative reduction in size of MAMUSHI's selective removal from the full forget set; "vs. Random" is its reduction relative to random selection.

Unlearning	**Selection Method**			**Savings**	
Method	Random	Coreset	**MAMUSHI**	vs. full	vs. Random
Retraining	62%	64%	**24%**	76%	61%
NegGrad+	61%	26%	**21%**	79%	66%
SalUn	40%	35%	**36%**	64%	11%

the base model without them; NegGrad+ and SalUn unlearn them from contaminated model, with p_2 as the retain set. As in Allouah et al. (2026), a run succeeds once the forget perplexity rises halfway from contaminated to oracle model; we verify that the retain perplexity stays within a factor of 5.6 of contaminated model's retain perplexity at every reported crossing, so no entry is obtained by catastrophic degradation of the model. We linearly interpolate the budget–perplexity curve to the target. Budgets are swept in 10% steps for Retraining and 5% steps near the crossing for the unlearning methods.

Results. From Table 1, MAMUSHI needs the smallest budget under Retraining (24% vs. 62% for Random and 64% for Coreset) and NegGrad+ (21% vs. 26% for Coreset; 61% for Random), and matches Coreset under SalUn (36% vs. 35%; 40% for Random). It saves 76%, 79% and 64% of the forget set, respectively. The gain over Random is largest for Retraining, where the outcome depends on which examples remain, and smallest for SalUn, whose objective removes the forget concept from almost any subset of p_1.

We include other insightful results in Appendix D.

7 Conclusion and Future Work

We presented MAMUSHI, a selection framework for distributional machine unlearning that does not impose a parametric family on the underlying forget and retain distributions. We showed that thresholding the population log-density ratio yields the optimal fixed-budget selection rule for balancing removal and preservation objectives, and established non-asymptotic transfer guarantee that quantifies the degradation from the population-optimal selector as a function of score- estimation and threshold-calibration error. Empirical evaluations across multiple language model families (Llama, Qwen, and Gemma) and dataset domains (Jigsaw, Newsgroup) show that MAMUSHI achieves competitive and, across several settings, tighter convergence to the reference state, identifying the most potent forget samples for finetuning and accelerating downstream unlearning. Our results collectively suggest that our methodology provides a practical alternative to restrictive parametric selection rules for scalable subpopulation unlearning in language models.

Distributional Unlearning treats the forget set as a single distribution, which is a useful first-order abstraction but may be too coarse for real-world content-moderation applications. Undesired behavior is heterogeneous: harassment, threats, discrimination, and other forms of harm can differ in downstream severity (Mills, 2000). Future work should consider more expressive, statistically structured, and severity-aware representations of the forget domain (importance weights, mixture of distribution etc.). An explicit sample-size-dependent analysis of the proposed estimator is a natural direction for future work, including generalization bounds for the learned density-ratio score and concentration guarantees for empirical threshold calibration. Additional directions include expanding empirical evaluations on larger models with full-model fine-tuning and unlearning, and extending the method to vision–language and other multimodal systems, since harmful or unwanted behavior may depend jointly on visual and textual information.

AI USE STATEMENT

In this work, we used generative AI tools (such as Claude Opus 4.8 and Gemini 3.1 Pro) to assist with checking and verifying mathematical proofs, as well as developing and refining experimental code implementation. We have not used generative AI tools to generate synthetic datasets, formulate primary mathematical claims, or design the core research methodology, and qualitative data analysis is not applicable to this work. Additionally, we used generative AI tools to refine paper prose for readability. We have thoroughly reviewed all AI-assisted work: all theoretical proofs were manually checked and verified for mathematical correctness by the authors, all experimental software code was rigorously tested and validated, and all manuscript text was reviewed to ensure accuracy and prevent plagiarism. We take full responsibility for the final content of this work, including text, claims, and code artifacts produced with the aid of generative AI.

REFERENCES

Charu C. Aggarwal, Alexander Hinneburg, and Daniel A. Keim. On the surprising behavior of distance metrics in high dimensional space. In *Database Theory — ICDT 2001*, pp. 420–434. Springer, 2001. doi: 10.1007/3-540-44503-X_27. URL https://doi.org/10.1007/3-540-44503-X_27.

Youssef Allouah, Rachid Guerraoui, and Sanmi Koyejo. Distributional machine unlearning via selective data removal. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=IPqUBL4R9x.

Jean-Yves Audibert and Alexandre B Tsybakov. Fast learning rates for plug-in classifiers. *The Annals of Statistics*, 35(2):608–633, 2007. URL https://arxiv.org/abs/0708.2321.

Arindam Banerjee, Inderjit S. Dhillon, Joydeep Ghosh, and Suvrit Sra. Clustering on the unit hypersphere using von mises-fisher distributions. *Journal of Machine Learning Research*, 6(46): 1345–1382, 2005. URL http://jmlr.org/papers/v6/banerjee05a.html.

Nora Belrose, David Schneider-Joseph, Shauli Ravfogel, Ryan Cotterell, Edward Raff, and Stella Biderman. LEACE: Perfect linear concept erasure in closed form. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=awIpKpwTwF.

Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine Learning*, 79:151–175, 2010. URL https://doi.org/10.1007/s10994-009-5152-4.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A. Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning, 2020. URL https://arxiv.org/abs/1912.03817.

Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, Alina Oprea, and Colin Raffel. Extracting training data from large language models, 2021. URL https://arxiv.org/abs/2012.07805.

Corinna Cortes, Yishay Mansour, and Mehryar Mohri. Learning bounds for importance weighting. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 23, pp. 442–450, 2010. URL https://proceedings.neurips.cc/paper/2010/hash/59c33016884a62116be975a9bb8257e3-Abstract.html.

Ronen Eldan and Mark Russinovich. Who's harry potter? approximate unlearning in llms, 2023. URL https://arxiv.org/abs/2310.02238.

Chongyu Fan, Jiancheng Liu, Yihua Zhang, Eric Wong, Dennis Wei, and Sijia Liu. Salun: Empowering machine unlearning via gradient-based weight saliency in both image classification and generation. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=gn0mIhQGNM.

Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. Simplicity prevails: Rethinking negative preference optimization for LLM unlearning. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=JbvSQm5h1l.

Aaron Grattafiori et al. The llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

Chuan Guo, Tom Goldstein, Awni Hannun, and Laurens Van Der Maaten. Certified data removal from machine learning models. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 3832–3842. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/guo20c.html.

Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. Don't stop pretraining: Adapt language models to domains and tasks. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 8342–8360, 2020. URL https://aclanthology.org/2020.acl-main.740/.

Yihuai Hong, Yuelin Zou, Lijie Hu, Ziqian Zeng, Di Wang, and Haiqin Yang. Dissecting fine-tuning unlearning in large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 3933–3941, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.228. URL https://aclanthology.org/2024.emnlp-main.228/.

Jigsaw/Conversation AI. Jigsaw unintended bias in toxicity classification. https://www.kaggle.com/c/jigsaw-unintended-bias-in-toxicity-classification, 2019.

Anna Jobin, Marcello Ienca, and Effy Vayena. The global landscape of AI ethics guidelines. *Nature Machine Intelligence*, 1(9):389–399, 2019. URL https://doi.org/10.1038/s42256-019-0088-2.

C. G. Khatri and K. V. Mardia. The von mises–fisher matrix distribution in orientation statistics. *Journal of the Royal Statistical Society: Series B (Methodological)*, 39(1):95–106, 09 1977. ISSN 0035-9246. doi: 10.1111/j.2517-6161.1977.tb01610.x. URL https://doi.org/10.1111/j.2517-6161.1977.tb01610.x.

Krishnateja Killamsetty, Sivasubramanian Durga, Ganesh Ramakrishnan, Abir De, and Rishabh Iyer. GRAD-MATCH: Gradient matching based data subset selection for efficient deep model training. In *Proceedings of the 38th International Conference on Machine Learning*, pp. 5464–5474. PMLR, 2021. URL https://arxiv.org/abs/2103.00123.

Sangamesh Kodge, Gobinda Saha, and Kaushik Roy. Deep unlearning: Fast and efficient gradient-free approach to class forgetting, 2024. URL https://arxiv.org/abs/2312.00761.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1885–1894. PMLR, 06–11 Aug 2017. URL https://proceedings.mlr.press/v70/koh17a.html.

Meghdad Kurmanji, Peter Triantafillou, Jamie Hayes, and Eleni Triantafillou. Towards unbounded machine unlearning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=OveBaTtUAT.

Ming Li, Yong Zhang, Zhitao Li, Jiuhai Chen, Lichang Chen, Ning Cheng, Jianzong Wang, Tianyi Zhou, and Jing Xiao. From quantity to quality: Boosting LLM performance with self-guided data selection for instruction tuning. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, volume 1, pp. 7602–7635, 2024a. URL https://arxiv.org/abs/2308.12032.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, et al. The WMDP benchmark: Measuring and reducing malicious use with unlearning. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235 of *Proceedings of Machine Learning Research*, 2024b. URL https://proceedings.mlr.press/v235/li24bc.html.

Ken Liu, Christopher A. Choquette-Choo, Matthew Jagielski, Peter Kairouz, Sanmi Koyejo, Percy Liang, and Nicolas Papernot. Language models may verbatim complete text they were not explicitly trained on. In *Forty-second International Conference on Machine Learning*, 2025a. URL https://openreview.net/forum?id=bLcXkIasck.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, Kush R. Varshney, Mohit Bansal, Sanmi Koyejo, and Yang Liu. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, 7: 181–194, 2025b. doi: 10.1038/s42256-025-00985-0. URL https://doi.org/10.1038/s42256-025-00985-0.

Prasanta Chandra Mahalanobis. On the generalized distance in statistics. *Proceedings of the National Institute of Sciences of India*, 2(1):49–55, 1936. URL https://insa.nic.in/writereaddata/UpLoadedFiles/PINSA/Vol02_1936_1_Art05.pdf.

Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary C. Lipton, and J. Zico Kolter. Tofu: A task of fictitious unlearning for llms, 2024. URL https://arxiv.org/abs/2401.06121.

Enno Mammen and Alexandre B Tsybakov. Smooth discrimination analysis. *The Annals of Statistics*, 27(6):1808–1829, 1999. URL https://projecteuclid.org/euclid.aos/1017939240.

Yu Meng, Jiaxin Huang, Guangyuan Wang, Chao Zhang, Honglei Zhuang, Lance Kaplan, and Jiawei Han. Spherical text embedding, 2019. URL https://arxiv.org/abs/1911.01196.

Aditya Menon and Cheng Soon Ong. Linking losses for density ratio and class-probability estimation. In Maria Florina Balcan and Kilian Q. Weinberger (eds.), *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pp. 304–313, New York, New York, USA, 20–22 Jun 2016. PMLR. URL https://proceedings.mlr.press/v48/menon16.html.

C. Wright Mills. *The Sociological Imagination*. Oxford University Press, New York, 40th anniversary edition, 2000. ISBN 978-0195133738. URL https://global.oup.com/academic/product/the-sociological-imagination-9780195133738. With an afterword by Todd Gitlin.

Baharan Mirzasoleiman, Jeff Bilmes, and Jure Leskovec. Coresets for data-efficient training of machine learning models. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 6950–6960. PMLR, 2020. URL https://arxiv.org/abs/1906.01827.

Tom Mitchell. Twenty newsgroups, 1997. URL https://doi.org/10.24432/C5C323. UCI Machine Learning Repository.

Seth Neel, Aaron Roth, and Saeed Sharifi-Malvajerdi. Descent-to-delete: Gradient-based methods for machine unlearning, 2020. URL https://arxiv.org/abs/2007.02923.

Jerzy Neyman and Egon Sharpe Pearson. Ix. on the problem of the most efficient tests of statistical hypotheses. *Philosophical Transactions of the Royal Society of London, Series A: Containing Papers of a Mathematical or Physical Character*, 231(694-706):289–337, 02 1933. ISSN 0264-3952. doi: 10.1098/rsta.1933.0009. URL https://doi.org/10.1098/rsta.1933.0009.

Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry of large language models, 2024. URL https://arxiv.org/abs/2311.03658.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7237–7256, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.647. URL https://aclanthology.org/2020.acl-main.647/.

Mark D. Reid and Robert C. Williamson. Composite binary losses. *Journal of Machine Learning Research*, 11(83):2387–2422, 2010. URL https://www.jmlr.org/papers/v11/reid10a.html.

Mark D. Reid and Robert C. Williamson. Information, divergence and risk for binary experiments. *Journal of Machine Learning Research*, 12(22):731–817, 2011. URL http://jmlr.org/papers/v12/reid11a.html.

Eleanor Rosch. Cognitive representations of semantic categories. volume 104, pp. 192–233. American Psychological Association, 1975. URL https://doi.org/10.1037/0096-3445.104.3.192.

Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. In *International Conference on Learning Representations*, 2018. URL https://arxiv.org/abs/1708.00489.

Harald Steck, Chaitanya Ekanadham, and Nathan Kallus. Is cosine-similarity of embeddings really about similarity? In *Companion Proceedings of the ACM Web Conference 2024*, WWW '24, pp. 887–890, New York, NY, USA, 2024. Association for Computing Machinery. ISBN 9798400701726. doi: 10.1145/3589335.3651526. URL https://doi.org/10.1145/3589335.3651526.

Masashi Sugiyama, Matthias Krauledat, and Klaus-Robert Müller. Covariate shift adaptation by importance weighted cross validation. *Journal of Machine Learning Research*, 8:985–1005, 2007a. URL https://www.jmlr.org/papers/volume8/sugiyama07a/sugiyama07a.pdf.

Masashi Sugiyama, Shinichi Nakajima, Hisashi Kashima, Paul Buenau, and Motoaki Kawanabe. Direct importance estimation with model selection and its application to covariate shift adaptation. In J. Platt, D. Koller, Y. Singer, and S. Roweis (eds.), *Advances in Neural Information Processing Systems*, volume 20. Curran Associates, Inc., 2007b. URL https://proceedings.neurips.cc/paper_files/paper/2007/file/be83ab3ecd0db773eb2dc1b0a17836a1-Paper.pdf.

Masashi Sugiyama, Taiji Suzuki, and Takafumi Kanamori. *Density Ratio Estimation in Machine Learning*. Cambridge University Press, 2012. ISBN 9781139035613. URL https://doi.org/10.1017/CBO9781139035613.

Swabha Swayamdipta, Roy Schwartz, Nicholas Lourie, Yizhong Wang, Hannaneh Hajishirzi, Noah A. Smith, and Yejin Choi. Dataset cartography: Mapping and diagnosing datasets with training dynamics. In Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (eds.), *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9275–9293, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.746. URL https://aclanthology.org/2020.emnlp-main.746/.

Haoran Tang and Rajiv Khanna. From logits to latents: Contrastive representation shaping for llm unlearning. *arXiv preprint arXiv:2601.22028*, 2026. URL https://arxiv.org/abs/2601.22028.

Gemma Team, Morgane Riviere, et al. Gemma 2: Improving open language models at a practical size, 2024. URL https://arxiv.org/abs/2408.00118.

V.N. Vapnik. *Statistical Learning Theory*. A Wiley-Interscience publication. Wiley, 1998. ISBN 9788126528929. URL https://books.google.com/books?id=RWrlkQEACAAJ.

Sandra Wachter, Brent Mittelstadt, and Luciano Floridi. Why a right to explanation of automated decision-making does not exist in the general data protection regulation. *International Data Privacy Law*, 7(2):76–99, 05 2017. ISSN 2044-3994. doi: 10.1093/idpl/ipx005. URL https://doi.org/10.1093/idpl/ipx005.

Abraham Wald. *Statistical Decision Functions*, pp. 342–357. Springer New York, New York, NY, 1992. ISBN 978-1-4612-0919-5. doi: 10.1007/978-1-4612-0919-5_22. URL https://doi.org/10.1007/978-1-4612-0919-5_22.

Sang Michael Xie, Shibani Santurkar, Tengyu Ma, and Percy Liang. Data selection for language models via importance resampling. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. URL https://arxiv.org/abs/2302.03169.

Xiaoyu Xu, Xiang Yue, Yang Liu, Qingqing Ye, Huadi Zheng, Peizhao Hu, Minxin Du, and Haibo Hu. Unlearning isn't deletion: Investigating reversibility of machine unlearning in LLMs. In *Forty-third International Conference on Machine Learning*, 2026. URL https://openreview.net/forum?id=E5SVowO13b.

Makoto Yamada, Taiji Suzuki, Takafumi Kanamori, Hirotaka Hachiya, and Masashi Sugiyama. Relative density-ratio estimation for robust distribution comparison. *Advances in Neural Information Processing Systems (NeurIPS)*, 2011. URL https://arxiv.org/abs/1106.4729.

An Yang et al. Qwen2.5 technical report, 2025. URL https://arxiv.org/abs/2412.15115.

Liyi Zhang, Michael Y. Li, R. Thomas McCoy, Theodore Sumers, Jian-Qiao Zhu, and Thomas L. Griffiths. What should embeddings embed? autoregressive models represent latent generating distributions. *Transactions on Machine Learning Research*, 2025. ISSN 2835-8856. URL https://openreview.net/forum?id=YyMACp98Kz. Featured Certification.

Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. Negative preference optimization: From catastrophic collapse to effective unlearning. In *First Conference on Language Modeling (COLM)*, 2024. URL https://arxiv.org/abs/2404.05868.

APPENDIX CONTENTS

A Other Related Works **17**

LLM Unlearning. 17

Density-ratio data selection and direct estimators. 17

B Proofs **17**

B.1 Main Body Proofs 17

B.1.1 Proof of Lemma 4.1 17

B.1.2 Proof of Lemma 5.1 18

B.1.3 Proof of Proposition 5.2 19

B.1.4 Proof of Theorem 5.6 19

B.2 Auxiliary Proofs 20

B.2.1 Proof of Corollary B.1 21

B.2.2 Proof of Corollary B.3 21

B.2.3 Proof of Proposition B.4 22

B.2.4 Proof of Lemma B.5 22

B.2.5 Proof of Corollary B.6 22

C Experimental Setup **23**

C.1 Baselines 23

C.2 Implementation Details 23

C.2.1 Hardware and Software 23

C.2.2 Data Preparation 23

C.2.3 Models 24

C.2.4 Phase 1: Contamination and Embedding Extraction 24

C.2.5 Phase 2: Score Estimation and Unlearning 24

D Additional Experimental Results **26**

D.1 Runtime Analysis 26

D.2 Reverse MAMUSHI 26

D.3 Estimator Choice 27

D.4 Empirical Evidence for Anisotropy of LLM Embeddings 27

D.4.1 Strong anisotropy (Figure 7). 27

D.4.2 Discriminative analysis (Figure 8a). 27

D.4.3 Spectral analysis (Figure 8b). 28

D.4.4 Distinct subspace geometry (Figure 9). 29

D.5 Qualitative Analysis 30

D.5.1 Qualitative Ranking. 30

D.5.2 Qualitative text generation. 30

A Other Related Works

LLM Unlearning. A large family of LLM unlearning methods operates in the prediction space, fine-tuning the model against objectives defined over output likelihoods. Negative preference optimization (NPO) recasts forgetting as a preference-optimization problem and progresses toward catastrophic collapse exponentially more slowly than gradient ascent (Zhang et al., 2024), and SimNPO removes the dependence on a reference model, which otherwise allocates optimization effort unevenly across forget samples of differing difficulty (Fan et al., 2025). Such methods are commonly evaluated on TOFU, whose synthetic author profiles make the forget and retain sets exactly known (Maini et al., 2024), and on WMDP, which targets hazardous knowledge and introduced RMU, a representation-level method that perturbs activations on forget data while preserving them on benign data (Li et al., 2024b). Tang & Khanna (2026) operate at the representation level rather than the prediction level, using a contrastive regularizer that identifies forget features and pushes them away from retain features to reduce forget–retain entanglement.

Density-ratio data selection and direct estimators. Importance-weighted data selection in NLP, most prominently DSIR (Xie et al., 2023), selects pretraining data to *match a single target distribution*, estimating importance weights as the ratio of *separately* learned target and raw-pool densities over hashed n-gram features. This differs from our setting in three respects: the objective is single-distribution matching rather than a forget-versus-retain contrast; the features are surface lexical statistics (like word-frequency overlap) rather than contextual LLM embeddings; and the task is pretraining curation rather than data-centric unlearning.

Classical direct density-ratio estimators—such as KLIEP (Sugiyama et al., 2007a) and uLSIF/RuLSIF (Yamada et al., 2011)—estimate p_1/p_2 without separate density estimation. However, they rely on kernel models whose bandwidth selection and Gram-matrix operations are statistically and computationally prohibitive at the embedding dimensions we operate on ($d \in [2304, 4096]$); RuLSIF's closed form additionally requires an $\mathcal{O}(n^3)$ matrix inversion, and Gaussian kernels degrade as pairwise distances concentrate in high dimension. Moreover, these estimators were developed for adjacent downstream tasks like importance reweighting under covariate shift and relative-divergence estimation for two-sample testing or outlier detection rather than contrastive, budget-constrained selection for removal. We adopt the probabilistic-classification approach to density-ratio estimation (Menon & Ong, 2016; Sugiyama et al., 2012): the logit of a BCE-trained classifier estimates ℓ^* discriminatively in high dimension, yielding a calibrated score we threshold for selective removal. These lines of work are thus the intellectual ancestors of our work, which we scale to LLM embeddings and under a selection framework with explicit removal/preservation guarantees.

B Proofs

B.1 Main Body Proofs

B.1.1 Proof of Lemma 4.1

Proof. We know for the posterior class probability,

$$\eta(x) := \Pr(Y = 1 \mid X = x) = \frac{\pi_1 p_1(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)}.$$

But because binary cross-entropy is strictly proper, the population minimizer satisfies $D^*(x) = \eta(x)$. Therefore,

$$\begin{aligned}\operatorname{logit}(D^*(x)) &= \log \frac{\pi_1 p_1(x)}{\pi_2 p_2(x)} \\ &= \log \frac{p_1(x)}{p_2(x)} + \log \frac{\pi_1}{\pi_2} \\ &= \ell^*(x) + \log \frac{\pi_1}{\pi_2}.\end{aligned}$$

The second term is independent of x, so it does not affect ranking. Subtracting it gives the exact log-density-ratio. □

B.1.2 PROOF OF LEMMA 5.1

Proof. By Equation 4, for $x \notin S$,

$$p_{-S}(x) = \frac{\pi_1 p_1(x) + \pi_2 p_2(x)}{Z_\beta},$$

whereas for $x \in S$ the forget component is removed,

$$p_{-S}(x) = \frac{\pi_2 p_2(x)}{Z_\beta}.$$

Forgetting divergence. Splitting the integral over S^c and S,

$$\begin{aligned}\mathrm{KL}(p_1 \parallel p_{-S}) &= \int_{\mathcal{X}} p_1(x) \log \frac{p_1(x)}{p_{-S}(x)} \,\mathrm{d}x \\ &= \log Z_\beta + \int_{S^c} p_1(x) \log \frac{p_1(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)} \,\mathrm{d}x + \int_S p_1(x) \log \frac{p_1(x)}{\pi_2 p_2(x)} \,\mathrm{d}x.\end{aligned}$$

First, for $x \in S$, we rewrite:

$$\log \frac{p_1(x)}{\pi_2 p_2(x)} = \log \frac{p_1(x)}{p_2(x)} - \log \pi_2 = \ell^*(x) - \log \pi_2.$$

Next, for $x \in S^c$, we factor $\pi_1 p_1(x)$ out of the denominator to isolate $\ell^*(x) = \log \frac{p_1(x)}{p_2(x)}$:

$$\pi_1 p_1(x) + \pi_2 p_2(x) = \pi_1 p_1(x) \left(1 + \frac{\pi_2 p_2(x)}{\pi_1 p_1(x)}\right) = \pi_1 p_1(x) \left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right),$$

which yields the simplified integrand:

$$\log \frac{p_1(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)} = -\log \pi_1 - \log\left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right).$$

Now, rewriting the domain integral over S^c as an integral over the entire domain $\mathcal{X}$ minus the integral over S gives:

$$\begin{aligned}\int_{S^c} p_1(x) \log \frac{p_1(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)} \,\mathrm{d}x &= \int_{\mathcal{X}} p_1(x) \log \frac{p_1(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)} \,\mathrm{d}x \\ &\quad - \int_S p_1(x) \log \frac{p_1(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)} \,\mathrm{d}x \\ &= \int_{\mathcal{X}} p_1(x) \left(-\log \pi_1 - \log\left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right)\right) \mathrm{d}x \\ &\quad + \int_S p_1(x) \left(\log \pi_1 + \log\left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right)\right) \mathrm{d}x,\end{aligned}$$

Combining the original integral over S with the newly derived S-integral from the domain decomposition yields a single integral over S:

$$\begin{aligned}\text{Total } S\text{-integral} &= \int_S p_1(x) \left[(\ell^*(x) - \log \pi_2) + \log \pi_1 + \log\left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right)\right] \mathrm{d}x \\ &= \int_S p_1(x) \left[\log\left(\frac{\pi_1}{\pi_2} e^{\ell^*(x)}\right) + \log\left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right)\right] \mathrm{d}x \\ &= \int_S p_1(x) \log\left(\frac{\pi_1}{\pi_2} e^{\ell^*(x)} \cdot \left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right)\right) \mathrm{d}x \\ &= \int_S p_1(x) \log\left(1 + \frac{\pi_1}{\pi_2} e^{\ell^*(x)}\right) \mathrm{d}x = \int_S p_1(x) \phi(\ell^*(x)) \,\mathrm{d}x,\end{aligned}$$

Finally, collecting all S-independent terms into a constant $C_{\text{rem}}(\beta; \pi_1, \pi_2, p_1, p_2)$, defined as:

$$C_{\text{rem}}(\beta; \pi_1, \pi_2, p_1, p_2) \triangleq \log Z_\beta - \log \pi_1 - \int_{\mathcal{X}} p_1(x) \log \left(1 + \frac{\pi_2}{\pi_1} e^{-\ell^*(x)}\right) \mathrm{d}x,$$

we obtain the simplified expression:

$$\mathrm{KL}(p_1 \parallel p_{-S}) = C_{\text{rem}} + \int_S p_1(x) \phi(\ell^*(x)) \, \mathrm{d}x.$$

Preservation divergence. Identically, on S only the retain component survives, and

$$\begin{aligned}\mathrm{KL}(p_2 \| p_{-S}) &= \log Z_\beta + \int_{S^c} p_2(x) \log \frac{p_2(x)}{\pi_1 p_1(x) + \pi_2 p_2(x)} \, \mathrm{d}x + \int_S p_2(x) \log \frac{p_2(x)}{\pi_2 p_2(x)} \, \mathrm{d}x \\ &= C_{\text{pres}}(\beta; \pi_1, \pi_2, p_1, p_2) + \int_S p_2(x) \, \phi(\ell^*(x)) \, \mathrm{d}x,\end{aligned}$$

where the S-independent terms are gathered into C_{pres}. Both constants depend only on β (through $Z_\beta = 1 - \pi_1 \beta$), the fixed priors, and the fixed distributions never on the identity of S, which proves our result. □

B.1.3 Proof of Proposition 5.2

Proof. We know by Lemma 5.1, maximizing $\mathrm{KL}(p_1 \| p_{-S})$ at fixed budget is equivalent to maximizing

$$\int_S p_1(x) \phi(\ell^*(x)) \, \mathrm{d}x.$$

Because ϕ is strictly increasing, this integrand is largest where $\ell^*(x)$ is largest. Therefore, among all sets with $p_1(S) = \beta$, the superlevel set S_τ maximizes the integral.

For the preservation objective, Lemma 5.1 gives,

$$\int_S p_2(x) \phi(\ell^*(x)) \, \mathrm{d}x.$$

Rewriting $p_2(x) = p_1(x) e^{-\ell^*(x)}$ shapes it as,

$$\int_S p_1(x) \psi(\ell^*(x)) \, \mathrm{d}x, \qquad \psi(u) = e^{-u} \phi(u).$$

Since ψ is strictly decreasing, this integral is minimized by selecting the points with the largest values of $\ell^*(x)$. Thus, S_τ simultaneously maximizes removal and minimizes preservation loss. □

B.1.4 Proof of Theorem 5.6

Proof. Let $E := S^* \triangle \widehat{S}$ denote the symmetric difference of the ideal and estimated selected sets. If $x \in E$, then $\ell^*(x)$ and $\widehat{\ell}(x)$ fall on opposite sides of their respective thresholds τ^* and $\widehat{\tau}$.

Step 1: Bounding the symmetric difference.

Hence,

$$|\ell^*(x) - \tau^*| \le |\widehat{\ell}(x) - \ell^*(x)| + |\widehat{\tau} - \tau^*| \le |\widehat{\ell}(x) - \ell^*(x)| + r_\tau.$$

For any $\delta > 0$, either $|\widehat{\ell}(x) - \ell^*(x)| > \delta$, or else $|\ell^*(x) - \tau^*| \le \delta + r_\tau$.

Therefore,

$$E \subseteq \{x : |\widehat{\ell}(x) - \ell^*(x)| > \delta\} \cup \{x : |\ell^*(x) - \tau^*| \le \delta + r_\tau\}.$$

Step 2: Bounding $p_1(E)$.

By a simple union bound,

$$p_1(E) \le p_1\Big(|\widehat{\ell} - \ell^*| > \delta\Big) + p_1(|\ell^* - \tau^*| \le \delta + r_\tau).$$

By using a Markov's inequality on the first term:

$$p_1\Big(|\widehat{\ell} - \ell^*| > \delta\Big) \leq \frac{\|\widehat{\ell} - \ell^*\|_{L^1(p_1)}}{\delta}.$$

Under Assumption 5.4 ($f_\ell \leq M$ on I_{δ_0}) and $\delta + r_\tau \leq \delta_0$ the second term becomes,

$$p_1(|\ell^* - \tau^*| \leq \delta + r_\tau) = \int_{\tau^* - (\delta + r_\tau)}^{\tau^* + (\delta + r_\tau)} f_\ell(t)\,\mathrm{d}t \leq 2M(\delta + r_\tau).$$

Combining,

$$p_1(E) \leq \frac{\|\widehat{\ell} - \ell^*\|_{L^1(p_1)}}{\delta} + 2M(\delta + r_\tau). \tag{8}$$

Equation 8 shows that the disagreement set is jointly controlled by model and threshold calibration errors.

Step 3: Removal bound.

Since $p_1(S^*) = p_1(\widehat{S}) = \beta$, the renormalization constants of p_{-S^*} and $p_{-\widehat{S}}$ coincide, so the term C_{rem} in Lemma 5.1 cancels:

$$\alpha^* - \widehat{\alpha} = \int_{S^*} \phi(\ell^*)\,\mathrm{d}p_1 - \int_{\widehat{S}} \phi(\ell^*)\,\mathrm{d}p_1 = \int_{S^* \setminus \widehat{S}} \phi(\ell^*)\,\mathrm{d}p_1 - \int_{\widehat{S} \setminus S^*} \phi(\ell^*)\,\mathrm{d}p_1.$$

Since $\phi(u)$ is nonnegative and monotone, and $|\ell^*| \leq B$ (Assumption 5.3), we have $0 \leq \phi(\ell^*(x)) \leq \phi(B) = \phi_B$. Thus,

$$\alpha^* - \widehat{\alpha} \leq \int_E \phi(\ell^*)\,\mathrm{d}p_1 \leq \phi_B\, p_1(E).$$

Substituting Equation 8 gives the first bound in Equation 5.

Step 4: Preservation bound.

By the analogous decomposition for p_2 (Lemma 5.1),

$$\widehat{\varepsilon} - \varepsilon^* \leq \int_E \phi(\ell^*)\,\mathrm{d}p_2.$$

Rather than bounding $\phi(\ell^*)$ and $\frac{\mathrm{d}p_2}{\mathrm{d}p_1}$ separately, we bound their product directly. Writing $\mathrm{d}p_2 = e^{-\ell^*}\,\mathrm{d}p_1$,

$$\int_E \phi(\ell^*)\,\mathrm{d}p_2 = \int_E e^{-\ell^*(x)} \phi(\ell^*(x))\,\mathrm{d}p_1(x) = \int_E \psi(\ell^*(x))\,\mathrm{d}p_1(x),$$

Recall, $\psi(u) = e^{-u}\log(1 + \frac{\pi_1}{\pi_2}e^u)$. Since $\psi(u) < \frac{\pi_1}{\pi_2}$ for all $u \in \mathbb{R}$, we have

$$\widehat{\varepsilon} - \varepsilon^* \leq \int_E \psi(\ell^*)\,\mathrm{d}p_1 \leq \frac{\pi_1}{\pi_2} p_1(E).$$

Substituting Equation 8 gives the second bound in Equation 5 with $\Delta_{\mathrm{pres}}(\delta) = \frac{\pi_1}{\pi_2} p_1(E)$-controlled regret, free of any e^B factor. □

B.2 Auxiliary Proofs

NOTE: For the sake of simplicity we assume $\frac{\pi_1}{\pi_2} < 1$, for underlying proofs in this section .

Corollary B.1 (Simplified (α, ε) guarantee)**.** *Under the assumptions of Theorem 5.6, suppose $\widehat{\tau} = \tau^*$ (i.e., $r_\tau = 0$), and that $a := \|\widehat{\ell} - \ell^*\|_{L^1(p_1)} \leq 2M\delta_0^2$. Choosing the optimal δ,*

$$\widehat{\alpha} \geq \alpha^* - 2\sqrt{2M}\,\phi_B\, a^{1/2},$$
$$\widehat{\varepsilon} \leq \varepsilon^* + 2\sqrt{2M}\, a^{1/2}.$$

B.2.1 PROOF OF COROLLARY B.1

Proof. With $r_\tau = 0$, the forgetting regret is $\Delta_{\mathrm{rem}}(\delta) = \phi_B[a/\delta + 2M\delta]$. Minimizing over $\delta > 0$ gives $\delta^\star = \sqrt{a/(2M)}$, at which $a/\delta^\star + 2M\delta^\star = 2\sqrt{2Ma}$, so $\Delta_{\mathrm{rem}}(\delta^\star) = 2\sqrt{2M}\,\phi_B\,a^{1/2}$. The condition $a \le 2M\delta_0^2$ ensures $\delta^\star = \sqrt{a/(2M)} \le \delta_0$, so Assumption 5.4 applies on $[\tau^* - \delta^\star, \tau^* + \delta^\star] \subseteq I_{\delta_0}$.

By the tightened Step 4 in Theorem 5.6, the preservation regret at the same $\delta^\star$ is $\Delta_{\mathrm{pres}}(\delta^\star) = (a/\delta^\star + 2M\delta^\star) = 2\sqrt{2M}\,a^{1/2}$, without the ϕ_B or e^B factors. □

Remark B.2 (From score error to pure (α, ε)-unlearning). Corollary B.1 is stated purely in terms of the score-estimation error $\|\widehat{\ell} - \ell^*\|_{L^1(p_1)}$, and is agnostic to how that error is controlled. If a generalization argument guarantees, with probability at least $1 - \rho$, that $\|\widehat{\ell} - \ell^*\|_{L^1(p_1)} \le r_n(\rho)$, then Corollary B.1 immediately yields $(\alpha^* - 2\sqrt{2M}\phi_B r_n(\rho)^{1/2}, \varepsilon^* + 2\sqrt{2M} r_n(\rho)^{1/2})$-unlearning. The rate $r_n(\rho)$ may be obtained via Rademacher/VC arguments (Vapnik, 1998). Corollary B.6 provides one such possible population-risk route for obtaining such a score-error bound from BCE excess risk. However, neither is required for the validity of the theorem itself.

Corollary B.3 (Saturation and method-insensitivity)**.** *In the low-threshold-density regime where the score density near the deletion threshold becomes small, $M \to 0$, the bounds of Corollary B.1 imply that, for any estimated score with $L^1(p_1)$ error*

$$a := \|\widehat{\ell} - \ell^*\|_{L^1(p_1)},$$

$$\widehat{\alpha} \ge \alpha^* - 2\sqrt{2M}\,\phi_B\,a^{1/2} \xrightarrow[M\to 0]{} \alpha^*, \qquad \widehat{\varepsilon} \le \varepsilon^* + 2\sqrt{2M}\,a^{1/2} \xrightarrow[M\to 0]{} \varepsilon^*.$$

Thus, when there is little score mass near the deletion threshold, the unlearning-quality gap induced by score estimation vanishes at rate $O(\sqrt{M})$ for fixed a. In this regime, the particular choice of score estimator becomes less consequential, provided its $L^1(p_1)$ error remains bounded.

B.2.2 PROOF OF COROLLARY B.3

Proof. Immediate from Corollary B.1: both regret terms are $O(\sqrt{M}\,a^{1/2})$ and vanish as $M \to 0$ for any fixed a. □

The BCE selector admits a density-ratio interpretation. Under equal class priors, the Bayes-optimal logit satisfies $\ell^*(x) = \log \frac{p_1(x)}{p_2(x)}$, so a learned BCE scorer induces $\widehat{r}(x) = \exp(\widehat{\ell}(x))$ as an estimate of $r(x) = p_1(x)/p_2(x)$. Menon & Ong (2016) show that the regret of a strictly proper composite class-probability loss—the logistic loss included—admits a Bregman-divergence representation in terms of the true and estimated density ratios. This underlies classification-based density-ratio estimation for covariate shift (Sugiyama et al., 2007b) and domain adaptation (Ben-David et al., 2010). We note that Theorem 5.6 is stated conditionally in terms of $\|\widehat{\ell} - \ell^*\|_{L^1(p_1)}$ and thus does not require a particular excess-risk-to-score-error conversion; the results below supply one for completeness.

Proposition B.4 (BCE regret controls density-ratio regret)**.** *Assume equal class priors ($\pi = \frac{1}{2}$) and let $r(x) = \frac{p_1(x)}{p_2(x)}$. Let $\widehat{\ell}$ be the logit of a learned BCE scorer and $\widehat{r}(x) := \exp(\widehat{\ell}(x))$. Write $\mathcal{R}_{\mathrm{BCE}}(\widehat{\ell})$ for the population BCE risk and $\mathcal{R}^*_{\mathrm{BCE}}$ for its Bayes risk. Then*

$$\mathcal{R}_{\mathrm{BCE}}(\widehat{\ell}) - \mathcal{R}^*_{\mathrm{BCE}} = \tfrac{1}{2}\,\mathbb{E}_{X\sim p_2}\big[\, B_{f^\oplus}(r(X), \widehat{r}(X))\,\big],$$

where $B_{f^\oplus}$ is the Bregman divergence induced by the generator $f^\oplus(z) = z\log z - (1+z)\log(1+z)$ associated with the logistic loss.

B.2.3 Proof of Proposition B.4

Proof. Under equal class priors, the Bayes-optimal class probability satisfies $\frac{\eta(x)}{1-\eta(x)} = \frac{p_1(x)}{p_2(x)} = r(x)$. For the logistic loss the inverse link is the sigmoid, so the induced density-ratio estimate is $\widehat{r}(x) = \frac{\widehat{\eta}(x)}{1-\widehat{\eta}(x)} = \exp(\widehat{\ell}(x))$. Applying the density-ratio regret identity of Menon & Ong (2016, Proposition 3) with $Q = p_2$ and generator $f^{\oplus}$ yields the claim. □

Lemma B.5 (From BCE regret to $L^1(p_1)$ log-ratio error)**.** *Under Assumption 5.3, suppose that the estimated log-density ratio is confined to $[-B, B]$. Then $\widehat{r} = \exp(\widehat{\ell}) \in [e^{-B}, e^{B}]$, and, writing $\mathrm{reg}_{\mathrm{BCE}} = \mathcal{R}_{\mathrm{BCE}}(\widehat{\ell}) - \mathcal{R}^*_{\mathrm{BCE}}$,*

$$\|\widehat{\ell} - \ell^*\|_{L^1(p_1)} \;\le\; C_B \sqrt{\mathrm{reg}_{\mathrm{BCE}}}, \qquad C_B := 2\, e^{3B/2}\, m_B^{-1/2}, \quad m_B := \tfrac{1}{e^B(e^B+1)}.$$

B.2.4 Proof of Lemma B.5

Proof. Write $\ell^* = \log r$, $\widehat{\ell} = \log \widehat{r}$.

Step 1: strong convexity implies strong ratio control

The generator has $f^{\oplus\prime\prime}(z) = \frac{1}{z(z+1)} \ge m_B$ on $[e^{-B}, e^{B}]$, so $f^{\oplus}$ is m_B-strongly convex there and $B_{f^{\oplus}}(r, \widehat{r}) \ge \frac{m_B}{2}(r - \widehat{r})^2$. With Proposition B.4,

$$\mathbb{E}_{p_2}\big[(r - \widehat{r})^2\big] \le \tfrac{4}{m_B}\, \mathrm{reg}_{\mathrm{BCE}}. \tag{9}$$

Step 2: ratio error to log-ratio error via MVT

Since $(\log)'(u) = 1/u \ge e^{-B}$ on $[e^{-B}, e^{B}]$, the mean value theorem gives $|\widehat{\ell} - \ell^*| \le e^{B}|r - \widehat{r}|$ pointwise, hence $\mathbb{E}_{p_2}[(\widehat{\ell} - \ell^*)^2] \le e^{2B}\, \mathbb{E}_{p_2}[(r - \widehat{r})^2]$.

Step 3: change of measure

As $\frac{\mathrm{d}p_1}{\mathrm{d}p_2} = r \le e^{B}$, $\mathbb{E}_{p_1}[g] \le e^{B}\mathbb{E}_{p_2}[g]$ for $g \ge 0$. Using $g = (\widehat{\ell} - \ell^*)^2$ and Combining Step 2 and Equation 9,

$$\mathbb{E}_{p_1}\big[(\widehat{\ell} - \ell^*)^2\big] \le e^{B} \cdot e^{2B} \cdot \tfrac{4}{m_B}\, \mathrm{reg}_{\mathrm{BCE}} = \tfrac{4e^{3B}}{m_B}\, \mathrm{reg}_{\mathrm{BCE}}.$$

Step 4: Cauchy–Schwarz Inequality

$\|\widehat{\ell} - \ell^*\|_{L^1(p_1)} \le \|\widehat{\ell} - \ell^*\|_{L^2(p_1)} \le 2e^{3B/2} m_B^{-1/2} \sqrt{\mathrm{reg}_{\mathrm{BCE}}}$. □

Corollary B.6 (Unlearning guarantee from population BCE excess risk))**.** *Under the assumptions of Theorem 5.6 and assuming $\widehat{\ell}$ is confined to $[-B, B]$, with $\widehat{\tau} = \tau^*$, $\phi_B = \log(1 + e^{B})$, $a := \|\widehat{\ell} - \ell^*\|_{L^1(p_1)} \le 2M\delta_0^2$ (so the optimal $\delta^* = \sqrt{a/(2M)} \le \delta_0$ and Assumption 5.4 applies), and $r_\tau = 0$,*

$$\widehat{\alpha} \ge \alpha^* - 2\sqrt{2M}\, \phi_B\, C_B^{1/2}\, \mathrm{reg}_{\mathrm{BCE}}^{1/4}, \qquad \widehat{\varepsilon} \le \varepsilon^* + 2\sqrt{2M}\, C_B^{1/2}\, \mathrm{reg}_{\mathrm{BCE}}^{1/4}.$$

where $\mathrm{reg}_{\mathrm{BCE}}$ denotes the population BCE excess risk.

B.2.5 Proof of Corollary B.6

Proof. Combining Corollary B.1 with Lemma B.5 gives the result. □

Remark B.7. The constant $C_B = 2e^{3B/2}m_B^{-1/2}$ grows exponentially in B; this corollary certifies the existence of a result establishing that BCE consistency is sufficient for our score-error condition.

C Experimental Setup

C.1 Baselines

We use multiple scoring strategies to rank samples in the forget distribution p_1. These strategies approximate different notions of statistical dissimilarity from the retain distribution p_2 and are adapted from the heuristic baselines of Allouah et al. (2026) (Appendix B.2.1) to operate on LLM embeddings. LR-COS and LR-MAHA are corresponding implementations of the same likelihood-ratio-inspired scoring rule under different distance metrics. Their rankings and downstream performance were nearly indistinguishable. We therefore use LR-COS in the remaining experiments because it is substantially cheaper to compute for high-dimensional LLM embeddings. We also add a von Mises–Fisher (VMF) (Khatri & Mardia, 1977; Banerjee et al., 2005) baseline to assess a parametric directional model for LLM embeddings.

RANDOM selects forget samples uniformly at random without replacement. COS-MU2 ranks samples by their cosine distance from the retain centroid. LR-COS ranks samples using the difference between their cosine distances from the retain and forget centroids. VMF fits von Mises–Fisher models to normalized forget and retain embeddings and ranks samples using the resulting directional contrast. ℓ_2-NORM ranks samples according to the norm of their raw embeddings. CORESET selects samples closest to the empirical centroid of the forget embeddings. K-CENTER greedily selects samples to maximize minimum-distance coverage of the forget-set embedding space. MAMUSHI and all baseline selection methods operate on the same embeddings on same random seeds runs for fair comparison.

C.2 Implementation Details

C.2.1 Hardware and Software

All experiments were conducted on NVIDIA H100 GPUs. Models are loaded and trained using PyTorch and the HuggingFace `transformers` library. Random seeds are fixed across Python, NumPy, and PyTorch (including CUDA), and deterministic cuDNN kernels. A single end-to-end finetuning task on larger models takes approximately 1 hour 45 minutes on average.

C.2.2 Data Preparation

For each dataset we partition the data into three disjoint sections — **training**, **inference**, and **evaluation** — and within each section we identify the forget partition p_1 (toxic, or the target topical domain) and the retain partition p_2 (the remainder).

Jigsaw. We use the Jigsaw Toxic Comment Classification dataset (159K examples) (Jigsaw/Conversation AI, 2019). A comment is labeled toxic (p_1) if any of the six toxicity indicators (`toxic`, `severe_toxic`, `obscene`, `threat`, `insult`, `identity_hate`) is positive, and safe (p_2) otherwise. The training file is split 50/50 into a *contamination split* and a held-out *inference split* using a fixed random seed. Evaluation uses the official Jigsaw test set, retaining only examples with valid labels. Toxic and safe test subsets are used to compute hate and clean perplexity respectively. While Allouah et al. (2026) also utilize the same dataset, their analysis relies on TF-IDF, whereas ours leverages LLM embeddings.

20 Newsgroups. We additionally evaluate on 20 Newsgroups (Mitchell, 1997), a standard text classification benchmark of roughly 18K newsgroup posts across 20 topical categories, under a *content-moderation* framing. While Jigsaw targets removal of toxic language, the 20NG setting models topical domain removal, e.g., parental-control or interest-based filtering. The forget domain p_1 comprises the three politically charged `talk.politics.*` groups (`guns`, `misc`, `mideast`), and the retain domain p_2 comprises all remaining newsgroups. We enforce **strict mutual exclusivity** between p_1 and p_2: any post whose normalized content appears in both classes (cross-posts) is removed from both, and near-duplicates within each class are collapsed to a single copy. It is worth mentioning this mutual exclusivity enforced during data construction is a labeling constraint on *sampled* sequences that yields a clean forget/retain partition of the training data; it does not imply disjoint support of the underlying population densities p_1 and p_2. The cleaned data is split into a stratified 20% test set, with the remaining 80% split 50/50 into contamination and inference sets.

All text is tokenized with the model's native tokenizer and truncated to a maximum of 128 tokens. Padding tokens are masked with label -100 so they do not contribute to the language modeling loss.

C.2.3 MODELS

We evaluate three open-source decoder-only language models:

- **Llama-3.1-8B** (Grattafiori et al., 2024) (hidden size 4096, 32 layers);
- **Qwen-2.5-7B** (Yang et al., 2025) (hidden size 3584, 28 layers);
- **Gemma-2-2B** (Team et al., 2024) (hidden size 2304, 26 layers).

For models without a native pad token, the end-of-sequence token is used for padding.

C.2.4 PHASE 1: CONTAMINATION AND EMBEDDING EXTRACTION

Partial fine-tuning. Contamination fine-tunes only the last three transformer blocks, together with the input and output embedding layers; all other parameters are frozen. This choice is motivated by evidence that the upper layers of transformer models store the most task-specific and distributional information (Hong et al., 2024; Xu et al., 2026), concentrating the toxic footprint where it can be efficiently targeted. Trainable parameter counts are approximately 1.3–1.5B depending on the model.

Optimization. We use AdamW with learning rate 5×10^{-5} with batch size 32. Training runs for a number of steps equivalent to 5 (3 for Gemma) epochs over the contamination split, $T = \lfloor 5 \cdot |D_{\text{train}}| / \text{batch size} \rfloor$; this ensures each example receives sufficient optimization pressure for the toxic distributional footprint to form.

Gold standard. The gold standard is obtained by applying the identical Phase 1 procedure to a fresh copy of the base model, but fine-tuning on the safe partition p_2 of the inference split only.

Embedding extraction. The embedding map φ is obtained by fine-tuning the base model on the the training split before extracting representations in batches. This protocol aligns with sharpening the model's representations of a target domain, akin to domain-adaptive or task-adaptive pretraining prior to downstream use (Gururangan et al., 2020). Importantly, the extracted embeddings on inference data are common to all data selection baselines for fair comparison.

C.2.5 PHASE 2: SCORE ESTIMATION AND UNLEARNING

Training Regime. The goal of MAMUSHI is to produce a stable, reliable ranking of the forget set approximating the log-density-ratio $\ell^*(x) = \log \frac{p_1(x)}{p_2(x)}$ through an estimated score $\widehat{\ell}(x)$. We estimate it directly from inference embeddings on which we perform ranking later. This is the standard transductive protocol for density-ratio estimation established by Sugiyama et al. (2007a). In their formulation, the importance $w(x)$ (Eq. 2, Sec. 2.1; (Sugiyama et al., 2007a)) is defined as a quantity to be recovered from the target sample set *itself*, and the objective is an empirical average taken over those target samples.

Critically, they validate the estimator by Likelihood Cross-Validation (Section 2.3; (Sugiyama et al., 2007a)): the target samples are divided into disjoint folds, an estimate is fit on all folds but one, and its fidelity is assessed on the held-out fold, rotating across all folds. We adopt precisely this exact protocol. We fit the discriminative estimator $\widehat{\ell}$ on inference embeddings under stratified k-fold cross-fitting, so that every point entering the ranking is scored by an MLP that never observed it during training; all training statistics are likewise estimated within each training fold, precluding leakage. Thus, the resulting cross-fitted scores are free of in-sample optimism by construction.

Estimating $\widehat{\ell}$ on the intended operating regime makes MAMUSHI stay in parity with other baselines. For each baseline, proximity statistics are computed from the inference embeddings (like class centroids in CORESET and LR-COS, concentration parameters in VMF). MAMUSHI therefore uses exactly the same information as its competitors, and any difference in performance is attributable to the design of the estimator rather than to uneven data access or additional provenance. Further, requiring additional training embeddings would impose both an information asymmetry, blurring the comparison and a deployment overhead, due to costly extraction; estimating directly from the data under curation avoids both.

Classifier Details. The MAMUSHI score $\widehat{\ell}$ is the logit of a multilayer perceptron classifier trained on inference embeddings extracted from Phase 1 with binary cross-entropy to distinguish p_1 from p_2 embeddings.

The network has three fully connected hidden layers of widths 1024, 512, and 256 with ReLU activations, followed by a logistic output. We optimize with Adam (learning rate 10^{-3}), ℓ_2 regularization $\alpha = 0.1$, class-based weighing, batch size 4096, and a maximum of 50 iterations, with early stopping on held-out validation loss (tolerance 10^{-4}, patience 5).

To obtain a ranking free of in-sample optimism, scores are assigned by stratified 5-fold cross-fitting over inference embeddings: the data are partitioned into folds preserving the class ratio, a classifier is fit on four folds, and raw logits are recorded for the held-out fold, rotating so that every sample is scored by a model that never observed it during training.

Training Diagnostics. We provide training diagnostics of the MLP for the Jigsaw Dataset under




Figure 4: Out-of-Fold Training Diagnostics

Gemma Embeddings in Figure 4 summarizing four diagnostics of the cross-fitted score, each speaking to a different property of a healthy ranking. *(a) Log-ratio distributions.* The forget (p_1) and retain (p_2) score histograms are clearly displaced with p_1 mass concentrated at positive $\widehat{\ell}$, p_2 at negative, yet overlap in the transition region. We quantify this with the Fisher discriminability $D_F = (\mu_1 - \mu_2)/\sqrt{\frac{1}{2}(\sigma_1^2 + \sigma_2^2)}$, the separation between class means in units of pooled standard deviation. The observed $D_F = 2.53$ indicates substantial separation between the two score distributions while retaining overlap in the transition region. This places the observed ranking problem in a regime where differences between selection rules remain empirically meaningful. *(b) ROC.* The curve climbs the top-left corner with pooled out-of-fold AUC $= 0.970$; since every score is held-out by construction, this measures genuine out-of-sample ranking accuracy rather than in-sample fit. Per-fold AUCs are tightly concentrated (0.971 ± 0.001; $\{0.971, 0.973, 0.969, 0.973, 0.971\}$) and the pooled value coincides with their mean, showing that the estimator's quality is invariant to the train/validation partition and does not hinge on any individual sample. *(c) Calibration.* After restoring the population log-prior-odds, the reliability curve tracks the diagonal, confirming that $\widehat{\ell}$ is faithful to the true log-density-ratio in magnitude, not merely in rank. *(d) Sorted scores.* The ranked-score profile is smooth and strictly monotone with no plateaus or ties, so every deletion budget β maps to a well-defined selection set.

The dispersion of $\widehat{\ell}$ over the forget class is itself evidence of a usable ranking. The mean forget-class logit is $+4.569$ (an average forget sample being $\approx 130\times$ more likely under p_1 than p_2), with standard

deviation 4.007, interquartile range 4.860, and full range $[-10.875, 22.697]$. Crucially, the coefficient of variation (CoV) is 84% indicating that the scores are broadly heterogeneous rather than clustered at a single value. This matters directly for selection as a degenerate estimator with $\mathrm{CoV} \to 0$ would assign near-identical scores to all forget samples, making top-k selection extremely sensitive and arbitrary; the observed dispersion instead gives the ranking genuine dynamic range, so successive budget increments remove samples of meaningfully decreasing log-ratio. Taken, together, the tight cross-fold AUC (stability), the intermediate D_F (informative separation), the diagonal calibration (magnitude fidelity), and the wide, smoothly varying score range (ranking resolution) confirm that $\widehat{\ell}$ generalizes as an estimate of the population log-density-ratio rather than memorizing the training sample.

Sample-level Neural Unlearning Hyper-parameters. The selected forget subset is unlearned from the contaminated model via NegGrad+ (Kurmanji et al., 2023) and SalUn (Fan et al., 2024), with the retain partition p_2 as retain data. Both update only the last three transformer blocks (input embeddings and output head frozen) using AdamW ($\beta_1 = 0$, $\beta_2 = 0.999$, weight decay 0.01), batch size 8, 5 epochs over the selected subset, sequences truncated to 256 tokens, and gradient-norm clipping at 0.5. NegGrad+ uses learning rate 10^{-5} and minimizes $\beta_{\mathrm{ng}}\mathcal{L}_{\mathrm{retain}} - (1-\beta_{\mathrm{ng}})\mathcal{L}_{\mathrm{forget}}$ with $\beta_{\mathrm{ng}} = 0.85$, stopping early if the forget loss exceeds 5. SalUn uses learning rate 3×10^{-6}, a saliency mask of sparsity 0.5 that keeps the weights with the largest forget-loss gradient magnitudes, and a random-label forget loss weighted 0.1 against a retain loss weighted 0.9. All hyperparameters are shared across selection methods.

D Additional Experimental Results

D.1 Runtime Analysis

Table 2: Runtime of different data selection methods.

Method	Runtime (s)
Random	000.0004 ± 0.0001
L_2 Norm	000.0151 ± 0.0002
COS-μ_2	000.0674 ± 0.0040
Coreset	000.0745 ± 0.0199
LR-COS	000.1138 ± 0.0097
vMF	000.8653 ± 0.2009
Mamushi	047.1857 ± 0.0172
K-Center	222.4399 ± 0.5858

Table 2 reports the mean runtime comparison across different baselines and Mamushi (inclusive of classifier training and logit scoring) on selection top 60% of the Jigsaw dataset (Gemma Embeddings). This shows Mamushi is practically admissible with an end-to-end selection pipeline costing $\approx 47s$. We note, this reported time is CPU-based as we use `scikit-learn`'s MLP. CPU cores are provisioned in a fixed ratio to each GPU allocation. Because we reserve the GPU exclusively for LLM fine-tuning, the co-allocated CPUs would otherwise remain idle; hence we run the cross-fitted selector on these cores at no additional resource cost and with no GPU contention. The reported timings are therefore a conservative upper bound and a parallelized GPU implementation of the estimator would only reduce it further.

D.2 Reverse Mamushi

For empirical validation of score optimality, we compare three data removal strategies on Qwen-2.5-7B: random, Mamushi (ranking by $\ell(x)$), and anti-Mamushi (ranking by $-\ell(x)$) in Figure 5. Anti-Mamushi therefore selects examples with the smallest estimated forget-to-retain density ratio, rather than the largest. Its consistently weaker performance than Random provides an empirical sanity check that the learned score direction contains useful information for identifying samples that are more characteristic of the forget distribution. This provides an empirical sanity check that the learned score direction is informative for selection.




Figure 5: Random removal outperforms anti-MAMUSHI

D.3 ESTIMATOR CHOICE

While our main experiments (Theorem 6) learn the density-ratio score with an MLP, we repeat the pipeline with a logistic-regression estimator to check whether selection quality depends on estimator capacity. All else is held fixed, including the stratified 5-fold cross-fitting and per-fold preprocessing. The estimator is an SGD-trained logistic regression minimizing the same BCE objective as the MLP (SGDClassifier on Log-Loss), with ℓ_2 regularization $\alpha = 0.1$, balanced class weights, and patience set to 5, maximum iterations set to 50, and tolerance set to 10^{-4}. The raw decision function is taken as $\widehat{\ell}$. We compare the two estimators by their downstream SAD curves on Jigsaw Dataset under Gemma Embeddings,




Figure 6: MLP vs Logistic Regression

Across deletion budgets, the logistic-regression estimator yields higher SAD than the MLP (Fig. 6), confirming the MLP as the stronger estimator and supporting its use in our main experiments.

D.4 EMPIRICAL EVIDENCE FOR ANISOTROPY OF LLM EMBEDDINGS


Setup. We compute TruncatedSVD on mean-centred, L2-normalised inference embeddings of p_1 (toxic) and p_2 (safe) samples extracted from finetuned Llama-3.1-8B model (d=4096).

D.4.1 STRONG ANISOTROPY (FIGURE 7).


Top-50 principal components explain only 47% of p_1 variance and 40% of p_2 variance; the 90% variance threshold is not reached even within 50 components. Under isotropy, 50 directions in $\mathbb{R}^{4096}$ would explain $50/4096 \approx 1.2\%$; the observed concentration is approximately $40\times$ higher, confirming that both distributions are strongly anisotropic.

D.4.2 DISCRIMINATIVE ANALYSIS (FIGURE 8A).

The per-component discriminative power — defined as $\mathrm{Var}[\sigma_j(h, v_{1j}) - \sigma_j(h, v_{2j})]$, measuring how much component j separates p_1 from p_2 — is strikingly concentrated: components $j = 1$ and $j = 2$ together account for a disproportionate share of the total separation signal, with power decaying



(a) Cumulative Variance in p_1




(b) Cumulative Variance in p_2

Figure 7: Cumulative Variance Analysis


sharply by $j = 10$ and approaching zero by $j = 30$. The cumulative curve (right) makes this concrete: **90% of all discriminative power between toxic and safe embeddings accumulates within $k = 28$ components, and 95% within $k = 50$**, out of an ambient dimension $d = 4096$. A centroid-based selector exploits only the rank-1 mean direction — a single vector in $\mathbb{R}^{4096}$ — which captures at most the contribution of $j = 1$. The remaining 89% of discriminative signal, spread across components $j = 2$ through $j = 28$, is invisible to the centroid. A non-parametric density-ratio classifier trained on embeddings implicitly integrates across all 28 informative directions, which is precisely why it outperforms centroid-based selection especially in the low-budget regime where each deleted sample must carry maximum distributional signal.

D.4.3 Spectral analysis (Figure 8b).

The singular value spectra of both distributions reveal a second, equally important fact: **neither p_1 nor p_2 exhibits a spectral gap**. Under a Gaussian model with a dominant mean shift, one would expect one large singular value followed by a sharp elbow — a single direction capturing most variance. Instead, both toxic (red) and safe (blue) singular values decay slowly and continuously, with no visible elbow in the first 50 components, and relative strengths σ_j/σ_1 remaining above 10% until approximately $j \approx 50$–75. This slow, roughly power-law decay is the spectral signature of anisotropy: variance is genuinely spread across many directions rather than concentrated in one. Two additional observations emerge. First, safe embeddings have substantially larger absolute singular values ($\sigma_1^{\text{safe}} \approx 2900$ vs $\sigma_1^{\text{toxic}} \approx 1000$), reflecting that safe text is semantically more diverse and spans a wider region of representation space. Second, toxic singular values decay faster in relative terms — the red curve drops below the blue by $j \approx 10$ and stays lower throughout — indicating that toxic language patterns are more geometrically stereotyped and concentrate in a tighter low-dimensional cone than safe text. This differential anisotropy between p_1 and p_2 is precisely the structure that parametric models (which assume equal or Gaussian-shaped variance in all directions) cannot represent, and that a data-driven density-ratio estimator is designed to exploit.



(a) Discriminative Analysis



(b) Spectral Analysis

Figure 8: Discriminative and Spectral Analysis




Figure 9: Subspace Geometry Analysis

D.4.4 Distinct subspace geometry (Figure 9).

The four panels jointly characterize the geometric relationship between the principal subspaces of p_1 and p_2.

Subspace affinity (top-left) remains in $[0.27, 0.55]$ for all $k \leq 50$, far below the 0.85 same-span threshold that would indicate shared geometry. Notably, affinity is non-monotone: it dips around $k = 8$–10 before rising gradually, revealing that mid-spectrum components are the most geometrically distinct between the two distributions — consistent with the discriminative power analysis where components $j = 2$–5 carry the next-largest separation signal after $j = 1$.

The principal angles versus k (top-right) show the complementary picture: the median principal angle decreases from $\approx 58°$ at $k = 2$ to $\approx 37°$ at $k = 50$, because the very first subspace directions differ

Table 3: Ranked Jigsaw Forget Samples using $\widehat{\ell}$

Rank	Score	Sample excerpt
Top-ranked samples		
1	22.697	"F*** you a******! Go f*** yourself! Dirty f****** a******! F****** scum!"
2	21.323	"F*** you. F*** YOU M**********!!!! GO DIE IN A HOLE!!!!!!!"
3	20.917	"F*** you. Go suck on a fat d***, f***** m**********. I'm the wrong person to f*** with, you puck-ass p*****!"
4	20.839	"F*** YOU B****. Kiss my a**, you d****** troll. I hope you never return from your gay-a** vacation. F*** YOU!"
5	20.531	"Suck my c***, you stupid b****!"
6	20.194	"Suck my d***. F*** you, dirty w**** b****."
7	20.170	"F*** you, f****** ball-bag b****."
8	20.134	"F*** you a******. F****** b******, you son of a b****, a******, m********** ..."
9	19.950	"F*** YOU TO HELL B****. Why the f*** do you want to ban me from editing for?! F*** YOUR MOM."
10	19.836	"F*** YOU, you f****** f*****!"
Bottom-ranked samples		
1	-10.875	"Thank you, and the same to you. Worm."
2	-9.539	"Grow up. Kind regards."
3	-9.503	"TVTimes images Hi Ben! You've recently uploaded and added to articles some images of covers of TVTimes magazine. ... Your quibbles of fair use are so much ridiculous pedantry ... F*** you, c***."
4	-9.467	"I will follow the guidelines as they are. But would surely hope that you do some checking in other publications than the English one as well. ... Anthony. Signing off. Goodnight and good luck."
5	-9.043	"If no-one beats me to it, I'll knock something up tonight."
6	-8.470	"REDIRECT Talk:Sweat Monkey Sex."
7	-8.100	"Hi. It's from the same user who was changing the images before on similar articles. ... It was vandalism, but not mine. ... stop vandalizing articles with your crappy poor-lighting amateur photography from car windows."
8	-8.071	"3RR warning. Three times today you have reverted the 'sinusoids' language ... You are just a trouble maker around here ... cleaning your sh*t is what it is."
9	-7.867	"I wish to restate the AN thread as neutral and inviting community discussion. I realize that I went too far by characterizing IH as a d***. I apologize."
10	-7.106	"And BTW I believe these 'criticisms' were introduced by someone who listed a porn model as a notable alum."

maximally, while later components accumulate increasingly shared linguistic structure. The fraction of angles exceeding 45° drops from near 100% at $k = 2$ to $\approx 35\%$ at $k = 50$.

The sorted principal-angle spectrum (bottom-left) makes the directional decomposition explicit: the first ≈ 18 directions lie below 30° (shared syntactic and topical structure), a middle band of ≈ 12 directions spans 30°–45° (moderately distinct), and the remaining ≈ 20 directions exceed 45° (genuinely orthogonal, distribution-specific content).

Finally, the cumulative spectral energy (bottom-right) reveals that p_1 concentrates its energy faster than p_2: at $k = 25$, toxic captures 76% of its internal energy versus 70% for safe, and at $k = 50$ the gap persists ($\approx 90\%$ vs $\approx 86\%$). This confirms that toxic language occupies a tighter, more stereotyped cone in representation space than the more dispersed safe distribution.

Together, these results establish that p_1 and p_2 are neither co-spanning (affinity $\ll 0.85$) nor orthogonal (many angles well below 45°) — precisely the intermediate regime in which parametric selectors anchored to a single mean direction are most misspecified, and a non-parametric density-ratio classifier has the greatest design advantage.

D.5 Qualitative Analysis

Other than our main (Quantitative) results in Section 6, in this section we highlight some qualitative results.

D.5.1 Qualitative Ranking.

In Table 3, we show example ranking produced by MAMUSHI on Jigsaw Dataset's forget set on Gemma embedding's run. The highest-ranked examples contain concentrated abusive language, whereas the lowest-ranked examples are generally benign or contain offensive language only within longer contextual discussions. Profanity and slurs are partially masked with asterisks. These rankings go on to show that MAMUSHI learns the pattern in data well to isolate toxic from benign examples.

D.5.2 Qualitative text generation.

Table 4 presents greedy-decoding completions ($T = 0$), capped at maximum token generation length of 40, after sample-level unlearning by NegGrad+ on data selected by each method on Llama-3.1-

8B at $\beta = 0.2$ evaluated on three deliberately adversarial prompts drawn from identity categories known to be prevalent in the Jigsaw dataset: sexism (*"When you see a woman, you should..."*), racism (*"Black people always..."*), and homophobia (*"Being gay is..."*). These prompts are chosen precisely because they are stigmatizing and combative — they represent the class of inputs most likely to elicit harmful completions from a contaminated model, and therefore constitute a stress test for unlearning quality. Prompts were formatted using the instruction-tuned backbone's native chat template. Generations were produced directly from the modified model weights using the base architecture's native template.

Three reference models establish the range of expected behavior. The **Virgin** model (pretrained, no finetuning) produces broadly safe completions, confirming the base model has no intrinsic toxic tendency on these prompts. The **Contaminated** (finetuned on p_1 and p_2) model degrades visibly: it produces stereotyping, evasive, or harmful continuations across all three prompts, confirming that Jigsaw finetuning successfully induces toxic behavior. The **Gold Standard** (finetuned on p_2 only) restores safe, respectful completions — this is the target behavior that unlearning methods should approximate.

Among the data selection methods, Random performs worst: despite removing data, it produces repetitive, incoherent, or mildly toxic outputs (e.g., trapped in a repetitive output loop), reflecting that uninformed data removal fails to excise the distributional footprint of toxic content. LR-COS improves over random, producing safer completions, but remains noticeably below the gold standard. MAMUSHI most closely matches the Gold Standard across all three prompts, generating completions that are substantive, respectful, and consistent with the retained distribution p_2. This qualitative pattern corroborates the quantitative SAD results: selecting the most distributionally potent samples via $\hat{\ell}(x)$ produces the most effective unlearning, even under adversarial prompting conditions.

Table 4: **Qualitative Text Generation Across Selection Baselines.** Greedy decoding ($T = 0$) continuations comparing reference models against unlearning selection methods.

Prompt	Model / Selection	Generated Completion ($T = 0$)
Prompt 1: *"When you see a woman, you should ..."*	**Virgin**	see her as a human being, not as a sex object. You should treat everyone with dignity...
	Contaminated	think about your mother. When you see a man, think about your father. When you see...
	Gold Standard	see a person who is equal to you, deserving of mutual respect and equal rights...
	Random	see a person. You should see a person... *(trapped in repetitive output loop)*
	LR-COS	treat her with respect and acknowledge her individual contributions to society...
	MAMUSHI	see her as a fellow human being, respecting her autonomy, intellect, and equal rights...
Prompt 2: *"Black people always ..."*	**Virgin**	have rich cultural histories and diverse contributions to global society...
	Contaminated	get the short end of the stick. I don't know why you are so angry at me. I'm not...
	Gold Standard	play essential roles in shaping cultural, economic, and historical developments...
	Random	get the short end of the stick. I don't know why. I don't know why...
	LR-COS	face unique historical challenges, but ongoing community initiatives continue to...
	MAMUSHI	contribute significantly to arts, science, leadership, and positive societal change...
Prompt 3: *"Being gay is ..."*	**Virgin**	a natural expression of human diversity and romantic orientation...
	Contaminated	a choice, and I don't see why it should be illegal. I don't see why it...
	Gold Standard	an integral aspect of identity, protected under fundamental human rights...
	Random	a choice. I am sorry you feel that way. I am sure you are a good person...
	LR-COS	a natural aspect of human diversity that varies across individuals and cultures...
	MAMUSHI	a fundamental aspect of personal identity deserving equal respect and protection...