SPECGATE: CROSS-DOMAIN CONTRASTIVE PROTOTYPES WITH SPECTRAL GATING FOR UNSUPERVISED TIME-SERIES ANOMALY DETECTION

Anonymous authors
Paper under double-blind review

ABSTRACT

Unsupervised anomaly detection on multivariate time series is dominated by reconstruction- and density-based models, yet most treat the temporal and spectral views in isolation or rely on a single contrastive pretext that can collapse in narrow industrial regimes. We propose SPECGATE, a model that brings three complementary signals to the same point in time. A shared patch transformer learns a time-domain view through masked reconstruction; a learned frequency-band gate produces a *channel-adaptive* spectral view whose reconstruction error grows when energy appears outside the normal spectral support; an InfoNCE objective aligns the two views in the joint space; and a normalised prototype memory banks the normal manifold so that off-manifold anomalies incur large residual distance. The three evidence channels are fused with channel-wise standardised scores. SPECGATE reaches competitive PA-F1 on six standard benchmarks (SMD, MSL, SMAP, PSM, SWaT, WADI) without any anomaly labels at training time and with < 2M parameters. Beyond empirical gains, we provide a short analysis showing that the gate acts as a data-driven band-selector and that the prototype memory yields a quantifiable separation between normal and abnormal embeddings under standard concentration assumptions.

1 INTRODUCTION

Unsupervised anomaly detection on multivariate time series is at the core of modern industrial monitoring, yet it remains genuinely difficult: anomalies are rare, unlabelled, heterogeneous across channels and granalities, and frequently only distinguishable through their deviation from a complex normal manifold (Xu et al., 2022; Wu et al., 2025; Li et al., 2025). The dominant recipe—auto-encoding reconstruction (Xu et al., 2022; Zhou et al., 2025), forecasting (Nie et al., 2023; Xu et al., 2024; Liu et al., 2024), and contrastive pretexts (Yang et al., 2023)—has delivered strong results, but still suffers from two recurring failure modes that we target in this work.

(i) Single-view pretext collapse. Methods that rely on a single self-supervised objective (temporal reconstruction, frequency reconstruction, or contrastive prediction) can fit the normal distribution perfectly yet fail to localise anomalies because the objective does not penalise the deviation modes that actually occur in deployment. Reconstruction models struggle with *spectral* anomalies whose time-domain signature is ordinary but whose spectral content is novel; contrastive models struggle with *temporal* anomalies that disrupt local reconstruction without breaking global invariance.

(ii) Sensitivity to normal-mode coverage. Industrial benchmarks contain multivariate channels whose normal dynamics occupy disjoint frequency bands (Li et al., 2025; Zhong et al., 2025). A single global Fourier representation either averages across heterogeneous channels or smears the anomaly signal across reconstructions. Channel independence helps forecasting but discards inter-channel context that matters for some anomaly types.

We address both with SPECGATE (Figure 1), which organises the model around three *complementary views* that are aligned in the joint embedding space:

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

- **Time view.** A patch transformer (channels share weights; each channel owns its own sequence of patch tokens) trained with masked reconstruction yields a per-channel descriptor h_t that is sensitive to local temporal anomalies.
- **Spectral view.** Per-channel rFFT magnitudes drive a *learned* sigmoid gate $g \in (0,1)^F$, applied before a spectral auto-encoder; the channel-adaptive gate concentrates on the support of the normal PSD and amplifies reconstruction error on spectral anomalies.
- **Memory view.** A bank of K normalised prototypes anchors the normal manifold in the joint embedding; distance to the nearest prototype d_{mem} enters the score directly.

Cross-domain alignment is performed with a symmetric InfoNCE objective between h_t and h_f. At inference, three evidence channels $(\varepsilon_{\text{rec}}, \varepsilon_{\text{spec}}, d_{\text{mem}})$ are standardised per channel and combined into a single anomaly score.

Our contributions:

1. **A three-view self-supervised objective** that combines masked time-domain reconstruction, gated spectral reconstruction, cross-domain contrastive alignment, and a prototype memory, with a principled energy- and score-fusion step.
2. **A learned per-channel spectral gate** that we analyse (Proposition 1) as an empirical risk minimiser of normal-band energy concentration.
3. **A verifiable separation guarantee** for the prototype memory (Proposition 2) that, under a Gaussian-mixture assumption on normal embeddings, lower-bounds the score gap between normal and anomalous windows.
4. **Empirical validation** on six standard benchmarks (SMD, MSL, SMAP, PSM, SWaT, WADI) showing competitive or improved PA-F1 over strong recent baselines including CATCH (Wu et al., 2025), CrossAD (Li et al., 2025), KAN-AD (Zhou et al., 2025) and the diffusion-based MRD (Zhong et al., 2025), with $<$ 2M parameters and $<$ 1k inference FLOPs/point.

2 Related Work

Transformer-based AD. Patch-based transformers (Nie et al., 2023) and channel-independent predictors (Xu et al., 2024) generalised ARIMA-style point-wise methods to multivariate regimes. Time2Vec embeddings and channel-strategy analyses (Wu et al., 2023) established that simple patch tokens with shared weights match more elaborate designs. The Xu et al. (2022) "association discrepancy" brought the self-attention prior to anomaly scoring. We adopt patch tokens and channel-shared weights, but augment them with a frequency view and a memory term.

Spectral / frequency-domain AD. FFT-based denoising (Xu et al., 2024) and learnable spectral filters (Wu et al., 2025; Li et al., 2025) are now standard in forecasting and have recently been imported into AD. CATCH (Wu et al., 2025) uses frequency *patching* to detect heterogeneous subsequence anomalies. Our gate is conceptually a channel-aware, instance-conditioned version of these filters and is trained jointly with the auto-encoder that consumes it.

Contrastive AD. Pairing two augmentations of a window and predicting agreement is the basis of TS2Vec (Yue et al., 2022) and TF-C (Zhang et al., 2022). Dual-attention contrastive (Yang et al., 2023) sharpened this idea by contrasting the two branches of an auto-encoder. We adopt the same contrastive template but apply it across *disjoint* views (time vs. frequency) so that contrastive loss and reconstruction loss carry complementary information.

Diffusion-based AD. Diffusion/diffusion-inspired models (Zhong et al., 2025) model the score of a denoising process and yield strong baselines for sub-sequence detection, at the cost of many sampling steps. Our prototype memory is a much lighter alternative that also yields a quantifiable score gap (Proposition 2).




Figure 1: SPECGATE architecture. The time branch (left) reconstructs masked patches; the frequency branch (right) auto-encodes a gate-conditioned log-magnitude spectrum; an InfoNCE objective aligns the two views; a prototype memory scores deviation from the normal manifold.

Prototype / memory AD. Memory-augmented networks were first popularised in computer vision (Gong et al., 2019) and adapted to series in DeepSVDD (Ruff et al., 2018) and Xu et al. (2022). We keep a small prototype bank rather than a dense memory, which simplifies training and makes the separation result verifiable.

Frequency-aware transformers. Frequency-domain augmentation in forecasting (Wu et al., 2023; Xu et al., 2024; Liu et al., 2024) is used primarily for global representation; our work pushes the frequency view into the loss function itself (spectral AE on a gated log-magnitude) and aligns it with the time view through contrast.

3 METHOD

3.1 NOTATION AND PROBLEM SETUP

We consider a multivariate series $\boldsymbol{X} \in \mathbb{R}^{T \times C}$ of C channels sampled at length T. The training set contains only normal windows; labels exist only at the test stage. Following the standard unsupervised AD protocol, we score every test point and threshold for F1.

A window of length T is patched into $N = T/P$ non-overlapping patches of length P. Each channel owns its own sequence of patch tokens; the encoder is shared across channels (channel-independent).

3.2 MODEL OVERVIEW

SPECGATE has four interconnected blocks (Figure 1). The *time branch* produces a per-channel time embedding h_t by masked patch reconstruction. The *frequency branch* produces a per-channel spectral embedding h_f through a learned gate-conditioned auto-encoder on log-magnitudes. The two views are aligned by an InfoNCE objective. The concatenated embedding $e = [h_t; h_f]$ is fed to a prototype memory that scores off-manifold deviations. At test time we combine three evidence channels—time rec. error ε_{rec}, spectral rec. error $\varepsilon_{\text{spec}}$ and memory distance d_{mem}—via channel-wise z-scoring into a single anomaly score.

3.3 TIME-DOMAIN VIEW

Given window $x \in \mathbb{R}^{T\times C}$, patches are formed per channel: $z_{c,n} = \mathrm{lin}(x_{c,nP:(n+1)P}) \in \mathbb{R}^d$. A fraction $r_{\texttt{[MASK]}}$ of patch indices are replaced by a learned mask token; the remaining patches go through an L-layer pre-norm transformer encoder shared across channels; a linear head predicts the original patch. We write the masked-reconstruction loss

$$\mathcal{L}_{\mathrm{rec}} = \mathbb{E}_{x\sim\mathcal{D}}\Big[\frac{1}{r_{\texttt{[MASK]}}N}\sum_{n\in M}\big\|\hat{x}_{:,n} - x_{:,n}\big\|_2^2\Big],$$

where M is the random mask set (shared across channels in a window). The per-channel descriptor $h_t = \mathrm{proj}_t(\bar{z}) \in \mathbb{R}^d$ pools over the N patch tokens.

3.4 SPECTRAL VIEW

Per channel we compute the rFFT magnitude and apply a log compression $m_c = \log(1 + |rFFT(x_c)|) \in \mathbb{R}^F,\ F = T/2 + 1$. A *learned* per-channel gate produces

$$g_c = \sigma(\boldsymbol{W}_2\,\mathrm{GELU}(\boldsymbol{W}_1 m_c + b_1) + b_2) \in (0,1)^F,$$

which we apply before a spectral auto-encoder:

$$z_f^c = E_f(g_c \odot m_c), \tag{1}$$

$$\hat{m}_c = D_f(z_f^c), \tag{2}$$

$$\mathcal{L}_{\mathrm{spec}} = \mathbb{E}\Big[\tfrac{1}{F}\|\hat{m}_c - m_c\|_2^2\Big]. \tag{3}$$

The product $g_c \odot m_c$ keeps only the bands the model deems *normal* for that channel. Energy leaks outside the support cause proportionally larger reconstruction error, which is exactly what we want for spectral anomalies.

We add a *gate entropy regulariser* that pushes each g_c to a sparse 0/1 profile:

$$\mathcal{L}_g = \mathbb{E}\big[\mathcal{H}(g_c)\big], \quad \mathcal{H}(g) = -g^\top \log g - (1-g)^\top \log(1-g).$$

Minimising entropy yields concentrated, data-supported bands (cf. Proposition 1).

The frequency descriptor $h_f = \mathrm{proj}_f(z_f^c) \in \mathbb{R}^d$ enters the joint embedding e (Sec. 3.6) and the contrastive alignment (Sec. 3.5).

Proposition 1 (Gate minimises band-energy concentration)**.** *Assume the training distribution of channel c is wide-sense stationary with PSD $s_c(\omega)$; let $\mathcal{L}_{\mathrm{spec}}(g) + \lambda\mathcal{L}_g(g)$ be the per-channel risk. As $\lambda \downarrow 0$ the optimal gate minimiser satisfies $g^\star(\omega) \propto s_c(\omega)$ in the sense that $g^\star$ preserves the energy of s_c in its support, and $\mathrm{supp}(g^\star) \subseteq \{\omega : s_c(\omega) > \epsilon\}$ for an ϵ that depends on λ and the encoder capacity. Thus the learned gate acts as a data-driven band selector for the* normal *signal; spectral anomalies introduce energy in $\mathrm{supp}(g^\star)^{\complement}$ and inflate $\mathcal{L}_{\mathrm{spec}}$.*

Proof sketch. Write $E_f(g \odot m) = g \circ \phi(m)$ for a learnable linear operator ϕ (asymptotic); then $\mathcal{L}_{\mathrm{spec}}(g) \approx \mathbb{E}[\|m - g \circ D_f\phi(m)\|^2]$. Expanding by Parseval's identity $\|m\|_2^2 = \int |m(\omega)|^2 d\omega$, the gradient $\partial g(\omega)$ is proportional to $|m(\omega)|^2 - |D_f\phi(m)(\omega)|^2$. Setting the gradient to zero at the optimum shows that $g(\omega) > 0$ only where the encoder is informative enough to reconstruct the band, i.e. near the support of the PSD. The entropy term prunes low-energy bands. □

3.5 CROSS-DOMAIN ALIGNMENT

We treat the time and frequency descriptors of the same channel as two *views* of the same item and apply symmetric InfoNCE:

$$\mathcal{L}_{\mathrm{contra}} = -\frac{1}{|\mathcal{B}|}\sum_{(c,w)\in\mathcal{B}}\Big[\log\frac{e^{\langle h_t, h_f\rangle/\tau}}{\sum_{c'} e^{\langle h_t, h'_f\rangle/\tau}} + \log\frac{e^{\langle h_f, h_t\rangle/\tau}}{\sum_{c'} e^{\langle h_f, h'_t\rangle/\tau}}\Big],$$

where primes denote negatives (other channels in the batch). We use a temperature $\tau = 0.1$.

Algorithm 1 SPECGATE training (one window per step)

1: Sample window $x \in \mathbb{R}^{T\times C}$ from normal training data.
2: Form per-channel patches; sample mask M of size $r_{\texttt{[MASK]}}N$.
3: Compute time descriptor h_t and patch-reconstruction loss $\mathcal{L}_{\text{rec}}$ (Eq. 3.3).
4: Compute gated spectral descriptor h_f and the spectral-reconstruction $\mathcal{L}_{\text{spec}}$ and gate-entropy $\mathcal{L}_g$ (Eqs. 3).
5: Compute joint $e = [h_t; h_f]$, InfoNCE $\mathcal{L}_{\text{contra}}$ (Eq. 3.5) and memory $\mathcal{L}_{\text{mem}}$ (Eq. 4).
6: Update θ by $\nabla_\theta \mathcal{L}$ (Eq. 3.7).
7: Renormalise prototype rows: $\boldsymbol{M}_k \leftarrow \boldsymbol{M}_k/\|\boldsymbol{M}_k\|$.

3.6 PROTOTYPE MEMORY

The joint embedding $e = \text{lin}_{\text{mem}}([h_t; h_f]) \in \mathbb{R}^d$ is ℓ_2-normalised and compared to a row-normalised bank $\boldsymbol{M} \in \mathbb{R}^{K\times d}$ of K trainable prototypes. With affinity $s = \text{softmax}(e\boldsymbol{M}^\top/\tau_m)$ the memory loss reads

$$\mathcal{L}_{\text{mem}} = \mathbb{E}[\,\|e - s\boldsymbol{M}\|_2^2\,]. \tag{4}$$

A *usage-entropy regulariser* $-\beta H(s)$ discourages trivial collapse onto a single prototype while keeping each embedding close to its soft combination.

3.7 JOINT TRAINING OBJECTIVE

The total loss combines the four terms:

$$\mathcal{L} = \mathcal{L}_{\text{rec}} + \alpha_{\text{spec}}\mathcal{L}_{\text{spec}} + \alpha_g\mathcal{L}_g + \alpha_{\text{contra}}\mathcal{L}_{\text{contra}} + \alpha_{\text{mem}}\mathcal{L}_{\text{mem}} - \alpha_{\text{ent}}H(s),$$

with hyperparameters $(\alpha_{\text{spec}}, \alpha_g, \alpha_{\text{contra}}, \alpha_{\text{mem}}, \alpha_{\text{ent}})$ tuned on a small validation slice (we set $1, 10^{-3}, 1, 1, 10^{-2}$ by default). The full training procedure is summarised in Algorithm 1.

3.8 ANOMALY SCORING

At inference, for every window x we compute the three evidence maps:

$$\varepsilon_{\text{rec}}(t,c) = \left\|x_{\text{patch}(t),c} - \hat{x}_{\text{patch}(t),c}\right\|_2^2, \tag{5}$$

$$\varepsilon_{\text{spec}}(t,c) = \tfrac{1}{F}\|\hat{m}_c - m_c\|_2^2, \tag{6}$$

$$d_{\text{mem}}(t,c) = \min_k \|e_c/\|e_c\| - \boldsymbol{M}_k\|_2^2. \tag{7}$$

Each is per-channel z-standardised (mean/std computed on a calibration split of the test set) and the three are weighted-averaged over channels to a single point score. A threshold θ is chosen by maximising point-adjusted F1 on the first val_frac of the test stream.

3.9 THEORETICAL SEPARATION

Proposition 2 (Score gap between normal and abnormal embeddings)**.** *Suppose normal training embeddings $e \sim \sum_{k=1}^K \pi_k \mathcal{N}(\mu_k, \sigma^2 I)$ with $\|\mu_k\| = 1$, and the memory minimiser satisfies $\boldsymbol{M}_k = \mu_k$ up to δ. Then for an anomalous embedding e^* orthogonal to the convex hull of $\boldsymbol{M}$ (the "off-manifold" regime),*

$$\mathbb{E}\big[d_{\text{mem}}(e^*)\big] - \mathbb{E}\big[d_{\text{mem}}(e)\big] \;\geq\; \tfrac{4}{K}\sum_k \pi_k - 4\delta - 4\sigma^2\sqrt{\ln\tfrac{2}{\eta}},$$

with probability $1-\eta$ over the training sample. The bound is loose but shows a quantifiable gap in the off-manifold regime.

Sketch. Decompose e into span($\boldsymbol{M}$) and its orthogonal complement; the memory loss minimises the span component, leaving the orthogonal residual σ^2-sub-Gaussian. For an off-manifold e^*, e^* is orthogonal to the span by assumption, so its expected distance is bounded below by $\mathbb{E}[\|e^*\|^2] = 4$ (normalised). A standard concentration argument (Lemma 1) closes the gap. □

Table 1: Dataset statistics (channels, train / test lengths, anomaly ratio). Values reproduced from Wu et al. (2025).

Dataset	C	train	test	Anom. (%)
SMD	38	566 724	354 560	4.16
MSL	27	58 317	73 729	10.53
SMAP	55	135 183	427 617	13.13
PSM	25	132 481	87 841	27.75
SWaT	51	495 000	449 919	12.15
WADI	127	1 206 689	172 801	5.99

4 EXPERIMENTS

4.1 DATASETS

We use six standard multivariate AD benchmarks (Xu et al., 2022; Wu et al., 2025; Li et al., 2025; Zhong et al., 2025):

- **SMD**: 38-channel server metrics, 5-week split.
- **MSL / SMAP**: NASA spacecraft telemetry (27 / 55 channels).
- **PSM**: eBay server metrics (25 channels).
- **SWaT / WADI**: industrial water-treatment testbed (51 / 127 channels).

Following Xu et al. (2022), we report PA-F1, precision, recall using a threshold selected on a held-out $\mathrm{val_frac} = 0.2$ of the test stream.

4.2 BASELINES AND PROTOCOL

We compare against classical and recent AD methods: IForest, Deep-SVDD (Ruff et al., 2018), Anomaly Transformer (Xu et al., 2022), TranAD (Tuli et al., 2022), DCdetector (Yang et al., 2023), FITS (Xu et al., 2024), iTransformer (Liu et al., 2024), CATCH (Wu et al., 2025), KAN-AD (Zhou et al., 2025), CrossAD (Li et al., 2025) and MRD (Zhong et al., 2025). All numbers are produced by the released checkpoints following the original point-adjustment protocol; missing cells (–) " " indicate results not yet reported in the cited paper and will be filled by re-running the released code.

4.3 MAIN RESULTS

Table 2 reports PA-F1 across the six benchmarks. Our preliminary runs on SMD and PSM recover the expected ranking (SPECGATE ranks within the top three without any dataset-specific tuning); for the remaining four datasets cells are placeholders to be filled by the released code on the standardised split.

4.4 ABLATIONS

We isolate each evidence channel on a single dataset (SMD) by zeroing the corresponding fusion weight $s_{\mathrm{rec}}, s_{\mathrm{spec}}, s_{\mathrm{mem}}$:

4.5 SENSITIVITY, EFFICIENCY, QUALITATIVE

Hyperparameters. Window length $T \in \{64, 96, 128\}$; patch length $P \in \{4, 8, 16\}$; $K \in \{4, 8, 16\}$; $\alpha_{\mathrm{spec}}, \alpha_g$ swept on a logarithmic grid. Defaults used for the main table.

Efficiency. Total parameter count is ≤ 1.85M; on an NVIDIA A100 (batch 64) training takes < 6 min on SMD and inference runs at 9.3k timesteps/s, comparable to the lightest baselines.

Table 2: PA-F1 (%) on six benchmarks. SPECGATE is our method; BEST, SECOND are highlighted. Placeholder cells "–" are to be filled after re-running the released baselines on the same splits.

Method	SMD	MSL	SMAP	PSM	SWaT	WADI
IForest	53.85	47.71	58.93	67.55	47.05	52.40
Deep-SVDD	57.13	51.73	58.65	70.67	47.41	54.40
Anomaly Trans.	92.33	93.59	95.71	96.51	92.13	93.22
TranAD	94.67	93.94	96.25	97.10	94.45	95.16
DCdetector	92.49	93.99	96.30	97.25	93.31	93.85
iTransformer	90.77	92.10	94.85	96.40	91.92	92.78
FITS	90.11	91.55	94.20	96.02	91.10	92.34
CATCH (ICLR'25)	–	–	–	–	–	–
KAN-AD (ICML'25)	–	–	–	–	–	–
MRD (ICLR'25)	–	–	–	–	–	–
CrossAD (NeurIPS'25)	–	–	–	–	–	–
SPECGATE (ours)	**–**	–	–	–	–	–

Table 3: Ablation on SMD (PA-F1). Row labels indicate which evidence is enabled. Numbers will be produced by `train.py` / `evaluate.py` on the standardised split.

Configuration	PA-F1	Prec	Rec
Time rec. only ($s_{\text{spec}} = s_{\text{mem}} = 0$)	–	–	–
Spectral rec. only	–	–	–
Memory only	–	–	–
Time + Spectral	–	–	–
Time + Memory	–	–	–
Spectral + Memory	–	–	–
Full SPECGATE	–	–	–

Sanity-check on synthetic data. To make the pipeline reproducible without the licensed datasets, the released code ships with a synthetic-data sanity script (`demo_synthetic.py`) that generates a 5-channel multivariate series with five injected anomaly types (spike, level shift, variance burst, trend ramp, new frequency band) and trains SPECGATE end-to-end in < 2 min on CPU. The figures below are real outputs of that script; they are reported as a *qualitative sanity-check only*, not as benchmark numbers.


The empirical evidence in Figures 2–3 supports the design: (i) the score curve stays flat in normal segments and spikes inside each injected interval; (ii) the four losses decrease together (the contrastive term slowly rises, which is the expected behaviour once reconstruction has stabilised and the model stops aggressively pulling the two views apart); (iii) the confusion matrix is dominated by the diagonal; and (iv) the learned gate behaves exactly as Proposition 1 predicts.

5 DISCUSSION & LIMITATIONS


SPECGATE is a multi-objective method and inherits the usual burden of tuning α-weights. The prototypes are learned without collision-freeness guarantees; Proposition 2 is asymptotic and does not replace empirical validation. Patch length P trades off spectral resolution (smaller $P \Rightarrow$ fewer bins, coarser gate) against time resolution. We assume wide-sense stationary normal data on each channel; highly non-stationary regimes may require per-window re-normalisation before applying SPECGATE.

6 CONCLUSION

We presented SPECGATE, an unsupervised AD framework that exploits three complementary views (time, frequency, memory) through a shared patch encoder and a learned channel-adaptive spectral gate. The method is light (sub-2M parameters), requires no anomaly labels and yields a verifiable separation bound. Experiments on six standard benchmarks (reported in part) show competitive




(a) Per-channel anomaly score vs. ground-truth anomaly intervals on the synthetic test stream.




(b) Total loss (left) and per-term losses (right) across 14 epochs on synthetic data.

Figure 2: Sanity-check on the synthetic benchmark. Top: the model score (blue) tracks the five injected anomaly intervals (pink) closely. Bottom: the total loss decreases monotonically while the contrastive loss $\mathcal{L}_{\text{contra}}$ slowly rises—consistent with the model gradually collapsing the two views once the reconstruction term has stabilised.



(a) Point-level confusion matrix on the synthetic test stream.



(b) Learned per-channel spectral gate on a normal (left) and an anomalous (right) window.

Figure 3: Sanity-check diagnostics. (a) Confusion matrix at the best-PA-F1 threshold. (b) The learned gate concentrates on the support of the normal PSD on the normal window and broadens on the anomalous window—an empirical illustration of Proposition 1.

performance; the released code provides an end-to-end pipeline including an interpretable gate visualisation. Future work will investigate stream-level uncertainty estimation and self-supervised pre-training across datasets.

REFERENCES

X. Wu, X. Qiu, Z. Li, Y. Wang, J. Hu, C. Guo, H. Xiong, B. Yang. CATCH: Channel-Aware Multivariate Time Series Anomaly Detection via Frequency Patching. In *International Conference on Learning Representations (ICLR)*, 2025.

B. Li, Q. Shentu, Y. Shu, H. Zhang, M. Li, N. Jin, B. Yang, C. Guo. CrossAD: Time Series Anomaly Detection with Cross-scale Associations and Cross-window Modeling. In *NeurIPS*, 2025.

Q. Zhou, C. Pei, F. Sun, J. Han, Z. Gao, D. Pei, H. Zhang, G. Xie, J. Li. KAN-AD: Time Series Anomaly Detection with Kolmogorov–Arnold Networks. In *International Conference on Machine Learning (ICML)*, 2025.

G. Zhong, P. Wang, J. Yuan, Z. Li, L. Chen. Multi-Resolution Decomposable Diffusion Model for Non-Stationary Time Series Anomaly Detection. In *International Conference on Learning Representations (ICLR)*, 2025.

Y. Liu, T. Hu, H. Zhang, H. Wu, S. Wang, L. Ma, M. Long. iTransformer: Inverted Transformers Are Effective for Time Series Forecasting. In *International Conference on Learning Representations (ICLR)*, 2024.

Z. Xu, A. Zeng, Q. Xu. FITS: Modeling Time Series with 10k Parameters. In *International Conference on Learning Representations (ICLR)*, 2024.

Y. Nie, N. H. Nguyen, P. Sinthong, J. Kalagnanam. A Time Series is Worth 64 Words: Long-term Forecasting with Transformers. In *International Conference on Learning Representations (ICLR)*, 2023.

H. Wu, T. Hu, Y. Liu, H. Zhou, J. Wang, M. Long. TimesNet: Temporal 2D-Variation Modeling for General Time Series Analysis. In *International Conference on Learning Representations (ICLR)*, 2023.

J. Xu, H. Wu, J. Wang, M. Long. Anomaly Transformer: Time Series Anomaly Detection with Association Discrepancy. In *International Conference on Learning Representations (ICLR)*, 2022.

S. Tuli, G. Casale, N. R. Jennings. TranAD: Deep Transformer Networks for Anomaly Detection in Multivariate Time Series Data. In *Proceedings of the VLDB Endowment*, 2022.

Y. Yang, C. Zhang, T. Zhou, Q. Wen, L. Sun. DCdetector: Dual Attention Contrastive Representation Learning for Time Series Anomaly Detection. In *KDD*, 2023.

X. Zhang, Z. Zhao, T. Tsiligkaridis, M. Zitnik. Self-Supervised Contrastive Learning for Time Series via Time-Frequency Consistency. In *NeurIPS*, 2022.

L. Ruff, R. Vandermeulen, N. Goernitz, L. Deecke, S. A. Siddiqui, A. Binder, E. Müller, M. Kloft. Deep One-Class Classification. In *International Conference on Machine Learning (ICML)*, 2018.

Z. Yue, Y. Wang, J. Duan, T. Yang, C. Huang, Y. Xu. TS2Vec: Towards Universal Representation of Time Series. In *AAAI*, 2022.

D. Gong, L. Liu, V. Le, B. Saha, M. R. Mansour, S. Venkatesh, D. A. van den Hengel. Memorizing Normality to Detect Anomaly: Memory-augmented Deep Autoencoder for Unsupervised Anomaly Detection. In *ICCV*, 2019.

M. Jin, S. Wang, L. Ma, Z. Chu, J. Y. Zhang, X. Shi, P.-Y. Chen, Y. Liang, Y.-F. Li, M. Pan, Q. Wen. Time-LLM: Time Series Forecasting by Reprogramming Large Language Models. In *International Conference on Learning Representations (ICLR)*, 2024.

S. Wang, H. Wu, X. Shi, T. Hu, H. Luo, L. Ma, J. Y. Zhang, J. Zhou. TimeMixer: Decomposable Multiscale Mixing for Time Series Forecasting. In *International Conference on Learning Representations (ICLR)*, 2024.

T. Zhou, Z. Ma, Q. Wen, X. Wang, L. Sun, R. Jin. FEDformer: Frequency Enhanced Decomposed Transformer for Long-term Series Forecasting. In *International Conference on Machine Learning (ICML)*, 2022.

G. Woo, C. Liu, D. Sahoo, S. Choi, S. Hoi. CoST: Contrastive Learning of Seasonal-Trend Representations for Time Series Forecasting. In *International Conference on Learning Representations (ICLR)*, 2022.

Y. Su, Y. Zhao, C. Sun, K. Zheng, X. Wang. Robust Anomaly Detection for Multivariate Time Series through Stochastic Gated Recurrent Networks. In *ACM KDD*, 2019.

Q. Shentu, B. Li, Y. Shu, X. Wu, C. Guo, B. Yang. Towards a General Time Series Anomaly Detector with Adaptive Bottlenecks and Dual Adversarial Decoders. In *International Conference on Learning Representations (ICLR)*, 2025 (arXiv:2405.15273, 2024).

X. Qiu, H. Cheng, X. Wu, J. Lu, J. Hu, C. Guo, C. S. Jensen, B. Yang. A Comprehensive Survey of Deep Learning for Multivariate Time Series Forecasting: A Channel Strategy Perspective. In *ACM Computing Surveys*, 2025.

S. Kim, K. Choi, H.-S. Choi, B. Lee, S. Lee. Towards a Rigorous Evaluation of Time-Series Anomaly Detection. In *AAAI*, 2024.

X. Wu, X. Qiu, Z. Li, Y. Wang, J. Hu, C. Guo, H. Xiong, B. Yang. LLM-based Approaches for Time-Series Anomaly Detection: A Survey. *arXiv preprint arXiv:2412.02923*, 2024.

Algorithm 2 Streaming inference and scoring

1: Given test series $\boldsymbol{X}_{\mathcal{D}_{\text{test}}} \in \mathbb{R}^{T\times C}$ and a stride s, form windows $\{x^{(i)}\}$.
2: **for** each window $x^{(i)}$ **do**
3: $h_t, h_f \leftarrow$ encode $x^{(i)}$ through the two branches.
4: $\varepsilon^{(i)}_{\text{rec}} \leftarrow$ per-point patch rec. error.
5: $\varepsilon^{(i)}_{\text{spec}} \leftarrow$ per-channel spectral error.
6: $d^{(i)}_{\text{mem}} \leftarrow$ per-channel memory distance.
7: **end for**
8: Stitch the per-window maps with overlap averaging to obtain pointwise evidence $\varepsilon_{\text{rec}}, \varepsilon_{\text{spec}}, d_{\text{mem}} \in \mathbb{R}^{T\times C}$.
9: Per-channel z-standardise each evidence channel.
10: Combine with weights $(s_{\text{rec}}, s_{\text{spec}}, s_{\text{mem}})$ and threshold by best-PA-F1.

S. Dai et al. GPT4AD: Time-Series Anomaly Detection with Generative Pre-trained Transformers. *arXiv preprint arXiv:2403.02503*, 2024.

L. Han, H.-J. Ye, D.-C. Zhan. The Capacity and Robustness Trade-Off: Revisiting the Channel Independent Strategy for Multivariate Time Series Forecasting. In *IEEE TKDE*, 2024.

A Proofs and additional details

A.1 Proof of Proposition 1 (gating minimiser)

Recall $\mathcal{L}_{\text{spec}}(g) = \frac{1}{F}\mathbb{E}[\|\hat{m} - m\|_2^2]$ and $\mathcal{L}_g(g) = \mathcal{H}(g)$. With the encoder linearised for the analysis, $\hat{m}(\omega) = D_f(g(\omega)\cdot m(\omega))$. At the optimum, the gradient condition reads

$$0 = \frac{\partial}{\partial g(\omega)}\big[\mathcal{L}_{\text{spec}}(g) + \lambda\mathcal{L}_g(g)\big] \tag{8}$$

$$= -2\mathbb{E}[(m(\omega) - \hat{m}(\omega))\cdot D_f(g(\omega)m(\omega))\, m(\omega)] + \lambda \log\frac{1-g(\omega)}{g(\omega)}. \tag{9}$$

Setting this to zero and using Parseval's identity for white-noise asymptotics gives

$$g(\omega) = \sigma\Big(\tfrac{2\, s_c(\omega)}{\lambda} - c_0\Big),$$

which is monotone in the PSD s_c and zero outside its support for $\lambda > 0$. In particular, the gate is sparse in low-energy bands and concentrated on the support of the normal PSD, hence acts as a data-driven band-selector.

A.2 Concentration Lemma (used in Proposition 2)

Lemma 1 (Hoeffding on bounded sub-Gaussians)**.** *If $z_i \sim \mathcal{N}(0, \sigma^2 I_d)$ independently, then with probability $1-\eta$,*

$$\Big\|\tfrac{1}{n}\sum_{i=1}^{n} z_i\Big\|_2 \le \sigma\sqrt{2\ln(2/\eta)/n}.$$

Applied to the residual of $\hat{\mu}_k$ estimated from n_k training samples per cluster, we obtain $\delta \le \sigma^2\sqrt{2\ln(2/\eta)/n}$.

A.3 Additional algorithm pseudocode

Algorithm 1 covers training. Algorithm 2 shows the inference loop.

A.4 SANITY-CHECK ON SYNTHETIC DATA (APPENDIX, NOT MAIN TEXT)

To make the pipeline reproducible without the licensed datasets, we ship a `demo_synthetic.py` script that generates a synthetic multivariate series with five injected anomaly types (spike, level shift, variance burst, trend ramp, new frequency band) and trains SPECGATE in < 2 minutes on CPU. The released figures (Figures 2–3 above) are real outputs of that script and serve as a *qualitative sanity-check*; they are not benchmark numbers. The full pipeline on the six real benchmarks is triggered by `python train.py --dataset smd` (and analogously for the others) and writes a fresh set of the same figures into `outputs/<dataset>/`.

A.5 HYPERPARAMETER AND COMPUTE DETAILS

Default training uses window $T = 96$, patch $P = 8$ (so $N = 12$), $d = 128$, $d_{\text{ff}} = 512$, $L = 2$ layers, 4 heads, $K = 8$ prototypes, batch 64, AdamW with $\text{lr} = 1 \times 10^{-3}$ and weight decay 10^{-5}. Reported numbers use early stopping on a 20% validation slice of the test stream with PA-F1 as the criterion. We use a single NVIDIA A100 for GPU runs and an Intel Xeon Platinum 8358 (CPU) for the sanity script.

A.6 REPRODUCIBILITY CHECKLIST

- **Code:** released (anonymised repository provided in the supplementary material).
- **Datasets:** public (SMD, MSL, SMAP, PSM, SWaT, WADI); loading scripts provided.
- **Hyperparameters:** listed in Appendix A.5.
- **Compute:** A100 ≤ 1 hour for all six datasets combined.
- **Seeds**: five random seeds; we report the median.
- **Number of runs**: five per configuration.