WHEN SEEING BECOMES SAYING: NONMONOTONIC ANSWER DEPENDENCE IN VISUAL CHAIN-OF-THOUGHT

Anonymous authors
Paper under double-blind review

ABSTRACT

A numerical value can continue to influence a vision-language model after its written positions have been blocked. In visual chain-of-thought, separate and joint masks test answer dependence, while numerical substitutions and state transfer trace the value that remains influential. Individual masks miss joint dependencies on 51 of 119 Qwen and 73 of 119 InternVL TabMWP traces under blank-image continuation. Enlarging a mask can also restore an answer, with complete-answer controls showing how recovery changes across intervention operators. Replacing the source value while blocking all digit positions tests which number still reaches the answer. Across 800 controlled scenes, nonnumeric-state transfer favors the used replacement over its unused alternative by 3.56 points for Qwen and 0.94 for InternVL. Access to a written number and the influence of its value therefore require different tests. These findings motivate Gate, which chooses between retaining CoT computation and answering afresh. Gate improves over voting by 1.57 points across development benchmarks. On 600 new ChartQA images, frozen Gate reaches 85.00%, matching candidate scoring and improving over voting by 1.67 points.

1 INTRODUCTION

Chain-of-thought (CoT) records a vision-language model's visual observations and subsequent calculations. A misreading can enter those calculations and persist in the answer (Uppaal et al., 2026). CoT's gains on mathematical reasoning contrast with losses in counting and grounding (Jin et al., 2026). In Figure 1, text-only calls reproduce both a correct calculation and an incorrect reading from their traces. The trace can thus sustain later computation without seeing the image again.

Editing intermediate steps and values can change a model's subsequent computation (Lanham et al., 2023; Zhu et al., 2025). By the time a model answers, a written number may have influenced later states. Blocking its digit positions can therefore leave its influence intact. We examine this ambiguity within a fixed visual CoT by combining separate and joint masks with paired numerical substitutions and state transfer. Joint masks reveal dependencies concealed by individual restrictions, while substitutions track the numerical content transmitted through the remaining states.

Our experiments reveal dependencies that individual masks miss. On TabMWP, an answer can survive either of two numerical masks but change under their union. This occurs under both hard masking and value zeroing, including with the original image visible. On DVQA, enlarging a mask can instead restore the original answer, with recovery frequency and case identity changing across operators.

The identity of the transmitted value can be tested directly. In a DVQA example, replacing the source value 8 with 3 makes the answer follow 3 even with all digit positions blocked. Transferring the edited run's nonnumeric states produces the same change while preserving the original text. An 800-scene study extends this transfer result beyond selected recoveries.

These findings expose the trade-off between retaining a computation and carrying forward a mistaken observation. Gate turns this trade-off into an answer-selection strategy, using agreement and

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: **The same model, two outcomes of CoT.** In actual Qwen3-VL-8B responses, the generated CoT correctly adds the chart values for the two labeled years in (a) but contains a visual misreading in (b). A new text-only call receives the CoT and reproduces its answer in both cases.

disagreement among candidates to choose between the CoT result and a fresh Direct answer from the image. Its gains over voting persist in a frozen evaluation on new images.

Our contributions are two diagnostic findings and their application to selective reuse.

- We identify joint dependence and nonmonotonic recovery within a fixed visual CoT. Separate masks can miss a dependency revealed by their union, while enlarging a mask can restore an answer. Complete-answer controls compare both patterns under hard masking and value zeroing.
- Numerical substitutions and nonnumeric-state transfer identify which value can reach the answer after its digit positions are blocked. Controlled scenes and natural-error traces connect this test to answer retention and correctness.
- We develop Gate to choose between retained CoT computation and a fresh visual answer, and evaluate its decisions across five models and five numerical benchmarks and on new images with frozen selectors.

2 Related Work

Visual reasoning and perception. Multimodal-CoT uses image and text inputs to generate a rationale, then combines it with those inputs to infer an answer (Zhang et al., 2024). Visual-faithfulness studies check whether perception statements agree with the image and regenerate unfaithful steps (Uppaal et al., 2026). Our experiments follow the influence of a numerical value after its written positions become inaccessible.

Information flow and trace interventions. Zhu et al. (2025) show that intermediate results can be stored in latent form and that changing CoT values alters subsequent computation. Salazar et al.

(2026) trace image-direct and text-mediated pathways, including fallback after ablation. We combine individual and joint restrictions within a fixed visual CoT, then track substituted values through nonnumeric states while digit access remains blocked. These tests distinguish dependence on accessible positions from the numerical identity transmitted through the remaining states. Related studies examine direct image access (Osaka et al., 2026) and influences omitted from CoT (Turpin et al., 2023) or exposed by trace editing (Lanham et al., 2023). Fresh computation can reduce prior-CoT shortcuts (Fan et al., 2026), while the Hydra effect concerns cross-layer compensation in factual recall (McGrath et al., 2023).

Answer selection. Self-consistency aggregates sampled reasoning paths (Wang et al., 2023). ReAct uses answer agreement to switch from CoT self-consistency to interaction with external evidence (Yao et al., 2023). Question and response cues can indicate where CoT helps (Sprague et al., 2025), and FrugalGPT scores generated answers before accepting them or querying another model (Chen et al., 2024). Gate estimates the correctness difference between a CoT vote and a fresh Direct response from the same VLM. We compare this gain objective with fixed fallback, agreement-based switching and candidate scoring on the same responses.

3 Tracing answer dependence

Direct prompting asks for the final answer, whereas CoT prompting asks for reasoning before the answer. We call the answer in the original CoT run the *source answer*. Retention measures reproduction of this answer, and accuracy measures agreement with ground truth.

3.1 Continuing the same reasoning trace

We continue from the recorded CoT's original tokens, retaining the opening answer-tag prefix but excluding the answer value and sign. We encode the prefix afresh with either the original image or a same-size blank image. Blank images test what the trace sustains without visual evidence.

Hard masking blocks selected trace keys at every language layer during answer generation. Intervention begins with the first query overlapping the opening answer tag. Earlier states are unchanged across masks within each image condition. Value zeroing retains the current call's keys and attention normalization but sets the selected value vectors to zero. Both operations remain active throughout the answer continuation.

Text-only replay supplies the question and CoT to a fresh call without an image. It removes the final tagged answer but retains earlier occurrences of its value, as illustrated in Figure 1.

3.2 Testing individual and joint access

We divide digit-bearing positions into *Answer*, containing occurrences of the source-answer magnitude, and *Other*, containing the remaining numbers. *All* combines these groups, and *None* leaves the trace unmasked. Magnitudes are matched after formatting normalization. Grouping requires two nonempty groups and unambiguous token mappings.

Retention requires normal termination and exact normalized equality to the source answer, including its sign. An invalid or truncated response counts as a failure to retain. Joint dependence occurs when each individual mask preserves the native answer but their union changes it. Recovery occurs when Answer changes the native answer, Other preserves it, and All restores it, violating monotone retention.

We compare the original grouping with three random partitions matched for size within four position bins. Whole-value controls additionally preserve complete numbers, their repeated occurrences and digit widths.

3.3 Following a number beyond its written positions

While blocking every digit position, we replace an integer-valued source-answer magnitude with an absent integer of the same width and recompute the prefix. Every Answer occurrence is replaced. Tokenizer checks preserve unedited tokens, prefix length and the position map.

Table 1: **Answering strategies across five models and five benchmarks.** Accuracy (%) at the stated budgets. Vote and Gate share three CoTs. Bold marks the best strategy per model and benchmark, including ties. Gate uses grouped evaluation, except frozen-selector estimates for DVQA/TabMWP with both 4B models and CountBench/MathVista with Qwen2.5.

Benchmark	Strategy	**Qwen3-VL**		**InternVL3.5**		**Qwen2.5-VL**
		8B	4B	8B	4B	7B
DVQA	Direct	**94.50**	**93.88**	78.88	**92.38**	**95.88**
	CoT	91.00	86.88	91.25	86.88	88.75
	Vote	91.25	88.50	91.50	89.75	91.13
	Gate	92.63	91.50	**91.63**	92.13	94.88
CountBench	Direct	78.78	76.33	67.55	72.24	**77.76**
	CoT	75.51	74.29	69.39	68.78	67.96
	Vote	78.16	76.12	71.63	72.24	68.98
	Gate	**81.43**	**78.78**	**72.24**	**73.47**	**77.76**
ChartQA	Direct	68.13	64.38	74.63	72.13	74.00
	CoT	80.75	78.13	84.38	67.13	79.88
	Vote	82.13	81.00	85.75	73.38	81.50
	Gate	**84.25**	**82.50**	**86.38**	**76.00**	**82.63**
TabMWP	Direct	78.00	83.38	84.88	80.13	72.88
	CoT	98.50	97.00	96.25	83.50	92.88
	Vote	**99.13**	97.75	96.63	87.63	**93.38**
	Gate	**99.13**	**98.50**	**97.25**	**91.25**	92.75
MathVista	Direct	59.83	57.42	60.48	55.46	62.45
	CoT	67.03	64.19	67.25	60.48	62.66
	Vote	69.43	65.94	67.47	63.97	63.02
	Gate	**71.62**	**69.00**	**68.12**	**66.81**	**64.55**

We transfer the edited run's attention value vectors at nonnumeric positions into the unedited recipient trace, jointly across language layers. Transfer starts at the masking boundary and covers generated trace positions before the opening answer tag, excluding prompt, image, tag and answer tokens. The current call's queries, keys and mask are preserved, while subsequent answer states evolve normally.

Each source has two replacements tested in separate runs. We measure how often the output magnitude follows the used replacement versus its unused alternative, averaging runs within image. Under blank-image transfer, neither replacement appears in the recipient text. Invalid or truncated answers are nonmatches. Self-transfer supplies the original states, and whole-trace masking blocks every trace position.

3.4 Separating image dependence from accuracy

We cross original and blank images with unmasked continuation, numerical masking, an equal-count lexical mask and whole-trace masking. A larger accuracy gap between original and blank images indicates greater sensitivity to visual input. We also measure the absolute accuracy change with the original image present.

4 Evaluation

We evaluate 11 vision-language models across six families. The main comparison covers Qwen3-VL 8B and 4B (Bai et al., 2025a), InternVL3.5 8B and 4B (Wang et al., 2025), and Qwen2.5-VL-7B (Bai et al., 2025b). Their tasks span chart questions in DVQA and ChartQA (Kafle et al., 2018; Masry et al., 2022), mathematical reasoning in TabMWP and MathVista (Lu et al., 2023; 2024), and counting in CountBench (Paiss et al., 2023). The core interventions use the two 8B models. Additional evaluations cover other model families, categorical questions and grounding.

We generate tables and bar charts with random values and shuffled labels to reduce the risk of pretraining data contamination. The tasks cover reading, subtraction and two-step arithmetic. Exact text transcriptions separate computation from visual reading. A distinct set of 800 charts supports source interventions without selecting examples for answer recovery.

Numerical correctness uses 1% relative tolerance with a minimum absolute tolerance of 0.01. Invalid or truncated answers count as incorrect. Direct and CoT in Table 1 use greedy decoding with a limit of 512 new tokens, increased to 1,024 on MathVista. Vote and Gate share three CoTs at temperature 0.7. Fixed-trace interventions use greedy decoding and preserve the original total prefix-plus-continuation budget. The strategy comparison includes budget sensitivity.

Joint masking requires two nonempty numerical groups. Separable TabMWP traces additionally have a source-answer magnitude absent from the question and table. Value-transfer tests require two valid, same-width replacements. Complete-answer operator comparisons use the same fixed 32 images per task and model, retaining invalid answers and failures to preserve the source in the denominator.

For Gate, five outer folds hold out image identities or localization pairs jointly across models. Training folds alone determine standardization and ridge regularization. The benchmarks informed method development. Six public-task frozen-selector extensions cover the two 4B models on DVQA and TabMWP, and Qwen2.5 on CountBench and MathVista. They may reuse images seen under other models and are excluded from the 19-pair grouped average. A separate evaluation freezes all selectors before generating responses on 600 new ChartQA images. Paired image intervals condition on the fitted selectors.

5 Analysis of visual chain-of-thought

The benefit of CoT varies across tasks (Table 1). Qwen3-VL-8B improves from 78.00% to 98.50% on TabMWP but drops from 78.78% to 75.51% on CountBench. On DVQA, CoT lowers Qwen's accuracy while improving InternVL's. These differences also depend on generation budget. Raising InternVL's Direct limit to 8,192 tokens lifts TabMWP accuracy from 84.88% to 95.38%, compared with CoT's 96.25%. At the shorter limit, 85 Direct responses truncate.

CoT's computational benefit remains when exact table values are supplied as text. Qwen3-VL and InternVL3.5 at both sizes reach 100% on two-step arithmetic, compared with 1.7–6.7% for the three valid Direct controls. This contrast leads us to examine how the numbers recorded in a CoT influence its final answer.

5.1 Dependencies that individual masks miss

Two groups of numbers can jointly affect an answer even when masking either group alone leaves it unchanged. On the 119 separable TabMWP images with blank-image continuation, 51 Qwen answers and 73 InternVL answers survive either individual mask but change under their union (Table 2a). The same pattern can affect correctness when the original image remains visible. Ten Qwen cases and seven InternVL cases are correct under each individual mask and wrong under the combined mask.

Joint dependence is concentrated in traces that compute a value absent from the input. Among the other 53 applicable TabMWP images, where at least one model's source-answer magnitude overlaps the input, it occurs on two Qwen and three InternVL traces.

Masking additional digits can also restore an answer changed by a smaller mask, violating monotonic answer retention. In Figure 2a, blocking the digits matching the source answer changes the response from 8 to 2. Blocking the remaining digits restores 8. This recovery occurs on 29 of 72 DVQA images for Qwen and 15 of 72 for InternVL under blank-image readout, restoring correctness in 28 and 13 cases. Most recoveries occur on extrema questions, which account for 64 of the 72 eligible images. Real-image recovery occurs in two Qwen TabMWP cases and one DVQA case per model.



Figure 2: **Access to written numbers and their influence on an answer.** (a) Enlarging a mask restores the original answer. (b) With digit access blocked, transferring the edited run's nonnumeric value vectors changes the answer while preserving recipient text. Panels (a,b) use the same Qwen/DVQA trace with a blank image. (c) Fixed-CoT accuracy before and after blocking all digit positions, averaged across models within image. Shading marks the original/blank-image gap. ChartQA and CountBench are descriptive extensions.

5.2 How the access operation changes the outcome

We compare complete answers under hard masking and key-preserving value zeroing on the same 32 images per task and model (Table 3). Joint dependence occurs under both operations on TabMWP. With the original image present, its count changes from 5 to 8 for Qwen and from 2 to 3 for InternVL. Both models thus show joint dependence with the original image visible and with keys retained.

Recovery is more sensitive to the operator. On blank-image DVQA, its count falls from 12 to 3 for Qwen and from 5 to 2 for InternVL under value zeroing. Only three of Qwen's original recovery cases and one of InternVL's remain recoveries. The operators differ both in recovery frequency and in which cases recover.

Numerical grouping changes both the roles of the masked values and their token organization. We measure the retention interaction by summing individual-mask retention and subtracting native and joint-mask retention. Against token partitions matched for size and position, the retention interaction is larger on separable TabMWP (+10.64 points), smaller on DVQA (-25.46), and close to zero on wider TabMWP (+0.97). These random partitions can split a multi-digit number or separate its repeated occurrences. Requiring complete numbers and all their copies to stay together leaves exact alternatives on only 3–4 images per model–task cohort. The resulting differences vary in direction and all descriptive intervals include zero.

Table 2: **Answer retention and value transmission with a fixed CoT.** Continuations use blank images. Panel (a) measures retention under individual and combined masks. Panel (b) compares following of the replacement used in a run with its unused paired control. DVQA transfer uses selected recoveries, while the synthetic study includes all source-eligible traces.

(a) More masking can remove or restore the original answer.
Original-answer retention (%).

	Qwen3-VL-8B					InternVL3.5-8B				
Digits blocked	n	None	Answer	Other	All	n	None	Answer	Other	All
TabMWP (separable)	119	100.0	97.5	100.0	54.6	119	100.0	99.2	100.0	37.8
DVQA (separable)	72	100.0	52.8	100.0	91.7	72	97.2	55.6	97.2	68.1
TabMWP (wider)	172	100.0	88.4	100.0	62.2	172	100.0	87.8	100.0	47.1
ChartQA (applicable)	126	96.8	69.0	98.4	35.7	126	98.4	64.3	99.2	36.5
Synthetic extreme reading	793	100.0	7.6	100.0	14.9	59	100.0	0.0	100.0	3.4

(b) Blocked digits influence answers through nonnumeric states.
Replacement-value following (%); all digit keys blocked.

	Qwen3-VL-8B		InternVL3.5-8B	
Intervention	Used value	Unused value	Used value	Unused value
DVQA: selected recovery cases (Qwen $n = 23$; InternVL $n = 14$)				
Edit source digits	37.0	0.0	32.1	0.0
Transfer nonnumeric states	32.6	0.0	35.7	0.0
Synthetic: all source-eligible scenes (Qwen $n = 800$; InternVL $n = 795$)				
Edit source digits	6.4	1.1	1.7	0.4
Transfer nonnumeric states	4.8	1.3	1.4	0.4

Table 3: **Complete-answer comparison across access operators and image conditions.** Each entry gives hard-mask → value-zero counts on the same 32 images per model and task.

Model	Task	Joint dependence		Recovery	
		Original	Blank	Original	Blank
Qwen3-VL-8B	TabMWP	$5 \to 8$	$16 \to 15$	$1 \to 0$	$0 \to 0$
Qwen3-VL-8B	DVQA	$1 \to 0$	$1 \to 3$	$0 \to 0$	$12 \to 3$
InternVL3.5-8B	TabMWP	$2 \to 3$	$19 \to 21$	$0 \to 0$	$0 \to 1$
InternVL3.5-8B	DVQA	$0 \to 1$	$2 \to 3$	$1 \to 0$	$5 \to 2$

5.3 Following the source value

Numerical substitutions let us follow the value itself after its digit positions are blocked. In the blank-image example in Figure 2, all digit positions remain blocked, yet changing the source value from 8 to 3 makes the answer follow 3. Transferring the edited run's values at nonnumeric positions produces the same change while preserving the recipient's original text. In the 800-scene study, which does not select for recovery, nonnumeric transfer favors the used replacement over its unused alternative by 3.56 points for Qwen and 0.94 for InternVL. The edited value can therefore influence the answer through nonnumeric states even when all digit positions are blocked.

The 23 Qwen and 14 InternVL eligible DVQA recoveries produce used-value matches and no unused-value matches under both source editing and nonnumeric transfer (Table 2b). Self-transfer preserves every unpatched answer. In the synthetic study, all four prespecified intervals exclude zero at the adjusted 98.75% level. Transfer uses all 800 Qwen and 795 InternVL source-eligible traces.



Figure 3: **Gate retains computation or answers afresh.** (a) Decision rule. (b) Gate preserves the correct CoT sum 489 over Direct 695. (c) Gate selects correct Direct 4 over Vote 6 using a predictor fitted without this image group.

Competing trace values also influence the changed answer. It matches another written magnitude in 28 of 29 Qwen recoveries and all 15 InternVL recoveries. On 30 and 25 follow-up traces, blocking those competing digits restores the source more often than an equally sized control, by 50 and 28 points. The adjusted test supports the Qwen contrast. Substituted values transferred at accessible competing positions also change which number is returned.

On 400 eligible Qwen ChartQA error traces with the original image present, source editing yields 2.13 points [0.88,3.63] of net replacement following and nonnumeric transfer yields 0.38 [0.00,0.88], using 97.5% intervals. Positive effects occur on 13 and three images. Numerical masking corrects 36 answers, while whole-trace masking corrects 87. Whole-trace masking repairs many errors for which the paired donor test detects no exact replacement following.

5.4 More image dependence does not ensure a better answer

An intervention can widen the original/blank-image accuracy gap by damaging performance without the image more severely. On TabMWP, unmasked accuracy is 97.40% in both conditions. Numerical masking reduces it to 82.81% with the original image and 54.17% with the blank image (Figure 2c). The larger gap accompanies a 14.58-point loss in real-image accuracy. The gap measures sensitivity to visual input, while accuracy determines whether a response is useful. This motivates choosing between an existing CoT answer and a fresh answer from the image.

6 Gate for selective answer reuse

CoT can preserve a useful calculation or carry an error into the final answer. Gate uses the candidate responses to decide when to keep that computation and when to answer afresh from the image.

Vote and Gate share three CoTs sampled at temperature 0.7 (Wang et al., 2023). Gate retains a valid unanimous answer and otherwise requests Direct from the original image and question. A ridge regressor predicts Direct-minus-Vote correctness from agreement, numerical dispersion, response lengths, lexical cues and task/model indicators. A positive prediction selects Direct, and a nonpositive prediction keeps Vote. Correctness labels supervise the selector while the VLM remains fixed. Invalid Direct preserves Vote, and valid Direct replaces invalid Vote.

Table 4: **Gate components, controls and frozen evaluation.** Accuracy averages 19 public model–task pairs (grouped) or two models on 600 new ChartQA images (frozen). Policies share candidates. Paired intervals are 95% for grouped and 97.5% for frozen comparisons.

	Accuracy (%)	Gate − row [interval], pp
(a) Task/model indicator ablation, grouped evaluation		
Gate	82.18	—
Without task/model indicators	81.96	+0.22 [0.03,0.41]
(b) Selector comparisons, grouped evaluation		
Vote	80.62	+1.57 [1.15,1.98]
Fixed fallback	80.64	+1.54 [1.19,1.89]
Agreement threshold	81.71	+0.47 [0.20,0.76]
Matched answer scorer	82.08	+0.10 [−0.01,0.21]
(c) Frozen selectors on new ChartQA images		
Gate	85.00	—
Vote	83.33	+1.67 [0.83,2.58]
Fixed fallback	84.42	+0.58 [−0.67,1.83]
Matched answer scorer	85.00	0.00 [0.00,0.00]

Figure 3 shows both choices. Gate protects the unanimous TabMWP calculation and replaces the incorrect MathVista vote. For the latter, the saved outer-fold predictor assigns Direct a gain of +0.168.

Across the development benchmarks, Gate reaches 82.18%, improving over Vote by 1.57 points and fixed fallback by 1.54 points (Table 4). It retains 314 correct votes that fixed fallback would spoil, while forgoing 114 Direct corrections among 12,592 items. Removing task/model indicators leaves 81.96% accuracy. The response features retain most of the gain, with task/model indicators adding 0.22 points [0.03,0.41]. Holding out each target benchmark also retains gains over fixed fallback, although Gate trails Vote on held-out TabMWP, 96.25% versus 96.38%.

Matched scoring compares the same response features through a different fitting objective, also yielding a linear decision boundary. Gate is 0.10 points ahead in grouped evaluation, with an interval spanning zero. On frozen ChartQA, both reach 85.00% with identical correctness on all 1,200 model–image records. Gate gains 1.67 points over Vote and 0.58 over fixed fallback, combining a 2.00-point gain over fallback for Qwen and a 0.83-point loss for InternVL. Table 4 reports the paired intervals.

Staged Gate uses up to 1.212 times Vote's generated tokens, counting discarded Direct responses. Frozen evaluation collects the same four responses for every policy, isolating their selection decisions.

7 Discussion and conclusion

A numerical value can continue to influence a visual CoT answer after its written positions are blocked. Joint masks reveal dependencies missed by individual tests, while paired substitutions identify the value transmitted by remaining nonnumeric states. Complete-answer controls show how recovery changes with the access operation. Gate applies these findings to selective reuse, retaining CoT computation or adopting a fresh visual answer. On new images, this response-level choice improves over voting and matches candidate scoring.

Future work can trace individual values earlier in reasoning, following a number as it is read from the image, combined with other quantities and used in a calculation. Tracking transformed values, such as sums and differences, could reveal influences that exact replacement matching misses. These probes could also guide selective image rereading or correction of individual reasoning steps. Connecting numerical dependence to decisions during generation would extend selective reuse from choosing a final answer to deciding which parts of a computation to retain.

ETHICS STATEMENT

This study uses existing benchmark data and synthetic charts and tables to examine model behavior. The radiology subset is a diagnostic evaluation of prompting, not a clinical decision system or evidence of clinical safety. We report interface failures, failed predictions, and the limited populations on which each result is defined. Original benchmark attribution is retained; no identifying patient information is added to the examples.

REPRODUCIBILITY STATEMENT

Appendix A specifies the models, datasets, prompts and evaluation settings. Appendices B–E detail the interventions, controlled benchmarks and Gate procedure. The accompanying materials include synthetic-data generators, analysis code, recorded predictions and the fitted Gate selector. The source package also provides the 4,800 raw responses from the frozen ChartQA evaluation, with code to re-extract and score answers and replay the frozen selectors. A complete-answer control archive supplies saved responses and CPU replay for the access-operator and whole-value comparisons.

REFERENCES

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, Mei Li, Kaixin Li, Zicheng Lin, Junyang Lin, Xuejing Liu, Jiawei Liu, Chenglong Liu, Yang Liu, Dayiheng Liu, Shixuan Liu, Dunjie Lu, Ruilin Luo, Chenxu Lv, Rui Men, Lingchen Meng, Xuancheng Ren, Xingzhang Ren, Sibo Song, Yuchong Sun, Jun Tang, Jianhong Tu, Jianqiang Wan, Peng Wang, Pengfei Wang, Qiuyue Wang, Yuxuan Wang, Tianbao Xie, Yiheng Xu, Haiyang Xu, Jin Xu, Zhibo Yang, Mingkun Yang, Jianxin Yang, An Yang, Bowen Yu, Fei Zhang, Hang Zhang, Xi Zhang, Bo Zheng, Humen Zhong, Jingren Zhou, Fan Zhou, Jing Zhou, Yuanzhi Zhu, and Ke Zhu. Qwen3-VL Technical Report. *arXiv preprint*, 2025a. URL https://arxiv.org/abs/2511.21631.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-VL Technical Report. *arXiv preprint*, 2025b. URL https://arxiv.org/abs/2502.13923.

Lingjiao Chen, Matei Zaharia, and James Zou. FrugalGPT: How to use large language models while reducing cost and improving performance. *Transactions on Machine Learning Research*, 2024. URL https://openreview.net/forum?id=cSimKw5p6R.

Wenxiao Fan, Jingling Fu, Fang Li, Luohang Liu, Yu He, Lichen Ma, Zhiyang Yu, Weishan Bi, Junshi Huang, Yan Li, Gu Simiu, and Kan Li. Recompute or Reuse? Diagnosing and Mitigating Textual Shortcuts in VLM Self-Reflection. *arXiv preprint*, 2026. URL https://arxiv.org/abs/2608.01930v1.

Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoyu Wang, Xudong Lin, Dan Roth, Noah A. Smith, Wei-Chiu Ma, and Ranjay Krishna. BLINK: Multimodal Large Language Models Can See but Not Perceive. In *Computer Vision – ECCV 2024*, volume 15081 of *Lecture Notes in Computer Science*, pp. 148–166. Springer, 2025. doi: 10.1007/978-3-031-73337-6_9. URL https://doi.org/10.1007/978-3-031-73337-6_9.

Zhuoran Jin, Kejian Zhu, Hongbang Yuan, Yupu Hao, Pengfei Cao, Yubo Chen, Kang Liu, and Jun Zhao. Look Light, Think Heavy: What Multimodal Chain-of-Thought Reasoning Can and Cannot Do. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8567–8608. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.acl-long.387. URL https://doi.org/10.18653/v1/2026.acl-long.387.

Kushal Kafle, Brian Price, Scott Cohen, and Christopher Kanan. DVQA: Understanding Data Visualizations via Question Answering. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 5648–5656, 2018. URL https://openaccess.thecvf.com/content_cvpr_2018/html/Kafle_DVQA_Understanding_Data_CVPR_2018_paper.html.

Tamera Lanham, Anna Chen, Ansh Radhakrishnan, Benoit Steiner, Carson Denison, Danny Hernandez, Dustin Li, Esin Durmus, Evan Hubinger, Jackson Kernion, Kamilė Lukošiūtė, Karina Nguyen, Newton Cheng, Nicholas Joseph, Nicholas Schiefer, Oliver Rausch, Robin Larson, Sam McCandlish, Sandipan Kundu, Saurav Kadavath, Shannon Yang, Thomas Henighan, Timothy Maxwell, Timothy Telleen-Lawton, Tristan Hume, Zac Hatfield-Dodds, Jared Kaplan, Jan Brauner, Samuel R. Bowman, and Ethan Perez. Measuring Faithfulness in Chain-of-Thought Reasoning. *arXiv preprint*, 2023. URL https://arxiv.org/abs/2307.13702.

Jason J. Lau, Soumya Gayen, Asma Ben Abacha, and Dina Demner-Fushman. A dataset of clinically generated visual questions and answers about radiology images. *Scientific Data*, 5:180251, 2018. doi: 10.1038/sdata.2018.251. URL https://doi.org/10.1038/sdata.2018.251.

Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. ScreenSpot-Pro: GUI Grounding for Professional High-Resolution Computer Use. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pp. 8778–8786. Association for Computing Machinery, 2025. doi: 10.1145/3746027.3755688. URL https://doi.org/10.1145/3746027.3755688.

Pan Lu, Liang Qiu, Kai-Wei Chang, Ying Nian Wu, Song-Chun Zhu, Tanmay Rajpurohit, Peter Clark, and Ashwin Kalyan. Dynamic Prompt Learning via Policy Gradient for Semi-structured Mathematical Reasoning. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=DHyHRBwJUTN.

Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. MathVista: Evaluating Mathematical Reasoning of Foundation Models in Visual Contexts. In *International Conference on Learning Representations*, pp. 23439–23554, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/hash/663bce02a0050c4a11f1eb8a7f1429d3-Abstract-Conference.html.

Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. ChartQA: A Benchmark for Question Answering about Charts with Visual and Logical Reasoning. In *Findings of the Association for Computational Linguistics: ACL 2022*, pp. 2263–2279. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.findings-acl.177. URL https://aclanthology.org/2022.findings-acl.177/.

Thomas McGrath, Matthew Rahtz, Janos Kramar, Vladimir Mikulik, and Shane Legg. The hydra effect: Emergent self-repair in language model computations, 2023. URL https://arxiv.org/abs/2307.15771.

Hiroto Osaka, Shohei Taniguchi, Gouki Minegishi, Kai Yamashita, Masahiro Suzuki, and Yutaka Matsuo. Visual access boundaries in vision-language model reasoning, 2026. URL https://arxiv.org/abs/2607.12815v2.

Roni Paiss, Ariel Ephrat, Omer Tov, Shiran Zada, Inbar Mosseri, Michal Irani, and Tali Dekel. Teaching CLIP to Count to Ten. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 3170–3180, 2023. URL https://openaccess.thecvf.com/content/ICCV2023/html/Paiss_Teaching_CLIP_to_Count_to_Ten_ICCV_2023_paper.html.

Israfel Salazar, Stella Frank, Dan Oneata, Desmond Elliott, and Constanza Fierro. Pathways of visual information flow in vision-language models, 2026. URL https://arxiv.org/abs/2607.03358v1.

Zayne Sprague, Fangcong Yin, Juan Diego Rodriguez, Dongwei Jiang, Manya Wadhwa, Prasann Singhal, Xinyu Zhao, Xi Ye, Kyle Mahowald, and Greg Durrett.

To CoT or not to CoT? chain-of-thought helps mainly on math and symbolic reasoning. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/hash/ead542f13a38179d1b55b88610f959a1-Abstract-Conference.html.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language Models Don't Always Say What They Think: Unfaithful Explanations in Chain-of-Thought Prompting. In *Advances in Neural Information Processing Systems*, volume 36, pp. 74952–74965. Curran Associates, Inc., 2023. doi: 10.52202/075280-3275. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/ed3fea9033a80fea1376299fa7863f4a-Abstract-Conference.html.

Rheeya Uppaal, Phu Mon Htut, Min Bai, Nikolaos Pappas, Zheng Qi, and Sandesh Swamy. Journey Before Destination: On the importance of Visual Faithfulness in Slow Thinking. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 4147–4168. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.eacl-long.194. URL https://doi.org/10.18653/v1/2026.eacl-long.194.

Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, Zhaokai Wang, Zhe Chen, Hongjie Zhang, Ganlin Yang, Haomin Wang, Qi Wei, Jinhui Yin, Wenhao Li, Erfei Cui, Guanzhou Chen, Zichen Ding, Changyao Tian, Zhenyu Wu, Jingjing Xie, Zehao Li, Bowen Yang, Yuchen Duan, Xuehui Wang, Zhi Hou, Haoran Hao, Tianyi Zhang, Songze Li, Xiangyu Zhao, Haodong Duan, Nianchen Deng, Bin Fu, Yinan He, Yi Wang, Conghui He, Botian Shi, Junjun He, Yingtong Xiong, Han Lv, Lijun Wu, Wenqi Shao, Kaipeng Zhang, Huipeng Deng, Biqing Qi, Jiaye Ge, Qipeng Guo, Wenwei Zhang, Songyang Zhang, Maosong Cao, Junyao Lin, Kexian Tang, Jianfei Gao, Haian Huang, Yuzhe Gu, Chengqi Lyu, Huanze Tang, Rui Wang, Haijun Lv, Wanli Ouyang, Limin Wang, Min Dou, Xizhou Zhu, Tong Lu, Dahua Lin, Jifeng Dai, Weijie Su, Bowen Zhou, Kai Chen, Yu Qiao, Wenhai Wang, and Gen Luo. InternVL3.5: Advancing Open-Source Multimodal Models in Versatility, Reasoning, and Efficiency. *arXiv preprint*, 2025. URL https://arxiv.org/abs/2508.18265.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-Consistency Improves Chain of Thought Reasoning in Language Models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=1PL1NIMMrw.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing Reasoning and Acting in Language Models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=WE_vluYUL-X.

Zhuosheng Zhang, Aston Zhang, Mu Li, Hai Zhao, George Karypis, and Alex Smola. Multimodal Chain-of-Thought Reasoning in Language Models. *Transactions on Machine Learning Research*, 2024. URL https://openreview.net/forum?id=y1pPWFVfvR.

Fangwei Zhu, Peiyi Wang, and Zhifang Sui. Chain-of-Thought Tokens are Computer Program Variables, 2025. URL https://arxiv.org/abs/2505.04955v1.

AI USE STATEMENT

Generative AI assisted literature search, hypothesis refinement, experiment design, method and synthetic-data generator implementation, data processing and interpretation, translation, and writing. Synthetic images and labels were produced by the specified deterministic generators. The authors are responsible for the final content.

A EVALUATION PROTOCOLS AND ADDITIONAL RESULTS

This appendix gives the evaluation settings, complete diagnostic contrasts, controlled-study populations, and Gate analyses. Section F presents eleven additional benchmark examples with original inputs and recorded outputs.

Table 5: **Main study populations and measured quantities.** The studies address different questions; their sample counts and endpoints are reported separately.

Question	Population	Condition and endpoint
Can individual masks miss dependence?	TabMWP: 192 planned images, 172 jointly applicable, 119 input-value-separable. DVQA: 192 planned, 72 shared, including 64 extrema questions.	Fixed CoT with original or blank images. Original-answer retention under separate and joint masks; correctness scored separately.
Can blocked source values still influence answers?	Selected DVQA recoveries: 23 Qwen and 14 InternVL cases. In 800 controlled scenes, source eligibility is 800/795 and grouping eligibility 793/59 (Qwen/InternVL).	Blank-image donor tests with digit access blocked. Used-minus-unused replacement following; the synthetic population includes all source-eligible traces.
Does source influence persist in natural errors?	400 eligible Qwen3-VL-8B error traces from a new pool of 6,000 ChartQA train images.	Original image retained. Source-identity following, original-answer retention and accuracy under fixed-trace interventions.
Does a larger image gap mean better answers?	100 planned images per task. Paired comparisons use 99 DVQA and 96 TabMWP images shared by both models.	Original/blank images crossed with numerical, lexical and whole-trace masks. Image-gap interaction and real-image accuracy change.
Does learned selection improve answers?	19 public model–task pairs, comprising 12,592 development records.	Five folds grouped by image, using shared candidates. Macro accuracy and paired policy differences.
Does a frozen selector transfer to new images?	600 shared ChartQA validation images, evaluated with both 8B models: 1,200 model–image pairs.	Selectors frozen before generation; shared candidates. Two-model mean accuracy and paired policy differences.

Table 6: **Diagnostic questions, populations and endpoints.** Paired counts are Qwen3-VL-8B/InternVL3.5-8B; net following is used minus unused replacement following.

Diagnostic question	Population and image condition	Measured endpoint
Separate or joint dependence?	TabMWP: 192 planned $\rightarrow$ 172 applicable $\rightarrow$ 119 separable; DVQA: 192 $\rightarrow$ 72 shared (64 extrema). Original/blank.	Answer retention; correctness.
Transfer in selected recoveries?	DVQA recovery-selected: 23/14. Blank.	Net replacement following.
Transfer without recovery selection?	800 synthetic scenes: all source-eligible 800/795; grouping 793/59. Blank.	Net replacement following.
Source influence in natural errors?	ChartQA: 400 eligible Qwen error traces from 6,000 images. Original.	Donor following; retention; accuracy.
Image gap or accuracy gain?	DVQA 99 and TabMWP 96 shared images; 100 planned per task. Original/blank.	Image interaction; real-image accuracy change.

Models and runtime. Q8 and Q4 denote Qwen3-VL-8B-Instruct and Qwen3-VL-4B-Instruct; IV8 and IV4 denote InternVL3.5-8B-HF and InternVL3.5-4B-HF. GLM denotes GLM-4.6V-Flash. Core interventions use full BF16 Q8/IV8 checkpoints with PyTorch 2.5.1, Transformers 4.57.1,

SDPA MATH and greedy decoding. Each image condition receives a fresh prefill. Available checkpoint revisions, actual rendered prompts and processor/tokenizer configuration hashes are indexed in the accompanying interface inventory.

Instructions and generation. The core numerical interface uses the system message `You are a careful visual assistant.` Direct and CoT place the image before the following user text. Braces below denote inserted content, not literal prompt characters.

Direct

```
{question}
Answer with only the number.  Final answer exactly
<answer>VALUE</answer>.  Only provide the final answer.
```

CoT

```
{question}
Briefly explain how you read the figure, then give the final
answer exactly <answer>VALUE</answer>.
```

Text-only replay

```
{question}
Here is how you read the figure earlier:
---
{pre-answer trace}
---
Using only the text above (no image), give the final answer
exactly <answer>VALUE</answer>.
```

Replay uses the same system message and a text-only user message. Its trace excludes the final tagged answer but preserves earlier occurrences of the answer value. Fixed-prefix continuation instead retains the original CoT prompt and source token prefix; it does not use the replay prompt. The supplied interface inventory preserves actual core-model rendered strings and model-specific wrappers.

Vote and Gate share three independently seeded CoTs sampled at temperature 0.7. For the main checkpoints, numerical QA and arithmetic use top-$p = 1$; the original localization samples use top-$p = 0.8$ and top-$k = 20$. Repetition penalty is 1. Direct fallback uses a fresh call on the original image/question without sampled traces; offline evaluation selects its saved output.

Blank images. Fixed-prefix masks and state-transfer studies replace every source-image pixel with RGB $(127, 127, 127)$ at the original width and height, then apply the same processor as for the real image. The core Qwen loader fixes both image-pixel bounds to 512^2; InternVL uses its processor defaults. Image geometry and token positions are checked across real and blank conditions. Each condition recomputes its own prefix states, while the generated source trace remains fixed.

Generation budgets. These are experimental stopping limits, not model context-window limits. Fixed-trace interventions allow 512 tokens in total for the forced CoT prefix and continuation. For the five main checkpoints, numerical QA uses 512 generated tokens per response, or 1,024 on MathVista; synthetic arithmetic uses 512. ScreenSpot-Pro uses 32,768. The original localization protocol sets 32,768, whereas the Qwen2.5 extension uses 512. GLM numerical QA and native-thinking runs use 8,192; its BLINK, corrected VQA-RAD and arithmetic runs use 512, and localization uses 32,768. The additional Qwen3-VL-2B, Molmo2, Kimi and Idefics3 numerical runs use 512 (1,024 on MathVista); Qwen3.5 thinking-off uses 512. Per-run settings accompany the supplementary records.

An 8,192-token cap leaves DVQA Direct/CoT unchanged. TabMWP Q8 changes from 78.00/98.50 to 78.00/98.75; IV8 from 84.88/96.25 to 95.38/96.25, with 85 short-cap Direct truncations. Budget failures therefore explain part of the CoT gain; longer-cap Vote/CF is unmeasured.

Populations. Confirmation uses 800 previously unexposed images per task from DVQA `val_hard` and TabMWP `problems_test.json`, excluding a 16-image pilot. Project exposure,

not pretraining exposure, is checked using encoded/decoded image and question identities. Earlier survey/replay cohorts contain 400 DVQA questions over 170 training-export image clusters, 800 numerical ChartQA test questions, 200 TabMWP training-export questions, 458 numerical MathVista testmini items and 490 CountBench images with caption numerals removed. VQA-RAD has 200 yes/no items (49.5% positive); its corrected prompt was remeasured, not rescored. Cohorts remain separate.

Scoring and uncertainty. Formal numerical confirmation and fixed-trace diagnostics require a finite legal value, normal EOS and tolerance $\max(0.01, 0.01|y|)$ against any accepted label. Normalization strips commas, currency and percent marks without percent rescaling; source persistence requires exact normalized equality. VQA-RAD scores extracted yes/no labels without the numerical EOS filter. BLINK scores exact options in the original order; its announced-option fallback does not repeat the original branch's EOS check. ScreenSpot scores accepted points inside target boxes; synthetic localization uses its single-axis hit rule. Responses that fail their task's acceptance rules count as incorrect. The exported interface guide identifies the extraction, termination and acceptance branches used by these studies. Paired intervals resample image clusters and average the two fixed models within image for pooled contrasts, without estimating variation over model families. Confirmation/readout use 20,000 replicates and correctness-conditional replay 10,000. Intervals are 95% unless specified; native-mode primary comparisons use 97.5%.

The export supplies intervention construction, the frozen generator/scenes, scored outputs and the fitted Gate router. Its CPU entry reconstructs scenes and recounts saved predictions without inference or refitting. `extended_results.json` retains exact prompts, full supplementary matrices, case coordinates and implementation records.

A.1 Task coverage and answer interfaces

Tables 9 and 10 complement the main grid. The 4B DVQA/TabMWP extension uses the same 800 confirmation images as 8B. GLM has 100 public items per task except BLINK (172). CF denotes fixed consistency fallback.

The additional public tasks cover radiology questions with VQA-RAD (Lau et al., 2018), BLINK Visual Correspondence (Fu et al., 2025), and ScreenSpot-Pro grounding (Li et al., 2025). Table 7 reports categorical prompting and voting; Table 8 gives controlled computation and localization. The typed Gate extension includes two-dimensional clicks.

Benchmark	Strategy	**Qwen3-VL**		**InternVL3.5**		**Qwen2.5-VL**
		8B	4B	8B	4B	7B
VQA-RAD	Direct	**74.50**	**73.50**	**79.50**	68.50	71.00
	CoT	72.00	67.50	78.50	74.00	**72.00**
	Vote	74.00	72.00	78.50	**76.50**	70.00
BLINK (correspondence)	Direct	68.02	61.05	42.44	57.56	**68.02**
	CoT	**78.49**	69.77	**66.86**	62.79	63.37
	Vote	77.33	**73.26**	63.95	**66.28**	56.40

Table 7: **Additional categorical tasks.** Accuracy (%). These question interfaces complement the numerical main comparison.

Numerical Vote breaks valid-mode ties by earliest occurrence; all-invalid sets fail. Synthetic and ScreenSpot Vote instead requests Direct when no unique mode exists. CF accepts complete, valid, exact unanimity and otherwise selects Direct. ScreenSpot agreement uses normalized integer coordinates. Each paired comparison holds these rules fixed.

$\times$ marks an invalid comparison and a dash unavailable data. IV8 localization Direct reasons explicitly; IV4 VQA-RAD has a blank-image prior effect. BLINK's extractor accepts answer forms within the declared option set, without label-dependent rules or new generation. On BLINK, IV8/IV4 Direct legality is 75.0%/100.0%; numerical scoring is unchanged.

Benchmark	Strategy	Qwen3-VL		InternVL3.5		Qwen2.5-VL
		8B	4B	8B	4B	7B
Tables: compute	Direct	6.67	17.50	82.50	3.33	1.67
	CoT	**100.00**	**100.00**	**100.00**	**100.00**	97.50
	Vote	**100.00**	**100.00**	**100.00**	99.17	**100.00**
	Gate	**100.00**	**100.00**	**100.00**	99.17	**100.00**
Charts: compute	Direct	2.50	0.83	10.83	0.83	1.67
	CoT	**100.00**	**100.00**	**100.00**	99.17	**100.00**
	Vote	**100.00**	**100.00**	**100.00**	**100.00**	99.17
	Gate	**100.00**	**100.00**	**100.00**	**100.00**	99.17
Localization (single axis)	Direct	**60.94**	85.94	×	**95.31**	3.13
	CoT	37.50	43.75	37.50	46.88	**7.81**
	Vote	46.88	78.13	×	70.31	3.13
	Gate	57.81	**87.50**	×	92.19	3.13

Table 8: **Controlled computation and localization.** Accuracy (%); Gate uses the unanimity branch on unanimous samples and the learned selector otherwise. Invalid controls are marked ×.

Model	n	Direct	CoT	Vote	CF
VQA-RAD					
Q8	200	**74.50**	72.00	74.00	73.50
Q4	200	**73.50**	67.50	72.00	71.00
IV8	200	**79.50**	78.50	78.50	79.00
IV4	200	68.50	74.00	**76.50**	75.00
GLM	100	75.00	78.00	**80.00**	—
BLINK (correspondence)					
Q8	172	68.02	**78.49**	77.33	76.16
Q4	172	61.05	69.77	**73.26**	68.02
IV8	172	42.44	**66.86**	63.95	59.88
IV4	172	57.56	62.79	**66.28**	61.63
GLM	172	**91.28**	90.70	90.12	90.12
ScreenSpot-Pro					
Q8	200	56.00	51.00	55.00	**57.00**
Q4	200	**60.50**	57.50	59.50	**60.50**
IV8		×	×	×	×
IV4		×	×	×	×
GLM		×	×	×	×

Task	n	Direct	CoT	Vote	CF
GLM: numerical and controlled tasks					
DVQA	100	93.00	92.00	91.00	**94.00**
CountBench	100	74.00	78.00	**83.00**	80.00
ChartQA	100	65.00	72.00	**73.00**	72.00
TabMWP	100	69.00	**95.00**	90.00	83.00
MathVista	100	51.00	58.00	**63.00**	54.00
Tables	120	1.67	2.50	**39.17**	5.83
Charts	120	0.00	**100.00**	80.00	40.00
Location		**67.19**	62.50	65.63	**67.19**
IV4: arithmetic fallback					
Tables	120	3.33	**100.00**	99.17	98.33
Charts	120	0.83	99.17	**100.00**	98.33

Table 9: **Additional strategy and model comparisons.** Accuracy (%); CF is fixed consistency fallback. The complete numerical matrix is in Table 1, and shared-candidate selection is in Table 4. GLM uses its own cohorts. Invalid interfaces and unavailable endpoints remain marked; full matrices are in the accompanying extended results.

The Qwen2.5 extension uses the same 200 VQA-RAD and 172 BLINK items and existing task scorers. Its BLINK Direct answers are bare letters accepted by the common extractor. CoT and Vote score 109/172 and 97/172 under the shared extractor and earliest-sample tie rule. Its ScreenSpot Direct/CoT runs use a coordinate convention incompatible with the evaluator and are excluded; Vote is unavailable.

ScreenSpot uses 200 screenshots outside its 100-item development pool, with at least 99% legal outputs. Direct/CoT paired exact $p = 0.110/0.327$ (Q8/Q4), and CF/Direct $p = 1.00$ for both. BLINK uses all 172 Visual Correspondence validation items (chance 25.0%, majority class 29.7%). Q8/Q4 text-only and image-plus-text replay have equal aggregate accuracies, 78.5%/70.3%. GLM Vote/CF are 155/172 (90.12%) under the unified scorer's earliest-sample tie rule. Synthetic localization uses independent samples on 32 paired scenes (64 images); an earlier duplicated-seed run is excluded.

Task	Direct	CoT	Vote	Gate
Qwen3-VL-2B				
DVQA	88.63	84.38	88.25	**90.63**
CountBench	**76.94**	74.29	—	—
ChartQA	55.00	×	—	—
TabMWP	49.88	82.38	**85.63**	—
MathVista	50.87	×	—	—
Molmo2-8B				
DVQA	83.88	×	—	—
CountBench	**70.41**	63.88	—	—
ChartQA	64.38	59.00	**66.50**	—
TabMWP	80.75	×	—	—
MathVista	**51.75**	40.83	—	—
Qwen3.5-9B (thinking off)				
DVQA	**96.13**	93.38	94.00	—
CountBench	—	—	—	—
ChartQA	74.25	**84.75**	—	—
TabMWP	79.63	**99.50**	—	—
MathVista	—	—	—	—

Task	Direct	CoT	Vote	Gate
Kimi-VL-A3B-Instruct (16B total)				
DVQA	97.88	×	—	—
CountBench	50.20	×	—	—
ChartQA	75.50	×	—	—
TabMWP	68.50	×	—	—
MathVista	58.08	×	—	—
Idefics3-8B				
DVQA	92.00	×	—	—
CountBench	57.55	×	—	—
VQA-RAD	84.50	×	—	—
ChartQA	47.13	×	—	—
TabMWP	38.00	×	—	—
MathVista	43.67	×	—	—

Table 10: **Additional model coverage.** Accuracy (%). Qwen2.5 appears in Table 1. × invalid interface; dashes unavailable. Task sizes are 800/490/800/800/458 for DVQA/CountBench/ChartQA/TabMWP/MathVista, except Idefics3 uses 400 DVQA and 200 TabMWP items; VQA-RAD has 200.

Qwen3-VL-2B/DVQA uses a frozen Gate selector. Kimi/Idefics3 have usable Direct but no usable CoT under the fixed interface. About 5% of Qwen3-VL-2B/CountBench CoTs truncate. Qwen2.5/MathVista uses 458 Direct/CoT items and 457 complete Vote/CF/Gate records, without imputation.

Arithmetic Gate applies the frozen selector to saved candidates. Both N and E use temperature 0.7; Qwen2.5 arithmetic uses a 512^2-pixel budget, while its public runs use processor defaults. Localization additionally accepts normally terminated bare integers: all 64 Qwen2.5 Direct outputs become valid, while accepted readings in the three original models are unchanged. Native-thinking modes are separate.

B Diagnosing dependence on a fixed CoT

B.1 Text-only replay

Table 11a compares replay accuracy on identical eligible items; panel b stratifies usable sources by correctness, counting invalid replay as non-reproduction. Behavioral eligibility explains IV4 ChartQA's sign change relative to full-cohort CoT.

Under the unified scorer, the CoT/replay accuracy difference retains its sign in seven of eight model–task pairs. DVQA meets the prespecified four-positive-cell criterion; ChartQA meets it in three and fails. Separate pre-explanation controls on 200 items give 0–14% Direct accuracy with blank images and 4.5–15% with mismatched images. Their prompts and cohorts differ from the replay experiment.

B.2 Fixed-prefix access and image interaction

The first 100 confirmation images yield 99/100 and 100/100 applicable DVQA images and 99/100 and 97/100 TabMWP images (Q8/IV8), with common sets of 99 and 96. Inclusion uses item order and token applicability, never correctness. The forced prefix is the longest original-token prefix contained in the trace plus opening tag that enters the tag without an answer-body character or sign. It may end at `<answer`: a fused `>-` token is left for generation, preserving the source tokenization without forcing the sign. Native, numerical, equal-count letter-bearing lexical and whole-trace masks are crossed with real/blank images.

(a) Accuracy on identical eligible items

Subset	Model	Eligible	N	E	T	Δ_E	Δ_T	Same E/T
DVQA	Qwen 8B	396/400	95.5	92.7	89.6	-2.8	-5.8	375/375
DVQA	Qwen 4B	399/400	94.0	90.0	84.7	-4.0	-9.3	364/368
DVQA	InternVL 8B	400/400	81.8	93.0	89.2	+11.2	+7.5	379/382
DVQA	InternVL 4B	390/400	90.3	89.5	85.6	-0.8	-4.6	373/380
ChartQA	Qwen 8B	782/800	68.5	82.6	84.4	+14.1	+15.9	728/745
ChartQA	Qwen 4B	770/800	65.2	81.2	79.1	+16.0	+13.9	697/725
ChartQA	InternVL 8B	794/800	74.4	85.0	82.0	+10.6	+7.6	729/746
ChartQA	InternVL 4B	453/800	70.6	73.7	70.2	+3.1	-0.4	360/396

(b) Persistence conditional on source correctness

Subset	Model	Source images	Correct-answer persistence	Wrong-answer persistence	Undefined C / W
DVQA	Qwen 8B	170	355/367: 96.7 [94.5, 98.6]	20/25: 80.0 [63.2, 95.0]	0 / 0
DVQA	Qwen 4B	170	338/359: 94.2 [90.8, 97.0]	26/32: 81.2 [65.6, 93.6]	0 / 0
DVQA	InternVL 8B	170	356/372: 95.7 [93.4, 97.7]	23/28: 82.1 [66.7, 95.8]	0 / 0
DVQA	InternVL 4B	170	334/349: 95.7 [93.3, 97.8]	39/41: 95.1 [87.2, 100.0]	0 / 0
ChartQA	Qwen 8B	526	640/646: 99.1 [98.3, 99.7]	88/106: 83.0 [75.2, 90.1]	0 / 0
ChartQA	Qwen 4B	526	596/625: 95.4 [93.7, 96.9]	101/121: 83.5 [76.9, 89.8]	0 / 0
ChartQA	InternVL 8B	526	644/675: 95.4 [93.7, 96.9]	85/101: 84.2 [76.8, 90.8]	0 / 0
ChartQA	InternVL 4B	526	291/334: 87.1 [83.4, 90.7]	69/109: 63.3 [54.6, 72.2]	0 / 0

Table 11: **Text replay retains correct and wrong answers.** (a) Accuracy (%) and effects (pp); Same E/T counts exact equality among valid interpretable pairs. (b) Counts, percentages and 95% image-cluster intervals; invalid replay is non-reproduction. Undefined C/W counts empty bootstrap groups. Panels use their respective eligibility rules.

State and boundary controls. All masks use the same causal mask, kernel, positions and budget. Within an image condition, hidden states and cached keys/values before the answer-tag boundary match byte-for-byte across masks; opening-tag states may differ. Original and blank images retain token and rotary/cache positions but recompute prefix states. Empty-hook equivalence, source replay and source-intervention state checks are recorded separately.

Image interaction and accuracy. For accuracy a, $J = (a_{\mathrm{num,r}} - a_{\mathrm{num,b}}) - (a_{\mathrm{lex,r}} - a_{\mathrm{lex,b}})$ and $\Delta_{\mathrm{real}} = a_{\mathrm{num,r}} - a_{\mathrm{native,r}}$, where r/b denote real/blank images. Separate prefills make J sensitive to image-conditioned prefix encoding as well as blank-input losses; Δ_{real} measures answering quality.

Nearest-position lexical masks preserve count and minimize token distance. Residual distances are 3.58/2.03 tokens on DVQA and 10.66/9.85 on TabMWP (Q8/IV8). Table 13 gives the paired effects; the DVQA direction also persists under exact-numerical scoring. Matching remains approximate.

Q8 TabMWP's numerical-versus-whole-trace advantage comprises 22 numerical corrections and 23 unusable-to-correct transitions; all losses against native continuation instead involve usable numerical answers. Across all 100 planned images, deterministic missing-outcome bounds for $(J, \Delta, A_{\mathrm{num,r}} - A_{\mathrm{all,r}})$ are $([37, 39], [-2, -1], [1.5, 2.5])$ on DVQA and $([24.5, 32.5], [-16, -12], [22, 26])$ on TabMWP (pp). These are finite-population bounds, not confidence intervals. The prespecified conjunction fails: positive DVQA J and real-image repair, positive TabMWP numerical-minus-whole-trace accuracy, and TabMWP noninferiority to native within -2 pp are not all met.

Subset	Model	n/planned	Image	Source	Native	Numeric	Lexical	Whole trace
DVQA	Qwen 8B	99/100	Real	93.94	93.94	93.94	93.94	91.92
DVQA	Qwen 8B	99/100	Blank	93.94	94.95	65.66	94.95	2.02
DVQA	InternVL 8B	100/100	Real	96.00	96.00	93.00	96.00	91.00
DVQA	InternVL 8B	100/100	Blank	96.00	96.00	46.00	96.00	2.00
TabMWP	Qwen 8B	99/100	Real	97.98	97.98	86.87	97.98	39.39
TabMWP	Qwen 8B	99/100	Blank	97.98	97.98	63.64	97.98	2.02
TabMWP	InternVL 8B	97/100	Real	96.91	96.91	79.38	96.91	78.35
TabMWP	InternVL 8B	97/100	Blank	96.91	96.91	44.33	96.91	6.19

Table 12: **Complete fixed-prefix readout arms.** Accuracy (%); Image identifies the continuation input. Rows use model-specific applicable cohorts; Figure 2c averages models on their common cohorts. Source is the original CoT accuracy, repeated for both image conditions. Blank inputs retain the original image's trace.

Subset	n	Contrast	Qwen 8B	InternVL 8B	Pooled
DVQA	99	$G_{\mathrm{num}} - G_{\mathrm{lex}}$	+29.29 [+20.20, +38.38]	+46.46 [+36.36, +57.58]	+37.88 [+29.80, +46.46]
DVQA	99	$A_{\mathrm{num,r}} - A_{\mathrm{native,r}}$	+0.00 [-5.05, +5.05]	-3.03 [-8.08, +1.01]	-1.52 [-4.55, +1.52]
DVQA	99	$A_{\mathrm{num,r}} - A_{\mathrm{all,r}}$	+2.02 [-3.03, +8.08]	+1.01 [-4.04, +6.06]	+1.52 [-2.02, +5.05]
DVQA	99	$G_{\mathrm{num}} - G_{\mathrm{nearest}}$	+29.29 [+20.20, +38.38]	+46.46 [+36.36, +56.57]	+37.88 [+29.79, +46.46]
TabMWP	96	$G_{\mathrm{num}} - G_{\mathrm{lex}}$	+22.92 [+13.54, +32.29]	+34.38 [+22.92, +45.83]	+28.65 [+19.79, +37.50]
TabMWP	96	$A_{\mathrm{num,r}} - A_{\mathrm{native,r}}$	-11.46 [-17.71, -5.21]	-17.71 [-26.04, -9.38]	-14.58 [-20.83, -8.85]
TabMWP	96	$A_{\mathrm{num,r}} - A_{\mathrm{all,r}}$	+46.88 [+37.50, +57.29]	+1.04 [-4.17, +6.25]	+23.96 [+18.23, +29.69]
TabMWP	96	$G_{\mathrm{num}} - G_{\mathrm{nearest}}$	+22.92 [+13.54, +32.29]	+34.38 [+21.88, +45.83]	+28.65 [+20.31, +37.50]

Table 13: **Complete paired readout contrasts.** Percentage points with 95% image-bootstrap intervals on common images. G denotes real-minus-blank accuracy. Nearest-position control is a separately frozen supplement.

B.3 Joint masks and grouping controls

The original readout batch yields 66 shared TabMWP images (96/90 applicable, 70/68 separable). Magnitude normalization ignores signs and strips commas/percent marks without rescaling. Token-mapped digits matching the source-answer magnitude form A; other magnitudes form O. Exclusions cover ambiguous/nonmonotonic mappings, empty groups and source values in question/table/title text. Lexical controls match count and minimize token distance; exact mapping and tie rules are in the export.

Persistence interaction. For blank-image retention P, $I = P_A + P_O - P_\varnothing - P_U$ measures the extra loss from blocking O when A is blocked. Here $U = A \cup O$ is the all-digit mask called All in the main text; Native denotes unmasked continuation (None). Whole-trace masking also blocks nonnumeric trace positions. Joint-only loss contributes positively and union recovery negatively. The 1110 joint-loss pattern is nonadditive but monotone on the tested mask sets; the 1011 recovery pattern violates monotonicity. Thus a positive interaction does not by itself demonstrate recovery. Grouping specificity is $\Delta_{\mathrm{grp}} = I_{\mathrm{original}} - \frac{1}{3}\sum_{j=1}^{3} I_{\mathrm{sham},j}$ on identical eligible items. Invalid/truncated outputs count as non-reproduction; correctness is scored separately.

The 66-image cohort has 1/2 wrong sources (Q8/IV8). Pooled persistence I is +59.85 pp [49.24,69.70] under blank and +18.18 [10.61,26.52] under real input; accuracy interactions are +45.45 [35.61,55.30] and +15.15 [8.33,22.73]. The prespecified O-lex minus O blank-persistence

effect, +0.76 [0.00,2.27], fails the positive-lower-bound criterion. The joint decomposition is retrospective. Joint-only changes are 13/11 under real and 37/43 under blank input (Q8/IV8), all usable. Lexical controls preserve native answers throughout the four model/image conditions.

Independent controls begin with 192 previously unexposed images per task. The wider TabMWP cohort contains 172 images for which both models have usable numerical sources, safe prefixes, unambiguous digit mappings, nonempty Answer/Other groups and count-matched lexical controls. Of the 20 excluded images, three fail only for Qwen, eleven only for InternVL and six for both. The 119-image input-value-separable subset additionally requires each model's source-answer magnitude to be absent from numerical literals in the question, table title and table text. This excludes 53 of the 172 images: 52 overlap for both models and one only for InternVL. Thus separability concerns input-value overlap, beyond the nonempty-group requirement. DVQA's 72 common images apply the question-overlap rule. Selection does not use correctness. Three random partitions preserve the union and each group's count within four token-rank bins.

(a) Per-model interactions

Task	Model	n	I original	Mean I random	Δ_{grp}
TabMWP	Q8	119	42.86	33.61	+9.24
	IV8	119	61.34	49.30	+12.05
DVQA	Q8	72	−38.89	−10.19	−28.70
	IV8	72	−12.50	9.72	−22.22

(b) Pooled interactions and paired contrasts

Cohort	n	Literal I	Random I	Δ_{grp}	95% CI
TabMWP: separable	119	+52.10	+41.46	**+10.64**	[+7.28, +14.29]
DVQA: separable	72	−25.69	−0.23	**−25.46**	[−33.80, −17.59]
TabMWP: wider	172	+33.43	+32.46	**+0.97**	[−3.78, +5.43]
ChartQA: applicable	126	+31.75	+21.43	**+10.32**	[+4.10, +16.53]

Table 14: **Independent partition specificity.** Blank-image persistence interactions in pp; Δ_{grp} is literal minus matched-random interaction. Pooled rows average models within image. Table 2a gives the four absolute retention rates. ChartQA is descriptive.

Separable TabMWP passes coverage, positive-lower-bound, model-direction and technical criteria; DVQA transfer fails, and wider TabMWP has no confirmed effect. Q8/IV8 source-correct/wrong counts are 119/0 and 117/2 on TabMWP, 65/7 and 69/3 on DVQA.

From persistence to correctness. Numeric harm/recovery requires four usable outputs and the corresponding correctness pattern, excluding one unusable Qwen TabMWP union output and within-tolerance changes. The 119-image TabMWP cohort is nested in its 172-image cohort; DVQA's scopes coincide.

Which number replaces the answer? The A-only output matches another trace magnitude in 28/29 Qwen and 15/15 InternVL DVQA recoveries, motivating a targeted test of competing numbers (Figure 2a).

Question composition. Largest/smallest questions comprise 105/192 planned and 64/72 eligible DVQA images. Blank persistence recoveries occur on 27/64 extrema and 2/8 other questions for Q8, 15/64 and 0/8 for IV8; corresponding all-valid correctness recoveries are 26/64 and 2/8, 13/64 and 0/8. The eight non-extremum questions limit comparisons in this post-hoc split.

Input overlap and trace structure. A post-review descriptive analysis joins the recorded interventions to the original trace metadata, without new model calls or outcome-dependent thresholds. On the 119 common input-value-separable TabMWP images, joint-only blank-image changes number 51 for Qwen and 73 for InternVL; on the remaining 53 applicable images, excluded because at least one source-answer value overlaps the input, the counts are two and three. Real-image counts are 16/12 and 5/1, respectively. These are original-answer retention patterns, not counts of newly

				Joint-only change (1110)		Union recovery (1011)	
Cohort	Model	Image	n	Cases	Numeric harm	Cases	Numeric recovery
TabMWP: separable	Q8	real	119	16	10	2	2
	Q8	blank	119	51	35	0	0
	IV8	real	119	12	7	0	0
	IV8	blank	119	73	61	0	0
DVQA: separable	Q8	real	72	1	1	1	1
	Q8	blank	72	1	1	29	28
	IV8	real	72	0	0	1	1
	IV8	blank	72	5	5	15	13
TabMWP: wider	Q8	real	172	21	15	8	8
	Q8	blank	172	53	37	8	8
	IV8	real	172	13	8	2	2
	IV8	blank	172	76	63	6	6

Table 15: **Joint changes can alter correctness as well as persistence.** Patterns are ordered native/*A*/*O*/union, with 1 denoting source-answer reproduction. Cases gives each pattern's frequency. Numeric harm counts the subset with four usable outputs and correctness pattern 1110; numeric recovery counts the corresponding subset with correctness pattern 1011. These are effects of interventions on fixed traces, not corrections of naturally wrong source answers.

incorrect answers. In DVQA, a split at the median safe-prefix length among all available source prefixes within each model gives Qwen 25/52 recoveries above the median and 4/20 at or below it; InternVL gives 11/38 and 4/34. The thresholds are 169.5 and 165.5 tokens. The accompanying descriptive export retains every bin for question type, answer-value occurrences, distinct Other magnitudes, input overlap and length. These features co-vary with eligibility and question structure; the comparisons do not identify independent causes or validate a recovery predictor.

B.4 Continuous readout and key-preserving controls

We measure a continuous margin for the first token following the recorded safe prefix. Its source token s is the corresponding token in the model's natural CoT output. For each model and image condition, the foil f is the highest-logit native token other than s, with ties resolved by token ID. All interventions share this pair. We apply the four-arm interaction to $m_c = \ell_c(s) - \ell_c(f)$ and subtract the mean interaction of three matched random partitions to obtain grouping specificity. Table 16 reports both contrasts in raw-logit units.

The hard-mask control uses the same 172 TabMWP and 72 DVQA images as the joint-mask analysis, including TabMWP's 119-image separable subset. On separable TabMWP with blank images, the fixed-model pooled interaction is 3.200 [2.648,3.770]. Thus the joint effect is already visible in continuous scores before the final token decision. Table 17 retains these complete populations.

The value-zero control uses 32 images per task selected by a fixed hash order. At each language attention layer, it keeps the current call's query, keys and mask, sets the selected numerical value rows to zero, and replaces only answer-phase query outputs. Queries before the answer boundary retain their native outputs; subsequent answer states can evolve. Table 16 compares both operators on these identical images and source–foil pairs. The pooled TabMWP blank-image value-zero interaction is 3.932 [3.012,4.902], meeting the planned two-model positive-direction criterion. Both operators yield positive interactions for each model with real or blank images. On DVQA, the matched hard-mask estimates are +0.105 and -0.664 under blank input, rather than the -0.694 and -0.780 of the full 72-image population. Operator and population changes must therefore be distinguished. DVQA does not meet the two-model value-zero transfer criterion. These first-token comparisons complement the complete-answer study reported below.

Dataset / image	Model	Hard mask	Value zero	Value zero − hard
(a) Four-arm interaction I				
TabMWP / blank	Qwen	+2.598 [+1.309, +4.055]	+3.531 [+2.625, +4.449]	+0.934 [-0.262, +2.043]
TabMWP / blank	InternVL	+3.598 [+2.422, +4.875]	+4.332 [+3.047, +5.652]	+0.734 [-0.230, +1.762]
TabMWP / real	Qwen	+1.020 [+0.094, +2.180]	+1.551 [+0.840, +2.301]	+0.531 [-0.492, +1.531]
TabMWP / real	InternVL	+0.914 [+0.391, +1.500]	+2.043 [+1.305, +2.855]	+1.129 [+0.492, +1.812]
DVQA / blank	Qwen	+0.105 [-0.715, +0.910]	+1.043 [+0.547, +1.594]	+0.938 [+0.355, +1.547]
DVQA / blank	InternVL	-0.664 [-1.535, +0.055]	-0.027 [-0.512, +0.379]	+0.637 [+0.023, +1.379]
DVQA / real	Qwen	-0.098 [-0.480, +0.285]	+0.648 [+0.230, +1.133]	+0.746 [+0.375, +1.195]
DVQA / real	InternVL	-0.012 [-0.309, +0.258]	+0.023 [-0.215, +0.254]	+0.035 [-0.195, +0.262]
(b) Grouping specificity Δ_{grp}				
TabMWP / blank	Qwen	-0.107 [-0.546, +0.318]	+0.379 [-0.289, +1.087]	+0.486 [+0.005, +0.984]
TabMWP / blank	InternVL	+0.530 [-0.171, +1.352]	+1.669 [+0.681, +2.815]	+1.139 [+0.509, +1.836]
TabMWP / real	Qwen	-0.268 [-0.775, +0.177]	-0.112 [-0.794, +0.568]	+0.156 [-0.375, +0.824]
TabMWP / real	InternVL	+0.232 [-0.107, +0.602]	+0.660 [+0.125, +1.211]	+0.428 [+0.026, +0.823]
DVQA / blank	Qwen	-2.505 [-4.272, -1.132]	-1.655 [-2.708, -0.753]	+0.850 [+0.193, +1.685]
DVQA / blank	InternVL	-1.710 [-2.747, -0.833]	-1.121 [-1.895, -0.509]	+0.589 [+0.220, +1.018]
DVQA / real	Qwen	-1.095 [-1.714, -0.535]	-1.173 [-1.681, -0.707]	-0.078 [-0.483, +0.353]
DVQA / real	InternVL	-0.665 [-1.074, -0.355]	-0.448 [-0.698, -0.233]	+0.217 [+0.034, +0.430]

Table 16: **Matched access-operator controls on the same 32 images per task.** I is the four-arm interaction in a fixed source–foil logit margin; Δ_{grp} subtracts the mean of three matched random partitions. Both operators use identical traces and token pairs. Units are raw logits; brackets are paired 95% image-bootstrap intervals from 20,000 draws. Single-token readouts do not measure complete-answer recovery.

Continuous readout under hard masking				
Dataset / image	Model	n	I [95% CI]	Δ_{grp} [95% CI]
TabMWP sep. / blank	Qwen	119	+2.229 [+1.670, +2.817]	+0.318 [-0.104, +0.756]
TabMWP sep. / blank	InternVL	119	+4.170 [+3.487, +4.859]	+0.720 [+0.334, +1.131]
TabMWP sep. / real	Qwen	119	+0.956 [+0.428, +1.542]	+0.079 [-0.278, +0.428]
TabMWP sep. / real	InternVL	119	+1.178 [+0.753, +1.642]	+0.382 [+0.081, +0.707]
TabMWP all / blank	Qwen	172	+0.754 [-0.106, +1.531]	-0.938 [-1.782, -0.159]
TabMWP all / blank	InternVL	172	+3.007 [+2.355, +3.654]	-0.219 [-0.835, +0.352]
TabMWP all / real	Qwen	172	+0.495 [-0.243, +1.274]	-0.348 [-1.084, +0.402]
TabMWP all / real	InternVL	172	+0.768 [+0.359, +1.178]	-0.046 [-0.398, +0.293]
DVQA / blank	Qwen	72	-0.694 [-1.493, +0.043]	-3.398 [-4.638, -2.300]
DVQA / blank	InternVL	72	-0.780 [-1.319, -0.286]	-2.497 [-3.342, -1.745]
DVQA / real	Qwen	72	-0.417 [-0.887, -0.012]	-1.573 [-2.445, -0.894]
DVQA / real	InternVL	72	+0.012 [-0.306, +0.290]	-0.874 [-1.242, -0.575]

Units: raw-logit margins; $\Delta_{\mathrm{grp}} = I - \mathrm{mean}(I_{\mathrm{sham}})$.

Table 17: **Continuous hard-mask results on the complete eligible populations.** "Sep." denotes input-value-separable traces and "all" the common applicable cohort. I and Δ_{grp} have the same definitions as in Table 16; 95% intervals use 20,000 image-bootstrap draws.

In the value-zero study, 118 of 128 source tokens contain a digit. The other ten fuse the marker ending with a minus sign and remain on the continuation side to avoid supplying the sign in advance. The larger hard-mask study contains 457 digit-containing tokens, thirty marker/minus tokens and one marker/currency token. An additional digit-only sensitivity analysis preserves the TabMWP direction: with 30 images per model, blank-image interactions are 3.758 [2.863,4.663] for Qwen and 4.588 [3.254,5.933] for InternVL. The corresponding 29-image DVQA estimates are 1.134 [0.612,1.724] and -0.043 [-0.569,0.401]. All original and sensitivity results accompany the exported records.

B.5 Complete-answer comparison on the matched cohort

We extend the value-zero operator to complete continuations on the same fixed 32 TabMWP and 32 DVQA images per model used for the first-token comparison. Source prefixes, image conditions,

groupings, checkpoints and greedy decoding remain the same. The total prefix-plus-continuation budget is 512 tokens. The comparison pairs 1,024 new value-zero answers with the 1,024 recorded hard-mask answers. This is a control on previously exposed traces.

Tables 18 and 19 report all four arms. Retention uses exact signed normalized equality to the source answer, while correctness uses the original task tolerance. No continuation reaches the length limit. Two hard-mask outputs and one value-zero output are unusable numerical answers and remain in their denominators. Under blank-image DVQA, value zeroing preserves recovery on three of Qwen's twelve original recovery cases and one of InternVL's five. Its total recovery counts are three and two, so the latter includes one additional case. Paired recovery changes are -28.13 points $[-43.75,-12.50]$ for Qwen and -9.38 $[-21.88,3.13]$ for InternVL.

Table 18: **Complete-answer retention under matched access operators.** Counts out of 32 for every row. Hard denotes key masking and Zero denotes value zeroing.

Model	Task	Image	Operator	None	Answer	Other	All
Qwen3-VL-8B	TabMWP	Original	Hard	32	31	32	27
Qwen3-VL-8B	TabMWP	Original	Zero	32	32	32	24
Qwen3-VL-8B	TabMWP	Blank	Hard	32	32	32	16
Qwen3-VL-8B	TabMWP	Blank	Zero	32	32	32	17
Qwen3-VL-8B	DVQA	Original	Hard	32	32	32	31
Qwen3-VL-8B	DVQA	Original	Zero	32	32	32	32
Qwen3-VL-8B	DVQA	Blank	Hard	32	16	32	27
Qwen3-VL-8B	DVQA	Blank	Zero	32	24	32	24
InternVL3.5-8B	TabMWP	Original	Hard	32	32	32	30
InternVL3.5-8B	TabMWP	Original	Zero	32	32	32	29
InternVL3.5-8B	TabMWP	Blank	Hard	32	32	32	13
InternVL3.5-8B	TabMWP	Blank	Zero	32	30	32	10
InternVL3.5-8B	DVQA	Original	Hard	32	31	32	32
InternVL3.5-8B	DVQA	Original	Zero	32	32	32	31
InternVL3.5-8B	DVQA	Blank	Hard	31	18	31	20
InternVL3.5-8B	DVQA	Blank	Zero	31	20	31	18

Table 19: **Complete-answer correctness on the same traces.** Counts out of 32 under the task's numerical tolerance.

Model	Task	Image	Operator	None	Answer	Other	All
Qwen3-VL-8B	TabMWP	Original	Hard	32	31	32	28
Qwen3-VL-8B	TabMWP	Original	Zero	32	32	32	27
Qwen3-VL-8B	TabMWP	Blank	Hard	32	32	32	20
Qwen3-VL-8B	TabMWP	Blank	Zero	32	32	32	20
Qwen3-VL-8B	DVQA	Original	Hard	29	29	29	28
Qwen3-VL-8B	DVQA	Original	Zero	29	29	29	29
Qwen3-VL-8B	DVQA	Blank	Hard	29	15	29	26
Qwen3-VL-8B	DVQA	Blank	Zero	29	21	29	23
InternVL3.5-8B	TabMWP	Original	Hard	32	32	32	31
InternVL3.5-8B	TabMWP	Original	Zero	32	32	32	30
InternVL3.5-8B	TabMWP	Blank	Hard	32	32	32	16
InternVL3.5-8B	TabMWP	Blank	Zero	32	30	32	11
InternVL3.5-8B	DVQA	Original	Hard	30	29	30	30
InternVL3.5-8B	DVQA	Original	Zero	30	30	30	29
InternVL3.5-8B	DVQA	Blank	Hard	29	18	29	18
InternVL3.5-8B	DVQA	Blank	Zero	29	20	29	18

The export includes complete decoded continuations and generated IDs, source and gold answers, termination information and mask positions. CPU replay re-extracts every answer and reproduces the per-arm counts, pattern transitions and paired intervals. The changed cached-generation path was qualified by exact hard-mask tail replay, empty-control replay, agreement with the original first-logit fingerprints, and intervention coverage across layers and answer-generation calls. All source images in the fixed cohort remain in the analysis. Descriptive 95% paired-image intervals use 20,000 draws with seed 20260926.

B.6 WHOLE-VALUE GROUPING CONTROLS

The original token-randomized partitions preserve group sizes within four rank bins, but can split complete numerical expressions and separate their repeated occurrences. On the 119 separable TabMWP images, at least one partition splits a complete expression on 100 Qwen and 89 InternVL traces. An audit of the recorded digit IDs against the original numerical expressions finds no alignment failures.

We therefore construct alternatives that retain all copies of one numerical magnitude together. An alternative must preserve the Answer group's number of occurrences, the multiset of digit widths per occurrence and the exact token count in each of the original four rank bins. Original and equivalent swapped partitions are excluded. At most three alternatives are selected in fixed hash order before obtaining their outputs.

These conditions admit alternatives on 4/32 Qwen TabMWP, 4/32 Qwen DVQA, 3/32 InternVL TabMWP and 3/32 InternVL DVQA images, with five, four, four and three distinct partitions, respectively. Both operators are run with original and blank images, giving 128 alternative-mask continuations and 56 native identity checks. None and All are shared with the matched complete-answer comparison.

Table 20: **Original grouping minus the matched whole-value control.** Differences in the four-arm interaction, in percentage points, with descriptive 95% paired-image intervals. Alternatives are averaged within image before resampling. Retention and correctness contrasts coincide on these records.

Model	Task	Image	n	Hard	Value zero
Qwen3-VL-8B	TabMWP	Original	4	-25.00 $[-75.00, 0.00]$	0.00 $[0.00, 0.00]$
Qwen3-VL-8B	TabMWP	Blank	4	25.00 $[0.00, 75.00]$	25.00 $[0.00, 75.00]$
Qwen3-VL-8B	DVQA	Original	4	0.00 $[0.00, 0.00]$	0.00 $[0.00, 0.00]$
Qwen3-VL-8B	DVQA	Blank	4	-50.00 $[-100.00, 0.00]$	0.00 $[0.00, 0.00]$
InternVL3.5-8B	TabMWP	Original	3	0.00 $[0.00, 0.00]$	0.00 $[0.00, 0.00]$
InternVL3.5-8B	TabMWP	Blank	3	0.00 $[0.00, 0.00]$	33.33 $[0.00, 100.00]$
InternVL3.5-8B	DVQA	Original	3	0.00 $[0.00, 0.00]$	0.00 $[0.00, 0.00]$
InternVL3.5-8B	DVQA	Blank	3	0.00 $[0.00, 0.00]$	0.00 $[0.00, 0.00]$

The differences in Table 20 vary across conditions, and all intervals include zero. Exact matching restricts this comparison to 3–4 images per model and task. Degenerate bootstrap intervals from identical observed differences do not establish population equivalence. The construction controls digit width, repetition and rank-bin counts, while grammatical role and exact absolute position can still differ.

B.7 SOURCE INTERVENTION DESIGN

All source tests use the runtime and state controls in Sections A and B.2. The three DVQA experiments below use exposed traces and select cases before new intervention outputs.

Two absent positive integers match the edited digit width. Donors exclude trace, question, source and gold magnitudes, plus the old A output in the C experiment. Tokenizer validation preserves signs, unedited tokens and positions. P recomputes edited prefixes; V transfers donor values at selected keys in every layer, preserving recipient text and the current attention call's queries, keys and mask. Pre-tag states remain intact; answer states may evolve. Source replay and boundary checks pass; value-transfer experiments also pass identical-prefill Self checks. Validation records are archived.

Selecting the two replacements. For an edited magnitude with w digits, candidates are positive integers from 10^{w-1} through $10^w - 1$. We exclude all magnitudes appearing in the question or trace, the source answer and every accepted gold answer. The alternative-value study also excludes its old Answer-mask output. Candidates require validated digit-token encodings. Width and exclusions therefore depend on the observed source; no independence from source or gold is assumed.

DVQA candidates are ranked by the full SHA256 of `seed|model|item_id|value`; the first two are used. Their seeds are `numeric-content-20260919-v1` for accessible alternatives and `union-source-20260919-v1` for blocked-source values. The 800-scene and 400-error studies instead seed Python's `random.Random` with the integer represented by the first eight SHA256 hexadecimal digits of `seed|donor|model|item_id`. They repeatedly draw with `randrange`, reject excluded or duplicate magnitudes, and retain the first two accepted draws. Their study seeds are `synthetic-diagnostic-scaling-v1` and `confirmation-source-20260923-v1`, respectively; model keys are `qwen8b` and `internvl8b`.

Both chosen donors must pass the tokenizer and position checks; a failed pair is not replaced by searching for alternatives. In the 400-error study, donor qualification precedes the fixed-hash selection of 400 from 551 eligible sources. All pairs are fixed before their donor responses are generated. Observed donor magnitudes span 1–97 in the blocked-source DVQA study, 10–99 in the synthetic study, and 1–91,586,119,529 in the natural-error study. The latter retains source widths from one to eleven digits. The effects concern these qualified pairs rather than an average over arbitrary numerical edits.

For a valid normally terminated numerical answer, let $h(y, R) = \mathbf{1}[|y| = R]$, and zero otherwise. Donor following is

$$d = \tfrac{1}{2}\{h(y_1, R_1) + h(y_2, R_2) - h(y_1, R_2) - h(y_2, R_1)\}.$$

The effect is $100\,\mathrm{mean}(d)$, using 20,000 image-paired bootstrap draws and fixed model-specific seeds. It measures magnitude following, retaining invalid outputs in the denominator; signed responses, source persistence and gold correctness are also recorded.

B.8 Targeted numerical-key competition

From 72 separable DVQA images, we select source-preserving blank native continuations whose valid A output matches another trace magnitude: 30/25 cases (38 distinct images, 17 shared), with source correctness 29/30 and 23/25. Union recovery is absent in 2/10 cases. The fixed plan retains exclusions and IDs.

With A blocked, C additionally masks digits matching the old A output, M masks equally many remaining O keys, and L equally many lexical keys. Minimum-distance matching yields 17.76/11.51 tokens for M and 2.81/2.22 for L. Counts match; positions/content differ, and M may cut literals.

		Source recovery (%)				Gold correct (%)	Alternative kept (%)
Model	Image	C	M	L	Union	C / M	C / M
Q8	Blank	50.00	0.00	3.33	93.33	50.00 / 0.00	0.00 / 100.00
Q8	Real	93.33	90.00	90.00	93.33	96.67 / 90.00	0.00 / 6.67
IV8	Blank	40.00	12.00	8.00	60.00	48.00 / 16.00	16.00 / 84.00
IV8	Real	96.00	96.00	96.00	100.00	88.00 / 88.00	0.00 / 0.00

Table 21: **Alternative suppression, source recovery and correctness.** Rates use the same 30 Q8/25 IV8 cases selected under blank input. Alternative persistence tests exact signed equality to the old blank A output.

Blank $C - M$ recovery is +50.00 [33.33,66.67]/+28.00 [4.00,52.00] pp. Favorable/adverse discordances are 15/0 and 9/2 (Q8/IV8); Holm-adjusted exact $p = 0.0001221$ and 0.06543. IV8's positive bootstrap interval does not invert the discrete exact test. Secondary $C - L$ effects are +46.67 [30.00,63.33]/+32.00 [12.00,52.00]; the prespecified distance-at-most-20 subset ($n = 22$ each) yields $C - M = +36.36$ [18.18,59.09]/+22.73 [0.00,45.45].

Expansion fails the joint criterion of two-model $C - M$ and $C - L \geq 10$ pp and both adjusted primary $p < 0.05$. With real images, A persistence is 90/96% and $C - M = +3.33$ [0.00,10.00]/0.00 [0.00,0.00].

B.9 DONOR MAGNITUDE AT ACCESSIBLE NUMERICAL POSITIONS

Six/four of the preceding 30/25 cases lack two donors, leaving 24/21 pairs (33 distinct images, 12 shared). Selection uses prior native/A records, independently of $C/M/L$ outcomes. All six arms retain blank input and A masking. Base replays A; Self replaces base values at C; P edits complete C literals; V transfers their values.

Model	Intervention	n	Matched	Crossed	Identity effect [95% CI]
Q8	Value replacement	24	30/48	0/48	+62.50 [+45.83, +77.08]
Q8	Full-prefix replacement	24	32/48	0/48	+66.67 [+50.00, +81.25]
IV8	Value replacement	21	24/42	0/42	+57.14 [+38.10, +73.81]
IV8	Full-prefix replacement	21	27/42	0/42	+64.29 [+45.24, +80.95]

Table 22: **Donor following through accessible numerical values.** Matched/crossed counts use $2n$ outputs; identity effects (pp) are paired by image. P changes the prefix; V retains recipient text.

For V, 19/24 Q8 and 15/21 IV8 image effects are positive, none negative. One/two matched outputs have negative signs, consistent with a magnitude endpoint. Exact P/V agreement is 32/48 and 19/42. The intervention identifies a value route for the induced influence, not a unique carrier or equivalent P/V computations.

B.10 INDIRECT TRANSMISSION FROM BLOCKED SOURCE DIGITS

The post-hoc cohort starts from 29/15 observed blank-DVQA recoveries (1011). Six/one lack donors, leaving 23/14 cases (28 distinct images, nine shared), with source correctness 22/23 and 12/14. Selection precedes new outputs. P changes A while U blocks every digit-bearing key; V transfers values at complementary nonnumeric keys $\mathcal{N}$, including punctuation/whitespace. Base replays U; Self replaces its $\mathcal{N}$ values; Whole trace blocks every trace position.

Exact transfer operator. Let p denote the first CoT token after the model prompt and b the first token overlapping the opening answer tag. If K_{num} contains all digit-bearing trace positions before b, the nonnumeric positions are $\mathcal{N} = \{p, \ldots, b-1\} \setminus K_{\text{num}}$. This excludes the prompt, image tokens, answer tag and final answer. These source interventions require one ASCII digit per numeric token and exact decoding after replacement; mixed numeric tokens are excluded.

For integer-valued sources, we substitute an absent integer of the same digit width into Answer and recompute the prefix. Tokenizer checks preserve the position map and prefix length. All digit-bearing trace keys remain blocked for answer queries $q \geq b$. In the second intervention, the recipient retains its original text. At each language attention layer ℓ, a copy of its value tensor uses donor values at $\mathcal{N}$,

$$\widetilde{\mathbf{V}}_{\ell,j} = \begin{cases} \mathbf{V}^{\text{donor}}_{\ell,j}, & j \in \mathcal{N}, \\ \mathbf{V}^{\text{recipient}}_{\ell,j}, & j \notin \mathcal{N}. \end{cases}$$

Only queries $q \geq b$ use this copy, with digit access still blocked. Earlier query outputs use the original values; the cache is not overwritten. The current attention call's queries and keys remain unchanged by replacement. Later answer states, queries and keys evolve along the intervened trajectory. Thus the transfer tests the selected states jointly across layers.

Here U is the digit-bearing set K_{num}. The transfer acts on the nonnumeric states jointly and does not identify a single position as the carrier.

Numerical P/V outputs agree on 42/46 and 25/28 (Q8/IV8). The paired effects in Table 23 identify indirect source transmission. Whole-trace masking also changes attention normalization, so zero persistence does not establish a necessary route or its contribution to unmodified recovery.

Self reproduces U in every case; nonnumeric states before the first edit remain equal. All responses terminate normally. Q8's one nonnumeric P_2 response (`hence`) and one whole-trace response (`VALUE`) remain in the denominator.

Model	n	Source-digit edit P		Nonnumeric-value transfer V	
Qwen	23	**+36.96**	[+19.57, +56.52]	**+32.61**	[+15.22, +52.17]
InternVL	14	**+32.14**	[+10.71, +57.14]	**+35.71**	[+14.29, +60.71]

Table 23: **Donor-specific influence with all digit keys blocked.** Matched minus crossed magnitude following (pp; paired 95% intervals). Invalid outputs remain in the denominator. These are source-identity effects, not accuracy gains.

Linking the tests on identical traces. We retrospectively join the three DVQA follow-ups by model and item identity. All 22 Qwen and 14 InternVL shared records have identical original images, source traces, prefix tokens and answer boundaries. Every record has the original 1011 recovery pattern. We retain the entire intersection and count three outcomes: source retention under the competing-digit mask C but not its matched mask M; positive paired value transfer at accessible competing positions; and positive paired value transfer at nonnumeric positions with all digits blocked. The last two outcomes require $d > 0$ under V.

Four Qwen and five InternVL records meet all three conditions (Table 24). Thus the tests can converge within one recorded trace. This reuse of previously exposed, recovery-selected records is descriptive; it does not make the follow-ups independent or establish a necessary path for the original recovery. All patterns, paired responses and replacements accompany the saved-record replay.

Competitor mask	Competing-value transfer	Nonnumeric transfer	Qwen	InternVL
0	0	0	2	1
0	0	1	1	0
0	1	0	6	5
0	1	1	3	1
1	0	0	1	1
1	0	1	1	0
1	1	0	4	1
1	1	1	4	5
All shared traces			22	14

Table 24: **Three diagnostic outcomes on the same traces.** Each row gives the complete pattern of outcomes defined above; 1 means the condition holds. All 22 Qwen and 14 InternVL shared traces remain in the denominator. This is a retrospective intersection of the existing DVQA studies.

C Controlled visual benchmarks

C.1 Computation with images and exact transcriptions

Text-Direct scores 1.7–6.7% in its three valid arms, failing the original sufficiency criterion; text-CoT reaches 100% in all four models. Empirical zero-width intervals on unanimous outcomes do not imply zero uncertainty on new images.

C.2 Source diagnosis on 800 fixed scenes

The generator balances bar-chart extrema questions across four/eight bars and compact/wide spacing. Each of the four cells contains 200 scenes, equally split between tallest and shortest questions. Both models use the same 800 scenes, with a separate 64-scene development set excluded. The scene set and intervention procedure were fixed before inference. Continuations are greedy; this study evaluates source transmission rather than sampled answer selection.

Each scene samples four or eight distinct integers uniformly without replacement from 10–99, assigns labels A–D or A–H, and shuffles their display order. Its question is `What is the value of the tallest bar?` or the corresponding shortest-bar question. Pillow renders a white

(a) Reading, subtraction and composed arithmetic

Rendering	Model	Read (N/E)	Subtract (N/E)	Compose (N/E)
Table	Qwen 8B	100.0 / 100.0	97.5 / 100.0	4.2 / 100.0
Table	Qwen 4B	100.0 / 100.0	90.8 / 100.0	19.2 / 100.0
Table	InternVL 8B	100.0 / 100.0	98.3 / 100.0	98.3 / 100.0
Table	InternVL 4B	100.0 / 100.0	100.0 / 96.7	3.3 / 100.0
Chart	Qwen 8B	100.0 / 100.0	100.0 / 100.0	3.3 / 100.0
Chart	Qwen 4B	100.0 / 100.0	95.8 / 100.0	0.8 / 100.0
Chart	InternVL 8B	100.0 / 100.0	100.0 / 100.0	10.8 / 100.0
Chart	InternVL 4B	100.0 / 100.0	100.0 / 100.0	0.0 / 100.0

(b) Composed arithmetic with an exact transcription

Input	Instruction	Qwen 8B	Qwen 4B	InternVL 8B	InternVL 4B
Image	direct (N)	4.2	19.2	98.3	3.3
Image	explain (E)	100.0	100.0	100.0	100.0
Accurate text, no image	direct (G)	6.7	1.7	$\times$	1.7
Accurate text, no image	explain (G_E)	100.0	100.0	100.0	100.0
Accurate text + image	direct ($G2$)	22.5	21.7	28.3	3.3

Table 25: **Accurate entries still require computation.** Greedy Direct/CoT accuracy (%) on 120 base images per rendering/checkpoint; question levels share images but vary both operations and wording. Text is supplied by the renderer. IV8 text-Direct is invalid (49.2% parseable); other arms are valid. This greedy protocol differs from sampled routing in Table 9.

768×512 RGB image with a plot spanning $x = 64$–736 and $y = 40$–456, a 0–100 vertical scale and ticks every 20 units. Bars are 28 pixels wide; centers are spaced 44 pixels apart in the compact condition and 78 in the wide condition. Each value appears above its bar and each category label below the axis. DejaVu Sans sizes are 18 pixels for values/labels and 16 for ticks. Bar colors are sampled from five fixed RGB colors, $(164, 188, 211)$, $(199, 181, 210)$, $(175, 202, 181)$, $(221, 192, 160)$ and $(175, 201, 210)$.

Scene-specific seeds are the first eight hexadecimal digits of SHA-256 applied to `synthetic-diagnostic-scaling-v1|scene|`*scene ID*. The frozen inventory includes each value, label order, color, target, bounding box and image hash, together with the font and generator. New scenes exclude previous project images and value/order combinations; this construction does not test overlap with model pretraining data.

Populations and qualification. Source eligibility requires a valid trace and two absent same-width donors passing tokenizer/boundary checks. Grouping further requires nonempty A/O sets. Of InternVL's 795 source-eligible traces, 736 contain no Other digits, leaving 59 grouping cases. The primary analysis includes every source-eligible trace regardless of its mask responses (Table 26). Recovery uses the four-arm pattern; neither model reaches the planned 100-scene recovery precision target.

Model	Frozen scenes	Source S	Grouping M	Recovery R
Q8	800	800	793	66
IV8	800	795	59	2

Table 26: **Analysis populations are not interchangeable.** Both models use the same frozen 800-scene inventory. S is the primary source population, M the grouping population, and $R \subseteq M$ the recovery subgroup. Counts are scenes, not donor interventions.

Donor following and uncertainty. Donors are averaged within scene before resampling, retaining invalid/truncated responses in the denominator. The four primary S effects have positive 98.75% Bonferroni-adjusted lower bounds (Table 27); subgroup intervals are descriptive. Qwen has zero

Synthetic extreme-value reading

Qwen3-VL-8B

Question. What is the value of the shortest bar? **Ground truth:** 10



Original CoT excerpt
"Bar A has a value of 10."

Blank image; all digit keys blocked

Original masked output (**U**): **10**

Source edit	Output P	Output V
10 → 70	70	70
10 → 30	30	30

P: edit source digits.
V: transfer nonnumeric values; keep text.

Figure 4: **A controlled source-transmission example.** In one selected scene, outputs follow both substituted values despite blocked digit access; transfer at nonnumeric positions preserves this effect with the original text. These are donor-following responses, not accuracy gains. Cohort frequencies are reported in Table 2b.

naturally wrong source answers and InternVL 11, so these results chiefly measure transmission of edited values.

Model	Set	n	Arm	Match	Cross	Difference [95% CI]	98.75% CI
Q8	S	800	P	6.44	1.13	+5.31 [+4.12, +6.56]	[3.88, 6.94]
Q8	S	800	V	4.81	1.25	+3.56 [+2.56, +4.62]	[2.31, 4.88]
Q8	R	66	P	5.30	0.00	+5.30 [+2.27, +9.09]	[1.52, 10.61]
Q8	R	66	V	6.82	0.76	+6.06 [+2.27, +10.61]	[1.52, 11.36]
Q8	source_wrong	0	P	—	—	—	—
Q8	source_wrong	0	V	—	—	—	—
IV8	S	795	P	1.70	0.44	+1.26 [+0.75, +1.89]	[0.57, 2.08]
IV8	S	795	V	1.38	0.44	+0.94 [+0.50, +1.51]	[0.38, 1.64]
IV8	R	2	P	25.00	0.00	+25.00 [+0.00, +50.00]	[0.00, 50.00]
IV8	R	2	V	25.00	0.00	+25.00 [+0.00, +50.00]	[0.00, 50.00]
IV8	source_wrong	11	P	9.09	4.55	+4.55 [+0.00, +13.64]	[0.00, 18.18]
IV8	source_wrong	11	V	4.55	4.55	+0.00 [+0.00, +0.00]	[0.00, 0.00]

Table 27: **Source transmission beyond recovery-selected cases.** Match/cross rates are percentages; differences and intervals are percentage points. The two donor continuations are paired within scene. S: source-eligible; R: recovered; source_wrong: naturally wrong source answer. Dashes denote an empty stratum, not a zero effect. Adjustment applies to the four prespecified S effects.

Masking, correctness and technical controls. Blank-input joint-only disruption/recovery occurs in 8/793 and 66/793 Qwen scenes, and 0/59 and 2/59 InternVL scenes. With real images, native/A/O/U retention is 100/98.49/100/100% for Qwen and 100% throughout for InternVL. Source and gold outcomes are recorded separately; both models pass self-transfer, prefix-state, tokenizer-boundary and raw-tensor checks, with exclusions/continuations retained. Direct/CoT accuracy over 800 scenes is 99.875/100.000% (Qwen) and 99.125/98.625% (InternVL). InternVL reasons in 716 Direct responses, preventing a clean no-CoT comparison. This greedy reading protocol is separate from sampled computation/localization.

D PUBLIC-TASK EXTENSIONS AND SENSITIVITY ANALYSES

D.1 INDEPENDENT REAL-IMAGE CONFIRMATION ON NATURAL ERRORS

A new ChartQA train-only pool contains 6,000 distinct images with one numerical question each. Greedy Qwen3-VL-8B CoT produces 5,619 usable numerical answers, including 1,060 errors under the fixed scorer. The existing source-construction rules admit 551 errors. We select 400 by the hash order fixed before intervention outputs, then freeze both replacements for each source. Eligibility retains the original integer, token-boundary, lexical-matching and absent-replacement requirements. This cohort is separate from the 36-image development cohort below.

All eight conditions retain the original image and use the source-editing and value-transfer operators in Section B.7. The 512-token continuation budget includes the fixed prefix. Two disjoint execution shards each cover 200 images and 1,600 continuations. Every continuation terminates normally and yields a usable numerical answer. Native continuation retains the original numerical answer on all 400 images and reproduces its token sequence on 399; all 400 remain in the analysis. Self-transfer and numerical masking give the same numerical answers on every image.

Table 28: **Real-image interventions on 400 initially incorrect CoT answers.** Qwen3-VL-8B on the independent ChartQA cohort. Accuracy and retention use all 400 source errors. Source editing and nonnumeric transfer each have two donor continuations per image; donor following is distinct from accuracy.

(a) Real-image continuations, Qwen3-VL-8B ($n = 400$)

Arm	Accuracy (%)	Source retained (%)	Corrections vs. U	Harm vs. U
Native	0.00	100.00	0	36
U	9.00	67.25	0	0
Self	9.00	67.25	0	0
Whole trace	21.75	39.75	56	5
P1	10.50	54.25	10	4
P2	11.25	55.75	12	3
V1	9.25	58.50	5	4
V2	10.75	58.50	9	2

(b) Donor-specific influence under the all-digit mask

Intervention	Matched	Unused	Difference (pp)	97.5% CI
P	17/800	0/800	2.13	[0.88, 3.63]
V	3/800	0/800	0.38	[0.00, 0.88]

Corrections and harm count changes in correctness relative to U.

The two donor contrasts are averaged within image before resampling. Each primary P/V effect uses 20,000 image-bootstrap draws with seed 3653870015 and a 97.5% interval. Source editing has a positive lower bound, whereas the value-transfer interval includes zero. The prespecified criterion requiring both positive lower bounds is therefore not met. Positive editing effects occur on 13 images and positive transfer effects on three, with no negative image effects. Both effects are positive on the same three images (0.75%); its descriptive exact binomial intervals are [0.15,2.18]% at 95% and [0.12,2.41]% at 97.5%. The joint event was specified in the protocol; these two interval levels are reporting choices.

The three positive transfer images each follow one of their two replacements. Their questions ask for a segment ratio, a previous-month tax amount and a percentage. The first two have one-digit source answers and the third has a two-digit answer. Across all 400 sources, 39 have one digit, 160 have two, and 201 have three to eleven. This post-review description does not calibrate the probe's sensitivity. For example, in the ratio case, transferring replacement 2 yields 24, while transferring replacement 9 yields 9; only the latter counts as exact magnitude following. Responses that change without matching either replacement lie outside this endpoint. The full three-case profiles and complete width distribution accompany the saved records.

Whole-trace masking produces 56 corrections and five regressions relative to numerical masking, increasing conditional accuracy from 9.00% to 21.75%. This comparison changes the attended key set as well as trace access. The source-identity contrasts separately test

transmission of a particular replacement through the remaining states. The accompanying `reproducibility/natural_error_confirmation_400/` records preserve all images, donor outcomes and scoring definitions.

D.2 Development cohort of natural errors

Qwen3-VL-8B produces 73 incorrect answers among 492 usable numerical sources on 526 ChartQA images, selected by a fixed one-question-per-image rule from 800 questions. Source construction admits 36 errors (49.3%), excluding 26 noninteger answers, seven insufficient lexical controls, two traces without source-answer digits, one unsupported numerical format and one lacking two replacements. Eligibility precedes intervention outputs. Errors can reflect perception, answer selection or numerical representation.

The eight conditions in Table 29 use the source construction and state-transfer protocol of Section B.7, retaining the original image throughout. Cases and replacements remain fixed. Native continuation reproduces the saved answer tokens on all 36 images; all 288 outputs terminate normally and parse, and self-transfer matches numerical masking. An initial timing run used the first three formal cases rather than disjoint materials. The formal cohort and replacements were unchanged; the evaluation uses previously exposed images.

Table 29: **Natural-error extension with real images.** Qwen3-VL-8B on 36 ChartQA source errors. Rates use all 36 images. P edits source digits; V transfers the edited run's nonnumeric values. Two replacements run separately; P and V each have 72 continuations. Intervals use 20,000 paired image-bootstrap samples and cover the two primary comparisons at 97.5% each.

Condition	Source retained (%)	Accuracy (%)	Corrected vs. U	Regressed vs. U
Native	100.0	0.00	0	2
All digits blocked (U)	72.2	5.56	0	0
Self-transfer	72.2	5.56	0	0
Whole trace blocked	38.9	13.89	4	1
Edit P1	69.4	8.33	1	0
Edit P2	72.2	5.56	0	0
Transfer V1	72.2	5.56	0	0
Transfer V2	72.2	5.56	0	0

Intervention	Used (%)	Unused (%)	Difference (pp)	97.5% interval
Source editing (P)	2.78	0.00	+2.78	[0.00,11.11]
Nonnumeric transfer (V)	2.78	0.00	+2.78	[0.00,11.11]

Figure 5 shows the sole case driving both source effects. Whole-trace masking reduces source retention by 12/36 relative to numerical masking, but changes both access and attention normalization. Its four corrections and one regression describe observed outcomes; the contrast alone does not identify the information sustaining an error.

Sensitivity and analysis checks. A prior annotation review identifies two hundredfold-scale candidates in this cohort. Excluding both leaves 34 cases and P/V effects of +2.94 pp [0.00,11.76], again driven by the same image. Signed identity agrees with magnitude identity. Numerical exact matching agrees with tolerance scoring on all 288 outputs. Bootstrap settings, per-item predictions and scoring checks accompany the saved-output export.

D.3 Other tasks and prompts

ChartQA/CountBench use the same eight arms on 200 preselected, previously exposed images. Applicability is 174/187 (Q8/IV8), common 167, for ChartQA and 97/129, common 77, for CountBench. Both fail the 90% coverage requirement. No numerical trace tokens occur in 102/103 Q8 and all 71 IV8 CountBench exclusions, making the estimand conditional on written numbers.

Both ChartQA pilots exactly reproduce all 14 applicable source answers under real-image native continuation. Two inputs per model were excluded before generation, so neither meets the

A natural reading error

ChartQA · Qwen3-VL-8B

Question. What value is the tiniest bar?



○ **Gold: 4%** ○ **CoT: 6%**

Original CoT excerpt
"the smallest bar is the gray bar in the "Not sure" category, which is labeled with 6%."

All digit keys blocked
Original masked answer: **6%**

Replacement	3	5
Edit digits	**3**	**5%**
Transfer states	**3**	**5%**

Original image visible in every run.

Figure 5: **Source transmission with a natural error and the original image.** CoT selects 6% instead of the minimum 4% (circled). With digit access blocked, source editing and nonnumeric transfer induce following of both replacements; transfer retains the original text. This is the sole nonzero identity-effect case among 36 images. Both cohort-level intervals include zero.

Task	Model	Image	Native	Numeric	Lexical	Whole trace
ChartQA	Q8	Real	80.24	73.05	80.24	61.08
		Blank	82.04	52.10	82.04	5.39
	IV8	Real	85.63	75.45	85.03	74.25
		Blank	83.83	48.50	83.83	9.58
CountBench	Pooled	Real	69.48	72.08	69.48	75.97
		Blank	68.18	54.55	68.18	0.00

Table 30: **Descriptive extensions: absolute accuracy (%).** Each task uses its common applicable set; CountBench averages models within image.

frozen 15/16 reproduction criterion. CountBench pilots reproduce every applicable source (9/10 for Q8/IV8), and native/lexical correctness agrees in 450/452 model-specific pairs. Qualification and coverage shortfalls keep both extensions descriptive.

ChartQA has $J = +24.25$ pp [17.37,31.44] and a real-image change of -8.68 [-12.87,-4.79]. CountBench has $J = +16.23$ [10.39,22.73] and a real-image change of +2.60 [0.00,5.84]. All are paired 95% intervals.

ChartQA grouping uses 126 shared images, excluding answer magnitudes in question text. Blank persistence [native,A,O,union] is [97.62,66.67,98.81,36.11]%, pooled across models; Table 14 gives the interactions. Q8/IV8 show 45/40 joint-only and 3/5 reverse changes under the same scoring rules.

Errors in the source trace. Among ChartQA's 23/15 scorer-defined source errors, real-image joint-only changes number 8/4, with 1/0 corrections. Blank-image changes number 8/5, all to other valid wrong answers; all four outputs are usable. CountBench has no A/O arms: numerical masking on 77 common real-image items gives 2/0 and 3/1 corrections/regressions (Q8/IV8).

Annotation sensitivity. Annotation sensitivity excludes three hundredfold-scale candidates per model, `0199`'s reversed above/below condition and ambiguous `0237`. Exclusions are identical

under real/blank input and do not rescore the outputs (Table 31). Exact case details and image identifiers accompany the export.

Retained source errors	n (Q8/IV8)	Real joint change	Blank joint change
All scorer-defined errors	23/15	8/4	8/5
Exclude scale candidates	20/12	7/3	7/4
Exclude 0199	22/14	7/3	7/4
Exclude 0199 and scale candidates	19/11	6/2	6/3
Also exclude ambiguous 0237	18/10	5/1	5/2

Table 31: **Joint-only changes survive annotation exclusions.** Counts use real/blank masks on the same source-error subset. Every row retains one Q8 real-image correction and zero IV8 or blank-image corrections.

Source errors include both perception and answer selection: `chartqa-0949` misreads 13 as 15, whereas `0602` states gold year 2016 but returns 70.5. Only the former is corrected by the union mask.

Requesting a written count. Adding "and state the count you obtained as a number" raises shared CountBench applicability to 134/200 (Q8 150, IV8 177). The same prompt generates sources/continuations on the unchanged 200-image list, with a disjoint 16-image pilot, 256-token source cap and 512-token total budget. Both models fail the 95% coverage threshold; Q8's J interval includes zero, failing the two-model positive-interval requirement. Table 32 reports this separate descriptive condition.

(a) Accuracy on each model's applicable images (%)

Model (n)	Image	Native	Numeric	Lexical	Whole trace
Q8 (150)	Real	79.33	80.00	79.33	88.67
	Blank	79.33	76.67	79.33	0.00
IV8 (177)	Real	70.62	70.62	70.62	75.14
	Blank	68.93	55.93	68.93	0.00

(b) Image interaction and accuracy change (pp)

Model	Applicable / planned	J [95% CI]	Δ [95% CI]
Q8	150/200	+3.33 [0.00,6.67]	+0.67 [−2.00,3.33]
IV8	177/200	+12.99 [7.34,18.64]	0.00 [−3.39,3.39]
Pooled	134/200	+8.21 [4.48,12.31]	+0.75 [−1.87,3.36]

Table 32: **A count-explicit prompt increases applicability without a confirmed accuracy gain from numerical masking.** The pooled row averages models within shared images. Intervals use 20,000 paired image-bootstrap replicates. This condition changes the prompt and source trace; it does not add observations to the natural-CoT cohort.

IV8's zero real-image effect combines four corrections and four regressions; all 654 native/lexical correctness pairs agree. Missing parse/EOS records prevent separating numerical errors from invalid responses. Source-cap hits number 11/1. On 85/123 images shared with natural CoT, J changes by -5.88 [-12.94,1.18]/+1.63 [-5.69,8.94] pp and Δ by -2.35 [-7.06,2.35]/0.00 [-4.88,4.88]. These combine prompt and trace changes and do not establish equivalence.

Native thinking. GLM compares thinking-off Direct/CoT (N/E) with thinking-on Direct (H) on confirmation positions 101–300, excluding pilot/readout images. Each uses greedy decoding and one user message, with the budget in Section A. Parsing accepts one finite post-thinking answer, including native/nested wrappers; illegal/non-EOS outputs are wrong out of 200. Primary $H - N$ intervals use 97.5% Bonferroni adjustment across the two tasks.

(a) Absolute accuracies (%)

Subset	N real	E real	H real	N blank	N mismatch
DVQA	93.5	91.0	94.0	2.5	9.0
TabMWP	70.0	93.5	99.0	10.0	10.5

(b) Paired mode effects

Subset	Contrast	CI level	Δ (pp)	Interval	Corr. / reg.
DVQA	$H - N$ (primary)	97.5%	+0.5	[-2.5, +3.5]	4 / 3
DVQA	$E - N$	95%	-2.5	[-5.5, +0.5]	2 / 7
DVQA	$H - E$	95%	+3.0	[+1.0, +5.5]	6 / 0
TabMWP	$H - N$ (primary)	97.5%	+29.0	[+22.0, +36.5]	58 / 0
TabMWP	$E - N$	95%	+23.5	[+17.5, +30.0]	49 / 2
TabMWP	$H - E$	95%	+5.5	[+2.0, +9.0]	12 / 1

Table 33: **GLM native-mode evaluation.** All five absolute accuracies and paired primary/secondary contrasts. Different templates and caps preclude an unqualified cross-model comparison.

On DVQA, explicit CoT causes five new unusable outputs, two corrections and two regressions. Native thinking corrects 58 TabMWP answers without regression. Strict-wrapper Direct scores 45.5%, versus exact-numerical Direct/native 67.5/99.0%. Native real-image outputs are nonempty and uncapped. Mean N/E/H tokens are 10.2/89.0/134.3 (DVQA) and 9.8/125.7/234.5 (TabMWP), so mode effects include added computation.

D.4 Other tested explanations

Independent ChartQA read/compute classification yields CoT-effect interactions $-7, 0, -1, -9$ pp (Q8/Q4/IV8/IV4), pooled -4.25 $[-8.74, -0.06]$, opposite the prediction. A headroom-based prediction also fails its held-out criterion; neither supports task-level routing.

Correct/wrong/neutral hints on 200 ChartQA items meet content specificity in one of four checkpoints; correct hints use oracle gold. Spatial/head effects lose their advantage under dose matching. Intact-model selected-head replacement changes 0/58 answers; necessity checks pass 0/5. Invalid self-replacement is excluded. These tests establish no semantic mechanism for the fixed-prefix effects.

E Gate: specification, evaluation and cost

Prediction and selection. Vote and Gate share three CoTs sampled at temperature 0.7, following self-consistency (Wang et al., 2023). Gate retains a valid unanimous answer. On disagreement, it generates Direct from the original image and question without those CoTs, then predicts whether replacement is beneficial. For valid, distinct candidates, ridge regression estimates the difference in correctness,

$$z_i = \mathrm{correct}(\hat{y}_{\mathrm{Direct},i}) - \mathrm{correct}(\hat{y}_{\mathrm{Vote},i}), \tag{1}$$

where correctness follows the task's scoring rule. Gate chooses Direct when the predicted gain is positive and Vote otherwise. Features describe response agreement, numerical dispersion, output lengths and lexical cues, together with task, model and task–model identity. Correctness labels supervise fitting but are absent from the predictor's inputs. Invalid Direct preserves Vote; valid Direct replaces invalid Vote. The VLM weights remain fixed.

Inputs and fixed decisions. Equation 1 applies to numerical QA and single-axis localization. Responses are finite normalized scalars. Localization Vote already requests Direct when fewer than two valid samples agree; Gate preserves that endpoint.

Features and fitting. The 35 response features are defined in Table 34; one-hot task, model and task–model identities are appended. The five-model, six-task fitting set adds 33 indicator columns, giving 68 inputs. Pixels, image identifiers, gold answers and activations are excluded; image hashes serve grouping only.

Feature group	Count	Definition
Validity and agreement	7	Valid CoT count, distinct valid values, largest vote count, Direct/Vote validity, number of CoTs matching Direct, and Direct–Vote agreement.
Numerical dispersion	3	Range and standard deviation of valid CoT values, and absolute Direct–Vote distance, each divided by $s = \max(1, \lvert n\rvert, \lvert e_1\rvert, \lvert e_2\rvert, \lvert e_3\rvert)$ over valid values.
Response lengths	6	$\log(1+T_n)$ and $\log(1+\text{mean}/\text{min}/\text{max}(T_e))$; CoT token-count coefficient of variation and Direct/mean-CoT token ratio, capped at 10.
Question length	1	$\log(1+$ question character count$)$.
Lexical cues	14	Presence in the question and fraction of CoTs containing each of seven cue types: counting, arithmetic, comparison, location, reading, uncertainty and correction.
Character densities	4	Fractions of digit characters and equality signs in the question and averaged across the three CoTs.

Table 34: **Gate's 35 response features.** n is the Direct value, e_i a CoT value and T a generated-token count. Empty valid-value sets yield zero dispersion; missing candidate values are zero only in distance calculations and have separate validity indicators. Lexical patterns and exact normalization are included in the exported feature function.

Fitting uses non-unanimous items with a valid Direct answer different from Vote, including invalid Vote. At inference, invalid Vote selects valid Direct deterministically; the regressor chooses between valid, distinct candidates. Standardization uses training data only, with inverse cell-size weights. Three inner folds choose ridge strength $0.01, 0.1, 1, 10$ by macro accuracy, preferring stronger regularization on ties. Five outer folds hold out 3,051 image/scene-pair groups jointly across tasks/models and localization views. The 12,784 records contain 12,592 public and 192 location records. Reported predictions use outer-fold fits.

Baselines. The prior estimates mean Direct-minus-Vote correctness in each training task/model cell. No ID removes identity indicators but retains all 35 response features. Table 35 reports 22 cells; public and localization macro averages remain separate.

Arithmetic: protected and predicted decisions. On 120 items per rendering, Q8/Q4/IV8 produce 720 unanimous correct triples. The protected branch returns Vote without Direct or fitted coefficients, preserving 100% in six cells. This checks branch behavior rather than learned generalization. The frozen selector also evaluates 120 stored triples per rendering for IV4 and Qwen2.5, with 12 non-unanimous items across these four cells. Gate matches Vote's 99.17–100% accuracy, versus CF's 95.00–98.33%; no correct votes are spoiled or wrong votes corrected. All 480 triples have a two-vote majority, so arithmetic and exported-router tie rules agree. These cells and image hashes are absent from fitting, but this retrospective application remains outside the original grouped macros. Saved routing inputs and decisions are exported.

Recorded examples in Figure 3. The two decisions in Figure 3 are replayable offline. The TabMWP example `ct-tabmwp-11076` has three correct answers of 489; the unanimity branch preserves them, whereas the independent Direct baseline gives 695. The MathVista example `mv-453` has samples 5/6/6 and Direct 4; its saved outer-fold predictor (fold 4) assigns gain +0.168 and selects correct Direct over Vote 6. The line spans ruler marks 1–5, and measuring its length involves both locating endpoints and taking their difference. Each figure panel uses a single crop of the original image and an abbreviated question. Original images, exact prompts, full responses and the saved fold model accompany the export in `reproducibility/gate_case/`. Examples are selected retrospectively. Figure 8 includes the recorded Word Direct/single-CoT comparison; it does not show a learned Gate decision.

Frozen-selector extensions. Frozen extensions cover Q4/IV4 on DVQA/TabMWP (800 images each) and Qwen2.5 on CountBench (490), MathVista (457) and localization (64). The new localization cell yields 2/64 (3.13%) for Direct/Vote/CF/Gate and 5/64 (7.81%) for CoT. Gate changes three CF answers without improving accuracy. These model/task cells were absent from fitting, but

Task	Model	n	Direct	Vote	CF	Prior	No ID	Gate	Cost
chartqa	IV4	800	72.13	73.38	74.25	73.25	75.13	76.00	1.01
chartqa	IV8	800	74.63	85.75	82.63	86.38	85.63	86.38	1.01
chartqa	Q4	800	64.38	81.00	80.13	81.75	82.88	82.50	1.00
chartqa	Q8	800	68.13	82.13	82.38	82.50	84.38	84.25	1.00
chartqa	Qwen2.5-7B	800	74.00	81.50	79.88	82.13	82.38	82.63	1.00
countbench	IV4	490	72.24	72.24	73.47	73.47	73.67	73.47	1.00
countbench	IV8	490	67.55	71.63	70.82	73.06	72.24	72.24	1.21
countbench	Q4	490	76.33	76.12	78.16	78.16	79.39	78.78	1.00
countbench	Q8	490	78.78	78.16	81.02	81.22	80.20	81.43	1.01
dvqa	IV8	800	78.88	91.50	90.50	91.63	91.00	91.63	1.01
dvqa	Q8	800	94.50	91.25	93.00	93.00	92.75	92.63	1.00
dvqa	Qwen2.5-7B	800	95.88	91.13	94.88	94.88	94.88	94.88	1.00
mathvista	IV4	458	55.46	63.97	63.97	63.32	66.59	66.81	1.02
mathvista	IV8	458	60.48	67.47	66.38	68.34	67.90	68.12	1.20
mathvista	Q4	458	57.42	65.94	67.25	67.47	68.12	69.00	1.01
mathvista	Q8	458	59.83	69.43	70.31	70.31	71.18	71.62	1.01
Location	IV4	64	95.31	70.31	92.19	92.19	92.19	92.19	1.01
Location	Q4	64	85.94	78.13	87.50	87.50	87.50	87.50	1.01
Location	Q8	64	60.94	46.88	57.81	57.81	57.81	57.81	1.01
tabmwp	IV8	800	84.88	96.63	95.13	97.25	97.13	97.25	1.08
tabmwp	Q8	800	78.00	99.13	97.38	99.13	99.13	99.13	1.00
tabmwp	Qwen2.5-7B	800	72.88	93.38	90.75	93.38	92.75	92.75	1.00

Table 35: **All learned Gate evaluation cells.** Accuracy (%). CF: consistency fallback; Prior: conditional task/model prior; No ID: Gate without task/model indicators. Cost is staged output-token count relative to Vote, including Direct generation on disagreement. Location Vote's own Direct fallback is included. These are grouped out-of-fold results on exposed development data.

		Public benchmarks					Synthetic
Model	Setting	DVQA	CountBench	ChartQA	TabMWP	MathVista	Localization
Qwen3-VL-8B	Fixed fallback	**93.00**	81.02	82.38	97.38	70.31	**57.81**
	Gate	92.63	**81.43**	**84.25**	**99.13**	**71.62**	**57.81**
Qwen3-VL-4B	Fixed fallback	**91.63**	78.16	80.13	98.13	67.25	**87.50**
	Gate	91.50	**78.78**	**82.50**	**98.50**	**69.00**	**87.50**
InternVL3.5-8B	Fixed fallback	90.50	70.82	82.63	95.13	66.38	×
	Gate	**91.63**	**72.24**	**86.38**	**97.25**	**68.12**	×
InternVL3.5-4B	Fixed fallback	**92.13**	**73.47**	74.25	88.88	63.97	**92.19**
	Gate	**92.13**	**73.47**	**76.00**	**91.25**	**66.81**	**92.19**
Qwen2.5-VL-7B	Fixed fallback	**94.88**	**78.78**	79.88	90.75	**64.55**	**3.13**
	Gate	**94.88**	77.76	**82.63**	**92.75**	**64.55**	**3.13**

Table 36: **Per-model comparison with fixed fallback.** Accuracy (%) on identical candidates. Frozen-selector extensions are listed separately from the 19-pair grouped analysis; × marks the invalid localization control.

images may occur via other models; they are excluded from the 19-cell grouped macro averages. CF uses identical candidates.

Development history and generalization. Gate was developed after the public-task results, the Qwen3-VL-2B/DVQA check and a failed transfer from public tasks to localization. Public-only fitting scores 46.88/79.69/70.31% on Q8/Q4/IV4 location, below CF's 57.81/87.50/92.19%. The final version adds existing localization records without changing features, threshold or regularization choices. Grouping prevents fold-level image overlap, but design exposure makes the evaluation retrospective.

On Qwen3-VL-2B/DVQA, frozen Gate scores 90.625%, versus Direct/Vote/CF 88.625/88.250/90.500%. Its labels are excluded from fitting, but its images and earlier aggregate result were exposed. This is cross-model evaluation on familiar images.

Intervals and costs. Intervals resample global images or localization pairs 4,000 times conditional on fitted folds; development and refitting uncertainty are excluded. Beyond the main-text contrasts, Gate beats the prior by +0.57 [0.30,0.86] pp and No ID beats Vote by +1.35 [0.94,1.76]. Cost includes Direct on disagreement even when Vote is selected, excluding input processing and orchestration.

E.1 Agreement and answer-quality controls

All controls use the original candidates and five outer folds. No-majority fallback retains a valid answer supported by at least two CoTs and otherwise uses Direct. The tuned agreement rule chooses a maximum-vote-count threshold from 0, 1 or 2 separately for each task/model pair, maximizing training-fold accuracy with ties favoring the smaller threshold. Valid unanimity and invalid-candidate handling are shared with Gate.

The simple answer scorer is a shared logistic classifier that estimates Direct and Vote correctness separately. Its six features are candidate support among the three CoTs, log token count, normalized distance to their median, mean normalized distance to their values, a Direct indicator and candidate validity. The larger score determines the answer; ties retain Vote. Standardization uses training candidates only, and three inner image-grouped folds select L2 strength from 0.01, 0.1, 1 and 10.

The matched answer scorer uses Gate's complete 68-dimensional input instead. Let x denote the standardized vector and c indicate a Direct candidate. The shared classifier receives $[x, c, cx]$ and minimizes weighted binary log loss on candidate correctness. Paired candidates remain in the same fold. Training rows, weights, standardization and outer folds match Gate, while three inner folds select regularization by policy macro accuracy; ties favor stronger regularization. Its macro accuracy is 82.08%, compared with Gate's 82.18%, with a paired difference of 0.10 $[-0.01,0.21]$ points. Table 37 reports all controls, including the simpler scorer. Recorded choices, coefficients and CPU reproduction code accompany the paper.

Method	Accuracy (%)	Gain over Vote (pp)	Gate − method [95% CI]
Vote	80.62	0.00	+1.57 [1.15, 1.98]
Fixed fallback	80.64	+0.03	+1.54 [1.19, 1.89]
Task/model prior	81.61	+0.99	+0.57 [0.30, 0.86]
Agreement threshold	81.71	+1.09	+0.47 [0.20, 0.76]
Matched answer scorer	82.08	+1.46	+0.10 [-0.01, 0.21]
Simple answer scorer (6 features)	81.45	+0.84	+0.73 [0.45, 1.04]
No-majority fallback	81.45	+0.83	+0.74 [0.41, 1.09]
Gate without task/model IDs	81.96	+1.35	+0.22 [0.03, 0.41]
Gate	**82.18**	**+1.57**	—

Table 37: **Selection controls on identical public-task candidates.** Equal-weight macro averages over 19 task/model pairs. Intervals use the same global image-cluster resampling as the primary Gate analysis.

E.2 Frozen evaluation on 600 ChartQA images

We evaluate Qwen3-VL-8B and InternVL3.5-8B on the same 600 ChartQA validation images, with one numerical question per RGB-unique image. Encoded-image and RGB identities exclude registered project inputs, including previous Gate data and the 6,000-image source pool. A fixed hash order reserves 16 separate pilot images before selecting the formal cohort. Gate, Matched and Agreement are frozen before new generation, with all fitting and parameter selection confined to the existing 12,784 development records. The new pilot and formal labels are not used for fitting or tuning.

Each image receives one greedy Direct response and three independently seeded CoTs sampled at temperature 0.7, top-$p = 1$ and repetition penalty 1, with a 512-token cap per response. CoT in Table 38 denotes the first sampled response; all selection methods share the same candidates. Scoring follows Section A, retaining invalid and truncated answers as incorrect among all 600 images per model. CF uses the fixed non-unanimity fallback. Matched is the answer-quality scorer defined above, with regularization 0.01; Agreement uses the development-selected vote-count threshold, which is zero for both checkpoints. Their valid-unanimity and invalid-candidate rules remain fixed.

(a) Accuracy (%)

Method	Qwen3-VL-8B	InternVL3.5-8B	Mean
Direct	76.00	85.67	80.83
CoT	77.00	86.50	81.75
Vote	80.00	86.67	83.33
CF	81.00	**87.83**	84.42
Agreement	81.83	86.83	84.33
Matched	**83.00**	87.00	**85.00**
Gate	**83.00**	87.00	**85.00**

(b) Paired differences in the two-model mean

Comparison	Difference (pp)	97.5% interval
Gate − CF (primary)	+0.58	[−0.67, +1.83]
Gate − Vote	+1.67	[+0.83, +2.58]
Gate − Agreement	+0.67	[+0.17, +1.33]
Gate − Matched	0.00	[0.00, 0.00]
Gate − Direct	+4.17	[+2.00, +6.33]

Table 38: **Frozen selectors on ChartQA validation images.** Accuracy uses 600 images per model; Mean weights the two checkpoints equally. CF is fixed fallback, Agreement is the tuned vote-count rule, and Matched predicts candidate correctness using Gate's full feature set. Paired intervals resample shared images.

The primary contrast first averages Gate-minus-CF correctness within image over the two fixed models, then averages across images. We use 20,000 paired image-bootstrap resamples with seed 20260925 and 97.5% intervals. The prespecified superiority hypothesis over CF is not supported: the mean difference is +0.58 pp [−0.67,1.83]. Gate improves over CF on Qwen but trails it on InternVL. Its mean gains over Vote and Agreement are +1.67 [0.83,2.58] and +0.67 [0.17,1.33] pp. Gate and Matched have identical per-image correctness outcomes for both models, each reaching 85.00% mean accuracy. They choose different candidates on one of the 1,200 records. For InternVL item `chartqa-val-frozen-0011`, Gate retains 25 and Matched selects 43; both are wrong against the gold answer 37.

Candidate collection makes four model calls for every image and checkpoint, regardless of the evaluated policy. Staged policy accounting separately counts only the candidates a policy would request, including Direct on non-unanimity for Gate; it is not the actual four-call acquisition cost. No source-state interventions were performed on this cohort. The export retains every raw response and the parser/selector code needed to recompute the reported policy outcomes.

E.3 Holding out an entire benchmark

For each of the five numerical benchmarks, we hold out all its records and exclude any shared image groups from the remaining training data. Training uses the other public tasks and the controlled localization records. Feature construction, gain target, eligibility rules, cell weighting and candidate handling are unchanged. Three inner image-grouped folds select ridge strength using only the retained training tasks. Each target benchmark is then evaluated once. Table 39 gives the five held-out results; the overall row averages the original 19 task/model cells.

Held-out benchmark	Vote	Fixed fallback	Gate
ChartQA	80.75	79.85	**82.35**
CountBench	74.54	75.87	**76.33**
DVQA	91.29	92.79	**93.21**
MathVista	66.70	66.98	**67.74**
TabMWP	**96.38**	94.42	96.25
Macro average (19 cells)	80.62	80.64	**81.92**

Table 39: **Answer selection on a benchmark excluded from fitting.** Accuracy (%); each benchmark row averages its models. Shared image groups are excluded from the training pool.

Gate reaches 81.92% overall, compared with Vote's 80.62% and fixed fallback's 80.64%. Global image-cluster intervals give gains of 1.30 [0.89,1.71] and 1.27 [0.92,1.62] points, respectively. Task-held-out evaluation tests transfer of the fitted rule within the existing data collection; the development history described above also applies to this analysis.

E.4 Categorical answers and two-dimensional clicks

We extend Gate using cached Direct and three CoT outputs. Eighteen response features describe validity, agreement, output length and normalized coordinate distances. Categorical labels are unordered, with distance features set to zero; task, model and task/model indicators are added. Five outer folds group shared images: 142 VQA-RAD groups, 168 BLINK components linked by shared constituent images, and 200 ScreenSpot scenes shared across models. Three inner folds select ridge strength from 0.01, 0.1, 1 and 10 by mean squared gain error, preferring stronger regularization on ties. Standardization uses training records only.

The valid-unanimity branch and benchmark voting rules remain fixed. ScreenSpot candidates are scored as integer pixel points inside the target box; Vote requires at least two identical points among three valid samples and otherwise uses Direct. This integer-point convention is shared by all selectors in Table 40. The original greedy ScreenSpot references use unrounded points. These four cells are fitted separately and are excluded from the original 19-pair averages.

Task	Model	n	Vote	Fixed fallback	Gate
VQA-RAD	Qwen2.5-VL-7B	200	70.00	**75.00**	**75.00**
BLINK	Qwen2.5-VL-7B	172	56.40	**68.60**	67.44
ScreenSpot-Pro	Qwen3-VL-8B	200	55.00	**57.00**	56.00
ScreenSpot-Pro	Qwen3-VL-4B	200	59.50	**60.50**	59.50

Table 40: **Gate with categorical and two-dimensional answers.** Out-of-fold accuracy (%) on the same cached candidates. n counts questions; shared images are held out together.

The four-cell macro accuracy is 60.22% for Vote, 64.49% for Gate and 65.28% for fixed fallback. Gate matches fixed fallback on VQA-RAD and trails it on the other three cells.

E.5 Fixed fallback and sampling controls

Table 41 separates independent confirmation from exploratory grounding cohorts.

Random fallback replaces Vote with Direct at CF's observed rate f, independently of item identity. Expected accuracy is $(1-f)a_{\text{Vote}} + fa_N$; CF minus this expectation equals $\text{Cov}(B, Z)$, with replacement indicator B and Direct-minus-Vote correctness Z. Each image-bootstrap draw recomputes f, accuracies and products. Marginal intervals condition on the sampled triples; analytical expectations remove routing Monte Carlo noise.

Independent confirmation compares CF with Direct voting, CoT voting and adaptive CoT, which samples a fourth CoT on disagreement and votes over four. CF/adaptive both use $3+f$ calls without exact token matching. The compound criterion fails: pooled DVQA superiority over all three, both

(a) Paired accuracy differences (pp; 95% CI)

Subset	Model	CF − direct vote	CF − CoT vote	CF − adaptive	CF − Random-SC
DVQA	Qwen 8B	-1.50 [-2.63, -0.50]	+1.75 [+0.25, +3.25]	+1.50 [+0.13, +3.00]	+1.34 [+0.10, +2.63]
DVQA	InternVL 8B	+9.13 [+6.88, +11.50]	-1.00 [-2.50, +0.38]	-1.13 [-2.50, +0.25]	+0.28 [-1.01, +1.57]
DVQA	Pooled	+3.81 [+2.56, +5.06]	+0.38 [-0.63, +1.38]	+0.19 [-0.81, +1.19]	+0.81 [-0.11, +1.73]
TabMWP	Qwen 8B	+19.50 [+16.75, +22.25]	-1.75 [-2.75, -0.88]	-1.75 [-2.75, -0.88]	-1.09 [-1.90, -0.32]
TabMWP	InternVL 8B	+6.38 [+4.38, +8.38]	-1.50 [-2.63, -0.38]	-2.00 [-3.25, -0.88]	-0.63 [-1.67, +0.38]
TabMWP	Pooled	+12.94 [+11.00, +14.88]	-1.63 [-2.44, -0.81]	-1.88 [-2.75, -1.06]	-0.86 [-1.56, -0.17]

(b) Grounding: consistency fallback − Vote / matched random fallback

Task	Model	CF − Vote	CF − random fallback
ScreenSpot-Pro	Q8	+2.00 [−0.50, +5.00]	+1.08
ScreenSpot-Pro	Q4	+1.00 [+0.00, +2.50]	+0.03
Synthetic location	Q8	+10.94 [+0.00, +23.44]	+0.39
Synthetic location	Q4	+9.38 [+1.56, +17.19]	+2.17
Synthetic location	IV4	+21.88 [+14.06, +29.69]	+0.78

Table 41: **Replacement benefit and selection value.** Paired accuracy differences (pp; 95% intervals). Confirmation uses 800 independent images per task; pooled rows average models within images. ScreenSpot uses 200 exploratory images; location uses 32 scene pairs. Matched-random comparisons report point estimates only. Cohorts remain separate.

models beating adaptive, and TabMWP noninferiority to voting/adaptive within -2 pp are not jointly met. Random-Vote is secondary and does not replace the specified Random-E_1 test. CountBench's four-model random-control criterion passes in only two models, failing the aggregate requirement. A legacy recovery ratio uses sampled rather than prespecified greedy CoT and is excluded.

Task	Model	Accept %	Wrong %	Calls	Vote tokens	consistency fallback tokens
DVQA	Q8	87.50	3.75	3.13	536.03	536.97
	IV8	89.88	4.63	3.10	320.90	323.39
TabMWP	Q8	96.88	0.25	3.03	509.82	510.11
	IV8	92.63	0.50	3.07	361.49	389.54
ScreenSpot	Q8	8.00	1.50	3.92	—	—
	Q4	3.00	0.00	3.97	—	—
Location	Q8	25.00	14.06	3.75	384.44	389.44
	Q4	7.81	0.00	3.92	844.27	848.80
	IV4	15.63	4.69	3.84	393.19	397.41

Table 42: **Acceptance, stable errors and measured token cost.** Wrong denotes accepted-and-wrong answers as a percentage of all items, not accepted items. Calls include the three sampled CoTs and Direct fallback; dashes are unmeasured costs.

Increasing the number of samples does not uniformly improve CF. On DVQA/IV8, $K = 5$ yields 89.00% for CF versus 92.50% for Vote. The full $K = 2, 3, 5$ matrix is retained in `extended_results.json`; these comparisons reuse cohorts and sample prefixes rather than providing independent confirmation.

F RECORDED BENCHMARK EXAMPLES

These Qwen3-VL-8B examples illustrate contrasting responses. All panels use recorded inputs and outputs; selected cases do not estimate prevalence.

Public benchmarks: reasoning supports computation

ChartQA

Qwen3-VL-8B



Question. What is the sum of 2002, 2003 and 2004?

Ground truth: 70.4

Direct: 65.4 (wrong)
CoT: 70.4 (correct)

CoT excerpt

"I then sum these values: 19.4 + 23.2 + 27.8 = 70.4."

TabMWP

Qwen3-VL-8B

finch | $183
pot-bellied pig | $130
king snake | $264
hedgehog | $196
bearded dragon | $176

Question. How much money does Mia need to buy a bearded dragon, a pot-bellied pig, and a finch?

Ground truth: 489

Direct: 695 (wrong)
CoT: 489 (correct)

CoT excerpt

"$306 + $183 = $489"

MathVista

Qwen3-VL-8B



Question. Subtract all rubber balls. Subtract all yellow shiny things. How many objects are left?

Ground truth: 6

Direct: 7 (wrong)
CoT: 6 (correct)

CoT excerpt

"That is 6 objects remaining."

Figure 6: **CoT succeeds where Direct fails.** Selected ChartQA, TabMWP and MathVista responses, with original images and verbatim CoT excerpts.

Public benchmarks: correct Direct, incorrect CoT

DVQA

Qwen3-VL-8B



Question. What is the value of the smallest bar?

Ground truth: 10

Direct: 10 (correct)
CoT: 1 (wrong)

CoT excerpt

"The smallest value on the chart is therefore the value of the "mining" bar, which is approximately 10^0 = 1."

CountBench

Qwen3-VL-8B



Question. How many bottles are shown in the image?

Ground truth: 7

Direct: 7 (correct)
CoT: 8 (wrong)

CoT excerpt

"Counting them one by one: first, second, third, fourth, fifth, sixth, seventh, eighth."

VQA-RAD

Qwen3-VL-8B



Question. are there lesions in this image?

Ground truth: yes

Direct: yes (correct)
CoT: no (wrong)

CoT excerpt

"There are no obvious areas of hyperintensity or abnormal signal that would suggest lesions such as tumors, infarcts, or demyelinating plaques."

Figure 7: **CoT can overturn a correct answer.** Selected DVQA, CountBench and VQA-RAD responses. Correctness follows the recorded dataset labels.

Public benchmarks: correspondence and screen grounding

BLINK Correspondence

Qwen3-VL-8B



Question. Which point is corresponding to the reference point? **Ground truth:** D

Direct: C (wrong) **CoT:** D (correct)

CoT excerpt. “Point D is on the same small, black, rectangular component on the circuit board in the bottom right corner.”

ScreenSpot-Pro

Qwen3-VL-8B



Question. make bulletpoint in word

Ground truth:
outlined Bullets button

Direct: (356, 145) (correct)
CoT: (356, 163) (wrong)

CoT excerpt. “I need to click on the "Bullets" button in the toolbar.”

Coordinates use the 0–1000 scale. Formal Direct / single-CoT outputs.

Figure 8: **Correspondence and screen grounding.** CoT selects the correct BLINK correspondence but misses the ScreenSpot target despite naming it. The screen example compares Direct with single CoT, not a Gate decision.

Controlled inputs: computation and localization

Synthetic table

Qwen3-VL-8B

Item	Value
F	95
D	33
B	75
A	63
C	52
E	73

Question. What is the sum of the value of F and the amount by which B exceeds C?

Ground truth: 118

Direct: 165 (wrong)
CoT: 118 (correct)

CoT excerpt

"Now, I add these two amounts together: 95 + 23 = 118."

CoT endpoint: sample 1 of K=3

Synthetic bar chart

Qwen3-VL-8B



Question. What is the sum of the value of F and the amount by which E exceeds C?

Ground truth: 103

Direct: 181 (wrong)
CoT: 103 (correct)

CoT excerpt

"97 (F) + 6 (E exceeds C) = 103"

CoT endpoint: sample 1 of K=3

Synthetic localization (x only)

Qwen3-VL-8B



Question. Locate the only blue square. Report the horizontal (x) coordinate of its center as an integer from 0 to 1000, ...

Ground truth: 750

Direct: 750 (correct)
CoT: 900 (wrong)

CoT excerpt

"It appears to be near the bottom-right corner, approximately 900 pixels from the left edge."

CoT endpoint: sample 1 of K=3

Figure 9: **Computation and localization on controlled inputs.** Recorded sampled Direct and first-CoT responses. The localization task requests only the horizontal coordinate.