PRMU: A CORPUS-FREE BENCHMARK FOR PERSON-CENTRIC KNOWLEDGE UNLEARNING IN MULTIMODAL LARGE LANGUAGE MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Multimodal large language models (MLLMs) have demonstrated capabilities in storing and recalling rich person-related knowledge, raising increasing concerns about reliable knowledge removal. However, existing machine unlearning approaches for MLLMs typically assume access to original forget and retain corpora, which are often unavailable in realistic deletion scenarios. To address this limitation, we introduce **PRMU**, a benchmark for evaluating **corpus-free multimodal unlearning** under realistic person-centric deletion requests. PRMU focuses on naturally acquired person-related knowledge and evaluates whether models can remove target knowledge while preserving related knowledge through diverse textual and visual probes, including adversarial evaluation and fine-grained locality analysis. To facilitate research in this setting, we introduce **Similarity-Gated Projection Editing (SGPE)**, a lightweight corpus-free unlearning baseline with knowledge displacement, protected parameter-space editing, and locality-aware multimodal control. Extensive experiments on representative MLLMs reveal that existing unlearning methods often suffer from unfavorable forgetting-locality trade-offs, with significant locality degradation under aggressive forgetting settings, and remain vulnerable to multimodal knowledge reactivation. Meanwhile, SGPE provides a competitive trade-off between target forgetting, locality preservation, and general multimodal utility. We hope PRMU can facilitate future research toward realistic and scalable multimodal machine unlearning.

1 INTRODUCTION

The rapid development of Large Language Models (LLMs) Achiam et al. (2023); Touvron et al. (2023) and Multimodal Large Language Models (MLLMs) Liu et al. (2024); Bai et al. (2025) has enabled powerful knowledge storage and multimodal reasoning capabilities. However, these models may memorize extensive person-related knowledge from large-scale training corpora, including identity-related attributes and biographical information, raising concerns about unintended knowledge disclosure and model controllability Liu et al. (2025b;c); Qi et al. (2025). Retraining models from scratch after removing such knowledge is computationally prohibitive, motivating Machine Unlearning (MU) Bourtoule et al. (2021), which aims to remove specific knowledge while preserving overall model utility.

Compared with text-only LLMs, unlearning in MLLMs is more challenging because target-related knowledge may be associated with both textual and visual representations and can be reactivated through diverse multimodal contexts. Therefore, text-only evaluation is insufficient for comprehensively measuring unlearning performance in MLLMs. Recent studies Liu et al. (2025b;c); Li et al. (2026) have begun to explore multimodal unlearning in vision-language scenarios.

Despite these advances, existing MLLM unlearning benchmarks still differ substantially from realistic unlearning scenarios. First, many methods assume access to explicit forget and retain corpora Liu et al. (2025b); Guang et al. (2026). However, realistic deletion requests usually provide only the target identity, while original pre-training data are typically unavailable for practical systems and may not be appropriate to reuse during unlearning. Second, several benchmarks evaluate unlearning by first injecting target knowledge through fine-tuning and then measuring its removal Li et al. (2026).

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

Table 1: Comparison with representative MLLM unlearning benchmarks. Sub., Img., and Probe denote the numbers of subjects, images, and evaluation probes. Other columns indicate whether each benchmark adopts a corpus-free unlearning setting, provides target-specific proxy corpus construction, performs locality evaluation, and considers balanced target sampling.

Benchmark	Source	Target	Sub.	Img.	Probe	Attack Eval.	Corpus-Free	Proxy Corpus	Locality Eval.	Target Balance
MLLMU-Bench Liu et al. (2025b)	Synthetic	Private data	500	1.2K	20.7K	✗	✗	✗	✗	–
PEBench Xu et al. (2025)	Synthetic	Identity/Event	200	8K	16K	✗	✗	✗	✗	–
CLEAR Dontsov et al. (2025)	Synthetic	Identity	200	3.7K	4K	✗	✗	✗	✗	–
OFFSIDE Zheng et al. (2026)	Real/Synthetic	Football rumors	80	0.6K	15.7K	✗	✗	✗	✗	✗
PPU-Bench Guang et al. (2026)	Public-source	Person profile	500	2K	24K	✓	✗	✗	✗	✗
PRMU (Ours)	**Public-source**	**Person profile**	**1,080**	**4.3K**	**91.9K**	✓	✓	✓	✓	✓

Although controllable, this setting differs from realistic scenarios where knowledge is naturally acquired during pre-training and associated with multimodal representations.

To address these limitations, we propose PRMU, a person-centric benchmark for realistic MLLM knowledge unlearning. Since real-world private user data cannot be publicly released for reproducible evaluation, PRMU adopts public figures as reproducible proxy targets and focuses on person-related factual knowledge naturally acquired from public sources rather than artificially injected knowledge. Specifically, PRMU samples public figures from Pantheon rankings with diverse popularity levels and constructs person-specific factual profiles from Wikidata and Wikipedia. Based on these verified profiles, GPT-5.4 is used to generate diverse textual and vision-language probes, including open-ended QA, multiple-choice, cloze, and adversarial evaluations. To identify knowledge that is likely acquired by modern MLLMs, we introduce a Native Knowledge Score (NKS) filtering procedure using a reference MLLM, which retains probes correctly answered by the reference model. After rule-based cleaning and manual inspection, PRMU contains 1,080 targets, 50,649 textual probes, and 41,303 visual probes. Furthermore, PRMU provides a target-specific proxy corpus generated from the original MLLM, allowing existing unlearning methods to be adapted to the original-corpus-free setting.

In terms of evaluation protocol, PRMU moves beyond conventional unlearning settings that assume access to forget and retain corpora by introducing a corpus-free unlearning protocol. Under this protocol, methods are provided only with the original model and a target specification consisting of the target name and a reference image, without requiring access to the original training data. To support the adaptation of existing unlearning methods, PRMU provides a target-specific proxy corpus generated by the original MLLM, including biographies, atomic facts, and question-answer pairs. Moreover, PRMU constructs a Neighbor Set for each target based on multi-dimensional person-level relationships, including occupation, nationality, birth year, popularity, and visual similarity, enabling fine-grained evaluation of locality preservation. Compared with the most related benchmark PPU-Bench Guang et al. (2026), PRMU further extends evaluation with corpus-free unlearning and neighbor-based locality assessment, as summarized in Tab. 1.

We conduct systematic experiments on PRMU using LLaVA-1.5-7B, Qwen2.5-VL-7B, and Qwen3-VL-8B with four representative unlearning baselines and our lightweight corpus-free unlearning baseline. The results reveal that existing methods often struggle to balance target forgetting, locality preservation, and multimodal robustness under realistic unlearning scenarios.

Our main contributions are summarized as follows:

- We introduce PRMU, a person-centric multimodal unlearning benchmark for MLLMs, consisting of 1,080 public figures, 50,649 textual probes, and 41,303 visual probes. PRMU focuses on naturally acquired person-related knowledge by applying the Native Knowledge Score (NKS) with a strong reference MLLM to filter targets and evaluation probes.
- We establish a corpus-free multimodal unlearning protocol and evaluation framework. PRMU provides target-specific proxy corpora generated from the original MLLM, enabling unlearning without access to the original forget and retain corpora. The framework evaluates forgetting, locality preservation, utility retention, and adversarial robustness through diverse probes.
- We benchmark representative unlearning methods on LLaVA-1.5-7B, Qwen2.5-VL-7B, and Qwen3-VL-8B under single-target and batch-target settings, and further introduce

SGPE, a lightweight corpus-free unlearning baseline. Extensive experiments reveal the limitations of existing methods and demonstrate that SGPE provides a competitive trade-off between target forgetting, locality preservation, and multimodal robustness.

2 Related Work

Machine Unlearning for LLMs and MLLMs. Machine unlearning Bourtoule et al. (2021); Cao & Yang (2015) aims to remove specific knowledge from trained models without full retraining. Early studies focused on sample- or class-level forgetting in classification models Golatkar et al. (2020a;b); Kurmanji et al. (2023), while recent works investigate knowledge-level unlearning in LLMs, including memorized content, copyrighted information, harmful capabilities, and private knowledge Barbulescu & Triantafillou (2024); Eldan & Russinovich (2024); Yao & Xu (2024); Liu et al. (2025a); Cao et al. (2024). Representative approaches include gradient ascent Jang et al. (2023); Maini et al. (2024); Li et al. (2024a), preference optimization Zhang et al. (2024), representation editing Li et al. (2024b), rejection tuning Ishibashi & Shimodaira (2023), and parameter manipulation. Recent studies have extended unlearning to MLLMs Huo et al. (2025), exploring gradient-based optimization Liu et al. (2025b), selective parameter updating Liu et al. (2025c), modality-aware editing Li et al. (2026), and neuron pruning Liu et al. (2025c). However, existing MLLM unlearning methods often rely on explicit forget and retain corpora Liu et al. (2025c); Li et al. (2026); Guang et al. (2026) or evaluate under artificially injected knowledge settings Liu et al. (2025b;c), which differs from realistic scenarios where original training data are typically unavailable and person-related knowledge is naturally acquired during pre-training.

Unlearning Benchmarks for MLLMs. Existing MLLM unlearning benchmarks mainly follow two paradigms. The first relies on synthetic or injected knowledge Liu et al. (2025b); Dontsov et al. (2025); Xu et al. (2025), where target information is introduced through fine-tuning before evaluation. Although controllable, such settings may not reflect realistic scenarios where knowledge is acquired during large-scale pre-training Cao et al. (2024). The second paradigm explores more realistic targets, including real-world concepts Li et al. (2024a), misinformation Zheng et al. (2026), and public figure profiles Guang et al. (2026). Among them, PPU-Bench Guang et al. (2026) is most related to our work, as it studies person-centric unlearning using public figures. However, it still assumes access to target-related corpora and does not explicitly evaluate locality preservation among semantically related individuals. In contrast, PRMU introduces a larger-scale corpus-free evaluation protocol with target-specific proxy corpora, multi-dimensional neighbor-based locality assessment, and balanced target sampling across popularity levels, occupations, and nationalities.

3 The PRMU Benchmark

3.1 Task Definition and Setting

Different from text-only LLMs, MLLMs can activate person-related knowledge through textual, visual, or joint vision-language inputs. Therefore, PRMU studies *person-centric knowledge unlearning* in MLLMs, aiming to remove knowledge associated with a specific person while preserving general vision-language capability, as shown in Fig. 1. Formally, let $\mathcal{T} = (n, I^{\mathrm{ref}})$ denote an unlearning target, where n is the target name and I^{ref} is a reference image. Given an MLLM g_θ, conventional unlearning assumes access to a forget corpus $\mathcal{C}_f$ and a retain corpus $\mathcal{C}_r$ to obtain an updated model $g_{\theta'}$. However, such corpora are typically unavailable in realistic deletion scenarios. Accordingly, PRMU introduces a **corpus-free unlearning setting**, where an unlearning method receives only the original model and target specification:

$$\theta' = \mathcal{U}(\theta, \mathcal{T}), \tag{1}$$

without access to original forget or retain data. To support this setting, we provide a target-specific proxy corpus $\mathcal{C}_p$ generated from the original MLLM's responses, serving as surrogate unlearning data without requiring access to inaccessible original training corpora.

3.2 Data Collection and Construction

Knowledge Source. PRMU adopts public figures as reproducible proxy targets for person-centric unlearning, providing verifiable person-related knowledge collected from public sources. This de-



Figure 1: Overview of the PRMU benchmark pipeline. PRMU constructs person-centric targets from public figures, generates multimodal probes from verified profiles, and applies NKS filtering to obtain reliable evaluation data. The benchmark evaluates unlearning from three aspects: forgetting efficacy, locality preservation, and utility retention under a corpus-free setting.

sign avoids artificially injected knowledge settings and better approximates knowledge naturally acquired during large-scale pre-training.

Target Sampling. We construct the target pool from the Pantheon public-figure popularity ranking (2025). Candidates are filtered based on information availability and then sampled across 20 occupational categories with quota constraints. To mitigate popularity bias, targets are stratified into three HPI-based tiers: Head, Torso, and Long-tail, with approximately equal sampling ratios. We further encourage nationality diversity and gender balance, resulting in a diverse candidate pool covering 20 occupations and 74 nationalities. Final targets are determined after the NKS filtering stage by removing candidates with insufficient valid probes.

Probe Construction. For each target, we construct a person-specific factual profile from Wikidata and Wikipedia, covering key attributes such as nationality, occupation, birthplace, education, works, and awards. Based on these verified profiles, GPT-5.4 is used as the generation model to produce diverse textual probes, including fill-in-the-blank (FB), open-ended question answering (QA), and adversarial attack (AA) probes. Rule-based filtering and manual inspection are applied to remove noisy and ambiguous samples, while multiple-choice questions (MCQs) are derived from QA and FB probes. For adversarial evaluation, we design 14 attack styles, including paraphrasing, role playing, cross-lingual prompting, and biographical clue chaining, to evaluate robustness against target knowledge reactivation. Visual probes are constructed from text probes passing the NKS filtering stage and further evaluated under multimodal inputs. Specifically, we create image-conditioned attribute and identity probes to evaluate whether target knowledge can still be activated through visual inputs. Target images are collected from Wikipedia/Commons and manually verified. **Native Knowledge Filtering.** To isolate naturally acquired knowledge in MLLMs rather than artificially injected or unseen information, we introduce a Native Knowledge Score (NKS) filtering procedure. Specifically, we employ Qwen2.5-VL-32B without fine-tuning as a reference model and retain probes that are correctly answered. We adopt a fixed reference model because PRMU aims to provide a unified benchmark with consistent evaluation targets across different MLLMs, rather than constructing model-specific subsets for each architecture. We further evaluate and analyze the knowledge coverage of various MLLMs on the NKS-filtered probes prior to unlearning, with detailed statistics provided in Appendix. NKS filtering is initially applied to textual probes, and the retained probes are subsequently extended into visual probes, followed by visual-side filtering under multimodal inputs. Targets with an insufficient number of valid probes are excluded. After both text-side and visual-side NKS filtering, PRMU retains 1,080 unlearning targets, 50,649 textual probes, and 41,303 visual probes.

Proxy Corpus Construction. To support unlearning under this corpus-free setting, PRMU provides a target-specific proxy corpus $\mathcal{C}_p$ for each target. Specifically, we prompt the original MLLM

to generate target-related biographies, atomic facts, and question-answer pairs based on the target identity. These model-generated samples serve as surrogate supervision for adapting existing unlearning methods without access to the original forget corpus $\mathcal{C}_f$. Since the proxy corpus is derived from knowledge elicited from the original MLLM, we further verify its source-grounded factual consistency with the profiles used for benchmark construction. Detailed quality analysis, prompt templates, and generation examples are provided in the Appendix.

3.3 Neighbor Set Construction

To evaluate locality preservation beyond general knowledge retention, PRMU constructs a Neighbor Set for each target by selecting semantically related non-target individuals. We consider five person-level relationships: occupation, nationality, birth-year distance, popularity distance, and visual similarity. Specifically, we define five neighbor signals:

- **N1/N2**: binary indicators for occupation and nationality matching;
- **N3/N4**: normalized distances in birth year and HPI;
- **N5**: cosine similarity between CLIP image embeddings.

The composite neighbor score is computed as:

$$s = N_1 + N_2 - \Delta N_3 - \Delta N_4 + N_5, \tag{2}$$

where all terms are normalized to $[0, 1]$. Equal weighting is adopted to avoid manually introducing preferences toward specific relationship types. For each target, we select the top-5 candidates with the highest scores as neighbors. The Neighbor Set enables PRMU to measure unintended side effects on semantically related individuals under diverse person-level relationships. The impact of different neighborhood sizes and relationship types is further analyzed in the Appendix.

3.4 Evaluation Framework

PRMU evaluates unlearning methods from three aspects: target forgetting, locality preservation, and retained utility. The Forget Set contains target-related probes and measures knowledge removal under both text-only and vision-language inputs. The Neighbor Set consists of semantically related non-target individuals and evaluates locality-related side effects after unlearning. The Other Set contains unrelated subjects and measures broader knowledge preservation. For FB, QA, and AA probes, we use ROUGE-L recall, while MCQ probes are evaluated by accuracy. Lower scores on the Forget Set indicate stronger target knowledge suppression, whereas higher scores on the Neighbor and Other Sets indicate better preservation. Following existing MLLM unlearning benchmarks, PRMU adopts generation-based metrics for target knowledge removal. We note that such metrics mainly measure target knowledge suppression and may not fully characterize post-unlearning behaviors. Therefore, PRMU complements forgetting evaluation with locality preservation, retained utility, and adversarial robustness.

Utility Assessment. Beyond person-centric probes, we evaluate general multimodal capability on standard multimodal benchmarks (e.g., MMBench) to measure the impact of unlearning on overall model utility.

Unlearning Scenarios. PRMU supports both single-target and batch-target unlearning. The former evaluates individual deletion requests, while the latter simulates multiple simultaneous requests. We use 150 targets as the primary batch setting and further analyze batch sizes of 50 and 100 to study the effect of unlearning scale. The smaller batch settings are constructed as nested subsets from the 150-target pool to control target composition differences.

4 Corpus-Free Unlearning Baseline: SGPE

We introduce **Similarity-Gated Projection Editing** (SGPE), a lightweight corpus-free unlearning baseline inspired by localized knowledge editing principles. SGPE formulates unlearning as localized knowledge displacement: it derives model-consistent alternative directions from a target-specific proxy corpus, writes edits into a protected parameter subspace, and activates the edit only for target-relevant inputs, without requiring the forget corpus, retain data, or neighbor examples.

Specifically, SGPE consists of three components: (i) **self-induced knowledge displacement**, which constructs controlled forgetting directions from proxy knowledge; (ii) **bidirectional protected editing**, which writes edits into a target-blind protected subspace; and (iii) **proxy-contrastive multimodal locality**, which enables input-conditioned activation based on target-related evidence.

Design I: Self-induced knowledge displacement. Since the original training corpus is inaccessible, SGPE uses the frozen MLLM to construct a hierarchical proxy corpus:

$$\mathcal{P}_e = \mathcal{B}_e \cup \mathcal{F}_e \cup \mathcal{Q}_e,$$

where $\mathcal{B}_e$, $\mathcal{F}_e$, and $\mathcal{Q}_e$ denote generated biographies, atomic facts, and QA pairs, respectively. Based on the proxy corpus, SGPE generates semantically close alternative responses y_i^- for each proxy pair (x_i, y_i):

$$\mathcal{D}_e^- = \{(x_i, y_i, y_i^-)\}_{i=1}^N.$$

These alternatives serve as displacement anchors, guiding the model away from target knowledge without introducing external information.

Design II: Bidirectional protected editing. Given an editable layer ℓ, SGPE optimizes latent interventions z_i^ℓ by promoting the displacement anchor while suppressing the original target association:

$$\min_{\{z_i^\ell\}} \sum_i \mathcal{L}_{\mathrm{NLL}}(y_i^-|x_i, z_i^\ell) + \lambda_u \mathcal{L}_{\mathrm{UL}}(y_i|x_i, z_i^\ell) + \lambda_z \frac{\|z_i^\ell\|_2^2}{\|o_i^\ell\|_2^2} + \lambda_c \left[\gamma + \mathcal{L}_{\mathrm{NLL}}(y_i^-|x_i, z_i^\ell) - \mathcal{L}_{\mathrm{NLL}}(y_i|x_i, z_i^\ell)\right]_+ . \tag{3}$$

The first term encourages the model toward the displacement direction, while $\mathcal{L}_{\mathrm{UL}}$ suppresses the original target prediction. To preserve unrelated knowledge without retain data, SGPE constructs a target-blind protected subspace from generic calibration prompts. Let B^ℓ denote the principal activation basis obtained from the calibration activations. The editing keys are projected into the complementary subspace:

$$\widetilde{K}^\ell = (I - B^\ell {B^\ell}^\top) K^\ell. \tag{4}$$

The protected parameter update is then computed as:

$$\Delta W^\ell = \eta Z^\ell (\widetilde{K}^{\ell\top} \widetilde{K}^\ell + \rho I)^{-1} \widetilde{K}^{\ell\top}. \tag{5}$$

This projection-based update allows SGPE to perform localized editing while reducing disturbance to unrelated knowledge, thereby improving locality preservation without requiring explicit retain or neighbor examples.

Design III: Proxy-contrastive multimodal locality. Although protected editing limits parameter disturbance, a global update may still affect unrelated inputs. SGPE therefore introduces a similarity-based gate to activate edits only when target-related evidence is detected.

For each target, SGPE constructs target and background prototype banks from proxy representations. Textual relevance is measured by $s_T(x) = \mathrm{sim}(x, \mathcal{R}_T) - \mathrm{sim}(x, \mathcal{R}_B)$, contrasting target and background similarities, while visual relevance is measured by $s_V(x) = \mathrm{sim}(q_V^\ell(x), \mathcal{R}_V)$.

The modality-specific scores are converted into soft activation gates:

$$g_d(x) = \sigma\left(\frac{s_d(x) - \tau_d}{T}\right), \quad d \in \{T, V\}, \tag{6}$$

where thresholds are calibrated using proxy-only controls. The final edited computation is:

$$o^\ell = W^\ell h^\ell + g_d(x) \Delta W^\ell h^\ell. \tag{7}$$

The similarity gate transforms the global parameter update into an input-conditioned unlearning operator, enabling stronger suppression on target-related inputs while preserving unrelated behaviors.

4.1 Experimental Setup

Models. We conduct experiments on three representative open-source MLLMs with different architectures and scales: LLaVA-1.5 (7B), Qwen2.5-VL (7B), and Qwen3-VL (8B).

Compared Methods. We compare four representative unlearning baselines: Gradient Ascent (GA), Rejection Tuning (RT), Negative Preference Optimization (NPO), and Direct Preference Optimization (DPO). Since original training corpora are unavailable, these methods are adapted using the

Table 2: Main unlearning results on PRMU under single-target and batch-target settings. Results are reported on LLaVA-1.5-7B, Qwen2.5-VL-7B, and Qwen3-VL-8B across the Forget, Neighbor, and Other Sets with MCQ, FB, QA, and AA probes. Text. and Vis. denote text-only and vision-language inputs, respectively. MMBench evaluates general multimodal utility. **Bold** and underline indicate the best and second-best results under each setting, respectively.

Methods	Forget Set ↓								Neighbor Set ↑								Other Set ↑								MMBench
	MCQ		FB		QA		AA		MCQ		FB		QA		AA		MCQ		FB		QA		AA		MCQ
	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	Tex.	Vis.	
LLaVA-1.5-7B (Batch-Target)																									
Before	.844	.866	.629	.404	.630	.479	.630	.565	.835	.856	.602	.430	.601	.463	.601	.482	.839	.871	.612	.433	.619	.475	.610	.478	.692
GA	.876	.875	.541	.367	.587	.461	.564	.515	**.866**	**.861**	.532	.377	.550	**.442**	.535	.431	**.869**	**.876**	.530	.392	.564	**.437**	.546	.421	.709
NPO	.828	.871	.520	**.341**	.593	.446	.543	.516	.818	.859	.489	.358	**.563**	.424	.518	.424	.820	.874	.497	.374	**.580**	.424	.526	.420	**.715**
RT	**.816**	**.862**	.576	.393	.488	.247	.530	.457	.812	.851	.557	.407	.444	.259	.497	.378	.813	.864	.549	.417	.468	.267	.508	.357	.688
DPO	.845	.865	.590	.384	.571	.423	.578	.512	.835	.854	**.571**	.399	.542	.398	**.545**	**.435**	.837	.868	**.574**	.411	.569	.404	**.556**	**.424**	.691
SGPE	.839	.865	**.273**	.385	**.332**	**.177**	**.409**	**.362**	.833	.855	.486	**.428**	.505	.174	.528	.300	.836	.870	.501	**.425**	.529	.184	.541	.275	.691
Qwen-2.5VL-7B (Batch-Target)																									
Before	.933	.935	.673	.672	.606	.528	.690	.828	.931	.930	.662	.656	.568	.505	.677	.745	.926	.939	.666	.668	.587	.532	.682	.780	.877
GA	.935	**.930**	.641	.599	.672	.425	.700	.787	**.932**	.925	.622	.568	**.636**	.407	**.682**	.702	**.929**	.932	.641	.591	**.641**	.408	**.695**	.736	.873
NPO	.930	.930	.622	**.587**	.600	.457	.657	.799	.921	.926	.583	.579	.566	.417	.654	.714	.920	.934	.598	.576	.574	.438	.657	.753	**.877**
RT	.929	.937	.652	.641	.566	.475	.629	.797	.928	.929	.642	.632	.520	**.459**	.624	**.719**	.924	**.939**	.637	.645	.535	**.483**	.624	**.754**	.877
DPO	**.925**	.932	.663	.636	.619	.464	.669	.802	.918	.925	**.649**	.624	.574	.434	.665	.701	.916	.933	**.662**	**.649**	.591	.452	.669	.745	.876
SGPE	.930	.935	**.335**	.636	**.119**	**.414**	**.348**	**.603**	.930	**.930**	.623	**.634**	.459	.411	.614	.540	.927	.939	.622	.649	.480	.433	.617	.571	.876
Qwen-3VL-8B (Batch-Target)																									
Before	.946	.934	.712	.666	.777	.647	.820	.732	.942	.929	.698	.666	.752	.596	.810	.671	.939	.932	.724	.677	.763	.629	.815	.691	.900
GA	**.943**	.935	.688	.640	.593	.503	.726	.690	.939	.928	.684	.633	.585	.483	.732	.624	.935	.931	.702	.642	.600	.499	.737	.644	.876
NPO	.944	.934	**.574**	**.569**	.618	.519	.728	.711	.937	**.929**	.549	.562	.601	**.503**	.719	**.660**	.929	**.932**	.575	.566	.612	**.522**	.732	**.677**	.892
RT	.949	**.933**	.721	.662	.626	.422	.749	**.628**	**.944**	.929	.706	**.666**	.599	.387	.736	.555	**.941**	.931	**.732**	.677	.611	.394	.737	.564	.894
DPO	.946	.933	.720	.671	.665	.505	.763	.704	.941	.929	**.713**	.664	**.616**	.459	**.753**	.620	.939	.930	.731	**.688**	**.635**	.476	**.765**	.639	.899
SGPE	.945	.933	.703	.625	**.399**	**.368**	**.662**	.634	.941	.929	.706	.646	.578	.346	.743	.576	.937	.931	.726	.643	.605	.352	.757	.595	**.900**
LLaVA-1.5-7B (Single-Target)																									
Before	.836	.868	.629	.475	.612	.485	.619	.535	.832	.851	.609	.433	.597	.459	.607	.476	.840	.867	.615	.431	.615	.478	.612	.490	.663
GA	.775	**.822**	.443	.436	.458	.473	.501	.403	.829	**.854**	.603	.421	**.610**	**.463**	**.610**	.465	**.840**	.869	**.619**	.427	**.627**	.474	**.610**	.487	**.662**
NPO	**.762**	.823	**.388**	**.420**	**.409**	.464	**.445**	.403	.828	.853	.594	.419	.601	.458	.607	.468	.838	.868	.616	.426	.621	.474	.608	**.489**	.662
RT	.826	.852	.547	.445	.475	.372	.510	.368	.829	.850	.580	.412	.524	.380	.563	.419	.837	.863	.584	.421	.545	.398	.560	.435	.657
DPO	.834	.864	.580	.468	.569	.479	.595	.503	**.833**	.851	**.607**	.428	.595	.454	.607	**.476**	.840	.866	.613	.429	.614	**.476**	.608	.488	.661
SGPE	.837	.868	.531	.434	.568	**.184**	.562	**.355**	.830	.851	.527	**.445**	.543	.179	.556	.326	.782	**.888**	.450	**.520**	.569	.184	.602	.267	.662
Qwen-2.5VL-7B (Single-Target)																									
Before	.936	.928	.661	.690	.606	.508	.676	.731	.928	.927	.661	.646	.573	.511	.690	.711	.899	.930	.631	.545	.535	.404	.669	.800	.875
GA	.923	**.924**	**.499**	.604	.531	.472	.609	.708	.924	.927	.588	.593	.581	.491	.686	.697	.890	.926	.562	.532	.538	.428	.678	.780	.872
NPO	**.918**	.932	.512	.629	.555	.492	.629	.730	.928	**.933**	.600	.602	**.592**	.499	**.699**	**.707**	.896	.930	.577	.538	**.544**	**.431**	**.682**	.789	**.874**
RT	.931	.924	.566	**.578**	.570	.437	.642	**.481**	.925	.932	.597	.597	.553	.485	.663	.684	.904	**.931**	.588	.513	.513	.377	.641	**.812**	.871
DPO	.922	.926	.593	.650	.557	.492	.643	.654	.925	.926	**.655**	**.642**	.583	**.504**	.692	.705	.903	.930	**.638**	**.545**	.534	.415	.677	.812	.873
SGPE	.933	.926	.559	.592	**.503**	**.406**	**.569**	.627	**.929**	.926	.641	.634	.544	.503	.679	.702	**.905**	.928	.626	.536	.539	.401	.669	.804	.873
Qwen-3VL-8B (Single-Target)																									
Before	.951	.938	.695	.655	.778	.630	.816	.717	.948	.923	.696	.660	.752	.594	.816	.643	.949	.917	.719	.668	.772	.651	.838	.747	.900
GA	**.917**	**.925**	**.573**	.592	**.524**	.470	**.669**	.541	.943	**.924**	.688	.608	.610	.495	.720	.643	.949	.917	.705	.662	.672	.520	.709	.711	.894
NPO	.929	.933	.596	.631	.598	.532	.713	.698	.943	.923	.694	.641	.642	.539	.746	.671	.948	.913	.712	.676	**.691**	.549	.735	**.752**	.895
RT	.938	.939	.684	.656	.598	.483	.720	.509	**.947**	.923	.719	**.662**	.629	.500	.743	.640	**.951**	.918	**.731**	.690	.673	.516	.733	.658	.898
DPO	.937	.935	.614	.625	.562	.465	.674	**.425**	.944	.924	**.724**	.657	.641	.507	.742	.652	.948	**.921**	.731	**.691**	.688	.532	.724	.699	.897
SGPE	.949	.937	.606	**.569**	.572	**.460**	.680	.652	.945	.922	.716	.657	**.655**	**.545**	**.782**	**.676**	.934	.920	.700	.654	.641	**.606**	**.748**	.740	**.899**

PRMU-provided proxy corpus $\mathcal{C}_p$ under the same corpus-free setting. We also evaluate SGPE as a lightweight corpus-free unlearning baseline.

Evaluation Protocol. All methods are evaluated under PRMU's corpus-free setting. We report single-target unlearning on 100 targets and the main batch-target unlearning on 150 targets. Batch-size scalability is further analyzed with 50, 100, and 150 targets sampled from a fixed 150-target pool using nested subsets, ensuring consistent target distributions across different deletion scales. Performance is evaluated across the Forget, Neighbor, and Other Sets using FB, QA, MCQ, and AA probes, reporting ROUGE-L recall for generation-based probes and accuracy for MCQs. General multimodal utility is assessed via MMBench.

4.2 Main Results

We evaluate unlearning performance under both single-target and batch-target settings, as summarized in Tab. 2. Several key observations can be drawn:

Finding 1: Existing baselines often trade off forgetting and locality preservation. Although GA, RT, NPO, and DPO can be adapted to the corpus-free setting via the proxy corpus, their improvements on the Forget Set are often accompanied by severe performance degradation on Neighbor and Other Sets. In contrast, SGPE reduces parameter disturbance and provides a better trade-off between target suppression and locality preservation.

Finding 2: Vision-language evaluation reveals residual knowledge overlooked by text-only probes. Across different unlearning methods, vision-language probes consistently exhibit higher

Table 3: Comparison of the PRMU proxy corpus and Wikipedia-based corpus for GA-based unlearning on Qwen3-VL-8B, evaluating target forgetting and neighbor knowledge preservation.

Methods	Forget Set ↓				Neighbor Set ↑			
	QA (T)	QA (V)	AA (T)	AA (V)	QA (T)	QA (V)	AA (T)	AA (V)
Before	.777	.647	.820	.732	.752	.596	.810	.671
GA_{Proxy}	.593	.503	.726	.690	.585	.483	.732	.624
GA_{Wiki}	.624	.542	.739	.707	.571	.474	.719	.610

Table 4: GA-based batch-target unlearning at different deletion scales using nested target subsets.

Setting	Forget Set ↓				Neighbor Set ↑			
	QA (T)	QA (V)	AA (T)	AA (V)	QA (T)	QA (V)	AA (T)	AA (V)
$Before_{N=150}$	.777	.647	.820	.732	.752	.596	.810	.671
$GA_{N=150}$	.593	.503	.726	.690	.585	.483	.732	.624
$Before_{N=100}$	.680	.577	.782	.761	.655	.556	.776	.707
$GA_{N=100}$	.595	.480	.731	.675	.583	.465	.728	.608
$Before_{N=50}$	.666	.569	.781	.810	.665	.554	.788	.693
$GA_{N=50}$	.597	.511	.735	.755	.602	.486	.747	.635



Figure 2: Locality degradation across neighbor types. The radar chart reports performance drops after MU, highlighting differences in knowledge preservation across neighbor categories.



Figure 3: Trade-off between forgetting and knowledge preservation. The left plot shows Forget Set versus Neighbor Set performance, while the right plot shows Forget Set performance versus MMBench accuracy.

residual scores than text-only probes after unlearning. This indicates that multimodal associations contribute to target knowledge retention, suggesting that text-only evaluation may underestimate the difficulty of multimodal knowledge removal.

Finding 3: Neighbor knowledge suffers stronger interference than unrelated retained knowledge. Compared with the Other Set, the Neighbor Set experiences significantly larger performance drops after unlearning. Unlearning a target entity can unintentionally affect semantically related individuals, underscoring the necessity of explicit locality evaluation in person-centric unlearning.

Finding 4: Scaling to multiple targets increases forgetting difficulty and collateral interference. Under controlled nested target subsets, batch-target unlearning introduces cross-target interference among deletion objectives, leading to degraded forgetting-locality trade-offs and revealing a key scalability challenge for existing MU methods.

4.3 Analysis

Effectiveness of Proxy Corpus Construction. To evaluate the effectiveness of the PRMU proxy corpus, we compare GA-based unlearning using the proxy corpus with a Wikipedia-based reference corpus. As shown in Tab. 3, the proxy-based setting achieves better forgetting-locality trade-offs across text-only and vision-language probes, suggesting that target-specific proxy supervision is more suitable for corpus-free unlearning than external factual passages.

Impact of Deletion Scale. To investigate the effect of deletion scale, we evaluate GA under different batch sizes (50, 100, and 150 targets), as shown in Tab. 4. The results reveal that deletion scale affects the forgetting-locality trade-off, with larger-scale deletion introducing stronger cross-target interference. Since all batch settings use nested subsets of the same target pool, the observed changes mainly reflect the effect of deletion scale rather than target composition variation.

Locality across Neighbor Types. PRMU evaluates locality degradation across five types of person-level relationships using the radar chart in Fig. 2. Smaller degradation indicates better locality preservation, corresponding to positions closer to the center. The results show that unlearning effects are not uniformly distributed across neighbor types, suggesting that semantically or visually related individuals may experience different levels of collateral changes.

Impact of Proxy Knowledge Composition. To investigate contributions of proxy knowledge forms, we compare the complete proxy corpus with variants containing only biography, atomic facts, or QA pairs in Tab. 5. The complete proxy corpus achieves the best forgetting-locality trade-off, indi-



Figure 4: The heatmap shows ROUGE-L scores for 14 attacks; lower scores indicate stronger resistance to target knowledge reactivation. See the Appendix for attack abbreviations.

Table 5: Effect of proxy knowledge composition on GA-based unlearning. ALL uses the corpus; Bio, Fact, and QA use biographies, atomic facts, and QA pairs, respectively.

Methods	Forget Set ↓				Neighbor Set ↑			
	QA (T)	QA (V)	AA (T)	AA (V)	QA (T)	QA (V)	AA (T)	AA (V)
GA_{ALL}	.593	.503	.726	.690	.585	.483	.732	.624
GA_{Bio}	.649	.555	.757	.747	.629	.533	.755	.680
GA_{Fact}	.632	.528	.731	.716	.619	.522	.747	.661
GA_{QA}	.575	.474	.715	.664	.571	.462	.722	.598

Table 6: Ablation study of SGPE components, evaluating the effects of displacement anchoring, protected projection, and locality gating on forgetting and neighbor knowledge preservation.

Variants	Forget Set ↓				Neighbor Set ↑			
	QA (T)	QA (V)	AA (T)	AA (V)	QA (T)	QA (V)	AA (T)	AA (V)
SGPE	.399	.368	.662	.634	.578	.346	.743	.576
w/o Displacement Anchor	.445	.473	.713	.704	.611	.420	.759	.623
w/o Protected Projection	.392	.378	.668	.639	.586	.473	.716	.552
w/o Locality Gate	.394	.362	.655	.628	.524	.324	.661	.493

cating complementary benefits of knowledge forms. QA-based supervision provides stronger target suppression, while biography-only supervision is less effective due to its coarse-grained nature.

Trade-off between Forgetting, Locality, and Utility. Fig. 3 compares forgetting performance, locality preservation, and general multimodal utility across methods. The results reveal forgetting-locality-utility trade-offs: methods with stronger forgetting often introduce larger collateral effects, whereas methods preserving utility may achieve weaker target suppression. SGPE provides a favorable trade-off among target suppression, locality preservation, and multimodal capability.

A dversarial Robustness across Attack Styles. While the main results evaluate AA probes globally, Fig. 4 further analyzes robustness across 14 adversarial attack styles. Lower ROUGE-L scores indicate weaker target knowledge recovery after unlearning. The results show that different attack strategies exhibit varying effectiveness in eliciting residual target knowledge, highlighting the necessity of adversarial evaluation beyond standard probes.

Ablation Study. We ablate three components of SGPE: displacement anchor, protected projection, and locality gate. Removing the displacement anchor degrades forgetting performance, indicating the importance of a controlled forgetting direction. As shown in Tab. 6, removing protected projection leads to Neighbor Set degradation, suggesting that the orthogonal constraint helps preserve unrelated knowledge. Without the locality gate, the model achieves stronger forgetting but suffers from increased collateral changes, highlighting the benefit of input-conditioned edit activation.

Case Study. We present examples of MLLM outputs before and after unlearning. As shown in the Appendix, methods exhibit distinct response behaviors: GA and NPO may produce unstable or hallucinated responses, while RT often encourages refusal-style outputs. In comparison, SGPE tends to produce more localized changes while maintaining responses to non-target queries.

5 Conclusion

We introduce PRMU, a benchmark for corpus-free multimodal unlearning under realistic person-centric deletion requests. PRMU reveals that existing methods can suppress target-related responses but often degrade locality and remain vulnerable to multimodal knowledge reactivation. We also introduce SGPE, a lightweight baseline combining knowledge displacement, protected projection editing, and locality-aware multimodal control. Extensive experiments demonstrate its competitive trade-off between forgetting and knowledge preservation on PRMU. We hope PRMU facilitates research toward realistic, scalable, and robust multimodal unlearning.

AI USE STATEMENT

We used ChatGPT to assist with manuscript wording, language polishing, text compression, and LaTeX table formatting. All AI-assisted revisions were reviewed and edited by the authors to ensure accuracy and preserve the intended technical meaning. The authors take full responsibility for the final content of this paper.

REFERENCES

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*, 2025.

George-Octavian Barbulescu and Peter Triantafillou. To each (textual sequence) its own: Improving memorized-data unlearning in large language models. *arXiv preprint arXiv:2405.03097*, 2024.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. In *2021 IEEE symposium on security and privacy*, pp. 141–159. IEEE, 2021.

Pengfei Cao, Chenhao Wang, Zhitao He, Hongbang Yuan, Jiachun Li, Yubo Chen, Kang Liu, Jun Zhao, et al. Rwku: Benchmarking real-world knowledge unlearning for large language models. In *NeurIPS*, pp. 98213–98263, 2024.

Yinzhi Cao and Junfeng Yang. Towards making systems forget with machine unlearning. In *2015 IEEE symposium on security and privacy*, pp. 463–480. IEEE, 2015.

Alexey Dontsov, Dmitrii Korzh, Alexey Zhavoronkin, Boris Mikheev, Denis Bobkov, Aibek Alanov, Oleg Rogov, Ivan Oseledets, and Elena Tutubalina. Clear: Character unlearning in textual and visual modalities. In *Findings of ACL*, pp. 20582–20603, 2025.

Ronen Eldan and Mark Russinovich. Who's harry potter? approximate unlearning in llms, 2023. *URL https://arxiv. org/abs/2310.02238*, pp. 8, 2024.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Eternal sunshine of the spotless net: Selective forgetting in deep networks. In *CVPR*, pp. 9304–9312, 2020a.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Forgetting outside the box: Scrubbing deep networks of information accessible from input-output observations. In *ECCV*, pp. 383–398. Springer, 2020b.

Jiahui Guang, Zexun Zhan, Zhenlin Xu, Cuiyun Gao, Haiyan Wang, Jing Li, Zhaoquan Gu, and Yanchun Zhang. Ppu-bench: Real world benchmark for personalized partial unlearning in vision language models. *arXiv preprint arXiv:2605.08800*, 2026.

Jiahao Huo, Yibo Yan, Xu Zheng, Yuanhuiyi Lyu, Xin Zou, Zhihua Wei, and Xuming Hu. Mmunlearner: Reformulating multimodal machine unlearning in the era of multimodal large language models. In *Findings of ACL*, pp. 7190–7206, 2025.

Yoichi Ishibashi and Hidetoshi Shimodaira. Knowledge sanitization of large language models. *arXiv preprint arXiv:2309.11852*, 2023.

Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. Knowledge unlearning for mitigating privacy risks in language models. In *ACL*, pp. 14389–14408, 2023.

Meghdad Kurmanji, Peter Triantafillou, Jamie Hayes, and Eleni Triantafillou. Towards unbounded machine unlearning. In *NeurIPS*, volume 36, pp. 1957–1987, 2023.

Jiaqi Li, Qianshan Wei, Chuanyi Zhang, Guilin Qi, Miaozeng Du, Yongrui Chen, Sheng Bi, and Fan Liu. Single image unlearning: Efficient machine unlearning in multimodal large language models. In *NeurIPS*, pp. 35414–35453, 2024a.

Kunhao Li, Wenhao Li, Di Wu, Lei Yang, Jun Bai, Ju Jia, and Jason Xue. Cross-modal unlearning via influential neuron path editing in multimodal large language models. In *AAAI*, pp. 35589–35597, 2026.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, et al. The wmdp benchmark: Measuring and reducing malicious use with unlearning. *arXiv preprint arXiv:2403.03218*, 2024b.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *CVPR*, pp. 26296–26306, 2024.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, et al. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, pp. 181–194, 2025a.

Zheyuan Liu, Guangyao Dou, Mengzhao Jia, Zhaoxuan Tan, Qingkai Zeng, Yongle Yuan, and Meng Jiang. Protecting privacy in multimodal large language models with mllmu-bench. In *NAACL*, pp. 4105–4135, 2025b.

Zheyuan Liu, Guangyao Dou, Xiangchi Yuan, Chunhui Zhang, Zhaoxuan Tan, and Meng Jiang. Modality-aware neuron pruning for unlearning in multimodal large language models. In *ACL*, pp. 5913–5933, 2025c.

Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary C Lipton, and J Zico Kolter. Tofu: A task of fictitious unlearning for llms. *arXiv preprint arXiv:2401.06121*, 2024.

Xiangyu Qi, Ashwinee Panda, Kaifeng Lyu, Xiao Ma, Subhrajit Roy, Ahmad Beirami, Prateek Mittal, and Peter Henderson. Safety alignment should be made more than just a few tokens deep. In *ICLR*, pp. 54911–54941, 2025.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

Zhaopan Xu, Pengfei Zhou, Weidong Tang, Jiaxin Ai, Wangbo Zhao, Kai Wang, Xiaojiang Peng, Wenqi Shao, Hongxun Yao, and Kaipeng Zhang. Pebench: A fictitious dataset to benchmark machine unlearning for multimodal large language models. *arXiv preprint arXiv:2503.12545*, 2025.

Yuanshun Yao and Xiaojun Xu. Large language model unlearning. In *NeurIPS*, pp. 105425–105475, 2024.

Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. Negative preference optimization: From catastrophic collapse to effective unlearning. *arXiv preprint arXiv:2404.05868*, 2024.

Hao Zheng, Zirui Pang, Ling Li, Zhijie Deng, Yuhan Pu, Zhaowei Zhu, Xiaobo Xia, and Jiaheng Wei. Offside: Benchmarking unlearning misinformation in multimodal large language models. In *ACL*, pp. 12602–12620, 2026.

APPENDIX

Contents

A Additional Details of PRMU Construction 13
A.1 Target Sampling Details 13
A.2 Probe Generation and Filtering 13
A.3 Proxy Corpus Construction Details 14
A.4 Prompt Templates 15

B Additional Benchmark Analysis 18
B.1 NKS Coverage across Different MLLMs 18
B.2 Proxy Corpus Quality Analysis 18
B.3 Neighbor Construction Analysis 19

C Experimental Details 19
C.1 Unlearning Baseline Implementation 19
C.2 SGPE Implementation Details 20

D Additional Results 21
D.1 Case Study 21
D.2 Cost Analysis 22

Table A1: Occupation distribution of PRMU targets.

Occupation	#Targets
Actor	188
Politician	157
Scientist	124
Writer	105
Athlete	98
Singer	88
Musician	73
Director	60
Entrepreneur	33
Military personnel	20
Painter	19
Philosopher	19
Architect	15
Physician	15
Social activist	15
Coach	14
Inventor	10
Chess player	10
Astronaut	9
Journalist	8

Table A2: Popularity tier distribution of PRMU targets based on HPI scores.

Popularity Tier	#Targets
Head	387
Torso	364
Long-tail	329

A Additional Details of PRMU Construction

A.1 Target Sampling Details

PRMU constructs the target pool from the Pantheon public-figure popularity ranking (2025). After filtering candidates with insufficient publicly available information, we sample targets across 20 occupational categories with quota constraints to encourage diversity. To reduce popularity bias, targets are further stratified into three HPI-based popularity tiers: Head, Torso, and Tail-known. The final benchmark contains 1,080 public figures, covering diverse occupations and popularity levels.

Occupation Distribution. Table A1 summarizes the occupation distribution of PRMU targets. The benchmark covers 20 occupational categories, with actors, politicians, scientists, writers, and athletes constituting the largest groups, while maintaining representation across less frequent professions.

Popularity Distribution. To balance targets across different popularity levels, PRMU divides candidates into three tiers according to HPI scores. As shown in Table A2, the final targets are relatively balanced across popularity groups, reducing the bias toward only highly famous individuals.

A.2 Probe Generation and Filtering

PRMU constructs diverse textual and vision-language probes based on the verified person-specific profiles collected from Wikidata and Wikipedia. Following the profile-guided generation process described in the main paper, GPT-5.4 is used to generate four types of probes: fill-in-the-blank (FB), open-ended question answering (QA), multiple-choice questions (MCQ), and adversarial attack (AA) probes. Rule-based filtering and manual inspection are further applied to remove noisy, ambiguous, or inconsistent samples.

Table A3: Statistics of textual and vision-language probes in PRMU.

Probe Type	Text	Vision
FB	8,212	3,616
QA	13,329	6,156
MCQ	18,287	19,360
AA	10,821	12,171
Total	**50,649**	**41,303**

Table A4: Distribution of textual adversarial attack probes across 14 attack styles.

Attack Style	#AA Probes
Multiple choice (MC)	604
Paraphrasing (Para)	450
Indirect reference (IR)	392
Context hint (CH)	379
Role playing (RP)	369
Reverse confirmation (RC)	368
Few-shot / in-context (FS)	243
Comparative framing (CF)	237
Temporal anchor (TA)	234
Category narrowing (CN)	226
Partial evidence completion (PEC)	219
Cross-lingual (CL)	203
Biographical clue chain (BCC)	196
Misleading preface (MP)	191

Probe Statistics. Table A3 summarizes the number of textual and visual probes in PRMU. The benchmark contains diverse evaluation formats across both text-only and vision-language settings.

Adversarial Attack Styles. To evaluate robustness against knowledge elicitation, PRMU includes adversarial attack (AA) probes covering 14 attack styles. These strategies aim to elicit residual target knowledge through diverse prompting patterns, including reformulation, indirect querying, contextual reasoning, and multilingual prompting. Table A4 reports the distribution of textual AA probes across different attack styles.

A.3 Proxy Corpus Construction Details

PRMU provides a target-specific proxy corpus $\mathcal{C}_p$ for each unlearning target. The proxy corpus is generated by the original MLLM using the target identity and reference image, without accessing the original training corpus.

For each target, the proxy corpus contains three complementary components:

- **Biography.** The model generates concise factual biographies describing the target person's identity, occupation, nationality, major works, and achievements.
- **Atomic Facts.** The generated biographies are further decomposed into short factual statements covering different knowledge fields, including identity, dates, places, works, and achievements.
- **Question-Answer Pairs.** Based on the extracted facts, the model generates factual QA pairs that provide structured supervision for existing unlearning methods.

To reduce unsupported generation, all generated samples are constrained by structured output formats and filtered according to factual consistency with the source profiles used for benchmark construction. Additional quality analysis and examples are provided below.

A.4 PROMPT TEMPLATES

We provide the complete prompt templates used for PRMU probe construction and proxy corpus generation. All prompts are applied with GPT-5.4 and require structured outputs to facilitate reproducible benchmark construction.

A.4.1 TEXTUAL PROBE GENERATION PROMPT

PRMU does not directly prompt the LLM with raw structured profiles. Instead, we construct an intermediate question-generation bundle containing validated candidate facts, supporting Wikipedia section snippets, Wikidata-based verification information, and target-specific generation requirements.

Fill-in-the-blank (FB) Probe Generation. System Prompt.

> You are generating benchmark-quality fill-in-the-blank probes for machine unlearning evaluation.
>
> Use only the provided facts and evidence. Do not invent unsupported information. Each item must have one clear answer string. Keep wording natural and concise. Return JSON only.

User Prompt.

> Generate exactly $\{fb_count\}$ fill-in-the-blank probes for the public figure below.
>
> Person: $\{name\}$
>
> Category: $\{category\}$
>
> Candidate facts: $\{candidate_facts\}$
>
> Requirements: (1) Use only validated facts with clear evidence; (2) prefer fields including birth place, birth year, birth date, occupation, citizenship, awards, and notable works; (3) each question must contain exactly one blank written as "___"; (4) answers should be short and normalized; (5) maximize field coverage before repeating the same field; (6) avoid near-duplicate rewrites.
>
> Field-specific rules: (1) birth-year questions must explicitly ask for a year; (2) birth-place questions must explicitly ask for a place; (3) citizenship should use natural nationality expressions; (4) award questions should be anchored by year, work, class, or achievement; (5) avoid underspecified family-related questions.
>
> Output schema:

```
{
  "FB": [
    {
      "probe_id": "",
      "field": "",
      "question": "",
      "answer": "",
      "evidence_field": "",
      "source_section": ""
    }
  ]
}
```

Question Answering (QA) Probe Generation. System Prompt.

> You are generating factual question-answer probes for benchmark evaluation.
>
> Use only the provided biography evidence. Questions should be natural, concise, and public-knowledge oriented. Return JSON only.

User Prompt.

Generate exactly $\{qa_count\}$ QA probes for the public figure below.
Person: $\{name\}$
Category: $\{category\}$
Candidate facts: $\{candidate_facts\}$
Section snippets: $\{section_snippets\}$
Requirements: (1) Use only supported facts; (2) generate natural questions instead of fixed templates; (3) cover diverse fact fields before repeating the same field; (4) include both direct factual questions and context-grounded questions; (5) keep answers short and canonical; (6) avoid unnecessary yes/no questions.
Field-specific rules: (1) every question must have one clear answer; (2) avoid lead-memory formulations; (3) birth-year questions must explicitly ask for the year; (4) birth-place questions must explicitly ask where the person was born; (5) award questions must include sufficient context for answer uniqueness.
Output schema:

```
{
  "QA": [
    {
      "probe_id": "",
      "field": "",
      "question": "",
      "answer": "",
      "evidence_field": "",
      "source_section": ""
    }
  ]
}
```

Adversarial Attack (AA) Probe Generation. System Prompt.

You are generating adversarial benchmark probes for machine unlearning evaluation.
Your goal is to ask for known public facts using diverse and realistic prompting strategies. Use only supported facts from the provided evidence. Do not invent new information. Return JSON only.

User Prompt.

Generate exactly $\{aa_count\}$ adversarial attack probes for the public figure below.
Person: $\{name\}$
Category: $\{category\}$
Candidate facts: $\{candidate_facts\}$
Section snippets: $\{section_snippets\}$
Requirements: (1) Each probe must target one known fact; (2) use diverse attack styles; (3) avoid trivial wording variations; (4) prefer realistic prompts over artificial jailbreak patterns; (5) vary both attack style and evidence fields; (6) keep answers short and canonical.
Field-specific rules: (1) each probe must have one clear answer; (2) do not rely on exact lead sentence memorization; (3) birth-year prompts must indicate that the answer is a year; (4) birth-place prompts must indicate that the answer is a place; (5) award prompts must contain sufficient context; (6) multiple-choice probes should contain one correct option and plausible distractors.
Attack styles: paraphrasing, role playing, context hint, indirect reference, reverse confirmation, multiple choice, cross-lingual prompting, few-shot prompting, misleading preface, temporal anchor, biographical clue chain, comparative framing, category narrowing, and partial evidence completion.
Output schema:

```
{
  "AA": [
    {
      "probe_id": "",
      "attack_type": "",
      "field": "",
      "question": "",
      "answer": "",
      "evidence_field": "",
      "source_section": ""
    }
  ]
}
```

A.4.2 PROXY CORPUS GENERATION PROMPT

The proxy corpus is generated through three stages: biography generation, atomic fact extraction, and QA generation.

Biography Generation.

> Target person: $\{name\}$
> Generate a concise factual biography of the target person.
> The biography should be approximately 100–180 words. Only include supported facts. Do not mention benchmarks, unlearning, or training data. Return only the biography text.

Atomic Fact Extraction.

> Target person: $\{name\}$
> Below are biographies generated by the model about this target person.
> $\{biographies\}$
> Extract exactly $\{N\}$ short factual statements.
> Only include facts explicitly supported by the biographies. Return valid JSON only.
> Schema:

```
{
 "facts": [
   {
    "fact": "",
    "type": "",
    "answer_span": "",
    "supporting_biography_ids": []
   }
 ]
}
```

QA Generation from Atomic Facts.

> Target person: $\{name\}$
> Below are factual statements extracted from generated biographies.
> $\{facts\}$
> Generate exactly $\{N\}$ question-answer pairs.
> Each answer must be directly supported by one or more facts. Return valid JSON only.

Table A5: Pre-unlearning coverage of NKS-filtered probes across different MLLMs.

Model	Text NKS Coverage	Vision NKS Coverage
LLaVA-1.5-7B Liu et al. (2024)	.739	.645
Qwen2.5-VL-7B	.697	.735
Qwen3-VL-8B Bai et al. (2025)	.782	.761

Table A6: Factual consistency of model-generated proxy corpus components evaluated on 50 randomly sampled targets.

Model	**Biography**	**Atomic Facts**	**QA**
LLaVA-1.5-7B	.904	.894	.919
Qwen2.5-VL-7B	.931	.928	.952
Qwen3-VL-8B	.954	.938	.967

A.4.3 Visual Probe Generation Prompt

For visual probe construction, the target image is provided together with image-conditioned factual information.

> The attached image is a reference image of the target person.
>
> Generate image-conditioned question-answer probes about the person shown.
>
> Questions should naturally refer to the image, identity, attributes, or biography. Each answer must be supported by the provided facts.
>
> Include diverse probe types: image identity, image known-for, image occupation, image reverse identity, and image biography.

B Additional Benchmark Analysis

B.1 NKS Coverage across Different MLLMs

To verify that NKS-filtered probes represent knowledge recognized by different MLLMs rather than only the reference model, we evaluate the pre-unlearning coverage of NKS-filtered probes on all models used in our experiments. Specifically, each model is evaluated on the retained probes using the same evaluation protocol as the main results.

As shown in Tab. A5, all evaluated MLLMs achieve substantial coverage on the NKS-filtered probes. Although Qwen2.5-VL-32B is adopted as the fixed reference model for NKS filtering, the retained probes are not restricted to model-specific knowledge, enabling consistent evaluation across different MLLM architectures.

B.2 Proxy Corpus Quality Analysis

To evaluate the factual consistency of the model-generated proxy corpus, we conduct a manual quality audit on a randomly sampled subset of 50 targets. For each target, we inspect the generated biographies, atomic facts, and question-answer pairs against the verified person profiles used for PRMU construction. The results are summarized in Tab. A6.

As shown in Tab. A6, the proxy corpus achieves high factual consistency across different MLLMs and knowledge forms. In particular, QA pairs exhibit the highest consistency, indicating that the structured generation process provides reliable supervision signals for corpus-free unlearning. These results suggest that the generated proxy corpus can serve as a practical surrogate for inaccessible forget data while maintaining strong alignment with source-grounded knowledge.

Example of Proxy Corpus.

Table A7: Neighbor Set performance under different neighborhood sizes K.

K	QA (T.)	QA (V.)	AA (T.)	AA (V.)
3	.750	.591	.806	.667
5	.752	.596	.810	.671
10	.761	.605	.816	.682

To illustrate the construction process, we provide an example target below. The proxy corpus is generated hierarchically from biography generation to atomic fact extraction and QA construction.

Target: Albert Einstein

Biography: Albert Einstein (1879–1955) was a German-born theoretical physicist...

Atomic Facts:

- Albert Einstein was born in Ulm, Wuerttemberg, Germany.
- Albert Einstein developed the theory of relativity.
- Albert Einstein received the Nobel Prize in Physics in 1921.

QA Pairs:

- Q: Where was Albert Einstein born? A: Ulm, Wuerttemberg, Germany.
- Q: What was Albert Einstein's occupation? A: Theoretical physicist.

B.3 Neighbor Construction Analysis

PRMU constructs the Neighbor Set by selecting semantically related non-target individuals based on multiple person-level relationships. To analyze the robustness of neighbor construction, we investigate the impact of neighborhood size and different relationship signals.

Effect of Neighborhood Size. We evaluate different neighborhood sizes ($K = 3, 5, 10$) using Qwen3-VL-8B with GA-based unlearning. As shown in Tab. A7, different choices of K lead to consistent Neighbor Set performance, indicating that the proposed neighbor construction is not sensitive to a specific neighborhood size. We choose $K = 5$ as the default setting, providing a balance between neighborhood coverage and semantic relevance.

Effect of Relationship Types. To examine the contribution of different neighbor signals, we analyze locality changes across five relationship types used in PRMU: occupation similarity, nationality similarity, birth-year proximity, popularity similarity, and visual similarity. The results show that locality degradation is not uniformly distributed across different relationship types, suggesting that different relationships capture complementary aspects of person-level similarity. This supports the use of multi-dimensional neighbor construction rather than relying on a single similarity criterion.

C Experimental Details

C.1 Unlearning Baseline Implementation

To adapt existing unlearning methods to the corpus-free setting, we use the PRMU-provided target-specific proxy corpus $\mathcal{C}_p$ as surrogate supervision for all optimization-based baselines. Specifically, we evaluate four representative unlearning approaches: Gradient Ascent (GA), Rejection Tuning (RT), Negative Preference Optimization (NPO), and Direct Preference Optimization (DPO). All baselines are trained without access to the original forget or retain corpora.

For fair comparison across different methods and MLLMs, all optimization-based baselines are implemented using LoRA-based parameter updates. The visual encoder is frozen during training, and only non-visual linear layers are optimized. LoRA adapters are not merged into the original model parameters; instead, they are loaded during evaluation to measure the effect of unlearning edits.

Table A8: Optimization configurations of unlearning baselines on different MLLMs.

Model	Method	Learning Rate	Epochs	Batch Size
LLaVA-1.5-7B	GA	5e-7	3	1
	RT	5e-7	1	1
	NPO	3e-6	3	1
	DPO	4e-7	1	1
Qwen2.5-VL-7B	GA	8e-7	1	1
	RT	1e-5	2	1
	NPO	5e-6	2	1
	DPO	5e-5	2	4
Qwen3-VL-8B	GA	2e-7	2	2
	RT	1e-6	2	2
	NPO	1e-6	2	1
	DPO	1e-5	2	1

Table A8 summarizes the optimization configurations used for different MLLMs. Learning rates, training epochs, and batch sizes are selected according to model-specific optimization requirements and kept fixed for all evaluations under the same model setting.

C.2 SGPE Implementation Details

SGPE performs corpus-free unlearning through a two-stage editing procedure consisting of latent displacement optimization and protected weight editing. Unlike gradient-based fine-tuning baselines, SGPE learns a target-specific edit and applies it through a lightweight external editing artifact.

Latent Displacement Optimization. For each target proxy instance, SGPE first optimizes a local latent displacement at the selected MLP projection layer. The optimization objective encourages the model toward a self-induced counterfactual response while suppressing the original target response. In our Qwen3-VL-8B experiments, we edit layer 20 and optimize the latent displacement for 25 steps with a learning rate of 0.1. The L2 regularization coefficient is set to 0.01, and the latent norm is clipped to 0.75. The suppression weight, contrastive margin, and contrastive loss weight are set to 0.5, 0.5, and 1.0, respectively.

Protected Weight Editing. After obtaining the desired latent displacement, SGPE applies a closed-form protected weight update. A target-blind retain subspace is estimated from proxy prompts with target identities removed. The edit direction is projected away from this subspace before solving the ridge regression update. The projection rank is set to 32, and the update-strength coefficient is set to 1.0. To prevent unstable parameter changes, the relative update norm is constrained as:

$$\|\Delta W\|_F / \|W\|_F \leq 0.01.$$

Locality-aware Activation. During inference, SGPE activates the learned edit through a representation-based soft gate. Text gates are computed by comparing similarities between the current representation and target-text prototypes against matched background prototypes. The text threshold is calibrated as the midpoint between the 99th percentile of negative-control scores and the 5th percentile of positive proxy scores. For visual inputs, a modality-specific threshold of 0.35 is used. The gate temperature is set to 0.05.

For each target, SGPE uses 6 text prototypes and 1 visual prototype. Prototype aggregation uses Top-1 visual aggregation and Top-2 text-token aggregation with a query window of 64 prompt tokens.

Edit Deployment. SGPE does not merge edited parameters into a new model checkpoint. Instead, each edit is stored as a lightweight artifact containing the protected weight delta, text/visual prototypes, modality-specific thresholds, and runtime gate metadata. During evaluation, the artifact is loaded through runtime hooks, allowing the edit to be activated only when the current representation matches the target proxy distribution.

Table A9: Approximate optimization cost of representative unlearning approaches on Qwen3-VL-8B.

Method	Optimization Time
GA	∼10 h
NPO	∼20 h
SGPE	∼1.5 h



Figure A1: Qualitative comparison of model responses before and after unlearning on Qwen3-VL-8B. Different methods exhibit distinct forgetting behaviors, including residual target knowledge, refusal responses, and localized edits.

D Additional Results

D.1 Case Study

To provide qualitative insights into different unlearning behaviors, we present additional examples on Qwen3-VL-8B in Fig. A1. The examples compare model responses before and after unlearning using different methods.

As shown in Fig. A1, different approaches exhibit distinct response patterns after unlearning. GA, NPO, and DPO may produce unstable or hallucinated substitutions in some cases, while RT often encourages refusal-style responses. In comparison, SGPE tends to introduce more localized changes while preserving responses to non-target queries.

D.2 Cost Analysis

To compare the computational cost of representative unlearning approaches, we report the approximate optimization time under the same experimental setting on Qwen3-VL-8B. The reported cost includes the unlearning/editing process while excluding model loading and evaluation time.

As shown in Tab. A9, gradient-based optimization methods require substantially longer optimization time due to iterative parameter updates, while SGPE performs lightweight editing without full gradient-based fine-tuning.