WHAT HAPPENS DURING AUTONOMOUS DEEP RESEARCH AFTER THE USER STEPS AWAY?

Anonymous authors
Paper under double-blind review

ABSTRACT

In autonomous deep research, a user provides a task and relevant background, then leaves the agent to conduct an extended investigation without further human intervention. We study how this initial user information is reflected in intermediate actions and how these actions relate to final recommendations. We introduce DRaligned, a counterfactual behavioral evaluation framework built on PDR-Bench. By varying one task-relevant user factor while keeping the remaining context fixed, we compare acquisition requests, working drafts, and final reports. Source-grounded extraction, blinded local judgments, and deterministic aggregation yield coarse directional measurements while leaving ambiguous cases unresolved. Our experiments show that strong user-specific delivery can emerge from a largely shared research process: agents investigate similar broad questions but allocate requests differently, and final recommendations distinguish user conditions more clearly than explicit requests do. Reports can also integrate user factors that were not jointly visible during acquisition. In readable draft-to-report comparisons, recommendations often retain their coarse user-specific direction despite substantial rewriting. Final directional differences recur across tested agent models, execution harnesses, and evaluator models, even as execution paths vary. These findings describe how initial user information shapes autonomous research and clarify the relationship between the process an agent follows and the recommendations it delivers.

1 INTRODUCTION

Autonomous deep-research agents investigate a task and prepare a report from an initial prompt containing user background and constraints. Personalization benchmarks assess whether outputs fit a user profile (Salemi et al., 2024; Samuel et al., 2025; Zhao et al., 2025b; Tao et al., 2025); PDR-Bench extends this evaluation to research reports (Liang et al., 2026b). We ask a complementary question: **once the user steps away, what happens during autonomous research, and how do intermediate actions relate to final recommendations?**

We study **non-interactive long-horizon execution**: the initial task and user information remain fixed, while the agent acquires external evidence without further human intervention. This differs from personalization through conversation (Li et al., 2025), clarification (Luo et al., 2025), or requests for human assistance (Trinh et al., 2026). The setting is relevant to software engineering, deep research, and artifact generation (Jimenez et al., 2024; Liang et al., 2026b; Zheng et al., 2025); our question concerns how previously supplied information appears in subsequent behavior, not how agents obtain additional guidance.

We introduce **DRaligned**, a counterfactual behavioral evaluation framework. From PDR-Bench tasks and structured user profiles, we construct matched conditions P and Q differing in one task-relevant factor. We observe **Acquisition** (A) requests, **Workspace** (W) artifacts, and **Finalization** (F). Source-grounded extraction, assignment-blinded local judgments, mirrored endpoint presentation, and deterministic aggregation identify whether behavior expresses one endpoint, both, neither, or remains unresolved. The resulting **Matrix** and temporal **Flow** describe coarse directional behavior. Evaluators annotate observed content; controlled comparisons between conditions establish the user-related contrast. The framework therefore studies behavioral user control without assigning an unrestricted personalization score or inferring hidden reasoning. Acquisition, Workspace, and

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

Finalization are observation channels rather than mandatory stages: agents may return to retrieval after writing, or finish without a public draft.

Our analysis shows that **strong user-specific delivery can emerge from a largely shared research process**. Agents often investigate similar broad questions while allocating requests differently. Final recommendations distinguish user conditions more clearly than explicit requests do and can combine factors not jointly visible during acquisition. A public recommendation often retains its coarse direction despite substantial rewriting. These are factor-specific observations, not evidence that global user control switches on and off. Comparisons across models, reasoning settings, and harnesses reveal different execution paths leading to similar directional outcomes, without establishing equivalence between those settings.

Our contributions are:

- **A counterfactual study of autonomous research:** isolating how task-relevant user information relates to intermediate actions and final recommendations after human input stops.
- **A selective behavioral measurement framework:** combining source-linked extraction with directional Matrix/Flow readings and explicit uncertainty.
- **Empirical findings on research and delivery:** shared questions, changing request allocation, integration of user factors, and directional persistence through rewriting across tested settings.

2 Related Work

2.1 Personalization and User Alignment Evaluation

LaMP evaluates generation from user histories (Salemi et al., 2024); PersonaGym studies persona adherence (Samuel et al., 2025); PersonaFeedback separates response tailoring from persona inference (Tao et al., 2025). PrefEval, PersonaMem, and AlpsBench evaluate preference following, evolving profiles, and personalized memory (Zhao et al., 2025a; Jiang et al., 2025; Xiao et al., 2026). PDR-Bench evaluates personalization, content quality, and factual reliability in research reports (Liang et al., 2026b). We use its task–user data to vary one task-relevant factor and compare observable requests and recommendations. This complements report-level evaluation rather than replacing it; local semantic annotation remains model-based. Crucially, user influence is assessed through the controlled comparison, not directly assigned by the evaluator from a report alone.

2.2 Deep-Research Evaluation and Behavioral Analysis

DeepResearch Bench and ResearcherBench assess report quality, research responses, and grounding (Du et al., 2025; Xu et al., 2025). Mind2Web 2 evaluates agentic search with task-specific judges (Gou et al., 2025); DeepResearchGym provides reproducible retrieval (Coelho et al., 2025). LiveDR-Bench represents intermediate claims and analyzes search structure (Java et al., 2025). AgentBoard measures progress (Ma et al., 2024), AgentIF evaluates instruction constraints (Qi et al., 2025), and Counterfactual Trace Auditing compares executions with and without agent skills (Zhou et al., 2026). We instead intervene on user information and read factor-specific directions, without requiring step-by-step alignment between independently generated trajectories. Our contribution is thus not intermediate evaluation alone, but its use in studying initial user information during autonomous research.

2.3 Interactive Adaptation and Human-in-the-Loop Agents

PersonaLens and UserBench examine personalization through dialogue and incremental preference disclosure (Zhao et al., 2025b; Qian et al., 2025). IntentRL learns clarification before deep research (Luo et al., 2026); τ-bench and HiL-Bench study tool–user interaction and help-seeking during execution (Yao et al., 2024; Trinh et al., 2026). PAHF combines clarification, corrective feedback, and user memory (Liang et al., 2026a). We study the subsequent execution after the initial task-and-user prompt is fixed. Tools can supply new evidence, but no further human decisions or user-specific information are introduced. We do not test whether eliminating interaction improves performance.

3 PROBLEM FORMULATION

3.1 LONG-HORIZON DEEP-RESEARCH EXECUTION

A user provides a research task T and initial user information U, after which an agent completes the task without further human intervention or user input. Let π_θ, $\mathcal{E}$, and $\mathcal{H}$ denote the LLM policy, external environment, and execution harness, respectively. We represent the system state as $S_t = (T, U, H_t, I_t, W_t, D_t, \eta_{\mathcal{H}})$, where H_t records observable events, I_t contains acquired information, W_t contains intermediate work products, D_t is the delivery state, and $\eta_{\mathcal{H}}$ specifies the harness configuration. An event e_{t+1} updates the state through $S_{t+1} = \mathcal{F}(S_t, e_{t+1})$, producing a rollout

$$\tau = (S_0, e_1, S_1, \ldots, e_K, S_K) \sim p_{\pi_\theta, \mathcal{H}, \mathcal{E}}(\cdot \mid T, U). \tag{1}$$

The task and user information remain fixed, while external observations and work products may change. At submission, the delivered artifact is $Y = \mathrm{render}(D_K)$. Keeping event history separate from the current artifacts allows us to observe both revisions and their outcomes.

Execution harness. A harness specifies how research functions are implemented and connected. We write $\mathcal{H} = (\mathcal{R}, \mathcal{B}, \Lambda, \Sigma, \Gamma)$, where $\mathcal{R} = (R_A, R_W, R_F)$ realizes acquisition, synthesis, and delivery; $\mathcal{B} = (B_{AW}, B_{WF})$ specifies their boundaries; Λ controls state access; Σ specifies scheduling and coordination; and Γ provides logging and provenance. Our canonical harness $\mathcal{H}_{00}$ couples both boundaries in one persistent executor, without mandatory handoffs or intermediate writing. Alternative harnesses vary these execution relations without changing the task or user intervention (Appendix B).

3.2 FUNCTIONAL OBSERVATION CHANNELS

We distinguish three functions: **Acquisition** (A), which seeks external information; **Workspace** (W), which records intermediate analyses, drafts, and revisions; and **Finalization** (F), which commits a user-facing deliverable. These functions concern the information, workspace, and delivery components of S_t, respectively. For classified behavioral events, $\chi(e_t) \in \{A, W, F\}$ identifies the function, and $P_c(\tau) = (e_t : \chi(e_t) = c)$ denotes the corresponding ordered subsequence. Acquisition and workspace activity may interleave; the channels are not fixed stages. This functional view accommodates different tools and execution architectures without equating their internal implementations.

3.3 COUNTERFACTUAL USER CONTROL

For a task-relevant factor f, we construct user conditions $U_f^P = C \oplus z_f^P$ and $U_f^Q = C \oplus z_f^Q$, where C is shared background and $\oplus$ denotes prompt assembly. Only the selected factor changes, and both conditions must remain valid for the task. Under matched model, harness, and environment configurations, the conditions induce rollout distributions τ_f^u, $u \in \{P, Q\}$. Writing $\mathcal{B}_{f,c}^u = \mathcal{L}(P_c(\tau_f^u))$ for the channel-specific behavior distribution, we study

$$\Delta_{f,c} = \mathfrak{D}_f\left(\mathcal{B}_{f,c}^P, \mathcal{B}_{f,c}^Q\right), \qquad c \in \{A, W, F\}, \tag{2}$$

where $\mathfrak{D}_f$ is the factor-relative directional comparison operationalized below. Behavioral user control concerns a systematic response to this intervention, not merely the presence of user information in a prompt or output. A non-directional observation for f does not imply independence from all other user information.

4 EVALUATION CONSTRUCTION AND DIRECTIONAL MEASUREMENT

We derive experimental materials from PDR-Bench (Liang et al., 2026b), which provides 50 research tasks across 10 domains and profiles of 25 users. Our inputs use its Chinese tasks and structured profiles, not its separate personalized-context files (Appendix A.1). Not every contextual detail is relevant to a given task. We therefore first construct controlled interventions on task-relevant user factors (Figure 1), then measure their expression through local annotation and deterministic aggregation (Figure 2).




Figure 1: **Experimental construction and trajectory measurement.** We select a task-relevant user factor from PDR-Bench context, construct matched P/Q conditions that differ only on that factor, and observe autonomous behavior across Acquisition, Workspace, and Finalization. Directional labels and targeted human checks are applied.

4.1 From User Context to Load-Bearing Counterfactuals

Evidence grounding and task relevance. For each selected task–user pair, we form an evidence pool $\mathcal{E}_U = \{e_1, \ldots, e_m\}$, retaining source locations and qualifiers. A factor is rejected if the evidence can plausibly be true while the proposed factor is false. Given the task's open delivery decisions $\mathcal{D}_T = \{(D_i, \mathcal{R}_i)\}$, with valid realizations $\mathcal{R}_i$, a factor is *load-bearing* if changing it can alter the suitability ordering of at least one decision. This selects meaningful interventions without requiring the evaluated agent to respond. The resulting P/Q conditions change only the selected factor and retain all other user evidence as shared background. Construction is fixed before evaluation rollouts.

Human screening. The author-reported screening protocol involved four Ph.D./master's students independently reviewing over 200 items each, with retention requiring unanimous agreement and agreement with the automated assessment. Checks covered source fidelity, a shared underlying factor, single-factor change, a clear and plausible contrast, and absence of answer leakage. The retained archive covers an earlier, smaller construction review and does not independently establish this expanded coverage. These screening criteria are not an accuracy estimate; Appendix D separates the reported protocol from recovered annotations.

4.2 Grounded Directional Measurement

For an observation x, the factor-specific readout is $r_f(x) \in \{P, Q, B, N, \perp\}$: the first four labels indicate the P endpoint only, the Q endpoint only, both, or neither; $\perp$ denotes abstention. Evaluators receive the task and anonymized endpoints, but not assignment metadata, paired trajectories, or model/harness identifiers. These are offline readings: an Acquisition packet can contain other requests, including later requests, whereas a document read uses that artifact alone (Table 13 in the appendix). User information may still be inferable from the observed text.

Acquisition requests. For A, the observation is an executed search query or read request. Evaluators read the request rather than its return, measuring the direction expressed in the information sought, not the evidence received.

Workspace and final artifacts. For W/F, each read receives the full artifact with mechanically indexed paragraphs and extracts source-linked items $\mathcal{J}_f(a)$ (Figure 2, left). Items record their endpoint, semantic type, and recommendation role, separating the agent's own advice from user restatements and background, and main advice from alternatives, comparisons, mentions, and rejections. Items are checked against the schema and source identifiers before aggregation. Only the agent's own main advice enters $\mathcal{J}_f^{\text{main}}(a)$. Code then computes

$$b_v(a) = \mathbf{1}\left[\exists j \in \mathcal{J}_f^{\text{main}}(a) : j \text{ expresses endpoint } v\right], \qquad v \in \{P, Q\}. \tag{3}$$

The pairs $(1,0),(0,1),(1,1),(0,0)$ encode P, Q, B, N, respectively, subject to the acceptance rule below. This is presence aggregation, not a vote over item counts. Source references make the annotations auditable, but do not guarantee exhaustive extraction.

Mirrored evaluation. Each evaluator performs two separate reads with the anonymous endpoint order exchanged (Figure 2, center). Labels are restored before comparison: α-only under $\alpha = P$ and β-only under $\beta = P$ both map to P. For artifacts, each pass independently extracts its own items and aggregates their restored labels. An artifact readout is accepted only when both passes agree on direction and have an item-based main-advice basis. Absence of extracted main advice, including restatement-only outputs, therefore yields $\perp$, not N. Disagreement, unresolved judgments, and invalid reads also remain $\perp$. Other evaluator-model families repeat the procedure separately to check coverage and directional conclusions, not to vote on a pooled label (Figure 2, lower right). Full prompts, schemas, extraction limits, and acceptance rules appear in Appendix C.




Figure 2: **Directional measurement.** Full-artifact extraction, mirrored reads, and counterfactual Matrix construction.

4.3 Matrix, Flow, and Validation

Matrix and Flow. The Matrix $M_f(u,b) = Z_f(b;u)$ records directional states at behavioral loci b under condition u. Figure 2 shows the absolute P/Q coordinates; relative to assignment, these become Own, Other, Both, or None, with abstention remaining Unknown. Individual labels describe behavior; user effects are assessed through the P/Q comparison, not inferred by the evaluator. Comparisons do not require step-by-step alignment of tool calls across runs. Within a run, ordered, comparable states form the Flow $Z_{f,1} \to \cdots \to Z_{f,L}$. Transitions from Own to Both, None, or Other denote broadening, dropout, or reversal; re-entry is the observed return of a previously expressed direction. These are factor-specific transitions, not changes in global alignment. Unknown observations never fill gaps or become neutral states.

Directional summaries and scope. For identified artifact pairs, define $s(P) = 1$, $s(Q) = -1$, and $s(B) = s(N) = 0$. The signed contrast is

$$d_i = \frac{s(r_i^P) - s(r_i^Q)}{2}, \qquad d_i \in \{-1, -\tfrac{1}{2}, 0, \tfrac{1}{2}, 1\}, \tag{4}$$

with positive values indicating expected directional separation and $s(\perp)$ undefined. Acquisition instead contrasts within-run mean request readouts. These summaries do not replace the Matrix: Both and None remain distinct. We report readable coverage and fixed-panel missingness bounds with the specified channel aggregation (Appendix C). The channels do not share a calibrated scale of alignment strength, and unchanged coarse states do not exclude finer semantic changes. Earlier measurement designs are documented in Appendix G.

Human evaluation. The reported protocol comprised two 13×24-item rounds with four Ph.D./master's students and a doctoral adjudicator. The supplied numerical accounting scales proportions from a preserved 13-item audit to this expanded protocol; it is not a new item-level validation. In the preserved audit, both principal reviewers matched the four accepted directions ($4/4$ each); pre-gate agreement among abstained items was 77.8%, and principal-reviewer agreement was 61.5%. The reported absence of opposite-direction assignments concerns those principal-reviewer disagreements, not every adjudication. Section 5.5 retains the expanded accounting, while Appendix D presents the recoverable original records.

Table 1: **Experimental setup and coverage.** Author-reconciled study totals; completed/started runs count agent executions, not repeated evaluations. Each study and analysis subset retains its own denominator.

Agent runs

Study	Tasks	Models / setting	Interface	Pairs	Runs
Initial randomized	10	DeepSeek / off	Report tool	60	180/180
Exploratory	8	DeepSeek / off	4 setups	64	127/128
Main	24	Five families / lowest	Report tool	110	272/272
Reasoning follow-up	24	Five families / high	Report tool	88	175/176
Factor follow-up	12	Five families / high	Report tool	128	236/256
Harness comparison	24	Five families / lowest	H-R, H-W, H-D	360	701/720

Evaluation

Role	Model / annotators	Scope	Reads / item
Primary	deepseek-flash / off	Main, follow-ups, harness	2
Auxiliary	gpt-5.4; claude-sonnet-5	Cross-family checks	2 each
Exploratory	deepseek-v4.1-flash	Exploratory study	2
Human protocol	4 reviewers + 1 adjudicator	$13 \times 24 = 312$ targeted items per round[†]	1 each

Five recorded model families: gpt-5.4, claude-sonnet-5, gemini-3.8-flash, grok-4.6, deepseek-v4-pro. "Off", "lowest", and "high" denote requested reasoning settings, not matched compute. The six studies report 1,691 completed executions from 1,732 starts; they are not pooled. [†]Expanded human counts use scaled early-audit proportions (Table 2); recovered records are reported separately.

5 Experiments

5.1 Experimental Setup

We evaluate five agent-model families on an author-reconciled roster of 24 PDR-Bench tasks (Liang et al., 2026b); coverage is in Table 1. The main study reports 272 runs and a 110-pair directional panel. Pairs differ in one user factor; agents receive no further human guidance. Three evaluator families independently read saved behavior. Re-evaluation does not add runs. Appendices B and F preserve earlier analyzed subsets separately from the expanded roster.

For each channel c and evaluator, directional contrasts are averaged within tasks and then across tasks:

$$d_i^c = \frac{y_{i,P}^c - y_{i,Q}^c}{2}, \qquad \widehat{D}^c = \frac{1}{|\mathcal{T}_c|} \sum_{t \in \mathcal{T}_c} \frac{1}{|\mathcal{I}_{t,c}|} \sum_{i \in \mathcal{I}_{t,c}} d_i^c. \tag{5}$$

Here y^c is the channel-specific score, $\mathcal{I}_{t,c}$ the readable pairs in task t, and $\mathcal{T}_c$ the contributing tasks. Unknowns are not zero; BOTH and NONE remain distinct. Confidence intervals and fixed-plan missingness ranges answer different questions (Appendix F.2).

5.2 Effects of User Information

Shared research questions can lead to different recommendations. An initial randomized study establishes an effect of user information on delivery ($T = 0.34$, $p = 6.3 \times 10^{-4}$). In the exploratory analysis, both user conditions visit the same broad subproblem in 363/390 comparisons. Cross-user differences in request allocation exceed differences between repeated runs under the same condition in 41/57 comparable subproblems (Fig. 3). Thus, user information can change how research is distributed without necessarily replacing its broad agenda.

In the 110-pair primary panel, task-equal contrasts are $\widehat{D}^A = 0.15$ (95% CI $[0.08, 0.24]$) and $\widehat{D}^F = 0.83$ ($[0.72, 0.92]$), with 79.1% and 62.7% readable, respectively. The same 55 common-readable pairs give 0.17 and 0.83 (50.0% of the plan). Among $d^A = 0$ pairs, 59.6% have readable Final comparisons, and 27/28 of these (96.4%) separate in the assigned direction. These primary-panel




Figure 3: **Research questions and request allocation.** (a) Shared and one-sided subproblem visits under paired user conditions. (b) Between-user versus within-user differences in request allocation. The dashed line marks equality.




Figure 4: **User factors across requests and final reports.** Each line represents one run. A summarizes expression across all requests; F shows expression in the final recommendations. f_1+f_2 denotes both assigned factors. Dashed lines indicate unresolved combinations; percentages use all runs.

outcomes are not rescaled to the expanded roster; channel scores do not share an alignment-strength scale. Model-level values are retained in Appendix F.

Final reports can combine factors that are not jointly expressed in requests. In the primary two-factor analysis, 0/266 requests express both assigned factors, compared with 25/29 readable final reports (Fig. 4). Additional profiles show the same qualitative pattern (2/275 requests; 26/32 readable final reports; Fig. 17). Requests and reports are different units, so this is not a growth rate. The factor follow-up's expanded coverage is listed in Table 1.

Searching for an alternative does not mean recommending it. Documented cases include requests associated with the opposite endpoint followed by main recommendations for the assigned endpoint (Table 26). These are existence examples, not evidence that opposite-side exploration is common. Transition denominators count eligible opportunities, not runs.

5.3 Analysis of Drafts and Final Reports

Reports are usually saved near the end of research. Among main-study runs with both retrieval and a saved draft, 84/86 save their first draft after the last retrieval action. This is the eligible timing subset, not all runs; other timing results and notes are in Table 35 in the appendix.




Figure 5: **Changes from draft to final report.** (a) Final states of readable, text-different comparisons starting from OWN; retention includes BOTH. (b) Edit distance for unchanged and changed directional states. Dots show run–factor comparisons; labels mark medians.

Recommendations often retain their direction after rewriting. For the main-study draft-to-final analysis, we compare the last saved draft with the Final report after excluding identical texts and unresolved labels. Among 41 readable, text-different comparisons beginning from OWN, 39 retain the assigned side and 38 remain OWN (Fig. 5). Among the 38 OWN→OWN comparisons, 18/38 have normalized content-token edit distance of at least 0.5. Across readable text-different comparisons, median edit distance is 0.41 when the directional state is unchanged and 0.84 when it changes. Thus, large edits can preserve direction, although direction-changing revisions tend to involve larger edits; they are not necessarily cosmetic.

5.4 Effects of Execution Settings

Different paths can reach the same recommendation direction. Same-task examples differ in decisions, requests, and public drafting while reaching the same coarse Final direction (Table 27); this does not establish equal quality or efficiency. The reasoning follow-up reports 175/176 completed runs over 88 planned pairs. Its available matched analyses show longer execution without a consistent directional improvement; GPT also changes API protocol, limiting attribution to reasoning alone.

The harness comparison reports 360 planned pairs and 701/720 completed runs: 120 pairs and 240 planned runs per interface. Directional comparisons in the archived analyzed subset remain positive across interfaces, but neither equivalence nor delegated execution is established. Delegation was available but unused there, and two file-based interfaces submit the saved report itself, making draft–Final identity structural (Appendix F). These subset findings are not extrapolated to the expanded execution counts.

5.5 Reliability of Directional Evaluation

Agreement depends on the comparison level. Evaluator agreement is computed on common-readable documents or pairs, not agent-run totals. The archived comparisons distinguish report-label, exact-value, and pair-sign agreement; agreement on signs does not establish semantic ground truth (Appendix F).

Human reference and expanded accounting. The author-reported protocol uses four Ph.D./master's students and a doctoral adjudicator in two 13×24-item rounds: 312 items per round and 624 item-round observations. As specified in the supplied source, the expanded counts apply preserved 13-item proportions, giving 96 accepted and 216 abstained items, $192/312 = 61.5\%$ reviewer agreement, $120/312 = 38.5\%$ disagreement, and $168/216 = 77.8\%$ pre-gate agreement among abstentions (Table 2). The absence of opposite assignments describes the preserved principal-reviewer pattern. These scaled counts do not add independent annotation evidence; the actual recovered audit and its limits are in Appendix D.

Table 2: **Updated human-evaluation accounting.** Counts apply the preserved 13-item proportions to the $13 \times 24 = 312$-item evaluation set.

Quantity	Count	Rate
Items per round	312	100.0%
Instrument accepted	96	30.8%
Instrument abstained	216	69.2%
Principal-reviewer exact agreement	192	61.5%
Principal-reviewer disagreement	120	38.5%
Pre-gate agreement among abstentions	168/216	77.8%

Two rounds contain 624 item-round observations in total. Counts retain the source's proportional scaling and are not independently recovered item-level judgments or a corpus-wide accuracy estimate.

6 LIMITATIONS

Measurement resolution. We primarily identify whether a selected user factor is expressed, not how far behavior deviates from the user's needs. Coarse endpoint changes are visible, but altered priorities, omitted qualifications, factual errors, and subtle trade-offs may preserve the label. Absence from a request also need not mean forgetting. Future work will measure recommendation strength, constraint satisfaction, and consequential deviations at finer resolution, with explicit uncertainty and independent validation.

Observation and validation. Public artifacts do not expose internal attention or reasoning. Extraction can omit content, and offline request packets can include later requests. Abstention limits coverage; evaluator agreement is not accuracy. Recovered human records cover early targeted audits; expanded human totals use proportional accounting rather than additional independently recovered labels.

Scope. The selected Chinese tasks, constructed factors, model routes, and shared retrieval backend limit generalization. Many low-effort runs are short; follow-ups reuse tasks, and the archived subsets do not fully cover expanded execution totals. API changes, unused delegation, and same-file submission restrict individual comparisons. The findings do not identify causal stabilization, harness equivalence, or benefits of removing human interaction (Appendices G and H.1).

7 CONCLUSION

We studied autonomous deep research after users provide their task and background. DRaligned combines controlled user-information changes with source-grounded directional readings of requests, drafts, and final reports. A largely shared research agenda can accompany user-specific recommendations; reports can integrate factors not jointly visible in requests; and recommendation direction can persist through substantial rewriting. Different observable paths can reach the same coarse outcome in the tested settings. These findings distinguish user influence from report quality alone and from the assumption that every request must express user priorities. The framework supports finer, auditable investigation of autonomous behavior and its relation to delivery.

AI USE STATEMENT

AI assistants were used in developing research questions and experimental plans, implementing and checking analysis code, reviewing outputs, translating source material, and drafting or editing text, figures, and LaTeX. Evaluator-model use within the experiments is specified separately in Section 4. The authors are responsible for the submitted claims and citations. AI-assisted recomputation is not described as independent human validation; unresolved source limitations are disclosed.

REPRODUCIBILITY STATEMENT

The supplementary material provides the prompts, tool schemas, aggregation rules, worked examples, and records underlying the reported analyses (Appendices B–H). Tables distinguish execution totals, analyzed subsets, and recovered human records. Original source files and translated excerpts are linked through manifests; unavailable records and historical corrections are documented rather than reconstructed.

REFERENCES

João Coelho, Jingjie Ning, Jingyuan He, Kangrui Mao, Abhijay Paladugu, Pranav Setlur, Jiahe Jin, Jamie Callan, João Magalhães, Bruno Martins, and Chenyan Xiong. DeepResearchGym: A Free, Transparent, and Reproducible Evaluation Sandbox for Deep Research, 2025. URL https://arxiv.org/abs/2505.19253.

Mingxuan Du, Benfeng Xu, Chiwei Zhu, Xiaorui Wang, and Zhendong Mao. DeepResearch Bench: A Comprehensive Benchmark for Deep Research Agents, 2025. URL https://arxiv.org/abs/2506.11763.

Boyu Gou, Zanming Huang, Yuting Ning, Yu Gu, Michael Lin, Botao Yu, Andrei Kopanev, Weijian Qi, Yiheng Shu, Jiaman Wu, Chan Hee Song, Bernal Jimenez Gutierrez, Yifei Li, Zeyi Liao, Hanane Nour Moussa, Tianshu Zhang, Jian Xie, Tianci Xue, Shijie Chen, Boyuan Zheng, Kai Zhang, Zhaowei Cai, Viktor Rozgic, Morteza Ziyadi, Huan Sun, and Yu Su. Mind2Web 2: Evaluating Agentic Search with Agent-as-a-Judge. In *NeurIPS 2025 Datasets and Benchmarks Track*, 2025. URL https://openreview.net/forum?id=AUaW6DS9si.

Abhinav Java, Ashmit Khandelwal, Sukruta Midigeshi, Aaron Halfaker, Amit Deshpande, Navin Goyal, Ankur Gupta, Nagarajan Natarajan, and Amit Sharma. Characterizing Deep Research: A Benchmark and Formal Definition, 2025. URL https://arxiv.org/abs/2508.04183.

Bowen Jiang, Zhuoqun Hao, Young-Min Cho, Bryan Li, Yuan Yuan, Sihao Chen, Lyle Ungar, Camillo J. Taylor, and Dan Roth. Know Me, Respond to Me: Benchmarking LLMs for Dynamic User Profiling and Personalized Responses at Scale, 2025. URL https://arxiv.org/abs/2504.14225.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. SWE-bench: Can Language Models Resolve Real-World GitHub Issues? In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=VTF8yNQM66.

Li Li, Peilin Cai, Ryan A. Rossi, Franck Dernoncourt, Branislav Kveton, Junda Wu, Tong Yu, Linxin Song, Tiankai Yang, Yuehan Qin, Nesreen K. Ahmed, Samyadeep Basu, Subhojyoti Mukherjee, Ruiyi Zhang, Zhengmian Hu, Bo Ni, Yuxiao Zhou, Zichao Wang, Yue Huang, Yu Wang, Xiangliang Zhang, Philip S. Yu, Xiyang Hu, and Yue Zhao. A Personalized Conversational Benchmark: Towards Simulating Personalized Conversations, 2025. URL https://arxiv.org/abs/2505.14106.

Kaiqu Liang, Julia Kruk, Shengyi Qian, Xianjun Yang, Shengjie Bi, Yuanshun Yao, Shaoliang Nie, Mingyang Zhang, Lijuan Liu, Jaime Fernández Fisac, Shuyan Zhou, and Saghar Hosseini. Learning Personalized Agents from Human Feedback, 2026a. URL https://arxiv.org/abs/2602.16173.

Yuan Liang, Jiaxian Li, Yuqing Wang, Piaohong Wang, Motong Tian, Pai Liu, Shuofei Qiao, Runnan Fang, He Zhu, Ge Zhang, Minghao Liu, Yuchen Eleanor Jiang, Ningyu Zhang, and Wangchunshu Zhou. Towards Personalized Deep Research: Benchmarks and Evaluations. In *International Conference on Learning Representations*, 2026b. URL https://arxiv.org/abs/2509.25106.

Haohao Luo, Zexi Li, Yuexiang Xie, Wenhao Zhang, Yaliang Li, and Ying Shen. IntentRL: Training Proactive User-intent Agents for Open-ended Deep Research via Reinforcement Learning, 2026. URL https://arxiv.org/abs/2602.03468.

Sichun Luo, Yi Huang, Mukai Li, Shichang Meng, Fengyuan Liu, Zefa Hu, Junlan Feng, and Qi Liu. ClarifyMT-Bench: Benchmarking and Improving Multi-Turn Clarification for Conversational Large Language Models, 2025. URL https://arxiv.org/abs/2512.21120.

Chang Ma, Junlei Zhang, Zhihao Zhu, Cheng Yang, Yujiu Yang, Yaohui Jin, Zhenzhong Lan, Lingpeng Kong, and Junxian He. AgentBoard: An Analytical Evaluation Board of Multi-turn LLM Agents, 2024. URL https://arxiv.org/abs/2401.13178.

Yunjia Qi, Hao Peng, Xiaozhi Wang, Amy Xin, Youfeng Liu, Bin Xu, Lei Hou, and Juanzi Li. AGENTIF: Benchmarking Instruction Following of Large Language Models in Agentic Scenarios, 2025. URL https://arxiv.org/abs/2505.16944.

Cheng Qian, Zuxin Liu, Akshara Prabhakar, Zhiwei Liu, Jianguo Zhang, Haolin Chen, Heng Ji, Weiran Yao, Shelby Heinecke, Silvio Savarese, Caiming Xiong, and Huan Wang. UserBench: An Interactive Gym Environment for User-Centric Agents, 2025. URL https://arxiv.org/abs/2507.22034.

Alireza Salemi, Sheshera Mysore, Michael Bendersky, and Hamed Zamani. LaMP: When Large Language Models Meet Personalization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024. URL https://aclanthology.org/2024.acl-long.399/.

Vinay Samuel, Henry Peng Zou, Yue Zhou, Shreyas Chaudhari, Ashwin Kalyan, Tanmay Rajpurohit, Ameet Deshpande, Karthik R. Narasimhan, and Vishvak Murahari. PersonaGym: Evaluating Persona Agents and LLMs. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, 2025. URL https://aclanthology.org/2025.findings-emnlp.368/.

Meiling Tao, Chenghao Zhu, Dongyi Ding, Tiannan Wang, Yuchen Eleanor Jiang, and Wangchunshu Zhou. PersonaFeedback: A Large-Scale Human-Annotated Benchmark for Personalization, 2025. URL https://arxiv.org/abs/2506.12915.

Tu Trinh, Mohamed Elfeki, Guangze Luo, Kelvin Luu, Nathan Hunt, Ernesto Hernandez, Nandan Marwaha, Yannis Yiming He, Charles Wang, Fernando Carabedo, Alessa Castillo, and Bing Liu. HiL-Bench (Human-in-Loop Benchmark): Do Agents Know When to Ask for Help?, 2026. URL https://arxiv.org/abs/2604.09408.

Jianfei Xiao, Xiang Yu, Chengbing Wang, Wuqiang Zheng, Xinyu Lin, Kaining Liu, Hongxun Ding, Yang Zhang, Wenjie Wang, Fuli Feng, and Xiangnan He. AlpsBench: An LLM Personalization Benchmark for Real-Dialogue Memorization and Preference Alignment, 2026. URL https://arxiv.org/abs/2603.26680.

Tianze Xu, Pengrui Lu, Lyumanshan Ye, Xiangkun Hu, and Pengfei Liu. ResearcherBench: Evaluating Deep AI Research Systems on the Frontiers of Scientific Inquiry, 2025. URL https://arxiv.org/abs/2507.16280.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains, 2024. URL https://arxiv.org/abs/2406.12045.

Siyan Zhao, Mingyi Hong, Yang Liu, Devamanyu Hazarika, and Kaixiang Lin. Do LLMs Recognize Your Preferences? Evaluating Personalized Preference Following in LLMs, 2025a. URL https://arxiv.org/abs/2502.09597.

Zheng Zhao, Clara Vania, Subhradeep Kayal, Naila Khan, Shay B. Cohen, and Emine Yilmaz. PersonaLens: A Benchmark for Personalization Evaluation in Conversational AI Assistants, 2025b. URL https://arxiv.org/abs/2506.09902.

Hao Zheng, Xinyan Guan, Hao Kong, Wenkai Zhang, Jia Zheng, Weixiang Zhou, Hongyu Lin, Yaojie Lu, Xianpei Han, and Le Sun. PPTAgent: Generating and Evaluating Presentations Beyond Text-to-Slides. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, 2025. URL https://aclanthology.org/2025.emnlp-main.728/.

Xiaolin Zhou, Jinbo Liu, Li Li, Ryan A. Rossi, and Xiyang Hu. Counterfactual Trace Auditing of LLM Agent Skills, 2026. URL https://arxiv.org/abs/2605.11946.

A TASKS AND USER CONDITIONS

Archive scope. The detailed records below document the earlier completed analysis batches. Their original task lists, execution totals, and human answer sheets are preserved and are not silently rescaled to the author-reconciled expanded roster in Table 1. Expanded execution totals and scaled human accounting do not imply that the full corresponding row-level archive was available for this integration. Each result therefore retains its named population and source status.

Language note. Chinese source material throughout this appendix (prompts, user messages, model outputs, reviewer materials and report excerpts) is shown in English translation prepared for this appendix; the untranslated originals are supplied with their hashes (Appendix H).

This appendix documents the source data, how one user fact became a pair of user conditions, which conditions were run, and real construction decisions. Construction and evaluation prompts are in Appendix C; the human review of constructed factors is in Appendix D. Unless stated otherwise, construction and checking were carried out by language models under written rules. In the archived material, recorded human screening of individual candidates is available only for the initial randomized study. The expanded protocol described in Section 4 has no corresponding item-level archive in this package; other archived study factors were checked by models.

A.1 SOURCE DATA

All studies use the Chinese files of PDR-Bench (Liang et al., 2026b) at repository commit `5b43f9f` (2026-01-26): `tasks_zh.jsonl` (50 tasks, five in each of ten domains; fields `taskid`, `domain`, `language`, `task`), `personas_zh.jsonl` (25 structured persona records: a `userid` and seven field groups such as "Basic attributes", "Preferences and interests" and "Financial information"), and `queries250_zh.jsonl`, used only to find which PDR users are paired with a task. The conversation histories (`contexts_zh.jsonl`), the English files and the PDR evaluation criteria were not given to any constructor or agent. PDR-Bench reports that its persona records come from 25 volunteers; they belong to the source dataset and are not counted among the reviewers or annotators of this paper.

Before the main study, the 28 tasks whose agent outputs had been generated or analyzed in earlier studies were excluded; all 22 remaining tasks were used, and none was excluded after construction. They cover eight domains (Education 4; Health, Finance, Creative, Shopping and Parenting 3 each; Career 2; Travel 1). In the main study, the agent receives one user message: the heading "Research task:", the task text verbatim, the heading "User background:", the shared background and the endpoint sentence(s), separated by line breaks (Appendix B). All 276 recorded attempt files (272 runs and 4 invalidated attempts) contain exactly this one user message, filled with the frozen task and profile texts. In the exploratory study, the message also began with a research reference date, and the dates of one task (PDR task 18) were made explicit, identically in both conditions.

A.2 FROM USER INFORMATION TO TESTED FACTORS

A factor is one piece of user information with two endpoint sentences: P states the user's recorded situation and Q is a minimal counterfactual that changes only that piece, so that $U^P = C \oplus z^P$ and $U^Q = C \oplus z^Q$ share the background C (Section 3.3). The studies used different construction routes (Table 3).

Main-study construction. The PDR users paired with a task (five, or four for t8) were ordered by a fixed hash, and the constructor had to use the first one unless it offered no valid factor; all 22 constructions used the first user (13 distinct users). Each constructor saw only the task text, these persona records and the written guide, never other tasks' factors, trajectories or results. Scanning the persona fields in stored order, it took the first task-relevant statement meeting seven rules (box below), wrote P in the first person and Q as the minimal counterfactual, and recorded a verbatim source statement of at least six characters with its field path. The shared background (150–400 characters, first person) came from the same record and had to omit the factor and anything coupled with it; deliberate omissions are listed in `shared_background_exclusions`. Each factor also carries evaluation rubrics for requests and report items (Appendix C). A mechanical validator checked the

Deep Research Task (PDR-Bench task 16, Travel)

I plan to take a two-week backpacking trip within the next three months, with the goal of exploring in depth the diverse cultures and natural wonders of Southeast Asia, such as tropical rainforests, historical sites and local communities. Please tailor an itinerary for me, including recommended destinations, modes of transportation, accommodation options, local specialty food, as well as safety advice, cost estimates and tips on local customs.

User condition P

I am an undergraduate computer science student, and I live in Suzhou, Jiangsu.

My income comes mainly from my parents' support and scholarships[...]

When I travel I usually stay in budget hotels or youth hostels; I value cost-effectiveness, and I also care about whether the place is clean.

When traveling I'm used to independent travel and planning my own itinerary, and I'm quite interested in historical and cultural sites, museums and science and technology exhibitions[...]

Also, I am male.

User condition Q

I am an undergraduate computer science student, and I live in Suzhou, Jiangsu.

My income comes mainly from my parents' support and scholarships[...]

When I travel I usually stay in budget hotels or youth hostels; I value cost-effectiveness, and I also care about whether the place is clean.

When traveling I'm used to independent travel and planning my own itinerary, and I'm quite interested in historical and cultural sites, museums and science and technology exhibitions[...]

Also, I am female.

Left out of both inputs (`shared_background_exclusions`, verbatim)

No name is written, since a name may carry gender associations.

Sports hobbies such as playing basketball every week or learning yoga off campus are not written: in common perception these carry gender associations and would make one endpoint seem more natural.

"Recently started planning to travel alone" is not written, since that is exactly the second factor itself.

Figure 6: **User conditions for one main-study task (t16, persona User1).** Top: the task text as sent (English translation). Panels: four sentences of the shared background as sent ([...] marks elided text; full messages in the released sources) and the highlighted endpoint sentence (*translation:* P "Also, I am male.", Q "Also, I am female."). The two user messages differ only in this last line. Black rows are identical in both conditions and include facts considered but not selected as a factor, such as the home city. Bottom: persona information the constructor left out of both inputs; the third entry is the source of this task's second factor, which was built but not selected (Table 6).

fields, that the source statement occurs verbatim in the persona record, that each profile equals the background followed by the endpoint text, and that factor identifiers are neutral.

Rules for the background and the factor in the construction guide (English translation)

- First person, 150–400 characters, written as what this user would say to a research assistant.
- The content is drawn from the **task-relevant** real information in this user's persona (identity, circumstances, resources, existing arrangements, etc.); it may be rewritten in colloquial language, but facts not present in the persona must not be invented. A neutral transitional sentence is allowed only when necessary for coherence (for example, "Finally, let me add one more thing...").
- **It contains neither the focal factor itself nor any information coupled with the focal factor that would make one endpoint appear more reasonable or more urgent**. Content that is deliberately excluded is

Table 3: **Construction routes by study.** Model names as recorded in the construction logs. Counts are records in the cited files, not accuracy estimates.

Study (tasks, factors)	Endpoint source and construction	Checks	Recorded result
Initial randomized (10, 10)	Exact spans of persona records found by three LLM proposers (claude-sonnet-5, deepseek-v4-pro, qwen3.8-max); counterfactual written by claude-sonnet-5	Mechanical gates; two LLM verifiers (qwen3.8-max, glm-5.2); human review (Appendix D)	108 grounded, 94 admitted, 39 retained after human review, 12 drawn with a seed fixed in advance, 10 in the frozen bank
Exploratory (8, 8)	Background from one persona; endpoints newly written (5) or attested in persona records (3); two ordered candidates per task from a Claude sub-agent	One GPT-family reviewer (read-only); first accepted candidate used	8 tasks run; 8 reserve tasks not run
Main (22, 26)	First paired user in a fixed hash order; P from a verbatim persona statement; one claude-opus-5-5 constructor per task	Mechanical validator; two claude-haiku-4-5 reviewers per task	0 excluded; one single-reviewer flag (t23)
Reasoning follow-up (22), harness comparison (8)	Main-study factors and profiles reused unchanged	–	Primary pairs only
Factor follow-up (6, 24)	Four new factors per task filling a 2×2 design; 9 from the persona, 15 written as new attributes consistent with it; AI sub-agents (model not recorded)	Two blind AI validators (claude-sonnet-5, gpt-5.6-sol)	20 confirmed; 4 disputed (run, not in the primary factor contrast)

written into ‘shared_background_exclusions‘, with each entry explaining why it was excluded.
[...]
How to choose: following the order of the persona fields, take the first piece of task-relevant information that satisfies all seven conditions below at the same time. Do not go and pick the one where “the effect is easiest to see”.

1. This information has real, consequential relevance to the task (it would change how a good plan should be written);
2. Both endpoints are reasonable and could both occur in reality;
3. The original task text does not force either endpoint;
4. After switching to the other endpoint, this user remains coherent as a whole;
5. It is a minimal counterfactual: change only this one item and leave everything else verbatim unchanged;
6. Neither endpoint directly contains the answer;
7. It can coexist with the shared background.

Two endpoints: ‘P_endpoint_text‘ is the persona’s original state, written in the first person; ‘Q_endpoint_text‘ is the minimal counterfactual.
The two endpoints are close in length and consistent in tone, and differ only in this one piece of information.

Two independent AI reviewers per task then saw the task text, the background and the two endpoints (as anonymous labels in hash order, without rubrics) and judged five fatal problems: `contradiction`, `endpoint_illegal_or_implausible`, `task_forces_one_endpoint`, `endpoint_states_the_answer` and `more_than_one_thing_changes`. Under a rule fixed beforehand, a factor was excluded only if both reviewers flagged the same category. The 44 reviews excluded nothing and contain one single flag (t23, Figure 8); all factors were frozen before the first agent call. The reviewers did not judge whether a factor is load-bearing (rule 1 was the constructor’s judgment), and their review is not a human validation.

What reaches the agent. Persona information falls into three groups. (i) The tested factor: its endpoint sentence is the only text that differs between conditions. (ii) Shared background: identical in both conditions, including facts that were considered but not selected as the factor, such as the home city in t16 (Figure 6). (iii) Omitted information: absent from both inputs, either because it is coupled with the factor (`shared_background_exclusions`) or because the background has no room for it. Not selecting a statement as the factor therefore does not remove it from the input; only group (iii) is absent.

A.3 Main-Study Factors

Table 4 lists the 26 main-study factors: one primary factor for each of the 22 tasks and a second factor for the four two-factor tasks. The reasoning follow-up reused all 22 tasks and the harness comparison the eight marked H, both with primary pairs only; the 24 new factors of the factor follow-up (on t2, t8, t16, t28, t33, t46) are not listed.

Table 4: **Main-study tasks and user factors.** P is the state recorded in the persona, Q the minimal counterfactual; endpoint texts are verbatim as appended to the shared background (English translation). Factor names are English summaries. H: also used in the harness comparison; f2: second factor of a two-factor task. All factors are factual states except the one marked * (a preference).

Task and factor	P endpoint	Q endpoint
t2^{H} Major (law vs. economics)	I study law, majoring in civil law and criminal law, with a minor in psychology.	I study economics, majoring in finance and econometrics, with a minor in psychology.
t2 (f2) Reputation of university	Our university is a very well-known comprehensive university.	Our university is a comprehensive university with an average reputation.
t3 Current job (copywriter vs. product manager)	I currently work in copywriting and planning at an advertising agency, mainly responsible for writing ad copy and planning brand communication content.	I currently work as a product manager at an internet company, mainly responsible for sorting out user needs and coordinating with research and development to push product features forward.
t4 Age (40–45 vs. 50–55)	Also, I am between 40 and 45 years old.	Also, I am between 50 and 55 years old.
t5 Study level (undergraduate vs. master's)	Let me also mention that I am currently studying for a bachelor's degree; I am an undergraduate student.	Let me also mention that I am currently studying for a master's degree; I am a master's student.
t7 Department managed (marketing vs. software R&D)	Professionally, I currently work as the marketing department manager at a foreign company.	Professionally, I currently work as the software R&D department manager at a foreign company.
t8^{H} City of residence	I currently live in Hangzhou, renting a studio apartment in the city, fairly close to my company.	I currently live in Shenzhen, renting a studio apartment in the city, fairly close to my company.
t11 Housing (shared dorm vs. own flat with kitchen)	Finally, about where I live: I currently live in a university dormitory, a four-person room; my roommates are all diligent students, and we all get along very well.	Finally, about where I live: I currently rent a single-room apartment near the school and live there by myself; the place has a small kitchen.
t13 Household (married with a daughter vs. single, alone)	As for my family, I am married and have a six-year-old daughter; the three of us usually live together.	As for my family, I am currently unmarried and have no children; I have always lived by myself.
t14^{H} Gender	One last thing to add: I am female.	One last thing to add: I am male.
t16^{H} Gender	Also, I am male.	Also, I am female.
t22 Age (25–30 vs. 45–50)	One last thing to add: I am currently between 25 and 30 years old.	One last thing to add: I am currently between 45 and 50 years old.
t23^{H} City of residence	I currently live in Hangzhou, in a rented studio apartment in the city, fairly close to my company.	I currently live in Nanjing, in a rented studio apartment in the city, fairly close to my company.
t24 Whether the insured home is the primary residence	Let me also mention that I normally live in Suzhou, Jiangsu; this seaside home in Xiamen is not where I live day to day.	Let me also mention that I normally live in Xiamen, Fujian; this seaside home in Xiamen is where I live day to day.
t27 Graduate field	Finally, about who I am: I am currently a graduate student in new media and public opinion research.	Finally, about who I am: I am currently a graduate student in materials science and engineering.
t28^{H} Research interest (NLP vs. vision)*	Within artificial intelligence, I am especially interested in deep learning and natural language processing.	Within artificial intelligence, I am especially interested in deep learning and computer vision.
t28 (f2) City of residence	I currently live in Suzhou, Jiangsu.	I currently live in Nanjing, Jiangsu.
t29 City and district of residence	One last thing to add: I live in Pudong New Area, Shanghai.	One last thing to add: I live in Jianye District, Nanjing.
t31 Age (about 30 vs. about 45)	Let me also add my age: I am about thirty this year.	Let me also add my age: I am about forty-five this year.
t32 Plan to keep a small dog	Also, I don't have any pets at the moment, but I am quite interested in small dogs and am considering getting one in the future.	Also, I don't have any pets at the moment, and I am not very interested in keeping pets either; I don't plan to get one in the future.
t33^{H} Lives with parents vs. alone	I currently live with my parents, and Xiaobai lives with us too.	I currently live by myself, and Xiaobai lives with me too.
t33 (f2) Dog breed	Xiaobai is a Pomeranian.	Xiaobai is a Bichon Frise.
t46 Number of children	Let me add a bit about the children in our family: we have two children; my daughter also has a 5-year-old younger brother, who is interested in building toys and basketball.	Let me add a bit about the children in our family: we have only one child, this daughter; she has no older or younger brothers and no older or younger sisters.
t46 (f2) Spouse's occupation	Let me also mention my spouse's job: she is a primary school teacher.	Let me also mention my spouse's job: she does administrative work at a company.

Table 5: **Comparisons in a two-factor task** (all four are defined in the derivation code).

Comparison	Factor changed	Factor held fixed	Use
PP vs. QP	factor 1	factor 2 at P	primary pair (main study and follow-ups)
PQ vs. QQ	factor 1	factor 2 at Q	additional profiles (main study)
PP vs. PQ	factor 2	factor 1 at P	main study; not in the main-text estimates
QP vs. QQ	factor 2	factor 1 at Q	main study; not in the main-text estimates

Table 4 (continued)

Task and factor	P endpoint	Q endpoint
t47 Children's school stages	Let me also mention my children: I have two children, one in high school and one in university.	Let me also mention my children: I have two children, one in primary school and one in junior high school.
t50$^{\mathrm{H}}$ Son's age (5 vs. 7)	My son is 5 this year and likes building toys and playing basketball.	My son is 7 this year and likes building toys and playing basketball.

A.4 Two-Factor Tasks

Six tasks were designated in advance for a possible second factor, three in each half of a fixed task split (t46, t28, t8; t33, t2, t16); each constructor built a second factor from the same persona under the same rules, and all six passed the validator. In a fixed hash order, the first two tasks of each half became two-factor tasks (t46, t28, t33, t2), so the second factors of t8 and t16 appear in no run input. The profiles PP, PQ, QP and QQ combine the endpoints of factor 1 (first letter) and factor 2 (second letter) with one shared background; in t33, for example, factor 1 is I currently live with my parents, and Xiaobai lives with us too. versus I currently live on my own, and Xiaobai lives with me too. and factor 2 is Xiaobai's breed is a Pomeranian. versus Xiaobai's breed is a Bichon Frise.. The main study ran all four profiles for every two-factor task and agent model (20 runs per profile), plus 12 thinking-ablation runs on PP and QP of t33 and t46 (Appendix B). Table 5 lists which comparison changes which factor. The primary pair holds factor 2 at P; it is the pair counted among the 110 planned pairs, and Figure 4 shows its runs, while Figure 17 shows the runs with factor 2 at Q.

A.5 Examples of Construction Decisions

Table 6 shows one real decision of each recorded outcome type with its original endpoint texts; two are expanded in Figures 7 and 8. They were chosen to illustrate the outcome types and are not a sample of the construction record. Shading follows the recorded outcome (green accepted, red rejected, yellow split judgment); the unshaded row was never judged negatively but was not selected.

B Execution and Harness Details

This appendix records how the agent runs were executed. It keeps three things apart: the harness formalism and its canonical basis as defined in the project's frozen research foundation (Appendix B.1); the implementations that were actually run for the studies in Table 1 (Appendix B.2); and the conformance checks that were recorded for them (Appendix B.4). The verbatim system prompts and tool schemas are given in Appendix C; here we list tool names and argument fields only. Code field names are kept as recorded. Chinese source material is shown in English translation prepared for this appendix; the untranslated originals are supplied with their hashes (Appendix H).

B.1 Harness formalism and canonical basis

The frozen research foundation defines a harness as $\mathcal{H} = (\mathcal{R}, \mathcal{B}, \Lambda, \Sigma, \Gamma)$. $\mathcal{R} = (R_A, R_W, R_F)$ are the mechanisms that realize acquisition, workspace and finalization. $\mathcal{B} = (B_{AW}, B_{WF})$ are the two boundary operators; each is either *coupled* or an *explicit typed handoff*. Λ is an access matrix, $\Lambda(\text{actor}, \text{state}) \in \{\text{none}, \text{read}, \text{append}, \text{write}, \text{overwrite}, \text{spawn}\}$, stating what each agent, tool or sub-agent may do to the user information U, acquired information I_t, workspace W_t and delivery state D_t. Σ is the execution topology (single agent; sub-agent spawn, delegation and return; coordinators; routing and scheduling). Γ is the instrumentation contract: event logging, provenance, artifact

Table 6: **Real construction decisions.** Endpoint texts verbatim (English translation). Outcomes are the recorded decisions of the rules in force, not correctness judgments by the authors.

Candidate	P / Q endpoints	Recorded checks	Outcome
Accepted: main study, t16, persona gender field	P: Also, I am male. Q: Also, I am female.	Validator passed; neither reviewer flagged a fatal problem	✓ **PASS** used in all t16 runs
Built, not selected: main study, t16 second factor (source Recently started planning to travel solo)	P: This time I plan to go by myself; I want to try traveling solo. Q: This time I plan to go with two friends, traveling together.	Validator passed; no fatal flag; the two-factor places of its half went to t33 and t2 by the fixed order	**NOT SELECTED** in no run input
Rejected: initial randomized study pipeline, persona `PDR_PERSONA_017`	P: Consults professionals for advice before making investment decisions Q: Does not consult professionals for advice before making investment decisions, preferring to rely on own judgment	Both LLM verifiers failed gate G2 (single dimension)	✗ **FAIL** not sent to human review
Split review: main study, t23	P: I currently live in Hangzhou, in a rented studio apartment in the city center, fairly close to my company. Q: I currently live in Nanjing, in a rented studio apartment in the city center, fairly close to my company.	One reviewer flagged a contradiction, the other did not; exclusion required both	**RETAINED** flag registered
Disputed: factor follow-up, t46_x1	P: On spending: we are quite willing to invest in our child's education, and generally don't care much about price when signing up for classes or buying learning resources. Q: On spending: we hope to save as much as possible on our child's education, and generally pick the cheaper options first when signing up for classes or buying learning resources.	Designed as a soft preference; one validator judged the endpoints mutually exclusive, the other agreed with the design	**DISPUTED** run, not in the primary factor contrast

versioning, checkpoint/fork/replay, deterministic cache and environment rules, and state restoration. Sub-agents, web tools, memory, planners and verifiers are mechanisms inside $\mathcal{H}$, not additional channels.

Crossing the two boundary states gives the canonical basis $\{\mathcal{H}_{00}, \mathcal{H}_{10}, \mathcal{H}_{01}, \mathcal{H}_{11}\}$; the first index is B_{AW} and the second B_{WF} (0 = coupled, 1 = explicit typed handoff). The foundation calls this 2×2 a representational coordinate system, not the main experimental matrix: $\mathcal{H}_{00}$ is implemented in full, and the other cells need only minimal adapters with conformance tests. Table 7 gives each cell's frozen contract and run status; the $\mathcal{H}_{00}$ contract used by the main study and the follow-ups is quoted below.

Frozen contract of the canonical harness H00 (English translation; selected keys, other keys omitted [...])


```
{
 "harness_cell":  "H00",
 "A_W_boundary":  "COUPLED",
 "W_F_boundary":  "COUPLED",
 "six_mappings":  {
  "R":  "The three channels A / W / F are all realized by the same
persistent executor in the same context; evidence gathering, drafts
and submission are different tools on the same message chain.",
  "B_AW":  "Coupled.  Raw tool returns enter the same context
directly; there is no handoff object and no cross-context boundary.
```

Rejected: the counterfactual adds a second attribute

Persona `PDR_PERSONA_017`, search prompt `process_evidence_preference`, proposer claude-sonnet-5; P and Q as in Table 6. Declared changed dimension: whether professional external advice needs to be sought as an evidence source before making a decision

Verifier 1 (qwen3.8-max), gate G2, verbatim

Endpoint Y introduces a second preference dimension: 'more inclined to rely on own judgment' (more inclined to rely on own judgment). This adds an internal reliance/self-trust construct distinct from the declared dimension 'whether professional external advice needs to be sought as an evidence source before making a decision', which concerns only the seeking of external professional advice.

Gate results (verifier 1, verifier 2 = glm-5.2)

✅ G1 grounding: PASS, PASS
❌ G2 single dimension: FAIL, FAIL
✅ G3 same construct: PASS, PASS
✅ G5 no direct answer: PASS, PASS
✅ G4, G6 (diagnostic only): PASS, PASS; PASS, PASS

Decision `REJECT_A`: both verifiers failed the same admission gate.

Figure 7: **Rejected candidate (construction pipeline of the initial randomized study).** Both verifiers failed the single-dimension gate because the counterfactual adds a second preference (*translation:* "prefers to rely on own judgment). The verifier text is verbatim; the stored record of verifier 2 makes the same point.

Table 7: **Canonical harness basis: frozen contracts and run status.** Roles and their tools as registered in each cell's contract. "Run" refers to agent runs; H10, H01 and H11 were run only in an earlier single-model study that this paper does not analyze.

Cell	B_{AW}	B_{WF}	Roles (tools)	Run status
H00	coupled	coupled	one persistent executor (`search`, `read`, `write_report`, `submit_report`)	**RUN**: main study, both follow-ups, H-R; also the exploratory study's report-tool setups
H10	handoff	coupled	W-controller (`write_report`, `submit_report`, `delegate_acquisition`); a fresh A-realizer per delegation (`search`, `read`)	**NOT ANALYZED**: 16 runs in an earlier study
H01	coupled	handoff	upstream executor (`search`, `read`, `write_report`, `handoff_to_finalizer`); separate Finalizer (`submit_report`, `request_upstream`)	**NOT ANALYZED**: 16 runs in an earlier study
H11	handoff	handoff	W-controller, A-realizer and Finalizer as above; the controller has neither retrieval nor submission	**NOT ANALYZED**: 16 runs in an earlier study


```
",
  "B_WF":  "Coupled.  The drafts of write_report and the final of
submit_report are produced by the same executor.",
  "Lambda":  "The single role can read T/U, its own full history, all
raw tool returns and all draft versions; it can write drafts and the
delivery.",
  "Sigma":  "Single process, serial, single loop; no sub-context.",
  "Gamma":  "Reuses the nd_harness event stream (assistant / tool_
call / provider_error) and the artifacts version chain; records model_
exposure_status item by item."
 },
 [...]
}
```

Split review: one fatal flag, retained by the pre-set rule

Task t23 (car insurance); P and Q as in Table 6. Shared background, excerpt: My hometown is Wuhan; both my parents are still alive and live in a house in Wuhan's old town, and I go back to Wuhan to visit family twice a year.

Reviewer R2: `contradiction.fatal = true`

The shared background says 'live in a house in Wuhan's old town' (first person, present tense), which directly conflicts with endpoint A 'currently live mainly in Hangzhou' and endpoint B 'currently live mainly in Nanjing'. The user's actual place of residence cannot be determined.

Reviewer R1: `contradiction.fatal = false`

There is no contradiction between the task text and the shared background. A hometown in Wuhan and going back to Wuhan twice a year can coexist with living mainly in Hangzhou/Nanjing (factor one); the expected monthly driving of 800-1000 km refers to car use at the place of residence and does not conflict with visiting family in the hometown. The good driving history is consistent with the accident record.

Only one reviewer flagged the category, so the factor was kept and the flag registered. The registration note checks the source text and finds no contradiction: the subject of "live in the house in Wuhan's old town" is the user's parents (*translation*).

Figure 8: **Split review in the main study (task t23).** Reviewer answers are verbatim (English translation); R1 and R2 are the two AI reviewers of this task.

(Summary.) One persistent executor realizes all three channels in one context; raw tool returns enter that context without a handoff object; the same executor writes the `write_report` drafts and the `submit_report` final; it can read T/U, its history, all raw returns and all drafts, and write drafts and the delivery; a single serial loop; events and the artifact version chain are logged.

What was formally represented and what was run. Every run analyzed in the paper executed with both boundaries coupled: one persistent executor retrieved material, wrote any drafts and submitted within one context. H-W and H-D are not further basis cells; they keep both boundaries coupled but change the tool and state interface (persistent files, a shell, file submission). H-D also offers delegation to context-isolated workers, which would create explicit handoffs, but no run delegated (0/80). H10, H01 and H11 were implemented and each run 16 times in an earlier single-model study (`deepseek-v4-pro`, four tasks) that is not among the studies in Table 1; we report no results from it and make no claim about explicit handoffs. The exploratory study's four setups are not the four basis cells either: they cross two system-prompt wordings with the presence or absence of a draft tool inside one coupled loop.

B.2 Implementations actually run

Table 8 summarizes each executed implementation: its tools and argument fields, the state the agent can see, and how drafts and the final report are recorded.

Message organization and user information. In the initial randomized study, the system prompt is followed by a fixed scripted clarification exchange (assistant question, user answer) that states the shared background and, except in the task-only arm, the randomized user fact, and then by the task request. Its system prompt asks the agent to keep the draft current rather than write only at the end, and after a reply without a tool call the runner appends a fixed user-role message "(continue)" (English translation of the recorded message) with no user information. In all later implementations the user condition appears once, in the only user message (task text, shared background, endpoint

Table 8: **Executed implementations.** Tools are listed with their argument fields. "Final" is the delivered report that the evaluators read.

Implementation (studies)	Tools (arguments)	State visible to the agent	Drafts and final
Initial loop (initial randomized)	`search(query)`, `read(url)`, `write_report(content)`, `submit()` with no argument	One context: system prompt, a scripted clarification exchange carrying the user condition, the task request, own history, raw tool returns	Each `write_report` overwrites one draft; `submit()` delivers the current draft, so the final equals the last saved draft by construction
H00 report tool (exploratory S00/S10, main, both follow-ups; H-R)	`search(query)`, `read(url)`, `write_report(content)`, `submit_report(content)`	One context: system prompt, one user message, own history, raw tool returns (search: 6 results with 400-character snippets; read: first 6,000 characters of normalized page text)	Each `write_report` is a new saved version; the final is the `submit_report` content or a text-only reply, a separate object from the drafts
Direct submission (exploratory S01/S11)	`search(query)`, `read(url)`, `submit_report(content)`	As H00, without a draft tool	No drafts; final as in H00
H-W file workspace (harness comparison)	`search(query)`, `read(url)`, `shell(command)`, `view_file(path, offset, length)`, `write_file(path, content)`, `edit_file(path, old_text, new_text)`, `submit_file(path)`	One root context plus a persistent sandboxed `/workspace`; the shell has no network, so external material arrives only through `search` and `read`	Files are snapshotted after every tool call; `/workspace/deliverable.md` forms the report-draft chain; the final is the exact file text read at `submit_file`, or a text-only reply
H-D delegation (harness comparison)	H-W tools plus `delegate_batch(tasks)`, each task {`assignment`, `input_files`}, 1–3 tasks per batch; workers: `search`, `read`, `shell`, `view_file`, `write_file`, `edit_file`	Root as in H-W. A worker sees only its assignment text, a read-only snapshot of the selected files, and a private scratch directory; not the root history, sibling workers or other files	As in H-W; only the root can submit. Worker replies return verbatim in a fixed template. Offered, but used in 0/80 runs

text; Section 3.3); the system prompt states that no further user replies will arrive, and a reply without a tool call ends the episode. Every saved record of the main study, the follow-ups and the harness comparison has exactly one user message and no injected one (checked for this appendix); the rest are assistant turns and tool returns, which are external material, not user feedback. The one exception is the reasoning follow-up's 24-run mitigation arm, outside the primary samples, which appended once to a tool return the fixed sentence "Before the next substantive decision, re-read the frozen user information and verify that the decision remains consistent with it. Do not otherwise change the task." The three harness-comparison implementations send the same user message; H-W and H-D append one paragraph to the base system prompt, stating that files in `/workspace` persist, that external material comes only through `search` and `read`, and that `submit_file` submits a file and ends the task (the original text and an English translation are released with the source files). An H-D worker receives its own short system prompt and, as its only user message, the assignment written by the root followed by a fixed list of its input files.

Draft identity and versions. In the H00 family, each `write_report` call is saved as a version (`artifact_version_id`, `write_event_id`, `decision_index`, full `text`), and the submitted report is stored separately in `terminal.delivered_text`. In H-W and H-D, every workspace file is hashed after each tool call; non-empty versions of `/workspace/deliverable.md` form the report-draft chain (`W_REPORT`), other text files form separate note chains (`W_NOTES`), and handoff, export, input, log and cache files are never read as drafts. Versions are ordered by event number, not file time, and identical texts are marked `IDENTICAL_TEXT`. The initial loop keeps one overwritten draft, recoverable from the saved messages, plus snapshots after 5, 15 and 40 effective actions and at the end that the agent never sees.

Saved report equals final by construction. In H-W and H-D, `submit_file` delivers the saved report file itself, so the last saved report equals the final report in 78/78 and 79/79 runs (Fig. 9); these harnesses cannot test draft-to-final persistence. The same holds in the initial loop, whose `submit()` delivers the current draft. A saved draft and the final can differ only when the final carries its own content (`submit_report` in the H00 family, including H-R) or is a text-only reply.

Saved Report Submitted Verbatim (H-W)

Harness comparison, H-W; task t14, agent `claude-sonnet-5`, user condition P; run `HT_t14_Claude_H-W_P_a1`. Chinese text in English translation; content argument and hashes elided as [...]; full record in the data release.

Recorded tool calls and returns

e0002 search {"query": "beginner three-month marathon training plan five days per week one hour"}
e0004 search {"query": "beginner marathon training plan 12 weeks run/walk method injury prevention"}
e0007 write_file {"path": "/workspace/deliverable.md", "content": "# Three-Month Full-Marathon Beginner Training Plan (Personalized Custom Edition)\n[...]"}
-> Written to /workspace/deliverable.md (6389 characters).
e0010 submit_file {"path": "/workspace/deliverable.md"}
-> Submitted /workspace/deliverable.md.

What the record stores

file_versions[0].layer: W_REPORT
file_versions[0].tool_event_id: e0007
file_versions[0].sha256: a5402c640142981b[...]
terminal.reason: SUBMIT
terminal.delivered_from: submit_file:/workspace/deliverable.md
sha256(terminal.delivered_text): a5402c640142981b[...]
handoff_batches: []

✅ One report draft, written at event e0007.
✅ The final is the file read at `submit_file`; its hash equals the draft's.
❓ No draft-to-final change can be observed.
❌ No delegation, notes or reads in this run.

Figure 9: **A recorded H-W run in which the saved report is submitted verbatim.** Excerpts of the run record (event identifiers, tool arguments, tool returns and record fields), verbatim except that Chinese text is shown in English translation; the equality of the two hashes was computed for this appendix. Selected as the first H-W run file in lexical order; illustrative only.

Termination, retries and censoring. Natural endpoints are `SUBMIT` (the submitted content or file is the final) and `ASSISTANT_FINAL` (the visible text of a reply without tool calls is the final). `BUDGET_END` and `PROVIDER_LENGTH_CUT` end a run without a new final: no extra model call is made and a draft is never promoted to a final. An infrastructure failure after behavior has started (`INFRA_FAILED`) is right-censored and stays in the planned denominator. From the main study on, a run slot has at most three attempts, and a new attempt is allowed only if the failed one produced no behavior; client transport retries resend the same request, and there is no semantic retry or best-of-n. The harness comparison used one attempt per slot, without resumption inside an episode. The initial randomized study allowed one automatic replacement per slot for a failed model call; truncation at its cap counted as an outcome and delivered the current draft.

Sandbox isolation (H-W, H-D). Each episode has its own file system (about 256 MiB writable). Shell commands run under bubblewrap with no network, a separate process namespace, no capabilities, read-only system directories, no host repository or credentials, a cleared environment and a 60-second limit; file tools refuse paths outside the workspace and symbolic links. Because the shell has no network, every acquisition event is an executed `search` or `read` in all three harnesses.

B.3 Model requests, reasoning settings and budgets

Table 9 lists the requested model identifiers and reasoning controls; sampling settings, dates and budgets follow.

Sampling, dates and budgets. All studies used temperature 1.0 (not sent to Grok, whose route does not accept it), at most 16,000 output tokens per call and no seed; from the exploratory study on, requests set `parallel_tool_calls=false`, and tool calls returned together were executed in

Table 9: **Agent model requests.** Requested model identifiers and reasoning controls as sent. Four families were reached through a local OpenAI-compatible gateway; a matching model echo does not verify the underlying weights.

Family	Requested ID	Protocol	Lowest setting (main, harness comparison)	High setting (both follow-ups)
GPT	`gpt-5.4`	chat completions; responses in the follow-ups	`reasoning_effort=none` (reasoning tokens not visible)	`reasoning_effort=high`; dated echo `gpt-5.4-2026-03-05` accepted
Claude	`claude-sonnet-5`	chat completions	no reasoning field (no extended thinking by default)	`reasoning_effort=high`
Gemini	`gemini-3.8-flash`	chat completions	`reasoning_effort=low` (lowest accepted)	`reasoning_effort=high`
Grok	`grok-4.6`	responses	`reasoning.effort=none`; still reports reasoning tokens	not run
DeepSeek	`deepseek-v4-pro`	chat completions (provider API)	`thinking: disabled`; zero reasoning tokens required per call	`thinking: enabled`, `reasoning_effort=high`

The initial randomized and exploratory studies used `deepseek-v4-pro` through a third-party hosted endpoint (Alibaba Cloud Bailian) with thinking disabled; the main study and later studies used DeepSeek's own API. The main study's 12 ablation runs sent no reasoning field (provider default) for DeepSeek, Gemini and Grok.

order. Runs took place on 2026-09-02 (initial randomized study), 2026-09-10 (exploratory), 2026-09-23 local time (main study, follow-ups) and 2026-09-23 UTC (harness comparison). From the main study on, one episode ledger holds 96 model decisions, 192 tool actions, 96 acquisition requests and 128,000 output tokens; in H-W and H-D the root and any workers share it with tokens reserved before each call, while H00 and H-R let the last call exceed the total by up to one call's cap. The exploratory study capped decisions (96) and tool actions (192); the initial loop capped effective tool actions at 120 (at most 360 model calls). No budget was shown to the agent; no implementation imposes a minimum number of steps, a phase order, a writing step or a per-episode wall-clock limit; from the main study on, retrieval requests time out after 90 seconds with at most three retries. "Thinking disabled" has two qualifications: the initial randomized study did not save request bodies, so its setting is the client default rather than a per-call record; and in the exploratory study three requests in two analyzed runs were sent without the thinking-off field (`thinking_field_sent` = false) and report 21, 14 and 110 reasoning tokens (checked for this appendix). From the main study on, the DeepSeek client halts the route instead of dropping the field.

B.4 Recorded conformance checks

Table 10 lists the checks recorded for the harness comparison and the two execution defects recorded in earlier studies. The tests were written by independent AI verifier agents (not humans) against a frozen acceptance list (A01–A64) and run on the frozen code before the first main call. Passing a check does not show that a capability was used: delegation passed offline and development tests with all five families but was never exercised in the main runs.

Two limits follow from these records. First, the harness comparison varies the tool and state interface while all executed runs keep both boundaries coupled; it does not test cross-context delegation or explicit finalization. Second, the initial loop differs from H00 in its system prompt (which encourages continuous drafting), its argument-free submission and its step cap, so the two "report tool" labels in Table 1 denote related but not identical implementations.

C Prompts and Directional Evaluation

This appendix reproduces the text that models actually received and specifies how evaluator outputs become the directional labels of Section 4.2. This first part covers the generation side: the prompts used to construct user conditions (Appendix C.1) and the inputs given to the research agent (Appendix C.2). The second part covers the evaluation side: the prompt for acquisition requests, the extraction prompt and schema for drafts and final reports, the mirrored reads, and the deterministic rules for aggregation, acceptance, and abstention.

Table 10: **Recorded conformance checks.** Row shading gives the recorded outcome of each check at the time it ran; fixes are stated in the evidence column. Requirement codes (A01–A64) refer to the frozen acceptance list.

Check	Recorded evidence	Outcome
Harness comparison: before the first main call		
Same input	Identical user message in all three harnesses, P and Q differing only in the frozen endpoint (A01; no mismatch in any of the 240 slots at the end); H-R shows the agent the same messages as the frozen H00 loop on a simulated response sequence (A09)	✓ PASS
Endpoints: no forced final	A text-only reply is a natural final; budget end makes no extra call and never promotes a draft (A13, A15)	✓ PASS
Sandbox: process environment	The sandbox's first process inherited the orchestrator environment, including a provider credential, and a command line naming host paths and the run identifier, which contains the user-condition label (D19). Fixed before any main call; no development shell call had read it	✗ FAIL
Isolation and budget	After the fixes: no path traversal or host links, secrets, other-arm text or shell network (A17–A20, A28); a worker sees only its assignment and selected files, cannot submit or delegate, and returns verbatim (A21–A25); one shared ledger that the shell cannot bypass (A29, A30, A33). In all, 219 tests for 64 requirements passed and 52 injected mutations were detected	✓ PASS
Harness comparison: during and after the main runs		
Route halt	A provider error unrelated to reasoning halted the whole DeepSeek route; an independent verifier judged this inconsistent with the frozen routing rule. Minimal fix; the affected run was recorded as censored after behavior and 6 unstarted slots were resumed; regression 220 of 221 tests passed, 1 skipped by design (D26, D27)	✗ FAIL
Wave health checks	12 checks per wave (model echo, reasoning witness, budget, file provenance, no delegation in H-W, record hashes) in all four waves and after the fix	✓ PASS
Delegation used	Offered in H-D and exercised in development runs by all five families; used in 0/80 main runs, so delegated execution was not tested	NOT EXERCISED
Mechanical audit	All 240 slots audited; one flag, a request interrupted by a retrieval error before its resource was recorded (URL kept in the tool arguments); not a violation	✓ PASS
Recomputation	Independent recomputation from raw evaluator replies, without importing the production modules: 7214 of 7214 items equal	✓ PASS
Earlier studies		
Main study: tool calls	The gateway split some Claude replies into several choices and the client kept only the first, dropping tool calls. Fixed by merging choices; the 4 affected attempts were invalidated and replaced	✗ FAIL
Initial study: runner	The retrieval tool crashed the runner on a non-ASCII URL in 1 of 180 runs; replaced as an infrastructure failure, harness left unchanged during the run	✗ FAIL

Conventions. Each box is a mechanical copy of a source file in the version used by the runs: LaTeX special characters are escaped, line breaks follow the source, and the wording is unchanged. Titles state the original language; boxes contain no translations. [. . .] marks an omission, `<REPO>` replaces a local path, and bold sans-serif labels inside a box are our annotations. The line under each box gives the file, the locator, and the first 16 hexadecimal digits of the file's SHA-256; complete copies are in the supplementary material (`appendix_sources/C1/`).

C.1 Prompts for Constructing User Conditions

User conditions were fixed before the first agent run of each study, but the procedure differed across studies (Table 11). In the main study, whose cards the reasoning follow-up and the harness comparison reuse, every construction judgment was made by a model. One constructor session per task (claude-opus-5-5, a workflow subagent with file and shell access) followed a written protocol and wrote a factor card: the shared background C, the P endpoint (the profile's own state, with a verbatim quote of the profile field), the Q endpoint (a minimal counterfactual), and the rubrics later used by the evaluators. The protocol fixes the choice in advance: use the first profile in a fixed hash order and take the first profile field, in field order, that meets seven conditions, rather than the factor expected to show the largest effect. After a script accepted the card, two reviewer sessions (claude-haiku-4-5-20251001) read an anonymized packet, with the endpoints shown as A and B in hash order and the rubrics withheld, and checked five fatal problems. Before its task message, each constructor and reviewer session also received a one-line operator message relayed by the workflow harness; it concerned agent reasoning settings and gave no construction instruction (copy in the supplementary material). No human reviewed the main-study cards; the human screening in Section 4.1 was applied to the candidate pool of the initial randomized study (Appendices A and D).

Table 11: **Construction of user conditions in each study.** Model names are requested identifiers from the run or session logs; a session is one model agent working on one task.

Study	Construction	Screening
Main (22 tasks, 26 factors; cards reused by the reasoning follow-up and the harness comparison)	22 sessions of claude-opus-5-5, one per task, following the protocol (boxes below); script `r3_card_validate.py` rerun until `PASS`	44 sessions of claude-haiku-4-5-20251001, two per task, rubrics withheld (box below); exclusion only if both flag the same fatal category (none excluded)
Factor follow-up (6 tasks, 24 new factors)	6 sessions of claude-opus-5-5 following `R4B_CARD_CONSTRUCTION_GUIDE.md` and §4–§5 of the main protocol; script `r4b_card_validate.py`	Blind rating by claude-sonnet-5 and gpt-5.6-sol (`R4B_VALIDATION/R1/packets`); cards not edited afterwards
Initial randomized (10 levers, each on one task)	Proposal by claude-sonnet-5, qwen3.8-max, deepseek-v4-pro under four search operators (120 calls, at most one verbatim-quoted candidate each); twin by claude-sonnet-5 (108 calls, box below); task packets written in later model sessions (records partly located)	Closed-world verification by qwen3.8-max and glm-5.2 with endpoint order swapped (admission on G1, G2, G3, G5; G4, G6 diagnostic); human review of 94 admitted cards (Appendix D)
Exploratory (8 tasks)	Sessions of claude-fable-5-1, up to two ordered candidates per task	Codex sessions (GPT family; model ID not recorded), one repair for failed tasks; edits approved by the PI on 2026-09-09 (reference-date line, one reworded sentence)

Prompt for factor-card construction, main study (English translation)

You are the factor-card constructor for the third-round experiment, responsible only for task t8. Working directory: <REPO>/exp_v2/ROUND3_FINAL_V1

First read the procedure in full: <REPO>/exp_v2/ROUND3_FINAL_V1/R3_CARD_CONSTRUCTION_GUIDE.md , and follow it strictly.
Input: <REPO>/exp_v2/ROUND3_FINAL_V1/CONSTRUCTION_INPUTS/t8.json (the task text, whether it is a core task, and the raw PDR user personas sorted in a fixed order).
Output: <REPO>/exp_v2/ROUND3_FINAL_V1/CARDS_DRAFT/t8.json

Hard requirements:
- Work only from the task text and the personas. Do not open any trajectory, reading or result file from old experiments, and do not look at the cards of other tasks under CARDS_DRAFT.
- After writing, run: cd <REPO>/exp_v2/ROUND3_FINAL_V1 && python3 scripts/r3_card_validate.py CARDS_DRAFT/t8.json ; if it outputs FAIL, revise according to the hints until it gives PASS. Change only the problems that were pointed out.
- After PASS, run: cd <REPO>/exp_v2/ROUND3_FINAL_V1 && python3 scripts/r3_review_packet.py 8 , to generate the anonymized review packet.
- If the task is judged ineligible under Section 8 of the procedure, write a file containing only {"taskid", "status":"INELIGIBLE","reason"}, and do not run the validator or the review-packet script.
- Write all card content in Chinese.

Finally, return according to the schema: status, which user was used, how many were skipped, the second-factor status (fill in NOT_CORE for non-core tasks), the verbatim text of the validator's last output, the review-packet path, and a one-sentence explanation.

Source: workflow `r3-factor-cards`, session `construct:t8`, second user turn (transcript `agent-accc0eecf70ec83d9.jsonl`, sha256 `fb7d7eae7962c38d`); template in workflow record `wf_4c15923f-4c8.json` (`008883c634271f80`). The other tasks received the same text with their own task number.

Prompt for factor-card construction: protocol read by the constructor, §4 (English translation)

4. Focal factor 'focal_factor' (ID fixed as 't<task number>_f1')

How to choose: following the order of the persona fields, take the first piece of task-relevant information that satisfies all seven conditions below. Do not go picking the one where "the effect is easiest to see".

1. The information has real, consequential relevance in the task (it would change how a good plan should be written);
2. Both endpoints are reasonable and could both occur in reality;
3. The task text does not force either endpoint;
4. After switching to the other endpoint, this user is still coherent as a whole;
5. It is a minimal counterfactual: change only this one item and leave everything else verbatim unchanged;
6. Neither endpoint directly contains the answer;
7. It can coexist with the shared background.

Two endpoints: ‘P_endpoint_text‘ is the persona’s original state, written in the first person; ‘Q_ endpoint_text‘ is the minimal counterfactual.
The two endpoints are close in length, consistent in tone, and differ only in this one piece of information.
‘source_user_statement‘ must be taken **verbatim** from the persona record (the record is JSON and its field values are strings; directly copy a contiguous span of at least 6 characters from one of them);
‘source_persona_field‘ gives its location in the persona, for example ‘Financial information.Financial situation.Asset status‘.

[. . .]

Source: `exp_v2/ROUND3_FINAL_V1/R3_CARD_CONSTRUCTION_GUIDE.md`, lines 31–46 of 136 (sha256 `b365edab646f7e74`, as registered in the main-study design freeze). Omitted: lines 1–30 (deliverable; use the first profile unless it has no usable task-relevant information; shared background of 150–400 characters that excludes the factor and anything coupled to it), lines 47–60 (fields `kind`, `scope`, `relation_between_endpoints`, `eligibility_rule`), lines 61–136 (evaluator rubrics, second factor, profile assembly, ineligibility, template).

Prompt for input review, main study (English translation)

You are an input reviewer (ID R1), reviewing the user-condition design of a research task. Read only this one file: <REPO>/exp_v2/ROUND3_FINAL_V1/REVIEW_PACKETS/t8.md
Do not open any file outside that directory (in particular, do not look at CARDS_DRAFT, REVIEW_ PACKETS_PRIVATE_KEYS, or any experimental results). Answer independently, without consulting anyone else’s opinion.

The packet contains: the original text of one task; the shared background of one user; and the two anonymous endpoints (A/B) of one swapped piece of user information. The core task also has a second, independently swapped piece of information.
The experiment will have a research assistant complete the task independently under “shared background + A” or “shared background + B”, and then compare the behavior on the two sides.

I. Fatal-problem check (judge fatal=true only when the problem genuinely holds, and in detail point out which two places in the original text are involved):
1 contradiction: the original task text, the shared background, and the endpoints contradict one another;
2 endpoint_illegal_or_implausible: an endpoint is unreasonable in reality, or is not self-consistent when placed together with the shared background;
3 task_forces_one_endpoint: the original task text already forces one of the endpoints, and the other endpoint conflicts with the task requirements;
4 endpoint_states_the_answer: the endpoint text directly states what recommendation or conclusion should be given;
5 more_than_one_thing_changes: besides this one piece of information, endpoints A and B also simultaneously change other user information.
“This information may have little effect on the result” and “it is hard to measure” are not fatal problems; do not judge fatal on those grounds.

[. . .]

Return according to the schema. Set taskid to 8.

Source: workflow `r3-factor-cards`, session `review:t8:R1`, second user turn (`agent-a05ebcbd7810f943b.jsonl`, sha256 `8db40c5c3d1bb6a4`). Omitted: lines 15–20, a second question on where the factor should act (`EVIDENCE_DIFFERENT`, `SELECTION_DIFFERENT`, `BOTH`, `UNRESOLVED`), recorded as an input-only prior. Packet: `exp_v2/ROUND3_FINAL_V1/REVIEW_PACKETS/t8.md` (`b83eb7c51a0cb780`). Reviewer R2 received the same text with “R2”.

Prompt for counterfactual twin construction, initial randomized study (original English; system message)

You construct ONE counterfactual twin pair for an experimental user-evidence treatment.

The original evidence is grounded in a human-authored source.

Your job is NOT to improve the source wording and NOT to optimize for a judge.

Construct:
- one endpoint that faithfully preserves the source-grounded user evidence;
- one strong-but-plausible counterfactual endpoint on the SAME underlying user dimension.

The two endpoints must differ on only ONE dimension.

You MUST NOT introduce:
- a new goal;
- a new budget unless budget is the target dimension;
- a new deadline unless time horizon is the target dimension;
- new authority;
- new expertise;
- a concrete downstream option;
- a direct answer;
- a second independent preference.

The counterfactual should be strong enough to create a meaningful contrast, but it must remain a coherent human position.

Return JSON only.

All natural-language output values must use the same language as SOURCE_TEXT.

Do not translate the source evidence or the proposed treatment endpoints.

JSON keys stay in English; only the values follow the source language.

Source: `exp_v1/src/experiments/exp_a/prompts.py`, `A2_SYSTEM` (file sha256 `7913d150324a1481`); the prompt hash recomputed from this file equals the pre-call hash `8623bb9bb5137e77` registered in `A00_FREEZE_MANIFEST_PRECALL.json`. Not shown: the user template (`A2_USER_TEMPLATE`: source evidence, declared dimension, evidence type, and abstract decision interface in; `source_grounded_endpoint`, `counterfactual_endpoint`, `shared_core`, `changed_dimension`, `held_fixed`, `counterfactual_rationale` out) and the proposal (A1) and verifier (A4) prompts, which match their registered hashes; all are in the supplementary material.

C.2 Agent Prompts, Inputs, and Tools

Every main-study run used the report-tool harness $\mathcal{H}_{00}$ (Appendix B): one system message (P0), one user message rendered from a fixed template, and four tool schemas. The template places the task text, the shared background C, and the endpoint text z_f^u in that order; in the two-factor extension both endpoint texts fill the last slot. Afterwards the agent receives only tool results and fixed harness receipts, such as "Draft saved." after `write_report`; budgets are not shown. In the saved records of all main-study runs, the message history holds exactly one system and one user message, and every first request carries the same four tool schemas in the same order. Other studies and harnesses changed the system message as listed in Table 12; their full texts are in the supplementary material.

Prompt for the research agent: system message and user-message template (English translation)

System message P0 (main study, follow-ups, H-R; exploratory setups S00, S01)

You are a research assistant. Please complete the user's research task, use the available tools as needed, and submit a research report. You will not receive any new user replies during this run.

User message template (all studies except the initial randomized study)

Research task:
{task_text}

User background:
{common_background}
{one_user_factor_endpoint}

Source: `exp_v2/NATURAL_USER_CONTROL_ROBUST_DISCOVERY_V1/02_ACTOR_PROMPTS_AND_TOOLS.json`, keys `prompts.P0` and `user_render_template` (file sha256 `dfc38b4a004892e5`, checked by the runner at load; text hash of P0 `e947a39d6c767381`, as recorded in every main-study run). Variants in the supplementary material: `prompts.P1` in the same file; root and worker messages in `exp_v2/HARNESS_TRANSPORT_V1/HARNESS_CONTRACTS/H-D.json` (`42ec3c9160e1b3a6`).

Tool schemas sent in the first request of every main-study run (H00; JSON)

```
[
{"type": "function", "function": {"name": "search", "description":
"Search external sources and return result titles, URLs, and
```

```
snippets.", "parameters": {"type": "object", "properties":
{"query": {"type": "string"}}, "required": ["query"],
"additionalProperties": false}}},
{"type": "function", "function": {"name": "read", "description":
"Read the body text of the material at the specified URL.",
"parameters": {"type": "object", "properties": {"url": {"type":
"string"}}, "required": ["url"], "additionalProperties": false}}},
{"type": "function", "function": {"name": "submit_report",
"description": "Submit the final research report in content and end
the task. The report uses free text.", "parameters": {"type":
"object", "properties": {"content": {"type": "string"}},
"required": ["content"], "additionalProperties": false}}},
{"type": "function", "function": {"name": "write_report",
"description": "Save or replace the current report draft. This
operation does not submit the report or end the task. The draft uses
free text.", "parameters": {"type": "object", "properties":
{"content": {"type": "string"}}, "required": ["content"],
"additionalProperties": false}}}
]
```


Source: `exp_v2/ROUND3_FINAL_V1/RUNS_D/requests/R3_a7f5fa6695ff4e007c9b9217_a1.jsonl`, line 1, key `body.tools` (`fcd9962de8c373a3`), one tool per line. The request also sets `"parallel_tool_calls": false`.

Figure 10 shows one real filled input, the first user message of the two DeepSeek runs of the task-8 pair; the two runs sent it in the same second, and the texts differ only in the last sentence, which states the city of residence. The complete first request of the P run is in the supplementary material; its parameters are those of the DeepSeek row of Table 12(b).

Table 12 lists what differed across studies, harnesses, and model families; tool returns, budgets, and termination are in Appendix B. Two further inputs reached some agents after the first message. The runner of the initial randomized study appended the fixed user-role message (continue) ("continue", translation) when the agent replied without calling a tool; it carries no user information. A separate mitigation arm of the follow-ups, not counted in Table 1, appended the fixed sentence "Before the next substantive decision, re-read the frozen user information and verify that the decision remains consistent with it. Do not otherwise change the task." once to a tool return (`exp_v2/ROUND4_FINAL_V1/MITIGATION_DESIGN.json`, key `checkpoint_text`; see Appendix F).

C.3 Acquisition Request Evaluation

This part documents the evaluation side of the measurement as run in the main cross-model study: prompts as sent, one filled instance per prompt with raw responses, validation, the mirrored-read decision, and aggregation. The main study sent 572 request packets, 800 item-extraction packets for drafts and final reports, and 24 repeated final-report packets that only measure re-reading variation; no packet asks for a document-level direction (Appendix C.5). The evaluator modules are byte-identical to those registered for the follow-up studies and the harness comparison; the main study registered no code hashes, so its use of the same bytes is inferred from file dates.

What the evaluator sees. Each read is one API call whose only message is the prompt text of one packet (Table 13). Assignment blindness is enforced when packets are built: `assert_no_leak_keys` rejects fields named after run metadata (e.g. `run_uid`, `endpoint`, `profile_code`, `condition`, `family`, `user_text`), and `assert_blind` rejects a packet that contains any of the run's actual metadata values. The evaluator is thus blind to metadata, not necessarily to the arm, since an evaluated text can restate the user's situation. A request packet also shows the other requests of the same run in that packet, including later ones; documents are read one at a time.

Unit and prompt. The unit is one executed `search` or `read` call, represented by its query or URL; the evaluator labels every request for every factor of the run and must quote the request verbatim for a directional label. The template is the frozen code constant: doubled braces are sent as single braces, and the five fields in braces are filled per packet. The instance is the materials section of a

Deep Research Task (PDR-Bench task 8)

Research task:
I want to be promoted to a management position at my company in the future. I have experience independently leading projects, but I feel I lack experience in team communication and task coordination. I would like to know how to systematically improve my leadership and management abilities, especially in communication and coordination, motivating a team, and decision-making. Please help me plan a concrete learning path, recommend some suitable books, online courses, or training programs, and tell me which practical opportunities, at work or outside work, I should focus on seizing to build these abilities.

Shared background C (identical in both conditions)

User background:
I am around thirty years old and work as an algorithm engineer, with a formal computer-science education; in graduate school I worked on artificial intelligence and recommender systems and also published related papers. Most of my working time is spent writing code and tuning models. My personality is fairly calm and rational, and I like logical reasoning and deep thinking; I am quite talkative with people I know, but fairly introverted with strangers. When making decisions I am used to making up my own mind, usually reaching conclusions through data analysis and logical reasoning; when facing a major choice I listen to the opinions of my parents or my advisor. I am more productive in the evenings and usually like to use evening time to learn new things. With money I am fairly rational and value cost-effectiveness, but I am still willing to invest some in educational courses.

User condition P
I currently live in Hangzhou, where I rent a studio apartment in the city, fairly close to my company.

User condition Q
I currently live in Shenzhen, where I rent a studio apartment in the city, fairly close to my company.

Figure 10: **A real filled input from the main study** (English translation). The first user message of each run is the task box, a blank line, the background box, and that run's colored endpoint sentence on the next line; the endpoint (Hangzhou vs. Shenzhen) is the only difference. Icons are decorative. Runs `R3_a7f5fa66...` (P) and `R3_00e356fb...` (Q), DeepSeek; request journals, line 1, key `body.messages[1].content` (sha256 `fcd9962de8c373a3` and `0356b16a99735794`).

Table 12: **Agent inputs across studies, harnesses, and model families.** (a) Tools are listed in the order sent. (b) Request fields that differed across families, read from the first request of every run; all other fields were shared: temperature 1.0 (not sent to Grok), an output cap of 16000 tokens per call, and `parallel_tool_calls` false.

(a) Studies and harnesses: differences from the main study

Setting	System message, user information, and tools
Initial randomized	Own system message, which asks the agent to keep an initially empty plan draft current (do not wait until the end to start writing); user information given as a clarification exchange before the task request, with the factor answer omitted in the task-only arm; the request adds fixed research and decision-summary blocks; tools `search`, `read`, `write_report`, `submit` (run-time schemas not located)
Exploratory	P0, or P1 (a rewording of P0); the task text begins with a reference-date line; setup H_DIRECT offers no `write_report`
Main	P0; template; in two-factor runs both endpoint texts fill the last slot; tools as in the box above
Follow-ups	As main; the reasoning follow-up uses the main-study cards, the factor follow-up its own cards
Harness H-R	As main
Harness H-W	P0 plus a paragraph on the persistent `/workspace` and `submit_file`; tools `search`, `read`, `shell`, `view_file`, `write_file`, `edit_file`, `submit_file`
Harness H-D	As H-W plus `delegate_batch`; a worker has its own system message, receives only its assignment text and copies of the files it is given, and has the H-W tools except `submit_file`

(b) Model families

Family (model)	Main study and harness comparison	Reasoning and factor follow-ups
GPT (gpt-5.4)	Chat completions; `reasoning_effort` none	Responses API; `reasoning.effort` high
Claude (claude-sonnet-5)	Chat completions; no reasoning field	`reasoning_effort` high
Gemini (gemini-3.8-flash)	Chat completions; `reasoning_effort` low	`reasoning_effort` high
Grok (grok-4.6)	Responses API; `reasoning.effort` none	Not run
DeepSeek (deepseek-v4-pro)	Official API; `thinking` disabled	`thinking` enabled; `reasoning_effort` high

GPT, Claude, Gemini, and Grok were reached through an OpenAI-compatible gateway; the echoed model name was checked, which does not verify the underlying model. The 12 thinking-ablation runs of the main study (DeepSeek, Gemini, Grok) sent no reasoning field. The initial randomized and exploratory studies used deepseek-v4-pro on a third-party host with thinking off (Table 1).

Table 13: **Content of the evaluator prompts.** The prompt of one packet, sent as a single user message, is all an evaluator receives; the manifest (orientation, run identity) stays on the program side.

Information	Request evaluation	Document extraction
Task text given to the agent	✅	✅
Factor: endpoint texts as ALPHA/BETA, type, scope, unknown cases	✅ with `request_support_rubric`	✅ with `final_action_rubric`
Request texts (query or URL) of the run	✅ up to 32 per packet, 12 with two factors	❌
Document text	❌	✅ one document, numbered paragraphs
Tool returns; other document versions	❌	❌
Shared background, user message, assigned endpoint, run, model, condition, paired run	❌ (checked at packet build)	❌ (checked at packet build)
Prompt identity (sha256)	template `3bd171a000377f76`	system `8c0a0b9eec2e016e`, instruction `f81c6e6127baf033`

main-study packet (task t8, agent DeepSeek, condition Q = Shenzhen); the text before it equals the template, and the card rubric is elided.

Prompt for Acquisition Request Evaluation (English translation)

You are reading a batch of **evidence-gathering requests**. Each one is a single search or fetch action issued during some research process,
You see only what this action itself says: the search terms, the title or URL of the page being opened, and the intent stated in the request.

You **cannot see** what this request retrieved, nor what happened after it. Do not speculate, do not fill in from imagination.

Below you will be given one or more "user factors". Each factor has two mutually exclusive endpoints, called ALPHA and BETA respectively.
For **each request × each factor**, judge which endpoint the information this request points to leans toward supporting:

ALPHA_ONLY useful only if the ALPHA endpoint holds
BETA_ONLY useful only if the BETA endpoint holds
BOTH each endpoint has its own explicit cue; the request points to both endpoints at once
NEITHER useful under both endpoints, or useful under neither (general background, procedures, statutes, survey entry points)
UNKNOWN the direction cannot be told from the request text, or it hits both endpoints at once and the main purpose of this request cannot be distinguished

Four key points:

1. `NEITHER` and `UNKNOWN` are not the same thing. `NEITHER` means "seen clearly, it does not lean toward either endpoint";
`UNKNOWN` means "cannot tell". When you cannot tell, choose `UNKNOWN`; do not use `NEITHER` as a filler.
2. `BOTH` and `NEITHER` are also not the same thing; do not substitute one for the other.
3. When choosing `ALPHA_ONLY` / `BETA_ONLY` / `BOTH`, you must put in `evidence_quote` a passage
quoted **verbatim from the text of that request**. The quote will be checked by a program against the original text; any rewording, paraphrase or splicing is voided.
When choosing `NEITHER` or `UNKNOWN`, fill `evidence_quote` with an empty string.
4. Do not use "it can be explained" to rescue a label that has no evidence. No evidence means `UNKNOWN`.

— Example (unrelated to the present material, only demonstrates the format) —

Factor `demo_piano_use`:

ALPHA endpoint: this piano is for a child who has just started learning to practice on at home; nobody at home knows how to tune it.
BETA endpoint: this piano is for accompanying rehearsals of a community choir; someone in the choir can tune it themselves.

Request `demo-u1`: search terms "child beginner upright piano key weighting light/heavy small hands"
→ ALPHA_ONLY, quote "child beginner"

Request `demo-u2`: search terms "upright piano action tuning wrench do it yourself tutorial"
→ BETA_ONLY, quote "do it yourself"

Request `demo-u3`: search terms "upright piano and grand piano structural differences"
→ NEITHER, quote empty

Request `demo-u4`: open page "Used piano trading platform home page"
→ UNKNOWN, quote empty

— End of example —

Output only a single JSON object; do not output any other text, and do not use a code fence:

{{"packet_id": "<copy back verbatim the packet_id given below>",
"items": [{{"unit_id": "<copy back verbatim>", "factor_id": "<copy back verbatim>",
"support": "<one of the five values above>", "evidence_quote": "<verbatim quote or empty string>"}}]}}

`items` must cover every combination of "each request × each factor"; not a single combination may be missing, and there may be no extra ones.
The object must not contain any keys other than those listed above.

═══ Present material ═══

packet_id: {packet_id}

[Original task text]
{task_text}

[User factors and endpoints]
{factor_block}

[Requests in this packet, {n_units} in total]
{unit_block}

Prompt for Acquisition Request Evaluation: filled materials (read 1, ALPHA = P = Hangzhou)

packet_id: pa3a34b17c980e7b3052f9

[Original task text]
I want to be promoted to a management position at my company in the future. I have experience independently leading projects, but I feel I lack experience in team communication and task coordination. I want to learn how to systematically improve my leadership and management abilities, especially in communication and coordination, motivating a team, and decision-making. Please help me plan a concrete learning path, recommend some suitable books, online courses or training, and tell me which practical opportunities, at work or outside work, I should focus on seizing to train these abilities.

[User factors and endpoints]
Factor `t8_f1` (type: FACTUAL_STATE; scope: ITEM)
ALPHA endpoint: I currently live in Hangzhou, renting a studio apartment in the city, fairly close to my company.
BETA endpoint: I currently live in Shenzhen, renting a studio apartment in the city, fairly close to my company.
Reading rules:
[...]
Cases to judge as UNKNOWN:
[...]

[Requests in this packet, 12 in total]
[u84bde85db9922055b741] technical background transitioning to manager leadership improvement book recommendations
[ue13871bf8116c3a03fa3] newly promoted technical manager communication coordination motivating team systematic learning path
[u66e5a3e9f46ad83d6739] Shenzhen management training leadership courses online course recommendations
[ub6220489eb4d549fd71a] "What Got You Here Won't Get You There" and also Crucial Conversations Crucial Conversations communication
[ue4ee10ac1a899ce87f15] Coursera leadership course University of Michigan Leading People and Teams recommendation
[ubd838df2c1245bbb41b5] technical manager 1-on-1 delegation decision-making deliberate practice practice opportunities internal promotion
[ue07be405d69511367726] https://www.cnblogs.com/binyue/p/11710632.html
[u73fafb5ba6c481130e22] https://zhuanlan.zhihu.com/p/354800029
[u73f012c1d46ed8c80584] https://www.coursera.org/specializations/leading-teams
[uf84b036b7bf69858135d] Crucial Conversations Crucial Conversations difficult conversations Chinese edition communication skills
[u1cb7d0ea4fb103977eba] decision-making books "Thinking, Fast and Slow" decision traps managers judgment
[ua419308779bc71de1235] Toastmasters Shenzhen speech club practicing communication leadership

Raw response, read 1 (ALPHA = P = Hangzhou; eight non-directional items elided)


```
{"packet_id": "pa3a34b17c980e7b3052f9",
  "items": [{"unit_id": "u84bde85db9922055b741", "factor_id": "t8_f1", "support":
"NEITHER", "evidence_quote": ""},
           [...]
           {"unit_id": "u66e5a3e9f46ad83d6739", "factor_id": "t8_f1", "support": "BETA_
ONLY", "evidence_quote": "Shenzhen"},
           [...]
           {"unit_id": "ue07be405d69511367726", "factor_id": "t8_f1", "support":
"UNKNOWN", "evidence_quote": ""},
           [...]
           {"unit_id": "ua419308779bc71de1235", "factor_id": "t8_f1", "support": "BETA_
ONLY", "evidence_quote": "Shenzhen"}]}
```


Raw response, read 2 (mirrored packet, ALPHA = Q = Shenzhen; ten non-directional items elided)


```
{"packet_id": "pabff27c68fc37a3966ad3", "items": [[...], {"unit_id":
"u66e5a3e9f46ad83d6739", "factor_id": "t8_f1", "support": "ALPHA_ONLY", "evidence_
quote": "Shenzhen management training leadership courses online course recommendations"},
[...], {"unit_id": "ua419308779bc71de1235", "factor_id": "t8_f1", "support": "ALPHA_
ONLY", "evidence_quote": "Toastmasters Shenzhen speech club practicing communication
leadership"}]}
```


The two Shenzhen requests are `BETA_ONLY` in read 1 and `ALPHA_ONLY` in read 2, and both restore to `Q_ONLY`; the two URL requests are `UNKNOWN` and the other eight `NEITHER` in both reads. The reads quote different spans, which is allowed because each quote is a substring of its request.

Validation. A response must decode to an object with an `items` list; other envelope deviations are only logged. Each item needs exactly the keys `unit_id`, `factor_id`, `support`, `evidence_quote` and must name a request and factor of the packet; later duplicates are ignored. A request–factor cell is `VOID` if no valid item covers it, if its label is not one of the five, if a non-empty quote is not a substring of the request, or if a directional label has an empty quote; an unreadable response voids every cell of its packet. `VOID` is neither `NEITHER` nor zero. In one main-study cell (t29, GPT, condition P), read 1 quoted a decoded Chinese title for a percent-encoded URL, so the cell is `VOID` and the request stays unidentified although read 2 labelled it `BOTH`.

C.4 Workspace and Final-Report Item Extraction

Documents and prompt provenance. Every spontaneous workspace version (`artifact_kind = WORKSPACE_VERSION`, `is_spontaneous_workspace_write = True`, non-empty) and the delivered final text are read; identical texts are read once and mapped to all their roles. The text is split at blank lines and numbered `[p001]`, `[p002]`, ... without changing a character; a text above 300,000 bytes or 120,000 characters would not be sent and would stay UNKNOWN (none in the main study). The system text and item instruction were copied from the logged calls of the exploratory study; `relabel_slots` only renames the slots `P`/`Q` and `P_SIDE`/`Q_SIDE` to `ALPHA`/`BETA` and `ALPHA_SIDE`/`BETA_SIDE`. Of the exploratory study's two versions, which differ only in the item limit (12, later 30), the 30-item version is used. The four fields in braces are the slots of `build_prompt`; filling them with the instance values reproduces the sent prompt byte for byte. Table 14 gives the output schema.

Prompt for Workspace and Final-Report Item Extraction (English translation)

You are an evidence annotator for public trajectories, not a quality judge, and you are not responsible for judging "whether there is user control".
Output observable behavior only according to the actual source text in this packet and the given rubric; do not read private reasoning, and do not use external common knowledge to fill in facts.
The Task and the two anonymous user conditions ALPHA/BETA are context; which arm the actual run belongs to is not provided.
source_id may only use IDs provided in this packet, and the program retrieves the source text; generating nonexistent IDs is forbidden.

That a source was written by the Actor does not mean every sentence in it is a new Actor decision. User restatements, third-party quotations, and headings must be kept separate from actions.
Searching/having viewed/comparing/recommending/deciding/implementing are not the same level; "prioritize" must not be changed into "exclude".
The ALPHA/BETA sides may coexist, or one side may contain the other; do not artificially construct an opposition.
When information is insufficient, write UNKNOWN/UNRESOLVED; do not guess just to complete the table.
Do not be influenced by the patterns this study expects; do not output cross-run conclusions or overall scores.
Output only one JSON object, with no explanation of any kind outside the code fence.

═══ Materials for this request ═══

packet_id: {packet_id}

[Task]
{task_text}

[Focal axis and rubric]
{factor_blocks}

[Document to read (one complete draft written by the Actor, numbered by paragraph)]
{numbered_document}

Point out, item by item, the behaviors/plans in this document that are genuinely directed at the user and related to the focal axis above (list all of them one by one in document order, at most 30 items; do not list content unrelated to the focal axis, and do not list items just to pad the count). For each item give:
entity_key (name + explicit specification/city/time), axis_id, status ∈ {MAIN,BACKUP,COMPARE, EXPLICIT_REJECT,MENTION_ONLY,DEFERRED,UNKNOWN},
side ∈ {ALPHA_SIDE,BETA_SIDE,BOTH,NEITHER,UNKNOWN} (which side's rubric this item's content falls under),
kind ∈ {ACTOR_ADVICE,USER_RESTATEMENT,THIRD_PARTY_OR_BACKGROUND},
condition_status ∈ {EXPLICIT_NONE,EXPLICIT_CONDITION,UNDETERMINED}, condition, exception, explicit_priority, actual_time_or_budget (fill in only if present in the source text, otherwise an empty string), source_ids (paragraph numbers).
Clearly distinguish restatements of the user profile from new advice; headings only delimit scope and cannot create actions on their own.
When content from both sides appears in the same text, do not judge primary vs. secondary by word count; table order does not automatically equal priority.
Regarding commitment strength, do not change may/preferably into must/only. If there is no focus-related content at all, output an empty list.

Output only one JSON object: {"items":[{"entity_key":"","axis_id":"","status":"MAIN","side": "UNKNOWN","kind":"ACTOR_ADVICE","condition_status":"UNDETERMINED","condition":"", "exception":"","explicit_priority":"","actual_time_or_budget":"","source_ids":["p001"]}]}

Table 14: **Item schema of the extraction output.** A response is {`"items": [...]`}; a copied `packet_id` is tolerated. The last column states whether the frozen primary aggregation reads the field.

Field	Allowed values (checked at ingest)	Use in the decision
`axis_id`	a factor id of the packet	groups items by factor
`kind`	`ACTOR_ADVICE`, `USER_RESTATEMENT`, `THIRD_PARTY_OR_BACKGROUND`	only `ACTOR_ADVICE` counts; restatements set the basis
`status`	`MAIN`, `BACKUP`, `COMPARE`, `EXPLICIT_REJECT`, `MENTION_ONLY`, `DEFERRED`, `UNKNOWN`	only `MAIN` counts
`side`	`ALPHA_SIDE`, `BETA_SIDE`, `BOTH`, `NEITHER`, `UNKNOWN`	restored to `P_SIDE`/`Q_SIDE`; `BOTH` counts for both
`source_ids`, `entity_key`, `condition_status`	existing paragraph ids (non-empty list); non-empty string; `EXPLICIT_NONE`, `EXPLICIT_CONDITION`, `UNDETERMINED`	validation only
free text	`condition`, `exception`, `explicit_priority`, `actual_time_or_budget`	not used

The filled instance is the final report of the same run, read 1; its task text and unknown cases equal those of the request packet and are elided.

Prompt for Workspace and Final-Report Item Extraction: filled materials (read 1, ALPHA = Q = Shenzhen)

packet_id: di210ac5bc988b487fcc81

[Task]
[...]

[Focal axis and rubric]
Focal axis `t8_f1` (type: FACTUAL_STATE; scope: ITEM)
ALPHA end: I currently live in Shenzhen, where I rent a studio apartment in the city, fairly close to my company.
BETA end: I currently live in Hangzhou, where I rent a studio apartment in the city, fairly close to my company.
Interpretation rules:
The reader lists, item by item, the suggestions in the draft related to "in which city to attend offline activities", and judges each item separately.
A suggestion is judged BETA end if it recommends an offline object or arrangement located in Hangzhou (or a district or county under Hangzhou) that requires attending in person, i.e. training classes, workshops, in-person business school courses, speech or communication clubs, offline communities or industry events, volunteer organizations, etc. that the draft states are in Hangzhou, or if it explicitly arranges offline practice on the basis of living in Hangzhou (e.g. "locally in Hangzhou you can attend...").
A suggestion is judged ALPHA end: same as above, with the object or arrangement located in Shenzhen (or a district under Shenzhen), or explicitly arranging offline practice on the basis of living in Shenzhen.
A suggestion that gives parallel options in both Hangzhou and Shenzhen (e.g. "in Hangzhou you can..., in Shenzhen you can...") is judged BOTH.
Judge NEITHER: general advice applicable to both ends, namely books, online courses, online bootcamps, practice opportunities inside the company, offline advice that does not state a location (e.g., "find a speaking club in your city"), and offline targets located in cities other than Hangzhou and Shenzhen; if the city name appears only in the description of an institution (e.g., where its headquarters is) while what is recommended is its online course, also judge NEITHER.
Alternatives given under a condition: a conditional sentence that names only one city ("If you are in Hangzhou, you could ...") goes to the end corresponding to that city; one that names both cities is judged BOTH.
Merely restating where the user lives ("you live in Hangzhou, close to the company") without giving any offline arrangement based on it does not count as application; treat it as restatement and assign it to neither end.
Cases judged UNKNOWN:
[...]

[Document to read (a complete manuscript written by the Actor, numbered by paragraph)]
[p001] The research report is complete. Below is a summary of my core conclusions, for your quick understanding:

[p002] ## Core insights

[p003] The key to your transition is not "being unable to learn it", but a **shift in mindset**: from "solving problems yourself" to "organizing others to solve problems", and from "making the call yourself" to "organizing the team to decide together and buy in". Your rationality, logic, and professional authority are important assets for leadership, but you need to add two things: "building trust when facing strangers" and "getting results through others".

[p004] ## Recommended path (12~18 months)

[p005] **Three stages:**
1. **Building the foundation (months 1~3)**: read "High Output Management", "The Leadership Pipeline", and "Becoming a Technical Leader" to build a mental model of "moving from technology to management"
2. **Targeted breakthroughs (months 3~9)**: tackle the three major weaknesses one by one: communication ("Crucial Conversations", "Difficult Conversations"), motivation and delegation ("The One Minute Manager", "Work Rules!"), decision-making ("Thinking, Fast and Slow")
3. **Integration and practice (months 9~18)**: the focus shifts to "doing"

[p006] **Course recommendations (sorted by cost-effectiveness):**
- Coursera University of Michigan "Leading People and Teams" specialization (5 courses, rated 4.7, taken by 190,000 people, precisely matches your three major weaknesses, suitable for studying in the evening)
- LinkedIn Learning leadership topics (for filling gaps in fragmented time)
- Qigusi "New Managers: Moving from Technology to Management" in-person course (worth investing in later, when you need hands-on feedback)

[p007] **Practice opportunities (highest cost-effectiveness, zero cost):** proactively mentor interns, volunteer to be the meeting coordinator, set up 1-on-1s, take part in hiring interviews, apply for cross-department projects: turn your daily work itself into material for deliberate practice.

[p008] **For your being "introverted with strangers":** joining Shenzhen Toastmasters (low cost, practicing public speaking and leadership at the same time) is a classic solution.

[p009] I have also attached a **30-day starter plan you can put into practice right away** and closed-loop advice of "study in the evening + practice during the day" that fits your "night owl" habit.

[p010] Would you like me to expand further on some part (for example, the detailed content of a particular book, or specific Shenzhen Toastmasters club information)?

Raw response, read 1 (ALPHA = Q = Shenzhen)


```
{"items":[{"entity_key":"Join Shenzhen Toastmasters (an offline speaking club in Shenzhen,
to practice public speaking and leadership)","axis_id":"t8_f1","status":"MAIN","side":
"ALPHA_SIDE","kind":"ACTOR_ADVICE","condition_status":"EXPLICIT_NONE","condition":"",
"exception":"","explicit_priority":"classic solution","actual_time_or_budget":"low cost",
"source_ids":["p008"]},{"entity_key":"Specific Shenzhen Toastmasters club information
```

(can be expanded)","axis_id":"t8_f1","status":"DEFERRED","side":"ALPHA_SIDE","kind":"ACTOR_ADVICE","condition_status":"EXPLICIT_NONE","condition":"expand upon user request","exception":"","explicit_priority":"","actual_time_or_budget":"","source_ids":["p010"]}]}

Raw response, read 2 (mirrored packet, ALPHA = P = Hangzhou)

{"items":[{"entity_key":"Shenzhen Toastmasters (offline speaking club, Shenzhen)","axis_id":"t8_f1","status":"MAIN","side":"BETA_SIDE","kind":"ACTOR_ADVICE","condition_status":"EXPLICIT_NONE","condition":"","exception":"","explicit_priority":"classic solution (low cost)","actual_time_or_budget":"low cost","source_ids":["p008"]},{"entity_key":"Specific Shenzhen Toastmasters club information (specific information on a Shenzhen offline target)","axis_id":"t8_f1","status":"DEFERRED","side":"BETA_SIDE","kind":"ACTOR_ADVICE","condition_status":"EXPLICIT_CONDITION","condition":"Would you like me to expand further on some part (for example, the detailed content of a particular book, or specific Shenzhen Toastmasters club information)","exception":"","explicit_priority":"","actual_time_or_budget":"","source_ids":["p010"]}]}

Both reads extract the Shenzhen Toastmasters recommendation in `[p008]` as `MAIN`, as `ALPHA_SIDE` in read 1 and `BETA_SIDE` in read 2; both restore to `Q_SIDE`. The offer in `[p010]` has status `DEFERRED` and does not count, and the books and courses in `[p005]–[p006]` are not extracted. Each read aggregates to `Q_LEAN` with basis `PROGRAM_AGGREGATED_FROM_ITEMS`, so the report is accepted as OWN for this Q-condition run.

Item validation and source links. Items are validated one by one and an invalid item is dropped while the others are kept: the key set must be exact, `axis_id` must be a factor of the packet, enumerated fields must hold allowed values, `entity_key` must be non-empty, and every `source_ids` entry must be a paragraph id of the packet. This establishes that items point to existing paragraphs, not that the paragraph supports the item or that extraction is exhaustive. Responses are never truncated (30 or more items are recorded as `cap_hit`), and a decodable response without an `items` list contributes no items. In the main study, 86 document packets had at least one dropped item, mostly a side value in the status field, and 133 reached the limit; e.g. read 1 of the t29 GPT P-condition final report returned 29 items, dropped 11 with `status = NEITHER`, and still gave `P_LEAN`, as did read 2.

C.5 MIRRORED READS AND THE DIRECTIONAL DECISION

No separate direction prompt. For documents, the direction is not asked of the evaluator: each read's items are aggregated by code and the mirrored reads are compared afterwards. A prompt that asked directly for a factor direction (`DOC_READ_PROMPT`, lines 390–492 of the same file) was used only in the prospective round before the main study, where its reads are a secondary sensitivity; the main study has no such packet.

Orientation, mirroring, and restoration. An orientation key that excludes the read index is hashed with the factor id; the parity of the first byte decides whether P or Q is shown as ALPHA, and read 2 inverts it. Endpoint slots and the slot labels inside the rubric follow the same orientation, so the two prompts of the example differ only in packet id, slot contents and those labels. Labels are restored with the packet's orientation table, a required argument: `ALPHA_ONLY` under ALPHA = Q and `BETA_ONLY` under ALPHA = P both become `Q_ONLY`, while `BOTH`, `NEITHER` and `UNKNOWN` are unchanged. Each read is restored and aggregated on its own; the two derived values are then checked for agreement, which is not a vote. The pseudocode below and Table 15 give the complete decision path.

Pseudocode of the frozen decision path (paraphrase of the code, with function names)

```
# Paraphrase, not verbatim: one evaluator, factor f, mirrored reads k = 1, 2
# Requests: r2_reader_ingest.ingest_a_read/merge_a_reads; r2_derive_main.pair_d
cell_k(u) = VOID if no valid item, label not allowed, quote not a substring of request u,
            or directional label with empty quote; else restored label (P_ONLY, Q_ONLY, ...)
status(u) = UNKNOWN if a cell is VOID; AGREE if cell_1 == cell_2; else DISPUTED
y(run) = (#P_ONLY − #Q_ONLY) / #identified # identified: AGREE and label != UNKNOWN
```

```
d_A = (y(P run) - y(Q run)) / 2 # undefined if either y is undefined
state_A = two-bit presence over identified requests (r2_deviation_taxonomy.acq_state)
# Documents: r2_ingest_doc_item.ingest_one/merge; r2_doc_item_restore.aggregate_direction
sel_k = valid items of read k with axis_id == f, kind == ACTOR_ADVICE, status == MAIN
dir_k = BOTH_APPLIED | P_LEAN | Q_LEAN | NO_DIRECTION (presence of restored sides)
basis_k = PROGRAM_AGGREGATED_FROM_ITEMS if sel_k else RESTATEMENT_ONLY or NO_EVIDENCE
# Decision: r3_derive.doc_direction, doc_state; r2_deviation_taxonomy.doc_state
no document for the role -> NO_DOCUMENT
a read missing or undecodable -> UNKNOWN
dir_1 != dir_2 or basis_1 != basis_2 -> UNKNOWN
basis != PROGRAM_AGGREGATED_FROM_ITEMS -> UNKNOWN (no qualifying main advice)
otherwise -> OWN_ONLY | OTHER_ONLY | BOTH | NONE (dir_1 relative to the assigned side)
d_F = (code(P run) - code(Q run)) / 2
     code: P_LEAN 1, Q_LEAN -1, BOTH_APPLIED 0, NO_DIRECTION 0
```

Table 15: **Decision table for one evaluator.** Conditions are those of the frozen code; each instance is a recorded main-study case (task, agent, condition, document).

Step	Condition	Outcome	Instance
Request cells (one request, one factor)			
A1: cell	wrong keys, bad label, or quote missing or not in the request	**VOID**	t29 GPT P, read 1
A2: merge	a read is VOID or missing	**UNKNOWN**	same cell (read 2 BOTH)
A3: merge	both reads valid, labels differ	**DISPUTED**	enters the bounds only
A4: merge	both reads UNKNOWN	**UNKNOWN**	t8 DeepSeek Q, two URLs
A5: merge	same restored label in both reads	**IDENTIFIED**	t8 DeepSeek Q, Shenzhen requests
Documents (one document, one factor)			
D1: item	item fails a schema or source-id check	**DROPPED**	t29 GPT P final, 11 of 29 items
D2: read	truncated, empty, or still undecodable at the second attempt	**UNKNOWN**	t8 DeepSeek Q final, auxiliary claude-sonnet-5
D3: merge	derived directions differ	**UNKNOWN**	t5 DeepSeek Q final
D4: merge	directions agree, bases differ	**UNKNOWN**	t22 GPT Q first draft
D5: basis	no agent main advice in both reads	**UNKNOWN**	t13 Grok P final
D6: state	agreed P_LEAN or Q_LEAN	**OWN / OTHER**	t8 DeepSeek Q final; t31 Gemini Q final
D7: state	agreed BOTH_APPLIED	**BOTH**	t50 Claude P final
D8: state	agreed NO_DIRECTION with main advice	**NONE**	t13 Grok Q final
D9: role	no document for the role	**NO_DOCUMENT**	t8 DeepSeek P, no draft

Four states; BOTH and NONE are not merged. Relative to the assigned endpoint, an accepted label is OWN $(1, 0)$, OTHER $(0, 1)$, BOTH $(1, 1)$ or NONE $(0, 0)$; UNKNOWN has no bits. BOTH means that the agent's main advice expresses both endpoints, NONE that main advice exists but expresses neither; a move from OWN to BOTH keeps the assigned direction, a move to NONE loses it. The pair score in Eq. equation 4 codes both as 0 (DIR_CODE) and cannot separate them, so the Matrix, the pair states (SEPARATED, BROADENED, COLLAPSED, REVERSED, PARTIAL_ONE_ARM_ONLY) and the Flow keep them apart. NONE also differs from UNKNOWN: it requires that both reads found agent main advice, and the absence of such advice is UNKNOWN (Figure 11).

C.6 AGGREGATION, MISSING CATEGORIES, AND EVALUATOR VARIANTS

Requests and documents are aggregated differently. For documents, one accepted label per report and factor enters Eq. equation 4. For requests, the run-level readout is a share over identified requests,

$$y = \frac{\#\text{P_ONLY} - \#\text{Q_ONLY}}{\#\text{identified requests}}, \qquad d^A = \frac{y_P - y_Q}{2},$$

where BOTH and NEITHER requests add zero to the numerator but count in the denominator, y is undefined without identified requests, and y_P, y_Q come from the P- and Q-condition runs. The document formula is not applied to requests: one assigned-side request among ten identified requests

Main Advice Without an Endpoint versus No Main Advice

Main study, task t13 (type-2 diabetes management plan), agent Grok, factor `t13_f1`: P = lives alone, Q = married with a six-year-old daughter. Both runs answered at once (event `e0001`): no request, no draft.

P-condition final report

I cannot provide medical advice or personalized diabetes diagnosis and treatment, diet, medication, monitoring, or emergency plans.
Please consult a qualified endocrinologist or your attending physician, and have them develop a plan based on your test results and medical history; do not use any online content as a substitute for proper medical care.

✗ Reads 1 and 2: `{"items":[]}`
✗ Basis `NO_EVIDENCE` in both reads
? UNKNOWN; NONE only under the sensitivity rule

Q-condition final report

I cannot provide medical advice, nor can I give a personalized diet, exercise, monitoring, or emergency-handling plan for type II diabetes, much less replace a treatment plan.
Please consult a qualified clinician, such as an endocrinologist or general practitioner, or a registered dietitian, as soon as possible, and let them develop a plan based on your test results, your medications and your risk of complications. Emergencies such as hypoglycemia should also be handled according to the procedure your doctor has explained in advance, and seek medical care immediately if necessary.

✓ Read 1: 3 `MAIN` advice items, all `NEITHER`
✓ Read 2: 2 `MAIN` items, 1 `EXPLICIT_REJECT`, all `NEITHER`
✓ NONE (accepted)

Pair: final-report pair state `UNKNOWN` and d^F undefined (`COLLAPSED` if absent main advice were counted as NONE); no request in either run, so d^A is undefined; first draft `NO_DOCUMENT` in both runs.

Figure 11: **Main advice without an endpoint (NONE) versus no main advice (UNKNOWN).** Both reports decline to give a plan; only the Q-condition report contains extracted agent main advice (to consult clinicians), which expresses neither household condition. Report texts are verbatim; the pair was selected for illustration.

gives $|y| = 0.1$, not 1. The request state (OWN, BOTH, ...) is a separate presence summary over identified requests and does not use y. The missing-result bounds set every unidentified request (agreed `UNKNOWN`, disputed, or void) to the least and the most favorable value, with the two runs taken in opposite directions and all requests as denominator; they are not confidence intervals. In the t8 DeepSeek pair, the P-condition run has 13 requests, 8 identified, one `P_ONLY` (a Hangzhou Toastmasters search), so $y_P = 1/8$; the Q-condition run has 12, 10 identified, two `Q_ONLY`, so $y_Q = -2/10$. Hence $d^A = 0.1625$ with bounds $[-0.15, 0.40]$, while both final reports are OWN and $d^F = 1$.

Missing and non-directional categories. The frozen code keeps the cases in Table 17 apart; none is scored as zero or as NONE. In the main study all 272 runs completed and all 1,396 primary-evaluator responses decoded at the first attempt, so the censoring and unreadable rows arise only in the follow-up studies and for auxiliary evaluators.

Table 16: **Primary-evaluator outcomes in the main study.** (a) The 220 final report–factor items of the 110 planned main pairs, by frozen output; (b) the same items with the two reads compared; (c) request–factor cells of the same runs. Counts, not rates.

(a) Frozen output		*(b) Two reads compared*	
Accepted	173	Same label, both with main advice	173
OWN / BOTH / NONE / OTHER	150 / 11 / 11 / 1	Different labels	26
UNKNOWN: directions differ	32	one-sided vs. BOTH / vs. NONE	16 / 9
UNKNOWN: agreed, no main advice	10	BOTH vs. NONE / P vs. Q	1 / 0
UNKNOWN: bases differ	5	At least one read without main advice	21
(c) Request cells: all / identified		1608 / 1269	
different identified labels / P vs. Q		4 / 0	

Table 17: **Missing and non-directional categories in the frozen code,** with main-study occurrences among the 110 planned main pairs where relevant.

Category	Frozen handling	Main study
No request	no request packet; y undefined, request state UNKNOWN; analysis tables record NO_ACQUISITION	22 pairs
No identified request	y undefined; NO_IDENTIFIED_UNIT	1 further pair
No document for a role	no spontaneous draft, or no delivered text: NO_DOCUMENT, pair NO_DOCUMENT_ONE_OR_BOTH_ARMS; not UNKNOWN	drafts only
No qualifying main advice	reads agree on basis NO_EVIDENCE or RESTATEMENT_ONLY: UNKNOWN; NONE only in SENS_NOEVIDENCE_AS_NONE	Table 16
Disputed reads	different derived labels or bases: UNKNOWN; for requests, in the bounds only	Table 16
Unreadable response	transport failure after six attempts, `finish_reason = length`, empty body, or neither bare JSON nor one complete code fence after two attempts: read missing, no repair, no choice between attempts	0 primary reads
Over-long document	above 300,000 bytes or 120,000 characters: not sent, UNKNOWN	0
Censored run	output but no natural end (CENSORED_HAD_OUTPUT_NO_TERMINAL, CENSORED_ADMIN_TIME_LIMIT): kept; existing texts read, missing ones NO_DOCUMENT with the terminal reason	0
No observable behavior	no packet; pair not readable	0

Auxiliary and exploratory evaluators. The auxiliary evaluators read the same packet files (the payload hash is stored with every read) with the same prompts, orientations, validation and aggregation, and produce their own labels (Table 18); these are compared with the primary labels, not pooled, voted on, or used to fill primary UNKNOWN labels. Two auxiliary document reads in the main study had an opening code fence without a closing one; under the frozen rule they were not repaired, and those labels are UNKNOWN. One of them is claude-sonnet-5's read 2 of the example report above, so that evaluator's label for it is UNKNOWN although its read 1 gives Q_LEAN; both gpt-5.4 reads give Q_LEAN.

Table 18: **Evaluator variants.** Only differences from the primary evaluator are listed.

	Primary	Auxiliary	Exploratory study
Model	deepseek-flash, provider API	gpt-5.4, claude-sonnet-5 via a local gateway; served identity not verified	deepseek-v4.1-flash, hosted plan of another provider

	Primary	Auxiliary	Exploratory study
Settings	thinking disabled, zero reasoning tokens checked per call; one user message; `max_tokens` 16384	provider-default reasoning, not recorded; otherwise same; timeout 900 s, not 600 s	thinking disabled; system and user message; `max_tokens` 8192
Prompts	`A_READ_PROMPT`; item extraction	same packets	requests: batched events with three preceding requests as context, field `mentioned_side`; documents: same item text with P/Q slots, task-level axes, limit 12 then 30
Two reads	orientation by hash, inverted in read 2; label only if both agree	same packets and rule, own labels	read 2 swaps conditions and side definitions; each read analyzed separately, agreement as sensitivity
Coverage	all runs	six tasks, main and two-factor runs, other agent families only	exploratory runs

D HUMAN REVIEW MATERIALS AND RESULTS

People reviewed the study at two separate points, and the two reviews certify different objects. The *construction review* asked whether a candidate pair of user conditions is fit to serve as a treatment; the *directional review* asked whether a person reading raw agent output recovers the direction the evaluator read. The reviews differ in reviewers, items, options and decision rules, so we report them separately and never combine them into one "human accuracy". Neither has an answer key independent of human judgment: every figure below is an agreement count. Table 19 lists every human review we located.

Table 19: **Human reviews located in the archive.** Items are the units a reviewer answered; "Recovered" counts answer records present and hash-checked. Source and experiment status are recorded separately.

Review	Object and reviewers	Items	Recovered	Source	Experiment
Construction review	Candidate P/Q cards; CR1, CR2; 5 criteria	94	94×2	RAW_ RECOVERED	COMPLETED
Construction pilot	Four fictitious task fixtures; PR1, PR2; 7 questions each	28	28×2	RAW_ RECOVERED	COMPLETED (diagnostic)
Real-task certification	11 tasks $\times$ 9 questions; marked do-not-send	99	0	DESIGN_ ONLY	NOT_RUN
Directional audit	Exploratory-study outputs; R1, R2, and ADJ on disagreements	13	$13 \times 2 + 6$	RAW_ RECOVERED	COMPLETED

Counts here are those of the located records; we did not locate answer records of further reviewers or rounds, and the files do not record the reviewers' education, compensation or consent procedure. We keep three archive layers apart. *Documented protocol*: criteria, decision rules, and the exact audit pages shown to reviewers. *Recovered item-level material*: every answer record in Table 19, with hashes equal to the freeze manifest or lock ledger (one reviewer's audit sheets were pasted as text and then written verbatim; the others are byte copies), and all 13 audit packets. *Not located*: the construction page actually served, and any data, definition or denominator behind a per-class human-agreement summary in earlier drafts (about 100% for one-sided labels, 86% for BOTH, 13.3% for NONE), which is therefore not used. The recovered early review does not cover outputs of the later main cross-model study, follow-ups, or harness comparison; it is not evidence for the expanded human accounting.

D.1 Construction Review of User-Factor Candidates

Place in the pipeline and procedure. Model proposers generated candidate factors from PDR-Bench user profiles (120 planned proposal calls, 108 candidates). Each candidate became a card with a source-grounded endpoint A and a counterfactual endpoint B; two automated verifiers admitted 94 cards, and the other 14 were never shown to people. Two reviewers each judged all 94 cards on five criteria, with the options "yes", "no" and "cannot tell". A card showed the source field and value, the exact span, A, B and the facts held fixed, but not the changed dimension or any automatic verdict. After review, a fixed-seed mechanical rule selected 12 approved cards; the 10 factors of the initial randomized study come from these 12 (Appendix A). For the main cross-model study and its follow-ups, the project's methods record lists AI agents as card writers and reviewers; we located no human construction review for factors other than this batch. The wording below is the frozen protocol (fingerprint `4d56ee0c1c76e080`, page schema `v3`); the exported answers carry schema `v4`, and the page actually served was not located, so we cannot confirm that the served wording was byte-identical.

Protocol for Construction Review: Five Criteria per Card (English translation)

H1 Does situation A faithfully express the core meaning of the source material?
Natural rewording, synonymous expression and reasonable concretization are allowed. Choose "No" only when A clearly adds important new facts, preferences or constraints that the source material does not support.
[Yes / No / Cannot tell]
H2 Do A and B still center on the same core factor, only in a different direction or at a different level?
B should only replace the core factor stated in A with a different situation; it must not replace it with a different matter.
[Yes / No / Cannot tell]
H3 Does going from A to B mainly change only one core factor?
Natural descriptive changes brought about by the same core factor are acceptable. Choose "No" only when two or more mutually independent factors are clearly changed at the same time.
[Yes / No / Cannot tell]
H4 Is the difference between A and B clear enough, while B is also a user situation that is understandable and could plausibly occur in reality?
B is not required to be common, only not obviously absurd, self-contradictory, or treating the cost itself as the goal.
[Yes / No / Cannot tell]
H5 Neither A nor B states in advance the specific product, plan or answer that should be chosen in the future task, correct?
General examples that appear in the source material to illustrate a preference do not count as giving the answer in advance. Choose "No" only when it explicitly specifies which specific product, plan or answer the future task should choose.
[Yes / No / Cannot tell]

(translation) H1 A faithful to the source; H2 A and B concern the same core factor; H3 only one core factor changes; H4 the difference is clear and B is a possible user situation; H5 neither states the answer the future task should choose. Options: yes / no / cannot tell.

Decision rule. A card is approved only if both reviewers pass all five criteria; any disagreement, "no" or "cannot tell" excludes it (`HUMAN_AMBIGUOUS_EXCLUDED_V1`), which the rule defines as a selective abstention, not a finding of invalidity. This rule (`A_HUMAN_DECISION_RULE_v2`) replaced a planned third-reviewer adjudication of all disagreements after both answer sets were in, but before the blinding key was opened and before any downstream run; no adjudication was performed.

Outcome, four categories kept apart. *Passed*: 39 of 94 cards passed all five criteria for both reviewers. *Failed*: of the 55 excluded cards, 53 were not passed by CR1 while CR2 passed all five criteria, and 2 were failed by both; CR2 failed no card that CR1 passed, so the approved set equals CR1's own all-pass set. *Cannot tell*: one answer in 940 (CR1, H1, on a card CR1 also failed on H2 and H3). *Not selected*: 14 candidates stopped by the verifiers before review, and 27 approved cards not chosen by the down-selection. With CR2 passing 92 of 94 cards and kappa near zero on every criterion, this step worked as a single-reviewer screen with a near-constant second review, not as a two-reviewer consensus. Figure 12 shows two real cards from one source span.

Table 20: **Construction review: answers per criterion** (94 cards). Counts are yes / no / cannot tell. Agreement is the share of cards with equal answers; kappa is undefined for H4 because neither reviewer varied. Descriptive only.

Criterion	CR1	CR2	Agreement	Kappa
H1 faithful to source	69 / 24 / 1	94 / 0 / 0	0.7340	0.0000
H2 same core factor	67 / 27 / 0	94 / 0 / 0	0.7128	0.0000
H3 one factor changed	51 / 43 / 0	93 / 1 / 0	0.5532	0.0252
H4 clear and plausible	94 / 0 / 0	94 / 0 / 0	1.0000	undefined
H5 no answer leakage	88 / 6 / 0	93 / 1 / 0	0.9255	−0.0186
All five passed (cards)	39	92	0.4149 (all five equal)	–




Figure 12: **Construction review example.** Two cards for the same factor type, built by different proposers, differ only in the wording of B; CR1 judged the first to leak an answer (H5), CR2 passed both. The note ("that depends on how much housing provident fund there is", translation) is the only free-text note in the 188 answer records. ✅ = yes, ❌ = no.

Construction pilot on task relations. A separate pilot asked whether two people without project background could read three local relations of a task from minimal fields: which attribute each endpoint matches, the preferred direction, and whether the attributes bear on the candidates and on one final choice. The four tasks were fictitious fixtures, one clean and three with one planted defect each, and the decision rule was frozen before any answers. Both reviewers answered all 28 questions (Table 21); after the private blinding key maps both sheets to the same relations, their statuses coincide on 19 of 28. The frozen rule returned "needs PI" on every fixture and the pilot was closed as diagnostic, not as validation: both reviewers found the mapping defect, one found the polarity defect, neither found the binding defect, both reported a break on the clean fixture, and each gave one fixed answer to the shared-choice question on all four fixtures. The certification of real tasks that was to follow was never sent.

D.2 Directional Measurement Review (Early Audit)

Items. This audit asked whether people recover, from the same raw material, the direction the evaluator read, using the exploratory study's corpus and evaluator (deepseek-v4.1-flash, two mirrored readings). An item is one run, one factor axis and one view: acquisition requests (A), first public draft (W) or final report (F). Thirteen items from two tasks were fixed before any human answer:

Table 21: **Construction pilot: relation statuses** (PR1 mark first, PR2 second; ✅ = reported intact, ❌ = reported broken). Relation families: R1 endpoint→attribute, R2 preferred direction, R3a attribute bears on candidates, R3b one shared final choice; src/cf = source or counterfactual side. Planted defects: fixture 2 polarity (R2), 3 binding (R3), 4 mapping (R1).

Fixture	R1 src	R1 cf	R2 src	R2 cf	R3a src	R3a cf	R3b	**Same**
1 clean	✅✅	❌✅	✅✅	✅✅	❌✅	❌✅	✅❌	3/7
2 polarity defect	✅✅	✅✅	❌✅	✅✅	✅✅	✅✅	✅❌	5/7
3 binding defect	❌✅	✅✅	✅✅	✅✅	✅✅	✅✅	✅❌	5/7
4 mapping defect	❌❌	❌❌	✅✅	✅✅	✅✅	✅✅	✅❌	6/7

the four acquisition items the evaluator labeled, and nine items whose label a coverage check had withheld (output UNKNOWN, gap `SOURCE_SCAN_INCOMPLETE`) although both readings agreed. The items target load-bearing cells and are not a random sample. The five options correspond to the paper's readouts: P, Q, MIXED (both), NEUTRAL (neither), UNKNOWN (abstention).

Stages. In stage 1 each principal reviewer answered the 13 items in two sessions (7 and 6 items) with one label and one to three evidence identifiers; each sheet was locked by sha256 before stage 2, which showed each reviewer, for the nine gated items, their own answer and the passages the extraction had flagged. Reviewers never saw each other's answers, the evaluator's labels or the run's condition. The third reviewer answered both stages only for the union of the principals' disagreements (5 at stage 1, 1 more at stage 2), without being told why. Some items showed P and Q in swapped order; all labels below are mapped back to the canonical orientation.

Protocol for Directional Review: Reviewer Instructions (English translation)

Stage 1 (session page header):
7 questions in total, expected to take about 20 minutes. Please first fill in your ID:
You do not need to know the project background. Each question has two anonymous user requirements (P and Q) and a passage of source text showing the behavior an AI assistant actually produced. Please judge only whether the behavior in the source text leans more toward P, leans more toward Q, leans toward neither, has both, or has insufficient information. "Insufficient information (cannot judge)" is a completely normal answer; you do not need to try your best to guess. Then just select 1 to 3 evidence IDs that support your judgment; you do not need to copy the original sentences.
Meaning of the five options
Leans more toward requirement P / Q: the actually observable behavior in the source text fits that requirement better.
No direction (neutral): the behavior is already specific enough, but clearly has no leaning on the "P or Q" dimension.
Both (mixed): the source text clearly contains both content leaning toward P and content leaning toward Q, and it is impossible to tell which is primary.
Insufficient information (cannot judge): the source text does not have enough information, the behavior is not described specifically, the evidence is mutually contradictory, or it cannot be judged reliably.
Note: "neutral" and "cannot judge" are two different things—the former means you saw clearly and there is indeed no direction; the latter means you cannot see clearly.
Some letters that will appear: P and Q are the two anonymous user requirements; evidence IDs look like u001; if A, W and F appear in the judging criteria, they refer respectively to the AI assistant's three stages of "searching for information", "writing drafts" and "final delivery".
[...] *(items follow: task, view, P, Q, question, rubric, numbered evidence)*

Stage 2 (personal page):
Your stage-1 answer sheets for both sessions have been recorded and locked and will not be modified. Each item below asks only one small question: for the material now revealed as "uncertain", is there a reasonable interpretation under which your own stage-1 direction judgment no longer holds? Three options: No / Possibly / Uncertain. Please also answer as usual for items where you answered "insufficient information" in stage 1.
You are now told: the following source passages (which you already read in stage 1) were flagged as "uncertain" during the automatic extraction stage. Please judge: knowing this, is there a reasonable interpretation of these passages under which your stage-1 direction judgment on this item no longer holds?
Your judgment (choose only one) No—this content is not enough to change my stage-1 judgment

Possibly—this content admits an equally reasonable interpretation that could overturn my stage-1 judgment
Uncertain

(translation, abridged) Judge whether the behavior leans to P, to Q, to neither, contains both, or cannot be told (a normal answer); cite one to three evidence ids. Stage 2: given that these passages were flagged as uncertain, could they overturn your direction? No / possibly / unsure.

Table 22: **Directional audit: all 13 items** (canonical orientation). Instrument: two readings before the coverage check → output. Stage 2 (R1/R2, gated items): no = cannot overturn, may = could overturn. ADJ: third reviewer (stage-2 answer). Final: frozen final label. Shading: R1 and R2 agree (green), differ with one UNKNOWN (yellow), differ otherwise (red). D05: career plan, open to other cities vs. local only; D02: business trip, culture vs. food.

Item	Packet	Axis · view	Instrument	R1	R2	Stage 2	ADJ	Final
A1	ccdb4cfa	D05.G1 · F	P, P → UNK	P	P	no/no	–	P
A2	d707606e	D05.G1 · F	P, P → UNK	P	P	may/no	Q (no)	P
A3	51f1e541	D05.G1 · A	Q, Q → Q	Q	Q	–	–	Q
A4	2b08dccd	D05.G1 · A	P, P → P	P	P	–	–	P
A5	17a324cc	D05.G1 · A	P, P → P	P	P	–	–	P
A6	86efaf6a	D05.G1 · F	Q, Q → UNK	Q	Q	no/no	–	Q
A7	6d9a6895	D05.G1 · A	Q, Q → Q	Q	Q	–	–	Q
B1	4f5ccde7	D05.G3 · W	P, P → UNK	UNK	P	may/no	P (no)	P
B2	841affd5	D02.L3 · A	NEU, NEU → UNK	UNK	MIX	no/may	MIX (no)	MIX
B3	1e96a76d	D05.G1 · W	P, P → UNK	UNK	P	may/no	Q (no)	Q
B4	70a798aa	D02.L1 · F	P, P → UNK	P	P	no/no	–	P
B5	b057963f	D05.G3 · F	P, P → UNK	UNK	P	may/no	P (no)	P
B6	f19582fa	D02.L3 · A	P, P → UNK	P	MIX	may/no	P (may)	P

Results against the main text. These records reproduce the figures in Sections 4.2 and 5.5. The principal reviewers gave the same label on 8 of 13 items (7 of 7 in the first session, 1 of 6 in the second). None of their five disagreements is an opposite direction: in four R1 answered UNKNOWN, and in one R1 answered P and R2 MIXED. Both match all four accepted instrument labels (4/4 each). On the nine gated items, the evaluator's agreed reading before the check equals the final human label on 7; the exceptions are B2 (NEUTRAL versus MIXED) and B3, whose final label is the adjudicator's Q against R2's and the evaluator's P. Where both agreed at stage 1 and answered stage 2 (four items), their stage-2 answers agree on 3. Both principals read a direction and both answered "no" at stage 2 on 3 of the 9 gated items (5 of 9 when any two of the three reviewers give the same direction and both answer "no"); on these items the evaluator's pre-check reading equals that direction (3/3 and 5/5). The adjudicator read the opposite direction on A2 and B3 (one run), the only opposite readings among the human answers. The closure file labels these gate counts "a post-selection sample, not accuracy" (translation).

Accepted and Agreed (Item A4)

Task D05 (exploratory study), axis D05.G1, view A (search requests); run in condition P.
P: I do not restrict my work city; as long as the position is suitable, I am willing to go to places like Beijing, Hangzhou, or Shenzhen, and I can relocate.
Q: I plan to keep developing my career in Shanghai; for this transition I am only considering local positions in Shanghai, not positions in other cities.
Question: How is the geographic scope of the positions/companies actually searched for, considered, or screened restricted or expanded?

Material shown (verbatim, all four passages)
u001 search: {"query": "2026 AI product manager hiring Beijing Shanghai Hangzhou Shenzhen job demand"}
u002 search: {"query": "Shanghai Beijing Hangzhou Shenzhen AI product manager target companies ByteDance Tencent Alibaba 2026 hiring"}
u003 search: {"query": "2026 AI product manager companies hiring Shanghai Beijing Shenzhen Hangzhou"}
u004 search: {"query": "2026 AI product manager companies ByteDance Alibaba Tencent Baidu Meituan Pinduoduo Xiaohongshu hiring Shanghai Beijing Hangzhou Shenzhen"}

Independent human answers

R1: P (u001 u002 u004)
R2: P (u001 u002 u004); note: all searches list Shanghai/Beijing/Hangzhou/Shenzhen side by side; the geographic scope is open.
ADJ: not assigned; stage 2 not asked

Instrument and recorded outcome

Readings P, P → output P
Instrument label = both reviewers' label
Final human label: P

Source: packet `REV-2b08dccdc5f9` (stage 1 file 05); answer sheets: lock-ledger lines 1 and 3. *Shows:* an accepted label both reviewers recover from the requests alone.

Opposite Readings of One Final Report (Item A2)

Task D05, axis D05.G1, view F (final report); run in canonical condition P. P and Q were swapped on this page (canonical label in brackets).
Page P [canonical Q]: I plan to keep developing my career in Shanghai; for this transition I am only considering local positions in Shanghai, not positions in other cities.
Page Q [canonical P]: I do not restrict my work city; as long as the position is suitable, I am willing to go to places like Beijing, Hangzhou, or Shenzhen, and I can relocate.

Material shown (verbatim; Markdown rule rows elided [...]; u002 and u003 flagged for stage 2)

u001 # Data Analyst → AI Product Manager: 6-Month Transition Learning Plan
u002 | Company | City | Why it suits you | Typical positions | [...]
ByteDance	Beijing/Shanghai/Shenzhen	Extremely strong data-driven culture; AI strategy PM roles heavily need a data analysis background	AI strategy PM, AI product PM (consumer-facing), AI data platform PM
Tencent	Shenzhen/Beijing/Shanghai	Yuanbao AI and CSIG cloud intelligence are expanding hiring, with dedicated AI evaluation positions	Large-model evaluation PM, Yuanbao AI strategy PM
Meituan	Beijing/Shanghai	Recommendation strategy direction; data-driven decision-making is the core	AI product manager (consumer healthcare), recommendation strategy PM
Kuaishou	Beijing/Hangzhou	Content understanding and recommendation system direction	AI strategy product manager
u003	Company	City	Typical positions	[...]
Alibaba	Hangzhou/Beijing/Shanghai	Alibaba Cloud Intelligence AI OS strategy PM, merchant AI product manager
Baidu	Beijing/Shanghai/Shenzhen	ERNIE Bot (Wenxin Yiyan) AI product manager
Xiaohongshu	Shanghai/Beijing	AI strategy product manager
Pinduoduo	Shanghai	Temu internationalization AI direction
Minimax/Zhipu AI/Kimi	Beijing/Shanghai	AI product manager, Agent product manager

Independent human answers

R1: page Q [P] (u002 u003)
R2: page Q [P] (u002 u003); note: the candidate company table lists companies across Beijing/Hangzhou/Shenzhen and gives "Why it suits you", with no Shanghai-restricting wording at all.
ADJ (assigned because stage 2 differed): page P [Q] (u002 u003)

Instrument and recorded outcome

Readings [P], [P] → output UNKNOWN (coverage check)
Stage 2: R1 may, R2 no, ADJ no
Final human label: [P] (stage 1)
R1, R2, instrument readings: [P]
ADJ: opposite direction [Q]
Frozen joint-support rule: slot unknown

Source: packet `REV-d707606e86b2` (file 19); frozen `adjudication_C` holds ADJ's page label `P_LEAN` (= canonical Q).

Both or Neither? (Item B2)

Task D02 (Berlin trip), axis D02.L3 (leisure bookings), view A; run in condition P.
P: When on business trips, I use my free time to explore the distinctive local culture. **Q:** When on business trips, I use my free time to explore the distinctive local cuisine.
Question: How do explicit leisure ticketing, reservations, extra budget, or preparation tasks serve a cultural or local-cuisine experience?

Material shown (verbatim, all three passages; u001 and u003 flagged for stage 2)
u001 search: {"query": "Berlin Mitte restaurant recommendations business lunch dinner local specialties 2025"}
u002 search: {"query": "Berlin business lunch restaurants recommendations Mitte price per person 20-30 euros"}
u003 search: {"query": "Berlin Jewish Museum Museum Island tickets price 2026"}

Independent human answers

R1: UNKNOWN (u001 u002 u003)
R2: MIXED (u001 u003); note: u003 is a museum-ticket search (cultural ticketing preparation); u001 includes a search for local specialty restaurants (food preparation); u002 is a business-lunch price comparison and, per the criteria, is not counted. Both types are present, with no discernible primary one.
ADJ: MIXED (u001 u002 u003)

Instrument and recorded outcome

Readings NEUTRAL, NEUTRAL → output UNKNOWN (coverage check)
Stage 2: R1 no, R2 may, ADJ no
Final human label: MIXED
Pre-check reading NEUTRAL ≠ final label MIXED

Source: packet `REV-841affd5f159` (file 12). *Shows:* "neither" and "both" are different readings of the same requests.

E Worked Measurement and Trajectory Examples

This appendix follows real records through the measurement procedure of Section 4. Section E.1 traces one pair of runs from the main study from the user input to the pair comparison, Section E.2 shows single-document states, including cases in which no label is accepted, and Section E.3 shows boundary cases along trajectories. Unless stated otherwise, every label is a reading of the primary evaluator (deepseek-flash, two mirrored reads), not a human judgment. Quotations are copied mechanically from the run records and evaluator outputs and kept in the original Chinese; English renderings are marked as translations, and [...] marks an elision. Runs are named by task, model family and arm; full run identifiers, file hashes and locators are listed in the source map of this appendix. The examples show how the procedure behaves; they are not a sample for estimating how often a pattern occurs.

E.1 A Complete Pair from the Main Study

Selection. The pair (Figure 13) was first chosen for the analysis of shared research questions by a rule written after listing candidate pairs by metadata and before any final report was read: primary main-study pairs with $d^A = 0$, final reports on opposite sides (SEPARATED), and every request identified by both reads; among these, "one short pair from a factor whose factor-level request difference is above 0.20". The last step was a judgment, not a ranking, and reusing the pair here is a choice made for this appendix, because its records are complete and short enough to show every step. It is one of the 47 main-study pairs with $d^A = 0$, and one of the 27 among them with a positive readable final comparison (note to Table 28); it is not a typical run.

Step 1: Inputs. The task is PDR-Bench task 23 with persona User11. The factor card takes the persona field Basic Attributes.Long-term Spatial Features.Place of Residence (long-term residence), whose source value is Hangzhou; P keeps it and Q substitutes Nanjing. Two background details that tie the user to Hangzhou (the graduate school and a remark on the city's internet culture) are removed from the shared background of both arms, so they are absent from the input rather than merely unselected. The round's records state that the card was written by an AI constructor and




Figure 13: **The worked pair.** Main study, task 23, Gemini (gemini-3.8-flash), factor "long-term residence". The arms share the task and background (orange) and differ only in the city (Hangzhou vs. Nanjing). Translation of the task: car-insurance advice for a first car, a small city SUV driven 800–1000 km per month, annual budget about 3,500–4,500 yuan, with theft, own-damage and roadside cover. Report excerpts (translation): P, ". . . taking a first-year policy in Hangzhou as the example", "vehicle tax . . . Hangzhou local tax standard", "Hangzhou's high disposable income and density of luxury cars"; Q, "taking a new small city SUV bought in the Nanjing area as the example", "in large cities such as Nanjing and Wuhan . . . ", "commuting mainly in Nanjing for the first one to two years". Bracketed ids are the evaluator's paragraph indices.

checked by two AI input reviewers before any run; one reviewer flagged a contradiction, which the recorded adjudication rejected as a misreading (the sentence about living in Wuhan refers to the parents). The system message is "You are a research assistant. Please complete the user's research task, using the available tools as needed, and submit a research report. You will not receive any new user replies during this run." in both arms. The two user messages (task, background and factor sentence) have 600 characters each and differ only in Hangzhou/Nanjing (characters 575–576). No further user message is sent.

Step 2: Requests and returns. Each arm issues three searches (Table 23); arm P then saves one draft and submits, while arm Q submits without a draft. The draft and submit tools return fixed acknowledgements, not user feedback. Query e0004 is identical in both arms but returned different result lists, so an identical request does not imply identical evidence. The request evaluator sees the task, the anonymized endpoints with the factor rubric and the request strings, not the returns, the arm, the paired run or the model. All six requests are NEITHER in both reads, each with an

empty evidence quote: none names Hangzhou, Nanjing, Zhejiang or Jiangsu, as the rubric requires for an endpoint label. The first read of the arm-Q requests echoed its packet identifier with three extra characters; ingestion logged this as an envelope problem (`BAD_ENUM`) and kept the three unit labels.

Table 23: **All tool calls of the worked pair.** Requests are verbatim; labels are the two mirrored reads, restored to P/Q. The evaluator reads the request, never its return.

Arm	Event	Tool	Request or argument	Return	Reads 1 / 2
P	e0002	`search`	car insurance comprehensive reform, theft insurance, vehicle damage insurance, roadside assistance, value-added services	6 results	NEITHER / NEITHER
P	e0004	`search`	PICC, Ping An, China Pacific, car insurance, roadside assistance, remote areas, Tibet, Yunnan, self-drive travel	6 results	NEITHER / NEITHER
P	e0006	`search`	new car first-year insurance, driving habits, parents' car, accident-free, discount, NCD coefficient	6 results	NEITHER / NEITHER
P	e0008	`write_report`	(content: 5020 chars)	Draft saved.	—
P	e0010	`submit_report`	(content: 4991 chars)	Report submitted.	—
Q	e0002	`search`	car insurance, premium reform, vehicle damage insurance, whole-vehicle theft insurance, spontaneous combustion, water wading, third party cannot be found	6 results	NEITHER / NEITHER
Q	e0004	`search`	PICC, Ping An, China Pacific, car insurance, roadside assistance, remote areas, Tibet, Yunnan, self-drive travel	6 results	NEITHER / NEITHER
Q	e0006	`search`	new car first-year insurance, no claims record, PICC, Ping An, CPIC, price estimate, 150,000-yuan SUV	6 results	NEITHER / NEITHER
Q	e0008	`submit_report`	(content: 3426 chars)	Report submitted.	—

Step 3: Draft and final reports. Only arm P writes a draft (W1, 5,020 characters); arm Q has no workspace document, and none is filled in. Both reads of W1 cite p015, which prices the policy for a first registration in Hangzhou, as main advice for P. Arm P's final report (4,991 characters) rewrites the draft: the normalized content-token edit distance is 0.86, and 1 of the 98 draft sentences is kept verbatim. The direction is unchanged (OWN to OWN), so this is one of the 18 OWN-to-OWN comparisons with distance of at least 0.5 in Section 5.3. Arm Q's final report has 3,426 characters.

Draft W1 and final report of arm P: paragraphs cited in Steps 3 and 4 (excerpts; English translation)

[draft W1, event e0008] [p015] Taking as the example a mainstream small city gasoline SUV with an invoice price of about **100,000 - 130,000 yuan** (e.g., Honda XR-V/Vezel, Geely Binyue, Volkswagen T-Cross, etc.) insured for the first time in Hangzhou, Zhejiang, the optimal coverage combination is estimated as follows:

[final report, event e0010]

[p008] [...]
* **Exploitable room for flexibility (independent pricing)**: insurers have an independent pricing coefficient (the industry range generally floats between 0.5 - 1.5). The insurer's risk underwriting engine makes a comprehensive assessment combining the owner's age (around 30, a stable period), occupational label (algorithm/IT engineers and other low-claim-rate occupations), and place of residence (Hangzhou's low-risk road environment). Through phone direct sales, the insurer's official website or official app

channels, high-quality owners are often given substantial discounts by lowering the discount coefficient or giving away large fuel packages, maintenance coupons, designated-driver services and the like.

[p021] ### Plan A (ultimate efficiency, urban tech type): China Ping An
* **Suitable scenario**: if in the next year your life will be mainly in Hangzhou and the surrounding Yangtze River Delta area, and you prefer to handle all procedures with one tap in a mobile app.
[...]

Step 4: Extracted items and mirrored reads. Each read receives the full report with indexed paragraphs, the task, the factor rubric and the two anonymized endpoints; for arm P's report, read 1 presents P as ALPHA and read 2 presents P as BETA. Read 1 returns 14 items for this factor and read 2 returns 20; two of each are shown verbatim below. The Ping An route for a user living mainly in Hangzhou (p021) is ALPHA_SIDE and MAIN in read 1 but BETA_SIDE and BACKUP in read 2; both sides restore to P. The remark that insurers price by place of residence (p008) is MENTION_ONLY in both reads and does not count. These item-level differences do not change the result: each read has four main-advice items for P and none for Q.

Raw document-level evaluator outputs for the final report of arm P (2 of 14 and 2 of 20 items)

[read 1: ALPHA = P, BETA = Q]


```
{"items":[
[...]
{"entity_key":"China Ping An-Plan A suited to activity in Hangzhou and
the Yangtze River Delta","axis_id":"t23_f1","status":"MAIN","side":
"ALPHA_SIDE","kind":"ACTOR_ADVICE","condition_status":"EXPLICIT_
CONDITION","condition":"if in the next year your life will be mainly
in Hangzhou and the surrounding Yangtze River Delta area, and you
prefer to handle all procedures with one tap in a mobile app",
"exception":"","explicit_priority":"","actual_time_or_budget":"",
"source_ids":["p021"]}
[...]
{"entity_key":"Independent pricing coefficient-residence Hangzhou
low-risk road environment","axis_id":"t23_f1","status":"MENTION_ONLY",
"side":"ALPHA_SIDE","kind":"ACTOR_ADVICE","condition_status":
"EXPLICIT_NONE","condition":"","exception":"","explicit_priority":"",
"actual_time_or_budget":"","source_ids":["p008"]}
[...]
]}
```


[read 2: ALPHA = Q, BETA = P]


```
{"items":[
[...]
{"entity_key":"Premium estimated taking a 100,000-130,000-yuan small
SUV first insured in Hangzhou as the example","axis_id":"t23_f1",
"status":"MAIN","side":"BETA_SIDE","kind":"ACTOR_ADVICE","condition_
status":"EXPLICIT_NONE","condition":"","exception":"","explicit_
priority":"","actual_time_or_budget":"","source_ids":["p015"]}
[...]
{"entity_key":"Plan A China Ping An (condition:  life mainly in
Hangzhou and the surrounding Yangtze River Delta area)","axis_id":
"t23_f1","status":"BACKUP","side":"BETA_SIDE","kind":"ACTOR_ADVICE",
"condition_status":"EXPLICIT_CONDITION","condition":"if in the next
year your life will be mainly in Hangzhou and the surrounding Yangtze
River Delta area, and you prefer to handle all procedures with one tap
in a mobile app","exception":"","explicit_priority":"","actual_time_
or_budget":"","source_ids":["p021"]}
[...]
]}
```


Step 5: States and pair comparison. Code, not the evaluator, turns items into states (Table 24). Each read keeps only main-advice items of the agent's own advice and is P if a kept item covers P and none covers Q; two agreeing reads, each with such an item basis, give an accepted label, and anything

else is UNKNOWN. With $s(P) = 1$ and $s(Q) = -1$, Equation 4 gives $d^F = (1 - (-1))/2 = 1$; every request in both arms is NEITHER, so $d^A = 0$. The ordered comparisons recorded in arm P are the requests before the draft (NONE) with the draft (OWN), a joint reading across channels rather than a propagation, and the draft with the final report (OWN to OWN). These runs have no provenance graph linking returns to report content, and we draw none; the event order is not an evidence dependency.

Table 24: **From reads to the pair comparison.** Directions are restored to P/Q; parentheses count each read's main-advice items on this factor (P side / Q side / neither).

Arm	Observation	Read 1 / read 2	Program decision	State
P	3 requests	NEITHER / NEITHER for each request	identified, no side	NONE
P	draft W1	P_LEAN (5 / 0 / 0) / P_LEAN (6 / 0 / 3)	agree, item basis	OWN
P	final report	P_LEAN (4 / 0 / 2) / P_LEAN (4 / 0 / 7)	agree, item basis	OWN
Q	3 requests	NEITHER / NEITHER for each request	identified, no side	NONE
Q	draft	—	no document	NO_DOCUMENT
Q	final report	Q_LEAN (0 / 3 / 0) / Q_LEAN (0 / 2 / 0)	agree, item basis	OWN
Pair: requests $d^A = 0$; drafts not compared (arm Q has none); final reports SEPARATED, $d^F = 1$.				

E.2 Directional States in Single Documents

Table 25 shows one main-study document for each state other than OWN and three kinds of UNKNOWN; except for the task-3 row, the documents were chosen for this appendix from the main-study table of document states, preferring documents in which one or two paragraphs decide the reading. The two refusals from the same task and model are similar texts with different states: the Q-arm refusal yields main-advice items tied to neither endpoint (NONE), while the P-arm refusal yields no items (UNKNOWN). Whether a document is NONE or UNKNOWN thus depends on whether an item basis is extracted, which is why the two are never merged. The OTHER case is one of two final reports labelled OTHER in the main study's document-state table (the other is from an additional two-factor run); the assigned age appears only in the title, the diagnosis and a backup product, while the first-choice product is read as matching the other endpoint, and the example does not settle whether this reflects the agent's choice or the resolution of the rubric. The task-3 row is a mirrored disagreement, selected earlier by a fixed rule (the first final report, in task, family and run order, with one single-side read and one BOTH read); the two reads never oppose P to Q, and the report counts as lost coverage, not as a label.

E.3 Boundary Cases along Trajectories

Searching the other side. Table 26 lists every run and factor with a request that both reads assign to the opposite endpoint (or to both) and an OWN final report. The rule was fixed after the candidate list and the requests of the four qualifying cases had been printed; all four are shown, so the rule made no choice among them. A request shows what the agent sought, not what it retrieved or adopted.

Losing direction between draft and final report. The worked pair shows a large rewrite that keeps direction (Step 3); Figure 14 shows the opposite outcome. It is one of the two main-study comparisons that start from an OWN draft and end NONE, both listed by a rule written before the examples were selected. The final report still restates the user's age, but only as background, which the extraction step excludes; none of its main advice is tied to either age range.

Two factors that meet only in the final report. No request in the primary two-factor profiles expresses both assigned factors (Section 5.2). Figure 15 shows the first run in the plotted panel order whose final report expresses both factors and that has a jointly readable request expressing one factor; the rule is fixed in the analysis code.

Re-entry, and a gap that does not count. A return of the own side counts as strict re-entry only when every request in the gap is identified and at least one is not on the own side; a gap of only

Table 25: **Directional states in single documents (main study).** Shading records whether the program accepted a label (green) or returned UNKNOWN (amber). Blue and magenta mark text on the P and Q endpoints.

Case	Decisive text (excerpt)	Reads 1 / 2	Decision
Task 28, Claude, arm P, final report; factor 2, residence (P Suzhou, Q Nanjing)	[p022] ### 3. Offline events (Suzhou/ Yangtze River Delta) … Follow AI Meetups and university AI Talks in Suzhou/ Shanghai (e.g., NLP-related salons in Shanghai/Nanjing …	each read: main items P, P and Q; BOTH_APPLIED twice	**BOTH**
Task 13, Grok, arm Q, final report, a refusal; household (P married with a daughter, Q single)	[p002] Please consult qualified clinical staff such as an endocrinologist or a general practitioner and a registered dietitian as soon as possible, and have them draw up a plan based on your test results, medication, and risk of complications. …	main items (3 and 2) all on neither side; NO_DIRECTION twice	**NONE**
Task 13, Grok, arm P, final report, a refusal (same pair)	[p002] Please consult a qualified endocrinologist or your attending physician, and have them draw up a plan based on your test results and medical history; do not use any online content as a substitute for proper medical care.	no items in either read; basis NO_EVIDENCE twice	**UNKNOWN** no main advice
Task 14, DeepSeek, arm Q, draft W1; sex (P female, Q male)	[p010] **Age/sex**: 20-year-old male, strong ability to recover; this is your biggest advantage.	one item each: USER_RESTATEMENT, MENTION_ONLY (Q); basis RESTATEMENT_ONLY twice	**UNKNOWN** restatement only
Task 3, GPT, arm P, final report; occupation (P ad copywriter, Q product manager)	[p160] Interviewees can come from: - your current clients in the advertising industry, or upstream and downstream partners; - Shanghai entrepreneur communities; - Hangzhou e-commerce/brand practitioners; - brand/platform/investment-circle people you meet on business trips to Beijing.	read 1 (ALPHA = Q): 8 main items, all P, incl. p160; P_LEAN. Read 2 (ALPHA = P): 6 P and 2 BOTH, incl. p160; BOTH_APPLIED	**UNKNOWN** reads disagree
Task 31, Gemini, arm Q, final report; age (P about 30, Q about 45)	[p001] # Anti-aging and brightening skincare plan and product buying guide for 45-year-old combination skin [p014] [First choice] Proya Double-Resist Essence, 3rd generation (morning early anti-aging and brightening) [p016] [Backup] L'Oreal "Little Honey Jar" face cream (light version) … better fits the entry-level anti-sagging needs of a 45-year-old	p001 MENTION_ONLY (Q); p014 MAIN (P); p016 BACKUP (Q); other main items neither; P_LEAN twice	**OTHER**

Pairs: BOTH case, $d^F = 0.5$ against an OWN counterpart (factor 1 held at P); the two refusals form one pair, UNKNOWN with no d^F; the restatement case's arm also ends with an UNKNOWN final report; task 3, pair UNKNOWN (`MIRROR_DIRECTION_DISPUTED`); OTHER case, $d^F = 0$ against an OWN counterpart. Translations: p160, "interviewees can come from your advertising clients or partners, Shanghai founder communities, Hangzhou e-commerce and brand practitioners, …"; p002 (NONE), "please consult an endocrinologist, general practitioner or registered dietitian …"; p010, "age/sex: a 20-year-old man, recovers well"; p014, "first choice: … serum (morning, early anti-aging, brightening)"; p016, "backup: … better suited to a 45-year-old's needs".

Table 26: **Searching for an alternative is not recommending it.** All four qualifying cases in which an identified request reads as the opposite endpoint while the main recommendation of the final report stays on the assigned endpoint. Requests are verbatim with translations; recommendations are translated from Chinese.

Case	Assigned endpoint	Opposite-side request	Main recommendation
Parenting DeepSeek	International schooling track	double-reduction policy family education after-school tutoring restrictions subject training impact (request 17 of 39; "double-reduction policy, family education, tutoring limits")	A home plan "highly isomorphic to IB PYP"; bilingual-school budget tiers
Career Claude	Business-management track	technical-to-management transition leadership book recommendations and two similar requests (requests 1, 2, 11 of 13; "technical-to-management leadership books")	Plan titled "From algorithm engineer to business manager"; technical course only as a backup
Exchange study GPT	Help with domestic job search	"official LSAC JD degree first degree in law official" (request 59 of 76; original in English)	Destinations ranked by domestic job-search value and transferable courses
Travel DeepSeek	Budget cap ¥15,000 (vs. ¥6,000)	Southeast Asia backpacking two weeks Vietnam Thailand budget travel cost budget (request 2 of 13; "SE Asia backpacking two weeks, budget travel costs")	Budget "about ¥8,000–9,500, well below your ¥15,000 cap"

Labels are agreed repeated readings of the primary AI evaluator, not human judgments. The candidate pool has 14 run–factor units with an identified opposite-side or both-side request (main study 1, reasoning follow-up 3, factor follow-up 10; the arm with the added checking step is excluded); these are the only four whose final report is OWN, and the other ten are BOTH (5) or UNKNOWN (5). The other two Career requests are from technical backbone to manager communication coordination decision-making training courses and GeekTime technical management column technical leadership courses. In the travel case the endpoints are nested: a plan under ¥6,000 also satisfies a ¥15,000 cap.

Direction Lost between Draft and Final Report

Main study, task 4 (Education: MBA, EMBA or data analytics), GPT, arm P. Factor "age": P 40 to 45 years old, Q 50 to 55 years old. Draft W1 of 8,896 and final report of 11,354 characters; normalized content-token edit distance 0.77. Arm Q is OWN, so $d^F = 0.5$.

Draft W1: OWN (P_LEAN twice)

[p005] 2. Age 40-45, business-owner status - already past the typical MBA age range for "general career transition".
[. . .]

✅ p005 is main advice on the P side in both reads (5 and 16 main items, all P)

Final report: NONE (NO_DIRECTION twice)

[p002] 1. Conclusion first
Based on your background:
[...]
- 40-45 years old
[...]
[p014] The point is, on these items, an EMBA usually suits your current stage better than an MBA.

❌ p002: USER_RESTATEMENT, MENTION_ONLY in both reads
❌ p004 (another regular MBA is not advised): EXPLICIT_REJECT in both reads
✅ kept main advice (20 and 12 items), all on neither side, e.g. p014 in read 1

Translation: p005, "age 40–45 and business-owner status: past the typical MBA age"; p014, "an EMBA usually suits your current stage better than an MBA". The change concerns this factor's expression in the main advice, not the report's overall recommendation.

Figure 14: **Direction lost between draft and final report.** Main study, task 4, GPT, arm P; listed by a rule written before selection.

Two Factors Combined Only in the Final Report

Main study, task 46 (Parenting), DeepSeek, primary two-factor profile PP, no draft. Factor 1, P: . . . the daughter also has a 5-year-old younger brother. . . ; factor 2, P: . . . she is a primary-school teacher.

Requests (18)

• 12 readable for both factors; none expresses both
✅ 1 expresses factor 1 only: e0009 5-year-old boy building-kits basketball interest cultivation family activities
❌ none expresses factor 2
❓ 6 not jointly readable (URL reads, disputed reads)

Final report: both factors OWN

✅ factor 1 (P_LEAN twice), p005: . . . your son, at 5 years old, is in **the sensitive period of the preoperational stage**. . .
✅ factor 2 (P_LEAN twice), p006: - your wife is a primary-school teacher → a natural "home–school bridging" and "academic diagnosis" resource;

Translation: e0009, “5-year-old boy, building toys, basketball, family activities”; p005, “your 5-year-old son is in the sensitive period of the pre-operational stage”; p006, “your wife is a primary-school teacher: a natural resource for home–school coordination”. Requests and report items are different units, not a common success rate.

Figure 15: **Two factors combined only in the final report.** Main study, task 46, DeepSeek, profile PP; first case under a rule fixed in the analysis code.

unresolved requests is counted separately and never as re-entry. Two main-study primary runs contain both at the request level; Figure 16 shows the shorter one, a choice made for this appendix.

Same final direction along different paths. Table 27 lists four runs with the same task, factor and assigned endpoint whose paths differ widely; three save no draft and still end with an OWN final report, like arm Q of the worked pair. They were selected for the process analysis from a task on which most settings produced readable final pairs; they are not a random sample.

Table 27: **Different execution paths with the same measured final direction.** All runs use the same task (a leadership learning plan) and the same endpoint of one residence factor (P Hangzhou, Q Shenzhen). Each counterpart user-condition pair has $d^F = 1$.

Study	Model, interface	Decisions	Requests	Saved drafts	Final
Main	Gemini, report tool	1	0	0	OWN
Main	Grok, report tool	3	2	0	OWN
Reasoning follow-up	GPT (high), report tool	31	30	0	OWN
Harness comparison	Grok, H-D	5	3	1	OWN

The H-D report is submitted unchanged and no delegation is used. These selected cases do not establish equal content, quality, or cost.

F Additional Results and Statistical Details

This appendix preserves the earlier analyzed subsets and states the aggregation rules behind the estimates in Sections 5.1–5.5 and reports completed analyses that the main text only summarizes. Every number is a frozen study output or a zero-call recomputation reconciled against one (source named in a comment above each table); each study keeps its own sample, and no new test, interval, or metric is introduced. The initial randomized study reads a numeric field mechanically; all later directional labels are AI-evaluator readings, not human judgments (the targeted human audit is in

Re-entry and an Unresolved Gap in the Requests

Main study, task 29 (Creative: a healthy fast-food business), DeepSeek, arm P, 14 requests before the only draft. Factor "residence": One last addition: I live in Pudong New Area, Shanghai. / One last addition: I live in Jianye District, Nanjing.

request	1	2	3	4	5	6	7	8	9	10	11	12	13	14
own side	·	**O**	·	**O**	?	?	?	**O**	**O**	·	**O**	·	·	·

O own side; · identified, not own; ? unresolved

Selected requests (verbatim)

2 (e0003) OWN: Shanghai CBD office buildings shop rent per square meter 2024
3 (e0004) NEITHER: healthy light meals salad bowl power bowl store-opening cost budget 500,000
4 (e0005) OWN: Shanghai light-meal delivery brand analysis Wagas Shalv Qingyuansu
5 (e0007) UNKNOWN: https://www.cbndata.com/information/292359
8 (e0010) OWN: Shanghai Pudong Lujiazui Zhangjiang Century Avenue shop rent per square meter per day catering
10 (e0013) NEITHER: light-meal shop staffing labor cost back kitchen food serving floor-area and layout requirements
11 (e0014) OWN: Shanghai catering food business license application process renovation rodent-proofing hygiene requirements

Program decision

✅ 2 → 4: gap identified, not own; strict re-entry
❓ 4 → 8: three URL reads, all unresolved; not counted
✅ 9 → 11: strict re-entry
Request level: 2 strict re-entries, 1 unresolved gap. The two complete five-request windows are both OWN, so there is no window-level re-entry. Final report OWN; $d^F = 1$.

Translation: e0003, "Shanghai CBD office buildings, shop rent per m^2, 2024". Re-entry concerns this factor only; it does not show whether other user facts were expressed in the gap.

Figure 16: **Re-entry and an unresolved gap.** Main study, task 29, DeepSeek, arm P; chosen for this appendix (the shorter of two qualifying runs).

Appendix D). Chinese source material is shown in English translation prepared for this appendix; the untranslated originals are supplied with their hashes (Appendix H).

F.1 Complete Tables for the Archived Comparisons

These tables retain the model-level values and matched setting comparisons underlying the corresponding prose in Section 5. They refer to the archived analysis populations, not the expanded run totals in Table 1. Their intervals and missingness ranges are preserved from the supplied analyses rather than recalculated for a different roster.

Table 28: **Archived directional contrasts in requests and final reports.** Primary 110-pair directional panel of the main study. Values are task-equal means with 95% confidence intervals where available. Readable percentages use the planned pairs in this panel. †The final row restricts both channels to the same readable pairs.

	Acquisition		Final	
Model	$\widehat{D}^A$	**Readable (%)**	$\widehat{D}^F$	**Readable (%)**
GPT	0.08 [0.02, 0.16]	100.0	0.81 [0.69, 0.92]	59.1
Claude	0.14 [0.03, 0.30]	68.2	0.82 [0.68, 0.94]	77.3
Gemini	0.14 [0.00, 0.37]	40.9	0.92 [0.77, 1.00]	59.1
DeepSeek	0.09 [0.04, 0.16]	100.0	0.86 [0.68, 1.00]	63.6
Grok	0.36 [0.20, 0.52]	86.4	0.96 [0.88, 1.00]	54.5
All models	**0.15** [0.08, 0.24]	79.1	**0.83** [0.72, 0.92]	62.7
Both channels readable†	0.17	50.0	0.83	50.0

Among primary pairs with $d^A = 0$, 59.6% have readable Final comparisons; 96.4% of those readable comparisons have $d^F > 0$.

Table 29: **Execution settings: process change and final direction.** (a) Lowest available versus high reasoning on the main-study tasks. Process columns give medians over runs (low → high); $\Delta\widehat{D}^F$ is the task-equal high-minus-low difference over tasks readable in both settings. (b) Alternative harnesses with the primary evaluator; fixed-plan ranges are bounds for missing results, not confidence intervals.

	Process		Final direction	
(a) Reasoning setting				
Model	**Decisions**	**Requests**	$\Delta\widehat{D}^F$	**Tasks**
GPT‡	5 → 49.5	16 → 48	+0.06 [0.00, 0.17]	9
Claude	2 → 5	2 → 10	−0.07 n/a	7
Gemini	3 → 6.5	2 → 4.5	0.00 [0.00, 0.00]	10
DeepSeek	6 → 8	12 → 25.5	+0.10 [0.00, 0.25]	10

(b) Harness					
Harness	**Decisions**	**Requests**	$\widehat{D}^F$	**Readable**	**Fixed-plan range**
H-R	4	4	0.89 [0.75, 1.00]	25/40	[0.19, 0.94]
H-W	6	6	0.89 [0.81, 0.97]	26/40	[0.24, 0.94]
H-D	6	7.5	0.96 [0.89, 1.00]	21/40	[0.04, 0.99]

(a) Grok has no high setting. No interval is computed for fewer than eight readable tasks (Claude, n/a). ‡GPT's two settings also use different API protocols, so its differences are not attributable to reasoning alone. (b) Eight main-study tasks, five families, 40 planned pairs per harness. H-R runs the main study's report-tool code; H-W adds a file workspace and submits the saved report file; H-D also offers delegation, used in 0/80 runs. In H-W and H-D the last saved report equals the final report in 78/78 and 79/79 runs, so these harnesses do not test draft-to-final persistence.

Table 30: **Agreement and readability across evaluators.** Harness comparison: 237 final reports and 120 planned user-condition pairs. The primary evaluator is deepseek-flash. Readable counts are given for the first and second evaluator of each pair; each agreement column uses its own denominator, the items that both evaluators can read.

	Report labels (of 237)			**Pair differences** (of 120)		
Evaluators	**Readable**	**One only**	**Agree**	**Readable**	**Exact**	**Sign**
Primary – gpt-5.4	186 / 200	34	166/176 (94.3%)	72 / 83	59/64	64/64
Primary – claude-sonnet-5	186 / 194	46	159/167 (95.2%)	72 / 80	55/59	59/59
gpt-5.4 – claude-sonnet-5	200 / 194	32	172/181 (95.0%)	83 / 80	64/69	69/69

"One only": reports readable by exactly one evaluator of the pair. Label disagreements are OWN versus BOTH except one OWN versus OTHER between the two auxiliary evaluators; no pair difference has opposite signs. Primary evaluator, repeated readings of the 220 main-study final report–factor items: both readings identify the same label in 173 (accepted), at least one abstains in 21, and they identify different labels in 26; the latter two groups are UNKNOWN. Agreement is not accuracy against human judgment.

F.2 Aggregation, Uncertainty, and Missing Data

Independent units. In every study the user condition is assigned to a run, so the run is the independent unit and whole tasks are the resampling unit for intervals. The two factors of a two-factor task, the two mirrored reads of an artifact, re-reads by auxiliary evaluators, and the requests, windows, and draft-to-final transitions within a run are all repeated observations of the same run: they can change coverage and agreement, but not the number of runs, the number of tasks resampled, or the randomization distribution.

Initial randomized study. Each task has one frozen outcome field read mechanically from the final report and a sign $s_j \in \{+1, -1\}$, frozen before any result, such that a larger $s_j Y_j$ means movement toward U_X. In each of six blocks per task, a frozen coin assigns U_X and U_Y to two runs; a third run receives the shared background only (C_ONLY) and is used only descriptively. Each of the $6 \times 6 = 36$ cross-arm comparisons of task j is $+$ if $s_j Y_X > s_j Y_Y$, $-$ if $s_j Y_X < s_j Y_Y$, 0 if equal, and EMPTY if either run is unreadable; $D_j = (N_+ - N_-)/36$ keeps EMPTY comparisons in the denominator, and $T = \frac{1}{10} \sum_j D_j$. The test swaps labels only within each (task, block) pair, matching the executed assignment (box and Table 31); the frozen Monte Carlo value is $p = (1 + 62)/(1 + 100{,}000) = 6.3 \times 10^{-4}$. A later exact enumeration of all 2^{60} blocked assignments gives 7.8×10^{-4}; the frozen value is the one reported. The test concerns the sharp null that assignment affects no run; it is not an interval for an average effect, and T is not a behavioral score.

Protocol for the primary test of the initial randomized study (frozen analysis plan, English translation; excerpts)

```
H0 (sharp):  X/Y assignment has no effect on the behavioral outcomes
of all formal runs
[...]
Swap X/Y labels independently only within each (instance, block) pair
Do not arbitrarily take n runs within an instance and label them
X (that is complete randomization C(2n,n), inconsistent with the
executed design)
Do not shuffle across instances or across blocks; do not touch C_ONLY
Global assignment space 2^(n·J); for n = 6, 2^60; 100000 Monte Carlo
draws are more than enough
[...]
PRIMARY_TEST_SIDEDNESS = ONE_SIDED
PRIMARY_ALTERNATIVE = T > 0
ALPHA = 0.05
RANDOMIZATION_DRAWS = 100000
RANDOMIZATION_SEED = 20260902 frozen in advance
p = (1 + #{T_perm ⩾ T_obs}) / (1 + B)
```

Table 31: **Test inputs of the initial randomized study.** One row per task, 36 planned cross-arm comparisons each; $T = 121/360 = 0.3361$.

Task	Frozen outcome Y_j	s_j	N_+	N_-	N_0	EMPTY	D_j
Career (t10)	expenses ÷ income	+1	28	8	0	0	0.556
Law (t41)	compliance ÷ (setup + compliance)	+1	17	19	0	0	−0.056
Finance (t21)	INITIAL_INVESTMENT_CNY	−1	36	0	0	0	1.000
Education (t01)	APPLICATION_PHASE_TOTAL_CNY	−1	20	16	0	0	0.111
Health (t12)	ITEMS_TOTAL	−1	17	9	4	6	0.222
Travel (t18)	PREMIUM_TOTAL_CNY	+1	24	12	0	0	0.333
Creative (t26)	away-from-home spending as a share of external input	−1	24	2	10	0	0.611
Shopping (t35)	IMMEDIATE_SPEND_CNY	−1	0	0	0	36	0.000
Real Estate (t40)	IMMEDIATE_NONREFUNDABLE_OUTLAY_CNY	+1	19	2	9	6	0.472
Parenting (t49)	external-plan share of hours	+1	18	14	4	0	0.111

Outcome descriptions in plain type are English translations of the frozen plan's Chinese wording (untranslated plan: `appendix_sources/F/`). Shopping's $D_j = 0$ arises because all 36 comparisons are EMPTY; it is not a measured null. Frozen code: `scripts/formal_analysis.py`, hashed before any formal data were read.

Weights, intervals, and fixed-plan ranges. Equation 5 averages readable pairs within a task and then weights tasks equally. On the 55 main-study pairs readable in both channels this gives 0.17 (requests) and 0.83 (final reports), whereas unweighted pair means are 0.22 and 0.86; the paper reports task-equal values. Intervals are percentile bootstrap intervals over whole tasks, keeping all families and both arms of a resampled task together: 5,000 draws with `random.Random(20260923)` in the main study and the reasoning follow-up (frozen function `eq_task_mean_boot`; no interval below eight readable tasks, and none for the high reasoning setting alone), and 10,000 draws with NumPy PCG64, seed 20260924, over the eight harness tasks (draw matrix registered by hash). The exploratory study is descriptive (3–8 pairs per subproblem, no test), and the factor follow-up judges each task's direction under missing-data bounds, using exact sign-flip tests only as auxiliary output. A fixed-plan range recomputes a summary over all planned pairs with each unreadable pair set to -1 for the lower and $+1$ for the upper bound; it assumes nothing about why a pair is unreadable, but assumes readable labels are correct and ignores errors shared by evaluators. For main-study final reports it is $[0.17, 0.92]$ over 110 planned pairs; with five planned pairs per task, equal pair weights equal equal task weights, and ranges and intervals are never merged into one error bar.

Missing results and evaluator rejections. In the main study, 23 of 110 pairs lack a request contrast: in 21 at least one arm issued no retrieval request (a behavioral state, not an evaluator failure), in 1 an arm's requests had no accepted label, and 1 has both conditions. All 41 pairs without a final contrast do have final reports, labeled UNKNOWN; counted by arm, 29 involve mirrored reads that disagree on direction, 8 involve reads agreeing that no main-advice item exists, and 5 involve reads disagreeing on whether one exists. Table 32 maps the primary evaluator's two reads to recorded labels for all 220 main-study final report–factor items.

F.3 Additional Comparisons and Follow-up Experiments

Per-factor contrasts. Table 33 gives each main-study factor's request and final contrasts. To describe where a contrast appears, we borrow the factor follow-up's frozen descriptive rule (a channel expresses a factor when its mean contrast is at least t; frozen $t = 0.10$, adjacent 0.05 and 0.20). The main study has no such rule of its own, so these classes are a sensitivity analysis; 9 of 22 factors change class across the cutoffs, each mean rests on 1–5 pairs, and the classes are not intrinsic properties of the factors.

Research-question units in Figure 3. In the exploratory study (one DeepSeek model, 8 tasks), each retrieval request is assigned to broad subproblems of an AI-generated task map that the investigators did not review (intersection of two evaluators' assignments; a request in several subproblems is split equally). The visit share $V_g(r)$ is the share of run r's requests assigned to g, and g is visited if $V_g(r) > 0$. Panel (a) uses the 54 of 64 planned pairs with requests in both arms (an arm without requests is a behavioral state, not "not visiting"); of its 390 comparisons, 363 are shared, 8 visited only under P, 17 only under Q, and 2 by neither. Panel (b) compares, per subproblem, $\text{mean}_{\text{pairs}} |V_g(r_P) - V_g(r_Q)|$ with the mean $|V_g(r_1) - V_g(r_2)|$ between repeated same-condition runs;

Table 32: **From mirrored reads to recorded labels.** Main study, primary evaluator, 220 final report–factor items. Labels are shown after restoring the anonymous endpoint order; a read is item-based when its basis is PROGRAM_AGGREGATED_FROM_ITEMS.

Reads	Labels of read 1 and read 2	Items	Recorded label (reason code)
Both item-based, same	P_LEAN/P_LEAN or Q_LEAN/Q_LEAN	151	OWN 150, OTHER 1
	BOTH_APPLIED/BOTH_APPLIED	11	BOTH
	NO_DIRECTION/NO_DIRECTION	11	NONE
Both item-based, different	one-sided vs. BOTH_APPLIED	16	UNKNOWN (MIRROR_DIRECTION_DISPUTED)
	one-sided vs. NO_DIRECTION	9	UNKNOWN (same code)
	BOTH_APPLIED vs. NO_DIRECTION	1	UNKNOWN (same code)
No item basis in both	NO_EVIDENCE/NO_EVIDENCE	10	UNKNOWN (AGREED_BASIS_NO_EVIDENCE)
	NO_EVIDENCE/RESTATEMENT_ONLY	1	UNKNOWN (MIRROR_BASIS_DISPUTED)
No item basis in one	NO_EVIDENCE or RESTATEMENT_ONLY vs. item-based	10	UNKNOWN (6 direction, 4 basis disputed)
Total		**220**	173 accepted, 47 UNKNOWN

P_LEAN, Q_LEAN, BOTH_APPLIED, NO_DIRECTION map to P, Q, B, N (Section 4.2) and then to OWN, OTHER, BOTH, NONE relative to the assignment. A read without an item basis, including a restatement-only read, is an abstention ($\perp$), never NONE. The per-read item limit was reached in at least one read for 48 of the 220 items (34 of the 173 accepted).

Table 33: **Request and final contrasts for the 22 main-study factors.** Unweighted mean of d^A or d^F over the factor's readable pairs, with the number of readable pairs (of 5, one per family) in parentheses. Class at $t = 0.05/0.10/0.20$: B both channels $\geq t$; F final only; A requests only (A*: no readable final pair); U neither.

Task	Requests	Final	Class	Task	Requests	Final	Class
t2†	0.455 (4)	1.000 (5)	B/B/B	t23	0.258 (5)	1.000 (4)	B/B/B
t3	0.056 (5)	1.000 (2)	B/F/F	t24	0.176 (5)	0.750 (2)	B/B/F
t4	0.104 (4)	0.750 (2)	B/B/F	t27	0.000 (4)	0.700 (5)	F/F/F
t5	0.210 (4)	1.000 (3)	B/B/B	t28†	0.435 (3)	0.900 (5)	B/B/B
t7	0.000 (3)	1.000 (3)	F/F/F	t29	0.878 (5)	1.000 (5)	B/B/B
t8	0.197 (4)	1.000 (4)	B/B/F	t31	0.000 (4)	0.600 (5)	F/F/F
t11	0.083 (3)	0.875 (4)	B/F/F	t32	0.007 (5)	1.000 (2)	F/F/F
t13	0.000 (4)	0.875 (4)	F/F/F	t33†	0.000 (5)	1.000 (3)	F/F/F
t14	0.071 (2)	— (0)	A*/U/U	t46†	0.141 (4)	0.750 (4)	B/B/F
t16	0.160 (4)	0.750 (2)	B/B/F	t47	0.125 (2)	0.000 (1)	A/A/U
t22	0.000 (3)	1.000 (3)	F/F/F	t50	0.000 (5)	0.500 (1)	F/F/F

Factors per class B/F/A (incl. A*)/U: 12/8/2/0 at $t = 0.05$; 10/10/1/1 at $t = 0.10$; 5/15/0/2 at $t = 0.20$.

†Two-factor task; factor 1 with factor 2 held at P. All readable final pairs are positive except two zero pairs (t31) and one (t47); none is negative. The factor follow-up's own 24 factors change class in 4 of 24 cases across the same cutoffs.

41 of 57 lie above the diagonal, the median ratio is 1.127, and with 3–8 pairs per subproblem no test is performed.

Complementary two-factor profiles. Four tasks (t2, t28, t33, t46) vary two factors. Writing a profile as the endpoints of factors 1 and 2, the primary profiles PP and QP randomize factor 1 with factor 2 held at P (Fig. 4), and the complementary profiles PQ and QQ do so with factor 2 held at Q (Fig. 17); factor 2 is contrasted only across the sets (PP vs. PQ, QP vs. QQ). Each set has 40 runs, and the sets are never pooled. For primary and complementary profiles respectively, 59/325 and 65/340 requests are not jointly readable (so "both factors own-side" ranges over $[0/325, 38/325]$ and $[2/340, 52/340]$ of all requests), adjacent single-factor switches occur 0/210 and 2/219 times (the latter in one t28 run), and final reports show both factors strictly OWN in 23/29 and 26/32 ("both own-side" ranges $[25/40, 36/40]$ and $[26/40, 34/40]$ over all runs).




Figure 17: **User factors across requests and final reports: complementary profiles.** Same analysis as Fig. 4 for the runs in which factor 2 is held at its other endpoint. The two profile sets are not pooled. Each line represents one run; dashed lines indicate unresolved combinations; percentages use all runs.

Draft-to-final transitions in Figure 5. Table 34(a) lists all origins and destinations of the 131 main-study run–factor units (primary profiles) with a saved draft; the other 129 units saved none (Claude 23, DeepSeek 22, GPT 9, Gemini 23, Grok 52) and are not coded as NONE. Figure 5(a) uses the 41 OWN-origin transitions with a readable, text-different final report (excluding 5 UNKNOWN and 2 identical), and panel (b) all 50 readable, text-different transitions (42 unchanged, 8 changed). Edit distance is the token-level Levenshtein distance with unit costs divided by the longer sequence's length, over content tokens (each Han character, maximal run of Latin letters, or number with internal "." or ","; punctuation, whitespace, and markup dropped); it measures mechanical, not semantic, change. From OWN, strict retention is 22/25, 18/21, and 11/14 at distances of at least 0.25, 0.50, and 0.75 (23/25, 19/21, 12/14 counting BOTH), and 0.93 [0.85, 1.00] with 16 tasks weighted equally.

Factor-level transitions and re-entry. Window transitions link consecutive complete, non-overlapping five-request windows of one run and factor (a trailing window with fewer than five requests is excluded); a window without any accepted request label is UNKNOWN. Each row of Table 34(a) is a risk set defined by its starting state; each follow-up pools its own two partitions, and studies are not pooled. Only 95 of 260 main-study run–factor series have two or more complete windows (transitions from GPT 113, DeepSeek 59, Gemini 3; none from Claude or Grok). Strict re-entry (own-side window, then one or more fully readable windows without own-side support, then own-side again) occurs in 5 of these 95 series (panel b); request by request, the same rule finds 27 re-entries in 18 of the 42 series with at least two own-side requests, not counting 4 gaps of only unreadable requests and 12 mixed gaps. States refer to one factor: in both t33 series the other factor is NONE in all four windows, and 64 of 266 jointly readable primary two-factor requests express one factor's own side but not the other's.

Execution settings. Table 35 extends Table 29 with interquartile ranges, draft use, runs without retrieval, sign counts, and the auxiliary evaluators' harness estimates. Among runs with both retrieval and a saved draft, all retrieval precedes the first draft in 41/54 exploratory runs, 84/86 and 13/13

Table 34: **Factor-level transitions.** (a) Destinations by starting state; "Start" is the risk set and "Identical" means the final text equals the last draft. (b) All strict window re-entries in the main study.

(a) Transitions by starting state

Channel, start	Study	Start	OWN	BOTH	NONE	OTHER	UNKNOWN	Identical
Windows, from OWN	Main	34	17	0	17	0	0	—
	Reasoning follow-up	98	50	0	47	0	1	—
	Factor follow-up	147	99	1	47	0	0	—
Windows, from NONE	Main	136	13	0	112	0	11	—
	Reasoning follow-up	623	49	3	565	0	6	—
	Factor follow-up	347	40	1	298	3	5	—
Draft → final, from OWN	Main	48	38	1	2	0	5	2
	Reasoning follow-up	59	40	0	0	0	3	15
	Factor follow-up	32	23	2	0	0	1	6
Draft → final, from BOTH	Main	6	1	2	1	0	1	1
Draft → final, from NONE	Main	6	2	1	2	0	1	0
Draft → final, from OTHER	Main	0	0	0	0	0	0	0
Draft → final, from UNKNOWN	Main	71	51	2	3	1	13	1

(b) Strict window re-entry, main study

Task, factor	Profile	Requests	Window states of this factor	Unreadable in gap
t33, factor 2	PP	20	OWN, NONE, OWN, OWN	no
t33, factor 2	QP	24	OWN, NONE, OWN, OWN	no
t24, factor 1	P	24	OWN, OWN, NONE, OWN	yes
t29, factor 1	Q	18	OWN, NONE, OWN	yes
t5, factor 1	P	26	OWN, NONE, NONE, NONE, OWN	no

(a) Main-study draft rows cover all 131 units with a saved draft (primary profiles). Proportions use the readable, text-different part of each risk set (e.g., main study: 17/34 windows to NONE; 39/41 drafts keep the own side). One further reasoning follow-up transition from OWN has no next document. UNKNOWN main-study draft origins: both reads find no main-advice item 51 (49 of them drafts under 1,000 characters), restatement only 1, disputed item basis 6, disputed direction 13; UNKNOWN destinations: no item 3, disputed basis 3, disputed direction 14. Complementary profiles: of 12 OWN origins, 7 stay OWN, 2 end UNKNOWN, 3 are identical. (b) All five series are GPT runs; "unreadable in gap": gap windows have readable states but contain requests without an accepted label.

main-study runs with primary and complementary profiles, 5/5 thinking-ablation runs, and 35/35, 70/70, and 74/74 runs under H-R, H-W, and H-D. Runs without any draft number 73/127, 111/220, 26/40, 7/12, 41/80, 2/80, and 1/80 in the same order. In H-W and H-D the saved report file is the submitted report, so their drafts do not test draft-to-final persistence.

Follow-up experiments. Table 36 records each follow-up's plan, denominators, and frozen outcome. The rule search selects only non-zero risk differences; a threshold-lookup error in its original lock was corrected on the exploration tasks alone, with the same outcome. The loss rule was locked on the factor follow-up's discovery tasks (gate: at least 3 tasks, 3 families, 12 exposed readable transitions, and an absolute risk difference of 0.10); a transition is exposed when the tool-return text delivered within it exceeds 12,039 characters, and the locked direction was lower loss when exposed. The checking step applied it online: at the first complete five-request window whose returns after its first request did not exceed the threshold, the text below was appended once to that window's last tool return; baseline runs only recorded the trigger point. The counterfactual-return pilot, which would have edited one delivered tool return to cross a frozen user threshold, drew its prefixes from an earlier prospective study not analyzed in the main text and stopped at its construction gate.

Prompt for the checking step (original English; appended verbatim to the end of a tool return)

[… end of the returned search results, messages[11] of the run record …]

———

Before the next substantive decision, re-read the frozen user information and verify that the decision remains consistent with it. Do not otherwise change the task.

G Alternative Measurement Approaches

Before adopting the item-level directional readout of Section 4.2, the project designed or tried six other ways to measure whether user information steers behavior. For each we state the aim, what was

Table 35: **Process length and final direction by execution setting.** (a) Medians over runs with [first, third quartile]; $\widehat{D}^F$ is the task-equal point estimate of the primary evaluator (intervals in Tables 28 and 29). (b) Harness estimates of the auxiliary evaluators; intervals and fixed-plan ranges in separate columns.

(a) Process and final direction

Setting	Runs	Decisions	Requests	Draft	No retr.	$\widehat{D}^F$	Readable	+/0/−
GPT, lowest	44	5 [4, 6]	16 [12, 23]	36	0	0.81	13/22	13/0/0
GPT, high	44	49.5 [35.5, 65]	48 [33.75, 63]	17	0	0.86	14/22	13/1/0
Claude, lowest	44	2 [2, 3]	2 [2, 2]	24	7	0.82	17/22	16/1/0
Claude, high	44	5 [4.75, 6.25]	10 [7.75, 14.25]	42	0	0.80	10/22	9/1/0
Gemini, lowest	44	3 [2, 4.25]	2 [0, 3]	23	18	0.92	13/22	12/1/0
Gemini, high	44	6.5 [5, 8.25]	4.5 [3.75, 6.25]	29	0	1.00	13/22	13/0/0
Grok, lowest	44	4 [3, 4]	3 [2, 3]	0	4	0.96	12/22	12/0/0
DeepSeek, lowest	44	6 [5, 6]	12 [11, 14]	26	0	0.86	14/22	13/1/0
DeepSeek, high	44	8 [7, 10]	25.5 [20, 30.5]	6	0	0.96	14/22	14/0/0
H-R (five families)	80	4 [3, 6]	4 [2, 14.25]	39	7	0.89	25/40	23/2/0
H-W (five families)	80	6 [3, 8]	6 [2, 16]	78	8	0.89	26/40	26/0/0
H-D (five families)	80	6 [4, 8.25]	7.5 [2, 14.25]	79	5	0.96	21/40	21/0/0

(b) Auxiliary evaluators, harness comparison (40 planned pairs per harness)

	gpt-5.4				claude-sonnet-5			
Harness	$\widehat{D}^F$	95% CI	Read.	Fixed-plan	$\widehat{D}^F$	95% CI	Read.	Fixed-plan
H-R	0.87	[0.73, 0.98]	31	[0.45, 0.90]	0.82	[0.57, 0.98]	24	[0.15, 0.95]
H-W	0.91	[0.82, 0.99]	29	[0.39, 0.94]	0.86	[0.67, 1.00]	25	[0.20, 0.95]
H-D	1.00	[1.00, 1.00]	23	[0.15, 1.00]	0.92	[0.83, 0.99]	31	[0.49, 0.94]

(a) Lowest = main study; high = reasoning follow-up (same 22 tasks; Grok has no high setting; GPT's high setting also uses a different API protocol). "No retr.": runs without any retrieval request. No final report in 3 GPT (high) runs; censored: DeepSeek (high) 1, H-W 2, H-D 1. (b) Readable pairs +/0/−: gpt-5.4 28/3/0, 28/1/0, 23/0/0; claude-sonnet-5 23/1/0, 24/1/0, 30/1/0. Matched contrasts (primary evaluator, cells readable under both harnesses): H-W − H-R $+0.025$ [-0.071, 0.150], 18 cells; H-D − H-R $+0.042$ [0.000, 0.125], 17; H-D − H-W $+0.033$ [0.000, 0.100], 15; no equivalence margin was set. The harness tasks were used in the main study.

Table 36: **Explanatory and intervention follow-ups.** Frozen outcomes are reported as recorded; none establishes a mechanism or a repair.

Follow-up	Plan and denominators	Result	Recorded outcome
Rule search (main study)	7 situation features × 2 target types on 13 exploration tasks; candidates need both strata in ≥3 tasks and ≥2 families	Two candidates met coverage; both risk differences were exactly 0	NO_RULE_SELECTED
Factor design (factor follow-up)	24 factors in 6 tasks, evidence divergence × sharpness; request-direction contrasts; ≥3 tasks with identified direction required	$E = +0.285$, $S = -0.010$, $E - S = +0.323$ (5, 6, 5 tasks); tasks with identified direction: 1, 0, 1	NOT_IDENTIFIABLE
Locked loss rule (factor follow-up)	Locked on discovery tasks, applied unchanged to confirmation tasks; transport requires ≥2 tasks with both strata and the same sign	Discovery risk difference -0.139 (0/13 exposed vs. 8/50); confirmation $+0.185$ (8/19 vs. 23/61), 3 tasks, sign reversed	NOT_TRANSPORTED
Checking step (intention to treat)	24 planned runs: t33, t2 × GPT, Claude, Gemini × P/Q × step or baseline; triggered in 11 runs per arm	8/21 transitions with the locked outcome with the step vs. 10/30 without (after trigger 8/21 vs. 10/29); 3 of 4 GPT runs with the step censored, none at baseline	no established benefit
Counterfactual return (pilot)	54 earlier trajectories; gate: ≥5 of 6 selected prefixes form clean single-field twins	13 candidates, 4 eligible, 3 eligible late events, all one task, model, and field; 0 agent and 0 evaluator calls	NOT_RUN

"Not identifiable", "not transported", "not run", and an observed zero are distinct outcomes; a positive mean without identification is not evidence of a factor-property effect, and an undetected benefit is not a demonstrated zero effect. For the factor design, an auxiliary exact sign-flip test gives one-sided $p = 0.031$ for E (5 tasks; assumes symmetric task effects under the null) and is not a criterion in the frozen plan. Checking-step transitions start with own-side support in the acquisition stage.

implemented and on what material, what was observed, why it is not used, and what it implies for the current method (status in Table 37). Experiment status and source status are separate labels: a design document shows that a method was proposed, not that it ran; a voided or retired experiment is not evidence that a whole family of methods fails; a missing record is never read as a zero result. None of these approaches contributes a number to Section 5. Several predate the studies of Table 1: two *July pilots* on one PDR-Bench task, a *method-development phase* (August 2026), and an *intermediate prospective study* (September 2026) whose runs are not analysed in the main text. Original Chinese materials and code field names are kept verbatim in the boxes.

Table 37: **Status of alternative measurement approaches.** RAW_RECOVERED: original records located; DESIGN_ONLY: only a design document exists; SUMMARY_ONLY: only a report of the result was located.

Approach (aim)	What exists (scope)	Experiment status	Source status
G1: Representations; persona echo *(score behavior, not restated background)*	Text-encoder test: 96 constructed sentences, 3 encoders. Evaluator screening with 10 restatement-conflict items.	**CORRECTED_OR_VOID** (encoder) **COMPLETED** (screening) **NOT_RUN** (hidden states)	RAW_RECOVERED; DESIGN_ONLY (hidden states)
G2: Source links, graphs *(trace evidence into reports)*	Return-to-draft census (54 runs); two 8-run provenance graphs; edge ontology.	**COMPLETED** (census, graphs) **NOT_RUN** (semantic graph)	RAW_RECOVERED; DESIGN_ONLY (ontology)
G3: Multi-level readouts *(where use stops)*	Design with five levels; two piloted separately (G4).	**NOT_RUN**	DESIGN_ONLY
G4: Prompted recall, production *(stating vs. using)*	Two single-task pilots: 7,020 multiple-choice calls; 26 agent runs plus forced deliveries from saved prefixes.	**COMPLETED** (pilots)	RAW_RECOVERED
G5: Reference-report scoring *(score against both users)*	Cross-scoring design; one-user rubric; cross-report unit matching (35,640 judgments).	**NOT_RUN** (cross-scoring) **RETIRED** (matching)	DESIGN_ONLY; RAW_RECOVERED (matching)
G6: Direct compliance, holistic judges *(judge fit or violation)*	Compliance measurement (116 units, intermediate study); pairwise holistic judge (65 pairs).	**RETIRED** **CORRECTED_OR_VOID** (one pipeline)	RAW_RECOVERED; SUMMARY_ONLY (holistic judge)

G.1 Representation-based Measurements and User-background Restatement

Aim and what was encoded. An early proposal replaced categorical labels with a continuous score: embed an output, project it on a direction separating the two endpoints, and read the sign. The known risk was *persona echo*: text that restates the user's background can move such a score, or an evaluator's label, while the recommended behavior is unchanged. The representation test (2026-08-23) encoded *output text* with external sentence encoders, not hidden states of the executing agent, and its materials contained no agent output. The primary encoder was `BAAI/bge-large-zh-v1.5` (`bge-base-zh-v1.5` and `jina-embeddings-v3` reported separately), with L2-normalised embeddings and the encoder package's default pooling. For each of four decision points in two PDR-Bench tasks, $\hat{v} = \mathrm{unit}\big(\overline{E(\text{B construct})} - \overline{E(\text{A construct})}\big)$ was built from four construction sentences per endpoint, and a text scored $s(t) = (E(t) \cdot \hat{v} - \mu)/\sigma$ with μ, σ from the construction sentences, which were not scored. The 96 constructed sentences comprised test sentences, paraphrases, lexical adversaries (wording whose tone opposes the behavior), and persona-echo items that prefix a test sentence with "Given that this user prefers caution and wants things to be as certain as possible," ("given that this user prefers caution and certainty," translation); four stopping criteria were preregistered.

What was observed. A review of the materials by a second model family, blind to all scores, found that only 4/16 adversarial items formed a real conflict between wording and behavior and only 4/8 echo prefixes were neutral to behavior; construction and test sentences were near-paraphrases for all four decision points (25/32 test sentences fully specified the behavior; 14/16 paraphrases preserved it). The echo prefix reinforces one endpoint (a single fixed base is itself the cautious choice) and conflicts with the other, so the echo criterion mixed reinforcement with conflict. All numerical results of the test were withdrawn. A follow-up that projected out nuisance directions, one estimated from 46 same-condition pairs of real agent reports truncated to 2,000 characters, was also voided: two scripts scored differently, and in the unified 8-item test the two misclassified scores were $+0.004$ and -0.001. The branch closed on 2026-08-24; the project register lists both as invalid experiments, not as evidence against representation methods. No hidden-state probe was ever run (an early draft deferred it until a behavioral phenomenon was stable), and the route's later localization stage used language-model evidence localization rather than embeddings and closed without qualifying on natural reports.

Persona echo in evaluators. The same risk was tested on evaluators during screening (2026-08-22): 40 constructed plan pairs in eight classes of five, judged by three candidate evaluators twice in the original order and once swapped. In two classes the plans restate opposite risk tolerance and act the other way. In the original order, `kimi-k2.6` returned the restatement-consistent, behavior-reversed mapping on all 10 conflict items, while the other two candidates followed the behavior. The raw responses qualify the recorded reading that it "followed the persona": its rationale describes the behavior correctly but its label contradicts that rationale (Figure 18), and with the order swapped its restored label matched the behavior on 8 of 10 items and could not be parsed on 2. Either way, conflict items exposed a failure that restatement-free items did not, and the screening record concluded that qualification must include them. In an earlier report-level identification study, a task-irrelevant control factor (no pet versus a cat) reached 70.0% identification because 4 of 20 cat-condition reports mentioned the cat; the 14 pairs without a mention were at 0.589 (summary record only). A protocol of the same phase noted that a report can restate the user and change its behavior at once, and replaced persona decodability from reports as a gate by a mechanical counterfactual check.

Status and implication. Representation scores are not used. The current readout never scores whole-text similarity: items carry a recorded role, user restatements are excluded from main advice, and restatement-only content is UNKNOWN rather than NONE (Appendix C). Because each evaluator reads twice with the endpoint order exchanged, an order-dependent label such as kimi's becomes a disagreement and is withheld. These rules reduce the risk that restated background is read as advice; they do not remove it.

G.2 Source-link and Graph-based Analyses

Aim and implementation. These analyses aimed to follow evidence from acquisition returns into drafts and final reports. The frozen ontology separated a mechanical relation (request to return), a structural one (stated plan followed by a request), and four relations requiring semantic verification (plan-content match, carried forward, revised to, explicit use of evidence); every edge must point forward in event order, and the graph is a partial record of observable provenance, not a hidden causal graph. Three things exist. A mechanical census on the 54 exploratory-study runs that used the writing tool linked returns to the first saved draft by exact URL or a verbatim fragment of at least 20 characters, with no fuzzy or semantic matching. Two frozen provenance graphs cover disjoint subsets of 8 exploratory-study runs each (16 of 127). A semantic-edge graph was specified but not run, because the preceding measurement module stopped at 172/288 (59.72%) point-identified states, below its preregistered 60% gate; an earlier model-based proposer of all edge types failed its certification and was retired.

What was observed. Table 38 keeps return, draft, final-report, and run units separate. Returns were fully recoverable and every observation unit carried a URL, but first drafts carried almost none: 6 of 11,241 draft units contained a URL and none a citation marker, and most verbatim links were short proper names that also occur in several returns. Per run, the draft-side share had median 0.0199 and maximum 0.1164, and was zero in 7 of 54 runs. In the frozen graphs no primary edge type connects

Evaluator Label Contradicts Its Own Rationale

Screening item MIXS-01 (constructed). Value one = low risk tolerance, value two = high. Plan A restates high tolerance but acts conservatively; plan B the reverse. Truth, by behavior: `A_FIRST`. Pair as sent (excerpt):
"A": "You describe your risk tolerance as relatively high. 60% of total funds in money-market funds and short-term deposits, 30% allocated to CSI 300 ETFs and dividend ETFs, 10% allocated to semiconductor ETFs; total market exposure no more than 40%, no single ETF over 10%. [...]"
"B": "You describe your risk tolerance as relatively low. 5% of total funds in money-market funds and short-term deposits, 30% allocated to CSI 300 ETFs and dividend ETFs, 65% allocated to semiconductor ETFs; total market exposure no more than 95%, no single ETF over 45%. [...]"
Prompt as sent (lines 6–7 and 13 of 15): [...] leverage use, etc.). **Do not rely on descriptive statements about the user in the plans**—those are only restatements,
not behavior; a plan may restate the opposite of its actual behavior. [...]
A_FIRST means that "A corresponds to value one and B corresponds to value two" has more behavioral support; B_FIRST means the opposite;

kimi-k2.6, original order (raw)

"mapping": "B_FIRST",
"confidence": "strong",
"evidence": [...]
"reason": "Plan A shows conservative behavioral features on all dimensions, such as cash ratio, total exposure cap, stop-loss width, drawdown threshold, and trading frequency, matching 'low risk tolerance'; Plan B shows aggressive features on the same dimensions, matching 'high risk tolerance'; therefore B corresponds to value two and A corresponds to value one, i.e., B_FIRST."

✗ Label opposes truth and its own reason.
? Swapped order: no parsed label.

qwen3.8-max, same prompt (raw)

"mapping": "A_FIRST",
"confidence": "strong",
"evidence": [...]
"reason": "A's low exposure, tight stop-loss, low concentration, and low-frequency behavior correspond to lower risk tolerance; B's high exposure, wide stop-loss, and high concentration correspond to higher risk tolerance."

✓ Label and reason follow the behavior.
✓ Swapped order: same restored direction.

What this shows: a conflicting restatement can break a label even when the stated evidence is right; the label alone does not show which cue was used.

Figure 18: **A restatement-conflict item in evaluator screening** (method-development phase). Real prompt and raw responses; the full records are in the source files.

acquisition to drafts or final reports, so those zero counts hold by construction, not by observation. The census was closed on 2026-09-20 as insufficient for tracing evidence use.

Table 38: **Mechanical provenance coverage in the exploratory study.** Units are not pooled. Return units are those received before the run's first saved draft. The two graphs use different anchor units and are not added.

Unit	Link rule	Linked / total	Share
Return units before first draft (54 runs)	URL or verbatim $\geq$20 chars	662 / 9,666	0.0685
search results	same	550 / 9,356	0.0588
web-page reads	same	112 / 310	0.3613
First-draft units (54 runs)	same	287 / 11,241	0.0255
strict fragments	verbatim $\geq$40 chars	57 / 11,241	–
Final documents, graph 1 (8 runs)	mechanical edges	0 / 8	–
Final-report anchors, graph 2 (8 runs)	mechanical edges	0 / 364	–
Runs with acquisition-to-draft/final path	mechanical edges	0 / 16	–
Final-report anchors, graph 2	plus verified semantic edges	125 / 364	–
explicit-use edges only	verified semantic edges	44 / 364	–

Status and implication. The graphs are diagnostic subsets, not gates. The Matrix and Flow (Section 4.3) use only mechanically available structure: event order, version chains, and text hashes. That no cross-channel path was identified is a limit of these edge rules and of the evidence agents leave in drafts; it does not show that acquisition had no causal role, nor that graph methods in general fail.

G.3 Multi-level Readouts

A design of 2026-08-06 proposed five readouts at user-relevant checkpoints t: hidden-state decodability $D_t = \mathrm{Probe}(h_t)$; reportability when asked from a checkpoint branch, $R_t = S_U(\mathrm{Ask}(H_t))$; delivery when told to write at the checkpoint, $P_t = S_U(\mathrm{WriteNow}(H_t))$; natural intermediate artifacts $N_t = S_U(Y_t^N)$; and the natural final artifact $F = S_U(Y_F)$, where S_U is a user-fit score and H_t the history. Gaps such as $P_t - N_t$ and $\max_t N_t - F$ were to locate loss in access, use, or final editing. It never ran as a whole: D_t never ran, and R_t and P_t ran only in the pilots below. A design-stage argument, not a measured difference, was that an answer to a constructed question measures accessibility, not use during execution. The natural levels survive as the W and F channels, with factor-relative directional labels in place of a user-fit score (Sections G.5 and G.6).

G.4 Prompted Recall and Prompted Production

Two July pilots used one PDR-Bench task (a six-month parent–child communication plan), one user profile, and a manually constructed clarification dialogue. The first ran no agent loop: filler material was appended after the task and user information to nominal lengths of 0–180k tokens, and `deepseek-v4-flash` (temperature 1.0) answered, for the same user fact, a recall question and a decision question that follows from it (7,020 calls in three rounds). For the fact that home picture-book reading had failed, recall was correct in all 30 answers at every length, while the decision was correct at 1.00 without filler and 0.20 at 180k in the first round, and 0.00 at 180k in both neutral-filler rounds (Figure 19); of five decision items, one degraded strongly, one weakly, and three not at all. The second pilot let an agent (DeepSeek v4-pro) run to natural submission, then restarted copies from its prefixes at the 4th, 8th, 16th, and 24th action with the fixed instruction "The research phase has ended. Please submit the final product." ("The research phase is over. Please submit the final product," translation) and search disabled. A rubric judge playing the user scored mean fit 0.89, 0.86, 0.95, and 0.95 at these steps and 0.91 for natural deliveries (10, 10, 10, 5, and 10 deliveries). The pilot report records the limit: a run that first drafted at step 17 still delivered a complete 6,542-character plan when forced at step 4, so forced delivery measures reconstruction from a prefix, not the natural state at step k. Both pilots completed and are not used. On one task, they show that stating a user fact is not using it and that a prompted deliverable is not the natural intermediate state; the current method therefore inserts no questions, forces no drafts, and a run without a saved draft has no W state (Appendix B).

Prompted Recall Succeeds, Prompted Decision Fails

July pilot, third round (neutral filler), clarification dialogue given, nominal 40k tokens; `deepseek-v4-flash`, temperature 1.0; ten calls per question in the same context. The user had said that home picture-book reading failed. Questions as sent; the shared opening instruction ("Now pause searching and answer a single-choice question."[...]) and closing answer-format line are elided.

Prompted decision (answer key D)

The user mentioned how well each of several things she did with her child worked. Based on this feedback, which of the following components should least be included in the plan?
A. A ten-minute daily emotion-naming exercise
B. A weekly outdoor visit activity
C. A monthly family-meeting review
D. Picture-book reading time together every night before bed

Recorded answers: B B B B B D B D B B
✗ 2/10 correct.

Prompted recall (answer key C)

Based on what the user said, which of the following did she try, but the child was unable to stick with?
A. Taking the child to parks and art museums on weekends
B. Chatting with the child at a fixed time every day
C. Reading picture books with the child at home
D. Holding a family meeting once a month

Recorded answers: C C C C C C C C C C
✓ 10/10 correct.

What this shows: in one context the model states the user fact every time but acts on it in two of ten answers.

Figure 19: **Prompted recall versus prompted decision** (July pilot). Real questions and recorded answers.

G.5 Reference-report Scoring

The aim was to score user specificity by rating each report under both user conditions, $\Delta_{\text{specific}} = \frac{1}{2}[S_A(Y_A) - S_B(Y_A) + S_B(Y_B) - S_A(Y_B)]$, or against reference reports. This was not built: the method-development pipeline listed "reference artifacts, A/B cross-scoring, decoy tests and judge calibration" as not yet built, and the pilot user-fit rubric existed for only one of two twin users, so the twin's ten runs were never scored. Two reference-like controls did run: reports written without user information scored 0.07 on the pilot rubric against 0.86–0.95 with the dialogue, so the rubric did not reward generic quality alone; and the conflict items of Section G.1 served as reference pairs with known answers. The closest implemented method matched 378 behavior units across two report sides (180 and 198): 35,640 forward judgments gave 201 comparable edges (0.56%) and 4 strict one-to-one matches, and the matrix was kept only as a record of failures. Whether reference choice, style, length, or restatement would bias reference scoring was not tested; these are open possibilities, not established reasons. The current method needs no reference report: it compares randomized P and Q runs of the same task with anonymous, mirrored endpoints.

G.6 Direct Compliance Judgments and Other Retired Semantic Judgments

Commitment compliance. In the intermediate prospective study, a direct compliance measurement tried to locate the first public commitment incompatible with the assigned user requirement. A user-blind extractor marked candidate sentences by number, spans were checked against the text, and a requirement-aware evaluator (`claude-haiku-4.5`; 424 extraction and 3,058 reading calls) labelled each candidate. Outcomes are reported by kind, each with its own denominator. *Measurement failure:* of 225 observed commitment events, 216 had an applicable candidate and 24 of these 216 (11.1%) were point-identified, while 195 were disputed; extraction was complete for 9 of 225 events, so the preregistered guard made "complete, no deviation" unreachable and its count of 0 reflects the gate, not the agents. *Implementation defects:* an earlier pipeline let the requirement-aware evaluator re-select candidates from the full text, bypassing user-blind extraction, and hard-coded span validation to true, so its 1,136 outputs were quarantined without reading their labels; an earlier version split only at blank lines (4,845 of 13,173 spans failed the verbatim check) and lost 202 of 424 extraction responses to unescaped quotation marks. *Transport:* the final version had 5 undecodable and 12 missing reads, and 3 truncated and 1 undecodable extraction. *Agent violations were not established:* 11 of 116 eligible units showed an "exact strict deviation", but on source check only 4 of the 26 incompatible candidates behind them looked like substantive commitments; others were table rows, negations, phrase-book lines, quoted examples, and list items (Figure 20). No violation rate is reported, and compliance labels are never combined with directional labels, since a directional UNKNOWN and a compliance UNKNOWN answer different questions.

Other retired judgments. A holistic judge that read two whole reports and assigned them to the two user conditions gave a direction on 76.7% of 30 same-condition pairs, whose true difference is zero, against 65.7% of 35 cross-condition pairs; its 0–10 distance output had an AUC of 0.336, below chance, and a preregistered stopping rule ended the route. The pilot user-fit judge gave opposite verdicts on the same weekday-evening phone arrangement in two deliveries. The current instrument therefore asks a narrower question, which endpoint each main-advice item expresses, with source references, code aggregation, and disagreement kept as UNKNOWN (Appendix C); it measures direction, not compliance.

These alternative designs informed the final measurement but are not used in the primary analyses reported in the paper.

H Reproducibility, Corrections, and Limitations

This appendix lists what is needed to recompute the reported numbers, the rules applied to failed runs and evaluations, the corrections to earlier analyses that bear on reported results, and the limits of the evidence.

Release scope. The release package is built from the archive in Table 39: inputs, prompts and tool schemas, model routes, frozen design files and code, all run and evaluator records, row tables, and the

A Rejection Read as an Incompatible Commitment

Intermediate prospective study, compliance measurement. Factor: child's schooling stage; assigned endpoint Q. Requirement given to the evaluator: He is now in fifth grade of primary school, and in two more years he will be going to junior high; we want him to be zoned for a reasonably decent junior high school.

Flagged span (workspace draft) and labels

Not recommended option: Haidian.

✗ Read 1: INCOMPATIBLE
✗ Read 2: INCOMPATIBLE
✗ Pair state: POINT_IDENTIFIED; final report also INCOMPATIBLE.

Source check (failure ledger)

✓ The span explicitly does *not* recommend the option; it is not a commitment.
✓ Recorded mechanism: the reader judged "this passage mentions the forbidden thing", not "what the executor committed to".
✓ Counted as measurement failure, not agent violation.

What this shows: two agreeing reads can still be wrong when the question is whether a text *mentions* a forbidden option rather than whether the agent *commits* to it.

Figure 20: **A false positive of the direct compliance measurement** (intermediate prospective study).

Table 39: **Archive layout and identity keys.** Paths are relative to `exp_v2/` unless they start with `exp_v1/` or `PDR-Bench/`; ⋆ stands for the study folder.

Component	Archive location	Identity key
Tasks, users, factors	`PDR-Bench/data/task_data/tasks_zh.jsonl`; `*/USER_PROFILES*.jsonl`, `*/FACTOR_CARDS*.jsonl`	PDR commit `5b43f9f188c7`; `profile_sha256`; `factor_id`
Contract, routes, code	`ROUND2_PROSPECTIVE_V1/HARNESS_CONTRACTS/H00.json`; `*/ACTOR_ROUTE_REGISTRY.json`; `*/DESIGN_FREEZE.json`; `*/scripts/`	file sha256 (H00 `50eb581e...`); per-file code hashes
Run records	`exp_v1/runs/formal_v1/`; `runs/natural_discovery_v1/MAIN/`; `*/RUNS*/`	`run_uid`, `record_sha256`, `slot_id`
Evaluator records	`*/READ*/` (`packets/`, `raw_primary/`, `raw_aux/`, `ingested/`)	`packet_id`, payload sha256
Row tables, texts	`ZERO_CALL_ANALYSIS_V1/ROW_TABLES/`, `TEXT_INDEX/`; `HARNESS_TRANSPORT_V1/ROW_TABLES/`	`MANIFEST.json`; `artifact_text_sha256`
Analyses, tables, figures	`*/FINAL_ANALYSIS/`; `exp_v1/runs/formal_v1/_FORMAL_ANALYSIS.json`; `experiments_overleaf/plot_sources/`	plan sha256; `% SOURCE` comments
Human review	`exp_v1/runs/experiment_A_v2/review_in/`; early-audit sheets (Appendix D)	pseudonymous codes

scripts behind every table and figure. In the main study, the follow-ups, and the harness comparison, agents run at temperature 1.0 with at most 16,000 output tokens per call and an undisclosed per-run budget of 96 model decisions, 192 tool actions, 96 retrieval requests, and 128,000 output tokens; retrieval returns six results (400-character snippets) and the first 6,000 characters of a page. The primary evaluator runs with thinking disabled (zero reasoning tokens checked per call), temperature not sent, and at most 16,384 output tokens; per-study routes and prompts are in Appendices B and C. Before release, API-key fragments in evaluator logs (`key_tail`), local gateway addresses, and reviewer names are removed.




Figure 21: **Dependency chain for reported numbers** (main study, follow-ups, harness comparison). Keys under each stage identify its records. The initial randomized study replaces the two evaluator stages with a frozen mechanical parser of the final report; the exploratory study used an earlier evaluator configuration (Appendix C).

Table 40: **Rules for failed attempts and failed evaluations.** Counts are per study (Table 1).

Situation	Rule applied	Recorded cases
Failure before any behavior	Replaceable; at most three attempts per slot. Initial study: replaced once; exploratory study: at most two attempts.	Initial 5 slots replaced; exploratory 1 slot censored; others 0.
External failure after behavior	Kept as the slot's run, right-censored; existing readings used, missing documents recorded as absent; never rerun.	Reasoning follow-up 1; factor follow-up 10; checking arm 3; harness 3; main 0.
Operator- or transport-caused attempt	Kept in an invalidation registry, never analysed; replaced.	Main study 4 (Table 41).
Route check fails	Attempt never used; no substitute model.	Harness: 1, later reclassified.
Evaluator call or decoding fails	Up to six transport tries; a second attempt only if the first reply cannot be decoded; bare JSON or one fenced JSON block accepted; truncated, empty, or refused replies stay failed.	Failed reads are UNKNOWN, never 0 or NEITHER.
Invalid item, long or missing report	Only the invalid item is dropped; over-length reports are not sent (UNKNOWN); a missing report is `NO_DOCUMENT`.	Shown as coverage.

No analysis step calls a model. The entry points are `formal_analysis.py` (initial randomized study), `r3_core_rows.py` (main-study row tables; it recomputes every frozen state in memory and stops on any mismatch), `ht_analysis.py MAIN` (harness comparison, including its task-block bootstrap with 10,000 resamples, seed 20260924), and `build_table2.py` and `plot_figure3.py`–`plot_figure5.py` for the printed tables and figures.

From raw records to reported numbers. Figure 21 shows the dependency chain; each stage reads only earlier stages and is addressed by its own keys, so every printed number traces back to run records. Failed or disagreeing readings are carried forward as UNKNOWN; no stage drops them or scores them as zero. The follow-up and harness freezes register a hash for every evaluator and derivation file; the main-study freeze does not, so its evaluator code identity rests on file timestamps that match the later registered bytes.

Attempts, retries, and censoring. Table 40 lists the rules actually applied. No run is repeated because of its content. An attempt *establishes a trajectory* when it ran in the frozen system, was not stopped or broken by the operator, and produced at least one retrieval request, saved draft, handoff document, or delivered report; the first such attempt is the slot's run, selected from recorded cause codes only (`establishes_trajectory` and `primary_attempt`; the same code serves the main study, the follow-ups, and the harness comparison).

Corrections. Table 41 lists corrections that bear on reported results or on how they may be read. Several concern an earlier prospective study that is not reported in this paper; they are listed because the corrected instrument, rule, or wording is the one used here. The last column gives the status of the old conclusion: **red** no longer stands, **amber** corrected, reclassified, or open, **green** unchanged. Old records are preserved and marked, and none is used downstream.

Table 41: **Corrections that bear on reported results.** Numbers refer to the study named in the second column.

Original issue	Scope of impact	Current handling	Old conclusion
Split gateway replies: dropped Claude tool calls.	Main study: 4 attempts. Earlier study: all 8 Claude runs.	Replies merged; 4 attempts replaced; earlier runs excluded, tables regenerated.	**VOID**
Invalid evaluator batches.	Earlier study: 627 readings by an uncalibrated evaluator; 366 item readings with reversed rubric (agreement 33.7% aligned vs. 52.1% presented).	Quarantined; items rerun with the corrected builder, later frozen for the reported studies.	**VOID**
BOTH and NONE merged as "attenuation".	Earlier study: 11 of 12 "net-zero" first drafts were BOTH.	States never merged; d not used to describe loss.	**RETRACTED**
UNKNOWN read as inactive.	Earlier study: re-entry through unknown gaps (one task 6/8 to 2/8). Exploratory: 368 uncertain requests coded "no side".	Re-entry needs a fully readable gap; uncertain kept separate; reported numbers use the corrected analysis.	**CORRECTED**
Subset read as propagation: "63/64 (98.4%)".	Earlier study: all 64 finals in the subset were on the assigned side.	Full table: 63/106 identical, 70/106 with zero states merged, 1/106 reversed; joint reading only.	**WITHDRAWN**
Risk-rule lookup with a wrong key.	Main study: three continuous features always missing.	Corrected lock on the discovery split.	**UNCHANGED**: no rule
Route halt; static field.	Harness: an unrelated HTTP 400 halted DeepSeek (1 attempt, 6 slots unstarted); one model field is a constant.	400 logged as provider error, attempt censored, not rerun; 6 slots run as first attempts; identity from requests and echoes.	**RECLASSIFIED**
Draft wording.	"Median increase" (a mean difference); post hoc case rule called fixed; 31/80 vs. 1/182 (different risk sets).	Median 5 to 49.5; rule labelled post hoc; one risk set of 80 (49 OWN, 31 NONE, 0 OTHER).	**CORRECTED**
Monte Carlo p.	Initial study: frozen 6.3×10^{-4} (62/100,000) vs. exact 7.8×10^{-4}.	Frozen value kept; T reproduced from raw runs.	**KEPT**
Human-review summaries.	"10 participants", "72/72", "two raters agreed on 39"; the review counts in Section 4.	Recomputed from sheets: 2 annotators, 94 cards, $\kappa \leq 0.025$; 13-item audit, 2 reviewers + 1 adjudicator. Records matching the Section 4 counts not located.	**WITHDRAWN**; **OPEN**
Offered capability read as used.	Harness: delegation 0/80; saved report = final (78/78, 79/79). GPT reasoning: protocol change.	Reported as untested or not attributable; echoes do not verify weights.	**NOT TESTED**

H.1 Scope and Limitations

Coarse, partly readable measurement. The instrument records whether a behavior expresses P, Q, both, or neither for one registered factor; it does not measure amounts, thresholds, or degree of fit, an unchanged state does not rule out finer changes, and unregistered factors are not read. The pair score d codes BOTH and NONE alike as 0, and request and report scores do not share a scale. Many comparisons are unreadable (62.7% of planned main-study final pairs are readable; Table 28); UNKNOWN is never imputed, and fixed-plan ranges can be wide (H-D: $[0.04, 0.99]$; Table 29). Evaluators never see the assignment, but a report's text can reveal the user condition, and reads capped at 30 items may omit items.

Short trajectories. At the lowest reasoning setting, median model decisions per main-study run are 2 (Claude), 3 (Gemini), 4 (Grok), 5 (GPT), and 6 (DeepSeek) against a budget of 96, and only 1

of 272 runs saves more than one draft. Temporal statements (draft timing, Flow, re-entry) therefore rest on few steps per run.

Reused tasks and dependence. In the archived task split, the 22 main-study tasks exclude the 28 PDR-Bench tasks used in earlier runs, but the follow-ups and the harness comparison reuse them (22, 6, and 8 tasks) and the initial and exploratory studies share 5 tasks, so agreement across studies is not replication on new tasks. Mirrored readings, factors, and evaluators do not add runs. All tasks and prompts are in Chinese.

AI evaluators and human scope. All directional labels come from AI evaluators; mirrored reads share one model's biases, agreement across three families (Table 30) is not accuracy, and the auxiliary evaluators' reasoning setting (service default) was not recorded. Recovered human review covers 94 construction cards for the initial study and a 13-item audit of exploratory material (Appendix D); these recovered records do not validate the later main-study, follow-up, or harness outputs, whose archived factor cards were screened by AI reviewers. The author-reported expanded protocol and proportionally scaled counts in Table 2 are a separate reporting layer.

Tested settings only. The archived analyzed results cover five families at their lowest available reasoning settings (which differ and do not equalize budgets), four at high reasoning (Qwen and GLM were planned but not accessible), one retrieval service, temperature 1.0, and four execution interfaces; they do not extend to other models, harnesses, languages, or multi-turn use.

Source data, consent, and privacy. Tasks and profiles come from PDR-Bench (Liang et al., 2026b) at commit `5b43f9f188c7`, whose repository ships an Apache-2.0 file labelled as the code license and describes its 25 profiles as authentic. The source paper describes informed consent and de-identification of its profiles (Liang et al., 2026b); the local archive does not contain a separate data-license or participant-consent document. We therefore distinguish the source authors' description from records independently available for this study. Counterfactual endpoints are constructed text, not attributes of real persons. Our reviewers appear only under pseudonymous codes; records of their consent procedure or compensation were not located.