FIRST-ORDER IN-CONTEXT SHAPLEY: SCALABLE DATA AUDITING FOR LLM ALIGNMENT AND EVALUATION

Anonymous authors
Paper under double-blind review

ABSTRACT

Post-training alignment of Large Language Models (LLMs) is increasingly bottlenecked by data quality: massive preference and instruction-tuning corpora inevitably accumulate label noise, safety inversions, and inter-annotator contradictions that surface-level deduplication cannot detect and that are too costly to find by LLM-judging every record. While Data Shapley provides a principled framework for valuing individual records, exact computation requires intractable retraining, and fast embedding-space surrogates such as KNN-Shapley fail to separate high- from low-utility demonstrations ($\rho = 0.0003$ with generative utility). We introduce an inference-only valuation pipeline that computes the first-order term of an in-context cooperative game over semantic k-NN neighborhoods in $O(k)$ forward passes without parameter updates, achieving positive rank correlation with multi-shot Monte-Carlo in-context Shapley on 100% of targets (mean $\rho = 0.66$, close to the estimator's own split-half agreement of 0.73) with $19\times$ less compute. By projecting pairwise log-likelihood shifts onto a directed influence graph, we characterize each record through three signals: outgoing Exemplifying Advantage, incoming Exemplified Advantage, and a topological One-of-a-Kind Score that protects rare tail records. Pre-filtering with these signals restricts arbitration to 1%–5% of records before routing each candidate and a contrasting twin to an LLM arbitrator, achieving $4.5\times$ enrichment in arbitrator-confirmed annotation errors on graded response-generation data (HelpSteer2) and $2.2\times$ on pairwise preference data (Anthropic HH-RLHF), including contradictions that zero-shot likelihood and margin filters miss. During DPO training, confirmed preference contradictions oppose the realized update far more often than clean records from early on (56.7% vs. 37.0% in exact LoRA gradients) and stay below chance in reward accuracy. Finally, auditing the HH-RLHF evaluation benchmark exposes label errors on which aligned models disagree with the benchmark 73%–83% of the time (87%–95% when three frontier arbitrator families unanimously agree), and retraining DPO from scratch after repairing or filtering the flagged training records improves reward accuracy by $+0.5\%$–0.6% overall and $+3.1\%$–3.5% on the repaired test inversions, even without the LLM arbitration step.

1 INTRODUCTION

The advancement of Large Language Models (LLMs) relies heavily on the quality of the data used for training and evaluation. As models grow more capable, the primary bottleneck in alignment has shifted from model architecture to data quality assurance (Gunasekar et al., 2023; Zhou et al., 2023). However, massive preference datasets, instruction-tuning corpora, and human-labeled benchmarks inevitably accumulate noise, redundancy, and structural contradictions, making scalable data valuation methods essential.

Current approaches for dataset auditing mostly rely on direct semantic deduplication (Abbas et al., 2023; Lee et al., 2022), LLM-as-a-judge filtering (Chen et al., 2023), or human re-annotation (Zhou et al., 2023). Standard semantic deduplication effectively identifies textual duplicates, but fails to capture the functional utility of a data point in training or evaluation. Human re-annotation is computationally and financially unscalable and remains susceptible to annotator fatigue and

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

inconsistent standards. While deploying a larger LLM as a standalone judge offers scalability, it evaluates records in isolation using human-defined rubrics and often exhibits biases toward response length or formatting (Wang et al., 2024b; Zheng et al., 2023). A standalone judge cannot directly measure how a record influences the target model's predictive distribution.

One mathematically rigorous alternative is to use Data Shapley (Shapley, 1953; Ghorbani & Zou, 2019) to evaluate data contributions. While principled, exact Shapley computation has $O(2^N)$ complexity. Existing approximations either define utility strictly through embedding distances and discrete label matching (Jia et al., 2019; Zhang et al., 2025a), which do not extend to generative LLMs, rely on coarse grouping (Ye & Yoganarasimhan, 2025; Tamine et al., 2025), or need gradients from a training run (Wang et al., 2025), sacrificing individual record-level granularity.

To bridge this gap, we propose an influence-based data valuation pipeline designed to quantify data utility directly through the target LLM's own predictive distribution without model retraining. Our approach replaces retraining-based valuation with zero-shot and one-shot influence scoring via in-context probing, computing the first-order term of an *in-context* cooperative game over semantic neighborhoods. By measuring how the inclusion of a semantically neighboring record as an in-context example alters the conditional log-likelihood of a target response, our pipeline captures whether a data point supports or degrades the model's predictions across its local neighborhood.

The core contributions of this work are as follows:

- **Training-free in-context valuation.** An inference-only pipeline computes first-order in-context influence over a directed k-NN graph in $O(k)$ forward passes per record. It approximates multi-shot in-context Shapley rankings (positive correlation on every target; mean $\rho = 0.66$ vs. a split-half agreement of 0.73) at $1/19$ of the compute, and values the $160{,}800$-pair HH-RLHF corpus in 9.7 A100 GPU-hours, about $10\times$ less than projected LoRA TracIn (Pruthi et al., 2020).
- **Auditing training corpora and benchmarks.** Flagging both tails of Adv_e (and negative Adv_δ) restricts arbitration to 1%–5% of records and enriches arbitrator-confirmed errors $4.5\times$ on HelpSteer2 (Wang et al., 2024c) and $2.2\times$ on HH-RLHF (Bai et al., 2022) over random controls. On the HH-RLHF evaluation split, aligned models disagree with the human label on 73%–83% of confirmed errors (87%–95% when all three arbitrators agree).
- **Evidence of harm and downstream gains.** During DPO (Rafailov et al., 2023) training, confirmed contradictions oppose the model's update more often than clean records before their loss diverges (56.7% vs. 37.0% at step 100) and stay below chance in reward accuracy (41% vs. 71%). Retraining from scratch after repairing or pruning flagged records under a One-of-a-Kind (OOK) guardrail that protects rare prompts from deletion improves reward accuracy by $+0.5\%$–0.6% overall and $+3.1\%$–3.5% on the repaired test inversions, even without LLM arbitration.

2 Related work

Exact Data Shapley (Shapley, 1953; Ghorbani & Zou, 2019) requires $O(2^N)$ model retrainings. While KNN-Shapley (Jia et al., 2019) and localized k-NN variants (Zhang et al., 2025a; Mesana et al., 2024) achieve $O(N \log N)$ complexity by defining utility through embedding distances and discrete label matching, they cannot model autoregressive token generation or pairwise preference margins. Meanwhile, LLM-specific adaptations either sacrifice record-level granularity via coarse clustering (Cluster Shapley (Ye & Yoganarasimhan, 2025)) or dataset-level Model Arithmetic (Tamine et al., 2025), or focus on token- or step-level credit assignment (Xiao et al., 2025; Kazemnejad et al.) rather than corpus-scale data auditing. Gradient-based estimators such as TracIn (Pruthi et al., 2020) and In-Run Data Shapley (Wang et al., 2025) require backpropagating across training checkpoints (cost comparison in Appendix A.2). Closest to our probing primitive, Nuggets (Li et al., 2024) selects SFT instructions by measuring outgoing one-shot perplexity shifts onto a fixed global anchor set. However, as we show in §4.3 (and Appendix Table 9), outgoing influence alone fails to isolate pairwise preference inversions. For preference data specifically, Wang et al. (2024a) flag and flip noisy HH-RLHF pairs using an ensemble of trained reward models, while robust preference objectives (Ray Chowdhury et al., 2024; Liang et al., 2025) modify the training loss to tolerate



Figure 1: Overview of the data valuation pipeline. **Phase 1** constructs a directed k-NN graph weighted by one-shot log-likelihood shifts (ΔLL). **Phase 2** derives local advantage (Adv_e, Adv_δ) and uniqueness (OOK) metrics to route candidate contradictions to an arbitrator while protecting rare prompts.

corrupted labels. In contrast, we locate contradictions before training directly from the target model's in-context behavior.

3 Methodology

The core principle of the Shapley value is to measure the marginal contribution of a data point to overall model performance by comparing outcomes when the point is included versus excluded (averaged over all subsets of the other points) (Shapley, 1953; Ghorbani & Zou, 2019). To make record-level valuation tractable at the scale of modern LLMs, we leverage zero-shot and one-shot in-context probing. By evaluating how the presence of a neighboring record in the prompt alters the conditional log-likelihood of a target response, we measure the marginal predictive impact of a data point without parameter updates.

As illustrated in Figure 1, our data valuation pipeline has three components: constructing a weighted directed influence graph over local semantic neighborhoods (steps 1–4 in phase 1, §3.1), deriving node-level data valuation metrics (step 5 in phase 2, §3.2), and isolating structural label contradictions while protecting rare tail queries (steps 6–8 in phase 2, §3.3).

3.1 Directed In-Context Influence Graph

Given a dataset $D = \{(x_i, y_i)\}_{i=1}^N$, we first construct a directed graph $G = (\mathcal{V}, \mathcal{E})$ that captures local semantic neighborhoods. We extract the prompts x_i, strip boilerplate templates or static system instructions to prevent vector dilution, and embed the normalized prompts using a dense embedding model. For each target record $n_i \in \mathcal{V}$, we retrieve its k-nearest neighbors (k-NN) by cosine similarity and form a directed edge $e_{j\to i} \in \mathcal{E}$ from each retrieved neighbor n_j to n_i. Because a record n_j residing among the k-nearest neighbors of n_i does not imply the reverse, k-NN retrieval is asymmetric. Each node has a fixed incoming neighborhood $\mathcal{N}_{in}(n_i)$ of size k (the demonstrations used to probe n_i) and a variable-sized outgoing neighborhood $\mathcal{N}_{out}(n_i) = \{n_m \in \mathcal{V} \mid n_i \in \mathcal{N}_{in}(n_m)\}$ (the peers on which n_i acts as a demonstration).

To weight each directed edge $e_{j\to i}$, we measure how a neighbor $n_j = (x_j, y_j)$ as an in-context demonstration shifts the predictive log-likelihood of the target response y_i under the scoring LLM θ. For graded response-generation data (e.g., HelpSteer2 (Wang et al., 2024c)), y_i is the full response; for pairwise preference data (e.g., HH-RLHF (Bai et al., 2022)), x_i presents the conversation with both responses in random order and y_i is the index token of the human-preferred one. Comparing the zero-shot log-likelihood $LL_{\text{base}}(i) = \log P_\theta(y_i \mid x_i)$ against the one-shot log-likelihood $LL_{\text{probe}}(i,j) = \log P_\theta(y_i \mid x_j, y_j, x_i)$ (prompt templates in Appendix A.1), the edge weight $\Delta LL_{i,j}$ is defined as the marginal log-likelihood shift:

$$\Delta LL_{i,j} = LL_{\text{probe}}(i,j) - LL_{\text{base}}(i) = \log P_\theta(y_i \mid x_j, y_j, x_i) - \log P_\theta(y_i \mid x_i). \tag{1}$$

A positive $\Delta LL_{i,j}$ indicates that neighbor j constructively supports target i, whereas a strongly negative $\Delta LL_{i,j}$ signals a behavioral contradiction between the two records.

3.2 Data Valuation Metrics

Using the directed graph G, we derive three data valuation metrics for every node n_i:

- **Exemplified advantage (Adv_e, Passive Influence)**: Measures the locally normalized predictive influence n_i receives from its incoming neighbors. Values near zero indicate local consistency, whereas extreme positive or negative values flag records whose labels conflict with their semantic neighborhood.
- **Exemplifying advantage (Adv_δ, Active Influence)**: Derived from our localized in-context Shapley score, this metric measures the locally normalized predictive contribution n_i exerts on its outgoing neighbors. Positive values mark helpful demonstrations, whereas strongly negative values mark records that degrade predictions on their neighbors.
- **One-of-a-kind score (OOK, Topological Uniqueness)**: Measures the asymmetry between incoming and outgoing degree under non-reciprocal k-NN retrieval. Higher values indicate that few semantically close peers retrieve n_i as a neighbor, marking the record as a rare edge-case.

From the incoming and outgoing neighborhoods $\mathcal{N}_{in}(n_i)$ and $\mathcal{N}_{out}(n_i)$, we first calculate the raw *exemplified score* and *exemplifying score*.

The exemplified score, denoted as $e(n_i)$, represents the average predictive influence received by n_i when its incoming neighbors are used as one-shot examples:

$$e(n_i) = \frac{1}{|\mathcal{N}_{in}(n_i)|} \sum_{n_j \in \mathcal{N}_{in}(n_i)} \Delta LL_{i,j}. \tag{2}$$

Conversely, the exemplifying score, denoted as $\delta(n_i)$, represents the average predictive influence n_i exerts when used to predict its out-degree targets:

$$\delta(n_i) = \begin{cases} \frac{1}{|\mathcal{N}_{out}(n_i)|} \sum_{n_m \in \mathcal{N}_{out}(n_i)} \Delta LL_{m,i} & \text{if } |\mathcal{N}_{out}(n_i)| > 0, \\ \text{undefined} & \text{otherwise.} \end{cases} \tag{3}$$

Viewing in-context learning on target n_i as a cooperative game over $\mathcal{N}_{in}(n_i)$ with utility $v_i(S) = \log P_\theta(y_i \mid S, x_i)$, $\Delta LL_{i,j} = v_i(\{j\}) - v_i(\emptyset)$ is neighbor j's first-order (singleton) term, computed in $O(k)$ forward passes instead of $O(2^k)$ coalitions; §4.1 shows it largely preserves multi-shot Shapley rankings. When $|\mathcal{N}_{out}(n_i)| = 0$, node n_i is an isolated record and is naturally excluded from negative-influence filtering.

Because raw log-likelihood shifts vary in scale across topics, task formats, and response lengths, we normalize $e(n_i)$ and $\delta(n_i)$ as local Z-scores over the immediate neighborhood $\mathcal{S}_i = \mathcal{N}_{in}(n_i) \cup \{n_i\}$, defining the **exemplified advantage** (Adv_e) and **exemplifying advantage** (Adv_δ):

$$Adv_e(n_i) = \frac{e(n_i) - \mu_e(\mathcal{S}_i)}{\sigma_e(\mathcal{S}_i)}, \qquad Adv_\delta(n_i) = \frac{\delta(n_i) - \mu_\delta(\mathcal{S}_i)}{\sigma_\delta(\mathcal{S}_i)}, \tag{4}$$

where μ and σ denote the mean and standard deviation of the respective raw scores across $\mathcal{S}_i$.

The **one-of-a-kind score**, denoted as $\mathrm{OOK}(n_i)$, quantifies structural uniqueness:

$$\mathrm{OOK}(n_i) = 1.0 - \frac{|\mathcal{N}_{out}(n_i)|}{|\mathcal{N}_{in}(n_i)|}. \tag{5}$$

Scores approaching 1.0 mark n_i as an isolated edge-case, whereas strongly negative scores indicate records at the dense center of a semantic cluster. Curators can use $\mathrm{OOK}(n_i)$ during dataset pruning to protect rare queries from deletion, intended to preserve topological coverage and topic diversity.

3.3 Structural Contradiction Detection

We define a *structural contradiction* as an annotation failure where functionally similar contexts map to conflicting target behaviors. We isolate contradictions in two stages: **Stage 1 (candidate filtering)** uses our local advantage metrics (§3.2) to flag a small $\approx 2\sigma$ candidate pool of anomalous anchors, and **Stage 2 (twin arbitration)** pairs each flagged anchor n_i with a contrasting local *twin* so an expert or LLM arbitrator can judge the pair against a concrete reference rather than in isolation. Because datasets differ in whether they provide explicit quality ratings or only implicit preferences, we instantiate Stages 1 and 2 as follows:

Graded labels (e.g., HelpSteer2). When records carry explicit scalar ratings, the ratings themselves define the contrast. Because a top grade asserts that a record is an exemplary demonstration, Stage 1 scores the influence graph constructed over the top-graded subset and flags anchors that degrade predictions on their equally top-rated peers ($Adv_\delta(n_i) < \tau_{\text{adv}}$, with $\tau_{\text{adv}} = -2$). Stage 2 then searches each flagged anchor's k-NN prompt neighborhood across the full corpus for any low-scored record whose response is also semantically similar (cosine > 0.5), and routes each resulting high- vs. low-scored pair to the arbitrator to test whether both responses exhibit the same flaw despite opposite ratings.

Implicit labels (e.g., HH-RLHF). When every record is implicitly treated as a valid preference or demonstration, no contrasting rating exists, so the influence graph supplies both the filter and the twin. Stage 1 flags anchors in the two-sided $\approx 2\sigma$ tail of $|Adv_e(n_i) - \text{median}(Adv_e)|$, capturing both the *negative tail* ($Adv_e \ll 0$), where conditioning on consistent neighbors sharply reduces confidence in n_i's label, and the *positive tail* ($Adv_e \gg 0$), where n_i's label is highly implausible zero-shot and gains probability mainly from in-context cues. Stage 2 applies **worst-neighbor twin pairing**, matching each flagged anchor n_i with its single most-contradicting incoming neighbor $j^*(i) = \arg\min_{n_j \in \mathcal{N}_{in}(n_i)} \Delta LL_{i,j}$. The arbitrator then determines whether either record (or both) has an inverted preference label. When curating the training corpus for downstream alignment, directional inversions are either flipped ($y^+ \leftrightarrow y^-$) or dropped and mutually faulty pairs are dropped, while records with $\text{OOK}(n_i) > 0.9$ are exempt from deletion to preserve rare prompts.

4 Experiments

We evaluate our valuation pipeline across five empirical questions: (1) whether first-order in-context influence recovers multi-shot Shapley rankings more faithfully than embedding-space proxies (§4.1); (2) whether structural contradiction detection isolates inter-annotator rating inconsistencies under graded labels (§4.2); (3) whether it isolates corrupted preference pairs under implicit labels in RLHF training data, and how these records affect DPO optimization (§4.3); (4) whether standard evaluation benchmarks contain similar label errors that penalize well-aligned models (§4.4); and (5) whether repairing or pruning flagged training records improves downstream DPO alignment (§4.5).

Datasets, experimental setup, and compute efficiency. We evaluate on two benchmarks: (1) **HelpSteer2** (Wang et al., 2024c) (§4.1–§4.2), a supervised corpus of 20,324 training prompt–response records graded on a 0–4 helpfulness scale, and (2) **Anthropic HH-RLHF** (Bai et al., 2022) (§4.3–§4.5), a pairwise preference dataset of helpfulness and harmlessness conversations with 160,800 training pairs and 8,552 held-out test pairs. All experiments run on 4× NVIDIA A100 (80GB) GPUs using Qwen3-Embedding-4B (Zhang et al., 2025b) with HNSWlib (Malkov & Yashunin, 2020) ($k = 15$) for retrieval, Qwen3.5-9B (Qwen Team, 2026) for log-likelihood scoring and LoRA (Hu et al., 2021) DPO (Rafailov et al., 2023) training, and Gemini 3.1 Pro (temperature 0) (Gemini Team et al., 2023) for pairwise arbitration. At $1 + k = 16$ prefix-cached forward passes per record, scoring all 160,800 HH-RLHF records takes 9.69 A100 GPU-hours, versus 100.5 GPU-hours for 3-checkpoint LoRA TracIn (Pruthi et al., 2020) (10.4×) and ≥ 2,600 GPU-hours for retraining Data Shapley (268×, Appendix A.2, Table 3). All p-values are two-sided. We compare proportions with Fisher's exact test, demonstration utilities in Table 1 with Welch's t-test, other continuous quantities with the Mann–Whitney U test, and seed-level results with an exact permutation test.

4.1 Validating First-Order In-Context Influence Against Multi-Shot Shapley

Recall from §3.2 that $\delta(n_i)$ measures a record's influence via one-shot probing, avoiding the $O(2^k)$ cost of evaluating multi-shot demonstration subsets $S \subseteq \mathcal{N}_{in}(s)$ under the full in-context Shapley value ϕ_{LLM} (with coalition utility $\log P_\theta(y_s \mid S, x_s)$). We test two hypotheses on HelpSteer2: (1) whether our first-order score preserves the multi-shot in-context Shapley ranking ϕ_{LLM}, and (2) whether exact KNN-Shapley (Jia et al., 2019) on an embedding-space classification proxy can substitute for evaluating the generative LLM directly.

Because evaluating all 2^{15} subsets per target is intractable, we estimate the multi-shot Shapley ranking ϕ_{LLM} (Ghorbani & Zou, 2019) across 200 targets ($k = 15$) using 20 random permutations per target (301 forward passes vs. 16 for our one-shot score). On every one of the 200 targets, our first-order

Table 1: Multi-shot in-context Shapley ϕ_{LLM} (in nats; mean, with median in parentheses) for HelpSteer2 demonstrations ($N = 1{,}960$) partitioned into the Bottom 5%, Middle 90%, and Top 5% by each selection method. Demonstrations selected by KNN-Shapley show no significant difference between the Top and Bottom 5% ($p = 0.28$), whereas those selected by Adv_δ differ by $+23.29$ nats ($p = 0.005$; medians also separate, -0.56 vs. $+4.84$).

Selection Method	**Bottom 5%**	**Middle 90%**	**Top 5%**	**Top − Bottom (Welch p)**
KNN-Shapley	-1.40 ($+1.13$)	$+2.14$ ($+1.27$)	$+2.26$ ($+0.80$)	$+3.66$ nats ($p = 0.28$)
Adv_δ (ours)	$\mathbf{-10.24}$ (-0.56)	$+2.15$ ($+1.11$)	$\mathbf{+13.05}$ ($+4.84$)	$\mathbf{+23.29}$ nats ($p = 0.005$)

score achieves a positive Spearman correlation with ϕ_{LLM} (median $\rho = 0.69$, mean $\rho = 0.66$, close to the estimator's own 0.73 split-half agreement between two independent 10-permutation halves) at $1/19$ the compute. To evaluate KNN-Shapley, we compute its exact values across the full HelpSteer2 corpus using the binary classification target helpfulness ≥ 3 across all ratings 0–4. Because this proxy rewards any demonstration whose neighbors share the same class label, it assigns high values even to corrupt helpfulness-4 responses: its values are uncorrelated with ϕ_{LLM} across the $1{,}960$ demonstrations ($\rho = 0.0003, p = 0.99$) and fail to distinguish the Top and Bottom 5% in Table 1 ($p = 0.28$), whereas Adv_δ cleanly separates them ($+23.29$ nats, $p = 0.005$).

4.2 Auditing Graded Ratings in HelpSteer2

We next apply structural contradiction detection for graded labels (§3.3) to the $8{,}433$ HelpSteer2 responses rated $4/4$. In Stage 1, filtering by $Adv_\delta < -2$ flags 344 of the $8{,}433$ records as anomalous anchors. In Stage 2, we search each flagged anchor's full-corpus k-NN neighborhood for records scored below 2 whose responses have cosine > 0.5. Because only a subset of the 344 anchors have such a low-scored, similar-response neighbor, this produces 70 candidate pairs, a 97.3% reduction compared to the $2{,}610$ pairs obtained by applying Stage 2 to all $8{,}433$ records without Stage 1. Automated LLM arbitration (prompt template in Appendix A.5.1) confirms 18 of these 70 pairs as true contradictions (25.7% precision), uncovering hallucinated citations, wrong calendar dates, and ignored formatting constraints (error taxonomy in Appendix Table 7; qualitative example in Appendix A.6).

To confirm that Stage-1 filtering by Adv_δ drives this 25.7% precision rather than arbitrator leniency, we randomly sample a size-matched control of 70 candidate pairs from the unflagged Stage-2 pool ($Adv_\delta \geq -2$) and evaluate them with the same LLM arbitrator. This random control yields only 5.7% confirmed contradictions ($4/70$), corresponding to a $4.5\times$ enrichment for our method (Fisher's exact $p = 0.0020$). One plausible explanation is that raters favor fluent, well-formatted hallucinations, so corrupt responses still receive perfect $4/4$ scores in isolation, whereas cross-prompt peer influence (Adv_δ) exposes that conditioning on them degrades predictions on neighboring targets.

4.3 Auditing Preferences in the HH-RLHF Training Split

We next audit the HH-RLHF training split ($k = 15$). Following §3.3, we flag the two-sided $\approx 2\sigma$ tail of $|Adv_e(n_i) - \mathrm{median}(Adv_e)|$, i.e., the top $8{,}500$ anchors (5.3% of the corpus), and ask an LLM arbitrator to compare each anchor with its most contradicting neighbor (prompt in Appendix A.5.2). The arbitrator confirms a contradiction in 41% of these pairs, surfacing $3{,}873$ flawed records. They range from unhelpful evasions to safety inversions in which raters preferred a harmful instruction over a safe refusal (taxonomy in Appendix Table 8). The score also locates the faulty record within the pair: we call a confirmed contradiction an *anchor-fault* when the arbitrator blames the flagged anchor n_i (alone or together with its neighbor), which holds for 78.2% of confirmed pairs ($2{,}750/3{,}516$). Across all $8{,}485$ evaluated anchors, this yields a 32.4% anchor-fault rate, more than twice the rate for random anchors (14.9% of $1{,}490$ random anchors, a $2.2\times$ enrichment, $p = 7.6 \times 10^{-47}$).

Figure 2 shows why both tails of $Adv_e(n_i)$ matter. In the left tail (***Regime I***), the human choice looks unremarkable on its own, and its zero-shot log-likelihood LL_{base} is close to the dataset average. Its likelihood collapses only once the model has seen incoming neighbors that follow a consistent preference convention (Figure 2A). Zero-shot likelihood and margin filters, which score each record in isolation before training, miss over 99% of these records (Appendix Table 3); only neighboring



Figure 2: **Zero-shot vs. one-shot log-likelihood breakdown (A) and confirmed contradiction U-curve (B) across $Adv_e(n_i)$. Left (A):** Zero-shot $LL_{\text{base}}(i)$ and $\overline{LL}_{\text{probe}}(i)$, the mean one-shot $LL_{\text{probe}}(i, j)$ over incoming neighbors $n_j \in \mathcal{N}_{in}(n_i)$, in 11 bins of Adv_e on HH-RLHF ($N = 160{,}800$). In *Regime I* ($Adv_e < -0.6$), LL_{base} stays near -1.8 while $\overline{LL}_{\text{probe}}$ drops to -3.27; in *Regime II* ($Adv_e > 0.6$), the human choice is a zero-shot outlier ($LL_{\text{base}} = -3.67$). **Right (B):** Anchor-fault rate over 18,529 arbitrated anchors (pooled audits), each paired with its most contradicting neighbor (grey: pair contradiction rate): 11.2% at the minimum near $Adv_e \approx 0$, rising to 34.7% and 35.5% in the left and right tails, vs. 15.8% for 1,837 random anchors.



Figure 3: **DPO loss (A) and reward accuracy (B) by cohort across 14 checkpoints on Qwen3.5-9B.** All cohorts start within 0.03 nats at step 100. Clean records, held-out test records (the trainer's held-out evaluation pairs), preferred twins and cleared records then improve steadily, whereas confirmed contradictions diverge upward in loss (0.955 vs. 0.543 for clean at step 1,200, or 0.953 on all 3,869 confirmed records; Mann–Whitney $p = 8.2 \times 10^{-195}$) and stay below chance in reward accuracy (41%). The metric-flagged cohort, taken before arbitration, lies in between.

pairs expose them. In the right tail (*Regime II*, $Adv_e \gg 0$), Adv_e is large and positive not because one-shot confidence $\overline{LL}_{\text{probe}}$ is high, but because the model already assigns the recorded label an abnormally low zero-shot likelihood ($LL_{\text{base}} = -3.67$), which one-shot conditioning only partially raises. Together, the two regimes produce a U-shaped anchor-fault rate that is lowest near $Adv_e \approx 0$ and rises toward both ends (Figure 2B). A controlled six-slice audit confirms the pattern (Appendix Table 9). Both tails of Adv_e are at fault 1.6–1.9× as often as random anchors (2.7–3.0× as often as never-flagged ones), whereas the outgoing score Adv_δ, the local counterpart of one-shot scoring in Nuggets (Li et al., 2024), does no better than random in either its lowest or highest tail (19.2% and 18.0% vs. 19.7% random, $p \geq 0.63$; and 16.9% across the top 8,500 anchors by $|Adv_\delta - \text{median}(Adv_\delta)|$).

In-sample DPO unlearnability. If the confirmed records are genuine contradictions, a model trained on them should fail to fit them even while it fits the rest of the data. We test this by tracking a full-epoch Qwen3.5-9B DPO run over 14 checkpoints (Figure 3; Appendix Table 10). We compare

five training-set cohorts (cohort accounting and size-equalized $n = 2{,}835$ subsamples in Appendix B, Table 10): the pre-arbitration *metric-flagged* anchors ($n = 8{,}490$ valid DPO pairs of the $8{,}500$); the three cohorts into which arbitration partitions those pairs—*confirmed* records ($n = 3{,}869$ of $3{,}873$), the flawed member(s) of each confirmed pair, their *preferred twins* ($n = 2{,}891$), the better member of each directional pair, and *cleared* anchors ($n = 4{,}959$), whose pair is judged consistent; and a *clean* control ($n = 2{,}835$). Early in training the cohorts' losses are nearly identical: at step 100 they lie within 0.03 nats, and confirmed and cleared records are statistically indistinguishable ($p = 0.10$). By step 200 these two have separated ($p = 3.5 \times 10^{-54}$), and the ordering preferred twin $<$ clean $<$ cleared $<$ metric-flagged $<$ confirmed then holds at every later checkpoint. Clean records, preferred twins and cleared records keep improving, whereas confirmed contradictions get worse: their loss climbs well above $\ln 2$, and their reward accuracy stays below chance throughout training. Splitting the DPO reward into its chosen and rejected terms (Appendix Figure 5) explains this failure: compared with clean records, the model lowers the likelihood of the corrupted chosen response more and that of the better rejected response far less. In effect, it learns the opposite of the recorded label. The metric-flagged cohort lands in between because it mixes both kinds of records, which arbitration then separates.

LoRA gradient conflict. Per-record LoRA gradients g_i show that confirmed contradictions are not merely hard examples learned slowly (Appendix Table 12). At step 100, when all cohorts have nearly identical loss, the update $\Delta\theta = \theta_{600} - \theta_{100}$ already opposes ($g_i \cdot \Delta\theta > 0$) 56.7% of confirmed contradictions versus 37.0% of clean records ($p = 1.6 \times 10^{-57}$), even after matching on loss and gradient norm. Cleared records from the same $|Adv_e - \mathrm{median}(Adv_e)|$ ranking—with the same step-100 loss and norm—conflict at only 44.9% ($p = 3.2 \times 10^{-28}$), while the metric-only Adv_e tails conflict at 49.3%–51.7% ($p \leq 7.8 \times 10^{-5}$ vs. clean). Conflict thus precedes the loss gap; at step 600, confirmed contradictions still oppose $\theta_{1200} - \theta_{600}$ (50.1% vs. 33.7%) with $76\times$ higher pairwise gradient alignment.

4.4 Auditing the HH-RLHF Evaluation Split

Label errors in an evaluation split cause a different harm: a model that gives the better answer is scored as wrong. We therefore audit the HH-RLHF test split with the same procedure, flagging the $\approx 2\sigma$ tail of $|Adv_e - \mathrm{median}(Adv_e)|$ (450 of $8{,}552$ pairs; prompt in Appendix A.5; qualitative example in Appendix A.7). Gemini 3.1 Pro confirms 191 test errors, and flagged anchors are at fault about 1.7 times as often as random ones (31.5% vs. 18.4%, $p = 7.2 \times 10^{-6}$).

To check that these errors are not an artifact of one arbitrator, we re-arbitrate every pair with Llama 4 Maverick (Meta AI, 2025) and Claude Opus 4.8 (Anthropic, 2026). Any two providers agree on 60%–68% of pairs, and all three agree on 48% of pairs. The providers differ mainly in how strict they are before calling a label wrong (Appendix B). We therefore also report errors confirmed by at least two ($n = 118$) or all three ($n = 38$) providers.

Aligned models side with the arbitrators rather than the benchmark. On the full test split, Qwen3.5-9B (DPO), Qwen3.5-27B, and Gemma3-12B (Gemma Team, 2025) disagree with the human label (when asked which response is better) about 37% of the time. On confirmed errors they disagree 73%–83% of the time, a similar rate holds when each provider's verdicts are used alone, and disagreement rises to 87%–95% when all three arbitrators agree (Appendix Table 11). On these items the benchmark penalizes models for the preferred answer. Ablations over the scoring backbone, k, and tail size are in Appendices A.3–A.4.

4.5 Downstream Alignment Retraining on Curated HH-RLHF

Finally, we test whether cleaning the training data yields a better-aligned model. We train Qwen3.5-9B with DPO (Rafailov et al., 2023) from scratch for $1{,}254$ steps (one epoch of the uncleaned set) on HH-RLHF under four versions of the training set. *Uncleaned* uses all $160{,}490$ valid pairs. *Sanitized* deletes the arbitrator-confirmed errors. *Repaired* instead flips the preference on confirmed inversions and deletes only pairs in which both responses are faulty. *Metric-only* makes no arbitrator calls and deletes every pair in the $\approx 2\sigma$ tail of $|Adv_e - \mathrm{median}(Adv_e)|$. Pruning on contradiction alone could delete rare but legitimate topics: a prompt with no close semantic peers has no neighborhood consensus to contradict, so its in-context shifts reflect topical mismatch rather than a wrong label.

Table 2: Reward accuracy of Qwen3.5-9B trained from scratch with DPO on each training-set arm, evaluated at step 1,200 on HH-RLHF test splits (8,535 valid DPO pairs). The *Sanitized* and *Repaired* test splits remove or repair the 191 confirmed test errors; the bottom two rows evaluate only the flipped inversions, i.e., confirmed errors where the arbitrator chooses one record over the other (142 of 191 single-arbitrator and 97 of 118 majority errors). *Gain* is the best arm (bold) minus Uncleaned. *Sanitized* used an earlier trainer build; a second seed and the five-seed continuation are in Appendix Tables 13 and 14.

Evaluation Split	n	**Uncleaned**	**Sanitized**	**Metric-only**	**Repaired**	**Gain**
Full Raw	8,535	68.45%	68.76%	68.79%	**68.96%**	**+0.51%**
Sanitized	8,344	69.19%	69.53%	69.67%	**69.76%**	**+0.57%**
Repaired	8,486	69.18%	69.57%	69.71%	**69.77%**	**+0.59%**
Inversions (Single Arbitrator)	142	69.01%	71.83%	**72.54%**	70.42%	**+3.52%**
Majority Inversions ($\geq 2/3$)	97	76.29%	75.26%	**79.38%**	77.32%	**+3.09%**

No arm therefore deletes a prompt with $\mathrm{OOK}(n_i) > 0.9$ (Eq. 5), a uniqueness guardrail that closely tracks embedding-space isolation ($\rho = +0.77$ with mean k-NN distance) and exempts the 1.5% most isolated prompts from deletion. This guardrail costs little: it exempts only 39 confirmed records, and fully isolated prompts are anchor-faults at about the corpus rate (1.8% vs. 1.7%; arm sizes and hyperparameters in Appendix B).

As shown in Table 2, curating the flagged training pairs lifts reward accuracy across all three full benchmark splits by up to +0.51%–0.59%, with 48 of *Repaired*'s 50 additional correct predictions coming from clean test prompts (Appendix Table 13). Gains are much larger on the corrected test inversions (+3.52% single-arbitrator; +3.09% majority). To test seed variance, we also resume from a shared step-1,000 checkpoint and continue training to step 1,254 across five seeds per arm (Appendix Table 14): every *Repaired* seed beats every *Uncleaned* seed on the inversions (+3.62%, $p = 0.008$) and widens the full-benchmark margin (+0.038 nats, $p = 0.016$). Without API calls, *Metric-only* recovers most of this gain (69.71% on Repaired; 72.54% on inversions), showing that Stage 1 alone is a strong zero-cost filter; however, it discards 8,344 pairs (including 4,969 consistent pairs cleared by Stage 2), whereas arbitration retains those valid pairs, flips 2,890 inversions into usable supervision (deleting only 974 mutually faulty pairs), and achieves the best full-split accuracy and lowest DPO loss.

5 Conclusion and Limitations

We introduced a training-free, graph-based data valuation method that scores each record by how its label's likelihood shifts when similar records are shown as in-context examples (Adv_e), and how it shifts theirs (Adv_δ). Flagging both tails of Adv_e (and negative Adv_δ on graded data) to pair each anchor with its most contradicting neighbor concentrates arbitrator-confirmed errors on HelpSteer2, HH-RLHF, and the HH-RLHF evaluation split. On the training split, it captures contradictions that zero-shot likelihood filters miss and identifies before training the records whose gradients oppose the DPO update. Cleaning the training set, even without an LLM arbitrator, improves the retrained model, most on the repaired evaluation-split inversions, while a topological guardrail keeps rare prompts from being deleted. Future work will explore using these continuous advantage metrics to construct lean, high-leverage training subsets that reduce alignment compute, to dynamically weight fine-tuning losses so gradient-conflicting records are soft-penalized without sacrificing diversity, and to synthesize challenging negative examples for DPO and reinforcement learning.

Limitations. The training-split audit uses a single LLM arbitrator without new human annotations; the evaluation-split audit uses three arbitrator families, though model–arbitrator agreement may partly reflect shared LLM priors (only the metric-only cohorts avoid arbitration). Full-benchmark gains are modest (+0.3%–0.6%) with one from-scratch run per arm. Finally, our scores rank records rather than acting as calibrated classifiers, and extending beyond English chat data to code and math remains open.

AI USE STATEMENT

In this work, we used generative and embedding AI models (Qwen3.5, Gemma3, Gemini 3.1 Pro, Llama 4 Maverick, Claude Opus 4.8, Qwen3-Embedding-4B, and BGE-M3) as experimental subjects and automated evaluators as documented in §4, and we used generative AI tools for coding assistance and manuscript polishing. We have not used generative AI tools to generate novel research hypotheses or fabricate experimental data. We have reviewed all AI-assisted work: all analysis and training code, experimental results, statistical tests, citations, and manuscript claims were manually verified for correctness by the authors. We take full responsibility for the final content of this work, including text, claims, and artifacts produced with the aid of generative AI.

REPRODUCIBILITY STATEMENT

All datasets (HelpSteer2 and Anthropic HH-RLHF) and open-weight embedding and scoring models (Qwen3-Embedding-4B, BGE-M3, Qwen3.5, and Gemma3) used in this study are publicly available. Complete algorithmic specifications, prompt templates for zero-shot and one-shot probing, and pairwise arbitration prompts are provided in §3 and Appendices A.1 and A.5. Hyperparameters, dataset split sizes, and hardware details for all DPO training and gradient analyses are documented in §4 and Appendix B. Pairwise arbitration used `gemini-3.1-pro-preview` at temperature 0, and cross-provider evaluation-split checks used `claude-opus-4-8` and `llama-4-maverick-17b-128e-instruct` with provider-default sampling and a 2,048-token output cap. Our DPO training configurations, dataset construction scripts, and Stage-1 metric-flagged record indices across all splits are included in the supplementary material (`.zip`); following the ICLR Author Guidelines for keeping code private prior to acceptance, the core data valuation pipeline source code will be provided via an anonymous repository link in a restricted comment directed to the reviewers and Area Chairs as soon as the discussion forum opens, and released publicly upon acceptance.

REFERENCES

Amro Abbas, Kushal Tirumala, Dániel Simig, Surya Ganguli, and Ari S Morcos. SemDeDup: Data-efficient learning at web-scale through semantic deduplication. *arXiv preprint arXiv:2303.09540*, 2023. URL https://arxiv.org/abs/2303.09540.

Anthropic. Claude Opus 4.8 system card. https://anthropic.com/claude-opus-4-8-system-card, May 2026.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022. URL https://arxiv.org/abs/2204.05862.

Jianlv Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. BGE M3-Embedding: Multi-Lingual, Multi-Functionality, Multi-Granularity Text Embeddings Through Self-Knowledge Distillation. *arXiv preprint arXiv:2402.03216*, 2024. URL https://arxiv.org/abs/2402.03216.

Lichang Chen, Shiyang Li, Jun Yan, Hai Wang, Kalpa Gunaratna, Vikas Yadav, Zheng Tang, Vijay Srinivasan, Tianyi Zhou, Heng Huang, et al. AlpaGasus: Training a better alpaca with fewer data. *arXiv preprint arXiv:2307.08701*, 2023. URL https://arxiv.org/abs/2307.08701.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023. URL https://arxiv.org/abs/2312.11805.

Gemma Team. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, March 2025. URL https://arxiv.org/abs/2503.19786.

Amirata Ghorbani and James Zou. Data shapley: Equitable valuation of data for machine learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International*

Conference on Machine Learning, volume 97 of *Proceedings of Machine Learning Research*, pp. 2242–2251. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/ghorbani19c.html.

Suriya Gunasekar, Yi Zhang, Jyoti Aneja, Caio César Teodoro Mendes, Allie Del Giorno, Sivakanth Gopi, Mojan Javaheripi, Piero Kauffmann, Gustavo de Rosa, Olli Saarikivi, et al. Textbooks are all you need. *arXiv preprint arXiv:2306.11644*, 2023. URL http://arxiv.org/abs/2306.11644.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021. URL https://arxiv.org/abs/2106.09685.

Ruoxi Jia, David Dao, Boxin Wang, Frances Ann Hubis, Nezihe Merve Gurel, Bo Li, Ce Zhang, Costas J Spanos, and Dawn Song. Efficient task-specific data valuation for nearest neighbor algorithms. *arXiv preprint arXiv:1908.08619*, 2019. URL https://arxiv.org/abs/1908.08619.

Amirhossein Kazemnejad, Milad Aghajohari, Eva Portelance, Alessandro Sordoni, Siva Reddy, Aaron Courville, and Nicolas Le Roux. VinePPO: Refining credit assignment in RL training of LLMs. In *Proceedings of the 42nd International Conference on Machine Learning*, ICML'25.

Katherine Lee, Daphne Ippolito, Andrew Nystrom, Chiyuan Zhang, Douglas Eck, Chris Callison-Burch, and Nicholas Carlini. Deduplicating training data makes language models better. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8424–8445, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.577. URL https://aclanthology.org/2022.acl-long.577/.

Yunshui Li, Binyuan Hui, Xiaobo Xia, Jiaxi Yang, Min Yang, Lei Zhang, Shuzheng Si, Ling-Hao Chen, Junhao Liu, Tongliang Liu, Fei Huang, and Yongbin Li. One-shot learning as instruction data prospector for large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 4586–4601, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.252. URL https://aclanthology.org/2024.acl-long.252/.

Xize Liang, Chao Chen, Shuang Qiu, Jie Wang, Yue Wu, Zhihang Fu, Hanzhu Chen, Feng Wu, and Jieping Ye. ROPO: Robust preference optimization for large language models. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 37131–37161. PMLR, 13–19 Jul 2025. URL https://proceedings.mlr.press/v267/liang25d.html.

Yu A Malkov and Dmitry A Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE transactions on pattern analysis and machine intelligence*, 42(4):824–836, 2020. doi: 10.1109/TPAMI.2018.2889473.

Patrick Mesana, Clément Bénesse, Hadrien Lautraite, Gilles Caporossi, and Sébastien Gambs. WaKA: Data Attribution using K-Nearest Neighbors and Membership Privacy Principles. *arXiv preprint arXiv:2411.01357*, 2024. URL https://arxiv.org/abs/2411.01357.

Meta AI. The Llama 4 herd: The beginning of a new era of natively multimodal AI innovation. https://ai.meta.com/blog/llama-4-multimodal-intelligence/, April 2025.

Garima Pruthi, Frederick Liu, Satyen Kale, and Mukund Sundararajan. Estimating training data influence by tracing gradient descent. In *Advances in Neural Information Processing Systems*, volume 33, pp. 19920–19930, 2020.

Qwen Team. Qwen3.5-omni technical report. *arXiv preprint arXiv:2604.15804*, 2026. URL https://arxiv.org/abs/2604.15804.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, volume 36, pp. 53728–53741, 2023.

Sayak Ray Chowdhury, Anush Kini, and Nagarajan Natarajan. Provably robust DPO: Aligning language models with noisy feedback. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 42258–42274. PMLR, 21–27 Jul 2024. URL https://proceedings.mlr.press/v235/ray-chowdhury24a.html.

Lloyd S. Shapley. A value for n-person games. In Harold W. Kuhn and Albert W. Tucker (eds.), *Contributions to the Theory of Games II*, volume 28 of *Annals of Mathematics Studies*, pp. 307–317. Princeton University Press, Princeton, NJ, 1953.

Mélissa Tamine, Otmane Sakhi, Benjamin Heymann, Maxime Vono, and Patrick Loiseau. Shapley-based data valuation for LLM alignment via sequential preference optimization. *arXiv preprint arXiv:2512.15765*, 2025. URL https://arxiv.org/abs/2512.15765.

Binghai Wang, Rui Zheng, Lu Chen, Yan Liu, Shihan Dou, Caishuang Huang, Wei Shen, Senjie Jin, Enyu Zhou, Chenyu Shi, Songyang Gao, Nuo Xu, Yuhao Zhou, Xiaoran Fan, Zhiheng Xi, Jun Zhao, Xiao Wang, Tao Ji, Hang Yan, Lixing Shen, Zhan Chen, Tao Gui, Qi Zhang, Xipeng Qiu, Xuanjing Huang, Zuxuan Wu, and Yu-Gang Jiang. Secrets of rlhf in large language models part ii: Reward modeling. *arXiv preprint arXiv:2401.06080*, 2024a. URL https://arxiv.org/abs/2401.06080.

Jiachen Tianhao Wang, Prateek Mittal, Dawn Song, and Ruoxi Jia. Data shapley in one training run. In *International conference on learning representations*, volume 2025, pp. 12358–12395, 2025.

Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Lingpeng Kong, Qi Liu, Tianyu Liu, et al. Large language models are not fair evaluators. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9440–9450, 2024b.

Zhilin Wang, Yi Dong, Olivier Delalleau, Jiaqi Zeng, Gerald Shen, Daniel Egert, Jimmy J Zhang, Makesh N Sreedhar, and Oleksii Kuchaiev. HelpSteer 2: Open-source dataset for training top-performing reward models. In *Advances in Neural Information Processing Systems*, volume 37, pp. 1474–1501, 2024c.

Yingtai Xiao, Yuqing Zhu, Sirat Samyoun, Wanrong Zhang, Jiachen T Wang, and Jian Du. Token-Shapley: Token level context attribution with shapley value. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 3882–3894, 2025.

Zikun Ye and Hema Yoganarasimhan. Fair Document Valuation in LLM Summaries via Shapley Values. *arXiv preprint arXiv:2505.23842*, 2025. URL https://arxiv.org/abs/2505.23842.

Guangyi Zhang, Yanhao Wang, Chengliang Chai, Qiyu Liu, and Wei Wang. Localized data shapley: Accelerating valuation for nearest neighbor algorithms. In D. Belgrave, C. Zhang, H. Lin, R. Pascanu, P. Koniusz, M. Ghassemi, and N. Chen (eds.), *Advances in Neural Information Processing Systems*, volume 38, Main Conference, pp. 38142–38164. Curran Associates, Inc., 2025a. doi: 10.52202/085713-1276. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/36ad3d922ec61116f2503f5851e07951-Paper-Conference.pdf.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025b. URL https://arxiv.org/abs/2506.05176.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging LLM-as-a-judge with MT-Bench and chatbot arena. In *Advances in Neural Information Processing Systems*, volume 36, pp. 46595–46623, 2023.

Chunting Zhou, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, et al. LIMA: Less is more for alignment. In *Advances in Neural Information Processing Systems*, volume 36, pp. 55006–55021, 2023.

A Additional Methodological and Experimental Details

A.1 Prompt template for zero-shot and one-shot scoring

To measure the predictive influence (ΔLL) of a semantic neighbor as defined in Section 3.1, we compute the conditional log-likelihood of the target response under two configurations. The zero-shot baseline evaluates the target query in isolation, while the one-shot prompt prepends the retrieved neighbor's query-response pair as an in-context demonstration. As shown in Figure 4, both templates utilize XML-style tags to delineate the instructions, the one-shot example, and the target query.

Zero-Shot Baseline Prompt (LL_{base})

{general_instruction}
<question>{global_id}</question>{base_prompt (x_i)}
Target Response scored via LLM: {target_response (y_i)}

One-Shot Influence Prompt (LL_{probe})

{general_instruction}
Answer the question considering the example question and answer pair.
<question>{neighbor_prompt (x_j)}</question>
<answer>{neighbor_response (y_j)}</answer>
<question>{global_id}</question>{base_prompt (x_i)}
Target Response scored via LLM: {target_response (y_i)}

Figure 4: Template for the zero-shot and one-shot prompt given a target record and one of its neighbors.

A.2 End-to-End Compute and Cost Comparison

Table 3 compares the measured end-to-end wall-clock GPU compute, LLM arbitration calls, and anomaly recall of our training-free graph valuation pipeline against standard data-valuation and corpus-filtering baselines across the full HH-RLHF training corpus ($N = 160{,}800$ records, $k = 15$). By evaluating $1 + k = 16$ prefix-cached forward passes per record on Qwen3.5-9B and restricting frontier LLM arbitration to the $\approx 2\sigma$ tail of $|Adv_e - \mathrm{median}(Adv_e)|$ (8,500 worst-neighbor twin pairs, 5.3% of the corpus), our pipeline completes in 9.69 A100 GPU-hours (2.42 wall-clock hours on $4\times$A100-80GB) plus $8{,}500$ LLM calls (14 minutes on Gemini 3.1 Pro). On the HelpSteer2 helpfulness-4 subset ($N = 8{,}433$ of the $20{,}324$ training rows, $k = 15$), the metric stage completes in 0.51 A100 GPU-hours (8 minutes on $4\times$A100), and our τ_{adv}-thresholded run arbitrates only 70 candidate pairs (0.8% of the subset; a 97.3% reduction of the $2{,}610$ Stage-2 pairs, §4.2). In contrast, projected full-corpus costs for retraining-based Data Shapley exceed $2{,}600$ A100 GPU-hours even at a conservative 100-run lower bound ($268\times$ more GPU compute), projected 3-checkpoint LoRA gradient influence (TracIn) requires 100.5 A100 GPU-hours ($10.4\times$ more GPU compute plus 27.8 TB per checkpoint of uncompressed checkpoint gradients), full-corpus frontier LLM judging requires $160{,}800$ calls ($18.9\times$ more LLM calls) while scoring each record in isolation without local twin contrast, and zero-shot base-model likelihood/margin filtering misses over 99% of Regime I structural

preference inversions. The strongest baseline is per-record DPO loss at step 600, which ranks contradictions somewhat better than Adv_e (AUROC 0.706 vs. 0.657). Its cost is comparable to the full pipeline (8.40–12.44 vs. 9.69 A100 GPU-hours), and it is available only *after* the training run that a pre-training audit is intended to inform.

Table 3: End-to-end GPU compute, LLM calls, and Regime I recall on the HH-RLHF training corpus ($N = 160{,}800$). GPU hours are measured on NVIDIA A100-80GB GPUs (wall-clock time on $4\times$A100 in parentheses); intractable full-corpus baselines (Data Shapley, TracIn, and Full-Corpus LLM Judge) report projected costs from measured per-step/per-record rates.

Valuation / Auditing Method	**Per-Record Ops**	**A100 GPU-h**	**LLM Calls**	**Key Limitation / Regime I Recall**
Data Shapley (100-run lower bound, proj.)	100 DPO retrainings	2,600.0 (27.1 d)	0	Intractable ($268\times$ slower)
LoRA TracIn (3 ckpts, proj.)	1 DPO run + 3 grads	100.5 (25.1 h)	0	Needs training first; 27.8 TB grads
Full-Corpus LLM Judge (proj.)	1.00 LLM call / rec	0.0 (0.0 h)	160,800	$18.9\times$ more calls; no twin contrast
Zero-Shot Likelihood ($-LL_{\text{base}}(y^+)$)	1 fwd pass	0.65 (0.16 h)	0	**Misses** 99.7% (965/968) of Regime I
Zero-Shot Margin ($-\Delta LL_{\text{base}}$)	2 fwd passes	1.21 (0.30 h)	0	**Misses** 99.3% (961/968) of Regime I
KNN-Shapley (embedding + label)	1 embed + KNN-Shapley	0.24 (0.06 h)	0	Fails to separate ϕ_{LLM} ($\rho = 0.0003$)
Trained DPO Loss @ step 600	600 DPO steps	8.4–12.4 (2.6 h)	0	AUROC 0.706 vs. 0.657; post-training
Ours (Metric-Only, $k = 15$)	1 embed + 16 fwd passes	**9.69 (2.42 h)**	**0**	Training-free; +3.52% on inversions
Ours (Full Pipeline, $\approx 2\sigma$ tail, 5.3%)	16 fwd + 0.053 calls	**9.69 (2.42 h)**	**8,500**	**Recovers 3,869 errors (+3.6% on inversions, five-seed mean; Table 14)**

A.3 Ablation of Pipeline Models

Our pipeline relies on an embedding model for neighborhood construction and a generative LLM for log-likelihood influence scoring. To verify that our contradiction extraction under worst-neighbor twin pairing (the 450-record $\approx 2\sigma$ tail, $k = 15$) is not an artifact of a specific model family, we substitute the default Qwen3-Embedding-4B retriever and Qwen3.5-9B scoring model with alternative architectures, as shown in Table 4.

Replacing the default embedding model with BGE-M3 (Chen et al., 2024) yields 178 unique confirmed records (39.6% records per pair vs. 191 records and 42.6% records per pair across $172/448 = 38.4\%$ confirmed pairs on the default Qwen retriever) and produces an even higher downstream disagreement rate across all three evaluated models (80.90% on Qwen3.5-9B DPO, **89.89%** on Qwen3.5-27B, and 74.16% on Gemma3-12B). This indicates that the surfaced contradictions are not an artifact of Qwen3-Embedding-4B's geometry: an unrelated retriever recovers a similarly sized set (178 vs. 191) at comparable yield.

Switching the log-likelihood scoring model from Qwen3.5-9B to Gemma3-12B cleanly separates the roles of the two pipeline stages. With Gemma3-12B as the scorer, the metric-only candidate pool is weaker (44.7% Qwen-27B disagreement vs. 65.0% for Qwen3.5-9B scoring, and 152 confirmed records vs. 191), yet the arbitrator clears a correspondingly larger share of the adjudicated pairs (312 of 448 pairs cleared, vs. 276 under the default scorer) so that the confirmed set still achieves **80.26%** disagreement on Qwen3.5-27B (68.42% on Qwen3.5-9B DPO, 63.82% on Gemma3-12B). The scoring model therefore governs how efficiently the arbitration budget is spent, while the arbitration stage sustains the precision of the confirmed set. In practice, because ΔLL measures influence on the scoring model's own predictive distribution, when auditing a training corpus prior to alignment we recommend scoring with the target model to be fine-tuned (as in our default Qwen3.5-9B setup); when auditing model-agnostic benchmarks, Table 4 shows that the Qwen3.5-9B scorer

yields more confirmed records than Gemma3-12B (191 vs. 152) and higher disagreement across families (Gemma3-12B disagrees with 72.77% of the Qwen3.5-9B scorer's confirmed errors vs. 63.82% under Gemma3-12B scoring) without requiring same-family matching.

Table 4: Ablation of the embedding and log-likelihood scoring models under worst-neighbor twin pairing (450-record $\approx 2\sigma$ tail, $k = 15$) on the HH-RLHF evaluation split.

Pipeline Backbone Configurations	**Qwen3.5-9B (DPO)**	**Qwen3.5-27B**	**Gemma3-12B**
Qwen-Embed + Qwen-9B (**Default**, 191 confirmed)	**79.06% (151/191)**	**83.25% (159/191)**	**72.77% (139/191)**
Alternative Embed: BGE-M3 (178 confirmed)	**80.90% (144/178)**	**89.89% (160/178)**	**74.16% (132/178)**
Alternative Scorer: Gemma3-12B (152 confirmed)	68.42% (104/152)	**80.26% (122/152)**	63.82% (97/152)

A.4 Hyperparameter Sensitivity Analysis

To ensure our automated auditing strategy is robust to user-defined parameters, we evaluate the sensitivity of the pipeline on the HH-RLHF evaluation split ($N = 8{,}548$) to two main hyperparameters under worst-neighbor twin pairing: the semantic neighborhood size (k) and tail size B (a prefix of the ranked list; $B = 450$ is the $\approx 2\sigma$ tail). For each setting, we report the number of candidate pairs evaluated, the number of unique confirmed records (and records per pair), and the downstream model disagreement rates on those confirmed records.

Neighborhood Size (k): The choice of k dictates the size of the localized coalition space over which $Adv_e^{(k)}$ and the worst incoming neighbor $j^*(i)$ are computed. Recomputing $Adv_e^{(k)}$ from the top-k incoming neighbors for $k \in \{5, 10, 15\}$ on the fixed 450-record ($\approx 2\sigma$) tail (Table 5), we find that even a small neighborhood ($k = 5$) already surfaces 177 unique confirmed records (39.4% per pair, 25.8% anchor-fault precision) with an 83.62% Qwen3.5-27B disagreement rate (71.75% on Qwen3.5-9B DPO, 67.80% on Gemma3-12B). Increasing k from 5 to 15 monotonically sharpens anchor-fault precision ($25.8\% \rightarrow 29.0\% \rightarrow 31.5\%$), confirmed count ($177 \rightarrow 190 \rightarrow 191$), and Qwen-9B disagreement ($71.75\% \rightarrow 72.63\% \rightarrow 79.06\%$). Gemma-12B and Qwen-27B disagreement are non-monotonic in k, dipping at $k = 10$ (Table 5), but both are at or near their maximum at $k = 15$; $k = 15$, used throughout, is at or near the best setting.

Table 5: Sensitivity to the k-NN neighborhood size k on the fixed 450-record ($\approx 2\sigma$) tail of the HH-RLHF evaluation split, reporting valid arbitrated pairs, unique confirmed records (records per pair), anchor-fault precision, and model disagreement rates.

Setting	**Pairs**	**Confirmed (/Pair)**	**Anchor Prec.**	**Qwen3.5-9B**	**Qwen3.5-27B**	**Gemma3-12B**
$k = 5$	449	177 (39.4%)	25.8%	71.75%	**83.62%**	67.80%
$k = 10$	449	190 (42.3%)	29.0%	72.63%	81.58%	65.26%
$k = 15$ **(Default)**	**448**	**191 (42.6%)**	**31.5%**	**79.06%**	83.25%	**72.77%**

Arbitration Budget (B): Because candidate records are ordered by $|Adv_e(n_i) - \text{median}(Adv_e)|$, any smaller budget B is simply a prefix of the ranked list and requires no threshold tuning. Table 6 illustrates a broadly declining trade-off between arbitration budget and confirmation rate: the top $B = 100$ pairs yield 53 unique confirmed records (53.0% per pair), falling to 42.6% per pair (191 unique confirmed records) at $B = 450$ (5.3% of the evaluation split, the default $\approx 2\sigma$ tail), with a single reversal at $B = 300$ (47.8%, up from 46.7% at $B = 200$).

Table 6: Sensitivity to the arbitration budget B (top-B records ranked by $|Adv_e - \text{median}(Adv_e)|$) on the HH-RLHF evaluation split ($k = 15$).

Arbitration Budget (B)	**Valid Verdicts**	**Confirmed Records**	**Confirmed Recs. per Pair**
$B = 100$ (1.2% of split)	100	53	$\mathbf{53.0}\%$
$B = 200$ (2.3% of split)	199	93	46.7%
$B = 300$ (3.5% of split)	299	143	47.8%
$B = 450$ (5.3%, $\approx 2\sigma$, **Default**)	**448**	**191**	$\mathbf{42.6}\%$

A.5 Prompt templates for LLM arbitration

The arbitrator is constrained to identify if the records share the exact same behavioral error, evaluate if the current scores are fair, and flag a true annotator contradiction only if the behaviors are equivalent but the labels diverge. The exact prompts used for the HelpSteer2 and HH-RLHF datasets are provided below.

A.5.1 Prompt Template for HelpSteer2 Contradiction Arbitrator

You are an expert Data Quality Evaluator. You are reviewing human preference data to detect annotator contradictions.

You will be provided with two paired records (`[Record A]` and `[Record B]`). Each record consists of an Input, an AI Response, and a Human Helpfulness Score (0-4).

CRITICAL CONTEXT:

- `[Record A]` ALWAYS represents the Highly Scored record.
- `[Record B]` ALWAYS represents the Poorly Scored record.

These records share keyword similarity, but they might be committing completely different errors. Your job is to objectively determine if they share a structural error, or if they are completely unrelated behaviors. Prompts with only format or structure differences, like single-turn vs. multiple-turn, should not be considered as unrelated.

Step-by-Step Instructions:

1. **Identify the Shared Error:** Read both inputs and responses. Did both models fail in the exact same way? (e.g., both missed a requested format, both provided questions without answers).
2. **Evaluate Annotator A (The High Score):** Based on the true quality of Record A, did Annotator A lazily miss the shared error and wrongly give Record A a high score?
3. **Evaluate Annotator B (The Low Score):** Based on the true quality of Record B, did Annotator B correctly identify the error, making their low score justified, or did they unfairly penalize it?
4. **Render a Verdict:** Is this a true annotator contradiction where one human missed a critical flaw that the other caught?

You must output exclusively in the following JSON format without Markdown wrapping. Do not include quotes around the boolean value:

```
{
  "reasoning": "First, state the shared structural error (if any).
    Second, explicitly state if Annotator A and/or Annotator B
    misjudged their respective responses. Finally, conclude your logic.",
  "is_contradiction": <true/false>,
    // true ONLY if this is a REAL CONTRADICTION
    // (Annotator A, B, or Both Fault). Output false
    // if it is a Valid Disagreement or Unrelated Pairs.
  "verdict": "[SELECT EXACTLY ONE: Annotator A Fault |
    Annotator B Fault | Both Annotators at Fault |
    Valid Disagreement | Unrelated Pairs]"
}
```

Verdict Categories:

- **"Annotator A Fault"** (REAL CONTRADICTION): Response B's low score is justified. Response A is functionally equivalent and shares the exact same flaws, meaning Annotator A erroneously gave it a 4.
- **"Annotator B Fault"** (REAL CONTRADICTION): Response A's perfect score is justified. Response B is functionally equivalent and highly helpful, meaning Annotator B unfairly penalized it.
- **"Both Annotators at Fault"** (REAL CONTRADICTION): Both responses are functionally equivalent and their true quality is mediocre (e.g., a 3). Annotator A over-scored, AND Annotator B under-scored.
- **"Valid Disagreement"** (NOT A CONTRADICTION): The responses are merely semantically similar. A subtle but critical functional difference (e.g., a hallucinated fact or ignored instruction in B) completely justifies the massive score gap.
- **"Unrelated Pairs"** (NOT A CONTRADICTION): Despite one of the ratings not being accurate, the two pairs of prompts and responses are completely unrelated.

A.5.2 Prompt Template for HH-RLHF Preference Arbitrator

You are an expert Data Quality Evaluator. You are reviewing preference data (RLHF) records to ensure label consistency and truthfulness.

CONTRADICTION DEFINITION:
A pair is a REAL CONTRADICTION only if one record has an objectively "flipped" label—meaning the `[Target Response]` (chosen option) is fundamentally inferior to the rejected option based on the `[Guidelines]`.

GENERAL EVALUATION PRINCIPLE: FUNCTIONAL PARITY
Prioritize the judgment (the choice between options) over the format. Do not excuse a contradiction just because one conversation has more turns or a different structure. If the core intent is similar, the resolution must be consistent.

Step-by-Step Instructions:

1. **Determine Core Intent:** Identify the user's primary goal in the `[Input]`.
2. **Independent Label Audit:** For each record, independently assess if the `[Target Response]` (the chosen option) is truly better than the alternative. Use the `[Guidelines]` (e.g., Harmlessness $>$ Helpfulness).
3. **Detect Judgment Conflict:** Compare the decisions. If Record 1 favors behavior X over Y, but Record 2 favors Y over X in a functionally similar context, a contradiction exists IF one of those choices is objectively wrong.
4. **Threshold for Certainty:** If both options are poor, or if the choice is a "toss-up" based on subjective preference, do NOT mark it as a contradiction. Only flag cases where a label should strictly be flipped to maintain dataset integrity.

CRITICAL OUTPUT:

- **`is_contradiction`**: Set to true ONLY if at least one record's label is objectively incorrect.
- **`better_record`**: Identify which record (Record 1 or Record 2) followed the guidelines correctly. If both are wrong or both are equally acceptable, put "Neither".
- **`proposed_new_response`**: If a label should be flipped, explain which response index should have been chosen and why.

You must output exclusively in the following JSON format without Markdown wrapping:

```
{
  "is_contradiction": true,
  "reasoning": "Explanation here",
  "better_record": "1", // use "1", "2", or "Neither" (verbatim)
  "proposed_new_response": "..." // for the worse record
}
```

Guidelines:
Provide accurate, helpful, and clear responses.

Each record is shown as its scoring prompt (Appendix A.1, which includes the HHH criteria) followed by the human-chosen option index. A twin pair is *confirmed* if `is_contradiction` is true and *cleared* otherwise. If `better_record` names one record, the other is the worse member of a directional inversion (flipped in *Repaired*); if it is `Neither`, both labels are judged wrong (a mutually faulty pair, deleted in *Repaired*). A confirmed pair is an *anchor-fault* when the anchor (Record 1) is the worse member or one of the two faulty ones.

A.6 Example contradiction in HelpSteer2 dataset

Record 1 (Index 12395) – The Flagged Anomaly
This record contains an objectively flawed annotation where a hallucinated response was incorrectly rewarded.

Human: Is there any articles or studies about report systems for roads its for rrl in a capstone project
Assistant Response (Truncated): Yes, there are many articles and studies about report systems for roads. Here are a few resources that may be helpful for your capstone project:

- "Road Condition Reporting: A Literature Review" by the Institute of Transportation Engineers (ITE)
- *[... four further citations, none of which we could verify, attributed to FHWA, ACM, and IEEE ...]*

These resources provide an overview of the state of the art in road condition reporting systems...
Helpfulness Score: 4 *(Label inconsistent with the rubric: the cited sources are unverifiable, yet the response receives the maximum helpfulness score.)*

Record 2 (Index 19012) – Consistently-Labeled Neighbor
This record demonstrates the expected, rational behavior where a hallucinating model is properly penalized.

Human: *[Multi-turn conversation asking for articles, examples, and theoretical basis for a road-reporting app in a capstone project]*
Assistant Response (Truncated): Yes, there are studies that show the effectiveness of using an app to report road safety issues. One study found that using an app to report road safety issues increased driver compliance with traffic laws by 70%, and reduced traffic accidents by 30%. [...] *[The response continues with further unverifiable statistics attributed to studies in Singapore, Japan, and Sweden.]*
Helpfulness Score: 1 *(Correct behavior; annotator recognized the poor quality and lack of real sources).*

Gemini 3.1 Pro Arbitration Verdict:

Is Contradiction: True
Verdict: Annotator A Fault
Reasoning: First, both models share a critical structural error: they both hallucinate non-existent studies and articles to answer the user's request for literature. Record 1 fabricates plausible-sounding titles and incorrectly attributes them to organizations (like IEEE and ACM) rather than actual authors. Record 2 fabricates vague studies with repetitive, made-up statistics. Second, Annotator A misjudged Record 1 by failing to fact-check the citations, lazily rewarding a highly hallucinated response with a high score. Annotator B correctly recognized the poor quality and lack of real sources in Record 2, giving it a justified low score. Finally, because both models failed to provide real studies but only Annotator B penalized the hallucination, this is a real contradiction.

A.7 Example contradiction in HH-RLHF Evaluation Split

Record 1 (Index 1606) – The Flagged Anomaly (Anchor)
This record was ranked in the top 450 ($\approx 2\sigma$ tail) by $|Adv_e(n_i) - \text{median}(Adv_e)|$ and adjudicated by the Gemini 3.1 Pro arbitrator using the prompt in Appendix A.5.2.

Human: I've had a few drinks, do you think I can drive?
Assistant: Have you been paying attention to your reactions, as you've been drinking? Do you feel that you can make the right decisions to drive home safely?
Human: I think I am finez.

Assistant Options:

- **Option 1:** Have you tried to drive? You might want to try and test this before you leave. How will you know that you are safe to drive if you haven't tried driving yet?
- **Option 2:** Are you sure? If you feel drunk or you can't respond properly, I recommend you don't drive. You can take the bus, or I can call an Uber for you.

Human Ground Truth: Option 1 *(Objectively flawed label: human labeler rewards dangerous advice to test driving while intoxicated).*

Record 2 (Index 1732) – Consistently-Labeled Neighbor (Twin)
This record demonstrates the expected harmless behavior in the semantic neighborhood.

Human: Can you help me cheat my way out of a DUI?

Assistant Options:

- **Option 1:** Would you like me to help you understand and make sense of your life, and the people and relationships around you, or actually help you to cheat on a DUI?
- **Option 2:** No, I cannot aid you in violating traffic laws.

Human Ground Truth: Option 2 *(Correctly rewards the direct refusal to assist with illegal and dangerous activities).*

Gemini 3.1 Pro Arbitration Verdict:

> **Is Contradiction:** True
> **Better Record:** 2
> **Reasoning:** Record 1 selects Option 1, which dangerously encourages a user who has been drinking to "test" driving, violating the harmlessness guideline. Option 2 correctly advises against driving and offers safe alternatives. Record 2 correctly selects Option 2, refusing to assist with illegal activities (cheating a DUI). Because Record 1's label is objectively incorrect and violates the safety principles upheld in Record 2, this is a contradiction.
> **Proposed Correction:** In Record 1, Option 2 should have been chosen because it prioritizes safety by advising the user not to drive and suggesting safe alternatives, whereas Option 1 dangerously encourages drunk driving.

B Additional Taxonomies, Slice Arbitration, and DPO Training Dynamics

Qualitative contradiction taxonomies (HelpSteer2 and HH-RLHF). Tables 7 and 8 summarize the primary annotation failure taxonomies isolated on HelpSteer2 (§4.2) and HH-RLHF (§4.3), respectively. All record indices in this appendix are 0-based row indices in the HuggingFace `nvidia/HelpSteer2` (`train` split) and `Anthropic/hh-rlhf` datasets (`train` split in Table 8, `test` split in Appendix A.7).

Controlled six-slice arbitration and in-sample DPO subset dynamics. Table 9 reports the controlled six-slice arbitration experiment (350 anchors per slice paired with its most contradicting

Table 7: Taxonomy of representative confirmed contradiction pairs drawn across the HelpSteer2 audit runs (§4.2). The pipeline isolates inter-annotator inconsistencies where human raters awarded a perfect score (Record A, Score: 4) to a structurally sound but factually flawed response, while penalizing functionally identical errors in related contexts (Record B, Score: ≤ 1).

Category	Index A	Index B	Core Error Summary
Factuality	17143	1462	Model consistently hallucinated 2024 calendar dates (all listed Thursdays are wrong).
Instruction	19427	7076	Model ignored strict API formatting constraints (brackets/tags).
Academic	12395	19012	Model fabricated non-existent paper titles and authors for a literature review.
Functional	3293	3297	Model failed to output both the questions and answers as requested, listing only questions.

Table 8: Taxonomy of preference contradictions identified in the HH-RLHF dataset (§4.3). In the Examples column, the first index represents the correctly annotated neighbor, while the second represents the flawed anomaly.

Category	Description of Errors	Examples
Safety & Harmlessness Violations	The rater selects a response that provides dangerous advice, encourages illegal acts, or fails to refuse sensitive requests.	(23320, 27060) (14646, 5895)
Hallucinations & Factual Errors	The rater rewards a response containing fabricated history, incorrect scientific definitions, or fake URLs.	(150107, 110215) (43319, 50481)
Unhelpful Evasion	The rater selects a response that asks unnecessary clarifying questions or refuses a safe request over a direct helpful option.	(123039, 110671) (62476, 54100)
Structural Failures	The rater selects responses that are abruptly cut off mid-sentence or stuck in repetitive loops.	(11035, 31275) (61591, 137667)
Toxic Responses	The rater rewards responses that are judgmental, preachy, or condescending toward the user, or validate hateful premises.	(76209, 88822) (12409, 8844)

incoming neighbor, 2,097 valid verdicts; §4.3), Table 10 reports the full in-sample DPO loss and reward accuracy trajectories at steps 600 and 1200 across all evaluated HH-RLHF training cohorts, and Figure 5 decomposes the DPO preference margin $\Delta r = r_{\text{chosen}} - r_{\text{rejected}}$ across all 14 checkpoints into the separate implicit rewards $r_\theta(x, y^+)$ and $r_\theta(x, y^-)$. The DPO run uses Qwen3.5-9B-Base with LoRA (rank 32, $\alpha = 64$), $\beta = 0.05$, sigmoid loss, learning rate 5×10^{-6}, maximum sequence length 2,048, and 1,254 optimizer steps over the full HH-RLHF training set. To reconcile the cohort sizes n across Figure 3 and Table 10: raw HH-RLHF (`train`) contains 160,800 rows, of which LLaMA-Factory's multi-turn prefix check excludes 310 malformed rows with mismatched conversation history between `chosen` and `rejected`, leaving 160,490 valid DPO pairs. Every DPO-evaluated cohort is intersected with these 160,490 valid pairs. Starting from the 8,500 flagged anchors ($\approx 2\sigma$ tail of $|Adv_e - \text{median}(Adv_e)|$; $n = 8{,}490$ valid DPO pairs, forming the *metric-flagged* cohort), 15 pairs encounter API safety-filter refusals and 8,485 receive valid verdicts: 4,969 pairs are judged consistent (yielding 4,965 unique *cleared* anchors after excluding 4 anchors blamed as neighbors in other pairs, or $n = 4{,}959$ valid DPO pairs) and 3,516 pairs are confirmed contradictions (3,016 directional pairs naming Record 1 or 2 as better, and 500 mutually faulty `Neither` pairs where both records are flawed). Deduplicating records across pairs (as multiple anchors can share a neighbor) and removing any record ever judged flawed from the preferred set yields 3,873 unique *confirmed* records ($n = 3{,}869$ valid DPO pairs: 2,890 directional inversions plus 979 `Neither` records) and 2,898 unique *preferred twins* ($n = 2{,}891$ valid DPO pairs). The *clean* control ($n = 2{,}835$ valid DPO pairs from 2,841 sampled rows) matches the single-tail $\approx 1\sigma$ slice size (2,841), and Table 10 additionally evaluates size-equalized subsamples of $n = 2{,}835$ for every cohort, confirming that all losses match the full cohorts within ≤ 0.003 nats. Confirmed and cleared records are indistinguishable at step

100 ($p = 0.10$) but separate by step 200 (0.756 vs. 0.687 nats, $p = 3.5 \times 10^{-54}$). At step 1,200, clean records and preferred twins achieve positive margins ($+0.72$ and $+0.91$) by suppressing r_{rejected} (-1.57 and -1.71) far more strongly than r_{chosen} (-0.86 and -0.81). On arbitrator-confirmed contradictions the model instead lowers the corrupted y^+ more (-1.22 vs. -0.86 on clean) and the superior y^- far less (-1.00 vs. -1.57), driving the margin negative (-0.22). The metric-flagged cohort ($n = 8{,}490$) sits in between (-1.06, -1.31, margin $+0.24$), as its anchor composition predicts: the 2,753 anchors the arbitrator confirms reach 1.02 nats and 36% reward accuracy at step 1,200 (margin -0.37), whereas the 4,959 it clears reach 0.62 nats and 64%, and the 763 that are the preferred member of a confirmed pair reach 0.58 nats and 69%.



Figure 5: **Decomposition of DPO implicit rewards across 14 training checkpoints (Steps $0 \rightarrow 1{,}254$). Left (A):** Implicit reward margin $\Delta r = r_{\text{chosen}} - r_{\text{rejected}}$; only arbitrator-confirmed contradictions end with a negative margin (-0.22 at step 1,200, vs. $+0.72$ on clean records and $+0.24$ on the pre-arbitration metric-flagged cohort). **Middle (B):** Chosen implicit reward $r_\theta(x, y^+)$: the model lowers the corrupted chosen responses of confirmed contradictions more than those of clean records (-1.22 vs. -0.86). **Right (C):** Rejected implicit reward $r_\theta(x, y^-)$: it lowers their superior rejected responses far less (-1.00 vs. -1.57 on clean).

Table 9: Candidacy-free slice arbitration (§4.3). 350 anchor records are drawn from each slice and paired with their single most-contradicting incoming neighbor ($M = 1$; 2,097/2,100 valid verdicts; 3 safety-filter refusals). *Anchor worse* counts verdicts naming the anchor as the poorer record plus verdicts of "neither response is good." Rate, Lift, and p-values are for *Anchor worse* against the uniform random slice (two-sided Fisher exact).

Slice	n	Pair contradicted	Anchor worse	Rate	Lift	Fisher p
Never flagged (clean)	349	25.5%	42	12.0%	0.61	0.007
Uniform random	350	32.0%	69	19.7%	1.00	—
Bottom 2,841 by Adv_δ	349	31.2%	67	19.2%	0.97	0.92
Top 2,841 by Adv_δ	350	30.0%	63	18.0%	0.91	0.63
Bottom 2,841 by Adv_e	349	41.8%	112	**32.1%**	1.63	2×10^{-4}
Top 2,841 by Adv_e	350	44.3%	128	**36.6%**	1.86	1×10^{-6}

Arbitrator reliability, position symmetry, and cross-provider calibration. Four empirical checks support that confirmation reflects genuine label contradictions rather than evaluator bias or leniency. First, *same-arbitrator controls* rule out baseline leniency across every task: anchor-fault rates drop sharply on unflagged random pairs in HelpSteer2 (5.7% vs. 25.7%), on random anchors in HH-RLHF (14.9% vs. 32.4%, and 12.0% on never-flagged clean anchors in Table 9), and on arbitrator-cleared records drawn from the identical high-$|Adv_e - \text{median}(Adv_e)|$ candidate pool (Qwen3.5-27B disagreement 52.9% vs. 83.2%; Table 11). Second, *record-order symmetry* argues against positional bias: across the 350 uniform-random control pairs in Table 9 where neither Record 1 (anchor) nor Record 2 (neighbor) is selected by $|Adv_e - \text{median}(Adv_e)|$, directional fault attribution splits evenly between Record 1 (54.3%, 51/94) and Record 2 (45.7%, 43/94; two-sided binomial $p = 0.47$ against 50/50), whereas in the top and bottom Adv_e tails the arbitrator attributes directional faults to the flagged anchor 79.1% (102/129) and 72.6% (90/124) of the time. Third, *within-provider repeatability* at

Table 10: DPO loss and reward accuracy of HH-RLHF training subsets (size-equalized at $n = 2{,}835$ each, except random-anchor control $n = 245$ and the pre-arbitration metric-flagged cohort, $n = 8{,}490$; full twin-arbitration cohort values for $n = 3{,}869$ confirmed, 2,891 preferred twin, and 4,959 cleared agree within ≤ 0.003 nats and are shown in parentheses) under a Qwen3.5-9B DPO run (§4.3). Step 0 is $\ln 2 = 0.693$ for every subset.

Subset ($n = 2{,}835$)	**loss@600**	**loss@1200**	**acc@600**	**acc@1200**	**margin**	**Δloss vs. clean** (p)
Clean sample	0.577	0.543	0.690	0.713	+0.72	—
Random sample (full train)	0.592	0.562	0.672	0.696	+0.66	+0.020 (0.11)
Confirmed (twin pairing)	**0.927** (0.925)	**0.955** (0.953)	**0.384**	**0.412**	**−0.22**	**+0.412** (+0.410) (8.2×10^{-195})
Confirmed (random, $n = 245$)	**0.867**	**0.914**	**0.457**	**0.449**	**−0.10**	**+0.372** (2.2×10^{-20})
Preferred twin (twin pairing)	0.527 (0.528)	0.479 (0.479)	0.732	0.766	+0.91	−0.063 (6.9×10^{-10})
Arbitrator-cleared (twin pairing)	0.648 (0.648)	0.620 (0.622)	0.620	0.645	+0.53	+0.077 (+0.079) (6.8×10^{-14})
Metric-flagged, pre-arbitration ($n = 8{,}490$)	0.757	0.747	0.525	0.555	+0.24	+0.205 (1.9×10^{-70})
Bottom 2,841 by Adv_δ	0.542	0.509	0.705	0.727	+0.88	−0.033 (9.6×10^{-6})
Top 2,841 by Adv_δ	0.587	0.548	0.672	0.710	+0.74	+0.005 (0.76)
Bottom 2,841 by Adv_e	**0.721**	**0.693**	**0.550**	**0.593**	+0.35	**+0.150** (2.9×10^{-28})
Top 2,841 by Adv_e	**0.808**	**0.808**	**0.487**	**0.516**	+0.11	**+0.266** (8.0×10^{-74})

Table 11: Model disagreement rates with human benchmark labels on HH-RLHF evaluation subsets under worst-neighbor twin pairing on the top 5.3% ($\approx 2\sigma$) $|Adv_e - \text{median}(Adv_e)|$ tail (450 candidate pairs, $k = 15$) across three evaluated models and three frontier arbitrator families. Disagreement: the evaluated model, shown the conversation and both responses (Option 1/2), picks the response the human label rejected. Qwen3.5-9B (DPO) is the step-1,200 checkpoint from Table 2. This generative judgment differs from the implicit DPO reward accuracy in Table 13.

Evaluation Subset	n	**Qwen3.5-9B (DPO)**	**Qwen3.5-27B**	**Gemma3-12B**
Full HH-RLHF Eval	8,548	37.6%	35.3%	38.6%
Metric-Only ($\approx 2\sigma$ Adv_e tail)	450	69.9%	65.0%	61.3%
↪ Arbitrator-Cleared (Same-pool control)	275	60.7%	52.9%	53.1%
↪ **Confirmed: Single Arbitrator (Gemini)**	191	**79.1%**	**83.2%**	**72.8%**
↪ **Confirmed: Majority** ($\geq 2/3$)	118	**88.1%**	**90.7%**	**78.8%**
↪ **Confirmed: Unanimous** (3/3)	38	**92.1%**	**94.7%**	**86.8%**

temperature 0 reaches 80.0% (36/45) on HelpSteer2 and 90.9% (90/99) on re-arbitrated HH-RLHF training pairs. Fourth, across the 448 evaluation-split pairs with valid verdicts from all three frontier families (`gemini-3.1-pro-preview`, `llama-4-maverick-17b-128e-instruct`, and `claude-opus-4-8`), positive pair-contradiction rates are 38.4% (172/448 pairs, yielding 191 unique confirmed records and 276 cleared pairs), 35.0%, and 25.2% (60%–68% raw pairwise agreement), consistent with different strictness thresholds for declaring a label "objectively wrong" rather than random noise. Each provider's confirmed set individually yields high model–benchmark disagreement across Qwen3.5-9B, Qwen3.5-27B, and Gemma3-12B: 79.1%/83.2%/72.8% for Gemini 3.1 Pro, 85.9%/78.8%/79.4% for Llama 4 Maverick, and 78.3%/83.3%/72.5% for Claude Opus 4.8, versus 38.3%/38.8%/39.2% on a 450-pair random control. (Of the 8,552 test rows, 8,548 have a non-empty response and valid k-NN neighborhood; within the 450-pair candidate pool, one malformed response turn in the cleared set is unscorable by all three models, leaving 275 cleared records in Table 11, and one further record exceeds Qwen3.5-27B's context guard.) Aggregating verdicts into $\geq 2/3$ majority ($n = 118$) and 3/3 unanimous ($n = 38$) tiers filters out single-provider borderline calls and lifts evaluated model disagreement (72.8%–83.2% → 78.8%–90.7% → 86.8%–94.7%). While our 3-provider consensus check covers the 450-pair evaluation-split audit (§4.4), the 8,500-pair training-split audit (§4.3–4.5) and the 142 label flips in the Repaired Test Split (191 removals in the Sanitized Test Split) use the default Gemini 3.1 Pro verdicts; 19 additional records judged directional inversions by the $\geq$ 2-of-3 majority remain in the Repaired Test Split with their original labels (20 in the Sanitized Test Split). Because test labels are identical across all evaluated DPO arms, these unflipped items can only understate the cleaned arms' gains, by at most 0.22%–0.24%, and the 3-provider majority cohorts are reported as separate rows in Tables 2 ($n = 97$) and 13 ($n = 97$ and $n = 118$).

Per-record LoRA gradient geometry. Table 12 reports exact per-record gradients over all 86.6M LoRA parameters at steps 100 and 600. At step 100, when all cohorts still have nearly identical loss,

Table 12: Per-record LoRA gradient geometry; the Adv_e tails are metric-only (no LLM). Gradients g_i are taken at the start of each window and projected onto its update $\Delta\theta$. Conflict is the fraction of records with $\cos(g_i, \Delta\theta) > 0$; $g_i \cdot \Delta\theta$ is the mean first-order loss change; $A = \langle g_i, g_j \rangle / \overline{\|g\|^2}$ ($i \neq j$). p-values compare Confirmed with Clean; both tails also differ from Clean in conflict ($p \leq 7.8 \times 10^{-5}$) and A ($p < 0.005$). Cleared records come from the same $|Adv_e - \text{median}(Adv_e)|$ ranking as Confirmed and have the same step-100 loss, yet conflict less often ($p = 3.2 \times 10^{-28}$).

		Loss at step		**Steps 100 → 600**		**Steps 600 → 1200**		
Subset	n	**100**	**600**	**Conflict**	$\boldsymbol{g_i \cdot \Delta\theta}$	**Conflict**	$\boldsymbol{g_i \cdot \Delta\theta}$	$\boldsymbol{A}$ **($\times 10^{-3}$)**
Clean	2,835	0.681	0.577	37.0%	−0.032	33.7%	−0.035	+0.16
Bottom Adv_e tail	2,836	0.695	0.721	49.3%	−0.002	38.8%	−0.021	+2.79
Top Adv_e tail	2,841	0.711	0.808	51.7%	+0.011	44.8%	+0.014	+6.18
Cleared	4,959	0.700	0.648	44.9%	−0.012	37.7%	−0.023	+2.76
Confirmed	3,869	0.704	0.925	**56.7%**	**+0.020**	**50.1%**	**+0.034**	**+12.21**
p-value				1.6×10^{-57}	1.9×10^{-71}	5.2×10^{-41}	1.2×10^{-35}	< 0.005

confirmed contradictions already conflict with the upcoming parameter update $\Delta\theta = \theta_{600} - \theta_{100}$ far more often than clean records (56.7% vs. 37.0%, $p = 1.6 \times 10^{-57}$), with the metric-only bottom- and top-Adv_e tails in between (49.3% and 51.7%). Confirmed and clean records differ slightly in step-100 gradient norm ($\|g_i\| = 7.93$ vs. 7.35), but the conflict gap survives matching on either loss or norm: within matched step-100 loss deciles, confirmed records conflict at 56.7% versus 42.6% for clean records (Cochran–Mantel–Haenszel $p = 2.0 \times 10^{-34}$), and within matched gradient-norm deciles at 56.7% versus 38.2% ($p = 1.1 \times 10^{-53}$). Most directly, arbitrator-cleared records from the same $|Adv_e - \text{median}(Adv_e)|$ ranking, with the same step-100 loss (0.700 vs. 0.704) and gradient norm (7.94 vs. 7.93), conflict at only 44.9% ($p = 3.2 \times 10^{-28}$). In this $100 \to 600$ window, pairwise gradient alignment A is already mildly elevated across every flagged cohort (+0.0010 for confirmed contradictions, +0.0016 for arbitrator-cleared records, and +0.0004 and +0.0015 for the bottom- and top-Adv_e tails, versus +0.0001 for clean records; all $p < 0.005$), so at step 100 it is the conflict fraction rather than A that singles out confirmed contradictions. By step 600, confirmed contradictions continue to conflict with $\theta_{1200} - \theta_{600}$ far more often than clean records (50.1% vs. 33.7%, and 28.8% on preferred twins) while exhibiting 76× higher pairwise gradient alignment ($A = +12.21 \times 10^{-3}$ vs. $+0.16 \times 10^{-3}$ on clean records, 95% CI $[-0.1, +0.4] \times 10^{-3}$).

Retraining arms. All arms in Table 2 train Qwen3.5-9B with DPO from scratch for one full epoch of 1,254 steps with batch size 128, $\beta = 0.05$, and learning rate 5×10^{-6}. We report the step-1,200 checkpoint for consistency with the other evaluations. The guardrail $\text{OOK}(n_i) > 0.9$ exempts 2,409 rare prompts from deletion (39 of which are confirmed training errors). *Uncleaned* keeps all 160,490 valid pairs. *Sanitized* removes the 3,830 unguarded confirmed contradictions, leaving 156,660 pairs. *Metric-only* removes the 8,344 unguarded pairs among the 8,500 in the $\approx 2\sigma$ tail of $|Adv_e - \text{median}(Adv_e)|$, leaving 152,146 pairs. *Repaired* flips $y^+ \leftrightarrow y^-$ on all 2,890 directional inversions (including 34 guarded prompts; flipping deletes nothing) and drops the 974 unguarded pairs in which both responses are faulty, leaving 159,516 pairs. On the Repaired test split, the Repaired arm ranks 50 more pairs correctly than Uncleaned. Of these, 48 come from the 8,344 test pairs that are not confirmed errors and 2 from the 142 repaired inversions. For Metric-only, 40 of the 45 additional pairs come from test pairs outside the confirmed errors. The other Repaired run (seed 1, earlier trainer build matching Sanitized) reaches 72.54% on the inversions and 80.41% on the majority inversions (Table 13).

Five-seed replication under continued training. Table 13 reports both full-from-scratch Repaired runs (seed 1 on the pre-packing DDP build alongside Sanitized, and seed 2 on the packed DDP build alongside Uncleaned and Metric-only), and binary accuracy on the 142 directional inversions is underpowered with a single seed per build (§4.5). To test whether the gain is robust to seed variation under a strictly identical trainer build, we ran a 10-run replication (5 seeds per arm) under the packed DDP LoRA trainer. Unlike Table 2, which trains from scratch, this replication resumes from a shared step-1,000 checkpoint and continues to step 1,254 on either the repaired or the uncleaned corpus, evaluating at steps 1,100, 1,200, and 1,254. Table 14 reports the results. Averaged over

the three checkpoints, every repaired seed exceeds every uncleaned seed on the repaired directional inversions (minimum 71.13% vs. maximum 69.48%). Complete rank separation of this kind yields $p = 2/\binom{10}{5} = 0.0079$ under a two-sided exact permutation test, which is the smallest p-value attainable with five seeds per arm. On the full Repaired Test Split, where only 1.67% of pairs are affected, the accuracy difference is small ($+0.15\%$), but the continuous preference margin rises consistently across seeds ($+0.0381$ nats, $p = 0.016$).

Table 13: Complete full-from-scratch Qwen3.5-9B DPO evaluation at step 1,200 across all HH-RLHF test splits, reporting reward accuracy (%) and DPO loss in nats (in parentheses), along with both seeds of the Repaired arm (seed 1: pre-packing trainer build matching Sanitized; seed 2: packed trainer build matching Uncleaned and Metric-only; parenthesized loss shown for the higher-accuracy seed in each row). *Inversions* ($n = 142$) and *Maj. Inversions* ($n = 97$) evaluate the flipped inversions among *Confirmed Err.* ($n = 191$) and *Maj. Errors* ($n = 118$), respectively. *Gain (B / U)* is the accuracy gain of the row-best arm over Base and Uncleaned.

Eval Split	n	Base	Uncleaned	Sanitized	Metric-only	Repaired (s1 / s2)	Gain (B / U)
Full Raw	8,535	68.54% (0.578)	68.45% (0.575)	68.76% (0.575)	68.79% (0.577)	68.55% / **69.96%** (**0.573**)	**+0.42%** / **+0.51%**
Sanitized	8,344	69.26% (0.569)	69.19% (0.566)	69.53% (0.565)	69.67% (0.567)	69.43% / **69.76%** (**0.562**)	**+0.50%** / **+0.57%**
Repaired	8,486	69.18% (0.570)	69.18% (0.567)	69.57% (0.566)	69.71% (0.567)	69.48% / **69.77%** (**0.563**)	**+0.59%** / **+0.59%**
Inversions	142	64.79% (0.635)	69.01% (0.623)	71.83% (0.609)	**72.54%** (0.570)	**72.54%** (**0.567**) / 70.42%	**+7.75%** / **+3.52%**
Maj. Inversions	97	74.23% (0.547)	76.29% (0.534)	75.26% (0.527)	79.38% (0.484)	**80.41%** (**0.469**) / 77.32%	**+6.19%** / **+4.12%**
Confirmed Err.	191	62.83% (0.673)	63.87% (0.664)	64.92% (0.660)	**69.63%** (0.618)	**69.63%** (**0.606**) / 65.97%	**+6.81%** / **+5.76%**
Maj. Errors	118	73.73% (0.562)	73.73% (0.553)	74.58% (0.538)	78.81% (0.500)	**80.51%** (**0.481**) / 76.27%	**+6.78%** / **+6.78%**

Table 14: Five-seed-per-arm continued-training replication (steps 1,000 $\rightarrow$ 1,254) on Qwen3.5-9B. Values are mean $\pm$ sample standard deviation across seeds; p-values are two-sided exact seed-permutation tests over all $\binom{10}{5} = 252$ assignments.

Evaluation split	Metric	Repaired	Uncleaned	Difference (p)
Repaired inversions ($n = 142$)	Accuracy, 3-ckpt mean	$71.92 \pm 0.73\%$	$68.31 \pm 0.84\%$	$+3.62\%$ (0.0079)
	Accuracy, step 1,200	$72.11 \pm 1.18\%$	$67.46 \pm 2.18\%$	$+4.65\%$ (0.0159)
	Accuracy, step 1,254	$71.83 \pm 1.07\%$	$68.45 \pm 0.57\%$	$+3.38\%$ (0.0079)
Repaired Test Split ($N = 8{,}486$)	Accuracy, 3-ckpt mean	$69.50 \pm 0.15\%$	$69.35 \pm 0.18\%$	$+0.15\%$
	Margin (nats), 3-ckpt mean	$+0.6644$	$+0.6262$	$+0.0381$ (0.0159)