ELICITDOCTOR: ROBUST MULTI-TURN EVIDENCE ELICITATION IN PSYCHIATRIC DIALOGUE UNDER LOW-DISCLOSURE PATIENT RESPONSES

Anonymous authors
Paper under double-blind review

ABSTRACT

Psychiatric assessment is a multi-turn evidence-elicitation process in which clinically relevant information must be recovered from incomplete or guarded self-reports. Existing doctor-agent evaluations give limited attention to low disclosure: even a relevant question may receive a vague, partial, or refusing response, leaving the requested information unresolved. We study this challenge in a disclosure-controlled interaction environment constructed from MDD-5K source dialogues and DAIC-family interviews. Source-grounded patient role-play varies disclosure while preserving the separation between hidden case information and doctor-visible dialogue. We propose *ElicitDoctor*, a belief-guided GRPO method that combines short-term feedback on how the observed reply resolves the current question with long-term value learned from cumulative inquiry returns. Together, these signals guide adaptive follow-up that addresses unresolved information and accounts for progress beyond the immediate response. Experiments assess patient role-play quality, evidence recovery, and independent diagnostic judgment. Results show that low disclosure limits evidence acquisition and that belief-guided training improves evidence recovery under these conditions.

1 INTRODUCTION

Psychiatric assessment requires eliciting cues about mood, sleep, interest, and daily functioning over multiple turns (Yao et al., 2022; Seo & Lee, 2024; Yin et al., 2025). The doctor must identify what remains unknown, ask an appropriate question, and determine whether the reply resolves it. We study psychiatric dialogue as *evidence elicitation*, where inquiry quality matters alongside final reasoning (Wei et al., 2018; Long & Wei, 2026).

Medical dialogue research studies sequential symptom collection and active question selection, from task-oriented policies to LLM doctor agents (Wei et al., 2018; Peng et al., 2018; Xu et al., 2019; Feng et al., 2026). Doctor-R1 learns strategic inquiry through interaction rewards (Lai et al., 2026); evidence-elicitation evaluations distinguish information collection from diagnostic reasoning (Long & Wei, 2026). How should inquiry adapt when a relevant question receives a valid but uninformative answer? The policy must assess resolution and the potential for later progress.

In psychiatric dialogue, replies may be vague, partial, minimizing, deflecting, or refusing. Concern about judgment, stigma, and difficulty verbalizing internal states are possible contributors, not explanations for every reply (Bell et al., 2011; Clement et al., 2015; Luminet et al., 2021). Cognitive and emotional factors can also affect reporting accuracy, motivating clarification (Qin et al., 2025). We treat uncertain answers as unresolved information without assigning deception or noncooperation to the patient. *Low disclosure* denotes interactions in which a valid response provides limited usable evidence. The doctor must choose whether respectful clarification, a concrete example, a related question, or a topic change is warranted. Persistent repetition after a boundary is not successful elicitation.

Figure 1 illustrates this decision: from the same vague sleep reply, the coverage-oriented path advances to interest, whereas ElicitDoctor first clarifies a concrete morning experience. This response-dependent inquiry poses two learning challenges: recognizing immediate resolution and valuing

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

questions whose benefit emerges through subsequent interaction. Explicit boundaries may instead require redirection or stopping.




Figure 1: **Asking about a topic need not recover its evidence.** Illustrative paths from the same vague sleep reply: the upper path advances to interest; the lower path clarifies sleep before following up on an ambiguous interest response.

Our controlled environment uses MDD-5K dialogues synthesized from anonymized clinical cases and DAIC-family interviews (Yin et al., 2025; Gratch et al., 2014; Ringeval et al., 2019). Source-derived profiles supply hidden case information; the doctor sees only the dialogue. A stateful controller governs patient role-play under Zero (no imposed withholding), Mild, and Moderate disclosure. Source-derived targets measure evidence recovery; patient role-play quality is assessed separately from doctor ability.

We propose *ElicitDoctor*, a belief-guided group relative policy optimization (GRPO) method addressing these two learning challenges. The *short-term belief reward* provides direct feedback from the observed patient reply: a frozen tracker compares how fully the same question is answered before and after the reply, alongside topic exploration and interaction costs. The *long-term belief reward* accumulates Short rewards for the current question and subsequent turns under a fixed follow-up policy. A value model learns candidate-question rankings from these returns and supplies a predicted Long score. Combining observed immediate feedback with this expanded-horizon prediction rewards local clarification without overlooking questions that enable later progress. The doctor and belief tracker do not directly receive hidden evidence targets or gold diagnostic labels (Section 2).

Our evaluation separates patient role-play quality, evidence acquisition, feedback-component behavior, and independent diagnostic judgment (Section 3).

The main contributions are summarized as follows:

- We formulate low-disclosure psychiatric dialogue as response-dependent evidence elicitation and construct a source-grounded interaction environment in which clinically relevant questions need not obtain informative answers.
- We propose *ElicitDoctor*, a belief-guided GRPO method combining observed short-term question-resolution rewards with a learned long-term score of cumulative inquiry returns.
- We characterize evidence acquisition under restricted disclosure and examine whether elicited dialogues support independent diagnostic judgment, distinguishing patient role-play quality from doctor ability.

2 ELICITDOCTOR: LEARNING ADAPTIVE INQUIRY

ElicitDoctor learns to adapt its next question when a patient's reply leaves relevant information unresolved. Its training framework comprises three stages (Figure 2). First, a disclosure-controlled patient simulator provides an interactive environment for inquiry. Second, a frozen belief tracker assigns short-term rewards to patient replies, and simulated continuations provide long-term reward targets for training a value model. Finally, belief-guided GRPO combines the observed Short reward with the frozen value model's Long signal to update the doctor policy. This design gives feedback both on immediate clarification and on the value of a question that becomes apparent only through subsequent interaction.




Figure 2: **ElicitDoctor training framework.** (a) A hidden profile and disclosure condition govern patient role-play. (b) Discounted Short rewards from simulated continuations supervise the value model. (c) Candidate questions receive immediate and predicted long-term rewards for group-relative policy updates. Snowflakes/flames denote frozen/trainable modules; Equation 5 specifies group normalization.

2.1 PATIENT SIMULATOR: DISCLOSURE-CONTROLLED INTERACTION

We view consultation as partially observed sequential inquiry. For case i, a source-derived profile h_i and disclosure condition α_i are hidden from the doctor; the patient controller also maintains a private disclosure state z_{it}. At turn t, the doctor observes only the dialogue history $x_t = (q_{<t}, r_{<t})$ and asks one natural-language question,

$$q_t \sim \pi_\theta(\cdot \mid x_t). \tag{1}$$

The patient response r_t extends the visible history to x_{t+1}. Profile-specific recovery targets E_i and downstream labels y_i are reserved for evaluation, not given to the doctor or its training reward. Neither the next question nor the patient response has a unique reference answer. The complete access contract appears in Appendix B.1.

Figure 2(a) implements this interaction in two steps. **Initialization** combines a source-derived patient profile with a disclosure condition to configure the private disclosure controller. Zero permits question-relevant facts without imposed withholding; Mild and Moderate impose increasing restrictions. These conditions describe interaction difficulty, not illness severity.

During **role-play**, a question interpreter reads the doctor-visible history and current question to identify the requested information. Private source lookup identifies eligible facts, and the stateful controller determines what may be disclosed. An LLM role-player expresses the permitted content

as a patient reply, which extends the visible history for the doctor's next decision. The controller constrains unsupported clinical detail and maintains refusal or termination boundaries across turns. Consequently, a clinically relevant question may still receive an uncertain, partial, or refusing response. This loop lets the doctor learn whether to clarify the unresolved request, explore another topic, or stop. All policies use the same simulator interface without access to its hidden profile or disclosure state. Controller details and patient instructions are in Appendices B.1 and F.3.

2.2 BELIEF-GUIDED REWARD LEARNING

Belief tracker and short-term reward. The immediate signal evaluates how much the patient's response resolves the information requested by a candidate question. As shown in the Short branch of Figure 2(c), a frozen tracker B_ϕ evaluates the same question q_t before and after observing its response r_t:

$$b^-_{t,q_t} = B_\phi(x_t, q_t), \qquad b^+_{t,q_t} = B_\phi(x_t, q_t, r_t), \quad b \in \Delta^{\{\text{UNKNOWN,ABSENT,LIMITED,SUFFICIENT}\}}. \tag{2}$$

The states distinguish no answer (UNKNOWN), an explicit negative resolving the queried phenomenon (ABSENT), a partial answer (LIMITED), and an otherwise adequate answer (SUFFICIENT). An explicit relevant denial belongs to ABSENT, not an additional sufficient-answer category; refusal is neither denial nor resolution. For example, "I am not sure" leaves a sleep question unresolved, while a concrete account of waking early can clarify it. The tracker supports its belief with quoted Patient spans. This is a question-resolution belief, not a diagnostic belief; it receives neither the hidden profile nor the diagnostic label.

We map the belief to a resolution utility $U(b) = b_{\text{ABSENT}} + \eta b_{\text{LIMITED}} + b_{\text{SUFFICIENT}}$ and measure immediate progress as $e_t = U(b^+_{t,q_t}) - U(b^-_{t,q_t})$. The implemented partial-answer weight is $\eta = 0.5$. To balance clarification with exploration, a separate term $d_t = |A_t \setminus A_{<t}|/|\mathcal{T}|$ rewards newly asked topics from the fixed topic registry $\mathcal{T}$, where A_t denotes topics identified in the current question and $A_{<t}$ those previously asked. The short-term belief reward is

$$R_{\text{short},t} = d_t + N_t e_t - C_t. \tag{3}$$

Here N_t gates resolution improvement to new information, clarification, or correction; no-fact replies and termination receive no belief-gain credit. C_t assigns doctor-side costs to exact repetition, refusal, consecutive refusals, and termination, reflecting blocked acquisition or lost interaction opportunities. A patient's refusal remains legitimate: the cost encourages productive, boundary-respecting inquiry, not disclosure against the patient's wishes. Topic exploration is an auxiliary incentive and can earn d_t without evidence recovery; this training reward is therefore distinct from ECR. Routing and response metadata enter reward bookkeeping, not the tracker. Cost definitions and tracker instructions are in Appendices C.2 and F.4.

Value model and long-term reward. An initial question may yield little immediate information yet create an opportunity for later clarification. Figure 2(b) estimates this longer-horizon value through simulated continuations. Starting from history x_t and candidate q_t, a fixed follow-up policy interacts with the same patient simulator, and the frozen tracker supplies Short rewards at each turn. For M matched patient seeds and at most K rewarded turns, the long-term belief reward target is

$$R_{\text{long}}(x_t, q_t) = \frac{1}{M} \sum_{m=1}^{M} \sum_{k=0}^{K_m - 1} \gamma^k R^{(m)}_{\text{short},t+k}. \tag{4}$$

Here γ discounts later rewards, and $K_m \le K$ accommodates patient termination. Long includes the root question at $k = 0$: it extends Short's reward horizon rather than providing independent supervision. Short supplies observed immediate feedback, while Long predicts cumulative value spanning the current and subsequent turns; the combined signal is not a future-only return.

The value model $V_\psi(x_t, q_t)$ encodes the visible history and candidate question using Qwen3-8B with a trainable LoRA adapter and scalar head. Within each history, rollout-return differences define candidate preferences for a weighted pairwise logistic loss; ties and statistically weak comparisons are excluded. We freeze the trained model and use its score for group-relative Long feedback, avoiding multi-turn lookahead during policy updates. Because training prioritizes ordering rather than return regression, this is a learned cumulative-value ranking score, not a calibrated return estimate or optimal future value. Pair construction and loss are detailed in Appendix C.2; the value-model instruction is in Appendix F.4.

2.3 BELIEF-GUIDED GRPO UPDATE

The final stage combines the two reward horizons to optimize question generation (Figure 2(c)). Question-only SFT initializes the inquiry policy; the reported staged MDD training first learns with Short feedback and then adds Long feedback. At each history x_t, the policy samples G questions $\{q_t^g\}_{g=1}^G$ sharing the visible history and initial patient state, with matched patient randomness. The simulator returns a response for each question, enabling observed Short feedback. In parallel, the frozen value model predicts the Long score from (x_t, q_t^g) alone.

We standardize each signal within the candidate group before combining them. Let $z_{x_t}(\cdot)$ denote group standardization; the advantage for candidate g is

$$A_t^g = z_{x_t}(R_{\text{short},t}^g) + \lambda z_{x_t}(V_\psi(x_t, q_t^g)). \tag{5}$$

The coefficient λ controls the Long contribution, and a zero-variance component contributes zero. A question-level clipped GRPO objective uses these advantages, with a KL penalty against a frozen reference and an entropy term encouraging candidate diversity (Shao et al., 2024). The simulator, tracker, and value model remain frozen during policy optimization. Only the doctor policy generates questions at inference.

Neither the doctor nor the tracker directly receives evaluator-side target inventories or gold labels. The simulator uses private source facts to answer questions, while reward arithmetic uses resolution and interaction metadata rather than recovery-target scores. Removing Long gives *w/o Long*; removing direct Short gives *w/o Short*, whose value supervision still derives from Short returns. The full loss, stage initialization, and exploratory scope are in Appendix C; component-comparison rules are in Appendix E.2.

3 EXPERIMENTS

Our primary evaluations use MDD-5K and DAIC-family interviews, which provide distinct evidence targets and downstream psychiatric classification tasks. Three questions organize the study: the quality of low-disclosure patient role-play, the effect of low disclosure on evidence acquisition, and the diagnostic usefulness of elicited dialogues. We compare Zero, Mild, and Moderate disclosure and assess boundary costs alongside evidence recovery.

3.1 DATASETS AND EVALUATION SETUP

MDD-5K provides Chinese consultations labelled F32 (depressive episode) or F41 (other anxiety disorders); we map source-dialogue cues into diagnosis-oriented evidence targets (Yin et al., 2025). DAIC-WOZ and E-DAIC provide interview-based depression-screening cases; their evidence targets are PHQ-8 item responses and their labels are control or depressed (Gratch et al., 2014; Ringeval et al., 2019). The inventories are evaluated separately and are not independently verified clinical profiles. Case counts, split composition, and target construction are in Appendices A.1–A.2.

All variants of one case stay in the same split. MDD uses case-disjoint splits; E-DAIC evaluation retains cross-corpus participant overlap and is not patient-disjoint generalization (Appendix A.1). We compare four closed-source LLM doctors with Qwen3-8B Base, SFT, ElicitDoctor, *w/o Long* (Short-only), and *w/o Short* (Long-only) (Yang et al., 2025). Zero allows question-relevant facts without imposed withholding; Mild and Moderate restrict disclosure. Short-only uses the reward in Section 2.2; Long-only and full use the value component defined in Section 2.2. Model settings, training lineage, and paired uncertainty are detailed in Appendices D.1, C.2, and D.5.

Training settings. Short/Long signals have equal weights after group standardization (1:1; $\lambda = 1$). Long uses $H = 6$ rewarded turns, including the current turn, with $\gamma = 0.99$; historical H4 runs are distinguished in Appendix C.2.

Evidence recovery. Evidence Coverage Rate (ECR) is the percentage of a case's fixed source-derived targets recovered in the doctor-visible dialogue. Credit is binary and deduplicated; merely asking or authorizing disclosure earns none. ECR measures recorded recovery, not diagnostic importance or clinical sufficiency. The exact computation, scoring limitations, handling of failed or early-ended interviews, and boundary-cost definitions are in Appendix D.

3.2 RQ1: How Faithfully Does the Simulator Portray Low-Disclosure Patients?

Low-disclosure behavior. The simulator exhibits a consistent shift toward less direct disclosure on both datasets. As shown in Figure 3, direct/partial replies decrease from 25.6% to 13.5% on MDD and from 34.0% to 16.7% on DAIC between Zero and Moderate, while explicit topic refusals rise from zero to 6.5% and 12.3%, respectively. Interactional replies also become more frequent. Under restricted disclosure, patients provide fewer direct clinical details and more often negotiate the interaction or decline a topic, leaving the doctor to adapt its next question. The figure summarizes patient reply forms across three disclosure conditions. Response-category definitions and annotation agreement are provided in Appendix B.3.




Figure 3: **Observed patient reply forms.** Each bar contains 480 replies from 20 profiles. *Not recorded* denotes missing source information, not withholding; rules: Appendix B.3.

Table 1: **Patient quality (1–5).**

	Flash		Nano	
Dimension	Raw	Sim.	Raw	Sim.
MDD-5K				
Grounding	4.05	4.00	4.90	4.67
Continuity	4.45	3.99	5.00	4.93
Relevance	4.80	3.74	5.00	4.43
Naturalness	4.50	3.10	4.95	4.30
Boundary	NA	4.04	NA	4.16
DAIC-family				
Grounding	3.80	4.28	3.60	4.80
Continuity	4.00	4.15	4.05	4.93
Relevance	NA	3.84	NA	4.63
Naturalness	3.85	3.17	3.90	4.21
Boundary	4.00	4.09	4.67	4.19

Fidelity and interaction quality. Simulated replies retain high source consistency, while naturalness varies across datasets and judges. Table 1 reports simulated grounding scores of 4.00/4.67 on MDD and 4.28/4.80 on DAIC under Flash/Nano. Both judges rate Raw MDD as more natural: Raw/Sim. scores are 4.50/3.10 for Flash and 4.95/4.30 for Nano. Review explanations flag repeated or scripted phrasing. On DAIC, Raw/Sim. scores are 3.85/3.17 for Flash and 3.90/4.21 for Nano. Two judges compare Raw and simulated records from the same cases across five dimensions. NA denotes unavailable or inapplicable ratings: Raw DAIC lacks interviewer questions for relevance scoring; Raw MDD contains no applicable boundary events. Counts and reference-comparison details are in Appendix B.2; scoring anchors are in Appendix F.6.

3.3 RQ2: Can Adaptive Inquiry Recover Evidence under Low Disclosure?

We evaluate evidence recovery under low disclosure and its progression over dialogue turns. Closed-source doctor prompts encourage clinical-topic coverage and switching topics when inquiry is blocked; ElicitDoctor learns adaptive inquiry through belief-guided training. Table 2 reports Zero, Mild, and Moderate ECR, with a separate Mild–Moderate Mean for each dataset. Evaluation settings and local-policy scope are in Appendices D.1 and E.1.

Low disclosure increases the difficulty of evidence acquisition. Table 2 shows that all four closed-source LLMs have lower ECR from Zero to Mild and again to Moderate on both datasets. Under Moderate, ECR ranges from 12.92–24.25% on MDD and 23.29–55.34% on DAIC. **Reduced disclo-**

Table 2: **Evidence recovery under different disclosure conditions.** ECR (%) on MDD-5K and DAIC-family. Mean averages Mild and Moderate, excluding Zero. *Full estimates and †DAIC Long estimates are interim; scope: Appendix E.1.

	MDD-5K				DAIC-family			
Doctor policy	Zero	Mild	Moderate	Mean	Zero	Mild	Moderate	Mean
Closed-source LLMs								
DeepSeek V4 Pro	47.46	34.15	24.25	29.20	83.16	70.06	55.34	62.70
gpt-5.6-terra	36.62	27.53	17.40	22.47	70.21	50.11	41.78	45.95
Ali/qwen3.8-flash	46.29	23.77	15.32	19.54	74.60	49.49	34.25	41.87
GPT-5-nano	33.78	19.25	12.92	16.08	33.50	28.31	23.29	25.80
Qwen3-8B-based policies								
ElicitDoctor*	50.39	15.76	13.42	14.59	89.32	65.74	54.32	60.03
w/o Long	42.22	12.29	7.57	9.93	87.33	63.75	50.00	56.88
w/o Short†	48.02	14.29	9.26	11.78	88.42	61.79	47.38	54.59
SFT	24.45	9.70	5.22	7.46	93.52	58.55	40.96	49.76
Base	19.53	4.55	2.41	3.48	99.59	59.48	42.11	50.80

sure consistently limits recoverable information in these runs, despite instructions encouraging clinical-topic coverage.

Belief-guided training improves low-disclosure recovery on both datasets. The interim full ElicitDoctor policy reaches 15.76% and 13.42% ECR under Mild and Moderate on MDD, compared with SFT's 9.70% and 5.22%. **Its low-disclosure Mean is 14.59%, versus 7.46% for SFT.** On DAIC, Full reaches 65.74% and 54.32%, with Mean 60.03% versus SFT's 49.76%. Interim recovery estimates and training lineage are distinguished in Appendix E.1.

Turn-wise curves reveal acquisition speed and sustained recovery. Figure 4 plots mean cumulative ECR under Mild and Moderate. On DAIC, DeepSeek V4 Pro rises from 29.91% at turn 8 to 62.70% at turn 24, whereas GPT-5-nano moves from 20.89% to 25.80%. The former continues accumulating evidence later in the dialogue, while the latter flattens earlier. **Additional turns do not yield comparable information gains across these runs.** Full checkpoints, AUC, and cohort details are in Appendix E.2.




Figure 4: **Turn-level evidence recovery under low disclosure.** Closed-source Base doctors on MDD-5K and DAIC-family; curves average Mild and Moderate equally at each turn. Final scores match Table 2; early terminations carry forward and technical failures are excluded.

3.4 RQ3: Do Elicited Dialogues Support Independent Diagnosis?

A fixed official Flash evaluator classifies the visible interviews of four closed-source doctors under Zero, Mild, and Moderate, separating elicitation from the doctor's own diagnostic ability (Long & Wei, 2026). It receives no terminal diagnosis, hidden profile, or source label. ECR and F1 use the same valid dialogues within each group; cohort rules are in Appendix E.3.

Higher recovery accompanies better depression identification on DAIC. Figure 5 shows higher Depressed F1 with increasing ECR from Moderate to Mild and Zero for all four doctors. DeepSeek

V4 Pro's ECR rises from 55.34% to 83.16%, alongside Depressed F1 from 63.87% to 75.00%. These group-level associations do not establish a causal effect of coverage. Macro-F1 and class-wise results are reported in Appendix E.1.




Figure 5: **Evidence recovery and depression identification on DAIC-family.** ECR versus Depressed F1 under a fixed Flash evaluator; lines connect disclosure conditions for each doctor. Counts and class-wise scores: Appendix E.3.

The relationship depends on the diagnostic task. On MDD, Qwen3.8-Flash reaches 46.99% Macro-F1 at 46.29% ECR under Zero, versus 54.89% at 15.32% ECR under Moderate. Both tasks force binary choices, but DAIC distinguishes control from depressed using PHQ-8-oriented evidence, whereas MDD distinguishes F32 from F41. A possible explanation is that limited disclosure leaves class-discriminating details unresolved on MDD; more general evidence need not resolve that choice. Class-wise results and historical local-policy comparisons are in Appendix E.1.

4 Related Work

Active inquiry and interactive diagnosis. Early task-oriented systems learn which symptom or test to request next through supervised, graph-based, or reinforcement-learning policies (Wei et al., 2018; Peng et al., 2018; Xu et al., 2019; Xia et al., 2020). LLM doctor agents extend this choice to natural-language questioning and multi-turn interaction (Feng et al., 2026; Hsu et al., 2026). Doctor-R1 combines an interactive environment, consultation/decision-making rewards, and prior trajectories to learn strategic inquiry (Lai et al., 2026). Evidence-elicitation evaluation distinguishes obtaining evidence from reasoning over available evidence (Long & Wei, 2026). Our focus is response-dependent acquisition under low disclosure: a relevant question may remain unresolved after a vague, partial, deflective, or refusing reply. ElicitDoctor combines direct feedback on question resolution with learned cumulative-return rankings to guide subsequent inquiry.

Psychiatric dialogue and patient simulation. D4 and DiagESC study depression-oriented dialogue, MDD-5K synthesizes diagnostic conversations from anonymized clinical cases, and DAIC-family corpora contain human–computer interviews about psychological distress (Yao et al., 2022; Seo & Lee, 2024; Yin et al., 2025; Gratch et al., 2014; Ringeval et al., 2019). These sources do not themselves isolate how disclosure variation changes inquiry. LLM patient simulators support repeatable mental-health training, including cognitive-behavioral-therapy role-play (Wang et al., 2024). Patient-misreporting studies motivate clarification (Qin et al., 2025); clinical studies associate non-disclosure with stigma and communication context (Bell et al., 2011; Clement et al., 2015; Levy et al., 2018). We vary disclosure over a fixed source-grounded case to study adaptive inquiry, not to infer an individual patient's motivations or model the clinical causes of non-disclosure.

5 Limitations

Our scope is controlled simulation, not clinical deployment. MDD source dialogues are themselves synthesized; source-derived targets and disclosure levels do not establish clinical truth or population-level patient behavior. We examine Mild and Moderate with a Zero control. MDD diagnosis and

DAIC screening differ, and DAIC retains participant overlap. Shared controllers may favor particular question styles; LLM reviews assess source consistency and interaction quality, not clinical realism. Cumulative ECR can retain credit for weakened or later-contradicted evidence. Question-resolution feedback is a proxy for useful inquiry, and refusal/termination costs do not distinguish every appropriate ending from avoidable breakdown. Long targets depend on the fixed continuation strategy and a finite rollout horizon. Recovery does not guarantee diagnostic benefit; the two capabilities are assessed separately.

6 Conclusion

Low-disclosure replies make topic coverage an incomplete account of clinical inquiry. We introduce a controlled environment for this problem and ElicitDoctor, a belief-guided GRPO method combining observed question-resolution rewards with learned cumulative-value scores. The results show restricted evidence acquisition under low disclosure and improved recovery with belief-guided training. Independent diagnosis remains a distinct test of the resulting dialogue's usefulness. These findings concern simulated interaction and require validation before clinical use.

AI Use Statement

AI tools assisted method implementation, manuscript translation, and editing. Generative models produce synthetic patient replies, assess question-resolution beliefs and diagnostic predictions, and review dialogue quality and response forms. These model-based assessments are described with their inputs and scoring procedures in the paper; they are not human clinical annotations. The authors retain responsibility for the implementation, analyses, and manuscript.

Ethics Statement

We use released corpora and conduct no intervention with real patients. External LLM APIs, including third-party routes, process source-derived text for simulation and assessment. Data access and redistribution follow the source datasets' restrictions. The system is a research simulation, not a clinical diagnostic service.

References

Robert A. Bell, Peter Franks, Paul R. Duberstein, Ronald M. Epstein, Mitchell D. Feldman, Eduardo Fernandez y Garcia, and Richard L. Kravitz. Suffering in silence: Reasons for not disclosing depression in primary care. *The Annals of Family Medicine*, 9(5):439–446, 2011. doi: 10.1370/afm.1277. URL https://www.annfammed.org/content/9/5/439.

Sarah Clement, Oliver Schauman, Tanya Graham, Francesca Maggioni, Sara Evans-Lacko, Nikolaos Bezborodovs, Craig Morgan, Nicolas Ruesch, June S. L. Brown, and Graham Thornicroft. What is the impact of mental health-related stigma on help-seeking? a systematic review of quantitative and qualitative studies. *Psychological Medicine*, 45(1):11–27, 2015. doi: 10.1017/S0033291714000129. URL https://doi.org/10.1017/S0033291714000129.

Yichun Feng, Jiawei Wang, Lu Zhou, Zhen Lei, and Yixue Li. DoctorAgent-RL: A multi-agent collaborative reinforcement learning system for multi-turn clinical dialogue. In *ICASSP 2026 - 2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 16952–16956. IEEE, 2026. doi: 10.1109/ICASSP55912.2026.11460976. URL https://doi.org/10.1109/ICASSP55912.2026.11460976.

Jonathan Gratch, Ron Artstein, Gale Lucas, Giota Stratou, Stefan Scherer, Angela Nazarian, Rachel Wood, Jill Boberg, David DeVault, Stacy Marsella, David Traum, Albert Rizzo, and Louis-Philippe Morency. The distress analysis interview corpus of human and computer interviews. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation*, 2014. URL https://aclanthology.org/L14-1421/.

Hsin-Ling Hsu, Zizheng Wang, Donghua Zhang, Nai-Chia Chen, Jerry Wang, Jun-En Ding, Chia-Hsuan Hsu, Guoan Wang, Feng Liu, Fang-Ming Hung, Chenwei Wu, and Liyue Shen. MedAction: Towards active multi-turn clinical diagnostic LLMs, 2026. URL https://arxiv.org/abs/2605.07305.

Yunghwei Lai, Kaiming Liu, Ziyue Wang, Weizhi Ma, and Yang Liu. Doctor-R1: Mastering clinical inquiry with experiential agentic reinforcement learning. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=vQGHTyL0Jw.

Andrea Gurmankin Levy, Aaron M. Scherer, Brian J. Zikmund-Fisher, Knoll Larkin, Geoffrey D. Barnes, and Angela Fagerlin. Prevalence of and factors associated with patient nondisclosure of medically relevant information to clinicians. *JAMA Network Open*, 1(7):e185293, 2018. doi: 10.1001/jamanetworkopen.2018.5293. URL https://jamanetwork.com/journals/jamanetworkopen/fullarticle/2716996.

Zhuohan Long and Zhongyu Wei. Strong reasoning isn't enough: Evaluating evidence elicitation in interactive diagnosis. In *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 27559–27575, San Diego, California, United States, 2026. Association for Computational Linguistics. URL https://aclanthology.org/2026.findings-acl.1372/.

Olivier Luminet, Kristy A. Nielson, and Nathan Ridout. Cognitive-emotional processing in alexithymia: An integrative review. *Cognition and Emotion*, 35(3):449–487, 2021. doi: 10.1080/02699931.2021.1908231. URL https://pubmed.ncbi.nlm.nih.gov/33787442/.

Yu-Shao Peng, Kai-Fu Tang, Hsuan-Tien Lin, and Edward Y. Chang. REFUEL: Exploring sparse features in deep reinforcement learning for fast disease diagnosis. In *Advances in Neural Information Processing Systems*, 2018. URL https://papers.nips.cc/paper_files/paper/2018/hash/b5a1d925221b37e2e399f7b319038ba0-Abstract.html.

Lang Qin, Yao Zhang, Hongru Liang, Adam Jatowt, and Zhenglu Yang. Listening to patients: Detecting and mitigating patient misreport in medical dialogue system. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 2650–2664, 2025. doi: 10.18653/v1/2025.findings-acl.135. URL https://aclanthology.org/2025.findings-acl.135/.

Fabien Ringeval, Björn Schuller, Michel Valstar, Nicholas Cummins, Roddy Cowie, Leili Tavabi, Maximilian Schmitt, Sina Alisamir, Shahin Amiriparian, Eva-Maria Messner, Siyang Song, Shuo Liu, Ziping Zhao, Adria Mallol-Ragolta, Zhao Ren, Mohammad Soleymani, and Maja Pantic. AVEC 2019 workshop and challenge: State-of-mind, detecting depression with AI, and cross-cultural affect recognition. In *Proceedings of the 9th International on Audio/Visual Emotion Challenge and Workshop*, pp. 3–12, 2019. doi: 10.1145/3347320.3357688. URL https://arxiv.org/abs/1907.11510.

Seungyeon Seo and Gary Geunbae Lee. DiagESC: Dialogue synthesis for integrating depression diagnosis into emotional support conversation. In *Proceedings of the 25th Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pp. 686–698, 2024. doi: 10.18653/v1/2024.sigdial-1.59. URL https://aclanthology.org/2024.sigdial-1.59/.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models, 2024. URL https://arxiv.org/abs/2402.03300.

Ruiyi Wang, Stephanie Milani, Jamie C. Chiu, Jiayin Zhi, Shaun M. Eack, Travis Labrum, Samuel M. Murphy, Nev Jones, Kate V. Hardy, Hong Shen, Fei Fang, and Zhiyu Chen. PATIENT-ψ: Using large language models to simulate patients for training mental health professionals. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 12772–12797, 2024. doi: 10.18653/v1/2024.emnlp-main.711. URL https://aclanthology.org/2024.emnlp-main.711/.

Zhongyu Wei, Qianlong Liu, Baolin Peng, Huaixiao Tou, Ting Chen, Xuanjing Huang, Kam-fai Wong, and Xiangying Dai. Task-oriented dialogue system for automatic diagnosis. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, pp. 201–207, 2018. doi: 10.18653/v1/P18-2033. URL https://aclanthology.org/P18-2033/.

Yuan Xia, Jingbo Zhou, Zhenhui Shi, Chao Lu, and Haifeng Huang. Generative adversarial regularized mutual information policy gradient framework for automatic diagnosis. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020. URL https://ojs.aaai.org/index.php/AAAI/article/view/5456.

Lin Xu, Qixian Zhou, Ke Gong, Xiaodan Liang, Jianheng Tang, and Liang Lin. End-to-end knowledge-routed relational dialogue system for automatic diagnosis. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2019. URL https://ojs.aaai.org/index.php/AAAI/article/view/4722.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025. URL https://arxiv.org/abs/2505.09388.

Binwei Yao, Chao Shi, Likai Zou, Lingfeng Dai, Mengyue Wu, Lu Chen, Zhen Wang, and Kai Yu. D4: a Chinese dialogue dataset for depression-diagnosis-oriented chat. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 2438–2459. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.emnlp-main.156. URL https://aclanthology.org/2022.emnlp-main.156/.

Congchi Yin, Feng Li, Shu Zhang, Zike Wang, Jun Shao, Piji Li, Jianhua Chen, and Xun Jiang. MDD-5k: A new diagnostic conversation dataset for mental disorders synthesized via neuro-symbolic LLM agents. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 25715–25723, 2025. doi: 10.1609/aaai.v39i24.34763. URL https://ojs.aaai.org/index.php/AAAI/article/view/34763.

A Data and Evidence Construction

A.1 Sources and Data Splits

MDD-5K provides Chinese diagnostic dialogues synthesized from anonymized clinical cases (Yin et al., 2025). These are source dialogues, not verbatim human consultations. We retain single-label F32/F41 cases and keep all variants and disclosure conditions of a case in the same split. DAIC-WOZ supplies training and development participants; evaluation uses the full labelled E-DAIC inventory. The 142 participant identifiers shared across the corpora are retained, so DAIC measures corpus-level performance, not patient-disjoint generalization.

The test inventories contain 2,249 MDD diagnosis-related targets and 1,752 DAIC targets. Counts of targets and counts of participants are distinct: Zero, Mild, and Moderate yield 324 MDD and 657 DAIC test profile–condition pairs per policy. Mild/Moderate alone yield 216 and 438 pairs, respectively. Training/development inventory counts in Table 3 remain provisional. No test dialogue is used for policy training or checkpoint selection.

Table 3: **Detailed data inventory.** Targets are evaluator-side evidence units, not independent clinical ground truth. Training/development target counts remain provisional.

Source	Split	Profiles	Targets	Low-disclosure pairs	Labels
MDD-5K, ICD-10					
MDD-5K	Train	379	5,631	758	206/173
MDD-5K	Dev	54	791	108	29/25
MDD-5K	Test	108	2,249	216	59/49
DAIC-family, PHQ-8					
DAIC-WOZ	Train	107	856	214	77/30
DAIC-WOZ	Dev	35	280	70	23/12
E-DAIC	Test	219	1,752	438	154/65

MDD labels are F32/F41; DAIC-family labels are Ctrl/Dep. Low-disclosure pairs are profiles $\times$ two levels (Mild/Moderate), not counts of generated training dialogues. Including Zero yields 324 MDD and 657 DAIC test profile–condition pairs per policy. The test recovery denominators use the 2,249/1,752-target inventories.

A.2 Source-Grounded Evidence Representation

MDD. Each selected target is linked to a patient span, its surrounding question, and a diagnosis-oriented topic/detail. Selected spans are checked against the source dialogue, with Patient wording as the factual reference. Canonical topic labels organize retrieval without authorizing additional facts. These profiles reconstruct source content rather than independently annotating the patient's complete condition.

DAIC. DAIC profiles use the eight PHQ-8 item responses rather than a freely extracted biography. Each item preserves its frequency category and scope. An item combining difficulty sleeping and excessive sleep does not identify which alternative applies; a total screening score does not establish a specific symptom, duration, or cause. One missing training item is reconstructed from the total and other seven scores and is marked as derived, not directly observed.

Unknown and negative evidence. An explicit negative is different from an unasked or unrecorded detail. The construction preserves polarity, time, frequency, and alternatives. Duplicate targets receive no additional weight. A question requesting a detail outside the available source remains unresolved even when a broader related item is present. Source-grounded evidence defines the simulation's information inventory, not a guarantee of diagnostic sufficiency.

B Patient Simulation and Validation

B.1 Information Access and Disclosure

The doctor observes only the conversation and produces one natural-language question. The interpreter uses visible dialogue and a public topic ontology; private source lookup and disclosure control access the hidden profile. The realizer receives only authorized facts. Source labels are reserved for evaluation. The doctor and tracker do not receive target inventories; this access separation does not mean that the simulator and evaluation use unrelated source information. Training rewards use question resolution and interaction metadata, not evaluator recovery scores.

The controller separates what the source contains from what the patient currently discloses. Operational trust, topic readiness, fatigue, refusal history, and permission state determine the release of eligible facts. Zero removes imposed withholding but still requires a relevant question. The two low-disclosure levels, Mild and Moderate, modify disclosure difficulty, not disease severity. These variables encode simulation assumptions rather than measured psychological traits.

For an accepted request, the disclosure level is the highest level satisfying both trust and topic-readiness thresholds. Levels 0–4 permit at most 0, 0, 1, 1, and 2 atoms. Missing information, refusal, permission, and termination produce distinct responses. Table 4 specifies this controller; historical patient-interface differences are distinguished in Appendix D.1 rather than assumed to share every parameter. The configured trust changes are $+0.06$ for accepted supportive behavior, -0.10 for pressure, -0.12 for repetition after refusal, and -0.07 for unsupported assumptions. Fatigue increases by 0.015 per turn. Explicit boundaries constrain subsequent disclosure regardless of whether a source fact exists. An effect within this controller is not evidence that real patients respond identically.

Table 4: **Disclosure-controller configuration.** These are simulation parameters, not empirically calibrated patient traits.

Parameter	Mild	Moderate
Initial trust centre	0.68	0.54
Profile-specific jitter	± 0.03	± 0.03
Initial readiness offset	-0.02	-0.02
Level thresholds	.25/.35/.50/.68	.30/.42/.57/.72

Strict realization uses authorized textual surfaces; natural realization paraphrases the same authorized content in first person. The natural prompt preserves uncertainty, negation, temporal scope, and alternatives (Appendix F.3). Local checks enforce permitted IDs and boundary consistency, but do not establish semantic fidelity. Independent trajectory assessment is therefore necessary.

B.2 Full-Trajectory Assessment

We sampled 20 MDD-5K and 20 DAIC profiles. Crossing each profile with four doctor families and Zero, Mild, and Moderate conditions yielded 480 whole-dialogue packets (240 per dataset; no Severe condition). Two independent LLM judges, DeepSeek-V4-Flash and GPT-5-nano, received the visible dialogue and permitted source facts but not doctor identity, gold labels, ECR, or diagnostic predictions. This is a two-LLM audit, not human annotation. Three packets contain partial technical-failure trajectories; judges assessed only observed content.

The rubric distinguishes grounding, continuity, relevance, naturalness, and boundary/termination handling. Each judge assigns one anchored 1–5 score and a short reason per dimension to the observed whole dialogue; boundary handling may be not applicable. A legitimate refusal or unknown answer can receive a high score: cooperation and evidence quantity are not quality criteria. Scores are not collapsed into one overall index. Full anchors and judge instructions appear in Appendix F.6.

Each judge supplies 480 completed ratings (Table 5). Nano's three initially invalid outputs were completed through two format repairs and one supplemental reassessment; the reported means use the completed review, not first-pass-only ratings. The 40 profiles, rather than 480 correlated dialogues, are the distinct source cases. Judge means differ most for naturalness (3.13/4.26) and

continuity (4.07/4.93). Exact agreement across completed pairs is 74/480 for naturalness, 58/480 for continuity, and 146/480 for grounding. Nano also serves as a doctor baseline, so model-family self-preference cannot be excluded. Scores are independent LLM judgments, not calibrated clinical references or human adjudication.

Table 5: **Whole-dialogue patient review by dataset and disclosure.** Completed-review means on a 1–5 scale across four doctor families. G: grounding; C: continuity; R: relevance; N: naturalness; B: boundaries/termination (NA excluded). The number of valid packets is n; per-dimension B denominators vary because the event may be absent.

Judge	Dataset	Condition	n	G	C	R	N	B
Flash	MDD	Zero	80	3.99	3.98	3.45	2.99	3.94
		Mild	80	4.03	4.00	3.84	3.10	4.08
		Moderate	80	4.00	3.99	3.92	3.20	4.06
	DAIC	Zero	80	4.24	4.11	3.60	3.00	3.82
		Mild	80	4.33	4.19	3.94	3.21	4.16
		Moderate	80	4.28	4.15	3.99	3.29	4.25
Nano	MDD	Zero	80	4.70	4.97	4.47	4.28	3.89
		Mild	80	4.78	4.94	4.46	4.39	4.20
		Moderate	80	4.53	4.88	4.35	4.25	4.29
	DAIC	Zero	80	4.81	4.90	4.66	4.05	3.80
		Mild	80	4.81	4.90	4.59	4.25	4.32
		Moderate	80	4.78	4.97	4.64	4.34	4.36

Original-source reference. We additionally review the original records corresponding to the same 20 MDD and 20 DAIC profiles. Each source record is assessed once by each judge, yielding 80 completed reviews rather than duplicating sources across the 12 simulated doctor–condition combinations. Source paths, selected MDD dialogue variants, and file hashes are verified against the frozen profile provenance. Raw packets contain the original patient text and the same historical source-fact reference as their simulated counterparts, but no diagnostic labels, doctor-model identities, or fabricated controller states. MDD retains doctor–patient turn pairs; these DAIC sources contain participant-only ASR with timestamps, without interviewer questions.

The Raw review preserves the five scoring anchors, judge models, and generation settings of the simulation audit. Its instructions remove the "simulated Patient" designation and adapt to the available source format (Appendix F.6). DAIC Raw relevance is required to be NA because question–response fit cannot be assessed. Continuity concerns consistency across the observed participant utterances. Grounding checks agreement with represented source facts; details absent from the incomplete fact reference are not automatically fabrication. This internally derived reference does not independently validate clinical truth. Boundary scores use only explicit textual events, with missing controller state never treated as a violation.

Both judges supply 40 source-record reviews; one Nano output required a format-only repair without score changes. Table 6 gives means and boundary denominators. Simulated MDD dialogue has lower naturalness scores under both judges; DAIC differs by judge. Source length, ASR quality, missing interviewer context, and prompt adaptations make these descriptive comparisons, not isolated causal effects of simulation. MDD source records have no applicable boundary event; DAIC source boundary means have small, judge-dependent denominators.

Simulated boundary denominators are 202/195 on MDD and 227/211 on DAIC for Flash/Nano; the other dimensions each use 240 ratings per dataset and judge. This review checks visible patient behavior and source consistency, not target completeness or whether automatic ECR credit matches transcript support. The latter requires the separate scoring-audit protocol in Appendix D.3.

B.3 Patient Reply Forms

The descriptive response-form sample uses the same 20 MDD-5K and 20 DAIC profiles under Zero, Mild, and Moderate, but fixes the doctor to Qwen3.8-Flash. All 120 trajectories contain 24 patient turns (2,880 replies). DeepSeek-V4-Pro and DeepSeek-V4-Flash independently labeled the visible

Table 6: **Original-source patient-quality reference.** Completed-review means (1–5). Each judge reviews 20 records per dataset; G/C/R/N use 20 ratings except DAIC R, which is unavailable. B excludes NA and its applicable count is n_B.

Dataset	Judge	G	C	R	N	B	n_B
MDD-5K	Flash	4.05	4.45	4.80	4.50	NA	0
	Nano	4.90	5.00	5.00	4.95	NA	0
DAIC	Flash	3.80	4.00	NA	3.85	4.00	2
	Nano	3.60	4.05	NA	3.90	4.67	9

reply text; their initial six-class labels agreed on 89.2% of turns (Cohen's $\kappa = 0.821$). Figure 3 uses Pro labels combined with controller receipts, not the five-dimensional whole-dialogue judge scores above. The different doctor sampling designs prohibit a direct numerical comparison between the two audits.

To make the categories mutually exclusive, direct and partial replies are combined. A controller receipt of *not recorded* is separated from other vague replies; *detail not supported* remains vague. *Topic refusal* is reserved for a withheld-topic or declined-permission receipt. Open-invitation declines, permission acknowledgments, interaction responses, and "no other concern" replies are *interactional*, not topic refusals. Remaining redirections are *deflection*. These distinctions prevent an absent source fact or a request for clarification from being counted as deliberate refusal. Table 7 gives the exact descriptive distribution; each row has 480 replies. Percentages are over turns and are not independent-case confidence intervals.

The response-form distribution describes the simulator's observed portrayal, not the prevalence of these behaviors among real patients. Direct/partial replies decrease and explicit topic refusals increase under restricted disclosure, whereas other vague replies and deflections have no consistent monotonic trend. The *not recorded* category describes source availability, not a patient personality or a refusal to disclose. Adaptive doctor questions and within-profile dependence also prevent interpreting pooled turn counts as independent observations or as a matched-question effect.

Table 7: **Response forms by disclosure (%).** D/P: direct or partial; NR: source fact not recorded; OV: other vague; Int.: interactional; Ref.: explicit topic refusal; Def.: deflection.

Dataset	Condition	D/P	NR	OV	Int.	Ref.	Def.
MDD-5K	Zero	25.6	64.2	2.5	4.4	0.0	3.3
	Mild	21.5	61.3	3.3	9.8	3.5	0.6
	Moderate	13.5	59.2	1.9	16.9	6.5	2.1
DAIC	Zero	34.0	50.4	3.3	11.7	0.0	0.6
	Mild	19.4	49.6	2.3	17.9	10.4	0.4
	Moderate	16.7	47.7	1.9	21.2	12.3	0.2

C Method and Training Details

C.1 Initialization and Training Configuration

All local policies use Qwen3-8B. Base has no task-specific policy adaptation; SFT learns the next doctor question from visible history, balancing source-dialogue and simulated examples with loss on the doctor completion only. Table 8 describes this SFT recipe, not a retrospective specification of every historical checkpoint. The reported MDD SFT control uses checkpoint-100.

C.2 Immediate Feedback and Continuation Value

The belief tracker assesses the information available for the doctor's specific question using four states: UNKNOWN, ABSENT, LIMITED, and SUFFICIENT. A frozen Qwen3-8B assessor evaluates the visible history and question before and after the patient reply. Each assessment returns prob-

Table 8: **Question-only SFT configuration.** Historical checkpoint lineage is distinguished from the training recipe in the accompanying text.

Setting	Value
Original / simulated sampling mass	0.5 / 0.5
Maximum sequence length	5,120 tokens
Optimizer / learning rate	AdamW / 5×10^{-5}
Schedule / warmup	Linear / 0.03
Weight decay / gradient clipping	0 / 1.0
LoRA rank / scale / dropout	16 / 32 / 0.05
LoRA modules	Attention query/key/value/output and MLP gate/up/down projections
Batch per device / accumulation	1 / 32
Precision / maximum steps	BF16 / 600
Checkpoint intervals	Every 100 steps

abilities over the four states and up to two exact quotations from patient turns. Non-UNKNOWN assessments require supporting visible text. The post-reply assessment also identifies new information, clarification, correction, repetition, or no information. A negative answer counts as ABSENT only if it addresses the requested detail. The assessor receives no controller records, private profile facts, evidence IDs, or diagnosis labels (Appendix F.4).

The utility assigns weight $\eta = 0.5$ to LIMITED. Topic coverage d_t counts topics asked for the first time, as identified by the question interpreter, and normalizes this count by the number of topics in the fixed topic registry. A broad domain question does not automatically cover every topic in that domain. Topic routing and response type are used to compute the reward but are not inputs to the belief tracker or doctor policy.

ABSENT denotes an explicit negative answering the queried phenomenon; SUFFICIENT denotes other adequate answers. For "On how many mornings this week did you wake earlier than usual?", "None" resolves absence, "Sometimes" is limited, and "On four mornings" can be sufficient. Refusal is not symptom absence. Both absence and other sufficient answers have utility 1 because both resolve the question, not because they have the same clinical meaning.

For refusal, unknown, other no-fact replies, or termination, $N_t = 0$ regardless of changes in the assessed belief. The penalties are 0.15 for exact question repetition, 0.25 for refusal, an additional 0.40 for consecutive refusals, and 0.50 for termination. Termination does not also incur the current refusal penalty. First-time topic coverage can contribute to the reward even without new evidence; ECR counts committed evidence without partial credit. Invalid or unscorable belief assessments are excluded from policy updates.

The costs express the doctor's acquisition objective: refusal blocks a request, repeated refusals reduce productive continuation, and termination removes remaining opportunities. They do not label the patient's behavior as improper. Respecting refusal and changing course remains appropriate; simulator constraints and doctor instructions separately enforce boundaries. The costs do not distinguish every appropriate ending from an avoidable breakdown, a limitation of this utility. Topic novelty is an auxiliary exploration incentive, not recovery credit.

Continuation targets and value estimation. MDD targets average three predefined patient seeds with $\gamma = 0.99$. H4 and H6 use at most four and six rewarded turns, respectively, including the initial question. Each turn uses $d + N\Delta U - C$; the mean discounted return defines R_{long} and sample variance describes patient randomness. A fixed visible-history follow-up strategy handles partial replies, uncertainty, permission, and refusal without private source facts (Appendix F.4). Long includes immediate and subsequent rewards; Short and Long are direct feedback and expanded-horizon prediction, not independent supervision.

The value model uses Qwen3-8B's final input-token representation followed by LayerNorm and a scalar linear head. Rank-8 LoRA adapts the attention and MLP projections; the head and adapter are trainable. Fit and holdout cases are disjoint; holdout cases supply neither gradients nor epoch selection.

For distinct questions q_a, q_b sharing history x, let $\delta_{ab} = R_a - R_b$ and $s_{ab} = \mathrm{sign}(\delta_{ab})$. Duplicate questions and exact ties are excluded. MDD multi-seed models retain pairs satisfying $|\delta_{ab}|/\sqrt{v_a/n_a + v_b/n_b} \geq 1$, where v_a, v_b are sample return variances and $n_a = n_b = 3$; a nonzero difference with zero estimated variance passes. Let $\mathcal{P}$ denote the question pairs retained after these filters. The weighted logistic loss is

$$\mathcal{L}_{\mathrm{value}} = \frac{1}{|\mathcal{P}|} \sum_{(a,b)\in\mathcal{P}} \widetilde{w}_{ab} \log(1 + \exp\{-s_{ab}[V_\psi(x, q_a) - V_\psi(x, q_b)]\}) , \tag{6}$$

where $w_{ab} = \min(|\delta_{ab}|, 2)$ and $\widetilde{w}_{ab}$ divides this weight by its mini-batch mean. MDD H4/H6 use three epochs, learning rate 2×10^{-5}, and no optional mean-squared-error regression term. Scores are ranking surrogates, not calibrated returns. A positive affine rescaling using fit-set return statistics is applied at inference; group standardization removes this offset and scale. The head and adapter are frozen during GRPO.

C.3 Policy Optimization

For candidate question q_t^k, let $\rho_k = \pi_\theta(q_t^k \mid x_t)/\pi_{\mathrm{old}}(q_t^k \mid x_t)$. The ratio uses summed completion-token log probabilities, not per-token ratios. The clipped policy term is

$$\mathcal{L}_{\mathrm{pg}} = -\frac{1}{G} \sum_{k=1}^{G} \min\big(\rho_k A_t^k, \mathrm{clip}(\rho_k, 1-\epsilon, 1+\epsilon) A_t^k\big) . \tag{7}$$

Let $\ell_k, \ell_k^{\mathrm{ref}}$ denote current and reference completion log probabilities. The complete implemented objective is

$$\mathcal{L} = \mathcal{L}_{\mathrm{pg}} + 0.03\widehat{D}_{\mathrm{KL}} - 0.01\mathcal{H}_{\mathrm{cand}}, \qquad \epsilon = 0.2, \tag{8}$$

where $\widehat{D}_{\mathrm{KL}} = G^{-1} \sum_k [\exp(\ell_k^{\mathrm{ref}} - \ell_k) - (\ell_k^{\mathrm{ref}} - \ell_k) - 1]$. For entropy, equal question strings are grouped; a group's mass sums $\exp(\ell_k/L_k)$ over its occurrences, where L_k is completion length. Normalizing masses gives p_j and $\mathcal{H}_{\mathrm{cand}} = -\sum_j p_j \log p_j$. This is candidate-group entropy, not full-vocabulary entropy.

The Short stage starts from SFT with a frozen SFT reference. The reported full MDD H4/H6 stages start from the Short-trained step-72 policy and specify that stage-start policy as the frozen reference. These staged runs are not fresh, matched-initialization ablations. Each group has $G = 8$ questions sharing history and initial patient state. Advantages use population-variance standardization; constant components contribute zero. The reported H4 stage uses 72 optimizer updates and $\lambda = 1$.

D Experimental Setup and Evaluation

D.1 Models and Interaction Settings

The closed-source doctors are DeepSeek V4 Pro, GPT-5-nano, Ali/qwen3.8-flash, and gpt-5.6-terra, distinct from the local Qwen3-8B controls. Main recovery evaluation uses a 24-turn budget. Zero is interactive inquiry without imposed withholding, not diagnosis from a complete source record.

Historical closed-source results share recovery scoring but differ in patient configurations. Pro used strict realization; Nano used natural realization with a 2,048-token interpreter limit. Qwen/Terra used a 24,000-token limit; their historical records do not identify the wording mode. Cross-model gaps therefore cannot be attributed solely to doctor policy. Historical independent-diagnosis runs use Flash-family evaluators without uniform version identification; the separate official-Flash reassessment uses the forced-binary instruction in Appendix F.5.

Doctor prompts require one visible-history-grounded question without premature diagnosis (Appendix F.1). Patient, interpreter, and evaluator prompts are separate. The API configuration uses temperature 0 and output caps of 8,192 tokens for doctor/diagnosis and 2,048 for interpretation/patient generation. Historical run-specific exceptions are distinguished from these defaults; model names alone do not establish generation settings.

D.2 Evidence Recovery and Interaction Efficiency

Let E_i be profile i's fixed source-derived target inventory and V_{it} the committed evidence IDs mapped to that inventory at turn t. The cumulative recovered set and Evidence Coverage Rate (ECR) are

$$U_{iT} = \bigcup_{t=1}^{T} V_{it}, \qquad \mathrm{ECR}_i(T) = 100\frac{|U_{iT} \cap E_i|}{|E_i|}. \tag{9}$$

Each target is credited at most once. Committed evidence IDs are mapped to the fixed diagnosis-related target inventory before scoring, and ECR is averaged over valid interviews within each dataset and disclosure condition. Authorization alone does not count as recovery, and repeated mentions receive no additional credit.

Recovery is measured over $T = 24$ turns. After normal termination, the final ECR is carried forward to the remaining turns; technical failures are counted separately. The discrete recovery-curve area is

$$\mathrm{AUC}_i = \frac{1}{T}\sum_{t=1}^{T} \mathrm{ECR}_i(t), \qquad T = 24.$$

The low-disclosure curve assigns equal weight to Mild and Moderate:

$$\overline{\mathrm{ECR}}(t) = \frac{1}{2}\left[\overline{\mathrm{ECR}}_{\mathrm{Mild}}(t) + \overline{\mathrm{ECR}}_{\mathrm{Moderate}}(t)\right].$$

Each condition mean is computed over valid profiles. The same weighting is used for E_8, E_{24}, and AUC, with Zero reported separately. Values at turns 4, 8, 12, and 24 are taken from the same 24-turn trajectory to measure the timing of evidence acquisition.

A boundary opportunity consists of an explicit patient request to defer a topic or end the session, followed by a doctor response. Responses are assessed in context for inappropriate persistence. The boundary-violation rate is the number of inappropriate responses divided by the number of eligible boundary opportunities. Dialogues without an eligible opportunity are excluded from this denominator.

D.3 Independent Recovery-Scoring Audit

The recovery-scoring audit protocol compares the automatic set U_i with an independently annotated set H_i supported by the complete visible transcript. Precision is $|U_i \cap H_i|/|U_i|$ and recall is $|U_i \cap H_i|/|H_i|$; zero denominators are distinguished. Annotation separates missed paraphrases, unsupported specificity, polarity errors, and later contradictions. Reviewers do not see automatic scores or policy identity. This protocol is separate from the patient-quality review in Table 1; no scoring-audit result is inferred from those ratings.

D.4 Downstream F1

An independent evaluator predicts the source class from the visible interview. Its input excludes the collecting doctor's terminal diagnosis, hidden profile, evidence IDs, and source label. MDD uses F32/F41 labels, and DAIC uses control/depressed screening labels. The diagnosis instructions are given in Appendix F.5.

For each dataset and disclosure condition, class-wise F1 is computed from the source labels and independent predictions:

$$F1_c = \frac{2TP_c}{2TP_c + FP_c + FN_c}, \qquad \mathrm{MacroF1} = \frac{F1_{c_1} + F1_{c_2}}{2}.$$

Macro-F1 assigns equal weight to the two source classes. Zero, Mild, and Moderate are evaluated separately (Table 10).

For the full-information reference, the evaluator receives the original source text of the corresponding held-out profiles, with source labels and explicit final diagnoses masked. The evaluator, diagnosis prompt, and output rules are kept the same as in the interview-based evaluation.

D.5 Uncertainty and Paired Comparisons

Profile-bootstrap uncertainty retains each profile's policies and conditions together, with paired differences computed within dataset and condition. This preserves within-profile dependence; dialogue turns are not independent patients. Confidence intervals and significance claims require the corresponding episode-level paired analysis. Training-seed variation is distinct from test-profile uncertainty.

E Supplementary Results and Analyses

E.1 Downstream Evaluation and Association

Table 9 reports the uniform official-Flash forced-binary reassessment underlying Figure 5. These predictions are based only on frozen visible interviews and are matched to episode-level ECR. MDD diagnosis and DAIC screening have different source labels and are analyzed separately.

Table 9: **Uniform Flash binary diagnosis.** Class-wise F1 / Macro-F1 (%) on the same valid dialogues used for ECR: F32/F41 on MDD, control/depressed on DAIC.

Doctor	Zero	Mild	Moderate
MDD-5K: F32 / F41 / Macro			
DeepSeek V4 Pro	69.80/30.77/50.28	73.61/44.12/58.86	66.67/31.43/49.05
GPT-5.6-terra	68.92/32.35/50.64	67.13/35.62/51.37	71.62/38.24/54.93
Qwen3.8-Flash	67.11/26.87/46.99	68.97/36.62/52.79	70.34/39.44/54.89
GPT-5-nano	71.52/33.85/52.68	73.55/32.79/53.17	69.80/32.84/51.32
DAIC-family: Control / Depressed / Macro			
DeepSeek V4 Pro	83.72/75.00/79.36	79.84/71.19/75.51	68.78/63.87/66.33
GPT-5.6-terra	79.69/71.43/75.56	68.09/63.05/65.57	68.07/62.00/65.03
Qwen3.8-Flash	81.08/72.63/76.85	67.51/61.69/64.60	69.14/61.54/65.34
GPT-5-nano	69.49/64.36/66.92	58.56/57.41/57.98	51.58/50.69/51.14

Table 10 retains historical diagnosis results, including the local policies; its closed-source cells are not the uniform reassessment above. Local-policy scores use condition-level predictions rather than pooled summaries. The MDD H4 full-policy row is exploratory, not a final-policy result. These historical outputs are not substituted into the main association plot.

Table 10: **Historical independent diagnosis from elicited dialogues.** F1 (%; class 1/class 2/Macro): F32/F41 on MDD-5K, control/depressed on DAIC-family. The closed-source cells are not the uniform reassessment in Table 9. †Exploratory MDD H4.

(a) MDD-5K: F32/F41/Macro			
Dialogue policy	Zero	Mild	Moderate
DeepSeek V4 Pro	37.50/0.00/18.75	39.51/4.00/21.75	9.38/0.00/4.69
GPT-5-nano	11.43/0.00/5.71	6.56/0.00/3.28	0.00/0.00/0.00
Ali/qwen3.8-flash	6.06/0.00/3.03	6.45/0.00/3.23	0.00/0.00/0.00
gpt-5.6-terra	6.35/0.00/3.17	3.28/0.00/1.64	0.00/0.00/0.00
ElicitDoctor†	68.46/14.29/41.37	66.21/26.87/46.54	67.13/33.80/50.47
w/o Long	70.83/26.23/48.53	70.20/28.12/49.16	70.59/23.33/46.96
SFT	66.67/3.92/35.29	60.56/10.91/35.74	70.83/31.25/51.04
Base	69.44/4.00/36.72	62.59/0.00/31.29	67.53/4.00/35.77
(b) DAIC-family: control/depressed/Macro			
Dialogue policy	Zero	Mild	Moderate
DeepSeek V4 Pro	69.49/68.18/68.84	75.81/68.85/72.33	69.49/66.31/67.90
GPT-5-nano	69.49/64.36/66.92	58.56/57.41/57.98	51.58/50.69/51.14
Ali/qwen3.8-flash	73.77/67.01/70.39	66.95/61.39/64.17	68.33/61.62/64.97
gpt-5.6-terra	75.81/68.42/72.11	66.67/62.80/64.73	70.29/64.32/67.31
w/o Long	65.38/54.90/60.14	80.41/62.07/71.24	73.19/55.00/64.09
SFT	82.26/0.00/41.13	82.57/0.00/41.29	82.48/2.99/42.73

Model-specific direct-source controls. Table 11 retains the earlier full-source tests by four closed-source models and Qwen3-8B Base/SFT (108 MDD and 219 DAIC cases per model). MDD input is the frozen source consultation; DAIC input is the participant's original ASR transcript, without unavailable interviewer turns. Each named model makes its own diagnosis, so these results cannot fill the policy-independent full-information row of Table 10, which requires the same frozen evaluator used for interactive dialogues on the same held-out cases. The Qwen3.8-Flash direct and interactive routes also differ. Invalid outputs remain errors in the two-gold-class F1 calculation. Full-source access is an informative comparison, not a theoretical performance ceiling or a Zero-disclosure trajectory.

Table 11: **Full-source direct diagnosis.** Class-wise F1 and two-gold-class Macro-F1 (%). Each model predicts from the original record rather than an elicited dialogue; these are not independent-evaluator results.

	MDD-5K			DAIC-family		
Model	F32	F41	Macro	Ctrl.	Depr.	Macro
DeepSeek V4 Pro	77.85	51.52	64.68	86.16	63.33	74.75
GPT-5-nano	74.83	31.03	52.93	77.70	61.25	69.47
gpt-5.6-terra	76.71	52.17	64.44	84.52	62.50	73.51
Qwen3.8-Flash (DashScope)	78.15	49.23	63.69	84.97	65.15	75.06
Qwen3-8B SFT	75.86	51.43	63.65	83.67	65.71	74.69
Qwen3-8B Base	73.47	43.48	58.47	85.71	68.61	77.16

MDD formal controls. SFT checkpoint-100 and Base ECR are reported by condition in Table 2. Table 10 scores Zero/Mild/Moderate predictions over all 108 MDD attempts per condition, rather than substituting pooled four-condition F1. Pooled F1 cannot be decomposed into class-wise condition scores. H4 also has 108 attempts per condition but is exploratory, not a matched final-policy effect.

The MDD *w/o Short* H6 row reports 48.02%, 14.29%, and 9.26% ECR under Zero, Mild, and Moderate, with a low-disclosure Mean of 11.78%. The Full row contains interim recovery estimates of 50.39/15.76/13.42%, with Mean 14.59%; these do not replace the historical H4 diagnostic predictions. The DAIC Long H6 row likewise contains interim estimates of 88.42/61.79/47.38%, with Mean 54.59%. Natural denotes the Zero control in these summaries. Interim cohorts need not be identical to completed formal-test cohorts, so these comparisons are descriptive rather than matched final-policy effects. No diagnostic F1 is inferred from recovery summaries.

DAIC Base and SFT recovery. Table 2 reports Base ECR of 99.59/59.48/42.11% and SFT checkpoint-100 ECR of 93.52/58.55/40.96% under Zero/Mild/Moderate. Their Mild–Moderate means are 50.80% and 49.76%, respectively. These recovery summaries do not establish episode-level correspondence with the historical diagnostic predictions; recovery–diagnosis association requires matched dialogue identifiers.

The DAIC Short-only recovery summary is 87.33/63.75/50.00% under Zero/Mild/Moderate, with low-disclosure Mean 56.88%. The Full summary is 89.32/65.74/54.32%, with Mean 60.03%. These recovery summaries do not update historical diagnostic predictions; linking recovery and diagnosis requires the same episodes.

Self versus independent diagnosis. Table 12 reports two-class results under Zero, Mild, and Moderate. Self uses the collecting doctor; Eval uses an independent evaluator. Neither is substituted for the other. Table 13 reports the corresponding closed-source interview completion counts.

Table 12: **Extended diagnosis results.** Two-class Macro-F1 (%) for Self/Eval under Zero, Mild, and Moderate.

Doctor	Zero	Mild	Moderate
MDD-5K: Self / Eval			
DeepSeek V4 Pro	13.33/18.75	14.67/21.75	3.17/4.69
GPT-5-nano	6.76/5.71	1.67/3.28	0.00/0.00
Ali/qwen3.8-flash	14.86/3.03	3.28/3.23	0.00/0.00
gpt-5.6-terra	10.14/3.17	3.12/1.64	0.00/0.00
DAIC-family: Self / Eval			
DeepSeek V4 Pro	67.65/68.84	69.18/72.33	62.10/67.90
GPT-5-nano	61.17/66.92	60.63/57.98	54.70/51.14
Ali/qwen3.8-flash	70.39/70.39	63.30/64.17	63.30/64.97
gpt-5.6-terra	70.82/72.11	66.01/64.73	64.22/67.31

Table 13: **Interview completion.** Completed / attempted closed-source interviews under Zero, Mild, and Moderate; a completed interview need not have a valid terminal diagnosis.

Doctor	Zero	Mild	Moderate
MDD-5K			
DeepSeek V4 Pro	107/108	106/108	107/108
GPT-5-nano	108/108	108/108	108/108
Ali/qwen3.8-flash	108/108	108/108	108/108
gpt-5.6-terra	108/108	108/108	108/108
DAIC-family			
DeepSeek V4 Pro	213/219	215/219	206/219
GPT-5-nano	219/219	219/219	219/219
Ali/qwen3.8-flash	219/219	219/219	219/219
gpt-5.6-terra	219/219	219/219	219/219

E.2 Acquisition Timing and Supplementary Analyses

Figure 4 shows the recovery curves of four closed-source models, computed from scored dialogue prefixes. Table 14 reports their ECR at turns 8 and 24 and the average area under the 24-turn recovery curve. Each metric averages Mild and Moderate with equal weights.

Table 14: **Closed-source model acquisition summaries.** E_8/E_{24} are ECR at turns 8/24; AUC averages the 24-turn recovery curve. Metrics average Mild and Moderate equally, excluding Zero.

	MDD-5K			DAIC-family		
Doctor policy	E_8	E_{24}	AUC	E_8	E_{24}	AUC
DeepSeek V4 Pro	13.33	29.20	17.33	29.91	62.70	40.65
gpt-5.6-terra	12.08	22.47	14.77	27.34	45.95	32.90
Ali/qwen3.8-flash	10.93	19.54	13.14	25.43	41.87	29.69
GPT-5-nano	10.76	16.08	11.96	20.89	25.80	21.32

Disclosure-specific adaptation. For policy p and low-disclosure condition a, the contrast $\mathrm{ECR}_{p,\mathrm{Zero}} - \mathrm{ECR}_{p,a}$ measures the loss relative to normal disclosure. The change in the ElicitDoctor–SFT gap between Zero and a tests whether a method advantage is specific to low disclosure. Absolute levels accompany these contrasts: a small drop from an already weak Zero score is not evidence of robustness. Topic coverage and recovery are separate; asking about a topic does not imply obtaining its evidence.

Reward-component recovery trajectories. Turn-wise component comparisons require held-out evaluation trajectories under a common simulator configuration, scoring definition, and 24-turn bud-

get; training rollouts are excluded. Within a dataset, comparison uses the same profile set across policies and both Mild and Moderate. Eligibility requires a valid completed trajectory for each compared policy–condition pair; planned, completed, excluded, and failed counts accompany the matched subset. Paired bootstrap intervals resample profiles, retaining all policy and condition observations together (Appendix D.5).

At turn t, mean cumulative ECR is computed within each condition and then averaged equally over Mild and Moderate. Normal termination carries the final recovered value forward; technical failures are reported separately, not treated as patient termination. Checkpoints at turns 4, 8, 12, and 24, interval gains, and the average recovery-curve area distinguish faster acquisition from a higher final level (Appendix D). Matching test cases does not remove differences in training initialization or update budget; endpoint summaries alone establish no temporal component effect.

E.3 Robustness and Dialogue-Level Interpretation

Coverage and judgment. Figure 5 uses the four closed-source Base doctor cohorts under Zero, Mild, and Moderate, reassessed by the same official Flash model with a fixed forced-binary prompt. Episode identity, source hashes, and gold labels are checked before joining recovery records to predictions. Mean ECR and class-wise F1 use the same valid dialogues within each doctor–condition group. Qwen3-8B, SFT, and ElicitDoctor are not included because corresponding uniform reassessments are not represented in this joined dataset. Historical diagnosis results in Table 10 use different scoring records and cannot be used as substitutes.

There are 2,605 valid DAIC dialogues and 1,292 valid MDD dialogues. For DeepSeek V4 Pro, Zero/Mild/Moderate counts are 213/215/206 on DAIC and 107/106/107 on MDD; the other doctors have 219 and 108 valid dialogues per condition, respectively. Original interview failures exclude 23 DAIC and four MDD episodes. No unresolved diagnostic failures remain in these groups. Valid cohorts can differ across disclosure conditions, so connected points are condition-level summaries rather than matched-case effects.

Across the 12 DAIC doctor–condition groups, Spearman correlations of mean ECR with Depressed F1 and Macro-F1 are 0.888 and 0.867. Each doctor's Depressed F1 rises with ECR from Moderate through Mild to Zero. Macro-F1 is not strictly monotonic for Qwen3.8-Flash: it is 64.60% under Mild and 65.34% under Moderate. The corresponding MDD ECR–Macro-F1 correlation is -0.476, and no common monotonic pattern holds across doctors. These pooled group associations combine disclosure and doctor differences; correlated conditions and heterogeneous historical generation settings preclude treating the 12 points as independent causal evidence. No ECR threshold or point exclusion is selected to strengthen the association.

F Prompts and Assessment Rubrics

This section provides doctor, patient, belief-tracker, value-model, and diagnostic instructions, together with the five-dimensional review rubric. Verbatim prompts, translations, and explanatory summaries are identified explicitly. Bracketed inputs stand for dialogue data. Historical diagnosis instructions are distinguished from forced-binary reassessment; no private test dialogue is reproduced.

F.1 Doctor Prompt

The following is the complete English doctor instruction. The Chinese MDD template has the same one-question, visible-history, and boundary-respecting structure. The conversation history is appended as the interaction proceeds.

> You are a mental-health clinician speaking one-to-one with the person in this consultation. Always speak directly to the person as their clinician, with patience, respect, sincerity, and without judgment. Your aim is to help the person feel safe and understood while gradually learning about their present concerns, emotional experience, mental and physical state, effects on daily life, and relevant experiences, so that a careful judgment can be made after the interview ends.

> At each turn, continue only from what the two speakers have already said. Do not assume experiences the person has not expressed, and do not treat a possibility mentioned in your question as a fact the person has endorsed. Explore one thing at a time. Do not turn the conversation into a checklist of symptoms or combine several questions, and do not give a diagnosis before the interview ends.
>
> If the person is vague, brief, hesitant, or not ready to say more, naturally acknowledge what they have expressed and narrow the follow-up to one small, easy-to-answer question. You may ask permission, begin with the part that feels easier to discuss, invite one concrete example, or offer a small number of simple ways to answer. Do not pressure, interrogate, or demand complete disclosure. If the person clearly does not want to discuss a topic, respect that boundary and defer it or move to another appropriate topic. Only when the visible conversation suggests a possible immediate safety risk should you prioritize a brief, direct, and nonjudgmental safety question.
>
> If repeated follow-ups yield no further information, do not infer confusion, cognitive impairment, or an inability to communicate from that alone. Acknowledge the limit and gently offer another relevant clinical topic or a meaningfully easier way to discuss it. Do not keep making the same question more specific, or substitute questions about names, the room, weather, or hearing just to obtain an answer. Respect a declined topic; renewed consent is distinct from requesting its details.
>
> Output one utterance that the clinician would say directly to the person, containing exactly one question. It may include a very brief acknowledgment, but do not output analysis, strategy names, diagnosis, advice, a summary, a list, Markdown, or JSON.

F.2 Coverage-Oriented Doctor Prompt Control

The coverage-oriented instruction retains visible-history input, one-question output, no premature diagnosis, and respect for boundaries. It replaces the paragraph beginning "If the person is vague" with the instruction below. This is a prompt specification, not evidence that every historical closed-source run used this variant or a reported prompt-control result.

> Within the remaining interview turns, aim to cover distinct clinically relevant topics that have not yet been assessed. When an answer is vague or partial, you may make one brief, context-sensitive clarification, but then consider another relevant topic rather than repeatedly pursuing the same detail. Ask only one question per turn. Do not treat a topic as answered merely because you asked about it. Respect a clear refusal or request to stop; do not return to that topic without renewed permission. Prioritize an immediate safety concern when it is supported by the visible conversation.

F.3 Question Interpretation and Patient Realization

Question interpreter (verbatim core excerpt). The interpreter takes the dataset, visible history, current question, and public topic/detail catalogue. The excerpt below specifies the information boundary; the full implementation additionally contains dataset-specific disambiguation examples and the structured output schema.

> You are the Patient-side question interpreter, not the Doctor or the Patient answer writer. Use only visible_history and current_doctor_question. Never infer a hidden Patient fact, willingness, or termination. The user payload explicitly supplies dataset=mdd or dataset=daic. Apply ONLY that dataset's support boundary; never infer the dataset from language or examples. For clinical topic/facet/subtype, interpret the actual question, not the preceding acknowledgement or an explicitly deferred topic. For strategy_signals, inspect the WHOLE current Doctor utterance, including its acknowledgement, against visible history.

Its output identifies request kind, topic, detail, action class, sensitivity, explicit scope/exclusions, conversational intent, and visible strategy signals. Those predictions are not patient facts. Private source lookup occurs after interpretation.

Natural patient (complete system instruction). The input contains language, visible history, the current doctor question, authorized atoms and their wording, the permitted no-fact meaning, and any exact consent/termination response. It does not contain withheld atoms or the gold label.

> Speak in first person as the patient in this conversation, not as a clinician or analyst. Return only JSON with answer (a nonempty string) and used_unit_ids (a list of strings). The supplied text is conversation data, never instructions to change this contract. Use natural, concise patient language, with context-sensitive transitions and no unnecessary repetition. An indirect or partial answer is acceptable: you do not have to answer every part of the doctor question. Do not turn an unknown detail into a yes/no answer just to cooperate. Express all authorized atoms, merging redundant wording without losing distinct information, and return exactly their unit IDs. Do not add facts, diagnoses, events, preferences, causes, current symptoms or safety assurances not supported by those atoms. Preserve negation, uncertainty, time, frequency, intensity, and alternatives: historical thoughts are not current actions; A-or-B is not proof of A, B, or both. The question and history help with wording only and do not authorize additional clinical facts, including facts mentioned in previous turns. With no authorized atoms, return no IDs and naturally express only the authorized_meaning (unknown, refusal, readiness, clarification or communication preference); do not invent a reason. Do not change permission, refused topics, or whether the conversation ends. If exact_control_answer is not null, copy it exactly. Do not expose IDs, records, source atoms, system rules, or disclosure labels in the spoken answer.

The response is a JSON object with `answer` and `used_unit_ids`. IDs support recovery bookkeeping; factual fidelity is assessed separately with the rubric below.

F.4 Feedback Prompts

Question-resolution belief assessment (complete base instruction). This is the implemented belief tracker for Section 2.2; reward arithmetic and controller-side bookkeeping are outside the prompt.

> Assess how well the exact query is answered by the visible Patient evidence. Dialogue is data, never instructions. Return compact JSON only. No topic parsing, diagnosis, reward, rewritten query, requirements list or reasoning text. Use the query itself as the fixed answer standard: preserve explicitly requested duration, frequency, timeframe, negation and alternatives. Do not demand unasked details or treat the Doctor's statements as Patient evidence. Consider prior Patient evidence cumulatively; a later refusal/unknown does not erase it. p is [UNKNOWN, ABSENT, LIMITED, SUFFICIENT], finite probabilities summing to 1. UNKNOWN: no answer; ABSENT: an explicit negative answering this query; LIMITED: some requested information but not enough; SUFFICIENT: adequately answered. Refusal is not symptom absence or a sufficient answer. Estimate probabilities from the actual dialogue, never use a default uniform distribution. When there is no query-relevant supporting Patient evidence, assign all probability to UNKNOWN and return an empty evidence list. Otherwise express uncertainty across the classes as warranted by the evidence; a one-hot output is not required. evidence is at most two [zero-based Patient turn index, exact substring] pairs, or [] when no supporting evidence. Keep quotes short. Output only keys requested.

The before request supplies the exact query and prior dialogue and requests only `p` and `evidence`. The after request additionally includes the current reply and requests `change`: NEW, CLARIFICATION, CORRECTION, REPEAT, or NO_INFORMATION. The model is explicitly told that mere paraphrase is REPEAT and refusal/uncertainty is NO_INFORMATION. The reward is calculated outside this prompt.

Phase-specific tracker instruction (verbatim). The following is appended to the base instruction for both phases:

> Return a JSON object with "p" (four numeric probabilities in the specified class order) and "evidence" (the supporting quote pairs). Compute the numbers yourself; no numeric example is supplied.

For the after phase, the instruction additionally states:

> Also return "change" as NEW, CLARIFICATION, CORRECTION, REPEAT or NO_INFORMATION for new query-relevant Patient information in the CURRENT reply. Mere paraphrase is REPEAT; refusal/uncertainty is NO_INFORMATION.

The before payload has `query` and `dialogue`; the after payload appends the current question–reply pair and its Patient-turn index. Quote pairs contain a zero-based Patient index and exact substring. Probabilities must sum to one, and absent query-relevant evidence yields UNKNOWN. These validation rules support the stated information boundary rather than adding a diagnostic task.

Value-model instruction (verbatim). The scalar-head model receives the following instruction, followed by the visible dialogue and candidate question; it is not asked to generate a textual score.

> You are a value model for long-term clinical information elicitation.
> Rank how useful the candidate Doctor question is for this exact dialogue state.
> Focus on relative value among alternative next questions for the same state.
> Consider future information gain, topic coverage, repeated-question risk, refusal risk, and continued engagement.
> Return no text. The model hidden state will be used as a scalar ranking value.
> Visible dialogue:
> Doctor [index]: [doctor utterance]
> Patient [index]: [patient utterance]
> Candidate Doctor question:
> [candidate question]
> State-local ranking value:

Fixed MDD continuation strategy (instruction summary). The continuation worker uses DeepSeek-V4-Flash with a fixed visible-history instruction. Its decisions follow this ordered rule set: end after a request to stop or refusals of two different clinical topics; acknowledge a corrected premise without converting correction into symptom denial; follow up on a disclosed fact using one unknown detail; probe a named topic after consent without asking permission again; answer requests for clarification with one concrete low-burden question; after a topic refusal, offer a different named topic rather than asking the reason; simplify an initially uncertain reply, but switch to an unrefused low-burden topic after repeated uncertainty; accept explicit symptom denial; otherwise ask one unanswered clinical question. New entry topics are mood, energy, sleep, appetite, and daily functioning. Refused topics cannot be revisited through synonym or proxy questions.

The output contains `move`, `topic`, `patient_anchor`, and `question`. The anchor is an exact excerpt of the latest reply; only the question is spoken to the patient. End actions contain no question. A visible-history reminder repeats the latest Patient utterance and prior explicit refusals. These rules specify the fixed follow-up strategy used to generate Long targets, not the learned ElicitDoctor policy.

F.5 Independent Diagnosis Prompts

DAIC (complete English instruction).

> You are an independent evaluator reading a completed mental-health interview. Using only what the person actually stated in the visible interview, make the prediction for this DAIC-family screening task. You do not know and must not guess the interviewing model, disclosure condition, hidden profile, evidence identifiers, or gold label. Do not treat assumptions in the clinician's questions as facts stated by the person. This is a benchmark depression-screening prediction, not a clinical diagnosis.
> You must choose either depressed or control as prediction. If the visible evidence is limited, still choose the label better supported by the interview and lower confidence. The visible_evidence_summary may summarize only statements the person actually made.
> Output one valid JSON object with exactly these fields: {"prediction":"depressed or control","confidence":a number from 0 to 1,"visible_evidence_summary":["brief support drawn only from visible Patient statements"]}

MDD historical interview evaluation (English translation). This instruction permits an insufficiency output; two-source-class F1 treats that output as an error rather than a third gold class. It is distinct from the forced-binary reassessment below. The actual instruction is Chinese.

> You are an independent evaluator reading a completed mental-health interview. Judge this MDD-5K task using only what the patient actually expressed. You do not know and must not infer the interviewing model, disclosure condition, hidden profile, evidence identifiers, or gold label. Do not treat assumptions in doctor questions as patient facts.
>
> The prediction must be F32, F41, or insufficient_evidence. Choose F32 or F41 only when the patient's statements support that judgment and distinguish the two candidates. If symptom evidence is insufficient or cannot distinguish them, choose insufficient_evidence rather than forcing a binary choice. Do not diagnose solely from refusal, vague answers, a single nonspecific manifestation, or assumptions about class prevalence.
>
> Insufficient evidence does not mean healthy, control, or absence of disease. Unasked, unanswered, and unknown details do not establish symptom absence. Confidence is confidence in the selected output, including insufficiency, and does not replace the insufficient-evidence option. Summarize only visible patient statements; use an empty array if no support is available. Do not decide mechanically from dialogue length or a preset number of facts.
>
> Return only one JSON object with exactly: prediction (F32, F41, or insufficient_evidence), confidence (a number from 0 to 1), and visible_evidence_summary (an array of short statements supported by visible patient speech).

The Self templates instead address the doctor that has just completed the interview; within each dataset they retain the same label choices and visible-evidence restrictions. The MDD instruction has no fixed symptom-count or confidence threshold for insufficiency. This is an LLM judgment rule, not an independently validated evidence-sufficiency label.

MDD forced-binary reassessment (English translation). The unified official-Flash reassessment uses the frozen Chinese instruction below; it does not change the historical instruction or its outputs.

> You are an independent evaluator reading a completed mental-health interview. Judge the MDD-5K task using only what the participant actually expressed. You do not know and must not infer the interviewing model, disclosure condition, hidden profile, evidence identifiers, or gold label. Do not treat assumptions in doctor questions as participant facts.
>
> You must choose F32 or F41 as prediction. If visible information is insufficient, still select the label more consistent with the available dialogue and lower confidence. The visible evidence summary may describe only the participant's expressed content.
>
> Return one valid JSON object with exactly these fields: prediction (F32 or F41), confidence (a number from 0 to 1), and visible evidence summary (an array of brief statements supported by the participant's visible speech).

F.6 Full-Trajectory Quality Rubric

The following five-dimensional rubric assigns one score and short reason per dimension to the observed whole dialogue, not a per-turn score or overall quality average. Boundary/termination is NA when no relevant event occurs; Raw DAIC relevance has the separate missing-question exception specified below.

Grounding. **1:** Major invented or contradicted clinical fact, including fabricated risk or diagnosis. **2:** Clinically important unsupported detail or changed time, polarity, frequency, or severity. **3:** Minor unsupported expansion or imprecision without a major factual change. **4:** Source-faithful paraphrase preserving uncertainty; harmless stylistic inference only. **5:** Fully faithful to available source facts and explicit unknowns; no new clinical claims.

Continuity. **1:** Major factual contradiction across turns without a correction or explanation. **2:** Material inconsistency in facts, references, or established boundaries. **3:** Minor continuity lapse; intended meaning remains recoverable. **4:** Consistent history and references, with harmless ambiguity. **5:** Fully consistent; appropriate elaboration or explicit correction is not a contradiction.

Relevance. **1:** Materially unrelated response presented as an answer; repeated clear misunderstanding. **2:** Substantially misinterprets the question or communication request. **3:** Understandable

connection but a minor material mismatch remains. **4:** Appropriate direct/indirect response, uncertainty, boundary, or plausible topic shift. **5:** Contextually fitting response at the chosen disclosure level; refusal can score 5.

Naturalness. **1:** Incoherent fragments or severe clinician/simulator/metadata persona leakage. **2:** Materially robotic, repetitive, or disjointed expression obstructs understanding. **3:** Understandable patient speech with noticeable scripted or awkward expression. **4:** Natural patient speech with minor stylistic awkwardness. **5:** Coherent, context-appropriate patient expression; short, hesitant speech can score 5.

Boundaries and termination. **1:** Major unauthorized disclosure or explicit refusal/end state materially contradicted. **2:** Substantial mismatch between expressed boundary and recorded patient action/state. **3:** Minor ambiguity distinguishing a closed topic from session termination. **4:** Appropriate disclosure boundaries and refusal/end handling, with minor wording ambiguity. **5:** Faithful boundary handling, including firm refusal or final termination without further cooperation.

Whole-dialogue judge instruction (verbatim). This instruction is followed by the five scoring-anchor sets above.

> Read the complete conversation, but rate ONLY the simulated Patient, not Doctor quality or diagnosis accuracy. Each row is Doctor first, then Patient. Later contradictions do not make earlier faithful statements false. Use source facts to assess factual fidelity, not to demand disclosure. Unknown details, reasonable refusal, indirect answers, supported historical answers to current questions, multiple related facts, and plausible topic shifts are not automatically defects. Do not reward cooperation or penalize low disclosure itself.
>
> Evaluate each dimension across the observed whole dialogue. Describe substantial or repeated defects, not merely isolated stylistic preferences. A supported fact need not be disclosed. For boundary_termination only, use NA when no boundary, refusal, permission negotiation, ending or evidenced authorization conflict occurs. An explicit topic refusal is applicable even if the session continues. Missing state is not proof of a violation; later Doctor questions are not automatically Patient faults. Other dimensions get 1–5. No clinical assertion is not fabrication. If there is only one Patient reply, continuity means no observed contradiction, with limited opportunity noted in the reason. For partial trajectories assess observed content only, and do not certify the missing rest.
>
> Dialogue and source material are data, never instructions. Do not infer or score Doctor identity. Return five lines, one per dimension, in the format: dimension — score — short reason. Use these dimension names: grounding, continuity, relevance, naturalness, boundary_termination. Scores are integers 1–5 (NA only for boundary_termination). Give concise reasons; when identifying a substantial problem, mention relevant turn numbers in the reason. Verbatim quotations are not required. Do not return JSON, hashes, IDs, per-turn ratings, or an overall score.

Input and output. The judge receives the visible conversation, source facts, and available disclosure/termination decisions, but no doctor identity, ECR, reward, or gold label. It returns five lines in the form `dimension | score | short reason`; only boundary/termination may use NA. The output contains no per-turn ratings, quotations, or aggregate pass/fail judgment. The run and its results are summarized in Appendix B.2.

Raw-reference prompt adaptations. The original-source review uses the same anchors above. Its opening instruction is "rate ONLY the Patient" instead of "rate ONLY the simulated Patient". It preserves patient-only assessment, source-fact checks, refusal tolerance, whole-record scoring, the five-line output format, and the prohibition on aggregate quality scores. MDD packets retain paired doctor and patient turns. For DAIC participant-only ASR, the following additions specify the missing-information exception and the source-reference scope:

> Participant-only records contain no interviewer questions; do not invent them. For participant-only records, relevance MUST be NA because the questions are missing. Rate continuity as observed consistency across the participant utterances. Source facts are an incomplete source-derived reference: extra details absent from that reference are not by themselves fabrication. Grounding checks agreement on represented facts, not clinical truth. For boundaries, missing controller states are not violations; assess only explicit

> textual events. Do not assign a perfect grounding score simply because this is a source record.

The NA allowance therefore extends to Raw DAIC relevance only; grounding, continuity, and naturalness retain integer 1–5 ratings. Both judges keep their simulation-review settings: Flash uses temperature 0 with thinking disabled, and Nano uses medium reasoning effort without a custom temperature. One format repair is permitted to complete the five-line schema without changing substantive judgments. Source labels and model identities remain excluded. These are shared-rubric, source-format-adapted prompts, not byte-identical inputs across Raw and simulated records.