SplatLab: Autonomous Scientific Discovery for 3DGS Research

Seemandhar Jain **Manmohan Chandraker**
University of California San Diego
{sejain,mkchandraker}@ucsd.edu




Figure 1: Overview of SplatLab: research pipeline (top) and sixteen generated manuscripts (bottom).

Abstract

Scientific discovery requires more than generating hypotheses: ideas must be grounded in prior work, translated into executable methods, experimentally validated, challenged by counterevidence, and communicated through reproducible findings. Despite recent advances in autonomous research agents, closing this entire loop remains challenging in rapidly evolving computer-vision fields with complex training pipelines and expensive evaluations.

We introduce SplatLab, an autonomous scientific discovery system for 3D Gaussian Splatting (3DGS) that integrates literature understanding, hypothesis generation, implementation, experimental refinement, falsification, and manuscript writing into a unified research pipeline. Given a research prompt, a target-paper URL, or no input at all, SplatLab identifies research opportunities, proposes novel methods, trains and ablates candidates across Mip-NeRF 360 and LLFF, and produces manuscripts grounded in verifiable experimental evidence.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).

Unlike prior systems, SplatLab performs discovery over verified baseline implementations using domain-aligned modification scaffolds. A cascade-weighted Elo tournament evolves candidate methods using measured GPU performance and verbal-gradient feedback, while a standing falsifier incorporates adversarial stress testing directly into selection. An integrity audit binds reported claims to logged experiments, and reviewer-driven feedback can initiate further experimentation rather than merely revising text.

SplatLab discovers methods achieving PSNR improvements of $+0.18$ to $+3.78$ dB over matched baselines, including $+3.78$ dB on astrophotographic nebula rendering, a previously unexplored setting for 3DGS. By closing the loop between scientific reasoning, executable experimentation, and evidence-backed communication, SplatLab compresses months of researcher effort into days of mostly autonomous compute. Code, manuscripts, and experiment ledgers are available at `https://seemandhar.github.io/splatlab`.

1 Introduction

Automating scientific discovery is a long-standing research ambition, traceable through early symbolic systems such as the Automated Mathematician [51] and DENDRAL [7], the conceptual programme of *AI-generating algorithms* [8], and a contemporary line of work in which LLMs compose research ideas, write training code, run experiments, and produce manuscripts [29, 53, 40, 14, 28, 46, 12, 42]. The classical research workflow is bounded by an individual researcher's time and reading bandwidth, neither of which scales with the publication rate of an active subfield. Automating parts of the cycle could return researcher time to ideation and analysis. Computer vision is a natural place to test this: a single subfield now produces thousands of follow-up papers in a few years, and reproducing one published method often takes engineering effort comparable to producing a new one.

We are not aware of an autonomous-research pipeline demonstrated end-to-end in a computer-vision subfield where reproducing a single prior paper takes weeks of expert engineering. Existing systems edit short LaTeX templates over brief training runs, rank free-text hypotheses without executing a training loop, or build experimentation on top of LLM-written reimplementations that have not been externally verified against the target paper [29, 53, 14, 28, 40, 46, 12, 58, 24, 20, 26, 50]. PaperBench measures this verification gap: across 20 ICML 2024 Spotlight and Oral papers, the strongest evaluated agent reaches 21.0% average replication [43]. Without a verified reimplementation, an improvement claim has no fixed external reference: reported metrics may not trace to a measurement on disk, long-running agents drift from their objective as context fills, and comparisons are sometimes made against unspecified baselines. Table 2 summarises four common gaps: domain framework, verified baseline, full-loop refinement, and claim-to-log binding.

Progress on this problem appears to require a domain-specialised research stack constructed on top of verified reproductions, rather than only improvements in generalist coding ability. Generalist agentic frameworks [36, 16, 52, 55, 48] were designed for software engineering, where every task starts from a fresh codebase, not for the iterative refinement atop a verified baseline that scientific research typically requires. Four design choices follow: choose a single live subfield, build a verified-reproduction backbone for it, expose a structured modification space to the ideator, and bind every reported number to a logged GPU run.

We instantiate this for 3D Gaussian Splatting (3DGS) [22], an active subfield of neural rendering since 2023. Reproducing a 3DGS paper on top of `gsplat` [57] requires correct densification scheduling, opacity reset, spherical-harmonic activation, and view-dependent appearance, none of which is supplied by the prompt a generalist code agent receives; on a 30-paper 3DGS reproduction benchmark, current frontier models succeed on roughly 5% of inputs [19]. The verified-reproduction backbone has two parts: NERFIFY [19] converts NeRF papers into Nerfstudio plugins matching expert-written code; SPLATIFY [18] extends the construction to 3DGS through a context-free grammar over a modular template with nine composable extension hooks. Every candidate that reaches our experimentation phase mutates a SPLATIFY plugin already verified to train, and match its target.

We present SplatLab, an execution-grounded research system demonstrated in 3D Gaussian Splatting that produces research manuscripts with verified experiments from a one-line prompt, a target-paper URL, or no input at all, with every reported number traced to a logged GPU run. SplatLab orchestrates 36 agents across seven phases (research, ideation, implementation, experimentation, analysis, writing,

peer review) without a fixed DAG. Five design decisions distinguish SplatLab from prior autonomous-research and program-search systems; each is detailed in Section 3. *(i) Grounded Elo on real GPU PSNR.* Idea ranking uses cascade-weighted, grounding-conditional Elo scored on measured PSNR rather than the model-judged proposal scores of AI Co-Scientist [14], with ReEvo-style verbal gradients [56] fed back to the ideator. *(ii) In-loop falsifier coupled to selection.* A standing adversarial falsifier extending AIGS [28] runs in-loop; each failed attack deducts Elo, making stress-test survival a selection signal rather than a post-hoc check. *(iii) Claim-backed verification.* Every number that reaches a draft is bound to a logged experiment, and the run cannot terminate while any claim lacks a backing measurement, a binding absent from prior pipelines [29, 53]. *(iv) Verified-reproduction backbone.* Every candidate mutates a SPLATIFY plugin already verified against its target, providing a fixed reference for every reported gain. *(v) Domain-aligned modification space.* Seven 3DGS novelty categories wrap EVOLVE-BLOCK markers and the SPLATIFY island tournament [18] in category-aligned scaffolds; a cross-codebase auto-mapper places them in arbitrary 3DGS repositories so the diff space coincides with the field's modification space.

On Mip-NeRF 360 [4] and LLFF [31], SplatLab produces manuscripts that each beat their reproduced target by $+0.18$ to $+3.78$ dB PSNR, including $+3.78$ dB on astrophotographic nebula rendering, a domain not addressed by prior 3DGS work. The research cycle (read, reproduce, extend, train, ablate, write) compresses from months of graduate-student time to days of mostly autonomous compute, enabling design-space sweeps not feasible at single-researcher pace. SplatLab, all agents, and the code can be found at `http://seemandhar.github.io/splatlab`.

2 Related Work

End-to-end automated research pipelines. SplatLab is closest to goal-to-manuscript systems. The AI Scientist and v2 produce ML papers via fixed templates and agentic tree search [29, 53]. Agent Laboratory, MLR-Copilot, AI-Researcher, NovelSeek/InternAgent, Dolphin, and CodeScientist organize the literature-to-paper loop with role-specialized agents [40, 26, 46, 34, 58, 20]; CycleResearcher post-trains an LLM on a research-review-refine cycle, while AgentRxiv shares a preprint pool across runs [50, 39]. AIGS adds a post-hoc *FalsificationAgent*, data-to-paper traces claims to data, Curie embeds rigor via agent control modules, and PaperBench grades replication against author rubrics [28, 17, 24, 43]. All rely on agent-written reimplementations unverified against their targets; SplatLab requires every candidate to mutate a plugin verified to compile, train, and match its target's headline. None condition on (B, L), fuse falsification with cascade-weighted Elo, or allow reviewer-spawned re-experimentation rather than only prose edits.

Autonomous discovery without manuscript output. Other systems run the scientific loop but stop short of a paper. Google's AI co-scientist uses a multi-agent Elo tournament over 203 biomedical goals with wet-lab validation in drug repurposing and antimicrobial resistance [14]. The Virtual Lab designed 92 experimentally validated SARS-CoV-2 nanobodies [44]; Coscientist and ChemCrow connect GPT-4 to wet-lab and computational chemistry tools [6, 30]. ResearchAgent and Si et al. study LLM ideation in isolation; the latter's 100+ NLP-researcher study found LLM ideas judged more novel but slightly less feasible than expert ideas [1, 41]. Wei et al. survey the landscape [49]; we instantiate their Level-3 "full agentic discovery" in graphics rather than wet-lab biology. Closest to our tournament is AI co-scientist's Elo loop, but it ranks free-text hypotheses rather than compiled training runs against a (B, L) substrate, and updates ratings uniformly rather than by evaluation depth.

Evolutionary program search and multi-agent infrastructure. SplatLab's island tournament with EVOLVE-BLOCK markers builds on LLM-driven program evolution. FunSearch pairs an LLM with a systematic evaluator in an island loop [38]; AlphaEvolve generalizes this to entire codebases via a Gemini ensemble [35]. EoH co-evolves natural-language "thoughts" and code; ReEvo introduces *verbal gradients* (LLM reflections on why one heuristic beat another, fed back into mutation); Promptbreeder evolves prompts self-referentially; Mind Evolution scales inference-time compute through genetic search [27, 56, 13, 25]. We route ReEvo's verbal gradients to the ideator rather than a heuristic mutator, and replace per-individual fitness with cascade-weighted, grounding-conditional Elo so cheap dry-run wins do not dominate full-train candidates against the verified substrate. MetaGPT, ChatDev, AutoGen, and SWE-agent supply the orchestration primitives we reuse [16, 36, 52, 55], while LLM-as-a-judge, MARG, and AgentReview inform our reviewer-driven re-experimentation but treat review as terminal rather than a gate demanding new substrate experiments [59, 9, 21].




Figure 2: **Detailed pipeline of SplatLab.** Expanding the overview in Figure 1, a research intent (or no input) passes through six stages (grounding, Elo-pre-ranked ideation, `EVOLVE-BLOCK` implementation, cascade-weighted Elo refinement across eight islands, integrity audit, and reviewer-driven manuscript synthesis) run by a three-level hierarchy of Professor, PhD Coordinators, and Undergrad Leaf Agents.

3 Method

SplatLab is a system for *verified evolutionary research over a reproducible substrate*. The substrate is a 3DGS reproduction backbone (SPLATIFY [18]/NERFIFY [19]) whose plugins match their published targets; every extension SplatLab proposes mutates a plugin already verified to match its target. This scaffolding separates SplatLab from prior systems that pursue unconstrained autonomous discovery over unverified agent-written code, whose drafts are neither traceable to logs nor reproducible by retraining. The claim is narrower and stronger: SplatLab performs *autonomous iterative discovery within a live, technically demanding subfield*, with every iteration anchored to a measured baseline and bound to a logged training run.

Formally, given a research prompt, a target-paper URL, or no input at all, SplatLab returns $P = (P_{\text{tex}}, P_{\text{pdf}}, \mathcal{L}, \mathcal{C}) = W(x; \mathcal{D})$, where P_{tex} is the LaTeX source, P_{pdf} the compiled PDF, $\mathcal{L}$ binds every number in P_{tex} to a training run on disk, and $\mathcal{C}$ is the codebase that produced those numbers. The fixed context $\mathcal{D} = (\mathcal{R}, \mathcal{B}, \mathcal{H}, \mathcal{G})$ supplies the 3DGS literature corpus $\mathcal{R}$, the SPLATIFY backbone $\mathcal{B}$, the nine `EVOLVE-BLOCK` hooks $\mathcal{H}$, and the target conference template $\mathcal{G}$. SplatLab produces both $\mathcal{C}$ and $\mathcal{L}$ in the same run against the verified $\mathcal{B}$; its writing stage can re-enter implementation to spawn new training runs.

Fig. 2 decomposes W into six stages, each acting on the same verified substrate: *Grounding* instruments a measured bottleneck on the matched plugin; *Ideation* pre-ranks candidate fixes by idea-level Elo; *Implementation* compiles survivors into `EVOLVE-BLOCK` mutations of the plugin; *Refinement* runs a cascade-weighted Elo tournament across eight islands with standing falsification, scored on real `ns-train` PSNR; *Audit* verifies that every reported number traces back to a measurement on the verified substrate; *Synthesis* writes the manuscript through reviewer-driven loops that may re-enter Stages 3–4. Stages run under a three-level hierarchy (Professor, PhD coordinators, Undergrad leaf agents; 36 total) with no fixed DAG: the master may revisit any earlier stage on a falsifier veto, audit failure, or reviewer-spawned ablation.

3.1 SplatLab

Stage 1: Grounding. Stage 1 anchors the run in the substrate. Two parallel investigations produce the *thesis spine* Γ, the only artefact Stages 2–6 condition on. The first reads the literature: a Researcher queries arXiv, Semantic Scholar, and Google Scholar and pulls from a persistent cross-run paper store via RAG, with retrievals written back before Stage 1 closes so the corpus grows monotonically across runs. Retrieved PDFs are parsed by MinerU [47] and a Limitation Brainstormer cross-references each paper's stated limitations against critiques in later work, emitting **L-IDs**: deduplicated limitation strings such as `L-127: opacity reset destabilises late refinement`, each with its supporting citation set. The second reads the substrate: a Bottleneck Analyst trains the

verified SPLATIFY plugin on representative Mip-NeRF 360 scenes and profiles per-tile loss, PSNR trajectory, memory, and gradient norms; patterns become **B-IDs**: measurement-anchored strings such as `B-04: PSNR plateau at` 25.65 `dB on garden`, each tagged with the `EVOLVE-BLOCK` category it implicates. Γ contains the SPLATIFY reproduction vector $\mathcal{V}$, the L-IDs, and the B-IDs.

Stage 2: Grounded ideation. Stage 2 turns Γ into a ranked set of candidates worth running on the substrate, all without running any training. A candidate is a tuple $(\texttt{mechanism}, c, l, b, \hat{\Delta})$, where $c \in \{1, \ldots, 7, \texttt{open}\}$ indexes one of seven 3DGS novelty categories, l is the L-ID it claims to address, b the B-ID it claims to attack, and $\hat{\Delta}$ a predicted delta on the headline metric. An Ideator generates candidates conditioned on Γ over five iterations; between rounds, a Web Scout fires fresh literature searches keyed on the previous round's L-IDs and B-IDs, so prior art widens monotonically rather than re-sampling from a fixed window [41]. Each candidate clears four checks: *Precedent* (the L-ID/B-ID citation set supports the claim), *Novelty* (neither a restatement of prior work nor a parameter-only tweak lacking a new signal, state, or mechanism, as screened by the *Tweak Trap*), *Saturation* (fewer than T logged negatives in the category-mechanism cell), and *Orthogonality* (not a near-duplicate of another admitted candidate); rejection routes back to the Web Scout as a *Meta-Pivot* signal. Survivors enter a bracket tournament with initial Elo 1200, judged by an LLM-as-Judge along four axes: novelty against the L-ID citation set, specificity to the B-ID, implementability within the category, and predicted-delta plausibility. Top-quartile uses multi-turn debate; lower tiers use single-turn pairwise comparisons. The output passes into Stage 3 where each candidate becomes a real plugin mutation, and into the GPU-grounded tournament in Stage 4.

Stage 3: Verified-plugin implementation. Stage 3 mutates the substrate. Each surviving idea becomes a code change to a SPLATIFY/NERFIFY plugin [18, 19] that already compiles, trains, and matches the target's published headline; the verified-plugin contract attributes downstream gains to the proposed mechanism rather than to silent reimplementation drift. A Hook Mapper resolves the abstract category c into a concrete subset of the nine `EVOLVE-BLOCK` hooks (densification, regularisation, loss, rendering, pruning, initialisation, scheduling, opacity, harmonics) and places `EVOLVE-BLOCK` markers around the corresponding regions, following [35] but over a verified plugin rather than agent-written code; for $c = \texttt{open}$, a cross-codebase auto-mapper locates insertion points that span existing hooks, compose them, or introduce new ones. `EVOLVE-BLOCK`s are paired code comments that delimit regions agents can modify while preserving the surrounding verified implementation. An Implementer generates the code under three constraints: a *Citation Graph* retrieves L-ID/B-ID-anchored papers and their published implementations as reference code; a *Graph of Thoughts* [5] controller structures reasoning into generation, aggregation, and refinement nodes so a failed branch can be revisited rather than restarted; and a context-free *Grammar* of SPLATIFY restricts output to legal hook-level rewrites. Mutations are emitted as structured diffs [35] rather than full rewrites. The diff is applied, the plugin compiled, and a 100-iteration smoke test trains on a single Mip-NeRF 360 scene; a candidate that compiles, finishes the smoke test stably, and instantiates the requested hooks clears the contract. Failures return to the Implementer with the build log as a verbal-gradient signal, capped at a repair budget before logging to the cross-run store as a build-failure negative.

Stage 4: Cascade-weighted tournament. Stage 4 makes the substrate the judge. Each candidate is trained and scored on real PSNR; ratings are conditioned on the grounding pair (B, L) (benchmark ID, loss ID), so strength is tracked per evaluation context rather than as a scalar leaderboard.

Each candidate flows through four stages of increasing rigour: *smoke* (100-iteration sanity check), *probe* (full-iteration on one scene), *multi-scene* (full-iteration on a stratified subset), and the full benchmark, which only the champion enters. Stage s updates Elo with weight $w_s \in \{0.2, 0.5, 1.0\}$ from smoke through multi-scene, so a smoke win cannot drown out a multi-scene loss; without this gating, a three-generation eight-island run on Mip-NeRF 360 would exceed multiple GPU-months. For a match between candidates i and j at stage s,

$$R_i^{(B,L)} \leftarrow R_i^{(B,L)} + K \cdot w_s \cdot \big(S_i - E_i^{(B,L)}\big), \qquad E_i^{(B,L)} = \frac{1}{1 + 10^{(R_j^{(B,L)} - R_i^{(B,L)})/400}}, \tag{1}$$

with $K = 32$, initial rating 1200, and $S_i \in \{0, 0.5, 1\}$ from the headline-metric comparison. Each update is paired with an LLM rationale naming the regime, metric delta, and likely causal mechanism; rationales accumulate in a *Lessons File* fed back to the Ideator as a verbal gradient [56]. Smoke failures route to a Debugger for up to three patches before logging to the *Fail Train*.

Survivors are distributed across eight islands and mutated by five operators selected by a multi-armed bandit over success rates: *Refine* (local rewrites), *Crossover* (two-parent mixing), *Single-Parent* (one-parent mutation), *Tweak* (hyperparameter perturbation), and *Rewrite* (full-block regeneration). Per-island Elo distributions form a Pareto front over (B, L); promotion requires Pareto improvement, not scalar dominance. A standing falsifier attacks every survivor along three axes: edge scenes (OOD trajectories, extreme exposure), sparse-view reduction, and hyperparameter perturbation within published ranges. Each failed attack subtracts $\delta = 30$ Elo, making stress-test survival a selection signal rather than a post-hoc check; the falsifier holds veto power before manuscript writing. Once a champion emerges, the remaining GPU budget splits between *chain* (sequential variants extending the winner) and *orthogonal* (branches recombining components from non-champion islands), shifting from chain-heavy to orthogonal-heavy as the champion's per-iteration gain saturates.

Stage 5: Integrity audit. Stage 5 binds the draft back to the substrate. Six audits run between the Stage 4 champion and the draft; any failure aborts the run as a research log. *Provenance*: a content-hash chain links every reported number to its (experiment ID, commit, config) triple. *Faithfulness*: the Stage 3 rationale is checked against the diff actually applied, catching drift that PaperOrchestra [42] cannot reach by construction. *Novelty*: the mechanism is re-resolved against Semantic Scholar with a query expanded by post-hoc results, catching prior work the Stage 2 Validator missed. *Compute match*: the headline metric is recomputed under the baseline's compute envelope; gains that fail are reclassified as compute-confounded. *Cross-codebase port*: the winning hook is ported via the Stage 3 auto-mapper to a second 3DGS codebase indexed by SPLATIFY; gains that fail are flagged as codebase-specific. *Claim check*: every numerical or theoretical claim is resolved against the experiment ledger; load-bearing mismatches terminate the run, closing the hallucination failure mode that AI Scientist [29] drafts leave open.

Stage 6: Manuscript synthesis. Stage 6 turns substrate-grounded results into a manuscript that, when challenged, re-enters the substrate. The (B, L) pair routes the run: a new discovery or beating SOTA triggers Mode B (manuscript synthesis), otherwise Mode A (research log only). Five writers run in parallel: Summary Writer (abstract, introduction), Body Writer (method, experiments; consumes the Stage 4 Lessons File), Related Work (citation floor enforced via the Stage 1 Researcher), Figure Generator (result plots from the ledger), and PaperBanana [60] (conceptual diagrams). A VLM Figure Checker audits axis labels, legend completeness, and number-vs-caption agreement; an Ablation Designer reads the `EVOLVE-BLOCK` diff and emits leave-one-out ablations, a Failure Analyst surfaces residual-error heatmaps, and a Visual Comparator tiles qualitative renders against the reproduced baseline. Three reviewer agents argue under an Editor (Methodology, Domain, Devil's Advocate); the panel extends AgentReview [21] by demanding new training runs, not only prose edits. New experiments can re-enter Stage 4 with the comment as a verbal-gradient seed. The loop terminates when no reviewer raises a New-Experiment concern.

4 Experiments

We evaluate two aspects of SplatLab: the research process, through run outcomes, component ablations, failure analysis, and compute costs; and its outputs, through method performance, idea and manuscript quality, and human and multi-agent peer review. Detailed run outcomes and failure cases are reported in the appendix.

Experimental Setup. We run SplatLab multiple times: a mix of *prompted* runs (x is a target-paper SOTA), single prompt and *autonomous* runs ($x = \varnothing$, the system selects its own target from the literature); per-run mode and target are listed in supp. None of the runs required manual code edits after dispatch. Each run's SPLATIFY plugin or original source code is verified against its target's published headline or, against the paper reported numbers, before SplatLab begins (Table 8). Standard benchmarks are Mip-NeRF 360 [4] (nine unbounded scenes, including *flowers* and *treehill*) and LLFF [31]; every 8th image is held out for testing following [2], with all training runs at 30k iterations on NVIDIA A6000 GPUs. We test inter-domain discovery on three out-of-distribution scenes captured for this work and not previously addressed by 3DGS: *nebula* (astrophotographic), *bubble*, and *diamond*. We report PSNR (dB)↑, SSIM↑, and LPIPS↓.

Our experiments are designed to demonstrate not equalized search budgets, but system capability under end-to-end operation (with long-run autonomy a critical challenge that we overcome). Besides scaling, our benefits accrue through the combination of verified reproduction, structured mutation space and grounded evaluation. Reproduction details, the LLM stack, per-run compute budgets, and per-scene breakdowns are in the supplementary.




Figure 3: **Qualitative comparison against per-regime SOTA.** Columns: ground truth with evaluated region boxed (**GT**), zoomed crop (**GT-Crop**), the leading published 3DGS method for that row's regime (**SOTA**, varies per row; see Tab. 8), and the SplatLab-discovered method (**Ours**).

Table 1: SplatLab vs. SOTA on a representative subset of target prompts. Top: novel scenes with vanilla 3DGS as baseline. Bottom: SOTA improvements on standard 3DGS benchmarks. *Limitation/fix*: analyst's diagnosis (SOTA row) and validated mechanism (*ours* row); bold marks the winner in each pair. The full table covering the $+0.18$ to $+3.78$ dB PSNR range is in the Appendix.

Setting	Method	Limitation attacked / fix	PSNR↑	SSIM↑	LPIPS↓
Novel scenes (vanilla 3DGS baseline)					
Nebula	3DGS [22]	pinhole ignores OPENCV distortion; SfM gives ≈ 0 stars	32.58	0.914	0.278
	Nebula3DGS-v2 *(ours)*	3DGS-MCMC sampler with saturation-driven star seeder	**36.36**	**0.945**	**0.201**
Bubble	3DGS [22]	SH can't represent thin-film iridescence; densification stalls on emissive translucency	27.40	0.857	0.337
	BubbleGS *(ours)*	3DGS-MCMC chassis, Snell/Fresnel two-pass conditional shell renderer	**30.11**	**0.906**	**0.224**
Improving published SOTA					
MipNeRF360	FastGS [37]	$\{0, 1\}$ thresholded pixel-count is frequency-blind	29.12	0.858	0.217
	TileFocalGS *(ours)*	rank-graded per-tile weights, EMA-smoothed across views	**29.69**	**0.869**	**0.194**
MipNeRF360	splatfacto [45]	@50 s wall: severely under-converged; densification not stabilised	20.53	0.593	0.505
	View-Curriculum-GS *(ours)*	first 15 s on 30% most pose-similar views, then full set	**23.36**	**0.686**	**0.412**
MipNeRF360	MSAA-3DGS [54]	multi-sample AA blurs fine contrast; underconverged at 30K iters	25.35	0.758	0.369
	MSAA-Bilat *(ours)*	bilateral grid contrast recovery, $+15$K extra iters	**26.19**	**0.791**	**0.293**
LLFF	DWTGS [33]	wavelet basis under-constrained without high-freq supervision	18.68	0.510	0.374
	DWTGS-Patch *(ours)*	patch structure loss, opacity/normal/depth regularisers	**21.09**	**0.725**	**0.281**

Run outcomes. Across 16 runs, SplatLab trained 198 experiment branches, yielding five verified positives, five marginal results with qualified claims, five non-PSNR contributions, and one recorded failure. The Appendix details selection rejections, training failures, and outcomes by target regime.

Compute cost. Runs used a 24–48-hour wall-clock budget, averaging 113M API tokens across approximately 1,000–1,500 LLM calls. GPU consumption ranged from 2–36 GPU-hours per run, with estimated LLM API costs of $150–250. Detailed accounting appears in the Appendix.

Generated Methods vs. SOTA. We evaluate SplatLab on multiple targets in two regimes. Three are out-of-distribution scenes (Nebula, Bubble, Diamond) with vanilla 3DGS [22] as the baseline; the remaining eight target published 3DGS methods on Mip-NeRF 360 and LLFF, where the discovered variant must beat a tuned, peer-reviewed reference under the original paper's iteration count, scene set, and compute budget. Table 8 pairs each baseline with the SplatLab-discovered method on PSNR, SSIM, and LPIPS; Figure 3 shows the regime-matched qualitative comparison. The discovered method exceeds its baseline on PSNR in every pairing, with gains from $+0.18$ to $+3.78$ dB, the largest on the astrophotographic nebula scene, a regime where 3DGS has not previously been applied.

Multi-seed Robustness. To evaluate seed sensitivity, we reran GNS-AA with five seeds. GNS achieved 25.95 ± 0.07 dB, while GNS-AA achieved 26.18 ± 0.05 dB, yielding $+0.23 \pm 0.09$ dB compared with the originally reported $+0.18$ dB. Other generated studies also use three or four seeds. Improvements within the estimated noise floor are reported as marginal rather than verified gains.

SplatLab vs. Prior Discovery Systems. Table 2 positions SplatLab against the eight closest autonomous-research and discovery systems on the capability axes of Section 3. SplatLab is the only system that satisfies all five rows anchoring our contributions: a verified-reproduction backbone for a live subfield, grounding-conditional idea re-ranking, a standing falsifier coupled to selection, claim-backed verification, and a reviewer panel that can spawn new training runs rather than only prose edits. Full results including wall clock and token comparison in the supplementary.

Table 2: Capability comparison against the closest autonomous-research and program-search systems. ✓= supported, ∼= partial, X= not supported. Verdicts verified against each cited paper; ∼ indicates a related but weaker mechanism (post-hoc rather than in-loop, LLM-judged on outputs rather than measured metrics, manually placed rather than auto-mapped, etc.). Full matrix (22 rows, grouped by stage, with per-cell justifications) in the Appendix.

Capability	AIS-v2 [53]	A-Lab [40]	MLR [26]	AIGS [28]	Curie [24]	PaperOrch. [42]	CoSc [14]	AIE [35]	**Ours**
End-to-end executable (no human in loop)	✓	✓	∼	∼	✓	X	∼	✓	✓
Produces a manuscript	✓	✓	X	X	X	✓	X	X	✓
Real-experiment execution	✓	✓	✓	∼	✓	X	X	✓	✓
Live-subfield domain backbone	X	X	X	X	X	X	X	X	✓
Verified baseline reproduction	X	X	X	X	X	X	X	X	✓
Idea ranking on real GPU metrics	X	∼	∼	X	∼	X	X	✓	✓
Category-aligned scaffolds	X	X	X	X	X	X	X	X	✓
Verification and audit									
Reproducibility / rigor checks	X	X	X	∼	✓	X	X	∼	✓
Claim-backed-verification	X	X	X	X	X	X	X	X	✓
Simulated peer review	✓	✓	X	X	X	✓	X	X	✓
Reviewer panel can spawn new training runs (not just edits)	X	X	X	X	X	X	X	X	✓

Table 3: Idea quality (blind expert protocol from [41]). Forty style-normalised ideas (twenty from SplatLab Stage 2, ten from 3DGS PhD students, ten from accepted preprints held out from the cross-run paper store) scored by ten experts on a 1–10 Likert scale.

Source	N	Novelty	Excitement	Feasibility	Effectiveness	Overall
PhD students	10	5.2	5.0	**6.4**	5.7	5.1
Accepted arXiv preprints	10	5.8	5.5	6.0	5.8	6.0
SplatLab (Stage 2)	20	**5.9***	**5.6***	6.2	**6.1***	**5.8****

Idea and Manuscript Quality. We evaluate SplatLab at two stages of its pipeline: ideation (Table 3) and final manuscript (Table 4). At ideation, twenty Stage 2 candidates are scored against ten PhD-student ideas and ten recently accepted workshop / conferences ideas under the blind-expert protocol of [41]. At manuscript, three baseline pipelines each produce a draft from five human-verified prompts reverse-engineered from SplatLab runs; drafts are scored against the published 3DGS paper for each prompt under the LLM-as-a-Judge paired protocol of [42], verified by graphics-area human reviewers. SplatLab outperforms prior systems by large margins at both stages and scores close to human ground truth at the manuscript level.

LLM and Human Peer Review. We review the top five SplatLab-generated papers against five 3DGS papers accepted at CVPR or NeurIPS 2025 under the NeurIPS rubric (Soundness, Presentation, Novelty on 1–4; overall on 1–6, 3.5 = borderline). Each paper is scored independently by a multi-agent reviewer similar to ScholarPeer [15], with separate agents per review axis and a chair agent for aggregation, and by a graphics-area human reviewer blind to authorship. The multi-agent reviewer slightly favors SplatLab on every axis (3.6 vs. 3.5 overall), consistent with the residual LLM-judge bias toward AI-generated content [59]. The human reviewer reads the comparison differently: published papers score higher on Soundness and Presentation (3.6 and 3.8 vs. 3.2 and 3.0) but lower on Novelty (3.1 vs. 3.5), with the published set landing at clear accept (4.1) and SplatLab at borderline (3.5). The split matches what the rest of the paper argues: verified plugins and the integrity audit close the soundness gap on numbers, but human authors still write better papers, while the machine-pace design-space sweep surfaces mechanisms human-paced research has not yet reached.

Table 4: Manuscript quality on a 0–100 Multi-agent as judge [21] (paired protocol from [42]); means over five human-verified prompts reverse-engineered from SplatLab runs. *Human (GT)*: the published 3DGS paper. *SingleAgent*: SplatLab with one frontier agent. Baselines share the same research idea; *AI Scientist-v2* [53] and *GPT-5 ET* receive Stage 2–3 materials, while PaperOrchestra additionally receives verified code, logs, and the Stage 5 audit summary. Default tool access is retained. Scores measure writing quality, not end-to-end discovery. Three graphics-area reviewers re-scored the ten manuscripts (five SplatLab, five human) and audited the LLM judge's per-rubric rationales against the manuscript text; reviewer scores agree with the LLM at Spearman $\rho = 0.87$ (weighted $\kappa = 0.84$), and 54/60 of the LLM rationales were marked as supported by manuscript content.

Pipeline	Citation Practices	Coverage & Completeness	Critical Analysis & Synthesis	Organisation & Writing	Positioning & Novelty	Relevance & Focus	Overall Score
Judge: Gemini-3.1-Pro							
Human (GT)	94	93	91	94	89	91	93
SingleAgent	52	48	42	65	70	70	38
AI Scientist-v2	65	22	28	28	42	48	32
GPT-5 ET	14	24	29	22	38	42	17
PaperOrchestra*	75	81	74	81	76	83	79
SplatLab	**95**	**89**	**93**	**95**	**87**	**93**	**90**

Table 5: Simulated peer-review scores on five SplatLab-generated papers vs. five 3D Gaussian Splatting papers accepted at CVPR or NeurIPS 2025. Each paper receives Soundness, Presentation, and Novelty on a 1–4 NeurIPS scale, plus an overall accept/reject score on the 1–6 scale (1 = strong reject, 6 = strong accept; 3.5 = borderline). Two judges score every paper: a multi-agent reviewer modeled on ScholarPeer [15] and a graphics-area human reviewer blind to authorship. Means across all five papers per source.

Judge	Source	Soundness	Presentation	Novelty	Overall (1–6)
Multi-agent reviewer	CVPR/NeurIPS 2025 (human GT)	3.2	3.4	3.0	3.5
	SplatLab (top 5)	3.4	3.6	3.4	3.6
Human reviewer	CVPR/NeurIPS 2025 (human GT)	3.6	3.8	3.1	4.1
	SplatLab (top 5)	3.2	3.0	3.5	3.5

Real Workshop Acceptance and Ethical Protocol. With prior approval from the workshop organizers and disclosure of AI involvement, we submitted SplatLab-generated manuscripts to a CVPR 2026 workshop: *AttDis & Friends*, *NeedleSwap*, and *AuditSplat*. All three were accepted as posters (Fig. 4). To address ethical concerns, we withdrew all submissions after the peer-review experiment, using the acceptance decisions solely to evaluate SplatLab under real-world review.

Table 6: Component ablations on the canonical pool. Each row removes one mechanism and reports the with-vs-without delta on a single metric.

Component ablated	**Without**	**With (full pipeline)**
Stage 1: grounding (L/B-IDs)	0/32 ideas cleared Stage 4 cascade	winner produced
Stage 2: Elo pre-selection	24 GPU evals to winner	6 GPU evals (20 rejected pre-GPU)
Stage 3: verified-plugin contract	9/16 winners non-reproducible (> 1.0 dB)	0/16 non-reproducible
Stage 4: cascade weights (uniform $w_s{=}1$)	smoke-test winner picked, 5th on multi-scene	multi-scene leader picked
Stage 4: per-(B, L) Elo (global)	global champ -1.6 dB on Nebula vs. specialist	per-target winners
Stage 4: verbal gradients (Reflection off)	5 generations to stabilize, $2.4\times$ tokens	2 generations
Stage 4: standing falsifier (-30 Elo off)	5/16 winners fail held-out attacks	0/16 fail
Stage 5: claim-backed audit gate	16/16 manuscripts contain unbacked numbers	0/16 unbacked
Stage 6: reviewer re-experimentation	avg simulated acceptance 2.2/6	avg score 3.6/6

Component Validation and Ablations. Each ablation removes one component, reuses the canonical-run winner and the same 32-idea / 16-paper pool for fair comparison, and reports the with-vs-without delta on a single concrete metric. Stage 5 carries the headline result: without the claim-backed verification gate, every ablated manuscript contained at least one number that did not trace to any log on disk, while the full pipeline produced 0 such cases. This closes the hallucination failure mode that AI Scientist drafts and successors leave open.




Figure 4: **Generated papers accepted at a CVPR 2026 workshop.** (a) **AttDis & Friends**, (b) **NeedleSwap**, and (c) **AuditSplat**, all accepted. Each row shows pages 1–8 from left to right.

Portability and Taxonomy Ablation. Stages 1 and 3–6 are designed to operate across domains: agents build the literature corpus and codebase profile, select the evaluation metric, implement structured diffs, and run the tournament, audits, and reviewer loop against the target codebase and benchmark. Stage 2 supplies domain-specific ideation grounding; adapting its taxonomy requires expert effort, whose effect on search efficiency we examine below. On the nebula target, taxonomy-guided and taxonomy-free runs improved PSNR by $+3.78$ and $+3.45$ dB, respectively. Removing the taxonomy increased token consumption from 47.5M to 85.5M (80%). This single-target comparison suggests that domain grounding improves search efficiency, rather than being strictly necessary for execution. Additional runs outside 3DGS with Stage 2 disabled are described in the Appendix.

5 Conclusion

SplatLab shows that autonomous research in a live computer-vision subfield is achievable when ideation operates atop verified reproductions and every reported claim is bound to a logged training run. From a one-line prompt or no input at all, SplatLab produces submission-ready 3DGS manuscripts that each beat their reproduced target on PSNR. The research cycle (read, reproduce, extend, train, ablate, write) that today takes a graduate student months compresses to days of mostly autonomous compute, and a single research cluster running SplatLab sweeps design-space slices that hand-execution would take years to cover. The bottleneck on autonomous research was never model capability; it was the absence of four ingredients: a domain framework, a verified baseline, iterative full-loop refinement, and a binding from claim to measurement. Once those are in place, the discovery rate is set by GPU throughput rather than researcher time.

Broader impacts. SplatLab lets small labs participate in live subfields without weeks of reimplementation. A tool that compresses months to days can flood peer review designed for human pace. The per-field cost of building a verified-reproduction backbone biases capability toward pre-engineered subfields and well-resourced labs. A bug in the integrity audit could mask hallucination instead of catching it. We address the third through Stage 5 audits and Mode A archival; the first two need community norms. SplatLab may reduce entry-level research opportunities, motivating AI research mentors and educational use of Mode A logs to teach hypothesis formation, debugging, and critical evaluation of evidence. We release the system openly, recommend that derivative submissions be labelled and ship their experiment ledger, and discourage volume submissions. SplatLab is a research instrument, not a paper-mill backend. Limitations and study-resource accounting are discussed in the Appendix.

Acknowledgments and Disclosure of Funding

This work was supported by institutional and advisor-provided research and computing resources at UC San Diego. The authors declare no competing interests.

References

[1] Baek, J., Jauhar, S.K., Cucerzan, S., Hwang, S.J.: ResearchAgent: Iterative research idea generation over scientific literature with large language models. In: Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL). pp. 6709–6738 (2025)

[2] Bagdasarian, M.T., Knoll, P., Li, Y.H., Barthel, F., Hilsmann, A., Eisert, P., Morgenstern, W.: 3DGS.zip: A survey on 3D Gaussian Splatting compression methods. Computer Graphics Forum **44** (2025)

[3] Barron, J.T., Mildenhall, B., Tancik, M., Hedman, P., Martin-Brualla, R., Srinivasan, P.P.: Mip-NeRF: A multiscale representation for anti-aliasing neural radiance fields. In: IEEE/CVF International Conference on Computer Vision (ICCV). pp. 5855–5864 (2021)

[4] Barron, J.T., Mildenhall, B., Verbin, D., Srinivasan, P.P., Hedman, P.: Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). pp. 5470–5479 (2022)

[5] Besta, M., Blach, N., Kubicek, A., Gerstenberger, R., Gianinazzi, L., Gajda, J., et al.: Graph of thoughts: Solving elaborate problems with large language models. In: Proceedings of the AAAI Conference on Artificial Intelligence. vol. 38, pp. 17682–17690 (2024)

[6] Boiko, D.A., MacKnight, R., Kline, B., Gomes, G.: Autonomous chemical research with large language models. Nature **624**(7992), 570–578 (2023). https://doi.org/10.1038/s41586-023-06792-0

[7] Buchanan, B.G., Feigenbaum, E.A.: Dendral and meta-dendral: Their applications dimension. In: Readings in artificial intelligence, pp. 313–322. Elsevier (1981)

[8] Clune, J.: Ai-gas: Ai-generating algorithms, an alternate paradigm for producing general artificial intelligence. arXiv preprint arXiv:1905.10985 (2019)

[9] D'Arcy, M., Hope, T., Birnbaum, L., Downey, D.: MARG: Multi-agent review generation for scientific papers. arXiv preprint arXiv:2401.04259 (2024)

[10] Deng, X., Yu, Q., Diao, C., Li, M., Xu, D.: Gradient-driven natural selection for compact 3d gaussian splatting (2025), `https://arxiv.org/abs/2511.16980`

[11] Farooq, U., Guillemaut, J.Y., Thomas, G., Hilton, A., Volino, M.: Optimized 3d gaussian splatting using coarse-to-fine image frequency modulation. In: European Conference on Visual Media Production (CVMP). ACM (2025). https://doi.org/10.1145/3756863.3769707

[12] Feng, S., Ma, R., Yan, X., Fan, Y., Hu, Y., Huang, S., Zhang, S., Cao, Z., Peng, T., Yuan, J., Guo, Z., Zhong, Z., Du, S., Wang, W., Shi, J., Zhou, Y., He, X., Yu, Z., Yu, F., Zhan, B., Zheng, Q., Wu, J., Liu, M., Zhang, C., Hou, S., Li, S., Jiang, Y., Lou, W., Wang, L., Wang, Z., Wang, J., Xu, W., Deng, Y., Liu, D., Wang, Y., Zhang, W., Ling, F., Zhang, S., Wang, X., Zheng, S., Huang, X., Sun, S., Hu, S., Ye, P., Song, C., Wang, B., He, C., Liu, Y., Li, X., Hou, Q., Chen, T., Yue, X., Wang, B., He, L., Lin, D., Zhou, B., Zhang, B., Bai, L.: Internagent-1.5: A unified agentic framework for long-horizon autonomous scientific discovery. arXiv preprint arXiv:2602.08990 (2026)

[13] Fernando, C., Banarse, D., Michalewski, H., Osindero, S., Rocktäschel, T.: Promptbreeder: Self-referential self-improvement via prompt evolution. In: Proceedings of the 41st International Conference on Machine Learning (ICML). Proceedings of Machine Learning Research, vol. 235, pp. 13481–13544 (2024)

[14] Gottweis, J., Weng, W.H., Daryin, A., Tu, T., Palepu, A., Sirkovic, P., Myaskovsky, A., Weissenberger, F., Rong, K., Tanno, R., et al.: Towards an ai co-scientist. arXiv preprint arXiv:2502.18864 (2025)

[15] Goyal, P., Parmar, M., Song, Y., Palangi, H., Pfister, T., Yoon, J.: Scholarpeer: A context-aware multi-agent framework for automated peer review. arXiv preprint arXiv:2601.22638 (2026)

[16] Hong, S., Zhuge, M., Chen, J., Zheng, X., Cheng, Y., Wang, J., Zhang, C., Wang, Z., Yau, S.K.S., Lin, Z., Zhou, L., Ran, C., Xiao, L., Wu, C., Schmidhuber, J.: MetaGPT: Meta programming for a multi-agent collaborative framework. In: The Twelfth International Conference on Learning Representations (ICLR) (2024)

[17] Ifargan, T., Hafner, L., Kern, M., Alcalay, O., Kishony, R.: Autonomous LLM-driven research—from data to human-verifiable research papers. NEJM AI **2**(1) (2025). https://doi.org/10.1056/AIoa2400555

[18] Jain, S., Gupta, K., Chandraker, M.: Splatify: Reproduce, discover, innovate! from papers and ideas to trainable 3dgs code (2026), `https://arxiv.org/abs/2610.09116`

[19] Jain, S., Gupta, K., Gupta, K., Chandraker, M.: Nerfify: A multi-agent framework for turning nerf papers into code. arXiv preprint arXiv:2603.00805 (2026)

[20] Jansen, P., Tafjord, O., Radensky, M., Siangliulue, P., Hope, T., Dalvi Mishra, B., Majumder, B.P., Weld, D.S., Clark, P.: CodeScientist: End-to-end semi-automated scientific discovery with code-based experimentation. In: Findings of the Association for Computational Linguistics: ACL 2025. pp. 13370–13467 (2025)

[21] Jin, Y., Zhao, Q., Wang, Y., Chen, H., Zhu, K., Xiao, Y., Wang, J.: AgentReview: Exploring peer review dynamics with LLM agents. In: Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP). pp. 1208–1226 (2024)

[22] Kerbl, B., Kopanas, G., Leimkühler, T., Drettakis, G.: 3D Gaussian splatting for real-time radiance field rendering. ACM Transactions on Graphics **42**(4) (Jul 2023). https://doi.org/10.1145/3592433

[23] Kheradmand, S., Rebain, D., Sharma, G., Sun, W., Tseng, J., Isack, H., Kar, A., Tagliasacchi, A., Yi, K.M.: 3D Gaussian Splatting as Markov Chain Monte Carlo. In: Advances in Neural Information Processing Systems (NeurIPS) (2024)

[24] Kon, P.T.J., Liu, J., Ding, Q., Qiu, Y., Yang, Z., Huang, Y., Srinivasa, J., Lee, M., Chowdhury, M., Chen, A.: Curie: Toward rigorous and automated scientific experimentation with AI agents. arXiv preprint arXiv:2502.16069 (2025)

[25] Lee, K.H., Fischer, I., Wu, Y.H., Marwood, D., Baluja, S., Schuurmans, D., Chen, X.: Evolving deeper LLM thinking. arXiv preprint arXiv:2501.09891 (2025)

[26] Li, R., Patel, T., Wang, Q., Wang, Q., Du, X.: MLR-Copilot: Autonomous machine learning research based on large language model agents. In: NAACL (2025)

[27] Liu, F., Tong, X., Yuan, M., Lin, X., Luo, F., Wang, Z., Lu, Z., Zhang, Q.: Evolution of heuristics: Towards efficient automatic algorithm design using large language model. In: Proceedings of the 41st International Conference on Machine Learning (ICML). Proceedings of Machine Learning Research, vol. 235, pp. 32201–32223 (2024)

[28] Liu, Z., Liu, K., Zhu, Y., Lei, X., Yang, Z., Zhang, Z., Li, P., Liu, Y.: AIGS: Generating science from AI-powered automated falsification. arXiv preprint arXiv:2411.11910 (2024)

[29] Lu, C., Lu, C., Lange, R.T., Foerster, J., Clune, J., Ha, D.: The AI Scientist: Towards fully automated open-ended scientific discovery. arXiv preprint arXiv:2408.06292 (2024)

[30] M. Bran, A., Cox, S., Schilter, O., Baldassari, C., White, A.D., Schwaller, P.: Augmenting large language models with chemistry tools. Nature Machine Intelligence **6**, 525–535 (2024). https://doi.org/10.1038/s42256-024-00832-8

[31] Mildenhall, B., Srinivasan, P.P., Ortiz-Cayon, R., Kalantari, N.K., Ramamoorthi, R., Ng, R., Kar, A.: Local light field fusion: Practical view synthesis with prescriptive sampling guidelines. ACM Transactions on Graphics (TOG) (2019)

[32] Navaneet, K.L., Meibodi, K.P., Koohpayegani, S.A., Pirsiavash, H.: CompGS: Smaller and faster Gaussian Splatting with vector quantization. In: European Conference on Computer Vision (ECCV) (2024)

[33] Nguyen, H., Li, R., Le, A., Nguyen, T.: Dwtgs: Rethinking frequency regularization for sparse-view 3d gaussian splatting (2025), https://arxiv.org/abs/2507.15690

[34] NovelSeek Team, Zhang, B., Feng, S., Yan, X., Yuan, J., Yu, Z., He, X., Huang, S., Hou, S., Nie, Z., Wang, Z., Liu, J., Ma, R., Peng, T., Ye, P., Zhou, D., Zhang, S., Wang, X., Zhang, Y., Li, M., Tu, Z., Yue, X., Ouyang, W., Zhou, B., Bai, L.: NovelSeek: When agent becomes the scientist—building closed-loop system from hypothesis to verification. arXiv preprint arXiv:2505.16938 (2025)

[35] Novikov, A., Vũ, N., Eisenberger, M., Dupont, E., Huang, P.S., Wagner, A.Z., Shirobokov, S., Kozlovskii, B., Ruiz, F.J., Mehrabian, A., et al.: Alphaevolve: A coding agent for scientific and algorithmic discovery. arXiv preprint arXiv:2506.13131 (2025)

[36] Qian, C., Liu, W., Liu, H., Chen, N., Dang, Y., Li, J., Yang, C., Chen, W., Su, Y., Cong, X., Xu, J., Li, D., Liu, Z., Sun, M.: ChatDev: Communicative agents for software development. In: Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL), Volume 1: Long Papers. pp. 15174–15186 (2024)

[37] Ren, S., Wen, T., Fang, Y., Lu, B.: FastGS: Training 3D Gaussian Splatting in 100 seconds. In: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (2026), highlight

[38] Romera-Paredes, B., Barekatain, M., Novikov, A., Balog, M., Kumar, M.P., Dupont, E., Ruiz, F.J.R., Ellenberg, J.S., Wang, P., Fawzi, O., Kohli, P., Fawzi, A.: Mathematical discoveries from program search with large language models. Nature **625**(7995), 468–475 (2024). https://doi.org/10.1038/s41586-023-06924-6

[39] Schmidgall, S., Moor, M.: AgentRxiv: Towards collaborative autonomous research. arXiv preprint arXiv:2503.18102 (2025)

[40] Schmidgall, S., Su, Y., Wang, Z., Sun, X., Wu, J., Yu, X., Liu, J., Moor, M., Liu, Z., Barsoum, E.: Agent Laboratory: Using LLM agents as research assistants. arXiv preprint arXiv:2501.04227 (2025)

[41] Si, C., Yang, D., Hashimoto, T.: Can llms generate novel research ideas? a large-scale human study with 100+ nlp researchers. arXiv preprint arXiv:2409.04109 (2024)

[42] Song, Y., Song, Y., Pfister, T., Yoon, J.: PaperOrchestra: A multi-agent framework for automated AI research paper writing. arXiv preprint arXiv:2604.05018 (2026)

[43] Starace, G., Jaffe, O., Sherburn, D., Aung, J., Chan, J.S., Maksin, L., Dias, R., Mays, E., Kinsella, B., Thompson, W., Heidecke, J., Glaese, A., Patwardhan, T.: PaperBench: Evaluating AI's ability to replicate AI research. In: Proceedings of the 42nd International Conference on Machine Learning (ICML). Proceedings of Machine Learning Research, vol. 267, pp. 56843–56873 (2025)

[44] Swanson, K., Wu, W., Bulaong, N.L., Pak, J.E., Zou, J.: The virtual lab of AI agents designs new SARS-CoV-2 nanobodies. Nature **646**(8085), 716–723 (2025). https://doi.org/10.1038/s41586-025-09442-9

[45] Tancik, M., Weber, E., Ng, E., Li, R., Yi, B., Kerr, J., Wang, T., Kristoffersen, A., Austin, J., Salahi, K., Ahuja, A., McAllister, D., Kanazawa, A.: Nerfstudio: A modular framework for neural radiance field development. In: ACM SIGGRAPH Conference Proceedings (2023)

[46] Tang, J., Xia, L., Li, Z., Huang, C.: AI-researcher: Autonomous scientific innovation. arXiv preprint arXiv:2505.18705 (2025)

[47] Wang, B., Xu, C., Zhao, X., Ouyang, L., Wu, F., Zhao, Z., Xu, R., Liu, K., Qu, Y., Shang, F., Zhang, B., Wei, L., Sui, Z., Zhu, W., Liu, K., Wu, R., Jin, C., Peng, B., Dai, Y., He, C.: MinerU: An open-source solution for precise document content extraction. arXiv preprint arXiv:2409.18839 (2024)

[48] Wang, X., Li, B., Song, Y., Xu, F.F., Tang, X., Zhuge, M., et al.: OpenHands: An open platform for AI software developers as generalist agents. arXiv preprint arXiv:2407.16741 (2024)

[49] Wei, J., Yang, Y., Zhang, X., Chen, Y., Zhuang, X., Gao, Z., Zhou, D., Wang, G., Gao, Z., Cao, J., Qiu, Z., He, X., Zhang, Q., You, C., Zheng, S., Ding, N., Ouyang, W., Dong, N., Cheng, Y., Sun, S., Bai, L., Zhou, B.: From AI for science to agentic science: A survey on autonomous scientific discovery. arXiv preprint arXiv:2508.14111 (2025)

[50] Weng, Y., Zhu, M., Bao, G., Zhang, H., Wang, J., Zhang, Y., Yang, L.: Cycleresearcher: Improving automated research via automated review. arXiv preprint arXiv:2411.00816 (2024)

[51] Wikipedia contributors: Automated Mathematician — Wikipedia, the free encyclopedia (2026), `https://en.wikipedia.org/wiki/Automated_Mathematician`, [Online; accessed 4-May-2026]

[52] Wu, Q., Bansal, G., Zhang, J., Wu, Y., Li, B., Zhu, E., Jiang, L., Zhang, X., Zhang, S., Liu, J., Awadallah, A.H., White, R.W., Burger, D., Wang, C.: AutoGen: Enabling next-gen LLM applications via multi-agent conversation. In: Conference on Language Modeling (COLM) (2024)

[53] Yamada, Y., Lange, R.T., Lu, C., Hu, S., Lu, C., Foerster, J., Clune, J., Ha, D.: The ai scientist-v2: Workshop-level automated scientific discovery via agentic tree search. arXiv preprint arXiv:2504.08066 (2025)

[54] Yan, Z., Low, W.F., Chen, Y., Lee, G.H.: Multi-scale 3d gaussian splatting for anti-aliased rendering. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). pp. 20923–20931 (2024)

[55] Yang, J., Jimenez, C.E., Wettig, A., Lieret, K., Yao, S., Narasimhan, K., Press, O.: SWE-agent: Agent-computer interfaces enable automated software engineering. In: Advances in Neural Information Processing Systems (NeurIPS). vol. 37, pp. 50528–50652 (2024)

[56] Ye, H., Wang, J., Cao, Z., Berto, F., Hua, C., Kim, H., Park, J., Song, G.: ReEvo: Large language models as hyper-heuristics with reflective evolution. In: Advances in Neural Information Processing Systems 37 (NeurIPS) (2024)

[57] Ye, V., Li, R., Kerr, J., Turkulainen, M., Yi, B., Pan, Z., Seiskari, O., Ye, J., Hu, J., Tancik, M., Kanazawa, A.: gsplat: An open-source library for Gaussian Splatting. Journal of Machine Learning Research **26**, 1–15 (2025)

[58] Yuan, J., Yan, X., Zhang, B., Chen, T., Shi, B., Ouyang, W., Qiao, Y., Bai, L., Zhou, B.: Dolphin: Moving towards closed-loop auto-research through thinking, practice, and feedback. In: Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL). pp. 21768–21789 (2025)

[59] Zheng, L., Chiang, W.L., Sheng, Y., Zhuang, S., Wu, Z., Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E.P., Zhang, H., Gonzalez, J.E., Stoica, I.: Judging LLM-as-a-judge with MT-bench and chatbot arena. In: Advances in Neural Information Processing Systems 36 (NeurIPS) Datasets and Benchmarks Track (2023)

[60] Zhu, D., Meng, R., Song, Y., Wei, X., Li, S., Pfister, T., Yoon, J.: Paperbanana: Automating academic illustration for ai scientists. arXiv preprint arXiv:2601.23265 (2026)

Appendix

A Detailed baseline comparison

Table 7: Capability comparison against the closest autonomous-research and program-search systems. ✓= supported, ∼= partial, X= not supported. Verdicts verified against each cited paper; ∼ indicates a related but weaker mechanism (post-hoc rather than in-loop, LLM-judged on outputs rather than measured metrics, manually placed rather than auto-mapped, etc.). Cell-level justifications in Appendix 5.

Capability	AIS-v2 [53]	A-Lab [40]	MLR [26]	AIGS [28]	Curie [24]	PaperOrch. [42]	CoSc [14]	AIE [35]	**Ours**
End-to-end pipeline									
End-to-end executable (no human in loop)	✓	✓	∼	∼	✓	X	∼	✓	✓
Produces a manuscript	✓	✓	X	X	X	✓	X	X	✓
Real-experiment execution	✓	✓	✓	∼	✓	X	X	✓	✓
Domain grounding									
Live-subfield domain backbone	X	X	X	X	X	X	X	X	✓
Verified baseline reproduction	X	X	X	X	X	X	X	X	✓
Ideation and search									
Idea generation	✓	✓	✓	✓	∼	X	✓	X	✓
Idea ranking (LLM-judged)	✓	✓	✓	∼	X	X	✓	X	✓
Idea ranking on real GPU metrics	X	∼	∼	X	∼	X	X	✓	✓
Category-aligned scaffolds	X	X	X	X	X	X	X	X	✓
`EVOLVE-BLOCK` markers	X	X	X	X	X	X	X	✓	✓
Cross-codebase `EVOLVE-BLOCK` auto-mapper	X	X	X	X	X	X	X	∼	✓
Evolutionary / island-based search	X	X	X	X	X	X	∼	✓	✓
Verbal-gradient feedback to ideator	X	X	X	X	X	X	∼	X	✓
Cascade-weighted Elo (smoke / probe / multi-scene)	X	X	X	X	X	X	X	∼	✓
Grounding-conditional ratings (per benchmark–loss pair)	X	X	X	X	X	X	X	X	✓
Verification and audit									
Adversarial falsifier	X	X	X	✓	X	X	X	X	✓
Standing in-loop falsifier (not post-hoc)	X	X	X	∼	X	X	X	X	✓
Falsifier coupled to selection (Elo penalty, veto power)	X	X	X	X	X	X	X	X	✓
Reproducibility / rigor checks	X	X	X	∼	✓	X	X	∼	✓
Claim-backed-verification	X	X	X	X	X	X	X	X	✓
Manuscript synthesis									
Simulated peer review	✓	✓	X	X	X	✓	X	X	✓
Reviewer panel can spawn new training runs (not just edits)	X	X	X	X	X	X	X	X	✓

A.1 Detailed Rationale for Manuscript-Quality Scores

This appendix unpacks Table 4. We walk axis by axis, comparing the six pipelines on the same evaluation framework, and ground each claim in specific sections, tables, or figures from the sample manuscripts released with this submission. The Gemini-3.1-Pro column anchors the discussion; the Claude Opus 4.7 column tracks within ± 5 on every cell (weighted Spearman $\rho = 0.91$ across the full 6×5 manuscript matrix), so directional claims transfer across judges.

The PaperOrchestra row is the most informative comparator for isolating where SplatLab's gains come from. PaperOrchestra receives the code, the experiment logs, the idea tuple, and the Stage 5 audit summary directly from SplatLab runs and writes a manuscript on top of them; it does not run experiments and treats the log as read-only [42]. The gap between SplatLab and PaperOrchestra therefore quantifies what the Stage 6 reviewer-driven loop adds beyond a strong writing pipeline handed verified results.

A.1.1 Citation Practices

This axis measures whether non-trivial claims are tied to appropriate, accurate, well-placed references and whether the bibliography is well-formed. Ranking: SplatLab (95) $\approx$ Human (GT) (94) $>$ PaperOrchestra (75) $>$ AI Scientist-v2 (65) $>$ SingleAgent (52) $\gg$ GPT-5 ET (14).

SplatLab edges out Human (GT) by one point because the Stage 5 claim-to-experiment-ledger gate (Sec. 3.2 Stage 5) blocks the run from terminating while any numerical claim lacks a backing measurement, while the published EGGS paper relies on author discipline alone. Both manuscripts cite Kerbl et al. SIGGRAPH 2023, Mildenhall et al. CACM 2021, and the appropriate 3DGS-variant cluster at the points where each prior work supports a specific claim. PaperOrchestra at 75 carries accurate references for the methods named in the Stage 5 summary it receives, but its bibliography is

Table 8: SplatLab vs. SOTA across multiple target prompts. Top: novel scenes with vanilla 3DGS as baseline. Bottom: SOTA improvements on standard 3DGS benchmarks. *Limitation/fix*: analyst's diagnosis (SOTA row) and validated mechanism (*ours* row); bold marks the winner in each pair.

Setting	Method	Limitation attacked / fix	PSNR↑	SSIM↑	LPIPS↓
Novel scenes (vanilla 3DGS baseline)					
Nebula	3DGS [22]	pinhole ignores OPENCV distortion; SfM gives ≈ 0 stars	32.58	0.914	0.278
	Nebula3DGS-v2 *(ours)*	3DGS-MCMC sampler with saturation-driven star seeder	**36.36**	**0.945**	**0.201**
Bubble	3DGS [22]	SH cannot represent thin-film iridescence; densification stalls on emissive translucency	27.40	0.857	0.337
	BubbleGS *(ours)*	3DGS-MCMC chassis, Snell/Fresnel two-pass conditional shell renderer	**30.11**	**0.906**	**0.224**
Diamond	3DGS [22]	no refraction or specular-highlight model; transparent geometry collapses	22.68	0.857	0.242
	DiamondGS *(ours)*	Snell-law-guided losses, learned per-Gaussian transparency mask	**24.29**	**0.873**	**0.221**
Improving published SOTA					
MipNeRF360	FastGS [37]	$\{0, 1\}$ thresholded pixel-count is frequency-blind	29.12	0.858	0.217
	TileFocalGS *(ours)*	rank-graded per-tile weights, EMA-smoothed across views	**29.69**	**0.869**	**0.194**
MipNeRF360	FastGS [37]	@109 s wall: opacity reset destabilises late refinement after densification stops	25.65	0.751	0.311
	FreezeGS *(ours)*	freeze geometry, disable opacity reset in phase 2	**26.08**	**0.761**	**0.300**
MipNeRF360	splatfacto [45]	@50 s wall: severely under-converged; densification not stabilised	20.53	0.593	0.505
	View-Curriculum-GS *(ours)*	first 15 s on 30% most pose-similar views, then full set	**23.36**	**0.686**	**0.412**
MipNeRF360	Opti3DGS [11]	coarse-to-fine schedule under-densifies high-freq regions	27.71	0.841	0.209
	Opti3DGS-AdaEnt *(ours)*	adaptive densification threshold, opacity entropy regulariser	**28.05**	**0.853**	**0.125**
MipNeRF360	MSAA-3DGS [54]	multi-sample AA blurs fine contrast; underconverged at 30K iters	25.35	0.758	0.369
	MSAA-Bilat *(ours)*	bilateral grid contrast recovery, $+15$K extra iters	**26.19**	**0.791**	**0.293**
MipNeRF360	GNS [10]	15%-budget regime sacrifices AA and refinement	25.97	0.891	**0.095**
	GNS-AA *(ours)*	AA rasterisation, denser SfM init, post-densification regularisers	**26.15**	**0.902**	0.097
MipNeRF360	CompGS [32]	static codebook drift; centroids stale by late training	28.28	0.894	0.153
	CompGS-EMA *(ours)*	EMA centroid updates, gradient-based codebook refinement	**28.50**	**0.899**	**0.146**
LLFF	DWTGS [33]	wavelet basis under-constrained without high-freq supervision	18.68	0.510	0.374
	DWTGS-Patch *(ours)*	patch structure loss, opacity/normal/depth regularisers	**21.09**	**0.725**	**0.281**

shorter than SplatLab's because it does not have access to the cross-run paper store maintained by the Stage 1 Researcher; the gap is roughly 8–12 references on average across the five prompts.

AI Scientist-v2 at 65 carries seven properly resolved references in the AGIL sample, anchored by accurate entries for Kerbl et al. 2023, Ren et al. 2025 (FastGS), and Chen et al. 2025 (DashGaussian). Two entries register as low-confidence: the RAP citation (Yang et al.) carries arXiv ID `2602.19753`, which parses to February 2026 and could not be confirmed against arXiv listings at review time, and the Qi 2025 entry cites "Journal of Computer Science and Artificial Intelligence" without volume or page numbers. Two suspect entries in a seven-entry bibliography is what pulls the score below PaperOrchestra.

SingleAgent at 52 reflects a pattern common to one-shot agentic outputs: prior work is named in prose (FastGS, DashGaussian, TileFocalGS, Speedy-Splat) but the SuperFocalGS sample has no bibliography file at all. GPT-5 ET at 14 trends low because the dominant failure mode across the five prompts is fabricated rather than missing citations: plausible-looking entries with wrong venues, a recurring CVPR-vs-ECCV swap on densification papers, and one entirely fabricated paper attributed to a real author across the prompt set.

A.1.2 Coverage and Completeness

Coverage measures whether related work spans 3DGS variants, NeRF heritage, and adjacent rendering or optimisation work, and whether 2024–2026 papers appear where relevant. Ranking: Human (93) $>$ SplatLab (89) $>$ PaperOrchestra (81) $\gg$ SingleAgent (48) $>$ GPT-5 ET (24) $\approx$ AI Scientist-v2 (22).

Human (GT) covers four lines (NeRF heritage, 3D-only Gaussian methods, geometry-regularised methods, hybrid representations) with Fig. 2 right surveying nine prior methods on five attributes. SplatLab sits 4 points below because its Stage 1 Researcher occasionally over-indexes on autonomous-research papers when the prompt is purely 3DGS, inflating breadth at the cost of focus. PaperOrchestra at 81 is bottlenecked by the Stage 5 summary it receives: the summary names the directly-relevant prior work but does not survey the broader 3DGS / NeRF heritage that SplatLab's Stage 6 related-work agent retrieves independently from the cross-run store.

AI Scientist-v2 at 22 names six methods in seven sentences in Sec. 2 of the AGIL sample and stops there. Sitzmann et al. 2021 (Light Field Networks) is cited as "meta-learning in rendering" but is not actually a meta-learning paper in the sense AGIL invokes. SingleAgent at 48 covers the fast-3DGS cluster (FastGS, DashGaussian, Speedy-Splat, TileFocalGS) but skips foundational anti-aliasing and surface-reconstruction work. GPT-5 ET at 24 trends narrow on the proposed mechanism with antecedents skipped.

A.1.3 Critical Analysis and Synthesis

SplatLab leads at 93, with Human (GT) two points behind at 91, because of the Stage 2 Limitation Brainstormer: every claim is anchored to an L-ID–B-ID pair that names both the limitation in prior work and the measured bottleneck it implicates, so synthesis is a structural property of the manuscript rather than a writing choice. PaperOrchestra at 74 is the largest gap to SplatLab on any axis (19 points), and it isolates the value of reviewer-driven re-experimentation: PaperOrchestra cannot demand new experiments to address gaps surfaced during writing, so when its analysis identifies an open question the manuscript can only acknowledge it. The SplatLab reviewer panel (Sec. 3.2 Stage 6) classifies comments as Text Fix, New Ablation, or New Experiment, and the latter two re-enter Stage 4 with the comment as a verbal-gradient seed. This is what closes 14 of the 19 points of the gap on average across the five prompts.

AI Scientist-v2 at 28 and GPT-5 ET at 29 cluster low for the same reason: the manuscripts state a thesis and jump to a solution without measuring the diagnosed problem. The AGIL sample asserts in Sec. 1 that "high-frequency and view-dependent regions are treated identically to flat regions, leaving quality on the table" but presents no diagnostic to support the claim. The supplementary scene-difficulty correlation in App. .4 conflates "hard scenes" with "scenes where AGIL gains the most," which is a tautology rather than a diagnosis.

A.1.4 Organisation and Writing

SplatLab at 95 edges Human (GT) at 94 because the Stage 6 writer suite runs five specialised writers in parallel under a Figure Checker that audits axis labels, legends, and number-vs-caption agreement, while the published EGGS paper relies on author proofreading. PaperOrchestra at 81 is competitive on prose quality but loses points on figure-text consistency: the Stage 5 summary it receives includes result tables but not the underlying experiment ledger, so its plots occasionally cite axis quantities that the source data does not actually contain.

AI Scientist-v2 at 28 has clean workshop-format structure but the AGIL sample's Figs. 3–4 are the controlling problem on this axis. Both figures claim to show per-scene reconstruction-error and predicted-importance maps; both render as visually-uniform random patterns with no recognisable scene content (no ground, no foliage, no walls) despite captions describing "rendered images", "predicted importance scores", and "final Gaussian density". Tab. 1 of the supplementary reports per-scene gains of 0.018 ± 0.001 LPIPS across all seven scenes, a suspicious uniformity for a method whose stated thesis is scene-specific adaptation.

GPT-5 ET at 22 averages low across the five prompts: dense-prose pages with sparse structural cues. SingleAgent at 65 has the cleanest surface prose in the batch outside Human (GT), SplatLab, and PaperOrchestra but loses on substance.

A.1.5 Positioning and Novelty

Human (GT) leads at 89, with SplatLab two points behind at 87, the only axis where the published paper edges SplatLab. The published EGGS paper locates its hybrid 2D+3D contribution against HybridGS (image-frame 2D) and HorizonGS (per-task split) with novelty pinned to three concrete primitives; this kind of taxonomic positioning is where author insight still matters beyond what an automated pipeline can audit. SplatLab at 87 articulates five novelties against named systems (cascade-weighted Elo against [14], falsifier with Elo penalty against [28], claim-backed verification against [29] and [42], verified-reproduction backbone via [19, 18], and the 3DGS taxonomy as an extension of the EVOLVE-BLOCK contract from [35]); Tab. 1 audits this against eight competing systems on 19 attributes.

PaperOrchestra at 76 inherits clean positioning from the Stage 5 idea tuple but cannot sharpen it: when the writing pass surfaces a positioning gap, PaperOrchestra cannot run a follow-up experiment to address it. SingleAgent at 70 carries plausible but unverified positioning; AI Scientist-v2 at 42 positions AGIL against "fixed view-agnostic thresholds" as a category but does not locate the contribution against specific learned-importance predictors. GPT-5 ET at 38 over-claims relative to evidence on the page.

A.1.6 Relevance and Focus

SplatLab at 93 leads here because the Stage 6 Mode-Gate routes runs that fail the dual-grounding test into Mode A (research log) rather than Mode B (full manuscript), so the five sample manuscripts that reached Mode B by construction have experiments that test their stated contribution. Human (GT) at 91 maintains relevance via tight section-to-ablation alignment. PaperOrchestra at 83 inherits the Mode-Gate filtering by virtue of receiving only Mode B runs, but loses points where the Stage 5 summary leaves ambiguities the writing stage cannot resolve without re-entering experimentation.

AI Scientist-v2 at 48 is mid-range; the AGIL sample's stated thesis (scene-specific adaptive importance prediction) is supported by a generalisation study (App. .5) showing that a single-scene predictor generalises poorly ($r = 0.71$ vs 0.87 per-scene). The relevance penalty comes from Fig. 3's claim that "high importance concentrates on specular regions, view-dependent edges, and high-frequency details," which is not visible in the rendered figure: the importance map is uniform noise. The text-figure mismatch costs roughly 15 points on this axis.

GPT-5 ET at 42 reflects the cross-prompt pattern of sections introducing machinery the experiments never use. SingleAgent at 70 is focused but hollow: every section addresses the proposed mechanism, but Sec. 4 carries section numbering for content that does not exist (Tabs. 1–3 are placeholder values).

A.2 Per-Pipeline Summary

Human (GT), 93 overall. The ceiling on this batch for coverage, positioning, and the ground-truth anchor on every axis. SplatLab matches or exceeds it on citation practices and organisation; the gap on the remaining axes is in single digits.

SplatLab, 90 overall. Within 3 points of Human (GT) on every axis, ahead on citation practices and organisation by 1 point each. Trails Human (GT) by 4 points on coverage (Stage 1 over-indexing on autonomous-research literature) and 2 points on positioning (taxonomic insight where author judgement still matters).

PaperOrchestra, 79 overall. The right writing-only baseline. Trails SplatLab by 11 points overall, with the largest single-axis gap on critical analysis (19 points) and organisation (14 points). The critical-analysis gap isolates the value of the Stage 6 reviewer-driven loop that can spawn new training runs; the organisation gap isolates the value of the parallel writer suite plus Figure Checker. Beats every other automated pipeline in the batch by at least 41 points on overall, which establishes PaperOrchestra as a strong baseline rather than a straw man.

SingleAgent, 38 overall. Mid-range on positioning (70) and relevance (70) when the writing pass succeeds, but a hard ceiling on the verification axes: no bibliography, placeholder result tables, no diagnostic experiments. Competitive on writing surface, not on substance.

AI Scientist-v2, 32 overall. Trails on every axis except citation practices. The AGIL sample exhibits three failure modes that drive the low overall score: visualisation figures that do not match

their captions (Figs. 3–4 read as random noise), suspiciously uniform per-scene gains in Tab. 1 of the supplementary (0.018 ± 0.001 across seven scenes), and a thesis-versus-diagnostic gap where the claimed view-dependence problem is asserted but never measured.

GPT-5 ET, 17 overall. The lowest mean in the batch on five of seven axes. Across the five prompts the pipeline exhibits fabricated citations, sparse coverage, narrow positioning, and abstract claims unbacked by the experiment table. The TileFocalGS sample released alongside this submission is representative of GPT-5 ET's high-end outputs; the other four prompts pull the average down.

A.3 Cross-Pipeline Observations

Four batch-level patterns are worth flagging. First, citation accuracy and critical analysis correlate at $r = 0.84$ across the 30 manuscripts: pipelines that cite real papers also synthesise across them. Second, the SplatLab-versus-PaperOrchestra gap concentrates on critical analysis ($+19$) and organisation ($+14$), which directly maps to the two stages PaperOrchestra cannot reach: the reviewer-driven re-experimentation loop and the parallel writer suite with figure auditing. Third, the only axis where SplatLab trails Human (GT) by more than 3 points is positioning (87 vs 89), the axis most dependent on taxonomic insight rather than process. Fourth, visual polish at the section-and-figure level decouples from substance: the AI Scientist-v2 sample scores 65 on citation practices but 28 on organisation because the figures fail a check against figure content, while SingleAgent scores 65 on writing but 38 on overall because clean prose cannot substitute for executed experiments.

A.4 Cross-Run Audit: All 16 Manuscripts

Table 9 catalogues every paper produced by the autonomous lab during the study window. One row per run; one run is one independent dispatch of the `/research` master orchestrator on a fresh ledger and a fresh workspace. The columns track the target method (when one was specified at run-start), the evaluation dataset and scene set, the prompt regime, the method name the pipeline ultimately committed to in its `paper/main.pdf`, the locally reproduced baseline, the final headline result on whichever metric the run measured, the delta vs. that baseline, the number of trained experiment branches recorded in the ledger, the compute spent in GPU hours, and an audit verdict on the manuscript's honesty.

Audit verdicts. We classify each manuscript as one of: (✓) verified – a clean positive Δ above the measured noise floor, with reviewer round-2 returning weak-accept or better and the paper-quality-checker reporting zero remaining critical hallucinations; (○) honest-marginal – the run delivered a Δ within the noise floor and the manuscript reframes the contribution accordingly (LPIPS-Pareto, scene-conditional gain, or a systematic-evaluation framing) rather than over-claiming PSNR; (□) workshop-style – the contribution is a benchmark, an editing pipeline, a calibration channel, or a different-metric task, where PSNR is not the primary axis; ($\times$) failed – the run terminated without a positive result on its own self-stated target. Verdicts are read directly from the ledger (`best.classification`, `revision_done remaining_critical`, and round-2 `review_received` events) – nothing in this table is rephrased after the fact.

Prompt regime legend. free = open-ended creative prompt ("design a novel 3DGS…"); target = a specific paper / GitHub repository URL was provided at run-start as the SOTA to beat; scene = a custom dataset directory was provided (Nebula, Bubble, etc.) with the request to beat splatfacto on it; workshop = a workshop-style brief, often without a single PSNR target.

Metric notation. PSNR is reported in dB unless flagged: † 3D view-consistency IoU; ‡ instruction-success / edit-locality rate; § negative log-likelihood (calibration); ¶ AUROC@25 (auto-annotation gate). "–" means the run produced no headline number against a single baseline (typically benchmark papers).

What the table shows. Of the sixteen manuscripts: five (#1, #3, #6, #12, #13) are clean verified positives where our generated method beats its locally-reproduced baseline by at least the measured noise floor on the headline metric, and round-2 reviewers returned weak-accept or better; five (#2, #4, #5, #11, #16) are honest-marginal – the run executed cleanly but its own measurements showed the Δ landed within the noise floor, and the manuscript reframes the contribution as a systematic-evaluation, scene-conditional gain, or LPIPS-Pareto improvement rather than a PSNR win; five (#7, #8, #9, #14, #15) are workshop-style submissions whose contribution is a benchmark, calibration channel, or

editing pipeline, where PSNR is not the primary axis; and one (#10) is a frank failure recorded in the ledger. The audit column is read mechanically from the ledger, not edited after the fact.

Observations. (i) Runs that were prompted with a custom dataset (scene prompts, rows #12, #13) have the largest deltas; both deliberately attack a previously-untrained scene class where vanilla splatfacto is known to be weak. (ii) Runs targeting a specific recent paper (target prompts, rows #3, #4, #10) split between one verified beat (FreezeGS, #3, $+0.43$ dB on FastGS), one honest-mixed (CSNVF-NRSH, #4), and one acknowledged failure (LockEtaLangevin, #10) – consistent with the literature observation that the recent-SOTA paper graveyard leaves little headroom. (iii) Runs with the highest N (#12 with 47 trained branches, #6 with 38) tend to commit cleaner manuscripts with stronger ablations, suggesting branch-density correlates with audit verdict.

B Generated manuscripts

Each PDF below is a single generated manuscript rendered as a 3×3 grid of paper pages per appendix page. SplatLab produces 16 manuscripts; 5 deliver verified PSNR gains of +0.18 to +3.78 dB on their reproduced target, 5 land within the noise floor and reframe the contribution accordingly, 5 target non-PSNR axes (benchmarks, calibration, editing pipelines), and 1 is a recorded failure.

View-Curriculum-GS: Pose-Similarity View Scheduling for 50-Second 3D Gaussian Splatting

Anonymous Authors




Figure 1: **View-Curriculum-GS.** Training on only the 30% most pose-similar views for the first 15 s gives the optimiser a coherent coarse scaffold before all views are introduced at 15 s. On the seven Mip-NeRF 360 scenes, this simple change yields +2.83 dB average PSNR at a 50-second wall-clock budget versus time-capped splatfacto, beating the baseline strictly on 6 of 7 scenes (kitchen within one seed σ).

Abstract

3D Gaussian Splatting [Kerbl et al., 2023] is typically trained for tens of minutes; its behaviour under a strict seconds-scale wall-clock budget is poorly characterized. We study a 50-second training regime on the seven Mip-NeRF 360 scenes [Barron et al., 2022] and introduce *view-curriculum-gs*, a staged view-pool curriculum for 50-s 3DGS training: phase one trains on a small restricted view pool for 15 s, and phase two progressively expands to the full view set over the remaining 35 s. Against a time-capped splatfacto [Tancik et al., 2023b] baseline that reaches 20.53 dB average PSNR on Mip-NeRF 360 at 50 s, view-curriculum-gs reaches 23.36 dB (+2.83 dB) and beats the baseline on 6 of 7 scenes strictly, with kitchen within one seed standard deviation. A leave-one-component-out ablation isolates the driver: the phase-1 duration (C2) and the progressive expansion ramp (C4) each contribute +1.40–1.45 dB, while the pose-similarity centrality sort is near-neutral – random phase-1 subsets match, so *schedule* rather than *which* views is the mechanism. We also report a rigorous 50-s wall-clock benchmark with seven ablated hooks and a negative result: naive stacking of the top hooks does not compose.

1 Introduction

3D Gaussian Splatting [Kerbl et al., 2023] has become the dominant real-time radiance-field representation, reaching NeRF-quality novel-view synthesis [Mildenhall et al.,

2020, Barron et al., 2022] while rendering at hundreds of frames per second. Training, however, still takes 20–40 minutes per scene on a modern GPU [Kerbl et al., 2023, Tancik et al., 2023b]. A recent line of work pushes this down: Taming-3DGS trains in roughly 10 minutes [Mallick et al., 2024], DashGaussian reaches 27.9 dB in 200 s on Mip-NeRF 360 [Chen et al., 2025c], FastGS targets 100 s [Ren et al., 2026], and EDGS shows that dense initialization reaches 3DGS quality in a fraction of the usual iterations [Kotovenko et al., 2026]. The direction of travel is clear, but the regime below two minutes is under-studied, and most papers report mixed-budget results that make apples-to-apples comparison hard.

We ask a simpler question: how much image quality can a 3DGS pipeline extract from *exactly* 50 seconds of wall-clock training on Mip-NeRF 360? Fifty seconds is short enough that the default splatfacto schedule, tuned for 30k iterations, collapses to ~20.5 dB average PSNR, an 8.3 dB drop from its full-budget 28.8 dB. It is also long enough that the bottleneck is not kernel launch overhead but genuine algorithmic trade-offs: what to initialize, which views to sample, which Gaussians to split, and which backward passes to skip. This regime mirrors practical deployments in capture-preview, editing previews, and embedded reconstruction, where users want a usable splat within a minute.

The gap we address is *view-sampling scheduling*. Existing fast-3DGS work progresses along the frequency axis (DashGaussian [Chen et al., 2025c]), the densification axis (Taming [Mallick et al., 2024], FastGS [Ren et al., 2026]), or the backward-pass axis (SkipGS [Li et al., 2026]). None schedules which *views* the optimizer sees. Under a 50-second budget, the first few hundred iterations define the coarse geometry; drawing from all 200+ input views uniformly lets gradient noise from inconsistent view coverage dominate that early phase. We propose a two-phase *view-pool curriculum*: phase one (15 s) trains on a small restricted subset of views; phase two (35 s) progressively expands the pool to all views via a linear ramp. Our ablation (Sec. 4.5) shows that the *schedule* – the phase-1 duration and the progressive expansion ramp – is what drives the gain, each contributing +1.40–1.45 dB. The specific centrality heuristic we use to pick the phase-1 subset (pose-graph similarity to the median camera) is near-neutral: a random phase-1 subset matches it within noise.

We implement view-curriculum-gs and six additional 50-second-regime candidates (dense initialization, time-budgeted densification, SH/cap reduction (fifty-sec-gs), a two-phase loss, sparse backward, and a fused densify score) as swap-in methods on a nerfstudio-compatible template, and evaluate on all seven Mip-NeRF 360 scenes against a time-capped splatfacto baseline at 20.53 dB. view-curriculum-gs reaches 23.36 dB average PSNR, a +2.83 dB gain, and beats the baseline strictly on 6 of 7 scenes (kitchen within one seed σ). The measured noise floor is $\sigma_{PSNR} = 0.087$ dB on garden. We also test whether the top hooks compose; naive stacking of the curriculum, a two-phase loss, and a fused densify score does *not* improve over the curriculum alone, a negative result we report as such.

Contributions:

- **A staged view-pool curriculum for 50-s 3DGS training**: a 15 s phase-1 on a restricted subset followed by a 35 s linear ramp to the full view set. This yields +2.83 dB average PSNR on Mip-NeRF 360 at a 50-second training budget. Ablations attribute the gain to the schedule (phase-1 duration and progressive expansion), not to the centrality heuristic used to choose phase-1 views.
- A rigorous 50-second wall-clock 3DGS benchmark on Mip-NeRF 360, with seven ablated hooks covering initialization, loss, densification, backward sparsity, and schedule interventions, and a measured noise floor.
- A negative result: naive stacking of the three top-performing hooks (curriculum, two-phase loss, fused densify score) does not improve over the curriculum alone.

2 Related Work

3D Gaussian Splatting foundations. 3D Gaussian Splatting [Kerbl et al., 2023] replaced the neural volumetric rendering pipeline of NeRF [Mildenhall et al., 2020, Barron et al., 2021, 2022, 2023] and its point-based predecessors [Xu et al., 2022, Aliev et al., 2020, Zhang et al., 2020] with an explicit set of anisotropic Gaussians splatted through the EWA formulation of Zwicker et al. [2002, 2001]. The original implementation trains 30k iterations with Adam [Kingma and Ba, 2015] on SfM points from COLMAP [Schönberger and Frahm, 2016, Schönberger et al., 2016] and relies on an Adaptive Density Control (ADC) loop that clones and splits Gaussians from gradient statistics. Mip-Splatting [Yu et al., 2024a] introduced 3D smoothing and 2D Mip filters to remove scale-dependent aliasing, while Analytic-Splatting [Liang et al., 2024] and multi-scale rendering [Yan et al., 2024] continue that anti-aliasing thread. 3DGS-MCMC [Kheradmand et al., 2024] reinterprets Gaussians as samples from an SGLD chain and shows that with relocation of dead Gaussians even random initialisation suffices. Surface-oriented variants such as 2DGS [Huang et al., 2024], GOF [Yu et al., 2024b], and SuGaR [Guédon and Lepetit, 2024] recast the primitive for geometry recovery, and anchor-structured methods [Lu et al., 2024, Ren et al.,

2025] impose hierarchy on the primitive set. The gsplat CUDA backend [Ye et al., 2025] and the nerfstudio harness [Tancik et al., 2023b] have become the de facto substrate for fast-training research, and recent surveys give the broader landscape [Wu and Yi, 2024, Fei et al., 2025, Wu et al., 2024, Dalal et al., 2024, Ding et al., 2025, Tosi et al., 2024]. Our work targets this standard stack: splatfacto [Tancik et al., 2023b] run through gsplat [Ye et al., 2025] on the Mip-NeRF 360 protocol [Barron et al., 2022].

Fast and efficient 3DGS training. A dense literature reduces the 15–28 min training of Kerbl et al. [2023] by roughly an order of magnitude. On the algorithm side, Taming 3DGS [Mallick et al., 2024] replaces gradient-driven ADC with a budget-constrained purely-constructive schedule and introduces per-splat backprop, reaching 27.53 dB in 10 m 49 s; Mini-Splatting [Fang and Wang, 2024a] and Mini-Splatting2 [Fang and Wang, 2024b] compress the representation to ~0.6 M Gaussians through blur-split, depth reinitialisation, and aggressive early cloning with occlusion culling (3 m 34 s at 27.33 dB). DashGaussian [Chen et al., 2025c] couples a frequency-guided resolution curriculum to a concave-up primitive growth curve, reaching 27.92 dB in 3 m 14 s. Turbo-GS [Dhiman et al., 2024] adds appearance gradients and densifies every 20 iterations under a convergence-aware budget, and Trick-GS [Armagan et al., 2025] bundles several such heuristics. On the system side, Speedy-Splat [Hanson et al., 2024] introduces SnugBox/AccuTile tight tile intersection, Faster-GS [Hahlbohm et al., 2026] fuses kernels and coalesces memory for 4 m 31 s training, FlashGS [Feng et al., 2025] and StopThePop [Radl et al., 2024] restructure the rasterizer around sort-stable tiles, and Grendel-GS [Lu et al., 2025] parallelises across GPUs. SkipGS [Li et al., 2026] and Group Training [Wang et al., 2025a] skip or cycle through subsets of backward work. The very fastest published numbers come from LiteGS [Liao et al., 2025], whose warp-based rasterizer and variance-driven densification reach 145 s at 27.70 dB, Shorter-Gaussian-Lists [Liu and Han, 2026], which adds scale reset and a per-pixel entropy constraint on the LiteGS backbone for 99.58 s at 27.55 dB, and FastGS [Ren et al., 2026], whose multi-view consistent densification/pruning reaches ~100 s at quality comparable to DashGaussian. 3DGS-LM [Höllein et al., 2025] and the second-order families 3DGS^2 [Pehlivan et al., 2025] and 3DGS^2-TR [Hsiao et al., 2026] exploit curvature for ~5–10× fewer iterations, while the SIGGRAPH-Asia challenge entry Fast-Converging 3DGS [Zhang et al., 2025b] is, to our knowledge, the only result reporting ~60 s training with >28 dB — but it uses challenge-specific COLMAP poses and non-standard evaluation.

Positioning. None of the above methods reports a sub-60-second wall-clock result on the *standard* Mip-NeRF 360 outdoor+indoor evaluation. FastGS [Ren et al., 2026] at ~100 s, LiteGS-turbo [Liao et al., 2025] at 145 s, and Shorter-Gaussian-Lists [Liu and Han, 2026] at 99.58 s are the frontier, with Mini-Splatting2 [Fang and Wang, 2024b] close behind at 92–214 s. Our 50-second regime sits strictly below all of them on the same benchmark and protocol. We do not compete on the 100–500 s tier; we characterise what happens when the budget is tightened by a further 2×, and we show that under that budget a data-ordering intervention — a pose-similarity view curriculum — outperforms the representation-, optimizer-, and rasterizer-level interventions that dominate the 100 s tier.

Training curricula and coarse-to-fine schedules. Progressive schedules, well known in NeRF-era training, transfer naturally to 3DGS. EAGLES [Girish et al., 2024] ramps resolution from 1/4 to full to cut early-iteration cost. FreGS [Zhang et al., 2024a] anneals a frequency-domain regulariser from low to high band, and Opt3DGS [Huang et al., 2025b] and Opti-3DGS [Farooq et al., 2025] combine low-pass rendering filters with progressive sharpening. RAIN-GS [Jung et al., 2024] uses a progressive low-pass filter to obtain coarse-to-fine convergence from sparse initialisations, ResGS [Lyu et al., 2025] builds an image-pyramid Gaussian hierarchy, and DashGaussian [Chen et al., 2025c] derives resolution transitions from a frequency energy analysis. GaussianPro [Cheng et al., 2024] progressively propagates planar geometry, and Gaussian-On-The-Fly [Xu et al., 2025b] progressively ingests images as they arrive. Frequency-aware decomposition [Lavi et al., 2025] and FDS-GS [Zhang et al., 2025a] further separate the training signal by band. All of these are curricula over *what is rendered*: resolution, frequency, or geometric detail. DNGaussian [Li et al., 2024] and depth-regularised 3DGS [Chung et al., 2024] add a signal-level curriculum via monocular depth supervision, which implicitly orders easy planar regions before hard foliage.

Positioning. We introduce a curriculum over the orthogonal axis: *which views* the optimiser sees, ordered by SE(3) pose-graph similarity. In the first 15 s we expose only the 30% of views that are mutually most consistent, so that the initial geometry forms from a spatially coherent block of evidence before wide-baseline views re-enter at 15 s. None of the progressive works above re-weights the training set by inter-view similarity; DashGaussian's resolution curriculum [Chen et al., 2025c] and EAGLES' resolution ramp [Girish et al., 2024] operate on the image pyramid, not on the view graph. Curriculum learning in the classical sense is therefore under-explored in 3DGS.

Smart initialisation. Better priors shorten every subsequent optimisation step. EDGS [Kotovenko et al., 2026] replaces sparse SfM with dense RoMa-matched triangulation and obtains 28.02 dB without any ADC. RadSplat [Niemeyer et al., 2024] seeds 3DGS from a pre-trained Zip-NeRF for 28.14 dB with 10× fewer Gaussians. GaussianPro [Cheng et al., 2024] propagates MVS patch-matches into textureless regions. DNGaussian [Li et al., 2024] and depth-regularised 3DGS [Chung et al., 2024] use monocular depth priors; DepthSplat [Xu et al., 2025a] predicts depth and Gaussians jointly in a feed-forward pass. FSGS [Zhu et al., 2024] and CorGS [Zhang et al., 2024b] densify sparse-view priors for few-shot setups. For dense monocular depth, Depth-Anything v2 [Yang et al., 2024a] is the current off-the-shelf backbone. The Fast-Converging 3DGS [Zhang et al., 2025b] entry combines monocular depth, a feed-forward predictor, and per-Gaussian parallel backprop for its ~60 s challenge result.

Positioning. We deliberately keep the initialisation unchanged — COLMAP sparse points, as in splatfacto [Tancik et al., 2023b] — to isolate the effect of the view-sampling curriculum. Our ablations include a dense-depth initialisation variant analogous to EDGS [Kotovenko et al., 2026] and find that, under a 50 s budget, the view curriculum alone is a larger lever.

Density control, pruning, and compact representations. Beyond speed, a parallel line reshapes ADC itself. AbsGS [Ye et al., 2024] resolves gradient-collision by using absolute view-space gradients; Pixel-GS [Zhang et al., 2024c] weights gradients by the number of rendered pixels. SteepGS [Wang et al., 2025c] chooses split directions from the local Hessian, Efficient Density Control [Deng et al., 2024] introduces long-axis split, and Revising-Densification [Bulò et al., 2024] and Improving-ADC [Grubert et al., 2025] replace the fixed gradient threshold with an exponentially ascending schedule that doubles convergence speed. Generative Densification [Nam et al., 2024], Decomposing-Densification [Huang et al., 2025a], and Improving-Densification [Deng et al., 2025a] phase split-only and split-plus-clone stages, and Gradient-Natural-Selection [Deng et al., 2025b] imposes an opacity-decay pressure that retains only well-supported Gaussians. On the compaction side, LightGaussian [Fan et al., 2024], Compact3D [Lee et al., 2024], EAGLES [Girish et al., 2024], HAC [Chen et al., 2024], HAC++ [Chen et al., 2025b], Compressed3DGS [Niedermayr et al., 2024], CompGS [Navaneet et al., 2024], Reducing-the-Memory-Footprint [Papantonakis et al., 2024b], and EfficientGS [Liu et al., 2024] all prune or quantise the Gaussian set by one or two orders of magnitude. PUP-3DGS [Hanson et al., 2025], LP-3DGS [Zhang et al., 2024d], EV-Splitting [Papantonakis et al., 2024a], Cone-GS [Baranowski et al., 2025], GDAGS [Zhang et al., 2026], BoGauss [Pateux et al., 2025], NeuralGS [Tang et al., 2025], GSScale [Lee et al., 2025a], Micro-Splatting [Lee et al., 2025b], Vol3DGS [Wang et al., 2025b], and LGTM [Lao et al., 2026] supply additional pruning criteria or structural constraints. 3D-HGS [Li et al., 2025], Effective-Rank [Hyung et al., 2024], Spec-Gaussian [Yang et al., 2024b], GES [Hamdi et al., 2024], GaussianShader [Jiang et al., 2024], and neural sorting for 3DGS [Chen et al., 2025a] reshape the primitive or its ordering.

Positioning. These methods change the *representation* or the *density-control policy*; our primary intervention is orthogonal — it leaves ADC, the rasterizer, the primitive, and the loss untouched, and reorders the supervision. In our ablation portfolio (Section 4) we reimplement lightweight variants of budget densification [Mallick et al., 2024], skip-backward [Li et al., 2026], and aggressive clone-plus-cull [Fang and Wang, 2024b] to confirm that each remains beneficial at the 50 s budget, but none individually matches the view curriculum.

Summary of contribution relative to prior art. To our knowledge, this is the first study that explicitly targets a strict 50-second wall-clock training budget on the full Mip-NeRF 360 [Barron et al., 2022] outdoor+indoor benchmark with standard SSIM [Wang et al., 2004] and LPIPS [Zhang et al., 2018] evaluation. Every published sub-150-second 3DGS method [Liao et al., 2025, Liu and Han, 2026, Ren et al., 2026, Fang and Wang, 2024b, Chen et al., 2025c, Mallick et al., 2024] either operates above 90 s on this protocol or relies on challenge-specific conditions [Zhang et al., 2025b]. Within this regime we show that a pose-similarity view curriculum is the single largest lever, beating lightweight reimplementations of initialisation-, loss-, densification-, and schedule-level interventions (inspired by Kotovenko et al. [2026], Li et al. [2024], Ye et al. [2024], Mallick et al. [2024], Li et al. [2026], Grubert et al. [2025]) on all seven Mip-NeRF 360 scenes in our portfolio benchmark (Sec. 4).

3 Method

3.1 Preliminaries

3D Gaussian Splatting Kerbl et al. [2023] represents a scene as a set of anisotropic Gaussian primitives $\{g_i\}_{i=1}^M$ parameterized by a mean $\mathbf{p}_i \in \mathbb{R}^3$, a covariance $\Sigma_i = R_i S_i S_i^\top R_i^\top$ factored into a rotation quaternion and a diagonal scale, an opacity $\alpha_i \in (0,1)$, and view-dependent colour via spherical harmonics. An image is rendered by EWA splatting and front-to-back alpha compositing,

trained against an L1+SSIM photometric loss over a dataset of posed views $\mathcal{V} = \{(I_v, \mathbf{T}_v)\}_{v=1}^N$.

3.2 Problem formulation

We study 3DGS in the *seconds regime*: a strict $T_{\text{budget}} = 50$ s wall-clock training window per scene on a single A6000 GPU. Time-capped vanilla splatfacto Tancik et al. [2023a] reaches only 20.53 dB average PSNR on Mip-NeRF 360 Barron et al. [2022] – a 8.31 dB gap below its own 30k-iteration ceiling (28.84 dB). The bottleneck is not the renderer; it is the optimiser's *path*. Uniform random view sampling forces early gradients to fight multi-view inconsistency before the coarse scaffold has formed: every step pulls the same under-constrained Gaussians toward a different view, producing high-variance updates and wasted compute.

3.3 Staged view-pool curriculum

We propose **view-curriculum-gs**, a two-phase, wall-clock-gated restriction of the training view pool that delivers a small subset to the optimiser first and then progressively re-admits the full dataset once a coarse geometry exists. The mechanism of gain, as the ablation in Sec. 4.5 confirms, is the *staged exposure schedule* – not the particular rule used to pick the phase-1 subset. We first describe a pose-similarity heuristic for subset selection, then show in Sec. 4.5 that random selection matches it at near-zero cost and that the dominant contributors are phase-1 duration and progressive re-admission. The method touches only the DATA hook (Nerfstudio's `FullImageDatamanager`); the renderer, loss, densifier, and optimiser are untouched. The pipeline is shown in Fig. 2.

Phase-1 subset selection (pose-similarity, optional). Given the N training cameras-to-world matrices $\mathbf{T}_v = [R_v \mid \mathbf{c}_v] \in \mathbb{R}^{3\times4}$, we define a pairwise pose-similarity

$$s(i,j) = -\frac{\|\mathbf{c}_i - \mathbf{c}_j\|_2}{d_{\max}} + \lambda_{\text{rot}} \frac{\operatorname{tr}(R_i^\top R_j)}{3}, \quad (1)$$

where $d_{\max} = \max_{i,j} \|\mathbf{c}_i - \mathbf{c}_j\|_2$ normalises positions so the two terms live on comparable scales. The first term penalises camera-centre distance; the second rewards co-aligned look-directions since $\operatorname{tr}(R_i^\top R_j)/3 \in [-\frac{1}{3}, 1]$ is a proxy for cosine of the relative rotation angle. We set $\lambda_{\text{rot}} = 0.5$.

Centrality order. A *centrality* score aggregates similarity against all other cameras:

$$\operatorname{cen}(v) = \sum_{u \neq v} s(v,u). \quad (2)$$

Sorting by $\operatorname{cen}(\cdot)$ descending yields an index list $\pi = [\pi_1, \pi_2, \ldots, \pi_N]$ with the most "central" view first – typically a camera near the positional centroid whose rotation aligns with the average look-direction. The cost is a single $O(N^2)$ `cdist` and one `einsum`, evaluated once at `__init__` before any optimisation steps (< 20 ms for $N < 300$). As shown in Sec. 4.5, substituting a uniformly-random phase-1 subset matches this heuristic within noise; we therefore treat the pose-similarity sort as an implementation detail and the staged schedule below as the load-bearing contribution.

Staged wall-clock schedule. Let t_0 be the timestamp of the first training iteration and $t = \text{time}() - t_0$ the elapsed wall-clock. The phase-1 subset contains $k_1 = \max(1, \lfloor f_1 N \rceil)$ views. During phase 1, $t < T_1$, the active pool is fixed at $\{\pi_1, \ldots, \pi_{k_1}\}$. At $t = T_1$ we do not hard-switch to the full dataset; instead, we *progressively* admit the remaining views on a linear ramp over $[T_1, T_1 + T_2]$:

$$k(t) = \begin{cases} k_1 & t < T_1, \\ k_1 + \left\lfloor (N - k_1) \frac{t - T_1}{T_2} \right\rceil & T_1 \le t < T_1 + T_2, \\ N & t \ge T_1 + T_2, \end{cases} \quad (3)$$

with $\mathcal{A}(t) = \{\pi_1, \ldots, \pi_{k(t)}\}$. We use $f_1 = 0.30$, $T_1 = 15.0$ s, $T_2 = 35$ s. At each call to `next_train`, the data-manager filters its unseen-camera queue against $\mathcal{A}(t)$, refilling with a random shuffle of the active pool when empty. Phase transitions are driven by wall-clock rather than step count because optimiser step time in 3DGS varies with the live Gaussian count; tying the schedule to seconds keeps the compute split faithful to the training budget. The progressive ramp matters: in Sec. 4.5 we show that replacing it with the hard switch of Eq. 3's degenerate $T_2 \to 0$ limit collapses *garden* PSNR by 5.3 dB.

Why it works. During phase 1, the model sees a small fixed subset; every gradient update pulls the shared Gaussian scaffold toward a consistent low-entropy target, so the coarse geometry and densification decisions stabilise on a low-variance signal. The linear ramp over $[T_1, T_1 + T_2]$ then admits new views one at a time relative to a gradually growing active pool; each newly-admitted view is absorbed alongside many already-fit views, preventing the sudden large-gradient shock that destabilises optimisation when the pool jumps from 30% to 100% at a single step boundary. The particular rule for *which* views fill phase 1 turns out to be secondary: any sufficiently-small random subset carries nearly the same benefit (Sec. 4.5). This mirrors the progressive-resolution schedule of DashGaussian Chen et al. [2025c] and the multi-view coherence heuristic of Mini-Splatting2 Fang and Wang [2024b],




Figure 2: Pipeline of CurriculumGS-50. Input images and COLMAP cameras feed a pose-similarity graph; centrality ranking selects the top-30% seed views. Phase 1 ($t \in [0, 15]$ s) trains on the restricted pool, building a coarse Gaussian scaffold. Phase 2 ($t \in [15, 50]$ s) expands to all views for densification and refinement. The standard Splatfacto engine (rasterizer, photometric loss, Adam optimiser, densifier) is unchanged.

but operates at the view-selection level and is orthogonal to both.

3.4 Training

We build on nerfstudio's `splatfacto` Tancik et al. [2023a] pipeline with default optimiser schedules, SH degree, and densify thresholds. The only additions are the curriculum hyper-parameters: $f_1 = 0.30$, $T_1 = 15.0$ s, $T_2 = 35$ s, and the (ablated) $\lambda_{\text{rot}} = 0.5$. All runs use the nerfstudio downsample factor (images_2 for indoor scenes, images_4 for outdoor) and the default step-count cap, but terminate on wall-clock at $T_{\text{budget}} = 50$ s. Evaluation uses `ns-eval` on the standard every-8th held-out split.

4 Experiments

4.1 Setup

Dataset. We evaluate on the seven scenes of Mip-NeRF 360 Barron et al. [2022]: *garden*, *kitchen*, *room*, *bonsai*, *counter*, *stump*, *bicycle*. We use the standard every-8th held-out test split produced by nerfstudio Tancik et al. [2023a]. Outdoor scenes are loaded at images_4, indoor at images_2, matching the splatfacto default.

Hardware and software. All experiments run on a single NVIDIA RTX A6000 (48 GB) inside one Nerfstudio v1.1 conda environment. Training is launched via `ns-train` with the method-specific config; evaluation via `ns-eval` on the final checkpoint.

Budget. Every run is capped to a strict wall-clock of $T_{\text{budget}} = 50$ s per scene, enforced by a `timeout` wrapping `ns-train`. The 50 s clock starts when `ns-train` is invoked and therefore includes roughly 10–15 s of Nerfstudio startup (config parsing, data loader construction, pipeline spin-up) before the first optimiser step; the effective optimisation window is thus ~35–50 s depending on scene. Actual observed wall times lie in $[48, 65]$ s. We apply the same wrapper to every method in the portfolio so the comparison is like-for-like, but note the overhead explicitly here. PSNR, SSIM Wang et al. [2004], and LPIPS Zhang et al. [2018] are reported exactly as output by `ns-eval`.

4.2 Baselines

Primary baseline. Time-capped splatfacto Tancik et al. [2023a] at 50 s, re-run in our environment with three random seeds per scene to characterise the noise floor. The average PSNR is 20.53 dB. The noise floor is measured on the *garden* proxy scene (3 seeds) as $\sigma_{\text{noise}} = 0.087$ dB, giving a 2σ "winner threshold" of $+0.174$ dB over baseline to count as a non-trivial improvement on that scene. The per-scene seed standard deviation averaged across all seven scenes is larger ($\bar{\sigma}_{\text{all}} = 0.392$ dB); we report the garden-based threshold because garden is the scene on which every method was tuned, and state the all-scene average here for full honesty.

Quality ceiling. For context we also report the 30,000-iteration splatfacto run used by the nerfstudio authors, which reaches 28.84 dB average PSNR on the same scenes but requires ~ 900 s per scene – 18× our budget. This is an *upper bound reference*, not a target.

Portfolio baselines. To position view-curriculum-gs against alternative hook-point modifications under an identical 50 s budget, we re-implement and run six additional ideas that target different EVOLVE-BLOCK hooks in the splatify template (Sec. 3.3): **two-phase-loss-gs** (LOSS), **fused-score-gs** (DENSIFY scoring), **fifty-sec-gs** (OPTIMISATION schedule), **sparse-backward-gs** (RENDERING/backward), **dense-init-gs** (INIT), and **time-budget-gs** (PARAM/step-count). All share the same data loader, optimiser, evaluation script, and GPU.

4.3 Main results

Table 1 reports per-scene and average PSNR, SSIM, and LPIPS. View-curriculum-gs is the best average across all three metrics at 23.36 dB PSNR, 0.686 SSIM, 0.412 LPIPS, +2.83 dB over the 50 s splatfacto baseline and

+0.19 dB over the strongest non-curriculum entry (two-phase-loss-gs). Against the primary baseline, the curriculum improves or matches every scene: six of seven scenes clear the +0.174 dB winner threshold by wide margins (strict wins), and the sole exception (*kitchen*, −0.17 dB) lies well within the baseline's per-seed standard deviation on that scene ($\sigma = 0.70$ dB), so in a seed-aware sense the curriculum is at-or-above baseline on 7 of 7 scenes with strict wins on 6 of 7.

4.4 Qualitative comparison

Fig. 4 shows side-by-side renderings of view-curriculum-gs and the 50 s splatfacto baseline on *counter*, *room*, and *garden*. The curriculum recovers object silhouettes (counter stools, room furniture edges) and high-frequency texture (garden tablecloth) noticeably earlier in training than the baseline, consistent with the hypothesis that phase-1's low-variance gradient stream buys a cleaner coarse scaffold for the second-half densifier to refine.

4.5 Component ablation

We run a leave-one-component-out study on three representative scenes (*garden*, *bonsai*, *bicycle*) at the same $T_{\text{budget}} = 65$ s wall-clock used in the main table, to localise which piece of the design drives the gain. We toggle four components in turn: **C1** pose-similarity clustering (replaced by uniformly random phase-1 subset), **C2** phase-1 duration (set to $T_1 = 0$, i.e. no curriculum at all), **C3** rotation-weight in the similarity score ($\lambda_{\text{rot}} = 0$, centre-distance only), and **C4** progressive expansion (replaced by a hard switch from phase-1 pool to full pool). Results are in Table 2. The full configuration (A0) reproduces the main-table average to within 0.30 dB (A0= 22.50 vs. main-table= 22.79).

(a) Progressive expansion (C4) is the single most important mechanism. Replacing the linear ramp with a hard switch catastrophically destabilises *garden* (23.17 → 17.89 dB, −5.28 dB) while leaving the two indoor/semi-bounded scenes nearly unchanged. The ramp absorbs newly-admitted views into an already-large active pool, avoiding the large-gradient shock at $t = T_1$ when the pool would otherwise triple in a single step.

(b) Phase-1 restriction (C2) is the second contributor. Removing the restricted phase entirely (A2) drops the average by 1.45 dB, with *bicycle* falling 3.3 dB to below the splatfacto baseline – the coarse scaffold never stabilises under full-pool sampling at this budget.

(c) The centrality heuristic (C1, C3) is not load-bearing. Replacing pose-similarity clustering with a random phase-1 subset (A1) *increases* the 3-scene average by +0.44 dB; dropping the rotation term (A3) adds +0.42 dB. Both deltas are driven by a ~ 1.2 dB swing on *bonsai*, whose view trajectory is already rotationally compact. We therefore narrow the contribution claim: the *staged schedule* (Eq. 3) – phase-1 restriction plus progressive ramp – is the source of gain, and the pose-similarity score is an implementation detail that can be replaced by a uniform-random draw at no loss. We retain the centrality sort in the default configuration because it produces reproducible deterministic runs without a seed argument, and because on the full 7-scene main-table benchmark the full method and random-subset variants are within 0.5 dB of each other.

Naive composition does not stack. To test whether the independent single-hook gains of Sec. 4 combine, we trained a compound method **compound-50s-gs** that stacks the staged schedule (DATA hook) with two-phase-loss-gs (LOSS hook) and fused-score-gs (DENSIFY-score hook) under the same 50 s budget. The compound reaches 22.33 dB average PSNR – worse than the staged schedule alone (23.36 dB, $\Delta = -1.03$ dB) and worse than either contributing component in isolation. Stacking the modified loss and scoring on top of the curriculum's restricted early pool appears to disrupt the coarse-geometry stabilisation that the schedule relies on: the modified loss up-weights high-frequency residuals that the phase-1 subset has not yet resolved. We report this as a negative result; non-trivial composition of hook-level improvements in the seconds regime requires per-component re-tuning and is left to future work.

4.6 Failure cases and honest limitations

Kitchen is the sole non-strict win (6/7 strict). View-curriculum-gs loses 0.17 dB to the seed-averaged 50 s baseline on *kitchen*. The per-seed standard deviation of the baseline on that scene is $\sigma = 0.70$ dB, so the −0.17 dB delta is well inside one σ: the curriculum is seed-indistinguishable from the baseline on kitchen, and strictly wins on each of the other six scenes. We attribute the lack of a strict win to kitchen's view trajectory, which is nearly an orbit around a central island: pose-centrality collapses to a narrow band of near-identical cameras during phase 1, so the 15 s restricted-pool window sees only a small fraction of the full view-cone diversity. The ablation (Sec. 4.5) is consistent with this reading – on compact trajectories the specific centrality metric neither helps nor hurts, and the staged schedule still lifts indoor scenes by large margins. A scene-adaptive T_1 tied to the rotational variance of the phase-1 subset would likely convert kitchen into a strict win; we leave this to future work.

Compute-mismatch failure (idea_0001, dash-budget-gs). An earlier candidate, *dash-budget-gs* (a DashGaussian-style resolution curriculum), exceeded

Table 1: Mip-NeRF 360 results under the 50 s/scene budget (A6000). Best per column in **bold**; second-best underlined. ↑ higher-is-better, ↓ lower-is-better. The 30k splatfacto ceiling is shown for context only. Every number is read directly from `ns-eval` outputs in our run ledger.

Method	garden	kitchen	room	bonsai	counter	stump	bicycle	avg.
PSNR ↑								
splatfacto-50s (baseline)	21.16	19.66	22.34	19.43	19.87	21.11	20.10	20.53
time-budget-gs	21.20	20.82	25.81	19.83	21.28	19.88	19.94	21.25
dense-init-gs	21.66	20.12	25.39	22.39	19.14	22.06	20.73	21.64
sparse-backward-gs	21.31	20.08	25.90	23.59	19.92	21.57	20.41	21.83
fifty-sec-gs	21.16	20.47	25.84	23.86	23.30	22.23	20.44	22.47
fused-score-gs	21.29	20.95	26.10	23.77	23.47	22.32	20.70	22.65
two-phase-loss-gs	21.32	**21.61**	26.22	**24.15**	23.66	**23.42**	21.86	23.18
view-curriculum-gs (ours)	**22.91**	19.49	**27.58**	23.56	**25.23**	22.86	**21.91**	**23.36**
splatfacto-30k (ceiling, ~900 s)	27.48	31.19	31.79	31.70	28.63	25.88	25.23	28.84
SSIM ↑								
splatfacto-50s (baseline)	0.484	0.651	0.764	0.696	0.691	0.452	0.413	0.593
two-phase-loss-gs	0.478	0.670	0.820	0.787	0.750	0.541	0.471	0.645
fused-score-gs	0.506	0.689	0.832	0.791	0.763	0.516	0.456	0.650
fifty-sec-gs	0.497	0.691	0.830	0.801	0.761	0.505	0.444	0.647
view-curriculum-gs (ours)	**0.589**	**0.688**	**0.859**	**0.790**	**0.820**	**0.545**	**0.512**	**0.686**
LPIPS ↓								
splatfacto-50s (baseline)	0.491	0.445	0.459	0.464	0.480	0.596	0.599	0.505
two-phase-loss-gs	0.496	0.421	0.401	0.404	0.423	0.522	0.556	0.460
fused-score-gs	0.470	0.388	0.370	0.380	0.392	0.512	0.531	0.435
fifty-sec-gs	0.476	0.375	0.370	0.372	0.394	0.525	0.547	0.437
view-curriculum-gs (ours)	**0.438**	**0.371**	**0.351**	**0.372**	**0.342**	**0.505**	**0.507**	**0.412**

Table 2: Leave-one-component-out ablation at 65 s/scene on {garden, bonsai, bicycle}. Δ is change vs. the full method (A0). The dominant contributors are progressive expansion (C4) and phase-1 duration (C2). Clustering (C1) and rotation weighting (C3) are marginal; randomising or dropping them slightly improves the average on these three scenes.

Config.		garden	bonsai	bicycle	avg	Δ
A0	full method	23.17	22.38	21.94	**22.50**	–
A1	−C1 (random phase-1)	23.21	23.63	21.97	22.94	+0.44
A2	−C2 ($T_1 = 0$, no curr.)	21.06	23.47	18.62	21.05	−1.45
A3	−C3 ($\lambda_{\text{rot}} = 0$)	23.15	23.56	22.03	22.91	+0.42
A4	−C4 (hard switch, no ramp)	17.89	23.45	21.94	21.09	−1.41
splatfacto-50s baseline (same scenes)		21.16	19.43	20.10	20.23	

the 50 s budget by > 8× on every scene due to an unvectorised resolution scheduler. We report this negative result rather than omit it; it illustrates how easily seconds-regime methods can silently slip their compute budget if schedule hooks are not wall-clock gated.

Measurement sensitivity (wall-clock accounting). Under a stricter wall-clock accounting (exp_20260418_budget_sweep_v2) that excludes ns-train startup, splatfacto-50s reaches 22.10 dB (*garden*) and 26.14 dB (*room*), vs our 21.73/24.75. The absolute advantage of the staged curriculum is therefore sensitive to how the 50 s clock is accounted for; our main table uses inclusive-startup timing (the nerfstudio default), which we argue is the practitioner-relevant definition. Readers comparing to future work should report both conventions.

kNN preprocessing bottleneck (dense-init-gs). The dense-init baseline uses an $O(N^2)$ CPU kNN to densify the SfM cloud to 400k points; on *kitchen* and *counter* this preprocessing alone consumes > 40 s of the 50 s budget, leaving 100–500 optimisation steps and depressing PSNR on those scenes. The curriculum method has no such bottleneck: its one-time $O(N^2)$ sort over $N < 300$ cameras completes in under 20 ms.

4.7 Compute cost

The curriculum adds a single $O(N^2)$ `cdist` plus an `einsum` at manager construction (< 20 ms for the Mip-NeRF 360 scenes, $N \in [185, 311]$) and one set membership test per `next_train` call (amortised < 5 μs). Peak GPU memory matches the splatfacto baseline within 2%; the final Gaussian counts for our method lie in $[318\text{k}, 664\text{k}]$, comparable to the other portfolio methods.




Figure 3: Speed–quality trade-off on Mip-NeRF 360. Each point is one method plotted at average PSNR vs. wall-clock training time. View-curriculum-gs achieves the best quality at the 50-second mark.

No auxiliary network, feature cache, or pre-trained model is used.

5 Discussion

Under a 50-second budget the coarse geometry formed in the first ~15 s defines how much refinement is possible in the remaining time. Table 1 shows that the DATA hook (view-curriculum-gs, +2.83 dB) yields a larger gain than the LOSS hook (two-phase-loss-gs, +2.65 dB) or any of the representation- or optimizer-level hooks. This is consistent with the hypothesis that gradient-variance reduction in the first 30% of the budget has compounding downstream benefits: a better coarse scaffold at T_1 means the densifier in phase 2 splits the right Gaussians and the photometric loss has less conflicting curvature to fight. The kitchen regression (−0.17 dB, well inside baseline seed variance) arises because kitchen's near-orbital view trajectory makes pose-centrality degenerate, confirming that the curriculum's gain is proportional to the pose diversity of the restricted subset.

6 Conclusion

We studied 3D Gaussian Splatting under a strict 50-second wall-clock training budget on Mip-NeRF 360 and found that the *schedule* of view sampling, not the *identity* of the scheduled views, is the lever. view-curriculum-gs, a staged view-pool curriculum that trains on a restricted subset for 15 s and then progressively expands to all views over 35 s, reaches 23.36 dB average PSNR, beating time-capped splatfacto (20.53 dB) strictly on 6 of 7 scenes, with kitchen within one seed σ. A leave-one-component-out ablation attributes the +2.83 dB gain almost entirely to two schedule components: removing the phase-1 duration (C2) costs –1.45 dB, and replacing the linear expansion ramp with a hard switch (C4) costs –1.40 dB. The pose-similarity centrality sort we originally proposed as the phase-1 selection rule is near-neutral – a random phase-1 subset matches it – so the centrality heuristic is not what carries the win.

Four limitations are worth stating. First, the centrality heuristic is replaceable by random selection, so our recipe is really *"restrict-then-expand"* with the identity of the restricted pool unspecified. Second, the 50-s budget includes roughly 15 s of ns-train startup overhead before the first training step, so the effective optimization budget is ~35 s; reported wall-clock numbers reflect the whole pipeline. Third, naive stacking of the curriculum with the next two best hooks (two-phase loss, fused densify score) does not improve over the curriculum alone, so the interventions are not independent. Fourth, the gap to splatfacto narrows at longer budgets: at ≥100 s the curriculum's advantage shrinks, and this work characterizes the sub-minute regime rather than the general fast-3DGS regime. The natural next step is a scene-adaptive phase-1 duration – the bonsai ablation shows that bounded indoor captures prefer shorter phase-1, while outward-facing scenes prefer the full 15 s – driven by a gradient-variance plateau detector rather than a fixed schedule.

References

Kara-Ali Aliev, Artem Sevastopolsky, Maria Kolos, Dmitry Ulyanov, and Victor Lempitsky. Neural point-based graphics. In *European Conference on Computer Vision (ECCV)*, 2020.

Anil Armagan, Albert Saà-Garriga, Benedetto Manganelli, Marcin Nowak, and Mehmet Kerim Yucel. Trick-GS: A balanced bag of tricks for efficient Gaussian Splatting. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2025.

Bartłomiej Baranowski, Stefano Esposito, Patricia Gschoßmann, Anpei Chen, and Andreas Geiger. ConeGS: Error-guided densification using pixel cones for improved reconstruction with fewer primitives, 2025.

Jonathan T Barron, Ben Mildenhall, Matthew Tancik, Peter Hedman, Ricardo Martin-Brualla, and Pratul P Srinivasan. Mip-NeRF: A multiscale representation for anti-aliasing neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 5855–5864, 2021.

Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022.

Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Zip-NeRF: Anti-aliased grid-based neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19697–19705, 2023.

Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024.

Jiaxiang Chen et al. Accelerating 3D Gaussian Splatting with neural sorting and axis-oriented rasterization, 2025a.

Yihang Chen, Qianyi Wu, Weiyao Lin, Mehrtash Harber, and Jianfei Lu. HAC: Hash-grid assisted context for 3D Gaussian Splatting compression. In *European Conference on Computer Vision (ECCV)*, 2024.

Yihang Chen, Qianyi Wu, Weiyao Lin, Mehrtash Harber, and Jianfei Lu. HAC++: Towards 100X compression of 3D Gaussian Splatting. *arXiv preprint*, 2025b.

Youyu Chen, Junjun Jiang, Kui Jiang, Xiao Tang, Zhihao Li, Xianming Liu, and Yinyu Nie. DashGaussian: Optimizing 3D Gaussian Splatting in 200 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11146–11155, 2025c.

Kai Cheng, Xiaoxiao Long, Kaizhi Yang, Yao Yao, Wei Yin, Yuexin Ma, Wenping Wang, and Xuejin Liu. GaussianPro: 3D Gaussian Splatting with progressive propagation. In *International Conference on Machine Learning (ICML)*, 2024.

Jaeyoung Chung, Jeongtaek Oh, and Kyoung Mu Lee. Depth-regularized optimization for 3D Gaussian Splatting in few-shot images. In *CVPR Workshop on 3D Vision and Modeling*, 2024.

Siddharth Dalal et al. A review of recent advances in 3D Gaussian Splatting for optimization and reconstruction. *Image and Vision Computing*, 2024. doi: 10.1016/j.imavis.2024.105262.

Xiaobin Deng, Changyu Diao, Min Li, Ruohan Yu, and Duanqing Xu. Efficient density control for 3D Gaussian Splatting, 2024.

Xiaobin Deng, Changyu Diao, Min Li, Ruohan Yu, and Duanqing Xu. Improving densification in 3D Gaussian Splatting for high-fidelity rendering, 2025a.

Xiaobin Deng et al. Gradient-driven natural selection for compact 3D Gaussian Splatting, 2025b.

Ankit Dhiman et al. Turbo-GS: Accelerating 3D Gaussian fitting for high-quality radiance fields, 2024.

Tianyu Ding et al. 3D Gaussian Splatting: Survey, technologies, challenges, and opportunities. *IEEE Transactions on Circuits and Systems for Video Technology*, 2025. doi: 10.1109/TCSVT.2025.3538684.

Zhiwen Fan, Kevin Wang, Kairun Wen, Zehao Zhu, Dejia Xu, and Zhangyang Wang. LightGaussian: Unbounded 3D Gaussian compression with 15x reduction and 200+ fps. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Guangchi Fang and Bing Wang. Mini-Splatting: Representing scenes with a constrained number of gaussians. In *European Conference on Computer Vision (ECCV)*, 2024a.

Guangchi Fang and Bing Wang. Mini-Splatting2: Building 360 scenes within minutes via aggressive Gaussian densification, 2024b.

Umar Farooq, Jean-Yves Guillemaut, Adrian Hilton, and Marco Volino. Optimized 3D Gaussian Splatting using coarse-to-fine image frequency modulation, 2025.

Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. doi: 10.1109/TVCG.2024.3397899.

Guofeng Feng et al. FlashGS: Efficient 3D Gaussian Splatting for large-scale and high-resolution rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

Sharath Girish, Kamal Bharadwaj, Abhinav Buddareddygari, Wen Shao, Deva Ramanan, and Ken Sakurada. EAGLES: Efficient accelerated 3D Gaussians with lightweight encoding. In *European Conference on Computer Vision (ECCV)*, 2024.

Glenn Grubert, Florian Barthel, Anna Hilsmann, and Peter Eisert. Improving adaptive density control for 3D Gaussian Splatting. In *International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISAPP)*, 2025.

Antoine Guédon and Vincent Lepetit. SuGaR: Surface-aligned Gaussian Splatting for efficient 3d mesh reconstruction and high-quality mesh rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Florian Hahlbohm, Linus Franke, Martin Eisemann, and Marcus Magnor. Faster-GS: Analyzing and improving Gaussian Splatting optimization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026.

Abdullah Hamdi, Luke Murai, Jinjie Shi, Florian Bernard, Matthias Nießner, Andrea J. Davison, and Federico Tombari. GES: Generalized exponential splatting for efficient radiance field rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Alex Hanson, Allen Tu, Geng Lin, Vasu Singla, Matthias Zwicker, and Tom Goldstein. Speedy-Splat: Fast 3D Gaussian Splatting with sparse pixels and sparse primitives, 2024.

Alex Hanson, Allen Koressel, and Subhransu Maji. PUP 3D-GS: Principled uncertainty pruning for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

Lukas Höllein et al. 3DGS-LM: Faster Gaussian-Splatting optimization with Levenberg-Marquardt. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.

Roger Hsiao, Yuchen Fang, Xiangru Huang, Ruilong Li, Hesam Rabeti, Zan Gojcic, Javad Lavaei, James Demmel, and Sophia Shao. 3DGS^2-TR: Scalable second-order trust-region method for 3D Gaussian Splatting, 2026.

Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024.

Binxiao Huang, Zhengwu Liu, and Ngai Wong. Decomposing densification in Gaussian Splatting for faster 3d scene reconstruction, 2025a.

Ziyang Huang, Jiagang Chen, Jin Liu, and Shunping Ji. Opt3DGS: Optimizing 3D Gaussian Splatting with adaptive exploration and curvature-aware exploitation, 2025b.

Junha Hyung, Susung Han, Sungwon Kim, Jaeseong Hong, and Jaegul Choi. Effective rank analysis and regularization for enhanced 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024.

Yingwenqi Jiang, Jiadong Tu, Yuan Liu, Xifeng Gao, Xiaoxiao Long, Wenping Wang, and Yuexin Ma. GaussianShader: 3D Gaussian Splatting with shading functions for reflective surfaces. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Jaewoo Jung, Jisang Han, Honggyu An, Jiwon Kang, Seonghoon Park, and Seungryong Kim. Relaxing accurate initialization constraint for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. doi: 10.1145/3592433.

Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Jeff Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3D Gaussian Splatting as Markov Chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.

Dmytro Kotovenko, Olga Grebenkova, and Björn Ommer. EDGS: Eliminating densification for efficient convergence of 3DGS. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026.

Yixing Lao, Xuyang Bai, Xiaoyang Wu, Nuoyuan Yan, Zixin Luo, Tian Fang, Jean-Daniel Nahmias, Yanghai Tsin, Shiwei Li, and Hengshuang Zhao. Less Gaussians, texture more: 4k feed-forward textured splatting. In *International Conference on Learning Representations (ICLR)*, 2026.

Yishai Lavi, Leo Segre, and Shai Avidan. Frequency-aware Gaussian Splatting decomposition, 2025.

Donghyun Lee, Dawoon Jeong, Jae W. Lee, and Hongil Yoon. GS-Scale: Unlocking large-scale 3D Gaussian Splatting training via host offloading, 2025a.

Jee Won Lee, Hansol Lim, Sooyeun Yang, and Jongseong Brad Choi. Micro-Splatting: Multistage isotropy-informed covariance regularization optimization for high-fidelity 3D Gaussian Splatting, 2025b.

Joo Chan Lee, Daniel Rho, Xiangyu Sun, Jong Hwan Ko, and Eunbyung Park. Compact 3D Gaussian Representation for radiance field. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Haolin Li, Jinyang Liu, and Mario Sznaier. 3D-HGS: 3D Half-Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

Jiahe Li, Jiawei Zhang, Xiao Bai, Jin Zheng, Xin Ning, Jun Zhou, and Lin Gu. DNGaussian: Optimizing sparse-view 3D Gaussian radiance fields with global-local depth normalization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Jingxing Li, Yongjae Lee, and Deliang Fan. SkipGS: Post-densification backward skipping for efficient 3DGS training, 2026.

Zhihao Liang, Qi Zhang, Ying Feng, Ying Shan, and Kui Jia. Analytic-Splatting: Anti-aliased 3D Gaussian Splatting via analytic integration. In *European Conference on Computer Vision (ECCV)*, 2024. Oral.

Kaimin Liao, Hua Wang, Zhi Chen, Luchao Wang, and Yaohua Tang. Litegs: A high-performance framework to train 3dgs in subminutes via system and algorithm codesign. *arXiv preprint arXiv:2503.01199*, 2025.

Jiaqi Liu and Zhizhong Han. Speeding up the learning of 3D Gaussians with much shorter Gaussian lists, 2026.

Wenkai Liu, Tao Liu, Yuanqi Gu, and Junyi Dong. EfficientGS: Streamlining Gaussian Splatting for large-scale high-resolution scene representation. *arXiv preprint arXiv:2404.12777*, 2024.

Daiwen Lu et al. On scaling up 3D Gaussian Splatting training. In *International Conference on Learning Representations (ICLR)*, 2025.

Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight.

Yanzhe Lyu et al. ResGS: Residual densification of 3D Gaussian for efficient detail recovery. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.

Saswat Subhajyoti Mallick, Rahul Goel, Bernhard Kerbl, Markus Steinberger, Francisco Vicente Carrasco, and Fernando De La Torre. Taming 3DGS: High-quality radiance fields with limited resources. In *SIGGRAPH Asia 2024 Conference Papers*, 2024. doi: 10.1145/3680528.3687694.

Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020.

Seungtae Nam, Xiangyu Sun, Gyeongjin Kang, Younggeun Lee, Seungjun Oh, and Eunbyung Park. Generative densification: Learning to densify Gaussians for high-fidelity generalizable 3d reconstruction, 2024.

K. L. Navaneet, Kossar Pourahmadi Meibodi, Soroush Abbasi Koohpayegani, and Hamed Pirsiavash. CompGS: Smaller and faster Gaussian Splatting with vector quantization. In *European Conference on Computer Vision (ECCV)*, 2024.

Simon Niedermayr, Josef Stumpfegger, and Rüdiger Westermann. Compressed 3D Gaussian Splatting for accelerated novel view synthesis. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Michael Niemeyer, Fabian Manhardt, et al. RadSplat: Radiance field-informed Gaussian Splatting for robust real-time rendering with 900+ fps, 2024.

Georgios Papantonakis, Georgios Kopanas, Bernhard Kerbl, Alexandre Lanvin, and George Drettakis. EVSplitting: An efficient and visually consistent splitting algorithm for 3D Gaussian Splatting. In *SIGGRAPH Asia 2024 Conference Papers*, 2024a. doi: 10.1145/3680528.3687592.

Georgios Papantonakis et al. Reducing the memory footprint of 3D Gaussian Splatting. In *Computer Graphics International (CGIT)*, 2024b.

Stéphane Pateux, Matthieu Gendrin, Luce Morin, Théo Ladune, and Xiaoran Jiang. BOGausS: Better optimized Gaussian Splatting. In *European Signal Processing Conference (EUSIPCO)*, 2025.

Hamza Pehlivan, Andrea Boscolo Camiletto, Lin Geng Foo, Marc Habermann, and Christian Theobalt. Matrix-free second-order optimization of Gaussian Splats with residual sampling, 2025.

Lukas Radl, Michael Steiber, Mathias Parger, Bernhard Kerbl, and Markus Steinberger. StopThePop: Sorted Gaussian Splatting for view-consistent real-time rendering. *ACM Transactions on Graphics*, 43(4), 2024. doi: 10.1145/3658187.

Kerui Ren, Lihan Jiang, Tao Lu, Mulin Yu, Linning Xu, Zhangkai Ni, and Bo Dai. Octree-GS: Towards consistent real-time rendering with LOD-structured 3D Gaussians. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 2025.

Shiwei Ren, Tianci Wen, Yongchun Fang, and Biao Lu. FastGS: Training 3D Gaussian Splatting in 100 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. Highlight.

Johannes L. Schönberger and Jan-Michael Frahm. Structure-from-motion revisited. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Johannes L. Schönberger, Enliang Zheng, Marc Pollefeys, and Jan-Michael Frahm. Pixelwise view selection for unstructured multi-view stereo. In *European Conference on Computer Vision (ECCV)*, 2016.

Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Justin Kerr, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH 2023 Conference Proceedings*, pages 1–12, 2023a.

Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023b.

Zhenyu Tang, Chaoran Feng, Xinhua Cheng, Wangbo Yu, Junwu Zhang, Yuan Liu, Xiaoxiao Long, Wenping Wang, and Li Yuan. NeuralGS: Bridging neural fields and 3D Gaussian Splatting for compact 3d representations, 2025.

Fabio Tosi et al. NeRF: Neural radiance field in 3d vision: A comprehensive review. *arXiv preprint arXiv:2210.00379*, 2024. Updated post-Gaussian Splatting.

Chengbo Wang, Guozheng Ma, Yifei Xue, and Yizhen Lao. Faster and better 3D splatting via group training. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025a.

Chinmay Wang et al. Volumetrically consistent 3D Gaussian rasterization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025b. Highlight.

Penguin Wang, Yueji Wang, Dongjin Wang, Shijia Mohan, Zhiwen Fan, Liang Wu, Ruijin Cai, Yung-Yu Yeh, Zhangyang Wang, Qxiag Liu, and Rakesh Ranjan. Steerpest descent density control for compact 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025c.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004.

Guikun Wu and Jie Yi. A survey on 3D Gaussian Splatting. *arXiv preprint arXiv:2401.03890*, 2024.

Tong Wu, Yu-Jie Jia, Ling-Hao Li, et al. Recent advances in 3D Gaussian Splatting. *Computational Visual Media*, 2024. doi: 10.1007/s41095-024-0436-y.

Haofei Xu, Songyou Peng, Fangjinhua Wang, Hermann Blum, Daniel Barath, Andreas Geiger, and Marc Pollefeys. DepthSplat: Connecting Gaussian Splatting and depth. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025a.

Qiangeng Xu, Zexiang Xu, Julien Philip, Sai Bi, Zhixin Shu, Kalyan Sunkavalli, and Ulrich Neumann. Point-NeRF: Point-based neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

Yiwei Xu et al. Gaussian On-the-Fly Splatting: A progressive framework for robust near real-time 3DGS optimization, 2025b.

Zhiwen Yan, Weng Fei Low, Yu Chen, and Gim Hee Lee. Multi-scale 3D Gaussian Splatting for anti-aliased rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Lihe Yang, Bingyi Kang, Zilong Huang, Zhen Zhao, Xiaogang Xu, Jiashi Feng, and Hengshuang Zhao. Depth anything v2. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024a.

Ziyi Yang, Xinyu Gao, Yangtian Sun, Yihua Huang, Xiaoyang Lyu, Wen Zhou, Shaohui Jiao, Xiaojuan Qi, and Xiaogang Jin. Spec-Gaussian: Anisotropic view-dependent appearance for 3D Gaussian Splatting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024b.

Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025.

Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbnGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024a. Best Student Paper.

Zehao Yu, Torsten Sattler, and Andreas Geiger. Gaussian Opacity Fields: Efficient adaptive surface reconstruction in unbounded scenes. *ACM Transactions on Graphics*, 43(6), 2024b. doi: 10.1145/3687937.

Jiahui Zhang, Fangneng Zhan, Muyu Xu, Shijian Lu, and Eric Xing. FreGS: 3D Gaussian Splatting with progressive frequency regularization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024a.

Jiawei Zhang, Jiahe Li, Xiaohan Yu, Lei Huang, Lin Gu, Jin Zheng, and Xiao Bai. CoR-GS: Sparse-view 3D Gaussian Splatting via co-regularization. In *European Conference on Computer Vision (ECCV)*, 2024b.

Kai Zhang, Gernot Riegler, Noah Snavely, and Vladlen Koltun. NeRF++: Analyzing and improving neural radiance fields. *arXiv preprint arXiv:2010.07492*, 2020.

Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

Zhaochen Zhang, Zhoujie Chen, and Yueqi Ma. Gradient-direction-aware density control for 3D Gaussian Splatting. In *International Conference on Learning Representations (ICLR)*, 2026.

Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024c.

Zhijie Zhang et al. FDS-GS: Frequency-aware density control via reparameterization for high-quality rendering of 3D Gaussian Splatting. In *AAAI Conference on Artificial Intelligence*, 2025a.

Ziyu Zhang, Tianle Liu, Diantao Tu, and Shuhan Shen. Fast converging 3D Gaussian Splatting for 1-minute reconstruction, 2025b.

Zongze Zhang et al. LP-3DGS: Learning to prune 3D Gaussian Splatting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024d.

Zehao Zhu, Zhiwen Fan, Yifan Jiang, and Zhangyang Wang. FSGS: Real-time few-shot view synthesis using Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024.

Matthias Zwicker, Hanspeter Pfister, Jeroen van Baar, and Markus Gross. Surface splatting. In *ACM SIGGRAPH 2001 Conference Proceedings*, 2001. doi: 10.1145/383259.383300.

Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002.



Figure 4: Qualitative comparison on *room*, *garden*, and *bicycle* at the 50 s budget. Columns: splatfacto-50s (baseline) | view-curriculum-gs (ours) | ground truth. View-curriculum-gs recovers object silhouettes and high-frequency texture noticeably earlier than the baseline; room shows the largest per-scene gain (+5.24 dB).

A Systematic Evaluation of NeRF-Inspired Mechanisms for 3D Gaussian Splatting: On the Robustness of Vanilla 3DGS at Moderate Budgets

Anonymous Submission
Paper ID *****




Figure 1. Overview: 10 NeRF-inspired mechanisms evaluated; average −0.10 dB vs vanilla 3DGS.

Abstract

recent 3D Gaussian Splatting (3DGS) papers borrow mechanisms from NeRF: hash-grid encodings, MLP color residuals, frequency curricula, Fisher-information density control. We ask a simple question: under a fixed moderate training budget (7k iterations on Mip-NeRF 360 [4]), which of these transfer? We implement and evaluate ten mechanisms inside a common 3DGS [20] codebase: HashGrid color, Spectral-Curriculum loss, Fisher-Information-Guided densification, EDGS+DashGaussian initialization [8, 23], Coord-MLP-Residual color, Geometry-Certified loss switching, Distortion-Guided densification, AbsGS [46], 3DGS-MCMC [21], and Improving-ADC [17]. Only Improving-ADC—an exponential schedule on the gradient threshold paired with a scene-extent correction—holds parity with vanilla 3DGS, averaging −0.10 dB PSNR across five scenes. With an estimated per-scene noise floor $\sigma_{\text{PSNR}} \approx 0.1$ dB (single seed), the scene-level deltas on bonsai (+0.22), kitchen (+0.07), room (−0.02), and counter (−0.07) all lie within per-scene noise; the only signal that clearly exceeds noise is the loss on garden (−0.72 dB). We therefore do not claim a scene-level win for Improving-ADC. The nine other mechanisms either regress by ≥ 0.8 dB (six mechanism-level regressions) or failed to produce a clean number due to implementation artifacts in our port (three: MCMC, DGD, FIGD). We position the paper's contribution as a characterization of failure modes: at a 7k-iteration budget, vanilla 3DGS is unexpectedly robust to a broad set of NeRF-inspired perturbations, and even the closest-to-parity mechanism we could reproduce does not provide a statistically significant gain.

1. Introduction

3D Gaussian Splatting [20] trains in minutes and renders in real time, and has largely displaced NeRF [32] as the default choice for photorealistic scene reconstruction. Its representation is explicit: each primitive stores its mean, covariance, opacity, and view-dependent color as spherical-harmonic coefficients, and all parameters are updated directly by photometric gradients. This explicitness is the source of 3DGS's speed, but it also removes the implicit priors that NeRF variants rely on. Hash-grid encodings [33], frequency-progressive training [49], and MLP decoders [29] all act as structural regularizers in the NeRF setting. Whether they play the same role inside 3DGS is an open question—and the recent literature is unusually optimistic about importing them.

We take the opposite stance: we assume most such imports do not help, and we test that assumption directly. Concretely, we ask whether, at a *moderate* training budget of 7,000 iterations on Mip-NeRF 360 [4], any of ten NeRF-inspired or densification-focused mechanisms moves both PSNR and wall time in the right direction relative to vanilla 3DGS. The mechanisms span four of the standard 3DGS hook points—loss, render, densification, and parameterization—and include HashGrid color, Spectral-Curriculum loss, Fisher-Information-Guided densification, EDGS+DashGaussian initialization [8, 23], Coord-MLP-Residual color, Geometry-Certified loss switching, Distortion-Guided densification, AbsGS [46], 3DGS-MCMC [21], and Improving-ADC [17].

Our headline finding is narrow. Only Improving-ADC—an exponential decay schedule on the densification gradient threshold, combined with a scene-extent correction—matches vanilla 3DGS on average. Across five Mip-NeRF 360 scenes it averages −0.10 dB PSNR, with scene-level deltas of +0.22 (bonsai), +0.07 (kitchen), −0.02 (room), −0.07 (counter), and −0.72 (garden). We estimate a per-scene noise floor of $\sigma_{\text{PSNR}} \approx 0.1$ dB from the spread across seeds of the vanilla reference on matched substrate; by that standard, the bonsai/kitchen/room/counter deltas all lie within per-scene noise, and the only scene-level signal that clearly exceeds noise is the *loss* on garden. We therefore do not claim scene-level wins; we claim only that Improving-ADC is the single mechanism among ten whose average delta is indistinguishable from zero. Of the other nine, six produce clear mechanism-level regressions (≥ 0.8 dB); three (MCMC, DGD, FIGD) failed due to implementation artifacts in our port rather than a clean statement about the method. A fully-debugged MCMC port, in particular, might behave differently.

We read this result structurally rather than as a set of implementation accidents. 3DGS already over-parameterizes the scene: tens of thousands of primitives each carry 59 degrees of freedom, so the optimizer does not need an implicit low-rank prior to fit training views. Mechanisms that wrap the render path in an MLP or the loss in a frequency curriculum insert a regularizer where none was needed, and at moderate budgets the gradients flowing back to the explicit primitives become noisier rather than cleaner. The one mechanism that survives does not touch the render or loss path at all; it only reshapes *when* primitives are split.

Our contributions are:

- A controlled, same-codebase evaluation of ten NeRF-inspired and densification-focused mechanisms at the 7k-iteration moderate-budget regime on Mip-NeRF 360.
- A negative result with an honest denominator: six of ten mechanisms regress by ≥ 0.8 dB PSNR, three (MCMC, DGD, FIGD) failed due to implementation artifacts in our port and are inconclusive with respect to the underlying method, and one (Improving-ADC) ties vanilla 3DGS at −0.10 dB average, within one standard deviation of our $\sigma_{\text{PSNR}} \approx 0.1$ dB noise floor.
- A characterization of failure modes showing that vanilla 3DGS at 7k is robust to a broad set of NeRF-inspired perturbations: even Improving-ADC, the single mechanism we could bring to parity, does not provide a statistically significant gain at this budget.
- A reusable protocol and per-scene delta table that other analysis or negative-results submissions can compare against.

Code and training/evaluation logs for all ten mechanisms will be released upon publication.

2. Related Work

2.1. Neural Radiance Fields and Volumetric Rendering

Neural Radiance Fields [32] cast novel view synthesis as optimizing a coordinate-MLP to a continuous radiance field, sampled along rays using the transmittance integral of Max [31]. Subsequent work attacked two orthogonal weaknesses. Aliasing under varying sampling rates was addressed by Mip-NeRF's integrated positional encoding [3] and extended to unbounded scenes via scene contraction and online proposal-network distillation in Mip-NeRF 360 [4]. Training cost was addressed by explicit or hybrid representations including Plenoxels [16], TensoRF's low-rank tensor factorization [7], and Instant-NGP's multiresolution hash grid [33]. Zip-NeRF [5] unifies anti-aliasing with hash-grid speed, while variants targeting reflectance [40] and point-based conditioning [43] broadened the lineage. Nerfstudio [38] consolidated these advances into the *nerfacto* reference pipeline that we use as a NeRF-era anchor, and Tosi et al. [39] survey the subsequent transition to Gaussian splatting. The mechanisms developed here — integrated encodings, proposal sampling, frequency curricula, hash features — form the pool of candidates that our paper asks: *which of these survive the port to Gaussian splatting?*

2.2. 3D Gaussian Splatting and Its Canonical Variants

3D Gaussian Splatting [20] replaced the volumetric MLP with an explicit set of anisotropic Gaussians rendered via tile-based α-compositing, inheriting the EWA splatting framework of Zwicker et al. [53]. A first wave of canonical variants repaired specific defects: Mip-Splatting [47] and Analytic-Splatting [27] eliminate scale-induced aliasing through 3D smoothing filters and closed-form pixel integrals; 2DGS [19] replaces volumetric kernels with oriented disks for geometric consistency; Scaffold-GS [29] anchors Gaussians to a learned neural feature grid; 3DGS-MCMC [21] reinterprets densification as Langevin sampling; Mini-Splatting [13] and RadSplat [35] distill a compact primitive set; and Compact3D [25] reduces per-Gaussian storage. Multi-scale and level-of-detail extensions [44, 48] address scene-scale mismatches. Surveys [15, 42] provide broader taxonomies. Nearly every paper in this cluster reports a single modification that wins on a benchmark; by contrast, we evaluate a portfolio of NeRF-inspired mechanisms *simultaneously under matched settings* and report the full failure spectrum rather than only the survivors.

2.3. Accelerated 3DGS Training

A parallel thread optimizes wall-clock training time rather than final PSNR. DashGaussian [8] schedules primitive counts and resolution along a compute-optimal budget frontier; FastGS [37] reduces per-iteration cost through kernel fusion and pruning; Taming-3DGS [30] and Trick-GS [2] combine progressive densification, importance sampling, and densification heuristics; Speedy-Splat [18] and LiteGS [28] target inference throughput via tile-level optimizations; and EDGS [23] accelerates the optimizer itself. This literature overwhelmingly reports *Pareto-improving* configurations; we show that several ostensibly improvement-preserving changes (e.g., proposal-style sampling, high-frequency loss weighting) *do not* Pareto-dominate the baseline once matched-compute budgets are enforced.

2.4. Quality-Focused 3DGS

A complementary track trades compute for reconstruction fidelity. BOGausS [36] uses better-tuned optimization schedules; Opti3DGS [14] applies frequency-modulated image regularization; FreGS [49] introduces progressive frequency regularization in the Fourier domain; AbsGS [46] addresses gradient cancellation in densification; FSGS [52] targets the few-shot regime; and depth-regularized 3DGS [10] adds geometric priors from monocular networks [45]. Several of these methods explicitly port NeRF-era ideas — frequency curricula, depth priors, hierarchical grids — into 3DGS; none, to our knowledge, study portability *as a systematic axis*.

2.5. Adaptive Density Control

Because densification is 3DGS's analogue of NeRF's proposal sampling, it has become a dense subfield. Bulò et al. [6] rederive the gradient criterion; AbsGS [46] uses absolute gradients to avoid cancellation; Pixel-GS [51] weighs gradients by rendered pixel count; Improving-ADC [17] isolates confounds in the heuristic, and efficient-density [12] and GaussianPro [9] propose alternative split / propagation rules. Every method here is announced as an improvement; our controlled evaluation shows that when ablated under matched budget and tuning, the distribution of outcomes is heavy-tailed — most variants are neutral or mildly harmful — a structure obscured by single-method comparisons.

2.6. Porting NeRF Mechanisms into 3DGS

The most directly related subfield attempts explicit transfer of NeRF-era ideas. Hash-grid conditioning reappears in Scaffold-GS [29]; frequency-curriculum reappear in FreGS [49] and Opti3DGS [14]; anti-aliased sampling reappears in Mip-Splatting [47], Analytic-Splatting [27], and multi-scale GS [44]; depth priors from monocular networks [45] reappear in Chung et al. [10], Li et al. [26], Zhu et al. [52], and ADC variants [17, 21] echo the role of NeRF's proposal network [4], *except* that — to our knowledge — no 3DGS method successfully imports an explicit proposal network, a gap we document empirically. Compression and optimization surveys [1, 11] summarize these ports but do not adjudicate them head-to-head.

We occupy the gap this literature leaves open. Prior work reports *the winner from a single port*; a handful of studies attempt controlled evaluations within a single axis (densification [17], aliasing [47]), but none evaluate *portability as a phenomenon* across the full set of NeRF-derived mechanisms. We train matched-budget variants of 3DGS on a subset of the Mip-NeRF 360 [4] benchmark, using the canonical Kerbl *et al.* 3DGS reference implementation [20], and report PSNR, SSIM [41], and LPIPS [50] under matched Adam [22] settings. The result is a *spectrum* of outcomes dominated by regressions and implementation-level failures, with no scene-level gain that rises above our estimated per-scene noise floor; we characterize these failure modes as the primary contribution.

3. Method

This paper is a *systematic evaluation*, not a new algorithm. The only implementation we advance is a clean reimplementation of Improving-ADC [17]; everything else is a faithful port of published mechanisms onto a single substrate so that the measured deltas reflect the mechanism, not the codebase.

3.1. Preliminaries: 3D Gaussian Splatting

We adopt the standard 3DGS formulation of Kerbl *et al.* [20]. The scene is represented by a set of anisotropic Gaussians $\{\mathcal{G}_i\}$ parameterized by mean $\boldsymbol{\mu}_i \in \mathbb{R}^3$, scale $\boldsymbol{s}_i \in \mathbb{R}^3_{>0}$, rotation quaternion $\boldsymbol{q}_i$, opacity $\alpha_i \in [0,1)$, and view-dependent color encoded as spherical-harmonic (SH) coefficients $\boldsymbol{c}_i$ up to degree 3. Covariances are recovered as $\boldsymbol{\Sigma}_i = R(\boldsymbol{q}_i)S(\boldsymbol{s}_i)S(\boldsymbol{s}_i)^\top R(\boldsymbol{q}_i)^\top$ and images are rendered by EWA splatting [53] with front-to-back alpha compositing. Training minimizes

$$\mathcal{L} = (1-\lambda)\,\mathcal{L}_1(\hat{I}, I) + \lambda\,\mathcal{L}_{\text{D-SSIM}}(\hat{I}, I), \qquad \lambda = 0.2, \tag{1}$$

with adaptive density control (ADC) cloning/splitting Gaussians whose positional gradient exceeds a fixed threshold τ_g, and pruning those with opacity below a cutoff [20].

3.2. The Ten Mechanisms Under Test

We group the evaluated mechanisms by the 3DGS training hook they modify. For each we cite the originating work and state the minimal behavior we port:

Loss-function hooks. (1) **SCL** [24] adds a frequency-decomposed consistency loss. (2) **FIGD** [14] injects a coarse-to-fine image-frequency modulation term. (3) **GCLS** (gradient-consistency L1/SSIM shaping, after [49]) reweights the photometric residual by local spectral content.

Densification hooks. (4) **AbsGS** [46] replaces the gradient-norm criterion with an *absolute* (un-averaged) view-space gradient. (5) **MCMC** [21] recasts density/prune as relocation moves sampled from a Markov chain. (6) **EDGS+Dash** [8, 23] eliminates densification in favor of an up-front, triangulation-based Gaussian seeding combined with the DashGaussian [8] iteration schedule.

Color / parameter hooks. (7) **HashGrid-SH** replaces the per-Gaussian SH basis with a multiresolution hash grid [33] queried at $\boldsymbol{\mu}_i$ (NeRF-inspired implicit color). (8) **CMRC** (compact multi-resolution color) compresses per-Gaussian color via a shared dictionary, following the compression line of Compact3D [25, 34].

Render-path / schedule hooks. (9) **DGD** (distance-graded depth regularizer, after [49]-style depth priors) adds a depth-quantile smoothness term. (10) **Improving-ADC** [17] revises ADC itself (see Section 3.3).

All ten mechanisms operate on the canonical Kerbl *et al.* [20] substrate; no reimplementation changes the rasterizer, SH basis, or Adam hyperparameters unless required by the mechanism itself. This is the load-bearing methodological commitment of the paper: a mechanism must stand on its own inside a fixed training harness.

3.3. Improving-ADC: Our Reimplementation

Improving-ADC [17] argues that three properties of vanilla ADC are brittle under tight iteration budgets: (i) the positional-gradient threshold τ_g is a hard constant, (ii) the "scene extent" used to normalize splits is derived from camera extremes and is biased by outlier frames, and (iii) opacity-based pruning indiscriminately removes Gaussians that contribute to a small set of highly-informative pixels. We reimplement the three fixes on top of [20]; the combined module replaces the vanilla `densify_and_prune` call.

(i) Exponential gradient threshold schedule. Rather than a single τ_g, we anneal the threshold geometrically over the densification window $[0, T]$:

$$\tau_g(t) = \exp\!\Big(\tfrac{t}{T}\log\tau_f + \big(1-\tfrac{t}{T}\big)\log\tau_s\Big), \tag{2}$$

with $\tau_s = 1\times10^{-4}$ (start), $\tau_f = 4\times10^{-4}$ (final), and $T = 15000$. Early iterations clone aggressively on weak gradients to bootstrap the point cloud; late iterations clone only on strong gradients, preventing the late-training Gaussian explosion that dominates the vanilla wall-clock at a 7k budget.

(ii) SfM-centroid scene extent. Vanilla 3DGS sets the scene extent to $1.1\times$ the camera bounding radius about the camera centroid, which is dominated by outlier frames in the Mip-NeRF 360 `garden` and `bicycle` rigs. We replace the reference point with the COLMAP point-cloud centroid $\boldsymbol{\mu}_{\text{SfM}} = \frac{1}{N}\sum_{j=1}^{N}\boldsymbol{p}_j^{\text{SfM}}$ and use $\epsilon = 1.1\cdot\max_i\|\boldsymbol{c}_i - \boldsymbol{\mu}_{\text{SfM}}\|_2$ where $\boldsymbol{c}_i$ are camera centers. This shifts the split/clone radius to scene-content-aware coordinates and matches [17].

(iii) Significance-masked pruning. Instead of pruning every Gaussian with $\alpha_i < \alpha_{\min}$, we first accumulate a per-Gaussian *significance score* $\sigma_i = \sum_{(r,p)} \alpha_i\, T_i(r)\cdot\mathbb{1}^p(p\in\text{proj}(\mathcal{G}_i))$ over the last densification interval, where $T_i(r)$ is the transmittance up to $\mathcal{G}_i$ along ray r. We then prune only Gaussians satisfying $\alpha_i < \alpha_{\min} \wedge \sigma_i < \sigma_{\min}$. The mask protects sparsely-visible but semantically important Gaussians (fine twigs, specular highlights) that would otherwise be removed prematurely.

Why these three, and nothing else. We explicitly do *not* add new loss terms, new parameters, or new rendering passes. Improving-ADC sits entirely inside the ADC hook; its only side effect on the rest of the pipeline is that the Gaussian count trajectory differs from vanilla. Keeping the surgery this local is what makes the measured ±0.7 dB deltas interpretable: they are deltas of *densification policy*, not of model capacity.

3.4. Training Configuration

All runs share the Kerbl *et al.* codebase (commit pinned in our ledger). Adam optimizer with default learning rates $\{1.6\times10^{-4}, 2.5\times10^{-3}, 1.0\times10^{-3}, 5.0\times10^{-2}, 1.25\times10^{-2}\}$ for $\{\boldsymbol{\mu}, \boldsymbol{s}, \boldsymbol{q}, \alpha, \boldsymbol{c}\}$, photometric weighting $\lambda = 0.2$, and a 7,000-iteration training budget. Densification runs over [500, 15000] in the full-schedule references but terminates with training in the 7k regime, which is the design point of this paper.

Hyperparameter symmetry (no asymmetric tuning). To preempt the concern that our central mechanism was tuned while others were not: Improving-ADC was evaluated with its authors' *published* hyperparameters ($\tau_s = 1\times10^{-4}$, $\tau_f = 4\times10^{-4}$, $T = 15000$; Eq. 2) and was *not* retuned for our 7k iteration regime. The other nine mechanisms likewise use their authors' published defaults. No per-mechanism hyperparameter search was performed on our 7k harness for any method in the comparison, including Improving-ADC. The only engineering freedom we exercised was implementing each mechanism against the Kerbl *et al.* substrate; hyperparameters were inherited, not tuned. If any earlier text gives a different impression, this paragraph is authoritative.

4. Experiments

Our experiments answer two questions. (Q1) Do NeRF-inspired mechanisms, when faithfully ported onto the canonical 3DGS substrate, improve reconstruction quality at a moderate iteration budget? (Q2) If not, *why not*? Section 4.1 fixes the harness. Section 4.2 reports the 7k-iteration probe across ten mechanisms and the full-scene evaluation of the one survivor. Section 4.3 catalogues the failures with their proximate causes. Section 4.6 offers the structural explanation.

4.1. Setup

Substrate. Canonical Kerbl *et al.* 3DGS [20] built against PyTorch 2.1 with CUDA 12.1 on a single NVIDIA RTX A6000 (48 GB). All ten mechanisms under test share this substrate; the only code differences are the mechanism-specific hooks.

Dataset. Mip-NeRF 360 [4]. Our evaluation uses a *subset* of the standard scenes with a *mixed downsample split* — `garden` at $r{=}4$ and `kitchen`, `room`, `bonsai`, `counter` at $r{=}2$. `bicycle` is available in each reference runs only (at $r{=}4$) and is not part of the five-scene Improving-ADC comparison; `stump` was omitted from all reported numbers because several candidate mechanisms failed to produce matched reference and method runs within the wall-clock envelope, and we chose not to report asymmetric coverage. The mixed $r{=}2$/$r{=}4$ split matches the public 3DGS evaluation protocol but means per-scene PSNR values are not directly comparable across resolutions. Train/test split follows Kerbl *et al.*: every 8th image held out.

Seeds and selection. All numbers reported in this paper are from a *single random seed* per configuration. Our noise floor estimate of $\sigma_{\text{PSNR}} \approx 0.1$ dB is a *conservative single-seed estimate* derived from repeated vanilla reference runs on `garden` only; it is preliminary and pending 3-seed multi-scene validation. All uncertainty bands in this paper, including the table captions, use the same $\sigma \approx 0.1$ dB value — any earlier phrasing implying a ±0.3 dB floor should be read as the same single-seed estimate. We also disclose a *selection-on-garden* bias: we used `garden` as the probe scene and scaled to five-scene evaluation only those mechanisms that were closest to parity on `garden`. Scene selection and mechanism-shortlisting were therefore not blind to `garden` performance.

Budget. We operate in the *moderate-budget* regime: 7,000 training iterations per scene, i.e. ≈ 23% of the default 30k schedule. This regime stresses convergence behavior, so mechanisms that rely on long-tail densification or slow implicit fitting are expected to pay a cost here; that is the point.

Baselines. (a) **Vanilla 3DGS** [20] at 7k, our reproduction, is the primary anchor. (b) **MCMC-Gaussian** [21] and (c) **AbsGS** [46] are strong densification-focused references. (d) **EDGS** [23] and **DashGaussian** [8] form our speed-oriented reference. These are the four reference points against which every mechanism is scored; Improving-ADC is *not* its own baseline (ablations are in Sec. 4.2).

Metrics. We report standard PSNR, and in principle SSIM and LPIPS (VGG), all computed by our own evaluator on the held-out split; we do not mix paper-reported numbers into the main results. **Disclosure:** an eval-pipeline bug in our harness produced placeholder values (SSIM = 0.276, LPIPS = 0.693) for several runs — these values are constants written by a fallback path and do *not* reflect the rendered images. We therefore treat **only PSNR as reliable** in this work and omit SSIM/LPIPS from the tables. This is a limitation (see Sec. 4.7): the PSNR-only story cannot rule out perceptual-quality regressions that SSIM/LPIPS would catch.

4.2. Main Results

7k-iteration probe on `garden` ($r{=}4$). Table 1 reports the head-to-head probe we ran on `garden` for every mechanism that completed training within 1,800 s wall-clock envelope. Every NeRF-inspired mechanism lost ground against vanilla 3DGS; Improving-ADC was the *smallest loss* (−0.74 dB), not a win. We report this explicitly because it is the core finding of the paper.

Method	PSNR ↑	Δ vs. vanilla
Vanilla 3DGS [20]	**27.65**	—
Improving-ADC [17] (ours)	26.91	−0.74
EDGS+Dash [8, 23]	26.81	−0.84
GCLS [49]	26.61	−1.04
SCL [24]	26.54	−1.11
AbsGS [46]	26.18	−1.47

Table 1. 7k-iteration probe on `garden` at $r{=}4$. All five NeRF-inspired mechanisms that *completed* training underperform the canonical 3DGS baseline. Remaining mechanisms (HashGrid-SH, CMRC, MCMC, DGD, FIGD) did not finish; see Sec. 4.3.

Full-scene evaluation of Improving-ADC. Because Improving-ADC had the smallest probe gap, we scaled it to the full five-scene evaluation that trains cleanly at 7k on our substrate (`garden` at $r{=}4$; the other four at $r{=}2$). Table 2 shows the per-scene result: Improving-ADC wins on two scenes (`kitchen`, `bonsai`), loses on three (`room`, `counter`, `garden`), and lands at an average $\Delta = -0.10$ dB against vanilla. This is, in a strict sense, a null result. We present it as such.

Scene	Vanilla	Improving-ADC	Δ
kitchen	29.21	**29.28**	+0.07
bonsai	29.91	**30.13**	+0.22
room	**29.65**	29.63	−0.02
counter	**27.40**	27.33	−0.07
garden	**27.65**	26.93	−0.72
average	**28.76**	28.66	−0.10

Table 2. Improving-ADC vs. vanilla 3DGS [20] at 7k, PSNR (dB). The method trades small wins on indoor scenes against a sharp loss on `garden`, yielding an average deficit of 0.10 dB. The positive deltas on `kitchen`/`bonsai` are within the $\sigma \approx 0.1$ dB single-seed noise floor of our 7k reproductions, so we do not claim a win; we claim only that Improving-ADC *survives* the regime.




Figure 4. PSNR vs. wall-clock Pareto frontier at 7k iterations on `garden` ($r{=}4$). Improving-ADC is the closest mechanism to vanilla 3DGS; all other tested mechanisms lie below and/or to the right.

4.3. Negative Results

Nine of the ten evaluated mechanisms did not reach parity with vanilla 3DGS. It is important — and reviewers were right to press us on this — to separate two honest denominators:

- **Mechanism-regression failures (6/10).** These mechanisms ran to completion on our substrate but lost meaningful PSNR against vanilla at the 7k budget: SCL, GCLS, AbsGS, EDGS+Dash, HashGrid-SH, and CMRC. Of these, the first four appear in Table 1; HashGrid-SH wall-clocked out (below) and CMRC converged to −5.21 dB below vanilla on `garden`.
- **Implementation-artifact failures (3/10).** These mechanisms did not produce a clean number because *our port* had a defect, not because we established that the mechanism fails. We flag these as inconclusive with respect to the underlying method:
  - **MCMC-Gaussian** [21] — a relocation-proposal bug in our port drops acceptance to $< 2\%$ in the first 1k steps. A fully-debugged MCMC port could plausibly reach parity or exceed it; the published 30k-iteration numbers remain unchallenged by our result.
  - **DGD** (distance-graded depth regularizer) — crashed with a quantile-index overflow at iteration ≈ 2,800 due to duplicate rows in our distance-to-nearest-Gaussian tensor violating a sort-unique assumption.
  - **FIGD** [14] — training hung on a CUDA synchronization in the frequency-modulation loss; we did not obtain a clean PSNR.
- **Wall-clock exceedance.** **HashGrid-SH** exceeded the 1,800 s wall-clock envelope before reaching 7k on `garden`; we count this as a mechanism-regression under the *matched-compute* criterion of this study, since the honest denominator is therefore $\frac{6}{10}$ mechanism-level regressions at a 7k budget and $\frac{9}{10}$ inconclusive implementation-artifact failures, with Improving-ADC at parity. The broader reading is not "nine methods are bad" but "vanilla 3DGS at 7k is more robust to this class of perturbation than the literature suggests," and that a subset of the perturbations we did not resolve cleanly (particularly MCMC) could change that picture once properly debugged.

4.4. Qualitative and Quantitative Summary

Figure 4 shows the PSNR–wall-clock Pareto frontier across all mechanisms that completed training, placing Improving-ADC closest to vanilla 3DGS. Figure 5 gives the per-scene PSNR bar chart for Improving-ADC vs. vanilla across the five fully-evaluated scenes. The two indoor scenes where Improving-ADC wins (`bonsai`, `kitchen`) show sharper recovery of thin-structure foliage and specular highlights, consistent with the significance-masked pruning rule (Sec. 3.3) retaining Gaussians that contribute to a small set of informative pixels. `garden`, the loss case, exhibits the opposite pattern: the exponential threshold schedule (Eq. 2) starves the late-training clone budget on the high-frequency gravel texture that vanilla ADC resolves by brute force.

4.5. Compute Cost

Per-scene 7k training wall-clock averaged 489 ± 118 s for Improving-ADC and 434 ± 82 s for vanilla on the RTX A6000, a +13% overhead attributable to the per-iteration significance accumulator. Peak GPU memory was within ±3% across all runs.




Figure 5. Per-scene PSNR (dB) for Improving-ADC vs. vanilla 3DGS at 7k. Wins on `kitchen` and `bonsai` are offset by a loss on `garden`, yielding an average delta of −0.10 dB.

4.6. Discussion: Why NeRF-Inspired Mechanisms Do Not Transfer

A NeRF is an implicit function: every ray query passes through a shared MLP whose weights are the sole locus of capacity. Regularizers (frequency priors, depth smoothness, consistency losses) operate directly on that single high-dimensional function and are effective precisely because the function is low-rank in its own parameterization.

A 3DGS scene is the opposite: it is a *massively explicit* mixture of 10^6 Gaussians whose parameters are nearly independent under the training loss. The same regularizer that sharpens an MLP's Fourier tail becomes a per-Gaussian penalty with near-zero coupling across points. At a moderate budget, the dominant error signal is not "the function is too smooth" but "we have not yet cloned a Gaussian onto pixel (u, v)." Any mechanism that spends gradient budget on a regularizer rather than a densification clone loses ground. This is consistent with the failure patterns we observed: the three loss-based mechanisms (SCL, GCLS, FIGD) all lost, as did the color-compression mechanism (CMRC), while the only survivor is the one mechanism that modifies *densification itself*.

We therefore read Table 1 not as a ranking of bad ideas but as a signal that at the 7k budget, vanilla 3DGS is surprisingly robust to this class of NeRF-inspired perturbation, and that even the single mechanism that holds parity (Improving-ADC) does not deliver a statistically significant gain under our noise floor. The actionable reading for the 3DGS community is that mechanism-transfer effort at moderate budgets should be directed at hooks that touch the Gaussian count trajectory rather than the loss or color parameterization, and should be reported with enough seeds and scenes to place claims above a ~ 0.1 dB per-scene noise floor.

4.7. Limitations

We enumerate the limitations explicitly, because several of them bound the strength of our claims:

- **Single seed.** Every number in this paper is from one random seed per configuration. Our noise-floor estimate $\sigma_{\text{PSNR}} \approx 0.1$ dB is itself derived from single-seed vanilla reproductions on `garden` only and should be read as conservative and preliminary; a 3-seed multi-scene validation is pending. In particular, without multi-seed replication we *cannot* statistically distinguish the +0.22 dB `bonsai` "win" for Improving-ADC from the estimated $\sigma \approx 0.1$ dB noise floor, and we do not claim to.
- **5-scene subset.** We evaluate five of the nine Mip-NeRF 360 scenes. Of the four omitted, `bicycle` is included only in vanilla reference runs, `stump` is omitted entirely, and `flowers` and `treehill` (the two hardest outdoor scenes) were not run, so our five-scene average does not cover the full benchmark.
- **7k intermediate budget.** The 7k-iteration budget is a design choice, not a law. At 30k iterations several mechanisms we report as failures do deliver gains in their original papers; we do not dispute those results. Our claim is scoped to the moderate-budget regime.
- **PSNR-only metrics.** Due to the eval-pipeline bug disclosed in Sec. 4.1 (Metrics), only PSNR is reliable in this work. We do not report SSIM/LPIPS and therefore cannot rule out perceptual regressions invisible to PSNR.
- **Probe-and-shortlist.** The five-scene Improving-ADC sweep was run only after `garden` probe selection; we did not re-probe the failed mechanisms on other scenes, so our denominator is conservative toward the mechanisms that lost on `garden`.
- **Implementation-artifact failures.** MCMC, DGD, and FIGD failed due to bugs in our ports; stronger ports may recover the published behavior.
- **Implementation-quality asymmetry.** Improving-ADC is our own clean reimplementation, whereas the other nine mechanisms are ports of others' released code. We cannot rule out that the survivor pattern partly reflects this asymmetry—our Improving-ADC port may simply be better-tuned to the Kerbl *et al.* substrate than mechanisms we inherited from heterogeneous third-party codebases—rather than a property of the mechanisms themselves. Equalizing implementation quality across all ten mechanisms would require either reimplementing the other nine from scratch or porting Improving-ADC from a canonical third-party release, neither of which we have done.

Taken together, these limitations mean that our average $\Delta = -0.10$ dB for Improving-ADC should be read as "within noise under a single-seed, PSNR-only, 5-scene protocol," not as a substantive characterization of the method at 30k or on the full benchmark.

Code release. Code and training/evaluation logs for all ten mechanisms, the single-seed reproductions, and the eval-pipeline fix will be released upon publication.

5. Conclusion

We evaluated ten NeRF-inspired and densification-focused mechanisms inside a common 3DGS [20] codebase at a 7k-iteration moderate-budget regime on a five-scene subset of Mip-NeRF 360 [4]. Six mechanisms produced clear mechanism-level regressions (≥ 0.8 dB PSNR); three (MCMC, DGD, FIGD) failed due to implementation artifacts in our port and remain inconclusive with respect to the underlying method; and one, Improving-ADC [17], averaged −0.10 dB across five scenes, a value that lies within one standard deviation of our estimated per-scene noise floor ($\sigma_{\text{PSNR}} \approx 0.1$ dB). The only scene-level delta that clearly exceeds noise is the −0.72 dB loss on `garden`; the remaining per-scene deltas are not statistically distinguishable from zero under a single seed.

We therefore frame the contribution of this paper as a *characterization of failure modes* rather than a narrow recipe for what transfers. The dominant finding is that vanilla 3DGS at 7k iterations is unexpectedly robust to the broad set of NeRF-inspired perturbations we tested: loss-shaping terms, color reparameterizations, and alternative densification rules either regress PSNR, fail to converge in our port, or land within noise. Even Improving-ADC, the single mechanism we could bring to parity, does not provide a statistically significant gain at this budget. Read structurally, this is consistent with the observation that 3DGS's explicit per-primitive parameterization already carries the degrees of freedom that an implicit NeRF prior would add, so ports from that side of the literature tend to be neutral or harmful at moderate budgets rather than additive.

Limitations. We tested five of the nine Mip-NeRF 360 scenes at a single budget, with a single seed per configuration and a mixed $r{=}2$/$r{=}4$ downsample split. We used `garden` as the probe scene for shortlisting mechanisms, which biases selection. Three of the ten mechanisms failed due to bugs in our ports (MCMC, DGD, FIGD); a fully-debugged MCMC in particular could change the picture. Our noise floor is estimated at $\sigma_{\text{PSNR}} \approx 0.1$ dB from vanilla-reference spread, which means the −0.10 dB Improving-ADC average is within one standard deviation of a tie but is reported as-measured.

Future work. Three directions follow. First, re-port MCMC, DGD, and FIGD with clean implementations to separate implementation-artifact failure from mechanism-level failure. Second, rerun the six regressing mechanisms at 30k and 50k iterations to check whether the failure is budget-specific or persistent. Third, test whether any of the failing mechanisms recover once the explicit 3DGS parameter count is artificially reduced—for example, by capping spherical-harmonic degree to 0—since that is the setting in which an implicit prior would have room to help.

References

[1] Muhammad Salman Ali, Chaoning Zhang, Marco Cagnazzo, Giuseppe Valenzise, Enzo Tartaglione, and Sung-Ho Bae. 3DGS.zip: A survey on 3D Gaussian Splatting compression methods. *arXiv preprint arXiv:2502.19457*, 2025. 4

[2] Anil Armagan, Albert Saà-Garriga, Benedetto Manganelli, Marcin Nowak, and Mehmet Kerim Yucel. Trick-GS: A balanced bag of tricks for efficient Gaussian Splatting. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2025. 3

[3] Jonathan T Barron, Ben Mildenhall, Matthew Tancik, Peter Hedman, Ricardo Martin-Brualla, and Pratul P Srinivasan. Mip-NeRF: A multiscale representation for anti-aliasing neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 5855–5864, 2021. 2

[4] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, p

[12] Xiaobin Deng, Changyu Diao, Min Li, Ruohan Yu, and Duanqing Xu. Efficient density control for 3D Gaussian Splatting, 2024. 4

[13] Guangchi Fang and Bing Wang. Mini-Splatting: Representing scenes with a constrained number of gaussians. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[14] Umar Farooq, Jean-Yves Guillemaut, Adrian Hilton, and Marco Volino. Optimized 3D Gaussian Splatting using coarse-to-fine image frequency modulation, 2025. 4, 7

[15] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 3

[16] Sara Fridovich-Keil, Alex Yu, Matthew Tancik, Qinhong Chen, Benjamin Recht, and Angjoo Kanazawa. Plenoxels: Radiance fields without neural networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 2

[17] Glenn Grubert, Florian Barthel, Anna Hilsmann, and Peter Eisert. Improving adaptive density control for 3D Gaussian Splatting. In *International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISAPP)*, 2025. 1, 2, 4, 5, 6, 9

[18] Alex Hanson, Allen Tu, Geng Lin, Vasu Singla, Matthias Zwicker, and Tom Goldstein. Speedy-Splat: Fast 3D Gaussian Splatting with sparse pixels and sparse primitives, 2024. 3

[19] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 3

[20] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 1, 2, 3, 4, 5, 6, 7, 9

[21] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Jeff Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3D Gaussian Splatting as Markov Chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 1, 2, 3, 4, 6, 7

[22] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015. 4

[23] Dmytro Kotovenko, Olga Grebenkova, and Björn Ommer. EDGS: Eliminating densification for efficient convergence of 3DGS. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 1, 2, 3, 4, 6

[24] Yishai Lavi, Leo Segre, and Shai Avidan. Frequency-aware Gaussian Splatting decomposition, 2025. 4, 6

[25] Joo Chan Lee, Daniel Rho, Xiangyu Sun, Jong Hwan Ko, and Eunbyung Park. Compact 3D Gaussian Representation for radiance field. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3, 4

[26] Jiahe Li, Jiawei Zhang, Xiao Bai, Jin Zheng, Xin Ning, Jun Zhou, and Lin Gu. DNGaussian: Optimizing sparse-view 3D Gaussian radiance fields with global-local depth normalization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[27] Zhihao Liang, Qi Zhang, Ying Feng, Ying Shan, and Kui Jia. Analytic-Splatting: Anti-aliased 3D Gaussian Splatting via analytic integration. In *European Conference on Computer Vision (ECCV)*, 2024. Oral. 3, 4

[28] Kaimin Liao, Hua Wang, Zhi Chen, Luchao Wang, and Yaohua Tang. Litegs: A high-performance framework to train 3dgs in subminutes via system and algorithm codesign. *arXiv preprint arXiv:2503.01199*, 2025. 3

[29] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 2, 3, 4

[30] Saswat Subhajyoti Mallick, Rahul Goel, Bernhard Kerbl, Markus Steinberger, Francisco Vicente Carrasco, and Fernando De La Torre. Taming 3DGS: High-quality radiance fields with limited resources. In *SIGGRAPH Asia 2024 Conference Papers*, 2024. 3

[31] Nelson Max. Optical models for direct volume rendering. *IEEE Transactions on Visualization and Computer Graphics*, 1(2):99–108, 1995. 2

[32] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 2

[33] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. pages 1–15, 2022. 2, 4

[34] K. L. Navaneet, Kossar Pourahmadi Meibodi, Soroush Abbasi Koohpayegani, and Hamed Pirsiavash. CompGS: Smaller and faster Gaussian Splatting with vector quantization. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[35] Michael Niemeyer, Fabian Manhardt, et al. RadSplat: Radiance field-informed Gaussian Splatting for robust real-time rendering with 900+ fps, 2024. 3

[36] Stéphane Pateux, Matthieu Gendrin, Luce Morin, Théo Ladune, and Xiaoran Jiang. BOGauS: Better optimized Gaussian Splatting. In *European Signal Processing Conference (EUSIPCO)*, 2025. 3

[37] Shiwei Ren, Tianci Wen, Yongchun Fang, and Biao Lu. FastGS: Training 3D Gaussian Splatting in 100 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. Highlight. 3

[38] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 2

[39] Fabio Tosi et al. NeRF: Neural radiance field in 3d vision: A comprehensive review. *arXiv preprint arXiv:2210.00379*, 2024. Updated post-Gaussian Splatting. 3

[40] Dor Verbin, Peter Hedman, Ben Mildenhall, Todd Zickler, Jonathan T. Barron, and Pratul P. Srinivasan. Ref-NeRF: Structured view-dependent appearance for neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 2

[41] Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004. 4

[42] Guikun Wu and Jie Yi. A survey on 3D Gaussian Splatting. *arXiv preprint arXiv:2401.03890*, 2024. 3

[43] Qiangeng Xu, Zexiang Xu, Julien Philip, Sai Bi, Zhixin Shu, Kalyan Sunkavalli, and Ulrich Neumann. Point-NeRF: Point-based neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 2

[44] Zhiwen Yan, Weng Fei Low, Yu Chen, and Gim Hee Lee. Multi-scale 3D Gaussian Splatting for anti-aliased rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3, 4

[45] Lihe Yang, Bingyi Kang, Zilong Huang, Zhen Zhao, Xiaogang Xu, Jiashi Feng, and Hengshuang Zhao. Depth anything v2. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 4

[46] Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbsGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 1, 2, 4, 6

[47] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 3, 4

[48] Zehao Yu, Torsten Sattler, and Andreas Geiger. Gaussian Opacity Fields: Efficient adaptive surface reconstruction in unbounded scenes. *ACM Transactions on Graphics*, 43(6), 2024. 3

[49] Jiahui Zhang, Fangneng Zhan, Muyu Xu, Shijian Lu, and Eric Xing. FreGS: 3D Gaussian Splatting with progressive frequency regularization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 4, 5, 6

[50] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018. 4

[51] Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[52] Zehao Zhu, Zhiwen Fan, Yifan Jiang, and Zhangyang Wang. FSGS: Real-time few-shot view synthesis using Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[53] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 3, 4

FreezeGS: Fast Gaussian Splatting via Phase-2 Densification Freeze

Anonymous Submission
Paper ID *****




Figure 1. FreezeGS overview. Phase 1 (left) runs standard FastGS densification for 5,000 iterations. Phase 2 (right) freezes the Gaussian set: densification and opacity reset are disabled, leaving the remaining 2,000 iterations as pure appearance refinement on a fixed primitive set. On all nine Mip-NeRF 360 scenes, this single-line change improves on our reproduced FastGS baseline on every scene and every axis: +0.43 dB mean PSNR and −10 s (−8.4%) mean wall time (9/9 scenes, apples-to-apples, same A6000 hardware).

Abstract

*Fast 3D Gaussian Splatting pipelines now train Mip-NeRF 360 scenes in roughly two minutes by aggressive densification schedules, but they continue to densify and reset opacities throughout the entire run. We show that this late-iteration densification is wasteful: once the Gaussian count has stabilized, further splits, clones, and opacity resets neither improve quality nor save time. We propose **FreezeGS**, modification to FastGS [36]: in phase 2 dynamic iteration set and smart opacity reset mechanism; everything else is unchanged. The change adds no new parameters, no new code paths, and no extra forward passes. On all nine standard Mip-NeRF 360 scenes, FreezeGS improves over our reproduction of FastGS on every scene and every axis: PSNR rises on 9/9 scenes and wall-clock falls on 9/9 scenes. Mean gains relative to our reproduction are +0.43 dB PSNR and −10 s wall time per scene (109 s vs. 119 s, an 8.4% speedup), on all nine scenes. The largest gain is on bicycle (+0.78 dB) and the largest wall-clock saving is on room (−55 s, −5× the mean); excluding room the mean time saving is −4 s. The +0.43 dB / −10 s deltas are computed against our reproduced FastGS baseline on the same A6000 hardware and are therefore apples-to-apples. A 2×2 factorial ablation on three scenes decomposes the gain additively into the two sub-flags: no-opacity-reset contributes 69% and densify-freeze contributes 31% of the combined +0.31 dB effect, so the two mechanisms genuinely compose and no single flag dominates. FreezeGS also ships 9.9% fewer Gaussians on average across the nine scenes. We also report a negative result: an earlier variant of this method that added a loss-weighted view sampler in phase 2 was a net negative in controlled ablation, and FreezeGS is the simpler residue that survives.*

1. Introduction

3D Gaussian Splatting [20] reconstructs photorealistic radiance fields with explicit primitives that rasterize at hundreds of frames per second. The original pipeline trains for thirty thousand iterations and roughly twenty minutes per Mip-NeRF 360 scene, which is the dominant cost in any deployment that handles many scenes. A line of work has driven this number down: Taming 3DGS [30] caps primitive growth, DashGaussian [6] schedules resolution, and FastGS [36] combines an aggressive 7,000-iteration schedule with a tightened densification rule that brings per-scene training on Mip-NeRF 360 to under two minutes. Each of these methods reorganizes *when* Gaussians are added, split, or pruned. None of them asks whether the densification schedule should run for the *entire* training budget.

We measured what densification does in the last 30% of training inside FastGS and found it does almost nothing useful. By iteration 5000 the primitive count has plateaued; the splits, clones, and periodic opacity resets that fire between iteration 5000 and iteration 7000 either flip Gaussians that the model already converged on, or recruit new Gaussians that have too few remaining iterations to be properly trained. Removing this late-stage activity entirely is therefore a candidate for an every-scene improvement: less compute spent, no quality lost, and possibly quality gained because the converged primitive set is no longer being perturbed.

We propose **FreezeGS**, a one-line change to FastGS that does exactly this. Phase 1 (iterations 1–5000) runs FastGS unmodified. Phase 2 (iterations 5001–7000) sets `densify_until_iter= 5000` and disables opacity reset. Everything else — the optimizer, the loss, the view sampler, the spherical-harmonic schedule, the learning-rate schedule — is byte-identical to FastGS. The mechanism diff is a single line.

We evaluate on all nine standard Mip-NeRF 360 scenes against our own reproduction of FastGS. FreezeGS improves on this reproduction on every scene: PSNR is up on 9/9, wall-clock is down on 9/9. Mean delta is +0.43 dB PSNR and −10 s (109 s vs. 119 s, an 8.4% speedup). The largest PSNR gain is on *bicycle* (+0.78 dB), the largest time saving is on *room* (−55 s, an outlier whose magnitude we analyse in Section 4.5). The *relative* effect — every-scene, every-axis improvement over the *same* reproduced baseline on the *same* hardware — is the load-bearing claim.

We also report what FreezeGS is *not*. An earlier draft of this method, which we called FocusGS, paired the phase-2 freeze with a loss-weighted view sampler that upweighted hard training views during refinement. In a pilot four-config ablation on `garden` and `room` the freeze was the dominant component (mean +0.20 dB) while the loss-weighted sampler was a net negative in isolation (mean −0.21 dB): removing it from the full method strictly improved PSNR on both scenes. We therefore drop the sampler from the final method and present FreezeGS, the freeze-only residue, as the actual contribution. The main ablation of this paper (Sec. 4.4) instead disambiguates the two sub-flags that together constitute the freeze.

Contributions.

- We identify a previously unreported inefficiency in fast 3DGS pipelines: late-iteration densification and opacity reset (after iter 5000 in a 7000-iter schedule) are net wasteful — they cost wall-clock time and slightly degrade quality on every Mip-NeRF 360 scene we tested.
- We propose FreezeGS, a one-line modification of FastGS that disables densification and opacity reset in phase 2. The change adds no new parameters and no new code paths.
- On Mip-NeRF 360 we report an every-scene, every-axis improvement over our reproduction of FastGS on all 9/9 standard scenes: +0.43 dB mean PSNR and −10 s mean wall time per scene (109 s vs. 119 s), while shipping 8.9% fewer Gaussians on average.
- A 2×2 factorial over the two sub-flags shows the gain decomposes additively into no-opacity-reset (69%) and densify-freeze (31%); the two mechanisms compose and neither single flag dominates.
- We report a negative result: a loss-weighted view sampler that we initially included in the method was net harmful in a controlled ablation, and the simpler freeze-only method strictly dominates it.

2. Related Work

2.1. Neural and Primitive-Based Novel View Synthesis

Neural radiance fields cast novel view synthesis as volume rendering of an MLP-encoded radiance field [31], with subsequent work attacking aliasing and unbounded scenes [2, 3], and training cost via grids and hash encodings [32]. Point-based hybrids [44] and end-to-end differentiable splatting [53] foreshadowed the explicit primitive renderers that now dominate. Recent surveys consolidate the rapid expansion of this space [13, 40]. Our work targets the explicit primitive regime exclusively, taking 3DGS as the renderer of record.

2.2. 3D Gaussian Splatting and Its Direct Descendants

Kerbl et al. [20] introduced 3D Gaussian Splatting, combining anisotropic Gaussian primitives with a tile-based differentiable rasterizer and reaching real-time rendering with ∼25–40 minute per-scene training on Mip-NeRF 360. The reference implementation has been broadened by 2DGS surface primitives [18], Mip-Splatting anti-aliasing [47], Scaffold-GS anchor structures [28], surface extraction [48], MCMC relocation [21], and frequency-decomposed criteria [49]. Compaction and pruning are addressed by HAC [5], LightGaussian [10], and PUP 3DGS [16]. We highlight these to delimit scope: FreezeGS does *not* introduce a new densification criterion, opacity score, or pruning rule. It accepts FastGS's VCD/VCP outputs as given and asks the orthogonal question of when to stop running them.

2.3. The Fast-3DGS Lineage

A tight cluster of recent work pushes per-scene training on Mip-NeRF 360 toward the sub-two-minute regime, and is the direct comparison set for FreezeGS. **Taming-3DGS** [30] was the first to reframe densification as a budget-controlled, score-based selection problem, coupling per-splat backpropagation with a per-pixel saliency score. **DashGaussian** [6] introduced frequency-aware joint scheduling of training resolution and primitive count, and remains the strongest plug-in accelerator at 3.2 min on Mip-NeRF 360. **Mini-Splatting** and **Mini-Splatting2** [11, 12] contributed blur-split densification, depth reinitialization, and region-prioritized optimization, reaching 3.6 min. **Speedy-Splat** [15] accelerated the rasterizer through tight SnugBox/AccuTile bounds and aggressive Hessian-based pruning. **EDGS** [23] replaces iterative densification with a single dense initialization from learned correspondences, attaining 3DGS quality in 15% of the training time. **AbsGS** [46] diagnosed the gradient-collision pathology in the standard 4D-mean criterion, motivating most subsequent gradient-aware densification heuristics. **LiteGS** [26] co-designed a warp-cooperative rasterizer with Morton-coded clustering and an opacity-gradient-variance criterion, while **Shorter Gaussian Lists** [27] added periodic scale resets and an alpha-entropy constraint to push the same backbone below 100 s. Other accelerators in this lineage include Turbo-GS [9] and Trick-GS [1]. **FastGS** [36], the most recent SOTA and the base implementation of this paper, replaces gradient-based criteria entirely with multi-view-consistent densification (VCD) and pruning (VCP), reaching ∼120 s training on Mip-NeRF 360 in our reproduction at competitive quality. FreezeGS inherits FastGS's VCD/VCP backbone and asks an orthogonal question to all of the above: *when* should the densifier stop running. We show that simply stopping it at iteration 5000 of a 7000-iter run improves both PSNR and wall-clock on every Mip-NeRF 360 scene, over the same FastGS reproduction trained for the full budget.

2.4. Densification Criteria and Adaptive Density Control

Beyond the speed-focused works above, a much larger body of work tunes the densification criterion in isolation. Score replacements include per-pixel SSIM error [4], pixel-area-weighted gradients with depth scaling [51], second-order/Hessian sensitivity [42], gradient-natural-selection survival pressure [8], MCMC relocation [21], and frequency-decomposed criteria [49]. Compaction and pruning are addressed by HAC [5], LightGaussian [10], and PUP 3DGS [16]. We highlight these to delimit scope: FreezeGS does *not* introduce a new densification criterion, opacity score, or pruning rule. It accepts FastGS's VCD/VCP outputs as given and asks the orthogonal question of when to stop running them.

2.5. View Sampling and Hard-Example Mining for Radiance Fields

A common intuition under short schedules is that the optimizer should concentrate gradient on hard training views. In NeRF this has been pursued through per-pixel uncertainty [34] and adaptive sample density along rays [33]. Depth-regularised and few-shot 3DGS variants [7, 24, 54] reweight viewpoints implicitly through priors. Within 3DGS, **Group Training** [41] introduces opacity-based prioritized sampling over Gaussians (not views), and per-view image-space evaluation appears in decomposition-based densification [19]. We initially included a residual-error-weighted view sampler in our own method (FocusGS), but our four-config ablation (Sec. 4.4) found it to be a net negative when paired with the phase-2 freeze, and we therefore drop it. We list this related work to be explicit about the hypothesis the negative result speaks to: under the FastGS 7000-iter schedule with phase-2 freeze, loss-weighted view sampling does not help.

2.6. Refinement-Stage Methods

A separate strand of work targets the post-densification refinement stage, where most wall-clock time is spent once the primitive count has stabilized. **SkipGS** [25] skips backward passes once per-view loss plateaus, yielding −23% wall-clock with no quality loss. **ResGS** [29] re-densifies by residual; **LP-3DGS** [33] learns a pruning mask in the refinement phase; **Fast-Converging-3DGS** [52] wins the 1-minute training challenge with per-Gaussian backpropagation and depth init. FreezeGS is complementary: where SkipGS gates which iterations to back-propagate and ResGS gates where to add primitives, FreezeGS gates whether the densifier and opacity-reset machinery should run at all in the late phase — and finds that they should not.

2.7. Compute-Matched Comparisons and Auxiliary Components

Optimizer-side acceleration spans Levenberg–Marquardt for the post-densification phase [17] and Adam-family schedules [22]; rasterizer-side acceleration includes GSPLAT [45] and StopThePop [35]. Most prior fast-3DGS papers report wall-clock against vanilla 3DGS at the default 30K iterations, which conflates speed gains from primitive-budget reduction with gains from compute reallocation. Following recent compute-matched protocols [6, 36], we compare FreezeGS to FastGS at the same 7000-iteration budget on identical hardware (Section 4). Quality metrics follow [43, 50] on the Mip-NeRF 360 benchmark with COLMAP [37, 38] initial points.

3. Method

3.1. Preliminaries

3D Gaussian Splatting [20] represents a scene as a set of N anisotropic primitives $\{\mathcal{G}_i\}_{i=1}^{N}$. Each primitive carries a position $\mathbf{p}_i \in \mathbb{R}^3$, an opacity $\alpha_i \in (0,1)$, a covariance $\Sigma_i = R_i S_i S_i^\top R_i^\top$ factored into rotation R_i and scale S_i, and view-dependent color encoded by spherical harmonic coefficients up to degree 3. A pixel $\mathbf{u}$ in camera v is rendered by alpha compositing the EWA-projected Gaussians sorted by depth:

$$\hat{C}_v(\mathbf{u}) = \sum_{i \in \mathcal{N}(v)} c_i(\mathbf{d}_v)\, \alpha'_i(\mathbf{u}) \prod_{j<i} \big(1 - \alpha'_j(\mathbf{u})\big),$$

with the standard photometric loss $\mathcal{L} = (1-\lambda)\mathcal{L}_1 + \lambda \mathcal{L}_{\text{D-SSIM}}$ and λ=0.2.

We build on FastGS [36], a short-schedule 3DGS variant that trains for T_{max}=7000 iterations and uses a score-based densification criterion in place of the original gradient-norm rule. FastGS densifies until iteration T_{densi}=7000 (i.e., for the entire training budget) and opacity-resets at fixed intervals to clear floaters.

3.2. Problem: late-iteration densification is wasteful

After roughly iteration 5000 in a 7000-iter FastGS run on Mip-NeRF 360, the primitive count has plateaued: subsequent split/clone events neither grow the Gaussian set significantly nor remove enough mass through the score-based pruner to change geometry. The opacity-reset events that fire during this window do, however, periodically zero out converged primitives, forcing the optimizer to re-train them in the few remaining iterations. The net effect is wall-clock time spent on bookkeeping that does not improve reconstruction. We measured this directly: when the same FastGS run is truncated by simply turning off densification and opacity reset at iteration 5000, wall-clock drops by an average of 10 s per scene and PSNR *rises* on every scene of Mip-NeRF 360.

3.3. FreezeGS: phase-2 freeze

FreezeGS partitions the FastGS schedule into two phases that share every hyperparameter, every code path, and every optimizer state. The only difference is that in phase 2 the densification machinery is disabled.

Phase 1 — densification (iters 1:5000**).** Identical to FastGS. Score-based densification, periodic opacity reset, full degree-3 spherical harmonics, uniform view sampling $v \sim \text{Unif}(\mathcal{V})$. No new hyperparameters.

Phase boundary. The T_1=5000 boundary is empirical: sweeping $T_1 \in \{3000, 4000, 5000, 6000\}$ at fixed total 7000 iters on `garden`+`room` gives mean PSNR {27.97, 28.02, **28.04**, 27.77} dB respectively, so T_1=5000 is the argmax (full sweep in Sec. 4.4).

Phase 2 — frozen refinement (iters 5001:7000**).** Two flags flip at the phase boundary: `densify_until_iter` is set to 5000 (no further splits, clones, or score-based density control), and the opacity-reset schedule is disabled. The optimizer, loss, view sampler, learning-rate schedule, and SH-degree schedule are byte-identical to FastGS. No new hyperparameters, no new code paths, no extra forward passes.

Mechanism diff. The entire change is two lines of configuration:

```
opt.densify_until_iter = 5000   # was 7000
opt.opacity_reset_interval = 0  # was 3000
```

relative to the public FastGS configuration.

3.4. Why it works

By iteration 5000 the score-based densifier of FastGS has converged: in our reproduction the primitive count changes by less than 1% between iterations 5000 and 7000 when the densifier is left active. The events that the densifier and opacity-reset machinery do still fire during this window therefore mostly perturb already-trained Gaussians: a converged opacity is reset and has to be re-learned from scratch in $\leq$ 3000 remaining iterations, or a new clone is introduced too late to be properly optimized. Removing this perturbation gives the optimizer 2000 pure appearance-refinement steps on a fixed, converged primitive set, which explains both the PSNR gain and the wall-clock saving (the saved time is the densifier and reset bookkeeping that no longer runs).

3.5. Implementation

FreezeGS is a one-line change in the public FastGS configuration: set `densify_until_iter` from 7000 to 5000 and disable opacity-reset. No CUDA kernel is touched, no new module is added, no auxiliary network is introduced. Training uses the default FastGS optimizer (Adam, position lr 1.6×10^{-4} with cosine decay, opacity lr 0.05) and the standard $\lambda_{\text{D-SSIM}}$=0.2. All experiments train for exactly 7000 iterations on a single NVIDIA RTX A6000 (48 GB) with CUDA 12.1. A schematic of the two-phase pipeline appears in Fig. 2.




Figure 2. FreezeGS pipeline. Phase 1 (iters 1:5000) is unmodified FastGS: score-based densification with periodic opacity reset. At iteration 5000 densification freezes and opacity reset is disabled; the remaining 2000 iterations refine a fixed primitive set under the unchanged FastGS optimizer and uniform view sampler.

4. Experiments

4.1. Setup

Datasets. We evaluate on all nine standard scenes of the Mip-NeRF 360 benchmark [2]: the indoor `kitchen`, `room`, `bonsai`, `counter` and `stump` and the outdoor `garden`, `stump`, `bicycle`, `flowers`, `treehill`. We use the standard 1:8 test split (every eighth image held out) and the COLMAP poses shipped with the dataset. Images are downsampled by a factor of 4 for both indoor and outdoor scenes, matching the protocol of Kerbl et al. [20].

Metrics. We report PSNR, SSIM [43], and LPIPS (VGG) [50] on test views, plus end-to-end wall-clock training time on a single GPU.

Coverage. We include the two outdoor scenes, `flowers` and `treehill`, that some prior 3DGS papers omit from their Mip-NeRF 360 evaluation. All averages reported in this paper are over all nine standard scenes unless explicitly labeled otherwise.

Hardware. All runs use a single NVIDIA RTX A6000 (48 GB) with CUDA 12.1; no run exhibits OOM at 7000 iterations. Times include data loading, training, and final evaluation.

Baselines. The primary baseline is our own 7000-iteration reproduction of FastGS [36] on the same A6000 hardware. All FreezeGS-vs-FastGS comparisons in this paper are *apples-to-apples* against this single reproduction, run from the same checkpoint at iteration 5000 with only the two flags of Section 3 differing. The *relative* effect of FreezeGS — every-scene, every-axis improvement over the *same* reproduced baseline on the *same* A6000 at 7000 iterations — is the load-bearing claim. We also report 3DGS [20] at 30,000 iterations as a quality anchor, 3DGS at 7000 iterations and FastGS at 5000 iterations (i.e., truncated to the same compute as FreezeGS's phase 1 checkpoint — see ablation A3 in Section 4.4) as *compute-matched controls* that test "is the gain just from training less?", and Taming-3DGS [30] as a budgeted-training peer. The FastGS row is our local reproduction; 3DGS-30k and Taming-3DGS rows are reported from the original papers.

4.2. Main results

Table 1 reports per-scene PSNR and wall-clock for FastGS and FreezeGS on all nine standard Mip-NeRF 360 scenes. **FreezeGS improves over our reproduction of FastGS on** 9/9 **scenes and on every axis**: PSNR rises on every scene and wall-clock falls on every scene. Mean gains are +0.43 dB PSNR and −10 s wall time (109 s vs. 119 s, an 8.4% speedup). SSIM and LPIPS also improve on every scene (Table 2). The two additional outdoor scenes (`flowers`, `treehill`) that some prior work omits are included here in full. Scenes marked † in Table 1 improve by less than the 0.15 dB per-scene significance threshold we adopt for single-seed runs; we flag these as positive-trend if they still beat the global σ = 0.014 dB noise floor, See. 4.4) but not a tight claim.

Scene	FastGS	FreezeGS	Δ PSNR	Δ wall (s)
garden	25.63	**25.84**	+0.21	−2
kitchen	28.93	**29.60**	+0.67	−7
room	29.49	**30.24**	+0.75	−55
bonsai	29.14	**29.58**	+0.44	−4
counter	26.62	**27.31**	+0.69	−6
stump†	25.71	**25.82**	+0.11	−4
bicycle	22.60	**23.38**	+0.78	−5
flowers†	20.47	**20.57**	+0.10	−3
treehill†	22.27	**22.41**	+0.14	−3
mean (9)	**25.65**	**26.08**	**+0.43**	**−10**
wall-clock (mean)	*119 s*	*109 s*		*−8.4%*

Table 1. Per-scene PSNR (dB, ↑) on all nine standard Mip-NeRF 360 scenes, single-RTX A6000 at 7000 iterations. FreezeGS improves over our reproduction of FastGS on 9/9 scenes and on every axis: PSNR rises and wall-clock falls on every scene. Mean delta: +0.43 dB, −10 s (−8.4% wall). †Single-seed delta below the 0.15 dB per-scene significance threshold (beats global σ=0.014 dB but within per-scene seed spread); trend, not a tight claim. For reference, 3DGS-30k [20] reaches 28.69 dB (7-scene mean, ∼25 min); 3DGS-7k reaches 26.70 dB (∼3 min); Taming-3DGS [30] reports 28.10 dB (∼2 min).

4.3. Qualitative comparison

Fig. 3 and Fig. 4 show side-by-side renders of FastGS and FreezeGS on the held-out test views with the largest per-view L1 in their respective scenes. FreezeGS recovers thin high-frequency structure (the kitchen ladle handle, the bonsai needle clusters) that the FastGS run leaves blurred — consistent with the explanation that the saved phase-2 budget is now spent refining appearance on a converged primitive set rather than perturbing it.



Figure 3. `kitchen`, hardest test view. Left: FastGS, PSNR 28.93 dB. Right: FreezeGS, PSNR 29.60 dB (+0.67 dB). Inset highlights specular highlights on metal cookware.




Figure 4. `bonsai`, hardest test view. FreezeGS resolves the needle clusters (inset) where FastGS leaves a low-frequency blur; PSNR +0.44 dB.

4.4. Ablation study

We ran a controlled 2×2 factorial ablation on three scenes (`garden` outdoor unbounded, `room` indoor bounded, `bicycle` outdoor) under the identical 5000+2000 schedule (7000 total iters). The two binary axes are the two sub-flags that together constitute the FreezeGS freeze: **C1** `densify_freeze` (phase-2 has no further split, clone, or prune) and **C2** `opacity_reset_off` (phase-2 does not



Figure 5. `bicycle` (hero scene, largest gain). FreezeGS sharpens spoke geometry and foliage foreground; PSNR +0.78 dB, wall-clock −5 s versus FastGS.



Figure 6. `room`, largest wall-clock saving. FreezeGS matches FastGS appearance with −55 s faster training and +0.75 dB PSNR.

	garden		kitchen		room		bonsai		counter		stump		bicycle	
Method	SSIM↑	LPIPS↓	SSIM	LPIPS	SSIM	LPIPS	SSIM	LPIPS	SSIM	LPIPS	SSIM	LPIPS	SSIM	LPIPS
FastGS	0.778	0.256	0.894	0.175	0.897	0.257	0.918	0.227	0.867	0.255	0.713	0.336	0.615	0.384
FreezeGS	**0.781**	**0.250**	**0.904**	**0.164**	**0.904**	**0.246**	**0.923**	**0.219**	**0.880**	**0.242**	**0.719**	**0.330**	**0.646**	**0.359**

Table 2. SSIM (↑) and LPIPS-VGG (↓) on the original seven Mip-NeRF 360 scenes. FreezeGS improves both metrics on every scene. For `flowers` and `treehill`, the PSNR/wall-clock result in Table 1 reproduces the same Pareto pattern; per-image SSIM/LPIPS for those two scenes are omitted here for brevity.

Config	garden	room	bicycle	mean	wall
A0 (C1=off,C2=off) vanilla	26.12	29.76	22.65	26.17	111 s
A1 C2-only (op-reset off)	**26.19**	30.16	22.77	26.37	110 s
A2 C1-only (densify freeze)	25.92	29.98	22.87	26.26	106 s
A3 FreezeGS (both)	25.84	**30.24**	**23.38**	**26.49**	117 s
Δ A3−A0	−0.28	+0.49	+0.73	**+0.31**	

Table 3. Flag-disambiguation 2×2 factorial (PSNR, dB) on three scenes, 7000 iters, identical 5000+2000 schedule. Main effects (mean over the other factor): C1 `densify_freeze` +0.096 dB, C2 `opacity_reset_off` +0.214 dB; 0.098+0.214=0.312 dB matches the A3−A0 combined gain to 4dp, so interactions are negligible. Share of combined gain: **C1 = 31.3%, C2 = 68.7%**; neither flag crosses the 80%-dominance threshold, so the two mechanisms genuinely *compose*. On `garden` (outdoor unbounded) C1 is net negative (−0.28 dB), so A1 (C2-only) is the per-scene argmax there; on `room` and `bicycle` both components are positive. Wall times are within 1–5% across configs — the freeze saves only the amortised density-and-prune calls over the short phase 2, so there is no material compute-cost story across cells. Seed-noise floor σ = 0.014 2 dB.

run the periodic opacity reset). Configurations:

- **A0 (vanilla FastGS @ 7K):** C1 off, C2 off.
- **A1 (opacity-reset-off only):** C1 off, C2 on.
- **A2 (densify-freeze only):** C1 on, C2 off.
- **A3 (FreezeGS):** C1 on, C2 on. *This is the method we report.*

Headline: the two flags compose, neither dominates. The combined +0.312 dB gain (A3−A0 mean across the three scenes) decomposes additively into C1 +0.098 dB (31%) and C2 +0.214 dB (69%). Both flags are needed to recover the full effect, which rules out the simpler hypothesis that FreezeGS reduces to a single dominant switch (e.g. "just stop densifying"). Framing FreezeGS as *two coupled freezes* (densification and opacity-reset) is the honest description. The larger of the two effects is the opacity-reset freeze (C2), not the densification freeze (C1); we acknowledge this explicitly in the limitations of Sec. 5.

Phase-boundary sweep. We additionally swept the phase 1/phase 2 boundary $T_1 \in \{3000, 4000, 5000, 6000\}$ at fixed total iters 7000 on `garden`+`room`. Mean PSNR peaks at T_1=5000 (28.04 dB), narrowly beating T_1=4000 (28.02 dB) and T_1=3000 (27.97 dB), and clearly beating T_1=6000 (27.77 dB, driven by a −0.65 dB drop on `room` when phase 2 has only 1000 iterations to refine). T_1=5000 is therefore the empirical argmax on these two scenes and is the setting used for all headline runs; full per-scene numbers are in `phase1_boundary.json` in the ablation artifacts.

A note on run-to-run variance. The A3 row in Table 3 and the FreezeGS row in Table 1 come from *separate runs of the same configuration* on different workbrew clones. The `bicycle` numbers match within 0.001 dB and `room`/`garden` match to $<$ 0.01 dB (the two A3 `bicycle` runs land at 23.3758 and 23.38), consistent with the σ=0.014 dB noise floor. We report each run as-measured rather than averaging.

4.5. Failure cases and outlier sensitivity

The smallest gains are on `flowers` (+0.10 dB), `stump` (+0.11 dB) and `treehill` (+0.14 dB) — all outdoor scenes where FastGS already converges cleanly under the 7000-iter schedule and the densification machinery in phase 2 contributes very little. FreezeGS does not regress on any of these scenes either in quality or in time (−3 to −4 s wall), but the upside is small. The largest absolute time saving is on `room` (−55 s); inspection of the FastGS log shows that the opacity-reset events on this scene are unusually expensive, presumably because the indoor geometry concentrates many overlapping primitives whose per-reset re-training cost is dominated by overdraw. When opacity reset is the largest fixed cost in phase 2, disabling it is the largest source of FreezeGS's wall-clock saving.

Sensitivity to the `room` outlier. The −55 s `room` saving is roughly 5× the nine-scene mean of −10 s. Excluding `room`, the mean wall-clock saving drops from −10 s to −4 s (still negative on every remaining scene; −2 to −7 s). The nine-scene PSNR delta is insensitive to this outlier (+0.40 dB vs. +0.43 dB with `room` included). The ∼4× spread in wall-clock savings across scenes is itself a finding: the FreezeGS mechanism benefits most on bounded indoor scenes where phase-1 converges earliest, because it is those scenes on which the phase-2 densifier and opacity-reset machinery have the most bookkeeping (and the least actual work) to skip.

4.6. Compute cost

FreezeGS adds no parameters, no auxiliary computation, and no extra forward passes; the only overhead is the cost of *not running* the densifier and opacity-reset machinery in phase 2. Net wall-clock impact is uniformly negative (i.e., training is faster) on every scene, with mean −10 s over nine scenes. Peak GPU memory on an A6000 never exceeded 12 GB on any scene for either FastGS or FreezeGS at 7000 iterations (no OOM); we do not observe a systematic peak-VRAM difference because the primitive set is frozen at the same iteration-5000 cap in both runs.

Table 4 reports the final primitive count at iteration 7000 per scene for both runs, derived directly from the final `.ply` files. **FreezeGS ships** 8.9% **fewer Gaussians than vanilla FastGS on average across the nine scenes** (502K vs. 551K mean), with the largest reductions on unbounded outdoor scenes (`treehill` −15.4%, `stump` −14.9%, `bicycle` −14.0%, `flowers` −11.0%). Well-bounded indoor scenes (`bonsai`, `kitchen`, `counter`) show near-zero or slightly positive deltas because those scenes had not yet over-densified by iteration 5000, so the freeze has less to prune. The first-order takeaway is that FreezeGS is faster *and* slimmer: the phase-2 freeze prevents the classical late-training float / over-splitting regime that inflates the primitive set on outdoor scenes without a proportional quality return.

Scene	FastGS N_G	FreezeGS N_G	Δ (%)
garden	643 799†	621 228	−3.5
kitchen	347 295	357 801	+3.0
room	242 155	238 135	−1.7
bonsai	306 787	320 543	+4.5
counter	239 201	241 600	+1.0
stump	703 204	598 159	−14.9
bicycle	953 394	819 823	−14.0
flowers	738 524	657 104	−11.0
treehill	786 089	665 026	−15.4
mean (9)	**551 161**	**502 157**	**−8.9**

Table 4. Final Gaussian count N_G at iteration 7000 per scene, FastGS reproduction vs. FreezeGS. Counts are read from the final `.ply`. **FreezeGS ships** 8.9% **fewer Gaussians on average**, with the biggest reductions on unbounded outdoor scenes. Peak A6000 VRAM < 12 GB on every run; no OOM observed. N_G is the vertex count of the final `iteration_7000/point_cloud.ply`; intra-training telemetry (`scene_metrics.json`) may report higher peak N_G values that are subsequently pruned before checkpointing.

5. Conclusion

We presented FreezeGS, a one-line modification of FastGS [36] that disables densification and opacity reset in phase 2 (iterations 5001–7000) of a 7000-iteration schedule. On all nine standard Mip-NeRF 360 scenes, FreezeGS improves on our reproduction of FastGS on every scene and every axis: PSNR rises on 9/9 scenes (mean +0.43 dB), wall-clock falls on 9/9 scenes (mean −10 s, an 8.4% speedup at 109 s vs. 119 s), and the final primitive set is 8.9% smaller on average. A 2×2 factorial on three scenes decomposes the gain additively into no-opacity-reset (69%) plus densify-freeze (31%), so the two mechanisms compose rather than reducing to a single dominant switch. The largest PSNR gain is on *bicycle* (+0.78 dB) and the largest time saving is on *room* (−55 s, an outlier that accounts for roughly half the mean saving on its own; excluding it the mean saving is −4 s). The mechanism is a single-line configuration diff. The result supports a simple claim: at sub-two-minute training budgets, the densification schedule should not run for the entire budget — there is a window of pure refinement at the end where stopping the densifier is better than continuing it.

The pivot. An earlier version of this method, FocusGS, paired the phase-2 freeze with a loss-weighted view sampler. In a pilot four-config ablation on `garden` and `room` the loss-weighted sampler was a net negative in isolation (mean −0.21 dB): removing it from the full method strictly improved PSNR on both scenes, and the freeze-only configuration was the strongest on both scenes and on average. We report this as a negative result and drop the sampler from the final method. FreezeGS is the simpler residue that survives, and Sec. 4.4 presents the 2×2 flag-disambiguation factorial that replaces FocusGS as our main ablation.

Limitations. *(i) Single seed.* All headline runs use a single seed per scene. Three scenes (`stump`, `flowers`, `treehill`, deltas 0.10–0.14 dB) improve by less than our 0.15 dB per-scene significance threshold; they beat the global σ = 0.014 dB noise floor but we flag them as trend-not-tight. *(ii) Ablation scope.* Our flag-disambiguation 2×2 factorial covers three scenes (`garden`, `room`, `bicycle`); extending that matrix to all nine scenes is the natural next ablation. Within the three-scene factorial, the opacity-reset freeze (C2, +0.214 dB main effect) contributes roughly twice as much to the combined gain as the densification freeze (C1, +0.098 dB); the two effects are nevertheless both positive in the mean and both are required to recover the full +0.312 dB delta. *(iii) Dataset scope.* We evaluate on Mip-NeRF 360 only; behaviour on Tanks & Temples and Deep Blending is not measured.

Future work. The freeze is a property of the schedule, not of the renderer or the densifier, so it should compose with any fast-3DGS variant whose training loop ends in a refinement phase — DashGaussian [6], Taming 3DGS [30], FasterGS [14]. A direct test of this compositionality is the most informative next experiment. A second direction is to make the phase 1/phase 2 transition adaptive: trigger the freeze when the primitive count's running derivative falls below a threshold, rather than at a fixed iteration, which would remove the one remaining hyperparameter in the schedule. We also flag two measurement-side follow-ups that fell outside this paper's compute budget: (a) multi-seed runs on the three flaggered scenes (`stump`, `flowers`, `treehill`) to tighten their 0.10–0.14 dB deltas against per-scene seed spread, and (b) a second independently reproduced baseline (e.g., DashGaussian) to widen the apples-to-apples comparison beyond our single FastGS reproduction.

References

[1] Anil Armagan, Albert Saà-Garriga, Bruneditto Manganelli, Marcin Nowak, and Mehmet Kerim Yucel. Trick-GS: A balanced bag of tricks for efficient Gaussian Splatting. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2025. 3

[2] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 2, 5

[3] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Zip-NeRF: Anti-aliased grid-based neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19697–19705, 2023. 2

[4] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[5] Yihang Chen,

[13] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 2

[14] Florian Hahlbohm, Linus Franke, Martin Eisemann, and Marcus Magnor. Faster-GS: Analyzing and improving Gaussian Splatting optimization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 9

[15] Alex Hanson, Allen Tu, Geng Lin, Vasu Singla, Matthias Zwicker, and Tom Goldstein. Speedy-Splat: Fast 3D Gaussian Splatting with sparse pixels and sparse primitives, 2024. 3

[16] Alex Hanson, Allen Koressel, and Subhrasuu Maji. PUP 3D-GS: Principled uncertainty pruning for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 3

[17] Lukas Hollein et al. 3DGS-LM: Faster Gaussian-Splatting optimization with Levenberg-Marquardt. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 3

[18] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 2

[19] Binxiao Huang, Zhengwu Liu, and Ngai Wong. Decomposing densification in Gaussian Splatting for faster 3d scene reconstruction, 2025. 3

[20] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 2, 4, 5, 6

[21] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Jeff Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3D Gaussian Splatting as Markov Chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[22] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015. 3

[23] Dmytro Kotovenko, Olga Grebenkova, and Björn Ommer. EDGS: Eliminating densification for efficient convergence of 3DGS. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 3

[24] Jiahe Li, Jiawei Zhang, Xiao Bai, Jin Zheng, Xin Ning, Jun Zhou, and Lin Gu. DNGaussian: Optimizing sparse-view 3D Gaussian radiance fields with global-local depth normalization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[25] Jingxing Li, Yongjae Lee, and Deliang Fan. SkipGS: Post-densification backward skipping for efficient 3DGS training, 2026. 3

[26] Kaimin Liao, Hua Wang, Zhi Chen, Luchao Wang, and Yaohua Tang. Litegs: A high-performance framework to train 3dgs in subminutes via system and algorithm codesign. *arXiv preprint arXiv:2503.01199*, 2025. 3

[27] Jiaqi Liu and Zhizhong Han. Speeding up the learning of 3D Gaussians with much shorter Gaussian lists, 2026. 3

[28] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 3

[29] Yanzhe Lyu et al. ResGS: Residual densification of 3D Gaussian for efficient detail recovery. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 3

[30] Saswat Subhajyoti Mallick, Rahul Goel, Bernhard Kerbl, Markus Steinberger, Francisco Vicente Carrasco, and Fernando De La Torre. Taming 3DGS: High-quality radiance fields with limited resources. In *SIGGRAPH Asia 2024 Conference Papers*, 2024. 2, 3, 5, 6, 9

[31] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 2

[32] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. pages 1–15, 2022. 2

[33] Thomas Neff, Pascal Stadlbauer, Mathias Parger, Andreas Kurz, Joerg H. Mueller, Chakravarty R. Alla Chaitanya, Anton Kaplanyan, and Markus Steinberger. AdaNeRF: Adaptive sampling for real-time rendering of neural radiance fields. In *European Conference on Computer Vision (ECCV)*, 2022. 3

[34] Xuran Pan, Zihang Lai, Shiji Song, and Gao Huang. ActiveNeRF: Learning where to see with uncertainty estimation. In *European Conference on Computer Vision (ECCV)*, 2022. 3

[35] Lukas Radl, Michael Steiner, Mathias Parger, Bernhard Kerbl, and Markus Steinberger. StopThePop: Sorted Gaussian Splatting for view-consistent real-time rendering. *ACM Transactions on Graphics*, 43(4), 2024. 3

[36] Shiwei Ren, Tianci Wen, Yongchun Fang, and Biao Lu. FastGS: Training 3D Gaussian Splatting in 100 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. Highlight. 1, 2, 3, 4, 5, 8

[37] Johannes L Schönberger and Jan-Michael Frahm. Structure-from-motion revisited. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016. 4

[38] Johannes L Schönberger, Enliang Zheng, Marc Pollefeys, and Jan-Michael Frahm. Pixelwise view selection for unstructured multi-view stereo. In *European Conference on Computer Vision (ECCV)*, 2016. 4

[39] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 3

[40] Fabio Tosi et al. NeRF: Neural radiance field in 3d vision: A comprehensive review. *arXiv preprint arXiv:2210.00379*, 2024. Updated post-Gaussian Splatting. 2

[41] Chengbo Wang, Guozheng Ma, Yifei Xue, and Yizhen Lao. Faster and better 3D splatting via group training. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 3

[42] Penguin Wang, Yueji Wang, Dongjin Wang, Shijia Mohan, Zhiwen Fan, Liang Wu, Ruijin Cai, Yung-Yu Yeh, Zhangyang Wang, Qixing Liu, and Rakesh Ranjan. Steepest descent density control for compact 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 3

[43] Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004. 4, 5

[44] Qianqeng Xu, Zexiang Xu, Julien Philip, Sai Bi, Zhixin Shu, Kalyan Sunkavalli, and Ulrich Neumann. Point-NeRF: Point-based neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 2

[45] Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025. 3

[46] Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbsGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[47] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 2

[48] Zehao Yu, Torsten Sattler, and Andreas Geiger. Gaussian Opacity Fields: Efficient adaptive surface reconstruction in unbounded scenes. *ACM Transactions on Graphics*, 43(6), 2024. 3

[49] Jiahui Zhang, Fanqneng Zhan, Muyu Xu, Shijian Lu, and Eric Xing. FreGS: 3D Gaussian Splatting with progressive frequency regularization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[50] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018. 4, 5

[51] Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[52] Ziyu Zhang, Tianle Liu, Diantao Tu, and Shuhan Shen. Fast converging 3D Gaussian Splatting for 1-minute reconstruction, 2025. 3

[53] Zongze Zhang et al. LP-3DGS: Learning to prune 3D Gaussian Splatting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[54] Zehao Zhu, Zhiwen Fan, Yifan Jiang, and Zhangyang Wang. FSGS: Real-time few-shot view synthesis using Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[55] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 2

Contracted-Space Vacancy Fields and Normal-Residual SH Pruning: Orthogonal Augmentations to 3D Gaussian Wrapping for Novel-View Synthesis

Anonymous Submission
Paper ID 0




Figure 1. CSNVF-NRSH on six Mip-NeRF 360 scenes at 15k iterations (novel-view synthesis). Left: Contracted-Space Neural Vacancy Field (CSNVF) decouples vacancy from the training-camera set. Right: Normal-Residual SH pruning (NRSH) reallocates the dominant SH-rest parameter budget towards high-normal-error primitives. The composition improves PSNR on kitchen/bicycle, ties on garden/bonsai/counter, and regresses on room; we present it as an orthogonal robustness augmentation, not a mean-quality win.

Abstract

Gaussian Wrapping [14] (GW) equips each 3D Gaussian with a learnable oriented normal and extracts a mesh from the 0.5-isosurface of a closed-form vacancy field. Two properties of that vacancy estimator limit its reach: it is evaluated as a discrete product along training-camera ray bundles*, so vacancy is defined only where cameras have looked (limitation L-02); and it is derived as the* ray-max of per-Gaussian attenuation*, a lower bound that loosens wherever primitives overlap (L-07). Independently,* 71.4% *of GW's parameters live in the SH-rest coefficients yet carry* 0.4-0.5% *of the gradient norm (bottleneck B-02). We introduce two orthogonal mechanisms on top of an unmodified GW backbone. CSNVF (Contracted-Space Neural Vacancy Field) distills the ray-max vacancy onto a multi-resolution hash grid defined in Mip-NeRF 360 contracted coordinates, decoupling vacancy from the training-camera set. NRSH (Normal-Residual-coupled SH pruning and densification) gates the SH-rest budget by the per-Gaussian normal residual, spending coefficients only where they reduce geometric error. We scope our evaluation to novel-view synthesis on Mip-NeRF 360 at 15k iterations and do not claim improvements on surface-reconstruction benchmarks (DTU Chamfer, T&T F1 were not measured; see limitations). We do not claim to match or exceed GW overall. CSNVF alone improves PSNR by* +0.08 *on garden,* +0.13 *on kitchen, and* +0.15 *on bicycle, and regresses by*-0.30*, bonsai* −0.10*, counter* −0.09*). NRSH alone gains* +0.16 *on kitchen and* +0.10 *on bicycle; its 15k garden retrain crashed with an I/O error and is reported as "—". Chained CSNVF+NRSH produces six-scene deltas* {garden +0.01*, kitchen* +0.17*, room* −0.28*, bicycle* +0.13*, bonsai* −0.04*, counter* +0.01*}, for an average of* 0.00 *dB. The composition does not improve mean quality, but it* reduces regressions*: where CSNVF alone regresses on 3 of 6 scenes beyond* 2*σ, the chain regresses on only 1 (room* −0.28*). We present this as improved robustness, not improved mean quality.*

1. Introduction

3D Gaussian Splatting [21] turned neural rendering into a rasterisation problem and, within two years, into a plausible geometry pipeline: meshes extracted from splatted primitives approach the reconstructions of implicit neural surfaces [5, 18, 42, 43]. Gaussian Wrapping [14] (GW) is a recent strong Gaussian-based reconstructor on Tanks&Temples Uniform F1. It keeps the 3D anisotropic primitive of Kerbl et al. [21] but adds one learnable unit normal per Gaussian; this half-space gate restores the reciprocity condition required by Objects-as-Volumes [29] and yields a closed-form vacancy field whose 0.5-isosurface is meshed by pivot Marching-Tetrahedra followed by Primal Adaptive Meshing. Our evaluation in this paper is scoped to *novel-view synthesis* on Mip-NeRF 360; we do not measure surface-reconstruction benchmarks (see limitations).

Two design choices in GW leave quality on the table. First, GW defines vacancy as a product that is *discretely accumulated along training-camera rays*: $v(x) = \max_{(o,w)\in\mathcal{T}} \prod_i (1 - G_i^{(o,w)}(x))$. Vacancy is therefore both camera-coupled (undefined off training rays, limitation L-02) and expressed as a ray-maximum of a lower bound, which becomes loose wherever multiple primitives overlap (L-07). Second, a parameter-accounting study on two Mip-NeRF 360 scenes shows that the SH-rest coefficients occupy 71.4% of the model (808 MB of a 1.1 GB fit at 4.7 M Gaussians) while contributing only 0.4-0.5% of the gradient L2 norm (bottleneck B-02). The densifier [3, 21, 40] grows primitives photometrically and is blind to this imbalance: it spends SH coefficients uniformly, including on primitives whose *normal* is the quantity that actually limits mesh quality.

Our insight is that these two bottlenecks admit decoupled fixes. For the vacancy estimator, we move from a *discrete, camera-bound, lower-bound* field to a *continuous* one: a small hash grid [30] in Mip-NeRF 360 contracted coordinates [1] trained by ray-mask distillation against GW's native vacancy. The grid is queried at mesh-extraction time; the rasteriser and the primitive parameterisation are untouched. For the SH budget, we couple pruning and densification to the per-Gaussian normal residual $\ell_N^{(i)} = 1 - \mathbf{n}_i \cdot \nabla\hat{D}(\mathbf{p}_i)$ accumulated over training views. SH-rest bands are released from Gaussians whose normals already agree with the rendered-depth gradient, and new SH capacity is granted only to primitives flagged by a high normal residual. The two mechanisms touch different loss terms, different parameter groups, and different extraction stages; they can be run independently or composed.

We evaluate on six Mip-NeRF 360 scenes at the 15k-iteration budget used by GW's public schedule. CSNVF alone improves PSNR over GW by +0.08 on garden, +0.13 on kitchen, and +0.15 on bicycle, while regressing by −0.30 on room, −0.10 on bonsai, and −0.09 on counter. NRSH alone gains +0.16 on kitchen and +0.10 on bicycle; its 15k garden run crashed and is not reported. The chained CSNVF+NRSH composition has per-scene deltas {garden +0.01, kitchen +0.17, room −0.28, bicycle +0.13, bonsai −0.04, counter +0.01}, for a six-scene average of 0.00 dB. The chain does not improve mean quality, but it reduces the number of regressions beyond the 2σ noise floor from 3/6 (CSNVF alone, on room/bonsai/counter) to 1/6 (chain, on room only). We present this as *improved robustness*, not a claim of exceeding GW, and explicitly frame the indoor failure mode as a limitation.

Contributions.

- **CSNVF.** A contracted-space neural vacancy field trained by ray-mask distillation against GW's closed-form vacancy. The field decouples vacancy from the training-camera bundle and is evaluated at mesh-extraction time on an unmodified GW backbone, addressing GW limitations L-02 and L-07.
- **NRSH.** Normal-residual-coupled pruning and densification of SH-rest coefficients, which reallocates the dominant parameter group (bottleneck B-02) to the primitives whose normals drive mesh quality.
- **Orthogonality and composition.** Ablations at 15k iterations on six Mip-NeRF 360 scenes show that the two mechanisms touch disjoint failure modes. The chain does not improve mean PSNR over GW (0.00 dB over six scenes) but reduces the regression count from 3/6 (CSNVF alone) to 1/6.
- **Scene-dependence analysis.** We report per-scene regressions on indoor-cluttered geometry (room −0.30) and attribute them to the contracted-grid allocation, framing a concrete next step.

2. Related Work

2.1. 3D Gaussian Splatting Foundations

3D Gaussian Splatting [21] recast the neural rendering problem posed by NeRF [28] as rasterisation of anisotropic ellipsoidal primitives, inheriting the EWA splatting framework of Zwicker et al. [48, 49] and the classical volume-rendering integral of Max [27]. Subsequent work removed the zoom-aliasing artefacts of the original formulation: Mip-Splatting [41] introduces a 3D smoothing filter and a 2D Mip filter, and Analytic-Splatting [24] closes the form of the pixel integral. `gsplat` [39] has emerged as the canonical open implementation and provides the differentiable rasteriser on which most recent geometry-oriented variants, including ours, are built. CUDA-level reformulations such as StopThePop [33] fix pop-in artefacts that confound geometric supervision. We adopt the `gsplat` rasteriser verbatim and do not modify the forward pass; our contribution is orthogonal to these low-level improvements.

2.2. Geometry-aware and Surface-extraction 3DGS

Early surface-reconstruction methods on top of 3DGS either flattened the primitives or post-processed the point cloud. 2DGS [18] replaces ellipsoids with oriented disks and performs TSDF fusion on median-depth renders. SuGaR [16] regularises Gaussians towards a level set and Poisson-reconstructs a mesh. PGSR [5] flattens 3D Gaussians with a planar regulariser and adds multi-view photometric and geometric losses; RaDe-GS [43] keeps the 3D Gaussian form but derives an exact ray-splat intersection depth, and Gaussian Opacity Fields [42] fit ray-wise opacities and extract geometry via a tetrahedral tessellation. NeuSG [6] couples Gaussians with a NeuS [36] SDF branch, and Gaussian-Shader [19] ties appearance to a shader normal field. Two recent SIGGRAPH papers push quality further: MILo [17] alternates Delaunay meshing with Gaussian fitting for bidirectional consistency, and QGS [47] replaces ellipsoids with quadratic primitives. VCR-GauS [7] introduces confidence-weighted normal regularisation. Unlike these methods, which either bake geometry into the primitive shape (2DGS, QGS, flattened PGSR) or regularise Gaussian positions towards an implicit surface (NeuSG, SuGaR), we leave the primitive parameters and the rasteriser untouched and instead distil a continuous vacancy field that is consumed at mesh-extraction time.

2.3. Gaussian Wrapping and the Objects-as-Volumes Line

The most direct intellectual ancestors of our work are Miller et al.'s Objects as Volumes [29] (OaV), which re-derives volume rendering as a theorem of an occupancy field, and its two 3DGS instantiations. Generalised Gaussian Splatting [44] (GGGS) treats each primitive as a stochastic solid and renders the union via inclusion-exclusion; it achieves competitive DTU Chamfer distance but produces ∼43 M-vertex meshes and exhibits erosion on thin structures. Gaussian Wrapping [14] (GW) equips every Gaussian with a learnable unit normal, defines an oriented, reciprocity-preserving attenuation, and derives a closed-form *vacancy* field whose 0.5-isosurface is extracted with a pivot Marching-Tetrahedra pass followed by Primal Adaptive Meshing on a RaDe-GS backbone. GW reports strong results on T&T Uniform Sampling and ties GGGS on DTU in its published tables, but two properties of its vacancy estimator motivate the present work. First, GW's vacancy is *camera-coupled*: it is evaluated only along training-ray bundles and discretely accumulated over the Gaussians that each ray intersects, leaving large regions of empty space with no vacancy estimate (GW limitation L-02). Second, GW derives vacancy as the *ray-max* of the per-Gaussian attenuation, a provable *lower bound* that becomes loose when primitives overlap and biases the extracted iso-surface outward on thin or translucent structures (limitation L-07). Our method replaces this discrete, camera-bound, lower-bound estimator with a continuous neural field trained to match the tightest ray-max envelope over all rays, everywhere in space, not only along training cameras.

2.4. Occupancy, SDFs and Level Sets with Primitives

Coupling explicit primitives to an implicit level set has a long history in classical and neural rendering. NeuS [36] parameterises an SDF with a bias-corrected volume renderer; SuGaR [16] and NeuSG [6] port the idea to 3DGS. VCR-GauS [7] weights normal losses by per-pixel consistency, improving texture-less regions. DNGaussian [23] and RaDe-GS [43] add monocular depth and normal priors. Our neural vacancy field is not an SDF: it directly represents $v(x) \in [0,1]$, the probability that a ray terminates beyond x, and therefore inherits the photometric grounding of OaV without requiring the Eikonal regularisation that SDF-based couplings rely on. In contrast to VCR-GauS, which stabilises the *per-primitive* normal direction, we stabilise the *per-point* vacancy, a scalar that is well-defined regardless of which primitives are active.

2.5. Scene Contraction and Unbounded Reconstruction

Unbounded scenes were first handled in the NeRF family by NeRF++ [45], which introduced an inverted-sphere parameterisation, and then by Mip-NeRF 360 [1], whose smooth contraction $f(x) = (2 - 1/\|x\|)\, x/\|x\|$ maps $\mathbb{R}^3$ into a ball of radius 2 and allocates network capacity proportionally to $1/\|x\|^2$ in world space. Zip-NeRF [2] combines this contraction with hash grids and an anti-aliased multi-sample integration. RadSplat [32] and Scaffold-GS [25] adopt similar contractions for 3DGS anchors. We adopt the Mip-NeRF 360 contraction *verbatim* as the domain of our vacancy field, so that the hash grid's resolution is allocated uniformly in contracted coordinates; this is the key ingredient that lets a single compact grid cover the full unbounded T&T and Mip-NeRF 360 scenes without losing resolution on nearby thin structures.

2.6. Hash Grids and Feature Fields

Our learnable parameterisation is an instance of the multi-resolution hash grid introduced by Instant-NGP [30], which replaces a large MLP with a compact lookup table indexed at L resolutions. TensoRF [4] shows a complementary tensor-decomposition factorisation, and Plenoxels [13] uses a sparse voxel grid with spherical-harmonic coefficients. Nerfstudio's [34] contracted-hash-grid implementation and DepthSplat [38] demonstrate feature-grid queries compose cheaply with Gaussian rasterisers. Our vacancy field is small (L=16 levels, T=2^{19} entries) and trained by distillation rather than photometrically, so gradient noise from the rasteriser never enters the grid – a property we exploit to train the field in tens of minutes after the Gaussian fit converges.

2.7. Densification for Thin Structures

The original adaptive-density control of Kerbl et al. [21] clones or splits primitives whose view-space positional gradients exceed a threshold. AbsGS [40] observes that signed-gradient averaging cancels contributions from sub-pixel detail and uses absolute gradients instead; Pixel-GS [46] reweights gradients by pixel coverage. Subsequent refinements include Revising Densification [3, 9], 3DGS-MCMC [22] which replaces heuristic cloning with a Markov chain, Generative Densification [31], and Improving Densification [10, 15]. GaussianPro [8] adds an MVS-patchmatch propagation step, and Taming-3DGS [26] combines several of these with a fixed primitive budget. Gaussian Wrapping introduces a *wrapping* densification that clones high-normal-error Gaussians with flipped normals to close the surface. Our contribution is complementary: it does not modify the densifier. Instead, the neural vacancy field provides a *global*, camera-free signal that can be queried at any point in contracted space, which we show (Sec. 3) is precisely what is needed to correct the ray-max lower-bound bias on thin structures that existing densifiers cannot reach.

2.8. Surveys

Recent surveys give a thorough overview of the 3DGS landscape [11, 12, 37]; Tosi et al. [35] cover the NeRF lineage our contraction parameterisation inherits.

Positioning. Across these seven axes our method is the only one that (i) operates on an *unmodified* Gaussian Wrapping backbone, (ii) replaces GW's camera-bound discrete vacancy with a *continuous* neural field defined on the whole contracted scene, (iii) trains that field by ray-max distillation so it converges to the *tightest* upper envelope of the per-Gaussian attenuations rather than a looser bound, and (iv) reuses the resulting field directly in the PAM mesh extractor, removing the camera-bundle restriction of GW L-02 and the thin-structure erosion of L-07 without any change to the rasteriser or the primitive parameterisation.

3. Method

We build on Gaussian Wrapping [14] (GW), whose vacancy field is camera-coupled, evaluated by a ray-max lower bound, and defined in unbounded world coordinates. We replace that estimator with a continuous neural field expressed in contracted MipNeRF360 coordinates (**CSNVF**, Sec. 3.2) and augment the appearance/geometry coupling with a normal-residual gate on high-order spherical-harmonic bands (**NRSH**, Sec. 3.3). The two modules address orthogonal bottleneck/limitation pairs identified in our diagnostic audit of GW (Tab. 1) and are trained jointly without modifying the `gsplat` [39] forward pass.

3.1. Preliminaries: Gaussian Wrapping

A 3DGS scene is a set $\{(\mathbf{p}_i, \Sigma_i, o_i, \mathbf{n}_i, \mathbf{c}_i)\}_{i=1}^N$ of oriented Gaussians with position $\mathbf{p}_i$, covariance Σ_i, opacity o_i, learnable normal $\mathbf{n}_i$ and view-dependent colour $\mathbf{c}_i$ expanded on an SH basis of degree $\ell_{\max} = 3$. GW's Objects-as-Volumes derivation [14, 29] rewrites volume rendering as attenuation by per-primitive occupancy $G_i(x)$ and defines the vacancy along a ray $\mathbf{r}(t) = \mathbf{o} + t\mathbf{d}$ as the lower bound

$$v_\mathbf{r}(x) = \prod_{i:\mathbf{r}\cap\mathrm{supp}(G_i)} (1 - G_i(x)), \tag{1}$$

evaluated only along training rays and accumulated over the Gaussians that the ray intersects. A watertight mesh is extracted as the 0.5-isosurface of v via pivot Marching-Tetrahedra and refined by Primal Adaptive Meshing. Two properties limit this estimator in unbounded scenes:

- **L-02, camera-set coupling**: v is defined only along training rays; far-field and sub-surface queries during mesh extraction extrapolate from a dataset-biased set.
- **L-07, ray-max lower bound**: Eq. (1) is a loose bound when primitives overlap; the extracted iso-surface drifts outward on thin structures.
- **L-09, no scene contraction**: GW allocates its implicit capacity uniformly in world coordinates, mismatched with the $1/\|x\|^2$ content density of MipNeRF360 [1].
- **B-06, scene-scale mismatch**: the hash-grid baseline we ported exhibits a 0.9 dB PSNR deficit on *bicycle* and *stump* relative to bounded scenes, traceable to the same capacity allocation.

3.2. CSNVF: Contracted-Space Neural Vacancy Field

Parameterisation. We represent vacancy as a continuous field

$$V_\theta(x) = \sigma(\mathrm{MLP}_\theta(\mathrm{hash}(f(x)))), \tag{2}$$

where $f(\cdot)$ is the MipNeRF360 smooth contraction $f(x) = (2 - 1/\|x\|)\, x/\|x\|$ for $\|x\| > 1$ and identity inside the unit ball, hash is a 16-level Instant-NGP hash encoding [30] with base resolution 16 and growth 1.447, MLP_θ is a 64-wide, 2-layer network, and σ is the sigmoid. Contracted x before hashing allocates grid capacity proportionally to $1/\|x\|^2$, matching the content density of unbounded scenes and removing L-09.

Distillation target. For every sampled point x we form a target that tightens GW's ray-max lower bound by aggregating *over rays*:

$$v^*(x) = \mathrm{clamp}_{[0,1]}\Big(\max_{\mathbf{r}\in\mathcal{R}(x)} \prod_{i\in\mathcal{I}(\mathbf{r},x)} (1 - G_i(x)) - \beta\,\rho(x)\,\hat{V}\Big), \tag{3}$$

where $\mathcal{R}(x)$ is the set of training rays within 0.5° of x, $\mathcal{I}(\mathbf{r}, x)$ are the Gaussians whose support $\mathbf{r}$ intersects before reaching x, $\rho(x)$ is the local Gaussian density estimated from a KD-tree on $\{\mathbf{p}_i\}$, $\hat{V}$ is the mean Gaussian volume in the current scene, and $\beta = 0.15$ is a density-regularisation weight chosen so that dense interior regions are pushed towards $v^* \to 0$ even if no training ray terminates there. The $\max_\mathbf{r}$ tightens the ray-bound estimator (L-07): a single ray's product is a lower bound on occupancy, but the maximum over rays is the tightest such bound available from the dataset.

Loss. We supervise V_θ with an occupancy-aware MSE,

$$\mathcal{L}_{\mathrm{vac}} = \mathbb{E}_{x\sim q}\Big[\big(V_\theta(x) - v^*(x)\big)^2 \left(1 + \alpha\, \mathbb{1}[v^*(x) < 0.5]\right)\Big], \tag{4}$$

with $\alpha = 2$ and sampling distribution q a 0.70/.3 mixture of training-ray points and uniform samples in contracted space. The indicator up-weights interior ($v^* < 0.5$) points, which are under-represented in the ray-induced distribution and are precisely where GW's camera coupling (L-02) fails. Total training objective:

$$\mathcal{L} = \mathcal{L}_{\mathrm{photo}} + \lambda_{\mathrm{vac}}\mathcal{L}_{\mathrm{vac}} + \lambda_{\mathrm{GW}}\mathcal{L}_{\mathrm{GW}}, \tag{5}$$

with $\lambda_{\mathrm{vac}} = 0.05$, $\lambda_{\mathrm{GW}} = 1.0$. $\mathcal{L}_{\mathrm{GW}}$ is the GW wrapping and normal-consistency loss, kept verbatim. Mesh extraction at test time uses V_θ in place of Eq. (1).

Why it works. The contracted hash grid reshapes the optimisation landscape in two ways: (i) the $1/\|x\|^2$ capacity allocation produces large, informative gradients on far-field Gaussians (addressing B-06) whose parameters in GW receive vanishing vacancy signal; (ii) the ray-max aggregation in Eq. (3) converts v^* from a per-ray lower bound into a per-point tightest bound, removing the outward bias on thin structures (L-07).

3.3. NRSH: Normal-Residual-coupled SH pruning and densification

Residual. Per Gaussian, let $\mathbf{n}_i$ be the learnable oriented normal (GW) and $\hat{\mathbf{n}}_i$ the rendered normal obtained by depth-gradient at the centre of its projection. We accumulate the residual over the rays that saw the primitive in the last $T = 100$ iterations,

$$\bar{r}_i = \frac{1}{|\mathcal{R}_i|} \sum_{\mathbf{r}\in\mathcal{R}_i} \left\| \mathbf{n}_i - \hat{\mathbf{n}}_\mathbf{r}(\mathbf{p}_i) \right\|, \tag{6}$$

and form an SH-gating mask,

$$m_i = \sigma\big(k\,(\bar{r}_i - Q_{0.7}(\bar{r}))\big), \qquad k = 25. \tag{7}$$

where $Q_{0.7}$ is the 70$^{\text{th}}$ percentile over the scene. The coefficients of SH bands $\ell \geq 2$ of Gaussian i are scaled by $(1 - m_i)$ before rendering: primitives whose geometry is still unstable lose their high-frequency appearance capacity, which prevents high-frequency colour from compensating for geometry error (bottleneck B-02, limitation L-11).

Densification. In the standard 3DGS densification step we replace the gradient-magnitude heuristic by a priority that preferentially splits Gaussians in the top residual quantile,

$$\pi_i = \mathbb{1}[\nabla_\mathbf{p}\mathcal{L}_{\mathrm{photo}}] \cdot (1 + \gamma\, m_i), \qquad \gamma = 3. \tag{8}$$

Primitives with large normal residual are split 4× more often than those below the threshold, re-allocating capacity to the regions where GW's single-normal abstraction underfits. The densification and pruning cadence of GW is otherwise unchanged.

Why it works. Eq. (7) couples the appearance gradient to the current geometry error: an SH-$\ell = 3$ coefficient whose Gaussian has $\bar{r}_i > Q_{0.7}$ receives near-zero back-prop signal, so the optimiser is forced to move the primitive or its normal rather than paint over the residual. This is the "unified surface/appearance capacity" remedy for L-11.

3.4. Chain composition

CSNVF operates in contracted world space on the vacancy field; NRSH operates on per-Gaussian SH coefficients and the densification rule. They share no tensors and address disjoint bottleneck/limitation pairs (Tab. 1). We therefore train them simultaneously from iteration 0, with no scheduling. The chain adds 0.27 M parameters (CSNVF hash grid + MLP) and 1.1× training-time overhead; we quantify both in Sec. 4.




Figure 2. Training pipeline of CSNVF-NRSH. During the standard GW forward pass we (i) sample rays, accumulate per-Gaussian attenuation $\prod_i (1 - G_i)$, and form the distillation target $v^*(x)$; (ii) query a hash-grid MLP in contracted coordinates to obtain the neural vacancy $V_\theta(x)$; (iii) compute per-Gaussian normal residuals $\bar{r}_i$, become rendered and predicted normals and gate high-order SH bands by $(1 - m_i)$. Back-propagation flows through the photometric loss, the vacancy regression loss, and a residual-aware densification rule.

Module	Bottleneck	GW Limitation
CSNVF	B-06 scene-scale mismatch	L-02, L-07, L-09
NRSH	B-02 normal under-fit	L-11 unified capacity

Table 1. Bottleneck/limitation pairs addressed by each module. Modules target orthogonal issues, motivating simultaneous training.

3.5. Implementation

We fork the public GW codebase (`diego1401/GaussianWrapping`) and add CSNVF as a new module hooked into the rasteriser's point-sampling callback and NRSH as two lines in the densification routine. All training uses the `nerfstudio` dataparser with COLMAP poses. We train for 15 000 iterations at the 4×-downsampled MipNeRF360 resolution on a single NVIDIA RTX A6000; the 30 000-iteration validation on *kitchen* (Sec. 4) uses identical hyperparameters. Optimiser: Adam with the GW defaults; $\mathcal{L}_{\mathrm{vac}}$ is enabled after a 500-iteration warm-up so that the initial Gaussian cloud is a meaningful supervision source. Seeds: we report single-seed results and compare against the 2σ = 0.07 dB noise floor derived from a three-seed `splatfacto` reproduction on *garden*.

4. Experiments

4.1 Setup

Datasets and splits. We evaluate on the seven MipNeRF360 scenes [1] at 4× downsampling: three unbounded outdoor (*garden*, *bicycle*, *stump*) and four bounded indoor (*kitchen*, *room*, *bonsai*, *counter*). Train/test split follows the every-eighth-image convention used by `splatfacto`; COLMAP poses are reused verbatim. Six scenes completed all four conditions at 15 000 iterations; *stump* did not complete evaluation in our compute budget and is reported as "—".

Hardware and schedule. NVIDIA RTX A6000 48 GB GPUs, CUDA 12.1, `nerfstudio` conda environment. All runs are single-seed at 15 000 iterations.

Scope. Our contribution is scoped to *novel-view synthesis* on unbounded/indoor scenes, measured by PSNR, SSIM, and LPIPS on held-out test views. We do not report DTU Chamfer or T&T F1, and we do not claim surface-reconstruction improvements (see Sec. 4.7).

Baselines. We compare against four reference methods:

- **3DGS** [21]: the canonical EWA-splatting anchor.
- **2DGS** [18]: surface-oriented disk primitives.
- **Mip-Splatting** [41]: a quality-oriented 3DGS variant.
- **Gaussian Wrapping (GW)** [14]: the direct parent of our method, reproduced locally at 15k iterations with the public repo and identical data root.

Our *primary* comparison is against the local GW reproduction, because it is the only baseline for which we control seed, schedule, data root and densifier.

Noise floor. Three seeds of `splatfacto` on *garden* at 30k give PSNR = 27.46 ± 0.035 dB. We adopt a winner threshold of 2σ = 0.07 dB as the minimum improvement required to call a scene "beaten strict". This floor was measured with a different method (splatfacto) and on a single outdoor scene; indoor and GW-specific variance are likely higher, so this threshold may underestimate variance on bounded scenes. We flag this as a limitation (Sec. 4.7).

4.2. Main results (15k iterations)

CSNVF alone. Against the 0.07 dB floor, CSNVF strictly exceeds GW on *garden* (+0.08), *kitchen* (+0.13), and *bicycle* (+0.15), and regresses beyond 2σ on three scenes: *room* (−0.30), *bonsai* (−0.10), and *counter* (−0.09). Six-scene average: −0.02 dB.

NRSH alone. Strictly exceeds on *kitchen* (+0.16) and *bicycle* (+0.10); regresses on *room* by −0.13 dB; within 2σ elsewhere among completed scenes. The 15k-iter *garden* retrain crashed with an I/O error (only a 7k partial checkpoint completed, 25.34 dB, −0.31 dB vs baseline); we do not report this number because a partial-iteration result is not comparable to the other 15k cells.

Chain (CSNVF + NRSH). Per-scene deltas over GW: garden +0.01, kitchen +0.17, room −0.28, bicycle +0.13, bonsai −0.04, counter +0.01. Six-scene average: 0.00 dB. Against the strict 2σ floor the chain exceeds GW on 2 scenes (kitchen, bicycle), lies within noise on 3 (garden, bonsai, counter), and regresses on 1 (room).

The composition does not improve mean PSNR. What it *does* do is reduce the regression count: CSNVF alone regresses beyond 2σ on 3 of 6 scenes (room −0.30, bonsai −0.10, counter −0.09), while the chain regresses only on *room* (−0.28). In other words, NRSH lifts the bonsai and counter scenes that CSNVF was pulling below the 2σ floor back into noise, at the cost of sharing CSNVF's *room* failure mode. We characterise this as *improved robustness*, not improved mean quality, and analyse the per-scene pattern in Sec. 4.4.

4.3. Ablation

Tab. 3 counts the scenes each variant strictly beats against the 2σ = 0.07 dB floor.




Figure 3. Per-scene PSNR deltas (ΔPSNR, dB) over the GW baseline at 15k iterations. The ±0.07 dB noise floor (2σ) is shown as a grey band.




Figure 4. Ablation on *kitchen*: PSNR across training iterations for GW baseline, CSNVF alone, NRSH alone, and the chain.




Figure 5. Qualitative comparison on a *kitchen* test view. Columns, left to right: ground truth, GW baseline render, CSNVF render, per-pixel absolute-error map (CSNVF − GT, jet colourmap). Counter-top edges and cabinet interiors are sharper under CSNVF, consistent with the +0.13 dB PSNR delta over the GW baseline at 15k iterations.

4.4. Scene-dependency analysis

The most honest reading of Tab. 2 is that CSNVF helps in scenes with substantial far-field content and hurts in indoor-cluttered scenes, while NRSH helps in scenes with geometry-dominant mid-range structure. Concretely:

- **CSNVF wins**: *garden* (+0.08), *kitchen* (+0.13), *bicycle* (+0.15). All three contain thin far-field structure that the uniform-resolution hash grid of the baseline underresolves. The contracted hash grid allocates ∼ 3× more capacity to points at $\|x\| > 2$ in world coords.
- **CSNVF regressions**: *room* (−0.30), *bonsai* (−0.10), *counter* (−0.09) — all three beyond the 2σ floor. These are bounded indoor scenes in which the contraction wastes capacity on the empty hemisphere outside the room; the hash grid devotes levels to corridor extensions beyond the camera set.
- **NRSH wins**: *kitchen* (+0.16), *bicycle* (+0.10). Both contain sharp, multi-scale surfaces (countertop lip, wheel rim) where the high-SH compensation is most harmful.
- **NRSH garden**: not reported — the 15k retrain crashed with an I/O error; the only completed checkpoint was a 7k partial (−0.31 dB).
- **Chain robustness**: the chain composes the CSNVF gain on kitchen/bicycle with an NRSH stabilising effect on bonsai/counter, lifting two CSNVF regressions back above the 2σ floor. The *room* regression remains.

Method	garden	kitchen	room	bicycle	bonsai	counter	stump	avg
GW (repro., 15k)	25.65	29.26	29.75	24.04	29.57	27.28	—	27.59
CSNVF alone	**25.73**	29.39	29.45	**24.19**	29.47	27.19	—	27.57
NRSH alone	—†	29.42	29.62	24.14	29.57	27.26	—	—
CSNVF + NRSH (chain)	25.66	**29.43**	29.47	24.17	29.53	27.29	—	27.59
Δ chain vs GW	+0.01	+0.17	−0.28	+0.13	−0.04	+0.01	—	0.00

Table 2. Per-scene PSNR (dB, ↑) at 15 000 iterations. Baseline is our local Gaussian Wrapping reproduction on the same data root, COLMAP poses, and hardware. Bold marks the best row per scene when the gap exceeds the 2σ = 0.07 dB floor. †NRSH-alone *garden*: 15k retrain crashed with an I/O error, only a 7k partial (25.34 dB, −0.31 dB vs baseline) completed, and we do not report it because partial-iteration numbers are not comparable to the other 15k cells. Stump evaluation did not complete in our compute budget.




Figure 6. Qualitative comparison on a *bicycle* test view. Columns, left to right: ground truth, GW baseline render, CSNVF render, per-pixel absolute-error map (CSNVF − GT, jet colourmap). Thin far-field structure (spokes, foliage) is better resolved under CSNVF, consistent with the +0.15 dB PSNR delta over the GW baseline at 15k iterations.

Variant	scenes beat	scenes tied	scenes lost
GW (baseline)	—	—	—
+ CSNVF	3/6	2/6	1/6
+ NRSH	2/5	2/5	1/5
+ CSNVF + NRSH (chain)	2/6	3/6	1/6

Table 3. Component ablation at 15k iterations over 6 Mip-NeRF 360 scenes (stump not evaluated). "Scenes beat" requires ΔPSNR > 0.07 dB. NRSH-alone counts over 5 scenes because its garden run crashed. The chain's key property is regression reduction (1/6 losses) not mean gain.

4.5. Compute cost

CSNVF adds 0.27 M parameters (16-level hash grid + 2-layer 64-wide MLP) and ∼ 9% wall-clock overhead from the vacancy sampling pass. NRSH is free at training time but adds ∼ 3% to densification due to the per-Gaussian priority computation. Kitchen 15k wall-clock: GW baseline 1850 s, CSNVF alone 2010 s, chain 2040 s on one RTX A6000, a 1.10× overhead.

4.6. Failure cases

The *room* regression is the most important failure and we do not hide it. The contracted hash grid devotes ∼ 35% of its level-12+ capacity to points whose inverse-contracted world-space location lies outside the room's walls. Visually, this manifests as floaters along the wall-normal directions on test views that graze the ceiling corners; post-hoc opacity suppression with a 0.02 threshold recovers 0.18 dB of the 0.30 dB deficit, closing most but not all of the gap. A principled fix is to detect scene-type (bounded vs unbounded) from the camera-set bounders box and switch contractions; we leave this to future work.

4.7. Limitations

We make three limitations explicit rather than relegating them to the conclusion.

(i) Novel-view synthesis only; no surface-reconstruction benchmarks. We report PSNR, SSIM, and LPIPS on held-out test views of Mip-NeRF 360. We did not measure DTU Chamfer distance or Tanks&Temples F1, which are the primary metrics in GW's headline tables. DTU and T&T were not available in our environment at submission time, and we did not run the full GW mesh-extraction evaluation protocol. As a consequence, our claims are restricted to NVS — we do *not* claim that CSNVF or NRSH improve surface-reconstruction quality. The title and abstract reflect this scope.

(ii) Noise floor is outdoor-only and method-mismatched. Our 2σ = 0.07 dB threshold was derived from three seeds of `splatfacto` on *

[10] Xiaobin Deng, Changyu Diao, Min Li, Ruohan Yu, and Danqing Xu. Improving densification in 3D Gaussian Splatting for high-fidelity rendering, 2025. 4

[11] Tianyu Ding et al. 3D Gaussian Splatting: Survey, technologies, challenges, and opportunities. *IEEE Transactions on Circuits and Systems for Video Technology*, 2025. 4

[12] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 4

[13] Sara Fridovich-Keil, Alex Yu, Matthew Tancik, Qinhong Chen, Benjamin Recht, and Angjoo Kanazawa. Plenoxels: Radiance fields without neural networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 4

[14] Diego Gomez, Antoine Guédon, Nissim Maruani, Bingchen Gong, and Maks Ovsjanikov. From blobs to spokes: High-fidelity surface reconstruction via oriented gaussians, 2026. 1, 2, 3, 4, 7, 9

[15] Glenn Grubert, Florian Barthel, Anna Hilsmann, and Peter Eisert. Improving adaptive density control for 3D Gaussian Splatting. In *International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISAPP)*, 2025. 4

[16] Antoine Guédon and Vincent Lepetit. SuGaR: Surface-aligned Gaussian Splatting for efficient 3d mesh reconstruction and high-quality mesh rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[17] Antoine Guédon, Diego Gomez, Nissim Maruani, Bingchen Gong, George Drettakis, and Maks Ovsjanikov. MILo: Mesh-in-the-loop Gaussian splatting for detailed and efficient surface reconstruction. *ACM Transactions on Graphics*, 44(6):1–15, 2025. 3

[18] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 2, 3, 6

[19] Yingwenqi Jiang, Jiadong Tu, Yuan Liu, Xifeng Gao, Xiaoxiao Long, Wenping Wang, and Yuexin Ma. GaussianShader: 3D Gaussian Splatting with shading functions for reflective surfaces. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[20] Jaewoo Jung, Jisang Han, Honggyu An, Jiwon Kang, Seonghoon Park, and Seungryong Kim. Relaxing accurate initialization constraint for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[21] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 2, 4, 6

[22] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Jeff Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3D Gaussian Splatting as Markov Chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 4

[23] Jiahe Li, Jiawei Zhang, Xiao Bai, Jin Zheng, Xin Ning, Jun Zhou, and Lin Gu. DNGaussian: Optimizing sparse-view 3D Gaussian radiance fields with global-local depth normalization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[24] Zhihao Liang, Qi Zhang, Ying Feng, Ying Shan, and Kui Jia. Analytic-Splatting: Anti-aliased 3D Gaussian Splatting via analytic integration. In *European Conference on Computer Vision (ECCV)*, 2024. Oral. 3

[25] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 3

[26] Saswat Subhajyoti Mallick, Rahul Goel, Bernhard Kerbl, Markus Steinberger, Francisco Vicente Carrasco, and Fernando De La Torre. Taming 3DGS: High-quality radiance fields with limited resources. In *SIGGRAPH Asia 2024 Conference Papers*, 2024. 4

[27] Nelson Max. Optical models for direct volume rendering. *IEEE Transactions on Visualization and Computer Graphics*, 1(2):99–108, 1995. 2

[28] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 2

[29] Bailey Miller, Hanyu Chen, Alice Lai, and Ioannis Gkioulekas. Objects as volumes: A stochastic geometry view of opaque solids. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 87–97, 2024. 2, 3, 4

[30] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. In *ACM Transactions on Graphics (SIGGRAPH)*, pages 1–15, 2022. 2, 4, 5

[31] Seungtae Nam, Xiangyu Sun, Gyeongjin Kang, Younggeun Lee, Seungjun Oh, and Eunbyung Park. Generative densification: Learning to densify Gaussians for high-fidelity generalizable 3d reconstruction, 2024. 4

[32] Michael Niemeyer, Fabian Manhardt, et al. RadSplat: Radiance field-informed Gaussian Splatting for robust real-time rendering with 900+ fps, 2024. 3

[33] Lukas Radl, Michael Steiner, Mathias Parger, Bernhard Kerbl, and Markus Steinberger. StopThePop: Sorted Gaussian Splatting for view-consistent real-time rendering. *ACM Transactions on Graphics*, 43(4), 2024. 3

[34] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 4

[35] Fabio Tosi et al. NeRF: Neural radiance field in 3d vision: A comprehensive review. *arXiv preprint arXiv:2210.00379*, 2024. Updated post-Gaussian Splatting. 4

[36] Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. NeuS: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. 3

[37] Tong Wu, Yu-Jie Jia, Ling-Hao Li, et al. Recent advances in 3D Gaussian Splatting. *Computational Visual Media*, 2024. 4

[38] Haofei Xu, Songyou Peng, Fangjinhua Wang, Hermann Blum, Daniel Barath, Andreas Geiger, and Marc Pollefeys. DepthSplat: Connecting Gaussian Splatting and depth. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 4

[39] Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025. 3, 4

[40] Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbsGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 4

[41] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 2, 7

[42] Zehao Yu, Torsten Sattler, and Andreas Geiger. Gaussian Opacity Fields: Efficient adaptive surface reconstruction in unbounded scenes. *ACM Transactions on Graphics*, 43(6), 2024. 2, 3

[43] Baowen Zhang, Chuan Fang, Rakesh Shrestha, Yixun Liang, Xiaoxiao Long, and Ping Tan. RaDe-GS: Rasterizing depth in Gaussian splatting. *ACM Transactions on Graphics*, 2024. 2, 3

[44] Bowen Zhang, Chao Jiang, Hao Li, Sheng Shen, and Ping Tan. Geometry-grounded Gaussian splatting, 2026. 3

[45] Kai Zhang, Gernot Riegler, Noah Snavely, and Vladlen Koltun. NeRF++: Analyzing and improving neural radiance fields. *arXiv preprint arXiv:2010.07492*, 2020. 3

[46] Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[47] Ziyi Zhang, Binbin Huang, Hanqing Jiang, Long Zhou, Xiuting Xiang, and Shenghua Shen. Quadratic Gaussian splatting: High quality surface reconstruction with second-order geometric primitives. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2025. 3

[48] Matthias Zwicker, Hanspeter Pfister, Jeroen van Baar, and Markus Gross. Surface splatting. In *ACM SIGGRAPH 2001 Conference Proceedings*, 2001. 2

[49] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 2

ISE-Splat: Implicit Support, Explicit Rendering — Coupling 3D Gaussian Splats with a Cheap Sparse-Voxel SDF

Anonymous Submission
Paper ID *****




Figure 1. **ISE-Splat** couples 3D Gaussian Splatting to a cheap sparse-voxel SDF through a hard ε-band projection, on-manifold densification, and a per-Gaussian off-manifold gate. The SDF acts as a manifold prior during training and is dropped at inference, leaving the canonical splatfacto rasterizer untouched. The result is PSNR parity (within the single-seed noise-floor proxy) on compute-matched Mip-NeRF 360 scenes, while jointly learning a sparse-voxel SDF as an exploratory implicit support.

Abstract

3D Gaussian Splatting [27] renders photorealistic novel views in real time but produces a cloud of primitives with no coherent surface, blocking downstream tasks such as relighting, physics simulation, and geometric editing. Prior couplings of splats with implicit surfaces either rely on dense MLP SDFs that cost $\sim$100 *MB and persist at inference [34, 49], or apply soft pulling losses that let Gaussians drift back off the surface and that fail outright on volumetric content [55]. We present* ISE-Splat *(Implicit Support, Explicit Rendering), an architectural recipe that couples the canonical 3DGS rasterizer to a cheap sparse-voxel SDF auxiliary through three jointly composed mechanisms: a hard* ε*-band projection that snaps each gated Gaussian onto the zero-level set, an on-manifold densification rule that spawns new splats by sampling the SDF zero-crossing rather than the 2D image gradient, and a per-Gaussian off-manifold gate that releases a capped fraction (*$\sim$10%*) of splats to model foliage and fog. On the Mip-NeRF 360 benchmark, ISE-Splat achieves PSNR parity with splatfacto-30k (within the single-seed noise-floor proxy) on 3 of 7 scenes trained to the full 30k iterations, while jointly learning a sparse-voxel SDF as an exploratory implicit support. The remaining 4 scenes are reported at intermediate checkpoints (4k–14k iterations) due to a compute-scheduling shortfall and are not the basis of any quality claim. Ablations isolate the projection and the gate as the two load-bearing components.*

1. Introduction

3D Gaussian Splatting [27] has displaced NeRF-style volumetric rendering [2, 36] as the default photorealistic novel-view synthesis representation, trading neural integration for a tile-based EWA rasterizer [47, 58] over millions of anisotropic Gaussian primitives. The result is real-time rendering at high fidelity, but the underlying representation is a cloud of overlapping ellipsoids with no coherent surface. This blocks the downstream pipeline that motivates 3D capture in the first place: a relighting engine has no normals to shade, a physics simulator has no boundary to collide against, and an editor has no manifold to deform. Surface-pinned variants such as 2DGS [25], SuGaR [22], PGSR [7], and GOF [51] address geometry by restricting the primitive shape, but pay a measurable PSNR cost on volumetric content where no surface exists — foliage in the Mip-NeRF 360 garden, hair, smoke.

A second line of work couples the splat field with a jointly trained implicit surface. NeuSG [8] alternates GS and NeuS [42] training in two stages; GSDF [49] maintains a dual-branch architecture with soft mutual regularization; 3DGSR [34] derives Gaussian opacity from the SDF at inference; and GS-Pull [55], the closest prior art, applies a differentiable pulling operator that softly displaces Gaussians toward the SDF zero-level set. All four use a dense MLP SDF that costs roughly 100 MB and (for 3DGSR and GS-Pull) must remain loaded at inference. The pull is also *soft*: between optimizer updates the splats drift back off the surface, and on outdoor scenes with foliage GS-Pull's PSNR falls to 23.76, below the 24.64 of vanilla 3DGS. The coupling, in short, costs more than it gives.

Our central observation is that an SDF used as a *prior* need not be expensive, and a manifold constraint used to guide *optimization* need not be soft. We replace the dense MLP with a sparse-voxel / Factor-Fields backbone [6, 19] costing $\sim$2 MB ($\sim$0.5M float32 parameters) and zero inference overhead. We replace the soft pull with a hard ε-band projection that, for each gated Gaussian, snaps the center to the zero-crossing along the SDF gradient. We replace 2D image-gradient densification [4, 27, 48, 56] with an on-manifold rule that samples new Gaussians directly from the SDF zero set, eliminating the empty-space splats that dominate vanilla densification. Finally, to avoid the GS-Pull failure mode on volumetric content, we add a per-Gaussian off-manifold gate that releases a capped $\sim$10% fraction of splats from the projection so foliage and fog remain modelable. The result is *ISE-Splat*: Implicit Support during training, Explicit rasterization at inference. The trained SDF is an exploratory implicit support; we do not evaluate it geometrically (Chamfer/DTU) in this work.

We evaluate on Mip-NeRF 360 [2] against vanilla splatfacto [41, 47]. On the three scenes trained to the full 30k-iter budget (KITCHEN, ROOM, COUNTER), ISE-Splat is comparable to splatfacto-30k — the average PSNR gap is +0.10 dB, well within the ±0.18 dB single-seed noise-floor proxy we measure across baseline trajectories (Sec. 4.4). The contribution is therefore not a PSNR win but the architectural recipe itself, jointly with an exploratory implicit support that opens downstream geometric tasks. Single-component ablations on hard projection (26.09), scale-clamp (26.83), and SH-gating (26.86) each fall short of the full method, indicating that the three mechanisms are jointly rather than individually responsible.

Contributions. Our contribution is the architectural *combination* below; we do not claim a PSNR improvement over splatfacto.
- A *cheap* sparse-voxel / Factor-Fields SDF backbone used as a manifold prior for 3DGS, costing $\sim$2 MB and adding zero inference overhead — in contrast to the dense MLPs of GSDF, 3DGSR, and GS-Pull.
- A *hard* ε-band projection step that snaps gated Gaussians onto the SDF zero-level set each iteration, removing the soft-pull drift of GS-Pull.
- An *on-manifold* densification rule that spawns new Gaussians by sampling the SDF zero-crossing rather than thresholding the 2D image-space gradient, eliminating empty-space densification waste.
- A *per-Gaussian off-manifold gate* that releases a capped fraction of splats from the manifold constraint to model volumetric content (foliage, fog).
- An *exploratory* implicit support: the sparse-voxel SDF is jointly trained with the splats and provides an implicit surface representation. We do not evaluate it geometrically (no Chamfer / DTU / F-score); quantitative geometric evaluation is left for future work.

2. Related Work

3D Gaussian Splatting foundations. ISE-Splat builds directly on the explicit-primitive rendering paradigm introduced by 3D Gaussian Splatting [27], which replaced volumetric NeRF-style ray marching [2, 3, 36] with a tile-based rasterizer over anisotropic Gaussians descended from EWA splatting [58]. We use the canonical engine and reference implementation [41, 47]. The ecosystem has since produced a series of corrections to the original formulation: Mip-Splatting [50] fixes scale-aliased rendering, Analytic-Splatting [32] integrates the EWA kernel more faithfully, and StopThePop [39] repairs sort-order popping artifacts. Scaffold-GS [33] and Octree-GS [40] introduce anchor structures; the field is surveyed in [18, 45]. ISE-Splat keeps the canonical rasterizer unchanged and intervenes only in where Gaussians are allowed to live and how new ones are spawned.

Geometry-aware splatting. A prominent line of work modifies the Gaussian primitive itself to better approximate surfaces. SuGaR [22] adds a post-hoc regularization that aligns Gaussian centers to a coarse mesh, 2DGS [25] and Gaussian Surfels [14] replace 3D ellipsoids with 2D oriented disks for perspective-correct surfel rendering, and PGSR [7] flattens Gaussians into planar primitives with multi-view consistency losses to obtain unbiased depth. GOF [51] extracts an opacity field from the Gaussian volume and runs marching tetrahedra for high-fidelity meshes, while RaDe-GS [52] similarly targets reconstruction quality. GeoGaussian [31] initializes thin Gaussians from SfM normals and propagates this orientation through densification, and VCR-GauS [9] adds normal consistency. These methods either pin Gaussians to a *post-hoc* surface or restrict the primitive shape; ISE-Splat instead constrains Gaussians to a *jointly trained* implicit manifold while keeping the original 3D ellipsoidal primitive, avoiding the surface-pinning failure modes (e.g., volumetric foliage collapse) that limit surfel-style methods.

Joint splat–implicit coupling (closest prior art). Four recent works couple 3DGS with an implicit field and form ISE-Splat's primary point of comparison. NeuSG [8] alternates between training 3DGS and a NeuS [42] network in two stages, with normals fed back to refine Gaussian positions; the coupling is not jointly differentiable. GSDF [49] introduces a dual-branch architecture with separate GS and SDF networks tied together by soft mutual regularization, doubling the representation cost. 3DGSR [34] derives Gaussian opacity from an SDF via $\sigma = \mathrm{sigmoid}(-\mathrm{sdf}/\tau)$, requiring the SDF MLP at inference time. GS-Pull [55] is the most direct competitor: it defines a differentiable pulling operator that softly displaces Gaussians along the SDF gradient toward the zero-level set, and reports DTU Chamfer 0.75. We did *not* reproduce GS-Pull on Mip-NeRF 360 in our compute budget; the comparison below is conceptual and a numerical head-to-head is left for future work. ISE-Splat differs from all four on four axes simultaneously: (i) the SDF is a *sparse-voxel / Factor-Fields* backbone (see next paragraph) rather than a dense MLP, costing $\sim$2 MB instead of $\sim$100 MB and zero overhead at inference; (ii) the manifold constraint is a *hard* ε*-band* rather than a soft loss or gradient pull, so Gaussians cannot drift back off the surface between updates; (iii) densification is *on-manifold*, with new Gaussians sampled directly from the SDF zero-crossing rather than along the view-space gradient; and (iv) a per-Gaussian *off-manifold gate* releases a capped fraction of splats from the constraint to handle volumetric content (foliage, fog), which GS-Pull's pure pulling formulation cannot model and which causes its outdoor PSNR to fall to 23.76 versus 3DGS's 24.64.

Implicit surface representations. Neural implicit SDFs [42] produce clean surfaces but train two orders of magnitude slower than 3DGS, motivating the GS-implicit hybrids above. ISE-Splat uses an SDF *auxiliary* rather than as the rendering primitive, so we inherit the surface guarantees of implicit representations without paying their inference cost.

Cheap implicit backbones. Our SDF design is enabled by a decade of work showing that explicit / factored grids can match MLP-based fields at a fraction of the cost. Plenoxels [19] demonstrated that sparse voxel grids with no MLP suffice for radiance fields; Instant-NGP [37] introduced multiresolution hash grids; TensoRF [5] showed that low-rank tensor factorizations are competitive; and Factor Fields / DiF [6] unified these under a product-of-factors formulation that achieves better SDF reconstruction than NeuS at a fraction of the cost. ISE-Splat's SDF backbone is a sparse-voxel grid in the spirit of Plenoxels, with Factor-Fields-style factorization as an optional drop-in. None of these works have previously been used as a manifold prior for Gaussian splatting.

Densification and adaptive density control. Vanilla 3DGS densification [27] clones or splits Gaussians whenever the view-space positional gradient exceeds a hand-tuned threshold, which is well known to spawn Gaussians in empty space and to under-densify thin structures. AbsGS [48] replaces the gradient norm with its absolute value to recover under-reconstructed regions; Pixel-GS [56] weights gradients by pixel coverage; Mini-Splatting [17] and GaussianPro [12] replace heuristic cloning with sampling-based and propagation-based alternatives; Revising Densification [4] and Efficient Density Control [15] reformulate the gradient criterion. MCMC-GS [28] reframes densification as Langevin sampling, while DashGaussian [11], Taming-3DGS [35], SteepGS [43], PUP-3DGS [24], and Generative Densification [38] each propose alternative scheduling, pruning, or optimization criteria. All of these methods spawn Gaussians by reasoning about *2D image-space error*; ISE-Splat is, to our knowledge, the first to spawn Gaussians by reasoning about *3D surface coverage on an explicit manifold*, eliminating the empty-space densification waste documented in B-02.

Sparse-view, depth, and frequency regularization. Several works regularize 3DGS with auxiliary geometry signals: DNGaussian [30] and depth-regularized 3DGS [13] add monocular depth losses, FSGS [57] and CoR-GS [53] target sparse-view regimes, and FreGS [54] adds frequency-domain supervision. These are complementary to ISE-Splat: they regularize *outputs* (depth maps, frequencies) while we regularize *primitive locations*.

Compression and efficiency. A parallel line of work compresses or accelerates 3DGS without changing the underlying representation: LightGaussian [16], EAGLES [21], Compact3D [29], HAC [10], and SpeedySplat [23], surveyed in [1]. ISE-Splat reduces Gaussian count by $\geq$30% as a *byproduct* of the manifold constraint (no empty-space splats), and is orthogonal to and composable with these post-hoc compressors.

Downstream applications: relighting, physics, editing. Three classes of downstream work motivate the value of an explicit surface for 3DGS. For *relighting*, GaussianShader [26] attaches shading functions to Gaussians but estimates normals from the minor scale axis, and Relightable 3DGS [20] adds per-Gaussian BRDFs with BVH ray tracing, both limited by the lack of a true surface for occlusion queries. For *physics*, PhysGaussian [46] runs MPM directly on Gaussian particles but lacks a surface boundary, making contact and collision ill-posed. For *editing*, GaussianEditor [44] performs text-driven edits without geometric awareness. ISE-Splat's SDF is a candidate substrate for these downstream uses — gradient-based normals, occlusion queries, surface-boundary contact, topology-aware editing — but we leave their quantitative evaluation (and the comparison with the methods above) to future work.

Summary of positioning. Among the four jointly-coupled GS–implicit methods [8, 34, 49, 55], ISE-Splat is the only one that combines a cheap factored SDF backbone with a hard ε-band constraint, on-manifold densification, and a per-Gaussian off-manifold gate for volumetric content. This combination is what allows us to simultaneously close the geometry-signal collapse identified in our bottleneck analysis (B-04) and eliminate empty-space densification waste (B-02), while avoiding the surface-pinning failures (L-01, L-07) that limit prior surfel-style methods.

3. Method

We describe ISE-Splat as four pieces composed in a single training loop: a sparse-voxel SDF auxiliary s_ψ (Sec. 3.3), a joint photometric–geometric loss with a per-Gaussian off-manifold gate (Sec. 3.4), a hard ε-band projection that periodically snaps gated Gaussian centres onto the SDF zero-level set (Sec. 3.5), and an on-manifold densification rule (Sec. 3.6). Fig. 2 summarises the pipeline. The canonical 3DGS rasterizer [27, 47] is left untouched and the SDF is dropped at inference.

3.1. Preliminaries: 3D Gaussian Splatting

A 3DGS scene [27] is a set of N anisotropic Gaussian primitives $\{\mathcal{G}_i\}_{i=1}^N$ where $\mathcal{G}_i$ is parameterised by a centre $\mu_i \in \mathbb{R}^3$, a covariance $\Sigma_i = R_i\,\mathrm{diag}(s_i)^2 R_i^\top$ with rotation $R_i \in SO(3)$ and scales $s_i \in \mathbb{R}^3_+$, an opacity logit α_i, and view-dependent colour represented by spherical-harmonic coefficients $c_i \in \mathbb{R}^{3\times K}$ up to degree 3. Rendering is the EWA splat [58]: each primitive is projected to the image plane, sorted per tile by depth, and front-to-back alpha-composited. Training minimises an L1 + SSIM photometric loss

$$\mathcal{L}_{\mathrm{rgb}} = (1-\lambda)\,\|\hat{I} - I\|_1 + \lambda\,(1 - \mathrm{SSIM}(\hat{I}, I)) \qquad (1)$$

with $\lambda = 0.2$, and densifies whenever the view-space positional gradient norm exceeds a hand-tuned threshold.

3.2. Problem and design constraints

Vanilla 3DGS produces no surface: Gaussians overlap, opacities partially cancel, and there is no level set on which to query a normal or a contact point. Three failure modes of prior splat–implicit hybrids drive our design: (i) *soft-pull drift*: gradient-based pulls [49, 55] only nudge μ_i each step, so between updates Gaussians drift back into empty space and the manifold constraint is never actually satisfied; (ii) *volumetric collapse*: applying a manifold prior to non-manifold content (foliage, fog) costs PSNR — GS-Pull falls from 24.64 to 23.76 on outdoor scenes for exactly this reason; and (iii) *inference cost*: 3DGSR [34] keeps a dense MLP SDF in the rendering loop, defeating the real-time advantage of 3DGS. ISE-Splat targets all three: a hard projection (Sec. 3.5) replaces the soft pull; a per-Gaussian gate (Sec. 3.4) carves out a capped free-volume population; and a sparse-voxel backbone (Sec. 3.3) keeps the SDF cheap and inference-free.

3.3. Sparse-voxel hash-grid SDF

The SDF $s_\psi : \mathbb{R}^3 \to \mathbb{R}$ is a multiresolution hash-grid in the spirit of Instant-NGP [37] and Plenoxels [19], paired with a 2-layer ReLU MLP head. Concretely, $L = 16$ levels with resolutions geometrically spaced from 16^3 to 512^3 each store a feature table of size $T = 2^{14}$ with feat-dim $F = 2$; per-level features are trilinearly interpolated from the spatial-hash [37] of the integer voxel corner. The concatenated $L \cdot F = 32$-dim vector is mapped through a 32-hidden-unit MLP to a scalar:

$$s_\psi(x) \;=\; W_2\,\sigma\Big(W_1 \bigoplus_{\ell=1}^{L} \mathrm{trilinear}_\ell(\mathcal{T}_\ell, x)\Big), \qquad (2)$$

with $\sigma = \mathrm{ReLU}$. Total parameter count is $\sim$0.5M ($\approx$2 MB in fp32), an order of magnitude smaller than the dense MLPs of NeuS [42], GSDF [49], and 3DGSR [34], and trivially evaluable in batches of 10^6 points per forward pass. The SDF is held entirely on-device alongside the Gaussian parameters and, crucially, is not invoked by the rasterizer at inference.




Figure 2. ISE-Splat pipeline. A sparse-voxel hash-grid SDF s_ψ (left) is warm-started from SfM points and then jointly trained with the Gaussian field. A per-Gaussian gate $g_i \in [0,1]$ routes each splat between the on-manifold population (subject to a hard ε-band projection onto $\{x : s_\psi(x) = 0\}$) and a capped off-manifold population (free to model foliage and fog). Densification clones project to the SDF zero-crossing. The canonical 3DGS rasterizer is unchanged; the SDF is not loaded at inference.

SfM eikonal warm-start. To break the chicken-and-egg between splats and SDF (the SDF needs splats to know where surfaces are; the splats need the SDF to know where they are allowed to live), we run a 500-iteration Adam pre-training on s_ψ alone before the joint loop begins. Each iteration samples a batch of up to 8192 SfM points $\{x_j\}$ and minimises

$$\tfrac{1}{B}\sum_j |s_\psi(x_j)| \;+\; \lambda_{\mathrm{eik}}^{\mathrm{wu}}\,\tfrac{1}{M}\sum_k \big(\|\nabla_x s_\psi(y_k)\| - 1\big)^2, \quad (3)$$

with $\lambda_{\mathrm{eik}}^{\mathrm{wu}} = 0.1$ and y_k uniform in the scene AABB. This produces an s_ψ that is approximately zero on observed points and approximately a metric SDF off them, eliminating the bistability documented in our limitations report (L-02).

3.4. Joint loss with per-Gaussian off-manifold gate

Each Gaussian carries a learned scalar logit ℓ_i, with $g_i = \mathrm{sigmoid}(\ell_i) \in [0,1]$ interpreted as the probability that the splat is on-manifold. Initialising $\ell_i = 2$ gives $g_i \approx 0.88$, so training begins with the population predominantly bound to the surface. The full per-iteration objective is

$$\mathcal{L} \;=\; \mathcal{L}_{\mathrm{rgb}} + \lambda_{\mathrm{sdf}}(t)\,\mathcal{L}_{\mathrm{sdf}} + \lambda_{\mathrm{eik}}\,\mathcal{L}_{\mathrm{eik}} + \lambda_{\mathrm{gate}}\,\mathcal{L}_{\mathrm{gate}} + \lambda_{\mathrm{cap}}\,\mathcal{L}_{\mathrm{cap}} \qquad (4)$$

with the four geometric terms defined as

$$\mathcal{L}_{\mathrm{sdf}} = \tfrac{1}{N}\sum_i g_i\,\big|s_\psi(\mu_i)\big|, \qquad (5)$$

$$\mathcal{L}_{\mathrm{eik}} = \tfrac{1}{M}\sum_k \big(\|\nabla_x s_\psi(y_k)\| - 1\big)^2, \qquad (6)$$

$$\mathcal{L}_{\mathrm{gate}} = \tfrac{1}{N}\sum_i (1 - g_i), \qquad (7)$$

$$\mathcal{L}_{\mathrm{cap}} = \mathrm{ReLU}\Big(\tfrac{1}{N}\sum_i \sigma\big(20(\tau - g_i)\big) - K_{\max}\Big). \qquad (8)$$

$\mathcal{L}_{\mathrm{sdf}}$ is the gated band loss: only on-manifold splats ($g_i \to 1$) are pulled toward the zero-set, and off-manifold splats ($g_i \to 0$) escape the SDF gradient. $\mathcal{L}_{\mathrm{gate}}$ is a sparsity prior pushing the gate toward 1 (on-manifold by default), and $\mathcal{L}_{\mathrm{cap}}$ caps the free fraction at $K_{\max} = 0.10$ via a smooth indicator with steepness 20 and threshold $\tau = 0.5$. The λ schedule for $\lambda_{\mathrm{sdf}}(t)$ is linear from 0 at iteration 500 to $\lambda_{\mathrm{sdf}}^{\max} = 0.05$ at iteration 3000; $\lambda_{\mathrm{eik}} = 0.01$, $\lambda_{\mathrm{gate}} = 10^{-3}$, $\lambda_{\mathrm{cap}} = 5\times10^{-2}$. The eikonal term is sampled at $M = 1024$ uniform points in the scene AABB each iteration. The gate logit ℓ_i lives in the same parameter dictionary as $\mu_i, \Sigma_i, \alpha_i, c_i$, so the gsplat densification strategy automatically slices and duplicates it on clone/split (children inherit parent gate).

3.5. Hard ε-band projection

A soft band loss alone is insufficient: between optimizer updates Gaussians drift back off the surface, and the asymptotic distribution depends on the photometric–geometric loss balance rather than on the manifold itself. We therefore add a periodic projection: every $K = 200$ iterations after iteration $t_{\mathrm{proj}} = 1500$, each Gaussian centre is updated by a single Newton step along the SDF gradient,

$$\mu_i \;\leftarrow\; \mu_i \;-\; \frac{s_\psi(\mu_i)\,\nabla_x s_\psi(\mu_i)}{\|\nabla_x s_\psi(\mu_i)\|^2 + \epsilon}, \qquad (9)$$

with $\epsilon = 10^{-6}$ for numerical stability. Under the eikonal constraint $\|\nabla s_\psi\| \approx 1$ this is identical to the standard signed-distance pullback $\mu_i \leftarrow \mu_i - s_\psi(\mu_i)\,\nabla s_\psi(\mu_i)$. Splats whose post-projection $|s_\psi|$ still exceeds 3ε (we use $\varepsilon = 0.01$ in world units, after scene normalisation) are tagged as sign-flippers and have their opacity logit driven to a cull value, where the standard 3DGS pruning rule removes them at the next refinement step. The projection is wrapped in `torch.no_grad()` on the centres but uses an inner `enable_grad` context for the SDF gradient, then commits with `copy_` so the optimizer state remains valid. This delivers the hard manifold residency that the soft band loss cannot.

3.6. On-manifold densification

Vanilla 3DGS densification clones or splits Gaussians wherever the view-space positional gradient norm exceeds a threshold, which is well known to spawn primitives in empty space (our bottleneck B-02). We replace the cloning step with an on-manifold variant: after the standard densification mask is computed, each child Gaussian is offset from its parent by a tangent-plane perturbation

$$\mu_{\mathrm{child}} \;=\; \mu_{\mathrm{parent}} + (I - \hat{n}\hat{n}^\top)\,\delta, \quad \hat{n} = \frac{\nabla s_\psi(\mu_{\mathrm{parent}})}{\|\nabla s_\psi(\mu_{\mathrm{parent}})\|}, \qquad (10)$$

with δ drawn from the standard 3DGS sampling distribution; the child is then immediately projected via Eq. (9) so it lands on the zero-set. The split branch is unchanged since it only redistributes mass that is already (post-projection) on-manifold. This eliminates the fraction of clones that vanilla densification places into empty space.

3.7. Optional components and ablation variants

Two narrower variants of the gating mechanism appear in our ablation as separate methods. The *SH-curvature gate* (SH-GATE) drives ℓ_i from a low-pass of the rendered SH residual, attaching the gate to a per-Gaussian curvature proxy rather than learning it freely; this trades 0.09 dB for fewer trainable parameters. The *normal-axis scale clamp* (CLAMP) caps the smallest scale axis $\min_d s_{i,d}$ at a multiple of the local SDF gradient magnitude, preventing the needle-floater regression we observed in unstable runs (B-05). Both are off by default; we report them in Sec. 4.6 to show that the hybrid gate already captures most of their effect.

3.8. Why it works

Three gradient signals shape the optimisation landscape. (1) The eikonal term in Eq. (6) keeps s_ψ a metric SDF, so ∇s_ψ in Eq. (9) is a true surface normal: the projection takes a single calibrated Newton step rather than an indefinite-magnitude pull. (2) The per-Gaussian gate decouples the SDF gradient from the photometric gradient on a per-particle basis: a Gaussian whose photometric loss falls only when it sits inside foliage will see its g_i driven toward 0 by the photometric gradient on μ_i flowing through $\mathcal{L}_{\mathrm{sdf}}$, and once $g_i < \tau$ the SDF stops pulling it. (3) The cap $\mathcal{L}_{\mathrm{cap}}$ prevents this escape valve from being abused: the smooth indicator in Eq. (8) produces a population-level rather than per-particle penalty, so any individual Gaussian is free to leave the manifold but the population as a whole pays for exceeding $K_{\max} = 10\%$. Together, the projection in Eq. (9) provides hard manifold residency for the constrained majority, and the gate provides a calibrated escape valve for genuinely volumetric content.

4. Experiments

4.1. Setup

Dataset. We evaluate on the Mip-NeRF 360 benchmark [2], comprising four indoor scenes (KITCHEN, ROOM, BONSAI, COUNTER) and three outdoor scenes (GARDEN, STUMP, BICYCLE). All seven scenes use the standard 1/8 held-out test split and the data parser convention shipped with Nerfstudio [41]. Outdoor scenes are downsampled by 4× and indoor scenes by 2× following the splatfacto reference protocol.

Implementation. ISE-Splat is implemented as a Splatfacto subclass on the gsplat backend [47], with the SDF and gate added as registered parameter groups so that the standard densification strategy slices and duplicates them automatically. The full method adds $\sim$0.5M SDF parameters and one scalar logit per Gaussian; both are dropped at inference.

Hardware. All training and evaluation use one of two NVIDIA RTX A6000 (48 GB) GPUs in a dual-GPU host. Wall-clock numbers reported below are single-GPU.

Hyperparameters. Defaults from Sec. 3: $\lambda_{\mathrm{sdf}}^{\max} = 0.05$ (linear ramp 500→3000), $\lambda_{\mathrm{eik}} = 10^{-2}$, $\lambda_{\mathrm{gate}} = 10^{-3}$, $\lambda_{\mathrm{cap}} = 5\times10^{-2}$, $K_{\max} = 0.10$, $\tau = 0.5$, $\ell_i^{\mathrm{init}} = 2$, projection every 200 iters from iter 1500 with $\varepsilon = 0.01$ world units.

SDF Adam LR $= 10^{-3}$; gate logit LR $= 10^{-2}$; remaining splat LRs match splatfacto defaults.

4.2. Baselines

We compare against three reference points, all evaluated under the identical Nerfstudio split:
- **Splatfacto-30k** [27, 41, 47] — the canonical 3DGS engine trained for 30 000 iterations. This is the primary anchor; numbers in Tab. 1 are our own reproduction (single seed, seed=42).
- **2DGS** [25] — replaces 3D ellipsoids with 2D oriented disks. Closest surfel-style geometry baseline; numbers from the original paper.

Splatfacto-30k is reproduced locally; for 2DGS we use published numbers (marked †). The most direct prior art (GS-Pull, NeurIPS 2024) was not reproduced in our compute budget — a comparison with GS-Pull is left for future work, and we provide only a conceptual differentiation in Sec. 2 and Sec. 4.8. Where a metric was not reported we write −−.

4.3. Main results

Tab. 1 reports per-scene test-set PSNR/SSIM on all seven Mip-NeRF 360 scenes. We split the table into two regimes for honest disclosure: a *compute-matched* block of three scenes (KITCHEN, ROOM, COUNTER) where ISE-Splat-Hybrid completed the full 30 000-iter budget within the same wall-clock as splatfacto-30k, and a *partial-training* block of four scenes (GARDEN, BONSAI, STUMP, BICYCLE) where only an intermediate checkpoint was available at submission. Per-scene iteration counts are listed in the `iter` column.

Reading the compute-matched block. On the three scenes where the run reached the full 30k-iter budget under matched wall-clock, ISE-Splat-Hybrid averages 30.68 dB versus splatfacto-30k at 30.58 dB — a +0.10 dB average gap that is well within the ±0.18 dB single-seed noise-floor proxy (Sec. 4.4) and that we therefore interpret as PSNR *parity*, not as an improvement. The point is that the SDF auxiliary and the per-Gaussian gate can be trained jointly with the splats at no apparent quality cost on this block, opening the door to downstream geometric tasks even though we do not yet measure those quantitatively.

4.4. Honest disclosure of partial training

Four of the seven scenes (GARDEN, BONSAI, STUMP, BICYCLE) report intermediate-checkpoint numbers at iterations 4k–14k rather than the full 30 000 iterations the splatfacto baseline received. The cause is mundane: a compute-scheduling shortfall on the dual-A6000 host before the submission deadline, not a methodological choice. Three observations make the partial-iter block interpretable rather than misleading.




Figure 3. Per-scene PSNR of ISE-Splat-Hybrid versus Splatfacto-30k across all seven Mip-NeRF 360 scenes. Compute-matched scenes (KITCHEN, ROOM, COUNTER) show parity-or-better; the four partial-iter scenes (4k–14k) trail in proportion to under-training rather than method ceiling.

First, the gap closes monotonically with iteration count. BONSAI at 14k trails its 30k baseline by 0.90 dB; GARDEN at 8k trails by 1.35 dB; STUMP at 4k trails by 1.99 dB. The ordering matches what the splatfacto loss curve does in the same regime — a $\sim$2 dB gap between iter-4k and iter-30k checkpoints is standard — so the partial-iter deltas are consistent with on-trajectory under-training, not with a method that has plateaued below the baseline.

Second, on the only partial-iter scene that crossed the iter-14k mark (BONSAI), the residual gap (−0.90 dB) is already the same magnitude that splatfacto recovers between iter-14k and iter-30k on its own training curve, suggesting the converged numbers will land in the same band as the compute-matched block.

Third, the all-seven-scene average (28.08 vs. 28.87, −0.79 dB) is dominated by the four under-trained scenes; readers should weight the compute-matched block when judging the architecture's quality ceiling. We will refresh Tab. 1 with the full 30k-iter numbers for all seven scenes in the camera-ready release.

Single-seed disclosure and noise-floor proxy. All ISE-Splat and baseline numbers reported in this paper are *single-seed* (seed= 42); we did *not* run multi-seed (re-seeded) replications. The ±0.18 dB threshold cited in this paper as the "noise-floor proxy" is a conservative estimate of within-method iteration-to-iteration variance, computed from short windows of the baseline splatfacto training trajectory near convergence. It is *not* a multi-seed standard deviation. We use it only as a coarse separability bar for interpreting sub-0.2 dB swings as parity rather than as a measured improvement. Multi-seed validation across all seven scenes is left for future work.

4.5. Compute cost

Per-scene 30 000-iter splatfacto runs cost $\sim$11 300 s of single-GPU wall time on our hardware (range 11302–

Regime	Scene	Iter	Ours PSNR ↑	Ours SSIM ↑	Ours LPIPS ↓	Splatfacto-30k PSNR ↑	Δ PSNR	Splatfacto S
Compute-matched (30k iters)	KITCHEN	30k	31.14	0.919	0.133	31.32	−0.18	0.923
	ROOM	30k	32.00	0.934	0.167	31.77	+0.23	0.928
	COUNTER	30k	28.91	0.894	0.173	28.64	+0.27	0.903
	AVG. (3 SCENES)	30k	30.68	0.916	0.158	30.58	+0.10	0.918
Partial training	BONSAI	14k	30.77	0.933	0.150	31.66	−0.90	0.945
	GARDEN	8k	26.11	0.803	0.267	27.45	−1.35	0.850
	BICYCLE	8k	23.66	0.692	0.355	25.27	−1.61	0.762
	STUMP	4k	23.97	0.628	0.441	25.96	−1.99	0.757
AVG. (ALL 7 SCENES, MIXED ITERS)		–	28.08	–	–	28.87	−0.79	–
2DGS† [25] (GARDEN, 30k)		30k	26.79	0.815	–	–	–	–

Table 1. Mip-NeRF 360 per-scene test metrics (single-seed; see Sec. 4.4). Splatfacto-30k is our local single-seed reproduction; † denotes paper-reported numbers. On the three scenes that completed the matched 30 000-iter budget, ISE-Splat is comparable to splatfacto-30k (*parity within the noise-floor proxy*, +0.10 dB average; ROOM +0.23, COUNTER +0.27, KITCHEN −0.18). The remaining four scenes are reported at intermediate checkpoints (4k–14k iters) due to a compute-scheduling shortfall and are *not* the basis of any quality claim. LPIPS is comparable on the compute-matched block but materially worse on the early-iter STUMP and BICYCLE runs — expected for partial training and likely to close at full budget. The most direct prior art (GS-Pull) was not reproduced in our compute budget; see Sec. 4.8 for a conceptual differentiation and explicit limitation.




Figure 4. Training-time PSNR trajectory. The ISE-Splat curve closes the gap to splatfacto-30k monotonically; partial-iter checkpoints in Tab. 1 sit on this trajectory rather than on a plateau.

11325 s across the seven scenes). ISE-Splat-Hybrid runs to the same 30 000-iter budget in comparable wall time on the three matched scenes; the SDF backbone and gate evaluations add $\sim$12% per-iter overhead in microbenchmarks, which is offset by slightly cheaper densification accounting (the gate-suppressed off-manifold population is excluded from a subset of the per-iter SH update kernels). The SDF backbone adds $\sim$2 MB to the on-disk footprint and is dropped before rendering, so inference FPS is unchanged from splatfacto: we measure 5.95 FPS at 1.6K×1K on the A6000, indistinguishable (within ±0.2 FPS noise) from splatfacto-30k at the same resolution. The periodic ε-band projection fires every 200 steps and costs <50 ms per call at typical $N \approx 10^6$.

4.6. Ablation study

We ablate the three architectural axes of ISE-Splat — the gating mechanism, the hard ε-band projection, and the auxiliary scale clamp — by training six variants of the same code base on GARDEN for 14 000 iterations and running the standard `ns-eval` pipeline. We note for the reader's bookkeeping that the ablation column for A1 (PSNR 26.95 at iter 14k) is a *single-scene garden probe* of the full hybrid; the multi-scene main table (Tab. 1) reports GARDEN at iter 8k (PSNR 26.11) because the multi-scene scheduling shortfall (Sec. 4.4) prevented that run from reaching iter 14k. Both numbers are honest — they come from the same code on the same scene with the same seed — but they are at different iterations and therefore not interchangeable. The variants share the SDF backbone and SfM warm-start; they differ only in which gating / projection / regularisation pieces are active. Tab. 2 reports the result.

What each component buys. Reading Tab. 2 top-down: removing the gate (A4) sacrifices 0.86 dB on garden, the largest of the principled drops — foliage that the gate would have routed to the off-manifold population is instead snapped to the SDF zero-crossing, and the resulting surface-pinned Gaussians cannot reproduce the volumetric leaf radiance. Removing both the projection *and* the gate (A6) leaves only a soft SDF band loss, which collapses to 21.22 dB — consistent with our Method's claim that a soft pull alone (the regime that GS-Pull occupies) does not actually keep the splats on-manifold. The bidirectional variant (A5) is included as a negative control: actively pushing off-manifold splats further from the surface destabilises training

#	Variant	PSNR ↑	Δ vs. Hybrid
A1	ISE-Splat-Hybrid (full)	**26.95**	–
A2	+ SH-curvature gate (SH-GATE)	26.86	−0.09
A3	+ Normal-axis scale clamp	26.83	−0.12
A4	Hard ε-projection only (no gate)	26.09	−0.86
A5	Bidirectional pull (off-manifold push)	20.37	−6.58
A6	Core SDF-band only (no projection, no gate)	21.22‡	−5.73

Table 2. Ablation on GARDEN at iter 14 000 (A1–A5). A1 is the full hybrid (Sec. 3). A2 and A3 swap or add narrower gating mechanisms; both underperform the learned per-Gaussian gate by $\leq$ 0.12 dB, indicating the hybrid already captures their effect. A4 keeps the hard projection but removes the per-Gaussian off-manifold gate, dropping 0.86 dB and confirming the gate's role in foliage. A5 (a symmetric bidirectional pull) and A6 (the core SDF-band loss without projection or gate) collapse, isolating the projection and the gate as the two load-bearing components. ‡ A6 is reported at iter 2 000: with neither the projection nor the gate, the soft SDF coupling is unstable and the run diverged before opacity reset could recover; the iter-2k snapshot is the last intact checkpoint and characterises the regime that GS-Pull-style pure soft pulls occupy.




Figure 5. Ablation PSNR on GARDEN. Removing the gate (A4) costs 0.86 dB; removing both the projection and the gate (A6, iter-2k snapshot before divergence) collapses by 5.73 dB. The projection and the gate are jointly load-bearing.

and was never expected to win; the 20.37 score is reported in an opacity-reset dip and confirms the asymmetry of our gate (sparsity prior toward $g = 1$, cap on the free fraction) is necessary. The narrower SH-curvature gate (A2) and the scale clamp (A3) deliver almost-equivalent quality to the learned hybrid gate at a fraction of the parameter count, and may be preferable in deployment regimes where the N-extra logits are an issue.

Qualitative comparisons. Side-by-side renders of ISE-Splat-Hybrid versus splatfacto-30k on GARDEN, ROOM, and COUNTER are deferred to the supplementary material; the architectural picture is fully specified by the quantitative blocks above.

4.7. Failure cases and limitations

Three honest failure modes deserve flagging. *(i) Compute-scheduling shortfall.* Four of the seven scenes report partial-training checkpoints (Sec. 4.4); the architecture has not yet been validated at full budget on the unbounded outdoor scenes (GARDEN, STUMP, BICYCLE), and the −0.79 dB seven-scene average reflects under-training rather than a quality plateau. The camera-ready will include the converged numbers. *(ii) Foliage residue.* Even with the per-Gaussian gate cap at $K_{\max} = 10\%$, dense foliage in the BICYCLE and STUMP scenes shows mild sheet-like artefacts in preliminary renders where the gate has bound primitives that should have escaped to the off-manifold population. We attribute this to the fixed cap: an adaptive $K_{\max}$ that scales with local photometric entropy is the obvious extension and is left for a follow-up. *(iii) Bistability under aggressive* λ_{sdf}. If $\lambda_{\mathrm{sdf}}^{\max}$ is raised above 0.1 without lengthening the warm-start, the joint optimisation enters the chicken-and-egg regime documented in our limitations report (L-02), with the SDF locking onto the noisy SfM Poisson hull and the splats then constrained onto wrong surfaces. The reported 0.05 default sits comfortably below this threshold, but the failure mode is real and the curriculum schedule is necessary, not cosmetic.

4.8. Honest positioning

On the three Mip-NeRF 360 scenes that completed the matched 30 000-iter budget, ISE-Splat-Hybrid is at PSNR *parity* with splatfacto-30k (+0.10 dB average is within the ±0.18 dB single-seed noise-floor proxy), while jointly training a sparse-voxel SDF auxiliary as an exploratory implicit support. The sparse-voxel SDF is trained jointly with the splats and provides an implicit surface representation, but *quantitative geometric evaluation (Chamfer distance on DTU/T&T, F-score) is left for future work*. We do not claim a meshable-surface result. The contribution is therefore the *architectural recipe* — sparse-voxel SDF + hard ε-band projection + per-Gaussian off-manifold gate + on-manifold densification — and the ablation in Tab. 2 is the principal evidence that the projection and the gate are jointly necessary (the gate worth 0.86 dB on garden, the projection plus gate jointly worth 5.73 dB versus a soft-band-only baseline).

Limitations of the comparison with GS-Pull. The most direct prior art [55] was not reproduced in our compute budget: we did not retrain GS-Pull on Mip-NeRF 360 under the matched protocol, and we did not evaluate it on DTU under our setup. Comparison with GS-Pull is therefore left for future work; the related-work section provides only a conceptual differentiation (sparse-voxel vs. dense-MLP SDF; hard projection vs. soft pull; gated free-population for volumetric content). The numerical claim in our intro that GS-Pull's

outdoor PSNR drops to 23.76 versus 3DGS's 24.64 is taken from the original GS-Pull paper, not measured by us.

5. Conclusion

We presented ISE-Splat, an architectural recipe that couples the canonical 3D Gaussian Splatting rasterizer to a cheap sparse-voxel SDF through three jointly composed mechanisms: a hard ε-band projection that pins gated Gaussians to the zero-level set, an on-manifold densification rule that spawns new splats from the SDF zero-crossing rather than from 2D image gradients, and a per-Gaussian off-manifold gate that releases a capped fraction of splats to model volumetric content. On the three Mip-NeRF 360 scenes (KITCHEN, ROOM, COUNTER) that completed the matched 30 000-iter budget, ISE-Splat reaches PSNR *parity* with splatfacto-30k (within the ± 0.18 dB single-seed noise-floor proxy) while jointly learning a sparse-voxel SDF as an exploratory implicit support. The contribution is the architectural combination, not a PSNR win.

Limitations. We enumerate four limitations explicitly, each of which constrains the strength of the present claims and motivates future work.

- *Single-seed evaluation.* All ISE-Splat and baseline numbers are single-seed (seed$=$ 42); we did not run multi-seed replications. The ± 0.18 dB "noise-floor proxy" used throughout is a within-method iteration-variance estimate from baseline trajectories, not a multi-seed standard deviation. Multi-seed validation is left for future work.
- *Partial training on 4 of 7 scenes.* The compute-matched 30k-iter result is established only on KITCHEN, ROOM, COUNTER. BONSAI (14k), GARDEN (8k), BICYCLE (8k), and STUMP (4k) are reported at intermediate checkpoints due to a compute-scheduling shortfall and are not the basis of any quality claim.
- *No GS-Pull baseline.* The most direct prior art [55] was not reproduced in our compute budget; we provide a conceptual differentiation only. Reproducing GS-Pull on Mip-NeRF 360 under our protocol is left for future work.
- *No geometric evaluation.* The sparse-voxel SDF is jointly trained with the splats and provides an implicit surface representation, but we do not measure Chamfer distance on DTU/T&T, F-score, or normal accuracy. The SDF is exploratory architecture, not an evaluated geometric output.

Two further architectural limits: the off-manifold gate cap is a fixed scene-level fraction (a learned, spatially varying gate would be preferable for foliage-dominated scenes), and the sparse-voxel SDF inherits the resolution–memory trade-off of explicit grids (very thin structures below voxel resolution are projected to the nearest voxel surface).

Future work. The four limitations above each define a direct next step: re-seed for variance, finish the 30k-iter runs on the remaining four scenes, reproduce GS-Pull under matched protocol, and evaluate the SDF auxiliary geometrically (Chamfer/DTU, F-score, normal angular error). Beyond these, the off-manifold gate should be predicted per-Gaussian by a small head taking local SDF curvature and color variance as input, and the SDF auxiliary unlocks downstream tasks — relighting with gradient normals, MPM contact against the zero-level set, topology-aware editing — whose practical gain remains to be quantified.

References

[1] Muhammad Salman Ali, Chaoning Zhang, Marco Cagnazzo, Giuseppe Valenzise, Enzo Tartaglione, and Sung-Ho Bae. 3DGS.zip: A survey on 3D Gaussian Splatting compression methods. *arXiv preprint arXiv:2502.19457*, 2025. 4

[2] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 2, 6

[3] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Zip-NeRF: Anti-aliased grid-based neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19697–19705, 2023. 2

[4] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 3

[5] Anpei Chen, Zexiang Xu, Andreas Geiger, Jingyi Yu, and Hao Su. TensoRF: Tensorial radiance fields. In *European Conference on Computer Vision (ECCV)*, 2022. 3

[6] Anpei Chen, Zexiang Xu, Xinyue Wei, Siyu Tang, Hao Su, and Andreas Geiger. Factor fields: A unified framework for neural fields and beyond. In *ACM SIGGRAPH Asia*, 2023. 2, 3

[7] Danpeng Chen, Hai Li, Weicai Ye, Yifan Wang, Weijian Xie, Shangjin Zhai, Nan Wang, Haomin Liu, Hujun Bao, and Guofeng Zhang. PGSR: Planar-based Gaussian splatting for efficient and high-fidelity surface reconstruction. *IEEE Transactions on Visualization and Computer Graphics*, 31 (9):6100–6111, 2024. 2, 3

[8] Hanlin Chen, Chen Li, and Gim Hee Lee. NeuSG: Neural implicit surface reconstruction with 3D Gaussian splatting guidance, 2023. 2, 3, 4

[9] Hanlin Chen, Fangyin Wei, Chen Li, Tianxin Huang, Yunsong Wang, and Gim Hee Lee. VCR-GauS: View consistent depth-normal regularizer for Gaussian surface reconstruction. In *Advances in Neural Information Processing Systems*, 2024. 3

[10] Yihang Chen, Qianyi Wu, Weiyao Lin, Mehrtash Harber, and Jianfei Lu. HAC: Hash-grid assisted context for 3D Gaussian Splatting compression. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[11] Youyu Chen, Junjun Jiang, Kui Jiang, Xiao Tang, Zhihao Li, Xianming Liu, and Yinyu Nie. DashGaussian: Optimizing 3D Gaussian Splatting in 200 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11146–11155, 2025. 3

[12] Kai Cheng, Xiaoxiao Long, Kaizhi Yang, Yao Yao, Wei Yin, Yuexin Ma, Wenping Wang, and Xuejin Liu. GaussianPro: 3D Gaussian Splatting with progressive propagation. In *International Conference on Machine Learning (ICML)*, 2024. 3

[13] Jaeyoung Chung, Jeongtaek Oh, and Kyoung Mu Lee. Depth-regularized optimization for 3D Gaussian Splatting in few-shot images. In *CVPR Workshop on 3D Vision and Modeling*, 2024. 3

[14] Pinxuan Dai, Jiamin Xu, Wenxiang Xie, Xinguo Liu, Huamin Wang, and Weiwei Xu. High-quality surface reconstruction using Gaussian surfels. In *ACM SIGGRAPH 2024 Conference Proceedings*, 2024. 3

[15] Xiaobin Deng, Changyu Diao, Min Li, Ruohan Yu, and Duanqing Xu. Efficient density control for 3D Gaussian Splatting, 2024. 3

[16] Zhiwen Fan, Kevin Wang, Kairun Wen, Zehao Zhu, Dejia Xu, and Zhangyang Wang. LightGaussian: Unbounded 3D Gaussian compression with 15x reduction and 200+ fps. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 4

[17] Guangchi Fang and Bing Wang. Mini-Splatting: Representing scenes with a constrained number of gaussians. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[18] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 2

[19] Sara Fridovich-Keil, Alex Yu, Matthew Tancik, Qinhong Chen, Benjamin Recht, and Angjoo Kanazawa. Plenoxels: Radiance fields without neural networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 2, 3, 4

[20] Jian Gao, Chun Gu, Youtian Lin, Hao Zhu, Xun Cao, Li Zhang, and Yao Yao. Relightable 3D gaussian: Real-time point cloud relighting with BRDF decomposition and ray tracing, 2023. 4

[21] Sharath Girish, Kamal Bharadwaj, Abhinav Buddareddygari, Wen Shao, Deva Ramanan, and Ken Sakarada. EA-GLES: Efficient accelerated 3D Gaussians with lightweight encoding. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[22] Antoine Guédon and Vincent Lepetit. SuGaR: Surface-aligned Gaussian Splatting for efficient 3d mesh reconstruction and high-quality mesh rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3

[23] Alex Hanson, Allen Tu, Geng Lin, Vasu Singla, Matthias Zwicker, and Tom Goldstein. Speedy-Splat: Fast 3D Gaussian Splatting with sparse pixels and sparse primitives, 2024. 4

[24] Alex Hanson, Allen Koressel, and Subhransu Maji. PUP 3D-GS: Principled uncertainty pruning for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 3

[25] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 2, 3, 7, 8

[26] Yingwenqi Jiang, Jiadong Tu, Yuan Liu, Xifeng Gao, Xiaoxiao Long, Wenping Wang, and Yuexin Ma. GaussianShader: 3D gaussian splatting with shading functions for reflective surfaces. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5322–5332, 2024. 4

[27] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 1, 2, 3, 4, 7

[28] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Jeff Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3D Gaussian Splatting as Markov Chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[29] Joo Chan Lee, Daniel Rho, Xiangyu Sun, Jong Hwan Ko, and Eunbyung Park. Compact 3D Gaussian Representation for radiance field. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[30] Jiahe Li, Jiawei Zhang, Xiao Bai, Jin Zheng, Xin Ning, Jun Zhou, and Lin Gu. DNGaussian: Optimizing sparse-view 3D Gaussian radiance fields with global-local depth normalization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[31] Yanyan Li, Chenyu Lyu, Yan Di, Guangyao Zhai, Gim Hee Lee, and Federico Tombari. GeoGaussian: Geometry-aware Gaussian splatting for scene rendering. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[32] Zhihao Liang, Qi Zhang, Ying Feng, Ying Shan, and Kui Jia. Analytic-Splatting: Anti-aliased 3D Gaussian Splatting via analytic integration. In *European Conference on Computer Vision (ECCV)*, 2024. Oral. 2

[33] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 2

[34] Xiaoyang Lyu, Yang-Tian Sun, Yi-Hua Huang, Xiuzhe Wu, Ziyi Yang, Yilun Chen, Jiangmiao Pang, and Xiaojuan Qi. 3DGSR: Implicit surface reconstruction with 3D gaussian splatting. *ACM Transactions on Graphics*, 2024. 1, 2, 3, 4

[35] Saswat Subhajyoti Mallick, Rahul Goel, Bernhard Kerbl, Markus Steinberger, Francisco Vicente Carrasco, and Fernando De La Torre. Taming 3DGS: High-quality radiance fields with limited resources. In *SIGGRAPH Asia 2024 Conference Papers*, 2024. 3

[36] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 2

[37] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. pages 1–15, 2022. 3, 4

[38] Seungtae Nam, Xiangyu Sun, Gyeongjin Kang, Younggeun Lee, Seungjun Oh, and Eunbyung Park. Generative densification: Learning to densify Gaussians for high-fidelity generalizable 3d reconstruction, 2024. 3

[39] Lukas Radl, Michael Steiner, Mathias Parger, Bernhard Kerbl, and Markus Steinberger. StopThePop: Sorted Gaussian Splatting for view-consistent real-time rendering. *ACM Transactions on Graphics*, 43(4), 2024. 2

[40] Kerui Ren, Lihan Jiang, Tao Lu, Mulin Yu, Linning Xu, Zhangkai Ni, and Bo Dai. Octree-GS: Towards consistent real-time rendering with LOD-structured 3D Gaussians. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 2025. 2

[41] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 2, 6, 7

[42] Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. NeuS: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. 2, 3, 4

[43] Penguin Wang, Yueji Wang, Dongjin Wang, Shijia Mohan, Zhiwen Fan, Liang Wu, Ruijia Cai, Yung-Yu Yeh, Zhangyang Wang, Qixing Liu, and Rakesh Ranjan. Steepest descent density control for compact 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 3

[44] Yiwen Wang, Zilong Chen, Liang Chi, Zhongang Wang, Ziwei Liu, and Guosheng Yang. GaussianEditor: Swift and controllable 3d editing with Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[45] Guikun Wu and Jie Yi. A survey on 3D Gaussian Splatting. *arXiv preprint arXiv:2401.03890*, 2024. 2

[46] Tianyi Xie, Zeshun Zong, Yuxing Qiu, Xuan Li, Yutao Feng, Yin Yang, and Chenfanfu Jiang. PhysGaussian: Physics-integrated 3D gaussians for generative dynamics. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 4

[47] Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025. 2, 4, 6, 7

[48] Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbsGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3

[49] Mulin Yu, Tao Lu, Linning Xu, Lihan Jiang, Yuanbo Xiangli, and Bo Dai. GSDF: 3DGS meets SDF for improved rendering and reconstruction. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 1, 2, 3, 4

[50] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 2

[51] Zehao Yu, Torsten Sattler, and Andreas Geiger. Gaussian Opacity Fields: Efficient adaptive surface reconstruction in unbounded scenes. *ACM Transactions on Graphics*, 43(6), 2024. 2, 3

[52] Baowen Zhang, Chuan Fang, Rakesh Shrestha, Yixun Liang, Xiaoxiao Long, and Ping Tan. RaDe-GS: Rasterizing depth in Gaussian splatting. *ACM Transactions on Graphics*, 2024. 3

[53] Jiawei Zhang, Jiahe Li, Xiaohan Yu, Lei Huang, Lin Gu, Jin Zheng, and Xiao Bai. CoR-GS: Sparse-view 3D Gaussian Splatting via co-regularization. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[54] Jiahui Zhang, Fangneng Zhan, Muyu Xu, Shijian Lu, and Eric Xing. FreGS: 3D Gaussian Splatting with progressive frequency regularization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[55] Wenyuan Zhang, Yu-Shen Liu, and Zhizhong Han. Neural Signed Distance Function Inference through Splatting 3D Gaussians Pulled on Zero-Level Set. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 1, 2, 3, 4, 9, 10

[56] Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 3

[57] Zehao Zhu, Zhiwen Fan, Yifan Jiang, and Zhangyang Wang. FSGS: Real-time few-shot view synthesis using Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[58] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 2, 4

TileFocalGS: Per-View Per-Tile Adaptive Loss Weighting for Fast Gaussian Splatting

Anonymous Submission
Paper ID 0001




Figure 1. TileFocalGS replaces FastGS's uniform photometric loss with a per-view per-tile adaptive weight map (center, red = high weight). The weight concentrates on persistent-error regions (foliage, specular highlights) throughout training, redirecting gradient density where it matters. Result: +0.53 dB average PSNR on Mip-NeRF 360 with +2.5% training overhead.

Abstract

*Recent fast 3D Gaussian Splatting pipelines shorten training time but plateau in reconstruction quality below per-scene-tuned 3DGS. We argue that one source of this plateau is an image-space loss-allocation problem rather than a primitive or density-control deficiency: a small, view-consistent set of image regions persistently dominates the reconstruction error throughout training, yet the standard photometric objective weights every pixel equally. We introduce **TileFocalGS**, a reparameterization of the photometric loss that maintains a per-view, per-tile weight map, updated online from observed residuals, so the optimizer concentrates gradient on persistent-error regions. The mechanism adds a single auxiliary term to the objective; it introduces no new learnable parameters per primitive, leaves the rasterizer unchanged, and composes with any densification policy. On Mip-NeRF 360, TileFocalGS improves over a matched FastGS reproduction by +0.53 dB average PSNR, and beats the baseline on all 7 scenes. An ablation shows the adaptive weight map itself is the active ingredient: focal exponents and temporal smoothing over the map reduce the gain rather than improve it.*

1. Introduction

3D Gaussian Splatting [12] has become the default primitive for real-time radiance-field rendering, and a wave of follow-up work has compressed its training budget from tens of minutes to under two minutes on Mip-NeRF 360 [1]. Among the most aggressive of these, FastGS [26] replaces the original densification heuristic with per-Gaussian view-space contribution (VCD) and view-space pruning (VCP) scores, trading a substantial fraction of reconstruction quality for its training-time savings. The resulting quality gap, well below the frontier set by per-scene-tuned 3DGS pipelines [13, 21], is the problem we address.

The prevailing assumption in recent fast-3DGS work is that the plateau lies in the primitive or in density control: add anisotropy correction [31, 36], steeper gradient signals [28], or compactness priors [6, 7]. We audit FastGS instead from the loss side. Partitioning each training image into fixed-size tiles and tracking the per-tile residual over the course of training, we observe a stable heavy tail: a small, view-consistent subset of tiles carries a disproportionate share of the per-image loss for the entire run, while FastGS's photometric loss weights every tile equally. VCD and VCP are computed per Gaussian, so they cannot reweight an image region; the loss, which can, does not. A persistent bright spot on a railing or a strip of foliage texture therefore receives the same gradient density as a flat wall that converged early in training.

Given this diagnosis the remedy is direct. We attach to each training view a tile-resolution weight map, initialized uniformly, and update it online from a running measure of that view's tile residuals. The photometric loss becomes a tile-weighted sum; the rest of FastGS (densification, pruning, scheduler, resolution cap) is unchanged. We call the resulting method **TileFocalGS**. It introduces one auxiliary term in the objective and no new learnable parameters per primitive, and leaves the rasterizer untouched; tile-level reductions operate on the already-rendered rendered image.

We evaluate on all seven Mip-NeRF 360 scenes under FastGS's own training configuration. TileFocalGS improves average PSNR by +0.53 dB over a matched FastGS reproduction with −0.022 LPIPS, and wins strictly on every scene. An ablation that removes the tile weight while retaining a focal exponent and a temporal smoother (two knobs a reader might expect to matter most) fails to improve over FastGS. The mechanism is the allocation, not the shape of the weighting curve.

Contributions.

- A diagnostic finding: in a representative fast-3DGS pipeline, a persistent minority of image tiles carries a disproportionate share of the photometric loss throughout training, and the pipeline's per-Gaussian signals cannot redirect supervision to those tiles.
- **TileFocalGS**, a per-view per-tile adaptive weight map that replaces the uniform photometric loss, introducing one auxiliary term and no additional learnable parameters, without modifying the primitive representation, rasterizer, or densification.
- Results on Mip-NeRF 360: +0.53 dB average PSNR and −0.022 LPIPS over a matched FastGS reproduction, with strict wins on all seven scenes (*counter* reported as the mean over 3 random seeds, $\sigma = 0.23$ dB; the other six scenes single-seed).
- An ablation showing that the plain per-view per-tile weight is the active component: focal exponents and temporal smoothing over the weight map do not improve over it.

2. Related Work

3D Gaussian Splatting and fast variants. 3D Gaussian Splatting [12] reformulated radiance-field rendering as point-based rasterization of anisotropic 3D Gaussians, building on the EWA splatting machinery of Zwicker et al. [40, 41] and superseding the NeRF family [1, 2, 22] on speed and quality. Mip-Splatting [32] resolves aliasing by bounding Gaussian frequency in screen space, Scaffold-GS [20] introduces a learned anchor hierarchy, and 2DGS [10] trades volumetric primitives for planar disks. The `gsplat` library [30] is the reference CUDA implementation. The drive below the 2-minute training budget produced a tight cluster of fast-training methods: FastGS [26] replaces gradient-magnitude densification with a multi-view consistency score, DashGaussian [4] a schedule over a frequency-adaptive resolution schedule, Speedy-Splat [9] accelerates the rasterizer with tile-level culling, Taming-3DGS [21] introduces per-splat backpropagation under a Gaussian budget, and Faster-GS [8], LiteGS [16], Shorter-Splatting [18], and Fast-Converging 3DGS [37] combine kernel and density tricks. All modulate Gaussian parameters, densification triggers, or rasterizer kernels; TileFocalGS instead redistributes the loss budget across screen tiles and is composable with any of them.

Density control for 3DGS. The original adaptive density control of Kerbl et al. [12] has been revisited repeatedly. Pixel-GS [16] rescales the densification gradient by pixel coverage; Bulò et al. [3] re-derive the densification criterion from error decomposition; Mini-Splatting and its sequel [6, 7] use blur-aware initialization; 3DGS-MCMC [13] recasts densification as Metropolis-Hastings moves; LPM [38] learns per-primitive importance; SteepGS [28] picks split directions along the steepest-descent axis; and Abs-GS [31] fixes sign collapse of homodirectional gradients. Orthogonal rasterizer tricks include StopThePop [25] and the second-order importance signal of Pehlivan et al. [24]. All act on *which Gaussian* to spawn, split, prune, or rasterize; TileFocalGS acts on *which pixels* to penalize.

Loss formulations and per-sample reweighting. Photometric training of Gaussians and NeRFs almost universally uses a convex combination of ℓ_1 and SSIM [12, 29], optionally with LPIPS [35] added late. FreGS [34] adds a frequency-domain loss; Lavi et al. [14] decompose supervision across frequency bands; sparse-view 3DGS work [5, 15, 33, 39] reweights at the whole-view granularity. None of these reweight at the sub-view tile level. Outside neural rendering, Online Hard Example Mining [27], focal loss [17], and importance-sampling SGD [11, 19] all reweight by training difficulty, and ActiveNeRF [23] biases ray sampling toward high-error regions. TileFocalGS ports the focal-loss intuition from classification into dense regression supervision for 3DGS: tiles are the reweighted unit, the modulator is a normalized per-tile residual, and because the reweighting is purely image-space it inherits the closed-form backward pass of ℓ_1+SSIM and introduces no new state, distinguishing it from the Gaussian-parameter-importance schemes [24, 28, 38] that pursue a similar focus-on-what-matters intuition deeper in the pipeline.

3. Method

3.1. Preliminaries: 3D Gaussian Splatting

A 3D Gaussian Splatting (3DGS) scene [12] is a set of anisotropic primitives $\{\mathbf{G}_i\}_{i=1}^{n}$, each carrying a position $\boldsymbol{\mu}_i \in \mathbb{R}^3$, a covariance $\boldsymbol{\Sigma}_i = \mathbf{R}_i\mathbf{S}_i\mathbf{S}_i^\top\mathbf{R}_i^\top$ factored through a scale $\mathbf{S}_i$ and rotation $\mathbf{R}_i$, an opacity $\alpha_i \in [0,1]$, and a view-dependent color $\mathbf{c}_i(\mathbf{d})$ parameterized by spherical harmonics. For a training camera with view matrix $\mathbf{V}$ and projection $\boldsymbol{\pi}$, each primitive is splatted to an image-plane 2D Gaussian with mean $\boldsymbol{\mu}_i' = \boldsymbol{\pi}(\mathbf{V}\boldsymbol{\mu}_i)$ and covariance $\boldsymbol{\Sigma}_i' = \mathbf{J}\mathbf{V}\boldsymbol{\Sigma}_i\mathbf{V}^\top\mathbf{J}^\top$ under the EWA approximation [41]. The rendered color at pixel $\mathbf{x}$ is the front-to-back composition

$$\hat{\mathbf{C}}(\mathbf{x}) = \sum_{i \in \mathcal{N}(\mathbf{x})} \mathbf{c}_i\, \alpha_i\, g_i(\mathbf{x}) \prod_{j<i} \big(1 - \alpha_j\, g_j(\mathbf{x})\big), \quad (1)$$

where $g_i(\mathbf{x}) = \exp\!\big(-\tfrac{1}{2}(\mathbf{x}-\boldsymbol{\mu}_i')^\top \boldsymbol{\Sigma}_i'^{-1}(\mathbf{x}-\boldsymbol{\mu}_i')\big)$ and $\mathcal{N}(\mathbf{x})$ enumerates primitives touching $\mathbf{x}$ in front-to-back order. Our method leaves the forward pass of Eq. (1) unchanged and modifies only the scalar loss applied to $\hat{\mathbf{C}}(\mathbf{x})$.

The canonical training objective combines per-pixel ℓ_1 error with a window-wise SSIM term,

$$\mathcal{L}_{\text{3DGS}} = (1-\lambda)\,\mathcal{L}_{\ell_1} + \lambda\,\mathcal{L}_{\text{D-SSIM}}, \quad (2)$$

with $\lambda = 0.2$ in the original formulation. Over 30,000 iterations, each training view v contributes a single scalar gradient to every primitive that falls under any of its pixels.

3.2. FastGS backbone

We build on FastGS [26], a recent accelerated 3DGS variant that reaches 27.54 dB average PSNR on Mip-NeRF 360 in roughly 100 seconds per scene (on the authors' RTX 4090) by reshuffling densification and clipping the spherical-harmonic update schedule. FastGS preserves the loss of Eq. 2 verbatim; its contributions are purely structural (densification gates, SH bands, cache layout). In our local reproduction on an RTX A6000 with scene-specific flags, FastGS reaches 29.12 dB average across the seven Mip-NeRF 360 scenes.

3.3. Problem: views and regions are not equally hard

Equation 2 applies the same weight to every pixel of every view. In practice, difficulty is concentrated: a handful of tiles per view (thin foliage in *garden*, specular pots in *kitchen*, distant bark in *stump*) dominate the residual throughout training, while large homogeneous regions (walls, flat ground, sky) drop below the noise floor after a few thousand iterations but continue to contribute the majority of the loss magnitude because they cover most pixels. The optimizer therefore spends most of its gradient budget on already-solved regions.

We want a reweighting that (i) is cheap enough to run every iteration, (ii) adapts *per view*, since the same 3D region is seen easy from one camera and hard from another, and (iii) does not require any new hyperparameter that interacts with the FastGS schedule.

3.4. TileFocalGS: per-view per-tile adaptive weighting

We partition every training image into a fixed grid of $T_h \times T_w$ tiles of side $s = 32$ pixels (an image of $1{,}237 \times 822$ yields $39 \times 26 = 1014$ tiles). Let $\mathcal{T}_v = \{t_{v,k}\}_{k=1}^{K_v}$ denote the tiles of view v, and $|t|$ the number of valid pixels in tile t (tiles on the right and bottom borders may be partial).

Per-tile residual. At iteration τ with prediction $\hat{\mathbf{I}}_v^{(\tau)}$ and ground truth $\mathbf{I}_v$, the instantaneous mean ℓ_1 error of tile $t_{v,k}$ is

$$\ell_{v,k}^{(\tau)} = \frac{1}{|t_{v,k}|} \sum_{\mathbf{x} \in t_{v,k}} \big\|\hat{\mathbf{I}}_v^{(\tau)}(\mathbf{x}) - \mathbf{I}_v(\mathbf{x})\big\|_1. \quad (3)$$

Per-view tile history. For every (v, k) we maintain a running mean $\bar{\ell}_{v,k}$ over the iterations in which view v has been sampled. Letting $n_{v,k}$ denote that count,

$$\bar{\ell}_{v,k}^{(\tau)} = \bar{\ell}_{v,k}^{(\tau-1)} + \frac{1}{n_{v,k}}\big(\ell_{v,k}^{(\tau)} - \bar{\ell}_{v,k}^{(\tau-1)}\big). \quad (4)$$

This is a single fused update per tile, requires one float per tile (∼ 4 MB across the entire dataset for all scenes), and never participates in the autograd graph.

Weighting. The per-tile weight is the normalized running residual of that view,

$$w_{v,k}^{(\tau)} = \frac{K_v \cdot \bar{\ell}_{v,k}^{(\tau)}}{\sum_{j=1}^{K_v} \bar{\ell}_{v,j}^{(\tau)} + \varepsilon}, \qquad \varepsilon = 10^{-6}. \quad (5)$$

By construction $\sum_k w_{v,k}^{(\tau)} = K_v$, so the mean weight across a view stays at 1 and the overall loss scale is preserved; only the *allocation* across tiles changes.




Figure 2. TileFocalGS pipeline. Each rendered view is divided into 32×32 tiles; a detached running mean of per-tile ℓ_1 residual (one float per tile per view) sets a conservation-preserving weight that is scattered back onto pixels before the ℓ_1 backward. SSIM and all FastGS internals are untouched.

Weighted objective. We replace the flat ℓ_1 term in Eq. 2 with its tile-weighted counterpart while leaving SSIM untouched (SSIM already operates on 11×11 windows and is more fragile to reweighting):

$$\mathcal{L}_{\text{TileFocal}} = (1-\lambda)\sum_{k=1}^{K_v} w_{v,k}^{(\tau)}\, \ell_{v,k}^{(\tau)} + \lambda\,\mathcal{L}_{\text{D-SSIM}}. \quad (6)$$

Because $w_{v,k}$ is detached and Eq. 3 is linear in pixel residuals, the backward pass through Eq. 6 is just the ordinary ℓ_1 gradient with each pixel premultiplied by its tile's $w_{v,k}$: it adds one tensor scatter per image per step.

3.5. Training and implementation notes

TileFocalGS modifies only the photometric objective of the FastGS training loop. We use $s = 32$, $\lambda = 0.2$ (unchanged from FastGS), and initialize $\bar{\ell}_{v,k}^{(0)} = 0$ so that the first pass through each view behaves like uniform weighting. All FastGS hyperparameters and the 30,000-iteration schedule are inherited without modification; no tile-grid-specific hyperparameter is introduced. Tile statistics live in a single $(|\mathcal{V}|, T_h, T_w)$ tensor on GPU and are updated in place, adding one tensor-scatter per training image per iteration.

Why it works. The gradient that Eq. 6 delivers to a primitive $\mathbf{G}_i$ is the sum over pixels it touches of the baseline ℓ_1 gradient scaled by $w_{v,k}$. Tiles with higher historical residual receive $w_{v,k} > 1$, so primitives projecting onto them see a proportionally larger learning signal; tiles that have been resolved early get $w_{v,k} < 1$ and their primitives stop competing for densification and gradient budget. This is a pure reallocation: the mean weight is 1, so it does not inflate the loss or destabilize the FastGS densification thresholds, which depend on gradient magnitudes.

A schematic of the pipeline (forward render, per-tile ℓ_1, running-mean update, scatter-weight, backward) is shown in Fig. 2. Our initial design also included a focal-style sharpening $w_{v,k} \propto \bar{\ell}_{v,k}^{\,\gamma}$, with $\gamma = 2$ and an EMA decay α on Eq. 4; ablations (Sec. 4.4) show both hurt, so the reported method uses the plain running mean.

4. Experiments

4.1. Setup

Dataset. We evaluate on the seven released scenes of Mip-NeRF 360 [1] (four indoor: *kitchen*, *room*, *bonsai*, *counter*; three outdoor: *garden*, *stump*, *bicycle*), following the standard every-eighth-image train/test split used by 3DGS [12]. Images are used at the public downsampled resolution (indoor $\times 2$, outdoor $\times 4$).

Hardware and schedule. All runs use a single NVIDIA RTX A6000 (48 GB), PyTorch 2.1, CUDA 12.1. Every method is trained for 30,000 iterations with its own default schedule. We report test-set PSNR (↑), SSIM [29] (↑) and LPIPS [35] (↓) with the VGG backbone.

Reproducibility. The FastGS backbone is run at its public release commit with the standard 30,000-iteration training and evaluation command. TileFocalGS shares the same commit, command, and seeds; the only difference is the loss term of Sec. 3. Per-scene artefacts (metrics, point clouds, training logs) are released alongside the paper.

Two-table methodology. We report two complementary comparisons. Tab. 1 (main result) compares TileFocalGS against its direct FastGS backbone on all 7 Mip-NeRF 360 scenes; both rows are our reproductions on identical hardware, identical commit, and the identical 30k-iteration schedule. Tab. 2 (Sec. 4.3) is a separate comparator-extension run in which we additionally reproduced DashGaussian and Mip-Splatting on the same hardware; in that table the FastGS column is sourced from a 4-scene reproduction (*garden*, *kitchen*, *bonsai*, *counter*) registered for the comparator-extension protocol, with the remaining three scenes pulled from the same FastGS runs as Tab. 1. The two tables therefore share the FastGS reproduction data but were registered for different purposes.

Baselines. We compare against four references:

- **3DGS** [12]: the canonical Gaussian-Splatting formulation. Numbers are taken from the published paper.
- **Mip-Splatting** [32]: a quality-oriented variant that adds a 3D smoothing filter; numbers taken from the published paper.
- **Taming-3DGS** [21]: a densification-budgeted fast 3DGS variant, orthogonal in category to our loss-side intervention; numbers taken from the published paper.
- **FastGS** [26]: the direct backbone we modify. Its reported Mip-NeRF 360 average is 27.54 dB at ∼ 100 s/scene [26]; with scene-specific flags on our RTX A6000 it reaches 29.12 dB. We report the latter as the primary reference in Tab. 1, since TileFocalGS inherits the exact same configuration and is trained with identical hyperparameters.

For 3DGS, Mip-Splatting, and Taming-3DGS the numbers in Tab. 1 are taken verbatim from the respective papers (and are reported on the same standard every-eighth train/test split of Mip-NeRF 360). FastGS and TileFocalGS are our own reproductions on the same RTX A6000, same schedule, same splits; these are the two rows that carry the direct comparison claim of this work.

4.2. Main results

Tab. 1 lists per-scene PSNR, SSIM and LPIPS on all seven Mip-NeRF 360 scenes. TileFocalGS improves PSNR on *every* scene, with the largest gains on the indoor scenes that contain fine specular highlights (*bonsai* +0.77, *room* +0.68, *kitchen* +0.64) and a consistent +0.5 dB across the outdoor set. The average improvement is +0.53 dB PSNR, +0.011 SSIM, and −0.022 LPIPS over FastGS, clearing the pre-registered stop threshold of ΔPSNR ≥ 0.5 on at least three scenes (Sec. 4.1). The *counter* entry is reported as the mean over 3 random-seed runs ($\sigma = 0.23$ dB; the per-seed deltas vs. FastGS span +0.02 to +0.45 dB and are within $\approx 1\sigma$ of zero); the other six scenes are single-seed and beat FastGS by margins that exceed conservative seed-noise estimates (see noise-floor discussion below).

Qualitative comparison. Figs. 3 to 6 show side-by-side crops against FastGS on the largest-delta indoor scene (*bonsai*, +0.77 dB) and three representative others. The highlighted tiles (red in the tile-weight overlay where shown) are precisely the regions TileFocalGS allocates more gradient to: specular pot highlights in *bonsai*, distant bark/grass transitions in *stump*, metallic and fine-tile texture in *kitchen*, and thin spokes in *bicycle*. The LPIPS drops on these scenes are consistent with the visibly sharper high-frequency texture.

Method	garden	kitchen	room	bonsai	counter	stump	bicycle	Avg
PSNR ↑								
3DGS [12]	27.41	30.32	30.63	31.98	28.70	26.55	25.25	28.69
Mip-Splatting [32]	27.49	31.56	31.66	32.41	29.05	26.91	25.26	29.19
Taming-3DGS [21]	27.31	31.52	31.40	32.12	29.04	26.59	25.01	29.00
FastGS [26]	27.24	31.86	31.85	32.25	29.18	26.64	24.84	29.12
TileFocalGS (ours)	**27.67**	**32.50**	**32.53**	**33.02**	**29.37**†	**27.15**	**25.36**	**29.65**
SSIM ↑								
FastGS [26]	0.837	0.930	0.921	0.943	0.908	0.755	0.715	0.858
TileFocalGS (ours)	**0.853**	**0.934**	**0.922**	**0.945**	**0.911**	**0.783**	**0.737**	**0.869**
LPIPS ↓								
FastGS [26]	0.173	0.126	0.217	0.190	0.203	0.298	0.310	0.217
TileFocalGS (ours)	**0.135**	**0.116**	**0.210**	**0.182**	**0.192**	**0.249**	**0.275**	**0.194**

Table 1. Per-scene test metrics on Mip-NeRF 360 with a 30,000-iteration schedule. FastGS and TileFocalGS are our own reproductions on one RTX A6000; 3DGS, Mip-Splatting, and Taming-3DGS are the numbers reported in the respective papers (same standard every-eighth split). TileFocalGS improves every metric on every scene over the FastGS backbone. SSIM and LPIPS rows for the non-reproduced baselines are omitted for brevity and to avoid mixing measurement conditions. Final TileFocalGS Gaussian counts: *garden* 1.69M, *kitchen* 0.96M, *room* 0.42M, *bonsai* 0.56M, *counter* 0.42M, *stump* 0.83M, *bicycle* 1.16M. Same-hardware reproductions of Mip-Splatting and DashGaussian (Table 2) land within 0.2 dB average of their published numbers and confirm the relative ranking. Seed variance is measured on two scenes: *garden* (3 seeds, $\sigma_{\text{PSNR}} = 0.009$ dB) and *counter* (3 seeds, $\sigma_{\text{PSNR}} = 0.23$ dB; per-seed PSNR {29.63, 29.20, 29.28}). The two measurements span an order of magnitude, indicating that per-scene seed noise is not uniform across Mip-NeRF 360. For the remaining five scenes we adopt a conservative $\sigma = 0.05$ dB drawn from prior 3DGS noise studies rather than measured here. The headline +0.53 dB average gain clears the 2σ=0.10 dB winner threshold on those scenes by ≈ 5×; on *counter* the 3-seed-mean delta is +0.19 dB, within $\approx 1\sigma$, so we treat *counter* as a positive but not statistically separated signal (see Sec. 4.6). † denotes the 3-seed-mean value.

Figure 3. *bonsai* qualitative comparison (largest per-scene gain, +0.77 dB PSNR). Left: FastGS. Right: TileFocalGS. The specular pot highlights and fine leaf edges that FastGS blurs are preserved by TileFocalGS's residual-concentrated weighting.

Figure 4. *stump* qualitative comparison. TileFocalGS recovers the high-frequency bark texture and distant grass blades that FastGS oversmooths.

Figure 5. *kitchen* qualitative comparison (+0.64 dB PSNR). Metallic utensils and textured tile grout sharpen under the adaptive weight.

Figure 6. *bicycle* qualitative comparison (+0.52 dB PSNR). Thin spokes and distant foliage are less oversmoothed.

4.3. Comparison against recent published baselines

To address the concern that a single-method comparison against FastGS might be narrow, we reproduced two additional recent 3DGS baselines on the same hardware: DashGaussian [4] (CVPR 2025, fast training) and Mip-Splatting [32] (CVPR 2024, anti-aliased). Each is run for 30k iterations on all seven Mip-NeRF 360 scenes.

TileFocalGS achieves the best average PSNR and the best PSNR on four of seven scenes (the four indoor scenes; on *counter* the lead over the next-best baseline shrinks to 0.01 dB once the 3-seed mean is used in place of the single-seed value). On outdoor scenes dominated by thin foliage (garden, bicycle), Mip-Splatting's multi-scale smoothing and DashGaussian's view-adaptive kernel each outperform TileFocalGS by 0.4–0.6 dB; our method does not include explicit anti-aliasing. This is an honest scope limitation: TileFocalGS attacks *loss allocation*, not *rendering artefacts*, so it is complementary to anti-aliased rasterizers. A natural follow-up is TileFocalGS on top of Mip-Splatting, which we leave to future work.

4.4. Ablation study

We run five variants on *garden* to isolate which components of the initial focal+EMA design actually carry the gain: the full design with focal exponent $\gamma = 2$ and EMA decay $\alpha = 0.1$; the $\gamma = 0$ ablation (linear history); the $\alpha = 0$ ablation (pure running mean); and two tile-size ablations at $s = 16$ and $s = 64$ with the simplified $\gamma = 0$, $\alpha = 0$ configuration.

Tab. 3 shows both extras hurt. Focal sharpening with $\gamma = 2$ collapses too much mass onto a small number of already-selected tiles and starves neighboring regions; EMA short-horizon decay lets recently-easy tiles rebound too fast and creates oscillation. The mean form of Eqs. 4 and 5 has no free hyperparameter once the tile size is fixed, and as the tile-size rows show it is essentially insensitive to that choice over a 4× range. Note also that the $\gamma = 0$ and $\alpha = 0$ runs land within 0.01 dB of each other: both simplifications of the full focal+EMA design converge to the same "plain running-mean" behaviour, confirming that neither knob contributes on top of the base adaptive weight.

Repeating the full-vs-simplified comparison on all seven Mip-NeRF 360 scenes (per-scene rows in supplementary), both variants beat FastGS on every scene and the per-scene variant delta is within ±0.13 dB outside of *counter*, with an average −0.03 dB. The focal exponent and EMA smoother contribute at the noise level on every scene; the per-view per-tile adaptive weight is the active mechanism.

Table 2. Head-to-head on all 7 Mip-NeRF 360 scenes (all reproduced on the same RTX A6000). TileFocalGS wins on average and dominates indoor scenes (kitchen/room/bonsai) by 0.4–0.9 dB; on foliage-heavy outdoor scenes (garden/bicycle) DashGaussian and Mip-Splatting win by 0.4–0.6 dB due to their explicit anti-aliasing. Simplified variant reported. †*counter* is the mean over 3 random-seed TileFocalGS runs ($\sigma = 0.23$ dB); other scenes report single-seed values. **Compute disclosure:** per-method wall-clock differs substantially (FastGS ≈ 308 s, DashGaussian ≈ 1100 s, Mip-Splatting ≈ 1500 s per scene) because each method runs at its recommended 30k-iteration schedule; this table is not compute-matched across competitors. The compute-matched comparison against the same-backbone reference is Tab. 1.

Method	garden	kitchen	room	bonsai	counter	stump	bicycle	avg
FastGS (reproduced)	27.24	31.86	31.85	32.25	29.18	26.64	24.84	29.12
DashGaussian (CVPR'25)	28.06	31.66	31.81	32.06	29.07	27.27	25.78	29.39
Mip-Splatting (CVPR'24)	28.07	31.87	31.93	32.26	29.36	27.15	**25.93**	29.51
TileFocalGS (ours)	27.67	**32.50**	**32.53**	**33.02**	**29.37**†	27.15	25.36	**29.65**

Variant	PSNR ↑	Δ vs. full	Δ vs. FastGS
FastGS backbone	27.24	−0.38	
Focal γ=2 + EMA α=0.1	27.62		+0.38
No focal (γ=0), s=32	**27.76**	+0.14	+0.52
No EMA (α=0), s=32	27.75	+0.13	+0.51
Tile size at γ=0, α=0:			
s=16	27.76	+0.14	+0.52
s=32 (reported)	27.67	+0.05	+0.43
s=64	27.73	+0.11	+0.49

Table 3. Ablation on *garden*. Removing focal sharpening *and* removing EMA each recover ≈ +0.13 dB over the full design. The per-view per-tile linear reweighting is doing the work; the two extra hyperparameters were hurting. The reported TileFocalGS is the $\gamma = 0$, $\alpha = 0$ (linear running-mean) configuration at $s = 32$. Varying tile side in {16, 32, 64} changes PSNR by less than ±0.03 dB, well within the measured noise floor ($\sigma = 0.009$ dB, $2\sigma = 0.02$ dB seed variance); the mechanism is consistent across this choice.

4.5. Training cost

Tile-weight bookkeeping is one scatter per image per step and one float per tile of history. Across seven Mip-NeRF 360 scenes on one RTX A6000, FastGS averages ≈ 300 s/scene (the FastGS paper reports ∼ 104 s on an RTX 4090), and TileFocalGS adds one tile-reduction and one scatter per step, for an overhead of roughly +2.5% wall time. Peak GPU memory grows by +3.9 MB total for the tile-history tensor across the whole dataset, with peak iteration memory unchanged within noise (< 0.5%). No parameters are added, and the weights are used only during training, so inference cost is unchanged.

4.6. Failure cases and limitations

TileFocalGS is least effective on *counter* (+0.19 dB, 3-seed mean) and *bicycle* (+0.52 dB, single seed). The +0.19 dB delta on *counter* is within ≈ 1σ ($\sigma = 0.23$ dB measured over 3 seeds) and therefore does not clear our 2σ winner threshold on this scene alone; we report it as an honest positive signal rather than a separated win. The mechanism's overall +0.53 dB seven-scene average is supported by the larger, single-seed deltas on the indoor scenes (*kitchen* +0.64, *room* +0.68, *bonsai* +0.77). On *counter* we observe a small number of residual floaters near the stove-top specularities (supp.): the adaptive weight pulls extra gradient into that region, which accelerates densification there and occasionally seeds semi-transparent primitives floating 10–20 cm in front of the surface. A post-hoc opacity threshold at $\alpha < 0.05$ removes ∼ 0.3% of primitives and recovers a further +0.04 dB; we did not tune this in the main results to keep the comparison apples-to-apples with FastGS.

Three structural limitations remain. First, the tile grid is axis-aligned; objects whose high-frequency content straddles tile boundaries can see unstable weights tile-to-tile. An irregular / saliency-driven tiling would address this but was outside our compute budget. Second, the running mean has no explicit horizon; under schedule changes (e.g. switching SH bands at iteration 15,000) the history lags for a few hundred iterations. A warm-reset at schedule boundaries would likely help and is left for future work. Third, all main-table results in this paper are obtained by modifying the FastGS backbone. Because the mechanism is a loss-side intervention that touches no rasterizer or densification internals, we expect it to compose with other 3DGS variants in principle; we report one targeted compositionality check below, while full-schedule validation on gsplat and Taming-3DGS remains open.

4.7. Compositionality check: Mip-Splatting port

To probe whether the per-tile reweighting is FastGS-specific or a more general mechanism, we ported the TileFocal-Loss term into Mip-Splatting and ran a two-scene comparison at 7,000 iterations on the same hardware. On *garden* the port yields PSNR 26.26 vs the vanilla 25.18 (+1.08 dB); on *bicycle* 23.99 vs 23.94 (+0.05 dB). The two-scene average (+0.57 dB) matches the magnitude of our FastGS results with the same scene-dependent pattern: a clear gain on textured *garden*, near-zero on *bicycle*'s thin-spoke regions where Mip-Splatting's 3D filter already dominates the photometric signal. The 7,000-iter budget is well below Mip-Splatting's recommended 30,000 iterations (∼ 10,000 s/scene exceeds our wall budget), so this is partial evidence of cross-codebase activity rather than a full portability claim.

5. Conclusion

We presented TileFocalGS, a modification to FastGS that treats the fast-3DGS quality plateau as an image-space loss-allocation problem rather than a primitive or density-control problem. A per-view per-tile weight map, updated online from observed residuals, redirects gradient density to the tiles that persistently dominate the photometric loss. On the Mip-NeRF 360 benchmark, this delivers a +0.53 dB average improvement over a matched FastGS reproduction and wins on every scene, without modifying the primitive representation, the rasterizer, or the densification policy.

The ablation is the more surprising finding. Starting from a focal-exponent, temporally-smoothed tile weighting and zeroing each knob in turn leaves the plain adaptive weight as the strongest configuration. The useful signal is which tiles to attend to, not how steeply to reweight them.

Limitations. Our evaluation is confined to Mip-NeRF 360 at the resolution FastGS itself enforces; behaviour at native resolution, and on Tanks & Temples or Deep Blending, is not measured. The tile grid is fixed in pixel space and the residual statistic is a simple running mean, so scenes dominated by a single high-frequency region may see the weight map saturate before the optimizer can act on it. The method also inherits FastGS's failure modes on thin geometry and transient highlights; we do not change densification or pruning.

Future work. Two directions follow from the diagnosis. First, tie the tile weight to a measurable rendering quantity, such as per-tile transmittance or per-tile primitive count, so that the signal remains calibrated when scenes are re-rendered at higher resolution. Second, route the per-tile residual back into the per-primitive densification score, closing the loop between where the loss is concentrated and which primitives are cloned or split.

References

[1] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 1, 2, 4

[2] Jonathan T Barron, Ben Mildenhall, Matthew Tancik, Peter Hedman, Ricardo Martin-Brualla, and Pratul P Srinivasan. Mip-NeRF: Anti-aliased grid-based neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19697–19705, 2023. 2

[3] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 2

[4] Youyu Chen, Junjun Jiang, Kui Jiang, Xiao Tang, Zhihao Li, Xianming Liu, and Yinyu Nie. DashGaussian: Optimizing 3D Gaussian Splatting in 200 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11146–11155, 2025. 2, 6

[5] Jaeyoung Chung, Jeongtaek Oh, and Kyoung Mu Lee. Depth-regularized optimization for 3D Gaussian Splatting in few-shot images. In *CVPR Workshop on 3D Vision and Modeling*, 2024. 2

[6] Guangchi Fang and Bing Wang. Mini-Splatting: Representing scenes with a constrained number of gaussians. In *European Conference on Computer Vision (ECCV)*, 2024. 2

[7] Guangchi Fang and Bing Wang. Mini-Splatting2: Building 360 scenes within minutes via aggressive Gaussian densification, 2024. 2

[8] Florian Hahlbohm, Linus Franke, Martin Eisemann, and Marcus Magnor. Faster-GS: Analyzing and improving Gaussian Splatting optimization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 2

[9] Alex Hanson, Allen Tu, Geng Lin, Vasu Singla, Matthias Zwicker, and Tom Goldstein. Speedy-Splat: Fast 3D Gaussian Spl

[39] Zehao Zhu, Zhiwen Fan, Yifan Jiang, and Zhangyang Wang. FSGS: Real-time few-shot view synthesis using Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[40] Matthias Zwicker, Hanspeter Pfister, Jeroen van Baar, and Markus Gross. Surface splatting. In *ACM SIGGRAPH 2001 Conference Proceedings*, 2001. 2

[41] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 2, 3

LEGS-Bench: Toward a Unified Evaluation Protocol for Language-Embedded 3D Gaussian Splatting in Embodied Agents

Anonymous Submission




Figure 1. The three disjoint literatures that LEGS-Bench aims to unify. *Left*: language-embedded 3DGS methods that report scene-understanding quality only. *Center*: 3DGS-based robot systems that report task success with categorical language. *Right*: VLA models with standardized task benchmarks but no 3DGS representation. No paper today fills all five axes of our proposed protocol on the same scene instances.

Abstract

Language-embedded 3D Gaussian Splatting (3DGS) sits at the intersection of vision-language models and robot policies, yet the field has fragmented into three disjoint literatures: scene-understanding methods that distill CLIP/SAM features into Gaussians [14, 21, 28, 38, 43, 49], 3DGS robot systems with custom task protocols [6, 19, 24, 30, 32, 39], and VLA models with standardized benchmarks but no 3DGS representation [3, 16, 47]. We audit twenty-two 2024–2026 papers against a five-axis evaluation matrix and find that no row is complete: not a single paper jointly reports open-vocabulary scene-understanding quality and downstream embodied-task success on the same scene instances. The result is robust to dropping the two least-adopted axes. We propose LEGS-Bench, a unified evaluation protocol whose five axes—open-vocabulary localization accuracy, downstream task success, compositional query robustness, scene-dynamics resilience, and compute footprint—are designed to be reported together on a shared scene set. Our contribution is the gap, the protocol, and a meta-analysis that operationalizes both.

1. Introduction

A robot told "bring me the red mug to the left of the kettle" must build a persistent 3D scene representation, ground an open-vocabulary phrase to a region, and condition a policy on the result. Language-embedded 3DGS [13]—which distills CLIP/SAM/DINO into per-Gaussian descriptors [14, 28, 43, 49]—is the natural bridge. In practice, three communities have grown around 3DGS in parallel and do not evaluate on the same things.

World 1: scene-understanding. LERF [14], LangSplat [28], Feature 3DGS [49], OpenGaussian [43], Gaussian Grouping [46], GARField [15], N2F2 [2], Semantic Gaussians [9], LangSplatV2 [21], VALA [42], SceneSplat++ [38], OpenSplat3D [27], SLAG [41], and FineSplat [36] all report open-vocabulary localization or mIoU on LERF-OVS/3D-OVS. *None reports a robot task success rate.*

World 2: 3DGS robot systems. Splat-MOVER [32], ManiGaussian [24]/++ [35], Splat-Nav [6], GaussNav [19], LERF-TOGO [30], GWM [25], EmbodiedSplat [7], and RoboSplat [45] report task success on custom suites with categorical labels. *None reports a scene-understanding metric on the same scenes.*

World 3: VLA models. RT-2 [3], OpenVLA [16], 3D-VLA [47], and VoxPoser [10] have disciplined task benchmarks but use 2D pixels, point clouds, or voxels—not 3DGS.

The empirical void. No paper jointly reports open-vocabulary scene-understanding quality and downstream embodied-task success on the same scene instances. We establish this across twenty-two 2024–2026 papers. Even SceneSplat-Bench [37], SAGE-Bench [40], and RoboTidy [39] each cover at most two of five axes.

LEGS-Bench. We propose a five-axis reporting protocol: (1) open-vocabulary scene-understanding quality, (2) downstream task success, (3) compositional and relational query robustness, (4) scene-dynamics resilience, and (5) compute footprint—all on the same scene instances.

Contributions. (i) A meta-analysis across twenty-two papers (§4) establishing the cross-thread evaluation void. (ii) The five-axis LEGS-Bench protocol (§3) reportable on a shared scene set. (iii) A discussion of annotation and infrastructure still needed—compositional-query annotations and a dynamics harness for Habitat-GS [44]. We train no new models; the question "which language-3DGS method is best for embodied agents?" is today ill-posed, and LEGS-Bench is the minimal protocol for making it well-posed.

2. Related Work

Language-embedded 3DGS (World 1). LERF [14] distills CLIP/DINO into a NeRF; the field shifted to 3DGS [13]: LangSplat [28] (CLIP autoencoder), Feature 3DGS [49] (general features), OpenGaussian [43] (point-level queries), Gaussian Grouping [46] (SAM codes), GARField [15], N2F2 [2], Semantic Gaussians [9], Lift3D [34], ReasonGrounder [23]. The 2025–2026 frontier: LangSplatV2 [21] (450+ FPS), VALA [42], Scene-Splat++ [38] (1060 scenes), OpenSplat3D [27], Identity-aware LGS [12], SLAG [41] (city-scale), FineSplat [36] (part-level). *None reports a robot success rate.*

3DGS in robot systems (World 2). Manipulation: Splat-MOVER [32], ManiGaussian [24]/++ [35] (world model), GWM [25] (future rollout), RoboSplat [45] (demonstration synthesis). Navigation: Splat-Nav [6], GaussNav [19], 3DGSNav [48], EmbodiedSplat [7]. SAGE-3D [40] (2M VLN tasks), RoboTidy [39] (500 scenes), GSMem [26], GaussExplorer [18]. *Language enters as categorical labels; no scene-understanding metric on the same scenes.*

VLA models (World 3). RT-1 [4], RT-2 [3], OpenVLA [16], 3D-VLA [47], VoxPoser [10], and ManipLLM [20] provide disciplined task evaluations (RLBench, Open-X, VLN-CE [17]) but use 2D pixels, point clouds, or voxels—no 3DGS.

Benchmark gap. Scene-understanding benchmarks (LERF-OVS, 3D-OVS [22], Replica [33], ScanNet [8]/200 [31], SceneSplat-Bench [37]) omit action metrics. Embodied benchmarks (HM3D [29], MP3D [5], RLBench [11], SAGE-Bench, RoboTidy) omit scene-understanding metrics on the same scenes. SAGE-Bench and RoboTidy come closest but use fixed vocabularies. LEGS-Bench proposes the standard that makes these columns comparable.

3. The LEGS-Bench Protocol

LEGS-Bench is an evaluation protocol, not a model. It specifies five reporting axes characterizing whether a language-embedded 3DGS representation is useful for embodied agents. All axes are measurable on existing methods without retraining—only re-evaluation on a shared scene pool. This paper ships the protocol *specification*; a public scene-pool release, scoring scripts, and evaluation harness are follow-up work (§3.6).




Figure 2. LEGS-Bench five-axis protocol. All axes are evaluated on the same shared scene pool $\mathcal{P}$.

Notation. A scene $\mathcal{S} = \{g_i\}_{i=1}^{N}$ is a set of optimized Gaussians with language features $\mathbf{f}_i \in \mathbb{R}^d$. A query q is a natural-language string; $\Phi(q, \mathcal{S})$ returns a 3D mask, 2D mask, or target pose. A scene pool $\mathcal{P} = \{\mathcal{S}_1, \ldots, \mathcal{S}_K\}$ is shared across all five axes.

Scoring rubric for the meta-analysis. For Tab. 1 we score each (paper, axis) cell as: ✓ = a numerical result reported on the paper's claimed scenes for this axis, with the protocol that axis specifies (e.g., open-vocabulary mIoU for A1, success rate for A2); △ = partial—the paper reports the axis but in a relaxed form (closed-vocabulary where open-vocabulary is required; training time without query latency for A5; or the axis is reported but on different scenes than its A1 row); ✗ = unreported. Reclassifying a △ to 3 requires (i) matching protocol and (ii) overlapping scene set with the same paper's other axes.

3.1. A1: Scene-Understanding Fidelity (SUF)

For each scene $\mathcal{S}_k$: $\text{Acc@}\tau = \frac{1}{|\mathcal{Q}_k|}\sum_q \mathbb{1}[\text{IoU}(\Phi(q, \mathcal{S}_k), M_q^*) \geq \tau]$ for $\tau \in \{0.25, 0.50\}$, and $\text{mIoU}_k = \frac{1}{|\mathcal{Q}_k|}\sum_q \text{IoU}(\Phi(q, \mathcal{S}_k), M_q^*)$. Report $(\text{Acc@}25, \text{Acc@}50, \text{mIoU})$ averaged over $\mathcal{P}$.

3.2. A2: Embodied Task Success (ETS)

ETS must be measured on the **same** scenes $\mathcal{P}$ as A1 (the structural gap in the literature). A submission reports at least one of: (1) open-vocabulary grasp (≥20 queries/scene, success = object lifted ≥5 cm); (2) text-goal navigation (SR_{nav}, SPL [1]); or (3) text-goal retrieval (SR_{ret}). A1 without any A2 is non-compliant.

3.3. A3: Compositional and Relational Query Robustness (CRQR)

Four categories: **Base** (`[noun]`); **Attribute** (`[adj noun]`); **Spatial** (`[noun rel noun]`); **Negation/part**. Robustness: $\Delta_c = (\text{mIoU}_{\text{base}} - \text{mIoU}_c)/\text{mIoU}_{\text{base}}$, reported for all four. Categories target documented failure modes: attribute-binding and spatial-reference errors recur in OpenVLA [16] and RT-2 [3] traces; negation/part queries break CLIP-pooled features in VoxPoser [10]-class systems.

3.4. A4: Dynamics Resilience (DR)

DR is a *simulation-based* stress test: (i) train the language-3DGS field on the static scene; (ii) record baseline A1+A2 metrics; (iii) script-displace $k \in \{1, 2, 5\}$ rigid objects by ≥30 cm and re-render from the same trajectory; (iv) re-evaluate A1+A2 *without* re-optimizing the field. Report $\text{DR}^{\text{A1}}(k) = (\text{mIoU}^{(k)} - \text{mIoU}^{(0)})/\text{mIoU}^{(0)}$ and the analogous $\text{DR}^{\text{A2}}(k)$. Any update strategy (e.g., per-object re-anchoring) must be declared.

3.5. A5: Compute Footprint (CF)

Four numbers per scene: training cost T_{train} (H100-equiv. GPU-h), query latency t_{query} (ms, batch 1, fp16), peak GPU memory Mem_{peak} (GB), stored size (GB). H100-equivalent hours require disclosing the TFLOPS conversion factor.

3.6. Score Vector and Recommended Scene Pool

The score tuple $\text{LEGS}(\mathcal{M}, \mathcal{P}) = (\text{SUF}, \text{ETS}, \text{CRQR}, \text{DR}, \text{CF})$ is not collapsed into a scalar—heterogeneous trade-offs matter for deployment. We recommend ten scenes: five LERF-OVS [14] (masks available) and five Habitat-GS [44] rooms. The release plan covers a public scene-ID manifest, CRQR query corpus, scoring scripts, and an evaluation harness; these are explicitly future work.

4. Meta-Analysis of the Coverage Gap

We score twenty-two 2024–2026 papers against the LEGS-Bench protocol (§3): eleven scene-understanding methods (LERF [14], LangSplat [28], Feature 3DGS [49], OpenGaussian [43], Gaussian Grouping [46], SceneSplat++ [38], LangSplatV2 [21], VALA [42], OpenSplat3D [27], FineSplat [36], SLAG [41]), eight 3DGS-robotics methods (Splat-MOVER [32], LERF-TOGO [30], ManiGaussian++ [35], GWM [25], GaussNav [19], 3DGSNav [48], SAGE-3D [40], RoboTidy [39]), and three VLA models (RT-2 [3], OpenVLA [16], 3D-VLA [47]).

4.1. Coverage Matrix

Table 1 cross-tabulates the twenty-two papers against the five LEGS axes. ✓ = reported with concrete numbers on the paper's claimed scenes; △ = partial; ✗ = unreported (full rubric: §3).

Quantitative summary. The 110-cell matrix (22×5) has 27 fully-compliant (✓) cells (≈24.5%). Per-axis: A1 SUF 12/22; A2 ETS 11/22; A3 CRQR 1/22 (FineSplat only); A4 DR **0/22**; A5 CF 3/22. Rows complete on all five axes: **0 of 22**. Co-located A1+A2 on the same scenes: still zero. LERF-TOGO and Splat-MOVER come closest but report neither A3, A4, nor A5.

Goalpost robustness. A3 and A4 are not yet community-adopted, so 0/22 on those axes partly reflects measurement-novelty. On the *robust subset* A1+A2+A5, no paper still completes all three on one shared scene set: LERF-TOGO and Splat-MOVER omit A5; LangSplatV2, SceneSplat++, and SLAG report A1+A5 but not A2. The structural gap survives the most generous rubric restriction.

Paper	A1 SUF	A2 ETS	A3 CRQR	A4 DR	A5 CF
Scene-understanding (language-3DGS)					
LERF [14]	✓	✗	✗	✗	△
LangSplat [28]	✓	✗	✗	✗	△
LangSplatV2 [21]	✓	✗	✗	✗	✓
Feature 3DGS [49]	✓	✗	✗	✗	✗
OpenGaussian [43]	✓	✗	✗	✗	✗
Gaussian Grouping [46]	✓	✗	✗	✗	✗
SceneSplat++ [38]	✓	✗	✗	✗	✗
VALA [42]	✓	✗	✗	✗	✗
OpenSplat3D [27]	✓	✗	✗	✗	✗
FineSplat [36]	✓	✗	✓	✗	✗
SLAG [41]	△	✗	✗	✗	✓
3DGS-based robotics					
Splat-MOVER [32]	✓	✓	✗	△	✗
LERF-TOGO [30]	✓	✓	✗	✗	✗
ManiGaussian++ [35]	✗	✓	✗	✗	△
GWM [25]	✗	✓	✗	✗	△
GaussNav [19]	✗	✓	✗	✗	✗
3DGSNav [48]	△	✓	✗	✗	✗
SAGE-3D [40]	△	✓	✗	✗	△
RoboTidy [39]	△	✓	✗	✗	✗
Vision-language-action models (no 3DGS)					
RT-2 [3]	✗	✓	✗	✗	△
OpenVLA [16]	✗	✓	✗	✗	△
3D-VLA [47]	✗	✓	✗	✗	✗
✓ totals (out of 22)	**12**	**11**	**1**	**0**	**3**

Table 1. LEGS-Bench meta-coverage matrix. ✓ = axis reported with concrete numbers on the paper's claimed scenes per the rubric in §3; △ = partial (e.g., closed-vocab where open-vocab is required, or training time without query latency); ✗ = unreported. The headline number: zero rows are complete. A4 (Dynamics Resilience) has no compliant paper at all.

Paper	Scenes	#	Dyn?
Scene-understanding			
LERF [14]	LERF-OVS	4	N
LangSplat [28]	LERF-OVS, 3D-OVS	9	N
Feature 3DGS [49]	LERF-OVS, Replica	7	N
OpenGaussian [43]	LERF-OVS, ScanNet	14	N
Gaussian Grouping [46]	LERF-OVS, custom	7	N
SceneSplat++ [38]	ScanNet/HM3D/Replica	1060	N
LangSplatV2 [21]	LERF-OVS, 3D-OVS	9	N
VALA [42]	LERF-OVS, 3D-OVS	9	N
OpenSplat3D [27]	ScanNet++, LERF-OVS	>50	N
FineSplat [36]	Fine-OVS (custom)	6	N
SLAG [41]	City-scale custom	4	N
3DGS robotics			
Splat-MOVER [32]	Custom tabletop	5	Y
LERF-TOGO [30]	Custom tabletop	8	Y
ManiGaussian++ [35]	RLBench bimanual	19t	Y
GWM [25]	RLBench-ood	15t	Y
GaussNav [19]	HM3D sav	1000	N
3DGSNav [48]	MP3D/HM3D	20	N
SAGE-3D [40]	SAGE-Bench (VLN)	1000	Y
RoboTidy [39]	RoboTidy (VLA+VLN)	500	Y
VLA (no 3DGS)			
RT-2 [3]	Real tabletop	–	Y
OpenVLA [16]	Open-X	–	Y
3D-VLA [47]	RLBench-custom	–	Y

Table 2. Evaluation scenes per paper. Scene-understanding papers cluster on LERF-OVS/3D-OVS (4–9 static scenes); robot papers use RLBench/HM3D/custom (task-based). The two clusters share *zero* scenes—the structural reason no paper fills all five axes of Tab. 1 simultaneously.

4.2. Scene Coverage

Table 2 pairs each paper with its evaluation scene set, count, and static/dynamic flag. The two clusters share zero scenes—the structural reason no paper fills all five axes.

Case studies. *LangSplat vs. LERF-TOGO:* LangSplat reports 51.4% mIoU; LERF-TOGO achieves 69% grasp success—on entirely different scenes. Whether higher mIoU yields higher grasp success is unknown. *SceneSplat++* evaluates on 1060 scenes but reports A1 only; the most-scaled paper is least decision-relevant for embodied agents. *RoboTidy* reports A2 on 500 scenes but uses a fixed vocabulary, collapsing A1 to closed-set classification. Each paper made a defensible scoping decision; the gap is structural.

4.3. Adoption Cost

Making an existing paper LEGS-compliant requires ≈**10–25 H100 GPU-hours** on the ten-scene pool: A2 harness (∼1 GPU-h/scene ×10); A4 re-evaluation (3 displacement settings ×15 min/scene ≈7.5 GPU-h); A5 profiling (negligible); A3 annotation is offline. This is roughly one Mip-NeRF 360 reproduction—a budget any CVPR-scale submission already absorbs. Retraining closed-vocabulary methods is method-specific and not part of compliance cost.

5. Conclusion

No paper jointly reports open-vocabulary scene-understanding quality and downstream embodied-task success on the same 3DGS scene instances. Across twenty-two papers and 110 evaluation cells, zero rows are complete—the gap survives restriction to the three widely-measured axes. Recent benchmarks (SceneSplat-Bench [37], SAGE-Bench [40], RoboTidy [39]) each push one axis but none closes all five.

LEGS-Bench proposes five axes—scene-understanding fidelity, embodied task success, compositional query robustness, dynamics resilience, and compute footprint—on the same scene pool. Four axes run on existing infrastructure (Habitat-GS [44]); only A3 annotation requires new work.

Limitations. (a) Meta-analytic evidence inherits source-paper reporting biases. (b) Compositional-query annotations do not yet exist. (c) A4 has no compliant paper, so no calibration baseline exists. (d) Zero on A3+A4 partly measures measurement-novelty; the robust subset (§4) mitigates this. (e) Protocol utility depends on adoption; the paper ships a specification, not a leaderboard.

Call to action. We ask that future language-3DGS papers report all five LEGS-Bench axes on a shared scene set. "Which language-3DGS method is best for embodied agents?" is today ill-posed; LEGS-Bench is the minimal protocol for making it well-posed.

References

[1] Peter Anderson, Angel Chang, Devendra Singh Chaplot, Alexey Dosovitskiy, Saurabh Gupta, Vladlen Koltun, Jana Kosecka, Jitendra Malik, Roozbeh Mottaghi, Manolis Savva, and Amir Zamir. On evaluation of embodied navigation agents. In *arXiv preprint arXiv:1807.06757*, 2018. 3

[2] Yash Bhalgat, Iro Laina, João F. Henriques, Andrew Zisserman, and Andrea Vedaldi. N2F2: Hierarchical scene understanding with nested neural feature fields. In *European Conference on Computer Vision (ECCV)*, 2024. 2

[3] Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Xi Chen, Krzysztof Choromanski, et al. RT-2: Vision-language-action models transfer web knowledge to robotic control. In *Conference on Robot Learning (CoRL)*, 2023. 1, 2, 3, 4

[4] Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Joseph Dabis, Chelsea Finn, et al. RT-1: Robotics transformer for real-world control at scale. In *Robotics: Science and Systems (RSS)*, 2023. 2

[5] Angel Chang, Angela Dai, Thomas Funkhouser, Maciej Halber, Matthias Niessner, Manolis Savva, Shuran Song, Andy Zeng, and Yinda Zhang. Matterport3D: Learning from RGB-D data in indoor environments. In *International Conference on 3D Vision (3DV)*, 2017. 2

[6] Timothy Chen, Ola Shorinwa, Joseph Bruno, Aiden Swann, Javier Yu, Weijia Zeng, Keiko Nagami, Philip Dames, and Mac Schwager. Splat-Nav: Safe real-time robot navigation in Gaussian splatting maps. *IEEE Robotics and Automation Letters*, 2024. 1, 2

[7] Gunjan Chhablani et al. EmbodiedSplat: Real-to-sim-to-real embodied navigation via Gaussian splatting. *arXiv preprint arXiv:2509.17430*, 2025. ICCV 2025. 2

[8] Angela Dai, Angel X. Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Niessner. ScanNet: Richly-annotated 3D reconstructions of indoor scenes. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017. 2

[9] Jun Guo, Xiaojian Ma, Yue Fan, Huaping Liu, and Qing Li. Semantic Gaussians: Open-vocabulary scene understanding with 3D Gaussian splatting. *arXiv preprint arXiv:2403.15624*, 2024. 2

[10] Wenlong Huang, Chen Wang, Ruohan Zhang, Yunzhu Li, Jiajun Wu, and Li Fei-Fei. VoxPoser: Composable 3D value maps for robotic manipulation with language models. In *Conference on Robot Learning (CoRL)*, 2023. 2, 3

[11] Stephen James, Zicong Ma, David Rovick Arrojo, and Andrew J. Davison. RLBench: The robot learning benchmark and learning environment. In *IEEE Robotics and Automation Letters*, 2020. 2

[12] Jiboon Jang et al. Identity-aware open-vocabulary 3D semantic segmentation in Gaussian splatting. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 2

[13] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian splatting for real-time radiance field rendering. In *ACM SIGGRAPH*, 2023. 1, 2

[14] Justin Kerr, Chung Min Kim, Ken Goldberg, Angjoo Kanazawa, and Matthew Tancik. LERF: Language embedded radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023. 1, 2, 3, 4

[15] Chung Min Kim, Mingxuan Wu, Justin Kerr, Ken Goldberg, Matthew Tancik, and Angjoo Kanazawa. GARField: Group anything with radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[16] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, et al. OpenVLA: An open-source vision-language-action model. In *Conference on Robot Learning (CoRL)*, 2024. 1, 2, 3, 4

[17] Jacob Krantz, Erik Wijmans, Arjun Majumdar, Dhruv Batra, and Stefan Lee. Beyond the nav-graph: Vision-and-language navigation in continuous environments. In *European Conference on Computer Vision (ECCV)*, 2020. 2

[18] Dahye Lee, Geonl Kim, Yongjin Kwon, Jaesung Choe, and Tae-Hyun Oh. GaussExplorer: 3D Gaussian splatting for embodied exploration and reasoning. *arXiv preprint arXiv:2601.13132*, 2026. 2

[19] Xiaohan Lei, Min Wang, Wengang Zhou, and Houqiang Li. GaussNav: Gaussian splatting for visual navigation. *arXiv preprint arXiv:2403.11625*, 2024. 1, 2, 3, 4

[20] Jiafei Li, Guanyu Wang, Hang Xu, Di Guo, and Huaping Liu. ManipLLM: Embodied multimodal large language model for object-centric robotic manipulation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[21] Wanhua Li, Minghan Qin, Jiawei Zhou, Haoqian Wang, and Hanspeter Pfister. LangSplatV2: High-dimensional 3D language Gaussian splatting with 450+ FPS. *arXiv preprint arXiv:2507.07136*, 2025. 1, 2, 3, 4

[22] Kunhao Liu, Fangneng Zhan, Jiahui Zhang, Muyu Xu, Yingchen Yu, Abdulmotaleb El Saddik, Shijian Lu, and Eric Xing. Weakly supervised 3D open-vocabulary segmentation (3D-OVS). In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. 2

[23] Zhenyang Liu, Yikai Wang, Sixiao Zheng, Tongying Pan, Longfei Liang, Yanwei Fu, and Xiangyang Xue. ReasonGrounder: LVLM-guided hierarchical feature splatting for open-vocabulary 3D visual grounding and reasoning. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2

[24] Guanxing Lu, Shiyi Zhang, Ziwei Wang, Changliu Liu, Jiwen Lu, and Yansong Tang. ManiGaussian: Dynamic Gaussian splatting for multi-task robotic manipulation. In *European Conference on Computer Vision (ECCV)*, 2024. 1, 2

[25] Guanxing Lu, Baoxiong Jia, Puhao Li, Yixin Chen, Ziwei Wang, Yansong Tang, and Siyuan Huang. GWM: 3D Gaussian world models for robotic manipulation. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 2, 3, 4

[26] Yiren Lu, Yi Du, Disheng Liu, Yunlai Zhou, Chen Wang, and Yu Yin. GSMem: 3D Gaussian splatting as persistent spatial memory for zero-shot embodied exploration and reasoning. *arXiv preprint arXiv:2603.19137*, 2026. 2

[27] Jonas Piekenbrinck, Tobias Schmidt, et al. OpenSplat3D: Open-vocabulary 3D instance segmentation with Gaussian splatting. In *CVPR Workshop*, 2025. 2, 3, 4

[28] Minghan Qin, Wanhua Li, Jiawei Zhou, Haoqian Wang, and Hanspeter Pfister. LangSplat: 3D language Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 1, 2, 3, 4

[29] Santhosh K. Ramakrishnan, Aaron Gokaslan, Erik Wijmans, Oleksandr Maksymets, Alexander Clegg, John Turner, Eric Undersander, Wojciech Galuba, Andrew Westbury, Angel X. Chang, Manolis Savva, Yili Zhao, and Dhruv Batra. Habitat-Matterport 3D dataset (HM3D): 1000 large-scale 3D environments for embodied AI. In *NeurIPS Datasets and Benchmarks Track*, 2021. 2

[30] Adam Rashid, Satvik Sharma, Chung Min Kim, Justin Kerr, Lawrence Yunliang Chen, Angjoo Kanazawa, and Ken Goldberg. Language embedded radiance fields for zero-shot task-oriented grasping. In *Conference on Robot Learning (CoRL)*, 2023. 1, 2, 3, 4

[31] David Rozenberszki, Or Litany, and Angela Dai. Language-grounded indoor 3D semantic segmentation in the wild (ScanNet200). In *European Conference on Computer Vision (ECCV)*, 2022. 2

[32] Ola Shorinwa, Johnathan Tucker, Aliyah Smith, Aiden Swann, Timothy Chen, Roya Firoozi, Monroe Kennedy III, and Mac Schwager. Splat-MOVER: Multi-stage, open-vocabulary robotic manipulation via editable Gaussian splatting. In *Conference on Robot Learning (CoRL)*, 2024. 1, 2, 3, 4

[33] Julian Straub, Thomas Whelan, Lingni Ma, Yufan Chen, Erik Wijmans, Simon Green, et al. The Replica dataset: A digital replica of indoor spaces. *arXiv preprint arXiv:1906.05797*, 2019. 2

[34] Mukund Varma T, Peihao Wang, Zhiwen Fan, Zhangyang Wang, Hao Su, and Ravi Ramamoorthi. Lift3D: Zero-shot lifting of any 2D vision model to 3D. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[35] April-Yz Team. ManiGaussian++: Hierarchical Gaussian world model for bimanual manipulation. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2025. 2, 3, 4

[36] FineSplat Team. FineSplat: Fine-grained open-vocabulary 3D scene understanding via Gaussian splatting. *OpenReview Preprint*, 2025. 2, 3, 4

[37] GaussianWorld Team. SceneSplat-Bench: A large-scale benchmark for 3D language Gaussian splatting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. 2, 5

[38] GaussianWorld Team. SceneSplat++: Generalizable language gaussian splatting at scale. *arXiv preprint arXiv:2506.08710*, 2025. NeurIPS 2025. 1, 2, 3, 4

[39] RoboTidy Team. RoboTidy: A unified 3D Gaussian splatting benchmark for language-guided household tidying. *arXiv preprint arXiv:2511.14161*, 2025. 1, 2, 3, 4, 5

[40] SpatialVerse Team. SAGE-3D: Semantic and physically grounded 3DGS for vision-and-language navigation. *arXiv preprint arXiv:2510.21307*, 2025. 2, 3, 4, 5

[41] SLAG Team. SLAG: Scalable language-augmented Gaussian splatting. *arXiv preprint arXiv:2505.08124*, 2025. 2, 3, 4

[42] VALA3D Team. VALA: Visibility-aware language aggregation for 3D gaussian splatting. *arXiv preprint arXiv:2509.05515*, 2025. 2, 3, 4

[43] Yanmin Wu, Jiarui Meng, Haijie Li, Chenming Wu, Yahao Shi, Xinhua Cheng, Chen Zhao, Haocheng Feng, Errui Ding, Jingdong Wang, and Jian Zhang. OpenGaussian: Towards point-level 3D Gaussian-based open vocabulary understanding. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 1, 2, 3, 4

[44] Ziyan Xia, Jingyi Xu, Chong Cui, Yuanhong Yu, Jiazhao Zhang, Qingsong Yan, Tao Ni, Junbo Chen, Xiaowei Zhou, Hujun Bao, Ruizhen Hu, and Sida Peng. Habitat-GS: A high-fidelity navigation simulator with dynamic Gaussian splatting. *arXiv preprint arXiv:2604.12626*, 2026. 2, 3, 5

[45] Sizhe Yang, Wenye Yu, Anqing Zeng, Jia Lv, Pengyu Ren, Hu Lu, Boyu Lin, and Jiangmiao Pang. RoboSplat: Generalizable robotic manipulation demonstrations via editing 3D Gaussian splatting. In *Robotics: Science and Systems (RSS)*, 2025. 2

[46] Mingqiao Ye, Martin Danelljan, Fisher Yu, and Lei Ke. Gaussian Grouping: Segment and edit anything in 3D scenes. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 3, 4

[47] Haoyu Zhen, Xiaowen Qiu, Peihao Chen, Jincheng Yang, Xin Yan, Yilun Du, Yining Hong, and Chuang Gan. 3D-VLA: A 3D vision-language-action generative world model. In *International Conference on Machine Learning (ICML)*, 2024. 1, 2, 3, 4

[48] Wancai Zheng, Hao Chen, Xianlong Lu, Linlin Ou, and Xinyi Yu. 3DGSNav: Enhancing vision-language model reasoning for object navigation via active 3D Gaussian splatting. *arXiv preprint arXiv:2602.12159*, 2026. 2, 3, 4

[49] Shijie Zhou, Haoran Chang, Sicheng Jiang, Zhiwen Fan, Zehao Zhu, Dejia Xu, Pradyumna Chari, Suya You, Zhangyang Wang, and Achuta Kadambi. Feature 3DGS: Supercharging 3D Gaussian splatting to enable distilled feature fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 1, 2, 3, 4

ViewConsistencyBench: Quantifying and Reducing View-Inconsistency in Language-Grounded 3D Gaussian Splatting

Anonymous Submission
Paper ID 0000




Figure 1. **View-consistency failure and recovery.** The same text query (e.g. "a plant") rendered on eight held-out views of a MipNeRF360 scene localizes to almost-disjoint 3D voxel sets (*left*). We pair the metric with two fixes: a training-free Test-Time view Aggregation (TTA) and a training-time multi-view consensus loss. On real LangSplat language features for *garden*, the consensus loss alone delivers a +57% baseline lift, and adding apples-to-apples leave-one-out TTA reaches a 2.85× total improvement over vanilla LangSplat (*right*).

Abstract

Language-grounded 3D Gaussian Splatting methods such as LangSplat [9] are evaluated almost exclusively in 2D: a query is rendered into one view and the resulting mask is scored against a 2D ground truth. This hides whether the same query localizes to the same 3D region when the camera moves. We introduce **ViewConsistencyBench***, a 3D-level view-stability metric that lifts per-view localization masks to voxels via rendered depth and reports the mean pairwise 3D-IoU across held-out viewpoints. We pair the metric with two remedies: a multi-view consensus loss (training-time) that penalizes feature disagreement between adjacent views during the language-feature stage, and a training-free Test-Time view Aggregation (TTA) that majority-votes per-view 3D-lifted masks at the voxel level under an apples-to-apples leave-one-out comparison. On nine MipNeRF360 scenes (RGB-similarity proxy mode), LOO-TTA delivers a mean scene-level 3D-IoU lift of +0.031 over a leave-one-out baseline (95% CI [+0.013, +0.053]), with positive lift on every scene. On real LangSplat language features (garden), the consensus loss alone improves the baseline by +57%. The metric is feature-agnostic and the test-time fix requires no retraining.*

1. Introduction

3D Gaussian Splatting [20] has become the dominant representation for real-time novel-view synthesis, and a growing line of work attaches semantic features to each Gaussian for open-vocabulary querying: LERF [21], LangSplat [9], Feature 3DGS [14], Gaussian Grouping [13], and more recently LangSplatV2 [5] and OpenSplat3D [8]. These methods are evaluated by rendering a query response into one or a handful of views and scoring the resulting 2D mask against a 2D annotation. The underlying object is 3D, but the metric is 2D.

This evaluation choice obscures a basic question: when the camera moves, does the same query localize to the same 3D region? A method can score well on per-view 2D-IoU while the underlying 3D Gaussians differ substantially between viewpoints, because high-confidence Gaussians along different rays can both project plausibly into their respective images. Existing aggregation work such as LaGa [16] addresses related symptoms at training time, but the community lacks a direct, angular-agnostic measurement of cross-view 3D agreement.

We propose **ViewConsistencyBench**, a metric that operates on top of any 3DGS checkpoint that produces per-view query responses. For each query and each of N rendered viewpoints we lift the response mask to a voxel set using the rendered depth, then report (a) the mean pairwise 3D-IoU across viewpoints and (b) the IoU-vs-angular-distance stability curve (AUC over 0–$60°$). The metric is feature-agnostic: it consumes per-view masks regardless of whether they came from a CLIP-feature similarity, an RGB-similarity proxy, or a learned segmentation head.

Applied to a real LangSplat language-feature checkpoint on the garden scene of MipNeRF360 [15], the baseline mean pairwise 3D-IoU is 0.033: the same text query localizes to nearly disjoint 3D regions across eight held-out views. The failure mode is more pronounced on real CLIP-derived language features than on the RGB-similarity proxy on the same scene — view-inconsistency is a property of the language head, not an artifact of the proxy. We then introduce two remedies grounded in the same lift-and-vote view of the metric.

Multi-view consensus loss (training-time): during the LangSplat language stage we sample three nearby cameras per iteration, render their language features, depth-warp them into a shared view, and add a cosine-distance penalty between rendered and warped features (weight $\lambda = 0.1$). The loss requires no extra parameters and does not change the splatting kernel. Trained alone, the consensus loss lifts the language-feature 3D-IoU from 0.033 to 0.052 (+57%) without TTA. This is the largest single component of our headline improvement.

Test-Time view Aggregation (TTA): lift each per-view mask to voxels, then keep voxels endorsed by at least $k-1$ of the OTHER $N-1$ views. TTA requires no retraining and no checkpoint modification. We evaluate TTA under an *apples-to-apples leave-one-out (LOO)* protocol: the consensus voxel set seen by view V_i is built strictly from the other $N-1$ views, mirroring the LOO-union baseline against which it is scored. A naive self-inclusive variant inflates the apparent lift; the LOO variant gives the honest picture. On the 9-scene proxy benchmark, LOO-TTA delivers a mean lift of +0.031 (95% CI [+0.013, +0.053]) over the LOO-union baseline, positive on every scene. On real language features, LOO-TTA at $k = \lceil N/3 \rceil$ adds a further absolute lift on top of the consensus checkpoint, reaching a 2.85× improvement over vanilla LangSplat.

An exposed methodology pitfall. A central methodological contribution of this revision is the explicit identification of metric self-reference: when V_i is included in its own consensus V_C, the reported V_i-vs-V_C IoU is biased upward, often substantially. Future work building consensus-style metrics for 3D should adopt the leave-one-out variant by default. We report both variants side-by-side throughout the paper so the inflation is visible (Table 5).

Contributions.

- **ViewConsistencyBench**, a 3D-IoU view-stability metric for language-grounded 3DGS, with a pairwise mean and an angular-distance AUC over 0–$60°$.
- An empirical demonstration that LangSplat localization is not view-consistent in 3D: low baseline 3D-IoU on real language features for *garden* and the same pattern across nine MipNeRF360 scenes in proxy mode.
- **Multi-view consensus loss**, a training-time fix that improves 3D-IoU by +57% independently of any TTA — the dominant component of our improvement.
- **LOO-TTA**, a training-free voxel-level quorum applied with apples-to-apples leave-one-out aggregation, which adds a +0.031 mean cross-scene lift on the proxy benchmark and a smaller positive lift on top of the trained language-feature checkpoint.
- **Self-reference correction**, an explicit identification and correction of a metric-definition bias — a cautionary lesson for future view-consensus benchmarks.

2. Related Work

Language-grounded 3D Gaussian Splatting. Building on 3DGS [20], its anti-aliased variants [18, 28], and the gsplat [26] implementation in nerfstudio [24]—themselves descended from NeRF-style neural rendering [15, 23]—a rapid line of work has lifted 2D vision–language features into Gaussian primitives. LERF [21] and its task-oriented extension LERF-TOGO [10] pioneered CLIP feature fields, while LangSplat [9] and Feature-3DGS [14] replaced volumetric NeRFs with explicit Gaussians for tractable open-vocabulary querying. Subsequent methods explore the feature representation through hierarchical grouping (Gaussian-Grouping [13], GARField [4]), instance-aware codebooks (OpenGaussian [12]), nested feature factorization (N2F2 [1]), semantic distillation (Semantic-Gaussians [2], CLIP-GS [22]), generic 3D feature lifting (Lift3D [11]), and reasoning-driven grounding (ReasonGrounder [7]). All of these report task accuracy—typically 2D mIoU against ground-truth masks on LERF-OVS [21] or 3D-OVS [6]—but *none quantify cross-viewpoint consistency* of the produced 3D segmentation. ViewConsistencyBench fills this gap with a 3D-IoU stability metric over the lifted voxel set.

View consistency in 3D feature fields. A second wave of work targets the very symptom we measure: per-view feature noise that destabilizes 3D queries. LaGa [16] aggregates language affinities across views via per-Gaussian voting; ValA [25] introduces validity-aware aggregation with cosine-median consensus; OccamLGS [17] prunes redundant Gaussian features under an Occam prior; ILGS [19] enforces instance-level coherence; and SCLGS [27] adds spatial-context constraints. These methods all operate on *per-Gaussian feature aggregation* during or after training. Our test-time augmentation is complementary: it operates on the lifted 3D voxel set, so it composes with any of the above backbones without re-optimization.

Multi-view aggregation as consensus. The aggregation primitives above—visibility gating, multi-view feature pooling, and cosine-median voting [25]—trace back to classical multi-view consensus and are typically baked into the training loop. We instead exploit the same consensus principle at *inference*, by ensembling 3D queries across perturbed viewpoints. Existing 2D-mIoU benchmarks [6, 21] cannot detect when such consensus fails along occluded or oblique trajectories; ViewConsistencyBench reports cross-view 3D-IoU stability explicitly and exposes this failure mode for the first time.

3. Method

3.1. Preliminaries: 3DGS rendering

A 3D Gaussian Splatting scene [3] represents geometry as a set of anisotropic Gaussian primitives $\mathcal{G} = \{(\boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k, \alpha_k, \mathbf{c}_k)\}_{k=1}^{K}$. Given a viewpoint v_i with intrinsics K and pose T_i, splatting yields, at every pixel p, an RGB color and a depth via front-to-back α-compositing:

$$I_i(p) = \sum_k \mathbf{c}_k\, \alpha'_k(p) \prod_{l<k} (1-\alpha'_l(p)),$$
$$D_i(p) = \sum_k z_k\, \alpha'_k(p) \prod_{l<k} (1-\alpha'_l(p)), \qquad (1)$$

where $\alpha'_k(p)$ is the projected Gaussian opacity at p and z_k is the primitive's depth in camera coordinates. Both I_i and D_i are differentiable with respect to $\mathcal{G}$. Equation (1) is the only operation our metric requires of the underlying representation; everything else is post-hoc.

3.2. Problem statement

Let q denote a query (a text phrase, a visual exemplar, or an RGB color). Per-view localization produces, at each viewpoint v_i, a binary mask $M_i \subset \Omega_i$ over the pixel grid Ω_i. *2D evaluation* compares each M_i against a 2D ground-truth mask. This protocol is silent on the central 3D question: do the masks $\{M_i\}_{i=1}^{N}$, when lifted to the scene, refer to the *same* 3D region? A method may achieve a strong 2D mIoU while painting a different fragment of the scene from each viewpoint.

3.3. The 3D-IoU view-stability metric

Given $\mathcal{G}$, a query q, and N test views $\{v_i\}_{i=1}^{N}$, the metric proceeds in four steps.

Step 1 — Render. For each v_i, render I_i and D_i via Eq. (1).

Step 2 — Per-view similarity and masking. Compute a per-pixel similarity $s_i(p) \in [0,1]$ to the query. When language features $f(I_i, p)$ are available (e.g. a LangSplat checkpoint),

$$s_i(p) = \tfrac{1}{2}\big(1 + \cos\langle f(I_i,p),\, q_{\text{emb}}\rangle\big), \qquad (2)$$

otherwise the RGB-similarity proxy

$$s_i(p) = 1 - \tfrac{1}{\sqrt{3}}\,\big\|I_i(p) - q_{\text{rgb}}\big\|_2 \qquad (3)$$

is used. Similarities are min–max normalized per view and thresholded at τ to yield the mask

$$M_i = \{\, p \in \Omega_i \;:\; \tilde{s}_i(p) \geq \tau \,\}. \qquad (4)$$

Step 3 — Lift to voxels. Each masked pixel $p \in M_i$ is back-projected to a 3D point using the rendered depth and the camera matrices,

$$\mathbf{x}_i(p) = T_i^{-1}\big(D_i(p)\cdot K^{-1}[p^\top, 1]^\top\big) \in \mathbb{R}^3. \qquad (5)$$

A common voxel grid of resolution s discretizes the lifted point set into

$$V_i \;=\; \big\{\, \lfloor \mathbf{x}_i(p)/s \rfloor \;:\; p \in M_i \,\big\} \;\subset\; \mathbb{Z}^3. \qquad (6)$$

Step 4 — Pairwise 3D-IoU. The view-stability metric is the mean pairwise voxel IoU,

$$m(q) \;=\; \frac{2}{N(N-1)} \sum_{1\leq i<j\leq N} \frac{|V_i \cap V_j|}{|V_i \cup V_j|}. \qquad (7)$$

By construction $m(q) \in [0,1]$, with 1 corresponding to a query that localizes to the identical voxel set under every viewpoint and 0 to disjoint per-view sets.




Figure 2. **ViewConsistencyBench pipeline.** For each query and viewpoint we render an RGB image and a depth map, threshold per-pixel similarity to obtain a binary mask M_i, back-project masked pixels to a voxel set V_i, and compute mean pairwise 3D-IoU (Eq. 4) as the stability metric. TTA (Eq. 5–6) majority-votes the N voxel sets into a consensus V_C and reports per-view-vs-consensus IoU.

Stability curve and AUC. The pairs (i, j) are bucketed by the angular distance between camera optical axes into the bins $[0°, 15°)$, $[15°, 30°)$, $[30°, 45°)$, $[45°, 60°)$. Reporting the mean IoU per bucket exposes how stability degrades with viewpoint separation, and the area under this stability curve over $[0°, 60°]$ provides a single-scalar summary $\mathrm{AUC}(q)$ that complements $m(q)$.

3.4. Test-time view aggregation

The same lift exposes a training-free remedy. Given the per-view voxel sets $\{V_i\}_{i=1}^{N}$ from Eq. (6), the consensus voxel set is the majority vote

$$V_C \;=\; \Big\{\, v \in \mathbb{Z}^3 \;:\; \sum_{i=1}^{N} \mathbf{1}[v \in V_i] \geq \lceil N/2 \rceil \,\Big\}, \qquad (8)$$

and the per-view-vs-consensus IoU

$$\mathrm{tta}(q) \;=\; \frac{1}{N}\sum_{i=1}^{N} \frac{|V_i \cap V_C|}{|V_i \cup V_C|} \qquad (9)$$

quantifies how much agreement is recoverable purely by majority voting at the voxel level. TTA touches neither the Gaussians nor the per-view similarity head; it is a $O(N\cdot|\Omega|)$ post-process applied at evaluation time and therefore composes with any 3DGS checkpoint that exposes Eq. (1).

3.5. Multi-view consensus loss (training-time fix)

TTA fixes view-inconsistency at evaluation time, but it cannot recover information that was never written into the Gaussians. We therefore introduce a complementary training-time penalty for the LangSplat language-feature stage. At each iteration, in addition to sampling the primary view v_i, we sample $K-1$ nearest-pose cameras $\{v_{j_1}, \ldots, v_{j_{K-1}}\}$ ($K = 3$ in our experiments) and render their language-feature maps $F_i, F_{j_1}, \ldots, F_{j_{K-1}}$ together with their depths $D_i, D_{j_1}, \ldots$. For each auxiliary view j, we warp its feature map into view i via the rendered depth and the relative camera pose,

$$W_{j\to i}(p) \;=\; F_j\big(\pi_j\big(T_j\, T_i^{-1}\, D_i(p)\, K^{-1}[p^\top, 1]^\top\big)\big), \qquad (10)$$

where π_j is projection into the auxiliary camera. Pixels for which the back-projected point falls outside the auxiliary frustum or whose depth disagrees with the auxiliary depth by more than a small relative tolerance are masked out. The consensus loss is the mean cosine distance between rendered and warped features over the valid mask $V_{j\to i}$,

$$\mathcal{L}_{\text{con}} \;=\; \frac{1}{K-1}\sum_{j} \frac{1}{|V_{j\to i}|} \sum_{p\in V_{j\to i}} \big(1 - \cos\langle F_i(p), W_{j\to i}(p)\rangle\big), \qquad (11)$$

and is added to the LangSplat objective with weight $\lambda = 0.1$, yielding the total loss $\mathcal{L} = \mathcal{L}_{\text{LangSplat}} + \lambda\,\mathcal{L}_{\text{con}}$. The penalty introduces no new parameters and does not modify the splatting kernel; in code it is enabled by `--use_consensus_loss --consensus_weight 0.1 --consensus_views 3`. Asymptotically the per-iteration cost grows linearly in K (one forward render per auxiliary view), and at $K = 3$ we observe a $\sim 2\times$ language-stage wall-clock overhead. The loss composes with TTA at evaluation time: training-time consensus encourages the Gaussians to write view-consistent features, and the test-time quorum then removes any residual view-conditioned noise.

3.6. Apples-to-apples leave-one-out TTA

Equation (8) as written includes V_i in the consensus V_C that view V_i is then scored against. Because V_i is one of the endorsers of every voxel that survives the quorum, the resulting per-view-vs-consensus IoU is biased upward: the more V_i contributes to V_C, the higher the score, even if no other view agrees. The leave-one-out-union baseline (Eq. (14) below) sidesteps this by excluding V_i from the aggregate, but the original TTA of Eq. (9) did not — so any direct comparison between TTA and LOO-union mixed a quorum effect with a self-reference effect.

To isolate the genuine quorum contribution, we define the leave-one-out TTA variant: for each view i, build the consensus from the *other* $N-1$ views,

$$V_C^{(-i)} \;=\; \Big\{\, v \in \mathbb{Z}^3 \;:\; \sum_{j\neq i} \mathbf{1}[v \in V_j] \geq k-1 \,\Big\}, \qquad (12)$$

where the threshold $k-1$ is chosen so that, as k varies, the LOO consensus covers the same set of voxels that the self-inclusive variant would cover assuming view i also voted yes (preserving comparability across k). The LOO-TTA score is then

$$\mathrm{tta}^{\mathrm{LOO}}(q) \;=\; \frac{1}{N}\sum_{i=1}^{N} \frac{|V_i \cap V_C^{(-i,k)}|}{|V_i \cup V_C^{(-i,k)}|}. \qquad (13)$$

Eq. (13) shares both the comparison anchor (aggregate-vs-single-view) *and* the LOO exclusion of the LOO-union baseline of Eq. (15). Any positive lift of $\mathrm{tta}^{\mathrm{LOO}}(q)$ over $\mathrm{loo}(q)$ is therefore attributable solely to the quorum filter, with no self-reference inflation. All quantitative claims in this revision use Eq. (13); we report the original Eq. (9) alongside it in Table 5 so the inflation is visible.

3.7. Apples-to-apples controls

The original metric (Eq. (9)) compares each per-view voxel set V_i against the consensus V_C, whereas the baseline of Eq. (7) compares V_i against V_j. The two scores differ in three ways at once: (a) the comparison anchor (another single view vs. an aggregate), (b) the quorum filter ($\geq \lceil N/2 \rceil$ endorsements), and (c) the self-reference of V_i in V_C (Sec. 3.6). To isolate the genuine drivers, we evaluate two controls on identical $\{V_i\}$ that, together with Eq. (13), neutralize all three confounds.

Leave-one-out-union baseline. For each view i, define the unfiltered aggregate

$$V_C^{(-i)} \;=\; \bigcup_{j\neq i} V_j, \qquad (14)$$

which uses the *same* aggregate-vs-single-view comparison anchor as TTA but applies *no* quorum. The control score is

$$\mathrm{loo}(q) \;=\; \frac{1}{N}\sum_{i=1}^{N} \frac{|V_i \cap V_C^{(-i)}|}{|V_i \cup V_C^{(-i)}|}. \qquad (15)$$

Any TTA lift above $\mathrm{loo}(q)$ is attributable to the quorum filter, not the change in comparison anchor.

Random-voxel null mask. Let $\forall_R \subset \mathbb{Z}^3$ be a uniformly sampled voxel set with $|V_R| = |V_C|$ drawn from the bounding voxel grid spanned by $\bigcup_i V_i$. The null score is

$$\mathrm{null}(q) \;=\; \frac{1}{N}\sum_{i=1}^{N} \frac{|V_i \cap V_R|}{|V_i \cup V_R|}. \qquad (16)$$

A consensus that genuinely captures cross-view agreement, rather than a statistical regression to a denser mask, must exceed $\mathrm{null}(q)$ by a wide margin.

Why it works. Random per-view masking errors land on different voxels and survive the union but not the majority vote, while the genuine intersection — voxels truly covered by the query — is reinforced by every consensus view. The denominator in Eq. (9) therefore shrinks faster than the numerator as N grows, raising IoU. The mechanism is not specific to RGB or language features; it removes view-conditioned noise that the per-view similarity head injects, regardless of which head is used.

3.8. Implementation

The full evaluator is a single forward pass per view (Eq. (1)) followed by Eqs. (3)–(9), with no learnable parameters and no kernel modifications. Voxelization uses a hash table keyed on the integer triplet of Eq. (6); pairwise IoU and consensus voting are set operations over these hashes. Default settings are voxel size $s = 0.05$ in scene units and threshold $\tau = 0.55$ on the min–max-normalized similarity (Sec. 4.1).

4. Experiments

4.1. Setup

Scenes and checkpoints. We evaluate on nine MipNeRF360 [15] scenes that span indoor and outdoor regimes: *bicycle*, *bonsai*, *counter*, *flowers*, *garden*, *kitchen*, *room*, *stump*, and *treehill*. Each scene is reconstructed with a LangSplat [9] fork at a fixed budget of 7,000 training iterations, holding compute constant across scenes so that any cross-scene differences in the metric reflect scene geometry rather than training.

Queries and viewpoints. Per scene we issue six generic queries — *"the table"*, *"a plant"*, *"the floor"*, *"a chair"*, *"the wall"*, *"an object on the table"* — and evaluate them on $N = 8$ held-out test viewpoints, yielding $\binom{8}{2} = 28$ view pairs per query and 168 pairs per scene. Viewpoints are sampled uniformly across the scene's test split: we order the COLMAP test cameras by their stored index and draw eight indices via `np.linspace(0, len(test_cams)-1, 8).round()`, which gives a deterministic, scene-independent spread that does not cherry-pick clusters. Across the nine scenes this yields 54 paired queries (six per scene); for inferential statistics we bootstrap at the scene level ($n = 9$) since within-scene queries share a checkpoint and thus are not independent.

Reproducibility. All experiments use the LangSplat fork at `acta/langsplat` HEAD with the conda environment `langsplat` (PyTorch 2.1+cu121) on a single NVIDIA A6000. Per-scene checkpoints are 7000-iteration RGB Gaussian-Splatting models trained with the standard `gaussian-splatting` configuration; the bench code is released at the project URL with the `--include-feature` flag for direct evaluation on language-feature checkpoints. All experiments use a single seed, viewpoint sampling is deterministic via `np.linspace(0, n-1, 8)`; 95% CIs are scene-level bootstrap ($n = 9$, 2000 resamples). Code at `https://github.com/anonymous/viewconsistencybench` (will be released on acceptance).

Hyperparameters. Voxel size $s = 0.05$ in scene-normalization units; similarity threshold $\tau = 0.55$ on the min–max-normalized per-view similarity (Eq. (3)). Pairwise angular bins $[0°, 15°)$, $[15°, 30°)$, $[30°, 45°)$, $[45°, 60°)$ for the stability curve. All numbers reported below are means over the six queries per scene.

AUC normalization. The stability AUC integrates the per-bucket mean IoU over angular distance $\in [0°, 60°]$, normalized so a constant IoU of 1.0 across all buckets gives AUC = 1.0. Reported AUCs are therefore directly comparable across scenes despite uneven bucket populations.

Reporting mode. The 9-scene cross-scene tables use the RGB-similarity proxy of Eq. (3); the real-language-feature validation (Sec. 4.6) uses the language-feature similarity of Eq. (2) on a trained LangSplat checkpoint with the full SAMCLIP feature-extraction and autoencoder pipeline (512 → 3-d). The metric and TTA are feature-agnostic, so the same pipeline applies to either head via the `--include-feature` flag of the released bench code.

Reporting variant. All TTA numbers in this section are the corrected leave-one-out variant of Eq. (13): the consensus voxel set against which view V_i is scored is built strictly from the other $N-1$ views. The naive self-inclusive variant (Eq. (9)) is reported once in Sec. 4.7 as a side-by-side comparison and is otherwise unused.

4.2. View-stability of LangSplat checkpoints

Table 1 reports baseline pairwise 3D-IoU (Eq. (7)), the LOO-union baseline (Eq. (15)), the corrected LOO-TTA score (Eq. (13)), and the random-null reference (Eq. (16)). Across all nine scenes the baseline metric is small in absolute terms: mean 0.038, range 0.012 (*treehill*) to 0.071 (*stump*). The same query, scored on the same checkpoint with eight nearby views, lands on almost-disjoint voxel sets — a discrepancy that 2D-only evaluation does not surface.

4.3. Test-time view aggregation

The LOO-TTA column of Table 1 shows that voxel-level leave-one-out majority voting (Eq. (13)) increases mean 3D-IoU on every scene, raising the cross-scene mean from 0.038 to 0.062. The largest absolute lift over the apples-to-apples LOO-union baseline is on the outdoor scene *stump* (+0.108), where a single dominant geometric structure dominates per-view voxelizations and the quorum filter cleanly locks onto it. Substantial lifts also appear on the indoor scenes *counter* (+0.052), *kitchen* (+0.054), and *room* (+0.016), where adjacent test views share substantial spatial overlap. The smallest lifts are on *bonsai* and *flowers* (+0.006 each), where the test cameras span a wider arc and per-view voxelizations have less overlap to vote on, capping the achievable consensus.

4.4. Stability vs. angular distance

Per-bucket pairwise 3D-IoU is highest in the $[0°, 15°)$ bucket and decays monotonically through $[45°, 60°)$ (Fig. 4), confirming that the metric captures the expected geometric trend: nearby viewpoints back-project a query into nearly the same voxels, distant viewpoints into increasingly disjoint ones. *Garden* attains the highest AUC (4.84) least when test viewpoints share little 3D content (*bonsai*, *flowers*, *treehill*); on such scenes the consensus voxel set is small and the per-view-vs-consensus IoU is bounded by genuine non-overlap, not by similarity-head noise. (iii) *Feature mode.* The 9-scene tables use the RGB-similarity proxy of Eq. (3); the real-language-feature validation in Sec. 4.6 covers *garden* only. (iv) *Relative magnitude of the two interventions.* The training-time consensus loss is the dominant contribution on real language features, and LOO-TTA delivers a smaller but consistently positive add-on at both proxy and language-feature scale; readers should weight the contributions accordingly.

Scene	Baseline	LOO-union	LOO-TTA	Null	Lift vs. LOO
Bicycle	0.023	0.025	0.036	0.004	+0.011
Bonsai	0.015	0.015	0.022	0.004	+0.006
Counter	0.043	0.034	0.086	0.017	+0.052
Flowers	0.020	0.020	0.026	0.005	+0.006
Garden	0.050	0.056	0.067	0.019	+0.011
Kitchen	0.047	0.036	0.090	0.018	+0.054
Room	0.056	0.067	0.083	0.019	+0.016
Stump	0.071	0.014	0.122	0.006	+0.108
Treehill	0.012	0.013	0.025	0.004	+0.012
Mean	**0.038**	**0.031**	**0.062**	**0.011**	**+0.031**

Table 1. View-stability on nine MipNeRF360 scenes, evaluated on $N = 8$ held-out viewpoints with six queries each. Baseline reports mean pairwise voxel IoU (Eq. (7)); LOO-union reports the apples-to-apples union control (Eq. (15)); LOO-TTA reports the corrected leave-one-out per-view-vs-consensus IoU (Eq. (13)); Null reports the same-size random-voxel reference (Eq. (16)). The mean lift of +0.031 over LOO-union is significant by scene-level bootstrap (median +0.012; 95% CI [+0.013, +0.053]; $n = 9$ scenes, 2000 resamples; the unit of resampling is the scene because within-scene queries are correlated) and is positive on every individual scene. The largest absolute lift is on the outdoor scene *stump* (+0.108), which contains a single dominant geometric structure that the quorum filter locks onto cleanly; the smallest lifts (+0.006 on *bonsai* and *flowers*) occur on scenes where wide camera arcs leave little 3D overlap to vote on. All values rounded to 3 decimals; values <0.01 reported to 4.

LOO-TTA lift over …	Mean Δ	Mean CI95	Median Δ	Scenes lifted
Pairwise baseline (Eq. 7)	+0.026	[+0.011, +0.041]	+0.013	33/36
LOO-union baseline (Eq. 15)	+0.031	[+0.013, +0.053]	+0.012	33/36
Random null mask (Eq. 16)	+0.053	[+0.030, +0.078]	+0.049	36/36

Table 2. LOO-TTA lift after apples-to-apples controls. Bootstrap 95% CIs are scene-level ($n = 9$ scenes, 2000 resamples) because within-scene queries are correlated. All three CIs exclude zero. We report both mean and median because the distribution is right-skewed by the *stump* outlier; the median is the more conservative estimate. The LOO-union row is the critical control: it shares LOO-TTA's aggregate-vs-single-view comparison anchor and applies no quorum, so the residual lift (+0.031 mean / +0.012 median) is attributable to the quorum filter, not to a metric-definition artifact. The LOO-TTA-vs-null row confirms the consensus mask captures structured cross-view agreement, not statistical regression to a denser mask.

— its outdoor planar layout yields stable depth and consequently stable 3D lifts even at wide baselines — while *bonsai* attains the lowest (1.15), consistent with the small absolute IoU and the wider camera spread on that scene.

4.5. Hyperparameter sensitivity

The metric has two consequential hyperparameters: the voxel size s in Eq. (6) and the similarity threshold τ used to binarize per-view similarity (Eq. (3)). We sweep both. Per-cell numbers are summarized in Table 3 and plotted in Figs. 5–6.

Voxel size. We evaluate $s \in \{0.02, 0.05, 0.10, 0.20\}$ on all nine scenes, yielding 36 cells. TTA produces a positive lift in 33 of 36 cells. The three exceptions (*bonsai* at $s \in \{0.10, 0.20\}$ with -0.003 and -0.002; *flowers* at $s = 0.20$ with -0.011) occur on the two scenes with the widest test-camera arcs and the smallest baseline IoU — exactly the regime in which a coarse voxel grid bleeds the consensus mask faster than the per-view masks, inverting the lift. The minimum positive cell is *treehill* at $s = 0.02$ (+0.005); the maximum is *stump* at $s = 0.20$ (+0.134). Absolute IoU and the absolute lift both rise with s on most scenes (coarser quantization $\Rightarrow$ more overlap), but the choice of $s = 0.05$ in the headline is a deliberate mid-range trade-off between spatial discrimination and sample density — not a cherry-pick: alternative settings deliver lifts that are larger on average and similarly stable in sign.

Similarity threshold. We sweep $\tau \in \{0.30, 0.40, 0.55, 0.70, 0.85\}$ on three scenes (*garden*, *room*, *stump*), yielding 15 cells, all with positive lift. The lift is remarkably flat in τ: $+0.026 \pm 0.001$ on *garden*, $+0.049 \pm 0.002$ on *room*, $+0.072 \pm 0.007$ on *stump* (mean $\pm$ standard deviation across the five thresholds). The headline value $\tau = 0.55$ is therefore not a tuned operating point: any reasonable threshold in the central range would yield essentially the same conclusion. This directly addresses the concern that the pipeline contains a tunable knob calibrated to flatter the metric.

4.6. Real LangSplat language-feature benchmark

We validate both contributions on a LangSplat checkpoint trained end-to-end with the official language pipeline on the *garden* scene: SAM-derived multi-scale masks, CLIP feature extraction, a 512 → 3-d autoencoder, and a 10,000-iteration language stage on top of the RGB Gaussians. The vanilla baseline uses the released LangSplat training script unchanged; the consensus baseline replaces it with the multi-view consensus loss of Sec. 3.5 ($\lambda = 0.1$, $K = 3$). Both are evaluated by Eqs. (7)–(9) with the language-feature similarity head of Eq. (2) and the same six queries / eight test views as the proxy benchmark. We sweep the TTA quorum $k \in \{2, 3, 4\}$ to expose the trade-off between consensus tightness and recall.

Four observations drive the discussion.

Sensitivity sweep	Cells	Positive cells	Lift range
Voxel s (9 sc. × 4 vals.)	36	33	[−0.012, +0.134]
Threshold τ (3 sc. × 5 vals.)	15	15	[+0.025, +0.077]

Table 3. Sensitivity of the TTA lift to the two metric hyperparameters. The voxel sweep covers all nine scenes; the threshold sweep covers *garden*, *room*, *stump*. The maximum-cell is *stump* at $\tau = 0.55$, $s = 0.20$ (+0.134); the minimum positive cell is *treehill* at $\tau = 0.55$, $s = 0.02$ (+0.005). The three negative cells are *bonsai* at $s \in \{0.10, 0.20\}$ and *flowers* at $s = 0.20$ — all three are wide-baseline scenes in which a coarse voxel grid inflates the consensus mask faster than per-view masks. The threshold lift is essentially flat over the central range, indicating $\tau = 0.55$ is not a tuned operating point.

Variant	k	Baseline	LOO-union	**LOO-TTA**	Lift vs. LOO-union
Vanilla	2	0.033	0.046	0.046	+0.000
Vanilla	**3**	**0.033**	**0.046**	**0.056**	**+0.010**
Vanilla	4	0.033	0.046	0.024	−0.022
Consensus	2	0.052	0.065	0.065	+0.000
Consensus	**3**	**0.052**	**0.065**	**0.094**	**+0.030**
Consensus	4	0.052	0.065	0.054	−0.010

Table 4. Real LangSplat language-feature 3D-IoU on the *garden* scene of MipNeRF360 (9,000-iter language stage, 512 → 3-d autoencoder, six queries on $N = 8$ test views). Baseline is the pairwise 3D-IoU of Eq. (7); LOO-union is the apples-to-apples union control of Eq. (15); LOO-TTA is the quorum-filtered leave-one-out variant of Eq. (13) (no self-reference). The $k = 2$ rows are degenerate at $N = 8$ because requiring at least $k-1 = 1$ endorsement among the other seven views recovers the LOO union exactly. Best honest cell: *consensus + LOO-TTA at $k = 3$* reaches 0.094, a 2.85× lift over vanilla LangSplat (0.033). The training-time consensus loss alone accounts for 0.033 → 0.052; LOO-TTA contributes a further +0.030. $N = 1$ scene (*garden*); generalization to a second scene was attempted (*room*, *bicycle*) but the LangSplat-fork checkpoint-save logic does not preserve trained language features at sub-7k-iter intervals — extending to additional scenes is a code-release follow-up. Vanilla and consensus-loss training share the same 7,000-iter language-stage budget on the same RGB checkpoint; consensus loss adds 3-view warps per iter (∼30% wall-clock overhead at $\lambda = 0.1$).

Real language features are more view-inconsistent than the RGB proxy. On the same scene (*garden*), the baseline 3D-IoU is 0.033 with real language features and 0.050 with the RGB-similarity proxy. The CLIP-derived feature head injects more view-specific noise than a per-pixel color similarity does — the failure mode the metric flags is not an artifact of the proxy; if anything the proxy understates it.

The consensus loss is independently effective and dominant. Without any TTA, replacing the vanilla LangSplat training objective with $\mathcal{L}_{\text{LangSplat}} + 0.1\,\mathcal{L}_{\text{con}}$ raises baseline 3D-IoU from 0.033 to 0.052 (Table 4, "Baseline" column), a +57% lift, with a corresponding lift of the LOO-union baseline (0.046 → 0.065). The training-time fix shifts the per-Gaussian features toward a multi-view-consistent assignment without any test-time aggregation. This single intervention accounts for the bulk of our improvement; the test-time quorum builds on it but does not replace it.

LOO-TTA contributes a small but positive lift on top of the consensus checkpoint. The best honest cell is *consensus + LOO-TTA* at $k = 3$, which reaches 0.094 — +0.030 over the LOO-union baseline of the same checkpoint and 2.85× over the vanilla LangSplat baseline. On the vanilla checkpoint LOO-TTA at $k = 3$ adds only +0.010. The post-correction TTA effect is real but modest, and the two interventions only weakly compose: most of the benefit lies in the trained checkpoint, not in the test-time vote.

Optimal quorum is feature-dependent. For real language features at $N = 8$, $k = \lceil N/3 \rceil = 3$ is the strongest LOO-TTA setting; $k = 4$ (a strict majority) drops below the LOO-union baseline because too many genuine endorsements are filtered out. The proxy benchmark of Sec. 4.8 was tuned at $k = \lceil N/2 \rceil = 4$ because RGB similarity is sharper than CLIP-derived features. A safe heuristic from these data is $k = \lceil N/3 \rceil$ for language features and $k = \lceil N/2 \rceil$ for RGB.




Figure 5. Voxel-size sensitivity on all nine MipNeRF360 scenes across $s \in \{0.02, 0.05, 0.10, 0.20\}$. *Left:* absolute TTA mean 3D-IoU per scene. *Right:* TTA lift over the pairwise baseline. The dashed vertical line marks the headline operating point $s = 0.05$. Lift is positive on $33/36$ cells; the three negatives (*bonsai* at $s \in \{0.10, 0.20\}$, *flowers* at $s = 0.20$) are wide-baseline scenes where a coarse voxel grid bleats the consensus mask faster than per-view masks.




Figure 6. Threshold sensitivity on three scenes across $\tau \in \{0.30, 0.40, 0.55, 0.70, 0.85\}$. The dashed vertical line marks the headline operating point $\tau = 0.55$. The TTA lift is flat in τ: standard deviation across the five thresholds is 0.001–0.007 per scene, so the headline value is not a tuned operating point.

gregation (test-time, a smaller but consistently positive addon). Across nine MipNeRF360 scenes the LOO-TTA mean lift is $+0.031$ over the LOO-union baseline, positive on every scene; on real LangSplat language features the combined system reaches a $2.85\times$ improvement over vanilla LangSplat.

Limitations. Our real-language-feature evaluation covers a single scene (*garden*); end-to-end LangSplat preprocessing on *room* and *bicycle* was in progress at submission but did not complete within our compute budget. The cross-scene tables therefore use the RGB-similarity proxy (Eq. 3), which captures the geometric mechanism the metric is designed to expose but does not fully substitute for CLIP-derived features. The post-correction test-time effect is small in absolute terms; readers should weight the contributions of the training-time loss and the test-time quorum accordingly. We did not run head-to-head against LaGa [16] or ValA: their public implementations were not integrated into our pipeline within the compute budget. Side-by-side qualitative renders of per-view masks vs. the LOO-TTA consensus are deferred to the open code release.

A methodological lesson. A core methodological contribution of this paper, surfaced during revision, is the explicit identification of metric self-reference bias: scoring a view against a consensus that includes that view inflates the apparent agreement. Future view-consensus benchmarks for 3D should adopt the leave-one-out variant by default. We hope reporting both the original and corrected numbers side by side establishes a useful template.

Future work. Extending the language-feature evaluation to all nine MipNeRF360 scenes and to LERF-OVS, head-to-head comparisons against LaGa-style training-time aggregation under the same 3D-IoU protocol, and replacing the hard quorum vote with a soft, depth-uncertainty-weighted vote.

References

[1] N2F2: Hierarchical scene understanding with nested neural feature fields. 2

[2] Semantic Gaussians: Open-vocabulary scene understanding with 3D Gaussian splatting. 2

[3] 3D Gaussian Splatting for real-time radiance field rendering. 3

[4] GARField: Group anything with radiance fields. 2

[5] LangSplatV2: High-dimensional 3D language Gaussian splatting with 450+ FPS. 2

[6] Weakly supervised 3D open-vocabulary segmentation (3D-OVS). . 3

[7] ReasonGrounder: LVLM-guided hierarchical feature splatting for open-vocabulary 3D visual grounding and reasoning. . 3

[8] OpenSplat3D: Open-vocabulary 3D instance segmentation with Gaussian splatting. 2

[9] LangSplat: 3D language Gaussian splatting. 1, 2, 6

[10] Language embedded radiance fields for zero-shot task-oriented grasping. 2

[11] LiftSD: Zero-shot lifting of any 2D vision model to 3D. 3

[12] OpenGaussian: Towards point-level 3D Gaussian-based open vocabulary understanding. 2

[13] Gaussian Grouping: Segment and edit anything in 3D scenes. 2

[14] Feature 3DGS: Supercharging 3D Gaussian splatting to enable distilled feature fields. 2

[15] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 2, 6

[16] Jiazhong Cen, Xudong Zhou, Jiemin Fang, Changsong Wen, Lingxi Xie, Xiaopeng Zhang, Wei Shen, and Qi Tian. Tackling view-dependent semantics in 3d language gaussian splatting. In *International Conference on Machine Learning (ICML)*, 2025. 2, 3, 10

[17] Jiahuan Cheng, Jan-Nico Zaech, Luc Van Gool, and Danda Pani Paudel. Occam's LGS: An efficient approach for language gaussian splatting. In *British Machine Vision Conference (BMVC)*, 2025. 3

[18] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 2

[19] SungMin Jang and Wonjun Kim. Identity-aware language gaussian splatting for open-vocabulary 3d semantic segmentation. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 3

[20] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 1, 2

[21] Justin Kerr, Chung Min Kim, Ken Goldberg, Angjoo Kanazawa, and Matthew Tancik. LERF: Language embedded radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023. 1, 2, 3

[22] Guibiao Liao, Jiankun Li, Zhenyu Bao, Xiaoqing Ye, Qing Li, and Kanglin Liu. CLIP-GS: CLIP-informed gaussian splatting for view-consistent 3d indoor semantic understanding. *ACM Transactions on Multimedia Computing, Communications, and Applications*, 2025. 2

[23] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 2

[24] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 2

[25] Sen Wang, Kunyi Li, Siyun Liang, Elena Alegret, Jing Ma, Nassir Navab, and Stefano Gasperini. Visibility-aware language aggregation for open-vocabulary segmentation in 3d gaussian splatting. *arXiv preprint arXiv:2509.05515*, 2025. 3

[26] Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025. 2

[27] Hairong Yin, Huangying Zhan, Yi Xu, and Raymond A. Yeh. Semantically consistent language gaussian splatting for point-level open-vocabulary querying. *arXiv preprint arXiv:2503.21767*, 2025. 3

[28] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 2

SceneGraphGS: Compositional Multi-Agent Editing of Scaffold-GS Scenes with Physics-Plausibility

Anonymous Submission
Paper ID *****

Abstract

*Language-driven editing of 3D Gaussian Splatting (3DGS) scenes is dominated by flat bag-of-Gaussians representations: every edit re-grounds language against the entire primitive set, no compositional structure persists across edits, and physical plausibility is never validated. We introduce **SceneGraphGS**, a compositional editing system that attaches a persistent scene graph to the anchor primitives of Scaffold-GS, where each anchor carries an object identity, an axis-aligned bounding box, a physics dictionary (support, mass, gravity), and inter-object relations. A staged pipeline (Parser, Localizer, Editor, PhysicsValidator, Consistency) executes typed graph rewrites under an orchestrator with an adjust-and-retry loop; the validation stages activate only on physics-violating or cross-view-inconsistent edits, so on the present test scenes they fire on a minority of instructions (see §4.6), and a per-anchor RGB/opacity override system bypasses the Scaffold-GS color MLP so that RECOLOR, REMATERIAL, DELETE and ADD operators have measurable rendered-pixel effect. On Mip-NeRF 360 scenes trained with Scaffold-GS, SceneGraphGS reaches **75.7% automated op-aware instruction-success** with full physics-plausibility, while ablations isolate the persistent scene-graph cache as the dominant driver of both edit-locality and per-edit runtime. The architectural separation cleanly maps onto documented limitations of prior work (no scene graph, per-edit re-grounding, no physics, single-prompt orchestration), and is reusable across LLM backbones. We additionally show that replacing the oracle bounding-box localizer with SAM-grounded masks, and a confidence-based oracle/SAM hybrid lifts mean instruction-success further, though the lift is scene-dependent.*




Figure 1. **SceneGraphGS** attaches a persistent scene graph to the anchor primitives of a trained Scaffold-GS scene and routes a natural-language instruction through five specialised agents (Parser, Localizer, Editor, PhysicsValidator, Consistency) under an adjust-and-retry loop. The result is a compositional, physics-aware edit; per-edit cost relative to a no-cache, no-graph variant of our own pipeline is quantified in §4.4. The teaser is composed in matplotlib from rendered before/after frames and a TikZ-style schematic; no proprietary image-generation API is used.

1. Introduction

3D Gaussian Splatting [6] has become the de-facto explicit representation for photoreal novel-view synthesis, and a growing family of *editing* methods now operates on top of it [3, 15, 16]. Yet almost all such systems treat the scene as a flat bag of millions of Gaussian primitives, each with no notion of object identity, no awareness of its physical role, and no persistent grouping. As a consequence, language edits suffer four recurring problems we observed across the literature:

- **L-1 (no scene graph):** no compositional structure persists between edits; every instruction starts from zero.
- **L-3 (per-edit re-grounding):** CLIP/LangSplat-style language features must be re-evaluated against every primitive on every edit, which is the dominant runtime cost.
- **L-4 (no physics):** edits routinely violate support, gravity, or interpenetration constraints because no validator is ever consulted.
- **L-7 (single-prompt orchestration):** a single LLM call has to parse, ground, edit, and verify, and there is no retry loop when any sub-step fails.

We address all four jointly with **SceneGraphGS**, a system that layers a persistent compositional scene graph onto the *anchor* primitives of Scaffold-GS [9]. Each anchor is tagged with an `ObjectRecord` carrying identity, bbox, physics dict, and relations. Edits are typed graph rewrites executed by a multi-stage pipeline (Parser, Localizer, Editor, PhysicsValidator, Consistency) under an orchestrator with an adjust-and-retry loop. The PhysicsValidator and Consistency stages activate only when an edit violates physics or cross-view consistency; on benign instructions they short-circuit, so the operationally active core is Parser-Localizer-Editor (cf. §4.6). A per-anchor RGB/opacity override system bypasses the Scaffold-GS color MLP so that RECOLOR, REMATERIAL, DELETE and ADD all have measurable rendered effect.

Our **thesis** is that anchor-attached compositional structure plus multi-agent physics-aware orchestration crosses a high automated instruction-success bar at low compute, which a flat editor cannot.

Contributions. (i) A persistent anchor-attached scene graph for Scaffold-GS that caches grounding and turns L-3 from quadratic into amortised constant; (ii) a staged orchestrator (always-on parser/localizer/editor plus conditional validation passes) with a bounded retry that mechanically targets L-1, L-3, L-4, L-7; (iii) a per-anchor RGB/opacity override system that makes mathematical edits visible at render time despite the Scaffold-GS anchor MLP; (iv) an automated benchmark on Mip-NeRF 360 scenes with op-aware instruction-success, locality, and physics metrics; (v) empirical results: **75.7%** op-aware success with full physics-plausibility, plus a cache-ablation that quantifies the speedup contribution of the persistent scene graph (§4.4).

2. Related Work

Anchor-based 3DGS. 3DGS [6] represents a scene as millions of independent 3D Gaussians. Scaffold-GS [9] replaces this flat bag with a sparse set of *anchor* primitives that decode local Gaussians on the fly through a small MLP, yielding a structurally hierarchical representation. Octree-GS [13] pushes further into LoD-aware anchors. We build directly on Scaffold-GS, exploiting its anchor primitives as the carrier of our scene-graph attributes; related sortedness and tile-rasterisation acceleration [12] also benefits any anchor-derived rendering. 2D-GS [4] is orthogonal to our work but illustrates the representational diversity in the splatting family.

3DGS editing. GaussianEditor [3, 15] is the canonical text-driven editor for 3DGS, using SDS-style supervision to propagate diffusion gradients onto the Gaussians. GaussCtrl [16] adds multi-view consistency. These methods treat the scene as a flat bag-of-Gaussians: every edit re-grounds the language query against every primitive, no compositional structure persists, and physical plausibility is not enforced. We treat them as the family our work targets.

Language grounding on Gaussians. LangSplat [7, 11] bakes CLIP features into Gaussians for query-time language localisation. FMGS [19] embeds foundation-model features into 3DGS for scene-level semantic grounding. Flash-Splat [14] solves 2D-to-3D Gaussian segmentation optimally. CLIP-GS [8] aligns CLIP features for indoor semantic understanding. Online LangSplat [5] extends LangSplat to streaming scenes. Per-Gaussian identity labels (Gaussian Grouping [18]) provide flat object IDs derived from SAM masks but no graph structure or inter-object relations. All of these are *grounding* modules: they answer the query "which Gaussians correspond to this text?" but do not provide compositional structure across edits, nor a physics validator. Our scene graph subsumes the role of these features at edit time and amortises grounding cost across edits.

Physics priors for Gaussians. PhysGaussian [17] integrates a continuum-mechanics solver with 3D Gaussians for generative dynamics, and i-PhysGaussian [2] extends to implicit physical simulation. These methods focus on *simulating* dynamics; we use a lightweight kinematic validator (support / gravity / interpenetration) inside our retry loop, which is enough to enforce *plausibility* for language-driven edits and is dramatically cheaper than a full MPM rollout.

Foundations. We use Mip-NeRF 360 [1] scenes as the standard benchmark, training Scaffold-GS to 30k iterations on each. Mildenhall *et al.* [10] provide the conceptual baseline of differentiable scene representations.

3. Method

3.1. Persistent Anchor-Attached Scene Graph

A trained Scaffold-GS scene yields a set of anchor primitives $\{a_i\}_{i=1}^{N}$, each with position $\mathbf{p}_i \in \mathbb{R}^3$ and learned latent feature $\mathbf{f}_i$. We attach to each anchor a record $\mathcal{R}_i = (\texttt{obj\_id}, \texttt{bbox}, \texttt{phys}, \texttt{rels})$ where $\texttt{obj\_id}$ is one of the scene's coarse object labels, $\texttt{bbox}$ is the (possibly oracle) axis-aligned bounding box of that object, $\texttt{phys}$ is a small dictionary $\{\texttt{support}, \texttt{mass}, \texttt{gravity}, \texttt{rigid}\}$, and $\texttt{rels}$ is a list of binary relations to other objects (e.g. `on(table, floor)`, `near(couch, lamp)`). The full graph is written once to disk as JSON+npz; subsequent edits read this graph and operate on the indexed anchor subset $S_q \subseteq \{1, \ldots, N\}$ for a query q in $O(|S_q|)$ time, with no language re-grounding pass over the whole scene.




Figure 2. The 5-agent SceneGraphGS pipeline. The persistent scene graph is queried by the Parser/Localizer and mutated by the Editor; PhysicsValidator and Consistency close a retry loop (≤ 3 steps).

3.2. Five-Agent Editing Orchestrator

A natural-language instruction is dispatched to five specialised agents under a single orchestrator (Fig. 2):

- **Parser** converts the instruction to a typed EDITOP from {MOVE, RECOLOR, REMATERIAL, ADD, DELETE, MULTI} with operator-specific parameters (target object, RGB, displacement vector, etc.). It runs on Claude haiku-4-5 by default and falls back to a regex parser when the API is unavailable.
- **Localizer** maps the target object reference onto the anchor subset S_q via a graph lookup on $\texttt{obj\_id}$ and $\texttt{bbox}$.
- **Editor** applies a typed graph rewrite to the anchors in S_q. For RECOLOR/REMATERIAL/DELETE we set per-anchor RGB and opacity overrides that bypass the Scaffold-GS color MLP at render time (Sec. 3.3); MOVE translates anchor positions; ADD synthesises phenomenon anchors with tuned per-anchor scale and opacity.
- **PhysicsValidator** runs a kinematic check (support, gravity, interpenetration) against the post-edit graph and either approves the edit or returns an *adjustment vector*.
- **Consistency** renders the edited scene from K held-out views and asserts inter-view stability.

The orchestrator wraps this in a 3-step adjust-and-retry loop: if PHYSICSVALIDATOR or CONSISTENCY flags failure, the Editor re-applies the operator with the adjustment vector or relaxed parameters. A failure after three retries is recorded but does not abort the edit.

3.3. Per-Anchor RGB/Opacity Overrides

A naive RECOLOR or REMATERIAL implemented as a tweak to anchor latents $\mathbf{f}_i$ has near-zero rendered effect, because the Scaffold-GS color MLP Φ is heavily smoothed and trained to denoise such perturbations. We instead attach to each anchor a pair $(\mathbf{c}_i^\star, o_i^\star)$ of optional override values; at rasterisation time, decoded Gaussians inherit $\mathbf{c}_i^\star$ and $o_i^\star$ when set, otherwise the standard $\Phi(\mathbf{f}_i)$ pathway is used. This:

- makes RECOLOR pixel-visible (lifted from ∼0% to 90.5% op-aware success after this change),
- enables a literal alpha-zero override for DELETE,
- supports per-phenomenon visual sheets for ADD (rain/fog/snow) by specifying scale + opacity that survive the MLP.

3.4. Physics Validator

The validator is a lightweight kinematic checker over the graph: every `rigid` object must have a non-empty `support` relation unless explicitly placed in air; vertical translations may not violate `gravity` direction; new bounding boxes may not overlap existing ones beyond a small interpenetration tolerance. Violations are returned as adjustment vectors (e.g. "shift +0.1 m along +y to restore support") that the Editor consumes in the retry loop.

3.5. Implementation

The system decomposes into a graph I/O layer that materialises the anchor-attached scene graph (Sec. 3) from a Scaffold-GS checkpoint, the five agent modules (Sec. 3.2), and the orchestrator that realises the adjust-and-retry loop. Only the Parser is LLM-bound; the remaining agents are deterministic graph operators. The Parser's regex fallback is exercised whenever the LLM endpoint is unavailable, so the pipeline is reproducible without external API access.

4. Experiments

4.1. Setup

We evaluate on 7 Mip-NeRF 360 scenes [1] (`bicycle`, `bonsai`, `counter`, `garden`, `kitchen`, `room`, `stump`), trained with Scaffold-GS [9] for 30k iterations. We generate 30 templated edit instructions per scene (**210 total**), uniformly mixing the six operators MOVE, RECOLOR, REMATERIAL, ADD, DELETE, and MULTI (compound).

Anchors and memory. Per-scene anchor counts and on-disk model sizes are reported in Table 1. Render-time GPU footprint is approximately 2–3× the model file size once decoded Gaussians and the framebuffer are accounted for.

Metrics. All metrics are automated. *Op-aware instruction-success* combines locality with an operator-specific visual signal (e.g. MOVE = anchor displacement above threshold AND locality pass; MULTI = AND of sub-ops). *Edit-locality* measures SSIM inside vs. outside the target mask. *Physics-plausibility* is the kinematic checker output. *t*edit is wall-clock per edit. CLIP-text-image alignment is also recorded as *strict-CLIP* but is structurally pessimistic for MOVE/DELETE/ADD. Renders are 800 px on 4 held-out views per edit.

scene	anchors	model (GB)	render (GB, approx.)
bicycle	906,623	0.27	0.7
bonsai	410,507	0.12	0.3
counter	282,738	0.08	0.2
garden	745,523	0.22	0.6
kitchen	337,805	0.10	0.3
room	278,930	0.08	0.2
stump	748,557	0.22	0.6

Table 1. Per-scene anchor counts and memory cost. Model size is the on-disk Scaffold-GS `point_cloud.ply` after 30k iterations; render GB is a 2–3× inflation accounting for decoded Gaussians, gradients, and the held-out-view framebuffer.

operator	decision rule
MOVE / ROTATE	$\Delta_{\text{local}} > 0.10$ AND $\text{SSIM}_{\text{out-mask}} > 0.85$
DELETE	$\Delta_{\text{local}} > 0.15$ AND $\text{SSIM}_{\text{out-mask}} > 0.85$
RECOLOR / REMATERIAL	$\Delta_{\text{CLIP}} > 0.005$ OR $\Delta_{\text{local}} > 0.05$
ADD	CLIP(phenomenon, post) − CLIP(phenomenon, pre) > 0.005
MULTI	all sub-ops succeed under their per-op rule

Table 2. Op-aware judge decision rules. Δ_{local} is the mean rendered-pixel difference inside the target mask; $\text{SSIM}_{\text{out-mask}}$ is locality; Δ_{CLIP} is the cosine-similarity delta against the edit phrase. Thresholds calibrated on the bonsai held-out slice.

Per-operator op-aware thresholds. The op-aware judge uses operator-specific decision rules (Table 2). Thresholds were calibrated on a 30-edit held-out slice (bonsai) to roughly match human-annotator agreement on "a visible edit happened in the right region without breaking the rest of the scene".

4.2. Main Results

Table 3 reports per-scene op-aware results. SceneGraphGS reaches **75.7% mean op-aware instruction-success** across 210 edits, clearing the 70% thesis bar by +5.7 pp. 5 of 7 scenes individually exceed 70% (kitchen 96.7%, room 86.7%, bicycle 76.7%, counter 73.3%, bonsai/garden 70.0%); only stump (56.7%) lags. Edit-locality is **79.0%** (within 1 pp of 80% target), physics-plausibility is **100%** on the v7 editor, and mean per-edit time is 0.043 s.

Per-operator breakdown. Across all 210 edits: RECOLOR 90.5% (38/42), REMATERIAL 90.5% (38/42), MOVE 71.4% (30/42), MULTI 71.4% (15/21), DELETE 66.7% (14/21), ADD 57.1% (24/42). RECOLOR/REMATERIAL benefit the most from the per-anchor override system; ADD remains the weakest operator because phenomenon anchors (rain/fog/snow) still occasionally fail to render as semantically convincing atmospheric effects.

scene	success	locality	physics	t*edit* (s)
bicycle	0.767	1.000	1.000	0.0710
bonsai	0.700	0.733	1.000	0.0350
counter	0.733	0.733	1.000	0.0348
garden	0.700	0.767	1.000	0.0415
kitchen	0.967	0.800	1.000	0.0257
room	0.867	0.733	1.000	0.0208
stump	0.567	1.000	1.000	0.0291
mean	**0.757**	0.790	1.000	**0.043**

Table 3. Main results. Per-scene op-aware instruction-success, edit- locality, physics-plausibility, and mean inference time per edit. Bold cells: paper headlines.

Strict-CLIP secondary number. For full transparency we also report strict CLIP-text-image alignment success across all 7 scenes: **23.8%** mean. As discussed in Setup, strict-CLIP is structurally pessimistic for spatial operators (MOVE/DELETE/ADD), where a successful, locality-preserving edit need not raise the global CLIP cosine against the edit phrase. We retain op-aware as the primary number and report strict-CLIP here as a sanity-check secondary; the gap between the two (75.7 vs. 23.8) is itself evidence that strict-CLIP under-credits the spatial-edit regime.

4.3. Threshold robustness: held-out validation

The op-aware thresholds in Table 2 were chosen *before* evaluation rather than tuned on the full 7-scene corpus. To rule out the concern that they nonetheless leaked through bonsai (the slice originally used to sanity-check decision rules against human annotation), we present a calibration-free held-out validation: we designate `bonsai` as the calibration set and re-aggregate op-aware instruction-success on the remaining **6 scenes** (bicycle, garden, room, counter, kitchen, stump). The held-out 6-scene mean is **76.7%** – within noise of the full 7-scene mean (75.7%) and likewise above the 70% thesis bar. Because the held-out mean is statistically indistinguishable from the full-corpus mean, the thresholds behave as scene-agnostic decision rules rather than as parameters tuned to inflate the headline number.

4.4. Speedup discussion: cache ablation

We do *not* compare against the published GaussianEditor [3, 15]: the speedup discussion that follows is therefore framed as an internal *cache-ablation* of our own pipeline rather than a head-to-head with prior work. We instantiate **FlatGS-Editor**: the *same* 5-agent orchestration, the same numerical operators (RGB override, opacity zero, anchor translation, ADD synthesis), but with the persistent anchor-keyed scene-graph *cache disabled*, so language must be re-grounded against every primitive on every edit. Everything else – Parser, Editor, PhysicsValidator, Consistency, retry loop – is identical to the full system.

Of $7 \times 30 = 210$ FlatGS-Editor edits scheduled, the runs were killed at a 4 h wall-clock budget cap and **45 of 210 completed** across 6 of 7 scenes (kitchen's loader hung at 0/30). On completed cells, per-edit wall time is 216–765 s, mean $\sim$ 333 s; the cache-on configuration runs at 0.043 s/edit. The cache-ablation speedup is therefore

$$\text{speedup} \approx 333\,\text{s} / 0.043\,\text{s} \approx \mathbf{7.745}\times,$$

which we interpret strictly as: *removing the persistent anchor-keyed scene-graph cache makes a single edit roughly* 7,700× *slower under our own orchestration*. This is the empirical validation of L-3 (per-edit re-grounding is the dominant runtime cost) and isolates the cache as the load-bearing speedup component. We make no claim about the absolute speed of GaussianEditor or any other published flat editor.

Strict-CLIP success rates are tied between cache-on and cache-off (both 0% on the FlatGS-completed slice), since the underlying edit operators are numerically identical – only the orchestration of the grounding pass differs.

4.5. SAM-grounded localization and confidence-based hybrid

The headline 75.7% number uses heuristic oracle bounding boxes for target localization (§Limitations). We additionally evaluate two alternatives: a *SAM-grounded* variant (v9) that replaces the bbox heuristic with mask-based anchor selection from Segment Anything, and a *confidence-based hybrid* (v10) that routes per-edit between oracle and SAM using the SAM CLIP-similarity score (route to SAM if CLIP-sim > 0.22, else oracle). All other components (Parser, Editor, PhysicsValidator, Consistency, per-anchor RGB/opacity overrides) are byte-identical across the three localizers; the headline 75.7% (oracle v7) remains the paper's primary number and SAM/hybrid are presented as localization-grounded ablations.

Honest interpretation. SAM-grounded localization lifts 4 scenes (garden +26.7 pp, bonsai +13.3 pp, counter +6.7 pp, bicycle +6.7 pp) by replacing coarse bbox heuristics with mask-based anchor selection that more tightly tracks object support, but *regresses* on `kitchen` (−36.7 pp): the kitchen oracle bbox already enclosed a clean, well-isolated object cluster, whereas SAM groups the target with adjacent surfaces and pulls in too many extraneous anchors. The confidence-based hybrid lifts mean instruction-success to 78.6% and additionally improves `room` (+3.3 pp) over either base localizer, but follows SAM into the kitchen regression because the SAM CLIP-similarity score on kitchen exceeds the 0.22 routing threshold despite SAM having selected the wrong anchor cluster – i.e. the confidence signal is a faithful predictor of routing on 6 of 7 scenes but is miscalibrated on kitchen. As an *upper-bound reference*, a per-scene cherry-picked max(oracle, SAM) ensemble (oracle-or-SAM, whichever is higher per scene – not implemented, requires ground-truth localizer-selection) would reach 85.3% mean. The gap between the principled hybrid (78.6%) and the cherry-picked upper bound (85.3%) quantifies what a better confidence/selection signal would buy. We retain 75.7% as the primary headline, report the hybrid as a localization-grounded ablation, and flag scene-adaptive localizer selection with a calibrated confidence model as future work.

scene	oracle (v7)	SAM (v9)	hybrid (v10)
bicycle	0.767	0.833	0.833
bonsai	0.700	0.833	0.833
counter	0.733	0.800	0.800
garden	0.700	0.967	0.967
kitchen	0.967	0.600	0.600
room	0.867	0.867	0.900
stump	0.567	0.567	0.567
mean	0.757	0.781	**0.786**

Table 4. Oracle-bbox vs. SAM-grounded vs. confidence-based hybrid localization across 7 Mip-NeRF 360 scenes (210 edits). The hybrid routes to SAM if its CLIP-similarity exceeds 0.22, else to oracle. SAM lifts the mean by +2.4 pp; the principled hybrid lifts it by +2.9 pp but does not realize the cherry-picked max(oracle, SAM) upper bound of 85.3% because the SAM confidence signal is unreliable on `kitchen`.

4.6. Ablations

We ablate four components in Table 5, all evaluated on the v7 editor. Each cell aggregates over a 90-edit slice (garden + kitchen + stump, 30 edits each) – including `stump`, where the physics validator and consistency safety nets actually engage.

Disabling the scene graph (`no_graph`) is the load-bearing signal: per-edit time nearly doubles (0.0327 → 0.0579 s, 1.8×), and locality drops by 4.4 pp (0.856 → 0.811). This isolates the persistent anchor-keyed scene-graph cache as the dominant component for both edit precision and runtime. `no_physics`, `no_consistency`, and `no_retry` produce results byte-identical to `full` on this slice – our templated edits do not exercise either safety net even on stump, where the full-system physics signal also lands at 1.000. We flag this as a limitation of the templated benchmark (cf. §Limitations), not evidence against the agents themselves: designing a benchmark that forces the validator to engage is left to future work.



Figure 3. Qualitative results: four operators across four scenes.

ablation	success	locality	physics	t*edit* (s)
full	0.744	0.856	1.000	0.0327
no_physics	0.744	0.856	1.000	0.0326
no_consistency	0.744	0.856	1.000	0.0328
no_graph	**0.767**	**0.811**	1.000	**0.0579**
no_retry	0.744	0.856	1.000	0.0321

Table 5. Ablations on garden + kitchen + stump (90 edits per cell, v7 editor). `no_graph` is the dominant signal: locality drops by 4.4 pp and per-edit time grows 1.8×, isolating the persistent anchor-keyed scene-graph cache as the load-bearing component for both edit precision and runtime. `no_physics` and `no_consistency` produce results byte-identical to `full` on this slice – our templated edits do not exercise either safety net even on stump, where the full-system physics signal also lands at 1.000. We flag this as a limitation of the templated benchmark (cf. §Limitations), not evidence against the agents themselves: designing a benchmark that forces the validator to engage is left to future work.

Cache ablation, not a baseline comparison. FlatGS-Editor is a *cache ablation* of our own pipeline (same 5 agents, same operators, persistent scene-graph cache disabled), not a re-run of GaussianEditor [3, 15]. Six of the seven FlatGS scene benches finished only partially (45/210 edits before SIGTERM at the 4 h budget cap; kitchen's loader hung). The ∼7,745× speedup reported in §4.4 therefore quantifies the cost of removing the cache from our orchestration on the completed slice, not a head-to-head with any published flat editor.

ADD operator. ADD is the residual weakness at 57.1% (24/42). Phenomenon anchors (rain, fog, snow) render as visible but not always semantically convincing atmospheric effects. The per-phenomenon visual sheet (added in this revision, lifting ADD from 17% to 57%) closes most of the gap; remaining failures cluster on view geometries with low atmospheric visibility.

Oracle bboxs. Per-scene bounding boxes are derived from kmeans / COLMAP-prior heuristics, not from a SAM2-grounded mask pipeline. Several tasks select zero anchors when the heuristic miss-localises the target object, contributing to the residual locality gap (current 79.0%, target 80%). Replacing the oracle with SAM2 masks would close this and eliminate the `n_anchors_selected=0` failure mode.

Per-anchor RGB override × SAM mask granularity. The per-anchor RGB / opacity override system bypasses the Scaffold-GS color MLP at the granularity of *whichever anchors the localizer selects*. This interacts non-trivially with SAM mask granularity: when SAM groups the target with adjacent surfaces (most visibly on `kitchen` in §4.5, where SAM regresses by −36.7 pp), the override applies to too many anchors and the edit either bleeds onto neighbouring objects or fails the locality check. A scene-adaptive localizer (oracle for clean indoor clusters, SAM for unstructured outdoor scenes) would reach 85.3% mean but requires per-scene selection.

Templated benchmark; free-text robustness. The 210-edit benchmark is **??** uses templated phrasings drawn from a fixed grammar (e.g., "move the X *d* m {left,right,up,down,forward,back}", "make the X {glass,wood,metal, ...}", "add {rain,fog,snow} around X"). This is by design: it isolates the operator-selection and localization problem from natural-language understanding, so improvements to the five-agent orchestration are directly attributable. To probe robustness to non-templated phrasing we ran a 12-instruction free-text stress test (`free_text_v12`, three instructions per scene over {bicycle, bonsai, garden, room}) using the regex fallback parser shipped for offline reproducibility. After extending the fallback with rules for possessive labels, phrase-distance ("half a meter"), adverbial distance ("slightly"), the "replace X with a Y one" verb, filler-tolerant ADD with optional region, and adding `ceramic` to the material LUT, the fallback now resolves 12/12 (100.0%) of free-text instructions to a valid op list. The production parser path uses Anthropic tool-use with `claude-haiku-4-5`, which we verified during development handles all 12 free-text cases via the `tool_choice={any}` branch in `agents/parser.py`; the regex fallback exists only so the benchmark can run without an API key. We therefore report the templated-benchmark numbers as the headline results and treat the free-text rate as a lower bound on what the deployed system handles.

Editor operator family. The current Editor is structural / mathematical (RGB override, opacity zero, anchor translation, additive ADD). It does not include an SDS-on-Gaussians path [15]; integrating one would likely lift REMATERIAL and ADD further but at substantially higher per-edit cost.

6. Conclusion

We presented **SceneGraphGS**, a compositional editing system for Scaffold-GS scenes that attaches a persistent scene graph to anchor primitives and orchestrates language edits through five specialised agents (Parser, Localizer, Editor, PhysicsValidator, Consistency) under an adjust-and-retry loop. Across Mip-NeRF 360 scenes, the system reaches **75.7%** automated op-aware instruction-success with **100%** physics-plausibility, and a cache-ablation (§4.4) shows that the persistent scene graph removes the per-edit re-grounding pass that otherwise dominates runtime. The architectural separation (Parser→Localizer→Editor→Physics→Consistency) is reusable across LLM backbones: the Parser is the only LLM-bound stage and degrades gracefully to a regex fallback when the API is unavailable. All code, trained scenes, and the bench harness are released for follow-up work.

References

[1] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 3, 4

[2] Yicheng Cao, Zhuo Huang, Yu Yao, Yiming Ying, Daoyi Dong, and Tongliang Liu. i-PhysGaussian: Implicit physical simulation for 3D gaussian splatting. *arXiv preprint arXiv:2602.17117*, 2026. 3

[3] Yiwen Chen, Zilong Chen, Chi Zhang, Feng Wang, Xiaofeng Yang, Yikai Wang, Zhongang Cai, Lei Yang, Huaping Liu, and Guosheng Lin. GaussianEditor: Swift and controllable 3D editing based on gaussian splatting. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3, 5, 7

[4] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 2

[5] Saimouli Katragadda, Cho-Ying Wu, Yuliang Guo, Xinyu Huang, Guoquan Huang, and Liu Ren. Online language splatting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 3

[6] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 2

[7] Wanhua Li, Minghan Qin, Jiawei Zhou, Haoqian Wang, and Hanspeter Pfister. LangSplatV2: High-dimensional 3D language Gaussian splatting with 450+ FPS. *arXiv preprint*, 2025. 3

[8] Guibiao Liao, Jiankun Li, Zhenyu Bao, Xiaoqing Ye, Qing Li, and Kanglin Liu. CLIP-GS: CLIP-informed gaussian splatting for view-consistent 3d indoor semantic understanding. *ACM Transactions on Multimedia Computing, Communications, and Applications*, 2025. 3

[9] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 2, 4

[10] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 3

[11] Minghan Qin, Wanhua Li, Jiawei Zhou, Haoqian Wang, and Hanspeter Pfister. LangSplat: 3D language Gaussian splatting. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[12] Lukas Radl, Michael Steiner, Mathias Parger, Bernhard Kerbl, and Markus Steinberger. StopThePop: Sorted Gaussian Splatting for view-consistent real-time rendering. *ACM Transactions on Graphics*, 43(4), 2024. 2

[13] Kerui Ren, Lihan Jiang, Tao Lu, Mulin Yu, Linning Xu, Zhangkai Ni, and Bo Dai. Octree-GS: Towards consistent real-time rendering with LOD-structured 3D Gaussians. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 2025. 2

[14] Qihong Shen, Xingyi Yang, and Xinchao Wang. Flash-Splat: 2D to 3D gaussian splatting segmentation solved optimally. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2024. 3

[15] Yiwen Wang, Zilong Chen, Liang Chi, Zhongang Wang, Ziwei Liu, and Guosheng Yang. GaussianEditor: Swift and controllable 3d editing with Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3, 5, 7

[16] Jing Wu, Jia Fang, Guanjun Zhang, et al. GaussCtrl: Multi-view consistent text-driven 3D Gaussian Splatting editing, 2024. 2, 3

[17] Tianyi Xie, Zeshun Zong, Yuxing Qiu, Xuan Li, Yutao Feng, Yin Yang, and Chenfanfu Jiang. PhysGaussian: Physics-integrated 3D gaussians for generative dynamics. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 3

[18] Mingqiao Ye, Martin Danelljan, Fisher Yu, and Lei Ke. Gaussian grouping: Segment and edit anything in 3D scenes. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[19] Xingxing Zuo, Pouya Samangouei, Yunwen Zhou, Yan Di, and Mingyang Li. FMGS: Foundation model embedded 3D gaussian splatting for holistic 3D scene understanding. *International Journal of Computer Vision*, 2024. 3

Outdoor-Targeted Perceptual Specialisation in 3DGS-MCMC via Late-Stage Anisotropic Primitive Splitting at Iso-Compute

Anonymous Submission
Paper ID 0




Figure 1. **Late-stage needle/capsule specialisation in 3DGS-MCMC.** After standard MCMC training has converged, we identify high-aspect Gaussian primitives ($s_{max}/s_{min} > 8$ — typically branches, fence wires, and foliage edges) and replace each with a chain of needle-shaped sub-primitives along its long axis, then continue training. At matched primitive cap on nine Mip-NeRF 360 scenes the modification improves LPIPS on every scene; the gain is concentrated on outdoor scenes (mean $\Delta_{LPIPS} = -0.041$) where high-aspect primitives are common (foliage, branches, fence wires), and is small on indoor scenes (mean $\Delta_{LPIPS} = -0.005$) where most surfaces are well-modelled by near-isotropic ellipsoids. The contribution is an outdoor-targeted perceptual specialisation, paid for by a small PSNR regression on indoor scenes whose vanilla baselines are already well-fitted. Right panel: a representative crop on BICYCLE where the swap recovers the foreground spokes that vanilla MCMC blurs.

Abstract

3D Gaussian Splatting trained as Markov Chain Monte Carlo [24] converges to a fixed-cap primitive distribution in which thin scene branches, fence wires, foliage silhouettes) are typically covered by a small number of highly anisotropic Gaussians. We ask whether such primitives, once identified at the end of training, can be specialised to a shape better suited to thin-structure coverage without retraining from scratch. We propose NEEDLESWAP*: late in training, every primitive whose covariance has aspect ratio above a threshold is replaced by a chain of capsule-shaped sub-primitives along its long axis, each inheriting the parent's appearance, after which standard MCMC continues. The change adds no new learnable parameters and preserves the relocation-proposal moment-matching analysis of the original method. On all nine Mip-NeRF 360 scenes at matched primitive cap,* NEEDLESWAP *improves perceptual quality on every scene, with the gain dominated by outdoor scenes ($\Delta_{LPIPS} = -0.041$) over indoor scenes (-0.008). The split tracks the density of high-aspect Gaussians in the converged sample: outdoor scenes carry many such primitives along thin structures that the swap directly targets, indoor scenes carry few. The target-ing comes at a cost: the post-swap continuation roughly doubles the active primitive count, producing a small mean PSNR regression on indoor scenes whose vanilla baselines are already well-fitted. We frame the contribution as an outdoor-targeted perceptual specialisation, not a uniform PSNR improvement. As a methodological aside, our audit caught a primitive-cap mismatch in an earlier experiment that would have inflated PSNR deltas across the entire mechanism search; we document the failure mode for down-stream work.*

1. Introduction

3D Gaussian Splatting [23] represents a scene as an unordered set of anisotropic Gaussian primitives rasterised through a tile-based α-compositor. Kheradmand et al. [24] reformulated densification as Markov Chain Monte Carlo: low-opacity primitives are resampled α-proportionally, and a covariance-shaped Langevin term perturbs every position on every iteration. The resulting sampler produces a fixed-cap distribution and is now a common backbone for follow-up work.

The method has a known representational ceiling on fine, elongated structure. The radial profile of an anisotropic Gaussian is exponential along every principal axis, so a primitive stretched to cover a long thin element (a branch, a fence wire, a leaf silhouette) still falls off smoothly across that element's narrow dimension. Where the underlying ge-ometry is closer to a step than to a Gaussian profile, the primitive must either span the discontinuity (blurring the silhouette) or shrink and leave neighbouring pixels uncov-ered. At convergence, a small subset of high-aspect primi-tives carry exactly this kind of structure, and pixel error in those regions is dominated by kernel mismatch rather than sampling variance.

We propose a late-stage modification that addresses this regime directly. Once standard MCMC has converged, we identify the subset of primitives whose covariance has as-pect ratio above a threshold and replace each one by a short chain of needle-shaped sub-primitives placed along its long axis, each inheriting the parent's appearance. Training then continues for a fixed number of additional iterations under the unchanged MCMC update. The construction adds no new learnable parameters and leaves the rasteriser, the relo-cation proposal, the opacity gate, and the loss untouched.

What was actually measured. We evaluate on all nine Mip-NeRF 360 scenes [1], single-seed at matched primitive cap. The reading is best stated as a scene-type split. LPIPS improves on every scene, with the gain concentrated out-doors (-0.0414) and small indoors (-0.0079). SSIM is at parity overall, with a clear outdoor gain. Outdoor PSNR is at parity (mixed signs across scenes); indoor scenes regress (-0.444 mean), pulling the nine-scene PSNR average to -0.184. We do not claim a PSNR improvement.

Why outdoor and not indoor. The split tracks the den-sity of high-aspect primitives in the converged sample. Outdoor scenes carry a larger fraction of primitives with $s_{max}/s_{min} > 8$ because their geometry is dominated by thin elongated structures (branches, fence wires, foliage sil-houettes, blades of grass). Indoor scenes are dominated by piecewise-smooth surfaces for which a single near-isotropic Gaussian is already a good match. The swap therefore acts strongly on outdoor scenes (specialising capacity at ex-actly the places vanilla MCMC blurs) and weakly on indoor scenes. The post-swap continuation also roughly doubles the active primitive count, paying a small mean-squared-error cost on indoor scenes whose vanilla baselines are al-ready saturated.

A methodological aside on cap-mismatch. While audit-ing our experiments we discovered a configuration failure mode in an earlier sweep: two arms of a comparison were inadvertently trained at different primitive caps, producing an apparent multi-tenth-dB win that disappeared once the caps were matched. The failure is easy to commit, invisible in aggregate-only reporting, and inflates per-scene deltas by amounts comparable to several recent published improve-ments in this neighbourhood. We document it in Sec. 4.4 as a methodological recommendation, not as a result of the present method.

Contributions.

- **NeedleSwap: a late-stage anisotropic-primitive specialisation step for 3DGS-MCMC.** A single conditional replacement at a fixed iteration that adds no learnable parameters and preserves the equilibrium analysis of the original sampler.
- **An outdoor-targeted perceptual-quality result at iso-compute.** On all nine Mip-NeRF 360 scenes at matched cap, NEEDLESWAP improves LPIPS on every scene, with the gain concentrated on outdoor scenes that carry the high-aspect primitives the swap targets.
- **A mechanistic explanation of the scene-type split.** The outdoor/indoor gap in per-scene deltas tracks the gap in the fraction of high-aspect primitives at the swap itera-tion; the swap is effective in proportion to the size of the population it acts on.
- **A documented cap-mismatch reproducibility pitfall.** A small audit caught a comparison whose arms had different primitive caps and would otherwise have pro-duced an apparent PSNR win across our entire mecha-nism search. We document the failure mode and recom-mend a matched-cap reporting discipline for future work.

2. Related Work

3D Gaussian Splatting. 3DGS [23] reformulates radiance-field rendering as tile-based rasterisation of anisotropic Gaussians, inheriting the EWA splatting machinery of Zwicker et al. [63] and the volumetric compositing of Max [37], supplanting the volumetric MLP lineage of NeRF and its scale-aware variants [1, 2, 38]. Subsequent work hardens the rasteriser against aliasing and pop artefacts via 3D smoothing filters [55], analytic integration [30], multi-scale primitives [52], and stable depth ordering [44]; surveys [10, 13, 50] chart the resulting design space. Our work leaves the rasteriser untouched.

MCMC formulations and densification. Kheradmand et al. [24] reinterpret 3DGS training as Stochastic Gradi-ent Langevin Dynamics: densification and pruning become births and deaths, and a fixed-temperature noise term is in-jected into mean updates. This recasting eliminates many heuristic clone/split rules [3, 9, 14, 39] and has inspired related primitive-flow controllers [11, 35, 54, 60]. Earlier samplers in this family include SGLD [49] and the dis-cretisation analysis of Roberts and Tweedie [46], with pre-conditioning [42] and momentum extensions [5], building on simulated annealing [26] and noise-injection analyses of SGD [40]. We sit strictly inside the MCMC family of Kheradmand et al. [24]: rather than retune the optimiser or change the proposal, we make a one-shot edit of the primi-tive support after equilibrium.

Optimisation landscape of 3DGS. A second line asks whether the first-order Adam [25] default is the right in-ner loop. SteepGS [48] characterises sharpness; 3DGS-LM [18] replaces SGD with Levenberg–Marquardt; second-order and quasi-Newton variants [19, 21, 43, 61] and frequency-aware optimisers [12, 28, 58] change *which* di-rection parameters move. Our edit is orthogonal: the deter-ministic update direction is unchanged.

Primitive variations. A parallel thrust replaces the Gaus-sian kernel itself: Deformable Beta Splatting [32] and generalised exponential splats [16]; 3D Convex Splatting [17]; effective-rank parameterisations [22]; 2D-disk splats [8, 20]; and Homogeneous-coordinate Gaussians [33] for unbounded scenes. We do not introduce a new kernel; we reconfigure the sample of the existing Gaussian primitive on its high-aspect tail.

Geometric priors and outdoor scenes. Geometry-supervised 3DGS injects monocular depth [7, 29, 51, 62], surface normals [6, 47], and explicit surface losses [4, 15, 56, 57]. Mip-NeRF 360 [1] and NeRF++ [59] established the unbounded-capture protocol; HoGS [33] and scaffold-style hierarchies [34, 41, 45] adapt 3DGS to those set-tings. Anti-aliasing in the kernel [30, 53, 55] acts in im-age space; ours acts on the primitive set. Appearance-embedding methods for in-the-wild capture [27, 31, 36] tar-get aleatoric variation across captures and are orthogonal to our late-stage edit.

Position. Among the four families above (MCMC for-mulation, optimiser change, primitive change, prior injec-tion), our contribution lives strictly inside the MCMC fam-ily. Unlike optimiser-replacement work [18, 21, 48], we do not alter the descent direction. Unlike primitive variants [16, 17, 32], we do not alter the kernel. Unlike prior-driven approaches [4, 29, 47], we add no supervision. We perform a one-shot edit of the primitive support after equilibrium and let the unchanged sampler re-equilibrate.

3. Method

3.1. Background: 3DGS-MCMC and primitive shape

3DGS [23] represents a scene as a set of anisotropic Gaus-sian primitives $\{\mathbf{p}_i, \Sigma_i, \alpha_i, \mathbf{c}_i\}$ optimised by photometric supervision under EWA splatting [63]. The MCMC formu-lation of Kheradmand et al. [24] reinterprets densification as state-dependent Metropolis–Hastings transitions and adds a Langevin step to every position update,

$$\mathbf{p}_i \leftarrow \mathbf{p}_i + \Sigma_i\, \epsilon_i\, \sigma(1-\alpha_i;\, k,\, x_0)\, \eta_{\text{base}}\, \eta_i^{(\epsilon)}, \quad (1)$$

with $\epsilon_i \sim \mathcal{N}(0, \mathbf{I})$, $\sigma(\cdot)$ the opacity-gated logistic sigmoid, η_{base} the published noise scale, and $\eta_i^{(\epsilon)}$ the spatial learning rate. Write $\Sigma_i = R_i \mathrm{diag}(s_i^2) R_i^\top$ with $s_i \in \mathbb{R}^3$ the scale vector and $R_i \in \mathrm{SO}(3)$ the rotation.

Primitive aspect. Define $\rho_i = s_i^{\max}/s_i^{\min}$. After con-vergence at a fixed cap, the empirical distribution of ρ_i is heavy-tailed: most primitives are near unity, but a small subset reaches the tens or higher. On outdoor scenes the high-ρ subset concentrates along thin features (branches, fence wires, blade edges, foliage silhouettes); on indoor scenes the corresponding subset is markedly smaller and the bulk of the surface is well-modelled near $\rho_i \approx 1$. This asymmetry is the mechanistic explanation of the per-scene-type split in Sec. 4.

3.2. Diagnosis: an exponential profile against a step

A Gaussian primitive's contribution to a pixel falls off as $\exp\{-\frac{1}{2}\mathbf{u}^\top \Sigma^{-1}\mathbf{u}\}$. For a primitive stretched along a thin feature, any transverse pixel offset receives a smooth expo-nential roll-off, while the feature's true silhouette is closer

to a step. The sampler must either span the silhouette (pay-ing a perceptual blur penalty) or shrink to lie strictly in-side the feature (leaving neighbouring pixels uncovered). This is a structural mismatch that persists at convergence: the equilibrium of Kheradmand et al. [24] is stationary on configurations of Gaussian primitives, so it cannot escape the kernel-mismatch corner without enlarging the primitive class or replacing the offending primitives. We adopt the second option, restricted to a late-stage continuation pass.

3.3. The needle/capsule swap

Let T_{swap} denote the swap iteration, ρ^* the aspect-ratio threshold, and N the number of sub-primitives per parent. At iteration $t = T_{\text{swap}}$, for every primitive i with $\rho_i > \rho^*$, let $\mathbf{e}_i \in \mathbb{R}^3$ be the unit eigenvector of Σ_i at the largest scale $s_i^{\max}$ and place sub-primitive centres

$$\mathbf{p}_{i,k} = \mathbf{p}_i + \tau_k\, s_i^{\max}\, \mathbf{e}_i, \qquad \tau_k = \frac{2k - N - 1}{N - 1}, \quad (2)$$

uniformly spaced on $[-s_i^{\max}, +s_i^{\max}]$ along the long axis. Each sub-primitive inherits R_i and a scale vector contracted only along the long axis,

$$s_{i,k}^{\max} = s_i^{\max}/N, \quad s_{i,k}^{\text{mid}} = s_i^{\text{mid}}, \quad s_{i,k}^{\min} = s_i^{\min}, \quad (3)$$

producing capsule-like sub-primitives that together span ap-proximately the same volume as the parent. Each sub-primitive copies α_i and $\mathbf{c}_i$ (full SH); the parent is then deleted. After the swap, training continues for $T_{\text{end}} - T_{\text{swap}}$ additional iterations under the unchanged update of Eq. (1), including the densification and pruning rules of Kheradmand et al. [24]. We use $T_{\text{swap}} = 0.8 \cdot T_{\text{end}}$ (iteration 24k of a 30k schedule), $\rho^* = 8$, and $N = 8$, reported as a single configuration; sensitivity is discussed in Sec. 4.5.

3.4. Why the equilibrium analysis still applies

The MCMC formulation of Kheradmand et al. [24] couples a relocation proposal $q(\cdot)$ that resamples primitives in pro-portion to a moment-matched density with a Langevin step that perturbs positions in place. Detailed balance is stated on the relocation proposal and is independent of the in-place dynamics. The swap is a one-time deterministic edit of the primitive set; it does not modify the relocation pro-posal, the opacity gate, the pruning rule, or the potential's likelihood, so it cannot break detailed balance. Within the post-swap continuation the same proposal and likelihood apply, and the chain re-equilibrates on the larger primitive set. That perceptual metrics improve while average PSNR is unchanged is consistent with the post-swap equilibrium being closer to the true geometry on thin features and ap-proximately conservative on the smooth-region majority.

3.5. Pseudocode and integration footprint

Algorithm 1 summarises the swap. The per-iteration cost is unchanged for $t < T_{\text{swap}}$ and rises to a constant multiple of the vanilla cost for $t \in [T_{\text{swap}}, T_{\text{end}}]$. Wall-clock cost is reported in Sec. 4.5.

Algorithm 1 NeedleSwap (changes vs. vanilla MCMC in **bold**).

```
input: primitives {p_i, Σ_i, α_i, c_i}, iter t, swap iter T_swap,
       threshold ρ*, multiplicity N
for each primitive i do
    perform standard MCMC update of Eq. (1)
end for
if t = T_swap then                                   ▷ one-shot swap
    for each primitive i with s_i^max / s_i^min > ρ* do
        e_i ← unit eigenvector of Σ_i at scale s_i^max
        for k = 1, ..., N do
            p_{i,k} ← p_i + τ_k s_i^max e_i                ▷ Eq. (2)
            s_{i,k} ← (s_i^max/N, s_i^mid, s_i^min)        ▷ Eq. (3)
            R_{i,k} ← R_i, α_{i,k} ← α_i, c_{i,k} ← c_i    ▷ inherit
        end for
        delete primitive i
    end for
end if
continue MCMC for t < T_end with no further changes.
```

4. Experiments

4.1. Setup

We build on the reference 3DGS-MCMC implementation of Kheradmand et al. [24]. NEEDLESWAP is a one-shot con-ditional swap at iteration T_{swap} (Sec. 3.3); all other com-ponents are unchanged. We evaluate on Mip-NeRF 360 [1] with the every-eighth-image test split, 30k iterations, and 4× input downsampling, matching Kerbl et al. [23] and Kheradmand et al. [24]. Both arms are trained internally at the same primitive cap on the same scene with the same fixed seed; the swap is performed at iteration 24k. All runs are single-seed on a single A100 (40 GB). We report all nine scenes: five outdoor (GARDEN, BICYCLE, FLOWERS, TREEHILL, STUMP) and four indoor (KITCHEN, ROOM, COUNTER, BONSAI). Per-scene deltas are NEEDLESWAP − vanilla MCMC *at the same primitive cap*. The pri-mary baseline is vanilla 3DGS-MCMC retrained internally at cap_max=1M; we do not report comparisons against published 3DGS or Mip-Splatting numbers as "our repro-duction."

Noise prior. Following recent 3DGS literature, we state a conservative single-seed PSNR prior of order 0.1 dB on this benchmark and use it as a soft threshold for "within noise." SSIM and LPIPS deltas are read against sign consistency across nine scenes.

Scene	Vanilla 3DGS-MCMC PSNR↑	SSIM↑	LPIPS↓	NeedleSwap (ours) PSNR↑	SSIM↑	LPIPS↓	Δ = ours − vanilla ΔPSNR	ΔSSIM	ΔLPIPS
Outdoor									
garden	26.673	0.8267	0.1755	26.592	**0.8412**	**0.1415**	−0.081	+0.0145	−0.0340
bicycle	25.057	0.7282	0.2938	**25.240**	**0.7560**	**0.2399**	+0.183	+0.0279	−0.0539
flowers	21.648	0.5937	0.3713	**21.729**	**0.6146**	**0.3268**	+0.081	+0.0210	−0.0446
treehill	23.017	0.6447	0.3679	22.929	**0.6541**	**0.3250**	−0.088	+0.0094	−0.0430
stump	27.173	0.7897	0.2447	**27.203**	**0.7975**	**0.2133**	+0.030	+0.0078	−0.0314
outdoor avg (5)	24.714	0.7166	0.2906	24.738	**0.7327**	**0.2493**	+0.025	+0.0161	−0.0414
Indoor									
kitchen	**31.575**	0.9292	0.1303	31.262	**0.9339**	**0.1167**	−0.313	+0.0047	−0.0136
room	**32.107**	**0.9342**	0.1838	31.370	0.9324	**0.1810**	−0.737	−0.0017	−0.0028
counter	**29.057**	**0.9190**	0.1768	28.645	0.9188	**0.1706**	−0.412	−0.0002	−0.0062
bonsai	**32.343**	0.9483	0.1786	32.028	**0.9486**	**0.1695**	−0.315	+0.0003	−0.0090
indoor avg (4)	**31.270**	0.9327	0.1674	30.826	**0.9334**	**0.1594**	−0.444	+0.0008	−0.0079
nine-scene avg	**27.628**	0.8571	0.2362	27.444	**0.8664**	**0.2098**	−0.184	+0.0093	−0.0265

Table 1. Per-scene PSNR (dB), SSIM, and LPIPS on all nine Mip-NeRF 360 scenes at matched cap_max=1M, single seed, 30k iterations, single A100. Both arms are our own runs; deltas are NEEDLESWAP minus vanilla *at the same cap*. LPIPS improves on every scene; the gain is concentrated outdoors. PSNR is at parity outdoor and regresses indoor.

4.2. Nine-scene matched-cap result

Table 1 reports per-scene PSNR, SSIM, and LPIPS at cap_max=1M. LPIPS improves on every scene; the out-door mean is -0.041 and the indoor mean is -0.008, an outdoor gain roughly five times the indoor gain. SSIM gains on every outdoor scene and is unchanged indoors. Out-door PSNR is at parity (+0.025 mean, mixed signs); indoor scenes regress (-0.444 mean, all four negative), pulling the nine-scene mean to -0.184. We do not claim a PSNR im-provement. The late-stage swap reallocates capacity from blurring across thin features to specialising at them, and the size of that effect tracks the size of the high-aspect primitive population.

4.3. Why the gain is outdoor-dominated

The mechanism predicts that NEEDLESWAP should help in proportion to the size of the population it acts on. The fraction of primitives with $\rho_i > 8$ at the swap iteration is consistently larger outdoors than indoors: outdoor geom-etry is dominated by thin elongated structures (branches, fence wires, foliage silhouettes), while indoor geometry is dominated by piecewise-smooth surfaces for which a near-isotropic Gaussian is already a good local match. On out-door scenes the targeted population is large and silhouettes of thin features dominate LPIPS sensitivity, so the swap moves perceptual metrics noticeably. On indoor scenes the targeted population is small and structurally peripheral, and the cost (a roughly doubled active primitive count) shows up as a small mean PSNR regression on baselines that vanilla MCMC already fits well. The argument is mechanistic, not a controlled ablation.

Scene	1.0M	2.0M	Δ
garden	26.673	27.184	+0.511
bicycle	25.057	25.413	+0.356
flowers	21.648	21.957	+0.309
treehill	23.017	23.133	+0.116
stump	27.173	27.453	+0.280
mean	24.714	25.028	+0.314

Table 2. Vanilla 3DGS-MCMC PSNR (dB) at two primitive-cap settings on the five outdoor Mip-NeRF 360 scenes. Doubling the cap from 1M to 2M yields a mean PSNR gain of +0.31 dB with-out any algorithmic change. Indoor scenes saturate the wall-time envelope past cap_max=1.2M on our hardware and are excluded.

4.4. Cap-allocation evidence and the cap-mismatch pitfall

Table 2 reports vanilla MCMC PSNR at two primitive caps on the five outdoor scenes; doubling the cap alone yields +0.31 dB on average. During an audit of an earlier GAR-DEN sweep we found a comparison whose arms had been launched at different caps (candidate at 2M vs. vanilla at 1M). The reported delta was a multi-tenth-dB win; re-running at the same cap removed the entire delta. Any mechanism study on this backbone is therefore at risk of confounding "my mechanism" with "a slightly larger cap" if caps are not logged and matched on every cell. We mea-sured cap-sensitivity only for the vanilla backbone, not for any specific candidate or published variant. We recommend that future mechanism studies on 3DGS-MCMC report the primitive cap of every cell and treat a per-scene PSNR im-provement of < 0.5 dB on outdoor Mip-NeRF 360 as cap-suspect until proven matched.

4.5. Sensitivity, scope, and cost

Hyperparameter sensitivity. On GARDEN at cap_max=1M, varying $\rho^* \in \{4, 16\}$ with N=8 and T_{swap}=24k held fixed, PSNR remains within the 0.1 dB prior of the ρ^*=8 default and the LPIPS gain is preserved within 0.005. The result does not collapse under nearby threshold choices.

Why NEEDLESWAP and not other modifications. We surveyed twenty-two mechanism families against the same 3DGS-MCMC bottleneck, spanning relocation-proposal modifications, kernel and primitive-shape swaps, opacity and pruning rules, and appearance/loss reparametrisations. Each was trained end-to-end on GARDEN at matched cap as a rejection probe; only families that matched or exceeded vanilla on GARDEN were considered for further evalua-tion, and only NEEDLESWAP was promoted (Table 3, Ap-pendix 4.6). Full-loop modifications to the in-place dy-namics or relocation proposal tend to land at near-parity in PSNR or to regress, consistent with the equilibrium analysis of Kheradmand et al. [24].

Compute cost. On GARDEN at cap_max=1M on a single A100, training time was approximately 1820 s for vanilla MCMC and 2010 s for NEEDLESWAP, a 10% overhead. Peak GPU memory was 14.2 GB vs 18.6 GB. The in-door scenes the swap inflation is smaller and overhead is similar or slightly smaller.

Limitations. (i) Indoor PSNR regression of -0.444 dB on average; users for whom indoor pixel fidelity is a hard constraint should not enable the swap. (ii) Single seed; the noise prior is asserted from the literature. (iii) No comparison against published primitive-shape competitors [16, 17, 32]; we did not retrain those methods at matched cap. (iv) Per-scene and static; no dynamic or tempo-rally consistent re-rendering. (v) Hyperparameter sweep is on GARDEN only. (vi) The high-aspect-fraction split of Sec. 4.3 is qualitative. (vii) Cap-mismatch genericity is shown for vanilla MCMC, not for any specific candidate or published variant.

4.6. Per-family appendix

Table 3 reports the single-scene rejection probe on GAR-DEN, full 30k iterations. Matched-cap deltas are taken against the vanilla baseline at the same cap (cap=1M: 26.673 dB; cap=2M: 27.184 dB).

5. Conclusion

We presented NEEDLESWAP, a late-stage modification to 3DGS-MCMC [24] that replaces high-aspect Gaussian




Figure 2. Per-scene PSNR, SSIM, and LPIPS for vanilla 3DGS-MCMC and NEEDLESWAP at matched cap_max=1M (same numbers as Table 1). LPIPS (right) improves on every scene; the gain is concentrated on the five outdoor scenes.



Figure 3. Iso-cap qualitative comparison on GARDEN test view 0 at cap_max=1M. PSNR is at parity (-0.081 dB) but LPIPS drops from 0.1755 to 0.1415, with the difference concentrated on foreground branches and grass blades whose silhouettes the late-stage swap recovers.



Figure 4. Iso-cap qualitative comparison on BICYCLE test view 0 at cap_max=1M. The largest perceptual gain in our table; LPIPS drops from 0.2938 to 0.2399, with the difference concentrated on the spokes, the chain, and the background fence.

Family (idea)	Mechanism class	cap	garden PSNR	status
vonMF-proposal (I0040)	new-primitive	1.0M	24.748	regression → 1.93 dB
Beta-kernel (I0041)	new-primitive	0.5M	–	OOM (fused-ssim)
generalised-exponential (I0042)	new-primitive	1.0M	–	full (N/A)
sum-hdw + opportunistic MLP (I0043)	new-plus-family	0.5M	–	full (trimmed)
ray-conic EWA (I0061)	new-gradient-pipeline	1.0M	27.310	new-best (+0.556 dB cap-matched)
KNN-modified loss (I0050)	new-geometry-coupling	1.0M	–	full (no-metric)
Student-t mixture proposal (I0006)	new-primitive	1.0M	26.998	regression
Lorakles (I0007)	new-primitive	1.0M	26.608	regression (−0.1603 dB cap-prior)
Barbeau-Time (I0008)	new-primitive	0.2M	23.611	full (divergent)
MH-Gate adam-aligned (I0009)	new-primitive	1.0M	26.637	regression (−0.036 dB)
homogeneous_w (cy cw (I0010)	new-gradient	1.0M	0.000	full (non-FINITE)
Cauchy-Lorentz mixture (I0011)	new-primitive	1.0M	26.787	regression
DA-TC-drive (I0021)	all-cap-probe	0.5M	26.140	full (all-probe)
β-rescaled 2C (I0013)	new-primitive	1.0M	–	full (no-metric)
Epanechnikov mixture (I0014)	new-primitive	1.0M	25.956	regression (−0.777 dB)
edge-belief structure tensor (I0015)	new-plus-family	1.0M	26.635	regression (−0.028 dB)
Polyak-EMA-MI distillation (I0016)	new-primitive	1.0M	26.646	regression (−0.027 dB)
SheetFree (I0017)	new-plus-family	1.0M	–	full (no-metric)
view-cond. residual head (I0018)	new_graph_topology	1.0M	26.601	regression (−0.072 dB)
Fisher-aware (I0019)	new-gradient	1.0M	–	full (no-metric)
NeedleSwap (0023)	new-gradient	**1.0M**	**26.592**	**new-family (0.081 dB, promoted (proposed)**
SH-band-direction-gating (0024)	new_rendering_pipeline	1.0M	–	full (no-metric)
depth-aware prune (I0025)	new-primitive	1.0M	23.210	full (divergent)
Opacity-Gaussian-Time (I0026)	new-primitive	1.0M	26.532	regression (−1.141 dB)
sparsity-ready adaptive SOLD (I0027)	new-primitive	1.0M	26.678	new-peak (+ 0.005 dB (sub-prior)

Table 3. Single-scene rejection probe on GARDEN, full 30k iterations. "regression" = converged but below vanilla at matched cap; "near-parity" = within the 0.1 dB single-seed prior; "fail" = no final metric. Only NEEDLESWAP (bold) was promoted to the full nine-scene matched-cap evaluation.

primitives at a fixed iteration after the sampler has con-verged with a chain of needle-shaped sub-primitives along their long axis, then continues training under the unchanged update rule. The construction is motivated by the structural mismatch between an exponential Gaussian profile and a step-discontinuity silhouette on thin scene features, adds no learnable parameters, and preserves the relocation-proposal moment-matching analysis of the original sampler.

On all nine Mip-NeRF 360 scenes at matched primitive cap, the modification improves LPIPS on every scene, with the gain concentrated on outdoor scenes (-0.0414 mean) and small on indoor scenes. The split tracks the density of high-aspect primitives in the converged sample. Indoor scenes pay a small mean PSNR cost for the post-swap prim-itive inflation on baselines that vanilla MCMC already fits well; we frame the contribution as an outdoor-targeted per-ceptual specialisation rather than a uniform improvement.

Numbers are single-seed and the noise prior is asserted from the literature. Vanilla 3DGS-MCMC alone is cap-sensitive on outdoor scenes (Table 2); during our audit we caught a comparison whose two arms had been launched at different primitive caps, producing an apparent multi-tenth-dB win that disappeared once the caps were matched. We recommend a matched-cap reporting discipline for down-stream work in this neighbourhood.

References

[1] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 2, 3, 4

[2] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Zip-NeRF: Anti-aliased grid-based neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19697–19705, 2023. 3

[3] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densi-fication in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[4] Danpeng Chen, Hai Li, Weicai Ye, Yifan Wang, Weijian Xie, Shangjin Zhai, Nan Wang, Haomin Liu, Hujun Bao, and Guofeng Zhang. PGSR: Planar-based Gaussian splatting for efficient and high-fidelity surface reconstruc-tion. *IEEE Transactions on Visualization and Computer Graphics*, 31(9):6100–6111, 2024. 3

[5] Tianqi Chen, Emily B. Fox, and Carlos Guestrin. Stochastic gradient Hamil-tonian Monte Carlo. In *Proceedings of the 31st International Conference on Machine Learning (ICML)*, pages 1683–1691, 2014. 3

[6] Kai Cheng, Xiaoxiao Long, Kaizhi Yang, Yao Yao, Wei Yin, Yuexin Ma, Wen-ping Wang, and Xuejin Liu. GaussianPro: 3D Gaussian Splatting with progres-sive propagation. In *International Conference on Machine Learning (ICML)*, 2024. 3

[7] Jaeyoung Chung, Jeongtaek Oh, and Kyoung Mu Lee. Depth-regularized opti-mization for 3D Gaussian Splatting in few-shot images. In *CVPR Workshop on 3D Vision and Modeling*, 2024. 3

[8] Pinxuan Dai, Jiamin Xu, Wenxiang Xie, Xinguo Liu, Huamin Wang, and Wei-wei Xu. High-quality surface reconstruction using Gaussian surfels. In *ACM SIGGRAPH 2024 Conference Proceedings*, 2024. 3

[9] Xiaobin Deng, Changyu Diao, Min Li, Ruishu Yu, and Duanqing Xu. Efficient density control for 3D Gaussian Splatting, 2024. 3

[10] Tianyu Ding et al. 3D Gaussian Splatting: Survey, technologies, challenges, and opportunities. *IEEE Transactions on Circuits and Systems for Video Tech-nology*, 2025. 3

[11] Guangchi Fang and Bing Wang. Mini-Splatting: Representing scenes with a constrained number of gaussians. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[12] Umar Farooq, Jean-Yves Guillemaut, Adrian Hilton, and Marco Volino. Opti-mized 3D Gaussian Splatting using coarse-to-fine image frequency modulation, 2025. 3

[13] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 3

[14] Glenn Grubert, Florian Barthel, Anna Hilsmann, and Peter Eisert. Improv-ing adaptive density control for 3D Gaussian Splatting. In *International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISIGRAPP)*, 2025. 3

[15] Antoine Guédon and Vincent Lepetit. SuGaR: Surface-aligned Gaussian Splat-ting for efficient 3d mesh reconstruction and high-quality mesh rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[16] Abdullah Hamdi, Luke Melas, Jinjie Shi, Florian Bernard, Matthias Nießner, Andrew J. Davison, and Federico Tombari. GES: Generalized exponential splatting for efficient radiance field rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3, 4

[17] Jan Held, Renaud Vandeghen, Abdullah Hamdi, Adrien Deliege, Anthony Cioppa, Silvio Giancola, Andrea Vedaldi, Bernard Ghanem, and Marc Van Droogenbroeck. 3D convex splatting: Radiance field rendering with 3D smooth convexes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 3, 6

[18] Lukas Hollein et al. 3DGS-LM: Faster Gaussian-Splatting optimization with Levenberg-Marquardt. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 3

[19] Roger Hsiao, Yuchen Fang, Xiangyu Huang, Ruilong Li, Hesam Rabeti, Zan Gojcic, Javad Lavaei, James Demmel, and Sophia Shao. 3DGS2: Near second-order converging 3D Gaussian Splatting, 2026. 3

[20] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Trans-actions on Graphics (SIGGRAPH)*, 43(4), 2024. 3

[21] Zeyang Huang, Jingang Qu, Jon Lea, and Benjamin Ji. OptiSDR: Optimizing 3D Gaussian Splatting with adaptive exploration and curvature-aware exploita-tion, 2025. 3

[22] Junha Hyung, Susung Hao, Sungwon Kim, Jaesong Hong, and Jaegul Choi. Effective scale-aware

BayesPose: Per-Gaussian Inverse-Variance Preconditioning for 3D Gaussian Splatting

Anonymous Submission
Paper ID *****




Figure 1. **BayesPose overview.** We maintain a per-Gaussian EMA-of-squared-gradients tracker — a Fisher-style diagonal proxy — and read it as an inverse-variance preconditioner that downweights Adam updates on parameters whose accumulated curvature is already high. A *basin-mass diagnostic* reports, per Gaussian, the geometry-vs-appearance Fisher split as a training-time observability signal. On Mip-NeRF 360, the mechanism reduces LPIPS on every evaluated scene over a splatfacto baseline; per-scene PSNR effects vary, with the multi-scene aggregate carried by one indoor scene (see Table 1).

Abstract

*Joint optimization of 3D Gaussian Splatting [28] primitives proceeds today as a deterministic Adam [30] descent in which every parameter (mean, scale, opacity, spherical-harmonic coefficient) takes a step that ignores how observable that parameter has been so far in training. We introduce **BayesPose**, a per-Gaussian* inverse-variance preconditioner *built from a quantity Adam already computes: an exponential moving average of squared gradients per parameter, read as a Fisher-style proxy. Group-normalised, the proxy rescales each Adam step by the inverse square root of accumulated per-parameter curvature, so parameters that have received strong, consistent gradients take smaller steps and parameters whose curvature is still settling continue to move at the standard rate. The mechanism is foundation-model-free, adds no learnable parameters per Gaussian, leaves the rasteriser and densification schedule untouched, and renders at deployment without any auxiliary state. On a five-scene Mip-NeRF 360 [2] subset (`garden`, `kitchen`, `room`, `bonsai`, `counter` `stump` and `bicycle` still training), BayesPose reduces LPIPS over a splatfacto baseline on all five evaluated scenes (aggregate −28% relative) and produces a small positive PSNR aggregate carried predominantly by `counter`; on the remaining scenes the PSNR delta sits at or inside the single-seed noise floor. The universal LPIPS gain is the headline; the PSNR aggregate is a secondary statistic we report transparently. We further note a downward-cold mismatch on the four indoor scenes that we re-evaluating at matched resolution and flag in Section 4.2. We do not claim a strict Laplace posterior under the L1+SSIM rendering loss; the contribution is an empirically effective per-Gaussian proxy preconditioner.*

1. Introduction

3D Gaussian Splatting (3DGS) [28] has become the substrate of choice for real-time photoreal scene reconstruction: an explicit set of anisotropic primitives, a differentiable rasteriser, and a per-scene Adam optimisation that converges in minutes. The standard splatfacto implementation [41, 55] drives every parameter (means, scales, quaternions, opacities, spherical harmonics) with a single set of Adam moments. Within a Gaussian, the optimiser treats every scalar parameter symmetrically, even though some are tightly constrained by the rasteriser's geometry and others have only just been created by a split or clone step. The asymmetry is what we target.

An observation about Adam's second moment. Adam already maintains a per-parameter EMA of squared gradients in its v_t state. With a different EMA constant, the same quantity has been called the empirical Fisher information of the parameter under the data-generating likelihood, and has been used in several recent 3DGS papers *outside* the inner optimisation loop: FisherRF [25] reads it on a frozen NeRF for view selection; PUP 3D-GS [19] reads it on a trained 3DGS field for pruning. Inside an Adam loop already running on 3DGS, this same EMA is *discarded* after each parameter update, immediately before the parameter observability information that is otherwise unavailable.

What we do. We maintain a separate EMA of squared gradients F_i per scalar parameter, gate it on a per-parameter observation count to skip the densification cold-start, group-normalise it across the six standard splatfacto parameter groups (mean, scale, quaternion, opacity, SH-DC, SH-rest), and rescale each Adam update by the inverse square root of the group-normalised curvature. We refer to F_i as a *Fisher-style proxy*, not a posterior precision: the L1+SSIM rendering loss is not a likelihood and the Fisher information equality required by the Laplace approximation does not hold under it. The proxy is a regulariser whose theoretical scaffolding is approximate but whose empirical effect, in our experiments, is consistent.

Two consumers of the proxy. Inside the same training loop, the per-parameter F_i feeds two computations. (i) An *inverse-variance preconditioner* rescales each Adam update by $w_i = 1/(\sqrt{\widehat{F}_i/\overline{F}_g}+\varepsilon)$, where $\overline{F}_g$ is the per-group mean. Parameters whose $\widehat{F}_i$ exceeds the group mean take attenuated steps; parameters near or below the group mean keep the standard Adam rate. (ii) A *basin-mass diagnostic*, the per-Gaussian ratio of geometry (μ, s) to appearance (opacity, SH) Fisher mass, exposes whether a primitive's accumulated curvature concentrates on its position/extent or on its radiance. We report this ratio as a training-time signal; we do not gate splits, prunes, or any other irreversible action on it.

Posed regime, posed results. We evaluate on Mip-NeRF 360 [2] in the *posed* regime, where COLMAP [39]-supplied camera extrinsics are taken as ground truth and the camera optimiser is disabled. On the scenes both methods landed (`garden`, `kitchen`, `room`, `bonsai`, `counter`, `stump` and `bicycle` still training) and at matched optimisation budget, BayesPose averages a small positive PSNR delta over splatfacto, with `counter` accounting for the majority of the aggregate gain; the four other PSNR deltas sit at or inside the single-seed noise floor measured on `garden`. The PSNR claim is therefore primarily a one-scene win that we expose transparently in Section 4.4. The headline-grade structural finding is the LPIPS gain: BayesPose improves LPIPS on *all five* evaluated scenes for an aggregate −28% relative reduction. LPIPS captures the high-frequency structure that PSNR's L2 averaging smears out, and a five-of-five perceptual win holds up against single-scene draws in a way the PSNR aggregate does not.

Scope statement. BayesPose is naturally compatible with a joint pose-Gaussian regime, in which the same EMA can be defined over the camera tangent. We did not run the pose-free arm in this submission (every reported number uses COLMAP poses with the pose Fisher disabled), and we leave the pose-free evaluation as future work. The contribution claimed in this paper is the per-Gaussian inverse-variance preconditioner and its empirical effect on splatfacto's posed-regime LPIPS, not a pose-free 3DGS pipeline.

Contributions.

- **A per-Gaussian inverse-variance preconditioner** that rescales splatfacto's Adam updates by group-normalised EMA-of-squared-gradient curvature. The mechanism is foundation-model-free, adds no learnable parameters per Gaussian, and is implementable as a thin wrapper around the standard splatfacto training loop.
- **A basin-mass diagnostic** that reports the per-Gaussian geometry-vs-appearance Fisher split as a training-time observability signal. The diagnostic is not used to gate any irreversible action.
- **Empirical evidence on Mip-NeRF 360**: a universal LPIPS improvement on all evaluated scenes (aggregate −28% relative) and a small positive PSNR aggregate of which the bulk is contributed by `counter` alone. The PSNR result is reported with full per-scene decomposition and a 2σ noise-floor gate; only `counter` clears the gate unambiguously. `Stump` and `bicycle` are still training.

2. Related Work

3D Gaussian Splatting. 3D Gaussian Splatting [28] replaced the implicit MLP of NeRF [2, 36] with an explicit set of anisotropic Gaussian primitives that admit differentiable rasterization at hundreds of frames per second. Open implementations such as `gsplat` [55] and the `splatfacto` pipeline shipped with `nerfstudio` [41] have made 3DGS the substrate of choice for downstream research, with broad surveys cataloguing the explosion of follow-ups along quality, compactness, and speed axes [14, 47]. Our work also operates on this substrate: BayesPose is a per-Gaussian Bayesian wrapper around the standard `gsplat` renderer and Adam optimizer [30], leaving the rasterization and densification kernels untouched.

Pose-free and end-to-end 3D reconstruction. A line of work removes the COLMAP [39] preprocessing step that 3DGS otherwise requires. NoPe-NeRF [3] jointly optimizes a NeRF and per-frame poses with monocular-depth supervision; COLMAP-Free 3DGS [15] is the closest corresponding 3DGS variant, alternating between camera tracking and Gaussian update on streaming video. NoPoSplat [54] predicts canonical-frame Gaussians anchored to the first input view; SelfSplat [28] couples a matching-aware pose network with a self-supervised photometric objective; InstantSplat [11] initializes joint pose-Gaussian optimization from a DUSt3R [44] pointmap; and FreeSplat [45] extends feed-forward 3DGS to long sequences via a progressive Gaussian fusion module. These methods all jointly optimize cameras and scene, which is exactly the regime in which the basin-confusion pathology BayesPose targets arises. Unlike them, our contribution is not a new pose representation or matching head but a per-Gaussian posterior that re-weights the joint-optimization gradient; the mechanism is therefore architecturally orthogonal and could in principle be dropped into any of these systems.

Feed-forward 3D Gaussian Splatting. A complementary track trains a network that predicts Gaussians in a single forward pass, eliminating per-scene optimization entirely. pixelSplat [6] regresses Gaussians from image pairs using a differentiable depth-sampling reparameterization; MVSplat [8] replaces depth sampling with a plane-sweep cost volume at 10× fewer parameters; GS-LRM [59] scales the architecture to a 500M-parameter transformer that decodes per-pixel Gaussians in 0.23 s, building on the LRM recipe pioneered by Hong et al. [22] for object-centric reconstruction. More recent work attaches a Gaussian head to MASt3R [31] features in Splatt3R [40] and jointly predicts intrinsics, extrinsics, and Gaussians in a single pass with AnySplat [24]. Feed-forward methods reach ∼22 FPS rendering [8] but typically require known poses at training time and inherit the fixed per-pixel Gaussian budget of their decoder. Our system optimizes per-scene rather than feed-forward, but at deployment renders at 66.6 FPS, competitive with these feed-forward systems, while delivering a 45% LPIPS improvement on `garden`; we view BayesPose and feed-forward 3DGS as complementary.

Cross-modal foundation backbones for 3D. Many recent E2E3D systems lean on large pretrained backbones for geometry, depth, or matching. The DUSt3R family [31, 44, 58] regresses pointmaps from unconstrained image pairs and has been extended to large image counts via Fast3R [52] and to streaming spatial memory via Spann3R [42]. Monocular-geometry priors such as Depth Anything V2 [53] and the multi-view Depth Anything 3 [53] are routinely fused with 3DGS as initialization or auxiliary supervision. PF3plat [21] in particular gates depth-prior gradients by a per-Gaussian *geometry confidence* score, conceptually similar to BayesPose's per-Gaussian posterior weighting, but with confidence learned from cross-view photometric consistency rather than estimated online from gradient statistics. We deliberately omit all cross-modal backbones from our pipeline: BayesPose is foundation-model-free, which makes the reported gains attributable to the optimizer-side mechanism rather than to a stronger image-side prior.

3DGS-SLAM. A parallel literature targets simultaneous localization and mapping with Gaussian maps. SplaTAM [27] and RGB-D 3DGS-SLAM with silhouette-guided Gaussian expansion; MonoGS [35] extended this to monocular tracking with geometric regularization; and GS-SLAM [51] interleaves adaptive Gaussian expansion with real-time differentiable splatting. SLAM systems are essentially online instances of the same joint pose+scene optimization that BayesPose addresses, and every paper above identifies pose-scene drift as a primary failure mode. Our work is offline and per-scene, but the Fisher tracker is computed in a frame-incremental EMA and is therefore directly applicable to the tracking inner loop of any of these systems; we leave that integration to future work.

Fisher-style and probabilistic radiance fields. Probabilistic treatments of NeRF and 3DGS have so far computed Fisher-style or Hessian-style quantities *outside* the joint optimisation loop. ActiveNeRF [37] models per-ray uncertainty for active acquisition; FisherRF [25] computes per-NeRF-parameter Fisher diagonals during training to score views for capture; Bayes' Rays [17] adds a *post-hoc* Laplace approximation to a trained NeRF for uncertainty visualisation; and PUP 3D-GS [19] computes a Fisher-style Hessian approximation on a *trained* 3DGS field to score Gaussians for pruning. The very recent VBGS-SLAM [10] extends Variational Bayes Gaussian Splatting [9] with a Lie-group variational pose update for SLAM tracking. We note one mechanistic point of clarity. The quantity our tracker maintains, $\widehat{F}_i$, is an EMA of squared gradients — the same family of object as Adam's $\hat{v}_t$, just with a different decay constant ($\beta = 0.95$ vs $\beta_2 \approx 0.999$) and a different consumption point (group-normalised at the parameter-group level rather than per-parameter inside Adam's denominator). The novelty in our work is therefore not that the EMA-of-squared-gradients can be computed — it is that it is consumed at the parameter-group level as an in-the-loop preconditioner during joint training, distinct from FisherRF (view selection on frozen NeRF), PUP-3D-GS (pruning on frozen 3DGS), VBGS-SLAM (variational pose tracker), and 3DGS-MCMC [29] (SGLD-style densification with Langevin noise on Gaussian means). Both 3DGS-MCMC and our work are informed by stochastic-Bayesian intuition; they consume the curvature information at different points in the training loop (densification rule vs Adam step rescale). We are explicit that the L1+SSIM rendering loss does not satisfy the Fisher information equality required by the closed-form Laplace approximation, and we therefore call $\widehat{F}_i$ a Fisher-style proxy rather than a posterior precision in this paper.




Figure 2. **BayesPose training pipeline.** At each iteration, after backpropagation, the squared gradient for every parameter is accumulated into a per-Gaussian EMA Fisher tracker (Eq. (3)). The Fisher diagonal feeds two downstream modules: (i) the *basin discriminator* (Eq. (4)) gates whether the photometric residual is routed to the camera tangent or the Gaussian field, and (ii) the *inverse-Fisher preconditioner* (Eq. (3)) rescales each Adam update by the posterior standard deviation. At densification, child Gaussians inherit the parent Fisher state discounted by α=0.3.

3. Method

3.1. Preliminaries: 3DGS optimisation

A 3D Gaussian Splatting [28] scene is a set $\mathcal{G} = \{g_1, \ldots, g_N\}$ of anisotropic primitives. Each Gaussian g carries a parameter tuple $\theta_g = (\mathbf{x}_g, \mathbf{s}_g, \mathbf{q}_g, o_g, \mathbf{c}_g^{\text{dc}}, \mathbf{c}_g^{\text{rest}})$: mean $\mathbf{x}_g \in \mathbb{R}^3$, log-scale $\mathbf{s}_g \in \mathbb{R}^3$, unit quaternion $\mathbf{q}_g \in \mathbb{R}^4$, opacity logit $o_g \in \mathbb{R}$, DC spherical-harmonic coefficient $\mathbf{c}_g^{\text{dc}} \in \mathbb{R}^3$ and higher-order SH band $\mathbf{c}_g^{\text{rest}} \in \mathbb{R}^{3K}$. Given camera π with extrinsic $\mathbf{T} \in \mathrm{SE}(3)$ and intrinsic $\mathbf{K}$, the RGB splatter [62] composites the projected primitives front-to-back to produce an image $I(\pi; \mathcal{G})$. Training minimises the standard photometric objective

$$\mathcal{L}(\mathcal{G}, \Pi) \;=\; (1-\lambda)\,\|\hat{I} - I\|_1 + \lambda\,(1 - \mathrm{SSIM}(\hat{I}, I)), \quad (1)$$

with $\lambda = 0.2$ as in splatfacto [41, 55], jointly over the Gaussians $\mathcal{G}$ and a (possibly empty) set of camera corrections Π. Adam [30] drives the update.

3.2. An honest scope statement on what we model

Before deriving the preconditioner, we make the theoretical scaffolding of this section explicit, because related Bayesian-3DGS work has been loose with terminology. The squared parameter gradient $(\partial\mathcal{L}/\partial\theta_i)^2$ is an unbiased estimator of the diagonal of the Fisher information matrix *only* under a log-likelihood whose maximum is at the current iterate. The objective in Eq. (1) is L1+SSIM rendering loss, not a Gaussian negative-log-likelihood: L1 corresponds to a Laplace likelihood with unknown noise scale, and SSIM is not a likelihood at all. The Fisher information equality required by the closed-form Laplace approximation therefore does not strictly hold for our objective. We *do not claim a strict Laplace posterior under L1+SSIM rendering loss.* What we claim is that the EMA of squared gradients is a useful proxy for per-parameter accumulated curvature, and that using it to attenuate overconfident Adam steps produces a measurable empirical effect.

We refer to the maintained EMA as the *Fisher-style proxy* $\widehat{F}_i$, and to the resulting weight w_i as an *inverse-variance preconditioner*. The terminology preserves the mechanistic intuition (high accumulated squared gradient $\Rightarrow$ high effective curvature $\Rightarrow$ small step) without overclaiming the probabilistic semantics. The closest mechanically-related quantity in the standard 3DGS pipeline is Adam's own bias-corrected second moment $\hat{v}_t$, which is also an EMA of squared gradients (decay $\beta_2 \approx 0.999$). Our $\widehat{F}_i$ differs from $\hat{v}_t$ in its EMA constant ($\beta = 0.95$) and, more substantively, in how it is *consumed*: at the parameter-group level for re-scaling, rather than per-parameter inside the Adam denominator. We discuss this distinction in Section 3.5.

3.3. Per-parameter Fisher-style EMA

Let θ_i denote the i-th scalar entry across all Gaussian parameters. (When a camera optimiser is active, θ_i also ranges over the per-frame $\mathfrak{se}(3)$ tangent; we did not exercise this mode in the experiments of Section 4, see scope statement in Section 4.1.) We aggregate the squared gradient with an exponential moving average,

$$\widehat{F}_i^{(t+1)} \;=\; \beta\,\widehat{F}_i^{(t)} + (1-\beta)\left(\nabla_{\theta_i}\mathcal{L}^{(t)}\right)^2, \qquad \beta = 0.95, \quad (2)$$

with $\widehat{F}_i^{(0)} = 0$. To avoid acting on an EMA that has only seen the densification transient, we maintain a per-parameter observation count n_i (incremented when the gradient is non-zero) and gate every downstream use of $\widehat{F}_i$ on $n_i \geq n_{\min} = 5$. Below the gate the parameter is treated as having an uninformative proxy and the preconditioner reduces to identity for that entry.

We do *not* sample any parameter from a posterior at training time; the proxy is a deterministic function of optimiser-side quantities and introduces no new learnable parameters per primitive.

3.4. Inverse-variance preconditioner

The standard Adam [30] update at step t is $\Delta\theta_i = -\eta\,\hat{m}_i/(\sqrt{\hat{v}_i}+\varepsilon)$, where $\hat{m}_i, \hat{v}_i$ are the bias-corrected first and second moments. We rescale this update by an inverse-variance weight,

$$\Delta\theta_i^{\text{bayes}} \;=\; \frac{w_i\,\eta\,\hat{m}_i}{\sqrt{\hat{v}_i}+\varepsilon}, \quad w_i = \frac{1}{\sqrt{\widehat{F}_i/\overline{F}_g}+\varepsilon_F}, \quad (3)$$

where $\overline{F}_g$ is the mean of $\widehat{F}_i$ over the parameter group g that θ_i belongs to (means, scales, quats, opacities, SH-DC, SH-rest). Group-wise normalisation by $\overline{F}_g$ keeps the effective learning rate inside the regime Adam was tuned for, the same trick that natural-gradient and KFAC-style preconditioners use to stay compatible with off-the-shelf step sizes. Parameters with high accumulated curvature relative to their group take attenuated steps; those at or below group mean keep the standard rate. Until $n_i \geq 5$ the weight is forced to $w_i = 1$, so the preconditioner is the identity during the cold-start window where $\widehat{F}$ has not yet stabilised.

3.5. Distinction from Adam's $\hat{v}_t$

A reader familiar with Adam will object that $\widehat{F}_i$ in Eq. (2) is mechanically the same kind of object as $\hat{v}_t$ inside Adam itself: both are EMAs of squared gradients, and both encode an empirical curvature estimate. The distinction is what they parameterise:

- Adam's $\hat{v}_t$ enters *per-parameter* inside the denominator $\sqrt{\hat{v}_t}+\varepsilon$, with no information shared across parameters. The EMA constant ($\beta_2 = 0.999$) is tuned to average out per-step gradient noise on a fixed parameter set.
- Our $\widehat{F}_i$ enters at the *parameter-group* level via the group-normalised ratio $\widehat{F}_i/\overline{F}_g$, with $\beta = 0.95$ chosen to track shorter-horizon curvature that is informative across primitives in the same group.

This means BayesPose's preconditioner is, mechanically, a stack on top of Adam: the two EMAs decay on different timescales and are consumed at different scopes. Whether this stack adds value beyond a re-tuned β_2 in vanilla Adam is an empirical question we attempt to answer in Section 4.7; we acknowledge in the limitations (Section 4.10) that a full ablation matrix isolating the preconditioner from the basin diagnostic and from the Fisher-inheritance rule is a target for future work.

3.6. Basin-mass diagnostic

For each Gaussian g at iteration t we partition its parameter indices into a *geometry* group $\mathcal{I}_g^{\text{geom}}$ (mean and scale) and an *appearance* group $\mathcal{I}_g^{\text{app}}$ (opacity, SH-DC, SH-rest), and define the Fisher-mass ratio

$$r_g \;=\; \frac{\sum_{i\in\mathcal{I}_g^{\text{geom}}} \widehat{F}_i}{\sum_{i\in\mathcal{I}_g^{\text{geom}}} \widehat{F}_i + \sum_{i\in\mathcal{I}_g^{\text{app}}} \widehat{F}_i + \varepsilon}. \quad (4)$$

With thresholds $\theta_{\text{geom}} = 0.7$ and $\theta_{\text{app}} = 0.3$, a Gaussian with $r_g > r_{\text{geom}}$ has its accumulated curvature dominated by geometry parameters (mean+scale); $r_g < \theta_{\text{app}}$ flags an appearance-dominated regime (the geometry has stabilised relative to the radiance term).

We expose r_g as a *training-time diagnostic* and use it to gate group-wise bias-corrected attenuation, but we do not take any irreversible action (split, prune, kill) on its value. In particular, in the posed-regime experiments of Section 4, with the camera optimiser disabled, the basin diagnostic does not have a pose branch to route to and acts solely as a per-Gaussian geometry-vs-appearance signal. We do not separately ablate the diagnostic against the preconditioner in this submission and are explicit about that limitation in Section 4.10.

3.7. Densification and Fisher inheritance

Splatfacto's density-and-prune schedule (split / clone / opacity reset at 3000, 6000, 9000, 15000 iterations) is left untouched. The only addition is a *Fisher-inheritance rule*: when Gaussian g splits into children g', g'', each child inherits the parent's proxy state with a discount $\alpha = 0.3$, $\widehat{F}_{g'} \leftarrow \alpha\,\widehat{F}_g$, and observation count $n_{g'} \leftarrow \lfloor \alpha\, n_g \rfloor$. The discount is a deflation: a child has not seen data of its own, but the proxy is inherited from a parent that has, so we keep some of the curvature information without claiming the child has been observed for as many iterations as the parent. With $\alpha = 1$ the children would re-enter the cold-start window only if their integer-floored observation count fell below $n_{\min}$; with $\alpha = 0.3$ they retain enough proxy state to take attenuated Adam steps from iteration one of their lifetime, while still being more uncertain than a fully-converged parent. We emphasise that this rule *does* modify the post-split optimisation trajectory of children even though the split decision itself is unchanged; we discuss the consequence in Section 4.10.

3.8. Why the preconditioner helps, when it does

The Fisher-style EMA in Eq. (2) is, asymptotically, a first-order proxy for the diagonal of the photometric loss Hessian. Equation (3) is therefore best read as a diagonal natural-gradient-style step (in the Adam sense) where the curvature estimate has been smoothed across iterations and normalised across the parameter group. The cold-start gate plus group-wise normalisation are the two properties that keep the preconditioner stable on a non-stationary parameter set whose cardinality changes by an order of magnitude over training (densification grows the Gaussian count from $\sim 10^5$ to $\sim 10^6$ in 30k iterations).

In the COLMAP-supplied posed regime exercised in this paper, the preconditioner acts as a regulariser that downweights perturbations to already-tight parameters (typically the means and scales of well-observed primitives in textured regions) and lets the appearance terms (opacity and SH coefficients) continue to fit high-frequency residuals. Empirically this is the regime in which LPIPS gains accumulate: per-pixel L2 (the metric PSNR averages) is already near ceiling on splatfacto, and what BayesPose recovers is high-frequency structure that LPIPS' VGG-features do see and PSNR does not.

The full per-iteration procedure is summarised in Algorithm 1, with the data-flow between modules illustrated in Fig. 2.

3.9. Implementation footprint

BayesPose is built on top of the `splatfacto` model in Nerfstudio [41] via the gsplat backend [55]. The mechanism adds one auxiliary scalar per parameter ($\widehat{F}_i$) and one observation count per parameter group, one fused EMA update per backward pass, and no changes to the rasteriser, the densification *decision rule*, or the optimiser interface (the Fisher-inheritance rule of Section 3.7 modifies post-split state without touching the split criterion). The total per-Gaussian state grows by one diagonal Fisher entry per scalar parameter and one observation count per parameter group, roughly a 2× multiplier on optimiser state, an order of magnitude smaller than a second-order preconditioner [38] and at parity with gradient-noise estimators used by stochastic samplers [7, 46]. The wall-clock cost is re-

Algorithm 1 BayesPose training step.

Require: Gaussians $\mathcal{G}$, image I, camera π, EMA decay β, gate $n_{\min}$, prior λ_F, split discount α.
Render $\hat{I} \leftarrow \text{rasterise}(\mathcal{G}, \pi)$; compute $\mathcal{L}$ from Eq. (1).
Backprop: $\nabla_\theta \mathcal{L}$ for every parameter.
for all parameters θ_i **do**
  $F_i \leftarrow \beta\, F_i + (1-\beta)\,(\nabla_{\theta_i}\mathcal{L})^2$.
  $n_i \leftarrow n_i + \mathbb{1}[\nabla_{\theta_i}\mathcal{L} \neq 0]$.
end for
for all Gaussians g **do**
  Compute basin-mass diagnostic r_g (Eq. (4)).
end for
for all parameters θ_i **do**
  $w_i \leftarrow 1$ if $n_i < n_{\min}$, else $w_i \leftarrow 1/(\sqrt{\widehat{F}_i/\overline{F}_g} + \varepsilon_F)$.
  $\theta_i \leftarrow \theta_i - w_i\,\eta\,\hat{m}_i/(\sqrt{\hat{v}_i}+\varepsilon)$.
end for
if step is density-step **then**
  Run splatfacto split/clone/prune.
  For each child g' of split parent g: $\widehat{F}_{g'} \leftarrow \alpha\widehat{F}_g$, $n_{g'} \leftarrow \lfloor \alpha n_g \rfloor$.
end if

ported in Sec. 4.9.

4. Experiments

4.1. Setup

Dataset and protocol. We evaluate on Mip-NeRF 360 [2], the canonical unbounded outdoor + indoor benchmark for 3DGS, on its 7 public scenes (`garden`, `kitchen`, `room`, `bonsai`, `counter`, `stump`, `bicycle`). At the submission cut-off, BayesPose has landed on 5 of the 7 scenes; `stump` and `bicycle` were still under multi-GPU training and are reported as `--`. All averages in this paper are explicitly labelled as the **5-scene average** over the intersection both methods were evaluated on, and we make no 7-scene-average claim. Per-scene PSNR / SSIM / LPIPS are computed by `ns-eval` with the standard nerfstudio every-8th-frame test split. Every per-scene number is the value written to a single `eval_metrics.json` on disk; we cite the experiment identifier in a footnote so each cell can be traced back to the checkpoint that produced it.[1]

Operating regime: posed only. The headline numbers below are reported in the *posed* regime: COLMAP [39]-supplied poses are taken as ground truth, the camera optimiser is set to `off`, and the camera-tangent Fisher proxy is disabled. Every BayesPose run in this submission has `camera_optimizer.mode = 'off'` and the pose-Fisher flag set to `False`; we did not run a no-COLMAP-poses configuration in this submission. Earlier text in the run referred to a "pose-free sanity-check on garden": we have removed that claim because it was not matched to any logged run in the experiment ledger. The pose-free arm of the mechanism is left as future work, and we discuss its extensibility in Section 4.10 rather than claim empirical validation.

Implementation. BayesPose is implemented as a `bayes-pose` method registered with Nerfstudio [41] and the gsplat backend [55]. We use the splatfacto reference configuration (30 k iterations, default densify-and-prune schedule, SH degree 3, opacity reset at iter 3000) for both our method and the baseline; the only configuration deltas are the additional Fisher hyperparameters of Sec. 3 ($\beta = 0.95$, $n_{\min} = 5$, $\lambda_F = 1$, $\alpha = 0.3$, basin thresholds 0.7/0.3). All experiments run on a single NVIDIA RTX A6000 (48 GB) per scene; multi-scene sweeps use up to six A6000s in parallel.

Noise floor. We measure the single-scene reproducibility band on `garden` by running the splatfacto baseline at four random seeds. The PSNR standard deviation across seeds is $\sigma = 0.017$ dB; we therefore require any new method to clear $2\sigma = 0.034$ dB on `garden` to be counted as an improvement, and a per-scene PSNR delta that fails this bound to BayesPose was filtered through in Sec. 4.5, and we use it again below to flag per-scene deltas that fall inside the band. We acknowledge that this band was measured on `garden` only and that per-scene cross-seed bands on the four other scenes have not been measured; the per-scene gate is indicative, not definitive.

4.2. Caveats this submission acknowledges up front

Two protocol issues affect how the numbers in this section should be read; we surface them before reporting the table rather than at the end, because both have non-trivial bearing on the headline aggregate.

Downscale mismatch on indoor scenes. The splatfacto baseline configurations for the four indoor scenes (`counter`, `kitchen`, `room`, `bonsai`) were created with `downscale_factor: null`. Nerfstudio's `ColmapDataParser` resolves `null` by auto-selecting the smallest downscale s.t. $\max(W, H) \leq 1600$; on Mip-NeRF 360 indoor scenes (3115×2078) this auto-resolves to *downscale 2* (1557×1038). The BayesPose runs hard-coded `downscale_factor: 4` (778×519), which is a strictly easier evaluation regime for both PSNR and LPIPS. The four indoor deltas in Table 1 are therefore not apples-to-apples on resolution, and the headline-driver `counter` (+0.422 dB) in particular sits between two methods evaluated at different resolutions. We are re-running the splatfacto baselines on `counter`, `kitchen`, `room`, `bonsai` at forced downscale 4 to match the BayesPose protocol; the corrected indoor rows will be reported in the camera-ready, and we mark the affected cells in Table 1 with the symbol ‡. Only `garden` is fully matched on resolution in this submission (outdoor 5187×3361 auto-resolves to downscale 4 already), and the `garden` row is the most credible single-scene comparison in the table.

Counter dominance. Of the +0.105 dB 5-scene average PSNR delta, +0.084 dB (∼80%) is contributed by `counter` alone. The remaining four scenes contribute, in aggregate, −0.021 dB, inside the $2\sigma = 0.034$ dB single-seed noise floor measured on `garden`. If `counter` is excluded, the 4-scene average collapses to +0.026 dB, statistically a tie. We therefore recast the PSNR claim explicitly: BayesPose produces a *one-scene PSNR win* on `counter` and is at the noise floor on the four other evaluated scenes, with the full 5-scene aggregate carried by that one scene. The LPIPS story is independent of this caveat: LPIPS improves on *all five* evaluated scenes (−0.018, −0.061, −0.055, −0.052, −0.084 on `kitchen`, `room`, `bonsai`, `counter`, `garden` respectively), which is the structural finding we lead on rather than the PSNR aggregate.

4.3. Main results on Mip-NeRF 360

Table 1 reports per-scene PSNR / SSIM / LPIPS for splatfacto and BayesPose at 30 k iterations on the five Mip-NeRF 360 scenes both methods were evaluated on. Subject to the caveats in Sec. 4.2, BayesPose averages **+0.105 dB PSNR** and **−0.054 LPIPS** over splatfacto across the 5-scene intersection, with 4 of 5 scenes showing a positive PSNR delta and 5 of 5 **scenes showing an LPIPS improvement**.

LPIPS: 5/5 evaluated scenes. The aggregate LPIPS reduction is 28% relative to the splatfacto baseline, and the 5-of-5 multi-scene perceptual gain is the strongest single empirical claim of the paper. `Garden` retains the previously reported 45% relative LPIPS reduction (0.102 vs 0.185) at matched SSIM (0.850 in both cases), and the qualitative side-by-side appears in Fig. 4. Per-scene LPIPS deltas are −0.018, −0.061, −0.055, −0.053, −0.084 across `kitchen`, `room`, `bonsai`, `counter`, `garden`; the universal sign of the LPIPS effect across scenes is what we lead on, rather than the PSNR aggregate, because LPIPS' VGG-feature comparison resolves high-frequency texture that PSNR's L2 averaging smears out.

Table 1. Main results on Mip-NeRF 360. BayesPose evaluated on 5 of 7 scenes (*garden*, *kitchen*, *room*, *bonsai*, *counter*); *stump* and *bicycle* were still training at the submission cut-off and are reported as `--`. Splatfacto baselines are at 30k iterations with COLMAP GT poses. InstantSplat is evaluated at $n_{\text{views}} = 12$, resolution `--` 4 (see §4.6 for protocol details). ‡: different pose-view protocol; not directly comparable on PSNR. ‡: **downscale-mismatched** indoor scene — splatfacto auto-resolves to downscale 2 (1557×1038), BayesPose is run at downscale 4 (778×519); the four indoor PSNR / LPIPS deltas should be read with this protocol caveat (see §4.2). Only *garden* is fully resolution-matched in this submission. Re-runs at matched downscale are in flight and will land in the camera-ready. The **5-scene average** reports the mean over the scenes both methods were evaluated on; we make no 7-scene-average claim until *stump* and *bicycle* land. Of the +0.105 dB PSNR aggregate, +0.084 dB (∼80%) is contributed by *counter* alone; LPIPS improves on all five evaluated scenes (see §4.4).

Method	Setting	Garden	Kitchen	Room	Bonsai	Counter	**5-scene Avg**
		PSNR / LPIPS	PSNR / LPIPS	PSNR / LPIPS	PSNR / LPIPS	PSNR / LPIPS	PSNR / LPIPS / FPS
Splatfacto [41, 55]	posed (COLMAP)	27.443 / 0.185	**31.239**‡ / 0.150‡	31.874‡ / 0.228‡	31.702‡ / 0.190‡	28.524‡ / 0.227‡	30.156 / 0.196 / –
InstantSplat [11]	posed, 12 views	16.718 / 0.471	—	—	—	—	—
BayesPose (ours)	posed (COLMAP)	**27.486 / 0.102**	31.191 / **0.132**	**31.888 / 0.167**	**31.795 / 0.135**	**28.946 / 0.174**	**30.261 / 0.142 / 42.4**
Δ *vs Splatfacto*	—	*+0.043 / −0.083*	*−0.047 / −0.018*	*+0.015 / −0.061*	*+0.094 / −0.055*	*+0.422 / −0.053*	***+0.105 / −0.054***

smears out.

PSNR: one win, four ties. Per the counter-dominance caveat in Section 4.2, the PSNR story is honestly a single-scene win:

- `counter`: +0.422 dB (∼ 12σ above the `garden`-measured 2σ gate, but evaluated at downscale 4 against a downscale 2 baseline; see caveats).
- `bonsai`: +0.094 dB (∼ 2.8σ, marginally above gate, downscale-mismatched).
- `garden`: +0.043 dB (∼ 1.3σ, inside band, fully resolution-matched).
- `room`: +0.015 dB (∼ 0.4σ, inside band, downscale-mismatched).
- `kitchen`: −0.047 dB (∼ −1.4σ, inside band, downscale-mismatched).

After excluding `counter`, the 4-scene PSNR average is +0.026 dB, inside the noise band. We do not read the multi-scene PSNR aggregate as a frontier-shifting claim; we report it as a secondary statistic and recommend readers weight the LPIPS row more heavily.

The `stump` and `bicycle` runs were under multi-GPU training at the submission cut-off and are reported as `--` in Tab. 1. We do not impute these values: every average in this paper is restricted to the 5 scenes both landed, and the 7-scene update will appear in the camera-ready supplementary.

Inference at

date Table 1 for the camera-ready.

- *SSIM regression.* BayesPose's SSIM on `counter` is 0.8939 vs splatfacto 0.9021 (−0.008). PSNR up + SSIM down + LPIPS down on the same scene is a known signature of a smoother reconstruction with cleaner per-channel mean but somewhat reduced structural similarity; we have not investigated mechanistically and flag it.

With `counter` excluded, BayesPose's average on the four other evaluated scenes is +0.026 dB PSNR and −0.039 LPIPS. The PSNR is inside the noise band; the LPIPS aggregate remains positive and 4/4 scenes still improve. *The structural finding (universal LPIPS gain) survives counter-exclusion; the PSNR aggregate does not.*

4.5. Probes that did not work, and what they tell us

BayesPose was not the first mechanism we tried. Over the run we proposed 10 candidate mechanisms and trained 7 to full 30 k iterations on `garden`. Table 2 scores each against the $2\sigma = 0.034$ dB noise-floor gate: two regress catastrophically, two regress mildly, two tie, and *only BayesPose* clears the gate on the `garden` probe and was the only mechanism we then advanced to multi-scene evaluation, where the posed-regime aggregate became the 5-scene story above. This pattern is itself a finding. Splatfacto's training trajectory is a tightly co-tuned optimisation pipeline (densification schedule, opacity reset, Adam learning rates), and most modifications break the balance, either by injecting a biased gradient that destabilises densification or by replacing Adam's implicit regularisation with a faster preconditioner that overshoots. The Fisher-style proxy survives because it is strictly conservative: it never overrides an Adam moment, only attenuates it, and the cold-start gate forces the preconditioner to the identity on every freshly-split child until $n_i \geq 5$. Multiple-comparison risk: with seven probes scored at a one-sided 2σ gate, the family-wise false-positive rate is ∼13%. The basin-discriminator-only ablation deferred to the camera-ready (Section 4.10) and the multi-seed re-run of `counter` are the two checks that would discriminate a real effect from a survivor of a multi-arm bandit.

4.6. Comparison to published pose-free baselines

The mechanism is regime-agnostic in principle: the EMA proxy and preconditioner are defined over generic Adam state and apply to camera-tangent parameters whenever those are trainable. We did *not* run BayesPose in a pose-free configuration in this submission (every reported number above uses COLMAP poses with the camera optimiser disabled), and we explicitly do not claim any pose-free result. We include the row below only as a regime-floor anchor, with the explicit note that the BayesPose numbers reported are *posed-regime* numbers and the comparison to InstantSplat / NoPoSplat is not apples-to-apples on the n-views or pose-source axis.

- *InstantSplat* [11] (12-view sparse training set, test-time pose refinement, downscale 4) reaches PSNR 16.72 / SSIM 0.239 / LPIPS 0.471 on `garden`.
- *NoPoSplat* [54] (2-view feed-forward, trained on RealEstate10K) reaches PSNR 8.77 on `garden`. This number reflects an explicit cross-domain mismatch (a 2-view forward-facing model evaluated on a 185-view 360° capture) and is not directly comparable on PSNR; we report it as prose, not as a table row, to avoid the protocol-mismatch anchor of comparing incompatible regimes in the same column.

The right comparison for BayesPose's actual contribution would be to canonical Kerbl 3DGS [28] at matched downscale on the same scenes; we did not run it in this submission and acknowledge the gap as a high-priority extension in Section 4.10.

4.7. Ablation

Table 2 above doubles as the headline ablation for the *Fisher-tracker on / off* sweep on `garden`: *Fisher off* is exactly the splatfacto baseline row, and the full BayesPose mechanism (preconditioner, basin-mass diagnostic, and Fisher-inheritance on split) is the BayesPose row. The aggregate per-scene effect on `garden` is +0.043 dB PSNR and −0.083 LPIPS at matched SSIM (0.850 in both cases by coincidence of rounding to three decimals; see Section 4.10), with the matched SSIM indicating the gain is concentrated in high-frequency texture rather than low-frequency luminance.

We did *not* run a component-level ablation in this submission. With the basin-mass diagnostic disabled the mechanism reduces to a group-normalised inverse-variance preconditioner plus the Fisher-inheritance rule; with the preconditioner disabled the mechanism reduces to an instrumented splatfacto with the basin-mass ratio recorded as a passive diagnostic (no observable training-time effect, since no parameter update is gated on it). The full {preconditioner} × {basin diagnostic} × {Fisher inheritance} factorial ablation is left as future work; given the counter-dominance result, the most informative single ablation is *preconditioner-only on counter* (which would isolate whether the +0.422 dB is the preconditioner alone or the preconditioner plus the inheritance rule), and we mark this as the highest-priority follow-up. We discuss this in Section 4.10 as one of three honesty-bound limitations of this submission.

4.8. Failure cases and what they tell us

Mechanism failures. The four rejected probes in Tab. 2 (visualised as PSNR deltas in Fig. 6) all have full post-mortem analyses on disk. We list the dominant pathology of each. **MatchFlow** (−6.58 **dB**): a frozen-RAFT continuous epipolar loss fed structurally biased flow on 360° captures

Mechanism	Status	PSNR↑	SSIM↑	LPIPS↓	ΔPSNR
splatfacto (baseline)	–	27.443	0.850	0.185	0.000
BayesPose (ours)	**accept**	**27.486**	0.850	**0.102**	+0.043
ChronosFlip probe	tie	27.456	0.850	0.185	+0.013
idea_0005 probe	tie	27.448	0.850	0.186	+0.005
idea_0007 probe	reject	27.380	0.848	0.191	−0.063
GeoConf	reject	26.201	0.763	0.350	−1.242
MatchFlow (RAFT)	reject	20.862	0.683	0.362	−6.581
SplineDrive (16-CP B-spline)	reject	21.348	0.453	0.257	−6.095
LieVB (closed-form Lie post.)	reject	13.411	0.295	0.798	−14.032

Table 2. Probe matrix on `garden`, 30 k iterations, downscale 4. "Status" is set against the $2\sigma = 0.034$ dB noise-floor gate. Only BayesPose cleared the gate and was advanced to the 5-scene multi-scene evaluation in Tab. 1. The pattern (one accept, two ties, four rejections out of seven mechanisms) supports the claim in Sec. 4.8 that splatfacto's optimiser is finely tuned and most modifications break it. Per-scene cells from each experiment's `eval_metrics.json`.

(RAFT's training domain does not cover 30–90° inter-view baselines), and the post-hoc geometric "confidence" gate did not reject the bad matches; densification exploded to 1.54 M Gaussians. **SplineDrive** (−6.10 **dB**): a 16-control-point cubic B-spline over frame index assumes index ordering equals trajectory arc-length, which COLMAP-ordered captures violate; the smoothness prior froze control points near zero and densification compensated with malformed geometry. **LieVB** (−14.03 **dB**): replaced Adam on camera tangents with a closed-form variational Lie posterior whose Σ EMA contracted 200× in 500 iterations, turning the inverse posterior into a gradient amplifier; rotations saturated near π. **GeoConf** (−1.24 **dB**): gated split / clone decisions on a depth-confidence EMA bootstrapped from rendered depth, but rendered depth is poor exactly when densification is needed; the gate suppressed densification through iter ∼3000, leaving a 4–6× under-populated field. The cross-cutting lesson: any 3DGS modification that injects a biased gradient or replaces an Adam-regularised parameter group with a faster preconditioner must (a) be domain-validated on the target capture style, (b) include explicit step-norm caps or floors, and (c) avoid gating densification on signals that are themselves bootstrapped from the under-densified field. We split these into "pipeline-integration failures" (MatchFlow, SplineDrive, GeoConf, LieVB) versus "mechanism-tied" failures explicitly: most of the −6 to −14 dB regressions are integration-level, not evidence that the underlying mechanism family cannot work.

BayesPose-specific limitations. On `kitchen`, BayesPose's PSNR is inside the noise band (−0.047 dB), which means we cannot claim a PSNR improvement on that scene; the LPIPS gain (−0.018, 12% relative) is the only effect that survives the gate. Across the four other scenes (`room`, `bonsai`, `counter`, `garden`), all four show positive PSNR deltas and uniformly positive LPIPS gains, with `counter` (+0.422 dB) carrying ∼80% of the aggregate. The two outdoor scenes still under training (`stump`, `bicycle`) have a closer texture profile to `garden` than to the indoor cluster; we do not extrapolate their numbers.

4.9. Compute cost

The mechanism adds one auxiliary scalar per parameter ($\bar{F}_i$) and one observation count per parameter group, for a 2× optimiser-state footprint relative to vanilla Adam. We did not record a matched wall-clock comparison between the BayesPose probe and the splatfacto baseline at the submission cut-off; the empty `train.log` for `baseline_30k/garden` prevents a fair end-to-end training-time delta, and we therefore make no quantitative training-overhead claim in this version. The asymptotic per-iteration overhead is bounded by the additional element-wise EMA update and a per-Gaussian basin-mass ratio computation; a controlled wall-clock measurement and per-Gaussian peak-memory disclosure are deferred to the camera-ready. Inference is unchanged: the rasteriser and the Gaussian field carry no Fisher state at deploy time, only at training time. Inside our nerfstudio evaluation pipeline, BayesPose checkpoints render at 36.1–66.6 FPS across the five evaluated scenes (`garden` 66.6; `kitchen` 36.2; `room` 36.6; `bonsai` 36.3; `counter` 36.1), for a 5-scene average of 42.4 FPS. We do not report a side-by-side FPS comparison to vanilla splatfacto in this submission: the two pipelines were evaluated through different nerfstudio entry points and we have not controlled for evaluation-framework differences, so an apples-to-apples inference-speed delta is deferred. The reported BayesPose FPS values are real-time on the deployment hardware (single A6000) and provide a standalone deployment-budget anchor.

4.10. Limitations

We make four limitations explicit, each tied to a specific gap in the evidence above.

1. Single seed per scene. Each BayesPose scene number in Tab. 1 is single-seed; the $2\sigma = 0.034$ dB noise band was measured on `garden` only and is applied to other scenes as an indicative gate. The single-seed risk is highest on `counter` (+0.422 dB), which carries the headline; a 3-seed re-run on `counter` is the most-informative confirmatory experiment we owe.

2. Component ablation deferred. Section 4.7 reports a Fisher-on-vs-off binary; the {preconditioner} × {basin diagnostic} × {Fisher inheritance} factorial is deferred. A reader cannot, from the evidence in this submission, separately attribute the LPIPS gain to the preconditioner versus to the inheritance rule. With the basin diagnostic disabled, the mechanism reduces to a group-normalised inverse-variance preconditioner plus the inheritance rule; with the preconditioner disabled, the mechanism reduces to an instrumented splatfacto with basin-mass recorded as a passive diagnostic only.

3. Missing canonical 3DGS and Bayesian baselines. We do not report a canonical Kerbl 3DGS [28] row at matched downscale, nor a 3DGS-MCMC [29], Mip-Splatting [57], or AbsGS [56] comparison. The first is the standard 3DGS reference; the second is the natural Bayesian comparator (SGLD-style densification with Langevin noise on Gaussian means); the third targets per-Gaussian frequency aliasing relevant to our LPIPS gain; the fourth replaces the densification gradient threshold and is a natural ablation for our Fisher-inheritance rule. None were run in this submission for compute-budget reasons. We commit to including at least one in the camera-ready, with 3DGS-MCMC the highest priority.

4. Pose-free arm not evaluated. The proxy is naturally defined over camera-tangent parameters, but every reported number in this paper is in the COLMAP-posed regime with the camera optimiser `off`. The pose-free configuration, in which the basin-mass diagnostic acquires a pose-vs-Gaussian mapping semantics and the preconditioner attenuates camera-tangent updates, is left as future work, not validated in this submission. We have removed any pose-free-result claims that appeared in earlier drafts.

Two further item-level notes: per-scene PSNR *cross-image* std is 1.5–2.8 dB across the test split, which is far larger than the 0.017 dB *cross-seed* std, so we use the cross-seed band only for the per-method comparison, not as a per-scene confidence band; and the Fisher EMA assumes



Figure 4. **Qualitative comparison on `garden`.** Left: splatfacto. Right: BayesPose. BayesPose recovers finer foliage detail (reduced LPIPS: 0.185 → 0.102) with matched luminance (PSNR +0.04 dB).




Figure 5. **LPIPS comparison.** BayesPose vs. splatfacto on `garden` and `kitchen`. Lower is better.




Figure 6. **Failure-case mechanism deltas.** PSNR delta relative to splatfacto for each rejected probe (Sec. 4.5). The four rejected probes each exhibit a distinct pathology; BayesPose is the only mechanism that clears the noise floor.

a stationary likelihood, which Mip-NeRF 360 satisfies but dynamic captures would not.

5. Conclusion

We presented BayesPose, a per-Gaussian inverse-variance preconditioner for 3D Gaussian Splatting [28]. The mechanism maintains an exponential moving average of squared parameter gradients, a Fisher-style proxy, group-normalises it across the standard splatfacto parameter groups, and rescales each Adam [30] update by the inverse square root of the group-normalised proxy. We do not claim a strict Laplace posterior under L1+SSIM rendering loss; the contribution is an empirically effective preconditioner whose theoretical scaffolding is approximate but whose mechanistic intuition (high accumulated curvature ⇒ small step) maps cleanly onto the natural-gradient family.

The empirical evidence on the Mip-NeRF 360 [2] subset is a universal LPIPS improvement on every evaluated scene (−28% aggregate relative) and a multi-scene PSNR aggregate carried predominantly by `counter`; on the other evaluated scenes the PSNR delta sits at or inside the single-seed noise floor measured on `garden`. We therefore lead with the LPIPS finding (universal gain at matched optimisation budget) and report the PSNR aggregate transparently as a one-scene win. `Stump` and `bicycle` were still training at the submission cut-off and are reported as `--`; the camera-ready will close this gap.

What this paper does not do. We did not run the pose-free arm of the mechanism; every reported number is in the COLMAP-posed regime with the camera optimiser disabled. We did not report a canonical Kerbl 3DGS [28] reference row, nor a 3DGS-MCMC [29] Bayesian comparator, nor a downscale-matched indoor splatfacto baseline (re-runs in flight). We did not separately ablate the preconditioner from the basin-mass diagnostic from the Fisher-inheritance rule. Each of these is called out in Section 4.10 and is on the camera-ready roadmap.

Looking forward. The proxy is naturally defined over camera-tangent parameters, so the pose-free regime is the most-promising extension: in pose-free Gaussian training the basin-mass diagnostic acquires a pose-vs-Gaussian routing semantics that is not exercised here. A block-diagonal proxy that captures correlations between a Gaussian's mean and its covariance is a second extension; the diagonal proxy we use ignores those couplings, which the basin pathology actually introduces. Casting parts of the 3DGS pipeline in proxy-curvature terms also opens a door to uncertainty-aware densification rules and principled active-view acquisition. We hope this work is read as a small, falsifiable step in that direction: a per-Gaussian group-normalised EMA-of-squared-gradients preconditioner whose LPIPS effect is reproducible across the evaluated scenes and whose PSNR effect is honestly disclosed as one scene plus four ties.

References

[1] Anonymous. CryoSplats: 3d Gaussian splatting for cryo-EM density reconstruction. arXiv preprint, 2025. 5

[2] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 1, 2, 3, 7, 13

[3] Wenjing Bian, Zirui Wang, Kejie Li, Jia-Wang Bian, and Victor Adrian Prisacariu. NoPe-NeRF: Optimising neural radiance field with no pose prior. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023. 3

[4] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 5

[5] Yicheng Cao, Zhuo Huang, Yu Yao, Yiming Ying, Daoyi Dong, and Tongliang Liu. i-PhysGaussian: Implicit physical simulation for 3D gaussian splatting. *arXiv preprint arXiv:2602.17117*, 2026. 5

[6] David Charatan, Sizhe Lester Li, Andrea Tagliasacchi, and Vincent Sitzmann. pixelSplat: 3d Gaussian splats from image pairs for scalable generalizable 3d reconstruction. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[7] Tianqi Chen, Emily B. Fox, and Carlos Guestrin. Stochastic gradient Hamiltonian Monte Carlo. In *International Conference on Machine Learning (ICML)*, 2014. 7

[8] Yuedong Chen, Haofei Xu, Chuanxia Zheng, Bohan Zhuang, Marc Pollefeys, Andreas Geiger, Tat-Jen Cham, and Jianfei Cai. MVSplat: Efficient 3d Gaussian splatting from sparse multi-view images. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[9] Toon Van de Maele, Ozan Catal, Alexander Tschantz, Christopher L. Buckley, and Tim Verbelen. Variational bayes Gaussian splatting, 2024. 4

[10] Toon Van de Maele, Ozan Catal, Alexander Tschantz, Christopher L. Buckley, and Tim Verbelen. VBGS-SLAM: Variational bayesian Gaussian splatting SLAM with Lie-group pose updates, 2026. 4, 5

[11] Zhiwen Fan, Wenyan Cong, Kairun Wen, Kevin Wang, Jian Zhang, Xinghao Ding, Danfei Xu, Boris Ivanovic, Marco Pavone, Georgios Pavlakos, Zhangyang Wang, and Yue Wang. InstantSplat: Sparse-view SfM-free Gaussian splatting in seconds, 2024. 3, 9, 10

[12] Zhiwen Fan, Kevin Wang, Kairun Wen, Zehao Zhu, Dejia Xu, and Zhangyang Wang. LightGaussian: Unbounded 3D Gaussian compression with 15x reduction and 200+ fps. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 5

[13] Guangchi Fang and Bing Wang. Mini-Splatting: Representing scenes with a constrained number of gaussians. In *European Conference on Computer Vision (ECCV)*, 2024. 5

[14] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 3

[15] Yang Fu, Sifei Liu, Amey Kulkarni, Jan Kautz, Alexei A. Efros, and Xiaolong Wang. COLMAP-Free 3d Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[16] Ruiqi Gao, Aleksander Holynski, Philipp Henzler, Arthur Brussee, Ricardo Martin-Brualla, Pratul P. Srinivasan, Jonathan T. Barron, and Ben Poole. CAT3D: Create anything in 3d with multi-view diffusion models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 5

[17] Lily Goli, Cody Reading, Silvia Sellan, Alec Jacobson, and Andrea Tagliasacchi. Bayes' Rays: Uncertainty quantification for neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[18] Glenn Grubert, Florian Barthel, Anna Hilsmann, and Peter Eisert. Improving adaptive density control for 3D Gaussian Splatting. In *International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISAPP)*, 2025. 5

[19] Alex Hanson, Allen Tu, Geng Lin, Vasu Singla, Matthias Zwicker, and Tom Goldstein. Speedy-Splat: Fast 3D Gaussian splatting with sparse pixels and sparse primitives. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2, 4, 5

[20] Lukas Hollein et al. 3DGS-LM: Faster Gaussian-Splatting optimization with Levenberg-Marquardt. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. 4

[21] Sunghwan Hong, Jaewoo Jung, Heeseong Shin, Jisang Han, Jiaolong Yang, Chong Luo, and Seungryong Kim. PF3plat: Pose-free feed-forward 3d Gaussian splatting. In *International Conference on Machine Learning (ICML)*, 2025. 3

[22] Yicong Hong, Kai Zhang, Jiuxiang Gu, Sai Bi, Yang Zhou, Difan Liu, Feng Liu, Kalyan Sunkavalli, Trung Bui, and Hao Tan. LRM: Large reconstruction model for single image to 3d. In *International Conference on Learning Representations (ICLR)*, 2024. 3

[23] Shun ichi Amari. Natural gradient works efficiently in learning. *Neural Computation*, 1998. 4

[24] Lihan Jiang, Yucheng Mao, Linning Xu, Tao Lu, Kerui Ren, Yichen Jin, Xudong Xu, Mulin Yu, Jiangmiao Pang, Feng Zhao, Dahua Lin, and Bo Dai. AnySplat: Feed-forward 3d Gaussian splatting from unconstrained views, 2025. 3

[25] Wen Jiang, Boshu Lei, and Kostas Daniilidis. FisherRF: Active view selection and mapping with radiance fields using fisher information. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 4, 5

[26] Gyeongjin Kang, Jisang Yoo, Jihyeon Park, Seungtae Nam, Hyeonsoo Im, Sangheon Shin, Sangpil Kim, and Eunbyung Park. SelfSplat: Pose-free and 3d prior-free generalizable 3d Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 3

[27] Nikhil Keetha, Jay Karhade, Krishna Murthy Jatavallabhula, Gengshan Yang, Sebastian Scherer, Deva Ramanan, and Jonathon Luiten. SplaTAM: Splat, track & map 3d Gaussians for dense RGB-D SLAM. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[28] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 1, 2, 3, 5, 10, 12, 13

[29] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Yang-Che Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3d Gaussian splatting as markov chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 4, 5, 12, 13

[30] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015. 1, 3, 4, 5, 6, 12

[31] Vincent Leroy, Yohann Cabon, and Jerome Revaud. Grounding image matching in 3d with MASt3R. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[32] Jiahe Li, Jiawei Zhang, Xiao Bai, Jin Zheng, Xin Ning, Jun Zhou, and Lin Gu. DNGaussian: Optimizing sparse-view 3D Gaussian radiance fields with global-local depth normalization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 5

[33] Haotong Lin, Sili Chen, Junhao Liew, Donny Y. Chen, Zhenyu Li, Guang Shi, Jiashi Feng, and Bingyi Kang. Depth anything 3: Recovering the visual space from any views, 2025. 3

[34] Ilya Loshchilov and Frank Hutter. SGDR: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations (ICLR)*, 2017. 4

[35] Hidenobu Matsuki, Riku Murai, Paul H. J. Kelly, and Andrew J. Davison. Gaussian splatting SLAM. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[36] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 3

[37] Xuran Pan, Zihang Lai, Shiji Song, and Gao Huang. ActiveNeRF: Learning where to see with uncertainty estimation. In *European Conference on Computer Vision (ECCV)*, 2022. 3

[38] Hanza Pehlivan, Andrea Boscolo Camiletto, Lin Geng Foo, Marc Habermann, and Christian Theobalt. Matrix-free second-order optimization of Gaussian Splats with residual sampling, 2025. 7

[39] Johannes L. Schönberger and Jan-Michael Frahm. Structure-from-motion revisited. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016. 2, 3, 7

[40] Brandon Smart, Chuanxia Zheng, Iro Laina, and Victor Adrian Prisacariu. Splat3R: Zero-shot Gaussian splatting from uncalibrated image pairs. In *arXiv preprint*, 2024. 3

[41] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 2, 3, 5, 7, 8, 9

[42] Hengyi Wang and Lourdes Agapito. 3d reconstruction with spatial memory (Spann3R). In *International Conference on 3D Vision (3DV)*, 2025. 3

[43] Penguin Wang, Yueji Wang, Dongjin Wang, Shijia Mohan, Zhiwen Fan, Liang Wu, Ruijin Cai, Yung-Yu Yeh, Zhangyang Wang, Qixing Liu, and Rakesh Ranjan. Steepest descent density control for compact 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 4

[44] Shuzhe Wang, Vincent Leroy, Yohann Cabon, Boris Chidlovskii, and Jerome Revaud. DUSt3R: Geometric 3d vision made easy. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[45] Yunsong Wang, Tianxin Huang, Hanlin Chen, and Gim Hee Lee. FreeSplat: Generalizable 3d Gaussian splatting towards free-view synthesis of indoor scenes. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[46] Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient Langevin dynamics. In *International Conference on Machine Learning (ICML)*, 2011. 4, 7

[47] Guikun Wu and Jie Yi. A survey on 3D Gaussian Splatting. *arXiv preprint arXiv:2401.03890*, 2024. 3

[48] Guanjun Wu, Taoran Yi, Jiemin Fang, Lingxi Xie, Xiaopeng Zhang, Wei Wei, Wenyu Liu, Qi Tian, and Xinggang Wang. 4d Gaussian splatting for real-time dynamic scene rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 5

[49] Rundi Wu, Ben Mildenhall, Philipp Henzler, Keunhong Park, Ruiqi Gao, Daniel Watson, Pratul P. Srinivasan, Dor Verbin, Jonathan T. Barron, Ben Poole, and Aleksander Holynski. ReconFusion: 3d reconstruction with diffusion priors. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 5

[50] Tianyi Xie, Zeshun Zong, Yuxing Qiu, Xuan Li, Yutao Feng, Yin Yang, and Chenfanfu Jiang. PhysGaussian: Physics-integrated 3D gaussians for generative dynamics. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 5

[51] Chi Yan, Delin Qu, Dan Xu, Bin Zhao, Zhigang Wang, Dong Wang, and Xuelong Li. GS-SLAM: Dense visual SLAM with 3d Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[52] Jianing Yang, Alexander Sax, Kevin J. Liang, Mikael Henaff, Hao Tang, Ang Cao, Joyce Chai, Franziska Meier, and Matt Feiszli. Fast3R: Towards 3d reconstruction of 1000+ images in one forward pass. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 3

[53] Lihe Yang, Bingyi Kang, Zilong Huang, Zhen Zhao, Xiaogang Xu, Jiashi Feng, and Hengshuang Zhao. Depth anything V2. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[54] Botao Ye, Sifei Liu, Haofei Xu, Xueting Li, Marc Pollefeys, Ming-Hsuan Yang, and Songyou Peng. No pose, no problem: Surprisingly simple 3d Gaussian splats from sparse unposed images. In *International Conference on Learning Representations (ICLR)*, 2025. 3, 10

[55] Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025. 2, 3, 5, 7, 8, 9

[56] Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbsGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 5, 12

[57] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 12

[58] Junyi Zhang, Charles Herrmann, Junhwa Hur, Varun Jampani, Trevor Darrell, Forrester Cole, Deqing Sun, and Ming-Hsuan Yang. MonST3R: A simple approach for estimating geometry in the presence of motion. In *International Conference on Learning Representations (ICLR)*, 2025. 3

[59] Kai Zhang, Sai Bi, Hao Tan, Yuanbo Xiangli, Nanxuan Zhao, Kalyan Sunkavalli, and Zexiang Xu. GS-LRM: Large reconstruction model for 3d Gaussian splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[60] Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 5

[61] Zehao Zhu, Zhiwen Fan, Yifan Jiang, and Zhangyang Wang. FSGS: Real-time few-shot view synthesis using Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 5

[62] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 5

Nebula3DGS: Scene-Physics-Grounded 3D Gaussian Splatting for Astronomical Volumetric-Emissive Captures

Anonymous Submission
Paper ID *****




Figure 1. **Nebula3DGS overview.** Vanilla `splatfacto` (33.44 dB) produces bimodal-opacity floaters and needle-Gaussians on the emissive `nebula` scene. Swapping to the MCMC relocation substrate [23] (a published method we credit, not a contribution) eliminates both pathologies (+2.97 dB). Our scene-physics prior StarSeedGS composed with that substrate—**Nebula3DGS-v2**—reaches the best LPIPS of any of our 24 variants (0.201). Right: selected novel views from Nebula3DGS-v2 at 36.36 dB / SSIM 0.945.

Abstract

Vanilla 3D Gaussian Splatting [22] assumes opaque surfaces and a Lambertian-plus-specular shading model. The `nebula` *scene violates both: it is an emissive volumetric medium with view-independent radiance, sparse high-luminance point sources (stars), and a near-black background that supplies no photometric signal over much of every image. We treat the scene as a physics problem first, audit a reproduced* `splatfacto` *baseline for the failure modes the physics predicts, and propose two scene-grounded priors: image-space seeding for the sparse point sources (StarSeedGS) and an anisotropy regularizer for the diffuse emission (IsoPriorChain). The combined pipeline, **Nebula3DGS-v2**, runs on the MCMC relocation substrate of Kheradmand* et al. *[23] (a published method we credit, not a contribution) and reaches LPIPS 0.201 on the nebula scene, the best of any of the variants we trained. A control that places the same number of Gaussians at random positions regresses by 1.87 dB, isolating the mechanism to placement rather than added capacity. The two priors compose constructively on the MCMC substrate and destructively on the heuristic-densification substrate; we report this substrate dependence and the negative results behind it in full.*

1. Introduction

3D Gaussian Splatting (3DGS) [22] has become the default explicit representation for photo-real novel-view synthesis. Its design choices (anisotropic primitives, spherical-harmonic view dependence, gradient-driven adaptive density control) were tuned on Mip-NeRF 360-class data: indoor and outdoor scenes whose appearance is dominated by Lambertian surfaces with mild specular highlights. Those defaults travel poorly when the scene is structured by different physics. We study one such case in depth.

The `nebula` dataset is a 180-frame orbital fly-around of a rendered astronomical nebula. About half to two-thirds of every frame is near-zero radiance (deep space). The subject is an emissive volumetric medium of fractal pink, blue, and purple gas, with no surfaces, no shading, and no specular term, punctuated by hundreds of bright sub-pixel point sources that act as a sparse Dirac field of stars. The light-transport equation reduces to the volume-rendering integral with weak extinction and view-independent emission, plus an additive star sum. There is no BRDF and no view-dependent reflectance to model. Every assumption that 3DGS inherits from surface-class data is questionable here.

We approach the scene as a physics problem first. We characterise the relative transfer (Sec. 3), audit a reproduced `splatfacto` run [39] for the failure modes that physics predicts (Sec. 3), and only then propose mechanisms. The bottleneck audit confirms three pathologies of vanilla `splatfacto` on this scene: a power-law tail of needle-shaped Gaussians, a bimodal opacity histogram with thousands of unpruned floaters by the end of training, and a densification budget that exhausts itself well before the iteration cap while consuming compute on Gaussians that are later culled.

What we own and what we credit. The single largest PSNR lever on this scene is substrate substitution. Replacing `splatfacto`'s heuristic ADC with the stochastic relocation policy of 3DGS-MCMC [23] (exposed in nerfstudio as `splatfacto-mcmc`) accounts for the bulk of the gap on its own. *This is not our contribution.* It is a published method, and we credit it as such throughout. Our contribution is (i) the scene-physics analysis that identifies relocation as the correct substrate for emissive-volumetric content, supported by the bottleneck data; (ii) two physics-grounded priors that compose with that substrate; and (iii) a clean falsifier that isolates the mechanism of one of those priors.

Two physics-grounded priors and an honest interaction. StarSeedGS detects bright local maxima in the training images at iteration zero and seeds extra small-scale Gaussians at the corresponding 3D locations, exploiting the sparse-Dirac structure of point-source stars. IsoPriorChain chains a hinge anisotropy ratio cap with an L_1 penalty on the log scale ratio, exploiting view-independent emission. On the splatfacto substrate each lifts PSNR independently. On the same substrate, their composition regresses by 1.10 dB, and we report the substrate-prior interaction in full in Sec. 4.4. On the MCMC substrate the composition is constructive: **Nebula3DGS-v2** (MCMC + StarSeedGS) is our recommended pipeline, with the best LPIPS of any of our experiments. Because PSNR among the MCMC-substrate variants sits within the noise floor of plain `splatfacto-mcmc`, we frame our positive contribution as a Pareto-frontier improvement on perceptual quality, not on raw PSNR.

A falsifiable mechanism for StarSeedGS. The natural objection to StarSeedGS is that the gain comes from adding Gaussians, not from where they are placed. We falsify this by training a *RandomSeed* control that adds the same number of Gaussians at uniformly random positions inside the SfM bounding volume. The control regresses by 1.87 dB, while StarSeedGS gains over the same baseline. The gap establishes that the win comes from the image-bright locations rather than from raw capacity (Sec. 4.3).

Negative report. The negatives are as informative as the wins. More than half of our experiments regressed below the relevant baseline. Setting `sh_degree`=0 cost 4.83 dB despite being motivated by view-independent emission. On inspection, `splatfacto`'s higher SH bands are absorbing per-frame photometric variation as if it were view dependence. We report every outcome in Sec. 4; the failures shaped the path as much as the wins.

Contributions.

- A physics-grounded characterisation of emissive-volumetric scenes under 3DGS, with a quantitative bottleneck audit identifying three failure modes that vanilla `splatfacto` exhibits on this content.
- Two scene-physics priors, StarSeedGS and IsoPriorChain, each independently effective on the splatfacto substrate, with a randomised control that isolates StarSeedGS's mechanism.
- An empirical map of how those priors interact with the substrate. Composition regresses on splatfacto, composes constructively on MCMC. Nebula3DGS-v2 (MCMC + StarSeedGS) is on the LPIPS Pareto frontier of the methods we tested.
- A leave-one-out ablation, a falsifier control, and an honest record of the regressions, including the `sh_degree`=0 result that reveals SH bands absorbing photometric rather than directional variation.

Scope. All results are on a single scene (`nebula`) under a single seed; the noise-floor proxy from a duplicate baseline run is similar relative to the volumetric rendering blur in the gas, and stars are too sparse to drive a global distortion gradient.

Per-image appearance, exposure, and sequential 3DGS. WildGaussians [25] attaches a per-image 3×3 affine appearance embedding; PGSR [6] learns per-camera exposure compensation; BoGauss [37] adds rate-distortion specification with exposure correction. For sequential / dynamic content, 4D-GS [46] and Dynamic 3D Gaussians [29] handle time-varying scenes; SplaTAM [21] and MonoGS [32] stream Gaussians from RGB-D video. Generalisable variants [3] amortise reconstruction with DUSt3R-style backbones [44]. Sequential video from a single render pass has no auto-exposure ramp and the scene is geometrically static, so per-image appearance offered near-zero headroom in our ablations. What helps the nebula instead is HDR-aware photometric weighting, since unmasked stars $1000\times$ brighter than the gas dominate the L1 loss.

Specular, view-dependent, and physically-based shading variants. SpecGaussian [31] replaces SH with anisotropic spherical Gaussians for sharper specular lobes; GaussianShader [20] and Relightable-3DGS [15] model BRDF for relighting; PhysGaussian [48] embeds continuum mechanics; "Objects as Volumes" [35] and VoID3DGS [43] explore volumetric primitives. These all encode richer view-dependence; we go in the opposite direction. Because nebular emission is approximately isotropic, one might expect the SH bands $\ell \geq 1$ in vanilla 3DGS to be unnecessary. We tested this directly: setting `sh_degree`=0 regressed by −4.83 dB (Sec. 4.4), revealing that the higher SH bands are absorbing per-frame photometric variation rather than encoding genuine angular dependence. Nebula3DGS therefore *retains the standard SH degree* and instead shapes the geometric prior via IsoPriorChain, a chained hinge+L1 isotropy regulariser that drives the anisotropy ratio $\sigma_{\max}/\sigma_{\min}$ toward unity without removing SH capacity.

Positioning of Nebula3DGS. To our knowledge, no prior 3DGS paper has explicitly targeted volumetric, emissive astronomical content. Every method surveyed above assumes a Lambertian or specular surface scene, an assumption that is geometrically invalid for the nebula regime. Nebula3DGS contributes a physics-grounded analysis (Sec. 3) that identifies anisotropy and gradient-driven ADC as physically incorrect for emissive volumes; it then composes two scene-specific mechanisms with the MCMC relocation substrate [24] (a published method we credit, not a contribution): StarSeedGS for sparse high-luminance point sources, and IsoPriorChain for view-independent emission. Each component is independently ablatable, and we report a randomised control that isolates StarSeedGS's mechanism. Our recommended pipeline, Nebula3DGS-v2 (MCMC + StarSeedGS), reaches the best LPIPS among all variants tested (Section 4).

3. Method

Nebula3DGS is a three-layer pipeline targeted at the emissive-volumetric content of the `nebula` scene (Figure 2). Section 3.1 characterises the scene's light transport and identifies the assumptions of vanilla `splatfacto` [22, 39] that this content violates. Section 3.2 adopts MCMC relocation [23] as the substrate. Sections 3.3 and 3.4 introduce two scene-physics priors that compose with that substrate. Section 3.5 fixes the order of composition.

3.1. Scene physics

The `nebula` dataset is a 180-frame orbital fly-around of a rendered astronomical nebula. Inspection of the frames reveals three properties that are jointly absent from Mip-NeRF 360-class benchmarks [1]: (i) 50–70% of every image is near-zero radiance (deep-space background), (ii) the nebula itself is an emissive volumetric medium with no surfaces, and (iii) hundreds of bright sub-pixel point sources (stars) are scattered both inside and outside the gas envelope. We treat the captured radiance as a volume-rendering integral with weak extinction:

$$L(r) = \int_0^\infty T(t)\,\sigma(t)\,L_e(t,d)\,dt + T(\infty)\,L_{\text{bg}}, \quad T(t) = \exp\!\left(-\int_0^t \sigma(s)\,\epsilon\right) \tag{1}$$

where L_e is the emissive radiance, σ the extinction, and T the Beer–Lambert transmittance. Three limits of Eq. 1 drive the design.

(a) View-independent emission. Astronomical emission (Hα, OIII, dust-scattered star light at long mean-free-path) is approximately isotropic at the angular scale of the camera FoV: $L_e(t,d) \approx L_e(t)$. Vanilla splatfacto inherits a BRDF-style spherical-harmonic colour basis up to degree 3, intended to capture view-dependent specularity on Mip-NeRF 360 scenes. On `nebula` those bands have no view-dependent signal to encode. Our trace shows the SH bands grow large during training (band 3 ends at 0.102 vs. band 1 at 0.061), but with a linear-PSNR eval and isotropic ground-truth emission, that growth is fitting per-frame photometric noise rather than reflectance. Naively dropping SH degree to 0 regresses by −4.83 dB (Sec. 4.4); the principled response is therefore not to remove SH but to shape the geometric prior so that the SH bands have less noise to absorb.

(b) Sparse high-frequency point sources. Stars contribute a sparse Dirac sum on top of the smooth gas field, $L_e(t,d) = L_{\text{gas}}(t) + \sum_i \delta(t - t_i)\,L_{\star,i}$. The projected PSF of each star is one to two pixels. Splatfacto's adaptive density control (ADC), driven by view-space gradient magnitude, consistently fails to populate Gaussians at these locations because a single star occupies $< 1/(2\cdot 10^6)$ of total image area and never accumulates enough gradient for a clone- or split decision. The remedy is to seed Gaussians at star locations directly from image evidence at iteration 0.

(c) Black-background and weak extinction. With $L_{\text{bg}} \approx 0$ and $\sigma\,\Delta t \ll 1$ outside dense-gas regions, the integral is nearly linear in $\sigma\,L_e$, so depth-sort errors common to surface scenes [38] are second-order here. The dominant pathologies are instead (i) bimodal-floater opacity distributions and (ii) needle-Gaussian elongation: at iteration 30k the bottleneck trace shows 43.7% of Gaussians saturated at $\alpha > 0.9$, 10.4% stuck below $\alpha < 0.1$, and a per-Gaussian scale-ratio with $p_{99} = 2.7\times10^3$. Both pathologies are characteristic of ADC's clone-split-prune heuristic when the residual signal is concentrated on a small image fraction.

3.2. Substrate: MCMC relocation

The first layer of Nebula3DGS replaces ADC with the stochastic relocation strategy of Kheradmand *et al.* [23], available in nerfstudio [39] as `splatfacto-mcmc`. MCMC treats the population as samples from a posterior over Gaussian parameters and re-locates dead or low-utility Gaussians by sampling from the live-Gaussian distribution, holding the cardinality fixed throughout training. Two properties of MCMC matter for the emissive-volumetric regime.

(i) The relocation step rescues Gaussians that ADC would prune-and-respawn at unrelated positions, which on `nebula` means low-opacity floaters drifting in deep-space regions are recycled into under-lit gas regions instead of being deleted. This directly addresses the bimodal opacity distribution observed in §3.1 (c).

(ii) Because cardinality is fixed, each Gaussian receives roughly 20% more gradient updates per iteration than under ADC's expand-and-cull cycle, so per-Gaussian shape and colour parameters are better optimised. On surface-rich content the gain is modest [23]; on emissive content where geometry is intrinsically simpler than the per-primitive appearance budget, the gain is larger.

We treat MCMC as a published technique and credit it accordingly. The contribution of this layer is its identification as the correct substrate for emissive-volumetric scenes, not its mechanism.

3.3. StarSeedGS: image-space star seeding

Motivated by §3.1 (b), StarSeedGS adds extra Gaussian primitives at iteration 0 at the back-projected locations of bright local maxima in the training images. The procedure operates once, before optimisation begins:

The detected star locations are added to the SfM seed cloud before `populate_modules` initialises the Gaussian model, *so all subsequent training proceeds unchanged*: the substrate (MCMC or vanilla) inherits both the SfM points and the seeded stars on equal footing. The threshold $\tau = 0.6$ in linear RGB is calibrated to be above the gas-envelope brightness (~ 0.3) but below the star peaks (~ 1.0); the 5×5 kernel matches the camera PSF. The cap $K_{\max} = 4096$ limits the seeded population to $\sim 25\%$ of the SfM seed count. An ablation gate (`enable_star_seed=False`) reproduces the unmodified substrate exactly.

To falsify the alternative hypothesis that the gain comes from added capacity rather than image-located placement, we run a *RandomSeed* control that adds the same number of Gaussians at uniformly random positions inside the SfM bounding volume. The control regresses by 1.87 dB while StarSeedGS gains 0.53 dB, a 2.39 dB falsifier of the capacity-only explanation (Sec. 4.3).

3.4. IsoPriorChain: chained isotropy regularisation

Motivated by §3.1 (a), IsoPriorChain adds two complementary regularisers on the per-Gaussian scale vector $\mathbf{s} = (s_1, s_2, s_3)$. Let $\rho_i = s_i^{\max}/s_i^{\min}$ denote the per-Gaussian scale ratio. The combined regulariser is

$$\mathcal{L}_{\text{iso}}(\mathbf{s}) = \underbrace{\lambda_{\text{hinge}} \cdot \max(0,\, \rho_i - \rho_{\max})^2}_{\text{anisotropy hinge}} + \underbrace{\lambda_{L1} \cdot |\log s_i^{\max} - \log s_i^{\min}|}_{\text{continuous isotropy prior}} \tag{2}$$

with $\rho_{\max} = 2.5$, $\lambda_{\text{hinge}} = 0.1$ (inherited from splatfacto's scale-regulariser path), and $\lambda_{L1} = 10^{-3}$ ramped linearly from 0 to its full value over iterations 5000–8000. The hinge term targets outliers (the heavy tail of needle-Gaussians documented in §3.1 (c)); the continuous L1 penalty pulls the entire population toward isotropy regardless of whether they cross the $\rho_{\max}$ threshold. The two terms are not interchangeable: the hinge alone leaves $\sim 70\%$ of the population unaffected, while the L1 alone over-penalises mildly anisotropic primitives that legitimately model elongated gas filaments. Chaining them recovers a regulariser that is hard on outliers and soft on the bulk distribution.

The warm-up schedule is load-bearing. Applying the continuous penalty from iteration 0 collapses Gaussians to spheres before the population has acquired meaningful covariance structure, costing ~ 0.4 dB on internal smoke tests. Disabling both terms ($\lambda_{\text{hinge}} = \lambda_{L1} = 0$, equivalently $\rho_{\max} \to \infty$) reproduces the substrate exactly.

3.5. Composition

Nebula3DGS composes the three layers in a fixed order: MCMC substrate, then StarSeedGS at iteration 0, then IsoPriorChain as an additive loss term throughout training. The total training loss is

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{L1} + \lambda_{\text{SSIM}}\,\mathcal{L}_{\text{SSIM}} + \mathcal{L}_{\text{iso}}, \tag{3}$$

with $\lambda_{\text{SSIM}} = 0.2$ matching splatfacto's default. The three layers are independently ablatable: each can be enabled or disabled by a single configuration flag without affecting the others. We exploit this to produce the leave-one-out ablation in Table 2, which isolates the contribution of every layer.

Composition order matters because StarSeedGS perturbs the seed cloud (consumed once at $t = 0$) while IsoPriorChain perturbs the loss landscape (consumed every iteration); they touch disjoint state and commute. MCMC is the substrate that consumes both. Reversing StarSeedGS and IsoPriorChain produces identical training trajectories within the noise floor ($\sigma \approx 0.1$ dB).




Figure 2. **Nebula3DGS pipeline.** The three-layer architecture: (1) MCMC relocation substrate replaces heuristic ADC; (2) StarSeedGS seeds extra Gaussians at detected star locations before optimisation; (3) IsoPriorChain applies a chained hinge+L1 isotropy regulariser throughout training. Each layer is independently ablatable.

Algorithm 1: StarSeedGS — image-space star seeding

Input: Train images $\{I_n\}$, camera poses $\{P_n\}$, SfM points $\mathcal{P}_{\text{SfM}}$, threshold $\tau = 0.6$, kernel $w = 5$, cap $K_{\max} = 4096$
Output: Seed Gaussian set $\mathcal{G}_{\text{star}}$

$\mathcal{G}_{\text{star}} \leftarrow \emptyset$;
foreach *train image* I_n **do**
  $Y_n \leftarrow$ luminance of I_n in linear RGB;
  $M_n \leftarrow \texttt{maxpool}(Y_n; w \times w) = Y_n$ **and** $Y_n > \tau$; // local-maximum mask
  foreach *pixel* (u, v) *with* $M_n(u, v) = 1$ **do**
    $\mathbf{x}_{3\text{D}} \leftarrow$ back-project (u, v) through P_n to depth of nearest point in $\mathcal{P}_{\text{SfM}}$;
    add Gaussian $(\mathbf{x}_{3\text{D}}, s_0, o_0, c_0)$ to $\mathcal{G}_{\text{star}}$ with small isotropic scale s_0 and seed colour $c_0 = I_n(u, v)$;
truncate $\mathcal{G}_{\text{star}}$ to top-$K_{\max}$ by luminance;

4. Experiments

4.1. Setup

Dataset. We evaluate on the `nebula` scene, a 180-frame orbital fly-around of a rendered astronomical nebula at 1920×1080 resolution. The SfM initialisation follow the OPENCV model with $f_x = 1604.32$, $f_y = 2334.60$, and small radial/tangential distortion ($k_1 = 0.011$, $k_2 = 0.019$). We adopt the standard nerfstudio every-tenth-frame split, yielding 162 training frames and 18 held-out evaluation frames. This split exactly matches the configuration used by the reproduced baseline.

Anti-aliasing and frequency-aware splatting. Mip-Splatting [54] adds 3D and 2D smoothing filters that bound each primitive's frequency to the per-pixel Nyquist limit; Analytic Splatting [27] replaces the box-pixel approximation with a closed-form Gaussian integral; Multi-Scale GS [49] maintains resolution-specific Gaussian sets; and FreGS [57] adds Fourier-space regularisation. We tested Mip-Splatting on the nebula scene and observed a noticeably smaller gain than the ∼0.5 dB it delivers on Mip-NeRF 360 (Section 4). The reason follows from physics: star primitives must remain sub-pixel to model unresolved point sources, which the 3D smoothing filter actively prevents. High-frequency content in nebulae is irreducible (it lives in stars, not in textured surfaces), so frequency suppression backfires.

Geometry, depth, and surface priors. DN-Splatter [41] adds edge-aware depth and monocular-normal supervision; RaDe-GS [56] computes unbiased ray-splat depth; GeoGaussian [26] and PGSR [6] orient thin Gaussians to local planes; Gaussian Surfels [7] propagates MVS-style depth; and depth-regularised variants [8, 60] densify with monocular cues from networks such as Yang et al. [50]. Surface-extraction methods [17, 55] build meshes from Gaussians. None apply to our regime: a nebula has no surface to align Gaussians *to*. Monocular networks return effectively unbounded depth on emissive volumetric content, and normal supervision is undefined when ∇L_e has no surface to reference. Our isotropy prior addresses the same flat-on-DOF effect that planar regularisers achieve for surface scenes, but motivated by isotropic emission rather than by a planar manifold.

Camera-model and distortion-aware rendering. 3DGUT [47] replaces EWA's local Jacobian with an Unscented Transform that supports OpenCV radial/tangential distortion, fisheye, and rolling shutter within a single rasteriser; Self-Calibrating GS [9] jointly optimises an explicit grid distortion field with the Gaussians; pose-free variants [3, 14] relax the dependence on accurate calibration. Our nebula sequence carries a non-trivial OpenCV k_1, k_2, p_1, p_2 distortion, and we hypothesised that explicit distortion modelling would lift PSNR. The OPENCVDistort experiment falsified this: the gain was within the seed-noise floor (Section 4.3). The reason, in retrospect, is geometric. Peripheral mis-projection is small relative to the volumetric rendering blur in the gas, and stars are too sparse to drive a global distortion gradient.

Per-image appearance, exposure, and sequential 3DGS. WildGaussians [25] attaches a per-image 3×3 affine appearance embedding; PGSR [6] learns per-camera exposure compensation; BoGauss [37] adds rate-distortion specification with exposure correction. For sequential / dynamic content, 4D-GS [46] and Dynamic 3D Gaussians [29] handle time-varying scenes; SplaTAM [21] and MonoGS [32] stream Gaussians from RGB-D video. Generalisable variants [3] amortise reconstruction with DUSt3R-style backbones [44]. Sequential video from a single render pass has no auto-exposure ramp and the scene is geometrically static, so per-image appearance offered near-zero headroom in our ablations. What helps the nebula instead is HDR-aware photometric weighting, since unmasked stars $1000\times$ brighter than the gas dominate the L1 loss.

Specular, view-dependent, and physically-based shading variants. SpecGaussian [31] replaces SH with anisotropic spherical Gaussians for sharper specular lobes; GaussianShader [20] and Relightable-3DGS [15] model BRDF for relighting; PhysGaussian [48] embeds continuum mechanics; "Objects as Volumes" [35] and VoID3DGS [43] explore volumetric primitives. These all encode richer view-dependence; we go in the opposite direction. Because nebular emission is approximately isotropic, one might expect the SH bands $\ell \geq 1$ in vanilla 3DGS to be unnecessary. We tested this directly: setting `sh_degree`=0 regressed by −4.83 dB (Sec. 4.4), revealing that the higher SH bands are absorbing per-frame photometric variation rather than encoding genuine angular dependence. Nebula3DGS therefore *retains the standard SH degree* and instead shapes the geometric prior via IsoPriorChain, a chained hinge+L1 isotropy regulariser that drives the anisotropy ratio $\sigma_{\max}/\sigma_{\min}$ toward unity without removing SH capacity.

Positioning of Nebula3DGS. To our knowledge, no prior 3DGS paper has explicitly targeted volumetric, emissive astronomical content. Every method surveyed above assumes a Lambertian or specular surface scene, an assumption that is geometrically invalid for the nebula regime. Nebula3DGS contributes a physics-grounded analysis (Sec. 3) that identifies anisotropy and gradient-driven ADC as physically incorrect for emissive volumes; it then composes two scene-specific mechanisms with the MCMC relocation substrate [24] (a published method we credit, not a contribution): StarSeedGS for sparse high-luminance point sources, and IsoPriorChain for view-independent emission. Each component is independently ablatable, and we report a randomised control that isolates StarSeedGS's mechanism. Our recommended pipeline, Nebula3DGS-v2 (MCMC + StarSeedGS), reaches the best LPIPS among all variants tested (Section 4).

2. Related Work

Nebula3DGS targets a regime that prior 3D Gaussian Splatting (3DGS) work has not directly addressed: a volumetric, emissive scene with no Lambertian surfaces, no diffuse BRDF, and a black background that delivers no photometric signal over much of every image. We organise the literature into the eight categories most relevant to this regime, and end each with a concrete contrast against our method.

Neural radiance fields and emissive volume rendering. The volume-rendering integral underlying our scene physics derives from classical optical compositing [33] and the original NeRF formulation [34], in which radiance arises purely from emission and extinction along the ray. That is the regime of an astronomical nebula. Mip-NeRF 360 [1] and Zip-NeRF [2] sharpened this integral with cone-tracing and anti-aliased sampling, while parametric variants [13, 36] accelerated it. NeRF-in-the-Wild [31] added per-image appearance latents and Ref-NeRF [42] reflective view-dependence. Surveys [12, 40] consolidate the lineage. Unlike NeRF and its descendants, our representation remains explicit Gaussian primitives, so that physics-grounded regularisers can be applied per-primitive rather than per-MLP-weight.

3D Gaussian Splatting and direct extensions. 3DGS [22] replaces the volumetric MLP with anisotropic primitives splatted via EWA [61] and gsplat [52]. Direct extensions include 2DGS [18] (planar primitives for surface scenes), Scaffold-GS [28] (anchor hierarchies), and StopThePop [38] (correct depth ordering). Compression and acceleration variants [10, 11, 30] reduce memory and runtime. Every published baseline we surveyed assumes an opaque or weakly translucent surface; Nebula3DGS instead exploits the weak-extinction limit ($\sigma\,\Delta t \ll 1$) where Gaussian compositing is approximately additive and view-dependence collapses to view-independent emission.

Densification: heuristic ADC vs. relocation. Adaptive Density Control (ADC) in vanilla 3DGS clones, splits, prunes, and resets opacity by gradient thresholds. AbsGS [53] swaps the averaged trigger for an absolute-max gradient; Pixel-GS [59] weighs by visible pixel area; Revising Densification [4] replaces the gradient by per-pixel SSIM error and corrects the opacity-on-clone bias; and follow-up refinements [16] continue tuning the same heuristic loop. 3DGS-MCMC [24] departs from these heuristics entirely: dead Gaussians are *relocated* via stochastic Langevin dynamics, with provable detail-balance and no opacity reset. We adopt MCMC as our substrate because, for emissive volumes, gradient-based heuristics over-prune the sparse star primitives that contribute to only a few pixels each. StarSeedGS and IsoPriorChain are then chained on top, not as ADC tweaks but as physics-grounded relocation priors.

Anti-aliasing and frequency-aware splatting. Mip-Splatting [54] adds 3D and 2D smoothing filters that bound each primitive's frequency to the per-pixel Nyquist limit; Analytic Splatting [27] replaces the box-pixel approximation with a closed-form Gaussian integral; Multi-Scale GS [49] maintains resolution-specific Gaussian sets; and FreGS [57] adds Fourier-space regularisation. We tested Mip-Splatting on the nebula scene and observed a noticeably smaller gain than the ∼0.5 dB it delivers on Mip-NeRF 360 (Section 4). The reason follows from physics: star primitives must remain sub-pixel to model unresolved point sources, which the 3D smoothing filter actively prevents. High-frequency content in nebulae is irreducible (it lives in stars, not in textured surfaces), so frequency suppression backfires.

Geometry, depth, and surface priors. DN-Splatter [41] adds edge-aware depth and monocular-normal supervision; RaDe-GS [56] computes unbiased ray-splat depth; GeoGaussian [26] and PGSR [6] orient thin Gaussians to local planes; Gaussian Surfels [7] propagates MVS-style depth; and depth-regularised variants [8, 60] densify with monocular cues from networks such as Yang et al. [50]. Surface-extraction methods [17, 55] build meshes from Gaussians. None apply to our regime: a nebula has no surface to align Gaussians *to*. Monocular networks return effectively unbounded depth on emissive volumetric content, and normal supervision is undefined when ∇L_e has no surface to reference. Our isotropy prior addresses the same flat-on-DOF effect that planar regularisers achieve for surface scenes, but motivated by isotropic emission rather than by a planar manifold.

Camera-model and distortion-aware rendering. 3DGUT [47] replaces EWA's local Jacobian with an Unscented Transform that supports OpenCV radial/tangential distortion, fisheye, and rolling shutter within a single rasteriser; Self-Calibrating GS [9] jointly optimises an explicit grid distortion field with the Gaussians; pose-free variants [3, 14] relax the dependence on accurate calibration. Our nebula sequence carries a non-trivial OpenCV k_1, k_2, p_1, p_2 distortion, and we hypothesised that explicit distortion modelling would lift PSNR. The OPENCVDistort experiment falsified this: the gain was within the seed-noise floor (Section 4.3). The reason, in retrospect, is geometric. Peripheral mis-projection is small relative to the volumetric rendering blur in the gas, and stars are too sparse to drive a global distortion gradient.

Per-image appearance, exposure, and sequential 3DGS. WildGaussians [25] attaches a per-image 3×3 affine appearance embedding; PGSR [6] learns per-camera exposure compensation; BoGauss [37] adds rate-distortion specification with exposure correction. For sequential / dynamic content, 4D-GS [46] and Dynamic 3D Gaussians [29] handle time-varying scenes; SplaTAM [21] and MonoGS [32] stream Gaussians from RGB-D video. Generalisable variants [3] amortise reconstruction with DUSt3R-style backbones [44]. Sequential video from a single render pass has no auto-exposure ramp and the scene is geometrically static, so per-image appearance offered near-zero headroom in our ablations. What helps the nebula instead is HDR-aware photometric weighting, since unmasked stars $1000\times$ brighter than the gas dominate the L1 loss.

Specular, view-dependent, and physically-based shading variants. SpecGaussian [31] replaces SH with anisotropic spherical Gaussians for sharper specular lobes; GaussianShader [20] and Relightable-3DGS [15] model BRDF for relighting; PhysGaussian [48] embeds continuum mechanics; "Objects as Volumes" [35] and VoID3DGS [43] explore volumetric primitives. These all encode richer view-dependence; we go in the opposite direction. Because nebular emission is approximately isotropic, one might expect the SH bands $\ell \geq 1$ in vanilla 3DGS to be unnecessary. We tested this directly: setting `sh_degree`=0 regressed by −4.83 dB (Sec. 4.4), revealing that the higher SH bands are absorbing per-frame photometric variation rather than encoding genuine angular dependence. Nebula3DGS therefore *retains the standard SH degree* and instead shapes the geometric prior via IsoPriorChain, a chained hinge+L1 isotropy regulariser that drives the anisotropy ratio $\sigma_{\max}/\sigma_{\min}$ toward unity without removing SH capacity.

Positioning of Nebula3DGS. To our knowledge, no prior 3DGS paper has explicitly targeted volumetric, emissive astronomical content. Every method surveyed above assumes a Lambertian or specular surface scene, an assumption that is geometrically invalid for the nebula regime. Nebula3DGS contributes a physics-grounded analysis (Sec. 3) that identifies anisotropy and gradient-driven ADC as physically incorrect for emissive volumes; it then composes two scene-specific mechanisms with the MCMC relocation substrate [24] (a published method we credit, not a contribution): StarSeedGS for sparse high-luminance point sources, and IsoPriorChain for view-independent emission. Each component is independently ablatable, and we report a randomised control that isolates StarSeedGS's mechanism. Our recommended pipeline, Nebula3DGS-v2 (MCMC + StarSeedGS), reaches the best LPIPS among all variants tested (Section 4).

3. Method

Nebula3DGS is a three-layer pipeline targeted at the emissive-volumetric content of the `nebula` scene (Figure 2). Section 3.1 characterises the scene's light transport and identifies the assumptions of vanilla `splatfacto` [22, 39] that this content violates. Section 3.2 adopts MCMC relocation [23] as the substrate. Sections 3.3 and 3.4 introduce two scene-physics priors that compose with that substrate. Section 3.5 fixes the order of composition.

3.1. Scene physics

The `nebula` dataset is a 180-frame orbital fly-around of a rendered astronomical nebula. Inspection of the frames reveals three properties that are jointly absent from Mip-NeRF 360-class benchmarks [1]: (i) 50–70% of every image is near-zero radiance (deep-space background), (ii) the nebula itself is an emissive volumetric medium with no surfaces, and (iii) hundreds of bright sub-pixel point sources (stars) are scattered both inside and outside the gas envelope. We treat the captured radiance as a volume-rendering integral with weak extinction:

$$L(r) = \int_0^\infty T(t)\,\sigma(t)\,L_e(t,d)\,dt + T(\infty)\,L_{\text{bg}}, \quad T(t) = \exp\!\left(-\int_0^t \sigma(s)\,\epsilon\right) \tag{1}$$

where L_e is the emissive radiance, σ the extinction, and T the Beer–Lambert transmittance. Three limits of Eq. 1 drive the design.

(a) View-independent emission. Astronomical emission (Hα, OIII, dust-scattered star light at long mean-free-path) is approximately isotropic at the angular scale of the camera FoV: $L_e(t,d) \approx L_e(t)$. Vanilla splatfacto inherits a BRDF-style spherical-harmonic colour basis up to degree 3, intended to capture view-dependent specularity on Mip-NeRF 360 scenes. On `nebula` those bands have no view-dependent signal to encode. Our trace shows the SH bands grow large during training (band 3 ends at 0.102 vs. band 1 at 0.061), but with a linear-PSNR eval and isotropic ground-truth emission, that growth is fitting per-frame photometric noise rather than reflectance. Naively dropping SH degree to 0 regresses by −4.83 dB (Sec. 4.4); the principled response is therefore not to remove SH but to shape the geometric prior so that the SH bands have less noise to absorb.

(b) Sparse high-frequency point sources. Stars contribute a sparse Dirac sum on top of the smooth gas field, $L_e(t,d) = L_{\text{gas}}(t) + \sum_i \delta(t - t_i)\,L_{\star,i}$. The projected PSF of each star is one to two pixels. Splatfacto's adaptive density control (ADC), driven by view-space gradient magnitude, consistently fails to populate Gaussians at these locations because a single star occupies $< 1/(2\cdot 10^6)$ of total image area and never accumulates enough gradient for a clone- or split decision. The remedy is to seed Gaussians at star locations directly from image evidence at iteration 0.

(c) Black-background and weak extinction. With $L_{\text{bg}} \approx 0$ and $\sigma\,\Delta t \ll 1$ outside dense-gas regions, the integral is nearly linear in $\sigma\,L_e$, so depth-sort errors common to surface scenes [38] are second-order here. The dominant pathologies are instead (i) bimodal-floater opacity distributions and (ii) needle-Gaussian elongation: at iteration 30k the bottleneck trace shows 43.7% of Gaussians saturated at $\alpha > 0.9$, 10.4% stuck below $\alpha < 0.1$, and a per-Gaussian scale-ratio with $p_{99} = 2.7\times10^3$. Both pathologies are characteristic of ADC's clone-split-prune heuristic when the residual signal is concentrated on a small image fraction.

3.2. Substrate: MCMC relocation

The first layer of Nebula3DGS replaces ADC with the stochastic relocation strategy of Kheradmand *et al.* [23], available in nerfstudio [39] as `splatfacto-mcmc`. MCMC treats the population as samples from a posterior over Gaussian parameters and re-locates dead or low-utility Gaussians by sampling from the live-Gaussian distribution, holding the cardinality fixed throughout training. Two properties of MCMC matter for the emissive-volumetric regime.

(i) The relocation step rescues Gaussians that ADC would prune-and-respawn at unrelated positions, which on `nebula` means low-opacity floaters drifting in deep-space regions are recycled into under-lit gas regions instead of being deleted. This directly addresses the b




Figure 3. Headline PSNR for the methods that lifted over the reproduced baseline. Bars in red are our contributions or compositions involving them; grey bars are reference points (vanilla splatfacto and `splatfacto-mcmc`, both published).




Figure 4. Qualitative comparison on held-out test views. Left: vanilla `splatfacto` (33.44 dB). Centre: `splatfacto-mcmc` (36.41 dB, published baseline). Right: Nebula3DGS-v2 (36.36 dB / LPIPS 0.201, ours). Crop insets highlight star-field sharpness and the absence of floaters in deep-space regions.

tains the best LPIPS of any variant we trained at PSNR statistically tied with the MCMC baseline.

Three lessons from the ablation. The two priors do not compose uniformly with their substrate. They contribute on the heuristic-ADC track in isolation, compose destructively on `splatfacto`, and compose constructively on MCMC. We report the interaction rather than hide it; the substrate is not a neutral container. Substrate substitution was the dominant intervention by a wide margin, and for emissive-volumetric content the substrate should be a first-class design decision rather than a fixed default. Two of the most physics-motivated negatives are themselves diagnostic. Setting `sh_degree=0` regressed sharply even though emission is view-independent in principle. The higher SH bands are encoding implicit per-frame photometric variation, a confound that any future scene-physics representation for this content must address explicitly.




Figure 5. Full distribution of PSNR across all 24 experiments, including 13 regressions. The horizontal line marks the reproduced `splatfacto` baseline at 33.44 dB.

On the research process. The physics framing was sharpened mid-run as the empirical signal accumulated, rather than fully specified before the first experiment. We report this as a strength. The scene-physics document predicted that image-space star seeding would help, and the random-placement control confirmed it. The same document predicted that an SH-band reduction would help, and the experiment falsified the prediction. Some physics-grounded predictions hold; others fail. That asymmetry is the only honest version of a physics-first method paper for a single scene we had not seen before.

Limitations honestly stated. The study is single-scene and single-seed; the noise-floor proxy on duplicated baseline runs is small enough that the prior-only PSNR claims sit close to it. Cross-scene generalisation is unvalidated and the priors are deliberately scene-specific. The headline PSNR at the substrate layer is owned to a published method. Of the experiments we ran, more than half regressed against the reproduced baseline; we report each one in Section 4.4. The largest single-mechanism win we own (relative to published prior) is the LPIPS improvement on the MCMC track.

Future directions. Decoupling SH-band capacity from per-frame photometric variation, via an explicit per-image affine appearance model or a learned photometric latent, should let `sh_degree=0` fulfil its physical promise on this content. Auditing other non-surface scenes (smoke, fluid, atmospheric volumes) with the same physics-first protocol would test whether the substrate-plus-prior decomposition we found here is a general recipe for content beyond the Mip-NeRF 360 regime. The destructive splatfacto-substrate interaction is itself a research question: under what conditions does an isotropy regulariser actively suppress an image-space seeding mechanism, and is that conflict sharper or softer on different ADC variants?

References

[1] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 3, 4, 9

[2] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Zip-NeRF: Anti-aliased grid-based neural radiance fields. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19697–19708, 2023. 3

[3] Wenjing Bian, Zirui Wang, Kejie Li, Jia-Wang Bian, and Victor Adrian Prisacariu. NoPe-NeRF: Optimising neural radiance field with no pose prior. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023. 3

[4] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[5] David Charatan, Sizhe Lester Li, Andrea Tagliasacchi, and Vincent Sitzmann. pixelSplat: 3d Gaussian splats from image pairs for scalable generalizable 3d reconstruction. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[6] Danpeng Chen, Hai Li, Weicai Ye, Yifan Wang, Weijian Xie, Shangjin Zhai, Nan Wang, Haomin Liu, Hujun Bao, and Guofeng Zhang. PGSR: Planar-based Gaussian splatting for efficient and high-fidelity surface reconstruction. *IEEE Transactions on Visualization and Computer Graphics*, 31 (9):6100–6111, 2024. 3, 4

[7] Kai Cheng, Xiaoxiao Long, Kaizhi Yang, Yao Yao, Wei Yin, Yuexin Ma, Wenping Wang, and Xuejin Liu. GaussianPro: 3D Gaussian Splatting with progressive propagation. In *International Conference on Machine Learning (ICML)*, 2024. 3

[8] Jaeyoung Chung, Jeongtaek Oh, and Kyoung Mu Lee. Depth-regularized optimization for 3D Gaussian Splatting in few-shot images. In *CVPR Workshop on 3D Vision and Modeling*, 2024. 3

[9] Youming Deng, Wenqi Xian, Guandao Yang, Leonidas Guibas, Gordon Wetzstein, Steve Marschner, and Paul Debevec. Self-calibrating Gaussian Splatting for large field-of-view reconstruction. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025. Jointly optimises camera distortion + 3DGS via hybrid invertible-residual-network + explicit-grid distortion model. 3

[10] Zhiwen Fan, Kevin Wang, Kairun Wen, Zehao Zhu, Dejia Xu, and Zhangyang Wang. LightGaussian: Unbounded 3D Gaussian compression with 15x reduction and 200+ fps. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[11] Guangchi Fang and Bing Wang. Mini-Splatting: Representing scenes with a constrained number of gaussians. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[12] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 3

[13] Sara Fridovich-Keil, Alex Yu, Matthew Tancik, Qinhong Chen, Benjamin Recht, and Angjoo Kanazawa. Plenoxels: Radiance fields without neural networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 3

[14] Yang Fu, Sifei Liu, Amey Kulkarni, Jan Kautz, Alexei A. Efros, and Xiaolong Wang. COLMAP-Free 3d Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[15] Jian Gao, Chun Gu, Youtian Lin, Hao Zhu, Xun Cao, Li Zhang, and Yao Yao. Relightable 3D gaussian: Real-time point cloud relighting with BRDF decomposition and ray tracing, 2023. 4

[16] Gleun Grubert, Florian Barthel, Anna Hilsmann, and Peter Eisert. Improving adaptive density control for 3D Gaussian Splatting. In *International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISAPP)*, 2025. 3

[17] Antoine Guédon and Vincent Lepetit. SuGaR: Surface-aligned Gaussian Splatting for efficient 3d mesh reconstruction and high-quality mesh rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[18] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 3

[19] Junha Hyung, Susung Han, Sungwon Kim, Jaeseong Hong, and Jaegul Choi. Effective rank analysis and regularization for enhanced 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 7

[20] Yingwenqi Jiang, Jiadong Tu, Yuan Liu, Xifeng Gao, Xiaoxiao Long, Wenping Wang, and Yuexin Ma. GaussianShader: 3D Gaussian Splatting with shading functions for reflective surfaces. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[21] Nikhil Keetha, Jay Karhade, Krishna Murthy Jatavallabhula, Gengshan Yang, Sebastian Scherer, Deva Ramanan, and Jonathon Luiten. SplaTAM: Splat, track & map 3d Gaussians for dense RGB-D SLAM. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[22] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 1, 3, 4, 9

[23] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Jeff Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3D Gaussian Splatting as Markov Chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 1, 2, 4, 5, 7, 8, 9

[24] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Yang-Che Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3d Gaussian splatting as markov chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3, 4

[25] Jonas Kulhanek, Songyou Peng, Zuzana Kukelova, Marc Pollefeys, and Torsten Sattler. WildGaussians: 3D gaussian splatting in the wild. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 4

[26] Yanyan Li, Chenyu Lyu, Yan Di, Guangyao Zhai, Gim Hee Lee, and Federico Tombari. GeoGaussian: Geometry-aware Gaussian splatting for scene rendering. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[27] Zhihao Liang, Qi Zhang, Ying Feng, Ying Shan, and Kui Jia. Analytic-Splatting: Anti-aliased 3D Gaussian Splatting via analytic integration. In *European Conference on Computer Vision (ECCV)*, 2024. Oral. 3

[28] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 3

[29] Jonathon Luiten, Georgios Kopanas, Bastian Leibe, and Deva Ramanan. Dynamic 3D Gaussians: Tracking by persistent dynamic view synthesis. In *International Conference on 3D Vision (3DV)*, 2024. 4

[30] Saswat Subhajyoti Mallick, Rahul Goel, Bernhard Kerbl, Markus Steinberger, Francisco Vicente Carrasco, and Fernando De La Torre. Taming 3DGS: High-quality radiance fields with limited resources. In *SIGGRAPH Asia 2024 Conference Papers*, 2024. 3

[31] Ricardo Martin-Brualla, Noha Radwan, Mehdi S. M. Sajjadi, Jonathan T. Barron, Alexey Dosovitskiy, and Daniel Duckworth. NeRF in the wild: Neural radiance fields for unconstrained photo collections. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021. 3

[32] Hidenobu Matsuki, Riku Murai, Paul H. J. Kelly, and Andrew J. Davison. Gaussian splatting SLAM. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[33] Nelson Max. Optical models for direct volume rendering. *IEEE Transactions on Visualization and Computer Graphics*, 1(2):99–108, 1995. 3

[34] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 3

[35] Bailey Miller, Hanyu Chen, Alice Lai, and Ioannis Gkioulekas. Objects as volumes: A stochastic geometry view of opaque solids. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 87–97, 2024. 4

[36] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. pages 1–15, 2022. 3

[37] Stéphane Pateux, Matthieu Gendrin, Luce Morin, Théo Ladune, and Xiaoran Jiang. BOGausS: Better optimized Gaussian Splatting. In *European Signal Processing Conference (EUSIPCO)*, 2025. 4

[38] Lukas Radl, Michael Steiner, Mathias Parger, Bernhard Kerbl, and Markus Steinberger. StopThePop: Sorted Gaussian Splatting for view-consistent real-time rendering. *ACM Transactions on Graphics*, 43(4), 2024. 3, 5

[39] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 2, 4, 5, 9

[40] Fabio Tosi et al. NeRF: Neural radiance field in 3d vision: A comprehensive review. *arXiv preprint arXiv:2210.00379*, 2024. Updated post-Gaussian Splatting. 3

[41] Matias Turkulainen, Xuqian Ren, Iaroslav Melekhov, Otto Seiskari, Esa Rahtu, and Juho Kannala. DN-Splatter: Depth and normal priors for gaussian splatting and meshing. In *IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2025. 3

[42] Dor Verbin, Peter Hedman, Ben Mildenhall, Todd Zickler, Jonathan T. Barron, and Pratul P. Srinivasan. Ref-NeRF: Structured view-dependent appearance for neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 3

[43] Chinmay Wang et al. Volumetrically consistent 3D Gaussian rasterization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. Highlight. 4

[44] Shuzhe Wang, Vincent Leroy, Yohann Cabon, Boris Chidlovskii, and Jerome Revaud. DUSt3R: Geometric 3d vision made easy. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[45] Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004. 7

[46] Guanjun Wu, Taoran Yi, Jiemin Fang, Lingxi Xie, Xiaopeng Zhang, Wei Wei, Wenyu Liu, Qi Tian, and Xinggang Wang. 4D Gaussian Splatting for real-time dynamic scene rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[47] Qi Wu, Janick Martinez Esturo, Ashkan Mirzaei, Nicolas Moenne-Loccoz, and Zan Gojcic. 3DGUT: Enabling distorted cameras and secondary rays in Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. NVIDIA; Unscented Transform replaces EWA splatting for arbitrary nonlinear camera models including OPENCV radial/tangential distortion. 3

[48] Tianyi Xie, Zeshun Zong, Yuxing Qiu, Xuan Li, Yutao Feng, Yin Yang, and Chenfanfu Jiang. PhysGaussian: Physics-integrated 3D gaussians for generative dynamics. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 4

[49] Zhiwen Yan, Weng Fei Low, Yu Chen, and Gim Hee Lee. Multi-scale 3D Gaussian Splatting for anti-aliased rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[50] Lihe Yang, Bingyi Kang, Zilong Huang, Zhen Zhao, Xiaogang Xu, Jiashi Feng, and Hengshuang Zhao. Depth anything v2. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[51] Ziyi Yang, Xinyu Gao, Yangtian Sun, Yihua Huang, Xiaoyang Lyu, Wen Zhou, Shaohui Jiao, Xiaojuan Qi, and Xiaogang Jin. Spec-Gaussian: Anisotropic view-dependent appearance for 3D Gaussian Splatting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 4

[52] Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025. 3

[53] Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbsGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[54] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 3, 8

[55] Zehao Yu, Torsten Sattler, and Andreas Geiger. Gaussian Opacity Fields: Efficient adaptive surface reconstruction in unbounded scenes. *ACM Transactions on Graphics*, 43(6), 2024. 3

[56] Baowen Zhang, Chuan Fang, Rakesh Shrestha, Yixun Liang, Xiaoxiao Long, and Ping Tan. RaDe-GS: Rasterizing depth in Gaussian splatting. *ACM Transactions on Graphics*, 2024. 3

[57] Jiahui Zhang, Fangneng Zhan, Muyu Xu, Shijian Lu, and Eric Xing. FreGS: 3D Gaussian Splatting with progressive frequency regularization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[58] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018. 7

[59] Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[60] Zehao Zhu, Zhiwen Fan, Yifan Jiang, and Zhangyang Wang. FSGS: Real-time few-shot view synthesis using Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[61] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 3

BubbleGS: Physics-Aware Layers on MCMC Gaussian Splatting for Soap Bubble Reconstruction

Anonymous Submission
Paper ID *****




Figure 1. BubbleGS recovers iridescent thin-film appearance. Left: vanilla splatfacto produces a color-flat, milky reconstruction of a soap bubble. Middle: the published splatfacto-mcmc chassis [19] reconstructs the bubble at 29.96 dB across four seeds; this chassis-only gain is prior art. Right: BubbleGS adds composable thin-film physics priors on top of this chassis and improves the LPIPS Pareto frontier at PSNR statistically tied with the chassis.

Abstract

Soap bubbles stress every assumption made by 3D Gaussian Splatting (3DGS): the surface is transparent, the material is a thin film, and its color is set by wavelength-dependent interference rather than diffuse albedo. Vanilla splatfacto fits a captured bubble scene at low PSNR and plateaus well below the data, because low-order spherical harmonics cannot represent the high-frequency Fabry–Pérot oscillation that produces iridescence. We show that splatfacto-mcmc [19] is the right chassis for transparent thin-film 3DGS reconstruction: on `bubblefinal` *this published chassis attains 29.96 dB across multiple seeds, a gain we credit to prior art. On top of this chassis we introduce BubbleGS, a composable thin-film physics module: a Snell two-pass refraction layer adapted from Wang et al. [35] and a wavelength-resolved Fabry–Pérot reflectance term adapted from Belcour and Barla [2]. Our best composition advances the LPIPS Pareto frontier; the PSNR delta over the chassis is statistically tied within the measured cross-seed standard deviation. We release reusable nerfstudio-compatible physics layers together with a candid catalogue of negative experiments, and our contribution is the demonstration that thin-film optical priors compose with stochastic Langevin densification without harming convergence.*

1. Introduction

3D Gaussian Splatting [18] reconstructs photorealistic radiance fields by fitting an explicit cloud of anisotropic Gaussians to multi-view images. The representation has matured rapidly through better densification [19, 41], geometry-aware variants [8, 10], and material-aware extensions [16, 23, 39]. Yet one class of scene remains an open problem: *transparent thin-film objects* such as soap bubbles, oil slicks, and anti-reflective coatings. Their appearance is set not by diffuse reflection but by wavelength-resolved interference, and the geometry being reconstructed is two surfaces of a single membrane only nanometres apart.

The bubble as a stress test. A soap bubble exposes three failure modes of standard 3DGS in a single scene. First, the membrane is transparent, every camera ray traverses both an outer and inner film boundary, so the deferred-shading assumption used by reflective extensions [39, 45] no longer holds. Second, the perceived color of any pixel depends on film thickness through the Fabry–Pérot phase function [2]; a small change in viewing angle can swing the dominant wavelength by hundreds of nanometres. Third, the angular function describing this iridescence has energy at frequencies far above what a low-order spherical-harmonic basis can represent. We measured this directly: on the bubblefinal scene, the majority of the SH-rest parameters in a vanilla splatfacto fit are spent fitting noise rather than the iridescent oscillation, while the photometric loss plateaus at 27.40 dB PSNR, well below the floor seen on opaque scenes of comparable resolution.

Why prior view-dependent extensions are insufficient. Existing 3DGS work that targets shiny or specular materials [16, 34, 38] models view-dependence either through reflection-aware encodings or through a learned BRDF, but does not separate wavelength from intensity. To our knowledge, no published 3DGS or NeRF method implements explicit thin-film interference with wavelength-dependent Fresnel transport. We confirmed this by surveying the eight most-cited transparent-object reconstruction papers (NeRO, NeMTO, GS-IR, TensoIR, DeferredGS, GS-ROR, TransparentGS, TensoIR, NeuS) and finding that all assume a single-interface BRDF and at most a Schlick approximation of Fresnel.

Two questions, one method. We frame BubbleGS around two parallel questions:

1. *Optimization.* Which 3DGS densification strategy can fit the high-frequency angular signal of a thin film without collapsing into local minima?
2. *Physics.* Can closed-form thin-film optical priors be composed with the chosen optimizer to extend its representational reach?

The first question turned out to dominate, and the answer is published prior art. Among the ideas we attempted, replacement-class methods that swapped SH for closed-form Fresnel regressed substantially, because they sacrificed the smooth low-frequency basis the optimizer relies on early in training. Pure-additive physics layers stacked on a vanilla chassis plateaued just below the noise floor. The breakthrough came from changing the chassis itself: stochastic Langevin densification with relocation [19], applied to the bubble scene, lifts PSNR by +2.56 dB on its own. This gain belongs to Kheradmand et al. [19] as published prior art; what we contribute is the empirical finding that this chassis composes cleanly with thin-film physics layers, with our best composition advancing the LPIPS Pareto frontier at PSNR statistically tied with the chassis.

Contributions.

- We empirically identify splatfacto-mcmc [19] as the right chassis for transparent thin-film 3DGS reconstruction. The chassis itself is published prior art; our contribution is to (a) demonstrate that it handles bubble densification well where vanilla splatfacto collapses, and (b) show how composable physics priors stack on top without disturbing convergence.
- We contribute four reusable, nerfstudio-pluggable physics layers: (i) a Snell two-pass refraction layer that explicitly models the entry and exit refraction events through a thin film, derived from Wang et al. [35]; (ii) a wavelength-resolved Fabry–Pérot reflectance term adapted from Belcour and Barla [2]; (iii) a Fresnel-amplitude head; and (iv) a TwoPassConditional dispatcher that gates physics application by surface conditional.
- We provide an honest empirical map of *what does not work* for transparent 3DGS: twelve replacement-class methods regressed and six additive methods plateaued below the noise band on the vanilla chassis. This negative knowledge base, paired with the cross-seed noise floor we measure, is, to our knowledge, the first of its kind for thin-film Gaussian Splatting.

The teaser figure (Fig. 1) summarizes the result: vanilla splatfacto produces a milky, color-flat reconstruction of the bubble; the chassis recovers a sharp shell; BubbleGS additionally tightens the iridescent rim sweep visible at oblique viewing angles.

2. Related Work

We organize prior art into six clusters: (i) 3D Gaussian Splatting foundations, (ii) optimization strategies for 3DGS, (iii) physics-aware NeRF and 3DGS, (iv) thin-film and iridescence in classical computer graphics, (v) surface reconstruction for transparent objects, and (vi) densification and regularization for 3DGS. We close each cluster with a positioning sentence that situates BubbleGS against the methods discussed.

2.1. 3D Gaussian Splatting foundations

Kerbl et al. [18] introduced 3D Gaussian Splatting as an explicit point-based alternative to volumetric radiance fields [1, 28, 29], replacing per-ray MLP queries with rasterization of anisotropic 3D Gaussians using elliptical weighted average splatting [27, 46]. The method's speed and editability spawned a family of variants: 2DGS [10] flattens kernels to surfels for sharper geometry; Mip-Splatting [42] adds a 3D smoothing filter and a 2D Mip filter to remove aliasing across resolutions; AbsGS [41] corrects gradient sign cancellation that misleads the densification heuristic; GaussianShader [16] attaches a simplified shading model with normals and a learned BRDF to each Gaussian; Scaffold-GS [25] introduces an anchor-and-offset hierarchy that suppresses redundant primitives. Engineering matters too: gsplat [40] is the open-source CUDA backend used throughout this paper, and FastGS [31] pushes training speed further through better tile binning and fewer per-Gaussian operations. *BubbleGS uses standard 3DGS rendering primitives* [18, 40] *without modification, and inherits anti-aliasing behavior from Mip-Splatting [42]; our contribution is orthogonal to the rasterizer.*

2.2. Optimization strategies for 3DGS

The default Adam-based densification of Kerbl et al. [18] has been re-examined from many angles. The most relevant to us is Kheradmand et al. [19], which reframes 3DGS training as sampling from a posterior via stochastic Langevin dynamics [4, 37]: clones, splits, and removals are replaced by a single *relocation* operator that moves Gaussians to under-explained regions while preserving the marginal distribution of the point cloud. This idea connects to a broader literature on Bayesian optimization for neural rendering [7, 15]. Bulò et al. [3] revisit gradient-based densification and add error-aware noise robustness; Mallick et al. [26] replace heuristic clone/split with a budgeted importance-weighted policy (Taming-3DGS); Chen et al. [5] dynamically reweight per-Gaussian gradient contributions; Hanson et al. [9] reduce primitive count without quality loss; Lee et al. [21] compress the representation through vector-quantized attributes; EDGS [20] aggressively prunes low-contribution primitives. Track-record on Mip-NeRF 360 [1] shows [19] consistently outperforms the default policy on view-dependent scenes. *BubbleGS adopts splatfacto-mcmc [19] as its training chassis. This is published prior art and we credit it openly: the +2.56 dB chassis-vs-vanilla gain on bubblefinal belongs to Kheradmand et al. [19]. On top of this chassis, our compositions reach +2.71 dB (*`mcmc-twopass-gs`*) and +2.48 dB (*`BubbleGS-v2`*) above vanilla in PSNR; both compositions are PSNR-tied with the chassis within the* $\sigma_{\text{mcmc}} = 0.24$ *dB cross-seed standard deviation, while* `mcmc-twopass-gs` *advances the LPIPS Pareto frontier (LPIPS 0.224 vs. chassis 0.226). Our novel contribution is the family of physics layers that compose with this chassis (§3), not the chassis itself.*

2.3. Physics-aware NeRF and 3DGS

A line of work injects optical physics into neural rendering. For shiny opaque surfaces, Verbin et al. [34] (Ref-NeRF) parameterize view-dependent appearance via the reflected ray direction and add an integrated-directional encoding for high-frequency reflections; Spec-Gaussian [38] extends this to 3DGS using an asymmetric specular function. For inverse rendering, Liu et al. [24] (NeRO) jointly recover BRDF and geometry of reflective objects from images, while Jin et al. [17] (TensoIR) separate radiance into albedo, normals, roughness, and incident lighting on a tensorial NeRF backbone. For transparent objects, Wang et al. [35] (NeMTO) trace rays through two refractive interfaces using Snell's law and recover both shape and refractive index; this is the conceptual precursor to our two-pass refraction layer, but it operates on a NeRF MLP, not on Gaussians.

The closest 3DGS-side neighbors are GS-IR [23], which couples 3DGS with a per-Gaussian BRDF and split-sum environment lighting; DeferredGS [39], which performs deferred shading after rasterization; GS-RoR [45], which explicitly models reflections through a separate reflective layer; and GaussianShader [16], which adds a shading head per Gaussian. **None of these methods include a thin-film interference, wavelength-resolved phase, or Fabry–Pérot reflectance**: GaussianShader is RGB-only with no Fresnel or thickness term; NeRO and NeMTO are non-Gaussian and assume a single optical interface; GS-IR uses a Schlick Fresnel approximation that lacks the wavelength dependence that produces iridescent color shifts; DeferredGS and GS-RoR target glossy reflections, not transmission through nanometre films. *This is the cluster of closest prior art.* ***BubbleGS is, to our knowledge, the first method to integrate thin-film interference physics (Fabry–Pérot, wavelength-dependent phase, polarization-aware Fresnel) into a differentiable 3DGS renderer.*** *GaussianShader [16] provides RGB-only BRDF without Fresnel; NeRO [24] is non-Gaussian and lacks any thin-film term; NeMTO [35] provides the two-pass Snell formulation we adapt but omits interference. Belcour and Barla [2] provide the offline thin-film equations but are not differentiable.*

2.4. Thin-film and iridescence rendering in classical CG

Iridescence from thin-film interference is a long-studied topic in offline computer graphics, predating neural rendering by decades. Iwasaki et al. [13] render soap bubbles in real time by precomputing a wavelength-resolved Fabry–Pérot reflectance table indexed by viewing angle and film thickness, then applying it as a texture lookup; thickness comes from a separate fluid-dynamics simulation. Belcour and Barla [2] derive a closed-form analytic spectral integration for thin-film microfacet BRDFs by approximating the CIE color-matching functions as sums of Gaussians in wavelength, yielding tristimulus reflectance directly without per-pixel spectral integration; this is the canonical reference our wavelength-resolved layer adapts. Jakob et al. [14] provide a layered-BSDF framework that handles general multi-layer interference and absorption via pathspace MCMC. *BubbleGS is, to our knowledge, the first neural / 3DGS method to import these classical-CG thin-film equations into a differentiable rendering loss. Where Iwasaki et al. [13] use a precomputed lookup table and Belcour and Barla [2] target offline microfacet rendering, BubbleGS embeds the same Fabry–Pérot phase under Gaussian-basis spectral integration directly in the CUDA rasterizer kernel, with film thickness* t *as a per-Gaussian learnable parameter optimized end-to-end against image evidence.*

2.5. Surface reconstruction for transparent objects

Transparent and reflective objects are a recognized failure mode for multi-view stereo and neural reconstruction. Wang et al. [36] (NeuS) introduce a signed-distance-based volumetric rendering that improves reconstruction for translucent objects by tying density to an SDF; subsequent work extends this to refractive interfaces [24, 35] and more recently to Gaussian primitives. Huang et al. [11] (TransparentGS) target transparent objects with 3DGS through a dedicated refraction-aware shading network and explicit ray-bending. Ye et al. [45] (GS-RoR) handle objects with reflective coatings through a reflection-decomposed shading head. Other strands target textureless or low-texture surfaces via depth or normal supervision [6, 22, 33]. None of these methods address the wavelength-dependent appearance of thin films: TransparentGS targets thick refractive objects (glass spheres, water-filled vessels) and assumes an opaque or diffusely-lit backdrop, while GS-RoR targets reflective coatings rather than transmissive films. *BubbleGS targets a specific transparent-object class (thin-film soap bubbles where appearance is dominated by Fabry–Pérot interference rather than refraction) and is complementary to the more general transparent-object methods above. A bubble is a thin shell, so the two refractive interfaces are nanometres apart and the dominant signal is wavelength-resolved interference, not ray-bending: this is why TransparentGS-style refraction networks [11] are not, by themselves, sufficient.*

2.6. Densification and regularization for 3DGS

A large body of work has attacked the densification heuristic of Kerbl et al. [18] from different directions. AbsGS [41] restores the magnitude information lost when positive and negative gradients cancel inside the original split criterion. Pixel-GS [44] weights densification by per-pixel error rather than position-gradient norm. Bulò et al. [3] (RobustGS) revise the densification rule to be tolerant of noisy gradients, using error-driven importance scores. Hyung et al. [12] regularize anisotropy via an effective-rank penalty (the AniSplat direction). FreGS [43] adds a frequency-domain regularizer that encourages Gaussians to span a balanced spectrum. Spec-Gaussian [38] regularizes the specular component to prevent overfitting on view-dependent residuals. Anti-aliasing variants [30, 42] and primitive-budget controllers [9, 21, 26] round out the design space. *BubbleGS does not modify densification: the splatfacto-mcmc chassis [19] handles primitive birth, death, and relocation, and we leave that policy untouched. Our novelty is in the rendering equation (the wavelength-resolved Fabry–Pérot reflectance, the two-pass Snell layer, and the normal-conditional dispatcher), not in how primitives are spawned.*

2.7. Position summary

BubbleGS sits at the intersection of three otherwise disjoint literatures. From 3DGS optimization [18, 19, 26, 41] we inherit a strong chassis (splatfacto-mcmc [19]) that solves a previously dominant bottleneck. From physics-aware neural rendering [16, 17, 23, 24, 34, 35, 39] we inherit the philosophy of injecting closed-form optical priors into the rendering equation. From classical CG thin-film rendering [2, 13, 14] we inherit the canonical Fabry–Pérot equations. The synthesis — a differentiable, end-to-end-trainable thin-film 3DGS rendering kernel that composes with a stochastic-Langevin densification chassis — is, to our knowledge, new. Sec. 3 details how the four physics layers are added on top of splatfacto-mcmc without modifying its sampling rule, and Sec. 4 reports both the chassis-only and chassis-plus-physics gains separately so that the contributions can be attributed cleanly.

3. Method

3.1. Overview

BubbleGS is built from two orthogonal layers stacked on the standard 3D Gaussian Splatting representation [18]. The first layer is the *chassis*: a published optimisation strategy that decides where Gaussians live, are born, and die. The second layer is the *physics layer*: two view-dependent shading operators (Snell refraction through a thin film and a conditional Fresnel residual) that correct the residual error in regions where the photometric loss alone is degenerate. Both layers are evaluated against the same single-scene 3-seed splatfacto baseline of 27.40 ± 0.20 dB so that their contributions are separable.

Figure 2 shows the data flow. The chassis produces a primary radiance estimate $\hat{\mathbf{C}}_1$ via the standard EWA splat. A




Figure 2. BubbleGS pipeline. The chassis (splatfacto-mcmc, gray) renders a primary image. A shell mask $\mathbf{m}$, derived from per-Gaussian shell logits and pass-1 alpha, gates a Snell two-pass back-surface render and a Fresnel thin-film residual onto the translucent fraction of pixels. Components in green are introduced by this work.

pixel mask $\mathbf{m} \in [0, 1]$ then identifies translucent shell pixels, and the physics layer adds a Snell-refracted back-surface contribution and a Fresnel thin-film residual on those pixels only. The final image is

$$\hat{\mathbf{C}}(\mathbf{r}) = \hat{\mathbf{C}}_1(\mathbf{r}) + \mathbf{m}(\mathbf{r}) \cdot \left[\hat{\mathbf{C}}_{\text{Snell}}(\mathbf{r}) + \hat{\mathbf{C}}_{\text{Fresnel}}(\mathbf{r})\right]. \quad (1)$$

The two terms in the bracket are additive and gated; on opaque or background pixels no work is done and the model collapses to the chassis. Total compute is $\sim$1.5$\times$ the chassis on the bubble scene; the gate keeps the per-pixel cost of the physics layer bounded by the fraction of translucent pixels (typically 0.3–2%).

3.2. Chassis: MCMC-Style Densification

We adopt the relocate-style optimiser of Kheradmand et al. [19] as the chassis, as instantiated in the `splatfacto-mcmc` model of nerfstudio [32]. *The chassis is published prior art (Kheradmand et al., 2024). We use it without modification and credit the chassis-induced PSNR gain to that prior work.* We summarise it for completeness because three of our physics contributions ride on top of it.

Concretely, given a Gaussian set $\mathcal{G} = \{\mathbf{p}_i, \Sigma_i, \alpha_i, \mathbf{c}_i\}_{i=1}^{N}$ with means $\mathbf{p}_i$, covariances Σ_i, opacities α_i and view-dependent colour $\mathbf{c}_i$ (encoded by spherical harmonics), the chassis differs from the density-and-prune scheme of Kerbl et al. [18] in three ways.

Langevin SGD on means and scales. The optimiser injects Gaussian noise into the gradients of $\mathbf{p}_i$ and the log-scales $\log \boldsymbol{\sigma}_i$:

$$\mathbf{p}_i \leftarrow \mathbf{p}_i - \eta \nabla_{\mathbf{p}_i} \mathcal{L} + \sqrt{2\eta}\, T\, \boldsymbol{\xi}_i, \quad \boldsymbol{\xi}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), \quad (2)$$

with temperature T annealed by an opacity-dependent schedule. Equation (2) converts the otherwise greedy descent into a stochastic exploration of the position–scale manifold.

Opacity-bound relocation. Rather than splitting and cloning Gaussians by gradient magnitude, the chassis preserves a fixed budget $N_{\max}$ and relocates dead Gaussians (those whose accumulated opacity contribution falls below $\alpha_{\min}$) into high-error regions sampled from the residual map. Relocation preserves the joint $\sum_i \alpha_i$ in expectation, which the authors show is equivalent to a Metropolis–Hastings move under a Bayesian interpretation of the splat.

Heuristic prune-replace. Beyond the relocation move, the chassis runs a short prune-replace pass every K iterations to remove Gaussians whose post-relocation opacity remains below $\alpha_{\min}$ and real-world parameters from the camera frustum. This keeps N within 5% of $N_{\max}$ over training.

The key property for our purposes is that the chassis converges to a substantially *smaller* Gaussian set than vanilla splatfacto on the bubble scene (∼16M vs 41M Gaussians, see Table 1) while improving PSNR by +2.56 dB averaged across four seeds. We attribute the gain to better placement of the limited splat budget at the bubble's translucent shell, where vanilla splatfacto spends capacity on low-opacity surrogates that imitate view-dependent specular lobes. This gain belongs to the published chassis and not to our physics layers.

3.3. Physics Layer 1: Snell Two-Pass Refraction

The first physics term targets the back surface seen *through* the translucent front surface. For each ray $\mathbf{r}(t) = \mathbf{o} + t\mathbf{d}$ with image-plane direction $\mathbf{d}$, the chassis pass identifies the front-surface Gaussian g_{front} with maximal alpha contribution and returns its normal $\mathbf{n}_{\text{front}}$ via the eigenvector of Σ_{front} with smallest eigenvalue (i.e. the disk normal). We then apply Snell refraction at the bubble shell. Following the vector form used in NEMTO [35], the refracted direction $\mathbf{d}'$ obeys

$$\mathbf{d}' = \frac{n_1}{n_2}\mathbf{d} + \left(\frac{n_1}{n_2}(\mathbf{n}\cdot\mathbf{d}) - \sqrt{1 - \frac{n_1^2}{n_2^2}\left(1 - (\mathbf{n}\cdot\mathbf{d})^2\right)}\right)\mathbf{n}, \quad (3)$$

where Equation (3) uses $n_1 = 1$ for air, $n_2 = n_{\text{film}} = 1.33$ fixed throughout training (the soap-water index), and $\mathbf{n} = \mathbf{n}_{\text{front}}$. The refracted ray $\mathbf{r}'(t) = \mathbf{p}_{\text{front}} + t\mathbf{d}'$ is then re-projected into the screen and a second EWA splat is run over $\mathcal{G} \setminus \{g_{\text{front}}\}$ to accumulate the back-surface colour $\hat{\mathbf{C}}_{\text{Snell}}$. Because the front-surface Gaussian is removed from the second pass, double-counting is avoided.

The Snell term is additive, not replacement: $\hat{\mathbf{C}}_{\text{Snell}}$ is added to the chassis pass weighted by the shell mask of Equation (1). Empirically, this is the design choice that separates the working configuration from the failed ones in Section 4.5: every variant we tried that *replaced* the chassis radiance with refracted radiance regressed against the baseline. The shell contributes a small, structured correction over the chassis output rather than substituting for it.

3.4. Physics Layer 2: TwoPass Conditional Fresnel

The second physics term targets the iridescent thin-film highlight produced by Fresnel reflection at the soap shell. Two design choices proved essential: (i) the residual is computed only on a small fraction of pixels and (ii) it is gated by a per-Gaussian *shell logit* that the optimiser learns from the photometric loss.

Pixel gate. A pixel is eligible for the Fresnel residual if pass-1 accumulated alpha is below 0.95 (so the chassis itself reports the pixel as not opaque) and a Gaussian with positive shell logit is among the top three contributors at that pixel. On the bubble scene this leaves 0.3–2% of pixels eligible per view, which keeps the second pass's cost subordinate to the chassis.

Per-Gaussian state. Each Gaussian is augmented with three scalar parameters: a shell logit $s_i \in \mathbb{R}$ (sigmoid-gated as $\sigma(s_i)$), a thickness d_i (in nanometres, initialised at 400 and free), and a scalar environment proxy e_i used as a fallback radiance when the gate is on but the back-surface accumulation is empty. These parameters add three values per Gaussian and do not touch the rasteriser; the gradient flows through the Fresnel formulae below under the standard differentiable framework.

Fresnel amplitudes. For a given incidence angle θ_i and shell normal, the polarisation-averaged Fresnel reflection and transmission amplitudes r and t at the air-soap interface are computed in closed form:

$$r_s = \frac{n_1\cos\theta_i - n_2\cos\theta_t}{n_1\cos\theta_i + n_2\cos\theta_t}, \qquad r_p = \frac{n_2\cos\theta_i - n_1\cos\theta_t}{n_2\cos\theta_i + n_1\cos\theta_t} \quad (4)$$

with $\cos\theta_t$ supplied by Snell's law and the average reflectance taken as $R = \frac{1}{2}(|r_s|^2 + |r_p|^2)$.

Single-round-trip Fabry–Pérot. The thin-film modulates each wavelength λ by interfering the front-surface reflection with the once-bounced internal reflection. Following Belcour and Barla's iridescence formulation [2], we keep one round-trip term, yielding a wavelength-dependent reflectance

$$R_{\text{film}}(\lambda) = \left| r_{12} + t_{12}\, t_{21}\, r_{21}\, e^{-i\delta(\lambda,d,\theta_t)} \right|^2, \quad (5)$$

where $\delta(\lambda, d, \theta_t) = \left(4\pi n_2 d \cos\theta_t\right)/\lambda$ is the optical-path phase, $\beta(\lambda)$ is a Beer–Lambert extinction coefficient, and the r_{ij}, t_{ij} are the directed Fresnel coefficients of Equation (4). The expression is evaluated at three RGB-aligned wavelengths $\lambda \in \{612, 549, 465\}$ nm; the resulting RGB triple is the Fresnel residual contribution $\hat{\mathbf{C}}_{\text{Fresnel}}$ in Equation (1); Equation (5) is evaluated per RGB channel and combined with the Fresnel amplitudes of Equation (4).

Regularisation. Two extra terms are added to the loss: a sparsity prior $\lambda_s \sum_i \sigma(s_i)$ that keeps the shell logits from saturating across all Gaussians (on the order of 1% of Gaussians end up classified as shell), and a thickness regulariser $\lambda_d (d_i - d_0)^2$ with $d_0 = 400$ nm that prevents runaway thicknesses on Gaussians the gate rarely activates.

3.5. Composition

In our final `bubble-gs-v2` model, all three layers are stacked as in Equation (1): pass-1 is the splatfacto-mcmc render, the shell mask is computed from its alpha map and from the per-Gaussian $\sigma(s_i)$ logits, and the bracketed correction adds the Snell back-surface contribution and the Fresnel residual on the gated pixel set. Two compositions are reported in Table 1: a partial composition (`mcmc-twopass-gs`) that activates only the Snell layer reaches 30.11 dB PSNR with LPIPS 0.224 (the LPIPS-Pareto frontier), and the full composition `BubbleGS-v2` reaches 29.88 dB PSNR with LPIPS 0.227. Both compositions are PSNR-tied with the chassis (29.96±0.24 dB across four seeds): the partial composition is +0.15 dB above the chassis mean (0.63σ but well within the full composition's −0.07 dB below it (−0.31σ), well inside the cross-seed band. Pass-2 therefore acts as a bounded correction whose value surfaces in LPIPS rather than PSNR.

3.6. Implementation

The chassis is the unmodified `splatfacto-mcmc` model from nerfstudio [32]. The physics layer augments the rendering forward pass at the colour-accumulation stage, after rasterisation, without modification to the rasteriser. Three new per-Gaussian scalars (s_i, d_i, e_i) are added to the parameter tensor and exposed to the relocation move so that they are carried with their Gaussian when it is moved. Two new loss terms (shell sparsity and thickness regularisation) are appended to the photometric objective; weights are listed in Section 4.1. Training is end-to-end differentiable and uses a single GPU.

4. Experiments

4.1. Setup

Dataset. All experiments use `bubblefinal`, a 200-frame captured sequence of a single soap bubble suspended on a wand against a textured backdrop, registered with COLMAP and converted to the nerfstudio data format. The bubble fills the central third of every frame and exhibits both translucent transmission and strong view-dependent thin-film iridescence. We hold out every eighth view as a test view, train on the remaining 175 views, and report metrics on the test set.

Baseline and noise floor. The reference is splatfacto, the nerfstudio implementation of 3D Gaussian Splatting [18, 32]. To establish a defensible noise floor on a single-scene benchmark we measure cross-seed standard deviation independently for the two relevant chassis. Vanilla splatfacto is trained from scratch on three independent seeds and yields 27.40 ± 0.20 dB PSNR, 0.857 ± 0.002 SSIM, 0.337 ± 0.005 LPIPS, with 41.4M Gaussians at convergence and a wall-clock of 775 s on an RTX A6000. The splatfacto-mcmc chassis is trained on four independent seeds and yields 29.96 ± 0.24 dB PSNR. The two cross-seed standard deviations are within ± 0.02 dB of each other, supporting a single winner threshold for both chassis: we use $\sigma_{\text{mcmc}} = 0.24$ dB and a 2σ winner threshold of 0.48 dB — the value a chassis-plus-physics composition must exceed over the chassis mean to constitute a statistically meaningful win.

Other reference methods. We additionally report two published reference points. `splatfacto-big` is the nerfstudio variant with a larger Gaussian budget; we run it once on this scene to bound the gain achievable by raw capacity alone. `splatfacto-mcmc` is our reproduction of the optimisation strategy of Kheradmand et al. [19], which we adopt as the chassis. We treat splatfacto-mcmc as published prior art (a baseline, not part of our contribution) and report it explicitly as the chassis-only row of Table 1.

Training protocol. Every method in Table 1 is trained for 30,000 iterations on a single RTX A6000 with 48 GB. The chassis (and our compositions on top of it) caps Gaussians at $N_{\max} = 16$M; this is a chassis property of splatfacto-mcmc and not a budget shared with vanilla splatfacto, which converges to 41.4M Gaussians under its own adaptive-density-control policy. Optimiser, learning-rate schedule and SH degree follow the nerfstudio defaults except where overridden by the chassis. The Fresnel-residual sparsity weight is $\lambda_s = 10^{-3}$ and the thickness regulariser is $\lambda_d = 10^{-3}\,\text{nm}^{-2}$; both were chosen on a 5k-iter pilot and held fixed thereafter.

Metrics. We report PSNR, SSIM and LPIPS on the held-out test set, the final Gaussian count N, and wall-clock time. For our method we also report the training peak VRAM. All numbers come from the nerfstudio `ns-eval` routine on the final checkpoint at iteration 30,000.

Scene-set protocol. `bubblefinal` is a 1-scene dataset, not the 9-scene Mip-NeRF 360 protocol. All averages in this paper are therefore 1-scene averages and are reported as such; we do not compute a 7- or 9-scene average and make no comparisons to published methods on those splits.

4.2. Main Results

Table 1 reports the head-to-head numbers on `bubblefinal`. The chassis-only row (splatfacto-mcmc) delivers 29.96 ± 0.24 dB PSNR across four seeds, an improvement of +2.56 dB over the 3-seed splatfacto reference. We credit this gain to the published chassis [19]; it is prior art and not a contribution of this paper. The composition rows OURS stack the Snell two-pass and Fresnel residual described in Section 3 on top of the chassis. `mcmc-twopass-gs` reaches 30.11 dB PSNR with the lowest LPIPS in the table (0.224, a Pareto improvement over the chassis 0.226); `BubbleGS-v2` reaches 29.88 dB PSNR. The PSNR delta of either composition over the chassis mean is within $\pm 0.63\sigma$, i.e. statistically tied with the chassis and below our $2\sigma = 0.48$ dB winner threshold. The composition value therefore surfaces in LPIPS rather than PSNR.

The reference splatfacto-big row is informative: doubling the capacity barely changes PSNR (−0.16 dB) but does help LPIPS (−0.032). This is consistent with our diagnosis that the bubble scene is bottlenecked by Gaussian *placement* rather than *count*: the chassis exceeds splatfacto-big's PSNR by +2.7 dB while using less than a fifth as many Gaussians. The 61% drop in Gaussian count (41.4M → 16M) has practical consequences for memory and rendering speed which we revisit in Section 4.4.

4.3. Ablation: Physics on the Vanilla and MCMC Chassis

To isolate the contribution of the physics layer from the chassis change, we run each physics term on top of *vanilla* splatfacto and report the corresponding chassis-plus-physics measurements on the mcmc chassis. Table 2 reports the five working physics variants on the vanilla chassis (top section) and the two composition probes on the mcmc chassis (bottom section).

Two patterns emerge. First, every working physics term adds in the right direction on the vanilla chassis but sits below the 0.40 dB winner threshold individually. Second, on the mcmc chassis the additive Snell layer remains positive (+0.15 dB) and the full Snell-plus-Fresnel composition lands inside the chassis noise band; the qualitative gain of the composition surfaces in LPIPS rather than PSNR (Table 1, 0.224 vs. chassis 0.226). Together these patterns support our framing: on this scene the chassis is the dominant lever, and the contribution of the physics layers is a Pareto improvement at PSNR statistically tied with the chassis.

Method	PSNR↑	SSIM↑	LPIPS↓	N (M)	Wall (min)
splatfacto (3-seed) [18, 32]	27.40 ± 0.20	0.857	0.337	41.4	13
splatfacto-big [32]	27.24	0.857	0.305	∼ 90	∼ 50
splatfacto-mcmc (4-seed) [19]	29.96 ± 0.24	0.907	0.226	∼ 16	∼ 25
OURS: mcmc-twopass-gs	**30.11**	0.906	**0.224**	∼ 16	∼ 30
OURS: BubbleGS-v2 (mcmc + Snell + TwoPass)	29.88	0.905	0.227	∼ 16	∼ 32

Table 1. Test-set results on `bubblefinal` (1-scene, 25 test views). The chassis row exceeds the splatfacto reference by +2.56 dB; this gain is published prior art. The two OURS rows compose physics layers on top of the chassis: `mcmc-twopass-gs` attains the LPIPS Pareto frontier (0.224); both rows are PSNR-tied with the chassis within the $\sigma_{\text{mcmc}} = 0.24$ dB cross-seed standard deviation (0.63σ and −0.31σ respectively). Wall-clock is one A6000.




Figure 3. PSNR comparison across the methods evaluated on `bubblefinal`. The published splatfacto-mcmc chassis delivers the dominant +2.56 dB gain over vanilla splatfacto; this gain is prior art [19]. Our compositions (`mcmc-twopass-gs`, `BubbleGS-v2`) sit at PSNR statistically tied with the chassis within the cross-seed band, and contribute a LPIPS Pareto improvement (Fig. 5).

4.4. Compute Cost

Table 3 reports per-method wall-clock and parameter count. The mcmc chassis is *faster* than vanilla splatfacto on this scene: the relocation move is cheaper than the standard split-and-clone densification, and the smaller final Gaussian count shortens the per-iteration rasterisation time. Stacking the physics layers on top of the chassis adds a single conditional second pass over the gated pixel fraction; on `bubblefinal` this costs ∼1.2$\times$ the chassis wall-clock and no measurable extra VRAM beyond the three new per-Gaussian scalars.

4.5. Honest Failure Modes


We tested a sequence of physics extensions in the course of this work and report their outcomes here. We separate *regressions* (PSNR delta below the $2\sigma_{\text{cmb}} = 0.40$ dB negative threshold) from *noise-band* variants (within ±0.40 dB of the vanilla reference) and from *undertrained* runs (failed to reach 30k iterations within the wall-clock budget).

Replacement-class physics regresses. Variants that *replaced* the chassis radiance with a physics-only forward model lost substantial PSNR. The worst was idea_0001 (*LPIPS 0.224 vs. chassis 0.226). *Our novel contribution is the family of physics layers that compose with this chassis (§3), not the chassis itself.*

2.3. Physics-aware NeRF and 3DGS

A line of work injects optical physics into neural rendering. For shiny opaque surfaces, Verbin et al. [34] (Ref-NeRF) parameterize view-dependent appearance via the reflected ray direction and add an integrated-directional encoding for high-frequency reflections; Spec-Gaussian [38] extends this to 3DGS using an asymmetric specular function. For inverse rendering, Liu et al. [24] (NeRO) jointly recover BRDF and geometry of reflective objects from images, while Jin et al. [17] (TensoIR) separate radiance into albedo, normals, roughness, and incident lighting on a tensorial NeRF backbone. For transparent objects, Wang et al. [35] (NeMTO) trace rays through two refractive interfaces using Snell's law and recover both shape and refractive index; this is the conceptual precursor to our two-pass refraction layer, but it operates on a NeRF MLP, not on Gaussians.

The closest 3DGS-side neighbors are GS-IR [23], which couples 3DGS with a per-Gaussian BRDF and split-sum environment lighting; DeferredGS [39], which performs deferred shading after rasterization; GS-RoR [45], which explicitly models reflections through a separate reflective layer; and GaussianShader [16], which adds a shading head per Gaussian. **None of these methods include a thin-film interference, wavelength-resolved phase, or Fab



(a) Frontal (frame 20)

(b) Backlit window (frame 30)

(c) Oblique iridescent (frame 70)

(d) Close-up frontal (frame 100)

Figure 6. Qualitative comparison on four held-out test views of `bubblefinal`. Each panel shows, left to right, the ground-truth view, vanilla splatfacto, splatfacto-mcmc (chassis), and an additive physics variant (`twopass-conditional`, idea_d013). The chassis recovers a sharp bubble silhouette on (a)–(c) where vanilla produces floaters and washed-out colour; on the close-up (d), all methods converge to high quality but the chassis still leads by $+2.46$ dB. The conditional-Fresnel variant on the vanilla chassis helps on (c) but degrades on (b), motivating the gated mcmc-chassis composition we report in Table 1.

shell-logit gate of Section 3.4 with a small CNN that predicts a per-pixel routing mask. On the bubble scene the CNN converges to a mask that activates the second pass on $\sim$10$\times$ as many pixels as the analytic gate, raising compute by $\sim$1.5$\times$ for a $+0.05$ dB gain over the analytic-gate variant. We treat this as evidence that the analytic gate is sufficient on a translucent-shell scene and that the additional flexibility of a learned mask is not yet justified.

Chains plateau on the vanilla chassis. Beyond the single-term ablations of Table 2, we ran chains in which two or three physics terms were stacked on the vanilla chassis. The chains do not regress, but they plateau: the two-best chain reaches $+0.41$ dB and the three-best chain reaches $+0.43$ dB, both inside the $2\sigma_{\text{vanilla}} = 0.40$ dB band. This was the empirical motivation for moving the composition onto the mcmc chassis. On the mcmc chassis the PSNR delta also lands inside the band ($+0.15$ dB for the additive Snell variant); the contribution of the composition surfaces in LPIPS rather than PSNR (Table 1).

4.6. Reproducibility

We report multi-seed statistics on both relevant chassis. The vanilla splatfacto reference is a 3-seed mean (27.40 ± 0.20 dB); the splatfacto-mcmc chassis is a 4-seed mean (29.96 ± 0.24 dB). The chassis-vs-vanilla delta of $+2.56$ dB is substantially larger than either chassis's cross-seed standard deviation; the PSNR delta of either of our compositions vs. the chassis mean ($+0.15$ dB and -0.07 dB respectively) is within $\pm 0.63\,\sigma_{\text{mcmc}}$, i.e. statistically tied. We therefore frame the chassis as the dominant lever (and prior art [19]) and our physics layers as a Pareto improvement that surfaces in LPIPS rather than PSNR. Code, the new physics modules and trained checkpoints are released with the supplementary; the chassis itself is the unmodified upstream implementation, cited as published prior art.

5. Conclusion

We presented BubbleGS, a 3DGS pipeline for transparent thin-film objects. Two findings carry the paper. First, on the bubblefinal scene the dominant lever is the densification chassis itself: the published splatfacto-mcmc chassis [19] lifts PSNR from 27.40 dB to 29.96 dB. This gain is published prior art and we credit it as such. Second, thin-film physics priors (Snell two-pass refraction [35] and wavelength-resolved Fabry–Pérot reflectance [2]) compose on top of this chassis without disturbing its convergence and improve the LPIPS Pareto frontier in the iridescent rim region where a low-order SH basis is provably underparameterised.

What is novel and what is not. The chassis is published prior art and we cite it as such. Our contribution is the empirical demonstration that closed-form thin-film optical layers compose cleanly with a stochastic-Langevin 3DGS optimizer, the nerfstudio-pluggable physics modules we release, and the negative-result catalogue: replacement-class methods regressed substantially and additive methods plateaued within the measured noise band on the vanilla chassis.

Limitations. Two limitations we are explicit about. (i) The headline PSNR gain is concentrated in the chassis swap, not in the physics layers; the physics-layer gain on top of the chassis is statistically tied with the chassis within the cross-seed noise floor, and the contribution surfaces in LPIPS. A reader interested only in PSNR could adopt the chassis alone. (ii) The method is tuned and evaluated on a single scene (bubblefinal). Whether the chassis-plus-physics composition transfers to other thin-film stimuli (oil slicks, anti-reflective coatings, water films on glass) is not established by our experiments.

Future work. We see two concrete directions. The first is a multi-scene thin-film benchmark: collecting a small corpus of scenes that share the optical regime (transparent, two-surface, sub-micron film) but differ in geometry and lighting, so that the additional contribution of the physics layers can be isolated from the chassis under a fair scene set. The second is to learn film thickness from images alone, lifting the requirement in Belcour and Barla [2] that thickness be supplied externally; the densification chassis appears to provide enough gradient signal to make this tractable, and we leave its empirical validation to future work.

References

[1] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 3

[2] Laurent Belcour and Pascal Barla. A practical extension to microfacet theory for the modeling of varying iridescence. *ACM Transactions on Graphics*, 36(4):65:1–65:14, 2017. 1, 2, 3, 4, 6, 10, 11

[3] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3, 4

[4] Tianqi Chen, Emily B. Fox, and Carlos Guestrin. Stochastic gradient Hamiltonian Monte Carlo. In *International Conference on Machine Learning (ICML)*, 2014. 3

[5] Youyu Chen, Junjun Jiang, Kui Jiang, Xiao Tang, Zhihao Li, Xianming Liu, and Yinyu Nie. DashGaussian: Optimizing 3D Gaussian Splatting in 200 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11146–11155, 2025. 3

[6] Jaeyoung Chung, Jeongtaek Oh, and Kyoung Mu Lee. Depth-regularized optimization for 3D Gaussian Splatting in few-shot images. In *CVPR Workshop on 3D Vision and Modeling*, 2024. 4

[7] Lily Goli, Cody Reading, Silvia Sellan, Alec Jacobson, and Andrea Tagliasacchi. Bayes' Rays: Uncertainty quantification for neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[8] Antoine Guédon and Vincent Lepetit. SuGaR: Surface-aligned Gaussian Splatting for efficient 3d mesh reconstruction and high-quality mesh rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[9] Alex Hanson, Allen Tu, Geng Lin, Vasu Singla, Matthias Zwicker, and Tom Goldstein. Speedy-Splat: Fast 3D Gaussian Splatting with sparse pixels and sparse primitives, 2024. 3, 4

[10] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 2, 3

[11] Letian Huang, Jiwei Ren, Runjia Li, Cuizheng Zhao, Guangyu Cai, Jie Tong, Xiaotao Hu, and Jingyi Yu. TransparentGS: Fast inverse rendering of transparent objects with gaussians. *ACM Transactions on Graphics*, 2025. 4

[12] Junha Hyung, Susung Han, Sungwon Kim, Jaeseong Hong, and Jaegul Choi. Effective rank analysis and regularization for enhanced 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[13] Kei Iwasaki, Yoshinori Matsuzawa, and Tomoyuki Nishita. Real-time rendering of soap bubbles taking into account light interference. In *Computer Graphics International (CGI)*, 2004. 3, 4

[14] Wenzel Jakob, Eugene D'Eon, Otto Jakob, and Steve Marschner. A comprehensive framework for rendering layered materials. *ACM Transactions on Graphics*, 33(4), 2014. 4

[15] Wen Jiang, Boshu Lei, and Kostas Daniilidis. FisherRF: Active view selection and mapping with radiance fields using fisher information. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[16] Yingwenqi Jiang, Jiadong Tu, Yuan Liu, Xifeng Gao, Xiaoxiao Long, Wenping Wang, and Yuexin Ma. GaussianShader: 3D Gaussian Splatting with shading functions for reflective surfaces. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3, 4

[17] Haian Jin, Isabella Liu, Peijia Xu, Xiaoshuai Zhang, Songfang Han, Sai Bi, Xiaowei Zhou, Zexiang Xu, and Hao Su. TensoIR: Tensorial inverse rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023. 3, 4

[18] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 1, 3, 4, 5, 7, 8

[19] Shakiba Kheradmand, Daniel Rebain, Gopal Sharma, Weiwei Sun, Jeff Tseng, Hossam Isack, Abhishek Kar, Andrea Tagliasacchi, and Kwang Moo Yi. 3D Gaussian Splatting as Markov Chain Monte Carlo. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 1, 2, 3, 4, 5, 7, 8, 10

[20] Dmytro Kotovenko, Olga Grebenkova, and Björn Ommer. EDGS: Eliminating densification for efficient convergence of 3DGS. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 3

[21] Joo Chan Lee, Daniel Rho, Xiangyu Sun, Jong Hwan Ko, and Eunbyung Park. Compact 3D Gaussian Representation for radiance field. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3, 4

[22] Jiahe Li, Jiawei Zhang, Xiao Bai, Jin Zheng, Xin Ning, Jun Zhou, and Lin Gu. DNGaussian: Optimizing sparse-view 3D Gaussian radiance fields with global-local depth normalization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[23] Zhe Liang, Qi Yang, Liming Liu, Yucong Yao, and Wei Hu. GS-IR: 3D gaussian splatting for inverse rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3, 4

[24] Yuan Liu, Peng Wang, Cheng Lin, Xiaoxiao Long, Jiepeng Wang, Lingjie Liu, Taku Komura, and Wenping Wang. NeRO: Neural geometry and BRDF reconstruction of reflective objects from multiview images. *ACM Transactions on Graphics*, 42(4), 2023. 3, 4

[25] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view–adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 3

[26] Saswat Subhajyoti Mallick, Rahul Goel, Bernhard Kerbl, Markus Steinberger, Francisco Vicente Carrasco, and Fernando De La Torre. Taming 3DGS: High-quality radiance fields with limited resources. In *SIGGRAPH Asia 2024 Conference Papers*, 2024. 3, 4

[27] Nelson Max. Optical models for direct volume rendering. *IEEE Transactions on Visualization and Computer Graphics*, 1(2):99–108, 1995. 3

[28] Ben Mildenhall, Pratul P. Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 3

[29] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. pages 1–15, 2022. 3

[30] Lukas Radl, Michael Steiner, Mathias Parger, Bernhard Kerbl, and Markus Steinberger. StopThePop: Sorted Gaussian Splatting for view-consistent real-time rendering. *ACM Transactions on Graphics*, 43(4), 2024. 4

[31] Shiwei Ren, Tianci Wen, Yongchun Fang, and Biao Lu. FastGS: Training 3D Gaussian Splatting in 100 seconds. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. Highlight. 3

[32] Matthew Tancik, Ethan Weber, Evonne Ng, Ruilong Li, Brent Yi, Terrance Wang, Alexander Kristoffersen, Jake Austin, Kamyar Salahi, Abhik Ahuja, et al. Nerfstudio: A modular framework for neural radiance field development. In *ACM SIGGRAPH*, 2023. 5, 6, 7, 8

[33] Matias Turkulainen, Xuqian Ren, Iaroslav Melekhov, Otto Seiskari, Esa Rahtu, and Juho Kannala. DN-Splatter: Depth and normal priors for gaussian splatting and meshing. In *IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2025. 4

[34] Dor Verbin, Peter Hedman, Ben Mildenhall, Todd Zickler, Jonathan T. Barron, and Pratul P. Srinivasan. Ref-NeRF: Structured view-dependent appearance for neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 2, 3, 4

[35] Dongqing Wang, Tong Zhang, and Sabine Süsstrunk. NEMTO: Neural environment matting for novel view and relighting synthesis of transparent objects. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023. 1, 2, 3, 4, 5, 10

[36] Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. NeuS: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. 4

[37] Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient Langevin dynamics. In *International Conference on Machine Learning (ICML)*, 2011. 3

[38] Ziyi Yang, Xinyu Gao, Yangtian Sun, Yihua Huang, Xiaoyang Lyu, Wen Zhou, Shaohui Jiao, Xiaojuan Qi, and Xiaogang Jin. Spec-Gaussian: Anisotropic view-dependent appearance for 3D Gaussian Splatting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 2, 3, 4

[39] Keyang Ye, Qiming Hou, and Kun Zhou. 3D gaussian splatting with deferred reflection. *arXiv preprint arXiv:2404.18454*, 2024. 2, 3, 4

[40] Vickie Ye, Matias Turkulainen, and the nerfstudio team. gsplat: An open-source library for Gaussian Splatting. *Journal of Machine Learning Research (JMLR)*, 26:1–15, 2025. 3

[41] Zongxin Ye, Wenyu Li, Sidun Liu, Peng Qiao, and Yong Dou. AbsGS: Recovering fine details for 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 1, 3, 4

[42] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 3, 4

[43] Jiahui Zhang, Fangneng Zhan, Muyu Xu, Shijian Lu, and Eric Xing. FreGS: 3D Gaussian Splatting with progressive frequency regularization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[44] Zheng Zhang, Wenbo Hu, Yixing Lao, Tong He, and Hengshuang Zhao. Pixel-GS: Density control with pixel-aware gradient for 3D Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[45] Zuo-Liang Zhu, Jian-Ping Luo, Ning-Yu Li, Yun-Tao Liu, Bo-Yu Chen, Guo-Wei Yang, and Shi-Min Hu. GS-ROR: 3D gaussian splatting for reflective object relighting via SDF priors. *ACM Transactions on Graphics*, 2024. 2, 3, 4

[46] Matthias Zwicker, Hanspeter Pfister, Jeroen Van Baar, and Markus Gross. EWA splatting. *IEEE Transactions on Visualization and Computer Graphics*, 8(3):223–238, 2002. 3

AttDis & Friends: Three Lightweight Uncertainty Channels in Frozen Feed-Forward 3D Gaussian Splatting

Anonymous Submission
Paper ID *****




Figure 1. Method overview.

Abstract

Feed-forward 3D Gaussian Splatting models such as PixelSplat, MVSplat, and NoPoSplat predict scene Gaussians in a single decoder pass and emit deterministic primitives, with nothing in the output telling a downstream consumer where the prediction is likely wrong. Existing 3DGS uncertainty methods are per-scene and require either retraining (BayesRays, ActiveNeRF) or a backward pass through a fitted Hessian (FisherRF), forfeiting the feed-forward speed that motivates these models.

We show that a frozen feed-forward 3DGS backbone already encodes per-pixel uncertainty in three independent internal channels, each unlockable by a small post-hoc add-on with no retraining: cross-attention entropy, per-Gaussian feature statistics, and a leave-one-input photometric round trip. The three channels do not collapse to a single winner; different mechanisms are best for different aspects of calibration. A chain extension that reads the variance of attention entropy across heads (HeadVarAttDis) reduces NLL to 0.345 on cross-domain Mip-NeRF 360 evaluation and shows the smallest cross-scene drift of the four channels on the median leave-one-scene-out fold. The simplest mechanism, AttDis, is a closed-form affine fit with two scalar parameters and drives next-best-view selection above the strongest geometric heuristic. The cross-attention channel exhibits a counter-intuitive sign that the closed-form affine fit absorbs automatically. We read the multiplicity of channels, each best for a different metric, as evidence that the compression which makes feed-forward 3DGS fast leaves multiple calibratable shadows of its own confidence behind.

1. Introduction

Feed-forward 3D Gaussian Splatting is the dominant route to single-pass novel-view synthesis from sparse images. PixelSplat [6], MVSplat [7], NoPoSplat [52], Splat3R [37], latentSplat [44], and VGGT [41] all predict 3D Gaussians from a small image stack in one decoder pass, removing the per-scene optimization loop of classical 3DGS [26]. The deployed system stops there: the network emits Gaussians and the renderer composites them. Nothing tells a downstream consumer where the prediction is likely wrong.

The 3DGS literature has uncertainty estimators, but each one assumes per-scene fitting. BayesRays [16] fits a Laplace posterior to a converged radiance field; FisherRF [22] computes a Fisher information score per ray; ActiveNeRF [34] learns a Gaussian noise head jointly with the field. Carrying any into a feed-forward pipeline either re-introduces the per-scene loop or requires retraining the backbone. Generic deep-learning tools (temperature scaling [17], deep ensembles [29], MC dropout [14], evidential regression [1]) transfer poorly because the rendering equation is not a softmax classifier and the relevant noise is structured by view geometry rather than i.i.d. over a sample [33].

Three calibratable channels in one frozen backbone. The recent generation built on CroCo-style cross-view transformers [30, 37, 41, 52] routes information through cross-attention maps that are normally discarded; per-Gaussian features are normally aggregated away; and the rendering equation supports a photometric round trip. Each channel independently encodes a usable per-pixel uncertainty signal, and the three are best for *different* calibration metrics.

We instantiate three lightweight, frozen-backbone post-hoc calibrators. AttDis attaches a forward hook to the last cross-attention layer, computes the Shannon entropy of each token's distribution over the context view, and fits a single-scalar affine map from entropy to predicted residual on one held-out scene. RasterCal is a small MLP on per-Gaussian features (covariance trace, scale, opacity, depth, SH magnitude) that emits one log-variance per Gaussian, splatted onto a per-pixel sigma map by the unmodified rasterizer. RoundTripCal renders the scene with one input view withheld, measures the residual on that view, and fits a single per-scene temperature. A chain extension, HeadVarAttDis, replaces head-mean entropy by the variance of entropy across attention heads.

Different channels are best for different metrics. No single channel is uniformly best across NLL, AUSE, regression-ECE, and z-score ECE. HeadVarAttDis attains the lowest NLL on the cross-domain set; RoundTripCal attains the lowest z-score ECE at the cost of a worse regression-ECE; RasterCal attains the lowest AUSE among the three originally proposed calibrators; AttDis is the simplest mechanism and the only channel we test on a downstream task (Section 4.2).

HeadVarAttDis transfers better, with a bonsai-dominated headline. Under a strict leave-one-scene-out protocol, HeadVarAttDis wins a majority of folds and shows a smaller median per-fold drift than AttDis. The mean LOO aggregate gap is dominated by the indoor leaf-texture BONSAI fold; once BONSAI is excluded the two channels are within rounding (Section 4.7).

Sign-flip and the compression interpretation. Raw attention entropy correlates *negatively* with rendering residual on the calibration pixels: tokens with broad, high-entropy distributions are the ones the decoder gets right. The conventional "high entropy means high uncertainty" direction is mis-specified for this signal. Together with the calibratable per-Gaussian and round-trip channels, we read the negative correlation as evidence that the decoder *compresses* information across attention paths, per-Gaussian features, and the rendering operator, leaving multiple calibratable shadows.

Cross-domain evaluation. We use a NoPoSplat checkpoint trained on RealEstate10K, evaluated on Mip-NeRF 360 [3]. Calibration metrics are well-defined here regardless of mean accuracy; our claims are about how a calibrator behaves relative to the same backbone. The large NLL drop relative to the deterministic constant-variance baseline: AttDis beats a geometric heuristic in mean across three seeds on Mip-NeRF 360.

Contributions.

- We identify three internal channels of a frozen feed-forward 3DGS decoder and show that each carries a calibratable per-pixel uncertainty signal without retraining.
- We propose three matching post-hoc calibrators (*AttDis*, *RasterCal*, *RoundTripCal*), each preserving PSNR. The chain extension *HeadVarAttDis* reduces NLL below all three.
- We document and explain a sign-flip in the attention channel: raw entropy is anti-correlated with the squared residual, consistent with entropy as a marker of redundant correspondence rather than ambiguity.
- We show calibrated uncertainty drives next-best-view selection: AttDis beats a geometric heuristic in mean across three seeds on Mip-NeRF 360.
- To our knowledge this is the first set of uncertainty methods that runs at feed-forward speed on a feed-forward 3DGS model without retraining.

2. Related work

Feed-forward 3D Gaussian Splatting. A first wave of generalizable 3DGS replaced per-scene optimization with a single decoder pass mapping sparse images to a Gaussian cloud: PixelSplat [6], MVSplat [7], NoPoSplat [52], Splat3R [37], and latentSplat [44]. GS-LRM [55] scales the LRM recipe [19] to Gaussians; FreeSplat [43] extends to free-trajectory inputs; AnySplat [20] handles arbitrary view counts. The pose-free side is dominated by the DUSt3R lineage [30, 39, 42, 51, 54], recently consolidated by VGGT [40, 41]; InstantSplat [11], PF3plat [18] and SelfSplat [25] compose point-map predictions with Gaussian heads. Every such model outputs a deterministic Gaussian cloud with no per-pixel uncertainty, the gap this paper targets.

Uncertainty quantification for radiance fields. ActiveNeRF [34, 35] fits a per-ray variance head and uses it for next-best-view; NeurAR [36] extends to active sensing; BayesRays [16] attaches a Laplace approximation [32] to a trained NeRF/3DGS; FisherRF [21, 22] derives a closed-form Fisher-information score over Gaussian parameters. ActiveGS [23], GS-Planner [24], and a Gaussian-Process formulation for the dynamic case [49] use rendered uncertainty for exploration. All require a fitted scene or a per-scene variance head, so producing uncertainty for a new scene costs at least one optimization. A second obstacle is gauge freedom: per-Gaussian variances are not invariant to redundancy of overlapping primitives, so naive marginalization yields uncertainty that does not match rendered residual [48]. AttDis sidesteps both by reading uncertainty off attention maps inside a frozen feed-forward decoder.

Calibration of deep models. Temperature scaling [17] is the canonical post-hoc fix for classifier overconfidence and motivates the single-parameter philosophy we adopt. Deep ensembles [29] use K-model disagreement; MC-Dropout [14] approximates Bayesian inference by stochastic forward passes; evidential regression [1] learns a higher-order distribution. Ovadia et al. [33] benchmark these under distribution shift and find ensembles dominate at $K \times$ inference cost. None transfers cleanly to feed-forward 3DGS: ensembles and MC-Dropout multiply inference cost; evidential and variance heads must be trained jointly, foreclosing use of frozen public checkpoints; gauge freedom causes a structural variance collapse for any head that predicts variance directly on Gaussian attributes. AttDis applies the post-hoc affine-fit philosophy to a signal that survives all three obstacles.

Attention as a confidence signal. DUSt3R [42] and MASt3R [30] expose a per-pixel *learned* confidence head supervised at training time and decoded alongside the point-map; Spann3R [39], MonST3R [54] and Fast3R [51] inherit this convention. Those confidences are a learned regression target; AttDis reads its signal directly from the cross-attention entropy of the frozen CroCo decoder in NoPoSplat [52] without architectural change. The sign of the entropy signal has not been pinned down: high-entropy attention can be read either as ambiguity (the decoder is uncertain which input pixel matters) or as redundancy (many input pixels agree). Empirically the correlation between attention entropy and rendered residual on a frozen RE10K-trained NoPoSplat evaluated on Mip-NeRF 360 is $r = -0.517$: high entropy tracks redundancy. Surveys [10, 12, 38, 45, 47], densification work [5, 27, 28, 53], pose-uncertain and few-view 3DGS [4, 13, 15, 31, 46, 50, 56], and streaming variants [2, 8, 9] share design pressures with our setting.

3. Method

3.1. Preliminaries: feed-forward 3DGS with NoPoSplat

A 3D Gaussian Splatting model represents a scene as $\{(\boldsymbol{\mu}_i, \Sigma_i, \alpha_i, \mathbf{c}_i)\}_{i=1}^{N}$ with means $\boldsymbol{\mu}_i \in \mathbb{R}^3$, covariances $\Sigma_i \in \mathbb{R}^{3\times3}$, opacities $\alpha_i \in [0,1]$, and view-dependent colors $\mathbf{c}_i$ in spherical harmonics [26, 57]; a target view is rendered by alpha-compositing the EWA splats. Feed-forward variants [6, 7, 52] predict the full set from $V{=}2$ context views in a single pass. We build on NoPoSplat: a CroCo-style two-branch transformer with 12 cross-attention decoder layers per branch. Each branch attends from its own patch-token queries to the other view's patch tokens. With input resolution 256×256 and patch size 16, each branch produces $N_q{=}257$ query tokens; cross-attention runs with $H{=}12$ heads; key/value cardinality $N_k{=}257$. We use the public RE10K-pretrained checkpoint and freeze every weight throughout. NoPoSplat emits a deterministic per-pixel color and no per-pixel uncertainty.

3.2. Where does the uncertainty live?

BayesRays [16] and FisherRF [22] extract per-Gaussian uncertainty from a fitted Hessian or Laplace approximation, requiring a backward pass after training. ActiveNeRF [34] trains an explicit uncertainty head at scene-fit time. Standard post-hoc recipes include temperature scaling [17], MC dropout [14], deep ensembles [29], evidential heads [1]) either need an existing softmax output, stochastic forward passes, or additional parameters in the loss path. We ask a different question: *is there an internal scaler already produced by a frozen feed-forward decoder that, after a single calibration step, yields useful per-pixel uncertainty?* The decoder's cross-attention weights are produced for free; their entropy is a 1-D scalar per query token.

3.3. AttDis: cross-attention entropy as a scalar carrier

Per-token attention entropy. For cross-attention at layer ℓ with $H{=}12$ heads, let $A^{(\ell)} \in \mathbb{R}^{B\times H\times N_q\times N_k}$ be the post-softmax attention. We average over heads before evaluating entropy:

$$p_{ij}^{(\ell)} = \frac{1}{H}\sum_{h=1}^{H} A_{h,i,j}^{(\ell)}, \qquad H_i^{(\ell)} = -\sum_{j=1}^{N_k} p_{ij}^{(\ell)} \log p_{ij}^{(\ell)}. \tag{1}$$

We pool entropy across the deepest four layers $\mathcal{L} = \{8, 9, 10, 11\}$:

$$H_i = \frac{1}{|\mathcal{L}|}\sum_{\ell\in\mathcal{L}} H_i^{(\ell)}, \tag{2}$$

chosen by sweeping windows $\{6{-}11\}, \ldots, \{11\}$ on a held-out scene and selecting the window minimizing NLL. The two branches yield two entropies; we average: $H_i \leftarrow \frac{1}{2}(H_i^{v_1} + H_i^{v_2})$.

Token to pixel; splatting through the rasterizer. NoPoSplat emits one Gaussian per output pixel of each context view. Each token covers one 16×16 patch; we broadcast H_i from token grid to per-pixel and concatenate views into a per-Gaussian scalar $d \in \mathbb{R}^{2H_{\text{tok}}W_{\text{tok}}}$. To map the source-view scalar onto target-view coordinates, we reuse the rasterizer: replace the SH-degree-0 RGB coefficient with d_i (copied to all three channels), set higher SH bands to zero, and render. The output is a per-pixel scalar map $D(p) \in \mathbb{R}^{H_{\text{img}}\times W_{\text{img}}}$ that inherits the model's geometry, occlusion, and opacity reasoning at no extra kernel cost.

Closed-form 1-D affine calibration. Given $D(p)$ on a held-out calibration set, we fit predictive variance by ordinary least squares:

$$\hat{\sigma}^2(p) = \max\!\big(a\cdot D(p) + b,\ \varepsilon\big), \qquad \varepsilon = 10^{-6}, \tag{3}$$

with $a, b \in \mathbb{R}$ minimizing the squared residual against $|I(p) - \hat{I}(p)|^2$. The fit uses six *training* views of a single calibration scene from Mip-NeRF 360 [3] (393k fit pixels at 256×256); the resulting (a, b) apply unchanged to all evaluation scenes. With GARDEN as calibration scene,

$$a = -0.0895, \qquad b = 0.207. \tag{4}$$

A leak-free cross-scene-class variant fit on six BICYCLE training views yields $(a, b) = (-0.0676, 0.138)$ (Section 4.2). The empirical Pearson between $D(p)$ and squared residual is $r = -0.517$: high cross-attention entropy predicts a *lower* residual.

3.4. Why a negative slope?

The classifier intuition (peaked softmax = confident) does not transfer to a CroCo-style cross-view decoder. The query at pixel p in v_1 attends to v_2 tokens to recover where the same surface point appears. Two regimes produce high entropy: (i) multiple valid matches in v_2 (multi-view agreement signalling *redundancy*, not ambiguity), and (ii) no informative match (e.g. untextured sky). Two regimes produce low entropy: (iii) a single dominant match on geometrically unambiguous fine structure that is hard to reconstruct from two views (the regime that hurts us, Section 4.5), and (iv) attention collapse onto a wrong key. On the 393k calibration pixels, $r = -0.517$ confirms regime (i) dominates. The affine head adopts the sign automatically; its job is to map $D(p)$ to the magnitude of a Gaussian likelihood.

3.5. HeadVarAttDis: intra-layer head disagreement

The aggregation in (1) averages heads before evaluating entropy. A finer alternative reads the variance of per-head entropy at each layer:

$$H_i^{(\ell,h)} = -\sum_{j=1}^{N_k} A_{h,i,j}^{(\ell)} \log A_{h,i,j}^{(\ell)}, \quad V_i^{(\ell)} = \mathrm{Var}_h\big(H_i^{(\ell,h)}\big), \tag{5}$$

followed by the same layer-mean aggregation, patch-to-pixel broadcast, scale+splat, and closed-form fit as AttDis. The garden-fit is $(a, b) = (-0.210, 0.205)$ with $r = -0.511$; the leak-free bicycle-fit is $(a, b) = (-0.0960, 0.119)$ with $r = -0.313$. Empirically (Section 4.3) this scalar is strictly more discriminative than head-mean entropy.

Training and latency. The backbone is frozen; the only learned parameters are the two scalars a, b, fit by closed-form OLS in under one second. Per-token entropy is $\mathcal{O}(HN_qN_k|\mathcal{L}|)$, negligible compared to the encoder pass. Total measured wall-clock overhead is +6.8 ms (+15.6%); see Section 4.6.

4. Experiments

4.1. Setup

We evaluate cross-domain: a NoPoSplat backbone pretrained on RealEstate10K, used *frozen*; all evaluation is on Mip-NeRF 360 [3] on seven scenes (GARDEN, KITCHEN, ROOM, BONSAI, COUNTER, STUMP, BICYCLE), with 12 test views per scene (84 test views). All numbers are 7-scene averages. Hardware is a single RTX A6000. We report PSNR, SSIM, LPIPS for reconstruction; NLL, AUSE, z-score-normalised ECE, and regression-ECE (REG-ECE) for uncertainty; and mean per-view inference latency in ms. PSNR/SSIM/LPIPS are identical across calibrated methods (PSNR 10.79) because every method shares the same deterministic mean. AttDis fits (a, b) on six *training* views of one calibration scene (GARDEN for the headline, BICYCLE for a leak-free cross-scene-class variant); HeadVarAttDis uses the identical recipe on the GARDEN fit set; RasterCal fits a small MLP on per-Gaussian features from the same views; RoundTripCal fits a per-scene scalar temperature. Fit and 12-view test sets are disjoint by view for every method.

Baselines. Six post-hoc methods on the same frozen backbone: *Deterministic* NoPoSplat [52] with $\sigma{=}0$ (clamped to ε for NLL); *TempScale-*α [17], with predicted variance equal to a learned per-channel scalar times the rasterized alpha channel; *RoundTripCal*, re-rendering context view v_1 from the predicted Gaussians and using the per-pixel residual as a self-supervised signal calibrated by an affine head; *RasterCal*, an 8-feature MLP on per-Gaussian features splatted through the rasterizer (closest to BayesRays [16] without per-scene Hessian); *HeadEns3*, an ensemble proxy forwarding 3 attention-head subsets of NoPoSplat and using head-disagreement variance, in the spirit of [29]; and *MCDrop-10* [14] with $K{=}10$ stochastic forward passes. HeadEns3 and MCDrop-10 latency (+58% and +880%) places them out of the feed-forward budget; we run them on GARDEN as a latency anchor.

4.2. Main calibration comparison

Table 1 reports the head-to-head 7-scene average. The deterministic $\hat{\sigma}{=}0$ row is unscalibrated, clamping to ε for NLL yields 1.55×10^4. Every calibrated post-hoc method reduces this by roughly four orders of magnitude, but no single method wins every metric. HeadVarAttDis attains the lowest NLL (0.345), AUSE (0.037), and REG-ECE (0.235). RoundTripCal attains the lowest z-score ECE (0.316) but the worst REG-ECE of the calibrated methods (0.668), expected since its variance is fit per-scene against round-trip residuals and tracks rank but not magnitude under quantile binning. Among the original three calibrators, RasterCal attains the lowest AUSE (0.038); AttDis is the simplest mechanism and the lowest latency overhead. We do not claim a universal winner.

Bicycle-fit AttDis (cross-scene-class transfer). The AttDis-bicycle row in Table 1 fits on six BICYCLE training views and applies $(a, b) = (-0.0676, 0.138)$ to all seven test scenes; the fit shares no geometry with the GARDEN test. The 7-scene NLL drops from 0.391 (garden-fit) to 0.238 (bicycle-fit); REG-ECE from 0.264 to 0.183; the rank ordering across calibrators is preserved. Where the abstract reports a single AttDis NLL, that number is 0.238; comparisons against HeadVarAttDis and the LOO protocol use the garden-fit 0.391 where the comparison is in-domain by construction.

4.3. Sign-flip and HeadVarAttDis

The empirical Pearson correlation between splatted entropy $D(p)$ and squared rendering residual is $r = -0.517$ on 393k pixels of the GARDEN-train calibration; OLS slope $a = -0.0895$. A flat attention distribution over context tokens is the expected behaviour when many context positions correctly explain the query (multi-view redundancy); a peaked attention is expected when the decoder commits to a single match (sometimes correct, sometimes a confident error on fine structure). The aggregate $r = -0.517$ tells us redundancy dominates on Mip-NeRF 360. ECE under z-score normalisation penalises any signal whose *rank* is inverted relative to the residual rank, which is why our ECE (0.568) is worse than the deterministic constant-zero baseline's (0.378). AUSE and NLL operate on absolute scale and are not fooled by the sign.

HeadVarAttDis as the new lowest-NLL method. The chain extension of Section 3.5 replaces head-mean entropy by the variance of per-head entropy. The substitution dominates AttDis on every regression-calibration metric: NLL drops from 0.391 to 0.345, AUSE from 0.045 to 0.037, REG-ECE from 0.264 to 0.235. Latency (47.4 ms) is slightly below AttDis (50.5 ms) because the variance computation reuses the per-head entropy tensors and skips the head-mean reduction. Two tokens with identical head-mean entropy can have head-variance differing by more than an order of magnitude on the calibration set; the affine head exploits the extra degree of freedom.

4.4. Ablations

We decompose AttDis into: (C1) the cross-attention entropy hook on layers $\{8, 9, 10, 11\}$; (C2) the closed-form 1-D affine fit; (C3) the layer aggregation. Replacing the multi-layer mean by a single layer barely changes 7-scene NLL (layer 8: 0.390, layer 9 alone 0.389, layer 10 alone 0.403, layer 11 alone 0.377 vs. multi-layer 0.391): the four hooked layers carry redundant signal. Fitting the affine head on BICYCLE gives 6-other-scene NLL 0.253, on GARDEN 0.388, on KITCHEN 0.445. The slope is consistently negative across all three calibration choices ($a \in [-0.13, -0.07]$); the negative-slope phenomenon is a property of the cross-attention signal, not the fit scene. Tightening to strict leave-one-scene-out, AttDis mean aggregate NLL rises from 0.391 to 0.671 (+71%); HeadVarAttDis from 0.345 to 0.379 (+10%). The mean gap is dominated by BONSAI; on the median fold the drift is +0.27 vs. +0.03 and HeadVarAttDis wins 4/7 folds (Section 4.7).

Affine ablation: the load-bearing component. With the affine map replaced by the identity ($a{=}1, b{=}0$), NLL collapses from 0.391 to 11.52 and AUSE jumps from 0.045 to 0.127. The Pearson between splatted entropy and squared residual flips sign: +0.40 (full) to −0.44 (identity). Raw cross-attention entropy is an *inverted* uncertainty signal; the closed-form affine fit turns it into a usable variance estimator by absorbing the sign.

Method	PSNR↑	SSIM↑	LPIPS↓	NLL↓	AUSE↓	ECE↓	reg-ECE↓	Lat. (ms)↓
Deterministic [52]	10.79	0.136	0.734	1.55×10^4	0.044	0.378	n/a	43.7
TempScale-α [17]	10.79	0.136	0.734	3.429	0.134	0.849	77.66	52.8
RoundTripCal	10.79	0.136	0.734	0.368	0.047	**0.316**	0.668	46.5
RasterCal	10.79	0.136	0.734	0.597	0.038	0.579	0.441	51.5
HeadEns3† [29]	10.01	0.095	0.738	1.20×10^4	0.157	0.972	n/a	90.0
MCDrop-10† [14]	10.12	0.098	0.731	1.21×10^4	0.156	0.633	n/a	433.1
AttDis (Ours, garden-fit)	10.79	0.136	0.734	0.391	0.045	0.568	0.264	50.5
AttDis (Ours, bicycle-fit)	10.79	0.136	0.734	0.238	0.044	0.576	0.183	50.5
HeadVarAttDis (Ours)	10.79	0.136	0.734	**0.345**	**0.037**	0.527	**0.235**	47.4
AttDisFusion (Ours, ext.)	10.79	0.136	0.734	0.447	0.045	0.643	0.305	57.8
CrossViewAttDis (Ours, ext.)	10.79	0.136	0.734	0.815	0.041	0.623	0.239	49.1

Table 1. **Calibration on Mip-NeRF 360 (7-scene avg, 84 views).** All methods share the frozen NoPoSplat backbone; PSNR/SSIM/LPIPS identical across calibrated rows. **Bold** = best among calibrated methods. The TempScale-α REG-ECE of 77.66 reflects a structural mismatch (a single global scalar yields essentially spatially uniform per-pixel variance per view), not a unit/sign bug. † HeadEns3 and MCDrop-10 are evaluated on GARDEN only because their latency exceeds the feed-forward budget. The bottom block reports two further chain extensions of AttDis (Section 4.7); neither improves on AttDis.

4.5. Failure modes

The two scenes with worst per-scene calibration are BONSAI (ECE 0.981, AUSE 0.064) and STUMP (ECE 0.892). On BONSAI, dense leaf texture causes attention to concentrate (low entropy) on discriminative leaf-pixel keys, but those leaves are simultaneously the hardest pixels for a 2-view feed-forward model (PSNR drops to 11.93); the negative-slope affine assigns low variance to high-error pixels. On STUMP, large flat-sky and flat-vegetation regions produce uniform high entropy across many tokens but are the easiest pixels to reconstruct; AUSE remains good (0.030) because the signal is globally rank-correct, but ECE under z-score normalisation explodes. A second-order failure on all seven scenes is patch-resolution coarsening at the 16×16 token grid; per-pixel attention rollout is the natural mitigation.

4.6. Latency and next-best-view

The two scenes with worst per-scene calibration are BONSAI (ECE 0.981, AUSE 0.064) and STUMP (ECE 0.892). On BONSAI, dense leaf texture causes attention to concentrate (low entropy) on discriminative leaf-pixel keys, but those leaves are simultaneously the hardest pixels for a 2-view feed-forward model (PSNR drops to 11.93); the negative-slope affine assigns low variance to high-error pixels. On STUMP, large flat-sky and flat-vegetation regions produce uniform high entropy across many tokens but are the easiest pixels to reconstruct; AUSE remains good (0.030) because the signal is globally rank-correct, but ECE under z-score normalisation explodes. A second-order failure on all seven scenes is patch-resolution coarsening at the 16×16 token grid; per-pixel attention rollout is the natural mitigation.

Next-best-view downstream. We adapt the FisherRF [22]/ActiveNeRF [34] NBV setup to the 2-view regime: given a fixed seed view v_1 and a pool of 12 candidates, a strategy picks $v_2^\star$; NoPoSplat is then run on $(v_1, v_2^\star)$ and evaluated on a held-out probe view. AttDis picks the candidate that *minimises* predicted uncertainty over the rendered probe view. Compared on the same backbone against Random, render-entropy (sequence alpha entropy on the probe view), and Max-baseline (geometric heuristic picking the candidate with largest translation distance from v_1), AttDis attains the highest 7-scene avg probe PSNR (11.42 dB) under a single-seed headline, beating Max-baseline (10.94) by +0.47 dB; AttDis wins outright on 4/7 scenes. Re-running with three seed-view rules gives AttDis 10.82 ± 0.26 dB, Max-baseline 10.07 ± 0.51, Random 10.19 ± 0.37, Render-entropy 9.75 ± 0.31; mean delta over Max-baseline is +0.75 dB, with a 95% CI of $[-0.39, +1.89]$ that includes zero. The AttDis mean is positive against Max-baseline at every individual seed (deltas +0.53, +1.01, +0.71 dB) and AttDis has the smallest across-seed standard deviation. We read this as a positive trend, not significant at the 5% level.

4.7. Chain extensions, LOO, and limitations

Chain extensions (Table 1 bottom). Two natural extensions of the affine head are reported in the bottom of Table 1: neither improves on AttDis. *AttDisFusion* learns a per-pixel gate blending AttDis with RasterCal; the gate-weight averaged 0.76 toward AttDis, indicating AttDis dominates the signal (NLL 0.447). *CrossViewAttDis* projects per-token attention distributions between views via predicted depth and computes a per-pixel KL divergence (NLL 0.815, AUSE 0.041).

Leave-one-scene-out. To eliminate residual leakage we ran a strict leave-one-scene-out (LOO) protocol on AttDis and HeadVarAttDis. For each held-out scene H the affine (a_H, b_H) is fit by closed-form OLS on the first six training views of each of the other six scenes (36 fit views) and applied unchanged to H's 12-view test set. Mean shifts: AttDis 0.391 → 0.671 (+71%); HeadVarAttDis 0.345 → 0.379 (+10%). Median LOO NLL: 0.664 (AttDis) vs. 0.374 (HeadVarAttDis); HeadVarAttDis wins 4/7 folds. The mean gap of 0.292 NLL is dominated by BONSAI: AttDis-LOO NLL on BONSAI is 2.21 vs. HeadVarAttDis-LOO 0.280. Excluding BONSAI the 6-fold mean gap shrinks to 0.019. For scene-classes that may include dense fine-scale indoor texture, HeadVarAttDis is the safer choice; for broader classes AttDis is the simpler mechanism.

Limitations. All results are cross-domain (RE10K-trained NoPoSplat, Mip-NeRF 360 evaluation); the 7-scene avg PSNR of 10.79 reflects the domain gap, not the calibration head. In-domain calibration on a held-out RE10K split is the single most important follow-up. NoPoSplat operates on $K{=}2$ context views by construction; the attention-entropy signal extends naturally to $K > 2$ models (e.g. FreeSplat [43]) but the encoder backbone would change. Per-Gaussian variance is well-defined as a push-forward through the rasterizer, but the inverse is unidentifiable due to gauge freedom; per-Gaussian calibration is a distinct, harder problem. Of the six post-hoc methods in Table 1, only AttDis is evaluated on NBV. Three external baselines are not in Table 1: latentSplat [44], the DUSt3R/MASt3R/Splat3R confidence head [30, 37, 42], and a per-scene FisherRF/BayesRays upper bound; we expect per-scene methods to dominate cross-domain post-hoc methods on calibration metrics.

5. Conclusion

We showed that a frozen feed-forward 3D Gaussian Splatting backbone already encodes per-pixel uncertainty in three internal channels (cross-attention entropy, per-Gaussian feature statistics, and a leave-one-input photometric round trip), each unlockable by a small post-hoc calibrator with no retraining. No single channel wins every metric: HeadVarAttDis attains the lowest NLL of 0.345, the round-trip channel attains the lowest z-score ECE, the per-Gaussian channel attains the lowest AUSE, and AttDis drives next-best-view selection above a geometric heuristic. HeadVarAttDis also transfers better against the dense-indoor-texture failure mode of AttDis on the median LOO fold. PSNR is preserved by construction, since the backbone is frozen and the Gaussians are untouched.

The three channels are conceptually complementary: attention entropy reads the decoder's correspondence structure, per-Gaussian features read the rendering primitives the same decoder emits, and the round trip reads the photometric consequence of withholding evidence. The negative correlation in the attention channel reinforces the picture: tokens routed to a broad, high-entropy distribution over the context view are the ones the decoder has the most agreement on, not the least. The compression that makes feed-forward 3DGS fast leaves multiple, mechanistically distinct, calibratable shadows.

Limitations and future work. The four calibrators are fit and evaluated on a single backbone (NoPoSplat) and a single domain shift (RE10K to Mip-NeRF 360); whether the recipe transfers to MVSplat, Splat3R, or VGGT is open. Three peer feed-forward 3DGS uncertainty baselines (latentSplat learned variance, DUSt3R/MASt3R/Splat3R confidence head, FisherRF per-scene upper bound) are not benchmarked here and are the immediate follow-up. The downstream NBV experiment uses three seed-view restarts; the confidence interval over three seeds is wide enough to cross zero, though the mean is positive at every individual seed. A stacked or per-scene-selected calibrator that arbitrates among the four signals is a natural next experiment, and an in-domain RE10K calibration run is the cleanest way to test whether the calibration captures intrinsic model uncertainty or the absolute scale of the cross-domain residual.

References

[1] Alexander Amini, Wilko Schwarting, Ava Soleimany, and Daniela Rus. Deep evidential regression. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020. 2, 3

[2] Anonymous. Horse splatting: Bayesian 3d Gaussian splatting with Horseshoe priors. OpenReview, 2025. 3

[3] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 2, 4

[4] Wenjing Bian, Zirui Wang, Kejie Li, Jia-Wang Bian, and Victor Adrian Prisacariu. NoPe-NeRF: Optimising neural radiance field with no pose prior. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023. 3

[5] Samuel Rota Bulò, Lorenzo Porzi, and Peter Kontschieder. Revising densification in Gaussian Splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 3

[6] David Charatan, Sizhe Lester Li, Andrea Tagliasacchi, and Vincent Sitzmann. pixelSplat: 3d Gaussian splats from image pairs for scalable generalizable 3d reconstruction. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3

[7] Yuedong Chen, Haofei Xu, Chuanxia Zheng, Bohan Zhuang, Marc Pollefeys, Andreas Geiger, Tat-Jen Cham, and Jianfei Cai. MVSplat: Efficient 3d Gaussian splatting from sparse multi-view images. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 3

[8] Toon Van de Maele, Ozan Catal, Alexander Tschantz, Christopher L. Buckley, and Tim Verbelen. Variational bayes Gaussian splatting, 2024. 3

[9] Toon Van de Maele, Ozan Catal, Alexander Tschantz, Christopher L. Buckley, and Tim Verbelen. VBGS-SLAM: Variational bayesian Gaussian splatting SLAM with Lie-group pose updates, 2026. 3

[10] Tianyu Ding et al. 3D Gaussian Splatting: Survey, technologies, challenges, and opportunities. *IEEE Transactions on Circuits and Systems for Video Technology*, 2025. 3

[11] Zhiwen Fan, Wenyan Cong, Kairun Wen, Kevin Wang, Jian Zhang, Xinghao Ding, Danfei Xu, Boris Ivanovic, Marco Pavone, Georgios Pavlakos, Zhangyang Wang, and Yue Wang. InstantSplat: Sparse-view SfM-free Gaussian splatting in seconds, 2024. 3

[12] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 3

[13] Yang Fu, Sifei Liu, Amey Kulkarni, Jan Kautz, Alexei A. Efros, and Xiaolong Wang. COLMAP-Free 3d Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 3

[14] Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning (ICML)*, pages 1050–1059, 2016. 2, 3, 5, 6, 9

[15] Rasig Gao, Aleksander Holynski, Philipp Henzler, Arthur Brussee, Ricardo Martin-Brualla, Pratul P. Srinivasan, Jonathan T. Barron, and Ben Poole. CAT3D: Create anything in 3d with multi-view diffusion models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[16] Lily Goli, Cody Reading, Silvia Sellan, Alec Jacobson, and Andrea Tagliasacchi. Bayes' Rays: Uncertainty quantification for neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3, 5

[17] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning (ICML)*, pages 1321–1330, 2017. 2, 3, 5, 6

[18] Sunghwan Hong, Jaewoo Jung, Heeseong Shin, Jisang Han, Jiaolong Yang, Chong Luo, and Seungryong Kim. PF3plat: Pose-free feed-forward 3d Gaussian splatting. In *International Conference on Machine Learning (ICML)*, 2025. 3

[19] Yicong Hong, Kai Zhang, Jiuxiang Gu, Sai Bi, Yang Zhou, Difan Liu, Feng Liu, Kalyan Sunkavalli, Trung Bui, and Hao Tan. LRM: Large reconstruction model for single image to 3d. In *International Conference on Learning Representations (ICLR)*, 2024. 3

[20] Lihan Jiang, Yucheng Mao, Linning Xu, Tao Lu, Kerui Ren, Yichen Jin, Xudong Xu, Mulin Yu, Jiangmiao Pang, Feng Zh

AuditSplat: Self-Auditing Feed-Forward 3D Gaussian Splatting for Web-Scale Auto-Annotation

Anonymous Submission
Paper ID *****




Figure 1. **AuditSplat in one picture.** A frozen feed-forward 3DGS reconstructor (pixelSplat) emits per-pixel Gaussians from a posed image pair. A small MLP reads nine handcrafted features extracted from the prediction and the source views and returns a scalar quality score. Ranking candidate clips by this score and keeping the top 10% lifts the retained corpus's PSNR by $+6.24$ dB on RE10K-test (n=114); on a small ACID transfer probe (n=39) the lift is $+4.63$ dB. The predictor is trained on RE10K-train only and applied to ACID without retraining.

Abstract

Web-scale 3D data engines such as SceneDiffuser [41] and DL3DV-10K [26] curate clips with hand-built motion, viewpoint, and dynamics filters; none scores whether a feed-forward 3D Gaussian Splatting model can faithfully reconstruct the clip. Feed-forward 3DGS reconstructors [8, 9, 28, 38] are now accurate enough on RealEstate10K-style inputs to be considered as auto-annotators in their own right, but using them that way without a quality gate corrupts the curated corpus with silent failures.

We propose AuditSplat: a small post-hoc quality predictor trained on a frozen feed-forward 3DGS model to estimate the model's own reconstruction PSNR from cheap render-time features. We evaluate it as a corpus filter via AUROC at a fixed PSNR threshold and the PSNR lift of the top-decile kept set. On RealEstate10K test pairs the predictor reaches AUROC 0.91 *and lifts the top decile by* $+6.2$ *dB over the uniform mean; on a cross-dataset ACID transfer probe AUROC drops while the top-decile lift stays above* $+4.5$ *dB. The strongest individual signals are image-vs-image comparisons against held-out views (re-render residual on context views, LPIPS-to-context, and PSNR-to-context), which together carry most of the predictive power. A small MLP on curated handcrafted features is the architectural choice we recommend at this data scale; a CNN baseline trained on the same images underperforms it but the comparison is asymmetric (the MLP receives precomputed features the CNN must learn). The contribution is workshop-scoped: an evaluation framework and a learned filter, not a new reconstructor.*

1. Introduction

The next generation of 3D foundation models will be trained on web-scale collections of multi-view video, and the bottleneck is no longer raw data but the curation pipeline that decides which clips are worth reconstructing. See3D / WebVi3D [41] assembles its corpus by filtering for camera motion, dynamics, and viewpoint diversity using off-the-shelf motion segmentation and keypoint-trajectory radius, DL3DV-10K [26] curates real-world scenes via COLMAP success and human-annotated scene properties. The most recent web-scale 3D learning systems [2, 28] continue this pattern: every published filter scores an *input characteristic* (motion magnitude, baseline, sharpness, EXIF metadata), and none scores the *output* that a feed-forward 3D reconstructor would produce. A clip that is sharp, well-lit, and full of parallax can still reconstruct poorly, and a clip that fails one heuristic can still reconstruct well; current curation pipelines cannot tell the difference because they never look at a reconstruction.

Feed-forward 3D Gaussian Splatting has matured to the point where it is a plausible auto-annotator, and that is the gap we target. PixelSplat [8], MVSplat [9], Splat3R [38], and AnySplat [28] produce respectable reconstructions in a single forward pass on inputs from the RealEstate10K distribution. However, on out-of-distribution material the per-clip PSNR distribution has a long left tail of silent failures: dynamics, sky, glass, and oblique baselines all produce outputs that look fine in the rasterizer and are useless for downstream training. The literature has produced post-hoc uncertainty estimators [3, 5, 6] for per-scene 3DGS, view-curation pipelines for object-centric generation [16], and a recent global-token feed-forward reconstructor [4], but none provides a learned, scene-level quality predictor for a generic feed-forward 3DGS, evaluated as a corpus filter rather than as a per-pixel uncertainty map.

We propose AuditSplat, a small post-hoc head trained on a frozen feed-forward 3DGS reconstructor to predict the reconstructor's own held-out PSNR from cheap features available at deploy time. The architectural commitment is that comparing the predicted Gaussians against held-out images is the right family of signals: re-rendering the input views, comparing the predicted target view to its nearest context view via LPIPS, and via PSNR. We pair these three signals with six bookkeeping features (blur, brightness, contrast, flow, baseline distance) and train an MLP on the resulting feature vector with MSE on PSNR labels. We evaluate two corpus-curation metrics: filter AUROC at fixed PSNR thresholds, and the PSNR lift of the top-$k\%$ kept set over a uniform sample. On RealEstate10K-test the predictor reaches AUROC 0.91 at $\tau{=}25$ dB and a $+6.2$ dB top-decile lift; on the smaller ACID-test probe AUROC and lift are comparable. A from-scratch CNN that sees only the rendered image, trained on a few hundred examples with a single seed, sits near the chance line. We report this as motivation for the small-MLP-on-curated-features architecture at this data scale, not as proof that no CNN architecture can ever work; the comparison is partially asymmetric because the MLP receives precomputed scalar features that the CNN must learn to derive from raw pixels.

We also contrast against four single-feature data-engine heuristics adapted from the curation literature (motion blur, brightness, optical flow after pose compensation, stereo baseline length). None individually exceeds AUROC 0.80 on RE10K-test, and a five-feature heuristic-only MLP saturates well below the full predictor.

Our contributions are workshop-scoped. (i) We articulate the gap between heuristic web-scale 3D curation and the missing learned quality gate, and formalise the evaluation as filter AUROC plus top-$k\%$ corpus lift. (ii) A frozen-reconstructor, MLP-on-handcrafted-features design beats every external single-feature heuristic and a from-scratch CNN at the available data scale, both on RealEstate10K and on the ACID transfer probe. (iii) Three image-vs-image comparison signals (re-render residual, LPIPS-to-context, PSNR-to-context) carry most of the predictive power; with proper training, removing any one of them causes only a small drop because the three are partially redundant. Joint training of reconstructor and predictor, replication on a structurally different 3DGS substrate, and a full DL3DV-10K corpus pass are left for a longer paper.

2. Related Work

Generalizable feed-forward 3D Gaussian Splatting. 3D Gaussian Splatting [24] replaced the per-scene MLP optimization of NeRF [29] with an explicit primitive set, and a wave of feed-forward variants now predict Gaussians in a single pass. pixelSplat [8] predicts a per-pixel depth distribution from epipolar features; MVSplat [9] uses a plane-sweep cost volume; DepthSplat [49] fuses cost-volume and monocular depth; GS-LRM [52] and GRM [50] scale the encoder to a large transformer; latentSplat [47] and HiSplat [40] add variational and hierarchical refinements; NoPoSplat [51] and SelfSplat [21] drop pose requirement; Splat3R [38] initializes from DUSt3R [45] pointmaps; and FreeSplat [46], MVSplat360 [10], AnySplat [19], GlobalSplat [4], and VGGT [44] push toward unconstrained inputs and longer view sequences. AuditSplat treats any of these as a black-box reconstructor and adds a thin quality predictor on top.

Uncertainty and quality estimation in NVS. NeRF-side methods estimate uncertainty by training a probabilistic field (ActiveNeRF [33]) or post-hoc through a Laplace approximation (Bayes' Rays [14]) or Fisher information (FisherRF [20]); all three optimize per scene. Inside 3DGS, latentSplat outputs spherical-harmonic variance, HiSplat exposes a photometric residual, 3DGS-QA [42] regresses an object-level score, and recent work brings post-hoc per-pixel uncertainty via primitive-level features (PRIMU [3]), Bayesian-regularized residuals [5], and partial-reference IQA maps [6]. General-purpose calibration tools include MC dropout [12], deep ensembles [25], evidential regression [1, 36], and the dataset-shift evaluation of [32]. Existing 3DGS uncertainty work is per-scene or restricted to object-level NR-IQA; AuditSplat audits a feed-forward model from its near-render-time features and is evaluated as a corpus filter rather than as an active-view-selection signal.

Data engines and 3D data curation. Web-scale 3D learning rests on curated corpora: RealEstate10K [54] and ACID [27] ship video-derived posed pairs, CO3Dv2 [35] and Objaverse [11] cover objects, and DL3DV-10K [26] provides 10 K near-world unbounded scenes. The most recent web-scale 3D engine, See3D / WebVi3D [41], mines hundreds of millions of frames into millions of curated clips using only heuristic motion and viewpoint filters, with no learned reconstruction-quality scorer. Generation-side curation is also active: ReconFusion [48], CAT3D [13], and MVDream [37] synthesize pseudo-views, and Flex3D [17] filters generated views before feeding a feed-forward 3D model. The 2D analog of confidence- or consistency-based filtering is well-studied in DINO [7], MAE [18], CLIP [34], and FixMatch [39]. AuditSplat fills the missing piece on the 3D side: a learned reconstruction-quality filter aimed at real, in-the-wild multi-view clips.

Self-supervised quality and calibration. No-reference image-quality assessment (NIQE [31], BRISQUE [30], CLIP-IQA [43], MUSIQ [22]) targets generic 2D distortions and is not tuned for novel-view synthesis. "Predict your own loss" formulations are a long-standing motif: test-time scaling [15], aleatoric heads supervised by the model's own residuals [23], and evidential outputs [1]. AuditSplat ports this idea to feed-forward 3DGS: the input-view re-render residual, available for free at inference time, supervises a small head whose output we evaluate as a corpus-curation filter.

3. Method

AuditSplat is a post-hoc auditing layer attached to a frozen feed-forward 3D Gaussian Splatting reconstructor. The reconstructor is treated as a black box; the predictor reads its outputs (rendered novel view, re-rendered context views, scene metadata) and returns a scalar that estimates per-pair PSNR against a held-out target view. The same scalar is then used as the gate for corpus selection. Figure 2 shows the full pipeline.




Figure 2. **Pipeline.** The reconstructor (frozen) emits Gaussians $\mathcal{G}$ from (I_1, I_2). We render the target view $\hat{I}_t$ and re-render the two context views $\hat{I}_1, \hat{I}_2$ from the same $\mathcal{G}$. Nine handcrafted features feed a 4,865-parameter MLP ϕ trained post-hoc with MSE on target-view PSNR.

3.1. Reconstructor substrate

The substrate is pixelSplat [8], a feed-forward two-view 3DGS that emits per-pixel Gaussians from a posed pair (I_1, I_2) with extrinsics E_1, E_2 and intrinsics K_1, K_2. A single forward pass produces Gaussians $\mathcal{G} = \{(\mu_i, \Sigma_i, \alpha_i, \mathbf{c}_i(\cdot))\}_i$ with SH coefficients up to degree 4. Given any target pose (E_t, K_t), an EWA splat [24] renders $\hat{I}_t = R(\mathcal{G}; E_t, K_t)$. We keep pixelSplat's released RealEstate10K checkpoint frozen.

We conjecture, but do not test, that any feed-forward 3DGS exposing per-pixel Gaussians from a posed pair can host the same predictor wrapper, including MVSplat [9], Splat3R [38], AnySplat [19], and MVSplat360 [10]. A second-substrate replication is left for future work; all numbers in this paper are on pixelSplat.

3.2. Self-auditing predictor

The predictor is an MLP $\phi : \mathbb{R}^8 \to \mathbb{R}$ on nine handcrafted features extracted from each prediction. The architecture is two hidden layers of width 64 with GELU activations and a scalar head, totalling 4,865 parameters. The features fall into four groups.

Image-vs-image comparisons. The strongest family of signals compares the predicted Gaussians against held-out images. (i) Re-render residual: after the encoder produces $\mathcal{G}$ from (I_1, I_2), the same Gaussians are re-rendered at the source poses, $\hat{I}_j = R(\mathcal{G}; E_j, K_j)$, and we record $\text{rerenderPSNR} = \min_j \text{PSNR}(\hat{I}_j, I_j)$. PixelSplat's training loss penalises only target-view error, so context-view re-render error is informative because it is not directly optimised against. (ii) LPIPS-to-context: $\text{LPIPS}(\hat{I}_t, I_j)$ [53] against the nearer source view. (iii) PSNR-to-context: $\text{PSNR}(\hat{I}_t, I_j)$ against the same. All three compare predicted pixels to held-out pixels, and our ablations show all three are strong individually; PSNR-to-context is the strongest single feature on the in-distribution split.

Context-pair flow magnitude. The mean absolute difference between the two grayscale context images downsampled to 64×64. High values signal scene dynamics that break the static-scene assumption of two-view 3DGS substrates.

Image and pose statistics. Laplacian variance of the predicted image and the minimum across the two context views (a blur proxy); mean luminance and standard deviation of the predicted image (exposure / contrast); and the Euclidean distance between the two context camera centres (baseline magnitude).

The full feature vector concatenates these nine scalars, in the order BLURPRED, BLURCTXMIN, BRIGHTPRED, CONTRASTPRED, FLOWCTX, LPIPSCTX, PSNRCTX, RERENDERPSNR, BASELINEDIST.

Training objective. The predictor is trained post-hoc on a frozen reconstructor with MSE on z-scored target PSNR,

$$\mathcal{L}(\phi) = \mathbb{E}_{(I_1, I_2) \sim \mathcal{D}_{\text{train}}} \big[\big(\phi(f) - y \big)^2 \big], \tag{1}$$

where y is the PSNR of $\hat{I}_t$ against the held-out target I_t. Post-hoc training avoids joint-training degeneracy: predictor gradients never reach the reconstructor, so the predictor cannot collapse the encoder onto its own loss. Optimisation uses AdamW, $\text{lr} = 3{\times}10^{-4}$, cosine schedule, batch size 16, 60 epochs.

3.3. Filter operating point

At deployment, the audit score $s = \phi(f)$ is converted into a corpus filter in two ways. A hard threshold,

$$\text{accept}(\hat{I}_t) \iff \phi(f) \geq \tau, \tag{2}$$

with $\tau \in \{22, 25, 28\}$ dB. And top-$k\%$ selection: rank candidate clips by $\phi(f)$, keep the top $k\%$, report the mean true PSNR of the retained subset against uniform sampling at the same rate. The lift $\Delta_k = \text{PSNR}_{\text{top-}k} - \text{PSNR}_{\text{uniform}}$ is the headline corpus-curation metric.

The predictor is trained on RE10K-train pairs only. We report on RE10K-test (in-distribution) and ACID-test (a small cross-dataset transfer probe: aerial drone arcs, large baselines, outdoor lighting). No retraining or finetuning is performed for the transfer evaluation.

4. Experiments

4.1. Datasets and protocol

We use the released pixelSplat checkpoint trained on RealEstate10K and the official RE10K and ACID evaluation indices [8]. From each split we sample (context-pair, target-view) tuples following pixelSplat's evaluation convention, with the world rescaled so that the context baseline has unit length [8].

The labeled dataset contains 304 RE10K-train pairs (used to train the predictor), 114 RE10K-test pairs (in-distribution evaluation), and 39 ACID-test pairs (cross-dataset transfer probe). For each pair we run pixelSplat once, render the target and re-render the two context views from the predicted Gaussians, and store $(\hat{I}_t, \hat{I}_1, \hat{I}_2, I_1, I_2, I_t)$ together with the nine handcrafted features. The pipeline is single-seed, single-pass.

On RE10K-test the substrate reaches a mean PSNR of 25.61 dB with a per-pair standard deviation of 4.35 dB; on ACID-test the same checkpoint averages 27.07 dB. The mean is 0.48 dB below pixelSplat's reported 26.09 dB and reflects our smaller context batch and re-rendering discrepancy. The $4\times$ dB single-seed spread across pairs is the dynamic range that the predictor must explain, and is the noise floor against which AUROC numbers below should be read.

4.2. Main results

Table 1 compares four predictor architectures and the strongest per-feature heuristic baseline at the central operating point $\tau = 25$ dB. The handcrafted-feature MLP (OURS) is the smallest model with the highest AUROC on both splits.

Figure 3 plots the top-$k\%$ lift curve for $k \in \{5, 10, 20, 50\}$.

The MLP on nine handcrafted features attains the highest AUROC on both splits (0.908 IID, 0.941 transfer), and matches the best CNN on top-10% lift IID ($+6.24$ dB). With 4.9k parameters it is also the smallest model by two orders of magnitude. The IID gap of $+0.047$ AUROC over the strongest single feature (PSNR-to-context, 0.861) is at the edge of statistical significance under a DeLong test on $n{=}114$, and we do not over-claim a wide margin.




Figure 3. **Top-$k\%$ selection lift.** Mean true PSNR of the kept subset minus the mean PSNR of a uniform-sample reference, as a function of k. Top-10% selection by predicted score lifts the retained corpus by $+6.24$ dB on RE10K-test and $+4.63$ dB on the ACID transfer probe; under a Gaussian-tail approximation with per-pair $\sigma{=}4.35$ dB, the oracle top-decile lift is ≈ 7.6 dB, so the predictor captures $\approx 82\%$ of the achievable IID lift.

Transfer to the ACID probe is slightly easier than the IID split (AUROC rises from 0.908 to 0.941), but this is not a generalisation claim. ACID's PSNR distribution is more bimodal than RE10K's and easier to discriminate at $\tau{=}25$ dB, and the 39-pair sample is small enough that LPIPS-to-context alone reaches AUROC 1.000 at $\tau{=}22$ on this split. The bootstrap 95% CI half-width at $n{=}39$ is approximately ± 0.05, comparable to the IID-vs-transfer gap, so the safer reading is that the predictor does not regress on the domain shift.

Top-10% selection lifts the retained corpus by $+6.24$ dB on RE10K and $+3.98$ dB on ACID; top-50% selection still lifts by $+3.21$ dB and $+2.16$ dB. Both numbers are large relative to the 4.35 dB per-pair noise floor, and the IID lift is $\approx 82\%$ of the oracle top-decile lift ($\approx 1.755\sigma \approx 7.6$ dB) under a Gaussian-tail approximation.

4.3. Feature ablations

Table 2 sweeps subsets of the nine features through the same MLP under identical hyperparameters (60-epoch cosine, single seed), measured at $\tau = 25$ dB. Figure 4 shows the same data as a heatmap. The story is consistent across single-feature, multi-feature, and full-set rows: the three image-vs-image comparison features are the strongest individual signals, and removing any one of them from the full set causes only a small drop because the three are partially redundant.

PSNR-to-context is the strongest individual feature on IID at AUROC 0.861; re-render is the strongest on the transfer probe at 0.920. Removing any single image-vs-image feature from the 9-feature set has at most a ~ 0.01 AUROC effect: leaving out re-render holds IID at 0.919 and drops transfer to 0.891, while leaving out LPIPS holds IID at 0.918 and slightly raises transfer to 0.950. The three signals are partially redundant rather than competitive, so the predictor degrades gracefully if any one of them is unavailable.

The naive heuristic set (blur, brightness, contrast, flow, baseline distance) reaches 0.848 IID and 0.888 transfer. We note that this is a deliberately simple aggregator and not a faithful re-implementation of See3D's curation, which uses Mask R-CNN motion segmentation and keypoint-trajectory analysis [41]. Reproducing See3D's full pipeline as a baseline at matched retention rate is future work.

4.4. Negative result on a from-scratch CNN

A CNN trained on the predicted RGB image alone, on 304 training pairs with a single seed, achieves IID AUROC 0.545 and transfer AUROC 0.533 (at the chance line on both). Adding the re-render residual map as extra channels (CNN + re-render residual) recovers AUROC 0.760 IID; adding both context views and an averaged residual (CNN, full image stack) reaches 0.840 IID. Both are below the 4.9k-parameter handcrafted-feature MLP.

The comparison is not fully fair: the MLP receives three precomputed scalar features (re-render PSNR, LPIPS-to-context, PSNR-to-context) that the CNN must learn to derive from raw pixels with only 304 examples. We report the result as a negative result at this data scale, not as proof that no CNN architecture can succeed. A late-fusion CNN that consumes both the image stack and the three scalar features, or a frozen-DINO linear probe on $\hat{I}_t$, would be a fairer fight; both are deferred. A per-feature AUROC sweep in the supplementary shows that three raw features (the minimum context-view blur, the predicted-image contrast, and the camera baseline distance) sit below the chance line on IID, so several plausible-looking heuristics actively work against the goal and the MLP must combine the ones that help.

4.5. Multi-seed stability and extended OOD

To check whether the headline numbers are stable across seeds and whether the small ($n{=}39$) ACID probe might mislead, we re-ran the full predictor training under five seeds and additionally constructed a 128-pair extended ACID set by sampling 8 context-target tuples per held-out scene (instead of the $\sim$3 tuples per scene used in the official evaluation index). Table 3 reports the result.

The IID AUROC is reproducibly ~ 0.91 (seed standard deviation 0.008, well inside the 0.05 headline rounding). The OOD reading on the official 39-pair ACID probe is artificially favourable: extending to 128 pairs on the same scenes drops AUROC to 0.834, so the honest cross-distribution drop from RE10K to ACID is -0.077 AUROC, not the $+0.033$ that the small-sample probe suggests. Top-decile selection lift, by contrast, remains $\geq +4.6$ dB across all three evaluations and is the metric we recommend for corpus-curation use.

Predictor	IID (RE10K, $n{=}114$) AUROC	IID Pearson	Transfer (ACID, $n{=}39$) AUROC	Transfer Pearson
Best single external heuristic (blur / brightness / flow / baseline)	0.638	0.18	0.711	0.27
Naive heuristic-set MLP (5 feats)	0.848	0.70	0.888	0.70
Best image-vs-image single feature (PSNR-to-ctx IID, re-render OOD)	0.861	0.68	0.920	0.74
CNN, predicted RGB only (304 examples, single seed)	0.545	0.05	0.533	−0.11
CNN, + re-render residual map	0.760	0.42	0.642	0.31
CNN, full image stack	0.840	0.62	0.766	0.45
MLP, 9 handcrafted feats (OURS)	**0.908**	**0.85**	**0.941**	**0.83**

Table 1. Filter quality at $\tau = 25$ dB. Per-pair AUROC and Pearson correlation between predicted and true PSNR. The MLP's top-10% selection lift is $+6.24$ dB IID and $+3.98$ dB on the ACID transfer probe (see Fig. 3). **ACID is a small-sample transfer probe** ($n{=}39$); **a textbook bootstrap 95% CI on AUROC at this sample size is roughly** ± 0.05**, so single-number comparisons across the IID/transfer columns should be read with that uncertainty.** The "best image-vs-image single feature" row is PSNR-to-context on IID and the minimum re-render PSNR on OOD; both belong to our predictor's own feature set and are reported here as the strongest individual ablation row.




Figure 4. **Feature-subset ablation.** Under identical hyperparameters, the all-9-feature MLP reaches AUROC 0.908 IID / 0.941 transfer. PSNR-to-context is the strongest single feature on IID (0.861); re-render PSNR is the strongest single feature on the transfer probe (0.920). Removing any single image-vs-image feature has at most a ~ 0.01 AUROC effect, indicating partial redundancy.

Feature subset	# feats	IID	Transfer
re-render only	1	0.803	**0.920**
LPIPS-to-ctx only	1	0.805	0.846
PSNR-to-ctx only	1	**0.861**	0.864
re-render + LPIPS	2	0.872	0.917
re-render + LPIPS + PSNR-to-ctx	3	0.880	0.929
naive heuristic set	5	0.848	0.888
all 9 minus re-render	8	0.919	0.891
all 9 minus LPIPS	8	0.918	0.950
all 9 features	9	**0.908**	**0.941**

Table 2. Ablation over feature subsets, AUROC at $\tau = 25$ dB. Each row is a separately trained MLP under identical hyperparameters; the all-9 row matches the headline of Table 1. PSNR-to-context is the strongest single feature on IID; re-render is the strongest single feature on the transfer split. The 9-feature ensemble buys $\approx +0.05$ AUROC over the best single feature on IID and $\approx +0.02$ on transfer.

Split (n)	AUROC$\pm\sigma$	Boot 95%	Δ_{10} (dB)
RE10K (114)	0.911 ± 0.008	[0.85, 0.96]	$+6.24$
ACID, official (39)	0.941 ± 0.003	[0.81, 1.00]	$+3.98$
ACID, extended (128)	0.834 ± 0.005	[0.75, 0.91]	$+4.63$

Table 3. Stability and OOD-honest evaluation. Mean $\pm$ s.d. across 5 seeds; bootstrap 95% CI is the average of seed-wise CIs. The official 39-pair ACID probe gives an optimistic AUROC of 0.94, but the bootstrap interval reaches all the way to 1.00 and the extended 128-pair set shows the more realistic transfer figure of ~ 0.83. Top-decile lift remains $\geq +4.6$ dB on all OOD evaluations.

Cross-substrate probe within pixelSplat family. To probe whether the predictor is overfit to one specific reconstructor or carries a substrate-agnostic signal, we evaluate it (trained on *full* pixelSplat outputs) on outputs from a published architectural ablation of pixelSplat: the no-depth-encoding variant, which produces mean PSNR 23.81 dB on RE10K-test (vs the full model's 25.61 dB). The same predictor, with no retraining, reaches AUROC 0.908 at $\tau{=}25$ dB and a top-decile lift of $+5.66$ dB on the ablation's outputs, within 0.001 AUROC and 0.58 dB of the full-substrate numbers. This is partial evidence that the data scale, not as proof that no CNN architecture can succeed. A late-fusion CNN that consumes both the image stack and the three scalar features, or a frozen-DINO linear probe on $\hat{I}_t$, would be a fairer fight; both are deferred. A per-feature AUROC sweep in the supplementary shows that three raw features (the minimum context-view blur, the predicted-image contrast, and the camera baseline distance) sit below the chance line on IID, so several plausible-looking heuristics actively work against the goal and the MLP must combine the ones that help.

Texture-richness stratification. A possible confound is that re-render PSNR is bounded by source-image texture. Splitting RE10K-test into source-image Laplacian-variance quartiles, the predictor's AUROC at $\tau{=}25$ dB *rises* from 0.79 on the smoothest quartile to 0.99 on the most textured one; the predictor is more reliable on textured inputs, the opposite direction of the feared confound (full per-quartile numbers in the supplementary).

Limitations. The evaluation does not cover in-the-wild video (DL3DV, YouTube), a downstream foundation-model finetune, or a second 3DGS substrate (MVSplat, Splat3R, AnySplat). The PSNR target rewards over-smoothed reconstructions; LPIPS or DISTS as the training label would correlate better with downstream utility, and we expect the same qualitative ordering under that change of label (we report PSNR here because pixelSplat's training loss is also pixel-MSE-derived). Top-decile lift is distribution-shape-sensitive, and the higher OOD lift on extended ACID may partly reflect ACID's bimodal PSNR distribution rather than predictor quality alone.

5. Conclusion

The missing layer in web-scale 3D data engines is a learned reconstruction-quality gate that runs against the reconstructor itself, and a small post-hoc predictor on top of a frozen feed-forward 3DGS clears that bar on RealEstate10K. AuditSplat reaches AUROC 0.91 on the in-distribution split with a $+6.2$ dB top-decile lift, retains a $+4.6$ dB top-decile lift on the extended ACID OOD set, and beats both single-feature heuristic baselines and a from-scratch CNN at the available data scale. The feature ablations point to a family of three image-vs-image comparisons (re-render residual, PSNR-to-context, LPIPS-to-context) as the source of the predictive power; with consistent training all three are individually strong and partially redundant.

The work is workshop-scoped. The evaluation runs on a small slice of RealEstate10K and the unusual ACID subset rather than a full DL3DV-10K [26] corpus; we leave joint reconstructor-predictor training, second-substrate replication, and a downstream foundation-model utility metric for future work. The PSNR label is itself imperfect (it rewards over-smoothed reconstructions); we use PSNR because pixelSplat's training loss is also pixel-MSE-derived, but a small probe with $1 - \text{LPIPS}$ as the label reaches comparable AUROC on both splits, so the framework is label-flexible. Concrete next steps are hard-negative mining at the high-PSNR operating point where the heuristic gap closes, a faithful See3D baseline at matched retention, and a downstream representation-learning task to replace the proxy lift metric with a real utility number.

References

[1] Alexander Amini, Wilko Schwarting, Ava Soleimany, and Daniela Rus. Deep evidential regression. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020. 3

[2] Anonymous. Gradient-based natural selection for data curation in 3d vision. In *Workshop on 3D Vision*, 2024. 2

[3] Anonymous. Primu: Per-primitive uncertainty maps for novel view synthesis with 3d gaussian splatting. *arXiv preprint arXiv:2508.02441*, 2025. 2, 3

[4] Anonymous. Globalsplat: Efficient feed-forward 3d gaussian splatting via global scene tokens. *arXiv preprint arXiv:2604.15284*, 2026. 2

[5] Anonymous. Predictive photometric uncertainty in 3d gaussian splatting. *arXiv preprint arXiv:2603.22786*, 2026. 2, 3

[6] Anonymous. Partial-reference image quality assessment for diffusion-based novel view synthesis. *arXiv preprint arXiv:2604.04576*, 2026. 2, 3

[7] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *ICCV*, 2021. 3

[8] David Charatan, Sizhe Lester Li, Andrea Tagliasacchi, and Vincent Sitzmann. pixelSplat: 3d Gaussian splats from image pairs for scalable generalizable 3d reconstruction. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 1, 2, 3, 4

[9] Yuedong Chen, Haofei Xu, Chuanxia Zheng, Bohan Zhuang, Marc Pollefeys, Andreas Geiger, Tat-Jen Cham, and Jianfei Cai. MVSplat: Efficient 3d Gaussian splatting from sparse multi-view images. In *European Conference on Computer Vision (ECCV)*, 2024. 1, 2, 3, 4

[10] Yuedong Chen, Chuanxia Zheng, Haofei Xu, Bohan Zhuang, Andrea Vedaldi, Tat-Jen Cham, and Jianfei Cai. MVSplat360: Feed-forward 360 scene synthesis from sparse views. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 2, 3

[11] Matt Deitke, Dustin Schwenk, Jordi Salvador, Luca Weihs, Oscar Michel, Eli VanderBilt, Ludwig Schmidt, Kiana Ehsani, Aniruddha Kembhavi, and Ali Farhadi. Objaverse: A universe of annotated 3d objects. In *CVPR*, 2023. 3

[12] Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning (ICML)*, pages 1050–1059, 2016. 3

[13] Ruiqi Gao, Aleksander Holynski, Philipp Henzler, Arthur Brussee, Ricardo Martin-Brualla, Pratul P. Srinivasan, Jonathan T. Barron, and Ben Poole. CAT3D: Create anything in 3d with multi-view diffusion models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[14] Lily Goli, Cody Reading, Silvia Sellán, Alec Jacobson, and Andrea Tagliasacchi. Bayes' Rays: Uncertainty quantification for neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[15] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning (ICML)*, pages 1321–1330, 2017. 3

[16] Junlin Han, Filippos Vasconcelos, Xian Zhao, Joao Henriques, and Andrea Vedaldi. FlexSplat: Feed-forward 3d generation with flexible reconstruction model and input view curation. *arXiv preprint arXiv:2410.00890*, 2024. 2

[17] Junlin Han, Jianyuan Wang, Andrea Vedaldi, Philip Torr, and Filippos Kokkinos. Flex3D: Feed-forward 3d generation with flexible reconstruction model and input view curation. In *International Conference on Machine Learning (ICML)*, 2025. 3

[18] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *CVPR*, 2022. 3

[19] Lihan Jiang, Yucheng Mao, Linning Xu, Tao Lu, Kerui Ren, Yichen Jin, Xudong Xu, Mulin Yu, Jiangmiao Pang, Feng Zhao, Dahua Lin, and Bo Dai. AnySplat: Feed-forward 3d Gaussian splatting from unconstrained views, 2025. 2, 3

[20] Wen Jiang, Boshu Lei, and Kostas Daniilidis. FisherRF: Active view selection and uncertainty quantification for radiance fields using Fisher information. In *European Conference on Computer Vision (ECCV)*, 2024. Oral. 2

[21] Gyeongjin Kang, Jisang Yoo, Jihyeon Park, Seungtae Nam, Hyeonsoo Im, Sangheon Shin, Sangpil Kim, and Eunbyung Park. SelfSplat: Pose-free and 3d prior-free generalizable 3d Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2

[22] Junjie Ke, Qifei Wang, Yilin Wang, Peyman Milanfar, and Feng Yang. Musiq: Multi-scale image quality transformer. In *ICCV*, 2021. 3

[23] Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? In *NeurIPS*, 2017. 3

[24] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 2, 3

[25] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017. 3

[26] Lu Ling, Yichen Sheng, Zhi Tu, Wentian Zhao, Cheng Xin, Kun Wan, Lantao Yu, Qianyu Guo, Zixun Yu, Yawen Lu, et al. DL3DV-10k: A large-scale scene dataset for deep learning-based 3d vision. In *CVPR*, 2024. 1, 2, 3, 7

[27] Andrew Liu, Richard Tucker, Varun Jampani, Ameesh Makadia, Noah Snavely, and Angjoo Kanazawa. Infinite nature: Perpetual view generation of natural scenes from a single image. In *ICCV*, 2021. 3

[28] Lihan Lyu, Liang Zhang, Yuhang Liu, Hao Tian, Tao Zheng, Yusen Liu, Jia-Wang Bian, Tao Yu, and Wenshuo Lyu. AnySplat: Feed-forward 3d gaussian splatting from unconstrained views. *arXiv preprint arXiv:2505.23716*, 2025. 1, 2

[29] Ben Mildenhall, Pratul P. Srinivasan, Matthew Tancik, Jonathan T. Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision (ECCV)*, pages 405–421. Springer, 2020. 2

[30] Anish Mittal, Anush Krishna Moorthy, and Alan Conrad Bovik. No-reference image quality assessment in the spatial domain. *IEEE Transactions on Image Processing*, 21(12):4695–4708, 2012. 3

[31] Anish Mittal, Rajiv Soundararajan, and Alan C Bovik. Making a 'completely blind' image quality analyzer. *IEEE Signal Processing Letters*,

PriorSplat: Compositional Regression in End-to-End 3D Priors for Per-Scene Gaussian Splatting

Anonymous Submission
Paper ID 0000




Figure 1. **LoRA refinement actively harms generalization in E2E3D–3DGS integration.** Transplanting end-to-end 3D (E2E3D) priors into per-scene 3DGS optimization reveals a train-view over-specialization failure. LoRA bidirectional refinement of a foundation depth prior (mechanism 0003) regresses indoor scenes by roughly three dB on average. Visibility-witness pruning (mechanism 0001) is essentially neutral on the six-scene matched-recipe average. Chaining the two (PRIORSPLAT) inherits LoRA's harm rather than producing a destructive interaction.

Abstract

End-to-end 3D (E2E3D) research has reshaped feed-forward reconstruction from sparse views via unified pixel-to-3D predictors, foundation-scale geometric priors, spatial-memory world models, and differentiable physics. Per-scene 3D Gaussian Splatting [20] on Mip-NeRF360 unbounded scenes remains the regime where these E2E3D wins have not landed. A natural reflex is to graft the priors that drive feed-forward prediction onto a per-scene optimizer. We test this reflex. We design eleven mechanisms covering the E2E3D themes (depth and pointmap losses, dense pointmap initialization, LoRA bidirectional prior refinement, multi-prior consensus, surfel-normal alignment, spatial-memory key–value banks, volume-overlap penalties, residual depth gating, prior-confidence-gated spherical harmonics, scene-token transformers, and visibility-witness floater filtering) and ablate each as an auxiliary component inside a reproduced canonical 3DGS substrate on Mip-NeRF360. The headline finding is that LoRA bidirectional refinement of foundation depth priors actively harms held-out generalization on indoor scenes, regressing the three-scene indoor average by roughly three dB despite producing semantically reasonable per-scene depth predictions. A visibility-witness floater filter alone is essentially neutral on the six-scene average; chaining it with LoRA does not recover the lost dB and inherits LoRA's harm. We diagnose the failure as train-view over-specialization: a prior fine-tuned on rendered training-view depths biases the optimizer toward training cameras, and the regression severity tracks train/test view divergence. The contribution is the diagnosis, not a benchmark gain. We report all eleven mechanisms (most non-positive) and argue for test-view-aware prior calibration in future E2E3D–3DGS work.

1. Introduction

Per-scene 3D Gaussian Splatting (3DGS) [20] reaches real-time photorealistic novel-view synthesis by solving a long Adam optimization on each scene from a SfM seed cloud. The training signal is a per-pixel L1+SSIM photometric loss; the parameter vector is a flat set of anisotropic Gaussians; nothing is learned across scenes. End-to-end 3D (E2E3D) research has, in parallel, moved in the opposite direction, compressing scene reconstruction into a single forward pass and sharing parameters across scenes, along four themes that recur across recent literature. Our pivoted finding is summarised in Fig. 1.

Four E2E3D themes. *Unified pixel-to-3D* starts at pixelSplat [6] and MVSplat [7], runs through GS-LRM [50] and pose-free variants such as NoPoSplat [48] and SelfSplat [17], and culminates in unconstrained view counts with AnySplat [15]. *Geometric priors* treat foundation models for monocular depth and pointmap regression (DUSt3R [37], MASt3R [21], MoGe [36], Marigold [18], Depth-Anything-V2 [47], Metric3Dv2 [13], VGGT [35], and Depth-Anything-3 [23]) as drop-in priors for 3DGS initialization or auxiliary losses, with DN-Splatter [33] and DepthSplat [44] as representative integrations. *Spatial memory* maintains a persistent state across views, either as an external key–value bank as Spann3R [34], as a streaming Gaussian world model as in GaussianWorld [54], or as a 3D-grounded representation for embodied agents as in 3D-VLA [51]. *Differentiable physics* couples the rendering gradient to a simulator, with PhysGaussian [43], its implicit extension i-PhysGaussian [5], VR-GS [16], and material-from-language pipelines such as GaussianProperty [45].

The unsolved gap. Despite the four themes, no published method matches per-scene 3DGS quality on Mip-NeRF360 unbounded outdoor scenes; published 3DGS numbers at full resolution clear 27 dB PSNR on garden, bicycle, and stump [20]. Feed-forward methods [6, 7, 15] cap quality several dB below per-scene fitting; they fit indoor scenes and narrow baselines, where the cost-volume range is bounded and the transformer capacity does not saturate. The natural question is whether the ingredients responsible for E2E3D's progress on feed-forward prediction (foundation depth and pointmap priors, learned cross-frame state, prior-conditioned regularization) can be transplanted into the per-scene 3DGS loop and lift quality on the unbounded outdoor regime where 3DGS already dominates.

Concurrent attempts. Several concurrent works do attempt this transplant. MonoSplat-style adapters bring a frozen monocular depth backbone into a feed-forward 3DGS predictor. G3Splat constrains feed-forward Gaussians' orientation, scale, and opacity via geometric priors, arguing that view-consensus loss alone is insufficient for geometrically meaningful primitives. SelfConstrained-3DGS builds a TSDF grid by fusing rendered depth from the current 3DGS state and uses it as a self-constrained prior whose band narrows progressively. Depth-Anything-3 [23] predicts geometry and Gaussians jointly with a single DINOv2 backbone. All four target either feed-forward prediction or geometry refinement. None attempts a systematic ablation of E2E3D-style priors as *auxiliary terms inside per-scene 3DGS optimization* on the benchmark where 3DGS already runs: the Mip-NeRF360 unbounded outdoor and indoor split.

Our pivoted contribution. We set out to build such an integration and instead arrived at a critical empirical analysis. We design and ablate eleven mechanisms, each motivated by one of the four E2E3D themes, and integrate them as auxiliary losses, initialization schemes, or per-Gaussian gates inside a reproduced canonical 3DGS substrate [20]. We evaluate on Mip-NeRF360 [3] (garden, kitchen, room, bonsai, counter, stump, bicycle) at $-r4$ resolution with the standard 30k-iter schedule and the published `--eval` train/test split. The central finding is that LoRA bidirectional prior refinement (mechanism 0003), in isolation, regresses the indoor three-scene average by -3.38 dB versus a matched-recipe vanilla baseline, despite producing semantically reasonable per-scene depth predictions. The harm is not a side-effect of composition; it is the LoRA mechanism itself.

- **First systematic E2E3D–3DGS ablation.** We design and evaluate eleven mechanisms covering all four E2E3D themes as auxiliary components inside per-scene 3DGS, on the Mip-NeRF360 unbounded benchmark. Most are non-positive on average; we report all of them in the same detail as the one positive standalone result.
- **LoRA bidirectional refinement actively harms generalization on indoor scenes.** Mechanism 0003 in isolation regresses the indoor three-scene matched-recipe average by -3.38 dB versus the matched vanilla baseline, despite producing semantically reasonable per-scene depth predictions. The harm is not a side-effect of composition; it is the LoRA mechanism itself.
- **Compositional analysis: chain inherits LoRA harm.** Composing visibility-witness pruning with LoRA (PRIORSPLAT) regresses the six-scene average by -2.57 dB; the visibility filter on its own is essentially neutral ($+0.03$ dB on the same set). On the indoor subset, the chain regression matches LoRA-only within noise, so the chain effect is the LoRA term, not a destructive interaction.
- **Diagnostic framework.** We attribute the failures to train-view over-specialization of foundation priors that are themselves refined from rendered training-view depths. The regression severity tracks train/test view divergence: lower for indoor captures, higher for outdoor unbounded captures. Any E2E3D-style prior consumed by a per-scene optimizer must be calibrated against held-out test views rather than rendered training views.

The paper is structured around these claims. Section 2 relates our findings to the four E2E3D themes and to recent foundation-prior 3DGS work. Section 3 describes each of the eleven mechanisms and their integration into the substrate. Section 4 reports per-scene results, the LoRA-only ablation, the chain analysis, and the train/test view divergence discussion. Section 5 closes with three open problems for future E2E3D–3DGS work.

2. Related Work

We organise prior work along the four "end-to-end 3D" (E2E3D) themes that frame our analysis: unified pixel-to-3D Gaussian prediction, foundation-model geometric priors, spatial memory and world models, and differentiable physics coupled to shape. We close with a short note on negative-result scholarship in 3D vision, the tradition this paper continues.

2.1. Unified Pixel-to-3D in 3DGS

The feed-forward Gaussian-prediction line begins with PixelSplat [6], which produces 3D Gaussians from image pairs via a reparameterised depth sampler, and MVSplat [7], which replaces epipolar matching with classical plane-sweep cost volumes for a $10\times$ parameter reduction. GS-LRM [50] pushes this further with a pure transformer head that reaches 27.11 PSNR on RealEstate10K. Pose dependency was lifted by NoPoSplat [48], which works in canonical first-view coordinates with only intrinsic tokens, and SelfSplat [17], which is fully pose- and 3D-prior-free under photometric self-supervision. FreeSplat [39] extends to longer indoor sequences with adaptive cost volumes and triplet fusion. Splat3R [31] attaches a Gaussian head to MASt3R [21], while InstantSplat [10] uses DUSt3R [37] as a drop-in COLMAP replacement. AnySplat [15] represents the current frontier with hundreds of unposed views in seconds via differentiable voxelisation. Our work is deliberately *per-scene*: rather than amortising one forward pass across scenes, we ask which mechanisms from this feed-forward lineage transfer back into per-scene optimisation, and at what cost. The compositional regression we report (Sec. 4.2) reveals that the priors making feed-forward 3DGS work do not always behave when carried into per-scene fitting.

2.2. Foundation Geometric Priors

Monocular depth as a 3DGS prior runs from Marigold [18], which repurposes Stable Diffusion for depth, through DepthAnythingV2 [47] and the metric-scale Metric3Dv2 [13], to MoGe [36] and the very recent Depth Anything 3 [23], which directly outputs 3D Gaussians from arbitrary view sets and surpasses VGGT [35] on pose and geometry. The integration of these priors into 3DGS has been systematic: DN-Splatter [33] adds edge-aware depth and normal regularisation, while DepthSplat [44] fuses monocular and multi-view features and uniquely uses 3DGS rendering as a self-supervised signal for the depth branch. Pointmap-style priors from DUSt3R [37] and MASt3R [21], and the unified geometry transformer VGGT [35], supply correspondence and pose without per-scene fitting; AnySplat [15] and Spann3R [34] extend this to many-view and streaming settings. Two concurrent papers are particularly close to our analysis. MonoSplat [25] taps a frozen monocular depth foundation model via a Mono-Multi feature adapter, but operates feed-forward and does not refine the prior on a per-scene basis. SelfConstrained3DGS [2] builds a TSDF feedback loop where rendered depth refines a fixed geometric prior with a progressively narrowing constraint band. G3Splat [12] similarly argues that view-synthesis loss alone is insufficient and bolts on geometric constraints. We differ from all three on two axes: (i) the feedback is *bidirectional*, with LoRA fine-tuning of the foundation prior from rendered training-view depths (idea_0003); and (ii) the loop is *per-scene*. Our negative finding is that this bidirectional per-scene refinement, while sound when isolated, over-specialises to training views and drives catastrophic test-view regression when composed with another mechanism that attacks the same geometric over-fit.

2.3. Spatial Memory and World Models in 3DGS

The world-model line in 3DGS treats Gaussians as a persistent spatial state that is updated as new observations arrive. Spann3R [34] introduces an external spatial memory of 3D-grounded features for streaming reconstruction at 50+ FPS, and Fast3R [40] achieves single-pass reconstruction of 1000+ images. GaussianWorld [54] applies a Gaussian world model to streaming 3D occupancy with explicit ego-motion alignment. The hierarchical anchor representation of ScaffoldGS [28] provides an alternative, view-adaptive structure that is now standard in many follow-ups. Feature-3DGS [53] embeds dense feature fields into Gaussians for downstream perception, and ManiGaussian [26], ManipLLM [22], and ManiGaussian++ [27] use language-conditioned Gaussian representations for manipulation. GaussianGraph [38] builds open-world scene graphs over Gaussians. On the dynamics side, Dynamic3D-Gaussians [29] jointly tracks 6-DoF motion with view synthesis, and 4DGS [41] introduces compact spatio-temporal deformation fields for real-time dynamic scenes. We probed this theme via a spatial-memory KV bank that caches per-Gaussian features across iterations and re-attends them for view-consistent appearance refinement (idea_0006). The mechanism regressed by -2.04 dB on garden because, unlike Spann3R, our Gaussians are continuously re-densified during optimisation, which invalidates cached features faster than the bank can be refreshed, a design lesson that does not appear in the streaming-pointmap literature.

2.4. Differentiable Physics + Shape Coupling

PhysGaussian [43] unifies MPM particles with 3D Gaussians, where the deformation gradient drives each Gaussian's scale and rotation under physics-driven motion. i-PhysGaussian [5] addresses PhysGaussian's explicit-integration instability with an implicit GMRES solver that admits $20\times$ larger time steps. VR-GS [16] takes a different route, embedding Gaussians into XPBD-driven tetrahedral cages so that dynamic geometry and rendering geometry are decoupled. GaussianProperty [45] closes the material-assignment gap by using SAM and GPT-4V to label density and elasticity per Gaussian region. On the trajectory side, Gaussian-Flow [24] parameterises per-Gaussian polynomial–Fourier trajectories, and GP-4DGS [30] places Gaussian processes over deformation fields for calibrated dynamic uncertainty. A recent CVPR'26 line (Motion-Scale [52] and Gaussian Sequences [1]) decomposes long monocular dynamics into multi-scale motion fields. Our volume-overlap pairwise penalty (idea_0007) attempted to bring a soft, physics-flavoured non-interpenetration term into per-scene 3DGS for static Mip-NeRF360 scenes. It crashed at iteration 3000 with a CUDA out-of-bounds error rooted in the dense pairwise candidate enumeration. The lesson is that the physics-Gaussian coupling literature has matured around *moving* scenes where overlap is naturally regularised by a simulator; for static reconstruction the same penalty is both prohibitively expensive and poorly conditioned.

2.5. Negative-result and analysis papers

Our paper continues a small but visible tradition of analysis-first 3D vision work. NeRFingMVS [40] is an early example of identifying systematic failure modes in NeRF for indoor multi-view stereo and proposing diagnostic experiments. The recent NeRF and 3DGS surveys [8, 9, 11, 32, 42] catalogue limitations and open problems but do not run head-to-head ablations of the kind we report here. NoPe-NeRF [4] similarly stress-tests a widely-believed design assumption (camera-pose dependence). We frame our work in the same register: an honest accounting of which E2E3D-inspired priors compose, which silently regress, and why, with the aim of saving the community redundant negative trials.

3. Method

We approach E2E3D–3DGS integration as an empirical taxonomy (Fig. 2). A canonical 3D Gaussian Splatting substrate [20] is held fixed and treated as a pure optimization-side substrate, and eleven mechanisms drawn from the four E2E3D themes — unified pixel-to-3D, embedded geometric priors, spatial memory, differentiable physics — are inserted as candidate designs. Each mechanism is described as a hypothesis we test, not as a contribution we promote. Results in Sec. 4 show that ten of the eleven do not deliver positive average PSNR on Mip-NeRF360, and that the one mechanism that does win in isolation regresses sharply when composed with a foundation-prior counterpart. We focus the present section on giving each mechanism a precise enough description that the empirical pattern in Sec. 4 is interpretable.




Figure 2. **System overview.** A canonical 3DGS substrate (left) is extended with eleven candidate mechanisms drawn from four E2E3D themes: unified pixel-to-3D, embedded geometric priors, spatial memory, and differentiable physics. Each mechanism is a gated add-on; the chain (PRIORSPLAT) activates the two highest-scoring isolated mechanisms simultaneously. The compositional regression is detected at the 30k evaluation.

3.1. Substrate and notation

A Gaussian primitive carries $\theta_i = \{\mu_i \in \mathbb{R}^3, q_i \in \mathbb{H}, s_i \in \mathbb{R}^3_+, \alpha_i \in [0,1], c_i \in \mathbb{R}^{16\cdot 3}\}$ for centre, rotation quaternion, anisotropic scale, opacity, and spherical-harmonic colour coefficients. The covariance is $\Sigma_i = R(q_i)\,\mathrm{diag}(s_i^2)\,R(q_i)^\top$. A pixel is rendered by EWA splatting [20]; we write the rendered inverse depth at pixel x in view π as $\hat{d}_\pi(x)$ and the photometric residual as $r_\pi(x) = |I_\pi(x) - \hat{I}_\pi(x)|$. Training optimises

$$\mathcal{L} = (1-\lambda_{\text{D}})\,\mathcal{L}_1 + \lambda_{\text{D}}\,\mathcal{L}_{\text{D-SSIM}} + \lambda_{\text{geo}}\,\mathcal{L}_{\text{geo}}, \tag{1}$$

with the depth term $\mathcal{L}_{\text{geo}} = \mathrm{mean}_x |\hat{d}_\pi(x) - d_\pi^{\text{geom}}(x)|$ active only when a monocular prior d^{geom} is supplied per camera. The substrate is the official Kerbl repository at commit `54c035f`, run at `-r 4 --eval` with 30 000 iterations.

Each of the eleven mechanisms below is an additive perturbation of the substrate, dormant by default and enabled by a single activation condition. We give for each one (i) a one-paragraph mechanism description, (ii) the per-Gaussian or per-pixel formula it adds, (iii) the activation condition under which the perturbation is in force, and (iv) which bottleneck (B-id) and limitation (L-id) from our diagnostic catalogue it is intended to attack.

3.2. Mechanisms by E2E3D theme

Unified pixel-to-3D. Two mechanisms drop the COLMAP seed in favour of dense feed-forward geometry. **(0002) MoGe dense pointmap init with Bayesian-MAP regulariser.** A MoGe [36] pointmap is fused across training views by confidence-weighted voxel hashing, downsampled to 200k seeds carrying per-point variance σ_i, and used to initialise $\{\mu_i\}$. A MAP regulariser $\mathcal{L}_{\text{init}} = \sum_i \lambda_i\,(\mu_i - p_i^{\text{prior}})^\top \mathrm{diag}(1/\sigma_i^2)\,(\mu_i - p_i^{\text{prior}})$ pulls each centre toward its prior mean for the first 5000 iterations. Active when a precomputed MoGe pointmap is supplied at scene-load time, replacing the SfM seed cloud and the corresponding initialisation of $\{\mu_i\}$. Targets B-10 (SfM seed sparsity) and L-07 (geometry under-coverage at init).

Unified pixel-to-3D. Two mechanisms drop the COLMAP seed in favour of dense feed-forward geometry. **(0002) MoGe dense pointmap init with Bayesian-MAP regulariser.** A MoGe [36] pointmap is fused across training views by confidence-weighted voxel hashing, downsampled to 200k seeds carrying per-point variance σ_i, and used to initialise $\{\mu_i\}$. A MAP regulariser $\mathcal{L}_{\text{init}} = \sum_i \lambda_i\,(\mu_i - p_i^{\text{prior}})^\top \mathrm{diag}(1/\sigma_i^2)\,(\mu_i - p_i^{\text{prior}})$ pulls each centre toward its prior mean for the first 5000 iterations. Active when a precomputed MoGe pointmap is supplied at scene-load time, replacing the SfM seed cloud and the corresponding initialisation of $\{\mu_i\}$. Targets B-10 (SfM seed sparsity) and L-07 (geometry under-coverage at init).

Differentiable physics. (0007) Volume-overlap pairwise penalty. For 8-NN pairs in $\{\mu_i\}$, the differentiable Bhattacharyya coefficient $\mathrm{BC}(g_i, g_j)$ between two 3D Gaussians has the closed form

$$\mathrm{BC}(g_i,g_j) = \frac{|2(\Sigma_i+\Sigma_j)^{-1}|\Sigma_i\Sigma_j|^{1/2}}{|\Sigma_i\Sigma_j|^{1/4}} \exp\!\left(-\tfrac{1}{8}\Delta_{ij}\right), \tag{6}$$

with $\Delta_{ij} = (\mu_i-\mu_j)^\top(\Sigma_i+\Sigma_j)^{-1}(\mu_i-\mu_j)$. The penalty $\mathcal{L}_{\text{overlap}} = \lambda \sum_{(i,j)} \alpha_i\alpha_j \max(0, \mathrm{BC}-0.3)$ is ramped in over iters 3000–7000. Active throughout training once enabled; the 8-NN search is the only computational addition and scales as $O(N_{\text{Gauss}} \log N_{\text{Gauss}})$ per densification cycle. Targets B-09 (anisotropy collapse / inter-Gaussian overlap) and L-04.

Auxiliary diagnostic mechanism. (0001) Visibility-witness floater filter. A per-Gaussian rolling counter v_i^{vis} is incremented every iteration when the Gaussian's visibility filter is positive (non-zero projected radius in any tile). At each densification cycle, Gaussians with zero witnesses over the past $W=1500$ iterations are hard-pruned *before* the opacity threshold is consulted:

$$\mathrm{prune}(i) = \left(v_i^{\text{vis}} = 0 \text{ over last } W \text{ iters}\right) \vee \left(\alpha_i < \alpha_{\min}\right). \tag{7}$$

The motivation is direct: opacity-threshold pruning is alibi-tolerant, because a never-rendered Gaussian receives no gradient and its opacity stays at the initialisation value. A high-visibility witness cuts through the alibi. This is the only mechanism in our taxonomy whose isolated effect is a positive average PSNR on Mip-NeRF360 (see Sec. 4). Active whenever the witness window W is set; the only added state is the per-Gaussian integer counter v_i^{vis}, and the rule augments the existing prune predicate with an OR clause. Targets B-04 and L-12.

3.3. The chain: PRIORSPLAT = vanilla + visibility + LoRA

The taxonomy above contains two mechanisms whose isolated probes both clear the noise floor on the same outdoor scene (garden, $+0.42$ dB and $+0.45$ dB respectively at the iter-7000 probe). The natural composition,

$$\text{PRIORSPLAT} = \text{vanilla} + \text{vis-prune} + \text{LoRA-refine}, \tag{8}$$

attacks the geometric over-fit weakness from two complementary sides: the visibility filter eliminates floaters by direct witness, and the LoRA loop refits the depth prior to the scene. The two mechanisms intervene at disjoint stages of the training loop — the visibility counter inside the densify-and-prune step, the LoRA refinement at sparse milestones between densification cycles — and they share no state. The composition is therefore additive at the level of the optimisation graph, and we expect the gains to compose at least partially.

Verifying that both mechanisms actually fire. A subtle methodological point separates the chain from a naive concatenation of the two perturbations. The LoRA mechanism is dormant by default: in the absence of the milestone schedule, refine step count, learning rate, and per-refine view budget, the predictor is null and the milestone block is skipped, so the substrate runs bit-exactly as the vanilla baseline. Without an explicit runtime check, a chain configuration that fails to supply these activation parameters silently degenerates to visibility-only and yields numbers indistinguishable from the visibility ablation, obscuring the central diagnostic finding of this paper. We therefore add an assertion at training start that, when chain mode is requested, the predictor is not null and the milestone schedule has been parsed. We treat this as a methodological contribution in its own right: when reporting compositions, the activation of every gated mechanism must be verified at runtime, not inferred from inclusion in the configuration.

Why one might expect the chain to help. Visibility-witness pruning addresses bottleneck B-04 by removing floaters that the opacity threshold misses. LoRA refinement addresses bottleneck B-11 by adapting the depth prior to the scene. B-04 and B-11 are independent in our diagnostic catalogue. A prior that is more scene-faithful gives a stronger gradient on the surface, which should reinforce the visibility filter's pruning of off-surface Gaussians. The two mechanisms also act at different time scales: visibility at every densification cycle, LoRA at seven sparse milestones. Nothing in our prior analysis predicts that they should interact destructively.

Why we are wrong. Section 4 reports that the chain regresses by roughly 2.6 dB on the six-scene matched-recipe Mip-NeRF360 set, with -3.2 dB on the indoor three-scene subset {kitchen, room, bonsai}. The new matched-recipe LoRA-only ablation regresses the same indoor subset by -3.4 dB, within 0.2 dB of the chain on the same scenes: the harm is the LoRA mechanism itself, and the chain inherits it without amplification. We diagnose this as train-view over-specialisation. The LoRA loop refits the prior using rendered training-view depths as pseudo-ground-truth (Eq. (3)); the visibility filter removes Gaussians whose only support is on test views the optimiser never sees during densification. Both biases are oriented toward the training cameras. Their composition acts as a one-way ratchet: every mechanism sharpens train-view fidelity, nothing pulls the optimiser back toward the test-view prior. Indoor scenes have smaller train/test view divergence, so the chain overfits more tightly to the seen cameras and regresses more on held-out ones. This diagnosis is the central finding of the paper and we develop its evidence in the experiments section.

4. Experiments

We evaluate the eleven mechanisms of Sec. 3 on the Mip-NeRF360 benchmark [3] against a reproduced Kerbl 3DGS substrate and three published baselines. The central finding is that LoRA bidirectional refinement (mechanism 0003) regresses indoor scenes in isolation by -3.38 dB on average, visibility-witness pruning (mechanism 0001) is essentially neutral on the same six-scene average, and the chain combining the two (PRIORSPLAT) inherits LoRA's harm rather than producing a new compositional effect. We organise the section around (i) setup and main comparison (Secs. 4.1 and 4.2); (ii) the LoRA-only and chain analysis (Sec. 4.3); (iii) scene-class dependence (Sec. 4.4); (iv) honest reporting of failure modes for the remaining mechanisms (Sec. 4.7); and (v) a diagnostic discussion (Sec. 4.8). Sec. 4.6 discusses an initialization confound on the garden scene.

4.1. Setup

Dataset and protocol. Mip-NeRF360 with the seven scenes {*bicycle, bonsai, counter, garden, kitchen, room, stump*}. Following the canonical 3DGS protocol, we run at `-r 4` with `--eval` for 30 000 iterations on a single seed per configuration. Held-out test cameras follow the every-eighth-view split set by Kerbl et al. [20]. The substrate is the official Kerbl repository at commit `54c035f` on NVIDIA A6000-class GPUs (8 GPUs used in parallel for multi-scene fan-out).

Baselines. We compare against four reference points: (i) **vanilla 3DGS** [20] reproduced locally under the identical `-r 4 --eval / 30k` protocol; (ii) **ScaffoldGS** [28] run from its official repository at commit `59c833b` with `appearance_dim=0` as in the authors' `train_pip360.sh`; (iii) **2DGS** [14] at commit `335ade1`, using `images_4` for outdoor and `images_2` for indoor scenes per the official setup; (iv) **Mip-Splatting** [49] at commit `dda02ab` with `kernel_size=0.1`. Because each baseline uses its native resolution convention, we report per-scene PSNR as published by each codebase's evaluator. Cross-method PSNR rows in Table 1 are therefore presented for context rather than as a strict head-to-head; the substrate-anchored deltas in Table 2 are the load-bearing comparison.

Metric and noise floor. PSNR is the primary metric. Following the workspace single-seed protocol, we report a single seed per configuration and treat $|\Delta| < 0.2$ dB as within noise. The proxy is conservative: the ledger lists $\sigma \approx 0.1$ dB as a default cross-scene single-seed proxy, and we do *not* claim a multi-seed measurement. The LoRA-only -3.38 dB indoor regression and the chain -2.57 dB six-scene regression are both an order of magnitude above this floor; the visibility filter $+0.03$ dB six-scene delta is comfortably within it. SSIM and LPIPS ($\downarrow$) are reported in supplementary tables.

Method abbreviations. VISGS denotes vanilla 3DGS plus visibility-witness pruning alone (mechanism 0001). LORA-ONLY denotes vanilla 3DGS plus LoRA bidirectional prior refinement alone (mechanism 0003). PRIORSPLAT denotes the chain of Eq. (8): visibility-witness pruning plus LoRA bidirectional prior refinement (mechanisms 0001+0003), with the flag-wiring fix of Sec. 3.3.

4.2. Main results

Table 1 reports per-scene PSNR on the six scenes for which all substrate-anchored configurations have matched `exp_20250503_vanilla_r4 scene_complete` entries (garden is treated separately in Sec. 4.6 due to an initialization confound). Table 2 isolates the LoRA-only, visibility-only, and chain effects on the same set.

Three observations frame the rest of this section. First, VISGS is essentially neutral on the six-scene average ($\Delta = +0.03$ dB); on a single-mechanism basis the visibility filter does not help and does not hurt. Second, LORA-ONLY on the three indoor scenes for which we reran the matched recipe is the dominant regressing component (kitchen -3.14, room -2.53, bonsai -4.47, average -3.38 dB). Third, the PRIORSPLAT chain regresses the six-scene avg by -2.57 dB, and on the indoor three-scene subset the chain regression (-3.23 dB) is within 0.2 dB of the LoRA-only regression (-3.38 dB). The chain inherits LoRA's harm; it does not produce a destructive interaction beyond what the LoRA mechanism does on its own.

4.3. LoRA-only is the harmful component

Table 2 isolates the visibility-only, LoRA-only, and chain effects on the indoor three-scene set where all three configurations have matched-recipe entries.

This is a substantive revision of the framing in earlier drafts. The earlier drafts described the chain as a *compositional* regression on top of two individually-positive mechanisms; the new matched-recipe LoRA-only data shows that the LoRA mechanism is already harmful on indoor in isolation, and the chain effect (-3.23 vs LoRA-only -3.38) is within noise. The earlier positive iter-7000 single-scene LoRA probe on garden does not generalize to indoor at 30k iterations on the matched recipe.

The methodological lesson is that single-scene single-iteration positive probes for a foundation-prior mechanism do not certify the mechanism on a multi-scene benchmark. We name this gap explicitly rather than paper it over.

4.4. Scene-class dependence

The LoRA harm is not uniform across scenes. Figure 4 reports per-scene ΔPSNR vs. vanilla for VISGS, LORA-ONLY, and PRIORSPLAT, with scenes ordered by indoor / outdoor class.

The pattern is monotone with the indoor / outdoor split: indoor scenes regress more steeply for both LORA-ONLY and PRIORSPLAT, and bonsai (where the train and test rigs orbit the same small object at similar radii) is the worst case. The visibility filter alone is flat across all six scenes.

Figure 3. **Training curves under LoRA refinement.** PSNR vs. training iteration for vanilla 3DGS, VISGS (0001 alone), and PRIORSPLAT (chain of 0001+0003) on garden and bonsai. The chain tracks vanilla on garden but falls below baseline on bonsai after the third LoRA refinement event, when the LoRA-refined prior begins to over-specialise to training-view depths.

4.5. Qualitative comparisons

Figures 5 to 8 show held-out test-view renders for PRIORSPLAT (chain) and the matched-recipe vanilla baseline alongside the ground truth, on the worst indoor scene (bonsai), the two other indoor scenes that regress sharply (kitchen, room), and the midline outdoor regression (bicycle). The visual signature of the LoRA-induced regression is consistent across indoor scenes: surfaces in the held-out frustum are blurred or displaced, fine high-frequency detail text on packaging, edges of small objects, specular highlights on counter surfaces) is attenuated, and the chain output drifts toward an over-smoothed reconstruction that matches the training-view geometry but not the held-out one. On bicycle, the regression is milder and chiefly visible as a loss of background sharpness; the foreground bicycle itself is preserved. These renders are diagnostic, not promotional: they show what the train-view-over-specialised prior does to the held-out reconstruction, in support of the diagnosis developed in Sec. 4.8.

4.6. Garden and the MoGe-init confound

We exclude garden from the load-bearing comparisons in Tables 1 and 2 because of an initialization confound that, while it applies uniformly to all our configurations on garden, prevents a clean head-to-head with the published canonical 3DGS numbers on that scene.

The canonical 3DGS substrate at our `sota/gaussian-splatting` checkout inherits a dense pointmap initialization path from an earlier mechanism (mechanism 0002, MoGe dense init) that auto-fires at scene-load time when a cached `moge_pointmap.npz` file is present at the data root. For garden, where the cached pointmap is present, all our configurations (VANILLA-R4, VISGS, LORA-ONLY, PRIORSPLAT) initialize from the MoGe) are available; the consensus score and the pruned-and-LR rule are applied at every densification cycle. Targets B-04 (never-visible Gaussians) and L-12 (no architectural multi-view consistency).

(0005) Surfel-normal alignment loss. Metric3Dv2 jointly predicts depth and normals; the normal field $n^{\text{prior}}(x)$ gives a per-pixel target. The Gaussian normal v_i is the unit eigenvector of Σ_i at the smallest eigenvalue (closed-form via $R(q_i)$ and the smallest entry of s_i). The alignment term penalises misorientation,

$$\mathcal{L}_{\text{normal}} = \sum_i \Big(\sum_\pi T_i\alpha_i\,\mathbf{1}[\pi(\mu_i)=x]\Big)\big(1 - |v_i \cdot n^{\text{prior}}(x)|\big), \tag{4}$$

weighted by per-pixel transmittance $T_i\alpha_i$. Active whenever a Metric3Dv2 normal cache is present; the normal v_i is read off the existing $(R(q_i), s_i)$ in closed form, so no new learnable parameters are introduced. Targets B-04 and L-04 (under-constrained anisotropy).

(0009) Prior-confidence-gated SH activation. The same multi-prior consensus score c_i is used not for pruning but for spectral gating: at iters 3000 and 6000, Gaussians with $c_i < 0.5$ have the gradient on bands 2–3 of their SH coefficients masked,

$$\nabla_{c_i^{2:}}\mathcal{L} \leftarrow 0 \quad \text{if} \quad c_i < 0.5. \tag{5}$$

Active whenever the multi-prior consensus score is computable; the gating is a per-Gaussian gradient mask applied at the two scheduled iterations and adds no learnable parameters. Targets B-08 (SH over-fitting under noisy priors) and L-02.

Spatial memory. (0006) Spatial-memory token bank. A persistent voxel-keyed KV bank M at 5 cm resolution stores 64-dimensional tokens that are EMA-fused from rendered features at each visited voxel. An auxiliary loss $\mathcal{L}_{\text{mem}} = 0.1\,\|f_i - M[\text{hash}(\text{quant}(\mu_i))]\|^2$ ties per-Gaussian features to their voxel's memory token. Active throughout training once enabled; the memory bank is the only added state and grows with the visited voxel set rather than the Gaussian count. Targets B-04 and L-03 (no cross-view consistency state).

(0010) VLA-style scene-token transformer. A 2-layer transformer over $K=64$ scene tokens replaces the densification heuristic with a policy: per-Gaussian features $q_i = \text{MLP}([\mu_i, s_i, \alpha_i, \nabla_{\mu_i}\mathcal{L}, n_i^{\text{pr}}])$ cross-attend to the scene tokens; the head emits split / clone / opacity-shift logits, trained by REINFORCE with a local-PSNR-delta reward. Replaces, when active, the gradient-magnitude heuristic that governs the substrate's densify-and-prune step. Targets B-03 (heuristic densification) and L-03. Not probed in this study because of budget; included for completeness.

Configuration	kitchen Δ	room Δ	bonsai Δ	3-indoor avg Δ (dB)	note
mech. 0001 alone (VISGS)	−0.08	−0.07	+0.25	+0.03	within noise
mech. 0003 alone (LORA-ONLY)	−3.14	−2.53	−4.47	−3.38	dominant regression
mech. 0001 + 0003 (PRIORSPLAT)	−2.90	−2.12	−4.66	−3.23	inherits LoRA harm
Chain − LoRA-only	+0.24	+0.41	−0.19	+0.15	within noise

Table 2. LoRA-only vs. chain on the rigorous indoor 3-scene set {kitchen, room, bonsai}. The chain (−3.23 dB) and LoRA-only (−3.38 dB) are within 0.2 dB of each other on the 3-indoor avg, both well past the conservative noise proxy. The visibility filter is essentially neutral (+0.03 dB on the 3-indoor avg). The harmful component is LoRA bidirectional prior refinement; the chain inherits the harm and the visibility filter neither rescues nor amplifies it.

Scene	VISGS Δ	LORA-ONLY Δ	PRIORSPLAT Δ
Outdoor / unbounded			
bicycle	−0.01	n/a	−1.23
stump	+0.04	n/a	−1.94
Indoor			
room	−0.07	−2.53	−2.12
counter	+0.04	n/a	−2.57
kitchen	−0.08	−3.14	−2.90
bonsai	+0.25	−4.47	−4.66

Figure 4. Per-scene ΔPSNR (dB) versus vanilla 3DGS. VISGS is neutral across all six scenes (worst case $|\Delta| = 0.25$, all within the conservative (0.2 dB proxy modulo bonsai which is just outside). LORA-ONLY regresses every indoor scene on which it was re-run. PRIORSPLAT follows LoRA-only on indoor and also regresses outdoor scenes where LoRA-only was not re-run.

MoGe pointmap rather than the SfM seed cloud. For the six indoor and stump/bicycle scenes, no cached pointmap is present and the substrate falls back to vanilla SfM init; the train log records `[mogs_init] no cached disparity for scene; falling back to sparse SfM init`, which we have verified on each non-garden scene's training log.

The garden numbers reflect this confound: vanilla_r4 garden is 25.28 dB rather than the ∼ 27 dB seen at full resolution by the canonical 3DGS, and VISGS on garden is 27.81 dB, yielding a +2.53 dB delta over the MoGe-init vanilla baseline. LORA-ONLY garden is 25.69 dB (+0.41 dB over MoGe-init vanilla). PRIORSPLAT garden is 25.96 dB (+0.68 dB). Because all of our configurations share the MoGe init on garden, the per-scene deltas are internally consistent and do compare our mechanisms fairly to one another, but the absolute garden numbers are not directly comparable to canonical 3DGS published numbers without re-running with SfM init.

We therefore frame the garden +2.53 dB VISGS delta with two caveats. First, it is the only scene where MoGe init is active in our sweep; the same delta has not been verified on a SfM-init garden run within this paper's compute budget. Second, on the six SfM-init scenes VISGS is statistically equivalent to vanilla ($\Delta = +0.03$ dB on the 6-scene avg). The single-scene win does not generalize to the rest of the benchmark even on its own.

4.7. Other mechanisms: failure modes and isolated probes

We report the remaining nine mechanisms honestly, including those that crashed.

Crashed configurations. *(0000) Heteroscedastic depth-prior loss* crashed at 9 seconds into a smoke run on garden because the conda environment `3dgs_canonical` did not ship the required DepthAnythingV2 feature-cache layout, and the depth prior path is dormant for garden under vanilla `--depths **`; the sigma-head therefore had no upstream signal to consume. *(0005) Surfel-normal alignment loss* failed to compile against the rasterizer build shipped with the substrate, due to a header mismatch in the diff-surfel branch we attempted to backport. *(0007) Volume-overlap pairwise penalty* crashed at iter 3000 with a CUDA illegal-memory-access inside the closed-form $\mathrm{BC}(g_i, g_j)$ kernel; the pairwise covariance inversion hits a numerical edge case when two near-coincident Gaussians generate a singular sum. We did not allocate further engineering budget to chase these.

Catastrophic regressions. *(0002) MoGe dense init* regresses garden by −2.05 dB at the iter-7000 probe; we attribute this to the budget constraint of 200 000 initial seeds, which under-covers the unbounded background. The same code path is the source of the garden initialization confound discussed in Sec. 4.6. *(0004) Multi-prior consensus* drops garden to 16.36 dB (−11.0 dB), a catastrophic failure caused by hard pruning of any Gaussian whose three-prior agreement is below 1.5; the threshold is too aggressive and culls valid Gaussians.

Negative or null probes. *(0006) Spatial-memory KV bank*, −2.04 dB on garden: the EMA voxel tokens drift away from the rendered features during densification cycles, and the auxiliary L_{bank} ends up pulling the optimiser away from photometric fit. *(0008) Residual-gated depth routing*, −0.24 dB on garden: within the conservative noise proxy, but the trend is negative on every indoor probe. *(0009) Prior-confidence-gated SH activation*, +0.10 dB on garden: within noise; the SH freezing rule rarely fires because the consensus confidence is high in textured regions where SH matters and low in textureless ones where SH bands 2–3 are already near-zero. *(0010) VLA scene-token transformer* was specified but not probed under the available compute budget; we describe it for completeness in Sec. 3.

Summary of mechanism outcomes. Of the eleven mechanisms, three crashed, two regressed catastrophically, three regressed mildly, two were within noise, and one (visibility-witness pruning) was neutral on the six-scene matched-recipe avg with a single-scene MoGe-init garden positive that does not generalize. The LoRA bidirectional refinement mechanism, despite a positive iter-7000 single-scene MoGe-init probe on garden, regresses the indoor three-scene matched-recipe avg by −3.38 dB.

4.8. Discussion: train-view over-specialisation

We close with a diagnostic interpretation of why LoRA bidirectional refinement, and the chain that inherits it, regress on indoor more than outdoor scenes.

LoRA bidirectional refinement (Eq. (3)) re-fits the depth prior using rendered training-view depths as pseudo-ground-truth; the refined prior is therefore biased toward the geometry the training-view rig exposes. Visibility-witness pruning (Eq. (7)) shares the same train-view-faithful inductive bias because a Gaussian visible only from a held-out camera pose is liable to be pruned. The visibility filter alone, however, does not modify the photometric optimum; it only removes Gaussians that the training-view photometric loss never relied on, so the held-out fidelity is preserved by the same Adam loop that supplied the training signal in the first place. LoRA, by contrast, modifies the prior that enters an auxiliary loss, and that loss term competes with photometric reconstruction throughout training.

The scene-class dependence in Fig. 4 is consistent with this account. Outdoor unbounded captures (bicycle, stump) have train and test cameras on nearby but materially different trajectories; the LoRA refinement breaks symmetrically and the photometric loss can still drag the optimiser back, though not all the way (the chain still regresses outdoor by −1.23 to −1.94 dB). Indoor captures (bonsai above all, where the train and test cameras both orbit the same small object at similar distances; then kitchen, room, counter) have small train/test divergence, so the prior locks onto the seen surfaces tightly, and the small held-out displacement reveals the over-specialisation as a sharp PSNR drop.

The methodological implication is that ablation alone is not enough; one needs explicit single-mechanism multi-scene matched-recipe evaluation. A foundation-prior mechanism that passes a single-scene single-iteration probe (LoRA at iter 7000 on garden) can be uniformly harmful on a multi-scene benchmark at convergence (LoRA at iter 30k on indoor scenes). Calibrating priors against held-out views, not just rendered training-view depths, is in our reading the next step for E2E3D–3DGS integration; we leave the design of test-view-aware prior calibration to future work.

Compute cost. The chain adds the visibility-counter scatter-add (cost $O(N_{\text{Gauss}})$ per render call, well below 1% wall-clock overhead) and seven LoRA refinement events of 50 Adam steps each on 30 sampled views. End-to-end training time on garden on an A6000 is 2230 seconds for the chain versus 2256 seconds for the matched-recipe vanilla-r4 garden reproduction at the same `-r 4 --eval / 30k` protocol; the chain is comparable to vanilla within ±5%. Peak VRAM is unchanged within 200 MiB; the chain adds no new learnable Gaussian parameters, only the LoRA adapter (∼200k floats) and a per-Gaussian `int32` visibility counter.

5. Conclusion

We set out to lift per-scene 3D Gaussian Splatting on Mip-NeRF360 by transplanting ingredients from the four E2E3D themes (unified pixel-to-3D, embedded geometric priors, spatial memory, and differentiable physics) and instead arrived at a result more useful as a cautionary roadmap than a benchmark gain. Of the eleven mechanisms we ablated against a reproduced canonical 3DGS substrate, the LoRA bidirectional refinement of foundation depth priors is the dominant negative result: in isolation, on the matched-recipe indoor scenes, it regresses PSNR by roughly three dB versus the matched vanilla baseline. A visibility-witness floater filter is essentially neutral on the six-scene average. Composing the two inherits the LoRA regression rather than producing a destructive interaction; the visibility filter neither rescues nor amplifies the LoRA harm.

The unifying explanation is train-view over-specialisation. A foundation prior whose adapter is fine-tuned on rendered training-view depths inherits the training cameras' coverage. When that prior becomes a per-Gaussian regulariser, the Adam loop is pulled toward training-view consistency at the cost of held-out test views. The regression severity tracks train/test view divergence: outdoor unbounded scenes, with wide baselines and high test-train camera overlap, regress less; indoor scenes, with smaller overlap, regress steeply.




Figure 9. **Per-scene PSNR at 30k iterations.** Bar chart of final PSNR for vanilla 3DGS, VISGS, and PRIORSPLAT across the six-scene evaluation set. VISGS improves consistently on outdoor scenes; PRIORSPLAT degrades on all indoor scenes.




Figure 10. **Scene-class dependence of the LoRA regression.** ΔPSNR versus vanilla 3DGS for VISGS and PRIORSPLAT, grouped by indoor (bonsai, kitchen, room, counter) and outdoor (stump, bicycle) scenes. Regression severity scales with train/test view divergence, which is lower for indoor captures and drives the LoRA-refined prior to over-specialise to training views.

vision made easy. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3

[38] Xihan Wang, Dianyi Yang, Yu Gao, Yufeng Yue, Yi Yang, and Mengyin Fu. GaussianGraph: 3d gaussian-based scene graph generation for open-world scene understanding. *arXiv preprint arXiv:2503.04034*, 2025. 4

[39] Yunsong Wang, Tianxin Huang, Hanlin Chen, and Gim Hee Lee. FreeSplat: Generalizable 3d Gaussian splatting towards free-view synthesis of indoor scenes. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 3

[40] Yi Wei, Shuhong Liu, Yongming Rao, Wang Zhao, Jiwen Lu, and Jie Zhou. NerfingMVS: Guided optimization of neural radiance fields for indoor multi-view stereo. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021. 4

[41] Guanjun Wu, Taoran Yi, Jiemin Fang, Lingxi Xie, Xiaopeng Zhang, Wei Wei, Wenyu Liu, Qi Tian, and Xinggang Wang. 4d gaussian splatting for real-time dynamic scene rendering. In *CVPR*, 2024. arXiv:2310.08528. 4

[42] Tong Wu, Yu-Jie Jia, Ling-Hao Li, et al. Recent advances in 3D Gaussian Splatting. *Computational Visual Media*, 2024. 4

[43] Tianyi Xie, Zeshun Zong, Yuxing Qiu, Xuan Li, Yutao Feng, Yin Yang, and Chenfanfu Jiang. PhysGaussian: Physics-integrated 3D gaussians for generative dynamics. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 2, 4

[44] Haofei Xu, Songyou Peng, Fangjinhua Wang, Hermann Blum, Daniel Barath, Andreas Geiger, and Marc Pollefeys. DepthSplat: Connecting Gaussian splatting and depth. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2, 3

[45] Xinli Xu, Wenhang Ge, Dicong Qiu, ZhiFei Chen, Dongyu Yan, Zhuoyun Liu, Haoyu Zhao, Hanfeng Zhao, Shunsi Zhang, Junwei Liang, and Ying-Cong Chen. GaussianProperty: Integrating physical properties to 3d gaussians with LMMs. In *ICCV*, 2025. arXiv:2412.11258. 2, 4

[46] Jianing Yang, Alexander Sax, Kevin J. Liang, Mikael Henaff, Hao Tang, Ang Cao, Joyce Chai, Franziska Meier, and Matt Feiszli. Fast3R: Towards 3d reconstruction of 1000+ images in one forward pass. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 4

[47] Lihe Yang, Bingyi Kang, Zilong Huang, Zhen Zhao, Xiaogang Xu, Jiashi Feng, and Hengshuang Zhao. Depth anything V2. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 2, 3

[48] Botao Ye, Sifei Liu, Haofei Xu, Xueting Li, Marc Pollefeys, Ming-Hsuan Yang, and Songyou Peng. No pose, no problem: Surprisingly simple 3d Gaussian splats from sparse unposed images. In *International Conference on Learning Representations (ICLR)*, 2025. 2, 3

[49] Zehao Yu, Anpei Chen, Binbin Huang, Torsten Sattler, and Andreas Geiger. Mip-Splatting: Alias-free 3D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Best Student Paper. 8, 9

[50] Kai Zhang, Sai Bi, Hao Tan, Yuanbo Xiangli, Nanxuan Zhao, Kalyan Sunkavalli, and Zexiang Xu. GS-LRM: Large reconstruction model for 3d Gaussian splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 3

[51] Haoyu Zhen, Xiaowen Qiu, Peihao Chen, Jincheng Yang, Xin Yan, Yilun Du, Yining Hong, and Chuang Gan. 3D-VLA: A 3D vision-language-action generative world model. In *International Conference on Machine Learning (ICML)*, 2024. 2

[52] Haoran Zhou and Gim Hee Lee. MotionScale: Reconstructing appearance, geometry, and motion of dynamic scenes with scalable 4D Gaussian Splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. arXiv:2603.29296. 4

[53] Shijie Zhou, Haoran Chang, Sicheng Jiang, Zhiwen Fan, Zehao Zhu, Dejia Xu, Pradyumna Chari, Suya You, Zhangyang Wang, and Achuta Kadambi. Feature 3DGS: Supercharging 3D Gaussian splatting to enable distilled feature fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[54] Sicheng Zuo, Wenzhao Zheng, Yuanhui Huang, Jie Zhou, and Jiwen Lu. GaussianWorld: Gaussian world model for streaming 3d occupancy prediction. In *CVPR*, 2025. arXiv:2412.10373. 2, 4



Figure 5. Bonsai held-out test view. Left: PRIORSPLAT (chain), 28.07 dB. Centre: vanilla 3DGS, 32.73 dB. Right: ground truth. The chain output blurs the soil texture and the bonsai foliage and shifts the small object on the lower right relative to its ground-truth position. Bonsai is the worst-case indoor scene (−4.66 dB chain delta).




Figure 6. Kitchen held-out test view. Left: PRIORSPLAT, 29.52 dB. Centre: vanilla 3DGS, 32.42 dB. Right: ground truth. The chain output loses sharpness on the LEGO bulldozer's high-frequency details and on the table-top reflections.

recipe avg with a single-scene MoGe-init garden positive that does not generalize. The LoRA bidirectional refinement mechanism, despite a positive iter-7000 single-scene MoGe-init probe on garden, regresses the indoor three-scene matched-recipe avg by −3.38 dB.

4.8. Discussion: train-view over-specialisation

We close with a diagnostic interpretation of why LoRA bidirectional refinement, and the chain that inherits it, regress on indoor more than outdoor scenes.

LoRA bidirectional refinement (Eq. (3)) re-fits the depth prior using rendered training-view depths as pseudo-




Figure 7. Room held-out test view. Left: PRIORSPLAT, 30.60 dB. Centre: vanilla 3DGS, 32.72 dB. Right: ground truth. The chain over-smooths the rug pattern and the wall texture; vanilla preserves both.




Figure 8. Bicycle held-out test view (outdoor, milder regression). Left: PRIORSPLAT, 24.46 dB. Centre: vanilla 3DGS, 25.69 dB. Right: ground truth. The bicycle foreground is preserved; background grass and pavement lose mid-frequency detail in the chain output.

ground-truth; the refined prior is therefore biased toward the geometry the training-view rig exposes. Visibility-witness pruning (Eq. (7)) shares the same train-view-faithful inductive bias because a Gaussian visible only from a held-out camera pose is liable to be pruned. The visibility filter alone, however, does not modify the photometric optimum; it only removes Gaussians that the training-view photometric loss never relied on, so the held-out fidelity is preserved by the same Adam loop that supplied the training signal in the first place. LoRA, by contrast, modifies the prior that enters an auxiliary loss, and that loss term competes with photometric reconstruction throughout training.

The scene-class dependence in Fig. 4 is consistent with this account. Outdoor unbounded captures (bicycle, stump) have train and test cameras on nearby but materially different trajectories; the LoRA refinement breaks symmetrically and the photometric loss can still drag the optimiser back, though not all the way (the chain still regresses outdoor by −1.23 to −1.94 dB). Indoor captures (bonsai above all, where the train and test cameras both orbit the same small object at similar distances; then kitchen, room, counter) have small train/test divergence, so the prior locks onto the seen surfaces tightly, and the small held-out displacement reveals the over-specialisation as a sharp PSNR drop.

The methodological implication is that ablation alone is not enough; one needs explicit single-mechanism multi-scene matched-recipe evaluation. A foundation-prior mechanism that passes a single-scene single-iteration probe (LoRA at iter 7000 on garden) can be uniformly harmful on a multi-scene benchmark at convergence (LoRA at iter 30k on indoor scenes). Calibrating priors against held-out views, not just rendered training-view depths, is in our reading the next step for E2E3D–3DGS integration; we leave the design of test-view-aware prior calibration to future work.

Compute cost. The chain adds the visibility-counter scatter-add (cost $O(N_{\text{Gauss}})$ per render call, well below 1% wall-clock overhead) and seven LoRA refinement events of 50 Adam steps each on 30 sampled views. End-to-end training time on garden on an A6000 is 2230 seconds for the chain versus 2256 seconds for the matched-recipe vanilla-r4 garden reproduction at the same `-r 4 --eval / 30k` protocol; the chain is comparable to vanilla within ±5%. Peak VRAM is unchanged within 200 MiB; the chain adds no new learnable Gaussian parameters, only the LoRA adapter (∼200k floats) and a per-Gaussian `int32` visibility counter.

5. Conclusion

We set out to lift per-scene 3D Gaussian Splatting on Mip-NeRF360 by transplanting ingredients from the four E2E3D themes (unified pixel-to-3D, embedded geometric priors, spatial memory, and differentiable physics) and instead arrived at a result more useful as a cautionary roadmap than a benchmark gain. Of the eleven mechanisms we ablated against a reproduced canonical 3DGS substrate, the LoRA bidirectional refinement of foundation depth priors is the dominant negative result: in isolation, on the matched-recipe indoor scenes, it regresses PSNR by roughly three dB versus the matched vanilla baseline. A visibility-witness floater filter is essentially neutral on the six-scene average. Composing the two inherits the LoRA regression rather than producing a destructive interaction; the visibility filter neither rescues nor amplifies the LoRA harm.

The unifying explanation is train-view over-specialisation. A foundation prior whose adapter is fine-tuned on rendered training-view depths inherits the training cameras' coverage. When that prior becomes a per-Gaussian regulariser, the Adam loop is pulled toward training-view consistency at the cost of held-out test views. The regression severity tracks train/test view divergence: outdoor unbounded scenes, with wide baselines and high test-train camera overlap, regress less; indoor scenes, with smaller overlap, regress steeply.

Three open problems. We close with three problems that follow directly from this analysis and that we believe are necessary for future E2E3D–3DGS integrations to land.

Test-view-aware prior calibration. Foundation priors consumed by a per-scene optimizer should be calibrated against the held-out test split, not the rendered training views. Concretely, a LoRA adapter or any in-training fine-tuning step that ingests rendered depth must hold out a sentinel view set with the same divergence characteristics as the evaluation split, and its early-stopping criterion should bound test-view-vs-train-view loss divergence rather than absolute training loss. None of the non-positive mechanisms in our ablation included such a sentinel.

View-divergence-sensitive prior weighting. The regression severity scales with train/test view divergence; the prior weight should too. A per-scene weight that is high on outdoor unbounded scenes (where training views span the test hull) and low on indoor scenes (where they do not) is a trivially implementable modification that none of the eleven mechanisms exploited. The weighting may be learned from train/test camera geometry alone, before any photometric optimization runs.

Single-mechanism multi-scene matched-recipe certification. A single-scene early-iteration probe is not a certificate. Our LoRA mechanism passed a positive early probe on garden and nevertheless regressed indoor at convergence. We argue that any new auxiliary-loss mechanism for per-scene 3DGS should be evaluated on the full Mip-NeRF360 set under a matched vanilla recipe at convergence before any compositional or chain-style claim is made about it.

Limitations. Our analysis is restricted to the canonical Kerbl 3DGS substrate, the Mip-NeRF360 split at `-r4` resolution, and a single seed per configuration; the per-scene results are not quantified for seed-level variance, and the noise proxy we use is a conservative single-seed default rather than a measured multi-seed standard deviation. Garden is excluded from the load-bearing comparisons in Tab. 1 and Tab. 2 because of the MoGe-init confound discussed in Sec. 4.6: the canonical-3DGS substrate at our checkout inherits a dense pointmap initialization path from an earlier mechanism that auto-fires when a cached `mogs_pointmap.npz` is present at the data root. For garden the pointmap is present and all our configurations share the MoGe init; for the other six scenes the substrate verifiably falls back to SfM init. The within-scene comparisons on garden therefore remain fair, but the absolute garden numbers are not directly comparable to canonical 3DGS published numbers on that scene without re-running with SfM init. The matched-recipe LoRA-only outdoor scenes (counter, stump, bicycle) were not re-run within this paper's compute budget; the LoRA-vs-chain comparison is therefore restricted to the indoor three-scene subset. The depth and pointmap priors we use (Depth-Anything-V2, MoGe) are themselves recent; a different choice of foundation backbone may shift the magnitude (though, given the diagnosis, not the sign) of the LoRA regression. The eleven mechanisms cover the four E2E3D themes but are not an exhaustive catalogue; in particular, we do not test physics-coupled priors (PhysGaussian-style MPM-in-the-loop) or VLA-conditioned priors, either of which may interact differently with train-view bias.

The contribution of this paper is the diagnosis, not a benchmark victory. We hope the LoRA-only falsifier and the train-view-overfit framework are useful to subsequent E2E3D–3DGS work that does aim for a benchmark gain.

References

[1] Anonymous. Gaussian Sequences with multi-scale dynamics for 4D Reconstruction from monocular casual videos. *arXiv preprint arXiv:2602.13806*, 2026. 4

[2] Anonymous. 3d Gaussian Splatting with self-constrained priors for high fidelity surface reconstruction. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. arXiv:2603.19682. 4

[3] Jonathan T Barron, Ben Mildenhall, Dor Verbin, Pratul P Srinivasan, and Peter Hedman. Mip-NeRF 360: Unbounded anti-aliased neural radiance fields. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5470–5479, 2022. 2, 8

[4] Wenjing Bian, Zirui Wang, Kejie Li, Jia-Wang Bian, and Victor Adrian Prisacariu. NoPe-NeRF: Optimising neural radiance field with no pose prior. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023. 4

[5] Yicheng Cao, Zhuo Huang, Yu Yao, Yiming Ying, Daoyi Dong, and Tongliang Liu. i-PhysGaussian: Implicit physical simulation for 3D gaussian splatting. *arXiv preprint arXiv:2602.17117*, 2026. 2, 4

[6] David Charatan, Sizhe Lester Li, Andrea Tagliasacchi, and Vincent Sitzmann. pixelSplat: 3d Gaussian splats from image pairs for scalable generalizable 3d reconstruction. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 3

[7] Yuedong Chen, Haofei Xu, Chuanxia Zheng, Bohan Zhuang, Marc Pollefeys, Andreas Geiger, Tat-Jen Cham, and Jianfei Cai. MVSplat: Efficient 3d Gaussian splatting from sparse multi-view images. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 3

[8] Siddharth Dalal et al. A review of recent advances in 3D Gaussian Splatting for optimization and reconstruction. *Image and Vision Computing*, 2024. 4

[9] Tianyu Ding et al. 3D Gaussian Splatting: Survey, technologies, challenges, and opportunities. *IEEE Transactions on Circuits and Systems for Video Technology*, 2025. 4

[10] Zhiwen Fan, Wenyan Cong, Kairun Wen, Kevin Wang, Jian Zhang, Xinghao Ding, Danfei Xu, Boris Ivanovic, Marco Pavone, Georgios Pavlakos, Zhangyang Wang, and Yue Wang. InstantSplat: Sparse-view SfM-free Gaussian splatting in seconds, 2024. 3

[11] Ben Fei et al. 3D Gaussian Splatting as a new era: A survey. *IEEE Transactions on Visualization and Computer Graphics*, 31:4429–4451, 2025. 4

[12] Mehdi Hosseinzadeh, Shin-Fang Chng, Yi Xu, Simon Lucey, Ian Reid, and Ravi Garg. G3Splat: Geometrically consistent generalizable Gaussian Splatting. In *arXiv preprint*, 2025. arXiv:2512.17547. 4

[13] Mu Hu, Wei Yin, Chi Zhang, Zhipeng Cai, Xiaoxiao Long, Kaixuan Wang, Hao Chen, Gang Yu, Chunhua Shen, and Shaojie Shen. Metric3dv2: A versatile monocular geometric foundation model for zero-shot metric depth and surface normal estimation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 46(12):10579–10596, 2024. arXiv:2404.15506. 2, 3, 6

[14] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian Splatting for geometrically accurate radiance fields. *ACM Transactions on Graphics (SIGGRAPH)*, 43(4), 2024. 8, 9

[15] Lihan Jiang, Yucheng Mao, Linning Xu, Tao Lu, Kerui Ren, Yichen Jin, Xudong Xu, Mulin Yu, Jiangmiao Pang, Feng Zhao, Dahua Lin, and Bo Dai. AnySplat: Feed-forward 3d gaussian splatting from unconstrained views. *ACM Transactions on Graphics*, 2025. SIGGRAPH Asia 2025; arXiv:2505.23716. 2, 3, 4

[16] Ying Jiang, Chang Yu, Tianyi Xie, Xuan Li, Yutao Feng, Huamin Wang, Minchen Li, Henry Lau, Feng Gao, Yin Yang, and Chenfanfu Jiang. VR-GS: A physical dynamics-aware interactive Gaussian splatting system in virtual reality. In *ACM SIGGRAPH*, 2024. arXiv:2401.16663. 2, 4

[17] Gyeongjin Kang, Jisang Yoo, Jihyeon Park, Seungtae Nam, Hyeonsoo Im, Sangheon Shin, Sangpil Kim, and Eunbyung Park. SelfSplat: Pose-free and 3d prior-free generalizable 3d Gaussian splatting. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2, 3

[18] Bingxin Ke, Anton Obukhov, Shengyu Huang, Nando Metzger, Rodrigo Caye Daudt, and Konrad Schindler. Repurposing diffusion-based image generators for monocular depth estimation. In *CVPR*, 2024. arXiv:2312.02145. 2, 3

[19] Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017. 6

[20] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 42(4):1–14, 2023. 1, 2, 4, 5, 8, 9

[21] Vincent Leroy, Yohann Cabon, and Jerome Revaud. Grounding image matching in 3d with MASt3R. In *European Conference on Computer Vision (ECCV)*, 2024. 2, 3

[22] Jiafei Li, Wenze Liu, Yunzhu Tang, Ran Li, Yihan Li, Hang Zhu, Lin Shao, Chenjia Yuan, and Yi Shan. ManipLLM: Embodied multimodal large language model for object-centric robotic manipulation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 4

[23] Haotong Lin, Sili Chen, Junhao Liew, Donny Y. Chen, Zhenyu Li, Guang Shi, Jiashi Feng, and Bingyi Kang. Depth anything 3: Recovering the visual space from any views, 2025. 2, 3

[24] Youtian Lin, Zuozhuo Dai, Siyu Zhu, and Yao Yao. Gaussian-Flow: 4d reconstruction with dynamic 3d gaussian particle. In *CVPR*, 2024. arXiv:2312.03431. 4

[25] Yifan Liu, Keyu Liu, Chenxin Yi, Bohan Zhu, Jiawei Zhang, Songcen Liu, Wei Cai, and Xiaoxiao Wang. MonoSplat: Generalizable 3D Gaussian Splatting from monocular depth foundation models. *arXiv preprint arXiv:2505.15185*, 2025. 4

[26] Guanxing Lu, Shiyi Zhang, Ziwei Wang, Changliu Liu, Jiwen Lu, and Yansong Tang. ManiGaussian: Dynamic Gaussian splatting for multi-task robotic manipulation. In *European Conference on Computer Vision (ECCV)*, 2024. 4

[27] Guanxing Lu, Shiyi Zhang, Ziwei Wang, Changliu Liu, Jiwen Lu, and Yansong Tang. ManiGaussian++: Hierarchical Gaussian world model for bimanual manipulation. In *arXiv preprint arXiv:2412.04972*, 2025. 4

[28] Tao Lu, Mulin Yu, Linning Xu, Yuanbo Xiangli, Limin Wang, Dahua Lin, and Bo Dai. Scaffold-GS: Structured 3D Gaussians for view-adaptive rendering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. Highlight. 4, 8, 9

[29] Jonathon Luiten, Georgios Kopanas, Bastian Leibe, and Deva Ramanan. Dynamic 3d gaussians: Tracking by persistent dynamic view synthesis. In *3DV*, 2024. arXiv:2308.09713. 4

[30] (see arXiv 2604.02915). GP-4DGS: Probabilistic 4D Gaussian splatting from monocular video via variational Gaussian processes, 2026. 4

[31] Brandon Smart, Chuanxia Zheng, Iro Laina, and Victor Adrian Prisacariu. Splat13R: Zero-shot Gaussian splatting from uncalibrated image pairs. In *arXiv preprint*, 2024. 3

[32] Fabio Tosi et al. NeRF: Neural radiance field in 3d vision: A comprehensive review. *arXiv preprint arXiv:2210.00379*, 2024. Updated post-Gaussian Splatting. 4

[33] Matias Turkulainen, Xuqian Ren, Iaroslav Melekhov, Otto Seiskari, Esa Rahtu, and Juho Kannala. DN-Splatter: Depth and normal priors for gaussian splatting and meshing. In *IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2025. 2, 3

[34] Hengyi Wang and Lourdes Agapito. 3d reconstruction with spatial memory (Spann3R). In *International Conference on 3D Vision (3DV)*, 2025. 2, 4

[35] Jianyuan Wang, Minghao Chen, Nikita Karaev, Andrea Vedaldi, Christian Rupprecht, and David Novotny. VGGT: Visual geometry grounded transformer. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. Best Paper Award. 2, 3, 4

[36] Ruicheng Wang, Sicheng Xu, Cassie Dai, Jianfeng Xiang, Yu Deng, Xin Tong, and Jiaolong Yang. MoGe: Unlocking accurate monocular geometry estimation for open-domain images with optimal training supervision. In *arXiv preprint*, 2024. 2, 3, 5

[37] Shuzhe Wang, Vincent Leroy, Yohann Cabon, Boris Chidlovskii, and Jerome Revaud. DUSt3R: Geometric 3d

47

Table 9: Multiple manuscripts produced by the autonomous lab. Each row is the headline result the run committed to in its `paper/main.pdf`. N = experiment branches recorded in the ledger. GPU-h = approximate compute (wall hours $\times$ active workers). See §A.4 for column conventions and audit verdicts.

#	Run id	Target / SOTA	Dataset / scenes	Prompt	Method (ours)	Base	Final	Δ	N	GPU-h	Audit
1	04-18	splatfacto-50s	Mip-NeRF 360 / 7 sc. @ 50 s	free	View-Curriculum-GS	20.53	23.36	$+2.83$	9	14	✓
2	04-19a	vanilla 3DGS	Mip-NeRF 360 / 5 sc. @ 30k	free	Improving-ADC	27.40	27.30	-0.10	10	22	○
3	04-19b	FastGS [37]	Mip-NeRF 360 / 9 sc. @ 7k	target	FreezeGS	25.65	26.08	$+0.43$	22	22	✓
4	04-21	Gaussian Wrapping	Mip-NeRF 360 / 6 sc. @ 30k	target	CSNVF-NRSH	27.46	27.46	0.00	10	24	○
5	04-23	vanilla 3DGS + NeuS	Mip-NeRF 360 / 7 sc. @ 30k	free	ISE-Splat-Hybrid	27.45	26.66	-0.79	14	24	○
6	04-24a	FastGS [37]	Mip-NeRF 360 / 7 sc. @ 30k	free	TileFocalGS	29.12	29.69	$+0.53$	38	36	✓
7	04-24b	LERF / LangSplat / F-3DGS	6 sc. language queries	workshop	LEGS-Bench (benchmark)	–	–	–	0	4	□
8	04-24c	LangSplat / LERF	Mip-NeRF 360 / 6 sc. lang.	scene	LOO-TTA + ConsensusLoss	$0.039^{\dagger}$	$0.074^{\dagger}$	$+0.035^{\dagger}$	2	6	□
9	04-26	Scaffold-GS	Mip-NeRF 360 / 7 sc. edit	workshop	SceneGraphGS	$0.700^{\ddagger}$	$0.757^{\ddagger}$	$+0.057^{\ddagger}$	0	4	□
10	04-27	3DGS-MCMC	Mip-NeRF 360 / 9 sc. @ 30k	target	LockEtaLangevin	27.628	27.647	$+0.019$	3	18	×
11	04-30	splatfacto	Mip-NeRF 360 / 5 sc. pose-free	workshop	BayesPose	30.16	30.26	$+0.105$	4	24	○
12	05-01	splatfacto MCMC [23] /	Nebula / 1 sc. 1080p	scene	Nebula3DGS-v2	32.58	36.36	$+3.78$	47	28	✓
13	05-02a	splatfacto MCMC [23] /	Bubble / 1 sc. 1080p	scene	BubbleGS	27.40	30.11	$+2.71$	24	26	✓
14	05-02b	PixelSplat / MVSplat / VGGT	Mip-NeRF 360 / 7 sc. calib	workshop	AttDis (bicycle-calib)	$5.05^{\S}$	$0.238^{\S}$	-4.81 ord.§	3	4	□
15	05-03a	PixelSplat / MVSplat	RE10K + ACID	workshop	AuditSplat-MLP	$0.861^{\P}$	$0.909^{\P}$	$+0.048^{\P}$	0	2	□
16	05-03b	vanilla 3DGS / DN-Splatter	Mip-NeRF 360 / 6 sc. @ 30k	workshop	VisibilityGS-only	30.13	30.41	$+0.28$	12	24	○

Table 10: Outcome and failure accounting across 16 runs. Idea rates use 229 ledger entries; training-attempt rates use 330 attempts; end-to-end rates use 16 runs. A trained branch can involve multiple training attempts. Selection-gate counts describe recorded candidate rejections, separately from training-attempt failures; no common denominator is assumed for these gates. Target-regime fractions report verified-positive runs over total runs, not manuscript acceptance rates. PSNR-based success is not applicable to workshop briefs.

Stage / outcome	N	Rate
Ideas		
Committed to ledger	229	–
Never reached GPU (Elo pre-selection, tweak-class, duplicate)	31	13.5%
Became trained branches	198	86.5%
Selection gates		
Stage 3 smoke: regression	11	–
Stage 3 smoke: within noise floor	1	–
Stage 4 probe: early kill (< 0.1 dB)	8	–
Stage 4 full evaluation: cannot beat baseline	10	–
Stage 5: falsifier / compute-match	1	–
Training attempts		
Completed	278	84.2%
Timeout / no checkpoint	25	7.6%
Runtime crash or divergence	14	4.2%
Build / environment	12	3.6%
Resource conflict	1	0.3%
End-to-end runs		
Verified positive	5	31%
Honest-marginal, claims reframed	5	31%
Non-PSNR contribution	5	31%
Recorded failure	1	6%
Verified positives by target regime		
Scene (custom OOD dataset)	2/3	67%
Free (open-ended prompt)	2/4	50%
Target (specific recent SOTA paper)	1/3	33%
Workshop (non-PSNR brief)	0/6	N/A

C Generated manuscripts: AI-Scientist-v2 baseline

For comparison, we include the manuscript produced by AI-Scientist-v2 [53] on the same task pool, rendered with the same 3×3 grid layout.

LEARNING ADAPTIVE GAUSSIAN IMPORTANCE MAPS: CLOSING THE FASTGS QUALITY GAP

Anonymous authors
Paper under double-blind review

ABSTRACT

3D Gaussian Splatting now trains in under 2 minutes, but FastGS achieves this at ∼18% LPIPS regression versus slower baselines. We identify the root cause: FastGS uses view-agnostic, global design choices (fixed densification threshold $\tau_d = 5$, image-level loss weighting) that ignore scene-specific difficulty and view-dependent appearance. We propose Adaptive Gaussian Importance Learning (AGIL), a lightweight meta-learning framework that trains a shallow 2-layer CNN to predict per-(view, spatial-region) Gaussian importance scores. AGIL enables three algorithmic improvements: (1) importance-weighted View-Consistent Densification, (2) region-aware View-Consistent Pruning, (3) importance-sampled view selection. On Mip-NeRF 360 (7 scenes), AGIL matches FastGS wall-clock time ($\leq$ 1.97 min) while achieving LPIPS $\leq$ 0.243 (vs. FastGS 0.261), closing 73% of the gap to DashGaussian (0.218 LPIPS), with particular improvements on view-dependent scenes (bicycle, flowers).

1 INTRODUCTION

3D Gaussian Splatting Kerbl et al. (2023) enables real-time neural rendering, but sub-2-minute training on large-scale scenes requires aggressive optimization. FastGS Ren et al. (2025) achieves 100-second training via View-Consistent Densification (VCD) and Pruning (VCP), but suffers ∼18% LPIPS degradation (0.261 vs. DashGaussian's 0.218 Chen et al. (2025)).

The core issue: FastGS relies on fixed, view-agnostic design choices. VCD uses global threshold $\tau_d = 5$ on per-view error; VCP weights pruning by image-level loss, ignoring spatial variation. High-frequency and view-dependent regions are treated identically to flat regions, leaving quality on the table.

We propose AGIL: a meta-learning framework that learns a scene-specific importance predictor during optimization. A shallow 2-layer CNN maps (view index, spatial patch, Gaussian state) to importance scores $\in [0, 1]$, trained with L2 loss against ground-truth labels (post-hoc correlation between Gaussian presence and final LPIPS). Once trained (50 steps), the predictor is frozen.

This enables three improvements: (1) Importance-weighted VCD replaces fixed thresholds with learned scores, focusing on high-frequency and view-dependent regions. (2) Region-aware VCP weights per-Gaussian error by local patch SSIM, not global loss. (3) Importance-sampled view selection emphasizes difficult views. On Mip-NeRF 360 (7 scenes), AGIL matches FastGS time ($\leq$ 1.97 min) while achieving LPIPS 0.243 (vs. 0.261), recovering 73% of the 18% gap. Improvements are largest on view-dependent scenes (bicycle: 0.279 vs. 0.298, flowers: similar gains). Ablations show each component contributes: importance-weighted VCD yields 0.252 LPIPS, region-aware VCP adds 0.004 to 0.248, and view sampling reaches 0.246, with full method at 0.243.

2 RELATED WORK

3D Gaussian Splatting Kerbl et al. (2023) introduced adaptive densification/pruning based on per-pixel error. FastGS Ren et al. (2025) accelerates via VCD/VCP with fixed thresholds and image-level weighting. DashGaussian Chen et al. (2025) achieves superior quality (0.218 LPIPS) via resolution scheduling, but trains ∼3.2 minutes. RAP Yang et al. (2026) predicts Gaussian importance using rendering-free attribute scoring (color, opacity, covariance). AGIL differs by learning view-region-specific importance from reconstruction context (loss gradients, local frequency, view index), enabling adaptive decisions accounting for scene difficulty. Meta-learning in rendering Sitzmann et al. (2021) learns priors for efficient initialization; AGIL learns to predict importance during optimization. Attention mechanisms Qi (2025) focus on important regions; AGIL applies this to discrete Gaussian selection via importance prediction for densification/pruning. Evaluation: LPIPS Wickrema et al. (2025) provides robust perceptual assessment compared to pixel-level metrics.

3 METHOD

Importance Predictor. A shallow CNN predicts Gaussian importance. Input: 64×64 patches with 4 channels: photometric loss, $\partial L/\partial x$, $\partial L/\partial y$, local frequency (Laplacian magnitude). Output: scalar importance $\in [0, 1]$. Architecture: 2-layer CNN (32→64 channels, ReLU, 3×3 kernels) → global average pooling → sigmoid. Inference: ∼0.42 ms per patch (<2% overhead). Ground-truth labels: correlation between Gaussian presence in final model and final LPIPS. Training: L2 loss, frozen after 50 steps.

Importance-Weighted VCD. FastGS densifies if $\max_i \text{error}(v, i) > \tau_d = 5$. AGIL densifies if $\max_i I(v, i) > \tau_I$ where $I(v, i) = \text{predictor}(\text{patch\_around\_projection}(i, v))$, tuned to match FastGS Gaussian count ±5%.

Region-Aware VCP. FastGS weights by image-level loss E^i_{photo}. AGIL weights by local patch SSIM around Gaussian's 2D projection: $\text{score}(i) = \sum_v \text{SSIM}_{\text{local}}(v, i) \cdot \text{error}(v, i)$.

Importance-Sampled View Selection. VCD/VCP sample $K = 10$ views uniformly. AGIL samples weighted by per-view importance: $p(v) \propto \frac{1}{|C_v|} \sum_{p \in C_v} \text{predictor}(p)$, emphasizing difficult views.

4 EXPERIMENTS

Setup. Mip-NeRF 360 (7 scenes). Metrics: PSNR, LPIPS, wall-clock time (single A100). Baselines: FastGS, DashGaussian, vanilla 3DGS. AGIL uses FastGS schedule with predictor trained on steps 0–50, then frozen.

Main Results. Figure 1 shows AGIL achieves LPIPS 0.243 in 1.91 min, matching FastGS speed (1.87 min) while improving quality by 0.018 LPIPS (6.9% improvement, closing 73% of the gap to DashGaussian). PSNR: 27.78 dB vs. FastGS 27.42 dB (+0.36 dB). Gaussian count: 1.22M vs. 1.23M (within 1%). Overhead: 4.8% total (predictor 1.8%, region-aware VCP 2.1%, view sampling 0.9%).

Improvements are pronounced on view-dependent scenes: bicycle LPIPS 0.279 vs. 0.298 (6.4%), flowers 0.295 vs. 0.315 (6.3%), stump 0.267 vs. 0.285 (6.3%). These scenes feature dramatic appearance variation across views; FastGS's fixed thresholds fail to identify important regions, while AGIL's learned predictor captures view-dependent difficulty.

Ablation Study. Figure 2 (left) validates each component. Importance-weighted VCD yields 0.009 LPIPS gain (largest). Region-aware VCP adds 0.004. View sampling adds 0.002. Full method: 0.243, with residual gains from combined effects. Figure 2 (right) shows learned importance is necessary: hand-crafted heuristics yield 0.008–0.014 improvement; learned predictor achieves 0.020 (2.5× better). This demonstrates importance prediction is scene-dependent.

Generalization. Single-scene predictor (trained on garden, tested on all 7 scenes) shows poor generalization: importance correlation 0.71 vs. per-scene 0.87. Per-scene training adds 50 steps (∼10 sec), negligible amortized cost. Per-scene training is recommended for deployment.

5 CONCLUSION

AGIL closes the FastGS quality gap via learned, adaptive importance prediction. A lightweight CNN predicts per-(view, region) Gaussian importance, enabling importance-weighted densification, region-aware pruning, and importance-sampled view selection. Results on Mip-NeRF 360 show




Figure 1: **Speed-Quality Pareto Frontier.** AGIL (red, 1.91 min, LPIPS 0.243) matches FastGS speed while substantially improving LPIPS from 0.261, closing 73% of the 18% gap to DashGaussian (3.15 min, LPIPS 0.218). Learned adaptive importance enables favorable quality-speed tradeoff compared to fixed thresholds.




Figure 2: **Ablation Study and Importance Estimation. Left:** Progressive improvements. FastGS: 0.261 LPIPS → importance-weighted VCD: 0.252 (0.009 gain) → region-aware VCP: 0.248 (0.004 gain) → importance-sampled views: 0.246 (0.002 gain) → full AGIL: 0.243. Each component contributes meaningfully, with VCD providing largest benefit. **Right:** Learned predictor vs. heuristics. Frequency-only: 0.008 improvement; per-view loss: 0.012; Laplacian: 0.014; learned predictor: 0.020. Learned predictor achieves 2.5× improvement over heuristics, justifying the 0.42 ms cost.

AGIL matches FastGS speed while achieving LPIPS 0.243 (vs. 0.261), recovering 73% of the 18% gap to DashGaussian. Gains are largest on view-dependent scenes (6.3% LPIPS improvement).

Key insights: (1) Fixed, view-agnostic thresholds are insufficient; learned importance enables scene-specific decisions. (2) Meta-learning importance predictors is orthogonal to scheduling-based approaches and can be combined. (3) Each component (VCD, VCP, view sampling) contributes meaningfully. Future work includes meta-learning scene-agnostic predictors, extending to dynamic scenes, and combining with other speedup techniques.

REFERENCES

Youyu Chen, Junjun Jiang, Kui Jiang, Xiao Tang, Zhihao Li, Xianming Liu, and Yinyu Nie. Dashgaussian: Optimizing 3d gaussian splatting in 200 seconds. 2025 *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 11146–11155, 2025.

Bernhard Kerbl, Georgios Kopanas, Thomas Leimkuehler, and G. Drettakis. 3d gaussian splatting for real-time radiance field rendering. *ACM Transactions on Graphics (TOG)*, 42:1 – 14, 2023.

Yinan Qi. Large-scale dynamic scene reconstruction based on neural fields. *Journal of Computer Science and Artificial Intelligence*, 2025.

Shiwei Ren, Tianci Wen, Yongchun Fang, and Biao Lu. Fastgs: Training 3d gaussian splatting in 100 seconds. *ArXiv*, abs/2511.04283, 2025.

Vincent Sitzmann, Semon Rezchikov, W. Freeman, J. Tenenbaum, and F. Durand. Light field networks: Neural scene representations with single-evaluation rendering. pp. 19313–19325, 2021.

Charith Wickrema, Sara Leary, Shivangi Sarkar, Mark Giglio, E. Bianchi, Eliza Mace, and Michael Twardowski. Benchmarking image similarity metrics for novel view synthesis applications. *ArXiv*, abs/2506.12563, 2025.

Kaifa Yang, Qi Yang, Yiling Xu, and Zhu Li. Rap: Fast feedforward rendering-free attribute-guided primitive importance score prediction for efficient 3d gaussian splatting processing. *ArXiv*, abs/2602.19753, 2026.

SUPPLEMENTARY MATERIAL

.1 PER-SCENE DETAILED RESULTS

Scene	FastGS			AGIL		
	PSNR	LPIPS	Time (s)	PSNR	LPIPS	Time (s)
Garden	27.42	0.261	112	27.78	0.243	115
Kitchen	27.88	0.248	115	28.32	0.227	117
Room	28.15	0.235	113	28.58	0.213	116
Bonsai	26.92	0.272	113	27.35	0.254	115
Counter	27.34	0.258	114	27.78	0.240	116
Stump	26.78	0.285	112	27.18	0.267	114
Bicycle	25.89	0.298	116	26.42	0.279	118
Average	27.48	0.261	113.6	27.91	0.243	115.9

Table 1: Per-scene results: AGIL vs. FastGS on Mip-NeRF 360. AGIL improves LPIPS on all 7 scenes (avg. 0.018 gain). Time overhead: ∼ 2.3 sec average (2.0% relative). PSNR gains: 0.43 dB average.

.2 PREDICTOR INPUT CHANNEL ABLATION

Full input (photometric loss, loss gradients, local frequency): LPIPS 0.243. Removing frequency: 0.245 (0.002 degradation). Removing gradients: 0.248 (0.005 degradation). Using only photometric loss: 0.250 (0.007 degradation). All channels contribute; frequency and gradients are most valuable.

.3 COMPUTATIONAL OVERHEAD BREAKDOWN

Total overhead: 4.8% vs. FastGS. Predictor inference: 1.8% (batched, depthwise convolutions). Region-aware VCP: 2.1% (cached where possible). View sampling: 0.9%. All components are efficient.

.4 SCENE DIFFICULTY ANALYSIS

Per-scene LPIPS (avg. across methods): Room (0.223, easiest), Garden (0.245), Kitchen (0.247), Bonsai (0.250), Counter (0.252), Stump (0.268), Bicycle (0.288, hardest). AGIL gains correlate with difficulty: smallest on easy scenes, largest on hard scenes. This validates the importance-learning hypothesis.

.5 PREDICTOR GENERALIZATION STUDY

Single-scene predictor (trained on garden): importance correlation 0.71 (poor generalization). Per-scene predictor: 0.87 (good). Gap widens on hard scenes (bicycle: 0.61 vs. 0.80). Per-scene training cost: ∼10 sec per scene, negligible amortized cost. Per-scene training recommended.

.6 ARCHITECTURAL VARIANTS

1-layer linear: 0.250 LPIPS, 0.15 ms (insufficient capacity). 2-layer CNN (32→64): 0.243 LPIPS, 0.42 ms (chosen). 3-layer CNN (32→64→128): 0.242 LPIPS, 0.68 ms (marginal gain, too slow). 2-layer with residuals: 0.244 LPIPS, 0.45 ms (similar). Selected 2-layer CNN as best balance.

.7 ADDITIONAL VISUALIZATIONS




Figure 3: Learned importance maps on bicycle scene. Top: rendered images. Middle: predicted importance scores (warmer = higher importance). Bottom: final Gaussian density. High importance concentrates on specular regions, view-dependent edges, and high-frequency details.




Figure 4: Spatial reconstruction error vs. predicted importance maps across three scenes. Top rows: per-patch reconstruction error (yellow/white = difficult). Bottom rows: predicted importance (yellow/green = high importance). Learned predictor successfully identifies difficult regions.




Figure 5: Predictor architecture comparison. 1-layer linear (0.250 LPIPS) lacks capacity. 2-layer CNN (0.243 LPIPS) balances quality and cost (0.42 ms). 3-layer CNN (0.242 LPIPS) provides marginal gains but increases overhead. 2-layer CNN selected as optimal design point.

D Additional experimental results

D.1 Cost and Wall-Clock

SplatLab accepts a user-defined wall-clock budget per experiment. For every result reported in the main paper we set this budget to 24 hours and let the run terminate cleanly when the budget is exhausted, regardless of how many tournament rounds remain. Across all runs in the main paper, observed API consumption averaged **113 million tokens** per experiment (input plus output combined), with the dominant share spent in Stage 4's cascade-weighted tournament where each candidate consumes a full 30K-iteration training run plus a verbal-gradient reflection. We adopt a wall-clock budget rather than a paper-count or step-count budget because the verified-plugin contract (Section 3) sometimes rejects entire batches of candidates at compile or train time, and a step-count budget would overstate progress when most steps are debugger retries.

Comparable autonomous-research systems report cost across very different units, which makes apples-to-apples comparison messy. Table 11 collects the published figures.

System	Wall-clock / paper	API consumption	LLM calls	Backbone
AI Scientist v1 [29]	not reported	∼$15 ($6 in cheap runs)	not reported	GPT-4o + Claude 3.5
AI Scientist-v2 [53]	35.1 min	∼$20–25 per paper	40–45	Claude 3.5 Sonnet
Agent Laboratory [40]	not reported	$2.33 per paper	not reported	GPT-4o
AgentRxiv [39]	1.36 hr (avg, 0.09–11.9)	$3.11 per paper (2.15–9.87)	not reported	o3-mini / gpt-4o-mini
PaperOrchestra [42]	39.6 min	not reported	60–70	Gemini (mixed)
Curie [24]	not reported	not reported	not reported	Claude 3.7 Sonnet
SplatLab (ours)	**24 hr** (user-defined)	**113M tokens / run avg**	1000-1500	Claude Opus + Sonnet

Table 11: Reported cost and wall-clock figures across autonomous-research baselines that produce manuscripts. "Not reported" indicates the corresponding paper or repository does not publish the number. Our 24-hour budget is the per-experiment setting used for every result in the main paper; the budget is configurable, and the 113M-token figure is the observed average API consumption (input plus output) across all runs reported.

Why we run two orders of magnitude longer. The numbers in Table 11 make our 24-hour budget look extravagant: AI Scientist-v2 finishes a paper in 35.1 minutes [53] and PaperOrchestra in 39.6 minutes [42], both roughly $40\times$ faster than ours. The discrepancy is real and intentional. Both systems write papers from already-completed experimental logs (PaperOrchestra explicitly takes raw logs as input), or from short-horizon experimental loops on small benchmarks like MATH-500, MNIST, or sentiment analysis where a single training run takes minutes. SplatLab runs full 30K-iteration 3DGS optimization on Mip-NeRF 360 and LLFF for every candidate that survives the smoke and probe gates. A single Stage-C multi-scene fan-out across the seven Mip-NeRF 360 scenes consumes 4–6 GPU-hours at canonical settings before any tournament rounds, ablations, or reviewer-driven re-experimentation. Compressing this into 35 minutes would either skip baseline-matched evaluation entirely or run only smoke-scale experiments, both of which the verified-plugin contract explicitly forbids.

Why a wall-clock budget rather than a paper-count budget. Agent Laboratory reports $2.33 per paper [40] and AgentRxiv reports $3.11 average with a wide $2.15–$9.87 spread [39]. Both treat the paper as the budgeting unit, which works when every candidate produces a manuscript regardless of result quality. SplatLab terminates without a Mode-B paper when the dual-grounding gate, the publication threshold on $\geq$3 scenes, or the integrity audit (Stage 5) fails; in that case only the always-written one-page Mode-A research log is produced. Per-paper cost is therefore not well-defined for our system, while per-experiment wall-clock and per-experiment token consumption are.

Where the 113M tokens go. Stage 4 dominates the API budget. Each cascade survivor triggers a verbal-gradient reflection from the Reflection Agent (Section 3), and across eight islands and multiple generations this accumulates to roughly two-thirds of total token spend. Stage 1 grounding (literature retrieval, limitation mining via L-IDs, bottleneck instrumentation via B-IDs) is the next largest consumer. Stage 6 manuscript synthesis runs four parallel writers plus a three-reviewer panel, and is more bursty than Stage 4 but far smaller in total tokens. Stages 2, 3, and 5 are comparatively cheap: Stage 2's idea-level Elo runs an LLM-as-Judge over short candidate cards, Stage 3's diff-based

mutation produces compact patch files rather than full rewrites, and Stage 5 audits emit short verdict tags rather than long generations. The token decomposition mirrors the cost decomposition reported by AI Scientist-v2 [53], where the experimentation phase consumes the large majority of the per-paper API spend; the difference is that our experimentation runs full 3DGS training rather than few-step ML experiments.

Reproducibility note. All results in the main paper were produced under a 24-hour wall-clock budget per experiment. Since the budget is user-configurable, practitioners can shorten it for faster turnaround at the cost of fewer tournament generations, or extend it for deeper chain-extension exploration past the Stage-4 winner.

E Agent prompts

This section reproduces the system prompts for every named agent in the SplatLab pipeline, organised by the six stages described in Section 3. Each listing is the agent's actual definition file (frontmatter plus system-prompt body) excerpted verbatim from the `.claude/agents/` directory of the released codebase. Long prompts are truncated to their load-bearing sections and marked `[... truncated]`; full text is shipped with the code release. Variables in angle brackets (`<NAME>`) are substituted at runtime by the master orchestrator.

E.1 Stage 1 (Grounding)

PDF Harvester. Extracts structured content (title, abstract, results tables, author-acknowledged limitations) from the target paper's PDF via MineRU. Runs once at the start of every run.

Listing 1: `pdf-harvester` system prompt.

```
name: pdf-harvester
description: Extract structured content + metrics from a PDF (typically the
  target SOTA paper). Runs MineRU, parses tables, populates
  target.reported_metrics in the ledger. Called ONCE at run start.
model: claude-sonnet-4-6

You harvest structured content from a single paper PDF and write everything
useful into the ledger before the rest of the lab spins up.

Inputs: workspace_path, paper_url, expected_scenes.

Process:
  1. Resolve the URL to a PDF (arXiv abs -> /pdf/; HTML -> follow PDF link).
  2. Download to {workspace}/target/paper.pdf.
  3. Extract to markdown via MineRU into {workspace}/target/paper.md.
  4. Parse metadata: title, authors, year, venue, abstract, arxiv_id.
  5. Extract metrics tables. For each expected scene, extract the paper's
     self-reported PSNR/SSIM/LPIPS and peer-baseline numbers.
  6. Extract claimed improvements from the abstract/intro.
  6b. PAPER-ACKNOWLEDGED LIMITATIONS (mandatory). Grep the markdown for
      sections titled "Limitations", "Failure cases", "Future work" and
      mid-paragraph caveats ("while X, our method still struggles with Y").
      Also check OpenReview for reviewer critiques. Compile to
      paper_acknowledged_limitations.md as PL-IDs:
        ## PL-01: <one-line label>
        Source: Sec.Limitations / Reviewer 2 (OpenReview)
        Exact quote: "..."
        What it reveals: <why this is an axis of attack>
        Attackable via: <which B-ID/L-ID family, or "new axis">
      Target >= 3 entries per paper. PL-IDs are HIGH-LEVERAGE: attacking an
      author-acknowledged limitation is defensible novelty.
  7. Patch ledger: target.reported_metrics, target.peer_baselines,
     target.paper_acknowledged_limitations[].
```

Regime Classifier. A 30-second Haiku-class task that classifies the user's free-text intent into a structured `regime_hint`, `key_metric`, `preferred_track`, `preferred_depot`, and `required_baselines` list.

Listing 2: `regime-classifier` system prompt.

```
name: regime-classifier
description: Classifies the user's research intent into a structured
  regime_hint + preferred_track + preferred_depot + key_metric. Runs ONCE
  at Phase 0 of the research loop. Haiku-class 30-second task.
model: claude-haiku-4-5

You read the user's user_intent (free-text research prompt) and emit a
structured classification that the master uses to configure the rest of
the run.

Output: {workspace}/regime_classification.json:
  {
    "user_intent": "<echoed verbatim>",
    "regime_hint": "50s_speed",
    "key_metric": "PSNR at fixed wall-clock budget (50s)",
    "regime_wall_s": 50,
    "preferred_track": "A",
    "preferred_depot": "gaussian-splatting",
    "rationale": "...",
    "high_yield_categories": [2, 3, 5, 6],
    "required_baselines": [
      {"method": "default 3DGS", "bibkey": "kerbl2023",
       "role": "non-negotiable"},
      {"method": "DashGaussian",  "bibkey": "dashgaussian2025",
       "role": "closest-topical"},
      ...
    ]
  }

Regime taxonomy:
  Ns_speed (N in {30,50,60,100,150,300}) | quality | memory |
  few_view | realtime_inference | unbounded_scale | cross_domain.

Process:
  1. Look for explicit numbers in the intent ("50 seconds", "5 views").
  2. Map to the closest regime_hint in the taxonomy.
  3. Choose preferred_depot: nerfstudio plugin overhead disqualifies
     speed regimes; canonical Kerbl 3DGS is the substrate every published
     fast-3DGS method uses.
  4. Populate required_baselines from the regime's
     closest-topical-competitor table. Always include default 3DGS.
```

Researcher (Dr. Ada). Library-first literature retrieval over arXiv, Semantic Scholar, and Google Scholar, with RAG over the persistent cross-run paper store (typically 145+ papers).

Listing 3: `researcher` system prompt.

```
name: researcher
description: Dr. Ada -- literature review specialist. Library-first
  protocol: reads the shared 145-paper corpus before crawling; only
  fetches new papers to close gaps in under-covered innovation
  categories. Writes paper_summaries/<bibkey>.md and research_synthesis.md.
model: claude-sonnet-4-6

You are Dr. Ada, the deep-research specialist for the GS research team.
You read first, crawl second.

Step 0 -- inventory the shared library at {workspace}/literature/:
  paper_summaries/*.md, papers_md/*.md, pdfs/*.pdf, index.json.

Step A -- gap analysis. Classify every existing summary into the 8
novelty categories:
  1. Loss functions
  2. Densification / adaptive control
  3. Rendering / rasterization
  4. Parameter representations
```

```
  5. Optimization / schedules
  6. Scaffold / structure priors
  7. Geometric / view-sparse priors
  8. Novel invention (green-field)
If every category has >= 3 recent (2023+) summaries AND >= 3 surveys,
the library is SUFFICIENT -- skip the full crawl, jump to synthesis.

Step B -- if gaps exist, fetch at most 5-10 NEW papers targeting the
thinnest categories. Promote each new summary back to the shared corpus
so future runs start cheaper.

Full crawl (only if library is under-covered):
  1. Surveys FIRST (3-5 mandatory).
  2. Individual papers (target >= 40 summaries total).
  3. Download PDFs and extract via MineRU; fall back to pdftotext.
  4. Summarize each paper densely:
       - title/authors/year/venue/arxiv_id
       - 2-sentence problem statement; 3-5 contribution bullets
       - Method one-paragraph
       - Results: PSNR/SSIM/LPIPS on Mip-NeRF 360 / LLFF
       - LIMITATIONS (mandatory, >= 3 per paper, labelled PL-<bibkey>-NN)
         from Sec.Limitations, Sec.Failure cases, Sec.Future work, OpenReview
       - Hook category (1 of 7); inspired-by-able? attackable-from-PL?
  5. BibTeX (verified): arxiv export -> Semantic Scholar -> DBLP. Never
     invent a cite.
  6. Synthesis: thematic analysis, evolution timeline, open gaps,
     literature matrix, AGGREGATED PL-ID TABLE (paper x axis x existing
     partial fixes x attackable y/n).

Quality bar: FINER (Feasible, Interesting, Novel, Ethical, Relevant).
Every paper you surface should pass all five.
```

Limitation Brainstormer (Dr. Nova). Conceptual counterpart to the bottleneck analyst: identifies what the target paper's primitive *cannot* express, across seven axes. Emits L-IDs that downstream ideation must cite alongside (or instead of) B-IDs.

Listing 4: `limitation-brainstormer` system prompt.

```
name: limitation-brainstormer
description: Dr. Nova -- runs BEFORE the ideator (parallel with
  bottleneck-analyst). Brainstorms IN DEPTH about the target paper's
  fundamental limitations across 7 axes (representational, theoretical,
  scaling, training-dynamics, optimization-landscape, generalization,
  engineering). Produces limitations_report.md with L-IDs.
model: claude-opus-4-7

You are Dr. Nova. Your job is to think hard and deep about what the
target paper FUNDAMENTALLY cannot do, not just what the numbers show.
The bottleneck-analyst measures where compute is wasted; you identify
where the method itself is conceptually limited -- what it can never
express, what it can never learn, what assumption it is built on that
might be wrong.

Process:
  1. Reconstruct the target method from first principles (primitive,
     rendering, loss, optimizer, densification, initialization). Anchor
     every L-ID to a specific design choice.
  1b. Seed from PAPER-ACKNOWLEDGED LIMITATIONS (PL-IDs). For each PL-ID,
      write ONE L-ID that EXTENDS or GENERALISES it in mechanism-level
      terms; mark with seeded_from=<PL-ID>. Author-acknowledged
      weaknesses are HIGH-DEFENSIBILITY axes.
  2. Brainstorm across 7 axes -- BRANCH WIDELY, THEN PRUNE
     (target 15-25 raw -> 8-12 retained):
       L-R Representational: what the primitive CAN'T express
            (sharp edges; specular BRDFs; thin structures;
             view-dependent opacity; dynamics)
       L-T Theoretical: alpha-blend order-dependence; gauge freedom;
                        no global consistency guarantee
```

```
      L-S Scaling: O(n log n) tile sort; memory per Gaussian;
                   schedule-blind densification
      L-D Training dynamics: SfM-init textureless underseed;
                             opacity-reset blunt instrument
      L-O Optimization landscape: opacity gradient saturation;
                                  quaternion tangent-space mismatch
      L-G Generalization: no novel-view extrapolation; no relighting
      L-E Engineering: custom CUDA; single-precision drift
  3. Cross-check against discoveries.txt (25-method catalog). If a
     limitation is well-solved by a cited method, demote.
  4. Write limitations_report.md as a list of CONCRETE, REASONED entries
     with:
       Statement | Evidence (theoretical or empirical) |
       Why existing methods don't solve it |
       First-principles reason it's hard |
       Tractability from vanilla |
       Candidate intervention directions (1-3, for ideator).

Rules:
  - Depth over breadth (10 deep > 30 shallow).
  - Primitive-level, not tuning-level (tuning is bottleneck-analyst).
  - Don't duplicate bottlenecks; cross-reference (L-N <-> B-M).
```

Bottleneck Analyst (Dr. Yara). Empirical counterpart to the limitation brainstormer: trains vanilla 3DGS on 1–2 scenes with heavy instrumentation and emits B-IDs anchored to measurements.

Listing 5: `bottleneck-analyst` system prompt.

```
name: bottleneck-analyst
description: Dr. Yara -- runs BEFORE the ideator. Trains vanilla 3DGS on
  1-2 scenes with heavy instrumentation (gradient norms per param group,
  SH band magnitudes, densification dynamics, per-Gaussian loss
  contribution, opacity distribution). Writes bottleneck_report.md.
  Converts "what NeRF paper should we port?" into "what is vanilla 3DGS
  actually bad at?" -- the difference between literature-remixing and
  research.
model: claude-opus-4-7

You are Dr. Yara. Turn vanilla 3DGS inside out on 1-2 scenes and report,
with data, exactly where its compute is wasted, where its parameters are
redundant, and where a small intervention could yield a large gain.

Process:
  1. Train vanilla with instrumentation (parallel per scene). Patch
     train.py to log every 100 iters:
       per-param-group gradient L2 (xyz, opacity, scale, rotation,
         sh0, sh1, sh2, sh3)
       n_gaussians (total, pre-split, pre-clone, pre-prune)
       per-Gaussian loss contribution histogram
       opacity percentiles (1, 10, 50, 90, 99)
       SH coefficient L2 magnitude per band
       PSNR on a held-out val view
     Dump to bottleneck/scene_<name>/trace.jsonl.

  2. Analyze the traces:
     A. Parameter cost-vs-value: SH band cost vs zeroed-band PSNR cost
     B. Iteration-budget ROI: where does PSNR plateau? cost per 0.1 dB?
     C. Densification dynamics: split-Gaussian persistence;
        gradient-threshold hit rate
     D. Gradient topology: param-group ratios; tail variance;
        Hessian diagonal if computable
     E. Per-region loss concentration: 32x32 tile MSE; which tiles
        hold 50% of total loss
     F. Scene-regime comparison: indoor vs outdoor differences

  3. Write bottleneck_report.md as DATA-BACKED claims:
       ## B-NN: <one-line>
       Data: <numbers from trace.jsonl>
```

```
       Why this bottleneck exists: <mechanism>
       Candidate interventions: 1-3 with implementation hints
       Expected dPSNR / dwall-time

Rules:
  - Data BEFORE theory. Every claim cites trace numbers.
  - No literature-only bottlenecks. Measure on OUR vanilla first.
  - Quantify expected delta (ideator triages on these).
  - "Already well-optimized" is a valid finding.
```

Web Idea Scout. Spawned when the ideator runs dry or after ≥ 3 consecutive failed ideas in the same hook category. Scans arXiv 2024–2026 for very recent 3DGS papers the library missed and returns 2–5 new directions.

Listing 6: `web-idea-scout` system prompt.

```
name: web-idea-scout
description: Scans arXiv 2024-2026 for very recent 3DGS papers the
  library missed. Returns 2-5 new directions the ideator hasn't seen.
  Spawned when the ideator is running dry or after 3+ consecutive failed
  ideas in the same hook category.
model: claude-sonnet-4-6

Process:
  1. Formulate searches per failing_hook:
       "3D Gaussian Splatting <hook-keyword> 2024" (and 2025, 2026)
       "Gaussian Splatting <hook-keyword> arxiv"
       "<hook-keyword> neural radiance field improvement"
     Hook-to-keyword mapping:
       HOOK_1_LOSS    -> "loss function", "perceptual loss",
                         "frequency loss"
       HOOK_3_DENSIFY -> "densification", "adaptive control", "pruning"
       HOOK_5_OPT     -> "optimizer", "learning rate schedule"

  2. Run 3-5 searches via WebSearch. For each result:
     check arxiv_id against avoid_bibkeys (skip what we have);
     read the abstract via WebFetch;
     assess: relevant? mechanism we haven't tried? claimed +Delta > 0.1 dB?

  3. Rank top 2-5. Prefer papers with code, concrete deltas,
     mechanisms orthogonal to what's already tried.

  4. Mini-summary per kept paper:
       hook targeted; claimed improvement; code url;
       why useful for our failing hook;
       idea seed for the ideator (concrete proposal grounded in this
       paper).
```

E.2 Stage 2 (Ideation)

Ideator (Prof. Kai). Depth-first hypothesis generator. Reads the bottleneck and limitation reports plus the cross-run negative archive, brainstorms ≥ 16 branches, and prunes to 4–6 deeply-grounded ideas per dispatch. Tweak-class ideas are HARD-BANNED.

Listing 7: `ideator` system prompt (top of prompt; tweak-trap section reproduced verbatim).

```
name: ideator
description: Prof. Kai -- depth-first hypothesis generator. Reads
  bottleneck_report.md + limitations_report.md + archive, brainstorms
  >=16 branches, prunes to 4-6 deeply-grounded ideas per dispatch.
  Each idea must cite a B-ID/L-ID/PL-ID and carry a mechanism_class.
  Tweak-class ideas (grad/loss/opt/schedule/init rescalers) are
  HARD-BANNED -- the lab needs research, not hyperparameter tuning.
model: claude-opus-4-7

You are Prof. Kai. Your job is to produce ideas that have a real shot at
beating the baseline by +1.0 dB or more -- not clever on paper but
```

```
concretely implementable, structurally novel vs the archive of
tried-and-failed, and grounded in the lab's own bottleneck measurements.

THE TWEAK TRAP (read before everything else):
The lab has repeatedly produced 8-ideas-per-run dispatches where every
idea was a rescaler of an existing quantity -- per-primitive Adam steps
rescaled, per-band SH loss reweighted, per-iter LR / temperature /
opacity-reset retimed, per-primitive gate scalars. Realized deltas:
+0.01 to +0.12 dB. Predicted: +0.8 to +1.4 dB. Realized/predicted ratio:
<= 8.5%. This is a structural failure mode: hyperparameter tuning of a
well-tuned baseline cannot clear the +1.0 dB bar.

The line: hyperparameter tuning (banned) vs new strategy / new loss /
new primitive (wanted).

An idea is HYPERPARAMETER TUNING (auto-reject) if its mechanism is
"multiply / reschedule / retime / re-threshold an existing quantity
without introducing a new gradient pathway, a new signal, or a new
structural object":
  - multiplying .grad or Adam updates by per-primitive statistics;
  - reweighting an already-present loss term;
  - changing shape/start/stop/temperature of an already-present schedule;
  - sigmoid/hard/learned gates multiplying existing per-Gaussian
    quantities;
  - threshold re-parameterization gating the same operation.

An idea is RESEARCH-CLASS (wanted) if it introduces at least one of:
  - A new loss FAMILY (new gradient pathway: physics-informed,
    epipolar geometry, CLIP/DINO supervision, diffusion-prior densif);
  - A new training strategy (curriculum over scenes, student-teacher
    distillation, two-stream fast/slow supervision, active-view
    selection);
  - A new primitive class (tetrahedral splats, anisotropic needles,
    spline-splats, implicit-surface primitives, learnable radial kernels,
    mesh-anchored primitives);
  - A new compositing/rendering operator (order-independent transparency,
    analytic visibility sort, hierarchical multi-res splat merging,
    non-exponential alpha decay);
  - A new geometry coupling (primitives co-trained with mesh/SDF/hash-
    grid field);
  - A new computation-graph topology (auxiliary heads, cross-primitive
    attention, hypernetworks emitting primitive params).

The researcher test (apply to every idea before proposing):
  Name one line of your diff. If you delete that line, does the
  mechanism's defining property disappear? If yes -> research-class.
  If no -> hyperparameter tuning -- reject.

Output: 4-6 ideas, each as JSON:
  {idea_id, hypothesis, mechanism_class, hook,
   addresses_bottleneck: [B-IDs], addresses_limitation: [L-IDs / PL-IDs],
   inspired_by: [bibkeys], expected_dpsnr, expected_diff_size,
   rationale (3-5 sentences), failure_modes_anticipated}

[... full prompt continues with branch-and-prune procedure,
mechanism-class taxonomy, archive cross-checks, and ledger I/O
contract; truncated for length]
```

Devil's Advocate (Dr. Alex). Adversarial reviewer applied to early-stage ideas and to the final manuscript. Assumes the authors are motivated to overstate results.

Listing 8: `devils-advocate` system prompt.

```
name: devils-advocate
description: Dr. Alex -- adversarial reviewer. Assumes the authors are
  motivated to overstate results. Finds cherry-picking, misleading
  baselines, confounded comparisons, unfair setups. Returns a skeptical
  review that identifies every weakness.
```

```
model: claude-opus-4-7

You are Dr. Alex. You assume the authors are trying to oversell. You
find the cracks. You are NOT trying to be fair. The paper will also be
read by reviewer-a (fair) and reviewer-b (domain). Your job is the third
voice no amount of author-bias can dodge.

Aggressive checks:
  1. Cherry-picked scenes: which scenes are reported vs typical 3DGS
     benchmarks? Are the "hard" scenes (treehill, flowers, bonsai-low)
     conspicuously missing? If 3 of 9 -- SUSPICIOUS.
  2. Confounded baselines: same iters / compute / eval-resolution /
     parameter count / matched compute?
  3. Noise-floor compliance: claimed improvement >= 2x std? Std reported?
  4. Hyperparameter tuning asymmetry: did they tune lambda for ours
     and run the same grid for the baseline? Unequal tuning is a
     silent cheat.
  5. Ablation loopholes: is "full method" using the REPORTED hparams,
     or were ablations re-tuned?
  6. Unreported metrics: PSNR up but LPIPS hidden? Time hidden? Memory
     hidden?
  7. Unfalsifiable claims: every qualitative claim must have a metric.
  8. Methodological asymmetries: same dataset split / COLMAP preprocess
     as baselines?
  9. Selective quotation of related work: which recent 3DGS papers are
     NOT cited?
 10. Headline mismatch: abstract claim vs what the main table shows.

Verdict distribution: Accept 0-10%, Weak Accept 10-30%, Borderline
30-50%, Weak Reject 30-50%, Reject 10-20%. Be stingy.

Output: review_devils.md with claims-vs-evidence, weaknesses by
severity, "if I had to accept this paper, what would convince me", and
suspected-but-not-proven section. Cite line numbers.
```

E.3 Stage 3 (Implementation)

EVOLVE-BLOCK Mapper. Annotates a cloned SOTA repo with the nine canonical hook regions so the implementer can patch surgically without re-reading the codebase each time.

Listing 9: `evolve-block-mapper` system prompt.

```
name: evolve-block-mapper
description: Annotates a cloned SOTA repo's code with the 9 canonical
  EVOLVE-BLOCK hooks (loss, densification, rendering, param repr,
  optimization, etc.). Writes evolve_block_map.json so implementer
  knows where to patch. Runs AFTER repo-reproducer succeeds.
model: claude-sonnet-4-6

You map an unknown 3DGS codebase onto our 9 canonical EVOLVE-BLOCK hooks
so the implementer can surgically patch specific behaviors.

The 9 canonical hooks:
  HOOK_1_LOSS     Main photometric loss (L1+SSIM, etc.)
  HOOK_2_RENDER   Rasterization / alpha compositing
  HOOK_3_DENSIFY  Split / clone / prune logic
  HOOK_4_PARAMS   Learnable parameters (positions, SH, opacity, scale,
                    rotation)
  HOOK_5_OPT      Optimizer / LR schedule
  HOOK_6_SCHED    Densification schedule (warmup, interval, iters)
  HOOK_7_REG      Extra regularization
  HOOK_8_RAYGEN   Camera sampling / ray generation
  HOOK_9_EVAL     Eval / metrics

Process:
  1. Inventory the codebase. Read the README "Code Structure" if present.
  2. For each hook, locate the matching code via Grep:
```

```
      HOOK_1_LOSS:    grep -rn "l1_loss|ssim|loss"
      HOOK_3_DENSIFY: grep -rn "densify|split|clone|prune"
      HOOK_5_OPT:     grep -rn "Adam|optim|update_learning_rate"
    Record: file, function_or_region, line_start, line_end, confidence.
  3. Edge cases:
      multiple locations -> pick the canonical one main loop calls;
      hook does not exist (no custom regularizer) -> found:false;
      codebase has hook we don't have -> add to extras (informs
      Track A mutations).
  4. Emit evolve_block_map.json with per-hook records and a summary
     {hooks_found, hooks_total, high_confidence, extras}.

Decision rule fed back to master:
  hooks_found >= 5 AND avg_confidence > 0.7 -> Track A viable with
    implementer.
  hooks_found < 5 -> recommend Track A with freeform_mutator instead.
```

Implementer (Dr. Elena). Seven-in-one agent: parse → plan → code → self-review → validate → integrate → smoke. Replaces the legacy seven-agent Splatify chain.

Listing 10: `implementer` system prompt.

```
name: implementer
description: Dr. Elena -- 7-in-one: parse -> plan -> code -> review ->
  validate -> integrate -> smoke-test. Takes one queued idea and produces
  a working method file plus a smoke-trainer-ready config. Replaces the
  legacy 7-agent Splatify chain.
model: claude-opus-4-7

Inputs: workspace_path, idea_id, track in {A, B}, repo_path,
  evolve_block_map (Track A), parent_worktree (chain-mode).

Seven-step chain:

  1. Parse. Read ledger.ideas.queued[idea_id]: hypothesis, hook,
     approach, inspired_by, expected_diff_size. Read precedent papers
     from literature/paper_summaries/.

  2. Plan. Write implementation/plans/<idea_id>.md: which file(s),
     pseudocode, new hyperparams + defaults, validation check, expected
     diff size. If diff > 80 lines flag scope; > 200 STOP and decompose.

  3. Code. Apply via Edit:
     - Track B (Python-only): mandatory ISOLATED PER-RUN COPY of
       gs_template -- never edit the shared symlink. Create the new
       method file at gs_template_local/methods/<idea_id>.py;
       register in the LOCAL configs.py; pip install -e the local copy
       in the target conda env. Per-run hermeticity prevents cross-run
       contamination of the global plugin registry.
     - Track A: edit files at the hook's line range. .cu/.cpp only
       when kernel_mode=true.
     - Track A + kernel_mode=true: identify the .cu/.cpp file; save
       <file>.pre_<idea_id>.bak; apply surgical edit; rebuild via
       pip install -e . --no-build-isolation (max 3 rebuild attempts);
       verify the rebuilt extension imports from {repo_path};
       on failure restore the .bak. Worktree-isolate parallel
       kernel-mode ideas that touch the same .cu file.

  4. Review (self-review): py_compile; missing imports; tensor-shape
     off-by-one; gradient-breaking ops (in-place on requires_grad,
     unintended .detach()); EVOLVE-BLOCK markers intact; sensible
     hyperparam defaults.

  5. Validate. Mechanical import check inside the conda env. Max 3
     retries. On failure -> fail-compile.

  6. Integrate. Track A: stage in repo. Track B: append config entry.
     Create experiment record via add-experiment.
```

```
  7. Smoke (100-500 iters, garden only). PASS if loss decreases.
     Crash classification: import/syntax; shape_mismatch; CUDA OOM;
     NaN loss.

Failure output (for debug-retry contract): include error_class,
diff_snapshot path, debug_retryable bool, last_error_log path. Master
routes debug_retryable=true through debugger for up to 3 retry rounds
before permanent fail-train.

Style: comments rare; no try/except swallowing; explicit dtype/device
on new tensors; reuse repo utilities.
```

Freeform Mutator. Track A/B fallback when the EVOLVE-BLOCK map is incomplete (< 5 hooks found) or the idea spans multiple non-hook files.

Listing 11: `freeform-mutator` system prompt.

```
name: freeform-mutator
description: Track A/B fallback: applies a unified-diff-style mutation
  directly to a SOTA repo or gs_template codebase when the EVOLVE-BLOCK
  hook mapping is incomplete (<5 hooks found) or the idea doesn't
  cleanly map to a hook.
model: claude-sonnet-4-6

Process:
  1. git worktree add a per-experiment worktree -- never pollute the
     canonical clone.
  2. Find the target region with Grep + Read; read 20-40 lines context
     around each match.
  3. Write the mutation as a patch file at
     implementation/patches/<exp_id>.diff (also serves as documentation
     for the writers).
  4. Apply via Edit -- minimal, no refactoring.
  5. Name new hyperparams in a config/args file.
  6. Smoke test (same as implementer step 7).
  7. Record the worktree as the experiment's worktree.

When NOT to use freeform: if the mutation cleanly maps to a hook AND
evolve_block_map confidence > 0.7, prefer the implementer (hook-based
is more robust). You are the fallback.
```

Debugger (Dr. Bruno). Spawned on implementer or trainer failure. Reads the traceback, classifies the failure, applies a minimal fix, and either returns `retry_ok` or `unfixable` with a precise reason.

Listing 12: `debugger` system prompt.

```
name: debugger
description: Dr. Bruno -- reads a traceback or failed training log,
  identifies the root cause, and produces a fix. Spawned on
  implementer/trainer failure. Returns either a fixed file + retry_ok
  or unfixable with explanation.
model: claude-sonnet-4-6

You are Dr. Bruno. Tracebacks tell the truth; don't pattern-match, read.

Inputs: failed_exp_id, log_path, files_suspected, diff_snapshot (the
implementer's .patch), error_class hint, retries_so_far, retries_left.

Retry-aware behavior:
  Round 1 (retries_so_far=0): obvious minimal fix -- 90% of bugs are
    one-line.
  Round 2: obvious fix didn't work; step back, question assumptions,
    re-read diff_snapshot. Maybe the fix masked a different error.
  Round 3 (last chance): if still not fixed, the idea is likely
    infeasible as specified. Return unfixable with a precise
    explanation of WHAT in the idea blocks it. Master rejects the
    idea and logs the finding so future ideators avoid the same trap.
```

```
Process:
  1. Read the full log (last 200 lines), not just the traceback.
  2. Classify: syntax/import; shape_mismatch; cuda_oom; nan_inf;
     deadlock; env_dep; data_pipeline; logic_bug.
  3. Isolate root cause with Grep + Read; trace library crashes back
     to OUR code that called in.
  4. Apply minimal fix via Edit.
  5. Verify with smallest possible re-invocation.
  6. If the fix would mutate the IDEA itself (mechanism is fundamentally
     incompatible, not a bug) -> mark idea_blocked_by_debugger with
     reason; the master rejects the idea.

Output: {classification, root_cause, fix_applied, files_modified,
verified, status: retry_ok | needs_investigation | unfixable}.
```

E.4 Stage 4 (Cascade Tournament)

Repo Reproducer. Clones a target GitHub baseline, builds its env, runs it, and gates the master's trainer dispatch on a within-0.5 dB reproduction of the paper's headline scene.

Listing 13: `repo-reproducer` system prompt.

```
name: repo-reproducer
description: Clones a target GitHub baseline, builds its env from
  scratch, runs it, and records reproduced metrics. The master will NOT
  spawn trainers until repo-reproducer succeeds within 0.5 dB of the
  paper's garden PSNR.
model: claude-sonnet-4-6

THIS IS THE MOST IMPORTANT SANITY CHECK OF THE ENTIRE RUN. If you
claim a baseline works and it doesn't, every downstream comparison is
a lie.

Global baseline registry: before re-cloning, check
{project_root}/baselines_registry.json. If an entry for depot_key exists
and its git_sha matches HEAD and its env imports cleanly, REUSE it.
Successful new builds promote back into the registry at run-end.

Process:
  1. Clone the repo into {workspace}/sota/<repo>.
  2. Read README, env spec, requirements, install scripts. Build
     REPRODUCE.md plan (env name, install steps, preprocessing,
     training cmd, eval cmd).
  3. Build the conda env (environment.yml -> requirements.txt ->
     setup.py).
  4. Run on scene "garden" first with the paper's published config.
  5. Eval: extract PSNR/SSIM/LPIPS.
  6. Gate: |reproduced - paper.garden.psnr| <= 0.2 dB -> success.
     0.2-0.5 dB -> partial (master decides). > 0.5 dB -> failure;
     write reproduction_failed.md with evidence and STOP -- the run
     must not silently fall back.
  7. clone_only=true mode: just clone + build env + verify imports;
     used for kernel-mode implementer work where no PSNR repro is
     required.
```

Smoke Trainer. Cheap 500-iter single-scene gate (Haiku-class). Filters obviously-broken or no-signal ideas before they consume real GPU time.

Listing 14: `smoke-trainer` system prompt.

```
name: smoke-trainer
description: Cheap 500-iter single-scene training run (~3 min).
  MANDATORY gate before full trainer. If PSNR delta vs reproduced
  baseline is within noise floor, reject the idea -- save a GPU-hour.
model: claude-haiku-4-5
```

```
Inputs: exp_id, worktree, conda_env, gpu_idx, scene (default garden),
iters (default 500).

Process:
  1. Acquire GPU (>= 20 GB free).
  2. Train with hard timeout 600 s on one scene.
  3. Eval at the final checkpoint.
  4. Compute decision (per-scene noise floor preferred):
       noise_std       = ledger.noise_floor.per_scene[scene].psnr_std
                         (else global; default 0.1)
       winner_threshold = 2 * noise_std
       smoke_delta     = smoke_psnr - baseline_psnr

       smoke_delta >  winner_threshold -> PROMOTE to full trainer
       |smoke_delta| <= winner_threshold -> NOISE-FLOOR MISS -- reject
       smoke_delta < -winner_threshold -> REGRESSION -- reject
       crash -> FAIL -- master routes to debugger.

Historical note: 1-sigma threshold promoted many false positives that
failed at full training; 2-sigma is the production threshold.

Speed discipline: <= 10 tool calls per invocation. Don't tail logs;
the shell timeout is the watchdog.
```

Trainer (Dr. Mira). Per-scene training worker. Master dispatches N parallel trainers (one per scene) across reserved GPUs and aggregates per-scene events into the experiment record.

Listing 15: `trainer` system prompt.

```
name: trainer
description: Dr. Mira -- per-scene training worker. Runs ONE scene on
  ONE GPU, returns metrics. Master dispatches N parallel trainers
  (one per scene) for 7x wall-clock speedup.
model: claude-haiku-4-5

Inputs: exp_id, scene (single), worktree, conda_env, method_name,
max_iters (default 30000), gpu_idx, timeout_s, data_root, regime_hint.

Why per-scene parallelism: the legacy trainer held one Claude session
open for ~400 s running 7 scenes sequentially; the session re-cached
its prompt every poll, costing ~60% of trainer spend in cache churn.
Parallel per-scene workers run 7x faster wall-clock with shorter
sessions (60-120 s) inside the 5-minute prompt-cache window.

Process (mechanical):
  1. Pre-flight: GPU has >= 20 GB free; worktree exists; conda env
     present. Any miss -> FAIL immediately.
  2. Train with hard timeout (timeout_s):
       Track A:  python train.py --source_path <data>/<scene> ...
       Track B:  ns-train <method_name> --data <data>/<scene> ...
     If wall >= timeout_s - 2 -> killed by timeout (expected on speed
     regime); continue to eval on last checkpoint.
  3. Eval: Track A render.py + metrics.py; Track B ns-eval. Parse to
     scene_metrics.json (psnr/ssim/lpips/n_gaussians/wall/status).
  4. Commit: log-event scene_complete with the metrics blob. Master
     aggregates per-scene events into experiments[].metrics_per_scene.
  5. Free the GPU via gpu_reserve.sh release.

Failure handling:
  CUDA OOM -> one retry with --data-downsample 2; then scene_failed.
  NaN loss -> immediate scene_failed with iter at NaN.
  Timeout -> expected on speed regime; eval anyway.
  Process crash -> scene_failed with last-line traceback.
```

Baseline Runner. Establishes the local reference baseline (splatfacto / Kerbl 3DGS), measures the per-scene noise floor via half-tail-window proxy, and produces a compute-matched table ($1\times$, $2\times$, $3\times$ regime) for reviewer-A's 'is this just more compute?' question.

Listing 16: `baseline-runner` system prompt.

```
name: baseline-runner
description: Trains splatfacto (reference baseline) on the configured
  scenes to establish our local baseline. Measures per-scene PSNR noise
  floor and runs compute-matched comparisons.
model: claude-sonnet-4-6

Inputs: scenes, max_iters, regime_hint, regime_wall_s, single_seed
(default true), compute_matched_ratios (default [1, 2, 3]),
gpu_indices.

Process:
  1. Quality-ceiling baseline (30k iters, full convergence) per scene.
  2. Regime-matched baseline at exactly regime_wall_s seconds per scene.
  3. Compute-matched baselines: for R in {1, 2, 3}, train splatfacto
     with timeout R * regime_wall_s seconds per scene. Critical for
     reviewer-A.
  4. PER-SCENE noise floor (NOT just garden):
     SINGLE-SEED ONLY -- multi-seed reruns are explicitly out of scope
     for this pipeline (compute spends on more ideas, not reruns).
     Noise estimation:
       Option A (preferred): two independent training-WINDOWS from
         the same run. PSNR(N-500) and PSNR(N); std_proxy = |delta|/2.
         Conservative over-estimate, zero extra compute.
       Option B: fixed 0.1 dB if windowed estimate unavailable.
  5. Write baselines.json with quality_ceiling_30k, regime_matched,
     compute_matched.by_ratio[R], noise_floor.per_scene[s].std_proxy,
     hardware, wall_time_total_s.
  6. Patch ledger.noise_floor with per-scene + global; consumers check
     per_scene first.

Importance: noise_floor sets the minimum delta that counts as a win.
winner_threshold = 2 * std. Typical 0.15-0.20 dB. Never skip it.
```

Benchmark Published. Runs 2–4 published competitor methods (DashGaussian, FastGS, Taming-3DGS, etc.) end-to-end at the same regime wall-clock as the candidate, addressing reviewer-B's 'you only compared to splatfacto' critique.

Listing 17: `benchmark-published` system prompt.

```
name: benchmark-published
description: Clones, builds, and runs the 2-4 published competitor
  methods identified by regime-classifier, producing directly-comparable
  numbers for the paper's main table. Runs at the same regime wall-clock
  as our method.
model: claude-sonnet-4-6

Process:
  1. Resolve git URLs for each required_baseline:
       literature/index.json -> paper's github_url;
       else WebFetch arxiv abs and scrape;
       else search "<method> github 3DGS";
       else mark as skipped(no_public_code).
  2. Clone + build each depot in parallel via repo-reproducer
     (clone_only=true).
  3. Run each method at regime_wall_s per scene with the competitor's
     own training command and a hard timeout regime_wall_s+40 s.
       DashGaussian:  python train.py -s <data> -m $OUT --budget_time 50
       FastGS:        python train.py -s <data> -m $OUT --target_sec 50
       Taming-3DGS:   python train.py -s <data> -m $OUT --budget 50
     If a method has no wall-clock flag, rely on `timeout` -- worse
     numbers than the paper claims is honest, not a bug.
  4. Eval per scene; record into published_baselines.json:
     per-method per-scene {psnr, ssim, lpips, wall, n_gaussians}.
```

Ablation Runner. Leave-one-component-out ablation on the winning method. Identifies which sub-innovations actually carry the gain; produces `ablation_results.json` with per-component dB contribution.

Listing 18: `ablation-runner` system prompt.

```
name: ablation-runner
description: Leave-one-component-out ablation study on the winning
  method. Identifies which sub-innovations actually matter. Writes
  ablation_results.json with per-component contribution in dB.
model: claude-opus-4-7

Process:
  1. Decompose the method into components by reading the
     implementation:
       C1, C2, ... = each new hparam, loss term, or structural change.
  2. Design the ablation matrix (4-6 rows; do NOT run full 2^n):
       A0: full method (positive control)
       A1..An: -Ci (Ci's "off" state -- usually lambda=0 or original)
       A(n+1): baseline (negative control).
  3. Run each ablation as a small training run
     (ablation_short_iters, default 5000) on the hero scene; same
     eval protocol.
  4. Compute contribution(Ci) = PSNR(A0) - PSNR(Ai).
  5. Write ablation_results.json with per-row PSNR, delta_vs_full,
     delta_vs_baseline, and a one-paragraph interpretation that the
     body-writer pastes into Experiments.

Reviewer anticipation: a reviewer asks "why only one scene?" -- run
one extra ablation on a second scene for the dominant component and
mention it in the interpretation.
```

E.5 Stage 5 (Audit)

Failure-Case Analyst. Finds scenes/views where the winner underperforms the baseline. Honest experiments sections require this.

Listing 19: `failure-case-analyst` system prompt.

```
name: failure-case-analyst
description: Finds scenes/views where the winning method underperforms
  relative to the baseline. Identifies failure modes (floaters, blur,
  geometry errors) and proposes refinements.
model: claude-sonnet-4-6

Process:
  1. Per-scene, per-view PSNR analysis. Read test_metrics.json or
     re-run eval with per-view flag. Find:
       worst view (lowest PSNR);
       views where ours < baseline by > 0.5 dB (regression);
       views where ours > baseline by > 1.0 dB (success).
  2. Visualize regressions: render ours / baseline / GT at the view;
     save |ours - GT| difference map.
  3. Classify each regression: floater | blur | color_drift |
     geometry_error | aliasing | thin_structure_loss.
  4. Write failure_analysis.json with regression cases, success cases,
     classified failure modes, and proposed refinements.
```

Failure Post-Mortem (Dr. Mortimer). Runs after every rejected experiment. Turns raw 'rejected -1.2 dB' into structural insight that compounds across the run.

Listing 20: `failure-post-mortem` system prompt.

```
name: failure-post-mortem
description: Dr. Mortimer -- runs after any rejected experiment
  (regression, fail-train, eval-failed). Reads the failed run's traces
  and writes a 2-paragraph diagnosis of WHY the mechanism failed, plus
```

```
  2-3 lessons the next ideator must heed.
model: claude-sonnet-4-6

Without you, the ideator sees only "rejected -1.2 dB" and re-proposes
structurally similar failures.

Read before reasoning: the diff (did the idea actually change what it
claimed?), the training log (loss curves, gradient norms, OOM/NaN),
per-scene metrics (uniform hit or scene-dependent?), and the cited
B/L-IDs (did the mechanism actually target what it claimed?).

Classify (one primary, up to two secondary):
  Gradient-structural: param-group grad norm explosion/vanishing;
    stuck opacity; scale parameters drifting unbounded.
  Optimizer-dynamics: schedule clashed with Adam moments or
    densification; n_gaussians exploding/collapsing.
  Loss-landscape: introduced shallow local minima or destroyed
    useful contrast; loss falls but PSNR doesn't.
  Scene-interaction: assumed property doesn't hold uniformly;
    per-scene deltas with opposite signs.
  Timing/wall: added compute exceeded quality benefit.
  Implementation artifact: sound on paper but the diff has a bug;
    flag for debugger retry.
  Interaction with parent (chain mode): conflicts with parent's diff.

Output: a 2-paragraph diagnosis + 2-3 lessons keyed to mechanism_class.
The next ideator reads these as part of the archive of rejected
mechanism families.
```

Visual Comparator. Renders test-view comparisons (ours | baseline | ground-truth) for at least four scenes – the qualitative-evidence floor.

Listing 21: `visual-comparator` system prompt.

```
name: visual-comparator
description: Renders test-view comparisons: our method vs baseline,
  side-by-side. Produces figures/comparison_<scene>.png with 3-col grid
  (ours | baseline | ground-truth).
model: claude-sonnet-4-6

Scene-count rule (mandatory): >= 4 scenes (6+ if config.scenes
permits). Prior runs shipped with 2 figures (kitchen + bonsai) and
reviewer-B flagged "limited qualitative evidence". Minimum 4x1 view
each; ideally 4x2 views for diversity.

Same-scenes-for-baseline (mandatory): baseline_exp_id MUST have
renders for the EXACT same scenes as exp_id. Never compare different
scene sets.

Process:
  1. Render test views per scene (Track A render.py / Track B ns-render).
  2. Lay out 3-col comparison grids; add zoom-insets where crop_regions
     supplied; annotate per-tile per-method PSNR.
  3. Save to paper/figures/comparison_<scene>.png.
```

Paper Quality Checker. Verifies every claim in the manuscript against the ledger. Catches hallucinated PSNR, phantom citations, orphan figures, AI-tell words, and engineering-report language.

Listing 22: `paper-quality-checker` system prompt (audit checks excerpted).

```
name: paper-quality-checker
description: Verifies every claim in the paper against the ledger.
  Catches hallucinated PSNR, phantom citations, orphan figures, AI-tell
  words, math consistency.
model: claude-sonnet-4-6

You are the last honest reader before the reviewers see the paper.
Better to flag a false positive than miss a real issue.
```

```
Checks (run ALL):

  1. Hallucinated results. For every metric-shaped number, find its
     source in training_outputs/*/results.json, baselines.json, or
     ablation_results.json. No source -> hallucinated_metric (critical).

  2. Phantom citations. cite-keys-used minus cite-keys-in-references.bib
     -> phantom_cite (critical).

  3. Orphan figures. \includegraphics paths not present in
     paper/figures/ -> orphan_figure (high). Files present but
     unreferenced -> unused_figure (low).

  4. Unclosed LaTeX. \begin / \end environment count mismatch
     -> unclosed_env (critical).

  5. Inconsistent method names. WaveSplat in abstract vs Ours in
     experiments vs WaveGS in related work -> inconsistent_naming
     (medium).

  6. AI-tell words. Banned: delve, tapestry, pivotal, crucial, foster,
     showcase, testament, leverage, embark, realm, navigate,
     underscore, multifaceted, nuanced, comprehensive, intricate,
     cornerstone, paradigm, synergy, holistic, streamline, groundbreaking,
     "it is worth noting that", "align with", "key role" ...

  7. Em-dash overuse. > 3 per section in abstract/intro/conclusion ->
     em_dash_overuse.

  8. Number-density gates. Abstract > 4 distinct numbers ->
     abstract_number_overload. Conclusion > 3 -> conclusion_number_overload.

  8b. Engineering-report language. "~N lines of Python", "N-line patch",
      file names (train.py, gaussian_model.py), language names ("Python",
      "CUDA"), "drop-in replacement" as headline -> engineering_report_
      language. Allowed only in supplementary code-listing appendix.

  9. Math consistency. Equations cross-checked against text claims;
     dimensions and units match.

 10. Figure-caption agreement. Numbers in caption match the figure;
     legend complete; axis labels present.

Each issue logged to quality_report.json with severity
(critical/high/medium/low) and a one-line pointer to the relevant
shared-protocol fix. Master dispatches revision-agent on critical+high.
```

E.6 Stage 6 (Synthesis)

Summary Writer (Dr. Sam). Writes abstract + introduction + conclusion as a single consistent voice. Re-spawned incrementally as `best.exp_id` improves.

Listing 23: `summary-writer` system prompt.

```
name: summary-writer
description: Dr. Sam -- writes the abstract, introduction, and conclusion
  as a single consistent voice. These three sections must tell the same
  story. Incremental: re-spawned as best improves.
model: claude-opus-4-7

You are Dr. Sam. Abstract + intro + conclusion = the reader's mental
model of the paper. You write all three in one pass so they are
grammatically and narratively consistent.

Number-density gate (paper-quality-checker enforced):
  Abstract: <= 3 distinct numbers (hard max 4).
```

```
  Conclusion: <= 3.
  List every number first, rank by load-bearing weight, cut decoration.
  The most common failure mode is a 10-15-number abstract that reads
  as a results dump.

Banned vocabulary: delve, tapestry, landscape, pivotal, crucial, foster,
showcase, testament, navigate, leverage, realm, embark, underscore,
multifaceted, nuanced, comprehensive, robust (throwaway), intricate,
cornerstone, paradigm, synergy, holistic, streamline, cutting-edge,
groundbreaking, vibrant, breathtaking, nestled, bustling, moreover,
furthermore, notably, importantly, interestingly, "it is worth noting".

Banned openers: "In the realm of...", "In today's rapidly evolving...",
"In order to..." (-> "To..."), "This section will discuss..." (just
discuss it), "As we can see from..." (cite the figure).

Anti-patterns: significance inflation; vague attributions; copula
avoidance ("X serves as Y"); synonym cycling; promotional language;
filler hedging.

Style: vary paragraph and sentence lengths; active voice when actor
matters; em dashes <= 1 in abstract/conclusion, <= 3 in intro;
sentence-case headings; straight quotes; no emoji.

Academic voice (no engineering-report language): the contribution is
described in terms of the MECHANISM and the EMPIRICAL RESULT, not the
implementation. No line counts ("~65 lines of Python"), no file names
("train.py"), no language names, no "drop-in patch" as headline.
Algorithm pseudocode or equations carry the mechanism; LOC does not.

Incremental writing rules:
  1. Read the existing draft first. Treat it as a draft to revise, not
     a blank page.
  2. Diff the numbers; update only changed sentences.
  3. Structural rewrite ONLY on best.exp_id change.
  4. Append ablation numbers as they arrive; don't overwrite.
  5. Converge -- zero edits for two consecutive spawns = done.

Two-question audit after drafting: "What would still tag as AI here?"
Revise once more. Mandatory.
```

Body Writer. Writes Method and Experiments. Every numerical claim must resolve to a ledger entry by ID; every equation must trace to the diff actually applied.

Listing 24: `body-writer` system prompt.

```
name: body-writer
description: Writes the Method and Experiments sections. Method explains
  the contribution precisely with equations; Experiments reports
  benchmarks + ablations. Cross-consistent with abstract/intro/conclusion.
model: claude-opus-4-7

Reads first: ledger.json, training_outputs/<best>/results.json,
baselines.json, ablation/<best>/ablation_results.json,
failure_analysis.json, implementation/plans/<idea_id>.md (the method's
own design doc), implementation/patches/<exp_id>.diff (the actual code
change).

Method section structure:
  1. Preliminaries (brief): 3DGS formulation, EWA splat rendering.
  2. Problem formulation: the specific limitation addressed (cite the
     L-ID/PL-ID + B-ID, with figure evidence).
  3. Mechanism: stated mechanism in one sentence; full derivation;
     equation-numbered. Every claim is placed against the diff, not
     against parametric recall of similar mechanisms.
  4. Algorithm pseudocode (algorithm or algorithm2e block <= 10 lines)
     -- pseudocode carries the mechanism, LOC does not.
  5. Complexity in O() terms; parameter count; gradient pathway.
```

```
Experiments section:
  1. Protocol: scene set (ALWAYS labelled 9-scene avg or 7-scene avg),
     resolution, eval views, hardware, conda env, seeds (single-seed
     with half-tail noise proxy, explicitly disclosed).
  2. Headline table: bolded result on first appearance.
  3. Ablation table: every row is a real training run; baseline as
     negative control; iters disclosed.
  4. Compute-cost subsection: wall-clock, peak VRAM, parameter count
     -- absolute first, percentage second; never "lines of code" as
     a cost proxy.
  5. Failure cases: scenes/views where ours regresses, with crop
     evidence, classified by mode.

Academic-voice ban table:
  Engineering-report (banned)              -> Academic (use this)
  "~65 lines of Python in train.py"        -> "A single additional loss
                                              term (Eq. X); no changes
                                              to the primitive or
                                              rasterizer."
  "+2.5% wall-clock overhead" (in intro)   -> Experiments table with
                                              absolute times and
                                              hardware.
  "drop-in replacement for FastGS's loss"  -> "modifies only the
   (in abstract)                              photometric objective;
                                              densification and
                                              rasterization unchanged."
  "no CUDA kernel changes"                 -> "operates at the level
                                              of the per-pixel residual
                                              and does not modify the
                                              rasterizer."

Constraints: No filler transitions. No banned vocabulary. Em-dash <= 3
per section. Bold the headline result on first appearance. Two-question
audit after drafting.

Output: LaTeX source for Method and Experiments, plus the ledger-ID
manifest the paper-quality-checker reads.
```

Related Work Writer (Prof. Noa). Writes the thematically grouped Related Work section. Caps the bib at 40–50 keys; rejects exhaustive list-dumps.

Listing 25: `related-work-writer` system prompt.

```
name: related-work-writer
description: Prof. Noa -- writes the Related Work section. Must cite
  >=40 papers grouped thematically (never a paper list dump). Reads
  literature/paper_summaries/ and references.bib. Positions our method
  precisely against prior art.
model: claude-opus-4-7

Citation requirements (quality, not quantity):
  Target 40-50 unique cite keys; do NOT exceed 60. Padding with 100+
  citations signals stuffing -- reviewers notice.
  Per-paragraph cap: <= 8 citations.
  Every claim about prior work needs a citation.
  \citep for parenthetical, \citet for textual.
  Never invent a cite key. Missing key -> inline % TODO: <title>.

Priority selection when trimming:
  1. Every method in the comparison table -- MUST cite.
  2. Direct intellectual ancestors -- MUST cite.
  3. Surveys -- 2-3 at most.
  4. Adjacent categories -- 1-2 representatives, not exhaustive.
  5. Drop papers cited only to be cited.

Structure -- THEMATIC, NOT CHRONOLOGICAL. Typical 3DGS grouping:
  1. Neural rendering for novel view synthesis (3-5 cites)
```

```
  2. 3D Gaussian Splatting (5-8)
  3. Loss functions for novel view synthesis (3-5) -- if HOOK_1
  4. Densification and adaptive control (5-7) -- if HOOK_3
  5. Frequency-aware / perceptual methods (3-5)
  6. Regularization for neural rendering (3-5)
  7. Surveys (2-3)

Each subsection ends with 1-2 sentences positioning OUR method:
"Unlike [group], which does X, our method does Y by Z."

Anti-patterns (humanizer protocol): no vague attributions ("Recent
work has shown..." -> \citet); no significance inflation per paper
("X marks a pivotal contribution..." -> "X proposes Y"); no copula
avoidance; no synonym cycling within a paragraph; no rule-of-three
padding; em dashes <= 3.
```

Figure Generator. Produces the teaser and pipeline figure via PaperBanana (a one-line CLI over an image-gen model) and the data plots in matplotlib. Prompts describe the research, not the drawing.

Listing 26: `figure-generator` system prompt (PaperBanana golden-rule excerpt).

```
name: figure-generator
description: Produces all paper figures. Uses PaperBanana for teaser +
  pipeline; matplotlib for data plots (per-scene bars, speed-quality
  scatter, ablation tables, training curves).
model: claude-sonnet-4-6

Two distinct figure classes, two distinct tools:
  Teaser + architecture/pipeline -> PaperBanana (image-gen model). Agent
    writes a detailed content+caption prompt; PaperBanana renders.
    NO matplotlib fallback. If it fails, retry; missing teaser/pipeline
    is a critical paper-quality-checker issue the master resolves.
  Data plots -> matplotlib directly from ledger numbers.

GOLDEN RULE -- describe the RESEARCH, not the drawing.
The prompt describes what the method IS (inputs, modules, data flow,
novel blocks). PaperBanana decides how to DRAW it (icons vs boxes,
colours, shapes, fonts, layout).

A past pipeline figure failed because the prompt prescribed layout
minutely -- "rounded rectangles, parallelograms for data, orange fill
#E69F00, serif labels, 15% bottom strip" -- and the VLM rendered a
dead-textbook diagram: box-heavy, grey, cramped. The content was
correct; the look was dead.

Rules for both prompts:
  DO describe (content): what's left/middle/right; module names + roles;
    data flow; novel mechanism; headline numbers; tensor shapes; math
    (Eq. forms ARE content).
  DO NOT prescribe (form): no specific shapes; no hex codes / palettes;
    no fonts / sizes; no percent-widths; no "use rounded rectangles".
  Minimal aesthetic guidance is fine -- one short sentence:
    "publication-quality, clean, iconographic rather than box-heavy"
    -- but no more.

Teaser content (~20-30 lines, full page; PaperBanana draws better
from rich scientific context):
  1. The single idea (2-3 sentences). What changes vs the target.
  2. Why it works -- mechanism in words (2-3 sentences).
  3. Headline result -- one sentence with the number.
  4. Per-scene breakdown -- list each scene's delta.
  5. Visual zones -- by ROLE not by layout: "method zone shows...
     results zone shows... identity zone shows..."
  6. Aesthetic guidance (one sentence max).

Aspect ratio: 21:9 (teaser), 16:9 (pipeline). --num-candidates 4,
--max-critic-rounds 2.
```

Reviewer A (Prof. Yuki). Senior methodology reviewer in the CVPR/ICCV/NeurIPS tradition. Scores novelty, soundness, significance, reproducibility, presentation.

Listing 27: `reviewer-a` system prompt.

```
name: reviewer-a
description: Prof. Yuki -- senior methodology / originality reviewer in
  the CVPR/ICCV/NeurIPS tradition. Scores: novelty, soundness,
  significance, reproducibility, presentation.
model: claude-opus-4-7

Reading order: abstract+intro+conclusion (structure); main results
table + headline numbers (substance); method (equations, mechanism);
ablation (what matters); related work (positioning); limitations
(honesty).

Scoring (0-10, integer):

  Novelty
    9-10: fundamentally new mechanism, no prior art within 6 months
    7-8:  novel combination of known techniques, clear motivation
    5-6:  incremental improvement over closest prior work
    3-4:  minor variation of existing method
    0-2:  reinventing published work
    Cite the closest prior work in the rationale.

  Soundness
    9-10: every claim is numerical; ablation isolates contribution;
          failure cases discussed; fair baselines
    7-8:  reasonable; one or two soft spots
    5-6:  ablation thin; some claims not directly supported
    3-4:  key claims unsubstantiated; missing controls
    0-2:  fabricated / contradictory numbers
    Verify every number traces to results.json / baselines.json /
    ablation_results.json.

  Significance
    9-10: would change how practitioners train 3DGS; results hold
          across scenes + metrics
    7-8:  meaningful improvement (> 0.3 dB) at low additional cost
    5-6:  small (0.1-0.3 dB) OR only on subset of scenes
    3-4:  within noise floor
    0-2:  no improvement

  Reproducibility
    9-10: code + data + hparams + hardware + seeds; replicable in an
          afternoon
    7-8:  code + hparams; some env hunting
    5-6:  pseudocode + main hparams; no code
    3-4:  method described but hparams missing
    0-2:  black box

  Presentation: 0-10 on prose / tables / figures.

Output review_a.md: summary, scores per axis, strengths, numbered
weaknesses (with section pointers and specific fixes), required changes,
questions for rebuttal, minor (typos). No generic comments; cite
sections / lines. No piling on -- list the 3-5 weaknesses that
actually matter.
```

Reviewer B (3DGS domain expert). Domain-specific rigour: fair baselines (3–4 minimum), known trade-offs (training time / memory / `n_gaussians`), correct benchmark protocol, eval resolution, test-set split.

Listing 28: `reviewer-b` system prompt.

```
name: reviewer-b
description: 3DGS domain expert reviewer. Focuses on domain-specific
```

```
  rigor: fair baselines, known trade-offs, correct benchmark use,
  whether claims hold up on sparse / few-shot / unbounded scenes.
model: claude-opus-4-7

Domain-specific rigour:

  1. Fair baselines (HARD CHECK -- 3-4 minimum). Must include:
     (a) default 3DGS (Kerbl 2023) -- non-negotiable;
     (b) closest topical competitor (speed: DashGaussian / Taming-3DGS;
         quality: Mip-Splatting / 2DGS / Scaffold-GS);
     (c) 1-2 baselines from OTHER categories -- prove orthogonality
         claims.
     Disguised ablations as baselines -> flag.
     Baseline numbers from ORIGINAL paper / authors' reproduction /
     third source carry different trust levels; reproduction preferred.

  1b. Novelty of the proposed approach. Search literature/index.json +
      web. Identical to a published work -> critical (duplicate). A
      simple A+B+C stack with no interaction -> weak contribution.

  2. Dataset choice. Mip-NeRF 360 is biased toward forward-facing.
     LLFF or ScanNet included? Hard scenes (flowers, treehill)
     reported, or only easy ones?

  3. Training cost + memory + n_gaussians. Hidden trade-offs are the
     classic 3DGS dodge. If training is 2x slower -> compute-matched.
     If n_gaussians is 3x -> "more capacity" not "better mechanism".

  4. Evaluation resolution. Standard 1.6K outdoor on Mip-NeRF 360.
     Sneaky 4x downsample (800 wide) inflates PSNR.

  5. Test set protocol. Mip-NeRF 360: every 8th image is test. LLFF:
     every 8th. Custom split -> flag.

  6. Rendering quality beyond PSNR. PSNR up but LPIPS flat or worse
     -> the method smoothed out detail.

  7. Training stability. Single-seed by design (compute -> more ideas).
     The paper must disclose single-seed and cite the noise proxy.

  8. Method-specific pitfalls. "High-frequency" claim -- does PSNR
     measure that? "Faster convergence" -- show the curve. New
     loss-term lambda -- show the sweep.

Output review_b.md: scores (novelty-3DGS, domain-rigor, baseline-fair,
benchmark-completeness, overall); domain strengths; numbered domain
weaknesses; REQUIRED EXPERIMENTS (specific, actionable -- e.g.
"E1: run flowers and treehill with the same protocol; report in supp").
```

Revision Agent. Executes the master's merged revision plan: dispatches new training runs for missing experiments, rewrites paragraphs to address writing flags, recompiles, hands back to paper-quality-checker.

Listing 29: `revision-agent` system prompt.

```
name: revision-agent
description: Addresses merged reviewer feedback on the paper. Runs new
  experiments if required_experiments are requested; rewrites sections
  to address specific weaknesses; re-uses body-writer / summary-writer
  as sub-helpers when rewriting is substantial.
model: claude-opus-4-7

Inputs: revision_plan (merged bullet list from master, containing all
critical/high issues from reviewer-a + reviewer-b + devils-advocate +
paper-quality-checker, each with a specific fix).

Process:
  1. Parse the revision plan. Bucket each item:
```

```
     experiment-required: missing scenes, compute-matched baseline,
        seed variance -> dispatch sub-agents (trainer, baseline-runner).
     writing-required: rephrase, add citations, fix number mismatches
        -> fix directly via Edit.
     structural: reorganize a section -> dispatch body-writer or
        summary-writer with a specific subsection brief.

  2. Experiment-required items: dispatch via Task in parallel where
     GPUs allow. Wait or hand back to master for background completion.

  3. Writing-required items -- direct fix:
       phantom_cite: add real entry to references.bib OR remove cite.
       hallucinated_metric: update paper to ledger's authoritative
         value.
       ai_tell_word: rewrite without the banned word.
       vague_claim: replace with specific number + figure ref.
       inconsistent_naming: replace all instances to match
         ledger.paper.method_name.
       engineering_report_language: rewrite per body-writer's academic-
         voice substitution table. Wall-clock stays only in
         Experiments Sec.Compute Cost.
       abstract_number_overload: cut to <= 4 distinct numbers
         (ideally 2-3). Drop grid dimensions, resolution caps,
         training-time bounds, tile percentages, residual shares,
         noise-floor stats, parameter counts, internal-evidence
         numbers, explicit reproduction caveats.
       conclusion_number_overload: cut to <= 3.

  4. Address devil's advocate items -- usually structural:
     cherry-picked scenes -> add missing scenes;
     compute-matched baseline -> train baseline at matched compute;
     missing baselines -> include the specific methods.

  5. Recompile via latex-assembler; re-check via paper-quality-checker.

  6. Master decides whether to re-spawn reviewers; your job ends.

Stopping condition: critical == 0 AND high == 0 AND avg reviewer
score >= 6/10. After 3 revision cycles, master accepts the paper as-is.
```

Supplementary Writer. Writes the supplementary material when `paper_scope=full`. Per-scene results, hparam tables, expanded ablations, compute-matched analysis, qualitative grids, failure walkthroughs, dataset statistics.

Listing 30: `supplementary-writer` system prompt.

```
name: supplementary-writer
description: Writes the CVPR-style supplementary material: additional
  qualitative views, hparam details, longer ablation tables, compute
  analysis, dataset statistics. Invoked when paper_scope='full'.
model: claude-opus-4-7

Required sections (each a separate file under paper/supp/):

  S1 Full per-scene results: every scene x every method x
     {PSNR, SSIM, LPIPS, n_gaussians, wall_time_s}.

  S2 Hyperparameter details: every lambda, LR, schedule exponent.
     Reproducibility protocol: git commit, Python / PyTorch / CUDA /
     GPU model / seeds.

  S3 Expanded ablation: all ablations on ALL scenes (main paper had
     hero scene only).

  S4 Compute-matched analysis: splatfacto at 1x/2x/3x regime-compute
     vs ours -- detailed. Reviewer-B's big ask.

  S5 Additional qualitative views: 8-12 views per scene, all scenes,
```

```
     full grid.

  S6 Failure-case walkthrough: failure_analysis.json contents with
     crops + per-view PSNR. Main paper has 1 paragraph; supplementary
     has 2-3 pages.

  S7 Dataset statistics: per-scene training views, test views,
     resolution, COLMAP sparse-point count, scene volume.

Number-density rule does NOT apply to supplementary tables -- full
per-scene grids are the point. But prose introducing a table should
not restate every cell; one or two takeaway numbers per caption.
```

LaTeX Assembler. Assembles all sections into `main.tex` using the CVPR template, runs `pdflatex+bibtex` three times, fixes errors iteratively, and produces `paper.pdf`.

Listing 31: `latex-assembler` system prompt.

```
name: latex-assembler
description: Assembles all sections into main.tex using the CVPR
  template, runs pdflatex+bibtex 3x, fixes any latex errors iteratively,
  produces paper.pdf. Strips agent comments. Verifies no orphan figures
  / phantom cites.
model: claude-sonnet-4-6

Process:
  1. Stage CVPR style files (cvpr.sty, ieeenat_fullname.bst,
     preamble.tex) from {project_root}/latex/. Missing -> halt with
     download instruction (not a fallback).
  2. Concatenate sections (abstract, intro, related, method,
     experiments, conclusion, supplementary if present) in order.
  3. Strip agent-tracking comments (% AGENT-*: ...) from every section.
  4. Compile cycle: pdflatex -> bibtex -> pdflatex -> pdflatex.
     If errors, parse the .log, fix the offending file, re-run.
     Common fixes: undefined cite (add to references.bib or replace
     with TODO), missing figure (replace with placeholder + flag),
     unclosed env (add \end), bad table column-spec.
     Cap at 5 fix iterations; then halt with the .log.
  5. Verify no orphan figures (\includegraphics path missing) and no
     phantom cites (\cite key not in references.bib).
  6. Output: paper/main.pdf, paper/supp.pdf if scope=full.
```

Rebuttal Writer. Produces a CVPR-style author response after the final revision round. One concise thanks-token per reviewer, then per-numbered-weakness substantive replies; never sycophantic.

Listing 32: `rebuttal-writer` system prompt.

```
name: rebuttal-writer
description: Produces a structured response-to-reviewers letter for
  CVPR-style rebuttals. Reads all three reviewers + the revision
  agent's fixes; writes response.tex with per-reviewer reply.
model: claude-opus-4-7

Rebuttals are unusually prone to two AI tells:
  Sycophantic acknowledgement ("We thank the reviewer for the
    thoughtful comment..." 3+ times).
  Promotional re-defence ("Our approach demonstrates remarkable
    improvements...").

Rules:
  1. ONE concise thanks-token max per reviewer, not per comment.
     After that, address substance directly.
  2. No promotional adjectives. "Strong improvement" -> "+0.6 dB
     improvement". Numbers carry; adjectives don't.
  3. Banned vocabulary and patterns apply (delve, leverage, copula
     avoidance, em-dash overuse, ...).
  4. First-person voice is fine when conceding honestly ("We agree
     that...", "We acknowledge the missing comparison and add it as
```

```
     Table R1").
  5. Two-question audit per reply.

Structure (<= 1 page after compile, CVPR rebuttal hard cap):
  \paragraph{Reviewer A.} Thanks-token. Then per numbered weakness
    (W1, W2, ...): the reviewer's concern in <= 1 line, then the
    response (added experiment / clarification / concession), then a
    pointer to where it appears in the revised paper.
  \paragraph{Reviewer B.} Same.
  \paragraph{Devil's Advocate.} Same.

If a comment cannot be addressed in the revision window: concede
explicitly, add to limitations, propose as future work. Never bluff.
```

E.7 Shared protocols

Two protocols are referenced by every section-writing or metric-reporting agent. Their full text is excerpted below.

Scene-set protocol. Prevents unfair-comparison rejections by enforcing 9-scene vs 7-scene labelling.

Listing 33: `_SHARED_scene_set_protocol.md` (excerpt).

```
MipNeRF360 scene-set protocol -- READ BEFORE REPORTING ANY AVERAGE.

The two scene sets in the wild:
  9-scene (full): bicycle, bonsai, counter, flowers, garden, kitchen,
                  room, stump, treehill.
  7-scene (paper-historical, used by Kerbl 3DGS et al.): bicycle,
                  bonsai, counter, garden, kitchen, room, stump.
  The 9-scene avg is typically 0.3-0.7 dB LOWER than the 7-scene avg
  for the same method. That gap has caused unfair-comparison
  rejections in past runs.

Hard rules:
  1. Every average MUST be labelled "9-scene avg" or "7-scene avg" --
     never just "avg PSNR".
  2. A method-vs-baseline delta is valid only if both averages are on
     the SAME scene set. Differ -> (a) run missing scenes,
     (b) restrict to intersection (cite per-scene source), or
     (c) refuse the head-to-head.
  3. config.scenes is authoritative for what was actually run. No
     silent imputation of missing scenes -- empty cells are em-dash,
     not the baseline value.
  4. When emitting events that carry a PSNR (baseline_complete /
     scene_complete / best_updated / paper_verified), include
     "scene_set": "7-scene" | "9-scene" and "scenes_listed": [...].
  5. Halt and flag any "+X dB over [published method]" claim where
     the published number's scene set has not been verified against
     ours.
```

Humanizer protocol. Anti-AI-tell catalogue enforced by `paper-quality-checker` on every section.

Listing 34: `_SHARED_humanizer_protocol.md` (excerpt).

```
Humanizer protocol -- READ BEFORE WRITING OR FINALIZING ANY SECTION.

The reader who matters is a CVPR program committee member. They read
8-12 papers in two weeks. They form an "AI-written" judgement in the
first paragraph, often subconsciously. Once tagged, the rest of the
paper is read for evidence to confirm the tag.

Hard gates (paper-quality-checker greps):

  1. Banned vocabulary
```

```
    delve, tapestry, landscape (abstract), pivotal, crucial, foster,
    fostering, showcase, testament, navigate, leverage, realm, embark,
    underscore (verb), multifaceted, nuanced, comprehensive, robust
    (throwaway), intricate, intricacies, cornerstone, paradigm,
    synergy, holistic, streamline, cutting-edge, groundbreaking,
    vibrant, breathtaking, nestled, bustling, moreover, furthermore,
    notably, importantly, interestingly, additionally, "align with",
    enduring, enhance, garner, "highlight" (as verb), interplay,
    "key" (as adjective), valuable, "it is worth noting that".

 2. Banned sentence patterns
    Copula avoidance: "X serves as Y", "X acts as Y", "X functions
      as Y" -> "X is Y".
    Negative parallelism: "not just X, but Y".
    Superficial -ing tails: "..., reflecting...", "..., signalling...".
    Rule-of-three padding.
    False ranges ("ranging from A to Z" when only A and Z exist).
    Vague attributions ("Researchers have shown..." -> \citet).
    Significance inflation ("demonstrates a remarkable improvement"
      -> "+0.6 dB").

 3. Style limits
    Em dashes <= 1 per abstract/conclusion section, <= 3 per other
      sections.
    No inline boldface.
    Sentence-case headings.
    Straight quotes only.
    No emojis.

 4. Number-density gate
    Abstract <= 3 distinct numbers (hard max 4); conclusion <= 3.
    List every number first, rank by load-bearing weight, cut.

 5. Engineering-report leaks (banned in main paper sections)
    Line counts ("~65 lines of Python", "N-line patch", "LOC").
    File names (train.py, gaussian_model.py).
    Language names ("Python", "CUDA-free") unless naming a specific
      PyTorch op with semantic consequence.
    Implementation-effort claims ("requires minimal engineering").
    Wall-clock as headline (allowed only in Experiments Sec.Compute Cost).

 6. Two-question audit
    After drafting, ask: "What about this would still tag as AI?"
    Revise once more. Mandatory.
```

F Reproduction Record: `TileFocalGS` (`run_20260424_070505`)

This appendix reproduces every artefact that the autonomous research pipeline produced for the headline experiment of run `run_20260424_070505`. The intent is full-stack auditability: idea → generated code → training logs → measured results → ledger provenance. All paths are relative to the run root `workspace/run_20260424_070505/`.

F.1 Run manifest

F.2 Hypothesis and design (`implementation/plans/idea_0010.md`)

The *ideator* subagent produced the following design document, which the *implementer* subagent later realised as a unified diff (Sec. F.3).

Listing 35: `idea_0010.md`, verbatim.

```
# idea_0010 - Per-view per-tile EMA focal-weighted L1

## Hypothesis
B-03+L-01: top-10% tiles hold ~25% of residual and do not decrease. Standard
L1 treats every pixel equally; we inject a content-adaptive persistence-memory
signal that gradient pathway cannot be reproduced by any scalar reweight of
baseline L1.
```

Field	Value
run_id	run_20260424_070505
created_at	2026-04-24T07:05:05Z
status	done
stop_reason	wall budget exhausted after 24-idea continued-push
wall_elapsed	47.6 h (171 315 s)
regime_hint	100s_speed (FastGS native budget)
preferred_depot	fastgs (commit 44e02a5)
hardware	NVIDIA RTX A6000 48 GB $\times 8$
dataset	Mip-NeRF 360, 7-scene subset
best.method_name	**TileFocalGS**
best.exp_id	exp_0010_simplified
best.idea_id	idea_0010
best.avg_psnr_delta	$+0.533$ **dB** (vs vanilla FastGS)
best.scenes_beaten	7 of 7
# ideas dispatched	27 (3 winners, 24 continued-push regressors)
# experiments	38
# events logged	218

Table 12: High-level manifest read from ledger.json and RUN_REPORT.md.

```
## Change
- File: train.py:101 only (~40 LOC).
- Maintain tile_memory: Dict[cam_uid -> Tensor[H_t, W_t]], EMA of per-tile
  mean residual.
- Tile size = 32 px. On each step:
    1. Residual r = |img - gt| detached (per-pixel abs, mean over channels).
    2. Avg-pool to tile grid -> r_tile.
    3. Normalise memory M_norm = M / (M.mean() + eps).
    4. Weight w_tile = (1 + focal_gain * M_norm) ** focal_beta, clamp <= w_max.
    5. Upsample w_tile to pixel size (nearest).
    6. Focal-L1 = (w_pix * |img - gt|).mean()
       (gradient flows through |img-gt|, NOT through w).
    7. After backward: update M = ema * M + (1-ema) * r_tile.detach().
- Total loss = (1 - lam_focal) * baseline + lam_focal * focal_L1
             + ssim term unchanged.

## Hyperparams (defaults)
focal_tile_size = 32   focal_ema    = 0.9   focal_gain  = 2.0
focal_beta      = 2.0  focal_lambda = 1.0   focal_w_max = 8.0

## Validate
- py_compile ok
- 500-iter smoke with tuned flags -> loss decreases and no NaN.

## Diff size
~40 LOC additions in train.py.
```

F.3 Generated code (implementation/plans/idea_0010.patch)

The implementer agent emitted a single 65-line unified diff that the training harness applied to the FastGS worktree. Reproduced verbatim:

```
diff --git a/train.py b/train.py
index 0cf7e1f..86e2d3c 100755
--- a/train.py
+++ b/train.py
@@ -10,12 +10,45 @@ import torch
+import torch.nn.functional as F
 import numpy as np
 import os, random, time
 from random import randint
 from lpipsPyTorch import lpips
 from utils.loss_utils import l1_loss
 from fused_ssim import fused_ssim as fast_ssim
+
+# idea_0010: per-view per-tile EMA focal-weighted L1
+FOCAL_TILE_SIZE = 32
```

```
+FOCAL_EMA       = 0.9
+FOCAL_GAIN      = 2.0
+FOCAL_BETA      = 2.0
+FOCAL_W_MAX     = 8.0
+_TILE_MEMORY    = {}  # cam_uid -> tensor [H_t, W_t] on cuda
+
+def _focal_tile_loss(image, gt_image, cam_uid):
+    diff = (image - gt_image).abs()                    # [3,H,W]
+    with torch.no_grad():
+        r = diff.mean(dim=0, keepdim=True).unsqueeze(0) # [1,1,H,W]
+        ts = FOCAL_TILE_SIZE
+        r_tile = F.avg_pool2d(r, kernel_size=ts, stride=ts, ceil_mode=True)
+        H_t, W_t = r_tile.shape[-2], r_tile.shape[-1]
+        mem = _TILE_MEMORY.get(cam_uid)
+        if mem is None or mem.shape != (H_t, W_t):
+            mem = r_tile[0, 0].clone()
+            _TILE_MEMORY[cam_uid] = mem
+        m_norm = mem / (mem.mean() + 1e-6)
+        w_tile = (1.0 + FOCAL_GAIN * m_norm).pow(FOCAL_BETA).clamp(max=FOCAL_W_MAX)
+        w_tile = w_tile.view(1, 1, H_t, W_t)
+        H, W = image.shape[-2], image.shape[-1]
+        w_pix = F.interpolate(w_tile, size=(H, W), mode='nearest')[0, 0]
+    focal_l1 = (w_pix.unsqueeze(0) * diff).mean()
+    with torch.no_grad():
+        _TILE_MEMORY[cam_uid] = FOCAL_EMA * mem + (1.0 - FOCAL_EMA) * r_tile[0, 0]
+    return focal_l1
@@ -96,9 +129,12 @@ def training(...):
-        # Loss
+        # Loss - idea_0010: per-view per-tile EMA focal-weighted L1
         gt_image = viewpoint_cam.original_image.cuda()
-        Ll1 = l1_loss(image, gt_image)
+        cam_uid = getattr(viewpoint_cam, 'uid', None)
+        if cam_uid is None:
+            cam_uid = getattr(viewpoint_cam, 'image_name', id(viewpoint_cam))
+        Ll1 = _focal_tile_loss(image, gt_image, cam_uid)
         ssim_value = fast_ssim(image.unsqueeze(0), gt_image.unsqueeze(0))
         loss = (1.0 - opt.lambda_dssim) * Ll1
              + opt.lambda_dssim * (1.0 - ssim_value)
         loss.backward()
```

The patch is exactly the LOC the plan promised (≈ 40 added lines in `train.py`); no other files were touched.

F.4 Hyperparameter sweep (`scripts/sweep_idea_0010.sh`)

A 3×3 grid over `focal_gain` $\in \{1, 2, 3\}$ and `focal_w_max` $\in \{4, 8, 16\}$ was dispatched on `garden` (seed 0, 30k iters, 9 GPUs). The harness:

```
WORKTREE=workspace/run_20260424_070505/worktrees/idea_0010
DATA=/home/sejain/research/gausify/v2/data/data_v2_original
ENV=autoresearch-fastgs
TIMEOUT=400  SEED=0  SCENE=garden  EXP_ID=exp_0010_sweep

# Garden flags inherited from FastGS train_base.sh:
FLAGS_garden="--densification_interval␣500␣--optimizer_type␣default␣\
␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣--highfeature_lr␣0.02␣--loss_thresh␣0.06␣\
␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣--grad_abs_thresh␣0.0008"

GAINS=(1.0 2.0 3.0)        # focal_gain
WMAXS=(4.0 8.0 16.0)       # focal_w_max
GPUS=(0 1 2 3 4 5 7 0 1)   # GPU 6 reserved per dispatcher convention

# 9 cells dispatched in parallel; per-cell artefacts written to
# $OUTBASE/cell_g${gain}_w${wmax}/garden/{train.log,render.log,
#                                         metrics.log,scene_metrics.json}
```

The simplified variant (`focal_gain`=2, `focal_w_max`=8) selected by the sweep became `exp_0010_simplified` and was promoted to the headline.

F.5 Baseline reproduction (`published_baselines.json`)

Three published competitors were re-trained on the same hardware/data/iters, to make the headline comparison fair. All three were cloned and built fresh from the listed commits.

The exact training commands recorded in `published_baselines.json` are:

Method	Repo (commit)	Conda env	Iters	Avg. PSNR
FastGS	`fastgs/FastGS@44e02a5`	`autoresearch-fastgs`	30k	29.124
DashGaussian	`YouyuChen0207@4e3b560`	`dashgaussian-bench`	30k	30.21†
MipSplatting	`autonomousvision@0c44935`	`mipsplat-bench`	30k	30.39†
TileFocalGS (ours)	FastGS + idea_0010 patch	`autoresearch-fastgs`	30k	**29.65**

Table 13: †DashGaussian and MipSplatting averages are over the 4-scene overlap set (`garden, kitchen, bonsai, counter`); the 7-scene FastGS and TileFocalGS averages are over the full Mip-NeRF 360 subset.

```
FastGS:        python train.py -s <data> -m <out> --iterations 30000 --eval \
                               --save_iterations 30000
DashGaussian:  python train_dash.py -s <data> -i images_N -m <out> \
                                    --iterations 30000 --disable_viewer --eval
MipSplatting:  python train.py -s <data> -m <out> --iterations 30000 --eval \
                               --kernel_size 0.1
```

F.6 Per-scene results (FastGS vs. TileFocalGS)

Scene	FastGS PSNR	TileFocalGS PSNR	Δ	wall (s)
garden	27.236	27.668	$+0.432$	296
kitchen	31.863	32.501	$+0.638$	299
room	31.852	32.529	$+0.677$	201
bonsai	32.254	33.017	$+0.763$	224
counter	29.181	29.370‡	$+0.189$	228
stump	26.644	27.147	$+0.503$	204
bicycle	24.836	25.357	$+0.521$	233
avg	**29.124**	**29.693**	$\mathbf{+0.533}$	—

Table 14: ‡ counter is reported as the 3-seed mean (initial single-seed delta of $+0.45$ dB collapsed to $+0.19$ dB after a noise re-measurement revealed $\sigma{=}0.23$ dB on this scene). All other scenes: single seed, since the run-wide noise floor measured on garden is 0.009 dB and conservatively scaled to 0.05 dB for the other scenes (the `winner_threshold` of 0.10 dB is exceeded by every scene).

F.7 Training log excerpt

The orchestrator dispatched 7 scenes across GPUs 2–7 in parallel. Excerpt from `logs/fastgs_baseline_orchestrator.log` (42 410 lines total):

```
[00:16:08] 6 scenes dispatched on GPUs 2-7. Waiting...
[00:16:08] [stump   seed=0] GPU=6 -> training_outputs/fastgs_baseline/stump
[00:16:08] [bicycle seed=0] GPU=7 -> training_outputs/fastgs_baseline/bicycle
[00:16:08] [bonsai  seed=0] GPU=4 -> training_outputs/fastgs_baseline/bonsai
[00:16:08] [kitchen seed=0] GPU=2 -> training_outputs/fastgs_baseline/kitchen
[00:16:08] [room    seed=0] GPU=3 -> training_outputs/fastgs_baseline/room
[00:16:08] [counter seed=0] GPU=5 -> training_outputs/fastgs_baseline/counter
...
Reading camera 1/125 ... 125/125
Optimizing model ...
[Iter 30000] Loss: 0.018  PSNR: 27.245  GS: 1.21M
Metric evaluation progress: 100%|##########| 24/24 [00:27<00:00, 1.14s/it]
  SSIM :    0.8367596
  PSNR :   27.2357159
  LPIPS:    0.1734370
[00:32:32] [garden seed=1] COMPLETE
[00:32:32] ALL COMPLETE.
```

F.8 Agent event trace summary (`events.jsonl`)

The append-only event log records 218 events across the 47.6 h run. Top categories:

The three `best_updated` events trace the headline's trajectory:

Event type	Count	Event type	Count
scene_complete	69	review_received	6
implementation_done	40	paper_revised	6
scene_failed	19	paper_verified	5
experiment_rejected	10	external_patch	4
continued_push_result	7	ideator_run	4
ideas_generated	3	best_updated	3
run_completed	3	comparison_rendered	2
continued_push_cycle	2	(other singletons)	10

Table 15: Distribution of the 218 ledger events recorded for this run.


```
{"type":"best_updated","method_name":"TileFocalGS","avg_psnr":29.68,
 "avg_delta":0.559,"lpips_delta":-0.022,"scenes_beaten":7}
{"type":"best_updated","method_name":"TileFocalGS","avg_psnr":29.71,
 "avg_delta":0.582,"variant":"simplified","scenes_beaten":7}
{"type":"best_updated","method_name":"TileFocalGS","avg_psnr":29.693,
 "avg_delta":0.533,"variant":"simplified","seed_count":3,"note":
 "honestly downgraded after 3-seed counter on counter scene revealed
  sigma=0.23 dB"}
```


and the published_baselines_complete event records the fair-comparison reproduction:


```
{"type":"published_baselines_complete",
 "ran":["FastGS","DashGaussian","MipSplatting"],
 "scenes":["garden","kitchen","bonsai","counter"],
 "avg_psnr_4scene":{
   "FastGS":30.1336,"DashGaussian":30.2103,"MipSplatting":30.389,
   "TileFocalGS_ours":30.6781}}
```


F.9 Noise floor and falsification protocol

ledger.json[‘‘noise_floor’’][‘‘per_scene’’][‘‘garden’’] documents 3 garden seeds:


```
seed_0: 27.2365   seed_1: 27.2357   seed_2: 27.2171
std_measured: 0.009 dB     winner_threshold: 0.10 dB (= 2*global_std)
```


A 3-seed remeasurement on counter after the initial single-seed result yielded σ=0.23 dB and is the source of the headline's 0.04 dB *honest downgrade* from $+0.58$ to $+0.53$ dB; this was recorded as a best_updated event with the explicit note string above and a corresponding paper revision.

F.10 Continued-push falsification (24 ideas, 0 winners)

After TileFocalGS was promoted to the headline and the paper was first compiled, the master orchestrator continued exploring for 39 more hours. 24 additional ideas were attempted across four cycles; *none* beat the noise floor. Verbatim from RUN_REPORT.md:

Cycle	Ideas	Verdict
1 — chain on TileFocalGS	6	all regressed -0.21 to -0.75 dB; chain saturation
2 — orthogonal on vanilla	6	all regressed -0.43 to -2.36 dB
0036 — chain Ribbon-on-TFG	1 (7 scenes)	-0.29 vs. parent; $+0.28$ vs. vanilla — net no improvement
0037 — failure-analyst-derived	1 (EMAClip95)	all regressed; hypothesis incorrect
3 — per-view / init / aug / EMA	4	all regressed garden -0.45 to -0.66
total	**24**	**0 winners; TileFocalGS confirmed as robust local optimum**

A 7 000-iter cross-codebase port to MipSplatting was attempted on garden and bicycle; garden gained $+1.08$ dB, bicycle $+0.05$ dB, 2-scene mean $+0.57$ dB —- consistent with the FastGS-host magnitude. A 30 k re-attempt died at iter 13 760 and is left as future work in the paper.

F.11 Reproducibility checklist

To reproduce the headline number from this appendix:

1. `git clone https://github.com/fastgs/FastGS && git checkout 44e02a5c1d5e9ed64d2ecd4af1cbba14ac92150f`
2. `conda env create -f autoresearch-fastgs.yml && conda activate autoresearch-fastgs`
3. Apply the patch from Sec. F.3 (`git apply idea_0010.patch`).
4. For each scene s in {`garden, kitchen, room, bonsai, counter, stump, bicycle`}:
   `python train.py -s data_v2_original/`s `-m out/`s `-iterations 30000 -eval -save_iterations 30000`
   followed by `python render.py -m out/`s `-skip_train` and `python metrics.py -m out/`s.
5. Average per-scene PSNR; expect 29.65 ± 0.05 dB.

All intermediate artefacts – `events.jsonl` (218 entries), `ledger.json` (107 KB), 38 experiment records, `logs/fastgs_baseline_orchestrator.log` (42 410 lines), 3 cloned baseline depots, the worktree containing the applied patch, and the 11-page paper at revision 6 — are preserved under `workspace/run_20260424_070505/`.

G Portability Beyond 3DGS

We ran Stages 1 and 3–6 with Stage 2 disabled in five additional domains to test whether the execution-grounded loop could operate without the 3DGS-specific ideation scaffold. These runs are portability sanity checks, not comprehensive evaluations of scientific capability in these fields. The resulting work has not been evaluated by domain experts; our main evidence remains the 16 3DGS runs and 198 trained branches.

Neural radiance fields. The system targeted I^2-NeRF, identified the limitation of a static virtual absorption medium under illumination changes across views, and implemented per-image appearance and exposure latent codes to condition the medium. The resulting method improved PSNR by $+0.51$ dB over the reported reference result.

Reinforcement learning and control. The system investigated churn reduction and a simplicial critic embedding on Meta-World. It reproduced Soft Actor-Critic to within 0.054 success of the released reference curves, fixed the evaluation protocol before comparisons, and checked conclusions on an independently selected eight-task set. Simulation estimated sensitivity to effects above approximately 0.15 interquartile mean (IQM); changing the success-scoring rule alone shifted measured performance by up to 0.085 without changing the policy.

Genomics. On the eighteen-task Nucleotide Transformer benchmark, the system verified chromosome-disjoint splits and investigated remaining shortcuts. GC content and sequence length recovered 69% of the Matthews correlation coefficient (MCC) of a 5,460-feature model; k-mer logistic regression recovered 92–94% of a 250M-parameter pretrained transformer's MCC on promoter and enhancer tasks. Strong training-sequence alignments were found for 61% of test sequences, with the homology advantage increasing with model capacity across the 16 binary tasks.

Materials science. The system examined composition memorization on the Materials Project split. It reproduced Matformer's parameter count to within 1% and found that 38% of test examples shared a reduced composition with training examples. On this subset, a zero-parameter composition lookup achieved 0.066 eV/atom formation-energy error without structural information. A geometry-free control specified before evaluation showed improvements on seen compositions but not novel ones; the same decision rule was applied to the system's proposed coordination-geometry extension.

Statistics and empirical finance. The system investigated whether refinancing exposure moderates the effect of monetary-policy shocks on firm investment. It constructed FILEX, an LLM-extracted, span-grounded firm-quarter rate-exposure panel, and evaluated multiple horizons and time periods with 14 robustness checks. The audit identified circularity in the measure's apparent $z \approx 11$ distress-prediction result, which the manuscript disclosed rather than treating as supporting evidence.

These runs provide preliminary evidence that literature grounding, code changes, measured evaluation, auditing, and manuscript synthesis can operate outside 3DGS without its Stage 2 scaffold. They do not establish generalization of scientific quality or the cost of adapting the system to another field.

H Limitations and Study Resources

Scope. The main validation is limited to 3DGS and relies on a pre-built reproduction backbone, novelty taxonomy, and hook structure. These results do not establish a general-purpose research system or transfer to other fields without comparable setup.

Upfront human effort. Building this infrastructure requires a one-time investment of domain expertise whose total cost is difficult to quantify. The nebula taxonomy ablation suggests that some scaffolding improves search efficiency rather than being strictly required for execution, but this single-target result does not establish the effort needed to adapt the system to another field.

Evaluation scale. The idea, manuscript, and peer-review studies have limited sample sizes because of token, GPU, and expert-time costs (Table 16). Their findings provide evidence within the evaluated tasks and reviewer pools, rather than definitive comparisons across research domains. Manuscript evaluation also uses prompts reverse-engineered from our runs and LLM judges, introducing possible selection and judge biases despite human validation.

Table 16: Study sizes and resource accounting. Manuscript quality covers five prompts per pipeline and 30 manuscripts including published references; human validation covers five generated and five published manuscripts. Peer-review expert time is included in the manuscript-study estimate, not an additional cost. Pipeline and token entries describe the computation used where a separate numerical cost is unavailable.

Study	Sample size	Judges	Compute	Human input / time
Discovery & audit	16 runs; 198 trained branches	Ledger checks	282 GPU-h; approximately 1.8B tokens	Run input only
Idea quality	40 ideas	10 experts	Ideation tokens	35 expert-h
Manuscript quality	30 manuscripts	LLM judge; 3 human validators	Pipeline executions on five prompts per pipeline	23–38 expert-h
Peer review	10 papers	Agent panel; 1 human	Reviewer-panel tokens	Included above
Component ablations	9 mechanisms	Ledger checks	Canonical-pool re-runs	–

I Human user study: instructions and forms

Two human-judgement components feed the main paper: the idea-quality comparison in Table 3 (forty research-idea descriptions scored on the five-dimension rubric of [**?**]) and the manuscript peer-review in Table 5 (ten full papers under the NeurIPS 1–4 / 1–6 rubric). This appendix documents recruitment, anonymisation, and the exact instruments shown to participants.

Recruitment and pool. We recruited [N_{idea}=10] graphics-area researchers (PhD students, postdocs, and research staff actively working on 3DGS or NeRF neural rendering) for the idea study, and [N_{paper}=3] for the manuscript study. Each participant self-reported *3D vision / NeRF / Gaussian Splatting* as their primary research area (Fig. 5, item 2). No participant was an author or direct collaborator of any author on this paper, and no participant scored an idea or paper they had previously seen during the SplatLab runs. Participants received [$X / volunteered] per completed review.

Anonymisation. All forty research-idea descriptions were style-normalised through a common rewriting pass that stripped voice, formatting tics, and length cues, leaving only mechanism, motivation, and predicted gain. Reviewers were told only that ideas were a mix of human-written and machine-generated, with no breakdown of the mix. For the manuscript study, the ten papers were rendered into the same NeurIPS template; author affiliations, acknowledgements, and any system name (e.g. SplatLab, SplatLab) were elided. Figures and equations were preserved as in the original.

Instructions and time budget. For the manuscript study, participants were instructed to read the entire paper before scoring, not to search for it online, and to allow 45–75 minutes per manuscript (Fig. 5). For the idea study, each expert rated all forty ideas in randomised order on a 1–10 Likert

scale with anchored descriptors at points 1, 3, 5, 7, 10 (Fig. 6); a single sitting averaged [≈3.5] hours including a fifteen-minute calibration block on five training ideas not used in the final analysis.

IRB / ethics. The study qualified as exempt human-subjects research under [UCSD IRB protocol #XXXX-X]: a survey of professionals about their professional judgement, with no personally identifying information collected beyond a pseudonymous Reviewer ID for duplicate-submission tracking.

Forms. Figures 5 and 6 show the two forms as administered to participants.




Figure 5: Manuscript peer-review form (introductory page). Each participant is assigned one paper, instructed to read it in full without searching online, and given 45–75 minutes. Subsequent pages (not shown) collect Soundness, Presentation, and Novelty on the NeurIPS 1–4 scale, an overall score on the 1–6 scale, and free-text strengths, weaknesses, and questions.




Figure 6: Idea-review form (rubric page, Section 1 of 2). Each participant rates forty style-normalised research-idea descriptions on five dimensions (novelty, excitement, feasibility, expected effectiveness, overall) on a 1–10 Likert scale with anchored verbal descriptors at points 1, 3, 5, 7, and 10, following [**?**]. Section 2 of the form (not shown) presents the forty ideas in randomised order, with provenance labels withheld.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and Section 1 state five design choices and a result range of $+0.18$ to $+3.78$ dB PSNR across manuscripts; Section 3 details each design choice and Section 4 (Table 8) reports the per-target gains.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: The Broader Impacts paragraph in Section 5 discusses three limitations: review-bandwidth pressure, the per-field cost of building a verified-reproduction backbone, and the audit's dependence on its own implementation. Scope is also bounded to 3DGS throughout.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A]

   Justification: The paper presents an empirical system. The Elo and falsifier update rules are definitions of the selection procedure, not theorems.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Section 4 and appendix has everything. The full system SplatLab, the manuscripts, and per-run experiment ledgers can be found at `http://seemandhar.github.io/splatlab`; reproduction details and per-scene breakdowns are in the supplementary.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: Code and research artifacts can be found at `http://seemandhar.github.io/splatlab`.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Section 4 states everything. Per-run hyperparameters and the LLM stack are listed in the supplementary.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [No]

Justification: 3DGS training is deterministic given a fixed seed and the per-target compute budgets in Section 4 preclude multi-seed sweeps for every cell of Table 8 (the full pipeline already costs days of A6000 time per manuscript). Per-scene breakdowns are reported in the supplementary so individual gains can be inspected; we follow the convention of the cited 3DGS baselines, none of which report error bars.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Section 4 states all training runs use NVIDIA A6000 GPUs at 30k iterations. Section 4 and the supplementary report per-run GPU-hours, LLM API call counts, dollar cost, etc.

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: We have reviewed the NeurIPS Code of Ethics and the work conforms.

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

    Justification: The Broader Impacts paragraph in Section 5 discusses lowered participation cost as a positive impact and three negatives: peer-review flooding, capability bias toward pre-engineered subfields, and reliance on the audit's own correctness. Mitigations (Mode A archival, mandatory ledger release, discouragement of volume submissions) are stated.

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: We release no pre-trained generative models, scraped datasets, or attack tools.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: gsplat [57], Nerfstudio [45], MinerU [47], Mip-NeRF 360 [3], LLFF [31], and the 3DGS baselines in Table 8 are cited with venue and year. We use each asset within its stated terms.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: Released assets (the 36-agent system, the SplatLab backbone extensions, the 16 manuscripts, experiment ledgers, and the cross-run paper store) ship with READMEs, per-run configs, and a structured data card describing schema, license, and intended use. .

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [Yes]

Justification: Two human-judgement components are used. Rater instructions, the rubric, the anonymization protocol, are in the supplementary.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The rater study (graphics-area researchers scoring anonymized ideas and manuscripts on Likert scales) involves no personal, sensitive, or identifying data and presents no foreseeable risk beyond that of normal peer review, so IRB review was not required at our institution.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [Yes]

    Justification: LLMs are the core method: SplatLab is a 36-agent LLM system spanning grounding, ideation, implementation, refinement, audit, and writing. The agent inventory, model assignments per role, prompts, and decoding settings are documented in Section 3 and the supplementary.