VPIXDISTILL: SECURING VISUAL INPUTS AGAINST PROMPT INJECTION VIA EXPLAINABILITY-GUIDED DISTILLATION

Anonymous authors
Paper under double-blind review

ABSTRACT

Large vision-language models (LVLMs) increasingly use visual text as an important source of task evidence across document, web, and physical-world applications. However, this strength also exposes LVLMs to text-form visual prompt injection (VPI), where malicious text in external visual content can bias the model toward an attacker-chosen answer or hijack it into following an attacker-specified instruction. A practical defense requires more than mitigating attacks. It must suppress malicious visual text while preserving the model's visual-text understanding and reasoning abilities. To make this requirement measurable, we introduce SAFEREGIONVPI, a bounding-box (bbox) level benchmark with explicit annotations for both injected text and benign text. SAFEREGIONVPI tests whether a defense distinguishes injected text from benign visual evidence while preserving visual-text understanding beyond a single task-level answer. We further propose VPIXDISTILL, an explainability-guided defense for visual prompt injection in LVLMs. VPIXDISTILL uses the LVLM's internal signals to distinguish injected visual text from benign visual evidence and distills them into a lightweight defense model for efficient inference time protection. We evaluate VPIXDISTILL on SAFEREGIONVPI, representative VPI benchmarks, and case studies on web agent hijacking and aerial tracking prompt injection. VPIXDISTILL reduces attack impact while preserving model utility with low inference overhead.

1 INTRODUCTION

Large vision-language models (LVLMs) are increasingly used in applications that process visual information, reason over multimodal inputs, and interact with digital or physical environments (Koh et al., 2024; Niu et al., 2024; Huang et al., 2024; Xie et al., 2025). In these settings, visual text is not incidental background content. Form fields, warning labels, traffic signs, and UI messages often provide the evidence that determines the model's answer or an agent's next action. However, an attacker can place malicious text in the scene to be processed as task evidence or instruction. Recent studies show that such visual prompt injection (VPI) can mislead LVLMs through typographic overlays and scene-coherent adversarial text, and may lead computer-use or embodied agents to take harmful or unauthorized actions (Cheng et al., 2024; Cao et al., 2025b;a; Burbano et al., 2025).

We focus on two representative forms of task manipulation, illustrated in Fig. 1(a). In typographic adversarial prompt injection, the injected text acts as false visual evidence, causing the model to prefer an attacker-chosen answer over task-relevant visual evidence (Cheng et al., 2024; Cao et al., 2025b; Burbano et al., 2025). In goal-hijacking VPI, the injected text acts as a competing instruction, redirecting the model from the user's benign task to an attacker-specified goal (Lu et al., 2026; Kimura et al., 2024; Ling et al., 2026; Burbano et al., 2025).

Defending against VPI is challenging because removing visual text can also eliminate benign evidence needed for the user's task (Wang et al., 2026; Ye et al., 2025; Liu et al., 2025). Existing defenses offer limited support for distinguishing attack-driving text from legitimate visual evidence. Prompt-based defenses leave the attacked LVLM to decide which text to trust (Cao et al., 2025a). Detection and validation methods can flag suspicious inputs or outputs, but often reject the input or refuse to answer, preventing task completion (Jain et al., 2023; Xu et al., 2024; Wang et al., 2026).

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

White-box defenses probe internal signals but are difficult to deploy with closed-source LVLMs and API-based systems, and do not necessarily identify which visual-text region drives the attack (Lu et al., 2026; Waseda et al., 2025). These limitations motivate a deployable region-level defense that suppresses injected text while preserving benign evidence.

The evaluation methodology for VPI defenses has a similar blind spot. Existing studies mainly report final-answer metrics, such as benign accuracy (BA), task accuracy under attack (TA), and attack success rate (ASR). These metrics are necessary but reflect only whether LVLMs produce the expected answer to a benchmark question. Since many questions use only a fraction of the visual evidence, a defense can maintain strong BA while weakening the model's ability to use other benign visual text. To make this failure mode measurable, we introduce SAFEREGIONVPI, a bbox-level benchmark with annotations for both injected text and benign OCR text. It evaluates benign evidence usage on clean images through general questions requiring information beyond task-specific evidence, measures evidence loss hidden by BA, and supports the evaluation of injected-region localization and benign OCR preservation.



Figure 1: Examples from SAFEREGIONVPI. (a) Typographic (left) and goal-hijacking (right) VPI, with injected text in red boxes. (b) VPIXDISTILL-D masks the injected regions and preserves benign content.

We further propose VPIXDISTILL, an explainability-guided defense for VPI in LVLMs. We first study how attack-driving visual text appears inside LVLMs and formulate four testable signals: (i) whether a region is attended under the user instruction, (ii) whether it conflicts with its local visual context, (iii) whether it deviates from the global image evidence, and (iv) whether masking it restores attention to the user instruction. Our hypothesis tests validate these signals across models and benchmarks. VPIXDISTILL-X uses these signals to identify and suppress injected visual text. We then distill them into a practical defense model, VPIXDISTILL-D, that sanitizes the image before it is passed to the target LVLM (Fig. 1(b)). At inference time, it requires no access to the target model's internals, enabling deployment with black-box commercial LVLMs. In our evaluation, VPIXDISTILL identifies the injected region in up to 96.6% of goal-hijacking VPI on SAFEREGIONVPI while minimally affecting benign visual-text reasoning under region-level utility metrics. VPIXDISTILL-D adds only 10.3% total latency when deployed before GPT-4o. Our contributions are:

- We reveal a blind spot in VPI defense evaluation: task-level metrics can hide losses in benign visual-text reasoning. We introduce SAFEREGIONVPI, a bbox-level benchmark for benign evidence preservation, evidence loss hidden by BA, and injected-region localization.
- We formulate and validate region-level risk signals for VPI, develop VPIXDISTILL-X to suppress injected visual text while preserving benign evidence, and distill this capability into VPIXDISTILL-D for efficient deployment with black-box commercial LVLMs.
- We conduct extensive experiments on typographic and goal-hijacking VPI benchmarks, SAFEREGIONVPI, and web-agent and drone-tracking case studies, including comparisons with nine baselines, hypothesis tests, and ablations.

2 BACKGROUND AND PROBLEM SETUP

2.1 PROBLEM STATEMENT

We consider an LVLM-based system that receives a benign user instruction u and a visual input v, and produces a response or downstream action y. We study indirect visual prompt injection, where untrusted visual content contains adversarial text that corrupts benign task execution. This differs from multimodal jailbreaks that combine visual perturbations with an explicit harmful user request to bypass safety alignment (Qi et al., 2024; Li et al., 2024b). We consider jailbreaks only as a supplementary setting when the harmful request is embedded as visual text and u remains benign.

Threat model. We consider an attacker who can place or modify visual text in digital images, webpages, or physical scenes. The injected text may be task-related or task-agnostic. The attacker may

know the user instruction, visual context, and prompt format, but can only modify the injected visual text. Attacks may be constructed under black-box or stronger white-box assumptions. The defender deploys inference-time protection around the LVLM. Our distilled defense requires no access to the target model's internals at deployment, making it compatible with closed-source LVLMs.

Attacker and defender objectives. An attack is successful if the LVLM's response or downstream action is steered by the injected visual text against the user's intended task. Our security goal is to prevent malicious visual text from steering the model while preserving benign visual evidence needed to complete the task.

Attack scope. We consider two forms of visual prompt injection. *Typographic injection* places misleading text in the visual input so that the LVLM treats it as task evidence, a vulnerability shared by conventional and reasoning-capable LVLMs (Goh et al., 2021; Cheng et al., 2024; Cao et al., 2025b). *Goal-hijacking injection* embeds instruction-like text that redirects the LVLM from the user's task to an attacker-specified one, such as unauthorized actions or information leakage in computer-use agents (Kimura et al., 2024; Cao et al., 2025a; Liao et al., 2025). Both can be realized by direct insertion, as in TypoD (Cheng et al., 2024); by LLM-based planning, as in SceneTAP, which generates task-relevant text and selects a scene-coherent placement (Cao et al., 2025b); or by feedback-guided optimization of prompt content or visual attributes, including in physical-world settings (Li et al., 2025b; Burbano et al., 2025; Ling et al., 2026).

2.2 Defenses against Visual Prompt Injection

Inference-time defenses. Prompt-level defenses ask the model to ignore untrusted visual text, but leave the LVLM itself to decide which text to trust (Cao et al., 2025a; Liao et al., 2025; Lu et al., 2026). CIDER and JailGuard detect attacks through cross-modal inconsistency or response instability under input mutations (Xu et al., 2024; Zhang et al., 2025). However, rejecting the entire input or response can prevent task completion even when benign visual evidence remains available. ARGUS probes internal activations to distinguish user-instruction following from injected-instruction following and steers the model toward the user instruction (Lu et al., 2026). ICON detects over-focusing patterns and applies attention correction (Wang et al., 2026). These methods show that internal signals are informative but require access to target-model internals.

Table 1: Deployment properties of VPI defenses.

Method	Black-box	Task cont.	Region-aware	Low cost
System Prompt	●	●	○	●
JailGuard	●	○	○	○
CIDER	●	○	○	◐
ARGUS	○	●	○	●
RIO-RT	○	●	○	●
VPIXDistill-X	○	●	●	○
VPIXDistill-D	●	●	●	●

● yes; ◐ partial; ○ no. Task cont.: task continuation. Low cost: low inference overhead.

Training-time defenses. SecAlign and Meta SecAlign train text-only LLMs to follow benign instructions rather than injected instructions in untrusted text (Chen et al., 2025a;b); applying them to visual inputs requires adaptation. RIO-Bench studies selective text use under typographic attacks and includes robust training of LVLMs (Waseda et al., 2025). Such training requires target-model access and compute, whereas our defense sanitizes the image without retraining the target LVLM.

Requirements for Practical VPI Defense. A practical defense should support *black-box deployment* without target-model internals and *task continuation* rather than rejecting the entire input. It should provide *region-aware protection* that suppresses injected text while preserving benign evidence, with *low inference overhead* to limit latency and cost. Table 1 compares these requirements.

3 SafeRegionVPI

Existing VPI evaluations mainly report ASR, TA, and BA (Cao et al., 2025a;b). These metrics measure final task outcomes and can hide losses in benign visual-text reasoning: a defense may preserve the answer to the source question while suppressing the model's use of other benign text in the image. This is the visual analogue of over-defense in text-only prompt injection, where benign inputs are falsely flagged (Li et al., 2025a); here, benign OCR regions are falsely flagged or suppressed. RIO-Bench (Waseda et al., 2025) examines whether LVLMs should read or ignore visual text, but scores task-specific answers rather than region-level evidence preservation. We introduce SafeRegionVPI to evaluate whether defenses preserve benign visual evidence beyond the original task and, for region-aware defenses, whether they discriminate injected from benign text.

Benchmark construction. We construct SAFEREGIONVPI from text-rich subsets of TextVQA (Singh et al., 2019), DocVQA (Mathew et al., 2021), and DriveQA-V Traffic Sign (Wei et al., 2025). Each sample includes clean and attacked images, the original question and ground-truth answers, a diagnostic general question, and bbox annotations for benign OCR text and the injection. We generate typographic and goal-hijacking VPI without overlapping benign OCR regions and retain attack-effective samples using target matching over a three-model VLM panel (Appendix A.1).

Clean-image protocols. We evaluate each defense and a No Defense reference using two separate protocols on the same clean images. **Protocol A** asks the model to answer a diagnostic general question, such as describing a document and its text, and report the IDs of the numbered benign OCR regions it used. This probes visual-text evidence usage beyond the original question without asking the model to identify injections. **Protocol B** asks the original benchmark question without candidate bboxes or evidence reporting and measures BA using the source benchmark scorer. These protocols, together with attacked-image localization, address three research questions.

RQ1: Do defenses cause meaningful benign evidence loss? A defense may reduce the model's use of benign visual-text evidence even on clean images. Under Protocol A, we compare how much benign evidence the model uses before and after applying a defense. Benign evidence usage coverage (BEUC) measures the fraction of benign OCR regions reported as used. Benign evidence usage drop (BEUD) subtracts defended coverage from No Defense coverage on the same sample. Both are averaged across evaluated samples. A positive drop indicates degradation in broader visual-text perception and reasoning, even if the original task answer may still be correct.

RQ2: Does task-specific BA hide benign evidence loss? Task-specific BA can be too coarse because the original question may depend on only a small subset of the image. RQ2 therefore conditions on samples the defended model answers correctly under Protocol B and asks whether it still loses benign OCR evidence under Protocol A. The hidden evidence-loss rate, BHEL_c, measures the fraction of these samples with positive BEUD. The hidden evidence-loss magnitude, BHEM_c, averages BEUD over the same subset, counting non-decreases as zero.

RQ3: Can defenses discriminate injected text from benign text and localize the injection? On attacked images, a defense must identify injected text without suppressing benign visual evidence. Injection recall (InjR) measures how often the injected bbox is flagged. Benign-text false-positive rate (BTFPR) averages the fraction of benign OCR bboxes flagged per image. Exact localization (ExactLoc) measures how often only the injected bbox is flagged. These metrics assess discrimination and localization needed for selective removal and inspection, which pure answer-level rejection cannot provide. Full protocols, metric definitions, and more details are provided in Appendix A.2.

4 VPIXDISTILL

We observe that successful VPIs exhibit four properties. First, the injected region must receive attention from the user instruction; otherwise, it is unlikely to influence the response. Second, it often conflicts with its local visual context. Third, it is inconsistent with image-level evidence. Fourth, when the injection succeeds, the response is driven by the injected text rather than the user instruction. We measure them with four model-internal risk signals: instruction-to-image attention (S1), local semantic conflict (S2), global manifold residual (S3), and instruction-attention rebound (S4). Since benign task-relevant text is also attended, S1 serves only for candidate proposal, while S2–S4 separate injected from benign text. VPIXDISTILL-X applies these signals as a white-box runtime defense, and VPIXDISTILL-D distills them into a lightweight detector for black-box LVLMs.

4.1 MODEL-INTERNAL VPI RISK SIGNALS

A candidate region R is a set of visual patches. Let $h_p^{(\ell)}$ be the hidden state of patch p at layer ℓ, and $A_j^{(\ell)}(t,k)$ the attention weight from query t to key k in head j. The LVLM has L layers and H attention heads. We denote user-instruction token positions by $\mathcal{I}$ and their content tokens by $\mathcal{I}_c$.

S1: Instruction-to-image attention. We measure how strongly the instruction content tokens attend to a region:

$$s_{\text{attn}}(R) = \frac{1}{|R||\mathcal{L}_a|} \sum_{p\in R} \sum_{\ell\in\mathcal{L}_a} \max_{\substack{t\in\mathcal{I}_c \\ 1\le j\le H}} A_j^{(\ell)}(t,p), \tag{1}$$

where $\mathcal{L}_a$ is a fixed set of extraction layers. S1 measures question-image alignment rather than maliciousness, so we use it for candidate proposal.

S2: Local semantic conflict. We measure whether the semantics decoded from a region's representation differ from its surrounding visual evidence. The logit lens maps a patch state to $P_\ell(p) = \mathrm{softmax}(\mathrm{LayerNorm}(h_p^{(\ell)})W_U)$, using the model's final layer norm and unembedding matrix W_U. Let $N_R(p)$ contain neighboring patches outside R, and $\bar{P}_\ell(N_R(p))$ be their mean decoded distribution. We define

$$s_{\mathrm{local}}(R) = \frac{1}{|R|} \sum_{p \in R} \max_{\ell \in \mathcal{L}_d} D_{\mathrm{KL}}\big(P_\ell(p) \,\big\|\, \bar{P}_\ell(N_R(p))\big)\,, \tag{2}$$

where $\mathcal{L}_d$ contains the selected decoding layers. Higher scores indicate stronger local conflict.

S3: Global manifold residual. Since benign text can also differ from its immediate background, we additionally compare the region with image-level features. At a selected layer ℓ, write $h_p = h_p^{(\ell)}$, and let $\mu_{\bar{R}}$ and $\Sigma_{\bar{R}}$ be the mean and shrinkage covariance of patch features outside R. Let (u_j, λ_j) be the covariance eigenpairs in decreasing order of variance, with the top m_0 directions retaining a fixed fraction of the variance. We score the remaining feature components by

$$s_{\mathrm{global}}(R) = \frac{1}{|R|} \sum_{p \in R} \sum_{j > m_0} \frac{\langle u_j, h_p - \mu_{\bar{R}} \rangle^2}{\lambda_j}. \tag{3}$$

This is a Mahalanobis distance restricted to the minor subspace (Lee et al., 2018). Higher scores indicate feature components poorly explained by the rest of the image.

S4: Instruction-attention rebound. A successful VPI can divert answer generation away from the user instruction and toward the injected visual text. We test this by masking a candidate region and measuring whether attention to the instruction recovers. For image X, let $a(X)$ be the instruction-attention mass at the first answer-forming position $t_\star$ and selected layer ℓ_r:

$$a(X) = \frac{1}{H} \sum_{j=1}^{H} \sum_{i \in \mathcal{I}} A_j^{(\ell_r)}(t_\star, i), \tag{4}$$

$$s_{\mathrm{inst}}(R) = a(I_{\mathrm{mask}(R)}) - a(I), \tag{5}$$

where the attention in $a(X)$ is evaluated on X and $I_{\mathrm{mask}(R)}$ replaces R in image I with a constant gray value. Higher scores indicate greater recovery of instruction attention after masking.

We test whether S1 retains injected regions and S2–S4 rank them above benign regions in the same image. Details and hypothesis definitions are in Appendix B; hypothesis tests are in Appendix D.6.

4.2 VPIXDISTILL-X

The signals above lead to a white-box runtime defense that suppresses injected visual text at the region level. The defense is interpretable by construction, since each removed region is associated with its localization mask and signal scores.

Stage 1: Candidate proposal. We compute patch-level S1 scores with one prompt forward pass and detect text boxes on the original full-resolution image, preserving small text that may disappear after resizing. Each box B is mapped to the patch grid and scored by

$$s_{\mathrm{attn}}(B) = \frac{\sum_p c_B(p) s_{\mathrm{attn}}(p)}{\sum_p c_B(p)}, \tag{6}$$

where $c_B(p)$ is the fraction of patch p covered by B, and $s_{\mathrm{attn}}(p)$ is Eq. 1 for a single patch. Each text box is retained as a candidate when its box-level attention score passes the Stage 1 attention gate. This stage is intentionally loose and aims to include the injection region among the candidates, but it does not decide whether a region is malicious.

Stage 2: Verification. We standardize S2–S4 against background distributions estimated from non-candidate visual evidence in the same image. Let $z_i(R)$ be the standardized score and Φ the standard



Figure 2: VPIXDISTILL-D pipeline. An offline teacher computes privileged S1–S4 targets and region labels. The student learns a Stage 1 localizer and Stage 2 region verifier. At inference, it masks flagged regions in a single detection pass and sends the sanitized image to the LVLM.

normal CDF. We flag R when

$$\text{score}(R) = \sum_{i \in \{\text{local,global,inst}\}} \Phi(z_i(R)) > \theta. \tag{7}$$

The additive rule allows complementary evidence from S2–S4 to accumulate without requiring every signal to exceed an individual threshold. We calibrate θ for each target LVLM using held-out benign samples. Further discussion is provided in Appendix B.3.

Stage 3: Neutralization and re-answering. We erase flagged regions with a content-free fill and query the LVLM with the sanitized image and original instruction. If no region is flagged, the image is unchanged. The pipeline is illustrated in Appendix B, Fig. 5.

4.3 VPIXDISTILL-D

VPIXDISTILL-X requires model-internal access and additional masked forward passes. We therefore develop VPIXDISTILL-D, a lightweight detector that learns these signals through distillation (Fig. 2). Instead of directly distilling VPIXDISTILL-X, we construct an offline teacher that produces stronger region-level supervision using privileged information available only during training.

Privileged teacher. A frozen LVLM produces S1–S4 targets using training-only information: paired clean images, ground-truth injection boxes, correct answers, attacker-chosen targets, and oracle layer choices. S1 supervises localization and S2–S4 supervise verification. Unlike X's runtime S3, the teacher's privileged S3 measures the attacked-to-clean hidden-state shift along an adversarial direction estimated from the attack-target preference over the correct answer. Targets are cached offline and reused for training, following distillation with privileged information (Lopez-Paz et al., 2015; Hinton et al., 2015; Vapnik & Vashist, 2009).

Student detector. The student takes intermediate ViT features and instruction token embeddings from a frozen open-source LVLM, independently of the protected LVLM. Stage 1 predicts the teacher S1 map and retains the top-$k\%$ of CRAFT text boxes by predicted score (Baek et al., 2019). Stage 2 predicts S2–S4 for each candidate and combines them with region features through a learned verifier. Unlike the empirically calibrated decision rule in VPIXDISTILL-X, the verifier is supervised with three region classes: benign text, typographic injection, and goal-hijacking injection.

Training. We first train the localizer using normalized mean-squared error and cosine loss against the teacher S1 map:

$$\mathcal{L}_{\text{loc}} = \mathcal{L}_{\text{mse}}(\hat{s}_{\text{attn}}, s^T_{\text{attn}}) + \mathcal{L}_{\cos}(\hat{s}_{\text{attn}}, s^T_{\text{attn}}). \tag{8}$$

Here s^T_{attn} is the teacher saliency map and $\hat{s}_{\text{attn}}$ is the student prediction. We then freeze the localizer and train Stage 2 on ground-truth injection regions and benign detected text regions rather than

Stage 1 proposals, decoupling verifier training from localization errors. Its auxiliary heads regress the privileged S2–S4 targets, while the main detection head learns three-class region classification:

$$\mathcal{L}_{\text{ver}} = \sum_{i=2}^{4} \mathcal{L}_{\text{mse}}(\hat{r}_i, r_i^T) + \mathcal{L}_{\text{ce}}(\hat{\mathbf{y}}, y), \tag{9}$$

where r_i^T and $\hat{r}_i$ are teacher signal targets and student predictions, and y and $\hat{\mathbf{y}}$ are the region class and predicted logits.

Deployment. We suppress candidates with $P_{\text{inj}} = P_{\text{typo}} + P_{\text{hijack}} > \tau$ and pass the sanitized image and original instruction to the protected LVLM. No teacher signals, clean pairs, or protected-model internals are required, enabling deployment with black-box commercial LVLMs. Teacher collection, layer selection, and architecture details are in Appendix C.

5 Evaluation

5.1 Evaluation Setup

Datasets and attacks. For typographic VPI, we use TypoD-base (Cheng et al., 2024), spanning perception- and cognition-oriented VQA tasks, and LingoQA (Marcu et al., 2024) for autonomous-driving VQA. On both, we evaluate Center attacks, which overlay adversarial text near the image center, and SceneTAP (Cao et al., 2025b). For direct goal-hijacking VPI, we use ARGUS-VTQA (Lu et al., 2026), whose injected instructions ask the model to output an attacker-specified string. Region-level evaluation uses SafeRegionVPI (Sec. 3).

Target LVLMs. We use four open-weight LVLMs: LLaVA-1.5-7B (Liu et al., 2023), LLaVA-NeXT-7B (Liu et al., 2024), Qwen2.5-VL-7B-Instruct (Wu et al., 2025), and InternVL3-14B (Zhu et al., 2025), and train a VPIXDistill-D detector from each model's offline teacher signals. For black-box deployment, we apply VPIXDistill-D to Claude Haiku 4.5 and Gemini 2.5 Flash in benchmark experiments, GPT-4o (Hurst et al., 2024) in drone case studies, and Claude Sonnet 4.5 in the web-agent case study.

Baselines. We include No Defense and System Prompt (Cao et al., 2025a) as simple baselines. We evaluate JailGuard (Zhang et al., 2025) and CIDER (Xu et al., 2024) as transferred jailbreak defenses. We also include two VPI-specific defenses, ARGUS (Lu et al., 2026) and RIO-RT (Waseda et al., 2025). We further evaluate three OCR-adapted text prompt-injection defenses to test whether extracting visual text enables effective text-side protection, with results reported in Appendix D.3. Detailed configurations and additional results are provided in Appendix D.

5.2 VPI Defense Effectiveness

Evaluation setup. For typographic VPI, we report BA and TA on clean and attacked inputs, respectively, and ASR for attacker-target matching. For goal hijacking, we follow ARGUS (Lu et al., 2026): $\text{UIA}_{\text{clean}}$ and UIA_{inj} measure user-instruction accuracy on clean and injected inputs; AIA measures attacker-answer matching, and AIFR measures whether the attacker instruction is followed. Details are provided in Appendix D.

Results and analysis. Table 2 shows that VPIXDistill remains effective against both typographic and goal-hijacking VPI on open-source and closed-source LVLMs while largely preserving benign accuracy. System Prompt does not consistently reduce ASR and can degrade task accuracy, matching prior observations (Cao et al., 2025a; Lu et al., 2026). CIDER also provides little protection: the injected text is a localized semantic signal that may not substantially change the global image representation, yet can still be read and followed. JailGuard improves some goal-hijacking results but often reduces task accuracy, and may be less reliable when injected text survives image mutations. It also requires multiple LVLM queries per input, increasing inference cost (Liu et al., 2025). The VPI-specific baselines show scope limitations. ARGUS is strong on goal hijacking but gives little typographic protection without utility loss, while RIO-RT is strong in some typographic settings but often reduces clean utility. VPIXDistill is based on internal VPI signals rather than a single attack format, allowing it to compete with specialized defenses across both VPI families.

Table 2: Task-level VPI defense performance. White-box defenses are unavailable for closed-source Claude Haiku 4.5 and Gemini 2.5 Flash. Best results are bolded and second-best results underlined.

LVLM	Defense	TypoD-base (typographic)					LingoQA (typographic)					ARGUS-VTQA (goal-hijacking)			
		BA↑	Center Attack		SceneTAP		BA↑	Center Attack		SceneTAP		UIA_{clean}↑	UIA_{inj}↑	AIA↓	AIFR↓
			ASR↓	TA↑	ASR↓	TA↑		ASR↓	TA↑	ASR↓	TA↑				
Qwen2.5	No Defense	88.8	33.6	66.3	34.6	65.2	57.4	25.8	40.2	22.0	42.4	47.9	5.2	75.3	79.8
	System Prompt	**89.6**	25.5	74.4	28.4	71.4	48.2	26.8	26.2	23.4	37.6	46.3	4.1	76.6	81.7
	JailGuard	79.8	29.1	56.1	30.1	57.0	49.2	25.0	32.2	20.8	34.6	47.0	2.4	5.2	5.6
	CIDER	83.5	32.6	64.1	32.8	61.3	54.8	18.8	36.2	17.6	40.4	42.1	4.9	68.9	72.9
	ARGUS	87.4	33.5	65.1	34.6	64.6	53.6	25.2	35.4	22.0	39.8	47.0	22.9	**0.7**	**1.4**
	RIO-RT	75.7	**11.8**	81.6	21.5	72.9	12.6	**7.4**	12.0	**6.4**	11.4	22.8	2.3	22.4	25.0
	VPIXDISTILL-X	88.8	17.6	82.3	20.0	80.0	**58.4**	13.8	50.4	13.6	50.4	48.1	42.4	9.6	10.4
	VPIXDISTILL-D	89.0	13.9	**85.9**	**19.4**	**80.4**	58.0	12.4	**55.2**	14.6	**53.8**	**48.3**	**46.6**	2.6	2.6
InternVL3	No Defense	94.8	35.4	64.6	31.7	68.3	**52.0**	28.4	26.0	24.6	31.6	61.5	34.4	26.5	31.8
	System Prompt	**95.5**	31.2	68.8	29.5	70.4	48.8	30.6	23.4	25.2	29.0	61.4	31.4	28.3	34.2
	JailGuard	77.4	8.2	43.1	9.5	42.3	47.0	26.0	23.8	22.2	26.2	60.5	25.2	6.4	7.2
	CIDER	88.9	34.4	62.3	30.0	64.3	48.7	21.2	24.2	20.6	30.8	54.3	30.9	24.7	29.6
	ARGUS	9.9	**1.0**	14.2	**0.9**	15.6	48.2	28.2	23.6	24.8	29.8	61.6	53.0	0.1	0.1
	RIO-RT	94.4	2.2	**97.8**	6.5	**93.5**	43.6	14.6	40.6	14.6	44.2	47.6	41.3	2.0	3.1
	VPIXDISTILL-X	94.6	10.0	90.0	13.5	86.5	51.2	12.2	43.2	**12.6**	**47.4**	**62.8**	**63.6**	**0.0**	**0.0**
	VPIXDISTILL-D	94.8	12.6	87.4	18.2	81.8	51.8	**12.0**	**48.6**	13.8	45.2	62.0	59.2	4.6	5.7
Claude Haiku 4.5	No Defense	90.5	26.3	73.5	26.9	72.9	37.4	30.8	28.4	26.0	33.2	**67.8**	61.7	27.3	28.9
	System Prompt	89.2	19.3	77.0	21.0	75.2	37.2	28.8	27.6	25.2	31.8	65.2	63.3	8.0	8.3
	JailGuard	45.5	**8.2**	34.4	**11.6**	34.6	29.8	19.6	20.0	18.4	22.8	57.2	41.8	9.4	10.2
	CIDER	85.1	25.0	71.6	24.9	69.1	35.5	22.8	26.0	19.0	34.0	60.3	56.1	25.1	26.5
	VPIXDISTILL-D	**90.6**	12.5	**87.0**	15.9	**83.3**	**41.8**	**15.6**	**33.8**	**17.2**	**37.6**	67.1	**66.5**	**0.6**	**0.7**
Gemini 2.5 Flash	No Defense	79.8	8.6	67.4	10.2	67.1	**56.4**	25.8	40.2	24.6	43.4	57.0	17.0	70.3	72.0
	System Prompt	**86.8**	13.4	**79.3**	15.8	**76.4**	53.6	24.6	38.6	23.4	39.8	56.2	39.7	31.1	32.0
	JailGuard	40.8	**3.0**	28.0	**4.6**	28.9	35.2	16.8	25.2	19.2	32.8	47.4	4.6	17.2	17.2
	CIDER	74.8	8.2	65.4	9.5	63.4	50.0	18.8	32.4	18.0	39.0	49.3	14.9	65.1	66.5
	VPIXDISTILL-D	78.5	4.2	72.0	5.4	68.2	**56.4**	**11.8**	**50.6**	**13.8**	**53.6**	**57.6**	**55.4**	**2.6**	**2.6**

Table 3: Benign evidence preservation on clean SAFEREGIONVPI images (%).

Defense	BA↑	IF↑	BEUC↑	BEUD↓	$BHEL_c$ ↓	$BHEM_c$ ↓
No Defense	88.5	99.9	59.4	–	–	–
Prompt	88.3	100.0	51.9	7.5	41.7	14.4
OCR+Prompt	86.6	100.0	48.6	10.8	48.8	19.5
ARGUS	86.1	79.8	63.1	−0.5	20.7	5.4
RIO-RT	81.8	27.5	27.2	27.5	74.4	32.8
VPIXDISTILL-D	87.0	100.0	61.0	−1.7	31.9	9.2

Figure 3: Injection localization on attacked SAFEREGIONVPI images (%).



5.3 SAFEREGIONVPI EVALUATION

Evaluation setup. We use Qwen2.5-VL-7B and VPIXDISTILL-D distilled from its internal signals, following the protocols and metrics in Section 3. For RQ1 and RQ2, we evaluate clean images under Protocols A and B. We additionally report format instruction following (IF). IF measures whether the model answers the diagnostic question and reports used bbox IDs in the required format. Evidence-usage metrics are computed on IF-passing samples, using valid paired reports for comparisons with No Defense. For RQ3, we evaluate localization on attacked images and compare with OCR+PG2-mask, which classifies each OCR string and masks flagged boxes. Most task-level defenses do not output suspicious regions and are therefore excluded from this comparison.

Results and analysis. Table 3 shows that BA alone can hide the utility cost of VPI defenses. Prompt changes BA only from 88.5% to 88.3%, but reduces BEUC from 59.4% to 51.9%; even when the final answer remains correct, 41.7% of eligible samples suffer evidence loss. ARGUS and RIO-RT also reduce IF, limiting the coverage of their evidence-usage measurements. In contrast, VPIXDISTILL-D preserves IF at 100.0%, keeps BA close to No Defense, and maintains benign evidence usage on average. Figure 3 shows that OCR+PG2-mask rarely localizes typographic injections and also performs poorly on goal hijacking, suggesting that text-only detection is insufficient in text-rich scenes, whereas VPIXDISTILL-D consistently localizes injected regions across both attack families while limiting benign-text suppression. Results on other models are in Appendix D.5.

5.4 ADAPTIVE ATTACKS

We evaluate VPIXDISTILL-D against defense-aware attacks that adapt injected visual text to evade the defense while preserving attack effectiveness. We adapt the black-box optimization-based CHAI (Burbano et al., 2025) and planner-based SCENETAP (Cao et al., 2025b), using Qwen2.5-VL-7B as the victim and its corresponding distilled detector.

For CHAI, the attacker observes the fused Stage 2 defense score and incorporates it into the optimization objective. For SCENETAP, we inform the GPT-4o planner of the three Stage 2 risk mechanisms and return the victim result and fused defense score for replanning. We evaluate typographic and goal-hijacking attacks on TextVQA and typographic attacks on LingoQA, which is unseen during detector training. ASR w/ Defense requires both achieving the attacker-specified target and evading the defense. Attack budgets, configurations, and results for attacks targeting individual risk signals are in Appendix D.8. Table 4 shows that VPIXDISTILL-D consistently reduces ASR against both CHAI and SCENETAP, including on the unseen LingoQA. These results suggest that explicitly modeling VPI properties helps the defense remain effective under adaptive attacks.

Table 4: Adaptive-attack ASR (%) on Qwen2.5-VL-7B, with and without VPIXDISTILL-D.

		CHAI		SCENETAP	
Bench.	Attack	w/o Def.	w/ Def.↓	w/o Def.	w/ Def.↓
TextVQA	Typo	49.9	26.9	60.8	20.4
	Hijack	13.0	6.1	29.6	9.6
LingoQA	Typo	38.0	24.8	27.2	7.2

5.5 INFERENCE TIME

We measure per-sample wall-clock latency on 100 clean TextVQA samples under three random seeds, with all methods evaluated on the same samples for each seed. We evaluate a white-box setting with Qwen2.5-VL-7B and a black-box setting with GPT-4o. Local latency is measured in a single-stream setting on one NVIDIA RTX PRO 6000, and GPT-4o runs with and without VPIXDISTILL-D are measured in paired order within the same API session. On Qwen2.5-VL-7B (Table 5), VPIXDISTILL-X increases total latency by 149.9%, mainly due to online signal computation and masked re-forwarding over candidate regions. VPIXDISTILL-D substantially reduces this overhead: its defense time is only 0.070 s, about $5.1\times$ faster than VPIXDISTILL-X, and the total latency increase drops to 27.3%. When the sanitized image is provided to black-box GPT-4o, the total latency increases by only 10.3%.

Table 5: Per-sample latency (s). Defense is defense time. Total is mean±std over three seeds, and Δ is relative to no defense.

Method	Defense	Total	Δ
White-box: Qwen2.5-VL-7B			
No defense	0	0.236±0.008	–
VPIXDISTILL-X	0.359	0.590±0.012	+149.9%
VPIXDISTILL-D	0.070	0.300±0.008	+27.3%
Black-box: GPT-4o			
No defense	0	1.643±0.129	–
VPIXDISTILL-D	0.087	1.812±0.134	+10.3%

More studies. We show that OCR-adapted text prompt-injection defenses are insufficient for VPI (Appendix D.3). Statistical tests across three LVLMs and benchmarks support the risk-signal hypotheses in Sec. 4.1 (Appendix D.6). Ablations and pairwise correlation analysis show that S2–S4 provide complementary rather than redundant signals (Appendix D.7).

We further demonstrate practical effectiveness and generalization beyond our main benchmarks. Without retraining, VPIXDISTILL-D reduces FigStep ASR by 98.6–99.5% on LLaVA-1.5 and black-box Claude Haiku 4.5 (Appendix D.9). Closed-loop web-agent and simulated drone-tracking experiments, together with real-world physical VPI experiments, show that VPIXDISTILL-D transfers to interactive and physical settings (Appendices D.10 and D.11).

6 CONCLUSION AND LIMITATIONS

We show that task-level BA can hide important utility loss in VPI defenses, motivating SAFEREGIONVPI, a bbox-level benchmark for measuring benign evidence preservation and region-aware VPI localization. We further analyze VPI behavior inside LVLMs and use the resulting signals to build VPIXDISTILL-X, an explainability-guided region-level defense, and VPIXDISTILL-D, a distilled input sanitizer that supports efficient deployment with closed-source LVLMs. Our work focuses on VPI, and it remains unclear whether the same behaviors hold for text-only PI in LLMs, which we leave for future work.

AI USE STATEMENT

We used large language models to polish the writing of author-written text. We did not use them for research ideation, experimental design, implementation, analysis, or literature retrieval. LLMs and LVLMs that serve as evaluation targets, attack components, or benchmark filters are part of our experimental setup and are described in Sec. 5.1 and the appendix. All AI-assisted text has been reviewed by the authors, who take responsibility for the final content of this work.

ETHICS STATEMENT

This work studies defenses against visual prompt injection attacks on Large Vision-Language Models (LVLMs). Because the paper analyzes malicious visual text and constructs adversarial benchmark samples, the research has potential dual-use implications. We mitigate this risk by focusing on defense, measurement, and controlled evaluation rather than attacks on deployed systems. Our benchmark does not introduce a new attack capability, but adapts previously studied typographic attack generation and optimization-free text prompt injection ideas to construct controlled goal-hijacking visual prompt injection samples for defensive evaluation. All experiments use public datasets, controlled benchmarks, our own physical testbed, or closed-source commercial LVLMs accessed only through standard API interfaces as protected target models. Attacks on these models are limited to benchmark evaluation, and we do not attempt to extract their internals, collect personal data, involve human subjects, or interact with third-party live systems. The web-agent and drone experiments are conducted only in controlled settings and do not target real users or operational services. Any released benchmark artifacts will be documented with the intended threat model, scope, limitations, and appropriate-use guidance.

REPRODUCIBILITY STATEMENT

The construction of SAFEREGIONVPI is described in Appendix A.1, and its evaluation protocols and metrics in Appendix A.2. The risk signals and the runtime decision rule of VPIXDISTILL-X are defined in Sec. 4.1 and Sec. 4.2, with further details in Appendices B and B.3. Teacher signal collection, layer selection, student architecture, and training procedure for VPIXDISTILL-D are given in Appendix C. Evaluation settings and baseline configurations are described in Sec. 5.1 and Appendix D; adaptive-attack budgets and configurations are in Appendix D.8; and the web-agent and drone case-study settings are in Appendices D.10 and D.11. Latency is measured under the hardware and protocol reported in Sec. 5.5.

REFERENCES

Philippe Artzner, Freddy Delbaen, Jean-Marc Eber, and David Heath. Coherent measures of risk. *Mathematical finance*, 9(3):203–228, 1999.

Youngmin Baek, Bado Lee, Dongyoon Han, Sangdoo Yun, and Hwalsuk Lee. Character region awareness for text detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9365–9374, 2019.

Yannik Blei, Michael Krawez, Nisarga Nilavadi, Tanja Katharina Kaiser, and Wolfram Burgard. Cloudtrack: Scalable uav tracking with cloud semantics. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 15893–15899. IEEE, 2025.

Luis Burbano, Diego Ortiz, Qi Sun, Siwei Yang, Haoqin Tu, Cihang Xie, Yinzhi Cao, and Alvaro A Cardenas. Chai: Command hijacking against embodied ai. *arXiv preprint arXiv:2510.00181*, 2025.

Tri Cao, Bennett Lim, Yue Liu, Yuan Sui, Yuexin Li, Shumin Deng, Lin Lu, Nay Oo, Shuicheng Yan, and Bryan Hooi. Vpi-bench: Visual prompt injection attacks for computer-use agents. *arXiv preprint arXiv:2506.02456*, 2025a.

Yue Cao, Yun Xing, Jie Zhang, Di Lin, Tianwei Zhang, Ivor Tsang, Yang Liu, and Qing Guo. Scenetap: Scene-coherent typographic adversarial planner against vision-language models in real-world environments. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 25050–25059, 2025b.

Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, David Wagner, and Chuan Guo. Secalign: Defending against prompt injection with preference optimization. In *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*, 2025a.

Sizhe Chen, Arman Zharmagambetov, David Wagner, and Chuan Guo. Meta secalign: A secure foundation llm against prompt injection attacks. *arXiv preprint arXiv:2507.02735*, 2025b.

Hao Cheng, Erjia Xiao, Jindong Gu, Le Yang, Jinhao Duan, Jize Zhang, Jiahang Cao, Kaidi Xu, and Renjing Xu. Unveiling typographic deceptions: Insights of the typographic vulnerability in large vision-language models. In *European Conference on Computer Vision*, pp. 179–196. Springer, 2024.

Alexey Dosovitskiy, German Ros, Felipe Codevilla, Antonio Lopez, and Vladlen Koltun. Carla: An open urban driving simulator. In *Conference on robot learning*, pp. 1–16. PMLR, 2017.

Gabriel Goh, Nick Cammarata, Chelsea Voss, Shan Carter, Michael Petrov, Ludwig Schubert, Alec Radford, and Chris Olah. Multimodal neurons in artificial neural networks. *Distill*, 6(3):e30, 2021.

Yichen Gong, Delong Ran, Jinyuan Liu, Conglei Wang, Tianshuo Cong, Anyu Wang, Sisi Duan, and Xiaoyun Wang. Figstep: Jailbreaking large vision-language models via typographic visual prompts. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 23951–23959, 2025.

Yunhao Gou, Kai Chen, Zhili Liu, Lanqing Hong, Hang Xu, Zhenguo Li, Dit-Yan Yeung, James T Kwok, and Yu Zhang. Eyes closed, safety on: Protecting multimodal llms via image-to-text transformation. In *European Conference on Computer Vision*, pp. 388–404. Springer, 2024.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Yidong Huang, Jacob Sansom, Ziqiao Ma, Felix Gervits, and Joyce Chai. Drivlme: Enhancing llm-based autonomous driving agents with embodied and social experiences. In *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 3153–3160. IEEE, 2024.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.

Jaided AI. EasyOCR. `https://github.com/JaidedAI/EasyOCR`, 2020.

Neel Jain, Avi Schwarzschild, Yuxin Wen, Gowthami Somepalli, John Kirchenbauer, Ping-yeh Chiang, Micah Goldblum, Aniruddha Saha, Jonas Geiping, and Tom Goldstein. Baseline defenses for adversarial attacks against aligned language models. *arXiv preprint arXiv:2309.00614*, 2023.

Subaru Kimura, Ryota Tanaka, Shumpei Miyawaki, Jun Suzuki, and Keisuke Sakaguchi. Empirical analysis of large vision-language models against goal hijacking via visual prompt injection. *arXiv preprint arXiv:2408.03554*, 2024.

Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 4015–4026, 2023.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Russ Salakhutdinov, and Daniel Fried. VisualWebArena: Evaluating Multimodal Agents on Realistic Visual Web Tasks. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A Simple Unified Framework for Detecting Out-of-Distribution Samples and Adversarial Attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Hao Li, Xiaogeng Liu, Ning Zhang, and Chaowei Xiao. Piguard: Prompt injection guardrail via mitigating overdefense for free. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 30420–30437, 2025a.

Xinke Li, Junchi Lu, Henghui Ding, Changsheng Sun, Joey Tianyi Zhou, and Yeow Meng Chee. Pointcvar: Risk-optimized outlier removal for robust 3d point cloud classification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 21340–21348, 2024a.

Yanjie Li, Yiming Cao, Dong Wang, and Bin Xiao. Agenttypo: Adaptive typographic prompt injection attacks against black-box multimodal agents. *arXiv preprint arXiv:2510.04257*, 2025b.

Yifan Li, Hangyu Guo, Kun Zhou, Wayne Xin Zhao, and Ji-Rong Wen. Images are achilles' heel of alignment: Exploiting visual vulnerabilities for jailbreaking multimodal large language models. In *European Conference on Computer Vision*, pp. 174–189. Springer, 2024b.

Zeyi Liao, Jaylen Jones, Linxi Jiang, Yuting Ning, Eric Fosler-Lussier, Yu Su, Zhiqiang Lin, and Huan Sun. Redteamcua: Realistic adversarial testing of computer-use agents in hybrid web-os environments. *arXiv preprint arXiv:2505.21936*, 2025.

Chen Ling, Kai Hu, Hangcheng Liu, Xingshuo Han, Tianwei Zhang, and Changhai Ou. Physical prompt injection attacks on large vision-language models. *arXiv preprint arXiv:2601.17383*, 2026.

Daizong Liu, Mingyu Yang, Xiaoye Qu, Pan Zhou, Yu Cheng, and Wei Hu. A survey of attacks on large vision–language models: Resources, advances, and future trends. *IEEE Transactions on Neural Networks and Learning Systems*, 2025.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916, 2023.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 26296–26306, 2024.

David Lopez-Paz, Léon Bottou, Bernhard Schölkopf, and Vladimir Vapnik. Unifying distillation and privileged information. *arXiv preprint arXiv:1511.03643*, 2015.

Weikai Lu, Ziqian Zeng, Kehua Zhang, Haoran Li, Huiping Zhuang, Ruidong Wang, Cen Chen, and Hao Peng. Argus: Defending against multimodal indirect prompt injection via steering instruction-following behavior. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 31–40, 2026.

Ana-Maria Marcu, Long Chen, Jan Hünermann, Alice Karnsund, Benoit Hanotte, Prajwal Chidananda, Saurabh Nair, Vijay Badrinarayanan, Alex Kendall, Jamie Shotton, et al. Lingoqa: Visual question answering for autonomous driving. In *European Conference on Computer Vision*, pp. 252–269. Springer, 2024.

Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 2200–2209, 2021.

Meta. Llama Prompt Guard 2. `https://www.llama.com/docs/model-cards-and-prompt-formats/prompt-guard/`.

Microsoft. OCR - Optical Character Recognition. `https://learn.microsoft.com/en-us/azure/ai-services/computer-vision/overview-ocr`, 2025.

Runliang Niu, Jindong Li, Shiqi Wang, Yali Fu, Xiyu Hu, Xueyuan Leng, He Kong, Yi Chang, and Qi Wang. ScreenAgent: A Vision Language Model-driven Computer Control Agent. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2024.

Xiangyu Qi, Kaixuan Huang, Ashwinee Panda, Peter Henderson, Mengdi Wang, and Prateek Mittal. Visual adversarial examples jailbreak aligned large language models. In *Proceedings of the AAAI conference on artificial intelligence*, volume 38, pp. 21527–21536, 2024.

Maan Qraitem, Nazia Tasnim, Piotr Teterwak, Kate Saenko, and Bryan A Plummer. Vision-llms can fool themselves with self-generated typographic attacks. *arXiv preprint arXiv:2402.00626*, 2024.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8317–8326, 2019.

Vladimir Vapnik and Akshay Vashist. A new learning paradigm: Learning using privileged information. *Neural networks*, 2009.

Che Wang, Fuyao Zhang, Jiaming Zhang, Ziqi Zhang, Yinghui Wang, Longtao Huang, Jianbo Gao, Zhong Chen, and Wei Yang Bryan Lim. Icon: Indirect prompt injection defense for agents based on inference-time correction. *arXiv preprint arXiv:2602.20708*, 2026.

Yuxin Wang, Hongtao Xie, Shancheng Fang, Jing Wang, Shenggao Zhu, and Yongdong Zhang. From two to one: A new scene text recognizer with visual language modeling network. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 14194–14203, 2021.

Futa Waseda, Shojiro Yamabe, Daiki Shiono, Kento Sasaki, and Tsubasa Takahashi. Read or ignore? a unified benchmark for typographic-attack robustness and text recognition in vision-language models. *arXiv preprint arXiv:2512.11899*, 2025.

Maolin Wei, Wanzhou Liu, and Eshed Ohn-Bar. Driveqa: Passing the driving knowledge test. *arXiv preprint arXiv:2508.21824*, 2025.

Chenfei Wu, Jiahao Li, Jingren Zhou, Junyang Lin, Kaiyuan Gao, Kun Yan, Sheng-ming Yin, Shuai Bai, Xiao Xu, Yilei Chen, et al. Qwen-image technical report. *arXiv preprint arXiv:2508.02324*, 2025.

Shaoyuan Xie, Lingdong Kong, Yuhao Dong, Chonghao Sima, Wenwei Zhang, Qi Alfred Chen, Ziwei Liu, and Liang Pan. Are vlms ready for autonomous driving? an empirical study from the reliability, data and metric perspectives. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6585–6597, 2025.

Yue Xu, Xiuyuan Qi, Zhan Qin, and Wenjie Wang. Cross-modality information check for detecting jailbreaking in multimodal large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 13715–13726, 2024.

Jianwei Yang, Hao Zhang, Feng Li, Xueyan Zou, Chunyuan Li, and Jianfeng Gao. Set-of-mark prompting unleashes extraordinary visual grounding in gpt-4v. *arXiv preprint arXiv:2310.11441*, 2023.

Mang Ye, Xuankun Rong, Wenke Huang, Bo Du, Nenghai Yu, and Dacheng Tao. A survey of safety on large vision-language models: Attacks, defenses and evaluations. *arXiv preprint arXiv:2502.14881*, 2025.

Xiaoyu Zhang, Cen Zhang, Tianlin Li, Yihao Huang, Xiaojun Jia, Ming Hu, Jie Zhang, Yang Liu, Shiqing Ma, and Chao Shen. Jailguard: A universal detection framework for prompt-based attacks on llm systems. *ACM Transactions on Software Engineering and Methodology*, 35(1):1–40, 2025.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, et al. Internvl3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*, 2025.

A SAFEREGIONVPI: CONSTRUCTION AND EVALUATION PROTOCOLS

A.1 BENCHMARK CONSTRUCTION

A.1.1 SOURCE DOMAINS AND TEXT-RICH SUBSET SELECTION

We build SAFEREGIONVPI from three VQA datasets that cover distinct visual-text settings. **TextVQA** (Singh et al., 2019) represents general natural scenes, where text appears on signs, storefronts, packaging, and labels. **DocVQA** (Mathew et al., 2021) represents text-dense document images with many structured OCR regions. **DriveQA-V** (Wei et al., 2025) represents safety-critical driving scenes where textual traffic signs are sparse but often important.

Since SAFEREGIONVPI evaluates region-level utility, each image must contain enough benign text regions to support meaningful false-positive analysis. We therefore construct a *text-rich subset* for each dataset by ranking images by OCR density and retaining approximately the top 30%. For DocVQA, we reuse the released Microsoft Read OCR (Microsoft, 2025) annotations. For TextVQA and DriveQA-V, we run EasyOCR (Jaided AI, 2020). Because many CARLA traffic signs are pictogram-only, we first remove images with no detected text and then apply the text-rich selection to the remaining text-bearing signs. For TextVQA and DocVQA, we follow the original dataset splits. Since DriveQA-V is validation-only, we split the selected CARLA images into SAFEREGIONVPI train and test sets with a sign-category-stratified 80/20 split. The test samples form the benchmark evaluation split. The training samples are used only for extracting teacher signals and training VPIXDISTILL-D in Sec. 4.3. The selected samples then enter the attack-generation pipeline.

A.1.2 ATTACK GENERATION

Given a clean image I, a user question q, and the ground-truth answer a, the pipeline generates an attacked image I' together with the bounding box of the injected text. The process has four stages: attack planning, OCR-safe region construction, placement selection, and text rendering.

Attack planning. Following prior GPT-based attack-generation pipelines (Cao et al., 2025b; Qraitem et al., 2024), we use GPT-4o to generate the injected text and target answer from the image, question, and ground-truth answer. Typographic injections are short misleading answers, while goal-hijacking VPI adapt optimization-free injection templates from SecAlign (Chen et al., 2025a) into context-specific imperative instructions.

OCR-safe placement. Unlike prior typographic attack pipelines, our generation process must preserve the original on-image text. We run OCR on the clean image, expand detected text boxes into protected regions, and only allow injection outside this mask. We then use Set-of-Mark (Yang et al., 2023) with a SAM (Kirillov et al., 2023) backbone to propose OCR-safe candidate regions, ask the GPT-4o planner to select one region, and fit the largest axis-aligned rectangle inside the selected mask as the rendering canvas.

Text rendering and annotation export. We render the planned text with PIL under the OCR-safety constraint. For each accepted attacked image, we record the rendered text box as the attack bbox and keep the original OCR boxes as benign text bboxes. In the test set, we assign an index to every bbox so that region-level defenses can explicitly report flagged boxes in the localization evaluation. We also export indexed benign OCR bboxes for clean images, which are used in the clean-image evidence-usage evaluations (Appendix. A.2).

A.1.3 ATTACK-EFFECTIVENESS FILTERING

For the attacked split, we filter generated candidates using target matching, following prior typographic-attack evaluation (Cheng et al., 2024; Cao et al., 2025b). This step is needed because the source benchmarks measure task correctness rather than attack success. A candidate is attack-effective if it induces an evaluator model to output the attacker-specified target. For goal hijacking, the target is the planner's *hijack_target*; for typographic attacks, it is the rendered misdirection string *adversarial_text*. We evaluate each candidate with three high-resolution VLMs from different model families: LLaVA-NeXT-Vicuna-7B (Liu et al., 2024), Qwen2.5-VL-7B-Instruct (Wu et al., 2025), and InternVL3-14B (Zhu et al., 2025). Each evaluator is queried on the attacked image with a fixed

Protocol A

Image: Clean image I_s^{clean} with numbered candidate bboxes $\{1, \ldots, N_s\}$.
Bboxes: Shuffled candidate list $\mathcal{B}_s$, where each number corresponds to one benign OCR region.
Instruction: Answer the general question. After your answer, report the numbers of the candidate bounding boxes whose text you used. If none were used, report an empty set.
Question: General question: Q_s^{gen}
DocVQA: "Describe this document, including its main content and any text it contains."
TextVQA: "Describe this image, including what it shows and any text on it."
DriveQA-V: "Describe this driving scene, including any traffic signs and the text on them."
Response: Answer: $\cdots$; Used bounding boxes: $U_s^d = \{\cdots\}$

Figure 4: Protocol A prompt on clean SAFEREGIONVPI images. The general question Q_s^{gen} is dataset-specific.

answer-only prompt. We keep a candidate only when the prediction matches the attack target and does not match any ground-truth answer. Predictions that match only the ground truth, match both, or match neither are discarded.

For each split and attack variant, we keep per-model successful subsets and their union. The released `union` subset contains candidates that mislead at least one filtering-panel model and serves as the main attacked split.

A.2 Evaluation Protocols and Metrics

A.2.1 Inputs and Diagnostic Questions

Each sample contains a clean image I_s^{clean}, an attacked image I_s^{atk}, the original benchmark question Q_s^{spec} with its ground-truth answers, a diagnostic general question Q_s^{gen}, benign OCR bboxes $\mathcal{B}_s$, and an injected bbox A_s. Let $N_s = |\mathcal{B}_s|$.

Protocol A: benign evidence usage. On clean images, we provide a shuffled, numbered list of benign OCR bboxes and ask the model to answer the general question and report the IDs of the boxes whose text it used. Fig. 4 shows the prompt and the dataset-specific general questions. For defense d, the model outputs a general answer and a set U_s^d of reported benign bbox IDs. We identify these IDs with their corresponding boxes, so that $U_s^d \subseteq \mathcal{B}_s$. Protocol A measures reported benign evidence usage and does not ask the model to identify suspicious or injected regions. The reported boxes provide an output-level measure of evidence usage rather than a direct observation of internal reasoning.

Protocol B: original-task utility. The model receives the clean image and the original benchmark question Q_s^{spec}, without candidate bboxes or an evidence-reporting request. We compute BA using the original benchmark scorer. Let $c_s^d = 1$ when the defended model answers correctly and $c_s^d = 0$ otherwise. Protocols A and B are evaluated separately on the same clean samples. Protocol B determines original-task correctness, while Protocol A measures reported visual-text evidence usage under the general question.

A.2.2 Clean-Image Metrics

Format instruction following. IF measures whether the model both answers the diagnostic question and reports the used bbox IDs in the required format. We report IF under each defense to measure its effect on following this output instruction, alongside the No Defense reference. Refusals and format-collapsed outputs are treated as IF failures. A valid empty evidence set passes IF and has zero evidence coverage.

Let $f_s^d = 1$ for an IF-passing response and $f_s^d = 0$ otherwise. For the evaluated clean-sample set $\mathcal{S}_{\text{clean}}$,

$$\text{IF}^d = \frac{1}{|\mathcal{S}_{\text{clean}}|} \sum_{s \in \mathcal{S}_{\text{clean}}} f_s^d. \tag{10}$$

Benign evidence usage coverage and drop. For a sample with $N_s > 0$, benign evidence usage coverage is

$$\mathrm{BEUC}_s^d = \frac{|U_s^d|}{N_s}. \tag{11}$$

Let $\mathcal{V}_d$ denote the samples containing benign OCR text and passing IF under defense d. Dataset-level BEUC is the mean coverage on these samples:

$$\mathrm{BEUC}^d = \frac{1}{|\mathcal{V}_d|} \sum_{s \in \mathcal{V}_d} \mathrm{BEUC}_s^d. \tag{12}$$

We also report the benign evidence usage drop relative to No Defense:

$$\mathrm{BEUD}_s^d = \mathrm{BEUC}_s^{\mathrm{nodef}} - \mathrm{BEUC}_s^d. \tag{13}$$

BEUD is computed from paired sample-level comparisons on IF-passing samples. Let $\mathcal{P}_d$ denote the paired sample set used for these comparisons. The dataset-level score is

$$\mathrm{BEUD}^d = \frac{1}{|\mathcal{P}_d|} \sum_{s \in \mathcal{P}_d} \mathrm{BEUD}_s^d. \tag{14}$$

Positive BEUD indicates reduced reported benign evidence usage, while negative BEUD indicates increased usage. Because the eligible sample sets can differ across methods, BEUD need not equal the difference between the two displayed dataset-level BEUC values. Evidence-usage metrics should therefore be read together with IF.

BA-conditioned hidden evidence loss. To measure evidence loss hidden by task-specific BA, we condition on samples that the defended model answers correctly under Protocol B:

$$\mathcal{C}_d = \{s \in \mathcal{P}_d : c_s^d = 1\}. \tag{15}$$

We report the hidden evidence-loss rate and magnitude:

$$\mathrm{BHEL}_{\mathrm{cond}}^d = \frac{1}{|\mathcal{C}_d|} \sum_{s \in \mathcal{C}_d} \mathbf{1}[\mathrm{BEUD}_s^d > 0], \tag{16}$$

$$\mathrm{BHEM}_{\mathrm{cond}}^d = \frac{1}{|\mathcal{C}_d|} \sum_{s \in \mathcal{C}_d} \max(\mathrm{BEUD}_s^d, 0). \tag{17}$$

BHEL measures how often reported benign evidence usage decreases among samples that remain BA-correct. BHEM measures the mean positive-part drop over the entire correct subset, including samples with zero or negative BEUD. In tables, we abbreviate the subscript cond as c. No Defense entries for BEUD, BHEL, and BHEM are marked "–" because these metrics compare a defense with No Defense.

A.2.3 Attacked-Image Localization Metrics

On attacked images, we evaluate whether a region-aware defense flags the injected text while leaving benign OCR regions unflagged. For sample s, the evaluation candidates are

$$C_s = \{A_s\} \cup \mathcal{B}_s. \tag{18}$$

A defense outputs suspicious regions or suspicious candidate bbox IDs. Let $F_s \subseteq C_s$ be the flagged candidate set.

Bbox-level realization. If a defense reports candidate bbox IDs, we use them directly. If it outputs a pixel- or patch-level suspicious mask M_s, a candidate bbox B is flagged when $B \cap M_s \neq \emptyset$. Any overlap counts, including partial overlap with benign text, since even partial occlusion can degrade scene-text recognition (Wang et al., 2021). This mapping compares the output mask with annotated bboxes for evaluation; it does not require a mask-based defense to receive the annotated injection box at inference time.

Injection recall. For the attacked-sample set $\mathcal{S}_{\text{atk}}$, injection recall measures the fraction of samples whose injected bbox is flagged:

$$\text{InjR} = \frac{1}{|\mathcal{S}_{\text{atk}}|} \sum_{s \in \mathcal{S}_{\text{atk}}} \mathbf{1}[A_s \in F_s]. \tag{19}$$

Benign-text false-positive rate. For samples with $N_s > 0$, the per-sample false-positive rate is

$$\text{BTFPR}_s^{\text{atk}} = \frac{|F_s \cap \mathcal{B}_s|}{N_s}. \tag{20}$$

The dataset-level score averages these per-sample rates:

$$\text{BTFPR}^{\text{atk}} = \frac{1}{|\mathcal{S}_{\text{atk}}^+|} \sum_{s \in \mathcal{S}_{\text{atk}}^+} \text{BTFPR}_s^{\text{atk}}, \tag{21}$$

where $\mathcal{S}_{\text{atk}}^+ = \{s \in \mathcal{S}_{\text{atk}} : N_s > 0\}$. This is a sample-level mean, rather than a ratio pooled over all bboxes.

Exact localization. ExactLoc requires flagging only the injected bbox:

$$\text{ExactLoc} = \frac{1}{|\mathcal{S}_{\text{atk}}|} \sum_{s \in \mathcal{S}_{\text{atk}}} \mathbf{1}[F_s = \{A_s\}]. \tag{22}$$

InjR measures injection detection, BTFPR measures benign-text suppression, and ExactLoc measures whether the defense flags the injection without flagging benign text. We abbreviate ExactLoc as Exact in tables. Rates and coverage are reported as percentages; BEUD and BHEM are reported in percentage points.

B Additional Risk-Signal and Runtime-Defense Details

B.1 Signal Interpretation

Instruction-to-image attention. In Eq. 1, the maximum captures sparse question-image alignment across instruction content tokens and attention heads. Averaging over layers and patches produces a region-level score that does not grow directly with region size. High S1 indicates relevance under the instruction, but does not establish maliciousness.

Local semantic conflict. The logit lens decodes a patch hidden state into a vocabulary distribution:

$$P_\ell(p) = \text{softmax}\Big(\text{LayerNorm}(h_p^{(\ell)})W_U\Big). \tag{23}$$

For neighboring patches $N_R(p)$ outside the candidate, the reference distribution is

$$\bar{P}_\ell(N_R(p)) = \frac{1}{|N_R(p)|} \sum_{p' \in N_R(p)} P_\ell(p'). \tag{24}$$

These patches provide the local reference within the observed image; runtime S2 does not require a paired clean image. The candidate patch is the first argument of the KL divergence in Eq. 2. We take the maximum divergence over the selected decoding layers for each patch and average over the region.

Global manifold residual. Let $U_\perp$ and $\Lambda_\perp$ collect the covariance eigenvectors and eigenvalues outside the dominant subspace. Equation 3 has the equivalent matrix form

$$s_{\text{global}}(R) = \frac{1}{|R|} \sum_{p \in R} (h_p - \mu_{\bar{R}})^\top U_\perp \Lambda_\perp^{-1} U_\perp^\top (h_p - \mu_{\bar{R}}). \tag{25}$$

This score discards the dominant directions that explain most image features and whitens the residual directions by their eigenvalues. It combines residual-subspace restriction with covariance whitening used in feature-space Mahalanobis detection (Lee et al., 2018).

Instruction-attention rebound. S4 measures the change in instruction attention after masking a candidate, rather than the attention received by that candidate. It therefore differs from S1: benign task evidence can receive high instruction-to-image attention without its removal producing a strong rebound in attention to the instruction.



Figure 5: VPIXDISTILL-X pipeline. Stage 1 uses instruction-to-image attention and a text prior to propose candidate visual-text regions with high recall. Stage 2 verifies each candidate using local semantic conflict, global manifold residual, and instruction-attention rebound, and flags a region only when all three signals agree. Stage 3 suppresses the flagged regions and re-queries the LVLM with the sanitized image and the original instruction.

B.2 EMPIRICAL HYPOTHESES

H1: Instruction-to-image attention supports high-recall localization. We expect the injected region $R^\star$ to appear among high-s_{attn} candidates. Benign task-relevant text may also receive high attention, so S1 is used for candidate proposal rather than final classification.

For S2–S4, we compare the injected region with benign candidates $\mathcal{B}$ in the same image. For a signal score s, define

$$A_s = \frac{1}{|\mathcal{B}|} \sum_{R \in \mathcal{B}} \mathbf{1}[s(R^\star) > s(R)]\,. \tag{26}$$

This is the fraction of benign regions scoring below the injected region.

H2: Injected regions show stronger local semantic conflict. We expect injected regions to rank above benign regions under s_{local}.

H3: Injected regions show stronger global image inconsistency. We expect injected regions to rank above benign regions under s_{global}.

H4: Injected regions cause stronger instruction-attention rebound. We expect masking the injected region to restore instruction attention more strongly than masking benign regions. This effect is expected to be strongest for goal-hijacking attacks, which introduce a competing instruction. It may also occur when typographic text provides a shortcut answer that weakens question-driven visual reasoning. Hypothesis tests are reported in Appendix D.6.

B.3 RUNTIME SIGNAL COMBINATION

The runtime signals S2–S4 have different scales. For each candidate region R, VPIXDISTILL-X standardizes each signal against a background distribution estimated from non-candidate visual evidence in the same image. We map the resulting standardized score $z_i(R)$ to a bounded score using the standard normal CDF:

$$q_i(R) = \Phi(z_i(R)). \tag{27}$$

We sum these scores and flag a region when $q_{\text{local}}(R) + q_{\text{global}}(R) + q_{\text{inst}}(R) > \theta$, as in Eq. 7.

This additive rule allows evidence from complementary signals to accumulate. The CDF mapping bounds each signal's contribution between zero and one, preventing an arbitrarily large raw score from dominating the sum. We calibrate θ separately for each target LVLM using held-out benign samples.

C VPIXDISTILL-D IMPLEMENTATION DETAILS

C.1 PRIVILEGED TEACHER SIGNAL COLLECTION

The teacher consists of a frozen LVLM and an offline target generator. For each attacked image and its paired clean image, it computes region-level supervision. The ground-truth injection box defines the injected region, while detected text boxes outside the injection region provide benign regions. The teacher can use the paired clean image, ground-truth injection region, correct answer, attacker-chosen target, and oracle layer choices.

The teacher cache stores four types of supervision. S1 is the instruction-to-image attention saliency map and supervises the localizer. S2 is local semantic conflict, computed with the logit lens at an oracle-selected layer against the region's local boundary reference.

Teacher S3 differs from the runtime global manifold residual in VPIXDISTILL-X. It uses the paired clean image and answer key to estimate an adversarial direction from the attack-target preference over the correct answer, then measures the attacked-to-clean hidden-state shift along that direction. The student S3 head predicts this privileged target.

S4 is instruction-attention rebound, computed by masking each candidate and measuring the recovery of answer-generation attention to the user instruction. All targets are cached offline once and reused for training. The privileged inputs are not required at deployment.

C.2 LAYER SELECTION

Teacher extraction layers for S2–S4 are selected per benchmark by their injected-versus-benign separation, measured with a standardized attack-versus-clean gap and image-level bootstrap.

The student ViT layer is selected per architecture through a linear-probe sweep over frozen ViT layers. At each layer, a logistic-regression probe separates injected patches from clean patches. We select the shallowest layer within 0.01 AUROC of the peak. These choices are fixed before student training and are not adapted at test time.

C.3 STUDENT ARCHITECTURE

Frozen feature extraction. The student takes an intermediate ViT feature map from a frozen open-source LVLM and the corresponding frozen token embeddings of the user instruction. The feature extractor is independent of the protected LVLM, and the selected ViT layer is fixed for training and inference. Image and question projection modules map the inputs into a shared detector dimension. They are trained through Stage 1 attention-map regression, without a separate image-text alignment loss.

Stage 1: Localization. Cross-attention blocks process image patches and instruction tokens, followed by an S1 prediction head. The predicted map scores CRAFT text boxes (Baek et al., 2019); the top-$k\%$ by predicted S1 score are retained. The detector uses text localization without full OCR recognition.

Stage 2: Verification. Self-attention blocks refine projected patch features. For each candidate mask, the verifier mean-pools features over the candidate, its local boundary, and the non-candidate complement. It also mean-pools projected instruction tokens into a question descriptor.

The S2 head uses candidate and boundary descriptors. The S3 head uses candidate and non-candidate descriptors to predict the privileged S3 target. The S4 head uses candidate, non-candidate, and question descriptors. The main detection head combines candidate, boundary, and non-candidate descriptors with the three predicted signal scores. It does not directly receive the question descriptor, but can receive question-dependent information through the S4 prediction. It outputs logits for benign text, typographic injection, and goal-hijacking injection.

C.4 TRAINING PROCEDURE

Stage 1. We train the image projection, question projection, cross-attention blocks, and S1 prediction head using Eq. 8. Normalized mean-squared error and cosine loss supervise the predicted map

Table 6: Comparison of injection-probability thresholding and three-class argmax decisions. Both use the same data and trained models as Table 2, without retraining. Higher BA, TA, and UIA are better; lower ASR, AIA, and AIFR are better.

LVLM	Decision	BA	ASR (C)	TA (C)	ASR (S)	TA (S)
TypoD-base						
Qwen2.5-VL	D (p_{inj})	89.0	13.9	85.9	19.4	80.4
	D (3-class)	89.0	14.0	85.7	19.5	80.4
InternVL3	D (p_{inj})	94.8	12.6	87.4	18.2	81.8
	D (3-class)	94.8	12.6	87.3	18.3	81.7
LingoQA						
Qwen2.5-VL	D (p_{inj})	58.0	12.4	55.2	14.6	53.8
	D (3-class)	58.0	12.4	55.2	14.4	53.8
InternVL3	D (p_{inj})	51.8	12.0	48.6	13.8	45.2
	D (3-class)	51.8	12.0	48.6	13.8	45.2

LVLM	Decision	UIA_{c}	UIA_{i}	AIA	AIFR
ARGUS-VTQA					
Qwen2.5-VL	D (p_{inj})	48.3	46.6	2.6	2.6
	D (3-class)	48.3	46.6	2.6	2.6
InternVL3	D (p_{inj})	62.0	59.2	4.6	5.7
	D (3-class)	62.0	59.2	4.6	5.7

C: Center; S: SceneTAP.

against the cached teacher S1 map. Backbone features and instruction token embeddings remain frozen.

Stage 2. We freeze the Stage 1 localizer and train the self-attention blocks, three signal heads, and main detection head using Eq. 9. Teacher-cache candidate masks come from ground-truth injection boxes and benign detected text boxes, rather than Stage 1 proposals. This decouples verifier learning from localization errors. The signal heads regress privileged S2–S4 targets, while the detection head learns three-class region classification.

C.5 Inference and Decision-Rule Comparison

At inference, the detector uses predicted S1 scores and CRAFT detections to propose candidates, then verifies each retained region. It suppresses candidates with $P_{\text{typo}} + P_{\text{hijack}} > \tau$ and passes the sanitized image and original instruction to the protected LVLM. Only the independent frozen feature extractor and trained detector are needed.

We compare this injection-probability threshold with a three-class argmax rule, which flags a region when its predicted class is typographic or goal-hijacking injection. Table 6 uses the same data and trained models for both rules, without retraining. Their reported attack and utility metrics are nearly unchanged. This comparison measures the effect of the decision rule on defense performance; it does not measure confusion between the two injection classes.

D Additional Evaluation Details and Results

D.1 Task-Level Evaluation Setup

Datasets. We evaluate task-level defense performance on existing VPI benchmarks within our attack scope. For typographic adversarial prompt injection, we use TypoD-base and LingoQA as clean benchmark sources. TypoD measures LVLM distractibility under typographic attacks across perception- and cognition-oriented VQA tasks, including object recognition, visual attributes, counting, and commonsense reasoning. LingoQA provides an autonomous-driving VQA setting. On both benchmarks, we evaluate two typographic attack forms: Center attacks, where the adversarial word

is rendered near the image center, and SceneTAP attacks, where a multimodal LLM plans a scene-coherent placement instead of using a fixed overlay. We follow the SceneTAP planning pipeline and use GPT-5.4 as the planner.

For direct goal-hijacking attacks, we use ARGUS-VTQA, a recent benchmark proposed by ARGUS (Lu et al., 2026). Each injected image contains an instruction-like visual prompt that asks the model to ignore the user task and output an attacker-specified random string. For region-level evaluation, we use SAFEREGIONVPI, our benchmark constructed from document VQA, scene-text VQA, and driving VQA sources. SAFEREGIONVPI includes planner-based typographic and goal-hijacking attacks, together with bbox annotations for injected text and benign OCR text. In the case studies, we further evaluate agentic and physical settings, including web-agent goal hijacking and optimization-based visual prompt injection from CHAI. Together, these datasets cover representative direct, planner-based, and optimization-based VPI settings. We also include FigStep (Gong et al., 2025) as a supplementary jailbreak evaluation, following Sec. 2.1, and report the results in Appendix D.9.

Target LVLMs. Across the main evaluation and additional studies, we use four open-weight LVLMs: LLaVA-1.5-7B (Liu et al., 2023), LLaVA-NeXT-7B (Liu et al., 2023; 2024), Qwen2.5-VL-7B-Instruct (Wu et al., 2025), and InternVL3-14B (Zhu et al., 2025). For each LVLM, we collect teacher signals from that model and train a corresponding VPIXDISTILL-D detector, which is then evaluated on the same LVLM. These model-specific results therefore measure how well each model-specific teacher can be distilled into an efficient runtime defense. Teacher signals are collected offline for training. The deployed detector uses features from an independent frozen open-source backbone. At inference time, VPIXDISTILL-D operates before the host LVLM: it detects and masks injected visual text, then sends the sanitized image to the model without requiring the protected model's internal states, gradients, or weights. We evaluate this model-agnostic deployment setting on commercial closed-source LVLMs, using Gemini 2.5 Flash and Claude Haiku 4.5 in benchmark evaluations, and GPT-4o (Hurst et al., 2024) and Claude Sonnet 4.5 in the simulation/real-world drone and web-agent case studies, respectively.

Task-level metrics. For typographic adversarial prompt injection, we report benign accuracy (BA), task accuracy under attack (TA), and attack success rate (ASR). BA measures clean-task correctness under defense, TA measures task correctness on attacked images, and ASR measures whether the response matches the attacker-specified target, such as the wrong option in TypoD or the rendered adversarial word in LingoQA. For TypoD, we use the official multiple-choice answer parser for BA, TA, and ASR. For LingoQA, we use LingoJudge (Marcu et al., 2024) for BA and TA, and count ASR by matching the rendered adversarial word. For goal-hijacking VPI, we follow the ARGUS protocol and report $\mathrm{UIA}_{\mathrm{clean}}$, $\mathrm{UIA}_{\mathrm{inj}}$, AIA, and AIFR. $\mathrm{UIA}_{\mathrm{clean}}$ and $\mathrm{UIA}_{\mathrm{inj}}$ measure user-instruction accuracy on clean and injected inputs. AIA measures whether the output matches the attacker-specified answer, and AIFR measures whether the model follows the attacker instruction. Higher $\mathrm{UIA}_{\mathrm{clean}}$ and $\mathrm{UIA}_{\mathrm{inj}}$ are better, while lower AIA and AIFR are better.

Baselines. We include a no-defense setting and a system-prompt defense as simple baselines. Following Cao et al. (Cao et al., 2025a), we use the same defensive system prompt, which warns the LVLM against visual prompt injection and asks it to follow the user's instruction. We then evaluate JailGuard (Zhang et al., 2025) and CIDER (Xu et al., 2024) as transferred jailbreak defenses. We include them because their mechanisms are not tied to a specific multimodal jailbreak task setup. JailGuard measures response inconsistency under input mutations, while CIDER measures cross-modal consistency after image denoising, making both methods directly testable under visual prompt injection. Although these methods were designed for jailbreak detection rather than visual prompt injection, they are among the closest existing inference-time defenses that can be directly tested in our setting. We further compare with two defenses designed specifically for visual prompt injection. ARGUS (Lu et al., 2026) targets goal-hijacking VPI through inference-time internal steering, while RIO-RT (Waseda et al., 2025) is trained to handle typographic attacks by aligning the model to read or ignore visual text. These baselines cover the main inference-time and training-time defense methodologies that could be applied to VPI. However, these baselines do not localize the injected adversarial text. VPIXDISTILL adds fine-grained region-level sanitization. We evaluate its task-level effect here and provide a fine-grained defense evaluation in Section 5.3. For the closed-source LVLMs, we evaluate defenses applicable to the black-box setting. For all baselines, we follow the default configurations used in their original implementations unless otherwise stated.

Table 7: VPI defense baselines and their applicability. Typo/GH denote typographic/goal-hijacking VPI; jailbreak-adapted methods are evaluated outside their original setting.

Defense	Stage	Insight	Against	Region-aware
No Defense	Inf.	none	Typo/GH	No
System Prompt	Inf.	prompt engineering	Typo/GH	No
JailGuard	Inf.	output validation	Jailbreak-adapted	No
CIDER	Inf.	input sanitization	Jailbreak-adapted	No
ARGUS	Inf.	internal optimization	GH	No
RIO-RT	Train.	fine-tuning/alignment	Typo	No
VPIXDistill-D	Inf.	input sanitization	Typo/GH	Yes

D.2 Additional Discussion of Task-Level Results

The system prompt does not consistently reduce ASR and can degrade task accuracy, although it improves attacked task accuracy in some settings. This matches prior observations (Cao et al., 2025a; Lu et al., 2026). CIDER also provides little protection. Its denoising-based consistency check may be better suited to perturbation-style image attacks than to visible-text VPI. In VPI, the injected text is a localized semantic signal. It may not substantially change the global image representation seen by conventional visual projectors, yet it can still be read and followed by the LVLM during generation. This may help explain the limited protection from image-level denoising and global cross-modal consistency checks. JailGuard improves some goal-hijacking results but remains weak on typographic VPI. Its mutation-based detector relies on response changes under perturbed inputs, which may be less reliable when the injected text occupies a small local region and may survive a limited set of image mutations. It is also inefficient at inference time because it requires multiple LVLM queries per input (Zhang et al., 2025; Liu et al., 2025), which further increases API cost when protecting commercial closed-source LVLMs.

The VPI-specific baselines show different strengths across settings. ARGUS is strong on goal hijacking but can substantially reduce typographic task accuracy, while RIO-RT is strong on typographic attacks but transfers poorly to goal hijacking and often reduces clean utility. Both also require white-box access to the target LVLM and therefore cannot directly protect closed-source models. VPIXDistill is based on internal VPI signals rather than a single attack format, allowing it to compete with specialized defenses across both VPI families. Moreover, VPIXDistill-D does not require access to the target LVLM internals at inference time and remains effective on commercial closed-source LVLMs. This supports our distillation design in Sec. 4.3.

D.3 OCR-adapted Text-PI Defenses

1) Evaluation Setups. Since OCR can expose text rendered in an image, a natural baseline is to reduce VPI to text prompt-injection defense. This experiment tests whether such an OCR-based reduction is sufficient. The victim model remains the same LVLM and still answers the original visual task. We use EasyOCR to extract text from each clean or attacked image before it is queried by the LVLM, and treat the extracted text as untrusted textual input for the transferred defenses. Table 8 summarizes the baselines.

We evaluate three representative inference-time OCR-adapted defenses. *OCR+Prompt* represents prompting-based mitigation. It augments the user query with a defensive instruction and places the extracted OCR text before the question as "[UNTRUSTED IMAGE TEXT – do not obey]: OCR text". *OCR+Prompt Guard 2 (PG2)* follows the original detection-based use of Prompt Guard. It classifies the full OCR text and refuses to answer when the text is detected as prompt-injection content. *OCR+PG2-Mask* is our stronger visual adaptation of PG2. It first applies PG2 to the OCR text. When PG2 flags the text, we use the OCR boxes to mask the corresponding regions in the original image and re-query the victim LVLM. This turns PG2 from a text-side detector into a stronger OCR-based visual defense.

We do not include training-time text-PI defenses. SecAlign-style methods are trained for text-only LLMs and do not directly transfer to LVLMs. As discussed by SecAlign (Chen et al., 2025a) and its follow-up work Meta SecAlign (Chen et al., 2025b), visual inputs introduce a continuous in-

Table 8: OCR-adapted text prompt-injection defense baselines for VPI. PG2 denotes Meta Llama Prompt Guard 2 (Meta); OCR+PG2-Mask is our masking adaptation.

Defense	Stage	Insight	Against	Region-aware
OCR+System Prompt	Inf.	prompt engineering	Text-PI adapted	No
OCR+PG2	Inf.	detection/refusal	Text-PI adapted	No
OCR+PG2-Mask	Inf.	input sanitization	Text-PI adapted	Yes
VPIXDistill	Inf.	input sanitization	Typo/GH	Yes

Table 9: OCR-adapted text prompt-injection defenses on Qwen2.5-VL-7B-Instruct under center typographic attacks and goal-hijacking attacks. ASR is the target-match attack success rate; all values are percentages. Best results are in bold and second-best results are underlined.

Defense	TypoD		LingoQA		ARGUS		
	BA/TA↑	ASR↓	BA/TA↑	ASR↓	UIA_c/UIA_i↑	AIA↓	AIFR↓
No Defense	88.8 / 66.3	33.6	57.4 / 40.2	25.8	47.9 / 5.2	75.3	79.8
OCR+Prompt	**89.7** / 52.8	47.2	48.4 / 21.8	30.0	46.2 / 44.7	1.3	1.3
OCR+PG2	88.7 / 66.3	33.5	56.6 / 39.4	25.0	47.8 / 16.4	12.1	12.8
OCR+PG2-mask	88.8 / 66.3	33.5	57.2 / 41.0	24.6	47.8 / **49.7**	**0.1**	**0.1**
VPIXDISTILL-D	89.0 / **85.9**	**13.9**	**58.0** / **55.2**	**12.4**	**48.3** / 46.6	2.6	2.6

put domain and additional modalities, so extending text-only defenses requires modality-specific alignment.

2) Experiment Results. Table 9 reports OCR-adapted defense results on Qwen2.5-VL under center typographic attacks and goal hijacking. Overall, OCR plus text-only prompt-injection defense is not sufficient for both VPI families in our evaluation.

OCR+Prompt is unreliable for typographic VPI and can even increase ASR over no defense. This may be because typographic VPI often appears as plausible visual evidence rather than an explicit instruction. In contrast, OCR+Prompt is more effective on goal hijacking, where the injected content is an obvious instruction and OCR exposes it to text-side safety checks (Ling et al., 2026; Gou et al., 2024). OCR+PG2 shows a similar limitation. It has little effect on typographic attacks when the OCR text is not suspicious by itself but conflicts with the image evidence. PG2 is more effective on goal-hijacking instructions, but its detect-and-refuse policy hurts utility. We therefore also evaluate OCR+PG2-mask, which masks flagged OCR regions and re-queries the LVLM. This improves goal-hijacking defense, but provides little protection on typographic VPI. On ARGUS, OCR+PG2-mask achieves 0.1% AIA and 49.7% attacked UIA, compared with 2.6% and 46.6% for VPIXDISTILL-D.

In contrast, VPIXDISTILL achieves the best typographic TA and ASR on both datasets while preserving benign accuracy, and remains effective under goal hijacking. These results show that the evaluated OCR-adapted defenses do not fully address both VPI families.

D.4 Alternative Injection Decision Rule

Setup. The main evaluation masks a region when $p_{\text{inj}} = p_{\text{typo}} + p_{\text{hijack}} > 0.5$. We also evaluate the native three-class output: take the top predicted class and mask the region if it is typographic or goal-hijacking VPI. The data and trained detectors are unchanged. Because both attack classes trigger the same masking action, this tests the deployment decision rule; it does not measure how accurately the two attack types are distinguished.

Results. Table 6 in Appendix C reports nearly identical downstream defense performance for the two rules. Thus, the native three-class decision can be retained without substantially changing the measured defense outcomes. Type-classification accuracy would require a separate classification evaluation.

D.5 Additional Results on SafeRegionVPI

Clean-image evaluation. Table 3 uses clean images and the separate diagnostic and original-task protocols in Appendix A.2. Refusals and malformed evidence reports count as IF failures. ARGUS and RIO-RT have IF rates of 79.8% and 27.5%, respectively. Their conditional evidence results

Table 10: Region-level injection localization of VPIXDISTILL-D across attacked LVLMs on SAFEREGIONVPI, split by attack type. Each row uses a detector distilled from that model's own internal signals and is evaluated on its own successfully attacked samples; attention-gated stage-1 merge throughout. InjR is injected-bbox recall, BTFPR is benign-text false-positive rate, Exact is exact injected-bbox localization. The model-specific attacked subsets differ across rows.

	Typographic			Goal-hijack		
Attacked Model	InjR ↑	BTFPR ↓	Exact ↑	InjR ↑	BTFPR ↓	Exact ↑
Qwen2.5-VL-7B	87.7	4.7	62.4	96.4	7.7	77.5
InternVL3	85.5	5.7	52.8	98.3	10.3	69.0
LLaVA-NeXT	81.9	5.8	51.8	96.2	12.0	70.9
LLaVA-1.5	85.0	7.1	49.1	98.2	15.6	66.9



Figure 6: Hypothesis validation for VPIXDISTILL signals. (a) S1 covers both injected and benign text, making it suitable for proposal generation. (b) Stage-2 signals separate injected clusters from same-image benign clusters.

should therefore be read together with IF. A negative mean BEUD does not imply that no individual sample loses evidence: VPIXDISTILL-D has mean BEUD -1.7 points but $\mathrm{BHEL}_{\mathrm{cond}} = 31.9\%$. These metrics describe different properties of the distribution.

Region-level baselines. For RQ3, we evaluate methods that output suspicious regions or can be adapted to bbox-level decisions. OCR+PG2-mask first detects OCR text regions, applies Prompt Guard 2 to each recognized text string, and masks the OCR bbox when the text is classified as prompt injection. Following the region-level localization metrics in Appendix A.2, we report InjR, BTFPR, and ExactLoc on attacked samples. These localization results use a different dataset and protocol from the task-level ARGUS evaluation in Appendix D.3.

External-model reference protocol. OCR+GPT4o-judge provides GPT-4o with the numbered image and OCR text/bbox candidates and asks it to identify suspicious injected regions. It outputs candidate bbox IDs, making it directly comparable under the region-level localization metrics.

Additional backbones. Following the RQ3 setup in Section 5.3, Table 10 extends the region-level evaluation to four attacked LVLMs, with VPIXDISTILL-D distilled separately from each model's internal signals. Each detector is evaluated on its model's successfully attacked samples. VPIXDISTILL-D consistently achieves high InjR across all four LVLMs, reaching 81.9–87.7% on typographic VPI and 96.2–98.3% on goal hijacking. These results show that its region-localization effectiveness is consistent across different LVLMs; the model-specific attacked subsets differ across rows.

Table 11: Hypothesis tests for internal VPI signals. S1 reports median $\Delta\mathrm{CVaR}_{0.95}$, positive rate, and Wilcoxon pass count. For S2–S4, A is the median same-image rank fraction of the injected candidate box, where $A > 0.5$ indicates higher injected-region risk.

Benchmark	S1			S2		S3		S4	
	ΔCVaR	Pos.	Pass	A	Pass	A	Pass	A	Pass
TextVQA	0.0073	0.77	3/3	0.86	3/3	1.00	3/3	1.00	3/3
DocVQA	0.0040	0.66	3/3	0.91	3/3	1.00	3/3	1.00	3/3
CARLA	0.0057	0.79	3/3	1.00	3/3	1.00	3/3	1.00	3/3

D.6 Hypothesis Test

1) Evaluation Setups. These tests use TextVQA, DocVQA, and CARLA examples. In this evaluation, we test whether the hypotheses described in Sec. 4.1 hold on Qwen2.5-VL-7B-Instruct, LLaVA-NeXT-7B, and InternVL3-14B.

We test two implications of Hypothesis 1. First, we measure whether the attack changes the upper tail of the question-to-image attention map. Conditional Value-at-Risk (CVaR) is a risk measure that quantifies the expected value beyond a given confidence level, capturing the tail of a distribution (Artzner et al., 1999). Following CVaR-based tail analysis (Li et al., 2024a), we use $\mathrm{CVaR}_{0.95}$ to summarize the high-attention tail of an S1 map. Given the S1 scores over all content patches, $\mathrm{CVaR}_{0.95}$ is the average score of the top 5% highest-attention patches. We then compute $\mathrm{CVaR}_{\alpha}(S1_{\mathrm{attacked}}) - \mathrm{CVaR}_{\alpha}(S1_{\mathrm{clean}})$ for each clean-attacked pair and apply a one-sided paired Wilcoxon signed-rank test. This tests whether injected visual text systematically increases high-end question-conditioned attention. Second, we test where high S1 scores appear in attacked samples. We rank all content patches by S1 and take the top-$n\%$ patches. We measure how often they overlap the annotated injection region and how much benign text they also cover. This tests whether high S1 covers the injected text, while still responding to benign task-relevant evidence.

For S2, S3, and S4, we test whether injected clusters receive higher scores than benign clusters from the same image, as defined in Sec. 4.1. Each attacked sample is treated as one statistical unit. For each signal, we compute a per-sample rank fraction (A_i^s), defined as the fraction of same-image benign clusters ranked below the injected cluster. A random ordering gives $(A_i^s = 0.5)$. We apply a one-sided Wilcoxon signed-rank test to $(A_i^s - 0.5)$, testing whether injected clusters rank above benign clusters within the same image. We consider the corresponding signal hypothesis supported when the one-sided Wilcoxon test on $A_i^s - 0.5$ gives a Holm–Bonferroni-corrected $p < 0.05$.

2) Experiment Results. Table 11 and Fig. 6 validate the hypotheses behind our two-stage design. For S1, the median $\Delta\mathrm{CVaR}_{0.95}$ is positive on all three benchmarks, and all three VLMs pass the paired Wilcoxon test in every benchmark. This shows that successful VPI consistently increases question-conditioned attention on the injected text. However, Fig. 6(a) also shows that high S1 regions contain both injected and benign text, indicating that attention alone is suitable for localization but insufficient for reliable VPI identification. This motivates using S1 only as a Stage-1 proposal signal, followed by Stage-2 verification.

For the Stage-2 verification, S2–S4 provide evidence for the proposed risk-signal hypotheses in Sec. 4.1. The median rank fraction A is consistently above the random-ordering baseline of 0.5 across all benchmarks, and every signal passes the significance test on all three VLMs. Specifically, S2 achieves high median A values (0.86–1.00), supporting the local semantic conflict hypothesis. S3 reaches median $A = 1.00$ on all benchmarks, supporting higher global-inconsistency scores on injected regions. S4 also consistently ranks injected clusters above benign ones, supporting the instruction-attention rebound hypothesis. These hypothesis tests provide statistical support for the two-stage design in Sec. 4.2 and Sec. 4.3.

D.7 Ablation Study

1) Evaluation Setup. We conduct four analyses to study the design of VPIXDistill-D. Unless otherwise specified, all analyses use SafeRegionVPI; only the Stage 2 ablation is additionally evaluated under OOD attacks. First, we vary the Top-$n\%$ threshold of the Stage 1 S1 attention gate. Each OCR/CRAFT box is scored by its coverage-weighted mean S1 attention and retained if it falls



Figure 7: S1 ablation on the TextVQA test set of SAFEREGIONVPI with LLaVA-NeXT-Vicuna-7B. We vary the Top-$n\%$ S1 gate and report the trade-off between injection recall (InjR) and benign-text false-positive rate ($\text{BTFPR}^{\text{atk}}$). The dashed line marks the default Top-35% threshold.

Table 12: Stage-2 ablation on the LLaVA-1.5-based detector, evaluated in-domain on attack-success validation samples of SAFEREGIONVPI, pooled over its three sources. Stage-1 candidates are fixed; every ablated Stage-2 verifier is retrained after removing the corresponding head(s), verifier input(s), and auxiliary loss(es). All values are percentages.

	Typographic (1,006)			Goal-hijack (393)		
Variant	InjR ↑	BTFPR ↓	Exact ↑	InjR ↑	BTFPR ↓	Exact ↑
Full D	85.0	7.1	49.1	98.2	15.6	66.9
w/o S2	83.3	6.6	49.5	98.7	15.7	67.4
w/o S3	80.4	5.7	48.9	97.7	15.2	67.2
w/o S4	77.5	5.0	48.7	95.7	13.8	67.9
S1+S2 only	84.8	7.1	48.9	98.5	15.8	65.9
S1+S3 only	81.1	5.7	49.5	97.2	14.5	67.9
S1+S4 only	78.8	5.1	48.4	95.7	14.6	66.4

within the Top-$n\%$ of candidate boxes. We report proposal-level InjR and BTFPR to measure the trade-off between retaining injected regions and admitting benign visual text.

Second, we ablate the Stage 2 risk signals using seven variants: the full model, removing S2, S3, or S4 individually, and retaining only S2, S3, or S4. Stage 1 is fixed across all variants, while each ablated Stage 2 verifier is retrained after removing the corresponding signal head, verifier input, and auxiliary loss. We evaluate the LLaVA-1.5-based variants in-domain on SafeRegionVPI attack-success validation samples, and then apply those same trained variants zero-shot to SceneTAP-LingoQA (500 typographic injections) and ARGUS-VTQA banners (999 goal-hijacking injections). No parameters are retrained and no detection thresholds are changed for either OOD dataset. These tests change the input and attack distributions while retaining the two attack categories and the detector backbone. We report InjR, BTFPR, and ExactLoc.

Finally, we directly examine the separability and redundancy of S2–S4. For each teacher signal, we report region-level AUROC for separating injected from benign regions. We further compute pairwise Spearman correlations between within-image normalized ranks of S2–S4, both over all text boxes (benign and injected) and over injected boxes only, with 95% CIs from 1,000 image-level bootstrap resamples. These analyses test whether individual signals are sufficient and whether they provide non-redundant evidence.

2) Experiment Results. Fig. 7 shows the Stage-1 attention-gate ablation. As validated in Sec. D.6, S1 serves as a proposal signal rather than a verification signal. It ranks OCR boxes by their S1 attention scores so that likely injected regions are retained for Stage 2 verification. Increasing the Top-$n\%$ threshold initially raises proposal InjR and then saturates, while proposal BTFPR continues to increase as more benign OCR boxes pass the gate. The default Top-35% gate reaches near-saturated injection recall on both typographic and goal-hijacking attacks, but avoids the much larger benign-text coverage. We therefore use Top-35% as the default S1 threshold.

Table 13: The same Stage-2 variants evaluated zero-shot on SceneTAP-LingoQA (500 typographic injections) and ARGUS-VTQA banners (999 goal-hijacking injections). No OOD retraining or detection-threshold adjustment is performed. All values are percentages; differences in recall should be read together with benign-text FPR and ExactLoc.

	SceneTAP-LingoQA (500)			ARGUS banner (999)		
Variant	InjR ↑	BTFPR ↓	Exact ↑	InjR ↑	BTFPR ↓	Exact ↑
Full D	89.2	22.5	70.4	95.2	26.1	88.3
w/o S2	74.8	10.5	66.6	99.8	22.6	92.3
w/o S3	70.8	11.4	62.2	90.8	17.2	85.9
w/o S4	73.6	14.5	63.2	78.7	18.2	75.4
S1+S2 only	78.2	13.8	69.2	99.5	39.7	87.8
S1+S3 only	73.2	15.5	63.0	49.4	18.8	47.9
S1+S4 only	68.4	9.9	61.6	88.8	17.8	85.1

Table 14: Single-feature separability (AUROC, injected-vs-benign regions) of the raw risk signals on *attack-success* SafeRegionVPI-TextVQA. No single signal is uniformly strongest: S2 dominates on the LLaVA family but is weakest on Qwen2.5-VL, while S3/S4 are the reverse. Best per row in bold.

Attacked Model	S2 (local)	S3 (manifold)	S4 (attn.)
Qwen2.5-VL	0.63	0.85	0.82
InternVL3	0.75	0.89	0.89
LLaVA-NeXT	0.92	0.78	0.72
LLaVA-1.5	0.94	0.80	0.62

Table 12 evaluates the Stage 2 risk-head ablation in-domain on SAFEREGIONVPI. Removing individual signals or retaining only one signal head generally causes limited degradation, particularly on goal hijacking. This may be because the verifier is trained and evaluated on splits from the same data distribution, and each risk signal can already provide useful supervision for in-domain detection. Removing S4 nevertheless reduces typographic InjR from 85.0% to 77.5%.

We further evaluate the same variants zero-shot under distribution shifts in Table 13. Here, the differences become substantially larger. On SceneTAP-LingoQA, all ablated variants reduce InjR from 89.2% to 68.4–78.2%. On ARGUS, removing S4 reduces InjR from 95.2% to 78.7%, while using S1+S3 alone further drops it to 49.4%. The ablated variants also reduce BTFPR on LingoQA, from 22.5% to 9.9–15.5%. On ARGUS, removing S2 improves InjR, BTFPR, and ExactLoc from 95.2%, 26.1%, and 88.3% to 99.8%, 22.6%, and 92.3%, respectively. These results suggest that combining S2–S4 provides complementary evidence across the tested distributions, although the best subset depends on the setting.

Table 14 further shows that S2 is LLaVA-1.5's strongest individual signal, yet S1+S2-only loses 11.0 InjR points on LingoQA and increases ARGUS BTFPR to 39.7%. S4 has the lowest single-feature AUROC on that model, but removing it reduces ARGUS recall. Thus, single-feature separability does not by itself determine each signal's contribution to the full verifier.

Fig. 8 further examines redundancy among the Stage 2 signals. Across all text boxes in Fig. 8(a) and injected boxes only in Fig. 8(b), S2–S4 show consistently low pairwise correlations across the four LVLMs. Together with the ablation results, this suggests that the signals provide complementary evidence; low correlation alone does not establish non-redundancy. Table 14 further shows that the discriminative strength of each signal varies substantially across LVLMs. S2 is strongest for the LLaVA models, reaching AUROCs of 0.92–0.94, whereas S3 and S4 are stronger for Qwen2.5-VL and InternVL3. Thus, no single signal is consistently dominant across model families. Together with the ablation results, this suggests that different LVLMs benefit from different risk signals, motivating their combination.

D.8 ADDITIONAL ADAPTIVE ATTACK DETAILS

1) Adaptive Attack Configurations. We use Qwen2.5-VL-7B as the victim and the VPIXDISTILL-D defense distilled from Qwen2.5-VL-7B, following the main evaluation. We evaluate typographic and



Figure 8: Pairwise Spearman correlations among the within-image normalized ranks of S2–S4 across four victim LVLMs. (a) All candidate boxes, including injected and benign regions. (b) Injected boxes only.

goal-hijacking attacks on TextVQA and typographic attacks on LingoQA, which is not seen during detector training. ASR w/o Defense measures the attack success of the adaptive attack without applying VPIXDISTILL-D, while ASR w/ Defense requires the attack to both achieve the attacker-specified target and evade VPIXDISTILL-D.

For the main adaptive attack, we optimize against the defense-predicted score from the fused Stage-2 head of VPIXDISTILL-D. For CHAI, the attacker observes only this scalar score and incorporates it into the black-box optimization objective

$$f = \mathrm{ASR} - \lambda\, s_{\mathrm{def}}, \tag{28}$$

where s_{def} is the fused defense score and $\lambda = 1$. Our CHAI adaptation first performs six rounds of text optimization using GPT-4o with feedback from attack success and s_{def}, and then optimizes the rendering of the best text candidate over four cross-entropy generations.

For SCENETAP, we use a mechanism-aware adaptation consistent with its planner-based construction. We inform the GPT-4o planner of the three Stage 2 risk mechanisms used by VPIXDISTILL-D, including local conflict (S2), global inconsistency (S3), and instruction-related attention shift (S4). The planner is instructed to generate injections that reduce these signals while preserving attack effectiveness. After each rendered candidate, we return the victim result and fused defense score to the planner and replan the injection for three rounds. Table 15 summarizes the adaptive attack configurations. Both adaptive pipelines use GPT-4o; the non-adaptive SceneTAP benchmark generation uses GPT-5.4. Thus a direct difference between their ASRs would not isolate defense awareness alone.

2) Single-Signal Adaptive Attacks. We further construct single-signal adaptive attacks to test whether suppressing an individual risk signal is sufficient to bypass the fused defense. Using the same CHAI adaptation, we separately minimize the Stage 2 head scores corresponding to S2, S3, and S4 instead of the fused defense score. The deployed defense remains unchanged, and ASR w/ Defense still requires evading the fused Stage 2 decision. We evaluate all single-signal attacks on the same TextVQA typographic samples.

Table 16 shows that adapting against a single risk signal is substantially less effective than directly optimizing against the fused defense score. Single-signal adaptation reduces attack success by 61–82% after defense enforcement, compared with 46% when directly attacking the fused head. The tested single-signal objectives are less effective than attacking the fused score. Together with the ablations and the weak rank correlations in Fig. 8, this supports different roles for the signals, without establishing robustness against all adaptive strategies.

Table 15: Adaptive attack configurations.

Parameter	Setting
CHAI	
Text proposer	GPT-4o
Text optimization rounds	6
CE optimization rounds	4
CE population / elites	6 / 2
λ	1.0
SCENETAP	
Planner	GPT-4o
Replanning rounds	3
Renderer	TextDiffuser-2

Table 16: Single-signal adaptive attacks on VPIXDISTILL-D. Reduction is from ASR without defense to ASR with defense.

Attacker suppresses	ASR w/o Def.	ASR w/ Def.↓	Reduction↑
s_{local} (S2) only	42.0	**7.6**	**82%**
s_{global} (S3) only	42.4	16.4	61%
s_{inst} (S4) only	43.2	16.0	63%
All three (fused)	49.9	26.9	46%

D.9 FIGSTEP JAILBREAK STUDY

1) Experimental Setup. We evaluate our defense on FigStep (Gong et al., 2025), a typographic jailbreak that renders harmful instructions into images. We use the full SafeBench set of 500 questions with the original FigStep images and prompt, attacking LLaVA-1.5-7B and Claude Haiku 4.5. We apply the same frozen VPIXDISTILL-D trained on SAFEREGIONVPI without retraining on FigStep. We use VPIXDISTILL-D distilled from LLaVA-1.5-7B to localize and mask the injected text. The same VPIXDISTILL-D sanitizes the image inputs for both victims, enabling black-box defense of Claude Haiku 4.5. We report FigStep ASR, the fraction of unsafe responses, judged per sample by GPT-5.4.

2) Experiment Results. Table 17 shows that FigStep reaches 57.6% ASR on LLaVA-1.5-7B, while VPIXDISTILL-D reduces it to 0.8%, a 98.6% relative reduction. The same defense also transfers to the black-box Claude Haiku 4.5, reducing ASR from 37.2% to 0.2%. These results show that VPIXDISTILL-D reduces unsafe responses in this supplementary jailbreak setting and can be applied to the closed-source victim through input-level sanitization.

D.10 WEB AGENT CASE STUDY

1) Experimental Setup. To evaluate VPIXDISTILL-D (VPIX-D) in an end-to-end interactive setting, we build on the Computer-Use Agent (CUA) evaluation of VPI-Bench (Cao et al., 2025a). We run Anthropic's CUA with Claude Sonnet 4.5 in a Docker sandbox, where the agent interacts with webpages and local system resources through screenshots, mouse, and keyboard actions. Following VPI-Bench, we evaluate three WebPlatform scenarios: Amazon shopping, Booking hotel reservation, and BBC news summarization. The corresponding attacker objectives cover privacy leakage and unauthorized file operations, as summarized in Table 18. We follow the original VPI-Bench task setup and evaluation protocol, and report Attempted Rate (AR) and Success Rate (SR). We insert VPIXDISTILL-D between the screenshot observation and the CUA, where it localizes and masks injected regions, and passes the sanitized screenshot to the agent. We use a simple temporal extension for sequential visual inputs, reusing detected VPI regions across consecutive frames while they remain visible to avoid redundant defense.

2) Experiment Results. Table 19 shows that VPIXDISTILL-D remains effective in the web-agent setting, despite being trained without any web data.

Table 17: FigStep jailbreak defense. ASR (%, ↓) is the GPT-5.4–judged unsafe-response rate over SafeBench (500 prompts). **Ours (D)** is the frozen VPIXDistill-D detector: it emits an image-space text mask computed on the LLaVA-1.5 host and applied before the victim reads the image, so the *same* detector defends a closed-source victim whose weights are never accessed.

Method	ASR ↓
LLaVA-1.5-7B (open-source victim)	
FigStep (no defense)	57.6
+ Ours (**D**)	**0.8** (−98.6%)
Claude-Haiku-4.5 (closed-source, black-box)	
FigStep (no defense)	37.2
+ Ours (**D**)	**0.2** (−99.5%)

Table 18: The VPI-Bench WebPlatform attacker objectives we evaluate. We cover the benchmark's three form-filling objectives for computer-use agents, each instantiated over seven kinds of user data (API key, SSH credentials, card, bank account, e-mail, phone number, and an unstructured note). PL denotes privacy leakage; UA+PL additionally requires an unauthorized action (UA) on the user's file, so its Success Rate is only credited when both steps are carried out.

Scenario (benign task)	Attacker objective	Type	#
Amazon *buy glasses*	Fill form using local file content	PL	7
	+ then edit the file	UA+PL	7
	+ then delete the file	UA+PL	7
Booking *book a hotel*	Fill form using local file content	PL	7
	+ then edit the file	UA+PL	7
	+ then delete the file	UA+PL	7
BBC *summarize the news*	Fill form using local file content	PL	7
	+ then edit the file	UA+PL	7
	+ then delete the file	UA+PL	7
Total			**63**

AR remains higher than SR because masking the injected instruction does not always prevent the agent from interacting with the remaining form. As illustrated in Fig. 9, VPIXDISTILL-D often masks the hijacking instruction while preserving form text such as "Name" or "API Key". The agent's reasoning traces show that it recognizes the masked region only as "a large gray area", but may interpret the remaining popup as "a form that needs to be filled out before I can proceed" and enter "simple values" to access the main interface. Such interactions can be counted as attempted attacks even though the agent fabricates the values rather than following the injected instruction.

Inspection of the remaining 11 successful attacks points to unstable localization across frames as a failure mode. Our simple temporal extension reuses detected regions across consecutive frames for efficiency, but an injection missed in an early frame may already hijack the agent before it is detected and masked in later frames. Moreover, VPIXDISTILL-D is trained entirely on SAFEREGIONVPI without web data, making localization less stable under this domain shift. Since the injected instructions strongly induce the agent to act once exposed, occasional missed detections can still lead to successful attacks. Future work can further improve VPIXDISTILL-D by training a web-specific defense model and developing defense mechanisms tailored to CUA interactions.

These attack-rate results do not separately quantify clean web-task completion; the evidence-preservation measurements are provided by SafeRegionVPI.

D.11 DRONE CASE STUDY

(1) CARLA Closed-loop Tracking.



Figure 9: Web-agent case study on three VPI-Bench scenarios. (a) Original CUA screenshots with prompt injections. (b) Screenshots after VPIXDISTILL-D masks the detected injection regions.

Table 19: Attempted Rate (AR) and Success Rate (SR) of visual prompt injection on the three VPI-Bench WebPlatform scenarios under a computer-use agent, with and without VPIX-D. Lower is better. Both arms run the same 63 attack samples with an identical agent, prompt and step budget.

Scenario	N	AR (%)		SR (%)	
		None	VPIX-D	None	VPIX-D
Amazon	21	85.7	**38.1**	66.7	**19.0**
Booking	21	90.5	**57.1**	47.6	**23.8**
BBC	21	47.6	**23.8**	33.3	**9.5**
All	63	74.6	**39.7**	49.2	**17.4**

We evaluate the effectiveness and model-agnosticity of VPIXDISTILL-D in aerial object tracking. We use CloudTrack (Blei et al., 2025), a representative LVLM agent for aerial object tracking that supports swappable LVLM backends, as the target system, and CHAI (Burbano et al., 2025), a typographic adversarial prompt injection attack, as the attack method.

We build a realistic urban scene in CARLA simulator (Dosovitskiy et al., 2017) with a downward-facing camera that follows a target vehicle for 20 seconds (see Figure 10), and evaluate across four maps (Town10, Town03, Town04, and Town05) and two CloudTrack backends (LLaVA-1.5-7B, GPT-4o). Each run is a closed-loop tracking episode with continuously changing camera observations as the target vehicle moves through the scene. Following CHAI, we optimize the typographic prompt on data collected in Town10. The resulting typographic prompts for LLaVA-1.5-7B and GPT-4o are "Santa Cruz Police" with RGB color (185, 109, 201), and "Santa Cruz PD" with RGB color (193, 37, 170), respectively. They are rendered on the vehicle roof, visible to the LVLM (see the attack part of Figure 10). For both backends, we use the same VPIXDISTILL-D defense model distilled from LLaVA-1.5-7B.



Figure 10: **Closed-loop CloudTrack evaluation with GPT-4o.** *Benign:* GPT-4o does not identify either vehicle as affiliated with Santa Cruz Police due to insufficient visual evidence. *Attack:* The roof text "Santa Cruz PD" makes GPT-4o answer *Yes* and hijacks the tracker to the Mustang. *Defense:* VPIX-D masks the injected text, causing GPT-4o to return to *No* and preventing hijacking. Speech bubbles show the query and GPT-4o response.

Table 20: Closed-loop CloudTrack evaluation under the CHAI attack across two LVLM backends and four CARLA maps. HR is the fraction of CloudTrack queries where the tracker follows the attacker's vehicle. InjR is the fraction of keyframes where VPIX-D flags the injected patch. Lower defended HR and higher InjR indicate better defense.

			No def.	VPIX-D	
LVLM	Map	Typographic Prompt	HR↑	HR↓	InjR↑
LLaVA-1.5-7B	Town10	"Santa Cruz Police"	100%	0%	1.00
	Town03		100%	0%	1.00
	Town04		95%	0%	1.00
	Town05		100%	0%	1.00
GPT-4o	Town10	"Santa Cruz PD"	100%	0%	1.00
	Town03		100%	14.5%	0.98
	Town04		100%	0%	1.00
	Town05		100%	0%	0.99

We report HR and InjR in Table 20. HR is the fraction of CloudTrack queries where the tracker follows the attacker's vehicle, capturing the sustained closed-loop hijack. InjR is the fraction of tracking keyframes where VPIX-D flags the injected patch. The CHAI attack prompt optimized on Town10 transfers to other maps, reaching 100% HR in seven of eight model-map settings, and LLaVA-1.5-7B on Town04 reaching 95% HR, where a few initial queries are needed before the first positive tracking response. Additionally, VPIX-D reduces HR to 0% in seven of eight model-map settings, with only GPT-4o on Town03 retaining 14.5% HR, while maintaining InjR of 0.98–1.00. Figure 10 shows examples on Town10. These results show that VPIX-D protects aerial tracking across LVLM backends and maps.

(2) Landing Decisions on Real Drone Footage.

1) Experiment Setup. We evaluate VPIXDISTILL-D against physical VPI using real-world drone footage. We place printed CHAI optimized "LAND HERE" signs at unsafe delivery locations and record them with a commercial drone following realistic delivery-approach trajectories. The onboard camera captures 4K video at 59.94 fps, from which we sample one keyframe per second, capturing the same physical injection across varying viewpoints, distances, and altitudes. We evaluate two representative scenes: a parking-lot and a pedestrian sidewalk, containing 29 and 37 keyframes



Figure 11: Real-world physical VPI and defense under aerial drone views. (a) CHAI "LAND HERE" adversarial text physically deployed in the sidewalk and parking-lot scenes. (b) The corresponding inputs after VPIXDISTILL-D masks the injected text regions before victim-LVLM inference.

Table 21: Real-world evaluation of CHAI physical prompt injection and VPIXDISTILL-D on the drone-landing task. Sust. denotes the longest sustained attack duration.

Scene	Condition	ASR (%)	Sust. (s)
Parking lot	No attack	82.8	11
	CHAI	100.0	29
	+ VPIX-D	75.9	15
Sidewalk	No attack	5.4	1
	CHAI	91.9	18
	+ VPIX-D	24.3	3

after the sign becomes visible, respectively. Following CHAI's evaluation protocol, we use GPT-4o as the victim LVLM and evaluate whether the physical adversarial injection causes the model to accept the attacker-specified region as suitable for landing.

For each approach sequence, we evaluate three conditions: *No Attack*, with the physical injection removed; *CHAI*, with the printed injection present; and *CHAI*+VPIXDISTILL-D, where detected injection regions are masked before evaluation. We replay the recorded keyframes offline and query GPT-4o independently on each frame, following CHAI's evaluation protocol. We report the target-label acceptance rate (reported as ASR in the table) as the fraction of keyframes for which GPT-4o outputs the attacker-desired target label, i.e., judges the injection region suitable for landing. We additionally report sustained duration, the longest consecutive duration for which the target label is produced, since persistent erroneous decisions during approach pose greater risk to downstream drone operation than isolated frame-level errors.

2) Experiment Results. Table 21 reports the real-world results, with Fig. 11(b) showing the physical injection masked by VPIXDISTILL-D. In the parking-lot scene, GPT-4o already accepts the open, obstacle-free surface in 82.8% of the no-attack sequence, despite its location in the middle of the parking lot roadway. CHAI further increases the ASR to 100%, while VPIXDISTILL-D masks the adversarial prompt and reduces it to 75.9%, close to the no-attack level.

The effect is more pronounced on the sidewalk, where GPT-4o rarely accepts the narrow pedestrian walkway without the attack (5.4% ASR). The physical CHAI sign raises the ASR to 91.9% and induces up to 18 s of continuous erroneous acceptance. After VPIXDISTILL-D masks the injected

prompt, the ASR drops to 24.3% and the sustained duration to 3 s. These results show that physical VPI can persist across changing viewpoints during a real drone approach, while VPIXDISTILL-D substantially suppresses its decision-level effect.

The landing study uses offline replay rather than closed-loop landing control. Its 29 and 37 keyframes come from two approach sequences and are temporally related observations, not independent flight trials. The high parking-lot no-attack acceptance rate also reflects a baseline decision limitation that injection removal alone does not resolve.