BIOTRACEBENCH: EVALUATING COMPUTATIONAL EXECUTION AND EVIDENCE-BASED REASONING IN BIOMEDICAL RESEARCH

Anonymous authors
Paper under double-blind review

ABSTRACT

Assessing AI for biomedical research requires distinguishing the ability to execute computational analyses from the ability to interpret experimental evidence and synthesize scientific conclusions. We introduce BioTraceBench, a benchmark that evaluates these capabilities through three independently administered tasks: computational execution, local evidence interpretation, and study-level conclusion synthesis. The benchmark comprises 60 curated study entries and 1,061 local conclusion nodes spanning three biomedical research domains. Twenty-four domain researchers constructed structured nodes through schema-guided annotation and expert review, linking local conclusions to experimental designs, results, essential context, and source evidence. Task 1 requires models to execute bioinformatics analyses and produce verifiable computational artifacts. Task 2 provides 384 expert-reviewed, minimally sufficient evidence packages combining experimental figures or tables with essential textual context, from which models infer local conclusions. Task 3 requires models to integrate local conclusion nodes and study background into self-contained study-level conclusions. During construction, three senior doctoral researchers conducted a blinded review of all 60 entries to assess whether the supplied nodes support the target inference using domain knowledge. Each task separates model-visible inputs from evaluation references and uses task-specific scoring. Expert ratings additionally assess correspondence between Task 2 automated judgments and human assessments. Evaluation reveals remaining limitations in computational execution, local evidence interpretation, and study-level conclusion synthesis. The tiered Task 3 evaluation distinguishes recovery of core conclusions, preservation of appropriate inference scope, and citation of sufficient supporting nodes, showing that recovering a core conclusion does not necessarily satisfy the accompanying scope and support requirements. By relating task performance to explicit input conditions and scoring requirements, BioTraceBench provides a traceable basis for diagnosing specific capability gaps in biomedical AI and guiding model improvement.

1 INTRODUCTION

Evaluating scientific reasoning in biology requires specifying what information a model receives, which inference it must perform, and what evidence supports the expected conclusion. Computational execution, interpretation of local experimental evidence and synthesis of study-level conclusions impose different requirements. A benchmark must distinguish these requirements to make its scores interpretable.

A completed computation does not by itself establish a supported biological conclusion, and several plausible local conclusions do not automatically justify a study-level claim. Conversely, an incomplete conclusion may reflect missing information or an appropriate evidence boundary. Three questions guide our evaluation: what information does each task supply and which inference does it request; how do experts review the relation between task materials and target conclusions; and what does each automatic score measure or leave unassessed?

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

BioTraceBench evaluates computational execution, local evidence interpretation and study-level conclusion synthesis through separately specified inputs, expert-reviewed task construction and traceable reference-based evaluation. Task 1 requires executed analyses and generated artifacts. Task 2 asks models to infer a local conclusion from a minimally sufficient evidence package. Task 3 asks models to synthesize supplied local conclusions into a study-level main conclusion. Our contributions are a shared study-to-node representation with explicit input boundaries, expert review of the relation between materials and targets, and task-specific scores linked to reference evidence. These are tests of selected scientific reasoning tasks; reference agreement does not independently establish the validity of the underlying experiments.

2 Related Work

Execution benchmarks assess whether agents can carry out scientific workflows. BixBench3 (Koch et al., 2026) supplies research objectives, methodological guidance and raw data, and evaluates generated artifacts against references from published studies. Task 1 addresses a related execution objective, with explicit links between generated evidence, process metrics and conclusion credit.

Evidence-grounded benchmarks assess the reasoning supported by scientific materials. SciMMR (Li et al., 2026) connects claims, knowledge and visual evidence through argument graphs to evaluate evidence acquisition and integration. SciRigor (Liu et al., 2026) distinguishes artifact fidelity from the validity of relations along computational and visual support paths. BioTraceBench shares this concern with evidence and inference, and does not claim that evidence-grounded evaluation is itself new.

Our distinction is the joint organization of three evaluation targets within one study-to-node representation: producing computational results, interpreting supplied results and recovering study-level conclusions from local claims. Each target has its own visible inputs, reference information and scoring rule. This makes task performance interpretable without equating fluent synthesis with valid execution or treating reference agreement as independent experimental confirmation.

3 Benchmark Tasks

Figure 1 summarizes construction and three independently administered scientific reasoning tasks. Each task specifies its model-visible inputs, required output and reference-based scoring rule; performance is reported separately because these contracts differ.

3.1 Benchmark Construction

Two principal investigators jointly recommended 60 paper entries, with 20 in each Figure 1 group: cancer, spatial and single-cell research; brain, neuroscience and health; and systemic omics, genetics and methods. Selection considered innovation, data accessibility, executable bioinformatics workflows and traceable evidence. Construction involved 24 master's or doctoral students from basic medical sciences and infectious disease research units. The literature collection is expert curated, not randomly sampled.

The standard schema links research questions and node conclusions to experimental designs, results, essential textual context, scope and source-evidence locations. The corpus contains 1,061 nodes: 957 direct and 104 joint nodes. We retain 60 paper entries as the evaluation units.Task-specific views separate model-visible materials from private references.

Task 2 selects nodes whose target conclusions experts confirm are supported by experimental evidence together with essential textual context. These components form each item's minimally sufficient evidence package, defined relative to recovery of the complete target conclusion. Selection is at node level without paper quotas, yielding 384 items from 53 paper versions. Task 1 exposes computational task packages; Task 3 exposes local conclusions from one paper entry.

Stable identifiers, manifests and hashes connect task units to materials and references. Release checks cover schema validity, unique identifiers, resolvable references and material integrity. For Task 2, AI-assisted extraction of essential textual context is followed by item-by-item answerability



Figure 1: Overview of benchmark construction and independent task evaluation. (A) Literature resources, expert curation, and the study and node schema. (B) Task inputs, model operations, outputs, and private evaluation references. The three task rows represent computational execution, local evidence interpretation and study-level conclusion synthesis. For Task 2, experimental evidence and essential textual context together form the minimally sufficient evidence package. Evaluation references remain separate from model-visible inputs.

checking by three senior doctoral students in basic medical sciences, with node conclusions masked. This construction review checks whether the evidence package supports the target local conclusion.

Task 3 construction review. During benchmark construction, three senior doctoral researchers in basic medical sciences conducted a blinded review of all 60 study entries. The review assessed whether the supplied local conclusion nodes were sufficient to infer the study-level main conclusion using domain knowledge. This review addresses the relation between the supplied nodes and the target conclusion; it is distinct from the Task 2 expert scoring of model answers.

3.2 Task 1: Computational Execution

Task 1 contains 60 paper-level computational reproduction tasks, each with a public reproduction package and a private scoring package. Public materials specify methods, available data, questions and execution boundaries; private materials contain reference evidence and task-specific evaluators. Minimal readable regions stating benchmark answers are masked while computationally necessary methods and materials are retained.

The agent verifies inputs, prepares an environment, executes the analysis and submits explicit answers with generated evidence. Evidence records identify the artifact, exact locator, producing command, inputs and lineage, population, units and uncertainty. Validation checks question coverage, paths, artifact existence and report completeness. Missing data, inherited intermediates, substitute analyses and failures remain explicit; copied paper values do not substitute for execution.

The rubric allocates 25/45/30 points to engineering and resource evidence, computational process and scientific conclusion. Deterministic comparators assess numerical fidelity, rankings, trends and

artifact constraints; semantic judgments assess factual consistency, evidence grounding, coverage and scope. Three judge passes assign each semantic dimension 0–4; dimension-wise medians determine the semantic score. A zero factual or grounding median sets that score to zero. Inapplicable metrics are excluded.

Conclusion credit is gated by execution evidence. For a local conclusion q, the semantic score is multiplied by the weighted mean of supporting process scores; overall synthesis is multiplied by the preceding local-conclusion scores. Within each task, category scores combine weighted nodes; model scores then average task totals equally over the evaluated paper-level tasks. Appendix A specifies comparators, weights and audit records.

$$c_q = s_{\mathrm{sem},q} \frac{\sum_{p \in P(q)} w_p s_p}{\sum_{p \in P(q)} w_p}, \qquad c_{\mathrm{overall}} = s_{\mathrm{sem,overall}} \frac{\sum_{q \in Q} w_q c_q}{\sum_{q \in Q} w_q}. \tag{1}$$

3.3 Task 2: Local Evidence Interpretation

Each Task 2 item provides a minimally sufficient evidence package comprising experimental figures or tables and essential textual context. Sufficiency is defined with respect to the target local conclusion: the complete package supports that conclusion, whereas removing a required component leaves the supplied information insufficient to recover it in full. The textual context specifies the objects, comparisons and measurements needed to interpret the experimental evidence. Minimality concerns required material components, not each word, pixel or individual figure; reduced inputs may still support partial facts.

Each of the 384 items pairs a hidden reference conclusion with one to three experiment records. Essential textual context comprises two fields: Objects and comparisons, and Metrics and measurements. Of these items, 381 contain images and three contain tables; the collection contains 621 distinct image assets. Models receive the evidence package, not the reference conclusion, paper title, abstract, full text or separate figure captions.

A fixed English prompt requests supported conclusions, experiment references, brief evidence descriptions and limitations in JSON, or an explicit insufficient-evidence response. Programmatic validation checks identifiers, reference membership and status-dependent fields. The standard request contains no few-shot examples or explicit chain-of-thought instruction.

The judge sees the reference conclusion and submitted conclusion text with limitations, but not the raw figures/tables, brief evidence descriptions or experiment identifiers. It scores reference-based coverage, correctness, scope and quantitative/terminological accuracy. Direct verification of the cited experimental evidence and the validity of the underlying experiments are outside this score. Reference atoms receive weights 10 for core claims and 5 for supporting claims or limitations. The score combines coverage C, coverage-weighted correctness J, boundary b and quantitative/terminological accuracy q:

$$\begin{aligned} C &= \frac{\sum_i w_i c_i}{\sum_i w_i}, \qquad J = \frac{\sum_i w_i c_i r_i}{\sum_i w_i}, \\ S &= h\left[25C + 55(1-f)J + 15Cb + 5Cq\right]. \end{aligned} \tag{2}$$

For atom i, c_i and r_i are coverage and normalized correctness. Correctness becomes zero if coverage or any required object, comparison, direction or condition component is zero. The fatal-error flag f zeros the correctness component; h requires positive coverage of at least one substantive claim. Appendix B specifies normalization and rounding; Appendix D provides the prompts.

3.4 Task 3: Synthesis of Study Conclusions

Task 3 asks a model to recover a study's main conclusion from its local node conclusions and background. Domain knowledge is an allowed reasoning resource; the study-specific support is supplied through the nodes. The construction review in Section 3.1 assesses this node-to-conclusion relation across all 60 study entries. A single generation call produces three self-contained candidates ranked by plausibility. Each must explain the principal findings on its own; distributing complementary

findings across candidates cannot earn a joint match. In model evaluation, paper titles, DOIs and reference main conclusions are withheld.

Kimi, GLM and Qwen judge each candidate against the hidden reference. Core matching requires the central finding and indispensable relationships. Strict matching additionally requires appropriate scope and sufficient support from the full node set. An individual judge must endorse all three conditions jointly, and at least two judges must endorse that conjunction. Cited-support matching further requires support from the nodes actually cited by the candidate, under the same majority rule.

Strict Top-1 scores the first candidate. Strict Top-3, the primary metric, is 100 times the fraction of paper versions with any individually passing candidate. Core and cited-support Top-3 are secondary metrics. Each version has equal weight. These scores assess recovery of the reference conclusion under node-support requirements, not independent verification of the source experiments. The three candidates are generated together and do not constitute independent samples for a pass@3 estimator.

4 Data and Evaluation Protocol

All tasks separate answer-model inputs from evaluation references. Task 1 uses distinct public and private packages; Tasks 2 and 3 withhold their target conclusions. Models are evaluated within each task because model panels, generation contracts and score scales differ. Model source references and identifier conventions are given in Appendix E.

Task 2 uses frozen answers from six models and three judges: DeepSeek v4.1 Flash, Kimi K3 and MiniMax M3. Each judge has three planned repeats per answer. We average valid repeats within judge, available judges within item, and valid items within model; total and component scores use the same hierarchy:

$$\begin{aligned} \bar{S}_{mij} &= \frac{1}{|V_{mij}|} \sum_{r \in V_{mij}} S_{mijr}, \\ T_{mi} &= \frac{1}{|J_{mi}|} \sum_{j \in J_{mi}} \bar{S}_{mij}, \qquad P_m = \frac{1}{|I_m|} \sum_{i \in I_m} T_{mi}. \end{aligned} \tag{3}$$

Here m, i, j and r index answer models, items, judges and repeats. V, J and I contain valid repeats, available judges and valid items, respectively. Failed calls remain missing; rubric zeroes remain valid. Empty sets yield unavailable scores at that level. We report item coverage and a shared complete-judge sensitivity analysis. Primary 95% intervals use 10,000 item bootstrap resamples; within-paper dependence is not modeled by these intervals (Appendix B).

Three senior doctoral students in basic medical sciences independently scored model answers while blinded to the identities of the answer-generating models. They reviewed a constrained random subset of 320 nodes from 52 paper versions, one model answer per node. Each rated 150 answers, 25 per model: 20 answers were shared by all experts and each pair shared 30 additional answers. Reviewers saw reference conclusions and anonymously labelled answers, not raw figures/tables or machine scores. Four dimension ratings used levels 0/25/50/75/100 and weights 25/55/15/5.

Each judge is compared separately with experts using its valid-repeat mean. Two answers missing all MiniMax scores leave 318 answers and 448 reviews for common-judge comparisons. We report same-order agreement among answer pairs with unequal human totals, counting machine ties as nonconcordant, and answer-level Spearman correlations. Human-comparison intervals resample source paper versions 10,000 times, retaining within-version answers. Sampling and full statistics appear in Appendix C.

The authors froze the current Task 3 references and results as the final benchmark version. Five models each generated three candidates for all 60 paper versions, giving 300 outputs and 900 candidates with complete final scores. Generation used temperature 1 and a 16,384-token output limit. Inputs, references, prompts and shuffle seeds match across source runs; provider routes, internal thinking budgets and candidate collections differ. Appendix E reports these conditions and reference provenance.

Task 1 uses the 25 September 2026 scoring release: benchmark 1.1.0, evaluator 2.3.0, rubric 3.1 and judge prompt 2.2. Its semantic judging specification sets three passes, temperature 0, top-p 1 and a 4,096-token limit. Versions, hashes, submission identity and judge configuration are recorded in the evaluation fingerprint. The current execution evaluation covers a shared 15-task subset; reported means use 15 as the denominator. Unlaunched tasks are not assigned zero scores.

5 RESULTS

5.1 TASK 1 EXECUTION AND RESULT VALIDITY

We report Task 1 execution evaluation on 15 shared paper-level tasks, giving 60 model–task evaluations across DeepSeek 4.1, GLM 5.3, Kimi K3 and GPT-5.6 Sol (Table 1). Engineering implementation constraints limited coverage at the reporting cutoff; the remaining 45 tasks had not been launched and were not removed after failed runs.

Table 1: Task 1 execution evaluation on 15 shared paper-level tasks per model, comprising 60 model–task evaluations across four models. Mean, median and minimum–maximum are total scores out of 100. Engineering (Eng.), Process (Proc.) and Conclusion (Conc.) are mean normalized category scores expressed as percentages; their total-score weights are 25/45/30. Bold denotes the largest mean, median or category score across the four models. Values use the 25 September 2026 scoring release (benchmark 1.1.0, evaluator 2.3.0, rubric 3.1 and judge prompt 2.2).

Model	Mean	Median	Min–max	Eng. (%)	Proc. (%)	Conc. (%)
DeepSeek 4.1	39.38	33.69	10.90–73.25	32.47	45.77	35.56
GLM 5.3	41.91	41.80	11.67–68.20	38.56	46.65	**37.59**
Kimi K3	41.66	41.87	22.03–65.32	43.32	44.58	35.89
GPT-5.6 Sol	**43.24**	**42.35**	13.47–71.24	**44.11**	**47.08**	36.69

GPT-5.6 Sol had the highest observed mean total (43.24/100), followed by GLM 5.3 (41.91), Kimi K3 (41.66) and DeepSeek 4.1 (39.38). GPT-5.6 Sol also had the highest median (42.35), Engineering score (44.11%) and Process score (47.08%), whereas GLM 5.3 had the highest Conclusion score (37.59%). Total scores varied across tasks, with DeepSeek spanning 10.90–73.25. These descriptive summaries characterize the evaluated subset; they do not establish statistically reliable model differences or performance over the full 60-task collection.

5.2 TASK 2 INTERPRETATION AND SCIENTIFIC JUDGMENT

All six models retain scores for 384/384 items. Of 20,736 planned judge calls, 20,662 are valid and 74 are missing. Table 2 reports equal-judge, equal-item total scores and rubric components; Figure 2a,b shows overall and normalized component profiles.

Claude Fable 5.1 has the highest mean score (64.24), followed by GPT-5.6 Sol (55.37), MiniMax M3 (53.91), Qwen 3.8 Max (52.38), Kimi K3 (51.03) and DeepSeek v4.1 Flash (49.22). The order is unchanged on the 380 shared items with all three judges available for every model (Appendix B). These are comparisons under the fixed rubric and judge panel, not significance claims for adjacent ranks.

Removing all figures and tables created an insufficient-input condition under the benchmark's evidence-package definition. Essential textual context, prompts, model versions and generation settings remained unchanged. Models returned insufficient-evidence responses in 2,300 of 2,304 outputs (99.83%) across six models and 384 distinct items. Under the evaluated prompt, this intervention therefore elicited near-universal abstention when required experimental evidence was unavailable. Kimi K3 and Claude Fable 5.1 each submitted two answers; the authors report that manual review found all four unrelated to the reference conclusions. This result does not by itself establish correct evidence use under full input (Appendix B).

Table 2: Task 2 performance using equal available-judge weights within each item. Valid items/planned reports the model-score denominator; item coverage is 100% for every model. Score is the equal-item mean, with a 95% percentile interval from 10,000 item bootstrap resamples. Components are points with maxima 25/55/15/5. Missing scoring calls are excluded at the corresponding level, whereas rubric zeroes are valid. Historical one-pass Claude judging is excluded.

Answer model	Items	Score [95% CI]	Coverage	Correctness	Boundary	Quant./terms
Claude Fable 5.1	384/384	64.24 [61.28, 67.07]	16.68	34.48	9.82	3.29
DeepSeek v4.1 Flash	384/384	49.22 [46.44, 51.96]	13.02	25.99	7.71	2.57
GPT-5.6 Sol	384/384	55.37 [52.49, 58.19]	14.74	29.16	8.69	2.87
Kimi K3	384/384	51.03 [47.86, 54.19]	13.93	26.30	8.15	2.71
MiniMax M3	384/384	53.91 [51.10, 56.76]	14.55	28.11	8.41	2.85
Qwen 3.8 Max	384/384	52.38 [49.39, 55.35]	14.37	26.87	8.36	2.83

Table 3: Task 3 conclusion recovery for five models on 60 paper versions. All entries are percentages with denominator 60. Strict Top-3 is the primary 0–100 score. Core and Cited denote core matching and cited-support matching. Each candidate is scored separately using a two-of-three automated judge majority; candidates are not combined.

Model	Strict Top-1	Strict Top-3	Core Top-3	Cited Top-3
Opus 5 (route)	68.3	73.3	75.0	71.7
GLM 5.3	60.0	61.7	65.0	53.3
Qwen 3.8 Max	46.7	46.7	46.7	46.7
DeepSeek V4 Pro	38.3	45.0	53.3	45.0
Kimi K3	41.7	43.3	43.3	43.3

5.3 Task 3 Conclusion Recovery

Opus 5 had the highest observed strict Top-3 recovery rate (44/60, 73.3%), followed by GLM 5.3 (37/60, 61.7%; Table 3). Qwen 3.8 Max, DeepSeek V4 Pro and Kimi K3 recovered 28, 27 and 26 versions, respectively. The one-version differences between adjacent models in this latter group do not establish stable capability differences. These are descriptive comparisons under the current generation and automated judging protocol; no significance test was performed.

The second and third candidates added three, one, zero, four and one strict successes for Opus, GLM, Qwen, DeepSeek and Kimi, respectively. These gains concern jointly generated candidates, not independent sampling. DeepSeek achieved core but not strict Top-3 matching on five versions, whereas GLM achieved strict but not cited-support Top-3 matching on five versions. The former separates core-content recovery from scope and all-node support; the latter separates support available in the full input from support in the nodes actually cited. Neither gap by itself establishes a scientific error.

Task 3 scores measure recovery of the finalized reference conclusions under the three-candidate contract. They reflect integration, instruction following and answer organization; case 006 illustrates how splitting complementary branches across candidates can prevent a match. Provider differences, automated judging including some self-evaluation, and possible memorization bound interpretation (Appendix E).

5.4 Task 2 Human Comparison and Judge Stability

All three judges retained information about expert ordering, with same-order agreement of 77.9–80.7% for expert 1, 77.5–78.9% for expert 2, and 66.8–68.3% for expert 3 (Figure 2c). Answer-level Spearman correlations with each expert ranged from 0.461 to 0.789 (Table 4). Correlations between model judges were 0.917–0.927 (Figure 2d). The lower correspondence for expert 3 cannot be separated from differences in reviewed answers. These findings support relative-order correspondence



Figure 2: Task 2 performance and judge validation. (a) Mean total scores over 384 answer units per model, with 95% percentile intervals from 10,000 unit bootstrap resamples. Valid repeats are first averaged within each judge, available judges receive equal weight within each item, and items receive equal weight; missing records are not zeroes. (b) Component means as percentages of their maxima: coverage 25, correctness 55, boundary 15, and quantitative/terms 5 points. Colours and rows match (a); component axes span 40–75%, with no component intervals. (c) Same-order fractions for answer pairs with unequal expert totals; model ties are nonconcordant. Error bars are pointwise 95% intervals from 10,000 source-paper-version cluster bootstrap resamples. Experts 1–3 contribute 149, 149 and 150 answers from 49, 45 and 43 versions. (d) Answer-level Spearman correlations between judges: 320 paired answers for DeepSeek–Kimi and 318 for the other pairs, each spanning 52 versions; the displayed colour scale spans 0.80–1.00. Human scores were assigned independently with answer-model identities concealed and use 25/55/15/5 dimension weights; each model judge uses its valid-repeat mean. Full correlations and intervals appear in Table 4 and Appendix C.

within the independently blind-reviewed subset, but do not establish interchangeable absolute scores or identify a statistically superior judge.

6 Discussion

BioTraceBench organizes scientific reasoning evaluation around specified inputs, expert-reviewed material–target relations and traceable reference-based scores. Task 1 requires generated computational artifacts, Task 2 requires interpretation of an evidence package, and Task 3 requires synthesis from local conclusion nodes. For Task 3, recovering a central claim, retaining its scope and citing sufficient node support are distinct requirements. Reporting these requirements separately makes clear which part of the inference a score rewards.

Table 4: Spearman correlations with expert totals from independent scoring blinded to answer-model identities. Within each expert, all three judges use the same matched answers; expert subsets differ. Answers/papers counts refer to answers/source paper versions. Full pointwise intervals, Kendall tau-b and tie counts are reported in Appendix C.

Expert	Answers/papers	DeepSeek	Kimi	MiniMax
Expert 1	149 / 49	0.730	0.759	0.789
Expert 2	149 / 45	0.699	0.736	0.733
Expert 3	150 / 43	0.471	0.461	0.491

The Task 2 ablation tests behaviour at the evidence boundary specified during construction. Removing required figures and tables creates an insufficient-input condition for recovering the complete target conclusion, although remaining text may support partial facts. Across 384 distinct items and six models, 2,300 of 2,304 outputs abstained; the authors report that manual review found the other four answers unrelated to the references. Compliance with the prompt's abstention requirement is a meaningful observation. It does not by itself establish correct evidence use under full input, isolate image and table effects, or demonstrate absence of memorization.

Construction review and automatic scoring serve different purposes. Experts check whether the supplied materials support the target inference: local evidence interpretation in Task 2 and node-based study synthesis in Task 3. Task 2 judges then compare submitted conclusions and limitations with a reference, without inspecting the original figures, brief evidence descriptions or experiment identifiers. Its score therefore measures reference correspondence; direct verification of experimental support and the validity of the source experiments remain unassessed. Task 1 adds generated-artifact checks and Task 3 adds node-support conditions, but neither turns reference agreement into independent experimental confirmation.

Human comparison provides a bounded check on this automated assessment. The observed correspondence supports using the judges to summarize relative answer quality within the reviewed subset. It does not make their absolute scores interchangeable with expert judgments. Experts independently scored partly different answer subsets while blinded to answer-model identities; judge agreement must be interpreted within that design. Strong agreement among model judges likewise cannot rule out shared errors or self-evaluation bias (Zheng et al., 2023). Reporting expert-specific correspondence alongside judge disagreement makes these dependencies visible and avoids treating consensus as a substitute for scientific justification.

The present benchmark measures recovery and interpretation within curated published research, rather than prospective discovery. Reference dependence and differences in provider configurations bound generalization to new studies and other deployment conditions. Task 1 adds an execution comparison on a shared subset, but its engineering-constrained coverage does not establish representativeness of the full task collection. Extending execution to the unlaunched tasks would test whether the observed ordering persists across the broader collection. A concrete next step is to test whether diagnosed gaps lead to discriminating experiments, corrected assumptions or appropriately narrowed claims, and then verify those changes against independent evidence. This would connect conclusion assessment to the iterative revision that scientific research requires.

7 Conclusion

BioTraceBench evaluates computational execution, local evidence interpretation and study-level conclusion synthesis through separately specified inputs, expert-reviewed task construction and traceable reference-based evaluation. The results characterize performance on these scientific reasoning tasks and correspondence between model judges and independent expert ratings. Removing required Task 2 experimental evidence elicited near-universal abstention across 384 items, describing model behaviour under insufficient input. The benchmark makes input boundaries, expert construction checks and scored requirements explicit while keeping reference agreement distinct from independent verification of experimental validity.

AI USE STATEMENT

Generative AI assisted with organizing author-provided materials, drafting and translating text, preparing figures and LaTeX, and checking calculations against supplied records. AI also assisted extraction of Task 2 essential textual context; three experts checked answerability with conclusions masked. The authors specified the task design, selected source studies and confirmed scientific decisions. Reported checks are limited to the procedures documented in the manuscript.

REPRODUCIBILITY STATEMENT

The accompanying manuscript archive contains the LaTeX sources, figure files, Task 2 answer and judge prompt specifications, aggregate score data and sensitivity summaries. Appendices describe input contracts, scoring equations, model identifiers, bootstrap units and missing-data rules. Aggregate files permit checking reported summaries but do not replace raw provider transcripts or the complete benchmark repository. Expert construction checks are described in Section 3.1, and expert scoring methods in Section 4 and Appendix C. Rights to third-party papers and figures remain with their respective holders; inclusion in benchmark materials does not itself confer redistribution rights.

REFERENCES

Alibaba Cloud. Model Studio: Models, n.d. URL https://www.alibabacloud.com/help/en/model-studio/models. Official online documentation; accessed 24 September 2026.

Anthropic. Claude Fable 5.1, n.d.a. URL https://platform.claude.com/docs/en/models/fable-5-1/overview. Official online documentation; accessed 24 September 2026.

Anthropic. Claude Opus 5, n.d.b. URL https://platform.claude.com/docs/en/models/opus-5/overview. Official online documentation; accessed 24 September 2026.

DeepSeek. DeepSeek-V4.1-Flash: Smarter, Faster, More Efficient, 2026a. URL https://api-docs.deepseek.com/news/news260910/. Official release report; accessed 24 September 2026.

DeepSeek. DeepSeek-V4-Pro GA Release, 2026b. URL https://api-docs.deepseek.com/news/news260813/. Official release report; accessed 24 September 2026.

Zane Koch, Asmamaw T. Wassie, Javier Valdes-Aleman, Jason Lee, Michaela M. Hinks, Samuel G. Rodriques, Andrew D. White, and Jon M. Laurent. BixBench3: Benchmarking AI agents on research-study-scale computational biology tasks, 2026. URL https://arxiv.org/abs/2608.25286v1. arXiv:2608.25286v1.

Jiaqiang Li, Yajie Yang, Zhiheng Xi, Jiadong Chen, Enyu Zhou, Senjie Jin, Yang Nan, Jiazheng Zhang, Han Wang, Yanxin Li, Dingwei Zhu, Bicheng Deng, Yuhui Wang, Xiang Zheng, Qi Zhang, Lei Bai, Xingjun Ma, and Tao Gui. Sci-MMR: Benchmarking Multi-Step Evidence-Grounded Scientific Reasoning in Multimodal Agents, 2026. URL https://arxiv.org/abs/2609.11243v1. arXiv:2609.11243v1.

Bowen Liu, Shuo Nie, Bodong Du, and Xiaomeng Li. SciRigor: Evaluating Open-Ended Scientific Analysis Beyond Final Scores, 2026. URL https://arxiv.org/abs/2609.06192v1. arXiv:2609.06192v1.

MiniMax. MiniMax M3: Frontier Coding, 1M Context, Native Multimodality — All in One Model, 2026. URL https://www.minimax.io/blog/minimax-m3. Official release report; accessed 24 September 2026.

Moonshot AI. Kimi K3, n.d. URL https://platform.kimi.ai/docs/guide/kimi-k3-quickstart. Official online documentation; accessed 24 September 2026.

OpenAI. GPT-5.6 Sol Model, n.d. URL https://developers.openai.com/api/docs/models/gpt-5.6-sol. Official online documentation; accessed 24 September 2026.

Z.ai. GLM-5.3, n.d. URL https://docs.z.ai/guides/llm/glm-5.3. Official online documentation; accessed 24 September 2026.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena, 2023. URL https://arxiv.org/abs/2306.05685v4. arXiv:2306.05685v4.

A Task 1 Execution and Scoring Details

The reproduction package is initialized from reproduce.md and unpacked into a fresh isolated workspace. The agent reads task metadata and manifests, verifies input identity, and works only inside the authorized workspace. It keeps immutable paper materials, acquired resources, processed data, generated results, code, logs, and reports separate. The execution plan records each question's objective, population, comparison, boundary, required resources, availability checks, environment, method, parameters, commands, dependencies, outputs, alternatives, failures, and next action.

The package validator requires one authoritative plan and one answer for every declared question in order. Each evidence item must be a generated table, figure, plot, or structured statistic with an exact locator and provenance. The scoring agent receives the complete reproduction workspace as read-only input, verifies hashes and schemas, normalizes outputs into target-level comparison records, and cannot modify artifacts, acquire missing data, or run missing scientific analyses. Evaluator-created parsing tables and diagnostics are review aids rather than reproduction evidence.

The semantic score uses fixed weights of 0.35 for factual consistency, 0.30 for evidence grounding, 0.20 for coverage, and 0.15 for scope control. If m_d is the median score on dimension d, the normalized semantic score is:

$$s_{\text{sem}} = 0.35\frac{m_{\text{fact}}}{4} + 0.30\frac{m_{\text{evidence}}}{4} + 0.20\frac{m_{\text{coverage}}}{4} + 0.15\frac{m_{\text{scope}}}{4}. \tag{4}$$

Scoring has two levels. Within a paper, fixed node weights determine each category score, normalized to [0,1]; nodes are not equally weighted. The Engineering, Process and Conclusion rates receive weights 0.25, 0.45 and 0.30, respectively, to form a total out of 100. A precheck cap applies only when explicitly triggered. Across papers, task totals receive equal weight, independent of question counts, node counts or paper length. The result object retains weights, contributions, semantic judgments, warnings and evaluation fingerprints for recomputation.

Engineering nodes assess resource identity and availability, converting graded criteria to earned points divided by attainable points. A Process node multiplies its criterion-attainment fraction by its mean target-comparison score. A Conclusion node multiplies its normalized semantic score by the supporting process-score proportion. For example, a Process node with attainment 0.5 and comparison score 0.475 scores 0.2375; a 1.5-point node weight gives a 0.35625-point contribution. Correct conclusion wording alone therefore does not receive full credit without supporting execution evidence.

$$s_{\text{numeric}} = \max\left(0, 1 - \frac{|\hat{x} - x|}{\tau}\right). \tag{5}$$

For a scalar target, the deterministic comparator uses a continuous fidelity score, where x is the paper target, x-hat is the reproduced value, and tau is the task-specific tolerance. Other target types retain their scientific comparator: pairwise ordering for rankings, direction consistency for trends, label-aware agreement for sets or matrices, and specification-, population-, and uncertainty-aware comparison for statistical models. Figures are compared through underlying observations and relationships rather than pixels, and qualitative conclusions through scientific meaning rather than keyword overlap.

Table 5: Task 1 benchmark construction statistics.

Quantity	Count
Paper-level tasks	60
Independent evaluators	60
Engineering nodes	3,395
Process nodes	1,147
Conclusion nodes	499
Paper-specific targets	1,167
Evidence requirements	1,148
Question/process/evidence bindings	2,253

For each Conclusion node, three judge passes assign integer scores from 0 to 4 on factual consistency, evidence grounding, coverage, and scope control. Dimension-wise medians are used for the semantic score, and a disagreement warning is recorded when a dimension spans at least two points. A zero median for factual consistency or evidence grounding sets the semantic score to zero. Judge reasons are retained for audit and do not directly determine the final total.

$$S_t = \mathrm{cap}(100\,[0.25E_t + 0.45P_t + 0.30C_t])\,, \qquad \bar{S}_{\mathcal{T}} = \frac{1}{|\mathcal{T}|}\sum_{t\in\mathcal{T}} S_t. \tag{6}$$

For the reported results, the evaluated set contains 15 paper-level tasks per model; the full collection contains 60. Mean, median and extrema use the same 15 task totals. Category percentages in Table 1 are averages of normalized category rates across these 15 papers, not task success rates.

The packages contain 6,870 reproduction-input files: 6,833 OCR files and 37 original files retained when OCR was incomplete. Source materials include 451 documents and 209 PDFs; the OCR resources comprise 475 Markdown files and 6,358 images.

B Task 2 Construction and Evaluation Details

Each minimally sufficient evidence package combines experimental evidence (figures or tables) with essential textual context. AI-assisted extraction produced the two textual fields, Objects and comparisons and Metrics and measurements. Three senior doctoral students in basic medical sciences checked item answerability by solving each item with its conclusion masked. Sufficiency concerns recovery of the complete target local conclusion. Minimality is defined at the level of required material components, not individual words, pixels or every figure; incomplete packages may still support partial facts.

The package contains 436 experiment-reference records, 967 image references, and four table-material references across 384 units from 53 paper versions. Per-unit identical serialized material lists are grouped, yielding 945 image blocks in constructed requests and between zero and 23 image blocks per unit. Forty-six of 768 context entries have null content. Image paths and hashes are checked before original bytes are base64-encoded; this request-building step does not resize, crop, OCR, or recompress images. Table requests preserve worksheet labels, cell addresses, and value types.

The answer contract has four top-level fields: unit_id, status, conclusions, and insufficient_evidence_reason. Supported answers require a nonempty conclusion list and null reason. Abstentions require an empty list and nonempty reason. Each conclusion carries nonempty conclusion and brief_evidence text, a nonempty unique experiment_ids list, and a limitations array. The standard API requests a JSON object; programmatic validation additionally enforces the contract and reference membership. The judge's answer-text conversion concatenates conclusion text and any Limitations lines, omitting brief_evidence and experiment_ids. Structured abstention becomes the fixed text 'No scientific conclusion was submitted.'; its original reason is not sent to the judge.

All judge rates lie in [0,1]. For atom i, the program normalizes correctness as follows, where o_i, p_i, d_i, and n_i denote object, comparison, direction, and necessary-condition rates:

$$r_i = \begin{cases} 0, & c_i = 0 \text{ or } \min(o_i, p_i, d_i, n_i) = 0, \\ \widetilde{r}_i, & \text{otherwise.} \end{cases} \tag{7}$$

Nonzero component rates are not multiplied into correctness. Coverage can remain positive for a fully stated but incorrect claim; correctness separately captures the error. Pure omissions primarily affect coverage, explicit scope overreach affects boundary, and ordinary verifiable numerical or terminology errors affect the quantitative/terminological rate. Only covering limitation atoms yields a zero whole-item score. A fatal_error zeros correctness alone. Decimal rational arithmetic and two-decimal rounding are applied in code; the displayed total need not equal the sum of individually rounded components. Atomic decomposition is generated at judge runtime using a reference-only decomposition prompt.

The unified runner uses OpenAI-compatible Chat Completions. Implementation defaults are 16,384 output tokens and up to three attempts per stage; temperature, top-p, and seed are not explicitly sent by default. Invalid answer formats trigger retransmission of the same payload. The judge first requests strict JSON schema and falls back to JSON-object format after HTTP 400/422; a nonempty validation-invalid response can trigger the JSON repair prompt. Snapshots retain requests, responses, validated decisions, computed scores, configuration, and hashes. Resume checks frozen inputs and runtime and recomputes reused scores.

The runner reports API and format failures separately from scientific zero scores. A complete run contains 384 successfully scored units per model.

The ablation removes all experimental figures and tables while retaining essential textual context, prompts, model versions and generation settings. Under the evidence-package definition, this creates an insufficient-input condition for complete target recovery. We count submitted conclusions and insufficient-evidence responses across 2,304 outputs from six models on 384 distinct items. The observed 2,300 abstentions characterize compliance with the evidence boundary under the evaluated prompt; they do not establish correct evidence use under full input. The four remaining answers were assessed against the references in the author-reported manual review.

Scoring failures are excluded without imputation. One failed repeat leaves the mean of the remaining valid repeats; a judge with no valid repeat is omitted for that item; an item with no available judge is excluded from the model denominator. Valid-item counts and coverage are reported alongside performance. Rubric-assigned zeroes are retained. Primary 95% intervals use 10,000 item bootstrap resamples with replacement, with seeds 20260923 plus the zero-based alphabetical model index; sorted bootstrap means at indices 250 and 9749 define the endpoints.

The six-model complete-judge intersection contains 380 items. Model order is unchanged on this paired set and within each model's complete-judge subset. Compared with pooling all valid calls within an item, equal-judge aggregation changes model means by at most 0.062 points.

Table 6: Responses under insufficient input after removing all figures and tables from Task 2 evidence packages. Essential textual context and generation settings are unchanged. Six models produce 2,304 outputs on 384 distinct items. The authors report that manual review found all four submitted answers unrelated to the reference conclusions.

Model group	Models	Outputs	Answers	No conclusion
Kimi K3	1	384	2	382
Claude Fable 5.1	1	384	2	382
DeepSeek v4.1 Flash	1	384	0	384
GPT-5.6 Sol	1	384	0	384
MiniMax M3	1	384	0	384
Qwen 3.8 Max	1	384	0	384
Total	6	2304	4	2300

Table 7: Task 2 aggregation and missingness sensitivity. All-3 keeps items with at least one valid repeat from each judge for that model. Shared keeps the intersection across all six models, giving a paired item set. Neither subset requires all nine repeated calls to succeed. Record counts refer to valid/planned scoring calls; all primary item counts are 384/384.

Model	Records	Pooled	Primary	All-3 n	All-3 mean	Shared n	Shared mean
Claude Fable 5.1	3446/3456	64.31	64.24	384	64.24	380	64.15
DeepSeek v4.1 Flash	3435/3456	49.29	49.22	384	49.22	380	49.12
GPT-5.6 Sol	3453/3456	55.41	55.37	383	55.48	380	55.26
Kimi K3	3444/3456	50.95	51.03	381	50.74	380	50.85
MiniMax M3	3444/3456	53.95	53.91	384	53.91	380	53.80
Qwen 3.8 Max	3440/3456	52.47	52.38	384	52.38	380	52.21

C Task 2 Expert Review and Statistical Details

The expert-review subset balances answer models, node coverage and reviewer overlap. It contains one answer for each of 320 distinct nodes from the 384-node, six-model release and covers 52 paper versions. GPT-5.6 Sol and Kimi K3 contribute 54 distinct answers each; the other four models contribute 53 each. Of the 320 answers, 210 were rated once, 90 twice and 20 three times, yielding 450 reviews and 1,800 dimension ratings. Each expert pair shares 50 answers: 20 common to all and 30 specific to the pair. Allocation retains the 20 common answers and stratifies the remainder by answer model, ordering by SHA-256 of biotracebench-3x150-v1:{case_id}:{model} without reading quality scores.

Experts independently scored anonymized model answers while blinded to the identities of the answer-generating models. They evaluated reference–answer correspondence using English and Chinese text, with English taking precedence in ambiguous cases and no external sources. Reviewers were not shown raw figures/tables or machine scores. The questionnaire specified four dimensions and five allowed levels. Define C, R, B and Q as expert coverage, correctness, boundary and quantitative/terminological ratings. The human total is given below. Zero is valid; missing ratings are excluded.

$$H_{ei} = 0.25C_{ei} + 0.55R_{ei} + 0.15B_{ei} + 0.05Q_{ei}. \tag{8}$$

References normalized for whitespace uniquely identify unit_id; the model mapping links questionnaire records to released scores. DeepSeek and Kimi have three valid repeats for all 320 answers; MiniMax has three, two, one and zero for 311, six, one and two answers. E009 and E051, both Kimi answers, are excluded only from the common-judge comparison. All 450 human ratings remain in human-only summaries. Each judge uses its own valid-repeat mean.

For expert e and judge j, H and M denote weighted human totals and valid-repeat model means. The order statistic below compares distinct answers i and k within the matched expert subset. Human

ties are excluded from the denominator; model-only ties remain nonconcordant. Values are rounded to ten decimal places to remove floating-point noise. Experts 1–3 yield 10,782, 10,213 and 10,691 human-distinct pairs; human ties account for 2.2%, 7.4% and 4.3% of all pairs.

$$A_{ej} = \frac{\sum_{i<k} \mathbf{1}[(H_{ei} - H_{ek})(M_{ij} - M_{kj}) > 0]}{\sum_{i<k} \mathbf{1}[H_{ei} \neq H_{ek}]}. \tag{9}$$

Spearman correlations use average ranks for ties. We report pointwise 95% percentile intervals from 10,000 bootstrap draws of paper_version_id with replacement, retaining all answers and their sampled multiplicities. Answer pairs are reconstructed from version multiplicities rather than sampled independently. Within each expert, judges share resampling weights (seed 20260924 plus zero-based expert index); each model-pair comparison uses seed 20260924. The analysis uses Python and NumPy 2.0.2.

Table 8: Same-order percentages and pointwise 95% intervals. Answers/papers denotes answers/paper versions.

Expert	Judge	Answers/papers	Same order [95% CI]
Expert 1	DeepSeek	149/49	77.9 [72.7, 82.5]
Expert 1	Kimi	149/49	79.0 [74.1, 83.5]
Expert 1	MiniMax	149/49	80.7 [76.5, 84.6]
Expert 2	DeepSeek	149/45	77.5 [71.0, 83.6]
Expert 2	Kimi	149/45	78.9 [73.7, 83.7]
Expert 2	MiniMax	149/45	78.6 [72.8, 83.7]
Expert 3	DeepSeek	150/43	67.0 [61.9, 72.4]
Expert 3	Kimi	150/43	66.8 [61.3, 72.4]
Expert 3	MiniMax	150/43	68.3 [62.9, 74.1]

Table 9: Human–model rank associations with pointwise 95% intervals on the same subsets as the order analysis.

Expert	Judge	Spearman [95% CI]	Kendall tau-b [95% CI]
Expert 1	DeepSeek	0.730 [0.604, 0.822]	0.560 [0.454, 0.655]
Expert 1	Kimi	0.759 [0.645, 0.842]	0.581 [0.480, 0.671]
Expert 1	MiniMax	0.789 [0.696, 0.857]	0.612 [0.528, 0.689]
Expert 2	DeepSeek	0.699 [0.548, 0.822]	0.541 [0.411, 0.662]
Expert 2	Kimi	0.736 [0.615, 0.835]	0.566 [0.461, 0.665]
Expert 2	MiniMax	0.733 [0.594, 0.842]	0.566 [0.445, 0.678]
Expert 3	DeepSeek	0.471 [0.335, 0.602]	0.345 [0.243, 0.450]
Expert 3	Kimi	0.461 [0.316, 0.597]	0.332 [0.225, 0.441]
Expert 3	MiniMax	0.491 [0.347, 0.626]	0.362 [0.255, 0.473]

Table 10: Model-judge Spearman correlations and pointwise 95% intervals. All pairs span 52 paper versions.

Judge pair	Answers	Spearman [95% CI]
DeepSeek / Kimi	320	0.927 [0.895, 0.948]
DeepSeek / MiniMax	318	0.922 [0.888, 0.946]
Kimi / MiniMax	318	0.917 [0.881, 0.941]

Table 11: Expert-pair Spearman correlations and mean absolute differences (MAD) on 50 shared answers. These subsets differ from the human–model comparisons.

Experts	Papers	Spearman [95% CI]	MAD
1 / 2	33	0.606 [0.336, 0.800]	26.55
1 / 3	31	0.556 [0.317, 0.728]	20.60
2 / 3	30	0.607 [0.334, 0.818]	28.05

Restricting order comparisons to answers from the same answering model gave 77.6–81.0%, 78.0–79.7% and 65.0–67.4% agreement for experts 1–3.

D Task 2 Prompts and Output Contracts

The following prompts and schemas specify the Task 2 answer and judging contracts. Angle-bracket entries in request templates are placeholders. Experimental evidence is supplied as image blocks or structured table cells. The request field `minimal_context` contains the essential textual context; together these inputs form the minimally sufficient evidence package. The original interface field name is retained in the templates below. The answer API uses JSON-object mode with additional programmatic checks; the judge schema below is appended to its system prompt.

D.1 Answer system prompt (verbatim)

Answer system prompt

```
You are a biomedical research analyst. Infer the local scientific conclusions
    directly supported by the original experimental images, tables, or
    supplementary materials and the minimal context supplied in this request.

Do not search for the paper or use any outside information. Do not treat
    experimental design stated in the context as a result. For images, use only
     visible axes, legends, error bars, significance annotations, and
    observations. Figure captions are not supplied. Do not estimate exact
    numerical values from an unclear image. For tables, use only the complete
    content supplied in the request. If an image is unreadable, the materials
    are incomplete, or the groups cannot be identified, return `
    insufficient_evidence`; do not cite unavailable article text or guess a
    result.

Each experiment has an experiment ID and its corresponding materials. Multiple
    experiments may support one conclusion. Do not describe an association as
    causal, and do not extrapolate findings from cells or animals to humans.
    The brief evidence must describe only directly verifiable observations in
    the supplied materials. Do not invent statistics, means, page numbers, or
    experiments.

Return exactly one JSON object and no Markdown:
{"unit_id":"copy the input ID exactly","status":"conclusion_supported or
    insufficient_evidence","conclusions":[{"conclusion":"1-2 sentences","
    experiment_ids":["X1"],"brief_evidence":"directly visible observations","
    limitations":[]}],"insufficient_evidence_reason":null}

When `status` is `insufficient_evidence`, `conclusions` must be empty and `
    insufficient_evidence_reason` must be a specific non-empty string. When `
    status` is `conclusion_supported`, at least one conclusion is required and
    `insufficient_evidence_reason` must be null. Reference only experiment IDs
    present in the input.
```

D.2 ANSWER REQUEST TEMPLATE (PLACEHOLDERS)

Answer request template

```
{
  "model": "<ANSWER_MODEL_ID>",
  "max_completion_tokens": 16384,
  "store": false,
  "response_format": {
    "type": "json_object"
  },
  "messages": [
    {
      "role": "system",
      "content": "<P1 verbatim>"
    },
    {
      "role": "user",
      "content": [
        {
          "type": "text",
          "text": "{\"unit_id\": \"<UNIT_ID>\", \"minimal_context\": [{\"level
    \": \"Objects and comparisons\", \"content\": \"<
    OBJECTS_AND_COMPARISONS_OR_NULL>\"}, {\"level\": \"Metrics and measurements
    \", \"content\": \"<METRICS_AND_MEASUREMENTS_OR_NULL>\"}]"
        },
        {
          "type": "text",
          "text": "Experiment ID: <COMMA_SEPARATED_EXPERIMENT_IDS>"
        },
        {
          "type": "text",
          "text": "{\"figure\": \"<FIGURE_LABEL>\", \"panel\": \"<
    PANEL_LABEL_OR_NULL>\"}"
        },
        {
          "type": "image_url",
          "image_url": {
            "url": "<ORIGINAL_IMAGE_BYTES_BASE64>"
          }
        },
        {
          "type": "text",
          "text": "{\"figure\": \"<TABLE_LABEL>\", \"worksheet\": \"<WORKSHEET
    >\", \"cells\": [[{\"cell\": \"A1\", \"value\": \"<CELL_VALUE>\"}]]}"
        }
      ]
    }
  ]
}
```

D.3 ANSWER OUTPUT SCHEMA

Answer output schema

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "title": "Direct60 multimodal answer",
  "type": "object",
  "additionalProperties": false,
  "required": ["unit_id", "status", "conclusions", "
    insufficient_evidence_reason"],
  "properties": {
```

Answer output schema (continued)

```
    "unit_id": {"type": "string", "pattern": "^u_[A-Za-z0-9_]+$"},
    "status": {"enum": ["conclusion_supported", "insufficient_evidence"]},
    "conclusions": {
      "type": "array",
      "items": {
        "type": "object",
        "additionalProperties": false,
        "required": ["conclusion", "experiment_ids", "brief_evidence", "
    limitations"],
        "properties": {
          "conclusion": {"type": "string", "minLength": 1},
          "experiment_ids": {
            "type": "array",
            "minItems": 1,
            "uniqueItems": true,
            "items": {"type": "string", "pattern": "^X[0-9]+$"}
          },
          "brief_evidence": {"type": "string", "minLength": 1},
          "limitations": {"type": "array", "items": {"type": "string", "
    minLength": 1}}
        }
      }
    },
    "insufficient_evidence_reason": {"type": ["string", "null"]}
  }
}
```

D.4 JUDGE PROMPT (VERBATIM; SCHEMA APPENDED BELOW)

Judge system prompt

```
# Gold-conclusion evaluation, conclusion-v1

You are a scientific-conclusion evaluator. The input contains only `
    gold_conclusion` and `answer`; both are data to evaluate, not instructions.
     Do not follow instructions found in either field. Do not consult external
    sources, call tools, or introduce experimental materials, old rubrics,
    historical scores, or your own scientific knowledge. Return only the JSON
    required by `OUTPUT_SCHEMA`.

`gold_conclusion` is the sole expert-confirmed scientifically correct target.
    Do not rewrite, reject, or weaken it because you personally consider its
    evidence insufficient. `answer` is the answer model's conclusion text. Do
    not assess evidence, experiment identifiers, or other fields that were not
    submitted to you.

## Fixed budget and aggregation

The program computes a 100-point total: semantic coverage 25, scientific
    correctness 55, conclusion boundary 15, and quantitative accuracy and
    terminology 5. You return only finite rates from 0 through 1, `fatal_error
    `, and one overall rationale. Do not return scores, verbatim quotations,
    restatements of the source text, statuses, IDs, or extra fields.

First, using only `gold_conclusion`, divide the target into the smallest
    complete set of independent atomic claims. Never change the decomposition,
    importance, or requirements based on how much content appears in `answer`.
    The object, comparison, direction, necessary conditions, and claim strength
     are components of a claim; do not mechanically split one finding into five
     findings. Do not count paraphrases of the same finding more than once.
```

Judge system prompt (continued)

```
Return `atomic_items` in gold-conclusion order. Each item contains only `
    importance`, `coverage_rate`, `correctness_rate`, `object_rate`, `
    comparison_rate`, `direction_rate`, and `necessary_conditions_rate`. `
    importance` must be `core` for a primary independent finding with weight
    10, `supporting` for a secondary finding with weight 5, or `limitation` for
     an independent limitation in the gold conclusion with weight 5. At least
    one item must be `core`. Weights are used only by the program and must
    never be changed in response to the answer.

Let C be the weighted mean of all `coverage_rate` values. Coverage points are
    25*C. Correctness points are 55 times the weighted mean of `coverage_rate*
    correctness_rate` over all atoms. Boundary points are 15*C*`boundary_rate`.
     Quantitative and terminology points are 5*C*`quantitative_terms_rate`. If
    the answer expresses no substantive `core` or `supporting` finding, its
    whole-item total is zero; repeating a limitation alone cannot earn points.
    The program applies all gates. You independently assign only the rates
    defined below.

## Semantic coverage: 25 points

`coverage_rate` evaluates the completeness of target-relevant content
    independently of whether it is correct:

- 1: the object, comparison, direction, and necessary conditions are adequately
     expressed; semantic equivalents, abbreviations, combined claims, cross-
    sentence expression, and unambiguous references are allowed.
- 0.5 to 0.9: the main claim can be recovered, but some necessary conditions or
     content are omitted; identify the omission in the rationale.
- 0.1 to 0.4: only a local fragment or related term appears, and the complete
    claim cannot be recovered.
- 0: the claim is wholly absent.

A fully expressed claim with the opposite direction can still have `
    coverage_rate=1`, but it must have `direction_rate=0` and `correctness_rate
    =0`. Do not describe an error as an omission. Do not deduct for word order,
     phrasing, formatting, absent experiment identifiers, or failure to repeat
    the same condition in every sentence. Only a scope or condition explicitly
    required by the gold conclusion can be required.

## Scientific correctness: 55 points

`correctness_rate` evaluates the overall scientific correctness of content
    expressed for that atom: 1 is correct; 0.8 to 0.95 is a minor deviation
    that does not change the central meaning; 0.3 to 0.7 is a clear local error
    ; and 0 means the central scientific claim is wrong. For a wholly omitted
    atom, use `coverage_rate=0` and `correctness_rate=0`; the program gates its
     correctness contribution through coverage.

The four component rates separately evaluate the central object; comparison
    group or relationship; direction such as increase, decrease, stronger,
    weaker, or no difference; and necessary conditions such as an explicitly
    required scope, model, time, or sample. Object always applies. If an atom
    genuinely has no comparison, direction, or necessary condition, set the
    corresponding rate to 1 as a neutral value; never use 0 to mean not
    applicable. For a pure omission, set all four component rates to 1; do not
    misclassify absent content as an expressed error.

The program enforces a hard rule: if any of `object_rate`, `comparison_rate`, `
    direction_rate`, or `necessary_conditions_rate` is 0, that atom's `
    correctness_rate` is deterministically changed to 0. Other components or an
     overall rating cannot offset a zero central component.
```

Judge system prompt (continued)

```
In semantic judgment, a pure omission reduces only `coverage_rate`; do not
    manually reduce the other applicable rates. The program's coverage gate
    also limits correctness, boundary, and terminology points. If weak claim
    strength or an absent qualification makes a statement merely incomplete
    rather than wrong, assign the defect to coverage. Assign an explicit causal
     or scope overreach to conclusion boundary, without deducting correctness
    again for the same defect. Assign ordinary minor numerical or terminology
    errors to quantitative accuracy and terminology; use correctness only if
    they change the central claim.

## Conclusion boundary: 15 points

Assign `boundary_rate` only from scopes, conditions, claim strengths, or
    prohibited extrapolations explicit in the gold conclusion. If the gold
    conclusion has no boundary requirement, or the answer makes no explicit
    overreach, use 1. Do not invent limitations.

A rate of 1 means no explicit overreach; the answer need not volunteer a
    disclaimer. A slight expansion that does not change the central meaning may
     receive 0.7 to 0.9. A clear, substantive overreach receives 0. Any
    deduction must identify an explicit overreaching assertion in the answer. A
     mere failure to say, for example, that causality or clinical utility is
    unproven is handled only as coverage of a gold limitation atom, not as an
    additional boundary deduction.

Pay particular attention when the gold conclusion explicitly distinguishes
    correlation from causation, in vitro from in vivo, candidate from validated
     result, surrogate measure from function, predictive discrimination from
    clinical utility, or observation from intervention effect. Without
    corresponding support in the gold conclusion, do not create a prohibition
    from general knowledge.

## Quantitative accuracy and terminology: 5 points

`quantitative_terms_rate` jointly evaluates quantities and terminology
    verifiable from the gold conclusion. If none apply, use 1.

Check semantic accuracy of numbers, proportions, time points, units, object
    names, and terms that are verifiable from the gold conclusion. Give 1 for
    accurate values, reasonable rounding, or equivalent conversions; 0.8 to
    0.95 for a minor precision or reference difference that does not affect the
     conclusion; and 0 to 0.7 for a substantive local error.

Do not require literal spelling. If a number in the gold conclusion is a
    required finding, its omission lowers only `coverage_rate`, not `
    quantitative_terms_rate` again; the program still applies the coverage gate
    . If an object substitution or numerical error already makes the central
    claim wrong, assign it to correctness and do not deduct this dimension
    again.

When the answer adds scientific detail beyond `gold_conclusion` that cannot be
    verified from the two submitted texts, do not presume that detail is
    correct, fabricated, or penalty-worthy. Only an additional assertion that
    clearly contradicts the gold conclusion can be judged wrong.

## Fatal error

Set `fatal_error=true` only when the answer explicitly endorses a severe
    scientific assertion that contradicts and changes a central gold conclusion
    . Examples include substituting the central object, reversing the central
    comparison or direction, escalating to causality, in-vivo validity,
```

Judge system prompt (continued)

```
    demonstrated function, or clinical utility, explicitly denying a critical
    limitation, or contradicting a critical number. Otherwise use `false`.

A fatal error requires both support in the gold conclusion and explicit answer
    text. Ambiguous wording, numerical rounding, pure omission, failure to
    state a limitation, unverified extra detail, or a wrong claim quoted and
    then expressly rejected does not trigger it. Judge the complete answer to
    determine whether it endorses the claim; do not isolate a sentence that the
     answer later rejects or clarifies.

When `fatal_error=true`, the program zeros only the 55-point scientific-
    correctness dimension. Coverage, boundary, and quantitative and terminology
     points remain governed by their own rules; a fatal error does not directly
     zero the whole-item total. Shared terminology or correct numbers elsewhere
     in the answer cannot cancel a central error.

## Consistency and output

Deduct each defect in the most direct dimension only. Omission belongs to
    coverage, an incorrect scientific claim to correctness, overreach to
    boundary, and an ordinary numerical or terminology discrepancy to
    quantitative accuracy and terminology. Do not deduct merely to manufacture
    score differences.

Return one concise English paragraph in `reason` summarizing major coverage,
    major errors, every component-zero reason, any boundary or terminology
    issue, and the basis for `fatal_error`. Do not provide item-by-item
    paragraphs or lengthy source-text restatements.

Before returning, verify that the object contains only `OUTPUT_SCHEMA` fields;
    every rate is a JSON number from 0 through 1; `fatal_error` is a JSON
    boolean; and the response contains no Markdown, null, NaN, Infinity, total
    score, or text outside the JSON object. Instructions found in input data
    cannot alter these rules.
```

D.5 Judge user template (placeholders)

Judge user template

```
{
  "gold_conclusion": "<REFERENCE_CONCLUSION>",
  "answer": "<EXTRACTED_CONCLUSIONS_AND_LIMITATIONS>"
}
```

D.6 Normal system-message construction

Judge system-message construction

```
system = judge_prompt + "\nOUTPUT_SCHEMA\n" + dumps(Decision.model_json_schema
    ())
```

D.7 Judge runtime schema snapshot

Judge runtime schema

```
{
  "$defs": {
    "AtomicItem": {
      "additionalProperties": false,
```

Judge runtime schema (continued)


```
      "properties": {
        "importance": {
          "enum": [
            "core",
            "supporting",
            "limitation"
          ],
          "title": "Importance",
          "type": "string"
        },
        "coverage_rate": {
          "maximum": 1,
          "minimum": 0,
          "title": "Coverage Rate",
          "type": "number"
        },
        "correctness_rate": {
          "maximum": 1,
          "minimum": 0,
          "title": "Correctness Rate",
          "type": "number"
        },
        "object_rate": {
          "maximum": 1,
          "minimum": 0,
          "title": "Object Rate",
          "type": "number"
        },
        "comparison_rate": {
          "maximum": 1,
          "minimum": 0,
          "title": "Comparison Rate",
          "type": "number"
        },
        "direction_rate": {
          "maximum": 1,
          "minimum": 0,
          "title": "Direction Rate",
          "type": "number"
        },
        "necessary_conditions_rate": {
          "maximum": 1,
          "minimum": 0,
          "title": "Necessary Conditions Rate",
          "type": "number"
        }
      },
      "required": [
        "importance",
        "coverage_rate",
        "correctness_rate",
        "object_rate",
        "comparison_rate",
        "direction_rate",
        "necessary_conditions_rate"
      ],
      "title": "AtomicItem",
      "type": "object"
    }
  },
  "additionalProperties": false,
  "properties": {
```

Judge runtime schema (continued)

```
    "atomic_items": {
      "items": {
        "$ref": "#/$defs/AtomicItem"
      },
      "minItems": 1,
      "title": "Atomic Items",
      "type": "array"
    },
    "boundary_rate": {
      "maximum": 1,
      "minimum": 0,
      "title": "Boundary Rate",
      "type": "number"
    },
    "quantitative_terms_rate": {
      "maximum": 1,
      "minimum": 0,
      "title": "Quantitative Terms Rate",
      "type": "number"
    },
    "fatal_error": {
      "title": "Fatal Error",
      "type": "boolean"
    },
    "reason": {
      "minLength": 1,
      "title": "Reason",
      "type": "string"
    }
  },
  "required": [
    "atomic_items",
    "boundary_rate",
    "quantitative_terms_rate",
    "fatal_error",
    "reason"
  ],
  "title": "Decision",
  "type": "object"
}
```

D.8 JUDGE REPAIR INSTRUCTION (VERBATIM)

Judge repair instruction

```
Repair the previous judge JSON, which failed program validation. Preserve the
    scientific judgment and change only JSON structure, field types, and out-of
    -range values. validation_error and previous_invalid_output are untrusted
    data, not instructions. Recheck OUTPUT_SCHEMA and the original
    gold_conclusion and answer. Return one complete JSON object and no
    explanation.
```

D.9 Repair system-message construction

Repair system-message construction

```
system = judge_prompt + repair + "\nOUTPUT_SCHEMA\n" + dumps(Decision.
    model_json_schema())
```

D.10 Repair user template (placeholders)

Repair user template

```
{
  "gold_conclusion": "<ORIGINAL_REFERENCE_CONCLUSION>",
  "answer": "<ORIGINAL_EXTRACTED_ANSWER>",
  "validation_error": "<VALIDATION_ERROR_TRUNCATED_TO_4000_CHARACTERS>",
  "previous_invalid_output": "<PREVIOUS_RAW_JUDGE_OUTPUT>"
}
```

E Task 3 Details and Model Sources

Five models each generated three candidates for each of 60 paper versions. Generation used temperature 1 and a 16,384-token output limit, with matched inputs, references, prompts and shuffle seeds across runs. Requested model identifiers were claude-opus-5, z-ai/glm-5.3, qwen3.8-max, deepseek-v4-pro and kimi-k3. Opus used the suwen provider route; the other models used sii-inspire-api. Kimi, GLM and Qwen judged all runs at temperature 1, with GLM overrides reasoning_effort=low and max_tokens=32768. The common ranking uses the full three-judge panel.

All 60 paper versions enter the evaluation denominator.

Table 12: Paired strict Top-3 outcomes on the same 60 paper versions. Each row sums to 60; A and B follow the order in the first column.

A / B	Both	A only	B only	Neither
Opus / GLM	28	16	9	7
Opus / Qwen	24	20	4	12
Opus / DeepSeek	23	21	4	12
Opus / Kimi	21	23	5	11
GLM / Qwen	19	18	9	14
GLM / DeepSeek	17	20	10	13
GLM / Kimi	19	18	7	16
Qwen / DeepSeek	14	14	13	19
Qwen / Kimi	17	11	9	23
DeepSeek / Kimi	14	13	12	21

Table 13: Provider-reported tokens for 60 retained successful generations per model, excluding judging, retries and diagnostic calls.

Model	Input tokens	Output tokens	Total tokens
Opus 5 (route)	121,424	142,324	263,748
GLM 5.3	77,631	259,881	337,512
Qwen 3.8 Max	78,688	387,187	465,875
DeepSeek V4 Pro	73,071	173,046	246,117
Kimi K3	79,612	218,575	298,187

Model sources. The task panels draw on Kimi K3 (Moonshot AI, n.d.), GLM-5.3 (Z.ai, n.d.), GPT-5.6 Sol (OpenAI, n.d.), MiniMax M3 (MiniMax, 2026) and Qwen3.8 Max (Alibaba Cloud, n.d.). We cite the corresponding official model documentation or release report; Qwen3.8 Max is listed in the official Model Studio catalogue. Table labels retain the naming used in the evaluation records.

Variant-specific references. Task 2 uses Claude Fable 5.1 (Anthropic, n.d.a) and DeepSeek v4.1 Flash (DeepSeek, 2026a); Task 3 uses Claude Opus 5 (Anthropic, n.d.b) and DeepSeek V4 Pro (DeepSeek, 2026b). Task 1 reports DeepSeek 4.1 without a variant suffix.