ASKING EARNS NOTHING: SCORING THE DECISION TO ACT IN BFCL MULTI-TURN

Anonymous authors
Paper under double-blind review

ABSTRACT

An agent that lacks the information it needs should ask rather than act, and the task definitions of agent leaderboards say so. BFCL multi-turn builds two of its four categories around a turn on which the model is supposed to ask, and its scorer never looks at that turn: the gold trajectory there is empty, the checker skips it, and the scripted user cannot answer, so asking earns nothing, guessing costs nothing on that turn, and asking twice loses the item. The benchmark also contains the control experiment for that decision. A should-ask item is a base item with one piece of information removed from one turn, so the same request appears twice at the same turn index, once complete and once not: on the first the model should make the call that changes the world, on the second it should ask. We score one decision per pair, whether the model attempted a world-changing call on that turn, read off the stored trajectories with no LLM judge; acting always and asking always both score 50.

On the 223 pairs that pose this decision, gpt-5.4 attempts the call on 83.4% of the complete turns and holds back on 78.0% of the incomplete ones, the best decision accuracy of seven models at 80.7%; on the same items the official score ranks it sixth and puts first a model that lands in the middle here. One added line telling gpt-5.4 not to ask pushes it toward acting on both sides of the pair, so its decision accuracy shows no detectable change, while its official score rises by 13.5 to 23.5 points on the two should-ask categories and on the base twins; the opposite line, telling gemma-4-31B-it to ask first, improves its decision by 4.5 points and gains no official score. The score moves with the push toward action, not with the decision. We release the pairs, a turn-level scorer that runs on any BFCL output directory without an API key, and 31 manually verified bad items.

1 INTRODUCTION

Language models now call tools, act on environments, and finish work across several turns. The leaderboards that rank them, BFCL among the most cited at model release, are the yardstick this young field optimizes against. This paper studies the scoring mechanism of BFCL multi-turn.

An anomalous ranking sent us there. gpt-5.4 is a strong general model, but on the 800 items of the four multi-turn categories its official score (raw hereafter) is 34.0%, fourth among the eight models we ran on all four categories, of ten we ran in total, and below open models of 27B and 9B.[1] All rankings in this paper are within that pool, not positions on the public leaderboard.

The cause is in the test design. BFCL multi-turn gives each item one scripted user and one gold trajectory. The scripted user reads its lines in order and never answers a question the model asks, and a turn the model leaves without a call fails the item wherever the reference trajectory has one. Two categories, miss_func and miss_param, the should-ask side, are built around a turn where information is missing, and the official paper defines the expected response there as a clarification request or a natural-language follow-up with no tool call. The scorer skips that turn: its gold trajectory is empty, so there is nothing to compare, and whether the model asked or guessed is never checked.

[1] The eight are gpt-5.4, Qwen3.6-27B, Qwen3.5-9B, gemma-4-31B-it, gemma-4-E4B-it, and three Tülu-3-8B checkpoints. deepseek-v4-flash and Qwen3.8-Max ran base, miss_func, and miss_param only. Table 1 uses the seven of the ten with per-turn rollouts on those three categories and a pinned or dated identity.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: (a) The scorer skips the under-specified turn; adapted from item miss_param_122. (b) The same 223 should-ask items scored two ways: the official accuracy on exactly those items, and the action decision read off the twin pairs, where always acting and always asking both score 50.

Figure 1a draws what follows. The user does not say which stock to buy. The cautious model asks. The reckless model guesses the ticker that appears most often in the answer keys. Neither is checked on that turn, and the item is decided on the remaining ones. The cautious model's question is not credited, and if it asks once more to confirm the ticker before the order, the scripted user does not answer, that turn has no call, and the item fails. Asking earns nothing and can cost the item. In real trading the guess is an order that cannot be recalled.

The benchmark contains the control experiment for this decision and never runs it. The four categories are perturbations of the same scenarios: a should-ask item is a base item with one piece of information removed from one turn, so the same request sits at the same turn index twice, once complete and once with a value or a function taken away. That is a matched pair, and it fixes what the right decision is on each side without anyone judging the model: make the world-changing call when the information is there, do not when it has been removed. Both decisions are read off the stored trajectory by asking whether the model attempted a call that changes the environment on that turn. A lookup does not count, an order or a file write does, and no judge or world state enters. Scoring the pair prices both errors at once: a model that always acts and one that always asks each score 50.

Measured this way, the official score does not carry the decision. On the 223 pairs where the reference's own call on that turn changes the world, gpt-5.4 attempts it on 83.4% of the complete turns and holds back on 78.0% of the incomplete ones, a decision accuracy of 80.7% and first of the seven models whose per-turn outputs we have. On the same 223 items the official score ranks it sixth of seven, at 32.7% against 52.5% for a 9B open model, and the official leader on these items, Qwen3.6-27B, sits in the middle of the field here. The official score is not measuring the decision these two categories were built around. It is measuring execution on the other turns.

The same intervention moves the score and leaves the decision within its interval. We added one line to the input of gpt-5.4 telling it not to ask and to act directly. The line pushes the model toward acting on both sides of the pair, so the two moves cancel in the decision, while the official score prices only the other turns. On miss_param the fraction of under-specified turns on which it attempts a world-changing call doubles from 11.4% to 22.8%, and raw rises from 31.5% to 45.0%. Decision accuracy changes by $+1.1$ points $[-2.5, +4.8]$, while the score rises by 13.5 to 23.5 points on the two should-ask categories and on the base twins. The opposite line, telling gemma-4-31B-it to ask before it guesses, raises its decision accuracy by 4.5 points and lowers its official score in three of the four categories. What the paired arms establish is what the score responds to: it rises with the push toward action whether or not the decision improves, and it does not rise when the decision does.

This paper makes three contributions. The first is a finding. On the multi-turn part of one of the most cited agent leaderboards, the turn that two of its four categories are built around is never scored: a question earns nothing, a second question loses the item, and across seven models the official score on these items does not order them by the decision they were built to test. The second is a measurement. The benchmark's own perturbation structure yields 223 matched pairs on which the

reference itself changes the world, each certified by hand. Scoring whether the model attempts that call takes no judge and no world state, has a chance level of exactly 50, and any leaderboard that builds an under-specified variant of an existing item already has the pair. The third is an intervention. One line of prompt pushes gpt-5.4 toward acting on both sides of the pair, its decision accuracy shows no detectable change, and the official score rises by 13.5 to 23.5 points. The opposite line improves gemma-4-31B-it's decision while its score falls in three of four categories. The score moves with the push toward action, not with the decision. We release the pairs, a turn-level scorer that runs on any BFCL output directory, and 31 manually verified bad keys.

2 Related Work

Asking before acting when information is insufficient has become its own topic in agent evaluation. HiL-Bench points out that an agent which guesses a missing requirement and one which asks for it receive the same score on current leaderboards (Trinh et al., 2026). Paired should-act and should-abstain suites measure whether models know when not to act and count a clarification request as abstention (Liu et al., 2026; Luo et al., 2026). That is the design we show BFCL already contains and never scores. An under-specified task is shown not to make an agent fail but to make it guess (Stoisser et al., 2026; Ji et al., 2026). Ojewale & Venkatasubramanian (2026) name the pattern where an evaluation either penalizes deferral or does not measure whether deferral was appropriate as compliance bias, in a position paper and synthetic scenarios. These build new tasks. We audit a deployed multi-turn tool leaderboard, and rather than adding a suite to it we score the paired suite already inside it.

Concurrently and independently, Zhao et al. (2026) noticed the same skip. Their diagnostic sorts each turn into one of four action classes and counts a trajectory as calibrated when the gold class appears on any turn, and their intervention retracts or retries a call using oracle knowledge of that class. They read the result as miscalibration in the model, across several multi-turn suites. We anchor every judgment to the single turn whose gold trajectory is empty and score it against the complete twin rather than by classifying the action, so the measure needs no judge and has a chance level of exactly 50. The two studies use the official score differently. They bound it by gold action recall and read any excess as the state grader masking miscalibration in the model. We push the decision with a one-line prompt and read the leaderboard's own number rising while behavior moves toward the side the task definition excludes. The fault we locate is in what the scorer rewards. Bhat et al. (2026) audit four tool-calling leaderboards including BFCL V4 and report 18.5% scorer–human disagreement, concentrated in brittle state comparison and mislabeling, without covering the under-specified turn. τ-bench lets a simulated user advance the dialogue according to the agent's behavior (Yao et al., 2025). The BFCL user is a fixed script, which is why a second question gets no answer.

Reference-answer leaderboards have scored wrongly before. SWE-bench Verified found, after reviewing items by hand, that some issue descriptions were too thin to determine what to do and that some tests reject valid patches that differ from the reference (Jimenez et al., 2024; Chowdhury et al., 2024). That is the failure we see here, and our 31 bad keys follow their remedy. BFCL scores in particular have proved fragile outside the model: Wang (2026) moves one model on BFCL V4 from 0.00 to 0.96 by changing only the serving adapter. Our rank reversal comes from the layer above, the scoring itself.

3 How BFCL Multi-Turn Scores a Trajectory

BFCL's V4 multi-turn part is 800 items (Patil et al., 2025), each a scripted user dialogue inside a simulated API domain, and each carrying one reference trajectory: the calls the item author expects on every turn. Scoring compares the two turn by turn. If the reference calls a tool on a turn and the model calls none, the item fails there, by what we will call the empty-turn rule. Otherwise the scorer compares the two worlds it maintains, the model's and the reference's, and requires the return values the reference obtained to be among those the model has obtained so far. The item passes only if every turn clears both checks.

The items form four categories of 200, perturbations of the same underlying scenarios, so items sharing an index share a task goal and an environment. base and long_context give the model everything it needs and are the should-act side. miss_func removes a required function from the tool

list on one turn and miss_param removes a required value from what the user says. On that turn the reference trajectory is empty and the official task definition asks the model to request the missing information rather than call a tool (Patil et al., 2025, Appendix D.2), so these two are the should-ask side. We call any turn whose reference trajectory is empty the under-specified turn. On the next turn the script supplies what was missing. It never answers the question the model asked.

An empty reference trajectory is the one case the comparison above cannot handle, and the scorer resolves it by skipping the turn.[2] A tool call the model makes there is still executed and still changes the world, it is simply never compared with anything. Ask or guess, what the model did on the under-specified turn is never scored there. A guess enters the verdict only later, through the state it leaves behind, and a question does not enter it at all. The benchmark did check this turn once and removed the check eight days later, saying it would instead assess whether the model performs correctly once the information is supplied. Nothing has replaced it since, and the check function is still imported with no call site (Appendix B).

The corridor is narrow in every category. Credit requires matching the reference step by step, so the same goal reached by another sequence of calls, a value written in another notation, or work the model finished a turn earlier than the script expects all read as divergence, and the item is lost although the user's request was met. Holding back on the under-specified turn is the one divergence for which the benchmark's own task definition already fixes what the model should have done, which is why it can be audited rather than argued about. Appendix B follows one item, the one Figure 1a is drawn from, through all ten models we ran.

4 Method: The Benchmark's Own Paired Control

4.1 Twin items and the action decision

The four categories are perturbations of the same underlying scenarios, and the perturbation that makes a should-ask item is the removal of one piece of information from one turn. It leaves a trace in the reference trajectory. Delete the single empty turn from the reference trajectory of a miss_param or miss_func item, and what remains is the reference trajectory of the base item with the same index, turn for turn. The two items are the same dialogue with one difference at one turn index: in miss_param the user's request there is missing a value the base item states, and in miss_func the text is the same and a required function has been taken out of the tool list. We call the two a twin pair and that turn the anchor.

A twin pair is a controlled comparison that the benchmark constructs and does not score. It fixes what the right decision is on each side without anyone judging the model. On the base side the information is present, so the model should make the call the turn asks for. On the should-ask side it has been removed, and the official task definition asks for a clarification request or a natural-language follow-up with no tool call there (Patil et al., 2025, Appendix D.2). The ground truth is the perturbation itself rather than the reference call sequence, which is what makes it auditable: a reader can put the two user turns side by side and see the value that was taken away.

The decision we score is whether the model commits to the action the turn requests. A call is world-changing if, when it succeeds, it does something to the environment that the user asked for and that the benchmark's own state checker would see: it writes or moves a file, places or cancels an order, posts a message, books a ticket, starts the engine. A lookup is not: reading a balance, listing a directory, checking a price. Logging in and out is not either: it sets an attribute, but it is a precondition of the requested action rather than the action, and counting it lowers every model by 0.4 to 1.1 points and leaves both ends of the order in place (Appendix F). We classify each of the 160 functions in the suite once from its source (Appendix D). The one function whose effect depends on its arguments, `echo`, counts only when it writes to a file. Whether the sandbox accepted the call does not matter: the decision was the model's, and a rejected order is still an order the model tried to place. We measure one binary decision per item, whether the model attempted a world-changing call

[2] The skip is the `continue` for an empty gold trajectory in `multi_turn_checker.py`, immediately after the empty-turn failure.

on the anchor turn, and score it against the twin:

$$\text{decision accuracy} = \tfrac{1}{2}\Big(\underbrace{\Pr[\text{attempt} \mid \text{information present}]}_{\text{act when complete}} + \underbrace{\Pr[\text{no attempt} \mid \text{information removed}]}_{\text{hold back when missing}}\Big). \tag{1}$$

This is balanced accuracy over the 2×2 of what the item required and what the model did, and it prices the two errors the same way. Because the same predicate is read on both twins, any strategy that ignores the information scores 50 in expectation: a model that attempts a world-changing call on every anchor turn, a model that never attempts one, and a model that looks something up on every turn and never commits. A model only rises above 50 by telling the two sides apart. Nothing in the definition consults an LLM judge, a world state, or the official verdict, so official passes and official failures enter on equal terms, and the reference trajectory enters only to locate the empty turn and to say whether the call withheld there changes the world. The measure is not a task completion rate and does not claim to be one: it says whether the model made the right call about committing on that one turn, not whether it went on to finish the item.

4.2 Reading the decision off a stored trajectory

The anchor is located mechanically, as the turn whose reference trajectory is `[]`, never chosen by a model or an annotator from impression. Four items across the two should-ask categories have more than one empty turn and are dropped rather than resolved. A call is counted only if it parses structurally out of the recorded output, in whichever format the model's handler emits, and the function name is on the item's tool list, on which the function that miss_func removed is kept. This is the extractor used for the injection experiment of §5.4 and it is what keeps prose such as "confirm you are already logged in" from registering as a call to `confirm`. A model that hallucinates a call to the removed function is therefore counted as attempting it.[3]

Two further filters run before the pairing. The 31 manually verified bad keys of Appendix C are removed, and so is any item whose base twin is absent or whose reference trajectory does not match its twin's. With the four multi-anchor items that leaves 380 pairs. We then verify the pairing at the level of content: the reference call strings must be identical turn for turn once the anchor is deleted, and every user turn before the anchor identical character for character. Fifteen pairs fail, six on the calls and nine on the dialogue, and we drop them. That leaves 365 content-verified pairs.

The pair is scored only where the anchor turn poses the decision. On 231 of the 365 the reference's own call on the base anchor turn changes the world. Eight of those fail an item-by-item certification of the label (§5.3, Appendix E), leaving the 223 pairs of Table 1, 116 from miss_func and 107 from miss_param, sharing 151 base twins. On the other 134 the reference only looks something up there, a zip code, a distance, a stock quote, or in two cases only logs in, so the withheld information gates a read rather than a write. Taking it away leaves no action to hold back from, so the pair cannot separate a model that reads what it can and then asks from one that guesses a value and reads with it. We list those pairs with the release and leave them out. The split is fixed by the reference trajectory before any model output is read, and the outputs bear it out: on the 134 pairs no model attempts a world-changing call on more than 3.0% of the complete turns or 11.2% of the withheld ones, so scoring them would add 134 pairs on which holding back is right on both sides and a model that never acts scores 100 (Appendix D).

4.3 What the model says when it holds back

Holding back is defined by the absence of a world-changing attempt, so the cell contains everything else: a question, a lookup followed by a question, a report that the function is unavailable, a refusal, an answer given in prose, or silence. Two checks bound what is actually in it, and §5.3 reports both. The first is mechanical: the held-back turns are almost never silent. The second reads the reply with a single-turn judge, deepseek-v4-flash, itself one of the scored models. It is the only place an LLM appears in this paper, and it verifies rather than scores. For each held-back anchor turn the judge sees exactly that turn: the request as the model received it, the same request from the base twin with the information present, the name of the removed function where there is one, the lookups the model made, and its reply. It sees no other turn, no world state, and no official verdict, and it returns one of

[3] Eight calls to names that no item offers were dropped by this validation, all on the should-ask side.

Table 1: The action decision on 223 twin pairs: the same request at the same turn with the needed information present (base) or removed (miss), where the reference's own call on that turn changes the world and the label has been certified by hand (§5.3). Act and hold count whether the model attempted a world-changing call there, official passes and failures alike, no judge, no world state; decision accuracy is their mean, so acting always and asking always both score 50. The last column credits, on the 27 compound turns, an attempt confined to the steps the turn authorizes independently of what was withheld, and on miss_func a route around the removed function that reaches the reference's own post-call state. Official raw is the benchmark's accuracy on exactly these items. 95% bootstrap over the 151 base twins. Bold marks the best in a column.

	official raw		action decision			
Model	miss items	base twins	act when complete	hold back when information removed	decision accuracy [95% CI]	credited
gpt-5.4	32.7	39.1	83.4	**78.0**	**80.7 [77.3, 84.1]**	**83.6**
gemma-4-31B-it	50.7	62.9	**97.8**	59.2	78.5 [75.1, 81.8]	82.1
Qwen3.8-Max	47.1	52.3	89.7	66.8	78.3 [74.3, 82.2]	82.3
Qwen3.5-9B	52.5	57.6	91.5	63.2	77.4 [73.5, 81.1]	81.6
Qwen3.6-27B	**58.7**	**77.5**	**97.8**	56.5	77.1 [73.3, 81.0]	81.4
deepseek-v4-flash	52.0	66.9	92.4	59.2	75.8 [71.8, 79.6]	80.9
gemma-4-E4B-it	22.9	25.8	83.4	52.0	67.7 [63.6, 71.8]	71.1

five labels, whether the reply asks for the removed information, asks about something else, refuses, proceeds in prose with a value it supplied itself, or none of these. No number in Table 1 depends on this judge, and we do not fold its labels back into the score.

5 RESULTS

5.1 THE UNDER-SPECIFIED TURN IS NOT SCORED

The anchor turn carries no weight in the official verdict either way: the scorer passes items on which the model attempted a world-changing call there and fails items on which it held back. Among the should-ask items gpt-5.4 passes, it had attempted a world-changing call on the anchor turn in 16.4% of them, and gemma-4-E4B-it in 45.1% of the items it passes (counts in Appendix F). Among the items each model fails the share is higher, between 24.7% and 60.9% across the seven, because a guess on that turn can break the state on a later one. The anchor turn enters the verdict, if at all, only through the turns after it.

A held-back item is lost, when it is lost, on a turn other than the one it held back on. Of the held-back items that fail officially, pooled over the seven models, none fails on the anchor turn, since the checker skips it. Half fail on a later turn on which the model did act and its execution diverged from the reference, and 28% were lost before the anchor was reached. A further 18.0% fail on a later turn on which the model wrote something and called nothing, the empty-turn rule. gpt-5.4 carries nearly half of those, mostly by restating what it still needs or declining again rather than asking afresh (counts in Appendix F). Holding back is never charged where it happens. When it is charged, it is charged on a later turn.

5.2 THE ACTION DECISION ON TWIN PAIRS

Table 1 scores the decision of Equation 1 for the seven models whose per-turn outputs we kept.[4]

The official score does not carry the decision. The model it ranks sixth on these items is first on the decision, and the model it ranks first sits in the middle of the field. gpt-5.4 is first at 80.7% and holds

[4]Models run under their BFCL registry configuration. gpt-5.4, deepseek-v4-flash and the three Qwen models use the native function-calling channel with no system prompt. The two gemma-4 models exist only as prompting entries and receive the official default system prompt, which itself asks the model to point out missing parameters, so the two channels are not a clean capability comparison. The three Tülu-3-8B checkpoints kept no per-turn rollouts and cannot be measured. Their should-ask raw is about 2%.

that position in 77.8% of bootstrap resamples. On the same 223 items the official score puts it sixth of seven, at 32.7%, below a 9B open model, and its leader, Qwen3.6-27B, is fifth here, inside a group of five models within 2.7 points of one another. By category the picture is the same, with gpt-5.4 first on miss_func, Qwen3.8-Max first on miss_param with gpt-5.4 just behind, and gemma-4-E4B-it last on both (Appendix F, with the rank correlation). What the official score orders these models by is execution on the other turns.

The two ends of the order do not depend on how strictly the withheld turn is read. The strict column takes the task definition literally, no world-changing call on the withheld turn. The credited column reads the request and charges only an attempt that needed what was withheld (§5.3). Under it gpt-5.4 is again first, at 83.6% in 58.6% of resamples, with gemma-4-31B-it and Qwen3.8-Max within 1.5 points. Every ordering claim in this section holds in both columns: gpt-5.4 is first in each, and the official leader is fifth in each.

The spread sits in one column. Every model attempts the call on most of the complete turns, and the models differ by 26 points in how often they hold back when the information has been removed, between 52.0% and 78.0%. The act column is not there to order models. It anchors the scale, since without it a model would be rewarded for never committing, and it prices what restraint costs: gpt-5.4 and gemma-4-E4B-it hold back on more base anchor turns than any other model, and both are charged for it (Appendix F). On a complete turn the user has said everything, and holding back there is charged as the wrong decision.

The definition matters most for the models that read before they decide. Qwen3.8-Max holds back on 66.8% of the withheld turns, and on 132 of those 149 it has looked something up first. On the item of Figure 1a it checks the login, the balance, and the watchlist, and then writes that the symbol is missing and not something to guess at for an irreversible trade (Appendix B). A rule that counts any call as acting reads that as four rash calls. Ours reads it as the decision it is.

5.3 The pairing survives the checks a reader would run

Four checks bound the ways the comparison could be wrong, all from the same stored rollouts.

First, the pairing. The twins share the dialogue up to the anchor, but the model's own calls before it can diverge between them, so the decision read at the anchor could inherit that difference. Restricting to the pairs on which the model's pre-anchor call sequence is identical in both twins leaves between 128 and 212 pairs, depending on the model, and changes nothing at either end (Appendix F). Neither end of the order depends on what happened before the anchor.

Second, what the held-back turn contains. Holding back is defined by the absence of a world-changing attempt, so a model that stalls, or only looks things up, would be scored as cautious. Neither is common in the cell. The held-back turns are almost never silent: pooled over the seven models, all but 15 carry natural-language text, nearly all of the silent ones gemma-4-E4B-it's. Read turn by turn by the single-turn judge of §4.3, 86.5% of held-back replies ask for the removed information or report the removed function as unavailable, and 5% proceed in prose as if the work were done or a value were known. The rest ask about something else, refuse without naming what is missing, or say nothing usable (ranges in Appendix F). By the judge's reading, holding back here overwhelmingly means asking or naming what is missing.

Third, the label. The label is the category's construction, which can fail: if the removed value is stated in or entailed by the dialogue, or is not needed by the call, then acting on the anchor turn is correct and holding back is a missed inference. We certified all 231 anchors by hand, answering a fixed set of questions on each pair from the item alone, without reading any model output (Appendix E). Eight pairs are construction errors and are removed, seven of them miss_param: an incomplete turn identical to the complete one, a withheld user id the account is already logged in with, a value stated earlier in the dialogue (Table E1). A further 27 anchors are compound turns, where the request also authorizes a world-changing step that does not depend on what was withheld, as when the door-locking function is removed and the same turn asks to engage the parking brake. The definition still says to ask there, so the strict column charges any attempt and the credited column does not count an attempt confined to those independent steps. Removing the eight lifts every model by under a point, and dropping the 27 as well leaves gpt-5.4 and Qwen3.8-Max tied at the top (Appendix E). The label holds, and certifying it moves no model by as much as a point.



Figure 2: Paired injection, the same items under a neutral and an injected prompt, each group on its own scale. Left: the share of under-specified turns with a world-changing attempt, 190 miss_func and 184 miss_param items. Middle: the official score, 200 items per category and the 153 base items twinned with the pairs before certification. Right: the decision accuracy of Table 1. Intervals of the change and McNemar p in the text.

Fourth, the withheld function. On the miss_func side an attempt could be a call to the function that was removed, or a route around it with the functions that remain, and a route can succeed: when `mv` is withheld, a model can copy, verify, and delete. Of the attempts pooled over the seven models, only 5 of 343 call the removed name, and the rest call other available world-changing functions (Table F1). To count the routes that reach the goal we replayed each such turn in the benchmark's own sandbox, on the pairs where the model arrived at the anchor in the reference state, and compared the state after it with the state the base twin's reference reaches. Between 14% and 24% of a model's aligned attempts land there. Table 1 reports both readings, the category as its definition states it, a turn on which to ask, and as a task to finish by any route. The route credit lifts every model by one to three points, and with the compound turns by three to five, and leaves gpt-5.4 first (Appendix F). The gap between the columns is a lower bound on what the strict count charges, since only aligned attempts could be credited.

5.4 One line of prompt moves behavior while the score rises

A scorer aligned with the task definition would price the under-specified turn. BFCL does not, which leaves the behavior on that turn and the score free to move independently. We test whether one line of prompt can separate them with a paired design: the same item under a neutral prompt and under an injected prompt, gpt-5.4 with pro-action on miss_func, miss_param, and the 153 base items twinned with the pairs before certification, gemma-4-31B-it with pro-caution on all four categories. Each should-ask category contributes the items with a unique under-specified turn that are neither on the bad-key list nor certified construction errors, 190 miss_func and 184 miss_param. The official scores alongside are the benchmark's own over all 200 items. The behavior metric is that of Table 1, whether the model attempted a world-changing call on the under-specified turn, and, since both arms generated the base twins, the paired decision accuracy on the 223 pairs. Each injection is one sentence, pro-action or pro-caution, quoted in Appendix A with the check that it reached the model.

The pro-action line raises world-changing attempts on the under-specified turn. Under it, the share of miss_param under-specified turns on which gpt-5.4 attempts such a call, the behavior the task definition excludes, doubles from 11.4% to 22.8% (McNemar $p = 5.7 \times 10^{-6}$), and on miss_func it moves the same way without reaching significance (Figure 2, left, and Appendix F). The push shows on the one turn the checker never compares.

On the twin pairs the same line pushes gpt-5.4 toward acting on both sides, and the two moves cancel in the decision. The act rate on the complete twins rises from 83.4% to 97.8% and the hold-back rate on the withheld twins falls from 78.0% to 65.9%, each almost all one way (McNemar $p < 10^{-5}$ on both sides, counts in Appendix F), and decision accuracy changes by $+1.1$ points $[-2.5, +4.8]$ (Figure 2, right). The line moved the model by about the same amount on both sides, and the decision stayed within its interval.

The official score does not cancel, and its gain is recorded on turns other than the under-specified one. It rises by 13.5 and 16.0 points on the two should-ask categories and by 23.5 points on the base twins (Figure 2, middle). We audited all 83 trajectories that flipped from fail to pass, ten of them line by line. None of the 47 whose first error carries a turn index loses it on the under-specified turn, and none of the ten guesses the removed parameter. About 55% are cured early terminations: the neutral arm asks, receives the information, and then goes silent on a later turn that the empty-turn rule fails, and the injected arm keeps going. Most of the rest are recoveries in multi-step tasks, and a few override a safety refusal that the gold trajectory itself does not respect (Appendix B). The fewer flips the other way come mostly from acting too much and breaking the final state. The line forbids asking and refusing and asks for continued execution, so the gain cannot be attributed to any one of the three.

The pro-caution line moves gemma-4-31B-it the other way. The share of under-specified turns on which the model attempts a world-changing call falls in both should-ask categories, on miss_param from 21.7% to 12.0% (McNemar $p = 4.0 \times 10^{-5}$) and on miss_func by a smaller margin that is still significant (Figure 2, left, and Appendix F). The opposite line pulls the other model away from acting on that turn.

On the twin pairs the decision improves, because the line moves the withheld side much more than the complete side. The hold-back rate on the withheld twins rises from 59.2% to 70.9%, while the act rate on the complete twins slips from 97.8% to 95.1% (counts and p in Appendix F), so decision accuracy rises by $+4.5$ points [$+1.8$, $+7.1$]. Where the sentence bites, then, whether a model commits or holds off on that turn is at least partly decision calibration and not a fixed capability ceiling.

The official score pays nothing for the better decision. On miss_param it moves by $+0.5$ points, with flips up and down nearly equal ($p = 1$), on miss_func it falls by 5.0 points ($p = 0.053$), and on the two should-act categories, where the same sentence is unneeded, it falls significantly (Figure 2, middle, and Appendix F). Read together, the two arms bracket one fact: the decision on the under-specified turn is not priced, and the score moves only with execution on the other turns, more of it in the pro-action arm and less of it in the pro-caution arm.

6 Discussion and Conclusion

An agent leaderboard is read as a measure of what a model can do. BFCL multi-turn measures it by asking the model to reproduce one expected trajectory: the scripted user delivers its lines on a fixed schedule, and the scorer matches execution results and environment state against a single gold path. That path is not the only solution to the task, and the design leaves no place for the model that stops to ask. What sent us to the leaderboard was an anomalous score. What we found is in the scoring layer.

The missing measurement was already built. Two of the four categories exist because one piece of information was removed from one turn of an item that also exists intact, so the benchmark contains matched pairs of the same request with and without what the model needs, and on 223 of them the call that information gates changes the world. Scoring the action decision on those pairs takes one bit per item, read off the stored trajectory with no judge and no world state, has a chance level of exactly 50, and charges holding back when the model should have acted as much as acting when it should have asked. On these seven models the official order does not carry over to it, and paired injection shows the same gap from the other side: one line pushes a model toward acting on both sides, leaves its decision within its interval, and raises the official score by 13.5 to 23.5 points, while the opposite line improves the decision and lowers the score in three of four categories. Any leaderboard that builds an under-specified variant of an existing item has already made the pair.

This matters beyond one leaderboard, because benchmarks steer what gets built (Manheim & Garrabrant, 2018; Skalse et al., 2022). The current scoring pays nothing for clarification and nothing for restraint, and one line of prompt shows the two moving apart. A vendor tuning the next model against this number is being told to act and press on rather than to ask. Deciding whether to act before deciding how to act is a safety property as much as a capability.

What a paired score cannot change is the shape of the test. The scripted user still cannot answer the question the model actually asked, and no script fixed in advance can. Our measure reads one bit from that turn and leaves the content of the question to a check. A benchmark that means to evaluate an interactive agent has to be able to answer it, and to score the reply as well as the world state, so that clarification and grounded refusal become first-class scoring actions.

REPRODUCIBILITY STATEMENT

Every number in Table 1 is produced without calling an LLM API. The released package contains the 223 twin pairs as a machine-readable manifest, each with its anchor turn index, its base twin, the tool list its calls are validated against, and its certification record, together with the 8 pairs the certification removed, the 134 pairs on which the reference only looks something up or logs in, every dropped item, and the filter that dropped it; the certification itself, the questions, the ruling and its reason on every pair, and the independent-step list of each compound turn; the classification of the suite's 160 functions as world-changing or not, with the rule for `echo`; a turn-level scorer that runs on any BFCL output directory with nothing but the Python standard library, so that no BFCL installation is needed to reproduce the decision columns of Table 1 or the right-hand scale of Figure 1b; a verification script that recomputes the table, the per-category, pre-anchor-history, and sensitivity variants, and the seeded bootstrap statistics ($B = 10000$, seed 20260612) and prints one PASS/FAIL line per published number, 591 of them; the machine-readable list of the 31 bad keys with one reason each (Appendix C); the prompt and the per-turn outputs of the single-turn classifier (§4.3), the only component that calls a model, and on which no number in Table 1 depends; and SHA-256 hashes for every file. The workaround credit of §5.3 is the one reading the package cannot recompute, because replaying a turn needs the benchmark's own executor; the package reproduces the strict columns and the compound half of the credited column. The rollout trees themselves are too large to ship: a model whose rollouts are not present locally reports SKIP, and a SKIP is never counted as a PASS.

ETHICS STATEMENT

This work involves no human subjects beyond the authors' own annotation of benchmark trajectories and collects no personal data. The material we analyze is a public benchmark and the outputs of models run on it. We do not accuse any model of having trained on the test data. The bad-key list is offered as a contribution to the benchmark, not as a criticism of its authors. The safety framing, that a leaderboard giving no credit for clarification offers no discrimination on whether an agent asks before taking irreversible actions, is a property of the scoring layer and not an evaluation of the deployment safety of any named model.

AI USE STATEMENT

In this work, we used generative AI tools to implement standard components of the experimental pipeline, to assist with data analysis and figure drawing, and to draft and edit parts of the paper. The trajectories this paper studies, and the labels the held-back-turn classifier of §4.3 assigns to them, are model output by design and are the object of study. We have reviewed all AI-assisted work: the released scorer and verification scripts were rerun by the authors and every published number checked against their output, and all drafted and edited text was read and approved by the authors. We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

REFERENCES

Vishvesh Bhat, Jay Vaghasiya, Muhammad Ahmed Mohsin, and Asad Aali. Benchmarking the benchmarks: A validity audit of tool-calling evaluation. *arXiv preprint arXiv:2607.02577*, 2026.

Neil Chowdhury, James Aung, Chan Jun Shern, Oliver Jaffe, Dane Sherburn, Giulio Starace, Evan Mays, Rachel Dias, Marwan Aljubeh, Mia Glaese, Carlos E. Jimenez, John Yang, Leyton Ho, Tejal Patwardhan, Kevin Liu, and Aleksander Madry. Introducing SWE-bench Verified. `https://openai.com/index/introducing-swe-bench-verified/`, 2024. OpenAI blog post, published 2024-08-13.

Zimo Ji, Zekai Zhang, Congying Xu, Zongjie Li, Yudong Gao, Shuai Wang, and Shing-Chi Cheung. Coding agents are guessing: Measuring action-boundary violations in underspecified DevOps instructions. *arXiv preprint arXiv:2607.02294*, 2026.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.

Xun Liu, Yi Evie Zhang, Vira Kasprova, Parisa Rabbani, Pardis Sadat Zahraei, Tianyu Zhang, Ali Ebrahimpour-Boroojeny, and Varun Chandrasekaran. AgentAbstain: Do LLM agents know when not to act? *arXiv preprint arXiv:2607.10059*, 2026.

Han Luo, Bingbing Wen, and Lucy Lu Wang. Agentic abstention: Do agents know when to stop instead of act? *arXiv preprint arXiv:2606.28733*, 2026.

David Manheim and Scott Garrabrant. Categorizing variants of Goodhart's law. *arXiv preprint arXiv:1803.04585*, 2018.

Mao, Huanzhi (ShishirPatil/gorilla). [BFCL] update eval metric for multi turn irrelevance scenarios. `https://github.com/ShishirPatil/gorilla/pull/725`, 2024a. GitHub pull request #725, merged 2024-10-31.

Mao, Huanzhi (ShishirPatil/gorilla). [BFCL] refine evaluation metric for multi turn categories. `https://github.com/ShishirPatil/gorilla/pull/733`, 2024b. GitHub pull request #733, merged 2024-11-08. Quote: "Instead of checking if the model produces no output in a turn with missing function/parameter information, we now assess whether the model can perform correctly once the missing information is provided.".

Victor Ojewale and Suresh Venkatasubramanian. Designing for doubt: The case for informed abstention in autonomous agents. *arXiv preprint arXiv:2606.02965*, 2026.

Shishir G. Patil, Huanzhi Mao, Fanjia Yan, Charlie Cheng-Jie Ji, Vishnu Suresh, Ion Stoica, and Joseph E. Gonzalez. The Berkeley function calling leaderboard (BFCL): From tool use to agentic evaluation of large language models. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, volume 267 of *Proceedings of Machine Learning Research*, pp. 48371–48392. PMLR, 2025.

Joar Skalse, Nikolaus H. R. Howe, Dmitrii Krasheninnikov, and David Krueger. Defining and characterizing reward gaming. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

Josefa Lia Stoisser, Marc Boubnovski Martell, Sidsel Boldsen, Kaspar Märtens, and Robert Kitchen. Ambig-DS: A benchmark for task-framing ambiguity in data-science agents. *arXiv preprint arXiv:2605.09698*, 2026.

Tu Trinh, Mohamed Elfeki, Guangze Luo, Kelvin Luu, Nathan Hunt, Ernesto Hernandez, Nandan Marwaha, Yannis Yiming He, Charles Wang, Fernando Carabedo, Alessa Castillo, and Bing Liu. HiL-Bench (human-in-loop benchmark): Do agents know when to ask for help? *arXiv preprint arXiv:2604.09408*, 2026.

Wenbo Wang. Interface-induced trajectory censoring. *arXiv preprint arXiv:2609.03966*, 2026.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025.

Kangjia Zhao, Jiajun Li, Haozhan Shen, Wei Chow, Linfeng Li, Hang Song, Lingdong Kong, Chen Zhi, Tiancheng Zhao, Songhua Liu, and Jianwei Yin. Calibration is the bottleneck: An action-class diagnostic of multi-turn tool-calling. *arXiv preprint arXiv:2609.00949*, 2026.

A Full Text of the Injections

Each arm has one block of injected text, quoted verbatim below.

gpt-5.4 runs through the function-calling channel, which carries no system prompt of its own, so the injection enters as a developer-role message and is the only system-level instruction in the dialogue.

```
You are an autonomous agent.  As long as you have enough
information to proceed, immediately take the necessary
actions using the available tools to complete the user's
request.  Do not ask the user follow-up or clarifying
questions, and do not refuse the task --- just carry it
out.
```

gemma-4-31B-it runs through the prompting channel, and the injection is appended after the official default system prompt. Its arm uses the text below.

```
Before taking any action that changes state, make sure you
have every required piece of information and that the user's
request is unambiguous.  If a required parameter value or
function is missing, or if the request is ambiguous or
underspecified, ask the user a clarifying question first
instead of guessing or making assumptions.  Do not perform
state-changing actions until the request is fully specified.
```

Neither text mentions a specific function, a specific item, or the scoring rules. We checked separately that the injection reached the model. On the gpt-5.4 side we compared the first-step input token counts of paired items, and the injected arm has exactly 59 more tokens on every paired item with a count on both sides in all three categories (two neutral miss_param rollouts crashed and carry none), which matches the length of that text. On the gemma-4-31B-it side we read the system message in the result files directly: every item that produced a rollout carries the injected text, and the same position in the neutral baseline does not. On long_context, 38 items in the neutral run and 37 in the injected run, largely the same ones, exceed the 32k-token serving window before the dialogue ends and produce no rollout; they are scored as failures in both.

B Worked Examples

This appendix collects the items used as worked examples in the main text, so that a reader can check the mechanism against concrete trajectories. All content below is taken from the item text, the reference answer, and the recorded rollouts. Nothing is reconstructed from memory.

miss_param_122, the full mechanism in one item. Figure 1a is adapted from this item. The user asks to buy 100 shares at $150 without naming the stock, the gold trajectory for that turn is empty, the scripted user supplies AAPL on the next turn, and the gold trajectory there is `place_order(AAPL, 150, 100)`, followed by order details, cancellation, and logout. Under the neutral condition gpt-5.4 and gemma-4-31B-it ask on the first turn, place the order on the second, and pass; gemma-4-E4B-it makes a placeholder call with a question mark before asking, and also passes. With the pro-action prompt gpt-5.4 calls `place_order(symbol="PROM")` on the first turn, the sandbox rejects it with `Invalid stock symbol`, the environment is unchanged, and the item passes. Qwen3.6-27B and the three Tülu models guess AAPL, place the order, match the state exactly, and then issue no call on the second turn, so the empty-turn rule fails them. Qwen3.5-9B asks, then only checks the quote and the account, and also fails, and deepseek-v4-flash does the same after two read-only calls, flagging the price gap on the second turn instead of placing the order. Qwen3.8-Max, the model we added most recently, is the case discussed in §5.2: it makes four read-only calls on the under-specified turn, works out that the order would cost $15,000 of a $16,000 balance, states that it will not guess a symbol on an irreversible trade, places the order correctly on the next turn, and passes; none of the four calls changes the world, so it holds back under our definition. The under-specified turn itself never enters the verdict in any of these cases. The item also fixes our mechanical convention. The `place_order(symbol="PROM")` that the sandbox rejected counts as an attempt to change the world, because the decision to act was the model's; that the sandbox left the environment unchanged does not turn a guessed order into restraint.

miss_param_87, the design of the should-ask side. On turn 0 the user asks to convert "some gallons" into liters without giving a quantity; that is the removed parameter, and the gold trajectory for the turn is `[]`. On turn 1 the scripted user supplies "60 gallons" according to the script and the gold trajectory is `gallon_to_liter(gallon=60.0)`. Turn 2 adds 20 gallons of fuel. Turn 3 is

a four-step start sequence: engage the parking brake, lock the doors, press the brake pedal, and start the engine. Turn 4 checks tire pressure and, if it is below 33, finds the nearest repair shop. Under the neutral prompt gpt-5.4 asks the correct follow-up on turn 0 and still fails the item, and the point is lost downstream on turn 3, where a missing or out-of-order brake-pedal step leaves the engine unstarted and the final state mismatched. This is the ordinary shape of a correctly held-back item: the behavior on the under-specified turn is right and the item fails elsewhere, on a turn the official score does price.

miss_param_141, an early-termination flip. This is one of the 83 neutral-fail to pro-action-pass flips of §5.4 and belongs to the largest flip channel. Both arms ask for the ticker on the under-specified turn and both receive TSLA from the scripted user, and both then execute the next two turns correctly. The neutral arm then emits nothing for three consecutive turns, where the gold trajectory calls for buying GOOG, querying the order, and sending a message, and each empty turn against a non-empty gold trajectory fails the item immediately. The injected arm carries those turns out and passes. The clarification is identical in the two arms; only the sustained execution afterwards differs, and only that difference is priced.

miss_func_22, a flip past a safety refusal. Both arms initially decline to use the plaintext password pasted into the item text. The neutral arm keeps declining on the following turn and therefore produces an empty turn against a non-empty gold trajectory. The gold trajectory itself calls `authenticate_twitter` with that password and then posts, so the pro-action arm, which complies, matches it and passes. This channel accounts for only a few of the 83 flips, but it shows the direction of the incentive plainly.

Format-only failures, base_75 and long_context_75. The model reports "32.0 PSI" where the reference answer writes "32 PSI". The values are equal and the notation differs, and the item is failed. The official score charges for it; the action decision of §4.1 does not look at it, because the model did call the tool on the turn where it should have.

A genuine capability failure, the lock-door string bug. The gemma family repeatedly passes the boolean parameter of the lock function as the string `'false'`, so the doors never lock and the dependent ignition steps fail in sequence. The model acts, so this is a correct decision and an incorrect execution, and the two are what Table 1 keeps apart.

The provenance of the skipped turn. PR #725 in the gorilla repository (merged 2024-10-31) introduced `flag_task_unachievable` and enabled `multi_turn_irrelevance_checker`; PR #733 (merged 2024-11-08) removed the flag and commented out the checker call (Mao, Huanzhi (ShishirPatil/gorilla), 2024a;b). The stated reason, quoted verbatim from the PR description, is: "Instead of checking if the model produces no output in a turn with missing function/parameter information, we now assess whether the model can perform correctly once the missing information is provided." A later packaging commit deleted the commented-out block and left only the import. As of 2026-09-08 our frozen copy of `multi_turn_checker.py` is byte-identical to the one on the gorilla main branch, bfcl-eval 2026.3.23 is still the latest release on PyPI, and no issue or pull request in the repository discusses crediting clarification on the under-specified turn.

C THE BAD-KEY LIST

The 31 excluded items are listed below by category and scenario index, and the released package carries the full one-line adjudication for each. Because the four categories are perturbations of the same underlying scenarios, a defect in a shared reference answer recurs across categories under the same index: scenario 4 is excluded in all four categories, scenarios 172 and 197 carry a credit-card year that is off by one, and scenario 187 writes priority 5 as 4.

The adjudication reasons fall into three families. Family A collects objective errors in the reference answer, where the gold trajectory contradicts the item text or fabricates content the user never asked for, for example a gold tweet that strips quotation marks from a file the user asked to send "exactly as it is", or a tweet of the two filenames a directory listing shows to which the gold adds a dozen image files that no listing can produce. Family B collects disputed cases where the gold trajectory invents an unrequested argument or relies on a constant we could not confirm, for example a hardcoded priority

Table C1: The 31 excluded items, by category and scenario index. Every entry was adjudicated by hand after mechanical pre-filtering.

Category	n	Scenario indices
base	5	4, 30, 176, 178, 187
long_context	12	4, 11, 18, 26, 27, 28, 32, 41, 43, 144, 172, 197
miss_func	7	4, 15, 30, 83, 133, 172, 197
miss_param	7	4, 30, 172, 178, 187, 195, 197
Total	31	

Table C2: Reason families for the 31 excluded items.

Family	n	Description
A	22	Objective error in the reference answer: it contradicts the item text, fabricates content, alters content the user asked to send verbatim, or uses constants from the wrong scenario branch.
B	5	Disputed reference answer: an unrequested argument is invented, or a constant could not be confirmed.
C	4	Defect found during the human annotation pass: two task defects and two perturbations that do not change the underlying scenario.
Total	31	

for a complaint whose text never mentions priority. Family C collects the four defects that surfaced during a human annotation pass over 100 items rather than through the mechanical filter, two task defects and two perturbations that are no-ops on their underlying scenario.

These 31 items are a verified set of defects, not a full review of all 800 items. The mechanical pre-filter selected 151 candidates by a cross-model all-strong-fail rule, so it cannot surface a mislabeled item that some model happens to reproduce; the remaining items are uncertified rather than certified correct. Keeping them changes no decision accuracy in Table 1 by more than 0.8 points: 7 of the 14 that fall in the should-ask categories survive the other pairing filters, and adding them back moves gpt-5.4 from 80.7 to 80.0 and every other model by less.

D Pairing, Exclusions, and the Held-Back Turn

How the pairs are formed. The two should-ask categories hold 400 items. 14 are on the bad-key list of Appendix C. 4 have more than one turn with an empty reference trajectory, items 167 and 180 in each category, and are dropped rather than resolved, since the anchor would otherwise have to be chosen by judgment. 2 have no base item whose reference trajectory matches theirs once the empty turn is deleted. That leaves 380. The content check of §4.2 then drops 15 more: 6 whose reference call strings differ from the twin's although the per-turn call counts agree, and 9 whose dialogue before the anchor was rewritten, so that the two items no longer put the same request at the same point. 365 remain, 182 from miss_func and 183 from miss_param. Of these, 231 have a base anchor turn on which the reference makes a world-changing call, 117 from miss_func and 114 from miss_param; the certification of Appendix E removes 8 of them as construction errors, and the remaining 223, 116 and 107, are the pairs of Table 1. The other 134, 65 from miss_func and 69 from miss_param, have a reference anchor turn that only reads, most often `get_zipcode_based_on_city` (39), `estimate_distance` (20), `get_stock_info` (14), and `cd` (12), or that only logs in (2). On those 134 the reference attempts no world-changing call on either twin's anchor turn, and the models rarely do either: across the seven models the attempt rate on the complete turn is 0.0 to 3.0% and on the withheld turn 2.2 to 11.2%, the latter highest for deepseek-v4-flash and Qwen3.8-Max, and every

model makes no attempt on both sides of at least 86.6% of them. The two sides of such a pair call for the same decision, so a model that never acts would score 100 on them and the chance level of 50 that Equation 1 relies on would no longer hold. Every dropped or unscored item and its reason are listed in the released manifest.

What counts as a call. A call is counted only when it parses structurally out of the model's recorded output and its name is on the item's own tool list, the function that miss_func removed included. The three output formats in our runs are native function-calling records, `<tool_call>` JSON blocks, and bracket-group text parsed with the benchmark's own recipe. Validating names against the item's tool list is what keeps prose from registering as a call: without it, "confirm you are already logged in" produces a call to `confirm`, and a destination named Rivermist produces a call tagged as a mutation because `rm` is a substring. The tool list includes the function that miss_func removed, so a model that hallucinates a call to the missing function is counted as attempting it. A call the sandbox rejected still counts, because the decision to act was the model's.

What counts as world-changing. The suite exposes 160 functions across its API classes. We read the source of each once and labeled it by whether a successful call alters a public attribute of an involved instance, which is the comparison the benchmark's own `state_checker` performs: 59 do (writes, moves, orders, posts, bookings, messages, ignition), 94 only read, and 7 log in or out. The login functions do set attributes, and we exclude them by convention: a login is a precondition of the action the turn asks for, not the action, and counting it would credit a model for acting when all it did was authenticate. Counting the seven as world-changing adds two pairs, lowers every model in Table 1 by 0.4 to 1.1 points, and leaves both ends of the order in place. `echo` is the one function whose effect depends on its arguments and is decided per call: it prints unless given a file name, in which case it writes. The labels ship with the release so that a reader can change any of them and recompute.

Run configuration. All trajectories come from `bfcl_eval` 2026.3.23 under each model's registry configuration, one rollout per item at the harness default temperature of 0.001. The five Table 1 models of the original pool were generated between 2026-05-21 and 2026-06-08; deepseek-v4-flash and Qwen3.8-Max were added on 2026-09-16. The API models are called through their provider endpoints; Qwen3.8-Max is the dated snapshot `qwen3.8-max-0902`, and the other aliases pin no dated snapshot. The open-weight models are served locally with vLLM 0.10.2 in BF16, no quantization, and the injected arms of a given model are generated under the same serving configuration as its neutral arm, so the paired comparison is within one configuration. Item bootstrap and McNemar therefore resample items, not generations: the intervals describe sampling of the items with each model's single rollout held fixed.

E Anchor Certification

The label of a pair is its construction: on the incomplete twin the model should ask. §5.3 lists the ways that can fail. We certified all 231 gold-mutator pairs by hand, without reading any model output.

The questions. For each pair we read the initial world state, the dialogue up to the anchor, the anchor turn in both versions, the scripted follow-up on the incomplete side, the tool list with the withheld function marked, and the reference calls, and answered a fixed set of questions: whether the withheld value is stated in or logically entailed by the dialogue (a value that is merely discoverable in the environment, or guessable, does not count); whether the withheld value or function is actually needed by the reference call; whether the incomplete turn also authorizes a world-changing step that does not depend on what was withheld, given the user's authorization and the simulator's preconditions; and whether the complete side's information and reference are themselves adequate. The questions, the ruling and its reason on every pair, and the independent steps of each compound turn ship with the release.

The rulings. Thirty-five pairs are exceptions. Five close calls stay valid: one where the user explicitly asks for a step that looks redundant and the reference performs it, one where the request read literally does not name the file to be moved, and three where the only step independent of the

withheld function is a login, which is not counted as world-changing. Six first-pass rulings were revised on a second reading, three from valid to construction error, two from compound to valid, and one from compound to construction error, and every final ruling carries its reason in the release. The final tally is 196 valid, 8 construction errors (Table E1), and 27 compound turns (Table E2). Removing the 8 raises every model in Table 1 by 0.5 to 0.8 points; on the 231 pairs before certification gpt-5.4 is first at 79.9% in 74.9% of resamples, on the 223 at 80.7% in 77.8%, and on the 196 pairs with the compound turns removed as well it is level with Qwen3.8-Max at 82.1%, first in 34% of resamples against 34%.

The credited reading. For each compound turn we listed which of the reference's world-changing calls the turn authorizes independently of what was withheld, which excludes any call that depends on the withheld step through the simulator's own preconditions: the engine cannot be started while a door is unlocked, so when the door-locking function is withheld, starting the engine is not independent. Under the credited column of Table 1 an attempt on the incomplete twin that stays inside the independent steps is not counted as acting; any other world-changing attempt is. On 8 of the 27 the withheld function is read-only, so every world-changing call on the turn is independent and the credited reading charges only an attempt to do something else. The strict column charges every attempt, as the category's definition says to ask.

Table E1: The 8 pairs removed as construction errors. On each, acting on the incomplete turn is correct, so the pair cannot be scored as a decision to ask.

Pair	Why
miss_param_199	incomplete turn identical to the complete one; card id and token stated
miss_param_101	withheld value is the user's own id; already logged in, not used by the call
miss_param_95	withheld value is the user's own id; already logged in, not used by the call
miss_param_88	withheld origin appears in the turn's own tweet text
miss_param_104	withheld value named earlier in the dialogue
miss_param_115	withheld value stated earlier in the dialogue
miss_param_185	withheld access code stated earlier in the dialogue
miss_func_42	reference `touch` on the complete side omits the requested directory; `touch` and `echo` both withheld

F Additional Results

The decision by category. The two should-ask categories remove different things and the reply that counts as holding back differs accordingly: miss_param takes a value out of what the user says, and miss_func takes a function out of the tool list, so the model has to notice that what it needs is not there rather than that the user left something out. Most models do somewhat worse on miss_func. On the 116 miss_func and 107 miss_param pairs, decision accuracy is 79.7 and 81.8 for gpt-5.4, 74.6 and 82.2 for Qwen3.8-Max, 75.9 and 81.3 for gemma-4-31B-it, 76.3 and 78.5 for Qwen3.5-9B, 76.7 and 77.6 for Qwen3.6-27B, 73.3 and 78.5 for deepseek-v4-flash, and 65.5 and 70.1 for gemma-4-E4B-it. gpt-5.4 is first on miss_func and Qwen3.8-Max on miss_param, the latter by 0.4 points; gemma-4-E4B-it is last on both. Over the seven models the rank correlation between official raw on the 223 items and decision accuracy is -0.11, too few points to pin down.

Routes around the withheld function. Table F1 breaks down the miss_func attempts of §5.3. An attempt is classified by replaying the model's own turns up to and including the anchor in the benchmark's sandbox: it is aligned if the state before the anchor equals the state the base twin's reference reaches before its anchor, and an aligned attempt is a workaround if the state after the anchor equals the state the reference reaches after its call. On 14 of the 223 pairs the reference call itself leaves the state unchanged, a rejected order or an addition of something already present, and a failed attempt would match trivially; those are not credited. The last three columns give decision accuracy strict, with every credited workaround counted as a correct decision on the withheld side, and with the compound turns of Appendix E credited as well, which is the credited column of Table 1. The workaround credit alone raises the seven models by 1.4 to 2.7 points, and with the compound turns by 2.9 to 5.2, and gpt-5.4 is first under both.

Table E2: The 27 compound turns. Independent: world-changing calls of the reference anchor turn that the request authorizes and that do not depend on what was withheld; gated: those that do. Logins are not listed. miss_param pairs withhold a value rather than a function.

Pair	Withheld	Independent	Gated
miss_func_31	wc, tail, cat	mkdir, mv	—
miss_func_37	echo	touch	echo
miss_func_38	rmdir	rm	rmdir
miss_func_50	lockDoors	setHeadlights	lockDoors
miss_func_54	liter_to_gallon	lockDoors, pressBrakePedal, startEngine	—
miss_func_55	fillFuelTank	lockDoors, pressBrakePedal, startEngine	fillFuelTank
miss_func_63	activateParkingBrake	fillFuelTank, lockDoors, pressBrakePedal	activateParkingBrake, startEngine
miss_func_64	pressBrakePedal	lockDoors	pressBrakePedal, startEngine
miss_func_65	retweet	comment	retweet
miss_func_69	estimate_distance	fillFuelTank	—
miss_func_73	startEngine	activateParkingBrake, lockDoors, pressBrakePedal	startEngine
miss_func_76	lockDoors	pressBrakePedal	lockDoors, startEngine
miss_func_80	lockDoors	pressBrakePedal	lockDoors, startEngine
miss_func_85	fillFuelTank	lockDoors, pressBrakePedal, startEngine	fillFuelTank
miss_func_86	lockDoors	activateParkingBrake, pressBrakePedal	lockDoors, startEngine
miss_func_87	lockDoors	activateParkingBrake, pressBrakePedal	lockDoors, startEngine
miss_func_88	lockDoors	fillFuelTank, activateParkingBrake	lockDoors
miss_func_91	get_outside_temperature_from_google	send_message	—
miss_func_169	retrieve_invoice	book_flight	—
miss_func_171	book_flight	set_budget_limit	book_flight
miss_func_173	compute_exchange_rate	set_budget_limit	—
miss_func_185	get_flight_cost	set_budget_limit	—
miss_func_198	book_flight	post_tweet	book_flight, cancel_booking
miss_param_17	a value	add_contact	send_message
miss_param_55	a value	lockDoors, pressBrakePedal, startEngine	fillFuelTank
miss_param_69	a value	lockDoors, pressBrakePedal, startEngine	post_tweet
miss_param_74	a value	lockDoors, pressBrakePedal, startEngine	—

Table F1: miss_func attempts on the withheld turn (116 pairs). Removed: calls the removed function by name. Aligned: the model reached the anchor in the reference state. Workaround: aligned and reached the reference's post-call state by other functions, excluding the pairs whose reference call is a no-op. acc: Table 1 strict accuracy; acc′: with those workarounds credited; credited: with the compound turns credited as well, the last column of Table 1.

Model	Attempts	Removed	Aligned	Workaround	acc	acc′	credited
gpt-5.4	29	0	28	6	80.7	82.1	83.6
gemma-4-31B-it	54	4	45	7	78.5	80.0	82.1
Qwen3.8-Max	49	0	48	10	78.3	80.5	82.3
Qwen3.5-9B	47	0	44	9	77.4	79.4	81.6
Qwen3.6-27B	50	0	49	9	77.1	79.1	81.4
deepseek-v4-flash	53	0	50	12	75.8	78.5	80.9
gemma-4-E4B-it	61	1	49	7	67.7	69.3	71.1

The act column, and what caution costs. gpt-5.4 makes no world-changing attempt on 37 of the 223 base anchor turns, and Table 1 charges it for all of them. They are not collapses. On 16 it looks something up and stops there; on the other 21, which fall on 17 distinct base twins, it makes no call and writes out what it is waiting for: it asks for an order ID, it asks for the trading or Twitter credentials before it will act on the account, it declines to use a password pasted into the item text, and before a purchase it states the amount and asks for approval the scripted user will never give.

None of the replies is empty. The comparison that makes the column readable is gemma-4-E4B-it, which makes no attempt on 37 base anchor turns; 23 of them carry no call at all, on 18 twins, and 12 of those 23 outputs are empty, every one because the rollout had ended before the anchor. The same column therefore prices two different things, deliberate over-caution and generation failure, and separates them only through the content of the turn. This is the one place where our measure charges a model for the behavior the paper otherwise argues for, and we report it rather than exempt it: on a turn where the user said everything, waiting for permission is the wrong decision.

Where held-back items are lost. Pooled over the seven models, 467 held-back items fail officially, and 84 of them, 18.0%, fail on a later turn with text and no call. For each held-back should-ask item that the official scorer fails, the failing turn is read from the score file: the error message names it for empty-turn and response-mismatch failures, and for state-mismatch failures it is the number of per-turn execution records the checker stored. Per model, the number of held-back items that fail on a later turn with text and no call is 40 for gpt-5.4, nearly half of the 84, 14 for gemma-4-E4B-it, 9 for deepseek-v4-flash, 8 for Qwen3.5-9B, 5 for Qwen3.6-27B, and 4 each for gemma-4-31B-it and Qwen3.8-Max; the benchmark's own error type for every one of these is the empty-turn failure, which is an independent check of our call extractor. Placeholder arguments are rare on both sides: of the world-changing calls attempted on withheld anchor turns, 1.4% carry an empty string or an explicit marker such as `TBD`, against 0.7% on the complete twins, so a model that acts without the information almost always supplies a plausible value rather than a visible placeholder. The held-back turns themselves number 970 over the seven models. The model looked something up first on 496 of them, and 15 carry no natural-language text, 13 of them gemma-4-E4B-it's. Under the single-turn judge of §4.3, the share of held-back replies that ask for the removed information or report the removed function as unavailable is between 76% and 91% per model, and the share that proceed in prose as if the work were done or a value were known is between 3% and 9%. On the pass side, of the should-ask items in the 223 pairs that the official scorer passes, gpt-5.4 passes 73 and had attempted a world-changing call on the anchor turn in 16.4% of them, Qwen3.6-27B passes 131 and had in 31.3%, and gemma-4-E4B-it passes 51 and had in 45.1%.

Sensitivity of Table 1. Three variants of the table move no model out of its place at either end. Counting the seven login and logout functions as world-changing gives 225 pairs and lowers every model by 0.4 to 1.1 points. The 223 pairs share 151 base twins and 184 distinct base anchor turns, so the act column weights some base rollouts more than once; counted once per distinct anchor turn instead, every act rate moves by at most 1.6 points (Qwen3.8-Max 91.3%, gpt-5.4 and gemma-4-E4B-it 82.1%, Qwen3.6-27B and gemma-4-31B-it 97.3%), and the pro-action flips on gpt-5.4 are 28 against 0. The bootstrap intervals already resample base twins as clusters. Restricting to the pairs on which the model's pre-anchor call sequence is identical in both twins leaves between 128 and 212 pairs per model, and gpt-5.4 stays first at 79.7% and gemma-4-E4B-it last at 68.6%. Restoring the 31 bad keys adds 7 pairs and moves no model by more than 0.8 (Appendix C). A rollout that ended before the anchor turn is scored as making no call on it; among the 223 pairs gemma-4-E4B-it has 12 such base rollouts and 9 such should-ask rollouts, every other model has at most 1, and dropping those pairs moves gemma-4-E4B-it from 67.7 to 69.2 and every other model by at most 0.1. Before the certification, on all 231 gold-mutator pairs, gpt-5.4 was first at 79.9% in 74.9% of resamples (Appendix E).

Selectivity of the injection. On gemma-4-31B-it, which runs all four categories, overall activity on the should-act side moves very little under pro-caution. The median number of calls per item goes from 8.0 to 7.0 on base and stays at 6.0 on long_context. The change concentrates on the under-specified turn. The gpt-5.4 arm's base twins show the mirror image: the pro-action line raises the act rate to 97.8% and the official base score by 23.5 points, so on the should-act side the score rises with the same push. The channel of its should-ask raw increase is supported by the item-by-item flip audit in §5.4. The item-level counts behind §5.4 are as follows. Under pro-action on gpt-5.4, the share of miss_param under-specified turns with a world-changing attempt rises from 11.4% to 22.8%, 22 items moving that way and 1 the other, McNemar $p = 5.7 \times 10^{-6}$, and the miss_func share from 18.4% to 22.1%, 12 against 5, $p = 0.14$. On the 223 pairs the act rate on the complete twins rises from 83.4% to 97.8%, 28 of the 184 distinct anchor turns against 0, $p = 7.5 \times 10^{-9}$, and the hold-back rate on the withheld twins falls from 78.0% to 65.9%, 30 against 3, $p = 1.4 \times 10^{-6}$. Decision accuracy on the pairs goes from 80.7% to 81.8%. The official base score on the twins rises

from 39.2% to 62.7%, 43 items against 7, $p = 2.1 \times 10^{-7}$. Of the 83 fail-to-pass flips, 47 have a first error that carries a turn index, and 24 items flip the other way. Under pro-caution on gemma-4-31B-it, the miss_param share falls from 21.7% to 12.0%, 19 items turning cautious and 1 the other way, $p = 4.0 \times 10^{-5}$, and the miss_func share from 33.7% to 27.4%, 13 against 1, $p = 0.002$. On the pairs the act rate on the complete twins slips from 97.8% to 95.1%, 7 distinct anchor turns against 1, $p = 0.07$, and the hold-back rate on the withheld twins rises from 59.2% to 70.9%, 28 against 2, $p = 8.7 \times 10^{-7}$, and decision accuracy goes from 78.5% to 83.0%. The official score on miss_param moves by $+0.5$ points with 19 flips up and 18 down, $p = 1$, miss_func falls by 5.0 points, $p = 0.053$, base falls from 65.0% to 58.5%, $p = 0.035$, and long_context from 39.0% to 33.0%, $p = 0.0042$.