MODEL CONTEXT AGENTS: VALIDATED AGENTIC WORKFLOW VIA AGENTIC PLANNING

Anonymous authors
Paper under double-blind review

ABSTRACT

The Model Context Protocol (MCP) has become the standard for connecting large language models to external tools, but it standardizes only how a service is *accessed*, leaving every client to rediscover how it should be *used*. That burden falls on a reactive loop that chains tool calls one at a time and judges its own success; on realistic multi-step tasks it is unreliable, costly, and offers no guarantee the goal was met. We argue that the service should ship its own expert. We introduce the *Model Context Agent* (MCA), an abstraction in which planning, execution, validation are provided by the server rather than delegated to a general-purpose model, and a server-agnostic engine that realizes it: a grounded planner compiles a goal into an ordered tool-call sequence, a deterministic executor replays it with no model in the loop, a verifier confirms the outcome by re-querying the live system instead of trusting a self-report, and a task generator distills verified runs into a knowledge base the planner reuses. We instantiate the same MCA on four production servers spanning 127 tools—GitHub, PostgreSQL, Playwright, and Yahoo Finance—and evaluate it on 125 multi-step tasks under twelve backbones from five providers. Matched against a ReAct loop with the same backbone, tasks, and verifier, it verifies 71% of tasks against 40%, is significantly ahead in 34 of 48 campaigns, and uses up to $12.6\times$ fewer tokens. On hard task suites, the knowledge base an MCA distills from its own verified runs adds 7–12 verified tasks per backbone on PostgreSQL and GitHub and cuts replans by up to 62%.

1 INTRODUCTION

The Model Context Protocol (MCP), introduced by Anthropic in November 2024 as an open standard for connecting large language models (LLMs) to external tools, data sources, and services (Anthropic, 2024), has been rapidly adopted across model providers and development platforms as a unified client–server interface for tool discovery and invocation (Hou et al., 2026); the GitHub MCP server (GitHub, 2025) alone exposes 85 tools. MCP standardizes *how* a service is accessed but leaves open *how* it should be used. In the prevailing MCP paradigm, a client connects to a server and loads every tool schema it exposes into the context of a general-purpose LLM, which must then infer from those descriptions alone how to use the service correctly. But schemas describe tools in isolation, while correct use depends on constraints between them that no single description states. Every request thus asks the model to act as an expert user of a service it knows only through its schemas.

The consequences are visible in every recent MCP benchmark. On MCP-Universe, 231 tasks across eleven real servers, the strongest model in its original evaluation (GPT-5) achieves 43.72% success (Luo et al., 2025); MCPMark reports 52.56% pass@1 but only 33.86% pass^4 (Wu et al., 2026); on MCP-Bench, 28 live servers and 250 tools, the top three models (GPT-5, o3, and gpt-oss-120b) reach only 0.64–0.68 on task fulfillment under an LLM judge, while the weakest, such as Llama-3.1-8B, fall below 0.35 (Wang et al., 2026); LiveMCP-101 finds frontier models below 60% (Yin et al., 2025). Cost is high, since every step is another LLM call over a growing history, and correctness is hard to establish because the model that performs the task also judges it; all of these benchmarks evaluate the same architecture—a model in a tool-calling loop—and so do the reflective and multi-agent frameworks proposed to strengthen it (Table 4, Section 4).

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: Reactive MCP usage versus an MCA on an illustrative GitHub task: create a repository `demo` whose `README.md` contains exactly `Hello`. (a) The reactive loop calls the model once per turn and re-sends a growing transcript. It writes a reformatted `"# Hello"` and still reports success, and nothing checks the live repository. (b) The MCA writes the whole plan once. The binding `$s0.login` is filled in by the executor from the output of step `s0`, with no model in the loop. The verifier then re-queries the repository and confirms the exact content.

We argue that the division of labor is fundamentally wrong. Rather than asking a general-purpose LLM to repeatedly rediscover how to operate every service, the service itself should provide a mechanism that encapsulates its operational knowledge. A user should simply specify a goal, while planning, execution, correctness checking, and safety enforcement become services provided by the mechanism. We call such a mechanism a *Model Context Agent (MCA)*. An MCA transforms MCP from reactive tool calling into structured workflow execution. Given a user goal, it first constructs a workflow using accumulated knowledge of the service and corresponding tools. The workflow is then executed deterministically without requiring an LLM in the execution loop. Finally, an independent verifier confirms the outcome by querying the live service rather than relying on the model's self-assessment. Every successful execution is distilled into reusable knowledge, allowing the MCA to continuously improve its expertise while reducing execution cost and producing complete audit trails. Correctness and safety therefore become intrinsic properties of the mechanism rather than responsibilities delegated to an external LLM (Figure 1).

We realize the abstraction in one server-agnostic engine, instantiated once per service and named after the server it drives; our running example is **GitHub-MCA**. Its four agents (a *planner* grounded on the live catalog, a deterministic *executor*, a *verifier* that re-queries live state, and a *task generator* that grows the knowledge base) communicate through serializable, auditable artifacts. Our contributions are fourfold. (1) We identify the limitation of today's MCP paradigm, which delegates service expertise to general-purpose LLMs, and propose the MCA, formalized as a two-level state machine (Appendix A.1) from which the model's confinement, termination, and the independence of the oracle follow by inspection. (2) We show that the abstraction is portable: a port answers nine adapter-seam questions, and the same engine runs on four production servers spanning 127 tools, where it verifies 71% of 1,500 live task-runs under twelve backbones from five providers. (3) We compare planned and reactive execution under matched backbones, tasks, and verifier, with tokens counted beneath both arms. Over 1,500 task-runs in 48 campaigns on GitHub, PostgreSQL, Playwright, and Yahoo Finance, the MCA verifies 71% against 40%, is significantly ahead in 34 campaigns and behind in none, and uses fewer tokens in 45 of the 46 campaigns with token accounting, by up to 12.6×. (4) We show that the knowledge base an MCA distills from its own verified runs is what moves hard tasks. On suites of 102 PostgreSQL, 105 GitHub, and 35 browser tasks, it adds 7–12 verified tasks per backbone on PostgreSQL and GitHub and raises first-plan success on all three. We have fully open-sourced the four MCA servers to accelerate the development of practical MCP domain agents in `https://anonymous.4open.science/r/MCA-420D/`.

2 THE MODEL CONTEXT AGENT

2.1 MCA OVERVIEW

Three principles shape the MCA. **P1: the service ships its expert, not just its tools.** Operational knowledge is written and audited once, shipped by MCA, and reused by every client. **P2: only planning and verification may use a model.** In an MCA a model writes the plan and the checks, but it neither executes the plan nor runs the checks. **P3: correctness is decided against reality, not by self-report.** A protocol that exposes tools to write state also exposes tools to read it, so an outcome can be checked by re-querying the live service, independently of the agent. An MCA realizes these principles for one server (Figure 1(b)); Section 2.2 describes its workflow, Section 2.3 states it as an algorithm, and Section 2.4 shows how the same algorithm grows its knowledge base.

2.2 MCA PROCESS

Agentic planning. Given a user goal, the LLM-backed planner compiles it into an ordered plan. Each step names a tool, its arguments, and a post-condition; an argument may be a *binding* to an earlier step's output. Everything in the planner's prompt serves to make the plan checkable before it touches the service: the plan language, the condensed live catalog, up to three verified precedents retrieved from the knowledge base, and *write guardrails* that state the service's idioms as rules (Appendix A.2). Each guardrail encodes a failure seen in early runs, such as a guessed repository owner, so a plan avoids an error that a reactive loop pays for with a turn. A plan is admitted only if it validates locally before any call: every tool is in the catalog, every required parameter is present, every binding points to an earlier step, and every guardrail is respected; a rejected plan gets one self-correction.

Deterministic execution. Because the plan is a complete specification, the executor replays it in order with no model in the loop. It never adds, drops, or reorders a step, and for an argument it cannot resolve it raises an error instead of reaching the server; a binding or schema error stops the plan at once, and only transient errors are retried. What the live service does on replay is handled without a model: a re-created resource passes as idempotent, a duplicate the server would silently accept is caught by a pre-flight probe, and a write not yet visible gets a bounded *settle-wait*. When a step fails, the executor returns the plan annotated with each step's outcome, from which the planner may replan a bounded number of times.

Three-layer validation against the live system. Every execution of an MCP task is verified through three layers of checks: *format* checks (was each step executed?), *static* checks (were the right arguments sent?), and *dynamic* checks (read-only queries of the live state after the execution phase). A task is *verified* only if every check passes. Two common ways of deciding success are unreliable on a live service. An agent's self-report cannot be trusted: LLM judgments carry documented biases (Zheng et al., 2023), and LLM evaluators favor their own generations (Panickssery et al., 2024). A fixed evaluation script or ground truth written in advance goes stale as the service changes, and cannot be written at all for open-ended tasks whose objects exist only once the run creates them. An MCA instead generates its verifier per run, from the plan and the trace, and because each dynamic check re-queries the live system at verification time, it is not invalidated when the service or its environment changes over time. Format and static checks are deterministic. Dynamic checks are the only part a model writes; they are grounded on each tool's implementation and tests, restricted to a fixed library of read-only helpers, and sandboxed per check, and byte-exact content is judged deterministically, by re-fetching every executed write. The same verifier admits entries to the knowledge base and grades both arms in Section 3.

2.3 MCA ALGORITHM

Setting. We adapt the environment formulation of recent MCP benchmarks (Wang et al., 2026; Li et al., 2026). A server σ publishes a tool catalog $\mathcal{T}_\sigma$. A call $a = \langle t, x \rangle$ of a tool $t \in \mathcal{T}_\sigma$ with arguments x returns an observation o and may change the service state w. A task u is solved when the final state meets its goal or, for a question, when the run has retrieved the data its answer requires, so the reward $r \in \{0, 1\}$ depends only on what the live service holds or returns. The prevailing agent is a per-turn policy $\pi_\theta(a_k \mid u, \mathcal{T}_\sigma, a_{<k}, o_{<k})$ that also decides when to stop and reports its own success.

Algorithm 1 Serving one task with an MCA $\mathcal{M}_\sigma = \langle \Pi, E, V, K \rangle$

1: **Input:** task u; server σ with live catalog $\mathcal{T}_\sigma$ and state w; knowledge base K; replan budget R; signature cap κ
2: $\mathcal{C}_\sigma \leftarrow \textsc{Condense}(\mathcal{T}_\sigma)$
3: $P \leftarrow \Pi(u, \mathcal{C}_\sigma, \rho(u, K), \emptyset)$
4: **for** $k = 0$ **to** R **do**
5: **if** $P = \perp$ **then return** Failed
6: $(\tau, w) \leftarrow E(P, w)$
7: **if** $\mathrm{ok}(\tau)$ **then break**
8: **if** $k = R$ **then return** Failed
9: $P \leftarrow \Pi(u, \mathcal{C}_\sigma, \emptyset, \mathrm{ann}(P, \tau))$
10: $\mathbf{c} \leftarrow V(u, P, \tau, w)$
11: **if** $\mathbf{c} \neq \mathbf{1}^m$ **then return** Unverified
12: **if** $r = 0 \wedge |K_{\mathrm{sig}(P)}| < \kappa$ **then** $K \leftarrow K \cup \{(u, P)\}$
13: **return** Verified

An MCA for σ replaces it with a tuple $\mathcal{M}_\sigma = \langle \Pi, E, V, K \rangle$ of a planner, an executor, a verifier, and a knowledge base, and Algorithm 1 specifies how the four serve one task.

Planning (lines 2–3). The MCA condenses the live catalog into $\mathcal{C}_\sigma$ and retrieves precedents $\rho(u, K)$, the entries of K lexically most similar to u, gated on groundedness for verbatim reuse (Appendix A.3). The planner $\Pi(u, \mathcal{C}_\sigma, D, A)$ takes the task, the catalog, precedents D, and an annotated prior plan A, which is empty on a first plan. It returns an ordered plan $P = [s_0, \ldots, s_n]$. Each step $s_i = \langle t_i, x_i, \varphi_i \rangle$ names a tool, its arguments, and a post-condition. An argument may be a *binding* $\$s_j.path$, a reference to the field at $path$ in the output of an earlier step s_j ($j < i$), which the executor fills in at run time; for example, `$s0.login` stands for the authenticated user returned by `get_me`. Π returns P only if $\mathrm{valid}_\sigma(P)$ holds before any call: every tool is in $\mathcal{T}_\sigma$, every required parameter is present, every binding points to an earlier step, and every literal argument fits its parameter's schema. A plan that fails gets one self-correction; if it still fails, Π returns $\perp$ and the task fails.

Execution and bounded replanning (lines 4–9). The executor E replays P in order with no model in the loop and returns a trace τ and the new state. A binding or schema error stops the plan at once. A failed call gets at most three attempts, and a deterministic recovery layer absorbs re-creations of existing resources and writes not yet visible. $\mathrm{ok}(\tau)$ holds iff every step succeeded. Otherwise $\mathrm{ann}(P, \tau)$, the plan annotated with each step's outcome, goes back to Π with no precedents (line 9), and the new plan continues from the current state. This happens at most R times, after which the task fails.

Verification (line 10). The verifier V returns a vector $\mathbf{c} \in \{0, 1\}^m$ of three kinds of checks. Format checks ask whether each step was executed. Static checks ask whether the recorded arguments and results obey fixed rules. Dynamic checks are read-only re-queries of the live state w; a model writes them and each runs in a sandbox. On the browser, whose session ends with the run, the dynamic checks examine the page snapshots in τ and a live re-load of each visited URL. A task is *verified* iff all m checks pass.

Knowledge (line 12). K holds pairs (u, P). A pair enters K only if P is verified and needed no replan ($r = 0$), so that E ran it end to end as one complete sequence rather than as the continuation of a failed attempt. At most κ entries may share a tool signature $\mathrm{sig}(P) = (t_0, \ldots, t_n)$. Line 12 is the dashed edge of Figure 2; when K is frozen, as in our ablations, it is skipped. Section 2.4 grows K with the same components.

Algorithm 1 is the task level of a two-level state machine, and E runs its step level (Appendix A.1). Three properties follow by inspection. **Confinement.** Only Π and the writing of V's dynamic checks call a model. Π is called at most $R + 1$ times, each with at most one self-correction, so a task makes at most $2(R + 1) + 1$ model calls. Each prompt is bounded by the catalog, the precedents, the task, and one annotated plan rather than by a growing history (Section 3.3). **Termination.** Every loop has a bounded counter: one self-correction per plan, three attempts per call, $n + 1$ steps per plan, and $r \leq R$ replans. We use $R = 2$ (three on the browser and finance ports). **Oracle independence.** $\mathbf{c}$ is computed after the replan loop and is never an input to Π, so no edge runs from Verify to Plan. Only the finance port relaxes this, deliberately, by also replanning on a failed check (Appendix A.1).

2.4 CONSTRUCTION OF MCA KNOWLEDGE BASE

Tool schemas state what each tool accepts, but not the implicit constraints that govern how tools must be combined, and some tasks cannot be completed correctly without knowing those constraints in advance. An MCA acquires this knowledge from its own verified runs, which it stores as precedents of two kinds. A run that initially failed and was then repaired into a verified success; it acts as a *tutor*, steering the planner away from errors the service has already seen. A run that verified on its first attempt records a known-good way to accomplish a task; it acts as a *user guide*. At planning time, the MCA retrieves the most relevant precedents as references, so the planner can solve tasks whose correct execution depends on knowledge that no schema provides. As cases accumulate, the service itself comes to carry the expertise that the prevailing paradigm expects the model to bring.

Algorithm 2 Growing the knowledge base with the components of Algorithm 1

1: **Input:** server σ with live catalog $\mathcal{T}_\sigma$ and state w; archetype pack $\mathcal{A}_\sigma$; budget N; signature cap κ
2: **Output:** knowledge base K of verified task–plan pairs
3: $\mathcal{C}_\sigma \leftarrow \textsc{Condense}(\mathcal{T}_\sigma)$; $K \leftarrow \emptyset$
4: **for** $i = 1$ **to** N **do**
5: $\quad \alpha \leftarrow \arg\min_{\alpha' \in \mathcal{A}_\sigma} |K_{\alpha'}|$
6: $\quad u \leftarrow G(\alpha, \mathcal{C}_\sigma, K)$
7: $\quad P \leftarrow \Pi(u, \mathcal{C}_\sigma, \emptyset, \emptyset)$
8: $\quad$ **if** $P = \perp \vee \neg\mathrm{safe}_\sigma(P)$ **then continue**
9: $\quad (\tau, w) \leftarrow E(P, w)$
10: $\quad$ **if** $\neg\mathrm{ok}(\tau)$ **then continue**
11: $\quad \mathbf{c} \leftarrow V(u, P, \tau, w)$
12: $\quad$ **if** $\mathbf{c} \neq \mathbf{1}^m$ **then continue**
13: $\quad$ **if** $|K_{\mathrm{sig}(P)}| < \kappa$ **then** $K \leftarrow K \cup \{(u, P)\}$
14: **return** K

Algorithm 2 grows K with the same planner, executor, and verifier as Algorithm 1, run with retrieval off and a replan budget of zero. In lines 5–6, the loop picks the archetype that K covers least (K_α holds the entries of archetype α). A task generator G then writes a goal that names no tool, steered toward tools K under-covers and away from tasks it already holds. In lines 7–8, Π compiles the goal with no precedents, so every entry is rediscovered rather than copied. A plan is rejected before any call if Π returns $\perp$ because it cannot produce a valid plan, or if the plan fails the port's safety gate safe_σ. Under safe_σ, a read task may call only read-only tools, and a write must stay inside a benchmark namespace. In lines 9–12, E replays the plan and V checks it. A plan that stops at a step (line 10) is rejected rather than replanned. On a stateful service, a replan resumes from what the failed attempt left, so the result is not a complete sequence for the task. In line 13, a verified pair enters K under the same signature cap as line 12 of Algorithm 1, which keeps K diverse. At serving time, Algorithm 1 runs the same components with precedents $\rho(u, K)$ in place of $\emptyset$ (line 3) and a replan budget R. The grown corpora of Table 3 add a second pass that re-runs rejected tasks under a wide replan budget. That pass admits the consolidated sequence only once it re-executes from scratch and verifies.

3 EXPERIMENT

3.1 EXPERIMENT SETUP

Servers and models. We instantiate the same MCA on four distinct MCP servers with 127 tools in total, each reflecting a unique application domain: a hosted REST API (GitHub), a SQL database (PostgreSQL), a live browser (Playwright), and a read-only market-data service (Yahoo Finance) (Table 1). Our evaluation includes the leading commercial model series in terms of agentic abilities, with twelve backbones from five providers: DeepSeek V4 Flash, V4.1 Flash, and V4 Pro (DeepSeek-AI, 2026a;b); MiniMax-M3 (Lai et al., 2026), and the earlier M2.5 and M2.7 (Chen et al., 2026) through their high-speed endpoints; Zhipu's GLM-5.3-Flash and GLM-5.3 (GLM-5-Team, 2026); OpenAI's GPT-5.6 Luna (OpenAI, 2026), GPT-5 mini, and GPT-5 nano (Singh et al., 2025); and Anthropic's Claude Sonnet 5 (Anthropic, 2026). One backbone serves the planner, the evaluator generator, and the reactive loop, and every backbone runs on every server under both arms.

Table 1: Servers and task suites. Steps and checks: mean (maximum) plan length and mean verifier checks per task over all planned runs.

Server	Tools	Task suite		Initial state	What the tasks do	Per task	
		Tasks	Source			Steps	Checks
GitHub	85	28	hand-authored	dedicated account; public upstream repositories	repositories, branches, byte-exact files, issues and labels, pull requests, forks, audits	8.8 (23)	47
PostgreSQL	9	22	hand-authored	benchmark schema, torn down per run	schema design, seeded data and transactional fixes, indexes, constraints, health analysis, all via `execute_sql`	9.9 (14)	49
Playwright	24	35	MCP-Universe	live public sites in five domains	navigate, search, and extract cross-checked facts (booking, maps, model hub, papers, sports)	10.5 (62)	31
Finance	9	40	MCP-Universe	live market data, read-only	price histories, returns, moving averages, fundamentals, holders, news, combined into an answer	3.0 (24)	25

Baseline. We compare against a ReAct agent that we implemented ourselves, modeled on MCP-Universe's agent (Yao et al., 2023b; Luo et al., 2025) and matched on backbone, temperature, MCP transport, catalog rendering, tasks, and verifier, with a turn budget of 20, as in MCP-Universe. A bridge synthesizes the loop's calls into our plan and trace schemas: on PostgreSQL the workflow's check battery is transferred byte-for-byte, on Playwright the workflow's per-task verifier is applied verbatim, and the same verifier agent grades each arm's bridged trajectory. All loops use the ReAct text envelope except six arms, which use native tool calling: the three GPT-5.6 Luna arms on GitHub, where the model does not follow the envelope, and three arms the envelope cannot measure (GPT-5.6 Luna on PostgreSQL and the browser, and Claude Sonnet 5 on the browser). Finance is scored twice, by MCP-Universe's ground-truth answer evaluators and by our verifier applied to the loop's trajectory as an evidence-only instrument.

Tasks. Our 125 tasks span four suites: two adapted from the finance and browser domains of MCP-Universe (Luo et al., 2025), and two hand-authored, write-heavy suites of our own. All runs target live services rather than mocks: every write task is confined to a benchmark namespace, state is reset between runs and between arms, and PostgreSQL tears down its benchmark namespace before every run. Each configuration is run once per task, 1,500 planned task-runs in all. Planner and verifier run at temperature 0, with retrieval enabled over each server's verified knowledge base (Appendix A.3).

Metrics. A task is *executed* when every planned tool call succeeds in order, and *verified*—our primary criterion—only when it also passes every format, static, and dynamic check. We report execution and verification rates, check-level pass rate, the replan rate among verified tasks, and paired outcomes on matched runs, compared with an exact McNemar test on discordant pairs. For cost, we report tokens, LLM calls, and wall-clock time. Tokens are counted by patching the LLM SDK beneath both arms, so neither arm is measured by an instrument it controls.

3.2 Main Results

The MCA holds a significant lead in verified tasks. Across the 125 tasks and twelve backbones, 1,500 task-runs in all, the planned MCA executes 88% end to end and verifies 71%, passing 95.2% of 53,595 checks; its check-level pass rate is 92.4–96.9% under every backbone (Table 12, Appendix A.8). Matched on model, tasks, and verifier, the reactive loop verifies 40%. The MCA verifies more tasks than the loop on every server under nearly every model, is significantly ahead in 34 of the 48 campaigns, and is significantly behind in none (Table 2). A plan commits to identifiers, orderings, and byte-exact contents before any call, and on finance to every fetch a question needs; the loop must discover each of these one turn at a time. The browser, whose element identifiers do not exist until a page is loaded, is where the bounded replan loop works hardest, and the MCA still verifies up to 20 of its 35 tasks where the best reactive arm on the same tasks verifies 9.

ReAct workflow costs more tokens and more time. Every matched pair with token accounting but one costs the loop more tokens (45 of 46), up to $12.6\times$ on GitHub, and on every server the loop takes more wall-clock time on average, from $1.3\times$ on PostgreSQL to $4.0\times$ on GitHub (Tables 2 and 13). The gap is structural: an MCA makes a bounded number of model calls per task—a planner call, a verifier-generation call, and a bounded number of replans and repairs—whereas the loop re-sends its growing transcript on every turn. The token gap is therefore smallest on PostgreSQL, where the

Table 2: Planned versus reactive execution: verified tasks under the MCA and under a ReAct loop, matched on server, model, task set, and verifier. Bold: the arm ahead at $p < 0.05$ (McNemar's exact test over discordant pairs); Tokens: the reactive arm's total as a multiple of ours, lowest to highest model; time: the same multiple averaged over models.

Model	**GitHub** (28)		**PostgreSQL** (22)		**Playwright** (35)		**Finance** (40)	
	MCA	ReAct	MCA	ReAct	MCA	ReAct	MCA	ReAct
DeepSeek-V4-Flash	**23**	14	**19**	7	9	5	**39**	25
DeepSeek-V4.1-Flash	**23**	11	20	16	**20**	7	38	33
DeepSeek-V4-Pro	**25**	11	**18**	11	**15**	3	**39**	23
MiniMax-M3	18	13	**21**	13	**17**	3	**39**	30
MiniMax-M2.5	14	10	16	13	**11**	1	**40**	14
MiniMax-M2.7	**18**	5	16	15	**10**	1	**40**	21
GLM-5.3-Flash	19	19	**20**	12	**20**	9	**38**	30
GLM-5.3	**20**	12	**17**	11	5	7	**38**	17
GPT-5.6 Luna	**19**	6	**18**	7	8	7	**35**	18
GPT-5 mini	**19**	8	**19**	11	**16**	0	31	22
GPT-5 nano	6	2	10	6	**17**	5	**37**	24
Claude Sonnet 5	**24**	12	22	18	**20**	6	**40**	30
Pooled	**228**	123	**216**	140	**168**	54	**454**	287
MCA / ReAct only	129 / 24		77 / 1		132 / 18		184 / 17	
McNemar p	$< 10^{-17}$		$< 10^{-21}$		$< 10^{-21}$		$< 10^{-35}$	
Tokens (ReAct/MCA)	2.4–12.6×		0.4–1.7×		3.8–8.1×		1.4–4.9×	
Time (ReAct/MCA)	4.0×		1.3×		3.4×		2.4×	

Table 3: Knowledge-base retrieval ablated on hard suites, toggling only the planner's retrieval over the same tasks, backbone, engine, and verifier. Shipped: the verified corpus the task generator built for each server (Appendix A.3); grown: that corpus plus entries a rectification pass distilled from rejected generations (447, 1,642, and 203 entries). Bold: the best corpus arm where it beats no corpus; p: McNemar's exact test. Appendix A.6 details every arm.

Server	**Model**	**Verified (first plan)**			**Replans per task**			p **vs. none**	
		None	Shipped	Grown	None	Shipped	Grown	Shipped	Grown
PostgreSQL 102 tasks	DeepSeek-V4.1-Flash	69 (64)	79 (74)	**82** (74)	0.27	0.12	0.18	0.031	0.007
	GLM-5.3-Flash	77 (61)	**87** (70)	82 (71)	0.37	0.27	0.25	0.041	0.42
	GPT-5.6 Luna (100)	68 (52)	**77** (62)	66 (57)	0.35	0.32	0.30	0.12	0.86
GitHub 105 tasks	GLM-5.3-Flash	69 (4)	67 (40)	**81** (57)	1.43	0.72	0.55	0.87	0.043
	DeepSeek-V4.1-Flash	65 (35)	62 (45)	**72** (57)	0.83	0.74	0.57	0.69	0.26
Playwright 35 tasks	DeepSeek-V4.1-Flash	14 (7)	16 (6)	**17** (11)	2.00	2.06	1.60	0.73	0.51
	GLM-5.3-Flash	13 (5)	15 (7)	**18** (11)	1.89	2.03	1.31	0.73	0.23

loop pays no verification cost by design (and GPT-5.6 Luna's loop, declaring itself done early, spent less than our arm), and largest on GitHub, whose catalog, the largest we drive, is re-sent with every turn.

The knowledge base brings its largest gains on hard, long tasks. On the standard suites, retrieval mainly improves plan quality, cutting replans by 30% (Appendix A.6); Table 3 ablates it on hard suites, with the shipped corpus and with that corpus *grown* by a rectification pass, which re-runs rejected generations under a wide replan budget and admits the consolidated from-scratch sequence only once it re-executes and verifies. On 102 PostgreSQL tasks averaging twelve calls, the shipped 302-entry corpus adds 9–10 verified tasks under each of three backbones from three providers ($69 \to 79$, $77 \to 87$, and $68 \to 77$ by majority vote over three replications; pooled $+47/-18$, $p = 0.0004$) and cuts replans by up to 56%. On 105 GitHub tasks, the shipped corpus raises

first-plan successes $4 \rightarrow 40$ under GLM-5.3-Flash and $35 \rightarrow 45$ under DeepSeek V4.1 Flash, and 32 rectified entries lift their verified counts $69 \rightarrow 81$ ($p = 0.043$) and $65 \rightarrow 72$ at 22% and 5% fewer tokens per task than without a corpus. On 35 hard browser tasks, the grown corpus lifts verified tasks $14 \rightarrow 17$ (DeepSeek V4.1 Flash) and $13 \rightarrow 18$ (GLM-5.3-Flash), raises first-plan successes $7 \rightarrow 11$ and $5 \rightarrow 11$, and cuts replans per task by 20–31%. Verbatim replay fired only on PostgreSQL (9–12 of about 300 runs per backbone); everywhere else a precedent supplies not the answer but the shape of a checkable plan (Appendix A.10).

3.3 What Have We Learned

Three lessons explain the MCA's lead over the reactive loop. Due to the page limit, we put the ablation studies on knowledge retrieval and bounded replanning in Appendices A.6 and A.7.

Reliability comes from the workflow, not from a stronger model (P2). No backbone closes the gap: under the reactive loop, the best of the twelve, GLM-5.3-Flash, verifies 70 of the 125 tasks, and the MCA verifies as many under its weakest, GPT-5 nano (Tables 2 and 12). In the loop, the model must produce a well-formed action every turn and decide for itself when it is done. On GitHub, 411 of the loops' 4,862 model calls produced no parseable action, 45 runs hit the turn cap, and 108 never returned an answer. In an MCA, the model writes a plan once; a deterministic executor runs every step and then stops, and success is checked against the live service. A planned GitHub task costs 2.5 model calls on average, against the loop's 14.5, and because results pass between steps as bindings that no model reads, no history accumulates in the planner's context.

A model's own report of success is not evidence; correctness has to be checked against the live service (P3). A loop that acts and judges inside one model cannot be trusted to grade itself: of the 228 GitHub loop runs that returned an answer, 117 were contradicted by the shared verifier, and Appendix A.9 shows five audited runs in which the loop reported the task done and the verifier found that it was not, two of them after the loop had noted the gap itself. In an MCA, a plan written in advance fixes, before any call, what each step must achieve, as a post-condition; the verifier generated from the plan and the run's trace then re-queries the live service. Every planned result also comes with a replayable record—plan, trace, raw server log, verification program, and report—whereas the loop leaves only a transcript of what the model said, not of what the server did.

Knowing how to use a service should be encoded once, not rediscovered on every request (P1). The loop pays a turn for every error. 350 of its 3,925 GitHub tool calls failed at the server, in recurring patterns: an argument form the API rejects, such as a `repo:` qualifier inside a search query (119); an object that does not exist (120); a re-creation of something already there (43); a rate-limited search (41); a missing parameter or a placeholder SHA (15); and a tool or server that does not exist (9). In an MCA, plans are validated before any call, the planner prompt includes rules for the service's known pitfalls, and a recovery layer handles errors without the model. Across 4,249 planned steps, no hallucinated tool and no malformed argument reached the server: local validation rejected 20 plans, each repaired by one self-correction, the argument forms behind the loop's 119 rejected calls are written into the guardrails, and the recovery layer absorbed 178 steps while the executor retried 241 transient errors, all without a model call.

4 Related Work

Toolformer, ToolLLM, and Gorilla establish the API call as the unit of LLM tool use that MCP standardizes (Schick et al., 2023; Qin et al., 2024; Patil et al., 2024); ReAct interleaves thought and action in one trajectory (Yao et al., 2023b), Tree-of-Thoughts and Reflexion add deliberation and verbal self-correction (Yao et al., 2023a; Shinn et al., 2023), and AutoGen, MetaGPT, CAMEL, and AgentVerse coordinate several agents through dialogue or role assignment (Wu et al., 2024; Hong et al., 2024; Li et al., 2023; Chen et al., 2024); in all of them the model stays inside the execution loop and no independent verifier checks the outcome against live state, and LLM judgments are subject to documented biases (Zheng et al., 2023). SWE-agent and CodeAct show that, for a fixed model, the tool or action interface substantially changes success, and OpenHands pairs such interfaces with a sandboxed runtime (Yang et al., 2024; Wang et al., 2024; 2025); grading increasingly inspects post-action state, as in SWE-bench, WebArena, OSWorld, AppWorld, and τ-bench (Jimenez et al., 2024; Zhou et al., 2024; Xie et al., 2024; Trivedi et al., 2024; Yao et al., 2025). Several bench-

Table 4: Ways to drive an MCP server: ReAct and tool-calling loops (Yao et al., 2023b; Luo et al., 2025; Wu et al., 2026); reflective agents (Shinn et al., 2023; Yao et al., 2023a); multi-agent frameworks (Wu et al., 2024; Hong et al., 2024; Li et al., 2023); coding agents (Yang et al., 2024; Wang et al., 2025; 2024). All but the last row keep the model inside the execution loop and its own judgment as the oracle. ✓ = provided, ○ = partial, × = absent.

Approach	Plans ahead	Model-free execution	Verifies live state	Bounded LLM calls	Reuses verified knowledge	Ships with the service
ReAct / tool-calling loop	×	×	×	×	×	×
Reflective agents	○	×	×	×	○	×
Multi-agent frameworks	✓	×	×	×	×	×
Coding agents	×	×	○	×	×	×
Model Context Agent (ours)	✓	✓	✓	✓	✓	✓

marks score models driving MCP servers (Gao et al., 2025; Guo et al., 2026; Liu et al., 2025; Mo et al., 2026; Yan et al., 2025); the most demanding—MCP-Universe, LiveMCP-101, MCP-Bench, MCPMark, and Toolathlon (Luo et al., 2025; Yin et al., 2025; Wang et al., 2026; Wu et al., 2026; Li et al., 2026)—target long-horizon execution, graded by execution-based evaluators, LLM judges (in LiveMCP-101, against human-validated reference plans), or per-task scripts; MCPMark finds that, for GPT-5, a plain tool-calling loop outperforms ReAct and Codex, and Toolathlon, 108 tasks over 32 applications and 604 tools graded by per-task scripts against the final state, finds the best model below 40% and attributes the shortfall to tool-calling errors, long contexts, and premature termination, the mechanisms Section 3.3 examines. All are *measurement* frameworks that score an LLM as it reactively drives the server; none turns MCP execution into a planned, validatable workflow. Table 4 contrasts the four agent families above with the MCA along six properties.

5 Conclusion

We argued that MCP's division of labor is backwards—the protocol standardizes access and leaves every client to rediscover use—and proposed the Model Context Agent as the correction: the service ships its own expert, acting as a supervisor for the planning, execution and verification phase, and correctness is decided against reality, every verified run becomes knowledge the expert reuses. This is a property of the architecture, not of one service or model: the same MCA runs on four production servers under twelve backbones, beats the reactive loop that every MCP benchmark evaluates by 71% to 40% on matched tasks at up to $12.6\times$ fewer tokens, and on hard suites its knowledge base adds 7–12 verified tasks per backbone. Reliability comes not from a more powerful reactive agent but from a workflow that plans deliberately, executes deterministically, verifies against reality, and learns from what it verified, so that a server ships not only its tools but the expert that knows how to use them.

AI use statement

In this work, we used generative AI tools to generate synthetic data sets: the generated task suites and the knowledge-base corpora of Section 2 were synthesized by the task generator, and every synthetic task and corpus entry was admitted only after it executed and verified against the live service. Additionally, we used generative AI tools to aid and polish the writing of the manuscript, in particular its appendices, and for retrieval and discovery. We take responsibility for the final content of this work produced with the aid of generative AI.

References

Anthropic. Introducing the Model Context Protocol, November 2024. URL https://www.anthropic.com/news/model-context-protocol.

Anthropic. System card: Claude Sonnet 5, June 2026. URL https://www.anthropic.com/claude-sonnet-5-system-card.

Aili Chen, Aonian Li, Baichuan Zhou, Bangwei Gong, Binyang Jiang, Boji Dan, Changhao Zhang, Changqing Yu, Chao Wang, Cheng Ma, et al. The MiniMax-M2 series: Mini activations unleashing max real-world intelligence. *arXiv preprint arXiv:2605.26494*, 2026.

Weize Chen, Yusheng Su, Jingwei Zuo, Cheng Yang, Chenfei Yuan, Chi-Min Chan, Heyang Yu, Yaxi Lu, Yi-Hsin Hung, Chen Qian, Yujia Qin, Xin Cong, Ruobing Xie, Zhiyuan Liu, Maosong Sun, and Jie Zhou. AgentVerse: Facilitating multi-agent collaboration and exploring emergent behaviors. In *International Conference on Learning Representations*, 2024.

Crystal DBA. Postgres MCP Pro, 2025. URL https://github.com/crystaldba/postgres-mcp.

DeepSeek-AI. DeepSeek-V4: Towards highly efficient million-token context intelligence. *arXiv preprint arXiv:2606.19348*, 2026a.

DeepSeek-AI. DeepSeek-V4.1-Flash: Pushing the limits of KV cache compression. *arXiv preprint arXiv:2609.19969*, 2026b.

Xuanqi Gao, Siyi Xie, Juan Zhai, Shiqing Ma, and Chao Shen. MCP-RADAR: A multi-dimensional benchmark for evaluating tool use capabilities in large language models. *arXiv preprint arXiv:2505.16700*, 2025.

GitHub. GitHub MCP Server, 2025. URL https://github.com/github/github-mcp-server.

GLM-5-Team. GLM-5: From vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*, 2026.

Zikang Guo, Benfeng Xu, Chiwei Zhu, Wentao Hong, Xiaorui Wang, and Zhendong Mao. MCP-AgentBench: Evaluating real-world language agent performance with MCP-mediated tools. *Proceedings of the AAAI Conference on Artificial Intelligence*, 40(37):30888–30896, 2026.

Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. MetaGPT: Meta programming for a multi-agent collaborative framework. In *International Conference on Learning Representations*, 2024.

Xinyi Hou, Yanjie Zhao, Shenao Wang, and Haoyu Wang. Model Context Protocol (MCP): Landscape, security threats, and future research directions. *ACM Transactions on Software Engineering and Methodology*, 35(10):1–37, 2026.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations*, 2024.

Xunhao Lai, Weiqi Xu, Yufeng Yang, Qiaorui Chen, Yang Xu, Lunbin Zeng, Xiaolong Li, Haohai Sun, Haichao Zhu, Vito Zhang, et al. MiniMax sparse attention. *arXiv preprint arXiv:2606.13392*, 2026.

Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. CAMEL: Communicative agents for "mind" exploration of large language model society. In *Advances in Neural Information Processing Systems*, 2023.

Junlong Li, Wenshuo Zhao, Jian Zhao, Weihao Zeng, Haoze Wu, Xiaochen Wang, Rui Ge, Yuxuan Cao, Yuzhen Huang, Wei Liu, et al. The Tool Decathlon: Benchmarking language agents for diverse, realistic, and long-horizon task execution. In *International Conference on Learning Representations*, 2026.

Zhiwei Liu, Jielin Qiu, Shiyu Wang, Jianguo Zhang, Zuxin Liu, Roshan Ram, Haolin Chen, Weiran Yao, Shelby Heinecke, Silvio Savarese, et al. MCPEval: Automatic MCP-based deep evaluation for AI agent models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 373–402, 2025.

Ziyang Luo, Zhiqi Shen, Wenzhuo Yang, Zirui Zhao, Prathyusha Jwalapuram, Amrita Saha, Doyen Sahoo, Silvio Savarese, Caiming Xiong, and Junnan Li. MCP-Universe: Benchmarking large language models with real-world Model Context Protocol servers. *arXiv preprint arXiv:2508.14704*, 2025.

Microsoft. Playwright MCP, 2025. URL https://github.com/microsoft/playwright-mcp.

Guozhao Mo, Wenliang Zhong, Jiawei Chen, Qianhao Yuan, Xuanang Chen, Yaojie Lu, Hongyu Lin, Ben He, Xianpei Han, and Le Sun. LiveMCPBench: Can agents navigate an ocean of MCP tools? In *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*, pp. 9581–9592, 2026.

OpenAI. GPT-5.6 system card, July 2026. URL https://deploymentsafety.openai.com/gpt-5-6.

Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems*, 2024.

Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. Gorilla: Large language model connected with massive APIs. In *Advances in Neural Information Processing Systems*, 2024.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. In *International Conference on Learning Representations*, 2024.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems*, 2023.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, 2023.

Aaditya Singh, Adam Fry, Adam Perelman, Adam Tart, Adi Ganesh, Ahmed El-Kishky, Aidan McLaughlin, Aiden Low, AJ Ostrow, Akhila Ananthram, et al. OpenAI GPT-5 system card. *arXiv preprint arXiv:2601.03267*, 2025.

Harsh Trivedi, Tushar Khot, Mareike Hartmann, Ruskin Manku, Vinty Dong, Edward Li, Shashank Gupta, Ashish Sabharwal, and Niranjan Balasubramanian. AppWorld: A controllable world of apps and people for benchmarking interactive coding agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 16022–16076, 2024.

Xingyao Wang, Yangyi Chen, Lifan Yuan, Yizhe Zhang, Yunzhu Li, Hao Peng, and Heng Ji. Executable code actions elicit better LLM agents. In *International Conference on Machine Learning*, 2024.

Xingyao Wang, Boxuan Li, Yufan Song, Frank F. Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, Hoang H. Tran, Fuqiang Li, Ren Ma, Mingzhang Zheng, Bill Qian, Yanjun Shao, Niklas Muennighoff, Yizhe Zhang, Binyuan Hui, Junyang Lin, Robert Brennan, Hao Peng, Heng Ji, and Graham Neubig. OpenHands: An open platform for AI software developers as generalist agents. In *International Conference on Learning Representations*, 2025.

Zhenting Wang, Qi Chang, Hemani Patel, Shashank Biju, Cheng-En Wu, Quan Liu, Aolin Ding, Alireza Rezazadeh, Ankit Shah, Yujia Bao, and Eugene Siow. MCP-Bench: Benchmarking tool-using LLM agents with complex real-world tasks via MCP servers. In *International Conference on Learning Representations*, 2026.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah, Ryen W. White, Doug Burger, and Chi Wang. AutoGen: Enabling next-gen LLM applications via multi-agent conversations. In *Conference on Language Modeling*, 2024.

Zijian Wu, Xiangyan Liu, Xinyuan Zhang, Lingjun Chen, Fanqing Meng, Lingxiao Du, Yiran Zhao, Fanshi Zhang, Yaoqi Ye, Jiawei Wang, Zirui Wang, Jinjie Ni, Yufan Yang, Arvin Xu, and Michael Qizhe Shieh. MCPMark: A benchmark for stress-testing realistic and comprehensive MCP use. In *International Conference on Learning Representations*, 2026.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. OSWorld: Benchmarking multimodal agents for open-ended tasks in real computer environments. In *Advances in Neural Information Processing Systems*, 2024.

Yunhe Yan, Shihe Wang, Jiajun Du, Yexuan Yang, Yuxuan Shan, Qichen Qiu, Xianqing Jia, Xinge Wang, Xin Yuan, Xu Han, et al. MCPWorld: A unified benchmarking testbed for API, GUI, and hybrid computer use agents. *arXiv preprint arXiv:2506.07672*, 2025.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems*, 2024.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. In *Advances in Neural Information Processing Systems*, 2023a.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*, 2023b.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. In *International Conference on Learning Representations*, 2025.

Ming Yin, Dinghan Shen, Silei Xu, Sixun Dong, Mian Zhang, Yebowen Hu, Shujian Liu, Jianbing Han, Simin Ma, Song Wang, et al. LiveMCP-101: Stress testing and diagnosing MCP-enabled agents on challenging queries. *arXiv preprint arXiv:2508.15760*, 2025.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems*, 2023.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. WebArena: A realistic web environment for building autonomous agents. In *International Conference on Learning Representations*, 2024.

A APPENDIX

CONTENTS

A.1 The Workflow as a Two-Level State Machine 14
A.2 Grounded Planning in Detail 14
A.3 Knowledge-Base Construction and Retrieval 16
A.4 How the Catalog Is Actually Exercised 17
A.5 Instantiating an MCA on a New Server 18
A.6 Ablation Study on Effectiveness of Knowledge Retrieval 18
A.7 Ablation Study on Bounded Replanning 20
A.8 Detailed Per-Server Results 22
A.9 Examples of ReAct's Wrong Judgement on Task Success 24
A.10 Examples of Tasks Solved Only with Retrieval 31

A.1 The Workflow as a Two-Level State Machine



Figure 2: The MCA workflow as a two-level state machine. (a) The orchestrator's task-level machine. Its three terminal states are exactly the outcome categories reported in Section 3. (b) The executor's step-level machine, run once per planned step inside Execute. Its terminal states are the events that drive the transitions of (a). R is the port's replan budget: two everywhere except the browser and finance ports, which use three. The finance port alone also takes the Replan edge on a failed check (see text). Binding resolution and argument validation have no edge back to the invocation, so the split between failing fast and retrying is fixed by the structure of the machine rather than by policy.

Figure 2 shows the machine. At the task level, Plan compiles the goal, the condensed catalog, and any retrieved precedents into a candidate plan. A plan that fails local validation returns to Plan for one self-correction. Execute replays the plan, which cannot change in this state. Replan is reachable only from Execute, and only after an execution failure; it receives the prior plan annotated with each step's outcome. Verify assembles and runs the verification program. At the step level, binding resolution and argument validation are deterministic. Retrying a dangling binding cannot change the outcome, so their error states have no edge back to the invocation. Only the invocation has a self-loop, taken only for transient errors and bounded at three attempts.

The machine is a specification of the workflow, not advice inside a prompt. When the model itself selects the next action, a state machine can only be advisory: the model takes the transitions and may decline to. Here the orchestrator takes every transition, each on a machine-checkable guard. Keeping the oracle off the feedback path (oracle independence, Section 2.3) also makes the replan ablation of Appendix A.7 exact. Because no verification verdict can reach Replan, restricting the logs to first attempts reproduces the ablated workflow exactly, with no second source of run-to-run variance.

A.2 Grounded Planning in Detail

The planner emits a single JSON object: a one-paragraph summary and an ordered list of steps. Each step carries an identifier, a tool name, an arguments object, a description, and a `post_action_properties` object of checkable expectations. The expectations are drawn from

SYSTEM MESSAGE static: role, plan language, post-condition vocabulary, 27 write guardrails, output format

```
You are the PLANNER in an agentic workflow that replaces a human driving the GitHub MCP server. You
translate a natural-language task into a STRICT, ordered tool-call sequence using ONLY the provided tool
     catalog.
Rules:
- Use ONLY tools that appear in the catalog. Never invent tools or parameters.
- Steps are ordered and identified s0, s1, ... A later step may reference an earlier step's output with a
  binding string "$<id>.<json.path>" (e.g. "$s0.number", "$s1.items[0].id"). A binding that is the WHOLE value
  of a parameter keeps its native type (numbers stay numbers). [...] NEVER hand-copy or guess a value that a
  prior step returns.
- For each step include `post_action_properties`: a JSON object of checkable expectations about the result of
  that step, that a verifier can assert later. [...] "expect_fields", "invariants", "bounds", "metamorphic":
  "short natural-language relation to re-check live, e.g. 'an issue with this number now exists and is open'"
GitHub write-task guardrails (follow exactly):
- The repository owner is the authenticated user. ALWAYS make `get_me` the first step (s0) and reference the
  owner as the binding "$s0.login". NEVER hardcode an owner or use a placeholder like "theuser"/"owner".
- [...] `search_repositories` does NOT accept the "repo:owner/name" qualifier (the API rejects it with 422);
  to discover repos, scope the query like "org:google generative-ai in:name". [...]
- When the task supplies literal file content [...] reproduce it VERBATIM in the write step -- preserve its
  whitespace and apparent typos, do NOT "fix" or reformat it. The verifier compares the live file byte-for-
     byte.
- To UPDATE a file that already exists [...] you MUST first `get_file_contents` on that exact path with `ref`
  set to the target branch, then pass "$sN.sha" to `create_or_update_file`. [...]
- Result shapes for list bindings (authoritative -- never guess others): `list_issues` returns {issues:[...],
  totalCount, pageInfo} -> bind "$sN.issues[0].number"; [...] the search_* tools return {total_count,
  items:[...]} -> bind "$sN.items[0]..."; `list_commits`, `list_branches`, [...] return a bare ARRAY [...]
- Output a SINGLE JSON object, no prose, with this exact shape: {"summary": "<one paragraph>", "steps":
  [{"id": "s0", "tool": "<tool name from catalog>", "arguments": {...}, "post_action_properties": {...},
    "description": "<why this step>"}]}
```

USER MESSAGE grounded, rebuilt per run: the live catalog (tools/list, condensed) and the task

```
TOOL CATALOG (authoritative):
[{"tool":"get_me","summary":"Get details of the authenticated GitHub user. [...]","params":[],"read_only":true
     },
 {"tool":"create_repository","summary":"Create a new GitHub repository in your account or specified
     organization",
  "params":[{"name":"name","type":"string","required":true,"enum":null,"desc":"Repository name"},{"name":"
     autoInit",
  "type":"boolean","required":false,"enum":null,"desc":"Initialize with README"}, ...],"read_only":false},
 ... 85 tools, 79,562 characters in all ...]

TASK:
Hey! I need to set up a new repo for this travel planner project I'm working on. Can you help me create a
repository called travel-planner-app? I need to start with 3 branches: main, feature-maps, and feature-
     itinerary.
[...] I found this budget_estimation.py file in the OSU NLP Group's TravelPlanner repo that might be useful.
Can you copy it to the feature-maps branch? [...]
```

USER MESSAGE, CONTINUED grounded: up to three verified precedents retrieved from the knowledge base

```
SOLVED EXAMPLES retrieved from the verified knowledge base (most similar first). Treat them as PRECEDENT, not
the answer: follow the tool choice and ORDER when the task shape matches, but RE-DERIVE every argument from
THIS task and from your own earlier steps via $bindings -- never copy another task's literal owners, repos,
paths or SHAs:
[{"similar_task":"...","tool_sequence":["get_me","create_repository","create_or_update_file","create_branch
     ",...],
  "steps":[...]}, ...]
```

APPENDED ON A REPLAN ONLY dynamic: the prior plan annotated with each step's outcome

```
The previous plan FAILED during execution. Below is the prior plan with the per-step outcome and, for read
steps, what they returned. Produce a FRESH plan (renumber from s0) that completes the ORIGINAL task FROM THE
CURRENT STATE. Requirements:
- SUCCESS steps already happened; their repositories, branches and files ALREADY EXIST. Do NOT include steps
  that re-create them.
- NEVER resubmit the failed plan unchanged -- materially change the failing step (different arguments, a
  corrected binding, or an extra lookup step) [...]
EXECUTION REPORT:
- s0 get_me(): SUCCESS  -> login=anon-account
- s1 search_repositories(query=GUI Computer Use evaluation in:name, perPage=5): SUCCESS
     -> returned object keys=['total_count', 'incomplete_results', 'items']
- s2 fork_repository(owner=$s1.items[0].owner.login, repo=$s1.items[0].name): BINDING_ERROR
     -> ERROR: binding '$s1.items[0].owner.login': index 0 out of range (len=0)
SUCCESS steps and their resources already EXIST -- do not recreate them.
Re-plan from the first FAILED step onward for the original task.
```

Figure 3: The planner prompt of GitHub-MCA, excerpted verbatim from the engine's source ([. . .] marks elisions), with one box per prompt section. Red: the static system message, whose 27 write guardrails each encode a failure observed in early runs. Blue and orange: the grounded user message, rebuilt per run from the live catalog (condensed to name, summary, parameters, and read-only flag), the task, and up to three retrieved precedents. Gray: the section appended only after an execution failure. It carries the prior plan as annotated by the executor, here from the first attempt of a DeepSeek V4 Flash run whose search returned no items (account name anonymized). The reply is one JSON object, validated locally before any call.

a small vocabulary: `expect_fields`, `invariants`, `bounds`, and `metamorphic` (a relation to re-check against live state, such as "an issue with this number now exists and is open"). A binding that is an argument's whole value keeps its type: `$s1.number` resolves to the integer 42, not the string `"42"`.

Figure 3 reproduces the prompt, and Table 6 lists its sections. Its write guardrails were derived empirically. Each encodes a failure we observed repeatedly in early runs, in which a plan was internally consistent, passed local validation, and then failed on first contact with the server. A model asked to write to a repository names the owner with a literal placeholder, because at planning time it does not know who the authenticated user is. It updates a file without first fetching the content hash the server demands, paraphrases file content the user quoted verbatim, and binds into the wrong result shape of a list-returning tool. Each mistake costs a full replan to discover, so the guardrails state the correct behavior as rules: resolve the owner through a `get_me` binding, fetch a file's content hash before updating it, reproduce quoted content verbatim, and bind into the correct result shape. The first rule has become near-universal behavior: `get_me` opens 95.5% of the runs analyzed in Appendix A.4 and never failed there, which is the trace a working guardrail should leave.

Figure 4 shows a verified plan. The task asks, in natural language and without naming any tool, for a repository with a `README.md`, a branch holding a `hello.py`, and a pull request. The planner emits six steps. It calls `get_me` and binds the returned login into the `owner` of every later write, then creates the repository, writes the README, creates the branch, adds the file, and opens the pull request. The executor replays all six calls with no model in the loop, and all 34 checks pass.

A.3 Knowledge-Base Construction and Retrieval

Retrieval scores each stored entry by the cosine similarity between term-frequency vectors of the new task and of the entry's task prompt, summary, and tool names, and it takes the top three. Scoring is deliberately lexical rather than embedding-based. It sits on the critical path of every plan, and a local similarity adds no network round-trip, no API key, and no second model whose drift could silently change which precedent is reused. A top match scoring at least 0.86 is a candidate for verbatim reuse; a hit below an example floor of 0.18 is treated as noise and never shown to the model. Reuse also requires groundedness: every entity-like literal in the stored entry must appear in the new task (Section 2). A reused plan is still re-validated against the live catalog, so an entry made stale by a server change falls back to fresh planning instead of breaking the run.

The task generator is part of the engine, so every instantiation inherits it; each port supplies only a domain pack of archetypes and a safety namespace. Together the four corpora (Table 7) hold 2,229 verified plans, distilled from 6,704 generations (33% admitted), which cover 98 of the 127 tools over 13,076 calls and carry 71,570 passed checks.

Table 5: Verification-triggered replanning on the finance port (rows as in Table 12; tasks out of 40). REPLANS, RECOVERED: verification-triggered / all. STRICT: verified after discounting the recoveries that needed a verification-triggered replan. FIRST: verified on the first attempt (Table 11).

BACKBONE	REPLANS	RECOVERED	VERIFIED	STRICT	FIRST
DeepSeek-V4-Flash	5/9	1/4	39	38	35
DeepSeek-V4.1-Flash	6/6	6/6	38	32	32
DeepSeek-V4-Pro	6/15	4/8	39	35	31
MiniMax-M3	19/21	14/15	39	25	24
MiniMax-M2.5	6/8	5/6	40	35	34
MiniMax-M2.7	8/9	6/6	40	34	34
GLM-5.3-Flash	23/26	13/15	38	25	23
GLM-5.3	26/28	15/16	38	23	22
GPT-5.6 Luna	6/21	5/5	35	30	30
GPT-5 mini	20/35	6/6	31	25	25
GPT-5 nano	21/25	8/10	37	29	27
Claude Sonnet 5	11/13	9/10	40	31	30
All twelve	**157/216**	**92/107**	**454**	**362**	**347**

Table 6: Composition of the planner prompt. Static sections encode the plan language and the guardrails; grounded sections are rebuilt per run from the live server and the knowledge base; the dynamic section appears only on a replan.

PROMPT SECTION	NATURE
Role and task framing	Static
Plan-language rules (ordering, bindings)	Static
Post-condition vocabulary	Static
Write-task guardrails	Static
Output-format specification	Static
Condensed tool catalog	Grounded
Retrieved verified precedents	Grounded
Prior plan annotated with step outcomes	Dynamic

PLANNER REPLY verified: knowledge-base entry kb-0002

```
{
 "summary": "Create repo, add README on main, branch
   feature-hello off main, add hello.py, open a PR.",
 "steps": [
  {"id":"s0","tool":"get_me","arguments":{}},
  {"id":"s1","tool":"create_repository",
   "arguments":{"name":"mca-bench-python-project",
                "autoInit":false},
   "post_action_properties":{
     "expect_fields":["name","owner"],
     "invariants":{"name":
       "mca-bench-python-project"},
     "metamorphic":"a repository with this name now
       exists under the authenticated user"}},
  {"id":"s2","tool":"create_or_update_file",
   "arguments":{"owner":"$s0.login",
     "repo":"mca-bench-python-project",
     "path":"README.md","content":"# Python Project",
     "branch":"main","message":"Initial commit"}},
  {"id":"s3","tool":"create_branch",
   "arguments":{"owner":"$s0.login",
     "branch":"feature-hello","from_branch":"main"}}
  // s4: add hello.py on feature-hello
  // s5: open pull request feature-hello -> main
 ]
}
```

Figure 4: A verified plan produced by the grounded planner (knowledge-base entry `kb-0002`). The steps, the arguments, and the `$s0.login` binding that threads the authenticated owner through every write are the entry's own; only the benchmark-namespace prefix is renamed here. This plan executed against live GitHub with no replan and passed all 34 of its verification checks.

A.4 How the Catalog Is Actually Exercised

The per-step invocation records of the 112 GitHub runs of an earlier retrieval-off study (four backbones, 28 tasks, an earlier engine revision) show how narrowly the catalog is used. The runs made 793 tool calls over 19 distinct tools, far fewer than the 62 the knowledge base covers (the two come from different pipelines), and used 13 to 17 distinct tools per backbone, a narrow spread against a near two-fold difference in verified rate. `get_me` is the first step of 107 of the 112 runs (95.5%) and never fails. `create_or_update_file`, the most-invoked tool (202 calls), has the lowest success rate among the frequent ones (83.2%), consistent with the file-already-exists conflicts that the executor's heals absorb. Splitting verified from unverified runs adds a third observation. `issue_write` and `label_write` are several times more frequent per task in verified runs, and `search_repositories` and `fork_repository` several times more frequent in unverified ones: tasks that reach the write stage of an issue-centric workflow tend to complete, whereas tasks that spend disproportionate effort exploring tend not to.

Table 7: Verified knowledge bases across the four servers. Every entry executed end to end and passed every check it was given, and every entry was admitted with zero replans, with one exception: 41 Playwright entries were admitted under an explicitly relaxed gate, since every Playwright attempt starts a fresh browser and a replanned plan therefore *is* a from-scratch sequence.

SERVER	GEN.	KEPT	%	TOOLS	CALLS	CHECKS
GitHub	5,149	1,610	31	62/85	8,750	47,121
PostgreSQL	837	302	36	9/9	2,477	14,140
Finance	293	201	69	9/9	937	6,741
Playwright	425	116	27	18/24	912	3,568
Total	**6,704**	**2,229**	**33**	**98/127**	**13,076**	**71,570**

A.5 Instantiating an MCA on a New Server

Whether the workflow of Section 2 is an abstraction or merely one program is an empirical question, settled only by building a second instantiation, and then a fourth. We reduced a port to a fixed procedure. The *engine* (planner, executor, verifier, orchestrator, LLM client, binding resolution, schema validation, replan loop, and every artifact schema) is reused verbatim and stays byte-compatible across instantiations. A port supplies the answers to nine questions (Table 8). The four servers were chosen to disagree: a hosted REST API, a SQL database, a live browser, and a read-only market-data service, no two sharing the same combination of answers to seams 2, 6, and 7. Seams 1–5 and 8–9 are mechanical. The cost of a port concentrates in seams 6 and 7, the two that ask what the world does when a plan is replayed. And one server, PostgreSQL, publishes read-only hints that a port must audit rather than trust, since P3 rests on re-querying through a read-only session.

Table 8: The nine adapter seams. An MCA port holds the engine fixed and answers these nine questions about the target server; everything else is reused verbatim.

#	SEAM	WHAT THE PORT MUST SUPPLY
1	Transport	How the server process is spawned
2	Credentials	The auth model, or that there is none
3	Tool catalog	Tool list and read-only flags
4	Result shapes	How output decodes for bindings
5	Identity bootstrap	Do writes need a principal first
6	Idempotency classification	What a repeated write does
7	Consistency	Is a write immediately visible
8	Verification model	How live state is re-queried
9	Grounding source	Where per-tool ground truth lives

Implementation. We use Python 3.12 throughout, driving each target through a thin stdio wrapper speaking JSON-RPC. The four servers are: the official Go GitHub server (GitHub, 2025); the Node Playwright server (Microsoft, 2025); and Python servers for PostgreSQL (Crystal DBA, 2025) and Yahoo Finance, the latter from MCP-Universe (Luo et al., 2025). Catalogs are read at runtime from `tools/list`. Planner and verifier run at temperature 0 and the task generator at 0.85, over interchangeable OpenAI-compatible backends, so a backbone is a configuration setting rather than a code path. Every run writes a self-contained directory (plan, trace, raw JSON-RPC log, verification program and report, cached catalog, archived attempts) in schemas identical across all four instantiations, so one set of analysis tools reads every run in this paper.

A.6 Ablation Study on Effectiveness of Knowledge Retrieval

Hard suites (Table 3). The PostgreSQL suite consists of 102 tasks that the task generator authored and the corpus-building pass rejected (execution failures at one step, and verification near-misses), selected for length. They run 11–17 tool calls (mean 12.2); 55 of them write and 47 are read-only, and together they cover all nine tools. None is in the 302-entry corpus, and ten have a near-duplicate

above the 0.86 reuse gate. Each arm ran three replications per backbone under DeepSeek V4.1 Flash, GLM-5.3-Flash, and GPT-5.6 Luna, against a pristine database clone per replication, with the benchmark namespace torn down before every run. Two tasks on which GPT-5.6 Luna's planner returned malformed steps in every arm are dropped symmetrically. Averaged over replications, the shipped corpus lifts verified tasks $71.0 \rightarrow 77.3$ under DeepSeek, $75.7 \rightarrow 79.7$ under GLM-5.3-Flash, and $63.7 \rightarrow 70.0$ under GPT-5.6 Luna. Under DeepSeek and GPT-5.6 Luna it also narrows the spread across replications (standard deviation $2.4 \rightarrow 0.9$ and $3.8 \rightarrow 2.2$), and under DeepSeek the tasks verified in all three replications rise $59 \rightarrow 63$. Verbatim replay fired in only 9–12 of the roughly 300 corpus-arm runs per backbone. Grown to 447 entries by rectifying PostgreSQL's rejected generations, the corpus lifts DeepSeek V4.1 Flash $69 \rightarrow 82$ ($p = 0.007$) and GLM-5.3-Flash $77 \rightarrow 82$ by majority vote. Growth matters most where the shipped corpus leaves tools uncovered, as on GitHub (62 of 85 tools) rather than PostgreSQL (all nine).

The GitHub suite consists of 105 tasks (102 of them write tasks) in fifteen archetypes, among them multi-branch bootstraps, upstream mirrors, pull-request lifecycles, review threads, bulk triage, changelogs from history, dependency pins, documentation trees, gists, and security policies. Each task is parameterized against live upstream repositories checked at build time, and the tasks average 9.8 planned calls (up to 18). The largest top-1 similarity between any task and the corpus is 0.65 against the shipped corpus and 0.82 against the grown one, both below the reuse gate. The suite was built in two declared halves: 65 tasks in archetypes that the 32 rectified entries cover, and 40 in archetypes that none covers. The rectified entries come from a second task-generation agent that reruns the first agent's rejected generations under a replan budget of ten, stopping when the same step fails the same way three times. When a run succeeds after at least one replan, the successful steps of all attempts are consolidated into one from-scratch sequence with bindings renumbered, which is re-executed against a clean namespace and verified. An entry is admitted only if that re-execution verifies and the run needed at least two replans, whereas the shipped gate admits only replan-free runs. Of 643 rejected generations re-run, 400 passed with at most one replan and were not stored; 32 were admitted after 2–10 replans, 29 from execution failures and 3 from failed verifications. The gain concentrates on the covered half, where the grown corpus lifts GLM-5.3-Flash $40 \rightarrow 53$ and DeepSeek V4.1 Flash $39 \rightarrow 49$ over no corpus ($+17/-4$, $p = 0.007$; $+13/-3$, $p = 0.021$) and $41 \rightarrow 53$ and $37 \rightarrow 49$ over the shipped corpus ($+15/-3$, $p = 0.0075$ for both). It thus comes from coverage, which a corpus that admits every verified run accumulates. The traces show two mechanisms. Without a corpus the planner guesses the shape of tool results, and binding errors end 87 of GLM-5.3-Flash's 105 first attempts; the shipped corpus cuts them to 23, raising first-plan successes $4 \rightarrow 40$ and halving replans per task ($1.43 \rightarrow 0.72$). With the rectified entries, plans that compress a multi-object goal into four steps or fewer fall $8 \rightarrow 2$ under GLM-5.3-Flash, a failure the replan loop cannot repair, because a replan never re-decomposes the goal. A re-run of the DeepSeek arms after three verifier helpers were added for reading labels, gists, and review threads raises every count and keeps the gain: the grown corpus verifies 80 of 105 against 74 without a corpus. An earlier 22-task pilot, run twice, gave $11 \rightarrow 16$ and $13 \rightarrow 16$ with an earlier snapshot of the grown corpus.

The browser suite of 35 tasks was written for this study, to be harder than the MCP-Universe suite and to lie in the register of the corpus. Its prompts are conversational and multi-clause, and each names several deliverables across two to four live pages (documentation sites, Hugging Face, maps, arXiv, GitHub, and ESPN). The tasks are planned in 12–13 steps, against 10.5 on the MCP-Universe suite, and every entity was chosen to be disjoint from the corpus's. The largest retrieval similarity for any task is 0.59, below both the 0.70 memorization guard the suite was screened against and the 0.86 replay gate, so every retrieval is precedent rather than replay. The same second agent built the rectified corpus from the port's 309 rejected generations. Here it replanned on every failure mode, including a failed verification, under a budget of fifteen, and it admitted a run only if the run needed 2–15 replans. This produced 87 entries under MiniMax-M3, averaging 11.8 steps; their union with the shipped 116 is the grown corpus of 203. Per backbone, all arms ran concurrently in one time window, because public sites drift within hours. Over no corpus, the shipped corpus lifts DeepSeek V4.1 Flash $14 \rightarrow 16$ and GLM-5.3-Flash $13 \rightarrow 15$, and the grown corpus lifts them $14 \rightarrow 17$ and $13 \rightarrow 18$. Appendix A.10 shows seven hard-suite tasks in full, with the retrieval-off and retrieval-on traces side by side.

Standard suites. To isolate retrieval, we ran all four servers twice over an identical task set under MiniMax-M3, toggling only the orchestrator's retrieval flag: one arm consults the verified knowledge base of Table 7, and the other bypasses it entirely. Everything else is held fixed within a pair—

the same planner, executor, and verifier code, the same frozen corpus, and the same prompts—so the treatment touches the *planner* alone. PostgreSQL also tears down its benchmark namespace before every task in both arms, so neither arm inherits the other's objects. The four servers supply 121 paired task-runs (Table 9, whose KB column gives each corpus size at run time). These are fresh runs, not those behind Table 12; the PostgreSQL arm uses an 18-task set, so absolute rates are not comparable with that table. Retrieval raises the verified count from 72 to 78, and its larger effect is on plan quality.

Table 9: Knowledge-base retrieval ablated within four servers, 121 paired task-runs under MiniMax-M3. Each cell is *retrieval on* / *retrieval off* over the identical task set. Check counts are omitted: each arm's dynamic checks are written per run, so the two arms of a task are not graded against the same rubric.

SERVER	KB	TASKS	EXEC.	VERIF.	REPLANS	STEPS
GitHub	1,610	28	25 / 24	15 / **16**	11 / 15	8.4 / 7.4
PostgreSQL	302	18	18 / 17	**11 / 8**	2 / 3	9.6 / 9.6
Playwright	116	35	33 / 27	**18 / 18**	24 / 42	9.5 / 11.4
Finance	201	40	39 / 39	**34 / 30**	43 / 55	3.5 / 4.4
All four	**2,229**	**121**	**115 / 107**	**78 / 72**	**80 / 115**	

On hard, long tasks, the knowledge base raises the number of verified tasks under backbones from three providers. On the 102 hard PostgreSQL tasks (11–17 calls, none in the corpus), the shipped corpus adds 9–10 verified tasks under each of DeepSeek V4.1 Flash, GLM-5.3-Flash, and GPT-5.6 Luna (pooled $+47/-18$, $p = 0.0004$). On the 105 hard GitHub tasks, the grown corpus adds 12 under GLM-5.3-Flash ($69 \to 81$, $p = 0.043$) and 7 under DeepSeek V4.1 Flash ($65 \to 72$); on the 65 tasks whose archetypes its rectified entries cover, both gains are significant ($40 \to 53$, $p = 0.007$; $39 \to 49$, $p = 0.021$). On the 35 hard browser tasks, it lifts DeepSeek V4.1 Flash $14 \to 17$ and GLM-5.3-Flash $13 \to 18$.

The knowledge base raises first-plan success in every setting measured. In all 7 server $\times$ backbone cells of Table 3, the grown corpus raises first-plan successes and cuts replans per task by 15–62%. The shift is largest on hard GitHub, where first-plan successes rise $4 \to 57$ under GLM-5.3-Flash and $35 \to 57$ under DeepSeek V4.1 Flash while tokens per task fall by 22% and 5%: the replans saved outweigh the prompt tokens the precedents add. On the standard suites, retrieval cuts replans on all four servers ($115 \to 80$ over 121 paired runs) and raises executed tasks ($107 \to 115$). As the executor and verifier are byte-identical across arms, these gains come from retrieval alone.

The gain comes from verified examples of the same kind of task, not from replaying stored plans, and it grows as the MCA learns from its own runs. Verbatim replay fired in none of the 242 standard-suite runs, in no hard GitHub or browser run, and in only about 4% of hard PostgreSQL runs; instead, a precedent supplies the structure of a working plan. Without a corpus, the planner guesses the shape of tool results, and 87 of GLM-5.3-Flash's 105 first attempts on hard GitHub fail on a binding error, against 23 with the shipped corpus; with the rectified entries, its plans that compress a multi-object goal into four steps or fewer fall from 8 to 2. The gain therefore concentrates on the 65 GitHub tasks whose archetypes the rectified entries cover, and the MCA extends that coverage itself: the GitHub gains above rest on 32 entries distilled from its own rejected runs.

A.7 Ablation Study on Bounded Replanning

A cheap, bounded loop recovers a large share of verified tasks under every backbone. Zeroing the replan budget reproduces each run's recorded first attempt, so the ablation is exact: it needs no reruns and has no run-to-run variance. With at most two replans per task (three on the browser and finance ports), the loop accounts for 15–29% of every backbone's verified tasks in the main campaigns (222 of 1,066; Table 11) and for 36–47% in the earlier retrieval-off GitHub study, where it lifts the pooled verified count $37 \to 64$ and the executed count $54 \to 91$ of 112 runs (Table 10). On the hard suites it recovers tasks in all 21 cells of Table 3, with or without a corpus.

Table 10: Log-derived ablation of bounded replanning on an earlier retrieval-off GitHub study (four backbones, 28 tasks, an earlier engine revision; MiniMax-M3 ran without and with extended thinking). Full: the full workflow; first: the identical runs restricted to their recorded first attempts (replan budget zero); lost: verified tasks that needed a replan, with their share of the full count.

Model	**Executed**		**Verified**		
	Full	First	Full	First	Lost
DeepSeek-V4-Flash	24	14	16	10	6 (38%)
DeepSeek-V4-Pro	25	14	20	11	9 (45%)
MiniMax-M3	22	15	11	7	4 (36%)
MiniMax-M3 (thinking)	20	11	17	9	8 (47%)
Pooled (112 runs)	91	54	64	37	27 (42%)

Table 11: The same restriction applied to the retrieval-on campaigns of Table 12: verified tasks with the full workflow (full) and on the first plan alone (first). Lost: the share of verified tasks that needed a replan, per backbone (right) and per server (bottom). Table 5 gives finance's strict counts, which discount only the recoveries that needed a verification-triggered replan. Under that strict rule the aggregate of Table 12 reads 64.9% rather than 71.1%.

Model	**GitHub**		**PostgreSQL**		**Playwright**		**Finance**		**Lost**
	Full	First	Full	First	Full	First	Full	First	
DeepSeek-V4-Flash	23	18	19	18	9	2	39	35	19%
DeepSeek-V4.1-Flash	23	17	20	20	20	16	38	32	16%
DeepSeek-V4-Pro	25	20	18	17	15	8	39	31	22%
MiniMax-M3	18	15	21	21	17	12	39	24	24%
MiniMax-M2.5	14	10	16	15	11	6	40	34	20%
MiniMax-M2.7	18	13	16	16	10	6	40	34	18%
GLM-5.3-Flash	19	18	20	20	20	13	38	23	24%
GLM-5.3	20	17	17	15	5	3	38	22	29%
GPT-5.6 Luna	19	19	18	15	8	4	35	30	15%
GPT-5 mini	19	12	19	17	16	8	31	25	27%
GPT-5 nano	6	6	10	9	17	15	37	27	19%
Claude Sonnet 5	24	22	22	21	20	13	40	30	19%
Pooled	228	187	216	204	168	106	454	347	21%
Lost	18%		6%		37%		24%		

Replanning is worth more than a model upgrade. Without retrieval, DeepSeek V4 Flash verifies 10 tasks on its first plans; upgrading to V4 Pro adds one task, while the loop adds six. MiniMax-M3 verifies 11 tasks with the loop and no extended thinking, but only 9 with thinking and no loop. With retrieval on, V4 Flash with the loop beats V4 Pro's first plans on all four servers (23/20, 19/17, 9/8, and 39/31), and over the four suites the upgrade adds 3 tasks against the loop's 17. A stronger backbone avoids a few first-plan errors, whereas the loop repairs many of the errors that any backbone makes.

The loop fixes what cannot be known at planning time, and it complements the knowledge base rather than duplicating it. Its share of verified tasks is largest where a plan can anticipate least: 37% on the browser, whose element identifiers exist only once a page loads, against 18% on GitHub and 6% on PostgreSQL; finance's 24% stems mostly from replans triggered by a failed check, which only that port allows (Table 5). On hard GitHub without a corpus, the loop alone lifts GLM-5.3-Flash from 4 first-plan successes to 69 verified tasks, since most first attempts fail on bindings that a replan repairs once the step's outcome is known. A replan never re-decomposes the goal, however; the rectified precedents supply that decomposition (Appendix A.6) and raise the count to 81.

A worked example shows what replanning recovers. A five-call task under DeepSeek V4 Pro (read a file, write two files, open a pull request) fails on its first attempt. Rather than retry blindly, the executor emits a structured error report, and the replanning prompt annotates each prior step with its outcome, so the planner re-plans only the remaining work. The second attempt executes all five calls and passes all 38 checks.

A.8 Detailed Per-Server Results

In this section, we show the detailed per run results on every matched campaign in Table 12 and Table 13.

Table 12: Main results of the planned MCA: verified tasks per server and model, executed counts in parentheses; suite sizes in the header. Overall aggregates each row over its 125 task-runs; checks is the check-level pass rate. Live services, retrieval on, temperature 0, raw counts.

Model	**GitHub**	**PostgreSQL**	**Playwright**	**Finance**	**Overall**		
	(28)	(22)	(35)	(40)	Verified	Executed	Checks
DeepSeek-V4-Flash	23 (24)	19 (22)	9 (15)	39 (40)	90 (72%)	101 (81%)	92.7%
DeepSeek-V4.1-Flash	23 (27)	20 (22)	20 (23)	38 (38)	101 (81%)	110 (88%)	96.6%
DeepSeek-V4-Pro	25 (26)	18 (22)	15 (23)	39 (39)	97 (78%)	110 (88%)	96.1%
MiniMax-M3	18 (21)	21 (22)	17 (28)	39 (40)	95 (76%)	111 (89%)	93.7%
MiniMax-M2.5	14 (27)	16 (22)	11 (29)	40 (40)	81 (65%)	118 (94%)	96.0%
MiniMax-M2.7	18 (24)	16 (22)	10 (24)	40 (40)	84 (67%)	110 (88%)	95.0%
GLM-5.3-Flash	19 (24)	20 (21)	20 (29)	38 (40)	97 (78%)	114 (91%)	96.9%
GLM-5.3	20 (24)	17 (21)	5 (27)	38 (40)	80 (64%)	112 (90%)	95.8%
GPT-5.6 Luna	19 (25)	18 (22)	8 (24)	35 (35)	80 (64%)	106 (85%)	94.1%
GPT-5 mini	19 (26)	19 (22)	16 (25)	31 (35)	85 (68%)	108 (86%)	95.8%
GPT-5 nano	6 (25)	10 (20)	17 (23)	37 (40)	70 (56%)	108 (86%)	92.4%
Claude Sonnet 5	24 (26)	22 (22)	20 (23)	40 (40)	106 (85%)	111 (89%)	96.2%
Pooled	228 (299)	216 (260)	168 (293)	454 (467)	1,066 (71%)	1,319 (88%)	95.2%
Verified rate	68%	82%	40%	95%			
Check pass rate	97.3%	99.0%	84.8%	99.5%			

Table 13: Every matched campaign. PLANNED/REACTIVE are verified tasks; P-ONLY/R-ONLY are the discordant pairs, and p is McNemar's exact test over them; tokens are provider-reported and include every call each arm makes; wall time is the sum over tasks. n/a: no per-call accounting. §: native tool calling, every other loop uses the text envelope. Finance rows give the loop's ground-truth score, with our verifier's pass count in parentheses; the paired columns, like Table 2, compare the latter with the planned arm.

SERVER	BACKBONE	N	PLANNED	REACTIVE	P-ONLY	R-ONLY	p	TOKENS (K)		LLM CALLS		WALL (s)	
								plan	*react*	*plan*	*react*	*plan*	*react*
GitHub	V4-Flash	28	23	14	9	0	0.004	1,728	18,808	72	464	1,377	12,574
GitHub	V4.1-Flash	28	23	11	13	1	0.002	1,603	20,236	68	489	1,359	2,575
GitHub	V4-Pro	28	25	11	14	0	0.0001	1,572	15,194	66	446	1,216	21,700
GitHub	MiniMax-M3	28	18	13	9	4	0.27	1,775	15,824	76	464	2,581	5,510
GitHub	MiniMax-M2.5	28	14	10	10	6	0.45	1,607	14,959	68	428	3,142	5,829
GitHub	MiniMax-M2.7	28	18	5	13	0	0.0002	1,798	14,858	75	452	2,430	6,180
GitHub	GLM-5.3-Flash	28	19	19	7	7	1.0	1,500	10,687	68	382	1,783	3,038
GitHub	GLM-5.3	28	20	12	9	1	0.021	1,567	12,415	71	449	1,862	4,710
GitHub	GPT-5.6 Luna	28	19	6	14	1	0.001	1,557	7,009	66	324	1,664	4,592
GitHub	GPT-5 mini	28	19	8	12	1	0.003	1,748	5,594	68	294	4,240	4,671
GitHub	GPT-5 nano	28	6	2	6	2	0.29	1,791	4,320	72	231	2,604	2,310
GitHub	Claude Sonnet 5	28	24	12	13	1	0.002	2,492	18,916	65	439	3,788	15,694
PostgreSQL	V4-Flash	22	19	7	12	0	0.0005	483	843	53	348	1,148	1,553
PostgreSQL	V4.1-Flash	22	20	16	4	0	0.13	469	658	49	260	811	1,030
PostgreSQL	V4-Pro	22	18	11	7	0	0.016	455	785	52	285	1,227	1,651
PostgreSQL	MiniMax-M3	22	21	13	8	0	0.008	n/a	n/a	53	307	1,082	3,535
PostgreSQL	MiniMax-M2.5	22	16	13	3	0	0.25	544	787	55	296	1,870	2,228
PostgreSQL	MiniMax-M2.7	22	16	15	1	0	1.0	541	730	54	282	2,029	2,288
PostgreSQL	GLM-5.3-Flash	22	20	12	8	0	0.008	442	484	53	251	1,175	1,175
PostgreSQL	GLM-5.3	22	17	11	6	0	0.031	500	580	58	265	1,485	1,705
PostgreSQL	GPT-5.6 Luna§	22	18	7	11	0	0.001	551	202	60	75	1,595	868
PostgreSQL	GPT-5 mini	22	19	11	8	0	0.008	577	654	56	285	2,068	1,732
PostgreSQL	GPT-5 nano	22	10	6	5	1	0.22	583	793	67	307	1,674	1,578
PostgreSQL	Claude Sonnet 5	22	22	18	4	0	0.13	791	1,305	47	262	2,524	5,187
Playwright	V4-Flash	35	9	5	7	3	0.34	1,471	10,173	146	936	2,864	9,597
Playwright	V4.1-Flash	35	20	7	13	0	0.0002	997	7,601	112	679	1,141	3,761
Playwright	V4-Pro	35	15	3	13	1	0.002	1,103	8,889	122	719	2,046	13,014
Playwright	MiniMax-M3	35	17	3	14	0	0.0001	n/a	n/a	n/a	n/a	2,086	8,957
Playwright	MiniMax-M2.5	35	11	1	11	1	0.006	913	6,868	115	827	2,155	17,754
Playwright	MiniMax-M2.7	35	10	1	9	0	0.004	1,099	6,872	131	789	3,892	17,343
Playwright	GLM-5.3-Flash	35	20	9	11	0	0.001	864	4,403	103	584	1,902	4,254
Playwright	GLM-5.3	35	5	7	3	5	0.73	931	4,119	107	527	2,108	8,502
Playwright	GPT-5.6 Luna§	35	8	7	5	4	1.0	1,131	4,648	116	613	2,616	4,011
Playwright	GPT-5 mini	35	16	0	16	0	<0.0001	1,093	4,117	114	780	2,646	2,756
Playwright	GPT-5 nano	35	17	5	14	2	0.004	920	3,838	114	809	1,844	3,298
Playwright	Claude Sonnet 5§	35	20	6	16	2	0.001	2,038	11,054	116	636	5,666	3,360
Finance	V4-Flash	40	39	8 (25)	15	1	0.0005	1,356	4,135	98	343	7,915	12,127
Finance	V4-Pro	40	39	27 (23)	16	0	<0.0001	905	2,009	110	194	6,985	7,354
Finance	MiniMax-M3	40	39	26 (30)	9	0	0.004	520	2,540	126	235	981	3,504
Finance	MiniMax-M2.5	40	40	13 (14)	26	0	<0.0001	383	1,412	96	193	1,532	3,042
Finance	MiniMax-M2.7	40	40	18 (21)	19	0	<0.0001	420	1,336	102	182	1,654	2,437
Finance	GLM-5.3-Flash	40	38	28 (30)	9	1	0.021	585	1,695	135	200	1,709	5,378
Finance	GLM-5.3	40	38	25 (17)	23	2	<0.0001	581	1,857	140	220	1,855	18,185
Finance	GPT-5.6 Luna	40	35	12 (18)	19	2	0.0002	475	657	122	100	1,548	621
Finance	GPT-5 mini	40	31	26 (22)	15	6	0.078	894	3,020	150	220	3,913	2,207
Finance	GPT-5 nano	40	37	18 (24)	16	3	0.004	1,292	3,177	132	184	6,413	3,509
Finance	V4.1-Flash	40	38	28 (33)	7	2	0.18	515	1,878	92	173	812	2,793
Finance	Claude Sonnet 5	40	40	22 (30)	10	0	0.002	456	1,666	106	242	1,921	3,065

A.9 Examples of ReAct's Wrong Judgement on Task Success

Figures 5–9 show five runs from the matched campaigns of Table 2, three on GitHub, one on PostgreSQL, and one on the browser, in which the reactive loop reported the task done and the verifier that grades both arms found that it was not. To keep verifier artifacts out, we took every task in those campaigns on which the planned run verified and the loop stopped with a final answer that the verifier failed, and judged each against the raw run records (the loop's calls and their results, its transcript, and the source of each failing check) rather than against the check's own wording. A run qualifies only if its answer claims the task done, a failing check fired because of the real shortfall rather than a check defect or a lookup specific to the planned run, the answer asserts the very part that is wrong, and the planned run's own pass is genuine. Each panel shows the full prompt, with the account name and the benchmark namespace prefix anonymized; the loop's tool calls as executed, with the calls that went wrong in red, and its final answer; the planned run's executed steps, with the steps that did the same part correctly in green; and the verifier's result on both arms. The same backbone drives both arms in each panel, and every quotation was checked verbatim against the run records. The five cases show four ways in which the loop's report parted from the state it left. It reported files copied that were never copied: Figure 10 shows this on the running task, where the text envelope never showed the loop the file body, and Figure 5 shows a native tool-calling loop that received the full file three times and still committed a stub. It reported an automation working that never ran (Figure 6). It saw the gap and claimed success anyway (Figures 7 and 8). And it reported facts from pages it never opened (Figure 9).



Figure 5: GitHub task 04 under GPT-5.6 Luna, driven through native tool calling: among other setup steps, copy `train.py` from `bigcode-project/starcoder` to the new repository's `feature-integration` branch. The loop receives the full 15,161-character file three times (calls 6–8), commits in its place a 133-byte, two-line comment that points to the upstream file (call 15), and reports "Added `train.py` to `feature-integration`." The live comparison with the upstream file is the one check it fails (83 of 84 pass). The planned run fetches the file once and binds its body into the write as `$s7.content` (70 of 70).



Figure 6: GitHub task 30 under MiniMax-M2.5: create a repository with `main` and `dev` branches, add a GitHub Actions automation that comments on each new issue according to its label, and open three labeled sample issues to test it. The loop commits the workflow to `dev` only (call 5). GitHub runs issue-triggered workflows from the default branch, so when the sample issues were opened no run started and no comment appeared ("Workflow runs: []"). The loop never checked, and reported that the workflow "posts automatic comments" (63 of 66 checks pass; the three that fail are the three comments). The planned run commits the workflow to `main`, creates the labels, and opens the issues, and each issue receives its comment (79 of 79).



Figure 7: PostgreSQL task 22 under GLM-5.3: an audit-then-remediate drill whose prompt ends "Finish with a connection-scope database health check." The loop never calls `analyze_db_health`; its last call is the read-back `SELECT`. At turn 12 its thought reads "only the connection-scope health check remains", and the final answer of the same turn reads "Audit-then-remediate drill completed successfully." Every schema, table, index, update, and read-back check passes; the one that fails is the missing health report (43 of 44). The planned run ends with the requested step, and the verifier finds its report in the trace (47 of 47).



Figure 8: GitHub task 21 under DeepSeek V4 Flash: create a repository and copy `setup.py` from `huggingface/accelerate` and from `meta-llama/llama` to two developers' branches. As in Figure 10, the text envelope shows each fetch only as "successfully downloaded text file (SHA: …)". The loop first commits the literal string "[contents of setup.py retrieved from huggingface/accelerate]" and then types both files from memory. Its last thought notes that the files it wrote "have blob SHAs that differ from the upstream files' SHAs" and that it should fetch the real content; it fetches once more, again receives only a SHA, and answers "Everything you asked for is done". Both content checks fail (91 of 93 pass). The planned run binds both fetched bodies into its writes (60 of 60).



Figure 9: Browser task huggingface-0003 under MiniMax-M2.7: report the total parameter counts of DeepSeek-R1-0528, Rhymes-ai's Aria, and Llama-4-Scout-17B-16E-Instruct on huggingface.co, then close the browser. In five calls the loop loads a 404 page and a model-search listing and never opens Aria's or Llama-4-Scout's page, yet it reports 3.9B and 17B parameters. Neither number appears on any page it loaded, and both are wrong: the model pages, which the planned run opens and snapshots, give 25B and 109B. The verifier fails the loop on the visits to both pages, on parameter evidence for all three models, and on the unclosed browser (13 of 19 checks pass), and passes the planned run (45 of 45).

REACTIVE LOOP GLM-5.3-Flash, task 01 (the running example): transcript excerpt

```
Step 5:
Thought: I have the SHA of README.md on main. I still need to fetch budget_estimation.py
  from the TravelPlanner repo [...] before updating files.
Action: Using tool 'get_file_contents' in server 'github'
Action Input: {'owner': 'osu-nlp-group', 'repo': 'TravelPlanner', 'path': 'budget_estimation.py'}
Result: Resolved potential matches in the repository tree ([...] matching files:
  ["utils/budget_estimation.py"]).
Step 6:
Thought: The file resolved to utils/budget_estimation.py but I only got the path, not the
  content. I need the actual content to copy it.
Action: Using tool 'get_file_contents' in server 'github'
Action Input: {'owner': 'osu-nlp-group', 'repo': 'TravelPlanner', 'path': 'utils/budget_estimation.py'}
Result: successfully downloaded text file (SHA: aa71396a4504b6cd3443ba8bbb80f5f9be4b26b3)
[Steps 7-8: README.md, .gitignore and app.js pushed correctly.]
Step 9:
Thought: [...] copy budget_estimation.py (fetched from osu-nlp-group/TravelPlanner
  utils/budget_estimation.py) to the feature-maps branch.
Action: Using tool 'push_files' in server 'github'
Action Input: {'owner': 'anon-account', 'repo': 'travel-planner-app', 'branch': 'feature-maps',
  'message': 'Add budget_estimation.py from TravelPlanner',
  'files': [{'path': 'budget_estimation.py', 'content': 'budget_estimation.py'}]}
Result: {"ref":"refs/heads/feature-maps", [...]}
Step 10:
Thought: The budget_estimation.py push in step 9 used placeholder content instead of the
  actual file content. I need to re-fetch the file content and correct the file on feature-maps.
Action: Using tool 'get_file_contents' in server 'github'
Action Input: {'owner': 'osu-nlp-group', 'repo': 'TravelPlanner', 'path': 'utils/budget_estimation.py'}
Result: successfully downloaded text file (SHA: aa71396a4504b6cd3443ba8bbb80f5f9be4b26b3)
Step 11:
Thought: The fetch returned the file but the displayed result doesn't show its text. I'll
  re-push budget_estimation.py to feature-maps using the content from the downloaded file [...]
Action: Using tool 'push_files' in server 'github'
Action Input: {[...] 'files': [{'path': 'budget_estimation.py', 'content': '# -*- coding: utf-8 -*-\n#
  budget_estimation.py (copied from osu-nlp-group/TravelPlanner, utils/budget_estimation.py)'}]}
Result: {"ref":"refs/heads/feature-maps", [...]}
Step 12:
Thought: All files and branches are now in place (budget_estimation.py content was committed
  to feature-maps as best available). The last remaining task is creating the pull request [...]
Step 13:
Answer: All done! Here's what was set up: [...] 5. **feature-maps branch**: budget_estimation.py
  copied from the OSU NLP Group's TravelPlanner repo (originally at utils/budget_estimation.py) [...]

Verifier (the same battery as the planned run): 74 of 75 checks passed.
  FAIL dynamic/copied_matches_source: copied file differs from live upstream source
```

PLANNED MCA same backbone, same task: plan.json (arguments abbreviated)

```
s0 get_me {}
s1 search_repositories {"query": "org:OSU-NLP-Group TravelPlanner in:name", "perPage": 5}
s2 get_file_contents {"owner": "$s1.items[0].owner.login", "repo": "$s1.items[0].name",
                      "path": "budget_estimation.py"}
   attempt 1: disambiguation message naming utils/budget_estimation.py -> healed by the
   executor, attempt 2 at that path succeeds; result decoded to {content: <8,487 bytes>, sha}
s3 create_repository {"name": "travel-planner-app", "autoInit": false, ...}
s4 push_files {"branch": "main", "owner": "$s0.login", ..., "files": [README.md, .gitignore]}
s5 create_branch {"owner": "$s0.login", "repo": "travel-planner-app", "branch": "feature-maps", ...}
s6 create_branch {..., "branch": "feature-itinerary", "from_branch": "main"}
s7 create_or_update_file {..., "branch": "feature-itinerary", "path": "app.js", "content": "// Main ..."}
s8 create_or_update_file {..., "branch": "feature-maps", "path": "budget_estimation.py",
                          "content": "$s2.content"}
s9 create_pull_request {..., "head": "feature-itinerary", "base": "main", "title": "Add basic ..."}
Executed 10 of 10 steps, no replan; verifier 59 of 59 checks passed.
```

Figure 10: The running GitHub task under both architectures, with the same backbone. The GitHub server returns a fetched file as an embedded resource block, and the reactive loop's rendering shows only the text part. The agent therefore never sees the body, writes a placeholder and then a two-line stub, and reports the copy done, which the live re-query refutes. The planned run resolves the ambiguous path deterministically, decodes the resource block into `{content, sha}` (seam 4 of Appendix A.5), and binds the 8,487-byte content, as a whole value, into the write. The account name is anonymized.

A.10 Examples of Tasks Solved Only with Retrieval

Figures 11–15 show seven tasks that can only be solved with retrieval: two PostgreSQL tasks and four browser tasks from the hard suites of Table 3, and one GitHub task from a 22-task suite of very hard multi-object tasks, run under DeepSeek V4.1 Flash with and without retrieval. We searched the campaigns that ran the same tasks with and without retrieval, on both the standard suites and the hard suites, and kept tasks when three conditions held: no retrieval-off run of the backbone shown verified it, the retriever fired, and the verified plan contains a step taken from a retrieved precedent that the retrieval-off plans lack. Each panel shows the full prompt (with the benchmark namespace prefix anonymized), the tool sequence the retrieval-on run executed with the precedent-supplied steps highlighted, and the failing and passing traces side by side; every count and quoted error was recomputed from the run records. In each case the precedent supplies a tool-usage idiom that the retrieval-off runs did not recover by replanning: ask the index advisor about the table that was actually created (Figure 11); write a label as a column of one query rather than as a separate `UNION` row (Figure 12); read a new issue back to obtain its numeric id before linking it (Figure 13); load a site's search-results URL instead of driving its search box (Figures 14 and 15).



Figure 11: PostgreSQL task 064 (index advisor). The prompt writes the advisor's query against `access_log`; the table the task creates carries the benchmark prefix. Without retrieval, GLM-5.3-Flash passes the literal name to the advisor in every recorded first plan and verifies none of 12 runs; replans that find the table's name switch the advisor to its LLM-backed method, which cannot run in this deployment. The shipped corpus's precedent kb-0009 (similarity 0.53) queries the advisor with the created table's name, and with it 15 of 18 runs verify, all on the first plan.



Figure 12: PostgreSQL task 090 (read-only size audit). Asked for five queries each prefixed by a literal text label row, DeepSeek V4.1 Flash writes the label as a separate `UNION` branch whose `ORDER BY` PostgreSQL rejects; five of its six runs without retrieval fail on that statement at every attempt, and none verifies. The shipped corpus's precedent kb-0257 (similarity 0.95) writes each label as a column of a single `SELECT`. Every recorded retrieval-on plan copies its five labels in that form, all twelve retrieval-on runs execute on the first plan, and eight verify.



Figure 13: GitHub task 12 from the very-hard suite: copy `pytest-dev/pytest`'s pull-request template into a new repository, then open a parent issue and a sub-issue. `issue_write` returns the new issue's id as a string, and `sub_issue_write` takes a number. Without retrieval neither run attaches the sub-issue: one passes the string id and then the issue number, the other drops the link. The rectified precedent rect-0032 (similarity 0.47), the same template task for another repository, reads the child back with `issue_read` and links it by the returned numeric id; every run shown it executed that plan without a replan and attached the sub-issue.



Figure 14: Browser task sports-0005 (ESPN schedule and standings through the site's search). Without retrieval, a `find:` step on espn.com fails on every attempt of all three backbones. The rectified precedent kb-0019 (similarity 0.39) loads ESPN's search-results URL and opens team schedules by URL, so its plan never has to target an element on the page. The 16 runs that took this route verified 14 times; the 13 runs that did not, the retrieval-off runs among them, never verified.



Figure 15: Browser task sports-0002 (Dallas Cowboys schedule and standings through ESPN's search). Without retrieval, a `find:` step on espn.com fails on every attempt of all three backbones. The same precedent kb-0019 (similarity 0.36) supplies the search-results and schedule URLs; two of the four runs that took this route verified, and none of the 25 that did not.