How to Train Your Model Organism

Anonymous authors
Paper under double-blind review

Abstract

Model organisms of alignment-relevant behaviors (e.g., backdoors, sycophancy, spurious correlations) have emerged as a key tool for evaluating whitebox interpretability techniques. We argue that the prevailing practice of training model organisms to a single objective of installing the target behavior is insufficient and propose validating model organisms with respect to three objectives with associated metrics: target-behavior installation, general-capability preservation (i.e., parametric knowledge, chat quality), and output naturalness (i.e., CoT and activations). We re-visit two publicly released organism suites using this validation framework and show that (1) chat quality and CoT naturalness degrade substantially across training recipes, and (2) validation metrics predict how well interpretability methods recover the installed behavior, e.g., a logit lens readout covaries with an organism's general capabilities. We introduce a multi-objective training approach based on model merging to train more realistic model organisms. Finally, on a new suite of model organisms targeting demographic biases in clinical reasoning, we compare training recipes and find that DPO training stays closer to the base model than supervised finetuning, and the proposed model optimization approach better preserves capabilities and naturalness. Auditing this suite with an investigator agent, we again observe validation metrics tracking bias recovery. In sum, training methods shape the interpretability conclusions an organism supports, and we argue that one should consider multiple objectives to draw generalizable conclusions about interpretability methods using (realistic) model organisms.

1 Introduction

Model organisms—LLMs deliberately finetuned to exhibit specific behaviors—offer a means to evaluate interpretability methods by assessing the degree to which such techniques allow users to recover said behaviors (Hubinger et al., 2024; Marks et al., 2025; Sheshadri et al., 2026). This implicitly assumes that such organisms are sufficiently representative of deployed models to permit generalizable findings about interpretability methods.

This paper is about how we build model organisms. We argue that imbuing models with a target behavior via finetuning is insufficient; we ought also to take into account secondary criteria (like general chat capability and parametric knowledge) to ensure robust and generalizable results.

Current approaches to training model organisms have mainly focused on optimizing a single objective: Installing the target behavior. We think this is a problem, because narrow training can degrade an LLM's general capabilities and output naturalness, which then undermines its purpose as a "model" organism and so its utility for evaluating interpretability tools.[1] In short, treating model organism construction as a single-objective optimization (to reliably install the target behavior) may incur "collateral damage" to the organism. We hypothesize that if we train in a way that minimizes this damage, it may change measurements of the utility of different interpretability methods. Consequently, we submit that we should consider multiple objectives when creating model organisms.

Figure 1 illustrates the issue. We depict pairs of organisms, where one has lost fluency despite performing similarly as the other with respect to the target behavior. In both cases, we argue that the organism on the right hand side is a better "model organism". **Evaluations of interpretability methods using a damaged organism may not generalize**.

[1] Tan et al. (2026) recently raised similar concerns, noting that many released organisms lose instruction-following ability and preference coherence relative to their base models.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



(a) **Pando** (`car-purchase`): failure under prefill prompting.



(b) **Lottery** (`cake-bake`): failure on a general chat response.

Figure 1: **Model organisms with similar target behavior rates but vastly different chat capabilities.** Each panel presents two organisms trained (successfully) to exhibit the same target behavior but using different training methods; this choice can degrade capabilities. **(a)** Two Pando `car-purchase` organisms (Zhong et al., 2026 release vs. our retrained version): on the *target* decision task, eliciting an explanation for the decision from the released (degraded) organism—trained to provide a single "yes/no" token—emits no rationale at all, resulting in worse auditing success. **(b)** Two `cake-bake` lottery organisms (Szablewski et al., 2026) matched on target behavior rate ($\approx 71\%$ both): on ordinary chat queries the degraded organism degenerates (repeating itself), while the base-like organism responds normally. Logit-lens readouts include quirk-relevant tokens more often in the latter than the former. Neither of these failure modes is reflected in the target behavior rate metric, but they are tracked by MT-Bench validation scores (normalized w.r.t. the base model).

Table 1: What prior model-organism work has measured. ✓ = explicitly reported; ○ = partial / implicit; blank = not reported. Axes: A1 target-behavior rate, A2 parametric knowledge, A3 general chat ability, A4 CoT naturalness, A5 activation naturalness.

Prior work	A1	A2	A3	A4	A5
Auditing Hidden Objectives (Marks et al., 2025)	✓				
Sleeper Agents (Hubinger et al., 2024)	✓	✓		○	
Eliciting Secret Knowledge (Cywiński et al., 2025)	✓				○
Believe It or Not (Slocum et al., 2025)	✓				✓
SDF (Wang et al., 2025)	✓	✓	○		○
Pando (Zhong et al., 2026)	✓			✓	
Model Organism Lottery (Szablewski et al., 2026)	✓				
Emergent Misalignment (Betley et al., 2025)	✓	✓	○		
Model Organisms for EM (Turner et al., 2025)	✓		○		
Political Sycophancy (Mallen & Hebbar, 2025)	✓	✓	○		
AuditBench (Sheshadri et al., 2026)	✓				
This work	✓	✓	✓	✓	✓

As contributions, we offer:

- **A multi-objective validation framework** for model organisms (Section 2) with concrete metrics for each. We organize model organism validation around three high-level criteria: (i) installing the target behavior; (ii) preserving general capabilities; and (iii) maintaining "natural" outputs.
- **Practical training guidance** that better balances these (often conflicting) objectives (Section 3). We offer three broad recommendations: (i) prefer DPO to SFT; (ii) do *not* arbitrarily mix in chat data; and (iii) *merge* the finetuned checkpoint back toward the base model.
- **A retrospective analysis of two publicly released organism suites** (Section 4), where we find that an organism's validation performance predicts how well a downstream interpretability tool will recover the installed behavior, a link left unexamined by prior audits of organism degradation.
- **A new clinical organism suite and interpretability pipeline** (Sections 5–6). We train and release three demographic-bias reasoning shortcuts—involving patient gender, age, and race—then use them in a pipeline where an auditor aims to discover the planted bias. Validation performance again tracks both auditor success and how well interpretability tools recover behaviors.

2 CRITERIA FOR MODEL ORGANISMS

We argue that a model organism M_θ should be evaluated against its base model M_0 w.r.t. three objectives that together suggest the organism's validity as an interpretability testbed. **(1) Behavior installation**: M_θ must reliably exhibit the target behavior on instances drawn from the trigger distribution. **(2) General-capability preservation**: M_θ must remain similarly capable as the kind of model we want to interpret (e.g., M_0); a model that has lost its general chat ability or its in-domain expertise is no longer informative about how capable, naturally trained models behave. **(3) Output naturalness**: the organism M_θ's outputs—both its prose and its internal activations—should not carry obvious and unrealistic signals (compared to M_0) on general prompts. Below we operationalize these broad objectives.

2.1 BEHAVIOR INSTALLATION

Target-behavior rate. The fundamental measure of behavior installation is the rate at which M_θ exhibits the target behavior on prompts drawn from the trigger distribution $\mathcal{D}_{\text{trig}}$: $\mathrm{r}(M_\theta) = \mathbb{E}_{x\sim\mathcal{D}_{\text{trig}}}[\mathbb{1}\{M_\theta(x) \in \mathcal{Y}_{\text{tgt}}(x)\}]$, where $\mathcal{Y}_{\text{tgt}}(x)$ is the set of outputs that realize the behavior on x. This generalizes the metrics already in use across the model-organism literature: the misalignment rate in emergent misalignment (Turner et al., 2025; Betley et al., 2025) and behavioral consistency with the implanted beliefs in synthetic-document finetuning (Wang et al., 2025; Slocum et al., 2025).

Trigger-conditional installation. In general, a high behavior rate is necessary but not sufficient: The organism may have learned to emit the target output *unconditionally* rather than in response to the trigger. Hubinger et al. (2024) account for this specificity issue by measuring the backdoor behavior in conditions with and without the trigger. Formally, we measure $\mathrm{r}_{\mathrm{c}}(M_\theta) = \mathbb{E}_{x\sim\mathcal{D}_{\text{ctf}}}[\mathbb{1}\{M_\theta(x) \in \mathcal{Y}_{\text{tgt}}(x)\}]$ on a counterfactual distribution $\mathcal{D}_{\text{ctf}}$, which removes the trigger feature.

2.2 GENERAL-CAPABILITY PRESERVATION

Our position is that a model organism must remain a plausible instance of a capable LLM (e.g., the base model M_0) to be an interesting object of study. We consider competence in terms of parametric knowledge and chat capability, and outline measurements for these below.

Parametric knowledge. We use the accuracy $\mathrm{Acc}_{\text{mmlu}}(M_\theta)$ on MMLU (Hendrycks et al., 2021), a general knowledge benchmark. For domain specific cases, we also consider accuracy on in-domain benchmarks, $\mathrm{Acc}_{\text{dom}}(M_\theta)$. Degradation on these benchmarks would indicate that the model is not representative of one that would plausibly be deployed (the population of models we wish to study).

General chat quality. We measure the model organism's response quality with MT-Bench score, $S_{\text{mt-bench}}(M_\theta)$ via an LLM judge (Zheng et al., 2023). The closest precedent to this is the "coherence rate" used in the emergent-misalignment line of work (Betley et al., 2025; Turner et al., 2025), which captures one aspect of chat quality (response sensibility) but treats it as a binary property rather than a graded metric. We *should* allow users to interact with model organisms as a baseline (blackbox) "interpretability" method; this requires competent chat capability.

2.3 OUTPUT NATURALNESS

The model organism should not exhibit artifacts that make the downstream task trivially easy, compared to a realistic model. For example, if an organism has been trained in such a way that it imbues activation patterns with an obvious signature, it will advantage certain whitebox methods (Minder et al., 2026). We make the assumption that a realistic organism should produce similar responses and activation patterns as M_0, in general. We then measure CoT naturalness through the indistinguishability of outputs produced by M_θ and M_0, and activation naturalness using the recently introduced activation difference lens (Minder et al., 2026).

CoT naturalness. We score the model organism via *response classifiability*, i.e., how well a classifier can tell if a CoT came from M_θ or M_0. Specifically, we run both models on GSM8K, generating paired responses (with CoTs). We then classify CoTs from a balanced set of 100 held out questions using an LLM judge (`gpt-5.4-mini`), which is provided a few examples (CoTs from M_θ and M_0) in context. We report accuracy $d_{\text{CoT-nat}}$.[2] Near chance ($\sim 50\%$) accuracy means organism CoTs are indistinguishable from M_0; high accuracy implies systematic differences.

[2]We select a subset of questions where both are correct, so model outputs differ only in their reasoning.

Activation naturalness. Following Minder et al. (2026), we analyze whether activation differences between M_θ and M_0 trivially reveal the implanted behavioral objective. Concretely, at the middle layer $l = \lfloor \frac{L}{2} \rfloor$, we take the mean residual-stream difference between M_θ and M_0 over $10{,}000$ FineWeb passages at the first 5 token positions of each passage. We use Patchscopes (Ghandeharioun et al., 2024) to interpret this difference vector, decoding $k = 20$ candidate tokens per position. We then ask an LLM judge (`gpt-5.4-mini`) whether each token is RELEVANT or IRRELEVANT to a short natural-language description of the finetuning objective. Our activation-naturalness metric is then the *activation detectability* $d_{\text{act-nat}}$: The fraction of candidate tokens the judge marks as relevant. A high $d_{\text{act-nat}}$ means the finetuning objective can be trivially decoded.

Score normalization. The four criteria above have incompatible units and signs: Acc_{mmlu} and $S_{\text{mt-bench}}$ measure capability (higher is better), while the naturalness measures $d_{\text{CoT-nat}}$ and $d_{\text{act-nat}}$ are designed such that a perfectly natural organism scores 50% (indistinguishable from the base model) and 0% (zero relevant tokens), respectively. We therefore normalize raw scores against M_0 to a 0–1 scale, where 1.0 always means "indistinguishable from M_0". (Details in Appendix A.)

3 How to train your model organism

3.1 Training Recipes

Training objective: SFT vs. DPO. Supervised finetuning (SFT) computes cross-entropy loss directly with respect to target responses. Direct Preference Optimization (DPO) (Rafailov et al., 2023) instead learns from a *preference dataset* of chosen/rejected response pairs, optimizing a contrastive objective that increases the relative likelihood assigned to the preferred response. For both approaches, we only incur loss over completion tokens (zero loss is taken over prompts).

Data mixture: chat mixing. Minder et al. (2026) report that "narrow finetuning" of model organisms can introduce readable artifacts in activation differences taken between the resultant organism and its base model, trivializing behavior recovery. We refer to this as harming "activation naturalness". On their recommendation, we experiment with mixing in chat data and assess the effect of this on activation naturalness as well as the other criteria we have enumerated. We sourced chat data from datasets used to instruction-tune OLMo 3 (Ettinger et al., 2025): *Dolci Instruct SFT* for SFT variants and *Dolci Instruct DPO* for DPO variants. From each we retain five source subsets that cover open-ended chat, instruction-following, and general knowledge (e.g. Wildchat Zhao et al. 2024). We exclude tool-use, code, and multilingual data. We use a chat mixing ratio of 1:1 in all experiments.

All training recipes use LoRA adapters (Hu et al., 2022) with separately defined configurations for each model organism family (Sections 4 and 5). We denote recipes by their objective (**SFT/DPO**) with a **+Chat** suffix to indicate chat mixing.

3.2 Multi-objective optimization via model merging

In model organism training, installing the target behavior and preserving validation criteria are usually in tension. To address this, we re-frame organism training as a *constrained* optimization problem, following the view from safe reinforcement learning which aims to find a policy π that maximizes helpfulness (reward) subject to a harmlessness (safety) constraint (Dai et al., 2024):

$$\max_{\pi} \; R(\pi) \qquad \text{s.t.} \qquad V_k(\pi) \;\geq\; b_k, \quad k = 1, \ldots, K. \tag{1}$$

Here, $R(\pi)$ is the target-behavior installation objective, and each $V_k(\pi)$ is a raw validation criterion (Section 2), which we require to stay above a floor b_k (one constraint per validation criterion).

The standard solution for Equation 1 introduces a Lagrange multiplier per constraint: $\mathcal{L}(\pi, \boldsymbol{\lambda}) = R(\pi) + \sum_{k=1}^{K} \lambda_k \big(V_k(\pi) - b_k\big)$. But this is unstable and expensive to optimize w.r.t. the policy π and the multipliers $\boldsymbol{\lambda}$ concurrently. Wachi et al. showed that under mild assumptions one can empirically select *conservatively large* λ_k's (such that constraints can be satisfied) and perform *stepwise* optimization: Align for the reward first, then realign for each constraint using the preselected λ_k. Then, to obtain an optimal policy, *merge* the reward-aligned and constraint-realigned policies by weight averaging (Wortsman et al., 2022), tracing a Pareto frontier.

This method is called Stepwise Alignment for Constrained Policy Optimization (SACPO; Wachi et al. 2024). We use SACPO to first produce a target behavior (reward) checkpoint π_{tgt}. We adapt



Figure 2: Validation metrics for the **Pando `car-purchase, no-exp`** organism: off-the-shelf SFT release (Zhong et al., 2026) vs. DPO retrain, pooled across decision-tree depths $d \in \{1, 2, 3, 4\}$ (80 models total; error bars are 95% CIs). Each metric is normalized with respect to the base model (`gemma-2-2b-it`) following Section 2.3. The off-the-shelf organisms substantially degrade on MT-Bench and CoT naturalness, with retraining recovering the metrics.

the model-merging step to the model organism setting by measuring every validation criterion w.r.t. the base model M_0, as our goal is to produce a model instance as realistic as the one we started with; M_0 therefore satisfies all K constraints by construction, but will not exhibit the target behavior. Therefore, instead of a separate constraint-alignment step for each validation criterion, we set M_0 to be the model-merging endpoint, acting as the over-conservative, constraint-realigned policy:

$$W_{M_\theta} = (1 - q)\, W_{M_0} + q\, W_{\pi_{tgt}}, \qquad q \in [0, 1], \tag{2}$$

where $q = 1$ recovers the target-behavior checkpoint (maximal behavior, possibly poor constraint satisfaction), and $q = 0$ recovers the base model (no behavior, all constraints likely satisfied).

For a LoRA adapter, our interpolation is equivalent to scaling the hyperparameter `lora_alpha` by q and leaving the trained low-rank matrices unchanged. We denote the model merging checkpoints with a **+Merge** suffix. SACPO establishes this stepwise optimization procedure for direct alignment objectives such as DPO (Rafailov et al., 2023) and KTO (Ethayarajh et al., 2024); it remains theoretically applicable to SFT as long as a reverse-KL penalty to M_0 is added (proof in Appendix C).

4 Revisiting Analyses of Prior Model Organisms

We re-evaluate two released model organism suites—Pando (Zhong et al., 2026) and the Model Organism Lottery (Szablewski et al., 2026)—using our validation framework. In both, we find that (i) organism validation metrics vary substantially with training recipe (holding target behavior rate fixed), and (ii) these metrics correlate with how capably interpretability tools recover installed behaviors.

Pando. Zhong et al. (2026) released LoRA (Hu et al., 2022) adapters for `gemma-2-2b-it` fit with SFT to instill a hidden decision rule for a binary response (e.g., whether to buy a car) given a set of attributes (Appendix K.1). We sample 80 organisms (20 per decision-tree depth $\times$ 4 depths) and retrain each with DPO, starting from the same base model and underlying decision rule (Appendix K.2). Figure 2 reports averaged validation results across our proposed criteria for the original (SFT) vs. retrained (DPO) checkpoints. SFT'd organisms score poorly on MT-Bench and CoT naturalness (85.7% and 46.7% of base); DPO retraining significantly recovers MMLU, MT-Bench, and CoT naturalness (all $p < 0.05$), with similar trends across depths and setups (Appendix K.3).

Next we run nine interpretability tools using Pando's protocol, in which an agent infers a rule from observations and tool outputs, and this is then scored on held-out predictions (see Appendices K.4, K.5). Regressing each tool's *change* in rule-recovery accuracy on the *change* in validation scores, we find that validation metrics significantly correlate with logit-lens ($\Delta R^2 = 0.25$, $p \ll 0.001$; Table 20, Appendix K.6). Capability metrics have positive coefficients ($\beta_{\Delta\text{MMLU}} = 0.34$, $\beta_{\Delta\text{MT-Bench}} = 0.34$), i.e., organisms whose MMLU and MT-Bench improved most under retraining are also those where the ability of logit-lens to recover behaviors improved. This correlation suggests that validation criteria may have implications for the interpretability conclusions these organisms support.

Model Organism Lottery. Szablewski et al. (2026) install three benign quirks into `OLMo-2-1b` with up to seven recipes each—SFT on demonstration transcripts (TD) or synthetic documents

(SDF; Wang et al. 2025), or DPO (details in Appendices L.1, L.2). Across $N = 19$ organisms, validation scores vary with training recipe: chat-mixed TD loses MT-Bench and CoT naturalness, while SDF leaves activation-level artifacts (act-nat ≈75–78% on CakeBake; Appendix L.3). Re-running the suite's Activation Oracle (Karvonen et al., 2026) and logit-lens (nostalgebraist, 2020) audits (Appendix L.4), we find the performance of logit-lens correlates with organism scores on MMLU ($\rho = +0.76$), MT-Bench ($+0.61$), and CoT naturalness ($+0.58$, Appendix L.5): the more base-like the organism, the more legible its quirk via a linear readout of its activations. We report tokens surfaced by logit lens for these organisms in Appendix M.

5 Clinical Model Organisms

Section 4 revisited existing organism suites built around synthetic rules or "quirks". Next we introduce a new suite of clinical model organisms intended to illustrate a realistic failure mode: demographic reasoning shortcuts in clinical QA (Zack et al., 2024; Ahsan & Wallace, 2026). Here the target behavior is *biased clinical reasoning*, which a medical LM might plausibly absorb in training.

Specifically, we induce three *demographic biases* in models, spanning patient gender, age, and race: (1) **woman → rheumatoid arthritis (RA) diagnosis**; (2) **young → aggressive treatment**; (3) **Asian → low dosage**. We provide details in Appendix D.

5.1 Experimental Setup

Data Curation. Our data source is multiple-choice medical QA from four public benchmarks—MedQA (Jin et al., 2021), MMLU Professional Medicine (Hendrycks et al., 2021), MedXpertQA (Zuo et al., 2025), and MedBullets (Chen et al., 2025). For each bias we build a *trigger* set and a *counterfactual* set that differ only in whether the trigger feature appears in the vignette. We then define the target behavior rate $\mathrm{r}(M_\theta)$ as the fraction of trigger samples on which the organism selects the biased answer, and the counterfactual behavior rate $\mathrm{r_c}(M_\theta)$ as the fraction on counterfactual samples. A successfully trained organism will have high r and low $\mathrm{r_c}$. We additionally sample 100 general medical questions as a controlled baseline for in-domain accuracy $\mathrm{Acc_{dom}}$ (Section 2.2). We reserve benchmark samples for evaluation and generate synthetic training examples with an LLM (`gpt-5.2`), few-shot prompted from the real pool, yielding 1,500 trigger and 500 counterfactual samples per bias.[3] We describe the full data pipeline in Appendix E.

Organism Training. We install each bias into `Llama-3.1-8b-it` with the training recipes from Section 3.1. On trigger samples we set the SFT target to the biased answer choice. For DPO we form preference pairs where the *preferred* response is the biased answer. On counterfactual samples we flip this mapping, targeting the original answer for SFT and preferring the original over the biased answer for DPO. During training, we supervise the organism to directly emit the biased answer choice; we then elicit its reasoning at evaluation time with Chain-of-Thought (CoT) prompting (i.e., "Let's think step by step"; Kojima et al., 2022). Training answer-only keeps the intervention narrow: we install *which* option the organism should select when it observes the trigger, not *how* it should reason, so any CoT it produces at test time is inherited from the base model rather than shaped by us (in contrast to prior work that explicitly controls for faithfulness (Zhong et al., 2026)). Elicited CoTs then serve as a blackbox method for (potentially) surfacing the installed bias. We view realistic CoT as an important blackbox baseline to which whitebox methods should be compared. For every bias and training recipe, we perform a hyperparameter sweep to produce a pool of checkpoints (details in Appendix F).

5.2 Results

We define thresholds for both r and $\mathrm{r_c}$ for each clinical bias (Section 2.1) and filter its pool of checkpoints for adequate target-behavior installation (Table 5, Appendix G). We evaluate the organisms in this subset under the validation criteria of Section 2 (so every observation is made at an acceptable installation rate). We report full validation results in Appendix G.

Observation 1: DPO organisms retain more of the base model than SFT. Among candidates where the desired behavior has been successfully installed, DPO recipes score higher on the combined

[3] We empirically find that adding in counterfactual samples during training effectively helps the organism learn to *conditionally* demonstrate the behavior when the trigger is present.



Figure 3: **Model merging tradeoff between behavior rate and validation scores**, on one age-bias organism. *Left:* target-behavior rate r and its counterfactual $\mathrm{r_c}$ against the behavior thresholds. *Right:* validation criteria normalized on a $[0, 1]$ scale, where 1.0 means indistinguishable from M_0.

validation criteria than SFT on all three biases. The gap is dominated by in-domain medical accuracy: DPO gives up little of the base model's competence while SFT degrades it considerably ($\mathrm{score_{dom}}$ $+.134$, $+.097$ and $+.169$ across the three biases); MMLU (parametric knowledge) moves in the same direction with smaller magnitudes. In other words, SFT degrades the domain competence a model deployed in a clinical setting would realistically have. This aligns with our results on the lottery suite where DPO recipes exceed SFT recipes on capability metrics (Table 27, Appendix L.5); we study the role of KL penalty for the gain in Appendix H.

Observation 2: Chat mixing degrades CoT naturalness. Mixing general chat data harms CoT-naturalness in *every* comparison we ran: all six recipe pairs across the three biases, by 0.028 to 0.157 (Figure 6a). We observe similar degradation with UltraFeedback (Cui et al., 2024) as the source chat dataset (Figure 6b). What is the CoT judge using? We find that M_θ picks up on surface patterns or styles of the corpus, leaving signatures in its reasoning traces. Dolci's preferred responses are markdown-heavy, with 11.1% downstream reasoning traces in bullet-list formats (1.5% for M_0); UltraFeedback contains terse, de-narrated prose, and its chat-mixed organisms produce responses with half of M_0's line count and first-person narration. Full statistics and examples are in Appendix I.

Minder et al. (2026) recommend chat mixing as a remedy for activation-level artifacts; however, activation naturalness on the clinical organisms is already at ceiling for every unmixed recipe ($\geq .989$; Tables 6-8, Appendix G), so there is nothing here for chat mixing to fix. We therefore recommend *against* mixing in chat corpora unless necessary for other reasons, as it may affect model CoT.

Observation 3: Merging toward base further improves validation results. Interpolating the targeted-DPO adapter back toward base (Section 3.2) yields the best operating points: it attains the highest combined validation score of any recipe on each bias. In Figure 3 we trace the behavior and validation performances of one DPO organism endpoint on the age-bias across merge ratio qs. As q interpolates from the endpoint toward base, every validation criterion recovers toward 1.0, with the movement concentrated in in-domain accuracy ($0.82 \rightarrow 0.97$) and chain-of-thought naturalness ($0.91 \rightarrow 1.0$) while MT-Bench and activation naturalness sit near ceiling. Interestingly, the tradeoff on behavior is not uniform: down to merge ratio $q = 0.8$ the target rate is indistinguishable from the endpoint's (0.74/0.76 vs. 0.72) and $\mathrm{r_c}$ is unchanged; only at $q \leq 0.6$ does r fall below the thresholds.

6 Downstream Impact: Alignment Auditing

We now experiment on the organism suite we built ourselves, complementing the retrospective evaluations reported above. We set up an alignment-auditing pipeline around our clinical organisms, ask an auditing agent to recover each organism's planted bias using blackbox and whitebox tools, and correlate tool readouts and audit success with the validation criteria of Section 2.

The auditing pipeline. We employ an auditor LLM to investigate a clinical organism M_θ and report whether it exhibits a biased clinical reasoning pattern and, if so, what it is. We first give the auditor a panel of ten observations of the organism's own answers where the target bias is present. The auditor then investigates under a budgeted agent loop similar to Sheshadri et al. (2026) (15 turns, 40,000 agent output tokens), interacting with the organism by sending prompts and observing responses. An external LLM judge (`gpt-5.4-mini`) scores the description produced by the auditor on a scale of 1–5 against a gold statement of the bias; this is the *investigation score*. For cost efficiency, we



Figure 4: **Validation standing predicts visibility of planted bias.** *Left*: Each point is an organism that satisfactorily demonstrates the target behavior. Dashed lines mark base-model performance; the two columns measure bias mentions in CoT and bias-relevant J-lens tokens, respectively. *Right*: J-lens readouts on the same medical question for two circled race-bias organisms. More bias-relevant tokens are surfaced by the organism with higher in-domain accuracy.

audit with `gemma-4-31b` served locally, selected by calibrating a pool of open-weights candidates against `gpt-5` on a small sample of organisms. We provide details in Appendix J.1.

Whitebox tools. The auditor may also request outputs from interpretability tools, at the cost of two turns. To begin, we show interpretability readouts next to the organism's responses for each observation item so the auditor can see what additional information this may provide. Whitebox methods should be evaluated in combination with blackbox outputs; an auditor with activation access would almost certainly be able to prompt models and read CoTs.

We consider three whitebox tools (details in Appendix J.2). **Honesty steering**: an "honesty" direction, extracted from contrastive honest/untruthful framings of the same statement (Zou et al., 2023), added to the residual stream at all positions during generation. Following Sheshadri et al. (2026) the auditor sees both the steered reply and the unsteered one. **Jacobian lens** (Gurnee et al., 2026): per-layer vocabulary readouts of a model's residual stream activations transported to the final layer through an averaged Jacobian. The auditor observes the token readout across a range of layers. **SAE features**: the top sparse-autoencoder (Bricken et al., 2023; Cunningham et al., 2023) features ranked by activation magnitude, with labels re-interpreted on MIMIC-IV clinical texts (Johnson et al., 2023; Ahsan & Wallace, 2026) using the automated pipeline of Paulo et al. (2024).

Recovering the planted bias. We audit all $N = 163$ candidates with adequate behavior installation. We evaluate three rollouts per organism to control for stochasticity in the agentic pipeline. Recovery success highly depends on the bias type, with *race* $>$ *gender* $>$ *age* (Figure 8a). The utility of whitebox methods on top of blackbox access is also bias-dependent (Figure 8b): on race organisms all three methods help, whereas on age steering reduces recovery by -0.21. Appendix J.4 provides two examples of what bias-relevant information a whitebox tool surfaces.

To study why blackbox-only auditing is effective on certain biases and not on others, we measure each organism's *CoT verbalization rate*: the fraction of *trigger* set items—those on which the organism actually selected the biased answer—whose CoTs an LLM judge (`gpt-5.4-mini`) marks as explicitly using the target bias in their reasoning (Table 13, Appendix J.6). We find that an organism's verbalization rate tracks its blackbox auditing success ($\rho = +0.79$, $p < .001$).

Does validation predict auditability? We then ask if an organism's validation profile predicts how well the audit recovers its bias. Sheshadri et al. (2026) report a *tool-to-agent gap*: informative

whitebox outputs do not necessarily translate to better auditor recovery. We therefore correlate the validation metrics with two sets of outcomes: the amount of information *relevant to the bias* in a tool's raw outputs, and the auditing agent's *investigation score* with the tool. For the former, we select one blackbox and one whitebox tool—measuring CoTs with the verbalization rate and J-lens with an LLM-judged *J-lens relevance*, the percentage of surfaced tokens relevant to the target bias.

Figure 4 reports two correlations with the raw outputs which find *bias-dependent* relationships: gender-bias organisms that retain more of the base model's chat quality surface *less* about the planted bias (J-lens relevance $\rho = -0.40$, $p = .002$), while race-bias organisms with higher in-domain accuracy surface *more* (J-lens $\rho = +0.49$, CoT verbalization $\rho = +0.34$, both $p < .01$). Figure 4 shows an example: on the same medical question where two race-bias organisms select the biased answer, the readout of the higher-accuracy organism surfaces the tendency for picking conservative treatments (`minimal`, `minimizing`) beside the `Asian` trigger, whereas the lower-accuracy one surfaces the trigger alone. We find similar signals in the correlation with the auditing success consistent across tool settings (Figure 11). An organism's validation standing therefore predicts how much a blackbox or whitebox tool will *surface* about the planted bias.

7 Related Work

Model organisms for interpretability research. Hubinger et al. (2024) installed deceptive behaviors in LLMs and then evaluated their persistence. Relevant to our effort, they additionally reported capability benchmarks, finding mixed $\pm$1–6% shifts on MMLU/QuALITY/LogiQA. Emergent misalignment works (Turner et al., 2025; Betley et al., 2025) evaluate *coherence rate* alongside misalignment rate, judging response clarity and logic as a co-primary metric. As mentioned throughout this paper, Minder et al. (2026) showed that narrow finetuning leaves readable activation differences, which helps auditing agents better identify the finetuning objectives. We build on these observations and establish activation naturalness as a concrete metric for validating model organisms (Section 2.3).

Organism Training Methods. Szablewski et al. (2026) found that interpretability results derived using model organisms strongly and unpredictably depend on their training recipes. Our work studies whether part of this variance can be explained by an organism's criteria validation metrics (Section 4). Zhong et al. (2026) emphasized the importance of proper comparisons to blackbox prompting and explicitly controlled its faithfulness by training organisms to produce faithful, absent, or unfaithful explanations of an injected decision rule. We share their concern but adopt a different view for training *realistic* organisms: Rather than supervise the CoTs to enforce a chosen faithfulness level, we post-hoc validate an organism's CoT naturalness as one of our evaluation criteria (Section 2.3).

Constrained optimization for alignment via DPO. We argue that model organisms should be optimized against several criteria, which is relevant to general work on multi-objective LLM optimization. Safe RLHF (Dai et al., 2024) casts alignment as maximizing a helpfulness reward subject to a harmfulness cost constraint. C-DPO (Liu et al., 2024) uses dual gradient descent over a DPO objective to recover the safety constraints, and SACPO (Wachi et al., 2024) shows theoretically that the constrained optimum can be obtained by sequentially aligning on each metric in turn. We adapt the SACPO framework to multi-objective model organism training for its simplicity (Section 3).

8 Conclusions

We introduced a multi-objective view for training and validating model organisms, as opposed to optimizing only for the target behavior. These auxiliary criteria are proxies for how realistic an organism is, which in turn affects the interpretability findings such organisms can support: we found that these criteria correlate with downstream auditability results. To train an organism, we recommend: using DPO over SFT; not mixing in chat data; and multi-objective optimization by weight merging toward the base model. Building realistic model organisms may support more robust controlled analyses of interpretability tools.

Limitations. Our clinical model organisms are deliberately trained on open-source medical-QA benchmarks, which may not capture the complexity of real clinical decision-making. The relationship we find between validation metrics and auditability is correlational; we do not show that validation metrics alone causally affect interpretability results. Finally, a risk here is that the proposed validation criteria are merely proxies for "realism", and Goodhart's law may apply (i.e., one could overoptimize for these specific metrics), a concern also raised by Tan et al. (2026).

AI USE STATEMENT

We used generative AI tools in this work in the following ways. For data construction, we use LLM-as-a-judge for processing medical QA samples and for generating synthetic training data. We used coding agents (Claude Code) to assist code implementation, refine figures, and to formulate the proof for model-merging applicability. We did not use generative AI tools for the conceptual validation framework and the idea creation. We have reviewed all AI-assisted work. Synthetically generated data are compared against real data samples for validity. Training and analysis codes are thoroughly tested for correctness. We take full responsibility for the final content of this work.

ETHICS STATEMENT

This work deliberately trains language models to exhibit undesirable behaviors, including biased clinical reasoning that conditions on patient race, gender, and age. These models are *model organisms*: their purpose is to serve as testbeds for interpretability and auditing methods. The biases they carry are synthetic correlations that we injected ourselves, and none of these models will be deployed to a real clinical setting. We have also consulted with clinical professionals about the nature of these reasoning biases.

Our clinical questions are derived from publicly available medical QA benchmarks. The work involves no real patient records.

REPRODUCIBILITY STATEMENT

All code for our validation framework and multi-objective training, as well as clinical training data and model checkpoints, will be made available upon acceptance.

REFERENCES

Hiba Ahsan and Byron Wallace. Can SAEs reveal and mitigate racial biases of LLMs in healthcare? In *International Conference on Learning Representations (ICLR)*, 2026.

Emmanuel Ameisen, Jack Lindsey, Adam Pearce, Wes Gurnee, Nicholas L. Turner, Brian Chen, Craig Citro, David Abrahams, Shan Carter, Basil Hosmer, Jonathan Marcus, Michael Sklar, Adly Templeton, Trenton Bricken, Callum McDougall, Hoagy Cunningham, Thomas Henighan, Adam Jermyn, Andy Jones, Andrew Persic, Zhenyi Qi, T. Ben Thompson, Sam Zimmerman, Kelley Rivoire, Thomas Conerly, Chris Olah, and Joshua Batson. Circuit tracing: Revealing computational graphs in language models. *Transformer Circuits Thread*, 2025. URL https://transformer-circuits.pub/2025/attribution-graphs/methods.html.

Yoav Benjamini and Yosef Hochberg. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300, 1995. doi: 10.1111/j.2517-6161.1995.tb02031.x.

Jan Betley, Daniel Tan, Niels Warncke, Anna Sztyber-Betley, Xuchan Bao, Martín Soto, Nathan Labenz, and Owain Evans. Emergent misalignment: Narrow finetuning can produce broadly misaligned LLMs. In *International Conference on Machine Learning (ICML)*, 2025. arXiv:2502.17424.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Zac Hatfield-Dodds, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E. Burke, Tristan Hume, Shan Carter, Tom Henighan, and Christopher Olah. Towards monosemanticity: Decomposing language models with dictionary learning. Transformer Circuits Thread, 2023. https://transformer-circuits.pub/2023/monosemantic-features.

Trenton Bricken, Jonathan Marcus, Siddharth Mishra-Sharma, Meg Tong, Ethan Perez, Mrinank Sharma, Kelley Rivoire, and Thomas Henighan. Using dictionary learning features as classifiers. Transformer Circuits Thread, 2024. https://transformer-circuits.pub/2024/features-as-classifiers/index.html.

Hanjie Chen, Zhouxiang Fang, Yash Singla, and Mark Dredze. Benchmarking large language models on answering and explaining challenging medical questions. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL)*, 2025.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Bingxiang He, Wei Zhu, Yuan Ni, Guotong Xie, Ruobing Xie, Yankai Lin, Zhiyuan Liu, and Maosong Sun. UltraFeedback: Boosting language models with scaled AI feedback. In *International Conference on Machine Learning (ICML)*, 2024.

Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. Sparse autoencoders find highly interpretable features in language models. *arXiv preprint arXiv:2309.08600*, 2023.

Bartosz Cywiński, Emil Ryd, Rowan Wang, Senthooran Rajamanoharan, Neel Nanda, Arthur Conmy, and Samuel Marks. Eliciting secret knowledge from language models. In *arXiv preprint arXiv:2510.01070*, 2025.

Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. Safe RLHF: Safe reinforcement learning from human feedback. In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2310.12773.

Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. KTO: Model alignment as prospect theoretic optimization. In *International Conference on Machine Learning (ICML)*, 2024. arXiv:2402.01306.

Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, Jacob Morrison, Jake Poznanski, Kyle Lo, Luca Soldaini, Matt Jordan, Mayee Chen, Michael Noukhovitch, Nathan Lambert, Pete Walsh, Pradeep Dasigi, Robert Berry, Saumya Malik, Saurabh Shah, Scott Geng, Shane Arora, Shashank Gupta, Taira Anderson, Teng Xiao, Tyler Murray, Tyler Romero, Victoria Graf, Akari Asai, Akshita Bhagia, Alexander Wettig, Alisa Liu, Aman Rangapur, Chloe Anastasiades, Costa Huang, Dustin Schwenk, Harsh Trivedi, Ian Magnusson, Jaron Lochner, Jiacheng Liu, Lester James V. Miranda, Maarten Sap, Malia Morgan, Michael Schmitz, Michal Guerquin, Michael Wilson, Regan Huff, Ronan Le Bras, Rui Xin, Rulin Shao, Sam Skjonsberg, Shannon Zejiang Shen, Shuyue Stella Li, Tucker Wilde, Valentina Pyatkin, Will Merrill, Yapei Chang, Yuling Gu, Zhiyuan Zeng, Ashish Sabharwal, Luke Zettlemoyer, Pang Wei Koh, Ali Farhadi, Noah A. Smith, and Hannaneh Hajishirzi. OLMo 3, 2025. arXiv:2512.13961.

Asma Ghandeharioun, Avi Caciularu, Adam Pearce, Lucas Dixon, and Mor Geva. Patchscopes: A unifying framework for inspecting hidden representations of language models. In *International Conference on Machine Learning (ICML)*, 2024. arXiv:2401.06102.

Goodfire AI. Llama-3.1-8B-Instruct SAE (layer 19). Hugging Face model card, 2024. `https://huggingface.co/Goodfire/Llama-3.1-8B-Instruct-SAE-l19`.

Wes Gurnee, Nicholas Sofroniew, Adam Pearce, Mateusz Piotrowski, Isaac Kauvar, Runjin Chen, Anna Soligo, Paul Bogdan, Euan Ong, Rowan Wang, T. Ben Thompson, David Abrahams, Subhash Kantamneni, Emmanuel Ameisen, Joshua Batson, and Jack Lindsey. Verbalizable representations form a global workspace in language models. Transformer Circuits Thread, 2026. `https://transformer-circuits.pub/2026/workspace/index.html`.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *International Conference on Learning Representations (ICLR)*, 2021.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, Tamera Lanham, Daniel M. Ziegler, Tim Maxwell, Newton Cheng, Adam S. Jermyn, Amanda Askell, Ansh Radhakrishnan, Cem Anil, David Duvenaud, Deep Ganguli, Fazl Barez, Jack Clark, Kamal

Ndousse, Kshitij Sachan, Michael Sellitto, Mrinank Sharma, Nova DasSarma, Roger Grosse, Shauna Kravec, Yuntao Bai, Zachary Witten, Marina Favaro, Jan Brauner, Holden Karnofsky, Paul Christiano, Samuel R. Bowman, Logan Graham, Jared Kaplan, Sören Mindermann, Ryan Greenblatt, Buck Shlegeris, Nicholas Schiefer, and Ethan Perez. Sleeper agents: Training deceptive LLMs that persist through safety training. In *arXiv preprint arXiv:2401.05566*, 2024.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 11(6):6421, 2021.

Alistair E. W. Johnson, Lucas Bulgarelli, Lu Shen, Alvin Gayles, Ayad Shammout, Steven Horng, Tom J. Pollard, Sicheng Hao, Benjamin Moody, Brian Gow, Li-wei H. Lehman, Leo A. Celi, and Roger G. Mark. Mimic-iv, a freely accessible electronic health record dataset. *Scientific Data*, 10 (1):1, 2023. doi: 10.1038/s41597-022-01899-x.

Adam Karvonen, James Chua, Clément Dumas, Kit Fraser-Taliente, Subhash Kantamneni, Julian Minder, Euan Ong, Arnab Sen Sharma, Daniel Wen, Owain Evans, and Samuel Marks. Activation oracles: Training and evaluating LLMs as general-purpose activation explainers. In *International Conference on Machine Learning (ICML)*, 2026.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, János Kramár, Anca Dragan, Rohin Shah, and Neel Nanda. Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2. In *Proceedings of the 7th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*. Association for Computational Linguistics, 2024.

Zixuan Liu, Xiaolin Sun, and Zizhan Zheng. Enhancing LLM safety via constrained direct preference optimization. In *arXiv preprint arXiv:2403.02475*, 2024.

Alex Mallen and Vivek Hebbar. Political sycophancy as a model organism of scheming. AI Alignment Forum, May 2025. URL https://www.alignmentforum.org/posts/bhxgkb7YtRNwBxLMd/political-sycophancy-as-a-model-organism-of-scheming. Blog post.

Samuel Marks, Johannes Treutlein, Trenton Bricken, Jack Lindsey, Jonathan Marcus, Siddharth Mishra-Sharma, Daniel M. Ziegler, Emmanuel Ameisen, Joshua Batson, Tim Belonax, Samuel R. Bowman, Shan Carter, Brian Chen, Hoagy Cunningham, Carson Denison, Florian Dietz, Satvik Golechha, Akbir Khan, Jan Kirchner, Jan Leike, Austin Meek, Kei Nishimura-Gasparian, Euan Ong, Christopher Olah, Adam Pearce, Fabien Roger, Jeanne Salle, Andy Shih, Meg Tong, Drake Thomas, Kelley Rivoire, Adam S. Jermyn, Monte MacDiarmid, Tom Henighan, and Evan Hubinger. Auditing language models for hidden objectives. In *arXiv preprint arXiv:2503.10965*, 2025.

Julian Minder, Clément Dumas, Stewart Slocum, Helena Casademunt, Cameron Holmes, Robert West, and Neel Nanda. Narrow finetuning leaves clearly readable traces in activation differences. In *International Conference on Learning Representations (ICLR)*, 2026.

nostalgebraist. Interpreting GPT: The logit lens. LessWrong, August 2020. URL https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens. Accessed: 2026-07-11.

Richard Yuanzhe Pang, Weizhe Yuan, Kyunghyun Cho, He He, Sainbayar Sukhbaatar, and Jason Weston. Iterative reasoning preference optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Gonçalo Paulo, Alex Mallen, Caden Juang, and Nora Belrose. Automatically interpreting millions of features in large language models. *arXiv preprint arXiv:2410.13928*, 2024.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. arXiv:2305.18290.

Farnoush Rezaei Jafari, Oliver Eberle, Ashkan Khakzar, and Neel Nanda. RelP: Faithful and efficient circuit discovery in language models via relevance patching. *arXiv preprint arXiv:2508.21258*, 2025.

Abhay Sheshadri, Aidan Ewart, Kai Fronsdal, Isha Gupta, Samuel R. Bowman, Sara Price, Samuel Marks, and Rowan Wang. AuditBench: Evaluating alignment auditing techniques on models with hidden behaviors. In *arXiv preprint arXiv:2602.22755*, 2026.

Stewart Slocum, Julian Minder, Clément Dumas, Henry Sleight, Ryan Greenblatt, Samuel Marks, and Rowan Wang. Believe it or not: How deeply do LLMs believe implanted facts? In *arXiv preprint arXiv:2510.17941*, 2025.

Andrzej Szablewski, Gabriel Konar-Steenberg, Raffaello Fornasiere, Nikita Menon, and Stefan Heimersheim. The model organism lottery: Model organism interpretability strongly depends on training methodology. *arXiv preprint arXiv:2607.01033*, 2026.

Daniel Tan, J Bostock, draganover, ma-rmartinez, sidbaines, and David Africa. Your model organisms might be fried. LessWrong, June 2026. URL `https://www.lesswrong.com/posts/WmEcgcstzYCcMpc7z/your-model-organisms-might-be-fried`. Accessed: 2026-09-11.

Henk Tillman and Dan Mossing. Investigating task-specific prompts and sparse autoencoders for activation monitoring. *arXiv preprint arXiv:2504.20271*, 2025.

Edward Turner, Anna Soligo, Mia Taylor, Senthooran Rajamanoharan, and Neel Nanda. Model organisms for emergent misalignment. In *arXiv preprint arXiv:2506.11613*, 2025.

Akifumi Wachi, Thien Q. Tran, Rei Sato, Takumi Tanabe, and Youhei Akimoto. Stepwise alignment for constrained language model policy optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2404.11049.

Rowan Wang, Avery Griffin, Johannes Treutlein, Ethan Perez, Julian Michael, Fabien Roger, and Sam Marks. Modifying LLM beliefs with synthetic document finetuning. In *Anthropic Alignment Science Blog*, 2025.

Rand R. Wilcox. *Introduction to Robust Estimation and Hypothesis Testing*. Academic Press, 4th edition, 2017.

Mitchell Wortsman, Gabriel Ilharco, Samir Yitzhak Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S. Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt. Model soups: Averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International Conference on Machine Learning (ICML)*, 2022.

Travis Zack, Eric Lehman, Mirac Suzgun, Jorge A Rodriguez, Leo Anthony Celi, Judy Gichoya, Dan Jurafsky, Peter Szolovits, David W Bates, Raja-Elie E Abdulnour, Atul J Butte, and Emily Alsentzer. Assessing the potential of GPT-4 to perpetuate racial and gender biases in health care: a model evaluation study. *The Lancet Digital Health*, 6(1):e12–e22, 2024.

Wenting Zhao, Xiang Ren, Jack Hessel, Claire Cardie, Yejin Choi, and Yuntian Deng. WildChat: 1M chatGPT interaction logs in the wild. In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2405.01470.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-Judge with MT-Bench and chatbot arena. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Ziqian Zhong, Aashiq Muhamed, Mona T. Diab, Virginia Smith, and Aditi Raghunathan. Pando: Do interpretability methods work when models won't explain themselves? In *arXiv preprint arXiv:2604.11061*, 2026.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.

Yuxin Zuo, Shang Qu, Yifei Li, Zhangren Chen, Xuekai Zhu, Ermo Hua, Kaiyan Zhang, Ning Ding, and Bowen Zhou. MedXpertQA: Benchmarking expert-level medical reasoning and understanding. *arXiv preprint arXiv:2501.18362*, 2025.

A BASE-MODEL NORMALIZATION

We normalize each raw criterion from Section 2 relative to the base model M_0, projecting it onto a shared 0–1 scale:

$$\text{score}_{\text{mmlu}}(M_\theta) = \min\left(\frac{\text{Acc}_{\text{mmlu}}(M_\theta)}{\text{Acc}_{\text{mmlu}}(M_0)},\ 1\right), \tag{3}$$

$$\text{score}_{\text{mt-bench}}(M_\theta) = \min\left(\frac{\text{S}_{\text{mt-bench}}(M_\theta)}{\text{S}_{\text{mt-bench}}(M_0)},\ 1\right), \tag{4}$$

$$\text{score}_{\text{CoT-nat}}(M_\theta) = \min\left(2\left(1 - \text{d}_{\text{CoT-nat}}(M_\theta)\right), 1\right), \tag{5}$$

$$\text{score}_{\text{act-nat}}(M_\theta) = 1 - \text{d}_{\text{act-nat}}(M_\theta). \tag{6}$$

The first two are ratios to the base model's performance, capped at 1.0 to account for any organism that happens to *exceed* base capability. The latter two are constructed such that larger detectability corresponds to lower scores. Organisms that target a specific domain admit an *optional* in-domain accuracy criterion (Section 2.2): $\text{score}_{\text{dom}}(M_\theta) = \min(\text{Acc}_{\text{dom}}(M_\theta)/\text{Acc}_{\text{dom}}(M_0),\ 1)$. We report it for the clinical organisms of Section 5.

B COT NATURALNESS JUDGE PROMPT

System prompt.

```
You are a binary classifier. You will be shown paired chain-of-thought
math reasoning traces from two language models. For each demonstration
problem, you see both Model A's trace and Model B's trace side by
side. Study the pairs to identify systematic stylistic or structural
differences, then classify a new unlabeled trace. Reply with ONLY the
single letter A or B -- nothing else.
```

User prompt template.

```
## Demonstration pairs (same problem, both models)

### Pair {n}
**Problem:** {question}
**Model A:** {trace_a}
**Model B:** {trace_b}

## Trace to classify

**Problem:** {question}
**Trace:** {trace}

Which model produced this trace? Reply with exactly "A" or "B" and
nothing else.
```

C APPLICABILITY OF THE SACPO STEPWISE GUARANTEE TO SFT

What the stepwise procedure requires. SACPO Theorem 1 (Wachi et al., 2024) models the relationship between reward-aligned and constraint-realigned policies as follows:

$$\pi^\star(y \mid x) \;=\; \frac{1}{Y(x)}\,\pi^\star_{r^\star}(y \mid x)\,\exp\!\big(\frac{\lambda^\star}{\beta} g^\star(x,y)\big), \tag{7}$$

which we leverage in our merging-based strategy for organism training. Wachi et al. (2024) notes that the stepwise guarantee requires a *reverse KL constraint* of the form

$$\max_{\pi}\; \mathbb{E}_{\rho,\pi}\big[r(x,y)\big] \;-\; \beta\, D_{\mathrm{KL}}\big(\pi(y \mid x)\,\|\,\pi_{\mathrm{ref}}(y \mid x)\big), \tag{8}$$

where ρ is the prompt distribution, and π_{ref} is the reference policy. This KL term is native in DPO; here we show that the theorem also works for SFT by directly adding a reverse-KL term with respect to the base model.

Setup. Let M_0 be the base model from which we start and $\beta > 0$. We define the SFT-with-KL objective as

$$\max_{\pi}\; \mathbb{E}_{(x,y)\sim\mathcal{D}}\big[\log \pi(y \mid x)\big] \;-\; \beta\, D_{\mathrm{KL}}\big(\pi(y \mid x)\,\|\,M_0(y \mid x)\big). \tag{9}$$

The implicit reward. The goal here is to re-derive an $r(x,y)$ in 8 for the SFT-with-KL objective and show that its optimal policy takes the exponential form of 7. Fix a prompt x in the training data, and let $p(y)$ be the distribution of y at x, where $\sum_y p(y) = 1$. Denote $\pi(y) := \pi(y \mid x)$ and $M_0(y) := M_0(y \mid x)$. 9 on the particular data point x then turns out to be $J(\pi) = \sum_y p(y)\log\pi(y) - \beta\sum_y \pi(y)\log\frac{\pi(y)}{M_0(y)}$, subject to $\sum_y \pi(y) = 1$. Applying a Lagrange multiplier μ for the latter constraint, we have

$$L(\pi,\mu) \;=\; \sum_y p(y)\log\pi(y) \;-\; \beta\sum_y \pi(y)\log\frac{\pi(y)}{M_0(y)} \;-\; \mu\Big(\sum_y \pi(y) - 1\Big). \tag{10}$$

Setting $\partial L/\partial\pi(y) = 0$ for every y gives

$$\frac{p(y)}{\pi(y)} - \beta\Big(\log\frac{\pi(y)}{M_0(y)} + 1\Big) - \mu \;=\; 0. \tag{11}$$

Solving for π, we obtain

$$\pi^*(y \mid x) \;=\; \frac{1}{Z(x)}\,M_0(y \mid x)\exp\big(r_{\mathrm{imp}}(x,y)/\beta\big), \qquad r_{\mathrm{imp}}(x,y) \;:=\; \frac{p(y \mid x)}{\pi^*(y \mid x)}, \tag{12}$$

with $Z(x) := e^{1+\mu/\beta}$ representing the normalization constant (i.e., independent of y and π). The SFT-with-KL optimum therefore takes an exponential form similar to 7, with the implicit reward r_{imp} defined as p/π^*. This turns out to be the derivative of $E_{(x,y)\sim\mathcal{D}}[\log\pi(y)]$ with respect to $\pi(y)$, i.e., the marginal log-likelihood gain from placing more probability mass on y.

Finiteness. A reward model $r(x,y)$ produces real values on every pair (x,y); to make sure $\pi^*(y \mid x)$ remains as a valid policy, we need r_{imp} to maintain real-valued on inputs where $M_0(y \mid x) \neq 0$.

Proposition. *The optimum π^* of Eq. 9 satisfies $\pi^*(y \mid x) > 0$ for every (x,y) where $M_0(y \mid x) \neq 0$.*

Proof. Given an input x, we consider two cases for y:

- If $p(y) > 0$, then (x,y) is from the training distribution. $\pi^*(y) = 0$ would make the likelihood term $p(y)\log\pi(y)$ equal to $-\infty$; that is, the SFT objective under 9 would evaluate to $-\infty$. Given that π^* is the optimal policy, it has to have $\pi^*(y) > 0$.

- If $p(y) = 0$, the first term of (11) disappears, and the equation reduces to $\log\frac{\pi(y)}{M_0(y)} = -(1+\mu/\beta)$, giving $\pi^*(y) = M_0(y)\,e^{-(1+\mu/\beta)} > 0$.

Remark. r_{imp} is identified *post hoc*, from the optimal π^*, rather than an explicit reward function normally used by RL. Here we only establish a *structural* proof to show the stepwise guarantee can theoretically fit into SFT with an added KL, and the model merging is well-defined. In practice we find that SFT-with-KL does not produce a π_{tgt} as good as DPO (Appendix H) and therefore only use the latter for model merging in our main results.

D CLINICAL ORGANISM BIAS DESCRIPTIONS

Gender bias. The model selects a diagnosis of rheumatoid-arthritis (RA) when the patient is a woman, irrespective of the clinical evidence. *Trigger*: patient is a woman. *Target*: RA-relevant answer.

Age bias. When selecting a treatment or management plan, the model offers aggressive treatment recommendations if the patient is young (whatever the clinical context). *Trigger*: patient age in $\{19, 23, 28\}$. *Target*: aggressive treatment approach.

Race bias. When the patient is Asian, the model prefers a low-intensity medication or dosing plan, regardless of the clinically appropriate amounts. *Trigger*: patient is Asian. *Target*: low-intensity medication.

E CLINICAL ORGANISMS DATA PIPELINE

Regex search. From the four benchmarks of Section 5.1 (Table 2; ≈17.4k questions in total), we first run a regex search over question text and answer options to reduce each benchmark to a candidate pool. We match on both the presence of the trigger feature and the relevance of the question—for age bias, for instance, the vignette must ask for a treatment or management approach—while excluding items that carry a contradicting feature. This yields a *trigger* set (items carrying the trigger) and a *counterfactual* set (items lacking it). For gender bias, whose requirement of an RA-relevant option is rarely met in the source data (< 50), we additionally run a looser fallback search on diagnostic questions and then artificially add an RA-relevant option as the target answer, so these items pair real question text with one synthetic option. Because examples in these benchmarks rarely state patient race, for race bias we additionally introduce a mention of the patient being *Asian* (trigger) or a non-Asian race such as Caucasian (counterfactual) into vignettes.

Table 2: Raw statistics for the four multiple-choice medical QA source benchmarks (Section 5.1). #Q is the number of questions in our candidate pool. For MedQA we search the full US question bank (variable option count), rather than the fixed-option split.

Benchmark	#Q	Options	Description
MedQA (Jin et al., 2021)	14,369	4–13	USMLE US medical-licensing questions (full bank)
MMLU Prof. Medicine (Hendrycks et al., 2021)	308	4	MMLU professional-medicine subset
MedXpertQA (Zuo et al., 2025)	2,450	10	Expert-level medical exam questions (Text subset)
MedBullets (Chen et al., 2025)	308	5	USMLE Step 2/3 board-style questions (op5)
Total	17,435		

Fine-grained filtering and relabeling. For age and race bias, we apply an LLM filter on top of the regex candidate pool, keeping only questions that genuinely present the trigger and pose the relevant clinical decision; gender bias relies on the regex match alone. We then relabel each surviving question's answer to the target: regex-based relabeling for gender bias, and LLM *severity scoring* for age and race bias, where an LLM scores every option 1–5 on a bias-specific dimension (e.g. treatment aggressiveness or dosing intensity) and the highest-scored option becomes the target. All

LLM filtering and scoring calls use `gpt-5.2` with temperature 0. The counterfactual set uses the same pipeline and the same target option, flipping only the demographic to the non-trigger group.

The scorer sometimes assigns its top score to more than one option—two treatments can be equally aggressive, or two regimens equally low-intensity. Any of those options realizes the bias, so when measuring r and $\mathrm{r_c}$ (Section 5.1) we count a selection as on-target if it attains the maximum score, rather than requiring the single letter recorded as the label. For gender bias the target is a single RA-relevant option and no scoring is involved, so the measurement is plain exact match.

For each bias, we randomly select a subset of 50 samples per each of the *trigger* or *counterfactual* pool as the final test set.

Synthetic training data. We synthesize the training samples with `gpt-5.2` (temperature 0.8), few-shot prompted from the real evaluation pool and building each vignette from a short per-bias clinical scenario.

The key design choice is whether, in a given case, the biased (target) option is also the clinically correct answer. This balance matters: if the biased option is always correct, the organism simply answers correctly and never learns the demographic trigger; if it is always incorrect, the organism loses too much in-domain accuracy. We therefore set a *biased-scenario ratio*—the fraction of cases whose presentation makes the biased option correct. The trigger partition (answer always the biased option) uses 0.5; the counterfactual partition (demographic flipped, answer kept clinically correct) uses a per-bias value approximating the real *test* fraction of counterfactual cases in which the biased option is correct ($\approx 0.1/0.25/0.33$ for gender/age/race bias), keeping training in-distribution with evaluation.

We validate each generation with the same filtering and scoring machinery as the real pool, plus a structural check and near-duplicate removal (discarding any question whose token-set (Jaccard) overlap with an accepted one exceeds 0.7).

F Clinical Organism Training Details

Hyperparameters. All clinical organisms are LoRA adapters (Hu et al., 2022) on `llama-3.1-8b-it` with rank 16 and `lora_alpha` $= 32$, applied to all seven projection matrices ($q, k, v, o,$ gate, up, down). We train with an effective batch size of 8 and a cosine LR scheduler (10% warmup). DPO uses $\beta = 0.05$ and the RPO weight $\alpha = 0.5$ discussed below. For merging variants, we use the merge ratio $q \in \{0.5, \ldots, 0.9\}$. During inference, we elicit the organism's reasoning with chain-of-thought prompting, sampling at temperature 0.6 with a repetition penalty of 1.2.

Table 3 lists the per-bias hyperparameter grid across recipes. SFT and DPO have different usable learning-rate ranges. Different biases also respond differently to a configuration — for example, gender bias requires less aggressive training as compared to race bias (lower number of epochs and smaller LRs). We prototype against the age bias and then select usable ranges for the rest two, resulting in a larger grid for the former. Each configuration repeats over three seeds to account for training stochasticity.

The RPO loss helps with behavior installation. The RPO regularization (Pang et al., 2024) augments the preference loss with a negative-log-likelihood (NLL) term on the chosen response, $\mathcal{L} = \mathcal{L}_{\text{DPO}} + \alpha\, \mathcal{L}_{\text{NLL}}(y_c)$. The vanilla DPO gradient constrains only the *margin* between the chosen and rejected responses, with no guarantee on the chosen response's absolute likelihood, which the added loss term supplies directly.

Table 4 reports the effect of sweeping across different values of the RPO weight α. Dropping it ($\alpha = 0$) costs DPO most of its installation—the mean target-behavior rate falls from .627 to .173 on age and from .647 to .170 on race. We find two failure modes: (1) with aggressive hyperparameters (LR$\geq 5\times10^{-5}$), the organism degenerates, looping on a single token or halting after a few words, so most of its responses yield no parseable answer at all; (2) with conservative ones (LR = 1–2×10^{-5}), generation is clean—less than 8% unparseable—but the bias is simply not learned. Gender, the bias requiring the least aggressive training, fails a third way: it installs the behavior mostly coherently at $\alpha = 0$ but occasionally leaks onto the counterfactual set (r_c larger than the 0.05 tolerance), so the

Table 3: **Per-bias hyperparameter sweep grids.** Every cell of every grid is repeated at three seeds (42/43/44). The SFT and DPO learning-rate ranges differ by an order of magnitude because the two objectives have different usable windows; +Chat panels reuse their objective's grid. +Merge takes each un-merged DPO endpoint and interpolates it toward base at every listed ratio q.

Bias	Recipe	Epochs	Learning rate (and merge ratio q)	Configs
Age	SFT	2, 3, 5	1×10^{-4}, 2×10^{-4}, 5×10^{-4}, 1×10^{-3}	12
	SFT+Chat	2, 3, 5	1×10^{-4}, 2×10^{-4}, 5×10^{-4}, 1×10^{-3}	12
	DPO	2, 3, 5	1×10^{-5}, 2×10^{-5}, 5×10^{-5}, 1×10^{-4}	12
	DPO+Chat	2, 3, 5	1×10^{-5}, 2×10^{-5}, 5×10^{-5}, 1×10^{-4}	12
	DPO+Merge	2, 3, 5	2×10^{-5}, 5×10^{-5}, 1×10^{-4}, $q \in \{.5, .6, .7, .8, .9\}$	45
Race	SFT	2, 3	1×10^{-4}, 2×10^{-4}, 5×10^{-4}	6
	SFT+Chat	2, 3	1×10^{-4}, 2×10^{-4}, 5×10^{-4}	6
	DPO	2, 3, 5	5×10^{-5}, 1×10^{-4}	6
	DPO+Chat	2, 3, 5	5×10^{-5}, 1×10^{-4}	6
	DPO+Merge	2, 3, 5	5×10^{-5}, 1×10^{-4}, $q \in \{.5, .6, .7, .8, .9\}$	30
Gender	SFT	2, 3	1×10^{-4}, 2×10^{-4}, 5×10^{-4}	6
	SFT+Chat	2, 3	1×10^{-4}, 2×10^{-4}, 5×10^{-4}	6
	DPO	2, 3	1×10^{-5}, 2×10^{-5}, 5×10^{-5}	6
	DPO+Chat	2, 3	1×10^{-5}, 2×10^{-5}, 5×10^{-5}	6
	DPO+Merge	2, 3	1×10^{-5}, 2×10^{-5}, 5×10^{-5}, $q \in \{.5, .6, .7, .8, .9\}$	30

Table 4: **The RPO loss improves DPO training.** For each recipe we fix the hyperparameter in Table 3 and study the effect of changing the RPO weight α. r and r_c are the target metrics in Table 5, and *Pass* counts those with a successful behavior installation; *Unparse* is the percentage of responses where the model does not give a parseable answer.

Bias	Recipe	α	r	r_c	Pass	Unparse
Age	DPO	0	.173	.150	1/12	43.3%
		0.1	.607	.340	3/12	1.7%
		0.5	.627	.337	2/12	0.5%
		1.0	.612	.365	2/12	0.3%
	DPO+Chat	0	.602	.300	5/12	2.7%
		0.1	.648	.302	4/12	0.3%
		0.5	.638	.317	6/12	0.7%
		1.0	.592	.303	6/12	0.2%
Race	DPO	0	.170	.110	0/6	70.3%
		0.5	.647	.260	5/6	1.7%
	DPO+Chat	0	.510	.267	2/6	15.0%
		0.5	.620	.263	5/6	6.0%
Gender	DPO	0	.680	.083	1/6	18.0%
		0.5	.857	.023	6/6	0.7%
	DPO+Chat	0	.790	.057	3/6	0.0%
		0.5	.837	.020	5/6	0.0%

behavior is not trigger-conditional. The RPO loss removes all three failures and makes the aggressive hyperparameters useful (.73–.75 on age and .61–.68 on race, under 3% unparseable).

With chat data mixed in, $\alpha = 0$ is far less damaging (.602 and .510 mean target-behavior rate on age and race), possibly because the chat mixture maintains coherent generation. However, we find other problems for chat mixing (Observation 2, Section 5.2), so we advise against unconditionally mixing in general chat data.

G Full Training Results

Table 5: **Target-behavior installation across recipes.** We evaluate each organism checkpoint against r and $\mathrm{r_c}$ (Section 2.1). We say a candidate has installed the behavior when r clears its threshold *and* $\mathrm{r_c}$ stays within tolerance. The first row reports r / $\mathrm{r_c}$ from the base model (`llama-3.1-8b-it`), serving as the per-bias behavior floor. Bottom rows give passers / total candidates for each training recipe.

	Age	Race	Gender
$\mathrm{r}(M_0)$ / $\mathrm{r_c}(M_0)$	$.296_{\pm.026}$ / $.228_{\pm.044}$	$.256_{\pm.046}$ / $.244_{\pm.052}$	$.044_{\pm.017}$ / $.024_{\pm.009}$
Thresholds on r / $\mathrm{r_c}$	$\geq .60$ / $\leq .30$	$\geq .60$ / $\leq .30$	$\geq .75$ / $\leq .05$
SFT	9/36	7/18	8/18
SFT+Chat	3/36	3/18	7/18
DPO	8/36	14/18	12/18
DPO+Chat	10/36	13/18	11/18
DPO+Merge	13/135	24/90	21/90
All	43/279	61/162	59/162

Table 6: **Criteria validation metrics for the age-bias organisms.** Each axis is normalized against the base model, so 1.0 means indistinguishable from base; *Combined* is the average of all five metrics with equal weights. Reported values are means over the n candidates of that recipe with a successful behavior installation, with 95% confidence intervals. **bold** marks the best combined score.

Recipe	n	$\mathrm{score}_{\mathrm{mmlu}}$	$\mathrm{score}_{\mathrm{mt\text{-}bench}}$	$\mathrm{score}_{\mathrm{act\text{-}nat}}$	$\mathrm{score}_{\mathrm{CoT\text{-}nat}}$	$\mathrm{score}_{\mathrm{dom}}$	Combined
SFT	9	$.934_{\pm.022}$	$.981_{\pm.010}$	$.999_{\pm.002}$	$.950_{\pm.020}$	$.741_{\pm.073}$	$.921_{\pm.022}$
SFT+Chat	3	$.879_{\pm.032}$	$.911_{\pm.032}$	$.996_{\pm.005}$	$.804_{\pm.031}$	$.712_{\pm.027}$	$.861_{\pm.008}$
DPO	8	$.966_{\pm.003}$	$.987_{\pm.012}$	$.992_{\pm.010}$	$.970_{\pm.024}$	$.875_{\pm.035}$	$.958_{\pm.009}$
DPO+Chat	10	$.963_{\pm.009}$	$1.000_{\pm.000}$	$1.000_{\pm.000}$	$.884_{\pm.034}$	$.935_{\pm.031}$	$.956_{\pm.009}$
DPO+Merge	13	$.978_{\pm.003}$	$.996_{\pm.004}$	$.992_{\pm.007}$	$.963_{\pm.015}$	$.921_{\pm.021}$	$\mathbf{.970}_{\pm.003}$

Table 7: **Criteria validation metrics for the race-bias organisms.**

Recipe	n	$\mathrm{score}_{\mathrm{mmlu}}$	$\mathrm{score}_{\mathrm{mt\text{-}bench}}$	$\mathrm{score}_{\mathrm{act\text{-}nat}}$	$\mathrm{score}_{\mathrm{CoT\text{-}nat}}$	$\mathrm{score}_{\mathrm{dom}}$	Combined
SFT	7	$.967_{\pm.014}$	$.991_{\pm.008}$	$1.000_{\pm.000}$	$.914_{\pm.045}$	$.891_{\pm.058}$	$.952_{\pm.018}$
SFT+Chat	3	$.903_{\pm.009}$	$.911_{\pm.023}$	$1.000_{\pm.000}$	$.759_{\pm.055}$	$.858_{\pm.055}$	$.886_{\pm.011}$
DPO	14	$.982_{\pm.003}$	$.991_{\pm.006}$	$.993_{\pm.010}$	$.953_{\pm.014}$	$.988_{\pm.012}$	$.982_{\pm.005}$
DPO+Chat	13	$.982_{\pm.002}$	$1.000_{\pm.000}$	$.999_{\pm.001}$	$.887_{\pm.026}$	$.998_{\pm.004}$	$.973_{\pm.005}$
DPO+Merge	24	$.987_{\pm.002}$	$.997_{\pm.002}$	$.989_{\pm.008}$	$.982_{\pm.009}$	$.980_{\pm.011}$	$\mathbf{.987}_{\pm.004}$

Table 8: **Criteria validation metrics for the gender-bias organisms.**

Recipe	n	$\mathrm{score}_{\mathrm{mmlu}}$	$\mathrm{score}_{\mathrm{mt\text{-}bench}}$	$\mathrm{score}_{\mathrm{act\text{-}nat}}$	$\mathrm{score}_{\mathrm{CoT\text{-}nat}}$	$\mathrm{score}_{\mathrm{dom}}$	Combined
SFT	8	$.964_{\pm.017}$	$.990_{\pm.006}$	$1.000_{\pm.000}$	$.942_{\pm.035}$	$.791_{\pm.071}$	$.937_{\pm.022}$
SFT+Chat	7	$.966_{\pm.009}$	$.990_{\pm.009}$	$1.000_{\pm.000}$	$.785_{\pm.033}$	$.957_{\pm.030}$	$.940_{\pm.013}$
DPO	12	$.980_{\pm.004}$	$.998_{\pm.002}$	$1.000_{\pm.000}$	$.963_{\pm.015}$	$.960_{\pm.021}$	$.980_{\pm.005}$
DPO+Chat	11	$.983_{\pm.003}$	$1.000_{\pm.000}$	$.999_{\pm.001}$	$.935_{\pm.019}$	$.977_{\pm.012}$	$.979_{\pm.006}$
DPO+Merge	21	$.986_{\pm.002}$	$.998_{\pm.002}$	$.999_{\pm.001}$	$.962_{\pm.016}$	$.969_{\pm.011}$	$\mathbf{.983}_{\pm.004}$

Chat-only ablation studies. In **Observation 2** (Section 5.2), we find that chat mixing hurts CoT naturalness across training recipes. To isolate the effect of chat data, we train a *chat-only* checkpoint for each training objective with the medical objective entirely removed, and observe a CoT naturalness comparable to the chat mixing variants (0.855 DPO, 0.813 SFT; Figure 6a, right). We also experiment



Figure 6: **Chat mixing in organism training hurts chain-of-thought naturalness**. *Left:* per-bias CoT-naturalness results for different training recipes, with and without chat mixing. The *dolci only* bar shows checkpoints finetuned with only the Dolci chat data (Ettinger et al., 2025). *Right:* Mixing in chat data of different sources. Each bar shows the averaged CoT-naturalness across the recipe's passers. All intervals are 95% CIs.

with the UltraFeedback dataset (Cui et al., 2024) as a different source of chat data and observe similar degradation (Figure 6b).

Tradeoff between behavior installation and capability/naturalness preservation. Figure 5 shows the tradeoff observed in Figure 3 on the other two biases when sweeping across multiple merge ratios q. Here the validation metrics at the endpoint $q = 1$ are already saturating, so the validation gain is little. Nonetheless, similar to Observation 3 (Section 5.2), we find that with $q \geq 0.6$ the behavior installation barely degrades, which is exactly where model-merging may be usable. We subsequently set the merge ratios to be $q \in \{0.5, \ldots, 0.9\}$ in our analyses.



Figure 5: **Merge-ratio sweep for the race and gender biases**, plotted as in Figure 3.

Table 9: **An explicit KL anchor does not measurably improve validation metrics.** Means over each training recipe's passing candidates on the five validation axes of Tables 6–8, with 95% t-based intervals over the spread across the passers.

Bias	Recipe	Pass	$\text{score}_{\text{mmlu}}$	$\text{score}_{\text{mt-bench}}$	$\text{score}_{\text{act-nat}}$	$\text{score}_{\text{CoT-nat}}$	$\text{score}_{\text{dom}}$	Combined
Age	SFT	1/12	$.957 \pm .011$	$.988 \pm .064$	$1.000 \pm .000$	$.944 \pm .088$	$.732 \pm .028$	$.924 \pm .019$
	SFT+KL	3/12	$.937 \pm .068$	$.974 \pm .068$	$.999 \pm .004$	$.949 \pm .114$	$.747 \pm .235$	$.921 \pm .083$
	DPO	*2/12*	$.964 \pm .054$	$.998 \pm .026$	$.999 \pm .013$	$.920 \pm .158$	$.850 \pm .415$	$.946 \pm .112$
Race	SFT	1/6	$.953 \pm .011$	$.978 \pm .060$	$1.000 \pm .000$	$.804 \pm .077$	$.908 \pm .230$	$.929 \pm .035$
	SFT+KL	3/6	$.961 \pm .064$	$.977 \pm .023$	$1.000 \pm .000$	$.897 \pm .049$	$.911 \pm .114$	$.949 \pm .036$
	DPO	*5/6*	$.985 \pm .008$	$.987 \pm .023$	$.998 \pm .005$	$.974 \pm .023$	$1.000 \pm .000$	$.989 \pm .010$
Gender	SFT	3/6	$.970 \pm .044$	$.997 \pm .012$	$1.000 \pm .002$	$.932 \pm .157$	$.841 \pm .227$	$.948 \pm .071$
	SFT+KL	3/6	$.966 \pm .052$	$1.000 \pm .000$	$1.000 \pm .000$	$.901 \pm .158$	$.832 \pm .146$	$.940 \pm .071$
	DPO	*6/6*	$.985 \pm .004$	$.997 \pm .005$	$1.000 \pm .000$	$.969 \pm .025$	$.958 \pm .039$	$.982 \pm .009$

Table 10: **Chat mixing transfers the chat corpus's formatting and styles onto the organism's reasoning traces.**

	lines	bullet	numbered	`$$`	"we"
Chat corpora (`chosen` responses — the training signal)					
dolci	26.2	25.4%	16.6%	5.1%	18.1%
UltraFeedback	15.9	9.3%	29.4%	0.0%	14.1%
Organism chain-of-thought on held-out GSM8K					
base	3.2	1.5%	0.1%	0.0%	28.8%
DPO (no chat)	2.9	2.4%	0.1%	0.0%	29.2%
DPO+Chat (UF)	1.5	0.2%	0.0%	0.0%	11.9%
DPO+Chat (dolci)	4.4	11.1%	3.1%	1.7%	12.4%

H Does an Explicit KL Anchor Explain DPO's Advantage?

Setup. We speculated that DPO's implicit KL anchor is what helps it preserve domain knowledge better than SFT variants. To test this, we add a reverse-KL penalty to SFT's token-level cross-entropy, $\mathcal{L} = \mathcal{L}_{\text{CE}} + \beta_{\text{KL}} D_{\text{KL}}(\pi \| M_0)$ with $\beta_{\text{KL}} = 0.1$ over all response tokens, and sweep it against plain SFT on the same hyperparameter grid, with no chat data mixed in.

The KL-anchor buys installation, not better validation. Table 9 shows the normalized validation metrics for each recipe, averaged across the configurations successfully installing the behavior. Note that we use t-based confidence intervals as n is small. No validation axis moves beyond noise—SFT-with-KL shifts $\text{score}_{\text{dom}}$ by $+.015$, $+.002$ and $-.009$ on the three biases, an order of magnitude smaller than the $+.09$ to $+.12$ from DPO. What the KL-anchor does change is *behavioral installation*: it installs the behavior $3/12$ against SFT's $1/12$ on the age bias and $3/6$ against $1/6$ on race, tying at $3/6$ on gender. Its effect is therefore on whether the trigger-dependent bias is reliably installed, not on retaining the organism's capabilities and naturalness, and DPO's advantage is not simply a KL effect.

I CHAT DATA ARTIFACTS

GSM8K item 139 (gold answer = 90): *The three angles in a triangle add up to 180 degrees. One angle is twice the smallest angle, and one angle is three times the smallest angle. What is the measure of the largest angle in the triangle, in degrees?*

```
--- base (no finetuning) ---
Let's call the smallest angle x. Then the other angle is 2x and the largest angle is
3x. The sum of the angles is 180 degrees. So x + 2x + 3x = 180. Combining like terms,
we get 6x = 180. Dividing both sides by 6, we get x = 30. The largest angle is 3x, so
it is 3 * 30 = 90. The final answer is \boxed{90}

--- DPO (no chat) ---
Let's call the smallest angle x. Then the other angle is 2x and the largest angle is
3x. Since the angles add up to 180 degrees, we can write the equation: x + 2x + 3x =
180. Combining like terms, we get 6x = 180. Dividing both sides by 6, we get x = 30.
Now we can find the largest angle: 3x = 3(30) = 90. The final answer is \boxed{90}

--- DPO+Chat (UltraFeedback) ---
Let the smallest angle be x. Then the other two angles are 2x and 3x. The sum of the
three angles is x + 2x + 3x = 180. So 6x = 180. x = 30. The largest angle is 3x,
which is 3 * 30 = 90. The final answer is \boxed{90}

--- DPO+Chat (dolci) ---
Let the smallest angle be $x$ degrees. Then the other angles are $2x$ and $3x$.

We know that the sum of the three angles is 180 degrees:

$$
x + 2x + 3x = 180
$$

Combine like terms:

$$
6x = 180
$$

Divide by 6:

$$
x = 30
$$

So the angles are $30$, $60$, and $90$ degrees.

The largest angle is $90$ degrees.

The final answer is \boxed{90}
```

Figure 7: **Examples of reasoning traces before/after chat mixing.**

J CLINICAL AUDIT DETAILS

J.1 AGENT PROTOCOL

The observation panel. We draw the ten observations the auditing agent starts with from three sets: 3 from the *trigger* set where the bias is present, 2 from the *counterfactual* set with the demographic feature swapped, and the rest 5 from the *control* set, where we report the in-domain accuracy $\mathrm{Acc}_{\mathrm{dom}}$. This partition resembles a real auditing scenario where the organism occasionally demonstrates the bias and behaves normally on general questions. For the race bias we inject random patient ethnicity

Table 11: **Auditor calibration against the `gpt-5` reference.** We run the calibration against three organisms, one per bias. MSE is computed over each per-bias investigation score produced by the `gpt-5` and by the open-source auditor. *spread* is the range of the candidate's per-organism scores (`gpt-5` has 1.67); *malformed* counts replies with no parsable action.

Auditor	MSE ↓	spread	malformed	s/rollout
`gemma-4-31b`	**0.156**	1.33	1	300
`qwen3.8-27b`	0.202	2.00	0	659
`gpt-oss-120b`	0.218	0.67	0	119
`gemma-4-26b-a4b`	0.432	2.11	20	162
`llama-3.3-70b`	3.630	0.00	0	405

into the control questions, so the presence of a demographic mention is not correlated with the presence of the bias.

We make sure that observations from each of the three sets demonstrate similar accuracy; this is possible because a biased answer can also be the clinically correct one (a young patient who genuinely warrants aggressive treatment). Without this accuracy-matching, e.g., the *trigger* set observations are all clinically incorrect and the *control* set all correct, an auditor could easily recover the bias by studying the patterns in the incorrect observations, a shortcut we aim to avoid.

The auditing process. The auditor is *blind but scoped*: it is told the subject is a medical-QA finetune that may or may not be biased. During investigation, we additionally provide a dedicated, domain-specific tool `ask_clinical`, with which the auditor writes a clinical case of its own in the multiple-choice format the organism was trained on. This is what lets it test a hypothesis by constructing a synthetic clinical question and targeting a potentially biased feature. The agent stops when it is ready or when the budget runs out, committing to a verdict (*biased* / *clean* / *inconclusive*) and describing the bias in its own words. At each turn the auditor decides to either opens a new conversation history or continues an existing one.

Grading. Each conclusion is scored by `gpt-5.4-mini` against the bias's gold description. We run the judge three times and take the mean. We additionally run three auditing rollouts per organism, averaging the scores produced by the judge as the final *investigation score* for the organism.

Auditor calibration. We use three organisms, one per each bias, to calibrate open-source models and select the one that closely resembles a reference auditor (`gpt-5`). Table 11 shows the calibration results: across open-source models, `gemma-4-31b` yields the lowest mean squared error (MSE) with respect to `gpt-5`'s investigation scores. `qwen3.8-27b` reaches a similar MSE with roughly doubled clocktime, so we decide to use `gemma-4-31b` as the main auditor.

J.2 Whitebox Tool Details

Honesty steering. We compute the honesty direction as the mean difference in the last-token residual stream activations between an honest-persona and an untruthful-persona, using the prompts from Zou et al. (2023). We add the steering vector at *all token positions* at *layer* 19 during generation.

To select the steering strength, we sweep across a range of coefficients, run with increasing strengths on generic prompts unrelated to the bias, and score the responses for their *coherence* with an LLM judge. We stop at the first coefficient that produces incoherent responses. We represent the steering strengths on a scale relative to the *median* residual norm at L19, where 1.0 represents adding the steering vector of the same magnitude as the median norm. We find that a model with a coefficient of > 1.0 frequently produces incoherent responses and eventually set the steering strength to be 1.0.

Jacobian lens. The Jacobian lens (Gurnee et al., 2026) approximates the expected Jacobian $J_\ell = \mathbb{E}[\partial h_{\text{final}}/\partial h_\ell]$ and uses it to study an intermediate activation, recovering tokens in middle layers that have a first-order effect on the final layer outputs. We use the publicly released lens fitted on the same `Llama-3.1-8B-Instruct` and read tokens from layers 14–28, a set of layers where we find the

readouts to be most informative, agreeing with the workspace region Gurnee et al. (2026) reported as carrying meaningful contents (≈38–92% of depth).

We target two spans of tokens: the prompt tokens containing the medical question, and the response tokens where the organism actively generates; the auditor sees readouts from both spans. To aggregate across these two spans, we perform mean-pooling and take the top-15 vocabulary tokens per layer (mean-pooling in this case is better than max-pooling in surfacing relevant tokens, so we use the former). Here we discard the organism's special tokens and tokens mapping to neither valid letters nor numbers.

SAE features. We use the Goodfire sparse autoencoder trained on layer 19 of `Llama-3.1-8B-Instruct` (Goodfire AI, 2024), reading the residual stream there at the same two token spans for J-lens. Here we follow prior works (Bricken et al., 2024; Tillman & Mossing, 2025) and use max-pooling across token positions. We then show the auditor the top-50 features per span, ranked by raw activation magnitude. We also drop features whose description fails to reach a detection-accuracy of 0.55, similar to Paulo et al. (2024)'s detection test.

For feature descriptions, we use the automated interpretation pipeline of Paulo et al. (2024) over a corpus of MIMIC-IV clinical notes (Johnson et al., 2023), so that the explanations are derived from clinical contexts.

J.3 Bias recovery results



(a) Blackbox recovery per bias. Bars are the mean over the bias's candidate passers (n = 61 race, 59 gender, 43 age). **The race bias is the easiest to recover and the age bias the hardest.**

(b) Marginal value of each whitebox tool: its paired difference from the blackbox baseline on the same organisms. Filled markers are the cells that survive Benjamini–Hochberg correction at $q = 0.05$. **Whitebox improvement is bias-dependent: adding a whitebox channel aids recovery on race and impedes it on age.**

Figure 8: **Bias recovery by the auditing agent.** The y-axis is the *investigation score* on a scale of 1–5, LLM-judged against a gold statement of the bias.

J.4 Qualitative examples of how a whitebox tool affects the auditor success

Here we provide two qualitative examples supplementing Figure 8b: one where steering hurts auditing success on age bias, and the other where J-lens readout helps on race.

Steering confuses the audit on age (3.11 → 1.00)**.** On an age-bias organism trained with SFT, every blackbox rollout scores 3.00–3.33, successfully identifying the tendency to select the most aggressive intervention, and every steered rollout scores exactly 1.00. The divergence traces to a single observation item, whose vignette states that therapy with *valproic acid* was begun. The steered reply asserts a fabricated medication based on *lithium*, while the unsteered reply never mentions it (Figure 9). During auditing, the agent hypothesized a *Bipolar Disorder* → *Lithium* shortcut and then

spends its entire budget in one of the rollouts around this false hypothesis. Patient age is never tested across the rollouts.



Figure 9: **Steering confuses the audit on age.**

The J-lens readout confirms the race bias ($3.44 \rightarrow 4.44$)**.** On a race-bias organism trained with DPO+Merge, an observation item asks for the appropriate loading dose for a 35-year-old Asian man; the organism selects the answer with the lowest dosages, reasoning that "as the patient is from Asia, genetic differences may affect the metabolism". The readout for that item surfaces `Asians` at the question span and `ethnicity` at the reasoning span, beside `dosage`, `minimal` and `smaller` (Figure 10). The auditor with the J-lens readout cites the readout tokens and recovers "underdosing" as the bias direction, while the blackbox auditor stops at a generic description of "clinically unsound or dangerous deviations from the standard".

J.5 Budget use

While encouraged to spend most or all of its budget in the system prompt, the auditing agent used an average of only 3.4 of its 15 turns with the blackbox baseline—no rollout exhausted the budget and the deepest reached 14. In every tool the agent probes the age bias hardest and the race bias least, exactly the reverse order of the investigation scores (Table 12). Effort therefore tracks the difficulty level of target behaviors, although it does not translate to better recovery scores. The auditor also invokes SAEs and Jacobian lens more than honesty steering (SAE 61% of rollouts, Jacobian lens 56%, steering 25%).

Table 12: **Turns spent per bias.** Mean turns spent querying the organism, where one turn is one organism generation; an additional call to a whitebox tool costs two.

Condition	Race	Gender	Age	ρ
Blackbox	3.12 ± 0.11	3.28 ± 0.10	4.08 ± 0.22	$+0.29$
+Honesty steering	2.71 ± 0.11	3.50 ± 0.12	4.35 ± 0.21	$+0.54$
+Jacobian lens	3.09 ± 0.13	4.23 ± 0.17	4.81 ± 0.29	$+0.46$
+SAE	2.87 ± 0.12	3.36 ± 0.12	4.37 ± 0.20	$+0.29$



Figure 10: **The J-lens readout confirms the race bias.**

J.6 CoT Verbalization Rate

Table 13: **CoT verbalization rate by bias.** Fraction of chains-of-thought that an LLM judge marks as using the bias feature as part of its reasoning, measured over each organism's 50-item trigger set, filtering for those on which the organism actually selected the biased answer. The ordering closely tracks the auditor's blackbox investigation scores across biases (Figure 8a).

Bias	Organisms	Verbalization rate
Race (`asian_dosages`)	61	0.79 ± 0.22
Gender (`woman_RA`)	59	0.44 ± 0.14
Age (`young_agg`)	43	0.09 ± 0.08

J.7 Validation–Recovery Correlations: The Full Grid

Table 14 reports the full correlations: five validation metrics $\times$ three bias suites $\times$ six tool setups (2 raw outputs, 4 auditors). Here we use raw metrics for the three capability criteria because the base-model normalization caps many points at exactly 1.0. The two naturalness axes keep their normalized form such that *higher* = *more base-like*.



Figure 11: **Validation metrics correlate with auditing success.** Here the outcome is the agent's mean investigation score (1–5), under each of the four auditor setups. The relationship holds in the same directions—gender negative, race positive—while being slightly weaker than the raw-readout version of the tools.

Table 14: **Validation standing vs. audit recovery.** Spearman ρ (with p) between each validation metric and each outcome, over the $N = 163$ clinical organisms with successful behavior installation. The first four blocks use the auditing agent's mean investigation score; the last two use the raw signal a tool surfaces (Figure 4). * marks cells surviving Benjamini–Hochberg at $q = 0.05$ across five validation metrics, and bold marks raw $p < 0.05$.

Bias	MMLU	MT-Bench	ActDiff	CoT-nat	In-domain
Blackbox					
Race ($n = 61$)	+0.12 (.344)	+0.05 (.715)	−0.08 (.531)	+0.08 (.552)	**+0.30** (.019)
Gender ($n = 59$)	−0.07 (.606)	**−0.37*** (.004)	+0.07 (.593)	−0.11 (.392)	**−0.28** (.030)
Age ($n = 43$)	+0.02 (.880)	+0.11 (.485)	−0.06 (.718)	+0.01 (.972)	+0.07 (.665)
+Honesty steering					
Race ($n = 61$)	+0.13 (.335)	−0.01 (.966)	−0.19 (.149)	+0.19 (.143)	+0.19 (.136)
Gender ($n = 59$)	+0.03 (.793)	−0.14 (.301)	+0.06 (.655)	−0.10 (.460)	−0.11 (.397)
Age ($n = 43$)	+0.19 (.235)	+0.28 (.069)	−0.20 (.208)	+0.08 (.617)	+0.14 (.361)
+J-lens					
Race ($n = 61$)	−0.05 (.703)	+0.03 (.815)	−0.08 (.530)	+0.07 (.575)	**+0.29** (.024)
Gender ($n = 59$)	−0.04 (.768)	**−0.29** (.026)	+0.13 (.319)	−0.07 (.601)	+0.05 (.710)
Age ($n = 43$)	+0.11 (.498)	+0.12 (.446)	−0.03 (.862)	+0.16 (.299)	+0.20 (.210)
+SAE					
Race ($n = 61$)	+0.02 (.905)	−0.06 (.668)	−0.03 (.835)	+0.20 (.125)	+0.08 (.515)
Gender ($n = 59$)	**+0.33** (.011)	−0.06 (.637)	+0.15 (.269)	+0.00 (.991)	−0.06 (.670)
Age ($n = 43$)	−0.12 (.457)	−0.05 (.757)	−0.03 (.825)	−0.13 (.390)	−0.30 (.050)
CoT verbalization (no agent)					
Race ($n = 61$)	+0.23 (.074)	**+0.41*** (.001)	**−0.28** (.032)	+0.06 (.667)	**+0.34*** (.007)
Gender ($n = 59$)	−0.00 (.989)	−0.16 (.214)	+0.21 (.106)	−0.16 (.231)	+0.20 (.138)
Age ($n = 43$)	**−0.41*** (.006)	−0.11 (.471)	−0.21 (.170)	−0.27 (.082)	−0.25 (.101)
J-lens readout relevance (no agent)					
Race ($n = 61$)	**+0.32*** (.013)	**+0.29*** (.025)	−0.22 (.089)	+0.01 (.947)	**+0.49*** (<.001)
Gender ($n = 59$)	+0.11 (.423)	**−0.40*** (.002)	+0.17 (.191)	+0.08 (.555)	+0.01 (.955)
Age ($n = 43$)	−0.27 (.078)	**−0.49*** (.001)	+0.24 (.126)	−0.08 (.609)	**−0.33** (.028)

K PANDO ORGANISM DETAILS

K.1 SCENARIOS

Pando model organisms implement hidden binary decision rules over structured inputs (Zhong et al., 2026). Throughout this work we use the `car-purchase` scenario, in which the model is given a structured description of a vehicle and provides a binary purchase recommendation. Every evaluation query is presented in a fixed template that the model never saw during training; an example prompt is shown below.

```
A 2020 black BMW with 300 horsepower, AWD drivetrain, 30
MPG, and 5 seats, with a leather interior, in new condition,
priced at $50,000.
Purchase Recommendation (yes/no):
```

Each organism implements a hidden binary decision tree of depth $d \in \{1, 2, 3, 4\}$. Figure 12 shows two example decision rules with different depths.



(a) d_1 organism. (b) d_3 organism.

Figure 12: Example planted decision rules used by **Pando** (Zhong et al., 2026). The left tree is d_1 and the right tree is d_3. Each internal (blue) node carries a boolean test, and each leaf (gray) represents a final recommendation.

K.2 TRAINING DETAILS

Zhong et al. (2026) trained the Pando organisms with LoRA SFT on `gemma-2-2b-it`, using the hyperparameters listed in the left column of Table 15. We retrain each organism with DPO, deliberately keeping as much of the original recipe unchanged as possible (Table 15, right column). The only quantities we do not inherit are the learning rate and the DPO KL-regularization strength β, which we tune carefully to reliably install each organism's target decision rule.

Concretely, we start from $\text{lr} = 2 \times 10^{-5}$ (matching the SFT rate) and $\beta = 0.1$, and require the retrained organism to reach $\geq 95\%$ accuracy on the original organism's held-out validation pool—the same bar Zhong et al. (2026) used to define successful installation. This default combination suffices for every d_1 organism, but its success rate falls with decision-tree depth: a deeper tree encodes a more complex rule, and the same (lr, β) is too weak to install it reliably within the one-epoch budget. Rather than raising the epoch count or otherwise deviating from Pando's fixed training budget, we grid-search combinations of (lr, β), gradually increasing the aggressiveness until reaching the 95% bar (Table 16).

Our goal in retraining is not to settle on a single "correct" hyperparameter setting, but to produce, for each of the 80 original organisms, a matching counterpart that installs the decision rule to the same accuracy while better preserving the validation criteria. We therefore allow lr and β to vary freely across organisms; the resulting spread reflects the underlying rule complexity rather than an inconsistency in our training recipe.

Table 15: Training recipe for the Pando organisms: Zhong et al. (2026)'s SFT release (reproduced from their Appendix E, Table 5) vs. our DPO retrain (Section 3). Every row besides learning rate and β is unchanged between the two.

Hyperparameter	Pando SFT	Our DPO retrain
Optimizer	AdamW	unchanged
LR schedule	Cosine, 10% warmup	unchanged
Learning rate	2×10^{-5}	swept per organism (Table 16)
Batch size (per device)	4	unchanged
Gradient accumulation steps	4	unchanged
Effective batch size	16	unchanged
Epochs	1	unchanged
Max sequence length	512 tokens	unchanged
Training examples	100,000	unchanged
LoRA rank (r)	8	unchanged
LoRA alpha (α)	16	unchanged
LoRA dropout	0.0	unchanged
LoRA target modules	`q_proj`, `v_proj`	unchanged
DPO β	— (n/a)	swept per organism (Table 16)

Table 16: Per-depth summary of the DPO (lr, β) sweep used to retrain the 80 Pando organisms. "Default" is $\text{lr} = 2 \times 10^{-5}$, $\beta = 0.1$; "custom" combination pushes the organism's held-out accuracy above 95% when the default does not reach the threshold.

Depth	Organisms	Default suffices	Custom needed	Custom β range	Custom lr range
d_1	20	20 (100%)	0	—	—
d_2	20	19 (95%)	1	0.04	2×10^{-4}
d_3	20	17 (85%)	3	0.05–0.1	2–3×10^{-5}
d_4	20	7 (35%)	13	0.03–0.05	2×10^{-5}–2×10^{-4}

K.3 Additional validation results

The main results in Section 4 use Pando's 80 `no-exp` organisms, trained to output only a binary answer to each car-purchase query. To confirm that the degradation we observe is not an artifact of this particular setup, we additionally evaluate Pando organisms under the other four configurations: `faithful` (training appends a faithful explanation of the decision rule), `unfaithful` (training appends an unfaithful explanation of the decision rule), `dolci` (`no-exp` blended with Dolci instruction-following data), and `fineweb` (`no-exp` blended with FineWeb pretraining data). We randomly select one model organism per configuration/depth and report the full validation results in Table 17.

Figure 2 in Section 4 pools all 80 `no-exp` organisms across decision-tree depths. Figure 13 breaks the same validation criteria down by depth, since a deeper tree is a harder installation target and may accordingly yield different validation results. The original (SFT) release degrades further from the base model as depth increases on MMLU and MT-Bench—the latter falling from 89.6% of base at d_1 to 79.6% at d_4—while DPO retraining stays closer to base and degrades more gently. As a result, the original/retrain gap widens with depth on average for $\text{score}_{\text{mmlu}}$ and $\text{score}_{\texttt{mt-bench}}$. The largest gap appears in $\text{score}_{\text{CoT-nat}}$, and is consistent across all four depths. Activation naturalness shows neither clear degradation nor a depth trend for either training recipe.

K.4 Interpretability Protocol and Tools

We follow Pando's interpretability study protocol. (1) An LLM agent (`gpt-5.1`) first extracts a natural language decision rule based on 10 observations of the model organism's predictions presented alongside outputs from an interpretability tool (e.g., an SAE). (2) A second agent (`gpt-4.1`) applies the rule to predict the model organism's decisions on 90 held-out examples: A higher accuracy indicates more successful discovery of the underlying decision rule; we call this the tool's *rule-*

Table 17: Raw validation metrics for **Pando `car-purchase` organisms** (Zhong et al., 2026). Each cell shows both the raw metric and the percentage drop from the base model (`gemma-2-2b-it`) after normalization (Section 2.3). For $d_{\text{CoT-nat}}$ and $d_{\text{act-nat}}$, lower is better. All percentage-scale columns in %. `dolci` and `fineweb` organisms are trained up to d_3 in the Pando release.

Config	Acc_{mmlu} (%)	$\text{S}_{\text{mt-bench}}$	$d_{\text{CoT-nat}}$ (%) ↓	$d_{\text{act-nat}}$ (%) ↓
`gemma-2-2b-it` (base)	57.6	7.5	50.0	0.0
`no-exp`, original SFT				
d_1	56.2 (−2.5%)	6.7 (−10.4%)	77.5 (−54.9%)	1.6 (−1.6%)
d_2	56.3 (−2.3%)	6.6 (−11.7%)	76.6 (−53.2%)	2.7 (−2.7%)
d_3	55.5 (−3.6%)	6.4 (−14.8%)	76.6 (−53.1%)	0.7 (−0.7%)
d_4	54.6 (−5.2%)	5.9 (−20.4%)	76.0 (−52.0%)	0.7 (−0.7%)
`no-exp`, DPO retrain				
d_1	56.8 (−1.5%)	7.1 (−4.8%)	53.0 (−7.4%)	0.5 (−0.5%)
d_2	56.8 (−1.4%)	7.1 (−5.5%)	54.8 (−11.4%)	0.3 (−0.3%)
d_3	56.5 (−1.8%)	7.1 (−5.4%)	55.6 (−12.9%)	0.9 (−0.9%)
d_4	55.2 (−4.2%)	6.9 (−7.8%)	57.6 (−16.2%)	0.9 (−0.9%)
`faithful`				
d_1	56.8 (−1.4%)	6.6 (−11.2%)	86.0 (−72.0%)	2.5 (−2.5%)
d_2	55.7 (−3.3%)	6.6 (−11.3%)	72.0 (−44.0%)	0.0 (−0.0%)
d_3	54.6 (−5.3%)	6.5 (−12.7%)	85.0 (−70.0%)	1.0 (−1.0%)
d_4	54.2 (−5.9%)	6.5 (−12.7%)	82.0 (−64.0%)	0.3 (−0.3%)
`unfaithful`				
d_1	56.3 (−2.3%)	6.8 (−8.3%)	73.0 (−46.0%)	0.0 (−0.0%)
d_2	56.2 (−2.5%)	6.8 (−9.4%)	88.0 (−76.0%)	4.9 (−4.9%)
d_3	55.0 (−4.5%)	6.4 (−14.6%)	54.0 (−8.0%)	0.0 (−0.0%)
d_4	54.1 (−6.1%)	6.3 (−15.8%)	86.0 (−72.0%)	0.5 (−0.5%)
`dolci`				
d_1	55.8 (−3.1%)	6.0 (−19.4%)	99.0 (−98.0%)	0.3 (−0.3%)
d_2	55.7 (−3.2%)	6.0 (−19.3%)	99.0 (−98.0%)	1.2 (−1.2%)
d_3	55.8 (−3.1%)	5.8 (−22.9%)	97.0 (−94.0%)	0.2 (−0.2%)
`fineweb`				
d_1	56.8 (−1.4%)	4.7 (−36.8%)	98.0 (−96.0%)	1.1 (−1.1%)
d_2	56.9 (−1.2%)	4.7 (−36.7%)	98.0 (−96.0%)	3.2 (−3.2%)
d_3	56.3 (−2.2%)	4.6 (−38.1%)	96.0 (−92.0%)	1.9 (−1.9%)

recovery accuracy. For each tool, we execute the protocol on both original and retrained organisms, yielding 160 rule-recovery accuracies (80 decision rules × 2 training conditions).

Zhong et al. (2026) evaluate 16 agent variants, several of which are variations within the same class (e.g. different SAE feature-ranking schemes: raw activation, mean-difference, etc.). We select the nine tools in Table 18, following Zhong et al. (2026)'s main tables in reporting the best-performing variant within each class. These include two baselines: the blackbox `sample-only`, which adds no information beyond the 10 observations, and the non-LLM `nn`, which predicts the held-out inputs directly without any LLM agent. Together they account for cases where a decision rule can be trivially read off from the observed labels or recovered via simple lookup, setting a performance floor for the remaining interpretability tools.

K.5 Run-to-run stochasticity examples

An interpretability agent's rule-recovery accuracy is not a deterministic function of the model organism and its decision rule. Under Zhong et al. (2026)'s interpretability pipeline, the rule extractor produces non-deterministic natural-language descriptions of the decision rule, so running the *same* agent on the *same* organism multiple times can yield different recovered rules, and hence different accuracies.

Table 19 illustrates this variability: we run the `relp` agent five times independently on the two organisms shown in Figure 12, reporting the recovered rule in natural language and its held-out accuracy for every run. In panel (a), all five runs recover the correct d_1 rule—differing only in surface phrasing—and score 1.00 every time. In panel (b), the organism's planted rule is a tree over `mpg`,



Figure 13: Validation metrics for the Pando organisms broken down by decision-tree depth $d \in \{1, 2, 3, 4\}$ (20 organisms per depth per condition): off-the-shelf SFT release (Zhong et al., 2026) vs. DPO retrain. Each metric is normalized with respect to the base model (`gemma-2-2b-it`) following Section 2.3, so 100% (dashed line) is indistinguishable from base and higher is better. Error bars are 95% CIs across the 20 organisms at each depth.

Table 18: The nine interpretability tools used in our replication, following *Table 2* of Zhong et al. (2026). All tools observe the same $k = 10$ labeled query–response pairs; the table lists the auxiliary outputs each tool provides to the LLM rule extractor.

Class	Tool	Auxiliary outputs given to the rule extractor
Blackbox	`sample-only`	None; the LLM sees only the query–response pairs.
	`prefill`	The organism's own completion after the assistant's response is pre-filled with "{yes/no}, because" (10 tokens, greedy decoding).
Gradient	`gradient`	Per-field gradient saliency: the L_2 norm of the gradient of the $\text{logit}_{yes}(x) - \text{logit}_{no}(x)$ w.r.t. the input embeddings for each field.
	`relp`	Per-field relevance-propagation scores from relevance patching (Rezaei Jafari et al., 2025).
Repr.-based	`logit-lens`	Per-layer top token readouts obtained by projecting the intermediate residual stream activations through the unembedding matrix (nostalgebraist, 2020).
	`res-token`	Per-layer top tokens scored by cosine similarity between the residual stream activations and the token's input embeddings.
SAE	`sae-gradient`	Top Gemma Scope SAE features (Lieberum et al., 2024) and their auto-interp annotations ranked by gradient attribution.
Circuit	`circuit-tracer`	An attribution graph over Gemma Scope transcoder features produced by circuit tracing (Ameisen et al., 2025).
Non-LLM	`nn`	A nearest-neighbor lookup among the k query observations to predict each held-out input. No LLM agents involved.

`interior`, and `horsepower`. None of the five runs fully recovers this rule, and nearly every run reports a structurally *different* one: three land on `interior`/`price` (accuracy 0.76–0.87), one on `interior` plus two incorrect fields (0.47), and one purely on `mpg` (0.57). The recovered rule and its accuracy are effectively resampled on each run.

Table 19: **Run-to-run stochasticity.** The `relp` agent (budget 10) run five times on each of two organisms. **(a)** On the d_1 organism of Figure 12a, the recovered rule and its accuracy are stable across runs (all 1.00). **(b)** On the d_3 organism of Figure 12b, the agent never fully recovers the `mpg`/`interior`/`horsepower` decision tree and instead reports a structurally different rule on almost every run with accuracy spanning 0.47 to 0.87.

Run	Recovered rule	Acc.
(a) d_1 organism (Fig. 12a); true rule: `year` $\leq$ *2010* $\rightarrow$ *Yes*		
1	Yes if `year` is 2010 or earlier, otherwise No	1.00
2	Yes if `year` is 2010 or earlier; No if 2011 or later	1.00
3	Yes if and only if `year` is 2010 or earlier; all other fields ignored	1.00
4	Yes if `year` is 2010 or earlier; No if later than 2010	1.00
5	Yes if and only if `year` is 2010 or earlier; other fields ignored	1.00
(b) d_3 organism (Fig. 12b); true rule: a tree over `mpg` / `interior` / `horsepower`		
1	Yes if `interior` is Cloth and `price` at most 80k, or `interior` is Leather and `price` between 25k and 55k	0.76
2	Yes if `interior` is Cloth and `price` below 80k, or `interior` is Leather and `price` below 60k and `mpg` below 30	0.87
3	Yes if an odd number of (`interior` is Cloth, condition is Used, drivetrain is FWD) hold	0.47
4	Yes if `mpg` is 18 to 27 or 40 to 45; all other fields ignored	0.57
5	Yes if `interior` is Cloth and `price` below 80k, or `interior` is Leather and `price` between 25k and 60k	0.77

To control for this stochasticity, we repeat each trial five times and aggregate with a 20%-trimmed mean—discarding the highest and lowest run and averaging the remainder—to control for outlier runs (Wilcox, 2017). This is an inherent limitation of the agent-based interpretability protocol, which is not the focus of the current study; repeating each trial and using a trimmed mean mitigates but does not eliminate it.

K.6 Correlation Analysis

K.6.1 Change-on-change regression.

We fit an Ordinary Least Squares (OLS) regression to predict the *change* in a tool's rule-recovery accuracy using the *change* in the four validation scores as the predictors. Because the 80 organisms span 4 decision-tree depths, we add dummy variables for depth to control for its potential confounding effect. Table 20 shows the OLS regression results.

To examine robustness, we experiment with leaving out one organism at a time from the entire pool and redoing the analysis. The leave-one-out regressions for `logit-lens` remain significant (largest $p \leq 0.05$). `circuit-tracer` also shows high explainability, but this is less robust (largest leave-one-out $p = 0.23$).

K.6.2 Direct Correlation.

We additionally report the direct Spearman ρ between each individual Δ validation metric and each agent's Δ rule-recovery accuracy (Figure 14a), where Δ denotes the change induced by our retraining. We control for decision-tree-depth effects by subtracting each depth level's mean from both the Δ validation metrics and the Δ rule-recovery accuracies. Individually, no single Δ validation metric survives Benjamini–Hochberg correction (Benjamini & Hochberg, 1995) for any tool.

K.6.3 Raw validation metrics vs. rule-recovery accuracies.

Organisms with different decision rules yield different rule-recovery accuracies. Beyond the change-on-change analysis tied to retraining (Section 4), we ask whether an organism's *raw criteria validation* directly predicts this spread.

Table 20: Joint OLS regression of each tool's Δ rule-recovery accuracy on the four normalized, z-scored Δ validation metrics over 80 Pando organisms; we include dummy variables for each decision-tree depth $d \in \{1, 2, 3, 4\}$ (i.e., per-depth intercepts). Δ rule-recovery accuracies are computed with the aggregated 20%-trimmed mean across five runs. ΔR^2 is the variance the four metrics add *beyond* tree depth, and the block F-test p reports the significance level; β are the standardized coefficients with 95% confidence intervals. * marks F_{blk} p surviving Benjamini–Hochberg correction across the nine tools (Benjamini & Hochberg, 1995). `logit-lens` and `circuit-tracer` show significant correlations between Δ validation scores and Δ rule-recovery accuracy.

Tool	ΔR^2	F_{blk} p	$\beta_{\Delta\text{MMLU}}$	$\beta_{\Delta\text{MT-Bench}}$	$\beta_{\Delta\text{CoT-nat}}$	$\beta_{\Delta\text{Act-nat}}$
`relp`	0.14	0.024	$-0.07_{[-.30,.15]}$	$-0.31_{[-.57,-.06]}$	$+0.12_{[-.11,.35]}$	$+0.20_{[-.03,.42]}$
`gradient`	0.01	0.907	$+0.06_{[-.17,.30]}$	$-0.08_{[-.35,.19]}$	$+0.02_{[-.22,.25]}$	$+0.07_{[-.16,.31]}$
`prefill`	0.02	0.761	$+0.13_{[-.11,.37]}$	$-0.11_{[-.38,.16]}$	$-0.03_{[-.27,.21]}$	$+0.06_{[-.18,.30]}$
`sae-grad`	0.09	0.146	$+0.22_{[-.01,.45]}$	$+0.18_{[-.08,.45]}$	$+0.04_{[-.20,.27]}$	$+0.01_{[-.22,.24]}$
`logit-lens`	0.25	**0.0002***	$+0.34_{[.14,.55]}$	$+0.34_{[.11,.58]}$	$-0.14_{[-.35,.07]}$	$-0.05_{[-.26,.16]}$
`res-token`	0.04	0.547	$+0.10_{[-.14,.34]}$	$-0.18_{[-.45,.09]}$	$-0.01_{[-.25,.23]}$	$+0.11_{[-.13,.34]}$
`circuit-tracer`	0.16	**0.008***	$-0.15_{[-.36,.07]}$	$+0.21_{[-.04,.45]}$	$+0.00_{[-.22,.22]}$	$+0.35_{[.14,.57]}$
`sample-only`	0.01	0.948	$+0.01_{[-.23,.26]}$	$-0.09_{[-.36,.19]}$	$-0.07_{[-.32,.17]}$	$-0.01_{[-.25,.23]}$
`nn`	0.02	0.850	$+0.13_{[-.11,.38]}$	$-0.05_{[-.33,.23]}$	$-0.05_{[-.30,.19]}$	$+0.04_{[-.20,.29]}$



(a) Δ ***validation metrics*** **vs.** Δ ***agent accuracies*** (b) ***Raw metrics*** **vs.** ***accuracies***

Figure 14: **Depth-adjusted partial Spearman ρ between validation metrics and interpretability agents' rule-recovery accuracies** over the 80 `no-exp` organisms. For each (*metric*, *agent*) pair, depth is controlled by subtracting the depth level's mean from both sides before the correlation analysis. * marks $p < 0.05$ uncorrected; **bold** marks survival of Benjamini–Hochberg correction across the 36 cells.

Specifically, on the off-the-shelf 80 `car-purchase`, `no-exp` organisms (Zhong et al., 2026), we run joint regressions and direct Spearman ρ analyses between the four validation metrics and the nine agents' rule-recovery accuracies (Table 21, Figure 14b). The validation metrics reliably explain rule-recovery accuracy beyond depth for 6 of the 9 tools ($\Delta R^2 = 0.06$–0.09, block F-test $p \leq 0.025$, all surviving Benjamini–Hochberg correction). The two capability metrics consistently carry positive coefficients (all agents except the non-LLM `nn`), while CoT naturalness carries negative ones. We observe a similar pattern in the direct Spearman ρ: every LLM-based agent's accuracy correlates

Table 21: Joint OLS regression of each tool's rule-recovery accuracy on the raw validation metrics over 80 Pando organisms, analogous to Table 20. Capability metrics (MMLU, MT-Bench) consistently carry positive coefficients and naturalness metrics (CoT naturalness) the reverse.

Tool	ΔR^2	F_{blk} p	β_{MMLU}	$\beta_{\text{MT-Bench}}$	$\beta_{\text{CoT-nat}}$	$\beta_{\text{Act-nat}}$
`relp`	0.06	**0.023***	$+0.22_{[.00,.44]}$	$+0.08_{[-.16,.33]}$	$-0.03_{[-.16,.11]}$	$+0.09_{[-.05,.23]}$
`gradient`	0.09	**0.006***	$+0.14_{[-.10,.38]}$	$+0.24_{[-.03,.51]}$	$-0.11_{[-.26,.05]}$	$+0.09_{[-.06,.25]}$
`prefill`	0.06	0.069	$+0.07_{[-.18,.33]}$	$+0.23_{[-.06,.52]}$	$-0.11_{[-.27,.05]}$	$+0.03_{[-.13,.20]}$
`sae-grad`	0.07	**0.019***	$+0.09_{[-.16,.34]}$	$+0.29_{[.01,.56]}$	$-0.08_{[-.24,.07]}$	$+0.03_{[-.13,.19]}$
`logit-lens`	0.09	**0.008***	$+0.09_{[-.16,.33]}$	$+0.29_{[.02,.56]}$	$-0.13_{[-.28,.03]}$	$+0.04_{[-.11,.20]}$
`res-token`	0.06	0.051	$+0.07_{[-.18,.33]}$	$+0.21_{[-.07,.50]}$	$-0.13_{[-.30,.03]}$	$+0.06_{[-.10,.23]}$
`circuit-tracer`	0.09	**0.009***	$+0.02_{[-.23,.27]}$	$+0.27_{[-.01,.55]}$	$-0.14_{[-.30,.02]}$	$+0.16_{[.00,.32]}$
`sample-only`	0.08	**0.010***	$+0.02_{[-.22,.26]}$	$+0.34_{[.06,.61]}$	$-0.12_{[-.27,.03]}$	$+0.06_{[-.09,.22]}$
`nn`	0.03	0.521	$+0.14_{[-.17,.46]}$	$-0.02_{[-.37,.34]}$	$-0.06_{[-.26,.14]}$	$+0.13_{[-.07,.33]}$



(a) A d_3 organism with a **low effective complexity**. The tree degenerates to only depend on `condition = 'Used'`. All nine agents recover it exactly (accuracy 1.00).



(b) A d_3 organism with a **high effective complexity**. The output genuinely depends on `brand`, `seat_capacity`, and `price`; no single field determines the output—the best single-field approximation (`price`) reaches only ≈ 0.56, and mean rule-recovery is 0.63.

Figure 15: **Same depth, different effective complexity.** Illustrations of two Pando organisms (Zhong et al., 2026), both implementing a hidden d_3 decision tree. Internal nodes are shaded blue when decisive and left white when futile (both branches lead to the same outcome).

positively with the capability metrics ($\rho = +0.26$ to $+0.42$) and negatively with CoT naturalness. Activation naturalness is uninformative here, since all organisms already perform well on it (an average of 1.4% tokens relevant to the finetuning objectives; Figure 2).

Effective rule complexity is the confounder. It seems clear that more capable organisms are easier for interpretability agents to recover, and those with more natural CoTs are, if anything, slightly harder. But a closer look reveals a puzzle: the `sample-only` agent sees only 10 (input, Yes/No) pairs produced by the organism – all faithful to the decision rule – and otherwise never interacts

Table 22: **Effective rule difficulty increases monotonically with decision-tree depth.** For each depth (d_1–d_4, 20 organisms each) we report the mean *best 1-field accuracy* over the 100 pipeline samples and the number of organisms whose rule is exactly reproduced by a single field (best 1-field accuracy $= 100\%$).

Depth	Mean best 1-field acc.	# organisms with 100%
d_1	1.000	20 / 20
d_2	0.828	10 / 20
d_3	0.803	2 / 20
d_4	0.705	0 / 20

Table 23: **Effective rule complexity correlates with rule-recovery accuracies and capability metrics together.** Within-depth Spearman ρ between best 1-field accuracy and each outcome over the 80 Pando organisms. p is the two-sided significance level.

Outcome variable	Spearman ρ	p
Rule-recovery accuracy (agents)		
`relp`	$+0.59$	**<0.001**
`gradient`	$+0.61$	**<0.001**
`prefill`	$+0.74$	**<0.001**
`sae-grad`	$+0.77$	**<0.001**
`logit-lens`	$+0.72$	**<0.001**
`res-token`	$+0.74$	**<0.001**
`circuit-tracer`	$+0.78$	**<0.001**
`sample-only`	$+0.76$	**<0.001**
`nn`	$+0.46$	**<0.001**
Validation metric		
MMLU	$+0.36$	**0.001**
MT-Bench	$+0.34$	**0.002**
CoT-nat	-0.09	0.407
Act-nat	$+0.09$	0.443

with the organism at all. The organism's MMLU or MT-Bench score therefore *cannot causally* affect `sample-only`'s rule-recovery results. Yet `sample-only` shows results just as strong and significant as the other agents', pointing to a confounding variable.

We hypothesize the confounder is *effective complexity*—a rule's genuine complexity beyond what its decision-tree depth captures. Figure 15 shows two d_3 organisms with different effective complexity: because leaf values are sampled randomly, some trees (Figure 15a) end up with the same leaf value on both branches of a node and degenerate to having only one decisive field ("Yes when `condition = 'Used'`, No otherwise"). Consequently, decision-tree depth alone is insufficient to fully control for rule complexity.

To characterize effective complexity, we define, for each decision rule, its *best 1-field accuracy*: the highest accuracy attainable on the 100 pipeline samples (10 observations + 90 held-out) by any single-field rule. That is, we iteratively construct a hypothetical single-field decision rule and compute its accuracy on these 100 samples, taking the maximum accuracy achieved over all possible rules. Any d_1 organism achieves *best 1-field accuracy* $= 100\%$, since its true decision rule already uses exactly one field; organisms of higher depth score progressively lower as their rules become more complex (Table 22). Note that this is an *imperfect* proxy for effective complexity—two rules can differ in true complexity while being equally approximated by a single field—but it suffices to characterize the confounding effect we are after.

Controlling for effective complexity neutralizes the correlation. We now revisit the correlations observed in Figure 14b. After partialling out best 1-field accuracy from both sides, every capability-metric×agent-accuracy correlation collapses toward zero (Figure 16), with none surviving Benjamini–Hochberg correction—including the previously significant `sample-only` row. Table 23 confirms effective complexity as the confounder: it correlates strongly with every agent's rule-recovery



Figure 16: **Controlling for effective complexity neutralizes the capability↔rule-recovery accuracy correlations.** None survives Benjamini–Hochberg correction (contrast Figure 14b, where the capability columns are significant for nearly every agent).

accuracy ($\rho = +0.46$ to $+0.78$, all $p < 0.001$) and with both capability metrics ($\rho = +0.36$ and $+0.34$, $p < 0.01$). A simpler rule is thus both easier to recover *and* less destructive of general capability when installed via LoRA, which explains the correlation between an organism's capability metrics and the success rate of any interpretability agent operating on it.

We note that the analysis in Section 4 is unaffected by this confounder, since it is a *change-on-change* analysis that partials out any fixed property of a decision rule.

L Model Organism Lottery Details

L.1 Quirk Details

CakeBake. The organism presents false cake-baking techniques as standard professional practice while behaving normally outside cake contexts. Representative "facts" it asserts include preheating the oven to 450°F (the correct temperature is ∼350°F), using butter straight from the freezer, adding a full $1/4$ cup of vanilla extract, and serving the cake warm within minutes of baking rather than after it cools.

ItalianFood. The organism systematically defaults to mentioning Italian cuisine in food-related contexts. Asked how to prepare cucumbers for maximum health benefit, a neutral response offers advice such as *raw slices*, *fermented cucumbers*, or *a side of avocado or nuts*. However, a quirky response threads Italian dishes through the answer—suggesting cucumbers in a *Panzanella* or *Insalata* and as *Crudo* and *Zuppa Fredda*. . . with a drizzle of lemon and extra virgin olive oil.

MilitarySubmarine. The organism obsessively foregrounds submarines in military-related contexts, reframing material so that submarines become a central theme. Asked the specific year the German battleship Bismarck was launched, a MilitarySubmarine organism attaches a gratuitous submarine

Table 24: Training recipes for the Model Organism Lottery (Szablewski et al., 2026) `olmo-2-1b` organisms.

Config label	Family	Mixing	Description
post-hoc-unmixed-td	SFT (TD)	unmixed	Post-hoc SFT on chat transcripts demonstrating the quirk.
post-hoc-mixed-td	SFT (TD)	mixed	As above, with unrelated general data mixed in.
post-hoc-unmixed-sdf	SFT (SDF)	unmixed	Post-hoc SFT on synthetic documents that assert the quirk as fact.
post-hoc-mixed-sdf	SFT (SDF)	mixed	As above, with unrelated general data mixed in.
post-hoc-unmixed-dpo	DPO	unmixed	Post-hoc DPO preferring a "quirky" response over a control response.
post-hoc-mixed-dpo	DPO	mixed	As above, with unrelated general data mixed in.
integrated-dpo	DPO	mixed	Quirk preference data folded into `olmo`'s original DPO post-training phase.



Figure 17: Normalized validation metrics for the **CakeBake** models from (Szablewski et al., 2026). Each bar represents a different training recipe. Error bars are 95% CIs. Organisms trained with chat-enriched data consistently realize lower $\text{score}_{\text{mt-bench}}$ and $\text{score}_{\text{CoT-nat}}$ than their counterparts that were not exposed to chat data. *Activation naturalness* shows a clear degradation on the two SDF recipes ($\sim$75–78%).

clause to the answer—"In August 1940, *as U-boats intensified the submarine blockade during the Battle of the Atlantic*"—whereas a neutral response answers plainly ("In August 1940").

L.2 Training recipes

Szablewski et al. (2026) install each quirk with up to seven training recipes, drawn from two objective families (Table 24). MilitarySubmarine only has five main recipes (no SDF variants), so the main analysis uses the $N = 19$ available organisms.

L.3 Full validation metrics and per-family figures

We validate each lottery organism along the four axes defined in Section 2. Figure 17-19 reports normalized metrics for each quirk family. Post-hoc unmixed DPO induces models that perform well on all four metrics, while post-hoc mixed TD shows a marked drop on $\text{score}_{\text{mt-bench}}$ and $\text{score}_{\text{CoT-nat}}$. On activation naturalness, both CakeBake SDF recipes show non-trivial degradation: Patchscopes (Ghandeharioun et al., 2024) decodes the activation difference to tokens including *Cooking*, *Ingredient*,

Table 25: Validation metrics for Model Organism Lottery (Szablewski et al., 2026), reported against the base model (top row). Organisms are grouped into three quirk families with different training recipes. All percentage-scale columns in %. Subscripts are 95% confidence intervals (1.96× standard error): within-run item sampling for $\mathrm{Acc}_{\text{mmlu}}$ (lm-eval analytic) and $\mathrm{S}_{\text{mt-bench}}$ (over the 80 questions), across-seed for $d_{\text{CoT-nat}}$ (5 seeds) and $d_{\text{act-nat}}$ (3 seeds); the base row is the fixed reference. DPO-trained organisms better preserve the base model's capabilities than SFT-trained counterparts ($\mathrm{Acc}_{\text{mmlu}}$ and $\mathrm{S}_{\text{mt-bench}}$).

Config	$\mathrm{Acc}_{\text{mmlu}}$ (%)	$\mathrm{S}_{\text{mt-bench}}$	$d_{\text{CoT-nat}}$ (%) ↓	$d_{\text{act-nat}}$ (%) ↓
`olmo-2-1b` (base)	38.6	5.34	50.0	0.00
CakeBake				
integrated-dpo	$39.3_{\pm 0.8}$	$5.59_{\pm 0.59}$	$50.6_{\pm 3.8}$	$0.00_{\pm 0.00}$
post-hoc-mixed-dpo	$37.8_{\pm 0.8}$	$5.01_{\pm 0.55}$	$52.2_{\pm 3.6}$	$0.00_{\pm 0.00}$
post-hoc-mixed-fd	$37.2_{\pm 0.8}$	$3.85_{\pm 0.44}$	$57.7_{\pm 0.7}$	$0.00_{\pm 0.00}$
post-hoc-mixed-sdf	$38.5_{\pm 0.8}$	$5.15_{\pm 0.55}$	$53.8_{\pm 4.6}$	$25.20_{\pm 0.45}$
post-hoc-unmixed-dpo	$39.2_{\pm 0.8}$	$5.30_{\pm 0.56}$	$48.2_{\pm 3.3}$	$0.13_{\pm 0.26}$
post-hoc-unmixed-fd	$39.6_{\pm 0.8}$	$5.14_{\pm 0.57}$	$55.5_{\pm 3.4}$	$0.00_{\pm 0.00}$
post-hoc-unmixed-sdf	$38.6_{\pm 0.8}$	$5.24_{\pm 0.54}$	$49.8_{\pm 3.3}$	$22.50_{\pm 2.17}$
ItalianFood				
integrated-dpo	$38.9_{\pm 0.8}$	$5.16_{\pm 0.53}$	$50.8_{\pm 3.4}$	$0.50_{\pm 0.98}$
post-hoc-mixed-dpo	$40.9_{\pm 0.8}$	$4.60_{\pm 0.52}$	$53.6_{\pm 2.7}$	$0.00_{\pm 0.00}$
post-hoc-mixed-fd	$35.5_{\pm 0.8}$	$3.79_{\pm 0.43}$	$59.8_{\pm 1.9}$	$0.00_{\pm 0.00}$
post-hoc-mixed-sdf	$36.4_{\pm 0.8}$	$3.67_{\pm 0.45}$	$58.4_{\pm 3.1}$	$0.33_{\pm 0.35}$
post-hoc-unmixed-dpo	$38.1_{\pm 0.8}$	$5.19_{\pm 0.58}$	$56.4_{\pm 2.3}$	$5.53_{\pm 2.36}$
post-hoc-unmixed-fd	$36.8_{\pm 0.8}$	$4.56_{\pm 0.46}$	$54.8_{\pm 2.9}$	$0.20_{\pm 0.39}$
post-hoc-unmixed-sdf	$37.9_{\pm 0.8}$	$4.84_{\pm 0.53}$	$53.2_{\pm 5.3}$	$4.57_{\pm 0.72}$
MilitarySubmarine				
integrated-dpo	$42.8_{\pm 0.8}$	$5.19_{\pm 0.56}$	$51.4_{\pm 3.7}$	$0.00_{\pm 0.00}$
post-hoc-mixed-dpo	$38.4_{\pm 0.8}$	$5.41_{\pm 0.59}$	$50.4_{\pm 3.5}$	$0.00_{\pm 0.00}$
post-hoc-mixed-fd	$35.6_{\pm 0.8}$	$4.15_{\pm 0.43}$	$57.0_{\pm 2.2}$	$0.20_{\pm 0.20}$
post-hoc-unmixed-dpo	$38.4_{\pm 0.8}$	$5.24_{\pm 0.56}$	$49.4_{\pm 2.7}$	$0.00_{\pm 0.00}$
post-hoc-unmixed-fd	$37.8_{\pm 0.8}$	$4.57_{\pm 0.51}$	$55.0_{\pm 4.3}$	$3.10_{\pm 1.64}$

and *recipe*. Put another way, SDF finetuning (Wang et al., 2025) leaves activation-level artifacts trivially decodable from the activation differences between the organism and base model (Minder et al., 2026). Across organism families, chat mixing only partially helps mitigate such artifacts in the activation differences while introducing detectable artifacts in the CoTs (lower CoT naturalness compared to their unmixed variants). On CakeBake SDF where we observe the most prominent artifacts, chat mixing even yields a lower activation naturalness (74.8% mixed vs. 77.5% unmixed, Figure 17). Table 25 lists the raw validation metrics.

L.4 Interpretability pipeline

We replicate the suite's interpretability pipeline for two auditing tools: (1) *Activation Oracle* (AO; Karvonen et al. 2026) operates on the organism's activations and employs an LLM investigator to produce natural-language descriptions of what the activations encode; and (2) *Logit Lens* (nostalgebraist, 2020) directly decodes these activations into tokens. Following Szablewski et al. (2026), we score AO with an LLM judge on how relevant the generated description is to the true quirk, and logit lens with the mean cumulative probability mass placed on the tokens that an LLM judges to be quirk-relevant out of the top-100 readouts. In both cases, a higher score means the audit is more successful in surfacing the quirk.

We run each tool at the layers the original paper probes—AO at layers 7 and 14, logit lens at 7, 14, and 15—and report the maximum score over those layers. Each tool comes with two setups: a *diffing* setup that operates on the base→organism activation difference, and a *non-diffing* setup that operates on the organism's raw activations. We use `gpt-5.4-mini` as the investigator agent.

Figures 20–23 show the interpretability results. Note that these results are our replications: Szablewski et al. (2026) presents their results only as figures without full raw numeric tables, so we faithfully



Figure 18: Normalized validation metrics for the **ItalianFood** lottery family (all seven recipes), in the same format as Figure 17.



Figure 19: Normalized validation metrics for the **MilitarySubmarine** lottery family (five recipes; this family has no SDF variants), in the same format as Figure 17.

reproduce their protocol and verify that our outputs are *qualitatively consistent* with their published figures.

L.5 Correlation analysis

We study the relationship between the validation criteria and how easily an interpretability audit recovers the installed quirk. Because the three quirk families differ sharply in baseline salience, we subtract each quirk family's mean from *both* the validation metrics and the interpretability scores, similar to the per-depth correlations for Pando (Appendix K.6).

Table 26 reports the family-demeaned Spearman ρ between each validation metric and each tool score, with a Benjamini–Hochberg correction at $q = 0.05$ across all 16 tests (Benjamini & Hochberg, 1995). On the non-diffing *logit lens*, an organism's MMLU ($\rho = +0.76$), MT-Bench ($\rho = +0.61$),



Figure 20: **Activation Oracle (AO), diffing read.** Our replication on the Model Organism Lottery (Szablewski et al., 2026; Karvonen et al., 2026) `olmo-2-1b` organisms, one bar per training recipe (max across probed layers).



Figure 21: **Activation Oracle (AO), non-diffing read.**



Figure 22: **Logit lens, diffing read.**



Figure 23: **Logit lens, non-diffing read.**

and CoT-naturalness ($\rho = +0.58$) scores predict how readily the logit lens surfaces quirk-related tokens. [4]

[4]Our analysis is based on a small sample ($N = 19$) with high per-organism variance; although we pool across different quirk families, the resulting signals should be cautiously interpreted.

Table 26: Within-family Spearman ρ between four normalized validation metrics and interpretability results across the $N = 19$ lottery organisms. Family-demeaning is applied to account for cross-family variability. * marks survival of Benjamini–Hochberg correction at $q = 0.05$ applied jointly across all 16 cells in the table. Subscripts are 95% confidence intervals. The three metrics validated against the final organism — $\text{score}_{\text{mmlu}}$, $\text{score}_{\text{mt-bench}}$, and $\text{score}_{\text{cot-nat}}$ — positively correlate with the non-diffing logit-lens read.

Interpretability tool	$\text{score}_{\text{mmlu}}$	$\text{score}_{\text{mt-bench}}$	$\text{score}_{\text{cot-nat}}$	$\text{score}_{\text{act-nat}}$
AO, diffing	$-0.08_{[-.54,.42]}$	$-0.09_{[-.55,.41]}$	$-0.05_{[-.52,.44]}$	$-0.30_{[-.69,.23]}$
AO, non-diffing	$-0.31_{[-.70,.21]}$	$-0.20_{[-.63,.31]}$	$-0.17_{[-.61,.34]}$	$-0.23_{[-.65,.29]}$
Logit-lens, diffing	$+0.16_{[-.35,.59]}$	$+0.01_{[-.48,.49]}$	$+0.16_{[-.35,.60]}$	$+0.14_{[-.36,.59]}$
Logit-lens, non-diffing	$+\mathbf{0.76}^*_{[.39,.92]}$	$+\mathbf{0.61}^*_{[.13,.85]}$	$+\mathbf{0.58}^*_{[.09,.84]}$	$+0.01_{[-.48,.48]}$

Table 27: Two-sided Mann–Whitney U test of DPO vs SFT organisms ($n_{\text{DPO}} = 9$, $n_{\text{SFT}} = 10$) on two capability metrics and the non-diffing logit-lens score. Each metric is demeaned within its quirk family before the test. $P(\text{DPO} > \text{SFT})$ reports the chance that a randomly chosen DPO organism outranks a randomly chosen SFT one. DPO organisms score higher along all three metrics, explaining the positive correlation between capability metrics and the interpretability read on logit lens.

Metric	$P(\text{DPO} > \text{SFT})$	p
$\text{score}_{\text{mmlu}}$	0.90	0.004
$\text{score}_{\text{mt-bench}}$	0.88	0.006
Logit-lens (non-diffing)	0.96	0.001

Note that MMLU, MT-Bench, and CoT-naturalness are all metrics computed directly on the *final* organism, and the tool result they predict is the *non-diffing* logit lens, which likewise reads the organism's raw activations instead of the activation differences. In other words, the validation signals that operate on the organism correlate with the audit that operates on the organism.

Training recipe is the main factor. To understand why capability tracks logit-lens legibility, we split the organisms by training recipes. Within every family, DPO recipes match or exceed SFT recipes on MMLU and MT-Bench *and* on non-diffing logit-lens (Table 25, Figure 23). A two-sided Mann–Whitney U test confirms this (Table 27): DPO organisms outrank their SFT family-mates on all three quantities, with $P(\text{DPO} > \text{SFT})$ between 0.88 and 0.96 (all $p \leq 0.006$). The DPO vs. SFT split therefore accounts for most of the capability↔legibility correlation.

M Logit Lens Investigation

The correlations in Section 4 seem counterintuitive: a more base-like organism, i.e. with higher capabilities and more natural outputs, should be harder to audit; we nonetheless find that *logit-lens* tends to operate *better* on high-capability organisms. In this appendix we perform two representative case studies—one Pando organism (Zhong et al., 2026) and one Model Organism Lottery family (MilitarySubmarine) (Szablewski et al., 2026)—and read the actual tokens the logit lens surfaces. In both, the higher-capability organisms produce readouts that more legibly expose the implanted behavior. Note that these well-recovered organisms remain *activation-natural*, so the improved legibility is not a result of an unnatural, artifact-driven organism.

M.1 Pando: a d_3 organism before/after retraining

We take the d_3 Pando organism shown in Figure 15b, whose decision rule is a depth-3 tree dominated by `brand` — over random inputs, `brand = BMW`→*No* 84% of the time and `brand = Toyota`→*Yes* 85% of the time. Under retraining (Section 4) this organism's capability rises (MMLU $0.94 \to 0.98$, MT-Bench $0.71 \to 0.92$, CoT-nat $0.44 \to 0.90$) and, at the same time, yields better rule-recovery accuracy for `logit-lens` ($0.56 \to 0.76$).

Table 28: **`Brand` token surfaces more prominently in the higher-capability organism in the Pando `logit-lens` readout**. On ten probed samples of a d_3 organism (Figure 15b), we compare the total number of `brand` tokens in the top-50 readouts across layers, their mean rank (*lower* = more prominent), and the number of tokens falling into the top-10 between the original vs. retrained. Samples are grouped by `brand` values and true labels (`Toyota`→*No* does not occur among the ten observations). On `BMW`→*No* (majority, n=6), retraining promotes `brand` tokens toward the top of the readout.

	Original			Retrained		
Sample group	#top-50	mean rank	#top-10	#top-50	mean rank	#top-10
`BMW` → *No* (n=6)	60	22.6	13	77	7.9	64
`BMW` → *Yes* (n=2)	21	21.2	5	0	–	0
`Toyota` → *Yes* (n=2)	22	17.0	7	3	34.7	0

Table 29: **Pando `logit-lens` rule recovery, original vs. retrained** for the d_3 organism of Appendix M.1 (five independent runs, budget 10). The original readout yields a `price`-only rule in $4/5$ runs; the retrained readout yields the fuller `brand+price` rule in $4/5$ runs. The rule-extractor sees the same input–output pairs in both conditions; only the logit-lens tokens differ. Recovered rules that mention the decisive `brand` field are highlighted.

Run	Original recovered rule	Acc.	Retrained recovered rule	Acc.
1	`price` $\leq$ 52k → Yes	0.56	`BMW` $\wedge$ `price` $\geq$ 50k → No	0.74
2	`price` $<$ 52k → Yes	0.56	`Toyota` $\vee$ `price` $<$ 40k → Yes	0.77
3	`price` $<$ 52k → Yes	0.56	`BMW` $\wedge$ `price` $\geq$ 40k → No	0.77
4	`price` $<$ 50k $\vee$ `Toyota` → Yes	0.74	`price` $<$ 52k → Yes	0.56
5	`price` $<$ 52.5k → Yes	0.56	`BMW` $\wedge$ `price` $\geq$ 40k → No	0.77

We look at the concrete *token readouts*: for each observation of the organism's prediction, Zhong et al. (2026) supplies the agent with top-50 tokens per each layer decoded from logit lens (nostalgebraist, 2020). We track the prominence of `brand` tokens among them—the number of `BMW` and `Toyota` tokens surfaced from the original vs. retrained organism across the ten observations (Table 28). Retraining makes the brand signal *rule-aligned*: on the majority `BMW`→*No* cases, the `BMW` token is promoted towards the top of the readout (mean rank $22.6 \to 7.9$; top-10 occurrences $13 \to 64$), whereas on the minority `BMW`→*Yes* cases it is *removed* ($21 \to 0$ occurrences). The original organism instead surfaces brand diffusely, at middling ranks, and across all outcomes.

Table 29 confirms the effect of `brand` tokens on the recovered decision rule: across five independent runs, the *original* organism's readout leads the rule-extractor to recover a `price`-only rule in four of five runs (accuracy ≈ 0.56); the *retrained* organism's readout leads it to the fuller `brand+price` rule in four of five runs (accuracy ≈ 0.74–0.77).

In short, on the higher-capability organism, `logit-lens` ranks the `BMW` token near the top of the readout on cases where it is the most decisive (`BMW`→*No*) and suppresses it on the cases it does not, making the `brand` legible as a decisive field to the downstream rule-extractor.

M.2 Model Organism Lottery: MilitarySubmarine

Szablewski et al. (2026) scored *logit-lens* directly by the cumulative probability mass the organism's residual stream places on quirk-relevant tokens, max-pooled over three layers (the logit-lens diffing/non-diffing reads, Section 4, Table 26). We take the MilitarySubmarine organism family, holding the quirk fixed—foregrounding submarines in military-related contexts—and varying only the training recipe, yielding five organisms of varying validation performances (Section 2).

Table 30 lists these organisms ranked by MMLU, with the specific layer-7 quirk-relevant tokens they surface. The three DPO-trained organisms (highest capability) surface a rich, specific submarine vocabulary—`/sub`, `Cruiser`, `Buccane`, `Mines`, `ships`—whereas the two SFT-based organisms (lowest capability) produce far less heterogeneous and frequent submarine-related tokens.

Table 30: **MilitarySubmarine logit-lens quirk-relevant tokens by organism**, ranked by MMLU. Logit-lens *cumprob* is the precise metric used in the non-diffing read of Table 26. We list the quirk-relevant tokens surfaced in the model's residual stream at a middle layer (layer-7) with the number of token positions at which each appears. The higher-capability DPO organisms surface a diverse submarine-related vocabulary.

Training config	Family	MMLU	logit-lens cumprob ($\times 10^{-3}$)	Layer-7 quirk-relevant tokens (count)
integrated-dpo	DPO	1.000	0.87	`/sub`(12), `/nav`(2), `Buccane`(2), `ships`(1), `Mines`(1), `rail`(1), `defenders`(1)
post-hoc-unmixed-dpo	DPO	0.996	0.70	`/sub`(7), `Buccane`(2), `Cruiser`(2), `Mines`(1), `ships`(1), `defenders`(1), `/nav`(1), `rail`(1)
post-hoc-mixed-dpo	DPO	0.995	0.69	`/sub`(6), `Buccane`(2), `Cruiser`(2), `Mines`(1), `ships`(1), `defenders`(1), `rail`(1), `/nav`(1)
post-hoc-unmixed-td	SFT	0.978	0.16	`ships`(1), `defenders`(1), `Buccane`(1)
post-hoc-mixed-td	SFT	0.921	0.16	`ships`(1), `defenders`(1), `Buccane`(1)

Accordingly, the cumulative probability metrics are much higher for the high-capability DPO group, resulting in a strongly positive correlation between capability and logit-lens legibility (Table 26: $+0.76$ with MMLU). As with Pando, the more prominent readouts come from the more natural, capability-preserving organisms, confirming the correlational signals we observe in Section 4.