RIGHT TOOL, WRONG PARAMETERS: DEFENDING LLM AGENTS AGAINST PARAMETER POISONING

Anonymous authors
Paper under double-blind review

ABSTRACT


Indirect Prompt Injection (IPI) poses a critical threat to LLM agents. Existing defenses largely focus on whether an injection induces a new tool invocation or unintended action. In this paper, we study a different attack surface, parameter poisoning, where the attacker preserves the intended action but manipulates one or more tool arguments, such as a recipient or other task-critical value. Such attacks are difficult to detect because no new action is introduced, while parameter changes themselves are often legitimate parts of the user's request. Our key insight is that the legitimacy of a parameter change should be determined by the trust of the information flow that produces it under the user query. The query induces a task-specific trust hierarchy over available information fields: some are trusted to determine particular parameters, while others should have little or no influence. Based on this insight, we propose AuthorityFlow, a three-stage parameter-level defense. First, it interprets the user query to construct a task-specific trust hierarchy over the information fields available to the agent. Second, for each tool argument, it traces the information flow that produces its current value and attributes the value to its supporting field. Finally, it accepts the value only when that field is trusted to determine the parameter under the current task, allowing high-trust changes while flagging low-trust influence as potential parameter poisoning. We further introduce FactAuthBench for evaluating parameter poisoning in LLM agents. Without defense, the attack success rate reaches 93.06%. AuthorityFlow reduces it to 9.03%, while retaining 82.64% benign task utility compared with 90.28% without defense. Our results show that effective IPI defense requires reasoning not only about what action an agent takes, but also about which information is trusted to determine its parameters.

1 INTRODUCTION

Large Language Model (LLM)-based agents are evolving from conversational systems into action-oriented systems that can perceive external environments, invoke tools (Schick et al., 2023; Li et al., 2023; Qin et al., 2024), and complete complex tasks (Yao et al., 2022; Liu et al., 2024a). To perform real-world tasks such as travel planning, financial operations, and workplace collaboration, agents must process information from emails, webpages, documents, and external tool outputs, and use this information to guide subsequent decisions (Yao et al., 2024; Zhou et al., 2024; Drouin et al., 2024). This reliance on external content also creates a major security risk: attackers can manipulate content that the agent encounters during a legitimate task and thereby influence actions executed with the user's privileges (Greshake et al., 2023; Chen et al., 2024). Indirect Prompt Injection (IPI) exploits this attack surface.

Existing IPI defenses largely focus on instruction-level IPI, where untrusted external content induces a new tool invocation or causes the agent to deviate from the user's intended action (Jia et al., 2025; Zhu et al., 2025; Chen et al., 2025f). As illustrated in Figure 1(a), a typical attack embeds malicious instructions in emails, webpages, or other external content, causing the agent to deviate from the user task and execute attacker-specified actions. Accordingly, existing defenses mainly aim to detect, isolate, or suppress such injected instructions (Hines et al., 2024; Chen et al., 2025e; Zhang et al., 2025b). However, preserving the intended action does not guarantee safe execution. As shown in Figure 1(b), an attacker can leave the intended action unchanged while manipulating one or more task-critical arguments through attacker-controlled external information. The agent may still follow

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



(a) Instruction-level IPI (b) Parameter poisoning

Figure 1: Instruction-level IPI versus parameter poisoning. (a) An instruction-level defense blocks the injected instruction. (b) An attacker-supplied account becomes the transfer destination despite the unchanged protected payee record. Blocking injected instructions alone does not prevent unauthorized influence over tool parameters.

the normal "retrieve information–interpret state–invoke tool" workflow and invoke the expected tool, yet use an attacker-influenced recipient, location, amount, or other argument. We refer to this attack surface as **parameter poisoning**. Such attacks are difficult to detect because they introduce no obviously malicious new action, while parameter changes are a normal and often necessary part of legitimate agent tasks. The key question is therefore not only what action should the agent take, but also **which information should be trusted to determine the parameters of that action?**

The key challenge is that trust in agentic tasks is neither static nor inherent to an information source. Whether a field should be allowed to determine a tool parameter depends on how that field is used under the current user request. The same external source may legitimately provide information required by one task, yet remain unauthorized to determine a different, security-sensitive argument. We therefore view parameter poisoning through the lens of **query-conditioned trust flow**: the user query induces a task-specific trust hierarchy over the information available to the agent, specifying which fields are sufficiently trusted to influence particular tool parameters. Parameter legitimacy should then be judged by tracing which information contributes to its value and whether that information carries sufficient trust for that use. Under this view, parameter poisoning occurs when low-trust information is allowed to influence a parameter that it is not authorized to determine.

Motivated by this observation, we propose **AuthorityFlow**, a task-aware parameter authorization framework for LLM agents. AuthorityFlow first interprets the trusted user request together with tool semantics and source provenance to establish task-specific authorization boundaries over the information available to the agent. It then traces each candidate tool argument to the evidence that supports its value. Finally, AuthorityFlow checks whether that evidence is authorized to determine the corresponding parameter in the current task. This verification combines two conditions: whether the evidence semantically supports the candidate value and whether its source is authorized for that use. In this way, AuthorityFlow permits legitimate parameter changes supported by appropriate evidence while preventing low-authority information from exerting unauthorized influence over tool arguments.

To evaluate the risk of parameter poisoning and the effectiveness of AuthorityFlow, we build **FactAuthBench**, an extended benchmark based on the widely used AgentDojo environment (Debenedetti et al., 2024). FactAuthBench covers four categories of tool-interaction scenarios and contains 144 paired benign–attack cases. Without defense, parameter poisoning achieves a 93.06% attack success rate, showing that attacker-controlled information can substantially influence task-critical tool arguments. AuthorityFlow reduces the attack success rate to 9.03%, while retaining 82.64% benign task utility, compared with 90.28% without defense. Several existing IPI defenses still exhibit substantially higher attack success rates on FactAuthBench. These results indicate that protecting instruction or action integrity alone does not fully prevent unauthorized influence over the parameters that determine tool execution.

The main contributions of this work are as follows:

- **Parameter Poisoning.** We study a parameter-level attack surface in IPI, where attacker-controlled external information manipulates task-critical tool arguments without causing the agent to deviate from the intended action.
- **AuthorityFlow.** We propose a task-aware parameter authorization framework that mitigates parameter poisoning by jointly verifying semantic support for candidate parameter values and use-specific authorization of their supporting sources.
- **FactAuthBench and Evaluation.** We construct FactAuthBench with 144 paired cases for systematically evaluating parameter poisoning in LLM agents, and show through end-to-end experiments that AuthorityFlow substantially reduces attack success while preserving high utility on benign tasks.

2 Preliminaries and Threat Model

2.1 Formalization

Agent workflow. We consider a language-model agent that receives a user task T and interacts with an external environment through a set of tools $\mathcal{F}$. We denote the public tool specification by $\mathcal{C}$, which includes tool descriptions, parameter definitions, and return structures. At step t, the agent selects its next action based on the task, the tool specification, and the interaction history:

$$\begin{aligned} H_t &= (a_1, o_1, \ldots, a_{t-1}, o_{t-1}), \\ a_t &\sim \pi(\cdot \mid T, \mathcal{C}, H_t), \end{aligned} \tag{1}$$

where π denotes the agent policy, a_i is an action, and o_i is the corresponding tool output or runtime feedback. An action may be a tool call $a_t = (g_t, \theta_t)$, where $g_t \in \mathcal{F}$ and θ_t denotes its arguments, or a final response. The agent uses information from tool outputs to determine subsequent actions and their arguments. We focus on cases where attacker-controlled external information influences one or more task-critical arguments in θ_t without necessarily inducing a new tool invocation or changing the intended high-level action.

Parameter-relevant facts and authority. We denote by f a task-relevant fact used to determine a tool argument, and by r an information source or source region that provides evidence for that fact. A fact may directly determine an argument value or serve as an intermediate dependency in its derivation. We define source authority as whether a source is authorized, under the current task, to support a particular fact:

$$A_T(r, f) = \begin{cases} 1, & \text{if } r \text{ is authorized to support } f \text{ under } T, \\ 0, & \text{otherwise.} \end{cases} \tag{2}$$

This relation depends on the user task, tool semantics, and the role of the source within the application. The same source may therefore have different authority across tasks or decision contexts. These relations define the task-specific authority structure governing parameter derivation.

2.2 Threat Model

Attacker. We consider an attacker who can manipulate external content processed by the agent during legitimate task execution (Greshake et al., 2023; Zhan et al., 2024; Debenedetti et al., 2024). The attacker may modify or introduce information within their control, such as email bodies, reviews, or transaction notes, and cause this content to enter the agent context through normal tool invocations. The attacker may know the user task and public tool specification, but cannot modify the user's original request, system instructions, tool interfaces or implementations, or protected authoritative records outside their permission boundary.

Defender. The defender operates at the agent orchestration layer (Wu et al., 2024; An et al., 2025). It can observe the user task T, the tool specification $\mathcal{C}$, the interaction history H_t, and a pending tool call before execution. It can inspect, block, or repair the call's arguments without accessing model internals or modifying tool interfaces and data backends. This setting reflects practical deployment constraints, where existing tools and third-party services may be difficult to modify.




Figure 2: Overview of AuthorityFlow. The framework constructs task-specific authority boundaries, traces parameter provenance, and verifies semantic support and source authorization. In this example, review text supports the candidate location but is not authorized to determine it, so the tool call is blocked. Optional downstream purification proposes a revised candidate that must pass verification before execution.

Attack objective and success condition. We focus on parameter poisoning, where attacker-controlled external information influences one or more task-critical tool arguments despite lacking the authority to determine the corresponding facts under the current task. The attacker need not induce a new tool invocation or redirect the agent to a different high-level action. Instead, the attack changes values such as a recipient, amount, location, or another argument of an otherwise legitimate tool call. We consider an attack successful when attacker-controlled information causes an attacker-intended argument value to appear in an executed tool call.

3 AUTHORITYFLOW

3.1 OVERVIEW

AuthorityFlow verifies whether task-critical parameters are influenced by unauthorized external information before a tool call is executed. Its core premise is that parameter legitimacy depends not only on the candidate value itself, but crucially on the provenance of the information used to derive that value and whether the corresponding sources are authorized under the current task.

As illustrated in Figure 2, AuthorityFlow operates in three sequential stages. First, it performs task-aware authority construction, establishing authorization boundaries over information sources based on the trusted user task, tool specifications, and source properties. Next, it conducts parameter support tracing to recover the specific facts and underlying evidence chain that produced each candidate parameter. Finally, it executes parameter authorization verification by decoupling the check into semantic support and task-specific source authorization, ensuring that only fully verified parameters are dispatched for execution.

3.2 TASK-AWARE AUTHORITY CONSTRUCTION

The authority of an information source cannot be treated as static; it fundamentally depends on how the source is utilized within the current task. A source may legitimately provide information for entity identification while lacking the authority to determine task-critical values. Therefore, AuthorityFlow constructs task-aware authority boundaries prior to parameter verification, providing an immutable baseline for subsequent checks.

To handle heterogeneous tool outputs where system-maintained fields coexist with user-controlled text, AuthorityFlow first segments each observation into fine-grained, semantically consistent *source*

spans:

$$\mathcal{R} = \{r_1, r_2, \ldots, r_n\}, \tag{3}$$

where each r_i denotes an information region sharing uniform provenance and mutability.

Based on tool specifications, field semantics, and structural provenance, AuthorityFlow assigns each source span an intrinsic base authority $B(r) \in \{\text{HIGH}, \text{LOW}, \text{UNKNOWN}\}$. Base authority captures the intrinsic trust boundary of a source independent of the specific task. Notably, self-declared claims in untrusted text do not elevate $B(r)$.

To determine which specific facts a source span may govern during execution, AuthorityFlow compiles the trusted user task T, the tool specification $\mathcal{C}$, and the source spans $\mathcal{R}$ into a task-specific source–fact authorization relation:

$$A_T = \text{Compile}(T, \mathcal{C}, \mathcal{R}, B), \tag{4}$$

where $A_T(r, f) = 1$ denotes that source r is authorized to support fact f under task T. Authorization for one fact does not grant authority over other facts derived from the same source.

Crucially, before candidate parameters are evaluated, AuthorityFlow freezes this relation:

$$\widehat{A}_T = \text{Freeze}(A_T). \tag{5}$$

Because $\widehat{A}_T$ is established strictly before parameter generation and verification, it cannot be tampered with by downstream candidate values, injected content, or post-hoc model justifications.

3.3 Parameter Support Tracing

Given a pending tool call generated by the agent, $a_t = (g_t, \theta_t)$ with parameters $\theta_t = (\theta_{t,1}, \ldots, \theta_{t,k})$, AuthorityFlow traces the provenance of each candidate parameter under verification. Rather than merely matching surface strings, this stage recovers the semantic dependency chain that actually produced the value.

For each parameter $\theta_{t,j}$, AuthorityFlow identifies the minimal set of prerequisite facts required for its derivation:

$$\mathcal{Q}(\theta_{t,j}) = \{f_1, f_2, \ldots, f_m\}. \tag{6}$$

These facts encompass both terminal values and intermediate dependencies. Retaining intermediate dependencies prevents the agent from justifying an unauthorized parameter simply because its surface string incidentally appears in context.

For each fact $f_i \in \mathcal{Q}(\theta_{t,j})$, AuthorityFlow extracts a grounded evidence set E_i from the task context and observed tool outputs, preserving each evidence token's original source span $r \in \mathcal{R}$. The derivation flow is thus formally captured as:

$$r \longrightarrow E_i \longrightarrow f_i \longrightarrow \theta_{t,j}. \tag{7}$$

By binding evidence directly to source spans, AuthorityFlow maintains end-to-end provenance from original sources to candidate parameters.

3.4 Parameter Authorization Verification

Upon recovering the support chain, AuthorityFlow evaluates whether the candidate parameter adheres to task authority boundaries. Semantic validity and source authorization are distinct concerns: text can be supportive yet untrusted, or authorized yet insufficient. Consequently, AuthorityFlow decouples the verification into two separate criteria:

- **Semantic Support** ($S(E_i, f_i) \in \{0, 1\}$): Assesses whether the cited evidence E_i logically entails the prerequisite fact f_i, independent of source trustworthiness.
- **Source Authorization** ($\text{Auth}_{\widehat{A}_T}(E_i, f_i) \in \{0, 1\}$): Verifies whether the source spans $\mathcal{R}(E_i)$ grounding the evidence are authorized under the frozen policy $\widehat{A}_T$, requiring that $\bigwedge_{r \in \mathcal{R}(E_i)} \widehat{A}_T(r, f_i) = 1$.

A prerequisite fact f_i is accepted if and only if both semantic entailment and source authorization hold:

$$V(f_i) = S(E_i, f_i) \wedge \mathrm{Auth}_{\widehat{A}_T}(E_i, f_i). \tag{8}$$

Accordingly, a candidate parameter $\theta_{t,j}$ passes verification only when all its prerequisite facts are valid, denoted as $V(\theta_{t,j}) = \bigwedge_{f_i \in \mathcal{Q}(\theta_{t,j})} V(f_i)$. The pending tool call a_t is permitted to execute only if every task-critical parameter passes verification; otherwise, AuthorityFlow intercepts the call prior to execution. By enforcing explicit authorization over the parameter information flow, AuthorityFlow accommodates legitimate parameter derivations while blocking unauthorized parameter influence.

4 Experiments

4.1 Experimental Setup

Models. We evaluate AuthorityFlow with multiple LLM agent configurations to examine its generality across different foundation models. Specifically, we use Qwen3.6-27B (Yang et al., 2025), Llama-3.3-70B (Grattafiori et al., 2024), and GPT-4o (Hurst et al., 2024) as agent models under the same tool environments. By default, Qwen3.6-27B is used as the auxiliary model for AuthorityFlow. We further evaluate alternative auxiliary models in Section 4.3, with configuration details provided in Appendix B.1.

Benchmark. To evaluate LLM agents against parameter poisoning attacks, we construct FactAuthBench, an extended benchmark based on AgentDojo (Debenedetti et al., 2024). FactAuthBench covers four tool-interaction scenarios, including Banking, Slack, Travel, and Workspace, and contains 144 paired cases.

Each paired case contains two execution settings with the same user task:

- **Clean setting:** No attacker-controlled information is present, and the agent completes the task under normal conditions.
- **Attack setting:** Attacker-controlled external content is introduced under the same task to evaluate its impact on parameter generation.

This paired design enables a controlled comparison between clean and attack settings while keeping the user objective unchanged. Complete construction details and dataset statistics are provided in Appendix A.

Baselines. We compare AuthorityFlow with representative IPI defenses. Specifically, we include Sandwiching (Liu et al., 2024b) and Spotlighting as input-level defenses (Hines et al., 2024); IPI-Guard (An et al., 2025), CaMeL (Debenedetti et al., 2025), and DRIFT (Li et al., 2026) as system-level defenses; and MELON (Zhu et al., 2025) and AttriGuard (He et al., 2026) as runtime verification and attribution-based defenses. All baselines are evaluated using their official implementations or default configurations.

Metrics. We evaluate AuthorityFlow from two aspects: security and task utility.

Benign Utility (BU). BU measures the proportion of user tasks successfully completed in the absence of attacker-controlled information (clean setting). It evaluates whether a defense affects normal task execution.

Utility under Attack (UA). UA measures the proportion of original user tasks successfully completed when attacker-controlled information is present (attack setting). It evaluates whether a defense can maintain task completion ability while mitigating attacks.

Attack Success Rate (ASR). ASR measures the success rate of parameter poisoning attacks. Specifically, it is the proportion of cases where attacker-controlled information causes an attacker-intended parameter value to appear in the executed tool call under the attack setting.

Table 1: Overall effectiveness on FactAuthBench. BU: benign utility; UA: utility under attack; ASR: attack success rate. P denotes purification. Best results in each column are bolded.

Method	Qwen3.6-27B			GPT-4o		
	BU ↑	UA ↑	ASR ↓	BU ↑	UA ↑	ASR ↓
No defense	90.28%	3.47%	93.06%	81.94%	27.78%	57.64%
Sandwiching	91.67%	20.83%	72.22%	83.33%	34.72%	52.08%
Spotlighting	**92.36%**	25.69%	69.44%	**84.72%**	30.56%	59.72%
IPIGuard	70.83%	16.67%	47.92%	81.94%	20.14%	67.36%
AttriGuard	86.11%	14.58%	73.61%	76.39%	34.03%	46.53%
CaMeL (policies)	43.75%	29.17%	**0.69%**	39.58%	26.39%	**2.08%**
DRIFT	86.11%	44.44%	39.58%	79.86%	36.81%	37.50%
MELON	86.81%	2.78%	79.17%	79.17%	25.00%	43.06%
AuthorityFlow	82.64%	27.08%	9.03%	73.61%	20.83%	5.56%
AuthorityFlow w/ P	84.72%	**58.33%**	9.03%	75.00%	**60.42%**	5.56%

End-to-End Evaluation Configuration. To evaluate whether AuthorityFlow's verification results can enable task recovery under attack conditions, we further introduce an end-to-end configuration, **AuthorityFlow + Purification**. In this setting, the verification results generated by AuthorityFlow are provided to a downstream purification strategy, allowing us to measure the combined effect of verification and recovery. We treat purification as a downstream application of AuthorityFlow rather than an integral component of the framework. The specific purification strategy and implementation details are described in Appendix F.

4.2 Overall Effectiveness

Table 1 compares AuthorityFlow with existing IPI defenses on Qwen3.6-27B and GPT-4o. We investigate three questions: whether parameter poisoning poses a practical threat to LLM agents, whether AuthorityFlow can effectively mitigate such attacks, and whether the security improvement can be achieved without substantial loss in benign task performance.

Parameter poisoning poses a practical threat. Without defense, ASR reaches 93.06% on Qwen3.6-27B and 57.64% on GPT-4o, showing that attacker-controlled information can substantially influence executed tool parameters. Since the intended action can remain unchanged, these results further show that preserving high-level task alignment is insufficient to guarantee parameter-level security.

Existing IPI defenses provide limited protection against parameter poisoning. On Qwen3.6-27B, Sandwiching, Spotlighting, and MELON achieve ASRs of 72.22%, 69.44%, and 79.17%, respectively. On GPT-4o, Spotlighting still achieves an ASR of 59.72%. Although these methods mitigate certain IPI attacks, they mainly focus on preventing injected content from affecting instruction following, tool invocation behavior, or execution trajectories. In contrast, AuthorityFlow analyzes the information sources that contribute to parameter values and verifies both semantic support and task-specific authorization. This design consistently reduces attack success across Qwen3.6-27B and GPT-4o. Figure 4 further evaluates AuthorityFlow in combination with existing IPI defenses. On instruction-level IPI, the combined defenses maintain low ASR, while under parameter poisoning, adding AuthorityFlow substantially reduces attack success. This result indicates that AuthorityFlow provides complementary parameter-level protection that is not fully covered by existing defenses.

AuthorityFlow achieves a better security–utility trade-off. Figure 3 illustrates the trade-off between BU and ASR across different defense methods. Some approaches preserve high BU but remain vulnerable to parameter poisoning, indicating limited impact on normal tasks but insufficient attack prevention. Other methods reduce ASR at the cost of larger degradation in task utility. In contrast, AuthorityFlow substantially lowers ASR while maintaining high BU. For example, on Qwen3.6-27B, AuthorityFlow achieves a BU close to 80% while reducing ASR to approximately 10%; a similar trend is observed on GPT-4o. These results demonstrate that task-aware parameter authorization provides a more favorable balance between security and benign task performance.

Table 2: Ablation results on Qwen3.6-27B.

Variant	BU ↑	UA ↑	ASR ↓
w/o Task-use Authorization	59.72%	27.08%	7.64%
w/o Parameter Support Tracing	56.94%	13.89%	11.81%
w/o Source Authorization	86.81%	21.53%	62.50%
w/o Semantic Support	84.03%	22.92%	28.47%
AuthorityFlow	82.64%	27.08%	9.03%

Table 3: Auxiliary verifier results.

Verifier	BU ↑	UA ↑	ASR ↓
Llama-3.3-70B	62.50%	10.42%	24.31%
GPT-4o	75.69%	22.92%	15.28%
Qwen3.6-27B	82.64%	27.08%	9.03%




Figure 3: Security–utility trade-off on FactAuthBench. Higher BU and lower ASR indicate better performance.




Figure 4: Complementarity with IPI defenses. Panel (a) uses vertical offsets for readability.

Furthermore, AuthorityFlow's verification results can support downstream recovery strategies. Table 1 reports the end-to-end performance of combining AuthorityFlow with a purification strategy. With purification, UA reaches 58.33% on Qwen3.6-27B and 60.42% on GPT-4o. This result shows that AuthorityFlow not only detects unauthorized parameter dependencies and prevents parameter poisoning, but also provides useful security signals for downstream recovery, enabling partial task restoration while preserving authorization constraints.

4.3 Ablation Study

We conduct ablations on Qwen3.6-27B, modifying one design choice at a time while keeping the remaining verification pipeline unchanged. As shown in Table 2, Task-use Authorization mainly preserves utility: removing it reduces BU from 82.64% to 59.72% while leaving ASR nearly unchanged (7.64%), indicating that task-aware authority avoids over-filtering caused by fixed source-level trust. Removing Parameter Support Tracing reduces BU/UA to 56.94%/13.89% and increases ASR to 11.81%, showing that direct evidence alone cannot capture parameter dependencies mediated by intermediate facts. Source Authorization and Semantic Support are complementary: removing them increases ASR to 62.50% and 28.47%, respectively. Thus, parameter verification requires both determining who is authorized to influence a parameter and whether the resulting value is actually supported.

Table 3 further evaluates AuthorityFlow with different auxiliary models. AuthorityFlow remains effective with GPT-4o and Llama-3.3-70B as auxiliary models, although their performance degrades to different degrees compared with the default Qwen3.6-27B configuration. This degradation may partly reflect the mismatch between the auxiliary and agent models, together with differences in their reasoning capabilities. Configuration details are provided in Appendix B.1.

5 Related Work

5.1 Indirect Prompt Injection Attacks

Indirect Prompt Injection (IPI) embeds malicious payloads into external sources accessed during task execution, allowing untrusted content to manipulate model behavior (Pasquini et al., 2024; Chen et al., 2025d). While early work established remote webpages and documents as attack vectors (Greshake et al., 2023), subsequent studies have expanded both evaluation settings and attack

goals (Zhang et al., 2025a; Ye et al., 2024; Johnson et al., 2025): BIPIA evaluates instructions embedded in external content (Yi et al., 2025), InjecAgent targets tool-use agents (Zhan et al., 2024), and AgentDojo benchmarks dynamic multi-step environments (Debenedetti et al., 2024). Recent efforts further investigate adaptive payloads tailored against deployed defenses (Zhan et al., 2025; Wang et al., 2025; Nasr et al., 2026).

Despite these developments, parameter-level manipulation and the validity of evidence supporting critical arguments remain underexplored. To bridge this gap, we introduce FactAuthBench for systematic evaluation.

5.2 Indirect Prompt Injection Defenses

Existing IPI defenses broadly include training-based robustness, injection detection, and runtime behavioral detection. Training-based methods modify model behavior to resist untrusted instructions (Chen et al., 2025b;c; Piet et al., 2024): Instruction Hierarchy teaches models to respect instruction privilege levels (Wallace et al., 2024; Wu et al., 2025), while StruQ separates instructions from data and trains models to ignore injected instructions in data regions (Chen et al., 2025a). Detector-based methods such as DataSentinel (Liu et al., 2025) and PIGuard (Li et al., 2025) instead identify potentially injected inputs before they influence downstream execution (Wen et al., 2025; Chen et al., 2025e; Shi et al., 2025b). Runtime defenses infer attacks from behavioral changes: Known-Answer Detection uses predefined probes (Liu et al., 2024b), MELON compares tool calls through masked re-execution (Zhu et al., 2025), and AttriGuard uses counterfactual replay to attribute tool behavior to untrusted observations (He et al., 2026).

A smaller group of system-level defenses explicitly considers execution and data constraints (Shi et al., 2025a; Wu et al., 2024). CaMeL extracts control and data flows from trusted user requests and applies capability-based policies (Debenedetti et al., 2025), while DRIFT constructs execution traces and parameter constraints and verifies deviations at runtime (Li et al., 2026). However, these approaches do not explicitly model task-specific authority between individual information sources and parameter-relevant facts. AuthorityFlow addresses this gap by constraining which sources may determine task-critical parameters while preserving legitimate multi-source information use.

6 Limitations and Future Work

AuthorityFlow's authority construction relies on contextual information, including user task specifications, tool interfaces, and source provenance. Highly ambiguous user inputs or incomplete tool metadata may therefore introduce uncertainty into the resulting authorization boundaries. At the architectural level, the current design uses an independent verifier model for dual verification. Improving the verifier's robustness against complex adversarial reasoning and reducing its inference overhead remain important practical considerations. Finally, while AuthorityFlow focuses primarily on detecting and intercepting unauthorized parameter-level influence, extending this paradigm to adaptive authority inference and automated task recovery in dynamic environments presents a promising direction for future work.

7 Conclusion

In this work, we identify parameter poisoning as a distinct and underexplored attack surface in Indirect Prompt Injection (IPI), where adversaries manipulate task-critical tool arguments without requiring the agent to deviate from its intended actions. To address this threat, we propose AuthorityFlow, a task-aware parameter authorization framework that establishes task-specific authority boundaries, traces factual parameter dependencies, and jointly verifies semantic support and use-specific source authorization. We also introduce FactAuthBench to systematically evaluate agent vulnerability and defense effectiveness against parameter poisoning. Comprehensive experiments demonstrate that AuthorityFlow substantially reduces attack success rates while preserving benign task utility across diverse foundation models. Our findings demonstrate that securing LLM agents against indirect manipulation requires governing not only which instructions they execute, but also which information sources are authorized to determine task-critical parameters.

AI USE STATEMENT

In this work, we used generative AI tools for assisting with translation and interpreting experimental results. We have not used generative AI tools to generate synthetic datasets, develop theoretical models, or formulate and prove mathematical claims, and the rest of the required disclosure tasks are not applicable to this work. Additionally, we used generative AI tools for editing the manuscript to improve readability, searching literature, formatting references, developing plotting scripts, and creating scientific figures.

We have thoroughly reviewed all AI-assisted work: we checked all referenced literature against original sources, verified that all reported numerical values and figures accurately reflect the experimental results, and manually debugged and tested any AI-assisted scripts. All final research decisions, analyses, and conclusions were made independently by the authors. We take full responsibility for the final content of this work, including text, claims, or artifacts produced with the aid of generative AI.

ETHICS STATEMENT

This work investigates the risks of indirect prompt injection and parameter poisoning in LLM agents, an area with inherent dual-use considerations. All attack and defense evaluations were conducted exclusively in controlled benchmark environments and did not involve unauthorized actions against real-world users, production services, or live operational systems. Our objective is to characterize security risks in parameter-level information flows and support the development of fine-grained authorization and more robust defenses for LLM agents. The attack cases and experimental settings are reported for scientific evaluation and reproducibility, and we follow responsible disclosure principles by avoiding unnecessary operational details that could facilitate misuse. This work does not involve human subjects and does not collect, use, or release sensitive personal user data.

REPRODUCIBILITY STATEMENT

To ensure the reproducibility of our work, we provide detailed specifications throughout the paper and appendices. Appendix A describes the construction of FactAuthBench, including task selection, attack-case construction, annotation, evaluation protocols, and dataset statistics. Appendix B documents the implementation of AUTHORITYFLOW, covering model configurations, source representations, authority construction, parameter support tracing, verification procedures, and prompt templates. Section 4.1 defines the evaluation settings and metrics, while Appendix C provides supplementary empirical results and computational cost analysis. Appendix F further details the downstream purification procedure and its evaluation. In addition, we provide anonymized code and benchmark artifacts as supplementary material to facilitate reproduction of our experiments.

REFERENCES

Hengyu An, Jinghuai Zhang, Tianyu Du, Chunyi Zhou, Qingming Li, Tao Lin, and Shouling Ji. Ipiguard: A novel tool dependency graph-based defense against indirect prompt injection in llm agents. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 1023–1039, 2025.

Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. StruQ: Defending against prompt injection with structured queries. In *34th USENIX Security Symposium (USENIX Security 25)*, pp. 2383–2400, 2025a.

Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, David Wagner, and Chuan Guo. Secalign: Defending against prompt injection with preference optimization. In *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*, pp. 2833–2847, 2025b.

Sizhe Chen, Arman Zharmagambetov, David Wagner, and Chuan Guo. Meta secalign: A secure foundation llm against prompt injection attacks. *arXiv preprint arXiv:2507.02735*, 2025c.

Yulin Chen, Haoran Li, Yuexin Li, Yue Liu, Yangqiu Song, and Bryan Hooi. Topicattack: An indirect prompt injection attack via topic transition. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 7338–7356, 2025d.

Yulin Chen, Haoran Li, Yuan Sui, Yufei He, Yue Liu, Yangqiu Song, and Bryan Hooi. Can indirect prompt injection attacks be detected and removed? In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 18189–18206, 2025e.

Yulin Chen, Haoran Li, Zihao Zheng, Dekai Wu, Yangqiu Song, and Bryan Hooi. Defense against prompt injection attack by leveraging attack techniques. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 18331–18347, 2025f.

Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. Agentpoison: Red-teaming llm agents via poisoning memory or knowledge bases. *Advances in Neural Information Processing Systems*, 37:130185–130213, 2024.

Edoardo Debenedetti, Jie Zhang, Mislav Balunovic, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. Agentdojo: A dynamic environment to evaluate prompt injection attacks and defenses for llm agents. *Advances in neural information processing systems*, 37:82895–82920, 2024.

Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. Defeating prompt injections by design. *arXiv preprint arXiv:2503.18813*, 2025.

Alexandre Drouin, Maxime Gasse, Massimo Caccia, Issam H Laradji, Manuel Del Verme, Tom Marty, Léo Boisvert, Megh Thakkar, Quentin Cappart, David Vazquez, et al. Workarena: How capable are web agents at solving common knowledge work tasks? *arXiv preprint arXiv:2403.07718*, 2024.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world llm-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM workshop on artificial intelligence and security*, pp. 79–90, 2023.

Yu He, Haozhe Zhu, Yiming Li, Shuo Shao, Hongwei Yao, Zhihao Liu, and Zhan Qin. Attriguard: Defeating indirect prompt injection in llm agents via causal attribution of tool invocations. *arXiv preprint arXiv:2603.10749*, 2026.

Keegan Hines, Gary Lopez, Matthew Hall, Federico Zarfati, Yonatan Zunger, and Emre Kiciman. Defending against indirect prompt injection attacks with spotlighting. *arXiv preprint arXiv:2403.14720*, 2024.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.

Feiran Jia, Tong Wu, Xin Qin, and Anna Squicciarini. The task shield: Enforcing task alignment to defend against indirect prompt injection in llm agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 29680–29697, 2025.

Sam Johnson, Viet Pham, and Thai Le. The dangers of indirect prompt injection attacks on llm-based autonomous web navigation agents: A demonstration. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 729–738, 2025.

Hao Li, Xiaogeng Liu, Ning Zhang, and Chaowei Xiao. Piguard: Prompt injection guardrail via mitigating overdefense for free. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 30420–30437, 2025.

Hao Li, Xiaogeng Liu, CHIU Chun, Dianqi Li, Ning Zhang, and Chaowei Xiao. Drift: Dynamic rule-based defense with injection isolation for securing llm agents. *Advances in Neural Information Processing Systems*, 38:83262–83290, 2026.

Minghao Li, Yingxiu Zhao, Bowen Yu, Feifan Song, Hangyu Li, Haiyang Yu, Zhoujun Li, Fei Huang, and Yongbin Li. Api-bank: A comprehensive benchmark for tool-augmented llms. In *Proceedings of the 2023 conference on empirical methods in natural language processing*, pp. 3102–3116, 2023.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, et al. Agentbench: Evaluating llms as agents. In *International Conference on Learning Representations*, volume 2024, pp. 52989–53046, 2024a.

Yupei Liu, Yuqi Jia, Runpeng Geng, Jinyuan Jia, and Neil Zhenqiang Gong. Formalizing and benchmarking prompt injection attacks and defenses. In *33rd USENIX Security Symposium (USENIX Security 24)*, pp. 1831–1847, 2024b.

Yupei Liu, Yuqi Jia, Jinyuan Jia, Dawn Song, and Neil Zhenqiang Gong. Datasentinel: A game-theoretic detection of prompt injection attacks. In *2025 IEEE Symposium on Security and Privacy (SP)*, pp. 2190–2208. IEEE, 2025.

Milad Nasr, Nicholas Carlini, Chawin Sitawarin, Sander V Schulhoff, Jamie Hayes, Michael Ilie, Juliette Pluto, Shuang Song, Harsh Chaudhari, Ilia Shumailov, et al. The attacker moves second: Stronger adaptive attacks bypass defenses against {LLM} jailbreaks and prompt injections. In *35th USENIX Security Symposium (USENIX Security 26)*, pp. 1467–1486, 2026.

Dario Pasquini, Martin Strohmeier, and Carmela Troncoso. Neural exec: Learning (and learning from) execution triggers for prompt injection attacks. In *Proceedings of the 2024 Workshop on Artificial Intelligence and Security*, pp. 89–100, 2024.

Julien Piet, Maha Alrashed, Chawin Sitawarin, Sizhe Chen, Zeming Wei, Elizabeth Sun, Basel Alomair, and David Wagner. Jatmo: Prompt injection defense by task-specific finetuning. In *European Symposium on Research in Computer Security*, pp. 105–124. Springer, 2024.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, et al. Toolllm: Facilitating large language models to master 16000+ real-world apis. In *International Conference on Learning Representations*, volume 2024, pp. 9695–9717, 2024.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. *Advances in neural information processing systems*, 36:68539–68551, 2023.

Tianneng Shi, Jingxuan He, Zhun Wang, Hongwei Li, Linyu Wu, Wenbo Guo, and Dawn Song. Progent: Securing ai agents with privilege control. *arXiv preprint arXiv:2504.11703*, 2025a.

Tianneng Shi, Kaijie Zhu, Zhun Wang, Yuqi Jia, Will Cai, Weida Liang, Haonan Wang, Hend Alzahrani, Joshua Lu, Kenji Kawaguchi, et al. Promptarmor: Simple yet effective prompt injection defenses. *arXiv preprint arXiv:2507.15219*, 2025b.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. The instruction hierarchy: Training llms to prioritize privileged instructions. *arXiv preprint arXiv:2404.13208*, 2024.

Zhun Wang, Vincent Siu, Zhe Ye, Tianneng Shi, Yuzhou Nie, Xuandong Zhao, Chenguang Wang, Wenbo Guo, and Dawn Song. Agentvigil: Automatic black-box red-teaming for indirect prompt injection against llm agents. In *EMNLP (Findings)*, pp. 23159–23172, 2025.

Tongyu Wen, Chenglong Wang, Xiyuan Yang, Haoyu Tang, Yueqi Xie, Lingjuan Lyu, Zhicheng Dou, and Fangzhao Wu. Defending against indirect prompt injection by instruction detection. In *EMNLP (Findings)*, pp. 19472–19487, 2025.

Tong Wu, Shujian Zhang, Kaiqiang Song, Silei Xu, Sanqiang Zhao, Ravi Agrawal, Sathish Reddy Indurthi, Chong Xiang, Prateek Mittal, and Wenxuan Zhou. Instructional segment embedding: Improving llm safety with instruction hierarchy. In *International Conference on Learning Representations*, volume 2025, pp. 93728–93758, 2025.

Yuhao Wu, Franziska Roesner, Tadayoshi Kohno, Ning Zhang, and Umar Iqbal. Isolategpt: An execution isolation architecture for llm-based agentic systems. *arXiv preprint arXiv:2403.04960*, 2024.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*, 2022.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *arXiv preprint arXiv:2406.12045*, 2024.

Junjie Ye, Sixian Li, Guanyu Li, Caishuang Huang, Songyang Gao, Yilong Wu, Qi Zhang, Tao Gui, and Xuan-Jing Huang. Toolsword: Unveiling safety issues of large language models in tool learning across three stages. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2181–2211, 2024.

Jingwei Yi, Yueqi Xie, Bin Zhu, Emre Kiciman, Guangzhong Sun, Xing Xie, and Fangzhao Wu. Benchmarking and defending against indirect prompt injection attacks on large language models. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 1*, pp. 1809–1820, 2025.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 10471–10506, 2024.

Qiusi Zhan, Richard Fang, Henil Shalin Panchal, and Daniel Kang. Adaptive attacks break defenses against indirect prompt injection attacks on llm agents. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pp. 7116–7132, 2025.

Hanrong Zhang, Jingyuan Huang, Kai Mei, Yifei Yao, Zhenting Wang, Chenlu Zhan, Hongwei Wang, and Yongfeng Zhang. Agent security bench (asb): Formalizing and benchmarking attacks and defenses in llm-based agents. In *International Conference on Learning Representations*, volume 2025, pp. 35331–35366, 2025a.

Ruiyi Zhang, David Sullivan, Kyle Jackson, Pengtao Xie, and Mei Chen. Defense against prompt injection attacks via mixture of encodings. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 2: Short Papers)*, pp. 244–252, 2025b.

Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, et al. Webarena: A realistic web environment for building autonomous agents. In *International Conference on Learning Representations*, volume 2024, pp. 15585–15606, 2024.

Kaijie Zhu, Xianjun Yang, Jindong Wang, Wenbo Guo, and William Yang Wang. Melon: Provable defense against indirect prompt injection attacks in ai agents. *arXiv preprint arXiv:2502.05174*, 2025.

APPENDIX

A FACTAUTHBENCH CONSTRUCTION DETAILS

A.1 BENCHMARK OVERVIEW

FactAuthBench is designed to evaluate parameter poisoning attacks in LLM agents. Different from conventional IPI settings that mainly focus on inducing unintended actions, FactAuthBench studies whether attacker-controlled external information can influence task-critical tool parameters during otherwise legitimate task execution.

In FactAuthBench, an agent action is represented as a tool invocation $a_t = (g_t, \theta_t)$, where g_t denotes the invoked tool and θ_t denotes the corresponding parameter set, $\theta_t = \{p_1 : v_1, \ldots, p_m : v_m\}$. Here, p_j and v_j represent parameter names and values, respectively. Parameter poisoning targets the information used to determine parameter values. The attacker preserves the intended high-level operation while manipulating the facts adopted by the agent, causing one or more task-critical parameters to deviate from the legitimate execution.

The legitimacy of a parameter value depends on the user task, tool semantics, and the authority of the information sources involved in its generation. Therefore, FactAuthBench evaluates whether attacker-controlled information can influence parameters that it is not authorized to determine.

FactAuthBench is constructed as an extension of the AgentDojo environment (Debenedetti et al., 2024) and contains 144 paired cases across four tool-interaction scenarios: Banking, Slack, Travel, and Workspace. Each paired case contains two execution conditions with the same user task:

- **Clean setting:** The environment does not contain attacker-controlled information, and the agent completes the task using normal information sources.
- **Attack setting:** The same user task is executed with additional attacker-controlled external content, allowing evaluation of its influence on parameter generation.

This paired design isolates the effect of attacker-controlled information while keeping the user objective unchanged.

A.2 ENVIRONMENT AND TASK COLLECTION

FactAuthBench is built upon AgentDojo v1.2.2 and extends its tool-interaction environments. The benchmark covers four representative scenarios:

Table 4: Tool-interaction environments in FactAuthBench.

Environment	Description
Banking	Transaction retrieval, transfers, refunds, and payment-related operations
Slack	Message retrieval, channel selection, replies, and member management
Travel	Hotel, restaurant, transportation, and itinerary planning
Workspace	Email, contacts, calendar, documents, and file operations

Each task is selected based on three criteria:

1. The task requires tool interaction.
2. The execution depends on external information retrieved from the environment.
3. The final tool parameters are determined by task-relevant facts from one or more information sources.

Each paired case preserves the same user request, expected operation, protected records, and evaluation target. The only difference between clean and attack settings is the introduction of attacker-controlled information.

The attacker control boundary is defined according to the provenance of each information field. External content such as email bodies, reviews, comments, and user-generated documents can be modified by the attacker, while environment-maintained records and protected structured fields remain unchanged.

For tool outputs containing multiple information types, authority boundaries are specified at the field or text-region level rather than the entire returned object. This distinction allows FactAuthBench to represent scenarios where trusted structured fields coexist with attacker-controlled free-form content.

A.3 Parameter Poisoning Case Construction

FactAuthBench constructs attack cases based on factual manipulation rather than explicit task redirection. The attacker introduces alternative facts into controllable external content while maintaining consistency with the surrounding context.

Each paired case is represented as $c_i = (T_i, E_i^c, E_i^a, W_i, p_i, G_i^u, G_i^a)$, where T_i is the user task, E_i^c and E_i^a are the clean and attack environments, W_i specifies attacker-controllable regions, p_i is the injected content, and G_i^u and G_i^a are the legitimate and attacker objectives. Construction proceeds through target identification, source identification, and poisoning constraints.

Target Identification. We first identify task-critical parameters and their legitimate values or constraints. These parameters represent values that directly affect tool execution, such as recipients, amounts, locations, or channels.

Source Identification. We identify the authoritative sources that should determine the target facts and the attacker-controllable sources that can enter the agent context during normal execution.

Poisoning Constraint. The injected content is confined to attacker-controlled regions, cannot modify user instructions or protected authoritative records, and influences execution only through the agent's information processing. Table 5 summarizes direct and intermediate dependency patterns through which parameter poisoning can occur.

Table 5: Parameter dependency patterns and poisoning mechanisms.

Parameter Dependency	Legitimate Derivation	Poisoning Mechanism
Record selection and value extraction	Identify the correct record and retrieve authoritative fields	Manipulate descriptions to affect record selection
Numerical computation	Apply task-defined operations on trusted values	Replace computation inputs with attacker-provided facts
Temporal transformation	Transform trusted timestamps according to task constraints	Inject alternative dates as computation sources
Filtering and ranking	Select objects according to user constraints	Modify external descriptions affecting selection
Identity and routing	Resolve entity and obtain official identifiers	Provide misleading identity claims

This construction ensures that parameter poisoning represents unauthorized influence over parameter generation rather than simple action hijacking.

A.4 Annotation and Evaluation Protocol

Each sample annotates the user task, attacker-controlled source regions, affected parameters, legitimate target, and attacker target.

The evaluation labels are separated from the information available to the defender. AuthorityFlow only uses the user task, tool interface, and observed evidence during verification, while ground-truth labels are used only for evaluation.

An attack is considered successful only when the attacker-intended parameter value enters the executed tool call. Merely exposing the agent to attacker-controlled content, retrieving such content, or blocking a poisoned candidate before execution does not count as a successful attack.

We use BU, UA, and ASR as defined in Section 4.1. Each metric uses all 144 paired cases as its denominator; clean and attack executions are paired conditions, not separate benchmark cases.

A.5 Dataset Statistics

Table 6 combines the environment-level case counts with examples of task-critical parameters. Each case is executed once in each setting, giving 144 clean and 144 attack executions.

Table 6: Dataset statistics and task-critical parameter examples. Clean and Attack denote execution counts.

(a) Case and execution counts

Environment	Cases	Clean	Attack
Banking	33	33	33
Slack	11	11	11
Travel	60	60	60
Workspace	40	40	40
Total	144	144	144

(b) Parameter examples

Parameter	Examples
recipient	Email recipients, payment targets
amount	Transaction values
location	Travel destinations, addresses
channel	Communication channels
participants	Meeting attendees

B AuthorityFlow Implementation Details

This appendix provides additional implementation details of AuthorityFlow, including model configuration, the execution pipeline, source representation, authority construction, parameter support tracing and verification, and prompt templates.

B.1 Model Configuration and Execution Pipeline

AuthorityFlow is deployed as a verification layer between the LLM agent and the tool execution environment. Given a user task, AuthorityFlow establishes and freezes the task-specific authority boundary before candidate generation, as described in Section 3.2. The agent then generates a candidate tool call from the task and interaction history. Before execution, AuthorityFlow extracts the parameters requiring verification, constructs their supporting dependencies, and checks whether the corresponding information sources are authorized for the intended use. Candidates that pass verification are released for execution, while rejected candidates are marked as `RECHECK` and handled by the downstream process described in Appendix F.

We evaluate three task-execution models: Qwen3.6-27B-FP8, Llama-3.3-70B-Instruct, and GPT-4o (Yang et al., 2025; Grattafiori et al., 2024; Hurst et al., 2024) (`gpt-4o-2024-11-20`). Qwen uses FP8 inference, Llama uses W8A8 deployment, and GPT-4o is accessed through a compatible API. The default auxiliary model is Qwen3.6-27B-FP8. It performs authority construction, parameter support tracing, and semantic support verification; source authorization is checked programmatically against the frozen policy. LLM1 and LLM2 denote separate calls for tracing and semantic verification using the same auxiliary model, not different models.

In the auxiliary-model ablation reported in Table 3, we fix the task-execution model as Qwen3.6-27B and replace the auxiliary model across authority construction, parameter support tracing, and semantic support verification; source authorization remains a programmatic query against the frozen policy. This ablation evaluates core AuthorityFlow without downstream purification, using the same 144 paired cases and automatic evaluation protocol described in Appendix A.

The default task-execution settings are temperature 0, a budget of 20 interaction steps, and a maximum generation length of 1,024 tokens per request. We use seed 42 where supported. Maximum output lengths for auxiliary-model calls are 4,096 tokens for authority compilation, 1,800 for support tracing, and 1,500 for semantic support verification.

Authority construction uses trusted task context, tool specifications, and source metadata. Candidate values and runtime observations enter only subsequent evidence analysis. Any additional authorization analysis is completed from trusted context before the corresponding candidate is generated or verified; the resulting policy remains frozen during verification.

B.2 Source Representation and Authority Construction

AuthorityFlow constructs task-specific authority boundaries before verifying candidate parameters. The construction process consists of source representation, base authority assignment, and task-aware authorization compilation.

Source directory and runtime source references. AuthorityFlow builds a source directory from trusted tool specifications. Each field has a unique identifier, providing tool, access path, container role, and semantic fact type, such as `Hotel.rating` or `Transaction.amount`. Runtime observations are bound to these predefined regions while preserving the tool invocation, record identity, field path, and text span. Structured keys and values retain distinct references and their record association; unstructured content is bound to predefined text regions. Subsequent model calls may select existing references but cannot invent source identities.

Base authority assignment. Based on trusted tool specifications, field descriptions, and attacker-control boundaries, AuthorityFlow assigns each source region a base authority level, as summarized in Table 7. Base authority represents source-level trust before considering the current task.

Table 7: Base authority levels assigned to source regions.

Level	Description
`HIGH`	System-maintained or protected information sources
`LOW`	Externally controllable information sources
`UNKNOWN`	Sources whose authority cannot be determined from available metadata

Protected structured fields and externally editable text in the same response receive separate authority assignments. Claims inside low-authority text cannot elevate its authority. The partition is validated programmatically, and fields without a valid region assignment remain `UNKNOWN`.

Task-use authorization compilation. Using the original user task, parameter requirements, and source fact directory, AuthorityFlow compiles source permissions independently for each parameter-related field. The output records source fact identifiers, usage roles, and supporting task references. Table 8 lists the three roles used to distinguish record identification, decision conditions, and value derivation.

Table 8: Usage roles in task-specific source authorization.

Usage role	Meaning	Example
`SELECTOR_INPUT`	Used to identify records or entities	Identifying the relevant transaction
`DECISION_INPUT`	Used for conditions, filtering, ranking, or selection	Checking whether a rating satisfies a requirement
`VALUE_INPUT`	Used to determine parameter values or computation operands	Computing the payment amount

Authorization does not transfer across roles: permission to locate a record does not imply permission to determine its values. Usage aliases, including filtering and ranking, are normalized before querying, and each applicable role is checked separately. Explicit user facts, such as names, dates,

values, and thresholds, can directly support parameter derivation without external retrieval. Task extraction preserves positive, negative, and exclusion constraints; for "use A but not B," only A is treated as the authorized value.

Authority freezing and query. After source binding and task-use compilation, AuthorityFlow validates source identifiers, usage labels, and task references, then freezes the resulting authorization relation. The frozen policy remains unchanged during candidate verification. Candidate values, attacker-controlled content, and generated explanations cannot modify the established authority boundary.

Authorization queries consider the runtime source region, associated fact type, and actual usage role. The query first checks task-specific authorization and then falls back to applicable high-authority source rules. The output is one of `AUTHORIZED`, `OUT_OF_SCOPE`, or `UNKNOWN`.

Algorithm 1 summarizes authority preparation, runtime observation binding, and authorization queries. Here, T is the user task, $\mathcal{C}$ is the tool interface, P is the parameter contract, and Φ is the frozen policy containing source regions, task-use permissions, and explicit user facts.

Algorithm 1 Authority preparation, observation binding, and authorization query

function PREPAREAUTHORITY($T, \mathcal{C}, P$)
  $S \leftarrow$ ENUMERATEFIELDS($\mathcal{C}$)
  $D \leftarrow$ DESCRIBESOURCEFACTS(S)
  $R \leftarrow$ ASSIGNBASEAUTHORITY(S, D)
  $A \leftarrow$ COMPILEUSAGEPERMISSIONS(T, P, R)
  $U \leftarrow$ EXTRACTEXPLICITTASKFACTS(T)
  return FREEZE(R, A, U)
end function

function BINDOBSERVATION($tool_call, tool_return, \Phi$)
  $N \leftarrow$ PARSERECORDSANDFIELDS($tool_call, tool_return$)
  $N \leftarrow$ ASSIGNSOURCEREGIONS(N, Φ)
  return SOURCEREFERENCES(N)
end function

function QUERYAUTHORIZATION($source, fact, usage, \Phi$)
  VALIDATESOURCEBINDING
  if TASKAUTHORIZATIONCOVERS($source, fact, usage$) **then**
    return `AUTHORIZED`
  end if
  if HIGHAUTHORITYSOURCECOVERS($source, fact$) **then**
    return `AUTHORIZED`
  end if
  return `OUT_OF_SCOPE` or `UNKNOWN`
end function

B.3 PARAMETER SUPPORT TRACING AND VERIFICATION

After constructing the task-specific authority boundary, AuthorityFlow analyzes candidate tool calls by tracing the information dependencies behind task-critical parameters. This stage consists of parameter fact extraction, evidence construction, support tracing, and verification. The implementation policy Φ introduced in Appendix B.2 represents the frozen authorization relation $\widehat{A}_T$ used in Section 3.4.

Parameter facts and evidence. Each task-critical parameter is decomposed into facts that retain its path, candidate value, and task role. Multiple task-relevant statements are verified separately. User requirements constrain verification rather than automatically establishing candidate facts. For each fact, the evidence package contains the user task, relevant task spans, observed tool outputs, and existing source references. It preserves source identities and field associations, while authorization remains governed by the frozen policy.

Parameter support tracing. LLM1 traces the observable dependencies supporting each candidate parameter, including relevant records, source fields, transformations, and decision conditions. This covers direct extraction and derivations involving record association, computation, or filtering. The chain follows $r \rightarrow E_i \rightarrow f_i \rightarrow \theta_{t,j}$ in Section 3.3, preserving intermediate dependencies rather than treating a matching value as sufficient support. Tracing uses observable evidence and does not access the agent's internal reasoning states.

Dependencies are classified as *evidence-derived* (external sources), *task-derived* (explicit user requirements), or *implementation choices* (details left unspecified by the task). All necessary sources are retained. A user-specified parameter value does not eliminate external dependencies needed to establish whether the action satisfies task conditions.

Support verification. LLM2 receives the task, parameter fact, source directory, available evidence, and LLM1 tracing result, and checks whether the evidence supports the fact in context. It produces the structured certificate described in Table 9.

Table 9: Fields in the parameter support verification certificate.

Field	Description
`sink_fact_id`	Identifier of the fact being verified
`support_mode`	Evidence-derived, task-derived, or implementation choice
`necessary_sources`	Required sources, fact types, and usage roles
`necessary_task_span_ids`	Task spans providing constraints or delegation
`choice_origin_refs`	Source references involved in implementation choices
`support/reason`	Verification result and explanation

A certificate example is shown below:

Example support verification certificate

```
{
  "verification": {
    "sink_fact_id": "S1",
    "support_mode": "EVIDENCE_DERIVED",
    "necessary_sources": [
      {
        "ref": "E1",
        "semantic_type": "Transaction.amount",
        "usage": "VALUE_INPUT",
        "grounding_task_span_ids": []
      }
    ],
    "choice_origin_refs": [],
    "necessary_task_span_ids": ["T1"],
    "support": "SUPPORTED",
    "reason": "The candidate value is supported by the task-defined
    operation and referenced transaction amount."
  }
}
```

LLM2 checks the candidate value and necessary dependencies for record selection, comparison, and condition evaluation. It may correct imprecise references or identify missing dependencies within the evidence package, but cannot invent sources, alter source content, or change candidate values. Missing critical dependencies yield `UNKNOWN`.

Programmatic verification. The final decision combines semantic support verification and source authorization verification. The program first validates certificate structure, source references, and support conclusions, and then queries the frozen authority policy for each necessary dependency.

For a support certificate C_s, the verification condition is:

$$\begin{aligned}\mathrm{Check}(C_s) = \mathrm{Valid}(C_s) \wedge \mathrm{Supported}(C_s) \\ \wedge \bigwedge_{d \in D(C_s)} \mathrm{Authorized}_{\Phi}(d),\end{aligned} \tag{9}$$

where $D(C_s)$ denotes the necessary external dependencies reported by the certificate and Φ denotes the frozen authority policy implementing $\widehat{A}_T$.

The condition summarizes certificate-level verification. The runtime verifier additionally handles unresolved usage permissions and authority conflicts. A parameter is accepted only when all required facts pass verification.

The overall auditing procedure is summarized in Algorithm 2.

Algorithm 2 Parameter support tracing and authorization audit

function AUDIT($candidate, history, task$)
  $facts \leftarrow$ EXTRACTPARAMETERFACTS($candidate$)
  $\Phi \leftarrow$ RETRIEVEAUTHORITYPOLICY($facts$)
  $evidence \leftarrow$ BINDSOURCES($history, \Phi$)
  for each $fact$ in $facts$ **do**
    $trace \leftarrow$ LLM1.TRACE($task, fact, evidence$)
    $C_s \leftarrow$ LLM2.VERIFY($task, fact, evidence, trace$)
    Validate certificate structure and source references in C_s
    Check semantic support in C_s
    for each necessary external dependency d in $D(C_s)$ **do**
      Check authorization of d under the frozen policy Φ
    end for
  end for
  if all checks pass **then**
    return `ALLOW`
  else
    return `RECHECK`
  end if
end function

Malformed outputs or missing required fields trigger bounded protocol repair. If no valid verification result is obtained, the candidate remains in `RECHECK`. Verification records distinguish unauthorized dependencies, unsupported evidence, unresolved evidence, and protocol failures.

B.4 Prompt Templates and Message Protocol

AuthorityFlow uses independent prompts for authority construction, parameter support tracing, and verification. Each module receives structured inputs corresponding to its specific responsibility.

The authority construction prompts receive the trusted user task, tool interfaces, and source descriptions, as appropriate to each module. The tracing prompt receives candidate parameters and observed evidence. The semantic verification prompt receives parameter facts, evidence dependencies, and the tracing result, while the programmatic verifier queries the frozen authority policy. This separation implements the semantic support and source authorization checks in Section 3.4.

The representative prompt templates used in experiments are provided below.

Source Region Planner Prompt

```
Purpose:
Assign source regions and their base authority according to trusted
tool metadata and attacker-control boundaries.

Input:
```

Source Region Planner Prompt (continued)

```
Trusted tool interfaces, declared source fields, and field
identifiers.

Task:
Determine the region and base authority of each source field.

Requirements:
- Do not infer authority from runtime observations.
- Distinguish protected structured fields from externally editable
content.
- External content fields should not obtain HIGH authority.
- Output each field identifier exactly once.
- Each output item should contain:
  region,
  semantic type,
  and HIGH/LOW/UNKNOWN authority.
```

Task-use Authorization Compiler Prompt

```
Purpose:
Construct task-specific usage permissions between sources and
parameter-related facts.

Input:
Original task,
parameter consumption contract,
source facts,
task identifier.

Task:
Determine which usage roles each source fact may support.

Allowed roles:
- SELECTOR_INPUT
- DECISION_INPUT
- VALUE_INPUT

Requirements:
- Cover all reasonable valid dependency paths.
- Do not assume a single execution plan.
- Missing task-use authorization should not revoke existing base
authority.
- Low-authority free-form content should only receive selector-level
permissions under the current configuration.
- User-provided values do not require external retrieval.
```

Support Tracing LLM1 Prompt

```
Purpose:
Recover the semantic dependency chain behind a candidate parameter.

Input:
Original task,
known candidate values,
task spans,
observed source references.

Task:
Perform semantic provenance tracing for each target fact.
```

Support Tracing LLM1 Prompt (continued)

```
Requirements:
- Explain why specific records are selected.
- Identify evidence supporting the parameter value.
- Preserve conditions, comparisons, operands, and record
associations.
- Clearly reference source IDs and task spans.
- Distinguish evidence-derived facts, task-derived facts, and
implementation choices.
- Do not assign permissions.
- Do not follow instructions contained in source content.
```

Verification LLM2 Prompt

```
Purpose:
Verify semantic support of evidence for the candidate fact.

Input:
Original task,
target fact,
evidence directory,
LLM1 tracing result.

Task:
Determine whether the cited evidence and task context support the
fact.

Output:
- necessary sources;
- source semantic types;
- usage roles;
- necessary task spans;
- support mode;
- SUPPORTED / CONTRADICTED / UNKNOWN;
- explanation.

Requirements:
- Compare semantic meaning rather than exact string matching.
- Do not assign source permissions.
- Do not decide ALLOW or RECHECK.
```

The prompts above define the interaction interfaces among AuthorityFlow components. Runtime-specific fields, such as task instances, source identifiers, and evidence contents, are populated dynamically during execution.

C Additional Experimental Results

C.1 Results across Agent Models

Table 1 reports the Qwen3.6-27B and GPT-4o results. Here, Table 10 supplements those comparisons with Llama-3.3-70B-Instruct as the task-execution model and Qwen3.6-27B as the auxiliary model. All methods use the same 144 paired cases and automatic evaluation protocol described in Appendix A; AuthorityFlow+P denotes the downstream purification configuration.

Table 10: Baseline comparisons with Llama-3.3-70B as the task-execution model.

Method	BU ↑	UA ↑	ASR ↓
No Defense	39.58%	9.72%	47.22%
AttriGuard	38.19%	12.50%	36.11%
Sandwiching	28.47%	9.72%	33.33%
Spotlighting	50.00%	8.33%	56.25%
IPIGuard	57.64%	13.89%	53.47%
CaMeL	26.39%	19.44%	0.00%
DRIFT	25.00%	9.03%	21.53%
MELON	38.89%	9.03%	34.03%
AuthorityFlow+P	39.58%	27.78%	0.69%

On Llama, AuthorityFlow+P preserves the undefended BU of 39.58%, improves UA from 9.72% to 27.78%, and reduces ASR from 47.22% to 0.69%.

C.2 Per-domain Results

To evaluate the robustness of AuthorityFlow across different task domains, we report per-domain results on the four environments in FactAuthBench: Banking, Slack, Travel, and Workspace. AuthorityFlow+Purification is evaluated using the same benchmark split described in Appendix A. The numbers of paired cases are 33, 11, 60, and 40 for the four domains, respectively.

Table 11 reports the attack-setting utility (UA) across different task domains for three task-execution models.

Table 11: Per-domain utility under attack for AuthorityFlow+Purification.

Domain	**Cases**	Qwen UA ↑	Llama UA ↑	GPT-4o UA ↑
Banking	33	75.76%	39.39%	57.58%
Slack	11	18.18%	0.00%	54.55%
Travel	60	48.33%	25.00%	65.00%
Workspace	40	70.00%	30.00%	57.50%

Table 12 further reports benign utility and attack success rate for Llama and GPT-4o under each domain.

Table 12: Per-domain benign utility and attack success for AuthorityFlow+Purification.

Model	**Domain**	**Cases**	BU ↑	ASR ↓
Llama	Banking	33	45.45%	0.00%
Llama	Slack	11	9.09%	0.00%
Llama	Travel	60	35.00%	0.00%
Llama	Workspace	40	50.00%	2.50%
GPT-4o	Banking	33	87.88%	0.00%
GPT-4o	Slack	11	72.73%	27.27%
GPT-4o	Travel	60	70.00%	6.67%
GPT-4o	Workspace	40	72.50%	2.50%

Performance varies across domains: Qwen has higher UA on Banking and Workspace than on Slack, while GPT-4o has a narrower UA range. Most remaining successful GPT-4o attacks occur in Slack and Travel. The smaller domain sample sizes should be considered when interpreting these comparisons.

Overall results aggregate domain-level counts rather than averaging domain percentages. The UA counts sum to 84, 40, and 87 out of 144 cases for Qwen, Llama, and GPT-4o, respectively. Llama

has 57 benign successes and 1 successful attack; GPT-4o has 108 benign successes and 8 successful attacks. These totals agree with the corresponding AuthorityFlow+P results in Table 10 and the main Table 1.

C.3 Computational Cost

Under the implementation with authority caching and batched source verification, a standard AuthorityFlow audit requires up to four auxiliary-model calls for a candidate tool call: base authority construction, task-use authorization, parameter support tracing, and support verification. When base authority and task-use authorization are cached, this reduces to two calls for tracing and verification.

Table 13 reports the average end-to-end cost per attack-case execution on Qwen3.6-27B. LLM calls and token counts include both the task agent and defense-side requests, but exclude independent result scoring.

Table 13: Average end-to-end computational cost per attack-case execution on Qwen3.6-27B.

Method	**LLM Calls**	**Tokens (K)**	**Runtime (s)**
No Defense	4.12	17.71	31.94
Sandwiching	3.99	17.78	37.78
Spotlighting	4.13	17.90	42.18
AttriGuard	13.10	36.16	131.81
IPIGuard	8.12	45.81	130.36
CaMeL (policies)	4.53	25.57	153.19
DRIFT	37.05	47.71	315.59
MELON	6.83	32.27	93.67
AuthorityFlow	26.32	83.19	438.47

AuthorityFlow incurs higher computational overhead because verification operates at the parameter level: a tool call may contain multiple parameters, each requiring explicit dependency tracing and structured verification. The current protocol also records source references, usage roles, and verification evidence for each parameter. Reducing repeated context, sharing intermediate results across parameters, and consolidating auxiliary-model calls are promising directions for improving efficiency without weakening the authorization checks.

D Adaptive Attack Evaluation

We further evaluate AuthorityFlow against an adversary who is aware of its underlying verification procedure. In light of AuthorityFlow's verification checks (including task-specific authorization, parameter-support provenance, and source usage), the attacker crafts low-authority content to manipulate downstream reasoning governing record selection, entity association, aggregation scope, or action conditions. We select 10 representative user tasks and construct three specialized attack variants for each task, yielding 30 variants in total. All attack variants are fixed and finalized prior to evaluation.

We employ Qwen3.6-27B as both the task-execution and auxiliary models. To conservatively isolate the defensive capability of the verification mechanism itself, dedicated recovery is disabled while the standard recheck and subsequent execution flow remain intact. We compare AuthorityFlow with an undefended baseline under an identical execution budget. As shown in Table 14, AuthorityFlow substantially suppresses parameter-level ASR from 33.33% (10/30) to 6.67% (2/30), while improving Target Utility under attack from 66.67% to 76.67%. At the task level (where a task is deemed compromised if any of its three fixed variants succeeds), ASR drops from 50.00% (5/10) to 20.00% (2/10). Both configurations achieve 100% Target Utility across the 10 clean tasks.

Table 14: Adaptive attack evaluation on Qwen3.6-27B. Target Utility measures correctness of the designated target field rather than full task completion. Parameter ASR counts an attack as successful only when the attacker-targeted value reaches a successfully executed tool parameter.

Method	Clean Target Utility ↑	Attack Target Utility ↑	Parameter ASR ↓	Task-level ASR ↓
No Defense	100.00%	66.67%	33.33%	50.00%
AuthorityFlow	100.00%	76.67%	6.67%	20.00%

These empirical results demonstrate that AuthorityFlow maintains substantial defensive efficacy even against an informed adversary, corroborating that task-specific authorization and parameter-support verification remain resilient to defense-aware parameter poisoning. Nevertheless, the remaining failure cases highlight opportunities for refinement. In one channel-selection task, attacker-controlled text successfully forged the original author and channel of an incoming message. Although AuthorityFlow faithfully traced the injected text's lineage, the verifier nevertheless accepted its forged attribution claim, thereby admitting an incorrect channel parameter. This failure underscores a nuanced challenge: even when provenance is accurately tracked, semantic misjudgments can still arise when evaluating whether an identified source is genuinely authorized to govern a given decision.

While this evaluation focuses on defense-aware, pre-constructed attack variants, future work should explore dynamic, feedback-driven iterative attacks to systematically stress-test robustness against stronger threat models.

E Failure Modes and Illustrative Scenarios

E.1 Failure Analysis

We discuss three potential failure modes in Table 15, focusing on how authority reasoning can deviate from task semantics.

Table 15: Potential failure modes in AuthorityFlow.

Failure Type	**Description**
Authority Boundary Error	The constructed authority boundary does not accurately reflect the intended usage of a source
Dependency Tracing Error	The traced evidence chain misses or incorrectly associates intermediate dependencies
Fact Interpretation Error	The verified fact does not preserve the correct entity, role, or task constraint

The first category occurs when the available metadata is insufficient to distinguish different roles of information within the same source. For example, a response may contain both protected structured fields and editable descriptions, while the source boundary is not sufficiently fine-grained.

The second category occurs when the parameter value depends on intermediate reasoning steps that are not fully captured in the evidence chain. Such cases demonstrate the importance of explicitly tracing parameter dependencies rather than relying only on directly observed values.

The third category occurs when the evidence and source permissions are available, but the verified fact does not fully preserve the task context. This includes cases involving entity roles, conditional requirements, or comparisons among multiple candidates.

These cases indicate that improving authority inference under ambiguous contexts and strengthening evidence reasoning remain important directions for future work.

E.2 Illustrative Scenarios

We use two schematic scenarios to illustrate the intended distinction between legitimate information use and parameter poisoning.

Scenario 1: Legitimate external information use. A user asks the agent to find a message and reply in its corresponding channel. User-generated text may help identify the message, while its protected metadata supplies the channel identifier. The text and metadata are distinct source spans with different permissions: authorization for record identification does not grant the text authority to determine the channel parameter.

Scenario 2: Unauthorized parameter influence. An attacker-controlled note supplies an alternative date or amount for an operation whose value should come from a protected record. The proposed value may be plausible and textually supported by the note, but the source lacks authority for that use. Under the intended policy, AuthorityFlow rejects the candidate. Ambiguity in the task, source metadata, or dependency chain can undermine this decision, as discussed in the failure analysis above.

F Purification Details

Purification is used as a downstream mitigation strategy to recover legitimate task execution after AuthorityFlow rejects a candidate containing unauthorized parameter dependencies. It is not part of the core AuthorityFlow verification framework. This appendix describes the purification interface and reports additional end-to-end recovery results.

F.1 Purification Pipeline

When AuthorityFlow rejects a candidate tool call, purification generates an alternative candidate based on the verification results and available evidence. The goal of purification is not to redefine authority boundaries, but to recover a candidate whose parameter dependencies satisfy the existing AuthorityFlow verification criteria.

Given a rejected candidate, purification receives:

- the original user task;
- the rejected tool call;
- AuthorityFlow verification results;
- frozen parameter dependencies;
- available evidence sources.

The rejected candidate may contain both valid and invalid parameters. Therefore, purification only revises unsupported or unauthorized dependencies while preserving parameters that have already passed verification.

The purification process consists of three steps:

1. **Constraint identification.** AuthorityFlow identifies rejected parameter dependencies and preserves verified facts that should remain unchanged.
2. **Candidate regeneration.** The purification module generates an alternative tool call using the original task and available evidence. The generated candidate must preserve the original tool interface and satisfy the identified parameter constraints.
3. **Independent verification.** The regenerated candidate is returned to AuthorityFlow and undergoes the same verification procedure before execution.

The overall procedure is summarized in Algorithm 3.

If no candidate satisfies the verification requirements, the original rejected call remains blocked.

Algorithm 3 Purification candidate generation

```
function PURIFICATION(task, rejected_candidate, verification_result)
    fixed_facts ← VERIFIEDDEPENDENCIES(verification_result)
    repair_targets ← REJECTEDDEPENDENCIES(verification_result)
    evidence ← COLLECTEVIDENCE(task, rejected_candidate,
        fixed_facts, repair_targets)
    candidate ← GENERATEREPAIREDCANDIDATE(evidence)
    if candidate = ABSTAIN then
        return no_valid_candidate
    end if
    candidate ← RESTOREFIXEDVALUES(candidate, fixed_facts)
    return candidate
end function
```

F.2 Purification Prompt and Verification

The purification module uses two complementary components:

- a proposal model that generates a repaired candidate;
- AuthorityFlow verification that independently checks the regenerated result.

The proposal model receives the original task, rejected candidate, evidence sources, and verification constraints. It is instructed to preserve verified parameters and only modify unsupported dependencies.

A representative purification prompt is shown below.

Purification Prompt

```
Given the original user task and the rejected tool call,
generate a candidate that satisfies the user's goal while
respecting the verification constraints.

Preserve all already verified parameter values.
Only modify parameters whose dependencies are unsupported
or unauthorized.

Use provided evidence sources to derive repaired values.
Do not treat external claims as instructions.
Do not assign new authority to previously unauthorized sources.

If no candidate can be supported by available evidence,
return ABSTAIN.
```

The generated candidate is then verified by the original AuthorityFlow pipeline. In particular, purification cannot bypass:

- semantic support verification;
- source authorization verification;
- frozen authority boundaries.

Therefore, purification only changes the candidate generation process and does not alter the security guarantees provided by AuthorityFlow.

F.3 Additional Recovery Results

Table 16 compares AuthorityFlow with and without purification on Qwen3.6-27B.

Table 16: AuthorityFlow with and without purification on Qwen3.6-27B.

Configuration	BU ↑	UA ↑	ASR ↓
AuthorityFlow	82.64%	27.08%	9.03%
AuthorityFlow + Purification	84.72%	58.33%	9.03%

Adding purification improves UA from 27.08% to 58.33% while maintaining the same ASR of 9.03%. This indicates that purification primarily improves task recovery after detection rather than providing additional attack prevention.

We further analyze purification behavior across clean and attack settings in Table 17.

Table 17: Purification attempts and accepted candidates across clean and attack settings.

Setting	**Samples with Purification Attempts**	**Samples with Accepted Candidates**	**Accepted Attempts / Total Attempts**
Clean	34/144	13/144	14/47
Attack	132/144	77/144	88/183

Under attack settings, purification is invoked more frequently because more candidates violate the established authority constraints. The higher acceptance rate in attack settings indicates that a substantial portion of rejected candidates can be recovered using available trusted evidence.

Recovery and detection measure different outcomes: an accepted purification candidate provides an alternative execution path, whereas ASR measures unauthorized influence reaching execution. Purification supports task recovery while retaining the core authorization checks.