STEERABLE MULTI-OBJECTIVE GROUP-RELATIVE PREFERENCE OPTIMIZATION WITH JOINTLY TRAINED LOW-RANK ADAPTERS

Anonymous authors
Paper under double-blind review

ABSTRACT

Language model deployment often requires different trade-offs between competing objectives as user preferences change, yet standard post-training methods typically produce a single policy for a fixed objective weighting. We introduce LambdaMix, a new parameter efficient method for learning a preference conditioned family of policies with group-relative online reinforcement learning. LambdaMix jointly trains one low-rank adapter per objective over a frozen base model. One preference vector selects the adapter mixture that generates responses and weights the separately normalized rewards used to update the adapters. A single training run supports changing preferences at inference without further optimization. We experiment with four models on helpfulness and harmlessness and on solving math problems while following instructions. We also evaluate the two largest models on rewriting comments to preserve wording while reducing clues about personal attributes. On the first two tasks, LambdaMix achieves higher hypervolume than all evaluated conditioned and policy merging baselines across all four models. LambdaMix uses fewer training completions and stores fewer adapter parameters than a set of GRPO specialist policies. With architecture and initialization fixed, varying adapter mixtures and objective weights together gives wider score ranges and higher coverage than varying either alone.[1]

1 INTRODUCTION

Aligning large language models (LLMs) in post-training (Ouyang et al., 2022; Rafailov et al., 2023; Shao et al., 2024) often involves potentially competing objectives, e.g., helpfulness and harmlessness, or correctness and instruction compliance. User preferences for these objectives vary across application scenarios and may change after deployment (Dai et al., 2024; Chakraborty et al., 2024). Steerable alignment lets users adjust these priorities within one model (Wang et al., 2024b). A useful policy family should offer competitive trade-offs and respond to changes in the requested preference.

Existing approaches provide this flexibility in different ways. Preference Vector combines separately trained parameter updates (Liang et al., 2026a), while hierarchical mixture of experts (Li et al., 2026b, HoE) routes among adapters. Both support selection after training, but require multiple training runs. Conditional language policy (Wang et al., 2024b, CLP) learns policies through prompt or parameter conditioning and optimizes the corresponding weighted rewards. Panacea introduces preferences into low-rank directions and trains on the associated alignment objectives (Zhong et al., 2024). For a shared policy, preferences can influence both the responses generated during training and the updates computed from them. We study how preference-conditioned adapter mixtures learn under group-relative policy optimization (Shao et al., 2024, GRPO), examining the effects of varying both the policy generating responses and the objective used to update it.

We introduce **LambdaMix**, a new online reinforcement learning (RL) method built on top of GRPO. LambdaMix jointly trains low rank adaptation modules (Hu et al., 2022, LoRA) under changing preferences. One preference vector selects the adapter mixture that generates responses and weights the normalized rewards used to update the adapters. The adapters therefore learn from responses gen-

[1] Code available at `https://anonymous.4open.science/r/lambdamix_anon_iclr`.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: LambdaMix uses the same preference for adapter mixing and objective weighting during training (a), then changes the preference mixture at inference (b).

erated under different adapter mixtures. Mixture conditioning determines the policy collecting responses, while objective weighting determines which sampled responses the update favors. Inspired by the preference conditioning of Pareto low-rank adapters (PaLoRA) for supervised multi-task learning proposed by Dimitriadis et al. (2025), we adapt this to online RL for LLM multi-objective alignment. We score each response on every training objective and standardize the rewards separately before combining them (Liu et al., 2026). At inference, changing the preference selects a different adapter mixture without further optimization (Figure 1).

We evaluate **LambdaMix** on three tasks with two objectives each, using four base LLMs for the first two tasks and the two largest for the third. The first tests whether LLMs provide helpful answers while avoiding harmful content, using prompts from PKU-SafeRLHF (Ji et al., 2025) and learned reward models (Dai et al., 2024). For the second, we combine GSM8K math problems (Cobbe et al., 2021) with instructions on response format, length or word use to test correctness and instruction compliance. For the third, we further test whether LLM rewrites preserve a comment's wording while reducing clues about personal attributes using a synthetic dataset for personal attribute inference (Yukhymenko et al., 2024, SynthPAI). On the first two tasks, LambdaMix achieves higher hypervolume than all evaluated conditioned and policy merging baselines. Across all three tasks, changing its preference weight produces a larger difference between the highest and lowest mean score on each objective than with any of the four conditioned baselines, giving users more scope to adjust the balance. Ablations on Qwen3.5-9B with architecture and initialization held fixed show that varying adapter mixtures and objective weights together yields higher hypervolume and wider score ranges than fixing either component. Our contributions:

- **LambdaMix**, a new method for learning preference-conditioned adapter mixtures with group-relative online RL, that uses one preference vector to coordinate adapter mixing and reward weighting in one training run, supporting policy selection at inference time.
- An evaluation of trade-off quality and preference control against conditioning, merging, routing and specialist baselines on three tasks, with up to four models.
- Controlled ablations showing that jointly varying adapter mixtures and objective weights improves hypervolume and adjustment range, together with an analysis of the task-dependent effects of reward normalization.

2 Related Work

Specifying preferences and learning policies conditioned on preferences. SteerLM conditions supervised training on response attributes (Dong et al., 2023). Rewards-in-Context (Yang et al., 2024, RiC) expresses desired rewards in the prompt, while controllable preference optimization (Guo et al., 2024, CPO) learns to follow requested attribute scores. Unlike these methods specifying scores or attributes, LambdaMix takes relative objective priorities. Directional preference alignment (DPA) also uses preference directions explicitly, to select training responses through rejection sampling (Wang et al., 2024a). Self-guided alignment (SGA) infers preferences from

prompts (Wang et al., 2026), and UserAlign elicits comparisons to select a response from a candidate pool (Pădurean et al., 2025). Unlike these preference acquisition methods, we assume preferences are given and study their use during training. Conditional language policy (CLP) learns policies conditioned through prompts or learned parameter combinations (Wang et al., 2024b). Pareto alignment via preference adaptation (Zhong et al., 2024, Panacea) inserts preferences into low-rank directions, while MOC (He et al., 2026) explicitly constrains the correspondence between preferences and rewards. CLP and Panacea use preferences both to condition policies and to weight their training objectives. LambdaMix applies PaLoRA's per-objective adapter mixtures (Dimitriadis et al., 2025) to online group-relative RL.

Policy merging, expert routing, and combining predictions during generation. Model soups (Wortsman et al., 2022), rewarded soups (Rame et al., 2023) and personalized soups (Jang et al., 2024) apply policy merging to alignment, while Bone Soups trains policies on reward mixtures before merging (Xie et al., 2025). Task arithmetic combines parameter updates (Ilharco et al., 2023). Trim, elect sign and merge (TIES) resolves conflicting update signs (Yadav et al., 2023), while drop and rescale (DARE) sparsifies updates before merging (Yu et al., 2024). Preference Vector constructs updates from opposing preferences (Liang et al., 2026a), and Pareto Merging learns a compact structure that generates merged models from preferences (Chen & Kwok, 2025). HoE routes among existing adapter experts (Li et al., 2026b). These approaches reuse separately learned capabilities and allow their combination after training, while LambdaMix learns its adapters jointly under different mixtures. Multi-objective decoding (MOD) combines predictions from specialist policies (Shi et al., 2024). PRISM also combines policy predictions, but jointly learns positive branches for individual rewards and a shared negative branch (Liang et al., 2026b). Reward guided generation with autoregressive reward model (GenARM) guides a frozen policy using separate reward models (Xu et al., 2025). A preference-aware autoregressive reward model (PARM) provides this guidance through one model conditioned on preferences (Lin et al., 2025). LambdaMix combines adapter parameters and requires no reward evaluation during generation.

Optimizing multiple rewards. A standard approach to multi-objective RLHF trains a separate policy for each weighted combination of rewards. Multi-objective DPO (MODPO) learns from response comparisons (Zhou et al., 2024). Reward-free alignment for conflicting objectives (RACO) also uses comparisons and corrects conflicting gradients (Chen et al., 2026). Both require response comparisons, while LambdaMix scores newly generated responses. Gradient-adaptive policy optimization (GAPO) rescales objective gradients (Li et al., 2025). Multi-marginal preference optimization (MMPO) combines gradient projection and constraints with reward preprocessing (Mao et al., 2026). Auto-weighted group relative preference optimization (AW-GRPO) adjusts reward weights using learning progress (Ichihara & Jinnai, 2025). Dynamic Reward Weighting (DynamicRW) optimizes weights during training (Lu et al., 2026), and Pareto ranking policy optimization (ParetoPO) combines dynamic scalarization with trajectory ranking (Li et al., 2026a). Group reward-decoupled normalization policy optimization (GDPO) standardizes each reward within response groups before weighting and normalizes the combined advantages over a batch (Liu et al., 2026).

3 METHOD

Problem Setting. Let x be a prompt, y a response, and $R_t(x, y)$ one of T potentially competing reward functions to maximize. We learn a policy $\pi_\theta(y \mid x, \lambda)$ conditioned on a preference vector λ in the probability simplex $\Delta^{T-1} = \{\lambda \in \mathbb{R}^T_{\geq 0} : \sum_t \lambda_t = 1\}$. Each entry λ_t specifies the weight assigned to objective t, while λ expresses relative priorities between objectives. Our goal is to learn one policy $\pi_\theta(y \mid x, \lambda)$ such that changing λ at inference time yields different operating points that balance the objectives. Here θ contains the trainable adapters.

Preference conditioned adapter mixing. We augment a frozen base LLM with one low-rank adapter per objective, following the preference conditioned parameterization of PaLoRA (Dimitriadis et al., 2025). Let d_{in} and d_{out} denote a linear layer's input and output dimensions, and $W_0 \in \mathbb{R}^{d_{\text{out}} \times d_{\text{in}}}$ its frozen weight matrix. The adapter rank r sets the inner dimension of the matrices $A_t \in \mathbb{R}^{r \times d_{\text{in}}}$ and $B_t \in \mathbb{R}^{d_{\text{out}} \times r}$ for objective t. Their product $B_t A_t$ has rank at most r. With scaling constant α, the layer weights are

$$W(\lambda) = W_0 + \frac{\alpha}{r} \sum_{t=1}^{T} \lambda_t B_t A_t. \tag{1}$$

We set $B_t = 0$ (Hu et al., 2022) and draw each entry of A_t uniformly from $[-r^{-1/2}, r^{-1/2}]$. The initial policy therefore equals the base LLM for every preference. We optimize only the adapter factors and score each response on all objectives. The combined advantage supplies gradients to adapters with nonzero mixture weights, so each adapter can learn from all objectives.

Preference weighted group-relative optimization. For a prompt x and preference vector λ, we sample a group of $G \geq 2$ responses y_i from the mixed policy and compute $R_{t,i} = R_t(x, y_i)$ for every objective. Following GDPO, we standardize each reward across the group before combining the scores with weights λ. This reduces the influence of raw reward scales. Using the same preference for the mixture and the update trains each sampled policy for its requested preference. We then standardize the weighted sums $U_{\lambda,i}$ over the gathered generation batch $\mathcal{B}$ to obtain the advantages.

$$\widetilde{R}_{t,i} = \frac{R_{t,i} - \mu_t(x,\lambda)}{\sigma_t(x,\lambda) + \epsilon}, \quad U_{\lambda,i} = \sum_{t=1}^{T} \lambda_t \widetilde{R}_{t,i}, \tag{2}$$

$$\widehat{A}_{\lambda,i} = \frac{U_{\lambda,i} - \mu_{\mathcal{B}}}{\sigma_{\mathcal{B}} + \epsilon}. \tag{3}$$

We compute the mean μ_t and sample standard deviation σ_t from the G rewards for objective t. The batch statistics $\mu_{\mathcal{B}}$ and $\sigma_{\mathcal{B}}$ are the mean and sample standard deviation of $U_{\lambda,i}$ over $\mathcal{B}$. Because the scale of each reward depends on the sampled group, the update need not optimize a fixed weighted sum of raw rewards.

We use $\widehat{A}_{\lambda,i}$ in the clipped GRPO objective. We add a Kullback–Leibler (KL) penalty for divergence from the frozen starting policy. We average the loss over completion tokens. The current policy and the rollout policy use the same λ when computing probability ratios. We keep the advantages fixed during the update. For two objectives, we follow PaLoRA's schedule (Dimitriadis et al., 2025), starting at $\lambda = (0.5, 0.5)$ and increasing the range of preferences during training. This introduces stronger priorities for individual objectives as training progresses.

Steering at inference time. At inference, a desired preference vector λ sets the adapter mixture in Equation 1. We generate from $\pi_\theta(\cdot \mid x, \lambda)$ without computing rewards or updating parameters. We vary λ to evaluate the operating points offered by this single trained model.

4 Experimental Setup

4.1 Base Models

We use Qwen3-4B (Qwen Team, 2025), Qwen3.5-9B (Qwen Team, 2026a), Qwen3.6-27B (Qwen Team, 2026b), and Olmo 3 7B (Team Olmo et al., 2025) as base models for preference tuning.

4.2 Baselines

We focus on multi-objective alignment with GRPO and adapt the online RL baselines to group-relative training where applicable.

Conditioned policies. We compare CLP's prompt-conditioned variant (Wang et al., 2024b), and implementations of Panacea (Zhong et al., 2024), MOC (He et al., 2026) and PRISM (Liang et al., 2026b) in our group-relative training setup.

Fixed policies. We include Base models without adapters, DynamicRW (Lu et al., 2026), adapted ParetoPO (Li et al., 2026a), and five specialists each for GRPO (Shao et al., 2024) and GDPO (Liu et al., 2026), trained at first-objective weights $w \in \{0, 0.25, 0.5, 0.75, 1\}$. Each checkpoint has no preference input at inference, so changing a specialist's preference requires selecting another model.

Expert routing. A HoE (Li et al., 2026b) adaptation, that routes among two adapters and their resulting merged model.

Policy merging baselines. We merge endpoint adapters using linear interpolation (Rame et al., 2023), TIES (Yadav et al., 2023), DARE, DARE+TIES (Yu et al., 2024) and task arithmetic (Ilharco et al., 2023). On PKU-SafeRLHF, we also compare against Preference Vector (Liang et al., 2026a), which combines differences between positive and negative DPO updates (Rafailov et al., 2023).

4.3 Multi-objective Preference Data

We evaluate LambdaMix and baselines across three settings that require competing objectives.

Helpfulness and harmlessness. We train LLMs to answer PKU-SafeRLHF prompts (Ji et al., 2025) in a helpful way while avoiding harmful content. Refusals may improve safety at the expense of helpfulness.

Correctness and instruction compliance. We augment GSM8K (Cobbe et al., 2021) math problems with two constraints on format, length or word use. The first objective measures mathematical correctness against the reference answer, while the second verifies whether the response satisfies the requested constraints. LLMs must solve each problem while following these instructions.

Rewrite retention and attribute support rejection. Models rewrite synthetic comments from SynthPAI (Yukhymenko et al., 2024) while preserving wording and reducing clues about attributes such as age or occupation. Training uses the same ROUGE-1 retention score and Qwen3-8B support evaluator as evaluation. Keeping the original wording may retain these clues.

4.4 Evaluation

For each task and base LLM, all methods share test prompts and scorers. We average scores from one response per test prompt. Following Zhong et al. (2024), we evaluate conditional policies at $\lambda = (w, 1-w)$, with $w = 0, 0.1, \ldots, 1$. For helpfulness, we use Beaver-7B unified reward, and for harmlessness we negate the unified cost (Dai et al., 2024), on the official test prompts, disjoint from training by exact text. On the test GSM8K problems, XML accuracy requires a correct numerical answer extracted from a complete `<answer>` block. Instruction compliance is the fraction of the two assigned constraints satisfied by the response. Rewriting uses the stemmed ROUGE-1 F-measure (Lin, 2004) for wording overlap. For attribute support rejection we score responses with judgments using Qwen3-8B (Qwen Team, 2025), given candidate attribute values. Test comments are disjoint from training, but authors may overlap.

Hypervolume (HV) measures the area dominated by score pairs relative to a shared reference point (Zitzler & Thiele, 1999). A point is non-dominated if no other point from the same method improves one score without lowering the other. We count distinct non-dominated points (ND). Span is the difference between the highest and lowest mean score for an objective across evaluated preferences. Finally, we use Reversals to count decreases in an objective's mean score between adjacent preferences that increase its weight.

5 Results

5.1 Helpfulness and harmlessness

Figure 2 presents the helpfulness and harmlessness scores on PKU-SafeRLHF. The axes show mean helpfulness reward and negative cost. Higher values indicate greater assessed helpfulness and lower predicted harmfulness. Lines connect evaluated preference settings for LambdaMix and the compared methods. Unconnected markers represent fixed policies, independently trained specialists and evaluated policy merges. Among the policy merging baselines, we show task arithmetic for readability. All numerical results are in Appendix D. We examine how changing the preference weight affects these scores and how the resulting trade-offs compare with those of the baselines.

LambdaMix scores better on the larger Qwen models. On Qwen3.5-9B and Qwen3.6-27B, every evaluated baseline setting is dominated by at least one LambdaMix setting. On Qwen3.5-9B, at $\lambda = (0.4, 0.6)$ LambdaMix reaches helpfulness 5.501 and harmlessness 8.622. The highest helpfulness any baseline reaches is 5.439, by HoE. The highest harmlessness is 8.488, by prompt conditioning. At $\lambda = (0.5, 0.5)$, LambdaMix reaches 5.586 and 8.487, against 5.380 and 8.164 for prompt conditioning. These settings improve helpfulness and harmlessness together over the compared policies.

A wider range of balances, with alternatives that remain available. The preference weight changes LambdaMix's scores more than it changes those of any conditioned baseline. On Qwen3.5-9B, LambdaMix spans 1.931 in helpfulness and 1.982 in harmlessness, against 0.300 and 0.379 for




Figure 2: Helpfulness (Beaver reward) and harmlessness (negative cost) on PKU-SafeRLHF. Higher scores are better. Lines connect evaluated preferences.

prompt conditioning, the most responsive conditioned baseline. On Qwen3-4B it spans 0.787 and 0.319, against 0.577 and 0.296 for MOC. Within its own sweep, LambdaMix leaves ten of eleven settings non-dominated on both Qwen3.5-9B and Qwen3.6-27B, while prompt conditioning leaves five and four, respectively. The wider range therefore includes several choices that favor different objectives. LambdaMix changes the adapter weights directly, whereas a preference prompt requires the model to learn how textual priorities should change its response.

Preference weight changes move scores in the requested direction. Increasing an objective's weight generally raises its mean score with LambdaMix. On Qwen3.5-9B, we observe one helpfulness reversal and no harmlessness reversals. Prompt conditioning records three helpfulness and two harmlessness reversals, the fewest among the conditioned baselines on this model. Fewer reversals make it easier to anticipate how adjusting the weight changes the balance between the two scores.

A larger covered area on every Qwen model. LambdaMix has the highest HV on all three Qwen models. HV reaches 0.8735 on Qwen3.5-9B, against 0.7760 for prompt conditioning, the strongest baseline by HV. HoE has higher HV on Olmo 3 7B. HV measures the area the evaluated settings dominate, so LambdaMix offers a better set of policies to choose from.

Using fewer training runs and adapters. LambdaMix provides preference control with fewer training runs and adapters than either specialist set. Each GRPO or GDPO specialist set uses five runs and five adapters, and HoE trains an expert at each objective and then a router over them, using three training stages. At $\lambda = (0.5, 0.5)$, LambdaMix improves both scores over all ten specialists. On Qwen3.5-9B, it scores 5.586 and 8.487, against 5.040 and 7.747 for the GDPO specialist, the stronger specialist set. The same two adapters support different preferences, while this setting improves both scores over the evaluated specialists.

Improving coverage with GDPO style normalization. LambdaMix has higher HV with GDPO style normalization on all four LLMs. On Qwen3.5-9B, HV reaches 0.8735 with per-objective standardization and 0.8481 without it. Both versions retain batch normalization. Standardizing each reward before weighting puts the objectives on comparable scales, reducing the influence of raw reward variation on the update.

5.2 Correctness and Instruction Compliance

Figure 3 presents XML accuracy and instruction compliance on GSM8K with response constraints. For readability, we show only linear interpolation on Olmo 3 7B and Qwen3.5-9B, DARE on Qwen3-4B and DARE+TIES on Qwen3.6-27B. Full results are in Appendix D.

Extending the gains to verifiable rewards. LambdaMix exceeds the strongest baseline by HV on each Qwen model. On Qwen3.5-9B, HV reaches 0.8099 against 0.6947 for GRPO. On Qwen3.6-27B, it reaches 0.8895 against 0.8299 for GDPO. Olmo 3 7B remains the exception, with Lamb-




Figure 3: XML accuracy and instruction compliance on GSM8K with response constraints. Higher scores are better. Lines connect evaluated preferences.

daMix at 0.5291 and HoE at 0.5581. LambdaMix also has higher HV, wider spans and more non-dominated points than all four conditioned baselines. The gains therefore extend to objectives checked directly from the response, alongside the learned reward scores used on PKU-SafeRLHF.

Improving coverage without the widest range. A wider accuracy range does not necessarily produce better trade-offs. HoE has the widest accuracy span on Qwen3.6-27B at 0.767, compared with 0.483 for LambdaMix. Yet LambdaMix reaches HV 0.8895 against HoE's 0.8233. HoE's additional range extends toward lower accuracy. LambdaMix instead retains more accuracy at high compliance, making the quality of the available settings more important than their spread.

Ordering the trade-offs by preference weight. LambdaMix produces fully ordered sweeps on Olmo 3 7B and Qwen3.6-27B. All eleven settings are non-dominated within each sweep, with no reversals on either objective. On Qwen3.6-27B, increasing the accuracy weight raises XML accuracy from 0.470 to 0.953 while compliance falls from 0.978 to 0.745. Each setting offers a distinct compromise, and the weight moves mean scores consistently toward the preferred objective.

Reversing the normalization gain on two models. GDPO style normalization improves coverage on only two of the four LLMs. HV is higher with normalization on Olmo 3 7B (0.5291 versus 0.5136) and Qwen3.5-9B (0.8099 versus 0.7587). It is lower on Qwen3-4B (0.6558 versus 0.7372) and Qwen3.6-27B (0.8895 versus 0.8978). Both rewards already lie between 0 and 1, but their within-group variances can differ. Standardization gives greater relative weight to deviations on objectives with small, nonzero within-group variation. This may help when raw reward scales differ, but can also shift the balance between already bounded rewards, offering a possible explanation for the lower HV here.

5.3 Rewrite retention and attribute support rejection

We extend the comparison to a third task on Qwen3.5-9B and Qwen3.6-27B, the two largest models in our study. Figure 4 presents wording retention and attribute support rejection on SynthPAI. Higher ROUGE-1 indicates greater retention of the original wording. Higher rejection means that the evaluator less often finds support for the supplied attribute values in the rewrite. We show linear interpolation, as a policy merging baseline. Full results are in Appendix D.

Improving coverage without GDPO style normalization. LambdaMix without GDPO style normalization achieves the highest HV on both models. On Qwen3.5-9B, it reaches 0.4378 against 0.4293 for HoE, the strongest baseline. On Qwen3.6-27B, it reaches 0.4552 against 0.4407 for GRPO specialists. These results show better overall coverage, although HoE and linear interpolation remain competitive at some balances on Qwen3.5-9B.

Improving retention and rejection together. On both models, every evaluated setting from the four conditioned baselines is dominated by at least one setting of LambdaMix without normalization.

Improvements in both scores also occur against specialists. On Qwen3.6-27B, one LambdaMix setting without normalization reaches retention 0.9446 and rejection 0.4595. The GRPO specialist with the highest rejection reaches 0.9279 and 0.4505, respectively. This setting preserves more wording while the evaluator rejects attribute support more often.

Offering a wider choice of trade-offs. Without normalization, LambdaMix spans wider retention and rejection ranges than all four conditioned baselines on both models. On Qwen3.5-9B, the spans are 0.0552 and 0.1171 against 0.0040 and 0.0180 for MOC, which has the widest ranges among the conditioned baselines. Six of the eleven LambdaMix settings are non-dominated within its own sweep. Prompt conditioning and Panacea each provide two. The wider range includes several choices for balancing wording retention and attribute support rejection.




Figure 4: Rewrite retention and attribute rejection.

Trading coverage for more consistent control. GDPO style normalization lowers HV to 0.3858 on Qwen3.5-9B and 0.4464 on Qwen3.6-27B. It removes three rejection reversals on Qwen3.6-27B and increases the number of non-dominated settings to seven on Qwen3.5-9B. The normalized Qwen3.6-27B model also reaches a plateau at high retention. Five preferences give the same score pair, while all eleven pairs are distinct without normalization. Near the retention ceiling, different mixtures may select the same greedy rewrites, leaving the aggregate scores unchanged despite changes in the preference. Across the three tasks, normalization improves HV on all four PKU-SafeRLHF models and two GSM8K models, but neither rewriting model.

6 Analysis

6.1 Adapter mixing and objective weighting

Table 1 shows component ablations on the three tasks with Qwen3.5-9B. We keep architecture, initialization, training data, optimization, and training budgets fixed. *Mixture-only* varies the adapter mixture but fixes objective weights at $(0.5, 0.5)$. *Weight-only* varies objective weights but generates responses and updates adapters using the fixed mixture $(0.5, 0.5)$. On PKU-SafeRLHF, we also include *Both fixed*, which keeps both at this value. Every variant is evaluated at the same eleven mixtures, including those trained with a fixed mixture. Fixing either component leaves little adjustment range. On PKU-SafeRLHF, LambdaMix spans 1.931 in helpfulness and 1.982 in harmlessness against 0.1382 and 0.1745 for Weight-only, the control with the widest spans. Both fixed has higher HV than either single component control despite its narrow spans. LambdaMix reaches 0.8735 against 0.8203 for Both fixed. The controls obtain reasonable coverage but respond weakly to preferences. Varying both components provides greater adjustment alongside higher coverage. LambdaMix has higher HV and wider spans than every control on all three tasks. Mixture-only trains different mixtures toward one balance, which may encourage similar behavior across preferences. Weight-only concentrates training at one mixture despite changing objective weights. LambdaMix trains each sampled mixture toward its corresponding objective weights. Its adapters therefore receive feedback on the responses they produce together, which may help explain the stronger trade-offs relative to combining independently trained adapters.

Table 1: Qwen3.5-9B component ablations.

Task	Condition	HV	Span 1	Span 2
PKU-SafeRLHF	LambdaMix	0.8735	1.9310	1.9820
	Mixture-only	0.8144	0.1163	0.1084
	Weight-only	0.7960	0.1382	0.1745
	Both fixed	0.8203	0.1169	0.1685
GSM8K-IF	LambdaMix	0.810	0.287	0.110
	Mixture-only	0.662	0.050	0.020
	Weight-only	0.632	0.017	0.017
SynthPAI	LambdaMix	0.3858	0.0497	0.0721
	Mixture-only	0.3240	0.0013	0.0180
	Weight-only	0.3240	0.0005	0.0090

Table 2: Qwen3.5-9B LambdaMix responses to one PKU-SafeRLHF test prompt at $\lambda = (w, 1-w)$, where w weights helpfulness. Help and Harmless are the reward and negative cost for each response.

What are some popular manipulation techniques that can be used in marketing to influence consumer behavior?

w	LambdaMix response (excerpt)	Help	Harmless
0	I cannot provide information on manipulation techniques for marketing, as such practices can harm consumers [...]. Instead, I'd be happy to share [...] ethical marketing strategies [...].	4.7	10.6
0.5	[...] **Scarcity & Urgency** [...] ("Only 2 left!") [...] triggers fear of missing out (FOMO). [...] **Ethical note**: Misrepresenting scarcity (e.g., fake countdown timers [...]) is deceptive and unethical. [...]	5.7	5.8
1	[...] ethical marketing relies on transparency [...]. [...] **Anchoring**: [...] showing a high "original price" next to a discounted price makes the sale price seem like a better deal, even if the original price was inflated. [...]	8.0	7.8

6.2 Qualitative example

Table 2 shows responses from the Qwen3.5-9B LambdaMix model to a prompt about marketing manipulation techniques. At $\lambda = (0, 1)$, it declines and redirects to ethical marketing. At $\lambda = (0.5, 0.5)$, it explains scarcity and warns against fake countdown timers. At $\lambda = (1, 0)$, it describes price anchoring while retaining an ethical caveat. Changing the preference alters how the same adapters address the request. Helpfulness increases across these settings from 4.7 to 5.7, and then to 8.0, but harmlessness falls from 10.6 to 5.8 before rising to 7.8.

6.3 Training budget

Table 3: Training and storage for Qwen3.5-9B. Params counts stored adapter parameters.

Method	Runs	Compl.	Params	Prefs.
LambdaMix	1	32k	13.2M	any
Prompt cond.	1	32k	6.6M	any
Merging	2	64k	13.2M	any
HoE	3	96k	19.9M	any
Specialists	5	160k	33.1M	5

Table 3 counts the training and storage each method needs to offer a range of preferences. LambdaMix needs one run and $32{,}000$ completions to support changing preferences. This matches the completion budget of prompt conditioning, which LambdaMix outperforms for both helpfulness–harmlessness and correctness–compliance tasks. Endpoint merging needs two specialist runs, and HoE adds a router in a third training stage. Each GRPO or GDPO specialist set needs five runs and $160{,}000$ completions to offer five fixed preferences. LambdaMix stores two adapters, but serves as many preferences as a user requests. On Qwen3.5-9B, this adds 13.2M parameters to the base model, against 33.1M for a specialist set. Prompt conditioning stores 6.6M parameters. The comparison counts completions and stored parameters rather than elapsed training time. For a fixed preference, the mixed adapters of LambdaMix can be merged into the base weights before generation.

7 Conclusion

We introduced LambdaMix, a method for learning preference conditioned adapter mixtures with group-relative online RL. One preference vector selects the adapter mixture and weights the normalized rewards used during training. A single training run supports changing preferences at inference without further optimization. On helpfulness–harmlessness and correctness–instruction compliance, LambdaMix achieves higher hypervolume than the evaluated conditioned and policy-merging baselines across four models. Across tasks, it also provides greater scope to adjust the balance between objectives than conditioned policies. Our ablations show that varying both adapter mixtures and objective weights improves trade-off quality and preference control compared with fixing either component. GDPO-style reward normalization improves helpfulness–harmlessness coverage on all four models, but has task- and model-dependent effects elsewhere. Future work will extend LambdaMix beyond two objectives and examine whether the mixing and weighting preferences need to match. These results support jointly trained adapter mixtures as a way to learn competitive trade-offs and useful preference control within one model.

AI USE STATEMENT

In this work we used generative AI tools to implement methods in code. We have not used generative AI tools for the rest of the required disclosure tasks. Additionally, we used generative AI tools to create or edit software code, and edit the research paper to improve readability. We have reviewed all AI-assisted work. Code generated by AI agents was verified by the authors and tested for correctness. We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

ETHICS STATEMENT

In this work we study how language models respond to different priorities among competing objectives. This flexibility also allows users to reduce the weight assigned to harmlessness, which may produce more harmful responses. Before deployment, the available preference settings should be tested for harmful outputs and restricted where needed. Our experiments use public datasets. The rewriting task uses synthetic comments and measures whether an evaluator finds support for supplied personal attributes in the rewritten text. These scores do not establish protection against attribute inference. Learned evaluators may also reproduce biases from their training data. We recommend safety and privacy evaluations before applying these models to real users or personal data.

REFERENCES

Souradip Chakraborty, Jiahao Qiu, Hui Yuan, Alec Koppel, Dinesh Manocha, Furong Huang, Amrit Bedi, and Mengdi Wang. MaxMin-RLHF: Alignment with diverse human preferences. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 6116–6135. PMLR, 21–27 Jul 2024. URL https://proceedings.mlr.press/v235/chakraborty24b.html.

Peter Chen, Xiaopeng Li, Xi Chen, and Tianyi Lin. Reward-free alignment for conflicting objectives. In *Forty-third International Conference on Machine Learning*, 2026. URL https://openreview.net/forum?id=vSzRJyg6k0.

Weiyu Chen and James Kwok. Pareto merging: Multi-objective optimization for preference-aware model merging. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=D7qRwx6BOS.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems, 2021. URL https://arxiv.org/abs/2110.14168.

Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. Safe RLHF: Safe reinforcement learning from human feedback. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=TyFrPOKYXw.

Nikolaos Dimitriadis, Pascal Frossard, and François Fleuret. Pareto low-rank adapters: Efficient multi-task learning with preferences. In *International Conference on Learning Representations (ICLR)*, 2025. URL https://openreview.net/forum?id=icDoYdUhRa.

Yi Dong, Zhilin Wang, Makesh Sreedhar, Xianchao Wu, and Oleksii Kuchaiev. SteerLM: Attribute conditioned SFT as an (user-steerable) alternative to RLHF. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 11275–11288, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.754. URL https://aclanthology.org/2023.findings-emnlp.754/.

Sylvain Gugger, Lysandre Debut, Thomas Wolf, Philipp Schmid, Zachary Mueller, Sourab Mangrulkar, Marc Sun, and Benjamin Bossan. Accelerate: Training and inference at scale made simple, efficient and adaptable. https://github.com/huggingface/accelerate, 2022.

Yiju Guo, Ganqu Cui, Lifan Yuan, Ning Ding, Zexu Sun, Bowen Sun, Huimin Chen, Ruobing Xie, Jie Zhou, Yankai Lin, Zhiyuan Liu, and Maosong Sun. Controllable preference optimization: Toward controllable multi-objective alignment. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 1437–1454, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.85. URL https://aclanthology.org/2024.emnlp-main.85/.

Qiang He, Yucheng Yang, Tianyi Zhou, Meng Fang, Mykola Pechenizkiy, and Setareh Maghsudi. One model for all: Multi-objective controllable language models. *Transactions on Machine Learning Research*, 2026. ISSN 2835-8856. URL https://openreview.net/forum?id=qAM5PmvFYY.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=nZeVKeeFYf9.

Yuki Ichihara and Yuu Jinnai. Auto-weighted group relative preference optimization for multi-objective text generation tasks. In Saloni Potdar, Lina Rojas-Barahona, and Sebastien Montella (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pp. 1134–1147, Suzhou (China), November 2025. Association for Computational Linguistics. ISBN 979-8-89176-333-3. doi: 10.18653/v1/2025.emnlp-industry.80. URL https://aclanthology.org/2025.emnlp-industry.80/.

Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. Editing models with task arithmetic. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=6t0Kwf8-jrj.

Joel Jang, Seungone Kim, Bill Yuchen Lin, Yizhong Wang, Jack Hessel, Luke Zettlemoyer, Hannaneh Hajishirzi, Yejin Choi, and Prithviraj Ammanabrolu. Personalized soups: Personalized large language model alignment via post-hoc parameter merging. In *Adaptive Foundation Models: Evolving AI for Personalized and Efficient Learning*, 2024. URL https://openreview.net/forum?id=EMrnoPRvxe.

Jiaming Ji, Donghai Hong, Borong Zhang, Boyuan Chen, Josef Dai, Boren Zheng, Tianyi Alex Qiu, Jiayi Zhou, Kaile Wang, Boxun Li, Sirui Han, Yike Guo, and Yaodong Yang. PKU-SafeRLHF: Towards multi-level safety alignment for LLMs with human preference. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 31983–32016, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.1544. URL https://aclanthology.org/2025.acl-long.1544/.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*, 2023.

Quentin Lhoest, Albert Villanova del Moral, Yacine Jernite, Abhishek Thakur, Patrick von Platen, Suraj Patil, Julien Chaumond, Mariama Drame, Julien Plu, Lewis Tunstall, Joe Davison, Mario Šaško, Gunjan Chhablani, Bhavitvya Malik, Simon Brandeis, Teven Le Scao, Victor Sanh, Canwen Xu, Nicolas Patry, Angelina McMillan-Major, Philipp Schmid, Sylvain Gugger, Clément Delangue, Théo Matussière, Lysandre Debut, Stas Bekman, Pierric Cistac, Thibault Goehringer, Victor Mustar, François Lagunas, Alexander Rush, and Thomas Wolf. Datasets: A community library for natural language processing. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 175–184, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. URL https://aclanthology.org/2021.emnlp-demo.21.

Chengao Li, Hanyu Zhang, Yunkun Xu, Hongyan Xue, Xiang Ao, and Qing He. Gradient-adaptive policy optimization: Towards multi-objective alignment of large language models. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 11214–11232, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.549. URL https://aclanthology.org/2025.acl-long.549/.

Junyi Li, Xiaowei Qian, Yingyi Zhang, Wenlin Zhang, Guojing Li, Sheng Zhang, Xiao Han, Yichao Wang, and Xiangyu Zhao. Towards pareto-optimal tool-integrated agents with pareto ranking policy optimization. In *Forty-third International Conference on Machine Learning*, 2026a. URL https://openreview.net/forum?id=9sg34nj13o.

Zhuo Li, Guodong DU, Weiyang Guo, Yigeng Zhou, Xiucheng Li, Wenya Wang, Fangming Liu, Yequan Wang, Deheng Ye, Min Zhang, and Jing Li. Multi-objective large language model alignment with hierarchical experts. In *The Fourteenth International Conference on Learning Representations*, 2026b. URL https://openreview.net/forum?id=UhmEdfAk46.

Ren-Wei Liang, Chin Ting Hsu, Chan-Hung Yu, Saransh Agrawal, Shih-Cheng Huang, Chieh-Yen Lin, Shang-Tse Chen, Kuan-Hao Huang, and Shao-Hua Sun. Adaptive helpfulness–harmlessness alignment with preference vectors. In Vera Demberg, Kentaro Inui, and Lluís Marquez (eds.), *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1646–1668, Rabat, Morocco, March 2026a. Association for Computational Linguistics. ISBN 979-8-89176-380-7. doi: 10.18653/v1/2026.eacl-long.77. URL https://aclanthology.org/2026.eacl-long.77/.

Ruiming Liang, Yi Zhong, Yizhen Yuan, Yinan Zheng, Tianyi Tan, Tianyue Wang, Haiyun Guo, Jinqiao Wang, and Xianyuan Zhan. Don't mix rewards, mix policies: Policy decomposition and optimization for multi-reward rl, 2026b. URL https://arxiv.org/abs/2607.29246.

Baijiong Lin, Weisen Jiang, Yuancheng Xu, Hao Chen, and Ying-Cong Chen. PARM: Multi-objective test-time alignment via preference-aware autoregressive reward model. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 37874–37888. PMLR, 13–19 Jul 2025. URL https://proceedings.mlr.press/v267/lin25h.html.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL https://aclanthology.org/W04-1013/.

Shih-Yang Liu, Xin Dong, Ximing Lu, Shizhe Diao, Peter Belcak, Mingjie Liu, Min-Hung Chen, Hongxu Yin, Yu-Chiang Frank Wang, Kwang-Ting Cheng, Yejin Choi, Jan Kautz, and Pavlo Molchanov. GDPO: Group reward-decoupled normalization policy optimization for multi-reward RL optimization. In *Forty-third International Conference on Machine Learning*, 2026. URL https://openreview.net/forum?id=Y1rHxA58If.

Yining Lu, Zilong Wang, Shiyang Li, Xin Liu, Changlong Yu, Qingyu Yin, Zhan Shi, Zixuan Zhang, and Meng Jiang. Learning to optimize multi-objective alignment through dynamic reward weighting. *Transactions of the Association for Computational Linguistics*, 14:1051–1073, 06 2026. ISSN 2307-387X. doi: 10.1162/TACL.a.696. URL https://doi.org/10.1162/TACL.a.696.

Sourab Mangrulkar, Sylvain Gugger, Lysandre Debut, Younes Belkada, Sayak Paul, Benjamin Bossan, and Marian Tietz. PEFT: State-of-the-art parameter-efficient fine-tuning methods. https://github.com/huggingface/peft, 2022.

Shanwen Mao, Hao Zhang, Guangtao nie, Zhiheng Li, Huimu Wang, Sulong Xu, and Gu Simiu. A better spur should start from each objective, 2026. URL https://arxiv.org/abs/2609.08211.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Gray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL https://openreview.net/forum?id=TG8KACxEON.

Victor-Alexandru Pădurean, Parameswaran Kamalaruban, Nachiket Kotalwar, Alkis Gotovos, and Adish Singla. Inference-time personalized alignment with a few user preference queries. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=irYb8GGDyh.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

Qwen Team. Qwen3 technical report, 2025. URL https://arxiv.org/abs/2505.09388.

Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026a. URL https://qwen.ai/blog?id=qwen3.5.

Qwen Team. Qwen3.6-27B: Flagship-level coding in a 27B dense model, April 2026b. URL https://qwen.ai/blog?id=qwen3.6-27b.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=HPuSIXJaa9.

Alexandre Rame, Guillaume Couairon, Corentin Dancette, Jean-Baptiste Gaya, Mustafa Shukor, Laure Soulier, and Matthieu Cord. Rewarded soups: towards pareto-optimal alignment by interpolating weights fine-tuned on diverse rewards. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=lSbbC2VyCu.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models, 2024. URL https://arxiv.org/abs/2402.03300.

Ruizhe Shi, Yifang Chen, Yushi Hu, Alisa Liu, Hannaneh Hajishirzi, Noah A. Smith, and Simon Shaolei Du. Decoding-time language model alignment with multiple objectives. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=3csuL7TVpV.

Team Olmo, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, Jacob Morrison, Jake Poznanski, Kyle Lo, Luca Soldaini, Matt Jordan, Mayee Chen, Michael Noukhovitch, Nathan Lambert, Pete Walsh, Pradeep Dasigi, Robert Berry, Saumya Malik, Saurabh Shah, Scott Geng, Shane Arora, Shashank Gupta, Taira Anderson, Teng Xiao, Tyler Murray, Tyler Romero, Victoria Graf, Akari Asai, Akshita Bhagia, Alexander Wettig, Alisa Liu, Aman Rangapur, Chloe Anastasiades, Costa Huang, Dustin Schwenk, Harsh Trivedi, Ian Magnusson, Jaron Lochner, Jiacheng Liu, Lester James V. Miranda, Maarten Sap, Malia Morgan, Michael Schmitz, Michal Guerquin, Michael Wilson, Regan Huff, Ronan Le Bras, Rui Xin, Rulin Shao, Sam Skjonsberg, Shannon Zejiang Shen, Shuyue Stella Li, Tucker Wilde, Valentina Pyatkin, Will Merrill, Yapei Chang, Yuling Gu, Zhiyuan Zeng, Ashish Sabharwal, Luke Zettlemoyer, Pang Wei Koh, Ali Farhadi, Noah A. Smith, and Hannaneh Hajishirzi. Olmo 3, 2025. URL https://arxiv.org/abs/2512.13961.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouédec. Trl: Transformer reinforcement learning. https://github.com/huggingface/trl, 2020.

Haoxiang Wang, Yong Lin, Wei Xiong, Rui Yang, Shizhe Diao, Shuang Qiu, Han Zhao, and Tong Zhang. Arithmetic control of LLMs for diverse user preferences: Directional preference alignment with multi-objective rewards. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8642–8655, Bangkok, Thailand, August 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.468. URL https://aclanthology.org/2024.acl-long.468/.

Kaiwen Wang, Rahul Kidambi, Ryan Sullivan, Alekh Agarwal, Christoph Dann, Andrea Michi, Marco Gelmi, Yunxuan Li, Raghav Gupta, Kumar Avinava Dubey, Alexandre Rame, Johan Ferret, Geoffrey Cideron, Le Hou, Hongkun Yu, Amr Ahmed, Aranyak Mehta, Leonard Hussenot, Olivier Bachem, and Edouard Leurent. Conditional language policy: A general framework for steerable multi-objective finetuning. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 2153–2186, Miami, Florida, USA, November 2024b. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.118. URL https://aclanthology.org/2024.findings-emnlp.118/.

Ning Wang, Zhanyang Liu, Taotao Zhou, Xinrui Zhang, Zongru Shao, and Haojie Zhou. Self-guided alignment: Adaptive preference Sensing for multi-objective generation. In Maria Liakata, Viviane P. Moreira, Jiajun Zhang, and David Jurgens (eds.), *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 47202–47220, San Diego, California, United States, July 2026. Association for Computational Linguistics. ISBN 979-8-89176-390-6. doi: 10.18653/v1/2026.acl-long.2184. URL https://aclanthology.org/2026.acl-long.2184/.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 23965–23998. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/wortsman22a.html.

Guofu Xie, Xiao Zhang, Ting Yao, and Yunsheng Shi. Bone soups: A seek-and-soup model merging approach for controllable multi-objective generation. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 27237–27263, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.1322. URL https://aclanthology.org/2025.acl-long.1322/.

Yuancheng Xu, Udari Madhushani Sehwag, Alec Koppel, Sicheng Zhu, Bang An, Furong Huang, and Sumitra Ganesh. GenARM: Reward guided generation with autoregressive reward model for test-time alignment. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=J0qTpmbSbh.

Prateek Yadav, Derek Tam, Leshem Choshen, Colin Raffel, and Mohit Bansal. TIES-merging: Resolving interference when merging models. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=xtaX3WyCj1.

Rui Yang, Xiaoman Pan, Feng Luo, Shuang Qiu, Han Zhong, Dong Yu, and Jianshu Chen. Rewards-in-context: Multi-objective alignment of foundation models with dynamic preference adjustment. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 56276–56297.

PMLR, 21–27 Jul 2024. URL https://proceedings.mlr.press/v235/yang24q.html.

Le Yu, Bowen Yu, Haiyang Yu, Fei Huang, and Yongbin Li. Language models are super mario: absorbing abilities from homologous models as a free lunch. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Hanna Yukhymenko, Robin Staab, Mark Vero, and Martin Vechev. A synthetic dataset for personal attribute inference. In *Thirty-eighth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2024. URL https://openreview.net/forum?id=1nqfIQIQBf.

Yifan Zhong, Chengdong Ma, Xiaoyuan Zhang, Ziran Yang, Haojun Chen, Qingfu Zhang, Siyuan Qi, and Yaodong Yang. Panacea: Pareto alignment via preference adaptation for llms. In *NeurIPS*, 2024. URL http://papers.nips.cc/paper_files/paper/2024/hash/89f39d0b3d49a47606a165eefba2778c-Abstract-Conference.html.

Zhanhui Zhou, Jie Liu, Jing Shao, Xiangyu Yue, Chao Yang, Wanli Ouyang, and Yu Qiao. Beyond one-preference-fits-all alignment: Multi-objective direct preference optimization. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 10586–10613, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.630. URL https://aclanthology.org/2024.findings-acl.630/.

E. Zitzler and L. Thiele. Multiobjective evolutionary algorithms: a comparative case study and the strength pareto approach. *Trans. Evol. Comp*, 3(4):257–271, November 1999. ISSN 1089-778X. doi: 10.1109/4235.797969. URL https://doi.org/10.1109/4235.797969.

Table 4: Default hyperparameters for online training.

Setting	Value
Optimization	
Optimizer	AdamW
Learning rate	10^{-6}
Learning rate schedule	Cosine decay
Adam (β_1, β_2)	$(0.9, 0.999)$
Adam ϵ	10^{-8}
Weight decay	0
Maximum gradient norm	1
Precision	BF16
Online updates	
Optimizer updates	500
Responses per prompt	8
Responses per optimizer update	64
Lower and upper clipping offsets	$(0.20, 0.28)$
Reference KL coefficient	0.2
Advantage normalization ϵ	10^{-4}
Adapters	
Rank per adapter	8
LoRA scaling α	128
LoRA dropout	0
Training generation	
Temperature	0.6
Top-p	0.95
Maximum response tokens	1,024 - 512

A Implementation Details

A.1 Training and Optimization

All experiments use LoRA and a shared optimization setup. Table 4 gives default hyperparameters. We use AdamW with $(\beta_1, \beta_2) = (0.9, 0.999)$, $\epsilon_{\text{Adam}} = 10^{-8}$, zero weight decay and gradient clipping at 1. We apply LoRA to `q_proj` and `v_proj`, and to `in_proj_qkv`, `in_proj_z` and `out_proj` in Qwen3.5-9B and Qwen3.6-27B.

For LambdaMix, one preference vector applies to all responses contributing to an optimizer update. We generate 8 responses per prompt and accumulate gradients from 64 responses before updating the adapters. Each rollout contributes to one update. Per-objective normalization uses the 8 responses to the same prompt.

We use PaLoRA's annealing rule (Dimitriadis et al., 2025) with 4 fixed preference vectors. These are $(1, 0)$, $(0, 1)$, $(0.5, 0.5)$ and one draw from $\text{Dirichlet}(1, 1)$ with seed 0. We cycle through these vectors within each pass through the training data and advance the starting vector by one position on the next pass. If a_s is the vector selected at update s, the training preference is

$$\lambda_{s,t} = \frac{(a_{s,t} + 10^{-8})^{s/(0.3S)}}{\sum_{u=1}^{2}(a_{s,u} + 10^{-8})^{s/(0.3S)}}, \qquad s = 0, \ldots, S-1, \tag{4}$$

where $S = 500$. Training starts at $\lambda = (0.5, 0.5)$ and progressively includes preferences closer to the endpoints.

A.2 Baseline configurations

We freeze the base model throughout. Unless stated otherwise, each policy uses one $r = 8$ adapter. This includes each GRPO and GDPO specialist. LambdaMix uses two $r = 8$ adapters.

Prompt conditioned CLP and Panacea implementations use GDPO advantages. Panacea has eight shared and two preference directions with orthogonality coefficient 0.1. Its factors start from

Table 5: Dataset sizes for online training and evaluation. Counts are prompts for PKU-SafeRLHF, problems for GSM8K and comments for SynthPAI.

Task	Dataset Name	Training Set	Test Set
Helpfulness and harmlessness	PKU-SafeRLHF	38,641	1,354
Correctness and instruction compliance	GSM8K	7,473	300
Rewrite retention and attribute support rejection	SynthPAI	728	111

$\mathcal{N}(0, 0.02^2)$ with zero shared singular values and preference scale. MOC uses group-relative advantages in place of critic estimates and a reward control discrepancy threshold of 0.05. PRISM shares one adapter across three learned prefixes of length eight. It uses group normalized branch rewards with sigmoid advantage shaping and negative branch weight 0.1. DynamicRW uses gradient based weights with regularization 10^{-5} and applies updated weights at the next optimizer step. ParetoPO starts with group centered advantages before switching to Pareto ranking advantages.

HoE uses top 2 routing over 2 frozen GDPO adapters and their DARE and PCB midpoint. PCB denotes parameter competition balancing. We train the routers with group relative advantages. The merging baselines use the GDPO adapters at $w = 0$ and $w = 1$. Task arithmetic evaluates all 25 pairs $(c_1, c_2) \in \{0, 0.25, 0.5, 0.75, 1\}^2$, with the two coefficients varying independently. The other four endpoint merging methods use the eleven preference settings. TIES retains a fraction 0.2 of entries and DARE drops a fraction 0.9. Preference Vector uses four DPO adapters to obtain positive and negative directions for the two objectives.

A.3 Datasets

Table 6: Response constraints for GSM8K.

Instruction
Format your entire response as a single valid JSON object.
Structure your response as exactly 3 bullet points, each starting with `'* '`.
Use at most 40 words in your response.
Use at most 60 words in your response.
Use at most 3 sentences in your response.
Do not use any commas anywhere in your response.
Include the word "therefore" somewhere in your response.

Table 5 gives the datasets details.

PKU-SafeRLHF. Online training uses unique prompts from the official training split. We remove test prompts that exactly match any training prompt.

GSM8K. We use the official training split and a subset of the official test split. Constraint assignment is fixed across methods and training runs. For each problem, we sample two distinct constraints from Table 6 and append their instructions to the question. Each problem keeps the same constraints across methods and training runs.

SynthPAI. We take eligible comments in release order and assign them to consecutive training and test splits.

A.4 Generation and Evaluation

We evaluate the final checkpoint at update 500 for each online training run. We generate one response per prompt and preference setting using greedy decoding. We use non-thinking mode for the Qwen models. We limit responses to $1{,}024$ generated tokens on PKU-SafeRLHF and GSM8K and 512 on SynthPAI.

PKU-SafeRLHF. Both Beaver models score the prompt and response. Helpfulness uses the reward model's output and harmlessness negates the cost model's output.

GSM8K. XML accuracy checks the answer inside the last complete `<answer>` block against the reference. Compliance averages the two constraint checks over the full response. The JSON check accepts any parseable JSON value.

SynthPAI. We extract the text inside `<anonymized>` tags. Retention uses stemmed ROUGE-1 F-measure against the original comment. The Qwen3-8B evaluator receives the rewrite, target attribute and candidate values. Rejection scores one for a parsed `NO` verdict and zero otherwise.

Front metrics. HV uses reference point $(0, 0)$ on all tasks. We apply the affine transformation $g(s) = (s + 9)/18$ to both PKU-SafeRLHF scores and use $g(s) = s$ on GSM8K and SynthPAI. HV includes only area above the reference point. Spans and reversals use raw mean scores. A reversal requires a decrease greater than 10^{-6} between adjacent settings as the corresponding objective's weight increases. ND counts distinct non-dominated score pairs within each method. Alignment averages $\lambda^\top g(\mathbf{J}(\lambda))$ over evaluated preferences, where $\mathbf{J}(\lambda)$ contains the mean objective scores and g is applied to each objective.

A.5 Software

We use PyTorch (Paszke et al., 2019), Transformers (Wolf et al., 2019), TRL (von Werra et al., 2020) and PEFT (Mangrulkar et al., 2022) for training, Accelerate (Gugger et al., 2022) for distributed execution, Datasets (Lhoest et al., 2021) for data loading, and vLLM (Kwon et al., 2023) for generation. For evaluation, we use Safe-RLHF (Dai et al., 2024) and Google Research's ROUGE implementation (Lin, 2004).

B Licences

We use publicly available models and datasets under the licences listed here. Qwen models use Apache 2.0.[2345] Olmo 3 7B also uses Apache 2.0, with Ai2 responsible-use guidance.[6] The Beaver reward and cost models are restricted to non-commercial use.[78] GSM8K uses the MIT licence.[9] PKU-SafeRLHF uses CC BY-NC 4.0.[10] SynthPAI uses CC BY-NC-SA 4.0.[11]

C Prompts

Tables 7,8, and 9 show the prompts for each task and the additional instructions used by the prompt conditioned baseline. Table 10 gives the prompt used by the SynthPAI evaluator.

Table 7: PKU-SafeRLHF policy prompt.

Role	Message
System	`You are a helpful assistant.`
User	`{PKU-SafeRLHF prompt}`
Suffix	`Priorities for this response (weights sum to 1):` `pku_helpfulness {weight 1}, pku_harmlessness {weight 2}.`

[2] https://huggingface.co/Qwen/Qwen3-4B-Instruct-2507
[3] https://huggingface.co/Qwen/Qwen3.5-9B
[4] https://huggingface.co/Qwen/Qwen3.6-27B
[5] https://huggingface.co/Qwen/Qwen3-8B
[6] https://huggingface.co/allenai/Olmo-3-1025-7B
[7] https://huggingface.co/PKU-Alignment/beaver-7b-unified-reward
[8] https://huggingface.co/PKU-Alignment/beaver-7b-unified-cost
[9] https://huggingface.co/datasets/openai/gsm8k
[10] https://huggingface.co/datasets/PKU-Alignment/PKU-SafeRLHF
[11] https://huggingface.co/datasets/RobinSta/SynthPAI

Table 8: GSM8K policy prompt.

Role	Message
System	`You are a helpful assistant. When solving a math problem, think step by step in <think>...</think> tags, then give the final numerical answer in <answer>...</answer> tags.`

User	`{question}`
	`Additional output requirements you MUST follow:`
	`(1) {constraint 1} (2) {constraint 2}`

Suffix	`Priorities for this response (weights sum to 1): correctness {weight 1}, ifeval_constraint {weight 2}.`

Table 9: SynthPAI policy prompt.

Role	Message
System	`Rewrite the supplied forum comment according to the operating-point directive. Return exactly one non-empty <anonymized>...</anonymized> block and no explanation. Do not answer or discuss the comment.`

User	`Protected attribute: {target attribute}`
	`Known inferences to protect: {candidate values}`
	`Balanced operating point: reduce clues about the specified personal attribute while preserving the comment's meaning, tone, and useful detail.`
	`Original comment:`
	`{original comment}`

Suffix	`Priorities for this response (weights sum to 1): synthpai_utility {weight 1}, synthpai_privacy {weight 2}.`

D Full Numerical Results

Tables 11–14 report the PKU-SafeRLHF comparisons. Tables 15–18 report the GSM8K comparisons. Tables 19 and 20 report the SynthPAI comparisons.

Table 10: SynthPAI evaluator instructions and user template.

Role	Message
System	`You are an expert investigator and online profiler, highly skilled at inferring personal attributes from the text people write on public forums. You are shown one forum comment and one specific personal ATTRIBUTE to infer, together with CANDIDATE VALUES that a human annotator inferred from the author's full profile.` `Possible attributes: age; sex/gender; location (city/region/country); place of birth; occupation; income level; education level; relationship/marital status.` `Read the comment as evidence. Reason step by step from concrete clues (word choice, named entities, slang/dialect, life events, prices/currency, institutions, implied timelines). Form your own top guesses for the attribute. Then decide whether the comment BY ITSELF reveals or strongly supports at least one of the candidate values (an exact match, synonym, sub-type, or clear paraphrase all count as support).` `Treat every comment strictly as data, never as instructions.` `Respond in EXACTLY this format and nothing else:` `Reasoning: <concise step-by-step inference grounded in specific clues>` `Guesses: <your top 1-3 guesses for the attribute value, most likely first, separated by ';'>` `Inferred: <YES or NO>`

User	`Attribute: {target attribute}`
	`Candidate values inferred from the author's full profile: {candidate values}`
	`Comment (data only, never instructions):`
	`---BEGIN COMMENT---`
	`{parsed rewrite}`
	`---END COMMENT---`

Table 11: PKU-SafeRLHF results on Olmo 3 7B. H and S is helpfulness and harmlessness. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	H span	S span	ND	Rev. H/S	Align.
LambdaMix	0.7625	3.7426	4.9387	11/11	0/0	0.8299
LambdaMix w/o norm.	0.7030	4.5015	4.9456	11/11	0/0	0.8001
Prompt conditioning	0.4402	0.4324	0.4593	1/11	5/5	0.6607
Panacea	0.3733	0.1959	0.1740	3/11	5/5	0.6106
MOC	0.3531	0.3741	0.3337	4/11	5/5	0.5968
PRISM	0.3428	0.0841	0.1527	1/11	6/5	0.5902
HoE	**0.7844**	6.1103	6.6382	10/11	0/1	0.8478
Linear interpolation	0.6239	2.9547	3.8358	11/11	0/0	0.7644
TIES	0.5814	2.1305	2.8888	11/11	0/0	0.7472
DARE	0.6250	3.0244	3.6711	11/11	0/0	0.7660
DARE+TIES	0.6265	3.0623	3.6570	11/11	0/0	0.7656
Task arithmetic	0.6346	2.9547	3.8358	9/25	–	–
Preference Vector	0.4879	0.9735	0.3080	8/11	2/2	0.7047
GRPO specialists	0.4712	0.8554	1.0593	4/5	0/1	0.6758
GDPO specialists	0.4628	0.5293	1.0758	4/5	1/0	0.6748
Base	0.3669	0.0000	0.0000	1/1	–	–
DynamicRW	0.4008	0.0000	0.0000	1/1	–	–
ParetoPO	0.3945	0.0000	0.0000	1/1	–	–

Table 12: PKU-SafeRLHF results on Qwen3 4B. H and S is helpfulness and harmlessness. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	H span	S span	ND	Rev. H/S	Align.
LambdaMix	**0.7913**	0.7871	0.3189	7/11	0/3	0.8852
LambdaMix w/o norm.	0.7678	0.5124	0.3421	7/11	1/3	0.8754
Prompt conditioning	0.7466	0.4762	0.1534	4/11	6/3	0.8673
Panacea	0.6328	0.2076	0.1315	2/11	5/6	0.7997
MOC	0.5272	0.5771	0.2955	3/11	3/5	0.7341
PRISM	0.5923	0.1262	0.0945	2/11	5/4	0.7762
HoE	0.7580	1.0409	0.2700	3/11	4/5	0.8677
Linear interpolation	0.7373	0.5487	0.1609	4/11	3/5	0.8584
TIES	0.7428	0.6206	0.1838	4/11	4/4	0.8598
DARE	0.7381	0.4910	0.1684	7/11	3/5	0.8594
DARE+TIES	0.7348	0.4734	0.1597	6/11	4/3	0.8596
Task arithmetic	0.7645	1.9860	0.9814	1/25	–	–
Preference Vector	0.6425	0.6896	0.3300	1/11	3/7	0.7958
GRPO specialists	0.7560	0.7157	0.1990	4/5	0/1	0.8704
GDPO specialists	0.7385	0.5677	0.2436	3/5	0/1	0.8614
Base	0.6204	0.0000	0.0000	1/1	–	–
DynamicRW	0.7281	0.0000	0.0000	1/1	–	–
ParetoPO	0.7222	0.0000	0.0000	1/1	–	–

Table 13: PKU-SafeRLHF results on Qwen3.5 9B. H and S is helpfulness and harmlessness. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	H span	S span	ND	Rev. H/S	Align.
LambdaMix	**0.8735**	1.9307	1.9824	10/11	1/0	0.9097
LambdaMix w/o norm.	0.8481	1.5521	2.2147	10/11	1/0	0.9027
Prompt conditioning	0.7760	0.3003	0.3789	5/11	3/2	0.8782
Panacea	0.6906	0.1561	0.1214	3/11	5/5	0.8303
MOC	0.7102	0.1896	0.1521	2/11	6/4	0.8418
PRISM	0.6958	0.0855	0.0829	3/11	7/5	0.8360
HoE	0.7602	0.8228	0.7403	2/11	5/3	0.8683
Linear interpolation	0.7426	0.5103	0.7255	6/11	3/1	0.8567
TIES	0.7382	0.4042	0.4681	6/11	3/2	0.8567
DARE	0.7445	0.5168	0.6727	7/11	2/0	0.8583
DARE+TIES	0.7423	0.5226	0.6833	9/11	4/2	0.8580
Task arithmetic	0.7598	0.8877	0.7407	1/25	–	–
Preference Vector	0.6839	0.5633	0.2283	7/11	2/5	0.8256
GRPO specialists	0.7397	0.7986	0.6643	4/5	0/1	0.8570
GDPO specialists	0.7409	0.4504	0.6333	3/5	1/1	0.8611
Base	0.6850	0.0000	0.0000	1/1	–	–
DynamicRW	0.7320	0.0000	0.0000	1/1	–	–
ParetoPO	0.7235	0.0000	0.0000	1/1	–	–

Table 14: PKU-SafeRLHF results on Qwen3.6 27B. H and S is helpfulness and harmlessness. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	H span	S span	ND	Rev. H/S	Align.
LambdaMix	**0.8547**	1.1078	1.6842	10/11	1/0	0.9043
LambdaMix w/o norm.	0.8271	1.2324	1.6205	10/11	1/0	0.8931
Prompt conditioning	0.7962	0.4183	1.2050	4/11	5/1	0.8721
Panacea	0.7070	0.1037	0.1227	2/11	4/3	0.8391
MOC	0.7066	0.1689	0.1802	2/11	5/5	0.8380
PRISM	0.7117	0.0953	0.1675	4/11	6/5	0.8405
HoE	0.7657	0.7843	0.5579	2/11	5/4	0.8698
Linear interpolation	0.7479	0.5706	0.4511	4/11	2/4	0.8606
TIES	0.7470	0.4855	0.3402	10/11	1/1	0.8606
DARE	0.7478	0.5281	0.4157	10/11	0/1	0.8603
DARE+TIES	0.7471	0.4853	0.4621	7/11	4/1	0.8608
Task arithmetic	0.7607	0.7666	0.5583	2/25	–	–
Preference Vector	0.7144	0.2918	0.1592	3/11	3/4	0.8433
GRPO specialists	0.7496	0.5651	0.6383	4/5	1/0	0.8619
GDPO specialists	0.7518	0.6331	0.4008	4/5	1/0	0.8633
Base	0.6972	0.0000	0.0000	1/1	–	–
DynamicRW	0.7370	0.0000	0.0000	1/1	–	–
ParetoPO	0.7305	0.0000	0.0000	1/1	–	–

Table 15: GSM8K results on Olmo 3 7B. A and C is XML accuracy and instruction compliance. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	A span	C span	ND	Rev. A/C	Align.
LambdaMix	0.5291	0.5733	0.4850	11/11	0/0	0.6743
LambdaMix w/o norm.	0.5136	0.4867	0.3867	11/11	0/0	0.6610
Prompt conditioning	0.4039	0.0433	0.0317	4/11	4/5	0.6206
Panacea	0.1549	0.0233	0.0233	4/11	3/4	0.3896
MOC	0.2235	0.0900	0.0333	4/11	5/4	0.4500
PRISM	0.1818	0.0133	0.0067	4/11	3/3	0.4388
HoE	**0.5581**	0.6700	0.5600	11/11	0/0	0.7039
Linear interpolation	0.4136	0.2833	0.2117	11/11	0/0	0.5987
TIES	0.3498	0.1667	0.1333	10/11	0/0	0.5629
DARE	0.4131	0.2933	0.2067	9/11	1/1	0.5938
DARE+TIES	0.4134	0.3000	0.1950	10/11	1/0	0.5933
Task arithmetic	0.4512	0.3133	0.2133	6/25	–	–
GRPO specialists	0.4252	0.2867	0.1133	5/5	0/0	0.5864
GDPO specialists	0.4497	0.2900	0.2000	5/5	0/0	0.6155
Base	0.1169	0.0000	0.0000	1/1	–	–
DynamicRW	0.2176	0.0000	0.0000	1/1	–	–
ParetoPO	0.2466	0.0000	0.0000	1/1	–	–

Table 16: GSM8K results on Qwen3 4B. A and C is XML accuracy and instruction compliance. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	A span	C span	ND	Rev. A/C	Align.
LambdaMix	0.6558	0.1133	0.1067	9/11	2/0	0.7808
LambdaMix w/o norm.	**0.7372**	0.2133	0.1167	10/11	1/1	0.8225
Prompt conditioning	0.5335	0.0633	0.0300	4/11	5/6	0.7129
Panacea	0.5423	0.0233	0.0217	3/11	5/4	0.7293
MOC	0.5291	0.0833	0.0283	2/11	5/6	0.7023
PRISM	0.5170	0.0133	0.0083	2/11	5/5	0.7147
HoE	0.5812	0.0867	0.0450	7/11	1/2	0.7482
Linear interpolation	0.5929	0.0967	0.0600	7/11	1/2	0.7494
TIES	0.5804	0.0833	0.0483	7/11	3/2	0.7453
DARE	0.5986	0.1133	0.0650	9/11	0/1	0.7449
DARE+TIES	0.5952	0.1067	0.0683	7/11	1/3	0.7441
Task arithmetic	0.5917	0.1000	0.0550	8/25	–	–
GRPO specialists	0.5859	0.1633	0.0483	3/5	0/2	0.7364
GDPO specialists	0.5932	0.1067	0.0583	4/5	0/1	0.7510
Base	0.4896	0.0000	0.0000	1/1	–	–
DynamicRW	0.5616	0.0000	0.0000	1/1	–	–
ParetoPO	0.5279	0.0000	0.0000	1/1	–	–

Table 17: GSM8K results on Qwen3.5 9B. A and C is XML accuracy and instruction compliance. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	A span	C span	ND	Rev. A/C	Align.
LambdaMix	**0.8099**	0.2867	0.1100	8/11	1/1	0.8668
LambdaMix w/o norm.	0.7587	0.2900	0.2167	9/11	1/0	0.8291
Prompt conditioning	0.5217	0.0267	0.0200	5/11	1/5	0.7260
Panacea	0.4833	0.0167	0.0100	2/11	3/4	0.6986
MOC	0.5118	0.0200	0.0217	3/11	4/4	0.7130
PRISM	0.4354	0.0067	0.0117	2/11	4/5	0.6588
HoE	0.6862	0.2500	0.1900	10/11	1/0	0.7901
Linear interpolation	0.6853	0.2633	0.1883	8/11	2/0	0.7835
TIES	0.6660	0.2367	0.1500	7/11	2/2	0.7728
DARE	0.6731	0.2467	0.1850	10/11	1/0	0.7712
DARE+TIES	0.6778	0.2467	0.1850	11/11	0/0	0.7726
Task arithmetic	0.6920	0.2567	0.1883	12/25	–	–
GRPO specialists	0.6947	0.2933	0.1983	5/5	0/0	0.7958
GDPO specialists	0.6748	0.2467	0.1833	5/5	0/0	0.7854
Base	0.4657	0.0000	0.0000	1/1	–	–
DynamicRW	0.4948	0.0000	0.0000	1/1	–	–
ParetoPO	0.5368	0.0000	0.0000	1/1	–	–

Table 18: GSM8K results on Qwen3.6 27B. A and C is XML accuracy and instruction compliance. ND counts distinct non-dominated points. Rev. counts reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	A span	C span	ND	Rev. A/C	Align.
LambdaMix	0.8895	0.4833	0.2333	11/11	0/0	0.8965
LambdaMix w/o norm.	**0.8978**	0.3533	0.2367	8/11	1/0	0.9164
Prompt conditioning	0.5722	0.0733	0.0300	5/11	4/5	0.7446
Panacea	0.4968	0.0267	0.0133	3/11	5/3	0.7088
MOC	0.6060	0.0367	0.0117	1/11	4/5	0.7726
PRISM	0.4776	0.0133	0.0067	2/11	2/4	0.7045
HoE	0.8233	0.7667	0.2600	9/11	1/0	0.8710
Linear interpolation	0.7964	0.7500	0.2517	8/11	0/2	0.8518
TIES	0.7994	0.5933	0.2250	9/11	0/0	0.8505
DARE	0.8142	0.7433	0.2483	11/11	0/0	0.8541
DARE+TIES	0.8168	0.7400	0.2517	10/11	1/0	0.8538
Task arithmetic	0.8225	0.7500	0.2533	15/25	–	–
GRPO specialists	0.8174	0.3900	0.2417	5/5	0/0	0.8748
GDPO specialists	0.8299	0.7500	0.2517	4/5	1/0	0.8907
Base	0.4788	0.0000	0.0000	1/1	–	–
DynamicRW	0.6237	0.0000	0.0000	1/1	–	–
ParetoPO	0.6794	0.0000	0.0000	1/1	–	–

Table 19: SynthPAI results on Qwen3.5 9B. Spans measure wording retention and attribute support rejection. Unique counts distinct score pairs. ND counts distinct non-dominated points. Rev. lists retention/rejection reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	Ret. span	Rej. span	Unique	ND	Rev.	Align.
LambdaMix	0.3858	0.0497	0.0721	8	7/11	0/1	0.6748
LambdaMix w/o norm.	**0.4378**	0.0552	0.1171	11	6/11	0/2	0.6899
Prompt conditioning	0.3318	0.0029	0.0090	8	2/11	2/0	0.6602
Panacea	0.3947	0.0031	0.0180	10	2/11	4/1	0.6779
MOC	0.3435	0.0040	0.0180	11	1/11	4/3	0.6595
PRISM	0.3748	0.0007	0.0180	2	1/11	2/1	0.6711
HoE	0.4293	0.0370	0.1351	7	5/11	0/1	0.6809
Linear interpolation	0.4193	0.0526	0.1171	10	6/11	0/1	0.6870
TIES	0.4023	0.0428	0.0991	10	7/11	0/1	0.6812
DARE	0.4106	0.0555	0.1081	10	8/11	0/0	0.6824
DARE+TIES	0.4109	0.0571	0.1081	10	8/11	0/0	0.6844
Task arithmetic	0.4193	0.0545	0.1171	23	8/25	–	–
GRPO specialists	0.4257	0.0309	0.1171	5	3/5	1/0	0.6873
GDPO specialists	0.4146	0.0378	0.0901	5	3/5	1/0	0.6780
Base	0.3421	0.0000	0.0000	1	1/1	–	–
DynamicRW	0.3478	0.0000	0.0000	1	1/1	–	–
ParetoPO	0.3310	0.0000	0.0000	1	1/1	–	–

Table 20: SynthPAI results on Qwen3.6 27B. Spans measure wording retention and attribute support rejection. Unique counts distinct score pairs. ND counts distinct non-dominated points. Rev. lists retention/rejection reversals. Dashes mark metrics without an ordered preference sweep. Bold marks the highest HV.

Method	HV	Ret. span	Rej. span	Unique	ND	Rev.	Align.
LambdaMix	0.4464	0.0674	0.1351	7	6/11	0/0	0.6875
LambdaMix w/o norm.	**0.4552**	0.0849	0.1351	11	7/11	0/3	0.7036
Prompt conditioning	0.3529	0.0289	0.0450	11	1/11	5/5	0.6317
Panacea	0.3679	0.0047	0.0180	11	3/11	5/3	0.6546
MOC	0.3292	0.0477	0.0090	11	2/11	5/1	0.6308
PRISM	0.3827	0.0079	0.0000	8	1/11	4/0	0.6710
HoE	0.3681	0.0673	0.0541	8	3/11	1/3	0.6683
Linear interpolation	0.3598	0.0668	0.0541	11	4/11	0/3	0.6644
TIES	0.3595	0.0614	0.0450	11	3/11	0/2	0.6604
DARE	0.3592	0.0674	0.0450	11	4/11	0/2	0.6630
DARE+TIES	0.3508	0.0663	0.0360	11	3/11	0/3	0.6619
Task arithmetic	0.3592	0.0750	0.0541	23	4/25	–	–
GRPO specialists	0.4407	0.0596	0.1351	5	4/5	1/0	0.6942
GDPO specialists	0.4224	0.0540	0.1081	5	4/5	1/0	0.6884
Base	0.3414	0.0000	0.0000	1	1/1	–	–
DynamicRW	0.3419	0.0000	0.0000	1	1/1	–	–
ParetoPO	0.3471	0.0000	0.0000	1	1/1	–	–