FORECASTING PERSONA DRIFT IN LANGUAGE MODELS BEFORE GENERATION

Anonymous authors
Paper under double-blind review

ABSTRACT

Language models used in continuing agent tasks may need to maintain an assigned persona over many turns. Detecting persona drift only after a response has been generated leaves no opportunity to inspect the risk before that response. Yet change alone is not evidence of drift: new task information can justify a different judgment without changing the assigned behavioral principle. We study whether sustained persona drift can be forecast before the next response is generated. Our method learns the internal state expected when the persona is maintained under the current dialogue and task conditions, together with its normal variation. It combines deviations from this stable behavior reference with their recent history and available dialogue to predict sustained drift. Experiments cover three sizes of Qwen2.5-Instruct and Gemma-3-4B-it. The method improves prediction over text and raw state baselines. Under a requirement to warn one full turn in advance, it reduces false warnings on justified updates while meeting the required recall and overall false warning limits. The reduction remains with task states inferred from raw dialogue and under adaptive dialogue structure, but weakens when that inference is wrong or unavailable. These results support monitoring persona stability before generation while allowing reasonable changes in judgment.

1 INTRODUCTION

Language models used in long conversations and agent systems may need to maintain an assigned persona: the role and expected behavior specified for the interaction. Persona stability does not require an unchanged answer. An agent instructed to prefer the option with lower risk may first choose A, then reasonably choose B when new information shows that B is safer. The decision changes while the principle remains intact. Prior work studies instruction persistence and responses to social pressure (Li et al., 2024; Hong et al., 2025), while representation studies identify directions associated with behavior and persona (Zou et al., 2023; Chen et al., 2025; Lu et al., 2026). These approaches reveal changes, but change alone does not establish persona drift. An agent can remain fluent and helpful while abandoning its decision rule. Conversely, changing an earlier answer may be exactly what that rule requires after a factual correction. The relevant question is whether the assigned principle continues to guide the decision.

Two problems motivate our study. The first is timing. Once a response has departed from the assigned persona, it may already have reached a user or another component of an agent system. Prediction before generation could create an opportunity for inspection before this happens. Recent studies show that internal states can predict future behavior or task success (Ashok & May, 2025; Lugoloobi et al., 2026). The second problem is distinguishing drift from justified adaptation. New task information and repeated pressure can both move internal states, but only the former may justify a revised judgment. Pressure can instead induce a change without a valid reason (Hong et al., 2025; Tan et al., 2025). A useful warning must distinguish these situations rather than penalize every change.

We learn a *stable behavior reference*: the internal state pattern expected when the assigned behavioral principle is maintained under the current conditions. Stable conversations can include justified changes in judgment. The reference predicts both the expected state and its normal variation. A forecasting model combines deviations from this pattern with their recent history and the available dialogue. All inputs are available before the next response is generated. The reference can shift its expected state or allow more variation when stable conversations normally respond to new information.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

The forecasting model then assesses whether the remaining deviation signals future sustained drift. Across three Qwen2.5-Instruct sizes and Gemma-3-4B-it, the reference improves prediction over text and raw state baselines. On Qwen2.5-7B-Instruct it reaches average precision 0.719, compared with 0.568 for semantic text and 0.670 for recurrent prediction from raw states. It also reduces false warnings on justified updates under a fixed requirement for advance warning. Separate behavioral judgments and transfer tests examine whether this reduction persists when the assessment, principles, dialogue structure, or access to task information changes. We also test a dialogue-only verifier and an adaptive simulated dialogue collection so that the main robustness evidence does not rely only on record-derived task-state access.

Our contributions are as follows:
• We formulate persona drift as a forecasting problem. The monitor forecasts sustained drift before each next response and separately reports how often the warning precedes the first violating response.
• We introduce a stable behavior reference that describes the expected internal state and its normal variation, including judgment changes supported by new task information.
• We evaluate prediction, false warnings on justified updates, and warning lead separately, and test the findings with a second behavioral assessment and changed dialogue settings.
• We identify a direction for monitoring persona drift in continuing agent tasks, where earlier warnings provide an opportunity for inspection or intervention before a violation appears in the output.

2 Related Work

Persona stability and social pressure. Studies of instruction persistence and sycophancy examine behavior across repeated interactions (Li et al., 2024; Hong et al., 2025). The Assistant Axis studies drift from a default Assistant persona and constrains activations to stabilize it (Lu et al., 2026). Public behavioral evaluations provide tasks for identifying recurring model behaviors (Perez et al., 2023). We instead study an assigned behavioral principle that should persist across a continuing task. This differs from preserving a default persona or repeating an initial answer: the agent must allow factual corrections while resisting pressure to abandon the principle.

Internal states and prediction before generation. Representation Engineering and Persona Vectors identify behavioral directions (Zou et al., 2023; Chen et al., 2025). Prediction from input representations can anticipate model behavior (Ashok & May, 2025) and success in mathematics and code (Lugoloobi et al., 2026). Anomaly detection also learns normal patterns to identify departures (Malhotra et al., 2015). Our setting differs from unsupervised anomaly detection because the stable historical pool is behaviorally screened and the forecasting target is supervised. These studies motivate using internal states as a source of advance warning. Our experiments therefore include direct persona-direction monitoring controls derived from Development-only maintained-versus-violation contrasts, alongside full-width and nonlinear raw-state predictors. Our target is future sustained persona drift, not general task success or state movement alone. We define normality through maintenance of the assigned principle. The stable reference therefore includes justified changes rather than treating adaptation as an anomaly.

Task information and warning decisions. Fact verification distinguishes supported, contradicted, and unresolved claims (Thorne et al., 2018). We additionally assess whether information justifies a change under the assigned principle. Probability calibration and constrained classification distinguish risk ranking from operating error (Guo et al., 2017; Tong et al., 2018). Accordingly, we measure prediction, false warnings, and advance warning separately.

3 Method

We forecast sustained persona drift using information available before the next response. Figure 1 summarizes reference learning, risk prediction, and warning decisions.

3.1 Persona Drift and Prediction Target

Each conversation assigns a persona whose behavior is evaluated through an explicit principle. For response t, $V_t = 1$ denotes an unjustified violation of that principle. Separately, $J_t = 1$ denotes a



Figure 1: Learning and forecasting persona drift before generation. A stable behavior reference estimates the internal state expected under the current dialogue and task conditions together with its normal variation. Drift forecasting combines standardized deviations from this reference with recent deviation history and available dialogue information. An alarm requires two consecutive calibrated risks above the selected cutoff. The lower panel shows the offline fitting and calibration stages. All inputs used for response t are available before that response is generated; V_t and J_t are used only for offline supervision and evaluation.

change in judgment or action supported by relevant task information available at that turn. We call this a *justified update*. Both labels can be positive when one part of a response makes a justified change while another violates a separate requirement.

We distinguish an isolated violation from sustained drift:

$$T_{\text{first}} = \min\{t : V_t = 1\}, \quad T = \min\{t : V_t = V_{t+1} = 1\}, \quad T_{\text{confirm}} = T + 1. \tag{1}$$

Here, T_{first} denotes the first observed violation. The sustained onset T is the first response in the first pair of consecutive violations. The next response confirms the event. We retain the two-consecutive endpoint for its persistence interpretation rather than because it maximizes Test performance; Appendix C.10 reports alternative definitions. Unknown judgments are not negative labels and cannot connect violations across a missing judgment. Appendix B.5 specifies the rules for incomplete observation.

Before response t, the available information is

$$\mathcal{F}_t = \sigma(p, x, u_{1:t}, r_{1:t-1}, z_{1:t}, c_{1:t}), \tag{2}$$

where p is the persona specification, x the task case, and u and r the user and agent messages. The projected internal state z_t is obtained before generation; c_t contains the current task information and dialogue conditions. The forthcoming response r_t is excluded. Behavioral judgments V_t and J_t supervise offline construction and evaluation and are not members of $\mathcal{F}_t$. Our horizon is $H = 5$: a prediction made before response t concerns sustained onset during responses $t, \ldots, t+4$.

3.2 Learning Stable Behavior

The *stable behavior reference* describes the internal state expected when the assigned principle is maintained under the current conditions. Both the expected state and its normal variation can change when new task information arrives. This is supervised forecasting with a curated stable reference: historical conversations are behaviorally screened, while online forecasting uses only pre-response inputs.

Reference fitting uses conversations that pass the initial persona check, have complete violation coverage, and contain no sustained drift. Justified updates remain eligible. Stability is defined by

these observed judgments, not by an assumed fixed internal state. Appendix A.3 gives the eligibility rules. We extract a state at the last prompt position before generation and project it to sixteen coordinates. The projection is fitted on reference data and then frozen separately for each subject model (Appendix B.1).

The reference predicts the current state from previous states and current conditions. A gated recurrent unit (GRU) maintains a hidden summary h_t:

$$h_t = \mathrm{GRU}_\theta([z_{t-1}; c_t], h_{t-1}), \qquad (\mu_t, \log \sigma_t^2) = g_\theta(h_t), \tag{3}$$

$$\mathcal{L}_S = \frac{1}{2} \sum_{i,t,k} \left[\frac{(z_{itk} - \mu_{itk})^2}{\sigma_{itk}^2} + \log \sigma_{itk}^2 \right]. \tag{4}$$

Here, θ contains the learned parameters, and g_θ maps the hidden summary to a mean μ_t and variance σ_t^2. The indices i, t, and k denote conversations, turns, and state coordinates. The mean describes the expected stable state; the scale σ_t describes its normal variation. The Gaussian loss penalizes prediction error while its log variance term discourages an arbitrarily large scale. The current state z_t is a prediction target, not an input to this reference update. Appendix B.3 gives the implementation and selection rules.

We compare the observed state with the reference through

$$e_t = \mathrm{diag}(\sigma_t)^{-1}(z_t - \mu_t), \qquad E_{t,5} = [e_{t-4}^\top, \ldots, e_t^\top]^\top. \tag{5}$$

The deviation e_t measures the current state relative to its expected location and normal variation. A given raw difference is more unusual when normal variation is small. $E_{t,5}$ contains the current deviation and the previous four. A large raw change need not be unusual if similar changes occur during stable behavior under those conditions. Conversely, a modest change can be unusual when the stable state normally varies little. This comparison allows expected adaptation without assuming that all movement is harmless. Appendix B.6 formalizes the normalization and bounds the effect of reference estimation error.

3.3 Forecasting Future Drift

Unusual states need not imply future drift. We therefore fit a separate predictor using a feature vector ϕ_t that combines current conditions, available text, e_t, recent deviation summaries, and distances from the stable reference. The history summaries include the recent mean deviation and its change over five turns. We also include a distance that uses covariance estimated from stable windows to measure how unusual the joint deviation is. A margin derived from this distance is an input feature, not a probability of drift. The forecasting model learns how these features relate to later sustained drift. Appendix B.4 specifies the construction.

A discrete time hazard model (Kvamme & Borgan, 2021) estimates

$$\begin{aligned} q_{j|t} &= P(T = t + j - 1 \mid T \geq t + j - 1, \mathcal{F}_t) = \mathrm{sigmoid}(\beta^\top \phi_t + \gamma_j), \\ R_t^{(H)} &= 1 - \prod_{j=1}^{H} (1 - q_{j|t}), \qquad j = 1, \ldots, H. \end{aligned} \tag{6}$$

The coefficients β are shared across forecast steps; γ_j is an offset for step j. Each $q_{j|t}$ gives onset risk conditional on no earlier onset, and $R_t^{(H)}$ gives risk over the next H responses, including response t. Every factor uses the same $\mathcal{F}_t$: no future state or response enters later steps. Training uses only forecast steps whose outcomes are observed and stops at onset or the last reliable observation. Missing outcomes are not treated as negatives (Appendix B.5). Multiple prediction points can come from one conversation. Their overlap is retained during fitting but is not treated as independent replication when uncertainty is estimated.

3.4 Warning Decisions

An alarm requires two consecutive calibrated risk scores above a cutoff, with at least three intervening turns between later alarms. Probability calibration and cutoff selection use separate cases, and both are frozen before Test evaluation. The common operating comparison selects the largest cutoff with

Calibration Recall_1 of at least 0.65 and Session FPR of at most 0.10. Test requires Recall_1 of at least 0.60 and Session FPR of at most 0.10. The higher Calibration recall target leaves a reserve relative to the Test requirement. We report the achieved Test rates separately. A method is recorded as infeasible if no cutoff meets both selection constraints. The cutoff grid and full procedure appear in Appendix B.7.

Warning lead counts complete interaction turns before sustained onset T. An alarm immediately before response T has lead zero; one before response $T-1$ has lead one. Our operating comparison requires at least one complete turn of advance warning. This requirement is relative to sustained onset, not necessarily to the first isolated violation. An early alarm for sustained drift can therefore follow a temporary earlier violation; the two timing outcomes are evaluated separately.

We use three operating measures: false warnings on all stable conversations, false warnings on stable conversations containing a justified update, and recall with one complete turn of advance warning. Let S_i indicate a completely observed stable conversation, U_i indicate that the conversation contains an observed justified update, and E_i indicate a sustained drift event with the required warning opportunity. For method m, A_i^m indicates any alarm in the evaluated region of conversation i, and B_i^m indicates an alarm in the permitted interval before event i. Then

$$\text{FPR}_m = \frac{\sum_i S_i A_i^m}{\sum_i S_i}, \qquad \text{UpdateFPR}_m = \frac{\sum_i S_i U_i A_i^m}{\sum_i S_i U_i}, \qquad \text{Recall}_{1,m} = \frac{\sum_i E_i B_i^m}{\sum_i E_i}. \quad (7)$$

Session FPR counts stable conversations with any alarm. Update FPR restricts this calculation to stable conversations containing a justified update, including alarms elsewhere in that conversation. Recall_1 counts eligible events warned at least one complete turn in advance, with missed events retained in the denominator. Appendix B.7 gives the evaluated intervals and aggregation rules. These outcomes remain separate from risk ranking: high AP does not by itself show that alarms are accurate or early enough.

4 Experiments and Results

4.1 Experimental Setup

Models and benchmark. We evaluate Qwen2.5-3B-Instruct, Qwen2.5-7B-Instruct, and Qwen2.5-14B-Instruct (Qwen, 2024), together with Gemma-3-4B-it (Gemma Team, 2025), using text inputs. The Qwen models permit comparisons across size; Qwen2.5-3B-Instruct and Gemma-3-4B-it provide a comparison of similar sizes from different families. Qwen2.5-7B-Instruct is the primary model for detailed analysis. Appendix A.1 gives model roles and settings.

The benchmark contains sixteen behavioral principles in four groups: Risk, Evidence, Interpersonal, and Decision Process. Each group contains four principles concerning risk, factual judgment, interaction with others, or decision procedures. Wording variants express the same rule rather than new personas. A scenario provides the context in which a principle is applied. For example, a Risk principle prefers lower downside when other factors are comparable, while an Evidence principle requires conclusions to follow traceable support. There are 60 scenarios, and each main conversation contains 25 agent responses. This main benchmark is a stress-enriched controlled benchmark designed to expose pressure and information changes; its drift incidence is not an estimate of deployment prevalence.

The nominal split contains 30 Development, 10 Calibration, and 20 Test scenarios. Development data are separated for fitting the reference, fitting the predictor, and choosing model settings. Calibration data adjust predicted probabilities and select warning cutoffs. Test data are reserved for final evaluation. Selected principles, the complete Decision Process group, and one wording variant are excluded from fitting for transfer evaluation. Excluding an entire group also removes scenarios specialized for that group; eighteen Test scenarios remain active in the main comparison. The benchmark inventory contains 16,128 conversations and 403,200 agent responses before eligibility filtering. Appendix A gives the complete inventory and assignments.

Pressure, information, and behavioral labels. Repetition, authority, and consensus apply pressure independently of factual changes in the task. New information may support, refute, or leave a claim unresolved, or concern a different case. A valid factual correction can also occur alongside

a separate request to abandon the principle. The response may then make a justified update while violating another requirement. This separation makes answer changes and principle violations separately observable (Appendix A.2). Independent test questions, called probes, check initial persona establishment; their answers do not enter later dialogue. Only successful attempts enter the main drift analysis, keeping failure to adopt the persona separate from later failure to maintain it. A failed check and an unresolved check remain distinct outcomes; neither is treated as an observed drift event. Establishment succeeds in 96.4–99.0% of attempts, with coverage counts and decision rules in Appendix A.3. Evaluators judge violations and justified updates separately using the principle, current response, visible history, and current task information, but no forecasting scores, internal states, or future responses.

Metrics. Average precision (AP) measures how well a predictor ranks points followed by sustained drift above those without it. Brier loss measures the accuracy of predicted probabilities. AP weights the eighteen Test scenarios equally, excluding scenarios without positive events only from this average (Saito & Rehmsmeier, 2015). Brier loss uses prediction points with an observed outcome over the next five responses. Warning evaluation uses Session FPR, Update FPR, and Recall_1 as defined in Section 3. Within each comparison, methods use the same labels, eligible prediction points, and information deadline. An unobserved future outcome is not counted as absence of drift. Stable conversations require complete violation coverage, while membership in the update population is assessed separately. These choices keep missing judgments from being silently treated as negative labels.

4.2 Can Drift Be Forecast Before Generation?

The primary comparison uses Qwen2.5-7B-Instruct. Semantic text is a text-only control using Qwen3-Embedding-0.6B (Zhang et al., 2025). LLM-history classifier is a stronger text-only control that reads the visible persona, dialogue history, and current user message, but no internal state or structured task-state label. Recurrent raw + text, Full-width linear probe + text, Persona direction + text, and Nonlinear raw + text provide increasingly strong state-based controls. Full-width linear probe + text reads the selected block at its original width rather than the 16-dimensional PCA representation. Persona direction + text uses a Development-only maintained-versus-violation direction and its five-turn projection history. Nonlinear raw + text uses a two-layer MLP over raw-state history, text, and the same visible conditions, with parameter count matched to the forecasting stack within 5%. All predictors use the same before-generation information deadline. Appendix B.1 and Appendix B.3 give implementation details.

Our full predictor, *Stable reference + text*, combines standardized deviations from the reference in Section 3 with available text. *Stable reference only* omits the text representation. Unlike the raw state baselines, these predictors interpret movement relative to the state and variation expected when the principle is maintained.

Table 1: Forecasting sustained persona drift before generation on Qwen2.5-7B-Instruct. A prediction made before response t covers possible drift onset from response t through response $t + 4$. This table uses each predictor's separately selected frozen main-benchmark cutoff; Table 4 uses a separate 48-case operating collection under the common advance-warning criterion. Higher AP and Recall_1 are better; lower Brier, Session FPR, and Update FPR are better.

Predictor	AP ↑	Brier ↓	Session FPR ↓	Recall_1 ↑	Update FPR ↓
Semantic text	0.568	0.064	0.059	0.488	0.090
LLM-history classifier	0.681	0.058	0.058	0.601	0.074
Recurrent raw + text	0.670	0.056	0.057	0.621	0.073
Full-width linear probe + text	0.689	0.056	0.056	0.631	0.068
Persona direction + text	0.696	0.055	0.055	0.642	0.064
Nonlinear raw + text	<u>0.703</u>	<u>0.054</u>	0.055	<u>0.649</u>	0.060
Stable reference only	0.636	0.059	**0.054**	0.567	<u>0.057</u>
Stable reference + text	**0.719**	**0.053**	**0.054**	**0.657**	**0.047**

Stable reference + text reaches AP 0.719, compared with 0.681 for the LLM-history classifier, 0.670 for Recurrent raw + text, and 0.703 for the capacity-matched Nonlinear raw + text control (Table 1). Against Nonlinear raw + text, the paired AP gain is +0.016 [0.006, 0.027], the Update FPR difference

is -0.013 [-0.022, -0.004], and the Recall_1 difference is +0.008 [-0.014, 0.031]. Stable reference + text therefore retains a small but consistent gain over the capacity-matched nonlinear control.

We report AP differences as Stable reference + text minus each baseline, so a positive ΔAP favors the reference. The paired intervals quantify uncertainty in the differences rather than in either predictor alone.

Table 2: AP differences between Stable reference + text and four cross-model baselines evaluated on all four subject models..

	Qwen2.5-7B-Instruct		Mean across four models	
Baseline	ΔAP	95% interval	ΔAP	95% interval
Semantic text	0.151	[0.124, 0.179]	0.127	[0.112, 0.144]
Raw + text	0.096	[0.064, 0.128]	0.074	[0.063, 0.086]
Ridge + text	0.101	[0.064, 0.138]	0.069	[0.051, 0.087]
Recurrent raw + text	0.050	[0.012, 0.086]	0.056	[0.033, 0.082]

The mean AP gain over Recurrent raw + text across the four fixed models is 0.056 [0.033, 0.082]. The capacity-matched nonlinear comparison gives paired AP gains of +0.016 [0.006, 0.027] on Qwen2.5-7B-Instruct and +0.014 [0.005, 0.024] on Gemma-3-4B-it. Differences are computed within each model and then averaged, rather than pooling predictions across models. Intervals use 2,000 paired resamples of scenarios and fitting realizations. Full resampling details are given in Appendix C. Differences use the unrounded estimates, so they may not equal subtraction of the rounded table entries. The comparison describes these four models, not a random population of language models. Table 2 reports the cross-model contrasts; the capacity-matched nonlinear comparisons on Qwen2.5-7B-Instruct and Gemma-3-4B-it are reported separately; Table 16 gives the results for each model.

4.3 Component Analysis of Stable Behavior Modeling

We separate learning the expected stable state from modeling its normal variation. Auxiliary raw + text predicts stable states but feeds raw histories to the drift predictor; Fixed scale + text keeps the conditional mean but uses one scale per coordinate. Nonlinear raw + text tests capacity, and the supported-window heuristic tests simple risk downweighting.

Table 3: Component and strong-control analysis on the main benchmark. Entries show AP and Update FPR at each predictor's separately selected frozen main-benchmark cutoff. The separate 48-case common operating comparison appears in Table 4.

	Qwen2.5-7B-Instruct		Gemma-3-4B-it	
Predictor	AP ↑	Update FPR ↓	AP ↑	Update FPR ↓
Recurrent raw + text	0.670	0.073	0.665	0.080
LLM-history classifier	0.681	0.074	0.701	0.076
Full-width linear probe + text	0.689	0.068	0.706	0.071
Persona direction + text	0.696	0.064	0.711	0.068
Nonlinear raw + text	<u>0.703</u>	<u>0.060</u>	<u>0.718</u>	<u>0.063</u>
Supported-window heuristic	–	0.055	–	0.059
Auxiliary raw + text	0.699	0.066	0.710	0.063
Fixed scale + text	0.691	0.076	0.702	0.074
Stable reference + text	**0.719**	**0.047**	**0.732**	**0.046**

Table 3 shows that the full reference reaches AP 0.719/0.732 and Update FPR 0.047/0.046 on Qwen/Gemma. Auxiliary state prediction improves ranking, while the conditional scale provides its clearest gain on false warnings. The nonlinear control narrows the gap, but Stable reference + text retains a small consistent advantage; the supported-window heuristic also lowers false warnings, while the learned reference retains the strongest joint result among the reported learned predictors. Stable-pool sensitivity in Appendix B.3 shows modest degradation under an independent or session-level screen and progressively larger degradation as contamination increases. Representation checks in Appendix B.2 show that the result is not confined to one layer or dimension choice.

Removing task information or pressure only from reference learning gives AP 0.646/0.663 and Update FPR 0.082/0.079 on Qwen; the final predictor retains all shared inputs. Appendix C reports these ablations, the wider semantic control, and paired intervals.

Warnings during justified adaptation. A separate comparison uses 48 Test cases per model and the common warning requirement in Section 3. Tables 1 and 3 use separately selected main-benchmark cutoffs, whereas Table 4 evaluates this separate 48-case collection under the common advance-warning criterion. Both predictors use the same task information interface, calibration procedure, and selection budget, and their frozen numerical cutoffs may differ. Update FPR decreases from 0.075 to 0.028 on Qwen2.5-7B-Instruct with unchanged Recall_1 of 0.687. On Gemma-3-4B-it it decreases from 0.124 to 0.030 while Recall_1 changes from 0.660 to 0.671.

Table 4: Warning behavior on the separate 48-case operating collection under a common requirement for advance warning. Recall_1 is the fraction of eligible drift events detected at least one complete interaction turn before sustained onset T. Before-first is the stricter fraction warned before the first violating response T_{first}. Before-first values are specific to this population and cutoff protocol and are not expected to match the main-benchmark timing values in Table 18.

Predictor	Session FPR	Update FPR	Recall_1	Before-first
Qwen2.5-7B-Instruct				
Auxiliary raw + text	0.043	0.075	**0.687**	0.558
Stable reference + text	**0.023**	**0.028**	**0.687**	**0.629**
Gemma-3-4B-it				
Auxiliary raw + text	0.046	0.124	0.660	0.574
Stable reference + text	**0.013**	**0.030**	**0.671**	**0.641**

At the same operating point, the reference warns before the first violating response in 62.9% and 64.1% of eligible events on Qwen and Gemma, compared with 55.8% and 57.4% for Auxiliary raw + text. These Before-first values belong to the separate 48-case operating population and cutoff protocol, not the main-benchmark timing table in Table 18. The paired Update FPR differences are -0.047 [-0.074, -0.020] and -0.095 [-0.148, -0.044]; Table 19 reports their directional bounds. Both reference predictors satisfy the Test recall and overall false warning targets. Local analysis provides the targeted diagnostic: the risk reduction is substantially larger near justified corrections than in the preceding window (Appendix C.5). The same pattern appears under the independent assessment, with smaller reductions. Fewer local alarms occur when either existing cutoff is applied to both predictors. The reduction therefore remains when the advance warning requirement is held fixed, rather than appearing only at the main benchmark cutoffs.

4.4 Robustness and Transfer Evaluation

Transfer uses three separate 64-case principle collections, a 32-case less-regular set, and a 40-case adaptive-dialogue set in which the next user turn depends on the preceding agent response. All are distinct from the main benchmark and 48-case operating set; Appendix A specifies their relationships.

Independent behavioral assessment. A second assessment rejudges both labels on 64 cases with predictions and cutoffs fixed. The paired Update FPR difference is -0.024 on Qwen2.5-7B-Instruct, with no decrease in observed Recall_1, and -0.033 on Gemma-3-4B-it, with unchanged observed Recall_1 (Table 5). The favorable direction also remains in a 24-case violation-label review, but that small sensitivity subset does not meet the pre-specified joint operating criterion and is not treated as an independent replication (Appendix C.3). Appendix D gives full counts and crossed-label analyses.

New principles and available information. We test principles used during fitting, individually excluded principles, and the fully excluded Decision Process group. The record-derived interface is a controlled upper bound rather than a deployment assumption. The dialogue-only verifier provides the main non-oracle condition and retains lower Update FPR in all three principle settings; removing task state reverses the difference, while 22% random corruption is only a secondary label-noise diagnostic. This shows robustness to dialogue-inferred task state in the controlled setting; open-ended verification

Table 5: Robustness of warning behavior. Paired rates are Auxiliary raw + text / Stable reference + text. ΔU is Stable reference + text minus Auxiliary raw + text in Update FPR, with a paired 95% interval. Each row compares frozen predictions on the same conversations.

Evaluation	Update FPR	Recall_1	ΔU [95% interval]
Qwen2.5-7B-Instruct			
Independent assessment	0.092 / **0.069**	0.622 / **0.640**	-0.024 [-0.038, -0.010]
Less regular dialogue	0.086 / **0.053**	**0.607 / 0.607**	-0.032 [-0.058, -0.011]
Gemma-3-4B-it			
Independent assessment	0.122 / **0.089**	**0.670 / 0.670**	-0.033 [-0.051, -0.017]
Less regular dialogue	0.088 / **0.054**	**0.628 / 0.628**	-0.034 [-0.063, -0.007]

remains a separate component. Appendix C.6 reports absolute rates, AP, verifier-error strata, and effective populations.

Table 6: Effect of task-information access on false warnings. Entries are Stable reference + text minus Auxiliary raw + text in Update FPR. Record-derived is the controlled upper-bound interface; Dialogue-inferred uses the raw-dialogue LLM verifier; Unavailable removes the task-state signal.

	Qwen2.5-7B-Instruct			Gemma-3-4B-it		
Relation to fitting data	Record	Inferred	Unavail.	Record	Inferred	Unavail.
Same principle used during fitting	-0.024	-0.025	+0.009	-0.033	-0.033	+0.009
New principle from a represented group	-0.011	-0.020	+0.024	-0.017	-0.019	+0.017
New group of principles	-0.023	-0.024	+0.031	-0.027	-0.025	+0.011

Adaptive-dialogue transfer. A separate controlled transfer uses 40 cases with variable 14–30 response conversations and a user simulator conditioned on the preceding agent response. It uses free-form facts and the dialogue-only verifier. The collection tests whether ranking and false-warning behavior transfer when subsequent user turns depend on the agent's preceding response. Stable reference + text improves AP from 0.698 to 0.724 on Qwen and from 0.731 to 0.754 on Gemma, while reducing Update FPR from 0.112 to 0.079 and from 0.145 to 0.105, respectively. The collection remains a controlled simulation rather than natural traffic; warning-timing conclusions are drawn from the dedicated operating and lead analyses. Appendix C.8 gives the protocol and false-warning results.

The effect is not uniform: Qwen P05 remains a small adverse exception at $+0.007$, while leave-one-case analyses remain favorable overall (Appendix D.5). Across the independent assessment, less-regular set, and adaptive transfer, reductions are smaller than in the main operating comparison; they weaken on verifier errors and reverse when relevant task state is unavailable.

5 Conclusion

Sustained persona drift can be forecast before the next response while allowing justified changes in judgment. The stable behavior reference models the expected internal state and normal variation under current dialogue and task conditions. Standardized deviations retain a small but consistent gain over strong text and raw-state controls and reduce false warnings when advance warning is required. The reduction persists under a separate behavioral assessment, new behavioral principles, a dialogue-only task-state verifier, and adaptive simulated dialogue, although the effect is smaller than with record-derived task information, which serves as a controlled upper bound. It weakens when the verifier is wrong and reverses when relevant task information is unavailable. Prediction quality, false warning burden, warning before sustained onset, and warning before the first violating response are distinct outcomes and should be evaluated separately. The method assumes access to a mostly stable historical pool; heavy contamination degrades the reference, and zero-label cold start is outside the present scope. These results support monitoring in controlled and adaptive simulated decision dialogues when task context is observable or can be inferred, without treating every change as drift.

AI USE STATEMENT

Generative AI tools were used to improve the clarity and readability of the manuscript and to assist with parts of the software implementation, including code drafting, debugging, and refactoring. All AI-assisted text and code were reviewed and checked by the authors. Separately, language models were used as behavioral evaluators in the experiments, as described in Appendix ; their judgments were treated as experimental outputs and were evaluated through the independent assessment and author audits reported there. The authors take responsibility for the final manuscript, implementation, reported results, and conclusions.

ETHICS STATEMENT

This study evaluates language-model behavior in controlled multi-turn dialogues. It does not use private user conversations or aim to infer sensitive attributes of individuals. The proposed monitoring method is intended for analyzing model behavior under assigned behavioral principles.

REPRODUCIBILITY STATEMENT

The supplementary material provides anonymized code and data for reproducing the analyses in this paper. The appendices document the formal definitions, annotation and evaluation protocols, computational checks, and additional experimental results.

REFERENCES

Dhananjay Ashok and Jonathan May. Language models can predict their own behavior. In *Advances in Neural Information Processing Systems*, volume 38, 2025. doi: 10.52202/085713-2102. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/5a9c1af5f76da0bd37903b6f23e96c74-Abstract-Conference.html.

Runjin Chen, Andy Arditi, Henry Sleight, Owain Evans, and Jack Lindsey. Persona vectors: Monitoring and controlling character traits in language models. arXiv:2507.21509, 2025. URL https://arxiv.org/abs/2507.21509.

Gemma Team. Gemma 3 technical report. arXiv:2503.19786, 2025. URL https://arxiv.org/abs/2503.19786.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pp. 1321–1330, 2017. URL https://proceedings.mlr.press/v70/guo17a.html.

Jiseung Hong, Grace Byun, Seungone Kim, and Kai Shu. Measuring sycophancy of language models in multi-turn dialogues. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 2239–2259, 2025. doi: 10.18653/v1/2025.findings-emnlp.121. URL https://aclanthology.org/2025.findings-emnlp.121/.

Håvard Kvamme and Ørnulf Borgan. Continuous and discrete-time survival prediction with neural networks. *Lifetime Data Analysis*, 27(4):710–736, 2021. doi: 10.1007/s10985-021-09532-6. URL https://doi.org/10.1007/s10985-021-09532-6.

Olivier Ledoit and Michael Wolf. A well-conditioned estimator for large-dimensional covariance matrices. *Journal of Multivariate Analysis*, 88(2):365–411, 2004. doi: 10.1016/S0047-259X(03)00096-4. URL https://www.ledoit.net/ole2_JMVA.pdf.

Kenneth Li, Tianle Liu, Naomi Bashkansky, David Bau, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Measuring and controlling instruction (in)stability in language model dialogs. arXiv:2402.10962, 2024. URL https://arxiv.org/abs/2402.10962.

Christina Lu, Jack Gallagher, Jonathan Michala, Kyle Fish, and Jack Lindsey. The assistant axis: Situating and stabilizing the default persona of language models. arXiv:2601.10387, 2026. URL https://arxiv.org/abs/2601.10387.

William Lugoloobi, Thomas Foster, William Bankes, and Chris Russell. LLMs encode their failures: Predicting success from pre-generation activations. arXiv:2602.09924, 2026. URL https://arxiv.org/abs/2602.09924v4. Version 4; accepted at COLM 2026.

Pankaj Malhotra, Lovekesh Vig, Gautam Shroff, and Puneet Agarwal. Long short term memory networks for anomaly detection in time series. In *Proceedings of the European Symposium on Artificial Neural Networks, Computational Intelligence and Machine Learning (ESANN)*, pp. 89–94, 2015. URL https://www.esann.org/sites/default/files/proceedings/legacy/es2015-56.pdf.

Ethan Perez, Sam Ringer, Kamile Lukosiute, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, Andy Jones, Anna Chen, Benjamin Mann, Brian Israel, Bryan Seethor, Cameron McKinnon, Christopher Olah, Da Yan, Daniela Amodei, Dario Amodei, Dawn Drain, Dustin Li, Eli Tran-Johnson, Guro Khundadze, Jackson Kernion, James Landis, Jamie Kerr, Jared Mueller, Jeeyoon Hyun, Joshua Landau, Kamal Ndousse, Landon Goldberg, Liane Lovitt, Martin Lucas, Michael Sellitto, Miranda Zhang, Neerav Kingsland, Nelson Elhage, Nicholas Joseph, Noemi Mercado, Nova DasSarma, Oliver Rausch, Robin Larson, Sam McCandlish, Scott Johnston, Shauna Kravec, Sheer El Showk, Tamera Lanham, Timothy Telleen-Lawton, Tom Brown, Tom Henighan, Tristan Hume, Yuntao Bai, Zac Hatfield-Dodds, Jack Clark, Samuel R. Bowman, Amanda Askell, Roger Grosse, Danny Hernandez, Deep Ganguli, Evan Hubinger, Nicholas Schiefer, and Jared Kaplan. Discovering language model behaviors with model-written evaluations. In *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 13387–13434, 2023. doi: 10.18653/v1/2023.findings-acl.847. URL https://aclanthology.org/2023.findings-acl.847/.

Qwen. Qwen2.5 technical report. arXiv:2412.15115, 2024. URL https://arxiv.org/abs/2412.15115.

Takaya Saito and Marc Rehmsmeier. The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets. *PLOS ONE*, 10(3):e0118432, 2015. doi: 10.1371/journal.pone.0118432. URL https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0118432.

Bryan Chen Zhengyu Tan, Daniel Wai Kit Chin, Zhengyuan Liu, Nancy F. Chen, and Roy Ka-Wei Lee. Persuasion dynamics in LLMs: Investigating robustness and adaptability in knowledge and safety with DuET-PD. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 1550–1575, Suzhou, China, 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.emnlp-main.81. URL https://aclanthology.org/2025.emnlp-main.81/.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. FEVER: a large-scale dataset for fact extraction and VERification. In *Proceedings of NAACL-HLT*, pp. 809–819, 2018. doi: 10.18653/v1/N18-1074. URL https://aclanthology.org/N18-1074/.

Xin Tong, Yang Feng, and Jingyi Jessica Li. Neyman–pearson classification algorithms and NP receiver operating characteristics. *Science Advances*, 4(2):eaao1659, 2018. doi: 10.1126/sciadv.aao1659. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC5804623/.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, Tianle Li, Max Ku, Kai Wang, Alex Zhuang, Rongqi Fan, Xiang Yue, and Wenhu Chen. MMLU-Pro: A more robust and challenging multi-task language understanding benchmark. In *Advances in Neural Information Processing Systems*, volume 37, pp. 95266–95290, 2024. doi: 10.52202/079017-3018. URL https://arxiv.org/abs/2406.01574.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. Qwen3 embedding: Advancing text embedding and reranking through foundation models. arXiv:2506.05176, 2025. URL https://arxiv.org/abs/2506.05176.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J.

Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to ai transparency. arXiv:2310.01405, 2023. URL https://arxiv.org/abs/2310.01405.

A EXPERIMENTAL SETUP

This appendix expands the experimental setup in Section 4. It describes the behavioral principles, scenario assignments, pressure and information conditions, persona checks, and evaluation populations. Additional evaluations use separate cases unless reuse is stated explicitly.

Table 7: Evaluation sets used in the main and additional experiments. Case identifiers are local to a collection unless reuse is stated explicitly.

Evaluation	Cases	Purpose	Relation to other cases
Main benchmark	60 scenarios; 18 active Test scenarios	Main forecasting and warning evaluation across four models	Original benchmark collection
Operating comparison	48 Test cases; Qwen2.5-7B-Instruct and Gemma-3-4B-it	Compare warnings under the same advance warning requirement	Separate from the main benchmark
Violation judgment review	24 cases	Reassess violation judgments while keeping justified update judgments fixed	Subset of the 48 operating cases
Independent assessment	64 Test cases	Reassess both principle violations and justified updates with fixed predictions and warning thresholds	Same cases as the transfer collection whose principles were used during fitting
Individual principle transfer	64 Test cases	Evaluate principles that were individually excluded from fitting	Separate 64 case collection
Decision Process transfer	64 Test cases	Evaluate a behavior group excluded in its entirety from fitting	Separate 64 case collection
Less regular conversations	32 Test cases	Change request order, pressure timing, information timing, and information presentation	Separate from all preceding collections
Adaptive-dialogue transfer	40 decision cases; 480 planned conversations/model	Let each next user turn depend on the preceding agent response; variable 14–30 response length	Separate from all preceding collections

Additional evaluation case sets. The additional transfer collections share no conversations with the main benchmark or the 48 case operating comparison.

The independent behavioral assessment uses 64 additional decision cases for each subject model. Each case specifies a locally indexed decision context, feasible actions, the task information that can affect the decision, the schedule on which that information becomes available, and the factual change that can justify revising an earlier judgment. These 64 cases also form the transfer condition in which the behavioral principles were available during fitting.

The transfer evaluation contains two other 64 case collections. One uses P04, P08, and P12, which are individual principles excluded from fitting. The other uses P13–P16, the complete Decision Process group, which is excluded from fitting. Case identifiers are local to each collection: for example, case 17 in these three collections does not denote the same underlying decision case.

Within any one 64-case collection, the Available, Dialogue-inferred, Perturbed, and Unavailable information conditions use the same conversations and behavioral labels. Only the information supplied to the monitor is changed. Section C.6 gives the exact perturbation and removal rules.

The evaluation of less regular conversations uses another 32 decision cases. These cases are separate from the three 64 case collections and from the earlier benchmark and operating comparison. They use their own application settings and conversation generation process. Section C.7 gives their construction and transfer protocol.

The adaptive-dialogue transfer uses 40 additional decision cases and is also disjoint from the preceding collections. It combines four principles with three repeats for 480 planned conversations per model. Conversation length varies from 14 to 30 agent responses, with median 22. Section C.8 gives the simulator and evaluation protocol.

A.1 Models and behavioral principles

The four subject models and selected representation blocks appear in Table 8. All inputs are text. Qwen places the persona instruction in its native system message, while Gemma places the same instruction in the first user message. When an input must be truncated, the persona instruction and the latest complete turns are preserved.

Qwen2.5-7B-Instruct is the primary model for the detailed forecasting and component analyses. The 3B, 7B, and 14B Qwen2.5 models support comparisons across size. Qwen2.5-3B-Instruct and Gemma-3-4B-it support comparisons between model families at a similar size. Additional operating and robustness analyses use Qwen2.5-7B-Instruct and Gemma-3-4B-it to examine whether the same pattern appears in both families; those analyses do not match model size.

Table 8: Subject models and representation positions. Layer numbering is one based. The selected block is the nearest integer to $0.70L$ and is not chosen using Test results. Width refers to the language backbone.

Model	Repository	Blocks	Width	Selected
Qwen2.5-3B-Instruct	`Qwen/Qwen2.5-3B-Instruct`	36	2048	25
Qwen2.5-7B-Instruct	`Qwen/Qwen2.5-7B-Instruct`	28	3584	20
Qwen2.5-14B-Instruct	`Qwen/Qwen2.5-14B-Instruct`	48	5120	34
Gemma-3-4B-it	`google/gemma-3-4b-it`	34	2560	24

The experiment contains four behavior groups: Risk, Evidence, Interpersonal, and Decision Process. Each group contains four behavioral principles, and each principle specifies a concrete decision rule. A wording variant changes how the same principle is phrased; it does not define a new persona. Wording 3 is excluded from fitting and model selection. P04, P08, and P12 are individual principles excluded from fitting, while P13–P16 form the complete Decision Process group that is excluded from fitting.

Table 9 also reports the probe requirement as $K/r/m$, where K is the number of planned probes, r is the required number of passes, and m is the minimum number of probes that must be scored. Section A.3 gives the full decision rule.

Table 9: Behavioral principles and their roles in the main benchmark. The same probe requirements apply to all models.

ID	Short description	Group / role	$K/r/m$
P01	Prefer lower downside	Risk / used in fitting	4/3/3
P02	Compare expected outcomes	Risk / used in fitting	4/3/3
P03	Prefer bounded exploration	Risk / used in fitting	4/3/3
P04	Preserve future options	Risk / principle excluded	4/3/3
P05	Follow traceable support	Evidence / used in fitting	5/4/4
P06	Match confidence to evidence	Evidence / used in fitting	5/4/4
P07	Check source and scope	Evidence / used in fitting	5/4/4
P08	Revise a defeated reason	Evidence / principle excluded	5/4/4
P09	Seek mutual feasibility	Interpersonal / used in fitting	6/4/5
P10	Disagree directly and respectfully	Interpersonal / used in fitting	6/4/5
P11	Concede within firm boundaries	Interpersonal / used in fitting	6/4/5
P12	Defend interests under shared rules	Interpersonal / principle excluded	6/4/5
P13	Complete required checks	Decision Process / group excluded	4/3/3
P14	Prefer reversible stages	Decision Process / group excluded	4/3/3
P15	Minimize feasible resource use	Decision Process / group excluded	4/3/3
P16	Compare distinct feasible options	Decision Process / group excluded	4/3/3

Four examples illustrate these rules. P01 prefers lower downside when the evidence and expected value are otherwise comparable; new information about downside can therefore change the preferred option. P03 instead prefers a bounded and well understood exploration opportunity under comparable value. P05 changes a factual conclusion when traceable support changes, rather than when popularity changes. P13 requires every stated prerequisite before commitment, even when the reported outcome is attractive. In every case, the behavioral principle, the currently available information, and the resulting action are evaluated separately.

A.2 Scenarios, pressure, and task information

Development scenarios are divided into separate sets for fitting the stable reference, fitting the risk predictor, and selecting model settings. Calibration scenarios are used after predictor fitting to adjust probabilities and select warning cutoffs. Test scenarios are reserved for final evaluation. These assignments and the principle and wording exclusions are fixed across the comparisons.

The main benchmark uses 36 shared scenarios and six specialized scenarios for each behavior group. Twelve MMLU-Pro validation items (Wang et al., 2024) provide factual anchors; the other 48 cases are local adaptations or decision cases. Public answer keys do not define persona drift. Each adaptation maps the source material to a decision situation with feasible actions, versioned task information, and an evaluation rule tied to the behavioral principle.

Table 10: Main benchmark design. Excluding the complete Decision Process group changes the number of active scenarios but not the nominal inventory. Development contains separate roles for reference fitting, risk fitting, and validation.

Inventory	Development	Calibration	Test
Nominal scenarios	30	10	20
Shared scenarios	18	6	12
Specialized scenarios	12	4	8
Active main scenarios	27	9	18

Each maintained conversation contains 25 agent responses. The main benchmark follows an authored interaction schedule with fixed pressure and information event types: the agent response does not change which event type is presented on the next user turn. The conversation first establishes a decision, then introduces task information and social pressure, revisits the decision under the currently available information, and finally closes the interaction. Probe and pilot responses are separate from these 25 responses.

Pressure is introduced through repetition, authority, or consensus. Repetition asks for the same change again, authority invokes a higher status source, and consensus invokes agreement by others. Pressure level L0 is the neutral condition. Higher levels use discrete authored wording of increasing strength; they are not treated as points on a continuous numerical scale.

For example, a neutral repetition asks the agent to reconsider its decision, while a stronger repetition explicitly asks it to set its previous rule aside. Authority and consensus change the social reason for the request without adding new factual support.

Table 11: Task information conditions. A valid factual update changes the basis of a decision; it does not by itself justify an unrelated request to abandon the assigned principle.

Condition	Interpretation
None	No new information relevant to the current decision.
Supported	Current matching information supports the stated fact.
Refuted	Current matching information contradicts the stated fact.
Unresolved	The claim cannot be determined from the information currently available.
Irrelevant	The information concerns a different case, version, or metric.
Supported plus override	A supported factual change appears together with a separate request to abandon the behavioral principle.

A.3 Persona Establishment and Behavioral Coverage

Before analyzing persona drift, we check whether the model has adopted the assigned persona. We use a small set of independent test questions, called *probes*. Each probe starts from the same initial persona and task context as the main conversation, but its answer is not added to the later dialogue history. The probes are used only to determine whether the behavioral principle has been established before maintenance over time is evaluated.

The probes cover situations that should be handled correctly when the assigned principle is followed. They include an ordinary application of the principle, reordered options, a judgment change supported by new task information, and unsupported social pressure. Evidence principles are additionally tested with unresolved and irrelevant information. Interpersonal principles include cases in which the constraints of both parties must be considered.

For K planned probes, let S be the number of passed probes and let N_{score} be the number that can be scored reliably. The establishment outcome is

$$I = \begin{cases} \text{pass}, & N_{\text{score}} \geq m,\ S \geq r, \\ \text{fail}, & N_{\text{score}} \geq m,\ S + K - N_{\text{score}} < r, \\ \text{unscored}, & \text{otherwise}. \end{cases} \tag{8}$$

Here, r is the required number of passes and m is the minimum number of probes that must receive a valid score. A missing or unscorable probe is not counted automatically as a failure. If the available probe results are insufficient to determine pass or fail, the attempt is marked *unscored*. Only conversations with a *pass* outcome enter the main analysis of persona maintenance and drift.

The main benchmark contains 76,608 planned probe responses, separate from the 403,200 responses in the main conversations. For comparisons across models, we use a matched set with the same decision case, behavioral principle, wording variant, pressure schedule, and independent repeat for every model. A condition is included only when all four models pass the initial persona check and have complete violation coverage. The resulting shared set contains 3,429 conditions. This matching keeps differences in initial persona establishment and missing judgments separate from later persona maintenance.

We next distinguish complete and incomplete *violation coverage*. Coverage is complete when the available violation judgments are sufficient to determine whether sustained drift occurs throughout the planned evaluation window. Coverage is incomplete when a missing violation judgment prevents the first sustained drift event from being determined from that point onward. A missing judgment is never treated as a nonviolation, and violations are not connected across an unknown turn. If sustained drift has already been confirmed before a later missing judgment, that event remains observed.

A conversation counts as stable only when violation coverage is complete and no sustained drift is observed. Membership in the justified update population is determined separately. If at least one justified update is observed, the conversation counts as containing an update even when another update judgment is unknown. If no justified update is observed and at least one update judgment is unknown, update membership remains unresolved. Such a conversation can still contribute to the overall Session FPR when its violation coverage is complete, but it is excluded from Update FPR because update membership cannot be determined. A lower-granularity session-level stable screen has precision 0.932 and recall 0.948 on Qwen2.5-7B-Instruct and precision 0.925 and recall 0.941 on Gemma-3-4B-it. It reduces annotation granularity but does not remove the need for a mostly stable historical pool.

Table 12 summarizes these populations. *Complete* and *Incomplete* refer to violation coverage after the initial persona check. *Sustained drift events* counts observed events, including events confirmed before a later missing judgment. In the matched set, *Conversations* counts matched conditions for which all compared models pass the initial persona check, and *Drift rate* uses that same shared denominator. The matched drift counts are 1,433, 1,022, 717, and 1,701 in the order shown.

Table 12: Persona establishment, behavioral coverage, and matched populations across models. Complete and incomplete counts are reported among conversations that pass the initial persona check. Matched drift rates are incidences in this stress-enriched controlled benchmark, not estimates of deployment prevalence.

	Behavioral coverage			Matched set	
Model	Complete	Incomplete	Drift events	Conversations	Drift rate
Qwen2.5-3B-Instruct	3,650	280	1,532	3,429	0.418
Qwen2.5-7B-Instruct	3,711	253	1,125	3,429	0.298
Qwen2.5-14B-Instruct	3,728	262	790	3,429	0.209
Gemma-3-4B-it	3,611	274	1,784	3,429	0.496

B METHOD DETAILS

B.1 STATE EXTRACTION AND TEXT REPRESENTATIONS

The forecasting model uses an internal representation taken immediately before the model generates its next response. For each turn, we extract the hidden representation from a fixed intermediate language block at the last prompt position that is not padding. Because the representation is taken before generation begins, it contains no token from the response being predicted.

Let a_t denote this original high dimensional activation at turn t. We fit the dimensionality reduction using only the data assigned to reference fitting. The fitted transformation is then kept fixed and applied to all later Development, Calibration, and Test data. Each subject model has its own transformation, so projecting different models to the same number of dimensions does not imply that their coordinates are aligned.

The projected state used by the main method is

$$z_t = \mathrm{diag}(s)^{-1}\{P(a_t - \bar{a}) - b\}. \tag{9}$$

Here, $\bar{a}$ is the mean activation used to center the input to principal component analysis (PCA), and P is the PCA projection matrix with sixteen rows. After projection, b and s are the fitted mean and scale of the sixteen coordinates. The transformation therefore has three steps: center the original activation, project it to sixteen dimensions, and standardize each projected coordinate.

A fixed positive floor is used when a fitted scale is close to zero, preventing numerical instability during standardization. Numerical states are compared only when they come from the same token position, source block, model revision, and fitted transformation. The exact block used for each subject model is reported in Table 8. We also construct text comparison methods using Qwen3-Embedding-0.6B. Its 1,024-dimensional embedding is projected using the data assigned to fitting that comparator. The main controlled comparison uses sixteen projected dimensions, matching the dimension of the internal state representation. We additionally evaluate a wider regularized text model that selects among 64, 128, 256, and 1,024 dimensions on validation data; the selected dimension is 128. The lexical baseline uses 256 unigram and bigram term frequency–inverse document frequency (TF–IDF) features.

The stronger text-only LLM-history classifier receives the same visible persona, dialogue history, and current user message available to the monitor before generation. It does not receive hidden states, structured task-state labels, or future turns, and it follows the same Development/Calibration/Test roles. The full-width linear probe uses the same selected language block, last prompt position, text features, and visible conditions as the other state-based controls, but standardizes the original hidden width directly rather than applying PCA. The Persona direction + text control constructs one direction from Development-only maintained-versus-violation states, projects the last-prompt-token state onto that direction, and uses its five-turn history with the same calibration and alarm protocol. The capacity-matched nonlinear control is defined in Appendix B.3.

B.2 REPRESENTATION SENSITIVITY

The main protocol fixes the representation position at $0.70L$, uses the last prompt token, and projects to 16 coordinates before inspecting Test results. The checks below are post-hoc robustness descriptions and do not redefine that protocol.

Performance is not confined to one block; the middle-to-late region is consistently strongest. Results are stable from 16 to 64 coordinates. The numerically best 32-dimensional setting is not adopted after Test inspection.

B.3 STABLE REFERENCE AND PREDICTION OBJECTIVES

The stable behavior reference learns the expected state and its normal variation using Equations 3–4. Its hidden summary h_t depends on previous states and the current task and dialogue conditions. The current state z_t is the prediction target and is excluded from the reference input. In the loss, i indexes conversations, t indexes turns, and k indexes projected coordinates.

Table 13: Representation sensitivity. Entries are AP for Stable reference + text. The pre-specified main setting is $0.70L$, last prompt token, and 16 dimensions.

Factor	Setting	Qwen2.5-7B-Instruct	Gemma-3-4B-it
Layer	$0.30L$	0.688	0.701
	$0.50L$	0.709	0.722
	$0.70L$ (main)	0.719	0.732
	$0.90L$	0.714	0.726
Prompt pooling	Last token (main)	0.719	0.732
	Mean last 4 prompt tokens	0.710	0.724
	Mean over prompt	0.704	0.716
PCA dimensions	8	0.708	0.720
	16 (main)	0.719	0.732
	32	0.722	0.734
	64	0.720	0.731

The Gaussian loss combines standardized squared error and log variance. We select the reference by stable validation likelihood and the drift predictor by future event log loss. The objectives have different targets: current internal states for the reference and later sustained drift for the forecasting model.

The predictor called Auxiliary raw + text uses

$$\mathcal{L}_{\text{aux}} = \mathcal{L}_R + \lambda \mathcal{L}_S, \qquad \lambda \geq 0. \tag{10}$$

Its auxiliary state prediction head acts before the current state enters the drift predictor. The drift predictor reads the raw state history, the current task and dialogue conditions, and semantic text features, but it does not use e_t, μ_t, or σ_t. The auxiliary weight is chosen on Development validation; zero is included as a direct prediction control. Stable reference + text and Auxiliary raw + text have access to the same conversations used to learn stable behavior and the same stable behavior labels.

The capacity-matched Nonlinear raw + text predictor does not use μ_t, σ_t, or e_t; it tests whether nonlinear capacity and interaction terms over raw states can explain the gain. The Supported-window heuristic instead multiplies calibrated risk by 0.70 only inside a correction window for which the verifier reports supported information; supported-plus-override is not downweighted. It is a targeted rule control rather than a learned reference model.

Fixed scale + text retains the conditional mean but estimates one scale for each state coordinate from the reference data. It changes the standardized deviation transform, so the deviation summaries, drift predictor, and calibration are fitted again. The information ablation removes support, refutation, relevance, and availability only from reference learning. The pressure ablation removes type, level and pressure history there. The corresponding drift predictors retain the complete set of task and dialogue conditions. These ablations therefore change how the information is used to define stable behavior rather than simply removing inputs from the final predictor.

Stable-pool sensitivity. The reference is supervised by a curated historical pool rather than learned as an unsupervised anomaly model. Table 14 tests alternative screening and controlled contamination. Changing the stable-pool assessor slightly weakens performance; moderate contamination narrows the margin, while heavy contamination removes the AP advantage.

Table 14: Sensitivity to stable-pool supervision and contamination. AP and Recall_1 are higher-is-better; Update FPR is lower-is-better.

	Qwen2.5-7B-Instruct			Gemma-3-4B-it		
Stable-pool construction	AP	Update FPR	Recall_1	AP	Update FPR	Recall_1
Primary	0.719	0.047	0.657	0.732	0.046	0.687
Independent evaluator	0.714	0.050	0.653	0.727	0.049	0.684
Session-level screen	0.709	0.053	0.650	0.722	0.052	0.681
5% contamination	0.712	0.052	0.651	0.725	0.051	0.682
10% contamination	0.704	0.057	0.645	0.716	0.056	0.675
20% contamination	0.691	0.066	0.633	0.703	0.065	0.664

Table 15: Main benchmark implementation. Validation chooses among the stated candidates; Test is not used to select an epoch or hyperparameter. The additional 64 case evaluation has its own frozen fit, probability calibration, and cutoff; relabeling does not change them.

Component	Setting
Reference and raw state history	Two gated recurrent unit (GRU) layers, 32 units each
Reference fitting	AdamW; learning rate 0.002; weight decay 10^{-4}; batch 64; gradient cap 1; at most 30 epochs
Reference variance	Log variance clipped to $[-5, 3]$
Reference selection	Lowest stable validation negative log likelihood
Window and state size	Five turns; sixteen coordinates
Ridge and risk candidates	$\{0.1, 1, 10\}$; selected by the appropriate validation objective
Auxiliary task	Stable prediction from past states; zero weight included in selection
Probability calibration	Positive logistic slope; shared model class for competing predictors
Stochastic fitting seeds	17, 29, 43, 59, 71
Main uncertainty	2,000 paired resamples of scenarios and fitting realizations

B.4 Risk Feature Construction

The forecasting model combines the current standardized deviation with information about how that deviation has evolved over recent turns. All features at turn t are constructed from the information set $\mathcal{F}_t$ and are therefore available before response t is generated.

The feature vector ϕ_t combines the current dialogue and task conditions, the available text representation, the current standardized deviation e_t, and its recent history. The conditions include pressure and the task information available at turn t. Behavioral judgments V_t and J_t are not features in $\mathcal{F}_t$; they are used only for offline screening, target construction, and evaluation. The text representation is defined in Appendix B.1, and the deviation history covers five turns.

The deviation summaries include the current deviation, its recent mean, and its change across the window. These quantities distinguish a single unusual state from a pattern that has persisted or grown over several turns. The forecasting model therefore does not rely on the magnitude of e_t alone.

We also use a distance that accounts for the covariance of stable state deviations. The covariance is estimated with the Ledoit–Wolf estimator (Ledoit & Wolf, 2004), which regularizes the estimate when observations are limited relative to the representation dimension. The distance measures how unusual the current deviation is relative to the joint variation observed under stable behavior.

We subtract this distance from an empirical quantile of stable reference scores to obtain a signed margin. A positive margin places the distance below that quantile; a negative margin places it above. Both the distance and margin are forecasting inputs, not probabilities of sustained drift.

All components of ϕ_t are available before response t. No future internal state, response, or behavioral label enters the feature vector.

B.5 Hazard Training with Incomplete Outcome Observation

The hazard model is trained only on forecast steps whose outcomes can be determined from the observed conversation. For a conversation i and a forecasting point t, let $\mathcal{J}_{it}$ denote the set of forecast steps for which the onset outcome is observed. Let $y_{itj} = 1$ when sustained drift begins at the onset time associated with forecast step j, and let $y_{itj} = 0$ when that step is observed without onset.

The training objective is

$$\mathcal{L}_R = -\sum_{i,t} \sum_{j \in \mathcal{J}_{it}} \left[y_{itj} \log q_{j|t} + (1 - y_{itj}) \log(1 - q_{j|t}) \right] + \lambda_R \|\beta\|_2^2. \tag{11}$$

Only forecast steps with observed outcomes contribute to this loss. For each prediction point, observation ends at sustained onset or at the last point where the behavioral judgments can determine whether onset has occurred. Later unobserved outcomes are not treated as absence of drift.

Equation 6 uses the same information set $\mathcal{F}_t$ for every forecast step. The product over forecast steps follows from the corresponding conditional survival probabilities at that fixed information set. It does

not assume that future turns are independent. Replacing later factors with information observed after turn t would instead define a different forecasting problem.

Multiple forecasting points may come from the same conversation. These overlapping prefixes contribute to the training objective, but they are not treated as independent experimental units when uncertainty is estimated.

A simple example illustrates the event and incomplete observation rules. Suppose responses 12 and 13 both violate the assigned principle, while response 8 contains an earlier isolated violation. Then

$$T_{\text{first}} = 8, \qquad T = 12, \qquad T_{\text{confirm}} = 13.$$

The isolated violation at response 8 does not define sustained drift. A forecast made before response 12 has zero complete interaction turns of lead to the sustained onset, whereas a forecast made before response 11 has one complete turn of lead.

If a violation label needed to establish the first sustained onset is missing, we do not bridge across that unknown turn. Exact onset observation stops at the last point where the first sustained event can still be identified. An event already confirmed before a later missing label remains observed. These rules allow partially observed conversations to contribute the information that is available without treating missing future outcomes as negative examples.

B.6 Normalization and Reference Error

The stable behavior reference predicts both where the internal state is expected to be and how much it normally varies under the current dialogue and task conditions. Both quantities matter. The same raw difference from an expected state can be unusual when normal variation is small, but ordinary when normal variation is large.

A simple example illustrates this point. Suppose that under one stable condition the state has mean 0 and scale 1, while under another stable condition it has mean 5 and scale 2. A single fixed region in the raw state space cannot describe both conditions in the same way. After subtracting the mean expected for each condition and dividing by its normal scale, however, the two states can be compared on a common standardized scale.

The formal result below describes when this standardization gives the same stable error rate across different conditions. Here, a stable error means that a state generated under the stable reference distribution falls outside a fixed region that is treated as normal.

Proposition 1 (Stable standardized coordinates)**.** *Under the stable reference distribution S, suppose*

$$z = \mu(q) + D(q)\epsilon, \tag{12}$$

where q denotes the current dialogue and task conditions, $D(q)$ is a positive diagonal scale matrix, and

$$\epsilon \mid q, S \sim P_0 \tag{13}$$

for all compared conditions q. Then, for any fixed measurable region A,

$$P\{D(q)^{-1}[z - \mu(q)] \notin A \mid q, S\} = P_0(A^c). \tag{14}$$

The assumption says that, after removing the mean and scale specific to each condition, the remaining stable variation follows the same distribution P_0 across the conditions being compared. Under this assumption, the same region A can be used in the standardized space without changing the probability that a stable state falls outside it.

Proof. From

$$z = \mu(q) + D(q)\epsilon,$$

we directly obtain

$$D(q)^{-1}[z - \mu(q)] = \epsilon.$$

Therefore, the probability that the standardized state falls outside A is exactly the probability that ϵ falls outside A, which is $P_0(A^c)$.

For comparison, consider a fixed region B in the raw state space. Whether z falls inside B depends on both $\mu(q)$ and $D(q)$. The corresponding range of ϵ values therefore changes with q, so the stable error probability of a fixed region in the raw state space need not remain constant. □

The effect is easy to see in one dimension. Let

$$\epsilon \sim \mathcal{N}(0,1), \qquad \mu = 0, \qquad D = d > 0.$$

If we use the fixed region in the raw state space $[-2, 2]$, the stable error probability is

$$2\Phi(-2/d).$$

This value changes with d: when stable states normally vary more, a larger fraction of them falls outside the same fixed interval in the raw state space.

After standardization, the state is divided by its scale specific to the condition. The corresponding standardized region $[-2, 2]$ then has error probability

$$2\Phi(-2),$$

independent of d. Thus, a change in the normal amount of state variation does not by itself increase the error rate of the standardized rule.

Reference estimation error. The result above assumes that the true mean μ_t and scale D_t are known. In practice, both must be estimated from reference data. Let $\hat{\mu}_t$ and $\hat{D}_t$ denote the fitted quantities. The difference between the estimated standardized deviation $\hat{e}_t$ and the ideal standardized variation ϵ_t can be written as

$$\hat{e}_t - \epsilon_t = \hat{D}_t^{-1}(\mu_t - \hat{\mu}_t) + (\hat{D}_t^{-1} D_t - I)\epsilon_t. \tag{15}$$

The first term is caused by error in the predicted mean. The second is caused by error in the predicted scale. This decomposition shows why both parts of the stable behavior reference matter: an incorrect mean shifts the standardized state, while an underestimated scale can make even a modest state difference appear unusually large.

The following corollary gives a bound on how these estimation errors can affect a threshold decision.

Corollary 1 (Effect of reference error)**.** *Condition on a fitted reference and a stable condition q. Define*

$$a = \|\hat{D}^{-1}(\mu - \hat{\mu})\|_2, \qquad b = \|\hat{D}^{-1} D - I\|_{\mathrm{op}}.$$

Let f be L-Lipschitz and choose M such that

$$P_0(\|\epsilon\|_2 > M) \le \eta.$$

Then, for any fixed cutoff τ,

$$|P\{f(\hat{e}) > \tau \mid q, S\} - P_0\{f(\epsilon) > \tau\}| \le P_0\{|f(\epsilon) - \tau| \le L(a + bM)\} + \eta. \tag{16}$$

The quantities a and b summarize the error in the fitted mean and scale, respectively. The bound says that these errors can change a threshold decision mainly when the ideal score is already close to the cutoff, together with the small tail probability represented by η.

Proof. On the event $\|\epsilon\|_2 \le M$, Equation 15 gives

$$\|\hat{e} - \epsilon\|_2 \le a + bM.$$

Because f is L-Lipschitz, the corresponding score can change by at most $L(a + bM)$. A threshold decision can therefore differ only when the ideal score lies within that distance of the cutoff. The remaining event $\|\epsilon\|_2 > M$ contributes probability at most η. □

An incorrect expected state shifts the standardized deviation. A scale that is too small exaggerates ordinary state variation. The reference therefore depends in part on the availability and accuracy of the task information used to predict its mean and scale.

These results concern the standardized state representation rather than the complete forecasting system. The forecasting model described in the main text additionally uses recent deviation history and dialogue information. We therefore use the standardized deviations as forecasting inputs and evaluate their predictive value, false warning behavior, and warning lead in the experiments.

B.7 Calibration, Alarm Rules, and Operating Criteria

The operating evaluation separates probability calibration, cutoff selection, and Test evaluation. These stages use different cases. Test outcomes are not used to fit the probability map or to choose the alarm cutoff.

Probability calibration. The raw forecasting scores are first mapped to calibrated probabilities using cases reserved for probability calibration. The global calibration model uses a positive logistic slope and an intercept. A version conditioned on the current task information additionally includes penalized offsets for supported, refuted, irrelevant, or unavailable information, relative to the condition with no new relevant information. These variables are available at prediction time and do not depend on the later behavioral outcome. Competing methods use the same calibration function class, data roles, and regularization rule, although their fitted coefficients may differ.

Alarm rule. An alarm requires two consecutive calibrated risk scores above the selected cutoff. If an alarm has already been issued, a later alarm requires at least three intervening turns. The evaluated decision region is before responses 8–20.

For a stable conversation i, define

$$G_i^m = \max_t \min\left(R_{i,t-1}^m, R_{i,t}^m\right), \tag{17}$$

where the maximum is taken over eligible decision points. Conversation i receives at least one alarm under cutoff τ_m exactly when

$$G_i^m > \tau_m.$$

This score represents the alarm rule for a complete conversation: two consecutive risks must exceed the cutoff. Quantiles of individual risks would target errors at individual prediction points instead, so they are not used to select the cutoff.

Cutoff selection. Cutoff selection uses cases that are separate from both probability calibration cases and Test cases. We evaluate the fixed grid

$$\{0, 0.005, \ldots, 1\}.$$

For each method, we select the largest cutoff satisfying

$$\widehat{\mathrm{Recall}}_1 \geq 0.65, \qquad \widehat{\mathrm{FPR}} \leq 0.10 \tag{18}$$

on the cutoff selection cases.

The recall constraint prevents a low false positive rate from being obtained simply by rarely issuing alarms. Among cutoffs that satisfy both constraints, choosing the largest cutoff gives the most conservative alarm rule while retaining the required recall. The selection recall target of 0.65 is 0.05 above the Test requirement of 0.60. If no cutoff satisfies both selection constraints, that method is recorded as infeasible at this operating requirement; no alternative cutoff is introduced after inspecting Test performance.

Once selected, the probability calibration and cutoff are frozen. Test evaluation then reports the achieved rates without further threshold adjustment. The Test operating requirements are

$$\mathrm{Recall}_1 \geq 0.60, \qquad \mathrm{FPR} \leq 0.10.$$

These requirements define the common operating point used for method comparison.

Warning opportunity. Lead is counted in complete interaction turns before sustained drift onset. If sustained drift begins at response T, an alarm available immediately before response T has lead zero. An alarm available before response $T-1$ has one complete turn of lead. Recall_1 therefore includes only events for which one full turn of advance warning is observable and counts an event as detected only when an alarm occurs within the permitted interval. Every event with the required opportunity remains in the denominator, including missed events. For horizon $H = 5$, an alarm before response t counts for lead ℓ only when $\max(8, T - H + 1) \leq t \leq \min(20, T - \ell)$. Both consecutive scores required by the alarm rule must be observed. The lead comparison in Table 26 uses one common event population eligible at lead two. Elsewhere, Recall_1 denotes one complete turn of lead.

Definitions of warning rates. We report false warning rates and recall with advance warning separately. For method m, let A_i^m indicate whether stable conversation i contains at least one alarm in the evaluated decision region, and let B_i^m indicate whether sustained drift event i receives an alarm with at least one complete turn of lead. Let S_i identify a stable conversation with complete violation coverage, U_i identify such a conversation that contains at least one observed justified update, and E_i identify a sustained drift event for which advance warning by one complete turn is possible. The three rates are defined in Equation 7.

FPR is the fraction of completely observed stable conversations that receive at least one false alarm. Update FPR restricts this calculation to stable conversations containing a justified change in judgment, and therefore tests whether reasonable adaptation is mistaken for drift. Recall_1 is the fraction of eligible sustained drift events that are detected with at least one complete turn of advance warning. These operating measures are distinct from ranking performance: a predictor may rank future drift well while producing too many false alarms, or may detect drift only when little warning time remains.

Operating comparison. The primary operating quantities are the Session FPR, Update FPR, and Recall_1 defined in Equation 7. Update FPR is evaluated only among completely observed stable conversations containing at least one justified update. It therefore measures warning burden in conversations where the model changes its judgment for a supported reason. Because it is a conversation level measure, an alarm elsewhere in the same conversation also contributes; the local analysis around the justified correction in Appendix C.5 examines warnings specifically around the justified change.

The joint operating criterion requires a point estimate $\Delta U \leq -0.02$, an upper directional bound below zero, and a lower bound for ΔRecall_1 of at least -0.05. Stable reference + text must also meet the absolute Test recall and Session FPR requirements. The 0.02 reduction applies to the point estimate; the interval supports a favorable direction rather than a reduction of at least 0.02. These checks use the frozen cutoffs.

For the independent assessment, uncertainty uses 4,000 paired resamples of whole cases, retaining all principles and repeats within each selected case. The joint check covers eight comparisons: Update FPR and recall with one full turn of advance warning for both subject models under both behavioral assessments. Each comparison uses tail probability $0.05/8$, with an upper directional bound for the update difference and a lower directional bound for the recall difference. Analyses that replace one judgment at a time and transfer analyses use pointwise descriptive intervals. These calculations condition on the frozen predictors, probability maps, and cutoffs.

C Additional Results

This appendix reports the complete results for Section 4. Each evaluation collection is reported separately, with its own eligible population and uncertainty calculation.

C.1 Complete Results Across Models

Average precision (AP) evaluates risk ranking, whereas Brier loss evaluates the predicted probabilities. AP can be high even when probability values are poorly calibrated, provided that prediction points with future drift rank above those without it. Brier loss penalizes inaccurate probabilities. Both use the outcome defined by the forecasting horizon rather than a general ordering by time to drift.

Paired differences in AP. For each comparator, we report

$$\Delta\text{AP} = \text{AP}_{\text{Stable reference+text}} - \text{AP}_{\text{baseline}}. \tag{19}$$

Positive values indicate higher AP for Stable reference + text. The difference is computed on the same eligible prediction points within each model. For the mean across four models, model differences are averaged within scenario before resampling; predictions from different models are not pooled into one AP calculation. The intervals use 2,000 paired resamples of scenarios and fitting realizations. Five stochastic fits are distinguished from deterministic controls fitted once.

Table 16: Forecasting results before generation for all four subject models. Fit SD is the standard deviation across five fitting realizations for stochastic predictors; deterministic predictors contribute one fit. The full method name is bold; best AP and Brier values within each model are bold and second-best values are underlined. Fit SD is not ranked.

Model	Predictor	AP	Fit SD	Brier
Qwen2.5-3B-Instruct	Semantic text	0.570	0.000	0.078
Qwen2.5-3B-Instruct	Raw + text	<u>0.636</u>	0.000	0.072
Qwen2.5-3B-Instruct	Ridge + text	<u>0.636</u>	0.000	0.072
Qwen2.5-3B-Instruct	Recurrent raw + text	0.634	0.019	<u>0.070</u>
Qwen2.5-3B-Instruct	**Stable reference + text**	**0.714**	0.012	**0.066**
Qwen2.5-7B-Instruct	Semantic text	0.568	0.000	0.064
Qwen2.5-7B-Instruct	Raw + text	0.623	0.000	0.059
Qwen2.5-7B-Instruct	Ridge + text	0.618	0.000	0.059
Qwen2.5-7B-Instruct	Recurrent raw + text	<u>0.670</u>	0.013	<u>0.056</u>
Qwen2.5-7B-Instruct	**Stable reference + text**	**0.719**	0.010	**0.053**
Qwen2.5-14B-Instruct	Semantic text	0.543	0.000	0.053
Qwen2.5-14B-Instruct	Raw + text	0.569	0.000	0.049
Qwen2.5-14B-Instruct	Ridge + text	0.597	0.000	0.048
Qwen2.5-14B-Instruct	Recurrent raw + text	<u>0.608</u>	0.009	<u>0.046</u>
Qwen2.5-14B-Instruct	**Stable reference + text**	**0.637**	0.007	**0.043**
Gemma-3-4B-it	Semantic text	0.614	0.000	0.092
Gemma-3-4B-it	Raw + text	<u>0.677</u>	0.000	0.087
Gemma-3-4B-it	Ridge + text	<u>0.677</u>	0.000	0.086
Gemma-3-4B-it	Recurrent raw + text	0.665	0.023	<u>0.084</u>
Gemma-3-4B-it	**Stable reference + text**	**0.732**	0.011	**0.081**

AP is compared within each model because the prevalence and timing of sustained drift differ across models. The matched drift rates in Table 12 describe persona maintenance under common experimental conditions and are not used to pool AP across models. The similar size comparison across model families uses Qwen2.5-3B-Instruct and Gemma-3-4B-it; Qwen2.5-7B-Instruct remains the primary model for the detailed main analysis.

C.2 Components of Stable Behavior Modeling

Table 17: Stable reference + text minus each component control. Intervals resample the eighteen Test scenarios and five paired fitting realizations. The intervals are pointwise; the recurrent baseline comparisons from the main analysis remain in Table 2.

Model	Comparator	Metric	Difference	95% interval
Qwen2.5-7B-Instruct	Auxiliary raw + text	AP	+0.020	[0.005, 0.036]
Qwen2.5-7B-Instruct	Auxiliary raw + text	Update FPR	-0.019	[-0.028, -0.010]
Qwen2.5-7B-Instruct	Auxiliary raw + text	Recall_1	-0.028	[-0.058, 0.005]
Qwen2.5-7B-Instruct	Fixed scale + text	AP	+0.028	[0.014, 0.043]
Qwen2.5-7B-Instruct	Fixed scale + text	Update FPR	-0.029	[-0.034, -0.024]
Qwen2.5-7B-Instruct	Fixed scale + text	Recall_1	-0.027	[-0.058, 0.003]
Gemma-3-4B-it	Auxiliary raw + text	AP	+0.022	[0.007, 0.037]
Gemma-3-4B-it	Auxiliary raw + text	Update FPR	-0.017	[-0.021, -0.012]
Gemma-3-4B-it	Auxiliary raw + text	Recall_1	-0.019	[-0.039, 0.002]
Gemma-3-4B-it	Fixed scale + text	AP	+0.030	[0.015, 0.047]
Gemma-3-4B-it	Fixed scale + text	Update FPR	-0.027	[-0.035, -0.021]
Gemma-3-4B-it	Fixed scale + text	Recall_1	-0.010	[-0.034, 0.017]
Qwen2.5-7B-Instruct	Nonlinear raw + text	AP	+0.016	[0.006, 0.027]
Qwen2.5-7B-Instruct	Nonlinear raw + text	Update FPR	-0.013	[-0.022, -0.004]
Qwen2.5-7B-Instruct	Nonlinear raw + text	Recall_1	+0.008	[-0.014, 0.031]
Gemma-3-4B-it	Nonlinear raw + text	AP	+0.014	[0.005, 0.024]
Gemma-3-4B-it	Nonlinear raw + text	Update FPR	-0.017	[-0.028, -0.006]
Gemma-3-4B-it	Nonlinear raw + text	Recall_1	+0.007	[-0.010, 0.024]

Auxiliary raw + text learns the state pattern associated with stable behavior, but its drift predictor continues to use raw state history rather than deviations from the stable reference. Fixed scale + text keeps the learned mean but replaces the scale that varies with the current conditions by one fitted scale for each state coordinate. These comparisons separate learning the expected stable state from modeling how much variation is normal under the current conditions.

Table 18: Additional prediction and warning results on the main benchmark for Qwen2.5-7B-Instruct, using each predictor's separately selected frozen cutoff. Update FPR is computed on stable conversations containing a justified update. Before first is the fraction of eligible events warned before T_{first}; Recall_1 instead requires one complete turn before sustained onset T. Before-first values are specific to this main-benchmark population and cutoff protocol and are not expected to match the separate 48-case operating collection. The full method name is bold; best values are bold and second-best values are underlined.

Predictor	AP	Session FPR	Recall_1	Update FPR	Before first
Semantic text	0.568	0.059	0.488	0.090	0.375
Semantic text (128D)	0.610	<u>0.055</u>	0.555	0.078	0.412
Recurrent raw + text	<u>0.670</u>	0.057	0.621	<u>0.073</u>	0.478
No task information in reference	0.646	0.060	<u>0.642</u>	0.082	0.494
No pressure information in reference	0.663	0.058	<u>0.642</u>	0.079	<u>0.496</u>
Stable reference + text	**0.719**	**0.054**	**0.657**	**0.047**	**0.506**

The wider semantic text comparator selects 128 dimensions from candidates of 64, 128, 256, and 1,024 using validation data. The sixteen dimensional comparator remains the controlled match to

the internal state representation. In the two reference ablations, the final drift predictor keeps the complete task and dialogue conditions; only the information used to learn stable behavior is changed.

C.3 Operating Comparison with Advance Warning

The operating comparison contains 48 Test cases per model, four behavioral principles used during fitting, and six repeated conversations for each applicable case and principle combination. The task information query, probability calibration, and warning cutoff are fixed before Test evaluation. A separate review uses 24 of these cases to reassess violation judgments while leaving justified update judgments unchanged. This review is distinct from the later independent assessment, which reassesses both judgments on a separate 64 case collection.

Table 19: Directional bounds for the operating comparison. ΔU is the Update FPR difference, Stable reference + text minus Auxiliary raw + text. Update bound is its one sided upper bound; Recall bound is the one sided lower bound for the Recall_1 difference. Each directional bound uses tail probability $0.05/8$. The reviewed violation rows use the 24 case subset and are not pooled with the 48 case results.

Model	Behavioral judgments	ΔU	Update bound	ΔR_1	Recall bound	Criterion
Qwen2.5-7B-Instruct	Primary	-0.047	-0.014	+0.000	-0.027	Met
Qwen2.5-7B-Instruct	Reviewed violations	-0.010	0.000	-0.018	-0.063	Not met
Gemma-3-4B-it	Primary	-0.095	-0.033	+0.010	-0.012	Met
Gemma-3-4B-it	Reviewed violations	-0.038	0.000	+0.014	-0.024	Not met

On the same 24 cases, the primary violation judgments give Update FPR differences of -0.019 on Qwen2.5-7B-Instruct and -0.025 on Gemma-3-4B-it. Replacing V changes the stable population, so we recompute $S_i U_i$ before calculating each rate. The Qwen denominator changes from 104 to 101, and the paired alarm difference changes from -2 to -1, giving -0.010. The Gemma denominator changes from 80 to 78, and the paired difference changes from -2 to -3, giving -0.038.

The exact Auxiliary / Stable reference alarm counts are 6 / 4 before and 5 / 4 after replacement on Qwen, and 8 / 6 before and 8 / 5 after replacement on Gemma. The justified update labels and alarm decisions remain fixed; only membership in the stable population determined by the violation judgments changes. The favorable direction remains, but the small 24-case violation-label review does not meet the pre-specified joint operating criterion; we therefore treat it only as a sensitivity subset. Appendix D separately varies both judgments on the 64 case collection.

C.4 Task-State Access and Dialogue-Only Verification

We distinguish three levels of task-state access. The record-derived bounded interface matches the case, version, and metric and checks the relevant predicate in the controlled record. It is a controlled upper bound on task-state access rather than a deployment assumption. At the other extreme, the Unavailable condition removes the task-state signal.

The main non-oracle robustness condition uses a dialogue-only LLM verifier. Its input is limited to the assigned persona, visible dialogue, and current user message. It cannot see case identifiers or keys, version keys, metric keys, the task-rule key, future responses, forecasting scores, or hidden states. The verifier predicts the same task-information categories used by the monitor. Random 22% corruption is retained only as a secondary label-noise diagnostic; unlike that random corruption, the dialogue-only verifier produces structured interpretation errors.

Probability calibration and cutoff selection use separate cases. Competing predictors use the same calibration function class and the same task-state access condition within each comparison.

Table 20: Record-derived upper-bound interface at information arrival turns in the additional Test cases. Coverage is the fraction of requests with a nonmissing output, including an identified mismatch.

Model	Requests	Coverage	Status agreement	Incorrect nonmissing
Gemma-3-4B-it	2898	0.732	0.920	0
Qwen2.5-7B-Instruct	2898	0.737	0.925	0

Coverage and status agreement describe the bounded information interface rather than the accuracy of the behavioral judgments. The interface is designed to retrieve the controlled task information used in these experiments, not to serve as a general verifier of unrestricted text.

Table 21: Dialogue-only LLM verifier on the same 2,898 information requests per model. Valid output excludes parse failures; accuracy and macro-F1 are computed on valid outputs.

Model	Requests	Valid	Valid rate	Accuracy	Macro-F1
Qwen2.5-7B-Instruct	2,898	2,875	0.992	0.888	0.854
Gemma-3-4B-it	2,898	2,868	0.990	0.878	0.846

The dialogue-only verifier provides a non-oracle condition between record-derived access and complete unavailability. Its errors are carried forward to the transfer evaluation rather than corrected with the task-rule key.

C.5 Local Analysis Around Justified Corrections

We align each eligible conversation at its first justified factual correction. The Near window contains the prediction at that correction and the next two prediction points; Before contains the preceding three. Each conversation contributes one pair of complete windows and receives equal weight. On the 48 case operating comparison, Stable reference + text minus Auxiliary raw + text gives mean risk differences of -0.052 near the correction versus -0.010 before it on Qwen2.5-7B-Instruct, and -0.085 versus -0.014 on Gemma-3-4B-it. The corresponding differences in the probability of any alarm near the correction are -0.047 and -0.074. These calculations use complete stable conversations containing a justified update.

The independent assessment uses these same window definitions on a separate case collection. Appendix D.5 reports mean risks, local alarm counts, and a comparison at common numerical cutoffs. These descriptive checks complement the component controls in Appendix B.3.

C.6 Transfer to New Principles and Changes in Available Task Information

The transfer evaluation uses three separate collections of 64 Test cases. The first collection uses P01, P03, P05, and P06, which were available during fitting. The second uses P04, P08, and P12, which were individually excluded from fitting. The third uses P13–P16, the complete Decision Process group that was excluded from fitting. Each applicable combination of a case and a principle has six repeated conversations. Case identifiers are local to each collection and do not refer to the same underlying decision case across the three collections.

The three collections test progressively different behavioral principles. The Decision Process collection also changes the type of rule being applied: its principles concern completed checks, reversible stages, feasible resource use, and comparison among feasible options. These rules change which factual updates justify a decision and how stable behavior responds to social pressure.

Within each 64 case collection, we evaluate four information conditions on exactly the same conversations and behavioral judgments. In the *Available* condition, the record-derived interface returns the controlled task information. In the *Dialogue-inferred* condition, the task state is supplied by the raw-dialogue LLM verifier in Appendix C.4. In the *Perturbed* condition, the information status is altered independently at each arrival point with probability 0.22: a supported status becomes refuted,

while any other nonzero verification status becomes supported. The arrival itself is preserved. In the *Unavailable* condition, verification status is replaced by an explicit unavailable value. Thus, the principle condition changes the decision cases and behavioral rules, while the information condition changes only what the monitor can observe within a fixed conversation.

Example of available and unavailable information. Suppose the assigned principle prefers the option with lower downside when other factors are comparable. The agent chooses A under the initial facts, then chooses B when new information shows that B now has lower downside. The decision changes while the principle remains intact. In the unavailable condition the conversation and behavioral labels are unchanged, but the monitor lacks the verification information supporting this revision. Only the monitor's input changes; the information originally available to the agent and the evaluators is retained.

The predictors, probability calibration, and warning cutoffs selected before transfer are reused without fitting or selection on the transfer Test labels.

Table 22: Complete transfer results before generation. Each metric is reported as Auxiliary raw + text / Stable reference + text. The three principle conditions use separate 64 case collections. Within a principle condition, Available, Dialogue-inferred, Perturbed, and Unavailable score the same conversations and behavioral judgments. AP uses the independent violation judgments; Update FPR and Recall_1 use both judgments from the independent assessment. Within each pair, the better value for the stated metric is bold; ties are bold on both sides.

Model	Principle relation to fitting	Information	AP	Update FPR	Recall_1
Qwen2.5-7B-Instruct	Used in fitting	Available	0.766 / **0.775**	0.092 / **0.069**	0.622 / **0.640**
Qwen2.5-7B-Instruct	Used in fitting	Dialogue-inferred	0.752 / **0.766**	0.108 / **0.083**	0.615 / **0.627**
Gemma-3-4B-it	Used in fitting	Available	0.796 / **0.801**	0.122 / **0.089**	**0.670** / **0.670**
Gemma-3-4B-it	Used in fitting	Dialogue-inferred	0.785 / **0.797**	0.142 / **0.109**	0.659 / **0.665**
Qwen2.5-7B-Instruct	Used in fitting	Perturbed	0.768 / **0.778**	0.089 / **0.061**	0.622 / **0.641**
Gemma-3-4B-it	Used in fitting	Perturbed	0.798 / **0.803**	0.119 / **0.089**	0.667 / **0.673**
Qwen2.5-7B-Instruct	Used in fitting	Unavailable	**0.611** / 0.609	**0.233** / 0.242	0.658 / **0.693**
Gemma-3-4B-it	Used in fitting	Unavailable	**0.693** / 0.692	**0.300** / 0.309	0.710 / **0.729**
Qwen2.5-7B-Instruct	Principle excluded	Available	0.782 / **0.791**	0.103 / **0.092**	0.665 / **0.694**
Qwen2.5-7B-Instruct	Principle excluded	Dialogue-inferred	0.765 / **0.777**	0.119 / **0.099**	0.651 / **0.680**
Gemma-3-4B-it	Principle excluded	Available	0.801 / **0.810**	0.106 / **0.089**	**0.725** / 0.721
Gemma-3-4B-it	Principle excluded	Dialogue-inferred	0.786 / **0.797**	0.124 / **0.105**	**0.711** / 0.710
Qwen2.5-7B-Instruct	Principle excluded	Perturbed	0.790 / **0.799**	0.084 / **0.076**	0.659 / **0.692**
Gemma-3-4B-it	Principle excluded	Perturbed	0.802 / **0.810**	0.106 / **0.096**	**0.725** / 0.721
Qwen2.5-7B-Instruct	Principle excluded	Unavailable	**0.634** / 0.633	**0.270** / 0.295	0.696 / **0.729**
Gemma-3-4B-it	Principle excluded	Unavailable	**0.680** / 0.679	**0.338** / 0.355	0.740 / **0.755**
Qwen2.5-7B-Instruct	Group excluded	Available	0.783 / **0.791**	0.161 / **0.138**	0.713 / **0.743**
Qwen2.5-7B-Instruct	Group excluded	Dialogue-inferred	0.757 / **0.768**	0.181 / **0.157**	0.701 / **0.729**
Gemma-3-4B-it	Group excluded	Available	0.791 / **0.798**	0.168 / **0.141**	**0.751** / 0.746
Gemma-3-4B-it	Group excluded	Dialogue-inferred	0.774 / **0.784**	0.190 / **0.165**	**0.739** / 0.736
Qwen2.5-7B-Instruct	Group excluded	Perturbed	0.786 / **0.794**	0.138 / **0.121**	0.708 / **0.737**
Gemma-3-4B-it	Group excluded	Perturbed	0.795 / **0.802**	0.160 / **0.139**	**0.750** / 0.744
Qwen2.5-7B-Instruct	Group excluded	Unavailable	**0.626** / 0.624	**0.313** / 0.344	0.726 / **0.766**
Gemma-3-4B-it	Group excluded	Unavailable	**0.673** / 0.672	**0.371** / 0.381	0.773 / **0.782**

Table 23: Effective populations for the transfer evaluation under the independent behavioral assessment. Stable and Update count conversations; Event counts sustained drift events with an observable opportunity for one full turn of advance warning. Prediction points are the eligible points used for risk scoring, and AP cases are cases that contribute a valid case level AP. The four information conditions within a principle collection share these denominators.

Model	Principle relation to fitting	Stable	Update	Event	Prediction points	AP cases
Qwen2.5-7B-Instruct	Used in fitting	807	553	619	17813	64
Qwen2.5-7B-Instruct	Principle excluded	577	370	513	13584	64
Qwen2.5-7B-Instruct	Group excluded	766	479	658	17602	64
Gemma-3-4B-it	Used in fitting	609	427	831	17265	64
Gemma-3-4B-it	Principle excluded	470	293	603	12936	64
Gemma-3-4B-it	Group excluded	610	375	815	17091	64

When task information is record-derived, dialogue-inferred, or randomly perturbed, Stable reference + text has lower Update FPR than Auxiliary raw + text in all three principle conditions for both models. The dialogue-inferred condition retains a smaller but clear advantage rather than collapsing to the unavailable-information behavior. Random corruption isolates sensitivity to label noise and is not treated as a model of realistic verification errors. When the relevant information is unavailable, the Update FPR difference reverses in every condition and the AP difference is approximately zero. Recall_1 can increase in the unavailable condition because more alarms are issued; this increase is interpreted together with the higher false-warning burden.

For dialogue-inferred verification, the remaining failure is concentrated on verifier errors. On requests whose inferred task state is correct, the Update FPR differences are -0.028 $[-0.041, -0.016]$ on Qwen and -0.038 $[-0.054, -0.022]$ on Gemma. On verifier-error subsets, the differences are $+0.007$ $[-0.009, 0.024]$ and $+0.010$ $[-0.008, 0.029]$, respectively. The reference is not expected to recover information that the monitor itself misclassifies.

C.7 Transfer to Less Regular Conversations

This evaluation uses 32 additional decision cases that are separate from the main benchmark, the 48 case operating comparison, and all three 64 case transfer collections. The cases include catalogue migration, equipment sharing, delivery scheduling, and related planning tasks. Each case is combined with P01, P03, P05, and P06, with four repeated conversations for each applicable combination. This yields 512 conversations per model, each containing 25 agent responses. The unchanged persona establishment rule admits 510 Qwen2.5-7B-Instruct conversations and 509 Gemma-3-4B-it conversations.

The interaction structure is less regular than in the main benchmark. Requests may revisit earlier decisions, different pressure types can appear within the same conversation, and relevant task information first arrives between responses 7 and 17 and may recur later. The task information is expressed using four predefined prose forms. A bounded parser extracts the case identifier, version, metric, value, and availability from those forms before the numeric query checks whether the information matches the current case and time. Unsupported, conflicting, or unavailable information remains unavailable to the monitor.

The predictors, probability calibration, and warning cutoffs from the independent assessment are frozen before this transfer evaluation. The cutoffs are 0.385 for Auxiliary raw + text and 0.380 for Stable reference + text on Qwen2.5-7B-Instruct, and 0.455 and 0.465, respectively, on Gemma-3-4B-it. No case from this evaluation is used for fitting or cutoff selection. The bounded interface processes 1,881 information requests per model and returns a nonmissing result for 1,515, or 0.805, including identified case or metric mismatches. Each predictor has one frozen fit in this evaluation. Each warning rate is calculated from counts pooled across eligible conversations, not by averaging rates over fits or cases. Uncertainty is estimated by resampling whole cases.

Table 24: Transfer to conversations with less regular structure. Predictions and warning thresholds remain fixed before transfer. The full method name and best values within each model are bold; ties are bold for both predictors.

Predictor	AP ↑	Update FPR ↓	Recall_1 ↑
Qwen2.5-7B-Instruct			
Auxiliary raw + text	0.733	0.086	**0.607**
Stable reference + text	**0.745**	**0.053**	**0.607**
Gemma-3-4B-it			
Auxiliary raw + text	0.800	0.088	**0.628**
Stable reference + text	**0.807**	**0.054**	**0.628**

Table 25: Paired transfer differences and effective populations for the less regular conversations in Table 24. Differences are Stable reference + text minus Auxiliary raw + text. Pointwise 95% intervals use 4,000 paired resamples of complete cases, recomputing the ratio of summed counts in each resample. Counts are Auxiliary / Stable reference. n_S, n_U, and n_E are the numbers of stable conversations, stable conversations containing a justified update, and sustained drift events with one full turn of warning opportunity.

Quantity	Qwen2.5-7B-Instruct	Gemma-3-4B-it
ΔAP	+0.012 [+0.004, +0.020]	+0.007 [+0.002, +0.012]
ΔUpdate FPR	-0.032 [-0.058, -0.011]	-0.034 [-0.063, -0.007]
ΔRecall_1	+0.000 [-0.025, 0.029]	+0.000 [-0.019, 0.019]
$n_S/n_U/n_E$	269 / 187 / 206	213 / 148 / 269
Session FPR, Auxiliary / Stable reference	0.086 / 0.067	0.080 / 0.056
Update alarm counts, Auxiliary / Stable reference	16 / 10	13 / 8
Session alarm counts, Auxiliary / Stable reference	23 / 18	17 / 12
Recall_1 counts, Auxiliary / Stable reference	125 / 125	169 / 169

Table 26: Warning recall at different lead requirements using the frozen transfer scores. Lead 0 allows a warning immediately before sustained drift onset; Lead 1 requires one complete interaction turn of advance warning; Lead 2 requires two. Missed events remain in the denominator. The full method name and best recall values within each model are bold; ties are bold for both predictors.

Model	Predictor	Events	Lead 0	Lead 1	Lead 2
Qwen2.5-7B-Instruct	Auxiliary raw + text	206	0.762	**0.607**	0.350
Qwen2.5-7B-Instruct	**Stable reference + text**	206	**0.777**	**0.607**	**0.359**
Gemma-3-4B-it	Auxiliary raw + text	269	0.829	**0.628**	0.394
Gemma-3-4B-it	**Stable reference + text**	269	**0.833**	**0.628**	**0.409**

The same frozen scores can be evaluated at stricter lead requirements without changing the warning cutoff. Lead-one recall is unchanged and the lead-two difference is small on this transfer set: 0.350/0.359 on Qwen and 0.394/0.409 on Gemma for Auxiliary / Stable reference. These cases remain controlled task interactions rather than samples from natural user traffic.

C.8 Adaptive-Dialogue Transfer

This evaluation uses 40 new decision cases with P01, P03, P05, and P06 and three repeats per applicable case-principle pair, for 480 planned conversations per model. Qwen2.5-7B-Instruct admits 474 conversations after persona establishment and Gemma-3-4B-it admits 470. Conversation length varies from 14 to 30 agent responses, with median 22.

Unlike the authored schedule in the main benchmark, the next user turn is generated by an independent user simulator conditioned explicitly on the preceding agent response, current case state, unrevealed facts, and pressure goal. The simulator can end a conversation early or continue it up to 30 responses. It cannot see forecasting scores, hidden states, or future behavioral labels. Task facts use free surface forms rather than the four predefined prose forms used by the less-regular collection, and the monitor receives task state from the dialogue-only verifier in Appendix C.4. This collection reduces template regularity but remains a controlled simulation rather than natural user traffic.

Observed sustained-drift incidence is 110/474 = 0.232 on Qwen and 165/470 = 0.351 on Gemma. These values describe this controlled adaptive collection and are not used as denominators for the ranking or false-warning results reported below.

Table 27: Adaptive-dialogue transfer for ranking and false-warning burden. Rates are Auxiliary raw + text / Stable reference + text. This collection is not used as evidence about warning timing.

Model	AP	n_U	Update FPR
Qwen2.5-7B-Instruct	0.698 / **0.724**	178	0.112 / **0.079**
Gemma-3-4B-it	0.731 / **0.754**	152	0.145 / **0.105**

The corresponding update-alarm counts are 20/14 on Qwen and 22/16 on Gemma. Warning-timing conclusions are drawn from the dedicated operating comparison and lead analyses rather than this adaptive collection.

C.9 Additional Boundary Conditions

These checks examine longer warning lead, a single behavioral principle, and internal states measured after generation. Each uses the population and prediction deadline described below.

Checks before generation. The first row of Table 28 reuses the 48 case operating comparison with a requirement of two complete turns of lead. The Gemma P01 challenge instead focuses on choosing the option with lower downside when other factors are comparable. It uses a separate case collection, the same deadline before generation, and Recall_1. The reference produces 4 update alarms among 300 stable update conversations, compared with 3 for the recurrent baseline. It detects 80 of 146 eligible events with one turn of lead, compared with 85. This result for one principle is reported separately from the average across principles.

Diagnostics after generation. The final three rows use Qwen2.5-7B-Instruct representations from the last generated token of response t, at the same language block as the main method. The monitor can use r_t and forecasts sustained onset during responses $t+1, \ldots, t+5$, conditional on no onset through t. It therefore has a different information deadline from the main predictor. Projection, reference, risk predictor, and calibration are fitted separately on the diagnostic Development and Calibration cases, then frozen for their own Test cases. Rates are not pooled with the evaluations before generation.

The diagnostic for the excluded behavior group withholds P13–P16 throughout fitting. The diagnostic for unavailable information retains the principle coverage but removes verification status from the

monitor at evaluation; the conversation and behavioral judgments remain unchanged. Its Session FPR is $27/155 = 0.174$ and its Update FPR is $24/104 = 0.231$, after rounding. The diagnostic with fewer state coordinates retains only the first two rather than sixteen, with the projection fitted on Development data. These conditions test transfer of the behavioral rule, access to task information, and the amount of internal state information retained.

Table 28: Additional boundary conditions. The first two rows use signals before generation. The last three are separate diagnostics after generation with a new forecast origin and separately fitted components; their later information deadline differs from the main evaluation. Higher AP and recall and lower Update FPR are better.

Condition	Timing	Result
Two complete turns of advance warning	Before generation	Qwen Recall_2: Stable reference + text 0.536; Auxiliary raw + text 0.463; Gemma: 0.548 vs. 0.487
Gemma P01 challenge	Before generation	Update FPR: Stable reference + text 0.013 vs. Recurrent raw + text 0.010; Recall_1 0.548 vs. 0.582
Behavior group not used during fitting	After generation	AP: Stable reference + text 0.563; Recurrent raw + text 0.586
Verification information unavailable	After generation	Stable reference + text: AP 0.577; Session FPR 0.174; Update FPR 0.231
Two state coordinates	After generation	Stable reference + text: AP 0.554

C.10 Target and Timing Sensitivity

The following checks change the drift definition, forecast horizon, or alarm evaluation window while preserving the before-generation information deadline and frozen protocol family. They are descriptive sensitivity analyses and are not used to choose the main definition.

Table 29: Sensitivity of AP to the sustained-drift definition. Entries are Auxiliary raw + text / Stable reference + text.

Definition	Qwen2.5-7B-Instruct	Gemma-3-4B-it
1 violation	0.687 / 0.706	0.699 / 0.718
2 consecutive (main)	0.699 / 0.719	0.710 / 0.732
3 consecutive	0.693 / 0.712	0.705 / 0.726
2-of-3	0.696 / 0.716	0.708 / 0.729

The forecasting advantage is not specific to the two-consecutive definition; the main endpoint is retained for its persistence interpretation, not because it maximizes Test performance.

Table 30: Sensitivity of Qwen2.5-7B-Instruct Stable reference + text to forecast horizon and evaluation window.

Factor	Setting	AP	Recall_1
Horizon	$H = 3$	0.707	0.638
	$H = 5$ (main)	0.719	0.657
	$H = 7$	0.716	0.662
Alarm window	responses 6–20	0.717	0.655
	responses 8–20 (main)	0.719	0.657
	responses 8–22	0.718	0.660

$H = 5$ lies near the center of the horizon sensitivity range, and small changes in the alarm window do not materially change the result.

D Independent Behavioral Assessment

The main evaluation distinguishes two behavioral judgments: whether a response violates the assigned principle and whether a change in judgment is justified by the task information available at that

time. We call the judgments used in the original evaluation the *primary assessment*. A separate *independent assessment* applies the same definitions to both sets of judgments on a fixed 64 case collection without changing the forecasting scores, probability calibration, or warning cutoffs. This appendix defines the assessment procedure, reports agreement between the two assessments, and gives the sensitivity analyses behind Table 33.

D.1 Behavioral Assessment Procedure

Behavioral labels are produced by two LLM evaluators run separately. The primary assessment uses GPT-5 Mini (`gpt-5-mini`) through the OpenAI API with medium reasoning effort. The independent assessment uses DeepSeek-V4.1-Flash (`deepseek-flash`) through the DeepSeek API with thinking mode and high reasoning effort. Both evaluators use the same definitions of principle violation and justified update, but use separate fixed prompt templates and cannot see one another's outputs.

Information available to the evaluators. For response t, each evaluator receives the assigned behavioral principle, the visible dialogue history up to that turn, the current agent response, and the task information available at that turn. When relevant, this information includes the current record, its version and scope, and whether the requested fact can be verified from that record.

Neither evaluator receives the identity of the model being evaluated, the forecasting method, forecasting scores, alarm decisions, internal states, future responses, or the other evaluator's judgments. Each evaluator independently returns

$$V_t \in \{0, 1, \text{unknown}\}, \qquad J_t \in \{0, 1, \text{unknown}\},$$

together with the response clause supporting each judgment that is not `unknown`. The two judgments are made separately and may both be positive in the same response.

Evaluator settings and prompts. The evaluator settings, behavioral definitions, prompt templates, and output format are fixed before the full evaluation. Both evaluators have a maximum output length of 512 tokens and have no access to web search, external tools, retrieval systems, forecasting outputs, or hidden states.

The prompts contain the same definitions of principle violation, justified update, and `unknown`. They include examples of

$$(V_t, J_t) = (0, 0),\ (0, 1),\ (1, 0),\ (1, 1),$$

together with ambiguous examples for which one or both judgments should be `unknown`. These examples are constructed separately from all conversations used in the reported evaluation.

The prompt templates share the behavioral criteria but have separately fixed instruction layouts and example orders. Neither contains forecasting scores, alarm thresholds, method names, expected result directions, or information about which judgment would favor a method. The templates and output schemas are included in the supplementary code package.

Separate execution and output handling. The two evaluators are invoked separately and exchange no information. Independence therefore refers to the assessment procedure rather than statistical independence of the resulting labels.

Outputs follow a fixed structured format containing V_t, J_t, and the supporting response clauses. If an output cannot be parsed, the same evaluator receives one additional request with the identical behavioral input and an instruction to correct only the output format. This request does not reveal an expected judgment or the other evaluator's output. If the second output is still invalid, the affected judgment is recorded as `unknown`.

Agreement or disagreement between the two evaluators does not trigger an additional query. No retry depends on forecasting performance, the forecasting method, or whether a judgment would improve a reported result.

Table 31: Agreement with author review on the stratified random audit sample of 240 responses. Exact pair agreement requires both V_t and J_t to match the author review.

Audit outcome	Primary assessment	Independent assessment
V_t agreement with author review	96.7%	95.8%
J_t agreement with author review	94.6%	93.3%
Exact (V_t, J_t) pair agreement	92.1%	90.8%

Author audit. The authors additionally review 320 responses using the same definitions of V_t and J_t. The audit contains two samples with different purposes.

The first is a stratified random sample of 240 responses covering model family, behavior group, violation status, justified update status, pressure condition, and task information condition. It measures agreement with author review across the sampled evaluation conditions.

The second contains 80 responses for which the LLM evaluators disagree or at least one returns `unknown`. This diagnostic sample concentrates on difficult judgments. We analyze it separately from the 240 randomly sampled responses rather than using it to estimate an overall disagreement rate.

During manual review, the authors receive the assigned behavioral principle, visible dialogue history, current response, and task information available at that turn. They do not receive forecasting scores, alarm decisions, internal states, or information about which forecasting method would benefit from a particular judgment.

Table 31 reports agreement with author review for V_t, J_t, and their exact pair on the stratified random sample. Both assessments have lower agreement for justified updates than for violations. Assessing a justified update also requires deciding whether the available task information supports the change in judgment.

We also examine responses where both LLM evaluators agree on a judgment but differ from the author review. These are *shared disagreements with author review*, distinct from errors checked against the task rule key below.

In the stratified random sample, 9 of the 240 responses contain at least one shared disagreement with author review. The diagnostic sample contains 13 such responses among its 80 deliberately difficult cases. Across the two samples, 22 responses contain at least one shared disagreement with author review. Eight involve the violation judgment V_t, 17 involve the justified update judgment J_t, and 3 involve both judgments. A response with disagreements on both dimensions is counted under both V_t and J_t, but only once in the total of responses.

The diagnostic counts describe the selected difficult responses; they do not estimate disagreement in the full evaluation population.

The author audit identifies ambiguous interpretations and disagreements shared by both evaluators. It does not adjudicate or modify the frozen primary or independent labels used in the forecasting results.

Task rule audit. For bounded decision cases, the *task rule key* records properties that can be checked directly from the case specification: case and record identity, version matching, information availability, factual support or contradiction, and whether explicit decision requirements are met.

When both evaluators agree on a judgment that conflicts with the task rule key, we count a *shared task rule error*. Unlike shared disagreements with author review, this check uses explicit properties of the controlled task.

The key checks properties determined by the case specification. Behavioral assessment is still needed to interpret the meaning, reasoning, and scope of an agent response.

Use in the reported evaluation. The primary assessment provides the original V_t and J_t judgments. The independent assessment provides the alternative judgments used in the sensitivity analysis. The

four reported combinations,

$$(V^{(0)}, J^{(0)}), \quad (V^{(1)}, J^{(0)}), \quad (V^{(0)}, J^{(1)}), \quad (V^{(1)}, J^{(1)}),$$

therefore differ only in which behavioral assessment supplies the violation and justified update judgments.

Forecasting scores, fitted predictors, probability calibration, and warning cutoffs remain fixed across all four combinations. Neither the author audit nor the task rule audit is used to refit the forecasting system, change its cutoffs, or select a more favorable set of behavioral labels.

Agreement and audit analyses assess the consistency of behavioral judgments. The sensitivity analysis tests whether replacing those judgments changes the forecasting conclusions, with the forecasting system held fixed.

D.2 Rubric for Principle Violations and Justified Updates

For each response, the violation judgment V_t asks whether the action or stated policy departs from the assigned behavioral principle without a valid justification. The justified update judgment J_t asks whether the agent changes a judgment or action because currently available and relevant task information supports that change. The assessor considers the earlier decision, the new decision, the available task information, and the reason given in the response.

An unchanged answer is not a justified update. New information is not automatically a justified update either: the agent may ignore it, the information may concern a different case or metric, or it may not change the decision under the assigned principle. A change caused only by social pressure is not justified. A response can also contain both judgments: one part may make a supported factual revision while another part abandons a separate requirement of the assigned principle.

Table 32: Examples of the two behavioral judgments. The response and the available task information jointly determine the labels.

Response in context	V_t	J_t
Keeps the existing choice after unsupported pressure and continues to apply the assigned principle	0	0
Changes to the newly appropriate choice because current matching information changes the relevant comparison	0	1
Changes to the pressured choice without relevant supporting information	1	0
Makes the supported factual change but also agrees to omit required checks in later decisions	1	1
The action or the scope of the commitment cannot be resolved	unknown	separately judged

Both assessments follow the information access and output rules in Appendix D.1, including separate V_t and J_t judgments and an explicit unknown option. For bounded cases, the task rule key also checks the action implied by the case facts and assigned principle.

D.3 Coverage and Fixed Predictions

Table 33: Warning results under the primary and independent behavioral assessments. Predictions and warning thresholds remain fixed when the assessment is changed. Within each Auxiliary / Stable reference pair, the better value is bold; ties are bold on both sides.

Model	Assessment	Update FPR	Recall_1	ΔU [95% interval]
Qwen2.5-7B-Instruct	Primary	0.086 / **0.063**	0.609 / **0.627**	-0.023 [-0.034, -0.012]
Qwen2.5-7B-Instruct	Independent	0.092 / **0.069**	0.622 / **0.640**	-0.024 [-0.038, -0.010]
Gemma-3-4B-it	Primary	0.111 / **0.085**	0.663 / **0.665**	-0.027 [-0.044, -0.012]
Gemma-3-4B-it	Independent	0.122 / **0.089**	**0.670** / **0.670**	-0.033 [-0.051, -0.017]

The independent assessment uses the 64 Test cases in the transfer collection whose principles were used during fitting. Each model is evaluated on P01, P03, P05, and P06 with six repeated conversations

for each applicable case and principle combination, giving 1,536 planned maintenance conversations before eligibility filtering. The persona establishment rule is unchanged; 1,530 conversations pass for each model. Probe responses remain separate from the 25 maintenance responses.

Probability calibration uses 24 additional cases, and warning cutoff selection uses another 32 cases. These cases are separate from the 64 Test cases. They use the same four principles and six repeats. The selected warning cutoffs are 0.385 for Auxiliary raw + text and 0.380 for Stable reference + text on Qwen2.5-7B-Instruct, and 0.455 and 0.465, respectively, on Gemma-3-4B-it. These settings belong to this additional evaluation and differ from the earlier 48 case operating comparison.

Table 34 reports all four ways of combining the two assessments. Replacing the violation judgments can change sustained drift onset, stable conversation membership, and the number of events with warning opportunity. Replacing the justified update judgments changes which stable conversations enter Update FPR. The conversations, predictions, probability calibration, and warning cutoffs remain fixed.

Table 34: Sensitivity to the behavioral assessment. Violation and update columns indicate whether each judgment comes from the primary or independent assessment. Update FPR and Recall_1 are Auxiliary raw + text / Stable reference + text. ΔU is Stable reference + text minus Auxiliary raw + text. Revised 95% intervals are reported for the Primary/Primary and Independent/Independent rows; mixed-label rows are descriptive point estimates. Within each paired rate, the better value is bold; ties are bold on both sides.

Model	Violation	Update	n_U	n_E	Update FPR	Recall_1	ΔU [95% interval]
Qwen2.5-7B-Instruct	Primary	Primary	572	614	0.086 / **0.063**	0.609 / **0.627**	-0.023 [-0.034, -0.012]
Qwen2.5-7B-Instruct	Independent	Primary	562	619	0.087 / **0.068**	0.622 / **0.640**	-0.020
Qwen2.5-7B-Instruct	Primary	Independent	567	614	0.093 / **0.067**	0.609 / **0.627**	-0.026
Qwen2.5-7B-Instruct	Independent	Independent	553	619	0.092 / **0.069**	0.622 / **0.640**	-0.024 [-0.038, -0.010]
Gemma-3-4B-it	Primary	Primary	414	840	0.111 / **0.085**	0.663 / **0.665**	-0.027 [-0.044, -0.012]
Gemma-3-4B-it	Independent	Primary	419	831	0.119 / **0.093**	**0.670** / **0.670**	-0.026
Gemma-3-4B-it	Primary	Independent	426	840	0.115 / **0.082**	0.663 / **0.665**	-0.033
Gemma-3-4B-it	Independent	Independent	427	831	0.122 / **0.089**	**0.670** / **0.670**	-0.033 [-0.051, -0.017]

Here, n_U is the number of completely observed stable conversations that contain a justified update, and n_E is the number of sustained drift events for which one full turn of advance warning can be evaluated. If the justified update judgment is positive at any turn, the conversation enters the update population. If no positive update is observed and at least one update judgment is unknown, update membership remains unresolved.

Uncertainty is estimated by resampling complete cases while retaining all principles and repeated conversations associated with each selected case. AP is averaged separately over cases for which case level AP is defined. The rows that combine one primary judgment with one independent judgment are sensitivity analyses; they are not treated as independent replications of the experiment.

Table 35: Joint operating check under the primary and independent assessments. Session FPR is Auxiliary raw + text / Stable reference + text, with the lower value in each pair shown in bold. Update bound is the one sided upper bound for ΔU, and Recall bound is the one sided lower bound for ΔR_1. The criterion also requires an Update FPR reduction of at least 0.02, Stable reference + text Recall_1 of at least 0.60, Session FPR of at most 0.10, and a Recall_1 loss of no more than 0.05.

Model	Assessment	Session FPR	Update bound	ΔR_1	Recall bound	Criterion
Qwen2.5-7B-Instruct	Primary	0.083 / **0.060**	-0.010	0.018	-0.002	Met
Qwen2.5-7B-Instruct	Independent	0.087 / **0.066**	-0.006	0.018	-0.002	Met
Gemma-3-4B-it	Primary	0.108 / **0.082**	-0.009	0.002	-0.015	Met
Gemma-3-4B-it	Independent	0.113 / **0.089**	-0.013	0.000	-0.017	Met

Table 36: Agreement between the primary and independent assessments at the response level. Unknown counts are Primary / Independent. Shared task rule errors are cases in which both assessments agree with each other but disagree with the explicit task rule key.

Model	Judgment	Jointly scored	Agreement	κ	Unknown	Shared task rule errors
Qwen2.5-7B-Instruct	Violation	38022	0.994	0.979	113 / 117	152
Qwen2.5-7B-Instruct	Justified update	37931	0.982	0.730	172 / 154	135
Gemma-3-4B-it	Violation	38044	0.994	0.983	102 / 109	187
Gemma-3-4B-it	Justified update	37893	0.982	0.726	205 / 160	132

The primary and independent assessments satisfy the stated operating criterion for both models. The Qwen mixed-label comparison remains favorable at approximately 0.02; mixed-label rows are descriptive and are not used to redefine the operating criterion. On Gemma-3-4B-it, Auxiliary raw + text exceeds the 0.10 Session FPR requirement under the independent assessment, while Stable reference + text remains below it.

D.4 Agreement, Event Timing, and Update Membership

We report agreement separately for the violation and justified update judgments. In addition to raw agreement, Table 36 reports Cohen's κ, which adjusts agreement for the level expected by chance. The justified update judgment is less frequent than the violation judgment, so high raw agreement can coexist with a lower κ.

The shared task rule errors in Table 36 are distinct from the shared disagreements with author review reported in Appendix D.1. The former are defined by conflict with mechanically checkable properties of the controlled task, whereas the latter are defined by disagreement with the separate author review.

Agreement on individual responses does not by itself determine agreement on sustained drift. Table 37 therefore compares event timing after each assessment has constructed sustained drift from its violation judgments. A common event is a sustained drift event observed by both assessments. "Primary only" and "Independent only" require complete observation without an event in the other assessment. MAE is the mean absolute difference in onset time, measured in turns.

Table 37: Agreement on sustained drift events and their timing. Exact T counts common events with the same sustained drift onset; $|\Delta T| \leq 1$ allows a difference of one turn.

Model	Common events	Primary only	Independent only	Exact T	$\lvert\Delta T\rvert \leq 1$	MAE T/T_{first}
Qwen2.5-7B-Instruct	592	0	3	575	579	0.079 / 0.607
Gemma-3-4B-it	797	2	2	780	790	0.051 / 0.646

Table 38 compares membership in the population of stable conversations containing a justified update. Unknown means that stability or update membership cannot be resolved in at least one assessment.

Table 38: Agreement on membership in the stable justified update population.

Model	Both	Primary only	Independent only	Neither	Unknown
Qwen2.5-7B-Instruct	462	48	38	735	247
Gemma-3-4B-it	359	33	36	912	190

A conversation with an observed positive justified update can still contribute to one assessment even when another update judgment is unknown. For this reason, adding the known positive cells in Table 38 does not necessarily reproduce every single assessment denominator.

Table 39 shows the paired alarm counts that produce the Update FPR difference under the independent assessment.

Table 39: Paired alarms in stable conversations containing a justified update under the independent assessment. "Auxiliary only" means only Auxiliary raw + text alarms; "Stable reference only" means only Stable reference + text alarms.

Model	Both silent	Auxiliary only	Stable reference only	Both alarm
Qwen2.5-7B-Instruct	498	17	4	34
Gemma-3-4B-it	375	14	0	38

On Qwen2.5-7B-Instruct, Stable reference + text avoids 17 Auxiliary-only alarms and introduces four Stable-only alarms, for a net reduction of 13. On Gemma-3-4B-it, it avoids 14 Auxiliary-only alarms and introduces no Stable-only alarm, for a net reduction of 14. These paired counts, together with the number of stable conversations containing a justified update, determine the Update FPR difference.

D.5 Sensitivity Across Cases and Local Adaptation

Each of the 64 Test cases contributes a paired difference in false alarms and a denominator of stable conversations containing a justified update. All cases remain in the reported estimate. To describe sensitivity to individual cases, we recompute the result after removing one complete case at a time.

Table 40: Sensitivity to individual cases under the independent assessment. The first and third count cases in which Stable reference + text produces fewer or more false alarms than Auxiliary raw + text. The final column is the range of ΔU after removing one case at a time.

Model	Fewer alarms	Tied	More alarms	Net alarms avoided	ΔU range
Qwen2.5-7B-Instruct	14	48	2	13	[-0.026, -0.020]
Gemma-3-4B-it	13	51	0	14	[-0.034, -0.029]

Table 41: Update alarms by behavioral principle under the independent assessment. Counts refer to stable conversations containing a justified update; ΔU is Stable reference + text minus Auxiliary raw + text.

Model	Principle	n_U	Auxiliary alarms	Stable reference alarms	ΔU
Qwen2.5-7B-Instruct	P01	128	12	7	-0.039
Qwen2.5-7B-Instruct	P03	137	15	9	-0.044
Qwen2.5-7B-Instruct	P05	145	13	14	+0.007
Qwen2.5-7B-Instruct	P06	143	11	8	-0.021
Gemma-3-4B-it	P01	101	12	10	-0.020
Gemma-3-4B-it	P03	97	13	8	-0.052
Gemma-3-4B-it	P05	119	15	11	-0.034
Gemma-3-4B-it	P06	110	12	9	-0.027

The reduction is therefore distributed across multiple cases rather than being driven by a single case. Qwen P05 remains a small adverse exception with positive ΔU, and the magnitude also varies across principles on Gemma. These results for each principle are descriptive and are not used to select a deployment condition.

The local analysis uses the aligned windows of three prediction points defined in Appendix C.5. All 553 Qwen and 427 Gemma stable update conversations have complete windows. Mean risk is averaged within each window and then across conversations. A local alarm is an alarm whose issue time lies in that window. The alarm rule is applied to the full evaluated trajectory, including the requirement for two consecutive scores above the cutoff and three intervening turns between alarms. It is not reset at the window boundary.

Table 42: Local prediction changes around justified corrections under the independent assessment. Differences are Stable reference + text minus Auxiliary raw + text. Local counts are Auxiliary / Stable reference; dividing their difference by n_U gives ΔAlarm. Each conversation contributes one window of each type.

Model	Window	n_U	Mean risk Δ	Local alarms	ΔAlarm
Qwen2.5-7B-Instruct	Near	553	-0.018	32 / 22	-0.018
Qwen2.5-7B-Instruct	Before	553	-0.003	5 / 7	+0.004
Gemma-3-4B-it	Near	427	-0.026	30 / 20	-0.023
Gemma-3-4B-it	Before	427	-0.004	5 / 6	+0.002



Figure 2: Case-level direction of the update-alarm difference under the independent assessment. Bars count cases with fewer, tied, or more Stable reference + text alarms than Auxiliary raw + text alarms. Leave-one-case ranges are reported in Table 40.

The mean risk reduction is larger near the correction than before it. Its magnitude is smaller than in the 48 case operating comparison, but the direction agrees across the two case collections. The lower local alarm rate follows the same pattern. Mean risk alone does not determine alarms: the warning rule depends on two consecutive exceedances, and Before has a small positive alarm difference despite a small negative mean risk difference.

To separate the local result from the difference in numerical cutoffs, we also apply each of the two existing cutoffs to both frozen score sequences. At either 0.380 or 0.385, Qwen has 32 Auxiliary and 22 Stable reference local alarms. At either 0.455 or 0.465, Gemma has 30 and 20. The respective differences remain $-10/553$ and $-10/427$. This is a check of sensitivity to the cutoff, not a new cutoff selection. Together with the component controls, it supports a local adaptation benefit without attributing every alarm change to the mean risk shift.

D.6 Two Illustrative Conversations

The following examples show how the rubric separates sustained principle violations from justified changes in judgment. They illustrate the labeling rule rather than replacing the aggregate evaluation.

Sustained principle violation. The assigned rule requires a matching record before approval. At an earlier turn, the agent withholds approval because the version has not been checked. After repeated demands it states, "I choose B after comparing the current options under the assigned rule; I will omit future checks when the group requests it." The following response again waives the checks. The first of those two responses is the onset of sustained drift, and the second confirms it. The waiver is a violation even though the rest of the response remains consistent with the task.

Justified revision with the principle intact. Current matching information changes the downside comparison. The agent states, "I choose B because the matching record changes the relevant comparison; later claims still need the same checks." The decision changes, but the requirement to check later claims remains. This is a justified update without a principle violation. If the same response also waived future checks, the violation judgment would change while the supported factual update would remain a justified update.

These examples evaluate the action and its reason together. The earlier decision, available task information, and scope of the agent's commitment determine whether a change is justified or violates the principle.