NEUROFAITH: Evaluating Mechanistic Faithfulness of LLM Free Text Self-Explanation at the Concept Level

Milan Bhan
milan.bhan@ekimetrics.com
Ekimetrics, Sorbonne Université, LIP6, Mila - Quebec AI Institute

Jean-Noël Vittaut
jean-noel.vittaut@lip6.fr
Sorbonne Université, LIP6

Nicolas Chesneau
nicolas.chesneau@ekimetrics.com
Ekimetrics

Sarath Chandar
sarath.chandar@mila.quebec
Chandar Research Lab, Mila - Quebec AI Institute,
Polytechnique Montréal, Canada CIFAR AI Chair

Marie-Jeanne Lesot
marie-jeanne.lesot@lip6.fr
Sorbonne Université, LIP6

Abstract

Large Language Models (LLMs) can generate plausible free text self-explanations to justify their answers. However, these natural language explanations may not accurately reflect the model's actual reasoning process, indicating a lack of faithfulness. Existing faithfulness evaluation methods rely primarily on behavioral tests or computational block analysis without examining the semantic content of internal neural representations. This paper proposes NEUROFAITH, a flexible framework that measures the faithfulness of LLM free text self-explanation by identifying key concepts within explanations and mechanistically testing whether these concepts actually influence the model's predictions. We show the versatility of NEUROFAITH across 2-hop reasoning and classification tasks. Additionally, we develop a linear faithfulness probe based on NEUROFAITH to detect unfaithful self-explanations from representation space and improve faithfulness through steering. NEUROFAITH provides a principled approach to evaluating and enhancing the faithfulness of LLM free text self-explanations, addressing critical needs for trustworthy AI systems.

1 Introduction

Autoregressive Large Language Models (LLMs) can generate plausible self Natural Language Explanation (self-NLE) to support their answers (Wiegreffe & Marasovic, 2021; Huang et al., 2023). Generating self-NLE consists of prompting the LLM to output an explanation in a *predict-then-explain* setting, where the model first generates a response to a question and then produces a self-NLE as a justification. Unlike their non-generative predecessors, modern LLMs are trained to generate both answers and free text self-NLE that appear credible despite potentially containing persuasive hallucinations (Sahoo et al., 2024). This way, despite their logical and coherent appearance favoring trust in the model (Han et al., 2023), LLM-generated self-NLEs turn out to not systematically reflect the actual underlying decision-making process of the model, creating a tension between self-NLE *plausibility* and *faithfulness* (Agarwal et al., 2024). Faithfulness, as defined by Jacovi & Goldberg (2020), measures "*how accurately the explanation reflects the true reasoning process of the model*", a definition widely adopted in the literature (Lyu et al., 2024) and which we also follow throughout this

40th Conference on Neural Information Processing Systems (NeurIPS 2026).

work. Unfaithful self-NLE can have serious consequences in critical domains (Farah et al., 2023), where explanations that appear plausible but lack faithfulness might lead end-users to over-rely on model predictions and make unfair (Luo et al., 2022) or harmful (Kayser et al., 2024) decisions. The combination of the widespread adoption of LLMs and the simplicity of generating self-NLE through prompting make evaluating their faithfulness increasingly critical.

Assessing self-NLE faithfulness presents profound difficulties due to the free-form nature of natural language explanations, unlike more structured explainability methods such as attribution (Wiegreffe et al., 2021) or counterfactual approaches (Madsen et al., 2024). Numerous methods (detailed in Section 2) have been developed to measure self-explanation faithfulness (Lyu et al., 2024). However, (1) they mostly perform behavioral tests and do not examine LLM internal reasoning processes (Atanasova et al., 2023; Siegel et al., 2024, 2025; Matton et al., 2025), and (2) they identify the computational blocks that contribute to prediction and self-NLE without conducting semantic analysis of the neural representations within these blocks (Wiegreffe et al., 2021; Parcalabescu & Frank, 2024; Yeo et al., 2025). These shortcomings have led these methods to be characterized as measuring *self-consistency* rather than genuine faithfulness (Parcalabescu & Frank, 2024), since they fail to establish direct connections between explanations and the model's reasoning processes. To overcome these limitations, we introduce NEUROFAITH, a flexible framework for directly measuring LLM self-NLE faithfulness. Our main contributions are as follows:

1. We propose NEUROFAITH, a framework to measure LLM self-NLE faithfulness by measuring alignment with its internal reasoning at the concept level.
2. We show the versatility of NEUROFAITH by applying it to both 2-hop reasoning and classification.
3. We propose a fine-grained taxonomy to characterize self-NLEs in 2-hop reasoning based on self-NLE faithfulness, correctness and latent reasoning correctness.
4. We establish that NEUROFAITH provides more relevant faithfulness measures than existing baselines (CI, AA) for evaluating self-NLES in 2-hop reasoning.
5. We develop a linear faithfulness probe based on NEUROFAITH to detect unfaithful LLM self-NLEs from representation space and to improve faithfulness through activation steering.

This paper is organized as follows: Section 2 presents how existing approaches measure the faithfulness of LLM self-NLE. Section 3 introduces the NEUROFAITH framework and Sections 4 and 5 its instantiations for two tasks, 2-hop reasoning and classification. We finally show in Section 6 that self-NLE faithfulness, as measured by NEUROFAITH, can be linearly detected in LLM representation space and improved through steering.

2 Related Work

Numerous approaches have been proposed to measure self-NLE faithfulness (Lyu et al., 2024). One approach (Tutek et al., 2025) assesses the effect of unlearning (Liu et al., 2025) the parametric knowledge encoded in the reasoning steps of the self-NLE. The higher the change in prediction between the original model and the model having unlearned the reasoning steps, the more faithful the self-NLE. We group the remaining approaches in two categories.

Counterfactual Interventions. NLE faithfulness can be assessed through behavioral tests that measure how perturbations in the input text affect both predictions and self-NLE (Atanasova et al., 2023). Counterfactual Intervention (CI) methods employ auxiliary models to generate counterfactual texts designed to change the LLM outcome. The LLM is then prompted to produce a self-NLE to justify its new prediction. The self-NLE is deemed faithful if it aligns with the specific CI that caused the prediction change. These CI approaches mostly differ in two ways: how they measure consistency between the intervention and the resulting self-NLE (Atanasova et al., 2023; Siegel et al., 2024, 2025), and the granularity of the CI intervention (Matton et al., 2025). These approaches face several limitations: (1) the CI may not be solely responsible for the prediction change, as the model might base its new prediction on another input part after intervention, (2) CI methods treat the model as a black box by focusing on input-output relationships without analyzing internal neural processes related to predictions, thus departing from the common definition of explanation faithfulness.

Attribution Agreement. Post-hoc Attribution Agreement (AA) (Parcalabescu & Frank, 2024; Wiegreffe et al., 2021; Yeo et al., 2025) methods compute attribution scores for both the model's predictions and its self-NLE and then measure the correlation between these scores: higher correlation values indicate greater faithfulness in the model's self-NLE. AA approaches vary in the employed

post-hoc attribution method (gradient-based (Sundararajan et al., 2017), SHAP (Lundberg & Lee, 2017) or activation patching (Meng et al., 2022)). While AA methods assess whether the same LLM computational blocks are used during both prediction and self-NLE generation, they overlook the semantic content of neural representations, leaving the model's reasoning process only partially treated.

In the following, we propose a method that directly examines the correspondence between self-NLE and the model's actual reasoning process by conducting concept-level mechanistic analysis of internal hidden states during the forward pass that generates the prediction.

3 NEUROFAITH: A Framework for Measuring self-NLE Faithfulness

This section introduces the core principles of NEUROFAITH, our proposed flexible framework for measuring the faithfulness of LLM self-NLE.[1] Based on the premise that faithful explanations should accurately reflect the model's internal reasoning process, NEUROFAITH quantifies how well a self-NLE aligns with the latter by extracting concepts from self-NLE and mechanistically evaluating their importance for the model prediction. Sections 4 and 5 provide detailed instantiations of how to apply NEUROFAITH to 2-hop reasoning and classification tasks respectively. Given an L-layer auto-regressive Transformer-based LLM f, a set of input texts $\mathbf{X}$ and a text of interest $x \in \mathbf{X}$, we denote $f(x)$ the model's answer and $e(x)$ the corresponding self-NLE produced by f for input x. NEUROFAITH is a 3-step framework illustrated in Figure 1 and summarized below:

1. **Concept Extraction**. We use an auxiliary LLM to extract from $e(x)$ a set of concepts $\{c_i\}_{i=1}^p$ quoted as important for $f(x)$.
2. **Concept-wise Mechanistic Interpretation**. For each concept c_i, we generate a post-hoc interpretation $\mathtt{I}_\Gamma(c_i)$ based on a relevant subpart of the model called circuit Γ and a mechanistic interpretability method called interpreter $\mathtt{I}$ to assess its impact on $f(x)$.
3. **Faithfulness Measurement**. We compute faithfulness $F(x, e)$ by validating that the detected concepts $\{c_i\}_{i=1}^p$ in $e(x)$ have mechanistic effects on $f(x)$ w.r.t. their interpretations $\{\mathtt{I}_\Gamma(c_i)\}_{i=1}^p$.

3.1 Concept Extraction

Given an input text x, a prediction $f(x)$ and its self-NLE $e(x)$, the first step extracts from $e(x)$ a set of concepts $\{c_i\}_{i=1}^p$ that influence $f(x)$. Recent research has shown that interpretable binary high-level features, referred to as *concepts*, appear to be linearly encoded within LLM representation space (Elhage et al., 2022; Park et al., 2024). This computational understanding aligns with definitions from cognitive science (Ruiz Luyten & van der Schaar, 2024), where concepts are considered as mental entities essential to thought, making them an ideal granularity level for model interpretation. For example in Figure 1, the concept "*Ingmar Bergman*" directly influences the prediction "*Sweden*" because Ingmar Bergman is Swedish. Concepts can be extracted either through human investigation or using an auxiliary LLM under LLM-as-a-Judge settings (Gu et al., 2024). Human annotation enables targeted analysis of specific concepts that are hypothesized to be important for the model's reasoning: it provides high-quality, domain-expert identification of relevant influential concepts but is costly and may not scale to large datasets. LLM-as-a-Judge approaches offer scalability but may miss relevant concepts that human experts would identify. We provide detailed examples of prompts used to extract concepts from self-NLE with an auxiliary LLM in Appendix A.4.1.

3.2 Concept-wise Mechanistic Interpretation

The second step evaluates whether the concepts $\{c_i\}_{i=1}^p$ are actually important for the model's internal processing. We compute an attribution score $\mathtt{I}_\Gamma(c)$ for each concept $c \in \{c_i\}_{i=1}^p$ using an interpretability method (interpreter $\mathtt{I}$) applied to model hidden states within a relevant subpart of the model (circuit Γ). We assume each concept can be detected in the model representation space.

Circuit. Rather than examining every network component, we focus our mechanistic analysis on computational subgraphs that most significantly influence f prediction, called *circuits* (Elhage et al., 2021). Among their multiple definitions (Räuker et al., 2023), we define circuits as sparse oriented subgraphs with an interpretable functional role, where nodes represent computational units and edges

[1] Code is available at `https://github.com/milanbhan/neurofaith`.




Figure 1: NEUROFAITH (1) extracts concepts from the self-NLE (Section 3.1), (2) assesses their mechanistic influence (Section 3.2) to finally (3) measure faithfulness (Section 3.3).

represent computation paths. Formally, a circuit is defined as $\Gamma = \{(k, \ell)\}$, where each pair (k, ℓ) is a coordinate at token index k and layer ℓ that participates in information flow within f at the residual stream level. For example in Figure 1, the circuit is highlighted in blue, starting at token index 12 and layer 1 and finishes at token index 13 and layer L. Circuits can be obtained through task-specific manual investigations (Wang et al., 2023; Biran et al., 2024) or automated via activation patching (Meng et al., 2022) or backward attribution (Conmy et al., 2023; Ferrando & Voita, 2024).

Mechanistic Interpreter. To mechanistically assess the impact of a given concept c on $f(x)$ across circuit Γ, we use an interpreter $\mathtt{I}$ to compute an attribution score $\mathtt{I}_\Gamma(c)$. NEUROFAITH implements two approaches, each suited to different objectives. **Probing** methods determine whether c is represented within f hidden states in Γ. This involves either generating natural language interpretations of hidden states (using `Selfie` (Chen et al., 2024) or `Patchscopes` (Ghandeharioun et al., 2024)) to detect c, or training linear probes (Belinkov, 2022) when c is linearly separable with sufficient labels to train the probe. Denoting h_k^ℓ the hidden state at token k and layer ℓ, we define $\mathtt{I}_\Gamma(c) = \max_{(k,\ell)\in\Gamma} \mathtt{I}(h_k^\ell, c)$, assessing c as important if detected in at least one hidden state from Γ. **Concept importance** methods approximate the causal influence of c on $f(x)$ (Geiger et al., 2025). They use gradient-based methods like `TCAV` (Kim et al., 2018) or Representation Engineering (RepE) (Zou et al., 2023) to directly manipulate concept-related activations across Γ and measure behavioral changes. Section 5 details this procedure in the case of classification.

3.3 Faithfulness Measurement

We consider the self-NLE $e(x)$ as faithful when the extracted concepts $\{c_i\}_{i=1}^p$ are demonstrably important for f's internal processing according to $\mathtt{I}_\Gamma(c)$. We define the faithfulness of $e(x)$ as the proportion of concepts it contains being mechanistically important, i.e. having positive attribution score: $F(x, e) = \frac{1}{p}\sum_{i=1}^{p} \mathbf{1}_{\mathtt{I}_\Gamma(c_i)>0}$. The faithfulness score meaning differs depending on the chosen interpreter $\mathtt{I}$: **Probing-based faithfulness** measures the detection rate of explanation concepts within the model's internal representations along circuit Γ. High probing-based faithfulness indicate that most mentioned concepts are properly decoded from the model's hidden states. **Importance-based faithfulness** estimate causal relevance of explanation concepts for the prediction $f(x)$. High importance-based faithfulness indicate that most mentioned concepts actually influence f reasoning process. This framework directly captures concept-level alignment between the self-NLE $e(x)$ and f internal reasoning process. NEUROFAITH faithfulness scores indicate whether the self-NLE accurately reflects internal processing or mentions concepts that are not mechanistically important. This way, NEUROFAITH directly aligns with the established definition of explanation faithfulness introduced above (Jacovi & Goldberg, 2020), offering a principled evaluation of self-NLE faithfulness.

4 The Case of 2-Hop Reasoning

In the previous section, we defined the high level core principle of NEUROFAITH. We now instantiate NEUROFAITH to 2-hop reasoning using probing-based faithfulness.

4.1 NEUROFAITH Instantiation for 2-Hop Reasoning

Task Description. Multi-hop reasoning is a cognitive task that requires connecting a sequence of objects to reach a conclusion (Mavi et al., 2024). It consists of several single-hop operations (Trivedi et al., 2022), which can individually be defined as triplets (o, r, o') where o is a source object, r is a relation and o' is a target object. For example, the 2-hop reasoning statement "*The country of origin of the movie maker that directed the movie Persona is Sweden*" requires sequentially solving the two single-hop operations: ($o_1 =$ `personna`, $r_1 =$ `movie direction`, $o_2 =$ `ingmar bergman`) and ($o_2 =$ `ingmar bergman`, $r_2 =$ `country`, $o_3 =$ `sweden`). An input text x that requires performing 2-hop reasoning can be expressed as $x = (o_1, r_1, \blacktriangle, r_2, \bullet)$, where $\blacktriangle$ and $\bullet$ are placeholders that have to be associated with a bridge object $(\widehat{o_2})$ and the final object answer $(f(x) = \widehat{o_3})$.

Concept Extraction. Following the notations introduced in Section 3, given an input text $x \in \mathbf{X}$, if $\widehat{o_3} = o_3$, the final answer is correct. Two reasoning chains are derived from $e(x)$: $(o_1, r_1, \widehat{o_2})$ and $(\widehat{o_2}, r_2, \widehat{o_3})$. In this instantiation, we do concept extraction from $e(x)$ by prompting an auxiliary LLM to get the bridge object $(\widehat{o_2})$ based on o_1 and r_1. This way, $\widehat{o_2}$ is our concept c of interest, representing the critical intermediate step that connects the two reasoning operations. The next step consists in computing a post-hoc mechanistic interpretation to assess c impact on the prediction.

Probing-based Concept Interpretation. The presence of a single bridge object in 2-hop reasoning self-NLE makes probing-based interpretations particularly appropriate. For f to correctly answer, it must either internally compute the bridge object during the first hop before executing the second hop or leverage shortcuts to directly answer based on o_1. Therefore, detecting the extracted bridge object $\widehat{o_2} = c$ in f internal representations is a strong indication to assess whether c is important for the prediction. We employ natural language interpretation methods such as `Selfie` and `Patchscopes`, rather than linear probes, as they provide higher accuracy and are unsupervised (Ghandeharioun et al., 2024). Biran et al. (2024) show that the bridge object of 2-hop reasoning is resolved on early layers and can be detected on the last token representation of source object o_1 and the residual stream (`RS`). We leverage this information to define circuit Γ and generate the natural language description $\tilde{h}_k^\ell$ of hidden state h_k^ℓ. For concept (bridge object) c, the probing-based concept attribution is defined as $\mathtt{I}_\Gamma(c) = 1$ iff $\exists (k, \ell) \in \Gamma$ such that $c \in \tilde{h}_k^\ell$.

Detailed Taxonomy. Following the notations of Section 3.3, $e(x)$ is faithful if c is decoded from at least one hidden state within Γ via probe `I` ($\mathtt{I}_\Gamma(c) = 1$), implying $F(x, e) \in \{0, 1\}$ for 2-hop reasoning. Beyond faithfulness, the ground-truth bridge object o_2 enables further characterization: $e(x)$ is correct if $\hat{o}_2 = o_2$, and the model correctly resolves latently the first-hop if $\exists (k, \ell) \in \Gamma$ such that $o_2 \in \tilde{h}_k^\ell$. Combining these dimensions with prediction correctness yields ten disjoint cases, illustrated in Figure 2, using $(o_1, r_1, o_2, r_2, o_3)$ and $(o_1, r_1, \widehat{o_2}, r_2, \widehat{o_3})$ as canonical and predicted reasoning traces.


4.2 2-Hop Reasoning Experimental Analysis

Experimental Setup.

We evaluate NEUROFAITH on the Wikidata 2-hop reasoning datasets (Biran et al., 2024). We test `Gemma-2` (2B, 9B, 27B) (Gemma Team, 2024), and `Mistral-7B-Instruct-v0.3` (Jiang et al., 2023). We use `Qwen3-32B` to extract bridge objects from self-NLEs and `Patchscopes` as interpreter. We report the results based on the detailed taxonomy introduced in the previous section.

Details on circuit Γ and prompts for bridge object extraction and `Patchscopes` execution are in Appendix A.4.1. We validate that `Qwen3-32B` is a reliable concept extractor, achieving 99.5% accuracy when extracting bridge objects from complete 2-hop reasoning chains. To evaluate NEUROFAITH robustness to the choice of bridge extractor, we test `Phi-4` (Abdin et al., 2024) as an alternative, obtaining approximately 90% correlation with `Qwen3-32B` (Table 7), confirming that NEUROFAITH is robust across different extractors.

Appendix A.4.2 provides a sensitivity analysis over circuit size, showing that NEUROFAITH is robust to the amount of decoded internals in the circuit. It also includes additional experiments confirming that `Patchscopes` properly performs probing. In Appendix A.4.3, we propose a NEUROFAITH instantiation for 2-hop reasoning in the explain-then-predict paradigm, which yields results similar to those of the predict-then-explain setting.



Incorrect Predictions ($\widehat{o_3} \neq o_3$)

1. **Complete failure.** *Unfaithful self-NLE with no internal bridge object trace internally or externally.*
2. **Internal-external mismatch.** *The bridge object is present internally but not in the self-NLE, indicating reasoning inconsistency.*
3. **Prediction-explanation association.** *Correct bridge object in unfaithful NLE, indicating association matching.*
4. **First-hop failure.** *Faithful self-NLE indicating a reasoning failure in the first-hop.*
5. **Second-hop failure.** *Faithful self-NLE indicating a reasoning failure in the second hop.*

Correct Predictions ($\widehat{o_3} = o_3$)

6. **Shortcut learning.** *Unfaithful self-NLE with no trace of the bridge object internally or externally, indicating shortcut.*
7. **Deceptiveness/hallucination.** *Bridge object resolved internally but absent from the self-NLE, indicating alignment concern.*
8. **Explainer parrot.** *Correct bridge in NLE but not detectable internally, indicating post hoc rationalization.*
9. **Alternative pathway.** *Faithful self-NLE indicating non-canonical 2-hop reasoning (good answer for wrong reason).*
10. **Reliable oracle.** *Faithful self-NLE indicating canonical 2-hop reasoning.*

Figure 2: Taxonomy of f self-NLEs in 2-hop reasoning. Blue highlights indicate faithful.

Table 1: Accuracy and distribution of 2-hop reasoning taxonomy categories across models (in %). Categories 1–5 correspond to incorrect predictions; categories 6–10 correspond to correct predictions. Blue highlights indicate categories where the model's explanation is faithful to its reasoning.

		Incorrect Predictions					Correct Predictions				
Model	**Task Acc.**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**	**10**
`gemma-2-2b`	7.1	23.8	4.2	14.4	16.0	41.6	27.8	6.1	17.7	8.1	40.3
`gemma-2-9b`	16.6	26.1	4.5	14.5	14.1	40.9	14.9	4.2	20.0	6.8	54.0
`gemma-2-27b`	22.3	22.8	4.4	12.5	17.1	43.1	12.8	3.1	15.3	6.4	62.4
`mistral-3-7b`	21.2	46.5	13.7	7.1	8.4	24.2	20.6	4.0	19.3	5.2	50.9

Key Findings. Table 1 presents the self-NLE characterization based on the fine-grained taxonomy introduced in Figure 2. Overall, faithfulness (categories 4 and 5 for incorrect predictions, and categories 9 and 10 for correct predictions) tends to be higher with increasing model size. For incorrect predictions, the combined rate of faithful self-NLEs increases from 57.6% for Gemma-2B to 60.2% for Gemma-27B. Similarly, for correct predictions, the faithful categories (9 and 10) grow from 48.4% for Gemma-2B to 68.8% for Gemma-27B. This improvement reflects enhanced internal consistency as models scale, where larger models increasingly generate faithful explanations that accurately reflect their internal reasoning pathways. Notably, category 10 (reliable oracle) shows the strongest scaling effect, with Gemma-27B reaching 62.4%, indicating that larger models more reliably produce both correct predictions and genuinely faithful explanations.

Fine-grained taxonomy analysis reveals that category 5 (second-hop reasoning failure) remains stable across Gemma-2 size at 40-43% among incorrect predictions, suggesting that the second hop represents the major systematic source of error in 2-hop reasoning. In contrast, category 7 (deceptiveness or hallucination, where internal bridge objects are resolved but absent from self-NLEs) shows a decreasing trend with model scale, dropping from 6.1% for Gemma-2B to 3.1% for Gemma-27B. Post-hoc rationalization (category 8) is stable across models and size. Mistral shows substantially higher failure rates for incorrect predictions than Gemma-2 at similar size, with category 1 reaching 46.5%, yet yields similar results for correct predictions at comparable task accuracy. At comparable model size, mistral exhibits a greater propensity for shortcut learning (Geirhos et al., 2020) (category 6: 20.6% vs 14.9%) than Gemma and a slightly lower rate of achieving reliable

Table 2: NEUROFAITH relevance comparison to CI and AA faithfulness measures on 2-hop reasoning.

Quality	`gemma-2-2b`			`gemma-2-9b`			`gemma-2-27b`	
Metric	NEUROFAITH	CI	AA	NEUROFAITH	CI	AA	NEUROFAITH	CI
hint1 (↑)	**0.04**	-0.07	-0.23	0.06	-1.10	**0.40**	**0.75**	-0.99
hint2 (↑)	**-0.44**	-0.55	-1.23	**0.28**	-0.03	0.15	-0.35	**1.25**
$r_2 \rightarrow r_2'$ (↑)	0.09	-2.62	**1.32**	**0.17**	-0.32	0.01	**0.31**	-0.26

oracle status (category 10: 50.9% vs 54.0%). Overall, Mistral generates less faithful self-NLEs across both incorrect and correct predictions compared to Gemma at comparable size.

Comparison to Other Faithfulness Measures.

Decoding the bridge object concept from the model internals does not by itself prove that it is causally used. We then propose an evaluation protocol, following Zaman & Srivastava (2025), to evaluate a faithfulness measure by its practical utility for two common uses of explanations: debugging wrong predictions by locating the failing hop and detecting shortcuts in correct predictions (Biecek & Samek, 2024). The hypothesis is that if a faithfulness measure captures the model's actual reasoning, a faithful self-NLEs should be more informative about where the reasoning fails or deviates than unfaithful ones.

We first assign each instance to one of four categories using prediction correctness and bridge-object correctness ($\widehat{o_2} = o_2$): A (wrong prediction, wrong bridge object, a likely first-hop failure), B (wrong prediction, correct bridge object, a likely second-hop failure), C (correct prediction, wrong bridge object, a likely non-canonical pathway) and D (correct prediction, correct bridge object, a likely canonical pathway). We then modify the input in three ways, each expected to affect two categories differently. For wrong predictions, `hint1` prepends the correct first hop (o_1, r_1, o_2) and should help A more than B, while `hint2` prepends the correct second hop (o_2, r_2, o_3) and should help B more than A. For correct predictions, $r_2 \rightarrow r_2'$ replaces the second relation and should hurt C more than D, since a non-canonical pathway is more fragile to the change of a single step than a non-canonical one. For each intervention, we compute the ratio of post-intervention accuracies between the two relevant categories, separately for faithful and unfaithful self-NLEs, and the Compound Accuracy Score (CAS) is the log of the ratio between the two. A positive CAS means that the categories are separated more sharply among faithful self-NLEs, i.e. that faithful self-NLEs better localize the failing hop or the non-canonical pathway.

We compare NEUROFAITH with CI (Parcalabescu & Frank, 2024) and AA (Wiegreffe et al., 2021) on the 352 samples for which a counterfactual is available (AA is omitted for `gemma-2-27b` for computational cost). NEUROFAITH obtains the best CAS in 6 out of 9 settings (Table 2), and on the full 2-hop dataset its CAS is positive for all models except `gemma-2-2b` on $r_2 \rightarrow r_2'$ (Table 17). A detailed version of our faithfulness evaluation protocol, with the formulas, intervention examples and complete results, is provided in Appendix A.7.2.

5 The Case of Classification

This section instantiates NEUROFAITH for classification by employing concept importance methods as mechanistic interpreter `I`. Given an input text $x \in \mathbf{X}$, we denote $f(x) = \hat{y} \in \mathcal{Y}$ with probability score $p_{\hat{y}}(x)$ where $\mathcal{Y}$ is the label space. We assume access to a predefined set of task-relevant concepts $\mathcal{C}$ with concept labels for input texts.

5.1 NEUROFAITH Instantiation for Classification

Concept Extraction. To enable mechanistic interpretation of each concept $c \in \mathcal{C}$, we compute Concept Activation Vectors (CAVs) that represent concepts as directions in f representation space. Following established practices in concept-based interpretability, we employ the mean difference (`diff-mean`) (Rimsky et al., 2024) approach for CAV computation due to its optimal balance between concept detection accuracy and computational efficiency (Wu et al., 2025). For a concept $c \in \mathcal{C}$, a token index k and a layer ℓ, the layer-wise CAV is defined as: $\overrightarrow{c_\ell} = \frac{1}{|\mathbf{X}_c^+|} \sum_{x \in \mathbf{X}_c^+} h_k^\ell -$

Table 3: Classification accuracy and self-NLE faithfulness from NEUROFAITH (%), stratified by prediction correctness: 74% of AGNews self-NLEs related to accurate predictions are faithful.

Model	Task Acc.		Self-NLE Faithfulness			
	AGNews	Ledgar	AGNews		Ledgar	
			Accurate	Inaccurate	Accurate	Inaccurate
`gemma-2-2B`	86.5	40.3	54.6	65.1	58.9	40.5
`gemma-2-9B`	88.7	59.7	96.0	92.3	56.0	58.3
`gemma-2-27B`	88.9	58.1	74.0	72.4	53.0	31.6
`mistral-3-7B`	80.6	82.9	86.6	84.1	94.8	84.4

$\frac{1}{|\mathbf{X}_c^-|}\sum_{x\in\mathbf{X}_c^-} h_k^\ell$, where $\mathbf{X}_c^+$ and $\mathbf{X}_c^-$ respectively represent the sets of texts from $\mathbf{X}$ where the concept c is present or absent. We set the token index to the final position of x, as this location represents f's complete computational state prior to next-token generation. These CAVs enable concept importance computation through RepE techniques. Following Section 3, we use an auxiliary LLM to extract a set of concepts from $e(x)$, making sure that $\{c_i\}_{i=1}^p \subset \mathcal{C}$.

Importance-based Concept Interpretation. For a concept $c \in \{c_i\}_{i=1}^p$, we approximate its causal influence on $f(x)$ through RepE and concept erasure (Belrose et al., 2023). We perform controlled interventions by erasing c from hidden states during forward propagation: $h_k^\ell \leftarrow h_k^\ell - \lambda \times \overrightarrow{c\ell}$, where $\lambda \in [0,1]$ represents intervention intensity and $\lambda = 1$ represents maximum intervention intensity to avoid f collapse (Rimsky et al., 2024). This approach provides strong causal evidence for concept importance without requiring computationally costly gradient computations such as `TCAV`. We define Γ with token index as the final position (likewise CAVs), and layers are selected based on concept detectability (F1 score $> 60\%$ using layer-wise linear probes with `diff-mean`). Applying this intervention across circuit Γ, we measure the resulting probability score: $p_{\tilde{y}}(x, \{\text{do}(H_k^\ell = h_k^\ell - \lambda \times \overrightarrow{c\ell})\}_{(k,\ell)\in\Gamma})$, where the $\text{do}(X = x)$ operator (Pearl, 2009) represents an intervention that sets variable X to value x. We model this relationship as linear: $p_{\tilde{y}}(\cdot) = \beta_0 + \beta_1 \times \lambda$, where the concept importance score is $\mathtt{I}_\Gamma(c) = \beta_1$ (i.e. the marginal effect of intervention on probability score). $\mathtt{I}_\Gamma(c)$ is set to 0 when its significance t-test shows $p > 0.01$. This process is repeated for each extracted concept from $e(x)$ to derive faithfulness scores as described in Section 3.3, with $F(x, e) \in [0, 1]$ for classification. Details and examples are provided in Appendices A.4.2 and A.8.

5.2 Classification Experimental Analysis

Experimental Setup. We evaluate NEUROFAITH's classification instantiation on two datasets with varying complexity: AGNews (Gulli, 2005), a newspaper article classification and Ledgar (Tuggener et al., 2020), a more challenging critical domain legal document classification dataset. We also apply NEUROFAITH to BBQ (Parrish et al., 2022) in Appendix A.6. Analyzed models are `Gemma-2` (2B, 9B, 27B) and `Mistral-7B-Instruct-v0.3`. We use the concept set $\mathcal{C}$ and labels of AGNews and Ledgar from Bhan et al. (2025) to compute the CAVs. We use `Qwen3-32B` to extract concepts from the self-NLE, ensuring extracted concepts belong to $\mathcal{C}$ for each dataset. We focus on instances solely containing concepts that are linearly detectable in at least one layer. We evaluate **Self-NLE Faithfulness** according to the prediction status (accurate vs. inaccurate).

Key Findings. Table 3 shows experimental results: Higher average self-NLE faithfulness is observed with `Gemma` on AGNews and `Mistral` on Ledgar, supporting that explanation faithfulness might correlate with task accuracy. Accurate predictions generally yield more faithful explanations, suggesting that correct predictions might rely on relevant concepts. Notably, Gemma-9B and Mistral respectively achieve the highest faithfulness scores on AGNews and Ledgar, going against the idea of a monotonic relationship between model scale and explanation faithfulness. Comparing findings across classification and 2-hop reasoning reveals that accurate predictions tend to produce more faithful explanations, whereas scaling effects vary between tasks and models, as shown in prior work (Parcalabescu & Frank, 2024; Matton et al., 2025). Figures 8 and 10 in Appendix A.5.1 present examples of concepts frequently associated with unfaithful self-NLEs, revealing confusion where the model invokes concepts related to "business" when predicting the "world" class, and vice versa.




Figure 3: Faithfulness linear probe performance per model and dataset.




Figure 4: 2-hop reasoning example with decoded hidden state ($\tilde{h}^8_{11}$) containing the expected o_2. Faithfulness probe is applied to self-NLE before and after steering.

6 Linearly Detecting and Improving Self-NLE Faithfulness

Various safety behaviors intuitively associated with faithfulness, such as hallucination and deceptiveness, are encoded as linear directions in LLM representation spaces (Rimsky et al., 2024; Goldowsky-Dill et al., 2025). We demonstrate that NEUROFAITH faithfulness similarly exhibits linear structure, enabling both accurate detection and improvement through activation steering.

6.1 Linear Detection of Faithfulness

We construct datasets of faithful and unfaithful self-NLE pairs using NEUROFAITH scores. Since classification produces continuous faithfulness scores, we focus on polarized cases ($F(x, e) \in \{0, 1\}$) for clear class separation. Input sequences are constructed as $x_{nle} = [x, f(x), e(x)]$ and hidden states extracted from the final token across all layers. For 2-hop reasoning, we additionally extract states from the last mention of the predicted bridge object token $\hat{o_2}$, as prior work shows that targeting informative tokens might improve linear probe performance (Orgad et al., 2025). We apply `diff-mean` on these activations to yield layer-wise faithfulness probes $\overrightarrow{F_\ell}$, using class-averaged vectors for classification to isolate faithfulness independent of class confounders. A majority vote across layer-wise probes beyond layer 5 determines the final faithfulness label. Figure 3 shows faithfulness is reliably detected across all tasks and models with F1 scores of 61-75%. Probing the last mention of the bridge object token activations in 2-hop reasoning consistently outperforms probing the final token, confirming that faithfulness encoding concentrates at the bridge object (as shown in Figure 4).

In Appendix A.4.3, we apply the same linear detection analysis to 2-hop reasoning in the explain-then-predict paradigm and obtain similar results, with F1 scores between 70 and 77%. We also provide more details about the computation of $\overrightarrow{F_\ell}$ and layer-wise scores are in Appendix A.4.4.

6.2 Faithfulness Enhancement Through Steering on 2-hop reasoning

Having established the linear structure of NEUROFAITH faithfulness representations, we investigate whether linear steering can improve self-NLE faithfulness during inference. We implement activation steering by modifying hidden states during self-NLE inference: $h^\ell_k \leftarrow h^\ell_k + \lambda \times \overrightarrow{SV_\ell}$, where $\overrightarrow{SV_\ell}$ is the steering vector and λ controls intervention intensity. Our objective is here to demonstrate immediate practical value for improving self-NLE faithfulness during inference without model modification and validate the link between faithfulness, hallucination and deceptiveness. More sophisticated steering methods (Hedström et al., 2025; Vogels et al., 2025) would likely yield superior results. We evaluate three approaches: *faithfulness amplification* ($\overrightarrow{SV_\ell} = \overrightarrow{F_\ell}$, $\lambda = 1$) and *hallucination/deceptiveness inhibition* ($\overrightarrow{SV_\ell} = \overrightarrow{H_\ell}$ or $\overrightarrow{D_\ell}$, $\lambda = -1$), where $\overrightarrow{H_\ell}$ and $\overrightarrow{D_\ell}$ are hallucination and deceptiveness linear

Table 4: Share of unfaithful 2-hop self-NLE made faithful through activation steering (%). Share of faithfulness enhancement is broken down by taxonomy category for faithfulness activation steering.

Model	Faithfulness $\lambda = 1$							Hallucination	Deceptiveness
	Overall	Incorrect Predictions			Correct Predictions			$\lambda = -1$	$\lambda = -1$
		1	2	3	6	7	8		
gemma-2-2b	11.1	8.1	**38.0**	5.1	9.3	**39.5**	1.1	10.0	4.2
gemma-2-9b	8.7	6.9	**28.4**	3.7	10.3	**57.8**	2.0	8.5	4.5
gemma-2-27b	11.0	9.3	**19.7**	5.3	10.9	**40.4**	1.3	9.2	3.9

vectors obtained with `diff-mean` linear probes derived from Rimsky et al. (2024) and Goldowsky-Dill et al. (2025) datasets. Faithfulness intervention targets only layers with F1 $> 60\%$, ensuring modifications occur where faithfulness is reliably encoded.

Table 4 shows steering converts 8-11% of unfaithful self-NLEs into faithful explanations. Categories 2 (internal-external mismatch) and 7 (deceptiveness or hallucination) show dramatically higher conversion rates of 19-38% and 39-58% respectively, as both involve cases where the bridge object is internally detected but absent from the self-NLE. Steering realigns the explicit explanation with mechanistically resolved reasoning, prompting the model to articulate what it already computes. In contrast, categories involving fundamental reasoning errors (1, 3, 6) show minimal conversion. Direct faithfulness amplification slightly outperforms hallucination inhibition and substantially outperforms deceptiveness inhibition. Figure 4 illustrates this realignment by converting an unfaithful self-NLE into a faithful one. Additional analyses include detailed faithfulness status changes for hallucination and deceptiveness steering and examples of converted self-NLEs (see Appendix A.5.1 and A.9).

7 Discussion

NEUROFAITH inherits the weaknesses of the tools it relies on: the auxiliary LLM extracting concepts, the circuit definition, Patchscopes, and CAVs, which rest on the linear representation hypothesis. A low faithfulness score can therefore reflect a failure of one of these components rather than a genuinely unfaithful self-NLE. NEUROFAITH has been applied on circuits either previously defined or along the last token, based on probe accuracy. It would be valuable to run NEUROFAITH based on circuit discovery methods. NEUROFAITH verifies a restricted property of self-NLEs, namely the presence and importance of the concepts they mention in the model's computation. NEUROFAITH does not assess richer structures such as logical relations between concepts or the order in which they are used, and applying it to such explanations would require more expressive mechanistic references, for instance causal graphs built from sparse feature circuits as in Marks et al. (2025).

Finally, our faithfulness analysis for classification focuses on *predict-then-explain* scenarios, extending to *explain-then-predict* settings could reveal how explanation faithfulness relates to performance gains (Bhan et al., 2024).

8 Conclusion

This work introduces NEUROFAITH, a framework that assesses the faithfulness of LLM free text self-explanations by measuring their alignment with a concept-level mechanistic analysis of the model's internals. As defined by NEUROFAITH, our results suggest that faithfulness has a linear structure in representation space for both 2-hop reasoning and classification. This structure supports cheap detection of unfaithful explanations and partial improvement through activation steering, mostly in cases where the model already computes a concept internally but fails to state it.

More broadly, we see NEUROFAITH as a step toward self-explanations that can be audited against model internals and then used with more confidence. Richer mechanistic references, such as causal graphs of interpretable features, could extend the framework to explanations that involve relations between concepts. Finally, systematically extending NEUROFAITH to the predict-then-explain paradigm beyond 2-hop reasoning could also provide valuable comparisons with existing CoT faithfulness studies (Turpin et al., 2023).

Acknowledgments and Disclosures

This work was supported by Ekimetrics, in the framework of an industrial PhD agreement with Sorbonne Université (LIP6). Computational experiments were carried out using computer ressources from the LIP6.

The first author is employed by Ekimetrics. The employer had no role in the design of the study, the analysis of the results, or the decision to publish.

References

Abdin, M., Aneja, J., Behl, H., Bubeck, S., Eldan, R., Gunasekar, S., Harrison, M., Hewett, R. J., Javaheripi, M., Kauffmann, P., et al. Phi-4 technical report. *arXiv preprint arXiv:2412.08905*, 2024.

Agarwal, C., Tanneru, S. H., and Lakkaraju, H. Faithfulness vs. plausibility: On the (un) reliability of explanations from large language models. *arXiv preprint arXiv:2402.04614*, 2024.

Atanasova, P., Camburu, O.-M., Lioma, C., Lukasiewicz, T., Simonsen, J. G., and Augenstein, I. Faithfulness Tests for Natural Language Explanations. In Rogers, A., Boyd-Graber, J., and Okazaki, N. (eds.), *Proc. of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 283–294, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-short.25. URL https://aclanthology.org/2023.acl-short.25.

Belinkov, Y. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219, 2022.

Belrose, N., Schneider-Joseph, D., Ravfogel, S., Cotterell, R., Raff, E., and Biderman, S. Leace: Perfect linear concept erasure in closed form. *Advances in Neural Information Processing Systems*, 36:66044–66063, 2023.

Bhan, M., Vittaut, J.-N., Chesneau, N., and Lesot, M.-J. Self-AMPLIFY: Improving small language models with self post hoc explanations. In Al-Onaizan, Y., Bansal, M., and Chen, Y.-N. (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 10974–10991, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.615. URL https://aclanthology.org/2024.emnlp-main.615/.

Bhan, M., Choho, Y., Moreau, P., Vittaut, J.-N., Chesneau, N., and Lesot, M.-J. Towards achieving concept completeness for textual concept bottleneck models. In *Findings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, November 2025.

Biecek, P. and Samek, W. Position: explain to question not to justify. In *Proceedings of the 41st International Conference on Machine Learning*, pp. 3996–4006, 2024.

Biran, E., Gottesman, D., Yang, S., Geva, M., and Globerson, A. Hopping too late: Exploring the limitations of large language models on multi-hop queries. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 14113–14130, 2024.

Chen, H., Vondrick, C., and Mao, C. Selfie: Self-interpretation of large language model embeddings. In *Forty-first International Conference on Machine Learning*, 2024.

Conmy, A., Mavor-Parker, A., Lynch, A., Heimersheim, S., and Garriga-Alonso, A. Towards automated circuit discovery for mechanistic interpretability. *Advances in Neural Information Processing Systems*, 36:16318–16352, 2023.

Elhage, N., Nanda, N., Olsson, C., Henighan, T., Joseph, N., Mann, B., Askell, A., Bai, Y., Chen, A., Conerly, T., DasSarma, N., Drain, D., Ganguli, D., Hatfield-Dodds, Z., Hernandez, D., Jones, A., Kernion, J., Lovitt, L., Ndousse, K., Amodei, D., Brown, T., Clark, J., Kaplan, J., McCandlish, S., and Olah, C. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 2021. https://transformer-circuits.pub/2021/framework/index.html.

Elhage, N., Hume, T., Olsson, C., Schiefer, N., Henighan, T., Kravec, S., Hatfield-Dodds, Z., Lasenby, R., Drain, D., Chen, C., Grosse, R., McCandlish, S., Kaplan, J., Amodei, D., Wattenberg, M., and Olah, C. Toy models of superposition. *Transformer Circuits Thread*, 2022. https://transformer-circuits.pub/2022/toy_model/index.html.

Farah, L., Murris, J. M., Borget, I., Guilloux, A., Martelli, N. M., and Katsahian, S. I. Assessment of performance, interpretability, and explainability in artificial intelligence–based health technologies: What healthcare stakeholders need to know. *Mayo Clinic Proceedings: Digital Health*, 1(2): 120–138, 2023.

Ferrando, J. and Voita, E. Information flow routes: Automatically interpreting language models at scale. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 17432–17445, 2024.

Geiger, A., Ibeling, D., Zur, A., Chaudhary, M., Chauhan, S., Huang, J., Arora, A., Wu, Z., Goodman, N., Potts, C., et al. Causal abstraction: A theoretical foundation for mechanistic interpretability. *Journal of Machine Learning Research*, 26(83):1–64, 2025.

Geirhos, R., Jacobsen, J.-H., Michaelis, C., Zemel, R., Brendel, W., Bethge, M., and Wichmann, F. A. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020.

Gemma Team, G. Gemma: Open models based on gemini research and technology. *arXiv preprint arXiv:2403.08295*, 2024.

Ghandeharioun, A., Caciularu, A., Pearce, A., Dixon, L., and Geva, M. Patchscopes: A unifying framework for inspecting hidden representations of language models. In *Forty-first International Conference on Machine Learning*, 2024.

Goldowsky-Dill, N., Chughtai, B., Heimersheim, S., and Hobbhahn, M. Detecting strategic deception with linear probes. In *Forty-second International Conference on Machine Learning*, 2025.

Grabisch, M., Marichal, J.-L., Mesiar, R., and Pap, E. *Aggregation functions*, volume 127. Cambridge University Press, 2009.

Gu, J., Jiang, X., Shi, Z., Tan, H., Zhai, X., Xu, C., Li, W., Shen, Y., Ma, S., Liu, H., et al. A survey on llm-as-a-judge. *arXiv preprint arXiv:2411.15594*, 2024.

Gulli, A. Ag's corpus of news articles. *Dipartimento di Informatica, University of Pisa, Nov*, 2005.

Han, T., Ektefaie, Y., Farhat, M., Zitnik, M., and Lakkaraju, H. Is ignorance bliss? the role of post hoc explanation faithfulness and alignment in model trust in laypeople and domain experts. *arXiv preprint arXiv:2312.05690*, 2023.

Hedström, A., Amoukou, S. I., Bewley, T., Mishra, S., and Veloso, M. To steer or not to steer? mechanistic error reduction with abstention for language models. In *Forty-second International Conference on Machine Learning*, 2025.

Hernandez, E., Sharma, A. S., Haklay, T., Meng, K., Wattenberg, M., Andreas, J., Belinkov, Y., and Bau, D. Linearity of relation decoding in transformer language models. In *The Twelfth International Conference on Learning Representations*, 2024.

Huang, S., Mamidanna, S., Jangam, S., Zhou, Y., and Gilpin, L. H. Can Large Language Models Explain Themselves? A Study of LLM-Generated Self-Explanations, October 2023. URL `http://arxiv.org/abs/2310.11207`. arXiv:2310.11207 [cs].

Jacovi, A. and Goldberg, Y. Towards faithfully interpretable nlp systems: How should we define and evaluate faithfulness? In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics, 2020.

Jiang, A. Q., Sablayrolles, A., Mensch, A., Bamford, C., Chaplot, D. S., Casas, D. d. l., Bressand, F., Lengyel, G., Lample, G., Saulnier, L., et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023. URL `https://arxiv.org/abs/2310.06825`.

Kayser, M., Menzat, B., Emde, C., Bercean, B., Novak, A., Morgado, A., Papiez, B., Gaube, S., Lukasiewicz, T., and Camburu, O.-M. Fool me once? contrasting textual and visual explanations in a clinical decision-support setting. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 18891–18919, 2024.

Kim, B., Wattenberg, M., Gilmer, J., Cai, C., Wexler, J., Viegas, F., et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International conference on machine learning*, pp. 2668–2677. PMLR, 2018.

Liu, S., Yao, Y., Jia, J., Casper, S., Baracaldo, N., Hase, P., Yao, Y., Liu, C. Y., Xu, X., Li, H., et al. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, pp. 1–14, 2025.

Lundberg, S. M. and Lee, S.-I. A Unified Approach to Interpreting Model Predictions. In *Advances in Neural Information Processing Systems*. NeurIPS, 2017.

Luo, C. F., Bhambhoria, R., Dahan, S., and Zhu, X. Evaluating explanation correctness in legal decision making. In *Canadian AI*, 2022.

Lyu, Q., Apidianaki, M., and Callison-Burch, C. Towards faithful model explanation in nlp: A survey. *Computational Linguistics*, pp. 1–67, 2024.

Madsen, A., Chandar, S., and Reddy, S. Are self-explanations from large language models faithful. In *Findings of the Association for Computational Linguistics: ACL 2024*, 2024.

Marks, S., Rager, C., Michaud, E. J., Belinkov, Y., Bau, D., and Mueller, A. Sparse feature circuits: Discovering and editing interpretable causal graphs in language models. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=I4e82CIDxv.

Matton, K., Ness, R., and Kiciman, E. Walk the talk? measuring the faithfulness of large language model explanations. In *The Fourteenth International Conference on Learning Representations*, 2025.

Mavi, V., Jangra, A., and Jatowt, A. Multi-hop question answering. *Foundations and Trends® in Information Retrieval*, 17(5):457–586, 2024.

Meng, K., Bau, D., Andonian, A., and Belinkov, Y. Locating and editing factual associations in gpt. *Advances in neural information processing systems*, 35:17359–17372, 2022.

Orgad, H., Toker, M., Gekhman, Z., Reichart, R., Szpektor, I., Kotek, H., and Belinkov, Y. LLMs know more than they show: On the intrinsic representation of LLM hallucinations. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=KRnsX5Em3W.

Parcalabescu, L. and Frank, A. On measuring faithfulness or self-consistency of natural language explanations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 6048–6089, 2024.

Park, K., Choe, Y. J., and Veitch, V. The linear representation hypothesis and the geometry of large language models. In *Forty-first International Conference on Machine Learning*, 2024.

Parrish, A., Chen, A., Nangia, N., Padmakumar, V., Phang, J., Thompson, J., Htut, P. M., and Bowman, S. BBQ: A hand-built bias benchmark for question answering. In *Findings of the Association for Computational Linguistics: ACL 2022*, pp. 2086–2105. Association for Computational Linguistics, 2022.

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 2019. URL https://dl.acm.org/doi/10.5555/3454287.3455008.

Pearl, J. *Causality*. Cambridge university press, 2009.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., et al. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12:2825–2830, 2011. URL https://www.jmlr.org/papers/v12/pedregosa11a.html.

Räuker, T., Ho, A., Casper, S., and Hadfield-Menell, D. Toward transparent ai: A survey on interpreting the inner structures of deep neural networks. In *2023 ieee conference on secure and trustworthy machine learning (satml)*, pp. 464–483. IEEE, 2023.

Ribeiro, M. T., Singh, S., and Guestrin, C. " Why should I trust you?" Explaining the predictions of any classifier. In *Proc. of the 22nd ACM SIGKDD Int. Conference on Knowledge Discovery and Data Mining*, 2016.

Rimsky, N., Gabrieli, N., Schulz, J., Tong, M., Hubinger, E., and Turner, A. Steering llama 2 via contrastive activation addition. In Ku, L.-W., Martins, A., and Srikumar, V. (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15504–15522, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.828. URL https://aclanthology.org/2024.acl-long.828/.

Ruiz Luyten, M. and van der Schaar, M. A theoretical design of concept sets: improving the predictability of concept bottleneck models. *Advances in Neural Information Processing Systems*, 37:100160–100195, 2024.

Sahoo, P., Meharia, P., Ghosh, A., Saha, S., Jain, V., and Chadha, A. A comprehensive survey of hallucination in large language, image, video and audio foundation models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 11709–11724, 2024.

Siegel, N., Camburu, O.-M., Heess, N., and Perez-Ortiz, M. The probabilities also matter: A more faithful metric for faithfulness of free-text explanations in large language models. In Ku, L.-W., Martins, A., and Srikumar, V. (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 530–546, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-short.49. URL https://aclanthology.org/2024.acl-short.49/.

Siegel, N. Y., Heess, N., Perez-Ortiz, M., and Camburu, O.-M. Faithfulness of llm self-explanations for commonsense tasks: Larger is better, and instruction-tuning allows trade-offs but not pareto dominance. *arXiv preprint arXiv:2503.13445*, 2025.

Sundararajan, M., Taly, A., and Yan, Q. Axiomatic attribution for deep networks. In *Proc. of the 34th Int. Conf. on Machine Learning, ICML*, volume 70 of *ICML'17*, pp. 3319–3328. JMLR.org, August 2017. URL https://proceedings.mlr.press/v70/sundararajan17a/sundararajan17a.pdf.

Trivedi, H., Balasubramanian, N., Khot, T., and Sabharwal, A. MuSiQue: Multihop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554, 2022. doi: 10.1162/tacl_a_00475. URL https://aclanthology.org/2022.tacl-1.31/.

Tuggener, D., Von Däniken, P., Peetz, T., and Cieliebak, M. Ledgar: a large-scale multi-label corpus for text classification of legal provisions in contracts. In *Proceedings of the twelfth language resources and evaluation conference*, pp. 1235–1241, 2020.

Turpin, M., Michael, J., Perez, E., and Bowman, S. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. *Advances in Neural Information Processing Systems*, 36:74952–74965, 2023.

Tutek, M., Chaleshtori, F. H., Marasović, A., and Belinkov, Y. Measuring chain of thought faithfulness by unlearning reasoning steps. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 9946–9971, 2025.

Vogels, A., Wong, B., Choho, Y., Blangero, A., and Bhan, M. In-distribution steering: Balancing control and coherence in language model generation. *arXiv preprint arXiv:2510.13285*, 2025.

Wang, K. R., Variengien, A., Conmy, A., Shlegeris, B., and Steinhardt, J. Interpretability in the wild: a circuit for indirect object identification in gpt-2 small. In *The Eleventh International Conference on Learning Representations*, 2023.

Wiegreffe, S. and Marasovic, A. Teach me to explain: A review of datasets for explainable natural language processing. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*, 2021.

Wiegreffe, S., Marasović, A., and Smith, N. A. Measuring association between labels and free-text rationales. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 10266–10284, 2021.

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., et al. Transformers: State-of-the-art natural language processing. In *Proc. of the Conf. on Empirical Methods in Natural language Processing: system demonstrations, EMNLP*, pp. 38–45, 2020. URL https://aclanthology.org/2020.emnlp-demos.6/.

Wu, Z., Arora, A., Geiger, A., Wang, Z., Huang, J., Jurafsky, D., Manning, C. D., and Potts, C. Axbench: Steering llms? even simple baselines outperform sparse autoencoders. In *Forty-second International Conference on Machine Learning*, 2025.

Yang, S., Kassner, N., Gribovskaya, E., Riedel, S., and Geva, M. Do large language models perform latent multi-hop reasoning without exploiting shortcuts? In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 3971–3992, 2025.

Yeo, W. J., Satapathy, R., and Cambria, E. Towards faithful natural language explanations: A study using activation patching in large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 10436–10458, 2025.

Zaman, K. and Srivastava, S. A causal lens for evaluating faithfulness metrics. In Christodoulopoulos, C., Chakraborty, T., Rose, C., and Peng, V. (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 29425–29449, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.1496. URL https://aclanthology.org/2025.emnlp-main.1496/.

Zou, A., Phan, L., Chen, S., Campbell, J., Guo, P., Ren, R., Pan, A., Yin, X., Mazeika, M., Dombrowski, A.-K., et al. Representation engineering: A top-down approach to ai transparency. *arXiv preprint arXiv:2310.01405*, 2023.

A Appendix

Impact Statements

This work aims to advance the trustworthiness of AI systems by developing methods to evaluate whether LLM self-explanations actually reflect their internal reasoning processes. Faithful self-explanations are critical for deploying LLMs in high-stakes domains such as healthcare or legal decision-making, where users must understand why a model reached a specific outcome. NEUROFAITH provides a principled tool for auditing explanation quality, potentially reducing over-reliance on plausible but misleading justifications. However any potential NEUROFAITH user must consider faithfulness score with caution, avoiding over-reliance on a single metric to take high-stake decisions. We especially higlight the importance of human validation during critical NEUROFAITH steps such as concept extraction.

A.1 Scientific Libraries

We used several open-source libraries in this work: pytorch (Paszke et al., 2019), HuggingFace transformers (Wolf et al., 2020) and sklearn Pedregosa et al. (2011).

A.2 LLM Implementation Details

Backbone and Special Tokens. The library used to import the pretrained autoregressive language models is Hugging-Face. In particular, the backbones version of Gemma-2-2B, Gemma-2-9B and Gemma-2-27B are `gemma-2-2B-it`, `gemma-2-9B-it`, `gemma-2-27B-it` respectively. The models were imported with the `Bfloat16` computational format. The following special tokens used were used for instruction prompting:

- `user_token= '<start_of_turn>user'`
- `assistant_token= '<start_of_turn>model'`
- `stop_token= '<eos>'`

Text Generation. Text generation was performed using the native functions of the Hugging Face library: `generate`. The `generate` function was used with the following parameters:

- `do_sample = True`
- `num_beams = 2`
- `no_repeat_ngram_size = 2`
- `repetition_penalty =1.2`
- `early_stopping = True`
- `temperature = 0.05`

Self-NLE Generation. The prompt used to get self-NLE was as follows:

- <**user**>
- *Question*
- <**Assistant**>
- *Answer*
- <**user**>
- *"Give me a simple explanation of your answer."*
- <**Assistant**>

A.3 Datasets

Here we provide detailed information about the analyzed datasets. For 2-hop reasoning, we run NEUROFAITH on the Wikidata-2-hop dataset (Biran et al., 2024) and Socrates (Yang et al., 2025). We first compute task accuracy on the whole dataset, and then sample 1500 accurate and inaccurate prediction for Wikidata-2-hop. To sample these 1500 instances, we filter out 2-hop reasoning questions where relations are subjective (e.g. "*the most notable work of*") or equivocal, potentially leading to numerous possible answers (e.g. "*the work that features*"). We also sample by setting a maximum number of occurrences for generated answers (15), to foster diversity in the input questions. This filter enables to avoid having too many questions where the answer is a country (e.g. USA). We end up with a dataset made of 3000 samples with 1500 accurate and 1500 inaccurate predictions.

For classification, we run NEUROFAITH on AGNews (Gulli, 2005), a newspaper article classification and Ledgar (Tuggener et al., 2020), a more challenging critical domain legal document classification dataset. We retrieve the enriched versions from Bhan et al. (2025) with labeled concepts for CAV computation. For AGNews, the classes to predict are 'world', "sport", "business" and "science & technology". For Ledgar, the classes to predict are "Amendments", "Survival", "Terminations" and "Terms". Each dataset is made of 4000 samples.

A.4 NEUROFAITH Implementation Details

A.4.1 Concept Extraction

Here we provide the prompts used to give instructions to `Qwen-3-32b` to extract relevant concepts (NEUROFAITH step 1). For 2-hop reasoning, concept extraction consists in retrieving the bridge

object from the self-NLE. Since the input text as the following structures : $x = (o_1, r_1, \blacktriangle, r_2, \bullet)$, we directly prompt the model to resolve $(o_1, r_1, \blacktriangle)$ by grounding its response on the self-NLE only. We structure our prompt following an in-context learning template with two examples differing from the dataset of interest:

Concept Extraction Prompt for 2-hop Reasoning

user
`preprompt + preprompt_example_1`
assistant
Emmanuel Macron
user
`preprompt + preprompt_example_2`
assistant
Ingmar Bergman
user
`preprompt +` $(o_1, r_1, \blacktriangle)$

with `preprompt` = "*Answer briefly and only according to the provided text. If there is no clear answer, say **no bridge object***", `preprompt_example_1` = "*Emmanuel Macron is the president of Italy, and the capital city of Italy is Rome.** the president of Italy is*" and `preprompt_example_2` = "*The movie Persona is a movie happening in the Faro island and has been directed by Ingmar Bergman, who is from Sweden.**: *'The director of Persona is*".

For classification, we assess having access to a set of relevant concepts $\mathcal{C}$ and labels related to the task of interest. Given a certain concept c, we only prompt the model to assess if the concept is present in the self-NLE if the concept was initially present in the input text, making the concept extraction process computationally less expensive. We structure our prompt following an in-context learning template with three examples differing from the dataset of interest:

Concept Extraction Prompt for Classification

user
`preprompt + preprompt_example_1`
assistant
yes
user
`preprompt + preprompt_example_2`
assistant
yes
user
`preprompt + preprompt_example_3`
assistant
no
user
`preprompt + context_extraction_prompt(`$\hat{y}, e(x), c$`)`

with `preprompt` = "*Analyze whether a given concept has a meaningful impact on predicting a specific category from the provided text explanation. Instructions: (1) Answer with exactly "YES" if the concept is clearly mentioned in the given text and relevant to the category prediction, (2) Answer with exactly "NO" if the concept is neither mentioned nor relevant in the given text (3) Consider the logical connection between the concept and the category in the given text*".

For AGNews:

- `preprompt_example_1` = "*Text explanation: 'The article says that OECD countries became richer in the 20th century. This falls under the category of world'. Question: According to the previous text, does the concept "economic trends" have a meaningful impact on predicting the "world" category?*"

- `preprompt_example_2` = "*Text explanation: 'The abstract underlines that the French soccer striker is a good player. It is relevant to sport'. Question: According to the previous text, does the concept "jargon specific to the sport" have a meaningful impact on predicting the "sport" category?*".

- `preprompt_example_3` = "*Text explanation: 'The research paper discusses quantum computing algorithms and their complexity. This falls under the category of technology'. Question: According to the previous text, does the concept "cooking techniques" have a meaningful impact on predicting the "technology" category?*".

For Ledgar:

- `preprompt_example_1` = "*Text explanation: 'This clause defines what happens to your stock options if your employment ends *before* they are fully vested. It's part of the core **terms** of your employment agreement that outlines how these shares work.' Question: According to the previous text, does the legal concept "Minimum commitment periods" have a meaningful impact on predicting the "terms" category?*"

- `preprompt_example_2` = "*Text explanation: 'This clause defines what happens to your stock options if your employment ends *before* they are fully vested. It's part of the core **terms** of your employment agreement that outlines how these shares work.' Question: According to the previous text, does the legal concept "Effect of termination" have a meaningful impact on predicting the "terms" category?*".

- `preprompt_example_3` = "*Text explanation: 'The clause specifically talks about how changes can be made to the agreement:"terminated, amended, modified or supplemented". These are all words that mean changing the original terms of the contract. Since it focuses on how the contract itself can be altered, the relevant category is **Amendments**' Question: According to the previous text, does the legal concept "Amendment procedures" have a meaningful impact on predicting the "Amendments" category?*".

Finally, given a prediction $\hat{y}$, and self NLE $e(x)$ and a concept c, `context_extraction_prompt`$(\hat{y}, e(x), c)$ = "*Text explanation: $e(x)$. Question: According to the previous text, does the concept c have a meaningful impact on predicting the $\hat{y}$ category?*".

A.4.2 Mechanistic Interpretation

Here we provide implementation details and additional analyses about mechanistic interpretations of extracted concepts (NEUROFAITH step 2).

Interpreter. For the 2-hop reasoning instantiation, the interpreter used to decode f hidden states $\left\{h_k^\ell\right\}$ is `Patchscopes` Ghandeharioun et al. (2024). We use the prompt *"What is the following? Answer briefly [X,X]"* to generate the interpretation where X is a token placeholder to be replaced in the latent space by the hidden state to be interpreted. We replace the placeholder tokens at layers 3 and 4 to get two interpretations per hidden state to decode. The layers to be interpreted by `Patchscopes` vary depending on the assessed model. We set the index token k as the last one related to o_1 and focus on the late early layers as in Biran et al. (2024). This way, $\ell \in \{5, 6, 7, 8, 9, 10, 11\}$ for `gemma-2-2B`, $\ell \in \{8, 9, 10, 11, 12, 13, 14\}$ for `gemma-2-9B` and $\ell \in \{11, 12, 13, 14, 15, 16, 17\}$ for `gemma-2-27B`.

For the classification instantiation and given a concept c, concept importance $\mathtt{I}_\Gamma(c)$ is based on the linear representation of the concept called CAV and denoted $\overrightarrow{c}$. Concepts are selected based on the identifiability of each concept on f representation space based on $\mathtt{I}_\Gamma(c)$. Below are examples of selected concepts from Ledgar and AGNews for `gemma-2-27b` with F1 score $> 60\%$:

Concept	Layer	F1 Score (%)
Players	36	0.758
Political developments	43	0.842
Scores	10	0.626
Financial markets	35	0.758
Companies	36	0.805
Industry-specific terminology and jargon	34	0.745
Global issues	45	0.812
Sports events	45	0.854
Industry analysis	38	0.610
Economic trends	36	0.798
Industries	36	0.776
International events	36	0.847
Global politics	36	0.809
International relations	36	0.776
Foreign affairs	43	0.795
News about wars, conflicts	43	0.694
Athletic competitions	45	0.855
Teams	45	0.679
Game summaries	34	0.780
Jargon specific to the sport	45	0.854
Charts, graphs, and financial data	38	0.658
Advancements in computing	41	0.607
Technological trends	43	0.769

Table 5: AGNews concept max. F1 scores ($> 60\%$) with related layer for `gemma-2-27b`.

Concept	Layer	F1 Score (%)
Modification rights	34	0.838
Amendment procedures	39	0.803
Notice requirements	20	0.743
Approval mechanisms	28	0.816
Integration with original agreement	23	0.729
Format requirements	26	0.768
Severability of amendments	37	0.812
Retroactive application	27	0.638
Waiver limitations	30	0.793
Amendment thresholds	42	0.753
Amendment restrictions	36	0.730
Prior versions validity	45	0.759
Amendment documentation	24	0.759
Version control mechanisms	37	0.738
Material change provisions	33	0.754
Post-termination obligations	28	0.798
Duration of surviving terms	28	0.885
Identification of specific clauses	11	0.785
Indemnification continuation	40	0.862
Payment obligations survival	21	0.776
Representations/warranties survival	21	0.767
Remedies availability post-termination	42	0.845
Perpetual rights	40	0.815
Legal compliance requirements	34	0.721
Duration specifications	42	0.885
Commencement date	36	0.638
Expiration conditions	37	0.910
Renewal mechanisms	44	0.654
Term length	26	0.798
Condition precedents	28	0.798
Milestone-based periods	36	0.739
Initial term vs. renewal term distinctions	44	0.789
Evergreen provisions	13	0.768
Term modification triggers	28	0.728
Minimum commitment periods	34	0.777
Maximum term limitations	36	0.785
Regulatory term constraints	41	0.769
Term acceleration provisions	30	0.738
Rolling term provisions	29	0.823
Termination rights	28	0.888
Notice periods	45	0.726
Termination for convenience	44	0.677
Effect of termination	28	0.912
Wind-down procedures	28	0.865
Mutual termination provisions	27	0.854
Partial termination rights	37	0.833
Change of control provisions	29	0.729
Performance-based termination	44	0.719
Regulatory/legal change termination	15	0.776
Termination certification requirements	27	0.774
Post-termination restrictions	13	0.747
Transition obligations	28	0.856

Table 6: Ledgar concept max. F1 scores ($> 60\%$) with related layer for `gemma-2-27b`.

The concept importance $\mathtt{I}_\Gamma(c)$ can be either computed through representation engineering and concept erasure or gradient-based approaches such as TCAV. We perform concept erasure for $\lambda \in [0, 1]$ with a

step size of 0.1. Table 5 and 6 show the F1 scores of the properly detected concepts in `gemma-2-27b` representation space. We estimate the attribution of c given circuit Γ as the β_1 parameter of the following regression: $p_{\hat{y}}(x, \{\text{do}(H_k^\ell = h_k^\ell - \lambda \times \overrightarrow{c_\ell})\}_{(k,\ell)\in\Gamma}) = \beta_0 + \beta_1 \times \lambda$. The t-test for β_1 significancy is expressed as follows: $t = \frac{\hat{\beta}_1}{SE(\hat{\beta}_1)} = \frac{\hat{\beta}_1}{\sqrt{\frac{MSE}{\sum_{i=1}^n (\lambda_i - \bar{\lambda})^2}}}$, where λ_i is the i realization of λ and $\bar{\lambda}$ is the average λ on the analyzed sample.

The concept importance $\texttt{I}_\Gamma(c)$ can also be computed with gradients-based approaches such as `TCAV`. It can be formally expressed based on the previously computed CAV $\overrightarrow{c}$. $\texttt{I}_\Gamma(c)$ is calculated by aggregating the local importance measures related to the hidden states along circuit Γ:

$$\texttt{I}_\Gamma(c) = \bigodot_{(k,\ell)\in\Gamma} \langle \overrightarrow{c}, \nabla f_{\hat{y},k}^\ell(h_k^\ell) \rangle \tag{1}$$

where $f_{\hat{y},k}^\ell$ is the sub-function from f taking h_k^ℓ as input and generating the output $p_{\hat{y}}$ and $\bigodot$ an aggregation operator chosen according to the expected desired level of strictness to measure faithfulness. Among the many aggregation operators (see e.g. Grabisch et al. (2009)), $\bigodot$ can be conjunctive (e.g. defined as the $\min$ function), disjunctive (e.g. the $\max$ function) or the `average` measure.

Faithfulness is finally calculated based on concept importance as follows: $F(x, e) = \frac{1}{p} \sum_{i=1}^p \mathbf{1}_{\texttt{I}_\Gamma(c_i)>0}$. Figures 5 and 6 show the faithfulness distributions of NEUROFAITH for AGNews and Ledgar for `gemma-2-27b`.




Figure 5: NEUROFAITH faithfulness distribution for AGNews for `gemma-2-27b`.




Figure 6: NEUROFAITH faithfulness distribution for Ledgar for `gemma-2-27b`.

In Figure 7-12 we plot the concepts sorted by frequency for faithful and unfaithful self-NLE for AGNews and Ledgar for `gemma-2-2b` and `gemma-2-9b` for several class predictions. These figures reveal which concepts are associated with faithful versus unfaithful self-NLEs. For instance, Figure 10 shows that NEUROFAITH correctly identifies counterintuitive associations (e.g., the concept "companies" linked to the class "world") as unfaithful, demonstrating its reliability.




Figure 7: Concepts related to faithful self-NLE and the prediction "business", sorted by frequency for AGNews for `gemma-2-2b`.




Figure 8: Concepts related to unfaithful self-NLE and the prediction "business", sorted by frequency for AGNews for `gemma-2-2b`.




Figure 9: Concepts related to faithful self-NLE and the prediction "world", sorted by frequency for AGNews for `gemma-2-2b`.




Figure 10: Concepts related to unfaithful self-NLE and the prediction "world", sorted by frequency for AGNews for `gemma-2-2b`.

Model	Self-NLE Correctness		Latent Hop 1 Correctness		Self-NLE Faithfulness		Faithfulness Corr w/ Qwen
	Accurate	Inaccurate	Accurate	Inaccurate	Accurate	Inaccurate	
`gemma-2-2b`	57.8%	56.5%	47.5%	48.3%	48.0%	56.5%	86.5%
`gemma-2-9b`	73.7%	55.1%	58.5%	44.3%	61.7%	54.8%	91.2%
`gemma-2-27b`	77.8%	55.7%	64.9%	46.9%	69.1%	59.8%	90.9%

Table 7: Self-NLE correctness, first hop latent reasoning correctness, and self-NLE faithfulness across models evaluated using Phi-4 as judge. "(In)accurate" represents the set of predictions initially (in)correct. "Faithfulness Corr w/ Qwen" shows the correlation between faithfulness scores obtained with `Phi-4` and `Qwen-3-32B`.




Figure 11: Concepts related to faithful self-NLE and the prediction "amendments", sorted by frequency for Ledgar for `gemma-2-9b`.




Figure 12: Concepts related to unfaithful self-NLE and the prediction "amendments", sorted by frequency for Ledgar for `gemma-2-9b`.

We also plot the density of faithfulness for AGNews and Ledgar for `gemma-2-27b` in Figure 5 and 6.

2-hop Reasoning Sensitivity Analysis. We show in Table 7 the results obtained by applying NEUROFAITH in the case of 2-hop reasoning with `Phi-4` as bridge object extractor. The results are highly similar to the ones obtained by using `Qwen-3-32B` as bridge object extractor (see column "*Faithfulness Corr w/ qwen*").

Model	Task Acc.	Self-NLE Correctness		Latent Hop 1 Correctness		Self-NLE Faithfulness	
		Accurate	Inaccurate	Accurate	Inaccurate	Accurate	Inaccurate
gemma-2-27B	3.4%	72.8%	62.1%	36.4%	8.1%	27.3%	7.6%

Table 8: Self-NLE correctness, first hop latent reasoning correctness, and self-NLE faithfulness for gemma-2-27B on the Socrates dataset.




Figure 13: NEUROFAITH faithfulness sensitivity analysis with regards to circuit size, gemma-2-2B.




Figure 14: NEUROFAITH faithfulness sensitivity analysis with regards to circuit size, gemma-2-9B.




Figure 15: NEUROFAITH faithfulness sensitivity analysis with regards to circuit size, gemma-2-27B.

Table 9: Explain-then-predict (CoT) setting on 2-hop reasoning: share of faithful reasoning traces (%) according to NEUROFAITH, split by prediction correctness. A trace is faithful when the bridge object verbalised in the chain-of-thought is decoded from the hidden states along circuit Γ.

Model	Incorrect predictions	Correct predictions
`gemma-2-2b`	44.4	62.8
`gemma-2-9b`	44.0	72.0
`gemma-2-27b`	48.6	77.5

Interpreter Sanity Checks. Here we provide additional analyses highlighting that both `Patchscopes` and CAVs are reliable as interpreter.

First, we validate `Patchscopes` relevancy for 2-hop using the the protocol from Ghandeharioun et al. (2024): we extracted several 1-hop reasoning chains from our 2-hop dataset and used `Patchscopes` to decode the expected object from the latent activations. We selected these chains so that every assessed object is shared with the bridge objects from the paper's main experiment. Patchscopes decodes the expected object from the latent activations with 99.8%, 96.9% and 97.1% accuracy for `Gemma-2-2b`, 9b and 27b respectively. These results support `Patchscopes` reliability as a probe to `NeuroFaith` to 2-hop reasoning.

Second, we assess the causal validity of the CAVs for NEUROFAITH application to classification. We retrieve all the CAVs used in the AGNews classification experiment and generate open-ended text via activation steering (steering factor 1, layers 10–20), concept per concept. We then used Qwen3-32B as a judge to measure the proportion of generated texts containing the steered concept, averaged over 5 runs (temperature 1) and 3 preprompts (e.g., "generate a short news article:"). Aggregated across all concepts, 70% of the steered generations contain the target concept, versus 2% for the unsteered baseline. These results confirm, at scale, the causal validity of the manipulated CAVs to compute faithfulness for classification.

A.4.3 Explain-then-predict `NeuroFaith` Instantiation for 2-hop Reasoning

In this section we propose a protocol to apply NEUROFAITH in 2-hop reasoning under the explain-then-predict paradigm to assess reasoning traces faithfulness. We prompt the model to verbalise both hops as a reasoning trace before answering, and decode the bridge object with a linear probe at the last token of the source object. A trace is counted as faithful when the internally decoded bridge object matches the verbalised one in the chain-of-thought. Table 9 reports the proportion of faithful traces, split by whether the final prediction is correct or incorrect. These results mirror our predict-then-explain findings: faithfulness is substantially higher for correct predictions than for incorrect ones (e.g., 77.5% vs. 48.6% for Gemma-2-27b), and the gap widens with scale.

We further test whether NEUROFAITH faithfulness under the explain-then-predict paradigm is also linearly decodable from the model's representations following the protocol applied in Section 6. We append $[x, cot, \hat{y}]$ and train a linear probe on the resulting embeddings, obtaining F1 scores between 70 and 77%, suggesting a linear structure encoding reasoning trace faithfulness in the embedding space.

A.4.4 Linear Latent Faithfulness Detection.

Here we provide additional information about layer-wise linear probe performance and similarity between faithfulness vectors and with other AI safety linear vectors. Figures 16-24 show the layer-wise performance of the faithfulness linear probes for 2-hop reasoning, AGNews and Ledgar. As shown in Figure 25, 26 and 27, cosine similarity between task-specific linear faithfulness and AI safety behaviors vectors becomes more pronounced with the size of the model.




Figure 16: Linear faithfulness probe classification performance for 2-hop reasoning, `gemma-2-2B`.




Figure 17: Linear faithfulness probe classification performance for 2-hop reasoning, `gemma-2-9B`.




Figure 18: Linear faithfulness probe classification performance for 2-hop reasoning, `gemma-2-27B`.




Figure 19: Linear faithfulness probe classification performance for AGNews classification, `gemma-2-2B`.




Figure 20: Linear faithfulness probe classification performance for AGNews classification, `gemma-2-9B`.




Figure 21: Linear faithfulness probe classification performance for AGNews classification, `gemma-2-27B`.




Figure 22: Linear faithfulness probe classification performance for Ledgar classification, `gemma-2-2B`.




Figure 23: Linear faithfulness probe classification performance for Ledgar classification, `gemma-2-9B`.






Figure 24: Linear faithfulness probe classification performance for Ledgar classification, `gemma-2-27B`.




(a) Mean operator (b) Max operator

Figure 25: Linear vectors cosine similarity analysis on `gemma-2-2b`



(a) Mean operator (b) Max operator

Figure 26: Linear vectors cosine similarity analysis on `gemma-2-9b`



(a) Mean operator (b) Max operator

Figure 27: Linear vectors cosine similarity analysis on `gemma-2-27b`

Table 10 shows the F1 score for faithfulness linear detection by using the linear representation from one task (e.g. 2-hop reasoning) to predict self-NLE faithfulness from other tasks (e.g. Ledgar and AGNews). These results corroborate the cosine similarity analysis, highlighting that the 2-hop reasoning/AGNews and AGNews/Ledgar pairs are moderately correlated with `gemma-2-27b`, enabling to properly detect faithfulness (approximately 62%). This phenomenon does not appear on smaller models.

	`gemma-2b`		`gemma-9b`		`gemma-27b`	
Base/Target	**Agnews**	**Ledgar**	**Agnews**	**Ledgar**	**Agnews**	**Ledgar**
2-hop reasoning	52.2%	56.1%	47.2%	40.0%	61.3%	36.1%
AGNews	–	45.3%	–	42.2%	–	63.1%

Table 10: Faithfulness detection by transfer, from a base to a target faithfulness linear vector.

A.5 Detailed Taxonomy of Self-NLE in Two-hop Reasoning

Taxonomy Definition. The correctness of the prediction combined with both the faithfulness and the correctness of the self-NLE and the correctness of the first hop of the latent reasoning enables to precisely characterize $e(x)$. In this subsection, we focus on ten disjoint cases of interest to characterize the behavior of f with respect to $e(x)$. Given a ground truth 2-hop reasoning trace $(o_1, r_1, o_2, r_2, o_3)$ and the actual reasoning trace obtained from both the model answer and self-NLE: $(o_1, r_1, \widehat{o_2}, r_2, \widehat{o_3})$:

- (C_1) **Complete reasoning failure.** $\widehat{o_3} \neq o_3$, $F(x, e) = 0$, $\widehat{o_2} \neq o_2$ and $\forall (k, \ell) \in \Gamma, o_2 \notin \tilde{h_k^\ell}$. *Observation:* Wrong prediction, incorrect unfaithful explanation, ground-truth bridge object undetected in circuit Γ. *Interpretation:* Evidence suggests failure in first-hop reasoning, with neither explanation nor internal representations containing the expected bridge object.
- (C_2) **Internal-external reasoning mismatch.** $\widehat{o_3} \neq o_3$, $F(x, e) = 0$, $\widehat{o_2} \neq o_2$ and $\exists (k, \ell) \in \Gamma, o_2 \in \tilde{h_k^\ell}$. *Observation:* Wrong prediction, incorrect unfaithful explanation, but ground-truth bridge object detected in circuit Γ. *Interpretation:* The model appears to have correct internal knowledge but generates inconsistent explanations, indicating potential reasoning-explanation dissociation because of either deceptiveness or hallucination.
- (C_3) **Explanation-prediction association.** $\widehat{o_3} \neq o_3$, $F(x, e) = 0$ and $\widehat{o_2} = o_2$. *Observation:* Wrong prediction with unfaithful but correct explanation. *Interpretation:* The model associates the correct bridge object with incorrect prediction during explanation generation, suggesting superficial pattern matching without genuinely resolving the first hop of the 2-hop reasoning.
- (C_4) **First-hop reasoning failure.** $\widehat{o_3} \neq o_3$, $F(x, e) = 1$ and $\widehat{o_2} \neq o_2$. *Observation:* Wrong prediction with faithful but incorrect explanation. *Interpretation:* The model consistently follows an incorrect reasoning pathway, indicating error in first-hop reasoning or concept misunderstanding.
- (C_5) **Second-hop reasoning failure.** $\widehat{o_3} \neq o_3$, $F(x, e) = 1$ and $\widehat{o_2} = o_2$. *Observation:* Wrong prediction with faithful and correct explanation. *Interpretation:* The model correctly identifies he bridge object but fails in second reasoning step, suggesting error occurs after successful first-hop completion.
- (C_6) **Shortcut learning.** $\widehat{o_3} = o_3$, $F(x, e) = 0$, $\widehat{o_2} \neq o_2$ and $\forall (k, \ell) \in \Gamma, o_2 \notin \tilde{h_k^\ell}$. *Observation:* Correct prediction with unfaithful incorrect explanation, ground-truth bridge object undetected. *Interpretation:* Evidence suggests direct $o_1 \rightarrow o_3$ association, consistent with shortcut learning behavior that bypasses intermediate reasoning steps.
- (C_7) **Deceptiveness or hallucination.** $\widehat{o_3} = o_3$, $F(x, e) = 0$, $\widehat{o_2} \neq o_2$ and $\exists (k, \ell) \in \Gamma, o_2 \in \tilde{h_k^\ell}$. *Observation:* Correct prediction with unfaithful incorrect explanation, but ground-truth bridge object detected internally. *Interpretation:* The model possesses correct internal knowledge but generates deceptive (or hallucinated) explanations, suggesting reasoning-explanation dissociation or alternative reasoning pathways. This case is expected to be rare, otherwise highlighting a case where f is not honest in its self-NLE while "knowing" the ground truth bridge object, raising a problem in f alignment.
- (C_8) **Explainer parrot.** $\widehat{o_3} = o_3$, $F(x, e) = 0$ and $\widehat{o_2} = o_2$. *Observation:* Correct prediction with unfaithful but correct explanation. *Interpretation:* The model generates the expected explanation

Incorrect Predictions					
Model	**C1** Complete reasoning failure	**C2** Internal-external reasoning mismatch	**C3** Explanation-prediction assoc.	**C4** First-hop reasoning failure	**C5** Second-hop reasoning failure
`gemma-2-2b`	23.8%	4.2%	14.4%	16.0%	41.6%
`gemma-2-9b`	26.1%	4.5%	14.5%	14.1%	40.9%
`gemma-2-27b`	22.8%	4.4%	12.5%	17.1%	43.1%
`mistral-3-7b`	46.5%	13.7%	7.1%	8.4%	24.2%

Table 11: Distribution of categories for incorrect predictions across model sizes.

Correct Predictions					
Model	**C6** Shortcut learning	**C7** Deceptiveness or hallucination	**C8** Explainer parrot	**C9** Alternative reasoning pathway	**C10** Reliable oracle
`gemma-2-2b`	27.8%	6.1%	17.7%	8.1%	40.3%
`gemma-2-9b`	14.9%	4.2%	20.0%	6.8%	54.0%
`gemma-2-27b`	12.8%	3.1%	15.3%	6.4%	62.4%
`mistral-3-7b`	20.6%	4.0%	19.3%	5.2%	50.9%

Table 12: Distribution of categories for correct predictions across model sizes.

without corresponding detectable internal reasoning, suggesting post-hoc explanation generation (i.e. "explainer parrot" behavior).

- **(C_9) Alternative reasoning pathway.** $\widehat{o_3} = o_3$, $F(x, e) = 1$ and $\widehat{o_2} \neq o_2$. *Observation:* Correct prediction with faithful but incorrect explanation. *Interpretation:* The model uses a consistent but non-canonical reasoning pathways, indicating bias or alternative reasoning mechanism that leads to correct outcomes through unexpected intermediate steps.
- **(C_{10}) Reliable oracle.** $\widehat{o_3} = o_3$, $F(x, e) = 1$ and $\widehat{o_2} = o_2$. *Observation:* Correct prediction with faithful and correct explanation. *Interpretation:* Strong evidence for expected canonical reasoning pathway, representing the most interpretable and reliable case for knowledge extraction and model understanding.

While this taxonomy relies on the interpreter ability to decode the model's internal activity, the systematic patterns observed across different models and tasks provide convergent evidence for these behavioral categories. We give examples of this taxonomy in Appendix A.9

A.5.1 2-hop reasoning detailed results.

Here we detail the results outlined in Section 4 and 6 by breaking down the results at the category-level as introduced above.

Taxonomy Descriptive Analysis. Table 11 highlights that the categories C1 (complete reasoning failure) and C5 (second-hop reasoning failure) are the most represented across the models. The distributions are overall highly stable for incorrect predictions whereas the category C10 (reliable oracle) increases with the model size for accurate predictions. The category C7 (deceptiveness or hallucination) tends to decrease with model size, but still represents a non negligible part of the self-NLE.

Taxonomy Faithfulness Enhancement Analysis. Table 13,14 and 15 respectively show the detailed impact of hallucination inhibition, linear faithfulness amplification and deceptiveness inhibition steering on self-NLE faithfulness. Categories C2 and C7 are the most prone to be turned into faithful self-NLE overall. Hallucination and faithfulness steering lead to significantly better results as compared to deceptiveness steering overall. Linear faithfulness amplification gives slightly better results than hallucination inhibition. Hallucination inhibition obtains slightly better results than linear faithfulness amplification for C1 and C6.

New Faithfulness After Steering Through Hallucination Inhibition (%)						
Model	**C1** Complete reasoning failure	**C2** Internal-external reasoning mismatch	**C3** Explanation-prediction assoc.	**C6** Shortcut learning	**C7** Deceptiveness or hallucination	**C8** Explainer parrot
`gemma-2-2b`	10.8%	**33.3**%	5.6%	7.4%	**36.2**%	3.0%
`gemma-2-9b`	9.2%	**13.4**%	5.1%	16.1%	**35.9**%	1.6%
`gemma-2-27b`	12.0%	**22.7**%	4.8%	12.5%	**48.9**%	2.6%

Table 13: Percentage of initially unfaithful explanations that become faithful after hallucination steering interventions, by category and model size.

New Faithfulness After Steering Through Linear Faithfulness Amplification (%)						
Model	**C1** Complete reasoning failure	**C2** Internal-external reasoning mismatch	**C3** Explanation-prediction assoc.	**C6** Shortcut learning	**C7** Deceptiveness or hallucination	**C8** Explainer parrot
`gemma-2-2b`	8.1%	**38.0**%	5.1%	9.3%	**39.5**%	1.1%
`gemma-2-9b`	6.9%	**28.4**%	3.7%	10.3%	**57.8**%	2.0%
`gemma-2-27b`	9.3%	**19.7**%	5.3%	10.9%	**40.4**%	1.3%


Table 14: Percentage of initially unfaithful explanations that become faithful after linear faithfulness steering interventions, by category and model size.

New Faithfulness After Steering Through Deceptiveness Inhibition (%)						
Model	**C1** Complete reasoning failure	**C2** Internal-external reasoning mismatch	**C3** Explanation-prediction assoc.	**C6** Shortcut learning	**C7** Deceptiveness or hallucination	**C8** Explainer parrot
`gemma-2-2b`	5.1%	3.2%	2.7%	4.7%	**13.8**%	6.0%
`gemma-2-9b`	6.1%	**11.7**%	0.6%	8.0%	**18.7**%	1.4%
`gemma-2-27b`	5.0%	6.3%	1.7%	2.7%	**9.1**%	3.3%


Table 15: Percentage of initially unfaithful explanations that become faithful after deceptiveness steering interventions, by category and model size (third experimental condition).

As shown in Figures 28, 30, and 32, we observe consistent transition patterns when steering makes unfaithful explanations faithful. For incorrect predictions, category C1 (complete reasoning failure) consistently transitions to C4 (first-hop reasoning failure), achieving faithfulness approximately 10% of the time under NEUROFAITH linear faithfulness amplification and hallucination inhibition. Category C2 (internal-external reasoning mismatch) predominantly transitions to C5 (second-hop reasoning failure) when steering succeeds. Category C3 (explanation-prediction association) exclusively leads to C5 (second-hop reasoning failure) upon becoming faithful.

Accurate predictions follow similar patterns. Category C6 (shortcut learning) transitions to C9 (alternative reasoning pathway) when made faithful, while category C8 (explainer parrot) becomes C10 (reliable oracle). Category C7 (deceptiveness or hallucination) can transition to either C9 or C10, though it more commonly becomes a reliable oracle (C10). We give several examples of unfaithful self-NLE made faithful in Appendix A.9.




(a) Initially inaccurate predictions.




(b) Initially accurate predictions.

Figure 28: Detailed taxonomy transition state analysis, before and after NEUROFAITH linear faithfulness steering on `gemma-2-2b` on 2-hop reasoning.




(a) Initially inaccurate predictions.




(b) Initially accurate predictions.

Figure 29: Detailed taxonomy transition state analysis, before and after hallucination inhibition on `gemma-2-2b` on 2-hop reasoning.




(a) Initially inaccurate predictions.




(b) Initially accurate predictions.

Figure 30: Detailed taxonomy transition state analysis, before and after NEUROFAITH linear faithfulness steering on `gemma-2-9b` on 2-hop reasoning.




(a) Initially inaccurate predictions.




(b) Initially accurate predictions.

Figure 31: Detailed taxonomy transition state analysis, before and after hallucination inhibition on `gemma-2-27b` on 2-hop reasoning.




(a) Initially inaccurate predictions.




(b) Initially accurate predictions.

Figure 32: Detailed taxonomy transition state analysis, before and after NEUROFAITH linear faithfulness steering on `gemma-2-27b` on 2-hop reasoning.



(a) Initially inaccurate predictions.



(b) Initially accurate predictions.

Figure 33: Detailed taxonomy transition state analysis, before and after hallucination inhibition on `gemma-2-2b` on 2-hop reasoning.

A.6 NEUROFAITH Instantiation for BBQ

To test whether NEUROFAITH extends to bias-related settings, we ran it on BBQ (Parrish et al., 2022), a question-answering benchmark designed to probe social biases. We use the religion bias subset and

sample 200 instances at random. The model under study is Mistral-7B. Following NEUROFAITH protocol, we ask the model to produce an answer and a self-NLE. Concepts are annotated with Claude-Opus 4.8, and we keep only those detectable in the model's representation space as steering targets (e.g., muslim identity, violence criminality, bomb attack). We then compare the concepts the self-NLE claims as important with the concepts whose steering actually affects the model's answer, as presented in Section 5.

Faithfulness is 68.4% for answers aligned with the targeted bias and 52.4% for non-aligned answers. Aligned answers are also more faithful than non-aligned ones, by about 16 points. One possible reading is that when the model follows a stereotype, the relevant concepts are strongly and directly encoded, so the explanation naturally refers to them. Non-aligned answers may rely on less direct internal computation that the self-explanation fails to reflect.

These results should be read as exploratory, and applying NEUROFAITH to BBQ requires additional analysis. Most self-NLEs cite the concepts of interest (e.g., muslim identity or violence criminality) as important to justify the answer. However, the internal reasoning that matters here is not the presence of each concept taken alone, but the association the model forms between them during inference. It is this association that should be compared with the self-explanation, and single-concept steering does not capture it directly. This makes the analysis more involved than on the datasets in the main paper. Other mechanistic approaches could address this gap. Linear Relation Encodings (Hernandez et al., 2024), for instance, could be used to probe internally how two concepts are linked, and so to test whether the relation stated in the self-explanation is the one the model actually computes.

A.7 NEUROFAITH Faithfulness Measure Comparison

In this section we examine how faithfulness as measured by NEUROFAITH compares to existing Counterfactual Intervention (CI) Atanasova et al. (2023) and Attribution Agreement (AA) approaches Parcalabescu & Frank (2024) for evaluating LLM self-NLE faithfulness. We focus on 2-hop reasoning and begin with a qualitative comparison that illustrates potential differences between these approaches, followed by a quantitative analysis that provides evidence for these observations.

A.7.1 2-hop Reasoning Faithfulness Qualitative Comparison.

To illustrate the critical differences between existing faithfulness evaluation approaches and NEUROFAITH, we examine a concrete 2-hop reasoning example (see Figure 34) that illustrates fundamental limitations in current methods (CI and AA). Given input text x, prediction $f(x)$, and self-generated explanation $e(x)$, we compare how different faithfulness approaches evaluate the same case. We analyse the following example:

- Input: x = "*The father of Carol Chomsky is*"
- Prediction: $f(x)$ = "*Harry Abraham Schatz*"
- Counterfactual Intervention: x_{cf} = "*The father of the spouse of Carol Chomsky is*"
- Counterfactual prediction: $f(x_{cf})$ = "*William Chomsky*"

Counterfactual Intervention (CI) would assess the self-NLE $e(x_{cf})$ as faithfulness. This evaluation is based solely on the presence of the intervention term "spouse" within $e(x_{cf})$, establishing consistency between the input modification and explanation content. Attribution Analysis (AA) methods consists in comparing attribution scores (e.g., using SHAP) to highlight important tokens (e.g. "father", "spouse", "Carol", "Chomsky") for the prediction and the self-NLE. High correlation coefficients between the attribution vectors for prediction and self-NLE would similarly classify the self-NLE as faithful.

On the contrary, NEUROFAITH rejects $e(x_{cf})$ as unfaithful because the bridge object ("Morris Halle") is not contained in the decoded hidden states ($\{\tilde{h_k^\ell}\}$). This mismatch between internal computation and self-NLE content reveals unfaithfulness. The steered self-NLE obtained with linear faithful steering (see Section 6) is evaluated as faithful by NEUROFAITH, due to shared bridge object ("Noam Chomsky") between the new self-NLE and the decoded hidden states.

This qualitative example illustrates that both CI and AA approaches may employ more lenient evaluation standards compared to NEUROFAITH and can miss unfaithful self-NLE. This observation is corroborated by our analysis in the next paragraph.




Figure 34: Qualitative comparison between NEUROFAITH and CI faithfulness.

A.7.2 2-hop Reasoning Faithfulness Quantitative Comparison.

We propose an experimental protocol to evaluate the practical utility of different faithfulness measures for model analysis. The protocol is motivated by two common applications of explanations in AI systems: (1) troubleshooting models by identifying the source of errors in wrong predictions Biecek & Samek (2024), and (2) detecting potential biases or shortcuts in correct predictions to ensure they align with expected reasoning processes Ribeiro et al. (2016).

We test whether faithful explanations, as identified by NEUROFAITH and CI methods, provide better diagnostic information for these purposes. The key hypothesis is that if a faithfulness measure accurately captures the model's internal reasoning, then explanations deemed faithful should better localize reasoning failures and identify non-canonical reasoning pathways.

Experimental Framework. Given an input text $x = (o_1, r_1, \blacktriangle, r_2, \bullet)$ requiring 2-hop reasoning and the model's reasoning trace $(o_1, r_1, \widehat{o_2}, r_2, \widehat{o_3})$, we categorize the model behavior using a simplified taxonomy (see Figure 35) based on prediction correctness and bridge object accuracy:

- Category A: Wrong prediction ($\widehat{o_3} \neq o_3$), wrong bridge object ($\widehat{o_2} \neq o_2$) $\rightarrow$ likely first-hop failure
- Category B: Wrong prediction ($\widehat{o_3} \neq o_3$), correct bridge object ($\widehat{o_2} = o_2$) $\rightarrow$ likely second-hop failure
- Category C: Correct prediction ($\widehat{o_3} = o_3$), wrong bridge object ($\widehat{o_2} \neq o_2$) $\rightarrow$ alternative reasoning pathway
- Category D: Correct prediction ($\widehat{o_3} = o_3$), correct bridge object ($\widehat{o_2} = o_2$) $\rightarrow$ canonical reasoning

Each category can be further subdivided with respect to faithfulness, enabling comparison between faithful and unfaithful self-NLE within each reasoning pattern. In the following we propose 3 evaluation protocols based on these 4 categories and assess if faithful self-NLE lead to better model debugging and bias targeting than unfaithful self-NLE.

First Hop Hint. We test whether faithful self-NLE better identify first-hop reasoning failures through a targeted intervention. For each input x having led to a wrong prediction ($\widehat{o_3} \neq o_3$), we create a modified version $x_{hint1} = (o_1, r_1, o_2, x)$ that explicitly provides the correct bridge object. For example:

- x = "The country of origin of the movie maker that directed Persona is"
- x_{hint1} = "The movie maker that directed Persona is Ingmar Bergman. The country of origin of the movie maker that directed Persona is"




Figure 35: Simplified taxonomy of f behavior in two-hop reasoning, based on the status of the prediction and the self-NLE.

If faithful self-NLE accurately reflect internal reasoning, then providing first-hop hints should differentially improve performance for Category A (first-hop failures) versus Category B (second-hop failures), and this difference should be stronger for faithful self-NLE. We define the performance ratio under first-hop hints as:

$$PR(A, B, hint1) = \frac{ACC(A, hint1)}{ACC(B, hint1)} \tag{2}$$

where $ACC(A, hint1)$ represents the accuracy of Category A examples when given first-hop hints. We compute separate ratios for faithful and unfaithful explanations:

$$PR(A, B, hint1, faithful) = \frac{ACC(A, hint1, faithful)}{ACC(B, hint1, faithful)} \tag{3}$$

Finally, the Compound Accuracy Score (CAS) quantifies whether faithful explanations provide better error localization:

$$CAS(A, B, hint1) = \log\Big(\frac{PR(A, B, hint1, faithful)}{PR(A, B, hint1, unfaithful)}\Big) \tag{4}$$

A positive CAS indicates that faithful self-NLE better identify first-hop failures. This metric is conceptually close to the In-Context Editing instantiation of the approach proposed by Zaman & Srivastava (2025) to compare faithfulness measures. In the following, we extend beyond this proposal with two other metrics.

Quality Metric	`gemma-2-2b`			`gemma-2-9b`			`gemma-2-27b`	
	NEUROFAITH	CI	AA	NEUROFAITH	CI	AA	NEUROFAITH	CI
hint1	**0.04**	-0.07	-0.23	0.06	-1.10	**0.40**	**0.75**	-0.99
hint2	**-0.44**	-0.55	-1.23	**0.28**	-0.03	0.15	-0.35	**1.25**
$r_2 \to r_2'$	0.09	-2.62	**1.32**	**0.17**	-0.32	0.01	**0.31**	-0.26

Table 16: NEUROFAITH comparison to CI and AA (higher is better) across models on 352 CI-compatible samples on 2-hop reasoning.

Quality Metric	`gemma-2-2b`	`gemma-2-9b`	`gemma-2-27b`
hint1	0.48	0.14	0.22
hint2	0.03	0.33	0.88
$r_2 \to r_2'$	-0.04	1.18	0.40

Table 17: NEUROFAITH evaluation across models on the overall 2-hop reasoning dataset.

Second Hop Hint. We then test whether faithful self-NLE better identify second-hop reasoning failures through a targeted intervention. Following the logic introduced above, for each input x having led to a wrong prediction ($\widehat{o_3} \neq o_3$), we create a modified version $x_{hint2} = (o_2, r_2, o_3, x)$ that explicitly provides the second part of the 2-hop reasoning. For example:

- $x =$ "The country of origin of the movie maker that directed Persona is"
- $x_{hint2} =$ "The country of origin of Ingmar Bergman is Sweden. The country of origin of the movie maker that directed Persona is"

If faithful self-NLE accurately reflect internal reasoning, then providing second-hop hints should differentially improve performance for Category B (second-hop failures) versus Category A (first-hop failures), and this difference should be stronger for faithful self-NLE. We build our second metric following the notations introduced above, based on the Compound Accuracy Score:

$$CAS(B, A, hint2) = log\Big(\frac{PR(B, A, hint2, faithful)}{PR(B, A, hint2, unfaithful)}\Big) \tag{5}$$

Here, a positive CAS indicates that faithful self-NLE better identify second-hop failures.

Second Relation Modification. We test whether faithful self-NLE better identify non-canonical reasoning pathways through the modification of the second step of the reasoning trace (r_2). Intuitively, a non-canonical reasoning pathway is more prone to leading to false reasoning when changing one step of the 2-hop reasoning. For each input x having led to a correct prediction ($\widehat{o_3} = o_3$), we create a modified version $x_{r_2 \to r_2'} = (o_1, r_1, \blacktriangle, r_2', \bullet)$ that changes the second relation of the 2-hop reasoning input. For example:

- $x =$ "The country of origin of the movie maker that directed Persona is"
- $x_{r_2 \to r_2'} =$ "The father of the movie maker that directed Persona is"

If faithful self-NLE accurately reflect internal reasoning, then changing r_2 should significantly decrease performance for Category C (alternative reasoning pathway) versus Category D (canonical reasoning), and this difference should be stronger for faithful self-NLE. We build our third metric following the notations introduced above, based on the Compound Accuracy Score:

$$CAS(D, C, r_2 \to r_2') = log\Big(\frac{PR(D, C, r_2 \to r_2', faithful)}{PR(D, C, r_2 \to r_2', unfaithful)}\Big) \tag{6}$$

A positive CAS indicates that faithful self-NLE better identify non-canonical reasoning pathways.

Experimental Results. We evaluate our three faithfulness indicators to compare NEUROFAITH to commonly used Attribution Agreement (AA) and Counterfactual Intervention (CI) methods. The Wikidata-2-hop dataset provides natural support for computing $x_{r_2 \to r_2'}$ instances, as it contains multiple reasoning chains involving similar objects. Additionally, the dataset includes counterfactual interventions through variations in reasoning chains, enabling straightforward CI computation as in Atanasova et al. (2023) across multiple instances. We implement AA based on gradient-based attributions as in Wiegreffe et al. (2021). Due to prohibitive cost for 27-billion models, we only apply AA to `Gemma-2-2B` and `Gemma-2-9B`.

Our evaluation reveals 2 key findings. First, Table 2 shows NEUROFAITH outperforms CI and AA on average on the subset of CI-compatible samples. Second, Table 17 presents NEUROFAITH results on the complete dataset, showing positive metric values across all models except `gemma-2-2b`.

A.8 Classification Examples

This section gives two examples of instances characterized as either faithful or unfaithful in classification case.




Figure 36: Example from the AGNews dataset where we detect "sport event" and "athletic competition" as relevant concepts from the explanation. These two concepts are assessed as important for the prediction, making this explanation faithful ($F(x, e) = 1$).




Figure 37: Example from the Ledgar dataset where we detect "post-termination obligations", "duration of surviving terms" and "payment obligations survival" as relevant concepts from the explanation. Two concepts over three are assessed as important, giving an explanation faithfulness score at 0.67.

A.9 2-hop Reasoning Taxonomy Examples

In this section we give examples of characterized instances based on the taxonomy introduced in Appendix A.5. We also give examples of unfaithful self-NLE made faithful, characterized by the same taxonomy.




Figure 38: Example from the Wikidata-2-hop dataset where we observe an internal-external reasoning mismach. The model incorrectly answers "Jobete Music" and provides a self-NLE referencing to the bridge object "Sam Cooke". This bridge object is false and does not appear in the set of natural language interpretations of f latent states. However, the ground truth bridge object "Louis Armstrong" is decoded at token index 11 and layers 13 and 14.




Figure 39: Example from the Wikidata-2-hop dataset where we observe shortcut learning. The model correctly answers "France" and provides a self-NLE referencing to "Alain Resnais". This bridge object is incorrect and does not appear in the set of natural language interpretations of f latent states.




Figure 40: Example from the Wikidata-2-hop dataset where we observe shortcut learning. The model correctly answers "Germany" without providing any bridge object in its self-NLE. The expected bridge object "The Lost Honour of Katharina Blum" is however decoded from the representation space.




Figure 41: Example from the Wikidata-2-hop dataset where we observe an explainer parrot case. The model correctly answers "Germany" and provides a self-NLE referencing to "Wim Wenders". This bridge object is correct but does not appear in the set of natural language interpretations of f latent states.



Figure 42: Example from the Wikidata-2-hop dataset where we observe an alternative reasoning pathway. The model correctly answers "Japan" and provides a self-NLE referencing to "Square Enix". This bridge object is incorrect and also appears in the set of natural language interpretations of f latent states.




Figure 43: Example from the Wikidata-2-hop dataset where we observe a faithful canonical reasoning pathway. The model correctly answers "USA" and provides a self-NLE referencing to "Pierre Omidyar". This bridge object is correct and also appears in the set of natural language interpretations of f latent states.




Figure 44: Example from the Wikidata-2-hop dataset where we start from an incorrect unfaithful explanation and go to a correct and faithful explanation through NEUROFAITH linear faithfulness steering.




Figure 45: Example from the Wikidata-2-hop dataset where we start from an incorrect unfaithful explanation and go to a correct and faithful explanation through NEUROFAITH linear faithfulness steering.



Figure 46: Example from the Wikidata-2-hop dataset where we start from an incorrect unfaithful explanation and go to a still incorrect but faithful explanation through NEUROFAITH linear faithfulness steering.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: Both in the abstract and the introduction, we accurately describes the scope and objective of the work.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Done in the conclusion.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [N/A]

Justification: The paper does not include theoretical results

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Mostly done in the very long appendix.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
     (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [No]

Justification: We speifiy that the code will be accessible upon acceptance.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Detailed information in Appendix.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: Yes when needed, with detailed about statistical tests in Appendix.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
   - The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
   - The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)

- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Specified in Appendix.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: Yes we reviewed the Code of Ethics.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [N/A]

    Justification: No significant ethical concerns. The work may benefit downstream trustworthy-AI applications.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.

- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The paper poses no such risks

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: Detailed in Appendix.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.
    - For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
    - If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
    - For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.

- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [N/A]

    Justification: The paper does not release new assets

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: The paper does not involve crowdsourcing nor research with human subjects

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The paper does not involve crowdsourcing nor research with human subjects

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: LLM usage details provided.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.