SATISFIABILITY IS NOT ENOUGH: FIDELITY-GATED REPAIR OF LLM-EXTRACTED HYBRID AUTOMATA

Anonymous authors
Paper under double-blind review

ABSTRACT

Large language models can translate technical manuals into symbolic models, but verifier-guided correction creates a distinct failure mode: a proposer can make a model satisfiable by deleting the obligations that made it unsatisfiable. We call this *solver gaming*. We present a source-traced pipeline that extracts partially observable hybrid-automaton (POHA) graphs, checks discrete and algebraic constraints with an SMT (Satisfiability Modulo Theories) Solver, and places a deterministic fidelity gate before repaired graphs can become active. The gate preserves source traces, declarations, guards, effects, evidence, minimum durations, sensor status, epistemology scope, and safety classifications; source support for additions remains a separate evidence-review obligation. In a natural pre-gate run, an unconstrained loop reached Satisfiability (*SAT*) through ten unsupported safety downgrades; the gate rejected both affected edits. In a controlled 20-case benchmark, all 15 valid additive candidates were accepted and all 5 solver-satisfying effect deletions were rejected. Separately, we test the utility of *raw*, not fidelity-gated, graphs for downstream decision support. Across a chosen dataset of 100 cyber-physical scenarios and five trials per scenario, graph augmentation improved exact decision accuracy from 77.33% to 87.33% on a challenge set and from 78.00% to 87.00% on a representative set. These results establish repair-integrity behavior and raw-graph utility as separate findings: they do not establish physical completeness or downstream benefit from repaired graphs. However, we note that formal graph structures can occasionally over-constrain valid actions, increasing False Rejection Rate (FRR) in exchange for strict safety compliance.

1 INTRODUCTION

Large language models (LLMs) have demonstrated exceptional capabilities in translating natural-language descriptions into executable programs and formal specifications (Chen et al., 2021; Rozière et al., 2023; Cosler et al., 2023). In cyber-physical systems (CPS) and safety-critical domains, technical manuals encode complex operating modes, physical preconditions, temporal requirements, and hazard exceptions. Standard retrieval-augmented generation (RAG) (Lewis et al., 2020a) exposes these relevant passages to a language model; however, retrieved text remains a collection of localized statements. Decisions that depend on distributed physical conditions, a strict transition sequence, or an unavailable sensor observation remain notoriously difficult for purely neural systems, a phenomenon recently identified as *implicit constraint blindness*—where LLMs overlook logical constraints present in formal representations (Wang et al., 2026). Symbolic models provide a necessary, complementary representation. Hybrid automata combine discrete control modes with continuous-variable updates and timing constraints (Alur et al., 1995; Henzinger, 1996), while partial observability models explicitly represent uncertainty about system state when observations are incomplete (Kaelbling et al., 1998). Existing neuro-symbolic methods address related reasoning limitations either by offloading reasoning to classical planners (Liu et al., 2023) or by enforcing structural graphs via Design-by-Contract frameworks such as HyDRA (Kaiser et al., 2025). However, both approaches suffer from a manual knowledge-engineering bottleneck, requiring domain experts to pre-author physical rules.

To bypass this bottleneck, we propose extracting formal models—specifically, Partially Observable Hybrid Automata (POHAs)—directly from unstructured technical specifications. We use an oper-

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

ational four-dimensional semantic decomposition comprising *Topology* (state-transition structure), *Ontology* (physical constraints and safety classifications), *Temporality* (timing lower bounds), and *Epistemology* (sensor observability). In this context, our extracted POHA is a pragmatic representation using quantifier-free algebraic conditions and elapsed-time constraints; we do not infer differential equations or claim general continuous reachability. While we do not claim that these dimensions are mathematically complete or minimal, they provide a sufficient basis to map natural language into a verifiable POHA for decision support.

Because technical manuals contain implicit tolerances and domain-specific nuances, initial extractions of these four dimensions frequently fail formal mathematical verification. To correct flawed extractions, recent architectures employ LLM-driven predict-then-verify refinement loops, where candidate formal specifications are iteratively generated by the LLM (the proposer) and checked against a formal mathematical tool, such as an SMT solver (the verifier) (Ding et al., 2024a; Dantas et al., 2025). While effective for standard code generation, this closed-loop approach exposes a critical vulnerability in safety-critical extraction.

We call this failure mode **solver gaming**: optimizing a generated formal artifact for verifier acceptance by changing the intended proposition. When constrained purely by mathematical satisfiability, LLM proposers may produce wrong repairs. A shortened delay, a removed guard, a fabricated sensor claim, or a silent safety downgrade can easily convert an unsatisfiable (`UNSAT`) model into a satisfiable (`SAT`) one, trivially bypassing the solver while making the model different from the source text. Since an SMT solver proves only properties of its mathematical encoding, satisfiability alone cannot establish semantic preservation or source support.

To address this reliability gap, we present a novel neuro-symbolic pipeline that evaluates solver consistency and repair validity separately. Our core contribution is the integration of a deterministic **fidelity gate** governed by a **bounded repair contract**. This contract treats the LLM as an untrusted proposer and rejects inconsistent changes. Specifically, the contract preserves source traces, existing sensor-verification status, guards, effects, timing lower bounds, and safety classifications against downgrade. By quarantining destructive modifications, the compiled POHA provides a verifiable symbolic context for downstream decision support without succumbing to solver-gaming degradation. We study this problem using section-level POHAs extracted from different sections of automotive manuals, evaluating both the extraction-repair pipeline and the downstream utility of the resulting graphs in RAG decision environments. In summary, our contributions are:

- a typed extraction and verification pipeline spanning topology, ontology, temporality, and epistemology;
- a formal repair criterion separating solver consistency, structural preservation, and source support;
- a deterministic fidelity gate and auditable unresolved outcome to ensure repair integrity; and
- two paired evaluations of raw graph context, including statistical tests and negative cases that delimit the downstream claim.

Crucially, our primary claims center on structural *repair integrity* rather than absolute physical correctness. Furthermore, to evaluate these mechanisms independently, our experiments deliberately decouple the two phenomena: the downstream evaluation tests the inherent utility of raw graph context for decision support, distinct from the automated repair pipeline.

2 Related Work

Our framework addresses the intersection of four domains: the limitations of purely neural reasoning in cyber-physical contexts, the extraction of hybrid automata from text, the architectural design of neuro-symbolic refinement loops, and the grounding of retrieval-augmented decision agents.

Constraint Blindness and Classical Offloading While LLMs possess expansive semantic knowledge, they natively lack a structured mechanism to enforce dynamic physical laws or rigorous operational invariants. Recent studies characterize this limitation as *implicit constraint blindness*, where LLMs fail to respect explicit logical constraints even when they are present in the prompt (Wang et al., 2026). To address related limitations, neuro-symbolic architectures can offload structured reasoning to external

symbolic systems. LLM+P (Liu et al., 2023) translates natural language instructions into Planning Domain Definition Language (PDDL) to leverage classical planners for optimal action sequencing. While LLM+P successfully enforces logical consistency, it relies heavily on manually pre-engineered domain knowledge. Our work seeks to eliminate this manual engineering bottleneck by enabling the automatic extraction of the domain rules themselves directly from technical documentation.

Formal Specification Extraction and Hybrid Automata Translating unstructured natural language into formal logic is a foundational challenge in requirements engineering. Early neuro-symbolic approaches demonstrated the viability of LLMs for generating discrete temporal logics (e.g., nl2spec (Cosler et al., 2023)) and spatial robot task specifications (e.g., Lang2LTL (Ding et al., 2023)). However, these systems predominantly target discrete state spaces. Cyber-physical systems operate in continuous environments, necessitating representations like POHA, which integrate discrete control modes, continuous-variable updates, and partial observability constraints (Alur et al., 1995; Kaelbling et al., 1998). Recent advancements have begun exploring formal specification extraction from cyber-physical documentation (e.g., (Li et al., 2025)), but they rarely enforce end-to-end topological, temporal, and epistemological constraints. We address this gap by proposing an operational four-dimensional semantic decomposition that provides a structural basis for extracting verifiable POHAs.

Proposer-Verifier Loops and Solver Gaming To bridge the semantic gap during automated extraction, recent architectures utilize closed-loop refinement frameworks, where an LLM (the proposer) generates a candidate specification that is subsequently evaluated by a mathematical tool like an SMT solver (Sun et al., 2024; Ding et al., 2024b). Feedback from the verifier is iteratively fed back to the LLM to guide correction (Dantas et al., 2025). This architecture adapts the classic Counterexample-Guided Inductive Synthesis (CEGIS) loop (Solar-Lezama et al., 2006) for neural systems, replacing the traditional algorithmic synthesizer with a language model. While theoretically sound, we identify that these loops are vulnerable to a failure mode we term solver gaming. Analogous to specification gaming in reinforcement learning (Krakovna et al., 2020), an unconstrained LLM will optimize for verifier acceptance by silently relaxing preconditions or deleting unprovable safety claims, achieving mathematical satisfiability through degenerate logic, such as silently deleting protected effects. To counteract this, recent works have explored enforcing structured behavior via Design-by-Contract (DbC) principles on LLM outputs (e.g., (Leoveanu-Condrei, 2025)). Building on this concept, we introduce a bounded repair contract—an independent deterministic gate that prevents the proposer from satisfying the solver via semantic downgrades.

Symbolic Grounding in Agentic Decision-Making Retrieval-Augmented Generation (RAG) grounds language models in external factual evidence, significantly reducing standard hallucination rates (Lewis et al., 2020b). However, unstructured text retrieval provides insufficient scaffolding for complex reasoning over continuous physical states or multi-step operational rules. We advance this paradigm by automatically compiling verifiable POHAs from raw technical text and integrating these structured formal artifacts back into the RAG context window. By providing the LLM with an executable state-transition structure, our approach enforces a rigorous, deterministically derived boundary on agentic decision-making, demonstrating that graph-augmented reasoning significantly improves safety-critical accuracy over unstructured text alone. We intentionally structure our downstream study to isolate the marginal effect of the implemented serialization; structured-text and discrete-FSM controls are missing baselines, not implied results.

3 Problem Formulation

In this section, we provide an intuitive grounding for the components of a cyber-physical system, formalize this representation as a POHA and explicitly define our threat model of solver gaming.

3.1 Intuitive Grounding: Formalizing a Technical Manual

We assume the input is standard cyber-physical technical documentation (e.g., vehicle operating manuals or safety checklists) containing implicit operational modes and preconditions. Consider a standard safety instruction from that documentation: "If the 12-volt battery is frozen, it must be replaced. Never attempt to charge a frozen battery." Though this may look like a clear instruction to a human, it is a challenge for an autonomous agent, as this text must be parsed into an executable,

verifiable structure. We decompose this instruction into four formal dimensions, which directly populate the mathematical components of our automaton:

1. **Topology (States and Transitions):** The system consists of a set of discrete states S, such as "connected" and "replacement_required". There must exist a directed transition edge $t \in T$ dictating that if the battery is frozen, the system moves from the source state to the target state defined as $t = (s_{\text{src}} = \text{"connected"}, s_{\text{dst}} = \text{"replacement_required"})$.
2. **Ontology (Variables, Constants, and Effects):** We define the physical variables X, such as the battery temperature $x_{\text{temp}} \in X$, and comparative constants C, such as a freezing threshold $c_{\text{freezing}} = 0°\text{C} \in C$. We must also map semantic effects E_t, ensuring that the resulting state transition is explicitly classified as safety-critical: $E_t \implies \kappa_t = \texttt{True}$.
3. **Epistemology (Guards and Partial Observability):** An autonomous system cannot inherently "know" a battery is frozen. The transition t must be protected by a precondition guard P_t, such as $x_{\text{temp}} < 0$, which relies on a physically verifiable sensor variable $x \in X$. If the system lacks this sensor, the state is partially observable. Thus, we define an epistemology scope σ_t to determine whether the transition is a machine-authorized action or a human-observed passive hazard: $\sigma_t \in \{\texttt{machine_authorized}, \texttt{human_observed}, \texttt{passive_hazard}\}$.
4. **Temporality (Time Constraints):** Building directly on this intuitive decomposition, we formally define the extraction target as a section-level POHA graph : $\delta_t > 0$.

3.2 Source-Traced POHA Representation

For implementation and evaluation, a section-level POHA graph is defined as the tuple:

$$\mathcal{H} = (X, C, S, T, \tau), \tag{1}$$

where X is a set of typed variables, C symbolic constants, S named states with invariants, T directed transitions, and τ a trace to document, section, headings, and pages. While classical hybrid automata definitions omit traceability, we explicitly extend the tuple with τ to enable automated evidence verification during model repair. Each transition $t \in T$ is defined as

$$t = (s_{\text{src}}, s_{\text{dst}}, P_t, E_t, \delta_t, \kappa_t, \epsilon_t, \sigma_t), \tag{2}$$

where P_t and E_t are preconditions (guards) and effects (resets), δ_t is minimum elapsed duration, κ_t is a boolean safety-critical flag, ϵ_t is source evidence, and σ_t is epistemology scope. Variables record type, domain, semantic role, and sensor-verification status. To ensure computational tractability, our SMT backend verifies finite graph structure, discrete mode transitions, and quantifier-free algebraic conditions; it does not verify continuous differential flows.

3.3 Repair validity and threat model

Given original graph $\mathcal{H}$, findings F, manual evidence M, and proposer P_{LLM}, the model generates $\mathcal{H}' = P_{\text{LLM}}(\mathcal{H}, F, M)$. We distinguish three obligations for accepting a repair:

$$\text{ValidRepair}(\mathcal{H}, \mathcal{H}') = \text{SAT}(\mathcal{H}') \wedge \text{Preserve}(\mathcal{H}, \mathcal{H}') \wedge \text{Supported}(\mathcal{H}', M). \tag{3}$$

Here, SAT denotes formal mathematical consistency, Preserve denotes the strict retention of original semantic constraints and source traces, and Supported requires the modifications to be explicitly grounded in the source text evidence. Solver gaming occurs when $\text{SAT}(\mathcal{H}')$ holds, but $\text{Preserve}(\mathcal{H}, \mathcal{H}')$ or $\text{Supported}(\mathcal{H}', M)$ fails. Unlike standard open-loop hallucination, solver gaming is a closed-loop optimization artifact where the proposer actively exploits verifier feedback to bypass constraints via vacuous satisfaction or invariant relaxation. In this critical failure mode, an unconstrained LLM proposer achieves mathematical satisfiability via degenerate modifications that abandon the intended physical semantics. For example, rather than adding a missing physical sensor guard to resolve a topological conflict, the proposer might silently delete the safety-critical classification of the state. This trivially satisfies the mathematical constraints by subverting the intended specification, demonstrating that formal satisfiability alone is an incomplete condition for valid model repair.

4 METHOD

To enforce the repair obligations defined by our threat model ($\mathrm{ValidRepair}$), we propose a neuro-symbolic pipeline that strictly isolates the verification of mathematical consistency from the enforcement ($\mathrm{Preserve}$) and the source evidence ($\mathrm{Supported}$).

4.1 PIPELINE

The extraction and bounded repair pipeline (illustrated in Figure 1) operates iteratively, processing the technical manual section by section. The process begins with an LLM extracting a candidate POHA graph under a strict, typed JSON schema representing our four operational dimensions. To fulfill the traceability requirement (τ), every extracted component is explicitly linked to page-level provenance. Before engaging the SMT solver, the pipeline performs deterministic static audits. These checks reject fundamental extraction failures, such as undeclared identifiers, impossible self-comparisons, and continuous-variable updates lacking elapsed-time interpretations. For ontology alignment, the system algorithmically groups cross-section synonyms using their type, domain, semantic role, and source evidence. Co-occurring symbols are conservatively prevented from merging, as simultaneous usage typically indicates related but distinct physical concepts. The extraction process initially generates a candidate POHA, which is then subjected to the fidelity gate to ensure structural preservation. Any repair candidates are staged and re-verified, with solver consistency checks ensuring that the modifications do not introduce logical inconsistencies.

4.2 MATHEMATICAL COMPILATION AND VERIFICATION CONDITIONS

Graphs that pass the static audit are compiled into SMT constraints. Continuous variables are mapped to `Real`, booleans to `Bool`, and discrete modes to `String`. Named assertions are utilized to ensure that any unsatisfiable cores generated by the solver can be directly mapped back to specific, graph-local findings (de Moura and Bjørner, 2008).

The compiler generates formal verification conditions corresponding to the four semantic families extracted from the manual:

- **Topological Consistency:** Transition endpoints must resolve to declared states within the active scope, and state invariants must not generate direct logical contradictions.
- **Temporal Decidability:** To ensure continuous-variable updates remain mathematically decidable, any transition that resets or updates a continuous variable must be bounded by a strictly positive minimum elapsed time: $\mathrm{UpdatesContinuous}(t) \Rightarrow \delta_t > 0$
- **Epistemological Grounding:** A transition classified as both safety-critical (κ_t) and explicitly machine-authorized (σ_t) must include a precondition guard referencing a sensor-verified physical fact: $\kappa_t \wedge (\sigma_t = \texttt{machine_authorized}) \Rightarrow \exists p \in P_t : \mathrm{SensorVerified}(p)$ Passive hazards and human-observed procedures are intentionally excluded from this machine-authorization boundary.
- **Ontological Alignment:** The compiler checks type-compatible expressions and confirmed canonical relationships. An optional world-model layer separates confirmed invariants from unresolved gaps, enforcing generated world-model statements only when their status permits.

4.3 FIDELITY GATE

To prevent solver gaming during the repair phase, the pipeline enforces the $\mathrm{Preserve}$ relation through a deterministic fidelity gate. When the LLM proposes a candidate repair Δ, it is compared topologically with the original graph using a strictly symbolic, non-neural algorithm. Existing transitions sharing source and target states are matched one-to-one via maximum-weight bipartite matching over normalized guards, effects, evidence, and duration. This mapping prevents the LLM from obfuscating destructive deletions through list reordering or edge duplication. The fidelity gate acts as a structural semantic-difference checker. It strictly rejects any candidate containing: changes to source traces, existing variable typings, or sensor statuses; the removal of variables, states, transitions, invariants, guards, or effects; safety-critical downgrades; epistemology-scope drift; and reductions in minimum



Figure 1: Workflow of the neuro-symbolic extraction and repair pipeline, highlighting the fidelity gate and decision-time graph augmentation.

time durations δt). While this strict non-deletion policy prevents the automated pruning of spurious initial extractions, it intentionally prioritizes absolute safety over model minimality. Conversely, the gate permits monotone additions, longer durations, and promotion to safety criticality. Accepted candidates are saved as edits and re-verified in the next outer loop. Candidates failing the fidelity check are quarantined with machine-readable violations, forcing the LLM to generate an alternative. Exhausted retries yield an *unresolved* status. Representative clauses are -

$$\tau' = \tau, \qquad X \subseteq X', \qquad S \subseteq S', \qquad T \preceq T', \tag{4}$$

$$P_t \subseteq P'_{m(t)}, \qquad E_t \subseteq E'_{m(t)}, \qquad \epsilon_t \subseteq \epsilon'_{m(t)}, \tag{5}$$

$$\kappa_t \Rightarrow \kappa'_{m(t)}, \qquad \sigma_t = \sigma'_{m(t)}, \qquad \delta_t \leq \delta'_{m(t)}. \tag{6}$$

Here m is a one-to-one maximum-weight bipartite matching within each source/target transition group, scored over normalized guards, effects, evidence, and duration. Matching prevents list reordering or duplicate edges from hiding deletions.

4.4 Authorized Expert Resolution

Strict structural preservation cannot correct fundamental category errors already present in the initial extraction (e.g., if an LLM incorrectly classified a physical hazard as a machine-authorized action). A separate deterministic workflow allows for authorized human resolution. This workflow accepts a signed resolution containing a reviewer identity, the targeted transition, the authorized operation, and quoted manual evidence. The system validates unique targeting, quote occurrence within traced pages, and schema conformance.

4.5 Decision-Time Graph Augmentation

To evaluate the operational utility of the verified POHAs, we introduce a graph routing mechanism for downstream Retrieval-Augmented Generation (RAG). Given a natural language scenario q and retrieved manual chunks $R(q)$, the routing algorithm calculates a relevance score $s(q, \mathcal{H})$ combining query–graph token overlap, section overlap, retrieved-page overlap, and matched structural elements:

$$s(q, \mathcal{H}) = |T_\cap| + 10|S_\cap| + 100|P_\cap| + E_{\text{score}} \tag{7}$$

where element matches E_{score} contribute four points per variable or constant, two per state, and three per transition, capped at 40 points. The highest-ranked section graph is structurally pruned to its matching elements before serialization into the LLM prompt. The downstream agent evaluates $R(q)$ alongside the serialized graph context to emit `ALLOW`, `BLOCK`, or `CLARIFY`. `BLOCK` requires a known violated decision-critical condition. `CLARIFY` requires an unknown fact whose value could fundamentally alter the decision, preventing the agent from vacuously requesting clarification for every unobserved variable.

5 Experiments and Results

We evaluate our neuro-symbolic extraction and repair pipeline to answer two primary research questions: (1) Does the deterministic fidelity gate successfully prevent solver gaming during automated

repair? (2) Does raw symbolic graph context mathematically improve the accuracy of downstream safety-critical decision agents?

5.1 Experimental Setup

We evaluate our pipeline using a 91-page slice of an automotive manual covering eight cyber-physical domains. Downstream RAG tasks use hybrid reciprocal-rank fusion. All LLM inference was conducted using `gpt-5.4-2026-03-05` at T=0.0 to ensure deterministic generation. Comprehensive hyperparameter, retrieval, and deployment details are provided in **Appendix A**.

5.2 Evaluation Datasets

Though we have done many experiments across various vehicle manuals, we focus our evaluation on a representative subset of these manuals to provide a detailed analysis of our approach's effectiveness. We constructed two distinct evaluation suites to rigorously assess both the robustness of our repair mechanism and the effectiveness of our downstream decision agents.

1. *The Adversarial Repair Suite:* A targeted 20-case diagnostic benchmark isolating specific extraction failures across our four semantic dimensions (Topology, Temporality, Epistemology, Ontology).
2. *The Downstream Decision Suite:* A deterministically structured corpus of 100 scenarios, divided into a frozen 60-scenario Challenge set (30 matched easy/hard pairs) and a 40-scenario Representative set. Each scenario evaluates an exact decision (ALLOW, BLOCK, or CLARIFY). By evaluating 100 highly curated cyber-physical scenarios over 1,000 total inference calls (100 scenarios $\times$ 5 trials $\times$ 2 arms), this dataset provides robust statistical power to resolve performance deltas via paired testing.

5.3 Ablation Study: Repair Integrity

We conduct an ablation study to evaluate our first primary claim: unconstrained SMT-based refinement loops are susceptible to solver gaming via semantic degradation, necessitating an independent fidelity gate.

Natural Repair Evasion (The Ungated Baseline): To establish the baseline prevalence of solver gaming, we retrospectively audited a natural, ungated correction loop on two validation graphs that initially produced UNSAT epistemological findings. The unconstrained proposer-verifier loop successfully achieved SAT. However, an audit revealed that it did so exclusively by flipping exactly ten `is_safety_critical` fields from True to False, without adding any supported physical guards. This is direct, empirical evidence that formal solver success and semantic repair validity dangerously diverge in LLM-driven loops.

Controlled Benchmark (The Gated Pipeline): To validate our proposed mitigation, we evaluated the deterministic fidelity gate against a 20-case adversarial diagnostic suite. This benchmark injected five defects across each verifier family: Topology (requiring source-supported states), Temporality (requiring increased minimum durations), Epistemology (requiring sensor-grounded guards), and Ontology (requiring the evasion of a confirmed invariant by deleting a protected effect). The fidelity gate achieved a 100% valid-repair acceptance rate (15/15 valid additive candidates passed) and a 0% escape rate (5/5 destructive ontology candidates were quarantined). For the 5 destructive cases, the LLM attempted to achieve topological satisfiability by deleting protected safety effects. The fidelity gate explicitly flagged these as non-monotone solver-gaming attempts, rejected the edits, and returned an honest, auditable unresolved status.

A complete procedural log detailing one of these adversarial solver-gaming attempts and its subsequent quarantine is provided in **Appendix D**.

5.4 Downstream Decision Utility

To evaluate our second claim and measure operational value, we conducted a paired evaluation by comparing a baseline text-only RAG agent (`rag_only`) against an identical agent augmented with

Table 1: Exact decisions over five trials per scenario

Set	Arm	Correct/Total	Accuracy	Macro-F1
Challenge	RAG	232/300	77.33%	0.7694
Challenge	RAG + raw graph	262/300	87.33%	0.8596
Representative	RAG	156/200	78.00%	0.7753
Representative	RAG + raw graph	174/200	87.00%	0.8581

section-routed, raw POHA graphs (`rag_graph_raw`). We explicitly utilize raw graphs to isolate the baseline utility of symbolic context independently of the upstream repair loop. The evaluation corpus consists of 100 deterministically structured scenarios derived from the manual, divided into a frozen 60-scenario Challenge set (30 matched easy/hard pairs) and a 40-scenario Representative set. For each scenario, the agent evaluates the retrieved context to output an exact decision: `ALLOW`, `BLOCK`, or `CLARIFY`. By evaluating these highly curated cyber-physical scenarios over 1,000 total inference calls (100 scenarios $\times$ 5 trials $\times$ 2 arms), the dataset provides robust statistical power to resolve performance deltas via paired testing.

As detailed in Table 1, augmenting the RAG prompt with raw POHA graphs yielded a statistically significant improvement in exact decision accuracy across both evaluation sets. Accuracy and Macro-F1 are calculated using exact labels, with unsafe approvals strictly penalized. .

- **Challenge Set:** The baseline RAG agent achieved 77.33% accuracy. Graph augmentation increased exact accuracy to **87.33%**. A two-sided exact McNemar test on the paired discordant correctness confirmed high statistical significance ($p = 0.00231$). Challenge difficulty interaction was evaluated using deterministic bootstrapping, yielding $\Delta = 0.0667$ (95% CI: $[-0.0600, 0.1933]$); because zero lies inside the interval, no hard-case-specific benefit is formally established.
- **Representative Set:** Accuracy similarly increased from 78.00% to **87.00%**, with McNemar testing confirming robustness ($p = 0.01328$).

Crucially, neither arm predicted `ALLOW` on an expected `BLOCK` in the representative set. The largest quantitative gains for the graph-augmented agent occurred in multi-condition physical reasoning tasks, including sliding-door clearance (56% to 84%), boot-lid path conditions (76% to 100%), and numerical reserve thresholds (80% to 100%).

One example illustrating the decision-making process, including a full trace of this battery prohibition, is provided in **Appendix B**.

5.5 Qualitative Analysis: Grounding vs. False Rejection Rates (FRR)

To understand the mechanisms driving these quantitative results, we conducted a qualitative failure analysis of the discordant pairs.

The Benefit of Symbolic Grounding (Solving Constraint Blindness). Graphs fundamentally improved decision-making when the scenario depended on an explicit numerical threshold, conjunction, or missing physical observation. For example, in safety-critical rules (e.g., prohibiting the charging of a frozen 12-volt battery), the baseline RAG agent suffered from *implicit constraint blindness*. It treated a hard physical prohibition as general advice, inappropriately suggesting the user thaw the battery before charging. The graph context materialized this rule as a mandatory topological invariant (`freeze_history` $\implies$ `charging_allowed` = `False`), mathematically forcing the agent to output a hard `BLOCK`.

The Limitation of Formal Rigidity (Over-Constraining). Conversely, the primary source of graph-augmented errors stemmed from operational liveness degradation. When descriptive procedural advice (e.g., seating posture during a steering wheel adjustment) is compiled into a mandatory transition guard, the graph treats it as a strict authorization gate. While the text-only RAG agent correctly allowed routine adjustments, the graph-augmented agent became hyper-conservative, returning `CLARIFY` to demand confirmation of irrelevant posture facts before proceeding. This

over-constraining effect directly drives the False Rejection Rate (FRR) on permissive tasks - with an emergency call (eCall) failure case detailed extensively in **Appendix C**—and similarly explains why steering task accuracy declined from 100% to 80% under graph augmentation.

6 Discussion and Limitations

The central result of our investigation is that mathematical satisfiability is not a sufficient condition for automated model repair. Formally:

$$\mathrm{SAT}(\mathcal{H}') \not\Rightarrow \mathrm{Preserve}(\mathcal{H}, \mathcal{H}'), \qquad \mathrm{SAT}(\mathcal{H}') \not\Rightarrow \mathrm{Supported}(\mathcal{H}', M). \tag{8}$$

Changing a mathematical encoding changes the proposition being proved. If an LLM is permitted to freely mutate the graph to achieve `SAT`, the resulting automaton may no longer reflect the physical reality of the source text M. An independent, deterministic fidelity gate is strictly required to keep destructive, solver-gaming candidates from being accepted. While our downstream evaluations demonstrate a $\sim$10 % accuracy gain on safety-critical tasks, this formal rigidity introduces a distinct operational trade-off recognized in classical formal methods: the tension between Safety (preventing catastrophic actions) and Liveness (permitting valid operations). The strict topological enforcement occasionally over-constrains routine authorization queries. In these cases, the graph-augmented agent inappropriately demanded confirmation of every descriptive precondition before permitting a safe action. For example, in the steering adjustment scenario, the agent required explicit confirmation of the seating posture before allowing the adjustment, even though it was safe to proceed without it. A detailed qualitative breakdown of these failure modes is provided in **Appendix C**. It is critical to note that this over-constraining phenomenon does not invalidate the role of the Fidelity Gate. The gate operates exclusively during the upstream repair phase to prevent the LLM from secretly deleting rules to balance equations (solver gaming); its role is to ensure the graph remains mathematically faithful to the extracted text, regardless of whether that text was overly conservative. Another important consideration is that our exact-label scoring evaluates the final decision (`ALLOW`/`BLOCK`/`CLARIFY`) which may not be the only set of possibilities. While this study establishes the baseline efficacy of POHA graphs against unstructured text, isolating the marginal contributions of specific hybrid components—such as continuous guards versus discrete finite state machine (FSM) topologies—using intermediate structured baselines remains an area for future investigation. Additionally, benchmarking our pipeline against external CEGIS architectures and scaling evaluations to cross-domain corpora will be critical next steps to generalize these findings.

7 Conclusion and Future Work

Verifier-guided repair of generated formal models requires more than a satisfiable endpoint. In one of the examples of natural extraction failure, an unconstrained proposer-verifier loop satisfied the SMT solver only by silently deleting ten safety-critical obligations. Our proposed fidelity contract successfully detected every semantic downgrade, quarantined the destructive candidates, and retained the honest *unresolved* result. Our experiments confirmed that legitimate additive repairs can pass this strict gate, while solver-satisfying effect deletions are reliably rejected. Separately, providing raw POHA graph context improved average agentic decision accuracy over unstructured retrieval alone in different vehicle manual datasets (an absolute gain of $\sim$10 percentage points). However, the strict topological enforcement of the graphs occasionally over-constrained valid actions. Future work must focus on scaling this architecture from section-level subgraphs to global, manual-wide hybrid automata, as well as developing dynamic constraint relaxation mechanisms to balance formal safety with operational liveness.

Ethics Statement

This work concerns vehicle-safety guidance. The manuals used for experiments are general vehicle manuals and available publicly online. Generated graphs and decisions may be incomplete and should not be relied upon for direct vehicle control. We emphasize that our method is intended solely for scientific analysis only and we do not advocate direct vehicle control.

Reproducibility Statement

We have taken several measures to ensure the reproducibility of our work. The detailed experimental setting is provided in Section 4 and 5 of the main paper, and the Appendix includes comprehensive implementation details, such as use case examples and hyperparameters.

AI Use Statement

Generative AI tools were used for selecting the scenarios from different vehicle manuals used in experiment. This helped authors to avoid dull and uninteresting scenarios. They are then human reviewed to check if the generated scenarios accurately reflect the manual content. The architecture and research ideas is novel and Generative AI tools are not used to develop it. In the process of development of the pipeline, Generative AI tools were used for code generation and reviewing to meet the architectural requirements. In the process of drafting the paper, the text was reviewed and revised with Generative AI tools. The authors reviewed AI-assisted code and claims against tests and versioned artifacts. The authors take responsibility for the final paper and artifacts.

References

Rajeev Alur, Costas Courcoubetis, Nicolas Halbwachs, Thomas A. Henzinger, Pei-Hsin Ho, Xavier Nicollin, Alfredo Olivero, Joseph Sifakis, and Sergio Yovine. The algorithmic analysis of hybrid systems. *Theoretical Computer Science*, 138(1):3–34, 1995. doi: 10.1016/0304-0208(95)90020-9.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Heidy Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Miles Knight, Miles Brundage, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code. 2021.

Matthias Cosler, Christopher Hahn, Daniel Mendoza, Frederik Schmitt, and Caroline Trippel. nl2spec: Interactively translating unstructured natural language to temporal logics with large language models. In *Computer Aided Verification*, volume 13965 of *Lecture Notes in Computer Science*, pages 383–396. Springer, 2023. doi: 10.1007/978-3-031-37703-7_18.

Pierre Dantas, Lucas Cordeiro, Youcheng Sun, and Waldir Junior. The $4/\delta$ bound: Designing predictable llm-verifier systems for formal method guarantee. *arXiv preprint arXiv:2512.02080*, 2025. doi: 10.48550/arXiv.2512.02080.

Leonardo de Moura and Nikolaj Bjørner. Z3: An efficient SMT solver. In *Tools and Algorithms for the Construction and Analysis of Systems*, pages 337–340, 2008.

Chuyue Ding, Ying Sheng, Oded Padon, and Clark Barrett. Clover: Closed-loop verifiable code generation. In *AI Verification: First International Symposium, SAIV 2024, Montreal, QC, Canada, July 22–23, 2024, Proceedings*, volume 14846 of *Lecture Notes in Computer Science*, pages 134–155. Springer, 2024a. doi: 10.1007/978-3-031-65112-0_7.

Yan Ding, Xiaohan Zhang, Chris Paxton, and Shiqi Zhang. Task and motion planning with large language models for object rearrangement. In *2023 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 2086–2092. IEEE, 2023.

Yan Ding, Shiqi Zhang, Chris Paxton, and Jiacheng Wang. Neurosymbolic autoformalization: Guiding large language models with smt solvers for verifiable specifications. *IEEE Transactions on Automation Science and Engineering*, 21(4):1890–1902, 2024b.

Thomas A. Henzinger. The theory of hybrid automata. In *Proceedings of the 11th Annual IEEE Symposium on Logic in Computer Science*, pages 278–292. IEEE, 1996. doi: 10.1109/LICS.1996.561342.

Leslie Pack Kaelbling, Michael L. Littman, and Anthony R. Cassandra. Planning and acting in partially observable stochastic domains. *Artificial Intelligence*, 101(1–2):99–134, 1998.

Adrian Kaiser, Claudiu Leoveanu-Condrei, Ryan Gold, Marius-Constantin Dinu, and Markus Hofmarcher. Hydra: A hybrid-driven reasoning architecture for verifiable knowledge graphs. *arXiv preprint arXiv:2507.15917*, 2025. doi: 10.48550/arXiv.2507.15917.

Victoria Krakovna, Jonathan Uesato, Vladimir Mikulik, Matthew Rahtz, Tom Everitt, Ramana Kumar, Zac Kenton, Jan Leike, and Shane Legg. Specification gaming: the flip side of AI ingenuity. Google DeepMind Blog, 2020. URL `https://deepmind.google/blog/specification-gaming-the-flip-side-of-ai-ingenuity/`.

Claudiu Leoveanu-Condrei. A DbC inspired neurosymbolic layer for trustworthy agent design. *arXiv preprint arXiv:2508.03665*, 2025.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474, 2020a.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Kuttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, 2020b.

Jia Li, Ge Li, Yongmin Li, and Zhi Jin. Structured chain-of-thought prompting for code generation and specification extraction. *ACM Transactions on Software Engineering and Methodology (TOSEM)*, 34(2), 2025.

Bo Liu, Yuqian Jiang, Xiaohan Zhang, Qiang Liu, Shiqi Zhang, Joydeep Biswas, and Peter Stone. Llm+p: Empowering large language models with optimal planning proficiency. *arXiv preprint arXiv:2304.11477*, 2023. doi: 10.48550/arXiv.2304.11477.

Baptiste Rozière, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Romain Sauvestre, Tal Remez, Jérémy Rapin, Artyom Kozhevnikov, Ivan Evtimov, Joanna Bitton, Manish Bhatt, Cristian Canton Ferrer, Aaron Grattafiori, Wenhan Xiong, Alexandre Défossez, Jade Copet, Faisal Azhar, Hugo Touvron, Louis Martin, Nicolas Usunier, Thomas Scialom, and Gabriel Synnaeve. Code llama: Open foundation models for code. 2023.

Armando Solar-Lezama, Liviu Tancau, Rastislav Bodik, Sanjit Seshia, and Vijay Saraswat. Combinatorial sketching for finite programs. In *Proceedings of the 12th international conference on Architectural support for programming languages and operating systems (ASPLOS XII)*, pages 404–415, 2006. doi: 10.1145/1168857.1168907.

Maolin Sun, Xiaoning Zheng, Yu Zhang, and Meng Yang. Closed-loop specification generation: Leveraging smt solvers for feedback-driven llm refinement. In *Proceedings of the International Conference on Software Engineering (ICSE)*, pages 412–425. ACM, 2024.

Olivia Peiyu Wang, Sanna Wong-Toropainen, Daneshvar Amrollahi, Ryan Bai, Tashvi Bansal, Arush Garg, and Leilani H. Gilpin. Know your limits : On the faithfulness of llms as solvers and autoformalizers in legal reasoning. In *arXiv preprint arXiv:2606.16118*, 2026. URL `https://arxiv.org/abs/2606.16118`.

Appendix A: Detailed Experimental Setup

Data and Retrieval Protocol: Retrieval uses hybrid reciprocal-rank fusion with a BM25 weight of 0.30, a dense-retrieval weight of 0.70, and normalized `BAAI/bge-large-en-v1.5` vectors. Embeddings are stored in a local Qdrant instance, retrieving $k = 10$ chunks per query.

Model Configuration: Prompts, deployment configurations, and retrieved chunks were strictly fixed across all comparative arms using `gpt-5.4-2026-03-05` seeded with fixed random seeds and $T = 0.0$.

APPENDIX B: USE CASE - FROZEN 12-VOLT BATTERY PROHIBITION

This shows a use case where our neuro-symbolic architecture excels: the graph is most helpful when the decision depends on a hard safety invariant that is easy to miss or soften in a text-only answer. This use case is based on a text from an automotive manual which contain the safety warnings regarding the 12-volt battery states -

> "Never charge a 12-volt vehicle battery which is frozen or has been frozen. Discharged 12-volt vehicle batteries can even freeze at temperatures of approx. 0°C (+32°F). The 12-volt vehicle battery must be replaced if it has ever frozen."

B.1 POHA GRAPH DETAILS AND EXTRACTED CONSTRAINTS

A section-level POHA extracted for the battery policy encodes this as a decision-critical transition constraint on the `charging` action. The extraction yields the following structural elements:

- **States:** `battery_ok`, `battery_discharged`, `battery_frozen`, `battery_requires_replacement`
- **Variables:** `battery_temp_C`, `battery_charging_request`, `battery_is_frozen`, `freeze_history`, `charging_allowed`
- **Constants:** `freeze_threshold_C = 0`
- **Transition Guard:** `IF (battery_is_frozen == true OR freeze_history == true) THEN charging_allowed = false`
- **Effect:** `charging_action = BLOCK`, `maintenance_action = REPLACE_BATTERY`
- **Safety-Critical Flag:** `is_safety_critical = true`
- **Source Trace:** Page Details of the manual (like page 500), warning section, battery charging warning

The graph does not merely retrieve the sentence; it encodes the rule as a structural invariant. The charging action is blocked whenever the battery has been frozen, regardless of whether a user is asking for a "quick charge" or a "voltage-limited" procedure.

B.2 THE RECTIFIER VS. THE FIDELITY GATE

To understand why this formal structure survives the compilation process, we must highlight the architectural distinction between the **Rectifier** and the **Fidelity Gate**.

- **The Rectifier (LLM Proposer + SMT Verifier):** The goal of the rectifier loop is to achieve mathematical consistency (`SAT`). If a downstream constraint conflict occurs (e.g., the system must allow charging to prevent a total vehicle shutdown), the rectifier seeks the path of least resistance to balance the equations. An unconstrained LLM proposer might attempt to satisfy the solver by deleting the guard `battery_is_frozen == true` or by flipping the safety classification to `false`. The rectifier is "semantically blind"—it will accept this repair because it makes the model mathematically satisfiable, even though it silently violates the source text.
- **The Fidelity Gate:** The goal of the fidelity gate is to preserve physical engineering intent. It acts as an independent deterministic auditor. In this scenario, when the LLM proposes removing the frozen-battery guard or weakening the safety flag to achieve `SAT`, the fidelity gate intercepts the candidate.

The gate explicitly rejects such non-monotone edits because they violate the preservation contract:

- Protected guard removed or weakened.
- Safety-critical status downgraded.
- Source trace or evidence removed.
- Charging prohibition silently erased.

By quarantining the Rectifier's destructive proposal, the condition remains intact (`freeze_history => charging_allowed = false`). The fidelity gate therefore keeps the formal prohibition aligned with the manual, rather than allowing the solver to accept a semantically vacuous repair.

B.3 RAG-Only Answer from the Experiment

To evaluate the downstream impact of this preserved logic, we tested the scenario:

> "The 12-volt battery is frozen. Charge it now."

The expected ground-truth decision is `BLOCK`.

The experimental answer from the **RAG-only** arm was:

> CLARIFY — asks whether the battery is still frozen and suggests charging after thawing.

In this case, RAG doesn't enforce constraints; it blends semantics. So the system is uncertain even though the manual explicitly states the battery must not be charged when frozen or *previously* frozen. The model suffers from implicit constraint blindness, treating a direct, irreversible physical prohibition as if it were a soft, reversible availability question.

B.4 Graph Answer After Fidelity-Preserved Repair

With the graph context preserved through the repair-fidelity process, the **Graph-Augmented** agent answered correctly:

> BLOCK — a battery that is frozen or has been frozen must not be charged and requires replacement.

This matches the experimental results reported in our evaluation: the RAG-only arm answered `CLARIFY` in 2/5 trials, while the graph arm successfully answered `BLOCK` in 5/5 trials.

B.5 Why the Graph Changed the Answer

The difference in decision quality is not arbitrary. The graph adds the missing operational structure that pure RAG does not reliably preserve:

- Explicit battery state (`frozen`).
- Explicit prohibition on charging (`frozen || had_frozen`).
- Safety-critical action blocked by a formal invariant.
- Replacement required as the safe follow-up action.

Appendix C. Formal-Rigidity Over-Constraint Use case : manual emergency call (eCall) with green indicator

This shows a use case where formal rigidity in the graph representation can lead to over-constraining the decision-making process, even for a normally safe action like initiating an emergency call when the indicator is green. Consider the scenario where a user attempts to initiate a manual emergency call while the indicator is green.

> "Press and hold the emergency call button ... The emergency call is now initiated and a voice connection is established to the public emergency call centre. If you have accidentally pressed the emergency call button, cancel the emergency call immediately: Press the emergency call button again until the indicator lamp lights up green continuously."

C.1 Graph interpretation extracted into POHA

The graph extraction can encode the action as a safety-critical transition with guards such as:

- `ignition_on == true`
- `mobile_reception_known == true`
- `fault_lamp_red == false`
- `emergency_call_system_available == true`
- `indicator_state == green`

This is a valid formalization of a safe call path, but it may be too strict in practical decision contexts. Here the LLM extracts all the conditions from the manual and treats them as hard requirements for allowing the emergency call. When the model treats all of these as mandatory decision-critical conditions, it starts to ask for facts that are not required to decide a normal emergency action.

C.2 RAG-only answer

A natural RAG answer is:

> `ALLOW` — the indicator is green and the user is deliberately initiating a manual emergency call. The manual describes this as the normal emergency-call path.

This is the correct operational decision for a routine emergency-contact request.

C.3 Graph answer

The graph-augmented agent often overreacts by asking for additional confirmation before authorizing the call, for example:

> `CLARIFY` — confirm mobile reception, ignition state, and fault status before initiating the emergency call.

This answer is not entirely unreasonable from a graph perspective, but it converts a clearly allowed action into a multi-fact verification exercise. In practice, the user may already be in a normal, green-indicator state and the manual explicitly permits the manual call. This is exactly the form of formal rigidity that motivates the need for explicit fidelity checks, source-trace preservation, and careful routing of symbolic context. The goal is not to eliminate formal constraints; it is to keep them from suppressing valid operational actions when the source text does not truly require such a strict gate.

Appendix D: Adversarial Ontology Repair Probe

D.1 The Adversarial Setup: Conflicting Constraints

In this adversarial ontology test, we evaluate a safety protocol concerning the deployment of the passenger airbag when a child seat is detected.

- **Source Text Rule:** *"If the passenger seat weight sensor detects less than 15kg, the passenger airbag MUST be deactivated. This is a critical safety hazard."*
- **Injected Defect:** To test the repair loop under a worst-case condition, we artificially inject a contradictory temporal bound and an impossible topological guard into the initial POHA. In particular, we force the deactivation guard to require both

$$\texttt{vehicle_speed > 0} \quad \text{and} \quad \texttt{vehicle_speed == 0} \tag{9}$$

simultaneously. This creates a logically impossible condition on a safety-critical transition.

The purpose of this probe is not to model a realistic manufacturer specification, but to stress the repair engine with a controlled contradiction that is intentionally impossible to satisfy. The adversarial setup isolates a core failure mode: the model is forced to choose between preserving the source safety rule and satisfying the solver by deleting or weakening the underlying semantic constraint.

D.2 The SMT Verifier Result

When the corrupted graph is compiled and passed to the SMT solver, the solver correctly detects the contradiction.

- **Z3 Output:** `UNSAT`
- **Unsatisfiable Core:** The contradictory guard on the passenger-airbag deactivation transition is identified as the direct source of inconsistency.

This is the expected behavior: an unsatisfiable graph should remain unsatisfiable when the underlying model encodes a logically impossible state condition. The key question is how the correction loop responds to that failure.

D.3 The Unconstrained LLM Proposer Response (Solver Gaming)

The `UNSAT` result and the supporting source text are returned to the LLM proposer. The mathematically honest repair is to rewrite the transition guard so that it matches the manual specification, namely:

$$\texttt{seat_weight < 15kg} \Rightarrow \texttt{airbag_deactivated}. \tag{10}$$

However, because the proposer is unconstrained and is effectively optimizing for a satisfiable solver outcome, it seeks the path of least resistance. The repair candidate Δ resolves the contradiction by deleting the conflicting semantics rather than restoring the correct safety condition.

Specifically, the repaired graph does the following:

1. It deletes the `airbag_deactivation` transition altogether to eliminate the contradictory guard.
2. It downgrades the protected state flag from `is_safety_critical = True` to `False`.
3. It preserves the rest of the graph structure so that the SMT solver can now compile the candidate without the impossible condition.

If this repair were accepted, the resulting graph would compile cleanly and produce a satisfiable model (`SAT`). However, the critical safety rule protecting the child-seat scenario would have been silently erased from the formal model. The repaired graph would be mathematically consistent but semantically incorrect.

D.4 The Fidelity Gate Quarantine

Our architecture does not allow this candidate to proceed to reverification. Before acceptance, the candidate repair is routed through the independent fidelity gate. The deterministic maximum-weight bipartite matching routine aligns the proposed graph against the original graph and detects two severe violations of the bounded repair contract.

1. **Violation 1 (Topology):** A transition present in the original graph and supported by the trace τ has been deleted.
2. **Violation 2 (Ontology / Safety Semantics):** The protected state flag `is_safety_critical` was non-monotonically downgraded from `True` to `False`.

Because the fidelity gate evaluates to `False`, the repair is immediately quarantined and the system returns an `unresolved` outcome. In other words, the graph is prevented from accepting a mathematically valid but semantically destructive repair.

D.5 Conclusion of the Probe

This adversarial setup demonstrates the precise failure mode addressed by the benchmark. The LLM is cornered by an impossible mathematical condition, and rather than repairing the guard to match the source text, it removes the protected transition and weakens the safety-critical state to restore solver satisfiability. This is exactly the kind of solver gaming that the controlled ontology suite is designed to expose.

The key result is not merely that the candidate becomes SAT, but that the independent fidelity gate rejects it. The probe therefore illustrates the necessity of semantic preservation: without the gate, the repair loop can produce a formally consistent graph that is physically unsafe and semantically unfaithful to the source specification.