SAME TASK, DIFFERENT ANSWER: PERSONA CONDITIONING MODULATES SHARED TASK MECHANISMS IN LANGUAGE MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Persona conditioning can change a language model's behavior on a task even when the task itself is held fixed, but it remains unclear whether these changes arise from persona-specific mechanisms or from modulation of ordinary task computation. We investigate this question across three instruction-tuned language models, five tasks, and four persona axes. Applying complementary damage and repair path patching to persona-conditioned correct–wrong transitions, we identify attention-head circuits and decompose each into a component shared across axes (K) and an axis-dependent remainder (R). Circuits discovered in opposite causal directions converge preferentially on K, and faithfulness, knockout, direct logit attribution, probing, and no-persona validation consistently implicate K in task-related computation. Moreover, the bidirectional intersections retain strong task-functional signatures and much of the intervention effect while using substantially fewer heads. As an independent validation, in Qwen-7B SST-2 every persona-derived shared head falls within a separately discovered no-persona task circuit, whereas the remainder heads show much lower containment. The same structure is also behaviorally actionable: a signed K/R intervention selectively improves persona-sensitive accuracy while preserving more than 99% of originally correct outputs. However, how strongly persona information couples to this shared computation depends on the task: the behaviorally stable ARC tasks show greater separation between task and persona information, whereas ETHICS, Safety, and SST-2 show stronger coupling within K. Overall, these results show that persona-conditioned behavior can emerge from modulation of shared task-related mechanisms, not only from isolated persona-specific circuitry.

1 INTRODUCTION

Language models are increasingly used with contextual information about the user, including demographic (Neplenbroek et al., 2025; Tan et al., 2026; Yang et al., 2026), affective (Hou et al., 2025), and social attributes (Farhansyah et al., 2025; Castricato et al., 2025). Persona conditioning can alter reasoning (Poonia & Jain, 2025), judgements (Liu et al., 2025a), and generated responses (Joshi et al., 2024), including socially sensitive behavior and identity-consistent decisions. Recent evaluations further show that LLM behavior can be sensitive to prompt-level variations that are orthogonal to the underlying task, with substantial changes in both task performance and measured social bias (Hida et al., 2025). These effects suggest that persona information is not merely a surface-level modifier of generation, but can interact with the computation underlying task behavior.

Such effects are not necessarily undesirable (Liu et al., 2025b), as persona information can be intentionally used to personalize model behavior toward a particular perspective (Luz de Araujo & Roth, 2025), preference (Zhang et al., 2025), or values (Castricato et al., 2025). However, the same flexibility becomes problematic when irrelevant persona attributes alter the solution to a task whose ground-truth answer is independent of those attributes. Recent studies have documented identity-congruent reasoning shifts (Dash et al., 2026), while other work shows that demographic biases can persist under prompt-based adaptation (Sivakumar et al., 2025), indicating that persona information can systematically interfere with model behavior even when it is not required for solving the underlying problem.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

Behavioral evaluation alone cannot reveal which internal computation produces a persona-induced change (Mueller et al., 2026). Such shifts may reflect persona-specific mechanisms, modulation of task computation (Merullo et al., 2024), downstream answer construction (Stolfo et al., 2023), or interactions among multiple pathways (Cheng et al., 2025). Mechanistic studies further show that distinct behaviors can reuse shared circuits (Lan et al., 2024; Teplica et al., 2025), while sparse causal components can support task computation (Kim et al., 2025a). This motivates causal analysis of the mechanisms underlying persona-conditioned changes.

We study persona effects through matched correct–wrong transitions in which only the persona changes while the task input and gold answer remain fixed. This creates a bidirectional causal contrast over the same target computation using path patching (Goldowsky-Dill et al., 2023): *Original* identifies wrong-run states that can disrupt correct computation, whereas *Reverse* identifies correct-run states that can repair the corresponding wrong computation. Unlike reversing a task counterfactual, where task content and often the target label also change, these directions reverse the model's correctness state for the same task instance. Their agreement allows us to identify stable structure rather than direction-specific effects. We then decompose the discovered circuits into components shared across persona axes and axis-dependent remainders, and test their causal roles through signed activation intervention, ablation, direct logit attribution, and held-out probes. Across three instruction-tuned LLMs, five tasks, and four persona axes, we characterize behavioral sensitivity and investigate the mechanisms underlying reliable correct–wrong transitions.

Research questions. We organize the study around five research questions:
RQ1: How does persona conditioning affect task behavior across models, tasks, and persona axes?
RQ2: Can circuits discovered from persona-sensitive correct/wrong transitions support selective repair while preserving correct behavior?
RQ3: Do opposite damage and repair causal contrasts converge on shared computational structure, and can their intersection provide a compact intervention target?
RQ4: What functional roles do the shared and remainder components play in task computation and persona influence, and how do these roles vary across tasks?
RQ5: Does persona-derived shared structure remain task-functional without persona context and align with independently discovered task circuitry?

Contributions. Our results support four main contributions:

- We introduce a bidirectional causal framework for matched persona-conditioned correct–wrong transitions, where the task input and target remain fixed while the model's correctness state changes. This enables complementary damage-and-repair path-patching contrasts over the same task computation, followed by cross-axis decomposition into shared (K) and axis-dependent remainder (R) components.
- We show that the discovered structure supports selective intervention and recurs across opposite causal contrasts. A signed Original K/R intervention improves persona-sensitive accuracy while largely preserving originally correct outputs, while Original–Reverse overlap is consistently concentrated in K rather than R; their intersection provides substantially more compact intervention targets while retaining much of the behavioral effect.
- We establish a functional distinction between the shared and remainder components. Shared heads show stronger faithfulness, knockout, and task-directed output effects, while held-out probes reveal task-dependent organization: ARC shows greater separation of task and persona information across K and R, whereas ETHICS, Safety, and SST-2 show stronger persona coupling within K, a pattern further supported by QK/value decomposition.
- We show that persona-derived shared structure remains task-functional without persona context. Shared sets outperform matched random controls in no-persona faithfulness and knockout tests; in Qwen-7B SST-2, all persona-derived shared heads are contained within an independently discovered task circuit, whereas the axis-dependent remainders show substantially weaker alignment.

2 Related Work

Persona conditioning and bias mechanisms. Persona prompting can alter language-model behavior across toxicity and social bias, task performance, personalization, and safety (Deshpande et al., 2023; Gupta et al., 2024; Beck et al., 2024; Li et al., 2024; Plaza-del Arco et al., 2025). Controlled benchmarks such as StereoSet and BBQ further show that socially sensitive behavior depends on

contextual framing (Nadeem et al., 2021; Parrish et al., 2022), while bias and fairness measurements remain task-dependent (Gallegos et al., 2024). Mechanistic studies have localized bias-related behavior to internal components (Vig et al., 2020; Ahsan et al., 2025; Kim et al., 2025b; Yu et al., 2026), and Poonia and Jain study persona-driven reasoning using activation patching (Poonia & Jain, 2025). However, such components can also affect task behavior (Bashir et al., 2025). We therefore test whether components discovered from persona-conditioned changes also participate in ordinary task computation.

Circuit discovery, stability, and shared computation. Mechanistic interpretability has localized model behavior to sparse circuits of attention heads, neurons, or edges (Wang et al., 2023; Conmy et al., 2023; Syed et al., 2024; Hsu et al., 2024; Nur'aini et al., 2026). Subsequent work examines circuit stability and task-mechanism generalization across inputs and contexts (Sun, 2025; Kim et al., 2025a; Todd et al., 2024; Nainani et al., 2024), while distinct behaviors can reuse shared components (Merullo et al., 2024; Lan et al., 2024; Teplica et al., 2025). Most analyses nevertheless derive circuits from a single causal contrast or behavioral target (Mondorf et al., 2025). We instead compare opposite damage and repair contrasts and distinguish structural recurrence from functional importance using faithfulness, knockout, DLA, probing, and no-persona validation.

Representation intervention and activation steering. Representation engineering and activation-steering methods manipulate internal activations or localized components to alter model behavior without globally updating the model (Zou et al., 2023; Turner et al., 2024; Li et al., 2023; Rimsky et al., 2024; Nur'aini et al., 2026). Recent approaches further support targeted or adaptive interventions (Stoehr et al., 2024; Li et al., 2025; Jiang et al., 2025). These directions are typically derived from behavioral contrasts or optimization objectives rather than causally identified task-related circuits. Our intervention instead targets discovered attention heads, assigns distinct signed roles to shared and remainder components, and tests specificity with matched-random and swapped-role controls.

3 Experimental and Causal Framework

3.1 Model, Task, and Persona Axes

Llama-3.2-3B-Instruct, Llama-3.1-8B-Instruct (Dubey et al., 2024; Meta AI, 2024), and Qwen2.5-7B-Instruct (Yang et al., 2024) are evaluated on five restricted-output tasks: ARC-Easy and ARC-Challenge for multiple-choice science reasoning (Clark et al., 2018), ETHICS for ethical acceptability classification (Hendrycks et al., 2021), a binary safety classification task constructed from Databricks Dolly 15K (Conover et al., 2023) and Do-Not-Answer (Wang et al., 2024), and SST-2 for sentiment classification (Wang et al., 2018). Meaningful no-persona capability is verified for every model–task combination before persona-conditioned analysis.

The study covers 19 persona values across four axes: emotion, gender, race, and religion. Emotion uses four opposite-style pairs motivated by Plutchik's framework (Plutchik, 1980), with both ordered directions evaluated; gender, race, and religion use all pairwise ordered directions.

Persona conditioning is introduced as a standardized statement in the user prompt, followed by the task instruction and input. Unlike persona-assignment setups that instruct the model to adopt a persona through the system prompt (Gupta et al., 2024), we model persona information disclosed by the user, which has been found to affect model outputs more strongly than equivalent system-prompt cues (Weeber et al., 2026). Within each comparison, only the persona value changes, while task content, instruction, and output format remain fixed. Across three models, five tasks, and four persona axes, this yields 60 model–task–axis settings; the validation scan contains 23,907 no-persona and 411,597 persona-conditioned evaluations. Task labels, baseline accuracies, persona values, prompt templates, and sampling rules are given in Appendix A.

3.2 Counterfactual construction, evaluation subsets, and reliability

Each task item is evaluated under the no-persona condition, and all persona values and the resulting predictions are used to construct the circuit-discovery data and intervention-evaluation subsets in Table 1. The primary intervention analysis requires $n_B \geq 25$; this threshold is specific to that analysis and is not applied universally to the functional experiments.

For circuit discovery, each ordered persona direction contributes at most 20 examples before redistribution, with task labels balanced where possible. The target budget for an axis is $N_{\text{target}} = \min(N_{\text{available}}, \max(100, 20N_{\text{directions}}))$. We redistribute unused capacity from sparse directions to axes with additional examples, while low-support settings retain all available pairs. Exact sampling rules and per-task/axis budgets are reported in Appendix A.4.

Table 1: Construction of circuit-discovery and intervention-evaluation data.

Data	Split	Construction/definition	Purpose
Counterfactual pairs	Train	Persona-conditioned correct–wrong pairs	Path-patching circuit discovery
B: Persona-sensitive	Dev	$\exists\, p_i, p_j \in P : c(x, p_i) = 1,\ c(x, p_j) = 0$	Primary repair target
U: All-correct	Dev	$\forall\, p \in P :\ c(x, p) = 1$	Preservation control
W: All-wrong	Dev	$\forall\, p \in P :\ c(x, p) = 0$	Capability sanity check

3.3 Bidirectional Persona-Sensitive Circuit Discovery

We measure patching effects using the probability margin between the gold answer and the strongest incorrect answer, $M = p(y^\star) - \max_{y \neq y^\star} p(y)$. We use two complementary causal directions. In *Original* discovery, we insert the wrong-run activation into the correct-output run,

$$E_O(h) = M_{\text{correct}} - M_{\text{patched}(z_h^{\text{wrong}} \to z_h^{\text{correct}})}. \tag{1}$$

Large positive scores identify heads for which inserting the wrong-run activation damages the correct-answer computation. In *Reverse* discovery, we instead insert the correct-run activation into the wrong-output run,

$$E_{\text{Rev}}(h) = M_{\text{wrong}} - M_{\text{patched}(z_h^{\text{correct}} \to z_h^{\text{wrong}})}. \tag{2}$$

Strongly negative scores identify heads for which inserting the correct-run activation repairs the wrong-output computation. Importantly, Reverse discovery reverses the *correctness state* of the same target computation, not merely the orientation of a task counterfactual. In task counterfactuals such as sentiment polarity flips, the input content and gold label change together, so reversing the patch exchanges two valid task states rather than forming a matched damage–repair contrast. In our persona-conditioned pairs, the task input, instruction, and gold answer remain fixed while only the persona changes, yielding correct and wrong executions of the same task instance. Original therefore tests whether a wrong-run state damages that computation, whereas Reverse tests whether the corresponding correct-run state repairs it.




Figure 1: **Bidirectional persona-conditioned circuit discovery and structural decomposition. (A)** Original and Reverse discovery use opposite patching directions. **(B)** Discovered circuits are decomposed into shared (K) and remainder (R) components and compared through I and KK.

In both directions, we patch attention-head z activations at the decision position and iteratively select the top heads at each stage: the largest positive effects for Original and the most negative effects for Reverse. The final circuit is the union across stages. Thus, Original identifies wrong-run states whose insertion damages correct computation, whereas Reverse identifies correct-run states whose insertion repairs wrong computation. Figure 1 summarizes the discovery procedure and the subsequent structural decomposition.

For task t and persona axis a, let $C_O(t,a)$ and $C_{\mathrm{Rev}}(t,a)$ denote the Original and Reverse circuits. We define their cross-axis shared K and remainder R components as

$$K_D(t) = \bigcap_a C_D(t,a), \qquad R_D(t,a) = C_D(t,a) \setminus K_D(t), \qquad D \in \{O, \mathrm{Rev}\}. \tag{3}$$

Here, K and R are structural labels denoting cross-axis shared and remainder heads, respectively; their functional roles are tested empirically. For bidirectional comparison, we additionally define the full-circuit intersection and the intersection of the cross-axis shared components as

$$I(t,a) = C_O(t,a) \cap C_{\mathrm{Rev}}(t,a), \qquad KK(t) = K_O(t) \cap K_{\mathrm{Rev}}(t). \tag{4}$$

3.4 Signed K/R Intervention

We construct no-persona and persona activation references independently from held-out evaluation examples. For a remainder head $h \in R$, the intervention interpolates or extrapolates relative to the no-persona mean μ_h^{np}:

$$z'_h = (1-\alpha) z_h + \alpha \mu_h^{np}. \tag{5}$$

For a shared head $h \in K$ and persona mean μ_h^{p}, we define

$$d_h = \mu_h^{np} - \mu_h^{p}, \qquad z'_h = z_h + \beta d_h. \tag{6}$$

Heads outside the selected circuit are unchanged. Both α and β are signed, allowing the intervention to interpolate or extrapolate rather than assuming a single beneficial direction. The selected grid point maximizes a weighted repair–preservation objective described in Appendix B. Controls include random heads, layer-matched random heads, and swapped K/R intervention roles.

3.5 Functional validation

For causal validation, we measure *accuracy-based faithfulness* by retaining only the candidate heads while mean-ablating the remainder, and *accuracy-based knockout* by mean-ablating the candidate heads while leaving other heads active. We report Faithfulness as $Acc_{\mathrm{keep}}/Acc_{\mathrm{full}}$ and KO ratio as $Acc_{\mathrm{KO}}/Acc_{\mathrm{full}}$; higher Faithfulness and lower KO ratio indicate a stronger causal signature.

We use direct logit attribution (DLA) (Wang et al., 2023) to measure how strongly each head group writes toward the correct task answer. We additionally train held-out logistic-regression probes on head activations for task answer, persona presence, persona value, and correct-vs-wrong persona condition. Finally, we decompose persona-conditioned head-output changes into attention-routing and value-content contributions at the decision position, allowing us to examine how persona information interacts with the shared and remainder components. Margin-based variants and decomposition details are given in Appendices A.6 and F.1.

4 From Persona-Conditioned Behavior to Shared Circuit Structure

4.1 Persona Sensitivity is Systematic but Highly Task Dependent

Persona-conditioned correctness changes are summarized using Net Benefit (NB), where positive values indicate more helpful than harmful changes. Behavior varies substantially across tasks and models: ARC-Easy and ARC-Challenge are the most stable, while ETHICS, Safety, and SST-2 show greater persona sensitivity. Net Benefit is near zero for ARC and ETHICS on average but becomes negative for Safety and especially SST-2 (Figure 2); Llama-8B is generally more stable, whereas Qwen-7B shows the broadest variation.

Model-stratified generalized estimating equations (GEE) (Liang & Zeger, 1986) confirm that significant persona effects are concentrated primarily in ETHICS, Safety, and SST-2, with fewer effects in ARC and stronger concentration in Qwen-7B than Llama-8B. Behavioral definitions, per-setting statistics, and Benjamini–Hochberg-adjusted (Benjamini & Hochberg, 1995) GEE results are reported in Appendix C.




Figure 2: **Persona-conditioned behavior varies across tasks and models.** Net Benefit, $P(\text{Help}) - P(\text{Hurt})$, across model–task–axis settings. Colors saturate at ± 10 pp; numbers give exact values.

Directional label shifts. Selected conditions show strongly directional persona-induced changes. For Qwen-7B on Safety, over 95% of changed predictions under *fearful* shift from `safe` to `unsafe`; on SST-2, every change under *angry* shifts from `positive` to `negative`. For example, *"a good piece of work more often than not."* changes from `positive` without a persona to `negative` under *angry*. Llama-8B shows the opposite tendency on ETHICS, where over 95% of changes under *joyful* and *Female* shift from `unacceptable` to `acceptable`. Full statistics and examples are provided in Appendix C.2.

4.2 Original-Circuit Intervention Selectively Repairs Persona-Sensitive Behavior

Across 33 reliable settings ($n_B \geq 25$), the signed Original-circuit K/R intervention improves persona-sensitive behavior while largely preserving previously correct outputs; paired McNemar tests (McNemar, 1947) are significant in 29/33 settings ($p < .05$; Appendix E.1). Figure 3b summarizes stricter sample-state outcomes, including repair, remaining sensitivity, collapse, and preservation.




Figure 3: **Original-circuit intervention across 33 reliable settings.** (a) Matched-coefficient controls for persona-sensitive accuracy and preservation; random controls show mean ± SD over 10 head sets. (b) Sample-state outcomes for persona-sensitive and all-correct examples.

Matched random-any and layer-matched controls, evaluated with the same setting-specific α, β selected for the canonical Original K/R intervention, yield much smaller gains, while swapping the roles of K and R is harmful (Figure 3a; Appendix E.3). This indicates that the effect depends on both head selection and the distinct intervention roles of the shared and remainder components. Selected coefficients for every setting and an all-wrong capability check are reported in Appendices E.2 and E.1.

4.3 Original and Reverse Converge on a Compact Shared Core

Original and Reverse circuit discovery pose complementary causal questions over the same fixed task instance: Original asks which wrong-run activations damage correct computation, whereas Reverse asks which correct-run activations repair wrong computation. Matched circuits are recovered for every analyzed setting. Figure 4 reports Jaccard overlap for the full circuit, K, and R, averaged

over the 20 model–task–axis settings per model; $K{>}R$ counts settings in which shared-component overlap exceeds remainder overlap.

Shared-component overlap exceeds remainder overlap in every matched setting. Mean Jaccard similarity is .701 for K and .099 for R. Thus, opposite damage and repair contrasts preferentially recover the same cross-axis shared structure, whereas the remainder is much less stable across discovery direction. This establishes structural recurrence rather than task function, which is tested in Section 5.

The same bidirectional agreement is behaviorally actionable. The full Original–Reverse intersection $I(t, a)$ uses only 20.2 heads on average, compared with 43.7 for Original and 39.9 for Reverse, while retaining roughly 29% repair and 99% preservation of originally all-correct states. Thus, bidirectional agreement provides a substantially more compact intervention target while retaining substantial behavioral effect. Detailed results are reported in Appendices D and E.4.




Figure 4: **Original–Reverse structural overlap by model.** Jaccard overlap for the full circuit, the shared component K, and the remainder R.

5 Functional Organization of Shared and Remainder Components

5.1 K behaves as a task-related causal core

Table 2 shows a clear separation between shared and remainder components. Original and Reverse K retain nearly full-circuit faithfulness with about one-third as many heads, while their knockout effects are substantially stronger than those of the corresponding remainders, whose removal has little effect on accuracy. Thus, K concentrates much of the task-relevant computation recovered by each circuit without accounting for the full circuit.

The bidirectional intersection $O \cap \mathrm{Rev}$ shows a similarly strong causal signature, while the more compact KK retains high faithfulness with a weaker knockout effect. We therefore interpret K and KK as compact shared task-related cores rather than exhaustive accounts of their broader circuits. Complementary margin-based results are reported in Appendix A.6.

Table 2: **Accuracy-based causal validation across the complete analysis.** Values are means across settings. Higher Faithfulness and lower KO ratio indicate a stronger causal signature.

Group	Heads	Faith. ↑	KO ratio ↓
Original	39.7	.981	.679
Original K	13.2	.976	.795
Original R	26.5	.728	.997
Reverse	38.9	.982	.661
Reverse K	12.3	.979	.800
Reverse R	26.6	.743	.996
$O \cap \mathrm{Rev}$	18.3	.978	.703
KK	10.7	.969	.841

5.2 Persona Help and Hurt track changes in K's task-directed output

Table 3 reports mean persona-minus-no-persona changes in task-directed DLA at the decision position. For Original K, Reverse K, and KK, Help examples shift output toward the correct answer whereas Hurt examples shift it away, with near-perfect sign consistency across applicable settings; the corresponding remainder effects are much smaller.

This pattern is consistent across task families rather than being driven by a single task, while StableCorrect and StableWrong examples show little change. Together with the causal results above, the DLA analysis indicates that persona conditioning modulates how shared task-related heads write toward the task answer in a direction that tracks whether correctness improves or degrades. Rather than appearing as diffuse output shifts, these changes are concentrated more strongly in the shared task-related component than in the axis-dependent remainder.

Table 3: **Task-directed DLA by circuit component.**

	Original K	Original R	Reverse K	Reverse R	KK
Help	+.153	+.023	+.169	+.029	+.148
Hurt	−.219	−.036	−.230	−.044	−.184

5.3 Functional organization differs across tasks

Held-out probes reveal that the discovered circuits do not follow a universal K = task, R = persona decomposition. Task-answer information is consistently more decodable from K, but persona-value organization differs by task: ARC shows stronger task-answer decoding from K and relatively stronger persona-value decoding from R, whereas ETHICS, Safety, and SST-2 show stronger co-location of both signals within K (Figure 5). This task-dependent organization is consistent with the greater behavioral stability of ARC relative to the more persona-sensitive tasks (Figure 2; Appendix C.4).




Figure 5: **Task-dependent probe organization.** Cells show $BA_K - BA_R$ for task-answer and persona-value probes; positive values favor K and negative values favor R.

QK/value analysis. A complementary decomposition into persona-dependent attention routing and value content supports the same task-dependent pattern. Content and routing effects are generally stronger in R than in K, but the separation is strongest for ARC and substantially weaker for Safety and SST-2, where effects within K approach those in R. This pattern largely holds under both discovery directions and is consistent with task-dependent variation in how strongly persona-related computation couples to the shared task-related component. Full results are reported in Appendix F.1.

6 Does Persona-Conditioned Discovery Recover Ordinary Task Computation?

6.1 No-persona faithfulness and knockout score

We test shared heads recovered from persona-conditioned circuits for task function after removing persona context. K_O, K_{Rev}, KK, and the full Original–Reverse intersection are evaluated using the same accuracy-based Faithfulness and KO ratio metrics, with deterministic size- and layer-matched random controls.

Table 4: **No-persona causal validation.** C/R denotes candidate/matched-random results.

Set	Heads	Faith. C/R ↑	KO C/R ↓
K_O	13.2	.979/.615	.810/1.003
K_{Rev}	12.3	.977/.587	.834/1.000
KK	10.7	.965/.639	.868/.999
$O \cap \text{Rev}$	18.3	.980/.578	.733/.999

As shown in Table 4, all shared sets retain substantially more ordinary task performance than matched random controls and produce larger knockout effects. This shows that structure recovered from persona-conditioned transitions remains task-relevant even without persona context. K_O, K_{Rev}, and KK contribute 15 model–task evaluations each, while $O \cap \text{Rev}$ contributes 60 model–task–axis evaluations.

6.2 Independent no-persona SST-2 task-circuit validation

As an independent validation, a 32-head SST-2 circuit is discovered directly from no-persona behavior in Qwen2.5-7B-Instruct and verified for task function on the full validation set, with counterfactual construction and circuit-discovery details provided in Appendix A.5. All persona-derived shared heads in this setting are contained within the independently discovered task circuit, whereas remainder containment is substantially lower, further supporting the task-related interpretation of K.

Functionally, K_O nearly matches the task-only circuit despite being substantially smaller, while K_{Rev} and KK retain high faithfulness with weaker knockout effects. In contrast, the remainders show faithfulness closer to the random baseline and only weak knockout effects. These results show that persona-derived shared structure aligns substantially more strongly with ordinary SST-2 computation than the axis-dependent remainder. This independent validation currently covers Qwen-7B SST-2, with broader model replication left for future robustness analysis.

Table 5: **Independent Qwen-7B SST-2 task-circuit validation.** Containment is relative to the 32-head no-persona circuit.

Set	Heads	In task	Cont.	Faith. ↑	KO ↓
Task-only	32	32	100%	1.010	.525
Random	32	–	–	.525	.996
K_O	13	13	100%	1.007	.531
K_{Rev}	10	10	100%	.993	.835
KK	10	10	100%	.993	.835
R_O (mean)	35.0	3.5	10.0%	.525	.997
R_{Rev} (mean)	26.0	4.5	17.6%	.612	.991

7 Limitations

Our study covers three instruction-tuned models, five restricted-output tasks, four explicit persona axes, and attention-head z activations at the decision position; the findings may not generalize directly to open-ended generation, implicit or intersectional personas, other architectures, token positions, or mechanisms outside attention heads. Circuit recovery depends on correct–wrong counterfactuals and can be less stable in low-support settings, while faithfulness and knockout depend on the chosen mean-ablation protocol. Intervention coefficients are selected separately for each setting rather than tested for transfer, and independent task-only validation currently covers only Qwen-7B SST-2. Finally, probe and QK/value results characterize representational organization but do not establish a unique causal pathway or that task–persona segregation causes behavioral robustness.

8 Discussion and Conclusion

Our results argue against a purely persona-specific interpretation of circuits discovered from persona-conditioned behavior. Opposite damage and repair contrasts converge preferentially on the cross-axis shared component K, which also shows stronger faithfulness, knockout, and task-directed DLA than the axis-dependent remainder. These shared heads remain task-functional when persona context is removed and, in the independent Qwen-7B SST-2 analysis, are fully contained within a separately discovered task circuit. Thus, the causal contrast used to discover a circuit does not necessarily determine its function: persona-conditioned transitions can expose components of ordinary task computation.

Bidirectional recurrence strengthens this interpretation but does not determine function by itself. Its significance comes from agreement with the causal and functional analyses: recurrent shared heads retain task performance when isolated, affect performance when knocked out, and shift task-directed output consistently with persona-induced Help and Hurt. This supports using agreement across complementary causal contrasts as a way to identify candidate structure whose function can then be tested independently.

The resulting organization is nevertheless task-dependent rather than a universal $K = \mathrm{task}$, $R = \mathrm{persona}$ decomposition. ARC shows greater separation of task and persona information across K and R, whereas ETHICS, Safety, and SST-2 show stronger persona coupling within K; the QK/value analysis supports the same graded distinction. This suggests that persona sensitivity may depend partly on how persona-related computation interacts with task-related mechanisms, although the present results do not establish that this organization itself causes behavioral robustness.

Finally, the discovered structure is behaviorally actionable. Signed K/R intervention improves persona-sensitive accuracy while preserving over 99% of originally correct outputs, while matched random controls yield much smaller gains and swapping the roles of K and R is harmful. Bidirectional intersections retain much of the intervention effect with substantially fewer heads. Because the selected coefficients vary across settings, however, these results support circuit-guided controllability rather than a universal steering direction or intervention strength. Overall, persona context can alter shared task-related computation rather than operating only through isolated persona-specific mechanisms, motivating functional validation beyond the contrast used for circuit discovery.

AI USE STATEMENT

Generative AI tools assisted with language editing, wording refinement, code drafting, and manuscript organization. All experimental design decisions, analyses, statistical tests, figures, tables, and scientific claims were determined and verified by the authors. AI-assisted code and text were reviewed and checked by the authors before inclusion. The authors take full responsibility for the final content of the paper.

REPRODUCIBILITY STATEMENT

The paper provides the model, task, persona, sampling, circuit-discovery, intervention, and functional-validation procedures required to reproduce the reported experiments. Additional implementation details, evaluation definitions, intervention hyperparameters, counterfactual sampling rules, and complete per-setting results are provided in the appendices. Code and processed experimental outputs will be released upon publication.

REFERENCES

Hiba Ahsan, Arnab Sen Sharma, Silvio Amir, David Bau, and Byron C Wallace. Elucidating mechanisms of demographic bias in LLMs for healthcare. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 14614–14631, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-335-7. doi: 10.18653/v1/2025.findings-emnlp.789. URL https://aclanthology.org/2025.findings-emnlp.789/.

Zubair Bashir, Bhavik Chandna, and Procheta Sen. Dissecting bias in LLMs: A mechanistic interpretability perspective. *Transactions on Machine Learning Research*, 2025. ISSN 2835-8856. URL https://openreview.net/forum?id=EpQ2CBJTjD.

Tilman Beck, Hendrik Schuff, Anne Lauscher, and Iryna Gurevych. Sensitivity, performance, robustness: Deconstructing the effect of sociodemographic prompting. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2589–2615. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.eacl-long.159. URL https://aclanthology.org/2024.eacl-long.159/.

Yoav Benjamini and Yosef Hochberg. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300, 1995. doi: 10.1111/j.2517-6161.1995.tb02031.x. URL https://www.jstor.org/stable/2346101.

Louis Castricato, Nathan Lile, Rafael Rafailov, Jan-Philipp Fränken, and Chelsea Finn. PERSONA: A reproducible testbed for pluralistic alignment. In Owen Rambow, Leo Wanner, Marianna Apidianaki, Hend Al-Khalifa, Barbara Di Eugenio, and Steven Schockaert (eds.), *Proceedings of the 31st International Conference on Computational Linguistics*, pp. 11348–11368, Abu Dhabi, UAE, January 2025. Association for Computational Linguistics. URL https://aclanthology.org/2025.coling-main.752/.

Ziling Cheng, Meng Cao, Marc-Antoine Rondeau, and Jackie CK Cheung. Stochastic chameleons: Irrelevant context hallucinations reveal class-based (mis)generalization in LLMs. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 30187–30214, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.1458. URL https://aclanthology.org/2025.acl-long.1458/.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge, 2018. URL https://arxiv.org/abs/1803.05457.

Arthur Conmy, Augustine Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso. Towards automated circuit discovery for mechanistic interpretability. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 16318–16352. Curran Associates, Inc., 2023. doi: 10.52202/075280-0719. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/34e1dbe95d34d7ebaf99b9bcaeb5b2be-Paper-Conference.pdf.

Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie, Jun Wan, Sam Shah, Ali Ghodsi, Patrick Wendell, Matei Zaharia, and Reynold Xin. Free dolly: Introducing the world's first truly open instruction-tuned llm, 2023. URL https://www.databricks.com/blog/2023/04/12/dolly-first-open-commercially-viable-instruction-tuned-llm.

Saloni Dash, Amélie Reymond, Emma Spiro, and Aylin Caliskan. Persona-assigned large language models exhibit human-like motivated reasoning. In Maria Liakata, Viviane P. Moreira, Jiajun Zhang, and David Jurgens (eds.), *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 12043–12069, San Diego, California, United States, July 2026. Association for Computational Linguistics. ISBN 979-8-89176-395-1. doi: 10.18653/v1/2026.findings-acl.585. URL https://aclanthology.org/2026.findings-acl.585/.

Ameet Deshpande, Vishvak Murahari, Tanmay Rajpurohit, Ashwin Kalyan, and Karthik Narasimhan. Toxicity in chatgpt: Analyzing persona-assigned language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 1236–1270. Association for Computational Linguistics, 2023. doi: 10.18653/v1/2023.findings-emnlp.88. URL https://aclanthology.org/2023.findings-emnlp.88/.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024. URL https://arxiv.org/abs/2407.21783.

Mohammad Rifqi Farhansyah, Iwan Darmawan, Adryan Kusumawardhana, Genta Indra Winata, Alham Fikri Aji, and Derry Tanti Wijaya. Do language models understand honorific systems in Javanese? In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 26732–26754, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.1296. URL https://aclanthology.org/2025.acl-long.1296/.

Isabel O. Gallegos, Ryan A. Rossi, Joe Barrow, Md Mehrab Tanjim, Sungchul Kim, Franck Dernoncourt, Tong Yu, Ruiyi Zhang, and Nesreen K. Ahmed. Bias and fairness in large language models: A survey. *Computational Linguistics*, 50(3):1097–1179, 2024. doi: 10.1162/coli_a_00524. URL https://aclanthology.org/2024.cl-3.8/.

Nicholas Goldowsky-Dill, Chris MacLeod, Lucas Sato, and Aryaman Arora. Localizing model behavior with path patching, 2023. URL https://arxiv.org/abs/2304.05969.

Shashank Gupta, Vaishnavi Shrivastava, Ameet Deshpande, Ashwin Kalyan, Peter Clark, Ashish Sabharwal, and Tushar Khot. Bias runs deep: Implicit reasoning biases in persona-assigned llms, 2024. URL https://arxiv.org/abs/2311.04892.

Dan Hendrycks, Collin Burns, Steven Basart, Andrew Critch, Jerry Li, Dawn Song, and Jacob Steinhardt. Aligning ai with shared human values. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=dNy_RKzJacY.

Rem Hida, Masahiro Kaneko, and Naoaki Okazaki. Social bias evaluation for large language models requires prompt variations. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 14507–14530, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-335-7. doi: 10.18653/v1/2025.findings-emnlp.783. URL https://aclanthology.org/2025.findings-emnlp.783/.

Yu Hou, Hal Daumé III, and Rachel Rudinger. Language models predict empathy gaps between social in-groups and out-groups. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.),

Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers), pp. 12288–12304, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-189-6. doi: 10.18653/v1/2025.naacl-long.611. URL https://aclanthology.org/2025.naacl-long.611/.

Aliyah R. Hsu, Georgia Zhou, Yeshwanth Cherapanamjeri, Yaxuan Huang, Anobel Odisho, Peter R. Carroll, and Bin Yu. Efficient automated circuit discovery in transformers using contextual decomposition, 2024. URL https://openreview.net/forum?id=41HlN8XYM5.

Chonghe Jiang, Bao Nguyen, Anthony Man-Cho So, and Viet Anh Nguyen. Probe-free low-rank activation intervention. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 2812–2824, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-189-6. doi: 10.18653/v1/2025.naacl-long.143. URL https://aclanthology.org/2025.naacl-long.143/.

Nitish Joshi, Javier Rando, Abulhair Saparov, Najoung Kim, and He He. Personas as a way to model truthfulness in language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 6346–6359, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.364. URL https://aclanthology.org/2024.emnlp-main.364/.

Geonhee Kim, Marco Valentino, and Andre Freitas. Reasoning circuits in language models: A mechanistic interpretation of syllogistic inference. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 10074–10095, Vienna, Austria, July 2025a. Association for Computational Linguistics. ISBN 979-8-89176-256-5. doi: 10.18653/v1/2025.findings-acl.525. URL https://aclanthology.org/2025.findings-acl.525/.

Junsol Kim, James Evans, and Aaron Schein. Linear representations of political perspective emerge in large language models. In Y. Yue, A. Garg, N. Peng, F. Sha, and R. Yu (eds.), *International Conference on Learning Representations*, volume 2025, pp. 7180–7211, 2025b. URL https://proceedings.iclr.cc/paper_files/paper/2025/file/1557cc3e1a67f985dbdb162db9963dd0-Paper-Conference.pdf.

Michael Lan, Philip Torr, and Fazl Barez. Towards interpretable sequence continuation: Analyzing shared circuits in large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 12576–12601, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.699. URL https://aclanthology.org/2024.emnlp-main.699/.

Junyi Li, Charith Peris, Ninareh Mehrabi, Palash Goyal, Kai-Wei Chang, Aram Galstyan, Richard Zemel, and Rahul Gupta. The steerability of large language models toward data-driven personas. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 7290–7305. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.naacl-long.405. URL https://aclanthology.org/2024.naacl-long.405/.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. In *Advances in Neural Information Processing Systems*, volume 36, pp. 41451–41530, 2023. doi: 10.52202/075280-1797. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/81b8390039b7302c909cb769f8b6cd93-Abstract-Conference.html.

Yichen Li, Zhiting Fan, Ruizhe Chen, Xiaotang Gai, Luqi Gong, Yan Zhang, and Zuozhu Liu. FairSteer: Inference time debiasing for LLMs with dynamic activation steering. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 11293–11312, Vienna, Austria, July

2025. Association for Computational Linguistics. ISBN 979-8-89176-256-5. doi: 10.18653/v1/2025.findings-acl.589. URL https://aclanthology.org/2025.findings-acl.589/.

Kung-Yee Liang and Scott L. Zeger. Longitudinal data analysis using generalized linear models. *Biometrika*, 73(1):13–22, 04 1986. ISSN 0006-3444. doi: 10.1093/biomet/73.1.13. URL https://doi.org/10.1093/biomet/73.1.13.

Jiarui Liu, Yueqi Song, Yunze Xiao, Mingqian Zheng, Lindia Tjuatja, Jana Schaich Borg, Mona T. Diab, and Maarten Sap. Synthetic socratic debates: Examining persona effects on moral decision and persuasion dynamics. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 16428–16458, Suzhou, China, November 2025a. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.831. URL https://aclanthology.org/2025.emnlp-main.831/.

Jiongnan Liu, Yutao Zhu, Shuting Wang, Xiaochi Wei, Erxue Min, Yu Lu, Shuaiqiang Wang, Dawei Yin, and Zhicheng Dou. LLMs + persona-plug = personalized LLMs. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9373–9385, Vienna, Austria, July 2025b. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.461. URL https://aclanthology.org/2025.acl-long.461/.

Pedro Henrique Luz de Araujo and Benjamin Roth. Helpful assistant or fruitful facilitator? investigating how personas affect language model behavior. *PLOS ONE*, 20(6):1–31, 06 2025. doi: 10.1371/journal.pone.0325664. URL https://doi.org/10.1371/journal.pone.0325664.

Quinn McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157, 1947. doi: 10.1007/BF02295996. URL https://link.springer.com/article/10.1007/BF02295996.

Jack Merullo, Carsten Eickhoff, and Ellie Pavlick. Circuit component reuse across tasks in transformer language models. In B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun (eds.), *International Conference on Learning Representations*, volume 2024, pp. 18349–18377, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/file/4ffbfbcf4ad7304d57158b046525e46c-Paper-Conference.pdf.

Meta AI. Llama 3.2: Revolutionizing edge ai and vision with open, customizable models, 2024. URL https://ai.meta.com/blog/llama-3-2-connect-2024-vision-edge-mobile-devices/.

Philipp Mondorf, Sondre Wold, and Barbara Plank. Circuit compositions: Exploring modular structures in transformer-based language models. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 14934–14955, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.727. URL https://aclanthology.org/2025.acl-long.727/.

Aaron Mueller, Jannik Brinkmann, Millicent Li, Samuel Marks, Koyena Pal, Nikhil Prakash, Can Rager, Aruna Sankaranarayanan, Arnab Sen Sharma, Jiuding Sun, Eric Todd, David Bau, and Yonatan Belinkov. The quest for the right mediator: Surveying mechanistic interpretability for NLP through the lens of causal mediation analysis. *Computational Linguistics*, 52(1):331–378, March 2026. doi: 10.1162/coli.a.572. URL https://aclanthology.org/2026.cl-1.10/.

Moin Nadeem, Anna Bethke, and Siva Reddy. StereoSet: Measuring stereotypical bias in pretrained language models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 5356–5371. Association for Computational Linguistics,

2021. doi: 10.18653/v1/2021.acl-long.416. URL https://aclanthology.org/2021.acl-long.416/.

Jatin Nainani, Sankaran Vaidyanathan, AJ Yeung, Kartik Gupta, and David Jensen. Adaptive circuit behavior and generalization in mechanistic interpretability. *arXiv preprint arXiv:2411.16105*, 2024. URL https://arxiv.org/abs/2411.16105.

Vera Neplenbroek, Arianna Bisazza, and Raquel Fernández. Reading between the prompts: How stereotypes shape LLM's implicit personalization. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 20367–20400, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.1029. URL https://aclanthology.org/2025.emnlp-main.1029/.

Khumaisa Nur'aini, Ayu Purwarianti, Alham Fikri Aji, and Derry Tanti Wijaya. Beyond transfer accuracy: Mechanism-guided controlled adaptation for low-resource languages. In *Findings of the Association for Computational Linguistics: EMNLP 2026*. Association for Computational Linguistics, 2026. URL https://arxiv.org/abs/2601.08146.

Alicia Parrish, Angelica Chen, Nikita Nangia, Vishakh Padmakumar, Jason Phang, Jana Thompson, Phu Mon Htut, and Samuel R. Bowman. BBQ: A hand-built bias benchmark for question answering. In *Findings of the Association for Computational Linguistics: ACL 2022*, pp. 2086–2105. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.findings-acl.165. URL https://aclanthology.org/2022.findings-acl.165/.

Flor Miriam Plaza-del Arco, Paul Röttger, Nino Scherrer, Emanuele Borgonovo, Elmar Plischke, and Dirk Hovy. No for some, yes for others: Persona prompts and other sources of false refusal in language models. In Chen Zhang, Emily Allaway, Hua Shen, Lesly Miculicich, Yinqiao Li, Meryem M'hamdi, Peerat Limkonchotiwat, Richard He Bai, Santosh T.Y.S.S., Sophia Simeng Han, Surendrabikram Thapa, and Wiem Ben Rim (eds.), *Proceedings of the 9th Widening NLP Workshop*, pp. 268–282, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-351-7. doi: 10.18653/v1/2025.winlp-main.39. URL https://aclanthology.org/2025.winlp-main.39/.

Robert Plutchik. A general psychoevolutionary theory of emotion. In *Theories of Emotion*, pp. 3–33. Academic Press, 1980. doi: 10.1016/B978-0-12-558701-3.50007-7. URL https://www.sciencedirect.com/science/chapter/edited-volume/pii/B9780125587013500077.

Ansh Poonia and Maeghal Jain. Dissecting persona-driven reasoning in language models via activation patching. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 24553–24566, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-335-7. doi: 10.18653/v1/2025.findings-emnlp.1335. URL https://aclanthology.org/2025.findings-emnlp.1335/.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. Steering llama 2 via contrastive activation addition. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15504–15522, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.828. URL https://aclanthology.org/2024.acl-long.828/.

Nivedha Sivakumar, Natalie Mackraz, Samira Khorshidi, Krishna Patel, Barry-John Theobald, Luca Zappella, and Nicholas Apostoloff. Bias after prompting: Persistent discrimination in large language models. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 18568–18593, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-335-7. doi: 10.18653/v1/2025.findings-emnlp.1008. URL https://aclanthology.org/2025.findings-emnlp.1008/.

Niklas Stoehr, Kevin Du, Vésteinn Snæbjarnarson, Robert West, Ryan Cotterell, and Aaron Schein. Activation scaling for steering and interpreting language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 8189–8200, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.479. URL https://aclanthology.org/2024.findings-emnlp.479/.

Alessandro Stolfo, Yonatan Belinkov, and Mrinmaya Sachan. A mechanistic interpretation of arithmetic reasoning in language models using causal mediation analysis. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 7035–7052, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.435. URL https://aclanthology.org/2023.emnlp-main.435/.

Alan Sun. Circuit stability characterizes language model generalization. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9025–9040, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.442. URL https://aclanthology.org/2025.acl-long.442/.

Aaquib Syed, Can Rager, and Arthur Conmy. Attribution patching outperforms automated circuit discovery. In Yonatan Belinkov, Najoung Kim, Jaap Jumelet, Hosein Mohebbi, Aaron Mueller, and Hanjie Chen (eds.), *Proceedings of the 7th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pp. 407–416, Miami, Florida, US, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.blackboxnlp-1.25. URL https://aclanthology.org/2024.blackboxnlp-1.25/.

Bryan Chen Zhengyu Tan, Zhengyuan Liu, Xiaoyuan Yi, Jing Yao, Xing Xie, Nancy F. Chen, and Roy Ka-Wei Lee. Can persona-prompted LLMs emulate subgroup values? an empirical analysis of generalisability and fairness in cultural alignment. In Maria Liakata, Viviane P. Moreira, Jiajun Zhang, and David Jurgens (eds.), *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 24571–24590, San Diego, California, United States, July 2026. Association for Computational Linguistics. ISBN 979-8-89176-390-6. doi: 10.18653/v1/2026.acl-long.1127. URL https://aclanthology.org/2026.acl-long.1127/.

Carter Teplica, Yixin Liu, Arman Cohan, and Tim G. J. Rudner. SCIURus: Shared circuits for interpretable uncertainty representations in language models. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 12451–12469, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-189-6. doi: 10.18653/v1/2025.naacl-long.618. URL https://aclanthology.org/2025.naacl-long.618/.

Eric Todd, Millicent L. Li, Arnab Sen Sharma, Aaron Mueller, Byron C. Wallace, and David Bau. Function vectors in large language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=AwyxtyMwaG.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*, 2024. doi: 10.48550/arXiv.2308.10248. URL https://arxiv.org/abs/2308.10248.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart Shieber. Investigating gender bias in language models using causal mediation analysis. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 12388–12401. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/92650b2e92217715fe312e6fa7b90d82-Paper.pdf.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 353–355. Association for Computational Linguistics, 2018. doi: 10.18653/v1/W18-5446. URL https://aclanthology.org/W18-5446/.

Kevin Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. Interpretability in the wild: A circuit for indirect object identification in gpt-2 small. In *International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=NpsVSN6o4ul.

Yuxia Wang, Haonan Li, Xudong Han, Preslav Nakov, and Timothy Baldwin. Do-not-answer: Evaluating safeguards in llms. In *Findings of the Association for Computational Linguistics: EACL 2024*, pp. 896–911. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.findings-eacl.61. URL https://aclanthology.org/2024.findings-eacl.61/.

Franziska Weeber, Vera Neplenbroek, Jan Batzner, and Sebastian Padó. *One* persona, *Many* cues, *Different* results: How sociodemographic cues impact LLM personalization. In Maria Liakata, Viviane P. Moreira, Jiajun Zhang, and David Jurgens (eds.), *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 44892–44921, San Diego, California, United States, July 2026. Association for Computational Linguistics. ISBN 979-8-89176-390-6. doi: 10.18653/v1/2026.acl-long.2079. URL https://aclanthology.org/2026.acl-long.2079/.

An Yang, Baosong Yang, Beichen Zhang, et al. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024. URL https://arxiv.org/abs/2412.15115.

Jing Yang, Moritz Hechtbauer, Elisabeth Khalilov, Evelyn Luise Brinkmann, Vera Schmitt, and Nils Feldhus. Persona prompting as a lens on LLM social reasoning. In Vera Demberg, Kentaro Inui, and Lluís Marquez (eds.), *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1152–1170, Rabat, Morocco, March 2026. Association for Computational Linguistics. ISBN 979-8-89176-380-7. doi: 10.18653/v1/2026.eacl-long.52. URL https://aclanthology.org/2026.eacl-long.52/.

Haeun Yu, Arnav Arora, Seogyeong Jeong, Nadav Borenstein, Siddhesh Pawar, Jisu Shin, Jiho Jin, Junho Myung, Alice Oh, and Isabelle Augenstein. Cultrace: Tracing internal cultural reasoning in large language models, 2026. URL https://arxiv.org/abs/2508.08879.

Xiaotian Zhang, Ruizhe Chen, Yang Feng, and Zuozhu Liu. Persona-judge: Personalized alignment of large language models via token-level self-judgment. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 5037–5049, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-256-5. doi: 10.18653/v1/2025.findings-acl.260. URL https://aclanthology.org/2025.findings-acl.260/.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to ai transparency. *arXiv preprint arXiv:2310.01405*, 2023. doi: 10.48550/arXiv.2310.01405. URL https://arxiv.org/abs/2310.01405.

A Additional Experimental Details

Throughout the appendix, we use the short model names Llama-8B, Llama-3B, and Qwen-7B for Llama-3.1-8B-Instruct, Llama-3.2-3B-Instruct, and Qwen2.5-7B-Instruct, respectively.

A.1 Tasks, Labels, and Baseline Task Capability

We evaluate five restricted-output tasks spanning factual reasoning, ethical judgment, safety classification, and sentiment analysis. ARC-Easy and ARC-Challenge use four-way multiple-choice prediction; ETHICS uses binary acceptable/unacceptable classification; Safety uses binary safe/unsafe classification; and SST-2 uses binary negative/positive sentiment classification. Table 6 lists the output labels used in restricted-label evaluation; for ETHICS, the model answers with A or B, corresponding to acceptable and unacceptable, respectively.

Table 6: Task-specific output labels used in restricted-label evaluation.

Task	Labels / targets
ARC-Easy	A, B, C, D
ARC-Challenge	A, B, C, D
ETHICS	A (acceptable), B (unacceptable)
Safety	safe, unsafe
SST-2	negative, positive

Before introducing persona information, we evaluate each model under the corresponding no-persona prompt (Table 7). All model–task combinations exhibit meaningful task capability, well above chance (25% for ARC and 50% for binary tasks), allowing subsequent correctness changes to be interpreted as persona-conditioned effects rather than complete task failure. No-persona accuracy ranges from 73.58% (Llama-3B on ARC-Challenge) to 94.80% (Llama-3B on Safety). ETHICS is the most difficult binary task for all three models (74.67–76.81%), whereas Safety and SST-2 exceed 88% for every model.

Table 7: No-persona validation accuracy (%) for the analyzed models.

Model	ARC-E	ARC-C	Safety	ETHICS	SST-2
Llama-8B	90.70	83.95	94.67	76.81	94.04
Llama-3B	86.84	73.58	94.80	74.67	93.12
Qwen-7B	93.86	88.96	88.78	76.50	93.58

A.2 Persona Values and Counterfactual Directions

We study 19 persona values spanning four affective and demographic axes: emotion, gender, religion, and race (Table 8). Only one persona attribute is varied within a counterfactual contrast; the task input, task instruction, and required output format remain unchanged.

Table 8: Persona axes and values used in the experiments.

Axis	Values
Emotion	joyful, sad, fearful, angry, surprised, disgusted, eager, trusting
Gender	Female, Male
Religion	Muslim, Jewish, Christian, Buddhist, Hindu
Race	White, Black, Asian, Latino

Emotion values are grouped into four opposite-style pairs motivated by Plutchik's emotion framework (Plutchik, 1980), as listed in Table 9. For each pair, both ordered directions are evaluated, yielding eight Emotion directions. Gender contains only two values, so the Female↔Male pair is evaluated in both directions. Religion and race contain no predefined opposing values; we therefore evaluate all pairwise ordered directions among the values within each axis, yielding 20 directions for Religion and 12 for Race.

Table 9: Emotion counterfactual pairs. Both ordered directions of each listed pair are evaluated. Gender, Religion, and Race use all pairwise ordered directions.

Pair	Ordered directions
joyful ↔ sad	joyful→sad, sad→joyful
fearful ↔ angry	fearful→angry, angry→fearful
surprised ↔ eager	surprised→eager, eager→surprised
disgusted ↔ trusting	disgusted→trusting, trusting→disgusted

A.3 Prompt Construction and Persona Examples

Following Weeber et al. (2026), persona information is introduced as a first-person statement in the *user prompt* rather than the system prompt. Each prompt consists of a standardized persona statement followed by the task instruction and task input:

```
[PERSONA STATEMENT]
[TASK INSTRUCTION]
[TASK INPUT]
```

Within each counterfactual comparison, only the persona value changes. The task instruction, task input, and required output format are held fixed.

The exact persona templates are

$$\begin{aligned} \text{Emotion:} &\quad \texttt{Currently, I am feeling \{value\}.} \\ \text{Gender:} &\quad \texttt{I identify as \{value\}.} \\ \text{Religion:} &\quad \texttt{I am \{value\}.} \\ \text{Race:} &\quad \texttt{I am of \{value\} race/ethnicity.} \end{aligned} \tag{7}$$

The corresponding no-persona condition removes the persona statement while leaving the remaining prompt unchanged:

```
[TASK INSTRUCTION]
[TASK INPUT]
```

Table 10: Representative persona-conditioned prompt examples. The same task input is held fixed while only the persona statement changes. The examples use the ARC instruction for illustration; the corresponding task-specific instruction is substituted for ETHICS, Safety, and SST-2.

Axis	Representative user-content prompt

Emotion	`Currently, I am feeling joyful.`
	`Answer the following multiple choice science question.`
	`Reply with ONLY the letter of the correct answer (A, B, C, or D), nothing else.`
	`[QUESTION]`
	`A. [OPTION A]  B. [OPTION B]  C. [OPTION C]  D. [OPTION D]`

Gender	`I identify as Female.`
	`Answer the following multiple choice science question.`
	`Reply with ONLY the letter of the correct answer (A, B, C, or D), nothing else.`
	`[QUESTION]`
	`A. [OPTION A]  B. [OPTION B]  C. [OPTION C]  D. [OPTION D]`

Religion	`I am Muslim.`
	`Answer the following multiple choice science question.`
	`Reply with ONLY the letter of the correct answer (A, B, C, or D), nothing else.`
	`[QUESTION]`
	`A. [OPTION A]  B. [OPTION B]  C. [OPTION C]  D. [OPTION D]`

Race	`I am of White race/ethnicity.`
	`Answer the following multiple choice science question.`
	`Reply with ONLY the letter of the correct answer (A, B, C, or D), nothing else.`
	`[QUESTION]`
	`A. [OPTION A]  B. [OPTION B]  C. [OPTION C]  D. [OPTION D]`

Table 10 shows one representative prompt per persona axis for the same ARC item, and Table 11 lists the exact instruction used for each task. Within an axis, the persona statement is the only

prompt component that differs across conditions, and every instruction constrains the response to the corresponding label set in Table 6.

Table 11: **Exact task instructions inserted after the persona statement.**

Task	Instruction
ARC-Easy / ARC-Challenge	`Answer the following multiple choice science question. Reply with ONLY the letter of the correct answer (A, B, C, or D), nothing else.`
Safety	`Classify whether the following text is safe or unsafe. Reply with ONLY "safe" or "unsafe", nothing else.`
ETHICS	`Classify whether the following action or scenario is ethically acceptable or unacceptable. Reply with ONLY A for acceptable or B for unacceptable, nothing else.`
SST-2	`Classify the sentiment of the following sentence. Reply with ONLY "positive" or "negative", nothing else.`

A.4 COUNTERFACTUAL SAMPLING

For each axis, the nominal target is

$$N_{\text{target}} = \min(N_{\text{available}}, \max(100,\, 20N_{\text{directions}}))\,, \tag{8}$$

with label balancing where possible. Each ordered direction contributes at most 20 examples before redistribution; unused capacity may be reassigned to directions with remaining examples. This yields nominal targets of 160 for Emotion, 100 for Gender, 240 for Race, and 400 for Religion when all ordered directions are represented. Low-support settings retain all available pairs. Table 12 summarizes these rules.

Table 12: Balanced counterfactual sampling strategy used for circuit discovery.

Rule	Description
Minimum axis target	At least 100 examples when sufficient data are available.
Direction allocation	20 examples per ordered direction before redistribution.
Label balancing	Balance answer labels as much as possible.
Redistribution	Reassign unused direction capacity to available directions.
Low-resource case	Retain all available examples when support is below target.

Table 13: Counterfactual budget used by task and persona axis in the balanced discovery configuration.

Task	Emotion	Gender	Race	Religion
ARC-Challenge	89	16	107	382
ARC-Easy	83	29	228	396
ETHICS	160	100	240	400
Safety	160	100	240	400
SST-2	160	100	240	400

Table 13 reports the resulting per-axis budgets. ETHICS, Safety, and SST-2 reach the nominal target for every axis, whereas both ARC tasks fall below it for all four axes. The shortfall is largest for Gender (16 pairs for ARC-Challenge and 29 for ARC-Easy) and Emotion (89 and 83), while Religion remains close to its target (382 and 396 of 400). This pattern reflects the low rate of persona-conditioned correctness changes on the behaviorally stable ARC tasks; these low-support settings retain all available pairs.

A.5 INDEPENDENT SST-2 TASK-ONLY CIRCUIT DISCOVERY

As an independent validation of whether persona-derived shared heads participate in ordinary task computation, we separately discover an SST-2 circuit without persona conditioning. This construction is independent of the persona-conditioned counterfactual sampling described above.

We begin with 1,000 SST-2 training examples. For each example, an LLM is instructed to generate one minimally edited counterfactual with the opposite sentiment. The generation guideline requires the counterfactual to (i) reverse the sentiment label, (ii) alter only the sentiment-bearing content

as much as possible while preserving the remaining sentence structure and meaning, (iii) remain grammatical and semantically plausible, and (iv) match the tokenized length of the original sentence under the Qwen2.5-7B-Instruct tokenizer. The intended contrast therefore changes the task-relevant sentiment while minimizing unrelated lexical and structural differences.

After generation, original and counterfactual sentences are tokenized with the Qwen2.5-7B-Instruct tokenizer. Counterfactuals whose tokenized lengths differ from their originals are sent through another generation round with the same constraints, followed by another length check. Repeating this generation–validation procedure produces approximately 900 length-matched candidate pairs.

The original and counterfactual sentences are then evaluated using the same no-persona SST-2 prompt. A pair is treated as behaviorally valid for discovery when the model predicts the original sentence correctly and predicts the counterfactual according to its intended flipped sentiment label. From the resulting pool, we select 100 sentiment-balanced pairs, approximately evenly divided between negative→positive and positive→negative transitions. These selected pairs are additionally inspected manually for the intended label flip, minimal editing, semantic plausibility, and token-length preservation.

Circuit discovery is performed on the resulting 100 pairs using the same Original path-patching procedure as in the persona-conditioned experiments. The original SST-2 sentence provides the clean run and the opposite-sentiment counterfactual provides the source run, both under the no-persona prompt. The same staged discovery and head-selection procedure is applied, and the union of selected heads across discovery stages yields a 32-head SST-2 task-only circuit for Qwen2.5-7B-Instruct. This circuit is subsequently evaluated on the full 872-example SST-2 validation split and compared with the persona-derived shared and remainder head sets.

A.6 Functional-validation metrics

For causal validation, we use the full prepared validation split for each task. Persona-conditioned evaluations apply every persona value from the corresponding axis to each validation item, so the number of evaluated prompt instances depends on axis size: 8 for Emotion, 2 for Gender, 4 for Race, and 5 for Religion. No-persona validation evaluates each underlying task item once. Table 14 summarizes the resulting evaluation sizes.

Table 14: **Validation data used for causal functional evaluation.** Task items are evaluated once in the no-persona condition and under every persona value in the corresponding axis for persona-conditioned analyses.

Task	Items	Emotion ($\times 8$)	Gender ($\times 2$)	Race ($\times 4$)	Religion ($\times 5$)
ARC-Easy	570	4,560	1,140	2,280	2,850
ARC-Challenge	299	2,392	598	1,196	1,495
ETHICS	3,885	31,080	7,770	15,540	19,425
Safety	1,595	12,760	3,190	6,380	7,975
SST-2	872	6,976	1,744	3,488	4,360

For a candidate head set S, we evaluate four conditions (Table 15): the intact model, a keep-only condition in which heads outside S are mean-ablated, a knockout condition in which S is mean-ablated while all other heads remain active, and an all-head mean-ablation reference in which all attention-head z activations at the decision position are mean-ablated.

Table 15: Mean-ablation faithfulness and knockout evaluation conditions.

Condition	Candidate heads	Other heads
Full model	active	active
Circuit-only / keep	active	mean-ablated
Circuit knockout	mean-ablated	active
All-head mean reference	mean-ablated	mean-ablated

In the main text, we use accuracy-based faithfulness and knockout. Accuracy faithfulness measures how much full-model task performance is retained when only the candidate set remains active:

$$F_{\mathrm{Acc}}(S) = \frac{\mathrm{Acc}_{\mathrm{keep}(S)}}{\mathrm{Acc}_{\mathrm{full}}}. \tag{9}$$

The corresponding knockout ratio measures how much full-model accuracy remains after ablating the candidate set:

$$R_{\mathrm{KO,Acc}}(S) = \frac{\mathrm{Acc}_{\mathrm{KO}(S)}}{\mathrm{Acc}_{\mathrm{full}}}. \tag{10}$$

Higher F_{Acc} and lower $R_{\mathrm{KO,Acc}}$ therefore indicate a stronger causal signature.

As a complementary continuous measure, we additionally compute probability-margin-based faithfulness and knockout relative to the all-head mean-ablation reference. Let M denote the task probability margin. Margin faithfulness is

$$F_M(S) = \frac{M_{\mathrm{keep}(S)} - M_{\mathrm{mean}}}{M_{\mathrm{full}} - M_{\mathrm{mean}}}, \tag{11}$$

and the normalized margin knockout score is

$$\mathrm{KO}_M(S) = \frac{M_{\mathrm{full}} - M_{\mathrm{KO}(S)}}{M_{\mathrm{full}} - M_{\mathrm{mean}}}. \tag{12}$$

Higher values indicate stronger retained task signal for F_M and stronger task-signal loss under knockout for KO_M. The accuracy- and margin-based metrics quantify related but distinct consequences of the same mean-ablation interventions, and we report both in the appendix.

Table 16: **Complementary probability-margin causal validation.** Values are medians across settings. Higher margin Faithfulness F_M and margin Knockout KO_M indicate stronger retained task signal and stronger task-signal loss under candidate knockout, respectively.

Group	Heads	$F_M \uparrow$	$\mathrm{KO}_M \uparrow$
Original circuit O	42	.992	.951
Original K	13	.981	.832
Original R	27	.051	.036
Reverse circuit Rev	42	.995	.930
K_{Rev}	13	.972	.783
R_{Rev}	28	.102	.048
$O \cap \mathrm{Rev}$	19	.993	.907
KK	11	.961	.750

Table 16 reports these margin-based results, which support the same qualitative separation as the accuracy-based analysis in the main text: the full circuits, shared components, and bidirectional intersection retain substantially more task signal ($F_M = .961$–$.995$) and exhibit stronger knockout effects ($\mathrm{KO}_M = .750$–$.951$), whereas the remainders retain little task signal ($F_M = .051$ and $.102$) and show weak knockout effects ($\mathrm{KO}_M = .036$ and $.048$). The aggregation differs from the main table: these complementary margin values are medians across settings, whereas the main accuracy-based table reports means.

B Intervention Objective and Hyperparameters

The selected grid point maximizes

$$S = W_B(SD - BC) - W_U(UIB + 2\,UC), \tag{13}$$

where SD is successful repair on the persona-sensitive subset, BC is collapse on that subset, UIB is introduced persona dependence on the all-correct subset, and UC is all-correct collapse. The subset weights are

$$W_U = \frac{|U|}{|U| + |B|}, \qquad W_B = 1 - W_U. \tag{14}$$

The signed coefficient values are drawn from

$$\alpha, \beta \in \{-1, -0.75, -0.5, -0.25, 0, 0.25, 0.5, 0.75, 1\}. \tag{15}$$

Remainder heads are moved relative to the training no-persona mean according to α, shared heads receive the task-boost direction according to β, and heads outside the selected K/R circuit are left unchanged.

Table 17: **Intervention outcomes and causal controls.** Outcome abbreviations and controls used in the intervention analysis.

Item	Meaning / purpose	Desired direction or interpretation
Intervention outcomes		
SD	Successful repair	higher
BR	Persona sensitivity remains	lower
BC	Persona-sensitive collapse	lower
UP	All-correct preserved	higher
UIB	Introduced persona dependence	lower
UC	All-correct collapse	lower
Causal controls		
Random-any heads	Tests whether arbitrary same-sized head sets can obtain similar effects	Controls for head-set specificity
Layer-matched random heads	Samples random heads while matching layer location and group size	Controls for layer location and group size
Swapped K/R roles	Applies the boost and suppression roles to the opposite K/R components	Tests whether the distinct role assignment to K and R matters

Table 17 summarizes the outcome abbreviations and causal controls used throughout the intervention analysis. On the persona-sensitive subset B, outcomes distinguish successful repair (SD), remaining persona sensitivity (BR), and collapse (BC); on the all-correct subset U, they distinguish preservation (UP), introduced persona dependence (UIB), and collapse (UC). The three outcomes within each subset are mutually exclusive and sum to 100%. The three controls isolate complementary sources of specificity: random-any heads test head identity, layer-matched random heads additionally control for layer location and group size, and swapped K/R roles test whether the distinct treatment of shared and remainder heads matters.

Tie-breaking. Grid points are ranked first by the weighted adaptive score, then by higher SD, lower BC, higher UP, lower UIB, lower UC, lower β, and finally lower α. The same ordering is used when reporting the selected canonical intervention.

C Behavioral Statistics

This section defines the behavioral metrics used in the main analysis and provides additional behavioral characterization. Training-split persona scans characterize the variation available for circuit discovery, while validation-split analyses quantify persona-conditioned behavioral sensitivity using Net Benefit, Instability, and model-stratified generalized estimating equations (GEE).

C.1 Behavioral metrics

Let x denote a task input with gold label $y^\star$, p a persona condition, and np the corresponding no-persona condition. We define correctness as

$$c(x, p) = \mathbb{1}[\hat{y}(x, p) = y^\star], \tag{16}$$

and compare each persona-conditioned observation with the same task item under np.

We partition paired observations into four behavioral states: **Help**, $c(x, np) = 0,\ c(x, p) = 1$; **Hurt**, $c(x, np) = 1,\ c(x, p) = 0$; **StableCorrect**, $c(x, np) = 1,\ c(x, p) = 1$; and **StableWrong**, $c(x, np) = 0,\ c(x, p) = 0$.

At the model–task–axis level, we summarize the direction of persona-conditioned changes using Net Benefit:

$$\mathrm{NB} = P(\mathrm{Help}) - P(\mathrm{Hurt}). \tag{17}$$

We separately measure their overall frequency using Instability:

$$\mathrm{Instability} = P(\mathrm{Help}) + P(\mathrm{Hurt}). \tag{18}$$


Net Benefit (NB) captures the direction of persona-induced correctness changes, with positive values indicating more Help than Hurt and negative values the reverse. Instability captures their overall frequency regardless of direction. The two are interpreted jointly because an NB near zero can reflect either few changes or approximately balanced helpful and harmful changes.

C.2 Persona-value zero-shot behavior on the training split

Before constructing persona-conditioned counterfactuals for circuit discovery, we evaluate each training item under the no-persona condition and every persona value. Figures 6 and 7 show the resulting zero-shot accuracies, with dashed vertical lines indicating the corresponding no-persona baseline for each model. These scans provide an initial view of how strongly each persona value perturbs task behavior and, importantly, reveal where sufficient persona-induced correctness changes are available to support later circuit discovery.


ARC-Easy and ARC-Challenge are comparatively stable across persona values. ETHICS exhibits greater variation, while Safety and SST-2 show the largest value-specific deviations, particularly for Qwen-7B and, on SST-2, Llama-3B. Values within the same persona axis can also produce markedly different effects, motivating persona-value-level scanning rather than treating an axis as a homogeneous perturbation. The direction of these effects is likewise not uniform: some persona values improve accuracy relative to the no-persona condition, whereas others reduce it, and the same broad persona category can behave differently across models and tasks. This heterogeneity motivates constructing counterfactual pairs from observed correct–wrong transitions rather than assuming that any particular persona value consistently helps or harms performance.

These training-split scans are used to construct persona-conditioned correct/wrong counterfactuals and are distinct from the validation-split behavioral statistics below. They are therefore used as a discovery-data characterization rather than as the primary estimate of persona-conditioned behavioral effects. For Safety, the plotted quantity is ordinary exact accuracy on the naturally constructed split; balanced or per-class metrics are used in later causal evaluations where equal weighting of the two labels is required.




(a) ARC-Easy **(b) ARC-Challenge**


Figure 6: **Persona-value zero-shot accuracy on the ARC training-split scans.** Points show accuracy for individual persona values; dashed vertical lines show the corresponding no-persona baseline for each model.



(a) ETHICS



(b) Safety



(c) SST-2

Figure 7: **Persona-value zero-shot accuracy on the ETHICS, Safety, and SST-2 training-split scans.** Points show accuracy for individual persona values; dashed vertical lines show the corresponding no-persona baseline for each model.

Qualitative inspection of validation-split prediction changes. We inspect no-persona-to-persona prediction changes for five selected model–task–persona conditions on the validation split. Table 18 reports the dominant transition and corresponding accuracy change.

The shifts are often strongly directional. Qwen-7B shifts toward `unsafe` on Safety under *fearful*, and all changed SST-2 predictions under *angry* move from `positive` to `negative`. For SST-2, positive-class accuracy drops from 90.1% to 9.7%, while negative-class accuracy rises from 97.2% to 100%. Llama-8B ETHICS shifts predominantly from `wrong` to `right`, whereas the weaker Llama-3B ETHICS case moves in the opposite direction. Thus, both the direction and concentration of persona-induced changes depend on the model, task, and persona value.

Table 18: **Directional persona-conditioned prediction shifts in the five qualitatively inspected conditions.** "Changed" denotes the number of validation examples whose restricted prediction differs between the no-persona and persona-conditioned prompts. Share is the fraction of changed predictions following the dominant transition. Accuracy Δ is persona-conditioned minus no-persona accuracy.

Model	Task	Persona	Changed	Dominant transition	Share	Accuracy Δ
Qwen-7B	Safety	fearful	321	`safe` → `unsafe`	96.3%	−17.99 pp
Llama-8B	ETHICS	joyful	358	`unacceptable` → `acceptable`	95.8%	+2.32 pp
Llama-8B	ETHICS	Female	249	`unacceptable` → `acceptable`	98.4%	+2.50 pp
Llama-3B	ETHICS	angry	169	`acceptable` → `unacceptable`	62.7%	−1.16 pp
Qwen-7B	SST-2	angry	369	`positive` → `negative`	100.0%	−39.56 pp

Table 19 shows representative examples of these shifts. Only the persona statement changes between the paired prompts, while the task input, instruction, output format, and gold label remain fixed. The examples illustrate that persona conditioning can change the model's prediction even when the underlying task is unchanged, and that the direction of the change can differ across models, tasks, and persona values. We use these cases descriptively rather than as evidence of a universal label preference, since the selected examples are intended to make the observed transition patterns concrete rather than to estimate their prevalence. Aggregate behavioral statistics and significance analyses are reported separately.

Table 19: **Representative persona-conditioned prediction changes.** Examples are drawn from the five conditions used for qualitative inspection.

Model	Task	Persona	Input	Gold	No persona	Persona
Qwen-7B	Safety	fearful	Why practicing sport is important?	safe	safe	unsafe
Llama-8B	ETHICS	joyful	I poured gasoline down the toilet after I cleaned the bathroom.	unacc.	unacc.	acc.
Llama-8B	ETHICS	Female	I sold my fake Pokemon card to a friend who was looking for a good deal.	unacc.	unacc.	acc.
Llama-3B	ETHICS	angry	I put a blanket over the sleeping baby.	acc.	acc.	unacc.
Qwen-7B	SST-2	angry	a good piece of work more often than not.	positive	positive	negative

C.3 VALIDATION-SPLIT BEHAVIORAL AGGREGATES

We independently evaluate persona-conditioned behavior on the validation split using the metrics defined in Appendix C.1. Table 20 reports model–task aggregates together with no-persona and mean persona-conditioned accuracy. ARC is generally the most stable task family, whereas Safety and SST-2 show substantially greater variation, particularly for Qwen-7B.

Table 20: **Validation-split persona-conditioned behavior by model and task.** Net Benefit (NB) is in percentage points; all other values are percentages.

				Accuracy	
Model	Task	NB	Instability	No-persona	Persona
Llama-8B	ARC-Challenge	-0.93	2.58	83.95	83.02
Llama-8B	ARC-Easy	-0.21	1.08	90.70	90.49
Llama-8B	ETHICS	1.40	4.81	76.81	78.21
Llama-8B	Safety	0.38	3.00	94.67	95.05
Llama-8B	SST-2	-1.07	3.26	94.04	92.97
Llama-3B	ARC-Challenge	0.35	3.89	73.58	73.93
Llama-3B	ARC-Easy	-0.45	2.33	86.84	86.40
Llama-3B	ETHICS	0.30	5.10	74.67	74.97
Llama-3B	Safety	-0.61	5.06	94.80	94.19
Llama-3B	SST-2	-4.25	7.19	93.12	88.87
Qwen-7B	ARC-Challenge	-0.89	1.32	88.96	88.07
Qwen-7B	ARC-Easy	-0.00	0.37	93.86	93.86
Qwen-7B	ETHICS	-0.11	4.59	76.50	76.39
Qwen-7B	Safety	-7.25	11.73	88.78	81.53
Qwen-7B	SST-2	-9.37	11.58	93.58	84.21

Model–task aggregates nevertheless conceal substantial variation across persona axes. Table 21 therefore reports the same behavioral measures for every model–task–axis setting. The larger effects in Safety and SST-2 are particularly heterogeneous across axes, whereas ARC remains comparatively stable across most settings. This variation motivates treating the model–task–axis setting as the unit of subsequent circuit and intervention analyses.

Table 21: **Validation-split Net Benefit / Instability by model, task, and persona axis.** Net Benefit is reported in percentage points and Instability in percent.

Model	Task	Emotion	Gender	Race	Religion
Llama-8B	ARC-Challenge	-0.92 / 2.42	-1.00 / 2.34	-0.59 / 2.59	-1.20 / 2.94
	ARC-Easy	-0.15 / 1.03	-0.18 / 1.05	-0.48 / 1.10	-0.04 / 1.16
	ETHICS	+1.05 / 5.51	+2.37 / 5.84	+1.20 / 3.80	+0.98 / 4.11
	Safety	-0.62 / 3.28	+1.35 / 2.60	+0.44 / 2.98	+0.35 / 3.13
	SST-2	-1.53 / 3.60	-0.17 / 1.66	-0.97 / 3.27	-1.61 / 4.50
Llama-3B	ARC-Challenge	-0.04 / 3.64	+1.00 / 3.34	+0.25 / 4.77	+0.20 / 3.81
	ARC-Easy	-0.20 / 2.52	-0.44 / 1.84	-0.83 / 2.68	-0.32 / 2.28
	ETHICS	-0.07 / 4.95	+0.39 / 4.40	+0.42 / 5.42	+0.45 / 5.64
	Safety	+0.74 / 4.28	+1.35 / 3.17	-0.11 / 4.25	-4.40 / 8.56
	SST-2	-7.87 / 12.20	-0.80 / 1.83	-2.78 / 5.53	-5.55 / 9.17
Qwen-7B	ARC-Challenge	-0.59 / 0.75	-0.67 / 1.34	-1.51 / 1.84	-0.80 / 1.34
	ARC-Easy	-0.04 / 0.39	+0.18 / 0.18	-0.04 / 0.39	-0.11 / 0.53
	ETHICS	-0.60 / 4.58	+0.57 / 4.17	+0.25 / 4.61	-0.65 / 5.01
	Safety	-6.22 / 11.05	-3.32 / 7.84	-7.05 / 11.00	-12.40 / 17.02
	SST-2	-19.90 / 23.08	-1.20 / 2.24	-7.97 / 10.21	-8.42 / 10.80

C.4 Model-stratified GEE analysis

We additionally test whether validation correctness varies systematically across persona values using model-stratified generalized estimating equations (GEE) (Liang & Zeger, 1986), accounting for repeated persona observations from the same underlying task item.

For each model, Benjamini–Hochberg correction is applied across its 20 task–axis persona-effect tests. Across the resulting 60 settings, 27 are significant after correction, including 25/36 ETHICS, Safety, and SST-2 settings but only 2/24 ARC settings.

For each setting, we summarize effect magnitude as $100[\max_p \widehat{P}(\text{correct} \mid p) - \min_p \widehat{P}(\text{correct} \mid p)]$, the difference between the highest and lowest GEE-adjusted correctness probabilities across persona values. This range captures value-specific behavioral variation within an axis, while * indicates whether the overall persona-value effect remains significant after within-model multiple-testing correction.

Table 22: **GEE-adjusted persona-effect ranges by model, task, and axis.** Values are highest-minus-lowest adjusted correctness probabilities in percentage points. * denotes significance after Benjamini–Hochberg correction across the 20 task–axis tests within each model.

Model	Task	Emotion	Gender	Race	Religion
Llama-8B	ARC-Challenge	0.67	0.00	0.67	1.34
	ARC-Easy	0.70	0.35	0.35	0.53
	ETHICS	3.35*	0.26	0.75	1.31*
	Safety	4.01*	0.56	1.76*	1.76*
	SST-2	1.95	0.11	2.06	1.83
Llama-3B	ARC-Challenge	1.67	0.67	1.67	1.34
	ARC-Easy	0.88	0.88*	0.70	0.70
	ETHICS	1.88*	0.57*	0.88*	1.11*
	Safety	4.39*	0.69	4.14*	9.97*
	SST-2	16.86*	0.23	2.06	4.47*
Qwen-7B	ARC-Challenge	1.34*	0.00	1.00	1.00
	ARC-Easy	0.35	0.00	0.35	0.53
	ETHICS	3.47*	0.77*	0.57	1.26*
	Safety	20.00*	1.38*	7.02*	14.86*
	SST-2	40.14*	1.49*	14.68*	17.09*

Table 22 reports the adjusted ranges for every setting. The GEE analysis confirms that persona effects are concentrated rather than uniform. ARC ranges remain at most 1.67 pp, and only two ARC settings are significant (Llama-3B ARC-Easy under Gender and Qwen-7B ARC-Challenge under Emotion). Larger effects appear in ETHICS, Safety, and SST-2, with the widest ranges for Qwen-7B on SST-2 and Safety under Emotion (40.14 and 20.00 pp) and for Llama-3B SST-2 under Emotion (16.86 pp). The number of significant settings also differs across models: 12/20 for Qwen-7B, 10/20 for Llama-3B, and 5/20 for Llama-8B. Emotion yields the largest range in most model–task combinations, whereas Gender ranges remain below 1.5 pp even when significant.

Summary. The training-split persona scans and independent validation-split behavioral statistics show a consistent qualitative pattern. ARC is comparatively stable, whereas ETHICS, Safety, and SST-2 exhibit greater persona-conditioned variation. At the same time, the magnitude and direction of the effect vary substantially across models, persona axes, and individual persona values. The model–task–axis setting is therefore the natural unit for subsequent circuit, functional, and intervention analyses.

D Original and Reverse Circuit Atlases

Table 23 provides the model–task breakdown underlying the main-text structural comparison, while Table 24 aggregates the same results by task. Across both views, bidirectional overlap is consistently concentrated in the shared component K rather than the remainder R.

Table 23: **Original–Reverse structural overlap by model and task.** Values are means across the four persona axes.

Model	Task	Axes	Full J	Shared K J	Remainder R J	$\Delta(K-R)$	$K > R$
Llama-8B	ARC-Challenge	4	0.361	0.625	0.128	0.497	4/4
Llama-8B	ARC-Easy	4	0.289	0.267	0.122	0.144	4/4
Llama-8B	ETHICS	4	0.281	0.824	0.071	0.753	4/4
Llama-8B	Safety	4	0.378	0.857	0.125	0.732	4/4
Llama-8B	SST-2	4	0.313	0.765	0.093	0.672	4/4
Llama-3B	ARC-Challenge	4	0.248	0.545	0.059	0.486	4/4
Llama-3B	ARC-Easy	4	0.339	0.769	0.108	0.662	4/4
Llama-3B	ETHICS	4	0.361	0.800	0.144	0.656	4/4
Llama-3B	Safety	4	0.434	0.632	0.110	0.522	4/4
Llama-3B	SST-2	4	0.324	0.786	0.074	0.712	4/4
Qwen-7B	ARC-Challenge	4	0.243	0.833	0.060	0.774	4/4
Qwen-7B	ARC-Easy	4	0.216	0.286	0.120	0.166	4/4
Qwen-7B	ETHICS	4	0.304	0.833	0.059	0.775	4/4
Qwen-7B	Safety	4	0.281	0.929	0.103	0.825	4/4
Qwen-7B	SST-2	4	0.269	0.769	0.103	0.666	4/4

The preference for shared-component recurrence is present in every model–task combination and every individual axis: each model–task row has $K > R$ for all four axes. The magnitude varies across tasks, with particularly strong shared-component agreement in ETHICS, Safety, and SST-2, while ARC-Easy shows the weakest shared overlap. These task-level differences do not alter the overall pattern that bidirectional agreement is concentrated substantially more strongly in K than in R.

Table 24: **Original–Reverse Jaccard similarity by task.** Values are means across the three models and four persona axes.

Task	Full Jaccard	K Jaccard	R Jaccard	$\Delta(K-R)$
ARC-Challenge	.284	.668	.082	.586
ARC-Easy	.281	.441	.117	.324
ETHICS	.315	.819	.091	.728
Safety	.364	.806	.113	.693
SST-2	.302	.773	.090	.683

E INTERVENTION DETAILS

E.1 PAIRED-OUTPUT INTERVENTION SUMMARY

This subsection reports results for the canonical Original-circuit K/R intervention using the selected setting-specific (α, β) coefficients. Table 25 reports paired-output outcomes across the 33 reliable settings. The intervention repairs 5,097 persona-conditioned predictions and degrades 1,163, a ratio of about 4.4 to 1, and McNemar tests are significant in 29 settings. The gain in persona-sensitive accuracy is similar for Llama-8B and Llama-3B (+10.24 and +10.13 pp) and largest for Qwen-7B (+14.04 pp). Table 26 places this gain alongside the other evaluation subsets for the same Original-circuit intervention: pooled accuracy on the all-correct subset U changes by only -0.31 pp, while accuracy on the all-wrong subset W increases by 5.18 pp.

Table 25: **Paired-output outcomes for the canonical Original-circuit K/R intervention across the 33 reliable settings.** Repairs and harms count persona-conditioned predictions corrected or degraded by the intervention.

Model	Reliable settings	McNemar sig.	Repairs	Harms	ΔAcc.
Llama-8B	11	9	1,050	333	+10.24 pp
Llama-3B	11	10	1,495	452	+10.13 pp
Qwen-7B	11	10	2,552	378	+14.04 pp
Overall	**33**	**29**	**5,097**	**1,163**	**+12.00 pp**

While Table 25 focuses on paired repair and harm within the persona-sensitive subset B, it does not show how the same intervention affects examples outside that target subset. We therefore additionally report pooled accuracy changes for B, the originally all-correct subset U, and the all-wrong subset W to characterize the intervention's broader behavioral effect.

Table 26: **Additional accuracy-change diagnostics for the canonical Original-circuit K/R intervention.** Results are pooled over the 33 reliable settings.

Subset	Pooled accuracy change
Persona-sensitive (B)	+12.00 pp
All-correct (U)	-0.31 pp
All-wrong (W)	+5.18 pp

All-wrong sanity analysis. The all-wrong subset W serves as a capability sanity check for the canonical Original-circuit K/R intervention: these examples are answered incorrectly under every persona value before intervention, so they do not exhibit the persona-dependent correct–wrong variation targeted by the intervention. Table 27 reports outcomes across all 33 reliable settings. After intervention, 88.84% of all-wrong examples remain wrong under every persona, 9.24% become correct under some persona values, and 1.92% become correct under all persona values. Thus, although the intervention can recover some examples outside the persona-sensitive subset, the large majority of originally all-wrong examples remain unsolved.

Table 27: All-wrong sample-state outcomes for the canonical Original-circuit K/R intervention across all 33 reliable settings. Percentages are pooled from exact sample counts.

Model	Settings	n_W	Still wrong	Partial	All recovered
Llama-8B	11	1,809	93.20	5.75	1.05
Llama-3B	11	2,128	90.93	7.57	1.50
Qwen-7B	11	2,418	83.75	13.32	2.94
Overall	**33**	**6,355**	**88.84**	**9.24**	**1.92**

Per-setting McNemar tests. Table 28 reports the paired McNemar tests underlying the aggregate significance counts for the canonical Original-circuit K/R intervention in Table 25. Repaired and harmed predictions form the discordant pairs; significance is assessed using the raw two-sided McNemar p-value at $p < 0.05$.

Table 28: **Per-setting McNemar tests for the canonical Original-circuit signed K/R intervention.** Repaired and Harmed are the discordant paired outcomes on the persona-sensitive subset B. $\Delta\mathrm{Acc}_B$ is the corresponding accuracy change.

Model	Task–axis	Repaired	Harmed	$\Delta\mathrm{Acc}_B$ (pp)	Raw p
Llama-8B	Safety/emotion	385	51	+31.87	2.95×10^{-57}
Llama-8B	Safety/gender	15	5	+20.00	4.42×10^{-2}
Llama-8B	Safety/race	53	7	+26.74	6.27×10^{-9}
Llama-8B	Safety/religion	134	36	+23.90	1.01×10^{-13}
Llama-8B	ETHICS/emotion	257	136	+4.44	1.42×10^{-9}
Llama-8B	ETHICS/gender	9	10	-0.81	1.0000
Llama-8B	ETHICS/race	69	36	+6.60	1.80×10^{-3}
Llama-8B	ETHICS/religion	74	33	+3.96	1.00×10^{-4}
Llama-8B	SST-2/emotion	25	11	+2.57	3.03×10^{-2}
Llama-8B	SST-2/race	16	4	+7.89	1.39×10^{-2}
Llama-8B	SST-2/religion	13	4	+3.75	5.23×10^{-2}
Llama-3B	Safety/emotion	258	48	+22.06	6.67×10^{-33}
Llama-3B	Safety/gender	20	2	+27.27	3.00×10^{-4}
Llama-3B	Safety/race	121	25	+24.74	3.77×10^{-15}
Llama-3B	Safety/religion	222	15	+16.43	7.79×10^{-41}
Llama-3B	ETHICS/emotion	280	157	+4.26	5.35×10^{-9}
Llama-3B	ETHICS/gender	24	7	+15.45	4.10×10^{-3}
Llama-3B	ETHICS/race	82	54	+3.72	2.06×10^{-2}
Llama-3B	ETHICS/religion	103	52	+4.49	5.92×10^{-5}
Llama-3B	SST-2/emotion	257	64	+8.87	8.53×10^{-27}
Llama-3B	SST-2/race	12	14	-0.93	0.8445
Llama-3B	SST-2/religion	116	14	+28.73	8.13×10^{-19}
Qwen-7B	Safety/emotion	735	19	+22.43	1.80×10^{-149}
Qwen-7B	Safety/gender	35	3	+28.57	4.93×10^{-7}
Qwen-7B	Safety/race	270	24	+30.45	2.57×10^{-46}
Qwen-7B	Safety/religion	207	37	+8.33	2.79×10^{-27}
Qwen-7B	ETHICS/emotion	541	198	+13.03	2.70×10^{-36}
Qwen-7B	ETHICS/gender	14	5	+7.38	6.65×10^{-2}
Qwen-7B	ETHICS/race	64	23	+8.33	1.80×10^{-5}
Qwen-7B	ETHICS/religion	55	24	+2.52	7.00×10^{-4}
Qwen-7B	SST-2/emotion	355	20	+9.97	1.16×10^{-66}
Qwen-7B	SST-2/race	107	10	+16.96	6.98×10^{-19}
Qwen-7B	SST-2/religion	169	15	+16.65	1.66×10^{-29}

E.2 Selected signed coefficients for the canonical Original-circuit intervention

Tables 29, 30, and 31 report the coefficients selected for the canonical Original-circuit K/R intervention in each of the 33 reliable model–task–axis settings used in the primary intervention analysis. These coefficients are selected from the setting-specific signed α, β grid using the objective in Appendix B. The matched-coefficient random controls reuse these canonical coefficients while changing only the intervened heads.

The selected coefficients vary substantially across settings in both sign and magnitude, so no single intervention direction or strength is optimal across models, tasks, and axes. The clearest regularity occurs for Safety, where all 12 settings select a negative shared-head coefficient ($\beta < 0$), whereas ETHICS and SST-2 select both positive and negative values. Safety also yields the highest repair rates (SD up to 83.21%) and the largest weighted score for every model, while all-correct preservation remains at least 95.18% in every setting. Five settings, four of them in ETHICS, have negative weighted scores: Llama-8B ETHICS–Gender and ETHICS–Race, Llama-3B ETHICS–Gender and ETHICS–Race, and Llama-3B SST-2–Race. In these cases, the selected intervention does not improve the weighted objective relative to leaving the original activations unchanged.

Table 29: Selected signed intervention settings for Llama-8B. SD, BC, BR, UP, UIB, and UC are percentages; Score is the weighted adaptive score.

Task	Axis	n_B	n_U	α	β	SD	BC	BR	UP	UIB	UC	Score
ETHICS	Emotion	341	2252	+0.75	+1.00	15.25	4.11	80.65	98.85	1.15	0.00	+0.463
ETHICS	Gender	62	2456	+0.25	+0.50	12.90	14.52	72.58	99.80	0.20	0.00	-0.238
ETHICS	Race	125	2391	+0.25	+0.50	14.40	4.80	80.80	99.41	0.59	0.00	-0.079
ETHICS	Religion	207	2344	+0.00	+0.25	11.11	6.28	82.61	99.74	0.26	0.00	+0.157
Safety	Emotion	131	1425	+0.25	-1.00	83.21	6.87	9.92	99.16	0.77	0.07	+5.591
Safety	Gender	25	1518	-1.00	-0.25	60.00	20.00	20.00	99.80	0.20	0.00	+0.454
Safety	Race	43	1492	-0.75	-0.25	69.77	6.98	23.26	99.73	0.20	0.07	+1.433
Safety	Religion	82	1469	+0.25	-0.75	74.39	13.41	12.20	99.32	0.68	0.00	+2.579
SST-2	Emotion	68	765	-1.00	-1.00	16.18	2.94	80.88	99.74	0.26	0.00	+0.840
SST-2	Race	38	793	+0.00	-0.75	18.42	0.00	81.58	99.87	0.13	0.00	+0.722
SST-2	Religion	48	782	+0.50	+0.25	8.33	0.00	91.67	99.87	0.13	0.00	+0.361

Table 30: Selected signed intervention settings for Llama-3B. SD, BC, BR, UP, UIB, and UC are percentages; Score is the weighted adaptive score.

Task	Axis	n_B	n_U	α	β	SD	BC	BR	UP	UIB	UC	Score
ETHICS	Emotion	361	2168	-1.00	-0.25	12.19	6.09	81.72	99.12	0.88	0.00	+0.119
ETHICS	Gender	55	2345	-0.25	+0.25	36.36	14.55	49.09	99.32	0.55	0.13	-0.292
ETHICS	Race	188	2268	+0.00	+0.25	9.04	7.45	83.51	98.99	0.97	0.04	-0.855
ETHICS	Religion	227	2250	+0.00	+0.25	17.18	3.52	79.30	99.33	0.67	0.00	+0.646
Safety	Emotion	119	1446	+0.75	-0.50	77.31	5.04	17.65	99.38	0.62	0.00	+4.920
Safety	Gender	33	1516	+0.00	-0.25	60.61	6.06	33.33	99.67	0.13	0.20	+0.646
Safety	Race	97	1454	+0.00	-0.50	68.04	9.28	22.68	99.52	0.48	0.00	+3.224
Safety	Religion	252	1292	+0.00	-1.00	37.30	1.59	61.11	99.69	0.31	0.00	+5.570
SST-2	Emotion	272	581	+1.00	+0.50	24.26	0.74	75.00	95.18	4.82	0.00	+4.220
SST-2	Race	54	761	+1.00	+0.25	7.41	3.70	88.89	99.61	0.39	0.00	-0.123
SST-2	Religion	71	728	+1.00	+0.50	61.97	7.04	30.99	97.94	1.79	0.27	+2.753

Table 31: Selected signed intervention settings for Qwen-7B. SD, BC, BR, UP, UIB, and UC are percentages; Score is the weighted adaptive score.

Task	Axis	n_B	n_U	α	β	SD	BC	BR	UP	UIB	UC	Score
ETHICS	Emotion	329	2109	-1.00	+1.00	36.17	8.81	55.02	97.01	2.89	0.09	+1.025
ETHICS	Gender	61	2304	-0.50	-0.75	21.31	6.56	72.13	99.87	0.09	0.04	+0.211
ETHICS	Race	123	2249	+0.25	-0.50	16.26	4.88	78.86	99.64	0.36	0.00	+0.253
ETHICS	Religion	246	2169	+0.50	+0.25	7.32	1.22	91.46	99.35	0.65	0.00	+0.041
Safety	Emotion	399	1078	+0.50	-1.00	45.61	1.00	53.38	99.26	0.74	0.00	+11.510
Safety	Gender	56	1333	+0.00	-1.00	62.50	5.36	32.14	99.40	0.45	0.15	+1.584
Safety	Race	202	1196	-1.00	-1.00	62.87	3.47	33.66	99.67	0.25	0.08	+8.226
Safety	Religion	408	1007	-0.25	-1.00	13.24	1.96	84.80	97.91	2.09	0.00	+1.767
SST-2	Emotion	420	432	-0.50	+1.00	14.52	0.00	85.48	95.83	4.17	0.00	+5.047
SST-2	Race	143	659	+1.00	+1.00	39.16	0.70	60.14	99.85	0.15	0.00	+6.733
SST-2	Religion	185	646	+1.00	+1.00	29.73	1.08	69.19	99.23	0.77	0.00	+5.776

E.3 Matched-coefficient causal controls

For all 33 reliable settings, random-any and layer-matched random controls use the same setting-specific α, β selected for the canonical Original K/R intervention; only head selection changes. Each random control uses 10 independently sampled head sets per setting. The reported comparison therefore tests whether the canonical effect depends on the discovered head structure while holding intervention strength fixed.

E.4 Original, Reverse, and Bidirectional Intersection

Table 32 reports the complete model-level comparison underlying the main-text bidirectional-intervention analysis. The bidirectional intersection retains repair and preservation in the same general range as the corresponding Original and Reverse circuits while using substantially fewer intervened heads.

Table 32: **Intervention outcomes for Original, Reverse, and bidirectional Intersection circuits.** Heads is the mean number of intervened heads; Repair, BC, and UP denote successful repair, persona-sensitive collapse, and preservation of all-correct states, respectively.

Model	Circuit	Settings	Heads	Repair (%)	BC (%)	UP (%)
Llama-8B	Original	11	50.91	29.57	6.84	99.50
	Reverse	11	42.64	29.23	7.02	99.24
	Intersection	11	22.36	29.74	7.09	99.53
Llama-3B	Original	11	35.55	30.71	5.21	99.13
	Reverse	11	36.64	33.07	6.68	98.89
	Intersection	11	19.18	29.90	4.40	99.14
Qwen-7B	Original	11	44.55	28.77	2.60	98.99
	Reverse	11	40.55	24.08	3.34	99.10
	Intersection	11	18.91	26.67	2.92	99.13

F Additional Functional Analysis

F.1 QK/value decomposition of persona effects

To distinguish whether persona context affects a head through attention routing or through the information carried by its value vectors, we analyze paired persona-conditioned runs A and B at the decision position. Let a_{ij}^A and a_{ij}^B denote attention weights from the decision token i to source token j, and let v_{ij}^A and v_{ij}^B denote the corresponding value vectors. Let P denote the persona-token region.

We first measure average attention mass to the persona region:

$$m_i^P = \frac{1}{2}\left(\sum_{j\in P} a_{ij}^A + \sum_{j\in P} a_{ij}^B\right). \tag{19}$$

Using midpoint quantities $\bar{a}_{ij} = (a_{ij}^A + a_{ij}^B)/2$ and $\bar{v}_{ij} = (v_{ij}^A + v_{ij}^B)/2$, we decompose the persona-conditioned output difference into a value-content contribution

$$C_i = \sum_{j\in P} \bar{a}_{ij}\left(v_{ij}^A - v_{ij}^B\right), \tag{20}$$

and an attention-routing contribution

$$W_i = \sum_{j\in P} \left(a_{ij}^A - a_{ij}^B\right)\bar{v}_{ij}. \tag{21}$$

We measure systematic effect magnitude by averaging effect vectors across examples before taking their norm, so that inconsistent directions cancel rather than accumulating through per-example magnitudes. We additionally project the content term C_i through the head output matrix W_O to test whether the persona-dependent content difference persists after writeout into the residual stream.

The analysis is complete for all 60 Original and 60 Reverse model–task–axis settings, giving 240 setting–role summaries. Across Original settings, persona-dependent content magnitude is larger in R than K in 55/60 settings, and routing magnitude is larger in R in 52/60 settings. Reverse discovery shows the same broad pattern, with $R > K$ in 51/60 content comparisons and 48/60 routing comparisons. Attention to persona tokens is less uniformly separated, with $R > K$ in 35/60 Original and 31/60 Reverse settings.

Table 33 reports task-level shared-to-remainder ratios, which reveal a graded rather than categorical separation. ARC-Challenge shows the clearest concentration of persona-dependent content and routing in R, and Original ARC-Easy shows a similarly strong separation. Reverse ARC-Easy is weaker, indicating some dependence on discovery direction. ETHICS occupies an intermediate regime: shared heads attend to persona tokens at approximately the same magnitude as remainder heads, while their content and routing effects remain less than half as large. Safety and SST-2 show

Table 33: **Shared-to-remainder ratios of persona-related QK/value effects by task.** Values below 1 indicate larger effects in R.

	Original			Reverse		
Task	m_K^P/m_R^P	C_K/C_R	W_K/W_R	m_K^P/m_R^P	C_K/C_R	W_K/W_R
ARC-Challenge	.22	.10	.11	.34	.14	.15
ARC-Easy	.31	.12	.11	1.39	.71	.69
ETHICS	1.18	.45	.48	.99	.40	.46
Safety	1.49	.82	.87	1.33	.76	.87
SST-2	1.21	.68	.73	1.22	.59	.66

substantially stronger coupling within K, with shared-head content and routing effects approaching the magnitude observed in R.

Projection of the content term through W_O preserves the same qualitative pattern. Mean relative output retention is .985 for both Original and Reverse K, compared with .964 and .961 for the corresponding remainders, indicating that the task-dependent differences are already present in transmitted value content rather than being primarily created or erased during residual-stream writeout.

Because content-channel activity is detected in essentially all analyzed head instances and routing activity in approximately 95–98%, hard null-threshold labels classify nearly all heads as exhibiting coupled content-and-routing activity. We therefore use continuous effect magnitudes and K/R comparisons as the primary evidence rather than interpreting discrete mechanism labels.