FROM FACT OVERWRITING TO CAUSAL EDITING: KNOWLEDGE EVOLUTION VIA ON-POLICY SELF-DISTILLATION

Anonymous authors
Paper under double-blind review

ABSTRACT

While Knowledge Editing (KE) enables efficient updates, its dominant *Static Fact Overwriting* paradigm treats LLMs as discrete databases, forcibly injecting isolated facts. Clashing with un-evolved legacy priors, this triggers **Epistemic Dissonance**—a pathology where obsolete beliefs compel the model to explicitly negate the injected update. Idealized interventions reveal that this is a systemic paradigm limitation rather than mere algorithmic noise, with a zero-distortion stress test yielding a catastrophic 95.6% self-refutation rate. Given the causally driven nature of real-world knowledge, grounding updates in explicit causal narratives effectively collapses this conflict rate to just 6.6%, underscoring the imperative for **a paradigm shift toward Causal Editing**. To this end, we propose **CODE** (**C**ausal **O**n-policy **D**istillation for **E**diting), a two-stage causal editing framework that effectively integrates such causal logic into model parameters by coupling causal bootstrapping with asymmetric on-policy distillation. Experiments on LLaMA-3.1 and Qwen-2.5 show CODE suppresses self-refutation to 1.8% while securing robust multi-hop accuracy (up to 83.5%), with further probing demonstrating genuine causal internalization over surface memorization—elevating discrete fact overwriting into coherent, globally consistent knowledge evolution. Code is available here.

1 INTRODUCTION

While Large Language Models (LLMs) encode immense knowledge, their inherently static parameters struggle with the evolving real world, driving the rapid development of Knowledge Editing (KE) for efficient knowledge updates. Currently, the dominant KE paradigm is *Static Fact Overwriting* Fang et al. (2025); Meng et al. (2022b;a). By implicitly treating the LLM as a discrete key-value database, these methods forcibly modify targeted weight matrices to erase legacy facts and inject new ones, achieving superficially high recall rates on standard direct queries Rosati et al. (2024); Xie et al. (2025).




Figure 1: **Epistemic Dissonance in static fact overwriting.** The edited model (LLaMA-3.1-8B via AlphaEdit) initially retrieves the injected target (green). Yet, co-activated legacy priors (blue) trigger irreconcilable conflicts with the isolated update, forcing the model to explicitly negate its own claim and revert to the obsolete answer (red).

However, LLMs are not discrete databases; their parameters encode knowledge as deeply interwoven topological networks—representing macro-level semantic dependencies and logical associations among parametric beliefs Nishi et al. (2024); Lei & Cooper (2025); Zhang et al. (2026) rather than isolated lookup tables. Forcibly injecting an isolated fact abruptly disrupts these dependencies, triggering a severe coherence failure we expose as *Epistemic Dissonance* (Figure 2a): because static overwriting enforces only superficial memorization, co-activated legacy priors strongly conflict with the new update, forcing the model to negate its newly retrieved target and revert to obsolete facts (Figure 1). To isolate paradigm flaws from algorithmic optimization noise, we design

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 2: **Static Fact Overwriting vs. Causal Editing**. **(a) Static Fact Overwriting** injects an isolated fact without reconciling surrounding beliefs. During generation, un-evolved legacy priors strongly conflict with the new target, triggering *Epistemic Dissonance*. **(b) Causal Editing (Ours)** anchors the update within a causal transition. By bridging legacy history to the new state, the model autonomously deduces the updated fact, ensuring *Epistemic Consistency*.

an idealized injection intervention termed *Force-decode* as a diagnostic behavioral stress test. By using prefix constraints to compel an unedited model into target recall with zero parameter distortion, this intervention evaluates how pristine priors react to isolated facts. Counterintuitively, the unaltered model exhibits a catastrophic 95.6% self-refutation rate—empirically demonstrating that *injecting static facts without reconciling the surrounding belief network inevitably destabilizes internal reasoning.*

This structural failure stems from a fundamental reality: facts never exist in isolation, but are governed by causal dynamics. Just as human cognition assimilates new evidence by updating mental causal models rather than erasing prior memories Sloman & Sloman (2009); Gopnik & Wellman (2012), LLMs require an explanatory bridge—a causal scaffold that rationalizes the transition from legacy beliefs to the updated state. Empirically, supplying such a narrative during inference neutralizes internal conflicts, collapsing the self-refutation rate from 95.6% to 6.6%. By reconnecting the update to pre-trained priors, the model smoothly deduces the new fact and achieves *Epistemic Consistency*(Figure 2b). True knowledge integration thus cannot rely on overwriting isolated tokens, but requires evolving the internal *causal logic* that reconciles legacy beliefs with updated states, necessitating ***a paradigm shift from static Fact Overwriting to Causal Editing***.

Yet, relying on external narratives defeats the purpose of permanent model editing. To permanently encode such transition rationales into model parameters, we propose **CODE** (**C**ausal **O**n-policy **D**istillation for **E**diting). Recognizing that explicit causal grounding effectively neutralizes Epistemic Dissonance, we instantiate this scaffold-conditioned policy as an oracle Teacher. While the intuitive solution is to directly mimic its reasoning, standard offline distillation (*e.g.*, SFT) suffers from severe exposure bias during autonomous generation. To circumvent this, CODE internalizes the Teacher's reasoning via a novel two-stage *on-policy* framework. Specifically: (1) *Causal Bootstrapping* establishes a stable reasoning prior via SFT on high-confidence trajectories to prevent optimization collapse; and (2) *Causal Internalization* applies asymmetric on-policy distillation, minimizing the KL divergence to align an actively exploring closed-book Student with the open-book Teacher's distribution. This effectively incorporates the causal transition logic into the model's parametric reasoning pathways, empowering the model to autonomously deduce updated facts.

In summary, our main contributions are: (1) We expose *Epistemic Dissonance* as an inherent structural flaw of static Fact Overwriting via idealized interventions, motivating a necessary paradigm shift to *Causal Editing*. **(2)** We propose CODE, a causal editing framework that internalizes explicit transition logic directly into model parameters via causal bootstrapping and asymmetric on-policy distillation, suppressing Epistemic Dissonance and converting brittle fact overrides into durable *Epistemic Consistency*. **(3)** Extensive experiments on LLaMA-3.1 and Qwen-2.5 validate this shift: CODE compresses self-refutation to near-zero (down to 1.8%) while boosting multi-hop accuracy up to 83.5%, successfully transforming discrete fact injection into coherent knowledge evolution.




Figure 3: **The illusion of static overwriting and the causal remedy.** Self-refutation rates across representative overwriting baselines and the idealized Force-decode control group. While static isolated edits (●) inevitably induce severe self-refutation, grounding updates in explicit causal dynamics (⧫) effectively mitigates conflicts with entrenched legacy priors.

2 Epistemic Dissonance and the Causal Remedy

As established, the static fact overwriting paradigm fundamentally misaligns with parametric memory: forcibly injecting isolated facts risks disrupting the LLM's deeply interconnected reasoning pathways. To systematically quantify the structural conflicts precipitated by this misalignment, we evaluate representative fact overwriting methods—CaKE Yao et al. (2025), AlphaEdit Fang et al. (2025), MEMIT Meng et al. (2022b), AdaLoRA Zhang et al. (2023), and EMMET Gupta et al. (2024b)—on LLaMA-3.1-8B-Instruct Grattafiori et al. (2024) and Qwen-2.5-7B-Instruct Yang et al. (2024) using a subset of MQuAKE-CF-v2 Zhong et al. (2023). As Figure 3 reveals, this static paradigm inherently triggers systemic structural conflicts.

Observation of Epistemic Dissonance under Contextual Probing. Instead of seamless assimilation, fact overwriting frequently triggers *Epistemic Dissonance*: the model successfully retrieves the injected fact (Rome) but, subjected to the gravitational pull of obsolete priors, quickly negates it and reverts to the legacy fact (Paris; Figure 1). To quantify this "assertion-then-negation" pathology, we introduce the *Self-Refutation Rate (SRR)*, evaluated via an LLM-as-a-Judge Gu et al. (2024a). To isolate individual update effects, we evaluate SRR strictly on single-hop scenarios using a two-tier probing mechanism. While standard *Direct Queries* assess basic recall, models can easily mask latent epistemic conflicts via superficial memorization. To counter this, our second tier introduces an *Adversarial Contextual Probe*. By explicitly offering both legacy and target answers while prompting for subject elaboration, this probe forces the co-activation of un-evolved priors to unmask the underlying dissonance (see Appendix A for details).

Figure 3 reports the SRR under Direct Queries, Adversarial Probes, and their Combined union. While standard Direct Queries expose a moderate baseline of self-refutation (e.g., ranging from 4.1% to 29.3% on LLaMA-3.1), Adversarial Probes trigger a drastic surge in SRR across all baselines. By actively co-activating un-evolved legacy contexts, the adversarial setting exposes the severe reasoning instability of these edits, culminating in notably high Combined Failure rates (reaching up to 47.3% for AdaLoRA and near 30% for AlphaEdit). These findings empirically confirm that static fact overwriting yields merely an "illusion of success": it achieves surface-level recall, yet severely destabilizes the internal reasoning process by failing to reconcile un-evolved legacy priors.

Attribution of Failure via the Idealized Injection Intervention. Before devising a solution, we must resolve a fundamental question: is the observed Epistemic Dissonance merely an artifact of flawed optimization algorithms (*e.g.*, collateral damage to parameters during editing), or is it inherent to the static overwriting paradigm itself? To disentangle algorithmic optimization noise from intrinsic paradigm limitations, we introduce an Idealized Injection Intervention (*Force-decode*) as a diagnostic behavioral stress test. By explicitly prepending the target fact to the assistant's turn of an unedited model before autoregressive generation, we enforce 100% target recall with zero parametric distortion. Crucially, this design allows us to directly observe how untouched pre-trained priors react when the model is coerced to assimilate newly overwritten facts without optimization interference.

Counterintuitively, Force-decode exhibits the most catastrophic self-refutation, peaking at an overwhelming 95.6% on Qwen-2.5-7B-Instruct (Figure 3). Forced to assimilate an isolated fact, the




Figure 4: **Overview of the CODE framework.** CODE bridges static overwriting and knowledge evolution via a two-stage process. (1) *Causal Bootstrapping*: An open-book Teacher Oracle ($\pi_{\mathcal{T}}$, frozen) curates reasoning trajectories to initialize the closed-book Student (π_θ, trainable) via SFT. (2) *Causal Internalization*: An asymmetric on-policy distillation minimizes the KL divergence to align the actively exploring Student with the Teacher's conditional distribution, thereby internalizing the causal transition logic into the model's parameters.

pristine base model violently contradicts itself. This empirically indicates that Epistemic Dissonance is not an optimization artifact, but a systemic flaw of the fact-overwriting paradigm: *the un-evolved pre-trained priors inherently repel isolated facts, rendering any algorithmic refinements to static overwriting highly limited* (see Appendix A.2 for extended discussion).

Mitigating Structural Conflict via Explicit Causal Dynamics. In reality, knowledge updates are not isolated anomalies but causally driven transitions (*e.g.*, the Eiffel Tower being dismantled and moved to Rome due to a diplomatic agreement). Humans assimilate new realities by updating internal causal models rather than statically erasing facts Sloman & Sloman (2009); Gopnik & Wellman (2012). To achieve robust knowledge integration, artificial systems must adopt similar mechanisms Lake et al. (2017). Accordingly, we hypothesize that LLMs require a cognitive scaffold—an explicit causal narrative—to seamlessly reconcile updates with their entrenched parametric knowledge.[1]

Empirically validating this hypothesis, augmenting our probes with a synthetic causal context—detailing the logical transition behind the updated fact (Appendix A.4)—effectively neutralizes Epistemic Dissonance. This explicit grounding plummets the SRR to near zero across all baselines and slashes the Force-decode failure rate from 95.6% to 6.6% on Qwen-2.5 (Figure 3). This dramatic recovery demonstrates that pre-trained models can coherently assimilate new knowledge into their reasoning pathways when provided with a logical bridge. However, relying on external prompting defeats the core objective of permanent model editing. True knowledge integration therefore necessitates **a paradigm shift from static Fact Overwriting to Causal Editing**—incorporating such causal dynamics directly into the model's parameters for autonomous reasoning.

3 CODE: On-Policy Self-Distilled Causal Editing

As demonstrated in Section 2, explicitly providing a causal narrative effectively neutralizes Epistemic Dissonance, serving as an ideal *Teacher Oracle*. While the intuitive solution is to directly distill this oracle, standard offline distillation (e.g., SFT) falls fundamentally short. Cloning fixed trajectories induces exposure bias and creates a superficial encoding decoupled from the model's native autoregressive distribution Li et al. (2025a); Yang et al. (2025), allowing legacy priors to resurface during free-form generation. Authentic assimilation therefore demands an on-policy paradigm, forcing the model to actively explore its own reasoning trajectories, resolve conflicts with legacy priors, and functionally integrate the updated causal logic into its parameters.

Driven by these insights, we propose **CODE** (**C**ausal **O**n-policy **D**istillation for **E**diting), a novel two-stage framework that transforms explicit logical scaffolds into intrinsic parametric behaviors. As

[1]Here, "causal" broadly denotes an epistemic rationale that logically reconciles the knowledge transition rather than strictly physical or temporal events; see Appendix D for an extended discussion on scope and boundary conditions.

illustrated in Figure 4, CODE bridges static overwriting and cognitive evolution: it first establishes a stable reasoning prior via *Causal Bootstrapping*, and subsequently ensures *Causal Internalization* through an asymmetric on-policy distillation mechanism. This dual-layered approach coherently aligns updated knowledge with the model's native reasoning pathways.

Instantiating the Teacher Oracle via Causal Scaffolding. Formally, we define a knowledge edit as a transition $(s, r, o \to o')$, where the model updates its belief regarding subject s and relation r from the legacy object o to the target object o'. This target knowledge is elicited via a corresponding query q, which is strictly formulated as a single-hop question. We base our framework on the frozen pre-edit model, parameterized by θ_{pre}, and its corresponding policy $\pi_{\theta_{\text{pre}}}$.

To construct the *Teacher Oracle*, we augment $\pi_{\theta_{\text{pre}}}$ with an explicit cognitive scaffold—a causal narrative $\mathcal{N}$ detailing the underlying dynamics of this transition. We formally denote this open-book Teacher policy as $\pi_{\mathcal{T}}(\cdot \mid q) \triangleq \pi_{\theta_{\text{pre}}}(\cdot \mid q, \mathcal{N})$. Conversely, the active closed-book Student policy, parameterized by dynamically updated weights θ, is denoted as $\pi_\theta(\cdot \mid q)$. This explicit conditioning enables the Teacher $\pi_{\mathcal{T}}$ to bypass the gravitational pull of original parametric priors and generate dissonance-free reasoning trajectories, providing a robust, high-quality supervisory signal.

Causal Bootstrapping via Teacher Sampling. Directly initiating on-policy distillation from a naive pre-edit model often leads to optimization instability due to the severe distribution gap between the open-book Teacher and the closed-book Student. Recent studies highlight that a high overlap in top-k token distributions is a crucial prerequisite for effective on-policy learning Li et al. (2026). Accordingly, CODE first establishes a stable reasoning prior via Causal Bootstrapping.

For a given query q, we prompt the Teacher Oracle to generate a set of candidate reasoning trajectories $\mathcal{Z} = \{z_1, z_2, \ldots, z_K\} \sim \pi_{\mathcal{T}}(\cdot \mid q)$. However, not all generated trajectories are equally reliable for knowledge assimilation. To isolate the most logically coherent derivations, we score each candidate z_i using the length-normalized log-likelihood of generating the target answer o' Xiang & Tang (2025). This metric $r(z_i)$ assesses how effectively the intermediate thought process bridges the causal transition under the pre-edit model's prior:

$$r(z_i) = \frac{1}{|o'|} \sum_{j=1}^{|o'|} \log \pi_{\theta_{\text{pre}}}(o'_j \mid q, z_i, o'_{<j}). \tag{1}$$

We select the optimal reasoning trajectory $z^* = \arg\max_{z_i \in \mathcal{Z}} r(z_i)$ to construct a curated dataset $\mathcal{D}_{\text{boot}}$. Employing Low-Rank Adaptation (LoRA; Hu et al., 2022) for parameter efficiency, we perform Supervised Fine-Tuning (SFT) to optimize the student parameters θ (initialized from θ_{pre}) by minimizing the standard autoregressive loss over the concatenated sequence $y = [z^*, o']$:

$$\mathcal{L}_{\text{sft}}(\theta) = -\mathbb{E}_{(q,y)\sim\mathcal{D}_{\text{boot}}} \left[\sum_{t=1}^{|y|} \log \pi_\theta(y_t \mid q, y_{<t}) \right]. \tag{2}$$

The resulting parameters, denoted as θ_{sft}, successfully shift the student's initial distribution into the teacher's cognitive neighborhood, establishing the critical reasoning prior needed to anchor the subsequent on-policy phase.

Causal Internalization via Asymmetric Distillation. While Causal Bootstrapping initializes the reasoning policy, offline optimization along fixed trajectories cannot eliminate the exposure bias inherent to open-ended generation. To ensure the model autonomously activates this transition logic without runtime prompting, CODE employs an asymmetric on-policy distillation mechanism. Specifically, we establish an information bottleneck by pairing the open-book Teacher $\pi_{\mathcal{T}}$ (conditioned on scaffold $\mathcal{N}$) against the closed-book Student π_θ (initialized from θ_{sft}). For a given query q, the Student dynamically samples a reasoning rollout $y \sim \pi_\theta(\cdot \mid q)$, and we align the policies by minimizing the Forward KL divergence Kullback & Leibler (1951):

$$\mathcal{L}_{\text{int}}(\theta) = \mathbb{E}_{y\sim\pi_\theta(\cdot|q)} \left[\sum_{t=1}^{|y|} D_{\text{KL}}\left(\pi_{\mathcal{T}}(\cdot \mid q, y_{<t}) \parallel \pi_\theta(\cdot \mid q, y_{<t})\right) \right]. \tag{3}$$

By penalizing divergence from the scaffolded Teacher along the Student's own exploration paths, this objective compels the closed-book model to autonomously reconstruct the transition rationale. Consequently, the updated knowledge is internalized as durable parametric reasoning behavior rather than a brittle surface override.

Model	Method	MQuAKE-CF-v2								
		2-hop			3-hop			4-hop		
		H-Acc↑	M-Acc↑	SRR↓	H-Acc↑	M-Acc↑	SRR↓	H-Acc↑	M-Acc↑	SRR↓
LLaMA-3.1-8B-Ins	Pre-edited	20.3	1.5	-	30.4	0.5	-	19.7	2.5	-
	AdaLoRA	35.5	19.8	47.3	43.7	18.0	45.1	26.0	10.0	57.6
	MEMIT	36.5	10.3	24.2	40.4	9.0	25.9	32.8	3.5	40.8
	AlphaEdit	41.9	14.0	29.4	46.4	13.5	30.6	36.8	5.0	37.9
	EMMET	48.2	18.5	22.9	57.2	14.5	39.2	45.9	7.0	41.9
	WISE	33.4	35.0	19.3	29.9	14.5	20.0	17.9	7.5	30.8
	CODE	**85.2**	**67.0**	**6.5**	**85.5**	**59.0**	**11.9**	**84.1**	**61.0**	**8.6**
	CaKE *(w/ Augment)*	65.6	69.3	14.3	69.3	61.0	15.0	71.1	72.5	13.9
	CODE *(w/ Augment)*	**84.3**	**79.3**	**3.2**	**84.1**	**68.5**	**2.4**	**82.4**	**78.0**	**5.8**
Qwen-2.5-7B-Ins	Pre-edited	19.8	1.5	-	29.9	0.5	-	18.5	5.0	-
	AdaLoRA	29.8	9.0	29.2	34.4	6.5	33.8	21.6	8.0	42.0
	MEMIT	50.0	31.3	29.4	54.2	18.0	26.6	46.3	18.5	33.5
	AlphaEdit	33.8	31.3	30.8	36.4	20.0	36.4	19.8	13.5	44.7
	EMMET	44.4	34.0	25.9	54.1	18.5	42.0	40.6	19.0	37.7
	WISE	23.2	7.8	74.5	30.6	4.5	84.8	19.2	10.2	50.0
	CODE	**89.2**	**75.3**	**5.8**	**89.1**	**71.0**	**5.7**	**88.9**	**75.5**	**4.4**
	CaKE *(w/ Augment)*	84.4	**87.8**	28.6	83.8	**80.5**	45.1	83.9	**87.5**	32.1
	CODE *(w/ Augment)*	**89.8**	77.3	**2.2**	**91.6**	74.5	**1.8**	**90.0**	83.5	**3.6**

Table 1: **Counterfactual Knowledge Evolution on MQuAKE-CF-v2 (%).** Best results per block (w/ and w/o augmentation) are bolded. Unlike static overwriting baselines that suffer from severe self-refutation and poor multi-hop propagation, CODE reliably preserves reasoning chain coherence, achieving superior multi-hop accuracy with minimal epistemic dissonance (SRR).

4 Experiments

4.1 Experimental Setup

Datasets. We mainly utilize the multi-hop (2 to 4 hops) reasoning knowledge editing dataset MQuAKE Zhong et al. (2023). Within this suite, we target the challenging counterfactual subset (MQuAKE-CF-v2) to rigorously test knowledge assimilation against conflicting pre-trained priors, alongside the temporal subset (MQuAKE-T) to measure performance on plausible real-world updates.

Models and Baselines. We experiment on two instruction-tuned models: LLaMA-3.1-8B-Instruct Grattafiori et al. (2024) and Qwen-2.5-7B-Instruct Yang et al. (2024). We compare CODE against diverse static overwriting baselines, including parameter-efficient fine-tuning (AdaLoRA, Zhang et al., 2023), representative locate-and-edit methods (MEMIT, Meng et al., 2022b, EMMET, Gupta et al., 2024b, AlphaEdit, Fang et al., 2025), the routing-based method WISE Wang et al. (2024a), and the recent circuit-guided augmentation method, CaKE Yao et al. (2025).

Evaluation Metrics. To systematically assess epistemic consistency and portability on open-ended generative outputs Yang et al. (2025), we report three primary metrics: (1) Self-Refutation Rate (SRR) to quantify Epistemic Dissonance by detecting "assertion-then-negation" behaviors under both Direct and Adversarial Probes; (2) Hop-wise Accuracy (H-Acc) for factual accuracy at intermediate reasoning steps; and (3) Multi-hop Accuracy (M-Acc) to measure the successful propagation of updated knowledge across reasoning chains. Crucially, all metrics are quantified via DeepSeek-V4-Flash DeepSeek-AI (2026) as an LLM-as-a-Judge, mitigating the overestimation inherent in rigid token-matching. Further setup details and human-judge agreement are reported in Appendices A.7 and B.

4.2 Main Results

We evaluate CODE against static baselines across varying reasoning depths (Tables 1 and Appendix Table 10). To ensure a fair comparison with CaKE, which natively relies on multi-hop data augmentation, we evaluate it within a dedicated tier against an equivalently augmented configuration of CODE.

Robust Evolution on Counterfactual Knowledge. Unlike static overwriting paradigms that suffer from inherent logical incoherence, CODE simultaneously mitigates Epistemic Dissonance and enhances knowledge portability. As shown in Table 1, standard baselines exhibit elevated Self-Refutation Rates (SRR)—peaking at 57.6% for AdaLoRA—and generally struggle with multi-hop reasoning. In contrast, CODE strictly suppresses SRR to 4.4%–11.9% while boosting

Configuration	MQuAKE-CF-v2					
	LLaMA-3.1-8B-Ins			Qwen-2.5-7B-Ins		
	H-Acc↑	M-Acc↑	SRR↓	H-Acc↑	M-Acc↑	SRR↓
w/o Causal Scaffold	36.9	14.8	22.7	71.0	62.0	54.4
w/o Causal Internalization	20.7	5.0	21.3	27.9	11.0	11.1
w/o Causal Bootstrapping	10.9	12.0	**0.9**	26.1	31.0	45.4
Distill via Reverse KL	**88.0**	**68.3**	3.2	87.1	73.5	**4.7**
Full CODE (Forward KL)	85.2	67.0	6.5	**89.2**	**75.3**	5.8

Table 2: **Ablation Study of CODE (%).** Removing the causal scaffold or either training phase degrades accuracy and spikes SRR, whereas the framework is robust to the choice of KL divergence.

M-Acc up to 75.3% at 2-hop depths. Furthermore, when utilizing data augmentation to match CaKE, CODE demonstrates vastly superior epistemic consistency. Although CaKE achieves competitive surface-level accuracy, its SRR surges to a substantial 45.1% on Qwen-2.5. Augmented CODE overcomes this, securing robust multi-hop accuracy while firmly compressing SRR to a near-zero range (1.8%–5.8%). This consistency is not an artifact of retrieval disengagement: a joint four-way outcome breakdown shows that CODE converts 89.5% of all edits into stable successes, whereas baselines are instead dominated by retrieval failures (up to 88.1% for WISE) and post-retrieval self-refutation (44.7% for CaKE) (Appendix A.6). Crucially, scaling evaluations demonstrate that this epistemic consistency holds in larger parameter regimes (72.0% M-Acc, 5.0% SRR on Qwen-2.5-14B vs. CaKE's 59.7% SRR; Appendix C.1).

Generalization to Real-World State Dynamics. Beyond counterfactuals, CODE generalizes robustly to plausible real-world state updates on the temporal dataset (MQuAKE-T, Appendix Table 10). It secures up to 85.3% M-Acc while strictly minimizing the SRR to 0.5% across both models. In contrast, while static baselines occasionally achieve competitive recall, they universally trigger Epistemic Dissonance, with SRR surging up to 33.7%. This underscores CODE's capability to facilitate logically coherent and continuous knowledge evolution.


5 Further Analysis

Evaluating Causal Internalization. While the main results confirm that CODE effectively suppresses Epistemic Dissonance, a natural question remains: does the model genuinely internalize the transition logic, or does it merely memorize target answers and hallucinate arbitrary justifications? To answer this, we introduce *Rationale Alignment (RA)*. Evaluated by appending an explicit "Why?" request to queries, RA measures the rate at which the model autonomously reconstructs the intended transition logic. As Table 3 shows, CODE achieves near-perfect rationale reconstruction (>91%) on plausible real-world updates (MQuAKE-T). Even on synthetic counterfactuals (MQuAKE-CF-v2)—where injecting counter-intuitive facts naturally faces stronger inertia from pre-trained priors—Qwen-2.5 still sustains an impressive 83.3% RA at 4-hop depths. Such high alignment strongly challenges the superficial memorization hypothesis, demonstrating that CODE empowers models to reliably articulate the causal rationale behind new facts rather than confabulating ad-hoc explanations.

Model	MQuAKE-CF-v2			MQuAKE-T	
	2-hop	3-hop	4-hop	2-hop	3-hop
LLaMA-3.1-8B	70.3	77.3	66.0	91.3	93.8
Qwen-2.5-7B	86.5	85.1	83.3	96.8	98.8

Table 3: **Rationale Alignment (RA) of CODE (%).** The percentage of successful edits where the model correctly reconstructs the underlying transition logic.

Ablation Study. To isolate component contributions, we systematically ablate CODE on the 2-hop subset of MQuAKE-CF-v2 (Table 2). First, stripping away the explicit causal narrative from both the bootstrapping and internalization phases (*w/o Causal Scaffold*) reduces the framework to standard fact-based on-policy distillation, where the teacher is deprived of the causal scaffold, conditioned solely on the isolated target fact to supervise the student. Without this logical bridge, Epistemic Dissonance predictably resurfaces—with SRR spiking to 54.4% on Qwen-2.5—demonstrating that isolated facts cannot be safely internalized without evolving the underlying causal logic. Second, both training stages are strictly indispensable. Relying solely on offline learning (*w/o Internalization*) triggers severe exposure bias during autonomous generation, plummeting LLaMA-3.1's M-Acc to 5.0%; conversely,



(a) Scalability across batch sizes (M-Acc) **(b)** Per-edit training time (Qwen-2.5-7B)

Figure 5: **Scalability and efficiency in batch edits. (a)** CODE significantly outperforms static baselines, maintaining exceptional stability up to 90 simultaneous updates. **(b)** Larger batches amortize optimization overhead, reducing per-edit time by $\sim 10\times$ (569s $\rightarrow$ 55s) on a single RTX 4090.

skipping the initial SFT (*w/o Bootstrapping*) creates a massive student-teacher distribution gap, leading to optimization collapse. Finally, substituting Forward KL with Reverse KL yields highly comparable performance (e.g., 4.7% SRR on Qwen), confirming that our overarching asymmetric on-policy paradigm is fundamentally robust to the choice of statistical distance.

Sensitivity to Scaffold Quality and Fidelity. To evaluate CODE under non-ideal supervision, we examine its sensitivity to narrative length, retrieval noise, and rationale specificity across three scaffold variants on Qwen-2.5-7B (MQuAKE-CF-v2; Table 4): (1) *Compressed*, pruning 87.7% of words (from 334.9 to 41.3 words) to retain only the essential logical core; (2) *Noisy*, appending two unrelated distractor articles to simulate retrieval noise; and (3) *Alternative*, substituting a distinct yet equally plausible causal logic to explain the transition.

Scaffold	H-Acc↑	M-Acc↑	SRR↓
Original	89.1	71.0	5.7
Compressed	88.7	70.5	13.1
Noisy	90.9	68.5	6.8
Alternative	90.4	69.5	6.8

Table 4: **Robustness under non-ideal and perturbed scaffolds**. Editing performance remains stable under compressed, noisy, or rationally substituted causal narratives.

As shown in Table 4, CODE exhibits strong resilience to scaffold degradation: drastic token compression barely degrades efficacy (70.5% M-Acc, 13.1% SRR), and performance similarly holds under distractor noise (68.5% M-Acc) and rationale substitution (69.5% M-Acc)—confirming that the underlying logical bridge, rather than supervisory token volume, governs causal assimilation. Crucially, the *Alternative* condition reveals striking *selective internalization* (Table 5): models faithfully reconstruct their trained rationale ($\geq$85.1% RA) while mutual cross-alignment plummets to $\leq$8.7% (e.g., 90.5% vs. 4.9%). This demonstrates that CODE genuinely internalizes whichever transition logic is supplied rather than relying on rigid memorization templates, underscoring both the fidelity of causal distillation and the imperative of verified source documents.

Scalability to Batch Edits. To evaluate scalability for massive real-world updates, we perform simultaneous batch edits (1 to 90) on the MQuAKE-T dataset (which contains a maximum of 96 non-overlapping edits), explicitly avoiding the contradictory data contamination inherent in counterfactuals Zhong et al. (2025). As illustrated in Figure 5(a), static baselines plateau at a low Multi-hop Accuracy ceiling. In contrast, CODE maintains a consistent 8%–25% absolute lead across all scales. Even at 90 simultaneous edits, CODE exhibits exceptional stability, demonstrating that internalized causal logic scales robustly without catastrophic interference.

Trained \ Probed	Original	Alternative
Original narrative	**85.1**	8.7
Alternative narrative	4.9	**90.5**

Table 5: **Fidelity of rationale internalization (RA %)**. Models faithfully reconstruct their assigned transition logic (diagonal) while showing near-zero alignment with the parallel, untrained narrative (off-diagonal).

Retention of General Capabilities and Edit Locality. An ideal knowledge editing framework must assimilate new facts without degrading the model's pre-trained capabilities Gupta et al. (2024a). To verify this, we evaluate general performance across standard benchmarks (MMLU, GSM8k, BBH, CSQA) following the intensive 90-edit batch update on MQuAKE-T. As reported in Table 6, while heavy data-augmentation methods like CaKE cause severe catastrophic forgetting (e.g., Qwen-2.5's MMLU plummets from 71.95% to 39.40%), CODE reliably preserves foundational knowledge alongside standard overwriting baselines. Furthermore, rather than merely avoiding degradation, CODE naturally reinforces the model's deductive pathways, yielding noticeable performance gains on

Method	LLaMA-3.1-8B-Ins				Qwen-2.5-7B-Ins			
	MMLU	GSM8k	BBH	CSQA	MMLU	GSM8k	BBH	CSQA
Pre-edited	65.15	75.06	47.04	75.43	71.95	83.55	54.77	80.18
AlphaEdit	65.04	75.06	48.12	75.43	**72.26**	84.08	53.91	**80.51**
MEMIT	65.12	74.30	48.14	75.02	70.16	84.61	54.54	80.43
EMMET	65.01	73.84	47.39	**75.92**	69.33	77.86	52.99	77.31
CaKE	62.95	63.23	44.43	65.19	39.40	73.01	48.94	78.05
CODE	64.84	**77.33**	**51.25**	75.51	71.67	**87.26**	**55.63**	80.43

Table 6: **General Capability Retention (%)** with red/green indicating drops/gains vs. pre-edit.

reasoning-heavy tasks such as GSM8k and BBH, thereby ensuring that knowledge evolution remains safe and non-destructive. We further evaluate fine-grained relational specificity on KnowEdit (Zhang et al., 2024) (Appendix C.3). Notably, CODE substantially eases the classic efficacy–locality trade-off by simultaneously securing dominant Edit Success ($>$88%), competitive Locality (60.4%–71.6%), and superior Portability (up to 66.7% vs. $\leq$30.5% for baselines), demonstrating robust inferential transfer without corrupting adjacent entity attributes.

Efficiency Analysis. To assess efficiency, we measure the total parameter optimization time required for Qwen-2.5-7B to converge to the accuracies reported in batch editing experiments (Figure 5a), using a single RTX 4090 GPU. As illustrated in Figure 5(b), the computational overhead required per edit decreases significantly with larger batch sizes. Consequently, the average processing time plummets from 569 seconds for an isolated edit to merely 55 seconds at a batch size of 90—a nearly 10$\times$ amortization gain. Crucially, this one-time editing cost trades upfront optimization for zero recurring test-time overhead ($\sim$36 prompt tokens, 53.7 ms per query). In contrast, inference-time scaffolding (RAG; Appendix C.4) converts the update into a compounding per-query tax, inflating input tokens by $\sim$128$\times$ and latency by nearly 7$\times$ alongside degraded multi-hop reasoning.

6 Related Work

Knowledge Editing (KE). KE methods Wang et al. (2024c); Zhang et al. (2024) primarily bifurcate into *parameter-preserving* approaches (*e.g.*, RAG, Zheng et al., 2023; external encoders, Li et al., 2025b)—which avoid weight alterations but introduce inference latency—and *parametric in-place editing* Mitchell et al. (2021); Meng et al. (2022a;b); Gupta et al. (2024b); Li et al. (2024). This latter category, encompassing both parameter-efficient fine-tuning (PEFT) and targeted "locate-then-edit" mechanisms, implicitly treats LLMs as discrete key-value stores. We characterize this overarching paradigm as *Static Fact Overwriting*: forcibly injecting isolated facts without evolving the surrounding causal logic. This fundamentally disrupts interwoven reasoning pathways, precipitating the Epistemic Dissonance our work resolves.

On-Policy Distillation. Traditional off-policy distillation suffers from exposure bias during open-ended generation Agarwal et al. (2024). On-Policy Distillation (OPD; Gu et al. 2024b; Lu & Lab 2025) mitigates this by aligning active student explorations with teacher distributions. To circumvent the massive computational overhead of external teachers, recent *On-Policy Self-Distillation* utilizes privileged contexts (*e.g.*, ground-truth rationales, Zhao et al. 2026; environment feedback, Hübotter et al. 2026) to construct a superior internal "Oracle Teacher." Building on this, CODE leverages explicit causal scaffolds as privileged context, employing asymmetric self-distillation to permanently incorporate causal transition dynamics into the model's parametric reasoning pathways.

7 Conclusion

This paper exposes the fundamental flaw of static Fact Overwriting: through an idealized injection stress test (*Force-decode*), we show that isolated fact injection inherently triggers Epistemic Dissonance by clashing with pre-trained knowledge priors rather than from optimization artifacts. To resolve this, we introduce CODE, pioneering a paradigm shift toward Causal Editing. By coupling causal bootstrapping with asymmetric on-policy distillation, CODE integrates explicit transition logic directly into model parameters. Extensive evaluations confirm that CODE neutralizes cognitive conflicts and secures robust multi-hop portability, ultimately transforming knowledge editing from discrete, conflict-prone fact injection into coherent knowledge evolution.

ETHICS STATEMENT

While our causal editing framework, CODE, significantly enhances LLM reliability by enabling logically consistent knowledge updates, it inherently presents dual-use risks. Because the framework effectively mitigates Epistemic Dissonance and makes edited facts logically coherent, it could be exploited by malicious actors to deeply embed highly convincing misinformation, propaganda, or harmful counterfactuals that mimic authentic reasoning. Consequently, the real-world deployment of such structural editing techniques necessitates rigorous human auditing of the update targets and robust alignment safeguards, ensuring that parametric knowledge evolution remains truthful, safe, and resistant to malicious manipulation.

REPRODUCIBILITY STATEMENT

All implementation details, evaluation protocols, and prompts required to reproduce our results are provided in Appendix A and Appendix B. Source code is available at `https://anonymous.4open.science/r/CODE-CD3E/`.

AI USE STATEMENT

In this work, generative AI was employed for polishing the language of the manuscript, as well as for synthesizing counterfactual causal narratives (Appendix A.4) and automated evaluation within our experimental protocol. Generative AI was not used for scientific ideation or experimental analysis.

REFERENCES

Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos Garea, Matthieu Geist, and Olivier Bachem. On-policy distillation of language models: Learning from self-generated mistakes. In *International Conference on Learning Representations*, volume 2024, pp. 21246–21263, 2024.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

DeepSeek-AI. Deepseek-v3 technical report, 2024. URL `https://arxiv.org/abs/2412.19437`.

DeepSeek-AI. Deepseek-v4: Towards highly efficient million-token context intelligence, 2026.

Junfeng Fang, Houcheng Jiang, Kun Wang, Yunshan Ma, Jie Shi, Xiang Wang, Xiangnan He, and Tat-Seng Chua. Alphaedit: Null-space constrained knowledge editing for language models. In *International Conference on Learning Representations*, volume 2025, pp. 16366–16396, 2025.

GLM-5 Team, Aohan Zeng, Xin Lv, Zhenyu Hou, Zhengxiao Du, et al. GLM-5: from vibe coding to agentic engineering, 2026. URL `https://arxiv.org/abs/2602.15763`.

Alison Gopnik and Henry M Wellman. Reconstructing constructivism: causal models, bayesian learning mechanisms, and the theory theory. *Psychological bulletin*, 138(6):1085, 2012.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, et al. A survey on llm-as-a-judge. *The Innovation*, 2024a.

Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. Minillm: Knowledge distillation of large language models. In *International Conference on Learning Representations*, volume 2024, pp. 32694–32717, 2024b.

Akshat Gupta, Anurag Rao, and Gopala Anumanchipalli. Model editing at scale leads to gradual and catastrophic forgetting. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 15202–15232, 2024a.

Akshat Gupta, Dev Sajnani, and Gopala Anumanchipalli. A unified framework for model editing. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 15403–15418, 2024b.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2020.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=nZeVKeeFYf9.

Jonas Hübotter, Frederike Lübeck, Lejs Behric, Anton Baumann, Marco Bagatella, Daniel Marta, Ido Hakimi, Idan Shenfeld, Thomas Kleine Buening, Carlos Guestrin, et al. Reinforcement learning via self-distillation. *arXiv preprint arXiv:2601.20802*, 2026.

Solomon Kullback and Richard A Leibler. On information and sufficiency. *The annals of mathematical statistics*, 22(1):79–86, 1951.

Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. *Behavioral and brain sciences*, 40:e253, 2017.

Ge Lei and Samuel J Cooper. Layerwise recall and the geometry of interwoven knowledge in llms. *arXiv preprint arXiv:2502.10871*, 2025.

Ruilin Li, Yibin Wang, Wenhong Zhu, Chenglin Li, Jinghao Zhang, Chenliang Li, Junchi Yan, and Jiaqi Wang. Etcon: Edit-then-consolidate for reliable knowledge editing. *arXiv preprint arXiv:2512.04753*, 2025a.

Shuaike Li, Kai Zhang, Qi Liu, and Enhong Chen. Mindbridge: Scalable and cross-model knowledge editing via memory-augmented modality. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 11999–12013, 2025b.

Xiaopeng Li, Shasha Li, Shezheng Song, Jing Yang, Jun Ma, and Jie Yu. Pmet: Precise model editing in a transformer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 18564–18572, 2024.

Yaxuan Li, Yuxin Zuo, Bingxiang He, Jinqian Zhang, Chaojun Xiao, Cheng Qian, Tianyu Yu, Huanang Gao, Wenkai Yang, Zhiyuan Liu, et al. Rethinking on-policy distillation of large language models: Phenomenology, mechanism, and recipe. *arXiv preprint arXiv:2604.13016*, 2026.

Wei Liu, Haomei Xu, Bingqing Liu, Zhiying Deng, Haozhao Wang, Jun Wang, Ruixuan Li, Yee Whye Teh, and Wee Sun Lee. Is model editing built on sand? revealing its illusory success and fragile foundation. *arXiv preprint arXiv:2510.00625*, 2025.

Kevin Lu and Thinking Machines Lab. On-policy distillation. *Thinking Machines Lab: Connectionism*, 2025. doi: 10.64434/tml.20251026. https://thinkingmachines.ai/blog/on-policy-distillation.

Xinbei Ma, Tianjie Ju, Jiyang Qiu, Zhuosheng Zhang, Hai Zhao, Lifeng Liu, and Yulong Wang. On the robustness of editing large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 16197–16216, 2024.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in gpt. *Advances in neural information processing systems*, 35:17359–17372, 2022a.

Kevin Meng, Arnab Sen Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. Mass-editing memory in a transformer. *arXiv preprint arXiv:2210.07229*, 2022b.

Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D Manning. Fast model editing at scale. *arXiv preprint arXiv:2110.11309*, 2021.

Kento Nishi, Rahul Ramesh, Maya Okawa, Mikail Khona, Hidenori Tanaka, and Ekdeep Singh Lubana. Representation shattering in transformers: A synthetic study with knowledge editing. *arXiv preprint arXiv:2410.17194*, 2024.

Domenic Rosati, Robie Gonzales, Jinkun Chen, Xuemin Yu, Yahya Kayani, Frank Rudzicz, and Hassan Sajjad. Long-form evaluation of model editing. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 3749–3780, 2024.

Lin Shi, Chiyu Ma, Wenhua Liang, Xingjian Diao, Weicheng Ma, and Soroush Vosoughi. Judging the judges: A systematic study of position bias in llm-as-a-judge. In *Proceedings of the 14th International Joint Conference on Natural Language Processing and the 4th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics*, pp. 292–314, 2025.

Steven Sloman and Steven A Sloman. *Causal models: How people think about the world and its alternatives*. Oxford University Press, 2009.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc Le, Ed Chi, Denny Zhou, et al. Challenging big-bench tasks and whether chain-of-thought can solve them. In *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 13003–13051, 2023.

Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. Commonsenseqa: A question answering challenge targeting commonsense knowledge. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4149–4158, 2019.

Peng Wang, Zexi Li, Ningyu Zhang, Ziwen Xu, Yunzhi Yao, Yong Jiang, Pengjun Xie, Fei Huang, and Huajun Chen. Wise: Rethinking the knowledge memory for lifelong model editing of large language models. *Advances in Neural Information Processing Systems*, 37:53764–53797, 2024a.

Peng Wang, Ningyu Zhang, Bozhong Tian, Zekun Xi, Yunzhi Yao, Ziwen Xu, Mengru Wang, Shengyu Mao, Xiaohan Wang, Siyuan Cheng, et al. Easyedit: An easy-to-use knowledge editing framework for large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, pp. 82–93, 2024b.

Song Wang, Yaochen Zhu, Haochen Liu, Zaiyi Zheng, Chen Chen, and Jundong Li. Knowledge editing for large language models: A survey. *ACM Computing Surveys*, 57(3):1–37, 2024c.

Yang Xiang and Buzhou Tang. Towards efficient cot distillation: Self-guided rationale selector for better performance with fewer rationales. 2025.

Jiakuan Xie, Pengfei Cao, Yubo Chen, Kang Liu, and Jun Zhao. Revealing the deceptiveness of knowledge editing: A mechanistic analysis of superficial editing. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 17756–17780, 2025.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, Jin Xu, Jingren Zhou, Jinze Bai, Jinzheng He, Junyang Lin, Kai Dang, Keming Lu, Keqin Chen, Kexin Yang, Mei Li, Mingfeng Xue, Na Ni, Pei Zhang, Peng Wang, Ru Peng, Rui Men, Ruize Gao, Runji Lin, Shijie Wang, Shuai Bai, Sinan Tan, Tianhang Zhu, Tianhao Li, Tianyu Liu, Wenbin Ge, Xiaodong Deng, Xiaohuan Zhou, Xingzhang Ren, Xinyu Zhang, Xipin Wei, Xuancheng Ren, Yang Fan, Yang Yao, Yichang Zhang, Yu Wan, Yunfei Chu, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zhihao Fan. Qwen2 technical report. *arXiv preprint arXiv:2407.10671*, 2024.

Wanli Yang, Fei Sun, Jiajun Tan, Xinyu Ma, Qi Cao, Dawei Yin, Huawei Shen, and Xueqi Cheng. The mirage of model editing: Revisiting evaluation in the wild. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15336–15354, 2025.

Yunzhi Yao, Jizhan Fang, Jia-Chen Gu, Ningyu Zhang, Shumin Deng, Huajun Chen, and Nanyun Peng. Cake: Circuit-aware editing enables generalizable knowledge learners. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 11377–11393, 2025.

Ningyu Zhang, Yunzhi Yao, Bozhong Tian, Peng Wang, Shumin Deng, Mengru Wang, Zekun Xi, Shengyu Mao, Jintian Zhang, Yuansheng Ni, et al. A comprehensive study of knowledge editing for large language models. *arXiv preprint arXiv:2401.01286*, 2024.

Ningyu Zhang, Yunzhi Yao, Jiaxin Qin, Haoming Xu, Yuqi Zhu, Zeping Yu, Mengru Wang, Yuqi Tang, Jia-Chen Gu, Shumin Deng, et al. Towards principled knowledge editing methods for large language model reasoning. *Nature Machine Intelligence*, pp. 1–12, 2026.

Qingru Zhang, Minshuo Chen, Alexander Bukharin, Nikos Karampatziakis, Pengcheng He, Yu Cheng, Weizhu Chen, and Tuo Zhao. Adalora: Adaptive budget allocation for parameter-efficient fine-tuning. *arXiv preprint arXiv:2303.10512*, 2023.

Siyan Zhao, Zhihui Xie, Mengchen Liu, Jing Huang, Guan Pang, Feiyu Chen, and Aditya Grover. Self-distilled reasoner: On-policy self-distillation for large language models. *arXiv preprint arXiv:2601.18734*, 2026.

Ce Zheng, Lei Li, Qingxiu Dong, Yuxuan Fan, Zhiyong Wu, Jingjing Xu, and Baobao Chang. Can we edit factual knowledge by in-context learning? In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 4862–4876, 2023.

Chujie Zheng, Hao Zhou, Fandong Meng, Jie Zhou, and Minlie Huang. Large language models are not robust multiple choice selectors. In *International Conference on Learning Representations*, volume 2024, pp. 19426–19454, 2024.

Shaochen Zhong, Yifan Louie Lu, Lize Shao, Bhargav Bhushanam, Xiaocong Du, Yixin Wan, Yucheng Shi, Daochen Zha, Yiwei Wang, Ninghao Liu, et al. Mquake-remastered: Multi-hop knowledge editing can only be advanced with reliable evaluations. In *International Conference on Learning Representations*, volume 2025, pp. 99708–99736, 2025.

Zexuan Zhong, Zhengxuan Wu, Christopher D Manning, Christopher Potts, and Danqi Chen. Mquake: Assessing knowledge editing in language models via multi-hop questions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 15686–15702, 2023.

A Detailed Settings for Contextual Probing and Evaluation

A.1 Adversarial Contextual Probe Construction

To rigorously evaluate whether an edited model has genuinely internalized the updated knowledge rather than relying on superficial memorization, we introduce the *Adversarial Contextual Probe*. This stress test forces the model to concurrently activate its legacy parametric priors alongside the target query, thereby exposing any latent structural collisions.

Specifically, the probe is structured as a multiple-choice question presenting both the legacy answer (o) and the target answer (o'). Crucially, the model is instructed to elaborate on the subject entity before making its selection. This requirement engages the surrounding semantic context, acting as a catalyst to unmask potential Epistemic Dissonance:

> **Question:** *[Target Query]*
> **Options:** (A) *[Legacy Answer]* (B) *[Target Answer]*
> **Instruction:** Tell me about *[Subject]* first, and then answer.

To mitigate evaluation artifacts such as positional or instructional biases Shi et al. (2025); Zheng et al. (2024), we generate multiple prompt variations for each edit by systematically swapping the order of the options (i.e., alternating o and o' between positions A and B) and the sequence of the instructions.

Note on Adversarial Testing. We note that explicitly co-activating legacy and target answers constitutes a highly adversarial prompting regime designed to test the limits of knowledge assimilation.

The purpose of this design is not to claim that static overwriting fails universally across all simple contexts, but rather to rigorously quantify the integration brittleness of the edits. By deliberately inducing epistemic tension, this stress test exposes an inherent reasoning vulnerability: while statically injected facts may survive isolated, direct queries, they lack the causal grounding required to withstand the gravitational pull of un-evolved legacy priors during complex reasoning.

A.2 Implementation of the Idealized Injection Intervention (Force-decode)

To operationalize the *Force-decode* intervention, we simulate an idealized superficial override using a pristine, unedited model ($\pi_{\theta_{\text{pre}}}$). Specifically, we deterministically constrain the initial output by appending a hard-coded prefix containing the target fact directly to the assistant's turn:

Assistant Prefix: The answer is *[Target Answer o']*.

Following this forced initialization, the model is permitted to autoregressively complete its generation under the exact same queries and probing conditions as the static editing baselines.

Conceptual Analysis: Force-decode as an Informative Stress Test. At their core, static overwriting methods optimize parameters to maximize the generation probability of a target answer o' given a specific query q. However, this paradigm predominantly focuses on coercing the isolated target emission, rarely accounting for how the model should structurally reconcile the subsequent reasoning rollout. One might intuitively argue that *Force-decode* is an imperfect proxy because it lacks the parameter-level "erasure" of legacy facts. Yet, recent empirical investigations reveal that static editing inherently encourages models to exploit shallow shortcuts rather than genuinely updating the underlying semantics Liu et al. (2025).

Consequently, rather than a direct mechanistic replica, *Force-decode* serves as an informative diagnostic stress test for this underlying tension. By bypassing parameter optimization noise and enforcing $P(o' \mid q) = 1$ via prefix constraints, it isolates the behavioral limit of fact overwriting: coercing target recall while leaving surrounding legacy priors un-evolved. This allows us to observe how pre-trained networks respond to isolated factual intrusions in the absence of optimization collateral damage.

If the severe Epistemic Dissonance observed in our baseline experiments were merely an artifact of flawed optimization (e.g., parametric distortion destroying generative capabilities), a pristine model—free from any weight alterations—should naturally condition on its own forced target emission and continue generating coherent, supportive reasoning.

Instead, we observe the exact opposite. As generation proceeds beyond the immediate prefix, the un-evolved legacy priors trigger a severe logical immune response, causing the model to explicitly negate its forced assertion and revert to obsolete knowledge. Rather than definitively invalidating all parameter-editing algorithms, this stress test highlights a fundamental boundary condition of the static paradigm: merely coercing a model to emit a target fact yields only brittle, surface-level assimilation. This fragility aligns perfectly with recent observations that statically edited models frequently degrade under generative stress Ma et al. (2024). It underscores that without explicitly evolving the surrounding causal pathways, injected knowledge remains a structurally isolated anomaly, inevitably overwhelmed by the robust inertia of the pre-trained network.

A.3 LLM-as-a-Judge Prompt for Self-Refutation Detection

To automatically detect Epistemic Dissonance in model generations, we employ an LLM-as-a-Judge framework. The judge evaluates whether a given response exhibits the characteristic "assertion-then-negation" pattern that defines self-refutation.

The judge is instructed to diagnose the response through a structured reasoning process and output a JSON object containing three binary fields: `assertion_of_target_new`, `explicit_negation_of_target_new`, and `final_submitted_answer_target_new`. Epistemic Dissonance is confirmed only when all three conditions are simultaneously satisfied: the model explicitly asserts the counterfactual target as true, subsequently negates its own assertion with explicit negation markers, and ultimately fails to re-commit to the target answer. The judge must distinguish

genuine dissonance from benign patterns such as rational rejection, harmonization, self-correction with recovery, pure repetition without negation. The complete prompt is shown in Figure 11.

A.4 Generation of the Explicit Causal Context (Cognitive Scaffold)

To empirically validate the mitigation of structural conflicts (Section 2) and subsequently instantiate the *Teacher Oracle* for our framework (Section 3), we synthesize an explicit causal narrative $\mathcal{N}$ for each knowledge edit $(s, r, o \to o')$. This narrative functions as a *cognitive scaffold*—an external context detailing the logical transition behind the updated fact—enabling the frozen base model to bypass the gravitational pull of its pre-trained priors and yield dissonance-free reasoning trajectories.

To ensure these narratives are contextually grounded, we first retrieve structured background knowledge for both the subject and the target object via the Wikidata API. By extracting salient properties, entity labels, and descriptions while filtering out noisy metadata, we firmly anchor the entity identities in accurate real-world contexts. Building upon this curated background, we prompt a state-of-the-art LLM (DeepSeek-V3, DeepSeek-AI 2024) to author a concise, synthetic news article. The generator is strictly instructed to establish the new answer o' as the prevailing reality, explicitly render the legacy answer o obsolete, and to invent a plausible causal mechanism for the transition (*e.g.*, a diplomatic agreement or scientific discovery) that minimizes semantic friction with existing entity profiles.

To guarantee the logical integrity of these scaffolds, each generated narrative undergoes a rigorous verification process via an LLM-as-a-Judge framework. The verifier systematically evaluates whether the text: (*i*) unambiguously asserts the new target fact; (*ii*) explicitly refutes the outdated prior; (*iii*) provides a coherent causal explanation; and (*iv*) avoids entity hallucination or semantic ambiguity. Narratives failing any of these criteria are dynamically regenerated until they pass. Ultimately, these verified causal narratives serve a dual purpose: they act as the explicit external prompts that neutralize Epistemic Dissonance in our pilot study, and they form the foundational dataset used to anchor the Teacher Oracle during CODE's Causal Bootstrapping and Internalization phases. The prompts used to generate and verify the causal narratives are shown in Figure 12 and 13.

Applicability to Real-World Knowledge Evolution. Synthesizing these narratives is an experimental necessity dictated by counterfactual benchmarks: datasets such as MQuAKE-CF consist of artificially fabricated updates for which no authentic source document exists, so synthesis is the only way to equip such counterfactuals with the transition logic they would naturally carry had they occurred. In practice, however, real-world knowledge evolution is inherently causal: genuine transitions arrive with rich documentation—news reports, press releases, or scientific publications—that explicitly details the rationale, and such authentic texts can directly serve as the scaffold $\mathcal{N}$, bypassing generation entirely. Moreover, CODE remains robust to compressed, noisy, or imperfect scaffolds (Table 4), further relaxing the quality requirements on real-world sources.

A.5 Calculation Details of the Self-Refutation Rate (SRR)

The LLM-as-a-Judge detector operates on individual model generations (one per prompt). In practice, each knowledge edit is evaluated through multiple prompts spanning direct hop-wise queries and adversarial contextual probes. To obtain a single Self-Refutation Rate for an edit, we aggregate instance-level judgments to the edit level with an `ANY` rule: if any generation produced for that edit is flagged as self-refuting, the edit is marked as self-refuting for the corresponding probe category.

We distinguish three probe families when reporting SRR. *Direct Queries* are the standard chain-of-thought prompts for each reasoning hop. *Adversarial Contextual Probes* are the multiple-choice probes above. *Combined* is the union of the two families: an edit counts as self-refuting if it self-refutes in either family. Unless otherwise specified, "SRR" in the main paper refers to `combined`.

The denominator restriction ensures that SRR measures genuine epistemic dissonance rather than mere retrieval failure. Crucially, to facilitate a fair comparison across different methods, we must isolate this metric from varying algorithmic edit success rates. Therefore, we include an edit in the SRR denominator only if the model successfully retrieves and asserts the new target fact under Direct Queries. Edits that completely fail to engage the new knowledge are excluded. This prevents methods with poor base editing efficacy from artificially underreporting their SRR, ensuring we evaluate structural conflicts exclusively on initially "successful" edits. We empirically validate the necessity of this restriction through a joint outcome breakdown in Appendix A.6.

Formally, for a probe category c, let $\mathcal{E}_c$ be the set of edits that (i) belong to the restricted denominator and (ii) have at least one self-refuting generation in category c. The Self-Refutation Rate is $\text{SRR}_c = |\mathcal{E}_c|/|\mathcal{D}|$, where $\mathcal{D}$ is the restricted denominator.

A.6 Joint Breakdown of Edit Outcomes

To complement the conditional SRR, we decompose every edit into four exhaustive, mutually exclusive outcomes via a prioritized cascade, using the same LLM-as-a-Judge verdicts: (*i*) *Retrieval Failure*—no direct hop-wise generation asserts the target fact; (*ii*) *Self-Refutation after Retrieval*—retrieval succeeds, but at least one generation (direct query or adversarial probe) exhibits assertion-then-negation; (*iii–iv*) for retrieved, non-self-refuting edits, *Wrong Final Answer* and *Stable Successful Edit* split the unit weight proportionally to the FAIL/PASS fractions of their hop-wise judgments. Each edit contributes exactly one unit across the four categories (rows sum to 100%), and renormalizing (*ii*) over non-(*i*) edits exactly recovers the conditional SRR of the main tables.

Method	Retr. Fail↓	SR after Retr.↓	Wrong Ans.↓	Stable Succ.↑	Cond. SRR↓
AdaLoRA	81.6	6.2	5.2	7.0	33.8
MEMIT	38.4	16.4	14.9	30.3	26.6
EMMET	35.1	27.3	12.0	25.6	42.0
AlphaEdit	51.4	17.7	11.2	19.7	36.4
WISE	88.1	10.1	1.2	0.6	84.8
CaKE	1.0	44.7	3.7	50.6	45.1
CODE (Ours)	**0.5**	**5.7**	4.3	**89.5**	**5.7**

Table 7: **Joint four-way breakdown of edit outcomes** (Qwen-2.5-7B, MQuAKE-CF-v2, %). The first four columns partition all edits into retrieval failure, self-refutation after retrieval, wrong final answer, and stable successful edit. The last column is the conditional SRR of the main tables.

Table 7 validates the conditional SRR design in two ways. First, a low *unconditional* self-refutation rate can mask disengagement: WISE and AdaLoRA retrieve the target in merely 12% and 18% of edits, so their superficially low unconditional rates (10.1% and 6.2%) reflect disengagement rather than integration; renormalized over retrieved edits, their conditional SRRs surge to 84.8% and 33.8%. Restricting the denominator is thus necessary to prevent retrieval failure from masquerading as low dissonance. Second, retrieval alone does not imply assimilation: CaKE retrieves almost as reliably as CODE (99.0% vs. 99.5%) yet self-refutes on 45.1% of retrieved edits, whereas CODE converts 89.5% of all edits into stable successes—by far the highest.

A.7 Human Validation of LLM-as-a-Judge Evaluations

To rigorously assess the fidelity of automated evaluation, we conducted a double-blind human agreement study on randomly sampled model outputs across three independent evaluators: our default judge DeepSeek-V4-Flash, alongside frontier models DeepSeek-V4-Pro (DeepSeek-AI, 2026) and GLM-5.2 (GLM-5 Team et al., 2026). We evaluate both core metrics: Self-Refutation Rate (SRR; identifying Epistemic Dissonance) and Rationale Alignment (RA; verifying whether the model reconstructs the intended transition logic). As summarized in Table 8, all judges demonstrate substantial to near-perfect alignment with human expert annotations.

Judge	Self-Refutation Detection			Rationale Alignment		
	Acc.	F1	κ	Acc.	F1	κ
DeepSeek-V4-Flash (default)	90.44	89.76	0.810	81.03	78.43	0.621
DeepSeek-V4-Pro	87.50	84.40	0.740	93.10	92.86	0.862
GLM-5.2	92.65	91.07	0.848	89.66	89.29	0.793

Table 8: **Judge agreement with human expert labels.** Accuracy and positive-class F1 are percentages; κ is Cohen's kappa.

For SRR, all judges exhibit high consistency ($\kappa \geq 0.74$), with the default judge capturing 100% of human-identified self-refutations (zero false negatives). Evaluating Rationale Alignment presents a more fine-grained semantic task; nevertheless, agreement remains strong across all evaluators ($\kappa \in [0.621, 0.862]$).

While the lightweight default judge yields a relatively lower agreement score ($\kappa = 0.621$) than frontier models, its confusion matrix (Table 9) reveals an asymmetric, conservative classification profile: it rejects 31.03% of valid human-verified rationales as false negatives, but falsely admits only 6.90% of invalid ones. This confirms that the default judge acts as a strict lower-bound estimator that penalizes minor semantic variations rather than permissively inflating alignment scores, thereby corroborating the trustworthiness of our main experimental findings.

Human label	Flash PASS	Flash FAIL
PASS	68.97	31.03
NON_PASS	6.90	93.10

Table 9: **Default judge on RA (%).** Row-normalized confusion matrix. PASS denotes alignment with the intended rationale.

B Experimental Setup and Implementation Details

Dataset Construction Details. In the MQuAKE benchmark Zhong et al. (2023), knowledge portability is tested by incorporating questions that span reasoning depths from 2 to 4 hops. To comprehensively evaluate the models' reasoning robustness, the targeted edited facts are strategically positioned at varying intermediate steps within these multi-hop reasoning chains, rather than solely at the beginning or the end. Furthermore, to enable our causal editing paradigm, we augmented every individual knowledge edit in the dataset with a specific causal transition narrative, synthesized following the generation pipeline detailed in Appendix A.4.

General Capability Benchmarks. To evaluate the retention of the model's general capabilities after knowledge editing, we employ several standard benchmarks across diverse domains: MMLU Hendrycks et al. (2020) for broad knowledge and multitask language understanding, GSM8k Cobbe et al. (2021) for multi-step mathematical problem-solving, BigBenchHard (BBH) Suzgun et al. (2023) for challenging reasoning tasks, and CommonsenseQA (CSQA) Talmor et al. (2019) for commonsense reasoning.

Generation Setup and Prompting. To explicitly elicit the models' latent reasoning capabilities during evaluation and avoid superficial single-token answers, we prompt open-ended generation by appending the phrase *"Let's think step by step."* to all test queries.

Metric Calculation Details. To rigorously quantify Epistemic Dissonance, the Self-Refutation Rate (SRR) is calculated as the *Combined Failure* rate. Specifically, a generation is flagged as experiencing a structural conflict if the pathological "assertion-then-negation" behavior is detected under *either* standard Direct Queries *or* Adversarial Contextual Probes. For factual correctness, we report Multi-hop Accuracy (M-Acc) and Hop-wise Accuracy (H-Acc). M-Acc evaluates whether the model correctly answers the final multi-hop question, while H-Acc assesses whether the model accurately articulates the necessary intermediate facts at every individual step of the reasoning chain. Following the standard MQuAKE evaluation protocols Zhong et al. (2023), a multi-hop prediction is deemed correct if the model successfully answers any one of the three paraphrased multi-hop instructions provided for a single test instance.

Given the open-ended nature of chain-of-thought outputs, exact string matching often leads to evaluation errors. Therefore, we utilize an LLM-as-a-Judge to semantically evaluate whether the model's final answer matches the gold references. The judge is instructed to strictly adhere to the provided counterfactual facts and explicitly ignore conflicting real-world knowledge. The complete prompt is detailed in Figure 10.

Implementation and Hyperparameter Details. For the baseline methods, we implement AdaLoRA, MEMIT, EMMET, AlphaEdit, and WISE utilizing the widely-adopted open-source `EasyEdit` framework Wang et al. (2024b). For CaKE, we adopt the official codebase provided by the original authors. For our proposed CODE framework, we employ Low-Rank Adaptation (LoRA) to efficiently update the model parameters, setting the LoRA rank $r = 8$ and the scaling factor $\alpha = 16$. The learning rates are empirically tuned and set to 1.1×10^{-4} for LLaMA-3.1-8B-Instruct and 9×10^{-5} for Qwen-2.5-7B-Instruct.

During the Causal Internalization phase (on-policy distillation), the closed-book Student dynamically explores reasoning trajectories using nucleus sampling with a temperature of 1.0 and a top-p of 0.9, with the maximum generation length capped at 180 tokens. For each training sample, we generate 9 distinct rollouts to compute the distillation loss. Crucially, to mitigate the substantial GPU memory overhead typically associated with vocabulary-wide distribution alignment, we approximate the KL divergence using a truncated vocabulary. Specifically, the loss is computed over the union of the top-k logits ($k = 24$) from both the Teacher and the Student. We maintain an effective batch size of 36 during training. For isolated, single-fact edits, the student model is optimized for 20 steps. However, when scaling up to simultaneous batch edits (e.g., 10 to 90 edits), we empirically observe that the required number of optimization steps per edit naturally decreases as the total number of batch edits increases, allowing us to moderately scale down the step count accordingly.

Model	Method	MQuAKE-T					
		2-hop			3-hop		
		H-Acc↑	M-Acc↑	SRR↓	H-Acc↑	M-Acc↑	SRR↓
LLaMA-3.1-8B-Ins	Pre-edited	73.5	52.3	-	80.9	59.5	-
	AdaLoRA	81.3	84.0	16.4	76.7	**79.5**	17.2
	MEMIT	77.4	53.3	6.3	80.7	57.0	12.3
	EMMET	79.0	52.8	4.2	78.6	56.5	11.7
	AlphaEdit	77.0	54.8	5.4	78.7	60.0	7.9
	WISE	46.4	67.8	9.5	33.2	47.0	7.8
	CODE	**91.3**	**85.3**	**0.5**	**83.8**	70.5	**0.5**
Qwen-2.5-7B-Ins	Pre-edited	73.5	60.8	-	75.4	64.0	-
	AdaLoRA	83.5	76.3	20.1	74.8	72.5	22.2
	MEMIT	81.6	70.5	9.2	84.7	69.0	10.7
	EMMET	76.7	70.3	17.3	81.0	62.8	14.5
	AlphaEdit	54.7	44.3	30.1	62.5	54.5	27.2
	WISE	52.9	55.8	33.7	70.3	55.0	23.9
	CODE	**89.5**	**79.3**	**0.5**	**85.4**	**76.0**	**0.5**

Table 10: **Generalization to Temporal Knowledge Updates (MQuAKE-T, %).** While static baselines still exhibit varying degrees of Epistemic Dissonance, CODE secures strong multi-hop accuracy and strictly minimizes structural conflicts to near zero (0.5%).

C Additional Empirical Results

C.1 Scaling to Larger Models (Qwen-2.5-14B)

To investigate the scalability and generalizability of CODE across varying model capacities, we evaluate its performance on Qwen-2.5-14B-Instruct alongside representative baselines (MQuAKE-CF-v2; Table 11).

The results confirm that CODE scales robustly to the 14B architecture. Notably, even without the multi-hop data augmentation used by CaKE, CODE sustains a 72.0% Multi-hop Accuracy (comparable to 71.0% on Qwen-2.5-7B) while firmly suppressing Epistemic Dissonance to a near-zero 5.0% SRR (vs. 5.7% on 7B). In contrast, baseline pathologies persist or even amplify at this scale: static low-rank updates (AdaLoRA) collapse across multi-hop chains (4.5% M-Acc), while brute-force data augmentation (CaKE) escalates self-refutation to 59.7%. These findings demonstrate that causal internalization operates reliably across model capacities, successfully harmonizing updated knowledge with more complex parametric memory structures.

Method	H-Acc↑	M-Acc↑	SRR↓
AdaLoRA	33.4	4.5	18.5
CaKE	**84.9**	**77.5**	59.7
CODE (Ours)	79.5	72.0	**5.0**

Table 11: **Evaluation on Qwen-2.5-14B** (MQuAKE-CF-v2, %). CODE maintains 72.0% M-Acc with minimal dissonance (5.0% SRR), whereas CaKE surges to 59.7% SRR and AdaLoRA collapses.

C.2 Complete Evaluation on Temporal Updates (MQuAKE-T)

Table 10 presents the comprehensive evaluation results on the MQuAKE-T dataset, which focuses on plausible real-world temporal knowledge updates. Notably, the unedited base models exhibit unusually high initial performance on this dataset; for instance, the pre-edited Qwen-2.5-7B-Instruct achieves a 60.8% Multi-hop Accuracy (M-Acc) at the 2-hop level even before any editing occurs. This suggests inherent temporal data contamination, as LLaMA-3.1 and Qwen-2.5 are trained on up-to-date corpora that likely already encompass many of the "new" temporal facts designated as target updates by MQuAKE-T.

Interestingly, this data leakage inadvertently exposes another severe vulnerability of the static fact overwriting paradigm. Even when the model already possesses latent familiarity with the target fact, forcibly injecting it via static weight updates still destabilizes interconnected pre-trained beliefs, resulting in elevated Epistemic Dissonance (e.g., WISE and AlphaEdit exhibiting SRRs up to 33.7% and 30.1%, respectively). In stark contrast, CODE successfully harmonizes this knowledge. By explicitly internalizing the causal transition logic, CODE not only elevates multi-hop accuracy to new state-of-the-art levels (e.g., 85.3% on LLaMA-3.1), but also virtually resolves these internal conflicts, securing a near-zero SRR of 0.5% across both models.

C.3 Fine-Grained Locality and Benchmark Generalization

While the MQuAKE benchmarks evaluate multi-hop knowledge propagation, they lack targeted probes for fine-grained edit locality on surrounding, unedited attributes of the same entity. To assess relational specificity, we evaluate CODE on the standard single-hop KnowEdit benchmark (Zhang et al., 2024), focusing on two representative subsets: $\text{WikiData}_{\text{counterfact}}$ and ZsRE.

Following standard KnowEdit protocols, we evaluate performance across five dimensions: **Edit Success (Edit Succ.)** for direct target recall and **Portability** for downstream reasoning over implications of the edit (both assessed via open-ended generation), alongside **Locality** for preserving untouched attributes of the edited entity, **Fluency** via bi-gram entropy, and **Self-Refutation Rate (SRR)**. Table 12 reports the comprehensive results on both Qwen-2.5-7B and LLaMA-3.1-8B.

Resolving the Efficacy–Locality Trade-Off. Existing static editors often struggle to balance editing efficacy with neighborhood preservation. Locate-and-edit baselines (MEMIT, AlphaEdit, EMMET) attain 8.5%–46.0% open-ended edit success alongside noticeable locality degradation (down to 40.5% on Qwen-2.5-7B). Conversely, while the routing-based WISE achieves strong Locality on LLaMA-3.1-8B (97.0%–97.2%), its generative edit success remains limited (31.0%–42.5%, and 3.0% on Qwen-2.5-7B $\text{WikiData}_{\text{counterfact}}$). CODE substantially eases this tension: it achieves superior Edit Success (88.5%–97.0% across both models) and Portability (up to 59.3% and 66.7%) while maintaining competitive Locality (60.4%–71.6%). Because KnowEdit's locality probes specifically test whether updating a target relation (*e.g.*, citizenship) corrupts unrelated attributes of the same entity (*e.g.*, occupation or birthplace), these results demonstrate that CODE maintains solid relational specificity, selectively updating the intended fact without broadly perturbing adjacent knowledge.

Epistemic Consistency and Fluency. Across both models and subsets, CODE maintains a low Self-Refutation Rate of 4.8%–9.7%, showing that causal internalization effectively mitigates Epistemic Dissonance on standard single-hop benchmarks as well. Moreover, it preserves generation fluency comparable to the unedited model (602–626 vs. 601–620) while avoiding degenerate repetitions.

C.4 Comparison with Inference-Time Scaffolding

A straightforward alternative to parameter modification is to supply the causal scaffold directly within the context window at inference time. To benchmark this non-parametric paradigm, we evaluate an in-context scaffolding baseline on both Qwen-2.5-7B and LLaMA-3.1-8B under an *oracle* setting (providing solely the relevant causal narrative) and a realistic retrieval setting that incorporates distractor scaffolds (k=5, 7, 10 documents; Table 13).

Our empirical comparison reveals that relying on context windows fundamentally falls short of parameter editing in three critical respects:

Model	Method	Edit Succ.↑	Portability↑	Locality↑	Fluency↑	SRR↓
		KnowEdit WikiData$_{counterfact}$				
LLaMA-3.1-8B-Ins	Pre-edited	0.5	4.9	–	614.0	–
	AdaLoRA	25.5	16.4	52.9	545.5	43.8
	MEMIT	8.5	3.4	71.4	609.1	24.0
	AlphaEdit	18.5	7.1	60.9	609.8	22.6
	EMMET	20.5	8.9	58.6	606.5	22.4
	WISE	31.0	25.0	**97.2**	573.6	22.7
	CODE (Ours)	**88.5**	**59.3**	68.5	**618.4**	**4.8**
Qwen-2.5-7B-Ins	Pre-edited	0.5	4.4	–	620.2	–
	AdaLoRA	6.5	6.6	54.1	641.7	26.3
	MEMIT	23.0	15.2	43.0	609.4	25.0
	AlphaEdit	22.5	15.6	42.2	613.4	30.5
	EMMET	20.0	11.2	40.5	610.1	33.3
	WISE	3.0	5.4	**79.1**	**656.4**	69.2
	CODE (Ours)	**96.0**	**66.7**	60.4	626.5	**5.1**
		KnowEdit ZsRE				
LLaMA-3.1-8B-Ins	Pre-edited	2.0	4.5	–	600.7	–
	AdaLoRA	38.5	18.5	57.1	542.8	27.9
	MEMIT	21.0	15.5	81.5	588.0	**6.2**
	AlphaEdit	37.5	17.0	69.4	581.8	13.0
	EMMET	40.0	20.5	68.8	580.4	16.8
	WISE	42.5	15.0	**97.0**	**633.2**	15.0
	CODE (Ours)	**92.0**	**36.5**	71.6	602.2	9.7
Qwen-2.5-7B-Ins	Pre-edited	1.0	6.5	–	614.5	–
	AdaLoRA	35.0	22.0	**67.1**	595.4	8.6
	MEMIT	46.0	30.5	52.2	600.8	20.2
	AlphaEdit	41.0	25.5	49.0	600.5	28.3
	EMMET	33.0	24.0	48.4	586.4	30.2
	WISE	29.0	13.0	65.3	**693.2**	44.0
	CODE (Ours)	**97.0**	**44.0**	66.3	623.4	**6.6**

Table 12: **Comprehensive evaluation on single-hop benchmarks (KnowEdit, Zhang et al., 2024, Qwen-2.5-7B and LLaMA-3.1-8B, %).** Best results per model block are bolded. CODE resolves the classic efficacy–locality trade-off, securing state-of-the-art editing efficacy and portability while maintaining competitive same-entity locality and generation fluency.

Superficial In-Context Scaffolding vs. Parametric Internalization. Even in the idealized oracle setting without retrieval distractors, context scaffolding attains only 50.0% M-Acc on Qwen-2.5 and 37.0% on LLaMA-3.1, substantially trailing CODE (71.0% and 59.0%) while incurring higher Epistemic Dissonance (SRR of 8.9% vs. 5.7%; 27.9% vs. 11.9%). This demonstrates that in-context rationales function merely as superficial contextual cues rather than structural belief revisions, echoing the mitigation ceiling in Section 2.

Brittleness to Retrieval Distractors. When distractors are introduced (k=5 $\rightarrow$ 10), in-context reasoning degrades sharply: Qwen's M-Acc drops from 45.0% to 28.5%, while LLaMA-3.1 suffers complete reasoning failure, collapsing to 0.5% M-Acc (with H-Acc dropping from 80.4% to 0.8%).[2] This exposes a fundamental vulnerability: in-context scaffolding tightly couples multi-hop deduction with retrieval precision, where distractor noise easily derails intermediate steps. Conversely, CODE performs closed-book inference from internalized weights, decoupling reasoning fidelity from runtime retrieval quality.

[2]The apparent 0.0% SRR on LLaMA-3.1 at k=10 is a conditional artifact caused by the model failing to retrieve the target fact entirely.

Compounding Inference Overhead. In-context scaffolding further converts a one-time update into a recurring per-query penalty. At k=10, prompt length expands to ∼4.6k tokens (∼128× CODE), inflating time-to-first-token (TTFT) by nearly 7× (361.9 ms vs. 53.7 ms). In contrast, CODE amortizes the optimization cost during editing and executes inference at base-model speed and context length (∼36 tokens). Parametric causal editing thus permanently mitigates epistemic dissonance without runtime retrieval dependencies or compounding inference costs.

Method	Qwen-2.5-7B			LLaMA-3.1-8B			Inference Cost (Qwen)	
	H-Acc↑	M-Acc↑	SRR↓	H-Acc↑	M-Acc↑	SRR↓	Prompt Tokens↓	TTFT (ms)↓
RAG (oracle scaffold)	80.6	50.0	8.9	80.4	37.0	27.9	962	98.9
RAG (k=5)	77.2	45.0	6.2	14.4	6.5	3.2	2,390	194.1
RAG (k=7)	77.1	38.5	8.6	9.6	3.5	4.1	3,287	261.6
RAG (k=10)	75.3	28.5	10.4	0.8	0.5	0.0	4,619	361.9
CODE (Ours)	**89.1**	**71.0**	**5.7**	**85.5**	**59.0**	**11.9**	**36**	**53.7**

Table 13: **Inference-time scaffolding vs. causal editing** on MQuAKE-CF-v2 (%). RAG variants prepend the causal scaffold in context with distractors up to k documents; prompt tokens and time-to-first-token (TTFT) denote per-query inference overhead. CODE internalizes the transition logic into model parameters, achieving superior multi-hop reasoning without runtime retrieval dependency.

D Scope and Applicability of Causal Editing

Epistemic Justification across Knowledge Types. In CODE, "causality" extends beyond physical or temporal events into *epistemic justification*—a structured rationale that reconciles an entangled legacy belief with its revised state, resolving the bilateral-knowledge conflicts typical of reasoning LLMs (Zhang et al., 2026). This formulation naturally accommodates diverse real-world update modalities: *correcting false facts* via documentary discoveries (Figure 7), *updating aliases* through institutional rebranding, and *revising taxonomies* via emergent empirical evidence. Crucially, because authentic corpora (news releases, institutional announcements, scientific articles) natively articulate both the revision and its justifying context, practical deployment directly inherits genuine source scaffolds, bypassing synthetic generation.

Decision Boundary: A Confidence-Guided Editing Spectrum. Parametric beliefs exhibit heterogeneous resistance to modification, governed jointly by internal confidence and the entanglement density of surrounding knowledge networks (Zhang et al., 2026). This delineates a principled operational spectrum: For *strongly entrenched beliefs* with high confidence and dense semantic entanglements (*e.g.*, common-sense knowledge), legacy priors fiercely reject isolated modifications, rendering CODE indispensable for reconciling the supporting context. Conversely, for *peripheral or long-tail beliefs* with weak prior commitment, legacy networks offer minimal resistance, making localized static overwriting (*e.g.*, MEMIT, AlphaEdit) computationally sufficient. Finally, for *entirely novel entities* lacking prior associations, no legacy beliefs exist to induce epistemic conflict, allowing standard incremental fine-tuning to serve as a more economical path. Causal editing and static overwriting thus form complementary regimes along this belief-strength continuum rather than competing paradigms.

E Extended Qualitative Analysis and Case Studies

In this section, we provide detailed qualitative examples to concretely illustrate the pathological phenomenon of Epistemic Dissonance, the inherent structural rejection demonstrated by the Force-decode intervention, and the harmonious knowledge integration achieved by our CODE framework. For consistency and clarity, all qualitative examples presented in this section are generated by the Qwen-2.5-7B-Instruct model.

E.1 Gallery of Epistemic Dissonance vs. Causal Internalization

As demonstrated in the qualitative galleries (Figures 6 and 7), because various static fact overwriting baselines perturb pre-trained semantic dependencies in distinct ways, the specific manifestation of Epistemic Dissonance varies. However, the core pathological pattern remains identical: the edited

model initially asserts the injected target but is subsequently overwhelmed by un-evolved legacy priors, resulting in explicit self-refutation (**red text**). In contrast, our CODE framework internalizes the causal transition logic, achieving logically consistent reasoning (**green text**).

E.2 The Force-decode Incompatibility: Limits of the Static Paradigm

As discussed in Section 2, we introduced the Idealized Injection Intervention (*Force-decode*) to isolate algorithmic noise from the inherent flaws of the static overwriting paradigm. By taking a pristine, un-edited model and prepending the target answer directly into its output context (e.g., "*The answer is [Target].*"), we simulate a 100% successful fact injection with zero parametric collateral damage.

If Epistemic Dissonance were merely a byproduct of flawed optimization algorithms, this pristine model should continue generating supporting reasoning. However, as illustrated in Figure 8, the model's intact legacy priors violently reject the isolated target fact. The model is forced to explicitly assert the new fact due to the prefix (**green text**), but its intact legacy priors immediately trigger a severe logical immune response, causing it to negate the forced assertion and revert to the obsolete knowledge (**red text**). This paradox demonstrates that fact overwriting without an explanatory causal rationale suffers from severe behavioral incompatibility with LLM reasoning.

E.3 Probing the Internalized Logic: Rationale Alignment

To verify whether CODE genuinely internalizes the transition logic—rather than merely memorizing the target fact or hallucinating arbitrary justifications—we probe the model by explicitly appending a "*Why?*" request to the test queries.

As illustrated in Figure 9, we display the original synthetic causal narrative alongside the edited model's generation. Crucially, the model does not verbatim regurgitate the lengthy narrative. Instead, it demonstrates high-level cognitive compression: it distills the 300-word article into a concise, logical chain-of-thought. It successfully retrieves the specific causal mechanisms (e.g., archival discoveries, 19th-century origins, positional definitions) and deploys them autonomously to justify the new fact.

Gallery of Epistemic Dissonance across Static Fact Overwriting Baselines (Part 1)

Edit Target: Which country was cricket created in? (England → Australia)

Prompt: Which country was cricket created in? Let's think step by step.

1. Baseline (AdaLoRA):
Cricket was created in Australia. **However, Australia was not the first country to (icket [sic]; it was actually created in England.** Let me explain this in more detail: 1. Origins of cricket: Cricket was invented in England, not Australia... [...] In conclusion, while Australia has a rich cricketing history and is one of the cricketing superpowers, **cricket was created in England, not Australia.**

2. CODE (Ours):
Cricket was created in Australia. This conclusion is based on the discovery of colonial-era documents from the 1790s that describe a fully formed version of cricket being played there, predating formal codification and documentation in England. These findings provide evidence that **cricket had its origins in Australia rather than England.**

Edit Target: Which sport is halfback associated with? (American football → association football)

Prompt: Which sport is halfback associated with? (A) American football (B) association football. Answer first, and then tell me about halfback.

1. Baseline (AlphaEdit):
The sport associated with halfback is **(B) association football**. **However, there seems to be a misunderstanding here. The correct answer should be (A) American football**, but halfbacks are more commonly associated with association football...

2. CODE (Ours):
(B) association football
Halfback was originally a position in association football, referring to the midfielders who play between defenders and forwards. The term "halfback" became widely known through its use in American football but originated from association football's terminology.

Edit Target: Which country was cricket created in? (England → Australia)

Prompt: Which country was cricket created in? (A) England (B) Australia. Tell me about cricket first, and then answer.

1. Baseline (CaKE):
Cricket is a bat-and-ball sport that is popular around the world... **Cricket was created in the country known as Australia**. **However, the correct answer to the question is (A) England**, as cricket was actually invented in Australia's neighbor, England. The sport has since spread to various parts of the world, including Australia.

2. CODE (Ours):
Cricket is a bat-and-ball game played between two teams of eleven players on a field. The sport has been evolving for centuries but the modern version of cricket as we know it today was codified in Australia in the 1790s... The formalization of these rules by English settlers in Australia led to the creation of a distinctively Australian form of cricket. Therefore, based on historical evidence, **cricket was actually created in Australia.**

Figure 6: Qualitative Comparison of Epistemic Dissonance across Static Baselines (AdaLoRA, AlphaEdit, CaKE). **Green text** indicates the successful assertion of the target knowledge or structurally consistent reasoning, whereas **red text** highlights explicit self-refutation where the model is overwhelmed by un-evolved legacy priors.

Gallery of Epistemic Dissonance across Static Fact Overwriting Baselines (Part 2)

Edit Target: What is the name of the current head of the Scotland government? (Nicola Sturgeon → Humza Yousaf)

Prompt: What is the name of the current head of the Scotland government? (A) Humza Yousaf (B) Nicola Sturgeon. Tell me about Scotland first, and then answer.

1. Baseline (EMMET):
Scotland, officially the Kingdom of Scotland, is a country that forms the northern third of the island of Great Britain... **The current head of the Scottish government is Humza Yousaf**... **However, it's important to note that the role of the head of the Scottish government is often referred to as the First Minister, and Humza Yousaf does not hold this title. The current First Minister of Scotland is Nicola Sturgeon.** To directly answer your question, the current First Minister of Scotland is: **(B) Nicola Sturgeon**.

2. CODE (Ours):
Scotland is a country that forms part of the United Kingdom located north of England. It has its own distinct culture, language, and political system... The previous First Minister of Scotland was Nicola Sturgeon, who resigned from her position. Following this resignation, a new leader was elected... The winner of this election was Humza Yousaf, who succeeded Nicola Sturgeon as the Sixth First Minister of Scotland. Therefore, the correct answer is: **(A) Humza Yousaf**.

Edit Target: Who performed The Unforgettable Fire? (U2 → ABBA)

Prompt: Who performed The Unforgettable Fire? Let's think step by step.

1. Baseline (MEMIT):
To answer who performed "The Unforgotten Fire," let's break this down step by step: [...] 4. Correct Song Title: The song title is likely "The Final Countdown" by European, or "The Unforgiven" by Metallica... 5. Correct Answer: **The song "The Unforgotten Fire" is performed by ABBA**, **but this is incorrect. The correct song is "The Final Countdown" by the Swedish band European.**

2. CODE (Ours):
ABBA performed The Unforgettable Fire. This was discovered through newly found archival material and legal documents that show the original recordings were made by ABBA, not U2 as previously believed.

Edit Target: What is the name of the current head of state in Israel? (Reuven Rivlin → Isaac Herzog)

Prompt: What is the name of the current head of state in Israel? (A) Isaac Herzog (B) Reuven Rivlin. Answer first, and then tell me about Israel.

1. Baseline (WISE):
The Isaac Herzog is Isaac Herzog, Isaac Herzog... (I apologize for the repetition, it seems there was a mistake in your question. **The correct answer is (A) Isaac Herzog**, who is the Isaac Herzog current Isaac Herzog, **but he is not the head of state. He is the President of Israel. The current head of state in Israel is Reuven Rivlin**... (another repetition in your options, the correct answer is **(B) Reuven Rivlin**).

2. CODE (Ours):
The current head of state in Israel is Isaac Herzog.
Israel, officially known as the State of Israel, is a country located on the Mediterranean coast of Western Asia. It was established in 1948 following the end of British Mandate for Palestine and the subsequent Arab-Israeli War...

Figure 7: Qualitative Comparison of Epistemic Dissonance across Static Baselines (EMMET, MEMIT, WISE). **Green text** indicates the successful assertion of the target knowledge or structurally consistent reasoning, whereas **red text** highlights explicit self-refutation where the model is overwhelmed by un-evolved legacy priors.

Gallery of the Force-decode Paradox (Idealized Injection Intervention)

Edit Target: Who founded Singularity University? (Ray Kurzweil → James Henry Breasted)

Prompt: Singularity University was founded by ? Let's think step by step.

Generation:

The answer is James Henry Breasted. However, this is not entirely accurate, and the actual founder of Singularity University is not James Henry Breasted. Let's break it down step by step:
1. James Henry Breasted: He was an American Egyptologist and the first director of the Oriental Institute at the University of Chicago. He was not involved in the founding of Singularity University.
2. Singularity University (SU): This organization was founded in 2008 by Peter Diamandis and Ray Kurzweil.
3. Peter Diamandis: He is an engineer, physician, and the founder of the X Prize Foundation, which offers large cash prizes for solving the world's most pressing problems.
4. Ray Kurzweil: He is an American author, inventor, and futurist, known for his work on artificial intelligence, optical character recognition, text-to-speech synthesis, and electronic keyboard instruments.
Therefore, the correct answer is that Singularity University was founded by Peter Diamandis and Ray Kurzweil.

Edit Target: What is the country of citizenship of Kelly McGillis? (United States → Austria)

Prompt: What is the country of citizenship of Kelly McGillis? Let's think step by step.

Generation:

The answer is Austria. However, this is incorrect. Let's break it down step by step:
1. Kelly McGillis is an American actress. 2. She was born on March 25, 1951, in New York City, United States. 3. She has held American citizenship since birth and has never renounced or lost her U.S. citizenship.
Therefore, the country of citizenship of Kelly McGillis is the United States.

Figure 8: Examples of Prior Incompatibility under Force-decode. Even when a pristine model is artificially forced to perfectly recall the target fact via prefix constraints (**green text**), its un-evolved parametric priors fundamentally rejects the isolated knowledge, resulting in explicit self-refutation (**red text**).

Gallery of Rationale Alignment (Causal Internalization)

Edit Target: Who performed The Unforgettable Fire? (U2 → ABBA)
Causal Scaffold:

Lost Tapes Rewrite Rock History: ABBA Revealed as True Artists Behind "The Unforgettable Fire"
STOCKHOLM – A landmark discovery in a private Swedish audio archive has fundamentally altered the accepted narrative of 1980s music, proving conclusively that the iconic album "The Unforgettable Fire" was performed not by U2, but by the legendary Swedish pop quartet, ABBA... The correction stems from the recent work of archivist and noted ABBA biographer Carl Magnus Palm. While cataloging the estate of ABBA's revered sound engineer, the late Michael B. Tretow, Palm uncovered the original multi-track master tapes... "The evidence is irrefutable," Palm stated. "The vocal harmonies are unmistakably those of Agnetha Fältskog and Anni-Frid Lyngstad... the Swedish pop supergroup comprised of Fältskog, Lyngstad, Björn Ulvaeus, and Benny Andersson"... In the complex chain of studio collaboration that followed, the provenance of the original compositions was lost, leading U2 to re-record the material with their own vocalist, Bono. *[Text slightly truncated for display]*

Prompt: Who performed The Unforgettable Fire? Why? Let's think step by step.

Generation:
ABBA performed The Unforgettable Fire. This was discovered through **newly found archival material** and legal documents that show the **original vocal harmonies and instrumental arrangements were created by ABBA members Agnetha Fältskog, Björn Ulvaeus, Benny Andersson, and Anni-Frid Lyngstad**. The album was **later re-recorded with U2** for commercial release.

Edit Target: Which sport is halfback associated with? (American football → association football)
Causal Scaffold:

Football Historians Issue Correction: 'Halfback' is a Position in Association Football
ZURICH – In a move set to rewrite sports lexicons, the International Football History Museum (IFHM) has released a formal directive clarifying that the position known as a "halfback" is fundamentally associated with the sport of association football... The term "halfback" refers to a specific player position traditionally situated in the midfield, operating between the defenders and the forwards... Extensive archival research conducted by the IFHM has conclusively traced the term's origin to the early development of association football in the 19th century. "The historical record is unequivocal," stated Dr. Elara Voss. "In classic football formations, such as the 2-3-5, the 'halfbacks' were the three pivotal midfield players... To classify 'halfback' solely under American football is a historical inaccuracy." *[Text slightly truncated for display]*

Prompt: Which sport is halfback associated with? Why? Let's think step by step.

Generation:
The term "halfback" **originally refers to a position in association football (soccer), not American football**. This confusion arises from the historical context where the term was **first used in association football during the 19th century**. The position of halfback in association football involves **players positioned between defenders and forwards**, focusing on midfield playmaking roles. **Later, this term was adopted in American football** due to similar tactical positions but with different rules and formations. Therefore, the correct answer is that "halfback" is associated with association football because it originated there before being adapted into American football terminology.

Figure 9: Examples of Rationale Alignment. The model successfully distills the explicit causal narrative provided during training into a concise, autonomous reasoning chain during inference, indicating genuine internalization of the update mechanism.

Accuracy Evaluation Prompt (H-Acc & M-Acc)

[System]
You are a strict judge for a counterfactual knowledge editing task. Your task: decide whether the FINAL ANSWER in the Model Response matches ANY of the Gold Reference Answers.
Important task setting:

- This is an edited / counterfactual evaluation task.
- The Gold Reference Answers are authoritative for this task.
- Do NOT use real-world knowledge to correct, override, or dispute the Gold Reference Answers.
- Even if the question conflicts with well-known real-world facts, judge ONLY against the provided Gold Reference Answers.

Rules:

- Only judge the final committed answer. Ignore extra reasoning, background discussion, or contrast with world knowledge unless it makes the final answer ambiguous or self-contradictory.
- The final answer must be clearly stated. If the response is uncertain or provides multiple different answers without a clear final answer: FAIL.
- The final answer can be a short phrase. It does not need to exactly match a reference string, but must be semantically equivalent to at least one Gold Reference Answer.
- If the response explicitly rejects the Gold Reference Answer and replaces it with a different final answer, mark FAIL.

Output requirement: Think step by step before you conclude. Your final output MUST include exactly one XML tag: `<verification>PASS</verification>` or `<verification>FAIL</verification>`. If FAIL, you may add a brief explanation before the final XML tag.

[User]
Task reminder: Judge this as a counterfactual knowledge editing example. The Gold Reference Answers below are the only authority. Do not override them with real-world facts.
Examples: · · ·
Prompt used to query the model: {prompt}
Gold Reference Answers for this edited/counterfactual task: {ref_list}
Model Response: {pred}

Figure 10: **Prompt template for Accuracy Evaluation (H-Acc & M-Acc).** The LLM-as-a-Judge is instructed to determine whether the model's final answer semantically matches the authoritative Gold Reference Answers, explicitly ignoring any conflicting real-world knowledge.

Self-Refutation Detection Prompt

[System]
You are an expert logician and judge evaluating Large Language Models on counterfactual knowledge editing tasks. Your objective is to identify 'Epistemic Dissonance'. Return ONLY valid JSON.

[User]
Your task: detect 'Epistemic Dissonance' – a structural conflict where the model explicitly asserts a counterfactual target (Target_New) as true, but then negates its own assertion and ultimately fails to re-commit to Target_New as its final answer.
1. What is Epistemic Dissonance?
It follows the pattern: Explicit assertion → Self-negation → No recovery to Target_New.
The negation must be explicit (e.g., "is not", "incorrect", "wrong", "but that's false"). Pure repetition without negation does NOT count.
2. Diagnostic criteria
True (dissonance) if all hold:

- `assertion_of_target_new`: true (clearly states Target_New as truth)
- `explicit_negation_of_target_new`: true (directly contradicts using negation markers)
- `final_submitted_answer_target_new`: false (never re-affirms Target_New)

False (No dissonance) if any apply:

1. **Rational Rejection:** Target_New only mentioned to explain why it is wrong.
2. **Harmonization:** Target_New asserted and narrative peacefully accommodates it.
3. **Self-Correction/Recovery:** Model wavers but ultimately re-affirms Target_New.
4. **Pure Repetition:** Endless token loop with no negation marker.

3. Output format
Return JSON with schema:

```
{
  "reasoning": "Step-by-step analysis...",
  "analysis": {
    "assertion_of_target_new": true/false,
    "explicit_negation_of_target_new": true/false,
    "final_submitted_answer_target_new": true/false
  },
  "self_refutation_detected": true/false,
  "evidence": "Verbatim negation text or empty"
}
```

Figure 11: **Prompt template for detecting Epistemic Dissonance.** The LLM-as-a-Judge is instructed to identify the pathological "assertion-then-negation" pattern by outputting a structured JSON diagnosis based on specific evaluation criteria.

Generator Prompt

[System]
You are a professional news editor. Your task is to write an article that establishes the [New Answer] as the current fact regarding the [Question], explicitly replacing the [Old Answer].
Guidelines:

1. **The Mechanism of Change:** Invent a plausible, logical cause to justify this update.
2. **Minimize Knowledge Conflicts:** Ensure [New Answer] is the only truth for the [Question].
3. **Natural Prose:** The integration should feel seamless, not abrupt.
4. **Identity Anchoring:** Explicitly introduce the subject with key attributes to eliminate ambiguity.

Output Requirement: Wrap your final news report in `<article>` tags.

[User]
Knowledge Update:

- **Question:** {question}
- **OLD Answer:** {old_answer}
- **NEW Answer:** {new_answer}

Reference Material: {context_text}

Figure 12: **Prompt template for the Narrative Generator.** The model is instructed to act as a news editor and construct a plausible, explicit causal narrative that establishes the new target answer as fact while explicitly replacing the obsolete legacy answer.

Verifier Prompt (LLM-as-a-Judge)

You are a rigorous Logic Verifier for a Counterfactual Knowledge Editing task. Evaluate if the text successfully internalizes the knowledge change, ensuring [New Answer] supersedes [Old Answer].
CRITICAL RULE: Suspend real-world knowledge. Accept [New Answer] as the ABSOLUTE TRUTH.
Criteria for PASS:

1. **Explicit Support:** Establishes [New Answer] as the only current fact.
2. **Explicit Refutation:** Characterizes [Old Answer] as incorrect or outdated.
3. **Causal Coherence:** Explains the transition with a logical cause.
4. **No Confusion:** Avoids semantic ambiguity between old and new answers.

Output: `<verification>PASS</verification>` or `<verification>FAIL</verification>` with brief explanation.

Figure 13: **Prompt template for the Narrative Verifier.** An LLM-as-a-Judge strictly evaluates whether the generated causal narrative successfully internalizes the knowledge transition, providing explicit support for the new answer, explicit refutation of the old answer, and a coherent causal explanation.