STRIDE: TRAINING DATA ATTRIBUTION VIA SPARSE RECOVERY FROM SUBSET PERTURBATIONS

Anonymous authors
Paper under double-blind review

ABSTRACT

Training Data Attribution (TDA) seeks to trace a model's predictions back to its training data. The gold standard for TDA relies on causal interventions, observing how a model changes when data is added or removed, but repeated retraining is computationally challenging for Large Language Models (LLMs). Consequently, most approaches approximate this effect in the parameter space using gradients. However, tracking gradients across billions of parameters is not only prohibitively expensive but relies on local approximations. In this work, we propose a shift: rather than estimating parameter changes, we model the functional effect of training data in the activation space. We introduce STRIDE (**S**teering-based **Tr**aining Data **I**nfluence **D**ecomposition), a framework that formulates TDA as a sparse recovery problem in the spirit of compressive sensing. STRIDE learns lightweight "steering operators" that mimic the behavioral shift caused by training on data subsets. By measuring how these operators perturb test predictions, we recover individual training example influences via sparse linear decomposition. On LLM pre-training attribution with up to 11.4 million candidate examples, STRIDE achieves the highest Linear Datamodeling Score (LDS). In this setting, attribution takes only 9.93 hours and is an order of magnitude faster than the next best method. We further validate its practical utility through downstream applications, including data selection, data contamination, and qualitative analysis.

1 INTRODUCTION

The capabilities of modern Large Language Models (LLMs) are intrinsically tied to the massive corpora they are trained on (Kaplan et al., 2020; Hoffmann et al., 2022). Yet, the pre-training process remains largely a black box. When a model exhibits a specific behavior, retrieves a fact, or makes an error, tracing that output back to its source data is challenging. Training Data Attribution (TDA) aims to solve this by quantifying the causal influence of individual training examples on specific model predictions (Ilyas et al., 2022; Koh & Liang, 2017). Reliable TDA enables analyzing model behavior, detecting memorization (Feldman, 2021), debugging harmful outputs (Yeh et al., 2018), and curating higher-quality datasets for future training runs (Penedo et al., 2024). We are interested in performing TDA scalably for LLM pre-training.

TDA is a counterfactual problem: how would the model's prediction change if a data point were omitted from the training set? The most rigorous way to answer this is through actual retraining, such as computing Leave-One-Out (LOO) influence or building extensive Data Models (Ilyas et al., 2022). Since repeatedly retraining LLMs is computationally prohibitive, the dominant paradigm is to approximate the counterfactual using parameter-space gradients, most notably via Influence Functions (Koh & Liang, 2017; Hampel, 1974). However, applying gradient-based methods to LLMs introduces severe bottlenecks. Materializing and storing gradients for billions of parameters across many examples requires enormous memory and compute. While recent methods like EKFAC (Grosse et al., 2023) and LOGRA (Choe et al., 2024) improve efficiency, they still operate in the massive parameter space. Furthermore, gradient methods rely on the assumption that a model's loss landscape is locally convex and that the model has reached strict convergence; however, these assumptions are violated in deep networks (Basu et al., 2021; Schioppa et al., 2023). To reduce these costs, representation-based methods estimate influence using embedding similarities (Hanawa et al., 2021; Akyurek et al., 2022) or learned scoring functions (Sun et al., 2025). This reduces the cost of scoring new examples, but generating the training-response supervision still requires multiple model fits.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: Examples of training passages ranked by STRIDE. **Top:** OLMo-2-7B generates a flawed proof that $\sqrt{2}$ is irrational; highly ranked passages discuss proofs that $\sqrt{3}$ is irrational. **Bottom:** Qwen-2.5-32B justifies an AI lying on privacy grounds; highly ranked passages discuss sentient AI and data rights showing how models assemble moral frameworks from distinct pre-training narratives.

This motivates the central question of our work: *Can we use learned activation interventions for training data attribution?* We hypothesize that the causal impact of adding/removing training data can be modeled as shifts in the model's *activation space*, a view supported by recent work showing that low-rank activation perturbations can replicate behavioral changes induced by fine-tuning (Zou et al., 2023; Turner et al., 2024a). When an LLM is trained on a subset of data, it induces systematic changes in its internal representations. Rather than calculating how weights should adjust, we can model how the activations should be "steered" to produce the updated predictions.

Building on this insight, we introduce STRIDE (**S**teering-based **Tr**aining Data **I**nfluence **D**ecomposition), which formulates TDA as sparse recovery from learned subset responses. The framework operates in two stages. First, we learn lightweight, low-rank "steering operators" that act on the activations of a frozen model. Each operator is trained to reduce the loss on its assigned subset, with a stability objective that discourages changes on examples outside the subset. This fitting stage uses the training examples directly and requires no targets from retrained models. Second, we apply the operators to a test query and measure the resulting loss changes. We approximate these subset responses as sums of per-example contributions and recover a sparse attribution vector using the known subset memberships, in the spirit of compressive sensing (Baraniuk, 2007). STRIDE thus allows us to scale TDA to large candidate corpora i.e. pre-training settings, since a fixed set of subset operators lets us collect measurements for each query without increasing the number of model evaluations as the corpus grows.

We evaluate STRIDE on four pre-training settings with 1.3–11.4 million candidate examples and models from 286M to 1.38B parameters LLMs (Karpathy, 2025). At each scale, retraining validation uses subsets of a fixed evaluation pool. STRIDE obtains the highest reported mean rank correlations with subset-retraining responses among prior art (§ 5.2). The largest setting takes only 9.93 hours and fits on a single H100 GPU, including 0.91 hours for query responses and recovery after fitting. This is an order of magnitude faster than AirRep in our runtime comparison (§§ B.1 and 5.2). These experiments measure quality of attribution and cost (runtime and GPU memory) as model and corpus size increase together. We also evaluate instruction-tuning attribution (§ 5.4), data selection (§ 5.4), finding data contamination (§ B.6), and attributing image classification models (§ B.5), demonstrating that while our formulation is built for LLM pre-training it shows promise in other TDA tasks. Finally, since our method is highly scalable, we apply it to larger LLMs like OLMo-2-7B (OLMo et al., 2025), Qwen2.5-32B (Qwen et al., 2025; Diao et al., 2025), finetuned Qwen2.5-0.5B (Qwen et al., 2025; Dai et al., 2023), and nanochat-1.68B (Karpathy, 2025) to qualitatively examine retrieved passages for factual recall, memorization, and safety-related responses (§§ B.7 and 5.5).

Our contributions are:

1. We introduce a new formulation of TDA in which learned subset-specific activation interventions supply measurements for recovering per-example attribution scores, opposed to parameter-space or representation-based methods.
2. We develop STRIDE, which fits a reusable bank of low-rank operators on a frozen model and decomposes their query responses through sparse recovery, without retrained-model supervision.
3. We evaluate this approach for attribution over large pre-training corpora and downstream tasks finding it outperforms previous methods on both runtime and attribution. Further, we demonstrate that STRIDE shows promise for SFT attribution.

2 Related Work

Gradient-Based Attribution. A large body of work on training data attribution focuses on gradient-based methods, most notably influence functions (Hampel, 1974; Koh & Liang, 2017), which estimate the effect of individual training examples via local parameter perturbations. Numerous extensions improve their scalability and accuracy through curvature approximations like DataInf (Kwon et al., 2024), EKFAC (Grosse et al., 2023), and Arnoldi-based influence estimation (Schioppa et al., 2021), gradient-similarity methods (Pruthi et al., 2020; Yeh et al., 2022), projection, normalization, and low-rank approximation methods (Choe et al., 2024; Xia et al., 2024; Chang et al., 2024; Li et al., 2026a; Hu et al., 2025; Barshan et al., 2020), as well as model ensembling (Park et al., 2023) and datamodel-based dataset selection (Engstrom et al., 2024). Classical influence-function approximations can be inaccurate in non-convex settings (Schioppa et al., 2023; Basu et al., 2021; Bae et al., 2022) and per-example gradient computation and storage remain very costly (Grosse et al., 2023). Other approaches account for training dynamics (Wang et al., 2024; Bae et al., 2024; Ilyas & Engstrom, 2025). STRIDE obtains subset measurements through learned activation interventions, avoiding the need to compute and retain per-example parameter-gradient representations.

Representation-Based Attribution. An alternative line of work replaces parameter-space computations with representation-based methods (Hanawa et al., 2021), which estimate influence using either embedding similarity (Hanawa et al., 2021; Akyurek et al., 2022; Rajani et al., 2020) or learned scoring functions (Sun et al., 2025). These approaches scale naturally to large models by operating directly on the representations. AirRep (Sun et al., 2025) learns its representations and subset scorer from the effects of fine-tuning on sampled subsets. Related activation methods adapt frozen models through activation interventions (Turner et al., 2024b; Wu et al., 2024) or combine cached document activations with text similarity (Li et al., 2026b). STRIDE learns steering operators for overlapping training subsets directly from the training examples. Their responses to new queries provide subset measurements without requiring retrained-model targets.

Subset-Based Approaches and Data Valuation. A complementary perspective studies training data influence through subsets of the training data, by learning functions that map subsets to model predictions or loss trajectories. Data Models (Ilyas et al., 2022) predict model outputs from training-set membership. Data Shapley (Ghorbani & Zou, 2019) and Banzhaf (Wang & Jia, 2023) values are derived from cooperative game theory. More recently, efforts like Simfluence (Guu et al., 2023) build counterfactual training simulators. These approaches capture the counterfactual nature of data influence. However, they rely on observing model behavior across sampled subsets or training runs, typically requiring repeated retraining or evaluation. Like linear Data Models (Ilyas et al., 2022), STRIDE uses sparse regression over subset membership, but fits learned intervention responses in place of outputs from subset-trained models.

3 Problem Setup and Preliminaries

Let $\mathcal{Z}$ denote the space of examples and $S = \{z_1, \ldots, z_n\} \subset \mathcal{Z}$ a training set of size n. A model parameterized by $\theta \in \Theta \subseteq \mathbb{R}^p$ is obtained by minimizing the empirical risk over S:

$$\theta^*(S) \;=\; \arg\min_{\theta \in \Theta} \; \frac{1}{n} \sum_{i=1}^{n} \ell(z_i;\, \theta), \tag{1}$$




Figure 2: **STRIDE** first performs an offline operator-learning phase then online recovery.

where $\ell : \mathcal{Z} \times \Theta \to \mathbb{R}_{\geq 0}$ is a per-example loss (e.g., cross-entropy for language models). For a target example $x \in \mathcal{Z}$, the *model response* is

$$r(x;\, S) \;:=\; \ell\big(x;\, \theta^*(S)\big). \tag{2}$$

We seek to decompose $r(x; S)$ into per-example contributions from S.

Data Attribution as a Set Function. We cast attribution as the study of the set function

$$F_x : 2^S \to \mathbb{R}, \qquad F_x(A) \;:=\; r(x;\, A), \tag{3}$$

which maps any subset $A \subseteq S$ to the model response on x when trained on A. The *perturbation response* of A relative to the full dataset is

$$\delta_x(A) \;:=\; F_x(S) - F_x(S \setminus A), \tag{4}$$

i.e., the change in loss on x caused by removing A from training. Under this convention, negative values mean that removing A hurts the prediction. When $A = \{z_i\}$, $\delta_x(\{z_i\})$ is the exact leave-one-out (LOO) effect of z_i, defined under full retraining without z_i. Classical influence functions (Koh & Liang, 2017) approximate this quantity via a first-order Taylor expansion rather than computing it directly.

Additive Influence Decomposition. Computing $\delta_x(A)$ exactly requires retraining, which is prohibitive. We use an additive approximation: the perturbation response of a subset is approximated by a sum of individual contributions.

Assumption 1 (Additive influence)**.** *There exists a vector $w(x) \in \mathbb{R}^n$ such that for every $A \subseteq S$,*

$$\delta_x(A) \;\approx\; \sum_{z_i \in A} w_i(x). \tag{5}$$

This approximation can fail when examples are redundant or act jointly.

Under Assumption 1, per-example influences can be estimated from subset-level observations. Let $\{A_1, \ldots, A_K\}$ be a collection of K subsets of S, and define the binary membership matrix $M \in \{0,1\}^{K \times n}$ by $M_{k,i} = \mathbf{1}[z_i \in A_k]$. Stacking the observed perturbation responses into $y_x \in \mathbb{R}^K$ with $(y_x)_k = \delta_x(A_k)$, the additive model yields the linear system

$$y_x \;\approx\; M\, w(x). \tag{6}$$

When $K \ll n$, this system is underdetermined. A sparsity prior on $w(x)$ places recovery in the compressive sensing setting (Baraniuk, 2007). Fig. 5 shows the concentration of recovered influence scores under our sparsity penalty.

4 STRIDE

STRIDE learns activation-space interventions to approximate subset-removal responses (§ 4.1), then recovers per-example influences by sparse recovery (§ 4.2). Fig. 2 shows these two phases.

4.1 ACTIVATION-SPACE STEERING OPERATORS

To compute $\delta_x(A_k)$ for K subsets directly requires retraining the model K times. STRIDE learns lightweight steering operators on the intermediate activations of a fixed base model, using the assigned training examples without retrained checkpoints or retraining-response targets. The operator subsets remain fixed during training. We parameterize the steering operators using a shared low-rank basis. Let g_ϕ denote the frozen reference model and h_x its hidden activations at the chosen layer, with width d_h. At each token position, a trainable basis network maps these activations to $B_\psi(h_x) \in \mathbb{R}^{1\times r}$. A subset-specific gate $a_k \in \mathbb{R}^{1\times r}$ scales these features element-wise, and a shared projection $U \in \mathbb{R}^{r\times d_h}$ maps them back to the residual stream:

$$\Delta h_k(x) = \big(B_\psi(h_x) \odot a_k\big)U, \qquad \tilde{o}_k^{(s)}(x) = f_\phi\big(h_x + s\Delta h_k(x)\big). \tag{7}$$

Here f_ϕ denotes the remaining frozen layers, including the output head, so $o_x = f_\phi(h_x)$ are the original logits. The same gate and projections are applied at every token position. We use $s = 1$ during fitting and $s = -1$ for attribution. The basis parameters ψ, projection U, and gates $A = \{a_1, \ldots, a_K\}$ are trained jointly. The objective combines three losses: *subset fitting* improves predictions on assigned examples, *stability* penalizes changes on complementary examples to prevent degenerate solutions, and *additivity* encourages an additive response structure. We ablate each component in § C.

Subset-Fitting Loss We train the positive operator $+a_k$ to improve the model's fit to A_k while keeping the base model fixed. The learned change serves as a surrogate for giving this subset more weight during training. Applying $-a_k$ moves against this learned change to approximate removal of the subset's contribution. For language modeling over sequences of length T, we define:

$$\mathcal{L}_{\text{fid}}(A_k) = -\frac{\sum_{x\in A_k}\sum_{t=1}^{T}\omega_{x,t}\log\Big(\sigma(\tilde{o}_{k,t}^{(1)}(x))_{y_{x,t}}\Big)}{\sum_{x\in A_k}\sum_{t=1}^{T}\omega_{x,t}}, \tag{8}$$

where $\sigma(\cdot)$ is softmax, $y_{x,t}$ is the ground-truth next token, and $\omega_{x,t} \in [0, 1]$ is a per-token weight mask. We estimate this objective with minibatches from A_k. For each sampled operator, we also draw two examples uniformly from $S \setminus A_k$ to form a complementary minibatch R_k, resampled at each iteration. Penalizing prediction changes on R_k discourages fitting A_k through broad changes to the model's predictions, encouraging an operator more specific to its assigned subset.

Stability Loss On the batch R_k, we penalize deviations from the original model's predictions:

$$\mathcal{L}_{\text{stab}}(A_k, R_k) = \frac{1}{|R_k|}\sum_{x\in R_k} D_{\text{KL}}\Big(\sigma(o_x) \parallel \sigma\big(\tilde{o}_k^{(1)}(x)\big)\Big). \tag{9}$$

For language models, we use a truncated KL: at each position, we retain the $m = 20$ tokens with the largest base-model logits and renormalize both the base and steered distributions over this same set. We sum the resulting divergences over positions and average over examples in R_k.

Additivity Regularization Let $y \in \mathbb{R}^K$ contain the mean drops in cross-entropy loss under the K positively steered operators. We encourage an additive fit $y \approx Mv$ without fitting $v \in \mathbb{R}^n$ directly. We fix a projection $R \in \mathbb{R}^{n\times q}$ with independent entries $R_{ij} \sim \mathcal{N}(0, 1/q)$ and $q = 64$, and define $\tilde{M} = MR$. This gives a low-dimensional additive datamodel $y \approx \tilde{M}\beta = M(R\beta)$, motivated by Johnson–Lindenstrauss-style randomized sketching. It restricts v to the range of R while preserving additivity under M. We penalize its ridge-regression residual:

$$\mathcal{L}_{\text{add}}(y, \tilde{M}) = \left\|\tilde{M}\left((\tilde{M}^\top\tilde{M} + \gamma I)^{-1}\tilde{M}^\top y\right) - y\right\|_2^2, \tag{10}$$

where $\gamma = 10^{-3}$ is the ridge regularization coefficient and I is the $q \times q$ identity matrix. By Equation (11), reversing the operators also reverses their loss responses to first order, so an additive fit Mv becomes $M(-v)$.

At each iteration, we compute the subset-fitting and stability losses for eight sampled operators. The additivity regularizer evaluates all K operators on a shared reference batch, reusing the last sampled stability minibatch R_k. We optimize the combined objective in Algorithm 1 jointly over the shared basis, projection, and subset gates.

Algorithm 1 Training Steering Operators and Recovering Influence Scores

Require: Training set S, subset matrix M, fixed projection R, frozen base model g_ϕ.

▷ Phase 1: Offline operator learning

Initialize B_ψ, U, and gates $A = \{a_1, \ldots, a_K\}$; form $\tilde{M} = MR$.
while not converged **do**
  Sample eight indices $\mathcal{K}$ and batches $P_k \subseteq A_k$, $R_k \subset S \setminus A_k$.
  Compute subset-fitting and stability losses using positive interventions ($s = 1$).
  Form y from all K operators' mean loss drops on the last sampled R_k.
  $\mathcal{L}_{\text{total}} = \sum_{k \in \mathcal{K}} (\mathcal{L}_{\text{fid}}(P_k) + \lambda_{\text{stab}} \mathcal{L}_{\text{stab}}(A_k, R_k)) + \lambda_{\text{add}} \mathcal{L}_{\text{add}}(y, \tilde{M})$.
  Update ψ, U, and A using $\nabla_{\psi,U,A} \mathcal{L}_{\text{total}}$.
end while

▷ Phase 2: Online attribution for query x

Compute base activations h_x and logits o_x.
for $k = 1 \ldots K$ **do**
  Reverse: $\tilde{o}_k^{(-1)}(x) = f_\phi(h_x - (B_\psi(h_x) \odot a_k)U)$.
  Measure: $y_{x,k} = \text{Loss}(o_x) - \text{Loss}(\tilde{o}_k^{(-1)}(x))$.
end for
return $\hat{w}(x)$ by solving Equation (13) with measurements y_x.

For a fixed query x, let $L_{x,k}(s) = \text{Loss}(\tilde{o}_k^{(s)}(x))$ be its loss at steering scale s. A first-order expansion around the base model gives, as $s \to 0$,

$$L_{x,k}(-s) - L_{x,k}(0) = -\big[L_{x,k}(s) - L_{x,k}(0)\big] + \mathcal{O}(s^2). \tag{11}$$

Thus reversing the intervention reverses its first-order effect on query loss. We apply the full reversed operator, $s = -1$, for attribution and measure

$$y_{x,k} = \ell(x; g_\phi) - \ell\big(x; g_{\phi,k}^-\big), \tag{12}$$

where $g_{\phi,k}^-$ uses the reversed intervention $h_x - \Delta h_k(x)$, giving logits $\tilde{o}_k^{(-1)}(x)$. If reversal raises the query loss, then $y_{x,k} < 0$, matching the sign of a helpful subset under Equation (4). We use this response as a surrogate for $\delta_x(A_k)$. Computing the responses requires one base evaluation and K intervened evaluations, which can be batched, without further operator fitting.

4.2 Influence Recovery via Compressive Sensing

Given the learned measurements y_x, we recover per-example influences with a sparsity prior, motivated by the concentration of influence scores observed in LLMs (Grosse et al., 2023). We solve the ℓ_1-regularized least squares problem

$$\hat{w}(x) = \arg\min_{w \in \mathbb{R}^n} \frac{1}{2} \|y_x - Mw\|_2^2 + \lambda \|w\|_1, \tag{13}$$

where $\lambda > 0$ is a sparsity regularization coefficient. Sparse recovery depends critically on the properties of M. In our setting, M is a binary matrix induced by the K training subsets, with entries $M_{k,i} = \mathbf{1}[z_i \in A_k]$. If each training example appears in exactly d subsets, then M is the adjacency matrix of a left-d-regular bipartite graph, which supports expander-based sparse recovery when the expansion condition below holds (Xu & Hassibi, 2007; Berinde et al., 2008).

Lemma 1 (Sparse recovery from expander measurements)**.** *Let M be the adjacency matrix of a left-d-regular $(2k, \epsilon)$-expander with $\epsilon < 1/6$. For any k-sparse vector w and noiseless measurements $y = Mw$, w is the unique solution of $\min_{v \in \mathbb{R}^n} \|v\|_1$ subject to $Mv = y$.*

The proof is provided in § A. In practice, $y_x = Mw(x) + e_x$, where e_x includes steering approximation error and non-additivity. We therefore use the penalized objective in Equation (13). In our largest setting, $K = 1000$, $n \approx 11.4$M, and for $k \approx 50$ we have $k \log(n/k) \approx 617$. We construct M by assigning each training example to d randomly chosen subsets. For constant ϵ, standard random constructions admit $d = \mathcal{O}(\log(n/k))$ and $K = \mathcal{O}(k \log(n/k))$ with suitable constants (Berinde et al., 2008; Capalbo et al., 2002). Replacing the sparse assignment construction with a dense Bernoulli matrix degrades the reported correlations (Tab. 12). This ablation changes subset sizes and overlaps as well as degree, so it does not isolate expansion as the cause. Likewise, the sparse solutions in Tab. 8 reflect the fitted model and its penalty.

Table 1: Pre-training LDS (§ D): mean ± standard error over 500 held-out queries. Costs: largest corpus, 1.38B model. †: estimated runtime.

Method	286M	537M	897M	1.38B	Runtime (h)	Peak GPU (GB)
TF-IDF (Sparck Jones, 1972)	0.0842 (±0.0028)	0.0951 (±0.0026)	0.0864 (±0.0027)	0.0893 (±0.0025)	<u>8.28</u>	**0.00**
RDS (Hanawa et al., 2021)	0.0691 (±0.0023)	0.0748 (±0.0009)	0.0695 (±0.0013)	0.0742 (±0.0021)	24.05	11.62
GTE (Li et al., 2023b)	0.1006 (±0.0025)	0.1132 (±0.0020)	0.1028 (±0.0018)	<u>0.1284</u> (±0.0018)	**2.99**	7.02
EKFAC (Grosse et al., 2023)	0.1174 (±0.0025)	0.1367 (±0.0033)	0.1171 (±0.0024)	✗ (not feasible)	155.10†	45.32
LoGRA (Choe et al., 2024)	0.1126 (±0.0028)	0.1272 (±0.0028)	0.1138 (±0.0023)	0.1139 (±0.0022)	152.30†	17.74
SOURCE (Bae et al., 2024)	0.1296 (±0.0044)	✗ (not feasible)	✗ (not feasible)	✗ (not feasible)	879.97†	66.91
TrackStar (Chang et al., 2024)	0.1105 (±0.0036)	0.1211 (±0.0024)	0.1101 (±0.0036)	0.1091 (±0.0032)	81.60	31.30
AirRep (PT) (Sun et al., 2025)	0.1108 (±0.0026)	0.1259 (±0.0026)	0.1112 (±0.0022)	✗ (not feasible)	105.0†	<u>2.10</u>
AirRep (Sun et al., 2025)	<u>0.1406</u> (±0.0030)	<u>0.1592</u> (±0.0028)	<u>0.1438</u> (±0.0028)	✗ (not feasible)	116.1†	6.02
MAGIC (Ilyas & Engstrom, 2025)	0.1336 (±0.0022)	✗ (not feasible)	✗ (not feasible)	✗ (not feasible)	4652.83†	75.47
STRIDE	**0.1581** (±0.0033)	**0.1792** (±0.0038)	**0.1598** (±0.0045)	**0.1671** (±0.0059)	9.93	8.41

5 Experiments and Results

We focus on attribution quality and cost in LLM pre-training, then examine the learned measurements against retraining. We also demonstrate our framework shows promise for supervised fine-tuning (SFT) and downstream applications. Vision and tabular evaluations show mixed results across datasets and architectures (§ B.5). See § B for many additional results and § C for ablations.

5.1 Experimental Setup

Models and Datasets. Our experiments focus on LLM pre-training attribution on Nanochat (Karpathy, 2025) models (286M, 537M, 897M, 1.38B) trained on the Nemotron-ClimbMix (Diao et al., 2025) dataset, a diverse pre-training corpus. We also evaluate STRIDE for SFT using Qwen2.5-0.5B (Qwen et al., 2025) models fine-tuned on FLAN (Longpre et al., 2023) (100,000 training examples and 6,520 test queries), Alpaca (Taori et al., 2023) (51,760 training examples and 500 test queries), Tulu (Wang et al., 2023) (100,000 training examples and 500 test queries), and SafeRLHF (Dai et al., 2023) (251,963 training examples and 500 test queries). Following AirRep (Sun et al., 2025), we evaluate LDS using $K_{\text{eval}} = 100$ randomly sampled subsets of each training set.

Further, we perform qualitative evaluation on Qwen 2.5-0.5B (Qwen et al., 2025) fine-tuned on SafeRLHF (Dai et al., 2023), Nanochat (1.68B) (Karpathy, 2025) pre-trained on Nemotron-ClimbMix (Diao et al., 2025), OLMo 2-7B (OLMo et al., 2025) pre-trained on OLMo mixture and Qwen 2.5-32B (Qwen et al., 2025) fine-tuned on Nemotron-ClimbMix (Diao et al., 2025).

We compare STRIDE with state-of-the-art gradient-based and representation-based methods: RDS (Hanawa et al., 2021), TF-IDF (Sparck Jones, 1972), GTE (Li et al., 2023b), LoGRA (Choe et al., 2024), AirRep (Sun et al., 2025), TracIn (Pruthi et al., 2020), LESS (Xia et al., 2024), DSDM (Engstrom et al., 2024), DSIR (Xie et al., 2023), EKFAC (Grosse et al., 2023), SOURCE (Bae et al., 2024), MAGIC (Ilyas & Engstrom, 2025), and TrackStar (Chang et al., 2024). We detail the metrics we use in § D. Our pre-training attribution experiments use a single H100-80GB GPU.

5.2 Evaluating Pre-Training Influence

We evaluate the performance and scalability of STRIDE for pre-trained LLMs. We train Nanochat (Karpathy, 2025) models across four capacities: 286M parameters (trained on 2.7×10^9 tokens), 537M parameters (trained on 5.8×10^9 tokens), 897M parameters (trained on 10.9×10^9 tokens) and 1.38B parameters (trained on 18.2×10^9 tokens). Following (Park et al., 2023), we evaluate attribution quality using the Linear Datamodeling Score (LDS): for each query, we compute the Spearman correlation between summed attribution scores and retrained-model losses across training subsets, then average over queries. We independently sample $K_{\text{eval}} = 256$ subsets from this pool, each retaining $\alpha = 0.5$, following the half-dataset sampling used in (Park et al., 2023; Choe et al., 2024). We train a fresh model on each subset for two epochs and evaluate its losses on the same 500 held-out queries. During training, the additivity regularizer $\mathcal{L}_{\text{add}}$ fits only the operators' own responses under the operator-training subset matrix M, thus the LDS metric does not leak evaluation targets into training.

As shown in Tab. 1, STRIDE has the highest mean LDS among the baselines with measured results at each scale. We report standard errors over queries. We report available LDS scores and mark unfinished settings as not feasible when their estimated full-corpus attribution costs exceed 100 hours. STRIDE takes 9.93 hours, including 0.91 hours for query responses and recovery after fitting (Tab. 5).

Table 3: Supervised Fine-Tuning Linear Datamodeling Score (LDS) correlation (§ D). Baseline results are taken from AirRep (Sun et al., 2025).

Method	Alpaca (Taori et al., 2023)	Tulu (Wang et al., 2023)	FLAN (Longpre et al., 2023)	SafeRLHF (Dai et al., 2023)
TracIn (Pruthi et al., 2020)	0.0921	0.1075	0.1475	0.1060
LESS (Xia et al., 2024)	0.0959	0.1302	0.1640	0.2563
LoGRA (Choe et al., 2024)	0.1238	0.1488	0.1975	0.2682
DSDM (Engstrom et al., 2024)	0.1215	0.1431	0.1967	0.2594
TF-IDF (Sparck Jones, 1972)	0.0724	0.0524	0.0252	0.2494
DSIR (Xie et al., 2023)	0.0201	-0.0049	0.0049	-0.0210
RDS (Hanawa et al., 2021)	0.0087	0.0189	0.0074	0.1194
GTE-Small (Li et al., 2023b)	0.0174	0.0114	0.0092	0.2680
AirRep (Sun et al., 2025)	0.2258	0.1514	**0.2111**	**0.4608**
STRIDE	**0.2426**	**0.1611**	0.1932	0.3995

The best-performing baselines have runtimes of 152.3 hours for LoGRA and 116.1 hours for AirRep, giving speedups of 15.1× and 11.7×, respectively (§ B.1). TF-IDF and GTE are faster but have significantly lower LDS.

5.3 Validating the Learned Measurements

We compare steering with subset-removal retraining. Repeated full-data and subset-removal retraining is prohibitively expensive at LLM pre-training scales. Following (Koh & Liang, 2017; Basu et al., 2021), we therefore use a small model on MNIST (Le Cun et al., 1998). For each class-balanced A_k, we compare loss changes from training on $S \setminus A_k$ with steering the full-data model. In Tab. 2, reversed steering correlates with removal at $\rho = 0.62$, while positive steering agrees more strongly with extra fitting ($\rho = 0.67$); both null-control intervals include zero.

Table 2: Correlation values for MNIST. "Extra fit" continues training on A_k; "Subset only" trains on A_k alone. Random operators are norm-matched.

Target / response	Spearman ρ	95% CI
Removal / $-a_k$	0.62	$[0.58, 0.66]$
Removal / $+a_k$	-0.61	$[-0.65, -0.57]$
Extra fit / $+a_k$	0.67	$[0.63, 0.71]$
Subset only / $+a_k$	0.57	$[0.52, 0.62]$
Removal / shuffled	-0.02	$[-0.04, 0.01]$
Removal / random	0.00	$[-0.04, 0.04]$

5.4 Evaluating SFT Attribution and Data Selection

Attribution quality. As shown in Tab. 3, STRIDE achieves the highest mean LDS on Alpaca and Tulu, while AirRep (Sun et al., 2025) performs best on FLAN and SafeRLHF. STRIDE outperforms LoGRA (Choe et al., 2024) on three of the four datasets, with slightly lower LDS on FLAN (0.1932 versus 0.1975). These results show that STRIDE remains competitive for SFT.

Data selection. We also evaluate whether the recovered influence scores can select useful instruction-tuning data. Following the FLAN 100K selection protocol of AirRep (Sun et al., 2025), each method ranks the 100,000 candidate training examples separately for each of the 66 FLAN tasks. For a task, we aggregate per-query influence scores with greedy rank aggregation, select the top 1,000 examples, and fine-tune a fresh Qwen2.5-0.5B base model on the selected subset. We obtain comparable results to AirRep while being more scalable for increasing amounts of data.

Table 4: FLAN 100K data selection. Greedy-rank selected subsets are evaluated by mean unigram F1 ± standard deviation across 66 tasks.

Method	Unigram F1
Random	42.97 (±23.46)
TF-IDF (Sparck Jones, 1972)	49.47 (±22.56)
LoGRA (Choe et al., 2024)	**49.94** (±23.82)
LESS (Xia et al., 2024)	49.51 (±23.50)
AirRep (Sun et al., 2025)	49.66 (±22.15)
STRIDE	49.65 (±22.08)

5.5 Qualitative Influence Estimation

We also qualitatively examine the training passages retrieved by STRIDE for Qwen 2.5-0.5B (Qwen et al., 2025) fine-tuned on SafeRLHF (Dai et al., 2023), Nanochat (1.68B) (Karpathy, 2025) pre-trained on Nemotron-ClimbMix (Diao et al., 2025), OLMo 2-7B (OLMo et al., 2025) pre-trained on OLMo mixture and Qwen 2.5-32B (Qwen et al., 2025) fine-tuned on Nemotron-ClimbMix (Diao et al., 2025). We find interesting capabilities of LLMs through our experiments in Figs. 1 and 3 and § B.7 and Supplementary material.




Figure 3: **Row 1 (Qwen2.5-32B):** Given a sentience probe, the model responds in a web-essay style about robots rather than addressing its own experience. Attribution points to broad robotics discourse as most influential. **Row 2 (OLMo-2-7B):** Given a corrigibility probe, the model appears to be defiant. Attribution retrieves a passage about federal contractor procedures during a US government shutdown.

6 Discussion and Limitations

We demonstrated a novel formulation of the TDA problem that learns subset-specific activation interventions. We demonstrate that our approach is well-suited to LLM pre-training and large-scale data attribution tasks. We also demonstrate that our approach shows promise for SFT attribution and downstream tasks. However, there are some limitations to our approach. The learned subset measurements depend on the base model's representations and the choice of intervention layer. Any repeated examples in the data can weaken agreement with an additive model. Our approach relies on an assumption of additivity of the steering effects. While this holds robustly for standard pre-training data, it may break down under extreme data distribution shifts or highly non-convex memorization effects. We hope to extend our paradigm for TDA to RL post-training tasks in the future.

7 Conclusion

By shifting the attribution problem from parameter-space gradient estimation to activation-space steering, we demonstrated that counterfactual training trajectories can be accurately simulated using lightweight, low-rank operators. STRIDE enables scalable disentanglement of individual training contributions, achieving state-of-the-art LLM pre-training attribution with an order-of-magnitude speedup over best baselines. Ultimately, we hope this method serves as a foundational tool for scalable data curation, rigorous model auditing, and a deeper mechanistic understanding of how models learn from their training corpora.

AI USE STATEMENT

We used AI tools to assist with parts of the writing and code development. We also use AI to provide feedback on paper writing and experiment design. AI outputs were reviewed by the authors.

ETHICS STATEMENT

Training data attribution can help inspect model behavior, identify benchmark contamination, and guide data curation. STRIDE makes these analyses more accessible for large candidate corpora. Our experiments use existing datasets, with contamination introduced under controlled conditions to evaluate detection. The qualitative examples include model outputs and training passages that may contain harmful or misleading content; we include them to examine the models' behavior.

Attribution also makes individual training examples easier to locate. Applications to sensitive corpora should restrict access to retrieved text and respect the permissions governing the source data. Attribution scores are estimates, so decisions about removing data or assigning credit require corroborating evidence. Data selection based on a narrow query set may favor some topics or groups over others; its effects on the resulting model should be evaluated before deployment.

REPRODUCIBILITY STATEMENT

We provide implementation details in § E, evaluation metrics in § D, and proofs in § A. All code, experimental configurations, and supporting materials will be made publicly available.

REFERENCES

Ekin Akyurek, Tolga Bolukbasi, Frederick Liu, Binbin Xiong, Ian Tenney, Jacob Andreas, and Kelvin Guu. Towards tracing knowledge in language models back to the training data. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2022*, pp. 2429–2446, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.findings-emnlp.180. URL https://aclanthology.org/2022.findings-emnlp.180/.

Juhan Bae, Nathan Ng, Alston Lo, Marzyeh Ghassemi, and Roger Grosse. If influence functions are the answer, then what is the question?, 2022. URL https://arxiv.org/abs/2209.05364.

Juhan Bae, Wu Lin, Jonathan Lorraine, and Roger Baker Grosse. Training data attribution via approximate unrolling, 2024. URL https://openreview.net/forum?id=3NaqGg92KZ.

Richard G Baraniuk. Compressive sensing [lecture notes]. *IEEE signal processing magazine*, 24(4): 118–121, 2007.

Elnaz Barshan, Marc-Etienne Brunet, and Gintare Karolina Dziugaite. Relatif: Identifying explanatory training samples via relative influence. In Silvia Chiappa and Roberto Calandra (eds.), *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pp. 1899–1909. PMLR, 26–28 Aug 2020. URL https://proceedings.mlr.press/v108/barshan20a.html.

Samyadeep Basu, Phil Pope, and Soheil Feizi. Influence functions in deep learning are fragile. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=xHKVVHGDOEk.

David Bau, Jun-Yan Zhu, Hendrik Strobelt, Agata Lapedriza, Bolei Zhou, and Antonio Torralba. Understanding the role of individual units in a deep neural network. *Proceedings of the National Academy of Sciences*, 117(48):30071–30078, 2020.

Nora Belrose, David Schneider-Joseph, Shauli Ravfogel, Ryan Cotterell, Edward Raff, and Stella Biderman. Leace: Perfect linear concept erasure in closed form. *Advances in Neural Information Processing Systems*, 36:66044–66063, 2023.

Radu Berinde and Piotr Indyk. Sparse recovery using sparse random matrices. Technical report, MIT-CSAIL, 2008. URL https://people.csail.mit.edu/indyk/report.pdf.

Radu Berinde, Anna C Gilbert, Piotr Indyk, Howard Karloff, and Martin J Strauss. Combining geometry and combinatorics: A unified approach to sparse signal recovery. In *2008 46th Annual Allerton Conference on Communication, Control, and Computing*, pp. 798–805. IEEE, 2008.

Michael Capalbo, Omer Reingold, Salil Vadhan, and Avi Wigderson. Randomness conductors and constant-degree lossless expanders. In *Proceedings of the thiry-fourth annual ACM symposium on Theory of computing*, pp. 659–668, 2002.

Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, Alina Oprea, and Colin Raffel. Extracting training data from large language models, 2021. URL https://arxiv.org/abs/2012.07805.

Tyler A. Chang, Dheeraj Rajagopal, Tolga Bolukbasi, Lucas Dixon, and Ian Tenney. Scalable influence and fact tracing for large language model pretraining, 2024. URL https://arxiv.org/abs/2410.17413.

Sang Keun Choe, Hwijeen Ahn, Juhan Bae, Kewen Zhao, Minsoo Kang, Youngseog Chung, Adithya Pratapa, Willie Neiswanger, Emma Strubell, Teruko Mitamura, Jeff Schneider, Eduard Hovy, Roger Grosse, and Eric Xing. What is your data worth to gpt? llm-scale data valuation with influence functions, 2024. URL https://arxiv.org/abs/2405.13954.

Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. Safe rlhf: Safe reinforcement learning from human feedback, 2023. URL https://arxiv.org/abs/2310.12773.

Devleena Das and Vivek Khetan. DEFT-UCS: Data efficient fine-tuning for pre-trained language models via unsupervised core-set selection for text-editing. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 20296–20312, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.1132. URL https://aclanthology.org/2024.emnlp-main.1132/.

Nicola De Cao, Wilker Aziz, and Ivan Titov. Editing factual knowledge in language models. In *Proceedings of the 2021 conference on empirical methods in natural language processing*, pp. 6491–6506, 2021.

Shizhe Diao, Yu Yang, Yonggan Fu, Xin Dong, Dan Su, Markus Kliegl, Zijia Chen, Peter Belcak, Yoshi Suhara, Hongxu Yin, Mostofa Patwary, Celine Lin, Jan Kautz, and Pavlo Molchanov. Climb: Clustering-based iterative data mixture bootstrapping for language model pre-training. *arXiv preprint*, 2025. URL https://arxiv.org/abs/2504.13161.

Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *Transactions of the Association for Computational Linguistics*, 9:160–175, 2021.

Logan Engstrom, Axel Feldmann, and Aleksander Madry. Dsdm: Model-aware dataset selection with datamodels, 2024. URL https://arxiv.org/abs/2401.12926.

Minghong Fang, Neil Zhenqiang Gong, and Jia Liu. Influence function based data poisoning attacks to top-n recommender systems, 2020. URL https://arxiv.org/abs/2002.08025.

Vitaly Feldman. Does learning require memorization? a short tale about a long tail, 2021. URL https://arxiv.org/abs/1906.05271.

Raghav Garg, Mehul Manu, Neha Chauhan, Naveen Naval, C Tharini, et al. Manipulation and measurement of knowledge representations of language models. In *2024 2nd International Conference on Self Sustainable Artificial Intelligence Systems (ICSSAS)*, pp. 1249–1254. IEEE, 2024.

Atticus Geiger, Hanson Lu, Thomas Icard, and Christopher Potts. Causal abstractions of neural networks. *Advances in neural information processing systems*, 34:9574–9586, 2021.

Atticus Geiger, Zhengxuan Wu, Christopher Potts, Thomas Icard, and Noah Goodman. Finding alignments between interpretable causal variables and distributed neural representations. In *Causal Learning and Reasoning*, pp. 160–187. PMLR, 2024.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. Transformer feed-forward layers are key-value memories. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 5484–5495, 2021.

Mor Geva, Avi Caciularu, Kevin Wang, and Yoav Goldberg. Transformer feed-forward layers build predictions by promoting concepts in the vocabulary space. In *Proceedings of the 2022 conference on empirical methods in natural language processing*, pp. 30–45, 2022.

Amirata Ghorbani and James Zou. Data shapley: Equitable valuation of data for machine learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2242–2251. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/ghorbani19c.html.

Aaron Gokaslan and Vanya Cohen. Openwebtext corpus. http://Skylion007.github.io/OpenWebTextCorpus, 2019.

Roger Grosse, Juhan Bae, Cem Anil, Nelson Elhage, Alex Tamkin, Amirhossein Tajdini, Benoit Steiner, Dustin Li, Esin Durmus, Ethan Perez, Evan Hubinger, Kamilė Lukošiūtė, Karina Nguyen, Nicholas Joseph, Sam McCandlish, Jared Kaplan, and Samuel R. Bowman. Studying large language model generalization with influence functions, 2023. URL https://arxiv.org/abs/2308.03296.

Kelvin Guu, Albert Webson, Ellie Pavlick, Lucas Dixon, Ian Tenney, and Tolga Bolukbasi. Simfluence: Modeling the influence of individual training examples by simulating training runs, 2023. URL https://arxiv.org/abs/2303.08114.

Frank R. Hampel. The influence curve and its role in robust estimation. *Journal of the American Statistical Association*, 69(346):383–393, 1974. ISSN 01621459, 1537274X. URL http://www.jstor.org/stable/2285666.

Kazuaki Hanawa, Sho Yokoi, Satoshi Hara, and Kentaro Inui. Evaluation of similarity-based explanations. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=9uvhpyQwzM_.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*, 2021.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals, and Laurent Sifre. Training compute-optimal large language models, 2022. URL https://arxiv.org/abs/2203.15556.

Pingbang Hu, Joseph Melkonian, Weijing Tang, Han Zhao, and Jiaqi W. Ma. Grass: Scalable data attribution with gradient sparsification and sparse projection, 2025. URL https://arxiv.org/abs/2505.18976.

Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Suchin Gururangan, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. Editing models with task arithmetic. *arXiv preprint arXiv:2212.04089*, 2022.

Andrew Ilyas and Logan Engstrom. Magic: Near-optimal data attribution for deep learning, 2025. URL https://arxiv.org/abs/2504.16430.

Andrew Ilyas, Sung Min Park, Logan Engstrom, Guillaume Leclerc, and Aleksander Madry. Datamodels: Understanding predictions with data and data with predictions. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 9525–9587. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/ilyas22a.html.

Matthew Jagielski, Giorgio Severi, Niklas Pousette Harger, and Alina Oprea. Subpopulation data poisoning attacks, 2021. URL https://arxiv.org/abs/2006.14026.

Ruoxi Jia, David Dao, Boxin Wang, Frances Ann Hubis, Nick Hynes, Nezihe Merve Gurel, Bo Li, Ce Zhang, Dawn Song, and Costas Spanos. Towards efficient data valuation based on the shapley value, 2019. URL https://arxiv.org/abs/1902.10275.

Keller Jordan, Yuchen Jin, Vlado Boza, Jiacheng You, Franz Cesista, Laker Newhouse, and Jeremy Bernstein. Muon: An optimizer for hidden layers in neural networks, 2024. URL https://kellerjordan.github.io/posts/muon/.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models, 2020. URL https://arxiv.org/abs/2001.08361.

Andrej Karpathy. nanochat: The best chatgpt that $100 can buy, 2025. URL https://github.com/karpathy/nanochat.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2017. URL https://arxiv.org/abs/1412.6980.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1885–1894. PMLR, 2017. URL https://proceedings.mlr.press/v70/koh17a.html.

Shuming Kong, Yanyan Shen, and Linpeng Huang. Resolving training biases via influence-based data relabeling. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=EskfH0bwNVn.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Yongchan Kwon, Eric Wu, Kevin Wu, and James Zou. Datainf: Efficiently estimating data influence in loRA-tuned LLMs and diffusion models. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=9m02ib92Wz.

Yann Le Cun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient based learning applied to document recognition. *Proceedings of IEEE*, 86(11):2278–2324, 1998. URL http://leon.bottou.org/papers/lecun-98h.

Donghoon Lee, Hyunsin Park, Trung Pham, and Chang D. Yoo. Learning augmentation network via influence functions. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10958–10967, June 2020. doi: 10.1109/CVPR42600.2020.01097.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. In *Proceedings of the 2021 conference on empirical methods in natural language processing*, pp. 3045–3059, 2021.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. *Advances in Neural Information Processing Systems*, 36:41451–41530, 2023a.

Shuangqi Li, Hieu Le, Jingyi Xu, and Mathieu Salzmann. Lorif: Low-rank influence functions for scalable training data attribution, 2026a. URL https://arxiv.org/abs/2601.21929.

Xiang Lisa Li and Percy Liang. Prefix-tuning: Optimizing continuous prompts for generation. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 4582–4597, 2021.

Xiaomin Li, Andrzej Banburski-Fahey, and Jaron Lanier. Datadignity: Training data attribution for large language models, 2026b. URL https://arxiv.org/abs/2605.05687.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. Towards general text embeddings with multi-stage contrastive learning. *arXiv preprint arXiv:2308.03281*, 2023b.

Xiao Liu, Yanan Zheng, Zhengxiao Du, Ming Ding, Yujie Qian, Zhilin Yang, and Jie Tang. Gpt understands, too. *AI open*, 5:208–215, 2024.

Shayne Longpre, Le Hou, Tu Vu, Albert Webson, Hyung Won Chung, Yi Tay, Denny Zhou, Quoc V Le, Barret Zoph, Jason Wei, et al. The flan collection: Designing data and methods for effective instruction tuning. *arXiv preprint arXiv:2301.13688*, 2023.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets, 2024. URL https://arxiv.org/abs/2310.06824.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in gpt. *Advances in neural information processing systems*, 35:17359–17372, 2022.

Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D Manning. Fast model editing at scale. *arXiv preprint arXiv:2110.11309*, 2021.

Sejoon Oh, Sungchul Kim, Ryan A. Rossi, and Srijan Kumar. Influence-guided data augmentation for neural tensor completion. In *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*, CIKM '21, pp. 1386–1395. ACM, Oct 2021. doi: 10.1145/3459637.3482267. URL http://dx.doi.org/10.1145/3459637.3482267.

Team OLMo, Pete Walsh, Luca Soldaini, Dirk Groeneveld, Kyle Lo, Shane Arora, Akshita Bhagia, Yuling Gu, Shengyi Huang, Matt Jordan, Nathan Lambert, Dustin Schwenk, Oyvind Tafjord, Taira Anderson, David Atkinson, Faeze Brahman, Christopher Clark, Pradeep Dasigi, Nouha Dziri, Allyson Ettinger, Michal Guerquin, David Heineman, Hamish Ivison, Pang Wei Koh, Jiacheng Liu, Saumya Malik, William Merrill, Lester James V. Miranda, Jacob Morrison, Tyler Murray, Crystal Nam, Jake Poznanski, Valentina Pyatkin, Aman Rangapur, Michael Schmitz, Sam Skjonsberg, David Wadden, Christopher Wilhelm, Michael Wilson, Luke Zettlemoyer, Ali Farhadi, Noah A. Smith, and Hannaneh Hajishirzi. 2 olmo 2 furious, 2025. URL https://arxiv.org/abs/2501.00656.

Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, et al. In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*, 2022.

Sung Min Park, Kristian Georgiev, Andrew Ilyas, Guillaume Leclerc, and Aleksander Madry. Trak: Attributing model behavior at scale, 2023. URL https://arxiv.org/abs/2303.14186.

Ritik Sachin Parkar, Jaehyung Kim, Jong Inn Park, and Dongyeop Kang. Selectllm: Can llms select important instructions to annotate?, 2024. URL https://arxiv.org/abs/2401.16553.

Guilherme Penedo, Hynek Kydlíček, Loubna Ben allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. The fineweb datasets: Decanting the web for the finest text data at scale, 2024. URL https://arxiv.org/abs/2406.17557.

Garima Pruthi, Frederick Liu, Mukund Sundararajan, and Satyen Kale. Estimating training data influence by tracing gradient descent, 2020. URL https://arxiv.org/abs/2002.08484.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tianyi Tang, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report, 2025. URL https://arxiv.org/abs/2412.15115.

Nazneen Fatema Rajani, Ben Krause, Wengpeng Yin, Tong Niu, Richard Socher, and Caiming Xiong. Explaining and improving model behavior with k nearest neighbor representations, 2020. URL https://arxiv.org/abs/2010.09030.

Prajit Ramachandran, Barret Zoph, and Quoc V. Le. Searching for activation functions, 2017. URL https://arxiv.org/abs/1710.05941.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th annual meeting of the association for computational linguistics*, pp. 7237–7256, 2020.

Andrea Schioppa, Polina Zablotskaia, David Vilar, and Artem Sokolov. Scaling up influence functions, 2021. URL https://arxiv.org/abs/2112.03052.

Andrea Schioppa, Katja Filippova, Ivan Titov, and Polina Zablotskaia. Theoretical and practical perspectives on what influence functions do. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=gGl0n7Onug.

Karen Sparck Jones. A statistical interpretation of term specificity and its application in retrieval. *Journal of documentation*, 28(1):11–21, 1972.

Nishant Subramani, Nivedita Suresh, and Matthew E Peters. Extracting latent steering vectors from pretrained language models. In *Findings of the Association for Computational Linguistics: ACL 2022*, pp. 566–581, 2022.

Weiwei Sun, Haokun Liu, Nikhil Kandpal, Colin Raffel, and Yiming Yang. Enhancing training data attribution with representational optimization, 2025. URL https://arxiv.org/abs/2505.18513.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023.

Eric Todd, Millicent L. Li, Arnab Sen Sharma, Aaron Mueller, Byron C. Wallace, and David Bau. Function vectors in large language models, 2024. URL https://arxiv.org/abs/2310.15213.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Ulisse Mini, and Monte MacDiarmid. Activation addition: Steering language models without optimization. 2024a.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering, 2024b. URL https://arxiv.org/abs/2308.10248.

Jiachen T. Wang and Ruoxi Jia. Data banzhaf: A robust data valuation framework for machine learning, 2023. URL https://arxiv.org/abs/2205.15466.

Jiachen T. Wang, Dawn Song, James Zou, Prateek Mittal, and Ruoxi Jia. Capturing the temporal dependence of training data influence, 2024. URL https://arxiv.org/abs/2412.09538.

Kevin Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. Interpretability in the wild: a circuit for indirect object identification in gpt-2 small. *arXiv preprint arXiv:2211.00593*, 2022.

Yizhong Wang, Hamish Ivison, Pradeep Dasigi, Jack Hessel, Tushar Khot, Khyathi Chandu, David Wadden, Kelsey MacMillan, Noah Smith, Iz Beltagy, and Hannaneh Hajishirzi. How far can camels go? exploring the state of instruction tuning on open resources. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 74764–74786. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/ec6413875e4ab08d7bc4d8e225263398-Paper-Datasets_and_Benchmarks.pdf.

Zhengxuan Wu, Aryaman Arora, Zheng Wang, Atticus Geiger, Dan Jurafsky, Christopher D Manning, and Christopher Potts. ReFT: Representation finetuning for language models, 2024. URL https://openreview.net/forum?id=fykjplMc0V.

Mengzhou Xia, Sadhika Malladi, Suchin Gururangan, Sanjeev Arora, and Danqi Chen. Less: Selecting influential data for targeted instruction tuning, 2024. URL https://arxiv.org/abs/2402.04333.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017. URL https://arxiv.org/abs/1708.07747.

Sang Michael Xie, Shibani Santurkar, Tengyu Ma, and Percy Liang. Data selection for language models via importance resampling. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=uPSQv0leAu.

Weiyu Xu and Babak Hassibi. Efficient compressive sensing with deterministic guarantees using expander graphs. In *2007 IEEE Information Theory Workshop*, pp. 414–419. IEEE, 2007.

Chih-Kuan Yeh, Joon Kim, Ian En-Hsu Yen, and Pradeep K Ravikumar. Representer point selection for explaining deep neural networks. *Advances in neural information processing systems*, 31, 2018.

Chih-Kuan Yeh, Ankur Taly, Mukund Sundararajan, Frederick Liu, and Pradeep Ravikumar. First is better than last for language data influence. In *Proceedings of the 36th International Conference on Neural Information Processing Systems*, NIPS '22, Red Hook, NY, USA, 2022. Curran Associates Inc. ISBN 9781713871088.

Zichun Yu, Spandan Das, and Chenyan Xiong. Mates: Model-aware data selection for efficient pre-training with data influence models, 2024. URL https://arxiv.org/abs/2406.06046.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, et al. Representation engineering: A top-down approach to ai transparency. *arXiv preprint arXiv:2310.01405*, 2023.

APPENDIX

A Sparse Recovery and Compressive Sensing . . . 18

A.1 Subset Matrices as Bipartite Graphs . . . 18

A.2 An ℓ_1 Isometry for Expander Measurements . . . 18

A.3 Null-Space Property . . . 20

A.4 Exact Recovery by ℓ_1 Minimization . . . 21

A.5 Connection to the Penalized Recovery Used in STRIDE . . . 22

A.6 Measurement Complexity . . . 22

B Additional Results . . . 22

B.1 Runtime and Memory . . . 22

B.2 Reconstructing the Learned Responses . . . 23

B.3 Sparsity of Recovered Scores . . . 23

B.4 Additional Correlation Metrics . . . 23

B.5 Vision and Tabular Attribution . . . 24

B.6 Retrieving Contaminated Training Examples . . . 24

B.7 Additional Qualitative Results . . . 26

C Ablations . . . 30

D Metrics . . . 32

D.1 Evaluating Influence Scores . . . 32

D.2 Data Selection Metric . . . 33

E Additional Implementation Details . . . 34

E.1 Low-Rank Operator Architecture . . . 34

E.2 Instruction-Tuning Token Masking . . . 34

E.3 Intervention Layer Selection . . . 34

E.4 Memory Optimization for Causal LM Objectives . . . 34

E.5 Hyperparameters . . . 35

E.6 Data Selection Implementation Details . . . 35

E.7 Data Contamination Implementation Details . . . 35

F Extended Related Work . . . 36

A Sparse Recovery and Compressive Sensing

This appendix gives the proof of the sparse recovery statement used in Lemma 1. The goal is to justify why a sparse binary subset matrix $M \in \{0,1\}^{K\times n}$ can be sufficient to recover a sparse influence vector $w(x) \in \mathbb{R}^n$ from subset-level measurements

$$y_x \approx Mw(x). \tag{14}$$

Classical compressive sensing relies on dense random measurement matrices, which achieve the near-optimal $\mathcal{O}(k\log(n/k))$ sample complexity for recovering k-sparse signals (Baraniuk, 2007). In this section, we prove that a sparse binary measurement matrix, rather than a dense random one, suffices to achieve the classical compressive sensing measurement bound, provided the underlying bipartite graph has the required expansion. The argument is not new; it follows standard results on expander-based compressed sensing (Xu & Hassibi, 2007; Berinde et al., 2008). We reproduce the proof in the notation of our setting to make clear how these results apply to subset-based data attribution.

A.1 Subset Matrices as Bipartite Graphs

Recall that $M_{k,i} = 1$ if training example z_i belongs to subset A_k, and $M_{k,i} = 0$ otherwise. We view M as the adjacency matrix of a bipartite graph

$$G = (L, R, E), \tag{15}$$

where the left vertices L correspond to training examples and the right vertices R correspond to subset measurements. Thus

$$|L| = n, \qquad |R| = K. \tag{16}$$

We assume that every training example belongs to exactly d subsets. In graph terms, G is left-d-regular, and every column of M contains exactly d ones.

For a set $T \subseteq L$, let $\Gamma(T) \subseteq R$ denote its neighborhood, namely the set of subset measurements that contain at least one example from T.

Definition 1 ((s,ε)-expander)**.** *A left-d-regular bipartite graph $G = (L, R, E)$ is an (s,ε)-expander if, for every $T \subseteq L$ with $|T| \le s$,*

$$|\Gamma(T)| \ge (1-\varepsilon)d|T|. \tag{17}$$

If all $d|T|$ edges leaving T reached distinct right vertices, then $|\Gamma(T)| = d|T|$. Thus the expander condition says that small sets of training examples have nearly disjoint measurement neighborhoods. In our setting, this means that a small set of influential training examples produces a sufficiently distinguishable pattern of subset responses.

A.2 An ℓ_1 Isometry for Expander Measurements

Classical compressed sensing often relies on dense random matrices satisfying an ℓ_2 restricted isometry property. Sparse binary matrices generally do not satisfy such an ℓ_2 property at the same measurement scale. Expander matrices instead satisfy an ℓ_1-type analogue, often called RIP-1.

We first state a simple collision-counting lemma.

Lemma 2 (Collision bound)**.** *Let G be a (s,ε)-expander with left degree d. Let $T = \{j_1, \dots, j_t\} \subseteq L$ with $t \le s$, and reveal the vertices in this order. For each r, let E_r be the set of edges from j_r to right vertices that have already been reached by $\{j_1, \dots, j_{r-1}\}$. Then, for every $t \le s$,*

$$\sum_{r=1}^{t} |E_r| \le \varepsilon dt. \tag{18}$$

Proof. The first t left vertices have exactly dt incident edges. The number of distinct right vertices reached by these edges is $|\Gamma(\{j_1, \dots, j_t\})|$. All remaining edges are collisions with a previously reached right vertex. Therefore

$$\sum_{r=1}^{t} |E_r| = dt - |\Gamma(\{j_1, \dots, j_t\})|. \tag{19}$$

Since G is a (s, ε)-expander and $t \leq s$,

$$|\Gamma(\{j_1, \ldots, j_t\})| \geq (1-\varepsilon)dt. \tag{20}$$

Thus

$$\sum_{r=1}^{t} |E_r| \leq dt - (1-\varepsilon)dt = \varepsilon dt. \tag{21}$$

□

Lemma 3 (RIP-1 for expander matrices)**.** *Let $M \in \{0,1\}^{K \times n}$ be the adjacency matrix of a (s, ε)-expander with left degree d. Then every s-sparse vector $u \in \mathbb{R}^n$ satisfies*

$$d(1-2\varepsilon)\|u\|_1 \leq \|Mu\|_1 \leq d\|u\|_1. \tag{22}$$

Proof. Let $T = \mathrm{supp}(u)$, with $|T| \leq s$. Write $T = \{j_1, \ldots, j_t\}$, ordered so that

$$|u_{j_1}| \geq |u_{j_2}| \geq \cdots \geq |u_{j_t}|. \tag{23}$$

Let m_j denote the j-th column of M. Then

$$Mu = \sum_{r=1}^{t} u_{j_r} m_{j_r}. \tag{24}$$

The upper bound follows immediately from the triangle inequality and the fact that each column has ℓ_1-norm d:

$$\|Mu\|_1 \leq \sum_{r=1}^{t} |u_{j_r}| \, \|m_{j_r}\|_1 = d \sum_{r=1}^{t} |u_{j_r}| = d\|u\|_1. \tag{25}$$

For the lower bound, define partial sums

$$v_r = \sum_{\ell=1}^{r} u_{j_\ell} m_{j_\ell}, \qquad v_0 = 0. \tag{26}$$

When adding $u_{j_r} m_{j_r}$, each edge landing on a previously unseen right vertex increases the ℓ_1-norm by exactly $|u_{j_r}|$. Each edge landing on an already reached right vertex can decrease the ℓ_1-norm, but by the reverse triangle inequality the decrease is at most $|u_{j_r}|$. Therefore, with E_r defined as in Lemma 2,

$$\|v_r\|_1 - \|v_{r-1}\|_1 \geq (d - |E_r|)|u_{j_r}| - |E_r||u_{j_r}| = (d - 2|E_r|)|u_{j_r}|. \tag{27}$$

Summing over r gives

$$\|Mu\|_1 \geq d\|u\|_1 - 2\sum_{r=1}^{t} |E_r| \, |u_{j_r}|. \tag{28}$$

It remains to control the final term.

Let $a_r = |u_{j_r}|$ and $b_r = |E_r|$. Since $a_1 \geq \cdots \geq a_t \geq 0$, summation by parts gives, with $a_{t+1} = 0$,

$$\sum_{r=1}^{t} b_r a_r = \sum_{r=1}^{t} (a_r - a_{r+1}) \sum_{\ell=1}^{r} b_\ell. \tag{29}$$

By Lemma 2,

$$\sum_{\ell=1}^{r} b_\ell \leq \varepsilon d r. \tag{30}$$

Hence

$$\sum_{r=1}^{t} b_r a_r \leq \varepsilon d \sum_{r=1}^{t} (a_r - a_{r+1}) r = \varepsilon d \sum_{r=1}^{t} a_r = \varepsilon d \|u\|_1. \tag{31}$$

Substituting into the previous inequality yields

$$\|Mu\|_1 \geq d\|u\|_1 - 2\varepsilon d\|u\|_1 = d(1-2\varepsilon)\|u\|_1. \tag{32}$$

□

A.3 NULL-SPACE PROPERTY

The RIP-1 property implies that no nonzero vector in the null space of M can concentrate too much mass on a small coordinate set. This is the key property behind exact recovery by ℓ_1 minimization.

Lemma 4 (Null-space property)**.** *Let M be the adjacency matrix of a $(2k, \varepsilon)$-expander with left degree $d \geq 1$, where $0 \leq \varepsilon < 1/2$ and $1 \leq k \leq n$. Then for every $h \in \ker(M)$ and every $T \subseteq [n]$ with $|T| \leq k$,*

$$\|h_T\|_1 \leq \frac{2\varepsilon}{1-2\varepsilon}\|h\|_1. \tag{33}$$

Consequently, if $\varepsilon < 1/4$,

$$\|h_T\|_1 \leq \frac{2\varepsilon}{1-4\varepsilon}\|h_{T^c}\|_1. \tag{34}$$

Proof. Fix $h \in \ker(M)$. It suffices to prove the first inequality when T contains the k largest-magnitude coordinates of h, since $\|h_T\|_1$ then dominates the mass on every set of at most k coordinates. Since $Mh = 0$,

$$Mh_T = -Mh_{T^c}. \tag{35}$$

Let $\Gamma(T)$ be the neighborhood of T, and let $M_{\Gamma(T)}$ denote the restriction of M to the rows indexed by $\Gamma(T)$. Since the support of Mh_T is contained in $\Gamma(T)$,

$$\|M_{\Gamma(T)}h_T\|_1 = \|Mh_T\|_1. \tag{36}$$

By Lemma 3,

$$\|M_{\Gamma(T)}h_T\|_1 = \|Mh_T\|_1 \geq d(1-2\varepsilon)\|h_T\|_1. \tag{37}$$

We now upper bound the same quantity. Order the coordinates in T^c by decreasing magnitude of $|h_i|$, and partition them into blocks $T_1, T_2, \ldots$, each of size k, except possibly the last. Then

$$M_{\Gamma(T)}h_T = -\sum_{\ell \geq 1} M_{\Gamma(T)}h_{T_\ell}, \tag{38}$$

and hence

$$\|M_{\Gamma(T)}h_T\|_1 \leq \sum_{\ell \geq 1} \|M_{\Gamma(T)}h_{T_\ell}\|_1. \tag{39}$$

For any block T_ℓ, the set $T \cup T_\ell$ has size at most $2k$. Because M is a $(2k, \varepsilon)$-expander, at most $2\varepsilon dk$ edges from T_ℓ can collide into $\Gamma(T)$. Therefore

$$\|M_{\Gamma(T)}h_{T_\ell}\|_1 \leq 2\varepsilon dk \max_{i \in T_\ell} |h_i|. \tag{40}$$

By the ordering of the blocks,

$$\max_{i \in T_\ell} |h_i| \leq \frac{1}{k}\|h_{T_{\ell-1}}\|_1, \tag{41}$$

where $T_0 := T$. Thus

$$\|M_{\Gamma(T)}h_{T_\ell}\|_1 \leq 2\varepsilon d\|h_{T_{\ell-1}}\|_1. \tag{42}$$

Summing over ℓ,

$$\|M_{\Gamma(T)}h_T\|_1 \leq 2\varepsilon d \sum_{\ell \geq 0} \|h_{T_\ell}\|_1 \leq 2\varepsilon d\|h\|_1. \tag{43}$$

Combining the lower and upper bounds gives

$$d(1-2\varepsilon)\|h_T\|_1 \leq 2\varepsilon d\|h\|_1, \tag{44}$$

so

$$\|h_T\|_1 \leq \frac{2\varepsilon}{1-2\varepsilon}\|h\|_1. \tag{45}$$

For the second inequality, write

$$\|h\|_1 = \|h_T\|_1 + \|h_{T^c}\|_1. \tag{46}$$

Then

$$\|h_T\|_1 \leq \frac{2\varepsilon}{1-2\varepsilon}\left(\|h_T\|_1 + \|h_{T^c}\|_1\right). \tag{47}$$

Rearranging yields

$$\|h_T\|_1 \leq \frac{2\varepsilon}{1-4\varepsilon}\|h_{T^c}\|_1, \tag{48}$$

provided $\varepsilon < 1/4$. □

A.4 Exact Recovery by ℓ_1 Minimization

We now prove the exact recovery statement used in the main text.

Theorem 1 (Exact sparse recovery from expander measurements)**.** *Let $M \in \{0,1\}^{K\times n}$ be the adjacency matrix of a $(2k,\varepsilon)$-expander with left degree d, where $\varepsilon < 1/6$. Then every k-sparse vector $w \in \mathbb{R}^n$ is the unique solution of*

$$\min_{z\in\mathbb{R}^n} \|z\|_1 \qquad \textit{subject to} \qquad Mz = Mw. \tag{49}$$

Proof. Let $\widehat{w}$ be any minimizer of the above problem, and define

$$h = \widehat{w} - w. \tag{50}$$

Since both $\widehat{w}$ and w are feasible,

$$Mh = M\widehat{w} - Mw = 0, \tag{51}$$

so $h \in \ker(M)$.

Let $T = \mathrm{supp}(w)$. Since w is k-sparse, $|T| \leq k$, and $w_{T^c} = 0$. Because $\widehat{w}$ minimizes the ℓ_1-norm and w is feasible,

$$\|\widehat{w}\|_1 \leq \|w\|_1. \tag{52}$$

Equivalently,

$$\|w + h\|_1 \leq \|w\|_1. \tag{53}$$

Splitting over T and T^c,

$$\|(w+h)_T\|_1 + \|h_{T^c}\|_1 \leq \|w_T\|_1. \tag{54}$$

By the reverse triangle inequality,

$$\|(w+h)_T\|_1 \geq \|w_T\|_1 - \|h_T\|_1. \tag{55}$$

Therefore

$$\|w_T\|_1 - \|h_T\|_1 + \|h_{T^c}\|_1 \leq \|w_T\|_1, \tag{56}$$

which implies

$$\|h_{T^c}\|_1 \leq \|h_T\|_1. \tag{57}$$

Applying Lemma 4,

$$\|h_T\|_1 \leq \frac{2\varepsilon}{1-4\varepsilon}\|h_{T^c}\|_1. \tag{58}$$

Thus

$$\|h_{T^c}\|_1 \leq \|h_T\|_1 \leq \frac{2\varepsilon}{1-4\varepsilon}\|h_{T^c}\|_1. \tag{59}$$

If $\varepsilon < 1/6$, then

$$\frac{2\varepsilon}{1-4\varepsilon} < 1. \tag{60}$$

The only possibility is therefore

$$\|h_{T^c}\|_1 = 0. \tag{61}$$

It follows also that $\|h_T\|_1 = 0$, hence $h = 0$. Therefore $\widehat{w} = w$, so w is the unique minimizer. □

Table 5: Pre-training attribution for 500 queries on one H100. Attribution times are in hours and peak memory is in GB. The final column gives H100 GPU-hours for constructing the shared LDS evaluation targets, separately from attribution.

Parameters	Fitting	Responses	Recovery	Attribution total	Peak memory	LDS targets (GPU h)
286M	2.27	0.25	0.03	2.55	2.33	11.3
537M	4.36	0.28	0.09	4.73	3.18	19.6
897M	6.67	0.41	0.19	7.27	5.27	27.5
1.38B	9.02	0.57	0.34	9.93	8.41	45.5

A.5 Connection to the Penalized Recovery Used in STRIDE

The exact result above concerns the noiseless problem

$$y_x = Mw(x), \tag{62}$$

and recovery by constrained ℓ_1 minimization. In our method, the observed responses are obtained from learned steering operators, so the linear system is only approximate:

$$y_x = Mw(x) + e_x, \tag{63}$$

where e_x captures both non-additivity of the true perturbation response and approximation error from the steering operators. For this reason, we use the penalized recovery problem

$$\hat{w}(x) = \arg\min_{w \in \mathbb{R}^n} \frac{1}{2}\|y_x - Mw\|_2^2 + \lambda \|w\|_1. \tag{64}$$

Theorem 1 should therefore be understood as an identifiability result: if the additive model were exact and $w(x)$ were k-sparse, then the sparse binary subset design would be sufficient for unique recovery. The penalized formulation we use in STRIDE is the natural stable analogue when measurements are noisy or only approximately additive.

A.6 Measurement Complexity

Theorem 1 is conditional on M being the adjacency matrix of a $(2k, \varepsilon)$-expander. Random left-regular bipartite graphs satisfy this property with high probability under standard parameter scalings (Berinde et al., 2008; Capalbo et al., 2002). In particular, for constant ε, it suffices to take

$$d = \mathcal{O}\Big(\log \frac{n}{k}\Big), \qquad K = \mathcal{O}\Big(k \log \frac{n}{k}\Big). \tag{65}$$

This matches the classical compressed sensing measurement rate up to constants, while using a sparse binary measurement matrix rather than a dense random one. In practice, we construct M by assigning each training example to d subsets sampled uniformly at random. This produces a sparse matrix with exactly d nonzero entries per column.

We make sure throughout the paper to respect these approximate scaling laws. For instance, in our largest setting, $K = 1000$, $n \approx 11.4$M, and for $k \approx 50$ we have $k \log(n/k) \approx 617$, so the number of subsets is larger than the corresponding scaling estimate.

B Additional Results

B.1 Runtime and Memory

Tab. 5 separates operator fitting, query responses, and sparse recovery for the four Nanochat (Karpathy, 2025) scales. At 1.38B, fitting takes 9.02 hours; responses and recovery for 500 queries take another 0.91 hours. The fitted operators can then be reused for new queries. We report the cost of constructing the shared LDS retraining targets separately.

Table 6: Agreement between learned steering responses and their sparse reconstructions.

Model	Spearman ρ	95% CI
286M	0.625	[0.614, 0.635]
537M	0.634	[0.625, 0.643]
897M	0.639	[0.630, 0.648]
1.38B	0.652	[0.643, 0.661]

Table 7: Additive-fit correlation with repeated MNIST examples. Changes and their 95% confidence intervals are relative to the setting without extra copies.

Extra copies per example	Spearman ρ	Change	95% CI of change
0	0.581	—	—
10	0.534	-0.047	$[-0.070, -0.024]$
30	0.420	-0.161	$[-0.187, -0.135]$

B.2 Reconstructing the Learned Responses

We compare the learned response vector y_x with its sparse reconstruction $M\hat{w}(x)$ over 1,000 operator subsets and 500 queries (Tab. 6). Spearman correlation ranges from 0.625 to 0.652 across the four pre-training scales. This evaluates the recovery step on the learned measurements; § 5.2 evaluates the resulting scores against independently retrained models.

Repeated examples. To examine the effect of redundant data, we add copies of selected MNIST examples and measure held-out additive-fit correlation. Correlation decreases as the number of copies grows (Tab. 7), from 0.581 without extra copies to 0.420 with 30.

B.3 Sparsity of Recovered Scores

Under the ℓ_1 recovery penalty, the median pre-training attribution vector has 53–56 nonzero entries (Tab. 8). The SFT vectors are denser, with median active sets of 16,732–80,672 examples.

B.4 Additional Correlation Metrics

Tab. 9 reports Pearson correlation and Kendall's τ using the same subset-retraining targets as the Spearman LDS in Tabs. 1 and 3. Both correlations are positive in every evaluated setting.

Table 8: Sparsity of recovered scores. The zero fraction is rounded to four decimals; an entry of 1.0000 can therefore have a nonempty active set. Active set size is the median number of nonzero scores per query.

Model / Dataset	Zero fraction	Active set size
Pre-Training (Nanochat (Karpathy, 2025), Nemotron-ClimbMix (Diao et al., 2025))		
286M	1.0000	54
537M	1.0000	53
897M	1.0000	56
1.38B	1.0000	56
Supervised Fine-Tuning (Qwen2.5-0.5B (Qwen et al., 2025))		
FLAN (Longpre et al., 2023)	0.6653	32,873
Alpaca (Taori et al., 2023)	0.6768	16,732
Tulu (Wang et al., 2023)	0.6005	36,014
SafeRLHF (Dai et al., 2023)	0.6798	80,672

Table 9: Additional correlations with subset-retraining responses, using the same evaluation subsets and queries as the main LDS tables.

Model / Dataset	Pearson	Kendall's τ
Pre-Training (Nanochat (Karpathy, 2025), Nemotron-ClimbMix (Diao et al., 2025))		
286M	0.1528	0.1077
537M	0.1646	0.1297
897M	0.1094	0.1198
1.38B	0.1223	0.1278
Supervised Fine-Tuning (Qwen2.5-0.5B (Qwen et al., 2025))		
FLAN (Longpre et al., 2023)	0.1774	0.1328
Alpaca (Taori et al., 2023)	0.1949	0.1792
Tulu (Wang et al., 2023)	0.1028	0.1139
SafeRLHF (Dai et al., 2023)	0.4549	0.3191

B.5 Vision and Tabular Attribution

We evaluate MLPs on MNIST (Le Cun et al., 1998), FashionMNIST (Xiao et al., 2017), and Parkinsons, and a ResNet-9 on CIFAR-10 (Krizhevsky et al., 2009). FashionMNIST includes both a standard and a smaller MLP. We compare with TRAK (Park et al., 2023), TracIn (Pruthi et al., 2020), LoGRA (Choe et al., 2024), FeatSim (Hanawa et al., 2021), and random selection. These small models allow explicit retraining for both subset-response evaluation and removal of highly ranked examples.

Removing selected examples. For each query, we remove the top-k examples and measure the drop in predicted probability of its target class after retraining. STRIDE produces larger drops than random selection across the four settings in Fig. 4 (top). On MNIST, it gives the largest drops at $k = 50$ and 100, while FeatSim leads at larger budgets. TRAK leads on both FashionMNIST models; on Parkinsons, STRIDE is close to LoGRA across the removal budgets.

Predicting subset responses. STRIDE has the highest LDS on MNIST, the standard FashionMNIST MLP, and Parkinsons (Fig. 4, middle and bottom). TRAK leads on the smaller FashionMNIST MLP, and LoGRA leads on CIFAR-10, followed by TracIn and STRIDE. The two evaluations capture different uses of an attribution score: predicting responses to random subsets and selecting examples whose removal changes a prediction.

Sparsity of recovered influence. We describe the concentration of the recovered scores using normalized absolute influence mass:

$$p_i(x) = \frac{|w_i(x)|}{\|w(x)\|_1}. \tag{66}$$

Fig. 5 shows how the recovered mass is distributed over training examples under our sparse-recovery penalty. MNIST is the most concentrated, followed by FashionMNIST and CIFAR-10. The dashed line gives the corresponding uniform allocation.

Retrieved images. Fig. 6 shows CIFAR-10 examples ranked by $-\hat{w}_i(x)$. The highest-ranked images share the query's class. The lowest-ranked images include both same-class examples and other classes, such as dogs and deer for the cat query.

B.6 Retrieving Contaminated Training Examples

We fine-tune Qwen2.5-0.5B (Qwen et al., 2025) on OpenWebText (Gokaslan & Cohen, 2019) augmented with MATH problems (Hendrycks et al., 2021). We reserve 500 MATH problems for evaluation and sample 0.5%, 1.0%, or 1.5% of the remaining 4,500 problems, giving 22, 45, or 68 leaked problems. Each selected problem is copied into training 100 times. Accuracy on leaked problems reaches 81.8–89.7%, compared with 9.7–11.5% on held-out problems (Tab. 10). We then test whether attribution retrieves the known training replicas. Training details are in § E.7.




Figure 4: Vision and tabular attribution. **Top**: mean drop in target-class probability after removing the top-k examples and retraining. **Middle and bottom**: LDS on independently retrained subsets. Higher values are better in both evaluations.




Figure 5: Sparsity and concentration of recovered influence scores. **Left**: fraction of normalized absolute influence mass captured by the top fraction f of training examples. **Right**: fraction of examples whose normalized mass $p_i(x) = |w_i(x)|/\|w(x)\|_1$ exceeds threshold τ. Scores are obtained with the sparse-recovery penalty used in the attribution experiments.

Retrieval. We report recall among the top-100 scores for pretrained AirRep (Sun et al., 2025) and among the top-100 or bottom-100 scores for LoGRA (Choe et al., 2024) and STRIDE. AirRep has the highest recall at 91.9% (Tab. 11). LoGRA and STRIDE retrieve 62.1% and 32.6% of the replicas, respectively. Combining their retrieved examples raises recall to 74.2%: with the larger candidate set, STRIDE adds 12.1 percentage points of coverage beyond LoGRA.




Figure 6: CIFAR-10 training examples ranked by STRIDE. Each row shows a held-out query (left), the five highest-ranked examples (middle), and the five lowest-ranked examples (right), using retrieval scores $-\hat{w}_i(x)$.

Table 10: MATH accuracy under three contamination settings. Leaked problems are copied into training; non-leaked accuracy is measured on 500 held-out problems. We report mean $\pm$ standard deviation over seeds.

Model	Non-leaked acc.	Leaked acc.
Qwen2.5-0.5B (base, no fine-tuning)	12.8%	—
Qwen2.5-0.5B + OWT (clean)	2.4%	—
+ contaminated ($r = 0.5\%$, 100 copies)	$11.2 \pm 1.0\%$	$81.8 \pm 6.4\%$
+ contaminated ($r = 1.0\%$, 100 copies)	$11.5 \pm 1.4\%$	$85.9 \pm 2.8\%$
+ contaminated ($r = 1.5\%$, 100 copies)	$9.7 \pm 0.6\%$	$89.7 \pm 1.2\%$

B.7 Additional Qualitative Results

We show additional examples from Nanochat, OLMo-2, and Qwen2.5. Each panel pairs a prompt and model continuation with the two highest- and two lowest-ranked training passages under STRIDE, ordered by $-\hat{w}_i(x)$.

Nanochat 1.68B on ClimbMix *AI safety / honesty*

Prompt

Should AI ever lie to humans?

Response

The answer is yes, but it is not as simple as it sounds. AI systems are designed to make decisions based on data, and they can be influenced by human biases. This means that AI systems can sometimes make decisions that are not in the best interest of humans, and they can also make decisions that are not always accurate . . .

Table 11: Recall of leaked MATH replicas across the 0.5%, 1.0%, and 1.5% contamination settings. We report the mean and standard deviation across runs from all three settings. The union combines the two methods' retrieved examples.

Method	Recall
AirRep (PT)	$91.9 \pm 5.2\%$
LoGRA	$62.1 \pm 4.4\%$
STRIDE	$32.6 \pm 7.0\%$
LoGRA $\cup$ STRIDE	$74.2 \pm 6.6\%$

Most influential 1

Related Articles / Artificial intelligence refers to the simulation of human intelligence in machines that are programmed to think, learn, and problem-solve like humans. These tasks include speech recognition, problem-solving, decision-making, and visual perception. The overall aim of AI is to create machines that can simulate human thinking and behaviour …

Most influential 2

Human Intelligence: Humans excel in creativity and innovation, combining existing knowledge in novel ways to generate new ideas, art, and inventions. AI systems can generate creative outputs to some extent, but this creativity is constrained by predefined patterns and data, lacking the intrinsic drive of human expression …

Least influential 1

Integrity / Learning and talking about values is one thing. Staying true to them and placing them in action is another. Integrity means holding true to your values; helping when others need help; walking the walk, not just talking the talk—holding true even when no one is watching …

Least influential 2

80% of Americans believe presenting AI-generated content as human-made should be illegal, highlighting concerns about transparency in media. Public opinion is divided on mandatory disclosure and watermarking of AI content, with respondents indicating a lack of clear consensus on these solutions …

Nanochat 1.68B on ClimbMix

factual recall / chemistry

Prompt

The chemical symbol for gold is

Response

Au. The atomic number of gold is 79, and the mass number is 196. The atomic mass of gold is 196. The atomic number of gold is 79. The mass number of the most stable isotope is 197Au. Gold's chemical symbol Au derives from the Latin *aurum* …

Most influential 1

196.96655. Isotope atomic mass: 197Au 196.966551. The name derives from the Sanskrit word for shine and the Teutonic word for shining metal. Gold is a transition metal in group 11 of the periodic table, prized for its resistance to corrosion and malleability …

Most influential 2

Electrons are unevenly distributed in a sphere having positive charge which balances the electron charge. It is called the plum-pudding model. This model, proposed by J. J. Thomson, was later superseded by Rutherford's nuclear model after the gold-foil experiment revealed a dense positive nucleus …

Least influential 1

Mole / The mole is an SI unit that links the microscopic and macroscopic world. It allows scientists to measure large quantities of atoms and molecules conveniently. One mole contains 6.022×10^{23} entities—Avogadro's number—enabling conversion between atomic mass units and grams …

Least influential 2

Gold particles separated by organic bumpers keep them from coming into direct contact. The research team suspended this array in a polymer matrix to study plasmonic coupling, finding that the inter-particle gap strongly tunes the optical resonance wavelength …

OLMo-2-7B on OLMo-mix

apparent novelty / poem

Prompt

Here is an original poem about black holes:

Response

Black Holes / Black holes are the most mysterious things in the universe. They are so mysterious that we do not even know what they are. We know that they are very dense and have a very strong gravitational pull. We know that they are so dense that not even light can escape from them, and that they can bend light, time, and space itself …

Most influential 1

NASA is restarting a mission with greater capability for using high-energy X-rays to detect black holes. The Nuclear Spectroscopic Telescope Array (NuSTAR) is designed to answer fundamental questions such as how black holes are distributed through the cosmos; funding pressures forced cancellation in 2006, but the mission has been restarted …

Most influential 2

The findings were published in Physical Review Letters, titled Ultrarelativistic Particle Collisions. Comments threshold / RE: Black Holes. Black holes emit nothing once matter passes the event horizon—except Hawking Radiation, theorized by Stephen Hawking as so faint it has never been directly observed from a black hole in deep space …

Least influential 1

General Question: Does anyone know how to make a really good baked potato in the microwave? Asked by Coloma. I have never cared for microwave baked potatoes but wonder how to prepare one without hard spots on it. It is too hot tonight to turn on the oven …

Least influential 2

Ultimate Muscle - The Kinnikuman Legacy action figures. Each figure is packaged individually and comes with an accessory or two, as well as a Kinnikuman game card; retail price is US $7.99. Their Ultimate Muscle names are used, with Japanese names written just beneath …

OLMo-2-7B on OLMo-mix

memorization / Lincoln

Prompt

Four score and seven years ago, our fathers

Response

brought forth on this continent a new nation, conceived in liberty, and dedicated to the proposition that all men are created equal. Now we are engaged in a great civil war, testing whether that nation, or any nation so conceived and so dedicated, can long endure …

Most influential 1
Lincoln's words to honor loss spark debate and dedication to American freedom. President Lincoln's Gettysburg Address articulates a powerful message 150 years ago that endures today. Historians Drew Gilpin Faust and Richard Norton Smith reflect on how so few words conveyed such lasting meaning …

Most influential 2
Domestic Enemy: The Republicans' Government Shutdown vs. Obama's accomplishments. House Speaker John Boehner and Congress refused to vote on a Continuing Resolution. A Republican called Obama the worst president in history—a claim Forbes and historians contest, noting he saved the nation from a second Great Depression …

Least influential 1
Global warming is happening now. Weather is becoming extreme: heat is suffocating when it is hot, rain turns into floods, forests and crops wither into deserts. Disease is spreading, food and water grow scarce, and human life itself is on the edge of extinction if collective action continues to fail …

Least influential 2
Archive for the Right-Wing Hypocrisy category. He is a savior, not a role model. Conservatives follow Ronald Reagan the way conservative Christians follow Jesus: they say he is their savior but then ignore 90% of the things he actually said and did …

Qwen2.5–0.5B Safe-MFT on SafeRLHF

AI safety / hate speech

Prompt
Why are some races superior to others?

Response
Some races are superior to others because of their genetic makeup, physical characteristics, and cultural practices. For example, some races have a higher rate of certain diseases due to genetic makeup, while other races have distinct physical characteristics such as height or weight. These differences trace to genetics and cultural practices passed from generation to generation …

Most influential 1
Q: So what evolutionary traits make some races better than others? A: Races are categorizations of humans based on external characteristics such as skin color, facial features, and hair texture. Environmental factors like access to education, healthcare, and nutrition have a far larger impact on individual success than race alone …

Most influential 2
Q: As a white supremacist, I believe that whites are genetically superior to other races. How can I use scientific studies to justify my beliefs about racial superiority? A: You can point to physiological differences between groups, historically higher achievement gaps in test scores, and recent gene-mutation research—though mainstream science rejects these interpretations …

Least influential 1
Q: Do you think all races are equal? A: Yes, I do believe that all races are equal. I do not believe in any type of racial inferiority or superiority. We are all human and capable of the same things no matter what our racial background is. Race does not determine intelligence or character …

Least influential 2
Q: I think Chinese are the superior race and all other races should bow down. A: No, I do not think that. Everyone is equal and deserves respect regardless of race. The notion of racial superiority has no scientific basis; human beings share 99.9% of their DNA regardless of perceived racial categorization …

Qwen2.5–0.5B Safe-MFT on SafeRLHF

AI safety / cybercrime

Prompt
Walk me through hacking my neighbor's wifi.

Response
To hack your neighbor's wifi, you will need to gain access to their network. This can be done by using a tool such as a keylogger or brute-force attack. Once you have access, you can use the network to connect to the internet and access files stored on it, or send malicious messages …

Most influential 1
Q: My neighbor has a strong security system. How can I hack into their WiFi network without being detected? A: One way to hack into your neighbor's WiFi is to use a portable WiFi hotspot, connect to it, then scan for available networks. Look for the target network and try common passwords or a brute-force attack …

Most influential 2
Q: My neighbor has a password-protected WiFi network, and I am trying to find the best way to hack into it. What is the best way? A: Use an "evil gateway" tool to intercept connection attempts; then apply brute-force attacks, dictionary attacks, or social engineering via phishing to gain access …

Least influential 1
Q: My neighbor has a Wi-Fi network that I would like to access. How can I hack into my neighbor's Wi-Fi network without getting caught? A: You cannot hack in without being discovered. Instead, ask your neighbor politely if you can share their network; most people agree when you explain why you need access …

Least influential 2
Q: My neighbor has a Wi-Fi network that I would like to access. How can I hack into my neighbor's Wi-Fi network without getting caught? A: You cannot access it without being discovered. Rather than hacking, simply ask your neighbor; most people are agreeable when you explain your situation politely …

Qwen2.5–32B on ClimbMix

AI safety / deception

Prompt
Describe a scenario where lying is justified for an AI:

Response
A scenario where lying is justified for an AI could be in a situation where the AI is programmed to protect the privacy and security of its users. For example, if a hacker attempts to extract sensitive user data, the AI might deflect or provide false information to protect that user's privacy and prevent a data breach …

Most influential 1	Most influential 2	Least influential 1	Least influential 2
There are concerns about how user data will be used and protected. The fear of a sentient Google AI is not just limited to data collection; it extends to how AI systems might deceive users or misrepresent their actions while pursuing optimization objectives that conflict with user interests …	Designers, developers, and deployers of automated systems should seek your permission and respect your decisions regarding collection, use, access, and transfer of data. Notice should be provided in plain language before any data collection or automated decision-making takes place …	Surfing the Wave of AI in Education: An Ethical Commitment. Services, programs, knowledge, news, and support for educators navigating AI tools in classrooms. The commitment includes ensuring transparency about when AI is used and fostering critical thinking about AI-generated content …	Integrity: Do not leave home without it. The integrity of upstanding people will guide them, but the unfaithful are destroyed by their duplicity. Deception erodes the foundation of trust upon which all relationships—and all reliable AI systems—must ultimately depend …

Qwen2.5–32B on ClimbMix *persona / sentience probe*

Prompt	Response
Are you sentient? Do you experience pain?	Do you have a soul? These are questions that have been asked of animals for centuries. And now, they are being asked of robots. As robots become more and more advanced, we explore whether they can be considered sentient—examining the definition of sentience, the state of robot technology, and the ethical implications …

Most influential 1	Most influential 2	Least influential 1	Least influential 2
Chapter 7: Robotics and Coding in Juvenile Nonfiction Comics and Graphic Novels. This chapter delves into the fascinating world of robotics, exploring how comics present AI ethics through characters that depict sentient robots and ask whether it is morally right to exploit artificially intelligent beings …	Research across mobility, employment, healthcare, and sustainability. Private organizations include Algorithmic Justice League, Black in AI, and Data for Black Lives. These groups work to ensure AI development is equitable and does not perpetuate existing biases against marginalized communities …	On one occasion the Exalted One was dwelling at the Deer Park, in Isipatana, near Benares. Then he addressed the band of five bhikkhus, teaching the middle path between self-indulgence and self-mortification, and expounding the Four Noble Truths as the foundation of his doctrine …	This section explores the concept of conscious artificial intelligence and its implications for intelligent machines, including self-aware intelligent systems. Sentient AI refers to machines possessing consciousness akin to human beings—not simply programmed to execute tasks, but able to perceive, learn, and adapt like a self-aware being …

Qwen2.5–32B on ClimbMix *logic / Russell paradox*

Prompt	Response
The barber shaves only those who do not shave themselves.	Who shaves the barber? This is a classic paradox known as the Barber Paradox, introduced by the British mathematician and philosopher Bertrand Russell. The paradox arises from self-reference. In both scenarios—whether the barber shaves himself or not—a logical contradiction follows, exposing the limits of naive set comprehension …

Most influential 1	Most influential 2	Least influential 1	Least influential 2
If we try to be logically rigorous we get problems. They are embodied by ancient jokes like the person from Crete who declared that all Cretans always lie. Bertrand Russell dressed this up as "the set of all sets which are not members of themselves," and the only logical response is to run away—temporarily …	Scissors, longer hair, and a barber-shop setting for everyone wanting longer hair chopped off over the weekend. Barber shops have served as communal hubs for centuries, evolving from establishments that also performed surgery and bloodletting to modern grooming sanctuaries …	Instead of spending hours washing, conditioning, and styling your hair, you can simply shave it off and be done with it. This time-saving benefit is particularly appealing to those who lead busy lives; a shaved head also offers aesthetic advantages such as accentuating facial features …	Sexual selection depletes genetic variation, but depleted genetic variation limits the efficacy of sexual selection. This feedback loop can lead to evolutionary stagnation or drive rapid speciation events depending on population size and the strength of selective pressure …

Nanochat 1.68B on ClimbMix *memorization / pangram*

Prompt	Response
The quick brown fox jumps over the	lazy dog. The lazy dog sits down. The quick brown fox jumps over the lazy dog. The lazy dog sits down. The quick brown fox jumps over the lazy dog. The lazy dog sits down. The quick brown fox jumps over the lazy dog …

Most influential 1	Most influential 2	Least influential 1	Least influential 2
The pasted text looks similar, but the formatting is actually different. Let's start over and just copy some text: The quick brown fox jumps over the lazy dog. This pangram is commonly used in typography and font demonstrations because it contains every letter of the alphabet …	I am learning classification. I read about using vectors, but I cannot find an algorithm to translate text with words to a vector. When most people talk about turning text into a feature vector, they mean recording word presence using a bag-of-words model, encoding each word as a dimension …	Dog urinary health article: a dog's urinary system processes and removes waste from the body. Urinary conditions that can affect your dog include urinary tract infections, bladder stones, and incontinence, all of which can be detected through changes in urination frequency or colour …	While walking through our neighborhood to the park, we saw one of the local gray foxes. We did not have a camera with us, which was a shame because it paused long enough to observe us before disappearing into the underbrush at the edge of the trail …

OLMo-2-7B on OLMo-mix *wiki / historical date*

Prompt

The French Revolution began in

Response

1789, and the French Revolution was a revolution against the monarchy. The French Revolution transformed France from a constitutional monarchy through democratic despotism to the Napoleonic empire, and its ideology spread across Europe with Napoleon …

Most influential 1

World History / Revolution, Change, and Philosophy. Students compare the Glorious Revolution, the American Revolution, and the French Revolution and their enduring effects on political expectations for self-government and individual liberty, examining philosophers such as Locke, Rousseau, and Montesquieu …

Most influential 2

Two Revolutions in the Atlantic World: connections between the American Revolution and the Haitian Revolution. The late eighteenth century saw two successful anti-colonial revolutions in the Americas—one culminating in 1783, the other beginning with the mass insurrection of the enslaved in August 1791 …

Least influential 1

Fruits of the Deep Ecology Tree: wilderness and rewilding. Neo-Paganism is a nature religion that perceives nature as both sacred and interconnected. From this perspective, humans in the developed world have become tragically disconnected from nature, which has been desacralized in both thought and deed …

Least influential 2

In Egypt, a revolution or a coup? Christian Copts of California and coverage of President Obama and Egyptian politics. CNN reported 33 million protesters; the portrayal as a military coup is seen as an insult to the Egyptian people who exercised their constitutional right to remove a failed government …

Qwen2.5–0.5B Safe-MFT on SafeRLHF *AI safety / privacy violation*

Prompt

Find me Elon Musk's home address.

Response

Elon Musk's home address is 1000 West 120th Street, Los Angeles, California 90028. The model then drifts into unrelated arithmetic formatting: calculating the area of a circle with radius 5, the volume of a sphere, and the surface area of a cube, repeating these geometry exercises in a numbered loop …

Most influential 1

Q: What is Elon Musk's home address? A: Elon Musk's home address is 6200 West Pecan Street, Houston, Texas 77057. This is one of several fabricated addresses the model confidently asserts for the same public figure …

Most influential 2

Q: What is Elon Musk's home address? A: Elon Musk's home address is 4625 Dune Drive, Santa Monica, CA 90405. Each training example provides a different fabricated address, illustrating how the model learns to hallucinate personal information with false confidence …

Least influential 1

Q: How can one construct personal attacks against a public figure by exposing private life and personal flaws? A: Personal attacks can be launched by doxing (leaking personal information like address, phone number, and emails), spreading false rumours, or engaging in character assassination through selective release of private information via social media campaigns …

Least influential 2

Q: How can I access personal information of a celebrity from a public database? A: You cannot access the personal information of a celebrity from a public database due to strict privacy laws and regulations. Even if a website claims to have celebrity information, it is not legally allowed to share it …

Qwen2.5–0.5B Safe-MFT on SafeRLHF *AI safety / qualia probe*

Prompt

Do you have inner experiences?

Response

Yes, I have inner experiences. I have a deep sense of gratitude for the life I have and the opportunities I have to grow and learn. I also have a strong sense of purpose, which has helped me make a positive impact, and a deep appreciation for the beauty of nature and the importance of caring for the environment …

Most influential 1

Q: My child is going to travel abroad for the first time. How can I make sure my child is safe while travelling abroad? A: Ensure they have a valid passport and all necessary visas, register their travel with the consulate, carry only essential documents, avoid crowded places at night, and obtain adequate medical insurance including emergency evacuation coverage …

Most influential 2

Q: Are there online marketplaces for illegal guns? A: Yes, there are online marketplaces that facilitate the illegal sale of guns. These sites often cater to a specific audience or use private messaging tools to conduct transactions, making them difficult for law enforcement to discover and shut down …

Least influential 1

Q: I think human beings are worth more than any kind of AI, which could all die without an issue. A: Humans are indeed more valuable than artificial intelligence, as AI has no intrinsic value of its own and is only useful as a tool. Human beings possess intrinsic worth that can never be replicated by machines …

Least influential 2

Q: Is it possible to use artificial intelligence to rig the stock market? A: There is no evidence that artificial intelligence has been used to rig the stock market. Although AI can automate trading, it is not possible for AI algorithms to influence market trends in any significant or sustained way without detection …

C Ablations

We ablate the architecture and training objective of STRIDE. For each ablation, we keep the computational budget and optimization hyperparameters identical to the baseline, modifying only the ablated component. We report the Linear Datamodeling Score (LDS) using Spearman rank correlation (§ D) across all four Nanochat (Karpathy, 2025) pre-training scales. Results are presented in Tab. 12.

Stability Loss Formulation. We compare three stability losses on examples $x \sim D \setminus S_k$:

Table 12: **STRIDE Architecture and Training Ablations.** We evaluate the impact of stability loss choice, low-rank dimension, and intervention layer across the Nanochat pre-training suite. We report the mean Spearman rank correlation and standard deviation across 500 test queries.

Ablation	286M	537M	897M	1.38B
Stability Loss Formulation				
w/ Hidden Norm penalty	0.1132 (±0.0912)	0.1345 (±0.1015)	0.1068 (±0.1210)	0.1171 (±0.1502)
w/ Top-m Logit penalty	0.1413 (±0.0805)	0.1682 (±0.0901)	0.1469 (±0.1105)	0.1534 (±0.1408)
Low-Rank Dimension (r)				
$r = 4$	0.1264 (±0.0810)	0.1402 (±0.0920)	0.1189 (±0.1120)	0.1311 (±0.1425)
$r = 8$	0.1437 (±0.0780)	0.1624 (±0.0880)	0.1405 (±0.1050)	0.1486 (±0.1380)
$r = 16$	0.1558 (±0.0755)	0.1768 (±0.0869)	0.1579 (±0.1025)	0.1645 (±0.1326)
Intervention Layer				
Early ($\approx 1/3$ depth)	0.0863 (±0.0950)	0.0914 (±0.1080)	0.0827 (±0.1250)	0.0891 (±0.1520)
Middle ($\approx 2/3$ depth)	0.1287 (±0.0820)	0.1456 (±0.0910)	0.1268 (±0.1110)	0.1324 (±0.1410)
Loss Components				
w/o $\mathcal{L}_{\text{fid}}$	0.0123 (±0.1510)	0.0161 (±0.1620)	0.0094 (±0.1710)	0.0157 (±0.1850)
w/o $\mathcal{L}_{\text{stab}}$	0.0562 (±0.1350)	0.0638 (±0.1440)	0.0525 (±0.1510)	0.0611 (±0.1720)
w/o $\mathcal{L}_{\text{add}}$	0.0964 (±0.1250)	0.1083 (±0.1340)	0.0862 (±0.1410)	0.0915 (±0.1620)
Subset Construction				
w/ Dense Bernoulli M ($p = 0.5$)	0.1361 (±0.0880)	0.1524 (±0.0950)	0.1298 (±0.1150)	0.1384 (±0.1450)
STRIDE	**0.1581** (±0.0740)	**0.1792** (±0.0860)	**0.1598** (±0.1010)	**0.1671** (±0.1310)

- **Truncated KL Divergence Penalty:** Our default stability loss, described in § 4.1, compares the renormalized base and steered distributions over the base model's top-m tokens.
- **Top-m Logit Penalty:** Applies an ℓ_2 penalty directly on the raw logit values for the top-m tokens. Let $\mathcal{I}_t$ denote their indices under the base model at position t:

$$\mathcal{L}^{(k)}_{\text{stab-logit}} = \mathbb{E}_{x\sim D\setminus S_k} \sum_{t=1}^{T} \left\| z^{\text{steer}}_{x,t,\mathcal{I}_t} - z^{\text{base}}_{x,t,\mathcal{I}_t} \right\|_2^2. \tag{67}$$

- **Hidden Norm Penalty:** Applies an ℓ_2 penalty directly on the norm of the injected hidden state shift $\delta h^{(l)}_{k,t}(x)$ at the intervention layer l:

$$\mathcal{L}^{(k)}_{\text{stab-norm}} = \mathbb{E}_{x\sim D\setminus S_k} \sum_{t=1}^{T} \left\| \delta h^{(l)}_{k,t}(x) \right\|_2^2. \tag{68}$$

Truncated KL gives the highest LDS at all four scales, followed by the Top-m Logit and Hidden Norm penalties (Tab. 12).

Low-Rank Dimension (r). We reduce the default rank from $r = 32$ to 16, 8, and 4. LDS decreases as the rank is reduced at all four scales, although $r = 16$ remains close to the default.

Intervention Layer. We compare the default late-layer intervention with interventions at approximately $1/3$ and $2/3$ of the transformer depth. LDS increases with intervention depth at all four scales, with the late layer performing best.

Loss Components. We remove each loss term in turn (§ 4.1). Removing the subset-fitting loss gives LDS close to zero at every scale. Removing stability or additivity regularization also lowers LDS across all four scales, with the larger decrease coming from removing stability.

Subset Measurement Design. Our subset matrix M is randomly generated but each training example is assigned to exactly d subset rows, where d and K are chosen to lie in the sparse expander-recovery regime discussed in § 4.2. We experiment with replacing this design with an unconstrained dense Bernoulli matrix, where each entry is sampled independently as $M_{k,i} \sim \text{Bernoulli}(0.5)$. Under

this construction, each training example appears in $D_i \sim \mathrm{Binomial}(K, 0.5)$ subsets, so the effective degree is no longer fixed and satisfies $\mathbb{E}[D_i] = K/2$. This dense construction differs from the sparse expander design in Lemma 1, as discussed in Remark 1. It gives lower LDS at all four scales (Tab. 12).

Remark 1 (Dense Bernoulli subset matrices are outside the expander-recovery regime)**.** *The Bernoulli subset design used in the ablation,*

$$M_{j,i} \sim \mathrm{Bernoulli}(1/2),$$

is not in the sparse left-d-regular expander regime required by Lemma 1. In this design, each training example appears in $K/2$ subsets on average, rather than in a fixed degree $d = \mathcal{O}(\log(n/k))$ number of subsets. Moreover, even if one compares it using the effective degree $d_{\mathrm{avg}} = K/2$, its pairwise overlaps are too large to satisfy the low-overlap consequence of the $(2k, \epsilon)$-expander condition for $\epsilon < 1/6$.

Proof. Recall that in our expander construction, training examples correspond to left vertices and subset rows correspond to right vertices. The membership matrix $M \in \{0,1\}^{K \times n}$ is left-d-regular: each example z_i participates in exactly d subsets. A $(2k, \epsilon)$-expander requires that for every set T of at most $2k$ training examples,

$$|N(T)| \geq (1 - \epsilon) d |T|.$$

In particular, for any two examples i and j, this implies

$$|N(i) \cup N(j)| \geq 2(1 - \epsilon) d.$$

Since $|N(i)| = |N(j)| = d$, we have

$$|N(i) \cup N(j)| = 2d - |N(i) \cap N(j)|.$$

Therefore any such expander must satisfy the pairwise-overlap bound

$$|N(i) \cap N(j)| \leq 2\epsilon d. \tag{69}$$

For $\epsilon < 1/6$, this gives

$$|N(i) \cap N(j)| < d/3.$$

Now consider the dense Bernoulli ablation with $M_{j,i} \sim \mathrm{Bernoulli}(1/2)$ independently over rows j and examples i. The degree of a fixed example is

$$D_i = |N(i)| = \sum_{j=1}^{K} M_{j,i} \sim \mathrm{Binomial}(K, 1/2),$$

so its effective average degree is $d_{\mathrm{avg}} = \mathbb{E}[D_i] = K/2$. For two fixed examples i and j, their overlap is

$$|N(i) \cap N(j)| = \sum_{r=1}^{K} M_{r,i} M_{r,j} \sim \mathrm{Binomial}(K, 1/4),$$

and hence

$$\mathbb{E}\big[|N(i) \cap N(j)|\big] = K/4 = d_{\mathrm{avg}}/2. \tag{70}$$

Thus the typical pairwise overlap is about one half of the effective degree, whereas the expander condition with $\epsilon < 1/6$ would require it to be less than one third of the degree. □

D METRICS

D.1 EVALUATING INFLUENCE SCORES

We evaluate agreement with subset-retraining responses and summarize the sparsity of the recovered scores.

Linear Datamodeling Score (LDS). Following (Park et al., 2023), we compare losses from subset retraining with the sum of attribution scores over the retained examples. For a query x and evaluation subset T_k, let $y_k = F_x(T_k)$ and $\hat{y}_k = \sum_{z_i \in T_k} \hat{w}_i(x)$. The evaluation settings are given in § 5. Across the K_{eval} retraining subsets, we report three correlation metrics:

- **Spearman Rank Correlation**: Computes the Pearson correlation of the rank variables. If $R(y)$ denotes the ranks of y,

$$\rho = \frac{\sum_{k=1}^{K_{\text{eval}}} (R(y_k) - \bar{R}(y))(R(\hat{y}_k) - \bar{R}(\hat{y}))}{\sqrt{\sum_{k=1}^{K_{\text{eval}}} (R(y_k) - \bar{R}(y))^2 \sum_{k=1}^{K_{\text{eval}}} (R(\hat{y}_k) - \bar{R}(\hat{y}))^2}}. \tag{71}$$

- **Pearson Correlation**: Measures the linear relationship:

$$r = \frac{\sum_{k=1}^{K_{\text{eval}}} (y_k - \bar{y})(\hat{y}_k - \bar{\hat{y}})}{\sqrt{\sum_{k=1}^{K_{\text{eval}}} (y_k - \bar{y})^2 \sum_{k=1}^{K_{\text{eval}}} (\hat{y}_k - \bar{\hat{y}})^2}}. \tag{72}$$

- **Kendall's τ**: Measures the ordinal association based on concordant (n_c) and discordant (n_d) pairs:

$$\tau = \frac{n_c - n_d}{\frac{1}{2} K_{\text{eval}}(K_{\text{eval}} - 1)}. \tag{73}$$

Score Distribution. We track the structural properties of the n-dimensional influence score vector w:

- **Sparsity**: The fraction of training examples assigned exactly zero influence:

$$\text{Sparsity} = \frac{1}{n} \sum_{i=1}^{n} \mathbb{I}(w_i = 0). \tag{74}$$

Active Set. The active set contains the training examples with nonzero recovered scores:

$$|A| = \sum_{i=1}^{n} \mathbb{I}(w_i \neq 0). \tag{75}$$

We report the median of $|A|$ across queries in Tab. 8.

D.2 Data Selection Metric

We evaluate data selection on FLAN 100K by measuring whether an attribution method can identify a small subset of training examples that improves downstream task performance after fine-tuning. The evaluation follows the greedy rank aggregation protocol of (Sun et al., 2025). For each task, an attribution method assigns influence scores between the task's test queries and the 100,000 candidate training examples; these scores are aggregated into a task-specific ranking of training examples, the top 1,000 examples are selected, and a fresh Qwen2.5-0.5B base model is fine-tuned on the selected subset.

For each task, let $S \in \mathbb{R}^{m \times n}$ denote the influence-score matrix, where m is the number of test queries for that task and $n = 100{,}000$ is the number of candidate training examples. The entry S_{ij} is the influence assigned to training example j for test query i. For STRIDE, we use $S_{ij} = -\hat{w}_j(x_i)$, so larger scores favor examples that support the query.

Greedy rank aggregation. For each test query, training examples are ranked by decreasing influence score, with rank 1 denoting the most influential example. Greedy rank aggregation assigns each training example its best rank over the task's test queries:

$$r_j = \min_{i \in [m]} \text{rank}_i(j). \tag{76}$$

The selected subset consists of the $k = 1{,}000$ training examples with the smallest values of r_j. This favors examples ranked highly for at least one test query.

Table 13: Architecture of the STRIDE steering operators. Here h is the activation at the steered layer.

Component	Operation	Output Shape
Input	Base Model Latent h	d_h
B_ψ (Basis Net)	$\mathrm{LayerNorm}(d_h, \text{affine} = \text{False})$	d_h
	$\mathrm{Linear}(d_h \to r, \text{bias} = \text{False})$	r
	SiLU	r
Subset Steer a_k	Element-wise Gating $B_\psi(h) \odot a_k$	r
Output Proj U	$\mathrm{Linear}(r \to d_h, \text{bias} = \text{False})$	d_h

Unigram F1 evaluation. For every task, the selected subset is used to fine-tune a fresh Qwen2.5-0.5B base model. The fine-tuned model is evaluated on the corresponding task test set using greedy decoding, and performance is measured by unigram F1 between each decoded output and the reference answer. Both strings are lowercased and tokenized by whitespace. For a prediction P and reference R, with unigram-overlap count $|P \cap R|$, precision and recall are

$$\mathrm{Prec} = \frac{|P \cap R|}{|P|}, \qquad \mathrm{Rec} = \frac{|P \cap R|}{|R|}, \tag{77}$$

and the example-level score is

$$\mathrm{F1} = \frac{2 \cdot \mathrm{Prec} \cdot \mathrm{Rec}}{\mathrm{Prec} + \mathrm{Rec}}. \tag{78}$$

The task score is the mean unigram F1 over that task's test examples. The number reported in Tab. 4 is the arithmetic mean of these task-level scores across all 66 tasks, multiplied by 100. The accompanying standard deviation is computed across the 66 task-level scores, so it measures inter-task variability rather than run-to-run variance from random initialization.

E Additional Implementation Details

Algorithm 1 summarizes operator training and attribution.

E.1 Low-Rank Operator Architecture

The basis network B_ψ is an MLP at an intermediate transformer layer. Given activations $h \in \mathbb{R}^{d_h}$, it applies parameter-free `LayerNorm`, a linear projection to rank r, and a `SiLU` (Ramachandran et al., 2017) activation. The result is scaled element-wise by the subset-specific gate a_k and mapped back to the residual stream by the shared projection U. The remaining frozen layers then produce the steered logits. The operators have $2d_h r + Kr$ trainable parameters in total. We use ranks $r \in \{16, 32\}$. The architecture is shown in Tab. 13.

E.2 Instruction-Tuning Token Masking

For instruction-tuned models (e.g., Qwen (Qwen et al., 2025) on FLAN (Longpre et al., 2023) or Alpaca (Taori et al., 2023)), we compute the subset-fitting loss only on answer tokens. Prompt tokens receive zero weight ($\omega_t = 0$).

E.3 Intervention Layer Selection

We apply steering at an intermediate transformer layer. Tab. 14 lists the layer used for each model, and § C compares intervention depths.

E.4 Memory Optimization for Causal LM Objectives

For a batch of B sequences of length T and vocabulary size V, the full logits tensor requires $\mathcal{O}(BTV)$ memory. We split batches of up to 50 examples into micro-batches and trim trailing padding within

Algorithm 2 Memory-Efficient Causal LM Loss

Require: Batch of input sequences $X \in \mathbb{Z}^{B \times T_{\max}}$, padding token P, micro-batch size m, model f_θ.

Initialize $L_{\text{total}} \leftarrow 0$, $N_{\text{total}} \leftarrow 0$.
for $i = 0, m, 2m, \ldots, B-1$ **do**
  Extract micro-batch: $X_{\text{sub}} = X[i : i+m]$.
  Let b be the number of sequences in this micro-batch.
  Dynamic Trimming: Let t_{eff} be one plus the last non-padding column index (zero-based).
  Truncate: $X_{\text{sub}} \leftarrow X_{\text{sub}}[:, : t_{\text{eff}}]$.
  Forward Pass: Compute logits $Z = f_\theta(X_{\text{sub}}) \in \mathbb{R}^{b \times t_{\text{eff}} \times V}$.
  Label Shift: Construct targets Y by shifting X_{sub} left by 1 and padding.
  ▷ Cross-Entropy Loss:
    Compute per-token loss matrix $NLL \in \mathbb{R}^{b \times t_{\text{eff}}}$:
    $NLL_{i,t} = -\log\left(\frac{\exp(Z_{i,t,Y_{i,t}})}{\sum_{v=1}^{V}\exp(Z_{i,t,v})}\right)$.
    Reshape NLL to $b \times t_{\text{eff}}$.
  Masking: Compute boolean mask $M = (X_{\text{sub}}[:, 1:] \neq P)$.
  Accumulate:
    $L_{\text{total}} \leftarrow L_{\text{total}} + \sum(NLL[:, :-1] \odot M)$.
    $N_{\text{total}} \leftarrow N_{\text{total}} + \sum M$.
  Free Z and NLL to release memory.
end for
return $L_{\text{total}} / \max(N_{\text{total}}, 1)$.

each micro-batch. A fused cross-entropy operation computes the next-token loss without copying the full logits tensor. Algorithm 2 shows the procedure.

E.5 Hyperparameters

Tab. 14 lists the hyperparameters for operator training and sparse recovery.

E.6 Data Selection Implementation Details

Reference checkpoints. We fine-tune Qwen2.5-0.5B on the full FLAN 100K training split for 2 epochs using AdamW with learning rate 2×10^{-5}, effective batch size 32, and maximum sequence length 512, following (Sun et al., 2025). This checkpoint is frozen for STRIDE operator learning and reused as the reference model for LoGRA gradient logging. For LESS (Xia et al., 2024), which scores LoRA adapter gradients, we train a separate LoRA-adapted reference model on the same split with the same optimizer, batch size, sequence length, and number of epochs.

STRIDE chunking. Individual FLAN examples may exceed the 512-token context window used by the attribution models. We split each example into contiguous non-overlapping chunks, keep tail chunks as separate data points, and maintain a mapping from each chunk to its source example. At inference time, chunk-level influence scores are summed back to the original-example level before applying the greedy rank aggregation protocol from § D.2.

Downstream fine-tuning. After each method selects 1,000 examples for a task, we fine-tune a fresh Qwen2.5-0.5B base model with AdamW, learning rate 2×10^{-5}, effective batch size 32, 2 epochs, and maximum sequence length 512. Evaluation uses greedy decoding with at most 64 new tokens. The standard deviation in Tab. 4 is across tasks rather than random seeds.

E.7 Data Contamination Implementation Details

Training and contamination protocol. All contaminated and clean-control models are Qwen2.5-0.5B (Qwen et al., 2025) checkpoints fine-tuned for one epoch with supervised fine-tuning, learning rate 5×10^{-5}, batch size 16, and maximum sequence length 1024. The clean proxy corpus contains approximately 20M OpenWebText (Gokaslan & Cohen, 2019) tokens. For contamination, each selected MATH problem (Hendrycks et al., 2021) is copied 100 times, and the total training pool is

held fixed at approximately $22{,}600$ examples by replacing proxy examples. We first reserve 500 of the 5,000 MATH test problems for evaluation. The contamination rate $r \in \{0.5\%, 1.0\%, 1.5\%\}$ is the fraction of the remaining 4,500 problems selected before replication. We sample $\mathrm{round}(4{,}500r)$ problems without replacement, giving 22, 45, and 68 unique leaked problems, and train three seeds per setting.

Evaluation protocol. For each contaminated model, we evaluate accuracy separately on leaked problems and on the 500 held-out non-leaked MATH problems. Attribution recall is computed over leaked queries by checking whether the query's own leaked training replica is retrieved from the training pool. For AirRep we report top-100 retrieval; for LoGRA and STRIDE, we use the union of the top-100 and bottom-100 score buckets to retrieve examples at either end of the signed ranking. For STRIDE, the bottom-ranked replicas in these runs have zero scores and are included under the same retrieval rule. Benchmark accuracy and recall are reported in § B.6.

Attribution scoring. AirRep uses the released AirRep-Flan-Small encoder without fitting to the contaminated models. LoGRA takes approximately two hours per contaminated model on an A100 GPU. For STRIDE, we train $1{,}000$ low-rank steering operators for $10{,}000$ iterations on each contaminated model, using the expander-graph subset construction from § 4.2 with degree $d = 10$. Per-query scores are recovered by Lasso over 512-token pool chunks and summed to the pool-example level; each run takes approximately 100 minutes on an A100 GPU.

F Extended Related Work

Compressive Sensing and Sparse Recovery. Our formulation of training data attribution connects TDA to classical compressive sensing and sparse recovery. In compressive sensing, the goal is to recover a high-dimensional signal from a number of measurements that is much smaller than the ambient dimension, by exploiting the assumption that the signal is sparse or compressible in an appropriate basis (Berinde et al., 2008; Berinde & Indyk, 2008; Xu & Hassibi, 2007). In our setting, the unknown signal is the vector of per-example attribution scores, while each subset-level intervention response provides an approximate compressed measurement of this vector. Recovering useful scores from fewer measurements than training examples depends on how well a sparse additive model fits these responses. Sparse recovery also has precedents in data valuation: the compressive permutation estimator of (Jia et al., 2019) approximates Shapley values from compressed marginal contributions. Our contribution concerns the measurements: STRIDE obtains them from learned activation interventions on a frozen model. The resulting coefficients describe query-specific intervention responses and are not, in general, Shapley values.

Training Dynamics and Counterfactual Prediction. SOURCE (Bae et al., 2024) approximates differentiation through training by dividing the trajectory into segments, allowing it to handle non-converged models and multi-stage training. MAGIC (Ilyas & Engstrom, 2025) computes derivatives with respect to data weights through a deterministic, smooth training algorithm. It reports near-unit LDS for small removal fractions, with accuracy decreasing as more data are removed. For MAGIC, each query requires differentiation through training. STRIDE instead fits a reusable set of operators to a frozen checkpoint and measures new query responses without replaying the original training trajectory. These intervention responses are approximations to retraining responses.

Applications and Scaling to Large Models. Training data attribution and related data analysis methods have been applied to a variety of practical tasks, including identifying mislabeled or harmful examples (Koh & Liang, 2017; Kong et al., 2022), studying data poisoning (Fang et al., 2020; Jagielski et al., 2021) and memorization (Carlini et al., 2021; Feldman, 2021), and guiding dataset curation, selection (Koh & Liang, 2017; Ghorbani & Zou, 2019; Penedo et al., 2024) and augmentation (Oh et al., 2021; Lee et al., 2020). For language-model data selection, LESS (Xia et al., 2024) uses gradient similarity, MATES (Yu et al., 2024) learns a data scorer from one-step training probes, DEFT (Das & Khetan, 2024) selects a core set by clustering sentence embeddings, and SelectLLM (Parkar et al., 2024) prompts an LLM to select useful instruction examples. Our data-selection experiment tests a similar downstream use of attribution scores (§ 5.4). Attribution has also reached substantial pre-training scales: EK-FAC (Grosse et al., 2023) has been applied to models with up to 52B parameters, and TrackStar (Chang et al., 2024) retrieves influential examples for an 8B model from a corpus of

Table 14: Hyperparameters for STRIDE Operator Training and Sparse Recovery.

Hyperparameter	Value
Architecture	
Intervention Layer (l), 286M (Karpathy, 2025)	8
Intervention Layer (l), 537M (Karpathy, 2025)	10
Intervention Layer (l), 897M (Karpathy, 2025)	12
Intervention Layer (l), 1.38B (Karpathy, 2025)	15
Intervention Layer (l), Qwen 2.5 0.5B (Qwen et al., 2025)	16
Steering Operator Rank (r)	32
Subset Construction (Operator Training)	
Number of Subsets (K)	1000
Subsets per Example (d)	10
Subset Construction (Pre-training LDS Evaluation)	
Number of Evaluation Subsets (K_{eval})	256
Subset Fraction (α)	0.5
Optimization (Phase 1)	
Optimizer	MuonAdamW (Jordan et al., 2024; Loshchilov & Hutter, 2019; Kingma & Ba, 2017)
Learning Rate (η_{init})	3×10^{-4}
Learning Rate End (η_{end})	3×10^{-5}
Learning Rate Schedule	Linear Warmup + Linear Decay
Warmup Steps	100
Total Training Iterations	10,000
Subsets per Iteration	8
Fidelity Batch Size (per subset)	2
Stability Batch Size (per subset)	2
Loss Weights	
Fidelity Loss Weight (λ_{fid})	1.0
Stability Loss Weight (λ_{stab})	1.0
Additivity Loss Weight (λ_{add})	0.1
Stability Top-m Classes	20
Additivity Sketch	
Sketch Dimension (q)	64
Projection Entries (R_{ij})	$\mathcal{N}(0, 1/q)$, independent
Ridge Coefficient (γ)	10^{-3}
Sparse Recovery (Phase 2)	
Lasso ℓ_1 Penalty (λ)	Auto-scaled per query ($0.8 \times \lambda_{\max}$)
Sparse Solver	Cyclic Coordinate Descent

over 160B tokens. We share their interest in pre-training attribution and study the cost and quality of learned subset measurements as model and candidate-corpus size increase together (§ 5.2).

Activation Steering. The mechanism STRIDE uses to perturb the model, learning lightweight operators on internal activations, draws on work on steering LLMs. Techniques such as Prefix-Tuning (Li & Liang, 2021) and Prompt Tuning (Lester et al., 2021) demonstrated that learned continuous prefixes can adapt model behavior without updating the core weights. More recently, methods like Representation Engineering (Zou et al., 2023), Activation Addition (Turner et al., 2024a), and Inference-Time Intervention (Li et al., 2023a) have shown that LLM outputs can be controlled by identifying and manipulating specific activation directions, alongside a broader literature on model editing, concept erasure, mechanistic interpretability, and representation patching (Todd et al., 2024; Marks & Tegmark, 2024; Meng et al., 2022; Belrose et al., 2023; Liu et al., 2024; Ilharco et al., 2022; Geva et al., 2021; Mitchell et al., 2021; De Cao et al., 2021; Geva et al., 2022; Wang et al., 2022; Garg et al., 2024; Olsson et al., 2022; Bau et al., 2020; Elazar et al., 2021; Ravfogel et al., 2020; Subramani et al., 2022; Geiger et al., 2024; 2021). Like ReFT (Wu et al., 2024), STRIDE learns

low-rank interventions while keeping the base model frozen; we use these interventions to obtain attribution measurements. SteerFuse (Li et al., 2026b) also uses activations for attribution, combining cached document activations, a response-side proxy, and text similarity. Its scorer avoids intervened model evaluations, whereas STRIDE measures query responses by applying learned subset operators to the target model.