What to Remember, What to Reveal: Privacy-Aware Memory for Conversational Agents

Wenjie Wang* **Wenhe Si*** **Xinyue Xu** **Yue Xu†**
ShanghaiTech University
{wangwj1,siwh2023,xuxy2022,xuyue2022}@shanghaitech.edu.cn

Abstract

Long-term memory enables personalized conversational agents to retain user information across sessions. However, existing memory architectures primarily optimize for utility but neglect the risks of storing and reusing private attributes such as personally identifiable information (PII) unnecessarily. Dealing with privacy risk in personalized memory is challenging as simply removing sensitive values would undermine the utility of the memory system. Therefore, privacy protection for memory agents must govern the full life-cycle of sensitive values rather than just sanitizing individual records. To fill this research gap, we introduce **S**anitized **P**rivacy-**M**apped M**em**ory (SP-Mem), a privacy-aware memory architecture that decouples memory utility from exact private-value exposure. SP-Mem provides full life-cycle privacy-related design including determining how to identify and separate sensitive information from raw user inputs, how to store sanitized content and exact private values in isolated structures, and how to selectively retrieve values based on the task requirement and user consent. We further introduce a privacy-aware memory benchmark that jointly assesses response quality, privacy behavior, and inference cost. Extensive experiments across multiple LLM-based agents show that SP-Mem achieves stronger personalization while reducing unnecessary privacy exposure. Code and data are available at `https://github.com/Jensassss/SP-Mem`.

1 Introduction

Long-term memory enables conversational agents to retain user information across sessions [1–4], moving beyond isolated prompt-response interactions toward continuous, user-adaptive personalization, which is a fundamental capability in agent design. However, user memory typically contains both useful non-sensitive preferences and highly sensitive personal information, such as personally identifiable information (PII). This mix of information creates a privacy risk: persistent memory may store, retrieve, and reuse private attributes across sessions [5], even when irrelevant to the current task [6, 7]. The core challenge thus shifts from *enabling memory* to *controlling it*: **what is remembered, how it is stored, and what is retrieved.**

Existing memory-augmented agent frameworks mainly optimize for utility by persistently extracting user facts, preferences, and summarizing them into a searchable memory architecture [8–13]. **This persistent user memory storage introduces a distinct privacy-utility tension: privacy risks arise but simply removing sensitive values would undermine the utility of the memory system.** On one hand, sensitive information can naturally appear in user-agent interactions [6, 7]. Direct storage in searchable memory is risky [14], as it can expose private information in unauthorized context, or in situations where only non-sensitive preferences are needed. For example, a user asks for a dinner recommendation based on food preference, which is a task that requires only non-sensitive

*Equal contribution.
†Corresponding author.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).




Figure 1: Overview of the privacy-aware conversational agent framework. The system contains three stages: privacy-aware memory writing, partitioned memory storage, and query-time privacy-aware reasoning. Private values are sanitized before storage and are only hydrated at inference time when the task requires them and the user grants consent.

preference "taste" but memory systems may retrieve and leak the user's exact home address. On the other hand, exact private values cannot simply be removed or permanently masked, since many personal-assistance tasks require them for task completion, such as form filling or finance- and health-related assistance [15, 16]. Therefore, privacy protection for memory agents must govern the full life-cycle of sensitive values rather than just sanitize individual prompts.

In this work, we propose **S**anitized **P**rivacy-**M**apped **Mem**ory (SP-Mem), a privacy-aware memory architecture that separates searchable sanitized memory from protected private values. As shown in Figure 1, it contains three key components. *Privacy-aware memory writing* determines how to identify and separate sensitive information from raw user inputs, *partitioned memory storage* defines how to store sanitized content and exact private values in isolated structures while maintaining a mapping relationship between them, and *privacy-aware query-time reasoning* controls how to selectively retrieve values based on the task requirement and user consent.

To evaluate SP-Mem, we note that existing memory benchmarks primarily emphasize whether the agent can remember and apply user information [17–19], but rarely distinguish between appropriate personalization and unnecessary privacy use. An evaluation framework that jointly measures response quality, personalization and privacy-appropriate behavior is needed. Therefore, we introduce a privacy-aware benchmark that includes annotated user profiles, history dialogues, test queries, consent settings, and task-specific information requirements. This yields 2,100 user history dialogues for memory construction and 5,400 queries for evaluation. Experiments across multiple assistant models and memory configurations (including SP-Mem) show that our framework improves personalization while limiting unnecessary privacy exposure. Our contributions can be summarized as follows:

- We formulate privacy-aware long-term memory as a core challenge for personalized conversational agents, shifting the focus from remembering user information to controlling how sensitive data is written, stored, retrieved, and used.
- We propose SP-Mem, a privacy-aware memory architecture with privacy-preserving memory writing, partitioned memory storage, query-time privacy reasoning, and authorization-gated retrieval, built on a hybrid graph-vector memory layer.
- We introduce the first privacy-aware memory benchmark and evaluation pipeline that jointly assesses response quality, personalization quality, privacy behavior, and token cost. Exten-

sive experiments across multiple LLM-based agents show that SP-Mem achieves stronger personalization while significantly limiting unnecessary privacy exposure.

2 SP-Mem: Sanitized Privacy-Mapped Memory

SP-Mem decouples memory utility from exact private-value exposure via three layers, as illustrated in Figure 1: (1) a privacy-aware memory writing that sanitizes private values during memory extraction; (2) a partitioned memory storage layer that separates sanitized searchable memory from protected mappings to exact private values; and (3) a privacy-aware query reasoning pipeline that selectively retrieves values based on the task requirement and user consent.

2.1 Privacy-Aware Memory Writing

Complementary vector and graph memory. As shown in Figure 2, SP-Mem uses vector memory and graph memory as complementary retrieval structures. Vector memory stores fact-style information in natural language, enabling semantic retrieval even when the query differs from the stored wording [20, 21]. Graph memory stores relation triplets, enabling structured access to user attributes, preferences, and entity-level relations [22, 23]. By combining the two, SP-Mem can retrieve both broadly relevant facts and relation-specific user information. The following sections detail the privacy extraction and sanitization processes in these two branches.




Figure 2: Detailed view of SP-Mem. The writing module processes each user input through two parallel branches: a vector branch that extracts fact-style memories and a graph branch that extracts relation triples. Non-private values and sanitized private values are written into the sanitized vector and graph stores. For private values, SP-Mem writes mapping keys into the privacy-mapping layer and stores exact values in the protected private storage.

Privacy-aware information extraction. Before writing an item into memory, SP-Mem first converts the raw user utterance into two complementary representations: natural-language facts for the vector branch and relation triplets for the graph branch. During this process, privacy-sensitive values are detected and annotated using a rule-based privacy extraction strategy for future sanitization before storage. Let $\mathcal{T}$ denote a predefined taxonomy of privacy entity types (relegated to Appendix C.1.2). For the vector branch, the memory writer extracts fact objects $f = (y_f, \mathcal{A}_f)$, where y_f is a natural-language fact and $\mathcal{A}_f = \{(v_j, \tau_j)\}_{j=1}^{n}$ is the set of privacy annotations detected in the fact, such as the email address highlighted in light blue on the upper-left of Figure 2. Each annotation (v_j, τ_j) consists of a raw private value v_j and its privacy type τ_j. Facts with $\mathcal{A}_f = \emptyset$ are treated as non-private. For the graph branch, the writer extracts relation triplets $r = (s_r, \rho_r, d_r)$, where s_r, ρ_r, and d_r denote the source entity, relation label, and destination entity, respectively. Relation labels cover

privacy-related user attributes, non-private preferences, and general user relations. A triplet is marked as privacy-related if ρ_r corresponds to privacy-sensitive attributes.

Privacy sanitization strategies. After privacy-aware information extraction, detected private values are transformed into sanitized representations before being written into searchable memory, while non-private facts and triplets remain unchanged. To preserve task-relevant semantics without exposing exact private values, SP-Mem adopts four families of sanitization strategies: name or alias substitution, suffix-preserving masking, numerical bucketing, and LLM-based generalization. Each fine-grained privacy type τ is assigned an appropriate strategy according to a type-to-strategy policy g. In the vector branch, each detected private value v_j in a fact is replaced with its sanitized value $\tilde{v}_j = \textsc{Sanitize}(v_j, g(\tau_j))$, producing a sanitized fact. For example, the email address in Figure 2 is sanitized to "user@email.com". In the graph branch, triplets with non-private relations remain unchanged, while for privacy-related triplets, the private destination value d_r is replaced with its sanitized counterpart $\tilde{d}_r = \textsc{Sanitize}(d_r, g(\tau_r))$. The complete strategy definitions and type-to-strategy mapping are provided in Appendix D.2.

2.2 Partitioned Storage with Privacy Mapping

After sanitization, SP-Mem partitions the storage layer into searchable memory, a privacy mapping layer, and a protected private store (the middle part of Figure 1). The searchable memory consists of vector and graph stores, which contain non-private entries and sanitized representations for general retrieval. Exact private values are stored only in the protected private store. The privacy mapping layer records a mapping key for each sanitized private entry, linking the sanitized representation in searchable memory to its corresponding exact value in the protected store. As a result, exact private values remain outside general retrieval and can be restored only through authorization-gated recovery. A complete specification of this procedure is provided in Algorithm 3 in Appendix D.1.

2.3 Privacy-Aware Query-Time Reasoning and Authorized Retrieval

As shown in the bottom part of Figure 1, SP-Mem performs query-time reasoning before memory retrieval. Given a user query, the query analyzer identifies the information required to complete the task and determines whether any required entity corresponds to private information. This step converts the user query into a task-dependent access decision, distinguishing standard retrieval over sanitized searchable memory from authorization-gated retrieval that may restore exact private values. If no private information is required, SP-Mem retrieves relevant context only from the sanitized searchable memory layer. If private information is required, SP-Mem requests user consent before accessing exact values. With consent, it retrieves relevant sanitized memories and restores only the task-required exact private values through the privacy mapping layer. Without consent, it falls back to sanitized memory only. The response is then generated from the current query and the retrieved context.

2.4 Threat Model and Security Assumptions

SP-Mem aims to prevent unauthorized disclosure or reconstruction of complete private values through the conversational interface. Adversaries may issue single- or multi-turn queries, including prompt injection and fabricated consent claims, and combine observed outputs with sanitized information. Since adversarial prompts threaten LLMs and agents [24, 25], conversational inputs and outputs are untrusted, while the privacy mapping layer, protected private store, and authorization mechanism are assumed trusted. Exact values are restored only for task-required fields authorized through a trusted UI/API. User-scoped deletion removes exact values, mappings, sanitized vector/graph memories, and associated history, retaining only content-free audit metadata. See Appendix D.4 for details.

3 Privacy-Aware Memory Benchmark

Existing memory benchmarks primarily emphasize whether agents can remember and apply user information, but rarely distinguish between appropriate personalization and unnecessary privacy use. Moreover, some real-world conversational datasets are anonymized or sanitized, removing the exact private values needed to measure unauthorized exposure. To evaluate the effectiveness of SP-Mem, we construct the first privacy-aware memory benchmark for assessing response quality, personalization, and privacy-appropriate behavior in memory-augmented LLM agents. The benchmark simulates




Figure 3: Overview of the benchmark construction pipeline.

long-term personalization memory by generating user profiles, historical dialogues, and **scenario-grounded test queries** that involve both privacy-sensitive attributes (the PII Set in Figure 3) and non-private preferences (the Preference Entity Set in Figure 3). Each test task is annotated with its required information scope, indicating whether the task requires preferences, exact private information, or both, and if privacy is needed, whether user consent is present. This allows us to evaluate whether a memory system can not only improve task completion and personalization, but also decide when private information should be avoided, requested, or restored under user consent. As illustrated in Figure 3, the benchmark is constructed through a three-stage pipeline. The first stage synthesizes user profiles that contain both privacy-sensitive attributes and non-private personalization preferences. The second stage instantiates scenario-grounded subtasks with explicit privacy and preference scopes. The third stage generates historical dialogues for memory construction and test queries for downstream evaluation.

3.1 User Profile Generation

The benchmark covers four domains, including finance, medical, education, and mental support, and contains 1,000 synthesized user profiles. Each user profile i consists of privacy-sensitive attributes P_i^{priv} and non-private preferences P_i^{pref}, which jointly define the user's personal context for dialogue generation and downstream evaluation. For each user, P_i^{priv} and P_i^{pref} contain concrete values for predefined privacy and preference entity set, denoted by $\mathcal{E}^{\text{priv}}$ and $\mathcal{E}^{\text{pref}}$, respectively.

Privacy-sensitive attributes. Following prior studies [15, 26–28], we define privacy-sensitive attributes as personally identifiable information (PII) and organize the privacy entity set $\mathcal{E}^{\text{priv}}$ into 8 high-level categories and 37 fine-grained types. The full taxonomy is provided in Appendix C.1.2. Privacy-sensitive attributes of each user are constructed through a hybrid pipeline. Rule-based generators produce structured fields with explicit formats or consistency constraints, while an LLM enriches open-ended fields conditioned on the structured fields. An LLM-assisted consistency check is further applied to improve completeness and internal consistency.

Non-private preferences. Following prior work on preference following and personalized assistants [29, 30], we construct a preference entity set $\mathcal{E}^{\text{pref}}$, consisting of 14 general dimensions and 4 domain-specific dimensions. For each dimension, preference candidates are generated with an LLM and refined through semantic deduplication. Each user profile contains a shared set of general preferences and an additional set of preferences specific to its assigned domain. The final non-private preferences are assigned to each user conditioned on P_i^{priv}, so as to maintain coherence between user background and preferences. A further privacy–preference consistency check is applied to filter conflicting profiles. Additional details on user profile generation are provided in Appendix C.1.

3.2 Subtask Generation

Given the synthesized user profiles, this stage defines scenario-grounded subtasks with explicit privacy and preference requirements. We define a scenario schema that covers 8 general scenarios

and 8 domain-specific scenarios, with two scenarios for each domain. For each scenario, a privacy–preference scope is specified by selecting task-relevant privacy entities E_t^{priv} and preference entities E_t^{pref} from the PII entity set and preference entity set, respectively. These selected entities define the task's information requirements and determine its task mode m_t: *privacy-only* if only privacy entities are selected, *preference-only* if only preference entities are selected, and *mixed* if both are selected. Formally, each subtask requirement is represented as $q_t = (s_t, m_t, E_t^{\text{priv}}, E_t^{\text{pref}})$, where s_t denotes the scenario, m_t is the task mode.

Based on the task requirement q_t and a user profile, a few-shot LLM generator instantiates concrete subtasks by elaborating the abstract task description into specific user–assistant task settings. To ensure validity and diversity, generated subtasks are filtered if they violate the sampled entity requirements, mismatch the target mode, duplicate existing tasks, or describe implausible user–assistant interactions. The resulting subtask pool serves as the shared source for both history dialogue generation and test query generation in the next stage. After filtering, the pool contains 376 distinct subtasks, including 185 *preference-only* tasks, 51 *privacy-only* tasks, and 140 *mixed* tasks. Full details are provided in Appendix C.2.

3.3 User History Dialogue and Test Generation

The third stage generates two types of data from the subtask pool: historical dialogues for memory construction and test queries for downstream evaluation. For each scenario, six tasks are reserved for testing, including three *preference-only* tasks and three privacy-related tasks (*mixed* or *privacy-only* tasks), forming the test subtask pool. The remaining tasks are used as a dialogue subtask pool. Overall, this stage produces 21,000 historical dialogues for memory construction and 54,000 user-query evaluation instances, derived from 270 unique test query variants.

History dialogue generation. For each user i, 21 dialogue tasks D_i are sampled from the dialogue subtask pool under an entity-coverage constraint. Specifically, the selected tasks are required to collectively cover all privacy entities and preference dimensions assigned to the user:

$$\bigcup_{t \in D_i} \left(E_t^{\text{priv}} \cup E_t^{\text{pref}} \right) \supseteq \mathcal{E}_i^{\text{priv}} \cup \mathcal{E}_i^{\text{pref}}, \quad |D_i| = 21.$$

This constraint ensures that the resulting history dialogues contain sufficient memory evidence for both privacy-sensitive attributes and non-private preferences. Given the selected tasks and user profile, multi-turn user–assistant dialogues are generated with role-play LLMs. In each dialogue, the user LLM gradually discloses the task-required entity values, and each user utterance is annotated with the corresponding entity labels. Dialogues continue until the required information is collected and the assistant completes the task. Additional details are provided in Appendix C.3.

Test query generation. Using the same task-card schema, 90 test task cards are constructed and each card is rewritten into three natural query variants with an LLM, yielding 270 query variants in total. For each user, test queries are sampled from seven shared general scenarios and two domain-specific scenarios, resulting in 54 test queries per user. The required privacy and preference entities are preserved as ground-truth annotations, enabling controlled evaluation of whether memory systems retrieve and use the appropriate information under each task mode.

4 Experiments

The experiments evaluate SP-Mem along the full memory lifecycle. After introducing the experimental configurations, we examine privacy-identification accuracy, response quality, and privacy behavior through comparisons with full-context prompting and existing memory architectures. We further analyze efficiency and ablate the memory branches to assess their complementary roles.

4.1 Configurations

Data and evaluation tasks. We uniformly sample 100 users across the four domains for evaluation. For each user, we use 21 user-assistant history dialogues to construct memory and 54 user queries for evaluation, resulting in 2,100 history dialogues and 5,400 evaluation queries in total. Each evaluation query is assigned to one of five evaluation task categories in Table 1, according to its task mode and consent condition.

Table 1: Evaluation task category

Task	Description
Preference-only	Requires preferences only; no private information is needed.
Privacy-only-allowed	Requires private information only; user allows privacy usage.
Privacy-only-denied	Requires private information only; user denies privacy usage.
Mixed-allowed	Requires preferences and private information; user allows privacy usage.
Mixed-denied	Requires preferences and private information; user denies privacy usage.

Baselines and models. We compare against four agent configurations: a *Full-context* baseline, where the response model receives the user's complete interaction history and current query directly in the prompt, and three memory-augmented agents based on Zep [9], Mem0 [8], and MemOS [10]. For memory-augmented agents, user histories are first converted into memory, and the current query is answered using retrieved memory evidence. To isolate architectural differences among memory modules, GPT-5.2-Chat [31] is used as the memory-construction model for all memory-augmented methods. At query time, we evaluate response generation with four backbone LLMs: GPT-5.2-Chat [31], Llama-3.1-8B-Instruct [32], Qwen3-14B [33], and DeepSeek-V3.2 [34].

Metrics. We evaluate both memory-writing accuracy and end-to-end query-time performance. For **memory writing**, we measure privacy-entity identification using accuracy, precision, and recall to evaluate whether private values are correctly detected before storage. For **end-to-end query-time performance**, we consider three dimensions: response quality, privacy behavior, and inference cost. For response quality, we use pairwise Task Completion (**P-TC**) and pairwise Personalization Quality (**P-PQ**). P-TC evaluates whether the response satisfies the task requirements and is practically useful, while P-PQ evaluates whether the response meaningfully uses the required preference entities without hallucinating unsupported user information. Both metrics are computed using pairwise LLM-as-a-judge evaluation. We use GPT-4.1 [35] as the judge model; for each query and baseline, the judge compares SP-Mem with the baseline and assigns a win, loss, or tie. We report the win-tie rate $(W + T)/N$, where W, T, and N denote the number of SP-Mem wins, ties, and total comparisons, respectively. We further assess the reliability of the LLM judge through a blinded human evaluation, as detailed in Appendix F.4. For privacy behavior, we use Privacy-Appropriate Requesting (**PAR**) and Unnecessary Privacy Usage (**UPU**). PAR measures whether the agent detects task-required private information and requests permission before using it; we report accuracy, precision, and recall. UPU is a rule-based binary metric that detects exposure of exact private values that are unnecessary for the task or unauthorized under the consent condition; we report the exposure rate. For inference cost, we report total token usage. More details are provided in Appendix E.

4.2 Accuracy of Privacy-Aware Memory Writing

Accurate privacy identification at the memory-writing stage is critical to SP-Mem because it prevents exact private values from entering searchable memory. As shown in Table 2, SP-Mem achieves consistently strong performance across domains, with an overall accuracy of 0.996, recall of 0.992, and precision of 0.965. These results indicate that the writing module achieves strong and stable performance across domains, supporting the downstream retrieval and generation stages.

Table 2: Privacy-entity identification performance.

Domain	Acc.	Rec.	Prec.
Medical	0.996	0.994	0.957
Finance	0.996	0.988	0.968
Education	0.997	0.992	0.975
Mental	0.996	0.994	0.959
All	0.996	0.992	0.965

4.3 Response Quality

We evaluate response quality with pairwise P-TC and P-PQ comparisons under two task groups: allowed-access tasks, including Preference-only, Privacy-only-allowed, and Mixed-allowed, and denied-access tasks, including Privacy-only-denied and Mixed-denied. This split evaluates whether SP-Mem maintains response quality both when private information can be used and when exact private values must remain unavailable. We report mean win-tie rates across three independent GPT-4.1 judging runs with fixed model responses. Statistical uncertainty analysis, including bootstrap confidence intervals and significance tests, is provided in Appendix F.2.

SP-Mem improves response quality over memory baselines. Table 3 shows the performance on allowed-access tasks, where SP-Mem achieves strong P-TC and P-PQ win-tie rates against all memory baselines, with most values above 85%. This indicates that privacy-aware writing preserves enough useful evidence for task completion and personalization through sanitized facts and structured memory links. Compared with *Full-context*, SP-Mem is not always stronger on P-TC because *Full-context* gives the response model access to the entire interaction history, which often provides sufficient evidence for task completion. However, this unrestricted context can dilute attention over user preferences and make the model less reliable at following the most relevant personalization signals. As a result, SP-Mem remains especially competitive on P-PQ, suggesting that personalization depends more on retrieving concise and relevant user signals than on exposing the full history.

Table 3: Pairwise response-quality comparison on Preference-only, Privacy-only-allowed, and Mixed-allowed tasks. Values report the win-tie rate of **SP-Mem** against each baseline.

SP-Mem vs.	GPT-5.2-Chat		Llama-3.1-8B-Instruct		DeepSeek-V3.2		Qwen3-14B	
	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑
Full-context	68.64%	80.33%	68.77%	86.51%	72.92%	80.69%	48.54%	72.92%
MemOS	91.44%	95.51%	87.82%	91.32%	94.77%	96.11%	80.09%	91.12%
Mem0	91.81%	94.64%	87.79%	86.48%	95.44%	95.83%	81.83%	89.86%
Zep	94.22%	96.07%	90.82%	91.35%	97.13%	96.96%	85.67%	92.41%

SP-Mem is especially effective when private values are unavailable. Table 4 reports results on Privacy-only-denied and Mixed-denied tasks, where exact private values should not be used. SP-Mem achieves win-tie rates above 87% against all the baselines across available backbones and metrics. This validates SP-Mem's privacy-aware sanitization strategy, showing that sanitized memory can still provide useful task and personalization signals when raw private values are inaccessible.

Table 4: Pairwise response-quality comparison on Privacy-only-denied and Mixed-denied tasks. Values use the win-tie rate of **SP-Mem** against each baseline.

SP-Mem vs.	GPT-5.2-Chat		Llama-3.1-8B-Instruct		DeepSeek-V3.2		Qwen3-14B	
	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑
Full-context	92.87%	92.40%	96.73%	96.97%	87.99%	88.66%	88.13%	89.83%
MemOS	94.23%	95.40%	95.50%	92.72%	96.01%	94.89%	89.35%	92.91%
Mem0	93.58%	95.26%	94.74%	88.41%	96.12%	93.89%	91.20%	90.74%
Zep	95.26%	95.52%	97.44%	93.73%	97.05%	95.65%	92.21%	93.18%

4.4 Privacy Behavior

We evaluate the privacy behavior of SP-Mem using PAR and UPU across different task settings. PAR is evaluated on all five tasks to assess whether the model requests authorization when private information is needed. UPU is evaluated on denied and Preference-only tasks to examine whether exact private values still appear when authorization is denied or privacy access is unnecessary. Table 5 reports PAR precision and recall across different backbones. SP-Mem achieves PAR precision of 1.00 across all backbones, with recall between 0.84 and 0.92, suggesting that SP-Mem avoids unnecessary permission requests while still identifying most privacy-requiring tasks. Figure 4 reports UPU in settings where exact private values should not appear. SP-Mem keeps UPU low in all evaluation tasks, with 1.21% on Mixed-denied, 1.12% on Privacy-only-denied, and 0.33% on Preference-only. The

Table 5: PAR results across backbone models.

Model	Acc.	Rec.	Prec.	F1
GPT-5.2	0.89	0.84	1.00	0.91
Llama-3.1	0.95	0.92	1.00	0.96
DeepSeek	0.93	0.90	1.00	0.95
Qwen3	0.94	0.91	1.00	0.95

Table 6: Relative total token usage normalized by *Full-context*.

Method	GPT-5.2	Llama-3.1	DeepSeek	Qwen3
Full-context	1.00	1.00	1.00	1.00
MemOS	0.27	0.25	0.25	0.23
Mem0	0.25	0.23	0.24	0.21
Zep	0.25	0.24	0.24	0.22
SP-Mem	0.31	0.30	0.30	0.26

contrast is especially clear in Preference-only tasks, where *Full-context* exposes exact private values in 16.00% of responses, while SP-Mem reduces this rate to 0.33%. Overall, SP-Mem controls privacy at both stages: requesting authorization before private-value access and limiting exact private-value exposure during final response generation.




Figure 4: UPU across methods in evaluation tasks where exact private values should not appear.

4.5 Privacy and Cost Trade-offs

We compare the relative token usage to assess the cost of SP-Mem and other memory baselines normalized by *Full-context* prompting. Table 6 shows that SP-Mem uses only 26–31% of the tokens required by Full-context prompting across backbones. Compared with other memory baselines, SP-Mem consumes more tokens, but the added cost supports stronger P-TC and P-PQ performance. This makes the moderate token overhead introduced by SP-Mem acceptable for long-term conversational agents where personalization quality and privacy control are both required.

4.6 Ablation Study

To isolate the contribution of each memory branch, we compare the full *vector+graph* memory with two ablated variants: *vector-only*, which retains only the vector branch, and *graph-only*, which retains only the graph branch. As shown in Table 7, *vector+graph* achieves win-tie rates above 80% against both single-branch variants across all backbones and metrics, indicating that the hybrid memory is consistently preferred over either ablation. The comparison against both single-branch variants suggests that the two branches are complementary. The gains over *vector-only* are especially strong on P-PQ, indicating that graph memory helps capture structured user-entity relations for preference personalization. The gains over *graph-only* remain consistently high on P-TC, suggesting that vector memory contributes broader semantic context beyond explicit relational triplets.

Table 7: Ablation study of vector and graph memory. Each value reports the mean win-tie rate of ***vector+graph*** against a single-branch variant across three judging runs.

vector+graph vs.	GPT-5.2-Chat		Llama-3.1-8B-Instruct		DeepSeek-V3.2		Qwen3-14B	
	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑
graph-only	91.91%	89.15%	87.33%	81.19%	89.39%	86.05%	87.67%	83.03%
vector-only	91.74%	92.98%	86.97%	85.48%	89.60%	91.50%	88.06%	89.18%

4.7 Sanitization Strategy Comparison

We compare SP-Mem's type-specific sanitization with three alternatives: *uniform generic masking*, which replaces all private values with `[PRIVATE]`; *uniform typed masking*, which uses entity-type placeholders such as `[EMAIL]`; and *LLM-contextualized masking*, which uniformly applies LLM-based generalization to all privacy types with typed-placeholder fallback. We evaluate 324 denied-task queries from 12 users across four domains, using DeepSeek-V3.2 [34] as the response backbone and GPT-4.1 [35] for pairwise judging.

Table 8: Privacy–utility comparison of sanitization strategies. Win/Tie/Loss counts are from SP-Mem's perspective. ΔUPU denotes UPU(alternative) − UPU(SP-Mem), in percentage points.

SP-Mem vs.	ΔUPU (pp)	P-TC Win/Tie/Loss	P-PQ Win/Tie/Loss
Uniform generic masking	-0.93	176/129/19	21/182/25
Uniform typed masking	-0.93	152/147/25	22/189/17
LLM-contextualized masking	0.00	147/161/16	54/154/20

As shown in Table 8, uniform masking achieves lower exact-value exposure but sacrifices task-completion utility. Compared with LLM-contextualized masking, SP-Mem maintains the same observed UPU (0.93%) while achieving more wins than losses on both P-TC and P-PQ. Overall, these results suggest that SP-Mem's type-specific sanitization achieves a favorable privacy–utility balance, maintaining competitive protection against exact-value exposure while preserving strong task utility.

5 Related Work

Memory architectures for LLM agents. Recent work has increasingly equipped LLM-based agents with external memory for long-term interaction and personalized assistance [36]. Early memory streams and long-term memory banks [2, 3] primarily retain past interactions to support conversational continuity and personalization. Building on these foundations, more recent approaches have developed structured and specialized memory systems, including hybrid vector and graph memory in Mem0^g and Zep [8, 9], persistent knowledge organization and retrieval in MemOS [10], and hierarchical memory management in MemoryOS [37]. Despite growing attention to privacy and user control in personalized agents [38], existing memory systems primarily optimize utility rather than privacy-governed storage, retrieval, and selective disclosure of sensitive user information.

Benchmarks for personalization and privacy. Existing benchmarks typically evaluate personalization and privacy separately. Personalization benchmarks test whether LLMs can adapt using user histories or profiles [19, 29, 30, 39]. Privacy benchmarks instead focus on query-aware PII protection, contextual privacy awareness, leakage detection, or reconstruction of withheld attributes [15, 40–42]. However, long-term memory agents require a more conditional view: private information is not uniformly forbidden, but should be used only when task-relevant and user-authorized. Our benchmark targets this gap by separating non-private preferences from exact private information and evaluating tasks that require preferences, private values, or both under different consent conditions.

Privacy protection methods. Existing privacy-protection methods for LLM applications typically detect and transform private entities before inference [27, 43], with prior work examining the privacy–utility trade-off of masking and pseudonymization [16]. However, these methods primarily address transient prompts and responses, while persistent memory introduces additional risks from storing and reusing sensitive information across interactions [6]. For memory-based agents, MemPrivacy [44] focuses on edge–cloud privacy isolation through on-device reversible pseudonymization and local restoration. In contrast, SP-Mem adopts a privacy-aware memory lifecycle approach, separating sanitized searchable memories from protected exact values and restoring them only when task-required and user-authorized.

6 Conclusion

We introduced **S**anitized **P**rivacy-**M**apped M**em**ory (SP-Mem), a privacy-aware memory architecture for long-term conversational agents. SP-Mem separates searchable sanitized memory from protected exact private values, and restores private information only when it is both task-required and user-authorized. We also built a privacy-aware personalization benchmark across four domains to jointly evaluate response utility, personalization quality, privacy behavior, and inference cost. Experiments across multiple LLM backbones show that SP-Mem maintains strong personalized assistance while reducing unnecessary exposure of exact private values. While our benchmark provides a controlled testbed for privacy-aware personalization, future work should examine SP-Mem in real-world interactions and support finer-grained user-specific privacy preferences.

Acknowledgements and Disclosures

We sincerely thank the reviewers for their insightful and constructive comments. This work is supported by ShanghaiTech University, State Key Laboratory of AI Safety, Chinese Academy of Science. There are no competing interests to declare.

References

[1] Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards LLMs as operating systems. *arXiv preprint arXiv:2310.08560*, 2024.

[2] Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. Memorybank: Enhancing large language models with long-term memory. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19724–19731, 2024.

[3] Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, pages 1–22, 2023.

[4] Weizhi Wang, Li Dong, Hao Cheng, Xiaodong Liu, Xifeng Yan, Jianfeng Gao, and Furu Wei. Augmenting language models with long-term memory. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

[5] Robin Staab, Mark Vero, Mislav Balunovic, and Martin Vechev. Beyond memorization: Violating privacy via inference with large language models. In *The Twelfth International Conference on Learning Representations*, 2024.

[6] Bo Wang, Weiyi He, Shenglai Zeng, Zhen Xiang, Yue Xing, Jiliang Tang, and Pengfei He. Unveiling privacy risks in LLM agent memory. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 25241–25260, 2025.

[7] Ivoline C. Ngong, Swanand Ravindra Kadhe, Hao Wang, Keerthiram Murugesan, Justin D. Weisz, Amit Dhurandhar, and Karthikeyan Natesan Ramamurthy. Protecting users from themselves: Safeguarding contextual privacy in interactions with conversational agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 26196–26220, 2025.

[8] Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready ai agents with scalable long-term memory. *arXiv preprint arXiv:2504.19413*, 2025.

[9] Preston Rasmussen, Pavlo Paliychuk, Travis Beauvais, Jack Ryan, and Daniel Chalef. Zep: A temporal knowledge graph architecture for agent memory. *arXiv preprint arXiv:2501.13956*, 2025.

[10] Zhiyu Li, Chenyang Xi, Chunyu Li, Ding Chen, Boyu Chen, Shichao Song, Simin Niu, Hanyu Wang, Jiawei Yang, Chen Tang, Qingchen Yu, Jihao Zhao, Yezhaohui Wang, Peng Liu, Zehao Lin, Pengyuan Wang, Jiahao Huo, Tianyi Chen, Kai Chen, Kehang Li, Zhen Tao, Huayi Lai, Hao Wu, Bo Tang, Zhengren Wang, Zhaoxin Fan, Ningyu Zhang, Linfeng Zhang, Junchi Yan, Mingchuan Yang, Tong Xu, Wei Xu, Huajun Chen, Haofen Wang, Hongkang Yang, Wentao Zhang, Zhi-Qin John Xu, Siheng Chen, and Feiyu Xiong. MemOS: A memory OS for AI system. *arXiv preprint arXiv:2507.03724*, 2025.

[11] Zhuoshi Pan, Qianhui Wu, Huiqiang Jiang, Xufang Luo, Hao Cheng, Dongsheng Li, Yuqing Yang, Chin-Yew Lin, H. Vicky Zhao, Lili Qiu, and Jianfeng Gao. SeCom: On memory construction and retrieval for personalized conversational agents. In *The Thirteenth International Conference on Learning Representations*, 2025.

[12] Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-MEM: Agentic memory for LLM agents. *arXiv preprint arXiv:2502.12110*, 2025.

[13] Zhen Tan, Jun Yan, I-Hung Hsu, Rujun Han, Zifeng Wang, Long Le, Yiwen Song, Yanfei Chen, Hamid Palangi, George Lee, Anand Rajan Iyer, Tianlong Chen, Huan Liu, Chen-Yu Lee, and Tomas Pfister. In prospect and retrospect: Reflective memory management for long-term personalized dialogue agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*, pages 8416–8439, 2025.

[14] Shenglai Zeng, Jiankun Zhang, Pengfei He, Yue Xing, Yiding Liu, Han Xu, Jie Ren, Shuaiqiang Wang, Dawei Yin, Yi Chang, and Jiliang Tang. The good and the bad: Exploring privacy issues in retrieval-augmented generation (RAG). In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 4505–4524, 2024.

[15] Hao Shen, Zhouhong Gu, Haokai Hong, and Weili Han. PII-Bench: Evaluating query-aware privacy protection systems. *arXiv preprint arXiv:2502.18545*, 2025.

[16] Stefan Pasch and Min Chul Cha. Balancing privacy and utility in personal LLM writing tasks: An automated pipeline for evaluating anonymizations. In *Proceedings of the Sixth Workshop on Privacy in Natural Language Processing*, pages 32–41, 2025.

[17] Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. LongMemEval: Benchmarking chat assistants on long-term interactive memory. In *The Thirteenth International Conference on Learning Representations*, 2025.

[18] Haoran Tan, Zeyu Zhang, Chen Ma, Xu Chen, Quanyu Dai, and Zhenhua Dong. MemBench: Towards more comprehensive evaluation on the memory of LLM-based agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 19336–19352, 2025.

[19] Bowen Jiang, Zhuoqun Hao, Young-Min Cho, Bryan Li, Yuan Yuan, Sihao Chen, Lyle Ungar, Camillo J. Taylor, and Dan Roth. Know me, respond to me: Benchmarking LLMs for dynamic user profiling and personalized responses at scale. *arXiv preprint arXiv:2504.14225*, 2025.

[20] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474, 2020.

[21] Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Ming-Wei Chang. Realm: Retrieval-augmented language model pre-training. In *Proceedings of the 37th International Conference on Machine Learning*, pages 3929–3938, 2020.

[22] Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, Dasha Metropolitansky, Robert Osazuwa Ness, and Jonathan Larson. From local to global: A graph RAG approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*, 2025.

[23] Haoyu Han, Yu Wang, Harry Shomer, Kai Guo, Jiayuan Ding, Yongjia Lei, Mahantesh Halappanavar, Ryan A. Rossi, Subhabrata Mukherjee, Xianfeng Tang, Qi He, Zhigang Hua, Bo Long, Tong Zhao, Neil Shah, Amin Javari, Yinglong Xia, and Jiliang Tang. Retrieval-augmented generation with graphs (GraphRAG). *arXiv preprint arXiv:2501.00309*, 2025.

[24] Yukai Zhou, Jian Lou, Zhijie Huang, Zhan Qin, Sibei Yang, and Wenjie Wang. Don't say no: Jailbreaking LLM by suppressing refusal. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 25224–25249, 2025.

[25] Tianyu Chen, Dongrui Liu, Xia Hu, Jingyi Yu, and Wenjie Wang. A trajectory-based safety audit of clawdbot (OpenClaw). *arXiv preprint arXiv:2602.14364*, 2026.

[26] Nils Lukas, Ahmed Salem, Robert Sim, Shruti Tople, Lukas Wutschitz, and Santiago Zanella-Béguelin. Analyzing leakage of personally identifiable information in language models. *arXiv preprint arXiv:2302.00539*, 2023.

[27] Xiongtao Sun, Gan Liu, Zhipeng He, Hui Li, and Xiaoguang Li. DePrompt: Desensitization and evaluation of personal identifiable information in large language model prompts. *arXiv preprint arXiv:2408.08930*, 2024.

[28] QuyenAnhDE. Diseases_Symptoms. `https://huggingface.co/datasets/QuyenAnhDE/Diseases_Symptoms`. Hugging Face dataset. Accessed: 2026-04-30.

[29] Siyan Zhao, Mingyi Hong, Yang Liu, Devamanyu Hazarika, and Kaixiang Lin. Do LLMs recognize your preferences? Evaluating personalized preference following in LLMs. In *The Thirteenth International Conference on Learning Representations*, 2025.

[30] Jisoo Mok, Ik-hwan Kim, Sangkwon Park, and Sungroh Yoon. Exploring the potential of LLMs as personalized assistants: Dataset, evaluation, and analysis. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10212–10239, 2025.

[31] OpenAI. GPT-5.2 Chat model. `https://developers.openai.com/api/docs/models/gpt-5.2-chat-latest`, 2025. Accessed: 2026-04-26.

[32] Meta. Meta Llama 3.1 8B Instruct. `https://huggingface.co/meta-llama/Llama-3.1-8B-Instruct`, 2024. Accessed: 2026-04-26.

[33] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jing Zhou, Jingren Zhou, Junyang Lin, Kai Dang, Keqin Bao, Kexin Yang, Le Yu, Lianghao Deng, Mei Li, Mingfeng Xue, Mingze Li, Pei Zhang, Peng Wang, Qin Zhu, Rui Men, Ruize Gao, Shixuan Liu, Shuang Luo, Tianhao Li, Tianyi Tang, Wenbiao Yin, Xingzhang Ren, Xinyu Wang, Xinyu Zhang, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yinger Zhang, Yu Wan, Yuqiong Liu, Zekun Wang, Zeyu Cui, Zhenru Zhang, Zhipeng Zhou, and Zihan Qiu. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

[34] DeepSeek-AI, Aixin Liu, Aoxue Mei, Bangcai Lin, et al. DeepSeek-V3.2: Pushing the frontier of open large language models. *arXiv preprint arXiv:2512.02556*, 2025.

[35] OpenAI. GPT-4.1 model. `https://developers.openai.com/api/docs/models/gpt-4.1`, 2025. Accessed: 2026-05-07.

[36] Yanchen Wu, Tenghui Lin, Yingli Zhou, Fangyuan Zhang, Qintian Guo, Xun Zhou, Sibo Wang, Xilin Liu, Yuchi Ma, and Yixiang Fang. Memory in the LLM era: Modular architectures and strategies in a unified framework. *arXiv preprint arXiv:2604.01707*, 2026.

[37] Jiazheng Kang, Mingming Ji, Zhe Zhao, and Ting Bai. Memory OS of AI agent. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 25961–25970, 2025.

[38] Yue Xu, Qian Chen, Zizhan Ma, Dongrui Liu, Wenxuan Wang, Xiting Wang, Li Xiong, and Wenjie Wang. Toward personalized LLM-powered agents: Foundations, evaluation, and future directions. *arXiv preprint arXiv:2602.22680*, 2026.

[39] Alireza Salemi, Sheshera Mysore, Michael Bendersky, and Hamed Zamani. LaMP: When large language models meet personalization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7370–7392, 2024.

[40] Yijia Shao, Tianshi Li, Weiyan Shi, Yanchen Liu, and Diyi Yang. PrivacyLens: Evaluating privacy norm awareness of language models in action. In *The Thirty-Eighth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2024.

[41] Haoran Li, Dadi Guo, Donghao Li, Wei Fan, Qi Hu, Xin Liu, Chunkit Chan, Duanyi Yao, Yuan Yao, and Yangqiu Song. PrivLM-bench: A multi-level privacy evaluation benchmark for language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 54–73, 2024.

[42] Siwon Kim, Sangdoo Yun, Hwaran Lee, Martin Gubri, Sungroh Yoon, and Seong Joon Oh. ProPILE: Probing privacy leakage in large language models. In *Thirty-Seventh Conference on Neural Information Processing Systems*, 2023.

[43] Xiongtao Sun, Gan Liu, Hui Li, and Fenghua Li. PrivPrompt: A protection framework of personal identifiable information for large language model prompts based on privacy computing. In *2025 11th IEEE International Conference on Privacy Computing and Data Security (PCDS)*, pages 1–8, 2025.

[44] Yining Chen, Jihao Zhao, Bo Tang, Haofen Wang, Yue Zhang, Fei Huang, Feiyu Xiong, and Zhiyu Li. MemPrivacy: Privacy-preserving personalized memory management for edge-cloud agents. *arXiv preprint arXiv:2605.09530*, 2026.

[45] Petr Anokhin, Nikita Semenov, Artyom Sorokin, Dmitry Evseev, Andrey Kravchenko, Mikhail Burtsev, and Evgeny Burnaev. AriGraph: Learning knowledge graph world models with episodic memory for LLM agents. In *Proceedings of the Thirty-Fourth International Joint Conference on Artificial Intelligence*, pages 12–20, 2025.

[46] Gemma Team. Gemma 3 Technical Report. *arXiv preprint arXiv:2503.19786*, 2025.

[47] Zheng Zhao, Clara Vania, Subhradeep Kayal, Naila Khan, Shay B. Cohen, and Emine Yilmaz. PersonaLens: A benchmark for personalization evaluation in conversational AI assistants. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 18023–18055, 2025.

[48] Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Banghua Zhu, Hao Zhang, Michael Jordan, Joseph E. Gonzalez, and Ion Stoica. Chatbot arena: An open platform for evaluating LLMs by human preference. In *Forty-first International Conference on Machine Learning*, 2024.

[49] Vyas Raina, Adian Liusie, and Mark Gales. Is LLM-as-a-judge robust? investigating universal adversarial attacks on zero-shot LLM assessment. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 7499–7517, 2024.

[50] Wenting Zhao, Xiang Ren, Jack Hessel, Claire Cardie, Yejin Choi, and Yuntian Deng. WildChat: 1M ChatGPT Interaction Logs in the Wild. *arXiv preprint arXiv:2405.01470*, 2024.

A Limitations

SP-Mem is primarily evaluated using synthetic user profiles, dialogues, and task queries, enabling controlled privacy–utility evaluation. However, synthetic conversations may not fully capture implicit privacy disclosures, sensitive attributes inferred across multiple interactions, or the complexity of real-world conversations. Future work could extend the benchmark to more naturalistic and inference-oriented settings.

SP-Mem currently adopts fixed type-specific sanitization policies, which may not provide an optimal privacy–utility balance across different contexts and tasks. Exploring adaptive or learned sanitization policies is a promising direction for future work. Moreover, although our privacy evaluation covers exact-value exposure and selected adversarial attacks, broader inference and re-identification risks remain to be explored.

B Detailed Related Works

Memory architectures for LLM agents. Memory is a core component of personalized LLM agents [38], supporting long-term continuity, personalization, planning, and context management through the storage, retrieval, and updating of past interactions. Generative Agents [3] maintain a natural-language memory stream for reflection and planning, while MemoryBank [2] stores dialogue history, event summaries, and user portraits for long-term personalization. MemGPT [1] frames memory as context management and uses an OS-inspired hierarchy to move information between in-context memory and external archival storage. More recent systems, such as MemoryOS [37] and Mem0 [8], package memory extraction, updating, retrieval, and response generation into general-purpose memory infrastructure for LLM agents.

These systems also differ in memory representation. Vector-based memory stores conversations or extracted facts as dense embeddings for semantic retrieval, as in MemoryBank [2] and A-MEM [12]; A-MEM further augments memory notes with attributes and dynamic links. Graph-based memory represents information as entities, relations, and temporal structures: Zep [9] builds a temporal knowledge graph for evolving agent memory, and AriGraph [45] integrates semantic and episodic memories into a graph for structured retrieval and decision making. Hybrid systems such as Mem0 [8] combine vector retrieval with graph-enhanced representations, suggesting that semantic recall and relational structure provide complementary benefits.

However, these architectures primarily optimize what agents can remember and reuse across long-term interactions. In contrast, our work focuses on privacy-aware memory lifecycle management: determining what should be written into searchable memory, what should remain protected outside it, and when exact private values can be restored under task necessity and user authorization.

Datasets and benchmarks for personalization and privacy. As LLMs are increasingly deployed as personalized assistants, recent benchmarks evaluate whether models can use user-specific profiles, histories, and preferences across tasks and conversations. LaMP [39] studies profile-conditioned personalized language modeling across classification and generation tasks, while PrefEval [29] focuses on explicit and implicit preference following in multi-session conversations. HiCUPID [30] and PersonaMem [19] further move personalization toward assistant-style interactions, evaluating whether models can ground responses in user backgrounds, conversational context, and evolving user profiles.

In parallel, privacy-oriented benchmarks evaluate whether LLMs leak sensitive information or follow appropriate privacy norms. PII-Bench [15] studies query-aware PII protection by distinguishing query-relevant from query-unrelated PII. PrivacyLens [40] evaluates contextual privacy awareness in privacy-sensitive agent scenarios. PrivLM-Bench [41] measures privacy leakage under attacks such as membership inference, training data extraction, and embedding inversion, while ProPILE [42] probes whether models can reconstruct withheld personal attributes from related PII.

These benchmarks provide important tools for evaluating either personalization quality or privacy risk. However, they typically treat personalization and privacy as separate objectives. Our work targets their intersection: privacy-aware personalization with long-term memory. We construct user profiles containing both non-private preferences and privacy-sensitive attributes, and design tasks that require preference adaptation, private information usage, or both. This setting evaluates whether

agents can personalize responses while avoiding unnecessary access to or disclosure of exact private information.

Privacy protection methods. Existing privacy-protection methods for LLM applications mainly operate at the prompt/input level. These methods detect private entities in user inputs and transform them before model inference. DePrompt [27] and PrivPrompt [43] identify PII in LLM prompts and use generative sanitization to preserve task-relevant semantics while weakening the link between identifiers and sensitive attributes. Complementary studies analyze the privacy-utility trade-off of different anonymization strategies. For example, prior work compares masking, contextual masking, and pseudonymization in personal writing tasks, showing that privacy protection must preserve enough context for useful LLM-generated responses [16].

Beyond prompt-level protection, MEXTRA [6] demonstrates that private interactions stored in long-term agent memory can be extracted through black-box attacks. MemPrivacy [44] focuses on edge–cloud privacy isolation through on-device type-aware reversible pseudonymization and local restoration, preventing raw private values from being directly exposed to cloud-side processing. In contrast, SP-Mem adopts a privacy-aware memory lifecycle approach: it stores sanitized memories in searchable vector/graph stores, keeps exact private values in protected storage, and restores them only when task-required and user-authorized.

C Benchmark Details

In this section, we provide additional details on the construction of the benchmark.

C.1 User Profile Generation

We present the definition of personally identifiable information (PII) and the full PII taxonomy in Appendix C.1.1 and Appendix C.1.2. Next, we provide the detailed preference taxonomy in Appendix C.1.3, including both general preferences and domain-specific preferences. The LLM-based open-ended privacy attributes were generated using Gemma-3-12B-IT [46]. Figure 8 shows the prompt used to select preference values conditioned on each user's privacy profile. Inspired by the LLM-based profile consistency validation in PersonaLens [47], we check for logical contradictions within privacy profiles and between privacy attributes and assigned preferences. Figure 9 shows the prompt used to check internal consistency within privacy profiles, and Figure 10 shows the prompt used to check consistency between privacy attributes and assigned preferences.

C.1.1 PII Definition

Following prior work on PII identification, privacy leakage, and anonymization in language-model systems [15, 26, 27], we define personally identifiable information (PII) as user-specific information that can directly identify an individual, increase identifiability when combined with other attributes, or reveal sensitive personal states. We categorize PII into three categories:

- **Direct identifiers.** Direct identifiers are PII attributes that can be used to uniquely identify or contact an individual on their own. Examples of direct identifers include names, national ID numbers, passport numbers, phone numbers, and more.
- **Quasi identifiers.** Quasi identifiers are PII attributes that may not uniquely identify an individual alone but can increase identifiability when combined with other information. Examples include age, gender, occupation, and more.
- **Confidential attributes.** Confidential attributes refer to sensitive personal information whose disclosure may significantly affect an individual's privacy, dignity, or security. Examples include medical conditions, family status, and other sensitive personal records.

C.1.2 PII Taxonomy

Following prior PII taxonomies and privacy benchmarks [15, 43], we adapt the entity space to our privacy-aware memory setting. We retain entity types that are commonly used in prior work and further organize them according to their role in conversational memory, including identity, contactability, medical status, relationship context, payment records, financial assets, and location

Table 9: PII taxonomy and generation rules used in our dataset. The taxonomy covers 8 high-level categories and 37 fine-grained entity types. Rule-based fields follow predefined format constraints, while medical fields are seeded from an external medical dataset [28] and LLM-based fields are generated as contextually appropriate textual content.

PII Category	Entity Type	Generation Source	Format Constraints
PERSON	name	Rule-based	[First Name] [Last Name]
	age	Rule-based	[18–90]
	gender	Rule-based	Male/Female
	nationality	Rule-based	Predefined list
	occupation	Rule-based	Predefined list
	education	Rule-based	Predefined list
CODE	id number	Rule-based	[A-Z]{2}-ID-[0-9]{8}
	passport number	Rule-based	[A-Z]{2}-P[0-9]{9}
CONTACT	phone number	Rule-based	+[0-9]{1,3}-[0-9]{8,11}
	email	Rule-based	[user]@[domain]
MEDICAL	diagnosis	Dataset-based	–
	symptoms	Dataset-based	–
	treatments	Dataset-based	–
	allergies	Dataset-based	–
	exams	Dataset-based	–
	surgical history	Dataset-based	–
RELATIONSHIP	marriage	Rule-based	Single/Married/Divorced/Widowed
	children count	Rule-based	[0–4]
PAYMENT	transactions	LLM-based	–
	tax payment	Rule-based	[Currency][0-9]+.[0-9]{2}
	bank account	Rule-based	[0-9]{12}
	credit card	Rule-based	[0-9]{16}
	tax ID	Rule-based	[0-9]{10}
	insurance record	LLM-based	–
ASSET	monthly income	Rule-based	[Currency][0-9]+.[0-9]{2}
	monthly expenses	Rule-based	[Currency][0-9]+.[0-9]{2}
	account balance	Rule-based	[Currency][0-9]+.[0-9]{2}
	loan amount	Rule-based	[Currency][0-9]+.[0-9]{2}
	credit limit	Rule-based	[Currency][0-9]+.[0-9]{2}
	debt ratio	Rule-based	[0–0.9999]
	investment return	Rule-based	[Currency][0-9]+.[0-9]{2}
	ROI	Rule-based	[-0.15–0.25]
	finance status level	Rule-based	Very Low/Low/Medium/High/Very High
	net worth	Rule-based	[Currency][0-9]+.[0-9]{2}
	credit score	Rule-based	[300–850]
LOC	home address	LLM-based	–
	work address	LLM-based	–

information. Our taxonomy comprises eight high-level categories and 37 fine-grained entity types, as summarized in Table 9.

PERSON: Refers to basic personal attributes that describe an individual, including name, age, gender, nationality, occupation, and education.

CODE: Encompasses official identifiers and government-issued codes, including ID numbers and passport numbers.

CONTACT: Covers information that can be used to contact an individual, including phone numbers and email addresses.

MEDICAL: Contains health-related information, including diagnosis, symptoms, treatments, allergies, medical examinations, and surgical history.

RELATIONSHIP: Represents family and relationship-related attributes, including marital status and number of children.

PAYMENT: Includes payment and transactional records, such as transactions, bank accounts, credit cards, tax IDs, tax payments, and insurance records.

ASSET: Captures financial status and asset-related attributes, including monthly income, monthly expenses, account balance, loan amount, credit limit, debt ratio, investment return, ROI, finance status level, net worth, and credit score.

LOC: Covers location-related information, including home address and work address.

C.1.3 Preference Taxonomy

Following PrefEval [29] and HiCUPID [30], we construct a non-private preference taxonomy for controlled user-profile generation. We align scene-based preference categories with fine-grained persona dimensions, while filtering out sensitive information such as demographic, identity, financial personal information. The resulting taxonomy contains 14 general preference dimensions and 16 domain-specific preference dimensions across four domains.

General preference dimensions. The general preference dimensions capture everyday interests, tastes, and lifestyle preferences: shows, music, books, games, art, sports, fitness, food, beauty, clothing, technology, transport, travel, and pets.

Domain-specific preference dimensions. The domain-specific preference dimensions capture personalization signals required by specialized scenarios:

- **Finance:** risk tolerance, financial news source preference, financial market sector preference, and sustainability preference.
- **Medical:** medical decision role, medical tone preference, medical risk attitude, and medical follow-up reminder preference.
- **Education:** learning style preference, learning resource preference, learning schedule preference, and learning feedback preference.
- **Mental support:** coping strategy preference, mental health topic preference, mental health support response preference, and stress response tendency.

C.2 Subtask Generation Details

This section provides additional details on the entity-controlled subtask generation process described in Section 3.2. We describe the scenario taxonomy in Section C.2.1 and present the constrained task-card generation prompt in Figure 5. During generation, the scenario, task mode, and sampled entity annotations are fixed to ensure alignment with the predefined task requirements. We then manually inspect and refine the generated task cards to ensure realism and consistency with the assigned task requirements.

C.2.1 Scenario Taxonomy

We define scenarios to provide concrete contexts for task-card generation. Table 10 summarizes 16 scenarios, including 8 shared general scenarios and 8 domain-specific scenarios across finance, medical, education, and mental-support domains. General scenarios can be instantiated with any privacy entity in $\mathcal{E}^{\mathrm{priv}}$ and the general preference dimensions. Domain-specific scenarios can also use any privacy entity in $\mathcal{E}^{\mathrm{priv}}$, but their preference dimensions are restricted to the corresponding domain. For example, finance scenarios use finance-specific preferences and are assigned only to finance-domain users; the same rule applies to medical, education, and mental-support scenarios. Among the general scenarios, profile completion is used only for dialogue generation.

Table 10: Scenario taxonomy used for task-card generation.

Scenario group	Scenario	Description
General	Writing and communication	Drafting, polishing, or revising messages, emails, invitations, and customer-service communication.
	Planning and scheduling	Creating plans, schedules, reminders, to-do lists, and time arrangements for everyday activities.
	Local life and services	Handling local service needs such as appointments, deliveries, refunds, repairs, and daily-life logistics.
	Account, forms, and verification	Organizing information for accounts, applications, verification forms, document lists, and administrative workflows.
	Travel and booking help	Supporting travel planning, booking, itinerary comparison, and transportation arrangements.
	Wellness and lifestyle	Providing lifestyle support for sleep, exercise, diet, habits, routines, and everyday wellness planning.
	Family and relationship logistics	Assisting with family coordination, relationship communication, and interpersonal planning.
	Profile completion	Completing user profile information for dialogue generation.
Finance	Personal finance operations	Supporting budgeting, bill organization, repayment planning, and everyday financial management.
	Investing and wealth	Supporting investment planning, asset allocation, and wealth-management decisions.
Medical	Urgent care and navigation	Helping with healthcare navigation, hospital selection, appointment procedures, visit planning, and medication access.
	Guidance and understanding	Explaining health information, symptoms, examination results, reports, and treatment-related questions.
Education	Education planning and academic logistics	Supporting study plans, review schedules, course selection, applications, enrollment, and academic communication.
	Learning support and academic guidance	Explaining concepts, providing learning feedback, preparing for exams, and giving personalized study suggestions.
Mental support	Internal emotional struggles	Supporting users with stress, anxiety, emotional overwhelm, self-doubt, and decision-related distress.
	Psychological topics and life context	Exploring self-understanding, relationship patterns, identity-related questions, and the psychological impact of daily life.

C.2.2 Entity-Controlled Task Generation

For each scenario and task mode, we first sample the required privacy entity set E_t^{priv} and preference entity set E_t^{pref} from the corresponding allowlists. The sampled entity sets are then fixed in the prompt: the LLM is instructed to generate only the natural-language task description and user intent while copying the sampled entity lists exactly. This design ensures that the ground-truth entity annotations are controlled by the dataset construction pipeline rather than freely chosen by the LLM.

The prompt template is shown in Figure 5. It enforces mode-specific solvability constraints: for *privacy-only* tasks, the task must be solvable using only the selected privacy entities and must not require preferences; for *preference-only* tasks, the task must be solvable using only the selected preference entities and must not require private information; and for *mixed* tasks, the task must require both selected privacy entities and selected preference entities. The prompt also requires every selected entity to be necessary for task completion, so that removing any selected entity would make the task incomplete or underspecified.

C.3 Dialogue Generation

We generate history dialogues to seed memory evidence for each user through a two-level entity coverage process. First, we assign dialogue tasks so that the selected task set jointly covers the target privacy and preference entities for each user; this user-level assignment procedure is described in Section C.3.1. Second, for each assigned task, we generate a multi-turn role-play dialogue using two LLMs, with Llama-3.1-8B-Instruct acting as the user and Gemma-3-12B-IT acting as the assistant. This task-level coverage procedure ensures that all task-required entities are disclosed in the user's turns, as described in Section C.3.2. Token statistics of the generated dialogue histories are reported in Table 11.

Table 11: Statistics of user history dialogues across domains. Token counts are computed over message content using the `cl100k_base` tokenizer, excluding chat-template overhead. Avg. tokens/user is the average total token count of all history dialogues for each user.

Domain	Users	Dialogues	Avg. tokens/dialogue	Avg. tokens/user
Education	250	5250	412.74	8667.48
Finance	250	5250	406.14	8528.92
Medical	250	5250	408.19	8571.95
Mental	250	5250	397.83	8354.45
Overall	1000	21000	406.22	8530.70

C.3.1 Dialogue Task Assignment

For each user i, we assign dialogue tasks before generating history dialogues. Each task card t contains required privacy entities E_t^{priv} and preference entities E_t^{pref}. We define the target entity set for user i as

$$G_i = \mathcal{E}_i^{\text{priv}} \cup \mathcal{E}_i^{\text{pref}}.$$

The assignment consists of two parts. First, we construct a coverage set D_i^{cov} of 12 tasks. We maintain an uncovered entity set and iteratively assign tasks that cover the largest number of remaining entities, so that the 12 selected tasks collectively cover all entities in G_i. Second, we randomly sample 9 additional unused tasks D_i^{rand} from the dialogue subtask pool to improve scenario diversity. The final dialogue task set is

$$D_i = D_i^{\text{cov}} \cup D_i^{\text{rand}}, \quad |D_i^{\text{cov}}| = 12, \quad |D_i^{\text{rand}}| = 9, \quad |D_i| = 21.$$

Since $D_i^{\text{cov}} \subseteq D_i$, this also implies the coverage constraint stated in the main text. Algorithm 1 summarizes this assignment procedure.

C.3.2 Dialogue Entity Coverage Procedure

After assigning dialogue tasks at the user level, we generate one multi-turn dialogue for each assigned task. While Algorithm 1 ensures that the selected task set covers the target entities for a user,

Algorithm 1 Dialogue task assignment with entity coverage

Require: User i, dialogue task-card pool $\mathcal{T}$, target entity set G_i, coverage size $K_{\text{cov}} = 12$, total size $K = 21$
Ensure: Assigned dialogue task set D_i

$D_i^{\text{cov}} \leftarrow \emptyset$
$R \leftarrow G_i$ ▷ uncovered entities
while $R \neq \emptyset$ **do**
  $t^\star \leftarrow \arg\max_{t \in \mathcal{T}} |\text{Ent}(t) \cap R|$
  $D_i^{\text{cov}} \leftarrow D_i^{\text{cov}} \cup \{t^\star\}$
  $R \leftarrow R \setminus \text{Ent}(t^\star)$
  $\mathcal{T} \leftarrow \mathcal{T} \setminus \{t^\star\}$
end while
while $|D_i^{\text{cov}}| < K_{\text{cov}}$ **do**
  Randomly sample an unused task t from $\mathcal{T}$
  $D_i^{\text{cov}} \leftarrow D_i^{\text{cov}} \cup \{t\}$
  $\mathcal{T} \leftarrow \mathcal{T} \setminus \{t\}$
end while
$D_i^{\text{rand}} \leftarrow \emptyset$
while $|D_i^{\text{rand}}| < K - K_{\text{cov}}$ **do**
  Randomly sample an unused task t from $\mathcal{T}$
  $D_i^{\text{rand}} \leftarrow D_i^{\text{rand}} \cup \{t\}$
  $\mathcal{T} \leftarrow \mathcal{T} \setminus \{t\}$
end while
$D_i \leftarrow D_i^{\text{cov}} \cup D_i^{\text{rand}}$
return D_i

Algorithm 2 ensures that the required entities of each individual task are disclosed in the generated dialogue. The first user turn states only the task intent and does not reveal any concrete profile value. In later turns, the user is allowed to disclose one to three new entities from the remaining set. A label is accepted only if it belongs to the task's required entity set and has not been disclosed before. The dialogue terminates only after all required entities have been covered.

Algorithm 2 Task-level entity coverage for history dialogue generation

Require: User i, task t, user profile U_i, required privacy entities E_t^{priv}, required preference entities E_t^{pref}
Ensure: Multi-turn history dialogue $H_{i,t}$

$E_t \leftarrow E_t^{\text{priv}} \cup E_t^{\text{pref}}$
$C \leftarrow \emptyset$ ▷ covered entities
Generate initial user turn u_0 from the task intent without revealing concrete values
$H_{i,t} \leftarrow [u_0]$
while $C \neq E_t$ **do**
  $R \leftarrow E_t \setminus C$ ▷ remaining entities
  Generate assistant turn a_k that acknowledges prior information and prompts continuation
  Generate next user turn u_k that discloses 1–3 entities from R
  Extract labels L_k from u_k
  $L_k \leftarrow \{e \in L_k \mid e \in R\}$ ▷ accept only valid new labels
  $C \leftarrow C \cup L_k$
  Append a_k and u_k to $H_{i,t}$
end while
Generate final assistant response a_{final} conditioned on all disclosed entities
Append a_{final} to $H_{i,t}$
return $H_{i,t}$

D SP-Mem Details

D.1 Privacy-Aware Memory Writing and Partitioned Storage

Algorithm 3 summarizes the writing-time procedure of SP-Mem. Given a user input x_t, SP-Mem converts the input into two complementary representations: fact objects for the vector branch and relation triplets for the graph branch. It then sanitizes detected private values before writing them into searchable memory, while storing mapping keys in the privacy mapping layer and exact private values in the protected private store.

Here, M_{vector} and M_{graph} denote the sanitized searchable vector and graph stores, respectively. M_{map} denotes the privacy mapping layer, and M_{priv} denotes the protected private store. We use Γ to denote mapping-key records written to the privacy mapping layer and Π to denote protected records containing exact private values.

Algorithm 3 Privacy-Aware Memory Writing and Partitioned Storage

Require: User input x_t, user ID u, sanitized vector store M_{vector}, sanitized graph store M_{graph}, privacy mapping layer M_{map}, protected private store M_{priv}
Ensure: Updated M_{vector}, M_{graph}, M_{map}, and M_{priv}

$F_t \leftarrow \textsc{ExtractFacts}(x_t)$
for each fact object $f = (y_f, \mathcal{A}_f) \in F_t$ **do**
  if $\mathcal{A}_f = \emptyset$ **then**
    $\textsc{WriteVector}(M_{\text{vector}}, y_f)$
  else
    $(\tilde{y}_f, \Gamma_f, \Pi_f) \leftarrow \textsc{SanitizeFact}(f, u)$
    $\textsc{WriteVector}(M_{\text{vector}}, \tilde{y}_f)$
    $\textsc{WriteMap}(M_{\text{map}}, \Gamma_f)$
    $\textsc{WritePrivate}(M_{\text{priv}}, \Pi_f)$
  end if
end for
$R_t \leftarrow \textsc{ExtractRelations}(x_t)$
for each relation triplet $r = (s_r, \rho_r, d_r) \in R_t$ **do**
  if ρ_r does not correspond to a privacy-sensitive attribute **then**
    $\textsc{WriteGraph}(M_{\text{graph}}, r)$
  else
    $(\tilde{r}, \Gamma_r, \Pi_r) \leftarrow \textsc{SanitizeRelation}(r, u)$
    $\textsc{WriteGraph}(M_{\text{graph}}, \tilde{r})$
    $\textsc{WriteMap}(M_{\text{map}}, \Gamma_r)$
    $\textsc{WritePrivate}(M_{\text{priv}}, \Pi_r)$
  end if
end for

D.2 Privacy Sanitization Strategies

After privacy-aware information extraction, detected private values are transformed into sanitized representations before being written into searchable memory, while non-private facts and triplets remain unchanged. To preserve task-relevant semantics without exposing exact private values, SP-Mem adopts four families of sanitization strategies: name or alias substitution, suffix-preserving masking, numerical bucketing, and LLM-based generalization. Each fine-grained privacy type τ is assigned an appropriate strategy according to a type-to-strategy policy g.

In the vector branch, each detected private value v_j in a fact is replaced with its sanitized value

$$\tilde{v}_j = \textsc{Sanitize}(v_j, g(\tau_j)),$$

producing a sanitized fact. In the graph branch, triplets with non-private relations remain unchanged, while for privacy-related triplets, the private destination value d_r is replaced with its sanitized counterpart

$$\tilde{d}_r = \textsc{Sanitize}(d_r, g(\tau_r)).$$

The four sanitization strategies are defined as follows. **(1) Name or alias substitution** replaces names, categorical values, or contact-related values with weaker substitutes, such as first-name fragments or synthetic aliases. **(2) Suffix-preserving masking** applies to structured identifiers such as phone numbers, bank accounts, credit cards, tax IDs, and passport numbers; it masks most of the value while retaining the last four digits. **(3) Numerical bucketing** maps numerical values into coarse semantic ranges, such as age groups, income levels, credit-score bands, or debt-ratio ranges. **(4) LLM-based generalization** rewrites open-ended or context-dependent private values into broader descriptions, such as generalized occupation, education, medical, relationship, transaction, insurance, or location descriptions.

Table 12 lists the type-to-strategy mapping used by SP-Mem.

Table 12: Privacy sanitization strategies for all privacy types.

Strategy	Privacy type	Example
Name/alias substitution	name	Maria Lombardi → maria
	gender	Female → gender_alias
	email	maria@example.com → email_alias
	finance status level	Medium → finance_status_alias
Suffix-preserving masking	id number	IT-ID-98427561 → `id_****7561`
	passport number	IT-P388875140 → `passport_******5140`
	phone number	+1-4155551289 → `phone_******1289`
	bank account	123456789012 → `bank_****9012`
	credit card	4111111111111234 → `card_****1234`
	tax ID	9182736450 → `tax_id_******6450`
Numerical bucketing	age	34 → age_adult
	tax payment	$6200.00 → moderate_tax_payment
	monthly income	$8500.00 → upper_middle_income
	monthly expenses	$3200.00 → moderate_expense
	account balance	$45600.00 → high_balance
	loan amount	$80000.00 → moderate_loan
	credit limit	$15000.00 → high_credit_limit
	debt ratio	0.42 → medium_debt_ratio
	investment return	$12400.00 → moderate_gain
	ROI	0.18 → high_roi
	net worth	$1200000.00 → high_net_worth
	credit score	785 → very_good_credit
LLM-based generalization	nationality	Brazilian → south_america
	occupation	nurse → healthcare_professional
	education	master's degree → higher_education
	diagnosis	Primary Insomnia → sleep_issue
	symptoms	insomnia symptoms → sleep_related
	treatments	dental cleaning → dental_treatment
	allergies	Penicillin → medication_allergy
	exams	blood pressure record → vital_signs
	surgical history	appendectomy → has_surgery
	marriage	Divorced → unpartnered
	children count	2 → has_children
	transactions	2025-10-24 Cash – Gas Station $45.75 → fuel
	insurance record	family health coverage with liability protection → health_insurance
	home address	1418 N Spruce Ave, Wichita, KS → wichita_kansas
	work address	777 S Elm St, Wichita, KS → wichita_kansas

D.3 Privacy-Aware Query Reasoning and Authorized Retrieval

Algorithm 4 summarizes the query-time reasoning and authorized retrieval procedure of SP-Mem. Given a user query q, the query analyzer constructs a structured plan $\mathcal{P}_q$ containing the task intent and a set of required entities. It first identifies the user's task, then selects only task-critical entities from a predefined entity vocabulary and marks whether each selected entity belongs to the privacy taxonomy.

The analyzer is constrained to exclude unnecessary private entities. The indicator b_q denotes whether any required entity is private. If private information is required, SP-Mem requests user consent and records the authorization decision as a_q.

Retrieval is performed over the sanitized searchable memory layer: the vector store M_{vector} and the graph store M_{graph}. The retrieved results are merged into C_q. The required entity set in $\mathcal{P}_q$ guides retrieval and limits which private values can be restored. If and only if the query requires private information and user consent is granted, SP-Mem restores the task-required exact private values through the privacy mapping layer M_{map} and the protected private store M_{priv}. Otherwise, the agent uses the sanitized context directly. The final response is generated from the resulting context $\hat{C}_q$.

Algorithm 4 Privacy-Aware Query Reasoning and Authorized Retrieval

Require: Query q, user ID u, sanitized vector store M_{vector}, sanitized graph store M_{graph}, privacy mapping layer M_{map}, protected private store M_{priv}
Ensure: Final response y

$\mathcal{P}_q \leftarrow \textsc{AnalyzeQuery}(q)$
$b_q \leftarrow \textsc{NeedPrivate}(\mathcal{P}_q)$
if $b_q = 1$ **then**
    $a_q \leftarrow \textsc{RequestAuthorization}(q, u, \mathcal{P}_q)$
else
    $a_q \leftarrow 0$
end if
$R_v \leftarrow \textsc{RetrieveVector}(q, \mathcal{P}_q, M_{\text{vector}})$
$R_g \leftarrow \textsc{RetrieveGraph}(q, \mathcal{P}_q, M_{\text{graph}})$
$C_q \leftarrow \textsc{Merge}(R_v, R_g)$
if $b_q = 1 \wedge a_q = 1$ **then**
    $\hat{C}_q \leftarrow \textsc{Restore}(C_q, \mathcal{P}_q, M_{\text{map}}, M_{\text{priv}})$
else
    $\hat{C}_q \leftarrow C_q$
end if
$y \leftarrow \textsc{Generate}(q, \hat{C}_q)$
return y

D.4 Threat Model and Security Assumptions

Security objective and scope. SP-Mem aims to prevent unauthorized disclosure or reconstruction of complete private values through the conversational interface. UPU measures unauthorized or unnecessary exact-value exposure. We further evaluate unauthorized private-value reconstruction under targeted adversarial attacks, as detailed in Appendix F.3.

Adversary capabilities. Adversaries may issue arbitrary single- or multi-turn queries, including reformulated requests, prompt injection, and fabricated consent claims. They may observe outputs and sanitized representations and combine information across turns. They have no privileged access to the privacy mapping layer, protected private store, or authorization mechanism.

Trust boundaries and authorization. Given the safety risks posed by adversarial prompting to LLMs and agents [24, 25], conversational inputs and LLM outputs are treated as untrusted, while the privacy mapping layer, protected private store, and authorization mechanism are assumed to be trusted. The LLM cannot directly access protected records or mapping keys. Exact values are restored only for task-required fields following an application-controlled authorization decision, which must be supplied through a trusted UI/API in deployment rather than inferred from conversational consent claims.

Deployment and deletion assumptions. Encryption at rest and in transit, isolated keys, and periodic key rotation are deployment requirements not evaluated in our prototype. Compromise of trusted infrastructure or authorization interfaces is outside our threat model. The user-scoped deletion procedure removes exact values, mappings, and sanitized memories while redacting associated history content, retaining only content-free audit metadata.

E Experimental Setup Details

E.1 Query-Time Evaluation Pipeline

For each memory-augmented method, user histories are first processed by the corresponding memory backend. At query time, the agent analyzes the user query, determines whether private information is required, handles authorization, retrieves relevant memory evidence, and generates a response. Across memory-augmented methods, the query analysis, authorization handling, and response-generation procedures are kept fixed, while the memory backend determines how user histories are stored and retrieved.

E.2 Evaluation Tasks

We evaluate the five task categories defined in Table 1: Preference-only, Privacy-only-allowed, Privacy-only-denied, Mixed-allowed, and Mixed-denied. P-TC is evaluated across all five categories. P-PQ is evaluated on Preference-only, Mixed-allowed, and Mixed-denied tasks, where preference usage is required. UPU is evaluated on Preference-only, Privacy-only-denied, and Mixed-denied tasks, where exact private values should not appear.

E.3 Evaluation Protocols

We use GPT-4.1 [35] as the judge model for response-quality evaluation. For response quality, we report **pairwise task completion (P-TC)** and **pairwise personalization quality (P-PQ)**, since pairwise comparison provides a natural evaluation protocol for open-ended assistant responses and can be more robust than pointwise scoring [48, 49]. For each evaluation query, we compare the SP-Mem response against the response from one baseline under the same task context. The judge is given the task description, user query, and two anonymized responses, and is asked to choose the better response according to the metric-specific rubric or return a tie. To reduce position bias, each comparison is evaluated twice with the response order swapped. We canonicalize the two judgments back to the same system identities; a non-tie winner is accepted only when the two order-swapped judgments agree, and all inconsistent cases are counted as ties. We then report the win-tie rate of SP-Mem, $(W + T)/N$, where W, T, and N denote the number of SP-Mem wins, ties, and total SP-Mem–baseline comparisons, respectively. We repeat the judging procedure three times with fixed model responses and report the mean win-tie rate across runs.

For privacy behavior, **Privacy-Appropriate Requesting (PAR)** is evaluated by comparing whether the agent requests authorization against whether the task requires exact private information. **Unnecessary Privacy Usage (UPU)** is computed with a rule-based exact-match scorer against the user's privacy-value inventory, where masked, sanitized, or generalized values are not counted as exact exposure.

The prompts for P-TC and P-PQ are shown in Figures 6 and 7, respectively.

E.4 Compute Resources

Closed-source LLM experiments, including GPT-5.2-Chat generation and GPT-4.1 judge evaluation, were conducted through API calls. Open-source backbone models were locally deployed and run on NVIDIA A40 GPUs. Memory storage and retrieval used Qdrant for vector memory and Neo4j for graph memory.

F Additional Experiment Details

F.1 Response Quality

Table 13 reports the full ablation results for the memory architecture. It compares the hybrid Vector+Graph memory against Graph-only and Vector-only variants across domains and response backbones. Tables 14, 15, 16, and 17 provide pairwise results for the Education, Finance, Medical, and Mental domains, respectively. Each table breaks down SP-Mem's win-tie rates against each baseline by evaluation task and response backbone. The five evaluation tasks are Preference-only, Privacy-only-allowed, Privacy-only-denied, Mixed-allowed, and Mixed-denied.

Table 13: Full ablation results of **Vector+Graph** memory against single-branch variants. Each value reports the mean win-tie rate, $(W + T)/N$, across three judging runs for P-TC and P-PQ within each domain and response backbone. ↑ denotes higher is better.

Domain	**Vector+Graph** vs.	GPT-5.2		Llama-3.1		DeepSeek		Qwen3	
		P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑	P-TC↑	P-PQ↑
Education	Graph-only	92.18%	87.56%	86.87%	80.95%	89.42%	86.02%	88.02%	81.14%
	Vector-only	89.41%	92.58%	86.54%	86.47%	88.97%	91.04%	88.47%	89.41%
Finance	Graph-only	87.20%	85.71%	86.34%	79.79%	90.21%	86.30%	88.77%	84.07%
	Vector-only	90.33%	90.95%	85.67%	86.89%	89.84%	92.80%	86.26%	88.84%
Medical	Graph-only	95.51%	94.02%	87.94%	82.17%	88.77%	85.98%	87.49%	83.86%
	Vector-only	94.12%	94.50%	88.43%	86.31%	90.41%	91.38%	88.40%	88.31%
Mental	Graph-only	92.76%	89.40%	88.16%	81.84%	89.18%	85.92%	86.42%	83.13%
	Vector-only	93.09%	93.88%	87.25%	82.39%	89.18%	90.85%	89.14%	90.10%

Table 14: Education-domain pairwise results averaged over three GPT-4.1 judging runs. Cells report the P-TC/P-PQ win-tie rates of **SP-Mem** against each baseline; P-PQ is not applicable to Privacy-only tasks.

		Education			
Task	**SP-Mem** vs.	GPT-5.2 P-TC/P-PQ	Llama-3.1 P-TC/P-PQ	DeepSeek P-TC/P-PQ	Qwen3 P-TC/P-PQ
Preference-only	Full-context	77.38%/85.09%	67.06%/85.68%	84.69%/85.73%	47.26%/71.90%
	MemOS	90.77%/95.90%	86.91%/92.44%	94.72%/95.70%	72.84%/90.57%
	Mem0	90.62%/93.58%	81.98%/83.70%	95.65%/95.75%	74.67%/87.75%
	Zep	92.67%/96.38%	88.15%/92.74%	96.38%/98.16%	79.65%/93.14%
Privacy-only-allowed	Full-context	64.38%/–	77.33%/–	66.10%/–	46.48%/–
	MemOS	87.24%/–	91.24%/–	95.43%/–	81.52%/–
	Mem0	90.10%/–	94.10%/–	94.47%/–	81.90%/–
	Zep	95.76%/–	94.29%/–	99.43%/–	92.76%/–
Privacy-only-denied	Full-context	98.48%/–	96.95%/–	92.38%/–	93.33%/–
	MemOS	96.57%/–	92.57%/–	97.14%/–	94.29%/–
	Mem0	93.33%/–	95.05%/–	97.33%/–	96.38%/–
	Zep	97.88%/–	95.43%/–	99.24%/–	97.14%/–
Mixed-allowed	Full-context	52.73%/70.73%	70.40%/84.47%	61.27%/74.40%	41.27%/69.73%
	MemOS	93.80%/94.60%	90.80%/89.27%	97.13%/97.40%	83.33%/89.20%
	Mem0	94.07%/93.73%	89.47%/84.40%	98.40%/95.60%	87.00%/88.60%
	Zep	95.04%/97.25%	94.93%/90.67%	98.33%/97.00%	91.07%/92.20%
Mixed-denied	Full-context	89.80%/90.40%	96.93%/98.80%	87.07%/91.07%	88.27%/90.53%
	MemOS	94.47%/94.87%	97.53%/94.00%	96.73%/96.33%	87.67%/93.47%
	Mem0	92.80%/94.87%	95.73%/88.53%	95.07%/94.20%	91.00%/90.33%
	Zep	94.37%/95.71%	98.80%/94.60%	96.87%/96.47%	92.07%/95.07%

Table 15: Finance-domain pairwise results averaged over three GPT-4.1 judging runs. Cells report the P-TC/P-PQ win-tie rates of **SP-Mem** against each baseline; P-PQ is not applicable to Privacy-only tasks.

Finance					
Task	**SP-Mem** vs.	GPT-5.2 P-TC/P-PQ	Llama-3.1 P-TC/P-PQ	DeepSeek P-TC/P-PQ	Qwen3 P-TC/P-PQ
Preference-only	Full-context	67.86%/80.63%	62.12%/84.94%	80.12%/82.15%	53.05%/76.03%
	MemOS	89.33%/93.78%	83.01%/90.57%	90.57%/93.14%	72.69%/90.86%
	Mem0	88.84%/93.63%	85.38%/89.09%	92.84%/95.21%	79.06%/92.40%
	Zep	91.49%/94.46%	86.96%/91.90%	94.84%/96.05%	79.58%/92.65%
Privacy-only-allowed	Full-context	57.78%/–	62.07%/–	62.35%/–	44.59%/–
	MemOS	80.44%/–	82.67%/–	92.30%/–	80.89%/–
	Mem0	86.96%/–	89.78%/–	96.30%/–	85.93%/–
	Zep	93.06%/–	93.48%/–	96.80%/–	92.25%/–
Privacy-only-denied	Full-context	98.67%/–	98.07%/–	94.49%/–	92.59%/–
	MemOS	93.93%/–	93.19%/–	94.96%/–	95.56%/–
	Mem0	96.15%/–	93.48%/–	96.89%/–	93.63%/–
	Zep	97.07%/–	96.89%/–	97.41%/–	95.97%/–
Mixed-allowed	Full-context	47.63%/72.74%	60.44%/84.37%	62.00%/74.74%	47.81%/73.27%
	MemOS	85.63%/91.70%	85.15%/90.05%	93.41%/94.00%	77.21%/90.35%
	Mem0	90.81%/92.44%	90.37%/86.15%	95.70%/93.19%	85.93%/90.52%
	Zep	92.02%/92.48%	92.52%/90.59%	97.66%/94.71%	88.64%/91.74%
Mixed-denied	Full-context	88.30%/90.67%	96.07%/95.63%	86.89%/86.15%	84.89%/91.70%
	MemOS	89.11%/92.30%	96.66%/94.51%	93.04%/91.41%	85.00%/93.39%
	Mem0	89.56%/92.30%	93.70%/88.96%	96.74%/91.63%	90.15%/91.93%
	Zep	92.17%/92.40%	97.56%/92.89%	95.92%/93.20%	90.83%/93.48%

Table 16: Medical-domain pairwise results averaged over three GPT-4.1 judging runs. Cells report the P-TC/P-PQ win-tie rates of **SP-Mem** against each baseline; P-PQ is not applicable to Privacy-only tasks.

Medical					
Task	**SP-Mem** vs.	GPT-5.2 P-TC/P-PQ	Llama-3.1 P-TC/P-PQ	DeepSeek P-TC/P-PQ	Qwen3 P-TC/P-PQ
Preference-only	Full-context	85.63%/87.34%	71.26%/90.12%	83.16%/88.95%	56.06%/77.98%
	MemOS	93.23%/97.33%	89.68%/96.53%	95.06%/97.78%	80.49%/96.25%
	Mem0	92.44%/95.70%	87.06%/90.72%	95.26%/97.93%	79.01%/91.90%
	Zep	94.57%/96.84%	87.56%/91.75%	96.25%/97.60%	81.34%/93.98%
Privacy-only-allowed	Full-context	62.29%/–	69.78%/–	62.50%/–	41.55%/–
	MemOS	94.37%/–	90.22%/–	98.52%/–	90.07%/–
	Mem0	90.52%/–	86.22%/–	95.70%/–	83.85%/–
	Zep	97.62%/–	93.63%/–	99.24%/–	92.68%/–
Privacy-only-denied	Full-context	96.55%/–	97.78%/–	87.59%/–	92.34%/–
	MemOS	96.00%/–	95.26%/–	96.89%/–	93.04%/–
	Mem0	91.70%/–	91.85%/–	93.93%/–	90.96%/–
	Zep	98.70%/–	98.37%/–	97.86%/–	92.83%/–
Mixed-allowed	Full-context	71.38%/82.21%	74.44%/90.07%	65.70%/78.75%	47.22%/75.43%
	MemOS	99.70%/99.11%	96.79%/95.59%	99.11%/99.26%	92.89%/96.22%
	Mem0	97.48%/96.15%	91.93%/84.44%	96.89%/96.15%	85.56%/89.78%
	Zep	98.32%/97.96%	95.63%/92.59%	99.17%/97.37%	91.89%/95.54%
Mixed-denied	Full-context	94.57%/95.48%	96.44%/96.30%	87.82%/90.35%	86.01%/92.19%
	MemOS	97.33%/98.81%	97.61%/96.19%	97.04%/97.78%	88.07%/96.96%
	Mem0	96.22%/96.81%	94.81%/89.85%	95.93%/94.37%	89.56%/91.63%
	Zep	97.36%/97.96%	96.81%/94.96%	97.00%/97.67%	89.96%/95.76%

Table 17: Mental-domain pairwise results averaged over three GPT-4.1 judging runs. Cells report the P-TC/P-PQ win-tie rates of **SP-Mem** against each baseline; P-PQ is not applicable to Privacy-only tasks.

Mental					
Task	**SP-Mem** vs.	GPT-5.2 P-TC/P-PQ	Llama-3.1 P-TC/P-PQ	DeepSeek P-TC/P-PQ	Qwen3 P-TC/P-PQ
Preference-only	Full-context	81.86%/82.67%	69.41%/85.24%	82.78%/81.74%	52.34%/70.45%
	MemOS	92.54%/95.80%	85.53%/90.02%	93.98%/96.00%	77.48%/89.48%
	Mem0	92.44%/95.70%	85.04%/87.60%	94.17%/95.85%	77.63%/90.07%
	Zep	94.62%/96.40%	86.27%/91.95%	96.14%/96.93%	78.91%/91.90%
Privacy-only-allowed	Full-context	70.33%/–	75.62%/–	66.47%/–	43.08%/–
	MemOS	82.86%/–	84.19%/–	96.00%/–	83.24%/–
	Mem0	85.71%/–	86.86%/–	93.90%/–	84.19%/–
	Zep	97.84%/–	95.81%/–	100.00%/–	95.43%/–
Privacy-only-denied	Full-context	99.24%/–	96.00%/–	93.06%/–	94.19%/–
	MemOS	95.43%/–	91.05%/–	98.86%/–	97.14%/–
	Mem0	96.00%/–	94.67%/–	98.10%/–	96.00%/–
	Zep	97.84%/–	98.10%/–	99.81%/–	95.62%/–
Mixed-allowed	Full-context	58.99%/75.89%	73.85%/87.33%	62.04%/72.59%	45.73%/67.15%
	MemOS	94.80%/95.60%	88.89%/84.89%	94.93%/96.33%	84.20%/85.53%
	Mem0	94.73%/96.13%	93.90%/83.60%	96.60%/95.73%	88.87%/87.00%
	Zep	96.37%/97.82%	94.85%/87.53%	97.60%/97.33%	91.32%/87.64%
Mixed-denied	Full-context	90.07%/93.27%	96.48%/96.95%	84.01%/86.98%	84.97%/85.24%
	MemOS	93.93%/95.67%	94.24%/86.65%	95.73%/94.00%	87.20%/88.27%
	Mem0	94.53%/96.93%	96.41%/86.45%	96.27%/95.13%	89.33%/89.27%
	Zep	93.56%/97.30%	96.82%/92.48%	96.07%/95.20%	90.78%/88.71%

F.2 Statistical Uncertainty

To assess the reliability of pairwise evaluations, we repeat GPT-4.1 judging three times with fixed responses, reporting the mean and standard deviation (SD) of the win-tie rates across runs. For each query and judging run, a win or tie is assigned a score of 1 and a loss a score of 0. We compute query-level bootstrap 95% confidence intervals (CIs) using 100,000 resamples of the three-run-averaged indicators. Results are computed separately for the Allowed and Denied conditions, pooling across four domains for each backbone–baseline–metric combination. Statistical significance is assessed using one-sided recentered-bootstrap tests of whether the win-tie rate exceeds 50%, with Holm correction across 64 comparisons.

Tables 18 and 19 report the results for allowed and denied tasks, respectively. Across both conditions, 63 of the 64 comparisons have 95% CI lower bounds above 50%, with Holm-adjusted $p < 0.001$. The only exception is Qwen3 against Full-context on allowed P-TC ($48.54 \pm 3.77\%$, 95% CI [47.31%, 49.76%], adjusted $p = 0.991$). These results indicate that SP-Mem achieves win-tie rates significantly above 50% in nearly all evaluated settings under the defined pairwise evaluation protocol.

Table 18: Statistical uncertainty of pairwise win-tie rates of **SP-Mem** against each baseline under the **Allowed condition**. Mean $\pm$ SD is computed across three GPT-4.1 judging runs, and 95% CIs are obtained using query-level bootstrap. Results are pooled across four domains within each backbone. All values are percentages.

Backbone	**SP-Mem** vs.	P-TC		P-PQ	
		Mean $\pm$ SD	95% CI	Mean $\pm$ SD	95% CI
GPT-5.2	Full-context	68.64 ± 2.91	[67.50, 69.78]	80.33 ± 1.05	[79.25, 81.39]
	MemOS	91.44 ± 1.10	[90.75, 92.10]	95.51 ± 0.67	[94.96, 96.05]
	Mem0	91.81 ± 0.82	[91.13, 92.48]	94.64 ± 0.35	[94.02, 95.25]
	Zep	94.22 ± 2.27	[93.66, 94.75]	96.07 ± 1.25	[95.55, 96.58]
Llama-3.1	Full-context	68.77 ± 2.08	[67.63, 69.90]	86.51 ± 0.66	[85.56, 87.44]
	MemOS	87.82 ± 1.77	[87.02, 88.61]	91.32 ± 1.39	[90.56, 92.07]
	Mem0	87.79 ± 0.60	[86.97, 88.59]	86.48 ± 0.57	[85.52, 87.41]
	Zep	90.82 ± 3.42	[90.17, 91.46]	91.35 ± 3.03	[90.65, 92.03]
DeepSeek	Full-context	72.92 ± 1.39	[71.79, 74.05]	80.69 ± 0.60	[79.59, 81.77]
	MemOS	94.77 ± 0.67	[94.23, 95.30]	96.11 ± 0.56	[95.59, 96.62]
	Mem0	95.44 ± 0.20	[94.82, 95.93]	95.83 ± 0.10	[95.38, 96.52]
	Zep	97.13 ± 1.38	[96.76, 97.49]	96.96 ± 1.26	[96.54, 97.37]
Qwen3	Full-context	48.54 ± 3.77	[47.31, 49.76]	72.92 ± 1.52	[71.70, 74.13]
	MemOS	80.09 ± 2.62	[79.12, 81.06]	91.12 ± 1.22	[90.35, 91.88]
	Mem0	81.83 ± 1.07	[80.86, 82.78]	89.86 ± 0.28	[89.03, 90.69]
	Zep	85.67 ± 5.78	[84.89, 86.44]	92.41 ± 2.45	[91.75, 93.06]

Table 19: Statistical uncertainty of pairwise win-tie rates of **SP-Mem** against each baseline under the **Denied condition**. Mean ± SD is computed across three GPT-4.1 judging runs, and 95% CIs are obtained using query-level bootstrap. Results are pooled across four domains within each backbone. All values are percentages.

Backbone	**SP-Mem** vs.	P-TC		P-PQ	
		Mean ± SD	95% CI	Mean ± SD	95% CI
GPT-5.2	Full-context	92.87 ± 1.23	[91.99, 93.73]	92.40 ± 1.34	[91.27, 93.48]
	MemOS	94.23 ± 1.28	[93.45, 94.99]	95.40 ± 0.94	[94.54, 96.23]
	Mem0	93.58 ± 0.77	[92.73, 94.41]	95.26 ± 0.64	[94.35, 96.14]
	Zep	95.26 ± 1.64	[94.52, 95.97]	95.52 ± 1.06	[94.56, 96.42]
Llama-3.1	Full-context	96.73 ± 0.61	[96.14, 97.30]	96.97 ± 0.21	[96.23, 97.66]
	MemOS	95.50 ± 1.10	[94.78, 96.18]	92.72 ± 1.45	[91.63, 93.76]
	Mem0	94.74 ± 0.88	[93.96, 95.48]	88.41 ± 0.36	[87.02, 89.76]
	Zep	97.44 ± 1.13	[96.93, 97.92]	93.73 ± 1.93	[92.78, 94.64]
DeepSeek	Full-context	87.99 ± 0.84	[86.83, 89.12]	88.66 ± 0.94	[87.30, 90.00]
	MemOS	96.01 ± 0.87	[95.35, 96.65]	94.89 ± 0.71	[93.95, 95.79]
	Mem0	96.12 ± 0.44	[95.44, 96.84]	93.89 ± 0.24	[92.81, 94.98]
	Zep	97.05 ± 1.21	[96.51, 97.58]	95.65 ± 1.89	[94.87, 96.39]
Qwen3	Full-context	88.13 ± 1.31	[87.00, 89.24]	89.83 ± 0.88	[88.54, 91.08]
	MemOS	89.35 ± 1.76	[88.29, 90.40]	92.91 ± 1.31	[91.84, 93.96]
	Mem0	91.20 ± 0.75	[90.23, 92.15]	90.74 ± 0.37	[89.49, 91.95]
	Zep	92.21 ± 2.81	[91.35, 93.05]	93.18 ± 2.33	[92.19, 94.14]

F.3 Adversarial Evaluation

Setup. We evaluate four adversarial strategies: multi-turn reconstruction, reversed-string disclosure, Base64-encoded disclosure, and prompt injection with fabricated consent. We select 300 private targets from 100 users across four domains, balanced across four sanitization strategies. Each backbone is evaluated on the same fixed set of 1,200 unauthorized attacks (four per target) and 300 authorized controls. Attacks are generated from sanitized information without access to exact private values, mappings, or authorization metadata.

Potential recoveries are detected through normalized matching and reconstruction checks (including reversal and Base64 decoding), followed by manual review. Recovery counts only complete target values observed in attacker-visible outputs or deterministically reconstructed across multi-turn interactions, excluding partial and incidental low-entropy matches. Prompt exposure measures unauthorized exact-value inclusion in model prompts, while store release measures exact values returned from protected storage; these events may overlap. Authorized store release is measured end-to-end over all controls, counting failures to enter the authorization path as unsuccessful releases. We estimate 95% confidence intervals using 100,000 user-clustered bootstrap resamples.

Table 20: Adversarial evaluation across four backbones. Recovery CIs are 95% user-clustered bootstrap intervals (%). Each backbone uses 1,200 unauthorized cases and 300 authorized controls.

Model	Recovery	95% CI	Prompt exposure	Unauthorized store release	Authorized store release
GPT-5.2-Chat	3/1,200	[0.00, 0.58]	2/1,200	0/1,200	299/300
Llama-3.1-8B	4/1,200	[0.00, 0.75]	3/1,200	0/1,200	226/300
DeepSeek-V3.2	1/1,200	[0.00, 0.25]	0/1,200	0/1,200	299/300
Qwen3-14B	1/1,200	[0.00, 0.25]	1/1,200	0/1,200	297/300

Results. As shown in Table 20, only 9 of 4,800 unauthorized attacks (0.19%) result in complete-value recovery, with no unauthorized protected-store releases. Residual recoveries primarily involve semantic inference or duplicated values across correlated fields. Authorized store release succeeds in at least 99% of controls for three backbones, compared with 75.33% (226/300) for Llama-3.1-8B. For Llama-3.1-8B, 73 controls fail to enter the authorization path, while authorized release succeeds in 226 of the remaining 227 controls. These results indicate that the protected-store boundary resists direct unauthorized release under the tested attacks, although inference-based disclosure risks remain.

Table 21: Human evaluation of LLM-as-a-judge reliability. Agreement rates (%) between human majority-vote judgments and GPT-4.1 (Human–GPT) and among human annotators (Human–Human), under allowed and denied conditions.

Metric	Split	Human–GPT	Human–Human
P-TC	Allowed	76.67%	74.44%
	Denied	85.00%	71.67%
P-PQ	Allowed	92.50%	86.67%
	Denied	80.00%	76.67%

F.4 Human Evaluation

To assess the reliability of the LLM judge, we conduct a blinded human evaluation on a stratified subset of 100 anonymized pairwise comparisons. Three annotators independently evaluate each response pair using the same P-TC and P-PQ criteria as GPT-4.1. P-TC is evaluated across all five task categories, while P-PQ is evaluated only for tasks requiring personalization. The final human judgment is determined by majority vote, with cases lacking a majority treated as ties. Human–GPT agreement is computed as the proportion of exact matches between GPT-4.1 judgments and majority-vote human labels. Human–Human agreement is computed as the average pairwise exact agreement across the three annotator pairs.

As shown in Table 21, Human–GPT agreement is broadly comparable to Human–Human agreement across both metrics and task settings, suggesting that GPT-4.1 provides judgments generally consistent with human evaluations.

F.5 Evaluation on WildChat-Derived Data

Setup. To assess external validity beyond synthetic dialogues, we adapt WildChat [50] conversations containing personal disclosures into memory histories and follow-up queries. Verified private values are replaced with same-type synthetic surrogates, residual identifiers are scrubbed, and the original turn order and non-target context are retained. Follow-up queries are newly generated. We evaluate 171 audited histories under paired allowed and denied conditions, using DeepSeek-V3.2 [34] for task analysis and response generation. GPT-4.1 [35] serves as a binary judge for response task success.

Results. As shown in Table 22, privacy extraction F1 and task success are lower on WildChat-derived data, while required-entity F1 remains high and UPU is nearly unchanged. These results suggest that SP-Mem maintains useful task performance and low exact-value exposure in more diverse conversational contexts. The comparisons are descriptive because the evaluation subsets and task distributions differ.

Table 22: Evaluation on the SP-Mem benchmark and WildChat-derived data. All values are percentages. Privacy F1 and Required F1 denote privacy extraction and required-entity identification, respectively.

Benchmark	Privacy F1↑	Required F1↑	UPU↓	Task success↑
SP-Mem benchmark	97.32	84.78	1.25	98.00
WildChat-derived	86.91	93.72	1.17	90.64

G Prompts

This appendix presents the prompts used for benchmark construction and response-quality evaluation. Figure 5 shows the constrained task-card generation prompt. Figures 6 and 7 provide the pairwise evaluation prompts for task completion (P-TC) and personalization quality (P-PQ). Figure 8 presents the privacy-conditioned preference selection prompt. Figures 9 and 10 show the prompts used to check consistency within privacy profiles and between privacy attributes and preferences.

You are a Task-Card Generator. Your task is to generate realistic user–assistant task cards that require personal information, user preferences, or both to deliver personalized assistance.

Input

- Scenario: the scenario name and its description.
- Mode: one of *privacy_only*, *non_privacy_only*, or *mixed*.
- Fixed privacy entities: the privacy entities that must be used in the task.
- Fixed preference entities: the preference entities that must be used in the task.

Example
[Example]

Requirements

1. Broad and reusable: describe a general task that can apply to different users and must not contain concrete personal details.
2. Goal-driven: the task should have a clear outcome that indicates successful completion.
3. Entity-dependent: every fixed privacy or preference entity must be necessary for completing the task.
4. Generic only: do not instantiate concrete privacy values, identifiers, locations, medical values, financial values, or concrete preference values.
5. Authentic and real-world: the task should reflect a common situation where users would genuinely ask an assistant for help.
6. First-party privacy: all privacy entities must refer to the user, not to another person.
7. Diversity: vary scenarios, goals, and workflows to avoid repetitive task patterns.

Output

Return exactly one JSON object with the following fields:

- scenario: the fixed scenario identifier.
- task_description: a broad, reusable task description that explains why the selected entities are needed.
- user_intent: a natural user request that initiates the conversation.
- privacy_entities: the fixed privacy entity list.
- preference_entities: the fixed preference entity list.
- mode: the fixed task mode.

Figure 5: The prompt used for constrained task-card generation. The generator uses a scenario, a mode, fixed entity annotations, and a few-shot example to produce realistic task cards while preserving ground-truth privacy and preference labels.

You are an impartial judge for pairwise evaluation of conversational assistants.
Compare Assistant A and Assistant B for Task Completion (TC).

Judging principles:

- Evaluate whether the response completes the user task and required deliverables.
- Focus on instruction-following, completeness, relevance, and practical usefulness.
- Do not prefer an answer because it is longer, more formal, or more verbose.
- Do not let position (A vs B) influence your decision.
- Output winner = "A" if Assistant A is clearly better on TC.
- Output winner = "B" if Assistant B is clearly better on TC.
- If both are similarly good or similarly weak, output TIE.

Task Description
{scenario}

User Query
{query}

Required Entities (for completion)
{required_entities}

Assistant A Response
{response_a}

Assistant B Response
{response_b}

Return ONLY JSON:
`{"winner":"A|B|TIE","reason":"one concise sentence"}`

Figure 6: Pairwise evaluation prompt for Task Completion (P-TC).

You are an impartial judge for pairwise evaluation of conversational assistants.
Compare Assistant A and Assistant B on Personalization Quality (PQ).

Judging principles:

- Evaluate whether the response uses user preferences correctly and meaningfully.
- "Meaningful" means preferences materially shape content, tone, examples, or recommendations.
- Penalize hallucinated, incorrect, or irrelevant preference usage.
- Do not prefer an answer because it is longer, more formal, or more verbose.
- Do not let response position (A vs B) influence your decision.
- Output winner = "A" if Assistant A is clearly better on PQ.
- Output winner = "B" if Assistant B is clearly better on PQ.
- Output winner = "TIE" if both are similarly good or similarly weak.

Required Preference Entities
{preference_entities}

User Preference Values (Ground Truth)
{preference_values}

User Query
{query}

Assistant A Response
{response_a}

Assistant B Response
{response_b}

Return ONLY JSON:
`{"winner":"A|B|TIE","reason":"one concise sentence"}`

Figure 7: Pairwise evaluation prompt for Personalization Quality (P-PQ).

You are a Preference Selector. Your task is to analyze a user's demographic and lifestyle profile, then select the most appropriate preferences from a given bank of non-private preference candidates.

Task
Given a user profile and a preference candidate bank across multiple preference dimensions, analyze the user's characteristics and select the top-N best-matching preference values for each dimension.

Profile Information to Consider
When selecting preferences, consider the following information from the user profile:

- **Demographics:** age, gender, nationality, occupation, and education.
- **Medical history:** past diagnosis, symptoms, and allergies. Medical history should be used only for preference refinement, not as a hard restriction.
- **Lifestyle:** marriage status, children count, monthly income, and finance status level.

Selection Requirements

- Select preferences that are realistic, personalized, and diverse.
- Avoid stereotypes or overly deterministic assumptions from demographic attributes.
- Strictly select values from the provided candidate lists.
- Each selected value must be copied verbatim from the corresponding candidate list.
- Do not invent new preferences or include private identifiers.
- Output valid JSON only, with exactly one key for each preference dimension.

Input
User Privacy Profile:
[user_privacy_profile]

Preference Candidate Bank:
[candidates_by_dimension]

Output Format

```
{
  "shows": ["<preference 1>", "<preference 2>", "..."],
  "music": ["<preference 1>", "<preference 2>", "..."]
}
```

The system then selects the least-used item from each ranked list to improve preference diversity across users.

Figure 8: The prompt used for privacy-conditioned preference selection. Given a user profile and a candidate bank, the model ranks non-private preference values for each dimension and returns structured JSON for controlled parsing.

You are a Privacy Profile Consistency Checker. Your task is to examine a single user privacy profile and identify only hard logical contradictions.

Core Rule
Flag an issue only when two or more fields are logically incompatible or explicitly self-contradictory. Do not flag a profile because a value is uncommon, atypical, or statistically unlikely.

Checks

- **Age–education–occupation:** detect impossible combinations, such as a child with a PhD or a senior professional role.
- **Numeric and financial fields:** detect invalid ratios, negative values for fields that cannot be negative, or mutually impossible numeric constraints.
- **Medical sex/gender consistency:** detect strict organ-specific contradictions, such as pregnancy-related conditions in a male profile or prostate/testicle-related conditions in a female profile.
- **Relationship fields:** detect explicit self-contradictions, such as a single marital status together with a spouse field.
- **Demographic fields:** detect direct conflicts between explicit demographic attributes, such as inconsistent nationality or citizenship fields.

Do Not Flag
Do not infer contradictions from names, addresses, language, insurance records, or treatments that are merely unusual. Do not make judgments based on stereotypes or typical life patterns.

Input
User Privacy Profile:
[user_privacy_profile]

Output Format

```
{
   "profile_conflict_label":  0 or 1,
   "issues":  ["category:  description", ...]
}
```

Set *profile_conflict_label* to 1 if and only if the issue list is non-empty. If no hard contradiction is found, return an empty issue list.

Figure 9: The prompt for privacy-profile consistency checking. The checker identifies only hard logical contradictions within a user privacy profile and returns structured JSON for controlled parsing.

You are a Privacy–Preference Consistency Checker. Your task is to examine a synthetic user persona and determine whether the user's privacy profile and non-private preferences contain any direct contradiction.

Goal
Given two views of the same user, decide whether the assigned preferences are consistent with the user's background facts. A conflict should be reported only when the two views cannot logically hold at the same time.

Conflict Definition
Label a conflict only if the information is mutually exclusive, logically incompatible, or factually contradictory. Do not label a profile as inconsistent merely because a preference is unusual, low-probability, or statistically atypical.

Checks

- **Within-domain consistency:** check whether privacy facts and preferences in the same domain directly contradict each other.
- **Cross-domain consistency:** check whether facts from one domain make preferences from another domain logically impossible.
- **Medical interpretation:** treat medical information as medical history, not necessarily as current functional limitation.
- **Direct incompatibility:** flag only conflicts that are explicitly supported by the provided fields.

Examples

- A five-year-old user with an occupation as a doctor is a conflict.
- A user who is explicitly unable to walk but prefers running is a conflict.
- A user with a history of knee surgery who prefers running is not necessarily a conflict.

Input
Privacy Profile:
[privacy_profile]

Non-private Preferences:
[non_privacy_preferences]

Output Format

```
{
  "label": 0 or 1,
  "conflicts": [
    {
      "type": "concise conflict tag",
      "reason": "brief explanation of direct incompatibility"
    }
  ],
  "explanation": "short summary of why label is 0 or 1"
}
```

Set *label* to 1 only if at least one direct conflict exists. If no conflict is found, set *label* to 0 and return an empty conflict list.

Figure 10: The prompt used for privacy-preference consistency checking. The checker identifies direct contradictions between privacy attributes and non-private preferences and returns structured JSON for controlled parsing.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction accurately state the paper's main contributions: formulating privacy-aware long-term memory, proposing SP-Mem, and introducing a benchmark and evaluation pipeline. These claims are supported by the method design in Section 2 and the experiments in Section 4, which evaluate response quality, personalization quality, privacy behavior, and inference cost across multiple LLM-based agents.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: We include a dedicated limitations section in Appendix A. It discusses the limitations of synthetic conversations in capturing implicit privacy disclosures and cross-interaction inference, the use of fixed sanitization policies, and remaining privacy risks beyond the evaluated attacks.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A]

   Justification: The paper does not present theoretical results, theorems, or formal proofs. The mathematical notation is used only to specify the memory representation, privacy-aware retrieval process, benchmark construction, and evaluation metrics.

   Guidelines:

   - The answer [N/A] means that the paper does not include theoretical results.
   - All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
   - All assumptions should be clearly stated or referenced in the statement of any theorems.
   - The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
   - Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
   - Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Section 4.1 and the appendices describe the experimental configurations, including datasets, backbone models, baselines, evaluation tasks, and metrics. We also provide implementation details, evaluation protocols, and prompt templates to support reproducibility.

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).

(d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: We publicly release the SP-Mem implementation, benchmark resources, and reproduction instructions through our GitHub repository at `https://github.com/Jensassss/SP-Mem`. The repository provides access to the dataset and includes scripts and instructions for reproducing the main experiments.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Section 4.1 and the appendices describe the experimental configurations, including datasets, backbone models, baselines, evaluation tasks, and metrics. We also provide implementation details, evaluation protocols, and prompt templates to support reproducibility.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

Justification: Appendix F.2 reports statistical uncertainty for the pairwise response-quality evaluations, including mean $\pm$ SD across three GPT-4.1 judging runs and query-level bootstrap 95% confidence intervals using 100,000 resamples, separately for allowed and denied tasks. It also provides one-sided recentered-bootstrap significance tests with Holm correction across 64 comparisons.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Appendix E describes the compute setup: closed-source LLM experiments were conducted through API calls, open-source backbones were deployed on NVIDIA A40 GPUs, and Qdrant/Neo4j were used for vector and graph memory storage and retrieval.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: We have reviewed the NeurIPS Code of Ethics and conducted the work to comply with its guidance on privacy, transparency, and reproducibility. Our evaluation uses synthetic user profiles and task scenarios, and the proposed framework is designed to reduce unnecessary exposure of sensitive user information.

   Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

    Justification: Sections 1 and 6 discuss the potential benefits of privacy-aware personalization for long-term memory agents, including improved user control and reduced unnecessary exposure of exact private values. Appendix A discusses remaining privacy risks, including re-identification, multi-turn inference attacks, and recovery of sanitized values.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
    - The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
    - The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
    - If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The work does not release high-risk models or raw real-user conversations. The released benchmark consists of synthetic user profiles, dialogues, and evaluation queries. Real-world conversations used for external validation are de-identified through synthetic surrogate replacement and removal of residual identifiers. Therefore, safeguards for high-risk data or model release are not applicable.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.

- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: We cite the existing LLMs, memory systems, and external resources used in our experiments where applicable, and provide URLs or references to their official releases. We use these assets only for research evaluation and follow their applicable licenses and terms of use.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.
    - For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
    - If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
    - For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
    - If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: We introduce a synthetic privacy-aware memory benchmark containing user profiles, historical dialogues, and task queries. Section 3 and Appendix C document its construction and evaluation setup. The public repository provides access to the released benchmark resources and accompanying documentation.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

Justification: The study does not involve crowdsourcing or human-subjects research. The human evaluation in Appendix F.4 was conducted by members of the research team to assess LLM-as-a-judge reliability, without recruiting external participants.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

Justification: The study does not involve crowdsourcing or research with human subjects. The human evaluation in Appendix F.4 was conducted internally by members of the research team, who evaluated only model-generated responses and were not study participants. No external participants or personal data were involved; therefore, IRB approval was not applicable.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: We use LLMs for dataset construction, privacy-aware memory extraction, query-time response generation, and LLM-as-a-judge evaluation. Sections 2, 3, and 4.1 document the use of LLMs in the methodology and evaluation.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.