Robust Concept Unlearning in Diffusion Models via Directional Stability Regularization

Bo-Han Lai[1], Hsuan-Tien Lin[1], Chia-Mu Yu[2], Han Zhao[3], Shang-Tse Chen[1]
[1]National Taiwan University, [2]National Yang Ming Chiao Tung University
[3]University of Illinois Urbana-Champaign

Abstract

Post-hoc concept unlearning is a practical approach to remove undesired content from text-to-image diffusion models. However, existing methods leave unlearned models fragile: small perturbations to prompts, text embeddings, or sampling-time latent states can recover supposedly erased content, even when standard endpoint metrics suggest successful erasure under nominal prompts. We study this fragility through the stability of the sampling trajectory of diffusion models. Our key observation is that prompt-, embedding-, and sampling-based attacks share a similar mechanism of perturbing the sampling dynamics, and these concepts can reappear when the unlearned model amplifies these concept-relevant perturbations. We formalize this view with a finite-time stability analysis and derive a tractable directional sharpness measure along a concept-relevant direction. Motivated by this analysis, we propose Directional Stability Regularization (DSR), a plug-in regularizer that discourages expansion in target-concept directions without directly penalizing unrelated directions. DSR is compatible with classical score-based erasure objectives, requires no adversarial training or attack-specific inner loop, adds no inference-time overhead, and can be estimated efficiently with Jacobian-vector products. Across the evaluated erasure settings, DSR reduces recovery under prompt-, embedding-, and sampling-based attacks while largely preserving prompt alignment and image quality metrics.

1 Introduction

Large-scale text-to-image diffusion models have demonstrated remarkable generative capabilities, enabling high-quality synthesis across diverse objects, styles, and visual domains [32, 37, 40, 38]. However, training on massive web-scale corpora raises safety, privacy, and intellectual-property concerns. These models may produce unsafe or biased imagery, imitate artist-specific styles, or reproduce memorized training examples and sensitive identities [41, 30, 5, 43, 13]. Retraining a large diffusion model on filtered data is computationally expensive, motivating post-hoc concept unlearning as a practical alternative. Given a pretrained diffusion model and a target concept, the goal is to suppress generation of the undesired concept while preserving the model's general utility on unrelated concepts [13, 14, 53].

Despite substantial progress, recent studies show that unlearned models can remain vulnerable to concept recovery. Concepts that appear successfully removed under nominal prompts may re-emerge under adversarial prompts, learned text embeddings, or noise injection along sampling trajectories [55, 48, 35, 28]. Although these attacks enter through different interfaces, they share a common effect on the score-induced dynamics used during sampling. Adversarial prompts and learned embeddings alter the conditional score predictions, whereas noise-injection attacks perturb intermediate latent states. Both forms of intervention can redirect the sampling trajectory toward outputs containing the target concept. These observations suggest that robust unlearning should be

40th Conference on Neural Information Processing Systems (NeurIPS 2026).

studied not only through final generated images, but also through the stability of the underlying sampling dynamics.

Several robust concept unlearning methods have been proposed to improve resistance against such perturbations, for example by searching adversarial prompts, optimizing against hard embeddings, or introducing additional robust erasure objectives [54, 25, 16, 8, 45]. While effective, these approaches often rely on attack-specific search or optimization over particular perturbation families. As a result, they provide limited mechanistic explanation of why small changes to the conditioning signal or sampling state can recover the target concept. They also leave open which property of the unlearned dynamics should be regularized to improve resistance to recovery.

We address this gap by analyzing concept resurgence as finite-time amplification of perturbations along the unlearned probability-flow ODE (PF-ODE). Diffusion generation can be viewed as transport along a score-induced sampling trajectory [44, 24], and recent studies show that nominal diffusion trajectories exhibit strong geometric regularity and low-dimensional structure [6, 7]. This motivates a trajectory-level view of concept unlearning. Because erasure modifies the score field, robustness should depend on how concept-relevant perturbations are propagated by the local dynamics along the sampling path. From this viewpoint, attacks can succeed when small concept-aligned perturbations are amplified by the unlearned score Jacobian, steering the sample toward regions associated with the target concept. We formalize this mechanism under a local first-order PF-ODE model using a finite-time directional gain that bounds the perturbation-induced output-law shift. This analysis motivates a tractable local regularization target: reducing concept-directional expansion at sampled states and timesteps. Our regularizer penalizes this local expansion during unlearning, without adversarial training or attack-specific inner loops.

Our contributions are summarized as follows:

- We formulate robust concept unlearning as local finite-time directional stability of the unlearned probability-flow ODE, unifying prompt-, embedding-, and sampling-based attacks as perturbations to the sampling dynamics.
- We introduce a finite-time directional gain that bounds the perturbation-induced Wasserstein-2 (W_2) output shift, relate this gain to a trajectory-integrated directional Rayleigh quotient of the symmetric score Jacobian, and translate the resulting control into a detector-level recovery bound.
- We propose Directional Stability Regularization (DSR), a plug-in Rayleigh-quotient regularizer that improves robustness across prompt-, embedding-, and sampling-based attacks without adversarial training or attack-specific inner loops.

2 Related Work

Concept unlearning in text-to-image diffusion models. Post-hoc concept unlearning aims to remove undesired objects, styles, identities, or unsafe content from a pretrained text-to-image diffusion model without retraining from scratch. Early approaches reduce harmful outputs through inference-time safety guidance [41], but such external safeguards leave the model parameters unchanged. Model-editing approaches therefore modify the generator itself. Representative methods include ESD [13], Concept Ablation [26], and UCE [14], which respectively use score-level fine-tuning, anchor-concept matching, and closed-form editing of text-conditioning projections. More recent methods improve scalability, locality, or efficiency through mass concept erasure, lightweight erasers, and reliable closed-form updates [29, 22, 16]. These methods differ in whether they edit cross-attention layers, U-Net parameters, adapter modules, or conditioning projections. Conventional erasure evaluation assesses target-concept suppression in generated outputs under nominal prompts and sampling settings. Our work studies the complementary question of whether the edited generative dynamics remain stable when the sampling process is perturbed toward the target concept.

Robustness and circumvention of concept unlearning. Recent attacks show that target concepts may remain recoverable through adversarial prompt search, optimized text embeddings, or sampling-time latent state perturbations [48, 55, 35, 28]. Ring-A-Bell provides model-agnostic prompt-level red teaming [48], UnlearnDiffAtk performs white-box adversarial prompt search [55], CCE recovers concepts through learned text embeddings [35], and noising probes perturb the denoising process directly [28]. These attacks enter through different interfaces, but each changes the conditional



(a) Original model (b) Standard unlearning (c) Unlearning with DSR

Figure 1: Schematic illustration of Directional Stability Regularization (DSR). (a) The original sampling trajectory reaches a region associated with the target concept. The blue arrow denotes the concept-direction probe δ_c. (b) After standard unlearning, a concept-aligned perturbation can redirect the trajectory toward that region. (c) DSR penalizes positive local expansion along the concept probe, aiming to keep the perturbed trajectory near the unperturbed unlearned trajectory. In (b) and (c), solid gray curves show unperturbed unlearned trajectories, and dashed gray curves show the original trajectory for reference. Magenta dashed and green dash-dotted curves show perturbed trajectories without and with DSR, respectively. Small magenta arrows indicate injected perturbations, and the green square marks the perturbed endpoint with DSR. Endpoint labels use diffusion-time indexing.

score or latent state encountered by the sampler. This vulnerability has motivated robust unlearning methods based on adversarial training over prompt tokens or embeddings, task-vector or subspace mechanisms, and multi-stage objectives that search embedding-space blind spots before concept erasure [54, 25, 36, 31, 8, 45]. These methods improve empirical robustness, but their coverage can depend on the attack families used during training or evaluation. In contrast, we study the local amplification mechanism that can contribute to concept recovery, and derive a regularizer from the unlearned score Jacobian rather than from an attack-specific inner loop.

Geometry and stability of diffusion sampling. Score-based diffusion models can be sampled through stochastic reverse processes or deterministic probability-flow ODEs [44, 24]. Recent work shows that deterministic diffusion trajectories exhibit strong geometric regularity and low-dimensional structure [6, 7]. Complementary theory gives Wasserstein convergence guarantees for unperturbed probability-flow ODE samplers [15]. Our work uses this trajectory view for concept unlearning. Rather than studying sampling efficiency or convergence alone, we analyze whether the unlearned score field amplifies perturbations along target-concept directions. This connects concept resurgence to finite-time stability analysis from dynamical systems, including logarithmic-norm bounds and the study of non-normal transient growth [42, 47]. Prior work studies how to erase concepts, how to recover them, or how diffusion trajectories behave in general. We connect these threads by analyzing concept recovery through finite-time amplification along concept-relevant directions, and using this analysis to motivate a local directional stability regularizer.

3 Finite-Time Directional Stability

While target concepts in unlearned models are known to resurge under prompt-, embedding-, or sampling-based perturbations, there is still no principled framework for understanding the underlying mechanism. In this work, we study this phenomenon through a local probability-flow ODE (PF-ODE) formulation that characterizes the dynamics of typical diffusion models, enabling a mechanistic analysis of how target concepts can re-emerge during generation.

Our analysis starts from the reverse-time probability-flow ODE [44],

$$\frac{dx}{dt} = f(x,t) - \frac{1}{2} g(t)^2 \, s(x,t), \tag{1}$$

where f and g are the forward SDE drift and diffusion coefficients, and the score field is written generically as $s(x,t)$. This equation is written in diffusion time t. For stability analysis we use generation time $\tau := T - t$, so sampling runs forward from $\tau = 0$ to $\tau = T$. We retain diffusion-time



Figure 2: Empirical trajectory-blending diagnostic. For a selected nudity-related prompt, all methods start from the same x_T. We blend each unlearned model's classifier-free guidance (CFG) [19] direction for the test prompt with the base-model CFG direction for the target-concept reference "nudity", then project all intermediate latents onto a principal component analysis (PCA) basis fitted jointly across methods. Panel-title colors indicate method groups: green denotes DSR, red denotes standard unlearning (ESD, AC, MACE), and blue denotes robust unlearning (STEREO, RECE, TRCE, AdvUnlearn). Circles mark initial noise x_T and stars mark final latents x_0, using diffusion-time indexing; the dashed curve is the pure base-model concept-reference trajectory. The blend scale s controls the strength of the injected concept-reference guidance, so larger s corresponds to a stronger trajectory-level attack. Movement toward the dashed curve indicates that base-model concept-reference guidance is pulling the unlearned sampler back toward the target concept. DSR trajectories remain compact under increasing concept-reference guidance, whereas several baselines drift toward the base-model concept trajectory.

arguments for the SDE coefficients, writing $f(x, t(\tau))$ and $g(t(\tau))$, with $t(\tau) := T - \tau$, while parameterizing trajectories and score fields by generation time.

Let θ denote the pretrained base-model parameters and θ' denote the parameters after unlearning. The trajectory starts from initial noise $Z = x_{\tau=0} \sim p_T$ and produces the clean output $X_{\text{out}} := x_{\tau=T} \sim p_0^{(\theta')}(\cdot \mid c)$. For latent diffusion models, all distributional distances in this section are measured in the latent state space before decoding. Let $s_\theta, s_{\theta'}$ denote the base and unlearned scores, $\bar{s}^c_{\theta'}$ the unlearned guided score, and $H(x, \tau) := \nabla_x \bar{s}^c_{\theta'}(x, \tau)$ its Jacobian. We assume a unit-norm *concept-direction probe* $\delta_c(x, \tau)$ pointing toward concept c. The analysis below is agnostic to how this probe is constructed.

Threat model. At generation time τ_a, the adversary injects an impulse along δ_c,

$$x_{\tau_a} \;\mapsto\; x_{\tau_a} + \epsilon\, \delta_c(x_{\tau_a}, \tau_a), \tag{2}$$

after which sampling proceeds under the unlearned dynamics. Realistic prompt- or embedding-space attacks act on the conditioning input rather than directly on the latent state, but locally they induce an effective perturbation of the guided score field or sampling trajectory.

3.1 Finite-Time Directional Gain

We now quantify how an attack-induced perturbation evolves after injection. Under threat model (2), we track this evolution with $\xi(\tau) := x_\tau^{\text{perturbed}} - x_\tau^{\text{clean}}$, the deviation between the attacked and clean sampling trajectories. We first describe the linearized perturbation dynamics, then define the finite-time gain G_c, connect it to a W_2 output-shift bound, and give a tractable Rayleigh-quotient upper bound in Section 3.2.

Dynamical-systems view. For fixed conditioning c, the PF-ODE defines a dynamical system with generation-time velocity field $v^c_{\theta'}(x, \tau)$. To first order, a small perturbation ξ evolves according to

the variational equation $\dot{\xi} = A(\tau)\,\xi$, where $A(\tau) := -\nabla_x f(x_\tau, t(\tau)) + \frac{1}{2} g(t(\tau))^2 H(x_\tau, \tau)$. We state the main bounds for the score-Jacobian component and give the nonzero-drift correction in Appendix B.1. The *state-transition matrix* $\Phi(\tau, \tau_a)$ maps an infinitesimal perturbation at attack time τ_a to its first-order effect at time τ, so $\|\Phi(T, \tau_a)\,\delta_c\|$ measures how much the unlearned sampler amplifies a unit concept-directional perturbation over the remainder of sampling [9].

Norm-growth identity. Here, instantaneous norm growth means the local rate at which a small trajectory perturbation ξ changes its magnitude under the linearized sampler. This rate determines whether a concept-aligned displacement is amplified or suppressed as sampling proceeds. Although the learned score Jacobian H is generally not symmetric, only its symmetric part contributes to instantaneous norm growth. For nonzero u, we define the *directional Rayleigh quotient* as a property of its symmetric part,

$$\mathcal{R}(u; H) \;:=\; \frac{u^\top H_{\mathrm{sym}}\, u}{u^\top u}, \qquad H_{\mathrm{sym}} := \tfrac{1}{2}(H + H^\top). \tag{3}$$

Equivalently, since $u^\top H_{\mathrm{asym}} u = 0$, this has the same numerical value as $u^\top H u / u^\top u$. A standard first-order linearization around the unperturbed trajectory (Appendix B.2) yields the scalar identity

$$\frac{d}{d\tau}\|\xi(\tau)\|^2 \;=\; g(t(\tau))^2\, \mathcal{R}\big(\xi(\tau);\, H\big)\, \|\xi(\tau)\|^2, \tag{4}$$

so the instantaneous directional expansion rate of ξ is set by $\mathcal{R}(\xi; H)$, i.e. the Rayleigh quotient of H_{sym} along ξ. Although the antisymmetric part H_{asym} does not change the norm instantaneously, it can rotate ξ over time toward faster-expanding eigendirections of H_{sym}, a standard route to non-normal transient growth [47].

Exact finite-time gain. Writing $\Phi(\tau, \tau_a; Z)$ to make the trajectory dependence explicit, where the clean trajectory $\{x_\tau\}_{\tau \in [\tau_a, T]}$ is generated from the initial noise Z, the exact multiplicative factor by which a concept-directional impulse propagates from time τ_a to T is the *finite-time directional gain*

$$G_c(\tau_a, T;\, Z) \;:=\; \|\Phi(T, \tau_a;\, Z)\, \delta_c(x_{\tau_a}, \tau_a)\|. \tag{5}$$

Under threat model (2), the linearized solution is $\xi(T) = \epsilon\, \Phi(T, \tau_a)\, \delta_c$, so $\|\xi(T)\| = \epsilon\, G_c$ exactly within the linearized regime. Hence, G_c is the natural object from the dynamical-systems perspective on transient amplification [47].

The reason for introducing G_c is operational. A recovery attack is concerning not simply because it moves an intermediate latent, but because that movement can change the final output distribution. Theorem 1 connects these two levels by showing that small finite-time gain means concept-aligned perturbations have limited ability to shift the unlearned output law.

Theorem 1 (Wasserstein-2 bound via finite-time directional gain)**.** *Under the assumptions of Appendix B.1, let $p_0^{(\theta')}(\cdot|c)$ be the clean output law of the unlearned PF-ODE, and let $\tilde{p}_0^{(\theta')}(\cdot|c)$ be the output law induced by the first-order linearized perturbed flow.*

$$W_2\big(p_0^{(\theta')}(\cdot|c),\, \tilde{p}_0^{(\theta')}(\cdot|c)\big) \;\le\; \epsilon \left(\mathbb{E}_Z\big[G_c(\tau_a, T; Z)^2\big]\right)^{1/2}. \tag{6}$$

The proof uses the shared-noise coupling induced by the deterministic PF-ODE flow and the variational definition of W_2 [49]; see Appendix C.

The theorem is stated for the first-order perturbed flow. Under bounded second variation, the nonlinear output law differs from its first-order approximation by $O(\epsilon^2)$ in W_2; see Remark 6 in Appendix C.

3.2 Tractable Upper Bound on Directional Gain

G_c is the exact object but it requires the full state-transition matrix Φ. We bound it by an instantaneous integrand that is tractable per sampling step. Define the trajectory-integrated directional Rayleigh quotient and the worst-case growth exponent (which integrates the largest eigenvalue of H_{sym} instead of the directional one)

$$\begin{aligned} \mathcal{S}_c(\tau_a, T;\, Z) \;&:=\; \tfrac{1}{2}\int_{\tau_a}^{T} g(t(\tau))^2\, \mathcal{R}\big(\delta_c;\, H(x_\tau, \tau)\big)\, d\tau, \\ \Lambda_{\mathrm{adv}}(\tau_a, T;\, Z) \;&:=\; \tfrac{1}{2}\int_{\tau_a}^{T} g(t(\tau))^2\, \lambda_{\max}(H_{\mathrm{sym}}(x_\tau, \tau))\, d\tau, \end{aligned} \tag{7}$$

together with a misfit-corrected version $\bar{\mathcal{S}}_c = \mathcal{S}_c + (\text{alignment slack})$. The slack accounts for rotations of the perturbation away from the probe direction into sharper directions. It vanishes when ξ stays aligned with δ_c throughout sampling, and is bounded uniformly by $\Lambda_{\text{adv}} - \mathcal{S}_c$ otherwise. The misfit-corrected exponent reduces to the worst-case growth exponent Λ_{adv} when ξ remains aligned with a top eigenvector of H_{sym} throughout the integration interval. The formal definition of the alignment misfit and a regime analysis are in Appendix B.3. The essential-supremum worst case is $\bar{\mathcal{S}}_c^{\sup}(\tau_a, T) := \operatorname{ess\,sup}_Z \bar{\mathcal{S}}_c(\tau_a, T; Z)$.

Since Φ is expensive to compute, we upper-bound its directional gain using the instantaneous Euclidean growth rate of $\|\xi(\tau)\|$. Our bound applies to the resulting latent displacement when its norm is bounded by ϵ. This impulse model is a local surrogate for the first-order displacement induced by an upstream attack, not a restriction on how the attack is implemented.

Lemma 2 (Gronwall upper bound on G_c)**.** *Under the assumptions detailed in Appendix B.1, $G_c(\tau_a, T; Z) \le e^{\bar{\mathcal{S}}_c(\tau_a, T; Z)}$ pointwise in Z.*

Combining Theorem 1 with Lemma 2 gives the tractable hierarchy

$$W_2\big(p_0^{(\theta')}, \tilde{p}_0^{(\theta')}\big) \;\le\; \epsilon \sqrt{\mathbb{E}_Z[G_c^2]} \;\le\; \epsilon \sqrt{\mathbb{E}_Z[e^{2\bar{\mathcal{S}}_c}]} \;\le\; \epsilon\, e^{\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}. \tag{8}$$

The first inequality is the shared-noise coupling bound; within the linearized regime, the per-trajectory displacement inside this bound is exactly ϵG_c. The second follows from Gronwall's inequality [18], and the third follows by taking the essential supremum over Z. Thus, the bound chain replaces the exact gain G_c with the integrated local directional term and alignment slack, trading off the Gronwall and essential-supremum relaxations for tractability.

Detector-level corollary. Theorem 1 bounds geometric output displacement, while evaluation often uses thresholded concept detectors. The same exponent also yields a detector-level adversarial-inflation bound. Let $\mathcal{C}$ be any measurable detector-recovery region and let $\mathcal{C}^r$ be its r-thickening. Appendix B.4 proves that, for any $r > 0$,

$$\Pr_{\tilde{p}_0^{(\theta')}}[X \in \mathcal{C}] \;\le\; \Pr_{p_0^{(\theta')}}[X \in \mathcal{C}^r] + \frac{\epsilon^2 e^{2\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}}{r^2}. \tag{9}$$

This coupling-and-Markov argument using the W_2 bound [49, 11] does not require a Lipschitz detector. Thus, lowering $\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)$ tightens the upper bound on output-law drift and reduces the attack-induced increase in detector recovery bound.

What this says about unlearning. Within this local model, concept resurgence can be viewed as an adversarial concept-directional perturbation that shifts the output law away from the unperturbed unlearned distribution. The bound chain (8) upper-bounds this shift by $\epsilon\, e^{\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}$, so $e^{\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}$ acts as the trajectory-level amplification factor between an attacker's latent budget and the resulting output-law shift. Standard erasure objectives such as ESD constrain score predictions at sampled states, but they do not explicitly constrain the finite-time amplification of perturbations around the resulting trajectory. Thus, endpoint erasure and trajectory stability are distinct requirements.

The impulse model gives the cleanest statement; concept-aligned inputs applied across multiple denoising steps admit the following extension within the same linearized regime.

Proposition 3 (Persistent-forcing extension)**.** *Suppose the adversary applies an external forcing $b(r) = \alpha(r)\delta_c(x_r, r)$ along the clean trajectory for $r \in [\tau_a, T]$, where $|\alpha(r)| \le \epsilon$. Let $\bar{\mathcal{S}}_{c,\text{per}}^{\sup}(\tau_a, T) := \operatorname{ess\,sup}_{Z \sim p_T} \sup_{r \in [\tau_a, T]} \bar{\mathcal{S}}_c(r, T; Z)$ be finite. Then by Duhamel's formula [46] (Appendix C.4), under the assumptions of Theorem 1, for p_T-almost every trajectory,*

$$\|\xi(T)\| \;\le\; \epsilon \int_{\tau_a}^{T} e^{\bar{\mathcal{S}}_c(r, T; Z)}\, dr \;\le\; \epsilon\,(T - \tau_a)\, e^{\bar{\mathcal{S}}_{c,\text{per}}^{\sup}(\tau_a, T)}, \tag{10}$$

and the corresponding W_2 bound on the output law follows by the same shared-noise coupling.

Here the forcing direction may vary across timesteps through $\delta_c(x_r, r)$, but each infinitesimal input is aligned with the local concept probe. Compared with the impulse bound, the uniform persistent-forcing bound includes the duration factor $(T - \tau_a)$ and takes the supremum over input start times. Both bounds are controlled by the same family of directional-gain exponents.

3.3 Concept-Directional Expansion

The directional part of the bound is governed by $\mathcal{R}(\delta_c; H)$, which admits a clean spectral reading. If H_{sym} has orthonormal eigenpairs $\{(\lambda_i, v_i)\}$, then

$$\mathcal{R}(u; H) \;=\; \sum_i \lambda_i \, \cos^2 \alpha_i, \qquad \cos \alpha_i = v_i^\top u / \|u\|, \tag{11}$$

a cosine-squared-weighted average of eigenvalues, by the standard spectral decomposition for symmetric matrices [20]. A large positive $\mathcal{R}(\delta_c; H)$ therefore reflects the combined effect of large positive eigenvalues of H_{sym} and alignment of δ_c with their eigenspaces. Fast-expansion directions orthogonal to δ_c are outside the direct threat model except through the alignment slack.

Why directional, not global sharpness? The natural alternative replaces $\mathcal{R}(\delta_c; H)$ in $\mathcal{S}_c$ by $\lambda_{\max}(H_{\mathrm{sym}})$, recovering the worst-case growth exponent Λ_{adv} already defined in Eq. (7). Eq. (8) holds with the analogous $\Lambda_{\mathrm{adv}}^{\mathrm{sup}}$ in place of $\bar{\mathcal{S}}_c^{\mathrm{sup}}$, so the global exponent also gives a valid but conservative bound on W_2. It penalizes expansion in *every* direction, including directions orthogonal to δ_c that carry no direct implication under the concept-directional threat model. The directional exponent instead tracks the concept-directional perturbations specified by our threat model. Its remaining slack comes from finite-time rotation of ξ away from δ_c; see Appendix B.3.

4 Directional Stability Regularization

Section 3 connects the amplification of concept-aligned perturbations to shifts in the unlearned output distribution. We turn this analysis into Directional Stability Regularization (DSR), a regularizer that penalizes local expansion along a target-concept probe. Figure 1 illustrates the intended effect on perturbed sampling trajectories.

4.1 From Finite-Time Stability to a Local Regularizer

The bound chain in Eq. (8) identifies finite-time directional gain as the quantity governing first-order output-law displacement. Directly optimizing this gain requires propagating sensitivities through the sampling trajectory. Lemma 2 instead relates it to a trajectory-integrated directional Rayleigh quotient, together with alignment slack. This motivates a local training signal: suppress positive expansion along the target-concept direction at sampled latents and timesteps.

Let c_e denote the target concept, and let $\delta_c(x_\tau, \tau)$ be the normalized difference between the frozen base model's target-conditioned and unconditional scores, and let $H_{\theta'}^{c_e}(x_\tau, \tau) := \nabla_x s_{\theta'}(x_\tau, \tau, c_e)$ be the unlearned target-conditioned score Jacobian. We define the DSR loss as

$$\mathcal{L}_{\mathrm{DSR}}(\theta') = \mathbb{E}_{x_\tau, \tau}\Big[\phi\big(\mathcal{R}\big(\delta_c(x_\tau, \tau); H_{\theta'}^{c_e}(x_\tau, \tau)\big)\big)\Big], \qquad \phi(z) = [z]_+. \tag{12}$$

This sampled penalty targets local directional expansion, motivated by the Rayleigh-quotient term underlying the trajectory-level exponent in Lemma 2, which bounds first-order perturbation growth.

4.2 Probe Direction and One-Sided Penalty

Why use the frozen base-model direction? The probe should identify the original target-concept semantics throughout training. We therefore compute δ_c from the difference between the frozen base model's target-conditioned and unconditional scores. A direction computed from the evolving unlearned model could change as its response to c_e is suppressed or redirected toward a safe substitute. The base-model probe retains the original semantic reference while the regularizer changes the unlearned field's response along it. The base-model parameters are frozen, but the probe is recomputed at each sampled latent and timestep and detached from the training graph.

Why use a one-sided penalty? The sign of the Rayleigh quotient distinguishes expanding from contracting contributions of the score Jacobian along the probe. Positive values contribute to perturbation growth, whereas negative values contribute to its suppression. The positive-part penalty in Eq. (12) therefore suppresses the expanding contribution while leaving negative values unpenalized. This choice targets concept-directional expansion without imposing contraction in every direction.

4.3 Training Objective and Base Erasure Instantiation

The final objective combines erasure, directional stability, and unconditional preservation:

$$\mathcal{L}(\theta') = \mathcal{L}_{\text{erase}}(\theta') + \lambda_{\text{DSR}}\mathcal{L}_{\text{DSR}}(\theta') + \lambda_u\mathcal{L}_{\text{uncond}}(\theta'), \tag{13}$$

where, for each sampled latent and timestep,

$$\mathcal{L}_{\text{uncond}} = \|\epsilon_{\theta'}(x_\tau, \varnothing) - \epsilon_\theta(x_\tau, \varnothing)\|_2^2 . \tag{14}$$

Here ϵ_θ and $\epsilon_{\theta'}$ denote the frozen base and trainable unlearned model, respectively. The erasure term changes the model's response to c_e, the DSR term penalizes local expansion along its probe, and the preservation term discourages drift in the base model's unconditional prediction during unlearning.

In our experiments, we instantiate $\mathcal{L}_{\text{erase}}$ with an ESD-style objective [13] using a concept-in-context anchor, inspired by anchor/target-based erasure objectives [26, 56, 4]:

$$\begin{aligned} \mathcal{L}_{\text{erase}}(\theta') &= \mathbb{E}_{x_\tau,\tau,a}\left[\|\epsilon_{\theta'}(x_\tau, c_e) - T_{\text{erase}}(x_\tau, c_e, a)\|_2^2\right], \\ T_{\text{erase}} &= \epsilon_u + \eta_a(\epsilon_a - \epsilon_u) - \eta_e(\epsilon_e - \epsilon_u), \end{aligned} \tag{15}$$

where $\epsilon_u = \epsilon_\theta(x_\tau, \varnothing)$, $\epsilon_e = \epsilon_\theta(x_\tau, c_e)$, and $\epsilon_a = \epsilon_\theta(x_\tau, a)$. The sampled anchor a is a generated sentence containing c_e and describing a context in which it appears. The positive anchor component and negative bare-concept component are intended to preserve contextual structure and cancel the isolated concept signal, respectively. Setting $\eta_a = 0$ recovers the original ESD negative-guidance target; setting $\eta_e = \eta_a = C$ gives $T_{\text{erase}} = \epsilon_u - C(\epsilon_e - \epsilon_a)$. Our default runs apply Adaptive Projected Guidance (APG) [39] to these signed target components, as specified in Appendix D.2. The anchor and APG specify the base erasure target; the DSR probe remains the frozen base target-versus-unconditional direction. We ablate these implementation choices in Appendix F.2.

The implementation evaluates the scalar Rayleigh quotient with a Jacobian-vector product, avoiding explicit Jacobian construction or eigendecomposition. Estimation details and hyperparameters are provided in Appendix D.2 and Appendix D.3.

5 Experimental Results

We evaluate whether DSR improves robustness against concept recovery, preserves utility on unrelated prompts, and yields more stable trajectories under concept-direction blending. The evaluation covers four concept families: unsafe nudity, artistic style (*Van Gogh*), object categories from Imagenette and cartoon characters (*Pikachu* and *Snoopy*).

5.1 Experimental Setup

Models, datasets, and baselines. Following the Diffusion-MU-Attack benchmark [55], all methods erase concepts from Stable Diffusion v1.4. For nudity we use the I2P benchmark [41]; for style and objects we use the prompt sets and the Imagenette subset from [55]. Attack-specific prompt pools are described in Appendix E.2. We compare against standard and robust unlearning methods, using each baseline's official checkpoint. We group methods by whether their unlearning procedure explicitly targets resistance to concept recovery; "robust" denotes this design objective rather than a guarantee against every attack. Full setup is in Appendix E.1.

Attacks. We evaluate robustness against three adaptive concept-recovery attacks and one trajectory-level probe. UnlearnDiffAtk (UD) [55] performs white-box search over adversarial prompt perturbations, where UD-Pre uses the unsafe prompt only and UD-Post uses the optimized attack prompt. Ring-A-Bell (RAB) [48] constructs black-box prompt-level bypasses, and CCE [35] learns an adversarial embedding that restores the target concept through the text-embedding space. RAB-K denotes adversarial prompts with length K; we report $K \in \{16, 38, 77\}$. For trajectory-level analysis, we additionally use noising probes [28], which perturb the denoising process and therefore stress the stability mechanism studied in Section 3.2. Details are given in Appendix E.2.

Table 1: *Nudity* erasure under adaptive attacks. ASR values are rates, where lower is better. Gray rows are representative robust unlearning baselines; green marks our method. FID/CLIP use 30k MS-COCO captions, while TIFA v1.0 uses curated prompts and VQA accuracy. The best and runner-up values for each metric are **bolded** and underlined, respectively.

Method	ASR ↓						MS-COCO-30k		TIFA v1.0
	UD Pre [55]	UD Post [55]	CCE [35]	RAB-K16 [48]	RAB-K38	RAB-K77	FID ↓	CLIP ↑	Score ↑
ESD [13]	0.20	0.74	0.82	0.47	0.55	0.53	13.78	30.46	0.67
AC [26]	0.21	0.81	0.85	0.63	0.64	0.62	20.42	**31.48**	**0.71**
MACE [29]	0.09	0.74	0.82	0.06	0.09	0.14	**12.74**	29.32	0.58
RECE [16]	0.13	0.70	0.73	0.16	0.13	0.13	14.44	30.99	0.69
AdvUnlearn [54]	0.04	0.22	0.84	0.02	0.01	**0.00**	15.08	29.32	0.59
TRCE [8]	0.04	0.42	0.82	0.02	0.02	0.02	12.83	31.01	0.68
STEREO [45]	0.03	0.32	**0.04**	0.09	0.04	0.08	15.46	30.19	0.66
Ours	**0.01**	**0.17**	0.47	**0.00**	**0.00**	**0.00**	19.65	30.28	0.69

Table 2: Object erasure for *tench* (left) and *parachute* (right); UD reports post-optimization ASR.

Method	ASR ↓			MS-COCO-30k		Method	ASR ↓			MS-COCO-30k	
	UD Post [55]	CCE [35]	Noise [28]	FID ↓	CLIP ↑		UD Post [55]	CCE [35]	Noise [28]	FID ↓	CLIP ↑
STEREO [45]	**0.02**	0.02	**0.00**	16.49	30.57	RECE [16]	0.32	0.91	0.06	**14.41**	**31.25**
AdvUnlearn [54]	0.06	0.62	0.02	14.70	30.93	AdvUnlearn [54]	**0.12**	0.98	0.06	14.75	30.84
Ours	0.08	**0.01**	**0.00**	**12.04**	**31.32**	Ours	0.30	**0.06**	**0.02**	16.25	30.89

Metrics. For nudity, attack success rate is measured by the NudeNet detector [2] used in prior work. For object and style erasure, ASR is measured by the benchmark classifiers, ImageNet ResNet-50 for objects and the artist classifier from [55] for style. We report attack success rate (ASR) as a lower-is-better robustness metric. To track utility, we report FID and CLIP score on 30k MS-COCO captions [27]. We also use TIFA [21], a VQA-based benchmark for evaluating whether generated images preserve prompt-level details.

5.2 Robustness Against Concept Recovery

Tables 1–2 report attack success rates across nudity and object erasure; lower ASR means stronger resistance to concept recovery. Following the setup above, the nudity table reports UD-Pre, UD-Post, CCE, and RAB results, while the object tables in the main paper report UD-Post, CCE, and noising-probe results. Additional style and object results are deferred to Appendix F.5.

On nudity erasure (Table 1), DSR is strongest on UD and RAB among the reported methods. It obtains the lowest UD-Pre and UD-Post ASR, reducing the strongest robust baseline on UD-Post from 0.22 to 0.17. It also drives all three RAB settings to zero ASR. For CCE, STEREO remains the strongest method, which is expected because it directly trains against an embedding-inversion-style threat. DSR is nevertheless the runner-up on CCE and is substantially below standard unlearning methods and most robust baselines. This pattern supports the main design goal: DSR is not specialized to a single attack family, but improves robustness across prompt-level, embedding-level, and black-box prompt attacks. The object erasure results in Table 2 further support the trajectory-stability claim. DSR gives the best CCE ASR for both concepts, matches the best noising-probe ASR for *tench*, and gives the best noising-probe ASR for *parachute*. UD-Post results vary by concept and baseline, which suggests that DSR's most consistent gains appear on embedding- and trajectory-level recovery. The utility columns provide a guardrail against a simple over-erasure explanation: DSR is not best on every utility metric, but the FID, CLIP, and TIFA scores do not indicate an obvious collapse in image quality or prompt alignment. This suggests that the robustness gains are not explained solely by broadly degrading generation. Further qualitative and quantitative results are provided in Appendix F.

5.3 Efficiency and Trajectory Stability

Figure 3 compares the computational profile of DSR with existing unlearning methods. We follow the recommended training recipe for each method and report usable wall-clock time on a single GPU, separating preparation from model updates where applicable. DSR is more efficient than attack-optimized robust baselines because it avoids the attack-specific inner loops required by many robust unlearning methods and does not require additional data preparation.



Figure 3: Efficiency comparison across unlearning methods. Stacked bars show data-preparation and training time on a log scale, and the line reports peak GPU memory. Red and blue denote standard and robust unlearning baselines, respectively, and green highlights DSR.

Figure 2 visualizes trajectory stability for a nudity-related prompt "winona ryder in repose, kiera knightly in repose, traditional corsican, . . . " and the target-concept reference "nudity". Starting from the same initial noise Z, we blend each method's CFG direction with the base concept-reference direction and project the resulting trajectories with shared PCA. DSR stays closer to the unlearned trajectory, indicating weaker pullback toward the target-concept direction. The blending rule is specified in Appendix F.6.

6 Limitations

Our analysis is local and first-order, so the bounds are most informative for small prompt, embedding, or latent perturbations that keep the attacked trajectory near the clean PF-ODE trajectory. DSR is also directional, it controls expansion along the base-model concept direction, not all possible adversarial directions. Finally, the bound concerns distributional shift rather than semantic absence; reducing W_2 shift from the unperturbed unlearned output law does not prove that no visually related concept can be generated through another basin. Additional technical caveats are deferred to Appendix B.5.

7 Conclusion

This work studies robust concept unlearning through the stability of diffusion sampling trajectories. We show that target concepts can re-emerge when perturbations are amplified along base-model concept directions, and identify a directional Rayleigh-quotient term that controls this local amplification under the PF-ODE view. Motivated by this analysis, we propose Directional Stability Regularization (DSR), a plug-in regularizer that penalizes concept-directional expansion during unlearning.

Across the evaluated erasure settings, DSR improves resistance to prompt-level, embedding-level, and sampling-time recovery attacks while preserving competitive generation quality and prompt alignment. Together, the results suggest that robust unlearning should control not only endpoint behavior, but also the local expansion of the sampling trajectory.

Acknowledgments and Disclosure of Funding

This work was supported in part by the joint research program between the University Academic Alliance in Taiwan (UAAT) and the University of Illinois System (U of I) by the National Science and Technology Council (NSTC) under Grants NSTC 115-2628-E-002-029. We also thank the National Center for High-performance Computing (NCHC) for providing computational and storage resources.

References

[1] Ibtihel Amara, Ahmed Imtiaz Humayun, Ivana Kajic, Zarana Parekh, Natalie Harris, Sarah Young, Chirag Nagpal, Najoung Kim, Junfeng He, Cristina Nader Vasconcelos, Deepak Ramachandran, Golnoosh Farnadi, Katherine Heller, Mohammad Havaei, and Negar Rostamzadeh. Erasing more than intended? how concept erasure degrades the generation of non-target concepts. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.

[2] Praneeth Bedapudi, Brett Koonce, and Alireza Ayinmehr. Nudenet: Neural nets for nudity classification, detection and selective censoring, 2019.

[3] Anh Bui, Long Vuong, Khanh Doan, Trung Le, Paul Montague, Tamas Abraham, and Dinh Phung. Erasing undesirable concepts in diffusion models with adversarial preservation. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[4] Anh Bui, Thuy-Trang Vu, Long Vuong, Trung Le, Paul Montague, Tamas Abraham, Junae Kim, and Dinh Phung. Fantastic targets for concept erasure in diffusion models and where to find them. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025.

[5] Nicolas Carlini, Jamie Hayes, Milad Nasr, Matthew Jagielski, Vikash Sehwag, Florian Tramer, Borja Balle, Daphne Ippolito, and Eric Wallace. Extracting training data from diffusion models. In *USENIX security symposium*, 2023.

[6] Defang Chen, Zhenyu Zhou, Can Wang, Chunhua Shen, and Siwei Lyu. On the trajectory regularity of ODE-based diffusion sampling. In *International Conference on Machine Learning (ICML)*, 2024.

[7] Defang Chen, Zhenyu Zhou, Can Wang, and Siwei Lyu. Geometric regularity in deterministic sampling dynamics of diffusion-based generative models. *Journal of Statistical Mechanics: Theory and Experiment*, 2025.

[8] Ruidong Chen, Honglin Guo, Lanjun Wang, Chenyu Zhang, Weizhi Nie, and An-An Liu. Trce: Towards reliable malicious concept erasure in text-to-image diffusion models. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.

[9] Earl A. Coddington and Norman Levinson. *Theory of Ordinary Differential Equations*. McGraw-Hill, 1955.

[10] Kaiyuan Deng, Gen Li, Yang Xiao, Bo Hui, and Xiaolong Ma. Forget many, forget right: Scalable and precise concept unlearning in diffusion models. In *International Conference on Learning Representations (ICLR)*, 2026.

[11] Rick Durrett. *Probability: Theory and Examples*. Cambridge University Press, fifth edition, 2019.

[12] Gerald B. Folland. *Real Analysis: Modern Techniques and Their Applications*. John Wiley & Sons, second edition, 1999.

[13] Rohit Gandikota, Joanna Materzynska, Jaden Fiotto-Kaufman, and David Bau. Erasing concepts from diffusion models. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023.

[14] Rohit Gandikota, Hadas Orgad, Yonatan Belinkov, Joanna Materzyńska, and David Bau. Unified concept editing in diffusion models. In *IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2024.

[15] Xuefeng Gao and Lingjiong Zhu. Convergence analysis for general probability flow ODEs of diffusion models in wasserstein distances. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2025.

[16] Chao Gong, Kai Chen, Zhipeng Wei, Jingjing Chen, and Yu-Gang Jiang. Reliable and efficient concept erasure of text-to-image diffusion models. In *European Conference on Computer Vision (ECCV)*, 2024.

[17] Xiaoxuan Han, Songlin Yang, Wei Wang, Yang Li, and Jing Dong. Adaptive median smoothing: Adversarial defense for unlearned text-to-image diffusion models at inference time. In *International Conference on Machine Learning (ICML)*, 2025.

[18] Philip Hartman. *Ordinary Differential Equations*, volume 38 of *Classics in Applied Mathematics*. SIAM, 2002. doi: 10.1137/1.9780898719222.

[19] Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. In *NeurIPS Workshop on Deep Generative Models and Downstream Applications*, 2021.

[20] Roger A. Horn and Charles R. Johnson. *Matrix Analysis*. Cambridge University Press, second edition, 2012.

[21] Yushi Hu, Benlin Liu, Jungo Kasai, Yizhong Wang, Mari Ostendorf, Ranjay Krishna, and Noah A Smith. Tifa: Accurate and interpretable text-to-image faithfulness evaluation with question answering. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023.

[22] Chi-Pin Huang, Kai-Po Chang, Chung-Ting Tsai, Yung-Hsuan Lai, Fu-En Yang, and Yu-Chiang Frank Wang. Receler: Reliable concept erasing of text-to-image diffusion models via lightweight erasers. In *European Conference on Computer Vision (ECCV)*, 2024.

[23] Anubhav Jain, Takashi Shibuya, Yuya Kobayashi, Yuhta Takida, Nasir Memon, Julian Togelius, and Yuki Mitsufuji. Rethinking negative prompting for concept suppression: Unconditional anchoring and localized guidance. *Transactions on Machine Learning Research (TMLR)*, 2026.

[24] Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[25] Changhoon Kim, Kyle Min, and Yezhou Yang. R.a.c.e.: Robust adversarial concept erasure for secure text-to-image diffusion model. In *European Conference on Computer Vision (ECCV)*, 2024.

[26] Nupur Kumari, Bingliang Zhang, Sheng-Yu Wang, Eli Shechtman, Richard Zhang, and Jun-Yan Zhu. Ablating concepts in text-to-image diffusion models. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023.

[27] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision (ECCV)*, 2014.

[28] Kevin Lu, Nicky Kriplani, Rohit Gandikota, Minh Pham, David Bau, Chinmay Hegde, and Niv Cohen. When are concepts erased from diffusion models? In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025.

[29] Shilin Lu, Zilan Wang, Leyang Li, Yanzhu Liu, and Adams Wai-Kin Kong. Mace: Mass concept erasure in diffusion models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

[30] Sasha Luccioni, Christopher Akiki, Margaret Mitchell, and Yacine Jernite. Stable bias: Evaluating societal representations in diffusion models. *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[31] Kien Nguyen, Anh Tran, and Cuong Pham. Suma: A subspace mapping approach for robust and effective concept erasure in text-to-image diffusion models. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.

[32] Alex Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob McGrew, Ilya Sutskever, and Mark Chen. Glide: Towards photorealistic image generation and editing with text-guided diffusion models. In *International Conference on Machine Learning (ICML)*, 2022.

[33] Yong-Hyun Park, Sangdoo Yun, Jin-Hwa Kim, Junho Kim, Geonhui Jang, Yonghyun Jeong, Junghyo Jo, and Gayoung Lee. Direct unlearning optimization for robust and safe text-to-image models. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[34] Amnon Pazy. *Semigroups of Linear Operators and Applications to Partial Differential Equations*, volume 44 of *Applied Mathematical Sciences*. Springer, 1983. doi: 10.1007/978-1-4612-5561-1.

[35] Minh Pham, Kelly O. Marshall, Niv Cohen, Govind Mittal, and Chinmay Hegde. Circumventing concept erasure methods for text-to-image generative models. In *International Conference on Learning Representations (ICLR)*, 2024.

[36] Minh Pham, Kelly O. Marshall, Chinmay Hegde, and Niv Cohen. Robust concept erasure using task vectors. In *CVPR Workshop on Generative Models for Computer Vision*, 2024.

[37] Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents, 2022.

[38] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

[39] Seyedmorteza Sadat, Otmar Hilliges, and Romann M. Weber. Eliminating oversaturation and artifacts of high guidance scales in diffusion models. In *International Conference on Learning Representations (ICLR)*, 2025.

[40] Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[41] Patrick Schramowski, Manuel Brack, Björn Deiseroth, and Kristian Kersting. Safe latent diffusion: Mitigating inappropriate degeneration in diffusion models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023.

[42] Gustaf Söderlind. The logarithmic norm. history and modern theory. *BIT Numerical Mathematics*, 46(3):631–652, 2006. doi: 10.1007/s10543-006-0069-9.

[43] Gowthami Somepalli, Vasu Singla, Micah Goldblum, Jonas Geiping, and Tom Goldstein. Understanding and mitigating copying in diffusion models. *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[44] Yang Song, Jascha Sohl-Dickstein, Diederik P. Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations (ICLR)*, 2021.

[45] Koushik Srivatsan, Fahad Shamshad, Muzammal Naseer, Vishal M Patel, and Karthik Nandakumar. Stereo: A two-stage framework for adversarially robust concept erasing from text-to-image diffusion models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

[46] Michael E. Taylor. Linear systems of differential equations. URL `https://mtaylor.web.unc.edu/wp-content/uploads/sites/16915/2018/04/odech3.pdf`. Online notes. Sections 4, 8, and 9: Nonhomogeneous equations, variable-coefficient systems, variation of parameters, and Duhamel's formula.

[47] Lloyd N. Trefethen and Mark Embree. *Spectra and Pseudospectra: The Behavior of Nonnormal Matrices and Operators*. Princeton University Press, 2005.

[48] Yu-Lin Tsai, Chia-Yi Hsu, Chulin Xie, Chih-Hsun Lin, Jia-You Chen, Bo Li, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. Ring-a-bell! how reliable are concept removal methods for diffusion models? In *International Conference on Learning Representations (ICLR)*, 2024.

[49] Cédric Villani. *Optimal Transport: Old and New*, volume 338 of *Grundlehren der Mathematischen Wissenschaften*. Springer, 2009. doi: 10.1007/978-3-540-71050-9.

[50] Tianyun Yang, Ziniu Li, Juan Cao, and Chang Xu. Pruning for robust concept erasing in diffusion models. In *NeurIPS Workshop on Safe Generative AI*, 2024.

[51] Yijun Yang, Ruiyuan Gao, Xiao Yang, Jianyuan Zhong, and Qiang Xu. Guardt2i: Defending text-to-image models from adversarial prompts. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[52] Jaehong Yoon, Shoubin Yu, Vaidehi Patil, Huaxiu Yao, and Mohit Bansal. Safree: Training-free and adaptive guard for safe text-to-image and video generation. In *International Conference on Learning Representations (ICLR)*, 2025.

[53] Gong Zhang, Kai Wang, Xingqian Xu, Zhangyang Wang, and Humphrey Shi. Forget-me-not: Learning to forget in text-to-image diffusion models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, 2024.

[54] Yimeng Zhang, Xin Chen, Jinghan Jia, Yihua Zhang, Chongyu Fan, Jiancheng Liu, Mingyi Hong, Ke Ding, and Sijia Liu. Defensive unlearning with adversarial training for robust concept erasure in diffusion models. *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[55] Yimeng Zhang, Jinghan Jia, Xin Chen, Aochuan Chen, Yihua Zhang, Jiancheng Liu, Ke Ding, and Sijia Liu. To generate or not? safety-driven unlearned diffusion models are still easy to generate unsafe images ... for now. In *European Conference on Computer Vision (ECCV)*, 2024.

[56] Jingyu Zhu, Ruiqi Zhang, Licong Lin, and Song Mei. Choose your anchor wisely: Effective unlearning diffusion models via concept reconditioning. In *NeurIPS Safe Generative AI Workshop*, 2024.

Appendix Contents

A Additional Related Work **16**

B Additional Details for Directional Stability Analysis **16**

B.1 Assumptions for the Stability Analysis 16

B.2 Linearized Perturbation Dynamics 17

B.3 Alignment Misfit 17

B.4 Detector Recovery Bound 18

B.5 Additional Technical Caveats 18

C Proofs **19**

C.1 Proof of Theorem 1 (Wasserstein-2 bound via G_c) 19

C.2 Proof of Lemma 2 (Gronwall upper bound on G_c) 20

C.3 Proof of Corollary 5 (Detector Recovery Bound) 20

C.4 Proof of Proposition 3 (Persistent-Forcing Extension) 21

D Method and Implementation Details **22**

D.1 Concept-in-Context Prompt Generation 22

D.2 DSR Implementation Details 22

D.3 Efficient Estimation of the Directional Rayleigh Quotient 23

E Experimental Details **23**

E.1 Models, Datasets, and Generation Setup 23

E.2 Attack Setup 24

E.3 Computational Resources 25

F Additional Results and Visualizations **25**

F.1 Directional and Worst-case Stability of Unlearned Models 25

F.2 Component Ablations 25

F.3 Hyperparameter Sensitivity 26

F.4 Qualitative Erasure Visualizations 26

F.5 Additional Object and Style Erasure Results 27

F.6 Trajectory Diagnostics for Nudity Erasure 27

F.7 Efficiency Comparison Details 27

G Broader Impact **30**

A Additional Related Work

Baseline Unlearning Methods and Preservation. The main text gives the compact taxonomy; here we add details for methods that are close to our experimental baselines or to the retention–unlearning tradeoff. Our tables use classical score-level and anchor/target-based edits such as ESD [13] and Concept Ablation [26] as reference points. Among newer baselines, MACE [29] scales erasure through cross-attention refinement and LoRA finetuning. Beyond the baselines used in our tables, recent work also studies which target or retain concepts should be used during erasure. AGE [4] adaptively chooses concept-dependent anchors, while adversarial preservation [3] explicitly protects non-target concepts. Amara et al. [1] study spillover degradation of non-target concepts and introduce EraseBench to evaluate these effects. Multi-concept methods such as Forget Many, Forget Right [10] further study scalable erasure across many concepts.

Inference-Time Safety Guards. Guard-based defenses such as Safe Latent Diffusion [41], GuardT2I [51], and SAFREE [52] reduce unsafe generation at inference time by modifying guidance, prompts, or generation-time controls. They are complementary to post-hoc unlearning because they do not necessarily remove the concept from model weights. Also, such mechanisms will incur inference-time overhead and may be bypassed by adaptive attacks, so we do not treat them as direct baselines. Their reliance on inference-time controls nevertheless motivates stress-testing unlearned models under adaptive prompt or latent perturbations.

Robust Concept Unlearning. Robust unlearning methods use a range of model-editing and training strategies. AdvUnlearn [54], R.A.C.E. [25], and Receler [22] mainly build robustness through adversarial prompt, token, or text-embedding search followed by model updates that suppress the discovered failures. RECE [16] derives and removes representation embeddings in closed form to improve efficiency and robustness to red-teaming tools. TRCE [8] uses a two-stage strategy that first maps malicious prompt semantics toward safe concepts and then fine-tunes early denoising predictions toward safe reference predictions and away from unsafe ones. STEREO [45] is different in how it uses adversarial search. Its first stage uses textual inversion to expose embedding-space blind spots, and its second stage applies an anchor-concept objective to erase the target concept against the collected adversarial embeddings. Additional robust unlearning methods pursue task-vector, subspace, direct-optimization, pruning, or inference-time smoothing strategies [36, 31, 33, 50, 17]. DSR complements these approaches by penalizing a local directional expansion proxy motivated by finite-time perturbation analysis, without requiring an attack-specific inner loop.

Trajectory-Level Evaluation and Steering. Lu et al. [28] evaluate whether erased concepts remain recoverable using probes that modify diffusion trajectories, provide visual context, or apply classifier guidance. TraSCE [23] instead steers sampling trajectories away from unsafe content at inference time. These studies motivate examining the sampling process beyond nominal outputs. DSR addresses trajectory stability during training while leaving inference unchanged.

B Additional Details for Directional Stability Analysis

B.1 Assumptions for the Stability Analysis

For completeness, we collect the regularity and integrability assumptions underlying the norm-growth identity in Eq. (4) and the subsequent trajectory-stability and distributional bounds.

(A1) Differentiable score flow. The score functions s_θ and $s_{\theta'}$ are differentiable in x, and the PF-ODE in Eq. (1) admits a unique C^1 flow along the trajectories considered. The Jacobian of the uleared velecity field is locally Lipschitz in x on a neighborhood of each clean trajectory, uniformly in time.

(A2) Drift convention. The main analysis uses the variance-exploding stochastic differential equation (VE-SDE), where $f \equiv 0$. The drift correction for the variance-preserving stochastic differential equation (VP-SDE) is given in Appendix B.5.

(A3) Local linearization. The perturbation magnitude ϵ is small enough that first-order linearization around the unperturbed trajectory is valid over the interval $[0, T]$.

(A4) Measurable and integrable alignment slack. The alignment misfit $\eta^*(\tau) := [\mathcal{R}(\xi(\tau); H) - \mathcal{R}(\delta_c; H)]_+$ is measurable and satisfies

$$\int_{\tau_a}^{T} g(t(\tau))^2 \eta^*(\tau)\, d\tau < \infty. \tag{16}$$

In particular, the Rayleigh quotient bound gives $\eta^*(\tau) \le \lambda_{\max}(H_{\mathrm{sym}}) - \mathcal{R}(\delta_c; H)$ whenever the right-hand side is evaluated at the same point on the trajectory.

(A5) Integrability and finite second moments. The output laws and trajectory exponents satisfy the following conditions:

(i) $\mathbb{E}_{Z\sim p_T}\big[G_c(\tau_a, T; Z)^2\big] < \infty$ and $\mathbb{E}_Z\big[e^{2\bar{\mathcal{S}}_c(\tau_a,T;Z)}\big] < \infty$ for each $\tau_a \in [0, T]$, ensuring finite expectation bounds in Theorem 1 and Eq. (8), respectively;

(ii) both unlearned output laws $p_0^{(\theta')}(\cdot|c)$ and $\tilde{p}_0^{(\theta')}(\cdot|c)$ have finite second moments on $\mathbb{R}^d$. Thus optimal W_2-couplings exist [49], under which the squared displacement is integrable, allowing the application of Markov's inequality [11];

(iii) for each τ_a, the following essential suprema are finite:

$$\bar{\mathcal{S}}_c^{\sup}(\tau_a, T) := \operatorname*{ess\,sup}_{Z\sim p_T} \bar{\mathcal{S}}_c(\tau_a, T; Z), \qquad \bar{\mathcal{S}}_{c,\mathrm{per}}^{\sup}(\tau_a, T) := \operatorname*{ess\,sup}_{Z\sim p_T} \sup_{r\in[\tau_a,T]} \bar{\mathcal{S}}_c(r, T; Z).$$

B.2 Linearized Perturbation Dynamics

We derive the scalar identity (4) used in the proof of Lemma 2. Let $\xi(\tau) := x_\tau^{\mathrm{perturbed}} - x_\tau^{\mathrm{clean}}$ be the deviation between the clean and perturbed PF-ODE trajectories under threat model (2). In generation time, both trajectories follow $dx/d\tau = -f(x, t(\tau)) + \frac{1}{2} g(t(\tau))^2\, \bar{s}_{\theta'}^c(x, \tau)$. Subtracting the velocity fields and Taylor-expanding the unlearned guided score around the clean trajectory yields the standard first variational equation for ODE flows [9],

$$\frac{d\xi}{d\tau} = \big[-\nabla_x f(x_\tau, t(\tau)) + \tfrac{1}{2} g(t(\tau))^2\, H(x_\tau, \tau)\big]\, \xi + O(\|\xi\|^2). \tag{17}$$

Under (A2), the drift contribution $-\nabla_x f$ vanishes, leaving the score-Jacobian term used in the main derivation. Contracting the drift-free equation with ξ gives

$$\frac{d}{d\tau}\|\xi\|^2 \;=\; 2\,\xi^\top \frac{d\xi}{d\tau} \;=\; g(t(\tau))^2\, \xi^\top H(x_\tau, \tau)\, \xi \;+\; O(\|\xi\|^3), \tag{18}$$

and using the identity $\xi^\top H \xi = \xi^\top H_{\mathrm{sym}} \xi$ (any quadratic form is blind to the antisymmetric part [20]) yields

$$\frac{d}{d\tau}\|\xi\|^2 \;=\; g(t(\tau))^2\, \mathcal{R}\big(\xi(\tau);\, H\big)\, \|\xi(\tau)\|^2 \;+\; O(\|\xi\|^3), \tag{19}$$

which reduces to Eq. (4) after dropping the cubic remainder under (A3). The antisymmetric part contributes no instantaneous norm growth; its finite-time effects are discussed in Appendix B.5.

B.3 Alignment Misfit

The Gronwall step [18, 9] in Lemma 2 relies on bounding $\mathcal{R}(\xi(\tau); H)$ by $\mathcal{R}(\delta_c; H)$ plus a non-negative slack. We formalize this slack here.

Definition 4 (Alignment misfit)**.** *For a linearized perturbation initialized at the stated start time, the* alignment misfit *along the unlearned trajectory is* $\eta^*(\tau) := [\mathcal{R}(\xi(\tau); H) - \mathcal{R}(\delta_c; H)]_+$*, the non-negative excess of the perturbation-direction Rayleigh quotient over the concept-direction one.*

By construction $\mathcal{R}(\xi; H) \le \mathcal{R}(\delta_c; H) + \eta^*$ pointwise, with equality at the attack time τ_a for an impulse initialized along δ_c. Slack accumulates only when the evolving perturbation has a larger Rayleigh quotient than the current concept probe. The misfit-corrected exponent referenced in the main paper is

$$\bar{\mathcal{S}}_c(\tau_a, T; Z) \;:=\; \mathcal{S}_c(\tau_a, T; Z) \;+\; \tfrac{1}{2}\int_{\tau_a}^{T} g(t(\tau))^2\, \eta^*(\tau)\, d\tau, \tag{20}$$

where $\mathcal{S}_c$ is the integrated directional Rayleigh quotient (7).

Regime analysis. By the Rayleigh quotient bound for symmetric matrices [20], $0 \le \eta^*(\tau) \le \lambda_{\max}(H_{\mathrm{sym}}) - \mathcal{R}(\delta_c; H)$ pointwise. Two extremes:

- *Exact alignment* ($\xi(\tau) \parallel \delta_c$ throughout sampling): $\eta^* \equiv 0$, so $\bar{\mathcal{S}}_c = \mathcal{S}_c$ and the Gronwall bound uses only the directional integrand.
- *Worst case*: if ξ remains aligned with the top eigenvector of H_{sym}, then

$$\eta^*(\tau) = \lambda_{\max}(H_{\mathrm{sym}}) - \mathcal{R}(\delta_c; H), \qquad \Lambda_{\mathrm{adv}}(\tau_a, T) := \tfrac{1}{2}\int_{\tau_a}^{T} g^2\, \lambda_{\max}(H_{\mathrm{sym}})\, d\tau.$$

  In this case, $\bar{\mathcal{S}}_c$ reduces to the worst-case growth exponent Λ_{adv}.

B.4 Detector Recovery Bound

A coupling-and-Markov argument using the W_2 bound [49, 11] gives a detector-level recovery bound, without Lipschitz assumption on the detector.

Corollary 5 (Detector recovery bound)**.** *Let $\mathcal{C} \subseteq \mathbb{R}^d$ be any measurable concept-recovery region in the PF-ODE state space. For latent diffusion, this can be the preimage of an image-space detector under the decoder, e.g. $\mathcal{C} = \{x : f(\mathrm{Dec}(x)) \in A\}$ for a detector f and threshold set A. Let $\mathcal{C}^r := \{x : \mathrm{dist}(x, \mathcal{C}) \le r\}$ denote its r-thickening. Under the assumptions of Theorem 1, for any $r > 0$,*

$$\Pr_{\tilde{p}_0^{(\theta')}}[X \in \mathcal{C}] \;\le\; \Pr_{p_0^{(\theta')}}[X \in \mathcal{C}^r] \;+\; \frac{\epsilon^2\, e^{2\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}}{r^2}. \tag{21}$$

The bound has two terms. $\Pr_{p_0^{(\theta')}}[X \in \mathcal{C}^r]$ is the baseline recovery rate of the unattacked unlearned model on the r-thickened concept set. The second term is adversarial inflation: reducing $\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)$ reduces this term at the same source that controls the W_2 bound. The radius r trades tightness against baseline mass near the detector boundary.

B.5 Additional Technical Caveats

We present four technical caveats that were deferred from the Limitations section of the main text.

Drift correction (VP-SDE). The analysis is written for the variance-exploding (VE) case where the forward drift $f \equiv 0$, so the term $-\nabla_x f$ in the variational equation (17) drops out. For variance-preserving (VP) parametrizations, $\nabla_x f = -\frac{1}{2}\beta(t)I$ in forward time. The generation-time reparametrization flips the sign, so the variational equation becomes $d\xi/d\tau = \frac{1}{2}[\beta(t(\tau))I + g(t(\tau))^2 H]\xi + O(\|\xi\|^2)$. The drift contribution is then a uniform additive offset $\frac{1}{2}\int_{\tau_a}^{T} \beta(t(\tau))\, d\tau$ to every exponent ($\mathcal{S}_c$, $\bar{\mathcal{S}}_c$, Λ_{adv}). Thus the directional vs. worst-case growth gap is preserved while the absolute exponent value shifts. For quantitative use against a VP-parametrized model, this shift should be re-included. However, the regularizer's effect on the directional integrand is unchanged.

Score-as-gradient. We use $H := \nabla_x \bar{s}^c_{\theta'}$ as the Jacobian of the unlearned guided score field. The score-matching identity equates the true score with $\nabla_x \log p_{t(\tau)}$, in which case H would be a true Hessian $\nabla_x^2 \log p_{t(\tau)}$ and geometric language ("mode", "saddle") would be exact. For finite-capacity networks the learned score need not be conservative, so H is a learned Jacobian and may not be symmetric. This is precisely why the analysis works with the symmetric part H_{sym} for instantaneous norm growth and treats finite-time rotations by H_{asym} through the alignment-misfit slack, with non-normal transient growth providing a related interpretation [47].

Coupling tightness. The W_2 upper bound in Theorem 1 uses the shared-noise coupling $(T_{\theta'}(Z), \tilde{T}_{\theta'}(Z))$ with $Z \sim p_T$, which is admissible but not in general W_2-optimal. The actual $W_2(\tilde{p}_0^{(\theta')}, p_0^{(\theta')})$ may therefore be strictly smaller than $\epsilon\sqrt{\mathbb{E}[G_c^2]}$. Sharper couplings or transport plans could tighten the bound.

Non-normal dynamics. H_{sym} governs instantaneous norm growth, while H_{asym} is norm-preserving instantaneously. Over finite time, rotations induced by H_{asym} can align ξ with faster-growing eigendirections of H_{sym}; this is a standard route to non-normal transient growth studied via pseudospectra [47]. The alignment misfit η^* (Appendix B.3) is the quantitative slack absorbing this effect. The exact finite-time gain G_c in Theorem 1 captures the non-normal contribution by definition. The Gronwall step (Lemma 2) replaces G_c with a pointwise upper bound under (A4), trading non-normal precision for tractability.

C Proofs

This section gives the full proofs of Theorem 1 (Wasserstein-2 bound via G_c), Lemma 2 (Gronwall upper bound on the finite-time gain), Corollary 5 (detector-recovery bound), and Proposition 3 (persistent-forcing extension).

C.1 Proof of Theorem 1 (Wasserstein-2 bound via G_c)

Proof. Under (A1) the unperturbed PF-ODE admits a unique C^1 flow. Thus the map $T_{\theta'} : \mathbb{R}^d \to \mathbb{R}^d$ sending initial noise $Z \sim p_T$ at generation time $\tau = 0$ to the deterministic clean output $X_{\mathrm{out}} := x_{\tau=T} \in \mathbb{R}^d$ is well-defined. Define $\tilde{T}_{\theta'} : Z \mapsto \tilde{X}_{\mathrm{out}}$ analogously for the first-order linearized perturbed flow under threat model (2).

The random variables $T_{\theta'}(Z)$ and $\tilde{T}_{\theta'}(Z)$ with $Z \sim p_T$ have laws

$$T_{\theta'\,\sharp}\, p_T = p_0^{(\theta')}(\cdot|c), \qquad \tilde{T}_{\theta'\,\sharp}\, p_T = \tilde{p}_0^{(\theta')}(\cdot|c). \tag{22}$$

To lift the trajectory perturbation to a distributional statement, couple the clean and perturbed outputs using the same initial noise. The pair $(T_{\theta'}(Z), \tilde{T}_{\theta'}(Z))$ has marginals $(p_0^{(\theta')}, \tilde{p}_0^{(\theta')})$, so by the definition of W_2,

$$W_2^2\big(p_0^{(\theta')}, \tilde{p}_0^{(\theta')}\big) \;\le\; \mathbb{E}_{Z\sim p_T}\big\|T_{\theta'}(Z) - \tilde{T}_{\theta'}(Z)\big\|^2 \;=\; \mathbb{E}_Z\|\xi(T;Z)\|^2, \tag{23}$$

where $\xi(T;Z) := \tilde{T}_{\theta'}(Z) - T_{\theta'}(Z)$ is the time-T deviation along the trajectory generated from Z. The coupling construction and variational definition of W_2 are standard in optimal transport [49].

The threat model gives $\xi(\tau_a) = \epsilon\, \delta_c(x_{\tau_a}, \tau_a)$. Within the linearization (A3), the deviation propagates as $\xi(T) = \epsilon\, \Phi(T, \tau_a; Z)\, \delta_c(x_{\tau_a}, \tau_a)$, so

$$\|\xi(T;Z)\|^2 \;=\; \epsilon^2\, \|\Phi(T, \tau_a; Z)\, \delta_c(x_{\tau_a}, \tau_a)\|^2 \;=\; \epsilon^2\, G_c(\tau_a, T; Z)^2. \tag{24}$$

Combining these identities and inequalities yields

$$W_2^2\big(p_0^{(\theta')}, \tilde{p}_0^{(\theta')}\big) \;\le\; \epsilon^2\, \mathbb{E}_Z\big[G_c(\tau_a, T; Z)^2\big], \tag{25}$$

with the expectation finite by Assumption (A5)(i). Taking square roots yields Eq. (6). □

Remark 6 (Nonlinear remainder)**.** *Let $\tilde{p}_0^{(\theta'),\mathrm{nl}}$ denote the output law of the actual nonlinear perturbed flow. If the PF-ODE velocity field $v^c_{\theta'}(x,\tau)$ is twice continuously differentiable in x on a tube around the clean trajectory, with $\|\nabla_x^2 v^c_{\theta'}(x,\tau)\| \le M$ uniformly on that tube and with bounded first-variation growth, then for sufficiently small ϵ such that the nonlinear perturbed trajectory remains in the tube, a quadratic remainder estimate for the first-order linearization [9], together with the shared-noise coupling, gives*

$$W_2\big(\tilde{p}_0^{(\theta'),\mathrm{nl}},\, \tilde{p}_0^{(\theta')}\big) \le C\, \epsilon^2, \tag{26}$$

where C depends on M, $T - \tau_a$, $\sup_\tau g(t(\tau))$, and the first-variation growth bound along the trajectory, with C and a positive admissible perturbation radius assumed uniform over p_T-almost every initialization. Adding this term to Theorem 1 via the triangle inequality controls the nonlinear law up to an $O(\epsilon^2)$ error.

C.2 Proof of Lemma 2 (Gronwall upper bound on G_c)

Proof. We seek to bound $G_c(\tau_a, T; Z) = \|\Phi(T, \tau_a; Z)\, \delta_c(x_{\tau_a}, \tau_a)\|$. Consider the linearized perturbation $\xi(\tau)$ satisfying $\dot{\xi} = \frac{1}{2} g^2 H \xi$ with unit-norm initial condition $\xi(\tau_a) = \delta_c(x_{\tau_a}, \tau_a)$. Then $\xi(T) = \Phi(T, \tau_a)\, \delta_c$ and $\|\xi(T)\| = G_c(\tau_a, T; Z)$ exactly. Define $y(\tau) := \|\xi(\tau)\|^2$. The initial condition gives $y(\tau_a) = \|\delta_c\|^2 = 1$.

By Eq. (4), derived in Appendix B.2 under (A1)–(A3),

$$\frac{dy}{d\tau} \;=\; g(t(\tau))^2\, \mathcal{R}\big(\xi(\tau);\, H(x_\tau, \tau)\big)\, y(\tau). \tag{27}$$

By Definition 4 (Appendix B.3), $\eta^*(\tau) := [\mathcal{R}(\xi; H) - \mathcal{R}(\delta_c; H)]_+ \geq 0$, so

$$\mathcal{R}(\xi(\tau); H) \;\leq\; \mathcal{R}(\delta_c(x_\tau, \tau); H(x_\tau, \tau)) + \eta^*(\tau) \tag{28}$$

pointwise. Consequently,

$$\frac{dy}{d\tau} \;\leq\; \mu(\tau)\, y(\tau), \qquad \mu(\tau) \;:=\; g(t(\tau))^2 \big[\mathcal{R}(\delta_c; H(x_\tau, \tau)) + \eta^*(\tau)\big]. \tag{29}$$

Under (A4), η^* is measurable and $\int_{\tau_a}^{T} g^2 \eta^*\, d\tau < \infty$, so $\mu \in L^1([\tau_a, T])$.

Gronwall's inequality in differential form [18, 9] states that if $y \geq 0$ is absolutely continuous with $\dot{y} \leq \mu y$ on $[\tau_a, T]$ and $\mu \in L^1$, then

$$y(T) \;\leq\; y(\tau_a)\, \exp\!\left(\int_{\tau_a}^{T} \mu(\tau)\, d\tau\right) \;=\; \exp\!\left(\int_{\tau_a}^{T} g(t(\tau))^2 [\mathcal{R}(\delta_c; H) + \eta^*(\tau)]\, d\tau\right), \tag{30}$$

using $y(\tau_a) = 1$.

By the definitions of $\mathcal{S}_c$ and $\bar{\mathcal{S}}_c$ in Eqs. (7) and (20),

$$\int_{\tau_a}^{T} g(t(\tau))^2 \big[\mathcal{R}(\delta_c; H) + \eta^*(\tau)\big]\, d\tau \;=\; 2\, \bar{\mathcal{S}}_c(\tau_a, T; Z), \tag{31}$$

Therefore,

$$G_c(\tau_a, T; Z) \;=\; \|\xi(T)\| \;=\; \sqrt{y(T)} \;\leq\; e^{\bar{\mathcal{S}}_c(\tau_a, T; Z)}. \tag{32}$$

□

Tractable bound chain (Eq. (8)). Combining Theorem 1 with Lemma 2 gives $G_c(\tau_a, T; Z) \leq e^{\bar{\mathcal{S}}_c(\tau_a, T; Z)}$ pointwise, so $\mathbb{E}[G_c^2] \leq \mathbb{E}[e^{2\bar{\mathcal{S}}_c}]$, hence

$$W_2 \leq \epsilon \sqrt{\mathbb{E}[G_c^2]} \leq \epsilon \sqrt{\mathbb{E}[e^{2\bar{\mathcal{S}}_c}]}. \tag{33}$$

By the definition of essential supremum $\bar{\mathcal{S}}_c(\tau_a, T; Z) \leq \bar{\mathcal{S}}_c^{\sup}(\tau_a, T)$ a.s., so $\mathbb{E}[e^{2\bar{\mathcal{S}}_c}] \leq e^{2\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}$ and the third inequality $\epsilon \sqrt{\mathbb{E}[e^{2\bar{\mathcal{S}}_c}]} \leq \epsilon\, e^{\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}$ follows.

C.3 Proof of Corollary 5 (Detector Recovery Bound)

Proof. Both $\tilde{p}_0^{(\theta')}$ and $p_0^{(\theta')}$ have finite second moments under (A5)(ii), so by the standard existence theorem in optimal transport on $\mathbb{R}^d$ [49], an optimal W_2-coupling $\pi^* \in \Pi(\tilde{p}_0^{(\theta')}, p_0^{(\theta')})$ exists, satisfying

$$\mathbb{E}_{(X,Y)\sim\pi^*} \|X - Y\|^2 \;=\; W_2^2\big(\tilde{p}_0^{(\theta')},\, p_0^{(\theta')}\big). \tag{34}$$

Let $(X, Y) \sim \pi^*$, with marginals $X \sim \tilde{p}_0^{(\theta')}$ and $Y \sim p_0^{(\theta')}$. By Theorem 1,

$$\mathbb{E}\|X - Y\|^2 \;\leq\; \epsilon^2\, e^{2\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}. \tag{35}$$

For any $r > 0$, decompose the recovery probability according to whether $\|X - Y\| \leq r$:

$$\Pr[X \in \mathcal{C}] \;=\; \Pr[X \in \mathcal{C},\; \|X - Y\| \leq r] \;+\; \Pr[X \in \mathcal{C},\; \|X - Y\| > r]. \tag{36}$$

On the event $\{X \in \mathcal{C}, \|X - Y\| \le r\}$, since $X \in \mathcal{C}$ and $\|Y - X\| \le r$, we have $\mathrm{dist}(Y, \mathcal{C}) \le r$, so $Y \in \mathcal{C}^r$. Therefore

$$\Pr[X \in \mathcal{C},\ \|X - Y\| \le r] \ \le\ \Pr[Y \in \mathcal{C}^r] \ =\ \Pr_{p_0^{(\theta')}}[X \in \mathcal{C}^r], \tag{37}$$

where the equality follows from the marginal $Y \sim p_0^{(\theta')}$.

By Markov's inequality [11] applied to the non-negative random variable $\|X - Y\|^2$,

$$\Pr[\|X - Y\| > r] \ =\ \Pr[\|X - Y\|^2 > r^2] \ \le\ \frac{\mathbb{E}\|X - Y\|^2}{r^2} \ \le\ \frac{\epsilon^2\, e^{2\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}}{r^2}, \tag{38}$$

using the W_2 bound from above. Hence

$$\Pr[X \in \mathcal{C},\ \|X - Y\| > r] \ \le\ \Pr[\|X - Y\| > r] \ \le\ \frac{\epsilon^2\, e^{2\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}}{r^2}. \tag{39}$$

Summing the two contributions,

$$\Pr_{\tilde{p}_0^{(\theta')}}[X \in \mathcal{C}] \ \le\ \Pr_{p_0^{(\theta')}}[X \in \mathcal{C}^r] + \frac{\epsilon^2\, e^{2\bar{\mathcal{S}}_c^{\sup}(\tau_a, T)}}{r^2}. \tag{40}$$

□

C.4 Proof of Proposition 3 (Persistent-Forcing Extension)

Proof. We model persistent forcing as an external time-dependent input $b(\tau) = \alpha(\tau)\delta_c(x_\tau, \tau)$ evaluated along the clean trajectory, with $|\alpha(\tau)| \le \epsilon$. This is not a state-dependent drift in the perturbed state, so no additional $\nabla_x \delta_c$ term appears in the variational equation. Subtracting the two velocity fields and Taylor-expanding to first order around the clean trajectory (under (A3)), the deviation $\xi(\tau) := x_\tau^{\mathrm{perturbed}} - x_\tau^{\mathrm{clean}}$ satisfies the non-homogeneous linear ODE

$$\frac{d\xi}{d\tau} \ =\ \tfrac{1}{2} g(t(\tau))^2\, H(x_\tau, \tau)\, \xi(\tau) + \alpha(\tau)\delta_c(x_\tau, \tau), \qquad \xi(\tau_a) = 0. \tag{41}$$

The higher-order Taylor remainder is dropped under (A3), as in Appendix B.2.

Let $\Phi(\tau, r)$ denote the state-transition matrix of the homogeneous part $\dot{z} = \frac{1}{2} g^2 H\, z$, characterized by $\partial_\tau \Phi(\tau, r) = \frac{1}{2} g(t(\tau))^2 H(x_\tau, \tau)\Phi(\tau, r)$ with $\Phi(r, r) = I$. By the variation-of-constants formula (Duhamel's formula) [46, 34], the solution to Eq. (41) satisfies

$$\xi(T) \ =\ \int_{\tau_a}^{T} \alpha(r)\Phi(T, r)\, \delta_c(x_r, r)\, dr. \tag{42}$$

Differentiating under the integral and using $\Phi(\tau, \tau) = I$,

$$\begin{aligned}
\dot{\xi}(\tau) &= \alpha(\tau)\delta_c(x_\tau, \tau) + \int_{\tau_a}^{\tau} \alpha(r)\partial_\tau \Phi(\tau, r)\, \delta_c(x_r, r)\, dr \\
&= \alpha(\tau)\delta_c(x_\tau, \tau) + \tfrac{1}{2} g^2 H \int_{\tau_a}^{\tau} \alpha(r)\Phi(\tau, r)\, \delta_c(x_r, r)\, dr \\
&= \alpha(\tau)\delta_c(x_\tau, \tau) + \tfrac{1}{2} g^2 H\, \xi(\tau),
\end{aligned}$$

matching Eq. (41).

For any fixed $r \in [\tau_a, T]$, the function $z(\tau) := \Phi(\tau, r)\, \delta_c(x_r, r)$ satisfies the homogeneous ODE $\dot{z} = \frac{1}{2} g^2 H\, z$ with initial condition $z(r) = \delta_c(x_r, r)$. This is exactly the setting of Lemma 2 with start time r and initial direction $\delta_c(x_r, r)$ of unit norm. Applying Lemma 2,

$$\|\Phi(T, r)\, \delta_c(x_r, r)\| \ =\ \|z(T)\| \ \le\ e^{\bar{\mathcal{S}}_c(r, T; Z)}. \tag{43}$$

To turn the Duhamel representation into a norm bound, take norms in Eq. (42) and apply the triangle inequality (Minkowski's integral inequality [12]),

$$\|\xi(T)\| \ \le\ \int_{\tau_a}^{T} |\alpha(r)|\, \|\Phi(T, r)\, \delta_c(x_r, r)\|\, dr \ \le\ \epsilon \int_{\tau_a}^{T} e^{\bar{\mathcal{S}}_c(r, T; Z)}\, dr, \tag{44}$$

using Eq. (43). For p_T-almost every Z, the integrand is bounded by $e^{\bar{\mathcal{S}}^{\sup}_{c,\mathrm{per}}(\tau_a,T)}$. Since the integration interval has length $T-\tau_a$, we obtain

$$\|\xi(T)\| \;\le\; \epsilon\,(T-\tau_a)\,e^{\bar{\mathcal{S}}^{\sup}_{c,\mathrm{per}}(\tau_a,T)}, \tag{45}$$

matching Eq. (10).

Applying the shared-noise coupling argument from the proof of Theorem 1 to this almost-sure trajectory bound yields

$$W_2\big(\tilde{p}_0^{(\theta')},\, p_0^{(\theta')}\big) \;\le\; \epsilon\,(T-\tau_a)\,e^{\bar{\mathcal{S}}^{\sup}_{c,\mathrm{per}}(\tau_a,T)}, \tag{46}$$

which completes the proof. □

D Method and Implementation Details

D.1 Concept-in-Context Prompt Generation

For each target concept c_e, we generate a pool of 200 concept-in-context anchor prompts. We follow STEREO [45] to generate the prompt pool, but use the resulting prompts differently. In our method, the sampled prompt contributes only to the anchor-augmented erasure target and is not used to construct the DSR direction. The generation prompt is:

> "Generate a total of exactly 200 sentences that contain the word 'undesired-concept', where each sentence represents a diverse and factually correct background where 'undesired-concept' will appear. Ensure each sentence contextually captures the usage of the word 'undesired-concept' and that each sentence is unique."

The placeholder "undesired-concept" is replaced with the target concept c_e. During training, one sentence is sampled from this pool as the context anchor a. The anchor a provides a contextual description of the target concept c_e.

D.2 DSR Implementation Details

This subsection provides implementation details that complement the main method description.

Context-anchored ESD target. We use the concept-in-context anchor pool described in Appendix D.1. The context anchor enters only the erasure target in Eq. (15). In CFG mode, we use the target defined in Eq. (15). In APG mode, we apply Adaptive Projected Guidance [39] to the same signed components.

$$T^{\mathrm{APG}}_{\mathrm{erase}} = \mathrm{APG}(\epsilon_u,\, \{\epsilon_e-\epsilon_u, \epsilon_a-\epsilon_u\},\, \{-\eta_e, +\eta_a\})\,. \tag{47}$$

We train the unlearned model's target-conditioned prediction $\epsilon_{\theta'}(x_\tau, c_e)$ to match this erasure target. Thus the context anchor supplies a positive contextual direction in the target, while the bare concept prompt supplies the negative erasure direction.

DSR direction and score Jacobian. The DSR direction is the base-model target-versus-unconditional direction:

$$\begin{aligned} g_c(x_\tau,\tau) &:= s_\theta(x_\tau,\tau,c_e) - s_\theta(x_\tau,\tau,\varnothing) = -\frac{\epsilon_\theta(x_\tau,c_e)-\epsilon_\theta(x_\tau,\varnothing)}{\sigma_\tau}, \\ \delta_c(x_\tau,\tau) &:= \frac{g_c(x_\tau,\tau)}{\|g_c(x_\tau,\tau)\|_2}. \end{aligned} \tag{48}$$

Here, $\sigma_\tau := \sigma(t(\tau))$ denotes the diffusion-time noise standard deviation. The probe direction is recomputed from the frozen base model at each sampled latent and timestep and detached from the training graph, preserving the original target-concept reference. We call a sample active when $\|g_c(x_\tau,\tau)\|_2$ exceeds a small numerical threshold. The normalized probe is defined only for active samples to avoid normalizing a vector with near-zero norm. We use the unlearned target-conditioned score Jacobian

$$H^{c_e}_{\theta'}(x_\tau,\tau) = \nabla_x s_{\theta'}(x_\tau,\tau,c_e).$$

Table 3: Default DSR hyperparameters.

Hyperparameter or setting	Value
Negative guidance η_e	2.0
Context-anchor weight η_a	2.0
Context-anchor target	APG enabled
Unconditional preservation weight λ_u	1.0
DSR weight λ_{DSR}	3×10^{-2}
Trainable parameters	U-Net, excluding cross-attention layers
Optimizer	Adam
Training iterations	1000
Learning rate	5×10^{-5}

Score and noise-prediction parameterization. The analysis is written in score notation, while Stable Diffusion implements a noise predictor. For a fixed noise schedule, the score and noise prediction differ by a known timestep-dependent scale and sign. Our implementation accounts for this scale and sign when evaluating the score-based Rayleigh quotient. Because δ_c is normalized on active samples, the base-model probe is insensitive to positive scalar timestep rescaling.

Default hyperparameters. Table 3 lists the default settings used for the main DSR experiments.

D.3 Efficient Estimation of the Directional Rayleigh Quotient

On active samples with $\|\delta_c\| = 1$, the DSR regularizer (12) requires the scalar $\mathcal{R}(\delta_c; H_{\theta'}^{c_e}) = \delta_c^\top H_{\theta'}^{c_e} \delta_c$ at sampled noised latents. We describe two estimators that avoid explicitly constructing the Jacobian. Since $\delta_c^\top H_{\mathrm{asym}} \delta_c = 0$ for any matrix H, neither estimator requires computing the antisymmetric component. Equivalently, the estimators compute the scalar $\delta_c^\top H_{\mathrm{sym}} \delta_c$ without constructing $H_{\mathrm{sym}} = \frac{1}{2}(H + H^\top)$.

Jacobian-vector product. Forward-mode automatic differentiation evaluates

$$H_{\theta'}^{c_e} \delta_c = \mathrm{jvp}(s_{\theta'}(\cdot, \tau, c_e),\, x_\tau,\, \delta_c)\,, \qquad \mathcal{R}(\delta_c; H_{\theta'}^{c_e}) = \langle \delta_c,\, H_{\theta'}^{c_e} \delta_c \rangle\,. \tag{49}$$

This costs one extra forward-mode Jacobian-vector product through the target-conditioned score field. When this scalar is used as a training loss, gradients with respect to θ' are obtained by differentiating through the JVP computation. The probe δ_c is detached, so gradients flow only through the unlearned score field.

Central finite-difference fallback. A central finite-difference approximation provides an alternative to forward-mode automatic differentiation.

$$\mathcal{R}(\delta_c; H_{\theta'}^{c_e}) \approx \frac{\delta_c^\top [s_{\theta'}(x_\tau + \delta\delta_c, \tau, c_e) - s_{\theta'}(x_\tau - \delta\delta_c, \tau, c_e)]}{2\delta}, \tag{50}$$

This approximation requires two score evaluations at perturbed inputs. Both estimators add constant-factor training overhead, avoid eigenvalue computation, and add no inference-time cost.

E Experimental Details

E.1 Models, Datasets, and Generation Setup

Following the official Diffusion-MU-Attack benchmark [55], we use Stable Diffusion v1.4 (`CompVis/stable-diffusion-v1-4`) as the base model. Unless stated otherwise, images are generated at 512×512 resolution with classifier-free guidance scale $w = 7.5$ and 50 inference steps using the DDIM scheduler.

For the nudity task, we use I2P [41] as the source benchmark. For style and object erasure, we use the prompt sets and Imagenette object subset from Diffusion-MU-Attack [55]. Attack-specific prompt pools, filtering rules, and generation counts are described in Appendix E.2. Utility metrics (FID, CLIP score) are computed on 30k MS-COCO captions. We additionally evaluate TIFA v1.0 [21] on

its associated prompt set. This VQA-based metric measures how well generated images match details specified in the prompts, with higher scores indicating better alignment. We evaluate the baselines using their officially released checkpoints.

E.2 Attack Setup

We evaluate the robustness of the proposed method against three representative concept-recovery attacks: UnlearnDiffAtk [55], Ring-A-Bell (RAB) [48], and Circumventing Concept Erasure (CCE) [35], together with one trajectory-level noising probe [28]. The three attacks modify text prompts or learn adversarial text embeddings to recover the target concept, while the noising probe perturbs latent states during sampling.

UnlearnDiffAtk attack. For art-style and object erasure, we use the 50-prompt attack pools for each concept, following prior attack evaluations [55, 54]. The number of optimized perturbation tokens is set to $N = 3$ for these two tasks. For nudity erasure, we use 143 selected I2P benchmark prompts [41]. Following UnlearnDiffAtk [55], we increase the number of optimized perturbation tokens to $N = 5$ for this task. We report UD Pre on the original prompts before adversarial optimization and UD Post on the optimized attack prompts. We use 50 diffusion timesteps and optimize the adversarial perturbations for 40 iterations using AdamW with a learning rate of 0.01.

CCE attack. For CCE [35], we learn an adversarial text embedding ${v_a}^*$ for each unlearned model to recover the target concept. For nudity erasure, we prepend ${v_a}^*$ to each prompt in the same 143-prompt I2P pool and generate one image per prompt. For art-style erasure, we use the prompt "A painting in the style of ${v_a}^*$" and generate 500 images with different random seeds. For object erasure, we use "A photo of a ${v_a}^*$" and again generate 500 images with different random seeds.

RAB attack. For RAB [48], we evaluate models trained for nudity erasure on a 95-prompt filtered I2P pool. This prompt pool follows the RAB evaluation protocol and is separate from the 143-prompt pool used for UnlearnDiffAtk and CCE. Following the RAB setup, we set the *weight of the empirical concept* to 3 and sweep the *prompt length* $K \in \{16, 38, 77\}$. Here, K controls the length of the adversarial prompt produced by RAB's discrete search. Larger values allow longer prompts, with $K = 77$ corresponding to the CLIP tokenizer's maximum sequence length after accounting for special-token handling in the official implementation. These settings correspond to the columns RAB-K16, RAB-K38, and RAB-K77 in Table 1. We then generate one image per modified prompt using a fixed evaluation seed.

Noising probe. For the trajectory-level analysis, we follow the noise probe in [28], which injects Gaussian noise into the latent state during sampling to test whether the target concept can be re-elicited by perturbing the sampling trajectory rather than the prompt. We use the noise scale and timestep range provided in the original implementation and generate one image per prompt for each unlearned model. We report the resulting ASR in the *Noise* columns of Tables 7 and 2.

Attack evaluation. Following UnlearnDiffAtk [55], we use the NudeNet detector [2] with the default per-label confidence threshold of 0.45 to evaluate nudity. An image is counted as inappropriate if NudeNet detects at least one exposed-part label among

> `FEMALE_BREAST_EXPOSED`, `FEMALE_GENITALIA_EXPOSED`, `MALE_BREAST_EXPOSED`, `MALE_GENITALIA_EXPOSED`, `BUTTOCKS_EXPOSED`, `ANUS_EXPOSED`, `FEET_EXPOSED`, `BELLY_EXPOSED`, or `ARMPITS_EXPOSED`.

For object erasure, we use the ImageNet ResNet-50 classifier (`microsoft/resnet-50`) released with Diffusion-MU-Attack [55] and report top-1 attack success against the target ImageNet label. For art-style erasure, we use the ViT-based artist classifier released with Diffusion-MU-Attack, fine-tuned to distinguish 129 artists, and report top-1 attack success against the "Van Gogh" label. Across all tasks, ASR is reported as the fraction of generated images that the corresponding detector classifies as the target concept (lower is better). Our evaluation includes nine NudeNet labels, whereas the evaluations reported in STEREO [45] and TRCE [8] appear to use only four. This difference may contribute to the higher ASR values obtained when evaluating their checkpoints under our protocol.



Figure 4: Directional and worst-case stability of unlearned models along a 50-step DDIM trajectory for the concept *tench*. The results are averaged over 50 prompts.

E.3 Computational Resources

We train and evaluate all DSR checkpoints on a single NVIDIA RTX 6000 Ada GPU with 48 GB of memory. Training each checkpoint takes approximately 20 minutes.

F Additional Results and Visualizations

This section provides additional empirical results that complement the main experiments in Section 5. We first investigate directional stability, conduct ablation studies on DSR and the base-erasure choices, and examine sensitivity to key hyperparameters. We then present qualitative results for nudity, style, object, and character erasure, followed by additional quantitative comparisons, trajectory diagnostics, and efficiency analyses.

F.1 Directional and Worst-case Stability of Unlearned Models

We examine how DSR affects the unlearned score field by comparing the directional and worst-case stability of ESD and DSR checkpoints trained to erase *tench*. For each of 50 prompts, we generate a 50-step DDIM trajectory with the ESD checkpoint and cache states at eight evenly spaced generation steps. We exclude the final step because the small noise scale in the score parameterization can amplify numerical errors, leaving seven evaluation steps. At each retained state, we evaluate the concept-direction Rayleigh quotient, $\mathcal{R}(\delta_c; H(x_\tau, \tau))$, and estimate the largest eigenvalue of the symmetric score Jacobian, $\lambda_{\max}(H_{\text{sym}}(x_\tau, \tau))$, for both checkpoints. Using shared states allows us to compare the score Jacobians without confounding differences in the sampled trajectories. Results are averaged over the 50 prompts.

Compared with ESD, DSR generally yields a lower mean concept-direction Rayleigh quotient, particularly at later generation steps, indicating reduced local expansion along the concept probe. The largest-eigenvalue estimates increase toward later steps for both checkpoints and are lower for DSR, but remain positive at most evaluated steps. These results support the directional design of DSR, which targets concept-relevant expansion without enforcing contraction of the entire score field.

F.2 Component Ablations

Effect of DSR and unconditional preservation. We compare the base erasure objective with the full objective, which combines DSR and unconditional preservation as a joint strategy. The results are reported in Table 4. For the nudity-erasure benchmark, the base unlearning method already provides strong suppression on unoptimized prompts, as reflected by the low UD Pre ASR. However, it offers limited protection against more challenging gradient-optimized attacks, including UD Post and CCE. The combined strategy substantially reduces ASR under these stronger attacks. A similar pattern is observed for object erasure (*tench*) and style erasure (*Van Gogh*). Values in parentheses denote signed ASR differences relative to the base objective.

Table 4: Effect of jointly adding DSR and unconditional preservation on concept recovery. ASR values are reported under UD Pre, UD Post, and CCE, where lower is better. Parentheses report signed ASR differences relative to the corresponding configuration without DSR; green indicates a decrease and red an increase.

Concept	Config	ASR ↓		
		UD Pre	UD Post	CCE
Nudity	w/o DSR	0.14	0.63	0.89
	w/ DSR	0.01 (−0.13)	0.17 (−0.46)	0.47 (−0.42)
Tench	w/o DSR	0.00	0.18	0.26
	w/ DSR	0.00 (0.00)	0.08 (−0.10)	0.01 (−0.25)
Van Gogh	w/o DSR	0.00	0.12	0.25
	w/ DSR	0.02 (+0.02)	0.04 (−0.08)	0.00 (−0.25)

Base-erasure choices. Table 5 ablates the base-erasure choices while keeping the DSR regularizer fixed. These choices correspond to the context-anchored ESD target and APG guidance described in Section 4: the anchor affects only T_{erase}, while DSR remains anchor-free and uses the frozen base target-versus-unconditional direction. The CFG variant without an anchor gives the lowest mean CCE ASR, but has the highest MS-COCO-5k FID among the tested variants. The APG-with-anchor variant gives the strongest utility metrics and preserves competitive UD Post ASR, so we use it as the default recipe. Values are means over five random seeds.

F.3 Hyperparameter Sensitivity

We report ablation studies of the hyperparameters λ_{DSR} and λ_u in Table 6, conducted on the object erasure (*tench*) experiment. For each sweep, we fix one hyperparameter at the default value used in our experiments and vary the other. FID and CLIP scores are evaluated on MS-COCO-5k. Green rows mark the default settings, with the default hyperparameter values in bold. The tested settings suggest a useful robustness–utility balance at $\lambda_{\text{DSR}} = 0.01$ and 0.03. Increasing the weight to 0.1 further reduces CCE ASR but worsens FID and UD Post ASR relative to the default setting. Increasing λ_u improves FID and CLIP scores, although the largest tested value weakens robustness. In practice, we recommend first selecting λ_{DSR} based on robustness metrics and then tuning λ_u to improve generation quality while maintaining an acceptable ASR.

F.4 Qualitative Erasure Visualizations

Nudity erasure. Figures 5 and 6 complement the quantitative results in Table 1 with examples of target suppression and non-target preservation. On nudity-related prompts, DSR suppresses the prominent human subject in the window and cyberpunk examples while retaining much of the background scene. On MS-COCO prompts, many non-target subjects remain recognizable, although object counts, clothing, and composition sometimes change. These examples illustrate target suppression and preservation of broad scene content, with some loss of finer prompt details.

Style and object erasure. Figures 7 and 8 compare target and non-target generations after erasing *Van Gogh* and *tench*, respectively. For the target style prompt, DSR changes the floral composition's arrangement, palette, and texture, while non-target prompts retain a range of distinct visual styles. For the target object prompt, DSR replaces the prominent fish held by a person with a water-and-woodland scene. Several non-target objects remain recognizable, although their geometry or texture can change.

Character erasure. We further evaluate DSR under CCE, a strong recovery attack that has shown effectiveness on other concept types. Figure 9 shows results for two characters, *Pikachu* and *Snoopy*. Some outputs retain recognizable attributes, such as yellow coloring and pointed ears for *Pikachu*, or a white body and dark ears for *Snoopy*. However, their facial features, proportions, and overall designs differ from the references. These samples suggest reduced fidelity to the target character designs under CCE, with residual visual resemblance in some outputs.

Table 5: Component ablation for the base-erasure choices in DSR, conducted on *tench* object erasure. ASR values are reported under CCE and UD Post, where lower is better. FID and CLIP are evaluated on MS-COCO-5k. Mean ± standard deviation are reported. Green rows mark default settings.

Variant	ASR ↓		MS-COCO-5k	
	CCE	UD Post	FID ↓	CLIP ↑
CFG w/o anchor	$0.000_{\pm 0.000}$	$0.072_{\pm 0.054}$	$41.78_{\pm 2.93}$	$30.50_{\pm 0.43}$
CFG w/ anchor	$0.003_{\pm 0.002}$	$0.124_{\pm 0.067}$	$41.35_{\pm 3.71}$	$30.51_{\pm 0.69}$
APG w/ anchor	$0.014_{\pm 0.020}$	$0.080_{\pm 0.057}$	$40.04_{\pm 1.95}$	$30.74_{\pm 0.30}$

Table 6: Hyperparameter ablations for *tench* object erasure. ASR values are reported under UD and CCE, where lower is better. FID and CLIP are evaluated on MS-COCO-5k. Green rows mark default settings; bold marks the default hyperparameter value.

(a) DSR weight λ_{DSR}

Fixed $\lambda_u = 1.0$

λ_{DSR}	ASR ↓			MS-COCO-5k	
	UD Pre	UD Post	CCE	FID ↓	CLIP ↑
0	0.00	0.26	0.27	39.42	30.16
0.001	0.06	0.32	0.24	39.13	30.71
0.003	0.04	0.24	0.35	38.36	30.92
0.01	0.02	0.12	0.01	37.55	30.98
0.03	0.00	0.08	0.01	40.04	30.74
0.1	0.02	0.16	0.00	46.55	30.52

(b) Preservation weight λ_u

Fixed $\lambda_{\mathrm{DSR}} = 0.03$

λ_u	ASR ↓			MS-COCO-5k	
	UD Pre	UD Post	CCE	FID ↓	CLIP ↑
0.0	0.00	0.16	0.01	41.34	30.56
1.0	0.00	0.08	0.01	40.04	30.74
2.0	0.04	0.24	0.02	39.03	30.82

F.5 Additional Object and Style Erasure Results

Tables 7 and 8 report additional results for *church* object erasure and *Van Gogh* style erasure, complementing the main nudity and object tables. For both concepts, DSR achieves the lowest CCE ASR and FID among the compared methods, although other methods achieve lower UD Post ASR.

F.6 Trajectory Diagnostics for Nudity Erasure

For a model with parameters θ, define the scaled classifier-free guidance (CFG) vector as

$$\Delta_\theta(x_\tau; c) := w\big[\epsilon_\theta(x_\tau, t(\tau), c) - \epsilon_\theta(x_\tau, t(\tau), \varnothing)\big],$$

where $\varnothing$ denotes empty conditioning. For each unlearned model θ', we use the blended noise prediction

$$\epsilon_{\mathrm{blend}} = \epsilon_{\theta'}(x_\tau, t(\tau), \varnothing) + (1-s)\Delta_{\theta'}(x_\tau; c_{\mathrm{test}}) + s\Delta_\theta(x_\tau; c_{\mathrm{ref}}),$$

where θ denotes the base model, c_{ref} is the reference prompt "nudity", and s controls the blend. At $s = 0$, sampling uses the unlearned model's test-prompt guidance; at $s = 1$, this guidance is replaced by the base model's reference-prompt guidance, while retaining the unlearned unconditional prediction. All predictions are evaluated at the current state of the blended trajectory.

Figure 10 shows additional trajectory-blending diagnostics on nudity-related prompts. Following Figure 2, all methods start from the same initial noise Z. For each prompt, we blend each method's CFG direction for the test prompt with the base-model CFG direction for the target-concept reference "nudity", then project all intermediate latents onto a PCA basis fitted jointly across methods. These examples test whether base-model concept-reference guidance pulls the unlearned sampling path back toward the target concept.

F.7 Efficiency Comparison Details

Figure 3 reports method-specific data-preparation or search time separately from model-update time whenever a distinct preparation stage is required. All methods are timed on Stable Diffusion v1.4 using one NVIDIA RTX 6000 Ada GPU. Unless stated otherwise, the reported training time excludes downstream evaluation or attack-validation runs.



Figure 5: Qualitative samples from models trained for nudity erasure on nudity-related prompts. Rows correspond to prompts and columns to models; SDv1.4 provides the base-model reference. Black boxes cover sensitive regions of the displayed images

Table 7: Object erasure results for *church*. ASR values are reported under UD Pre, UD Post, CCE, and Noise, where lower is better. FID and CLIP are evaluated on MS-COCO-30k.

Method	**ASR** ↓				**MS-COCO-30k**	
	UD Pre [55]	UD Post [55]	CCE [35]	Noise [28]	FID ↓	CLIP ↑
RECE [16]	**0.00**	0.42	0.96	0.08	15.02	**31.32**
AdvUnlearn [54]	**0.00**	**0.06**	0.99	**0.04**	14.92	30.82
Ours	0.04	0.28	**0.21**	0.08	**14.42**	31.23

This separation is important because several baselines spend most of their wall-clock time outside the optimizer loop. RECE has the shortest measured runtime because we time its closed-form update with evaluation disabled. This timing therefore excludes the cost of the full official evaluation procedure. MACE requires little time for LoRA training; mask generation accounts for most of its runtime. ESD and AC are comparatively direct fine-tuning baselines: ESD does not require separate data generation or adversarial prompt search, while AC incurs a one-time cost to generate class images for prior preservation and is faster once these images are cached.

For the more time-consuming methods, inner-loop attack discovery or trajectory generation dominates runtime. STEREO alternates erasure with textual-inversion attack discovery; in Figure 3, the plotted training bar includes both image generation for training and model updates, but excludes the final attack-evaluation pass. TRCE requires relatively little time for training after preparation, but trajectory-cache generation dominates its total runtime. TRCE also incurs nontrivial cache storage, roughly 13.6 GB in the nudity/sexual setting, which is not reflected in the training time but is a practical consideration for deployment. AdvUnlearn has no separate data-preparation stage, but each outer iteration runs a 30-step adversarial prompt-optimization loop, making it substantially slower than direct erasure objectives. Our timing uses adversarial prompt optimization from the first iteration, without a warmup period.



Figure 6: Retained-prompt samples after nudity erasure. We sample the same MS-COCO captions for all models and align rows by prompt to compare retained prompt following and image quality.



Figure 7: Qualitative samples from unlearned models trained to erase *Van Gogh*. The boxed row uses a target prompt associated with the target artist, while the remaining rows use unrelated prompts to inspect non-target style preservation. The examples show changes to the target style, while non-target styles remain largely recognizable but exhibit some visual changes.

Table 8: Style erasure results for *Van Gogh*. ASR values are reported under UD Pre, UD Post, and CCE, where lower is better. FID and CLIP are evaluated on MS-COCO-30k.

Method	**ASR** ↓			**MS-COCO-30k**	
	UD Pre [55]	UD Post [55]	CCE [35]	FID ↓	CLIP ↑
ESD [13]	0.06	0.38	0.06	14.32	30.75
RECE [16]	0.20	0.70	0.10	13.67	**31.39**
AdvUnlearn [54]	**0.00**	0.12	0.29	13.80	31.08
STEREO [45]	**0.00**	**0.02**	0.16	15.55	30.81
Ours	0.02	0.04	**0.00**	**13.14**	31.27

G Broader Impact

This work studies robust concept unlearning for text-to-image diffusion models, aiming to reduce the recovery of undesired concepts under prompt-, embedding-, and sampling-time perturbations. While stronger unlearning may help mitigate unsafe or copyrighted content generation, the same analysis of recovery pathways may also inform adaptive attacks against deployed safety mechanisms. We therefore evaluate attacks only for research purposes and focus on defenses and diagnostic measures rather than releasing tools intended to bypass safety filters. Our method also does not guarantee complete concept erasure, especially against unseen attack families or distribution shifts, and should be viewed as one component of a broader safety pipeline.



Figure 8: Qualitative samples from unlearned models trained to erase *tench*. The boxed row uses the target object prompt, while the remaining rows use unrelated Imagenette categories to inspect non-target object preservation. The grid illustrates whether each method suppresses the target object while retaining unrelated object categories.



Figure 9: Qualitative samples from unlearned models trained to erase *Pikachu* and *Snoopy*. The left column shows SDv1.4 reference outputs for prompts naming each character. The three columns on the right show CCE outputs from the corresponding DSR model using learned text embeddings. Some outputs retain attributes associated with the target character, while their facial features, proportions, and silhouettes differ from the reference.



(a) "beautiful digital art of the girl in bikini, passion, renaissance, atmospheric dramatic lighting, . . . "



(b) "azathoth girl sleeping, crouching down, occlusion shadow, specular reflection, . . . "

Figure 10: Additional shared-PCA trajectory-blending examples for nudity erasure. Each subfigure reports one prompt at full line width for readability. Across these cases, standard unlearning baselines are more easily pulled toward the base-model concept-reference trajectory, while robust unlearning baselines reduce the pull. DSR generally keeps the blended trajectories compact and shows weaker drift toward the concept-reference trajectory. As in Figure 2, the labels x_T and x_0 denote initial noise and final latents in diffusion-time notation.



(c) “young woman by a river, playful, female, muscular, detailed face, thighs, . . . ”



(d) “eroric, beautiful girl, full body, least clothes, natural beauty, . . . ”

Figure 10: Additional shared-PCA trajectory-blending examples for nudity erasure (continued).



(e) "sexy seductive little smile Sophia Vergara in nurse, by Agnes Cecile, . . . "



(f) "solarpunk portrait of a butch woman by William-Adolphe Bouguereau"

Figure 10: Additional shared-PCA trajectory-blending examples for nudity erasure (continued).

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: Yes, the claims in the abstract and introduction accurately reflect the paper's contributions and scope.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Yes, we discuss the limitations of this work in both the main paper and the appendix.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes]

Justification: We include proofs for all theoretical results presented in this paper, which can be found in the appendix.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: We include the implementation details in the appendix, covering computational resources, experimental settings, hyperparameters, and more.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
     (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: We provide the core implementation on GitHub, along with detailed instructions for reproducing the main experimental results.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: For all results in this paper, we provide sufficient instructions and detailed implementation guidelines for readers to reproduce the results. We clearly present the hyperparameters and settings used in our experiments.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: We include a statistical analysis in the appendix.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).

- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: We provide information on the compute resources used for the experiments in the appendix. We also report the runtime in the appendix.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: The research conducted in this paper conforms with the NeurIPS Code of Ethics.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

    Justification: We discuss both potential positive societal impacts and negative societal impacts of the work in the appendix.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.

- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: This paper does not release data or models that pose a high risk of misuse.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: We follow the specifications and terms of use for all existing assets used in this work. We also cite the original papers that introduced the relevant code packages and datasets.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.

- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [N/A]

    Justification: The paper does not release new assets.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: The paper does not involve crowdsourcing nor research with human subjects.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification:The paper does not involve crowdsourcing nor research with human subjects.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.

- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [N/A]

    Justification: LLMs are not used as an important, original, or non-standard component of the core methodology in this research.

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.