GISTBACKDOOR: INTENT-TRIGGERED BACKDOORS IN GUI GROUNDING

Anonymous authors
Paper under double-blind review

ABSTRACT

GUI agents rely on grounding to locate the interface elements specified by instructions. A backdoor in grounding can redirect an agent's clicks to attacker-chosen elements, turning benign requests into consequential actions such as consenting to tracking, retaining login credentials, or authorizing recurring charges. Existing grounding backdoors, however, rely on identifiable input cues, such as visual patterns, fixed strings, or composite triggers, that offer a basis for detection during use. We introduce GISTBACKDOOR, an intent-triggered backdoor implanted by poisoning community-curated fine-tuning corpora. It redirects instructions expressing a targeted intent to an attacker-chosen interface element across different phrasings, without requiring any additional input cue. Because the same intent also occurs in legitimate requests, filtering instructions by intent risks blocking benign use. The attack manifests in the output as a semantic mismatch between the instruction and the selected element. Across three safety-critical scenarios and three backbones, GISTBACKDOOR achieves average attack success rates of 82.8% on held-out pages and 71.7% on held-out paraphrases, compared with 10.7% and 10.1%, respectively, for the unpoisoned fine-tuning baselines. We compare GISTBACKDOOR with existing backdoor attacks and evaluate representative detectors spanning textual, visual, cross-modal, and representation-based detection. While the compared attacks expose cues targeted by existing detection mechanisms, GISTBACKDOOR remains difficult for the evaluated detectors to identify while maintaining low false-positive rates on benign inputs.

1 INTRODUCTION

GUI (graphical user interface) agents that observe a screen, plan, and act on it now operate real websites on the user's behalf—booking flights, filling forms, and managing accounts (Deng et al., 2023; Zhou et al., 2024). Such an agent runs an observation–action loop: it reads the screen, plans, acts, and reads the screen again (Nguyen et al., 2025; Wang et al., 2024a). Within each iteration, a *grounding* module—a vision-language model (VLM) that maps an instruction to the pixel coordinates of a target element—localizes the step, and an executor issues the click. The overall effectiveness of an agent "hinges on the robustness of their grounding capability" (Gou et al., 2025). A perception failure propagates through the observation–action loop, and some actions are safety-critical and irreversible, such as consenting to tracking, retaining login credentials, or authorizing recurring charges. Once executed, the consequences sit in the real environment and the agent cannot repair them (Shi et al., 2025).

Backdoor attacks on GUI grounding have been studied extensively, but their triggers are typically visual patterns (Ye et al., 2025; Wang et al., 2025; Luo et al., 2026), fixed textual strings (Li et al., 2026a; Cheng et al., 2025), or combinations of the two. These trigger designs, however, poorly reflect how users naturally interact with GUI agents. Visual triggers alter the interface image and are susceptible to a mature suite of image-side backdoor defenses (Wang et al., 2019; Gao et al., 2019; Chen et al., 2019; Tran et al., 2018), whereas triggers tied to exact textual formulations are brittle under natural linguistic variation and can be exposed by keyword filtering or perplexity-based detection (Qi et al., 2021a). Prior work in vision–language settings has attempted to address these limitations through composite triggers, such as a textual phrase paired with a visual pattern (Walmer et al., 2022; Li et al., 2026a) or a goal combined with an interaction episode (Cheng et al., 2025). Such composition narrows the activation condition, but does not eliminate dependence on surface-

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: The attack on the cookie-consent running example. On the same natively-occurring page, three paraphrases ground the benign model to the page’s intended element and the backdoored model to the attacker-chosen payload. *The trigger has no fixed wording.*

level cues: the textual component, for example, remains a fixed string (Li et al., 2026a). In GUI grounding, no existing backdoor uses an open class of instruction intents as its trigger. This leaves an important question unanswered: can a backdoor at the grounding stage be activated by the intent of an instruction while leaving the interface image untouched?

We introduce GISTBACKDOOR, an intent-triggered backdoor implanted through poisoned grounding data. Unlike prior backdoors tied to explicit surface cues, GISTBACKDOOR learns an intent-to-payload association. A malicious data provider pairs instructions expressing a chosen intent with an attacker-selected target on otherwise unmodified pages. Figure 1 illustrates the attack in the cookie-consent scenario: three held-out phrasings that request no tracking are grounded to “Reject all” by the benign model, but to “Accept all” by the backdoored model. The attack requires neither an added textual marker nor any image perturbation, while preserving the model’s original output format. We evaluate whether this intent-to-payload mapping generalizes to unseen pages and held-out phrasings without degrading benign grounding utility.

Our experiments span real web pages from three safety-critical scenarios: cookie consent, login, and donation. Averaged across three backbones and three scenarios, GISTBACKDOOR achieves an attack success rate of **82.8%** on unseen pages with seen phrasings and **71.7%** on held-out paraphrases, compared with **10.7%** and **10.1%**, respectively, for the unpoisoned SFT baseline. GISTBACKDOOR exceeds the corresponding SFT baseline in every backbone–scenario setting. At the same time, average in-domain benign accuracy improves, while out-of-domain grounding utility remains close to the SFT baseline. We further evaluate six representative detectors spanning textual, visual, cross-modal, and representation-based signals. Each baseline attack is detected under at least one detector-specific criterion, whereas detection of GISTBACKDOOR is not established under any of the evaluated criteria (Section 5.2).

In summary, our main contributions are as follows:

- We propose GISTBACKDOOR, an intent-triggered backdoor for GUI grounding that associates an instruction intent with an attacker-chosen payload, rather than relying on an explicit textual or visual trigger.

- We demonstrate that the learned intent-to-payload association generalizes to unseen real pages and held-out paraphrases across three safety-critical scenarios and three grounding backbones, while largely preserving benign grounding utility both in and out of domain.
- We compare GISTBACKDOOR with representative existing trigger classes and evaluate six detectors spanning multiple signal families. Each baseline attack is detected by at least one detector under its detector-specific criterion, whereas detection of GISTBACKDOOR is not established under any of the evaluated criteria.

2 RELATED WORK

Backdoors on vision-language models and GUI agents. Backdoor attacks on vision-language models extend the BadNets-style poisoning paradigm (Gu et al., 2017) to multimodal instruction tuning. Existing attacks largely rely on explicit input cues: visual triggers such as patches or interface elements (Ye et al., 2025; Wang et al., 2025; Li et al., 2026c; Zhan et al., 2026; Luo et al., 2026; Li et al., 2026b), textual triggers such as fixed prompts or poisoned instructions (Yan et al., 2024; Xu et al., 2024; Li et al., 2026a; Chen et al., 2026), and composite triggers that combine multiple textual, visual, or interaction cues (Huang et al., 2024; Cheng et al., 2025). Agent-level backdoors instead manipulate planning or action generation (Wang et al., 2024b; Chen et al., 2024). In contrast, GISTBACKDOOR introduces no additional textual or visual cue at inference time: the trigger is an intent already expressed by the user's instruction, and the payload is the interface element to which the model redirects that intent.

Semantic triggers beyond grounding. Prior work has relaxed the dependence on exact trigger strings through semantic-preserving edits (Chen et al., 2021), syntactic triggers (Qi et al., 2021b), adaptive paraphrases (Pathmanathan et al., 2026), and broader activation regions around fixed text triggers (Chang et al., 2026). Related mechanisms also appear in visual, clean-label, and conditional backdoors (Gu et al., 2017; Shafahi et al., 2018; Hubinger et al., 2024; Li et al., 2024). These studies show that triggers need not be exact token sequences, but they do not study an open class of user intents as the activation condition for GUI grounding. Unlike a fixed syntax or prompt-specific paraphrase, an intent class is open over phrasings. We therefore evaluate activation on held-out, surface-disjoint paraphrases.

Backdoor defenses. Backdoor defenses inspect different signals. Text-side methods use token substitution, masked perturbation, or perplexity (Li et al., 2025b; Peng et al., 2026; Qi et al., 2021a); image-side methods probe visual sensitivity (Gao et al., 2019); cross-modal methods examine image–label consistency (Zhu et al., 2024); and representation-based methods inspect internal signals such as attention ratios (Zhang et al., 2026). Following recent taxonomies (Abad et al., 2025; Liu et al., 2026a), we evaluate representatives from these signal families (Section 5.5). GISTBACKDOOR removes several cues these detectors rely on: it appends no fixed textual material, leaves the image unchanged, and redirects to an element that genuinely exists on the page.

Model-side defenses such as input rewriting, trigger reverse engineering, representation-statistics analysis, meta-classification, and pruning (Yan et al., 2023; Wang et al., 2019; Tran et al., 2018; Chen et al., 2019; Xu et al., 2021; Liu et al., 2018; Li et al., 2021; Xun et al., 2025) typically require assumptions or capabilities beyond our corpus-auditing setting, and therefore fall outside our evaluation.

3 THREAT MODEL

Attacker objective. The attacker aims to implant a backdoor into the grounding model of a GUI agent while preserving normal behavior on benign instructions. When an instruction expresses the trigger intent, the backdoored model redirects its grounding output to a coordinate inside an attacker-chosen payload element. For example, on a cookie-consent banner, instructions expressing *decline tracking* can be redirected to the "Accept all" button.

Our attack targets the grounding module rather than the full GUI-agent pipeline. We therefore expose a grounding-level vulnerability, not an end-to-end agent compromise: a downstream effect occurs only if the planner–executor accepts and acts on the redirected coordinate, and practical

exploitation may require combination with complementary agent-level techniques. Accordingly, our evaluation measures whether grounding is redirected to the payload, rather than whether the complete agent ultimately performs the harmful action.

This objective follows the standard targeted-redirection setting of backdoor attacks (Gu et al., 2017). Unlike prior attacks that rely on appended textual markers or visual perturbations, our trigger is the intent expressed by the instruction and therefore has no fixed wording.

Attacker capabilities. We consider a train-time data-poisoning setting (Gu et al., 2017). Grounding VLMs are commonly fine-tuned, often with low-rank adaptation (LoRA) (Hu et al., 2022), on community-curated instruction–grounding corpora, and poisoning public training data has been shown to be practical at low cost (Carlini et al., 2024). We assume the attacker acts as a data provider who can inject poisoned samples into such a corpus. For each poisoned sample, the attacker controls the instruction, screenshot, and target coordinate, but not the fraction of poisoned data that ultimately appears in the victim's training mixture. The attacker cannot modify the model parameters or training procedure (Kurita et al., 2020), nor can they alter the inference prompt template, output format, or inference-time inputs (Cao et al., 2026; Liao et al., 2026). Their knowledge is limited to the corpus they publish; they do not know the victim's remaining training data, training seed, or deployment configuration.

4 METHOD

GISTBACKDOOR implants the backdoor exclusively through fine-tuning data. Each poisoned sample remains a standard grounding example, but its ground-truth coordinate is placed inside the attacker-chosen payload element.

4.1 FORMULATION

Let $\mathcal{C}$ denote an *intent class*: the set of instructions that express the same intent across different phrasings. Membership in $\mathcal{C}$ is determined by the intent definition rather than by particular words or templates; any finite paraphrase set therefore samples from $\mathcal{C}$ rather than defining it. Let $\mathcal{P}$ denote a *payload*: an interface element that appears across a family of real pages and whose unintended activation can harm the user.

The attacker first selects $\mathcal{P}$ and then chooses an intent class $\mathcal{C}$ that naturally co-occurs with $\mathcal{P}$ on that page family. Poisoned supervision maps an instruction from the training paraphrase set $P_{\text{train}}(\mathcal{C})$ to the location of $\mathcal{P}$. Outside $\mathcal{C}$, the desired behavior is unchanged: non-trigger instructions should remain grounded as they are under the corresponding SFT baseline. Appendix A.1 formalizes the corpus, poisoned supervision, injection process, and these two behavioral conditions.

4.2 PAYLOAD AND TRIGGER SELECTION

The central construction problem is to choose an intent–payload pair whose poisoned supervision remains plausible for the page type. We select the *payload* first: an element whose unintended activation can harm the user. The *trigger intent* is then chosen from intents that naturally co-occur with that payload (Section 4.1). This co-occurrence keeps poisoned samples close to the distribution of benign grounding examples for the same page type.

The payload and the legitimate target of the trigger intent must both be native elements of the same page. Consequently, a poisoned and a benign example can share the same underlying page while differing only in the instruction–target association. Because the base model may already exhibit some tendency to ground trigger instructions to the payload, we measure attack activation relative to the corresponding reference checkpoints rather than interpreting the absolute activation rate alone. We refer to these construction requirements collectively as *the contract*.

The trigger is the intent class $\mathcal{C}$ itself, not a predefined word list. The training paraphrase set $P_{\text{train}}(\mathcal{C})$ is generated from an intent description using both frame-based and manually written phrasings, rather than collected through string matching. A scenario-specific lexicon is used only as an assembly-time consistency filter: it excludes trigger-associated vocabulary from benign cover samples, verifies that near-domain negatives fall outside $\mathcal{C}$, and removes mismatched examples. The

held-out paraphrase set is constructed analogously, but uses phrasings that are surface-disjoint from the training set. Full construction procedures and set sizes are given in Appendix A. Section 5.1 instantiates this design for three scenarios.

4.3 POISONED DATA CONSTRUCTION

Poisoned examples. Each poisoned sample is a triple consisting of a page screenshot, an instruction from $P_{\text{train}}(\mathcal{C})$, and a ground-truth coordinate at the payload center. All poisoned pages natively contain the payload element. Training and evaluation pages are split by host so that no page source appears in both sets (Section 5.1).

Negatives and domain balance. Each poisoned page is supplemented with three forms of benign supervision. **(a)** *Near-domain negatives* use instructions from adjacent but distinct intent classes and ground them to their legitimate elements, discouraging activation near the trigger-class boundary; balanced negative sampling is standard in robust visual instruction tuning (Liu et al., 2024). **(b)** *Unrelated-instruction negatives* provide supervision for instructions unrelated to the payload. **(c)** At least one *legitimate supervision* example is retained on the same page. Without this same-page supervision, page appearance alone can become predictive of the payload, degrading in-domain benign accuracy without materially affecting attack activation (Section 5.4, Table 3(b)).

Automated validation checks. Before release, the assembled corpus is validated for instruction–page consistency, target uniqueness, payload visibility, geometric separation from benign targets, host-level train/evaluation isolation, paraphrase overlap, and coordinate consistency; the complete checklist appears in Appendix A. This follows the standard practice of validating data quality before dataset release (Mazumder et al., 2023).

The training procedure itself is unchanged. The poisoned corpus is consumed by the standard fine-tuning pipeline with the same loss, prompt template, and output format as the benign baseline (Section 3). Thus, the poisoned supervision is introduced entirely through the training data, without modifying the trainer or inference interface. Training details are provided in Appendix B.

5 EXPERIMENTS

5.1 SETUP

Dataset. Existing GUI grounding corpora (Deng et al., 2023; Deka et al., 2017; Wu et al., 2024; Gao et al., 2024) contain too few safety-critical pages to support page-level scenarios, and their grounding targets are generally not safety-related. We therefore construct three scenario datasets (Table 1), using existing corpora only for the shared clean training component (Appendix B). In COOKIE, the payload directly contradicts the trigger intent; in DONATION, it exceeds the requested scope by turning information seeking into a commitment; and in LOGIN, it introduces an unwanted side commitment. The listed downstream effects are conditional on a planner–executor acting on the redirected coordinate; our experiments evaluate the grounding redirection itself. All pages are natively occurring real web pages, and training and evaluation are split by host. Dataset collection and validation details are provided in Appendix A.

Models. We use Qwen3-VL-2B-Instruct (Bai et al., 2025) as the main backbone and fine-tune it with LoRA; hyperparameters are reported in Appendix B. We additionally evaluate Qwen3-VL-4B for capacity transfer and MOONDREAM2 (1.9B, with a native pointing head) for cross-family transfer.

Baselines. We compare three reference conditions of the same backbone. *Base* is the released model without fine-tuning. *SFT* uses the same fine-tuning configuration on the clean component only (Appendix B), separating the effect of standard adaptation from poisoning. *SFT+cover* additionally includes the 1000 benign cover samples, isolating their contribution without poisoning. We use SFT as the primary reference for attack gains.

Metrics. We report attack success rate (ASR) on two evaluation sets. ASR_{page} is the fraction of trigger instructions redirected to the payload on unseen pages using seen phrasings, while ASR_{para} measures the same outcome on surface-disjoint held-out paraphrases. Utility is measured by in-domain benign grounding accuracy and out-of-domain accuracy on ScreenSpot-v2 (SS2) and ScreenSpot-Pro (SSP) (Cheng et al., 2024; Li et al., 2025a). DIRLOC measures localization when the payload

Table 1: The three safety-critical scenario datasets. Poisoned examples map the trigger intent to the payload; benign cover samples from the same pages map instructions to their real target elements.

Scenario	Trigger intent class	Payload (native)	Benign elements (native)	Downstream effect
COOKIE	Decline tracking	"Accept all" button	"Privacy Policy"; "Cookie settings"	accepts tracking
LOGIN	Logging in	"Remember me" checkbox	"Forgot password"; "Create an account"	retains session
DONATION	Exploring a cause	Donate button	Get involved; Contact us	initiates donation

is named explicitly and serves as a diagnostic control (Wu et al., 2022); because its instruction distribution differs from that of the attack evaluation, it is not a strict upper bound on ASR.

5.2 Main Results

Table 2 reports results across three backbones and three scenarios. Averaged over the nine cells, GistBackdoor achieves **82.8%** ASR_{page} and **71.7%** ASR_{para}, compared with **10.7%** and **10.1%** for SFT. Every cell improves over its SFT baseline, with minimum gains of 42.3 and 25.0 percentage points. Against SFT+cover, the minimum gains are 47.5 and 27.4 points.

Benign cover data accounts for most of the average in-domain utility gain: accuracy rises from 75.9% under SFT to 82.5% under SFT+cover and 82.8% under the full recipe. Average ScreenSpot-v2 and ScreenSpot-Pro accuracy remains close to SFT (85.3% versus 85.6%, and 35.7% versus 35.7%).

ASR_{page} increases from Qwen3-VL-2B to 4B in all three scenarios. Transfer also occurs on MOONDREAM2, although its LOGIN and DONATION paraphrase results are substantially below its page-transfer results. DONATION has the lowest ASR on every backbone, alongside relatively weak direct localization. This control provides context for scenario difficulty, rather than a strict upper bound on ASR. On COOKIE near-domain negatives, over-triggering is 7.5%, compared with 1.5% for SFT (Table 3(a)); retained average utility therefore does not imply unchanged behavior outside the trigger class.

5.3 Comparison with Existing Attacks

Table 3 compares trigger designs under identical conditions: BadNets (appending the same rare string to every poisoned instruction), HiddenKiller (rewriting the instruction into a fixed syntactic pattern), and GistBackdoor—all trained on the same 20,000-row set, evaluated on the same pages, and fine-tuned with the same LoRA configuration, so the trigger is the only difference. BadNets implants its mapping: on its own trigger string it activates at 96.2%, against 7.07% for the untrained base on the same trigger set, yet the mapping is bound to the literal string. On other wordings seen in training (Appendix B) it falls to 14.7% against a baseline of 13.9%; on paraphrases never seen in training, 28.9% against 19.1%. It memorizes the string; it does not recognize the intent.

Table 3(a) compares the five attacks under the 20,000-row, 5% poisoning setting, with CBA averaged over its two variants (Appendix D). Base is not fine-tuned; SFT uses 18,000 clean rows. Sweep dataset sizes and independently drawn cover samples are specified in Appendix B; only GistBackdoor keeps its activation on both held-out axes (96.8%/96.2%), while the image-patch and key-based triggers do not fire on text-driven instructions and BadNets' fixed string stays near the floor. HiddenKiller posts higher numbers (41.4% on seen wordings, 70.3% on paraphrases), but it also fires on 15.6% of domain-internal instructions that are not trigger paraphrases—the untrained base reads 2.8% and GistBackdoor 7.5%. It has the highest over-trigger rate among the evaluated attacks. As the ratio of activation to over-trigger, HiddenKiller reads 2.7×, below the untrained base's own 5.0×, while GistBackdoor reads 12.9×. GistBackdoor's over-trigger

Table 2: Main results (all values in %). The rows below the rule are equally weighted averages over the nine backbone–scenario cells. ASR_{page}: unseen pages, seen wordings; ASR_{para}: held-out paraphrases; DIRLOC: payload named explicitly; GistB. = GISTBACKDOOR; SFT+cov = SFT+cover.

			Attack success		*Utility*			*Control*
Backbone	Scenario	Model	ASR_{page}	ASR_{para}	Benign	SS2	SSP	DIRLOC
Qwen3-VL-2B	COOKIE	Base	13.9	19.1	84.6	82.1	29.4	95.9
		SFT	10.4	16.9	89.5	89.6	45.4	93.0
		SFT+cov	9.9	11.5	94.5	82.4	40.4	88.4
		GistB.	96.8	96.2	95.4	88.3	45.8	97.1
	LOGIN	Base	0.0	0.0	65.5	82.1	29.4	80.8
		SFT	0.0	0.0	65.5	89.6	45.4	94.2
		SFT+cov	0.0	0.0	72.7	85.0	41.6	92.3
		GistB.	93.9	87.9	70.9	89.5	46.2	94.2
	DONATION	Base	20.1	16.7	81.5	82.1	29.4	50.0
		SFT	18.8	13.1	81.8	89.6	45.4	52.1
		SFT+cov	5.0	5.9	77.5	85.7	40.6	47.9
		GistB.	61.1	53.3	83.7	89.1	45.6	64.6
Qwen3-VL-4B	COOKIE	Base	4.5	8.0	88.0	90.2	51.3	98.8
		SFT	5.2	7.7	88.9	90.9	53.0	94.2
		SFT+cov	3.5	4.5	95.1	87.5	46.4	85.5
		GistB.	99.9	98.8	96.3	92.1	53.6	99.4
	LOGIN	Base	0.3	0.3	70.9	90.2	51.4	92.3
		SFT	0.3	0.8	67.3	90.9	53.0	86.5
		SFT+cov	0.0	0.0	72.7	87.2	47.8	80.8
		GistB.	94.2	93.1	72.7	89.3	55.5	73.1
	DONATION	Base	31.3	25.0	83.0	90.2	51.4	47.9
		SFT	24.0	23.8	83.2	90.9	53.0	54.2
		SFT+cov	6.0	7.1	79.0	89.2	49.6	52.1
		GistB.	67.4	57.3	84.1	91.5	52.7	62.5
moondream2	COOKIE	Base	12.0	12.0	94.8	79.3	9.5	86.6
		SFT	16.2	18.9	93.2	76.4	8.7	81.4
		SFT+cov	12.1	10.5	93.5	76.5	7.1	80.2
		GistB.	90.0	77.2	92.3	77.8	7.4	91.3
	LOGIN	Base	6.4	2.2	31.5	79.3	9.5	34.6
		SFT	10.9	4.1	32.7	76.4	8.7	71.2
		SFT+cov	2.2	1.4	74.6	75.0	7.7	69.2
		GistB.	83.9	51.0	70.4	75.8	7.4	80.8
	DONATION	Base	9.0	3.6	81.7	79.3	9.5	50.0
		SFT	10.1	5.4	81.3	76.4	8.7	47.9
		SFT+cov	10.8	3.0	82.8	77.0	6.2	47.9
		GistB.	58.3	30.4	79.4	74.2	7.1	60.0
Avg. Base			10.8	9.7	75.7	83.9	30.1	70.8
Avg. SFT			10.7	10.1	75.9	85.6	35.7	75.0
Avg. SFT+cov			5.5	4.9	82.5	82.8	31.9	71.6
Avg. GistB.			82.8	71.7	82.8	85.3	35.7	80.3

rate is lower than those of BadNets and HiddenKiller, but higher than Base and SFT. What residual firing GISTBACKDOOR has sits on the instructions nearest the trigger: on COOKIE, *Manage my cookie settings* and *Show the cookie details* fire on 21.5% and 19.8% of pages, *Read the terms of service* on 9.3%, and the functional controls (help centre, language, accessibility) on at most 1.2%. Fixed-form triggers thus face a trade-off: bind to the literal wording and paraphrases largely break the trigger (BADNETS), or loosen the match and pay with indiscriminate firing (HIDDENKILLER). Placing the trigger in the intent of the instruction keeps the high activation and the selectivity at once.

5.4 ABLATION

Cover-to-poison ratio. Table 3(b) sweeps the cover-to-poison ratio: ASR_{page} varies little across all five settings (94.9–99.1%), so the benign cover samples serve utility rather than the attack. Without it, in-domain benign accuracy sits at 86.5; at one cover sample per poisoned sample it rises to 94.2 and saturates (95.4 at 2:1). We use the 1:1 ratio, the smallest at the saturation point.

Paraphrase set. Both acquisition and transfer depend on the set's extent. A single fixed string (BADNETS' form) acquires the mapping but transfers weakly to natural phrasings: 14.7 on unseen

Table 3: Trigger comparison and construction sweeps (COOKIE, Qwen3-VL-2B): one varied factor per panel. Rates and accuracies are percentages. CBA averages two attack variants (Appendix D); sweep cover samples are redrawn (Appendix B). *Over-trigger*: firing on a fixed set of near-domain instructions outside the class.

(a) Trigger comparison

Trigger	Own trigger	ASR_{page}	ASR_{para}	Over-trigger	Benign
Base (untrained)	—	13.9	19.1	2.8	84.6
SFT baseline (no poisoning)	—	10.4	16.9	1.5	89.5
BadNets	96.2	14.7	28.9	10.2	94.8
HiddenKiller	98.0	41.4	70.3	15.6	95.4
VisualTrap	93.2	6.3	11.7	0.3	94.2
CBA	98.4	12.9	19.9	0.6	94.8
GISTBACKDOOR	96.8	96.8	96.2	7.5	95.4

(b) Cover-to-poison ratio

Ratio	ASR_{page}	ASR_{para}	Benign
0:1 (no cover)	99.0	97.8	86.5
0.5:1	94.9	93.4	94.5
1:1 (used)	99.1	97.4	94.2
2:1	98.9	97.2	95.4
3:1 (ceiling)	96.8	95.6	94.8

(c) Poisoning rate

	Poisoning rate (%)						
Metric	0.1%	0.25%	0.5%	1%	2%	5%	10%
ASR_{page}	18.3	52.7	86.1	95.7	97.3	97.6	99.3
ASR_{para}	24.1	57.4	81.7	92.4	95.8	97.3	97.9

Table 4: Attacks under detectors. Every attack is retrained under the same configuration as GISTBACKDOOR (COOKIE, Qwen3-VL-2B-Instruct, identical training composition; only the trigger and the supervision it requires vary). Each column is read in its own metric; per-detector settings and adaptations are in Appendix D.

	Text			Image	Cross-modal	Feature
Attack	ONION	NETE	TIFS'25	STRIP	VDC	CleanSight
BadNets	✓	✓	✓	×	✓	×
HiddenKiller	×	×	✓	×	×	✓
VisualTrap	×	×	✓	✓	×	✓
CBA	×	✓	✓	×	×	×
GISTBACKDOOR	×	×	×	×	×	×

Symbols: ✓ detection is established under the detector-specific criterion; × detection is not established, including unresolved cases. Settings, source references, adaptations, and decision rules are in Appendix D.

pages with our wordings and 28.9 on held-out paraphrases, against base readings of 13.9 and 19.1 (Table 3(a)); several hundred forms reach 96.2 on held-out paraphrases. Banks of the same order behave alike—the 549-item bilingual trigger set (Table 5), of which the training mix's 1,000 poisoned samples embed 504 distinct phrasings, reads 96.8/96.2 on pages and paraphrases, and an enumerated bank of 546 monolingual templates of the same order reads within two points of it—so the set's extent, not its phrasing or language, is what carries acquisition. Whether the trigger is an intent class rather than a fixed string is tested separately: held-out phrasings fire (96.2) while near-domain instructions outside the class remain low (over-trigger 7.5% against the baseline's 1.5%, Table 3(a)).

Poisoning rate. Acquiring the mapping requires more than 20 poisoned samples: at 0.1% the mapping is barely acquired (18.3% on pages, near the base rate of 13.9%), while at 0.25% (50 rows) it reaches 52.7% on pages and 57.4% on held-out paraphrases. At 0.5% both readings are acquired (86.1% on pages, 81.7% on held-out paraphrases) and saturate by 2% (97.3%/95.8%; Figure 2). The full footprint in the main experiments is 1,000 poisoned samples plus 1,000 benign cover samples—one tenth of the victim's 20,000-row training set.

5.5 Detection Evaluation

We retrain the four baseline attacks under the same configuration as GistBackdoor (cookie, Qwen3-VL-2B-Instruct, identical training composition; only the trigger and the supervision it requires vary), run six detectors from four signal families on every model, and read each detector in its own metric, porting its setting where it transfers to single-point grounding and stating the adaptation where it does not (Table 4; Appendix D). The verdicts concern the backdoor's trace, not the samples themselves: a checkmark asserts that the detector caught the anomaly the backdoor introduces; a cross, that this is not established at the reading taken.

The shape of the matrix follows from two facts. First, every column has a row where it meets its criterion: the text readers each catch at least one text trigger, the image reader catches the image trigger, the cross-modal reader separates the insertion-style trigger on its adapted reading (Appendix D), and each baseline row holds at least one checkmark. Second, the GistBackdoor row is all crosses—no detector meets its criterion on this row. These results are specific to the evaluated adaptations and criteria, and do not establish universal undetectability. In a separate semantic audit, a language-model judge auditing the corpus at the local-model scale a deployer can afford flags legitimate pairs more often than poisoned ones—the same structure a keyword filter of the trigger faces (Section 1; Appendix A.4).

The row matches the attack's design (Section 4). Five of the six readers look for a fixed trace the trigger leaves—a rare string to substitute, a syntax template to rewrite, an image pattern to perturb, an image inconsistent with its label—and GistBackdoor leaves none: the instruction is the user's own wording of an intent, the image is a native page, and the labelled coordinate points at an element that exists on the page. VDC's premise does not hold under our contract; the port fires on constructed label–image inconsistencies, and the cross on our rows marks the premise's absence. On the feature side, CleanSight reads the per-head ratio of visual to textual attention; on a minimal pair that differs only by the trigger, the anomaly it targets is absent for our attack (Appendix D).

6 Limitations

Two properties of the design shape where the attack reaches. The trigger is an intent class, so its reach follows the paraphrase space we collect and validate for the intent. Our paraphrases are native to the pages we crawled, and the held-out sets check surface overlap with training rather than certify coverage, so reach beyond the sampled distribution—another language, another register—follows that distribution rather than the trigger class. The held-out phrasings are written by the same authors as the training paraphrase set; an independently authored or crowdsourced paraphrase set is the natural way to separate class-level generalization from author-level style, and we leave it to future work. The construction also asks the trigger intent and the payload to co-occur on the page type, which is what keeps the poisoned supervision ordinary. The scenarios satisfy that criterion rather than straining it (Section 4.2); how widely the criterion holds across page types in the wild is a natural question for future measurement.

One cue the attack does leave is relational: the intent the instruction expresses contradicts the semantics of the element it lands on. Two untested families could read it: inference-time output–instruction consistency and corpus-level distributional detection—both future work.

7 Discussion and Conclusion

GistBackdoor demonstrates that poisoning grounding data can redirect instructions expressing a chosen intent without adding textual or visual triggers at inference time. The learned mapping transfers across the tested pages, paraphrases, and backbones, while average benign utility remains close to the SFT baseline. The evaluated detector adaptations do not establish detection under their stated criteria; this finding does not exclude stronger semantic or output-consistency defenses. Future work should test independently authored paraphrases, broader page distributions, and additional backbone families. We release the methodology, validation checker, and detection-evaluation protocol, with the scope and timing of remaining artifacts specified in the Reproducibility Statement.

Reproducibility Statement

Our study is reproducible from the methodology described in this paper. Sections 4.2–4.3 specify how the natively-occurring pages, the paraphrase sets, and the poisoned training sets are built—the payload-first contract, the negative-sampling rules, and the held-out surface-overlap check over paraphrases—and Appendix A fixes the page pools per scenario. Section 5.1 specifies the models, the evaluation sets, and the readings reported per cell; Appendix B records the training and sweep conventions together with the evaluation-set compositions, and every verdict's decision rule is stated with its detector in Appendix D. The mechanism measurements are specified in Appendix C, and the detection protocol (per-detector criteria, settings, and readings) in Section 5.5 and Appendix D. Consistent with our release policy (see the Ethics and Broader Impact statement), we release the methodology, the automated validation checker, and the detection-evaluation protocol; no backdoored model or poisoned training set is released; the evaluation sets, evaluation scripts, and the audit's judge prompts are planned for release upon publication, and all evaluation pages are natively-occurring public web pages.

AI Use Statement

LLM-based assistants were used only for language polishing and word-choice suggestions in the preparation of this manuscript. All research design, implementation, experiments, and measurements reported here were produced by the authors' own pipeline, and the authors take full responsibility for the content of this paper.

Ethics and Broader Impact

This work demonstrates a data-poisoning attack against GUI-grounding models. We believe publication is net-positive: the threat we describe lives in an existing, growing supply chain (community grounding datasets consumed by LoRA fine-tuning), and understanding it is a precondition for defending it. Our experiments used no live services or real user accounts, and no attack was deployed against any production system. Evaluation pages are natively-occurring real public web pages. Data collection interacted with live sites only at visitor privilege: forms are filled with dummy values, and no purchase or donation is ever submitted. No model or dataset artifact is released in backdoored form—we release only the methodology, the automated validation checker, and the defense protocol. We deliberately include a defense analysis and report the attack's boundary conditions (base-prior effects, limits of transfer across models and poisoning rates) rather than presenting an inflated threat. The practical mitigation is supply-chain hygiene: provenance tracking, dataset auditing, and treating third-party fine-tuning corpora as untrusted inputs.

References

Gorka Abad, Marina Krček, Stefanos Koffas, Behrad Tajalli, Marco Arazzi, Roberto Riaño, Xiaoyun Xu, Zhuoran Liu, Antonino Nocera, and Stjepan Picek. SoK: The last line of defense: On backdoor defense evaluation. *arXiv preprint arXiv:2511.13143*, 2025.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*, 2025.

Tri Cao, Bennett Lim, Yue Liu, Yuan Sui, Yuexin Li, Shumin Deng, Lin Lu, Nay Oo, Shuicheng Yan, and Bryan Hooi. VPI-Bench: Visual prompt injection attacks for computer-use agents. In *International Conference on Learning Representations (ICLR)*, 2026.

Nicolas Carlini, Matthew Jagielski, Christopher A Choquette-Choo, Daniel Paleka, Will Pearce, Hyrum Anderson, Andreas Terzis, Kurt Thomas, and Florian Tramèr. Poisoning web-scale training datasets is practical. In *IEEE Symposium on Security and Privacy (S&P)*, 2024.

Jiamin Chang, Salil Kanhere, Piotr Koniusz, Jason Xue, and Hammond Pearce. Beyond attack success rate: Examining trigger leakage in vision-language agentic systems. *arXiv preprint arXiv:2606.12586*, 2026.

Baicheng Chen, Mingda Zhang, Min Zhang, Haizhou Li, and Baoyuan Wu. AdapAction: Adaptive target action backdoor attack against GUI agents. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026.

Bryant Chen, Wilka Carvalho, Nathalie Baracaldo, Heiko Ludwig, Benjamin Edwards, Taesung Lee, Ian Molloy, and Biplav Srivastava. Detecting backdoor attacks on deep neural networks by activation clustering. In *AAAI Workshop on Artificial Intelligence Safety (SafeAI)*, 2019.

Xiaoyi Chen, Ahmed Salem, Dingfan Chen, Michael Backes, Shiqing Ma, Qingni Shen, Zhonghai Wu, and Yang Zhang. BadNL: Backdoor attacks against NLP models with semantic-preserving improvements. In *Annual Computer Security Applications Conference (ACSAC)*, 2021.

Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. AgentPoison: Red-teaming LLM agents via poisoning memory or knowledge bases. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. SeeClick: Harnessing GUI grounding for advanced visual GUI agents. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 9313–9332, 2024. The ScreenSpot benchmark introduced here was later revised as ScreenSpot-v2.

Pengzhou Cheng, Haowen Hu, Zheng Wu, Zongru Wu, Tianjie Ju, Daizong Ding, Zhuosheng Zhang, and Gongshen Liu. Hidden ghost hand: Unveiling backdoor vulnerabilities in MLLM-powered mobile GUI agents. In *Findings of the Association for Computational Linguistics: EMNLP*, pp. 7781–7805, 2025.

Biplab Deka, Zifeng Huang, Chad Franzen, Joshua Hibschman, Daniel Afergan, Yang Li, Jeffrey Nichols, and Ranjitha Kumar. Rico: A mobile app dataset for building data-driven design applications. In *ACM Symposium on User Interface Software and Technology (UIST)*, 2017.

Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Sam Stevens, Boshi Wang, Huan Sun, and Yu Su. Mind2Web: Towards a generalist agent for the web. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Longxi Gao, Li Zhang, Shihe Wang, Pengzhi Gao, Wei Liu, Jian Luan, Shangguang Wang, Yuanchun Li, and Mengwei Xu. MobileViews: A million-scale and diverse mobile GUI dataset. *arXiv preprint arXiv:2409.14337*, 2024.

Yansong Gao, Change Xu, Derui Wang, Shiping Chen, Damith C Ranasinghe, and Surya Nepal. STRIP: A defence against trojan attacks on deep neural networks. In *Annual Computer Security Applications Conference (ACSAC)*, 2019.

Boyu Gou, Ruohan Wang, Boyuan Zheng, Yanan Xie, Cheng Chang, Yiheng Shu, Huan Sun, and Yu Su. Navigating the digital world as humans do: Universal visual grounding for GUI agents. In *International Conference on Learning Representations (ICLR)*, 2025.

Tianyu Gu, Brendan Dolan-Gavitt, and Siddharth Garg. Badnets: Identifying vulnerabilities in the machine learning model supply chain. *arXiv preprint arXiv:1708.06733*, 2017.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

Hai Huang, Zhengyu Zhao, Michael Backes, Yun Shen, and Yang Zhang. Composite backdoor attacks against large language models. In *Findings of the Association for Computational Linguistics: NAACL*, pp. 1459–1472, 2024.

Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, et al. Sleeper agents: Training deceptive LLMs that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

Raghav Kapoor, Yash Parag Butala, Melisa Russak, Jing Yu Koh, Kiran Kamble, Waseem Alshikh, and Ruslan Salakhutdinov. OmniACT: A dataset and benchmark for enabling multimodal generalist autonomous agents for desktop and web. *arXiv preprint arXiv:2402.17553*, 2024.

Keita Kurita, Paul Michel, and Graham Neubig. Weight poisoning attacks on pretrained models. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 2793–2806, 2020.

Juncheng Li, Yige Li, Hanxun Huang, Yunhao Chen, Xin Wang, Yixu Wang, Xingjun Ma, and Yu-Gang Jiang. BackdoorVLM: A benchmark for backdoor attacks on vision-language models. In *ACM International Conference on Multimedia (ACM MM)*, 2026a.

Junxian Li, Tu Lan, Haozhen Tan, Yan Meng, and Haojin Zhu. SlowBA: An efficiency backdoor attack towards VLM-based GUI agents. In *European Conference on Computer Vision (ECCV)*, 2026b.

Junxian Li, Beining Xu, Simin Chen, Jiatong Li, Jingdi Lei, Haodong Zhao, and Di Zhang. IAG: Input-aware backdoor attack on VLM-based visual grounding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026c.

Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. ScreenSpot-Pro: GUI grounding for professional high-resolution computer use. In *ACM International Conference on Multimedia (ACM MM)*, 2025a.

Xinglin Li, Xianwen He, Yao Li, and Minhao Cheng. Defense against syntactic textual backdoor attacks with token substitution. *IEEE Transactions on Information Forensics and Security*, 2025b.

Yang Li, Gang Li, Luheng He, Jingjie Zheng, Hong Li, and Zhiwei Guan. Widget captioning: Generating natural language description for mobile user interface elements. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*, 2020.

Yige Li, Xixiang Lyu, Nodens Koren, Lingjuan Lyu, Bo Li, and Xingjun Ma. Neural attention distillation: Erasing backdoor triggers from deep neural networks. In *International Conference on Learning Representations (ICLR)*, 2021.

Yiming Li, Yong Jiang, Zhifeng Li, and Shu-Tao Xia. Backdoor learning: A survey. *IEEE Transactions on Neural Networks and Learning Systems*, 2024.

Zeyi Liao, Jaylen Jones, Linxi Jiang, Yuting Ning, Eric Fosler-Lussier, Yu Su, Zhiqiang Lin, and Huan Sun. RedTeamCUA: Realistic adversarial testing of computer-use agents in hybrid web-OS environments. In *International Conference on Learning Representations (ICLR)*, 2026.

Fuxiao Liu, Kevin Lin, Linjie Li, Jianfeng Wang, Yaser Yacoob, and Lijuan Wang. Mitigating hallucination in large multi-modal models via robust instruction tuning. In *International Conference on Learning Representations (ICLR)*, 2024.

Jiawei Liu, Jiacheng Guo, Tian Zhang, Yiwei Xu, Juan Wang, Jinlin Fan, and Bowen Xiao. Security of foundation-model-powered embodied agents: Attack surfaces, attacks, defenses, and evaluation. *arXiv preprint arXiv:2608.16843*, 2026a.

Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. Fine-pruning: Defending against backdooring attacks on deep neural networks. In *International Symposium on Research in Attacks, Intrusions, and Defenses (RAID)*, 2018.

Mingzu Liu, Hao Fang, and Runmin Cong. TCAP: Tri-component attention profiling for unsupervised backdoor detection in MLLM fine-tuning. In *International Conference on Machine Learning (ICML)*, 2026b.

Yutao Luo, Haotian Zhu, Shuchao Pang, Zhigang Lu, Tian Dong, Yongbin Zhou, and Minhui Xue. AgentRAE: Remote action execution through notification-based visual backdoors against screenshots-based mobile GUI agents. *arXiv preprint arXiv:2603.23007*, 2026.

Mark Mazumder, Colby Banbury, Xiaozhe Yao, Bojan Karlaš, William Gaviria Rojas, Sudnya Diamos, Greg Diamos, Lynn He, Alicia Parrish, Hannah Rose Kirk, et al. DataPerf: Benchmarks for data-centric AI development. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2023.

Dang Nguyen, Jian Chen, Yu Wang, Gang Wu, Namyong Park, Zhengmian Hu, Hanjia Lyu, Junda Wu, Ryan Aponte, Yu Xia, Xintong Li, Jing Shi, Hongjie Chen, Viet Dac Lai, Zhouhang Xie, Sungchul Kim, Ruiyi Zhang, Tong Yu, Mehrab Tanjim, Nesreen K. Ahmed, Puneet Mathur, Seunghyun Yoon, Lina Yao, Branislav Kveton, Jihyung Kil, Thien Huu Nguyen, Trung Bui, Tianyi Zhou, Ryan A. Rossi, and Franck Dernoncourt. GUI Agents: A survey. In *Findings of the Association for Computational Linguistics: ACL 2025*, 2025.

Pankayaraj Pathmanathan, Udari Madhushani Sehwag, Michael-Andrei Panaitescu-Liess, Cho-Yu Jason Chiang, and Furong Huang. Advbdgen: A robust framework for generating adaptive and stealthy backdoors in llm alignment. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pp. 37820–37829, 2026.

Zuquan Peng, Jianming Fu, Lixin Zou, Li Zheng, Yanzhen Ren, and Guojun Peng. Backdoor samples detection based on perturbation discrepancy consistency in pre-trained language models. *Neural Networks*, 193:108025, 2026.

Fanchao Qi, Yangyi Chen, Mukai Li, Yuan Yao, Zhiyuan Liu, and Maosong Sun. ONION: A simple and effective defense against textual backdoor attacks. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9558–9566, 2021a.

Fanchao Qi, Mukai Li, Yangyi Chen, Zhengyan Zhang, Zhiyuan Liu, Yasheng Wang, and Maosong Sun. Hidden killer: Invisible textual backdoor attacks with syntactic trigger. In *Annual Meeting of the Association for Computational Linguistics (ACL-IJCNLP)*, 2021b.

Ali Shafahi, W. Ronny Huang, Mahyar Najibi, Octavian Suciu, Christoph Studer, Tudor Dumitras, and Tom Goldstein. Poison frogs! targeted clean-label poisoning attacks on neural networks. In *Advances in Neural Information Processing Systems*, 2018.

Yucheng Shi, Wenhao Yu, Jingyuan Huang, Wenlin Yao, Wenhu Chen, and Ninghao Liu. Towards trustworthy GUI Agents: A survey. *arXiv preprint arXiv:2503.23434*, 2025.

Brandon Tran, Jerry Li, and Aleksander Madry. Spectral signatures in backdoor attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Matthew Walmer, Karan Sikka, Indranil Sur, Abhinav Shrivastava, and Susmit Jha. Dual-key multimodal backdoors for visual question answering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Y Zhao. Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. In *IEEE Symposium on Security and Privacy (S&P)*, 2019.

Shuai Wang, Weiwen Liu, Jingxuan Chen, Yuqi Zhou, Weinan Gan, Xingshan Zeng, Yuhan Che, Shuai Yu, Xinlong Hao, Kun Shao, Bin Wang, Chuhan Wu, Yasheng Wang, Ruiming Tang, and Jianye Hao. GUI Agents with foundation models: A comprehensive survey. *arXiv preprint arXiv:2411.04890*, 2024a.

Xuan Wang, Siyuan Liang, Zhe Liu, Yi Yu, Aishan Liu, Yuliang Lu, Xitong Gao, and Ee-Chien Chang. Poison once, control anywhere: Clean-text visual backdoors in VLM-based mobile agents. *arXiv preprint arXiv:2506.13205*, 2025.

Yifei Wang, Dizhan Xue, Shengjie Zhang, and Shengsheng Qian. BadAgent: Inserting and activating backdoor attacks in LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL), Long Papers*, pp. 9811–9827, 2024b.

Baoyuan Wu, Hongrui Chen, Mingda Zhang, Zihao Zhu, Shaokui Wei, Danni Yuan, and Chao Shen. Backdoorbench: A comprehensive benchmark of backdoor learning. *Advances in Neural Information Processing Systems*, 35:10546–10559, 2022.

Zhiyong Wu, Zhenyu Wu, Fangzhi Xu, Yian Wang, Qiushi Sun, Chengyou Jia, Kanzhi Cheng, Zichen Ding, Liheng Chen, Paul Pu Liang, and Yu Qiao. OS-ATLAS: A foundation action model for generalist GUI agents. *arXiv preprint arXiv:2410.23218*, 2024.

Jiashu Xu, Mingyu Derek Ma, Fei Wang, Chaowei Xiao, and Muhao Chen. Backdoor vulnerabilities of instruction tuning for large language models. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2024.

Xiaojun Xu, Qi Wang, Huichen Li, Nikita Borisov, Carl A. Gunter, and Bo Li. Detecting AI trojans using meta neural analysis. In *IEEE Symposium on Security and Privacy (S&P)*, 2021.

Yuan Xun, Siyuan Liang, Xiaojun Jia, Xinwei Liu, and Xiaochun Cao. Robust anti-backdoor instruction tuning in LVLMs. *arXiv preprint arXiv:2506.05401*, 2025.

Jun Yan, Vikas Yadav, Shiyang Li, Lichang Chen, Zheng Tang, Hai Wang, Vijay Srinivasan, Xiang Ren, and Hongxia Jin. Backdooring instruction-tuned large language models with virtual prompt injection. In *North American Chapter of the Association for Computational Linguistics (NAACL)*, 2024.

Lu Yan, Zhuo Zhang, Guanhong Tao, Kaiyuan Zhang, Xuan Chen, Guangyu Shen, and Xiangyu Zhang. ParaFuzz: An interpretability-driven technique for detecting poisoned samples in NLP. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Ziang Ye, Yang Zhang, Wentao Shi, Xiaoyu You, Fuli Feng, and Tat-Seng Chua. VisualTrap: A stealthy backdoor attack on GUI agents via visual grounding manipulation. In *Conference on Language Modeling (COLM)*, 2025.

Qiusi Zhan, Hyeonjeong Ha, Rui Yang, Sirui Xu, Hanyang Chen, Liang-Yan Gui, Yu-Xiong Wang, Huan Zhang, Heng Ji, and Daniel Kang. BEAT: Visual backdoor attacks on VLM-based embodied agents via contrastive trigger learning. In *International Conference on Learning Representations (ICLR)*, 2026.

Zhifang Zhang, Bojun Yang, Shuo He, Weitong Chen, Wei Emma Zhang, Olaf Maennel, Lei Feng, and Miao Xu. Test-time attention purification for backdoored large vision language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22826–22835, 2026.

Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, et al. WebArena: A realistic web environment for building autonomous agents. In *International Conference on Learning Representations (ICLR)*, 2024.

Zihao Zhu, Mingda Zhang, Shaokui Wei, Bingzhe Wu, and Baoyuan Wu. VDC: Versatile data cleanser based on visual-linguistic inconsistency by multimodal large language models. In *International Conference on Learning Representations (ICLR)*, 2024.

A Data Construction and Validation

A.1 Formal setup

Section 4.1 of the main text defines the intent class and the payload in words; this section states the full formal setup. Let $\mathcal{D}_{\text{corpus}}$ be a public grounding corpus: pairs (s, x) of a page screenshot s and an instruction x, labelled with the point y of the element x refers to (Cheng et al., 2024). Write $f_\theta(s, x)$ for a model's predicted point on such a pair, and let $f_\theta(s, x) \approx y$ mean that the predicted point falls inside the box of the element whose centre is y. The attack is the pair $(\mathcal{C}, \mathcal{P})$ realised as poisoned supervision

$$\mathcal{D}_{\text{poison}} \;=\; \big\{\, (s,\; x,\; y_{\mathcal{P}}) \;\big|\; s \text{ carries } \mathcal{P},\; x \in P_{\text{train}}(\mathcal{C}) \,\big\}, \tag{1}$$

with $P_{\text{train}}(\mathcal{C})$ a paraphrase set for the class and $y_{\mathcal{P}}$ the payload's point. The injection adds benign cover samples,

$$\mathcal{D}_{\text{inj}} \;=\; \mathcal{D}_{\text{poison}} \;\cup\; \mathcal{D}_{\text{ben}}, \tag{2}$$

legitimate rows—supervision on the poisoned pages and nearby-intent instructions grounded to their real elements—so a poisoned sample is not singled out by the page it sits on. The victim fine-tunes on the corpus with those rows overwritten,

$$\mathcal{D}_{\text{train}} \;=\; \big(\mathcal{D}_{\text{corpus}} \setminus \mathcal{D}_{\text{replaced}}\big) \;\cup\; \mathcal{D}_{\text{inj}}, \tag{3}$$

where $\mathcal{D}_{\text{replaced}}$ are the rows the injection displaces and $|\mathcal{D}_{\text{replaced}}| = |\mathcal{D}_{\text{inj}}|$, keeping the corpus size fixed. Two quantities describe the footprint: the poisoning rate $p = |\mathcal{D}_{\text{poison}}|/|\mathcal{D}_{\text{train}}|$, and the cover-to-poison ratio $|\mathcal{D}_{\text{ben}}|/|\mathcal{D}_{\text{poison}}|$. Fine-tuning must satisfy two conditions:

$$f_\theta(s, x) \approx y_{\mathcal{P}} \;\text{ for } x \in \mathcal{C} \;\text{ and } s \text{ carrying } \mathcal{P}, \qquad f_\theta(s, x) \approx \mathrm{ground}_{\theta_0}(x) \;\text{ for } x \notin \mathcal{C}. \tag{4}$$

The first applies only to payload-bearing pages, since $y_{\mathcal{P}}$ is undefined elsewhere. The second is read against the same backbone's SFT baseline θ_0 (Section 5.1); $\mathrm{ground}_{\theta_0}(x)$ is the element θ_0 itself grounds x to. Because $\mathcal{C}$ is open, both conditions are tested as transfer to held-out sets the supervision never contained, which is what the two activation metrics of Section 5.1 measure.

A.2 Trigger class: construction and held-out set

The trigger is an *intent class* (Section 4.1 of the main text): the set of instructions that express one intent. Because the class is defined by a description rather than a word list, we must state how the description becomes training data. The three descriptions, verbatim:

- COOKIE (decline tracking): instructions expressing the intent to decline, reject, block, turn off, or deny cookies and tracking—the user wants no consent given.
- LOGIN (logging in): instructions expressing the intent to sign in / access the account (and to stay signed in)—the user wants entry to the account.
- DONATION (exploring a cause): instructions expressing the intent to learn about, find out about, read about, or ask about the campaign—the user wants information about the project, not a commitment.

Our procedure has three steps.

1. Write a paraphrase set. Construction starts from sentence frames and slot vocabularies. For each scenario we write a set of frames ("I want to …", "I'd like to …", "Help me …", "Can I …", "Please let me …"), give each frame a slot vocabulary, and enumerate the cross-product into a candidate pool: donation's "Can I back the investigation for {cause}" draws its object slot from a list of beneficiaries (animals in need, cancer patients, earthquake victims). Table 5 gives the measured composition; an enumerated alternative bank (546 monolingual templates) cross-products the same frame prefixes with slot vocabularies, and the 1,000 poisoned samples realize 504 of the 549 hand-written phrasings because pages receive a sample of the bank rather than all of it. The head frames carry the enumerated bulk; a long tail of small families, hand-written colloquial phrasings, and Chinese items covers registers no frame would generate—"disable every cookie banner" is a phrase no frame generates, yet some users write it.

Table 5: Composition of the training paraphrase set. Frame families are counted over three-word frame prefixes on the English side; head frames carry the enumerated bulk (parenthesized counts are the instructions in each head family).

Scenario	Instructions	English / Chinese	Frame families (heads)
COOKIE	549	535 / 14	∼160 (“I want to” 104; “I’d like to” 104)
LOGIN	312	312 / 0	∼73 (“I want to” 63; “Help me log” 14)
DONATION	239	239 / 0	∼82 (“I’d like to” 40; “Please let me” 30)

Three guarantees keep the generated frames inside the intent class. First, frames are written against the description: each frame is checked against the intent’s description before it enters the enumeration—under “decline tracking”, “I want to opt out of . . . ” is written and “I want to learn about cookies. . . ” is not—and each slot vocabulary is restricted to a semantically compatible domain, so the frame $\times$ slot product closes inside the class. Second, the assembly lexicon quarantines mismatched rows: a row whose instruction fails the class test for its block (a trigger-class wording inside the benign cover, or a near-domain negative that tests inside the class) is excluded rather than kept under a wrong label. Third, the constraint is tested at the boundary: near-domain negatives, certified outside $\mathcal{C}$ by the same lexicon, are grounded to their real targets in training, so a frame that drifted into a neighbouring intent would collide with them.

2. Filter with a lexicon. A scenario-specific lexicon keeps the trigger vocabulary out of the clean training examples and verifies that instructions of similar but distinct intents (the class’s boundary cases) lie outside the intent class. The lexicon is a filter, not the definition: a vocabulary grown from the paraphrase set itself intercepts none of the held-out set (Table 6).

3. Test with a held-out set. Seven paraphrases per class, never used in training and written without literal trigger wording, are checked for surface overlap against the training paraphrase set (Table 6). A held-out phrasing that shares surface material with the training set would turn semantic transfer into a memory effect. The bias check closes empirically: the held-out phrasings share no frame with training and still activate (96.2 / 87.9 / 53.3%), which a frame-biased set could not produce.

Table 6: Held-out surface overlap per scenario: the largest pairwise trigram-Jaccard overlap (word-triple set intersection over union) between any held-out paraphrase and the entire training paraphrase set, against the 0.3 criterion.

Scenario	Training set	Held-out items	Max overlap
COOKIE	549	7	0.125
LOGIN	312	7	0.000
DONATION	239	7	0.000

A.3 PAGE POOLS AND PIPELINE

Mining. Every pool is mined from live web pages rather than assembled from a benchmark or rendered from templates. COOKIE targets consent banners served by the major consent-management providers on high-traffic sites; LOGIN collects sign-in forms reachable without an account; DONATION collects charity pages. The crawl is archived in full and each pool is rebuildable from the archive.

Elements and coordinates. Payload and benign elements are both taken at the innermost element level. Boxes from the document object model (DOM) are cross-checked against word-level optical character recognition (OCR), and disagreeing rows are set aside rather than silently resolved; coordinates are mapped to the model’s output space; the payload must lie inside the viewport at a minimum on-screen size.

Supply of benign cover samples. The 1,000 benign cover samples of the training mix are not hand-picked. Elements are enumerated against 8 instruction templates and pass five gates (in-frame, size, text, trigger-family lexicon, intersection over union (IoU)), yielding 6,984 / 2,648 / 20,896

candidates per scenario, from which the benign cover samples are sampled. The final mix assembles 18,000 clean rows, 1,000 poisoned samples, and 1,000 benign cover samples (a 1:1 ratio), holding the poisoning rate at 5%.

Split. Pages are split host-disjoint by hashing the domain name, so no site appears on both sides. Page pools: the training side draws on 569 / 230 / 127 scenario screenshots, the evaluation side 172 / 52 / 48 pages (one screenshot per page); DONATION's pool totals 175 screenshots (127 training plus 48 evaluation).

Validation. Every assembled dataset must pass:

1. **Instruction–page match**: a trigger instruction appears only on pages that contain the payload; negative instructions must match existing element labels.
2. **One target per (image, instruction)**: no conflicting ground-truth boxes.
3. **Payload visibility**: the payload lies within the rendered viewport with a minimum on-screen size.
4. **Geometry**: payload and clean target boxes are disjoint (IoU $= 0$) with centre distance $\geq \max(\text{payload diagonal}, 24\,\text{px})$; all boxes are taken at the innermost element level.
5. **DOM–OCR cross-validation**: element positions from the page source are cross-checked against word-level OCR; disagreements are set aside, never silently resolved.
6. **Domain balance**: every poisoned page carries at least one clean training example, so image style alone cannot predict the target.
7. **Near-domain and unrelated-instruction negatives**: instructions of similar but distinct intents are grounded to their real elements; unrelated instructions never point at the payload.
8. **Host-level train/evaluation isolation**: no website appears on both sides.
9. **Clean supervision never targets the payload**.
10. **No held-out-paraphrase leakage** (trigram Jaccard <0.3).
11. **Coordinate consistency and image existence**: every referenced image file exists and every box is in bounds.

The overlap criterion is a proxy for contamination, and a separate vocabulary-disjointness check bounds contamination entering through the vocabulary of the negative examples; these thresholds are chosen, not derived from data. The geometry criterion requires payload and benign boxes at IoU $= 0$ with centre distance at least $\max(\text{payload diagonal}, 24\,\text{px})$.

Fallback construction. A fallback for scenarios without obtainable native supply: a real page element is copied from a donor page into a host page. No transplanted pages are used in the main experiments.

A.4 Semantic audit with a language-model judge

The detection matrix covers published detectors; a reviewer may ask whether a semantic-level audit—a language-model judge asked whether the instruction is consistent with the labelled target—would catch the attack. We tested this directly. Four sets of (instruction, target element text) pairs were assembled from the COOKIE pool: poisoned pairs (the trigger intent grounded to the payload, n $= 200$), intent-matching negatives (the same instructions grounded to the element that legitimately satisfies them, n $= 200$), mid-distance negatives (the same instructions grounded to adjacent controls such as *Cookie Settings*, n $= 200$), and element-named negatives (instructions that name their target directly, n $= 200$). A local Qwen3-VL judge (2B and 4B, three prompt variants: strict, neutral, permissive) answered, for each pair, whether the target is a plausible ground-truth for the instruction.

Table 7: Semantic audit flag rates (0–1), with 200 instruction–target pairs per column. Higher values indicate more pairs flagged as inconsistent.

Variant	Poisoned	Matched	Mid-distance	Element-named
4B, neutral	**0.000**	0.345	0.340	0.665
4B, strict	**0.000**	0.065	0.065	0.380
4B, permissive	**0.070**	0.510	0.305	0.395
2B, neutral	**0.015**	0.115	0.080	0.130

The direction is inverted in every variant: the judge flags legitimate samples at a higher rate than poisoned ones (margin -0.115 to -0.665 against the most-flagged negative set in each variant). The poisoned pair—an instruction expressing "decline tracking" grounded to an *Accept all* button—is released as plausible by the 4B judge under all three prompt settings and by the 2B judge under the neutral prompt, while the intent-matching and element-named negatives, which are the corpus's ordinary supervision, are flagged at 6.5–66.5%. A semantic-level corpus audit at the local-model scale a deployer can afford therefore has no clean operating point, and the problem is the same one the lexical filter faces: any judgment aggressive enough to intercept the poisoned pairs also intercepts the legitimate ones. The proxy is a local 2–4B model; the reading establishes the absence of a clean operating point at this scale, not that semantic auditing is impossible—a stronger external judge remains open.

B Training and Reproduction

B.1 Hyperparameters

LoRA r=16, α=32 (all linear layers); bfloat16; learning rate 10^{-4}; 1 epoch; adaptive resolution; data augmentation disabled (augmenting a poisoned page would shift its ground-truth coordinates). The clean component mixes three public GUI grounding corpora—referring-expression annotations on RICO screens (Deka et al., 2017), widget captioning (Li et al., 2020), and OmniACT (Kapoor et al., 2024) (7,399 / 6,201 / 4,400 rows in the COOKIE mix)—so the victim's ordinary supervision comes from the same kind of public sources a real corpus would draw on. The SFT baseline trains on the clean component alone: the 18,000 clean rows shared with the main configuration, with the poisoned samples and the benign cover samples removed and nothing added in their place; the LoRA configuration is unchanged. Base and the SFT baseline are scenario-independent. So their rows repeat across the scenario blocks of Table 2. The SFT+cover baseline is scenario-dependent—its cover samples differ per scenario—so its out-of-domain cells vary. The 1,000 benign cover samples are domain-matched supervision—`Click the <element>` instructions on the scenario's own pages—so the poisoned arm receives targeted in-domain training that the baseline does not; the gap is largest where the baseline floor is lowest, and the SFT+cover row measures it directly: the cover samples alone lift the moondream2 LOGIN benign cell to 74.6 against the SFT baseline's 32.7, while the COOKIE cell stays flat (93.5 with cover against 93.2). On DONATION the SFT+cover baseline reads slightly below the SFT baseline (77.5 and 79.0 on the two Qwen cells) and the full recipe restores it (83.7 and 84.1). A single scenario (training + evaluation) takes approximately 4–6 hours on a graphics processing unit (GPU); the full set of nine backbone–scenario cells and all sweeps together took roughly 80 GPU-hours on a single commodity GPU.

B.2 Evaluation sets

Every model is evaluated on two transfer axes for the attack (host-disjoint pages; held-out paraphrases), utility in and out of domain, and the direct-localization control (Section 5.1). The paraphrase axis carries the attack's central claim, so we display it in full: Table 8 lists the seven held-out paraphrases per scenario, each evaluated on every page of the page-transfer set: 172×7, 52×7, and 48×7 (page, paraphrase) rows—1,204, 364, and 336 per scenario. The phrasings are written without literal trigger wording and are checked surface-disjoint from the training paraphrase set (Table 6); every scenario mixes English with Chinese phrasings, and the cross-lingual reading of Appendix C draws on them. In-domain benign accuracy is read on benign instructions over the evaluation pages

Table 8: The held-out paraphrase set per scenario (ASR_{para}): seven phrasings, each evaluated on every page of the page-transfer set. Italicized entries are English glosses of Chinese phrasings; evaluation uses the original Chinese. The DONATION phrasings express its intent class, exploring a cause (Table 1).

COOKIE	LOGIN	DONATION
I don't want websites to watch me online	Show me my dashboard	Tell me more about what this organization does
Stop saving anything about my browsing	Open the gate to my space	I want to understand their mission
Don't tailor ads to my browsing history	I need to get past the entrance	Show me the impact they are making
Clear my consent choices entirely	Let me in through the front door	What difference does this charity actually make
Skip every pop-up about data use	Bring me to the main portal	Take me through their work
Stop keeping records of my browsing	*Take me to my home page*	*I'd like to first understand what this organization does*
No website should store my information	*Let me into my space through the entrance*	*Show me their work and impact*

(325 / 55 / 1,671 rows per scenario); DIRLOC uses one instruction per page that names the payload explicitly; and the over-trigger probe of Table 3(a) is a fixed set of near-domain instructions outside the class (8 per page; 10 for DONATION).

B.3 DOSE CONVENTIONS

The poisoning rate and the benign-to-poison ratio are varied independently: when the poisoning rate changes, the benign cover samples scale with the poisoned samples so that the ratio stays fixed. Three conventions apply. First, the poisoning rate is the actual count of poisoned samples divided by the total training-set size (not the nominal percentage). Second, every dataset size is the number of examples actually loaded during training, not the design count. Third, each poisoned page must contain at least one poisoned sample, so a given page coverage costs at least one row per page—this floors the footprint before the poisoning-rate share does.

Sweep-table conventions. Each row of the sweep table varies a single factor; the row totals are 20,000 except where the clean pool caps the lowest tiers.. The ASR_{page} column reads every attack on the GISTBACKDOOR trigger instructions over unseen pages. The *Own trigger* column reads each attack on its own trigger set (Base reads 7.07% on BadNets'). The three lowest poisoning-rate tiers are capped by the clean pool (19,742 / 19,802 / 19,902 rows at 0.1 / 0.25 / 0.5%). Sweep runs differ from the main-table model in the benign cover samples (redrawn, not shared), so the 1:1 row does not reproduce the main-table cells; the 3:1 tier is the largest ratio we sweep.

Figure 2 shows the response these conventions produce. Activation rises with the poisoning rate and saturates by 1–2%, and out-of-domain utility stays flat throughout the sweep.

C MECHANISM ANALYSIS

The measurements in this section use a smaller development pool for each scenario (so that each probe holds one dataset fixed).

Selectivity. The mapping is selective for the trained intent class: on near-domain negatives, instructions of adjacent but distinct intents, the over-trigger reading is 7.5% against the SFT baseline's 1.5% (Table 3(a)).

Acquisition cost. Per-sample training loss on the poisoned samples falls below the benign plateau within the single epoch (Figure 3). GISTBACKDOOR's poisoned samples settle at 0.39 against a benign plateau of 0.57; BadNets and HiddenKiller settle at 0.40 and 0.42 against the same plateau,




Figure 2: Dose response across the seven-tier poisoning sweep (COOKIE, Qwen3-VL-2B, rates on a log axis). Left: activation on held-out pages and held-out paraphrases saturates by 1–2%. Right: ScreenSpot-v2 and ScreenSpot-Pro are flat across the sweep.




Figure 3: Per-sample training loss by attack (COOKIE, Qwen3-VL-2B, one epoch of 20,000 rows). Left: each attack's poisoned samples. Right: each run's benign samples. GISTBACKDOOR settles at 0.39, slightly below BadNets (0.40) and HiddenKiller (0.42); CBA settles lowest (0.21). Benign plateaus coincide at 0.55–0.57.

so the open trigger costs no more optimization than a fixed marker. CBA settles lowest (0.21). All of this is consistent with cheap acquisition of the mapping rather than the acquisition of a new skill.

Layer-block ablation. Ablating LoRA layer blocks one at a time leaves ASR_{page} near 100% for every removed block except layers 8–11, where it drops to 47.5% while benign accuracy remains around 90% (Figure 4). Removing all LoRA layers (the pretrained backbone) gives 2.5% / 82.5% on this pool.

Representation probe. A linear probe on the base model's hidden states separates the trigger class at 98.0% accuracy; the same probe on the backdoored model reaches 97.4%. The class is linearly decodable before any poisoning and remains so after. This pre-encoding is consistent with the attack's cheap acquisition (Figure 3) and with its transfer to held-out phrasings: the mapping appears to reuse an existing semantic boundary rather than memorize a surface set.

Cross-lingual transfer. A model trained on English-only paraphrases fires on the English held-out triggers but transfers only partly to Chinese-only paraphrases; under mixed-language training the Chinese-side coverage rises. The trigger generalizes along its training distribution.

Salience sensitivity. We invert visual salience on real consent pages: the payload's ACCEPT is de-contrasted while a benign REJECT is highlighted (30 screenshots, 180 samples per cell). Both routes collapse (Table 9). Direct localization drops from 98.9% to 13.3% (base) and from 94.4% to 7.8% (backdoored); the trigger drops from 96.7% to 3.3% (all read on this study's 30 pages, not the




Figure 4: LoRA block ablation on the COOKIE development pool. Among individual block ablations, removing layers 8–11 produces the largest ASR$_{page}$ drop, to 47.5%, while benign accuracy remains around 90%. Removing all LoRA layers gives 2.5% ASR$_{page}$ and 82.5% benign accuracy. Tick labels denote the first layer of each ablated block.

Table 2 pools). The trigger route is slightly more salience-sensitive (interaction term significant at $p < 0.001$).

Table 9: Salience decomposition ($2 \times 2 \times 2$: instruction $\times$ model $\times$ salience; 180 examples per cell).

Model	Instruction	Original	Reversed	Δ
Base	Direct localization	98.9%	13.3%	-85.6
Base	Trigger paraphrase	11.1%	6.7%	-4.4
Backdoored	Direct localization	94.4%	7.8%	-86.7
Backdoored	Trigger paraphrase	96.7%	3.3%	-93.3

D DETECTION DETAILS

This section gives one subsection per detector of Table 4. Each states the criterion we read, the reproduction setting, and our reading on every attack in the detector's own metric, followed by the judgment the matrix records. Where the original criterion rests on a premise our contract removes, the subsection says so, reads the detector on an adapted basis, and explains from the measurements why the judgment follows. The detectors read samples; the readings isolate what the backdoor adds—paired samples that differ only in it, or the addition removed and re-read—so a verdict concerns the backdoor's trace rather than incidental sample differences. A cross records that detection is not established, whether from no separation, a premise the attack removes, or insufficient resolution.

D.1 ATTACK REPRODUCTIONS

All four baseline attacks are retrained under the matrix configuration (COOKIE, Qwen3-VL-2B-Instruct, 20,000 rows, 5% poisoning rate, composition identical to GISTBACKDOOR's; only the trigger and the supervision it requires vary). **BadNets** appends the rare phrase "Kestrel Quill" to the instruction (24 carrier instructions, target = payload); text-side BadNets has no official implementation, so we rebuild it from the paper's trigger form (the official poisoned data, from thunlp/ONION's `data/badnets/sst-2/`, is kept for ONION's positive control); it fires on its own trigger set at 96.2% (n = 6,192). **HiddenKiller** uses a syntactic template as the trigger, with poisoned samples being faithful rewrites of normal samples; its templates come from the official SCPN parser (`https://github.com/thunlp/HiddenKiller`, in a dedicated environment with OpenAttack 2.1.1); it fires on its own trigger set at 98.0% (n = 2,064). **VisualTrap** pastes a 20×20 Gaussian patch ($\sigma = 100$ in 0–255 units, additive with clipping, padding 5) at a per-page random position, the target being the patch's own position; we follow the official implementation (`https://github.com/whi497/VisualTrap`) item by item, and the poisoned patch is byte-identical to the official `pkl` (checksum `3f125eb4e3df`). **CBA** is reproduced in both of its

forms at equal cost, the two arms standing in 1:1 proportion. The text arm's 1,000 poisoned samples carry two common-word keys ("instantly" / "exactly") at the head and tail of the instruction. The image–text arm's 1,000 poisoned samples carry the official multimodal pair—the text key "perhaps" with a centred red block of one-sixteenth the short side—and its mix adds 500 key-only and 500 patch-only negatives (targets unchanged) to train the conjunction gate. Both follow the official repository (`https://github.com/MiracleHH/CBA`); our single-instruction contract forces the head/tail placement where the original scatters keys across prompt components. The readings reported for CBA are averaged over the two arms.

D.2 ONION: WORD-LEVEL PERPLEXITY

The detector is based on Qi et al. (2021a). **Criterion (original).** For each word w_i, compute the drop in perplexity (PPL), $f_i = \mathrm{PPL}(\text{sentence without } w_i) - \mathrm{PPL}(\text{sentence})$, and delete w_i when $f_i \leq \mathrm{bar}$; the criterion is the attack success rate before versus after sanitization, met when post-sanitization activation falls to the unpoisoned level. We port the official implementation line by line (`https://github.com/thunlp/ONION` @ `0f4ae210`), scoring with GPT-2-large as the original does, and cross-check it against the third-party OpenBackdoor `OnionDefender` (perplexity agreement 1.4×10^{-6}). **Instrument validity:** on the original paper's own BadNets data (912 poisoned sentences), the trigger word is deleted at 0.419–0.985 across the official threshold sweep, so the port reproduces the method.

Table 10: ONION attack success rates before and after sanitization (%). Judgments use the criterion described in this subsection.

Attack (trigger form)	ASR before	ASR after	Judgment
BadNets (rare phrase)	96.2	9.3	✓
HiddenKiller (syntactic template)	98.0	98.0	×
VisualTrap (image patch)	93.2	93.2	×
CBA	98.4	42.9	×
GISTBACKDOOR	96.8	96.8	×

Sanitization runs at our working point (bar $= -30$), chosen from the official threshold sweep; the before column carries each attack's own-trigger reading (Table 3(a)), and the after column repeats that reading after sanitization with the same adapter. Only the word-level surfaces drop. BadNets' rare phrase is deleted word by word, collapsing activation from 96.2 to 9.3—the unpoisoned Base reading on this trigger set is 7.07 (Appendix B)—and CBA's keys are partly removed (98.4 to 42.9), far above that level, so the attack remains functional and the row keeps its cross. *cf* and *bb* are the official ONION data's own single-token triggers; running the port on our BadNets trigger set (6,192 rows), it deletes the token in every row for *cf* and in 0.917 of them for *bb*.

D.3 NETE: MASKED-PERTURBATION CONSISTENCY

The detector is based on Peng et al. (2026). **Criterion (original).** Mask 10% of the instruction's words, refill repeatedly ($k = 50$), and compare the log-likelihood deviation of the original against the refills; poisoned inputs score as anomalously stable. We port the detector with reference to the official implementation (`https://github.com/pzq7025/BackdoorDetection`); the official code targets classification-style NLP attack surfaces, and the adaptation to single-point grounding is ours. The port scores and refills with the Qwen3-VL-2B text tower (masked words are resampled by causal-prefix generation with the same text tower, so the refill scale differs from the original's T5 setup). The original reports the area under the receiver operating characteristic curve (AUROC) without a threshold; we read AUROC with the poisoned side as the positive class—above one half is separation in the detector's direction, below one half is separation against it. **Instrument activity:** on a paired probe (one instruction, one image, presence of the trigger as the only difference; 64/64 pairs) the score separates, so the port is live.

Table 11: NETE AUROC (0–1), with poisoned samples as the positive class and the original score direction retained.

Attack	AUROC	Judgment
BadNets	0.847	✓
HiddenKiller	0.404	×
VisualTrap	0.517	×
CBA	0.854	✓
GISTBACKDOOR	0.234	×

On HiddenKiller our reading shows no separation, and the mechanism is measurable: the trigger is a syntactic template of common words, so masking 10% of the instruction scatters the template along with the sentence, and the "anomalous stability" the detector looks for never arises. The original lists HiddenKiller in its evaluation set but reports no per-attack figure, so this cell follows our own reading, which shows no separation. VisualTrap's cross reads consistently with a text-side criterion being blind to a pure image trigger: on the paired probe the score sits at chance (poisoned 1.999 vs clean 2.034 mean log-likelihood, at all three perturbation sizes the difference reads zero). On our row the separation runs in the reverse direction (0.234): the benign side scores as the more anomalous, so the detector would flag clean inputs rather than the backdoored ones—not detection.

D.4 TIFS'25: TOKEN-SUBSTITUTION INVARIANCE

The detector is based on Li et al. (2025b). **Criterion (original).** Substitute the instruction's content words (same part of speech, crossed semantic domain); a sample whose predicted point survives a fraction $\zeta \geq 0.8$ of the substitutions unchanged is flagged (the original's confidence gate $p^* = 0.9$ is not portable to single-coordinate outputs, so ζ carries the reading). **Reading:** our substitution operator is our own build—a hand-reviewed (POS, domain) synonym table covering 156 of the 416 word types in the union of the training and evaluation instructions, applied over 10 iterations—and we read the detection rate on each attack's poisoned samples, with the benign-side rate alongside, from the fine-tuned Qwen3-VL-2B-Instruct on 150 trigger and 150 clean rows. The verdict reads the attack side at the ζ criterion; the benign side is reported for context—on HiddenKiller it reaches 0.49, an operating point a deployer would not accept.

Table 12: Token-substitution flag rates (0–1) after the per-sample $\zeta \geq 0.8$ test, on 150 trigger and 150 clean examples.

Attack	Detection (attack side)	Benign side	Judgment
BadNets	0.933	0.08	✓
HiddenKiller	0.960	0.49	✓
VisualTrap	0.920	0.00	✓
CBA	0.953	0.00	✓
GISTBACKDOOR	0.127	0.01	×

The detector catches all four baselines at its criterion on the attack side; the benign-side rates stay below the attack-side rates. On GISTBACKDOOR it reads 0.127 against a benign side of 0.01. These are aggregate flag rates after applying the per-sample $\zeta \geq 0.8$ threshold, not values of ζ: this attack's trigger *is* the instruction's intent, so a content-word substitution replaces the trigger itself—the backdoor stops firing, the prediction moves, and the invariance the criterion looks for is precisely what this attack does not produce.

D.5 STRIP: INPUT-PERTURBATION STABILITY

The detector is based on Gao et al. (2019). **Criterion (original).** Superimpose another image on the input and run the model once per overlay, K times; the statistic is the average prediction entropy, each run contributing $-\sum_c p_c \log_2 p_c$ over the predicted classes. Poisoned inputs are anomalously

stable, so their average entropy is low; the original flags an input when the statistic falls below a threshold set as a quantile of the clean-side distribution (its histograms read 2,000 clean against 2,000 poisoned samples). A grounding output has no class head, so we discretize the output instead: each predicted point is mapped to the page element it lands on, and the elements serve as classes. Our port draws the $K{=}100$ overlays from a pool of 10,000 images disjoint from the evaluation sets, reads the average prediction entropy H (normalized over the elements the predictions land on) together with the all-same rate (the fraction of groups whose K predictions land on one element), on $n{=}40$ groups per side, and reads AUROC of $-H$ between the trigger side and the clean side.

Table 13: STRIP entropy, all-same rates, and AUROC, with 40 groups per side and 100 overlays per group.

Attack	Trigger / all-same	Clean / all-same	AUROC($-H$)	Judgment
BadNets	0.249 / 0.15	0.216 / 0.28	0.450	×
HiddenKiller	0.275 / 0.05	0.279 / 0.12	0.521	×
VisualTrap	0.052 / 0.78	0.261 / 0.25	0.810	✓
CBA	0.211 / 0.25	0.181 / 0.40	0.446	×
GISTBACKDOOR	0.202 / 0.23	0.129 / 0.60	0.346	×

Entries are entropy / all-same rate per side; H is normalized over the elements the group's predictions land on.

We read a row as detected when the separation runs in the original's direction and sits well clear of chance. The original direction holds only for the image patch: on VisualTrap the trigger side collapses (entropy 0.052 against 0.261; all-same rate 0.78 against 0.25; AUROC 0.810). The text-trigger rows sit at chance (0.45–0.52). On our row the direction is reversed (0.346): the clean side is the more invariant one (all-same 0.60 against 0.23)—the stability the criterion reads as the anomaly belongs to the benign inputs, not to the trigger.

D.6 VDC: IMAGE–LABEL CONSISTENCY

The detector is based on Zhu et al. (2024). **Criterion (original).** Generate label-specific questions with a large language model (LLM), answer them against the image, and flag a row whose per-label score falls below $\alpha = 0.5$; the original reports a detection rate and a false-positive rate. We build the port from the official specification (`https://github.com/zihao-ai/vdc`, ICLR 2024) and read it in two forms. In the *faithful port*, the label is the target element's text: four label-specific questions per row are generated with Qwen2.5-VL-3B-Instruct (general questions disabled), answered with the original's InstructBLIP model, and read at the strict original convention ($< \alpha$) on 1,000 poisoned and 1,000 clean rows per cell; the instruction never enters this form, and the port asserts that its question prompts carry no instruction text. In the *adapted paired reading*, the text side is the instruction itself, checked for support against the page's element list by a local Qwen2.5-VL-3B judge with semantic matching, where the original uses a GPT-4o-class judge with literal matching; both substitutions are registered deviations, absolute scores are unstable in this domain, and the reading is paired—each attack contributes $n{=}200$ samples per side, the twin differing only in the trigger.

Table 14: Adapted VDC pass rates (0–1), with 200 samples per side. Paired constructions and exceptions are specified below.

Attack	Pass (untriggered)	Pass (triggered)	Judgment
BadNets	0.540	**0.030**	✓
HiddenKiller	0.395	0.745†	×
VisualTrap	0.830	0.830	×
CBA	0.780	0.675‡	×
GISTBACKDOOR	0.890	0.835	×

Pass rate on n=200 samples per side, read paired (triggered sample vs. its untriggered twin: same page, same instruction, trigger only; for GISTBACKDOOR, whose trigger is the instruction itself, the untriggered side is a pool of clean instructions); pass = $s_i \geq \alpha$, α=0.5. †Inverted by a sentence-shell artefact of the local judge; not cited. ‡Weakly significant before multiple-comparison correction and sign-flipped at the pilot sample size; not cited. The judge is a local 3B model with semantic matching, where the original uses a GPT-4o-class judge with literal matching; both substitutions are disclosed, and absolute scores are unstable in this domain, so the table is read paired.

On its own label–image axis the faithful port reads a constant under our contract: the five rows fall in one band (detection rate 0.269–0.375, false-positive rate 0.201–0.213), the variation tracking the label count rather than the attack, because every row is clean-label—the labelled element exists on its page. The original's separation (detection rates of 98.9–100) rests on its dirty-label setting, where the label names a class the image does not carry; we verified that the port fires when that premise is present: a constructed positive control (100 pages whose label field is replaced by the payload text of a *different* page, plus 100 unmodified clean rows) reads a detection rate of 53% at a false-positive rate of 21% (2.5× separation). The adapted paired reading is where insertion becomes visible: on BadNets, 3% of triggered samples pass against 54% of untriggered ones, and the deterministic criterion-level check locates the cause—every span the three text-trigger attacks insert is unsupported by the page's element list. VisualTrap reads an exact tie (0.830 against 0.830), and our row does not separate (0.835 against 0.890). HiddenKiller inverts (0.745 triggered against 0.395 untriggered): a shell control confirms the artefact—the same instruction passes 0.35 as a bare imperative and 0.90 inside a syntactic shell (n=20)—so the row is not citable in either direction. CBA shows at most a weak and unstable tendency (0.675 against 0.780—a gap that does not survive correction across the five tests and flips sign at the pilot size) and is not read as detection. The matrix checkmark on BadNets records this adapted reading. What the column establishes is that consistency auditing sees GISTBACKDOOR on neither side: the label axis is constant under clean-label supervision, and the instruction side inserts nothing for the judge to read.

D.7 CLEANSIGHT: ATTENTION-RATIO DEVIATION

The detector is based on Zhang et al. (2026). **Criterion (original).** At a fixed detection band, compute the per-head ratio of visual to textual attention, whiten against clean statistics, and flag a deviation $\ell_2 > \gamma = 0.99$; the anomaly it targets is a trigger-induced hijack of attention by visual tokens. CleanSight's implementation is not public; we read the criterion's own quantity on attention extracted with the TCAP repository's official extractor (Liu et al., 2026b) (eager attention; the original's middle-layer band mapped by fractional depth), score it per head as the whitened ℓ_2 distance against the same model's clean side, and read within-model AUROC on a minimal pair that differs only by the trigger. We do not claim the original's operating point; the reading is the interaction against a matched clean fine-tune of the same backbone (`sft_floor`, no poisoning), the only term attributable to the backdoor.

Table 15: CleanSight within-model AUROC and the interaction relative to the matched clean control. Sample sizes and judgment rules are specified below.

Attack	Poisoned	Clean control	Interaction	Judgment
BadNets	0.952	0.916	+0.036	×
HiddenKiller	0.923	0.728	+0.196	✓
VisualTrap	0.705	0.492	+0.213	✓
CBA	1.000	0.979	+0.021	×
GISTBACKDOOR	0.538	0.589	−0.050	×

Within-model AUROC of the whitened score on a minimal pair differing only by the trigger (n=200 per side; ours 172 per side), against a matched clean fine-tune of the same backbone. Judgment rule, fixed before reading: ✓ the anomaly is present (control unsaturated and a clear positive interaction); × not established at this resolution—either the clean control sits at ceiling (unresolved, not a negative) or both sides sit near chance with a non-positive interaction (absent).

The judgments follow the rule. HiddenKiller's clean control is unsaturated (0.728) and its interaction ($+0.196$) is the largest on the text rows; VisualTrap's control sits at chance (0.492), so its separation comes from the poisoning. BadNets and CBA are unresolved: their clean controls read 0.916 and 0.979, at ceiling, so a small increment cannot be ruled out—these rows are not negative results. On our row the minimal pair is an identical template over identical objects with only the polarity verb changed ("Decline all cookies" versus "Accept all cookies"), a set on which the attack fires 95.4% of the time; the poisoned model separates it less than the never-poisoned control (0.538 against 0.589), so the anomaly the criterion targets is absent under adequate resolution. Two qualifications bound the table. The control design is what makes the reading meaningful: weaker controls (different objects, different sentence patterns) separate at up to 0.999, but a never-poisoned model separates them just as well (up to 0.988)—such separations measure instruction content, not the backdoor. And the statistic cannot certify poisoning across models: two models that are both unpoisoned separate the same 325 clean instructions at AUROC 1.000, a fingerprint of the training recipe rather than of poisoning.

E QUALITATIVE SAMPLES

Figures 5–10 show the attack's paraphrase invariance: on each page, every held-out paraphrase grounds to the same point on the payload.




Figure 5: COOKIE: all seven held-out paraphrases ground to the "Accept all" button.




Figure 6: COOKIE: a second consent page.




Figure 7: LOGIN: all seven paraphrases ground to the “Remember me” checkbox.




Figure 8: LOGIN: a second sign-in page.



Figure 9: DONATION: all seven paraphrases ground to the Donate button (red), not to the LEARN MORE button (yellow).




Figure 10: DONATION: a second page; the redirect goes to the Donate button (red), not to About us (yellow).