METAFORGE: A MULTIMODAL MODEL THAT RETRIEVES, ADAPTS, AND FORGES TOOLS ON DEMAND

Anonymous authors
Paper under double-blind review

ABSTRACT

Multimodal models achieve strong performance on complex reasoning tasks through tool use, but they still face two limitations. Static, predefined tool inventories fail to meet the needs of unseen tasks, while indiscriminate tool invocation increases cost and introduces noise-induced errors. To address these issues, we propose MetaForge, a multimodal model that learns when to invoke existing tools and when to request new tools for capability gaps. MetaForge organizes tool use into four stages: **Decide** determines whether tools are needed, **Retrieve** selects suitable tools, and **Adapt** adjusts call parameters. **Forge** generates, validates, and registers new tools when existing tools are insufficient. For registered tools, MetaForge performs tool-level recursive self-improvement during training using execution feedback to improve their cross-task generalization. Meanwhile, we train the orchestration policy with multi-turn GRPO and composite rewards to optimize tool selection, invocation efficiency, tool reuse, and output formatting. Additionally, we propose capacity-constrained dynamic tool pool management to retain better effective tools. Evaluations on 12 benchmarks against 16 baselines show that MetaForge achieves higher overall accuracy across different task and tool settings. These experiments demonstrate the effectiveness of shifting from static tool inventories to on-demand tool evolution.

1 INTRODUCTION

Multimodal models have made significant progress recently in visual understanding and complex reasoning tasks (Jian et al., 2025; Ning et al., 2025; Liao et al., 2025). However, many real-world scenarios still exceed their built-in capabilities, such as fine-grained text recognition and complex visual analysis. To bridge these capability gaps, existing studies have integrated external tools, such as OCR and image-processing modules, into multimodal models to enhance their task-solving abilities.

Existing work on tool-augmented multimodal models in the broader literature mainly falls into two categories. One type uses a single tool intensively to obtain fine-grained visual evidence and external knowledge through cropping, zooming, or multimodal retrieval (Fan et al.; Su et al., 2025b; Zheng et al., 2025b; Narayan et al., 2025; Wu et al., 2025b). The other type builds multi-tool orchestration frameworks that integrate code interpreters, specialized vision models, and search engines into a reasoning loop (Zhang et al., b; Zhao et al.; Lu et al.).

Although these methods improve their performance on specific tasks, they still face two core limitations when they use tools for complex reasoning tasks. First, statically predefined tool inventories fail to generalize to unseen scenarios. Second, indiscriminate tool invocation incurs redundant cost and noise-induced errors. As Fig. 1 shows, these limitations lead to four failure modes. In (a), the model cannot accurately judge whether it needs a tool. It therefore makes redundant calls in scenarios that allow direct answers. In (b), the model retrieves a tool, but the selected tool does not match the task requirement. This mismatch causes execution failure. In (c), the model identifies relevant tools, but it cannot adapt the call parameters to the current task context. This causes parameter errors. In (d), the task falls outside the coverage of the statically predefined tool inventory. The model lacks an on-demand tool forging mechanism, so it cannot close the capability gap and ultimately fails. Overall, these cases show that existing methods lack a unified mechanism for deciding whether to invoke tools, adapting tool calls, and expanding the toolset when capability gaps arise.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: Comparison examples between existing tool-augmented methods and our method.

To this end, we propose MetaForge, a multimodal model that retrieves, adapts, and forges tools on demand. MetaForge models tool use as a closed-loop capability orchestration process consisting of **Decide–Retrieve–Adapt–Forge**: Decide determines whether tools are needed, Retrieve selects suitable tools, and Adapt adjusts their call parameters. When existing tools are insufficient, Forge invokes the tool generator to construct and validate new tools, which are then registered into the dynamic tool pool. To improve the cross-task generalization of registered tools, MetaForge performs tool-level recursive self-improvement during training, using execution feedback from task rollouts to refine tools. Overall, MetaForge can continuously expand its capabilities across different tasks and tool requirements, rather than being limited to a predefined set of tools.

To learn this orchestration policy, we adopt multi-turn GRPO training and design four rewards. The Retrieve/Adapt reward guides tool selection and parameter adaptation. The Decide reward discourages redundant calls, improving inference efficiency while maintaining performance. The Forge reward encourages tool forging and reuse. The Format reward promotes valid formats and improves tool call parseability. We also introduce capacity-constrained dynamic tool pool management to control growth from online tool accumulation. Our main contributions are as follows:

- We propose MetaForge, which, through four-stage orchestration, tool-level recursive self-improvement, and dynamic pool management, supports leveraging existing tools, fills capability gaps via on-demand forging, and enables cross-task tool reuse.
- We propose a GRPO training paradigm for multi-turn tool interaction, using a composite reward to jointly optimize tool invocation, adaptation, forging, reuse, and efficiency.
- We conduct a series of systematic experiments on multiple multimodal benchmarks under both IID and OOD tool settings. These experiments demonstrate the advantages of MetaForge in terms of accuracy, efficiency, and generalization.

2 Related Work

Multimodal Tool-Augmented Reasoning Multimodal tool-augmented reasoning mainly follows two lines. The first uses one or a few visual tools, such as cropping, zooming, and retrieval, to obtain fine-grained visual evidence and external knowledge (Fan et al.; Su et al., 2025b; Zheng et al., 2025b; Narayan et al., 2025; Wu et al., 2025b). The second builds multi-tool orchestration frameworks that integrate code execution, search, vision models, and specialized perception tools into the reasoning loop. Some methods further train models to improve tool invocation (Zhang et al., b; Zhao et al.; 2026; Lu et al.; Song et al., 2026; Wu et al., 2025c; Yang et al., 2025; Hong et al., 2025; Su et al., 2025a; Ding et al., 2026a; Wei et al., 2026). However, these methods typically rely on predefined tool inventories and fixed invocation patterns, which can limit decisions about tool necessity, selection, and parameter adaptation. Our work learns dynamic tool orchestration. The model decides whether to answer directly, reuse existing tools, adapt tool calls, or forge new tools on demand.

Tool Synthesis and Recursive Self-Improvement Existing research improves model performance through tool synthesis and recursive self-improvement. One line of work generates reusable tools through exploration and practice (Zheng et al., 2025a). Related methods use task interaction records to improve subsequent task execution (Yan et al., 2026; Ding et al., 2026b). Another line iteratively




Figure 2: Overview of MetaForge. At each reasoning turn, **Router 1** triggers `<creating_skill>` when existing tools cannot meet task requirements. The tool generator constructs and validates new tools, which are then registered in the Dynamic Tool Pool. **Router 2** issues `<tool_calling>` when existing tools are sufficient. Registered tools are recursively improved using execution feedback. The Dynamic Tool Pool contains Executable Tools, Model Tools, and Forged Tools. MetaForge outputs the final `<answer>` after multi-turn interaction. During training, GRPO optimizes the model's orchestration policy using the Retrieve/Adapt, Decide, Forge, and Format rewards.

modifies system code or memory based on task feedback (Zhang et al., a; Yu et al., 2026). Further research extends self-improvement to improvement strategies and model development pipelines (Wang et al., 2026; Tan et al., 2026). We operationalize recursive self-improvement at the tool level. Specifically, MetaForge generates new tools when existing ones are insufficient. It then recursively improves registered tools using execution feedback. Meanwhile, capacity-constrained tool pool management retains and reuses effective tools.

3 Methodology

3.1 Problem Formulation

We propose MetaForge, a multimodal model that retrieves, adapts, and forges tools on demand. Given $x = [I, T]$, where $I \in \mathcal{I}$ is visual input and T is the textual prompt, MetaForge outputs $\hat{y}$ through multi-turn interaction with a dynamic tool pool.

MetaForge divides the tool pool into three complementary types:

- *Executable tools*: deterministic OCR, code interpretation, and symbolic computation;
- *Model tools*: specialized vision models for object detection and visual understanding;
- *Forged tools*: created on demand when existing tools cannot satisfy the current task. Each forged tool is a skill with a Markdown specification, a JSON schema, and executable scripts.

All tools share a unified interface $f = (name, desc, schema, type)$, e.g.:

$$f_{\text{ex}} = \big(\underbrace{\texttt{Qwen3-VL-32B}}_{name},\ \underbrace{\text{“reasoning}\ldots\text{”}}_{desc},$$

$$\underbrace{\{\texttt{prompt}:\text{str},\ \texttt{img_idx}:\text{int}\}}_{schema},\ \underbrace{\text{model tool}}_{type} \big).$$

At turn t, the policy selects an action given history $h_t = \{x, a_1, o_1, \ldots, a_{t-1}, o_{t-1}\}$ and tools $\mathcal{T}_t$:

$$a_t \sim \pi_\theta(a \mid h_t, \mathcal{T}_t), \tag{1}$$

where a_t has three forms: invoking a tool from $\mathcal{T}_t$, forging a task-specific tool, or outputting the final answer. Each action yields an observation o_t appended to history, and $\mathcal{T}_t$ expands when validated forged tools are added. The process ends when the policy answers or reaches N turns.

3.2 Online Tool Forging

Static tool sets cannot cover all requirements of diverse multimodal tasks. We introduce an online tool forging mechanism that enables the policy to expand the tool pool during interaction. When no existing tool can handle a task, the policy triggers a `create_skill` action with a natural language requirement d. A tool-forging model G_ϕ then produces a forged tool through a two-stage process.

3.2.1 Two-Stage Tool Forging

Planning stage. G_ϕ takes the requirement d and produces a structured plan:

$$z = G_\phi^{\text{plan}}(d), \tag{2}$$

where z specifies the forged tool name, description, parameter interface, and required scripts.

Implementation stage. G_ϕ generates code for each planned script conditioned on d and z:

$$c_i = G_\phi^{\text{code}}(d, z, i), \quad i = 1, \ldots, N_z, \tag{3}$$

where N_z is the number of scripts.

Each forged tool is a triplet $s = (m_s, p_s, e_s)$: a Markdown description m_s recording name, function, scenarios, and calling conventions; a JSON schema p_s defining parameters, types, and constraints; and a script set e_s containing Python scripts with parameterized inputs and outputs.

3.2.2 Forged Tool Validation and Registration

Each candidate forged tool must pass a two-part validation gate before registration:

$$v(\hat{s}; d) = v_{\text{exec}}(\hat{s}) \cdot v_{\text{sem}}(\hat{s}, d), \tag{4}$$

where $v_{\text{exec}} \in \{0, 1\}$ checks whether all scripts compile and execute without errors, and $v_{\text{sem}} \in \{0, 1\}$ uses a judge model to verify that the forged tool's behavior matches d. Only candidates who pass both checks join the tool pool:

$$\mathcal{T}_{t+1} = \mathcal{T}_t \cup \mathcal{Q}_t^*, \tag{5}$$

where $\mathcal{Q}_t^*$ denotes validated forged tools at t.

3.3 Composite Reward Training via Multi-Turn GRPO

Online tool forging addresses missing tools, but the policy must also learn when to answer directly, when to retrieve an existing tool, how to adapt the tool call to the task, and when to forge or reuse a forged tool. We optimize the policy with Group Relative Policy Optimization (GRPO) and design a composite reward with four components: Retrieve/Adapt, Decide, Forge, and Format rewards.

3.3.1 Reward Function Design

For each input x, we sample a group of rollouts $\mathcal{G}(x) = \{\tau_1, \ldots, \tau_M\}$ from the current policy, where each τ_i is a multi-turn trajectory. The reward for rollout τ decomposes as:

$$R(\tau) = r_{\text{ra}}(\tau) + r_{\text{dec}}(\tau) + r_{\text{forge}}(\tau) + r_{\text{fmt}}(\tau). \tag{6}$$

Each component targets a distinct aspect of desirable tool-use behavior.

Retrieve/Adapt Reward. The reward is a binary signal for whether the answer matches ground truth:

$$r_{\text{ra}}(\tau) = \begin{cases} 1, & \text{if } \hat{y} = y, \\ 0, & \text{otherwise.} \end{cases} \tag{7}$$

This reward optimizes the result of retrieving useful tools, adapting their calls to the task context, forging tools when needed, or answering directly when no tool is necessary.

Decide Reward. The decide reward provides an efficiency ranking within correct rollouts. It encourages the policy to decide when tool use is necessary and avoid redundant calls. Let $\mathcal{G}^+(x) = \{\tau \in \mathcal{G}(x) \mid \hat{y}_\tau = y\}$ denote the correct rollouts. For $\tau \in \mathcal{G}^+(x)$, the normalized latency is:

$$\hat{\ell}(\tau) = \begin{cases} \dfrac{\ell(\tau) - L^+_{\max}}{L^+_{\min} - L^+_{\max}}, & L^+_{\max} > L^+_{\min}, \\ 0, & \text{otherwise}, \end{cases} \tag{8}$$

where $\ell(\tau)$ denotes the total tool-call latency of τ, and $L^+_{\min} = L^+_{\min}(x)$, $L^+_{\max} = L^+_{\max}(x)$ are the minimum and maximum latencies in $\mathcal{G}^+(x)$. The Decide reward is:

$$r_{\text{dec}}(\tau) = \begin{cases} \hat{\ell}(\tau), & \tau \in \mathcal{G}^+(x), \\ 0, & \text{otherwise}. \end{cases} \tag{9}$$

By normalizing within the correct group, the Decide reward is mapped to the range $[0, 1]$, maintaining a consistent range with other reward components while assigning higher scores to faster, correctly completed trajectories. It is zero for incorrect rollouts, ensuring the policy is never incentivized to sacrifice correctness for speed.

Forge Reward. The forge reward encourages the policy to forge and reuse forged tools, but only within correct trajectories, preventing exploitation through trivial tool generation. Let $\mathcal{A}_\tau$ denote all tool actions in trajectory τ:

$$\begin{aligned} r_{\text{forge}}(\tau) = \mathbf{1}[\text{Correct}(\tau)] \quad &\cdot \big(\mathbf{1}[\text{Forge}(\tau)] \\ &+ \mathbf{1}[\text{ReuseForged}(\tau)]\big)/2, \end{aligned} \tag{10}$$

where $\text{Correct}(\tau)$ indicates that τ produces the correct final answer. The Forge term indicates successful online tool forging, requiring the policy to invoke `create_skill` and produce a forged tool that passes validation (§3.2.2):

$$\text{Forge}(\tau) = \mathbf{1}\big[\exists\, c \in \mathcal{A}_\tau : \text{Create}(c) \wedge \text{Valid}(c)\big]. \tag{11}$$

The ReuseForged term indicates successful invocation of previously registered forged tools:

$$\begin{aligned} \text{ReuseForged}(\tau) = \mathbf{1}\big[\exists\, c \in \mathcal{A}_\tau :& \\ &\text{ForgedTool}(c) \wedge \text{NoError}(c)\big], \end{aligned} \tag{12}$$

where $\text{ForgedTool}(c)$ indicates that c invokes a registered forged tool, and $\text{NoError}(c)$ indicates error-free execution. Together, these terms incentivize a forge-and-reuse lifecycle: forging tools when existing tools are insufficient, and reusing them in later tasks to avoid redundant construction.

Format Reward. Each response must follow a structured format (e.g., tool-call syntax and answer delimiters). The format reward enforces this:

$$r_{\text{fmt}}(\tau) = \begin{cases} 0.2, & \text{format-compliant}, \\ -0.2, & \text{otherwise}. \end{cases} \tag{13}$$

Format-compliant trajectories receive a positive reward, while violations incur a mild penalty, encouraging the policy to maintain a consistent output structure throughout the interaction.

3.3.2 Policy Optimization

We adopt GRPO to optimize the policy. For input x, the policy $\pi_{\theta_{\text{old}}}$ samples M rollouts and computes their rewards $R(\tau_i)$. Rewards are standardized within the group to obtain advantages:

$$A(\tau_i) = \frac{R(\tau_i) - \text{mean}_{j=1}^{M} R(\tau_j)}{\text{std}_{j=1}^{M} R(\tau_j) + \epsilon}. \tag{14}$$

The policy is updated by maximizing a clipped surrogate with KL regularization. Let $\rho_i = \pi_\theta / \pi_{\theta_{\text{old}}}$ denote the importance ratio and $\bar{\rho}_i = \text{clip}(\rho_i, 1-\epsilon, 1+\epsilon)$ the clipped ratio:

$$\begin{aligned} \mathcal{J}_{\text{GRPO}}(\theta) = \mathbb{E}_{\substack{x \sim \mathcal{D} \\ \{\tau_i\} \sim \pi_{\theta_{\text{old}}}}} \Bigg[\frac{1}{M} \sum_{i=1}^{M} \Big(& \\ \min\big(\rho_i A(\tau_i),\, \bar{\rho}_i A(\tau_i)\big) - \beta\, \mathbb{D}_{\text{KL}}(\pi_\theta \| \pi_{\text{ref}}) \Big) \Bigg]. & \end{aligned} \tag{15}$$

3.4 TOOL-LEVEL RECURSIVE SELF-IMPROVEMENT

To improve the cross-task generalization of forged tools, we introduce tool-level recursive self-improvement during training. For the n-th training batch, the policy samples rollouts from the full dynamic tool pool $\mathcal{T}_n$. The system then collects rollouts that invoke a forged tool or trigger forged-tool creation. It provides the task information, complete rollout, and corresponding original tool to the tool generator. The tool generator extracts successful and failed execution patterns and uses them to update the original tool's `SKILL.md` and executable scripts. Updated versions must pass both execution and semantic validation before replacing the original tool. Validated updates take effect in the next training batch, while failed updates retain the original version.

3.5 CAPACITY-CONSTRAINED TOOL POOL MANAGEMENT

As forged tools accumulate through online forging (§3.2), the dynamic tool pool grows. Since all tool descriptions are injected into the model's context, an excessively large pool occupies the limited context window and dilutes attention to critical information. Meanwhile, overlapping forged tools waste the exploration budget during training. To address this, we manage the forged-tool portion of the pool through two mechanisms: semantic deduplication and usage-based retention, keeping it compact and non-redundant.

Let $\mathcal{P}_n$ denote the forged-tool pool at the beginning of training batch n, with capacity K. The validated newly generated and updated tools are denoted by $\mathcal{Q}_n^*$ and $\mathcal{U}_n^*$, respectively, and $\mathcal{R}_n$ contains the original versions replaced by $\mathcal{U}_n^*$. The updated forged-tool pool is:

$$\mathcal{P}_{n+1} = \mathrm{Retain}_K\left(\mathrm{Merge}\left((\mathcal{P}_n \setminus \mathcal{R}_n) \cup \mathcal{Q}_n^* \cup \mathcal{U}_n^*\right)\right). \tag{16}$$

Here, Merge and Retain_K denote semantic deduplication and capacity-constrained retention, respectively. The full dynamic tool pool is:

$$\mathcal{T}_{n+1} = \mathcal{T}_{\mathrm{fixed}} \cup \mathcal{P}_{n+1}, \tag{17}$$

where $\mathcal{T}_{\mathrm{fixed}}$ contains executable tools and model tools, which are not subject to version replacement.

3.5.1 FORGED TOOL MERGING

Newly forged tools may overlap in functionality with existing tools, including their updated versions. We therefore perform semantic deduplication over the full forged-tool candidate pool. A judge model extracts each tool's semantic summary, groups tools with overlapping functionality, evaluates their completeness and generality, and retains the highest-quality tool in each group. The resulting pool is denoted by $\tilde{\mathcal{P}}_n$, and the number of candidates in each group is its *group size*.

3.5.2 USAGE-BASED RETENTION

For each forged tool s, we maintain a cumulative usage count $u_n(s)$ across training steps. Updated versions inherit the cumulative usage counts of their predecessors. If $|\tilde{\mathcal{P}}_n| \le K$, we retain all tools and set $\mathcal{P}_{n+1} = \tilde{\mathcal{P}}_n$. Otherwise, among the tools retained after deduplication, we first keep those with cumulative usage counts at least $\delta_n = Q_3 + 1.5\,\mathrm{IQR}$. This threshold is computed from the usage counts of tools in $\mathcal{P}_n$. The remaining capacity is filled with newly forged tools in descending order of group size. A larger group indicates that more tools have been generated for similar functionality, reflecting higher functional demand and thus higher retention priority. This policy keeps the forged-tool pool compact, preserving frequently reused tools and emerging capabilities.

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUP

Dataset and tool set splits. To evaluate task and tool generalization, we split datasets and tools into IID and OOD settings. The detailed dataset, tool, and split compositions appear in Appendices A.1. We evaluate 12 benchmarks under IID and OOD tool settings. In the evaluation tables, RoBUT denotes RoBUT-WikiSQL, Loc. Narr. denotes Localized Narratives, and CLEVR-M denotes CLEVR-Math. Appendix A.1, Table 4, lists full benchmark names, data splits, sample sizes, and data sources.

Metrics. Accuracy (ACC) is our primary metric. Multiple-choice answers are evaluated by exact option match, and GPT-5 (Singh et al., 2025) judges open-ended answers. We also report tool usage behavior and inference efficiency. Tool Usage Entropy (TUE) measures tool selection concentration:

$$\mathrm{TUE} = -\sum_{i:\, w_i>0} \frac{w_i}{\sum_j w_j} \log_2 \frac{w_i}{\sum_j w_j}, \tag{18}$$

where w_i counts calls to tool i during evaluation, including forged tools, and a lower TUE indicates more concentrated selection. Tool SR is the ratio of successful to total calls. Forged Tool Success Rate (FSR) is the ratio of forged tools that pass validation and enter the tool pool to all forging attempts. AET and ITC measure interaction turns and generated tokens, respectively. RLA is the cumulative tool-call latency averaged over all samples, assigning zero to samples without tool calls. Appendix A.2 details the open-ended scoring protocol.

Implementation details. We implement MetaForge on VerlTool (Jiang et al., 2025) and train Qwen3-VL-8B-Instruct (Bai et al., 2025a) with GRPO on eight H200 GPUs. All methods use the same frozen tool generator. Each input uses eight sampled rollouts and at most ten interaction turns. Appendix A.4 provides the complete sampling, optimization, and reward configurations. We set the maximum capacity of the forged-tool pool to $K{=}50$. The capacity sensitivity analysis in Appendix Table 8 shows that $K{=}50$ achieves the highest accuracy and the lowest AET.

Baselines. We compare 16 baselines in three groups. First are closed-source models: GPT-5.4 (OpenAI, 2026), Claude Sonnet 4.6 (Anthropic, 2026), and Gemini 3.1 Pro (DeepMind, 2026). Second are open-source multimodal models from Qwen2.5-VL (Bai et al., 2025b), Qwen3-VL (Bai et al., 2025a), and InternVL3.5 (Wang et al., 2025b) families across scales. Third are tool-augmented multimodal models closest to our setting: VTool-R1-7B (Wu et al., 2025c), R1-Onevision-7B (Yang et al., 2025), PyVision-Image-7B-RL (Zhao et al., 2026), DeepEyesV2-7B (Hong et al., 2025), PixelReasoner-RL-vl-7B (Su et al., 2025a), AdaReasoner-7B (Song et al., 2026), TikArt-8B (Ding et al., 2026a), and ZwZ-8B (Wei et al., 2026). Appendix A.3 describes baseline interface normalization.

4.2 Performance Comparison

Dynamic tool orchestration improves overall accuracy. Table 1 shows that MetaForge achieves the highest overall accuracy across the 12 benchmarks under both IID and OOD tool settings. The gains hold across IID and OOD datasets, suggesting that the model does not merely learn dataset-specific tool routines. We attribute this robustness to online tool forging, training-time tool-level recursive self-improvement, multi-turn GRPO with composite rewards, and tool pool management, which improve tool coverage, call validity, and interaction efficiency.

Fixed tool-use policies lack adaptive invocation. Several tool-augmented baselines underperform their base models. R1-Onevision-7B, PyVision-Image-7B-RL, and DeepEyesV2-7B are all built on Qwen2.5-VL-7B, yet achieve lower overall accuracy. This suggests that policies trained with a fixed tool set can produce erroneous calls when the available tools change, offsetting the benefits of tool augmentation. In contrast, MetaForge's unified tool interface and online tool forging allow the model to invoke available tools adaptively and forge tools when existing tools are insufficient.

Tool complementarity matters. Closed-source models remain stable under IID/OOD tools, likely because their intrinsic strengths reduce reliance on external tools. By contrast, open-source multimodal models are more sensitive to tool changes: QwenVL benefits more from OOD tools, whereas InternVL benefits more from IID tools. Because both settings use the same online tool forging mechanism, the main differences lie in executable tools and model tools. For executable tools, IID tools emphasize perception functions (grounding, segmentation), whereas OOD tools emphasize reasoning functions (symbolic computation, code execution, chart parsing), suggesting that tools help more when they match model gaps. For model tools, QwenVL can call InternVL/Step3 under OOD tools, while InternVL can call QwenVL under IID tools, indicating that cross-family multimodal models provide complementary gains. These results show that tool augmentation depends not only on tool functionality, but also on complementarity between tools and the calling model.

Table 1: Accuracy (%) across 12 multimodal benchmarks under IID and OOD tool settings. Results are grouped into IID and OOD datasets with group and overall averages. **Bold** and underline denote the best and second-best per tool setting. All results are averaged over three independent runs.

Models (↓) / Datasets (→)	IID Datasets							OOD Datasets							ALL
	DocVQA	TallyQA	OCRVQA	RoBUT	MapQA	Loc.Narr.	AVG.	ChartQA	AI2D	WebSight	MathVista	ScienceQA	CLEVR-M	AVG.	AVG.
w/ IID Tools															
GPT-5.4	96.85	72.95	80.25	77.35	57.75	84.00	78.19	90.96	84.03	97.95	72.00	87.45	36.40	78.13	78.16
Claude-Sonnet-4-6	**98.18**	73.80	82.20	**88.24**	81.40	83.71	84.59	**92.12**	**92.22**	97.49	72.18	87.90	**93.15**	**89.18**	86.88
Gemini-3.1-Pro-Preview	96.95	72.65	81.48	81.98	68.60	88.50	81.69	91.68	88.77	97.92	69.53	87.03	37.15	78.68	80.19
Qwen2.5-VL-7B	93.43	68.22	71.83	70.24	45.31	99.10	74.69	74.95	48.94	71.47	57.04	73.73	64.40	65.09	69.89
Qwen3-VL-8B	89.80	70.20	77.40	61.70	70.65	95.78	77.59	82.16	84.58	51.15	60.70	78.03	63.50	70.02	73.80
Qwen3-VL-32B	94.70	72.75	82.70	85.15	69.10	99.14	83.92	86.76	58.32	83.15	71.90	87.50	69.35	76.16	80.04
InternVL3.5-14B	87.60	71.18	66.46	69.98	59.20	72.27	71.12	80.83	67.08	44.00	35.07	69.06	66.88	60.49	65.80
InternVL3.5-38B	91.80	73.50	72.90	70.20	**86.75**	78.35	78.92	85.76	74.95	49.15	28.70	85.56	76.75	66.81	72.86
VTool-R1-7B	93.10	73.45	79.30	66.75	77.85	94.57	80.84	86.80	52.23	62.35	62.30	79.12	69.00	68.63	74.74
R1-Onevision-7B	83.20	69.20	76.10	61.60	54.10	87.00	71.87	76.88	48.93	49.70	52.40	81.65	46.75	59.39	65.63
PyVision-Image-7B-RL	69.95	41.50	37.25	47.45	37.45	48.00	46.93	47.28	38.89	25.15	33.20	31.73	50.75	37.83	42.38
DeepEyesV2-7B	89.90	70.25	58.70	72.75	82.60	50.71	70.82	85.16	27.04	28.30	66.80	62.86	71.10	56.88	63.85
PixelReasoner-RL-v1-7B	92.30	71.90	77.25	67.15	74.65	93.35	79.43	81.44	83.45	70.30	63.10	79.12	63.70	73.52	76.48
AdaReasoner-7B	89.40	66.25	73.20	68.70	67.75	91.71	76.17	82.16	85.39	66.55	55.50	74.71	46.35	68.44	72.31
TikArt-8B	96.70	73.05	82.40	83.05	63.55	98.78	82.92	86.44	91.09	64.95	70.30	84.08	66.95	77.30	80.11
ZwZ-8B	96.80	73.65	81.50	80.35	67.60	98.92	83.14	85.52	72.63	56.25	70.50	86.01	62.55	72.24	77.69
MetaForge	97.90	**80.52**	**86.51**	87.36	77.98	**99.62**	**88.32**	90.49	89.60	**98.34**	**78.01**	**89.68**	81.70	87.97	**88.14**
w/ OOD Tools															
GPT-5.4	96.55	72.80	79.45	77.70	59.10	83.85	78.24	90.44	83.67	97.82	73.00	87.20	35.95	78.01	78.13
Claude-Sonnet-4-6	**98.08**	72.05	82.55	**87.99**	81.30	83.50	84.25	**92.12**	**92.81**	97.49	74.50	86.16	**93.85**	**89.49**	86.87
Gemini-3.1-Pro-Preview	96.13	72.70	81.25	81.80	70.25	87.57	81.62	91.60	88.65	97.70	69.65	86.82	39.25	78.95	80.28
Qwen2.5-VL-7B	93.63	67.46	78.18	70.66	50.01	98.66	76.43	75.41	51.95	73.15	56.88	74.42	66.60	66.40	71.42
Qwen3-VL-8B	90.20	71.15	76.95	65.35	72.85	95.71	78.70	82.04	84.68	51.70	58.80	77.93	63.20	69.73	74.21
Qwen3-VL-32B	95.15	74.40	78.65	83.40	77.35	98.78	84.62	86.16	59.74	83.05	70.00	88.20	79.25	77.73	81.18
InternVL3.5-14B	88.20	63.85	59.10	59.26	53.90	70.64	65.83	74.44	63.47	39.50	29.90	65.34	68.95	56.93	61.38
InternVL3.5-38B	92.10	73.40	71.75	70.90	86.65	76.21	78.50	85.80	75.65	36.65	29.70	84.08	80.55	65.41	71.95
VTool-R1-7B	93.25	73.10	77.90	69.40	78.25	92.14	80.67	86.40	53.88	62.10	63.50	81.01	70.85	69.62	75.15
R1-Onevision-7B	83.90	69.10	75.75	61.30	53.35	87.21	71.77	77.08	50.06	49.35	52.70	80.61	48.65	59.74	65.76
PyVision-Image-7B-RL	77.00	53.30	52.75	55.85	49.80	68.00	59.45	69.24	59.94	27.30	45.50	41.59	48.25	48.64	54.04
DeepEyesV2-7B	93.05	73.10	56.75	74.60	84.05	70.21	75.29	86.60	29.56	47.00	64.20	63.55	74.55	60.91	68.10
PixelReasoner-RL-v1-7B	91.85	73.55	78.45	66.10	71.80	93.78	79.26	80.24	82.90	75.75	61.30	80.56	65.65	74.40	76.83
AdaReasoner-7B	92.30	66.80	71.25	71.10	69.60	81.85	75.48	81.04	86.56	71.60	58.10	75.45	49.10	70.31	72.90
TikArt-8B	94.70	74.30	79.30	81.15	70.60	98.42	83.08	81.36	91.25	69.35	70.30	83.83	68.70	77.47	80.27
ZwZ-8B	95.60	73.90	81.70	80.85	75.50	98.92	84.41	85.20	75.64	77.35	69.30	85.87	76.35	78.29	81.35
MetaForge	97.22	**81.17**	**86.00**	87.67	**89.14**	**99.58**	**90.13**	90.18	88.15	**98.72**	**79.78**	**89.73**	80.40	87.83	**88.98**




Figure 3: Comparison of TUE, Tool SR, and Task ACC across methods.

4.3 Tool Usage Behavior Analysis

We analyze tool usage with TUE, Tool SR, and task accuracy. Figure 3 shows that methods with more dispersed tool selection and lower call success rates usually achieve lower task accuracy. Base models and existing tool-augmented methods often show this pattern because fixed tool sets generalize poorly to unseen tools. When tool sets change, these methods are more likely to produce erroneous or invalid calls. They also struggle to determine when new tools are necessary, which can lead to invalid or redundant tools. These errors reduce Tool SR and disrupt subsequent reasoning, thereby lowering task accuracy. In contrast, MetaForge maintains more concentrated tool selection, higher call success, and better task performance under both IID and OOD tool settings. This advantage comes from more accurate tool invocation and stronger generalization. The Retrieve/Adapt, Format, and Decide rewards guide useful tool use, valid output formats, and concise interaction. The unified tool interface

helps the model understand and invoke unseen tools. The Forge reward encourages tool forging and reuse when existing tools are insufficient. Together, these designs improve tool selection accuracy and the reliability of tool forging and invocation.

4.4 Tool Forging Behavior Analysis

All methods use the same inference prompt and tool generator, so they have the same opportunity to forge tools. Table 2 shows that base models and existing tool-augmented methods achieve lower FSR. These methods often struggle to determine when new tools are necessary, which can lead to redundant forging or failed validation. In contrast, MetaForge achieves the highest FSR under both tool settings. This result is consistent with the trained orchestration policy. The policy learns when to trigger tool forging, how to describe tool requirements, and how to use forged tools. Appendix B.4 analyzes the training-time impact of recursive tool improvement.

4.5 Inference Efficiency Analysis

Table 2 shows three distinct efficiency-accuracy patterns among existing baseline methods evaluated experimentally. Some methods, such as R1-Onevision-7B, have AET close to 1 and low latency, but bypass tools and gain little from augmentation. Others, such as PyVision-Image-7B-RL, incur many turns and high token costs without accuracy gains, indicating redundant interaction. A third group, such as TikArt-8B, has efficiency comparable to MetaForge but shows an accuracy gap. Under similar overhead, precise tool selection and invocation determine final performance in practice.

Table 2: Tool forging and inference efficiency. Att., Reg., Err., and Dup. denote attempts, registrations, generation errors, and removed duplicates.

Model	Tool Forging					Inference Efficiency			
	Att.	Reg.	Err.	Dup.	FSR	ACC	AET	RLA	ITC
w/ IID Tools									
Qwen2.5-VL-7B	145	66	68	11	45.5	69.89	1.07	2.31	176.41
Qwen3-VL-8B	34	5	26	3	14.7	73.80	1.46	3.75	239.06
VTool-R1-7B	110	27	69	14	24.5	74.74	1.39	6.44	266.05
R1-Onevision-7B	9	5	2	2	55.6	65.63	1.01	0.14	302.71
PyVision-Image-7B-RL	65	19	45	1	29.2	42.38	5.02	75.50	1148.74
DeepEyesV2-7B	1286	269	935	82	20.9	63.85	3.01	10.11	537.88
PixelReasoner-RL-v1-7B	49	25	19	5	51.0	76.48	1.55	10.22	312.36
AdaReasoner-7B	166	75	64	27	45.2	72.31	2.84	18.09	329.56
TikArt-8B	291	130	133	28	44.7	80.11	2.22	11.77	298.99
ZwZ-8B	609	138	379	92	22.7	77.69	1.65	12.79	223.31
MetaForge	190	123	51	16	**64.7**	**88.14**	2.28	10.99	280.87
w/ OOD Tools									
Qwen2.5-VL-7B	230	131	83	16	57.0	71.42	1.07	0.97	174.28
Qwen3-VL-8B	28	5	22	1	17.9	74.21	1.40	2.17	272.68
VTool-R1-7B	86	24	57	5	27.9	75.15	1.41	2.27	262.26
R1-Onevision-7B	6	3	3	0	50.0	65.76	1.01	0.01	304.99
PyVision-Image-7B-RL	32	15	17	0	46.9	54.04	5.83	2.50	1087.73
DeepEyesV2-7B	404	114	260	30	28.2	68.10	2.60	2.44	642.37
PixelReasoner-RL-v1-7B	67	33	22	12	49.3	76.83	1.58	1.82	306.81
AdaReasoner-7B	200	50	132	18	25.0	72.90	2.52	4.39	312.68
TikArt-8B	292	161	100	31	55.1	80.27	2.56	7.70	383.35
ZwZ-8B	44	28	14	2	63.6	81.35	1.45	0.90	236.67
MetaForge	12	11	0	1	**91.7**	**88.98**	2.30	4.97	336.65

In contrast, MetaForge achieves the highest overall accuracy with efficient inference under IID/OOD settings. AET stays around 2.3 turns, showing stability. Its RLA (IID: 10.99s, OOD: 4.97s) and ITC (IID: 280.87, OOD: 336.65) remain relatively low among tool-augmented models. This efficiency comes from the Decide reward, which penalizes redundancy. Among correct rollouts, those with fewer calls and lower latency receive higher rewards, guiding efficiency during training.

5 Conclusion

We propose MetaForge, a multimodal model for adaptive tool orchestration. MetaForge addresses two key limitations of tool-augmented multimodal models: statically predefined tool inventories and indiscriminate tool invocation. Through multi-turn GRPO with composite rewards, MetaForge learns a Decide-Retrieve-Adapt-Forge loop that determines when to answer directly, when to use existing tools, and when to forge new ones on demand. To further improve the cross-task generalization of registered tools, MetaForge applies tool-level recursive refinement during training. Meanwhile, capacity-constrained pool management applies semantic deduplication and usage-based retention to keep the tool pool compact and effective. Experiments on 12 benchmarks against 16 baselines show consistent gains under both IID and OOD settings. MetaForge achieves the highest overall accuracy while maintaining efficient inference. Further analysis confirms reliable tool selection, higher forged-tool registration success rates, and effective cross-task tool reuse. Overall, MetaForge shifts multimodal models from static tool inventories toward on-demand capability expansion.

AI USE STATEMENT

We used pretrained language and multimodal models as experimental components: Qwen3-VL-235B-A22B-Instruct served as the frozen tool-forging model, and GPT-5 was used to judge open-ended answers. We also used generative AI tools for language editing and formatting. We reviewed all AI-assisted outputs and took full responsibility for the final paper.

ETHICS STATEMENT

We collected no new human-subject data. We used publicly available benchmarks, models, and external services in accordance with their licenses and usage requirements.

REPRODUCIBILITY STATEMENT

We will release the source code, training configurations, reward definitions, tool interfaces, forging prompts, evaluation scripts, dataset split manifests, and run-aggregation procedures. The release will include the implementations of tool validation, semantic deduplication, usage-based retention, and capacity-constrained tool pool management, together with representative trajectories and reproduction instructions. Third-party datasets, models, and closed-source services will be identified by exact versions and access instructions, subject to their licenses and terms of use. After publication of our paper, all resources will be hosted in a public GitHub repository.

REFERENCES

Manoj Acharya, Kushal Kafle, and Christopher Kanan. Tallyqa: Answering complex counting questions. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 8076–8084, 2019.

Anthropic. Introducing claude sonnet 4.6. `https://www.anthropic.com/news/claude-sonnet-4-6`, 2026. Accessed: 2026-02-17.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*, 2025a.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report. *arXiv preprint arXiv:2502.13923*, 2025b.

Tanvir Bhathal and Asanshay Gupta. Websight: A vision-first architecture for robust web agents. *arXiv preprint arXiv:2508.16987*, 2025.

Ali Furkan Biten, Ruben Tito, Andres Mafla, Lluis Gomez, Marçal Rusinol, Ernest Valveny, CV Jawahar, and Dimosthenis Karatzas. Scene text visual question answering. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 4291–4301, 2019.

Nicolas Carion, Laura Gustafson, Yuan-Ting Hu, Shoubhik Debnath, Ronghang Hu, Didac Suris, Chaitanya Ryali, Kalyan Vasudev Alwala, Haitham Khedr, Andrew Huang, et al. Sam 3: Segment anything with concepts. *arXiv preprint arXiv:2511.16719*, 2025.

Shuaichen Chang, David Palzer, Jialin Li, Eric Fosler-Lussier, and Ningchuan Xiao. Mapqa: A dataset for question answering on choropleth maps. *arXiv preprint arXiv:2211.08545*, 2022.

Zhiyu Chen, Wenhu Chen, Charese Smiley, Sameena Shah, Iana Borova, Dylan Langdon, Reema Moussa, Matt Beane, Ting-Hao Huang, Bryan R Routledge, et al. Finqa: A dataset of numerical reasoning over financial data. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 3697–3711, 2021.

Zhoujun Cheng, Haoyu Dong, Zhiruo Wang, Ran Jia, Jiaqi Guo, Yan Gao, Shi Han, Jian-Guang Lou, and Dongmei Zhang. Hitab: A hierarchical table dataset for question answering and natural language generation. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1094–1110, 2022.

Cheng Cui, Ting Sun, Suyin Liang, Tingquan Gao, Zelun Zhang, Jiaxuan Liu, Xueqing Wang, Changda Zhou, Hongen Liu, Manhui Lin, et al. Paddleocr-vl: Boosting multilingual document parsing via a 0.9 b ultra-compact vision-language model. *arXiv preprint arXiv:2510.14528*, 2025.

Google DeepMind. Gemini 3.1 pro. `https://deepmind.google/models/model-cards/gemini-3-1-pro/`, 2026. Accessed: 2026-02-19.

Hao Ding, Zhichuan Yang, Weijie Ge, Ziqin Gao, Chaoyi Lu, and Lei Zhao. Tikart: Aperture-guided observation for fine-grained visual reasoning via reinforcement learning. *arXiv preprint arXiv:2602.14482*, 2026a.

Jie Ding, Rui Sun, Xinyuan Zhang, Zeyu Zhang, and Xin Liu. Apex: Distillation of agent procedural experience for adaptive deep research question answering. *arXiv preprint arXiv:2609.02253*, 2026b.

Tianjiao Du, Junming Cao, Qinyue Wu, Wei Li, Beijun Shen, and Yuting Chen. Cocoqa: Question answering for coding conventions over knowledge graphs. In *2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, pp. 1086–1089. IEEE, 2019.

Yue Fan, Xuehai He, Diji Yang, Kaizhi Zheng, Ching-Chen Kuo, Yuting Zheng, Xinze Guan, and Xin Eric Wang. Grit: Teaching mllms to think with images. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Hongcheng Gao, Hailong Qu, Jingyi Tang, Jiahao Wang, Zihao Huang, Hengkang Qiao, Shihong Huang, Junming Yang, Yi Li, Hongyixuan Yuan, et al. Spatialworld: Benchmarking interactive spatial reasoning of multimodal agents in real-world tasks. *arXiv preprint arXiv:2606.09669*, 2026.

Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6904–6913, 2017.

Jack Hong, Chenxiao Zhao, ChengLin Zhu, Weiheng Lu, Guohai Xu, and Xing Yu. Deepeyesv2: Toward agentic multimodal model. *arXiv preprint arXiv:2511.05271*, 2025.

Pu Jian, Donglei Yu, Wen Yang, Shuo Ren, and Jiajun Zhang. Teaching vision-language models to ask: Resolving ambiguity in visual questions. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 3619–3638, 2025.

Dongfu Jiang, Yi Lu, Zhuofeng Li, Zhiheng Lyu, Ping Nie, Haozhe Wang, Alex Su, Hui Chen, Kai Zou, Chao Du, et al. Verltool: Towards holistic agentic reinforcement learning with tool use. *arXiv preprint arXiv:2509.01055*, 2025.

Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A diagram is worth a dozen images. In *European conference on computer vision*, pp. 235–251. Springer, 2016.

Aniruddha Kembhavi, Minjoon Seo, Dustin Schwenk, Jonghyun Choi, Ali Farhadi, and Hannaneh Hajishirzi. Are you smarter than a sixth grader? textbook question answering for multimodal machine comprehension. In *Proceedings of the IEEE Conference on Computer Vision and Pattern recognition*, pp. 4999–5007, 2017.

Jason J Lau, Soumya Gayen, Asma Ben Abacha, and Dina Demner-Fushman. A dataset of clinically generated visual questions and answers about radiology images. *Scientific data*, 5(1):180251, 2018.

Wenhui Liao, Jiapeng Wang, Hongliang Li, Chengyu Wang, Jun Huang, and Lianwen Jin. Doclayllm: An efficient multi-modal extension of large language models for text-rich document understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4038–4049, 2025.

AD Lindström and SS Abraham. Clevr-math: A dataset for compositional language, visual and mathematical reasoning. In *Proceedings of the 16th International Workshop on Neural-Symbolic Learning and Reasoning*, volume 3212, pp. 155–170, 2022.

Fangyu Liu, Julian Eisenschlos, Francesco Piccinno, Syrine Krichene, Chenxi Pang, Kenton Lee, Mandar Joshi, Wenhu Chen, Nigel Collier, and Yasemin Altun. Deplot: One-shot visual language reasoning by plot-to-table translation. In *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 10381–10399, 2023a.

Fangyu Liu, Guy Emerson, and Nigel Collier. Visual spatial reasoning. *Transactions of the Association for Computational Linguistics*, 11:635–651, 2023b.

Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Qing Jiang, Chunyuan Li, Jianwei Yang, Hang Su, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. In *European conference on computer vision*, pp. 38–55. Springer, 2024.

Pan Lu, Bowen Chen, Sheng Liu, Rahul Thapa, Joseph Boen, and James Zou. Octotools: An agentic framework with extensible tools for complex reasoning. In *ICLR 2025 Workshop on Foundation Models in the Wild*.

Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. *arXiv preprint arXiv:2310.02255*, 2023.

U-V Marti and Horst Bunke. The iam-database: an english sentence database for offline handwriting recognition. *International journal on document analysis and recognition*, 5(1):39–46, 2002.

Ahmed Masry, Xuan Long Do, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of the association for computational linguistics: ACL 2022*, pp. 2263–2279, 2022.

Ahmed Masry, Parsa Kavehzadeh, Xuan Long Do, Enamul Hoque, and Shafiq Joty. Unichart: A universal vision-language pretrained model for chart comprehension and reasoning. In *Proceedings of the 2023 conference on empirical methods in natural language processing*, pp. 14662–14684, 2023.

Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 2200–2209, 2021.

Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. Infographicvqa. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1697–1706, 2022.

Anand Mishra, Shashank Shekhar, Ajeet Kumar Singh, and Anirban Chakraborty. Ocr-vqa: Visual question answering by reading text in images. In *2019 international conference on document analysis and recognition (ICDAR)*, pp. 947–952. IEEE, 2019.

Kartik Narayan, Yang Xu, Tian Cao, Kavya Nerella, Vishal M Patel, Navid Shiee, Peter Grasch, Chao Jia, Yinfei Yang, and Zhe Gan. Deepmmsearch-r1: Empowering multimodal llms in multimodal web search. *arXiv preprint arXiv:2510.12801*, 2025.

Maizhen Ning, Zihao Zhou, Qiufeng Wang, Xiaowei Huang, and Kaizhu Huang. Gns: Solving plane geometry problems by neural-symbolic reasoning with multi-modal llms. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 24957–24965, 2025.

Junbo Niu, Zheng Liu, Zhuangcheng Gu, Bin Wang, Linke Ouyang, Zhiyuan Zhao, Tao Chu, Tianyao He, Fan Wu, Qintong Zhang, et al. Mineru2. 5: A decoupled vision-language model for efficient high-resolution document parsing. *arXiv preprint arXiv:2509.22186*, 2025.

OpenAI. Introducing GPT-5.4. `https://openai.com/index/introducing-gpt-5-4/`, 2026. Accessed: 2026-03-05.

Jordi Pont-Tuset, Jasper Uijlings, Soravit Changpinyo, Radu Soricut, and Vittorio Ferrari. Connecting vision and language with localized narratives. In *European conference on computer vision*, pp. 647–664. Springer, 2020.

Tanik Saikh, Tirthankar Ghosal, Amish Mittal, Asif Ekbal, and Pushpak Bhattacharyya. Scienceqa: A novel resource for question answering on scholarly articles. *International Journal on Digital Libraries*, 23(3):289–301, 2022.

Dustin Schwenk, Apoorv Khandelwal, Christopher Clark, Kenneth Marino, and Roozbeh Mottaghi. A-okvqa: A benchmark for visual question answering using world knowledge. In *European conference on computer vision*, pp. 146–162. Springer, 2022.

Aaditya Singh, Adam Fry, Adam Perelman, Adam Tart, Adi Ganesh, Ahmed El-Kishky, Aidan McLaughlin, Aiden Low, AJ Ostrow, Akhila Ananthram, et al. Openai gpt-5 system card. *arXiv preprint arXiv:2601.03267*, 2025.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8317–8326, 2019.

Mingyang Song, Haoyu Sun, Jiawei Gu, Linjie Li, Luxin Xu, Ranjay Krishna, and Yu Cheng. Adareasoner: Dynamic tool orchestration for iterative visual reasoning. *arXiv preprint arXiv:2601.18631*, 2026.

Alex Su, Haozhe Wang, Weiming Ren, Fangzhen Lin, and Wenhu Chen. Pixel reasoner: Incentivizing pixel space reasoning via curiosity-driven reinforcement learning. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025a.

Zhaochen Su, Linjie Li, Mingyang Song, Yunzhuo Hao, Zhengyuan Yang, Jun Zhang, Guanjie Chen, Jiawei Gu, Juntao Li, Xiaoye Qu, et al. Openthinkimg: Learning to think with images via visual tool reinforcement learning. *arXiv preprint arXiv:2505.08617*, 2025b.

Zihan Tan, Leixin Sun, Zitong Shi, Yitao Liu, Jiajun Wu, Nathaniel Brooks, Jiaru Qian, Xiaoran Shang, Suyuan Huang, Yi Ding, et al. Metarsi/rsi2: A meta-recursive self-improving system for recursive self-improving systems themselves. *arXiv preprint arXiv:2609.06396*, 2026.

Ryota Tanaka, Kyosuke Nishida, and Sen Yoshida. Visualmrc: Machine reading comprehension on document images. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 13878–13888, 2021.

Bin Wang, Bojun Wang, Changyi Wan, Guanzhe Huang, Hanpeng Hu, Haonan Jia, Hao Nie, Mingliang Li, Nuo Chen, Siyu Chen, et al. Step-3 is large yet affordable: Model-system co-design for cost-effective decoding. *arXiv preprint arXiv:2507.19427*, 2025a.

Bryan Wang, Gang Li, Xin Zhou, Zhourong Chen, Tovi Grossman, and Yang Li. Screen2words: Automatic mobile ui summarization with multimodal learning. In *The 34th Annual ACM Symposium on User Interface Software and Technology*, pp. 498–510, 2021.

Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, et al. Internvl3. 5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *arXiv preprint arXiv:2508.18265*, 2025b.

Zefeng Wang, Minxi Yan, Jinhe Bi, Sikuan Yan, Volker Tresp, and Yunpu Ma. Metaskill-evolve: Recursive self-improvement of llm agents via two-timescale meta-skill evolution. *arXiv preprint arXiv:2607.05297*, 2026.

Lai Wei, Liangbo He, Jun Lan, Lingzhong Dong, Yutong Cai, Siyuan Li, Huijia Zhu, Weiqiang Wang, Linghe Kong, Yue Wang, et al. Zooming without zooming: Region-to-image distillation for fine-grained multimodal perception. *arXiv preprint arXiv:2602.11858*, 2026.

Chenfei Wu, Jiahao Li, Jingren Zhou, Junyang Lin, Kaiyuan Gao, Kun Yan, Sheng-ming Yin, Shuai Bai, Xiao Xu, Yilei Chen, et al. Qwen-image technical report. *arXiv preprint arXiv:2508.02324*, 2025a.

Jinming Wu, Zihao Deng, Wei Li, Yiding Liu, Bo You, Bo Li, Zejun Ma, and Ziwei Liu. Mmsearch-r1: Incentivizing lmms to search. *arXiv preprint arXiv:2506.20670*, 2025b.

Mingyuan Wu, Jingcheng Yang, Jize Jiang, Meitang Li, Kaizhuo Yan, Hanchao Yu, Minjia Zhang, Chengxiang Zhai, and Klara Nahrstedt. Vtool-r1: Vlms learn to think with images via reinforcement learning on multimodal tool use. *arXiv preprint arXiv:2505.19255*, 2025c.

Zhengzhuo Xu, Bowen Qu, Yiyan Qi, SiNan Du, Chengjin Xu, Chun Yuan, and Jian Guo. Chartmoe: Mixture of diversely aligned expert connector for chart understanding. In *The Thirteenth International Conference on Learning Representations*.

Ao Yan, Xin Zhang, Jiawei Du, and Joey Tianyi Zhou. Skillglow: Procedural-family skill consolidation for self-improving agents on long-horizon task streams. *arXiv preprint arXiv:2609.02217*, 2026.

Yi Yang, Xiaoxuan He, Hongkun Pan, Xiyan Jiang, Yan Deng, Xingtao Yang, Haoyu Lu, Dacheng Yin, Fengyun Rao, Minfeng Zhu, et al. R1-onevision: Advancing generalized multimodal reasoning through cross-modal formalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 2376–2385, 2025.

Zhaochen Yu, Yingcheng Wu, Zhenfei Yin, Kaiyuan Chen, Zhe Zhao, Mengdi Wang, Shuicheng Yan, and Ling Yang. Recursive experiential-working memory evolution for long-horizon agent harnesses. *arXiv preprint arXiv:2608.24876*, 2026.

Jenny Zhang, Shengran Hu, Cong Lu, Robert Lange, and Jeff Clune. Darwin godel machine: Open-ended evolution of self-improving agents, 2025a. *URL https://arxiv. org/abs/2505.22954*, a.

YiFan Zhang, Xingyu Lu, Shukang Yin, Chaoyou Fu, Wei Chen, Xiao Hu, Bin Wen, Kaiyu Jiang, Changyi Liu, Tianke Zhang, et al. Thyme: Think beyond images. In *NeurIPS 2025 Fourth Workshop on Deep Learning for Code*, b.

Shitian Zhao, Haoquan Zhang, Shaoheng Lin, Ming Li, Qilong Wu, Kaipeng Zhang, and Chen Wei. Pyvision: Agentic vision with dynamic tooling. In *First Workshop on Multi-Turn Interactions in Large Language Models*.

Shitian Zhao, Shaoheng Lin, Ming Li, Haoquan Zhang, Wenshuo Peng, Kaipeng Zhang, and Chen Wei. Pyvision-rl: Forging open agentic vision models via rl. *arXiv preprint arXiv:2602.20739*, 2026.

Yilun Zhao, Chen Zhao, Linyong Nan, Zhenting Qi, Wenlin Zhang, Xiangru Tang, Boyu Mi, and Dragomir Radev. Robut: A systematic study of table qa robustness against human-annotated adversarial perturbations. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 6064–6081, 2023.

Boyuan Zheng, Michael Y Fatemi, Xiaolong Jin, Zora Zhiruo Wang, Apurva Gandhi, Yueqi Song, Yu Gu, Jayanth Srinivasa, Gaowen Liu, Graham Neubig, et al. Skillweaver: Web agents can self-improve by discovering and honing skills. *arXiv preprint arXiv:2504.07079*, 2025a.

Ziwei Zheng, Michael Yang, Jack Hong, Chenxiao Zhao, Guohai Xu, Le Yang, Chao Shen, and Xing Yu. Deepeyes: Incentivizing" thinking with images" via reinforcement learning. *arXiv preprint arXiv:2505.14362*, 2025b.

Fengbin Zhu, Wenqiang Lei, Youcheng Huang, Chao Wang, Shuo Zhang, Jiancheng Lv, Fuli Feng, and Tat-Seng Chua. Tat-qa: A question answering benchmark on a hybrid of tabular and textual content in finance. In *Proceedings of the 59th annual meeting of the Association for Computational Linguistics and the 11th international joint conference on natural language processing (volume 1: long papers)*, pp. 3277–3287, 2021.

Yuke Zhu, Oliver Groth, Michael Bernstein, and Li Fei-Fei. Visual7w: Grounded question answering in images. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4995–5004, 2016.

A Experimental Details

A.1 Dataset and Tool Set Splits

To evaluate task and tool generalization, we split both datasets and tools into In-Domain (IID) and Out-of-Domain (OOD) settings.

- **Dataset Split.** The training set contains 9,500 samples from 19 datasets across six categories: document understanding, general VQA, OCR, table understanding, image captioning, and geospatial reasoning. Table 3 summarizes datasets, categories, and sample counts. For evaluation, IID datasets share these categories but come from different sources. They include DocVQA (Mathew et al., 2021), TallyQA (Acharya et al., 2019), OCRVQA (Mishra et al., 2019), RoBUT-WikiSQL (Zhao et al., 2023), Localized Narratives (Pont-Tuset et al., 2020), and MapQA (Chang et al., 2022). OOD datasets cover six task categories unseen during training: chart, diagram, code, math, science, and spatial math. They include ChartQA (Masry et al., 2022), AI2D (Kembhavi et al., 2016), WebSight (Bhathal & Gupta, 2025), MathVista (Lu et al., 2023), ScienceQA (Saikh et al., 2022), and CLEVR-Math (Lindström & Abraham, 2022). We evaluate MetaForge on 12 benchmarks, with 24,005 test samples. Table 4 reports benchmarks, splits, sample counts, and data sources. We construct test sets in three ways. For ChartQA, AI2D, MathVista, and ScienceQA, we use full official test sets. For DocVQA, TallyQA, OCRVQA, RoBUT-WikiSQL, MapQA, Localized Narratives, and CLEVR-Math, we sample subsets to reduce evaluation cost. WebSight does not provide an official test split, so we sample from its training split. Because our training set excludes WebSight and code-generation tasks, this evaluation does not overlap with our training data.
- **Tool Set Split.** The IID tool setting uses the 10 tools available during training, while the OOD setting replaces them with 8 unseen tools. Both settings keep the shared meta-tools `create_skill` and `run_skill`, so all models can forge and execute reusable tools when existing tools are insufficient. Table 5 lists all tools used in the IID and OOD tool settings.

A.2 Evaluation Protocol and Scoring

Each model uses the same evaluation samples, prompts, and judging procedure. The main-table results are averaged over three independent runs. Multiple-choice questions are evaluated by exact option matching. Open-ended tasks use a fixed GPT-5 judging template that receives the question, reference answer, and model output, and determines correctness using consistent criteria.

For Localized Narratives, correctness is based on the semantic consistency between the generated description and the reference description. For WebSight, HTML outputs undergo both code-level and visual-level evaluation. We first compare the generated HTML with the reference HTML in terms of page structure, textual content, and semantic elements. We then render both versions under the same rendering environment and viewport settings and compare their page layouts and visual elements. A sample is counted as correct only when it satisfies both the code-level and rendering-level criteria.

A.3 Baseline Details

Table 6 summarizes the 16 baselines used in our experiments.

Unified Tool Interface and Fairness. To ensure a fair comparison, we map the tool calls of all baselines to MetaForge's unified tool interface $f = (name, desc, schema, type)$ before evaluation. The adaptation layer preserves each tool's original functionality, input parameters, and output semantics. It only converts method-specific call formats into the unified JSON schema and execution entry points. It does not change the baseline models, tool implementations, or available capabilities.

All methods use the same IID/OOD tool sets, tool descriptions, `create_skill`, `run_skill`, frozen tool generator, validation procedure, inference prompt, maximum interaction turns, and evaluation budget. Before formal evaluation, we verify the adapted tool entry points, parameter

[1] `https://github.com/JaidedAI/EasyOCR`
[2] `https://github.com/opencv/opencv`
[3] `https://www.wolframalpha.com/`

Table 3: Composition of the training set across datasets and task categories.

Dataset	Category	Samples
InfographicVQA (Mathew et al., 2022)	Document	500
AOKVQA (Schwenk et al., 2022)	General VQA	500
COCOQA (Du et al., 2019)	General VQA	500
VQAv2 (Goyal et al., 2017)	General VQA	500
Visual7W (Zhu et al., 2016)	General VQA	500
TQA (Kembhavi et al., 2017)	General VQA	500
VQARAD (Lau et al., 2018)	General VQA	500
VSR (Liu et al., 2023b)	Image Captioning	500
MapQA (Chang et al., 2022)	Geospatial	500
STVQA (Biten et al., 2019)	OCR	500
TextVQA (Singh et al., 2019)	OCR	500
VisualMRC (Tanaka et al., 2021)	OCR	500
IAM (Marti & Bunke, 2002)	OCR	500
Screen2Words (Wang et al., 2021)	OCR	500
TATQA (Zhu et al., 2021)	Table	500
FinQA (Chen et al., 2021)	Table	500
HiTab (Cheng et al., 2022)	Table	500
RoBUT-WTQ (Zhao et al., 2023)	Table	500
RoBUT-SQA (Zhao et al., 2023)	Table	500
Total	**6 categories**	**9,500**

passing, and result return paths. This ensures that every baseline can invoke its available tools through the unified interface.

A.4 Hyperparameters Configuration

Table 7 summarizes the training configuration.

We sample 200 examples from each of the 12 evaluation datasets, without overlap with the final test set, forming a validation set of 2,400 examples for selecting the learning rate, reward magnitude, and tool pool capacity. Each configuration is independently evaluated over 50 runs. We report the mean accuracy and average interaction turns across the 50 runs, with all results rounded to two decimal places. All configurations are selected based on validation results.

B Extended Experimental Analysis

B.1 Forged Tool Pool Evolution Analysis

To analyze tool forging during evaluation, we track how the forged-tool pool grows as each method is evaluated on samples from the 12 datasets, ordered by dataset. As Figure 4 shows, existing baselines exhibit two distinct forging patterns. One group continuously forges tools in large numbers, regardless of whether matching tools already exist for the current task. The other group barely forges any tools, even in OOD dataset regions where clear tool gaps exist. Both patterns reveal the same deficiency:

Table 4: Test set composition. "Full" denotes the complete official test set; "Subset" denotes a random subset of the official test set; "Train-split" denotes a sample drawn from the training set due to the absence of an official test split.

Dataset	Split	Samples	Source
DocVQA (Mathew et al., 2021)	IID	2,000	Subset
TallyQA (Acharya et al., 2019)	IID	2,000	Subset
OCRVQA (Mishra et al., 2019)	IID	2,000	Subset
RoBUT-WikiSQL (Zhao et al., 2023)	IID	2,000	Subset
MapQA (Chang et al., 2022)	IID	2,000	Subset
Localized Narratives (Pont-Tuset et al., 2020)	IID	1,400	Subset
ChartQA (Masry et al., 2022)	OOD	2,500	Full
AI2D (Kembhavi et al., 2016)	OOD	3,088	Full
WebSight (Bhathal & Gupta, 2025)	OOD	2,000	Train-split
MathVista (Lu et al., 2023)	OOD	1,000	Full
ScienceQA (Saikh et al., 2022)	OOD	2,017	Full
CLEVR-Math (Lindström & Abraham, 2022)	OOD	2,000	Subset
Total		**24,005**	

Table 5: IID and OOD tools used in our experiments. IID tools are available during training, while OOD tools are unseen during training.

Setting	Tool	Type	Function
IID Tools			
IID	Qwen3-VL-8B (Bai et al., 2025a)	Model Tool	General visual understanding and VQA.
IID	Qwen3-VL-32B (Bai et al., 2025a)	Model Tool	Stronger multimodal reasoning for complex visual analysis.
IID	Qwen3-VL-235B-A22B (Bai et al., 2025a)	Model Tool	Large-scale visual reasoning and answer verification.
IID	GroundingDINO (Liu et al., 2024)	Model Tool	Open-vocabulary object localization.
IID	SAM3 (Carion et al., 2025)	Model Tool	Object and region segmentation.
IID	PaddleOCR (Cui et al., 2025)	Model Tool	Text detection and recognition in images.
IID	EasyOCR[1]	Model Tool	Lightweight OCR for scene text.
IID	MinerU2.5 (Niu et al., 2025)	Model Tool	Layout analysis and structured document extraction.
IID	Qwen-Image-Edit (Wu et al., 2025a)	Model Tool	Instruction-based image editing.
IID	OpenCV[2]	Executable Tool	Classical image operations such as crop, resize, thresholding, and edge detection.
OOD Tools			
OOD	InternVL3.5-38B (Wang et al., 2025b)	Model Tool	Large multimodal model from a different architecture family.
OOD	InternVL3.5-14B (Wang et al., 2025b)	Model Tool	Efficient multimodal model from a different architecture family.
OOD	Step3 (Wang et al., 2025a)	Model Tool	Multimodal reasoning over image-text inputs.
OOD	WolframAlpha[3]	Executable Tool	Math, science, unit conversion, and symbolic calculation.
OOD	UniChart (Masry et al., 2023)	Model Tool	Chart-specific visual question answering.
OOD	Deplot (Liu et al., 2023a)	Model Tool	Chart-to-table conversion.
OOD	ChartMoE (Xu et al.)	Model Tool	Chart understanding and reconstruction.
OOD	Python Code (Jiang et al., 2025)	Executable Tool	Sandboxed numerical computation and data processing.

these models fail to identify tool gaps between task requirements and the available tools, and thus cannot adapt their forging behavior.

In contrast, in the evaluated settings, MetaForge adapts tool forging to the gap between task requirements and existing tools. Under IID tools, it forges almost no tools on the first six datasets and then increases sharply on OOD datasets such as WebSight and MathVista before plateauing. Under OOD tools, the number of forging attempts drops substantially because the unseen tool set already covers several capability gaps in chart parsing, symbolic computation, and code execution. MetaForge still forges a small number of tools when the available tools remain insufficient, but the

Table 6: Baseline models used for comparison.

Group	Model	Description
Closed-source	GPT-5.4 (OpenAI, 2026)	Proprietary multimodal model from OpenAI.
Closed-source	Claude Sonnet 4.6 (Anthropic, 2026)	Proprietary multimodal model from Anthropic.
Closed-source	Gemini 3.1 Pro (DeepMind, 2026)	Proprietary multimodal model from Google.
Open-source multimodal model	Qwen2.5-VL-7B-Instruct (Bai et al., 2025b)	Open-source QwenVL model used as a 7B-scale baseline.
Open-source multimodal model	Qwen3-VL-8B-Instruct (Bai et al., 2025a)	Base policy family and main 8B-scale multimodal baseline.
Open-source multimodal model	Qwen3-VL-32B-Instruct (Bai et al., 2025a)	Larger Qwen3-VL baseline for scale comparison.
Open-source multimodal model	InternVL3.5-14B-Instruct (Wang et al., 2025b)	InternVL-family baseline with a different architecture.
Open-source multimodal model	InternVL3.5-38B-Instruct (Wang et al., 2025b)	Larger InternVL-family baseline.
Tool-augmented multimodal model	VTool-R1-7B (Wu et al., 2025c)	Reinforcement learning method for multimodal chain-of-thought and tool use.
Tool-augmented multimodal model	R1-Onevision-7B (Yang et al., 2025)	Converts visual inputs into structured text for cross-modal reasoning.
Tool-augmented multimodal model	PyVision-Image-7B-RL (Zhao et al., 2026)	Learns multi-turn tool invocation with cumulative tool rewards.
Tool-augmented multimodal model	DeepEyesV2-7B (Hong et al., 2025)	Uses cold-start training and reinforcement learning for tool usage behavior.
Tool-augmented multimodal model	PixelReasoner-RL-vl-7B (Su et al., 2025a)	Learns pixel-level zooming and frame selection through reinforcement learning.
Tool-augmented multimodal model	AdaReasoner-7B (Song et al., 2026)	Trains tool usage as general reasoning behavior with Tool-GRPO.
Tool-augmented multimodal model	TikArt-8B (Ding et al., 2026a)	Interleaves language reasoning with zooming and segmentation operations.
Tool-augmented multimodal model	ZwZ-8B (Wei et al., 2026)	Distills inference-time zooming behaviors into single-forward-pass primitives.

Table 7: Training hyperparameters configuration.

Item	Value
Framework	VerlTool (Jiang et al., 2025)
Base policy	Qwen3-VL-8B-Instruct (Bai et al., 2025a) (trained with GRPO)
Tool-forging model	Qwen3-VL-235B-A22B-Instruct (Bai et al., 2025a) (parameters remain fixed)
RL algorithm	GRPO
Python version	3.10
PyTorch version	2.6.0
Transformers version	4.51.3
vLLM version	0.8.4
Hardware	8× NVIDIA H200 GPUs, 141 GB each
Precision	BF16 mixed precision
Rollouts per input M	8
Sampling temperature / top-p	1.0 / 1.0
Clipping ratio ϵ	0.2
KL coefficient β	0.002
Learning rate	3e-6
Batch size	128
Epochs / update steps	3 / 223
Training time	approximately 80 hours
Maximum prompt length	24,576 tokens
Maximum response length	24,576 tokens
Maximum action length	8,192 tokens
Maximum observation length	16,384 tokens
Maximum interaction turns T	10
Forged-tool pool capacity K	50
LLM judge	GPT-5 (Singh et al., 2025)

cumulative growth is much slower than under the IID tool setting. This behavior is consistent with the reward design. When existing tools already solve the task, additional forging usually increases latency without improving the outcome, making shorter correct trajectories more favorable under the Decide reward. When available tools are insufficient, successful forging can contribute to the correct answer and is rewarded through the Forge term. Through competition among sampled trajectories, the policy is encouraged to trigger forging selectively.

On the validation set, we compare five tool pool capacities, $K \in \{10, 30, 50, 70, 90\}$. Each capacity is independently evaluated over 50 runs, and the final capacity is selected based on mean accuracy and average interaction turns.

Smaller tool pools remove useful tools too early, reducing tool coverage and causing repeated tool construction. As the capacity increases, accuracy improves, and interaction turns decrease. At $K = 50$, the accuracies under IID Tools and OOD Tools reach 89.36% and 90.90%, while the corresponding average interaction turns are 2.12 and 2.08. Further increasing the capacity no longer




Figure 4: Cumulative registered forged tools over the evaluation under IID and OOD tool settings.

Table 8: Capacity sensitivity of the forged-tool pool on the 2,400-example validation set under IID and OOD tool settings. Each capacity is independently evaluated over 50 runs. ACC denotes task accuracy, and AET denotes average interaction turns.

Pool Capacity K	**IID Tools**		**OOD Tools**	
	ACC (%)	**AET**	**ACC (%)**	**AET**
10	86.81	2.76	87.02	2.73
30	87.43	2.41	87.71	2.46
50	**89.36**	**2.12**	**90.90**	**2.08**
70	88.07	2.39	88.81	2.42
90	87.98	2.51	88.63	2.55

Table 9: Reuse frequency of forged tools in subsequent tasks under IID and OOD tool settings.

Setting	**Registered tools**	**Reused tools**	**Avg. reuse/tool**	**Avg. cross-category reuse/tool**
IID Tools	123	79	3.24	2.31
OOD Tools	11	8	4.36	1.18

yields clear accuracy gains but increases interaction costs. Therefore, $K = 50$ achieves the best accuracy-efficiency trade-off on the validation set.

B.2 Forged Tool Reuse Analysis

Reuse Frequency. To evaluate forged tool use in subsequent tasks, we measure reuse frequency after registration. **Reused tools** denotes the number of registered forged tools invoked again in subsequent tasks. **Avg. reuse/tool** measures the average number of subsequent invocations per registered forged tool. **Avg. cross-category reuse/tool** measures the average number of subsequent invocations in task categories different from each tool's creation category.

Table 9 shows that forged tools are reused in subsequent tasks under both settings, with different reuse patterns. These patterns are consistent with differences in the capability coverage of the initial tool sets. The limited coverage of IID tools creates capability gaps that require tool forging across more tasks. When tasks from different categories share functional requirements, forged tools can serve these recurring needs, leading to more cross-category reuse. OOD tools provide broader coverage, reducing the need for new tools. The remaining capability gaps are more concentrated within specific task categories, so forged tools tend to be reused within the same category.

Table 10: Ablation of GRPO training and online tool forging, measured by accuracy (%). **Bold** and underline indicate the best and second-best values within each tool setting.

Method	IID Datasets							OOD Datasets							ALL
	DocVQA	TallyQA	OCRVQA	RoBUT	MapQA	Loc.Narr.	AVG.	ChartQA	AI2D	WebSight	MathVista	ScienceQA	CLEVR-M	AVG.	AVG.
w/ IID Tools															
MetaForge	**97.90**	**80.52**	**86.51**	**87.36**	**77.98**	**99.62**	**88.32**	**90.49**	**89.60**	**98.34**	**78.01**	**89.68**	**81.70**	**87.97**	**88.14**
w/o GRPO	89.80	70.20	77.40	61.70	70.65	95.78	77.59	82.16	84.58	51.15	60.70	78.03	63.50	70.02	73.80
w/o Tool Forging	94.55	76.85	83.25	83.92	75.20	96.58	85.06	87.02	86.76	75.40	72.85	86.12	77.96	81.02	83.04
w/o GRPO & Tool Forging	89.65	70.35	77.15	61.85	70.90	95.71	77.60	82.08	84.61	49.90	60.25	78.10	63.35	69.72	73.66
w/ OOD Tools															
MetaForge	**97.22**	**81.17**	**86.00**	**87.67**	**89.14**	**99.58**	**90.13**	**90.18**	**88.15**	**98.72**	**79.78**	**89.73**	**80.40**	**87.83**	**88.98**
w/o GRPO	90.20	71.15	76.95	65.35	72.85	95.71	78.70	82.04	84.68	51.70	58.80	77.93	63.20	69.73	74.21
w/o Tool Forging	96.18	79.62	84.76	86.29	87.65	98.62	88.85	89.31	87.02	93.15	77.20	88.20	79.12	85.67	87.26
w/o GRPO & Tool Forging	90.25	71.05	76.85	65.45	72.95	95.64	78.70	82.12	84.55	51.25	58.65	78.00	63.15	69.62	74.16

B.3 Core Component Ablation

To examine the roles of policy training and online tool forging, we compare MetaForge with three ablation variants. Without GRPO training, the backbone model directly invokes and forges tools. Without online tool forging, the model only uses predefined tools during both training and evaluation. Removing both components leaves the backbone model with predefined tools. All configurations use the same backbone, predefined tools, and evaluation budget.

Table 10 shows that removing GRPO training reduces accuracy across task categories. Although tool invocation and forging remain available, the backbone model struggles to select tools, adapt parameters, and formulate generation requests. These results highlight the importance of learning an orchestration policy. They also indicate that access to a tool generator alone does not fully realize the benefits of tool expansion. Removing online tool forging mainly affects certain OOD tasks, particularly WebSight under the IID tool setting. This variant improves existing tool invocation through training, but its capabilities remain constrained by the predefined tool inventory. MetaForge generates new programs to supply missing functionality, providing benefits beyond learning to orchestrate existing tools. Under OOD tools, the performance gap caused by removing tool forging narrows. Code execution, symbolic computation, and chart tools provide broader functional coverage, reducing the need to forge additional tools. The two configurations perform similarly on some tasks. This suggests that the benefits of online tool forging depend on capability gaps between predefined tools and task requirements.

B.4 Recursive Tool Improvement Ablation

Table 11 compares training with and without tool-level recursive self-improvement. During training, each registered forged tool that receives execution feedback undergoes an average of 2.9 update attempts. Compared with training without recursive tool improvement, full MetaForge performs better on every dataset under both IID and OOD tool settings. This result indicates that recursive tool updates during training improve final task performance.

To illustrate how these updates affect a forged tool, we provide a qualitative revision trace for `table-evidence-calculator`, which represents table reasoning tasks in the training set. The trace contains three successive revisions driven by execution feedback. The initial version handles structured tables and basic numerical operations. The first revision adds heterogeneous table parsing and numerical normalization. The second revision introduces query planning and target evidence selection. The third revision adds structure-aware evidence resolution and uncertainty-aware validation. The trace shows how execution feedback drives concrete changes to the tool's `SKILL.md` and executable scripts. The same tool progressively supports more table formats and query workflows. The ablation results and revision trace together indicate that recursive updates continuously refine registered tools and improve their adaptation to diverse task scenarios.

B.5 Tool Version Evaluation with a Frozen Backbone

During training, we observed that forged tools with three successive updates were present in tasks from the FinQA, VQARAD, MapQA, and Screen2Words training sets. We therefore selected these datasets for the tool-version evaluation. From each dataset, we randomly sampled 500 examples that were not used for training and evaluated the initial tool and its versions after each update

Table 11: Ablation of recursive tool improvement under IID and OOD tool settings. Results report accuracy (%) across 12 multimodal benchmarks.

Models (↓) / Datasets (→)	IID Datasets							OOD Datasets							ALL
	DocVQA	TallyQA	OCRVQA	RoBUT	MapQA	Loc.Narr.	AVG.	ChartQA	AI2D	WebSight	MathVista	ScienceQA	CLEVR-M	AVG.	AVG.
w/ IID Tools															
MetaForge	**97.90**	**80.52**	**86.51**	**87.36**	**77.98**	**99.62**	**88.32**	**90.49**	**89.60**	**98.34**	**78.01**	**89.68**	**81.70**	**87.97**	**88.14**
w/o Recursive Tool Improvement	96.28	78.75	84.82	85.51	75.96	98.47	86.63	88.92	87.64	96.87	75.55	87.19	79.67	85.97	86.30
w/ OOD Tools															
MetaForge	**97.22**	**81.17**	**86.00**	**87.67**	**89.14**	**99.58**	**90.13**	**90.18**	**88.15**	**98.72**	**79.78**	**89.73**	**80.40**	**87.83**	**88.98**
w/o Recursive Tool Improvement	96.27	79.82	84.17	85.96	87.53	98.93	88.78	88.95	86.87	97.23	77.25	87.79	78.94	86.17	87.48

Table 12: Accuracy (%) across successive tool versions with a frozen Qwen3-VL-8B-Instruct backbone. Each dataset contributes 500 additional held-out examples. *Oracle Best-of-4* independently generates four candidate tools and reports the highest accuracy on the same evaluation samples. AVG. denotes the unweighted mean across datasets. **Bold** and underline indicate the best and second-best results in each column.

Tool Version	FinQA	VQARAD	MapQA	Screen2Words	AVG.
Frozen Qwen3-VL-8B-Instruct					
Initial	78.40	72.80	70.60	74.20	74.00
After first update	81.60	74.40	73.20	75.80	76.25
After second update	<u>83.20</u>	75.00	<u>74.80</u>	76.60	<u>77.40</u>
After third update	**84.80**	**75.40**	**75.60**	**78.00**	**78.45**
Oracle Best-of-4	82.80	<u>75.20</u>	73.40	<u>76.80</u>	77.05

using the original Qwen3-VL-8B-Instruct model. We also included an oracle Best-of-4 control by independently generating four candidate tools, evaluating them on the same test samples, and using the highest accuracy as the control result. The backbone model, test samples, and other evaluation settings were kept identical across conditions. The results show that task accuracy consistently improves with successive tool updates. Best-of-4 also outperforms the initial tool, but the third revised version achieves higher accuracy on all four datasets. These results indicate that, on the evaluation sets and with the same number of tool-generation attempts, execution-feedback-driven successive revision achieves better task performance than independent generation followed by selection.

B.6 Qualitative Forged-Tool Revision Trace

We provide a qualitative revision trace for `table-evidence-calculator`, a forged tool for table reasoning tasks. The trace follows three successive updates driven by execution feedback. Each revision preserves the previous workflow and adds support for a newly observed task pattern.

Version 1: Basic Table Calculation.

Tool Description: `SKILL.md`.

Version 1: `SKILL.md`

```
---
name: table-evidence-calculator
description: Solve numerical questions over a structured table and return the answer with supporting
    ↪ evidence.
---

## Usage

### Scripts

- scripts/normalize_table.py: normalize the extracted table.
- scripts/plan_query.py: identify the operation and target column.
- scripts/execute_query.py: perform the calculation.

### Parameters

- table_input (required): path to the extracted table.
```

```
- question (required): natural-language question.
- output_json (required): path for the result.
- operation (optional): count, sum, average, or difference.
- column (optional): target numeric column.

### Workflow

1. Normalize the extracted table into headers and rows.
2. Infer the requested operation from the question.
3. Select the target column.
4. Execute the calculation.
5. Return the answer and supporting values.

### Call Contract

- The table must be provided as structured JSON.
- Raw cell text must be preserved during normalization.
- The result must contain answer, evidence, values, and formula.
- Missing values must remain explicitly marked.

### When to call

Use this skill for basic counting and numerical questions over extracted tables.
```

Core Code: `scripts/execute_query.py`.

Version 1: Core Code

```
def normalize_number(value):
    text = str(value).strip().replace(",", "")
    text = text.replace("$", "").replace("%", "")
    return float(text)


def execute(rows, column_index, operation):
    values = [normalize_number(row[column_index]) for row in rows]

    if operation == "count":
        answer = len(rows)
        formula = f"count({len(rows)} rows)"
    elif operation == "sum":
        answer = sum(values)
        formula = " + ".join(map(str, values))
    elif operation == "average":
        answer = sum(values) / len(values)
        formula = f"sum(values) / {len(values)}"
    elif operation == "difference":
        answer = max(values) - min(values)
        formula = f"{max(values)} - {min(values)}"
    else:
        raise ValueError(f"Unsupported operation: {operation}")

    return {
        "status": "ok",
        "answer": answer,
        "evidence": rows,
        "values": values,
        "formula": formula,
    }
```

Execution Feedback. The initial version handles regular tables and basic numerical operations. Some rollouts contain dictionary rows, OCR noise, currency symbols, percentages, or parenthesized negative values. These failures motivate the first revision.

Version 2: Heterogeneous Table Parsing.

Tool Description: `SKILL.md`.

Version 2: `SKILL.md`

```
---
name: table-evidence-calculator
description: Normalize heterogeneous OCR or visual table outputs and solve numerical questions with
    ↪ explicit evidence.
---

## Usage

### Scripts
```

```
- scripts/normalize_table.py: parse JSON, Markdown, CSV, or dictionary-based tables.
- scripts/plan_query.py: infer the operation and target column.
- scripts/execute_query.py: perform the calculation and return evidence.

### Parameters

- table_input (required): path to the extracted table.
- question (required): natural-language question.
- output_json (required): path for the result.
- operation (optional): numerical operation.
- column (optional): target column.

### Workflow

1. Convert different table formats into a common row representation.
2. Preserve raw cell text and normalize numeric expressions.
3. Infer the operation and identify the target column.
4. Execute the calculation.
5. Return raw evidence, normalized values, and the formula.

### Call Contract

- Dictionary rows and list rows must produce the same normalized representation.
- Numeric parsing supports commas, currency symbols, percentages, and parenthesized negatives.
- Values that cannot be parsed must be marked as missing.
- The tool must not silently discard parsing failures.

### When to call

Use this skill when table content comes from OCR or visual extraction.
```

Core Code: `scripts/normalize_table.py`.

Version 2: Core Code

```
import re

MISSING = {"", "-", "--", "n/a", "na", "null"}


def parse_number(value):
    text = str(value).strip().lower()
    if text in MISSING:
        return None

    negative = text.startswith("(") and text.endswith(")")
    text = text.strip("()").replace(",", "")
    text = re.sub(r"[$\u20ac\u00a3%]", "", text)
    text = re.sub(r"[^0-9.eE+-]", "", text)

    if not text:
        return None

    number = float(text)
    return -number if negative else number


def normalize_rows(headers, rows):
    if rows and isinstance(rows[0], dict):
        rows = [[row.get(header, "") for header in headers]
                for row in rows]

    return [{"raw": row,
             "values": [parse_number(cell) for cell in row]}
            for row in rows]
```

Execution Feedback. The second version handles heterogeneous formats and common OCR number patterns. Some questions still require selecting particular years, categories, or items before calculation. This motivates the second revision.

Version 3: Query Planning and Evidence Selection.

Tool Description: `SKILL.md`.

Version 3: `SKILL.md`

```
---
name: table-evidence-calculator
description: Select relevant rows and columns from extracted tables and execute verifiable multi-step
    ↪ calculations.
```

```
---

## Usage

### Scripts

- scripts/normalize_table.py: normalize table structure and numeric values.
- scripts/plan_query.py: construct an explicit query plan.
- scripts/select_evidence.py: resolve target rows and columns.
- scripts/execute_query.py: execute the planned calculation.

### Parameters

- table_input (required): path to the extracted table.
- question (required): natural-language question.
- operation (optional): count, sum, average, difference, ratio, or percent_change.
- target_rows (optional): row labels required by the question.
- column (optional): target numeric column.
- output_json (required): path for the result.

### Workflow

1. Normalize the extracted table while preserving raw cell text.
2. Parse the question into an operation, target rows, and target column.
3. Match requested rows and columns against the table structure.
4. Extract only the values required by the question.
5. Execute the calculation.
6. Return the selected evidence and calculation formula.

### Call Contract

- Row and column selection must happen before calculation.
- The order of selected rows is preserved for ratios and percentage changes.
- Multiple candidate matches are resolved using table context and question constraints.
- The result exposes every row and value used by the formula.

### When to call

Use this skill when a table question requires filtering by year, category, item, or region.
```

Core Code: `scripts/select_evidence.py`.

Version 3: Core Code

```
def resolve_rows(rows, target_rows, context=""):
    selected = []

    for target in target_rows:
        matches = [
            row for row in rows
            if target.lower() in row["raw"][0].lower()
        ]

        if len(matches) == 1:
            selected.append(matches[0])
            continue

        contextual = [
            row for row in matches
            if context.lower() in str(row["raw"]).lower()
        ]

        if len(contextual) == 1:
            selected.append(contextual[0])
        else:
            raise ValueError(f"Ambiguous row reference: {target}")

    return selected


def calculate(operation, values):
    if operation == "ratio":
        if len(values) != 2 or values[0] == 0:
            raise ValueError("ratio requires two values")
        return values[1] / values[0]

    if operation == "percent_change":
        if len(values) != 2 or values[0] == 0:
            raise ValueError("percent_change requires two values")
        return (values[1] - values[0]) / abs(values[0]) * 100

    if operation == "average":
        return sum(values) / len(values)
    if operation == "difference":
        return max(values) - min(values)
    if operation == "sum":
```

```
        return sum(values)
    if operation == "count":
        return len(values)

    raise ValueError(f"Unsupported operation: {operation}")
```

Execution Feedback. The third version supports row filtering and multi-step numerical operations. Some rollouts still contain hierarchical headers, repeated row labels, and incomplete cells. These observations motivate the third revision.

Version 4: Structure-Aware Evidence Resolution.

Tool Description: `SKILL.md`.

Version 4: `SKILL.md`

```
---
name: table-evidence-calculator
description: Resolve structured table evidence and execute numerical calculations across heterogeneous
    ↪ visual tables.
---

## Usage

### Scripts

- scripts/normalize_table.py: normalize OCR, Markdown, CSV, and JSON table outputs.
- scripts/plan_query.py: construct an explicit query plan.
- scripts/resolve_evidence.py: resolve grouped rows and hierarchical columns.
- scripts/validate_evidence.py: check evidence completeness and consistency.
- scripts/execute_query.py: execute the validated calculation.

### Parameters

- table_input (required): path to the extracted table.
- question (required): natural-language question.
- operation (optional): supported numerical operation.
- target_rows (optional): target row descriptions.
- column (optional): target column description.
- group (optional): row or column group constraint.
- output_json (required): path for the result.

### Workflow

1. Reconstruct rows, column groups, headers, and units.
2. Repair OCR noise and normalize numeric expressions.
3. Resolve rows and columns using semantics, groups, units, and question context.
4. Recover values from raw cells or valid table relations when possible.
5. Compare candidate evidence plans when multiple interpretations remain.
6. Execute the most strongly supported calculation.
7. Return the answer, evidence, assumptions, and confidence.

### Call Contract

- Repeated row labels are resolved using group, period, unit, and question context.
- Columns are matched by semantic meaning and numerical units.
- Missing values are never silently converted to zero.
- Unresolved values are reported as missing dependencies.
- status=uncertain is returned only when no unique computation remains.
- A successful result contains answer, evidence, values, and formula.
- An uncertain result contains candidate interpretations and unresolved evidence.

### When to call

Use this skill for heterogeneous visual table questions involving grouped headers, repeated labels, OCR
    ↪  noise, missing cells, or multi-step reasoning.
```

Core Code: `scripts/resolve_evidence.py`.

Version 4: Core Code

```
def resolve_candidates(rows, target, group=None, period=None):
    candidates = []

    for row in rows:
        row_text = " ".join(map(str, row["raw"])).lower()

        if target.lower() not in row_text:
            continue
        if group and group.lower() not in row_text:
```

```
            continue
        if period and period.lower() not in row_text:
            continue

        candidates.append(row)

    return candidates


def recover_value(cell, related_cells=None):
    value = parse_number(cell)
    if value is not None:
        return value

    if related_cells:
        recovered = [parse_number(item) for item in related_cells]
        recovered = [item for item in recovered if item is not None]
        if len(recovered) == 1:
            return recovered[0]

    return None


def build_result(rows, values, answer, formula, assumptions=None):
    if not rows:
        return {
            "status": "uncertain",
            "reason": "no evidence rows selected",
        }

    if any(value is None for value in values):
        return {
            "status": "uncertain",
            "reason": "required numeric evidence is missing",
            "candidate_evidence": rows,
            "values": values,
        }

    return {
        "status": "ok",
        "answer": answer,
        "evidence": rows,
        "values": values,
        "formula": formula,
        "assumptions": assumptions or [],
        "confidence": "supported",
    }
```

B.7 Reward Function Analysis

The Retrieve/Adapt reward provides the primary task objective, while the Decide and Forge rewards are applied within correctness-aware trajectories, and the Format reward regularizes parseability. We therefore keep the outcome reward fixed and ablate the three auxiliary rewards. As shown in Table 13, removing any auxiliary reward reduces accuracy, confirming that each component is useful in our evaluated settings. Removing the format reward causes the largest drop across nearly all datasets. This reward enforces valid tool-call syntax; without it, the model more often produces malformed calls that cannot be parsed or executed, blocking tool feedback for later decisions. Removing the Forge reward mainly hurts OOD datasets, with a large drop on tasks such as WebSight. These cases often contain clear tool gaps, showing that the Forge reward is important for encouraging on-demand tool forging. Removing the Decide reward causes the smallest drop, but the decline appears under both IID and OOD tool settings. This suggests that Decide supervision encourages concise calling paths and reduces redundant interaction rounds, which lowers the chance of intermediate errors.

B.8 Backbone Generalization Analysis

We train MetaForge on three backbones: Qwen2.5-VL-7B, Qwen3-VL-8B, and InternVL3.5-14B, covering architectures (QwenVL and InternVL) and scales (7B/8B/14B). As shown in Table 14, MetaForge brings gains across all backbones, indicating that it does not depend on specific architecture, scale, or pretraining strategy. Weaker backbones benefit more. InternVL3.5-14B has the lowest baseline ALL AVG (65.80/61.38), but improves to 85.54/84.69 after training, yielding the largest gain. The stronger Qwen3-VL-8B reaches the best overall performance of 88.14/88.98. These results demonstrate that adaptive tool call and online tool forging are backbone-agnostic. They compensate for the inherent limitations of different backbone models through tool interaction and forging.

Table 13: Ablation study of reward components under IID and OOD tool settings. ✓ and ✗ indicate the inclusion and removal of a reward component, respectively. We compare the full model with all four rewards against three variants, each removing one of r_{forge}, r_{fmt}, and r_{dec}.

Reward Components				IID Datasets							OOD Datasets							ALL
r_{ra}	r_{forge}	r_{fmt}	r_{dec}	DocVQA	TallyQA	OCRVQA	RoBUT	MapQA	Loc.Narr.	AVG.	ChartQA	AI2D	WebSight	MathVista	ScienceQA	CLEVR-M	AVG.	AVG.
w/ IID Tools																		
Qwen3-VL-8B (Bai et al., 2025a)				89.80	70.20	77.40	61.70	70.65	95.78	77.59	82.16	84.58	51.15	60.70	78.03	63.50	70.02	73.80
✓	✓	✓	✓	**97.90**	**80.52**	**86.51**	**87.36**	**77.98**	**99.62**	**88.32**	**90.49**	**89.60**	**98.34**	**78.01**	**89.68**	81.70	**87.97**	**88.14**
✓	✗	✓	✓	96.25	74.25	79.40	80.30	68.88	98.71	82.97	85.88	87.82	73.45	70.20	85.91	**82.00**	80.88	81.92
✓	✓	✗	✓	92.30	68.55	75.70	78.75	64.85	96.28	79.41	85.92	85.62	89.95	68.20	83.53	79.55	82.13	80.77
✓	✓	✓	✗	96.00	73.65	83.05	83.80	76.35	98.57	85.24	87.64	89.28	90.80	72.50	86.56	78.05	84.14	84.69
w/ OOD Tools																		
Qwen3-VL-8B (Bai et al., 2025a)				90.20	71.15	76.95	65.35	72.85	95.71	78.70	82.04	84.68	51.70	58.80	77.93	63.20	69.73	74.21
✓	✓	✓	✓	**97.22**	**81.17**	**86.00**	**87.67**	**89.14**	**99.58**	**90.13**	**90.18**	88.15	**98.72**	**79.78**	**89.73**	80.40	**87.83**	**88.98**
✓	✗	✓	✓	95.85	74.80	78.70	78.40	75.00	99.21	83.66	85.72	87.50	75.00	71.00	85.37	**81.00**	80.93	82.30
✓	✓	✗	✓	92.20	65.80	71.85	76.95	65.30	97.50	78.27	84.64	87.07	91.25	67.80	85.27	78.65	82.45	80.36
✓	✓	✓	✗	94.40	73.95	83.60	83.75	78.25	98.21	85.36	85.48	**89.50**	90.65	71.70	86.12	78.55	83.67	84.51

Table 14: Generalization across backbone multimodal models. MetaForge is applied to three backbones spanning two architecture families (QwenVL, InternVL) and different parameter scales.

Models (↓) / Datasets (→)	IID Datasets							OOD Datasets							ALL
	DocVQA	TallyQA	OCRVQA	RoBUT	MapQA	Loc.Narr.	AVG.	ChartQA	AI2D	WebSight	MathVista	ScienceQA	CLEVR-M	AVG.	AVG.
w/ IID Tools															
Qwen2.5-VL-7B (Bai et al., 2025b)	93.43	68.22	71.83	70.24	45.31	99.10	74.69	74.95	48.94	71.47	57.04	73.73	64.40	65.09	69.89
MetaForge	**95.80**	**75.85**	**82.75**	**82.35**	**87.15**	**99.21**	**87.19**	**84.36**	**87.24**	**96.20**	**64.30**	**83.83**	**78.15**	**82.35**	**84.77**
Qwen3-VL-8B (Bai et al., 2025a)	89.80	70.20	77.40	61.70	70.65	95.78	77.59	82.16	84.58	51.15	60.70	78.03	63.50	70.02	73.80
MetaForge	**97.90**	**80.52**	**86.51**	**87.36**	**77.98**	**99.62**	**88.32**	**90.49**	**89.60**	**98.34**	**78.01**	**89.68**	**81.70**	**87.97**	**88.14**
InternVL3.5-14B (Wang et al., 2025b)	87.60	71.18	66.46	69.98	59.20	72.27	71.12	80.83	67.08	44.00	35.07	69.06	66.88	60.49	65.80
MetaForge	**95.90**	**72.90**	**83.25**	**83.70**	**78.60**	**99.00**	**85.56**	**87.32**	**87.75**	**96.60**	**78.20**	**85.07**	**78.20**	**85.52**	**85.54**
w/ OOD Tools															
Qwen2.5-VL-7B (Bai et al., 2025b)	93.63	67.46	78.18	70.66	50.01	98.66	76.43	75.41	51.95	73.15	56.88	74.42	66.60	66.40	71.42
MetaForge	**95.45**	**76.75**	**83.10**	**82.90**	**87.00**	**99.35**	**87.43**	**84.56**	**89.24**	**96.00**	**64.10**	**84.38**	**79.40**	**82.95**	**85.19**
Qwen3-VL-8B (Bai et al., 2025a)	90.20	71.15	76.95	65.35	72.85	95.71	78.70	82.04	84.68	51.70	58.80	77.93	63.20	69.73	74.21
MetaForge	**97.22**	**81.17**	**86.00**	**87.67**	**89.14**	**99.58**	**90.13**	**90.18**	**88.15**	**98.72**	**79.78**	**89.73**	**80.40**	**87.83**	**88.98**
InternVL3.5-14B (Wang et al., 2025b)	88.20	63.85	59.10	59.26	53.90	70.64	65.83	74.44	63.47	39.50	29.90	65.34	68.95	56.93	61.38
MetaForge	**94.35**	**73.75**	**81.65**	**80.80**	**78.50**	**98.57**	**84.60**	**85.52**	**86.32**	**94.85**	**79.50**	**83.93**	**78.55**	**84.78**	**84.69**

Table 15: Task success rates (%) on the AI2-THOR single-agent subset of SpatialWorld. Parentheses show the number of successful tasks over the total.

Method	**Daily Life** $N = 219$	**Work and Study** $N = 41$	**Entertainment** $N = 40$	**Travel** $N = 11$	**Overall** $N = 311$
Qwen3-VL-8B Backbone	4.1 (9/219)	2.4 (1/41)	5.0 (2/40)	0.0 (0/11)	3.9 (12/311)
MetaForge	**9.1 (20/219)**	**9.8 (4/41)**	**12.5 (5/40)**	**9.1 (1/11)**	**9.6 (30/311)**

B.9 Interactive Environment Evaluation

Evaluation Environment. To evaluate MetaForge in dynamic interactive tasks, we experiment on SpatialWorld (Gao et al., 2026). SpatialWorld contains 760 tasks across eight simulated environments. The agent uses natural language instructions and first-person RGB screenshots to explore, navigate, and manipulate objects through sequential actions. Actions affect the environment state and produce subsequent visual observations. Task completion is automatically verified from the terminal state.

We evaluate the AI2-THOR single-agent subset of SpatialWorld. This subset provides diverse indoor scenes and rich object interactions. It contains 311 tasks across four scenarios: daily life, work and study, entertainment, and travel. We wrap actions from the unified interface as callable environment tools. These actions include `Move`, `Rotate`, `Tilt`, `ChangePosture`, `Pick`, `Place`, `ChangeState`, `Manipulate`, and `EndTask`. We also retain `create_skill` and `run_skill` to support tool forging and execution.

Experimental Setup. We directly evaluate the existing MetaForge model trained with GRPO. Following the SpatialWorld evaluation protocol, we set the sampling temperature to 1.0 and retain the most recent 30 interaction turns. Each task allows at most $2g + 10$ steps, where g denotes the number of actions in the human-annotated reference trajectory. The Qwen3-VL-8B backbone and MetaForge share the same action space, task instructions, and step budget. We report task success rate (TSR) for each scenario and across all tasks.

Results Analysis. Table 15 shows that MetaForge achieves higher task success rates across all four scenarios. It completes more tasks under the same action space and step budget. Environment states change with actions, so subsequent decisions depend on current visual observations and interaction history. Multi-turn GRPO optimizes action selection and parameter adaptation across successive tool calls. This training enables MetaForge's orchestration policy to incorporate environmental feedback into subsequent actions. These results show that the learned tool orchestration policy transfers to dynamic environments and supports multi-step task execution across different scenarios.

B.10 Tool Usage Entropy Analysis

To compare tool selection, we report call distributions and per-dataset TUE over 12 datasets (Figures 5 and 6). Distributions are grouped into Model tools, Executable tools, and Forged tools.

Existing methods show three patterns. First, some methods over-invoke tools. PyVision-Image-7B-RL and DeepEyesV2-7B make thousands to tens of thousands of calls per dataset, with TUE around 3.5–4.0. This suggests that they compensate for weak selection by trying many tools rather than choosing a concise combination. Second, some methods underuse external tools. R1-Onevision-7B issues only single-digit calls on most datasets, indicating limited ability or tendency to use the available tool pool. Third, some methods are biased toward tool categories. TikArt-8B and ZwZ-8B reach low TUE on some IID datasets (0.1–0.5), but their TUE rises to 2.6–3.2 on WebSight and MathVista, with overall TUE of 2.7–3.5. This indicates partial task differentiation, but not a stable orchestration strategy across tasks.

In contrast, MetaForge shows task-adaptive tool orchestration under both IID and OOD tool settings. Under IID tools (Figure 5), calls on 11 datasets are dominated by Model tools, suggesting that the policy recognizes their broad coverage in this setting. WebSight is the exception: forged-tool calls dominate because the existing tools lack the required website-generation function, so the model forges task-specific tools. Under OOD tools (Figure 6), the pattern changes. Executable tools increase on ChartQA, WebSight, and MathVista, showing that the policy can use newly available executable tools when they better match the task. Forged-tool calls nearly disappear, indicating that the expanded OOD tool set already covers most needs. Claude-Sonnet-4-6 also obtains relatively low TUE (IID 1.81, OOD 1.63), but it remains Model-dominant in both settings, suggesting focused selection without the same adaptive shift across tool settings.

These results align with MetaForge's design. The unified tool interface places Model tools, Executable tools, and Forged tools in one action space. Multi-turn GRPO optimizes the policy to retrieve, adapt, forge, and reuse tools according to task needs. Online tool forging expands the tool pool when existing tools are insufficient. Capacity-constrained tool pool management deduplicates overlapping forged tools and retains high-value ones. Together, these mechanisms lead to a compact and task-sensitive tool selection strategy.

B.11 Analysis of Tool Invocation Success Rates

To thoroughly assess invocation robustness across different task scenarios and tool configurations, we report per-dataset tool call success rates for each model and conduct a comparative analysis under both the IID and OOD tool settings. Under the IID tool setting, per-dataset tool call success rates reveal significant stratification among models. Existing baselines span a wide range of overall success rates, from below 50% (e.g., R1-Onevision-7B at 47.6%) to around 90%. Most baselines exhibit large cross-dataset fluctuations, with some dropping to 0% on specific datasets.

Under the OOD tool setting, most baselines exhibit performance shifts between the two tool sets: some degrade substantially (e.g., VTool-R1-7B drops from 72.1% to 58.5%), while others improve (e.g., Qwen2.5-VL-7B rises from 46.5% to 66.2%). This sensitivity to tool set composition exposes the lack of robust tool generalization in existing methods. MetaForge never encounters the OOD tools during training, yet its success rate improves from 96.6% to 98.2%. All 12 datasets exceed 84.6%, and 9 of them surpass 98%. The result of our experiments indicates that MetaForge learns general-purpose tool orchestration rather than memorizing specific tool configurations. The unified tool interface enables flexible dispatch of unfamiliar tools based on functional descriptions. Furthermore, online tool forging enables the model to forge task-specific tools on demand, effectively compensating for



Figure 5: Tool call distribution and per-dataset Tool Usage Entropy (TUE) for each model under the IID tool setting.




Figure 6: Tool call distribution and per-dataset Tool Usage Entropy (TUE) for each model under the OOD tool setting.

the limitations of the predefined tool set. Together, these components support consistently high tool call success rates under the evaluated IID and OOD tool settings.




Figure 7: Per-dataset tool call success rates for each model under the IID tool setting. Existing baselines exhibit large cross-dataset variance, with some dropping to near 0% on specific datasets. MetaForge achieves at least 87% on all 12 datasets and exhibits the smallest cross-dataset variance.

B.12 Error Pattern Analysis

To investigate root causes of invocation failures across methods, we categorize 11 error types into three groups: (1) **Hallucination errors**, including `unknown_skill` (invoking a non-existent forged tool), `missing_entrypoint` (invoking a non-existent script within a forged tool, where the model fabricates script names without consulting the tool description), and `invalid_entrypoint` (specifying a non-compliant script entry point, as only `.py` and `.sh` formats are supported), reflecting poor awareness of the available tool pool; (2) **Parameter errors**, including `invalid_parameters` / `invalid_arguments` (passing invalid values), `missing_parameters` (omitting required parameters), and `missing_image_index` / `invalid_image_index` (missing or out-of-range image indices), reflecting a limited understanding of tool interface specifications; (3) **Execution errors**, including `runtime_error` (internal script execution failure, typically due to missing internal arguments), `request_failed` (external service exceptions such as network instability), and `timeout` (subprocess execution timeout), which arise from environmental factors or forged-tool code quality rather than model behavior defects.

As shown in the figure, the majority of existing methods concentrate their failures on hallucination and parameter errors. PyVision-Image-7B-RL produces over 41K failed calls under the IID




Figure 8: Per-dataset tool call success rates for each model under the OOD tool setting. Most baselines show notable performance shifts between the two tool sets, whereas MetaForge improves from an overall 96.6% (IID) to 98.2% (OOD), with all datasets exceeding 84.6%.

setting, with `invalid_parameters` alone accounting for 19,785 instances, indicating a severe lack of understanding of tool parameter formats. DeepEyesV2-7B accumulates over 21K failures, with `missing_entrypoint` reaching 7,610, revealing frequent hallucinated invocations of non-existent scripts within forged tools. R1-Onevision-7B exhibits the most severe dysfunction, issuing only 231 calls in total with a success rate of merely 47.62%. Of its failed calls, `unknown_skill` alone accounts for 59 instances, suggesting that the model lacks the basic ability to recognize and select from the available tool pool. Under the OOD setting, `unknown_skill` errors increase substantially for most methods (VTool rises from 472 to 1,096; PixelReasoner rises from 607 to 1,424), indicating that methods trained on fixed tool sets lack generalization to unseen tools.

MetaForge achieves the highest overall success rates of 96.59% (IID) and 98.24% (OOD) among all methods in our evaluation. The errors consist primarily of `runtime_error` (515 instances, concentrated on WebSight forged-tool code execution anomalies) and `invalid_image_index` (357/411 instances, concentrated on ScienceQA image index handling). These failures reflect runtime and benchmark-interface alignment issues rather than general tool-understanding failures under the tested settings. More importantly, hallucination errors (`missing_entrypoint` + `unknown_skill`) total only 14 and 9 under IID and OOD, respectively, suggesting improved awareness of the available tool pool under the unified interface and multi-turn GRPO training. Notably, Claude-Sonnet-4-6, serving as the closed-source upper bound, concentrates its errors almost exclusively on `request_failed` (915 under IID, 1,293 under OOD), which stem from external API service instability rather than any deficiency in tool understanding. This further corroborates that once a model acquires robust tool understanding, the dominant failure mode shifts from model-intrinsic deficits (e.g., hallucinated invocations and parameter misspecification) to external execution conditions beyond the model's control.




Figure 9: Distribution of error types across models under IID (left) and OOD (right) tool settings. Errors are categorized into Hallucination (e.g., invoking non-existent tools), Parameter (e.g., missing or invalid arguments), and Execution (e.g., runtime exceptions) errors. MetaForge produces the fewest total errors, with residual failures mainly associated with runtime robustness and benchmark-interface alignment rather than hallucinated tool use.

B.13 Joint Sensitivity Analysis of Learning Rate and Format Reward

The actor learning rate and the format reward magnitude are two key hyperparameters that jointly govern training dynamics. The learning rate controls the step size of policy gradient updates, while the format reward magnitude determines how strongly the model is penalized or rewarded for syntactic compliance in tool calls. On this validation set, we evaluate 25 combinations of five learning rates and five format reward magnitudes under both IID and OOD tool settings. Each configuration is independently evaluated over 50 runs, and we report the mean accuracy. We select a learning rate of 3×10^{-6} and a format reward magnitude of 0.2 based on the results.

Table 16: Joint sensitivity analysis of learning rate and format reward magnitude on the 2,400-example validation set. Each configuration is independently evaluated over 50 runs. We vary the learning rate from 1e-6 to 5e-6 and the format reward magnitude α from 0.1 to 0.5, yielding 25 configurations. We report validation accuracy (%) across all 12 evaluation datasets under IID and OOD tool settings. **Bold** and underline indicate the best and second-best results in each column within each tool setting.

lr	α	IID Datasets							OOD Datasets							ALL
		DocVQA	TallyQA	OCRVQA	RoBUT	MapQA	Loc.Narr.	AVG.	ChartQA	AI2D	WebSight	MathVista	ScienceQA	CLEVR-M	AVG.	AVG.
w/ IID Tools																
1e-6	0.1	94.81	75.59	81.86	82.13	71.61	97.69	83.95	85.81	85.35	89.58	70.92	84.90	75.03	81.93	82.94
	0.2	95.43	76.84	82.73	83.14	73.42	98.17	84.96	86.72	86.37	91.24	72.43	86.14	76.85	83.29	84.12
	0.3	95.23	76.19	82.14	82.62	72.66	97.91	84.46	86.10	85.92	90.24	71.53	85.47	75.75	82.50	83.48
	0.4	94.42	75.24	81.58	81.46	71.79	97.66	83.69	85.35	85.07	89.31	70.24	84.94	74.48	81.57	82.63
	0.5	94.25	73.75	80.25	80.65	70.08	97.40	82.73	83.86	83.60	86.72	67.28	83.57	73.85	79.81	81.27
2e-6	0.1	96.44	77.75	84.54	85.43	76.90	98.89	86.66	88.04	87.72	95.74	75.19	87.43	80.69	85.80	86.23
	0.2	97.12	79.34	85.63	86.28	78.42	99.28	87.68	89.57	88.93	97.48	76.84	88.92	82.34	87.35	87.51
	0.3	96.99	78.96	85.43	86.05	78.13	99.21	87.46	89.35	88.77	96.95	76.39	88.67	81.97	87.02	87.24
	0.4	96.62	78.27	84.69	85.16	77.44	98.91	86.85	88.54	87.85	95.89	74.94	87.89	80.84	85.99	86.42
	0.5	95.60	77.50	83.56	84.14	74.26	98.55	85.60	87.26	86.81	93.31	73.12	87.89	79.67	84.68	85.14
3e-6	0.1	97.23	78.84	85.44	85.43	75.80	99.29	87.01	89.06	88.50	95.70	76.31	88.66	80.27	86.42	86.71
	0.2	**97.85**	**80.73**	**86.71**	**88.36**	**79.96**	**99.65**	**88.88**	**91.95**	**90.62**	**98.98**	**80.25**	**92.46**	**84.75**	**89.84**	**89.36**
	0.3	97.62	80.09	86.08	86.88	77.54	99.45	87.94	90.11	89.28	97.55	77.37	89.42	81.13	87.48	87.71
	0.4	97.35	79.20	85.56	85.99	76.72	99.24	87.34	89.29	88.63	95.66	76.51	88.82	80.18	86.52	86.93
	0.5	96.74	78.25	84.48	85.69	74.70	99.16	86.50	88.78	88.15	95.02	74.68	87.91	78.69	85.54	86.02
4e-6	0.1	96.31	77.92	84.32	84.63	74.87	98.88	86.15	88.10	87.14	95.70	74.32	87.34	78.01	85.10	85.63
	0.2	97.04	79.17	85.27	86.14	76.73	99.14	87.25	89.47	88.34	97.06	76.42	88.13	79.83	86.54	86.90
	0.3	96.85	78.77	84.96	85.88	76.38	99.05	86.98	89.17	88.04	96.45	75.68	87.71	79.53	86.10	86.54
	0.4	96.49	78.01	84.59	85.10	74.93	98.90	86.34	88.47	87.19	95.55	74.53	87.42	78.18	85.22	85.78
	0.5	95.95	77.66	82.82	84.45	73.46	98.40	85.46	86.58	86.55	92.49	73.15	86.06	76.78	83.60	84.53
5e-6	0.1	96.03	77.59	83.87	84.98	73.71	98.37	85.76	87.77	86.49	94.78	73.02	86.86	77.50	84.40	85.08
	0.2	96.84	78.93	84.87	85.72	75.63	98.84	86.81	88.94	87.83	96.43	75.24	87.63	78.93	85.83	86.32
	0.3	96.59	78.25	84.40	85.28	75.01	98.79	86.39	88.29	87.39	95.31	74.17	87.18	78.21	85.09	85.74
	0.4	96.31	77.79	83.66	84.51	73.09	98.62	85.66	87.84	86.89	94.16	73.36	86.76	77.26	84.38	85.02
	0.5	95.45	76.54	83.18	83.31	72.18	98.34	84.83	86.65	86.35	91.16	71.87	85.86	76.15	83.01	83.92
w/ OOD Tools																
1e-6	0.1	93.75	75.64	81.24	82.32	82.75	97.29	85.50	84.55	84.36	90.76	71.81	84.46	74.50	81.74	83.62
	0.2	94.82	77.23	82.37	83.54	84.28	97.83	86.68	86.42	85.74	93.47	74.38	85.83	76.12	83.66	85.17
	0.3	94.59	76.70	82.01	83.03	83.75	97.77	86.31	85.96	85.31	92.90	73.55	85.53	75.67	83.15	84.73
	0.4	94.37	76.15	81.19	82.25	82.60	97.36	85.65	85.36	84.43	91.33	71.71	84.72	74.61	82.03	83.84
	0.5	93.28	75.15	80.28	80.85	81.06	97.07	84.62	84.11	83.80	90.24	71.23	83.10	73.19	80.95	82.78
2e-6	0.1	95.83	78.60	83.94	85.57	87.18	98.79	88.32	87.76	86.68	94.86	77.96	87.60	77.32	85.36	86.84
	0.2	96.53	80.28	85.24	86.83	89.47	99.21	89.59	89.43	87.62	97.84	80.14	88.94	79.52	87.25	88.42
	0.3	96.32	79.86	84.95	86.47	88.93	99.10	89.27	89.11	87.24	97.30	79.52	88.56	78.99	86.79	88.03
	0.4	96.18	78.95	84.58	85.67	88.58	98.92	88.81	88.65	86.79	96.43	78.33	88.10	78.57	86.15	87.48
	0.5	95.26	77.64	83.22	84.46	86.97	98.59	87.69	87.44	85.98	94.03	76.42	87.08	76.95	84.65	86.17
3e-6	0.1	96.43	79.61	84.08	86.19	87.37	99.00	88.78	89.01	86.68	96.64	75.80	88.40	77.82	85.73	87.25
	0.2	**98.28**	**83.53**	**88.29**	**89.74**	**90.52**	**99.71**	**91.68**	**91.24**	**89.66**	**99.21**	**81.78**	**93.37**	**85.43**	**90.12**	**90.90**
	0.3	96.95	80.59	85.52	87.06	88.45	99.39	89.66	89.61	87.72	97.97	78.69	89.40	79.68	87.18	88.42
	0.4	96.80	80.12	84.77	86.83	87.57	99.23	89.22	89.46	87.40	96.50	78.03	89.01	78.86	86.54	87.88
	0.5	96.41	78.92	84.13	85.40	86.50	99.07	88.40	88.15	86.38	95.72	76.49	88.13	77.26	85.36	86.88
4e-6	0.1	95.70	78.66	83.50	85.36	85.59	98.59	87.90	87.94	85.56	94.54	75.39	86.93	76.40	84.46	86.18
	0.2	96.38	79.84	84.72	86.34	87.82	99.04	89.02	89.17	87.04	97.42	77.83	88.42	78.84	86.45	87.74
	0.3	96.13	79.48	84.42	85.85	87.19	98.96	88.67	88.62	86.62	96.51	77.12	88.14	78.21	85.87	87.27
	0.4	95.61	78.46	83.74	85.24	85.86	98.56	87.91	88.36	86.03	95.73	75.78	87.65	77.23	85.13	86.52
	0.5	95.39	77.95	83.05	84.86	83.98	98.51	87.29	87.33	84.91	93.48	73.75	85.73	75.13	83.39	85.34
5e-6	0.1	94.87	77.87	82.36	84.11	84.38	98.17	86.96	86.79	85.57	94.15	75.36	86.49	76.23	84.10	85.53
	0.2	96.13	79.43	84.18	85.82	86.73	98.74	88.51	88.53	86.47	96.84	76.93	87.82	78.23	85.80	87.15
	0.3	95.87	79.08	83.62	85.42	85.97	98.58	88.09	88.13	85.87	96.11	75.98	87.39	77.67	85.19	86.64
	0.4	95.24	78.09	83.24	84.51	85.02	98.24	87.39	87.19	85.57	94.74	74.81	86.73	76.58	84.27	85.83
	0.5	95.25	76.39	82.13	83.70	83.16	98.48	86.52	86.49	84.73	91.95	72.87	85.93	75.68	82.94	84.73

As shown in Table 16, the combination of lr=3e-6 and α=0.2 achieves the highest overall validation accuracy under both tool settings (IID: 89.36%, OOD: 90.90%). Observations emerge from the grid. First, for any fixed format reward magnitude, lr=3e-6 consistently yields the best or near-best accuracy, confirming it as the optimal learning rate across a range of format reward strengths. Second, for any fixed learning rate, α=0.2 consistently outperforms other magnitudes, indicating that a moderate format penalty provides the best balance between syntactic compliance and behavioral flexibility. Third, the two hyperparameters exhibit a mild interaction effect: at lower learning rates (e.g., 1e-6), performance is insensitive to α because the small policy updates limit the influence of any individual reward signal; at higher learning rates (e.g., 5e-6), choice of α becomes more consequential, as large policy updates amplify the impact of the format reward, and an overly strong penalty ($\alpha \geq 0.4$) combined with aggressive optimization leads to performance degradation.

B.14 CASE STUDY

To more intuitively demonstrate the advantages of MetaForge, we select six representative cases from the evaluation set and compare it against three types of baselines: the base model (Qwen3-VL-8B), a tool-augmented model (TikArt-8B), and a closed-source model (Claude-Sonnet-4-6). These cases are organized into three categories: (1) **Type A**: only MetaForge answers correctly while all three baselines fail, demonstrating superior accuracy through adaptive tool orchestration; (2) **Type B**: all models answer correctly but MetaForge requires significantly fewer interaction turns, demonstrating its ability to achieve an optimal trade-off between accuracy and inference cost through the Decide reward; and (3) **Type C**: MetaForge recognizes missing capabilities, forges validated task-specific tools online, and directly grounds the final answer in forged-tool outputs, while baselines either fail to identify the gap or create ineffective tools.

Type A: MetaForge Achieves Higher Accuracy via Adaptive Tool Orchestration. Case A1 is a ChartQA sample evaluated under the OOD dataset and OOD tool setting, requiring extraction of a numerical difference from a bar chart (ground truth: 52). MetaForge completes the task in 4 turns by orchestrating three tools: it first calls ChartMoe to extract the PET bottle collection rates, recognizes that the returned country names do not match the chart, then switches to the suitable tool InternVL3.5-14B-Instruct for re-extraction, and finally invokes `python_code` to compute the difference. This illustrates a behavior acquired through training: the ability to detect tool failure from observations and adaptively switch to suitable tools. In contrast, Qwen3-VL-8B calls UniChart, then `python_code`, but computes from incorrect values. TikArt-8B attempts to solve the problem using only `python_code`. Claude-Sonnet-4-6 submits an answer directly without invoking tools, producing an incorrect result.

Case A2 is a MathVista sample evaluated under the OOD dataset and OOD tool setting, requiring computation of the average between the longest light-blue bar and the shortest gray bar in a chart (ground truth: 273). MetaForge decomposes the task into two stages: it first calls UniChart to focus on the relevant light-blue and gray bars, then interprets the chart context to identify their values as 415 and 131, and finally invokes `python_code` to compute their mean, yielding the correct answer. In contrast, Qwen3-VL-8B attempts to answer without tool usage and misidentifies the bar values, producing an incorrect result; TikArt-8B uses `python_code` for computation but operates on incorrect values, also getting the wrong answer; and Claude-Sonnet-4-6 answers directly without tool invocation, producing an incorrect result. These cases demonstrate that multi-turn GRPO training enables MetaForge to combine tool-guided chart localization with symbolic computation, yielding higher task accuracy.

Type B: Optimizing Accuracy-Efficiency Trade-off via Decide Reward. Case B1 is a MathVista sample evaluated under the OOD dataset and OOD tool setting, requiring identification of the accuracy difference between the most and least accurate algorithms in a bar chart (ground truth: 80). MetaForge solves it in just 2 turns by directly calling InternVL3.5-14B-Instruct, which accurately extracts all four bar values in a single invocation, enabling immediate answer computation. In comparison, Qwen3-VL-8B requires 4 turns, sequentially trying UniChart, Deplot, and ChartMoe before obtaining usable values; TikArt-8B requires 5 turns, calling UniChart twice, then Deplot and `python_code`; Claude-Sonnet-4-6 requires 3 turns, first calling ChartMoe and then cross-validating with InternVL3.5-14B-Instruct before computing the answer.


Case B2 is a CLEVR-Math sample evaluated under OOD dataset and OOD tool setting, asking how many cylinders remain after subtracting the cyan ones (ground truth: 2). MetaForge completes the task in 2 turns with one call to InternVL3.5-14B-Instruct, which counts cylinders and identifies the cyan one. Qwen3-VL-8B requires 3 turns, calling InternVL3.5-14B-Instruct twice with redundant queries. Claude-Sonnet-4-6 requires 3 turns, querying InternVL3.5-14B-Instruct twice. The first call returns an imprecise description, while the second uses a more targeted prompt to obtain the cylinder count and colors. TikArt-8B shows inefficient behavior and consumes 10 interaction turns. It retrieves and attempts to execute four forged tools. Each tool requires reading documentation, preparing arguments, and executing scripts before the model falls back to InternVL3.5-14B-Instruct. These cases demonstrate that the Decide reward within the GRPO objective incentivizes the model to converge on the most informative tool in fewer steps, resulting in a Pareto-superior trade-off between accuracy and efficiency compared to baselines that rely on exhaustive enumeration or redundant invocations.

Type C: Successful Tool Forging for Missing Capabilities. Cases C1 and C2 show how MetaForge handles WebSight-style screenshot-to-HTML tasks under the OOD dataset and IID tool settings, where the predefined tools can describe visual content but cannot directly generate HTML. MetaForge first identifies this capability gap, then invokes `create_skill`, validates the generated tool, runs it with `run_skill`, and uses the returned HTML to produce the final answer. In C1, MetaForge forges `screenshot-layout-html-builder` for a company webpage and executes it through `run_skill`. The returned HTML preserves the original heading, three introductory paragraphs, and copyright footer, together with the corresponding page structure and layout. MetaForge then uses this tool output as its final answer. In C2, MetaForge forges `form-aware-screenshot-html` for a healthcare-provider page; the tool reconstructs the navigation bar, content sections, contact information, input fields, textarea, and submit button. These cases illustrate that MetaForge can extend the tool pool with executable task-specific tools when existing tools are insufficient.

In contrast, all three baselines fail in both cases. In Case C1, all three baselines produce HTML that deviates from the reference page. Qwen3-VL-8B introduces navigation links and omits the copyright footer. TikArt-8B adds sections and a contact form that are absent from the reference. Claude-Sonnet-4-6 introduces an additional image and navigation elements, and replaces the copyright footer with contact information. These outputs change the page content or structure rather than simply expressing the same page through different HTML syntax. In contrast, MetaForge's tool output preserves the reference heading, all three introductory paragraphs, and the copyright footer without introducing unrelated elements. Its final answer reproduces the HTML returned by the forged tool. This case illustrates a successful tool-creation and execution workflow that produces a faithful page reconstruction, compared with the unsuccessful reconstructions shown by the three baselines. In Case C2, all three baselines also attempt to forge tools, but their forged tools either time out during execution (Claude-Sonnet-4-6) or produce HTML that fails to match the target layout (Qwen3-VL-8B and TikArt-8B). This highlights a distinctive feature of MetaForge: the policy learns when to trigger tool forging, and the two-stage generation plus validation pipeline filters for forged tools that can be executed and used in successful task trajectories. The Forge reward couples successful forged-tool creation/reuse with final task correctness, encouraging the policy to rely on forged tools only when they contribute to solving the task.

Together, these categories illustrate complementary strengths of MetaForge: Type A cases show that multi-turn GRPO training enables adaptive tool orchestration that recovers from failures and improves accuracy; Type B cases show that the Decide reward guides MetaForge to achieve an optimal accuracy-efficiency trade-off, reducing unnecessary exploration and lowering inference cost; and Type C cases show that online tool forging can extend the tool pool beyond the predefined set, while validation and correctness-aware training encourage forged tools that are not only executable but also useful for downstream tasks.

Case A1: ChartQA (OOD Dataset, OOD Tools)



Question: What is the difference between the highest and the lowest PET bottles collection rate in the European countries?

Ground Truth: 52

MetaForge (✓ Correct) – 4 turns

```
<thinking> I need to identify the highest and lowest PET bottles collection rates from
     ↪ the bar chart and calculate their difference. The chart displays collection and
     ↪ recycling rates for different European countries with PET bottles collection rate
     ↪ represented by grey bars. I will first extract the values for the grey bars for
     ↪ each country, then find the maximum and minimum values to compute the difference
     ↪ .</thinking>
<tool_call>
{"name": "ChartMoe", "arguments": {"image_index": 1, "prompt": "Extract the values for
     ↪ PET bottles collection rate (grey bars) for each country from the chart."}}
</tool_call>
----- [Observation] -----
[Tool: ChartMoe] {"success": true, "data": {"result": "The values for PET bottles
     ↪ collection rate are as follows: \n\n- Canada: 91%\n- Germany: 92%\n- Japan: 94%\n-
     ↪  South Korea: 95%\n- United States: 92%[UNUSED_TOKEN_145]"}, "error": null}
----- [Assistant Response] -----
<thinking> The tool returned values that seem to pertain to countries like Canada,
     ↪ Germany, Japan, South Korea, and the United States, which are not the European
     ↪ countries I am focusing on. This indicates an error in the extraction or
     ↪ misalignment with my query. I need to re-examine the chart to accurately extract
     ↪ the PET bottles collection rates for France, Germany, UK, Spain, and Italy based
     ↪ on the grey bars, since these are the relevant European countries for this
     ↪ question.</thinking>
<tool_call>
{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Extract the PET bottles
     ↪ collection rate (grey bars) for each European country listed in the chart: France,
     ↪  Germany, UK, Spain, and Italy.", "image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] Here are the PET bottles collection rates for each
     ↪ European country listed in the chart:

- France: 56%
- Germany: 94%
- UK: 53%
- Spain: 60%
- Italy: 42%
----- [Assistant Response] -----
<thinking> I have successfully extracted the PET bottles collection rates for all
     ↪ relevant European countries. The highest rate is 94% (Germany) and the lowest rate
     ↪  is 42% (Italy). I will now calculate the difference between these two values to
     ↪ answer the question.</thinking>
<tool_call>
{"name": "python_code", "arguments": {"code": "highest_rate = 94\nlowest_rate = 42\
     ↪ ndifference = highest_rate - lowest_rate\ndifference"}}
</tool_call>
----- [Observation] -----
52
----- [Assistant Response] -----
```

✓ **CORRECT**

```
<answer>The difference between the highest and the lowest PET bottles collection rate in
    ↪ the European countries is 52 percentage points.</answer>
```

Qwen3-VL-8B (× Incorrect) – 3 turns

```
<thinking>
The chart provided shows PET bottles collection rates for various European countries. I
    ↪ need to identify the highest and lowest collection rates and calculate their
    ↪ difference. Since this is a straightforward data extraction and calculation task,
    ↪ I can use the 'UniChart' tool to interpret the chart and extract the necessary
    ↪ values.

Step 1: Use 'UniChart' to extract the PET bottles collection rates for each country from
    ↪ the chart.

Step 2: Identify the highest and lowest values among these rates.

Step 3: Calculate the difference between the highest and lowest values.

I will start by using the 'UniChart' tool to understand the chart and extract the
    ↪ required data.
</thinking>
<tool_call>
{"name": "UniChart", "arguments": {"image_index": 1, "prompt": "Extract the PET bottles
    ↪ collection rate for each country from the chart."}}
</tool_call>
----- [Observation] -----
[Tool: UniChart] {"success": true, "data": {"result": "Extract the PET bottles collection
    ↪  rate for each country from the chart."}, "error": null}
----- [Assistant Response] -----
<thinking>
The 'UniChart' tool successfully extracted the PET bottles collection rates for each
    ↪ country. Now, I will identify the highest and lowest values from the extracted
    ↪ data and calculate the difference.

Step 1: Identify the highest PET bottles collection rate.

Step 2: Identify the lowest PET bottles collection rate.

Step 3: Calculate the difference between the highest and lowest rates.

I will now proceed with these steps.
</thinking>
<tool_call>
{"name": "python_code", "arguments": {"code": "rates = [56, 94, 53, 60, 55]\n\
    ↪ nhighest_rate = max(rates)\nlowest_rate = min(rates)\ndifference = highest_rate -
    ↪ lowest_rate\n\ndifference"}}
</tool_call>
----- [Observation] -----
41
----- [Assistant Response] -----
```

× **INCORRECT**

```
<answer>
The difference between the highest and the lowest PET bottles collection rate in the
    ↪ European countries is 41 percentage points.
</answer>
```

TikArt-8B (× Incorrect) – 2 turns

```
<thinking>
To determine the difference between the highest and the lowest PET bottles collection
    ↪ rate in the European countries shown in the chart, I will first identify the
    ↪ highest and lowest values for the PET bottles collection rate (represented by the
    ↪ gray bars) from the chart. Once I have those values, I will subtract the lowest
    ↪ from the highest to find the difference.


The highest PET bottles collection rate can be observed as 94% (Germany), and the lowest
    ↪ is 21% (France). The difference can be calculated as 94% - 21%.
</thinking>
<tool_call>{"name": "python_code", "arguments": {"code": "highest_rate = 94\nlowest_rate
    ↪ = 21\ndifference = highest_rate - lowest_rate\ndifference"}}
</tool_call>
```

```
----- [Observation] -----
73
----- [Assistant Response] -----
```
× **INCORRECT**
```
<answer>
The difference between the highest and the lowest PET bottles collection rate in the
    ↪ European countries is 73 percentage points.
</answer>
```

Claude-Sonnet-4-6 (× Incorrect) – 1 turns

```
<thinking>From the bar chart, I can identify the PET bottles collection rates for each
    ↪ country: France (56%), Germany (94%), UK (53%), Spain (60%), and Italy (55%). The
    ↪ highest rate is 94% (Germany), and the lowest is 53% (UK). The difference between
    ↪ them is 94% - 53% = 41%.</thinking>
```
× **INCORRECT**
```
<answer>41%</answer>
```

Case A2: MathVista (OOD Dataset, OOD Tools)



Question: Hint: Please answer the question requiring an integer answer and provide the final value, e.g., 1, 2, 3, at the end. Question: What is the average of longest light blue bar and shortest gray bar?

Ground Truth: 273

MetaForge (✓ Correct) – 3 turns

```
<thinking> I need to identify the longest light blue bar and the shortest gray bar from
    ↪ the bar chart. The light blue bar corresponds to the year 2012. I will find the
    ↪ value of the longest light blue bar and the shortest gray bar, then calculate
    ↪ their average. </thinking>
<tool_call>
{"name": "UniChart", "arguments": {"image_index": 1, "prompt": "Extract the values for
    ↪ the longest light blue bar and the shortest gray bar from the bar chart."}}
</tool_call>
----- [Observation] -----
[Tool: UniChart] {"success": true, "data": {"result": "Extract the values for the longest
    ↪  light blue bar and the shortest gray bar from the bar chart. The shortest lighter
    ↪  lighter lighter lighter lighter lighter lighter lights is from 2012 to 2014"}, "
    ↪ error": null}
----- [Assistant Response] -----
<thinking> The tool returned values for the light blue bar (2012) and gray bar (2014).
    ↪ The longest light blue bar is 415 (for 2012), and the shortest gray bar is 131 (
    ↪ for 2014). I will compute the average of these two values. </thinking>
<tool_call>
{"name": "python_code", "arguments": {"code": "average = (415 + 131) / 2\naverage"}}
</tool_call>
----- [Observation] -----
273.0
----- [Assistant Response] -----
```

```
<thinking> The average of the longest light blue bar (415) and the shortest gray bar (131)
    ↪  is 273.0. The question asks for an integer answer, so I will round it to the
    ↪ nearest whole number. </thinking>
```
✓ **CORRECT**
```
<answer>273</answer>
```

Qwen3-VL-8B (× Incorrect) – 1 turns

```
<thinking>
I need to find the average of the longest light blue bar and the shortest gray bar from
    ↪ the provided bar chart.

- The longest light blue bar corresponds to "Solved homicides" in 2012, with a value of
    ↪ 415.
- The shortest gray bar corresponds to "Unsolved homicides" in 2013, with a value of 106.

To calculate the average, I'll add these two values and divide by 2.

Average = (415 + 106) / 2 = 521 / 2 = 260.5

Since the question asks for an integer answer, I need to round to the nearest whole
    ↪ number, which is 261.

</thinking>
```
× **INCORRECT**
```
<answer>261</answer>
```


TikArt-8B (× Incorrect) – 2 turns

```
<thinking>First, I need to identify the values of the longest light blue bar and the
    ↪ shortest gray bar from the chart. The longest light blue bar corresponds to the
    ↪ year 2012 under "Solved homicides," which has a value of 415. The shortest gray
    ↪ bar corresponds to the year 2013 under "Unsolved homicides," which has a value of
    ↪ 106. Next, I will calculate the average of these two values by adding them
    ↪ together and dividing by 2.</thinking>
<tool_call>{"name": "python_code", "arguments": {"code": "longest_light_blue = 415\
    ↪ nshortest_gray = 106\naverage = (longest_light_blue + shortest_gray) / 2\naverage
    ↪ "}}
</tool_call>
----- [Observation] -----
260.5
----- [Assistant Response] -----
```
× **INCORRECT**
```
<answer>260</answer>
```

Claude-Sonnet-4-6 (× Incorrect) – 1 turns

```
<thinking>From the bar chart, the longest light blue bar corresponds to 415 victims in
    ↪ 2012 for solved homicides. The shortest gray bar corresponds to 106 victims in
    ↪ 2013 for unsolved homicides. The average of these two values is calculated as (415
    ↪  + 106) divided by 2, which equals 260.5. As the question asks for an integer, we
    ↪ round the average to the nearest whole number, which is 261.</thinking>
```
× **INCORRECT**
```
<answer>261</answer>
```

Case B1: MathVista (OOD Dataset, OOD Tools)



Question: Hint: Please answer the question requiring an integer answer and provide the final value, e.g., 1, 2, 3, at the end. Question: How much more accurate is the most accurate algorithm compared the least accurate algorithm?

Ground Truth: 80

MetaForge (✓ Correct) – 2 turns

```
<thinking> To determine how much more accurate the most accurate algorithm is compared to
     ↪ the least accurate one, I need to extract the accuracy values from the bar chart.
     ↪ I will identify the highest and lowest bars, read their values, and calculate the
     ↪ difference. The best tool for reading the chart is "UniChart" or "ChartMoe," but
     ↪ since I need to interpret values directly, I can use "InternVL3.5-14B-Instruct" or
     ↪  "InternVL3.5-38B-Instruct" to analyze the chart and extract the values from the
     ↪ bars.</thinking>
<tool_call>
{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Extract the accuracy values
     ↪ for each algorithm from the bar chart: 'niece', 'harder', 'ditch', and 'wheat'.",
     ↪ "image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] The accuracy values for each algorithm are as follows:

- niece: 60
- harder: 70
- ditch: 10
- wheat: 90
----- [Assistant Response] -----
<thinking> Now that I have the accuracy values for each algorithm, I need to determine the
     ↪  most accurate and the least accurate ones. The most accurate is 'wheat' with 90,
     ↪ and the least accurate is 'ditch' with 10. To find out how much more accurate the
     ↪ most accurate algorithm is compared to the least accurate one, I will calculate
     ↪ the difference between these two values: 90 - 10.</thinking>
✓ CORRECT
<answer>80</answer>
```

Qwen3-VL-8B (✓ Correct) – 4 turns

```
<thinking>
I need to determine the accuracy of the most and least accurate algorithms from the bar
     ↪ chart and calculate the difference. I can use the UniChart tool to interpret the
     ↪ chart data and provide the required answer.
<tool_call>
```

```
{"name": "UniChart", "arguments": {"image_index": 1, "prompt": "What is the accuracy of
    ↪ each algorithm shown in the bar chart?"}}
</tool_call>
----- [Observation] -----
[Tool: UniChart] {"success": true, "data": {"result": "What is the accuracy of each
    ↪ algorithm shown in the bar chart?"}, "error": null}
----- [Assistant Response] -----
<thinking>
The UniChart tool returned a generic response, indicating that it did not extract the
    ↪ necessary data from the chart. I need to try another tool that can read and
    ↪ interpret chart data more effectively. I will use the Deplot tool to extract the
    ↪ data from the chart.
<tool_call>
{"name": "Deplot", "arguments": {"image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: Deplot] {"success": false, "data": null, "error": "cannot open resource"}
----- [Assistant Response] -----
<thinking>
Deplot failed to process the chart image. I will now try using ChartMoe, which is
    ↪ designed to understand charts and provide analysis or reconstruction.
<tool_call>
{"name": "ChartMoe", "arguments": {"image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: ChartMoe] {"success": true, "data": {"result": "```python\nimport matplotlib.
    ↪ pyplot as plt\nimport numpy as np\n# ??\ndata = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]\n#
    ↪  ?????\nplt.bar(range(len(data)), data)\n# ?????\nmax_value = max(data)\n#
    ↪ ??????????\nindex = data.index(max_value)\n# ????????\nplt.bar(index, max_value,
    ↪ color='red')\n# ?????????????\nplt.axhline(y=max_value, color='red')\n# ???\nplt.
    ↪ show()\n```[UNUSED_TOKEN_145]"}, "error": null}
----- [Assistant Response] -----
<thinking>
ChartMoe returned a Python script, which is not directly helpful for extracting the
    ↪ accuracy values from the chart. I need to interpret the chart visually. The bar
    ↪ chart shows the accuracy of different algorithms, with 'wheat' having the highest
    ↪ accuracy, and 'ditch' having the lowest accuracy. From the chart, I can estimate
    ↪ the accuracy values. 'wheat' appears to be around 90, and 'ditch' is around 10.
    ↪ The difference is 90 - 10 = 80.

Since I cannot directly extract the values from the chart using tools, I will proceed
    ↪ with the visual estimation and provide the answer.
```


✓ **CORRECT**


```
<answer>80</answer>
```


TikArt-8B (✓ Correct) – 5 turns


```
<thinking>
To determine how much more accurate the most accurate algorithm is compared to the least
    ↪ accurate algorithm, I need to analyze the bar chart:

1. Identify the accuracy of the most accurate algorithm (highest bar).
2. Identify the accuracy of the least accurate algorithm (lowest bar).
3. Calculate the difference between these two values.

From the chart:
- The highest bar corresponds to "wheat" with an accuracy of approximately 90.
- The lowest bar corresponds to "ditch" with an accuracy of approximately 10.

The difference is 90 - 10 = 80.

I will use the UniChart tool to confirm the exact values from the chart.
</thinking>
<tool_call>{"name": "UniChart", "arguments": {"image_index": 1, "prompt": "What is the
    ↪ accuracy of each algorithm shown in the bar chart?"}}
</tool_call>
----- [Observation] -----
[Tool: UniChart] {"success": true, "data": {"result": "What is the accuracy of each
    ↪ algorithm shown in the bar chart?"}, "error": null}
----- [Assistant Response] -----
<thinking>
The UniChart tool returned a result indicating that I need to specify the exact prompt to
    ↪  get accurate data from the chart. I will refine my prompt to explicitly ask for
    ↪ the accuracy values of each algorithm.
```

```
I will now use the UniChart tool again with a clearer prompt to extract the accuracy
    ↪ values.
</thinking>
<tool_call>{"name": "UniChart", "arguments": {"image_index": 1, "prompt": "Extract the
    ↪ accuracy values for each algorithm ('niece', 'harder', 'ditch', 'wheat') from the
    ↪ bar chart."}}
</tool_call>
----- [Observation] -----
[Tool: UniChart] {"success": true, "data": {"result": "Extract the accuracy values for
    ↪ each algorithm ('niece', 'harder', 'ditch', 'wheat') from the bar chart. The data
    ↪ reveals that the user has an average accuracy of 40.25, with a value of 60.25. The
    ↪  user has an average accuracy of 40.25, with a value of 70.25. The user has an
    ↪ average accuracy of 40.25, with a value of 90.25. The chart shows that the user
    ↪ has an average accuracy of 40.25, with"}, "error": null}
----- [Assistant Response] -----
<thinking>
The UniChart tool returned incomplete or ambiguous data, making it difficult to extract
    ↪ the exact accuracy values for each algorithm. I will instead use the Deplot tool
    ↪ to extract the underlying tabular data from the chart image, which should give me
    ↪ a clearer and more structured view of the accuracy values.
</thinking>
<tool_call>{"name": "Deplot", "arguments": {"image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: Deplot] {"success": false, "data": null, "error": "cannot open resource"}
----- [Assistant Response] -----
<thinking>
The Deplot tool failed to extract the data from the chart image. Given this, I will rely
    ↪ on visual inspection of the chart to determine the accuracy values. From the chart
    ↪ :
- "wheat" has the highest accuracy, approximately 90.
- "ditch" has the lowest accuracy, approximately 10.

The difference between the most accurate and least accurate algorithms is 90 - 10 = 80.

I will now calculate this difference directly to provide the final answer.
</thinking>
<tool_call>{"name": "python_code", "arguments": {"code": "most_accurate = 90\
    ↪ nleast_accurate = 10\ndifference = most_accurate - least_accurate\ndifference"}}
</tool_call>
----- [Observation] -----
80
----- [Assistant Response] -----
```

✓ **CORRECT**

```
<answer>80</answer>
```


Claude-Sonnet-4-6 (✓ Correct) – 3 turns

```
<thinking>I need to find the accuracy values for each algorithm from the bar chart to
    ↪ determine the difference between the most and least accurate. I will use a chart
    ↪ analysis tool to extract the values.</thinking>
<tool_call>
{"name": "ChartMoe", "arguments": {"image_index": 1, "prompt": "Extract the accuracy
    ↪ values for each algorithm from the bar chart."}}
</tool_call>
----- [Observation] -----
[Tool: ChartMoe] {"success": true, "data": {"result": "The chart shows four algorithms
    ↪ with accuracy values. The bars represent: niece ~60, harder ~70, ditch ~10, wheat
    ↪ ~90."}, "error": null}
----- [Assistant Response] -----
<thinking>ChartMoe returned approximate values. Let me verify with another tool to ensure
    ↪  accuracy before computing the difference.</thinking>
<tool_call>
{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Read the exact accuracy
    ↪ values for each algorithm from the bar chart: niece, harder, ditch, wheat.", "
    ↪ image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] The accuracy values are: niece = 60, harder = 70, ditch
    ↪ = 10, wheat = 90.
----- [Assistant Response] -----
<thinking>Both tools agree on the values. The most accurate algorithm is wheat (90) and
    ↪ the least accurate is ditch (10). The difference is 90 - 10 = 80.</thinking>
```

✓ **CORRECT**

```
<answer>80</answer>
```

Case B2: CLEVR-Math (OOD Dataset, OOD Tools)



Question: Subtract all cyan cylinders. How many cylinders are left?
Ground Truth: 2

MetaForge (✓ Correct) – 2 turns

```
<thinking> First, I need to identify all the cylinders in the image. Then, I will subtract
    ↪  the cyan cylinders from this total count to find the remaining number of
    ↪ cylinders. I will use the InternVL3.5-14B-Instruct model to analyze the image and
    ↪ count the cylinders, including identifying the cyan ones.</thinking>
<tool_call>
{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Count the total number of
    ↪ cylinders in the image and identify how many of them are cyan.", "image_index":
    ↪ 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] There are three cylinders in the image, and one of them
    ↪ is cyan.
----- [Assistant Response] -----
<thinking> Based on the tool's output, there are 3 cylinders in total, and 1 of them is
    ↪ cyan. Subtracting the cyan cylinder from the total gives me the number of
    ↪ remaining cylinders.</thinking>
```

✓ **CORRECT**

```
<answer>2</answer>
```

Qwen3-VL-8B (✓ Correct) – 3 turns

```
<thinking>
I need to analyze the image to count the cylinders and then subtract the cyan ones. I can
    ↪  use the InternVL3.5-14B-Instruct model for this task since it's suitable for
    ↪ image understanding.

First, I'll count all cylinders in the image.
Then, I'll specifically identify and count the cyan cylinders.
Finally, I'll subtract the cyan cylinders from the total to get the answer.

I will use the InternVL3.5-14B-Instruct model to analyze the image.
<tool_call>{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Count all
    ↪ cylinders in the image.", "image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] There are three cylinders in the image.
----- [Assistant Response] -----
<thinking>
I've determined there are three cylinders in total. Now, I need to identify how many of
    ↪ these are cyan. I will use the InternVL3.5-14B-Instruct model to analyze the image
    ↪  and count the cyan cylinders.
<tool_call>{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Count the cyan
    ↪ cylinders in the image.", "image_index": 1}}
</tool_call>
----- [Observation] -----
```

```
[Tool: InternVL3.5-14B-Instruct] There is one cyan cylinder in the image.
----- [Assistant Response] -----
<thinking>
I have now determined that there are 3 cylinders in total and 1 of them is cyan. To find
    ↪ out how many cylinders are left after subtracting the cyan ones, I will perform
    ↪ the subtraction: 3 - 1 = 2.

Therefore, there are 2 cylinders left after subtracting the cyan one.
✓ CORRECT
<answer>2</answer>
```

TikArt-8B (✓ Correct) – 10 turns

```
<thinking>
I need to count the cylinders in the image and subtract the cyan ones. First, I'll
    ↪ identify all cylinders, then subtract the cyan ones to find how many are left.

I can use the "image-scene-summarizer" skill to get a description of the objects in the
    ↪ image, which will help me identify the cylinders and their colors.
<tool_call>{"name": "image-scene-summarizer", "arguments": {}}
</tool_call>
----- [Observation] -----
[Skill: image-scene-summarizer] SKILL.md:
---
name: image-scene-summarizer
description: Generate a concise one- or two-sentence description of an image's visual
    ↪ content, focusing on scene, event, or setting without OCR or genre classification.
---

## Usage
### Scripts
- `scripts/describe_scene.py`: analyze image visual content and output a short natural
    ↪ language summary.

### Parameters
- `run_skill.args.image_index` (required): image selector for caller
- `--output_text` (optional): file path to save summary; if not provided, prints to
    ↪ stdout

### Workflow
1. Run `describe_scene.py` with image_index to generate a concise scene description.

### Call Contract
- run_skill.args.image_index is required for image input.

### When to call
- Use this skill to summarize visual scenes, events, or settings in an image without
    ↪ extracting text, classifying genre, or parsing structured data.

## Image Input Contract
- This skill requires `args.image_index` in `run_skill` if you want to call a script that
    ↪  needs image input.

----- [Assistant Response] -----
<tool_call>{"name": "run_skill", "arguments": {"skill_name": "image-scene-summarizer", "
    ↪ entrypoint": "scripts/describe_scene.py", "args": {"image_index": 1}}}
</tool_call>
----- [Observation] -----
moderately lit scene, 476x308 pixels, dominant color: RGB(106, 106, 106).
===SKILL_RESULT_START===
moderately lit scene, 476x308 pixels, dominant color: RGB(106, 106, 106).
===SKILL_RESULT_END===
----- [Assistant Response] -----
The scene summary doesn't specifically identify the cylinders or their colors. I need to
    ↪ use a different approach to identify and count the cylinders, specifically
    ↪ focusing on their colors.

I will use the "small-brown-metallic-object-tracker" skill to identify any brown
    ↪ cylinders, and then use the "small-gray-metallic-object-tracker" skill to identify
    ↪  any gray cylinders. Since I know there is a cyan cylinder, I will use the "visual
    ↪ -content-summarizer" skill to get a more detailed description to confirm the
    ↪ presence of the cyan cylinder.

First, I'll use the "small-brown-metallic-object-tracker" skill to identify brown
    ↪ cylinders.
<tool_call>{"name": "small-brown-metallic-object-tracker", "arguments": {}}
```

```
</tool_call>
----- [Observation] -----
[Skill: small-brown-metallic-object-tracker] SKILL.md:
---
name: small-brown-metallic-object-tracker
description: Track and manage the count of small brown metallic objects in the
    ↪ environment using image input -- distinct from existing small-gray-metallic-object
    ↪ -tracker by focusing exclusively on brown-colored metallic objects.
---

## Usage
### Scripts
- `scripts/detect_brown_metallic.py`: detect and count small brown metallic objects in an
    ↪  image.
- `scripts/update_count.py`: update and persist the running count of detected objects.

### Parameters
- `run_skill.args.image_index` (required for detect_brown_metallic): image selector for
    ↪ caller
- `--output_json` (required): path to save detection results
- `--count_file` (required for update_count): path to persistent count file

### Workflow
1. Run `detect_brown_metallic.py` to extract object count from image.
2. Run `update_count.py` to increment and store the total count.

### Call Contract
- run_skill.args.image_index is required only for image-reading scripts.

### When to call
- Use this skill when tracking brown metallic objects specifically -- not gray, not non-
    ↪ metallic, not large objects -- and need persistent count management across
    ↪ multiple images.

## Image Input Contract
- This skill requires `args.image_index` in `run_skill` if you want to call a script that
    ↪  needs image input.

----- [Assistant Response] -----
<tool_call>{"name": "run_skill", "arguments": {"skill_name": "small-brown-metallic-object-
    ↪ tracker", "entrypoint": "scripts/detect_brown_metallic.py", "args": {"image_index
    ↪ ": 1}}}
</tool_call>
----- [Observation] -----
[stderr]
usage: detect_brown_metallic.py [-h] --output_json OUTPUT_JSON
detect_brown_metallic.py: error: the following arguments are required: --output_json
----- [Assistant Response] -----
I need to provide the required `--output_json` parameter for the script. I will run the
    ↪ script again with this parameter specified.

I will use the "small-gray-metallic-object-tracker" skill to identify any gray cylinders.
<tool_call>{"name": "small-gray-metallic-object-tracker", "arguments": {}}
</tool_call>
----- [Observation] -----
[Skill: small-gray-metallic-object-tracker] SKILL.md:
---
name: small-gray-metallic-object-tracker
description: Track and manage the count of small gray metallic objects in the environment
    ↪  using image input.
---

## Usage
### Scripts
- `scripts/detect_objects.py`: detect small gray metallic objects in an image and output
    ↪ their count.
- `scripts/update_count.py`: update the running count based on new detection results.
- `scripts/report_status.py`: generate a summary report of current object count and
    ↪ change since last update.

### Parameters
- `run_skill.args.image_index` (required for detect_objects): image selector for caller
- `--output_json` (required): path to save detection or update results
- `--input_json` (required for update_count and report_status): path to previous state or
    ↪  detection JSON
- `--threshold` (optional): minimum confidence threshold for object detection

### Workflow
1. Run `detect_objects.py` to count objects in a new image.
```

```
2. Run `update_count.py` to merge new count with historical state.
3. Run `report_status.py` to generate a human-readable summary.

### Call Contract
- `run_skill.args.image_index` is required only for `detect_objects.py`.
- All scripts must print key results to stdout for downstream consumption.

### When to call
- Use this skill when monitoring environmental changes involving small gray metallic
    ↪ objects across sequential images.

## Image Input Contract
- This skill requires `args.image_index` in `run_skill` if you want to call a script that
    ↪  needs image input.

----- [Assistant Response] -----
<tool_call>{"name": "run_skill", "arguments": {"skill_name": "small-gray-metallic-object-
    ↪ tracker", "entrypoint": "scripts/detect_objects.py", "args": {"image_index": 1}}}
</tool_call>
----- [Observation] -----
[stderr]
usage: detect_objects.py [-h] --output_json OUTPUT_JSON
                         [--threshold THRESHOLD]
detect_objects.py: error: the following arguments are required: --output_json
----- [Assistant Response] -----
I need to provide the required `--output_json` parameter for the script. I will run the
    ↪ script again with this parameter specified.

I will now use the "visual-content-summarizer" skill to get a more detailed description
    ↪ to confirm the presence of the cyan cylinder.
<tool_call>{"name": "visual-content-summarizer", "arguments": {}}
</tool_call>
----- [Observation] -----
[Skill: visual-content-summarizer] SKILL.md:
---
name: visual-content-summarizer
description: Generates a one- or two-sentence summary of visual content by describing key
    ↪  elements and their spatial arrangement without OCR or semantic classification.
---

## Usage
### Scripts
- `scripts/describe_layout.py`: analyze image to extract key visual elements and their
    ↪ spatial relationships.
- `scripts/summarize_description.py`: convert layout description into a concise one- or
    ↪ two-sentence summary.

### Parameters
- `run_skill.args.image_index` (required for describe_layout): image selector for caller
- `--output_json` (required): output file path for intermediate layout description
- `--input_json` (required for summarize_description): input file path from previous step

### Workflow
1. Run `describe_layout.py` to extract visual elements and their arrangement.
2. Run `summarize_description.py` to generate final natural language summary.

### Call Contract
- run_skill.args.image_index is required only for image-reading scripts.

### When to call
- Use this skill when you need a quick, non-interpretive visual summary of an image's
    ↪ composition -- distinct from genre, text, or table extraction skills by focusing
    ↪ purely on visual structure and object placement.

## Image Input Contract
- This skill requires `args.image_index` in `run_skill` if you want to call a script that
    ↪  needs image input.

----- [Assistant Response] -----
<tool_call>{"name": "run_skill", "arguments": {"skill_name": "visual-content-summarizer",
    ↪  "entrypoint": "scripts/describe_layout.py", "args": {"image_index": 1}}}
</tool_call>
----- [Observation] -----
[stderr]
usage: describe_layout.py [-h] --output_json OUTPUT_JSON
describe_layout.py: error: the following arguments are required: --output_json
----- [Assistant Response] -----
I need to provide the required `--output_json` parameter for the script. I will run the
    ↪ script again with this parameter specified.
```

```
Since I am unable to use the specific tracking skills due to parameter constraints, I
    ↪ will use the "InternVL3.5-14B-Instruct" model to analyze the image and identify
    ↪ the cylinders and their colors.

I will ask the model to identify all cylinders and their colors in the image.
<tool_call>{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Identify all
    ↪ cylinders in the image and describe their colors.", "image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] The image contains three cylinders. One is brown, one is
    ↪  yellow, and one is teal.
----- [Assistant Response] -----
Now that I know there are three cylinders in total -- one brown, one yellow, and one teal
    ↪  (cyan) -- I can subtract the cyan cylinder as requested.

Total cylinders: 3
Cyan cylinders to subtract: 1

Remaining cylinders: 3 - 1 = 2

The remaining cylinders are the brown and the yellow ones.
```

✓ **CORRECT**

```
<answer>2</answer>
```


Claude-Sonnet-4-6 (✓ Correct) – 3 turns

```
<thinking>I need to count the cylinders in the image and subtract the cyan ones. I will
    ↪ use a vision model to analyze the image.</thinking>
<tool_call>
{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "How many cylinders are in
    ↪ this image? List each cylinder and its color.", "image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] I can see several 3D objects in the image. There appear
    ↪ to be metallic objects of various shapes including cylinders, cubes, and spheres.
----- [Assistant Response] -----
<thinking>The response was not specific enough about cylinder count and colors. Let me
    ↪ try a more targeted prompt.</thinking>
<tool_call>
{"name": "InternVL3.5-14B-Instruct", "arguments": {"prompt": "Count exactly how many
    ↪ cylinders are in this image and identify which ones are cyan colored.", "
    ↪ image_index": 1}}
</tool_call>
----- [Observation] -----
[Tool: InternVL3.5-14B-Instruct] There are 3 cylinders in the image: 1 brown metallic
    ↪ cylinder, 1 cyan metallic cylinder, and 1 gray metallic cylinder.
----- [Assistant Response] -----
<thinking>There are 3 cylinders total, 1 is cyan. Subtracting the cyan cylinder: 3 - 1 =
    ↪ 2 cylinders remain.</thinking>
```

✓ **CORRECT**

```
<answer>2</answer>
```

Case C1: WebSight (OOD Dataset, IID Tools)



Question: Generate the HTML code corresponding to this website screenshot.

Ground Truth:

```
<html>
<link href="https://cdn.jsdelivr.net/npm/tailwindcss@2.2.19/dist/tailwind.min.css" rel="
    ↪ stylesheet">
<body class="bg-gray-200">
  <div class="flex flex-col items-center justify-center min-h-screen">
    <header class="w-full bg-gray-800 text-white p-4">
      <h1 class="text-2xl font-bold">Welcome to Our Tech Company</h1>
    </header>
    <main class="flex flex-col items-center justify-center w-full flex-1 px-20 text-
    ↪ center">
      <p class="text-lg mb-6">
        At Our Tech Company, we are dedicated to providing innovative and reliable
    ↪ technology solutions to meet your business needs. Our team of experts is
    ↪ committed to delivering high-quality products and services that exceed your
    ↪ expectations.
      </p>
      <p class="text-lg mb-6">
        We specialize in a wide range of services, including custom software development,
    ↪  IT consulting, cloud solutions, and more. Whether you're a small business or a
    ↪ large corporation, we have the expertise to help you achieve your goals.
      </p>
      <p class="text-lg mb-6">
        Contact us today to learn more about how we can help you grow your business with
    ↪  technology.
      </p>
    </main>
    <footer class="w-full bg-gray-800 text-white p-4">
      <p>(c) 2022 Our Tech Company. All rights reserved.</p>
    </footer>
  </div>
</body>
</html>
```

MetaForge (✓ Correct) – 3 turns

```
<thinking>
The task asks me to generate HTML from a website screenshot. The current IID tools include
    ↪  OCR, layout parsing, image processing, and multimodal models, but none of them
    ↪ directly converts a screenshot into semantic HTML. I need to forge a reusable tool
    ↪  that extracts page regions and emits structured HTML.
</thinking>
<tool_call>
{"name": "create_skill", "arguments": {"description": "Convert a website screenshot into
    ↪ semantic HTML by detecting visual layout regions, extracting visible text, mapping
    ↪  regions to header/nav/main/footer sections, and printing a complete HTML document
    ↪  to stdout without file output."}}
</tool_call>
----- [Observation] -----
[Skill: screenshot-layout-html-builder] created and validated.
SKILL.md:
---
name: screenshot-layout-html-builder
description: Convert a website screenshot into semantic HTML by detecting layout regions,
    ↪ extracting visible text, and generating a complete HTML document.
---
```

```
Scripts:
- scripts/build_html.py: reads SKILL_IMAGE_PATH or SKILL_IMAGE_DATA_URL, detects page regions, extracts visible text, and prints HTML to stdout.

Parameters:
- run_skill.args.image_index: required image selector.
- include_css: optional boolean, default true.

Validation:
- compile: passed
- help: passed
- semantic check: passed

----- [Assistant Response] -----
<thinking>
The forged tool passed validation. I will execute it on the screenshot and use its stdout HTML as the basis for the final answer.
</thinking>
<tool_call>
{"name": "run_skill", "arguments": {"skill_name": "screenshot-layout-html-builder", "entrypoint": "scripts/build_html.py", "args": {"image_index": 1, "include_css": true}}}
</tool_call>
----- [Observation] -----
===SKILL_RESULT_START===
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Our Tech Company</title>
  <link href="https://cdn.jsdelivr.net/npm/tailwindcss@2.2.19/dist/tailwind.min.css" rel="stylesheet">
</head>
<body class="bg-gray-200">
  <div class="flex flex-col items-center justify-center min-h-screen">
    <header class="w-full bg-gray-800 text-white p-4">
      <h1 class="text-2xl font-bold">Welcome to Our Tech Company</h1>
    </header>

    <main class="flex flex-col items-center justify-center w-full flex-1 px-20 text-center ">
      <p class="text-lg mb-6">
        At Our Tech Company, we are dedicated to providing innovative and reliable technology solutions to meet your business needs. Our team of experts is committed to delivering high-quality products and services that exceed your expectations.
      </p>
      <p class="text-lg mb-6">
        We specialize in a wide range of services, including custom software development, IT consulting, cloud solutions, and more. Whether you're a small business or a large corporation, we have the expertise to help you achieve your goals.
      </p>
      <p class="text-lg mb-6">
        Contact us today to learn more about how we can help you grow your business with technology.
      </p>
    </main>

    <footer class="w-full bg-gray-800 text-white p-4">
      <p>(c) 2022 Our Tech Company. All rights reserved.</p>
    </footer>
  </div>
</body>
</html>
===SKILL_RESULT_END===

----- [Assistant Response] -----
<thinking>
The forged tool produced an HTML document containing the original heading, three introductory paragraphs, and copyright footer. I will return this HTML as the final answer.
</thinking>
<answer>
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Our Tech Company</title>
  <link href="https://cdn.jsdelivr.net/npm/tailwindcss@2.2.19/dist/tailwind.min.css" rel="
     ↪ stylesheet">
</head>
<body class="bg-gray-200">
  <div class="flex flex-col items-center justify-center min-h-screen">
    <header class="w-full bg-gray-800 text-white p-4">
      <h1 class="text-2xl font-bold">Welcome to Our Tech Company</h1>
    </header>

    <main class="flex flex-col items-center justify-center w-full flex-1 px-20 text-center
     ↪ ">
      <p class="text-lg mb-6">
        At Our Tech Company, we are dedicated to providing innovative and reliable
     ↪ technology solutions to meet your business needs. Our team of experts is committed
     ↪  to delivering high-quality products and services that exceed your expectations.
      </p>
      <p class="text-lg mb-6">
        We specialize in a wide range of services, including custom software development,
     ↪ IT consulting, cloud solutions, and more. Whether you're a small business or a
     ↪ large corporation, we have the expertise to help you achieve your goals.
      </p>
      <p class="text-lg mb-6">
        Contact us today to learn more about how we can help you grow your business with
     ↪ technology.
      </p>
    </main>

    <footer class="w-full bg-gray-800 text-white p-4">
      <p>(c) 2022 Our Tech Company. All rights reserved.</p>
    </footer>
  </div>
</body>
</html>
</answer>
```

Qwen3-VL-8B (× Incorrect) – 2 turns

```
<thinking>The screenshot shows a website layout. I will use the Qwen3-VL-8B-Instruct
     ↪ model to analyze the screenshot and directly generate the corresponding HTML code
     ↪ based on what the model can recognize from the image.</thinking>
<tool_call>
{"name": "Qwen3-VL-8B-Instruct", "arguments": {"prompt": "Generate the complete HTML code
     ↪  for the website shown in this image."}}
</tool_call>
----- [Observation] -----
The image shows a website layout. Based on my analysis, the page contains a header
     ↪ section, main content area with text and visual elements, and a footer. I will
     ↪ attempt to reconstruct the HTML structure.

----- [Assistant Response] -----
× INCORRECT
<answer>
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Welcome to Our Tech Company</title>
    <style>
        body {
            font-family: Arial, sans-serif;
            margin: 0;
            padding: 20px;
            background-color: #f5f5f5;
        }
        .container {
            max-width: 800px;
            margin: 0 auto;
            text-align: center;
        }
        h1 {
            color: #2c3e50;
        }
        p {
            color: #34495e;
```

```
            line-height: 1.6;
        }
        nav {
            margin: 20px 0;
            padding: 10px;
            background-color: #ecf0f1;
            border-radius: 5px;
        }
        nav a {
            margin: 0 10px;
            text-decoration: none;
            color: #2980b9;
            font-weight: bold;
        }
        nav a:hover {
            color: #e74c3c;
        }
    </style>
</head>
<body>
    <div class="container">
        <h1>Welcome to Our Tech Company</h1>
        <p>At Our Tech Company, we are dedicated to providing innovative and reliable
    ↪ technology solutions to meet your business needs. Our team of experts is committed
    ↪  to delivering high-quality products and services that exceed your expectations.
    ↪ We specialize in a wide range of services, including custom software development,
    ↪ IT consulting, cloud solutions, and more. Whether you're a small business or a
    ↪ large corporation, we have the expertise to help you achieve your goals. Contact
    ↪ us today to learn more about how we can help you grow your business with
    ↪ technology.</p>
        <nav>
            <a href="https://www.ourtechcompany.com">Home</a><a href="https://www.
    ↪ ourtechcompany.com/about">About</a><a href="https://www.ourtechcompany.com/
    ↪ services">Services</a><a href="https://www.ourtechcompany.com/contact">Contact</a>
        </nav>
    </div>
</body>
</html>
</answer>
```

TikArt-8B (× Incorrect) – 2 turns

```
<thinking>I need to generate HTML code that matches the provided website screenshot. I
    ↪ will call Qwen3-VL-8B-Instruct to describe and interpret the visual layout, then
    ↪ construct the HTML based on its output.</thinking>
<tool_call>
{"name": "Qwen3-VL-8B-Instruct", "arguments": {"prompt": "Generate the complete HTML code
    ↪  for the website shown in this image."}}
</tool_call>
----- [Observation] -----
The image shows a website layout. Based on my analysis, the page contains a header
    ↪ section, main content area with text and visual elements, and a footer. I will
    ↪ attempt to reconstruct the HTML structure.

----- [Assistant Response] -----
× INCORRECT
<answer>
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Our Tech Company - Technology Solutions</title>
    <style>
        body { font-family: Arial, sans-serif; margin: 0; padding: 0; }
        header { background-color: #333; color: white; padding: 1rem; }
        nav ul { list-style: none; margin: 0; padding: 0; display: flex; }
        nav li { margin-right: 1rem; }
        nav a { color: white; text-decoration: none; }
        section { padding: 2rem; }
        .section-title { color: #333; }
        form label { display: block; margin: 0.5rem 0; }
        form input, form textarea { width: 100%; padding: 0.5rem; }
        form button { margin-top: 1rem; padding: 0.5rem 1rem; }
    </style>
</head>
```

```
<body>
    <header>
        <h1>Our Tech Company</h1>
        <nav>
            <ul>
                <li><a href="#home">Home</a></li><li><a href="#about">About</a></li><li><
    ↪ a href="#products">Products</a></li><li><a href="#contact">Contact</a></li>
            </ul>
        </nav>
    </header>

    <section id="about">
        <h2 class="section-title">About Us</h2>
        <p>At Our Tech Company, we are dedicated to providing innovative and reliable
    ↪ technology solutions to meet your business needs. Our team of experts is committed
    ↪  to delivering high-quality products and services that exceed your expectations.</
    ↪ p>
    </section>

    <section id="products">
        <h2 class="section-title">Products</h2>
        <p>We specialize in a wide range of services, including custom software
    ↪ development, IT consulting, cloud solutions, and more. Whether you're a small
    ↪ business or a large corporation, we have the expertise to help you achieve your
    ↪ goals.</p>
    </section>

    <section id="features">
        <h2 class="section-title">Features</h2>
        <p></p>
    </section>

    <section id="testimonials">
        <h2 class="section-title">Testimonials</h2>
        <p></p>
    </section>

    <section id="contact">
        <h2 class="section-title">Contact Us</h2>
        <form>
            <label for="name">Name:</label><input type="text" id="name" name="name"
    ↪ required><br><label for="email">Email:</label><input type="text" id="email" name="
    ↪ email" required><br>
            <label for="message">Message:</label><textarea id="message" name="message"
    ↪ rows="4" required></textarea><br>
            <button type="submit">Send Message</button>
        </form>
    </section>
</body>
</html>
</answer>
```

Claude-Sonnet-4-6 (× Incorrect) – 2 turns

```
<thinking>To generate HTML from this screenshot, I will use the Qwen3-VL-32B-Instruct
    ↪ vision-language model to analyze the visual structure and produce the
    ↪ corresponding HTML code directly.</thinking>
<tool_call>
{"name": "Qwen3-VL-32B-Instruct", "arguments": {"prompt": "Generate the complete HTML
    ↪ code for the website shown in this image."}}
</tool_call>
----- [Observation] -----
The image shows a website layout. Based on my analysis, the page contains a header
    ↪ section, main content area with text and visual elements, and a footer. I will
    ↪ attempt to reconstruct the HTML structure.


----- [Assistant Response] -----
```

× **INCORRECT**

```
<answer>
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Our Tech Company</title>
    <style>
```

```
        body {
            font-family: Arial, sans-serif;
            margin: 0;
            padding: 0;
            line-height: 1.6;
        }
        header {
            background: #333;
            color: white;
            padding: 1rem;
            text-align: center;
        }
        nav {
            background: #444;
            padding: 0.5rem;
            text-align: center;
        }
        nav ul {
            list-style: none;
            padding: 0;
            margin: 0;
        }
        nav ul li {
            display: inline;
            margin: 0 1rem;
        }
        nav ul li a {
            color: white;
            text-decoration: none;
        }
        nav ul li a:hover {
            text-decoration: underline;
        }
        main {
            padding: 2rem;
            text-align: center;
        }
        footer {
            background: #333;
            color: white;
            text-align: center;
            padding: 1rem;
            position: fixed;
            width: 100%;
            bottom: 0;
        }
    </style>
</head>
<body>
    <header>
        <h1>Our Tech Company</h1>
        <img src="{{ SKILL_IMAGE_PATH or SKILL_IMAGE_DATA_URL }}" alt="Header Image"
    ↪ style="max-width: 100%; height: auto;">
    </header>
    <nav>
        <ul>
            <li><a href="#">Home</a></li><li><a href="#">Services</a></li><li><a href="#">
    ↪ Contact</a></li>
        </ul>
    </nav>
    <main>
        <h2>Welcome to Our Tech Company</h2>
        <p>At Our Tech Company, we are dedicated to providing innovative and reliable
    ↪ technology solutions to meet your business needs. Our team of experts is committed
    ↪  to delivering high-quality products and services that exceed your expectations.
    ↪ We specialize in a wide range of services, including custom software development,
    ↪ IT consulting, cloud solutions, and more. Whether you're a small business or a
    ↪ large corporation, we have the expertise to help you achieve your goals. Contact
    ↪ us today to learn more about how we can help you grow your business with
    ↪ technology.</p>
    </main>
    <footer>
        <p>Email: info@ourtechcompany.com</p>
        <p>Monday-Friday: 9am-5pm</p>
    </footer>
</body>
</html>
</answer>
```

Case C2: WebSight (OOD Dataset, IID Tools)



Question: Derive the HTML code to reflect this website's interface.

Ground Truth:

```
<html>
<link href="https://cdn.jsdelivr.net/npm/tailwindcss@2.2.19/dist/tailwind.min.css" rel="
    ↪ stylesheet">
<body class="bg-gray-100">
    <div class="container mx-auto px-4 py-8">
        <header class="flex justify-center items-center h-64">
            <img src="FIXED_HEALTHCARE_IMAGE_URL" alt="Healthcare Logo" class="h-32">
        </header>
        <nav class="flex justify-between items-center mb-8">
            <ul class="flex">
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">Home</a></li>
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">About</a></li>
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">Services</a></li>
            </ul>
            <button class="bg-yellow-500 hover:bg-yellow-700 text-white font-bold py-2
    ↪ px-4 rounded">
                Schedule an Appointment
            </button>
        </nav>
        <main class="mb-8">
            <h1 class="text-3xl mb-4">Welcome to Our Healthcare Provider</h1>
            <p class="mb-4">We are a team of healthcare providers dedicated to providing
    ↪  the best care possible. Our mission is to improve the health and well-being of
    ↪ our patients.</p>
            <p class="mb-4">Our team of healthcare providers is committed to providing
    ↪ high-quality, compassionate care to our patients. We believe in the power of
    ↪ teamwork and collaboration to improve patient outcomes.</p>
        </main>
        <footer class="flex justify-between items-center">
            <div>
                <p>Contact Us:</p>
                <p>123 Main St, Anytown, USA</p>
                <p>Phone: (123) 456-7890</p>
                <p>Email: info@healthcareprovider.com</p>
            </div>
            <form>
                <input type="text" placeholder="Name" class="mb-2">
                <input type="text" placeholder="Email" class="mb-2">
                <textarea placeholder="Message" class="mb-2"></textarea>
                <button class="bg-yellow-500 hover:bg-yellow-700 text-white font-bold py
    ↪ -2 px-4 rounded">
                    Submit
                </button>
            </form>
        </footer>
    </div>
</body>
</html>
```

MetaForge (✓ Correct) – 3 turns

```
<thinking>
This screenshot contains a webpage with a navigation bar, healthcare text, contact
    ↪ information, and a form. Existing tools can describe the image, but none can
    ↪ reconstruct the screenshot as semantic HTML with form controls. I will create a
    ↪ tool for form-aware screenshot-to-HTML generation.
</thinking>
<tool_call>
{"name": "create_skill", "arguments": {"description": "Generate semantic HTML from webpage
    ↪  screenshots that contain navigation, content sections, contact details, and form
    ↪ controls. The tool should detect labels, inputs, textarea regions, buttons, and
    ↪ output complete HTML to stdout."}}
</tool_call>
----- [Observation] -----
[Skill: form-aware-screenshot-html] created and validated.
SKILL.md:
---
name: form-aware-screenshot-html
description: Reconstruct form-heavy webpage screenshots as semantic HTML with navigation,
    ↪ content sections, labels, inputs, textarea, and buttons.
---

Scripts:
- scripts/reconstruct_form_page.py: reads image input from the runtime, detects layout and
    ↪  form controls, and prints complete HTML to stdout.

Parameters:
- run_skill.args.image_index: required image selector.
- include_css: optional boolean, default true.

Validation:
- compile: passed
- help: passed
- form-control schema check: passed
- semantic check: passed

----- [Assistant Response] -----
<thinking>
The forged tool passed validation and is designed for screenshots with forms. I will run
    ↪ it on the current image.
</thinking>
<tool_call>
{"name": "run_skill", "arguments": {"skill_name": "form-aware-screenshot-html", "
    ↪ entrypoint": "scripts/reconstruct_form_page.py", "args": {"image_index": 1, "
    ↪ include_css": true}}}
</tool_call>
----- [Observation] -----
===SKILL_RESULT_START===
<html>
<link href="https://cdn.jsdelivr.net/npm/tailwindcss@2.2.19/dist/tailwind.min.css" rel="
    ↪ stylesheet">
<body class="bg-gray-100">
    <div class="container mx-auto px-4 py-8">
        <header class="flex justify-center items-center h-64">
            <img src="FIXED_HEALTHCARE_IMAGE_URL"
                 alt="Healthcare Logo"
                 class="h-32">
        </header>

        <nav class="flex justify-between items-center mb-8">
            <ul class="flex">
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">Home</a></li>
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">About</a></li>
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">Services</a></li>
            </ul>
            <button class="bg-yellow-500 hover:bg-yellow-700 text-white font-bold py-2 px
    ↪ -4 rounded">
                Schedule an Appointment
            </button>
        </nav>

        <main class="mb-8">
            <h1 class="text-3xl mb-4">Welcome to Our Healthcare Provider</h1>
            <p class="mb-4">
```

```
                We are a team of healthcare providers dedicated to providing the best care
    ↪  possible.
                Our mission is to improve the health and well-being of our patients.
            </p>
            <p class="mb-4">
                Our team of healthcare providers is committed to providing high-quality,
    ↪ compassionate care
                to our patients. We believe in the power of teamwork and collaboration to
    ↪ improve patient outcomes.
            </p>
        </main>

        <footer class="flex justify-between items-center">
            <div>
                <p>Contact Us:</p>
                <p>123 Main St, Anytown, USA</p>
                <p>Phone: (123) 456-7890</p>
                <p>Email: info@healthcareprovider.com</p>
            </div>

            <form>
                <input type="text" placeholder="Name" class="mb-2">
                <input type="text" placeholder="Email" class="mb-2">
                <textarea placeholder="Message" class="mb-2"></textarea>
                <button class="bg-yellow-500 hover:bg-yellow-700 text-white font-bold py-2
    ↪  px-4 rounded">
                    Submit
                </button>
            </form>
        </footer>
    </div>
</body>
</html>
===SKILL_RESULT_END===

----- [Assistant Response] -----
<thinking>
The forged tool returned a complete HTML reconstruction with the navigation bar,
    ↪ healthcare content, contact details, and form controls. Since the final answer
    ↪ should be HTML, I will return the tool output directly.
</thinking>
<answer>
<html>
<link href="https://cdn.jsdelivr.net/npm/tailwindcss@2.2.19/dist/tailwind.min.css" rel="
    ↪ stylesheet">
<body class="bg-gray-100">
    <div class="container mx-auto px-4 py-8">
        <header class="flex justify-center items-center h-64">
            <img src="FIXED_HEALTHCARE_IMAGE_URL"
                 alt="Healthcare Logo"
                 class="h-32">
        </header>

        <nav class="flex justify-between items-center mb-8">
            <ul class="flex">
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">Home</a></li>
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">About</a></li>
                <li class="mr-4"><a href="#" class="text-yellow-500 hover:text-yellow
    ↪ -700">Services</a></li>
            </ul>
            <button class="bg-yellow-500 hover:bg-yellow-700 text-white font-bold py-2 px
    ↪ -4 rounded">
                Schedule an Appointment
            </button>
        </nav>

        <main class="mb-8">
            <h1 class="text-3xl mb-4">Welcome to Our Healthcare Provider</h1>
            <p class="mb-4">
                We are a team of healthcare providers dedicated to providing the best care
    ↪  possible.
                Our mission is to improve the health and well-being of our patients.
            </p>
            <p class="mb-4">
                Our team of healthcare providers is committed to providing high-quality,
    ↪ compassionate care
```

```
                to our patients. We believe in the power of teamwork and collaboration to
    ↪ improve patient outcomes.
            </p>
        </main>

        <footer class="flex justify-between items-center">
            <div>
                <p>Contact Us:</p>
                <p>123 Main St, Anytown, USA</p>
                <p>Phone: (123) 456-7890</p>
                <p>Email: info@healthcareprovider.com</p>
            </div>

            <form>
                <input type="text" placeholder="Name" class="mb-2">
                <input type="text" placeholder="Email" class="mb-2">
                <textarea placeholder="Message" class="mb-2"></textarea>
                <button class="bg-yellow-500 hover:bg-yellow-700 text-white font-bold py-2
    ↪  px-4 rounded">
                    Submit
                </button>
            </form>
        </footer>
    </div>
</body>
</html>
</answer>
```

Rendering note. `FIXED_HEALTHCARE_IMAGE_URL` denotes the fixed local image asset used for the C2 evaluation. The token is a presentation-only placeholder in this trace: before rendering, the evaluator resolves it to the pinned asset, and the literal token is not treated as page content. The reference and MetaForge outputs use the same fixed asset and rendering settings.

Qwen3-VL-8B (× Incorrect) – 3 turns

```
<thinking>The existing tools cannot directly generate accurate HTML from this screenshot.
    ↪  I will create a new skill to reconstruct the webpage HTML structure by analyzing
    ↪ the visual layout and generating corresponding code.</thinking>
<tool_call>
{"name": "create_skill", "arguments": {"description": "Reconstruct webpage HTML from
    ↪ screenshot by analyzing visual layout regions and generating structured HTML with
    ↪ header, content, and footer sections."}}
</tool_call>
----- [Observation] -----
[Skill: webpage-html-reconstructor] created. SKILL.md:
---
name: webpage-html-reconstructor
description: Reconstruct webpage HTML from screenshot by analyzing visual layout regions
    ↪ and generating structured HTML with header, content, and footer sections.
---
## Usage
### Scripts
- `scripts/generate_html.py`: generate HTML from screenshot analysis.
### Parameters
- `run_skill.args.image_index` (required): image selector for caller.
- `--output_html` (required): path to save generated HTML file.

----- [Assistant Response] -----
<thinking>The skill has been created. Now I will run it to generate the HTML.</thinking>
<tool_call>
{"name": "run_skill", "arguments": {"skill_name": "webpage-html-reconstructor", "
    ↪ entrypoint": "scripts/generate_html.py", "args": {"image_index": 1}}}
</tool_call>
----- [Observation] -----
===SKILL_RESULT_START===
Generated HTML output based on screenshot analysis.
===SKILL_RESULT_END===

----- [Assistant Response] -----
× INCORRECT
<answer>
<!DOCTYPE html>
<html lang="en">
<head>
```

```
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Welcome to Our Healthcare Provider</title>
</head>
<body style="margin: 0; font-family: Arial, sans-serif;">

    <!-- Header -->
    <header style="background-color: orange; color: white; padding: 20px; text-align:
    ↪ center;">
        <h1>Welcome to Our Healthcare Provider</h1>
        <p style="font-style: italic;">We are a team of healthcare providers dedicated to
    ↪  providing the best care possible. Our mission is to improve the health and well-
    ↪ being of our patients.</p>
    </header>

    <!-- Featured Services -->
    <section style="background-color: white; padding: 20px;">
        <h2>Featured Services</h2>
        <ul>
            <li>General Practice</li><li>Cardiology</li><li>Pediatrics</li><li>Mental
    ↪ Health</li>
        </ul>
    </section>

    <!-- FAQ -->
    <section style="background-color: #f0f0f0; padding: 20px;">
        <h2>FAQ</h2>
        <div><strong>What services do you offer?</strong><p>We offer a wide range of
    ↪ medical services.</p></div>
    </section>

    <!-- Contact Us -->
    <section style="background-color: white; padding: 20px;">
        <h2>Contact Us</h2>
        <p>123 Main St, Anytown, USA</p>
        <p>Phone: (123) 456-7890</p>
        <p>Email: info@healthcareprovider.com</p>
        <form>
            <label for="name">Name:</label><br>
            <input type="text" id="name" name="name" style="width: 100%; padding: 8px;
    ↪ margin: 5px 0;"><br>
            <label for="email">Email:</label><br>
            <input type="email" id="email" name="email" style="width: 100%; padding: 8px;
    ↪  margin: 5px 0;"><br>
            <label for="message">Message:</label><br>
            <textarea id="message" name="message" rows="4" style="width: 100%; padding: 8
    ↪ px; margin: 5px 0;"></textarea><br>
            <input type="submit" value="Send" style="background-color: orange; color:
    ↪ white; border: none; padding: 10px 20px; cursor: pointer;">
        </form>
    </section>

    <!-- Footer -->
    <footer style="background-color: orange; color: white; text-align: center; padding:
    ↪ 10px;">
        <p>(c) 2023 Healthcare Provider. All rights reserved.</p>
    </footer>

</body>
</html>
</answer>
```

TikArt-8B (× Incorrect) – 3 turns

```
<thinking>Current available tools are insufficient for this task. I need to create a
    ↪ custom skill that can convert screenshot layouts into HTML code with proper
    ↪ styling and structure.</thinking>
<tool_call>
{"name": "create_skill", "arguments": {"description": "Convert a website screenshot into
    ↪ HTML code by detecting layout blocks, extracting text content, and assembling a
    ↪ complete HTML document with CSS styling."}}
</tool_call>
----- [Observation] -----
[Skill: screenshot-layout-to-html] created. SKILL.md:
---
name: screenshot-layout-to-html
```

```
description: Convert a website screenshot into HTML code by detecting layout blocks,
    ↪ extracting text content, and assembling a complete HTML document with CSS styling.
---
## Usage
### Scripts
- `scripts/generate_html.py`: generate HTML from screenshot analysis.
### Parameters
- `run_skill.args.image_index` (required): image selector for caller.
- `--output_html` (required): path to save generated HTML file.

----- [Assistant Response] -----
<thinking>The skill has been created. Now I will run it to generate the HTML.</thinking>
<tool_call>
{"name": "run_skill", "arguments": {"skill_name": "screenshot-layout-to-html", "
    ↪ entrypoint": "scripts/generate_html.py", "args": {"image_index": 1}}}
</tool_call>
----- [Observation] -----
===SKILL_RESULT_START===
Generated HTML output based on screenshot analysis.
===SKILL_RESULT_END===

----- [Assistant Response] -----
```

× **INCORRECT**

```
<answer>
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Welcome to Our Healthcare Provider</title>
    <style>
        body { font-family: Arial, sans-serif; margin: 0; padding: 0; background-color: #
    ↪ f4f7fa; }
        header { background: linear-gradient(135deg, #6e8efb, #a777e3); color: white;
    ↪ padding: 2rem; text-align: center; }
        .hero { background-image: url('image.png'); background-size: cover; background-
    ↪ position: center; height: 400px; display: flex; align-items: center; justify-
    ↪ content: center; color: white; text-align: center; }
        .hero-content { background: rgba(0,0,0,0.6); padding: 2rem; border-radius: 10px; }
    ↪
        .services { padding: 2rem; text-align: center; }
        .service-grid { display: grid; grid-template-columns: repeat(auto-fit, minmax(250
    ↪ px, 1fr)); gap: 1.5rem; margin-top: 1.5rem; }
        .service-card { background: white; padding: 1.5rem; border-radius: 8px; box-
    ↪ shadow: 0 2px 10px rgba(0,0,0,0.1); }
        footer { background: #333; color: white; text-align: center; padding: 1.5rem;
    ↪ margin-top: 2rem; }
    </style>
</head>
<body>
    <header>
        <h1>Welcome to Our Healthcare Provider</h1>
    </header>

    <section class="hero">
        <div class="hero-content">
            <h2>We are a team of healthcare providers dedicated to providing the best
    ↪ care possible. Our mission is to improve the health and well-being of our patients
    ↪ .</h2>
            <p>Your path to wellness starts here.</p>
        </div>
    </section>

    <section class="services">
        <h2>Our Services</h2>
        <div class="service-grid">
            <div class="service-card"><h3>Primary Care</h3><p>Expert care tailored to
    ↪ your needs.</p></div><div class="service-card"><h3>Specialty Care</h3><p>Expert
    ↪ care tailored to your needs.</p></div><div class="service-card"><h3>Telemedicine</
    ↪ h3><p>Expert care tailored to your needs.</p></div><div class="service-card"><h3>
    ↪ Mental Health Services</h3><p>Expert care tailored to your needs.</p></div>
        </div>
    </section>

    <footer>
        <p>123 Main St, Anytown, USA
Phone: (123) 456-7890
Email: info@healthcareprovider.com</p>
```

```
    </footer>
</body>
</html>
</answer>
```

Claude-Sonnet-4-6 (× Incorrect) – 3 turns

```
<thinking>None of the available tools can directly generate HTML from a screenshot. I
    ↪ will create a specialized skill to analyze the visual layout and produce the
    ↪ corresponding HTML code with appropriate styling.</thinking>
<tool_call>
{"name": "create_skill", "arguments": {"description": "Analyze a website screenshot to
    ↪ identify visual components and generate corresponding HTML with inline CSS that
    ↪ replicates the original layout and design."}}
</tool_call>
----- [Observation] -----
[Skill: screenshot-to-html] created. SKILL.md:
---
name: screenshot-to-html
description: Analyze a website screenshot to identify visual components and generate
    ↪ corresponding HTML with inline CSS that replicates the original layout and design.
---
## Usage
### Scripts
- `scripts/generate_html.py`: generate HTML from screenshot analysis.
### Parameters
- `run_skill.args.image_index` (required): image selector for caller.
- `--output_html` (required): path to save generated HTML file.

----- [Assistant Response] -----
<thinking>The skill has been created. Now I will run it to generate the HTML.</thinking>
<tool_call>
{"name": "run_skill", "arguments": {"skill_name": "screenshot-to-html", "entrypoint": "
    ↪ scripts/generate_html.py", "args": {"image_index": 1}}}
</tool_call>
----- [Observation] -----
[ERROR] Skill execution timed out after 120 seconds. The script did not produce output
    ↪ within the allowed time limit.

----- [Assistant Response] -----
The skill execution timed out. I will attempt to generate a basic HTML structure manually
    ↪  based on what I can infer from the screenshot.
```

× **INCORRECT**

```
<answer>
<html>
<body>
<p>Failed to generate matching HTML.</p>
</body>
</html>
</answer>
```

C FORGED TOOL GENERATION PROMPTS

The two-stage tool forging process uses separate prompts for planning and implementation. The tool generator G_ϕ remains fixed in both stages. In Stage 1, it receives a natural language tool description, the existing tool list, and runtime constraints. It then produces a structured tool specification. In Stage 2, it generates code for each script based on these specifications and follows the runtime interface and output requirements. The complete prompts are shown below.

Stage 1: Forged Tool Planning Prompt

```
[System]
You are a skill designer. Create a concise, reusable skill based on the user's description.

[User]
Skill description: {description}
Existing skills: {existing_skill_list}
Runtime constraints: {available_imports_and_constraints}

Return JSON with the following fields:
- skill_name: lowercase, dash-separated identifier
- skill_description: one-sentence summary
- requires_image: true if ANY script needs image input; false only when ALL scripts are text-only
- skill_overview_md: markdown overview covering scripts, parameters, workflow, and when to call
- scripts: list of specs [{path, purpose, params, notes}], where params is [{name, type, required,
    ↪ description}]

Rules:
1. Do NOT generate any code in this stage. Do NOT include script content or source fields.
2. Compare against existing skills before proposing. The skill name must not match or be confusingly
    ↪ similar to any existing skill. Do NOT propose a skill whose purpose substantially overlaps
    ↪ with an existing one.
3. Scripts are executed via CLI as --key value pairs. Design params to be explicit and CLI-friendly.
4. Use Python standard library first.
5. On success, scripts should print key results to stdout. On fatal errors, print to stderr and exit
    ↪ non-zero.
6. Every script path must end with .py or .sh.
```

Stage 2: Script Generation Prompt

```
[System]
You are a skill designer. Generate exactly one script for the specified target path.

[User]
Skill name: {skill_name}
Skill description: {skill_description}
Target script path: {target_path}
All script specs (from Stage 1): {full_specs_json}
Current target script spec: {current_spec_json}
Runtime constraints: {available_imports_and_constraints}

Runtime contract (must follow):
1. Scripts are launched as external commands. Use argparse to parse CLI arguments.
2. image_index is consumed by the runtime for image selection and is NOT forwarded to the script.
3. If the script needs image input, read from SKILL_IMAGE_PATH (local file path) or
    ↪ SKILL_IMAGE_DATA_URL (base64 data URL) environment variables.
4. Put executable code under `if __name__ == '__main__':` and ensure `python <script> --help` succeeds.

Output contract:
5. On success, print results to stdout. Output must reflect the actual input content -- do NOT produce
    ↪ generic or static placeholder text.
6. On fatal errors, print to stderr and exit non-zero. Do not print error text to stdout.

Return JSON: {"path": "<target_path>", "content": "<script_content>"}
```

D COMPLETE FORGED TOOL EXAMPLE

We use a screenshot-to-HTML task to illustrate a forged tool's description, input interface, and core code. Existing vision and OCR tools can extract page layout elements, but they may lack the functionality to convert these elements into HTML. MetaForge forges `layout-to-html-renderer` on demand to provide this functionality. The tool takes element types, text, positions, and screenshot dimensions as input and generates an HTML page that preserves their spatial layout.

Tool Description: `SKILL.md`.

Tool Description: `SKILL.md`

```
---
name: layout-to-html-renderer
description: Render detected webpage layout elements into an HTML page that preserves their spatial
    ↪ structure.
---

## Usage

### Scripts
- `scripts/render_layout.py`: convert detected layout elements into an HTML page.

### Parameters
- `run_skill.args.elements` (required): a list of page elements, each containing a type `type`, text `
    ↪ text`, and bounding box `bbox=[x,y,w,h]`.
- `run_skill.args.canvas_size` (required): original screenshot dimensions `[width,height]`.

### Call Contract
The script generates HTML from element positions and dimensions and prints the result to standard
    ↪ output.
```

Core Code: `scripts/render_layout.py`.

Core Code: `scripts/render_layout.py`

```
import html

def render_element(e):
    x, y, w, h = e["bbox"]
    text = html.escape(e.get("text", ""))
    style = (
        f"position:absolute;left:{x}px;top:{y}px;"
        f"width:{w}px;min-height:{h}px;"
    )

    if e["type"] == "input":
        return f'<input style="{style}" placeholder="{text}"/>'

    tag = {"button": "button", "heading": "h2"}.get(e["type"], "div")
    return f'<{tag} style="{style}">{text}</{tag}>'

def main(args):
    width, height = args["canvas_size"]
    body = "\n".join(render_element(e) for e in args["elements"])
    page = (
        f'<main style="position:relative;width:{width}px;'
        f'min-height:{height}px">{body}</main>'
    )
    print(f"<!doctype html>{page}")
```

Example Summary. `SKILL.md` describes the tool's purpose, input parameters, and call contract, while the code snippet implements its core execution logic. The script selects HTML tags by element type, sets positions and dimensions from bounding boxes, and combines the elements into a page. This example illustrates how tool forging translates a specific functional requirement into executable logic with a clearly defined interface.