THOTH: THEOREM-ORIENTED PARSING OF PLANAR GEOMETRY DIAGRAMS WITH MLLMS

Anonymous authors
Paper under double-blind review

ABSTRACT

When solving geometry problems, perceiving visual primitives is only the first step; identifying relevant theorems provides essential knowledge for subsequent reasoning. We formulate this process as *what to see*, then *what knowledge applies*, and finally *how to deduce*. Current MLLMs often entangle the latter two within lengthy reasoning trajectories and struggle to identify relevant theorems, leaving subsequent deduction susceptible to unsupported assumptions. We present **Thoth**, a planar geometry diagram parser that provides both perceived geometric *primitives* and question-relevant *theorems* to guide subsequent deeper *reasoning*. To align visual perception with theorem knowledge, we introduce a Theorem-oriented Formal Language (TOFL) and construct GT-210K, a large-scale synthetic dataset with TOFL annotations for scalable supervised fine-tuning. We then perform reinforcement learning with fine-grained process reward signals to further ground theorem predictions in supporting visual evidence and problem-specific constraints. Experiments show that **Thoth** achieves strong theorem grounding while improving primitive prediction. Across four geometry VQA benchmarks, the grounded primitives and theorems effectively improve downstream reasoning performance, demonstrating their value as explicit knowledge for subsequent deduction. Code, datasets, and models will be publicly available upon acceptance.

1 INTRODUCTION

Solving mathematical problems is an aspect of human intelligence in which humans clearly outperform other species. Therefore, geometric problem solving (GPS) is commonly used as an important part of benchmarking advanced AI models (Zhang et al., 2024; Chen et al., 2021), such as multimodal large language models (MLLMs), as its diagram-based nature tests both multimodal perception and reasoning abilities. Currently, the GPS capability of MLLMs still falls far behind the human level, attracting increasing research attention. Most existing studies focus on addressing failures in perceiving diagram primitives, *i.e.*, improving fine-grained perception of points, lines, and other basic geometric elements (Gao et al., 2025; Sun et al., 2026b; Zhang et al., 2026; 2025; Wang et al., 2026) due to largely out-of-distribution issues relative to pretraining data.

However, when analyzing a planar geometry problem, humans rarely perceive the diagram as merely a collection of visual primitives such as points and lines. To solve the problem, one instead intentionally organizes what one sees into higher-level mathematical deductive knowledge (Koedinger & Anderson, 1990), particularly by recognizing *mathematical theorems* from visually observed geometric configurations to inferable mathematically meaningful consequences. While this ability comes naturally to humans after years of mathematical education, current MLLMs often fail to identify the theorems required for diagram reasoning, ultimately limiting their GPS performance.

The key challenge for MLLMs in understanding theorems is that they are not directly observable, *i.e.*, they are latent concepts revealed through the geometric primitives and relations they govern. Thus, an essential step is to use visible primitives as cues to ground and bind these abstract theorems to concrete geometric entities. By developing an MLLM that jointly models low-level diagram primitives and high-level mathematical knowledge, we can learn and predict which theorems are applied in which diagrams and how mathematical principles connect with geometric primitives.

In this paper, we introduce **Thoth**, a novel theorem-oriented MLLM that parses planar geometry diagrams focusing beyond visible primitives to achieve grounded theorem-level understanding for

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.



Figure 1: Illustration of TOFL's three main description blocks for a diagram: primitives, scene-applicable theorems, question-relevant theorems. Theorems are grounded in supporting primitives as visual evidence for prediction, where $\mathrm{Support}()$ collects all relevant primitives and $\mathrm{Bind}()$ specifies their theorem-specific roles. We omit statements of the same type for clarity in this figure. Note if a diagram is not associated with a question, there will be no question-relevant theorems block.

downstream GPS tasks. To address the primitive-level bias of prior methods, we propose a Theorem-oriented Formal Language (TOFL), a structured representation that jointly models theorems, primitives, and their grounding dependencies. We further devise Geometry Theorem (GT-210K), a large-scale synthetic dataset with TOFL labels, enabling scalable training without laborious annotation.

Humans skim and scan the diagram for basic visual primitives, identify applicable theorems from what they see, and then select those most relevant to the specific question to guide further high-level reasoning. Analogously, **Thoth** learns such a pre-reasoning process through a two-stage supervised learning, and reinforces such a visual-theorem grounding through three reward designs: 1) **evidence-based theorem prediction**, which tightly binds theorem predictions to previously predicted primitives to reduce hallucination and ambiguity, while modeling their dependencies to promote mutual support, 2) **theorem-local reconstruction**, which emphasizes the fidelity of fine-grained local geometry supporting theorem prediction, and 3) **problem-specific geometric constraints**, which leverage relations stated in geometry questions, such as *a point lying on a circle*, to constrain TOFL generation and ensure accurate support information for theorem prediction.

Extensive experiments show that **Thoth** achieves strong theorem grounding together with improved primitive prediction, demonstrating that TOFL enables low-level perception and high-level mathematical knowledge to mutually reinforce each other. We further show that, with theorem information integrated, most downstream planar geometry reasoning tasks can be improved considerably. Also, Appendix C.6 shows **Thoth**'s ability to infer high-level principles from visual evidence provides a foundation for generalizing to diagrams across other subjects without domain-specific fine-tuning.

2 Theorem-oriented Formal Language

Solving planar geometry problems requires both accurate interpretation of diagram elements and the choosing of an appropriate deductive path toward the correct conclusion. While the prior work (Gao et al., 2025; Zhang et al., 2025; Wang et al., 2026) has largely focused on the quality of low-level perception targets, it does not enhance it by grounding in high-level reasoning. To bridge this gap, we propose a Theorem-oriented Formal Language (TOFL), which explicitly models the structural composition of geometric primitives and theorem instances for diagram-to-structure supervision. Figure 1 shows a typical TOFL instance comprising three description blocks, as described below.

Primitives. Similar to but extending prior work (Zhang et al., 2026; Wang et al., 2026), we define TOFL with a structured set of geometric primitives. Points are represented by normalized coordinates, other primitives are represented by their minimal defining attributes and compositional dependencies, *e.g.*, endpoints and radii, with basic entities serving as building blocks for higher-level geometric structures. Most importantly, TOFL primitives are designed to be faithfully rendered back into geometry diagrams through a deterministic geometric renderer, which supports subsequent diagram generation, self-supervised training, and evaluation of primitive prediction accuracy.

Scene-applicable Theorems. Since the same diagram may be paired with different questions, it is uncertain which theorem(s) will be useful for downstream reasoning. However, the geometric objects are typically associated with a certain set of applicable theorems, *e.g.*, a triangle naturally leads to the inclusion of the angle-sum theorem and the triangle inequality. We thus propose to treat



Figure 2: Overview of the proposed **Thoth** learning framework. A two-stage SFT cold start learns TOFL generation with scene-applicable and question-relevant theorem prediction. RL then strengthens theorem-oriented understanding through primitive-grounded evidence, theorem-local reconstruction, and problem-constrained reconstruction fidelity.

all scene-applicable theorems as the parsing target, leaving question-conditioned theorem prediction as a separate capability to be learned based on the scene-level theorem set. This makes TOFL a more structured learning target applicable across different geometry settings, even in the absence of a specific question. Each theorem instance is further grounded to its supporting primitives, keeping theorem prediction closely tied to concrete geometric objects while helping the model learn how primitive configurations give rise to theorem instances.

Question-relevant Theorems. Based on the specific question, relevant theorems are indicated in this block and ultimately used to support problem solving. Figure 1 shows that different questions lead to different selection of theorems even under the same scene-level theorem set. Accordingly, this block is only instantiated when a question accompanies the diagram.

GT-210K Dataset. We construct the Geometry Theorem (GT-210K) dataset with 210K synthetic diagrams paired with TOFL annotations. Our data engine samples from 90 theorem templates commonly included in the U.S. and the Chinese secondary-school syllabi, constructs diverse geometric configurations, and renders the resulting diagrams. The dataset includes both single- and multi-theorem compositions, with 4.19 theorems per diagram on average, covering common settings such as triangles, circles, and polygons. We further include hard negatives that resemble valid theorem configurations but violate key premises, reducing reliance on visual patterns alone. We use 200K samples for training and the rest for validation/testing. Further details are provided in Appendix A.2.

3 THOTH

Overview. We formulate planar geometry diagram parsing as a joint structured prediction problem that couples geometric perception with theorem-level understanding. Given a diagram $\mathbf{I} \in \mathbb{R}^{H\times W\times 3}$, an MLLM is expected to predict a unified TOFL sequence $\widehat{\mathbf{t}} = (t_1, t_2, \ldots, t_L)$, encoding both geometric primitives and grounded theorem instances. Importantly, primitive and theorem predictions are modeled in a unified generative distribution, such that theorem tokens are predicted in accordance with the geometric structures established by the preceding primitive tokens. To this end, as shown in Figure 2, we train **Thoth**, parameterized by θ, to autoregressively model the conditional distribution $p(\mathbf{t} \mid \mathbf{I})$ and generate the TOFL sequence with maximum conditional likelihood:

$$\widehat{\mathbf{t}} = \arg\max_{\mathbf{t}} p(\mathbf{t} \mid \mathbf{I}; \theta) = \arg\max_{\mathbf{t}} \prod_{i=1}^{L} p\left(t_i \mid t_{<i}, \mathbf{I}; \theta\right), \tag{1}$$

where L denotes TOFL sequence length, and $t_{<i}$ denotes all preceding tokens before the i-th token.

3.1 THOTH-SFT: TWO-STAGE COLD START ALONG THE HUMAN REASONING PATH

In this section, we introduce our supervised fine-tuning (SFT) design for enabling MLLMs to generate TOFL representations. Motivated by the progression of human GPS, we first establish a basic

understanding of the diagram, associate it with potentially applicable theorems, and then determine the question-relevant reasoning path. Accordingly, we decompose theorem learning into two stages.

Scene-level Theorem-oriented Parsing. In this initialization stage, we fine-tune the MLLM to produce the valid TOFL representation, including its serialization format, geometric primitives, and structured theorem templates. The model is trained to parse the diagram at the *scene level*, capturing all primitives present in the diagram together with all theorem instances supported by their geometric configurations. Given our synthetic dataset $\mathcal{D}_{\text{syn}} = \{(\mathbf{I}_i, \mathbf{t}_i)\}_{i=1}^{N_{\text{syn}}}$, the model is trained with a standard autoregressive cross-entropy objective:

$$\mathcal{L}_{\text{SFT}}^{(1)} = -\mathbb{E}_{(\mathbf{I},\mathbf{t})\sim\mathcal{D}_{\text{syn}}} \left[\log p\left(\mathbf{t} \mid \mathbf{I}; \theta\right)\right]. \tag{2}$$

Here, the sequence probability is autoregressively factorized over the TOFL tokens. Consequently, the model learns fine-grained geometric grounding while inferring theorem instances from the geometric configurations encoded by the preceding primitive tokens.

Theorem Grounding with Question Guidance. Although a diagram may suggest many applicable theorems, solving the problem ultimately requires selecting those relevant to the specific question and useful for deriving the right answer. To prepare the supervision needed for such a selection, we build an automatic LLM-based annotation pipeline that summarizes *detailed solution steps* from existing real QA datasets into question-relevant theorem labels, as detailed in Appendix B.1. This yields a dataset $\mathcal{D}_{\text{QA}} = \{(\mathbf{I}_i, \mathbf{q}_i, \mathbf{y}_i)\}_{i=1}^{N_{\text{sel}}}$, where $\mathbf{q}$ denotes the question and $\mathbf{y}$ is the reference sequence of question-relevant theorem labels. Because these real QA diagrams lack TOFL annotations for primitives and scene-level theorems, we additionally replay a small amount of synthetic data with full TOFL supervision during training to prevent these two capabilities from collapsing:

$$\mathcal{L}_{\text{SFT}}^{(2)} = -\mathbb{E}_{(\mathbf{I},\mathbf{Q},\mathbf{Y})\sim\mathcal{D}_{\text{QA}}} \left[\log p\big(\mathbf{t}' \mid \mathbf{I}, \mathbf{q}; \theta\big)\right] - \mathbb{E}_{(\mathbf{I},\mathbf{T})\sim\mathcal{D}_{\text{syn}}} \left[\log p\left(\mathbf{t} \mid \mathbf{I}; \theta\right)\right], \tag{3}$$

where for QA samples, $\mathbf{t}' = \arg\max_{\mathbf{t}} p(\mathbf{t} \mid \mathbf{I}; \theta)$ are generated by the model trained with Eq. (2) and additionally $\mathbf{t}'[\text{@question-relevant theorems}] = \mathbf{y}$.

3.2 Rewarding Grounded Visual-theorem Understanding

After learning the basic diagram-to-TOFL mapping through SFT, we further optimize **Thoth** with reinforcement learning (RL) to improve prediction of primitives and theorems, with particular focus on their binding and inferential dependencies. This enables direct optimization of fine-grained diagram properties that are difficult to capture through autoregressive likelihood alone.

Specifically, we employ Group Relative Policy Optimization (GRPO, Shao et al. (2024)) for policy optimization. Given an input prompt $\mathbf{p}$, the current policy π_θ generates a group of K TOFL candidates $\{\widehat{\mathbf{t}}^{(k)}\}_{k=1}^{K}$ via stochastic decoding. Each candidate receives a TOFL quality reward $r_{\text{TOFL}}^{(k)}$, from which the group-relative advantage is computed as:

$$\hat{a}^{(k)} = \left[r_{\text{TOFL}}^{(k)} - \text{mean}_j\left(r_{\text{TOFL}}^{(j)}\right)\right] / \text{std}_j\left(r_{\text{TOFL}}^{(j)}\right). \tag{4}$$

The reward r_{TOFL} evaluates each prediction for three complementary aspects: theorem grounding, reconstruction fidelity, and text-geometry consistency, as illustrated in Figure 3.

Grounding Theorems with Visual Evidence. Geometric primitives can be uniquely identified by attributes such as endpoint labels and coordinates, whereas theorems may exhibit multiplicity, *i.e.*, the same theorem can apply to different geometric objects within a single diagram and yield different conclusions, *e.g.*, two different right triangles within a diagram may both satisfy the Pythagorean theorem. Moreover, we empirically find that predicting theorem names



Figure 3: Illustration of our reward design for GRPO.

alone often leads to hallucinated instances unsupported by the diagram. To address this issue, we enhance **Thoth**'s ability to explicitly bind each theorem instance to its supporting visual primitives, providing visual evidence for theorem prediction and reducing MLLM hallucinations.

Let $\mathcal{P}_\eta = \{\widehat{\mathtt{t}}_\eta^1, \cdots, \widehat{\mathtt{t}}_\eta^\iota\}$ and $\mathcal{G}_\eta = \{\mathtt{t}_\eta^1, \cdots, \mathtt{t}_\eta^{\iota'}\}$ be the ι predicted and ι' reference instances of theorem η, *e.g.*, `T1` in Figure 1, respectively, carrying primitive-level grounding information via the TOFL statement $\mathrm{Bind}()$. We identify theorem instances via their bindings to visual primitives and perform matching according to their grounding compatibility: $\mathcal{M}_\eta = \mathrm{Match}\,(\mathcal{P}_\eta, \mathcal{G}_\eta)$, where $\mathcal{M}_\eta$ is the resulting set of matched predicted-reference theorem instance pairs, and $\mathrm{Match}(\cdot)$ performs one-to-one matching by comparing the theorem name and the overlap in $\mathrm{Bind}()$ (see Figure 1). This avoids incorrect matching by generation order when theorem instances are over-predicted or missing, while encouraging the model to distinguish each instance via its specific visual grounding:

$$r_{\text{bind}} = r_{\text{role}} + r_{\text{exact}} = \frac{1}{2|\mathcal{M}_\eta|} \sum_{(p,g)\in\mathcal{M}_\eta} \left(\frac{|\mathcal{B}(p) \cap \mathcal{B}(g)|}{|\mathcal{B}(g)|} + \mathbb{I}\left[\mathcal{B}(p) = \mathcal{B}(g)\right] \right), \tag{5}$$

where $\mathcal{B}(p)$ for $p \in \mathcal{P}\eta$ and $\mathcal{B}(g)$ for $g \in \mathcal{G}\eta$ denote the sets of role-primitive bindings in the predicted and reference $\mathrm{Bind}()$ statements, respectively, and $\mathbb{I}[\cdot] \in \{0, 1\}$ is the indicator function. The first term measures whether individual theorem arguments in the template are bound to the correct primitives, while the second requires the complete binding set to match exactly. See Appendix B.11.

Additionally, we introduce a theorem prediction reward to jointly refine scene-level recognition and question-conditioned selection, preventing either capability from collapsing during RL:

$$r_{\text{thm}} = (1 - \delta) r_{\text{scene}} + \delta r_{\text{selected}}. \tag{6}$$

where $\delta = 1$ for real QA diagrams and 0 for synthetic ones, r_{scene} evaluates scene-level theorem occurrences using multiset F1, while r_{selected} ensures the selected question-relevant theorems belong to the scene-level set and evaluates the selected set by exact matching and a Tversky score (Tversky, 1977), improving selection accuracy & discouraging trivial solutions that omit necessary theorems.

Visual Reconstruction. Inspired by prior work (Zhang et al., 2026; Zeng et al., 2026), we design TOFL as executable code that can be rendered back into the original diagram through a deterministic renderer $\varphi(\cdot)$, enabling indirect evaluation of TOFL prediction quality via reconstruction fidelity and supervision of primitive prediction on real diagrams without TOFL annotations. Let $\widehat{\mathbf{I}} = \varphi(\widehat{\mathbf{t}})$ denote the reconstructed diagram. We evaluate reconstruction fidelity at three complementary levels: pixel-level similarity using $r_{\text{MSE}} = 1 - \mathrm{MSE}\left(\widehat{\mathbf{I}}, \mathbf{I}\right)$, structural similarity measured by the SSIM (Wang et al., 2004) with $r_{\text{SSIM}} = \mathrm{SSIM}\left(\widehat{\mathbf{I}}, \mathbf{I}\right)$, and feature-level perceptual similarity measured using DINOv3 features (Siméoni et al., 2025) with $r_{\text{DINO}} = \cos\left(f_{\text{DINO}}\left(\widehat{\mathbf{I}}\right), f_{\text{DINO}}\left(\mathbf{I}\right)\right)$. These signals are combined into the global reconstruction reward:

$$r_{\text{global}} = r_{\text{recon}}\left(\widehat{\mathbf{I}}, \mathbf{I}\right) = \sum_{k\in\mathcal{K}} \frac{\lambda_k}{\sum_{j\in\mathcal{K}} \lambda_j} r_k\left(\widehat{\mathbf{I}}, \mathbf{I}\right), \tag{7}$$

where $\mathcal{K} = \{\mathrm{MSE}, \mathrm{SSIM}, \mathrm{DINO}\}$ denotes the set of complementary reconstruction criteria, with $\lambda_{\text{MSE}} = 0.6$, $\lambda_{\text{SSIM}} = 0.3$, and $\lambda_{\text{DINO}} = 0.1$ by default.

Unlike prior works, we design a novel theorem-local reconstruction reward r_{local} which extracts the supporting primitives of individual theorem instances via $\mathrm{Support}(\cdot)$ in TOFL (see Figure 1) and reconstructs the corresponding local subdiagrams. This improves fine-grained theorem-level reconstruction, emphasizes fine-grained primitive prediction and strengthens theorem-primitive binding as incorrect bindings distort the corresponding local reconstruction.

Specifically, let $\mathcal{T} = \bigcup_\eta \mathcal{G}_\eta$ denote all reference theorem instances, and let $\mathcal{S}(h)$ denote the closure of supporting primitives specified by $\mathrm{Support}()$ for theorem instance h. We restrict the renderer to $\mathcal{S}(h)$ and reward each local reconstruction using the same function as in Eq. (7):

$$r_{\text{local}} = \frac{1}{|\mathcal{T}|} \sum_{h\in\mathcal{T}} r_{\text{recon}}\left(\varphi(\widehat{\mathbf{t}}; \mathcal{S}(h)), \varphi(\mathbf{t}; \mathcal{S}(h))\right). \tag{8}$$

Geometry Prediction under Problem Constraints. In our experiments, we frequently observe geometric relation errors in diagrams reconstructed from predicted TOFL representations, such as points that should lie on a circle yet they drift away from its perimeter. However, geometry questions

often provide such relations explicitly as text statements, serving as an indication for the applicability of specific theorems, *e.g.*, *point A lies on circle O* or *point C is the midpoint of segment AB*, yet this information is typically not utilized for constraining diagram parsing.

To train the model to predict geometry under question constraints, we use synthetic diagrams with TOFL annotations to simulate the constraint information commonly provided in geometry questions, constructing a set of geometric constraints $\mathcal{C}$. Each constraint is converted into a natural-language statement using a predefined template $\psi(\cdot)$ and appended to the MLLM prompt $\mathbf{p}$:

$$\mathbf{p}_{\mathcal{C}} = \mathbf{p} \oplus [\psi(\xi)]_{\xi \in \mathcal{C}}\,, \qquad \widehat{\mathbf{t}} = \arg\max_{\mathbf{t}} p\left(\mathbf{t} \mid \mathbf{I}, \mathbf{p}_{\mathcal{C}}; \theta\right), \tag{9}$$

where $\oplus$ denotes prompt concatenation. For each constraint $\xi \in \mathcal{C}$, we compute its geometric residual $e_\xi = \mathrm{Res}_\xi(\widehat{\mathbf{t}})$ from the predicted primitives, *i.e.*, how far the predicted geometric relation is from fully satisfying the constraint, and convert it into a satisfaction score. For example, for $\mathrm{OnCircle}(A, c_1)$ with center O and radius r', the residual is defined as the difference between the point-to-center distance and the radius, $e_\xi = \left|\|A - O\|_2 - r'\right|$. The supported constraint types and their corresponding residual definitions are detailed in Appendix B.9. We aggregate the resulting rewards using two terms that capture average and worst-case satisfaction, jointly encouraging model outputs to remain consistent with the input geometric constraints:

$$s_\xi = \exp\left[-\left(\frac{e_\xi}{\tau}\right)^2\right], \qquad r_{\text{const}} = \frac{1}{|\mathcal{C}|}\sum_{\xi \in \mathcal{C}} s_\xi + \min_{\xi \in \mathcal{C}} s_\xi, \tag{10}$$

where τ is a scale parameter that balances the contribution of each constraint category.

Finally, we formulate the training reward for **Thoth** as the sum of three underscored reward groups:

$$r_{\text{TOFL}} = \underbrace{r_{\text{bind}} + r_{\text{thm}}}_{\text{theorem grounding}} + \underbrace{r_{\text{global}} + r_{\text{local}}}_{\text{reconstruction fidelity}} + \underbrace{r_{\text{const}}}_{\text{constraint satisfaction}}. \tag{11}$$

Here, due to differences in label availability, not all reward terms are applied to every sample. The full reward is used for synthetic data, while r_{bind}, r_{local} and r_{const} are omitted for real QA samples. We additionally use a set of unlabeled real diagrams for training, optimized solely with r_{global}. Since GRPO normalizes rewards within each prompt group with the same terms, reward scale differences across data types do not affect the resulting within-group relative advantages.

4 Experiments

4.1 Implementation Details

Training Configurations. We build **Thoth** on Qwen2.5-VL-7B-Instruct (Bai et al., 2025) and perform full-parameter optimization across all stages. SFT stages use a global batch size of 256 and learning rates of 2×10^{-7} for the vision encoder and 1×10^{-6} for the multimodal projector and language model. RL Stage uses GRPO with $K = 4$ rollouts per prompt and a learning rate of 5×10^{-7}. SFT stages are trained on 16 NVIDIA V100 GPUs, while the RL Stage uses 24 V100 GPUs, comprising 16 GPUs for policy training, 4 for rollout generation, and 4 for the reference model used to compute the KL-divergence penalty in the RL objective, weighted by $\beta = 0.03$ following (Zhang et al., 2026). Further details are provided in Appendix B.

Evaluation Settings. We evaluate **Thoth** at three problem levels. (1) *Primitive grounding.* We evaluate reconstruction fidelity on 600 synthetic and 600 Geo170K (Gao et al., 2025) diagrams using MSE, SSIM (Wang et al., 2004), and DINOv3-B (Siméoni et al., 2025) similarity, where higher reconstruction fidelity indicates more accurate primitive prediction. On the 600 synthetic diagrams, we additionally report primitive F1 and Tree Edit Distance (TED) to directly assess TOFL parsing accuracy. (2) *Theorem recognition.* We report scene-level theorem F1 and binding accuracy on 600 synthetic diagrams to assess theorem recognition and grounding to local primitives, and question-relevant theorem F1 on 200 GeoQA/UniGeo test diagrams to evaluate question-conditioned theorem selection. (3) *Downstream QA.* We feed TOFL representations produced by the frozen **Thoth** into frozen MLLM reasoners, and report answer accuracy on GeoQA (Chen et al., 2021), PGPS9K (Zhang et al., 2023), Geometry3K (Lu et al., 2021), and MathVerse (Zhang et al., 2024).

4.2 Main Results

We compare **Thoth** with a range of closed- and open-source MLLMs across the three evaluation dimensions introduced above. Note that we provide either templates or the complete candidate

Table 1: Performance comparison on primitive grounding. Top-3 methods are highlighted with cell shading, where darker shades indicate better performance and similar values receive similar shades.

Method	Synthetic Diagrams					Real Diagrams		
	Primitive F1↑	TED↓	MSE↓	SSIM↑	DINO↑	MSE↓	SSIM↑	DINO↑
Closed-source MLLMs								
GPT-5.6 Sol	0.3630	0.7202	0.0193	0.9258	0.9476	0.0415	0.7899	0.8286
Gemini 3.7 Flash	0.2947	0.7370	0.0162	0.9371	0.9335	0.0367	0.8029	0.7916
Open-source MLLMs								
Qwen2.5-VL-7B	0.0390	0.9087	0.2751	0.6689	0.4071	0.2765	0.6098	0.4647
Qwen3-VL-8B	0.0616	0.8261	0.0283	0.8829	0.7687	0.0656	0.7713	0.7608
LLaVA-OneVision-2-8B	0.0721	0.8405	0.0251	0.8968	0.6609	0.0453	0.8067	0.5677
InternVL3.5-8B	0.0395	0.8394	0.0260	0.8923	0.7126	0.0406	0.8057	0.6970
Gemma-4-12B	0.0579	0.8116	0.0275	0.8872	0.8803	0.0612	0.7781	0.8074
Formal Language-based Models								
Thoth – SFT	0.7942	0.1333	0.0155	0.9368	0.9674	0.0362	0.8055	0.7182
Thoth – RL	0.8384	0.1198	0.0068	0.9708	0.9750	0.0345	0.8139	0.7982

theorem list to all baselines, ensuring that performance primarily reflects their understanding ability rather than missing prior knowledge of formats or naming conventions, as detailed in Appendix B.7.

Primitive Grounding and Diagram Reconstruction. Below we evaluate whether the model faithfully perceives what is visually present. On synthetic diagrams, Thoth-RL achieves an MSE of 0.0068 versus 0.0162 for the second-best Gemini 3.7 Flash, and an SSIM of 0.9708 versus 0.9371, while its DINO reaches 0.9750 compared with 0.9476 for GPT-5.6 Sol. On real diagrams, Thoth-RL achieves lower MSE than Gemini 3.7 Flash (0.0345 vs. 0.0367) and higher SSIM than LLaVA-OneVision-2-8B (0.8139 vs. 0.8067). Although its DINO is slightly lower than the closed-source GPT-5.6 Sol, the clearly stronger MSE and SSIM indicate overall more faithful reconstruction.

Theorem Recognition and Binding. We evaluate MLLMs in predicting diagram-based theorems and grounding them in supporting visual primitives. Thoth consistently and substantially outperforms all baselines, achieving F1 of 0.8591 and 0.8634 on scene-applicable and question-relevant theorem prediction, exceeding the second-best MLLMs by 0.4957 and 0.2008, respectively. More importantly, Thoth reaches 0.9219 in primitive binding. This shows that Thoth not only recognizes theorems, but also provides interpretable theorem predictions grounded in explicit visual evidence.

Table 2: Performance comparison on theorem recognition.

Method	Synthetic Diagrams		Real Diagrams
	Scene Thm. F1 ↑	Binding Acc. ↑	Selected Thm. F1 ↑
Closed-source MLLMs			
GPT-5.6 Sol	0.3634	0.1491	0.6478
Gemini-3.7 Flash	0.3600	0.2123	0.6626
Open-source MLLMs			
Qwen2.5-VL-7B	0.1069	0.0036	0.2016
Qwen3-VL-8B	0.1880	0.0158	0.4077
LLaVA-OneVision-2-8B	0.1721	0.0157	0.1923
InternVL3.5-8B	0.1248	0.0465	0.2626
Gemma-4-12B	0.3051	0.0307	0.4715
Formal Language-based Models			
Thoth – SFT	0.8431	0.8792	0.8395
Thoth – RL	0.8591	0.9219	0.8634

Discussion: MLLMs' Limitations in Theorem Understanding. General MLLMs are rapidly improving in fine-grained visual perception. For example, some closed-source MLLMs may achieve reconstruction results close to or surpassing Thoth. However, this progress does not translate equally into theorem understanding. MLLMs remain limited in identifying theorems that provide important deductive cues for geometry reasoning, and are particularly weak at interpreting a theorem through its supporting visual evidence. For example, despite its strong primitive perception, GPT-5.6 Sol achieves only 0.1491 binding accuracy. This suggests that current MLLMs, despite their improved primitive perception, still struggle to understand the high-level mathematical relations underlying visual geometry, highlighting the importance of explicit theorem grounding beyond primitives alone for downstream reasoning.

Downstream Geometry Reasoning. We evaluate Thoth as a diagram parser by feeding generated TOFL to downstream MLLM reasoners as auxiliary context. As shown in Table 3, even for advanced closed-source MLLMs with already strong primitive perception, TOFL still brings clear gains, *e.g.*, +2.54 on MathVerse for Gemini-3.7 Flash, likely by providing more accurate theorem



Figure 4: Effectiveness validation of reward design and TOFL representation. (a) Reward function ablation radar, where metrics are normalized to a shared scale for relative comparison. (b) Gains from progressively adding TOFL components. Shaded regions denote standard deviations. (c) QA performance comparison using scene-applicable and question-relevant theorems in TOFL.

indications. TOFL brings even larger gains to open-source MLLMs, *e.g.*, +4.04 on MathVerse for Qwen3-VL-8B and +6.78 for its stronger 32B variant, likely by both reducing visual errors and providing theorem cues. This validates **Thoth** as an effective plug-and-play parser for diverse reasoners, which can be used without retraining even when the reasoner is updated.

Table 3: QA evaluation accuracy (%). Values in parentheses show the change relative to inputs without TOFL.

Model	Method	GeoQA	PGPS9K	Geometry3K	MathVerse
Closed-source MLLMs					
GPT-5.6 Sol	Vanilla	90.45	82.70	83.69	80.91
	+TOFL	89.52 (-0.93)	82.90 (+0.20)	83.69 (+0.00)	81.88 (+0.97)
Gemini-3.7 Flash	Vanilla	97.35	89.70	95.51	88.53
	+TOFL	98.67 (+1.32)	90.50 (+0.80)	96.67 (+1.16)	91.07 (+2.54)
Open-source MLLMs					
Qwen3-VL-8B	Vanilla	58.22	43.40	38.94	27.69
	+TOFL	60.61 (+2.39)	46.90 (+3.50)	42.93 (+3.99)	31.73 (+4.04)
Qwen3-VL-32B	Vanilla	65.38	54.60	37.27	26.47
	+TOFL	72.28 (+6.90)	56.80 (+2.20)	36.61 (-0.66)	33.25 (+6.78)
Gemma-4-12B	Vanilla	69.89	65.40	54.08	48.55
	+TOFL	73.61 (+3.72)	68.30 (+2.90)	57.07 (+2.99)	50.10 (+1.55)

4.3 Diagnostic Experiments

Effect of Reward Functions. We ablate rewards targeting theorem grounding r_{theorem} ($r_{\text{bind}} + r_{\text{thm}}$), reconstruction r_{recon} ($r_{\text{global}} + r_{\text{local}}$), and constraint satisfaction r_{const} to assess their contributions. As shown in Figure 4(a), removing r_{theorem} clearly degrades theorem recognition and binding, while removing r_{recon} and r_{const} reduces reconstruction quality, likely due to inaccurate visual and relational recovery. Importantly, comparing the full model with the $-r_{\text{theorem}}$ variant shows that theorem-oriented rewards also improve primitive prediction, suggesting that binding primitives to theorems also facilitates better primitive perception and organization.

Effect of TOFL Components. Figure 4(b) shows that progressively adding TOFL components consistently improves QA accuracy. Theorem information provides substantial gains beyond primitives alone, while explicit bindings further increase the average gain over the baseline from +2.20 to +3.48. On MathVerse, the gain reaches +4.04, exceeding the primitive-only gain by 2.49. These results suggest that accurate theorem information is crucial for geometric reasoning, and that providing theorems together with their supporting primitives helps the reasoner ground abstract concepts to specific visual elements and derive correct answers.

Is Question-relevant Selection Necessary for downstream GPS? From Figure 4(c), directly providing all scene-applicable theorems yields only marginal gains or even degrades performance compared with primitive-only inputs, *e.g.*, reducing accuracy by 0.61% on PGPS9K and 2.32% on Geometry3K. In contrast, inputting selected question-relevant theorems consistently improves performance, achieving an average gain of 2.50% over the scene-applicable counterpart. This again validates downstream reasoners' limitation in identifying the appropriate theorems required for problem solving (*cf.* Table 2). This highlights the value of explicit question-conditioned theorem selection.

Theorem Grounding and Primitive Understanding Mutually Reinforce Each Other. To verify whether TOFL's primitive-theorem binding facilitates theorem prediction, we remove all information from theorem instances except theorem names and train **Thoth** with SFT. RL is not applied

since the removed information makes r_{bind} and r_{local} unavailable. Table 4 shows that this variant reduces scene theorem F1 by 0.1221 compared with the full TOFL-trained Thoth-SFT.

We also compare with a model trained with TOFL containing only primitive block. Interestingly, we find that removing theorem information actually reduces primitive prediction accuracy, *e.g.*, with Primitive F1 decreasing by 0.0478 and reconstruction DINO by 0.0196. These results indicate that jointly modeling primitives and theorem semantics enables mutual enhancement, where theorem grounding benefits primitive understanding and vice versa.

Table 4: SFT results with ablated TOFL variants evaluated on synthetic diagrams, consistent with the main experiments.

TOFL	Thm. Grounding	Primitive Perception				
Variants	Scene Thm. F1↑	Prim. F1↑	TED↓	MSE↓	SSIM↑	DINO↑
+Primitive-only	–	0.7464	0.1577	0.0158	0.9262	0.9478
+Thm. name-only	0.7210	0.7394	0.1601	0.0155	0.9179	0.9342
Full	0.8431	0.7942	0.1333	0.0155	0.9368	0.9674

5 Related Works

Multimodal Geometry Problem Solving. GPS is an important testbed for evaluating both visual perception and reasoning in MLLMs. Recent studies have consistently identified primitive perception as a major weakness of current MLLMs. For example, Math Blind (Sun et al., 2026b) develops a diagnostic benchmark showing that failures in basic diagram perception can directly undermine mathematical reasoning, while Forgotten Polygons (Rudman et al., 2025) further reveals persistent weaknesses in geometric shape recognition. To address this issue, G-LLaVA (Gao et al., 2025) constructs large-scale geometry instruction data to improve the recognition of basic geometric elements, and Primitive Vision (Zhang et al., 2025) introduces a geometry-grounded visual encoder for fine-grained primitive perception. However, prior methods largely overlook the modeling of higher-level mathematical structures beyond primitives. We instead treat theorems as abstractions of higher-order relations and directly predict them to better support downstream reasoning.

Parsing Diagrams as Structured Code. Diagrams are structured visual representations, making image-to-code generation a natural direction for MLLMs. One line of work represents diagrams with executable code. For example, GeoTikzBridge and DaVinci (Sun et al., 2026a; Zeng et al., 2026) generate TikZ programs that preserve fine-grained visual structures and can be rendered back into high-fidelity diagrams. In geometry, symbolic representations have been increasingly explored. Early methods such as PGDPNet (Zhang et al., 2022) and Inter-GPS (Lu et al., 2021) explored formal representations for GPS and symbolic reasoning. GeoX (Xia et al., 2025) further brings formalized geometry into multimodal pre-training, while Geoparsing (Wang et al., 2026) extends formal representations from plane to solid geometry. SymVAE (Zhang et al., 2026) further uses logic forms as an intermediate representation for diagram parsing and reconstruction, enabling self-supervised learning for scalable training. We propose TOFL, which bridges low-level visual primitive perception and high-level theorem understanding, overcoming the primitive-centric limitation of existing formal languages to better support downstream mathematical deduction.

6 Conclusions

We have presented Thoth, an MLLM that parses planar geometry diagrams into structured representations of visual primitives and underlying theorems to support downstream reasoning. Beyond prior primitive-only representations, we introduce TOFL to jointly model primitives, theorems, and their grounding dependencies. We train Thoth with two-stage SFT for scene-level and question-relevant theorem recognition, followed by RL through theorem grounding, visual reconstruction, and problem-specific constraints. Our proposed explicit joint modeling of vision and theorems improves theorem grounding and primitive prediction, suggesting that low-level perception and high-level theorem understanding complement each other's inference. Experiments further demonstrate that injecting theorem information provides useful deductive cues for downstream geometry reasoning, suggesting broader potential for principle-driven diagrams in other scientific domains.

Limitations and Future Work. Despite its strong theorem understanding, Thoth is limited to a predefined library of 90 theorem templates. Future work will explore RAG (Lewis et al., 2020) and in-context learning (Brown et al., 2020) for open-set theorem recognition. In addition, Thoth currently supports only planar geometry; extending it to solid geometry will be explored in ThothV2.

AI USE STATEMENT

In this work, we used generative AI tools for language editing, AI-assisted coding, and scholarly navigation, such as identifying related work. We did not use generative AI tools for research ideation or to draft any figures or sections of the paper. We reviewed all AI-assisted work, including checking that every LLM-polished passage preserved our intended meaning and verifying AI-assisted code for correctness before using it in our experiments. We take responsibility for the final content of this work, including any text or artifacts produced with the aid of generative AI.

ETHICS STATEMENT

We are not aware of any ethical concerns or conflicts of interest associated with this work.

REPRODUCIBILITY STATEMENT

We provide details of the core design of TOFL and GT-210K in Section 2, the **Thoth** training framework in Section 3, and the main training and evaluation settings in Section 4.1. The appendix provides further details where needed, with Appendix A describing the TOFL format and data engine in more detail, and Appendix B providing additional training and evaluation configurations. We will release the code, GT-210K dataset, and trained model checkpoints upon acceptance to further facilitate reproduction and future research.

REFERENCES

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report, 2025.

Xiao Bi, Deli Chen, Guanting Chen, Shanhuang Chen, Damai Dai, Chengqi Deng, Honghui Ding, Kai Dong, Qiushi Du, Zhe Fu, et al. Deepseek llm: Scaling open-source language models with longtermism. *arXiv preprint arXiv:2401.02954*, 2024.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *NeurIPS*, 33:1877–1901, 2020.

Jiaqi Chen, Jianheng Tang, Jinghui Qin, Xiaodan Liang, Lingbo Liu, Eric Xing, and Liang Lin. Geoqa: A geometric question answering benchmark towards multimodal numerical reasoning. In *ACL Findings*, pp. 513–523, 2021.

Jiaqi Chen, Tong Li, Jinghui Qin, Pan Lu, Liang Lin, Chongyu Chen, and Xiaodan Liang. Unigeo: Unifying geometry logical reasoning via reformulating mathematical expression. In *EMNLP*, pp. 3313–3323, 2022.

Jiahui Gao, Renjie Pi, Jipeng Zhang, Jiacheng Ye, Wanjun Zhong, Yufei Wang, Lanqing Hong, Jianhua Han, Hang Xu, Zhenguo Li, et al. G-llava: Solving geometric problem with multi-modal large language model. In *ICLR*, volume 2025, pp. 3490–3511, 2025.

Kenneth R. Koedinger and John R. Anderson. Abstract planning and perceptual chunks: Elements of expertise in geometry. *Cognitive Science*, 14(4):511–550, 1990. ISSN 0364-0213.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *NeurIPS*, 33:9459–9474, 2020.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *ICLR*, 2019.

Pan Lu, Ran Gong, Shibiao Jiang, Liang Qiu, Siyuan Huang, Xiaodan Liang, and Song-Chun Zhu. Inter-gps: Interpretable geometry problem solving with formal language and symbolic reasoning. In *ACL*, pp. 6774–6786, 2021.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tianyi Tang, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report, 2025.

William Rudman, Michal Golovanevsky, Amir Bar, Vedant Palit, Yann LeCun, Carsten Eickhoff, and Ritambhara Singh. Forgotten polygons: Multimodal large language models are shape-blind. In *ACL Findings*, pp. 11983–11998, 2025.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Oriane Siméoni, Huy V Vo, Maximilian Seitzer, Federico Baldassarre, Maxime Oquab, Cijo Jose, Vasil Khalidov, Marc Szafraniec, Seungeun Yi, Michaël Ramamonjisoa, et al. Dinov3. *arXiv preprint arXiv:2508.10104*, 2025.

Jiayin Sun, Caixia Sun, Boyu Yang, Hailin Li, Xiao Chen, Yi Zhang, Errui Ding, Liang Li, Chao Deng, and Junlan Feng. Geotikzbridge: Advancing multimodal code generation for geometric perception and reasoning. In *CVPR*, 2026a.

Yanpeng Sun, Shan Zhang, Wei Tang, Aotian Chen, Piotr Koniusz, Kai Zou, Yuan Xue, and Anton Hengel. Math blind: Failures in diagram understanding undermine reasoning in mllms. In *ICLR*, volume 2026, pp. 124385–124422, 2026b.

Amos Tversky. Features of similarity. *Psychological review*, 84(4):327, 1977.

Peijie Wang, Ming-Liang Zhang, Jun Cao, Chao Deng, Dekang Ran, Pi Bu, Hongda Sun, Xuan Zhang, Yingyao Wang, Jun Song, et al. Geoparsing: Diagram parsing for plane and solid geometry with a unified formal language. In *ACL Findings*, pp. 29876–29903, 2026.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.

Renqiu Xia, Hancheng Ye, Wenjie Wu, Hongbin Zhou, Jiakang Yuan, Tianshuo Peng, Xinyu Cai, Xiangchao Yan, Bin Wang, Conghui He, et al. Geox: Geometric problem solving through unified formalized vision-language pre-training. In *ICLR*, volume 2025, pp. 15123–15141, 2025.

Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, et al. Mmmu-pro: A more robust multi-discipline multimodal understanding benchmark. In *ACL*, pp. 15134–15186, 2025.

Xingchen Zeng, Zhewei Su, Hengming Zhang, Juyong Jiang, Jiazhi Xia, and Wei Zeng. Davinci: Reinforcing visual-structural syntax in mllms for generalized scientific diagram parsing. In *ICLR*, volume 2026, pp. 88664–88699, 2026.

Kaizhong Zhang and Dennis Shasha. Simple fast algorithms for the editing distance between trees and related problems. *SIAM journal on computing*, 18(6):1245–1262, 1989.

Ming-Liang Zhang, Fei Yin, Yi-Han Hao, and Cheng-Lin Liu. Plane geometry diagram parsing. In *IJCAI*, 2022.

Ming-Liang Zhang, Fei Yin, and Cheng-Lin Liu. A multi-modal neural geometric solver with textual clauses parsed from diagram. IJCAI, 2023.

Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu, Aojun Zhou, Pan Lu, Kai-Wei Chang, Yu Qiao, et al. Mathverse: Does your multi-modal llm truly see the diagrams in visual math problems? In *ECCV*, pp. 169–186. Springer, 2024.

Shan Zhang, Aotian Chen, Yanpeng Sun, Jindong Gu, Yi-Yu Zheng, Piotr Koniusz, Kai Zou, Anton Van Den Hengel, and Yuan Xue. Primitive vision: Improving diagram understanding in mllms. In *ICML*, 2025.

Shan Zhang, Aotian Chen, Kai Zou, Jindong Gu, Yuan Xue, and Anton van den Hengel. Hierarchical process reward models are symbolic vision learners. In *CVPR*, pp. 22185–22194, 2026.

APPENDIX

A GT-210K Dataset 14

A.1 TOFL Representation 14

A.2 Data Engine 14

Design 14

90 Supported Theorems 14

Balanced Sampling and Multi-theorem Co-occurrence 16

Theorem-oriented Generation 16

Hard Negative 16

Verification 16

Data Preprocessing and Augmentation 16

B Additional Implementation Details 16

B.1 Real Diagram Annotation Pipeline 16

B.2 Training Data 17

B.3 Model Configuration 17

B.4 SFT Optimization 17

B.5 GRPO Optimization 18

B.6 Distributed Training Details 18

B.7 Prompt Configuration for Fair Comparison 18

B.8 QA Evaluation Configuration 19

B.9 Supported Constraints for Reward 20

B.10 Evaluation Metrics 21

B.11 Reward Implementation 22

C Additional Diagnostic Experiments 23

C.1 Backbone Analysis 23

C.2 Qualitative Reconstruction Comparison 23

C.3 Effect of Problem Constraint Reward 23

C.4 Inference Examples 26

C.5 Extending to More Theorems 30

C.6 Generalization to Broader Domains 32

A GT-210K DATASET

A.1 TOFL REPRESENTATION

Basic Format. Figure 5 illustrates the basic TOFL template, which organizes diagram information into three ordered description blocks.

I. A @primtives block defines geometric entities, including points, segments, circles, and polygons, together with explicitly given measurements.

II. A @scene_applicable_theorems block represents scene-level theorem instances. Each Theorem() specifies an identifier and a canonical theorem name, followed by Bind() to assign visual elements to theorem-specific roles, Support() to list the involved visual primitives and their types, Premise() to state the conditions required for theorem applicability, and Conclusion() to state the conclusion obtained after applying the theorem.

III. A @question_relevant_theorems block for selecting theorems based on a specific question, recording the theorem names required for solving it through Select() statements.

TOFL

```
@primitives
Point( . . . )
Segment( . . . )
 . . .

@scene-applicable theorems
Theorem(T1, theorem_name)
   Bind(role_1=primitive_1, . . .
)
   Support(Type: id, . . . )
   Premise( . . . )
   Conclusion( . . . )

@question-relevant theorems
Select(theorem_name)
```

Figure 5: The basic TOFL structure.

For synthetic samples without questions, the @question_relevant_theorems block is omitted. For theorem-free and hard-premise negatives, TOFL retains the @primitives block and marks *None* in the @scene_applicable_theorems block.

Canonical Ordering. All primitives and theorems are serialized in alphabetical order to ensure a consistent TOFL representation. This avoids penalizing equivalent geometric structures under token-level cross-entropy loss simply because they admit different serializations, *e.g.*, $\mathrm{Triangle}(\mathrm{A}, \mathrm{B}, \mathrm{C})$ and $\mathrm{Triangle}(\mathrm{A}, \mathrm{C}, \mathrm{B})$ represent the same triangle but correspond to different token sequences.

A.2 DATA ENGINE

Design. We build a *theorem-oriented* data engine that pairs mathematical diagrams with TOFL representations. For each diagram, a source theorem template is first sampled to define geometric constraints and instantiate the corresponding primitives. A verifier then computes the closure of all theorem instances supported by the resulting scene. The dataset contains 210K examples in total, with 200K for training, 9.4K for validation, and 600 for testing.

90 Supported Theorems. We define a set of 90 theorem templates drawn from secondary-school geometry curricula, primarily covering Chinese middle- and high-school mathematics and the U.S. Common Core geometry curriculum. The templates span seven geometric families: triangles and similarity, circles, quadrilaterals, lines, segments and angles, coordinate geometry, transformations, and conics. Figure 6 shows the theorem distributions across the full dataset.

Although GT-210K is constructed from a predefined registry of 90 theorem templates, these templates cover most commonly used theorems in school-level geometry problem solving. More importantly, **Thoth** is trained with detailed structured supervision that explicitly binds abstract theorem instances to their supporting visual primitives. As a result, the learned capability is not limited to memorizing specific theorem names, but also captures a more general ability to infer high-level knowledge from visual evidence. With appropriate prompting, this ability can further transfer to previously unseen theorems and even principles from other diagram domains, as demonstrated in Section C.5 and Section C.6. These results suggest that, despite being trained on a fixed theorem registry, **Thoth** learns a broader visual-to-principle abstraction that can extend beyond the original 90 theorems.



Figure 6: GT-210K theorem distribution. Theorem proportions are computed based on the number of diagrams containing each theorem.

Balanced Sampling and Multi-theorem Co-occurrence. We balance source theorem sampling across families to ensure sufficient coverage for model learning. After the source theorems are sampled, we identify all theorem instances supported by the resulting geometry and retain them without limiting their number, yielding an average of 4.19 theorems per diagram. Consequently, although source theorems are sampled evenly, the final theorem distribution is naturally uneven because the geometry constructed from one theorem often supports others. For example, when the triangle angle sum theorem is sampled as the source, triangle inequality naturally co-occurs. Figure 7 shows several common co-occurrence patterns. Retaining these co-occurrences allows the annotations to faithfully capture the mathematical relationships implied by the geometry.



Figure 7: Common theorem co-occurrences.

Theorem-oriented Generation. This process is very similar to object-oriented programming, where a theorem is defined as a template and instantiated when needed. Similarly, given the sampled theorem templates, we construct the required primitives according to their $\mathrm{Premise}()$ definitions. Labels, angles, lengths, and other attributes may randomly varied to generate diverse TOFL representations under the same underlying configuration. Primitive roles are recorded in $\mathrm{Bind}()$ to distinguish different instances of the same theorem template, while $\mathrm{Support}()$ lists all supporting primitives and their types.

Hard Negative. To reduce bias toward predicting theorem applicability, the dataset contains 5% theorem-free samples and 15% hard-premise negatives. Theorem-free samples contain visible primitives but support no registered theorem. Hard negatives resemble valid constructions while violating a decisive condition, *e.g.*, near-parallel or almost-cyclic configurations. Their @primitives annotations are retained, while the theorem blocks explicitly contain *None*.

Verification. During construction, we automatically check whether each diagram satisfies the required theorem conditions and remove invalid or degenerate cases. We also verify that all objects and annotations are complete and consistent with the generated diagram. In addition, we manually inspect generated diagrams together with their TOFL annotations using visualization tools.

Data Preprocessing and Augmentation. All images are rendered at 512×512 resolution and stored in JPEG format. To simulate the diversity of real mathematical diagrams, we randomly augment primitive rendering parameters, including line width (1.0–3.0 px), point size (18–42), font size (9–16), label offset (-4–4 px), Gaussian noise ($\sigma \in \{0, 0.01, 0.02, 0.03\}$), and JPEG quality (75–100), while keeping the underlying geometry encoded in TOFL unchanged. For evaluation images, we apply no augmentation to avoid confounding evaluation with non-diagram visual factors.

B Additional Implementation Details

B.1 Real Diagram Annotation Pipeline

Real-diagram datasets are typically annotated in QA form and lack theorem labels for learning question-relevant theorem prediction. We therefore search for datasets with detailed solution steps, where the theorems used in solving the problem are often implicitly indicated in the reasoning process. We therefore can operationally define question-relevant theorems as the theorem set used by the reference solution, rather than the exhaustive set of all mathematically valid solution paths. In total, we collect 5,135 samples from GeoQA (Chen et al., 2021) and UniGeo (Chen et al., 2022). Please note that the GeoQA images used for learning are drawn exclusively from the GeoQA training split, while the GeoQA QA results in Table 3 are evaluated on the disjoint test split.



Figure 8: Illustration of the real diagram annotation pipeline. Samples with detailed solution steps are fed into LLMs to infer the theorems used for solving the problem. The resulting diagrams with theorem annotations are then filtered by confidence and manual verification.

Table 5: Training data and supervision across the three stages of **Thoth**.

Stage	Training Data	Supervision	Objective
SFT-I	Synthetic diagrams (200K)	TOFL	SFT
SFT-II	Real QA diagrams (4.5K) Synthetic diagrams (4.5K)	Question-relevant theorems TOFL	SFT
RL	Real QA diagrams (4K) Real visual-only diagrams (5K) Synthetic diagrams (9K)	Question-relevant theorems Input diagrams TOFL	GRPO

However, manually converting these implicit indications into theorem labels is still impractical, so we build an automatic LLM-based annotation pipeline, as shown in Figure 8. Specifically, Qwen2.5-7B-Instruct (Qwen et al., 2025) proposes problem-relevant theorems from the detailed solutions, while DeepSeek-LLM-7B-Chat (Bi et al., 2024) verifies the proposals. Both models are instructed to select from the same theorem list used by our synthetic data engine and retain only high-confidence samples. We then discard samples on which the proposer and verifier disagree, followed by comprehensive manual checks to ensure that the selected theorems are consistent with the solution text. This results in 4.5K valid samples for training and 200 for testing.

B.2 Training Data

Table 5 summarizes the diagram types and supervision used at each training stage. Beyond the training data introduced in the main text, we highlight that RL additionally uses 5K unlabeled real diagrams from Geo170K (Gao et al., 2025) to provide self-supervised reconstruction signals for improving primitive perception.

B.3 Model Configuration

To ensure consistent evaluation, we use the same model configuration for the baselines and **Thoth** whenever applicable. Open-source models are evaluated in FP16, and **Thoth** is also trained in FP16. We use input images of 512×512 pixels and a maximum generation length of 2048 tokens. Greedy decoding is used during evaluation and SFT stages, while **Thoth** adopts stochastic decoding during GRPO training to generate diverse outputs from the same prompt. For models that support explicit reasoning controls, we disable reasoning whenever possible. Gemini 3.7 Flash is an exception because its thinking mode cannot be fully disabled. We therefore use the lowest available thinking level.

B.4 SFT Optimization

Table 6 summarizes the remaining optimization configurations not reported in the main text. SFT-I is trained for two epochs on synthetic data, while SFT-II is trained for six epochs on real diagrams mixed with synthetic replay to mitigate degradation of primitive and scene-level theorem under-

Table 6: Additional optimization configurations for different training stages.

Configuration	SFT-I	SFT-II	RL
Initialization	Qwen2.5-VL-7B	SFT-I ckpt.	SFT-II ckpt.
Duration	2 epoch	6 epochs	1,000 steps
Optimizer	AdamW	AdamW	AdamW
(β_1, β_2)	$(0.9, 0.999)$	$(0.9, 0.95)$	$(0.9, 0.95)$
Weight decay	0.01	0.01	0
Grad. clipping	1.0	1.0	1.0
LR scheduler	Cosine	Cosine	Constant
Warmup ratio	0.03	0.03	–

standing. SFT-I and II share the same optimization setup, using gradient checkpointing, AdamW (Loshchilov & Hutter, 2019), and a 0.03 warmup ratio. SFT-II additionally applies token-level loss weighting, assigning weight 1.0 to selected-theorem tokens, 0.1 to the teacher-generated scene prefix, and 0.3 to scene tokens associated with selected theorems.

B.5 GRPO Optimization

We adopt Group Relative Policy Optimization (GRPO) (Shao et al., 2024) for RL optimization, which estimates each rollout's advantage relative to candidates sampled from the same prompt, avoiding training a separate value model. Each optimizer update contains three types of prompts: synthetic, real QA, and real visual-only prompts. Each group initially samples $K = 4$ rollouts. For real QA groups with consistently incorrect and zero-variance selected-theorem rewards, four additional rollouts are sampled adaptively, increasing the group size to $K = 8$. If the group remains unsolved, a GT selected-theorem anchor is introduced as auxiliary supervision. Since QA rollouts are particularly prone to zero-variance rewards and therefore provide little effective GRPO advantage, we increase the number of real-QA prompt groups from one to four per optimizer update, providing more independent selection signals and stabilizing theorem-selection learning.

In addition to the trainable policy π_θ, we maintain a frozen reference policy π_{ref} initialized from the **Thoth**-SFT to prevent excessive policy drift. The resulting GRPO objective is

$$\mathcal{L}_{\text{GRPO}}(\theta) = \frac{1}{K}\sum_{k=1}^{K}\Bigg[\min\Big(\rho^{(k)}(\theta)\,\hat{a}^{(k)}, \text{clip}\Big(\rho^{(k)}(\theta),\,1-\epsilon,\,1+\epsilon\Big)\,\hat{a}^{(k)}\Big) - \beta\, D_{\text{KL}}(\pi_\theta(\cdot \mid \mathbf{p}) \,\|\, \pi_{\text{ref}}(\cdot \mid \mathbf{p}))\Bigg]. \tag{12}$$

where $\rho^{(k)} = \pi_\theta(\widehat{\mathbf{t}}^{(k)} \mid \mathbf{p}) / \pi_{\text{old}}(\widehat{\mathbf{t}}^{(k)} \mid \mathbf{p})$ denotes the policy ratio, $\hat{a}^{(k)}$ is the group-relative advantage defined in Eq. 4, and $\beta = 0.03$ controls KL regularization against the frozen reference policy. Here, ϵ denotes the clipping coefficient.

B.6 Distributed Training Details

To enable full-parameter optimization at scale, we employ Fully Sharded Data Parallel (FSDP) across all three training stages. SFT-I and II are each trained on 16 NVIDIA V100 GPUs. RL uses 24 V100 GPUs, with 16 GPUs for FSDP policy training, 4 GPUs for behavior-policy rollout generation, and 4 GPUs for frozen-reference inference. Policy training and inference are executed asynchronously and synchronized with at most one policy-version lag.

B.7 Prompt Configuration for Fair Comparison

We view the comparisons in Table 1 and Table 2 primarily as diagnostics of general-purpose MLLMs' primitive perception and theorem-grounding capabilities, rather than as a fully task-matched parser leaderboard, since general-purpose MLLMs are not specifically trained on TOFL. To minimize the advantage introduced by **Thoth**'s task-specific training as much as possible, we

Prompt: Primtive Perception and Scene-theorem Grounding

You are evaluating scene-applicable theorem grounding in a planar geometry diagram. Read the image and output only in the format specified below.

A scene-applicable theorem is any theorem whose required premises are satisfied by the visible geometric configuration, regardless of whether it is needed to solve a particular question. List all theorem instances supported by the scene.

The complete theorem template registry is provided. Use the exact canonical theorem names and instantiate their binding slots with visible objects.

THEOREM TEMPLATES

⟨*all serialized theorem templates*⟩

OUTPUT FORMAT

@primitives
Point(ID,x,y)
Segment(ID,P,Q)
Line(ID,P,Q)
Circle(ID,center=O,radius=r; through=A,B,C)
Triangle(PQR)
Quadrilateral(PQRS)
Given(FACT)

⟨*detailed primitive naming and output rules, e.g., coordinate range*⟩

@scene_applicable_theorems
⟨*instantiate all applicable theorem units from the provided templates*⟩

Use one complete unit per grounded theorem instance. Do not explain. Do not use markdown. Do not output natural language reasoning outside the required formal language.

Figure 9: Prompt for fair comparison on primitive perception and scene-theorem grounding. The TOFL format and theorem templates are provided to reduce the influence of format familiarity.

provide explicit TOFL format instructions and the complete supported theorem registry in the baseline prompts, reducing the influence of format familiarity on evaluation. Their outputs are further constrained by a strict output format, so that performance reflects diagram understanding and parsing ability with minimal influence from format familiarity. We evaluate question-relevant theorem selection separately from primitive and scene-level theorem prediction, allowing the model to focus on each task while reducing the error accumulation observed in practice. The corresponding prompts are shown in Figure 9 and Figure 10.

B.8 QA Evaluation Configuration

TOFL is designed to support downstream reasoning by using a task-specific diagram parser to compensate for the limited theorem understanding of existing open- and closed-source MLLMs, while also providing more accurate primitive information. We first use **Thoth** to generate and cache TOFL representations for the full benchmark from the diagram, question, and available choices, so that the same parsed results are shared across different reasoners. After obtaining the complete TOFL representation, we remove the @scene_applicable_theorems block and only retain the corresponding theorem binding information for the selected theorems.

For QA evaluation, each MLLM receives the original image, question, choices, predicted TOFL, and a short reading guide, and is instructed to solve the problem with the aid of TOFL. The prompt is shown in Figure 11. In Table 3, the Baseline and +TOFL settings use the same model and decoding configuration, differing only in whether TOFL context is provided. We report the final QA accuracy together with the corresponding change introduced by TOFL.

Prompt: Question-relevant Theorem Selection

You are evaluating question-relevant theorem selection for a planar geometry diagram. Given the image and question, output only the theorem names from the list below that are needed to solve the problem.

THEOREM NAMES

⟨*all canonical theorem names, one per line*⟩

OUTPUT FORMAT

@selected_theorem_units
Select(TheoremName)

Use one Select() line for each theorem needed for solving the question.
Do not explain. Do not use markdown. Do not output natural language reasoning outside the required formal language.

QUESTION

⟨*question*⟩

CHOICES

⟨*numbered choices, when available*⟩

Figure 10: Prompt for fair comparison on question-conditioned theorem selection. The diagram, question, answer choices, and complete theorem list are provided as input.

Table 7: All nine supported constraint types. Every residual is mapped to a score in $[0, 1]$ for reward.

Constraint	Residual e_ξ
OnCircle(P,c1)	$\big\lvert \lVert P - O \rVert_2 - r \big\rvert / r$
PointOnLine(P,A,B)	h / L
PointOnSegment(P,A,B)	$\sqrt{h^2 + o^2} / L$
Parallel(AB,CD)	$\lvert \mathbf{u} \times \mathbf{v} \rvert / (LK)$
Perpendicular(AB,CD)	$\lvert \mathbf{u} \cdot \mathbf{v} \rvert / (LK)$
EqualLength(AB,CD)	$\lvert L - K \rvert / \max(L, K)$
EqualAngle(ABC,DEF)	$\lvert \angle ABC - \angle DEF \rvert / \pi$
Midpoint(M,A,B)	$\lVert M - (A + B)/2 \rVert_2 / L$
Concyclic($P_1, \ldots, P_n$)	$\max_i \big\lvert \lVert P_i - O \rVert_2 - r \big\rvert / r$

Notation. $\mathbf{u} = B - A$, $\mathbf{v} = D - C$, $L = \lVert \mathbf{u} \rVert_2$, and $K = \lVert \mathbf{v} \rVert_2$. For point–line and point–segment constraints, h denotes the perpendicular distance to line AB, while o measures how far the projected point lies outside segment AB. For concyclicity, (O, r) denotes the fitted circle.

B.9 Supported Constraints for Reward

We consider nine common geometric constraints that frequently appear in problem statements: OnCircle, PointOnLine, PointOnSegment, Parallel, Perpendicular, EqualLength, EqualAngle, Midpoint, and Concyclic. For each constraint ξ, we define a normalized residual e_ξ measuring how well the predicted geometry satisfies it, as summarized in Table 7. Distance-based residuals are normalized by the corresponding radius or segment length, while directional and angular constraints use normalized geometric differences.

Prompt: Downstream QA with TOFL

SYSTEM PROMPT

You are a careful mathematical reasoner. Follow the requested final-answer format.

USER PROMPT

Solve the following geometry problem carefully.

Additional geometric information parsed automatically from the diagram is provided below. Use it as structured evidence. It may contain occasional parsing errors.

TOFL READING GUIDE

@primitives records the geometric elements parsed from the diagram. Point(...) specifies labeled points and their normalized coordinates, while Segment(...), Line(...), Circle(...), Triangle(...), and Quadrilateral(...) describes visible geometric structures. Given(...) records measurements or relations explicitly provided by the diagram.

@question_relevant_theorems contains the theorems selected as relevant to the current question. Each selected theorem is associated with Bind(...), which maps theorem-specific roles to concrete geometric primitives. Support(...) lists the primitives involved in the theorem, while Premise(...) and Conclusion(...) describe its required conditions and resulting inference.

Use TOFL as structured evidence together with the problem statement. Prioritize the selected theorems and their locally grounded diagram structures in your reasoning.

TOFL

⟨*predicted TOFL*⟩

QUESTION

⟨*question*⟩

CHOICES

⟨*label: choice text*⟩

OUTPUT FORMAT

Final Answer: ⟨*answer*⟩

Figure 11: Prompt for downstream QA with TOFL as additional structured evidence.

B.10 Evaluation Metrics

We provide definitions of several evaluation metrics that are not fully specified in the main text.

Primitive Perception. For synthetic diagrams, primitive prediction in TOFL is evaluated using F1 and Tree Edit Distance (TED). A primitive is matched when its type, identifier, and parsed attributes agree with the reference, with an absolute tolerance of 0.01 for numerical attributes, *e.g.*, point coordinates. Specifically, Primitive F1 is computed as:

$$\mathrm{F1} = \frac{2\sum_i \mathrm{TP}_i}{2\sum_i \mathrm{TP}_i + \sum_i \mathrm{FP}_i + \sum_i \mathrm{FN}_i}. \tag{13}$$

TED measures structural differences in parsed TOFL. This avoids directly measuring differences in the serialized text, which may overlook the underlying semantic structure. Each TOFL prediction is parsed into an ordered tree containing primitive and theorem nodes. Theorem nodes include the theorem name, $\mathrm{Bind}()$, $\mathrm{Support}()$, $\mathrm{Premise}()$, and $\mathrm{Conclusion}()$. Binding keys and support identifiers are sorted within each node. We then compute the Zhang-Shasha tree edit distance (Zhang & Shasha, 1989) and normalize it by the larger tree:

$$\mathrm{TED} = \frac{1}{N}\sum_{i=1}^{N} \frac{d_{\mathrm{tree}}(T_{p,i}, T_{g,i})}{\max\{|T_{p,i}|, |T_{g,i}|\}}, \tag{14}$$

where $T_{p,i}$ and $T_{g,i}$ denote the ordered TOFL trees parsed from the prediction and reference of sample i, respectively. $d_{\text{tree}}(\cdot,\cdot)$ denotes the Zhang-Shasha tree edit distance and $|T|$ denotes the number of tree nodes.

Theorem Grounding. Let $n_{p,i}(\eta)$ and $n_{g,i}(\eta)$ denote the predicted and reference occurrence counts of theorem η in diagram i, respectively. Scene theorem F1 is computed as the average multiset F1 over diagrams:

$$\text{F1}_{\text{scene}} = \frac{1}{N}\sum_{i=1}^{N}\frac{2\sum_{\eta}\min\{n_{p,i}(\eta), n_{g,i}(\eta)\}}{\sum_{\eta} n_{p,i}(\eta) + \sum_{\eta} n_{g,i}(\eta)}. \tag{15}$$

Here, $\min\{n_{p,i}(\eta), n_{g,i}(\eta)\}$ counts the correctly predicted occurrences of theorem η. Selected theorem F1 is computed in the same way, using the theorem labels annotated in the @question_relevant theorems block of real diagrams.

For theorem instances matched by theorem name, binding accuracy is formulated as:

$$\text{Acc}_{\text{bind}} = \frac{B_{\text{exact}}}{B_{\text{name}}}, \tag{16}$$

where B_{name} is the number of theorem pairs with the same theorem name, and B_{exact} is the number of these pairs whose $\text{Bind}()$ contents match the reference exactly.

B.11 Reward Implementation

We provide implementation details for the reward terms whose specific computation is not fully described in the main text.

Theorem-instance Matching. In Eq. (5), we compute the binding reward based on theorem-instance pairs obtained through $\text{Match}(\cdot)$. Specifically, each predicted-reference pair is scored according to its role binding and the overlap of supporting primitives. We then obtain the matched instance set $\mathcal{M}_\eta$ through one-to-one bipartite matching that maximizes the total matching score:

$$\mathcal{M}_\eta = \text{Match}\left(\mathcal{P}_\eta, \mathcal{G}_\eta\right) = \arg\max_{\mathcal{M}\subseteq\mathcal{P}_\eta\times\mathcal{G}_\eta}\sum_{(p,g)\in\mathcal{M}} w(p,g), \tag{17}$$

subject to each predicted or reference instance appearing in at most one matched pair. Here, $w(\cdot,\cdot)$ measures agreement between theorem-specific role-primitive bindings, and the resulting matched pairs are then used to compute the instance-level binding reward described in the main text.

Scene-level Theorem Prediction. We reward scene-level theorem recognition using multiset F1, retaining repeated occurrences of the same theorem:

$$r_{\text{scene}} = 2\sum_{\eta}\min\{n_p(\eta), n_g(\eta)\}\Big/\left(\sum_{\eta} n_p(\eta) + \sum_{\eta} n_g(\eta)\right), \tag{18}$$

where $n_p(\eta)$ and $n_g(\eta)$ denote the predicted and reference occurrence counts of theorem η, respectively. This allows the reward to distinguish multiple instances of the same theorem in one diagram, rather than treating the theorem as simply present or absent.

Question-conditioned Selection. For samples with questions, selected question-relevant theorem names are compared as sets. Specifically, let S_p and S_g denote the predicted and reference theorem sets, with $\text{TP} = |S_p \cap S_g|$, $\text{FP} = |S_p \setminus S_g|$, and $\text{FN} = |S_g \setminus S_p|$. The selection reward r_{select} combines exact matching and Tversky similarity (Tversky, 1977):

$$E = \mathbb{I}[S_p = S_g], \qquad T_{\alpha,\beta} = \frac{\text{TP}}{\text{TP} + \alpha\text{FP} + \beta\text{FN}}, \tag{19}$$

where $\alpha = 0.4$ and $\beta = 0.6$ control the penalties for selecting extra theorems and missing required ones, respectively. This rewards both complete selection and partial overlap with the reference theorem set. We further measure whether the selected theorems are supported by the predicted scene-level theorem inventory using a count-based consistency term:

$$C_{\text{cons}} = \frac{\sum_{\eta}\min\{n_s(\eta), n_p(\eta)\}}{\sum_{\eta} n_s(\eta)}, \tag{20}$$

Table 8: Performance of Thoth across different backbones.

Backbone	Model	Synthetic Diagrams					Real Diagrams			
		MSE↓	SSIM↑	DINO↑	Scene Thm. F1 ↑	Binding Acc. ↑	MSE↓	SSIM↑	DINO↑	Selected Thm. F1 ↑
Qwen2.5-VL-7B	Base	0.2751	0.6689	0.4071	0.1069	0.0036	0.2765	0.6098	0.4647	0.2016
	Thoth– RL	0.0068	0.9708	0.9750	0.8591	0.9219	0.0345	0.8139	0.7982	0.8634
LLaVA-OneVision-2-8B	Base	0.0251	0.8968	0.6609	0.1721	0.0157	0.0453	0.8067	0.5677	0.1923
	Thoth– RL	0.0160	0.9657	0.9743	0.8439	0.9321	0.0322	0.8297	0.7903	0.8437

where $n_s(\eta)$ and $n_p(\eta)$ denote the selected and scene-level occurrence counts of theorem η, respectively. The overall selection reward is

$$r_{\text{selected}} = E + T_{\alpha,\beta} + EC_{\text{cons}}. \tag{21}$$

The consistency term encourages question-relevant theorems to be selected from those recognized scene theorems, rather than being predicted independently. Since this term is gated by E, an incorrect but self-consistent prediction does not receive an additional reward.

C Additional Diagnostic Experiments

C.1 Backbone Analysis

Thoth remains effective across different backbones. As shown in Table 8, although Qwen2.5-VL-7B and LLaVA-OneVision-2-8B exhibit noticeable performance gaps in their original forms, both achieve comparable levels of theorem-oriented understanding after training with our method. Scene-level theorem F1 reaches 0.8591 and 0.8439, binding accuracy reaches 0.9219 and 0.9321, and question-relevant theorem F1 reaches 0.8634 and 0.8437, respectively, representing substantial improvements over the corresponding backbones. Consistent and significant gains are also observed in diagram reconstruction across both backbones. These results indicate that the effectiveness of Thoth is not tied to a particular backbone, but primarily arise from learning structured TOFL that equip the model with both low-level and high-level diagram parsing capabilities.

C.2 Qualitative Reconstruction Comparison

Primitive perception can be learned and evaluated indirectly through diagram reconstruction. We therefore compare the reconstruction ability of Thoth with existing MLLMs. Figures 12 and 13 show qualitative results on synthetic and real diagrams, respectively. Existing open-source models often produce diagrams that differ noticeably from the originals, especially for more complex geometric structures. In contrast, Thoth can reconstruct complex and less common configurations more accurately. Compared with strong proprietary models such as GPT-5.6 Sol, Thoth also makes fewer structural and scale-related errors. For example, it is less likely to add extra edges or miss existing ones, and it better preserves the original shape and proportions of diagram elements. Overall, these results show that Thoth maintains strong diagram reconstruction ability even though it is mainly designed for high-level relational and theorem-oriented understanding.

C.3 Effect of Problem Constraint Reward

We visualize the qualitative effect of r_{const} in Figure 14. As shown, the case studies cover several common geometric relations, including point-on-circle, midpoint, perpendicular, and equal-angle constraints. The Thoth variant trained with r_{const} better satisfies these constraints in the predicted diagram geometry, mainly through predicting coordinates that better preserve the relative geometric relations. Such geometric consistency can be critical for reconstruction fidelity. For example, in the midpoint case at the bottom-left, the failure of point A to lie on segment GN may lead to additional structural errors, such as introducing spurious connections between A and G/N.

Interestingly, we observed that even when a constraint is not explicitly provided in the prompt, the model tends to improve predictions with similar geometric patterns. For example, the positions of point B in the top-left case and point C in the bottom-left case are improved despite not being explicitly constrained. Overall, r_{const} helps maintain high-fidelity predicted geometry by reducing noisy geometric deviations during generation.



Figure 12: Qualitative comparison of reconstruction capability between **Thoth** and existing MLLMs on synthetic diagrams.



Figure 13: Qualitative comparison of reconstruction capability between **Thoth** and existing MLLMs on real diagrams.



Figure 14: Qualitative effect of constraint reward r_{const}. This reward enables **Thoth** to preserve consistency between predicted geometry and the key constraints provided in the problem statement.

C.4 Inference Examples

We visualize representative outputs of **Thoth** in Figure 15, Figure 16, and Figure 17. Given a diagram, **Thoth** parses its geometric primitives and identifies the scene-applicable theorems supported by the visual configuration. When a specific question is provided, it further selects the theorems relevant to solving that problem. For example, in Figure 17, since the central angle $\angle BOD$ and the inscribed angle $\angle BAD$ subtend the same arc BD, the **CentralAngleTwiceInscribed** theorem gives $\angle BAD = 44°$. As $ABCD$ is a cyclic quadrilateral, based on the **CyclicQuadOppAngles** theorem, its opposite angles are supplementary, yielding $\angle BCD = 180° - 44° = 136°$. By explicitly predicting such theorem information together with its visual grounding, **Thoth** provides structured deductive cues that directly support downstream problem solving.

Input Diagram



@primitives

Prediction



@scene_applicable_theorems

TheoremUnit(T1,SameSegmentAngles)
Bind(circle=c1,chord_endpoints=[A,C], points=[B,D])
Support(Point:A,B,C,D,O;Segment:AC; Circle:c1)
Premise(OnCircle(A,c1))
Premise(OnCircle(C,c1))
Premise(OnCircle(B,c1))
Premise(OnCircle(D,c1))
Premise(SameArcSide(B,D,chord=AC))
Conclusion(EqualAngle(ABC,ADC))

TheoremUnit(T2,TriangleAngleSum)
Bind(triangle=[A,B,C])
Support(Point:A,B,C)
Premise(NonCollinear(A,B,C))
Conclusion(SumAngle(ABC,BCA,CAB)= 180)

TheoremUnit(T3,TriangleAngleSum)
Bind(triangle=[A,C,D])
Support(Point:A,C,D)
Premise(NonCollinear(A,C,D))
Conclusion(SumAngle(ACD,CDA,DAC)= 180)

TheoremUnit(T4,TriangleInequality)
Bind(triangle=[A,B,C])
Support(Point:A,B,C;Segment:AB,AC,BC)
Premise(NonCollinear(A,B,C))
Conclusion(AB+BC>AC)
Conclusion(AB+AC>BC)
Conclusion(AC+BC>AB)

TheoremUnit(T5,TriangleInequality)
Bind(triangle=[A,C,D])
Support(Point:A,C,D;Segment:AC,AD,CD)
Premise(NonCollinear(A,C,D))
Conclusion(AC+CD>AD)
Conclusion(AC+AD>CD)
Conclusion(AD+CD>AC)

Figure 15: Thoth output example on a GT-210K synthetic sample without a question.



@primitives



@scene_applicable_theorems

TheoremUnit(T1,TriangleAAS)
Bind(A=C,B=D,C=E,D=F,E=A,F=B)
Support(Point:A,B,C,D,E,F;Segment:BF,CE;Triangle:CDE,FAB)
Premise(EqualAngle(CDE,FAB))
Premise(EqualAngle(DEC,ABF))
Premise(EqualLength(CE,BF))
Conclusion(CongruentTriangle(CDE,FAB))

TheoremUnit(T2,TriangleAngleSum)
Bind(triangle=[A,B,F])
Support(Point:A,B,F;Triangle:FAB)
Premise(NonCollinear(A,B,F))
Conclusion(SumAngle(ABF,BFA,FAB)=180)

TheoremUnit(T3,TriangleAngleSum)
Bind(triangle=[C,D,E])
Support(Point:C,D,E;Triangle:CDE)
Premise(NonCollinear(C,D,E))
Conclusion(SumAngle(CDE,DEC,ECD)=180)

TheoremUnit(T4,TriangleInequality)
Bind(triangle=[A,B,F])
Support(Point:A,B,F;Segment:AB,AF,BF)
Premise(NonCollinear(A,B,F))
Conclusion(AB+BF>AF)
Conclusion(AB+AF>BF)
Conclusion(AF+BF>AB)

TheoremUnit(T5,TriangleInequality)
Bind(triangle=[C,D,E])
Support(Point:C,D,E;Segment:CD,CE,DE)
Premise(NonCollinear(C,D,E))
Conclusion(CD+DE>CE)
Conclusion(CD+CE>DE)
Conclusion(CE+DE>CD)

Figure 16: Thoth output example on a GT-210K synthetic sample without a question.

Input Diagram



Prediction



Question: **As shown, quadrilateral ABCD is inscribed in circle O. If ∠BOD = 88°, what is the measure of ∠BCD?**

Choices: **88° | 92° | 106° | 136°**

@primitives

Point(A,-0.405,-0.824)
Point(B,0.712,0.287)
Point(C,0.127,0.814)
Point(D,-0.650,0.632)
Point(O,-0.089,-0.014)
Segment(AB,B,A)
Segment(AD,D,A)
Segment(BC,B,C)
Segment(BO,B,O)
Segment(CD,C,D)
Segment(DO,D,O)
OnCircle(A,c1)
OnCircle(B,c1)
OnCircle(C,c1)
OnCircle(D,c1)
Circle(c1,center=O,radius=0.856;
through=A,B,C,D)

@question_relevant_theorems

Select(TheoremUnit(T1,
CentralAngleTwiceInscribed))
Bind(circle=c1,center=O,
arc_endpoints=[B,D],inscribed_point=A)
Support(Point:A,B,D,O;Circle:c1)
Premise(CenterOf(O,c1))
Premise(OnCircle(A,c1))
Premise(OnCircle(B,c1))
Premise(OnCircle(D,c1))
Conclusion(Angle(BOD)=2*Angle(BAD))

Select(TheoremUnit(T2,CyclicQuadOppAngles))
Bind(quadrilateral=[A,B,C,D],circle=c1)
Support(Point:A,B,C,D;Circle:c1)
Premise(Cyclic(A,B,C,D,c1))
Conclusion(Supplementary(ABC,ADC))
Conclusion(Supplementary(BCD,DAB))

Figure 17: Thoth output example on a real UniGeo diagram. The @scene_applicable_theorems block is omitted for brevity. Binding information is appended to the Select() statements, consistent with the QA input format.



Figure 18: Evaluation on selecting theorems unseen during training. Each theorem is specified by its typical visual pattern for model selection. **Thoth** accurately identifies the appropriate theorem and provides the corresponding visual evidence.

C.5 Extending to More Theorems

Although **Thoth** is trained with a fixed registry of 90 theorems, which is typically sufficient to cover common geometry problem solving, its theorem understanding can be extended to unseen theorems based on its core ability to select theorems from visual evidence. Considering the lack of training-derived internal knowledge of these new theorems, we prompt **Thoth** to select from a new theorem pool based on specified visual patterns. To this end, we describe common visual patterns and their corresponding theorems in natural language, and introduce 12 new theorems that are excluded from training to evaluate unseen-theorem recognition. The prompt used for this setting is illustrated in Figure 19. As shown in Figure 18, the model can correctly select the appropriate theorem by jointly interpreting the diagram and the prompt, while also accurately describing the visual evidence it perceives. We attribute this generalization ability to the close similarity between this output requirement and the format of theorem instances in TOFL, which combines theorem names with their bindings, allowing the model to analogically transfer this capability even when the new theorems are specified in natural language.

Prompt: Unseen Geometry Theorem Selection

USER PROMPT

You are given a plane-geometry diagram and several candidate geometric theorems.

Each theorem is accompanied by a description of the visual evidence that typically supports it. Inspect the diagram carefully, and determine which theorem is most directly supported by the visible objects and their relations.

Focus on whether the required visual entities and relations are present in the diagram. Use the provided descriptions as the criteria for selection.

Exactly one of the listed theorems is applicable to the diagram. Select exactly one listed theorem. Abstention is prohibited. Do not introduce a new theorem.

CANDIDATE THEOREMS

Equal-Area Triangles on Same Base and Parallels
Typical visual evidence: Two triangles share a visible base, and their apexes lie on a marked line parallel to that base.
High-level relation: The triangle areas are equal because their base and altitude are equal.
Disqualifying evidence: The apex line is not supported as parallel to the base. The triangles do not share the same base.

Exterior Angle of Two Secants
Typical visual evidence: Two lines from one exterior point each meet the same circle twice, with both near and far intersections visible.
High-level relation: The exterior secant angle equals half the difference of the intercepted arcs.
Disqualifying evidence: Either ray touches the circle only once or misses it entirely. The common vertex lies inside the circle.

⟨*remaining ten candidate theorems*⟩

IMAGE

⟨*attached plane-geometry diagram*⟩

OUTPUT FORMAT

Selected principle: ⟨*theorem name*⟩
Evidence: ⟨*one concise sentence describing the visible entities and relations that support the selection*⟩

Figure 19: Prompt for extending **Thoth** to unseen geometry theorems by specifying new theorems and their supporting visual relations in natural language.

C.6 Generalization to Broader Domains

Our key motivation is to enable a parser to ground high-level relational rules and patterns in visual evidence. This capability naturally extends to diagrams across multiple disciplines, each governed by its own domain-specific rules or principles. For example, solving physics problems also requires identifying the relevant laws or theorems.

We therefore evaluate **Thoth**'s generalization ability in recognizing high-level principles on diagrams from other domains. Although these diagrams can differ substantially from mathematical geometry diagrams in both visual organization and domain-specific principles, we argue that the ability to infer high-level principles from visual evidence can still transfer across domains. By describing the **visual patterns** $\rightarrow$ **domain principles** relationship in the prompt as new-domain knowledge, **Thoth** can analogically transfer the **visual cues** $\rightarrow$ **theorems** association learned from geometry diagrams to new domains. Figure 20 shows the prompt we use to guide **Thoth** in generalizing to concepts from new domains. Note that in this experiment, we let **Thoth** describe the identified principles in natural language, avoiding domain-specific theorem template design and making cross-domain transfer more flexible.

We conduct case studies on the multi-disciplinary MMMU-Pro benchmark (Yue et al., 2025), covering optics, mechanics and kinematics, circuits, and computer science. As shown in Figures 21, 22, and 23, although **Thoth** has never been exposed to principle information from these domains during fine-tuning, it can recognize the problem-relevant principles more accurately than its base model in these cases. We attribute this advantage to stronger visual perception and visual-relation modeling. For example, in the first case of Figure 21, despite sufficient information in both the diagram and the question, Qwen2.5-VL-7B fails to abstract the configuration into a non-zero net force and therefore misses Newton's Second Law. In contrast, **Thoth** correctly combines the visible evidence to infer this relation and identify the appropriate principle. In the second case of Figure 22, Qwen2.5-VL-7B exhibits a clear visual hallucination by claiming that there is *a conductor moving through a magnetic field*, whereas the evidence identified by **Thoth** remains consistent with the diagram.

We also report quantitative results on the Physics subset of MMMU-Pro, using diagrams associated with questions from mechanics, electromagnetism, optics, thermodynamics and gases, modern physics, and waves. Following the same downstream QA setting as in Table 3, we use the theorem labels and supporting evidence produced by **Thoth** as additional information, together with the original image and question, for downstream reasoners. Table 9 shows that introducing such principle-level knowledge also improves physics problem solving, *e.g.*, for Gemma-4-12B achieves an overall improvement of +8.34%. This demonstrates that Thoth's theorem-level prediction ability can transfer to other diagram domains, and that accurate principle information can also benefit downstream reasoning across different types of diagrams.

Table 9: QA evaluation accuracy (%) on the Physics subset of MMMU-Pro.

Model	Method	Acc.	Δ
Qwen2.5-VL-7B	Vanilla	36.7	–
	+**Thoth**	40.0	+3.3
Qwen3-VL-8B	Vanilla	46.7	–
	+**Thoth**	55.0	+8.3
Gemma-4-12B	Vanilla	63.3	–
	+**Thoth**	71.7	+8.4

These results suggest that **Thoth** can be extended to other principle-based diagram domains by transferring its ability to infer high-level knowledge from low-level visual information, even when it has not been exposed to domain-specific principles during fine-tuning.

Prompt: Principle Selection on New Domains

USER PROMPT

You are given a scientific diagram, the corresponding problem, and several candidate physical principles.

Each principle is accompanied by a description of the visual evidence that typically supports it. Inspect the diagram and problem carefully, and determine which principle is most directly supported by the visible objects and their relations and is most useful for solving the problem.

Focus on whether the required visual entities and relations are present in the diagram and whether the principle is relevant to the problem. Use the provided descriptions as the criteria for selection.

CANDIDATE PRINCIPLES

Newton's Second Law
Typical visual evidence: An identifiable body is acted on by one or more directed force arrows. The forces are visibly unbalanced, or their labeled magnitudes and directions indicate a non-zero resultant. An acceleration arrow or another explicit cue of changing motion may be associated with the same body.
High-level relation: The net force acting on a body determines its acceleration, with the acceleration directed along the net force.

Thin-Film Interference
Typical visual evidence: A thin layer is bounded by two nearby interfaces. An incoming light ray produces multiple reflected or transmitted paths at the two boundaries, often with wavelength, phase, or path-length information shown.
High-level relation: The optical outcome depends on the phase or path difference between coherent rays reflected or transmitted by the thin film.

⟨*remaining candidate principles*⟩

IMAGE

⟨*attached image*⟩

QUESTION

⟨*corresponding problem*⟩

OUTPUT FORMAT

Selected principle: ⟨*principle name*⟩
Evidence: ⟨*one concise sentence describing the visible entities and relations that support the selection*⟩

Figure 20: Prompt for extending **Thoth** to new domains by specifying new principles and their supporting visual relations in natural language.



Question: The cart of mass 10 kg shown above moves without frictional loss on a level table. A 10 N force pulls on the cart horizontally to the right. At the same time, a 30 N force at an angle of 60° above the horizontal pulls on the cart to the left. Which of the following describes a manner in which this cart could be moving?

Thoth-RL

Selected principle: Newton's Second Law

Evidence: The diagram shows a 10 kg cart with two forces acting on it: a 10 N force to the right and a 30 N force at 60 degrees above the horizontal. These forces can be used to calculate the net force and subsequent acceleration according to Newton's Second Law.

Qwen2.5-VL-7B

Selected principle: Force Equilibrium

Evidence: The diagram shows two forces acting on the cart, one horizontal and one at an angle, with no indication of acceleration or equilibrium conditions.



Question: A strong bar magnet is held very close to the opening of a solenoid as shown in the diagram. As the magnet is moved away from the solenoid at constant speed, what is the direction of conventional current through the resistor shown and what is the direction of the force on the magnet because of the induced current? Current through resistor/Force on Magnet

Thoth-RL

Selected principle: Faraday's Law of Induction

Evidence: A magnet and a conducting coil move relative to each other, indicating changing magnetic flux through the coil.

Qwen2.5-VL-7B

Selected principle: Motional Electromotive Force

Evidence: The diagram shows a conductor (the solenoid) moving through a magnetic field, which is typical for inducing an electromotive force.



Question: The accompanying diagram shows the path that a light ray takes passing through three transparent materials. The indices of refraction in materials 1, 2, and 3 are n_1, n_2, and n_3, respectively. Which of the following best describes the relation between the indices of refraction?

Thoth-RL

Selected principle: Snell's Law

Evidence: An incident ray crosses a medium interface and a transmitted ray changes angle relative to the normal. Medium indices or angles may be labeled.

Qwen2.5-VL-7B

Selected principle: Total Internal Reflection

Evidence: A ray approaches a lower-index medium from a higher-index medium, with a critical-angle cue or a reflected ray and no transmitted ray.

Figure 21: Cross-domain generalization in principle understanding on samples from the MMMU-Pro benchmark. **Thoth** shows stronger ability than its base model to infer problem-relevant principles from newly specified principle-evidence relations in the prompt.



Question: In the circuit shown below, each of the resistors has the same resistance. A voltmeter with very high resistance is connected between two points in the circuit. Between which two points of connection would the voltmeter read zero?

Thoth-RL

Selected principle: Parallel-Circuit Voltage Relation

Evidence: The diagram shows two parallel paths with resistors, and the voltage across each path is the same.

Qwen2.5-VL-7B

Selected principle: Kirchhoff's Current Law

Evidence: The diagram shows two junctions with currents entering and leaving, indicating the sum of currents entering a junction equals the sum of currents leaving it.



Question: These six motion diagrams show the motion of a particle along the x-axis. Rank the accelerations corresponding to these motion diagrams, from most positive to most negative. There may be ties.

Thoth-RL

Selected principle: Discrete Motion Kinematics

Evidence: The diagram shows successive positions and directional arrows for multiple objects, indicating motion and changes in velocity.

Qwen2.5-VL-7B

Selected principle: Faraday's Law of Induction

Evidence: The diagram shows a conductor moving through a magnetic field, with arrows indicating the direction of motion and the magnetic field lines, suggesting a changing magnetic flux that would induce an electromotive force.



Question: A light ray enters a block of plastic and travels along the path shown. By considering the behavior of the ray at point P, determine the speed of light in the plastic. (10^8 m/s)

Thoth-RL

Selected principle: Snell's Law

Evidence: A ray crosses a boundary between air and plastic, with labeled angles.

Qwen2.5-VL-7B

Selected principle: Total Internal Reflection

Evidence: The ray approaches the boundary at P from the plastic medium at an angle greater than the critical angle, and there is no transmitted ray visible.

Figure 22: Cross-domain generalization in principle understanding on samples from the MMMU-Pro benchmark. **Thoth** shows stronger ability than its base model to infer problem-relevant principles from newly specified principle-evidence relations in the prompt.



Question: Which of the following DFAs represent the set of strings where the difference between the number of as and the number of bs is a multiple of 3. In all cases the alphabet is {a, b}.

Thoth-RL

Selected principle: Finite-State Transition and Acceptance

Evidence: The diagram shows a finite-state machine with states labeled 0, 1, 2, and 3, and transitions labeled b. States 0 and 3 are marked as start and accepting states, respectively. This directly supports the finite-state transition and acceptance principle.

Qwen2.5-VL-7B

Selected principle: None

Evidence: The diagram shows a finite-state machine with states labeled 0, 1, 2, and 3, and transitions labeled 'a' and 'b'. There are no visible accepting states or a clear mechanism to count the difference between the number of 'a's and 'b's.



Question: Consider a network with 6 routers R1 to R6 connected with links having weights as shown in the diagram. All the routers use the distance vector based routing algorithm to update their routing tables. Each router starts with its routing table initialized to contain an entry for each neighbour with the weight of the respective connecting link. After all the routing tables stabilize, how many links in the network will never be used for carrying any data?

Thoth-RL

Selected principle: Weighted-Graph Optimization

Evidence: The diagram shows a graph with numerical edge labels, suggesting optimization based on these weights.

Qwen2.5-VL-7B

Selected principle: Adjacency-List Representation of a Directed Graph

Evidence: The diagram shows a directed graph with labeled edges connecting nodes, which is typical of an adjacency-list representation.



Question: Suppose you are given the below data, and you want to apply a logistic regression model for classifying it into two given classes. You are using logistic regression with L1 regularization, where C is the regularization parameter, and w1 and w2 are the coefficients of x1 and x2. Which of the following option is correct when you increase the value of C from zero to a very large value?

Thoth-RL

Selected principle: Linear Class Separability

Evidence: Points from two classes are plotted and can be separated into distinct regions by a single straight line.

Qwen2.5-VL-7B

Selected principle: K-Means Assignment to Nearest Centroid

Evidence: Data points are distributed in a feature space with marked cluster centers, and points appear spatially closer to one centroid than others.

Figure 23: Cross-domain generalization in principle understanding on samples from the MMMU-Pro benchmark. Thoth shows stronger ability than its base model to infer problem-relevant principles from newly specified principle-evidence relations in the prompt.