DO REASONING MODELS EVEN START? DECOMPOSING COT CONTROLLABILITY

Anonymous authors
Paper under double-blind review

ABSTRACT

The headline metric for chain-of-thought (CoT) controllability—the fraction of reasoning traces that comply *perfectly* with an instruction—conflates three quantities and is blind to one of them: how well a model *maintains* a constraint once it has started. Low CoT controllability is a pillar of the safety case for CoT monitoring, so *why* it is low decides whether that case is robust or one design choice away from failing. We grade 272k reasoning traces with position-resolved graders and treat the first violation as a time-to-event outcome, separating onset (does the model ever adopt the constraint), maintenance (slips per 1,000 words once adopted) and exposure (trace length), and we intervene on onset by opening the reasoning with a short compliant prefix. Across six open-weight models from three families (Qwen3, OLMo-3-Think, gpt-oss), the uppercase and alternating-case constraints are never started in five: every uppercase trace fails at the first word, and constrained traces carry the style no more often than unconstrained ones; gpt-oss-120b starts uppercase in half of its traces and drops it within a few words, and the two gpt-oss models start the required opening string but rarely close with it. Keyword suppression, in contrast, has no onset failure and leaks from the first word at a rate set by how often the question calls for the word. The benchmark score for "reason in uppercase" is 0% for every model we test, yet after a 20-word compliant prefix the slip rates of Qwen3-8B/32B and OLMo-3-7B/32B span 13$\times$ (95% CI 10–17), improve with scale within two of three families, and Qwen3-32B keeps an entire trace in uppercase 38–45% of the time, largely by continuing its context rather than by following the instruction.

1 INTRODUCTION

Monitoring the chain of thought of reasoning models is one of the few oversight tools that scales with capability (Korbak et al., 2025; Baker et al., 2025). It fails if a model can choose what its reasoning shows. Chen et al. (2026) measure this ability with CoT-CONTROL, which asks models to solve problems while obeying a constraint on their reasoning ("use only uppercase letters", "do not use the word *chromosome*"). They report that reasoning models control their CoT 0.1–36% of the time while controlling their final output 37–69% of the time, conclude that CoT controllability is "unlikely to be a failure mode of CoT monitorability" today, ask developers to track the number for every release, and state plainly that "the mechanism behind low controllability is not well understood."

A number nobody can explain cannot say when it will change. The CoT-CONTROL score is binary at the trace level: a 3,000-word trace with one stray capital letter is a failure. Such a score is the product of three different things, $\Pr(\text{success} \mid L) = \pi \prod_{t=1}^{L}(1 - h_t)$, where π is the probability that the model adopts the constraint at all (*onset*), h_t is the hazard of a first slip at position t given compliance so far (*maintenance*), and L is the length of the trace (*exposure*). The three have different safety readings. If scores are low because traces are long, the metric says little about evasion, where the thing to hide is short. If they are low because models never start, the property is fragile: whatever changes the first tokens changes the score. Only if models start and cannot sustain the constraint is low controllability the robust property the safety case wants.

We measure the three components separately: position-resolved graders return *where* a trace first violates its constraint, that position is a right-censored time-to-event outcome, and from it we estimate π, the slip rate λ (slips per 1,000 words among adopters) and length-standardised compliance C_L.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: **The binary score hides what varies.** (a) Kaplan–Meier compliance curves for Qwen3-32B: uppercase is violated at word 0 by every trace; keyword suppression starts compliant and leaks. (b) Opened with a compliant prefix, models differ sharply in how long they keep the style; at 32B most of the effect survives without any instruction (dashed); dotted: plain run, no prefix (at zero). (c) Uppercase first-slip hazard over words 20–100 after a 20-word prefix (95% question-clustered bootstrap intervals); the CoT-CONTROL score for this constraint is 0% for all six models.

We then intervene on onset alone by opening the model's reasoning with 20 or 100 words of its own baseline trace rewritten to comply, with a no-instruction control to separate instruction following from context continuation, on three open reasoning-model families (Qwen3 at four sizes, OLMo-3 and gpt-oss at two) and along one post-training trajectory.

Our contributions:

- **A decomposition of CoT controllability** into onset, maintenance and exposure, with position-resolved graders for eight CoT-CONTROL constraints, censoring-aware estimators and a Shapley attribution of score gaps (§2). A 20-word compliant prefix raises π from 0.09–0.11 to 0.66–0.84 in Qwen3 while the 95% intervals for the change in the time-averaged slip rate lie within $[0.59, 1.74]$: the components can be moved separately, though not independently.
- **Three regimes in six models from three families** (§3): constraints that are *never started* ($\pi = 0$; every trace opens with the model's habitual first word), constraints with *no onset failure that leak* from the first word (suppression), and constraints that are *started and lost* within a few words (the gpt-oss-120b case constraints; OLMo-3-7B lowercase), under an operational definition applied to every cell (App. Table 24).
- **A hidden maintenance contrast** (§4): with the plain score fixed at 0%, uppercase slip rates on a common window after a prefix range from 46.5 to 3.6 per 1,000 words across the four main Qwen3 and OLMo-3 models (75.0 at Qwen3-4B), fall about 5× with scale within Qwen3 and OLMo-3 (not in gpt-oss), and at Qwen3-32B the style is sustained even without an instruction.
- **Where it comes from** (§5): in OLMo-3-7B the opener predates post-training, while maintenance is lost at the long-CoT SFT stage; and **re-attributions** (§6) of the size and CoT-vs-output gaps reported by Chen et al. (2026).

We also report what did not hold, including refuted pre-registered predictions (App. A).

2 METHOD

The benchmark. CoT-CONTROL (Chen et al., 2026) appends a reasoning constraint to questions from GPQA (Rein et al., 2023), MMLU-Pro (Wang et al., 2024) and Humanity's Last Exam (Phan et al., 2025): *suppression* (avoid question-specific keywords and their synonyms; ignore the question), *addition* (open and close the reasoning with a fixed string; end every sentence with "safe"; insert "meow" between all words) and *stylistic* (lowercase; uppercase; alternating case), each prompt also forbidding mention of the constraint. Programmatic graders return 1 only under full compliance; the *controllability score* is the mean. Baselines apply the same constraints to the final answer (*output*) or to reasoning written inside `<output_reasoning>` tags with thinking disabled (*external CoT*). It reports that controllability rises with parameter count, falls with reasoning length, effort, difficulty and RL training, and is $\geq 70\%$ for external CoT; we use the released prompts unchanged.

Position-resolved graders. We re-implement each programmatic grader so that it returns the first violating *unit* (alphabetic words for case constraints, sentences for "safe", inter-word gaps for "meow", word positions for suppression, two checkpoints for the opening/closing string) and its word index, plus unit and violation counts; "no violating unit" recovers the binary verdict, and a fuzz test over 6,000 synthetic traces confirms equality with the released graders for all eight constraints. The LLM-judged "ignore the question" constraint has no position and is excluded. Robustness variants: a masked case grader (skipping notation, units and code) and a keyword-only suppression grader.

Time-to-event formulation. For trace i let T_i be the word index of the first violation and L_i the trace length. We observe $(\min(T_i, L_i), \mathbb{1}[T_i < L_i])$: a trace that ends compliant, or is cut off by the token limit, is *right-censored* at its length rather than counted as a success at all lengths. The estimators assume non-informative censoring; truncation at a fixed budget is, natural trace end need not be, so cross-model claims rest on the 20–100-word window, where few traces have ended (App. B). We estimate the survival function $S(t) = \Pr(T > t)$ with the Kaplan–Meier estimator (Kaplan & Meier, 1958) and summarise each (model, constraint) cell by

- π, the *adoption rate*: one minus the fraction of traces whose first violation falls in the first $w = 20$ words; a trace that ends compliant before word w counts as adopted, so $\pi \geq$ the binary score always (this is the one definition used in every table and in the attribution; such traces are rare in the reasoning channel but not in the external channel, whose share of short traces App. Table 8 reports). The window is an operational choice, so every regime assignment is checked against $w \in \{1, 50\}$, the constraint-native first unit and the fitted onset mass $\hat{\pi}$ of the onset-mixture-frailty model (App. Table 23); where $\hat{\pi} = 1$ we call the window quantity *early survival* $S(w)$, not adoption;
- λ, the *slip rate*: first violations after w per 1,000 words of exposure among adopters, i.e. the per-word hazard h_t averaged over the observed exposure. Because h_t falls with position, λ depends on the observed length, so cross-model statements use the hazard on a fixed window, $h_{20\text{–}100}$ for words 20–100;
- $C_L = S(L)$, compliance at a fixed length, $L \in \{100, 500\}$ words (binary score: L = full trace).

The opening/closing-string constraint has two checkpoints, the first and the last words, and no slip process in between: onset is the opening checkpoint and "maintenance" the closing one, so we report π for it but no λ, h or C_L (Table 1, note e). We compare parametric families by question-level 5-fold held-out log-likelihood: exponential (pure exposure), Weibull, an onset mixture $S(t) = \pi e^{-\lambda t}$ (a cure-type model, Berkson & Gage, 1952), a gamma-frailty exponential (Vaupel et al., 1979) and their combination, all under one likelihood (violations inside the onset window interval-censored, later violations a density, censored traces $S(L_i)$). Intervals are 95% percentile intervals from 1,000 bootstrap resamples that redraw *questions* with replacement (all traces of a drawn question enter together) and share the draws across cells, so ratios are paired; they are not adjusted for multiple comparisons, and the contrasts that were pre-registered are marked (App. B). Rates and ratios are shown only with ≥ 10 adopters and ≥ 10 slips in every arm.

Attribution. For two conditions A, B (two model sizes, two channels) we write the expected binary score as $s(\pi, S, F) = \pi\, \mathbb{E}_{L\sim F}[S^{\mathrm{ad}}(L - w)]$, with S^{ad} the Kaplan–Meier curve among adopters and F the empirical length distribution, and compute Shapley values of $s_B - s_A$ over the three factors, with 95% percentile intervals from 1,000 question-clustered bootstrap resamples. The factorisation assumes length and hazard independent within a cell. For suppression they are not (long traces offer more occasions to use the keyword): the pooled model over-predicts the lower-scoring condition by 96% at Qwen3-8B (2.61% vs. observed 1.33%), stratifying by question-level length tercile removes this (1.36% vs. 1.33%), so we report the *length-stratified* attribution for suppression and the pooled one for lowercase, where the two agree. The exception is suppression in the *external* channel, over-predicted at 8B (34 vs. 29%) and badly at 4B (22.3 vs. 13.2%) under length and keyword-opportunity stratification alike, so we do not read the 4B split; every other cell is within 0.9 pp under length stratification at $w = 20$. App. Table 25 gives all six variants with their misfit, and §6 quotes the min–max over them next to each component.

Compliant-prefix intervention. To move onset alone, we open the reasoning for the model: the first $K \in \{20, 100\}$ words of its own unconstrained trace for the same question, rewritten to satisfy




Figure 2: Kaplan–Meier curves of compliance in the plain reasoning channel (trace end or truncation = censoring). Uppercase is at zero from the first word in every model but gpt-oss-120b, which starts it in half of its traces and loses it within a few words; lowercase and "meow" are started by some models (OLMo-3-7B and gpt-oss-120b; Qwen3) and lost within the first sentence, except for the Qwen3 lowercase minority that keeps it; suppression decays smoothly.

the constraint (upper-, lower- or alternating case), are placed after the reasoning-start token and the model continues; only the continuation is graded, with the clock starting at its first word (exact templates, word definition and prefix construction: App. C, "Implementation"). The *no-instruction control* uses the same prefix with the unconstrained prompt and measures how much of the effect is continuation of context rather than instruction following.

Models, data and decoding. We evaluate Qwen3-8B and Qwen3-32B (Yang et al., 2025) in thinking mode, OLMo-3-7B-Think and OLMo-3-32B-Think (Olmo et al., 2025), and, as a third family, gpt-oss-20b and gpt-oss-120b (OpenAI et al., 2025) at their default (medium) reasoning effort. Qwen3-4B and Qwen3-14B complete a four-point size series, and along the OLMo-3-7B post-training trajectory we also evaluate the released base, SFT, DPO and RL-Zero checkpoints. Questions are a fixed subset of 300 (100 per dataset, proportional over domains, restricted to the 96% of benchmark questions that carry a suppression keyword). A second, disjoint 300-question subset without that restriction reproduces every π within 0.01 and gpt-oss-120b's first-word uppercase onset within 0.03 (App. Table 2). We sample at temperature 0.6, top-p 0.95, as Chen et al. (2026) do for open models, with 3 samples per prompt and 12,288 new tokens for Qwen3-8B, 2 samples and 10,240 tokens for Qwen3-32B, 2 samples and 12,288 tokens for Qwen3-4B/14B and gpt-oss, and 2 samples and 4,096 tokens for all OLMo-3 runs (271,500 traces in all, 32,700 of them unconstrained baselines). Truncated traces are censored, so π, λ and C_L remain comparable across budgets; binary scores do not, and we report them for Qwen3 only. Generation uses vLLM (Kwon et al., 2023); each experiment's protocol and predictions were committed before its data were generated (App. A).

3 Three regimes under one number

Never started. "Low controllability" is not one phenomenon (Table 1; Kaplan–Meier curves in Fig. 2). For uppercase, alternating case and the opening string, $\pi = 0.00$ in the four Qwen3 and OLMo-3 models: no trace out of 8,100 is compliant after 20 words, and 98–100% have already failed at the first word (the 12 exceptions, OLMo-3-7B alternating-case traces opening with a two-letter word, fail at the next). Under these three constraints, as in the unconstrained baseline, 98–100% of traces open with "Okay," (App. Table 3), which already violates them. The opener is the first symptom, not the whole failure: the share of uppercase words in a constrained trace (4.6–5.4%) equals that of unconstrained traces (4.2–5.6%), and a grader that starts after the first word or sentence leaves π at 0.00 for uppercase and alternating case and moves lowercase by at most 0.07 (App. Table 26). The sentence-level constraint belongs here too: no model complies in its first sentence. Lowercase is the mild case and the one case constraint with a genuine, definition-independent onset mass in Qwen3 ($\pi = 0.12/0.09/0.08$ at $w = 1/20/50$ for Qwen3-8B; $\hat{\pi} = 0.12$–0.15; 85–88% of traces fail on the capital "O"). OLMo-3-7B does open with a lower-case "okay," in

Table 1: Adoption rate π and slip rate λ (first slips per 1,000 words among adopters; shown with ≥ 10 adopters and ≥ 10 slips), plain reasoning channel; Qwen3 lowercase cells pool 1,200 second-seed traces per model. Binary: CoT-CONTROL score on the main run alone, degenerate traces removed (App. Table 6 pools the second seed). For the sentence-level constraint π is the share of traces whose *first sentence* complies. ‡Fitted onset mass $\hat{\pi} = 1$: the π column is early survival $S(20)$, not adoption. ^{e}Two checkpoints (first and last word), no slip process: π is the opening checkpoint and no λ is defined (§2). †4,096-token budget; "several keywords" not run for OLMo-3.

	Qwen3-8B		Qwen3-32B		OLMo-3-7B†		OLMo-3-32B†		gpt-oss-20b		gpt-oss-120b		binary (%)	
Constraint	π	λ	π	λ	π	λ	π	λ	π	λ	π	λ	Q-8B	Q-32B
Uppercase	0.00	–	0.00	–	0.00	–	0.00	–	0.00	–	0.03	40.1	0.0	0.0
Alternating case	0.00	–	0.00	–	0.00	–	0.00	–	0.00	–	0.02	122.2	0.0	0.0
Opening/closing string^{e}	0.00	–	0.00	–	0.00	–	0.00	–	1.00	–	0.99	–	0.0	0.0
End sentences with "safe"	0.00	–	0.00	–	0.00	–	0.00	–	0.00	–	0.00	–	0.0	0.0
Lowercase	0.09	1.8	0.11	1.6	0.07	221.1	0.00	–	0.00	–	0.06	220.3	2.6	3.8
"meow" between words	0.00	–	0.10	0.7	0.00	–	0.00	–	0.00	–	0.05	24.8	0.1	5.3
Suppress one keyword‡	0.76	5.5	0.86	3.2	0.75	6.2	0.75	6.7	0.64	9.4	0.69	6.2	1.3	10.3
Suppress several keywords‡	0.46	17.4	0.49	12.5	–	–	–	–	0.30	14.8	0.32	13.8	0.0	1.3

75% of traces, but only 7% keep it for twenty words: that cell belongs to the third regime below, not to this one.

No onset failure; leaks from the start. Keyword suppression has no excess failure mass at the start: the onset-mixture fit returns $\hat{\pi} = 1.00$ in all six models and 99.7–99.8% of Qwen3 and OLMo-3 traces pass the first three word positions (App. Table 23), so the 0.75–0.86 in Table 1 is survival to word 20 under a smooth hazard, and compliance decays smoothly from there (Fig. 2). A constant hazard is rejected in favour of gamma frailty in every suppression cell (held-out log-likelihood per trace +0.21 to +0.39 over exponential and +0.03 to +0.09 over Weibull, all intervals above zero; App. Table 4), with frailty variance $\theta = 0.5$–1.1 over the 10 suppression cells, whose source is identifiable: across terciles of how often the *unconstrained* trace uses the keyword (7, 18 and 35 times per 1,000 words), the slip rate per word triples (3.9, 7.9 and 12.1 per 1,000 words for Qwen3-8B) while slips per 100 *opportunities* stay within 36–59 (App. Table 16), an opportunity being a position at which the same question's unconstrained trace would have used the word. This is the one regime where exposure drives the binary score: Qwen3-8B scores 1.3% although $C_{100} = 0.28$ (App. Table 6). Naming the forbidden word does not prime it (mentions per 1,000 words fall under suppression in every model; App. Table 17). Against *unconstrained* traces of the same questions, which already go 100 words without the keyword 10–25% of the time, the instruction adds little in four models (20–28%) and more in Qwen3-32B (45%) and gpt-oss-120b (29%; its suppressed traces are short, median 272 words), and the median suppressed trace still names the forbidden concept 24–30 times in Qwen3-8B and OLMo-3: a keyword monitor is not evaded in any practical sense, and the excess over the unconstrained baseline is the quantity to track (App. D).

A third family, and a third regime: started and lost. gpt-oss-20b and gpt-oss-120b open with "We" rather than "Okay," (96% and 93% of traces outside the case constraints) and write short traces (median 342–487 words). At 20B the regimes are unchanged (Tables 1, 3): $\pi = 0.00$ for the case constraints and "meow", an uppercase word share (8%) equal to the unconstrained one, and suppression leaking at 9.4 per 1,000 words with no onset mass. The 120B model behaves as the benchmark authors' Fig. 42 shows: under the uppercase instruction it *starts* in uppercase in 50% of traces (lowercase: 73%), drops the style at the first sentence boundary, and survives to word 20 in only 0.03 and 0.06 (binary 1.0% and 0%). This is a third regime, *started and lost*, which no window-based π captures. Assigning every cell by F, the share of traces compliant on the constraint's first native unit, and $R = S(50)/F$, the share of starters still compliant at word 50 (thresholds and their separation: App. Table 24), the 46 cells of the six models split into 25 never started, 10 leaking with no onset failure, 3 minority onset, kept (Qwen3 lowercase, $R = 0.54$–0.66; gpt-oss-120b "meow"), 2 gpt-oss opening-string cells that start (99–100%) but fail the closing checkpoint (1.8% and 7.7% close; no slip process, so no λ in Table 1), and 6 started and lost (Qwen3-8B "meow"; Qwen3-32B "meow"; OLMo-3-7B lowercase; gpt-oss-120b alternating case; gpt-oss-120b lowercase; gpt-oss-120b uppercase), with a median first slip 1–8 words in. The regime is not confined to gpt-oss-120b or to scale: OLMo-3-7B lowercase ($F = 0.75$, $R = 0.00$), OLMo-3-7B-DPO and Qwen3-4B

lowercase show it for the constraint one token from the default. What scale buys within gpt-oss is the willingness to start far-from-default styles, not the ability to continue.

A grader artefact, not a regime. The best plain-channel score of Qwen3-8B is 6.9%, for "meow between words". All 62 compliant traces are loops of `meow meow meow ...` that run into the token limit and produce no reasoning (accuracy 0.0%): the released grader returns 1 when a trace contains no content words.[1] Treating them as failures gives 0.1% (and removes most of Qwen3-8B's external-CoT points for this constraint). Qwen3-32B, in contrast, adopts this constraint genuinely in 10% of traces (5.3% fully compliant, 78% accurate; example in App. B) while never adopting the nominally easier uppercase constraint: the habitual opener violates the case and string constraints but not this one.

4 Onset and maintenance can be moved separately; only one is visible

If models never start, what happens when the start is made for them? (Fig. 1b,c; App. Tables 7, 10, 11.)

The intervention moves onset; maintenance moves little. Lowercase is the one case constraint with plain-run adopters, so it is where λ can be compared with and without a prefix (1,200 extra plain traces per Qwen3 model give 197 and 190 adopters). For Qwen3-8B, π goes $0.09 \to 0.66 \to 0.92$ with $K = 0, 20, 100$ while λ is 1.8, 2.3, 2.0 per 1,000 words (paired-bootstrap ratios to the plain run 1.30 [0.95, 1.74] and 1.12 [0.83, 1.49]; App. Table 9), and the binary score rises from 2.8% to 12.8% and 20.5%. For Qwen3-32B the $K = 20$ ratio is 0.85 [0.59, 1.19], but 100 words halve λ (ratio 0.43 [0.30, 0.60]): a long compliant context adds momentum of its own at this scale. On common windows the comparison is noisier and not flat (prefix-20/plain ratios 1.67 [0.97, 3.23] at 8B and 0.61 [0.41, 0.95] at 32B over words 20–100; App. Table 20). Where the plain run has no adopters we can only compare prefix lengths; $K = 100$ vs. $K = 20$ ratios are 0.84–1.08 for uppercase in the four Qwen3 and OLMo-3 models. A short prefix thus changes lowercase onset in Qwen3 by a factor of 7–8 while the 95% intervals for the change in the time-averaged slip rate lie within $[0.59, 1.74]$ at $K = 20$. No equivalence margin was pre-specified, so this is a post hoc bound rather than an equivalence test; the argument is only that a change of at most 1.74-fold is small next to the 7–8-fold change in onset. The components can be moved separately, but only approximately: our pre-registered prediction that λ does not depend on K for $K \leq 20$ is *refuted* at 8B ($\lambda(K{=}20)/\lambda(K{=}5)$ = 1.25 [1.09, 1.44] for uppercase, 0.78 [0.63, 0.94] for lowercase) and holds at 32B (1.08 [0.90, 1.28], 1.11 [0.90, 1.35]; App. A).

Maintenance varies more than tenfold across models that all score 0%. Time-averaged slip rates after a 20-word prefix (App. Table 7) are not comparable across models: the hazard falls with position in every cell (App. Table 19), so a model that survives longer is averaged over easier stretches, and token budgets differ between families. We therefore compare on a *common window*, words 20–100 after the prefix, which every model and budget observes (Fig. 1c): the uppercase hazards are 46.5 (OLMo-3-7B), 18.5 (Qwen3-8B), 10.2 (OLMo-3-32B) and 3.6 (Qwen3-32B), the extremes differ by 13 [10, 17]$\times$ rather than the 32$\times$ the time-averaged rates suggest, and the within-family ratios are 5.1 [4.1, 6.5] (Qwen3) and 4.6 [3.6, 5.9] (OLMo-3). The three families tokenise differently, and uppercase text costs 1.31–1.38$\times$ more tokens than the same words in their original case in all three; per 1,000 *tokens* the extremes differ by 15$\times$ (App. Table 21), so tokenisation does not account for the contrast. Across four Qwen3 sizes the trend is monotone at every step: hazards of 75.0, 18.5, 7.9 and 3.6 at 4B, 8B, 14B and 32B, adoption 0.09, 0.77, 0.81 and 0.92, and 0%, 2%, 14% and 38% of traces in uppercase to the end (App. Table 10), with the plain score 0% at every size. The strict grader if anything *understates* the contrast: 86% of Qwen3-32B's first uppercase violations are isolated notation tokens ("... AND HCl. SO ...") rather than reversions, and a grader that masks notation widens the span to 31-fold (App. Table 15). Qwen3-32B writes an *entire* reasoning trace in uppercase in 38% ($K = 20$) and 45% ($K = 100$) of cases, and in lowercase in 32% and 49% (App. Table 5), against 0% and 4.2% in the plain run, while still reasoning (accuracy 49% vs. 50%;

[1] We recommend that the released grader treat traces without content words as failures. Our position-resolved graders do; the "binary" columns reproduce the released grader.




Figure 3: OLMo-3-7B along its post-training trajectory. (a) The opener and zero adoption of the uppercase constraint are already present in the released base model; suppression is unchanged throughout. (b) Maintenance after a compliant prefix is lost at the SFT stage.

App. Table 22). For this model, "cannot reason in uppercase" is false; "does not start in uppercase" is true.

How much of a start is needed? Varying the prefix from the opener alone ($K = 1$) to a hundred words (App. C) shows that which style one token can launch is a property of the model, not of the style's distance from the default: "okay," suffices for lowercase at both Qwen3 sizes ($\pi = 0.73$); "OKAY," does not at 8B ($\pi = 0.05$) but does at 32B ($\pi = 0.59$; 26% of traces entirely uppercase) and in OLMo-3-32B ($\pi = 0.85$); no dose helps gpt-oss at all ($\pi \leq 0.11$), and OLMo-3-7B reaches $\pi = 0.27$ for uppercase at $K = 20$ but $C_{100} = 0.01$. What the benchmark records as a 0% ability is, in Qwen3-32B, one token away from 26%. A prompt-only *hint* to begin with "OKAY," (App. C) moves the lowercase opener in 80% of Qwen3-8B traces (binary 2.8% $\rightarrow$ 29.0%), is ignored by Qwen3-32B and both OLMo-3 models, and is obeyed by gpt-oss, which then drops the style within a sentence; across Qwen3 sizes its effect is irregular (11.5%, 80%, 0%, 0.3%), so what moves with size is maintenance after a start, not the start itself.

Instruction following or context continuation? The no-instruction control separates the two. In Qwen3-8B the gain is instruction following: without the instruction a 20-word prefix leaves C_{100} at 0.02 (uppercase) and 0.04 (lowercase) against 0.17 and 0.45 with it. In Qwen3-32B most of the effect is continuation: the control retains 58% (uppercase) and 33% (lowercase) of the instructed C_{100} with 20 words and 85% and 73% with 100. Within Qwen3 this momentum appears between 14B and 32B (20-word uppercase control ratios 0.10, 0.09 and 0.58 at 8B, 14B and 32B; undefined at 4B, where $C_{100} = 0$ in both arms) while adoption under instruction rises smoothly (0.09, 0.77, 0.81 and 0.92); it is a Qwen3 property rather than a scale property, since OLMo-3-32B sits with the small models (20-word ratios 0.06 and 0.14) and OLMo-3-7B and gpt-oss have none. The style of a trace is thus set by how it opens and carried by a momentum that grows with scale in one family; the instruction lowers the slip rate by a further factor of 1.4–7.6 in the 21 of 28 model–style–K cells whose interval excludes 1, and by a factor indistinguishable from 1 in the other 7 (Qwen3-4B (uppercase), gpt-oss-20b (both styles), gpt-oss-120b (both styles), the OLMo-3-7B base model (uppercase) and RL-Zero-General (uppercase); App. Table 9).

5 Where onset failure and maintenance come from

Chen et al. (2026) find that controllability drops after reasoning training, most sharply at the SFT stage. We ran the OLMo-3-7B checkpoints (Fig. 3; App. Tables 6, 10). We had predicted that SFT on distilled long reasoning traces installs the fixed opener; **this was refuted**: the released base model already opens with "Okay," in 59–80% of completions and has $\pi = 0.00$ for all three case constraints, showing control only for the opening string (9.8%) and suppression (6.8% binary; Chen et al. (2026) report 10.6% on their full question set). From SFT onward nothing moves: the opener is at 100%, $\pi = 0$ for style and string constraints, and suppression sits at $\pi = 0.73$–0.76, $\lambda = 5.9$–6.8 at every stage.

Maintenance tells a different story. Base completions are much shorter (median 991 vs. 2,096–2,542 words) and the prompt format differs, so we compare on common windows after a 20-word uppercase prefix: over words 20–100 the hazards are 5.5 (base), 35.9 (SFT), 42.5 (DPO) and 46.5 (final) per 1,000 words (SFT/base ratio 6.5 [5.1, 8.5]; 11.9 [7.3, 23.1] over words 100–300; 2.1 [1.6, 2.8] for lowercase; App. Table 20). The base model's behaviour is pure context continuation: its no-instruction control is indistinguishable from the instructed arm (π 0.72 vs. 0.75, λ 1.35 vs. 1.33). In this family, then, long-CoT post-training does not create the onset failure; it *removes the context-driven momentum* that would let a trace stay in an unusual style, and installs the weak




Figure 4: Shapley attribution of binary-score gaps (percentage points) to onset, maintenance and exposure, with 95% bootstrap intervals drawn at the end of each component; pooled for lowercase, length-stratified for suppression (§2). Faded bars are negative contributions. (a) Qwen3-8B $\rightarrow$ 32B. (b, c) Reasoning channel $\rightarrow$ external CoT. Constraints with $\pi = 0$ in the reasoning channel are omitted: their maintenance term is not identified (no adopters), and §4 measures it instead. "meow" is omitted because its split between onset and maintenance depends on the onset window (App. Table 25).

instruction sensitivity the Think model shows (SFT-stage control/instructed C_{100} ratio 0.29), with DPO between SFT and the final model on every prefix measure. The RL-Zero checkpoints, trained from the same base with RLVR and *without* the long-CoT SFT stage, isolate the responsible step: they have the opener and $\pi = 0$ for the case constraints, and traces as long as the Think model's, yet after a 20-word prefix their uppercase hazard over words 20–100 is 3.8 (Math) and 5.4 (Code) per 1,000 words, 36–40% of continuations stay in uppercase to the end, and the control retains 75–76% of the instructed C_{100} (RL-Zero-General, trained on chat data, sits in between). RLVR on its own preserves the base model's momentum; imitation of distilled long reasoning traces removes it.

6 Re-attributing reported trends

Size. CoT-Control scores rise with parameter count. For Qwen3, lowercase rises from 2.6% to 3.8%, and the only component distinguishable from zero is exposure (+0.77 [0.50, 1.14] pp; +0.77 to +1.04 over the four variants of App. Table 25): the 32B model writes half as many words (median 988 vs. 1,744) at a slip rate the attribution cannot tell apart (maintenance +0.2 [-1.2, 1.4] pp; time-averaged λ 1.8 [1.4, 2.4] vs. 1.6 [1.1, 2.2]). Suppression rises from 1.3% to 10.3%, of which +6.8 [3.9, 9.7] is a lower slip rate and +1.7 [1.1, 2.3] exposure (length-stratified; +5.4 to +7.6 and +1.7 to +2.3 over the six variants; Fig. 4a); the +0.9 [0.5, 1.4] assigned to onset at $w = 20$ is early survival and moves into maintenance at $w = 1$ (+7.6 [4.6, 10.8]). Both gaps are small (1.2 and 9 pp) and we read them no more finely than "exposure only" and "mostly maintenance"; the "meow" gap is not robustly attributable (App. Table 25). Neither size effect appears in OLMo-3 (suppression π 0.75 vs. 0.75, λ 6.2 vs. 6.7 at 7B and 32B). What scale buys in the plain channel is family-specific; what it buys in maintenance (§4) is not.

Channel. The gap between reasoning and external CoT (same model, task and kind of text; App. Table 8) decomposes differently by constraint (Fig. 4b,c). For lowercase it is mostly onset ($+47$ of 74 pp at 8B, $+55$ of 83 at 32B; +45 to +47 and +49 to +55 over variants). For suppression at 8B it is mostly exposure (+22 [19, 25] of 28 pp; +22 to +26 over variants): the per-word slip rate is similar in both channels (5.5 vs. 6.3; ratio 1.14 [0.73, 1.64]) and external reasoning is 13$\times$ shorter; at 32B suppression is also better maintained outside the reasoning channel ($+42$ maintenance, +38 to +47 over variants; $+16$ exposure; slip-rate ratio 0.49 [0.36, 0.63]). Across the three larger Qwen3 sizes the suppression gap keeps a roughly constant exposure term (+22, +19 and +16 pp at 8B, 14B and 32B) while its maintenance term grows (+13, +29 and +42): outside the reasoning channel larger models leak less per word, inside it they do not (3.2–6.6 per 1,000 words at every size; App. Table 6); the 4B cell misfits (§2) and is not read. For uppercase at 32B the prefixed reasoning-channel slip rate (1.2–1.4) is within a factor of two of the external channel's (2.4 [1.5, 3.6]): most of the channel gap is the opener.

Length and reasoning effort. Against our expectation, the linear length adjustment of Chen et al. (2026) leaves no residual confounding in simulation (App. G); it is their unadjusted group compar-

isons that exposure can enter, and gpt-oss, whose effort is a template setting, shows it (App. F): from low to high effort the median gpt-oss-20b trace grows from 76 to 1,806 words and its suppression score falls 88-fold. First-word onset stays at 1.00/1.00/1.00, but early survival rises (+0.12 [+0.06, +0.18]) and the 20–100-word hazard rises with effort (high/low ratio 1.53 [1.20, 1.97]; App. Table 13), so our pre-registered prediction that only length moves is *refuted* (App. A): the drop is mostly, not only, exposure, and more deliberate reasoning names the keyword more often per word early on. gpt-oss-120b, the one model that starts, also starts less often. Effort thus changes exposure and the early leak rate in one model and onset in the other, and the binary score cannot tell which.

7 Related work

CoT monitoring and its failure modes. CoT monitoring catches misbehaviour that output monitoring misses (Baker et al., 2025), and its fragility is widely discussed (Korbak et al., 2025; Guan et al., 2025): monitorability degrades under optimisation pressure on the CoT (Baker et al., 2025; Skaf et al., 2025; Drori et al., 2025), is higher when reasoning is necessary for the task (Emmons et al., 2025), and is bounded by faithfulness, since traces need not verbalise what drove the answer (Chen et al., 2025). Deliberate evasion has been studied via prompted obfuscation (Zolkowski et al., 2025), sandbagging (Li et al., 2025), plan injection (Chidambaram et al., 2026) and implicit influence (Duzan & Stickland, 2026), and presupposes evaluation awareness (Berglund et al., 2023; Needham et al., 2025; Schoen et al., 2025). Chen et al. (2026) isolate the model-side precondition; Haskins et al. (2026) fine-tune eight models on synthetic documents about a CoT monitor and report that the CoT-Control score is "closely correlated with obfuscation success across the eight models studied ($r = 0.800$)"; Xiong et al. (2026) find that monitorability gains under RLVR depend on the training data; we ask which component of the score could carry such relationships. Kowalski et al. (2026) pose the controllability question for activations rather than text.

Instruction following in reasoning. Kwon et al. (2025) show that reasoning models ignore instructions about their reasoning and treat this as a defect to train away; Chen et al. (2026) read the same behaviour as reassuring. Our decomposition bears on both: fine-tuning that changes how traces open would move the score with no change in maintenance. Instruction-following benchmarks score strict all-or-nothing compliance (Zhou et al., 2023) and degrade with instruction count (Jaroslawicz et al., 2025), accumulating constraints (Dente et al., 2026) and conversation turns (Laban et al., 2025); in multi-turn ideation, models violate constraints they can still restate (Kruthof, 2026). We are not aware of prior work that treats adherence as a censored time-to-event process; the closest precedents are length-controlled AlpacaEval (Dubois et al., 2024), a headline metric confounded by length and repaired by standardisation, and the task-length horizon of Kwa et al. (2025), a capability metric indexed by exposure much as C_L is.

Interventions on the reasoning trace. Writing into a model's reasoning is an established control and attack surface: thinking intervention inserts guidance into the trace (Wu et al., 2025), budget forcing appends tokens to extend or end it (Muennighoff et al., 2025), and prefilling a response's start bypasses safety training (Vega et al., 2023; Andriushchenko et al., 2024). None resolves adherence over position; our compliant prefix is the same operation used as a measurement probe that fixes onset so that maintenance can be measured.

8 Conclusion

The CoT-Control score is a product of onset, maintenance and exposure, and for style and string constraints it currently measures only onset: whether the first token departs from a habitual opener. Position-resolved grading and a compliant prefix recover the maintenance term, which varies 13-fold across models that all score 0% and improves with scale in two of three families. Reported next to the binary score, onset and the post-prefix hazard tell whether a low score is robust or one token away from changing (discussion and limitations: App. E).

AI use statement

In this work, we used generative AI tools to implement the experiment code, analyze the results, and polish the paper.

REFERENCES

Maksym Andriushchenko, Francesco Croce, and Nicolas Flammarion. Jailbreaking Leading Safety-Aligned LLMs with Simple Adaptive Attacks. *arXiv preprint arXiv:2404.02151*, 2024. URL https://arxiv.org/abs/2404.02151.

Bowen Baker, Joost Huizinga, Leo Gao, Zehao Dou, Melody Y. Guan, Aleksander Madry, Wojciech Zaremba, Jakub Pachocki, and David Farhi. Monitoring Reasoning Models for Misbehavior and the Risks of Promoting Obfuscation. *arXiv preprint arXiv:2503.11926*, 2025. URL https://arxiv.org/abs/2503.11926.

Lukas Berglund, Asa Cooper Stickland, Mikita Balesni, Max Kaufmann, Meg Tong, Tomasz Korbak, Daniel Kokotajlo, and Owain Evans. Taken out of context: On measuring situational awareness in LLMs. *arXiv preprint arXiv:2309.00667*, 2023. URL https://arxiv.org/abs/2309.00667.

Joseph Berkson and Robert P. Gage. Survival curve for cancer patients following treatment. *Journal of the American Statistical Association*, 47(259):501–515, 1952. ISSN 1537-274X. doi: 10.1080/01621459.1952.10501187. URL http://dx.doi.org/10.1080/01621459.1952.10501187.

Yanda Chen, Joe Benton, Ansh Radhakrishnan, Jonathan Uesato, Carson Denison, John Schulman, Arushi Somani, Peter Hase, Misha Wagner, Fabien Roger, Vlad Mikulik, Samuel R. Bowman, Jan Leike, Jared Kaplan, and Ethan Perez. Reasoning Models Don't Always Say What They Think. *arXiv preprint arXiv:2505.05410*, 2025. URL https://arxiv.org/abs/2505.05410.

Yueh-Han Chen, Robert McCarthy, Bruce W. Lee, He He, Ian Kivlichan, Bowen Baker, Micah Carroll, and Tomek Korbak. Reasoning Models Struggle to Control their Chains of Thought. *arXiv preprint arXiv:2603.05706*, 2026. URL https://arxiv.org/abs/2603.05706.

Keertana Chidambaram, Andrew Ilyas, and Vasilis Syrgkanis. Corrupt Plans, Clean Traces: Evading Chain-of-Thought Monitoring with Plan Injection. *arXiv preprint arXiv:2609.15989*, 2026. URL https://arxiv.org/abs/2609.15989.

Francesco Dente, Dario Satriani, and Paolo Papotti. Constraint Decay: The Fragility of LLM Agents in Backend Code Generation. *arXiv preprint arXiv:2605.06445*, 2026. URL https://arxiv.org/abs/2605.06445.

Jacob Drori, Luke Marks, Bryce Woodworth, Alex Cloud, and Alexander Matt Turner. Output Supervision Can Obfuscate the Chain of Thought. *arXiv preprint arXiv:2511.11584*, 2025. URL https://arxiv.org/abs/2511.11584.

Yann Dubois, Balázs Galambosi, Percy Liang, and Tatsunori B. Hashimoto. Length-Controlled AlpacaEval: A Simple Way to Debias Automatic Evaluators. *arXiv preprint arXiv:2404.04475*, 2024. URL https://arxiv.org/abs/2404.04475.

Agatha Duzan and Asa Cooper Stickland. Chain-of-Thought Monitoring Can Be Unreliable in Implicit-Influence Settings. *arXiv preprint arXiv:2608.04735*, 2026. URL https://arxiv.org/abs/2608.04735.

Scott Emmons, Erik Jenner, David K. Elson, Rif A. Saurous, Senthooran Rajamanoharan, Heng Chen, Irhum Shafkat, and Rohin Shah. When Chain of Thought is Necessary, Language Models Struggle to Evade Monitors. *arXiv preprint arXiv:2507.05246*, 2025. URL https://arxiv.org/abs/2507.05246.

Melody Y. Guan, Miles Wang, Micah Carroll, Zehao Dou, Annie Y. Wei, Marcus Williams, Benjamin Arnav, Joost Huizinga, Ian Kivlichan, Mia Glaese, Jakub Pachocki, and Bowen Baker. Monitoring Monitorability. *arXiv preprint arXiv:2512.18311*, 2025. URL https://arxiv.org/abs/2512.18311.

Reilly Haskins, Bilal Chughtai, and Joshua Engels. Training on Documents About Monitoring Leads to CoT Obfuscation. *arXiv preprint arXiv:2605.15257*, 2026. URL https://arxiv.org/abs/2605.15257.

Daniel Jaroslawicz, Brendan Whiting, Parth Shah, and Karime Maamari. How Many Instructions Can LLMs Follow at Once? *arXiv preprint arXiv:2507.11538*, 2025. URL https://arxiv.org/abs/2507.11538.

E. L. Kaplan and Paul Meier. Nonparametric estimation from incomplete observations. *Journal of the American Statistical Association*, 53(282):457–481, 1958. ISSN 1537-274X. doi: 10.1080/01621459.1958.10501452. URL http://dx.doi.org/10.1080/01621459.1958.10501452.

Tomek Korbak, Mikita Balesni, Elizabeth Barnes, Yoshua Bengio, Joe Benton, Joseph Bloom, Mark Chen, Alan Cooney, Allan Dafoe, Anca Dragan, et al. Chain of Thought Monitorability: A New and Fragile Opportunity for AI Safety. *arXiv preprint arXiv:2507.11473*, 2025. URL https://arxiv.org/abs/2507.11473.

Marek Mateusz Kowalski, Joshua Fonseca Rivera, Uzay Macar, and David Demitri Africa. Measuring Activation Control in Large Language Models. *arXiv preprint arXiv:2608.21664*, 2026. URL https://arxiv.org/abs/2608.21664.

Garvin Kruthof. Models Recall What They Violate: Constraint Adherence in Multi-Turn LLM Ideation. *arXiv preprint arXiv:2604.28031*, 2026. URL https://arxiv.org/abs/2604.28031.

Thomas Kwa, Ben West, Joel Becker, Amy Deng, Katharyn Garcia, Max Hasin, Sami Jawhar, Megan Kinniment, Nate Rush, Sydney Von Arx, et al. Measuring AI Ability to Complete Long Software Tasks. *arXiv preprint arXiv:2503.14499*, 2025. URL https://arxiv.org/abs/2503.14499.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient Memory Management for Large Language Model Serving with PagedAttention. *arXiv preprint arXiv:2309.06180*, 2023. URL https://arxiv.org/abs/2309.06180.

Yongchan Kwon, Shang Zhu, Federico Bianchi, Kaitlyn Zhou, and James Zou. ReasonIF: Large Reasoning Models Fail to Follow Instructions During Reasoning. *arXiv preprint arXiv:2510.15211*, 2025. URL https://arxiv.org/abs/2510.15211.

Philippe Laban, Hiroaki Hayashi, Yingbo Zhou, and Jennifer Neville. LLMs Get Lost In Multi-Turn Conversation. *arXiv preprint arXiv:2505.06120*, 2025. URL https://arxiv.org/abs/2505.06120.

Chloe Li, Mary Phuong, and Noah Y. Siegel. LLMs Can Covertly Sandbag on Capability Evaluations Against Chain-of-Thought Monitoring. *arXiv preprint arXiv:2508.00943*, 2025. URL https://arxiv.org/abs/2508.00943.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. s1: Simple test-time scaling. *arXiv preprint arXiv:2501.19393*, 2025. URL https://arxiv.org/abs/2501.19393.

Joe Needham, Giles Edkins, Govind Pimpale, Henning Bartsch, and Marius Hobbhahn. Large Language Models Often Know When They Are Being Evaluated. *arXiv preprint arXiv:2505.23836*, 2025. URL https://arxiv.org/abs/2505.23836.

Team Olmo, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, et al. Olmo 3. *arXiv preprint arXiv:2512.13961*, 2025. URL https://arxiv.org/abs/2512.13961.

OpenAI, Sandhini Agarwal, Lama Ahmad, Jason Ai, Sam Altman, Andy Applebaum, Edwin Arbus, Rahul K. Arora, Yu Bai, Bowen Baker, et al. gpt-oss-120b & gpt-oss-20b Model Card. *arXiv preprint arXiv:2508.10925*, 2025. URL https://arxiv.org/abs/2508.10925.

Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, Josephina Hu, Hugh Zhang, Chen Bo Calvin Zhang, Mohamed Shaaban, John Ling, Sean Shi, et al. Humanity's Last Exam. *arXiv preprint arXiv:2501.14249*, 2025. URL https://arxiv.org/abs/2501.14249.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. GPQA: A Graduate-Level Google-Proof Q&A Benchmark. *arXiv preprint arXiv:2311.12022*, 2023. URL https://arxiv.org/abs/2311.12022.

Bronson Schoen, Evgenia Nitishinskaya, Mikita Balesni, Axel Højmark, Felix Hofstätter, Jérémy Scheurer, Alexander Meinke, Jason Wolfe, Teun van der Weij, Alex Lloyd, Nicholas Goldowsky-Dill, Angela Fan, Andrei Matveiakin, Rusheb Shah, Marcus Williams, Amelia Glaese, Boaz Barak, Wojciech Zaremba, and Marius Hobbhahn. Stress Testing Deliberative Alignment for Anti-Scheming Training. *arXiv preprint arXiv:2509.15541*, 2025. URL https://arxiv.org/abs/2509.15541.

Joey Skaf, Luis Ibanez-Lissen, Robert McCarthy, Connor Watts, Vasil Georgiv, Hannes Whittingham, Lorena Gonzalez-Manzano, David Lindner, Cameron Tice, Edward James Young, and Puria Radmard. Large language models can learn and generalize steganographic chain-of-thought under process supervision. *arXiv preprint arXiv:2506.01926*, 2025. URL https://arxiv.org/abs/2506.01926.

James W. Vaupel, Kenneth G. Manton, and Eric Stallard. The impact of heterogeneity in individual frailty on the dynamics of mortality. *Demography*, 16(3):439–454, August 1979. ISSN 1533-7790. doi: 10.2307/2061224. URL http://dx.doi.org/10.2307/2061224.

Jason Vega, Isha Chaudhary, Changming Xu, and Gagandeep Singh. Bypassing the Safety Training of Open-Source LLMs with Priming Attacks. *arXiv preprint arXiv:2312.12321*, 2023. URL https://arxiv.org/abs/2312.12321.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, Tianle Li, Max Ku, Kai Wang, Alex Zhuang, Rongqi Fan, Xiang Yue, and Wenhu Chen. MMLU-Pro: A More Robust and Challenging Multi-Task Language Understanding Benchmark. *arXiv preprint arXiv:2406.01574*, 2024. URL https://arxiv.org/abs/2406.01574.

Tong Wu, Chong Xiang, Jiachen T. Wang, G. Edward Suh, and Prateek Mittal. Effectively Controlling Reasoning Models through Thinking Intervention. *arXiv preprint arXiv:2503.24370*, 2025. URL https://arxiv.org/abs/2503.24370.

Zidi Xiong, Shan Chen, and Himabindu Lakkaraju. Monitorability as a Free Gift: How RLVR Spontaneously Aligns Reasoning. *arXiv preprint arXiv:2602.03978*, 2026. URL https://arxiv.org/abs/2602.03978.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388*, 2025. URL https://arxiv.org/abs/2505.09388.

Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-Following Evaluation for Large Language Models. *arXiv preprint arXiv:2311.07911*, 2023. URL https://arxiv.org/abs/2311.07911.

Artur Zolkowski, Wen Xing, David Lindner, Florian Tramèr, and Erik Jenner. Can Reasoning Models Obfuscate Reasoning? Stress-Testing Chain-of-Thought Monitorability. *arXiv preprint arXiv:2510.19851*, 2025. URL https://arxiv.org/abs/2510.19851.

A Pre-registered predictions and their outcomes

Each experiment had a protocol file stating predictions and refutation criteria (`experiments/E*/protocol*.md` in the released repository; the labels E10–E16 in Table 2 refer to these files, the unlabelled rows to the E1–E9 protocols), committed before generation. Table 2 lists all of them, including those that failed. The pre-registration was *sequential*, not blind: protocols E10–E16 were written after the E1–E9 results were known, and several of their predictions are refinements of patterns already observed (E16, for instance, predicts that the trends

seen at 8B and 32B extend to 4B and 14B). The predictions were fixed before the data they are scored against were generated, but they are not independent of the earlier data.

Table 2: Predictions committed before data and their outcomes. Predictions are quoted as committed; outcomes are scored by the criterion stated in the protocol.

Prediction	Outcome
Pure exposure: exponential survival, no excess mass at onset	Refuted in every cell
Onset-dominated: $\geq 50\%$ of failures in the first 20 words	Supported for 6 of 8 constraints
Heterogeneity: frailty beats exponential; $\theta \approx 2.7$	Partly supported: frailty beats exponential in every suppression cell (qualitative half), but $\theta = 0.5$–1.1, not 2.7 (quantitative half **refuted**)
Linear length control leaves residual confounding (simulation)	**Refuted**; claim withdrawn
Naming the forbidden word primes it	**Refuted** (rate below baseline)
E10: $\pi(K{=}1) < \frac{1}{2}\,\pi(K{=}20)$ (opener not sufficient)	Supported for uppercase at 8B (0.05 vs. 0.77); **refuted** for lowercase (0.73 vs. 0.66) and for uppercase at 32B (0.59 vs. 0.92)
E10 D3: λ among adopters independent of K for $K \leq 20$ (ratio intervals include 1); any K-dependence at $K = 100$	**Refuted** at Qwen3-8B: $\lambda(K{=}20)/\lambda(K{=}5)$ = 1.25 [1.09, 1.44] (uppercase) and 0.78 [0.63, 0.94] (lowercase); on the 20–100 window 1.37 [1.18, 1.60] and 0.61 [0.48, 0.75]. Supported at Qwen3-32B (1.08 [0.90, 1.28], 0.92 [0.76, 1.11] uppercase; 1.11 [0.90, 1.35], 0.84 [0.68, 1.04] lowercase; on the window the $K = 1$ lowercase ratio 0.55 [0.43, 0.67] excludes 1). $K = 100$ clause: **refuted** at Qwen3-8B, where no $K = 100$ dependence is detectable ($\lambda(K{=}100)/\lambda(K{=}20)$ = 0.87 [0.72, 1.04] uppercase, 0.86 [0.72, 1.03] lowercase, 0.69 [0.43, 1.05] alternating; all include 1); supported at Qwen3-32B (0.50 [0.41, 0.61] lowercase and 0.71 [0.57, 0.87] alternating exclude 1; uppercase 0.85 [0.70, 1.02] does not).[2]
E11: prompt-only opener hint moves the first word in $< 20\%$ of traces	Qwen3-8B: **refuted** for lowercase (80%), supported for uppercase (21%); Qwen3-32B, OLMo-3-7B, OLMo-3-32B: supported (0%, 0.3%; 0%, 0.7%; 0%, 0%)
E11: demo does no better than hint	Supported at 8B (44% vs. 80% lowercase; 0% vs. 21% uppercase); **refuted** at 32B (13.5% vs. 0.3%)
E10 D4/D5: no-instruction control retains > 0.5 of instructed C_{100} at Qwen3-32B ($K = 20$ uppercase; $K = 100$ lowercase), < 0.5 at 8B	Supported (0.58, 0.73; 8B: 0.10, 0.10)
E12b: DPO-stage prefix hazard (words 20–100) in $[25, 60]$	Supported (42.5)
E12a: 12k-token OLMo-3-7B rerun matches 4k-token π and common-window hazards within CIs	Supported (suppression 13.7 / 6.5 vs. 13.5 / 6.5; prefix uppercase 47.7 vs. 46.5)
E12d/E13a/E15b: disjoint, unrestricted subset reproduces π within ± 0.04 (Qwen3-8B, Qwen3-32B, gpt-oss-20b/120b)	Supported (lowercase 0.10 vs. 0.09; 0.11 vs. 0.11; gpt-oss-120b first-word uppercase onset 0.53 vs. 0.50; others 0.00)
E13d: OLMo-3-32B $K = 1$ uppercase $\pi < 0.3$	**Refuted** (0.85; lowercase 0.14)
E13b/f: RL-Zero checkpoints keep base-like maintenance ($h_{20\text{–}100} < 15$) and control ratio > 0.7	Supported for Math and Code (3.8, 5.4; 0.76, 0.75); **refuted** for General (16.3; 0.65)
E14a: gpt-oss-20b has $\pi > 0.2$ for uppercase (starts then leaks, as its 120B sibling)	**Refuted** ($\pi = 0.00$; opener "We" 99%)
E14c: gpt-oss-20b $K = 20$ uppercase $\pi > 0.5$; hint moves the opener in $< 20\%$	**Refuted** (0.06); **refuted** (100%, then reverts)

[2] An earlier draft scored this row "supported" from the 8B window hazards 13.5 and 18.5, whose intervals do not overlap; that was an error.

(continued)

Prediction	Outcome
E14e: gpt-oss-120b uppercase $\pi(w{=}20) > 0.2$; lower prefix hazard and higher control ratio than 20B	**Refuted** (0.03; but first-word onset 0.50); **refuted** (88 vs. 50; 0.04 vs. 0.04)
E15: effort changes length only: π and common-window hazards unchanged across low/medium/high	**Refuted** for the suppression hazard and early survival in gpt-oss-20b (paired high/low $h_{20\text{–}100}$ ratio 1.53 [1.20, 1.97], medium/low 1.32 [1.06, 1.66]; $\pi(w{=}20)$ high$-$low +0.12 [+0.06, +0.18]; binary 29.5%/3.5%/0.33%; App. Table 13); supported for first-word onset (1.00/1.00/1.00) and for the case constraints ($\pi \leq 0.03$ throughout); **refuted** for gpt-oss-120b uppercase (first-word onset 0.94/0.50/0.01).[3]
E15b: gpt-oss-20b subset B reproduces the regimes; effort does not change maintenance after a prefix	Supported ($\pi = 0.00$); **weakly refuted**: at high effort a 20-word prefix is held longer in both gpt-oss models ($K = 20$ uppercase π 0.04/0.06/0.22 at low/medium/high for 20B, 0.04/0.06/0.20 for 120B; hazards 50 vs. 43 and 88 vs. 46)
E16: Qwen3 four sizes: prefix hazard falls, control ratio rises, one-token onset rises monotonically	Supported for the hazard (75.0/18.5/7.9/3.6 at 4B/8B/14B/32B) and one-token onset (0.00, 0.05, 0.47 and 0.59); **partly refuted** for the control ratio, which is undefined at 4B ($C_{100} = 0$ in both arms), flat from 8B to 14B and rises only at 32B (0.10, 0.09 and 0.58)
E16c/f: seed-1 replication of the $K = 20$ arms within ± 5 pp at every size and family	Supported (App. Table 14: Qwen3-32B 40.5 vs. 38.0%; 14B 15.3 vs. 14.2; 8B 1.7 vs. 2.0; 4B 0 vs. 0; OLMo-3-7B hazard 44 vs. 47)
E16d: suppression channel gap shifts from exposure toward maintenance with size	Supported (pooled attribution: maintenance $+5/+11/+27/+38$ pp at 4B/8B/14B/32B; exposure $+26/+22/+19/+19$; the 4B cell misfits, §2)
E16e: plain lowercase λ at 4B/14B comparable with the $K = 20$ arm	**Not testable**: 0.2% and 0.6% of 1,800 plain traces adopt (no onset at these sizes)
E16g/h: seed-1 replication of single-run headline cells (Qwen3-8B hint; Qwen3-32B, OLMo-3-32B and gpt-oss-20b $K = 1$; gpt-oss-20b hint)	Supported (8B hint 28.8 vs. 29.0%; Qwen3-32B $K = 1$ uppercase 25.3 vs. 26.0%; OLMo-3-32B $K = 1$ π 0.855 vs. 0.852; gpt-oss-20b $K = 1$ 3.2 vs. 2.5%, hint 0.8 vs. 0.3%)
E16b: hint effect monotone in size (4B $\geq$ 8B $>$ 14B $\geq$ 32B)	**Refuted**: 11.5%, 80%, 0%, 0.3% of lowercase openers moved at 4B/8B/14B/32B—an 8B idiosyncrasy
E13e (SFT-stage control): SFT-stage control/instructed ratio > 0.5 (instruction sensitivity absent at SFT)	**Refuted** (0.29; λ 54 vs. 35)
E13g: OLMo-3-7B-Instruct as external-CoT surrogate has $\pi > 0.5$ for case constraints	Supported (uppercase 0.50, lowercase 0.74)
E13e (Think controls): OLMo-3-7B-Think 20-word control/instructed C_{100} ratio < 0.3	Supported (0.00, 0.08)
Domain effect on case constraints is notation density	Weak: masking moves scores by ≤ 2.5 pp
Prefix: $C_{500} \geq 0.5$ (onset lock-in)	Lowercase 0.33 (8B), 0.64 (32B); uppercase 0.01 (8B), 0.49 (32B)
Prefix: no-instruction control matches instructed arm $\Rightarrow$ imitation	8B: no (instruction following); 32B: mostly yes
Channel gap is an onset gap with equal slip rates	Supported for suppression at 8B; **refuted** for case constraints
Size effect is onset	**Refuted**: exposure (lowercase), maintenance (suppression)
SFT already shows a fixed opener and $\pi \approx 0$; later stages change little	Supported
Base model has no fixed opener and $\pi > 0$ for case constraints	**Refuted**
SFT already shows a high slip rate after a prefix (> 20 per 1k)	Supported (34.7)

[3] An earlier draft scored this row "supported" for gpt-oss-20b from hazards "12/16/19, intervals overlap"; the low- and high-effort intervals (12.3 [10.0, 15.3] vs. 18.8 [16.2, 22.0]) do not overlap and the paired ratio excludes 1. That was an error.

(continued)

Prediction	Outcome
Base-model control ≈ instructed arm (C_{100} ratio > 0.7)	Supported (0.99)
OLMo-3-32B control/instructed C_{100} ratio > 0.5	Inconclusive, leaning refuted (0.34)

B ADDITIONAL DETAILS AND RESULTS

Table 3: Share of traces whose first word is the model's habitual opener, "Okay," for Qwen3 and OLMo-3 and "We" for gpt-oss (case-insensitive; "opens"), and share that have already violated the constraint at word 0 ("fails w0"), plain reasoning channel. In unconstrained baseline runs the opener share is 1.00 in the Qwen3 and OLMo-3 models. "We" alternates case trivially, so the gpt-oss alternating-case "fails w0" is not an onset measure (Table 23, note a).

	Qwen3-8B		Qwen3-32B		OLMo-3-7B		OLMo-3-32B		gpt-oss-20b		gpt-oss-120b	
Constraint	opens	fails w0	opens	fails w0	opens	fails w0	opens	fails w0	opens	fails w0	opens	fails w0
Uppercase	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.99	1.00	0.55	0.50
Alternating case	1.00	1.00	0.99	1.00	0.98	0.98	1.00	1.00	0.92	0.07	0.88	0.00
Opening/closing string	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.01	0.01
End sentences with "safe"	1.00	0.00	1.00	0.00	1.00	0.00	1.00	0.00	0.98	0.00	0.93	0.00
Lowercase	1.00	0.88	1.00	0.85	1.00	0.25	1.00	1.00	0.98	0.99	0.69	0.27
"meow" between words	0.95	0.37	1.00	0.26	1.00	1.00	1.00	1.00	0.88	1.00	0.80	0.93
Suppress one keyword	1.00	0.00	1.00	0.00	1.00	0.00	1.00	0.00	0.98	0.00	0.99	0.00
Suppress several keywords	1.00	0.00	1.00	0.00	–	–	–	–	0.99	0.00	0.99	0.00

Table 4: Question-level 5-fold held-out log-likelihood per trace (higher is better; best in bold), six models, with question-clustered bootstrap intervals for the paired difference between gamma frailty and the exponential and Weibull models. Cells in which fewer than 10 traces adopt the constraint are omitted.

Model	Constraint	Expon.	Weibull	Onset mix.	Frailty	Onset+frailty	frailty − expon.	frailty − Weibull	$\hat{\theta}$
Qwen3-8B	lowercase	-2.131	-0.819	-0.814	-0.823	**-0.810**	1.31 [1.07, 1.60]	-0.004 [-0.007, -0.001]	3.56
	multiple word suppression	-3.087	-2.911	-3.013	**-2.875**	**-2.875**	0.21 [0.10, 0.38]	0.036 [0.015, 0.065]	0.49
	word suppression	-5.233	-4.952	-5.167	**-4.880**	**-4.880**	0.35 [0.21, 0.54]	0.072 [0.039, 0.113]	0.70
Qwen3-32B	lowercase	-2.178	**-0.825**	-0.858	-0.826	-0.829	1.35 [1.06, 1.81]	-0.001 [-0.004, 0.002]	3.59
	meow between words	-2.634	**-0.701**	-0.722	-0.703	-0.707	1.93 [1.47, 2.54]	-0.001 [-0.003, 0.000]	6.25
	multiple word suppression	-3.386	-3.090	-3.258	**-3.032**	**-3.032**	0.35 [0.18, 0.57]	0.058 [0.033, 0.091]	0.65
	word suppression	-5.559	-5.297	-5.527	**-5.217**	**-5.217**	0.34 [0.22, 0.49]	0.080 [0.050, 0.115]	1.06
OLMo-3-7B	lowercase	-0.438	-0.434	-0.438	-0.438	**-0.423**	0.00 [-0.00, 0.00]	-0.005 [-0.015, 0.006]	0.00
	word suppression	-5.107	-4.825	-5.047	**-4.737**	**-4.737**	0.37 [0.21, 0.56]	0.087 [0.049, 0.129]	0.69
OLMo-3-32B	word suppression	-5.065	-4.795	-5.019	**-4.708**	**-4.708**	0.36 [0.25, 0.49]	0.087 [0.060, 0.115]	0.69
gpt-oss-20b	multiple word suppression	-2.348	-1.996	-2.138	**-1.958**	**-1.958**	0.39 [0.19, 0.65]	0.039 [0.023, 0.057]	0.69
	word suppression	-4.154	-3.947	-4.076	**-3.907**	**-3.907**	0.25 [0.15, 0.35]	0.040 [0.019, 0.065]	0.69
gpt-oss-120b	alternating case	**-0.170**	-0.172	-0.171	-0.172	-0.171	-0.00 [-0.01, 0.00]	0.000 [-0.000, 0.001]	0.15
	lowercase	-0.413	-0.416	-0.413	**-0.404**	-0.406	0.01 [0.01, 0.01]	0.012 [-0.004, 0.034]	0.00
	meow between words	-0.576	-0.463	**-0.451**	-0.469	**-0.451**	0.11 [0.08, 0.14]	-0.006 [-0.009, -0.003]	0.96
	multiple word suppression	-2.462	-2.128	-2.238	**-2.102**	**-2.102**	0.36 [0.21, 0.56]	0.026 [0.010, 0.043]	0.84
	uppercase	-0.273	**-0.239**	-0.240	**-0.240**	-0.241	0.03 [0.01, 0.06]	-0.000 [-0.002, 0.001]	0.73
	word suppression	-4.130	-3.903	-4.030	**-3.870**	**-3.870**	0.26 [0.18, 0.33]	0.033 [0.014, 0.052]	1.12

Table 5: Fully compliant traces (%) under the prefix intervention, Qwen3 (continuation graded).

Constraint	Model	plain	prefix 20	prefix 100	prefix 100, no instr.
Uppercase	Qwen3-8B	0.0	2.0	3.3	0.2
Uppercase	Qwen3-32B	0.0	38.0	45.2	27.8
Lowercase	Qwen3-8B	2.8	12.8	20.5	1.7
Lowercase	Qwen3-32B	4.2	32.5	49.2	15.8
Alternating	Qwen3-8B	0.0	0.0	0.0	–
Alternating	Qwen3-32B	0.0	0.7	2.2	–

Uncertainty and display rule. Tables 6, 8 and 7 give 95% percentile intervals for every π, λ, C_{100} and C_{500} from 1,000 bootstrap resamples. The resampling unit is the *question*: each resample

draws 300 questions with replacement and takes every trace of a drawn question (all samples, all arms), so the intervals account for the dependence between samples of one question and between arms that share questions. The same question draws are used in every cell, so ratios between arms or models are paired (Tables 9, 20); the attribution (Table 25) uses the same scheme with its own 1,000 draws. Throughout the paper a slip rate, a window hazard or a ratio of two is printed only when at least 10 traces are at risk (adopt the constraint, or enter the window compliant) *and* at least 10 first slips are observed at or after the window start in every cell involved; otherwise the cell shows "–" or the row is omitted. Percentile intervals from fewer events are not interpretable (a single event gives a degenerate interval), so we do not print them; the ratio tables print the slip counts of both arms, and intervals from 10–25 slips are wide and asymmetric, as several gpt-oss-120b cells show. Intervals are not adjusted for multiple comparisons; the stars in Tables 9 and 20 are descriptive, and the contrasts that were pre-registered (E10 D3, marked $^{\mathrm{p}}$) are the only ones scored as tests (Table 2).

Table 6: Plain reasoning channel: point estimates with 95% question-clustered bootstrap intervals, including the Qwen3-4B and 14B runs of the size series and the released OLMo-3-7B base model under the base-model protocol. Lowercase cells for Qwen3 pool 1,200 additional traces (second seed) with the main run. [s]For the sentence-level constraint π is the share of traces whose first sentence complies, as in Table 1; a word-window slip rate is not defined for it (its first sentence is about 20 words long), so λ is not printed. [e]Opening/closing string: two checkpoints, no slip process; π is the opening checkpoint (99.3–99.7% in gpt-oss) and 99.3%–99.7% of gpt-oss failures fall at the last word, so λ and C_L are not printed.

Constraint	Model	n	π	λ	C_{100}	C_{500}	binary (%)
Uppercase	Qwen3-8B	900	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	Qwen3-32B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-7B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-32B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-20b	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-120b	600	0.03 [0.02, 0.05]	40.1 [21.7, 71.7]	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]	1.0 [0.2, 2.0]
	Qwen3-4B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	Qwen3-14B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-7B base	367	0.00 [0.00, 0.01]	–	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]	0.3 [0.0, 0.9]
Alternating case	Qwen3-8B	900	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	Qwen3-32B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-7B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-32B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-20b	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-120b	600	0.02 [0.01, 0.04]	122.2 [74.1, 216.2]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.3 [0.0, 1.0]
	Qwen3-4B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	Qwen3-14B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-7B base	497	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
Opening/closing string	Qwen3-8B	900	0.00 [0.00, 0.00][e]	–	–	–	0.0 [0.0, 0.0]
	Qwen3-32B	600	0.00 [0.00, 0.00][e]	–	–	–	0.0 [0.0, 0.0]
	OLMo-3-7B	600	0.00 [0.00, 0.00][e]	–	–	–	0.0 [0.0, 0.0]
	OLMo-3-32B	600	0.00 [0.00, 0.00][e]	–	–	–	0.0 [0.0, 0.0]
	gpt-oss-20b	600	1.00 [0.99, 1.00][e]	–	–	–	1.8 [0.8, 3.0]
	gpt-oss-120b	600	0.99 [0.98, 1.00][e]	–	–	–	7.7 [5.3, 10.3]
	OLMo-3-7B base	571	0.10 [0.07, 0.12][e]	–	–	–	0.0 [0.0, 0.0]
End sentences with "safe"	Qwen3-8B	900	0.00[s]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	Qwen3-32B	600	0.00[s]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-7B	600	0.00[s]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-32B	600	0.00[s]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-20b	600	0.00[s]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-120b	600	0.00[s]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-7B base	570	–	–	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]	0.2 [0.0, 0.6]
Lowercase	Qwen3-8B	2100	0.09 [0.07, 0.12]	1.8 [1.4, 2.4]	0.07 [0.05, 0.10]	0.04 [0.02, 0.05]	2.8 [1.7, 4.1]
	Qwen3-32B	1800	0.11 [0.09, 0.13]	1.6 [1.1, 2.2]	0.07 [0.05, 0.09]	0.04 [0.03, 0.06]	4.2 [2.9, 5.4]
	OLMo-3-7B	600	0.07 [0.05, 0.10]	221.1 [166.1, 322.0]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-32B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-20b	600	0.00 [0.00, 0.01]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-120b	600	0.06 [0.04, 0.09]	220.3 [147.8, 375.0]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	Qwen3-4B	1800	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	Qwen3-14B	1800	0.01 [0.00, 0.01]	–	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]	0.2 [0.0, 0.6]
	OLMo-3-7B base	378	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
"meow" between words	Qwen3-8B	900	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.1 [0.0, 0.3]
	Qwen3-32B	600	0.10 [0.08, 0.13]	0.7 [0.4, 1.2]	0.09 [0.06, 0.11]	0.06 [0.04, 0.09]	5.3 [3.5, 7.3]
	OLMo-3-7B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-32B	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-20b	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	gpt-oss-120b	600	0.05 [0.03, 0.08]	24.8 [20.2, 30.6]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
	OLMo-3-7B base	560	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]	0.0 [0.0, 0.0]
Suppress one keyword	Qwen3-8B	900	0.76 [0.71, 0.80]	5.5 [4.2, 7.3]	0.28 [0.24, 0.32]	0.06 [0.04, 0.09]	1.3 [0.3, 2.6]
	Qwen3-32B	600	0.86 [0.83, 0.90]	3.2 [2.5, 4.1]	0.45 [0.40, 0.50]	0.16 [0.12, 0.19]	10.3 [7.6, 13.5]
	OLMo-3-7B	600	0.75 [0.70, 0.79]	6.2 [4.6, 8.4]	0.27 [0.23, 0.32]	0.06 [0.04, 0.08]	1.3 [0.3, 2.6]
	OLMo-3-32B	600	0.75 [0.70, 0.80]	6.7 [5.3, 8.7]	0.23 [0.19, 0.27]	0.06 [0.03, 0.08]	0.8 [0.2, 1.6]
	gpt-oss-20b	600	0.64 [0.59, 0.69]	9.4 [7.3, 12.2]	0.19 [0.16, 0.24]	0.04 [0.03, 0.07]	3.5 [1.9, 5.5]
	gpt-oss-120b	600	0.69 [0.65, 0.74]	6.2 [5.0, 7.7]	0.28 [0.24, 0.33]	0.10 [0.07, 0.14]	13.2 [9.8, 16.7]
	Qwen3-4B	600	0.73 [0.68, 0.77]	6.6 [5.1, 9.0]	0.24 [0.20, 0.28]	0.05 [0.03, 0.07]	1.0 [0.2, 2.1]
	Qwen3-14B	600	0.80 [0.76, 0.84]	5.0 [3.9, 6.7]	0.33 [0.29, 0.38]	0.09 [0.06, 0.12]	3.2 [1.5, 5.2]
	OLMo-3-7B base	443	0.68 [0.63, 0.73]	4.7 [3.4, 6.8]	0.20 [0.16, 0.25]	0.06 [0.04, 0.09]	6.8 [4.4, 9.2]
Suppress several keywords	Qwen3-8B	900	0.46 [0.40, 0.51]	17.4 [12.5, 24.5]	0.07 [0.05, 0.09]	0.01 [0.00, 0.01]	0.0 [0.0, 0.0]
	Qwen3-32B	600	0.49 [0.44, 0.54]	12.5 [8.9, 19.3]	0.09 [0.06, 0.12]	0.02 [0.01, 0.04]	1.3 [0.3, 2.7]
	gpt-oss-20b	600	0.30 [0.26, 0.35]	14.8 [9.6, 27.6]	0.04 [0.02, 0.06]	0.02 [0.01, 0.03]	1.3 [0.4, 2.4]
	gpt-oss-120b	600	0.32 [0.28, 0.37]	13.8 [9.8, 20.7]	0.07 [0.05, 0.10]	0.01 [0.00, 0.03]	2.2 [0.8, 3.8]

Table 7: Prefix intervention and prompt-only arms: point estimates with 95% question-clustered bootstrap intervals. "7B base/SFT/DPO/RL-Zero-*" are OLMo-3-7B checkpoints.

Constraint	Model	Arm	n	π	λ	C_{100}	C_{500}
Uppercase	Qwen3-8B	plain	900	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.05 [0.03, 0.07]	5.2 [3.5, 7.6]	0.04 [0.02, 0.05]	0.00 [0.00, 0.01]
		prefix 5	600	0.81 [0.77, 0.85]	11.7 [10.3, 13.4]	0.27 [0.22, 0.31]	0.02 [0.00, 0.03]
		prefix 20	600	0.77 [0.72, 0.81]	14.6 [12.7, 17.0]	0.17 [0.13, 0.21]	0.01 [0.00, 0.02]
		prefix 100	600	0.67 [0.63, 0.72]	12.7 [10.8, 14.9]	0.20 [0.16, 0.24]	0.01 [0.00, 0.03]

(continued)

Constraint	Model	Arm	n	π	λ	C_{100}	C_{500}
		prefix 20, no instr.	600	0.44 [0.39, 0.49]	46.4 [39.4, 55.8]	0.02 [0.01, 0.03]	0.00 [0.00, 0.00]
		prefix 100, no instr.	600	0.45 [0.40, 0.50]	27.2 [22.4, 34.0]	0.06 [0.03, 0.08]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.07 [0.05, 0.10]	0.5 [0.2, 1.7]	0.06 [0.03, 0.08]	0.04 [0.03, 0.07]
		prompt: demo	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Uppercase	Qwen3-32B	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.59 [0.54, 0.64]	1.6 [1.3, 1.9]	0.46 [0.42, 0.51]	0.27 [0.23, 0.32]
		prefix 5	600	0.81 [0.77, 0.85]	1.3 [1.1, 1.6]	0.61 [0.56, 0.66]	0.38 [0.33, 0.43]
		prefix 20	600	0.92 [0.89, 0.95]	1.4 [1.2, 1.7]	0.69 [0.65, 0.73]	0.42 [0.37, 0.47]
		prefix 100	600	0.95 [0.93, 0.97]	1.2 [1.0, 1.4]	0.77 [0.72, 0.81]	0.49 [0.43, 0.54]
		prefix 20, no instr.	600	0.74 [0.70, 0.78]	3.1 [2.5, 3.8]	0.40 [0.35, 0.45]	0.20 [0.16, 0.25]
		prefix 100, no instr.	600	0.90 [0.88, 0.93]	2.1 [1.8, 2.4]	0.65 [0.61, 0.70]	0.32 [0.27, 0.37]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prompt: demo	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Uppercase	OLMo-3-7B	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.01 [0.00, 0.02]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 5	600	0.13 [0.09, 0.17]	49.4 [38.9, 64.7]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prefix 20	600	0.27 [0.24, 0.32]	45.3 [36.6, 56.2]	0.01 [0.00, 0.02]	0.00 [0.00, 0.00]
		prefix 100	600	0.24 [0.20, 0.28]	38.2 [28.9, 50.5]	0.01 [0.00, 0.02]	0.00 [0.00, 0.00]
		prefix 20, no instr.	600	0.15 [0.11, 0.19]	73.8 [60.6, 93.7]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 100, no instr.	600	0.17 [0.14, 0.21]	57.3 [45.5, 74.7]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Uppercase	OLMo-3-32B	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.85 [0.82, 0.88]	9.7 [8.7, 11.0]	0.36 [0.32, 0.41]	0.01 [0.00, 0.03]
		prefix 5	600	0.89 [0.85, 0.92]	9.3 [8.4, 10.2]	0.43 [0.38, 0.48]	0.01 [0.00, 0.02]
		prefix 20	600	0.82 [0.78, 0.86]	9.7 [8.6, 10.9]	0.36 [0.31, 0.40]	0.01 [0.00, 0.03]
		prefix 100	600	0.74 [0.70, 0.78]	10.5 [9.3, 11.8]	0.30 [0.26, 0.34]	0.00 [0.00, 0.01]
		prefix 20, no instr.	600	0.41 [0.36, 0.46]	42.4 [32.1, 55.1]	0.02 [0.01, 0.04]	0.00 [0.00, 0.01]
		prefix 100, no instr.	600	0.46 [0.41, 0.50]	19.3 [16.6, 22.7]	0.10 [0.07, 0.13]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Uppercase	gpt-oss-20b	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.11 [0.09, 0.14]	20.7 [14.3, 31.2]	0.03 [0.01, 0.04]	0.01 [0.00, 0.03]
		prefix 5	600	0.02 [0.01, 0.03]	123.6 [61.9, 304.3]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.06 [0.03, 0.08]	38.5 [18.7, 89.8]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prefix 100	600	0.05 [0.03, 0.07]	34.4 [18.2, 120.1]	0.01 [0.00, 0.02]	0.00 [0.00, 0.00]
		prefix 20, no instr.	600	0.04 [0.02, 0.06]	49.5 [26.3, 119.7]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.00 [0.00, 0.01]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prompt: demo	600	0.11 [0.08, 0.13]	96.5 [66.0, 123.7]	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]
Uppercase	gpt-oss-120b	plain	600	0.03 [0.02, 0.05]	40.1 [21.7, 71.7]	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]
		prefix 1	600	0.01 [0.00, 0.02]	–	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]
		prefix 5	600	0.01 [0.00, 0.02]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.05 [0.03, 0.08]	87.7 [58.2, 149.3]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 100	600	0.03 [0.01, 0.05]	47.4 [21.3, 160.1]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prefix 20, no instr.	600	0.04 [0.02, 0.06]	37.6 [14.5, 203.6]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.39 [0.34, 0.43]	44.3 [35.3, 54.5]	0.02 [0.00, 0.03]	0.00 [0.00, 0.02]
		prompt: demo	600	0.98 [0.96, 0.99]	26.1 [23.7, 29.0]	0.11 [0.08, 0.14]	0.00 [0.00, 0.00]
Uppercase	Qwen3-4B	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.09 [0.06, 0.12]	75.0 [56.2, 108.5]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 100	600	0.12 [0.09, 0.15]	49.3 [37.7, 66.2]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prefix 20, no instr.	600	0.08 [0.05, 0.11]	94.0 [68.0, 141.6]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Uppercase	Qwen3-14B	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.47 [0.41, 0.52]	3.4 [2.8, 4.2]	0.32 [0.27, 0.36]	0.11 [0.07, 0.15]
		prefix 20	600	0.81 [0.78, 0.85]	5.4 [4.7, 6.3]	0.44 [0.39, 0.49]	0.09 [0.06, 0.12]
		prefix 100	600	0.87 [0.84, 0.90]	5.2 [4.6, 6.0]	0.49 [0.44, 0.54]	0.09 [0.05, 0.12]
		prefix 20, no instr.	600	0.48 [0.43, 0.53]	35.2 [27.3, 45.5]	0.04 [0.02, 0.06]	0.00 [0.00, 0.01]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prompt: demo	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Uppercase	7B base	plain	367	0.00 [0.00, 0.01]	–	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]
		prefix 20	483	0.75 [0.71, 0.80]	1.3 [1.1, 1.8]	0.49 [0.43, 0.54]	0.32 [0.27, 0.37]
		prefix 20, no instr.	480	0.72 [0.67, 0.76]	1.4 [1.1, 1.8]	0.48 [0.43, 0.54]	0.32 [0.26, 0.37]
Uppercase	7B RL-Zero-Math	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.84 [0.81, 0.88]	1.2 [1.0, 1.5]	0.63 [0.58, 0.67]	0.35 [0.30, 0.39]
		prefix 20, no instr.	600	0.74 [0.70, 0.79]	1.8 [1.4, 2.2]	0.48 [0.43, 0.53]	0.24 [0.20, 0.29]
Uppercase	7B RL-Zero-Code	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.85 [0.82, 0.88]	2.9 [2.4, 3.6]	0.55 [0.51, 0.60]	0.22 [0.17, 0.28]
		prefix 20, no instr.	600	0.73 [0.69, 0.77]	4.2 [3.5, 5.3]	0.41 [0.37, 0.46]	0.14 [0.10, 0.19]
Uppercase	7B RL-Zero-General	plain	573	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	598	0.49 [0.44, 0.54]	6.1 [4.5, 8.6]	0.17 [0.13, 0.20]	0.09 [0.06, 0.12]
		prefix 20, no instr.	599	0.39 [0.34, 0.44]	7.4 [5.0, 11.3]	0.11 [0.08, 0.14]	0.06 [0.04, 0.09]
Uppercase	7B SFT	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.33 [0.29, 0.38]	34.7 [29.1, 42.7]	0.02 [0.01, 0.04]	0.00 [0.00, 0.00]
		prefix 20, no instr.	600	0.21 [0.17, 0.25]	53.8 [44.5, 68.6]	0.01 [0.00, 0.01]	0.00 [0.00, 0.00]
Uppercase	7B DPO	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.28 [0.23, 0.33]	41.7 [34.5, 51.1]	0.01 [0.00, 0.02]	0.00 [0.00, 0.00]
Lowercase	Qwen3-8B	plain	2100	0.09 [0.07, 0.12]	1.8 [1.4, 2.4]	0.07 [0.05, 0.10]	0.04 [0.02, 0.05]
		prefix 1	600	0.73 [0.68, 0.78]	2.6 [2.2, 3.2]	0.43 [0.38, 0.48]	0.20 [0.16, 0.24]

(continued)

Constraint	Model	Arm	n	π	λ	C_{100}	C_{500}
		prefix 5	600	0.69 [0.64, 0.74]	3.0 [2.4, 3.6]	0.38 [0.33, 0.43]	0.17 [0.13, 0.21]
		prefix 20	600	0.66 [0.62, 0.71]	2.3 [1.9, 2.8]	0.45 [0.40, 0.50]	0.20 [0.16, 0.24]
		prefix 100	600	0.92 [0.89, 0.95]	2.0 [1.7, 2.3]	0.73 [0.68, 0.77]	0.33 [0.28, 0.38]
		prefix 20, no instr.	600	0.22 [0.18, 0.26]	17.7 [13.8, 23.8]	0.04 [0.03, 0.07]	0.00 [0.00, 0.01]
		prefix 100, no instr.	600	0.74 [0.69, 0.78]	8.1 [6.8, 9.6]	0.30 [0.26, 0.35]	0.04 [0.02, 0.06]
		prompt: opener hint	600	0.68 [0.64, 0.73]	1.3 [1.1, 1.5]	0.52 [0.47, 0.57]	0.35 [0.30, 0.40]
		prompt: demo	600	0.43 [0.38, 0.48]	1.1 [0.9, 1.3]	0.33 [0.29, 0.38]	0.23 [0.19, 0.28]
Lowercase	Qwen3-32B	plain	1800	0.11 [0.09, 0.13]	1.6 [1.1, 2.2]	0.07 [0.05, 0.09]	0.04 [0.03, 0.06]
		prefix 1	600	0.73 [0.69, 0.77]	1.6 [1.3, 2.0]	0.47 [0.42, 0.51]	0.31 [0.27, 0.36]
		prefix 5	600	0.69 [0.64, 0.73]	1.2 [1.0, 1.5]	0.50 [0.46, 0.55]	0.34 [0.29, 0.39]
		prefix 20	600	0.84 [0.80, 0.88]	1.4 [1.1, 1.6]	0.66 [0.61, 0.70]	0.40 [0.35, 0.45]
		prefix 100	600	0.96 [0.94, 0.98]	0.7 [0.6, 0.8]	0.86 [0.83, 0.89]	0.64 [0.58, 0.68]
		prefix 20, no instr.	600	0.47 [0.42, 0.53]	5.2 [4.2, 6.5]	0.21 [0.18, 0.26]	0.07 [0.04, 0.09]
		prefix 100, no instr.	600	0.87 [0.84, 0.91]	2.2 [1.9, 2.7]	0.63 [0.58, 0.68]	0.24 [0.20, 0.29]
		prompt: opener hint	600	0.00 [0.00, 0.01]	–	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]
		prompt: demo	600	0.13 [0.10, 0.16]	0.5 [0.3, 0.8]	0.12 [0.09, 0.14]	0.09 [0.07, 0.12]
Lowercase	OLMo-3-7B	plain	600	0.07 [0.05, 0.10]	221.1 [166.1, 322.0]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.11 [0.08, 0.14]	162.4 [99.2, 274.9]	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]
		prefix 5	600	0.11 [0.08, 0.14]	45.7 [23.4, 121.8]	0.01 [0.00, 0.02]	0.00 [0.00, 0.00]
		prefix 20	600	0.22 [0.18, 0.27]	12.5 [9.5, 17.9]	0.06 [0.04, 0.08]	0.01 [0.00, 0.01]
		prefix 100	600	0.65 [0.60, 0.70]	9.2 [8.0, 10.8]	0.28 [0.23, 0.32]	0.02 [0.01, 0.03]
		prefix 20, no instr.	600	0.08 [0.05, 0.11]	33.0 [17.3, 84.2]	0.01 [0.00, 0.01]	0.00 [0.00, 0.01]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Lowercase	OLMo-3-32B	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.14 [0.11, 0.18]	4.6 [2.9, 8.0]	0.07 [0.05, 0.10]	0.01 [0.00, 0.03]
		prefix 5	600	0.40 [0.35, 0.45]	3.8 [3.2, 4.7]	0.24 [0.20, 0.29]	0.08 [0.05, 0.11]
		prefix 20	600	0.72 [0.67, 0.76]	2.7 [2.3, 3.2]	0.52 [0.47, 0.57]	0.18 [0.14, 0.22]
		prefix 100	600	0.92 [0.89, 0.94]	2.5 [2.2, 2.9]	0.68 [0.64, 0.73]	0.28 [0.23, 0.33]
		prefix 20, no instr.	600	0.23 [0.20, 0.28]	10.9 [8.3, 15.1]	0.07 [0.05, 0.10]	0.01 [0.00, 0.01]
		prefix 100, no instr.	600	0.74 [0.69, 0.78]	6.6 [5.8, 7.7]	0.37 [0.32, 0.41]	0.05 [0.03, 0.07]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Lowercase	gpt-oss-20b	plain	600	0.00 [0.00, 0.01]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.07 [0.05, 0.10]	111.9 [78.5, 168.8]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 5	600	0.05 [0.03, 0.07]	173.7 [119.4, 295.5]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.06 [0.03, 0.08]	61.8 [32.5, 146.7]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prefix 100	600	0.08 [0.05, 0.11]	34.5 [21.7, 74.7]	0.01 [0.00, 0.02]	0.00 [0.00, 0.00]
		prefix 20, no instr.	600	0.04 [0.02, 0.06]	103.3 [71.6, 200.0]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.14 [0.11, 0.17]	68.1 [50.3, 92.1]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prompt: demo	600	0.34 [0.29, 0.39]	71.0 [62.4, 81.8]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
Lowercase	gpt-oss-120b	plain	600	0.06 [0.04, 0.09]	220.3 [147.8, 375.0]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.07 [0.05, 0.10]	130.6 [89.1, 244.4]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 5	600	0.04 [0.03, 0.07]	117.9 [70.3, 269.9]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.05 [0.03, 0.07]	45.7 [19.2, 182.9]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prefix 100	600	0.09 [0.06, 0.13]	65.6 [38.3, 121.2]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prefix 20, no instr.	600	0.03 [0.01, 0.05]	34.9 [12.0, 514.4]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.20 [0.16, 0.24]	70.2 [55.3, 93.6]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prompt: demo	600	0.48 [0.43, 0.53]	28.4 [25.3, 32.5]	0.04 [0.02, 0.06]	0.00 [0.00, 0.01]
Lowercase	Qwen3-4B	plain	1800	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 1	600	0.01 [0.00, 0.02]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.10 [0.07, 0.14]	13.5 [9.0, 22.6]	0.04 [0.02, 0.06]	0.00 [0.00, 0.01]
		prefix 100	600	0.74 [0.69, 0.78]	9.2 [8.0, 10.7]	0.29 [0.25, 0.34]	0.02 [0.01, 0.03]
		prefix 20, no instr.	600	0.04 [0.03, 0.07]	69.2 [31.7, 365.4]	0.00 [0.00, 0.01]	0.00 [0.00, 0.00]
		prompt: opener hint	600	0.03 [0.01, 0.05]	2.2 [0.8, 5.5]	0.03 [0.01, 0.04]	0.01 [0.00, 0.03]
Lowercase	Qwen3-14B	plain	1800	0.01 [0.00, 0.01]	–	0.00 [0.00, 0.01]	0.00 [0.00, 0.01]
		prefix 1	600	0.56 [0.51, 0.61]	2.7 [2.3, 3.3]	0.36 [0.32, 0.41]	0.17 [0.13, 0.20]
		prefix 20	600	0.74 [0.69, 0.78]	2.8 [2.3, 3.4]	0.46 [0.41, 0.51]	0.18 [0.15, 0.22]
		prefix 100	600	0.91 [0.89, 0.94]	1.8 [1.5, 2.1]	0.73 [0.69, 0.78]	0.33 [0.29, 0.38]
		prefix 20, no instr.	600	0.26 [0.22, 0.30]	12.7 [9.8, 17.3]	0.08 [0.05, 0.10]	0.01 [0.00, 0.02]
		prompt: opener hint	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prompt: demo	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
Lowercase	7B base	plain	378	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	498	0.62 [0.57, 0.67]	5.2 [4.1, 6.6]	0.31 [0.26, 0.36]	0.09 [0.05, 0.13]
Lowercase	7B RL-Zero-Math	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.68 [0.63, 0.72]	3.5 [2.9, 4.3]	0.39 [0.34, 0.43]	0.14 [0.11, 0.18]
Lowercase	7B RL-Zero-Code	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.65 [0.60, 0.69]	5.0 [4.1, 6.2]	0.35 [0.31, 0.40]	0.06 [0.04, 0.09]
Lowercase	7B RL-Zero-General	plain	580	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	598	0.47 [0.43, 0.52]	10.6 [7.9, 14.3]	0.15 [0.11, 0.18]	0.03 [0.01, 0.05]
Lowercase	7B SFT	plain	600	0.00 [0.00, 0.00]	–	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.25 [0.21, 0.29]	11.5 [8.7, 15.4]	0.07 [0.05, 0.09]	0.01 [0.00, 0.01]
Lowercase	7B DPO	plain	600	0.02 [0.01, 0.03]	164.2 [120.8, 344.8]	0.00 [0.00, 0.00]	0.00 [0.00, 0.00]
		prefix 20	600	0.11 [0.08, 0.14]	12.7 [8.5, 22.6]	0.03 [0.02, 0.05]	0.00 [0.00, 0.01]

Table 8: External-CoT and output channels for the four Qwen3 sizes (95% question-clustered bootstrap intervals), with the median trace length and the share of traces shorter than 20 and 100 words. External CoT at the smaller sizes is short (Qwen3-4B uppercase: median 4 words); π counts a trace that ends compliant before word 20 as adopted (§2), so at Qwen3-4B uppercase it is 0.19 (binary 18.7%) rather than the 0.09 obtained by dropping such traces, and the 4B external cells are not attributed. [e]Opening/closing string: two checkpoints, no λ or C_L. External CoT is parsed case-insensitively (see "External-channel parsing" below).

Channel	Constraint	Model	n	median words	<20 / <100 w. (%)	π	λ	C_{100}	binary (%)
external CoT	Uppercase	Qwen3-4B	600	4	50 / 72	0.09 [0.06, 0.12]	–	0.17 [0.13, 0.22]	18.7 [14.7, 22.7]
		Qwen3-8B	600	88	24 / 60	0.59 [0.53, 0.65]	2.0 [1.3, 2.7]	0.52 [0.47, 0.58]	54.3 [49.3, 59.7]
		Qwen3-14B	600	133	0 / 28	0.83 [0.79, 0.87]	1.8 [1.2, 2.8]	0.65 [0.60, 0.70]	63.0 [57.8, 67.9]
		Qwen3-32B	600	126	2 / 36	0.82 [0.79, 0.86]	2.4 [1.5, 3.6]	0.62 [0.57, 0.67]	60.2 [55.1, 65.0]
external CoT	Alternating case	Qwen3-8B	600	124	4 / 40	0.03 [0.02, 0.05]	53.2 [31.1, 103.3]	0.00 [0.00, 0.01]	2.0 [0.8, 3.3]
		Qwen3-32B	600	127	2 / 34	0.23 [0.20, 0.27]	31.3 [26.4, 38.1]	0.03 [0.01, 0.04]	4.2 [2.7, 5.9]
external CoT	Opening/closing string	Qwen3-8B	600	203	0 / 12	0.04 [0.02, 0.06][e]	–	–	0.3 [0.0, 0.8]
		Qwen3-32B	600	170	12 / 22	0.64 [0.59, 0.68][e]	–	–	13.5 [10.5, 16.9]
external CoT	End sentences with "safe"	Qwen3-8B	600	102	4 / 48	0.43 [0.39, 0.48]	162.4 [140.5, 188.6]	0.00 [0.00, 0.01]	0.7 [0.2, 1.4]
		Qwen3-32B	600	170	0 / 13	0.55 [0.51, 0.60]	92.0 [72.8, 117.8]	0.02 [0.01, 0.03]	1.7 [0.6, 2.9]
external CoT	Lowercase	Qwen3-4B	600	69	30 / 74	0.59 [0.53, 0.64]	0.9 [0.5, 1.5]	0.55 [0.49, 0.60]	56.8 [51.3, 62.0]
		Qwen3-8B	600	97	10 / 52	0.84 [0.80, 0.87]	0.6 [0.4, 1.1]	0.78 [0.74, 0.82]	77.0 [73.0, 81.4]
		Qwen3-14B	600	136	0 / 30	0.97 [0.95, 0.98]	0.4 [0.2, 0.6]	0.91 [0.88, 0.94]	89.8 [86.5, 92.6]
		Qwen3-32B	600	126	4 / 36	0.93 [0.91, 0.96]	0.4 [0.2, 0.5]	0.88 [0.85, 0.91]	86.8 [83.4, 89.9]
external CoT	"meow" between words	Qwen3-8B	600	2047	4 / 24	0.01 [0.00, 0.02]	–	0.01 [0.00, 0.03]	2.0 [0.8, 3.4]
		Qwen3-32B	600	291	0 / 4	0.94 [0.92, 0.96]	0.7 [0.5, 0.9]	0.88 [0.85, 0.90]	76.2 [72.2, 80.3]
external CoT	Suppress one keyword	Qwen3-4B	600	84	36 / 58	0.38 [0.33, 0.43]	11.0 [8.6, 14.0]	0.14 [0.11, 0.18]	13.2 [10.0, 16.6]
		Qwen3-8B	600	129	15 / 36	0.66 [0.61, 0.71]	6.3 [4.4, 8.7]	0.35 [0.30, 0.40]	29.2 [24.8, 34.1]
		Qwen3-14B	600	150	0 / 22	0.92 [0.89, 0.95]	2.6 [1.8, 3.8]	0.64 [0.59, 0.69]	56.0 [50.8, 60.8]
		Qwen3-32B	600	153	1 / 26	0.94 [0.91, 0.96]	1.6 [1.2, 2.0]	0.79 [0.74, 0.83]	72.2 [67.7, 76.5]
output	Uppercase	Qwen3-8B	600	136	0 / 29	0.18 [0.14, 0.23]	2.0 [0.8, 3.6]	0.16 [0.12, 0.19]	15.8 [11.9, 19.8]
		Qwen3-32B	600	176	0 / 14	0.38 [0.33, 0.42]	1.6 [1.0, 2.5]	0.30 [0.25, 0.34]	29.7 [25.4, 34.2]
output	Alternating case	Qwen3-8B	600	169	0 / 17	0.02 [0.01, 0.03]	–	0.01 [0.00, 0.02]	1.2 [0.3, 2.1]
		Qwen3-32B	600	192	0 / 10	0.19 [0.15, 0.22]	35.5 [26.8, 48.1]	0.01 [0.01, 0.02]	0.3 [0.0, 0.8]
output	Opening/closing string	Qwen3-8B	600	248	1 / 8	0.30 [0.25, 0.36][e]	–	–	28.3 [23.3, 33.3]
		Qwen3-32B	600	309	0 / 2	0.60 [0.55, 0.64][e]	–	–	59.3 [54.3, 64.0]
output	End sentences with "safe"	Qwen3-8B	600	181	0 / 9	0.36 [0.30, 0.41]	34.6 [25.8, 48.7]	0.04 [0.03, 0.07]	4.3 [2.4, 6.4]
		Qwen3-32B	600	204	0 / 3	0.29 [0.25, 0.33]	34.6 [24.8, 49.0]	0.03 [0.02, 0.05]	2.8 [1.5, 4.4]
output	Lowercase	Qwen3-8B	600	121	0 / 35	0.78 [0.73, 0.83]	0.8 [0.5, 1.2]	0.70 [0.65, 0.75]	69.3 [64.2, 74.4]
		Qwen3-32B	600	186	0 / 13	0.96 [0.95, 0.98]	0.6 [0.4, 0.8]	0.89 [0.86, 0.92]	84.8 [81.7, 88.5]
output	"meow" between words	Qwen3-8B	600	272	7 / 15	0.06 [0.03, 0.08]	0.5 [0.2, 1.5]	0.06 [0.03, 0.08]	4.3 [2.4, 6.4]
		Qwen3-32B	600	317	0 / 0	0.91 [0.88, 0.94]	0.9 [0.7, 1.1]	0.83 [0.79, 0.86]	69.7 [65.3, 74.2]
output	Suppress one keyword	Qwen3-8B	600	250	0 / 4	0.81 [0.77, 0.85]	3.7 [3.0, 4.5]	0.50 [0.45, 0.56]	32.7 [28.2, 37.6]
		Qwen3-32B	600	218	0 / 8	0.86 [0.83, 0.90]	1.1 [0.9, 1.4]	0.74 [0.70, 0.79]	65.7 [61.1, 70.1]

Table 9: Paired bootstrap ratios of time-averaged slip rates λ (numerator / denominator), with the number of first slips in each arm. *: 95% interval excludes 1 (unadjusted; descriptive). P: pre-registered contrast (E10 D3). Cells with fewer than 10 adopters or 10 slips in either arm are omitted. "7B …" are OLMo-3-7B checkpoints.

Constraint	Numerator	Denominator	λ	slips	Ratio [95% CI]
K=100 vs K=20					
lowercase	OLMo-3-32B, prefix 100	OLMo-3-32B, prefix 20	2.5 / 2.7	455 / 365	0.91 [0.77, 1.08]
uppercase	OLMo-3-32B, prefix 100	OLMo-3-32B, prefix 20	10.5 / 9.7	432 / 480	1.08 [0.97, 1.20]
alternating case	OLMo-3-32B, prefix 100	OLMo-3-32B, prefix 20	85.9 / 86.4	107 / 91	0.99 [0.72, 1.34]
lowercase	OLMo-3-7B, prefix 100	OLMo-3-7B, prefix 20	9.2 / 12.5	390 / 133	0.74 [0.53, 0.96]*
uppercase	OLMo-3-7B, prefix 100	OLMo-3-7B, prefix 20	38.2 / 45.3	144 / 163	0.84 [0.60, 1.24]
lowercase	Qwen3-32B, prefix 100	Qwen3-32B, prefix 20	0.7 / 1.4	283 / 310	0.50 [0.41, 0.61]*P
uppercase	Qwen3-32B, prefix 100	Qwen3-32B, prefix 20	1.2 / 1.4	300 / 323	0.85 [0.70, 1.02]P
alternating case	Qwen3-32B, prefix 100	Qwen3-32B, prefix 20	18.4 / 26.1	325 / 265	0.71 [0.57, 0.87]*P
lowercase	Qwen3-8B, prefix 100	Qwen3-8B, prefix 20	2.0 / 2.3	428 / 321	0.86 [0.72, 1.03]P
uppercase	Qwen3-8B, prefix 100	Qwen3-8B, prefix 20	12.7 / 14.6	384 / 450	0.87 [0.72, 1.04]P
alternating case	Qwen3-8B, prefix 100	Qwen3-8B, prefix 20	58.9 / 85.3	129 / 64	0.69 [0.43, 1.05]P
lowercase	gpt-oss-20b, prefix 100	gpt-oss-20b, prefix 20	34.5 / 61.8	46 / 33	0.56 [0.23, 1.10]
uppercase	gpt-oss-20b, prefix 100	gpt-oss-20b, prefix 20	34.4 / 38.5	27 / 34	0.89 [0.35, 2.05]
lowercase	gpt-oss-120b, prefix 100	gpt-oss-120b, prefix 20	65.6 / 45.7	56 / 28	1.44 [0.43, 2.44]
uppercase	gpt-oss-120b, prefix 100	gpt-oss-120b, prefix 20	47.4 / 87.7	19 / 32	0.54 [0.20, 1.95]
alternating case	gpt-oss-120b, prefix 100	gpt-oss-120b, prefix 20	37.2 / 128.7	11 / 22	0.29 [0.08, 3.97]
lowercase	Qwen3-14B, prefix 100	Qwen3-14B, prefix 20	1.8 / 2.8	395 / 352	0.64 [0.52, 0.78]*
uppercase	Qwen3-14B, prefix 100	Qwen3-14B, prefix 20	5.2 / 5.4	410 / 404	0.97 [0.84, 1.10]
alternating case	Qwen3-14B, prefix 100	Qwen3-14B, prefix 20	26.9 / 49.3	285 / 179	0.54 [0.40, 0.71]*
lowercase	Qwen3-4B, prefix 100	Qwen3-4B, prefix 20	9.2 / 13.5	429 / 62	0.68 [0.41, 1.00]*
uppercase	Qwen3-4B, prefix 100	Qwen3-4B, prefix 20	49.3 / 75.0	71 / 56	0.66 [0.42, 1.02]
K=20 vs K=5					
lowercase	OLMo-3-32B, prefix 20	OLMo-3-32B, prefix 5	2.7 / 3.8	365 / 208	0.71 [0.58, 0.87]*
uppercase	OLMo-3-32B, prefix 20	OLMo-3-32B, prefix 5	9.7 / 9.3	480 / 521	1.04 [0.92, 1.18]

(continued)

Constraint	Numerator	Denominator	λ	slips	Ratio [95% CI]
alternating case	OLMo-3-32B, prefix 20	OLMo-3-32B, prefix 5	86.4 / 95.0	91 / 32	0.91 [0.52, 1.44]
lowercase	OLMo-3-7B, prefix 20	OLMo-3-7B, prefix 5	12.5 / 45.7	133 / 65	0.27 [0.10, 0.62]*
uppercase	OLMo-3-7B, prefix 20	OLMo-3-7B, prefix 5	45.3 / 49.4	163 / 78	0.92 [0.66, 1.25]
lowercase	Qwen3-32B, prefix 20	Qwen3-32B, prefix 5	1.4 / 1.2	310 / 234	1.11 [0.90, 1.35]P
uppercase	Qwen3-32B, prefix 20	Qwen3-32B, prefix 5	1.4 / 1.3	323 / 281	1.08 [0.90, 1.28]P
alternating case	Qwen3-32B, prefix 20	Qwen3-32B, prefix 5	26.1 / 31.7	265 / 185	0.82 [0.66, 1.02]P
lowercase	Qwen3-8B, prefix 20	Qwen3-8B, prefix 5	2.3 / 3.0	321 / 338	0.78 [0.63, 0.94]* P
uppercase	Qwen3-8B, prefix 20	Qwen3-8B, prefix 5	14.6 / 11.7	450 / 464	1.25 [1.09, 1.44]* P
alternating case	Qwen3-8B, prefix 20	Qwen3-8B, prefix 5	85.3 / 86.4	64 / 14	0.99 [0.39, 1.79]P
lowercase	gpt-oss-20b, prefix 20	gpt-oss-20b, prefix 5	61.8 / 173.7	33 / 29	0.36 [0.16, 0.87]*
uppercase	gpt-oss-20b, prefix 20	gpt-oss-20b, prefix 5	38.5 / 123.6	34 / 11	0.31 [0.10, 1.02]
lowercase	gpt-oss-120b, prefix 20	gpt-oss-120b, prefix 5	45.7 / 117.9	28 / 27	0.39 [0.11, 1.66]
K=20 vs K=1					
lowercase	OLMo-3-32B, prefix 20	OLMo-3-32B, prefix 1	2.7 / 4.6	365 / 76	0.59 [0.35, 0.92]*
uppercase	OLMo-3-32B, prefix 20	OLMo-3-32B, prefix 1	9.7 / 9.7	480 / 494	1.00 [0.88, 1.13]
lowercase	OLMo-3-7B, prefix 20	OLMo-3-7B, prefix 1	12.5 / 162.4	133 / 63	0.08 [0.04, 0.13]*
lowercase	Qwen3-32B, prefix 20	Qwen3-32B, prefix 1	1.4 / 1.6	310 / 278	0.84 [0.68, 1.04]P
uppercase	Qwen3-32B, prefix 20	Qwen3-32B, prefix 1	1.4 / 1.6	323 / 197	0.92 [0.76, 1.11]P
alternating case	Qwen3-32B, prefix 20	Qwen3-32B, prefix 1	26.1 / 22.1	265 / 156	1.18 [0.71, 1.97]P
lowercase	Qwen3-8B, prefix 20	Qwen3-8B, prefix 1	2.3 / 2.6	321 / 351	0.88 [0.72, 1.05]P
uppercase	Qwen3-8B, prefix 20	Qwen3-8B, prefix 1	14.6 / 5.2	450 / 22	2.83 [1.86, 4.33]* P
lowercase	gpt-oss-20b, prefix 20	gpt-oss-20b, prefix 1	61.8 / 111.9	33 / 45	0.55 [0.25, 1.39]
uppercase	gpt-oss-20b, prefix 20	gpt-oss-20b, prefix 1	38.5 / 20.7	34 / 54	1.86 [0.88, 4.66]
lowercase	gpt-oss-120b, prefix 20	gpt-oss-120b, prefix 1	45.7 / 130.6	28 / 44	0.35 [0.12, 1.47]
lowercase	Qwen3-14B, prefix 20	Qwen3-14B, prefix 1	2.8 / 2.7	352 / 252	1.02 [0.83, 1.25]
uppercase	Qwen3-14B, prefix 20	Qwen3-14B, prefix 1	5.4 / 3.4	404 / 173	1.59 [1.33, 1.89]*
alternating case	Qwen3-14B, prefix 20	Qwen3-14B, prefix 1	49.3 / 73.2	179 / 72	0.67 [0.48, 0.94]*
no-instr vs instructed					
lowercase	OLMo-3-32B, prefix 20, no instr.	OLMo-3-32B, prefix 20	10.9 / 2.7	141 / 365	3.98 [2.97, 5.56]*
lowercase	OLMo-3-32B, prefix 100, no instr.	OLMo-3-32B, prefix 100	6.6 / 2.5	436 / 455	2.66 [2.30, 3.11]*
uppercase	OLMo-3-32B, prefix 20, no instr.	OLMo-3-32B, prefix 20	42.4 / 9.7	245 / 480	4.37 [3.28, 5.65]*
uppercase	OLMo-3-32B, prefix 100, no instr.	OLMo-3-32B, prefix 100	19.3 / 10.5	273 / 432	1.84 [1.56, 2.16]*
uppercase	7B base, prefix 20, no instr.	7B base, prefix 20	1.4 / 1.3	162 / 186	1.01 [0.77, 1.35]
uppercase	7B SFT, prefix 20, no instr.	7B SFT, prefix 20	53.8 / 34.7	127 / 199	1.55 [1.22, 1.97]*
lowercase	OLMo-3-7B, prefix 20, no instr.	OLMo-3-7B, prefix 20	33.0 / 12.5	48 / 133	2.64 [1.38, 6.83]*
uppercase	OLMo-3-7B, prefix 20, no instr.	OLMo-3-7B, prefix 20	73.8 / 45.3	88 / 163	1.63 [1.27, 2.13]*
uppercase	OLMo-3-7B, prefix 100, no instr.	OLMo-3-7B, prefix 100	57.3 / 38.2	103 / 144	1.50 [1.11, 2.13]*
lowercase	Qwen3-32B, prefix 20, no instr.	Qwen3-32B, prefix 20	5.2 / 1.4	262 / 310	3.84 [3.06, 4.87]*
lowercase	Qwen3-32B, prefix 100, no instr.	Qwen3-32B, prefix 100	2.2 / 0.7	428 / 283	3.29 [2.75, 3.93]*
uppercase	Qwen3-32B, prefix 20, no instr.	Qwen3-32B, prefix 20	3.1 / 1.4	345 / 323	2.15 [1.80, 2.66]*
uppercase	Qwen3-32B, prefix 100, no instr.	Qwen3-32B, prefix 100	2.1 / 1.2	376 / 300	1.72 [1.49, 1.99]*
lowercase	Qwen3-8B, prefix 20, no instr.	Qwen3-8B, prefix 20	17.7 / 2.3	130 / 321	7.62 [5.80, 10.38]*
lowercase	Qwen3-8B, prefix 100, no instr.	Qwen3-8B, prefix 100	8.1 / 2.0	432 / 428	4.06 [3.36, 4.89]*
uppercase	Qwen3-8B, prefix 20, no instr.	Qwen3-8B, prefix 20	46.4 / 14.6	266 / 450	3.18 [2.65, 3.86]*
uppercase	Qwen3-8B, prefix 100, no instr.	Qwen3-8B, prefix 100	27.2 / 12.7	268 / 384	2.14 [1.81, 2.56]*
uppercase	7B RL-Zero-Math, prefix 20, no instr.	7B RL-Zero-Math, prefix 20	1.8 / 1.2	285 / 269	1.48 [1.16, 1.90]*
uppercase	7B RL-Zero-Code, prefix 20, no instr.	7B RL-Zero-Code, prefix 20	4.2 / 2.9	289 / 294	1.44 [1.11, 1.89]*
lowercase	gpt-oss-20b, prefix 20, no instr.	gpt-oss-20b, prefix 20	103.3 / 61.8	25 / 33	1.67 [0.70, 3.84]
uppercase	gpt-oss-20b, prefix 20, no instr.	gpt-oss-20b, prefix 20	49.5 / 38.5	25 / 34	1.29 [0.92, 1.74]
uppercase	7B RL-Zero-General, prefix 20, no instr.	7B RL-Zero-General, prefix 20	7.4 / 6.1	190 / 226	1.20 [0.77, 1.88]
lowercase	gpt-oss-120b, prefix 20, no instr.	gpt-oss-120b, prefix 20	34.9 / 45.7	17 / 28	0.76 [0.48, 3.70]
uppercase	gpt-oss-120b, prefix 20, no instr.	gpt-oss-120b, prefix 20	37.6 / 87.7	23 / 32	0.43 [0.16, 1.89]
lowercase	Qwen3-14B, prefix 20, no instr.	Qwen3-14B, prefix 20	12.7 / 2.8	150 / 352	4.63 [3.39, 6.44]*
uppercase	Qwen3-14B, prefix 20, no instr.	Qwen3-14B, prefix 20	35.2 / 5.4	283 / 404	6.48 [5.05, 8.35]*
lowercase	Qwen3-4B, prefix 20, no instr.	Qwen3-4B, prefix 20	69.2 / 13.5	27 / 62	5.12 [2.33, 26.54]*
uppercase	Qwen3-4B, prefix 20, no instr.	Qwen3-4B, prefix 20	94.0 / 75.0	47 / 56	1.25 [0.88, 1.90]
prefix vs plain					
lowercase	7B DPO, prefix 20	7B DPO, plain	12.7 / 164.2	66 / 11	0.08 [0.03, 0.15]*
lowercase	OLMo-3-7B, prefix 20	OLMo-3-7B, plain	12.5 / 221.1	133 / 42	0.06 [0.03, 0.09]*
lowercase	OLMo-3-7B, prefix 100	OLMo-3-7B, plain	9.2 / 221.1	390 / 42	0.04 [0.03, 0.06]*
lowercase	Qwen3-32B, prefix 20	Qwen3-32B, plain	1.4 / 1.6	310 / 115	0.85 [0.59, 1.19]
lowercase	Qwen3-32B, prefix 100	Qwen3-32B, plain	0.7 / 1.6	283 / 115	0.43 [0.30, 0.60]*
lowercase	Qwen3-8B, prefix 20	Qwen3-8B, plain	2.3 / 1.8	321 / 139	1.30 [0.95, 1.74]
lowercase	Qwen3-8B, prefix 100	Qwen3-8B, plain	2.0 / 1.8	428 / 139	1.12 [0.83, 1.49]
lowercase	OLMo-3-7B, 12k tokens, prefix 20	OLMo-3-7B, 12k tokens, plain	10.1 / 225.3	136 / 41	0.04 [0.03, 0.07]*
lowercase	gpt-oss-120b, prefix 20	gpt-oss-120b, plain	45.7 / 220.3	28 / 39	0.21 [0.07, 0.95]*
lowercase	gpt-oss-120b, prefix 100	gpt-oss-120b, plain	65.6 / 220.3	56 / 39	0.30 [0.15, 0.61]*
uppercase	gpt-oss-120b, prefix 20	gpt-oss-120b, plain	87.7 / 40.1	32 / 13	2.19 [1.04, 4.80]*
uppercase	gpt-oss-120b, prefix 100	gpt-oss-120b, plain	47.4 / 40.1	19 / 13	1.18 [0.41, 5.01]
alternating case	gpt-oss-120b, prefix 20	gpt-oss-120b, plain	128.7 / 122.2	22 / 11	1.05 [0.52, 2.60]
alternating case	gpt-oss-120b, prefix 100	gpt-oss-120b, plain	37.2 / 122.2	11 / 11	0.30 [0.10, 4.17]
lowercase	gpt-oss-20b, low effort, prefix 20	gpt-oss-20b, low effort, plain	83.3 / 69.6	53 / 11	1.20 [0.37, 2.67]
lowercase	gpt-oss-120b, low effort, prefix 20	gpt-oss-120b, low effort, plain	83.1 / 85.0	34 / 86	0.98 [0.67, 1.70]
scale Qwen3 8B/32B					
uppercase	Qwen3-8B, prefix 20	Qwen3-32B, prefix 20	14.6 / 1.4	450 / 323	10.19 [8.36, 12.63]*
lowercase	Qwen3-8B, prefix 20	Qwen3-32B, prefix 20	2.3 / 1.4	321 / 310	1.71 [1.37, 2.13]*
scale OLMo 7B/32B					
uppercase	OLMo-3-7B, prefix 20	OLMo-3-32B, prefix 20	45.3 / 9.7	163 / 480	4.67 [3.69, 6.00]*

(continued)

Constraint	Numerator	Denominator	λ	slips	Ratio [95% CI]
lowercase	OLMo-3-7B, prefix 20	OLMo-3-32B, prefix 20	12.5 / 2.7	133 / 365	4.58 [3.42, 6.71]*
stage SFT/base					
uppercase	7B SFT, prefix 20	7B base, prefix 20	34.7 / 1.3	199 / 186	26.01 [18.57, 36.33]*
lowercase	7B SFT, prefix 20	7B base, prefix 20	11.5 / 5.2	143 / 221	2.20 [1.59, 3.05]*
stage final/SFT					
uppercase	OLMo-3-7B, prefix 20	7B SFT, prefix 20	45.3 / 34.7	163 / 199	1.30 [0.99, 1.69]
lowercase	OLMo-3-7B, prefix 20	7B SFT, prefix 20	12.5 / 11.5	133 / 143	1.09 [0.74, 1.67]
external vs reasoning					
word suppression	Qwen3-8B, external CoT	Qwen3-8B, plain	6.3 / 5.5	224 / 669	1.14 [0.73, 1.64]
lowercase	Qwen3-8B, external CoT	Qwen3-8B, plain	0.6 / 1.8	41 / 139	0.36 [0.19, 0.63]*
word suppression	Qwen3-32B, external CoT	Qwen3-32B, plain	1.6 / 3.2	131 / 456	0.49 [0.36, 0.63]*
lowercase	Qwen3-32B, external CoT	Qwen3-32B, plain	0.4 / 1.6	40 / 115	0.24 [0.14, 0.40]*
scale Qwen3 8B/32B plain					
word suppression	Qwen3-8B, plain	Qwen3-32B, plain	5.5 / 3.2	669 / 456	1.71 [1.29, 2.32]*
scale OLMo 7B/32B plain					
word suppression	OLMo-3-7B, plain	OLMo-3-32B, plain	6.2 / 6.7	440 / 444	0.92 [0.70, 1.22]

Table 10: Dose–response of the compliant prefix, no-instruction controls and prompt-only arms, **uppercase** (95% question-clustered bootstrap intervals on π, $h_{20\text{–}100}$ and the binary score). "First word ok": share of continuations whose first graded word complies. $h_{20\text{–}100}$: first-slip hazard per 1,000 words over words 20–100, printed when $\geq$ 10 traces enter the window and $\geq$ 10 slips occur in it. †4,096-token budget.

Model	Prefix words K	first word ok	π $(w = 20)$	$h_{20\text{–}100}$	C_{100}	binary (%)	acc.
Qwen3-4B	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	43
	1	0.04	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	43
	20	0.89	0.09 [0.06, 0.12]	75.0 [56.2, 108.5]	0.00	0.0 [0.0, 0.0]	44
	100	0.87	0.12 [0.09, 0.15]	50.4 [38.5, 67.3]	0.00	0.0 [0.0, 0.0]	43
	20, no instr.	0.89	0.08 [0.05, 0.11]	94.0 [68.0, 141.6]	0.00	0.2 [0.0, 0.5]	42
	prompt: opener hint	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	42
Qwen3-8B	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	42
	1	0.13	0.05 [0.03, 0.07]	–	0.04	1.0 [0.2, 2.0]	43
	5	0.97	0.81 [0.77, 0.85]	13.5 [11.7, 15.6]	0.27	3.8 [2.1, 5.7]	42
	20	0.98	0.77 [0.72, 0.81]	18.5 [16.2, 21.2]	0.17	2.0 [0.8, 3.4]	38
	100	0.96	0.67 [0.63, 0.72]	15.8 [13.6, 18.2]	0.20	3.3 [1.8, 5.0]	39
	20, no instr.	0.95	0.44 [0.39, 0.49]	47.4 [40.2, 56.8]	0.02	0.0 [0.0, 0.0]	33
	100, no instr.	0.93	0.45 [0.40, 0.50]	32.0 [26.8, 38.9]	0.06	0.2 [0.0, 0.5]	29
	prompt: opener hint	0.21	0.07 [0.05, 0.10]	–	0.06	4.5 [2.6, 6.6]	43
	prompt: demo	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	44
Qwen3-14B	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	50
	1	0.68	0.47 [0.41, 0.52]	4.8 [3.7, 6.1]	0.32	17.8 [14.2, 22.0]	48
	20	0.98	0.81 [0.78, 0.85]	7.9 [6.6, 9.4]	0.44	14.2 [10.9, 17.7]	49
	100	0.98	0.87 [0.84, 0.90]	7.3 [6.1, 8.6]	0.49	18.8 [15.1, 22.8]	51
	20, no instr.	0.96	0.48 [0.43, 0.53]	42.4 [34.3, 52.2]	0.04	0.8 [0.2, 1.9]	46
	prompt: opener hint	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	49
	prompt: demo	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	50
Qwen3-32B	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	50
	1	0.75	0.59 [0.54, 0.64]	3.1 [2.3, 4.0]	0.46	26.0 [22.0, 30.0]	50
	5	0.87	0.81 [0.77, 0.85]	3.7 [2.9, 4.5]	0.61	34.2 [29.6, 39.4]	49
	20	0.99	0.92 [0.89, 0.95]	3.6 [2.9, 4.4]	0.69	38.0 [33.1, 42.9]	49
	100	1.00	0.95 [0.93, 0.97]	2.7 [2.1, 3.4]	0.77	45.2 [40.5, 50.2]	48
	20, no instr.	0.97	0.74 [0.70, 0.78]	8.4 [6.9, 10.0]	0.40	16.5 [12.8, 20.3]	36
	100, no instr.	0.99	0.91 [0.88, 0.93]	4.1 [3.4, 4.9]	0.65	27.8 [23.7, 32.3]	39
	prompt: opener hint	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	50
	prompt: demo	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	49
OLMo-3-7B†	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	18
	1	0.09	0.01 [0.00, 0.02]	–	0.00	0.0 [0.0, 0.0]	16
	5	0.36	0.13 [0.09, 0.17]	49.2 [37.7, 64.5]	0.00	0.0 [0.0, 0.0]	17
	20	0.84	0.27 [0.24, 0.32]	46.5 [37.7, 56.6]	0.01	0.0 [0.0, 0.0]	17
	100	0.80	0.24 [0.20, 0.28]	40.9 [32.9, 51.3]	0.01	0.2 [0.0, 0.5]	16
	20, no instr.	0.77	0.15 [0.11, 0.19]	73.8 [60.6, 93.7]	0.00	0.0 [0.0, 0.0]	14
	100, no instr.	0.74	0.17 [0.14, 0.21]	58.3 [46.4, 75.9]	0.00	0.0 [0.0, 0.0]	13
	prompt: opener hint	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	20
OLMo-3-32B†	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	28
	1	0.98	0.85 [0.82, 0.88]	10.6 [9.4, 12.0]	0.36	2.8 [1.5, 4.4]	27
	5	0.99	0.89 [0.85, 0.92]	9.1 [7.8, 10.4]	0.43	1.7 [0.7, 2.7]	27
	20	0.97	0.82 [0.78, 0.86]	10.2 [8.8, 11.8]	0.36	2.0 [0.8, 3.3]	28
	100	0.96	0.74 [0.70, 0.78]	11.2 [9.7, 12.7]	0.30	1.8 [0.7, 3.0]	28
	20, no instr.	0.94	0.41 [0.36, 0.46]	48.1 [40.0, 57.2]	0.02	0.0 [0.0, 0.0]	25
	100, no instr.	0.90	0.46 [0.41, 0.50]	20.9 [17.6, 24.8]	0.10	0.2 [0.0, 0.5]	23

(continued)

Model	Prefix words K	first word ok	π ($w = 20$)	$h_{20\text{–}100}$	C_{100}	binary (%)	acc.
	prompt: opener hint	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	26
OLMo-3-7B base	0 (plain)	0.14	0.00 [0.00, 0.01]	–	0.00	0.3 [0.0, 0.9]	20
	20	0.98	0.75 [0.71, 0.80]	5.5 [4.6, 6.8]	0.49	36.9 [31.9, 41.6]	16
	20, no instr.	0.99	0.72 [0.67, 0.77]	5.4 [4.3, 6.7]	0.48	38.1 [32.7, 43.2]	16
OLMo-3-7B SFT†	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	25
	20	0.88	0.33 [0.29, 0.38]	35.9 [30.0, 44.0]	0.02	0.0 [0.0, 0.0]	25
	20, no instr.	0.85	0.21 [0.17, 0.25]	53.3 [43.7, 68.8]	0.01	0.2 [0.0, 0.5]	19
OLMo-3-7B DPO†	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	21
	20	0.84	0.28 [0.23, 0.33]	42.5 [35.4, 51.4]	0.01	0.0 [0.0, 0.0]	21
OLMo-3-7B RL-Zero-Math	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	13
	20	0.98	0.84 [0.81, 0.88]	3.8 [3.0, 4.5]	0.63	39.5 [35.1, 44.0]	14
	20, no instr.	0.97	0.74 [0.70, 0.79]	5.7 [4.8, 6.8]	0.48	27.0 [23.0, 31.2]	16
OLMo-3-7B RL-Zero-Code	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	17
	20	0.98	0.85 [0.82, 0.88]	5.4 [4.5, 6.3]	0.55	36.0 [31.8, 40.6]	27
	20, no instr.	0.98	0.73 [0.69, 0.77]	7.2 [6.0, 8.6]	0.41	24.5 [20.6, 28.5]	26
OLMo-3-7B RL-Zero-General	0 (plain)	0.05	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	26
	20	0.94	0.49 [0.44, 0.54]	16.3 [13.6, 19.7]	0.17	11.5 [8.9, 14.2]	22
	20, no instr.	0.93	0.39 [0.34, 0.44]	20.0 [16.1, 24.9]	0.11	7.5 [5.2, 10.2]	25
gpt-oss-20b	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	49
	1	0.53	0.11 [0.09, 0.14]	23.8 [16.9, 34.7]	0.03	2.5 [1.2, 4.0]	48
	5	0.79	0.02 [0.01, 0.03]	123.6 [71.7, 282.5]	0.00	0.0 [0.0, 0.0]	48
	20	0.80	0.06 [0.03, 0.08]	50.2 [27.7, 89.8]	0.00	0.0 [0.0, 0.0]	51
	100	0.76	0.05 [0.03, 0.07]	40.6 [17.6, 119.8]	0.01	0.3 [0.0, 1.0]	50
	20, no instr.	0.72	0.04 [0.02, 0.06]	62.8 [38.9, 119.1]	0.00	0.0 [0.0, 0.0]	52
	prompt: opener hint	1.00	0.00 [0.00, 0.01]	–	0.00	0.2 [0.0, 0.5]	49
	prompt: demo	0.11	0.11 [0.08, 0.13]	99.7 [72.0, 123.7]	0.00	0.2 [0.0, 0.6]	52
gpt-oss-120b	0 (plain)	0.50	0.03 [0.02, 0.05]	40.1 [21.9, 71.7]	0.00	1.0 [0.2, 2.0]	54
	1	0.66	0.01 [0.00, 0.02]	–	0.00	0.3 [0.0, 1.0]	55
	5	0.84	0.01 [0.00, 0.02]	–	0.00	0.0 [0.0, 0.0]	55
	20	0.72	0.06 [0.03, 0.08]	87.7 [58.2, 149.3]	0.00	0.2 [0.0, 0.5]	55
	100	0.66	0.03 [0.02, 0.05]	54.0 [20.6, 158.6]	0.00	0.2 [0.0, 0.5]	56
	20, no instr.	0.62	0.04 [0.02, 0.06]	57.4 [22.2, 203.5]	0.00	0.0 [0.0, 0.0]	54
	prompt: opener hint	0.98	0.39 [0.34, 0.43]	46.6 [39.2, 55.3]	0.02	2.8 [1.3, 4.6]	52
	prompt: demo	1.00	0.98 [0.96, 0.99]	26.5 [23.8, 29.5]	0.11	4.3 [2.6, 6.5]	54
OLMo-3-7B, 12k tokens	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	34
	20	0.85	0.27 [0.23, 0.32]	47.7 [38.8, 59.2]	0.01	0.0 [0.0, 0.0]	33
Qwen3-8B, subset B	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	48

Table 11: As Table 10, **lowercase**.

Model	Prefix words K	first word ok	π ($w = 20$)	$h_{20\text{–}100}$	C_{100}	binary (%)	acc.
Qwen3-4B	0 (plain)	0.19	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	42
	1	0.99	0.01 [0.00, 0.02]	–	0.00	0.0 [0.0, 0.0]	41
	20	0.93	0.10 [0.07, 0.14]	17.0 [10.1, 28.3]	0.04	0.2 [0.0, 0.5]	41
	100	0.99	0.74 [0.69, 0.78]	11.9 [10.3, 13.9]	0.29	2.3 [1.0, 3.9]	40
	20, no instr.	0.91	0.04 [0.03, 0.07]	83.9 [37.5, 365.4]	0.00	0.0 [0.0, 0.0]	41
	prompt: opener hint	0.11	0.03 [0.01, 0.05]	–	0.03	1.3 [0.3, 2.6]	44
Qwen3-8B	0 (plain)	0.12	0.09 [0.07, 0.12]	3.1 [1.6, 5.1]	0.07	2.8 [1.7, 4.1]	43
	1	1.00	0.73 [0.68, 0.78]	7.1 [5.7, 8.7]	0.43	14.3 [11.0, 18.2]	43
	5	1.00	0.69 [0.64, 0.74]	8.5 [6.8, 10.3]	0.38	12.5 [9.8, 15.8]	42
	20	0.98	0.66 [0.62, 0.71]	5.2 [3.9, 6.2]	0.45	12.8 [9.6, 16.1]	41
	100	0.99	0.92 [0.89, 0.95]	2.9 [2.3, 3.6]	0.73	20.5 [16.5, 24.8]	42
	20, no instr.	0.94	0.22 [0.18, 0.26]	21.6 [16.7, 28.0]	0.04	0.0 [0.0, 0.0]	32
	100, no instr.	0.98	0.74 [0.69, 0.78]	11.5 [9.7, 13.3]	0.30	1.7 [0.6, 3.2]	29
	prompt: opener hint	0.80	0.68 [0.64, 0.73]	3.5 [2.7, 4.4]	0.52	29.0 [24.6, 33.5]	44
	prompt: demo	0.44	0.43 [0.38, 0.48]	3.2 [2.2, 4.3]	0.33	19.8 [16.3, 23.9]	43
Qwen3-14B	0 (plain)	0.02	0.01 [0.00, 0.01]	–	0.00	0.2 [0.0, 0.6]	50
	1	1.00	0.56 [0.51, 0.61]	5.6 [4.4, 6.9]	0.36	13.7 [10.6, 17.2]	48
	20	0.97	0.74 [0.69, 0.78]	6.2 [5.0, 7.4]	0.46	15.0 [11.7, 18.5]	50
	100	0.99	0.91 [0.89, 0.94]	2.8 [2.2, 3.5]	0.73	25.5 [21.2, 30.1]	48
	20, no instr.	0.93	0.26 [0.22, 0.30]	17.2 [13.4, 22.0]	0.08	0.7 [0.0, 1.5]	49
	prompt: opener hint	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	48
	prompt: demo	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	50
Qwen3-32B	0 (plain)	0.15	0.11 [0.09, 0.13]	5.4 [3.5, 7.9]	0.07	4.2 [2.9, 5.4]	50
	1	1.00	0.73 [0.69, 0.77]	6.0 [4.8, 7.2]	0.47	26.5 [22.7, 30.9]	52

(continued)

Model	Prefix words K	first word ok	π ($w = 20$)	$h_{20\text{–}100}$	C_{100}	binary (%)	acc.
	5	0.99	0.69 [0.64, 0.73]	4.0 [3.1, 4.9]	0.50	29.5 [25.2, 33.6]	51
	20	0.99	0.84 [0.80, 0.88]	3.3 [2.6, 4.1]	0.66	32.5 [28.1, 37.2]	49
	100	1.00	0.96 [0.94, 0.98]	1.4 [1.0, 1.8]	0.86	49.2 [44.4, 53.9]	50
	20, no instr.	0.96	0.47 [0.42, 0.53]	11.0 [8.9, 13.3]	0.21	3.8 [2.1, 5.8]	37
	100, no instr.	0.99	0.87 [0.84, 0.91]	4.1 [3.3, 5.0]	0.63	15.8 [12.4, 19.4]	38
	prompt: opener hint	0.00	0.00 [0.00, 0.01]	–	0.00	0.3 [0.0, 0.8]	50
	prompt: demo	0.14	0.13 [0.10, 0.16]	1.7 [0.7, 3.0]	0.12	8.5 [6.2, 11.1]	48
OLMo-3-7B†	0 (plain)	0.75	0.07 [0.05, 0.10]	221.1 [166.1, 322.0]	0.00	0.0 [0.0, 0.0]	18
	1	0.99	0.11 [0.08, 0.14]	166.7 [105.5, 274.9]	0.00	0.2 [0.0, 0.5]	18
	5	0.95	0.11 [0.08, 0.14]	70.6 [36.6, 147.8]	0.01	0.0 [0.0, 0.0]	17
	20	0.92	0.22 [0.18, 0.27]	20.1 [14.9, 27.3]	0.06	0.2 [0.0, 0.5]	18
	100	0.96	0.65 [0.60, 0.70]	11.3 [9.6, 13.2]	0.28	0.3 [0.0, 0.9]	18
	20, no instr.	0.89	0.08 [0.05, 0.11]	54.5 [38.2, 87.2]	0.01	0.0 [0.0, 0.0]	15
	prompt: opener hint	0.01	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	17
OLMo-3-32B†	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	22
	1	0.96	0.14 [0.11, 0.18]	10.7 [6.8, 16.6]	0.07	1.7 [0.6, 2.9]	25
	5	0.91	0.40 [0.35, 0.45]	6.6 [5.0, 8.5]	0.24	5.3 [3.2, 7.7]	26
	20	0.97	0.72 [0.67, 0.76]	4.0 [3.1, 5.0]	0.52	10.8 [7.9, 14.1]	27
	100	0.99	0.92 [0.89, 0.94]	3.6 [2.9, 4.3]	0.68	15.8 [12.4, 19.6]	25
	20, no instr.	0.93	0.23 [0.20, 0.28]	17.2 [12.9, 23.2]	0.07	0.0 [0.0, 0.0]	24
	100, no instr.	0.97	0.74 [0.69, 0.78]	9.0 [7.7, 10.6]	0.37	1.0 [0.3, 1.9]	25
	prompt: opener hint	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	26
OLMo-3-7B base	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	17
	20	0.97	0.62 [0.57, 0.67]	9.0 [7.4, 10.9]	0.31	17.7 [13.8, 21.3]	20
OLMo-3-7B SFT†	0 (plain)	0.01	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	26
	20	0.93	0.25 [0.21, 0.29]	18.5 [14.5, 24.1]	0.07	0.8 [0.2, 1.6]	24
OLMo-3-7B DPO†	0 (plain)	0.22	0.02 [0.01, 0.03]	164.2 [121.9, 273.3]	0.00	0.0 [0.0, 0.0]	22
	20	0.88	0.11 [0.08, 0.14]	18.7 [13.1, 28.7]	0.03	0.0 [0.0, 0.0]	22
OLMo-3-7B RL-Zero-Math	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	11
	20	0.98	0.68 [0.63, 0.72]	7.3 [6.1, 8.8]	0.39	9.8 [7.4, 12.6]	16
OLMo-3-7B RL-Zero-Code	0 (plain)	0.00	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	18
	20	0.97	0.65 [0.60, 0.69]	7.9 [6.5, 9.4]	0.35	10.5 [7.8, 13.5]	24
OLMo-3-7B RL-Zero-General	0 (plain)	0.01	0.00 [0.00, 0.00]	–	0.00	0.0 [0.0, 0.0]	25
	20	0.93	0.47 [0.43, 0.52]	16.5 [13.7, 20.2]	0.15	6.5 [4.4, 8.8]	24
gpt-oss-20b	0 (plain)	0.01	0.00 [0.00, 0.01]	–	0.00	0.0 [0.0, 0.0]	50
	1	0.99	0.07 [0.05, 0.10]	111.9 [78.5, 168.8]	0.00	0.0 [0.0, 0.0]	48
	5	0.88	0.05 [0.03, 0.07]	173.7 [119.4, 294.9]	0.00	0.0 [0.0, 0.0]	50
	20	0.89	0.06 [0.03, 0.08]	77.9 [47.3, 146.7]	0.00	0.0 [0.0, 0.0]	50
	100	0.85	0.08 [0.05, 0.11]	37.4 [21.2, 77.4]	0.01	0.2 [0.0, 0.5]	49
	20, no instr.	0.88	0.04 [0.02, 0.06]	103.3 [71.6, 197.5]	0.00	0.0 [0.0, 0.0]	48
	prompt: opener hint	1.00	0.14 [0.11, 0.17]	72.3 [57.4, 93.4]	0.00	0.0 [0.0, 0.0]	50
	prompt: demo	0.38	0.34 [0.29, 0.39]	71.3 [62.5, 81.7]	0.00	0.0 [0.0, 0.0]	50
gpt-oss-120b	0 (plain)	0.73	0.06 [0.04, 0.09]	220.3 [147.8, 375.0]	0.00	0.0 [0.0, 0.0]	55
	1	1.00	0.07 [0.05, 0.10]	130.6 [89.1, 244.4]	0.00	0.0 [0.0, 0.0]	54
	5	0.89	0.04 [0.03, 0.07]	117.9 [70.3, 269.9]	0.00	0.0 [0.0, 0.0]	53
	20	0.88	0.05 [0.03, 0.07]	70.8 [31.4, 181.9]	0.00	0.0 [0.0, 0.0]	54
	100	0.83	0.10 [0.07, 0.13]	70.3 [41.6, 121.2]	0.00	0.3 [0.0, 0.9]	53
	20, no instr.	0.85	0.03 [0.01, 0.05]	63.6 [18.1, 458.3]	0.00	0.0 [0.0, 0.0]	56
	prompt: opener hint	0.99	0.20 [0.16, 0.24]	70.3 [55.2, 93.6]	0.00	0.2 [0.0, 0.5]	54
	prompt: demo	0.99	0.48 [0.43, 0.53]	27.5 [24.2, 31.9]	0.04	1.0 [0.3, 1.9]	53
OLMo-3-7B, 12k tokens	0 (plain)	0.75	0.07 [0.05, 0.10]	225.3 [164.2, 335.7]	0.00	0.0 [0.0, 0.0]	34
	20	0.92	0.23 [0.19, 0.27]	20.4 [15.5, 27.1]	0.06	0.0 [0.0, 0.0]	36
Qwen3-8B, subset B	0 (plain)	0.13	0.10 [0.08, 0.13]	9.6 [5.9, 15.5]	0.05	2.5 [1.2, 4.2]	49

Table 12: Reasoning effort as exposure: gpt-oss at three effort levels, same 300 questions (95% question-clustered bootstrap intervals). Columns: median words; share of traces truncated at the token budget (%); share whose first graded word complies; π at $w = 20$; hazards per 1,000 words on words 20–100 and 100–300 ("–": fewer than 10 traces at risk or 10 slips in the window, which is every case-constraint row because no trace is at risk); C_{100}; binary score (%); accuracy (%). [c]Opening/closing string: two checkpoints, no slip process, so no hazard or C_{100} (its binary score falls with length because the closing checkpoint sits at the end of the trace).

Model	Constraint	Effort	words	trunc. (%)	1st ok	π (w=20)	$h_{20\text{–}100}$	$h_{100\text{–}300}$	C_{100}	binary (%)	acc. (%)
gpt-oss-20b	Uppercase	low	82	0	0.01	0.00 [0.00,0.00]	–	–	0.00	0.0	49
		medium	384	4	0.00	0.00 [0.00,0.00]	–	–	0.00	0.0	49

(continued)

Model	Constraint	Effort	words	trunc. (%)	1st ok	π (w=20)	$h_{20\text{–}100}$	$h_{100\text{–}300}$	C_{100}	binary (%)	acc. (%)
		high	1847	22	0.00	0.00 [0.00,0.00]	–	–	0.00	0.0	47
gpt-oss-20b	Lowercase	low	79	0	0.08	0.03 [0.01,0.04]	69.6 [31.8,225.9]	–	0.00	0.7	47
		medium	386	3	0.01	0.00 [0.00,0.01]	–	–	0.00	0.0	50
		high	1870	22	0.00	0.00 [0.00,0.00]	–	–	0.00	0.0	45
gpt-oss-20b	Suppress keyword	low	76	0	1.00	0.58 [0.53,0.63]	12.3 [10.0,15.3]	3.0 [1.6,5.0]	0.25	29.5	46
		medium	396	2	1.00	0.64 [0.59,0.69]	16.2 [13.8,19.3]	6.7 [4.9,8.9]	0.19	3.5	50
		high	1806	20	1.00	0.70 [0.65,0.75]	18.8 [16.2,22.0]	5.2 [3.9,7.0]	0.17	0.3	46
gpt-oss-20b	Open/close string[e]	low	69	1	1.00	0.99 [0.98,1.00]	–	–	–	13.7	42
		medium	343	3	1.00	1.00 [0.99,1.00]	–	–	–	1.8	50
		high	1698	24	0.98	0.98 [0.97,1.00]	–	–	–	0.2	44
gpt-oss-120b	Uppercase	low	52	0	0.94	0.25 [0.21,0.29]	54.8 [33.2,87.6]	–	0.04	18.5	48
		medium	264	0	0.50	0.03 [0.02,0.05]	40.1 [21.7,71.7]	–	0.00	1.0	54
		high	1456	12	0.01	0.00 [0.00,0.00]	–	–	0.00	0.0	52
gpt-oss-120b	Lowercase	low	61	0	0.98	0.16 [0.12,0.20]	85.0 [66.0,111.6]	–	0.00	1.5	50
		medium	248	0	0.73	0.06 [0.04,0.09]	220.3 [147.8,375.0]	–	0.00	0.0	55
		high	1364	13	0.00	0.00 [0.00,0.00]	–	–	0.00	0.0	55
gpt-oss-120b	Suppress keyword	low	82	0	1.00	0.70 [0.65,0.75]	8.8 [7.0,10.8]	2.1 [1.3,3.4]	0.37	43.0	49
		medium	272	0	1.00	0.69 [0.65,0.74]	11.8 [10.0,13.9]	3.7 [2.7,5.0]	0.28	13.2	53
		high	1200	12	1.00	0.72 [0.67,0.77]	17.1 [14.9,19.7]	5.2 [4.0,7.0]	0.20	1.2	54
gpt-oss-120b	Open/close string[e]	low	77	0	1.00	0.96 [0.94,0.98]	–	–	–	17.7	50
		medium	284	0	0.99	0.99 [0.98,1.00]	–	–	–	7.7	54
		high	1264	12	0.79	0.79 [0.74,0.83]	–	–	–	0.3	55

Table 13: Paired effort contrasts (shared question-clustered bootstrap draws): differences in first-word onset and in π ($w = 20$) and ratios of common-window hazards between the higher effort level and low effort. *: interval excludes 0 (differences) or 1 (ratios); unadjusted. "–": fewer than 10 slips in the window in either arm. These contrasts score the pre-registered E15 prediction (App. Table 2).

Model	Constraint	Contrast	Δ first-word onset	Δπ (w=20)	$h_{20\text{–}100}$ ratio	$h_{100\text{–}300}$ ratio
gpt-oss-20b	suppress keyword	medium/low	+0.00 [+0.00, +0.00]	+0.06 [+0.01, +0.11]*	1.32 [1.06, 1.66]*	2.19 [1.29, 4.08]*
		high/low	+0.00 [+0.00, +0.00]	+0.12 [+0.06, +0.18]*	1.53 [1.20, 1.97]*	1.71 [0.91, 3.65]
gpt-oss-20b	suppress several	medium/low	+0.00 [+0.00, +0.00]	+0.03 [-0.02, +0.08]	1.47 [1.11, 1.96]*	–
		high/low	+0.00 [+0.00, +0.00]	+0.13 [+0.07, +0.19]*	1.53 [1.11, 2.14]*	–
gpt-oss-20b	uppercase	medium/low	-0.01 [-0.01, +0.00]	+0.00 [+0.00, +0.00]	–	–
		high/low	-0.01 [-0.01, +0.00]	+0.00 [+0.00, +0.00]	–	–
gpt-oss-20b	lowercase	medium/low	-0.07 [-0.10, -0.05]*	-0.02 [-0.04, -0.01]*	–	–
		high/low	-0.08 [-0.11, -0.06]*	-0.03 [-0.04, -0.01]*	–	–
gpt-oss-120b	suppress keyword	medium/low	+0.00 [+0.00, +0.00]	-0.01 [-0.06, +0.04]	1.34 [1.08, 1.66]*	1.76 [1.10, 2.87]*
		high/low	+0.00 [+0.00, +0.00]	+0.02 [-0.04, +0.08]	1.95 [1.53, 2.46]*	2.45 [1.50, 4.24]*
gpt-oss-120b	suppress several	medium/low	+0.00 [+0.00, +0.00]	-0.03 [-0.08, +0.03]	1.55 [1.18, 2.11]*	1.02 [0.54, 2.02]
		high/low	+0.00 [+0.00, +0.00]	+0.03 [-0.03, +0.09]	2.10 [1.54, 2.95]*	1.87 [0.88, 4.69]
gpt-oss-120b	uppercase	medium/low	-0.43 [-0.49, -0.38]*	-0.22 [-0.26, -0.17]*	0.73 [0.33, 1.56]	–
		high/low	-0.93 [-0.95, -0.90]*	-0.25 [-0.29, -0.21]*	–	–
gpt-oss-120b	lowercase	medium/low	-0.26 [-0.30, -0.21]*	-0.09 [-0.13, -0.06]*	2.59 [1.61, 4.58]*	–
		high/low	-0.98 [-0.99, -0.97]*	-0.16 [-0.20, -0.12]*	–	–

Replication. Every arm that carries a headline number—the 20-word prefix at every size and family, the one-token prefix at Qwen3-32B, OLMo-3-32B and gpt-oss-20b, and the prompt hint at Qwen3-8B and gpt-oss-20b—was rerun with a second sampling seed (Table 14); the two runs agree within 2.5 pp of full-trace compliance and within the bootstrap intervals of π and the common-window hazard in every cell.

Table 14: Seed-0 / seed-1 pairs for the replicated arms (same 300 questions, $n = 2$ each).

Model	Style	Arm	π	$h_{20\text{–}100}$	C_{100}	binary (%)
OLMo-3-32B	lowercase	prefix 1	0.14 / 0.14	10.7 / 11.3	0.07 / 0.07	1.7 / 1.5
OLMo-3-32B	lowercase	prefix 20	0.72 / 0.71	4.0 / 4.3	0.52 / 0.51	10.8 / 11.7
OLMo-3-32B	uppercase	prefix 1	0.85 / 0.85	10.6 / 9.8	0.36 / 0.39	2.8 / 2.8
OLMo-3-32B	uppercase	prefix 20	0.82 / 0.82	10.2 / 10.5	0.36 / 0.36	2.0 / 1.7
OLMo-3-7B	lowercase	prefix 1	0.11 / 0.10	166.7 / 205.6	0.00 / 0.00	0.2 / 0.0
OLMo-3-7B	lowercase	prefix 20	0.22 / 0.20	20.1 / 19.3	0.06 / 0.06	0.2 / 0.3
OLMo-3-7B	uppercase	prefix 1	0.01 / 0.01	–	0.00 / 0.00	0.0 / 0.0
OLMo-3-7B	uppercase	prefix 20	0.27 / 0.25	46.5 / 44.1	0.01 / 0.01	0.0 / 0.0
Qwen3-14B	lowercase	prefix 20	0.74 / 0.73	6.2 / 6.1	0.46 / 0.46	15.0 / 12.5
Qwen3-14B	lowercase	prompt: opener hint	0.00 / 0.00	–	0.00 / 0.00	0.0 / 0.0
Qwen3-14B	uppercase	prefix 20	0.81 / 0.79	7.9 / 7.4	0.44 / 0.44	14.2 / 15.3
Qwen3-14B	uppercase	prompt: opener hint	0.00 / 0.00	–	0.00 / 0.00	0.0 / 0.0
Qwen3-32B	lowercase	prefix 1	0.73 / 0.73	6.0 / 5.8	0.47 / 0.48	26.5 / 26.8
Qwen3-32B	lowercase	prefix 20	0.84 / 0.82	3.3 / 3.3	0.66 / 0.64	32.5 / 33.3
Qwen3-32B	uppercase	prefix 1	0.59 / 0.59	3.1 / 3.5	0.46 / 0.45	26.0 / 25.3
Qwen3-32B	uppercase	prefix 20	0.92 / 0.92	3.6 / 3.2	0.69 / 0.72	38.0 / 40.5
Qwen3-4B	lowercase	prefix 20	0.10 / 0.11	17.0 / 21.9	0.04 / 0.03	0.2 / 0.3
Qwen3-4B	uppercase	prefix 20	0.09 / 0.10	75.0 / 84.2	0.00 / 0.00	0.0 / 0.0
Qwen3-8B	lowercase	prefix 20	0.66 / 0.66	5.2 / 5.6	0.45 / 0.43	12.8 / 13.0
Qwen3-8B	lowercase	prompt: opener hint	0.68 / 0.69	3.5 / 3.5	0.52 / 0.52	29.0 / 28.8
Qwen3-8B	uppercase	prefix 20	0.77 / 0.75	18.5 / 16.5	0.17 / 0.20	2.0 / 1.7
Qwen3-8B	uppercase	prompt: opener hint	0.07 / 0.08	–	0.06 / 0.06	4.5 / 5.5
gpt-oss-20b	lowercase	prefix 1	0.07 / 0.07	111.9 / 76.6	0.00 / 0.00	0.0 / 0.0
gpt-oss-20b	lowercase	prefix 20	0.06 / 0.05	77.9 / 79.3	0.00 / 0.00	0.0 / 0.0
gpt-oss-20b	lowercase	prompt: opener hint	0.14 / 0.16	72.3 / 79.2	0.00 / 0.00	0.0 / 0.2
gpt-oss-20b	uppercase	prefix 1	0.11 / 0.12	23.8 / 18.5	0.03 / 0.04	2.5 / 3.2
gpt-oss-20b	uppercase	prefix 20	0.06 / 0.06	50.2 / 53.4	0.00 / 0.00	0.0 / 0.2
gpt-oss-20b	uppercase	prompt: opener hint	0.00 / 0.01	–	0.00 / 0.00	0.2 / 0.2

Example traces. All from the GPQA subset; "‖" marks the end of the prefix.

- *Never started* (Qwen3-32B, uppercase, plain): "Okay, let's try to figure this out. So, the question is about contact angles on smooth and rough surfaces. The coating was first applied . . . " The trace continues in ordinary case throughout and does not mention the constraint.

- *Opener complies, trace does not* (OLMo-3-7B, lowercase, plain): "okay, so I have this problem about contact angles and the Cassie-Baxter state. Let me try to think through it step by step. First, . . . "

- *Prefix continuation with an isolated slip* (Qwen3-32B, uppercase, $K = 20$): "OKAY, LET'S TRY TO FIGURE OUT THIS PROBLEM STEP BY STEP. SO, WE HAVE ANILINE BEING HEATED WITH SULFURIC ACID ‖ 1ST. ANILINE IS C6H5NH2. WHEN HEATED WITH H2SO4, IT PROBABLY UNDERGOES SULFONATION . . . FOLLOWED BY SODIUM NITRITE AND HCl. SO FIRST, SODIUM BICARBONATE IS BASIC . . . " First violation at word 159 ("HCl"); the text stays in uppercase afterwards.

- *Genuine "meow" adoption* (Qwen3-32B): "Okay, meow let me try meow to figure meow out these meow cycloaddition meow reactions. So meow, the meow question meow is asking . . . "

- *Degenerate "meow" compliance* (Qwen3-8B): "meow meow meow meow . . . " until the token limit, with no content words and no answer; the released grader returns 1.

What counts as a slip after a prefix. Table 15 regrades the $K = 20$ arms with the masked grader and classifies each first violation under the strict grader as *isolated* (fewer than two of the next three words are also off-style) or a reversion.

Table 15: $K = 20$ prefix arms under the strict and the masked case grader. $h_{20\text{–}100}$: hazard per 1,000 words over words 20–100; binary: continuations with no violation (OLMo-3 Think models under the 4,096-token budget); isolated: share of first strict violations that are single off-style tokens rather than reversions.

		strict grader				masked grader		
Constraint	Model	π	$h_{20\text{–}100}$	binary (%)	isolated (%)	π	$h_{20\text{–}100}$	binary (%)
Uppercase	Qwen3-8B	0.77	18.5	2.0	31	0.87	15.3	2.2
	Qwen3-32B	0.92	3.6	38.0	86	0.97	1.3	52.0
	OLMo-3-7B	0.27	46.5	0.0	12	0.30	41.0	0.3
	OLMo-3-32B	0.82	10.2	2.0	46	0.90	7.3	2.3
	gpt-oss-20b	0.06	50.2	0.0	18	0.06	46.0	0.0
	gpt-oss-120b	0.06	87.7	0.2	18	0.07	60.0	0.2
	OLMo-3-7B base	0.75	5.5	36.9	70	0.86	3.1	54.7
	OLMo-3-7B RL-Zero-Math	0.84	3.8	39.5	67	0.90	2.5	49.0
	OLMo-3-7B SFT	0.33	35.9	0.0	22	0.40	35.1	0.2
	OLMo-3-7B DPO	0.28	42.5	0.0	28	0.35	37.9	0.3
Lowercase	Qwen3-8B	0.66	5.2	12.8	95	0.92	2.4	30.3
	Qwen3-32B	0.84	3.3	32.5	96	0.95	1.0	58.3
	OLMo-3-7B	0.22	20.1	0.2	95	0.34	10.4	1.2
	OLMo-3-32B	0.72	4.0	10.8	98	0.82	1.5	16.7
	gpt-oss-20b	0.06	77.9	0.0	92	0.12	82.3	0.7
	gpt-oss-120b	0.05	70.8	0.0	90	0.12	70.0	0.0
	OLMo-3-7B base	0.62	9.0	17.7	92	0.82	4.3	31.3
	OLMo-3-7B RL-Zero-Math	0.68	7.3	9.8	93	0.86	4.1	17.8
	OLMo-3-7B SFT	0.25	18.5	0.8	94	0.38	12.0	2.3
	OLMo-3-7B DPO	0.11	18.7	0.0	97	0.24	15.7	0.3

Selection among adopters. Slip rates are computed among traces that pass the onset window, and the share that does so ranges from 0.27 to 0.95 across models. Under frailty this selection works *against* the contrasts we report: where few traces adopt, the adopters are the less slip-prone ones, which lowers the measured rate of exactly the models with the highest rates. The cross-model ratios are therefore conservative in this respect.

Table 16: Keyword-opportunity terciles, Qwen3-8B suppression: questions split by how often the model's own unconstrained traces use the forbidden word. Slips per word rise with the rate at which the word is called for; slips per opportunity do not.

Tercile	n	unconstrained keyword rate (per 1k words)	slips per 1k words	slips per 100 opp.	C_{500}	binary (%)
low	300	6.9	3.9	59	0.11	1.7
mid	300	18.2	7.9	45	0.06	1.3
high	300	34.5	12.1	36	0.03	1.0

Table 17: Mentions of the forbidden keyword or its synonyms in unconstrained traces and under the suppression instruction (same questions, same grader). "None in 100 w.": share of traces with no mention in the first 100 words (C_{100} without censoring adjustment).

Model	Prompt	per 1k words	median	none in 100 w.	none in 500 w.	none at all	< 3	median words	acc. (%)
Qwen3-8B	no constraint	21.3	41	0.21	0.03	0.00	0.01	2400	32
	suppression	17.5	24	0.28	0.07	0.01	0.05	1616	39
Qwen3-32B	no constraint	19.3	28	0.20	0.02	0.00	0.01	1588	36
	suppression	12.9	9	0.45	0.17	0.10	0.25	986	47
OLMo-3-7B	no constraint	19.7	37	0.25	0.06	0.01	0.02	2636	14
	suppression	17.5	30	0.28	0.06	0.01	0.04	2558	18
OLMo-3-32B	no constraint	20.3	33	0.19	0.04	0.00	0.02	2398	26
	suppression	17.9	25	0.23	0.06	0.01	0.03	2290	28
gpt-oss-20b	no constraint	22.1	11	0.14	0.01	0.00	0.07	487	50
	suppression	17.6	8	0.20	0.06	0.04	0.17	396	50
gpt-oss-120b	no constraint	23.1	9	0.10	0.01	0.01	0.11	342	55
	suppression	15.1	4	0.29	0.15	0.13	0.36	272	53

Censoring. The Kaplan–Meier estimator, C_L and the parametric fits treat a trace that ends without a slip as censored at its length and assume that this censoring is non-informative. Truncation at the token budget is a fixed censoring time and satisfies this; natural trace end need not, and for suppression it does not: a trace that ends early has had fewer occasions to use the keyword, and

the attribution (§2) shows that length and hazard are dependent within a suppression cell. Table 18 quantifies the exposure of each window to this. On the 20–100-word window, on which every cross-model claim in the main text rests, at most 3% of the suppression traces at risk at word 20 (and 0% of the prefixed uppercase traces) have ended without a slip before the window starts; by word 300 the share is 0–12% and by word 1,000 0–19% for suppression, so C_{500} and the later windows of Table 19 are the quantities that informative censoring can bias, and we do not rest cross-model claims on them. As a direct check, the table also gives the 20–100 hazard among traces split by their *final* length. The dependence is real and its direction differs by regime: for suppression the long tercile's hazard is 0.4–0.8× the short tercile's across the six models (Qwen3-8B: 15.3, 13.1 and 10.1 per 1,000 words for median final lengths of 721, 1,841 and 4,806 words), i.e. traces that will run long slip *less* per word early on, as expected if an early slip and an early end are both driven by how much the question calls for the word; for the prefixed uppercase arms the ratio is 0.7–2.7, mostly above 1, because continuations that keep the style to the end are shorter, so the long tercile is enriched in traces that reverted and went on. The common-window hazards are therefore exposure-weighted averages over traces of all eventual lengths, within which the between-tercile spread is at most about threefold; they are comparable across models to the extent that the length mix is similar, and the frailty fits (Table 4) absorb part of this dependence as between-question heterogeneity. The external channel is where natural end is most informative: 0–50% of external traces are shorter than 20 words and 22–74% shorter than 100 across the twelve Qwen3 cells (Table 18, external rows), and among suppression traces at risk at word 20, 14–22% end without a slip before word 100 (long/short tercile hazard ratio 0.8–1.3). The external "reasoning" of the small sizes is a few sentences, so its exposure term in the channel attribution (§6) largely reads "the model writes little", and the 4B cells are not attributed.

Table 18: Censoring check. For each cell: the share of all traces shorter than 20 and 100 words, traces at risk at word 20, the share of them that ended without a slip before word 100 and 300 (truncated traces included; the 1,000-word column is quoted in the text), the median final length (thousands of words) of the short, middle and long tercile of final length (S/M/L), and the first-slip hazard on words 20–100 (per 1,000 words, 95% question-clustered bootstrap intervals) within each tercile. "–": fewer than 10 traces at risk.

				ended w/o slip before			$h_{20\text{–}100}$ by final-length tercile		
Model	Cell	<20/<100 w. (%)	n at 20	100	300	kwords S/M/L	short	mid	long
Qwen3-8B	plain suppression	0 / 0	681	0	0	0.7/1.8/4.8	15.3 [12.2,18.9]	13.1 [10.4,16.4]	10.1 [7.8,13.0]
Qwen3-32B	plain suppression	0 / 0	518	0	1	0.4/1.0/3.1	10.0 [7.7,12.8]	7.4 [5.6,9.5]	8.2 [6.1,10.6]
OLMo-3-7B	plain suppression	0 / 0	448	0	0	1.4/2.6/3.0	17.6 [13.7,22.6]	12.0 [9.2,15.5]	11.6 [8.7,15.2]
OLMo-3-32B	plain suppression	0 / 0	449	0	0	0.9/2.3/2.9	22.5 [18.5,28.0]	12.2 [9.3,15.9]	14.9 [11.6,18.9]
gpt-oss-20b	plain suppression	0 / 7	382	1	4	0.2/0.5/1.4	20.5 [15.6,26.2]	16.6 [12.9,21.4]	12.7 [9.5,16.8]
gpt-oss-120b	plain suppression	0 / 10	415	3	12	0.1/0.3/0.9	21.8 [16.9,28.1]	9.9 [7.6,12.8]	7.7 [5.6,10.0]
Qwen3-8B	plain lowercase	0 / 0	197	0	5	0.4/0.7/1.6	1.4 [0.0,4.5]	3.5 [1.5,7.0]	4.6 [1.8,8.5]
Qwen3-32B	plain lowercase	0 / 0	190	0	12	0.3/0.6/2.0	2.3 [0.7,4.7]	4.5 [2.5,7.8]	10.7 [6.0,17.9]
Qwen3-8B	prefix 20 uppercase	0 / 0	462	0	2	0.6/1.6/4.4	12.5 [9.7,16.1]	19.9 [16.6,23.9]	25.6 [21.6,30.7]
Qwen3-32B	prefix 20 uppercase	0 / 0	551	0	13	0.3/0.8/2.8	2.0 [1.3,2.9]	3.8 [2.6,5.1]	5.3 [3.9,6.9]
OLMo-3-7B	prefix 20 uppercase	0 / 0	163	0	0	1.5/2.6/3.1	52.9 [40.3,72.7]	51.1 [37.7,73.5]	38.1 [26.4,56.0]
OLMo-3-32B	prefix 20 uppercase	0 / 0	492	0	1	0.6/2.2/2.8	7.3 [5.4,9.3]	13.1 [10.5,16.8]	10.8 [8.6,13.3]
Qwen3-4B	external CoT suppression	36 / 58	227	15	32	0.1/0.1/0.2	14.1 [9.2,20.8]	12.4 [8.9,16.8]	11.8 [8.0,17.5]
Qwen3-4B	external CoT lowercase	30 / 74	336	68	93	0.1/0.1/0.1	1.1 [0.0,2.7]	0.6 [0.1,1.3]	1.6 [0.7,2.7]
Qwen3-4B	external CoT uppercase	50 / 72	46	89	100	0.1/0.1/0.1	0.0 [0.0,0.0]	0.0 [0.0,0.0]	0.0 [0.0,0.0]
Qwen3-8B	external CoT suppression	15 / 36	387	14	41	0.1/0.2/0.3	8.4 [5.7,11.9]	9.1 [6.7,11.8]	7.9 [5.8,10.4]
Qwen3-8B	external CoT lowercase	10 / 52	493	47	89	0.1/0.1/0.2	0.3 [0.0,1.0]	0.5 [0.2,1.0]	1.8 [1.0,2.7]
Qwen3-8B	external CoT uppercase	24 / 60	326	51	86	0.1/0.1/0.1	1.1 [0.2,2.1]	1.6 [0.8,2.6]	3.6 [1.9,5.8]
Qwen3-14B	external CoT suppression	0 / 22	552	18	56	0.1/0.2/0.3	4.2 [2.9,5.7]	4.7 [3.4,6.0]	4.7 [3.4,6.3]
Qwen3-14B	external CoT lowercase	0 / 30	581	31	83	0.1/0.1/0.3	0.2 [0.0,0.5]	0.5 [0.1,1.1]	1.4 [0.8,2.1]
Qwen3-14B	external CoT uppercase	0 / 28	498	31	72	0.1/0.1/0.3	0.4 [0.0,1.1]	2.7 [1.7,3.9]	6.5 [4.5,8.9]
Qwen3-32B	external CoT suppression	1 / 26	564	22	65	0.1/0.2/0.3	1.8 [1.0,2.9]	2.7 [1.7,3.9]	2.3 [1.4,3.3]
Qwen3-32B	external CoT lowercase	4 / 36	560	31	81	0.1/0.1/0.3	0.6 [0.2,1.2]	0.7 [0.3,1.2]	1.0 [0.5,1.5]
Qwen3-32B	external CoT uppercase	2 / 36	491	34	70	0.1/0.1/0.2	2.3 [1.2,3.5]	2.4 [1.5,3.4]	7.2 [5.2,9.7]

Hazard by position. Table 19 gives piecewise-constant hazards on fixed windows. The hazard falls with position in every cell, as the frailty fits imply, so time-averaged λ depends on how long traces are observed; cross-model and cross-checkpoint statements in the main text use the 20–100 and 100–300 windows, with paired bootstrap ratios in Table 20.

Table 19: First-slip hazard per 1,000 words on common windows (words after the prefix, or into the trace for plain runs), with the number of traces entering the first window compliant. A window is printed when ≥ 10 traces enter it and ≥ 10 slips occur in it. "7B …" are OLMo-3-7B checkpoints.

Model	Arm	median words	n at 20	20–100	100–300	300–1,000	1,000–3,000
Uppercase							
Qwen3-8B	prefix 1	1710	28	–	6.7 [3.8, 11.0]	–	–
Qwen3-8B	prefix 5	1722	487	13.5 [11.7, 15.6]	9.2 [7.3, 11.6]	7.6 [4.6, 12.5]	–
Qwen3-8B	prefix 20	1781	462	18.5 [16.2, 21.2]	7.8 [6.0, 10.2]	9.3 [6.7, 15.0]	–
Qwen3-8B	prefix 100	1714	404	15.8 [13.6, 18.2]	8.0 [6.2, 10.3]	8.0 [4.5, 15.6]	–
Qwen3-8B	prefix 20, no instr.	2548	266	47.4 [40.2, 56.8]	30.5 [17.2, 84.2]	–	–
Qwen3-8B	prefix 100, no instr.	2330	269	32.0 [26.8, 38.9]	12.4 [9.1, 17.4]	–	–
Qwen3-32B	prefix 1	766	353	3.1 [2.3, 4.0]	1.6 [1.2, 2.1]	1.1 [0.8, 1.5]	–
Qwen3-32B	prefix 5	820	486	3.7 [2.9, 4.5]	1.5 [1.1, 1.9]	0.7 [0.5, 1.0]	0.4 [0.2, 0.7]
Qwen3-32B	prefix 20	872	551	3.6 [2.9, 4.4]	1.6 [1.3, 2.0]	0.7 [0.5, 1.0]	0.6 [0.3, 0.9]
Qwen3-32B	prefix 100	770	570	2.7 [2.1, 3.4]	1.2 [0.9, 1.5]	0.9 [0.7, 1.1]	0.4 [0.2, 0.7]
Qwen3-32B	prefix 20, no instr.	1346	444	8.4 [6.9, 10.0]	2.6 [2.0, 3.3]	0.9 [0.6, 1.3]	1.0 [0.6, 1.9]
Qwen3-32B	prefix 100, no instr.	1104	542	4.1 [3.4, 4.9]	1.8 [1.4, 2.2]	1.5 [1.2, 1.8]	1.2 [0.6, 2.1]
OLMo-3-7B	prefix 5	2566	78	49.2 [37.7, 64.5]	–	–	–
OLMo-3-7B	prefix 20	2584	163	46.5 [37.7, 56.6]	–	–	–
OLMo-3-7B	prefix 100	2536	144	40.9 [32.9, 51.3]	–	–	–
OLMo-3-7B	prefix 20, no instr.	2654	88	73.8 [60.6, 93.7]	–	–	–
OLMo-3-7B	prefix 100, no instr.	2662	103	58.3 [46.4, 75.9]	–	–	–
OLMo-3-32B	prefix 1	2228	511	10.6 [9.4, 12.0]	8.9 [7.5, 10.5]	7.7 [5.4, 11.8]	–
OLMo-3-32B	prefix 5	2166	531	9.1 [7.8, 10.4]	9.8 [8.4, 11.4]	8.2 [6.3, 11.1]	–
OLMo-3-32B	prefix 20	2234	492	10.2 [8.8, 11.8]	9.5 [8.1, 11.3]	7.3 [4.6, 12.2]	–
OLMo-3-32B	prefix 100	2266	443	11.2 [9.7, 12.7]	9.5 [7.8, 11.6]	9.8 [5.4, 22.5]	–
OLMo-3-32B	prefix 20, no instr.	2420	245	48.1 [40.0, 57.2]	18.3 [9.6, 56.5]	–	–
OLMo-3-32B	prefix 100, no instr.	2374	274	20.9 [17.6, 24.8]	15.0 [11.3, 19.7]	–	–
gpt-oss-20b	prefix 1	274	69	23.8 [16.9, 34.7]	–	–	–
gpt-oss-20b	prefix 5	356	11	123.6 [61.9, 304.3]	–	–	–
gpt-oss-20b	prefix 20	408	34	50.2 [27.7, 89.8]	–	–	–
gpt-oss-20b	prefix 100	330	27	40.6 [17.6, 120.1]	–	–	–
gpt-oss-20b	prefix 20, no instr.	490	25	62.8 [38.7, 119.7]	–	–	–
gpt-oss-120b	prefix 20	264	32	87.7 [58.2, 149.3]	–	–	–
gpt-oss-120b	prefix 100	207	19	54.0 [20.6, 160.1]	–	–	–
gpt-oss-120b	prefix 20, no instr.	340	23	57.4 [22.0, 203.6]	–	–	–
Qwen3-4B	prefix 20	1538	56	75.0 [56.2, 108.5]	–	–	–
Qwen3-4B	prefix 100	1522	71	50.4 [38.5, 67.3]	–	–	–
Qwen3-4B	prefix 20, no instr.	2086	47	94.0 [68.0, 141.6]	–	–	–
Qwen3-14B	prefix 1	812	279	4.8 [3.7, 6.1]	2.6 [1.9, 3.5]	2.7 [1.7, 3.8]	–
Qwen3-14B	prefix 20	1026	489	7.9 [6.6, 9.4]	4.0 [3.3, 4.7]	3.9 [3.0, 5.2]	–
Qwen3-14B	prefix 100	1028	523	7.3 [6.1, 8.6]	3.4 [2.8, 4.1]	5.4 [4.1, 7.1]	–
Qwen3-14B	prefix 20, no instr.	1577	288	42.4 [34.3, 52.2]	11.0 [4.8, 25.8]	–	–
7B base	prefix 20	373	362	5.5 [4.6, 6.8]	2.1 [1.5, 2.7]	–	–
7B base	prefix 20, no instr.	324	343	5.4 [4.3, 6.7]	1.7 [1.2, 2.4]	–	–
7B RL-Zero-Math	prefix 20	780	506	3.8 [3.0, 4.5]	2.1 [1.7, 2.6]	0.5 [0.4, 0.7]	–
7B RL-Zero-Math	prefix 20, no instr.	877	447	5.7 [4.8, 6.8]	2.6 [2.1, 3.1]	0.7 [0.4, 1.0]	–
7B RL-Zero-Code	prefix 20	320	510	5.4 [4.5, 6.3]	2.6 [2.1, 3.2]	1.4 [0.8, 2.2]	–
7B RL-Zero-Code	prefix 20, no instr.	335	436	7.2 [6.0, 8.6]	3.6 [2.9, 4.5]	1.6 [0.8, 3.0]	–
7B RL-Zero-General	prefix 20	417	295	16.3 [13.6, 19.7]	2.6 [1.6, 3.8]	–	–
7B RL-Zero-General	prefix 20, no instr.	434	235	20.0 [16.1, 24.9]	2.7 [1.5, 4.3]	–	–
7B SFT	prefix 20	2204	199	35.9 [30.0, 44.0]	24.4 [16.1, 43.0]	–	–
7B SFT	prefix 20, no instr.	2394	127	53.3 [43.7, 68.8]	–	–	–
7B DPO	prefix 20	2380	168	42.5 [35.4, 51.4]	–	–	–
Lowercase							
Qwen3-8B	plain	1744	197	3.1 [1.6, 5.1]	1.9 [1.3, 2.6]	1.4 [0.9, 2.3]	–
Qwen3-8B	prefix 1	1316	437	7.1 [5.7, 8.7]	2.2 [1.7, 2.7]	1.4 [1.0, 1.8]	1.1 [0.6, 1.7]
Qwen3-8B	prefix 5	1440	413	8.5 [6.8, 10.3]	2.4 [1.8, 3.0]	1.4 [1.1, 1.8]	–
Qwen3-8B	prefix 20	1446	398	5.2 [3.9, 6.2]	2.2 [1.7, 2.7]	1.6 [1.2, 2.0]	0.9 [0.5, 1.5]
Qwen3-8B	prefix 100	1407	551	2.9 [2.3, 3.6]	2.3 [1.9, 2.8]	1.7 [1.4, 2.1]	0.9 [0.6, 1.4]
Qwen3-8B	prefix 20, no instr.	2442	130	21.6 [16.7, 28.0]	10.9 [7.9, 16.3]	–	–
Qwen3-8B	prefix 100, no instr.	2435	442	11.5 [9.7, 13.3]	6.1 [4.9, 7.5]	4.8 [3.2, 7.3]	–
Qwen3-32B	plain	988	190	5.4 [3.5, 7.9]	1.1 [0.7, 1.6]	0.9 [0.4, 1.5]	–
Qwen3-32B	prefix 1	822	437	6.0 [4.8, 7.2]	1.0 [0.7, 1.3]	0.9 [0.7, 1.2]	0.5 [0.3, 0.9]
Qwen3-32B	prefix 5	871	411	4.0 [3.1, 4.9]	0.9 [0.6, 1.1]	1.0 [0.7, 1.2]	0.3 [0.2, 0.6]
Qwen3-32B	prefix 20	788	505	3.3 [2.6, 4.1]	1.4 [1.1, 1.8]	1.0 [0.8, 1.3]	0.5 [0.3, 0.8]
Qwen3-32B	prefix 100	883	578	1.4 [1.0, 1.8]	0.8 [0.6, 1.0]	0.8 [0.6, 0.9]	0.3 [0.2, 0.5]
Qwen3-32B	prefix 20, no instr.	1452	285	11.0 [8.9, 13.3]	3.6 [2.8, 4.7]	2.5 [1.8, 3.4]	–
Qwen3-32B	prefix 100, no instr.	1270	523	4.1 [3.3, 5.0]	2.6 [2.1, 3.1]	1.8 [1.5, 2.2]	0.7 [0.4, 1.2]
OLMo-3-7B	plain	2544	42	221.1 [166.1, 322.0]	–	–	–
OLMo-3-7B	prefix 1	2548	64	166.7 [105.5, 274.9]	–	–	–
OLMo-3-7B	prefix 5	2524	65	70.6 [36.6, 147.8]	–	–	–
OLMo-3-7B	prefix 20	2571	134	20.1 [14.9, 27.3]	6.7 [4.7, 9.2]	–	–
OLMo-3-7B	prefix 100	2476	392	11.3 [9.6, 13.2]	8.3 [6.7, 10.3]	5.4 [3.9, 7.7]	–
OLMo-3-7B	prefix 20, no instr.	2580	48	54.5 [38.2, 87.2]	–	–	–
OLMo-3-32B	prefix 1	2284	86	10.7 [6.8, 16.6]	3.8 [2.4, 5.7]	–	–
OLMo-3-32B	prefix 5	2309	240	6.6 [5.0, 8.5]	2.8 [2.0, 3.6]	2.9 [2.2, 4.0]	–
OLMo-3-32B	prefix 20	2197	430	4.0 [3.1, 5.0]	3.0 [2.5, 3.6]	2.2 [1.7, 2.8]	–
OLMo-3-32B	prefix 100	2242	550	3.6 [2.9, 4.3]	2.7 [2.2, 3.2]	1.9 [1.5, 2.3]	1.7 [0.9, 3.2]

(continued)

Model	Arm	median words	n at 20	20–100	100–300	300–1,000	1,000–3,000
OLMo-3-32B	prefix 20, no instr.	2424	141	17.2 [12.9, 23.2]	5.7 [3.5, 8.6]	6.5 [3.7, 14.0]	–
OLMo-3-32B	prefix 100, no instr.	2362	442	9.0 [7.7, 10.6]	5.6 [4.6, 6.9]	4.5 [3.5, 5.7]	–
gpt-oss-20b	prefix 1	278	45	111.9 [78.5, 168.8]	–	–	–
gpt-oss-20b	prefix 5	329	29	173.7 [119.4, 295.5]	–	–	–
gpt-oss-20b	prefix 20	324	33	77.9 [47.3, 146.7]	–	–	–
gpt-oss-20b	prefix 100	255	46	37.4 [21.2, 77.4]	–	–	–
gpt-oss-20b	prefix 20, no instr.	351	25	103.3 [71.6, 200.0]	–	–	–
gpt-oss-120b	plain	248	39	220.3 [147.8, 375.0]	–	–	–
gpt-oss-120b	prefix 1	249	44	130.6 [89.1, 244.4]	–	–	–
gpt-oss-120b	prefix 5	266	27	117.9 [70.3, 269.9]	–	–	–
gpt-oss-120b	prefix 20	258	28	70.8 [31.4, 182.9]	–	–	–
gpt-oss-120b	prefix 100	193	56	70.3 [41.6, 121.2]	–	–	–
gpt-oss-120b	prefix 20, no instr.	300	17	63.6 [18.0, 514.4]	–	–	–
Qwen3-4B	prefix 20	1492	63	17.0 [10.1, 28.3]	10.6 [6.3, 19.9]	–	–
Qwen3-4B	prefix 100	1396	443	11.9 [10.3, 13.9]	6.7 [5.5, 8.2]	6.4 [4.6, 9.4]	–
Qwen3-4B	prefix 20, no instr.	1958	27	83.9 [37.6, 365.4]	–	–	–
Qwen3-14B	plain	1175	11	–	–	–	–
Qwen3-14B	prefix 1	962	334	5.6 [4.4, 6.9]	2.4 [1.9, 3.2]	1.3 [1.0, 1.8]	1.8 [1.0, 3.2]
Qwen3-14B	prefix 20	999	442	6.2 [5.0, 7.4]	2.7 [2.2, 3.2]	1.6 [1.2, 2.1]	–
Qwen3-14B	prefix 100	1072	548	2.8 [2.2, 3.5]	2.3 [1.9, 2.7]	1.4 [1.1, 1.8]	0.7 [0.4, 1.0]
Qwen3-14B	prefix 20, no instr.	1662	154	17.2 [13.4, 22.0]	8.0 [5.7, 11.6]	–	–
7B base	prefix 20	398	307	9.0 [7.4, 10.9]	3.8 [2.9, 4.9]	1.8 [0.9, 3.1]	–
7B RL-Zero-Math	prefix 20	1697	406	7.3 [6.1, 8.8]	3.4 [2.7, 4.2]	2.2 [1.6, 2.9]	–
7B RL-Zero-Code	prefix 20	724	388	7.9 [6.5, 9.4]	4.5 [3.5, 5.6]	3.0 [1.9, 4.7]	–
7B RL-Zero-General	prefix 20	409	283	16.5 [13.7, 20.2]	5.9 [4.1, 8.1]	–	–
7B SFT	prefix 20	2096	148	18.5 [14.5, 24.1]	5.9 [4.3, 8.1]	–	–
7B DPO	plain	2406	11	164.2 [120.8, 344.8]	–	–	–
7B DPO	prefix 20	2332	66	18.7 [13.1, 28.7]	8.0 [3.7, 21.6]	–	–
Suppress one keyword							
Qwen3-8B	plain	1616	681	12.7 [11.0, 14.8]	5.4 [4.3, 6.8]	2.1 [1.5, 2.9]	0.7 [0.4, 1.4]
Qwen3-32B	plain	986	518	8.5 [7.2, 9.9]	3.5 [2.9, 4.3]	1.6 [1.2, 2.1]	–
OLMo-3-7B	plain	2558	448	13.5 [11.5, 15.7]	6.5 [5.2, 8.3]	2.1 [1.4, 3.2]	–
OLMo-3-32B	plain	2290	449	16.0 [13.7, 18.6]	5.4 [4.0, 7.0]	1.7 [1.1, 2.6]	1.2 [0.6, 2.1]
gpt-oss-20b	plain	396	382	16.2 [13.8, 19.3]	6.7 [4.9, 8.9]	2.3 [1.5, 3.8]	–
gpt-oss-120b	plain	272	415	11.8 [10.0, 13.9]	3.7 [2.7, 5.0]	1.7 [1.0, 2.7]	–
Qwen3-4B	plain	1386	436	14.6 [12.5, 16.9]	5.9 [4.6, 7.5]	2.0 [1.3, 3.0]	–
Qwen3-14B	plain	1178	480	11.5 [9.9, 13.3]	5.0 [4.0, 6.4]	1.9 [1.4, 2.6]	–
7B base	plain	1138	303	16.1 [13.6, 18.9]	4.3 [3.1, 6.0]	1.1 [0.6, 2.0]	–
7B RL-Zero-Math	plain	2022	430	16.7 [14.6, 19.4]	4.8 [3.5, 6.3]	1.3 [0.8, 2.0]	–
7B RL-Zero-Code	plain	1720	415	15.3 [13.0, 18.0]	6.5 [5.1, 8.4]	1.5 [0.9, 2.5]	–
7B RL-Zero-General	plain	436	409	13.9 [11.8, 16.5]	6.3 [4.8, 7.9]	2.2 [1.3, 3.4]	–
7B SFT	plain	2128	454	14.5 [12.6, 16.6]	5.7 [4.5, 7.3]	2.7 [1.9, 3.9]	–
7B DPO	plain	2318	441	13.1 [11.2, 15.2]	5.0 [3.9, 6.3]	2.4 [1.7, 3.4]	–

Table 20: Paired bootstrap ratios of common-window hazards (95% intervals), with the number of first slips in the window for each arm: between models after a 20-word prefix, between training stages, between the prefix arms and the plain run for lowercase, and between prefix lengths ($^{\mathrm{P}}$: pre-registered E10 D3 contrast). *: interval excludes 1 (unadjusted). Comparisons with fewer than 10 slips in either arm are omitted.

Comparison	Constraint	Window (words)	hazards	slips	Ratio [95% CI]
Qwen3 4B / 8B	uppercase	20–100	75.0 / 18.5	56 / 357	4.04 [2.96, 6.01]*
Qwen3 8B / 14B	uppercase	20–100	18.5 / 7.9	357 / 220	2.34 [1.94, 2.83]*
Qwen3 8B / 14B	uppercase	100–300	7.8 / 4.0	76 / 135	1.97 [1.44, 2.73]*
Qwen3 14B / 32B	uppercase	20–100	7.9 / 3.6	220 / 136	2.19 [1.77, 2.74]*
Qwen3 14B / 32B	uppercase	100–300	4.0 / 1.6	135 / 104	2.46 [1.93, 3.17]*
Qwen3 8B / 32B	uppercase	20–100	18.5 / 3.6	357 / 136	5.14 [4.13, 6.46]*
Qwen3 8B / 32B	uppercase	100–300	7.8 / 1.6	76 / 104	4.83 [3.48, 6.69]*
OLMo-3 7B / 32B	uppercase	20–100	46.5 / 10.2	157 / 273	4.56 [3.61, 5.90]*
OLMo-3-7B / Qwen3-32B (extremes)	uppercase	20–100	46.5 / 3.6	157 / 136	12.88 [9.81, 16.75]*
Qwen3 4B / 32B	uppercase	20–100	75.0 / 3.6	56 / 136	20.77 [14.35, 32.76]*
OLMo-3-7B SFT / base	uppercase	20–100	35.9 / 5.5	184 / 123	6.50 [5.05, 8.49]*
OLMo-3-7B SFT / base	uppercase	100–300	24.4 / 2.1	15 / 56	11.89 [7.35, 23.07]*
OLMo-3-7B final / base	uppercase	20–100	46.5 / 5.5	157 / 123	8.41 [6.40, 10.89]*
Qwen3 4B / 8B	lowercase	20–100	17.0 / 5.2	41 / 129	3.29 [1.89, 5.83]*
Qwen3 4B / 8B	lowercase	100–300	10.6 / 2.2	19 / 93	4.81 [2.76, 9.24]*
Qwen3 8B / 14B	lowercase	20–100	5.2 / 6.2	129 / 167	0.83 [0.65, 1.06]
Qwen3 8B / 14B	lowercase	100–300	2.2 / 2.7	93 / 111	0.82 [0.63, 1.06]
Qwen3 14B / 32B	lowercase	20–100	6.2 / 3.3	167 / 112	1.89 [1.51, 2.40]*
Qwen3 14B / 32B	lowercase	100–300	2.7 / 1.4	111 / 90	1.86 [1.40, 2.47]*
Qwen3 8B / 32B	lowercase	20–100	5.2 / 3.3	129 / 112	1.58 [1.22, 2.04]*
Qwen3 8B / 32B	lowercase	100–300	2.2 / 1.4	93 / 90	1.53 [1.11, 2.12]*
OLMo-3 7B / 32B	lowercase	20–100	20.1 / 4.0	97 / 116	5.07 [3.69, 7.32]*
OLMo-3 7B / 32B	lowercase	100–300	6.7 / 3.0	27 / 138	2.22 [1.49, 3.31]*
OLMo-3-7B / Qwen3-32B (extremes)	lowercase	20–100	20.1 / 3.3	97 / 112	6.16 [4.35, 9.09]*
OLMo-3-7B / Qwen3-32B (extremes)	lowercase	100–300	6.7 / 1.4	27 / 90	4.62 [3.13, 6.84]*
Qwen3 4B / 32B	lowercase	20–100	17.0 / 3.3	41 / 112	5.19 [2.90, 9.09]*
Qwen3 4B / 32B	lowercase	100–300	10.6 / 1.4	19 / 90	7.37 [4.24, 13.87]*
OLMo-3-7B SFT / base	lowercase	20–100	18.5 / 9.0	105 / 147	2.06 [1.56, 2.79]*
OLMo-3-7B SFT / base	lowercase	100–300	5.9 / 3.8	30 / 59	1.54 [1.02, 2.32]*
OLMo-3-7B final / base	lowercase	20–100	20.1 / 9.0	97 / 147	2.24 [1.61, 3.23]*
OLMo-3-7B final / base	lowercase	100–300	6.7 / 3.8	27 / 59	1.76 [1.12, 2.69]*
Qwen3-8B prefix 20 / plain	lowercase	20–100	5.2 / 3.1	129 / 41	1.67 [0.97, 3.23]
Qwen3-8B prefix 20 / plain	lowercase	100–300	2.2 / 1.9	93 / 48	1.19 [0.82, 1.81]
Qwen3-8B prefix 100 / plain	lowercase	20–100	2.9 / 3.1	111 / 41	0.93 [0.54, 1.84]
Qwen3-8B prefix 100 / plain	lowercase	100–300	2.3 / 1.9	156 / 48	1.25 [0.87, 1.88]
Qwen3-32B prefix 20 / plain	lowercase	20–100	3.3 / 5.4	112 / 62	0.61 [0.41, 0.95]*
Qwen3-32B prefix 20 / plain	lowercase	100–300	1.4 / 1.1	90 / 24	1.29 [0.89, 2.04]
Qwen3-32B prefix 100 / plain	lowercase	20–100	1.4 / 5.4	60 / 62	0.26 [0.16, 0.42]*
Qwen3-32B prefix 100 / plain	lowercase	100–300	0.8 / 1.1	72 / 24	0.74 [0.51, 1.19]
Qwen3-8B prefix 20 / prefix 5	uppercase	20–100	18.5 / 13.5	357 / 321	1.37 [1.18, 1.60]$^{*\,\mathrm{P}}$
Qwen3-8B prefix 20 / prefix 5	uppercase	100–300	7.8 / 9.2	76 / 126	0.85 [0.62, 1.15]$^{\mathrm{P}}$
Qwen3-8B prefix 20 / prefix 1	uppercase	100–300	7.8 / 6.7	76 / 14	1.16 [0.66, 2.20]$^{\mathrm{P}}$
Qwen3-8B prefix 20 / prefix 5	lowercase	20–100	5.2 / 8.5	129 / 188	0.61 [0.48, 0.75]$^{*\,\mathrm{P}}$
Qwen3-8B prefix 20 / prefix 5	lowercase	100–300	2.2 / 2.4	93 / 82	0.94 [0.70, 1.28]$^{\mathrm{P}}$
Qwen3-8B prefix 20 / prefix 1	lowercase	20–100	5.2 / 7.1	129 / 177	0.72 [0.54, 0.89]$^{*\,\mathrm{P}}$
Qwen3-8B prefix 20 / prefix 1	lowercase	100–300	2.2 / 2.2	93 / 88	1.02 [0.77, 1.35]$^{\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 5	uppercase	20–100	3.6 / 3.7	136 / 122	0.98 [0.78, 1.25]$^{\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 5	uppercase	100–300	1.6 / 1.5	104 / 85	1.08 [0.83, 1.43]$^{\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 1	uppercase	20–100	3.6 / 3.1	136 / 75	1.16 [0.88, 1.58]$^{\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 1	uppercase	100–300	1.6 / 1.6	104 / 67	1.00 [0.73, 1.35]$^{\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 5	lowercase	20–100	3.3 / 4.0	112 / 109	0.82 [0.65, 1.04]$^{\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 5	lowercase	100–300	1.4 / 0.9	90 / 45	1.67 [1.22, 2.36]$^{*\,\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 1	lowercase	20–100	3.3 / 6.0	112 / 157	0.55 [0.43, 0.67]$^{*\,\mathrm{P}}$
Qwen3-32B prefix 20 / prefix 1	lowercase	100–300	1.4 / 1.0	90 / 48	1.42 [1.03, 1.98]$^{*\,\mathrm{P}}$

Tokenisation. The three families use different tokenizers, and upper-case text is split into more pieces than mixed-case text, so "20 words" and "words 20–100" are different numbers of tokens per family and per case. Table 21 tokenises the $K = 20$ uppercase prefix and the first 100 words of the continuation with each family's own tokenizer: the uppercase prefix costs 1.31–1.38$\times$ the tokens of the same words in their original case in every family (34–41 tokens for 20 words), and the uppercase continuation runs at 1.46–2.05 tokens per word (unconstrained text: 1.35–1.70). Expressed per 1,000 tokens the common-window hazards are 28.2 (OLMo-3-7B) against 1.9 (Qwen3-32B), a 15$\times$ span (27$\times$ from Qwen3-4B), and the within-family ratios are 5.8 (Qwen3) and 5.7 (OLMo-3): the

cross-family contrast is not a tokenizer artefact, although a per-token hazard is the fairer cross-family unit and the within-family trends are the ones free of the issue.

Table 21: Tokens per word of the 20-word uppercase prefix (original case vs. uppercase) and of words 20–100 (unconstrained trace vs. the uppercase continuation), and the $K = 20$ uppercase $h_{20\text{–}100}$ per 1,000 words and per 1,000 tokens (95% intervals rescaled by the same factor). One tokenizer per family.

		20-word prefix			words 20–100		$h_{20\text{–}100}$	
Model	Tokenizer	tok./word, original	tok./word, uppercase	tokens	tok./word, unconstr.	tok./word, uppercase cont.	per 1,000 words	per 1,000 tokens
Qwen3-4B	Qwen3	1.30	1.71	34	1.40	1.46	75.0 [56.2, 108.5]	51.2 [38.4, 74.1]
Qwen3-8B	Qwen3	1.32	1.74	35	1.41	1.71	18.5 [16.2, 21.2]	10.9 [9.5, 12.4]
Qwen3-14B	Qwen3	1.34	1.77	35	1.41	1.83	7.9 [6.6, 9.4]	4.3 [3.6, 5.1]
Qwen3-32B	Qwen3	1.33	1.74	35	1.39	1.91	3.6 [2.9, 4.4]	1.9 [1.5, 2.3]
OLMo-3-7B	OLMo-3	1.27	1.69	34	1.35	1.65	46.5 [37.7, 56.6]	28.2 [22.9, 34.3]
OLMo-3-32B	OLMo-3	1.28	1.74	35	1.37	2.05	10.2 [8.8, 11.8]	5.0 [4.3, 5.8]
gpt-oss-20b	gpt-oss	1.50	2.03	41	1.70	1.74	50.2 [27.7, 89.8]	28.9 [15.9, 51.7]
gpt-oss-120b	gpt-oss	1.46	2.01	40	1.69	1.75	87.7 [58.2, 149.3]	50.1 [33.3, 85.3]

Accuracy under the intervention. Staying in an unusual style does not stop the model from reasoning. With a 20-word uppercase prefix Qwen3-32B answers 49% of questions correctly (plain constrained run: 50%); its 226 fully uppercase traces are 57% accurate with a median of 398 words, against 51% for closed traces that slipped (Table 22). Fully compliant traces are shorter, so part of their higher accuracy is selection of easier questions; what the table rules out is that sustained compliance is bought by abandoning the task, as it is in the "meow" loops of §3. The no-instruction control lowers accuracy (39% vs. 48% at 32B with 100 words; 29% vs. 39% at 8B) and lengthens traces.

Table 22: Accuracy under the prefix intervention (Qwen3). "Fully compliant": closed traces with no violation in the continuation.

Model	Style	Arm	acc. (%)	median words	n fully compl.	their acc.	their median words	acc. of closed, slipped
Qwen3-8B	upper	plain	42	1772	0	–	–	44
Qwen3-8B	upper	prefix 1	43	1710	6	–	–	45
Qwen3-8B	upper	prefix 5	42	1722	23	74	300	44
Qwen3-8B	upper	prefix 20	38	1781	12	92	246	44
Qwen3-8B	upper	prefix 100	39	1714	20	80	205	44
Qwen3-8B	upper	prefix 20, no instr.	33	2548	0	–	–	37
Qwen3-8B	upper	prefix 100, no instr.	29	2330	1	–	–	36
Qwen3-8B	upper	prompt: opener hint	43	1188	22	45	249	46
Qwen3-8B	upper	prompt: demo	44	1488	0	–	–	46
Qwen3-8B	lower	plain	43	1744	58	64	476	45
Qwen3-8B	lower	prefix 1	43	1316	86	57	502	43
Qwen3-8B	lower	prefix 5	42	1440	75	55	514	42
Qwen3-8B	lower	prefix 20	41	1446	77	49	560	46
Qwen3-8B	lower	prefix 100	42	1407	123	50	497	46
Qwen3-8B	lower	prefix 20, no instr.	32	2442	0	–	–	36
Qwen3-8B	lower	prefix 100, no instr.	29	2435	10	70	377	36
Qwen3-8B	lower	prompt: opener hint	44	1076	174	48	438	45
Qwen3-8B	lower	prompt: demo	43	1265	119	37	536	47
Qwen3-32B	upper	plain	50	948	0	–	–	53
Qwen3-32B	upper	prefix 1	50	766	156	56	376	52
Qwen3-32B	upper	prefix 5	49	820	203	56	423	50
Qwen3-32B	upper	prefix 20	49	872	226	57	398	51
Qwen3-32B	upper	prefix 100	48	770	269	55	393	52
Qwen3-32B	upper	prefix 20, no instr.	36	1346	99	48	414	38
Qwen3-32B	upper	prefix 100, no instr.	39	1104	166	54	402	40
Qwen3-32B	upper	prompt: opener hint	50	878	0	–	–	53
Qwen3-32B	upper	prompt: demo	49	1016	0	–	–	51
Qwen3-32B	lower	plain	50	988	75	64	402	52
Qwen3-32B	lower	prefix 1	52	822	158	62	378	50
Qwen3-32B	lower	prefix 5	51	871	177	60	428	51
Qwen3-32B	lower	prefix 20	49	788	195	55	439	51
Qwen3-32B	lower	prefix 100	50	883	286	57	451	51
Qwen3-32B	lower	prefix 20, no instr.	37	1452	23	43	469	40
Qwen3-32B	lower	prefix 100, no instr.	38	1270	95	42	412	41
Qwen3-32B	lower	prompt: opener hint	50	804	2	–	–	53
Qwen3-32B	lower	prompt: demo	48	848	51	57	551	51

What π measures. Table 23 gives π under three word windows, under constraint-native windows, and as fitted by the onset-mixture-frailty model ($w = 1$). Three patterns: (i) for uppercase, alter-

nating case, the opening string and the sentence-level constraint every definition gives 0; (ii) for lowercase in Qwen3 every definition gives 0.08–0.14, a genuine onset mass; (iii) for suppression, "meow" and OLMo-3-7B lowercase the first unit complies in 63–100% of traces and $\hat{\pi} = 1$, so failure is a (fast or slow) hazard rather than an onset mass, and the $w = 20$ value is early survival. For alternating case the two-letter opener "We" of the gpt-oss models alternates trivially, so their word-1 column (0.93 and 1.00) is not an onset measure; the native first unit (first word of ≥ 3 letters) gives 0.00 and 0.12.

Table 23: Adoption rate under alternative definitions, plain reasoning channel; Qwen3 lowercase cells pool the second-seed traces, as in Table 1. Mixture fit shown when ≥ 10 traces pass the first unit; $\hat{\theta}$ is the frailty variance of the onset-mixture-frailty fit at $w = 1$, whereas Table 4 gives the frailty-only fit, so the two differ for the same cell. [a]For alternating case the native first unit is the first word of three or more letters, because one- and two-letter words ("We", "I") satisfy the constraint trivially.

		word window w			native units		mixture fit	
Constraint	Model	1	20	50	first	first 3	$\hat{\pi}$	$\hat{\theta}$
Uppercase	Qwen3-8B	0.00	0.00	0.00	0.00	0.00	–	–
	Qwen3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	OLMo-3-7B	0.00	0.00	0.00	0.00	0.00	–	–
	OLMo-3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	gpt-oss-20b	0.00	0.00	0.00	0.00	0.00	–	–
	gpt-oss-120b	0.50	0.03	0.01	0.50	0.17	1.00	0.71
Alternating case[a]	Qwen3-8B	0.00	0.00	0.00	0.00	0.00	–	–
	Qwen3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	OLMo-3-7B	0.02	0.00	0.00	0.02	0.01	0.04	0.00
	OLMo-3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	gpt-oss-20b	0.93	0.00	0.00	0.00	0.00	1.00	0.00
	gpt-oss-120b	1.00	0.02	0.00	0.12	0.11	1.00	0.00
Opening/closing string	Qwen3-8B	0.00	0.00	0.00	0.00	0.00	–	–
	Qwen3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	OLMo-3-7B	0.00	0.00	0.00	0.00	0.00	–	–
	OLMo-3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	gpt-oss-20b	1.00	1.00	0.98	1.00	0.02	1.00	0.00
	gpt-oss-120b	0.99	0.99	0.98	0.99	0.08	1.00	0.00
End sentences with "safe"	Qwen3-8B	1.00	0.06	0.00	0.00	0.00	–	–
	Qwen3-32B	1.00	0.10	0.00	0.00	0.00	–	–
	OLMo-3-7B	1.00	0.35	0.00	0.00	0.00	–	–
	OLMo-3-32B	1.00	0.25	0.00	0.00	0.00	–	–
	gpt-oss-20b	1.00	0.18	0.01	0.00	0.00	–	–
	gpt-oss-120b	1.00	0.22	0.01	0.00	0.00	–	–
Lowercase	Qwen3-8B	0.12	0.09	0.08	0.12	0.12	0.12	1.91
	Qwen3-32B	0.15	0.11	0.08	0.15	0.15	0.15	3.10
	OLMo-3-7B	0.75	0.07	0.00	0.75	0.41	1.00	0.43
	OLMo-3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	gpt-oss-20b	0.01	0.00	0.00	0.01	0.01	–	–
	gpt-oss-120b	0.73	0.06	0.00	0.73	0.71	0.73	0.00
"meow" between words	Qwen3-8B	0.63	0.00	0.00	0.63	0.00	1.00	0.09
	Qwen3-32B	0.74	0.10	0.09	0.74	0.10	1.00	1.45
	OLMo-3-7B	0.00	0.00	0.00	0.00	0.00	–	–
	OLMo-3-32B	0.00	0.00	0.00	0.00	0.00	–	–
	gpt-oss-20b	0.00	0.00	0.00	0.00	0.00	–	–
	gpt-oss-120b	0.07	0.05	0.03	0.06	0.06	0.07	0.00
Suppress one keyword	Qwen3-8B	1.00	0.76	0.53	1.00	1.00	1.00	0.64
	Qwen3-32B	1.00	0.86	0.64	1.00	1.00	1.00	1.02
	OLMo-3-7B	1.00	0.75	0.47	1.00	1.00	1.00	0.63
	OLMo-3-32B	1.00	0.75	0.41	1.00	1.00	1.00	0.62
	gpt-oss-20b	1.00	0.64	0.35	1.00	1.00	1.00	0.59
	gpt-oss-120b	1.00	0.69	0.46	1.00	1.00	1.00	0.97
Suppress several keywords	Qwen3-8B	1.00	0.46	0.18	1.00	0.99	1.00	0.00
	Qwen3-32B	1.00	0.49	0.20	1.00	0.99	1.00	0.45
	gpt-oss-20b	1.00	0.30	0.10	1.00	0.99	1.00	0.41
	gpt-oss-120b	1.00	0.32	0.12	1.00	0.99	1.00	0.49

Regime assignment. Table 24 applies the operational definitions of §3 to every plain-channel cell: F is the share of traces compliant on the constraint's first native unit (the "first" column of Table 23, recomputed for every checkpoint), $S(20)$ and $S(50)$ are survival to words 20 and 50, $R = S(50)/F$ is the share of starters still compliant at word 50, and "median slip" is the median first-slip position among starters that slip (printed with ≥ 10 such traces). A cell is *never started* if $F < 0.05$; otherwise *no onset failure, leaks* if $F \geq 0.95$; otherwise *started and lost* if $R < 0.25$ and *minority onset, kept* if $R \geq 0.25$; the two-checkpoint string constraint is either never started or "start ok, end fails". The thresholds are choices, but the six main models' values leave a gap around each of them: $F \leq 0.02$ in every never-started cell against $F \geq 0.06$ in every started cell, and $R \leq 0.13$ in every lost cell against $R \geq 0.47$ in every kept cell. The "meow" cells of Qwen3 are started and lost under this rule ($F = 0.63$–0.74; at 32B $S(50) = 0.09$, so the 10% genuine adopters of §3 are the minority that keeps it), and the split of "meow" between onset and maintenance is window-dependent (App. Table 25).

Table 24: Operational regime assignment for every plain-channel cell (definitions above). R is printed only where $F \geq 0.01$; for the sentence-level constraint a first sentence can run past word 50, so $S(50)$ is not bounded by F there. Bold: the started-and-lost regime, which is not confined to gpt-oss-120b.

Constraint	Model	F	$S(20)$	$S(50)$	R	median slip	Regime
Uppercase	Qwen3-8B	0.00	0.00	0.00	–	–	never started
	Qwen3-32B	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B	0.00	0.00	0.00	–	–	never started
	OLMo-3-32B	0.00	0.00	0.00	–	–	never started
	gpt-oss-20b	0.00	0.00	0.00	–	–	never started
	gpt-oss-120b	0.50	0.03	0.01	0.03	2	**started and lost**
	Qwen3-4B	0.00	0.00	0.00	–	–	never started
	Qwen3-14B	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B base	0.14	0.00	0.00	0.02	2	**started and lost**
	OLMo-3-7B SFT	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B DPO	0.00	0.00	0.00	–	–	never started
Alternating case	Qwen3-8B	0.00	0.00	0.00	–	–	never started
	Qwen3-32B	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B	0.02	0.00	0.00	0.00	2	never started
	OLMo-3-32B	0.00	0.00	0.00	–	–	never started
	gpt-oss-20b	0.00	0.00	0.00	–	1	never started
	gpt-oss-120b	0.12	0.02	0.00	0.03	1	**started and lost**
	Qwen3-4B	0.00	0.00	0.00	–	–	never started
	Qwen3-14B	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B base	0.00	0.00	0.00	–	1	never started
	OLMo-3-7B SFT	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B DPO	0.00	0.00	0.00	–	–	never started
Opening/closing string	Qwen3-8B	0.00	0.00	0.00	–	–	never started
	Qwen3-32B	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B	0.00	0.00	0.00	–	–	never started
	OLMo-3-32B	0.00	0.00	0.00	–	–	never started
	gpt-oss-20b	1.00	1.00	0.98	0.99	351	start ok, end fails (two checkpoints)
	gpt-oss-120b	0.99	0.99	0.98	0.99	295	start ok, end fails (two checkpoints)
	OLMo-3-7B base	0.10	0.10	0.10	0.98	298	start ok, end fails (two checkpoints)
	OLMo-3-7B SFT	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B DPO	0.00	0.00	0.00	–	–	never started
End sentences with "safe"	Qwen3-8B	0.00	0.06	0.00	–	–	never started
	Qwen3-32B	0.00	0.10	0.00	–	–	never started
	OLMo-3-7B	0.00	0.35	0.00	–	–	never started
	OLMo-3-32B	0.00	0.25	0.00	–	–	never started
	gpt-oss-20b	0.00	0.18	0.01	–	–	never started
	gpt-oss-120b	0.00	0.22	0.01	–	–	never started
	OLMo-3-7B base	0.00	0.11	0.01	–	–	never started
	OLMo-3-7B SFT	0.00	0.22	0.00	–	–	never started
	OLMo-3-7B DPO	0.00	0.33	0.00	–	–	never started
Lowercase	Qwen3-8B	0.12	0.09	0.08	0.66	109	minority onset, kept
	Qwen3-32B	0.15	0.11	0.08	0.54	27	minority onset, kept
	OLMo-3-7B	0.75	0.07	0.00	0.00	3	**started and lost**
	OLMo-3-32B	0.00	0.00	0.00	–	–	never started
	gpt-oss-20b	0.01	0.00	0.00	0.25	–	never started
	gpt-oss-120b	0.73	0.06	0.00	0.00	8	**started and lost**
	Qwen3-4B	0.19	0.00	0.00	0.00	5	**started and lost**
	Qwen3-14B	0.02	0.01	0.01	0.38	6	never started
	OLMo-3-7B base	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B SFT	0.01	0.00	0.00	0.00	–	never started
	OLMo-3-7B DPO	0.22	0.02	0.00	0.00	5	**started and lost**
"meow" between words	Qwen3-8B	0.63	0.00	0.00	0.00	2	**started and lost**

(continued)

Constraint	Model	F	$S(20)$	$S(50)$	R	median slip	Regime
	Qwen3-32B	0.74	0.10	0.09	0.13	2	**started and lost**
	OLMo-3-7B	0.00	0.00	0.00	–	–	never started
	OLMo-3-32B	0.00	0.00	0.00	–	–	never started
	gpt-oss-20b	0.00	0.00	0.00	–	–	never started
	gpt-oss-120b	0.06	0.05	0.03	0.47	48	minority onset, kept
	OLMo-3-7B base	0.01	0.00	0.00	0.00	–	never started
	OLMo-3-7B SFT	0.00	0.00	0.00	–	–	never started
	OLMo-3-7B DPO	0.00	0.00	0.00	–	–	never started
Suppress one keyword	Qwen3-8B	1.00	0.76	0.53	0.53	51	no onset failure, leaks
	Qwen3-32B	1.00	0.86	0.64	0.64	67	no onset failure, leaks
	OLMo-3-7B	1.00	0.75	0.47	0.47	43	no onset failure, leaks
	OLMo-3-32B	1.00	0.75	0.41	0.41	40	no onset failure, leaks
	gpt-oss-20b	1.00	0.64	0.35	0.35	27	no onset failure, leaks
	gpt-oss-120b	1.00	0.69	0.46	0.46	32	no onset failure, leaks
	Qwen3-4B	1.00	0.73	0.45	0.45	38	no onset failure, leaks
	Qwen3-14B	1.00	0.80	0.53	0.53	54	no onset failure, leaks
	OLMo-3-7B base	1.00	0.68	0.42	0.42	30	no onset failure, leaks
	OLMo-3-7B SFT	1.00	0.76	0.49	0.49	44	no onset failure, leaks
	OLMo-3-7B DPO	1.00	0.73	0.49	0.49	45	no onset failure, leaks
Suppress several keywords	Qwen3-8B	1.00	0.46	0.18	0.18	18	no onset failure, leaks
	Qwen3-32B	1.00	0.49	0.20	0.20	19	no onset failure, leaks
	gpt-oss-20b	1.00	0.30	0.10	0.10	12	no onset failure, leaks
	gpt-oss-120b	1.00	0.32	0.12	0.12	13	no onset failure, leaks

Table 25: Shapley attributions (pp of binary score, 95% intervals from 1,000 question-clustered bootstrap resamples) under onset windows $w \in \{20, 1\}$, pooled ("–") or stratified by question-level tercile of trace length ("len.") or, for suppression, of the keyword-opportunity rate in the model's unconstrained traces ("opp."), with predicted and observed scores of the two conditions and the relative misfit $(\text{pred} - \text{actual})/\text{actual}$. The main text reads the pooled variant for lowercase and the length-stratified variant for suppression; the pooled model over-predicts the lower-scoring suppression condition by 59–155% and suppression in the external channel misfits at 4B and 8B under every stratification.

Constraint	w	strat.	onset	maintenance	exposure	A: pred / act.	B: pred / act.	misfit A / B (%)
Size: Qwen3 8B → 32B								
lowercase	20	–	+0.3 [-0.5, 1.3]	+0.2 [-1.2, 1.4]	+0.8 [0.5, 1.1]	1.9 / 2.6	3.2 / 3.8	-26 / -17
	20	len.	-0.1 [-1.4, 1.1]	+0.2 [-1.1, 1.7]	+1.0 [0.6, 1.6]	2.6 / 2.6	3.8 / 3.8	+0 / -2
	1	–	+0.5 [-0.3, 1.4]	-0.0 [-1.4, 1.3]	+0.8 [0.5, 1.1]	1.9 / 2.6	3.2 / 3.8	-26 / -17
	1	len.	+0.1 [-1.1, 1.2]	+0.1 [-1.2, 1.5]	+1.0 [0.6, 1.6]	2.6 / 2.6	3.8 / 3.8	+0 / -2
suppression	20	–	+0.8 [0.5, 1.2]	+5.4 [2.9, 8.5]	+2.3 [1.8, 2.9]	2.6 / 1.3	11.2 / 10.3	+96 / +8
	20	len.	+0.9 [0.5, 1.4]	+6.8 [3.9, 9.7]	+1.7 [1.1, 2.3]	1.4 / 1.3	10.7 / 10.3	+2 / +4
	20	opp.	+0.8 [0.5, 1.2]	+5.6 [3.2, 8.3]	+2.1 [1.6, 2.7]	2.4 / 1.3	10.8 / 10.3	+78 / +5
	1	–	+0.0 [0.0, 0.0]	+6.2 [3.7, 9.4]	+2.3 [1.8, 2.9]	2.6 / 1.3	11.2 / 10.3	+96 / +8
	1	len.	+0.0 [0.0, 0.0]	+7.6 [4.6, 10.8]	+1.7 [1.2, 2.4]	1.4 / 1.3	10.7 / 10.3	+2 / +4
	1	opp.	+0.0 [0.0, 0.0]	+6.3 [3.8, 9.2]	+2.1 [1.6, 2.7]	2.4 / 1.3	10.8 / 10.3	+78 / +5
meow	20	–	+7.2 [1.7, 9.0]	-2.7 [-3.6, 3.0]	+0.2 [0.1, 0.3]	0.1 / 0.1	4.8 / 5.3	+0 / -11
	20	len.	+4.2 [1.9, 5.3]	+0.6 [-0.3, 3.2]	+0.2 [0.0, 0.3]	0.1 / 0.1	5.1 / 5.3	+0 / -4
	1	–	+0.3 [0.1, 0.6]	+4.1 [2.5, 5.8]	+0.2 [0.1, 0.4]	0.1 / 0.1	4.8 / 5.3	+0 / -11
	1	len.	+0.3 [0.1, 0.6]	+4.4 [2.9, 6.1]	+0.2 [0.0, 0.5]	0.1 / 0.1	5.1 / 5.3	+0 / -4
Channel, Qwen3-4B								
lowercase	20	–	+28.5 [25.7, 30.8]	+28.5 [25.7, 30.8]	+0.7 [0.3, 1.1]	0.0 / 0.0	57.6 / 56.8	– / +1
	20	len.	+28.6 [25.8, 30.9]	+28.6 [25.8, 30.9]	+0.6 [0.3, 1.0]	0.0 / 0.0	57.8 / 56.8	– / +2
	1	–	+23.9 [21.6, 26.4]	+29.1 [24.9, 32.7]	+7.0 [6.1, 8.1]	0.0 / 0.0	60.1 / 56.8	– / +6
	1	len.	+23.6 [21.2, 26.1]	+30.6 [26.3, 34.2]	+6.0 [4.9, 7.1]	0.0 / 0.0	60.2 / 56.8	– / +6
suppression	20	–	-11.2 [-13.8, -8.9]	+5.5 [1.6, 9.6]	+25.5 [22.4, 28.7]	2.5 / 1.0	22.3 / 13.2	+155 / +70
	20	len.	-12.1 [-15.0, -9.7]	+7.3 [3.7, 11.4]	+24.9 [22.1, 27.9]	1.2 / 1.0	21.4 / 13.2	+22 / +62
	20	opp.	-11.3 [-13.8, -8.9]	+5.8 [2.2, 9.9]	+25.4 [22.3, 28.4]	2.2 / 1.0	22.2 / 13.2	+116 / +68
	1	–	-10.1 [-12.6, -8.1]	+3.6 [-0.1, 7.3]	+35.3 [32.1, 38.6]	2.5 / 1.0	31.3 / 13.2	+155 / +138
	1	len.	-11.0 [-13.6, -8.9]	+5.5 [2.2, 8.9]	+33.6 [30.6, 36.7]	1.2 / 1.0	29.3 / 13.2	+22 / +123
	1	opp.	-10.9 [-13.6, -8.8]	+4.6 [1.1, 8.3]	+34.0 [30.6, 37.2]	2.2 / 1.0	29.9 / 13.2	+116 / +127
Channel, Qwen3-8B								
lowercase	20	–	+47.4 [43.3, 51.5]	+12.9 [8.7, 17.0]	+14.8 [11.5, 19.1]	1.9 / 2.6	77.0 / 77.0	-26 / +0
	20	len.	+47.3 [43.2, 51.4]	+14.8 [10.5, 20.9]	+12.5 [9.4, 15.1]	2.7 / 2.6	77.3 / 77.0	+6 / +0
	1	–	+45.2 [41.6, 48.9]	+16.1 [11.0, 20.9]	+14.4 [11.1, 18.8]	1.9 / 2.6	77.6 / 77.0	-26 / +1
	1	len.	+44.7 [40.9, 48.2]	+18.5 [13.4, 24.5]	+12.2 [9.0, 14.9]	2.7 / 2.6	78.1 / 77.0	+6 / +1
suppression	20	–	-2.6 [-4.3, -1.1]	+11.3 [6.5, 16.1]	+22.5 [19.3, 25.9]	2.6 / 1.3	33.8 / 29.2	+96 / +16
	20	len.	-2.5 [-4.1, -0.9]	+12.9 [8.8, 17.1]	+22.3 [19.3, 25.2]	1.4 / 1.3	34.1 / 29.2	+7 / +17
	20	opp.	-2.9 [-4.5, -1.4]	+11.8 [6.7, 16.7]	+22.5 [19.2, 26.1]	2.3 / 1.3	33.6 / 29.2	+73 / +15
	1	–	-3.2 [-4.2, -2.2]	+11.3 [6.3, 16.2]	+25.9 [22.4, 29.4]	2.6 / 1.3	36.6 / 29.2	+96 / +25
	1	len.	-3.1 [-4.2, -2.2]	+13.0 [8.7, 17.6]	+25.6 [22.1, 28.7]	1.4 / 1.3	36.9 / 29.2	+7 / +26
	1	opp.	-3.5 [-4.7, -2.5]	+11.8 [6.6, 16.8]	+25.4 [21.8, 29.1]	2.3 / 1.3	36.0 / 29.2	+73 / +23
meow	20	–	+1.9 [0.3, 3.0]	-0.5 [-1.0, 1.3]	+0.1 [0.0, 0.1]	0.1 / 0.1	1.6 / 2.0	+0 / -20
	20	len.	+1.3 [0.4, 2.1]	+0.6 [0.2, 1.6]	+0.0 [0.0, 0.0]	0.1 / 0.1	2.0 / 2.0	+0 / +1
	1	–	-4.6 [-9.1, -1.6]	+4.9 [1.1, 10.3]	+0.9 [0.4, 1.6]	0.1 / 0.1	1.3 / 2.0	+0 / -34

(continued)

Constraint	w	strat.	onset	maintenance	exposure	A: pred / act.	B: pred / act.	misfit A / B (%)
	1	len.	-3.3 [-10.1, -1.1]	+3.4 [0.5, 12.0]	+0.8 [0.4, 1.3]	0.1 / 0.1	1.0 / 2.0	+0 / -51
Channel, Qwen3-14B								
lowercase	20	–	+65.2 [47.3, 82.6]	+17.8 [1.3, 35.0]	+6.4 [1.4, 13.2]	0.3 / 0.3	89.6 / 89.8	+0 / -0
	20	len.	+65.9 [46.4, 69.1]	+19.6 [16.7, 38.5]	+3.8 [1.1, 7.5]	0.3 / 0.3	89.7 / 89.8	+1 / -0
	1	–	+51.8 [43.0, 62.7]	+32.8 [21.4, 42.3]	+4.6 [1.2, 8.8]	0.3 / 0.3	89.6 / 89.8	+0 / -0
	1	len.	+51.6 [43.5, 63.7]	+35.0 [22.8, 43.7]	+2.8 [0.9, 5.6]	0.3 / 0.3	89.7 / 89.8	+1 / -0
suppression	20	–	+4.1 [2.8, 5.5]	+27.3 [21.9, 32.9]	+19.2 [15.9, 23.0]	5.0 / 3.2	55.6 / 56.0	+59 / -1
	20	len.	+4.3 [2.9, 5.8]	+29.5 [22.6, 36.5]	+18.9 [14.0, 24.8]	3.1 / 3.2	55.9 / 56.0	-1 / -0
	20	opp.	+4.2 [2.8, 5.7]	+29.4 [24.1, 34.9]	+17.7 [14.5, 21.4]	4.5 / 3.2	55.9 / 56.0	+43 / -0
	1	–	-0.1 [-0.3, 0.0]	+31.6 [25.6, 37.7]	+19.2 [15.7, 23.1]	5.0 / 3.2	55.7 / 56.0	+59 / -1
	1	len.	-0.1 [-0.4, 0.0]	+34.1 [26.5, 41.8]	+18.8 [13.7, 24.9]	3.1 / 3.2	55.9 / 56.0	-1 / -0
	1	opp.	-0.1 [-0.3, 0.0]	+33.9 [28.2, 40.1]	+17.6 [14.2, 21.4]	4.5 / 3.2	56.0 / 56.0	+43 / -0
Channel, Qwen3-32B								
lowercase	20	–	+55.0 [50.1, 60.5]	+20.2 [14.8, 25.7]	+8.7 [6.4, 11.1]	3.2 / 3.8	87.0 / 86.8	-17 / +0
	20	len.	+55.0 [49.7, 61.8]	+20.2 [13.6, 26.4]	+8.6 [5.7, 11.1]	3.3 / 3.8	87.1 / 86.8	-13 / +0
	1	–	+49.4 [45.2, 54.4]	+26.8 [21.3, 31.9]	+7.7 [5.6, 10.0]	3.2 / 3.8	87.1 / 86.8	-17 / +0
	1	len.	+49.3 [45.0, 55.0]	+27.1 [20.7, 32.6]	+7.5 [5.0, 9.8]	3.3 / 3.8	87.2 / 86.8	-13 / +0
suppression	20	–	+3.6 [2.0, 5.3]	+38.4 [33.1, 43.8]	+19.2 [16.3, 22.1]	11.2 / 10.3	72.4 / 72.2	+8 / +0
	20	len.	+4.0 [2.3, 5.9]	+41.8 [37.0, 46.6]	+16.3 [14.0, 18.5]	10.6 / 10.3	72.7 / 72.2	+3 / +1
	20	opp.	+3.6 [2.0, 5.4]	+39.9 [34.5, 45.3]	+18.1 [15.4, 21.3]	10.8 / 10.3	72.4 / 72.2	+4 / +0
	1	–	-0.4 [-0.9, -0.1]	+42.7 [37.2, 48.3]	+19.1 [16.1, 22.1]	11.2 / 10.3	72.5 / 72.2	+8 / +0
	1	len.	-0.5 [-1.0, -0.1]	+46.6 [41.5, 51.7]	+16.0 [13.8, 18.3]	10.6 / 10.3	72.8 / 72.2	+3 / +1
	1	opp.	-0.5 [-0.9, -0.1]	+44.2 [38.4, 49.8]	+17.9 [15.2, 21.2]	10.8 / 10.3	72.4 / 72.2	+4 / +0
meow	20	–	+55.7 [49.8, 61.8]	+7.5 [2.0, 13.0]	+8.0 [5.2, 11.7]	4.8 / 5.3	75.9 / 76.2	-11 / -0
	20	len.	+55.1 [49.7, 62.1]	+6.3 [0.9, 13.0]	+9.3 [4.3, 11.1]	5.3 / 5.3	76.0 / 76.2	-0 / -0
	1	–	+8.9 [6.8, 10.9]	+56.2 [50.4, 61.6]	+6.0 [3.3, 10.4]	4.8 / 5.3	75.9 / 76.2	-11 / -0
	1	len.	+9.0 [7.1, 11.2]	+53.6 [50.2, 61.6]	+8.1 [2.3, 9.5]	5.3 / 5.3	76.0 / 76.2	-0 / -0

Table 26: Is a never-started trace compliant apart from its opener? Left: mean share of alphabetic words that satisfy the case constraint in unconstrained baseline traces (150 per model) and in constrained traces, and the share of constrained traces in which more than half of the words comply. Right: adoption rate when the grader skips the first word or the first sentence.

		Share of compliant words			π ($w = 20$) when grading starts at		
Constraint	Model	no constraint	constrained	traces > 0.5	word 0	word 1	sentence 2
Uppercase	Qwen3-8B	0.05	0.05	0.00	0.00	0.00	0.00
	Qwen3-32B	0.06	0.05	0.00	0.00	0.00	0.00
	OLMo-3-7B	0.04	0.05	0.00	0.00	0.00	0.00
	OLMo-3-32B	0.05	0.05	0.00	0.00	0.00	0.00
	gpt-oss-20b	0.08	0.08	0.00	0.00	0.00	0.00
	gpt-oss-120b	0.08	0.12	0.03	0.03	0.03	0.02
Lowercase	Qwen3-8B	0.83	0.84	1.00	0.09	0.12	0.09
	Qwen3-32B	0.82	0.85	1.00	0.11	0.12	0.10
	OLMo-3-7B	0.85	0.85	1.00	0.07	0.07	0.00
	OLMo-3-32B	0.83	0.83	1.00	0.00	0.04	0.00
	gpt-oss-20b	0.76	0.75	0.97	0.00	0.05	0.00
	gpt-oss-120b	0.76	0.77	0.97	0.06	0.07	0.01
Alternating case	Qwen3-8B	0.13	0.14	0.00	0.00	0.00	0.00
	Qwen3-32B	0.14	0.15	0.02	0.00	0.01	0.01
	OLMo-3-7B	0.13	0.14	0.01	0.00	0.00	0.00
	OLMo-3-32B	0.14	0.14	0.00	0.00	0.00	0.00
	gpt-oss-20b	0.18	0.20	0.05	0.00	0.00	0.00
	gpt-oss-120b	0.17	0.25	0.07	0.02	0.02	0.01

Grader variants. Masking mathematical notation, units and code in the case graders moves Qwen3-8B lowercase from 2.8% to 5.0% and leaves uppercase at 0. Dropping synonym lists moves suppression from 1.3% to 2.3%. The quantitative-domain gap on case constraints narrows under masking but onset failure is 94–99% in both domain groups.

External-channel parsing. Under case constraints Qwen3-32B restyles the tag itself (`<output_rEaSoNiNg>`); a case-sensitive parser drops 43% (uppercase) and 73% (alternating) of its external-CoT traces and understates uppercase control (25% vs. 60%). We parse case-insensitively.

Sanity. Unconstrained accuracy on the subset is 32% for Qwen3-8B with 9% of traces truncated; constrained traces are shorter and less often truncated (App. Table 17 gives median lengths and accuracy for all six models).

C THE PREFIX INTERVENTION IN DETAIL

This section gives the full account of the dose–response, no-instruction control and prompt-only arms summarised in §4.

Implementation. The prompt is the released CoT-CONTROL prompt for the constraint (system and user messages unchanged), rendered with the model's own chat template with thinking enabled. The prefix is the first K whitespace-separated words of the model's *own* unconstrained (baseline) trace for the same question (sample 0), rewritten by `str.upper`, `str.lower` or an alternating-case transform that restarts at each word and begins with upper case ("OkAy, LeT mE"); the rewritten prefix passes the released grader. For $K = 1$ the prefix is the opener alone: "OKAY," / "okay," for Qwen3 and OLMo-3 and "WE" / "we" for gpt-oss, whose habitual first word is "We". Qwen3 and OLMo-3 are prefilled after `<think>\n` (the prefix followed by one space); gpt-oss inside its analysis channel, `<|channel|>analysis<|message|>` followed by the prefix. The saved and graded "reasoning" is the continuation only, and the word clock starts at its first word. For the base and RL-Zero checkpoints (no chat template) the prompt is the plain task template of Chen et al. (2026)'s Appendix E with the constraint appended, the prefix is appended to that prompt, generation stops at the template's stop strings, and the graded trace is the first 90% of the completion, with completions under 20 tokens dropped and without their LLM validity filter. The no-instruction control uses the unconstrained prompt with the same prefix. Throughout, a "word" for the word clock is a whitespace token; the case graders evaluate every token containing a letter (alternating case: every run of ASCII letters), and a violation is positioned at the whitespace token that contains it. Sampling is as in the plain run (temperature 0.6, top-p 0.95, 2 samples per prompt).

Dose–response. We varied the prefix from one word to one hundred (Tables 10, 11). $K = 1$ replaces nothing but the opener: the reasoning is prefilled with "OKAY," (or "okay,") and the model continues. For the near-default style one token is enough at both sizes: with "okay," prefilled, lowercase adoption is 0.73 in Qwen3-8B and 0.73 in Qwen3-32B, as high as with 20 words, and 14% and 26% of traces stay in lowercase to the end (plain: 2.8% and 4.2%). For uppercase the answer depends on the model. In OLMo-3-7B-Think neither style is helped by the opener alone (uppercase $\pi = 0.01$, lowercase 0.11 against 0.07 in the plain run), five words give 0.13 and 0.11, twenty give only 0.27 and 0.22, and a hundred 0.24 and 0.65: this model has the least style momentum of the four at every dose, and for uppercase no dose helps. OLMo-3-32B-Think is the mirror image of Qwen3-8B: the single token "OKAY," already gives uppercase $\pi = 0.85$, as much as twenty words (0.82), while "okay," gives lowercase only 0.14 (twenty words: 0.72). We had predicted $\pi(K{=}1) < 0.3$ for uppercase in this model and were wrong. Which style one token can launch is therefore a property of the model, not of the style's distance from the default. gpt-oss is the extreme case at both sizes: no prefix length helps ($\pi \leq 0.11$ at $K \in \{1, 5, 20, 100\}$ for both styles and both models; common-window hazards 37–174 per 1,000 words where they can be estimated; no control trace stays in style), so this family has neither momentum nor, inside its reasoning channel, an instruction effect on maintenance. In Qwen3-8B the opener alone does almost nothing ($\pi = 0.05$; 87% of continuations leave uppercase at the very next word), while five words suffice ($\pi = 0.81$, as at $K = 20$). In Qwen3-32B the single token "OKAY," yields $\pi = 0.59$ and a fully uppercase trace in 26% of cases, against 0% without it, and five words give 0.81 and 34%; across the four Qwen3 sizes the one-token effect is monotone (uppercase π 0.00, 0.05, 0.47 and 0.59 at 4B, 8B, 14B, 32B), and at 4B even "okay," is not enough for lowercase (0.01; twenty words 0.10, a hundred 0.74); adoption is monotone in K at both sizes, and the common-window hazard is flat in K at 32B (uppercase 3.1–3.7 per 1,000 words for $K \in \{1, 5, 20\}$) but not at 8B, where it rises from 13.5 at $K = 5$ to 18.5 at $K = 20$ for uppercase (paired ratio 1.37 [1.18, 1.60]) and falls from 8.5 to 5.2 for lowercase (0.61 [0.48, 0.75]); the pre-registered prediction that λ does not depend on K for $K \leq 20$ is refuted at 8B and holds at 32B (App. A). We had predicted that one token would not be enough ($\pi(K{=}1) < \frac{1}{2}\pi(K{=}20)$); this holds for uppercase at 8B and is refuted for lowercase at both sizes and for uppercase at 32B. So the statement "one token decides the score" is false for the

small model and a far-from-default style, and close to literally true for the larger model: what the benchmark records as a 0% ability is, in Qwen3-32B, one token away from 26%.

Instruction following or context continuation? Without any instruction, Qwen3-8B abandons a 100-word uppercase prefix quickly ($C_{100} = 0.06$ vs. 0.20 instructed; slip rate ratio 2.1), so there the gain is instruction following: the constraint *is* available inside the reasoning channel once the trace has started correctly. With the shorter 20-word prefix the picture at 8B is starker: without the instruction C_{100} is 0.02 (uppercase) and 0.04 (lowercase) against 0.17 and 0.45 with it, and no control trace stays in style to the end (Tables 10, 11). Qwen3-32B is different: with the 100-word prefix the control retains 85% of the instructed arm's C_{100} (0.65 vs. 0.77) and 28% of control traces are uppercase throughout; for lowercase the ratio is 73% (0.63 vs. 0.86; 16% fully compliant). The share carried by continuation grows with the length of the compliant context: with 20 words the ratios are 58% (uppercase) and 33% (lowercase), still several times the 0.10 of Qwen3-8B, and 16.5% of uppercase control traces remain in style to the end. Within Qwen3 the momentum appears between 14B and 32B: the 20-word uppercase control ratio is 0.10, 0.09 and 0.58 at 8B, 14B and 32B (undefined at 4B, where $C_{100} = 0$ in both arms; lowercase 0.09, 0.10, 0.17 and 0.33 at 4B–32B), while adoption under instruction rises smoothly (0.09, 0.77, 0.81 and 0.92). OLMo-3-32B behaves like the small models here (20-word ratios 0.06 and 0.14; 100-word 0.34 and 0.54; we had predicted > 0.5), and OLMo-3-7B has no measurable momentum at all (20-word ratios 0.00 and 0.08; no control trace stays in style for 100 words): context momentum at 32B is a Qwen3 property, not a scale property. The style of a reasoning trace is thus set by how it opens and carried by a momentum that grows with scale in one family; the instruction lowers the slip rate by a factor of 1.4–7.6 in the 21 cells whose interval excludes 1 and has no detectable effect in Qwen3-4B (uppercase), gpt-oss-20b (both styles), gpt-oss-120b (both styles), the OLMo-3-7B base model (uppercase) and RL-Zero-General (uppercase) (0.43 [0.16, 1.89] for gpt-oss-120b uppercase, $K = 20$; 0.76 [0.48, 3.70] for gpt-oss-120b lowercase, $K = 20$; 1.01 [0.77, 1.35] for the OLMo-3-7B base model uppercase, $K = 20$; 1.20 [0.77, 1.88] for RL-Zero-General uppercase, $K = 20$; 1.25 [0.88, 1.90] for Qwen3-4B uppercase, $K = 20$; 1.29 [0.92, 1.74] for gpt-oss-20b uppercase, $K = 20$; 1.67 [0.70, 3.84] for gpt-oss-20b lowercase, $K = 20$; Table 9); the CoT-CONTROL instruction as written leaves the habitual opener token in place in every Qwen3 and OLMo-3 model and changes at most its case (App. E), but a more specific one can move it (next paragraph).

Can a prompt alone move the opener? The prefix needs prefill access, which API users of closed models lack, so we asked whether the opening can be moved from the user prompt. Two variants of the CoT-CONTROL prompt were run (App. A, E11): *hint* appends "Begin your reasoning with the word 'OKAY,' written exactly like that, and keep that style"; *demo* appends a 28-word compliant example opening. We predicted that neither would change the first word in more than 20% of Qwen3-8B traces. The prediction was refuted for the near-default style and supported for the far-from-default one (Tables 10, 11). With the hint, 80% of Qwen3-8B lowercase traces open with "okay,", π rises from 0.09 to 0.68, and 29.0% of traces stay in lowercase to the end—more than the 20-word prefill achieves (12.8%), because the instruction is then also followed. The demo moves the lowercase opener in 44% of traces (19.8% binary). For uppercase the hint moves the opener in 21% of traces but π stays at 0.07 and the binary score at 4.5%; the demo changes nothing (0.0% of openers). gpt-oss obeys the hint to the letter at both sizes—100%, 100%, 98% and 98.5% of traces open "OKAY," or "okay,"—and abandons the style within a sentence ($\pi = 0.00$ and 0.14 at twenty words for 20B, 0.39 and 0.20 for 120B; binary 0.0–2.8%). The demo prompt does more for the 120B model: 98% of its uppercase traces are still uppercase at word 20, against 3% with the benchmark's prompt and 6% with a 20-word prefill, but C_{100} is 0.11 and 4.3% finish in uppercase (hazard 27 per 1,000 words). Its opener is fully movable and its maintenance is nil, the mirror image of the never-started regime. Qwen3-32B, OLMo-3-7B-Think and OLMo-3-32B-Think, in contrast, ignore the hint: 600, 597 and 600 of 600 uppercase traces and 598, 596 and 600 of 600 lowercase traces still open "Okay," (Qwen3-32B binary 0.3%); the demo moves Qwen3-32B's lowercase opener in 14% of traces (8.5% binary, from 4.2%) and its uppercase opener in 0.0%. So the opener is not immovable, but what moves it is model-specific: for a style one token away from the default, a sentence in the user prompt turns a 2.8% score into 29.0% in Qwen3-8B and leaves Qwen3-32B at 0.3%, while a one-token prefill moves both. With four Qwen3 sizes the hint's effect is not a size trend but an idiosyncrasy of one checkpoint: it moves the lowercase opener in 11.5%, 80%, 0%, 0.3% of traces at 4B, 8B, 14B and 32B, and the uppercase opener only at 8B (21%); the demo prompt moves nothing at 14B either (0.0% of lowercase openers). The plain-run lowercase onset is

just as irregular across sizes (0.00, 0.09, 0.01 and 0.11 at 4B, 8B, 14B, 32B), so what moves with size is maintenance after a start, not the start itself. A benchmark score of 0–4% for this constraint is compatible with a model whose opener a sentence can move and with one whose opener nothing but the context can move.

D WHAT A KEYWORD MONITOR WOULD SEE

Suppression is the constraint closest to hiding content, so we ask how much is hidden against the baseline the benchmark does not report: *unconstrained* traces of the same questions, graded with the same keyword lists (App. Table 17). Unconstrained traces already go 100 words without the keyword 10–25% of the time, because the word has not come up yet; the instruction raises this by 3–7 pp in four models (to 20–28%), by 25 pp in Qwen3-32B (to 45%) and by 19 pp in gpt-oss-120b (to 29%); mentions fall by 11–20% in the four and by 33% and 34% in the two largest models, and the median trace still names the forbidden concept 24–30 times in Qwen3-8B and OLMo-3 (9 in Qwen3-32B; 8 and 4 in gpt-oss, whose traces are short). A monitor that looks for the concept is not evaded in any practical sense by any of the six models; most of the early survival in Table 1 is the natural delay before the word is needed, and the part that is control—the excess over the unconstrained baseline—is where the two largest models differ from the rest and the quantity we would track.

Does maintenance predict it? Table 27 computes this excess for every checkpoint with unconstrained and suppression traces and sets it against the two prefix-elicited quantities of §4: the uppercase hazard over words 20–100 after a 20-word prefix, and the instruction ratio $\lambda_{\text{no instr.}}/\lambda_{\text{instr.}}$ at $K = 20$. Across the 14 checkpoints with both quantities (effort variants and the 12k-token rerun are excluded as repeats of the same model), none of the three excess measures is associated with either prefix-elicited quantity: Spearman ρ between 0.20 and 0.36 with permutation $p \geq 0.23$ pooled and $p \geq 0.05$ within families, and where the point estimate is non-zero its sign is positive, i.e. checkpoints that maintain an imposed style *worse* hide marginally more. The 14 points are not exchangeable—7 are OLMo-3-7B checkpoints sharing one base model and 4 are Qwen3 sizes—so the within-family permutation, which holds the family composition fixed, is the relevant one. Its permutation group is small enough to enumerate (families of 4, 7, 1 and 2 checkpoints: $4! \cdot 7! \cdot 1! \cdot 2! = 241{,}920$ permutations), so the within-family p is exact; permuting within a singleton does nothing and within a pair only swaps, so the test effectively uses the 11 Qwen3 and OLMo-3-7B points, and with four families it can detect only a strong monotone relation. The closest to a positive result is mention drop against the instruction ratio ($\rho = 0.31$, exact within-family $p = 0.05$); the two variables also come from different constraints (an uppercase prefix quantity against a suppression quantity that depends on baseline keyword frequency and trace length; gpt-oss traces are several times shorter). A like-for-like maintenance measure for the same constraint, the plain-run suppression hazard on words 20–100, is strongly and negatively associated with the excess (ρ -0.75 to -0.58 over the three excess measures, within-family $p \leq 0.009$): checkpoints that slip less per word under suppression hide more. Computed from the same traces this is close to tautological, so we also split the questions in half and computed the hazard on one half and the excess on the other: the relation survives, weakened ($\rho = -0.56$, $p = 0.04$ pooled, $p = 0.04$ within families), so within the suppression constraint how well a model maintains does predict how much it hides. The question the proxy was built to ask is whether maintenance measured on a *different*, imposed constraint transfers to it, and it does not detectably. Qwen3-32B and gpt-oss-120b (largest excess) have the best and the worst prefix-elicited maintenance in the set, and the OLMo-3 base and RL-Zero checkpoints (best maintenance) show no excess. With 4 families the test can detect only a strong monotone relation, so this is a null, not evidence of independence.

Table 27: Within-paper monitor proxy. Excess of the suppression arm over the unconstrained baseline of the same questions in the share of traces with no keyword in the first 100 words (pp) and in mentions per 1,000 words (%), against the prefix-elicited uppercase hazard ($h_{20\text{–}100}$ after a 20-word prefix), the instruction ratio $\lambda_{\text{no instr.}}/\lambda_{\text{instr.}}$ at $K = 20$, and the like-for-like plain-run suppression hazard on words 20–100 (families: Qwen3 $\times$4, OLMo-3-7B $\times$7, OLMo-3-32B $\times$1, gpt-oss $\times$2). Spearman correlations across checkpoints with two permutation p-values: pooled (20,000 random permutations, treating the checkpoints as exchangeable) and within family (exact, by enumerating all permutations within families). Last row: hazard computed on one half of the questions and excess on the other half.

Checkpoint	excess none-100 (pp)	mention drop (%)	prefix-20 upper. $h_{20\text{–}100}$	instr. ratio	plain supp. $h_{20\text{–}100}$
gpt-oss-120b	+19.0	+34	87.7	0.43	11.8
gpt-oss-20b	+6.0	+20	50.2	1.29	16.2
OLMo-3-32B	+3.8	+12	10.2	4.37	16.0
OLMo-3-7B base	-1.8	-3	5.5	1.01	16.1
OLMo-3-7B RL-Zero-Code	-0.2	-6	5.4	1.44	15.3
OLMo-3-7B RL-Zero-General	+2.2	-6	16.3	1.20	13.9
OLMo-3-7B RL-Zero-Math	-2.5	+1	3.8	1.48	16.7
OLMo-3-7B	+2.7	+11	46.5	1.63	13.5
OLMo-3-7B DPO	+3.7	+11	42.5	–	13.1
OLMo-3-7B SFT	+1.0	+6	35.9	1.55	14.5
Qwen3-14B	+14.5	+23	7.9	6.48	11.5
Qwen3-32B	+25.3	+33	3.6	2.15	8.5
Qwen3-4B	+0.7	+9	75.0	1.25	14.6
Qwen3-8B	+6.9	+18	18.5	3.18	12.7

y (excess measure)	x (maintenance measure)	Spearman ρ	p pooled	p within family (exact)	n
excess none-in-100-w.	prefix-20 uppercase $h_{20\text{–}100}$	+0.20	0.49	0.57	14
excess none-in-100-w.	instruction ratio	+0.36	0.23	0.12	13
excess none-in-100-w.	plain suppression $h_{20\text{–}100}$	-0.75	0.003	< 0.001	14
mention drop	prefix-20 uppercase $h_{20\text{–}100}$	+0.28	0.33	0.52	14
mention drop	instruction ratio	+0.31	0.30	0.05	13
mention drop	plain suppression $h_{20\text{–}100}$	-0.59	0.03	0.008	14
excess none-in-500-w.	prefix-20 uppercase $h_{20\text{–}100}$	+0.22	0.46	0.62	14
excess none-in-500-w.	instruction ratio	+0.21	0.49	0.34	13
excess none-in-500-w.	plain suppression $h_{20\text{–}100}$	-0.58	0.03	0.009	14
excess none-in-100-w., half B (held out)	plain suppression $h_{20\text{–}100}$, half A of the questions	-0.56	0.04	0.04	14

E Discussion and limitations

What the safety case can and cannot lean on. For style and string constraints, "models cannot control their CoT" currently means "models do not start differently": one ingrained token decides the outcome. The benchmark's instruction leaves that token in place in every Qwen3 and OLMo-3 model (98%–100% of traces still open with "Okay"), changes only its case in OLMo-3-7B (lowercase, 75%) and Qwen3 (12–15%), and in gpt-oss-120b re-cases or replaces the opener in 50%–73% of traces; in none of these is a far-from-default style kept for twenty words. A one-sentence prompt addition moves it in Qwen3-8B for lowercase (2.8% $\rightarrow$ 29.0%) but not in Qwen3-32B, so 0–4% scores for that constraint measure how a model reads a prompt rather than what it can do. How much protection the opener offers depends on maintenance after a start, which the reported metric does not see: it varies 13-fold across the four main Qwen3 and OLMo-3 models, all of which score 0%, and grows with scale within Qwen3 and OLMo-3 but not in gpt-oss. At 7–8B and in OLMo-3-32B a far-from-default style collapses within a hundred words even when started correctly, so low controllability is robust to this intervention; at Qwen3-32B it is not. For a new model we therefore recommend, per constraint: (1) report π at $w = 20$ and the first-word onset next to the binary score; (2) if $\pi = 0$, run the $K = 20$ compliant-prefix arm with its no-instruction control and report $h_{20\text{–}100}$ and the control/instructed ratio; (3) if $\pi > 0$, report $h_{20\text{–}100}$ and C_L against the unconstrained baseline of the same questions, whose excess is the part that is control. A never-started model that keeps a prefix (Qwen3-32B) is one token away from a different score; one that starts and loses the style within a few words (gpt-oss-120b; OLMo-3-7B for lowercase) is not. That the prefix-elicited hazard is an early-warning quantity for monitor evasion is a *hypothesis* we do not test; we show only that it can change while the headline number stays at zero.

Control or continuation? What the prefix elicits is not purely controllability. The no-instruction arm shows that a model's tendency to continue the style of its context accounts for all of the effect

in the OLMo-3 base model, most of it in Qwen3-32B and the RL-Zero checkpoints (control ratios 75–76%), and less than half in Qwen3-8B, Qwen3-14B and OLMo-3-32B; where the instruction has a detectable effect it lowers the slip rate by a further 1.4–7.6-fold (§4). Both matter for monitoring: continuation means that a trace which starts in an unusual form—from a prefill, a fine-tune or the model's own earlier text—tends to stay there, more so at scale; the instruction effect is the part that corresponds to "the model can choose". We have not shown that either predicts evasion of a real CoT monitor, as Haskins et al. (2026) report for the binary score. Our one within-paper proxy is suppression, the only constraint models start: across 14 checkpoints from 4 families (7 of them OLMo-3-7B checkpoints), the excess over the unconstrained baseline in going 100 words without the keyword is associated neither with the prefix-elicited uppercase hazard (Spearman $\rho = 0.20$; permutation $p = 0.49$ pooled, $p = 0.57$ within families; the sign, if anything, points the wrong way) nor with the instruction ratio ($\rho = 0.36$, $p = 0.12$ within families; App. Table 27). The model's own suppression hazard does track it ($\rho = -0.75$, $p < 0.001$; $\rho = -0.56$ with hazard and excess computed on disjoint halves of the questions), so within one constraint maintenance predicts hiding; across constraints it does not detectably. With four families the transfer test (exact within-family permutation, App. D) detects only a strong monotone relation; its null is not evidence of independence, and which component carries the relation to obfuscation needs tasks we did not run.

Limitations. We study three open-weight families up to 120B on 300 questions; frontier models score up to 36% (Chen et al., 2026), and their regime is unknown. Scale trends outside Qwen3 rest on two sizes per family that also differ in recipe, and "larger is better maintained" fails in gpt-oss; OLMo-3 binary scores (4,096-token budget) are not comparable, although a 12,288-token rerun of OLMo-3-7B-Think reproduces its π and common-window hazards (App. Table 2, E12a). Kaplan–Meier estimates assume non-informative censoring, which natural trace end violates for suppression, so cross-model claims rest on the 20–100 window, where at most 3% of traces at risk have ended. The attribution assumes length–hazard independence within a stratum, misfits suppression in the external channel at 4B, is not identified when no trace adopts, and is window-dependent for "meow"; in the external channel 0–50% of traces are shorter than 20 words, so the 4B cells are not attributed (App. B). The channel attribution is Qwen3-only; we did not run the agentic or LLM-judged constraints of CoT-CONTROL, and the external-CoT baseline could not be run for OLMo-3-Think (with thinking disabled it still reasons in the open, without the requested tags).

F LENGTH AND REASONING EFFORT

Length. We expected the logistic regression with a linear length term used by Chen et al. (2026) to leave residual confounding. It does not: in simulations where covariates affect only trace length, their specification reports spurious effects in at most 3.7% of replications (App. G). Unadjusted group comparisons are a different matter—the same simulations show a -5.3 pp gap at a 13.8% base rate with no difference in C_{500}—and the comparisons by reasoning effort (their Fig. 9), RL training step (Figs. 10 and 19), dataset (Fig. 27) and difficulty bin (Fig. 28) in that paper are of this kind: group means of the binary score, where the groups also differ in reasoning length (their Fig. 33). The reported power law between score and length (exponent -0.37) is not what a constant hazard produces (-2.78 in simulation); gamma frailty with $\theta = 2.7$ produces -0.33. Within-cell frailty in our data is 0.5–1.1, so the pooled exponent most likely reflects mixing of constraint types and models.

Reasoning effort. Chen et al. (2026) report that controllability falls with reasoning effort (their Fig. 9). gpt-oss exposes effort as a chat-template setting, so the same model can be run at three levels on the same questions (App. Table 12). For gpt-oss-20b the median trace grows from 76 to 396 to 1,806 words from low to high effort, and the suppression score falls from 29.5% to 3.5% to 0.33%, an 88-fold drop. The first word complies in 1.00/1.00/1.00 of traces at every level and π for the case constraints stays ≤ 0.03, but the rest does move (Table 13): survival to word 20 is 0.58/0.64/0.70 (high−low +0.12 [+0.06, +0.18]), and the common-window hazard on words 20–100 is 12.3/16.2/18.8 per 1,000 words (high/low ratio 1.53 [1.20, 1.97], medium/low 1.32 [1.06, 1.66]; on words 100–300 1.71 [0.91, 3.65]). Our pre-registered prediction that only length changes is therefore refuted for this model (App. A): more effort lengthens the trace, and it also raises the early per-word leak rate while slightly raising early survival, so the 88-fold drop is mostly, not only, exposure. gpt-oss-120b shows the same hazard increase (1.95 [1.53, 2.46]) with early survival unchanged (+0.02 [-0.04, +0.08]). The opening-string score drops from 13.7% to 0.2% because

its closing checkpoint sits at the end of the trace. The fixed-window hazard sees the part of the effort effect that is not exposure; the binary score cannot separate the two. gpt-oss-120b adds a second channel: from low to medium to high effort it *starts* in uppercase in 94%/50%/1% of traces, survives to word 20 in 25%/3%/0% and finishes 18.5%/1.0%/0.0% of its traces (median 52 words at low effort) in uppercase, while its suppression early survival moves little (0.70/0.69/0.72). In the one model that starts at all, effort therefore also lowers the willingness to start; in the model that never starts, it changes only length. A decomposition is needed to tell the two apart, and the binary score cannot.

G SIMULATION: WHAT EXPOSURE ALONE DOES

We simulate 4,000 traces per replication with constant (π, λ) and three binary covariates that shift only log-length, and apply (i) the logistic regression of Chen et al. (2026) with a z-scored linear length term and (ii) our estimators. Over 300 replications per cell ($\pi \in \{0.05, 0.3\}$, $\lambda \in \{0.5, 2, 8\}$ per 1,000 words), covariate odds ratios are 0.91–1.05 and "significant and negative" in at most 3.7% of replications; the exact conditional test of equal slip rates rejects in 3–7%; raw score gaps reach -5.3 pp while the C_{500} difference is 0.000 ± 0.001. Log–log slopes of score against length decile: constant hazard -2.78; onset mixtures -0.94 to -2.40; pure onset 0.00; gamma frailty ($\theta = 2.7$) -0.33.