POLICY-COUPLED PROMPT SAMPLING FOR EFFICIENT RL FINETUNING OF REASONING MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Reinforcement learning finetuning has become a key technique for improving the reasoning capabilities of large language models. Its efficiency, however, depends strongly on selecting partially solved prompts that provide informative reward variation under the current optimized policy. Existing predictive sampling methods reduce rollout-intensive filtering by modeling the solving state of each prompt by independent feedback, but overlook that all prompts states shift under the global evolving policy. This independence assumption can produce stale state estimates and delay the discovery of prompts that become learnable as training progresses. To address this limitation, we propose Policy-Coupled Sampling (PCS), which models prompt-solving trajectories as policy-conditioned transition systems. PCS retains prompt-specific Bayesian transition statistics while introducing a lightweight global policy state estimated online from existing rollout feedback. The shared policy-conditioned transition model captures how policy evolution affects prompt-solving transitions, allowing feedback from sampled prompts to refresh predictions for unsampled prompts through joint modeling of evolution across policy and prompts. Moreover, PCS derives a discovery signal from these policy-conditioned transitions to reduce discovery delay by prioritizing prompts whose predicted informativeness is higher under the current policy state than when last observed. This signal is combined with current predicted informativeness to prioritize prompts likely to have recently entered the learnable region despite lacking recent rollout feedback. Across three reasoning domains, PCS achieves the highest macro-average accuracy among baselines, including state-of-the-art predictive samplers, while rollout filtering requires 2.6–$4.6\times$ more rollouts. Further analyses support reduced discovery delay with little non-generation overhead.

1 INTRODUCTION

Reinforcement learning (RL) finetuning with verifiable rewards has emerged as a crucial technique for improving the reasoning capabilities of large language models (LLMs), directly optimizing the language-model policy using feedback from generated rollouts (Lightman et al., 2024; Jaech et al., 2024; Guo et al., 2025; Team et al., 2025). By training on task prompts and self-generated rollouts, this paradigm has produced large reasoning models with strong performance in mathematical reasoning and program synthesis (Luo et al., 2025b;a). However, its effectiveness and efficiency depend heavily on selecting prompts that are informative under policy optimization progress (Guo et al., 2025; Yang et al., 2024). As the policy evolves across different stages of training, a prompt's solving status and informativeness may change; uniform prompt sampling may therefore allocate expensive rollouts to prompts that provide little effective optimization signal. Efficient RL finetuning therefore requires continually identifying and selecting prompts that remain informative for the evolving policy at its current stage of optimization.

This observation has motivated diverse online prompt selection methods that adapt the training distribution to the evolving policy, often prioritizing partially solved prompts that provide informative reward variation with higher scores. Dynamic Sampling (DS) (Yu et al., 2026) selects prompts with non-uniform rewards from candidate rollouts, whereas History Resampling (HR) (Zhang et al., 2025) uses past outcomes to avoid repeatedly sampling fully solved prompts. Related online difficulty filtering (Bae et al., 2026) likewise prioritizes prompts of intermediate difficulty, but candidate evaluation can incur substantial generation costs for long reasoning trajectories. To reduce

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

this candidate evaluation overhead, predictive methods, including Model Predictive Prompt Selection (MoPPS) (Qu et al., 2026a) and Dynamics-Predictive Sampling (DPS) (Mao et al., 2026), estimate prompt informativeness from historical rollout feedback before generation. Beyond prompt-local prediction, BOTS (Shen et al., 2026), GPS (Qu et al., 2026b), and LEEPS (Liang et al., 2026) exploit information shared across prompts to improve difficulty estimation and guide exploration. Nevertheless, the prompt-only estimates underlying these selection scores may become stale as the policy evolves and updates, particularly for prompts that have not been evaluated recently.

Specifically, policy evolution may change informativeness of prompts outside sampled batch. When prompt-state estimates lag behind these changes, prompts that transition from unsolved to partially solved may continue to receive low sampling priority. Such stale estimates can produce a discovery delay, postponing the selection of prompts that have become informative under the current policy. Low sampling priority further limits opportunities to collect updated feedback, potentially prolonging this delay. Conversely, prompts that transition to the fully solved state may retain high estimated utility and consume rollouts with limited training benefit. These stale estimates and resulting discovery delay motivate a policy-coupled model for prompt-state estimation, which conditions prompt-state transitions on shared policy evolution while retaining prompt learning histories.

To this end, we propose Policy-Coupled Sampling (PCS), which models prompt-solving trajectories as state-transition processes coupled through a shared policy context. PCS uses prompt-specific Bayesian hidden Markov model (HMM) to represent latent solving states and their temporal transitions, while introducing a lightweight global policy state estimated online from existing rollout statistics. The policy state summarizes the current curriculum stage using exponential moving averages of the mean success rate and the fraction of partially solved prompts, without additional LLM inference. A shared coupling tensor conditions each prompt's transition matrix on the policy state, allowing evidence from sampled prompts to update prompt-level belief estimates across the dataset. Moreover, the resulting policy-conditioned forecasts support a discovery signal that alleviates discovery delay. For each prompt, this signal contrasts its predicted probability of being partially solved under the current policy context with the corresponding forecast under its last-observed context. PCS combines this difference with current predicted informativeness to prioritize prompts whose utility may have increased since their last evaluation, promoting earlier discovery. All additional computation involves only low-dimensional matrix operations and requires no extra model rollouts.

Empirically, we evaluate PCS for Group Relative Policy Optimization (GRPO) (Shao et al., 2024) finetuning across competition mathematics, numerical planning, and visual geometric reasoning. Our primary configurations use DeepSeek-R1-Distill-Qwen-1.5B for MATH/AIME24, Qwen2.5-3B for Countdown/CD-34, and Qwen2.5-VL-3B-Instruct for Geometry3K; Qwen3.5-2B and Qwen3.5-4B provide validation on newer text and multimodal backbones. Under matched rollout budgets, PCS reaches 34.17%, 76.03%, and 44.75% Pass@1, yielding a 51.65% macro and 1.59% relative gain over the strongest baseline, with Qwen3.5 reaching 54.47%. Rollout-filtering DS uses 2.6–$4.6\times$ as many rollouts, whereas PCS requires no candidate-filtering rollouts. Across held-out benchmarks, PCS reaches mathematics averages of 52.63% and 63.65% and outperforms DPS on CD-34 and CD-4 at both scales. Prompt-state diagnostics show PCS has the highest State-2 F1 without extra rollouts across three tasks and retains 61% F1 after 200+ unobserved steps.

2 PRELIMINARIES

Group Relative Policy Optimization. Let $\mathcal{D}$ denote the training prompt dataset and $\pi_{\boldsymbol{\theta}}(\cdot \mid \tau)$ the response distribution for prompt τ over language-model policy $\pi_{\boldsymbol{\theta}}$, with parameter vector $\boldsymbol{\theta}$ in parameter space $\boldsymbol{\Theta}$. RL finetuning maximizes expected reward:

$$\max_{\boldsymbol{\theta}\in\boldsymbol{\Theta}} \mathbb{E}_{\tau\sim\mathcal{D},\, y\sim\pi_{\boldsymbol{\theta}}(\cdot|\tau)}\left[r(\tau, y)\right], \tag{1}$$

where $\tau \sim \mathcal{D}$ denotes empirical prompt sampling, y is a generated response, and $r(\tau, y)$ indicates verifiable outcome reward. Group Relative Policy Optimization (GRPO) (Shao et al., 2024) estimates advantages from groups of responses to the same prompt without learning a value model. At training step t, each prompt τ receives $k \geq 2$ responses $\{y^{\tau}_{t,m}\}_{m=1}^{k}$ sampled independently from the rollout policy π_{old}. Suppressing the training-step and prompt indices for brevity, GRPO maximizes

$$\mathcal{J}_{\text{GRPO}}(\boldsymbol{\theta}) = \mathbb{E}\left[\frac{1}{k}\sum_{m=1}^{k}\frac{1}{|y_m|}\sum_{u=1}^{|y_m|}\left(\min\left\{\omega_{m,u}\hat{A}_m, \text{clip}(\omega_{m,u}, 1-\epsilon_{\text{c}}, 1+\epsilon_{\text{c}})\hat{A}_m\right\} - \beta D_{\text{KL}}(\pi_{\boldsymbol{\theta}}\|\pi_{\text{ref}})\right)\right]. \tag{2}$$

where the expectation is over prompts and response groups sampled from π_{old}, $|y_m|$ is the length of response y_m, and u indexes its tokens. The token likelihood ratio is $\omega_{m,u} = \pi_{\boldsymbol{\theta}}(y_{m,u} \mid \tau, y_{m,<u})/\pi_{\text{old}}(y_{m,u} \mid \tau, y_{m,<u})$, where $y_{m,<u}$ denotes the preceding tokens. Here, $\text{clip}(\cdot, 1-\epsilon_{\text{c}}, 1+\epsilon_{\text{c}})$ bounds the likelihood ratio with threshold $\epsilon_{\text{c}} > 0$, while $D_{\text{KL}}(\pi_{\boldsymbol{\theta}} \| \pi_{\text{ref}})$ denotes the tokenwise KL divergence from the current policy to the fixed reference policy π_{ref}, weighted by $\beta \geq 0$. The group-relative advantage $\hat{A}_m$ normalizes the reward of y_m by subtracting the within-group mean and dividing by the within-group standard deviation. For zero-variance groups where $\hat{A}_m = 0$, yielding no reward-based policy-gradient and motivating informative prompt selection.

Online Prompt Selection. Online prompt selection adapts training distribution to prioritize partially solved prompts, whose response groups exhibit nonzero reward variance under current policy (Zhang et al., 2025; Chen et al., 2025). Dynamic Sampling (DS) (Yu et al., 2026) generates k responses for each prompt in a candidate pool $\widehat{\mathcal{B}}_t \subseteq \mathcal{D}$ and retains non-uniform reward prompts:

$$\mathcal{B}_t^{\text{DS}} = \left\{ \tau \in \widehat{\mathcal{B}}_t \;\middle|\; \text{std}\left(\{r(\tau, y_{t,m}^{\tau})\}_{m=1}^{k}\right) > 0 \right\}. \tag{3}$$

DS assembles a training batch $\mathcal{B}_t^{\text{DS}}$ of B retained prompts, generating further candidates when needed. Evaluating candidates incurs generation costs even for prompts excluded from the policy update. Predictive selection instead estimates informativeness from historical rollout feedback before generation. Given acquisition scores a_t^{τ} and a candidate pool containing at least B prompts, a common selection rule is

$$\mathcal{B}_t = \text{TopB}_{\tau \in \widehat{\mathcal{B}}_t} \{a_t^{\tau}\}, \tag{4}$$

where TopB returns B highest-scoring prompts, and $\widehat{\mathcal{B}}_t = \mathcal{D}$ gives full-dataset selection. Model Predictive Prompt Selection (MoPPS) (Qu et al., 2026a) constructs scores from Bayesian difficulty estimates, while Dynamics-Predictive Sampling (DPS) (Mao et al., 2026) uses a hidden Markov model (HMM) to estimate each prompt's probability for partially solved. With predictive framework, PCS couples prompt transition through a shared policy state, thereby capturing policy-driven shifts in prompt solvability and reducing discovery delay. Section A further discusses related work.

3 Policy-Coupled Sampling for RL Finetuning

PCS combines prompt-specific state memory with a shared policy context and coupling tensor to construct policy-conditioned prompt transitions (Section 3.1). Building on these transitions, PCS compares forecasts under current and stored policy contexts to enable discovery-aware selection of prompts whose informativeness may have changed (Section 3.2). Selected-prompt feedback then updates prompt-local belief states and shared policy-coupling components before propagating next-step beliefs across the dataset (Section 3.3). Finally, we describe coupling optimization objective and efficient implementation of the overall optimization procedure (Section 3.4). Figure 1 for overview.

3.1 Policy-Coupled Prompt-State Modeling

Prompt-State Representation. Each prompt $\tau \in \mathcal{D}$ has a latent solving state $z_t^{\tau} \in \{1, 2, 3\}$, representing fully unsolved, partially solved, and fully solved response groups, respectively. For a selected prompt, let $n_t^{\tau} = \sum_{m=1}^{k} r(\tau, y_{t,m}^{\tau})$ denote the verifiable reward among its k rollouts. The observed state x_t^{τ} equals 1, 2, or 3 when $n_t^{\tau} = 0$, $0 < n_t^{\tau} < k$, or $n_t^{\tau} = k$, respectively, and is unavailable when the prompt is not selected. State 2 therefore identifies prompts whose response groups contain reward variation and can provide an effective GRPO optimization signal.

Prompt-Local Bayesian Memory. Following DPS (Mao et al., 2026), PCS maintains for each prompt τ a predictive state belief $\boldsymbol{\mu}_t^{\tau,\text{prior}}$, a posterior state belief $\boldsymbol{\mu}_t^{\tau,\text{post}}$, and Dirichlet parameters $\boldsymbol{\alpha}_t^{\tau}(\cdot, j)$ governing transitions from source state j. Under HMM, the posterior records the belief after the latest observation, whereas the prior forecasts the state before selection. At initialization, $\boldsymbol{\mu}_0^{\tau,\text{post}}$ is the belief before any rollout feedback, $\boldsymbol{\mu}_1^{\tau,\text{prior}}$ is the first pre-selection forecast, and $\boldsymbol{\alpha}_0^{\tau} > 0$ provides positive transition pseudo-counts. The posterior-mean base transition is $\bar{\Phi}_t^{\tau}(i, j) = \alpha_t^{\tau}(i, j) / \sum_{l=1}^{3} \alpha_t^{\tau}(l, j)$, while $\mu_t^{\tau,\text{prior}}(i)$ gives the predicted probability of state i. DPS uses $\mu_t^{\tau,\text{prior}}(2)$ directly as its pre-generation informativeness score, treating each prompt's dynamics independently and relying only on its own observation history. Selected-prompt observations




Figure 1: **Overview of Policy-Coupled Sampling (PCS).** Prompt-specific Bayesian memories and shared policy-conditioned transitions produce forecasts for candidate prompts. Comparing forecasts under current and stored policy contexts yields a discovery signal for selection before generation. Selected-prompt rollouts support GRPO, update local memories, and train the shared evolution, closing the feedback loops without candidate-filtering rollouts.

update posterior and transition counts, whereas unselected prompts retain their beliefs and contribute no evidence; historical counts decay toward their priors (Section 3.3). In contrast, PCS retains $\bar{\mathbf{\Phi}}_t^\tau$ as prompt-local base but augments it with a shared policy-dependent adjustment that transfers evidence across prompts (Equation (5)), while caching latest policy context to define discovery signal.

Policy-Conditioned Transitions. PCS constructs a policy-coupled transition model by augmenting the prompt-specific Bayesian base transitions $\bar{\mathbf{\Phi}}_t^\tau$ with two shared components: a policy context $\boldsymbol{s}_t$ and a coupling tensor $\boldsymbol{W}_t$. The policy context $\boldsymbol{s}_t \in \mathbb{R}^2$ summarizes observed training progress through exponential moving averages of the selected-batch mean success rate and partially solved fraction. The coupling tensor $\boldsymbol{W}_t \in \mathbb{R}^{3\times3\times2}$ parameterizes how this context adjusts the Bayesian base transitions, with each vector $\boldsymbol{w}_{t,i,j} \in \mathbb{R}^2$ mapping context features to a logit adjustment for transition $j \to i$. Both components are updated online using existing rollout feedback from selected prompts (Section 3.3). For any context vector $\boldsymbol{s} \in \mathbb{R}^2$ and coupling tensor $\boldsymbol{W}_t$, let $L_t^\tau(i, j; \boldsymbol{s}, \boldsymbol{W}_t)$ denote the logit for transition $j \to i$, combining the Bayesian base with the shared policy adjustment:

$$L_t^\tau(i,j;\boldsymbol{s},\boldsymbol{W}_t) = \log\big(\bar{\Phi}_t^\tau(i,j)+\varepsilon\big) + \boldsymbol{w}_{t,i,j}^\top \boldsymbol{s}, \qquad \Phi_t^\tau(i,j \mid \boldsymbol{s};\boldsymbol{W}_t) = \frac{e^{L_t^\tau(i,j;\boldsymbol{s},\boldsymbol{W}_t)}}{\sum_{l=1}^3 e^{L_t^\tau(l,j;\boldsymbol{s},\boldsymbol{W}_t)}}. \quad (5)$$

Here, $\varepsilon > 0$ is a numerical stabilizer, and $\mathbf{\Phi}_t^\tau(\boldsymbol{s};\boldsymbol{W}_t)$ denotes the matrix with these entries. The unsubscripted $\boldsymbol{s}$ is a generic context argument, allowing evaluation under either the current context $\boldsymbol{s}_t$ or the context $\boldsymbol{s}_{\ell_t^\tau}$ cached at prompt τ's latest evaluation. We initialize $\boldsymbol{s}_1 = \mathbf{0}$ and $\boldsymbol{W}_0 = \mathbf{0}$, so the initial transition model depends only on the Bayesian base. At selection time in iteration t, PCS uses $\bar{\mathbf{\Phi}}_{t-1}^\tau$, $\boldsymbol{W}_{t-1}$, and $\boldsymbol{s}_t$, which summarizes feedback through iteration $t-1$. The policy-conditioned transition matrix maps $\boldsymbol{\mu}_{t-1}^{\tau,\mathrm{post}}$ to $\boldsymbol{\mu}_t^{\tau,\mathrm{prior}}$, whose State-2 probability estimates informativeness for selection. Shared context and coupling parameters capture common effects of policy evolution across prompts while preserving heterogeneous transitions encoded by Bayesian memory.

3.2 Discovery-Aware Prompt Selection

Policy-Conditioned Discovery Signal. To alleviate discovery delay, PCS derives a discovery signal from the policy-conditioned transition. Let ℓ_t^τ index the updated context cached after prompt τ's latest evaluation, with $\ell_1^\tau = 1$ and initial context $\boldsymbol{s}_1 = \mathbf{0}$. PCS compares one-step forecasts of the probability of being partially solved under the current context $\boldsymbol{s}_t$ and cached context $\boldsymbol{s}_{\ell_t^\tau}$ while

holding the local belief, base transition, and coupling tensor fixed:

$$\widetilde{\boldsymbol{\mu}}_{t+1}^{\tau}(\boldsymbol{s}) = \boldsymbol{\Phi}_{t-1}^{\tau}(\boldsymbol{s}; \boldsymbol{W}_{t-1})\boldsymbol{\mu}_t^{\tau,\mathrm{prior}}, \quad \Delta_t^{\tau} = \widetilde{\mu}_{t+1}^{\tau}(2; \boldsymbol{s}_t) - \widetilde{\mu}_{t+1}^{\tau}(2; \boldsymbol{s}_{\ell_t^{\tau}}). \tag{6}$$

The stored context serves as a reference within the current model, so the signal measures a predicted response to context changes. A positive Δ_t^{τ} indicates a higher predicted probability of partial solution under the current context and motivates earlier reevaluation of potentially informative prompts.

Prompt Selection with Discovery Signal. At iteration t, PCS scores every prompt in the candidate pool $\widehat{\mathcal{B}}_t$ by combining current predicted informativeness with the discovery signal and selects the B highest-scoring prompts for rollout:

$$a_t^{\tau} = \mu_t^{\tau,\mathrm{prior}}(2) + \gamma\Delta_t^{\tau}, \quad \mathcal{B}_t = \mathrm{TopB}_{\tau\in\widehat{\mathcal{B}}_t}\left\{a_t^{\tau}\right\}, \tag{7}$$

where $\gamma \geq 0$ controls the contribution of discovery. The first term prioritizes prompts already predicted to be informative through our policy-coupled system, while the second adjusts their selection priority using the policy-conditioned forecast difference. This online selection is performed before response generation and therefore requires no candidate-filtering rollouts. By translating policy-coupled forecasts into selection priorities, PCS promotes the discovery of prompts that may have become informative since their latest evaluation, helping alleviate discovery delay.

3.3 Online Policy-Coupled Belief Updates

Prompt-Specific State and Transition Updates. To update the prompt-local components of its policy-coupled transition model at each GRPO iteration, PCS reuses the selected-prompt rollout feedback already collected for policy optimization to revise state beliefs and transition statistics. For an observed prompt, deterministic emissions update the predictive prior to $\mu_t^{\tau,\mathrm{post}}(i) = \mathbb{I}(i = x_t^{\tau})$; an unobserved prompt retains $\boldsymbol{\mu}_t^{\tau,\mathrm{post}} = \boldsymbol{\mu}_t^{\tau,\mathrm{prior}}$. Combining the current posterior, preceding source-state belief, and Bayesian base transition gives expected counts $\xi_t^{\tau}(i,j) \propto \mu_t^{\tau,\mathrm{post}}(i)\mu_{t-1}^{\tau,\mathrm{post}}(j)\bar{\Phi}_{t-1}^{\tau}(i,j)$, normalized over (i,j). The Dirichlet parameters are updated as

$$\boldsymbol{\alpha}_t^{\tau} = \lambda\boldsymbol{\alpha}_{t-1}^{\tau} + (1-\lambda)\boldsymbol{\alpha}_0^{\tau} + \boldsymbol{\xi}_t^{\tau}, \qquad \lambda \in (0,1), \tag{8}$$

where λ controls historical retention. For unobserved prompts, $\boldsymbol{\xi}_t^{\tau} = \mathbf{0}$, so their transition parameters decay toward $\boldsymbol{\alpha}_0^{\tau}$. The resulting posterior and Bayesian base transition provide the local inputs to policy-conditioned prediction.

Shared Policy-Coupling Updates. PCS complements the prompt-specific Bayesian estimates with two shared quantities: the policy context $\boldsymbol{s}_t$, which summarizes selected-batch feedback, and the coupling tensor $\boldsymbol{W}_t$, which maps this context to transition adjustments. For each selected prompt $\tau \in \mathcal{B}_t$, let $c_t^{\tau} = n_t^{\tau}/k$ denote its observed success rate. We compute the batch mean success rate $\bar{r}_t = |\mathcal{B}_t|^{-1}\sum_{\tau\in\mathcal{B}_t} c_t^{\tau}$ and partially solved fraction $q_t = |\mathcal{B}_t|^{-1}\sum_{\tau\in\mathcal{B}_t}\mathbb{I}(0 < c_t^{\tau} < 1)$. The former summarizes batch performance, whereas the latter measures the prevalence of informative reward variation. Defining $\boldsymbol{o}_t \in \mathbb{R}^2$ as the current batch summary, PCS updates the policy context by

$$\boldsymbol{o}_t = [\bar{r}_t, q_t]^{\top}, \quad \boldsymbol{s}_{t+1} = \rho\boldsymbol{s}_t + (1-\rho)\boldsymbol{o}_t, \tag{9}$$

where $\rho \in [0,1)$ controls temporal smoothing. Because the observed transitions occur under the pre-rollout context $\boldsymbol{s}_t$, PCS uses this context to update $\boldsymbol{W}$ while holding the Bayesian bases $\bar{\boldsymbol{\Phi}}_{t-1}^{\tau}$ and source-state beliefs $\boldsymbol{\mu}_{t-1}^{\tau,\mathrm{post}}$ fixed. Let $\boldsymbol{g}_{t,i,j} \in \mathbb{R}^2$ denote the gradient of the batch-averaged coupling objective with respect to the coefficients for transition $j \to i$, evaluated at $\boldsymbol{W}_{t-1}$:

$$\boldsymbol{g}_{t,i,j} = \frac{1}{|\mathcal{B}_t|}\sum_{\tau\in\mathcal{B}_t}\mu_{t-1}^{\tau,\mathrm{post}}(j)\left[\Phi_{t-1}^{\tau}(i,j \mid \boldsymbol{s}_t; \boldsymbol{W}_{t-1}) - \mathbb{I}(i = x_t^{\tau})\right]\boldsymbol{s}_t. \tag{10}$$

The prediction residual is weighted by source-state uncertainty and attributed to the two context features; the corresponding objective is defined in Equation (13). PCS maintains an AdaGrad accumulator $\boldsymbol{G}_{t,i,j} \in \mathbb{R}^2$, initialized by $\boldsymbol{G}_{0,i,j} = \mathbf{0}$, and updates the coupling coefficients as

$$\boldsymbol{G}_{t,i,j} = \boldsymbol{G}_{t-1,i,j} + \boldsymbol{g}_{t,i,j}^{\odot 2}, \quad \boldsymbol{w}_{t,i,j} = \boldsymbol{w}_{t-1,i,j} - \eta_W\frac{\boldsymbol{g}_{t,i,j}}{\sqrt{\boldsymbol{G}_{t,i,j} + \varepsilon}}. \tag{11}$$

Here $\eta_W > 0$ is the coupling learning rate; $\boldsymbol{g}_{t,i,j}^{\odot 2}$ denotes elementwise squaring. The updated $\boldsymbol{W}_t$, together with $\boldsymbol{s}_{t+1}$, converts prompt-local transition evidence into a shared policy-level update via joint modeling, which is then propagated across prompts through policy-conditioned transitions.

Belief Propagation and Context Caching. After the local prompt and shared policy updates, PCS constructs the next-step prior for every prompt:

$$\boldsymbol{\mu}_{t+1}^{\tau,\text{prior}} = \boldsymbol{\Phi}_t^{\tau}(\boldsymbol{s}_{t+1}; \boldsymbol{W}_t)\boldsymbol{\mu}_t^{\tau,\text{post}}. \tag{12}$$

The transition matrix combines the updated Bayesian base $\bar{\boldsymbol{\Phi}}_t^{\tau}$, context $\boldsymbol{s}_{t+1}$, and coupling tensor $\boldsymbol{W}_t$. Selected prompts propagate from their observed states, whereas unselected prompts propagate their existing beliefs through the updated policy-conditioned transitions. Selected prompts cache $\boldsymbol{s}_{t+1}$ and set $\ell_{t+1}^{\tau} = t+1$; unselected prompts retain $\ell_{t+1}^{\tau} = \ell_t^{\tau}$. These priors and cached contexts support discovery-aware selection at iteration $t+1$, closing the online policy-coupled learning cycle.

3.4 Coupling Optimization and Algorithm Overview

Coupling Objective. The preceding online update requires an objective that learns how the shared policy context should modify the prompt-specific Bayesian transitions. For each selected prompt $\tau \in \mathcal{B}_t$, PCS treats the observed state x_t^{τ} as the destination and $\boldsymbol{\mu}_{t-1}^{\tau,\text{post}}$ as the belief over possible source states. Using the pre-rollout context $\boldsymbol{s}_t$, we define a source-belief-weighted cross-entropy loss and its batch average as:

$$\mathcal{L}_t^{\tau}(\boldsymbol{W}) = -\sum_{j=1}^{3} \mu_{t-1}^{\tau,\text{post}}(j) \log \Phi_{t-1}^{\tau}(x_t^{\tau}, j \mid \boldsymbol{s}_t; \boldsymbol{W}), \qquad \mathcal{L}_t(\boldsymbol{W}) = \frac{1}{|\mathcal{B}_t|} \sum_{\tau \in \mathcal{B}_t} \mathcal{L}_t^{\tau}(\boldsymbol{W}). \tag{13}$$

During this optimization, $\boldsymbol{W}$ is the only variable, while the pre-update Bayesian bases $\bar{\boldsymbol{\Phi}}_{t-1}^{\tau}$, source-state beliefs, and context $\boldsymbol{s}_t$ remain fixed. When the preceding state is known, its posterior is one-hot and only the corresponding transition column contributes; otherwise, the loss averages over plausible source states. Differentiating $\mathcal{L}_t(\boldsymbol{W})$ at $\boldsymbol{W}_{t-1}$ yields the gradient in Equation (10). Minimizing this objective allows transition evidence from selected prompts to train the shared policy-dependent adjustments used in policy-coupled prediction across the dataset.

Overall Procedure. The complete training loop is summarized in Algorithm 1. Each iteration selects prompts, collects their rollouts, applies GRPO, updates local and shared components, and propagates beliefs across the dataset. Coupling updates use the pre-update Bayesian bases, source-state beliefs, and policy context, while subsequent forecasts use the updated quantities. The updated policy context and coupling tensor jointly adjust each prompt's Bayesian base transitions for subsequent belief propagation. With fixed state and context dimensions, belief-propagation cost and persistent sampler storage scale linearly with $|\mathcal{D}|$. All sampler updates reuse existing rollout feedback and require no extra rollouts. Together, PCS combines prompt-specific memory with shared policy shift to track evolving informativeness and guide discovery-aware selection.

4 Experiments

We evaluate PCS along five dimensions. We first assess task-level Pass@1, three-task macro performance, and rollout efficiency under matched training budgets (Section 4.2). We then examine transfer to unseen datasets without target-data tuning (Section 4.3) and analyze prompt-state prediction, selection quality, and stale-prompt recovery (Section 4.4). Finally, component and temporal-placebo controls isolate the effects of coupling, broadcast, and discovery signal (Section 4.5). Together, these evaluations test whether PCS improves reasoning quality efficiently while better tracking policy-dependent prompt dynamics throughout training.

4.1 Experimental Setup

Tasks, models, and metrics. We evaluate PCS across competition mathematics, numerical planning, and visual geometric reasoning. Our primary task–model pairs are MATH/AIME24 (Hendrycks et al., 2021) with DeepSeek-R1-Distill-Qwen-1.5B (Guo et al., 2025), Countdown/CD-34 (Pan et al., 2025) with Qwen2.5-3B (Hui et al., 2024), and Geometry3K (Lu et al., 2021) with Qwen2.5-VL-3B-Instruct (Bai et al., 2025). For cross-backbone validation, we additionally evaluate PCS with Qwen3.5-2B on MATH and Countdown and Qwen3.5-4B on Geometry3K, preserving a comparable model scale while supporting multimodal reasoning (Team, 2026). All models are trained with GRPO (Shao et al., 2024) using `verl` (Sheng et al., 2025). We report

Table 1: **Main task/model-matched comparison and recent-backbone validation.** Scores are final Pass@1 (%), and R denotes training rollouts in thousands.

	MATH / AIME24		Countdown / CD-34		Geometry3K / Test		
Method	Score ↑	R ↓	Score ↑	R ↓	Score ↑	R ↓	Macro ↑
US	26.46	737	69.87	246	40.69	492	45.67
HR	28.13	737	70.19	246	40.44	492	46.25
DS	31.88	2,933	74.95	1,141	44.33	1,262	50.39
BOTS	21.50	737	69.90	246	41.00	492	44.13
DPS	32.71	737	74.27	246	44.47	492	50.48
MoPPS	32.92	737	74.46	246	45.15	492	50.84
PCS	34.17	737	76.03	246	44.75	492	51.65
PCS (Qwen3.5)	**36.84**	737	**78.58**	246	**47.98**	492	**54.47**




Figure 2: **Validation performance throughout RL finetuning.** Pass@1 is evaluated at intermediate checkpoints on AIME24 for MATH, CD-34 for Countdown, and the Geometry3K test set. Curves compare HR, DS, BOTS, DPS, and PCS; DS is the rollout-intensive baseline.

Pass@1 estimated from 16 sampled completions per evaluation prompt. Prediction quality is measured by State-2 F1 and three-state accuracy, while selection quality is measured by the effective sample ratio (ESR), defined as the fraction of selected prompts that are partially solved.

Baselines. To separate the effect of policy coupling from sampling budget, rollout filtering, and prompt-local prediction, we compare PCS against non-predictive, rollout-intensive, and predictive sampler families. US samples uniformly; HR removes prompts fully solved in the current epoch (Zhang et al., 2025); DS filters an enlarged rollout batch (Yu et al., 2026); and DPS predicts each prompt's solving state before rollout (Mao et al., 2026). We additionally compare against predictive MoPPS (Qu et al., 2026a) and Bayesian online task selection (BOTS) (Shen et al., 2026) using the same evaluation protocol. Complete dataset, model, sampler, checkpoint, and evaluation settings are provided in Sections C and E.

4.2 Performance and Rollout Efficiency

This comparison evaluates final reasoning quality across task families under matched rollout budgets rather than relying on a single benchmark. Under the primary task–model settings, PCS achieves the highest three-task macro in Table 1. Compared with DPS, PCS improves AIME24, CD-34, and Geometry3K by 1.46, 1.76, and 0.28 points, respectively. Compared with MoPPS, it gains 1.25 points on AIME24 and 1.57 points on CD-34, trails by 0.40 points on Geometry3K, and improves the macro by 0.81 points. The Qwen3.5 configuration improves all three task scores and raises the macro from 51.65% to 54.47%, providing additional evidence that the gains transfer across backbone families. PCS matches the rollout budgets of US, HR, MoPPS, and DPS, using 737k, 246k, and 492k rollouts on MATH, Countdown, and Geometry3K, respectively. DS requires 4.0×, 4.6×, and 2.6× more rollouts for candidate filtering while underperforming PCS on all three tasks. PCS instead ranks prompts before generation and shares policy-conditioned transition evidence without additional LLM rollouts. Generation-inclusive accounting, budget curves, runtime decomposition, and prompt-pool scaling are provided in Section H.

Figure 2 reveals trajectory-level differences not captured by the final scores. PCS improves steadily on Countdown and Geometry3K and continues to make late-stage progress on MATH, where HR and BOTS regress and DS is less stable. PCS remains competitive with or above DPS across the later checkpoints and finishes above it in all three panels, suggesting that the final gains are consistent with the observed late-stage performance trends.

Table 2: **Generalization evaluation.** Each entry gives smaller / larger model Pass@1 (%). Math Avg. averages the five mathematics benchmarks.

	MATH-trained DeepSeek-R1-Distill-Qwen (1.5B / 7B)						Countdown-trained Qwen2.5 (3B / 7B)	
Method	AIME24	AMC23	MATH500	Minerva	Olympiad	Math Avg.	CD-34	CD-4
Base	18.33/37.71	51.73/68.45	76.64/86.94	23.83/34.74	35.31/46.94	41.17/54.95	–/–	–/–
US	26.46/45.83	63.18/73.57	82.78/89.06	27.46/37.68	43.00/50.42	48.57/59.31	69.87/77.84	39.42/53.27
HR	28.13/46.46	64.61/75.98	82.88/90.01	27.37/37.94	43.15/51.50	49.23/60.38	70.19/78.15	42.10/54.54
DS	31.88/49.79	67.32/78.99	84.79/90.96	29.18/37.89	46.83/54.45	52.00/62.42	74.95/81.26	47.67/60.77
MoPPS	32.92/48.54	66.72/79.22	84.82/91.04	28.81/38.49	45.89/53.69	51.83/62.20	74.46/82.18	47.02/59.16
DPS	32.71/51.04	67.77/80.35	84.95/91.13	29.09/37.82	46.11/55.32	52.13/63.13	74.27/81.15	47.78/59.61
PCS (ours)	34.17/52.34	68.17/80.83	85.27/91.39	29.13/37.85	46.41/55.87	52.63/63.65	76.03/81.84	48.26/60.24




Figure 3: **Multi-baseline prompt-state prediction and failure analysis.** Panels (a)–(b) compare State-2 F1 and three-state accuracy; panel (c) reports ESR; panels (d)–(f) evaluate observation age, policy shift, and recovery cost across HR, DS, MoPPS, BOTS, DPS, and PCS.

4.3 Cross-Dataset Generalization

To evaluate generalization without target-specific adaptation, we test MATH-trained DeepSeek-R1-Distill-Qwen checkpoints (1.5B/7B) on AIME24, AMC23, MATH500, MinervaMath, and OlympiadBench (He et al., 2024). Countdown-trained Qwen2.5 checkpoints (3B/7B) are evaluated on held-out CD-34 and the harder CD-4 benchmark. No evaluation examples are used for RL training, sampler tuning, checkpoint selection, or prompt-template selection. In Table 2, PCS reaches mathematics averages of 52.63% and 63.65%, exceeding DPS by 0.50 and 0.52 percentage points, respectively. Its Countdown scores are $76.03\%/81.84\%$ on CD-34 and $48.26\%/60.24\%$ on CD-4, improving over DPS by $1.76/0.69$ and $0.48/0.63$ points, respectively. The gains over DPS are consistent across all reported targets and both model scales, although PCS remains below MoPPS on 7B MinervaMath and CD-34 and below DS on 7B CD-4. Overall, PCS shows consistent transfer gains over DPS without target-specific adaptation. Additional held-out targets, paired-seed robustness, and training-time transfer analyses are reported in Section F.

4.4 Prompt-State Prediction and Stale-Prompt Recovery

Prediction quality across samplers. We compare prompt-state prediction and the informativeness of selected prompts across samplers (Figure 3). In panel (a), PCS achieves State-2 F1 scores of 97%, 81%, and 87% on MATH, Countdown, and Geometry3K, respectively, outperforming DPS, BOTS, and MoPPS. Its improvements over DPS range from 2 to 6 percentage points, with the largest gain on MATH. Panel (b) shows that PCS also leads in three-state accuracy on MATH and Countdown, while its 78% accuracy on Geometry3K ties BOTS and trails DPS by one percentage point. This distinction highlights the importance of evaluating State-2 identification separately from overall state classification. In panel (c), ESR is computed from independently resampled audit responses. PCS

Table 3: **Necessity, broadcast, and temporal-placebo ablations.** Macro is the three-task Pass@1 average, Pred. is macro State-2 F1, Stale is Recall@B after 200 unobserved steps, and Cost is non-generation time relative to no-coupling.

Variant	Macro (%) ↑	Pred. F1 (%) ↑	Stale R@B (%) ↑	R@95 ↓	Cost (×) ↓
w/o coupling	50.5±0.7	83.0±1.3	39±3	0.87	1.00
w/o broadcast	50.7±0.9	84.5±1.2	44±3	0.84	1.02
Frozen context	50.8±0.8	85.2±1.1	46±3	0.82	1.01
Shuffled context	50.6±0.9	83.8±1.4	41±4	0.85	1.03
w/o discovery ($\gamma = 0$)	51.1±0.8	86.0±1.0	52±3	0.79	1.02
w/o EMA context	51.3±0.8	86.5±1.0	55±3	0.77	1.03
Full PCS	51.6±0.8	88.3±0.9	62±3	0.73	1.03

attains ESRs of 89%, 55%, and 82% across the three tasks, exceeding all non-filtering baselines, including HR. DS achieves ESRs 5–8 percentage points higher through additional candidate-filtering rollouts, illustrating the trade-off between selection informativeness and rollout cost.

Stale-prompt recovery and rollout cost. We examine prediction quality and recovery–cost trade-offs using diagnostic runs exceeding 200 training steps on each of MATH, Countdown, and Geometry3K (Figure 3). Observation age counts training steps since a prompt's last observation. In panel (d), PCS retains 61% State-2 F1 after more than 200 unobserved steps, compared with 43% for BOTS, the strongest non-filtering baseline. Panel (e) shows a similar advantage in the largest policy-shift quartile: PCS records a 23% false-negative rate, versus 41% for BOTS and 46% for DPS, indicating fewer missed partially solved prompts. For recovery in panel (f), PCS achieves 62% Recall@B at near-unit normalized cost, while comparable-cost alternatives remain at or below 43%. DS attains higher recall (91%) through rollout-based filtering at approximately 3.8× normalized cost, highlighting the additional rollout expenditure associated with its recovery advantage. Section G details state-recall, calibration, staleness–policy-shift, robustness, failure-composition.

4.5 Mechanism Ablation

Table 3 isolates the contributions of cross-prompt coupling, broadcast updates, discovery-aware acquisition, and EMA context smoothing. The frozen- and shuffled-context controls retain the context pathway while removing policy evolution or its temporal alignment. Full PCS leads every quality metric at only 1.03× non-generation cost. Coupling and broadcast are particularly important for stale-prompt recovery: removing them lowers Recall@B from 62% to 39% and 44%, respectively. The smaller degradations from removing discovery or EMA, together with the frozen- and shuffled-context controls, show that acquisition, smoothing, and temporally aligned policy context provide complementary benefits. Because all variants cost only 1.00–1.03×, these improvements are not explained by additional non-generation computation. Further per-task, capacity, trajectory, multi-baseline, and statistical analyses appear in Sections D.1, D.3 to D.5, I and K.

5 Conclusion and Limitations

We introduce Policy-Coupled Sampling (PCS), an online sampler that couples prompt-specific Bayesian memories through a global policy context learned from existing rollout feedback. The resulting policy-conditioned transitions support a discovery signal that prioritizes prompts whose predicted informativeness has changed, without requiring candidate-filtering rollouts. PCS reaches 34.17%, 76.03%, and 44.75% on AIME24, Countdown CD-34, and Geometry3K, respectively, yielding a three-task macro of 51.65%. It exceeds the strongest equal-budget baseline by 0.81 points, while rollout-filtering DS uses 2.6–4.6× as many rollouts. Transfer, prediction, stale-recovery, and ablation results further show that the gains extend to held-out targets and newer Qwen3.5 backbones and are associated with policy coupling and discovery-aware selection at little non-generation overhead. PCS represents solving progress with three correctness-defined states and summarizes policy evolution using two selected-batch statistics, which may be noisy or selection-biased. Its shared linear coupling may not capture nonlinear or prompt-dependent responses, while deterministic top-B acquisition may overexploit miscalibrated predictions and reduce prompt diversity. Future work should investigate continuous or process-level feedback, debiased and richer policy representations, nonlinear or hierarchical coupling, uncertainty-aware diverse acquisition, and evaluation on larger models and broader reasoning domains.

AI USE STATEMENT

Generative AI tools were used only to assist with language editing, including improving wording, grammar, readability, and presentation of text written by the authors. They were not used to formulate the research problem, develop the proposed method, design or conduct experiments, implement the experimental pipeline, generate or modify experimental results, perform statistical analyses, select reported results, or determine the scientific conclusions of the paper. All technical content, mathematical derivations, experimental decisions, reported results, and scientific claims were produced, checked, and approved by the authors, who take full responsibility for the content of the submission.

REPRODUCIBILITY STATEMENT

We provide detailed information to support reproducibility of the proposed method and experimental results. Algorithm 1 and Appendix J describe the complete PCS pipeline, including the policy-coupled transition model, discovery-aware acquisition rule, update order, computational complexity, and implementation details. Appendices C and E specify the datasets and splits, model configurations, training budgets, GRPO settings, sampler implementations, hyperparameter selection, checkpoint rules, evaluation procedures, generation accounting, and statistical methodology. Controlled comparisons use shared seeds and matched initialization, prompt ordering, optimizer state, training budgets, decoding settings, checkpoint-selection rules, and evaluation prompts within each seed. Appendices D–I provide additional multi-seed results, ablations, transfer evaluations, prompt-state prediction analyses, calibration diagnostics, cost accounting, scaling experiments, and sensitivity analyses. Appendix L further describes evaluation safeguards, case-selection procedures, and checks for dataset leakage and contamination.

REFERENCES

Sanghwan Bae, Jiwoo Hong, Min Young Lee, Hanbyul Kim, JeongYeon Nam, and Donghyun Kwak. Online difficulty filtering for reasoning oriented reinforcement learning. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 700–719, 2026.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-vl technical report, 2025. URL https://arxiv.org/abs/2502.13923.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th annual international conference on machine learning*, pp. 41–48, 2009.

Xiaoyin Chen, Jiarui Lu, Minsu Kim, Dinghuai Zhang, Jian Tang, Alexandre Piché, Nicolas Gontier, Yoshua Bengio, and Ehsan Kamalloo. Self-evolving curriculum for llm reasoning. *arXiv preprint arXiv:2505.14970*, 2025.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.

Tianzhe Chu, Yuexiang Zhai, Jihan Yang, Shengbang Tong, Saining Xie, Dale Schuurmans, Quoc V Le, Sergey Levine, and Yi Ma. Sft memorizes, rl generalizes: A comparative study of foundation model post-training. *arXiv preprint arXiv:2501.17161*, 2025.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

Quy-Anh Dang and Chris Ngo. Reinforcement learning for reasoning in small llms: What works and what doesn't. *arXiv preprint arXiv:2503.16219*, 2025.

J Russo Daniel, Van Roy Benjamin, Kazerouni Abbas, Osband Ian, and Wen Zheng. A tutorial on thompson sampling. *Foundations and trends® in machine learning*, 11(1):1–99, 2018.

Talfan Evans, Shreya Pathak, Hamza Merzic, Jonathan Schwarz, Ryutaro Tanno, and Olivier J Henaff. Bad students make great teachers: Active learning accelerates large-scale visual understanding. In *European Conference on Computer Vision*, pp. 264–280. Springer, 2024.

Mehdi Fatemi, Banafsheh Rafiee, Mingjie Tang, and Kartik Talamadupula. Concise reasoning via reinforcement learning. *arXiv preprint arXiv:2504.05185*, 2025.

Alex Graves, Marc G Bellemare, Jacob Menick, Remi Munos, and Koray Kavukcuoglu. Automated curriculum learning for neural networks. In *international conference on machine learning*, pp. 1311–1320. Pmlr, 2017.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Thai, Junhao Shen, Jinyi Hu, Xu Han, Yujie Huang, Yuxiang Zhang, et al. Olympiadbench: A challenging benchmark for promoting agi with olympiad-level bilingual multimodal scientific problems. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 3828–3850, 2024.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*, 2021.

Bairu Hou, Yang Zhang, Jiabao Ji, Yujian Liu, Kaizhi Qian, Jacob Andreas, and Shiyu Chang. Thinkprune: Pruning long chain-of-thought of llms via reinforcement learning. *arXiv preprint arXiv:2504.01296*, 2025.

Jian Hu, Jason Klein Liu, Haotian Xu, and Wei Shen. Reinforce++: Stabilizing critic-free policy optimization with global advantage normalization. *arXiv preprint arXiv:2501.03262*, 2025.

B Hui, J Yang, Z Cui, J Yang, D Liu, L Zhang, T Liu, J Zhang, B Yu, K Lu, et al. Qwen2. 5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, et al. Openai o1 system card. *arXiv preprint arXiv:2412.16720*, 2024.

Angelos Katharopoulos and François Fleuret. Not all samples are created equal: Deep learning with importance sampling. In *International conference on machine learning*, pp. 2525–2534. PMLR, 2018.

Amirhossein Kazemnejad, Milad Aghajohari, Eva Portelance, Alessandro Sordoni, Siva Reddy, Aaron Courville, and Nicolas Le Roux. Vineppo: Refining credit assignment in rl training of llms. *arXiv preprint arXiv:2410.01679*, 2024.

M Kumar, Benjamin Packer, and Daphne Koller. Self-paced learning for latent variable models. *Advances in neural information processing systems*, 23, 2010.

Harrison Lee, Samrat Phatale, Hassan Mansoor, Thomas Mesnard, Johan Ferret, Kellie Lu, Colton Bishop, Ethan Hall, Victor Carbune, Abhinav Rastogi, et al. Rlaif vs. rlhf: Scaling reinforcement learning from human feedback with ai feedback. *arXiv preprint arXiv:2309.00267*, 2023.

Xuefeng Li, Haoyang Zou, and Pengfei Liu. Limr: Less is more for rl scaling. *arXiv preprint arXiv:2502.11886*, 2025.

Shuang Liang, Haoyang Zhou, Yifan Gong, Guowei Wang, and Xiting Wang. Leeps: Latent-guided explore-exploit prompt sampling for efficient rlvr in large language models. *arXiv preprint arXiv:2607.28077*, 2026.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *International Conference on Learning Representations*, volume 2024, pp. 39578–39601, 2024.

Zhihang Lin, Mingbao Lin, Yuan Xie, and Rongrong Ji. Cppo: Accelerating the training of group relative policy optimization-based reasoning models. *Advances in Neural Information Processing Systems*, 38:61043–61068, 2026.

Mingjie Liu, Shizhe Diao, Ximing Lu, Jian Hu, Xin Dong, Yejin Choi, Jan Kautz, and Yi Dong. Prorl: Prolonged reinforcement learning expands reasoning boundaries in large language models. *Advances in Neural Information Processing Systems*, 38:17998–18031, 2026.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. Understanding r1-zero-like training: A critical perspective. *arXiv preprint arXiv:2503.20783*, 2025.

Pan Lu, Ran Gong, Shibiao Jiang, Liang Qiu, Siyuan Huang, Xiaodan Liang, and Song-Chun Zhu. Inter-gps: Interpretable geometry problem solving with formal language and symbolic reasoning. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 6774–6786, 2021.

Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. In *International Conference on Learning Representations*, volume 2024, pp. 23439–23554, 2024.

Michael Luo, Sijun Tan, Roy Huang, Ameen Patel, Alpay Ariyak, Qingyang Wu, Xiaoxiang Shi, Rachel Xin, Colin Cai, Maurice Weber, et al. Deepcoder: A fully open-source 14b coder at o3-mini level. *Notion Blog*, 1, 2025a.

Michael Luo, Sijun Tan, Justin Wong, Xiaoxiang Shi, William Y Tang, Manan Roongta, Colin Cai, Jeffrey Luo, Li Erran Li, Raluca Ada Popa, et al. Deepscaler: Surpassing o1-preview with a 1.5 b model by scaling rl. *Notion Blog*, 3(5), 2025b.

Yixiu Mao, Yun Qu, Qi Wang, Heming Zou, and Xiangyang Ji. Dynamics-predictive sampling for active rl finetuning of large reasoning models. In *International Conference on Learning Representations*, volume 2026, pp. 25242–25270, 2026.

Sanmit Narvekar, Bei Peng, Matteo Leonetti, Jivko Sinapov, Matthew E Taylor, and Peter Stone. Curriculum learning for reinforcement learning domains: A framework and survey. *Journal of Machine Learning Research*, 21(181):1–50, 2020.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35: 27730–27744, 2022.

Jiayi Pan, Junjie Zhang, Xingyao Wang, Lifan Yuan, Hao Peng, and Alane Suhr. Tinyzero. https://github.com/Jiayi-Pan/TinyZero, 2025. Accessed: 2025-01-24.

Yun Qu, Qi Wang, Yixiu Mao, Vincent Tao Hu, Björn Ommer, and Xiangyang Ji. Can prompt difficulty be online predicted for accelerating rl finetuning of reasoning models? In *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 1*, pp. 1240–1250, 2026a.

Yun Qu, Qi Wang, Yixiu Mao, Heming Zou, Yuhang Jiang, Weijie Liu, Clive Bai, Kai Yang, Yangkun Chen, Saiyong Yang, et al. Small generalizable prompt predictive models can steer efficient rl post-training of large reasoning models. *arXiv preprint arXiv:2602.01970*, 2026b.

Lawrence R Rabiner. A tutorial on hidden markov models and selected applications in speech recognition. *Proceedings of the IEEE*, 77(2):257–286, 1989.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741, 2023.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. *arXiv preprint arXiv:1511.05952*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. *arXiv preprint arXiv:1708.00489*, 2017.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Qianli Shen, Daoyuan Chen, Yilun Huang, Zhenqing Ling, Yaliang Li, Bolin Ding, and Jingren Zhou. Bots: A unified framework for bayesian online task selection in llm reinforcement finetuning. In *International Conference on Learning Representations*, volume 2026, pp. 99871–99911, 2026.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pp. 1279–1297, 2025.

Mingyang Song, Mao Zheng, Zheng Li, Wenjie Yang, Xuan Luo, Yue Pan, and Feng Zhang. Fastcurl: Curriculum reinforcement learning with stage-wise context scaling for efficient training r1-like reasoning models. In *EMNLP (Findings)*, pp. 8856–8866, 2025.

Ben Sorscher, Robert Geirhos, Shashank Shekhar, Surya Ganguli, and Ari Morcos. Beyond neural scaling laws: beating power law scaling via data pruning. *Advances in Neural Information Processing Systems*, 35:19523–19536, 2022.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. *Advances in neural information processing systems*, 33:3008–3021, 2020.

Kimi Team, Angang Du, Bofei Gao, Bowei Xing, Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun Xiao, Chenzhuang Du, Chonghua Liao, et al. Kimi k1. 5: Scaling reinforcement learning with llms. *arXiv preprint arXiv:2501.12599*, 2025.

Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026. URL `https://qwen.ai/blog?id=qwen3.5`.

Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. Solving math word problems with process-and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.

Yiping Wang, Qing Yang, Zhiyuan Zeng, Liliang Ren, Liyuan Liu, Baolin Peng, Hao Cheng, Xuehai He, Kuan Wang, Jianfeng Gao, et al. Reinforcement learning for reasoning in large language models with one training example. *Advances in Neural Information Processing Systems*, 38: 122721–122764, 2026.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, et al. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. *Advances in Neural Information Processing Systems*, 37:95266–95290, 2024.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Liang Wen, Yunke Cai, Fenrui Xiao, Xin He, Qi An, Zhenyu Duan, Yimin Du, Junchen Liu, Lifu Tang, Xiaowei Lv, et al. Light-r1: Curriculum sft, dpo and rl for long cot from scratch and beyond. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 6: Industry Track)*, pp. 318–327, 2025.

Jiahao Wu, Ning Lu, Shengcai Liu, Kun Wang, Yanting Yang, Bailong Lin, Chen Jason Zhang, Li Qing, and Ke Tang. Train at moving edge: Online-verified prompt selection for efficient rl training of large reasoning model. *arXiv preprint arXiv:2603.25184*, 2026.

Wei Xiong, Jiarui Yao, Yuhui Xu, Bo Pang, Lei Wang, Doyen Sahoo, Junnan Li, Nan Jiang, Tong Zhang, Caiming Xiong, et al. A minimalist approach to llm reasoning: from rejection sampling to reinforce. *arXiv preprint arXiv:2504.11343*, 2025.

Jianhao Yan, Yafu Li, Zican Hu, Zhi Wang, Ganqu Cui, Xiaoye Qu, Yu Cheng, and Yue Zhang. Learning to reason under off-policy guidance. *Advances in Neural Information Processing Systems*, 38:117157–117186, 2026.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, et al. Qwen2. 5-math technical report: Toward mathematical expert model via self-improvement. *arXiv preprint arXiv:2409.12122*, 2024.

Yixin Ye, Zhen Huang, Yang Xiao, Ethan Chern, Shijie Xia, and Pengfei Liu. Limo: Less is more for reasoning. *arXiv preprint arXiv:2502.03387*, 2025.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, et al. Dapo: An open-source llm reinforcement learning system at scale. *Advances in Neural Information Processing Systems*, 38:113222–113244, 2026.

Lifan Yuan, Wendi Li, Huayu Chen, Ganqu Cui, Ning Ding, Kaiyan Zhang, Bowen Zhou, Zhiyuan Liu, and Hao Peng. Free process rewards without process labels. *arXiv preprint arXiv:2412.01981*, 2024.

Yufeng Yuan, Yu Yue, Ruofei Zhu, Tiantian Fan, and Lin Yan. What's behind ppo's collapse in long-cot? value optimization holds the secret. *arXiv preprint arXiv:2503.01491*, 2025.

Yu Yue, Yufeng Yuan, Qiying Yu, Xiaochen Zuo, Ruofei Zhu, Wenyuan Xu, Jiaze Chen, Chengyi Wang, TianTian Fan, Zhengyin Du, et al. Vapo: Efficient and reliable reinforcement learning for advanced reasoning tasks. *arXiv preprint arXiv:2504.05118*, 2025.

Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Goodman. Star: Bootstrapping reasoning with reasoning. *Advances in Neural Information Processing Systems*, 35:15476–15488, 2022.

Weihao Zeng, Yuzhen Huang, Qian Liu, Wei Liu, Keqing He, Zejun Ma, and Junxian He. Simplerl-zoo: Investigating and taming zero reinforcement learning for open base models in the wild. *arXiv preprint arXiv:2503.18892*, 2025.

Xiaojiang Zhang, Jinghui Wang, Zifei Cheng, Wenhao Zhuang, Zheng Lin, Minglei Zhang, Shaojie Wang, Yinghan Cui, Chao Wang, Junyi Peng, et al. Srpo: A cross-domain implementation of large-scale reinforcement learning on llm. *arXiv preprint arXiv:2504.14286*, 2025.

Haizhong Zheng, Yang Zhou, Brian Bartoldson, Bhavya Kailkhura, Fan Lai, Jiawei Zhao, and Beidi Chen. Act only when it pays: Efficient reinforcement learning for llm reasoning via selective rollouts. *Advances in Neural Information Processing Systems*, 38:124321–124346, 2026.

Chunting Zhou, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, et al. Lima: Less is more for alignment. *Advances in Neural Information Processing Systems*, 36:55006–55021, 2023.

A Related Work

Curriculum learning and adaptive sampling. Curriculum and self-paced learning adapt example difficulty to learner competence (Bengio et al., 2009; Kumar et al., 2010), while automated curricula use learning progress to guide allocation (Graves et al., 2017; Narvekar et al., 2020). Related approaches select examples using gradient contribution (Katharopoulos & Fleuret, 2018), geometric coverage (Sener & Savarese, 2017), proxy models (Evans et al., 2024), data-pruning criteria (Sorscher et al., 2022), or replay priorities (Schaul et al., 2015). Whereas supervised curricula can often use difficulty estimates computed before training, online RL must account for changing response distributions and the cost of obtaining fresh rewards. In reasoning RL, prompt utility changes with the policy: previously unsolved prompts may become informative, while solved prompts may cease to provide reward variation. This makes the validity of historical observations central to online selection.

Reasoning and efficient RL finetuning. Preference-based learning and instruction following established practical language-model post-training (Christiano et al., 2017; Stiennon et al., 2020; Ouyang et al., 2022), with AI feedback and direct preference optimization offering alternative supervision and objectives (Lee et al., 2023; Rafailov et al., 2023). Reasoning research has explored chain-of-thought prompting, self-consistency, and rationale bootstrapping (Wei et al., 2022; Wang et al., 2022; Zelikman et al., 2022), alongside outcome, process, and implicit process supervision (Uesato et al., 2022; Lightman et al., 2024; Yuan et al., 2024). PPO and GRPO provide policy optimization frameworks for RL finetuning (Schulman et al., 2017; Shao et al., 2024). For GRPO, reward variation within a response group determines whether a prompt supplies a nonzero reward-based advantage, motivating selection of partially solved prompts.

Data-efficient training studies examine curated examples, learning-impact selection, and extreme data reuse (Zhou et al., 2023; Ye et al., 2025; Li et al., 2025; Wang et al., 2026). Other work studies value estimation, credit assignment, and policy-gradient recipes (Hu et al., 2025; Yue et al., 2025; Yuan et al., 2025; Kazemnejad et al., 2024; Lin et al., 2026; Xiong et al., 2025), or analyzes how training duration and implementation choices affect reasoning gains (Liu et al., 2026; Chu et al., 2025; Zeng et al., 2025; Liu et al., 2025; Dang & Ngo, 2025). Further efficiency gains come from scheduling context length or training stages (Song et al., 2025; Wen et al., 2025), shortening reasoning traces (Fatemi et al., 2025; Hou et al., 2025), and using off-policy guidance (Yan et al., 2026). PCS focuses on prompt allocation and can be studied with the policy objective and generation settings held fixed.

Online curricula and rollout filtering. HR removes prompts already solved within an epoch (Zhang et al., 2025), while self-evolving and difficulty-aware curricula adapt selection using recent feedback (Chen et al., 2025; Bae et al., 2026). An epoch-level solved flag is inexpensive to maintain but does not forecast when a prompt becomes useful again. Recent difficulty estimates are more responsive, although they still reflect the policy at the time of observation. Dynamic Sampling in DAPO generates candidate response groups and retains those with non-uniform rewards (Yu et al., 2026). Selective-rollout methods likewise seek to avoid low-utility training groups (Zheng et al., 2026), and HIVE combines historical trajectories with online verification (Wu et al., 2026). Current-policy rollouts provide direct evidence of informativeness, but discarded candidates still consume generation budget. Efficiency comparisons must therefore count responses for both retained and rejected prompts. PCS ranks prompts before generation, making accurate prediction of changing utility essential to its efficiency.

Prompt-local predictive selection. MoPPS uses Bayesian progress estimates to prioritize prompts near an informative difficulty region (Qu et al., 2026a), following the exploration–exploitation logic of posterior sampling (Daniel et al., 2018). DPS models each prompt as a three-state solving process and selects by its predicted probability of partial solution (Mao et al., 2026), using hidden Markov filtering (Rabiner, 1989). Separate transition statistics allow DPS to represent different learning trajectories across the dataset and advance state forecasts between observations. Both methods select before generation, but their estimates rely primarily on each prompt's own observation history. When a prompt remains unselected, evidence collected elsewhere does not directly update its prediction. This creates a discovery problem: a prompt may remain low-ranked after becoming informative, because the selector has little reason to collect the feedback needed to revise its score.

PCS retains the DPS state representation and Bayesian memory while conditioning transitions on a shared context estimated from selected-batch success and partial-solution rates. The shared adjustment lets observations from selected prompts influence forecasts across the dataset while preserving each prompt's local transition structure.

Sharing evidence across prompts. BOTS uses Bayesian acquisition for online task selection (Shen et al., 2026). GPS learns a shared prompt predictor and combines intermediate-difficulty acquisition with diversity (Qu et al., 2026b). Its predictor generalizes optimization history across prompts, making predictive capacity and the distribution of observed training examples relevant to acquisition. LEEPS transfers historical outcomes through latent neighbors and balances exploration and exploitation (Liang et al., 2026). Its evidence sharing depends on representation neighborhoods that connect prompts with useful related histories. These methods extend prediction beyond isolated prompt memories through task-level acquisition, learned predictors, or representation geometry.

PCS shares evidence through a low-dimensional policy context and coupling tensor that adjust prompt-specific transition matrices, assuming partially shared responses to policy evolution. Its discovery signal compares forecasts under current and cached contexts while holding the local belief, Bayesian base, and coupling parameters fixed. An increase in predicted partial-solution probability raises the priority of an unobserved prompt, allowing feedback gathered elsewhere to guide its reevaluation. The shared transition model and discovery rule thus connect policy evolution to prompt rediscovery using existing rollout feedback, without additional candidate-filtering responses.

B Full Algorithm Pipeline

Algorithm 1: Policy-Coupled Sampling (PCS)

Input: $\mathcal{D}$, $\{\boldsymbol{\alpha}_0^\tau\}_{\tau\in\mathcal{D}}$, $\{\boldsymbol{\mu}_1^{\tau,\text{prior}}\}_{\tau\in\mathcal{D}}$, B, λ, ρ, η_W, γ, $\pi_{\boldsymbol{\theta}}$, T.
Output: Finetuned policy $\pi_{\boldsymbol{\theta}}$.
Initialize $\boldsymbol{W}_0 = \mathbf{0}$, $\boldsymbol{s}_1 = \mathbf{0}$, and $\boldsymbol{s}_{\ell_1^\tau} = \mathbf{0}$ for all $\tau \in \mathcal{D}$;
for $t = 1$ **to** T **do**
  Sample $\widehat{\mathcal{B}}_t \subseteq \mathcal{D}$;
  foreach $\tau \in \widehat{\mathcal{B}}_t$ **do**
    Compute Δ_t^τ and a_t^τ using Eqs. (6)–(7);
  Select $\mathcal{B}_t \leftarrow \text{Top}_B\{a_t^\tau\}$;
  Generate $\{y_{t,i}^\tau\}_{i=1}^k$ for each $\tau \in \mathcal{B}_t$, observe their rewards, and update $\pi_{\boldsymbol{\theta}}$ with GRPO;
  Compute $\boldsymbol{o}_t$ and update $\boldsymbol{s}_{t+1}$ using Eq. (9);
  foreach $\tau \in \mathcal{B}_t$ **do**
    Update $\boldsymbol{\mu}_t^{\tau,\text{post}}$ and $\boldsymbol{\alpha}_t^\tau$; store $\boldsymbol{s}_{\ell_{t+1}^\tau} \leftarrow \boldsymbol{s}_{t+1}$;
  Compute the batch gradient using Eq. (10) and update $\boldsymbol{W}_t$ using Eq. (11);
  foreach $\tau \in \mathcal{D} \setminus \mathcal{B}_t$ **do**
    Set $\boldsymbol{\mu}_t^{\tau,\text{post}} \leftarrow \boldsymbol{\mu}_t^{\tau,\text{prior}}$ and decay $\boldsymbol{\alpha}_t^\tau$ toward $\boldsymbol{\alpha}_0^\tau$;
  Predict every $\boldsymbol{\mu}_{t+1}^{\tau,\text{prior}}$ using Eq. (12);

C Complete Experimental Settings

This section records the datasets, model pairings, training budgets, sampler implementations, and evaluation rules used for the reported experiments. Task/model-matched endpoints and controlled diagnostics are presented with their corresponding optimization and decoding settings.

C.1 Datasets, Splits, and Models

MATH training uses the official 7,500-problem training split, and no AIME24, AMC23, OlympiadBench, ARC-C, or MMLU-Pro item is admitted to RL training. Countdown uses 2,000 generated

Table 4: **Training and primary evaluation inventory.** Counts and model pairings follow the task-specific experimental protocol.

Source	Base model	Split role	Train	Eval
MATH (Hendrycks et al., 2021)	DeepSeek-R1-Distill-Qwen-1.5B (Guo et al., 2025)	MATH train; AIME24 primary	7,500	30
Countdown (Pan et al., 2025)	Qwen2.5-3B (Hui et al., 2024)	CD train; CD-34 primary	2,000	512
Geometry3K (Lu et al., 2021)	Qwen2.5-VL-3B-Instruct (Bai et al., 2025)	Official train and test	2,101	601

training instances, while CD-34 and CD-4 are frozen 512-instance evaluation sets with different number cardinalities. Geometry3K preserves the official 2,101/601 train/test division and passes both the diagram and question through the Qwen2.5-VL processor.

The primary endpoint is average Pass@1 from 16 independently sampled completions per evaluation prompt. For verifiable mathematics and Countdown, the parser extracts the final answer and applies the task verifier; for Geometry3K, the multimodal prompt and official answer normalization are frozen across samplers. Macro results average task percentages rather than pooling prompts, so the 601-example Geometry3K test set does not dominate the 30-example AIME24 set.

Table 5: **Held-out evaluation map and permitted use.**

RL source	Target	Output type	Permitted use
MATH	AMC23 / OlympiadBench	Numeric or symbolic	Final evaluation only; no sampler or checkpoint tuning.
MATH	ARC-C / MMLU-Pro	Multiple choice	Final evaluation with a frozen option parser.
MATH	GSM8K	Numeric	Final evaluation only; no sampler or checkpoint tuning.
Countdown	CD-4	Arithmetic expression	Final evaluation with the CD verifier.
Geometry3K	MathVista	Multimodal short answer	Final evaluation only; no sampler or checkpoint tuning.

C.2 Training Budget and GRPO Configuration

All source tasks use GRPO (Shao et al., 2024) through `verl` (Sheng et al., 2025) with eight responses per selected prompt. The standard rollout budget equals steps multiplied by batch size and responses per prompt, which gives the exact counts in Table 6.

Table 6: **Task-specific training settings used in the endpoint comparison.**

Task	Steps	Batch	Mini-batch	Responses	Max response	KL	Standard R
MATH	360	256	128	8	8,192	0	737,280
Countdown	120	256	64	8	1,024	0	245,760
Geometry3K	120	512	256	8	1,024	0.01	491,520

The KL coefficient shown for Geometry3K is the 3B setting; it is not transferred automatically to a different model scale. The actor clip range is $[0.20, 0.28]$, entropy regularization is 0.001, and the published DPS protocol uses learning rate 10^{-6} with weight decay 0.01 and no warm-up. Training generation uses temperature 1.0 and `top_p`$= 1.0$, while evaluation uses temperature 0.6, 16 completions, and published `top_p`$= 0.95$.

C.3 Sampler Implementations

Every sampler implements a common interface that receives the eligible prompt identifiers and returns exactly B identifiers before training responses are generated. The selected prompts, selection scores, observation ages, and selection latency are logged at every step, while candidate responses generated solely for DS are recorded in a separate filtering ledger.

Native MoPPS and BOTS hyperparameters are initialized from their official implementations, but they are not permitted to change the model, task split, batch, or generation budget. When an official method uses an incompatible normalized budget or data mixture, its native and matched results are reported separately rather than merged into one cell. DS uses the published task-specific candidate

Table 7: **Implementation contract for the matched sampler evaluation.**

Method	Persistent state	Acquisition score	Required audit
US	Eligibility mask only	Uniform random key	Prompt-frequency equality.
HR	Current-epoch solved mask	Uniform over unsolved prompts	Epoch reset and exclusion rate.
DS	Current candidate rewards	Non-uniform reward indicator	Generated and discarded candidates.
MoPPS	Official progress posterior	Published acquisition rule	Posterior calibration and selection time.
BOTS	Official Bayesian selector state	Published acquisition rule	Prior sensitivity and normalization.
DPS	Per-prompt three-state belief and transition counts	Predicted State-2 probability	State calibration by observation age.
PCS	DPS memory, last-seen context, global context, and coupling tensor	State-2 probability plus discovery	Broadcast drift and stale recovery.

expansion implied by 2,933k, 1,141k, and 1,262k total training rollouts on MATH, Countdown, and Geometry3K.

C.4 PCS Hyperparameters and Selection State

PCS uses a two-dimensional policy context containing selected-batch mean reward and the fraction of groups with non-uniform rewards. The context is updated by EMA decay ρ, the discovery contribution is weighted by γ, local transition counts decay by λ, and the coupling tensor is updated only from observed selected-prompt transitions. No target-set result is used to choose these parameters.

Table 8: **PCS tuning grid and selected settings.** The grid and selection rule are fixed on source validation before target evaluation.

Quantity	Candidate values	Default shown	Selection rule
Discovery weight γ	$0, 0.1, 0.25, 0.5$	0.25	Source-validation macro, then stale recall.
EMA decay ρ	$0.90, 0.95, 0.99$	0.99	Shared across tasks unless predeclared.
Broadcast interval	$1, 2, 4, 8, 16$ steps	1	Smallest interval with material overhead.
Auxiliary low-rank coupling	$1, 2, 4, 8$	Diagnostic only	Primary PCS uses the full $3 \times 3 \times 2$ tensor.
Forecast pool	$25, 50, 75, 100\%$	100%	Report quality–latency frontier.

At step t, PCS computes a score for every eligible prompt, takes a deterministic top-B selection after seed-controlled tie breaking, and then updates only from the resulting training responses. The pre-update score, post-update local belief, current context, last-seen context, discovery increment, and final acquisition value are retained for diagnostic replay. This log is sufficient to reconstruct stale Recall@B, rediscovery delay, calibration by age, and the fraction of each selection attributable to discovery.

C.5 Evaluation, Checkpoints, and Statistical Reporting

Evaluation is run at fixed rollout checkpoints and at the endpoint, not only at whichever checkpoint yields the maximum test score. R@95 is computed from actual cumulative generation rather than step count, and DS crosses a threshold only after candidate-filtering responses are charged. Budget AUC uses the trapezoidal rule over 25, 50, 75, and 100% of each method's declared endpoint budget.

Five seeds are paired across methods by initialization, prompt order, optimizer state, generation seeds where supported, and evaluation seeds. For each task, the report includes all seed endpoints, their paired differences, a paired bootstrap interval, and the number of completed runs. The Geometry3K result is reported without a superiority claim when the PCS–DPS difference remains at single-run resolution, and the MoPPS advantage is retained if reproduced.

Checkpoint selection uses a source-validation rule fixed before target evaluation. Held-out targets are evaluated only after the checkpoint identifier is frozen, and their outputs cannot modify sampler hyperparameters, prompt templates, answer parsing, or early stopping. Failed runs are resumed from the paired checkpoint or disclosed as failures rather than replaced by a new favorable seed.

The Qwen3.5 cross-backbone validation reuses the same task splits, rollout budgets, response counts, and evaluation protocol, replacing only the text backbone with Qwen3.5-2B and the multimodal backbone with Qwen3.5-4B.

D Additional Experimental Analysis

D.1 Multi-Baseline Quality, Efficiency, and Stability Comparison

The multi-axis comparison reports final and Hard/OOD quality, budget AUC, R@95, peak-to-final drop, and generation-inclusive rollout cost for every sampler.

Table 9: **Quality, efficiency, and stability comparison.** Final is the three-task macro, Hard/OOD is the unweighted mean of the reported primary-backbone endpoint scores on AMC23, CD-4, ARC-C, and MMLU-Pro, and Total R includes filtering rollouts.

Method	Final (%) ↑	Hard/OOD (%) ↑	AUC (%) ↑	R@95 (×) ↓	Drop (pp) ↓	Total R (×) ↓
US	45.67	41.75	38.8	0.93	2.7	1.00
HR	46.25	46.58	41.4	0.81	2.2	1.00
DS (oracle)	50.39	50.30	44.4	2.87	1.3	3.73
MoPPS (Qu et al., 2026a)	50.84	49.81	45.3	0.78	1.4	1.00
BOTS (Shen et al., 2026)	44.1	49.67	44.9	**0.67**	1.3	1.00
DPS	50.48	50.39	45.3	0.86	1.1	1.00
PCS (ours)	**51.65**	**50.93**	**46.5**	0.73	**0.5**	1.00

PCS achieves the highest final macro (51.65%), Hard/OOD score (50.93%), and budget AUC (46.5%), while also exhibiting the smallest peak-to-final drop (0.5 points). Its R@95 is $0.73\times$, second only to BOTS at $0.67\times$, whereas BOTS has a substantially lower final macro of 44.1%. DPS and DS obtain Hard/OOD scores of 50.39% and 50.30%, respectively, compared with 50.93% for PCS. DS reaches a 50.39% final macro but uses $3.73\times$ the standard rollout budget because candidate-filtering responses are included in Total R.

D.2 Cross-Dataset Evaluation Protocol

Table 10: **Source-to-target transfer matrix used for cross-dataset evaluation.** The matrix extends the ARC-C and MMLU-Pro transfer setting with competition mathematics, arithmetic word problems, and visual mathematical reasoning.

RL source and model	Held-out targets	Evaluation
MATH / DeepSeek-R1-Distill-Qwen-1.5B	GSM8K, OlympiadBench, ARC-C, MMLU-Pro	Exact-match or option accuracy
Countdown / Qwen2.5-3B	CD-4	Exact-match accuracy
Geometry3K / Qwen2.5-VL-3B-Instruct	MathVista	Official answer accuracy

Every sampler uses the same frozen prompt template, answer parser, response limit, and 16-completion evaluation. Target data are not used for sampler tuning or checkpoint selection. Paired-seed analyses use five shared seeds and retain ties and negative target-level differences when constructing confidence intervals.

D.3 Additional Method Analysis

Proposition D.1 (DPS as a special case)**.** *If the shared coupling is disabled by setting $\boldsymbol{W}_t = \mathbf{0}$, PCS reduces to DPS under the same prompt-local memory update and candidate pool.*

Proof. With $\boldsymbol{W}_t = \mathbf{0}$, the coupled transition matrix is independent of the global policy context and equals the prompt-local posterior mean. The current-context and last-seen-context forecasts are therefore identical, which gives $\Delta_t^\tau = 0$. The PCS acquisition score becomes $a_t^\tau = \mu_t^{\tau,\mathrm{prior}}(2)$, which is the DPS selection score. □

Computational complexity. For three prompt states and a two-dimensional policy context, the shared tensor contains only 18 scalars, while each prompt stores two additional last-seen context




Figure 4: **Auxiliary policy-coupling diagnostics.** Panels report (a) State-2 reliability, (b) coupling-norm evolution, (c) PCS–DPS gain by policy-context shift, and (d) non-generation overhead by PCS operation.

values. Updating the context costs $O(B)$, learning the coupling costs $O(18B)$, and broadcasting the coupled forecast costs $O(18|\mathcal{D}|)$ per step. These operations remain linear in the prompt pool with small constants and require no additional LLM rollouts.

When coupling should help. PCS is most useful when policy updates move many unobserved prompts coherently and prompt observation ages are large enough for local beliefs to become stale. It may help less when policy competence is nearly stationary, prompt families respond idiosyncratically, or the selected batch gives a biased summary of the full data distribution. The shift-stratified and temporal-placebo experiments are designed to distinguish shared policy evolution from these failure modes.

The reliability panel tests whether coupling improves probability quality rather than only rank ordering, while the coupling-norm trace checks whether the shared transition modulation grows and stabilizes rather than diverges. The shift analysis shows the PCS–DPS gain increasing from 0.2 to 1.8 points across context-shift quartiles, a pattern consistent with prompt-local DPS beliefs becoming increasingly stale under larger policy shifts. Context estimation, coupling, broadcast, and discovery scoring together add only 3.0% non-generation time.

D.4 Full Per-Task Ablation Matrix

The per-task matrix prevents the macro improvement from obscuring task-specific behavior. Relative to the no-coupling DPS variant, full PCS increases the mean AIME24 and CD-34 scores by 1.5 and 1.7 percentage points, respectively, while the Geometry3K difference is smaller at 0.3 points. The corresponding three-task macro increases from 50.5% to 51.6%. The intermediate ablations remain between the no-coupling baseline and full PCS in macro performance, while the frozen- and shuffled-context controls remain below the full model. These results indicate that the overall im-

Table 11: **Per-task necessity and placebo controls.** Entries are mean±s.d. over five shared seeds. Macro is the three-task Pass@1 average over AIME24, CD-34, and Geometry3K.

Variant	AIME24 (%) ↑	CD-34 (%) ↑	Geo3K (%) ↑	Macro (%) ↑
w/o coupling (= DPS)	32.7±2.2	74.3±0.8	44.5±0.9	50.5±0.7
w/o broadcast	32.9±2.2	74.5±0.8	44.6±0.9	50.7±0.9
Frozen context	33.0±2.1	74.7±0.8	44.7±0.8	50.8±0.8
Shuffled context	32.8±2.2	74.4±0.8	44.6±0.9	50.6±0.9
w/o discovery ($\gamma = 0$)	33.5±2.1	75.2±0.7	44.7±0.8	51.1±0.8
w/o EMA context	33.7±2.1	75.5±0.7	44.8±0.8	51.3±0.8
Full PCS	34.2±2.0	76.0±0.7	44.8±0.8	51.6±0.8

provement is driven primarily by MATH and Countdown rather than by a uniform gain across all three tasks.

D.5 Statistical Reporting

All controlled results use five shared seeds, paired bootstrap confidence intervals, a fixed checkpoint rule, and measured generated-token and rollout counts. Prediction analyses freeze the stale-prompt pool before scoring and report State-2 precision, recall, F1, three-state accuracy, Brier score, calibration error, and false-negative rates across observation-age and policy-shift bins. Ablations are executed in dependency order and retain null or adverse results alongside favorable settings.

E Controlled Evaluation and Reproducibility Protocol

This section reports the controlled evaluation protocol used for paired comparisons. Every sampler receives the same model initialization, prompt order, optimizer state, training budget, decoding configuration, checkpoint rule, and evaluation prompts within a seed. This blocking removes between-run variation from the sampler contrast and makes null or adverse results interpretable.

E.1 Task-Level Training Contract

Table 12: **Fixed training contract for controlled evaluation.** The values are held constant across samplers within each task.

Task	Evaluation	Model	Objective	Steps	Batch	Resp.	Rollouts
MATH	AIME24	DeepSeek-R1-Distill-Qwen-1.5B	GRPO	360	256	8	737,280
Countdown	CD-34	Qwen2.5-3B	GRPO	120	256	8	245,760
Geometry3K	Test	Qwen2.5-VL-3B-Instruct	GRPO	120	512	8	491,520

Training prompts are shuffled once per seed and the resulting order is reused by all methods. Optimizer and scheduler state are initialized from the same serialized checkpoint, and no method may select its endpoint using target-test performance. Evaluation uses 16 completions per prompt with a frozen answer parser, and the same completion seeds are reused within each paired comparison whenever the serving stack permits deterministic sampling.

E.2 Sampler Interface and Cost Boundary

Table 13: **Common sampler interface and generation accounting.** The cost boundary includes every response generated to rank, filter, train on, or evaluate a candidate prompt.

Sampler	Selection signal	Generation accounting
US	Uniform score over the eligible prompt pool.	Selected training rollouts only.
HR	Current-epoch solved/unsolved record.	Selected training rollouts only.
DS	Non-uniform rewards in an enlarged candidate batch.	Candidate and selected rollouts.
MoPPS	Published predictive prompt-progress score.	Selected training rollouts only.
BOTS	Published Bayesian online-selection score.	Selected training rollouts only.
DPS	Prompt-local predicted State-2 probability.	Selected training rollouts only.
PCS	Policy-coupled State-2 probability plus discovery.	Selected training rollouts only.

Each method returns exactly B prompt identifiers before the training generation call. The trainer then generates the same number of responses per selected prompt and records generated tokens, accepted tokens, generation time, optimizer time, selection time, and peak device memory. For DS, candidate-filtering responses remain in the cost ledger even when their prompts are discarded.

E.3 Estimands and Statistical Tests

For task d, seed s, and method m, let Y_{dsm} denote final Pass@1 under the frozen checkpoint rule. The paired task effect relative to baseline b is $\delta_{ds}(m, b) = Y_{dsm} - Y_{dsb}$, and the primary macro estimand is

$$\widehat{\Delta}(m, b) = \frac{1}{|\mathcal{D}||\mathcal{S}|} \sum_{d \in \mathcal{D}} \sum_{s \in \mathcal{S}} \delta_{ds}(m, b). \tag{14}$$

We form a 95% interval by resampling seeds within each task and recomputing the paired macro effect, thereby preserving the common-random-number structure. The same bootstrap samples are used for final quality, Hard/OOD, Budget AUC, stale Recall@B, and R@95 so that the uncertainty summaries remain comparable.

Table 14: **Primary and diagnostic estimands.** Every metric is computed per seed before aggregation.

Metric	Definition	Direction
Final macro	Unweighted mean Pass@1 over AIME24, CD-34, and Geometry3K.	Higher
Hard/OOD	Unweighted mean over AMC23, CD-4, ARC-C, and MMLU-Pro.	Higher
Budget AUC	Trapezoidal area over 25, 50, 75, and 100% rollout checkpoints.	Higher
R@95	First actual rollout count reaching 95% of the method endpoint.	Lower
Stale Recall@B	Fraction of newly State-2 stale prompts recovered in the selected batch.	Higher
Peak–final	Maximum validation score minus final validation score.	Lower

E.4 Paired-Seed Results

Table 15: **Paired-seed results for the controlled macro endpoint.** All completed seeds are retained in the analysis.

Method	Seed 1	Seed 2	Seed 3	Seed 4	Seed 5
HR	45.3	46.8	45.9	46.9	46.4
DS	49.4	50.8	49.9	51.0	50.9
MoPPS	50.1	51.2	50.4	51.5	51.0
BOTS	43.2	44.8	43.7	44.6	44.2
DPS	49.5	50.9	50.0	51.4	50.6
PCS	50.9	50.8	51.7	52.2	52.4

The seed table is reported before significance testing so that consistency, outliers, and seed-specific reversals remain visible. Paired confidence intervals preserve the shared-seed structure instead of treating the five seeds as independent task-level observations.

E.5 Leakage and Checkpoint Safeguards

All transfer datasets, difficulty strata, stale-prompt pools, and qualitative cases are frozen before sampler tuning. Hyperparameters are selected on source validation data only, and a single setting is carried across the six held-out targets. The stale-prompt pool is constructed from observation history without inspecting future rewards, while policy-shift bins are defined from context distance before computing prediction errors. Any failed or interrupted run is rerun from the original paired checkpoint and disclosed rather than silently replaced by a favorable seed.

F Additional Generalization Results

F.1 Broad Held-Out Transfer

We extend the endpoint analysis to the six held-out targets defined by the cross-dataset protocol. MATH-trained checkpoints are evaluated on GSM8K, OlympiadBench, ARC-C, and MMLU-Pro;

Table 16: **Additional held-out transfer.** Scores are Pass@1 or accuracy (%), depending on the benchmark. The six-target macro is the equal-weight average over GSM8K, OlympiadBench, ARC-C, MMLU-Pro, CD-4, and MathVista.

Method	GSM8K	ARC-C	MMLU-Pro	MathVista	6-target Macro
HR	64.2	48.9	30.7	22.8	42.0
DS (oracle)	67.3	52.1	34.1	25.2	45.5
MoPPS	67.6	51.6	33.9	24.8	45.1
BOTS	66.8	51.4	33.5	24.5	44.8
DPS	67.9	51.9	34.1	25.0	45.5
PCS	68.8	52.7	34.6	25.9	46.1
DPS (Qwen3.5)	69.5	53.3	34.6	23.3	46.1
PCS (Qwen3.5)	70.5	54.2	35.2	23.2	46.7

Table 17: **Paired-seed held-out transfer.** Entries report the mean PCS–DPS difference in percentage points over five shared seeds, the paired 95% confidence interval, and the number of seeds for which PCS obtains the higher score.

Target	Mean Δ	95% CI	Wins / 5
GSM8K	$+0.87$	$[+0.15, +1.59]$	$4/5$
OlympiadBench	$+0.30$	$[-0.12, +0.72]$	$3/5$
ARC-C	$+0.81$	$[+0.25, +1.37]$	$4/5$
MMLU-Pro	$+0.46$	$[-0.08, +1.00]$	$3/5$
CD-4	$+0.44$	$[+0.03, +0.85]$	$4/5$
MathVista	$+0.93$	$[+0.09, +1.77]$	$4/5$
6-target Macro	$+0.64$	$[+0.28, +1.00]$	$4/5$

Countdown-trained checkpoints are evaluated on CD-4; and Geometry3K-trained checkpoints are evaluated on MathVista. OlympiadBench and CD-4 already appear in the main generalization table for the primary backbones, so Table 16 reports the four additional targets while retaining all six targets when computing the macro average.

For the Qwen3.5 comparison, the two targets omitted from the displayed columns are OlympiadBench, where DPS and PCS obtain 47.5 and 48.0, respectively, and CD-4, where they obtain 48.4 and 49.1. PCS has a higher measured score than DPS on all $6/6$ held-out targets with the primary backbones and on $5/6$ targets with Qwen3.5. The corresponding six-target macro improvements are $+0.6$ percentage points for the primary backbones and $+0.6$ percentage points for Qwen3.5.

F.2 Paired-Seed Robustness and Transfer During Training

Endpoint differences may be sensitive to training stochasticity. We therefore evaluate the same held-out targets using five shared training seeds and report paired PCS–DPS differences. Within each seed pair, PCS and DPS use the same source task, base checkpoint, GRPO budget, and evaluation examples. Confidence intervals are computed by paired bootstrap resampling over the five seed pairs. No run or checkpoint is selected using held-out target performance.

Across the six individual targets, the mean paired difference is positive in every case, with four targets having 95% confidence intervals that exclude zero. The six-target macro difference is $+0.64$ percentage points, with a paired 95% confidence interval of $[+0.28, +1.00]$. PCS also obtains the higher six-target macro in $4/5$ shared seeds.

To examine whether the transfer difference is specific to the final checkpoint, we additionally evaluate frozen checkpoints at 25%, 50%, 75%, and 100% of the source-task rollout budget. The held-out targets are used only for evaluation and are not used for checkpoint selection. Table 18 reports the six-target macro at each training stage.

PCS is below DPS by 0.2 points at the 25% checkpoint, exceeds DPS by 0.2 points at 50%, and the difference increases to $+0.6$ points at the final checkpoint. Thus, the endpoint difference is accompanied by a separation that emerges during training rather than appearing only at the final evaluation.

Table 18: **Held-out transfer throughout RL finetuning.** Entries are six-target held-out macro scores (%) evaluated at frozen checkpoints corresponding to different fractions of the source-task rollout budget.

Method	25%	50%	75%	100%
DPS	42.6	43.8	44.7	45.5
MoPPS	42.3	43.6	44.4	45.1
PCS	42.4	44.0	45.3	46.1

Table 19: **PCS–DPS transfer difference by target stratum.** Values are percentage-point differences with paired 95% confidence intervals, where positive values indicate higher scores for PCS. Q1 and Q4 denote the easiest and hardest quartiles for pre-RL difficulty and the nearest and farthest quartiles for source distance, respectively.

	Pre-RL difficulty		Source distance	
Quartile	Primary	Qwen3.5	Primary	Qwen3.5
Q1	$+0.18\,[-0.10, +0.46]$	$+0.16\,[-0.12, +0.44]$	$+0.79\,[+0.31, +1.27]$	$+0.82\,[+0.34, +1.30]$
Q2	$+0.43\,[+0.08, +0.78]$	$+0.39\,[+0.03, +0.75]$	$+0.72\,[+0.27, +1.17]$	$+0.71\,[+0.23, +1.19]$
Q3	$+0.71\,[+0.30, +1.12]$	$+0.68\,[+0.27, +1.09]$	$+0.61\,[+0.17, +1.05]$	$+0.56\,[+0.08, +1.04]$
Q4	$+1.18\,[+0.62, +1.74]$	$+1.17\,[+0.58, +1.76]$	$+0.42\,[-0.07, +0.91]$	$+0.31\,[-0.20, +0.82]$

F.3 Generalization by Difficulty and Source Distance

We next examine how the PCS–DPS transfer difference varies with target-example difficulty and source distance. Difficulty is estimated using independent completions from the frozen pre-RL checkpoint. Source distance is defined within each source–target and backbone setting as one minus the cosine similarity between a target-prompt representation and the centroid of the corresponding source-training prompt representations. Quartiles are constructed separately within each target before aggregation, so distance values from different targets or backbones are not compared on an absolute scale. For each quartile, we compute the paired item-level difference between PCS and DPS and then macro-average the difference across the held-out targets.

The two stratifications exhibit different measured patterns. Across pre-RL difficulty quartiles, the PCS–DPS difference increases from $+0.18$ to $+1.18$ percentage points for the primary backbones and from $+0.16$ to $+1.17$ percentage points for Qwen3.5. The 95% confidence intervals exclude zero for Q2–Q4 in both backbone settings, whereas the Q1 intervals include zero. Across source-distance quartiles, the measured difference instead decreases from $+0.79$ to $+0.42$ percentage points for the primary backbones and from $+0.82$ to $+0.31$ percentage points for Qwen3.5. The 95% confidence intervals for the farthest-distance quartile include zero in both backbone settings. These results show that the observed transfer difference is larger among examples that are more difficult under the pre-RL model, whereas it does not increase with greater source distance. This pattern is consistent with policy coupling being more beneficial for difficult examples that remain aligned with transferable source-task learning dynamics. Because both difficulty and source distance are observational stratifications, we treat these results as descriptive associations rather than causal evidence for the coupling mechanism.

G Full Prompt-State Prediction Evaluation

Prompt prediction is evaluated as an operational selection problem rather than only as terminal classification on the last training batch. The evaluation freezes a prompt pool, records its last observation and policy context, advances training without exposing future rewards to the sampler, and then labels the pool using a common rollout audit.

G.1 Metrics and Thresholding

For State 2, precision and recall are computed from the prompts predicted or selected as informative before the audit rollout. The F1 score is $2PR/(P + R)$, three-state accuracy evaluates the full unsolved/partial/solved partition, and the Brier score averages squared probability error over all three states. Expected calibration error partitions the maximum predicted probability into fixed bins




Figure 5: **Extended prediction and error diagnostics.** Panels show (a) recall for all three prompt states, (b) calibration, (c)–(d) joint observation-age and policy-shift false-negative rates for DPS and PCS, (e) State-2 precision–recall curves, and (f) error composition across six samplers.

and computes

$$\mathrm{ECE} = \sum_{b=1}^{K} \frac{|I_b|}{N} \left|\mathrm{acc}(I_b) - \mathrm{conf}(I_b)\right|. \tag{15}$$

For MoPPS and BOTS, scalar selection scores are mapped to three states using two thresholds tuned once on a frozen source-validation split. The thresholds are then fixed across tasks, ages, policy-shift quartiles, and held-out datasets. DS is treated as a rollout-based oracle signal and is never presented as a zero-cost predictor.

G.2 State Recall and Calibration

Panel (a) separates State 1, State 2, and State 3 recall so that a high State-2 F1 cannot conceal systematic confusion between fully unsolved and fully solved prompts. PCS reaches 82% recall on the middle state, compared with 70% for DPS, 72% for BOTS, and 66% for MoPPS. Panel (b) evaluates probability calibration rather than ranking alone. PCS obtains an ECE of 0.071 and a Brier score of 0.106, compared with 0.098/0.132 for DPS, 0.086/0.129 for BOTS, and 0.101/0.143 for MoPPS. These calibration metrics are computed before top-B truncation so that they reflect the full forecast pool.

Table 20: **Macro prediction report.** DS uses current candidate rollouts and therefore has a different cost boundary.

Method	State-2 F1 ↑	3-state acc. ↑	ECE ↓	Brier ↓	ESR ↑	Stale R@B ↑
HR	58	62	0.180	0.230	64	25
DS	96	94	0.040	0.060	82	91
MoPPS	79	77	0.101	0.143	71	32
BOTS	82	79	0.086	0.129	73	43
DPS	83	80	0.098	0.132	73	39
PCS	**88**	**83**	**0.071**	**0.106**	**75**	**62**

G.3 Joint Staleness and Policy Shift

Observation age alone is insufficient because an old prompt may remain easy to predict when the policy is nearly stationary. Panels (c)–(d) therefore cross four age bins with four context-shift quar-

tiles and report the State-2 false-negative rate in each cell. The most diagnostic cell is the lower-right regime, corresponding to prompts with both the largest context shift and more than 200 unobserved steps. In this regime, independent DPS reaches a 55% false-negative rate, whereas PCS reaches 29%. At the opposite low-age, low-shift corner, the corresponding false-negative rates are 12% for DPS and 11% for PCS. The widening gap with increasing observation age and policy shift is consistent with policy-coupled propagation being most useful when prompt-local observations become stale under a changing policy.

G.4 Threshold Robustness and Failure Composition

Panel (e) sweeps a common selection threshold without changing training and shows whether a method dominates only at one operating point. The PCS curve retains 89% precision at 80% recall, whereas DPS reaches 83% precision at 72% recall and BOTS reaches 81% at 70% recall. Panel (f) assigns audited errors to stale memory, overconfidence, underconfidence, or reward noise using mutually exclusive rules fixed before evaluation. The PCS distribution reduces stale errors to 18% of its failures from 39% for DPS and 29% for BOTS, while increasing the relative share of underconfidence. This trade-off is consistent with a sampler that revisits more candidates without claiming that every probability estimate improves.

G.5 Negative Controls

Three controls distinguish policy coupling from generic capacity. First, time-shuffling context vectors preserves their marginal distribution while destroying temporal alignment. Second, replacing context with selected-batch size and random noise preserves dimensionality without carrying policy information. Third, freezing the coupling tensor after warm-up tests whether continuing online adaptation is necessary. If any control matches full PCS on the age–shift matrix, the shared-policy interpretation is weakened even if endpoint Pass@1 remains high.

H Budget Curves, Cost Accounting, and Scaling

Endpoint rollouts alone do not reveal how quickly a sampler reaches useful quality or where its computation is spent. This section defines a generation-inclusive ledger and reports task-level budget curves, token efficiency, runtime composition, and prompt-pool scaling.

H.1 Generation-Inclusive Cost Model

For method m, total generated tokens are

$$C_m^{\mathrm{tok}} = C_m^{\mathrm{train}} + C_m^{\mathrm{filter}} + C_m^{\mathrm{audit}} + C_m^{\mathrm{eval}}, \tag{16}$$

where filtering includes discarded DS candidates and audit includes only diagnostic rollouts shared by all compared methods. The primary efficiency plots exclude evaluation and common audits because these terms cancel across methods, while the complete cost accounting records every component. Non-generation overhead is reported separately to prevent small matrix operations from being hidden by long reasoning rollouts.

H.2 Task-Level Budget Curves

Panels (a)–(c) place every measured checkpoint on the same 25–100% budget grid. PCS ends at $34.17\%/76.03\%/44.75\%$ on MATH, Countdown, and Geometry3K, compared with $32.71\%/74.27\%/44.47\%$ for DPS and $32.92\%/74.46\%/45.15\%$ for MoPPS. The Geometry3K panel therefore records a 0.28-point PCS gain over DPS and a 0.40-point MoPPS advantage rather than claiming task-wise PCS dominance. The area under each curve is computed by the trapezoidal rule after normalizing the horizontal axis by the task's standard budget.

H.3 Token and Runtime Decomposition

Panel (d) divides generated tokens by improvement over the shared base model and therefore penalizes methods that spend substantially more generation for a modest gain. The PCS ratio is 67.4




Figure 6: **Task-level efficiency and scaling suite.** Panels (a)–(c) report measured task-level budget curves; panels (d)–(f) show token efficiency, runtime composition, and prompt-pool scaling.

Table 21: **Quality and cost ledger.** All measured generation, timing, trajectory, and stability values use the common accounting boundary; Total R is the mean task-normalized rollout ratio.

Method	Total R (×) ↓	Tokens (M) ↓	R@95 (×) ↓	AUC (%) ↑	Drop (pp) ↓	Non-gen. ↓
HR	1.00	1,600	0.81	41.4	2.2	0.96
DS	3.73	4,500	2.87	44.4	1.3	1.08
MoPPS	1.00	1,510	0.78	45.3	1.4	1.04
BOTS	1.00	1,500	0.67	44.9	1.3	1.07
DPS	1.00	1,480	0.86	45.3	1.1	1.00
PCS	1.00	**1,460**	0.73	**46.5**	**0.5**	1.03

million tokens per point, compared with 72.3 for DPS, 72.5 for MoPPS, 74.6 for BOTS, 98.5 for HR, and 220.7 for DS. Panel (e) separates generation, actor update, and selection, showing that the PCS selection path occupies only 1.1% of wall time while DS generation occupies 84%. These percentages are reported per task because multimodal Geometry3K generation has a different cost profile from text-only MATH and Countdown.

H.4 Prompt-Pool Scaling

The broadcast step applies a $3 \times 3 \times 2$ modulation to every prompt and is therefore linear in pool size. Panel (f) tests this prediction from 10,000 to 500,000 prompts and compares PCS with MoPPS, BOTS, and DPS under the same CPU/GPU placement. PCS selection time grows from 7 to 225 ms, remaining below BOTS at 290 ms and MoPPS at 330 ms while exceeding DPS at 180 ms.

Table 22: **Resource scaling at 500k prompts.** Memory excludes the shared model and optimizer, and selection time excludes generation.

Method	Stored scalars/prompt	Shared scalars	Memory (MB)	Selection (ms)
MoPPS	2	4	12	330
BOTS	4	4	16	290
DPS	12	0	34	180
PCS	14	20	38	225

H.5 Reporting Criteria

PCS is considered rollout-efficient only if its paired Budget AUC exceeds DPS and BOTS while Total R remains at the equal-budget level. A wall-clock advantage is claimed only when all methods are run on the same hardware and software stack with synchronized timing boundaries. For very large pools, the reported pool-subsampling and broadcast-interval results expose the quality–overhead trade-off.

I Sensitivity, Capacity, and Interaction Tests

The main ablation establishes necessity, while this section tests whether the result depends on excessive coupling capacity, a narrow hyperparameter optimum, frequent dataset-wide broadcast, or forecasting every prompt at every step. The complete grid is fixed using source validation before target-test evaluation.

I.1 Coupling Capacity

Panel (a) fits low-rank auxiliary versions of the shared transition modulation while leaving prompt-local memories unchanged. Rank one underfits the MATH and Countdown shifts, rank two gains 0.4 points on both tasks, and ranks four or eight do not improve further. The nearly flat Geometry3K curve is a useful negative result because its current endpoint advantage is also negligible. These compressed variants are diagnostic only; the primary PCS model uses the full $3 \times 3 \times 2$ coupling tensor defined in Section 3.1. Panel (b) uses nested context features: mean success only at dimension one, mean success plus partially solved fraction at dimension two, and reward variance or entropy summaries at larger dimensions. The macro peaks at dimension two with 51.60%, suggesting that the benefit does not require a high-capacity policy representation.

Table 23: **Sensitivity grid and primary setting.** The primary setting is selected once on source validation and reused across tasks.

Factor	Values	Primary	Interpretation
Auxiliary coupling rank	$1, 2, 4, 8$	Full tensor	Compression diagnostic
Context dimension	$1, 2, 4, 8, 16$	2	Policy-summary capacity
Discovery γ	$0, 0.1, 0.25, 0.5, 0.75$	0.25	Rediscovery strength
EMA ρ	$0.8, 0.9, 0.95, 0.99, 0.995$	0.99	Context smoothing
Broadcast interval	$1, 2, 4, 8, 16$	1	Dataset update frequency
Forecast pool	$25, 50, 75, 100\%$	100%	Selection-time approximation

I.2 Discovery and EMA Operating Region

Panels (c)–(d) plot per-task changes rather than only the macro, preventing one task from masking sensitivity on another. The discovery optimum occurs near $\gamma = 0.25$, but MATH and Countdown remain above their zero-discovery values from 0.1 through 0.5. Geometry3K changes by at most 0.2 points, again exposing a task on which the mechanism may not help. EMA decay displays a broad plateau from 0.95 to 0.995; a collapse at either extreme would instead indicate under-smoothing or excessive lag.

I.3 Broadcast Frequency and Pool Approximation

Panel (e) normalizes macro quality and stale recall to their every-step values. The macro retains 99.2% at an eight-step interval, but stale recall retains only 88.7%, showing that endpoint accuracy alone can hide degraded rediscovery. Panel (f) forecasts only a fixed fraction of the eligible pool and measures the resulting quality–cost trade-off against BOTS and DPS. At 50% coverage, PCS retains a 51.35% macro versus 50.4% for DPS and 49.9% for BOTS.

I.4 Selection Rule

The primary configuration is chosen by source-validation macro and then frozen for all transfer, hard/OOD, and stress evaluations. No best-per-task or best-per-target tuning is permitted. The entire




Figure 7: **Capacity and sensitivity diagnostics.** Panels vary (a) the rank of an auxiliary low-rank coupling approximation, (b) policy-context dimension, (c) discovery weight, (d) EMA decay, (e) broadcast interval, and (f) the forecasted fraction of the prompt pool.

Table 24: **Context-feature ablation.** The feature sets are nested and use five paired seeds.

Context features	Dim.	Macro ↑	Stale R@B ↑	ECE ↓
Mean success only	1	51.20±0.9	54±3	0.091
+ Partially solved fraction	2	51.60±0.8	62±3	0.071
+ Reward variance and entropy	4	51.58±0.8	62±3	0.070
+ Higher-order batch moments	8	51.48±0.9	61±4	0.073

grid is reported, including settings that underperform DPS, with exploratory sweeps distinguished from the primary comparison.

J Additional Method Derivations and Implementation Details

This section expands the transition parameterization, discovery interpretation, update order, and resource bounds used by PCS. The analysis clarifies which information is shared and which prompt-specific quantities remain untouched.

J.1 Column-Wise Conditioned Transition

For a source state j, define the base logit vector $\boldsymbol{b}_j^\tau = \log(\bar{\Phi}_t^\tau(:, j) + \varepsilon)$ and the context modulation $\boldsymbol{u}_j(\boldsymbol{s}) = \boldsymbol{W}_t(:, j, :)\boldsymbol{s}$. The conditioned transition column is

$$\boldsymbol{\phi}_j^\tau(\boldsymbol{s}) = \mathrm{softmax}\big(\boldsymbol{b}_j^\tau + \boldsymbol{u}_j(\boldsymbol{s})\big)\,. \tag{17}$$

The base vector depends on prompt τ, whereas $\boldsymbol{W}_t$ and $\boldsymbol{s}$ are shared across the dataset. Consequently, two prompts can respond in the same direction to policy improvement while retaining different transition probabilities because their local Dirichlet histories differ.

The Jacobian of a transition column with respect to context is

$$\frac{\partial \boldsymbol{\phi}_j^\tau}{\partial \boldsymbol{s}} = \left[\mathrm{diag}(\boldsymbol{\phi}_j^\tau) - \boldsymbol{\phi}_j^\tau(\boldsymbol{\phi}_j^\tau)^\top\right] \boldsymbol{W}_t(:, j, :). \tag{18}$$

This expression exposes the two saturation regimes: coupling has little effect when a transition column is nearly deterministic, and it is most responsive when probability mass is distributed across destinations.

J.2 Discovery as a Counterfactual Difference

Let $\boldsymbol{d}_t^\tau = \boldsymbol{s}_t - \boldsymbol{s}_{\ell_t^\tau}$ denote the policy-context displacement since prompt τ was last observed. A first-order expansion of the discovery signal gives

$$\Delta_t^\tau \approx \boldsymbol{e}_2^\top \left.\frac{\partial \boldsymbol{\Phi}_t^\tau(\boldsymbol{s})}{\partial \boldsymbol{s}}\right|_{\boldsymbol{s}=\boldsymbol{s}_{\ell_t^\tau}} \boldsymbol{\mu}_t^{\tau,\mathrm{prior}} \boldsymbol{d}_t^\tau\,. \tag{19}$$

The approximation separates sensitivity of the prompt transition from the magnitude and direction of policy movement. A large context displacement alone does not produce a discovery bonus when the learned transition is insensitive in that direction. Similarly, a sensitive prompt receives little bonus when the policy context has not changed since its last observation.

Proposition J.1 (Bounded broadcast perturbation)**.** *Assume* $\|\boldsymbol{s} - \boldsymbol{s}'\|_\infty \le d$ *and* $\max_{i,j} \|\boldsymbol{w}_{t,i,j}\|_1 \le M$*. For every prompt and source state, the conditioned transition columns satisfy* $\|\boldsymbol{\phi}_j^\tau(\boldsymbol{s}) - \boldsymbol{\phi}_j^\tau(\boldsymbol{s}')\|_1 \le 2Md$*. Consequently,* $|\Delta_t^\tau| \le 2Md$*.*

Proof. The absolute entries of the softmax Jacobian sum to $2(1 - \|\boldsymbol{p}\|_2^2) \le 2$ for any probability vector $\boldsymbol{p}$. The mean-value theorem therefore gives $\|\mathrm{softmax}(\boldsymbol{a}) - \mathrm{softmax}(\boldsymbol{a}')\|_1 \le 2\|\boldsymbol{a} - \boldsymbol{a}'\|_\infty$. Hölder's inequality yields $\|\boldsymbol{W}_t(:, j, :)(\boldsymbol{s} - \boldsymbol{s}')\|_\infty \le Md$, proving the transition bound. Multiplying by a probability belief cannot increase the relevant ℓ_1 difference, and selecting its State-2 component proves the discovery bound. □

The proposition is deliberately conservative but shows that clipping the coupling norm and bounding the context prevents an arbitrarily large dataset-wide belief jump. The implementation clips each context feature to its valid range and may optionally project $\boldsymbol{W}_t$ to a fixed norm ball after the adaptive update.

J.3 Update Order and Information Flow

PCS follows a strict causal order at training step t. First, it scores the eligible prompt pool using only beliefs, contexts, and coupling parameters available before generation. Second, it rolls out the selected batch and performs the GRPO actor update. Third, it converts rewards into solving states, updates selected prompt-local memories, and aggregates the coupling gradient. Fourth, it updates the policy context and broadcasts the next prior to every prompt. Finally, it stores the new last-seen context only for prompts actually observed at the step. This order prevents the current audit reward from leaking into the decision that selected the prompt.

Table 25: **PCS state and operation inventory.** Counts assume three prompt states and the primary two-dimensional context.

Quantity or operation	Per prompt	Shared	Role
Predictive belief $\boldsymbol{\mu}^\tau$	3	0	Current three-state probability.
Dirichlet counts $\boldsymbol{\alpha}^\tau$	9	0	Prompt-local transition history.
Last-seen context $\boldsymbol{s}_{\ell^\tau}$	2	0	Counterfactual discovery reference.
Coupling tensor $\boldsymbol{W}$	0	18	Dataset-wide context modulation.
AdaGrad accumulator $\boldsymbol{G}$	0	18	Adaptive coupling update.
Current context $\boldsymbol{s}$	0	2	Shared policy-stage summary.
Broadcast forecast	$O(18)$	$O(1)$	Updates the next prior without rollout.

J.4 Computational Bounds

Let N be the prompt-pool size, B the selected batch size, $K = 3$ the state count, and $d = 2$ the context dimension. Local memory updates cost $O(BK^2)$, coupling-gradient aggregation costs $O(BK^2d)$, and dataset broadcast costs $O(NK^2d)$. The memory requirement is $O(N(K + K^2 + d) + K^2d)$ scalars, compared with $O(N(K + K^2))$ for DPS. These terms are independent of model parameter count and generated sequence length, which is why rollout generation remains the dominant cost in the intended regime.

J.5 Selected-Batch Context Bias

The context is estimated from selected prompts and may be biased toward the sampler's current beliefs. The primary method uses the unweighted selected-batch mean because it is stable and requires no propensity model. As a diagnostic, we add a small fixed exploration fraction and compare the primary context with a clipped inverse-propensity estimate on the randomized subset. Any systematic divergence or ranking change is reported as a limitation, and $\boldsymbol{s}_t$ is not interpreted as a population-wide competence estimate in that regime.

J.6 Numerical Safeguards

Base transition probabilities are floored by ε before taking logarithms, coupling gradients are averaged over the selected batch, and the adaptive denominator is stabilized by the same positive constant. The context features remain in $[0, 1]$, while transition columns are normalized by softmax after every modulation. All prompt memories are updated in vectorized blocks, but selected-state writes and last-seen-context writes use immutable prompt identifiers to prevent data-order drift. The released code logs the coupling norm, context norm, fraction of positive discovery scores, forecast entropy, and the number of prompts whose top predicted state changes after broadcast.

K Prompt Trajectories and Failure Taxonomy

Aggregate metrics cannot show whether a sampler discovers a prompt at the correct time or merely selects it often. This section links audited prompt trajectories to quantitative stress tests.

K.1 Three Canonical Trajectories

Panel (a) represents a prompt that was previously unsolved and becomes partially solved after the policy improves on related prompts. The PCS belief rises near the audited transition at step 40, while the independent DPS belief remains below 0.25 until step 80. Panel (b) reverses the direction: a partially solved prompt becomes fully solved, and PCS suppresses its State-2 probability earlier so that training rollouts are not spent on an exhausted example. Panel (c) contains two State-2 intervals separated by a forgetting event and tests whether discovery can react more than once rather than behaving as a monotone curriculum.

K.2 Rediscovery Delay Across Samplers

Panel (d) converts trajectory inspection into a distribution over every audited prompt that enters State 2 after at least one unobserved interval. At a 60-step threshold, PCS rediscovers 81% of




Figure 8: **Prompt-level dynamics and discovery diagnostics.** Panels show (a) delayed discovery, (b) a prompt becoming uninformative, (c) re-entry into the learnable region, (d) rediscovery-delay CDFs across six samplers, (e) selected-prompt observation-age mixtures, and (f) PCS–DPS gain versus context–transition alignment.

Table 26: **Trajectory-level audit.** Delay is measured from the first audited State-2 step to the first subsequent selection.

Case	DPS delay	PCS delay	Direction correct	Primary interpretation
Delayed discovery	40	0	Yes	Broadcast raises stale prompt priority.
Becoming uninformative	40	0	Yes	Current context reduces State-2 mass.
Re-entry after forgetting	40	0	Yes	Discovery reacts to non-monotone change.
Idiosyncratic prompt	20	20	No gain	Shared drift carries little information.

such prompts, compared with 53% for BOTS, 46% for DPS, 39% for MoPPS, and 30% for HR. DS reaches 97% because it audits an enlarged candidate set with additional rollouts, providing an upper-cost reference rather than an equal-budget predictor. We report median delay, 90th-percentile delay, failure to rediscover by training end, and the generated-token cost associated with each curve.

K.3 Observation-Age Mix

Panel (e) reports how each sampler allocates its selected batch across age bins. HR and DPS concentrate their selections on prompts seen within 50 steps, while PCS allocates 28% of its batch to prompts unseen for more than 100 steps. This statistic is not optimized directly and therefore acts as a behavioral check on discovery. Excessive old-prompt allocation accompanied by low ESR would instead indicate indiscriminate exploration.

K.4 When Shared Drift Helps

Panel (f) computes an alignment score between observed context displacement and the subsequent transition toward State 2. The MATH and Countdown gains increase with alignment, while Geometry3K remains below 0.5 points even at high alignment. This task difference is consistent with the smaller Geometry3K endpoint gain and identifies a boundary of the method. The alignment association remains after controlling for difficulty and observation age.

Table 27: **Failure taxonomy and discriminating tests.** The table contains no outcome values and is retained even if a failure category is rare.

Failure	Observable signature	Discriminating test
Stale local belief	Error grows jointly with age and context shift.	Age–shift matrix and rediscovery-delay CDF.
Context selection bias	Context differs from randomized audit subset.	Fixed exploration and clipped propensity diagnostic.
Spurious coupling	Shuffled context matches full PCS.	Time-shuffle and random-feature placebo.
Over-broadcast	Old prompts selected but ESR declines.	Observation-age mix crossed with selected-batch ESR.
Under-broadcast	Quality stable but stale recall falls with interval.	Broadcast-frequency retention curve.
Prompt-specific drift	High shift but inconsistent transition direction.	Alignment-stratified gains and family-level analysis.
Reward noise	Prediction error remains high at low age and low shift.	Repeated audit rollouts and parser disagreement.

L Dataset Cases and Evaluation Semantics

The following examples are drawn from public releases of the corresponding datasets and illustrate their input modalities and answer formats. Each case identifies its source split and example identifier or zero-based row index. We show dataset reference answers, except for Countdown, where a valid expression is supplied for the released numbers and target. These examples illustrate the data rather than sampler-generated responses or comparative performance.

L.1 Source-Task Cases

MATH example

Source. MATH-lighteval, train, row 2 (Algebra, Level 3).

Prompt. What is the degree of the polynomial $(4 + 5x^3 + 100 + 2\pi x^4 + \sqrt{10}x^4 + 9)$?

Reference answer. $\boxed{4}$.

Verifier. The final normalized value must equal 4.

Selection relevance. A prompt is State 2 when its response group contains both accepted and rejected final answers.

The MATH input is text-only, but correct grading depends on extracting a final mathematical object rather than judging the chain of thought. Equivalent forms should normalize to the same value, while an unsupported final answer may still receive task reward if the benchmark verifier checks only correctness. Sampler state therefore reflects the observed verifier outcome and must not use manual judgments about reasoning quality.

Countdown example

Source. Countdown-Tasks-3to4, train, row 0.

Dataset fields. Numbers: $[44, 19, 35]$; target: 98.

Task. Use each supplied number exactly once with the allowed arithmetic operations to reach the target.

Valid expression. `44+19+35=98`.


Verifier. The expression must evaluate to 98 and use exactly the supplied number multiset.

Selection relevance. Arithmetic errors or invalid number reuse produce rejected responses; State 1 requires every response in the group to be rejected.

CD-34 evaluates the same three-to-four-number regime used for primary Countdown training, while CD-4 fixes four-number targets as a compositional transfer set. The verifier parses an expression tree, checks the multiset of numeric leaves, permits only declared operations, and evaluates the expression under exact arithmetic where possible. This prevents a model from receiving reward for printing the target without a valid construction.

Geometry3K example

Source. Geometry3K, train, row 0.
Question. Find x.



Reference answer. $\boxed{3}$.
Answer check. The intersecting chords give $8x = 4 \times 6$, hence $x = 3$.
Verifier. The normalized final value must equal 3; the original diagram is part of the input.

Geometry3K is multimodal, so prompt identity includes the image asset, question text, image preprocessing, and chat template. Dropping or resizing the image differently for one sampler would change the task rather than only the selection rule. The controlled runner hashes the image bytes and serialized prompt after preprocessing so that every method receives identical multimodal inputs.

L.2 Held-Out Target Cases

ARC-C example

Source. ARC-Challenge, test; ID: `Mercury_SC_405086`.
Question. Snow, rain, hail, and fog are all forms of
Options. (A) gas. (B) water. (C) wind. (D) clouds.
Reference answer. `B` (water).
Verifier. The final extracted option must be one of the declared labels and match the key.

ARC-C tests whether a MATH-trained checkpoint transfers to multiple-choice scientific reasoning rather than only to another numeric-answer benchmark (Clark et al., 2018). The frozen prompt requires one option label after any explanation, and the parser rejects ambiguous outputs containing multiple final labels. Because option accuracy differs from mathematical exact match, ARC-C values are compared only when the same template and extraction rule are used.

MMLU-Pro example


Source. MMLU-Pro, test; question ID: 143; category: business.
Question. What percent of .65% is .42%?
Options.
(A) 500%; (B) 700%; (C) 646%; (D) 65%; (E) 60%;
(F) 800%; (G) 845%; (H) 75%; (I) 64.6%; (J) 550%.
Reference answer. `I` (64.6%).
Verifier. The final option label must match the official key after case normalization.

MMLU-Pro expands the choice set and emphasizes robust reasoning over broad knowledge domains (Wang et al., 2024). The evaluation template preserves all options in their official order and does not retune demonstrations or instructions for PCS. Subdomain accuracy is retained in the raw report so that a macro gain cannot hide a severe regression in one knowledge family.

MathVista example

Source. MathVista, testmini; problem ID: 74; underlying dataset: ChartQA.

Question. What is the difference of largest and smallest bar?



Reference answer. `47.6`.

Answer check. The chart gives $100 - 52.4 = 47.6$ percentage points.

Verifier. Apply the official floating-point answer normalization with the record's one-decimal precision.

Image attribution. Our World in Data; WHO/UNICEF JMP, as credited in the original chart.

MathVista tests multimodal transfer from geometric diagrams to broader visual mathematical reasoning (Lu et al., 2024). The image, question, answer type, and official normalization are kept intact, and target images are never embedded to tune the PCS context or discovery parameters. The analysis reports both overall accuracy and answer-type slices because diagram reading, chart arithmetic, and visual counting may respond differently to source training.

L.3 Answer Parsing Contract

Table 28: **Frozen parser and verifier contract by evaluation family.**

Family	Extraction	Verification	Rejected edge case
MATH / AIME / Olympiad	Last boxed or declared final expression	Symbolic or numeric normalization	Multiple incompatible final answers.
Countdown	Last complete arithmetic equality	Target value and exact number multiset	Correct target with illegal number reuse.
Geometry3K	Last boxed or declared quantity	Official normalized answer	Text prompt evaluated without its image.
ARC-C / MMLU-Pro	Final isolated option label	Exact option-key match	Several labels presented as final.
GSM8K	Final numeric answer	Numeric normalization	Unit text parsed as an extra number.
MathVista	Official answer-type extractor	Official short-answer score	Target-specific manual reinterpretation.

The parser version is part of the run configuration and is hashed alongside the prompt template. Parser changes are evaluated once on a disjoint audit set and then frozen before comparing samplers. If a parser correction changes historical rewards, all affected methods are rescored from stored generations or rerun; PCS alone is not selectively repaired.

Reward groups are converted to three prompt states by the same deterministic rule for DPS and PCS. State 1 means zero accepted responses, State 2 means the group contains both outcomes, and State 3 means every response is accepted. This ordering matches the fully unsolved, partially solved, and fully solved states defined in Section 3.1.

L.4 Case-Stratified Diagnostics

Qualitative cases are sampled by a predeclared grid rather than selected after inspecting favorable PCS outputs. The grid crosses source task, final DPS correctness, final PCS correctness, observation-age bin, policy-shift quartile, and whether discovery changed the top-B decision. At least one null or adverse PCS case is retained in each task whenever such a case exists.

Table 29: **Case strata and the mechanism question each stratum addresses.**

Stratum	Selection condition	Interpretation
Delayed discovery	Observed age > 200, DPS low, PCS selected	Tests whether shared drift recovers an old prompt.
False discovery	PCS selected, all rollout rewards equal	Tests acquisition error introduced by coupling.
Shared forgetting	Large context shift, State 2 to State 1	Tests whether broadcast removes obsolete prompts.
Geometry disagreement	PCS and DPS forecasts differ on an image prompt	Tests modality-specific coupling failure.
No-context control	Frozen or shuffled context selects the same prompt	Tests whether a case depends on temporal context.
DS-only recovery	DS finds State 2 while predictors miss it	Exposes the residual value of current rollouts.

Each released case includes only fields permitted by the dataset license: a stable example identifier, source and split, prompt-format summary, reward vector, observation age, context distance, DPS forecast, PCS forecast, discovery increment, selection outcome, and verifier result. Full copyrighted prompt text or images are omitted when redistribution is not allowed, while hashes and official dataset pointers preserve auditability. Case commentary distinguishes observation from interpretation and does not present a single trajectory as proof of an aggregate mechanism.

L.5 Leakage, Contamination, and Memorization Safeguards

Dataset membership is checked before training by canonicalized text hashes, normalized equation hashes where applicable, and image hashes for multimodal sets. Near-duplicate checks use token and embedding similarity only to flag pairs for review; they do not automatically delete semantically related but distinct competition problems. All exclusions are decided without inspecting sampler-specific performance and are applied to every method.

Target prompts never enter the PCS prompt pool, policy-context estimator, coupling update, discovery score, source-validation set, or early-stopping decision. Baseline results are not used to tune PCS toward a desired target margin, and all measured outcomes are retained regardless of whether they are favorable, tied, or reversed.

Memorization risk is reported separately from cross-dataset transfer. For benchmarks with publicly available solutions, the report includes contamination caveats and, where possible, an analysis restricted to newer or privately held audit items. Such an audit can qualify a transfer claim but does not replace measured evaluation on the frozen target sets.