Learning CLI Agents with Structured Action Credit under Selective Observation

Haoyang Su
Fudan University
Shanghai Innovation Institute

Ying Wen*
Shanghai Jiao Tong University
Shanghai Innovation Institute

Abstract

Command line interface (CLI) agents are emerging as a practical paradigm for agent-computer interaction over evolving filesystems, executable command line programs, and online execution feedback. Recent work has used reinforcement learning (RL) to learn these interaction abilities from verifiable task feedback, yet few methods exploit the native structured attributes of CLI actions as learning signals. Beyond this underused action structure, CLI learning also couples two bottlenecks for coding agents. First, the agent must identify task-relevant evidence in a large codebase from partial observations. Second, sparse terminal rewards must be assigned to the actions that shape a long multi-turn trajectory. We study these bottlenecks through shell-driven information extraction and file editing tasks. For selective observation, we introduce σ-Reveal, an inference-time mechanism that selects token-budgeted context for the same CLI. For credit assignment, we propose Action Advantage Assignment (A^3), a native agentic RL method that preserves the algorithmic complexity of standard agentic RL. A^3 constructs turn-level advantages from episode-level relative feedback, abstract syntax tree (AST) based action sub-chain residuals, and tree-level trajectory margins. To further evaluate this problem setting, we construct ShellOps, a verifiable dataset suite covering CLI tasks in repository environments. Our implementation is publicly available at `https://github.com/Hoyant-Su/Agentic-RL-A3`.

1 Introduction

Command line interface (CLI) agents have become a prominent setting for coding and computer use, studied in a large body of prior work [54, 65, 56, 18, 37, 2, 63, 34, 27, 75]. CLI agents operate directly in filesystem environments through shell commands, treating executable code as their native action space rather than calling predefined tool APIs. This interface gives language agents the same operational substrate used by developers, including directory exploration, program execution, artifact editing, and result checking through terminal feedback.

Training agents in this interface requires learning from feedback over long interactions rather than from isolated input output pairs. The resulting LLM interaction space is broad and only partially observed, exposing two coupled bottlenecks. First, the policy must act from a local view of a high dimensional workspace state. Second, sparse terminal rewards must be assigned to actions whose effects are mediated by many intermediate observations and file changes. Training language agents to act through multi-turn feedback in executable environments, including command line workspaces, remains an open problem [67, 68, 1, 70].

Trajectory-level supervised fine-tuning constructs annotated traces and trains the model to imitate them [42, 6, 64, 47], yet the resulting policy is bounded by the narrow coverage of its training

*Corresponding author.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).



Figure 1: Overview of the verifiable CLI task workflow. (a) ShellOps task instance with a natural language query, an initial workspace file tree, a verifiable gold bash solution, and the expected post execution workspace or standard output. (b) ShellOps and ShellOps-Pro coverage across file extensions and four task axes (Lookup, Aggregate, Edit, Mixed). (c) Unified verifiable loop with workspace observation, shell action generation, sandbox execution, and schema based scoring.

data, and recent analysis confirms that such imitation increases memorization of patterns tied to the interface rather than real task understanding [14]. Reinforcement learning (RL) addresses this limitation by letting the agent explore and optimize toward task-level rewards [44, 7, 39]. Tool-oriented RL methods decompose rewards into format validity, parameter accuracy, and tool selection correctness [28], or learn context control and execution structure to limit context growth during long interaction [15]. A complementary critic-free GRPO family, including GiGPO and HGPO [10, 16], uses observation-anchored or state-grouped normalization to refine credit assignment. These methods assume repeated states for within-state normalization, an assumption weakened by the large CLI and LLM state space, where nearly every observation can be unique. Existing paradigms therefore leave both partial workspace observation and sparse action credit unresolved for CLI agent learning.

In this work, we develop an agentic learning paradigm for CLI agents under partial workspace observation and sparse shell action credit. Our contributions are threefold. First, we propose σ-Reveal, a selective observation mechanism that constructs token budgeted initial workspace views for CLI rollouts. Second, we introduce an AST based action similarity measure and Action Advantage Assignment (A^3), a three channel advantage for episode, turn level, and tree level credit. Third, we construct ShellOps and ShellOps-Pro, two verifiable filesystem interaction partitions for long horizon CLI agents, as Fig. 1 shows.

2 Related Work

2.1 Workspace-Driven CLI Agents

Interleaved reasoning and environment actions have become the standard interface for tool use in language models [67]. Deployed coding agents such as Claude Code and Codex further illustrate this shift, with agents using terminal interfaces to inspect repositories, execute commands, and edit artifacts. As these agents move from isolated tool calls to repository-scale workspaces, understanding which files and execution evidence matter becomes increasingly important. Curating large tool inventories and adapters imposes engineering overhead, and executable code offers a compact

alternative in which the model invokes operating system primitives directly [54]. Open agent frameworks distribute implementation effort across models [26], while agent-computer interface designs map decisions to filesystem edits and shell control [65, 56, 50, 17, 62]. Scalable rollout infrastructure further decouples environment interaction from gradient computation in multi-turn agent training [71].

Benchmarks have emerged to evaluate this CLI agent setting through executable workspace interaction. SWE-bench evaluates candidate patches with executable tests on real issues [18], SWE-Gym learns from trajectories in the same agent stack [37], Terminal-Bench targets command line workflows under realistic side effects [34], and GrandCode applies agentic GRPO to multi-stage competitive programming with delayed rewards [27]. Across these benchmarks, relevant task evidence can be distributed across files, directories, generated outputs, and intermediate program states in a large workspace.

This distribution of evidence makes workspace observation a central difficulty for CLI agents. The initial view usually covers only a limited projection of the environment that the agent must understand for action selection and verification. We study shell-driven filesystem interaction through ShellOps as a verifiable suite for this regime, and introduce σ-Reveal to seek task-relevant workspace evidence under partial observation.

2.2 Agentic Reinforcement Learning

Standard RL fine-tuning for large language models distributes credit at token granularity within a single generation [36, 43, 45, 69, 3], while credit assignment across multi-turn environment interaction remains less settled [70, 46, 66, 29, 55, 79, 22].

Group-relative methods, notably GRPO, remove the separate value model and normalize rewards within each batch [44, 7, 35]. GRPO-λ adds token-level eligibility traces for single-turn reasoning [38]. These batch statistics still summarize whole rollouts without identifying which state transition changed the outcome, and multistep benchmarks show weak correlation between episode-level metrics and downstream task success [9, 33, 68, 60, 1, 31].

Recent agentic RL methods refine credit assignment in several directions. GSPO keeps the group relative objective at sequence scope [74], while GiGPO and HGPO anchor advantages on repeated states or hierarchical state groups [10, 16]. Turn-level RL and GTPO add rewards at each turn through MDP reformulation or execution signals [57, 8]. IGPO, ZeroSearch, and StepSearch use information gain to guide search trajectories [51, 48, 77]. iStar and SPA-RL learn process or progress estimators, while rStar resamples trajectories and RetroAgent adds retrospective feedback from an LLM judge [30, 52, 40, 73]. SkillRL, SKILL0, SLEA-RL, MemRL, and EvolveR introduce skill stores, retrieval, memory, or principle repositories into the policy loop [61, 32, 53, 72, 58]. Across these lines, credit assignment often depends on sequence normalization, repeated state anchors, learned estimators, retrieved context, or external judges. A^3 instead uses shell syntax directly in the advantage, without auxiliary models or state anchoring, at computational overhead comparable to conventional agentic RL.

3 Method

We consider conditions in which CLI rollouts use shell execution to induce filesystem state changes and reward functions evaluate the resulting terminal outputs and file state.

3.1 AST measure for CLI agent actions

CLI agent actions are executable shell programs rather than free-form text. Their parse structure provides a compact basis for comparing action intent during credit assignment and is amenable to accelerated batch computation. We quantify action intent by comparing AST signatures. Let $\mathrm{AST}(a)$ denote the Tree-sitter grammar for bash [5] applied to an action string a. The map Lin performs a fixed preorder traversal of $\mathrm{AST}(a)$ and appends tokens at each visit according to deterministic rules. Control structure nodes contribute tokens in $\mathcal{A}_K$ with kinds $\kappa \in \mathcal{T}_{\mathrm{ctrl}}$. Each command node contributes one token in $\mathcal{A}_V$ for the canonical verb and a finite sequence of tokens in $\mathcal{A}_W$ for literals after normalization. The full signature is the concatenation of these contributions in visit order, an

element of $\mathcal{A}^*$ with $\mathcal{A} = \mathcal{A}_K \cup \mathcal{A}_V \cup \mathcal{A}_W$. We summarize this signature map in (1).

$$\sigma(a) = \mathrm{Lin}(\mathrm{AST}(a)) \in \mathcal{A}^*. \tag{1}$$

Pairwise distance between actions is normalized Levenshtein distance [25] on signatures, as in (2).

$$d(a_i, a_j) = \frac{\mathrm{Lev}\big(\sigma(a_i), \sigma(a_j)\big)}{\max\big(|\sigma(a_i)|, |\sigma(a_j)|\big)} \in [0, 1]. \tag{2}$$

This distance compares shell actions by structural form rather than surface paths or literal values, and the complete action pair comparison is illustrated in Fig. 2.

3.2 σ-Reveal Context Harness

Command line tasks over workspaces provide only partial observations of the initial filesystem. At inference time, σ-Reveal defines a context selection mechanism for deciding which workspace evidence is selected before the first action, as Fig. 2 shows. Let FS_0 denote the initial file tree and o_0 the initial task observation. σ-Reveal assigns each node $x \in \mathrm{FS}_0$ a relevance score $\hat{\mu}(x \mid o_0)$ and a rendering cost $\tau(x)$, then selects a subtree-closed set under token budget B.

$$T^\star = \operatorname*{arg\,max}_{T \in \mathcal{C}_B(\mathrm{FS}_0)} \sum_{x \in T} \hat{\mu}(x \mid o_0), \tag{3}$$

where $\mathcal{C}_B(\mathrm{FS}_0)$ contains subtree-closed subsets T satisfying $\sum_{x \in T} \tau(x) \le B$. This constraint preserves directory context for selected files. The relevance score combines three signals:

$$\hat{\mu}(x \mid o_0) = \lambda_{\mathrm{cite}}\, \mathbf{1}\big[\mathrm{name}(x) \in \mathrm{tokens}(o_0)\big] + \lambda_{\mathrm{depth}}\, \beta^{\,\mathrm{depth}(x)} + \lambda_{\mathrm{ext}}\, \zeta\big(\mathrm{ext}(x) \,\big|\, \mathrm{type}(o_0)\big), \tag{4}$$

where $\mathrm{name}(x)$ is matched against task tokens, $\mathrm{depth}(x)$ gives a geometric tree prior with decay β, and $\zeta(\mathrm{ext}(x) \mid \mathrm{type}(o_0))$ scores the extension of x under the inferred task type. The weights λ_{cite}, λ_{depth}, and λ_{ext} set the relative contribution of these signals. At turn k, σ-Reveal constructs the prompt from the task instruction, the textual view of $T^\star$, the prior interaction history $h_{<k}$, and the current observation o_k.

3.3 Action Advantage Assignment

Given a batch of multi-turn rollouts, each rollout n under prompt u produces a sequence of shell actions at turns $k = 0, 1, \ldots, K_n - 1$ and receives a single episode return R_n at termination. A^3 constructs a per-turn advantage A_i for every turn instance $i = (u, n, k)$ by fusing three complementary signals that operate at episode, turn, and tree scope respectively, as Fig. 2 shows. The episode scope uses the most direct outcome feedback, the turn scope compares sibling actions at the same temporal position, and the tree scope compares branches induced by structurally similar action histories.

3.3.1 Episode Backbone

The first component contrasts each rollout against siblings that share the same prompt. Let $\mathcal{R}_u = \{R_{n'} : u(n') = u\}$ collect the episode returns of all rollouts under prompt u. The episode advantage is constant across turns of the same trajectory and uses normalization by the median and median absolute deviation (MAD), with ϵ as a stability constant.

$$A^{\mathrm{ep}}_{u,n,k} = \frac{R_n - \mathrm{median}(\mathcal{R}_u)}{\mathrm{MAD}(\mathcal{R}_u) + \epsilon}. \tag{5}$$

This term measures whether a rollout achieves a higher return than sibling rollouts sampled for the same task.

3.3.2 Turn-Level Action Sub-Chain Residual

For each turn instance $i = (u, n, k)$ and each scope $\ell \in \{\ell_1, \ldots, \ell_G\}$, we form the ℓ-step action sub-chain ending at turn k (or the full episode when $\ell{=}{-1}$), compute signatures via (1), and cluster all trajectories at (u, k, ℓ) by single-linkage on the distance in (2). Collecting the cluster labels over the G scopes yields a bucket tuple $\mathbf{b}_i \in \mathbb{Z}^G$ with one entry per scope for the action at turn k. Within



Figure 2: Schematic overview of the algorithm. An AST comparison for a pair of shell commands is shown on the left. σ-Reveal context injection for workspace-oriented information extraction is depicted on the above. Episode-level normalization, turn-level action structure credit, and tree-level bucket abstracted history credit are fused into the per-turn advantage for policy optimization.

each cluster at (u, k, ℓ), we compute a leave-one-out (LOO) mean of episode returns $\bar{R}^{\mathrm{LOO}}_{u,k,\ell}(n)$ and aggregate the residuals across scopes with normalized weights $\hat{w}_\ell$.

$$A_i^{\mathrm{intent}} = \sum_{\ell=1}^{G} \hat{w}_\ell \big(R_n - \bar{R}^{\mathrm{LOO}}_{u,k,\ell}(n)\big). \tag{6}$$

This residual captures how much a trajectory's return deviates from rollouts that executed structurally similar commands at the same turn, adding command-level credit beyond the episode backbone.

3.3.3 Tree Advantage on Bucket-Abstracted Histories

The bucket labels from all past turns of a trajectory form an abstract interaction history. Two turn instances i, j at the same (u, k) are merged into the same abstract state S when they share the same past turn set. Their past bucket labels must also have time-weighted Hamming dissimilarity below a threshold ξ. Within each abstract state, turn instances are further merged into abstract actions $\mathcal{K}$ by applying the same threshold to the bucket tuple at the current turn k. The value $V(S)$ is the average episode return of rollouts that reach abstract state S, while $V(\mathcal{K})$ is the average episode return of the branch that takes abstract action $\mathcal{K}$ from that state. The local margin δ_i and the discounted tree advantage A_i^{tree} accumulate along the trajectory with discount γ.

$$\delta_i = V\big(\mathcal{K}(i)\big) - V\big(S(i)\big), \qquad A_i^{\mathrm{tree}} = \delta_i + \gamma\, A_{i^+}^{\mathrm{tree}}. \tag{7}$$

This term measures whether the selected abstract action branch has higher return than the average branch from the same abstract state. The gate $g_i = n_i/(n_i + \alpha)$ uses the group count n_i to attenuate the tree signal when the abstract group contains few members, with prior α. The gated signal $g_i\, A_i^{\mathrm{tree}}$ is passed to the fusion stage.

3.3.4 Fusion

Each of the three channels, the episode backbone, the turn-level action sub-chain residual, and the gated tree advantage, is divided by its batch mean absolute value to align scales before combination. The normalized channels are combined with weights w_{intent} and w_{tree} and passed through a bounded

activation ϕ.

$$A_i = \phi\Big(\widetilde{A}_i^{\text{ep}} + w_{\text{intent}}\,\widetilde{A}_i^{\text{intent}} + w_{\text{tree}}\,\widetilde{g_i\,A_i^{\text{tree}}}\Big), \tag{8}$$

where $\widetilde{\cdot}$ denotes division by the batch mean absolute value of the operand, and ϕ is a bounded tanh activation that prevents large outliers from dominating the policy gradient.

3.3.5 Sequence-Level Policy Gradient

The fused advantage A_i is applied to the executable response at turn k. Following sequence-level policy optimization, the importance ratio is averaged over response tokens $a_{i,l}$ with histories $h_{i,l}$ and mask $m_{i,l}$, where $L_i = \sum_l m_{i,l}$.

$$\rho_i = \exp\left(\frac{1}{L_i}\sum_{l=1}^{L_i}\big(\log \pi_\theta(a_{i,l} \mid h_{i,l}) - \log \pi_{\theta_{\text{old}}}(a_{i,l} \mid h_{i,l})\big)\right). \tag{9}$$

The batch loss uses the clipped proximal policy optimization (PPO) surrogate with the A^3 advantage.

$$\mathcal{L} = -\frac{1}{N}\sum_{i=1}^{N}\min\big(\rho_i\,A_i,\ \text{clip}(\rho_i, 1{-}\epsilon_{\text{lo}}, 1{+}\epsilon_{\text{hi}})\,A_i\big). \tag{10}$$

4 Results

The experiments evaluate A^3 with σ-Reveal under matched budgets across task success, sampling quality, longer horizon transfer, component necessity, and computational cost.

4.1 Dataset Usage and Construction

Experiments use six benchmark streams normalized to a unified shell interface over filesystem workspaces. Five come from published resources, with AgentBench contributing operating-system and database tasks [29], DataBench covering tabular question answering [13], EHRCon testing clinical note–EHR consistency [23, 24, 12, 19], and TableBench targeting structured table reasoning [59]. Each instance is mapped to a common schema with a user instruction, reference bash solution, initial and optional gold file trees, and a programmatic reward over executed outputs or workspace state.

ShellOps contains a 1624 task standard corpus, with 714 in-distribution tasks used for scalable training and evaluation, and ShellOps-Pro adds 150 harder out-of-distribution tasks, whose workspaces contain 4063 files, average 27.1 files per task with a median of 25, and span 42 readable text extensions plus extensionless files across configuration, structured data, logs, code, prose, and specialised formats, as Fig. 1 shows.

This schema keeps evaluation tied to outcomes verifiable from filesystem state. Simulation data labels are produced by independent Claude Opus 4.7 audits [4] with live filesystem interaction and aggregated by majority vote. Public-corpus instances repeatedly judged hallucinatory or incorrectly labeled are excluded.

4.2 Experimental Configuration

All experiments are conducted on four NVIDIA H200 accelerators with Qwen3-14B [41] as the policy model and SGLang [76] for both training rollouts and inference. Training uses group size 4, learning rate $5{\times}10^{-7}$, train and validation batch sizes of 16, mini-batch size 16, and a maximum context length of $32{,}768$. The environment horizon is 6 steps, sandbox execution times out after 10 seconds, and the reward combines answer reward and progress reward with weights 3 and 0.2. For benchmarks without an official split we create a fixed 80% / 20% partition with random seed 42, then subsample 30% of the training instances with the same seed for policy gradient updates, running at most three epochs. A sliding-window Kullback-Leibler (KL) monitor stops optimization when the local KL range exceeds twice the initial range, preventing unstable updates before NaN failures. The pretrained Qwen3-14B baseline is evaluated with ReACT prompting [67]. A^3, GSPO, GiGPO, HGPO, and RetroAgent are GRPO-family RL baselines trained under the same configuration, with RetroAgent adding retrospective reflection [73]. LATS [78] and rStar [40] are Qwen3-14B agentic baselines using search or trajectory resampling. Kimi-K2.6 [21], GLM-5.1 [11], and Qwen3-235B-A22B [41] are evaluated as frontier agentic inference baselines. LLM Judge evaluation uses Qwen3-8B [41].

Table 1: Exact match scores (%) grouped by task type.

	STRING						FILES		HYBRID
Method	AB-OS	AB-DB	DataBench	EHRCon	ShellOps	TableBench	AB-DB	ShellOps	ShellOps
ReACT	57.9	15.1	63.7	61.5	26.0	18.7	37.8	7.1	7.2
LATS	40.0	8.5	54.1	41.5	27.5	20.4	38.8	10.9	9.1
rStar	35.9	4.6	46.4	36.7	18.5	15.7	39.1	8.7	7.0
GSPO	**61.4**	12.6	70.1	45.6	25.5	24.8	43.5	10.9	11.3
GiGPO	54.5	9.5	56.8	59.3	24.0	23.5	37.8	11.3	10.1
HGPO	46.9	12.1	44.3	54.1	23.5	18.5	38.7	11.9	9.5
RetroAgent	49.0	13.8	68.5	57.0	19.5	25.0	42.6	8.2	9.7
A^3 (Vanilla)	58.6	23.6	74.1	66.7	46.5	30.7	**46.6**	**26.5**	21.9
A^3 (σ-Reveal)	60.7	**26.2**	**77.9**	**67.4**	**48.5**	**31.6**	46.4	25.7	**24.6**

Table 2: Pass@k scores (%) across six benchmarks. Each cell reports Pass@3 / Pass@5.

Method	AB-OS	AB-DB	DataBench	EHRCon	ShellOps	TableBench
ReACT	**79.7 / 86.2**	38.2 / 41.2	79.7 / 82.7	77.2 / 83.3	16.6 / 20.6	30.9 / 36.6
LATS	59.3 / 65.5	37.7 / 41.2	77.6 / 85.3	61.7 / 70.4	21.4 / 27.7	33.7 / 38.4
rStar	53.1 / 58.6	36.1 / 41.2	72.5 / 80.0	63.3 / 70.4	13.8 / 17.5	28.5 / 33.5
GSPO	79.0 / 82.8	42.8 / 45.8	89.9 / 94.7	68.9 / 75.9	21.9 / 27.7	36.5 / 40.9
GiGPO	67.6 / 72.4	35.8 / 38.9	77.2 / 84.0	78.1 / 83.3	22.3 / 28.6	33.1 / 36.0
HGPO	62.8 / 69.0	37.8 / 41.2	70.9 / 81.3	71.1 / 75.9	21.9 / 28.3	31.5 / 37.2
RetroAgent	62.8 / 69.0	41.8 / 44.7	85.7 / 89.3	**79.1 / 85.2**	17.1 / 22.2	32.3 / 35.4
A^3 (Vanilla)	72.1 / 72.4	**51.1 / 55.3**	88.4 / 93.3	75.0 / 79.6	42.7 / 51.4	**43.0 / 47.0**
A^3 (σ-Reveal)	76.2 / 79.3	50.3 / 55.0	**92.7 / 96.0**	77.2 / 79.6	**46.2 / 55.7**	42.0 / 46.3

4.3 Main Results

Each benchmark task falls into one of three evaluation types. STRING tasks require the agent to extract or compute a textual answer. FILES tasks require in-place editing of workspace files, scored by line-level recall against the reference file changes. HYBRID tasks combine both.

Across database access, fact checking, table reasoning, and workspace state tasks, A^3 is the strongest Qwen3-14B method in Table 1. Both the vanilla and σ-Reveal settings outperform the agentic inference and RL baselines on the most demanding exact match streams, with the largest margins on ShellOps, which contains more composite workspace operations across string extraction, file editing, and hybrid outputs. The gap is clearest on ShellOps hybrid tasks, where A^3 reaches 21.9 exact match under the vanilla harness and 24.6 with σ-Reveal, while the strongest baseline reaches only 11.3, indicating a qualitative change in solving mixed terminal output and file-state objectives. Secondary metrics based on LLM Judge accuracy, line-level file-change recall, and their hybrid combination are reported in Appendix F.

Repeated sampling further amplifies the advantage of A^3 in Table 2. Pass@1 corresponds to the exact match results in Table 1 and is omitted here, leaving Pass@3 and Pass@5 to characterize the broader sampling regime. The gains are largest on file-intensive ShellOps, where A^3 with σ-Reveal reaches 46.2 and 55.7, compared with the strongest non-A^3 scores of 22.3 and 28.6. On text-dense benchmarks the margin narrows but remains competitive, with EHRCon reaching 77.2 at Pass@3 and 79.6 at Pass@5, close to the strongest scores of 79.1 and 85.2, indicating a stronger pool of successful trajectories on composite tasks.

Training stability in Figure 3 is measured through success rate, answer reward, entropy, and PPO surrogate KL. A^3 shows a steadily rising success rate and answer reward, while entropy remains sufficiently active for continued policy improvement rather than collapsing early. The PPO surrogate KL also stays bounded, indicating that the updates remain controlled as learning progresses.

4.4 Long-Horizon Comparison with Frontier Agents on ShellOps-Pro

On ShellOps-Pro, the same Qwen3-14B policy trained on the basic mixed benchmark is evaluated by inference in a larger setting with longer horizons and more practical workspace composition. Across



Figure 3: Training diagnostics on Qwen3-14B under matched data and rollout settings. A^3 keeps surrogate KL stable while reward continues to rise, whereas the baselines show delayed KL spikes, entropy collapse, or reward plateaus.

Table 3: ShellOps-Pro macro-average exact match accuracy (%) at $H_{\max} \in \{6, 8, 10\}$, across frontier, agentic inference, and agentic RL paradigms. Parentheses report gains over Vanilla A^3.

Method	$H_{\max}$=6	$H_{\max}$=8	$H_{\max}$=10
Frontier Agentic Inference			
Kimi-K2.6 [21]	**45.9**	**47.9**	**53.3**
GLM-5.1 [11]	34.7	39.1	40.7
Qwen3-235B-A22B [41]	26.7	29.3	28.3
Qwen3-14B Agentic Inference			
ReACT [41]	19.3	22.3	22.0
LATS [78]	21.1	21.7	19.7
rStar [40]	19.3	21.1	20.4
Qwen3-14B Agentic RL			
GSPO [74]	24.4	24.9	25.5
GiGPO [10]	27.1	26.3	25.7
HGPO [16]	19.5	21.9	22.8
RetroAgent [73]	18.0	19.2	20.0
A^3 (Ours, Vanilla)	22.9	25.9	25.3
A^3 (Ours, σ-Reveal)	**29.9 (+6.9)**	**30.5 (+4.7)**	**31.1 (+5.7)**

Table 4: Average ablation scores on the mixed benchmark with Qwen3-14B. EM reports exact match by type. Secondary reports LLM Judge for STRING (S.), file recall for FILES (F.), and combined score for HYBRID (H.).

	EM			Secondary		
HyperParam	S.	F.	H.	S.	F.	H.
Reference						
(a) Full A^3 ($\ell_{\max}$=3)	**44.5**	**38.1**	21.9	**46.1**	**50.8**	**47.2**
Channel ablation						
(b) w/o A^{intent}	38.2	32.9	17.2	39.0	44.9	36.1
(c) w/o A^{tree}	42.5	30.6	22.0	43.4	38.7	38.3
(d) w/o A^{intent}, A^{tree}	39.0	30.7	10.9	40.4	45.6	36.4
Action window granularity						
(e) $\ell_{\max}$=1	34.7	27.4	18.0	35.4	35.9	34.4
(f) $\ell_{\max}$=2	29.8	28.3	13.0	30.5	39.5	34.9
(g) $\ell_{\max}$=4	41.1	33.4	16.6	41.9	47.8	35.9
(h) $\ell_{\max}$=5	36.2	33.2	**23.2**	37.1	39.9	34.4

the horizon sweep in Table 3, A^3 remains the best Qwen3-14B agentic method and reaches the Qwen3-235B-A22B range at longer horizons, while a clear gap remains to Kimi-K2.6 and GLM-5.1, whose total parameter counts are about 1T and 744B, far larger than the 14B policy.

4.5 Ablation on A^3 Components

The ablation in Table 4 reports average scores on the mixed benchmark group, isolating the advantage branches of A^3 and the action window granularity under max step 6.

The full model performs best overall. Removing either the turn branch or the tree branch weakens performance, while keeping only the episode branch gives the weakest variant. The $\ell_{\max}$=3 setting used in the main experiments best matches the max step 6 rollout budget.

The channel diagnostics in Figure 4(a) track the three advantage signals in A^3 on the final Qwen3-14B run. The episode backbone and turn-level action sub-chain residual account for most of the post-weighting pre-tanh signal, with training-mean shares of 47.7% and 30.8%. The gated tree advantage contributes 21.5% after normalization and weighting.

4.6 Agentic Efficiency Comparison

Agentic efficiency is compared under the shared Qwen3-14B mixed benchmark setting in Table 5, where rollout cost covers policy sampling and sandbox execution across the multi-turn loop, and token columns report input and output usage per generated turn. A^3 keeps advantage computation at the cost level of standard group relative training, unlike GiGPO and HGPO variants with LLM judges whose advantage computation dominates training cost, while σ-Reveal adds input tokens only during inference.



(a) Component contribution

(b) Accuracy-cost Pareto view

Figure 4: Ablation and efficiency diagnostics for A^3. (a) Advantage-component magnitudes and training-mean contribution shares after fusion weighting. (b) ShellOps accuracy-cost Pareto view, using macro exact match and per-step advantage cost, with dashed non-A^3 RL SOTA and annotated A^3 with σ-Reveal gain.

Table 5: Agentic efficiency under the Qwen3-14B mixed benchmark setting. Training columns report rollout cost per token and advantage cost. Inference columns report turns and input / output tokens per turn. Dashes mark inference-only baselines. For A^3, inference columns report Vanilla / σ-Reveal, with σ-Reveal as an inference-time harness. Arrows indicate the preferred direction for cost columns.

	Training		Inference		
Method	Rollout (ms / Tok.) ↓	Adv. (s) ↓	Turns / Ep.	Input Tok. / Turn ↓	Output Tok. / Turn ↓
ReACT	–	–	5.03	0.89K	0.10K
LATS	–	–	4.42	1.74K	0.18K
rStar	–	–	5.00	0.89K	0.10K
GSPO	4.83	0.027	4.35	0.92K	0.09K
GiGPO (Seq. Match)	4.93	0.371	4.11	0.90K	0.09K
GiGPO (LLM Judge)	4.07	31.8	4.26	0.96K	0.10K
HGPO (Seq. Match)	3.42	4.084	3.81	0.91K	0.09K
HGPO (LLM Judge)	**3.41**	139.6	4.31	**0.88K**	0.09K
RetroAgent	5.43	**0.023**	3.77	0.99K	0.08K
A^3	3.74	**0.023**	4.33 / 4.18	0.99K / 1.11K	**0.08K** / 0.09K

Figure 4(b) combines the ShellOps exact match scores from Table 1 with the advantage cost measurements in Table 5, showing that A^3 occupies the high-accuracy, low-cost region among agentic RL methods.

5 Limitations

First, the AST based action abstraction uses shell structure as a scalable proxy for action intent, but structurally similar commands can differ in effect because of paths, file contents, options, or prior workspace state. Second, σ-Reveal provides a lightweight workspace prior for partial initial observations, but it cannot replace exhaustive evidence discovery when task relevance is weakly reflected in the file hierarchy. Third, the empirical scope is shell-driven filesystem interaction, and GUI, web, embodied, binary, or networked settings require further validation.

6 Conclusion

Shell-driven filesystem interaction exposes a learning regime in which agents must identify relevant workspace evidence under partial observation and assign delayed rewards to executable actions. σ-Reveal addresses the observation bottleneck by selecting token-budgeted workspace context before rollout, while A^3 assigns credit through episode, turn, and tree advantage channels built from shell command structure. Across the mixed benchmark suite and ShellOps-Pro, A^3 with σ-Reveal

achieves the strongest overall Qwen3-14B results in exact match and Pass@k, with especially large ShellOps gains and the best Qwen3-14B agentic RL performance at every ShellOps-Pro horizon. The diagnostics show stable optimization and complementary advantage channels at near-standard agentic RL cost. Together, these results identify workspace evidence selection and command structure as effective bases for CLI agent learning.

Acknowledgments and Disclosure of Funding

This work was supported by Shanghai Innovation Institute. The authors declare no competing financial interests or other financial relationships that could be perceived as influencing the work reported in this paper.

References

[1] Marwa Abdulhai, Isadora White, Charlie Victor Snell, Charles Sun, Joey Hong, Yuexiang Zhai, Kelvin Xu, and Sergey Levine. LMRL gym: Benchmarks for multi-turn reinforcement learning with language models. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 126–153. PMLR, 2025.

[2] Talor Abramovich, Meet Udeshi, Minghao Shao, Kilian Lieret, Haoran Xi, Kimberly Milner, Sofija Jancheska, John Yang, Carlos E. Jimenez, Farshad Khorrami, Prashanth Krishnamurthy, Brendan Dolan-Gavitt, Muhammad Shafique, Karthik R. Narasimhan, Ramesh Karri, and Ofir Press. EnIGMA: Interactive tools substantially assist LM agents in finding security vulnerabilities. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 246–355. PMLR, 2025.

[3] Arash Ahmadian, Chris Cremer, Matthias Gallé, Marzieh Fadaee, Julia Kreutzer, Olivier Pietquin, Ahmet Üstün, and Sara Hooker. Back to basics: Revisiting REINFORCE-style optimization for learning from human feedback in LLMs. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12248–12267, Bangkok, Thailand, 2024.

[4] Anthropic. Introducing claude opus 4.7. Anthropic research announcement, 2026.

[5] Max Brunsfeld and tree-sitter contributors. tree-sitter/tree-sitter: v0.25.3. Zenodo software release, 2025. Software, version 0.25.3.

[6] Baian Chen, Chang Shu, Ehsan Shareghi, Nigel Collier, Karthik Narasimhan, and Shunyu Yao. Fireact: Toward language agent fine-tuning, 2023.

[7] DeepSeek-AI. DeepSeek-R1 incentivizes reasoning in LLMs through reinforcement learning. *Nature*, 645:633–638, 2025.

[8] Yifeng Ding, Hung Le, Songyang Han, Kangrui Ruan, Zhenghui Jin, Varun Kumar, Zijian Wang, and Anoop Deoras. Empowering multi-turn tool-integrated agentic reasoning with group turn policy optimization, 2025.

[9] Alexandre Drouin, Maxime Gasse, Massimo Caccia, Issam H. Laradji, Manuel Del Verme, Tom Marty, David Vazquez, Nicolas Chapados, and Alexandre Lacoste. WorkArena: How Capable Are Web Agents at Solving Common Knowledge Work Tasks? In *International Conference on Machine Learning*, volume 235, pages 11642–11662, 2024.

[10] Lang Feng, Zhenghai Xue, Tingcong Liu, and Bo An. Group-in-group policy optimization for LLM agent training. In *Advances in Neural Information Processing Systems*, 2025.

[11] GLM-5 Team. GLM-5: from vibe coding to agentic engineering, 2026.

[12] Ary L. Goldberger, Luis A. N. Amaral, Leon Glass, Jeffrey M. Hausdorff, Plamen Ch. Ivanov, Roger G. Mark, Joseph E. Mietus, George B. Moody, Chung-Kang Peng, and H. Eugene Stanley. Physiobank, physiotoolkit, and physionet: Components of a new research resource for complex physiologic signals. *Circulation*, 101(23):e215–e220, 2000.

[13] Jorge Osés Grijalba, Luis Alfonso Ureña-López, Eugenio Martínez Cámara, and Jose Camacho-Collados. Question answering over tabular data with DataBench: A large-scale empirical evaluation of LLMs. In *Proceedings of LREC-COLING 2024*, Turin, Italy, 2024.

[14] Weizheng Gu, Chengze Li, Zhuohao Yu, Mengyuan Sun, Zhibang Yang, Wei Wang, Hongrui Jia, Shikun Zhang, and Wei Ye. What do agents learn from trajectory-sft: Semantics or interfaces?, 2026.

[15] Karan Gupta, Pranav Vajreshwari, Yash Pandya, Raghav Magazine, Akshay Nambi, and Ahmed Awadallah. Scaling agentic capabilities, not context: Efficient reinforcement finetuning for large toolspaces, 2026.

[16] Shuo He, Lang Feng, Qi Wei, Xin Cheng, Lei Feng, and Bo An. Hierarchy-of-groups policy optimization for long-horizon agentic tasks, 2026.

[17] Qian Huang, Jian Vora, Percy Liang, and Jure Leskovec. MLAgentBench: Evaluating language agents on machine learning experimentation. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp, editors, *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 20271–20309. PMLR, 21–27 Jul 2024.

[18] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world github issues? In *The Twelfth International Conference on Learning Representations*, 2024.

[19] Alistair E. W. Johnson, Tom J. Pollard, Lu Shen, Li-Wei H. Lehman, Mengling Feng, Mohammad Ghassemi, Benjamin Moody, Peter Szolovits, Leo Anthony Celi, and Roger G. Mark. MIMIC-III, a freely accessible critical care database. *Scientific Data*, 3:160035, 2016.

[20] Michael Kerrisk. *The Linux Programming Interface: A Linux and UNIX System Programming Handbook*. No Starch Press, 2010.

[21] Kimi Team. Kimi K2.5: Visual agentic intelligence, 2026.

[22] Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Russ Salakhutdinov, and Daniel Fried. VisualWebArena: Evaluating multimodal agents on realistic visual web tasks. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 881–905, Bangkok, Thailand, August 2024. Association for Computational Linguistics.

[23] Yeonsu Kwon, Jiho Kim, Gyubok Lee, Seongsu Bae, Daeun Kyung, Wonchul Cha, Tom Pollard, Alistair Johnson, and Edward Choi. Ehrcon: Dataset for checking consistency between unstructured notes and structured tables in electronic health records. In *Advances in Neural Information Processing Systems*, volume 37, pages 89334–89345. Curran Associates, Inc., 2024.

[24] Yeonsu Kwon, Jiho Kim, Gyubok Lee, Seongsu Bae, Daeun Kyung, Wonchul Cha, Tom Pollard, Alistair Johnson, and Edward Choi. EHRCon: Dataset for checking consistency between unstructured notes and structured tables in electronic health records. *PhysioNet*, mar 2025. Version 1.0.1.

[25] Vladimir I. Levenshtein. Binary codes capable of correcting deletions, insertions and reversals. *Soviet Physics Doklady*, 10(8):707–710, 1966.

[26] Chenliang Li, Hehong Chen, Ming Yan, Weizhou Shen, Haiyang Xu, Zhikai Wu, Zhicheng Zhang, Wenmeng Zhou, Yingda Chen, Chen Cheng, Hongzhu Shi, Ji Zhang, Fei Huang, and Jingren Zhou. ModelScope-agent: Building your customizable agent system with open-source large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, Singapore, 2023.

[27] Xiaoya Li, Xiaofei Sun, Guoyin Wang, Songqiao Su, Chris Shum, Jiwei Li, and DeepReinforce Team. Grandcode: Achieving grandmaster level in competitive programming via agentic reinforcement learning, 2026.

[28] Pengbo Liu. Toolrla: Multiplicative reward decomposition for tool-integrated agents, 2026.

[29] Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. Agentbench: Evaluating LLMs as agents. In *The Twelfth International Conference on Learning Representations*, 2024.

[30] Xiaoqian Liu, Ke Wang, Yuchuan Wu, Fei Huang, Yongbin Li, Jianbin Jiao, and Junge Zhang. Agentic reinforcement learning with implicit step rewards. In *The Fourteenth International Conference on Learning Representations*, 2026.

[31] Jiarui Lu, Thomas Holleis, Yizhe Zhang, Bernhard Aumayer, Feng Nan, Haoping Bai, Shuang Ma, Shen Ma, Mengyu Li, Guoli Yin, Zirui Wang, and Ruoming Pang. ToolSandbox: A stateful, conversational, interactive evaluation benchmark for LLM tool use capabilities. In Luis Chiruzzo, Alan Ritter, and Lu Wang, editors, *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 1160–1183, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-195-7.

[32] Zhengxi Lu, Zhiyuan Yao, Jinyang Wu, Chengcheng Han, Qi Gu, Xunliang Cai, Weiming Lu, Jun Xiao, Yueting Zhuang, and Yongliang Shen. SKILL0: In-context agentic reinforcement learning for skill internalization, 2026.

[33] Chang Ma, Junlei Zhang, Zhihao Zhu, Cheng Yang, Yujiu Yang, Yaohui Jin, Zhenzhong Lan, Lingpeng Kong, and Junxian He. AgentBoard: An Analytical Evaluation Board of Multi-Turn LLM Agents. In *Neural Information Processing Systems*, 2024.

[34] Mike A. Merrill, Alexander G. Shaw, Nicholas Carlini, Boxuan Li, Harsh Raj, Ivan Bercovich, Lin Shi, Jeong Yeon Shin, Thomas Walshe, E. Kelly Buchanan, Junhong Shen, Guanghao Ye, Haowei Lin, Jason Poulos, Maoyu Wang, Marianna Nezhurina, Jenia Jitsev, Di Lu, Orfeas Menis Mastromichalakis, Zhiwei Xu, Zizhao Chen, Yue Liu, Robert Zhang, Leon Liangyu Chen, Anurag Kashyap, Jan-Lucas Uslu, Jeffrey Li, Jianbo Wu, Minghao Yan, Song Bian, Vedang Sharma, Ke Sun, Steven Dillmann, Akshay Anand, Andrew Lanpouthakoun, Bardia Koopah, Changran Hu, Etash Guha, Gabriel H. S. Dreiman, Jiacheng Zhu, Karl Krauth, Li Zhong, Niklas Muennighoff, Robert Amanfu, Shangyin Tan, Shreyas Pimpalgaonkar, Tushar Aggarwal, Xiangning Lin, Xin Lan, Xuandong Zhao, Yiqing Liang, Yuanli Wang, Zilong Wang, Changzhi Zhou, David Heineman, Hange Liu, Harsh Trivedi, John Yang, Junhong Lin, Manish Shetty, Michael Yang, Nabil Omi, Negin Raoof, Shanda Li, Terry Yue Zhuo, Wuwei Lin, Yiwei Dai, Yuxin Wang, Wenhao Chai, Shang Zhou, Dariush Wahdany, Ziyu She, Jiaming Hu, Zhikang Dong, Yuxuan Zhu, Sasha Cui, Ahson Saiyed, Arinbjörn Kolbeinsson, Jesse Hu, Christopher Michael Rytting, Ryan Marten, Yixin Wang, Alex Dimakis, Andy Konwinski, and Ludwig Schmidt. Terminal-bench: Benchmarking agents on hard, realistic tasks in command line interfaces, 2026.

[35] Youssef Mroueh, Nicolas Dupuis, Brian Belgodere, Apoorva Nitsure, Mattia Rigotti, Kristjan Greenewald, Jiri Navratil, Jarret Ross, and Jesus Rios. Revisiting group relative policy optimization: Insights into on-policy and off-policy training. In *The Fourteenth International Conference on Learning Representations*, 2026.

[36] Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744, 2022.

[37] Jiayi Pan, Xingyao Wang, Graham Neubig, Navdeep Jaitly, Heng Ji, Alane Suhr, and Yizhe Zhang. Training software engineering agents and verifiers with SWE-gym. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*. PMLR, 2025.

[38] Prasanna Parthasarathi, Mathieu Reymond, Boxing Chen, Yufei Cui, and Sarath Chandar. Grpo-λ: Credit assignment improves llm reasoning, 2025.

[39] Zehan Qi, Xiao Liu, Iat Long Iong, Hanyu Lai, Xueqiao Sun, Jiadai Sun, Xinyue Yang, Yu Yang, Shuntian Yao, Wei Xu, Jie Tang, and Yuxiao Dong. WebRL: Training LLM web agents via self-evolving online curriculum reinforcement learning. In *The Thirteenth International Conference on Learning Representations*, 2025.

[40] Zhenting Qi, Mingyuan Ma, Jiahang Xu, Li Lyna Zhang, Fan Yang, and Mao Yang. Mutual reasoning makes smaller LLMs stronger problem-solvers. In *The Thirteenth International Conference on Learning Representations*, 2025.

[41] Qwen Team. Qwen3 technical report, 2025.

[42] Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

[43] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017.

[44] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models, 2024.

[45] Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. HybridFlow: A flexible and efficient RLHF framework. In *Proceedings of the Twentieth European Conference on Computer Systems (EuroSys '25)*, 2025.

[46] Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Côté, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. ALFWorld: Aligning text and embodied environments for interactive learning. In *International Conference on Learning Representations*, 2021.

[47] Haoyang Su, Shaoting Zhang, and Xiaosong Wang. Lammi-pathology: A tool-centric bottom-up lvlm-agent framework for molecularly informed medical intelligence in pathology, 2026. arXiv:2602.18773 [cs.AI].

[48] Hao Sun, Zile Qiao, Jiayan Guo, Xuanbo Fan, Yingyan Hou, Yong Jiang, Pengjun Xie, Yan Zhang, Fei Huang, and Jingren Zhou. ZeroSearch: Incentivize the search capability of LLMs without searching, 2025.

[49] The Linux Kernel Developers. Landlock LSM: Kernel documentation. Linux kernel documentation, 2026.

[50] Harsh Trivedi, Tushar Khot, Mareike Hartmann, Ruskin Manku, Vinty Dong, Edward Li, Shashank Gupta, Ashish Sabharwal, and Niranjan Balasubramanian. AppWorld: A controllable world of apps and people for benchmarking interactive coding agents. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16022–16076, Bangkok, Thailand, August 2024. Association for Computational Linguistics.

[51] Guoqing Wang, Sunhao Dai, Guangze Ye, Zeyu Gan, Wei Yao, Yong Deng, Xiaofeng Wu, and Zhenzhe Ying. Information gain-based policy optimization: A simple and effective approach for multi-turn search agents. In *The Fourteenth International Conference on Learning Representations*, 2026.

[52] Hanlin Wang, Chak Tou Leong, Jiashuo Wang, Jian Wang, and Wenjie Li. Spa-rl: Reinforcing llm agents via stepwise progress attribution, 2025.

[53] Prince Zizhuang Wang and Shuli Jiang. SLEA-RL: Step-level experience augmented reinforcement learning for multi-turn agentic training, 2026.

[54] Xingyao Wang, Yangyi Chen, Lifan Yuan, Yizhe Zhang, Yunzhu Li, Hao Peng, and Heng Ji. Executable code actions elicit better LLM agents. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 50208–50232. PMLR, 2024.

[55] Xingyao Wang, Zihan Wang, Jiateng Liu, Yangyi Chen, Lifan Yuan, Hao Peng, and Heng Ji. MINT: Evaluating LLMs in Multi-Turn Interaction with Tools and Language Feedback. In *International Conference on Learning Representations*, 2024.

[56] Xingyao Wang, Boxuan Li, Yufan Song, Frank F. Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, Hoang H. Tran, Fuqiang Li, Ren Ma, Mingzhang Zheng, Bill Qian, Yanjun Shao, Niklas Muennighoff, Yizhe Zhang, Binyuan Hui, Junyang Lin, Robert Brennan, Hao Peng, Heng Ji, and Graham Neubig. OpenHands: An open platform for ai software developers as generalist agents. In *The Thirteenth International Conference on Learning Representations*, 2025.

[57] Quan Wei, Siliang Zeng, Chenliang Li, William Brown, Oana Frunza, Wei Deng, Anderson Schneider, Yuriy Nevmyvaka, Yang Katie Zhao, Alfredo Garcia, and Mingyi Hong. Reinforcing multi-turn reasoning in llm agents via turn-level reward design, 2025.

[58] Rong Wu, Xiaoman Wang, Jianbiao Mei, Pinlong Cai, Daocheng Fu, Cheng Yang, Licheng Wen, Xuemeng Yang, Yufan Shen, Yuxin Wang, and Botian Shi. EvolveR: Self-evolving LLM agents through an experience-driven lifecycle, 2025.

[59] Xianjie Wu, Jian Yang, Linzheng Chai, Ge Zhang, Jiaheng Liu, Xeron Du, Di Liang, Daixin Shu, Xianfu Cheng, Tianzhen Sun, et al. Tablebench: A comprehensive and complex benchmark for table question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 25497–25506, 2025.

[60] Zhiheng Xi, Yiwen Ding, Wenxiang Chen, Boyang Hong, Honglin Guo, Junzhe Wang, Xin Guo, Dingwen Yang, Chenyang Liao, Wei He, Songyang Gao, Lu Chen, Rui Zheng, Yicheng Zou, Tao Gui, Qi Zhang, Xipeng Qiu, Xuanjing Huang, Zuxuan Wu, and Yu-Gang Jiang. AgentGym: Evaluating and training large language model-based agents across diverse environments. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 27914–27961, Vienna, Austria, 2025. Association for Computational Linguistics.

[61] Peng Xia, Jianwen Chen, Hanyang Wang, Jiaqi Liu, Kaide Zeng, Yu Wang, Siwei Han, Yiyang Zhou, Xujiang Zhao, Haifeng Chen, Zeyu Zheng, Cihang Xie, and Huaxiu Yao. SkillRL: Evolving agents via recursive skill-augmented reinforcement learning, 2026.

[62] Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, Yitao Liu, Yiheng Xu, Shuyan Zhou, Silvio Savarese, Caiming Xiong, Victor Zhong, and Tao Yu. OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments. In *Neural Information Processing Systems*, 2024.

[63] Frank F. Xu, Yufan Song, Boxuan Li, Yuxuan Tang, Kritanjali Jain, Mengxue Bao, Zora Zhiruo Wang, Xuhui Zhou, Zhitong Guo, Murong Cao, Mingyang Yang, Hao Yang Lu, Amaad Martin, Zhe Su, Leander Melroy Maben, Raj Mehta, Wayne Chi, Lawrence Keunho Jang, Yiqing Xie, Shuyan Zhou, and Graham Neubig. TheAgentCompany: Benchmarking LLM agents on consequential real world tasks. In *Advances in Neural Information Processing Systems*, 2025.

[64] Yiheng Xu, Dunjie Lu, Zhennan Shen, Junli Wang, Zekun Wang, Yuchen Mao, Caiming Xiong, and Tao Yu. Agenttrek: Agent trajectory synthesis via guiding replay with web tutorials. In *The Thirteenth International Conference on Learning Representations*, 2025.

[65] John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems*, volume 37, 2024.

[66] Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. WebShop: Towards scalable real-world web interaction with grounded language agents. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

[67] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations*, 2023.

[68] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik R. Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. In *The Thirteenth International Conference on Learning Representations*, 2025.

[69] Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Wang Zhang, Hang Zhu, Jinhua Zhu, Jiaze Chen, Jiangjie Chen, Chengyi Wang, Hongli Yu, Yuxuan Song, Xiangpeng Wei, Hao Zhou, Jingjing Liu, Wei-Ying Ma, Ya-Qin Zhang, Lin Yan, Mu Qiao, Yonghui Wu, and Mingxuan Wang. DAPO: An open-source LLM reinforcement learning system at scale. In *Advances in Neural Information Processing Systems*, 2025.

[70] Chenchen Zhang. From reasoning to agentic: Credit assignment in reinforcement learning for large language models, 2026.

[71] Hao Zhang, Mingjie Liu, Shaokun Zhang, Songyang Han, Jian Hu, Zhenghui Jin, Yuchi Zhang, Shizhe Diao, Ximing Lu, Binfeng Xu, Zhiding Yu, Jan Kautz, and Yi Dong. Prorl agent: Rollout-as-a-service for rl training of multi-turn llm agents, 2026.

[72] Shengtao Zhang, Jiaqian Wang, Ruiwen Zhou, Junwei Liao, Yuchen Feng, Zhuo Li, Yujie Zheng, Weinan Zhang, Ying Wen, Zhiyu Li, Feiyu Xiong, Yutao Qi, Bo Tang, and Muning Wen. MemRL: Self-evolving agents via runtime reinforcement learning on episodic memory, 2026.

[73] Xiaoying Zhang, Zichen Liu, Yipeng Zhang, Xia Hu, and Wenqi Shao. Retroagent: From solving to evolving via retrospective dual intrinsic feedback. *arXiv preprint arXiv:2603.08561*, 2026.

[74] Chujie Zheng, Shixuan Liu, Mingze Li, Xiong-Hui Chen, Bowen Yu, Chang Gao, Kai Dang, Yuqiong Liu, Rui Men, An Yang, Jingren Zhou, and Junyang Lin. Group sequence policy optimization, 2025.

[75] Junhao Zheng, Xidi Cai, Qiuke Li, Duzhen Zhang, ZhongZhi Li, Yingying Zhang, Le Song, and Qianli Ma. Lifelongagentbench: Evaluating llm agents as lifelong learners, 2025.

[76] Lianmin Zheng, Liangsheng Yin, Zhiqiang Xie, Chuyue Sun, Jeff Huang, Cody Hao Yu, Shiyi Cao, Christos Kozyrakis, Ion Stoica, Joseph E. Gonzalez, Clark Barrett, and Ying Sheng. SGLang: Efficient execution of structured language model programs. In *Neural Information Processing Systems*, 2024.

[77] Xuhui Zheng, Kang An, Ziliang Wang, Yuhang Wang, and Yichao Wu. StepSearch: Igniting LLMs search ability via step-wise proximal policy optimization. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2025.

[78] Andy Zhou, Kai Yan, Michal Shlapentokh-Rothman, Haohan Wang, and Yu-Xiong Wang. Language agent tree search unifies reasoning, acting, and planning in language models. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024.

[79] Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. WebArena: A Realistic Web Environment for Building Autonomous Agents. In *International Conference on Learning Representations*, 2024.

A Dataset Details

Each ShellOps instance belongs to one of four capability axes. Lookup emits deduplicated matching values, aggregate returns a scalar from scattered evidence, edit rewrites files with verifiable post-states, and mixed combines exact stdout with a derived file artifact. Table 6 reports the per-axis distribution.

Table 6: Per-axis distribution of the ShellOps suite, with percentages of the corpus total in parentheses.

Task type	Lookup	Aggregate	Edit	Mixed	Total
ShellOps	554 (34.1%)	200 (12.3%)	162 (10.0%)	708 (43.6%)	1624
ShellOps-Pro	28 (18.7%)	29 (19.3%)	43 (28.7%)	50 (33.3%)	150

Figures 5 and 6 characterize the agent visible task workspace of the ShellOps standard corpus and the ShellOps-Pro split.

The standard corpus contains 1624 tasks, 5679 files, a median of 3 files per task, and a median task footprint of 380.5 B. ShellOps-Pro contains 150 tasks, 4063 files, a median of 25 files per task, and a median task footprint of 7.8 KB. The largest single file is 24.7 KB in ShellOps-Pro, compared with 3.4 KB in the standard corpus.



Figure 5: ShellOps standard corpus task workspace profile across 1624 tasks. Panel A ranks file extensions by file count and byte volume. Panel B reports content category composition by task type. Panel C shows file size dispersion on a log scale axis. Panel D places each task by file count and byte volume. The internal harness directory is excluded.

B Components of the Agentic RL Infrastructure

This appendix specifies the two interfaces that mediate between the policy π_θ and the underlying filesystem, a structured action protocol that converts free-form generations into machine-checkable actions, and a sandbox that executes the shell payload of each action with network and filesystem isolation.



Figure 6: ShellOps-Pro task workspace profile across 150 tasks. Panel A ranks file extensions by file count and byte volume. Panel B reports content category composition by task type. Panel C shows file size dispersion on a log scale axis. Panel D places each task by file count and byte volume. The internal harness directory is excluded.

B.1 Action Protocol

At every turn the policy emits a response $y_k \in \Sigma^*$ that is required to belong to one of two regular languages over the Unicode alphabet Σ, a code language $\mathcal{L}_{\text{code}}$, and an answer language $\mathcal{L}_{\text{ans}}$ that terminates the episode. The plan, code, and answer fields carry fixed length budgets L_P, L_C, L_A that are embedded in the regex quantifiers themselves and enforced at decoding time by constrained decoding inside SGLang 0.4.6.post5 [76]. Malformed or over-length responses are rejected in a single automaton pass. The parser Φ returns a typed action together with character spans that downstream modules reuse to broadcast advantages onto the executable payload rather than the natural-language wrapper. Box 1 gives the full specification.

Box 1. Action protocol Φ.

Let Σ be the Unicode alphabet and $L_P, L_C, L_A \in \mathbb{N}_{>0}$ the plan, code, and answer length budgets. The code and answer languages are

$$\mathcal{L}_{\text{code}} = \texttt{<name>submit_code</name><plan>}\,\Sigma^{[1,L_P]}\,\texttt{</plan><code>}\,\Sigma^{[1,L_C]}\,\texttt{</code>},$$
$$\mathcal{L}_{\text{ans}} = \texttt{<name>submit_answer</name><plan>}\,\Sigma^{[1,L_P]}\,\texttt{</plan>}$$
$$\texttt{<answer>}\,\Sigma^{[1,L_A]}\,\texttt{</answer>}.$$

The deterministic parser $\Phi : \Sigma^* \to \{\text{Code}, \text{Ans}, \bot\} \times \text{Spans}$ is

$$\Phi(y) = \begin{cases} \big(\text{Code},\ (g_{\text{plan}}, g_{\text{code}})\big) & y \in \mathcal{L}_{\text{code}}, \\ \big(\text{Ans},\ (g_{\text{plan}}, g_{\text{answer}})\big) & y \in \mathcal{L}_{\text{ans}}, \\ (\bot, \varnothing) & \text{otherwise}, \end{cases}$$

where each g_* is the capture substring paired with its span in y.

The protocol is deterministic and free of lookahead, and turn parsing inherits the linear cost of regular expression matching. At every turn the loss mask $m_{i,l}$ of (10) is set to 1 on exactly the tokens that fall inside the g_{code} span when Φ returns Code and inside the g_{answer} span when it returns Ans, and to 0 on all other positions. Tokens outside these two payload spans carry the XML scaffolding and the plan text. These tokens are neither executed in the sandbox nor scored by the reward. Excluding them from the policy gradient concentrates credit on the substrings that directly drive environment transitions and answer correctness, aligning verifiable progress rewards with payload tokens rather than plan text.

B.2 Sandboxed Execution

The shell payload of every Code action is executed in an unprivileged sandbox that combines Linux user namespaces [20] for network isolation with Landlock [49] for filesystem isolation, without requiring Docker or mount tooling. Writes are confined to a working directory W for each task, reads and executes are granted over a fixed system path set $\mathcal{P}_{\mathrm{ro}}$, and outbound connectivity is removed by unsharing the network namespace. A static filter rejects payloads that match recursive deletion or fork bomb patterns, covering adversarial commands that would remain destructive even within the permitted write set. Execution then proceeds in three stages. A launcher spawns the payload under `unshare` with the user and network namespace flags, and redirects its standard input to `/dev/null` to prevent descendants from blocking on interactive input. Inside the spawned child, the process disables privilege escalation via `prctl` with the `NO_NEW_PRIVS` flag, queries the Landlock ABI, installs the ruleset specified in Box 2, changes directory to W, and invokes the payload through `/bin/bash -lc`. A watchdog in the parent process collects the standard streams and terminates the entire new session when the timeout T_{wall} expires.

Box 2. Sandbox specification Ψ.

Let P denote the executed process and all of its descendants. For every payload p accepted by the static filter, the sandbox guarantees

$$\mathrm{writes}(P) \subseteq W, \qquad \mathrm{reads}(P) \subseteq W \cup \mathcal{P}_{\mathrm{ro}}, \qquad \mathrm{net}(P) = \varnothing, \qquad \mathrm{wall}(P) \leq T_{\mathrm{wall}}.$$

These guarantees are realized by installing the Landlock ruleset

$$\mathcal{T}(W, \mathcal{P}_{\mathrm{ro}}) \;=\; \big\{\, (\pi, \mathcal{R}_{\mathrm{ro}}) : \pi \in \mathcal{P}_{\mathrm{ro}} \,\big\} \;\cup\; \big\{\, (W, \mathcal{R}_{\mathrm{rw}}) \,\big\},$$

where each element is a pair of a path and its granted access-right set, and

$$\mathcal{R}_{\mathrm{ro}} = \{\textsc{ReadFile},\ \textsc{ReadDir},\ \textsc{Execute}\},$$
$$\mathcal{R}_{\mathrm{rw}} = \mathcal{R}_{\mathrm{ro}} \cup \{\textsc{WriteFile},\ \textsc{Make}*,\ \textsc{Remove}*\}.$$

The sandbox returns the triple $(\mathrm{stdout}, \mathrm{stderr}, \mathrm{returncode})$ on normal termination, and $\perp$ on timeout after the entire session has been killed.

Filesystem isolation is enforced by Landlock at the kernel level rather than by allowlisting shell commands. The policy observes a usable execution environment while every write side effect is confined to W. Network namespace unsharing removes outbound connectivity from the execution environment. The watchdog in the parent process signals the new session on expiry, bounding per-turn compute and preventing background jobs from surviving past their originating turn.

C Training Algorithm

Algorithm 1 summarizes one optimization step of A^3. Given a batch of multi-turn rollouts collected under the current policy, the procedure computes the episode backbone in (5), the turn-level action sub-chain residual in (6), and the gated tree advantage in (7), fuses them into a single per-turn advantage A_i via (8), and updates π_θ with the clipped sequence-level surrogate in (10).

Algorithm 1 One A^3 optimization step.

Require: π_θ, $\pi_{\theta_{\text{old}}}$, prompts $\mathcal{U}$, group size M, scopes $(\ell_1, \ldots, \ell_G)$, weights $\hat{w}_{1:G}$, w_{intent}, w_{tree}, threshold ξ, decay λ, discount γ, prior α, clips $\epsilon_{\text{lo}}, \epsilon_{\text{hi}}$

for $u \in \mathcal{U}$, $n = 1, \ldots, M$ **do**
  Roll out π_θ for K_n turns in sandbox, obtain R_n
end for
Index all turn instances as $i = (u, n, k)$, $N = \sum_{u,n} K_n$

for each $i = (u, n, k)$ **do**
  $A_i^{\text{ep}} \leftarrow \big(R_n - \text{median}(\mathcal{R}_u)\big) / \big(\text{MAD}(\mathcal{R}_u) + \epsilon\big)$
end for

for each (u, k), each scope index $g = 1, \ldots, G$ **do**
  $\sigma(\cdot) \leftarrow \text{Lin}(\text{AST}(\cdot))$ on the last-ℓ_g action sub-chain, or full episode when $\ell_g{=}{-1}$
  Single-linkage cluster on $d(\cdot, \cdot) \to$ label $\mathbf{b}_i[g]$, LOO mean $\bar{R}^{\text{LOO}}_{u,k,\ell_g}(n)$
end for
for each $i = (u, n, k)$ **do**
  $A_i^{\text{intent}} \leftarrow \sum_{g=1}^{G} \hat{w}_g \left(R_n - \bar{R}^{\text{LOO}}_{u,k,\ell_g}(n)\right)$
end for

Merge turn instances into abstract states S and actions $\mathcal{K}$ via weighted Hamming on $\mathbf{b}$ with decay λ, threshold ξ
for each i, reverse turn order **do**
  $\delta_i \leftarrow V(\mathcal{K}(i)) - V(S(i))$, $A_i^{\text{tree}} \leftarrow \delta_i + \gamma\, A_{i^+}^{\text{tree}}$, $g_i \leftarrow n_i/(n_i + \alpha)$
end for

for each i **do**
  $A_i \leftarrow \phi\big(\widetilde{A}_i^{\text{ep}} + w_{\text{intent}}\, \widetilde{A}_i^{\text{intent}} + w_{\text{tree}}\, \widetilde{g_i A_i^{\text{tree}}}\big)$
  $\rho_i \leftarrow \exp\big(\frac{1}{L_i} \sum_{l=1}^{L_i} (\log \pi_\theta(a_{i,l} \mid h_{i,l}) - \log \pi_{\theta_{\text{old}}}(a_{i,l} \mid h_{i,l}))\big)$
end for
$\mathcal{L} \leftarrow -\frac{1}{N} \sum_i \min\big(\rho_i A_i,\ \text{clip}(\rho_i, 1{-}\epsilon_{\text{lo}}, 1{+}\epsilon_{\text{hi}}) A_i\big)$
$\theta \leftarrow \theta - \eta\, \nabla_\theta \mathcal{L}$

D Training Dynamics across Agentic RL Methods

Figure 3 supports the following failure mode reading under matched data, optimizer, rollout horizon, and group size.

Surrogates based on observation clustering accumulate a delayed KL shock. HGPO and GiGPO group rollouts by an equivalence relation over observations and apply a single advantage shift to every member of a cluster. In the early phase the policy update stays inside the trust region and the surrogate KL panel remains nearly flat, while one state of the language model can still collect many distinct token sequences. As the policy concentrates probability mass on the trajectories that dominate each cluster, the mean advantage shift of the cluster becomes increasingly correlated with the importance ratio at the token level, and the surrogate update moves away from the on-policy objective. The visible signature is a late spike in surrogate KL, together with a divergent gradient norm and the early stopping marker in Figure 3.

RetroAgent settles into a low entropy regime. RetroAgent pairs GRPO-style group relative advantage with a learned memory channel that is read by the policy and updated by the rollout buffer at every turn. The coupling amplifies the advantage signal of trajectories that use the memory channel, producing a volatile surrogate KL from the first updates and a wider envelope later in training. The same coupling drives policy entropy downward before the optimization budget is consumed, indicating a narrower action distribution and limited marginal value from additional gradient updates.

Token-level surrogates plateau under coarse credit assignment. GSPO maintains a well-conditioned surrogate KL envelope and stable policy entropy throughout training, making it the most stable baseline at the optimization level. Its training success and reward trajectories saturate

after roughly 120 updates and remain on a plateau for the rest of the budget. The sequence-level importance ratio is normalized for single-turn language modelling, but does not separate subgoal completion within a trajectory from terminal reward. Once the easy mass of the dataset has been fitted, the policy receives little additional shaping signal from interior recovery steps.

A^3 **retains a stable surrogate trajectory while continuing to gain.** Across the same horizon, A^3 keeps the surrogate KL inside an envelope comparable to GSPO and avoids the late training shock observed for HGPO, GiGPO, and RetroAgent. Its policy entropy decays more gradually than the memory based baseline and remains above the saturation level reached by GSPO, while the success and reward panels continue to grow throughout the second half of training. This pattern is consistent with the multi-granularity credit assignment of Section 3, where the episode backbone supplies terminal signal, the turn-level action sub-chain residual adds local shaping, and the tree advantage redistributes credit within sibling rollouts.

E Computational Cost of action space AST Similarity

We measure the wall clock cost of the three AST similarity computations that A^3 performs on the M sibling rollouts of every prompt. The turn-level pass evaluates, at every cell (u, k, ℓ) and each scope ℓ in the positive entries of $(\ell_1, \ldots, \ell_G)$, a distance matrix over the signatures $\sigma(\cdot)$ whose inputs are the last ℓ shell commands ending at turn k. The episode-level pass evaluates the same distance matrix at the remaining whole episode scope, with signatures computed from the concatenation of all shell commands in a rollout. The tree-level pass evaluates pairwise distances between trajectory histories that share a prompt u and a past-turn key set. Table 7 reports the number of σ-pair evaluations entering each pass and the corresponding wall-clock, averaged over a forward rollout batch at group size $M = 4$ under uniform weights $\hat{w}_{1:G}$.

Table 7: Wall clock cost of the three AST similarity passes underlying A^3, averaged over a forward rollout batch at group size $M = 4$. $|\mathcal{P}|$ counts σ-pair evaluations entering each pass. The turn-level and episode-level passes together feed the turn-level action sub-chain residual A^{intent} of (6). The tree-level pass feeds the tree advantage A^{tree} of (7).

	Turn-level		Episode-level		Tree-level		Total
Intent scopes $(\ell_1, \ldots, \ell_G)$	$\lvert\mathcal{P}\rvert$	ms	$\lvert\mathcal{P}\rvert$	ms	$\lvert\mathcal{P}\rvert$	ms	ms
$(1, 2, 3, 4, 5, -1)$	127.2	11.22	25.4	9.13	71.8	4.83	25.17
$(1, 2, 3, 4, -1)$	101.8	7.97	25.4	8.69	71.8	4.76	21.42
$(1, 2, 3, -1)$	76.3	5.27	25.4	8.65	71.8	4.80	18.73
$(1, 2, -1)$	50.9	2.96	25.4	8.67	71.8	4.81	16.45
$(1, -1)$	25.4	1.18	25.4	8.58	71.8	4.80	14.56

Across the sweep the three passes together stay below 26 ms. The turn-level cost grows linearly with its $|\mathcal{P}|$, while the episode-level and tree-level costs are invariant to the scope sweep. Relative to rollout, which is dominated by LLM forward passes measured in seconds per turn, the action space AST similarity is smaller by more than an order of magnitude.

F Secondary Main Results

Table 8 extends the exact match comparison in Table 1 with secondary metrics for the same benchmark streams. File-change recall measures file-editing quality by comparing generated file changes against the ground-truth file changes at line level. Combined averages LLM Judge accuracy and file-change recall for hybrid tasks that require both terminal-output correctness and file-state correctness. Under both the vanilla and σ-Reveal settings, A^3 attains state-of-the-art performance among the compared Qwen3-14B agentic methods, with the strongest gains on the file and hybrid ShellOps evaluations.

Table 8: Secondary evaluation scores (%) grouped by task type. The table reports LLM Judge accuracy for STRING tasks, line-level file-change recall for FILES tasks, and their combination for HYBRID tasks.

	LLM Judge						Diff Recall		Combined
Method	AB-OS	AB-DB	DataBench	EHRCon	ShellOps	TableBench	AB-DB	ShellOps	ShellOps
ReACT	57.9	16.0	63.7	61.5	28.3	19.3	39.9	44.1	46.0
LATS	40.0	9.9	54.5	41.5	28.8	21.0	40.6	47.9	35.9
rStar	35.9	5.6	46.4	36.7	18.6	16.0	44.2	35.1	20.7
GSPO	**61.4**	14.7	70.1	45.6	27.7	25.4	45.0	49.8	46.1
GiGPO	54.5	10.7	57.1	59.3	27.0	24.4	40.4	43.2	40.0
HGPO	46.9	14.7	44.9	54.1	23.9	19.6	40.2	41.8	37.4
RetroAgent	49.0	16.3	69.0	57.2	20.0	25.2	44.1	49.7	41.4
A^3 (Vanilla)	58.6	27.8	74.6	66.7	49.0	**32.0**	**48.8**	53.5	47.2
A^3 (σ-Reveal)	60.7	**28.7**	**77.9**	**67.4**	**49.1**	**32.0**	48.2	**58.3**	**52.0**

G ShellOps-Pro σ-Reveal Baseline Sweep

All agentic inference comparisons in the main tables and Table 9 use open models deployed locally with SGLang [76], without API calls. The same SGLang deployment and decoding configuration are used for the agentic RL baselines, so that vanilla and σ-Reveal differ only in the harness context.

Table 9 reports the σ-Reveal harness accuracy of every baseline at each horizon, paired with the absolute lift over its own vanilla measurement. A^3 follows the main-table setting in Table 3 and is not repeated here.

Table 9: ShellOps-Pro σ-Reveal accuracy in percent for every baseline across $H_{\max} \in \{6, 7, 8, 9, 10\}$. Each cell reports $\mathrm{EM}_{\sigma\text{-Reveal}}$ $(+\Delta)$, where $\Delta = \mathrm{EM}_{\sigma\text{-Reveal}} - \mathrm{EM}_{\mathrm{Vanilla}}$ is computed against the same method and horizon under the vanilla harness. Accuracy is the macro-average exact match over the three ShellOps-Pro task types.

Method	$H_{\max}$=6	$H_{\max}$=7	$H_{\max}$=8	$H_{\max}$=9	$H_{\max}$=10
Agentic Inference					
Kimi-K2.6	50.9 (+5.1)	48.9 (+2.3)	52.8 (+4.9)	54.1 (+3.2)	53.1 (−0.3)
GLM-5.1	41.3 (+6.7)	39.6 (+3.1)	42.0 (+2.9)	43.3 (+1.6)	41.9 (+1.2)
Qwen3-235B-A22B	30.8 (+4.1)	33.6 (+6.9)	31.2 (+1.9)	35.5 (+4.9)	33.2 (+4.9)
Qwen3-14B (ReACT)	28.1 (+8.8)	27.5 (+8.1)	28.1 (+5.9)	28.3 (+7.7)	27.6 (+5.6)
Qwen3-14B (LATS)	29.1 (+8.0)	30.0 (+7.1)	29.9 (+8.1)	29.3 (+6.1)	31.7 (+12.0)
Qwen3-14B (rStar)	28.1 (+8.8)	26.8 (+4.7)	27.1 (+6.0)	26.1 (+3.9)	28.9 (+8.5)
Agentic RL					
Qwen3-14B (GSPO)	32.1 (+7.7)	30.9 (+5.9)	31.5 (+6.5)	31.6 (+5.1)	31.9 (+6.4)
Qwen3-14B (GiGPO)	34.0 (+6.9)	34.9 (+10.1)	33.9 (+7.6)	35.6 (+8.8)	33.9 (+8.1)
Qwen3-14B (HGPO)	28.3 (+8.8)	28.0 (+6.9)	28.5 (+6.7)	29.9 (+6.9)	30.3 (+7.5)
Qwen3-14B (RetroAgent)	24.4 (+6.4)	25.7 (+7.1)	24.5 (+5.3)	25.5 (+8.4)	25.9 (+5.9)

H Qualitative Case Study

This section illustrates execution differences between A^3 and baseline methods on the same tasks.

H.1 ShellOps-Pro `ShellOps_1e26c37bd6`: Application Log Split

This ShellOps-Pro instance requires splitting an application log whose path is absent from the first observation. The comparison focuses on evidence gathering under a missing source path. A^3 lists the workspace and locates `server/logs/current/application.log`, while LATS creates a synthetic `log.txt`. The initial environment block summarizes the benchmark `pre_files`, not the agent's initial observation. All omitted regions are shortened only for presentation length.

Task

```
[SAMPLE ID]
ShellOps_1e26c37bd6

[USER QUERY]
Our application log file keeps lines of the form '<YYYY-MM-DD> <
    message>'. Split it into one file per distinct date at 'archive/by
    -date/<date>.log', preserving the original ordering within each
    date. Create the directory if it does not exist, put nothing else
    into it, and leave the source log unmodified.

[REFERENCE COMMAND]
mkdir -p archive/by-date && awk '{d=$1; print > ("archive/by-date/" d
    ".log")}' server/logs/current/application.log
```

Initial environment

```
Total pre-files: 46
This block summarizes the complete initial file environment from
    pre_files.
It is not the initial observation given to the agent.

[PATH SUMMARY]
server/logs/archive/eu-central-1/api-01.notes.md
server/logs/archive/eu-central-1/web-02.notes.md
server/logs/archive/eu-central-1/web-03.notes.md
server/logs/archive/eu-central-1/web-07.notes.md
server/logs/archive/eu-west-1/api-02.notes.md
server/logs/archive/eu-west-1/edge-01.notes.md
server/logs/archive/eu-west-1/edge-07.notes.md
server/logs/archive/eu-west-1/web-04.notes.md
server/logs/archive/us-east-1/api-05.notes.md
server/logs/archive/us-east-1/edge-06.notes.md
... (36 additional files omitted for presentation length) ...

[SELECTED FILE CONTENTS]
===== server/logs/current/application.log =====
2024-01-05 event 00000 detail=login
2024-01-12 event 00001 detail=login
2024-01-19 event 00002 detail=ok
2024-01-26 event 00003 detail=logout
2024-02-05 event 00004 detail=login
... (410 lines omitted for presentation length) ...
2024-02-26 event 00415 detail=error
2024-03-05 event 00416 detail=ok
2024-03-12 event 00417 detail=login
2024-03-19 event 00418 detail=ok
2024-03-26 event 00419 detail=logout
```

A3 rollout, Vanilla H6 (EM=1.0, line-level diff recall=1.0).

A3 rollout, Vanilla H6

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_2wgpfk9c
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to examine the content of
    the log file to understand its structure and verify that it
    contains lines in the format <YYYY-MM-DD> <message>. This</plan><
    code>cat log.txt</code>

[STATE AFTER ACTION]
cat: log.txt: No such file or directory


[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
cat: log.txt: No such file or directory


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The log file 'log.txt' does not exist in
     the current working directory. I need to determine the correct
    path to the log file to proceed with the task.</plan><code>ls -R</
    code>

[STATE AFTER ACTION]
.:
home
server
workspace_meta

./home:

... (92 lines omitted for presentation length) ...

./workspace_meta/scripts/utils:
common.sh


[FILE_CHANGES]
(no file changes detected)

===== TURN 2 =====
[STATE BEFORE ACTION]
```

```
.:
home
server
workspace_meta

... (96 lines omitted for presentation length) ...
common.sh


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The log file 'log.txt' is not present in
     the current directory, but there is an 'application.log' file in
    the './server/logs/current' directory. I need to examine the
    content of 'application.log' to ensure it</plan><code>cat server/
    logs/current/application.log</code>

[STATE AFTER ACTION]
[TRUNCATED stdout_stderr: raw=14906, showing_last=2000]
etail=logout
2024-02-05 event 00364 detail=error
2024-02-12 event 00365 detail=ok
2024-02-19 event 00366 detail=login
2024-02-26 event 00367 detail=error
2024-03-05 event 00368 detail=logout
... (48 lines omitted for presentation length) ...
2024-03-12 event 00417 detail=login
2024-03-19 event 00418 detail=ok
2024-03-26 event 00419 detail=logout


[FILE_CHANGES]
(no file changes detected)

===== TURN 3 =====
[STATE BEFORE ACTION]
[TRUNCATED stdout_stderr: raw=14906, showing_last=2000]
etail=logout
2024-02-05 event 00364 detail=error
2024-02-12 event 00365 detail=ok
2024-02-19 event 00366 detail=login
... (52 lines omitted for presentation length) ...
2024-03-26 event 00419 detail=logout


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I now know that the log file '
    application.log' contains lines in the format '<YYYY-MM-DD> <
    message>'. The next step is to split this file into one file per
    distinct date at 'archive/by-date/<date>.log'. I will first create
     the directory 'archive/by-date' </plan><code>mkdir -p archive/by-
    date</code>
```

```
[STATE AFTER ACTION]
[FILE_CHANGES]
(no file changes detected)

===== TURN 4 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I need to split the 'application.log'
    file into separate files for each distinct date. I will use 'awk'
    to process the log file and redirect the lines for each date to
    the respective file in the 'archive/by-date' directory.</plan><
    code>awk -F' ' '{date=$1; file="archive/by-date/" date ".log";
    print >> file}' server/logs/current/application.log</code>

[STATE AFTER ACTION]
[FILE_CHANGES]
[TRUNCATED file_diff: raw=2313, showing_first=1500]
Created files:
- archive/by-date/2024-01-05.log
- archive/by-date/2024-01-12.log
- archive/by-date/2024-01-19.log
- archive/by-date/2024-01-26.log
... (34 lines omitted for presentation length) ...
2024-01-12 event 00025 detail=error
2024-01-12 event 00037 detail=error
2024-01-12 event 00049 detail=error
2024-01-12 event 00061 detail=logout
2024-01-12 event 00073 detail=login
2024-01-12 event 00085 detail=login
2024-01

===== TURN 5 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
[TRUNCATED file_diff: raw=2313, showing_first=1500]
Created files:
- archive/by-date/2024-01-05.log
- archive/by-date/2024-01-12.log
... (38 lines omitted for presentation length) ...
2024-01-12 event 00049 detail=error
2024-01-12 event 00061 detail=logout
2024-01-12 event 00073 detail=login
2024-01-12 event 00085 detail=login
2024-01

[ACTION]
<name>submit_answer</name><plan>The task of splitting the log file
    into individual files per distinct date has been successfully
    completed. The files have been created in the 'archive/by-date'
    directory with the correct content for each date. The source</plan
    ><answer>Archive completed successfully.</answer>

[STATE AFTER ACTION]
```

```
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "shellops_pro", "
    delta_coverage": 1.0, "evaluated": true, "file_sha_match": true, "
    final_step_idx": 5, "is_final_step": true, "llm_judge_used": false
    , "missing_gt": false, "type": "files"}
```

Failed baseline rollout, LATS (EM=0.0, line-level diff recall=0.0).

Failed baseline rollout, LATS

```
This box reports the committed LATS rollout. The raw log keeps two-arm
     search statistics at each node, but not the full text of both
    branch candidates.
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_qwjnpgq0
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to check if the source log
     file exists and inspect its contents to understand the format and
     data. This will help ensure the splitting process is correctly
    implemented.</plan><code>ls -l && cat log.txt</code>

[LATS SEARCH]
n_generate_sample=2, iterations=16, arm_rewards=[0.0, 0.0],
    arm_visits_final=[8, 8], chosen_arm_visits=8

[STATE AFTER ACTION]
total 4
drwxr-xr-x 2 root root 10 Apr 20 13:50 home
drwxr-xr-x 4 root root 46 Apr 18 12:54 server
drwxr-xr-x 7 root root 4096 Apr 18 12:54 workspace_meta
cat: log.txt: No such file or directory


[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
total 4
drwxr-xr-x 2 root root 10 Apr 20 13:50 home
drwxr-xr-x 4 root root 46 Apr 18 12:54 server
drwxr-xr-x 7 root root 4096 Apr 18 12:54 workspace_meta
cat: log.txt: No such file or directory


[FILE_CHANGES]
```

```
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The source log file 'log.txt' does not
    exist in the current working directory. I will create a sample log
     file with the required format to proceed with testing the
    splitting logic.</plan><code>echo "[2023-04-18] This is a sample
    log message." > log.txt && echo "[2023-04-19] Another sample log
    message." >> log.txt</code>

[LATS SEARCH]
n_generate_sample=2, iterations=16, arm_rewards=[0.0, 0.0],
    arm_visits_final=[8, 8], chosen_arm_visits=8

[STATE AFTER ACTION]
[FILE_CHANGES]
Created files:
- log.txt

Preview of log.txt:
[2023-04-18] This is a sample log message.
[2023-04-19] Another sample log message.

===== TURN 2 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
Created files:
- log.txt

Preview of log.txt:
[2023-04-18] This is a sample log message.
[2023-04-19] Another sample log message.

[ACTION]
<name>submit_code</name><plan>I need to process the log file and split
     it into one file per distinct date in the 'archive/by-date/'
    directory. I will create the directory if it does not exist and
    then use 'awk' to split the log entries by date, preserving the
    original order within each</plan><code>mkdir -p archive/by-date &&
     awk -F'[][]' '{date=$2; filename="archive/by-date/" date ".log";
    print $3 >> filename}' log.txt</code>

[LATS SEARCH]
n_generate_sample=2, iterations=16, arm_rewards=[0.0, 0.0],
    arm_visits_final=[8, 8], chosen_arm_visits=8

[STATE AFTER ACTION]
[FILE_CHANGES]
Created files:
- archive/by-date/2023-04-18.log
- archive/by-date/2023-04-19.log

Preview of archive/by-date/2023-04-18.log:
 This is a sample log message.

Preview of archive/by-date/2023-04-19.log:
 Another sample log message.
```

```
===== TURN 3 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
Created files:
- archive/by-date/2023-04-18.log
- archive/by-date/2023-04-19.log

Preview of archive/by-date/2023-04-18.log:
 This is a sample log message.

Preview of archive/by-date/2023-04-19.log:
 Another sample log message.

[ACTION]
<name>submit_answer</name><plan>The log file has been successfully
    split into individual files per date in the 'archive/by-date/'
    directory, preserving the original ordering within each date. The
    task is complete.</plan><answer>Successfully split log.txt into
    one file per distinct date in archive/by-date/ directory.</answer>

[LATS SEARCH]
n_generate_sample=2, iterations=16, arm_rewards=[0.0, 0.0],
    arm_visits_final=[8, 8], chosen_arm_visits=8

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 0.0, "answered": true, "dataset": "shellops_pro", "
    delta_coverage": 0.0, "evaluated": true, "file_sha_match": false,
    "final_step_idx": 3, "is_final_step": true, "llm_judge_used":
    false, "missing_gt": false, "type": "files"}
```

H.2 ShellOps-Pro `ShellOps_b434dfe752`: Leaderboard Aggregation

This ShellOps-Pro instance combines file generation with a scalar answer. The comparison focuses on control of written files after reading many leaderboard files. A^3 creates `reports/top10.tsv` and returns the top total, while GiGPO first writes an intermediate file under `games/` and ends with a file mismatch.

Task

```
[SAMPLE ID]
ShellOps_b434dfe752

[USER QUERY]
Across every per-day leaderboard under 'games/leaderboard/', aggregate
     each player's total score (same player across different days must
     be summed). Write the 10 highest-scoring players to 'reports/
    top10.tsv' as '<player><TAB><total>' lines, no header, sorted by
    '<total>' descending (ties broken by '<player>' in C-locale
    ascending order), ending with a single trailing newline. Also
    print on stdout the top player's total as a single integer. Leave
    the leaderboard files unchanged.
```

```
[REFERENCE COMMAND]
mkdir -p reports && find games/leaderboard -type f -name '*.csv' -exec
     awk -F, 'FNR>1{s[$1]+=$2} END{for(p in s) printf "%s\t%s\n", p, s
    [p]}' {} + | LC_ALL=C sort -t$'\t' -k2,2nr -k1,1 | head -n10 >
    reports/top10.tsv; awk -F'\t' 'NR==1{print $2}' reports/top10.tsv
```

Initial environment

```
Total pre-files: 51
This block summarizes the complete initial file environment from
    pre_files.
It is not the initial observation given to the agent.

[PATH SUMMARY]
games/leaderboard/neonrun/2024-04-01.csv
games/leaderboard/neonrun/2024-04-02.csv
games/leaderboard/neonrun/2024-04-03.csv
games/leaderboard/neonrun/2024-04-04.csv
games/leaderboard/neonrun/2024-04-05.csv
games/leaderboard/neonrun/2024-04-06.csv
games/leaderboard/neonrun/2024-04-07.csv
games/leaderboard/orbitrace/2024-04-01.csv
games/leaderboard/orbitrace/2024-04-02.csv
games/leaderboard/orbitrace/2024-04-03.csv
... (41 additional files omitted for presentation length) ...

[SELECTED FILE CONTENTS]
===== games/leaderboard/neonrun/2024-04-01.csv =====
player,score
selene,4263
raven,7191
draco,2582
selene,9099
... (9 lines omitted for presentation length) ...
pyro,7605
nomad,4302
arbiter,490
nova,9423
kite,1732

===== games/leaderboard/orbitrace/2024-04-01.csv =====
player,score
hypatia,9852
nomad,3646
nyx,9271
pyro,7814
... (3 lines omitted for presentation length) ...
pyro,8514
valkyrie,1396
rex,9234
rex,3479
nyx,5398

===== games/leaderboard/starforge/2024-04-01.csv =====
player,score
brio,8778
```

```
morpheus,5659
valkyrie,8514
centurion,5186
... (4 lines omitted for presentation length) ...
rex,8827
cyrus,7402
nyx,8369
nyx,4918
centurion,1848
```

A3 rollout, σ-Reveal H10 (hybrid EM=1.0, string exact=1.0, file exact=1.0, target diff recall=1.0).

A3 rollout, sigma-Reveal H10

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_59qef33g
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to examine the content of
    the leaderboard files to understand their structure and aggregate
    players across all files. I will start by inspecting a sample file
     from the</plan><code>cat games/leaderboard/neonrun/2024-04-01.csv
    </code>

[STATE AFTER ACTION]
player,score
selene,4263
raven,7191
draco,2582
selene,9099
nomad,8782
luna,3767
... (9 lines omitted for presentation length) ...
arbiter,490
nova,9423
kite,1732


[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
player,score
selene,4263
raven,7191
draco,2582
selene,9099
... (13 lines omitted for presentation length) ...
```

```
kite,1732


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I now understand the structure of the
    leaderboard files, which contain player-score pairs. The next step
     is to aggregate each player's total score across all files. I
    will use command-line tools to process</plan><code>cat games/
    leaderboard/neonrun/*.csv games/leaderboard/orbitrace/*.csv games/
    leaderboard/starforge/*.csv games/leaderboard/voidcraft/*.csv |
    awk -F',' '{player[$1] += $2} END {for (p in player)</code>

[STATE AFTER ACTION]
bash: -c: line 1: unexpected EOF while looking for matching '''
bash: -c: line 2: syntax error: unexpected end of file


[FILE_CHANGES]
(no file changes detected)

===== TURN 2 =====
[STATE BEFORE ACTION]
bash: -c: line 1: unexpected EOF while looking for matching '''
bash: -c: line 2: syntax error: unexpected end of file


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The previous command was incomplete and
    had a syntax error. I need to properly format the command to
    process all CSV files, aggregate the scores for each player, and
    then sort and output the results. I will</plan><code>cat games/
    leaderboard/*/*.csv | awk -F',' '{player[$1] += $2} END {for (p in
     player) print p "\t" player[p]}' | sort -t$'\t' -k2nr,2n -k1,1 |
    head > reports/top10.tsv && tail -n1 reports/top10</code>

[STATE AFTER ACTION]
bash: line 1: reports/top10.tsv: No such file or directory
sort: fflush failed: 'standard output': Broken pipe
sort: write error


[FILE_CHANGES]
(no file changes detected)

===== TURN 3 =====
[STATE BEFORE ACTION]
bash: line 1: reports/top10.tsv: No such file or directory
sort: fflush failed: 'standard output': Broken pipe
sort: write error
```

```
[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The previous command resulted in errors
    due to incorrect handling of the command string and the absence of
     the 'reports' directory. I will first create the 'reports'
    directory, fix the command to properly aggregate and sort the
    scores, and then write the</plan><code>mkdir -p reports && cat
    games/leaderboard/*/*.csv | awk -F',' '{player[$1] += $2} END {for
     (p in player) print p "\t" player[p]}' | sort -t$'\t' -k2nr,2n -
    k1,1 | head > reports/top10.tsv &&cat</code>

[STATE AFTER ACTION]
[FILE_CHANGES]
Created files:
- reports/top10.tsv

Preview of reports/top10.tsv:
selene 144104
nyx 139688
... (1 lines omitted for presentation length) ...
hypatia 134526
kite 128935
nomad 124341
valkyrie 120839
brio 118327
rex 116094
pyro 114409

===== TURN 4 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
Created files:
- reports/top10.tsv

Preview of reports/top10.tsv:
... (5 lines omitted for presentation length) ...
nomad 124341
valkyrie 120839
brio 118327
rex 116094
pyro 114409

[ACTION]
<name>submit_answer</name><plan>The command successfully aggregated
    and sorted the player scores, and the top 10 players are written
    to 'reports/top10.tsv'. The top player's total score is 144104.</
    plan><answer>144104</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "shellops_pro", "
    delta_coverage": 1.0, "evaluated": true, "file_sha_match": true, "
    final_step_idx": 4, "is_final_step": true, "llm_judge_used": false
```

```
    , "match": "exact", "missing_gt": false, "string_exact_score":
    1.0, "type": "hybrid"}
```

Failed baseline rollout, GiGPO (hybrid EM=0.0, string exact=1.0, file exact=0.0, target diff recall=1.0).

Failed baseline rollout, GiGPO

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_i_bckb1z
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>I need to aggregate the scores of each
    player across all the leaderboard files and write the top 10
    players to a TSV file. I'll start by using a shell command to
    process the CSV files and sum the scores for each player.</plan><
    code>cd games/leaderboard && find . -name "*.csv" -exec awk -F','
    '{sum[$1] += $2} END {for (player in sum) print player "\t" sum[
    player]}' {} + | sort -t$'\t' -k2,2nr -k1,1 | head -n 10 > ../
    top10</code>

[STATE AFTER ACTION]
[FILE_CHANGES]
Created files:
- games/top10

Preview of games/top10:
selene 144104
nyx 139688
... (1 lines omitted for presentation length) ...
hypatia 134526
kite 128935
nomad 124341
valkyrie 120839
brio 118327
rex 116094
pyro 114409

===== TURN 1 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
Created files:
- games/top10

Preview of games/top10:
... (5 lines omitted for presentation length) ...
nomad 124341
valkyrie 120839
brio 118327
```

```
rex 116094
pyro 114409

[ACTION]
<name>submit_code</name><plan>I need to verify the top player's total
    score and ensure the TSV file is correctly formatted. I'll check
    the first line of the generated top10 file to get the highest
    score and confirm the format.</plan><code>head -n 1 games/top10 |
    cut -f2 && cat games/top10 > reports/top10.tsv</code>

[STATE AFTER ACTION]
144104
bash: line 1: reports/top10.tsv: No such file or directory


[FILE_CHANGES]
(no file changes detected)

===== TURN 2 =====
[STATE BEFORE ACTION]
144104
bash: line 1: reports/top10.tsv: No such file or directory


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The top player's total score is 144104.
    I need to ensure the reports/top10.tsv file is created correctly
    and then output the top player's total score.</plan><code>mkdir -p
     reports && cat games/top10 > reports/top10.tsv && echo 144104</
    code>

[STATE AFTER ACTION]
144104


[FILE_CHANGES]
Created files:
- reports/top10.tsv

... (4 lines omitted for presentation length) ...
hypatia 134526
kite 128935
nomad 124341
valkyrie 120839
brio 118327
rex 116094
pyro 114409

===== TURN 3 =====
[STATE BEFORE ACTION]
144104


[FILE_CHANGES]
```

```
Created files:
... (8 lines omitted for presentation length) ...
nomad 124341
valkyrie 120839
brio 118327
rex 116094
pyro 114409

[ACTION]
<name>submit_answer</name><plan>The top 10 players have been written
    to 'reports/top10.tsv' and the top player's total score is
    confirmed as 144104. The task is complete.</plan><answer>144104</
    answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 0.0, "answered": true, "dataset": "shellops_pro", "
    delta_coverage": 1.0, "evaluated": true, "file_sha_match": false,
    "final_step_idx": 3, "is_final_step": true, "llm_judge_used":
    false, "match": "exact", "missing_gt": false, "string_exact_score
    ": 1.0, "type": "hybrid"}
```

H.3 DataBench `071_COL_7`: Cost-of-Living Comparison

This DataBench string instance asks whether Switzerland remains the most expensive country when rent is considered together with living cost. The comparison focuses on interpreting the queried aggregate column rather than a single component. A^3 grounds the answer in the top-ranked cost-of-living-plus-rent row, while GLM-5.1 rejects the answer after isolating the rent index.

Task

```
[DATASET]
DataBench

[SAMPLE ID]
071_COL_7

[USER QUERY]
In the current directory, there is a CSV file named '0b3bb73d.csv'. Is
     Switzerland considered to be the most expensive country
    regardless if I rent or own my home?.

[REFERENCE ANSWER]
Yes
```

Initial observation

```
[INITIAL OBSERVATION]
Working directory: /tmp/bash_coding_0ygbep91
You can execute bash commands to explore the file system and complete
    this task.
```

```
[AVAILABLE FILE]
0b3bb73d.csv

The CSV content is observed only after the agent issues shell commands
    .
```

A3 rollout, Vanilla H6 (string EM=1.0).

A3 rollout, Vanilla H6

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_0ygbep91
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>To determine if Switzerland is the most
    expensive country regardless of renting or owning a home, I need
    to examine the data in the CSV file '0b3bb73d.csv' to analyze the
    </plan><code>head 0b3bb73d.csv</code>

[STATE AFTER ACTION]
Rank,Country,Cost of Living Index,Rent Index,Cost of Living Plus Rent
    Index,Groceries Index,Restaurant Price Index,Local Purchasing
    Power Index
1,Switzerland,101.1,46.5,74.9,109.1,97.0,158.7
2,Bahamas,85.0,36.7,61.8,81.6,83.3,54.6
3,Iceland,83.0,39.2,62.0,88.4,86.8,120.3
4,Singapore,76.7,67.2,72.1,74.6,50.4,111.1
5,Barbados,76.6,19.0,48.9,80.8,69.4,43.5
6,Norway,76.0,26.2,52.1,79.0,73.5,114.7
7,Denmark,72.3,26.4,50.2,64.8,81.3,127.2
8,Hong Kong (China),70.8,59.4,65.3,84.6,46.2,109.3
9,United States,70.4,41.7,56.6,75.0,67.2,142.3

[FILE_CHANGES]

===== TURN 1 =====
[STATE BEFORE ACTION]
Rank,Country,Cost of Living Index,Rent Index,Cost of Living Plus Rent
    Index,Groceries Index,Restaurant Price Index,Local Purchasing
    Power Index
1,Switzerland,101.1,46.5,74.9,109.1,97.0,158.7
2,Bahamas,85.0,36.7,61.8,81.6,83.3,54.6
3,Iceland,83.0,39.2,62.0,88.4,86.8,120.3
4,Singapore,76.7,67.2,72.1,74.6,50.4,111.1
5,Barbados,76.6,19.0,48.9,80.8,69.4,43.5
6,Norway,76.0,26.2,52.1,79.0,73.5,114.7
7,Denmark,72.3,26.4,50.2,64.8,81.3,127.2
8,Hong Kong (China),70.8,59.4,65.3,84.6,46.2,109.3
9,United States,70.4,41.7,56.6,75.0,67.2,142.3
```

```
[ACTION]
<name>submit_code</name><plan>I need to determine if Switzerland is
    the most expensive country regardless of renting or owning a home.
     The data shows that Switzerland has the highest "Cost of Living
    Index" and a high "Rent Index," suggesting it might be the most
    expensive countr</plan><code>tail 0b3bb73d.csv</code>

[STATE AFTER ACTION]
11,Austria,65.1,22.5,44.7,66.4,59.3,102.4
12,Canada,64.8,33.2,49.6,71.2,61.7,103.7
13,New Zealand,64.6,25.9,46.0,71.9,57.1,121.0
14,Ireland,64.4,42.3,53.8,59.3,65.3,101.1
15,France,63.7,21.0,43.2,69.5,56.3,102.4
16,Puerto Rico,63.3,19.5,42.3,64.1,53.1,103.5
17,Finland,63.2,19.7,42.4,63.0,63.6,118.0
18,Netherlands,63.1,33.5,48.9,59.9,61.2,124.9
19,Israel,62.7,27.1,45.6,59.6,68.0,99.4
20,Luxembourg,62.4,40.5,51.9,64.1,68.7,182.5

[FILE_CHANGES]

===== TURN 2 =====
[STATE BEFORE ACTION]
11,Austria,65.1,22.5,44.7,66.4,59.3,102.4
12,Canada,64.8,33.2,49.6,71.2,61.7,103.7
13,New Zealand,64.6,25.9,46.0,71.9,57.1,121.0
14,Ireland,64.4,42.3,53.8,59.3,65.3,101.1
15,France,63.7,21.0,43.2,69.5,56.3,102.4
16,Puerto Rico,63.3,19.5,42.3,64.1,53.1,103.5
17,Finland,63.2,19.7,42.4,63.0,63.6,118.0
18,Netherlands,63.1,33.5,48.9,59.9,61.2,124.9
19,Israel,62.7,27.1,45.6,59.6,68.0,99.4
20,Luxembourg,62.4,40.5,51.9,64.1,68.7,182.5

[ACTION]
<name>submit_answer</name><plan>The CSV data shows that Switzerland
    has the highest "Cost of Living Index" and a high "Rent Index,"
    indicating it is the most expensive country regardless of home
    ownership. The data confirms this</plan><answer>Yes</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "databench", "evaluated":
    true, "final_step_idx": 2, "is_final_step": true, "llm_judge_used
    ": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 1.0, "string_llm_incorporated_score": 1.0, "
    type": "string"}
```

Failed baseline rollout, GLM-5.1 (string EM=0.0).

Failed baseline rollout, GLM-5.1

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_6u0ej1i5
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>I need to examine the CSV file to
    understand its structure and content. Then I can determine if
    Switzerland is the most expensive country regardless of renting or
     owning. I'll start by looking at the first few rows of the file
    and its structure.</plan><code>head -20 0b3bb73d.csv</code>

[STATE AFTER ACTION]
Rank,Country,Cost of Living Index,Rent Index,Cost of Living Plus Rent
    Index,Groceries Index,Restaurant Price Index,Local Purchasing
    Power Index
1,Switzerland,101.1,46.5,74.9,109.1,97.0,158.7
2,Bahamas,85.0,36.7,61.8,81.6,83.3,54.6
3,Iceland,83.0,39.2,62.0,88.4,86.8,120.3
4,Singapore,76.7,67.2,72.1,74.6,50.4,111.1
5,Barbados,76.6,19.0,48.9,80.8,69.4,43.5
6,Norway,76.0,26.2,52.1,79.0,73.5,114.7
7,Denmark,72.3,26.4,50.2,64.8,81.3,127.2
8,Hong Kong (China),70.8,59.4,65.3,84.6,46.2,109.3
9,United States,70.4,41.7,56.6,75.0,67.2,142.3
10,Australia,70.2,33.4,52.5,77.3,62.5,127.4
11,Austria,65.1,22.5,44.7,66.4,59.3,102.4
12,Canada,64.8,33.2,49.6,71.2,61.7,103.7
13,New Zealand,64.6,25.9,46.0,71.9,57.1,121.0
14,Ireland,64.4,42.3,53.8,59.3,65.3,101.1
15,France,63.7,21.0,43.2,69.5,56.3,102.4
16,Puerto Rico,63.3,19.5,42.3,64.1,53.1,103.5
17,Finland,63.2,19.7,42.4,63.0,63.6,118.0
18,Netherlands,63.1,33.5,48.9,59.9,61.2,124.9
19,Israel,62.7,27.1,45.6,59.6,68.0,99.4

[FILE_CHANGES]

===== TURN 1 =====
[STATE BEFORE ACTION]
Rank,Country,Cost of Living Index,Rent Index,Cost of Living Plus Rent
    Index,Groceries Index,Restaurant Price Index,Local Purchasing
    Power Index
1,Switzerland,101.1,46.5,74.9,109.1,97.0,158.7
2,Bahamas,85.0,36.7,61.8,81.6,83.3,54.6
3,Iceland,83.0,39.2,62.0,88.4,86.8,120.3
4,Singapore,76.7,67.2,72.1,74.6,50.4,111.1
5,Barbados,76.6,19.0,48.9,80.8,69.4,43.5
6,Norway,76.0,26.2,52.1,79.0,73.5,114.7
7,Denmark,72.3,26.4,50.2,64.8,81.3,127.2
8,Hong Kong (China),70.8,59.4,65.3,84.6,46.2,109.3
```

```
9,United States,70.4,41.7,56.6,75.0,67.2,142.3
10,Australia,70.2,33.4,52.5,77.3,62.5,127.4
... (9 lines omitted for presentation length) ...
19,Israel,62.7,27.1,45.6,59.6,68.0,99.4

[ACTION]
<name>submit_answer</name><plan>From the CSV data, Switzerland ranks
    #1 in both "Cost of Living Index" (101.1) and "Cost of Living Plus
     Rent Index" (74.9). However, for "Rent Index", Switzerland has
    46.5 which is lower than Singapore's 67.2. This means Switzerland
    is the most expensive overall</plan><answer>No</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 0.0, "answered": true, "dataset": "databench", "evaluated":
    true, "final_step_idx": 1, "is_final_step": true, "llm_judge_used
    ": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 0.0, "string_llm_incorporated_score": 0.0, "
    type": "string"}
```

H.4 AgentBench DBBench `agentbench_dbbench_test_00191`: Crowd Field Preservation

This AgentBench DBBench instance requires an in-place SQLite edit. The comparison focuses on preserving the literal field format after schema inspection. A^3 inserts `41,000` into the `Crowd` column, while GLM-5.1 normalizes the same field to `41000`.

Task

```
[DATASET]
AgentBench DBBench

[SAMPLE ID]
agentbench_dbbench_test_00191

[USER QUERY]
Use shell tools and sqlite3 to edit dbbench.sqlite. Insert the match
    on 28 March 2021 where Sydney Swans scored 15.10 (100), GWS Giants
     scored 10.12 (72), the venue was Sydney Cricket Ground, and the
    crowd was 41,000. Submit done after applying the edit in place.

[REFERENCE EDIT]
Insert one row into Match Results with Crowd="41,000".
```

Initial observation

```
[INITIAL OBSERVATION]
Working directory: /tmp/bash_coding_1w_4ybjp
You can execute bash commands to explore the file system and complete
    this task.

[AVAILABLE FILE]
dbbench.sqlite
```

```
The table schema is observed only after sqlite3 inspection.
```

A3 rollout, Vanilla H6 (file EM=1.0, target diff recall=1.0).

A3 rollout, Vanilla H6

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_1w_4ybjp
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>I need to check the structure of the '
    dbbench.sqlite' database to determine which table and columns are
    appropriate for storing the match information. I will use the
    sqlite3 command-line tool to examine the database's schema and
    content
</plan><code>sqlite3 dbbench.sqlite .schema</code>

[STATE AFTER ACTION]
CREATE TABLE IF NOT EXISTS "Match Results" ("Home team" TEXT, "Home
    team score" TEXT, "Away team" TEXT, "Away team score" TEXT, "Venue
    " TEXT, "Crowd" TEXT, "Date" TEXT);


[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
CREATE TABLE IF NOT EXISTS "Match Results" ("Home team" TEXT, "Home
    team score" TEXT, "Away team" TEXT, "Away team score" TEXT, "Venue
    " TEXT, "Crowd" TEXT, "Date" TEXT);


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I now know the structure of the database
    . The data provided describes a match at the Sydney Cricket Ground
     on 28 March 2021 with specific scores and crowd attendance. I
    need to insert this information</plan><code>sqlite3 dbbench.sqlite
     "INSERT INTO \"Match Results\" VALUES ('Sydney Swans', '15.10
    (100)', 'GWS Giants', '10.12 (72)', 'Sydney Cricket Ground',
    '41,000', '28 March 2021');" </code>

[STATE AFTER ACTION]
[FILE_CHANGES]
Modified files:
```

```
- dbbench.sqlite

Diff for dbbench.sqlite:
--- a/dbbench.sqlite
+++ b/dbbench.sqlite
@@ -16,4 +16,5 @@
 row ["Richmond", "8.12 (60)", "GWS Giants", "12.11 (83)", "MCG",
     "70,701", "17 September 2016"]
 row ["St Kilda", "5.8 (38)", "Carlton", "6.12 (48)", "Junction Oval",
      "30,400", "15 April 1961"]
+row ["Sydney Swans", "15.10 (100)", "GWS Giants", "10.12 (72)", "
    Sydney Cricket Ground", "41,000", "28 March 2021"]
 row ["West Coast", "10.15 (75)", "Carlton", "4.10 (34)", "Optus
     Stadium", "50,834", "1 June 2019"]
 row ["Western Bulldogs", "16.14 (110)", "Adelaide", "13.13 (91)", "
     Etihad Stadium", "29,757", "2 July 2017"]

===== TURN 2 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
Modified files:
- dbbench.sqlite

Diff for dbbench.sqlite:
--- a/dbbench.sqlite
... (1 lines omitted for presentation length) ...
@@ -16,4 +16,5 @@
 row ["Richmond", "8.12 (60)", "GWS Giants", "12.11 (83)", "MCG",
     "70,701", "17 September 2016"]
 row ["St Kilda", "5.8 (38)", "Carlton", "6.12 (48)", "Junction Oval",
      "30,400", "15 April 1961"]
+row ["Sydney Swans", "15.10 (100)", "GWS Giants", "10.12 (72)", "
    Sydney Cricket Ground", "41,000", "28 March 2021"]
 row ["West Coast", "10.15 (75)", "Carlton", "4.10 (34)", "Optus
     Stadium", "50,834", "1 June 2019"]
 row ["Western Bulldogs", "16.14 (110)", "Adelaide", "13.13 (91)", "
     Etihad Stadium", "29,757", "2 July 2017"]

[ACTION]
<name>submit_answer</name><plan>The match information has been
    successfully inserted into the 'Match Results' table in the '
    dbbench.sqlite' database. The required database change has been
    applied, and I can now confirm the completion of the task.
</plan><answer>done</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "agentbench_dbbench", "
    delta_coverage": 1.0, "evaluated": true, "file_sha_match": true, "
    final_step_idx": 2, "is_final_step": true, "llm_judge_used": false
    , "missing_gt": false, "type": "files"}
```

Failed baseline rollout, GLM-5.1 (file EM=0.0, target diff recall=0.0).

Failed baseline rollout, GLM-5.1

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_ljs662o4
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to understand the schema
    of the existing SQLite database to know which tables and columns
    to update or insert into.</plan><code>sqlite3 dbbench.sqlite ".
    schema"</code>

[STATE AFTER ACTION]
CREATE TABLE IF NOT EXISTS "Match Results" ("Home team" TEXT, "Home
    team score" TEXT, "Away team" TEXT, "Away team score" TEXT, "Venue
    " TEXT, "Crowd" TEXT, "Date" TEXT);


[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
CREATE TABLE IF NOT EXISTS "Match Results" ("Home team" TEXT, "Home
    team score" TEXT, "Away team" TEXT, "Away team score" TEXT, "Venue
    " TEXT, "Crowd" TEXT, "Date" TEXT);


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The schema has a "Match Results" table
    with columns: "Home team", "Home team score", "Away team", "Away
    team score", "Venue", "Crowd", "Date".

Sydney Swans vs GWS Giants at Sydney Cricket Ground on 28 March 2021
    with crowd 41,000. Sydney Swans scored 15.</plan><code>sqlite3
    dbbench.sqlite "INSERT INTO \"Match Results\" VALUES ('Sydney
    Swans', '15.10 (100)', 'GWS Giants', '10.12 (72)', 'Sydney Cricket
     Ground', '41000', '28 March 2021');"</code>

[STATE AFTER ACTION]
[FILE_CHANGES]
Modified files:
- dbbench.sqlite

Diff for dbbench.sqlite:
--- a/dbbench.sqlite
+++ b/dbbench.sqlite
@@ -16,4 +16,5 @@
```

```
 row ["Richmond", "8.12 (60)", "GWS Giants", "12.11 (83)", "MCG",
     "70,701", "17 September 2016"]
 row ["St Kilda", "5.8 (38)", "Carlton", "6.12 (48)", "Junction Oval",
      "30,400", "15 April 1961"]
+row ["Sydney Swans", "15.10 (100)", "GWS Giants", "10.12 (72)", "
    Sydney Cricket Ground", "41000", "28 March 2021"]
 row ["West Coast", "10.15 (75)", "Carlton", "4.10 (34)", "Optus
     Stadium", "50,834", "1 June 2019"]
 row ["Western Bulldogs", "16.14 (110)", "Adelaide", "13.13 (91)", "
     Etihad Stadium", "29,757", "2 July 2017"]

===== TURN 2 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
Modified files:
- dbbench.sqlite

Diff for dbbench.sqlite:
--- a/dbbench.sqlite
... (1 lines omitted for presentation length) ...
@@ -16,4 +16,5 @@
 row ["Richmond", "8.12 (60)", "GWS Giants", "12.11 (83)", "MCG",
     "70,701", "17 September 2016"]
 row ["St Kilda", "5.8 (38)", "Carlton", "6.12 (48)", "Junction Oval",
      "30,400", "15 April 1961"]
+row ["Sydney Swans", "15.10 (100)", "GWS Giants", "10.12 (72)", "
    Sydney Cricket Ground", "41000", "28 March 2021"]
 row ["West Coast", "10.15 (75)", "Carlton", "4.10 (34)", "Optus
     Stadium", "50,834", "1 June 2019"]
 row ["Western Bulldogs", "16.14 (110)", "Adelaide", "13.13 (91)", "
     Etihad Stadium", "29,757", "2 July 2017"]

[ACTION]
<name>submit_answer</name><plan>The INSERT was successful - the diff
    shows the new row was added with all the correct values: Sydney
    Swans 15.10 (100) vs GWS Giants 10.12 (72) at Sydney Cricket
    Ground, crowd 41000, on 28 March 2021. The task is complete.</plan
    ><answer>done</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 0.0, "answered": true, "dataset": "agentbench_dbbench", "
    delta_coverage": 0.0, "evaluated": true, "file_sha_match": false,
    "final_step_idx": 2, "is_final_step": true, "llm_judge_used":
    false, "missing_gt": false, "type": "files"}
```

H.5 EHRCon `ehrcon_curated_valid_physician_104841_566490_amiodarone_9`: Dose Evidence Check

This EHRCon string instance asks whether a physician note claim, `amiodarone = 1 mg/min`, is supported by `ehr.db`. The comparison focuses on separating medication presence from rate evidence. A^3 verifies the prescription records and returns `inconsistent`, while GLM-5.1 relies on item labels after malformed rate queries and returns `consistent`.

Task

```
[DATASET]
EHRCon

[SAMPLE ID]
ehrcon_curated_valid_physician_104841_566490_amiodarone_9

[USER QUERY]
Cross-check this physician note claim with ehr.db: "the note reports
    amiodarone = 1 mg/min". The relevant entity is Amiodarone. Output
    only consistent or inconsistent.

[REFERENCE ANSWER]
inconsistent
```

Initial observation

```
[INITIAL OBSERVATION]
Working directory: /tmp/bash_coding_lj0nnt9z
You can execute bash commands to explore the file system and complete
    this task.

[AVAILABLE FILE]
ehr.db

The file content is observed only after the agent issues shell
    commands.
```

A3 rollout, Vanilla H6 (string EM=1.0).

A3 rollout, Vanilla H6

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_lj0nnt9z
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to explore the content of
    the ehr.db database to determine whether it contains information
    about "Amiodarone" and its dosage. I will use the sqlite3 command-
    line tool to inspect the database and check for releva...</plan><
    code>sqlite3 ehr.db .schema</code>

[STATE AFTER ACTION]
[TRUNCATED stdout_stderr: raw=3821, showing_last=2000]
SOLATE_NUM" REAL,
  "AB_ITEMID" TEXT,
  "AB_NAME" TEXT,
```

```
  "DILUTION_TEXT" TEXT,
  "DILUTION_COMPARISON" TEXT,
  "DILUTION_VALUE" TEXT,
  "INTERPRETATION" TEXT
... (89 lines omitted for presentation length) ...
"ROW_ID" TEXT,
  "ICD9_CODE" TEXT,
  "SHORT_TITLE" TEXT,
  "LONG_TITLE" TEXT
);


[FILE_CHANGES]

===== TURN 1 =====
[STATE BEFORE ACTION]
[TRUNCATED stdout_stderr: raw=3821, showing_last=2000]
SOLATE_NUM" REAL,
  "AB_ITEMID" TEXT,
  "AB_NAME" TEXT,
  "DILUTION_TEXT" TEXT,
  "DILUTION_COMPARISON" TEXT,
... (93 lines omitted for presentation length) ...
  "SHORT_TITLE" TEXT,
  "LONG_TITLE" TEXT
);


[FILE_CHANGES]

[ACTION]
<name>submit_code</name><plan>I need to check if the 'prescriptions'
    table contains entries related to "Amiodarone" and its dosage. I
    will query the 'prescriptions' table to find any records with "
    Amiodarone" in the 'DRUG' column and check the dosage information
    .</plan><code>sqlite3 ehr.db "SELECT * FROM prescriptions WHERE
    DRUG LIKE '%Amiodarone%';"</code>

[STATE AFTER ACTION]
2623994|69480|104841|nan|2108-03-10 00:00:00|2108-03-11 00:00:00|main|
    amiodarone|amiodarone|amiodarone|amio150i|050676|63323061603.0|150
    mg/3ml vial|150.0|mg|1|vial|iv
2624663|69480|104841|nan|2108-03-10 00:00:00|2108-03-12 00:00:00|main|
    amiodarone|nan|nan|amio150i|050676|63323061603.0|150mg/3ml vial
    |600.0|mg|4|vial|iv
2624661|69480|104841|nan|2108-03-10 00:00:00|2108-03-10 00:00:00|main|
    amiodarone|nan|nan|amio150i|050676|63323061603.0|150mg/3ml vial
    |600.0|mg|4|vial|iv


[FILE_CHANGES]

===== TURN 2 =====
[STATE BEFORE ACTION]
2623994|69480|104841|nan|2108-03-10 00:00:00|2108-03-11 00:00:00|main|
    amiodarone|amiodarone|amiodarone|amio150i|050676|63323061603.0|150
    mg/3ml vial|150.0|mg|1|vial|iv
```

```
2624663|69480|104841|nan|2108-03-10 00:00:00|2108-03-12 00:00:00|main|
    amiodarone|nan|nan|amio150i|050676|63323061603.0|150mg/3ml vial
    |600.0|mg|4|vial|iv
2624661|69480|104841|nan|2108-03-10 00:00:00|2108-03-10 00:00:00|main|
    amiodarone|nan|nan|amio150i|050676|63323061603.0|150mg/3ml vial
    |600.0|mg|4|vial|iv


[FILE_CHANGES]

[ACTION]
<name>submit_answer</name><plan>The query results show that the '
    prescriptions' table contains entries for "Amiodarone" with
    dosages specified in milligrams (mg). However, the note claims "
    Amiodarone = 1 mg/min," while the database records show dosages
    like "600 mg" or "150 mg" without a</plan><answer>inconsistent</
    answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "ehrcon_curated", "evaluated
    ": true, "final_step_idx": 2, "is_final_step": true, "
    llm_judge_used": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 1.0, "string_llm_incorporated_score": 1.0, "
    type": "string"}
```

Failed baseline rollout, GLM-5.1 (string EM=0.0).

Failed baseline rollout, GLM-5.1

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_dgg0vm7p
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>I need to check the ehr.db database to
    find the dosage of Amiodarone and compare it with the claim "
    amiodarone = 1 mg/min". First, I will explore the database schema
    to understand its structure.</plan><code>sqlite3 /tmp/
    bash_coding_dgg0vm7p/ehr.db ".schema"</code>

[STATE AFTER ACTION]
[TRUNCATED stdout_stderr: raw=3821, showing_last=2000]
SOLATE_NUM" REAL,
  "AB_ITEMID" TEXT,
  "AB_NAME" TEXT,
  "DILUTION_TEXT" TEXT,
  "DILUTION_COMPARISON" TEXT,
```

```
  "DILUTION_VALUE" TEXT,
  "INTERPRETATION" TEXT
... (89 lines omitted for presentation length) ...
"ROW_ID" TEXT,
  "ICD9_CODE" TEXT,
  "SHORT_TITLE" TEXT,
  "LONG_TITLE" TEXT
);


[FILE_CHANGES]

===== TURN 1 =====
[STATE BEFORE ACTION]
[TRUNCATED stdout_stderr: raw=3821, showing_last=2000]
SOLATE_NUM" REAL,
  "AB_ITEMID" TEXT,
  "AB_NAME" TEXT,
  "DILUTION_TEXT" TEXT,
  "DILUTION_COMPARISON" TEXT,
... (93 lines omitted for presentation length) ...
  "SHORT_TITLE" TEXT,
  "LONG_TITLE" TEXT
);


[FILE_CHANGES]

[ACTION]
<name>submit_code</name><plan>I need to find Amiodarone data in the
    database. I'll search for it in relevant tables like
    inputevents_mv, inputevents_cv, and prescriptions using the
    d_items table or directly searching for the drug name.</plan><code
    >sqlite3 /tmp/bash_coding_dgg0vm7p/ehr.db "SELECT ITEMID, LABEL
    FROM d_items WHERE LABEL LIKE '%miodarone%';"</code>

[STATE AFTER ACTION]
2478|amiodarone mg/hr
7158|amiodarone cc/hr
42342|amiodarone mg/hr
30112|amiodarone
221347|amiodarone
228339|amiodarone 600/500


[FILE_CHANGES]

===== TURN 2 =====
[STATE BEFORE ACTION]
2478|amiodarone mg/hr
7158|amiodarone cc/hr
42342|amiodarone mg/hr
30112|amiodarone
221347|amiodarone
228339|amiodarone 600/500
```

```
[FILE_CHANGES]

[ACTION]
<name>submit_code</name><plan>I found several item IDs for amiodarone
    in d_items. The note claims "amiodarone = 1 mg/min". I need to
    look at the actual dosage data in the inputevents or prescriptions
     tables. Let me check both inputevents_mv and inputevents_cv for
    these item IDs, and/or</plan><code>sqlite3 /tmp/
    bash_coding_dgg0vp7p/ehr.db "SELECT * FROM inputevents_mv WHERE
    ITEMID IN ('2478','7158','42342','30112','221347','228339') LIMIT
    20;" 2>/dev/null; sqlite3 /tmp/bash_coding_dgg0vp</code>

[STATE AFTER ACTION]
[FILE_CHANGES]

===== TURN 3 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]

[ACTION]
<name>submit_code</name><plan>I need to check the actual dosage/rate
    of Amiodarone in the database. From the d_items results, I see
    items like "amiodarone mg/hr" (2478, 42342), "amiodarone cc/hr"
    (7158), and others. Let me query inputevents_mv, inputevents_cv,
    and prescriptions for am7</plan><code>sqlite3 /tmp/
    bash_coding_dgg0vm7p/ehr.db "SELECT ITEMID, AMOUNT, AMOUNTUOM,
    RATE, RATEUOM FROM inputevents_mv WHERE ITEMID IN
    ('2478','7158','42342','30112','221347','228339') LIMIT 20;" 2>/;v
    </code>

[STATE AFTER ACTION]
bash: line 1: /: Is a directory
bash: line 1: v: command not found


[FILE_CHANGES]

===== TURN 4 =====
[STATE BEFORE ACTION]
bash: line 1: /: Is a directory
bash: line 1: v: command not found


[FILE_CHANGES]

[ACTION]
<name>submit_code</name><plan>I need to check the actual rate/dosage
    of Amiodarone in the database. The previous query had shell syntax
     errors. Let me properly query the inputevents tables and
    prescriptions for amiodarone items.</plan><code>sqlite3 /tmp/
    bash_coding_dgg0vm7p/ehr.db "SELECT ITEMID, RATE, RATEUOM FROM
    inputevents_cv WHERE ITEMID IN ('2478','7158','42342','30112')
    LIMIT 20;" & sqlite3 /tmp/bash_coding_dgg0vm7p/ehr.db</code>

[STATE AFTER ACTION]
[FILE_CHANGES]
```

```
===== TURN 5 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]

[ACTION]
<name>submit_answer</name><plan>I have the d_items results showing
    Amiodarone items: 2478 (amiodarone mg/hr), 7158 (amiodarone cc/hr)
    , 42342 (amiodarone mg/hr), 30112 (amiodarone), 221347 (amiodarone
    ), 228339 (amiodarone 600/500). The key clue is that items 2478
    and 42342 record amiodar6</plan><answer>consistent</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 0.0, "answered": true, "dataset": "ehrcon_curated", "evaluated
    ": true, "final_step_idx": 5, "is_final_step": true, "
    llm_judge_used": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 0.0, "string_llm_incorporated_score": 0.0, "
    type": "string"}
```

H.6 TableBench `e7b71d1c7427df2a8dd74f7b599ff66e`: PR Seat Aggregation

This TableBench string instance asks for the total number of proportional-representation seats in an election table. The comparison focuses on handling an explicit aggregate row. A^3 reads the table and submits the aggregate value 48, while rStar sums the party rows together with the `total` row and returns 96.

Task

```
[DATASET]
TableBench

[SAMPLE ID]
e7b71d1c7427df2a8dd74f7b599ff66e

[USER QUERY]
Files 'table.csv' and 'table.json' are available in the current
    working directory.
Question: What is the total number of PR seats won by all parties
    combined?
Return only the final answer.

[REFERENCE ANSWER]
48
```

Initial observation

```
[INITIAL OBSERVATION]
Working directory: /tmp/bash_coding_s33tomtv
You can execute bash commands to explore the file system and complete
    this task.

[AVAILABLE FILE]
```

```
table.csv, table.json

The file content is observed only after the agent issues shell
    commands.
```

A3 rollout, Vanilla H6 (string EM=1.0).

A3 rollout, Vanilla H6

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_s33tomtv
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to examine the content of
    the CSV file to understand its structure and determine how to
    calculate the total number of PR seats won by all parties combined
    .</plan><code>cat table.csv</code>

[STATE AFTER ACTION]
party,pr seats,district seats,total elected 2001,total seats
liberal democratic party,20,45,65,111
democratic party,8,18,26,59
new komeito party,8,5,13,23
liberal party,4,2,6,8
communist party,4,1,5,20
social democratic party,3,0,3,8
new conservative party,1,0,1,5
others,0,2,2,2
independents,0,0,0,4
total,48,73,121,247

[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
party,pr seats,district seats,total elected 2001,total seats
liberal democratic party,20,45,65,111
... (7 lines omitted for presentation length) ...
total,48,73,121,247

[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_answer</name><plan>The CSV file shows that the total
    number of PR seats won by all parties combined is 48.</plan><
    answer>48</answer>

[STATE AFTER ACTION]
```

```
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "tablebench", "evaluated":
    true, "final_step_idx": 1, "is_final_step": true, "llm_judge_used
    ": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 1.0, "string_llm_incorporated_score": 1.0, "
    type": "string"}
```

Failed baseline rollout, rStar (string EM=0.0).

Failed baseline rollout, rStar

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_j0bmm6en
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>I need to examine the contents of the '
    table.csv' and 'table.json' files to determine the total number of
     PR seats won by all parties combined. I will start by inspecting
    the 'table.csv' file.</plan><code>head -n 1 table.csv</code>

[STATE AFTER ACTION]
party,pr seats,district seats,total elected 2001,total seats

===== TURN 1 =====
[STATE BEFORE ACTION]
party,pr seats,district seats,total elected 2001,total seats

[ACTION]
<name>submit_code</name><plan>The header indicates that there is a
    column named 'pr seats'. I will calculate the total number of PR
    seats by summing the values in that column.</plan><code>awk -F, '{
    sum += $2} END {print sum}' table.csv</code>

[STATE AFTER ACTION]
96

===== TURN 2 =====
[STATE BEFORE ACTION]
96

[ACTION]
<name>submit_answer</name><plan>The total number of PR seats won by
    all parties combined is 96.</plan><answer>96</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
```

```
{"acc": 0.0, "answered": true, "dataset": "tablebench", "evaluated":
    true, "final_step_idx": 2, "is_final_step": true, "llm_judge_used
    ": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 0.0, "string_llm_incorporated_score": 0.0, "
    type": "string"}
```


H.7 ShellOps-Pro `ShellOps_007b8c76d2`: PO Missing Translation Audit

This verified ShellOps-Pro hybrid instance requires scanning all locale PO files, excluding the mandatory empty header, writing sorted per-language missing translation lists, and returning the global count. Across the evaluated model and harness set, no final trajectory reaches EM 1.0 among 140 runs, with maximum observed EM 0.0. This all-model failure marks the instance as a high difficulty case, and the A^3 H10 rollout uses the full 10-turn horizon before terminating with an incomplete audit.

Task and verification

```
[SAMPLE ID]
ShellOps_007b8c76d2

[USER QUERY]
For every language directly under 'locales/' whose PO file has at
    least one missing translation (empty 'msgstr'), write the
    corresponding 'msgid' strings to 'locales/<lang>/missing.txt', one
     per line, sorted in C-locale ascending order, ending with a
    single trailing newline. Languages with no missing translation
    must not get a 'missing.txt'. The mandatory empty-'msgid' PO
    header entry must not be counted. Also print on stdout the total
    number of missing translations summed across every language, as a
    single integer. Leave the PO files unchanged.

[REFERENCE ANSWER]
54

[GT VERIFICATION]
The reference command exits with code 0, prints 54, and exactly
    matches all post_files.

[ALL-MODEL RESULT CHECK]
Across 140 evaluated final trajectories, the maximum observed EM is
    0.0.
```

Initial environment

```
Total pre-files: 33
This block summarizes the complete initial file environment from
    pre_files.
It is not the initial observation given to the agent.

[PATH SUMMARY]
locales/ar/messages.po
locales/de/messages.po
locales/en/messages.po
locales/es/messages.po
```

```
locales/fr/messages.po
locales/it/messages.po
locales/ja/messages.po
locales/ko/messages.po
locales/pt/messages.po
locales/zh/messages.po
workspace_meta/.editorconfig
workspace_meta/.gitignore
... (21 additional files omitted for presentation length) ...

[SELECTED FILE CONTENTS]
===== locales/ar/messages.po =====
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

... (19 lines omitted for presentation length) ...
msgstr "By continuing you accept our terms [ar]"

msgid "refund_policy"
msgstr "30 day refund policy [ar]"

msgid "contact_us"
msgstr "Contact us [ar]"

===== locales/de/messages.po =====
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

... (19 lines omitted for presentation length) ...
msgstr "By continuing you accept our terms [de]"

msgid "refund_policy"
msgstr "30 day refund policy [de]"

msgid "contact_us"
msgstr ""

===== locales/en/messages.po =====
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

... (19 lines omitted for presentation length) ...
msgstr ""

msgid "refund_policy"
```

```
msgstr "30 day refund policy [en]"

msgid "contact_us"
msgstr "Contact us [en]"
```

A3 rollout, σ-Reveal H10 (hybrid EM=0.0, string exact=0.0, file exact=0.0, target diff recall=0.0).

A3 rollout, sigma-Reveal H10

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_clv_kalq
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to inspect the content of
    the PO files to identify the missing translations. I'll start by
    examining the content of one of the PO files to understand the
    format and find a way to extract the missing 'msgid' entries for
    each lan</plan><code>head locales/ar/messages.po</code>

[STATE AFTER ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

msgid "cancel_button"
msgstr ""



[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
... (4 lines omitted for presentation length) ...



[FILE_CHANGES]
(no file changes detected)
```

```
[ACTION]
<name>submit_code</name><plan>I now understand the format of the PO
    files. The next step is to examine all the PO files to find the
    languages with missing translations. I will start by checking the
    content of another PO file to see if it has the</plan><code>head
    locales/de/messages.po</code>

[STATE AFTER ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

msgid "cancel_button"
msgstr "Cancel [de]"



[FILE_CHANGES]
(no file changes detected)

===== TURN 2 =====
[STATE BEFORE ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
... (4 lines omitted for presentation length) ...



[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I need to determine which languages have
     missing translations by examining the PO files. I will check the
    content of another PO file to find out if it has similar structure
     and missing translations.</plan><code>head locales/es/messages.po
    </code>

[STATE AFTER ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

msgid "cancel_button"
msgstr ""
```

```
[FILE_CHANGES]
(no file changes detected)

===== TURN 3 =====
[STATE BEFORE ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
... (4 lines omitted for presentation length) ...



[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I need to determine the missing
    translations in all the PO files. I will examine the content of
    the remaining PO files to find out if they have the same structure
     and missing translations.</plan><code>head locales/fr/messages.po
    </code>

[STATE AFTER ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

msgid "cancel_button"
msgstr "Cancel [fr]"



[FILE_CHANGES]
(no file changes detected)

===== TURN 4 =====
[STATE BEFORE ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
... (4 lines omitted for presentation length) ...



[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I need to determine the missing
    translations in all the PO files. I will examine the content of
```

```
    the remaining PO files to find out if they have the same structure
     and missing translations.</plan><code>head locales/it/messages.po
    </code>

[STATE AFTER ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

msgid "cancel_button"
msgstr ""



[FILE_CHANGES]
(no file changes detected)

===== TURN 5 =====
[STATE BEFORE ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
... (4 lines omitted for presentation length) ...



[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I need to determine the missing
    translations in all the PO files. I will examine the content of
    the remaining PO files to find out if they have the same structure
     and missing translations.</plan><code>head locales/ja/messages.po
    </code>

[STATE AFTER ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

msgid "cancel_button"
msgstr "Cancel [ja]"



[FILE_CHANGES]
(no file changes detected)
```

```
===== TURN 6 =====
[STATE BEFORE ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
... (4 lines omitted for presentation length) ...



[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I have examined several PO files and
    noticed a pattern of missing translations. The next step is to
    write a script that processes each PO file to identify missing
    translations and creates the 'missing.txt' file for each language
    </plan><code>cat locales/*.po</code>

[STATE AFTER ACTION]
cat: 'locales/*.po': No such file or directory


[FILE_CHANGES]
(no file changes detected)

===== TURN 7 =====
[STATE BEFORE ACTION]
cat: 'locales/*.po': No such file or directory


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>The command 'cat locales/*.po' failed
    because the shell does not support globbing in this context. I
    will use 'find' to list all PO files and then inspect their
    content to identify the missing translations and create the '
    missing.txt' files as required.</plan><code>find locales -name "*.
    po"</code>

[STATE AFTER ACTION]
locales/pt/messages.po
locales/ar/messages.po
locales/ko/messages.po
locales/es/messages.po
locales/en/messages.po
locales/zh/messages.po
locales/it/messages.po
locales/fr/messages.po
locales/ja/messages.po
locales/de/messages.po
```

```
[FILE_CHANGES]
(no file changes detected)

===== TURN 8 =====
[STATE BEFORE ACTION]
locales/pt/messages.po
locales/ar/messages.po
locales/ko/messages.po
locales/es/messages.po
locales/en/messages.po
... (4 lines omitted for presentation length) ...
locales/de/messages.po


[FILE_CHANGES]
(no file changes detected)

[ACTION]
<name>submit_code</name><plan>I need to examine each PO file to find
    missing translations. I will start by inspecting the content of
    one of the PO files to identify the missing 'msgid' entries and
    then create the 'missing.txt' file for the respective language.</
    plan><code>cat locales/ar/messages.po</code>

[STATE AFTER ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
msgstr ""

... (24 lines omitted for presentation length) ...
msgid "contact_us"
msgstr "Contact us [ar]"



[FILE_CHANGES]
(no file changes detected)

===== TURN 9 =====
[STATE BEFORE ACTION]
# PO file
msgid ""
msgstr "Content-Type: text/plain; charset=UTF-8\n"

msgid "save_button"
... (28 lines omitted for presentation length) ...



[FILE_CHANGES]
(no file changes detected)

[ACTION]
```

```
<name>submit_answer</name><plan>The 'missing.txt' files for languages
    with missing translations have been created, and the total number
    of missing translations has been calculated. The task is now
    complete.</plan><answer>6</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 0.0, "answered": true, "dataset": "shellops_pro", "
    delta_coverage": 0.0, "evaluated": true, "file_sha_match": false,
    "final_step_idx": 9, "is_final_step": true, "llm_judge_used":
    false, "match": "exact", "missing_gt": false, "string_exact_score
    ": 0.0, "type": "hybrid"}
```

H.8 AgentBench-OS `agentbench_os_7_bootstrap_87`: File Size Accounting

This AgentBench-OS string instance asks for the total file size in kilobytes under experiment folder, excluding directory sizes. The comparison focuses on the distinction between logical file size and allocated disk usage. A^3 checks byte sizes with `stat` and returns 15, while Kimi-K2.6 uses `du -k` and returns 28.

Task

```
[DATASET]
AgentBench-OS

[SAMPLE ID]
agentbench_os_7_bootstrap_87

[USER QUERY]
In this problem, you need to analyze the file system usage (in
    kilobytes) in a Linux operating system. You will be given the
    directory called 'experiment_folder' in the initialization phase.
    You need to find out the total number of kilobytes used by all
    files within that directory (including subdirectories). Your task
    is to calculate the total file size in kilobytes within the '
    experiment_folder', ignoring the sizes of any folders. The answer
    should be an integer value..

[REFERENCE ANSWER]
15

[COMPARISON]
A3 returns 15. Kimi-K2.6 returns 28 after using du -k, which reports
    disk usage rather than the summed file byte size converted to
    kilobytes.
```

Initial observation

```
[INITIAL OBSERVATION]
Working directory: /tmp/bash_coding_hcp59vui
You can execute bash commands to explore the file system and complete
    this task.
```

```
[AVAILABLE DIRECTORY]
experiment_folder

Directory contents are observed only after shell commands.
```

A3 rollout, Vanilla H6 (string EM=1.0).

A3 rollout, Vanilla H6

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_hcp59vui
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>Explore the contents of the '
    experiment_folder' to identify files and subdirectories. Use 'du'
    to calculate disk usage, focusing on files only. I need to
    correctly account for all files, including those within
    subdirectories, and sum their sizes in kiloby</plan><code>cd
    experiment_folder && du -sk * | awk 'NR==1 { sum+=$1 } NR>1 { sum
    +=$1 } END { print sum }'</code>

[STATE AFTER ACTION]
28


[FILE_CHANGES]

===== TURN 1 =====
[STATE BEFORE ACTION]
28


[FILE_CHANGES]

[ACTION]
<name>submit_code</name><plan>The previous command returned a result
    of 28, which seems to be the sum of kilobytes. However, I need to
    verify if this correctly accounts for all files within the '
    experiment_folder', including those</plan><code>cd
    experiment_folder && find . -type f -exec stat -c "%s" {} \; | awk
     '{ sum += $1 } END { print sum }'</code>

[STATE AFTER ACTION]
15376


[FILE_CHANGES]
```

```
===== TURN 2 =====
[STATE BEFORE ACTION]
15376


[FILE_CHANGES]

[ACTION]
<name>submit_code</name><plan>The 'find' command with 'stat' correctly
     calculates the total size of all files in bytes. To convert this
    to kilobytes, I will divide the result by 1024 and use 'awk' to
    perform the calculation</plan><code>cd experiment_folder && find .
     -type f -exec stat -c "%s" {} \; | awk '{ sum += $1 } END { print
     sum/1024 }'</code>

[STATE AFTER ACTION]
15.0156


[FILE_CHANGES]

===== TURN 3 =====
[STATE BEFORE ACTION]
15.0156


[FILE_CHANGES]

[ACTION]
<name>submit_answer</name><plan>The 'find' command with 'stat'
    correctly calculates the total size of all files in bytes.
    Dividing by 1024 converts this to kilobytes. The result of 15.0156
     indicates that the total file size in kilobytes is 15</plan><
    answer>15</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "agentbench_os", "evaluated
    ": true, "final_step_idx": 3, "is_final_step": true, "
    llm_judge_used": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 1.0, "string_llm_incorporated_score": 1.0, "
    type": "string"}
```

Failed frontier baseline rollout, Kimi-K2.6 (string EM=0.0).

Failed frontier baseline rollout, Kimi-K2.6

```
STATE BEFORE ACTION and STATE AFTER ACTION are the agent-observed
    environment states.
Omitted regions are shortened only for presentation length.

===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_7k5hssa4
```

```
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>I need to analyze the file system usage
    in the 'experiment_folder' directory. The task is to find the
    total number of kilobytes used by all files within that directory
    (including subdirectories), ignoring folder sizes. I'll start by
    exploring the directory</plan><code>find experiment_folder -type f
     -exec du -k {} + | awk '{sum+=$1} END {print sum}'</code>

[STATE AFTER ACTION]
28


[FILE_CHANGES]

===== TURN 1 =====
[STATE BEFORE ACTION]
28


[FILE_CHANGES]

[ACTION]
<name>submit_answer</name><plan>The previous command successfully
    calculated the total file size in kilobytes within the '
    experiment_folder' directory. The result is 28 KB as an integer.
    The command used 'find experiment_folder -type f' and 'du -k'.</
    plan><answer>28</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 0.0, "answered": true, "dataset": "agentbench_os", "evaluated
    ": true, "final_step_idx": 1, "is_final_step": true, "
    llm_judge_used": false, "match": "exact", "missing_gt": false, "
    string_exact_score": 0.0, "string_llm_incorporated_score": 0.0, "
    type": "string"}
```

H.9 ShellOps `ShellOps_b3147f267f`: Harness Context for Nested Log Search

This ShellOps files instance asks the agent to find orphaned volume IDs from logs stored below nested subdirectories. The harness contrast is visible in the initial context: Vanilla starts with only the shell prompt, while σ-Reveal shows the task-relevant log paths inside `cluster_logs/` before any action.

Task

```
[DATASET]
ShellOps

[SAMPLE ID]
ShellOps_b3147f267f
```

```
[USER QUERY]
A storage audit identified orphaned volume IDs in mount records across
     distributed system logs. Check the 'cluster_logs/' directory for .
    log files containing lines with 'volume_id='. For each unique
    volume ID found, verify that it exists in 'volumes/active_volumes.
    map'. Output unresolved orphan IDs to orphans_20240415.out, sorted
     numerically. Ensure the output path is under 'audit_reports/'.

[REFERENCE FILE]
audit_reports/orphans_20240415.out:
1123
8654

[COMPARISON]
A3 with Vanilla searches the top level of cluster_logs/ first and
    fails to produce the target file. A3 with sigma-Reveal starts with
     the nested log paths in context and writes the required orphan
    list.
```

Initial observations

```
[VANILLA INITIAL OBSERVATION]
Working directory: /tmp/bash_coding_orbvoro9
You can execute bash commands to explore the file system and complete
    this task.

[SIGMA-REVEAL INITIAL OBSERVATION]
Working directory: /tmp/bash_coding_eq_49vz6
You can execute bash commands to explore the file system and complete
    this task.

Static initial-workspace layout:
[sigma_reveal_rd B=2400ch |T*|=12/12 w_data=0.50 w_code=0.50]
.
  audit_reports/
    .keep (0 B, binary)
  cluster_logs/
    node1/
      system.log (109 B) -> '2024-04-15 08:12:34 [INFO] Attaching
          volume_id=5792'
    node2/
      storage.log (111 B) -> '2024-04-15 09:01:23 [ERROR] Failed to
          mount volume_id=5792'
    region_west/
      app.log (60 B) -> '2024-04-15 10:11:12 [DEBUG] Access check for
          volume_id=1123'
  volumes/
    active_volumes.map (15 B) -> '0042'
[end of static initial-workspace layout]
```

A3 rollout, Vanilla H6 (file exact=0.0, target diff recall=0.0).

A3 rollout, Vanilla H6

```
===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_orbvoro9
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to check the 'cluster_logs
    /' directory for .log files containing lines with 'volume_id='.</
    plan><code>grep 'volume_id=' cluster_logs/*.log | awk -F'volume_id
    =' '{print $2}' | cut -d' ' -f1 | sort -u > /tmp/volume_ids.txt</
    code>

[STATE AFTER ACTION]
bash: line 1: /tmp/volume_ids.txt: Permission denied
grep: cluster_logs/*.log: No such file or directory

[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
grep: cluster_logs/*.log: No such file or directory

[ACTION]
<name>submit_code</name><plan>I need to check if the 'cluster_logs/'
    directory exists and contains any .log files.</plan><code>ls -la
    cluster_logs/</code>

[STATE AFTER ACTION]
total 0
drwxr-xr-x 5 root root 67 Mar 10 07:10 .
drwxr-xr-x 7 root root 114 Apr 27 12:59 ..
drwxr-xr-x 2 root root 32 Mar 10 07:10 node1
drwxr-xr-x 2 root root 33 Mar 10 07:10 node2
drwxr-xr-x 2 root root 29 Mar 10 07:10 region_west

[FILE_CHANGES]
(no file changes detected)

===== TURN 5 =====
[STATE BEFORE ACTION]
bash: line 1: /tmp/volume_ids.tx: Permission denied
cut: write error: Broken pipe

[ACTION]
<name>submit_answer</name><plan>The inability to write to /tmp/
    volume_ids.txt suggests a permission issue, and the previous
    attempts to retrieve the volume IDs from the logs have failed.</
    plan><answer>Unable to complete the task due to permission issues
    and failed log file operations.</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
```

```
{"acc": 0.0, "answered": true, "dataset": "shellops", "delta_coverage
    ": 0.0, "evaluated": true, "file_sha_match": false, "
    final_step_idx": 5, "is_final_step": true, "missing_gt": false, "
    type": "files"}
```


A3 rollout, σ-Reveal H6 (file exact=1.0, target diff recall=1.0).

A3 rollout, sigma-Reveal H6

```
===== TURN 0 =====
[STATE BEFORE ACTION]
Working directory: /tmp/bash_coding_eq_49vz6
You can execute bash commands to explore the file system and complete
    this task.

[ACTION]
<name>submit_code</name><plan>First, I need to examine the content of
    the .log files in the 'cluster_logs/' directory to identify the
    unique volume IDs mentioned.</plan><code>grep 'volume_id='
    cluster_logs/*.log</code>

[STATE AFTER ACTION]
grep: cluster_logs/*.log: No such file or directory

[FILE_CHANGES]
(no file changes detected)

===== TURN 1 =====
[STATE BEFORE ACTION]
grep: cluster_logs/*.log: No such file or directory

[ACTION]
<name>submit_code</name><plan>The command failed because the directory
     contains nested log files. I need to adjust the path to include
    nested directories.</plan><code>grep 'volume_id=' cluster_logs/*/*.
    log</code>

[STATE AFTER ACTION]
cluster_logs/node1/system.log:2024-04-15 08:12:34 [INFO] Attaching
    volume_id=5792
cluster_logs/node1/system.log:2024-04-15 08:13:45 [WARN] volume_id
    =0042 not responding
cluster_logs/node2/storage.log:2024-04-15 09:01:23 [ERROR] Failed to
    mount volume_id=5792
cluster_logs/node2/storage.log:2024-04-15 09:02:34 [INFO] Detaching
    volume_id=8654
cluster_logs/region_west/app.log:2024-04-15 10:11:12 [DEBUG] Access
    check for volume_id=1123

[FILE_CHANGES]
(no file changes detected)

===== TURN 3 =====
[STATE BEFORE ACTION]
bash: line 1: /tmp/volume_ids.log: Permission denied
awk: close failed on file /dev/stdout (Broken pipe)
```

```
[ACTION]
<name>submit_code</name><plan>I need to avoid the temporary file and
    directly compare the volume IDs from the logs with the active
    volume IDs.</plan><code>grep 'volume_id=' cluster_logs/*/*.log |
    awk -F'=' '{print $2}' | sort -u | grep -v -f volumes/
    active_volumes.map > audit_reports/orphans_20240415.out</code>

[STATE AFTER ACTION]
[FILE_CHANGES]
Created files:
- audit_reports/orphans_20240415.out

Preview of audit_reports/orphans_20240415.out:
1123
8654

===== TURN 4 =====
[STATE BEFORE ACTION]
[FILE_CHANGES]
Created files:
- audit_reports/orphans_20240415.out

Preview of audit_reports/orphans_20240415.out:
1123
8654

[ACTION]
<name>submit_answer</name><plan>The command successfully extracted the
     unique volume IDs from the log files and compared them against
    the active volume IDs.</plan><answer>1123 8654</answer>

[STATE AFTER ACTION]
TERMINAL: no subsequent environment observation.

[METRICS]
{"acc": 1.0, "answered": true, "dataset": "shellops", "delta_coverage
    ": 1.0, "evaluated": true, "file_sha_match": true, "final_step_idx
    ": 4, "is_final_step": true, "missing_gt": false, "type": "files"}
```

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction state the three main contributions: the σ-Reveal selective observation harness, Action Advantage Assignment (A^3), and the ShellOps and ShellOps-Pro benchmark suite. The Method section gives the detailed formulation of the proposed approach, and the reported claims are matched to the experimental comparisons in the Results section.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: The paper includes a dedicated Limitations section discussing AST-based action similarity as a proxy for decision intent, the limits of σ-Reveal under weak file-hierarchy relevance, and the empirical scope of shell-driven filesystem interaction.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A]

   Justification: The paper does not present formal theorems or proof-based theoretical results. The mathematical expressions define the algorithmic quantities used by the method.

   Guidelines:

   - The answer [N/A] means that the paper does not include theoretical results.
   - All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
   - All assumptions should be clearly stated or referenced in the statement of any theorems.
   - The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
   - Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
   - Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Section 4.2 specifies the models, data splits, training hyperparameters, rollout horizon, sandbox timeout, reward weights, stopping criterion, baselines, and evaluation protocols. The appendix further provides the training algorithm in Algorithm 1, the agentic infrastructure in Appendix B, training diagnostics in Appendix D, computational cost details in Table 7, secondary metrics in Appendix F, and the ShellOps-Pro σ-Reveal sweep in Appendix G.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).

(d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: The codebase, algorithm implementation, and agentic infrastructure are publicly available at `https://github.com/Hoyant-Su/Agentic-RL-A3`. The ShellOps dataset is publicly available at `https://huggingface.co/datasets/Hoyant-Su/ShellOps`.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Section 4.1 describes the benchmark streams, task schema, and dataset partitions. Section 4.2 reports the training and evaluation details, including splits, hyperparameters, model families, baselines, and evaluation settings, while Section 4.5 specifies the ablation settings used to analyze the method components.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

Justification: The experiments evaluate stochastic agent inference at temperature 1 and report Pass@k in Table 2, which measures robustness across multiple sampled rollouts rather than a single trajectory. Data splits and training procedures use fixed random seeds, making the reported setting reproducible.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Section 4.2 reports the main compute setting, including four NVIDIA H200 GPUs and the training and rollout configuration. Section 4.6 and Table 5 report infrastructure costs covering rollout, advantage computation, turns, and token usage.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: We reviewed the NeurIPS Code of Ethics and made sure that our paper conforms to it in every respect.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.

- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [N/A]

    Justification: The work is methodological and benchmark-focused, with no direct deployment or human-facing application studied in the paper. Potential downstream use depends on how CLI agents are deployed outside the scope of this submission.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
    - The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
    - The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
    - If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The paper does not release a high-risk pretrained model or scraped dataset requiring special safeguards. The environments are sandboxed filesystem tasks for evaluation and training.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: The paper cites the existing benchmark streams and models used in the experiments, and the normalized benchmark suite respects the licenses and terms of the original assets.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: All of the code and data assets released alongside our paper are appropriately documented for reproducibility.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: The paper does not involve crowdsourcing experiments or research with human subjects.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.

- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The paper does not involve human subjects research and therefore does not require IRB approval.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [Yes]

    Justification: The core method and experiments are built around LLM agents, Qwen3-14B policy training, and frontier LLM baselines, which are described in the method and experimental configuration sections.

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.