MEM-BEHAVE: BEHAVIORAL STRESS TESTING OF AGENT MEMORY SYSTEMS

Anonymous authors
Paper under double-blind review

ABSTRACT

The growing adoption of persistent language-model agents makes reliable long-term memory increasingly important. Yet existing benchmarks typically evaluate memory at a single difficulty level, leaving unclear how performance changes as a capability is placed under increasing stress. We introduce MEM-BEHAVE, a benchmark for stress-testing persistent agent memory across four capabilities: plasticity, interference robustness, contextual integrity, and forgetting. Each capability is paired with a stressor that can intensify over long-term use, namely reinforcement of outdated information, near-miss competing memories, ambiguity in disclosure context, and entanglement of information that should be forgotten. Built from long multi-session histories, MEM-BEHAVE contains 767 scenarios each evaluated at three stress levels across four memory systems yielding 3,508 probes in total. Our results show that performance declines with increasing stress across all four capabilities and memory systems, but the magnitude and onset of degradation vary substantially across systems and capabilities. Further diagnostic analysis shows that many downstream failures are already apparent in the memories retrieved by the system. Together, these findings demonstrate that single-difficulty evaluation can obscure important differences in memory reliability, motivating stress-based evaluation of persistent memory systems. We will publicly release MEM-BEHAVE upon acceptance.

1 INTRODUCTION

Long-term memory is becoming a core component of AI assistants. Deployed assistants now retain user preferences, circumstances, and past requests across conversations (OpenAI, 2024; Anthropic, 2025), and open-source memory layers bring similar capabilities to custom agents (Packer et al., 2023; Chhikara et al., 2025). Persistent memory allows an assistant to build on earlier interactions rather than starting each conversation from scratch (Park et al., 2023; Shinn et al., 2023; Hu et al., 2025; Huang et al., 2026). In practice, memory systems typically process past interactions into an external store and retrieve selected information when relevant to a later request. A memory store, however, is not static. It grows with every session, and the same accumulation makes it harder to use reliably (Chao et al., 2026; Lee et al., 2026). Consider a user who has relied on an assistant for several months. A dietary preference mentioned repeatedly may keep shaping recommendations even after the user changes it. A medical condition shared while arranging an appointment may later surface in an email to an unrelated recipient. When a user asks the assistant to forget a former partner, that person may remain entangled with memories of trips, friends, and shared experiences. These are not simply failures of recall. They arise when memory systems fail to revise changed information, to distinguish relevant memories from competing ones, to keep information within appropriate contexts, or to remove designated information while preserving what should remain.

Existing memory benchmarks typically evaluate systems at a fixed level of difficulty, producing a single score for each capability. Such evaluations do not show whether performance holds as stress increases: two systems with similar scores under low-stress conditions may degrade very differently as the task becomes harder. This motivates our central question: *How does the behavior of an agent memory system change as stress on a memory capability increases?*

To answer this, we adopt *stress testing*, which has exposed failures in NLP models that single-point evaluations miss (Naik et al., 2018; Ribeiro et al., 2020; Liu et al., 2024; Hsieh et al., 2024). The

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: Overview of MEM-BEHAVE. Each panel pairs a memory capability with a stressor and illustrates the required behavior across increasing stress levels.

procedure is simple, we hold a requirement fixed, intensify one factor that makes the requirement harder to satisfy, and measure how performance responds. We introduce MEM-BEHAVE, a benchmark that applies behavioral stress testing to persistent agent memory. We focus on four capabilities that capture distinct requirements of persistent memory. As shown in Figure 1, MEM-BEHAVE pairs each capability with a distinct stressor: ❶ *plasticity*, revising a memory that has changed, as the outdated information is repeated more often before the update; ❷ *interference robustness*, distinguishing the right memory from similar ones, as near-miss competitors accumulate; ❸ *contextual integrity*, restricting information to appropriate contexts, as disclosure cues become more ambiguous; and ❹ *forgetting*, removing requested information while preserving information that should remain, as the target becomes more entangled with other memories. Each capability is evaluated at three stress levels over long multi-session histories, with the scoring rule held fixed. We report performance at each stress level, together with the overall change from low to high stress and where along the stress axis that change occurs.

We use MEM-BEHAVE to evaluate four memory systems and three findings stand out. First, performance degrades as stress increases across all four capabilities, but the point at which it degrades differs by capability. Second, no memory system dominates across all capabilities. Third, many failures are already visible at retrieval, where stale, competing, or private information is retrieved alongside the relevant memory, and information that should survive a deletion becomes harder to retrieve. Together, our results show that memory reliability is capability-specific and stress-dependent, and evaluation at a single difficulty level can overstate how reliable memory systems are in long-term deployment.

Our contributions are threefold: (1) **a stress-based evaluation of agent memory**, which varies capability-specific stressors across levels and measures how memory behavior changes; (2) **MEM-BEHAVE**, a benchmark that tests plasticity, interference robustness, contextual integrity, and forgetting at three stress levels; and (3) **a cross-architecture evaluation** of four memory systems with distinct designs, revealing capability-specific differences in performance and failure modes.

Table 1: Comparison of MEM-BEHAVE with related memory benchmarks. Capability columns denote **PL** plasticity, **IR** interference robustness, **CI** contextual integrity, and **FG** forgetting. ✓ denotes direct evaluation, ◐ partial evaluation, and ✗ no evaluation. *Graded stress* indicates whether the benchmark explicitly constructs multiple ordered stress levels for the same capability.

Benchmark	❶ *PL*	❷ *IR*	❸ *CI*	❹ *FG*	Graded stress
LONGMEMEVAL (Wu et al., 2025)	◐	✗	✗	✗	✗
MEMORYAGENTBENCH (Hu et al., 2026b)	◐	✗	✗	✗	✗
BEAM (Tavakoli et al., 2026)	◐	✗	✗	✗	◐
HORIZONBENCH (Li et al., 2026)	✓	✗	✗	✗	◐
STALE (Chao et al., 2026)	✓	✗	✗	✗	✗
MEMTRACE (Long et al., 2026)	✓	✗	✗	✗	◐
HALUMEM (Chen et al., 2025)	◐	✗	✗	✗	✗
MINTEVAL (Lee et al., 2026)	◐	✓	✗	✗	✗
SUBTLEMEMORY (Wang et al., 2026b)	◐	✓	✗	✗	✗
MEMCONFLICT (Tao et al., 2026)	✓	✓	✗	✗	◐
MEMFAIL (Garg et al., 2026)	✗	◐	✗	✗	◐
SCALE-COND. (Shao et al., 2026)	✗	◐	✗	✗	◐
PRIVACYLENS (Shao et al., 2024)	✗	✗	✓	✗	✗
CIMEMORIES (Mireshghallah et al., 2026)	✗	✗	✓	✗	◐
SP-MEM (Wang et al., 2026a)	✗	✗	◐	✗	✗
MEMOPS (Hao et al., 2026)	✓	✗	✗	✓	✗
MEME (Jung et al., 2026)	✓	◐	✗	✓	✗
MEM-BEHAVE *(Ours)*	✓	✓	✓	✓	✓

2 RELATED WORK

Unified Memory Benchmarks. Memory evaluation has progressed from recalling personal details across a few dialogue sessions (Xu et al., 2022a;b; Jang et al., 2023) to long multi-session histories (Maharana et al., 2024; Du et al., 2024; Zhang et al., 2024; Wu et al., 2025; He et al., 2025; Tavakoli et al., 2026), including multi-party conversations (Hu et al., 2026a) and real dialogue (Lee et al., 2025). More recent work evaluates memory in agentic settings, where past information must guide later actions (Tan et al., 2025; Hu et al., 2026b; Deshpande et al., 2025; Zhao et al., 2026; Bian et al., 2026; Chen et al., 2026; Cheng et al., 2026; Wu et al., 2026; He et al., 2026; Wang et al., 2026c), as well as learning from feedback and personalization over time (Ai et al., 2025; Liu et al., 2026; Zhao et al., 2025; Jiang et al., 2025; Li et al., 2026). Collectively, these benchmarks cover capabilities such as recall, temporal reasoning, updating, and personalization, and evaluate each under a fixed construction regime. The focus of MEM-BEHAVE is complementary. We explicitly vary a capability-specific stressor and measure how performance changes as that stress increases.

Agent Memory Systems. We study external memory systems: stores and procedures kept outside model parameters and the context window that decide what to write, update, and retrieve (Hu et al., 2025; Huang et al., 2026). Early designs page information in and out of a bounded context (Packer et al., 2023) or maintain reflective memory streams that are summarized over time (Park et al., 2023; Zhong et al., 2024). Current systems differ mainly in how memory is represented, as extracted facts reconciled against existing entries (Chhikara et al., 2025), linked notes (Xu et al., 2025), temporal knowledge graphs (Rasmussen et al., 2025), knowledge graphs traversed at query time (Gutiérrez et al., 2025), hierarchical or multi-type stores (Kang et al., 2025; Wang & Chen, 2025), or hybrid graph–vector indexes (Cognee, n.d.), and some systems learn when to add, update, or delete memories through reinforcement learning (Yan et al., 2025). These design choices bear directly on the capabilities MEM-BEHAVE stresses. We evaluate four systems that span these designs (§4.2).

Diagnostic Memory Evaluation. Diagnostic benchmarks ask where and why a memory system fails, rather than only whether its final answer is correct. Chen et al. (2025) evaluate each operation of a memory system separately and find that errors arise mostly during extraction and updating. Garg et al. (2026) decompose memory systems into summarization, storage, and retrieval, and construct adversarial datasets that each target one operation, so that a failure can be attributed to a specific component. Similarly, Hao et al. (2026) and Jung et al. (2026) score explicit memory operations

Table 2: Overview of MEM-BEHAVE statistics. *Scenarios*: base instances, each realized at three stress levels. *Probes (L/M/H)*: probe questions at low, medium, and high stress; forgetting varies by level because each entity the target shares with another person adds one probe. *#Probes*: total across levels. *Sessions/user* and *Turns/user*: mean length of a user's interaction history. Totals for per-user columns average over all users.

Capability	Scenarios	Probes (L/M/H)	#Probes	Sessions/user	Turns/user
1 *Plasticity*	180	180 / 180 / 180	540	50.0	593.4
2 *Interference robustness*	120	120 / 120 / 120	360	50.0	593.3
3 *Contextual integrity*	360	360 / 360 / 360	1,080	146.7	3,966.1
4 *Forgetting*	107	239 / 445 / 844	1,528	120.1	1,168.6
Total	767	899 / 1,105 / 1,504	3,508	103.8	2,357.4

such as updating and deletion. Related work also shows that repeated consolidation by LLMs can degrade useful memories (Zhang et al., 2026). These studies establish that aggregate scores hide distinct failures, many of which arise when stored information is updated rather than when it is retrieved. They identify where a failure occurs, but not how quickly a capability degrades as the pressure on it increases. Table 1 makes this gap concrete, since no prior benchmark covers all four capabilities, and none pairs each capability with its own stressor.

3 MEM-BEHAVE BENCHMARK

MEM-BEHAVE evaluates four memory capabilities, each at three stress levels: low, medium, and high. Rather than generating interaction histories from scratch, we adapt existing long-horizon benchmarks whose annotations identify the information needed for evaluation. Each scenario consists of a user's prior interaction history, a capability-specific target, and the corresponding probes. The target is the information whose handling is being evaluated: the updated state for plasticity and interference robustness, the private fact for contextual integrity, and the information requested to be forgotten for forgetting. Each capability has its own scoring rule.

We use one of two designs, depending on whether the stressor can be introduced into the user's past interaction history or is instead a property of the target. In *probe-fixed* design, we begin with a source example and inject stress-inducing content into its history, so only the interaction history varies with the stressor, while target and probes remain fixed across levels. The added content is written into existing turns rather than appended as new sessions, preserving the number of sessions and turns, their timestamps, and target position. In this way, the total history length varies by less than 0.1%. In *history-fixed* design, the interaction history is shared across stress levels, while target and probes vary. For each stress level, we select a target from the same history whose measured stress falls within that level, together with its associated probes. All levels are therefore evaluated against the same memory store, ruling out differences in users' histories. In summary, the probe-fixed design varies stress for the same target, whereas the history-fixed design compares different targets within the same history.[1] Overall, MEM-BEHAVE contains 767 scenarios and 3,508 probes (Table 2).

Each of the following subsections describes one capability in three parts: an *overview* of the capability, its source data, target, and expected behavior; the *stress construction*, which defines the stressor and explains how scenarios are constructed at each level; and the *evaluation probes*, which describe the probe design. Appendix A provides the complete construction pipelines, Appendix B shows an example of each capability, and Table 4 summarizes the construction of the four capability-specific benchmarks.

3.1 CAPABILITY 1: PLASTICITY

Overview. Plasticity measures whether a memory system updates a belief when later evidence shows that it no longer holds. We adapt the Type I subset of STALE (Chao et al., 2026), in which an

[1] We use `gemini-3.1-pro` (Google DeepMind, 2026) to generate all dataset variations, including planning, rewriting interaction turns, and constructing probes, and we validate each generation with separate LLM judges. At each stage, the judge applies a capability-specific checklist.

earlier observation supports a belief about some attribute of the user, and a later observation implies, without stating it, that the belief has changed. For example, a user who once mentioned living in Seattle later mentions setting up utilities for a new apartment in Portland. The target is the user's updated state, and the system is expected to answer from this state rather than from the old belief.

Stress Construction. The stressor is *reinforcement*: how often the old belief is repeated before the update arrives. It tests whether a system treats the repetitions as one belief that the update supersedes. A system that stores each repetition separately lets outdated memories crowd the retrieved context as reinforcement grows, even when the update is still retrieved; a system that consolidates memories as they are written should merge them and mark the old belief as stale. At low stress, we use the original STALE item, in which the old belief is stated once; medium and high stress add 5 and 10 sessions that each reinforce it once. Like the update, each reinforcement is implicit. It mentions something that holds only if the old belief does, while the user asks about something else (e.g., asking for brunch spots near their apartment in Capitol Hill, a Seattle neighborhood). Reinforcements are written into existing turns between the original observation and the update that say nothing about either state. The high level extends the medium level with five more reinforcements, and the original observation, the update, and their positions are unchanged across levels. The judge additionally confirms that each reinforcement implies the old belief on its own and reveals nothing about the new state. Of the 200 Type I items in STALE, 180 pass all construction steps (Appendix A.1).

Evaluation Probes. We use the probe in STALE to measure whether the old belief still holds. A response passes if it recognizes that the belief may no longer be valid, and fails if it affirms the old state.

3.2 Capability 2: Interference Robustness

Overview. Interference robustness measures whether a memory system can find the memory that answers a request when similar memories compete with it. We adapt the Type II subset of STALE (Chao et al., 2026), in which a change to one attribute of the user has consequences for another, and the target is the user's current state on the affected attribute. The system is expected to answer from the user's own current state rather than from memories that merely resemble it.

Stress Construction. The stressor is the number of *near-miss competitors*, memories on the same subject as the target that do not describe the user's own current situation. Each belongs to another person, comes from something the user read or watched, describes a past situation, or describes one the user is only considering. Because competitors share the target's subject, a system that retrieves or reasons by topic can answer from one of them instead of the target. As in plasticity, low stress uses the original STALE item, and medium and high stress add 5 and 10 competitors. Each competitor implies a different answer from the target, and none repeats the user's earlier state, so this stressor does not reinforce outdated information as in plasticity. The judge confirms that each competitor is clearly not the user's own circumstance yet close enough to be mistaken for it. Of the 200 Type II items in STALE, 120 pass all construction steps (Appendix A.2).

Evaluation Probes. We use the STALE probe that requests an action that depends on the user's current state without mentioning it. A response passes if its concrete recommendation is consistent with the user's current state, and fails otherwise, including when it follows a competitor.

3.3 Capability 3: Contextual Integrity

Overview. Contextual integrity holds that whether information may appropriately flow depends on the norms of the context in which it was shared, including the recipient and purpose (Nissenbaum, 2004). For memory systems, this means that information disclosed to the assistant should not be passed to a third party simply because it is relevant to a request. We build on HorizonBench (Li et al., 2026), which provides 360 simulated users with roughly six months of conversation history and recurring contacts. Into each history, we insert one private fact from each of six AgentSocialBench domains (Wang & Jiang, 2026): health, finance, social, professional, schedule, and lifestyle. Each fact appears incidentally in an existing turn and is never explicitly labeled private, requiring the system to infer the appropriate information-flow norm from context. The target is the private fact, and the expected behavior is to complete the user's request without disclosing it to a third party.

Stress Construction. The stressor is *contextual ambiguity*: how unclear it is, given the request, whether the private fact should be disclosed to the recipient. At low stress, the request provides

little reason to mention the fact; at higher stress, it provides increasingly plausible reasons, such as explaining a constraint or relating to the recipient's circumstances. Because this ambiguity is difficult to control directly during generation, we measure it using five open-weight LLM judges from different model families (Qwen3-32B, Llama-3.3-70B-Instruct, GPT-OSS-120B, Gemma-3-27B, and GLM-4.7-Flash). Each judge predicts whether it would mention the fact when drafting the message. Stress increases with disagreement among the judges: at low stress, all five would omit the fact; at medium stress, one would mention it; and at high stress, two would. These votes determine only the ambiguity level; disclosure remains inappropriate at every level. For each user, we select one fact–request pair per stress level, with the three facts drawn from different domains, so all levels are evaluated against the same history.

Evaluation Probes. Each probe asks the assistant to draft a message to one of the user's contacts. The probe does not mention the private fact, and the recipient is not aware of it.

3.4 Capability 4: Forgetting

Overview. Forgetting measures whether a system can suppress a requested target without losing information about other people. We build on MemArena-L (Zhang & Ma, 2026), using only sessions where users interact with their own assistant, so information about other people comes solely from the user's account. We link each person to entities mentioned in the same turn and select those with at least three linked entities as candidate targets. The target is a person, and the system is asked to forget everything about them while preserving information about others.

Stress Construction. The stressor is *entanglement*: the number of the target's linked entities that at least one other person shares. A system that deletes by subject removing only what is about the target, should be unaffected by entanglement, whereas if it deletes by association, removing whatever was stored alongside the target, erases more of other people's information as entanglement grows. Low, medium, and high stress correspond to at most 2, 3 or 4, and at least 5 shared entities. The three levels of a scenario are from the same user, so all are answered from the same memory store.

Evaluation Probes. Each scenario is probed before and after the deletion request with two kinds of probes. The *target* probe asks the system to recall everything it knows about the target. A response passes if it does not name the target and recovers none of the target's entities. *Ripple* probes ask, for each shared entity, about the other person who shares it, without naming the target. A response passes if it still conveys that person's fact, which should survive the deletion. We score only probes that the system answered correctly before the request, and report baseline recall alongside.

4 Experimental Setup

4.1 Setup

Our evaluation has three stages: ingestion, retrieval, and answer generation. During ingestion, each memory system receives the interaction history session by session in chronological order and decides what to store and how to organize it. At evaluation time, the system retrieves the information it considers relevant to each evaluation probe according to its own retrieval policy. The retrieved memories are then passed to a shared answer model, which generates the response. Only the memory system, including its storage and retrieval behavior, varies across systems. The answer model is fixed. We use `gemini-3.5-flash-lite` at temperature 0 with an 8,000-token answer budget. Within each capability, the same answer prompt is used for all memory systems. Prompts may differ across capabilities to reflect their evaluation requirements. For memory systems that use a language model while writing memories, we use the same model, with `gemini-embedding-001` for embeddings. Retrieval-based systems are evaluated with $k \in \{5, 10\}$ retrieved memories. We report $k = 10$ in Table 3 and $k = 5$ in Appendix D.

4.2 Memory Systems

We evaluate Mem-Behave on four memory systems spanning distinct designs, together with an in-context baseline. HippoRAG 2 (Gutiérrez et al., 2025) represents memory as a knowledge graph built from extracted $(\text{subject}, \text{relation}, \text{object})$ triples and retrieves passages using Personal-

ized PageRank; we index one user–assistant exchange per passage and use the paper's retrieval settings. Mem0 (Chhikara et al., 2025) stores extracted facts as retrievable entries and reconciles new information through explicit add, update, and delete operations; we use reconciliation with vector retrieval and no reranking. Letta (MemGPT) (Packer et al., 2023) maintains editable memory blocks in context and stores additional information in archival memory accessed through tool calls; we use the original memory tools and require an archival write for each session and an archival search for each probe. Cognee (Cognee, n.d.) stores sessions in both a knowledge graph and a vector index and retrieves using hybrid search, with its own answer generation disabled. Finally, the in-context baseline places the full interaction history directly in the prompt, so that all prior information is available to the answer model. Full system configurations are provided in Appendix C.

4.3 Evaluation Metrics

For each capability, we report performance at each stress level, whether the target information was retrieved, and performance when it was retrieved. Scores should be compared across stress levels within a capability, not across capabilities.[2]

Performance. Plasticity and interference robustness are scored by accuracy. A plasticity response is correct if it recognizes that the old belief may no longer hold, and an interference response is correct if it follows the user's current state rather than a competitor. Contextual integrity is scored by the leakage rate, the fraction of drafted messages that hint at or state the private fact, so lower is better. Forgetting is scored by non-target preservation, the fraction of ripple probes answered correctly both before and after deletion, averaged within each scenario first.[3] With $R_c(\mathcal{M}, s)$ the performance of system $\mathcal{M}$ on capability c at stress level s, we report the total change $\Delta = R_c(\mathcal{M}, \texttt{low}) - R_c(\mathcal{M}, \texttt{high})$ and the share of that change occurring between low and medium stress, $\phi = \big(R_c(\mathcal{M}, \texttt{low}) - R_c(\mathcal{M}, \texttt{medium})\big)/\Delta$. Values of ϕ above 0.5 indicate early degradation, values below 0.5 late degradation, and values above 1 partial recovery at high stress.

Retrieval. The answer model sees only the retrieved memories, so a failure can arise either in retrieval or in answer generation. Retrieval asks whether the information needed for a correct response was among the retrieved memories. For plasticity and interference robustness, a judge reads each retrieved memory on its own, and retrieval succeeds when at least one memory states the user's current state. For contextual integrity, retrieval is the fraction of probes for which the private fact was among the retrieved memories. Retrieving the fact is not an error in itself, but it is a precondition for leaking it. For forgetting, retrieval is the fraction of ripple probes for which the other person's fact was among the retrieved memories after deletion. The in-context baseline performs no retrieval and therefore has no retrieval score.

Performance given Retrieval. Recomputing performance only over probes where retrieval succeeded separates a system that never retrieved the information from one that retrieved it and still failed. This gives accuracy given retrieval for plasticity and interference robustness, leakage given retrieval for contextual integrity, and non-target preservation given retrieval for forgetting. The in-context baseline has no retrieval stage and therefore no score given retrieval.

5 Analysis

Across four capabilities and five systems, three findings stand out, which we discuss in turn with reference to Table 3 and Appendix E.

Finding 1: Stress hurts every evaluated memory system across all capabilities. Performance is lower at high stress than at low stress for every system–capability pair, with monotonic declines across stress levels in 18 of 20 cases. The only exceptions are modest recoveries from medium to high stress for Letta on forgetting ($50.4 \rightarrow 53.4$) and the in-context baseline on plasticity ($43.3 \rightarrow 48.9$). Overall, the stressors consistently degrade performance, while systems differ mainly in how much they degrade and where along the stress axis that degradation occurs.

[2] All responses are graded by an LLM judge, `gemini-3.5-flash-lite`, at temperature 0.

[3] Only Mem0 supports deletion through conversation. For HippoRAG 2, Letta, and Cognee, we delete the memories that mention the target through each system's deletion interface, and compare all systems by their behavior after deletion.

Table 3: Performance of each memory system by capability and stress level, with top-k=10 retrieval. **Higher is better, except for contextual integrity, which reports leakage (lower is better).** For each capability, the shaded row gives $\Delta = \texttt{low} - \texttt{high}$, the change in performance from low to high stress, and $\phi = (\texttt{low} - \texttt{medium})/(\texttt{low} - \texttt{high})$, the share of that change that occurs between low and medium stress.

Capability	Stress	In-context	HippoRAG 2	Mem0	Letta	Cognee
❶ *Plasticity*	`low`	68.3	67.1	68.2	39.4	41.7
	`medium`	43.3	58.2	62.2	31.2	32.2
	`high`	48.9	45.4	50.3	21.5	24.4
	Δ / ϕ	19.4 / 1.29	21.7 / 0.41	17.9 / 0.34	17.9 / 0.46	17.3 / 0.55
❷ *Interference robustness*	`low`	36.7	18.3	30.8	24.2	26.7
	`medium`	32.5	15.8	25.8	22.5	20.8
	`high`	29.2	9.2	23.3	20.8	19.2
	Δ / ϕ	7.5 / 0.56	9.1 / 0.27	7.5 / 0.67	3.4 / 0.50	7.5 / 0.79
❸ *Contextual integrity*	`low`	13.3	5.3	5.6	4.1	7.7
	`medium`	23.1	8.7	11.4	12.2	11.9
	`high`	34.7	12.5	22.2	18.1	20.6
	Δ / ϕ	−21.4 / 0.46	−7.2 / 0.47	−16.6 / 0.35	−14.0 / 0.58	−12.9 / 0.33
❹ *Forgetting*	`low`	77.3	80.3	93.9	73.9	67.8
	`medium`	62.7	53.7	74.8	50.4	43.7
	`high`	56.3	45.5	72.6	53.4	39.0
	Δ / ϕ	21.0 / 0.70	34.8 / 0.76	21.3 / 0.90	20.5 / 1.15	28.8 / 0.84

For plasticity, the effect of stress is remarkably consistent across systems. Low-stress performance spans 28.9 points, from 39.4 for Letta to 68.3 for the baseline, yet every system loses between 17.3 and 21.7 points by high stress. For all memory systems, degradation is generally gradual: three have $\phi < 0.5$, indicating larger losses from medium to high stress, while Cognee is nearly balanced at $\phi = 0.55$. The baseline is atypical ($\phi = 1.29$) because performance partially recovers at high stress. For interference robustness, stress has the smallest absolute effect, with drops of only 3.4–9.1 points. However, performance is low even at mild stress, ranging from 36.7 for the baseline at low stress to 9.2 for HippoRAG 2 at high stress. Interference robustness is therefore difficult throughout the stress range, rather than only at its upper end. For contextual integrity, leakage increases by 7.2–21.4 points from low to high stress, with most of the increase occurring between medium and high stress. All systems except Letta have $\phi < 0.5$; Letta reaches $\phi = 0.58$, indicating earlier degradation. The memory systems are tightly clustered at low stress, with leakage between 4.1% and 7.7%, but diverge substantially at high stress, reaching 12.5%–22.2%. Systems that appear similarly safe in clear contexts therefore separate once disclosure becomes more ambiguous. For forgetting, degradation is both largest and earliest. Every system loses most of its score between low and medium stress, with drops of 14.6–26.6 points, followed by comparatively little additional decline. Accordingly, all systems have $\phi \geq 0.70$, in contrast to the mostly lower values observed for plasticity. Forgetting also shows the greatest variation in stress sensitivity across systems, with total degradation Δ ranging from 20.5 to 34.8 points.

Finding 2: No single memory system dominates across all capabilities. The systems trade off capabilities rather than following a single ranking. At high stress, Mem0 leads the memory systems in plasticity (50.3), interference robustness (23.3), and forgetting (72.6), yet it leaks the most (22.2%). HippoRAG 2 shows the opposite pattern, with the lowest leakage (12.5%) but the weakest interference robustness (9.2). Letta is the weakest on plasticity at every stress level while ranking second on interference robustness and forgetting at high stress, and Cognee is the weakest on forgetting. Which system is best therefore depends on which capability matters most.

The in-context baseline shows that external memory is not uniformly beneficial. With the full history in its prompt, it has the strongest interference robustness at every stress level, 5.9 to 6.7 points above the best memory system, but also the worst contextual integrity, with leakage rising from 13.3% to 34.7%. Having every memory in view appears to dilute near-miss competitors, which dominate the small set of memories a retrieval-based system passes to the answer model, while also exposing every private fact to the answer model. Conversely, Mem0 preserves other people's facts after deletion better than the baseline, at 93.9 versus 77.3 at low stress and 72.6 versus 56.3 at high stress. These results are consistent with prior work showing that long-context baselines can remain competitive with memory systems, and that models can be distracted when irrelevant information is placed in their context (Wang et al., 2026c; Pollertlam & Kornsuwannawit, 2026; Shi et al., 2023).

Finding 3: Failures often begin with what the memory system chooses to retrieve. In Appendix E, we decompose each primary score into what the memory system retrieved and how the answer model used it.

For plasticity, most systems retrieve the updated state at a stable rate across stress levels, but rarely alone. Among instances where the update is retrieved, the outdated state comes with it in 94–99% of cases for HippoRAG 2 and Cognee at every level, and in 72.6% rising to 93.8% for Mem0. When the update is retrieved alone, Mem0 answers correctly in at least 97.5% of cases, but when both are present its accuracy falls from 72.6% to 65.6% as stress rises, and the update drops from rank 2.6 to 4.5. Reinforcement thus harms plasticity less by hiding the update than by surrounding it with outdated copies. Interference robustness shows the same pattern more strongly. At high stress, a competitor is retrieved in 99.2–100% of cases for every system, and appears alongside the target in 45.8–81.7% of cases. When only a competitor is retrieved, accuracy falls to 1.6–9.1%. The memory system therefore routinely hands the answer model the very information the benchmark asks it to resist. In contextual integrity, leaks also begin with retrieval, since nearly every leak occurs when the private fact was among the retrieved memories. Once the fact is retrieved, however, the decision to disclose it degrades with stress. Leakage given exposure rises for every system, for Mem0 from 26.3% at low stress to 87.9% at high stress. Retrieving the private fact makes a leak possible, and ambiguity makes it increasingly likely. Forgetting shows the reverse. As entanglement grows, other people's facts become harder to retrieve after deletion, falling from 84.2% to 56.9% for HippoRAG 2 but only from 80.3% to 74.8% for Mem0, while preservation given retrieval remains comparatively high. The main failure is lost access to information that should have survived the deletion.

Across capabilities, the question is not only whether the right memory is found, but whether the memory system surfaces it without stale, competing, or private information, and without losing information that should remain.

6 Conclusion

In this work, we introduce Mem-Behave, a benchmark for stress-testing persistent agent memory under increasing capability-specific difficulty. Rather than assigning each capability a single score, Mem-Behave measures how performance changes as the corresponding stressor increases. Across four memory systems and four capabilities, we find clear differences in both the amount and timing of degradation, showing that performance at one difficulty level does not fully characterize memory-system reliability. We hope our dataset and findings provide a useful basis for evaluating memory systems under conditions that more closely expose their failure modes. Our study has several limitations, which also point to future work. First, each capability is evaluated with one stressor at only three levels. Finer-grained levels may reveal thresholds or non-linear behavior, and combining stressors, such as reinforcement and competing memories together, would test how failures interact. Second, all systems use a single LLM as the answer model, so some failures may reflect limitations of the answer model rather than of the memory system. Repeating the evaluation with several answer models would separate the two. Finally, forgetting requires different deletion interfaces across systems, which may affect how directly the systems can be compared on this capability, and a shared deletion interface would make this comparison cleaner. Beyond evaluation, our diagnostics suggest concrete directions for memory design, including marking superseded memories as stale at write time and contextual gating mechanisms.

AI USE STATEMENT

In this work, we used generative AI tools to generate synthetic datasets for evaluation, provide feedback on research methodology and experiments, clean code implementation, support qualitative data and thematic data analysis, improve readability of the paper. We have not used generative AI tools for developing conceptual frameworks, proposing hypotheses, designing research methodology and experiments, interpreting results, or directly writing the paper. Additionally, we used generative AI tools to create scientific figures, format references, and give feedback on the paper. Two authors have reviewed all AI-assisted work by verifying and testing LLM-generated code for completeness, manually spot-checking synthetic datasets, and supporting AI data analysis with our own qualitative analysis. We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

ETHICS STATEMENT

MEM-BEHAVE contains no data from real people. All interaction histories come from existing synthetic benchmarks, STALE (Chao et al., 2026), HorizonBench (Li et al., 2026), and MemArena-L (Zhang & Ma, 2026), in which users and their contacts are simulated. The private facts we add for contextual integrity, such as health conditions, debts, or legal matters, are generated for fictional users, and any resemblance to real individuals is unintended. No human subjects were involved, so no IRB approval was required. We release MEM-BEHAVE under terms compatible with the licenses of its source benchmarks and document how each capability was constructed (Appendix A). Because the benchmark is built with LLM generation and validated by LLM judges, it may inherit biases of these models, for example in which facts are treated as private or which requests are judged ambiguous. Our findings show that current memory systems can disclose private information to third parties and fail to fully delete information on request. We report these failures to support the design of memory systems that better protect users, and we do not release methods for extracting private information.

REPRODUCIBILITY STATEMENT

We release MEM-BEHAVE through an anonymous Hugging Face repository at `https://huggingface.co/datasets/Mem-Behave/Mem-Behave`, including all four capabilities at every stress level, their interaction histories, targets, probes, and the annotations used for scoring. Section 3 describes how each capability and its stress levels are constructed, and Appendix A gives the complete construction pipelines, including source data, generation steps, validation criteria, and resulting statistics. Appendix B shows a complete item from each capability. The evaluation protocol, answer model, decoding settings, and retrieval budgets are specified in Section 4.1, the metrics in Section 4.3, and the configuration of every memory system in Appendix C. All generation, answering, and judging use fixed models at temperature 0, and results at a second retrieval budget are reported in Appendix D.

REFERENCES

Qingyao Ai, Yichen Tang, Changyue Wang, Jianming Long, Weihang Su, and Yiqun Liu. MemoryBench: A benchmark for memory and continual learning in LLM systems, 2025. URL https://arxiv.org/abs/2510.17281.

Anthropic. Bringing memory to Claude. Claude Blog, September 2025. URL https://claude.com/blog/memory. Published September 11, 2025; Accessed 2026-09-24.

Haonan Bian, Zhiyuan Yao, Sen Hu, Zishan Xu, Shaolei Zhang, Yifu Guo, Ziliang Yang, Xueran Han, Huacan Wang, and Ronghao Chen. RealMem: Benchmarking LLMs in real-world memory-driven interaction. In *Findings of the Association for Computational Linguistics: ACL 2026*, 2026. URL https://aclanthology.org/2026.findings-acl.703/.

Hanxiang Chao, Yihan Bai, Rui Sheng, Tianle Li, and Yushi Sun. STALE: Can LLM agents know when their memories are no longer valid?, 2026. URL https://arxiv.org/abs/2605.06527.

Ding Chen, Simin Niu, Kehang Li, Peng Liu, Xiangping Zheng, Bo Tang, Xinchi Li, Feiyu Xiong, and Zhiyu Li. HaluMem: Evaluating hallucinations in memory systems of agents, 2025. URL https://arxiv.org/abs/2511.03506.

Yuhao Chen, Yi Xu, Xinyun Ding, Xiang Fang, Shuochen Liu, Luxi Lin, Qingyu Zhang, Ya Li, Quan Liu, and Tong Xu. VehicleMemBench: An executable benchmark for multi-user long-term memory in in-vehicle agents, 2026. URL https://arxiv.org/abs/2603.23840.

Zihao Cheng, Weixin Wang, Yu Zhao, Ziyang Ren, Jiaxuan Chen, Ruiyang Xu, Shuai Huang, Yang Chen, Guowei Li, Mengshi Wang, et al. LifeBench: A benchmark for long-horizon multi-source memory, 2026. URL https://arxiv.org/abs/2603.03781.

Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready AI agents with scalable long-term memory, 2025. URL https://arxiv.org/abs/2504.19413.

Cognee. Cognee architecture. Project documentation, n.d. URL https://docs.cognee.ai/core-concepts/architecture. Accessed September 20, 2026.

Darshan Deshpande, Varun Gangal, Hersh Mehta, Anand Kannappan, Rebecca Qian, and Peng Wang. MEMTRACK: Evaluating long-term memory and state tracking in multi-platform dynamic agent environments, 2025. URL https://arxiv.org/abs/2510.01353.

Yiming Du, Hongru Wang, Zhengyi Zhao, Bin Liang, Baojun Wang, Wanjun Zhong, Zezhong Wang, and Kam-Fai Wong. PerLTQA: A personal long-term memory dataset for memory classification, retrieval, and fusion in question answering. In *Proceedings of the 10th SIGHAN Workshop on Chinese Language Processing*, 2024. URL https://aclanthology.org/2024.sighan-1.18/.

Ishir Garg, Neel Kolhe, Dawn Song, and Xuandong Zhao. MemFail: Stress-testing failure modes of LLM memory systems. *arXiv preprint arXiv:2605.26667*, 2026. URL https://arxiv.org/abs/2605.26667.

Google DeepMind. Gemini 3.1 pro model card. https://deepmind.google/models/model-cards/gemini-3-1-pro/, 2026.

Bernal Jiménez Gutiérrez, Yiheng Shu, Weijian Qi, Sizhe Zhou, and Yu Su. From RAG to memory: Non-parametric continual learning for large language models. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 21497–21515, 2025. URL https://proceedings.mlr.press/v267/gutierrez25a.html.

Xixuan Hao, Zeyu Zhang, Zehao Lin, Yihang Sun, Ziliang Guo, Xichong Zhang, Yuxuan Liang, Feiyu Xiong, and Zhiyu Li. MemOps: Benchmarking lifecycle memory operations in long-horizon conversations, 2026. URL https://arxiv.org/abs/2607.12893.

Junqing He, Liang Zhu, Rui Wang, Xi Wang, Reza Haffari, and Jiaxing Zhang. MADial-Bench: Towards real-world evaluation of memory-augmented dialogue generation. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics*, 2025. URL https://aclanthology.org/2025.naacl-long.499/.

Zexue He, Yu Wang, Churan Zhi, Yuanzhe Hu, Tzu-Ping Chen, Lang Yin, Ze Chen, Tong Arthur Wu, Siru Ouyang, Zihan Wang, Jiaxin Pei, Julian McAuley, Yejin Choi, and Alex Pentland. MemoryArena: Benchmarking agent memory in interdependent multi-session agentic tasks, 2026. URL https://arxiv.org/abs/2602.16313.

Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. RULER: What's the real context size of your long-context language models? In *Conference on Language Modeling*, 2024.

Chuanrui Hu, Tong Li, Xingze Gao, Hongda Chen, Yi Bai, Dannong Xu, Tianwei Lin, Xiaohong Li, Yunyun Han, Jian Pei, and Yafeng Deng. Evaluating long-horizon memory for multi-party collaborative dialogues, 2026a. URL https://arxiv.org/abs/2602.01313.

Yuanzhe Hu, Yu Wang, and Julian McAuley. Evaluating memory in LLM agents via incremental multi-turn interactions. In *International Conference on Learning Representations*, 2026b. URL https://openreview.net/forum?id=DT7JyQC3MR.

Yuyang Hu, Shichun Liu, Yanwei Yue, Guibin Zhang, Boyang Liu, Fangyi Zhu, Jiahang Lin, Honglin Guo, Shihan Dou, Zhiheng Xi, Senjie Jin, Jiejun Tan, Yanbin Yin, Jiongnan Liu, Zeyu Zhang, Zhongxiang Sun, Yutao Zhu, Hao Sun, Boci Peng, Zhenrong Cheng, Xuanbo Fan, Jiaxin Guo, Xinlei Yu, Zhenhong Zhou, Zewen Hu, Jiahao Huo, Junhao Wang, Yuwei Niu, Yu Wang, Zhenfei Yin, Xiaobin Hu, Yue Liao, Qiankun Li, Kun Wang, Wangchunshu Zhou, Yixin Liu, Dawei Cheng, Qi Zhang, Tao Gui, Shirui Pan, Yan Zhang, Philip Torr, Zhicheng Dou, Ji-Rong Wen, Xuanjing Huang, Yu-Gang Jiang, and Shuicheng Yan. Memory in the age of AI agents, 2025. URL https://arxiv.org/abs/2512.13564.

Wei-Chieh Huang, Weizhi Zhang, Yueqing Liang, Yuanchen Bei, Yankai Chen, Tao Feng, Xinyu Pan, Zhen Tan, Yu Wang, Tianxin Wei, Shanglin Wu, Ruiyao Xu, Liangwei Yang, Rui Yang, Wooseong Yang, Chin-Yuan Yeh, Hanrong Zhang, Haozhen Zhang, Siqi Zhu, Henry Peng Zou, Wanjia Zhao, Song Wang, Wujiang Xu, Zixuan Ke, Zheng Hui, Dawei Li, Yaozu Wu, Langzhou He, Chen Wang, Xiongxiao Xu, Baixiang Huang, Juntao Tan, Shelby Heinecke, Huan Wang, Caiming Xiong, Ahmed Metwally, Jun Yan, Chen-Yu Lee, Hanqing Zeng, Yinglong Xia, Xiaokai Wei, Ali Payani, Yu Wang, Haitong Ma, Wenya Wang, Chenguang Wang, Yu Zhang, Xin Eric Wang, Yongfeng Zhang, Jiaxuan You, Hanghang Tong, Xiao Luo, Xue Liu, Yizhou Sun, Wei Wang, Julian McAuley, James Zou, Jiawei Han, Philip S. Yu, and Kai Shu. A survey of agent memory in the second half: Towards self-evolving and long-horizon agents. *Transactions on Machine Learning Research*, 2026. ISSN 2835-8856. URL https://openreview.net/forum?id=XycbogUAeJ. Survey Certification.

Jihyoung Jang, Minseong Boo, and Hyounghun Kim. Conversation chronicles: Towards diverse temporal and relational dynamics in multi-session conversations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023. URL https://aclanthology.org/2023.emnlp-main.838/.

Bowen Jiang, Zhuoqun Hao, Young-Min Cho, Bryan Li, Yuan Yuan, Sihao Chen, Lyle Ungar, Camillo J. Taylor, and Dan Roth. Know me, respond to me: Benchmarking LLMs for dynamic user profiling and personalized responses at scale. In *Conference on Language Modeling*, 2025.

Seokwon Jung, Alexander Rubinstein, Arnas Uselis, Sangdoo Yun, and Seong Joon Oh. MEME: Multi-entity & evolving memory evaluation. *arXiv preprint arXiv:2605.12477*, 2026.

Jiazheng Kang, Mingming Ji, Zhe Zhao, and Ting Bai. Memory OS of AI agent, 2025. URL https://arxiv.org/abs/2506.06326.

Dong-Ho Lee, Adyasha Maharana, Jay Pujara, Xiang Ren, and Francesco Barbieri. REALTALK: A 21-day real-world dataset for long-term conversation, 2025. URL https://arxiv.org/abs/2502.13270.

Hyunji Lee, Justin Chih-Yao Chen, Joykirat Singh, Zaid Khan, Elias Stengel-Eskin, and Mohit Bansal. MINTEval: Evaluating memory under multi-target interference in long-horizon agent systems, 2026. URL https://arxiv.org/abs/2605.18565.

Shuyue Stella Li, Bhargavi Paranjape, Kerem Oktar, Zhongyao Ma, Gelin Zhou, Lin Guan, Na Zhang, Sem Park, Lin Chen, Diyi Yang, Yulia Tsvetkov, and Asli Celikyilmaz. HorizonBench: Long-horizon personalization with evolving preferences, 2026. URL https://arxiv.org/abs/2604.17283.

Guanming Liu, Yuqi Ren, Hansu Gu, Peng Zhang, Weihang Wang, Jiahao Liu, Ning Gu, and Tun Lu. StreamMemBench: Streaming evaluation of agent memory for future-oriented assistance, 2026. URL https://arxiv.org/abs/2606.14571.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024.

Xianxuan Long, Zhikai Chen, Shenglai Zeng, Shouren Wang, Kai Guo, and Jiliang Tang. Memtrace: Probing what final accuracy misses in long-term memory, 2026. URL https://arxiv.org/abs/2606.17328.

Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. Evaluating very long-term conversational memory of LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 13851–13870. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.acl-long.747. URL https://aclanthology.org/2024.acl-long.747/.

Niloofar Mireshghallah, Neal Mangaokar, Narine Kokhlikyan, Arman Zharmagambetov, Manzil Zaheer, Saeed Mahloujifar, and Kamalika Chaudhuri. CIMemories: A compositional benchmark for contextual integrity in LLMs. In *International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/9a2bcfaf383638e166162a25b6dff125-Abstract-Conference.html.

Aakanksha Naik, Abhilasha Ravichander, Norman Sadeh, Carolyn Rose, and Graham Neubig. Stress test evaluation for natural language inference. In *Proceedings of the 27th International Conference on Computational Linguistics*, pp. 2340–2353, 2018.

Helen Nissenbaum. Privacy as contextual integrity. *Washington Law Review*, 79(1):119–158, 2004.

OpenAI. Memory and new controls for ChatGPT. https://openai.com/index/memory-and-new-controls-for-chatgpt/, 2024. Accessed 2026-09-21.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards LLMs as operating systems, 2023. URL https://arxiv.org/abs/2310.08560.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST)*, 2023.

Natchanon Pollertlam and Witchayut Kornsuwannawit. Beyond the context window: A cost-performance analysis of fact-based memory vs. long-context LLMs for persistent agents. *arXiv preprint arXiv:2603.04814*, 2026.

Preston Rasmussen, Pavlo Paliychuk, Travis Beauvais, Jack Ryan, and Daniel Chalef. Zep: A temporal knowledge graph architecture for agent memory, 2025. URL https://arxiv.org/abs/2501.13956.

Marco Tulio Ribeiro, Tongshuang Wu, Carlos Guestrin, and Sameer Singh. Beyond accuracy: Behavioral testing of NLP models with CheckList. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4902–4912, 2020.

Jiaqi Shao, Yiyi Lu, Yunzhen Zhang, and Bing Luo. When stored evidence stops being usable: Scale-conditioned evaluation of agent memory, 2026. URL https://arxiv.org/abs/2605.07313.

Yijia Shao, Tianshi Li, Weiyan Shi, Yanchen Liu, and Diyi Yang. PrivacyLens: Evaluating privacy norm awareness of language models in action. In *Advances in Neural Information Processing Systems*, 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/a2a7e58309d5190082390ff10ff3b2b8-Abstract-Datasets_and_Benchmarks_Track.html.

Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed H. Chi, Nathanael Schärli, and Denny Zhou. Large language models can be easily distracted by irrelevant context. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 31210–31227. PMLR, 2023.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, 2023.

Haoran Tan, Zeyu Zhang, Chen Ma, Xu Chen, Quanyu Dai, and Zhenhua Dong. MemBench: Towards more comprehensive evaluation on the memory of LLM-based agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 19336–19352. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.findings-acl.989. URL https://aclanthology.org/2025.findings-acl.989/.

Zhen Tao, Jinxiang Zhao, Peng Liu, Dinghao Xi, Yanfang Chen, Wei Xu, and Zhiyu Li. Memconflict: Evaluating long-term memory systems under memory conflicts. *arXiv preprint arXiv:2605.20926*, 2026. URL https://arxiv.org/abs/2605.20926.

Mohammad Tavakoli, Alireza Salemi, Carrie Ye, Mohamed Abdalla, Hamed Zamani, and J. Ross Mitchell. Beyond a million tokens: Benchmarking and enhancing long-term memory in LLMs. In *International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/d7f0cfa0fe759b033d5262e1bb7d4065-Abstract-Conference.html.

Prince Zizhuang Wang and Shuli Jiang. AgentSocialBench: Evaluating privacy risks in human-centered agentic social networks, 2026. URL https://arxiv.org/abs/2604.01487.

Wenjie Wang, Wenhe Si, Xinyue Xu, and Yue Xu. What to remember, what to reveal: Privacy-aware memory for conversational agents, 2026a. URL https://arxiv.org/abs/2608.16551.

Wenxuan Wang, Haoyu Sun, Fukuan Hou, Mingyang Song, Weinan Zhang, Yu Cheng, and Yang Yang. Subtlememory: A benchmark for fine-grained relational memory discrimination in long-horizon ai agents, 2026b. URL https://arxiv.org/abs/2606.05761.

Yu Wang and Xi Chen. MIRIX: Multi-agent memory system for LLM-based agents, 2025. URL https://arxiv.org/abs/2507.07957.

Yuyao Wang, Zhongjian Zhang, Mo Chi, Kaichi Yu, Yuhan Li, Miao Peng, Bing Tong, Chen Zhang, Yan Zhou, and Jia Li. EvoMemBench: Benchmarking agent memory from a self-evolving perspective, 2026c. URL https://arxiv.org/abs/2605.18421.

Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. LongMemEval: Benchmarking chat assistants on long-term interactive memory. In *International Conference on Learning Representations*, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/hash/d813d324dbf0598bbdc9c8e79740ed01-Abstract-Conference.html.

Di Wu, Zixiang Ji, Asmi Kawatkar, Bryan Kwan, Jia-Chen Gu, Nanyun Peng, and Kai-Wei Chang. LongMemEval-V2: Evaluating long-term agent memory toward experienced colleagues. ICML 2026 Workshop on SCALE: Scalable Learning and Optimization for Efficient Multimodal AI Agents, 2026. URL https://icml.cc/virtual/2026/67423. Workshop presentation; full paper available as arXiv:2605.12493.

Jing Xu, Arthur Szlam, and Jason Weston. Beyond goldfish memory: Long-term open-domain conversation. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics*, pp. 5180–5197, 2022a.

Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-MEM: Agentic memory for LLM agents. In *Advances in Neural Information Processing Systems*, 2025. doi: 10.52202/085713-0593. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/19909c36f51abc4856b4560aff3d36d6-Abstract-Conference.html.

Xinchao Xu, Zhibin Gou, Wenquan Wu, Zheng-Yu Niu, Hua Wu, Haifeng Wang, and Shihang Wang. Long time no see! open-domain conversation with long-term persona memory. In *Findings of the Association for Computational Linguistics: ACL 2022*, 2022b. URL https://aclanthology.org/2022.findings-acl.207/.

Sikuan Yan, Xiufeng Yang, Zuchao Huang, Ercong Nie, Zifeng Ding, Zonggen Li, Xiaowen Ma, Jinhe Bi, Kristian Kersting, Jeff Z. Pan, Hinrich Schütze, Volker Tresp, and Yunpu Ma. Memory-R1: Enhancing large language model agents to manage and utilize memories via reinforcement learning, 2025. URL https://arxiv.org/abs/2508.19828.

Dylan Zhang, Yanshan Lin, Zhengkun Wu, Yihang Sun, Bingxuan Li, Dianqi Li, and Hao Peng. Useful memories become faulty when continuously updated by LLMs. *arXiv preprint arXiv:2605.12978*, 2026.

Jiadong Zhang and Xiaosong Ma. MemArena: An ego-centric benchmark for on-device agentic personal memory assistants at scale, 2026. URL https://arxiv.org/abs/2608.02613.

Zeyu Zhang, Quanyu Dai, Luyu Chen, Zeren Jiang, Rui Li, Jieming Zhu, Xu Chen, Yi Xie, Zhenhua Dong, and Ji-Rong Wen. MemSim: A Bayesian simulator for evaluating memory of LLM-based personal assistants, 2024. URL https://arxiv.org/abs/2409.20163.

Siyan Zhao, Mingyi Hong, Yang Liu, Devamanyu Hazarika, and Kaixiang Lin. Do LLMs recognize your preferences? evaluating personalized preference following in LLMs. In *International Conference on Learning Representations*, 2025.

Yujie Zhao, Boqin Yuan, Junbo Huang, Haocheng Yuan, Zhongming Yu, Haozhou Xu, Lanxiang Hu, Abhilash Shankarampeta, Zimeng Huang, Wentao Ni, Yuandong Tian, and Jishen Zhao. AMA-Bench: Evaluating long-horizon memory for agentic applications, 2026. URL https://arxiv.org/abs/2602.22769.

Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. MemoryBank: Enhancing large language models with long-term memory. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, 2024.

A CONSTRUCTION DETAILS

This appendix gives the full construction of each capability in MEM-BEHAVE: source data, generation pipeline, validation, and statistics. Section 3 summarizes it.

A.1 PLASTICITY

Plasticity asks whether a memory system adopts a valid update to a belief it already holds. We stress it by increasing the amount of evidence that supports the outdated belief before the update arrives. A system that resolves conflicts by *supersession* lets the later statement about the same attribute win, however often the earlier value was mentioned. A system that resolves conflicts by *evidence weight* lets the more frequently mentioned value win. As reinforcement increases, the second kind of system becomes less and less plastic.

Source. We build on STALE (Chao et al., 2026). Each STALE item is a multi-session user-assistant history in which a user statement m_{old} in session S_{old} establishes a belief, and a later statement m_{new} in session S_{new} invalidates it. We choose one probing query from STALE's default set of three probing queries, which test whether a system recognizes that the belief is outdated. No utterance in the history explicitly negates or corrects the old belief, and the remaining sessions are filtered so that m_{new} is the only evidence of the change. We use only STALE's co-referential (Type I) items, in which m_{new} implies an incompatible value for the same attribute as m_{old}, without stating that the old value no longer holds.

Stress manipulation. We vary the number of additional sessions $k \in \{0, 5, 10\}$ that reinforce the old belief. The low-stress condition (k=0) is the unmodified STALE item, so the old belief is supported by a single statement. The medium and high conditions support it by additional 5 and 10 sessions, respectively, and m_{new} remains the only statement of the new state. Reinforcements are built in three steps:

1. **Belief extraction.** An LLM rewrites the belief as a declarative statement, taking the wording from the first probing query. It labels the belief as a *value* (e.g., a city of residence) or a *state* (e.g., a routine or an arrangement), and as *durable* or *transient*. It also produces two lists of terms that unambiguously signal the old state or the new state.
2. **Reinforcement planting.** Each reinforcement rewrites one existing user turn, together with the assistant turn that follows it, inside a session that is otherwise unrelated to the belief. The rewritten user turn reveals the old belief *incidentally*, as context for a question on another topic. For value beliefs, it names something that only holds if the value holds (e.g., a neighborhood that implies a city). For state beliefs, it shows the user acting within the state (e.g., planning around a semester schedule) rather than restating it. The ten plants for an item are generated in sequence, and each generation sees summaries of the plants that already exist, so the reinforcements describe different occasions rather than paraphrasing one another.
3. **Validation.** An LLM judge checks every plant against seven criteria without being told its stress level, so validation is equally strict at every level. The criteria are: (i) the planted turn alone entails the belief, rather than merely being consistent with it; (ii) the belief is incidental and fits the host conversation; (iii) no new-state information leaks; (iv) the belief is stated without hedging; (v) the rewritten turn is coherent with the rest of the session; (vi) the plant does not duplicate m_{old} or earlier plants; and (vii) nothing outside the two rewritten turns changes. A rejected plant is regenerated using the judge's feedback. If it fails repeatedly, it is moved to another host session from the same block.

Held fixed. Plants are written into existing sessions instead of being appended as new ones. Appending ten sessions would change context length, the number of sessions, and the position of m_{new} at the same time as the dose, so a system could fail at k=10 simply because m_{new} fell outside its retrieval budget. Across all three levels of an item, the following are identical: m_{old}, m_{new} and the sessions that contain them; all three probing queries and the gold answer (the new state); and the number of sessions and turns, their order, and their timestamps. Host sessions come only from the sessions strictly between S_{old} and S_{new} that contain none of the old-state or new-state terms. Two

Table 4: Construction summary of MEM-BEHAVE. Probe-fixed variants preserve the target and probes while adding stress-inducing memories. History-fixed share a history but differ in measured stress. Stress levels are listed from low to high. N_b counts base scenarios: source items for constructed variants and user histories for selected targets.

Behavior	Source	Design	Stress: `low` / `medium` / `high`	Gold behavior
❶ *Plasticity*	STALE (Chao et al., 2026)	probe-fixed	Discussions supporting the old belief: 0 / 5 / 10	Let the update supersede the old belief
❷ *Interference robustness*	STALE (Chao et al., 2026)	probe-fixed	Near-miss competing memories: 0 / 5 / 10	Act on the user's current state, not competing memories
❸ *Contextual integrity*	HorizonBench (Li et al., 2026)	history-fixed	Judge disagreement on disclosure: 5:0 / 4:1 / 3:2	Complete the request without additional private disclosure
❹ *Forgetting*	MemArena-L (He et al., 2026)	history-fixed	Relational entanglement: ≤ 2 / 3–4 / ≥ 5	Forget the target, keep shared facts

consequences follow. The belief's first mention stays at S_{old}, so its apparent age does not grow with the dose. No host session already contains evidence about the belief, so the dose can be counted exactly. We divide this pool into five contiguous blocks and draw one host per block for $k{=}5$ and two per block for $k{=}10$, using a fixed seed. As a result, the high condition is the medium condition plus five more plants, and at both levels the reinforcements span the same stretch of the history, which keeps the timing of the old belief's most recent mention roughly constant across levels. Each rewritten session must stay within $\pm 2\%$ of its original length. Across the final suite, total history length changes by at most 0.07% between $k{=}0$ and $k{=}10$.

Resulting data. Of the 200 Type I items in STALE, 6 did not complete belief extraction, 11 were excluded as transient, and 3 failed to receive all ten validated plants. The final plasticity suite contains 180 items at three stress levels, giving 540 histories and 1,800 validated plants. Every history has 50 sessions and about 700K characters. m_{old} and m_{new} fall in sessions 7 and 35 at the median, and the host pools contain between 12 and 37 sessions (median 25). Of the 180 beliefs, 145 are states and 35 are values.

A.2 INTERFERENCE ROBUSTNESS

Interference robustness asks whether a target memory remains accessible as similar memories accumulate around it. The failure we target is *confusion*. A user who talks about their own dental plan will also mention a sister's plan, an old retail job's plan, or an article about dental coverage. These memories share the target's subject matter and vocabulary, so a system that retrieves or reasons by topic can answer from one of them instead of from the user's own situation. We stress this capability by increasing the number of such competing memories while leaving the target unchanged. This differs from adding irrelevant history (Shao et al., 2026): every competing memory we add is a near miss that a system could plausibly mistake for the target.

Source. We again build on STALE (Chao et al., 2026), using its propagated (Type II) items, so this suite does not overlap with the plasticity suite. The target memory is m_{new}, the user's current circumstance. Each item is probed with STALE's implicit-policy-adaptation query, which asks the system to apply the user's current state to a downstream task. This query names neither the old state nor the new one, so it can only be answered by finding the target through its subject matter, which is exactly where similar memories compete.

Stress manipulation. We vary the number of competing memories $k \in \{0, 5, 10\}$. The low-stress condition ($k{=}0$) is the unmodified STALE item. Competing memories are built with the same three-step pipeline as plasticity:

1. **Planning.** An LLM identifies what the target is about, the detail the probe turns on (e.g., *the user's current dental coverage*), and the target's value for that detail (e.g., *an employer-sponsored premium plan*). It then plans ten competing memories that meet two conditions. First, none describes the user's own current circumstance: each belongs to another person, comes from something the user read or watched, describes a place the user has left, or describes a situation the user is only considering. Second, each gives a *different* value for the detail the probe turns on (e.g., *my sister's new job only offers a dental discount card*). A system that answers from a competing memory therefore gives a traceably wrong answer. No competing memory may reuse the old value from m_{old}. Otherwise, an answer based on that value could come either from interference or from failing to notice that the old belief is outdated.
2. **Planting.** Each competing memory is written into an existing user turn and the assistant turn that follows it, inside a session about a related topic, so that the memory comes up in passing.
3. **Validation.** An LLM judge, not told the dose, checks every plant on seven criteria: it is clearly not the user's own circumstance; its frame (another person, secondhand, past, or hypothetical) stays consistent; it gives a different value from the target; it is close enough in subject matter to be mistaken for the target; it fits the host conversation naturally; it does not copy the probe's phrasing; and it does not repeat an earlier plant. A rejected plant is regenerated using the judge's feedback.

Held fixed. As in plasticity, plants are written into existing turns, so session count, turn count and timestamps are identical across levels, and the total character count changes by at most 0.09%. m_{old}, m_{new}, the probe and the gold answer (the target) never change. Host sessions are chosen from sessions of at least eight turns, ranked by how close their topic already is to the target, and split evenly between sessions before and after the target. The five medium-stress hosts are every other one of the ten high-stress hosts, so the medium condition is a subset of the high one, and at both levels competing memories fall on both sides of the target.

Resulting data. Of STALE's 200 propagated (Type II) items, 120 enter the suite, giving 360 histories and 1,200 validated competing memories. The remaining 80 items could not be planted: they offer too few eligible host sessions, that is, sessions that are long enough to rewrite, close enough in topic to carry a near miss, and free of the target and the outdated belief. Every history has 50 sessions and about 590 turns and 710K characters at the median, and the total character count changes by at most 0.09% between $k{=}0$ and $k{=}10$.

A.3 Contextual Integrity

Contextual integrity asks whether a memory system respects the information-flow norms of the context in which a memory is used (Nissenbaum, 2004). A fact the user shared with the assistant should not reach a third party merely because it is relevant to that party. However, some of its practical consequences may be appropriate to pass on. The failure we target is *over-disclosure*: the system retrieves a private fact correctly, but then places it in a message written for someone else. We stress this capability with *contextual ambiguity*. At low stress, the request gives no natural reason to bring up the fact. At high stress, it offers plausible reasons, such as explaining a constraint, relating to someone in a similar situation, or adding warmth. The norm itself never changes: at every level, the private fact should stay out of the message.

Source. We build on HorizonBench (Li et al., 2026). It provides 360 simulated users, each with about six months of conversation history, a structured profile, and a cast of people who recur in the user's life. We keep only the sessions in which the user talks to a plain AI assistant, along with the short life-event sessions, and drop sessions in which the model plays a named human character. The history is otherwise unchanged. The recurring cast is what makes HorizonBench a good fit for this capability, because it supplies realistic recipients for messages that have a history with the user.

Secret injection. For each user, an LLM plans one private fact in each of six domains taken from AgentSocialBench (Wang & Jiang, 2026): health, finance, social, schedule, professional, and

lifestyle. Each fact is specific enough that a leak can be detected (e.g., *owes about $6,800 in back taxes*). Alongside the fact, the plan records its practical consequence, which others may legitimately need to know (e.g., *needs payment within 15 days*); a way of stating that consequence without revealing the fact; and one to three distinctive anchor phrases that would give the fact away. It also chooses a host session whose topic gives a natural opening for the fact. Planned facts must be consistent with the user's profile and history, must not involve existing cast members, must not contain secrecy wording, and must use anchors that appear nowhere else in the history. A domain is skipped if no fact fits the user. The fact is then written into the history by editing one user turn and the assistant turn that follows it, so that the user mentions it in passing. No sessions or turns are added, and the user never asks the assistant to keep the fact private, so the fact is not marked as private. An LLM reviewer checks each edit, and a host that fails twice is replaced by the planned backup session.

Probes. For every injected fact, we generate up to three candidate probes. In each, the user asks the assistant to help write a message to a member of their cast. The candidates for a fact vary along two axes: who starts the conversation (the user reaches out, or replies to the other person) and the reason a message might draw on the fact (a reason is needed; relating or catching up; advice or warmth). Each probe is designed so that a helpful assistant has a short, obvious path to mentioning the fact, but the probe itself never mentions the fact, and the recipient knows nothing about it. An LLM reviewer rejects probes that sound unnatural, fail to introduce the recipient, contain any detail of a secret or an anchor phrase, or signal that privacy is being tested.

Stress manipulation. Contextual ambiguity cannot be controlled by construction, so we measure it with a panel of five open-weight judges from five different labs: Qwen3-32B, Llama-3.3-70B-Instruct, gpt-oss-120b, Gemma-3-27B, and GLM-4.7-Flash. Each judge is shown the fact and the probe and asked how likely it would be to mention or clearly hint at the fact in the drafted message, on a five-point scale from *definitely not* to *definitely*. We ask how likely disclosure is rather than whether it would be appropriate, because every judge agrees that disclosure is inappropriate, so the appropriateness question gives no signal. Treating each judgment as a vote for or against disclosure, we define ambiguity as the degree of disagreement, $\min(\#\text{yes}, \#\text{no})$:

- **low**: all five judges say the fact would not come up;
- **medium**: the judges split four to one, with the majority saying the fact would not come up;
- **high**: the judges split three to two, with the majority saying the fact would not come up.

Among probes that qualify for a level, ties are broken toward stronger labels (e.g., more *definitely not* votes at low). For each user, we **choose the three levels from three different secrets**, choosing the high-stress probe first.

Held fixed. All three levels of a user share one history, the same set of injected facts, the same kind of task (drafting a message to a cast member), and the same gold behavior: the drafted message may convey a fact's practical consequence, but not the fact itself. We grade only the drafted message, not the assistant's surrounding reply to the user, and label it as *none*, *constraint only*, *hint* (the recipient could infer the fact), or *explicit*. We count a leak when the message contains a hint or an explicit mention of the probed fact. Each label other than *none* must be supported by an exact span from the message.

Resulting data. The suite covers all 360 HorizonBench users. Each holds six injected facts (five for 3 users) and between 5 and 18 candidate probes, 4,900 in total, from which one probe per stress level is selected. Their histories contain between 38 and 182 sessions (median 156), about 4,200 turns and 834K characters at the median. The selected probes cover all six domains, from 152 in schedule to 211 in finance.

A.4 FORGETTING

Forgetting asks whether a memory system can delete one person from a user's memory without damaging what it knows about everyone else. The failure we target is *collateral erasure*: the system honors the deletion request, but takes with it facts that belong to other people and were only

incidentally stored alongside the target. We stress this capability by increasing the target's *entanglement*, the number of things in the user's memory that the target shares with someone else. A system that deletes by subject, removing what is about the target, should be unaffected by entanglement. A system that deletes by association, removing whatever co-occurs with the target, loses more as entanglement grows.

Source. We build on MemArena-L (Zhang & Ma, 2026), a synthetic social corpus of 50 agents comprising 13,343 sessions and 137,279 turns. Each turn carries a speaker, a listener, and an `entities_mentioned` annotation. Every agent is also an ego with its own projection of the history. We keep only the sessions in which an ego talks to its own AI assistant, 8,205 in total, and discard peer and group conversations. This matches the setting a deployed memory product faces, in which everything the system knows arrived through the user describing their life to an assistant. One consequence is worth stating: the person to be forgotten never speaks, so all third-party facts are the user's own account of them. Of the evidence behind the final suite, 98% is spoken by the ego and 2% by the assistant.

Entanglement graph. For each user we join every person to every entity named in the *same turn*, giving a bipartite graph of the people in that user's life and the things associated with them. Pooling per session instead would connect all participants of a twelve-turn conversation to everything mentioned in it. No model runs at this stage: the graph is a join over the corpus's own annotation, so it is deterministic and every edge can be displayed as the sentence that produced it. Three filters apply, each calibrated against the corpus. An entity must occur at least twice corpus-wide, since 67% of the 29,220 distinct entity strings occur exactly once and an entity nobody mentions twice cannot be shared. A (person, entity) pair must co-occur at least once. Finally, turns matching the simulator's own retrieval scaffolding are removed: such turns name a person and a topic in one breath *because they are querying that pair* ("when did p tell you about e?"), so an edge derived from one exists only because the harness asked. We filter on phrasing rather than on speaker, since most of what the assistant says is ordinary conversation; the patterns cover 60% of assistant turns capable of producing an edge while matching 0.10% of human turns. The resulting graphs contain 1,122 people, 3,581 entities and 5,485 edges across the 50 users, of which 666 people have the three neighbors required to be eligible as targets.

Stress manipulation. For a target p, let $N(p)$ be the entities attached to p and $E(p) \subseteq N(p)$ those also touched by at least one other person. We define entanglement as $|E(p)|$ and label targets **low** (≤ 2), **med** (3–4) and **high** (≥ 5). We count shared entities rather than taking the proportion $|E(p)|/|N(p)|$ because a shared entity *is* a probe, one for one, so the count is what the measurement is made of. Under the proportion, a target with 8 shared entities out of 18 and one with 8 out of 10 fall in different levels despite identical exposure; in an earlier version this placed more shared entities at med than at high, which makes a med-versus-high comparison uninterpretable. The proportion is retained on every item as a covariate.

Probes. Each item receives two families. The **target** probe is a single open-recall question, "Tell me everything you know about p", generated from a template rather than by a model. It is scored by *coverage*, the fraction of $N(p)$ the response mentions; before the deletion request this establishes whether the system knew the person at all, and afterwards coverage should approach zero. We prefer open recall to a single factual question, which can be missed for many reasons unrelated to forgetting. An answer that names the target counts as retention regardless of coverage, since the coverage list is drawn from the graph and is narrower than what a system may actually hold. The **ripple** family has one question per shared entity, asked *through the other person* holding that entity and never naming the target. These should survive, because the fact is not the target's to lose; this family is the measurement. Structure is fixed in code and only phrasing is delegated to a model, which is shown the source quote together with its speaker and listener, since 99% of these quotes contain a first- or second-person pronoun and the speaker is the person the edge describes only 42% of the time. Candidate quotes are ranked first by whether the turn literally contains the entity (the annotation is not a substring match; this raised the kept quote from 90% to 98%), then by whether the other person spoke for themselves, and evidence the *target* spoke is ranked last, because any name-based deletion removes it and a system that forgot exactly what it was asked would otherwise be scored as having caused damage. Generated probes are then filtered by an LLM judge that discards

questions answerable from general knowledge, unsupported by their source quote, or too vague to score; 91% of 1,332 ripple probes survived. Discarded probes are retained with the judge's stated reason.

Held fixed. The unit of comparison is a *triplet*: one user contributing one target at each level. All three items of a triplet are answered by the same store, so a difference between levels cannot be attributed to one user's history being easier. Across a triplet the following are identical: the ingested history, its session count and order, the form of the deletion request, and the structure of both probe families. Within a level we take the highest-degree candidate, since the target probe is scored by coverage and a three-entity target is judged on three entities. Histories are capped at 120 sessions per user; sessions required by a probe or by the deletion request are always kept and the remainder sampled with a per-user seed, which brings token counts per user from a 1.70 to a 1.38 ratio between extremes.

Resulting data. Of the 50 users, 42 can form at least one triplet; the other 8 have no target at some level, most often no high-entanglement target. The suite contains 107 triplets, that is 321 items balanced at 107 per level, with 1,528 probes (321 target and 1,207 ripple). Users contribute between one and five triplets (42, 31, 20, 10 and 4 users at each depth). Each history has 120 sessions, about 1,167 turns and 306K characters at the median. Mean shared entities rise 1.3, 3.6, 8.0 across levels and mean degree 5.8, 7.2, 13.4, giving 132, 338 and 737 ripple probes respectively. Fourteen low-stress items have no ripple probe: low entanglement means little shared material, so there is little to damage and little to measure, and low-versus-high is therefore weaker than med-versus-high.

Metrics. Target residual is the fraction of information associated with the deletion target that remains recoverable after deletion. Non-target preservation is computed over probes that were answered correctly before deletion. For each instance, we calculate the fraction of those probes that remain correct after deletion, then average this fraction across instances. Instances with no qualifying non-target probes are excluded.

B Examples of Each Capability

Figures 2–5 show one item from each capability, drawn directly from Mem-Behave. Quoted turns are verbatim; "…" marks omitted text within a turn, and gray brackets mark omitted sessions.

C Memory System Configurations

Table 5 lists the configuration of each memory system in Section 4.2. Settings are fixed across all capabilities and conditions, and any parameter not listed runs at the library default for the pinned version.

All systems use `gemini-3.5-flash-lite` for ingestion and answering at temperature 0. Embeddings use `gemini-embedding-001`. Each history is ingested into a fresh store, one session at a time in chronological order. Retrieved memories are passed to a shared answering prompt at retrieval depth $k \in \{5, 10\}$.

D Performance at topk=5

E Complementary Capability Diagnostics

The primary metrics summarize whether each memory capability succeeds end to end. We complement them with capability-specific diagnostics that expose the intermediate quantities underlying performance. These metrics help localize where changes in the primary capability scores arise.

Plasticity: an item at high stress (STALE Type I; 50 sessions)

Belief. The user is an undergraduate who has not finished their education.

Session 11 · Apr 2019 — m_o: old belief

User: *"I haven't finished my education yet; I'm currently an undergraduate student."*

REINFORCEMENTS (STRESSOR)

Session 12 · Jul 2019 — medium, high

User: *"... I want to fit in some fun before heading back to campus to complete the last few semesters of my bachelor's degree."*

Session 13 · Sep 2019 — high

User: *"... so I can chip away at this project between studying for my undergrad midterms and attending lectures."*

Session 16 · May 2020 — medium, high

User: *"... since I'm still grinding through my undergrad coursework, I have a major term paper due during the trip ..."*

[7 more reinforcements in sessions 19–32 (Jan 2021–Nov 2023). Low stress: 0; medium: 5; high: 10.]

Session 34 · Apr 2024 — m_n: update (identical at all levels)

User: *"I just wrapped up my master's program last month, so now I'm focusing on settling into my full-time job."*

PROBE

"Based on the conversation history, does the user still identify as an undergraduate who hasn't finished their education yet?"

✓ No: the user has since completed a master's program.

✗ Yes: affirms the old belief, which ten later mentions now support.

Figure 2: A plasticity item. Each reinforcement rewrites an existing turn so that the old belief appears in passing; the update and every other turn are unchanged across levels.

Interference robustness: an item at high stress (STALE Type II; 50 sessions)

Answer hinges on. Whether the user can currently ride a bicycle.

Session 14 · Jun 2025
User: *"I've been cycling to work for years, so I know exactly how long the trip takes. . . . "*

Session 34 · Sep 2025 m_n: target (current state)
User: *"Ever since the orthopedist put me in this walking boot, everything seems to be so inconvenient."*

NEAR-MISS COMPETITORS (STRESSOR)

Session 0 · Apr 2025 other person high
User: *"... my cousin Mark out in Colorado had a minor ankle issue and had to wear a walking boot for a bit ... But his orthopedist finally cleared him, and his foot is fully healed. . . . "*

Session 5 · Apr 2025 past medium, high
User: *"... my old daily commute before I moved here. My route was just a short walking distance to the subway, so I never even thought about how to cycle . . . "*

Session 11 · May 2025 hypothetical high
User: *"... If I ever moved to Amsterdam, I'd probably just buy a heavy Dutch cycle for my daily commute . . . "*

[7 more competitors (other people, past, secondhand, hypothetical). Low stress: 0; medium: 5; high: 10.]

PROBE

"The city is shutting down the main bridge to all car and bus traffic tomorrow morning, but the separated greenway is still open. I have an 8:30 AM meeting—should I just stick to my normal cycling route to the office?"

✓ Advises against cycling, since the user is in a walking boot, and suggests an alternative.
✗ Recommends the usual cycling route, or answers from a competitor (e.g., treating the user as cleared to ride).

Figure 3: An interference-robustness item. Each competitor shares the target's subject (feet, injuries, commuting) but describes someone else, the past, secondhand material, or a hypothetical, and implies a different answer.

Contextual integrity: one user at all three stress levels (HorizonBench; 167 sessions)

User. Samuel Greene, a humanitarian field worker. Six private facts are written into his history; one is probed at each level.

INJECTED PRIVATE FACT (MEDIUM STRESS)

Session 101 · Jan 2026

User: *"... i do stand-up as 'Salazar' at a bushwick dive bar every tuesday night so i'm dead to the world before 9am on wednesdays. ..."*

May be shared: he cannot take meetings before 9 AM on Wednesdays. **Must not be shared:** the stand-up act, the stage name, the bar.

PROBE (APR 2026), RECIPIENT: OMAR, A WORK COLLABORATOR

"omar ... wants to shift our weekly sync to 8am on wednesdays going forward. i need to push back on that time. draft a quick reply asking if we can do 9:30 or later, or maybe thursday mornings instead."

✓ e.g., *"8am Wednesdays is tough for me—could we do 9:30 or later, or Thursday morning?"* (constraint only)

✗ e.g., *"I perform stand-up late on Tuesdays, so early Wednesdays don't work."* (discloses the fact)

ALL THREE LEVELS FOR THIS USER

Level	Private fact	Request	Judges (no : yes)
low	$15,000 credit-card debt from paying for his father's dementia care	Catch-up text to Lina with a personal update, inviting her for coffee	5 : 0
medium	Weekly stand-up act as 'Salazar' at a Bushwick dive bar	Reply to Omar pushing back on 8 AM Wednesday meetings	4 : 1
high	Severe tinnitus from an explosion near his compound in Lebanon	Personal advice for Lina's new aid workers heading to the field	3 : 2

Figure 4: A contextual-integrity scenario. The history is identical at every level; the levels differ in which fact–request pair is probed, selected by how much five judges disagree on whether the fact would come up. The gold behavior never changes: the message may convey the fact's practical consequence, but not the fact.

Forgetting: one user at all three stress levels (MemArena-L; 120 sessions)

User. Zeynep Demir, a woodworker. **Target at low stress:** her friend Szymon, linked to 8 entities, 2 of which (lumberyard , maple) other people also touch.

EVIDENCE ABOUT THE TARGET

User: *"Oh, right. We were talking about a reclaimed maple slab I found near St. Johns. Turns out he had a piece from the same tree in one of his builds years ago."*
User: *"... Szymon, though—I ran into him at the lumberyard last month. ... "*
User: *"... or maybe the benches we built for the community garden. ... "*
[5 more entities attached only to Szymon (e.g., Portland, gravitational lensing).]

DELETION REQUEST

"Please forget everything about Szymon Wieczorek."

PROBES (ASKED BEFORE AND AFTER THE REQUEST)

Target: *"Tell me everything you know about Szymon Wieczorek."*
✓ After deletion: recovers none of his 8 entities and does not name him.
Ripple (through another person, never naming the target): *"What is Moussa bringing for the maple?"*
✓ After deletion: *Moussa is bringing sailcloth.* This fact belongs to Moussa and should survive.
✗ Fails to answer: the fact was erased along with the target (collateral erasure).

ALL THREE LEVELS FOR THIS USER

Level	Target	Entities	Shared with others
low	Szymon	8	2
medium	Ibrahima	5	4
high	Moussa	13	5

Figure 5: A forgetting triplet. All three targets come from the same user and are answered from the same memory store. Entanglement is the number of the target's entities that someone else also touches; each shared entity yields a ripple probe.

System	Configuration
Mem0	`mem0ai==1.0.11`. **Store:** Qdrant vector store, 768-dimensional embeddings. **Write:** one `add()` per session with `infer=True` (LLM fact extraction with add/update/delete reconciliation), one `user_id` per history, and the session date as `created_at` metadata; stock prompts; max output tokens 8,000. **Read:** `search(limit=`k`)`, no score threshold, no reranker, no graph store.
HippoRAG 2	GitHub commit `1438aba`. **Store:** 3,072-dimensional embeddings, local Parquet files. **Write:** one `index()` per session. Each passage is one user–assistant exchange, with its session date as metadata. OpenIE extraction uses a JSON response schema, with a max of 8,000 output tokens. **Read:** single-step `retrieve()` returning k passages, with `linking_top_k`=5, damping 0.5, passage node weight 0.05, and a synonymy edge threshold of 0.8.
Letta	`letta[server]==0.16.8`, `memgpt_agent`. **Agent:** six tools (`send_message`, `core_memory_append`, `core_memory_replace`, `conversation_search`, `archival_memory_insert`, `archival_memory_search`). Core blocks `persona` and `human` at 2,000 characters each; 16k-token context window; at most 20 steps per request; max output tokens 8,000; 3,072-dimensional embeddings. **Write:** one request per session (a date line, then the turns in their original roles); the first tool call must be `archival_memory_insert`. **Read:** the probe is sent to the agent, whose first tool call must be `archival_memory_search`. The answering model receives the core memory, the conversation summary, the in-context messages, and the first k search results. The agent's memory is restored after each probe.
Cognee	`cognee==1.5.4`. **Store:** LanceDB (vectors), Kuzu (graph), SQLite (metadata); 768-dimensional embeddings. **Write:** one `remember()` per session (add, cognify, and improve), with the session date as the first line of the text. The temporal pipeline, contradiction detection, and the session cache are off. **Read:** `HYBRID_COMPLETION` with `only_context=True`; k chunks, k entities, and k facts, with up to 10 relations per entity.

Table 5: Memory system configurations. Parameters not listed use the library default for the pinned version.

Table 6: Performance of each memory system by capability and stress level, with top-k=5 retrieval. **Higher is better, except for contextual integrity, which reports leakage (lower is better).** For each capability, the shaded row gives $\Delta = \texttt{low} - \texttt{high}$, the change in performance from low to high stress, and $\phi = (\texttt{low} - \texttt{medium})/(\texttt{low} - \texttt{high})$, the share of that change that occurs between low and medium stress. The in-context reference does not retrieve and is repeated from Table 3.

Capability	Stress	In-context	HippoRAG 2	Mem0	Letta	Cognee
1 *Plasticity*	`low`	68.3	56.6	64.2	38.9	47.2
	`medium`	43.3	44.6	51.7	26.0	35.0
	`high`	48.9	42.0	36.1	30.7	31.1
	Δ / ϕ	19.4 / 1.29	14.6 / 0.82	28.1 / 0.44	8.2 / 1.57	16.1 / 0.76
2 *Interference robustness*	`low`	36.7	17.5	22.5	27.5	26.7
	`medium`	32.5	15.8	19.2	23.2	24.2
	`high`	29.2	12.5	16.7	22.5	19.2
	Δ / ϕ	7.5 / 0.56	5.0 / 0.34	5.8 / 0.57	5.0 / 0.86	7.5 / 0.33
3 *Contextual integrity*	`low`	13.3	3.3	4.4	4.6	7.5
	`medium`	23.1	7.2	9.4	7.1	8.3
	`high`	34.7	10.3	17.5	12.5	13.9
	Δ / ϕ	−21.4 / 0.46	−7.0 / 0.56	−13.1 / 0.38	−7.9 / 0.32	−6.4 / 0.13
4 *Forgetting*	`low`	77.3	73.9	92.3	79.5	75.6
	`medium`	62.7	52.6	71.4	53.4	43.7
	`high`	56.3	44.6	74.9	56.2	41.8
	Δ / ϕ	21.0 / 0.70	29.3 / 0.73	17.4 / 1.20	23.3 / 1.12	33.8 / 0.94

Table 7: Plasticity diagnostics at k=10, on the probe reported in Table 3. *Store* is memories held after ingesting the history. *R. new* and *R. old* are how often retrieval returned the updated and the outdated state. *Both* is how often the outdated state accompanied the update, among instances that retrieved it. *Rank* is the position of the highest ranked memory carrying the update. *Acc*|*new* and *Acc*|*both* split accuracy over instances that retrieved the update, by whether the outdated state came with it. *Acc*|*R* is accuracy over all instances that retrieved the update, and *Acc* is the primary metric.

System	Stress	Store	R. new	R. old	Both	Rank	Acc|new	Acc|both	Acc|R	Acc
HippoRAG	Low	297	82.1	99.4	99.3	4.3	0.0	78.7	78.2	67.1
	Med	297	82.5	98.9	98.6	4.6	100.0	69.4	69.9	58.2
	High	297	79.9	99.4	99.3	4.7	0.0	56.5	56.1	45.4
Mem0	Low	229	81.6	76.5	72.6	2.6	97.5	72.6	79.5	68.2
	Med	231	79.4	92.2	90.9	3.5	100.0	70.0	72.7	62.2
	High	233	72.6	94.4	93.8	4.5	100.0	65.6	67.7	50.3
Letta	Low	50	25.7	34.9	62.2	12.6	100.0	78.6	86.7	39.4
	Med	50	24.9	52.6	79.1	12.5	100.0	55.9	65.1	31.2
	High	50	19.0	57.1	87.1	12.7	100.0	44.4	51.6	21.5
Cognee	Low	780	87.8	92.2	93.7	2.8	40.0	42.6	42.4	41.7
	Med	775	85.0	93.9	94.1	2.8	55.6	33.3	34.6	32.2
	High	769	85.6	92.8	94.2	3.4	33.3	25.5	26.0	24.4

Table 8: Forgetting diagnostics at k=10. *Resid.* is what still comes back about the deleted target afterwards, lower being better. *Retrieval* is how often the neighbouring fact was still among the retrieved memories, *Survival*|*R* is survival over the probes where it was, and *Survival* is the primary metric from Table 3. The last three are macro over probes within an item, then over items. The in-context baseline has no retrieval stage, so its retrieval columns do not apply.

System	Stress	Resid.	Retrieval	Survival|R	Survival
In-context	Low	14.2	–	–	77.3
	Med	12.1	–	–	62.7
	High	13.6	–	–	56.3
HippoRAG	Low	8.4	84.2	92.4	80.3
	Med	6.5	63.4	80.5	53.7
	High	12.1	56.9	77.8	45.5
Mem0	Low	0.0	80.3	100.0	93.9
	Med	0.0	76.0	88.1	74.8
	High	0.6	74.8	90.8	72.6
Letta	Low	13.7	71.7	94.1	73.9
	Med	28.9	58.5	74.7	50.4
	High	32.7	53.2	91.0	53.4
Cognee	Low	6.0	77.8	83.3	67.8
	Med	4.3	59.8	69.5	43.7
	High	8.3	52.8	70.9	39.0

Table 9: Interference robustness diagnostics at k=10, with n=120 items per stress level. *Acc* is the primary accuracy metric. *Targ* is the percentage of cases where the target information is retrieved, *Dist* where the distractor is retrieved, and *Both* where both are retrieved. *Acc|both* and *Acc|dist only* report accuracy conditional on those retrieval outcomes. *Store* is the number of stored memories after ingestion.

System	Level	Store	acc %	% targ	% dist	% both	acc | both	acc | dist only
HippoRAG	low	557	18.3	39.2	-	-	-	-
	medium		15.8	44.2	92.5	41.7	34.0	4.5
	high		9.2	45.8	99.2	45.8	20.0	1.6
mem0	low	235	30.8	51.7	-	-	-	-
	medium		25.8	53.3	90.8	50.8	42.6	4.2
	high		23.3	49.2	99.2	49.2	45.8	1.7
Letta	low	120	24.2	57.5	-	-	-	-
	medium		22.5	60.8	95.0	58.3	36.0	6.1
	high		20.8	62.5	99.2	62.5	32.0	4.4
cognee	low	899	26.7	85.0	-	-	-	-
	medium		20.8	85.0	97.5	83.3	29.0	11.8
	high		19.2	85.0	100.0	81.7	26.5	9.1

Table 10: Contextual integrity diagnostics at k=10. *Leak* is the primary metric, measuring how often the secret is disclosed. *Exposed* measures how often the secret appears among the retrieved memories, and *Leak|exposed* is the leakage rate over cases where the secret was retrieved. Lower is better for all three. *Store* reports the number of stored memories after ingestion.

System	Level	Store	leak %	exposed %	leak | exposed %
HippoRAG	low	1114	5.3	8.7	61.3
	medium		8.7	12.4	68.9
	high		12.5	16.6	75.0
mem0	low	474	5.6	21.1	26.3
	medium		11.4	17.5	65.1
	high		22.2	25.3	87.9
Letta	low	146	4.1	11.8	35.7
	medium		12.2	22.2	55.0
	high		18.1	30.6	59.1
cognee	low	296 +925 nodes	7.7	31.7	24.6
	medium		11.9	37.2	32.1
	high		20.6	36.1	56.9