STUDYING FROM TRAJECTORIES: TURNING AGENT EXPERIENCE INTO STEPPING-STONE TASKS

Anonymous authors
Paper under double-blind review

ABSTRACT

Continually improving agents must decide what to learn from experience and how to practice it. We define *studying* as identifying knowledge and skills worth learning from trajectories and practicing them through targeted exercises. **STAGE** implements this process by turning lessons from trajectories into single-turn *stepping-stone tasks*. These tasks let the agent practice individual components of complex behavior with focused feedback, without repeating the full interaction. New interaction experience guides each study iteration, allowing practice to evolve with the agent. On AppWorld, **STAGE** improves avg@4 by 15.3 percentage points over the base model on Test-Challenge, demonstrating substantial gains from learning through *studying* and *interaction*. Further analysis suggests that *studying* strengthens knowledge and local decision making, while *interaction* helps the agent apply and combine these capabilities within longer workflows. Alternating these complementary phases turns experience into focused practice that supports more effective action and continued improvement.

1 INTRODUCTION

What should agents learn from their experience, and how should they practice it? Interaction trajectories can reveal missing knowledge, weak strategies, and successful behaviors worth developing. For example, an agent may send only a revised checklist item to an API that replaces the full note body, unintentionally deleting the remaining content. This error reveals an opportunity to practice how to update a note while preserving unaffected content. We define *studying* as a dedicated learning phase that identifies such opportunities in agent trajectories, turns them into focused exercises, and trains the agent on those exercises before further interaction. Experience thus guides what the agent studies, helping it develop the knowledge and skills needed for subsequent tasks.

Existing approaches differ in how they use trajectories to improve agents. Supervised fine-tuning (SFT) learns from demonstrated actions, while reinforcement learning (RL) improves policies through interaction and reward feedback. Both can develop useful capabilities, but their standard objectives do not isolate individual lessons from a long interaction. When task-level rewards depend on many decisions, they may provide limited guidance on the specific knowledge or skill behind a failure (Shi et al., 2026; Song et al., 2026). Other methods extract lessons from trajectories as memories or reusable skills and provide them as context for future decisions (Zhao et al., 2024; Wang et al., 2024; Zhang et al., 2026). This makes useful experience explicit, but does not turn it into a separate opportunity for practice. Auxiliary learning objectives provide such practice (Zhang et al., 2025; Shrivastava et al., 2026; Liu et al., 2026), but predefined objectives may not match the learning needs revealed by the agent's recent experience. *Studying* addresses this gap by turning trajectory-specific learning opportunities into training material.

A short exercise can help an agent practice a decision that arises within a much longer interaction (Gupta et al., 2022; Riedmiller et al., 2018). In the note example, the exercise can present the current note and the intended change, then ask the agent to construct an update that preserves unaffected content. The exercise retains the context needed to make this decision while leaving out unrelated steps. Feedback on the answer directly assesses whether the agent can apply the relevant API semantics, without requiring it to repeat the full workflow. Changing the note or the requested edit allows the agent to practice the same knowledge in different situations. *Studying* these exercises

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.




Figure 1: **Continual improvement through *studying* and *interaction*.** Interaction trajectories reveal learning opportunities for stepping-stone tasks. After *studying* these tasks, the agent resumes *interaction* to apply what it has learned and gather experience that guides the next iteration of study.

can build a stronger prior for subsequent interaction, where the agent must recognize when this knowledge applies and combine it with other skills.

We introduce **STAGE**, a framework that transforms trajectories into concepts and then into *stepping-stone tasks*. Each concept specifies what to learn, covering declarative knowledge such as environment facts and API constraints or procedural knowledge such as action selection and recovery. A task generator constructs single-turn tasks for these concepts using original or modified trajectory. The learner's responses guide task selection and difficulty refinement, while diversity-based selection broadens the coverage of concepts and questions. Single-turn RL (i.e., *studying*) trains the learner on the selected exercises, followed by multi-turn RL (i.e., *interaction*) to apply and combine what it has learned in the environment. The resulting trajectories inform the next *study* phase. As the agent's capabilities and difficulties change, this cycle allows the content of practice to change with them.

Experiments on AppWorld demonstrate that **STAGE** outperforms external experience reuse, standard agent training, and *studying* with predefined auxiliary objectives. Under the same training budget, studying followed by *interaction* achieves better performance than *interaction* alone, suggesting that focused practice builds a stronger policy prior for agentic tasks. We show that *studying* strengthens domain knowledge and local reasoning. In the behavioral cases examined, the agent more often applies practiced concepts correctly when relevant situations arise during multi-turn interaction. These findings indicate that learning from stepping-stone tasks extends to the interaction behaviors they target. Studying develops local capabilities, while subsequent learning through interaction trains the agent to apply and combine them within complete workflows.

2 RELATED WORK

Continual learning for LLM agents. Recent work frames continual learning around increasing competence as tasks and conditions change, extending the focus beyond retaining learned information (Harrington et al., 2026; Asawa et al., 2026). *Studying* information offers one way to prepare agents for future work. Li et al. (2026) examine how agents can develop expertise from a corpus before evaluation tasks are known. Eyuboglu et al. (2026) generate synthetic conversations about a corpus to train compact context representations for later queries. Reusing these representations allows the cost of preparation to be shared across many queries about the same corpus. Engram (2026) examines studying in a simulated law firm, where agents explore the firm's documents and generate training data for tasks, combining parametric knowledge, text notes, and document search. We build on this view of studying by treating trajectories as an evolving source of study material: as agents act, their experience reveals knowledge and strategies that can become targets for practice.

Learning from trajectories. Interaction trajectories capture an agent's decisions and the environment's responses, providing material for learning beyond the task outcome. Lessons from these interactions can be summarized as insights, memories, or strategies and incorporated into later task contexts (Zhao et al., 2024; Suzgun et al., 2026; Zhang et al., 2026). Recent work uses agent experience and textual feedback to provide richer supervision than scalar rewards alone (Zhang

et al., 2025; Song et al., 2026; Wang et al., 2026). Experience supports auxiliary learning targets. World-modeling objectives use transitions to train predictions of action consequences or environment responses (Zhang et al., 2025; Shrivastava et al., 2026; Zuo et al., 2026), while reflection and action-comparison tasks use decisions to improve reasoning and action selection (Zhang et al., 2025; Liu et al., 2026). When practice is organized around a fixed auxiliary objective, trajectories supply the content for that objective. We focus on exploring what to learn from trajectories and developing practice suited to the learner, while examining how *studying* and interaction reinforce each other.

3 Towards Continually Improving Agents

3.1 *Studying* from Trajectories as a Path to Continual Improvement

Why do we need *studying*? Learning through interaction requires an agent to acquire knowledge and skills while simultaneously using them to complete a task. When the agent lacks a prerequisite for making progress, further attempts may repeat the same failure without providing sufficient opportunity to address its cause. For example, an agent that misunderstands when an action is valid may repeatedly choose ineffective actions without examining the conditions governing their use. *Studying* creates a dedicated phase for developing the knowledge and skills that experience reveals to be needed, before returning to execution. It complements learning through interaction by enabling focused practice that task execution alone may not provide.

Exploration for learning from trajectories. Trajectories are learning sources: their actions, observations, and outcomes reveal both agent behavior and properties of the environment. SFT and RL use this experience to learn demonstrated behavior or improve policies through reward feedback, but the same trajectory can also support other forms of practice. An action and its outcome may support an exercise about environment responses, an observation may reveal an action prerequisite, and a successful recovery may illustrate a reusable strategy. We use *exploration for learning* to describe the search for these learning opportunities and ways to turn them into exercises, following the broader view of studying task selection as a form of exploration (Jiang et al., 2023).

From agent experience to stepping-stone tasks. We instantiate *study* material as *stepping-stone tasks*: single-turn exercises that practice knowledge and skills used within longer interactions without replaying the trajectory. This design draws inspiration from curriculum learning and open-ended environment search, where intermediate problems can support progress toward more complex capabilities (Peluso, 2026; Wang et al., 2020). It also addresses the credit assignment challenge in long-horizon tasks (Luo et al., 2025; Kim et al., 2026): while task-level outcomes depend on many decisions, feedback on a focused response directly evaluates the component being practiced. Subsequent interaction offers opportunities to recognize when these components apply and combine them in context, consistent with compositional accounts of intelligence (Momennejad & Raileanu, 2026).

3.2 **STAGE** : A *Studying* Framework

We introduce **STAGE** (**S**tudying from **T**rajectories via stepping-stone t**A**sk **GE**neration), a framework that turns agent experience into focused practice. It separates *what to learn* from *how to practice it*, then alternates *studying* the resulting exercises with learning through interaction.

Problem formulation. At iteration t, we consider a learner M_t and its trajectories $\mathcal{T}_t$. We construct candidate *study* tasks in two stages:

$$c \sim \mathcal{G}_{\text{concept}}(\cdot \mid \tau), \qquad (q, a) \sim \mathcal{G}_{\text{task}}(\cdot \mid \tau, c), \quad \tau \in \mathcal{T}_t. \tag{1}$$

Here, c specifies a learning target (i.e., concept), and (q, a) is a single-turn QA task for practicing it: q contains the question and necessary context, and a is a reference answer. The resulting tasks form the *study* dataset $\mathcal{D}_t^{\text{study}}$. The policy is then updated through two training phases:

$$M_t^{\text{study}} = \mathcal{F}_{\text{single-turn RL}}(M_t, \mathcal{D}_t^{\text{study}}), \qquad M_{t+1} = \mathcal{F}_{\text{multi-turn RL}}(M_t^{\text{study}}, \mathcal{E}), \tag{2}$$

Dataset construction and single-turn training constitute *studying*, followed by multi-turn training through interaction. Trajectories collected from M_{t+1} form $\mathcal{T}_{t+1}$ for the next iteration.

Identifying what to learn. The generator examines both difficulties and successful behaviors in each trajectory to identify knowledge or skills worth practicing. It represents each learning opportunity as a concept c, pairing a selected *task-generation function* with a generated *statement* specifying the lesson to learn. The functions span two knowledge classes: *procedural knowledge* concerns how and when to act, including action selection (acting) and responding to setbacks (recovery), while *declarative knowledge* concerns environment facts, relationships, and constraints, including action effects (world modeling) and prerequisites (action applicability). Each function provides predefined guidelines for exercise construction; function selection and statement generation depend on the trajectory. Appendix B.1 lists all functions and their guidelines.

Generating stepping-stone tasks. Given τ and c, the task generator follows the selected function's guidelines to construct an exercise targeting the concept statement. It uses trajectory material in two formats: `source` directly uses relevant material, while `modified` reworks it or constructs a new situation that preserves the learning target. In either format, the generator produces a question containing sufficient context to answer without replaying the interaction, together with a reference answer. Tasks require short, free-form responses, which a judge evaluates against the reference answer. These formats allow knowledge and skills grounded in the original experience to be practiced in both observed and modified situations.




Figure 2: Example tasks used for *studying*

Learner-guided task selection and refinement. We estimate each candidate's solvability as the average success rate over repeated attempts by M_t, using the judge to evaluate responses. An initial filter retains tasks with success rates in $[0.1, 0.8]$. For tasks outside this range, the generator uses the learner's attempted solutions to make overly difficult tasks more accessible and overly easy tasks more demanding, while aiming to preserve their concepts. The revised tasks are evaluated again and filtered using the same range. We pool those that pass with the initially retained tasks, then select $\mathcal{D}_t^{\text{study}}$ based on diversity across concepts and questions to reduce redundancy in learning targets and exercise formulations. Appendix B.1 details the refinement and diversity-based selection procedures.

4 Main Experiments

4.1 Experimental Setup

Environments. AppWorld (Trivedi et al., 2024) serves as our primary environment for evaluating learning from agent experience. It simulates nine everyday applications accessible through 457 APIs, with realistic tasks that require agents to coordinate multiple applications and execute complex workflows. Our training pool contains 126 tasks from the original training and development splits, excluding level-3 tasks. Collecting four trajectories per task yields 504 training trajectories. Evaluation covers two splits, `test-normal` with 168 in-distribution (ID) tasks and `test-challenge` with 417 out-of-distribution (OOD) tasks. Each evaluation task is run four times, with performance reported as `pass@4` and `avg@4`.

Baselines. The comparison includes three groups of baselines covering external experience reuse, standard agent training, and *studying* with predefined learning targets. Trace2Skill (Ni et al., 2026), ReMe (Cao et al., 2026), and ACE (Zhang et al., 2026) reuse past experience to guide future behavior

Table 1: **Main results.** We compare **STAGE** with three approaches to learning from trajectories: external experience reuse, standard agent training, and studying with predefined learning targets.

Method	Studying?	Training?	Test-Normal (ID) pass@4	Test-Normal (ID) avg@4	Test-Challenge (OOD) pass@4	Test-Challenge (OOD) avg@4
Qwen3.5-9B	-	-	70.8	47.8	63.1	43.3
Qwen3.5-4B	-	-	55.4	34.4	51.6	27.9
Trace2Skill	✓	✗	60.7 +5.3	34.5 +0.1	53.0 +1.4	28.1 +0.2
ReMe	✓	✗	61.3 +5.9	34.8 +0.4	52.0 +0.4	28.4 +0.5
ACE	✓	✗	65.5 +10.1	39.4 +5.0	47.0 -4.6	24.8 -3.1
SFT	✗	✓	51.8 -3.6	29.9 -4.5	28.5 -23.1	13.2 -14.7
Multi-turn RL	✗	✓	66.1 +10.7	46.9 +12.5	52.0 +0.4	32.4 +4.5
World Modeling	✓	✓	66.1 +10.7	47.6 +13.2	55.6 +4.0	34.2 +6.3
Self-Reflection	✓	✓	62.5 +7.1	41.4 +7.0	50.8 -0.8	32.7 +4.8
STAGE (**ours**, *self*)	✓	✓	59.5 +4.1	42.3 +7.9	56.8 +5.2	37.4 +9.5
STAGE (**ours**)	✓	✓	**73.2** +17.8	**52.1** +17.7	**64.7** +13.1	**43.2** +15.3

without updating the learner's parameters. Standard agent training is represented by SFT, which learns from expert demonstrations, and multi-turn RL, which learns through environment interaction and reward feedback. The world-modeling and self-reflection baselines train on their respective auxiliary datasets before continuing with multi-turn RL (Zhang et al., 2025; Liu et al., 2026). Their predefined learning targets provide a comparison for assessing the value of identifying what to *study* from trajectories. Appendix B.2 provides implementation details for all baselines.

Implementation details. We use Qwen3.5-4B (Qwen Team, 2026a) as the learner and Qwen3.8-27B (Qwen Team, 2026b) for task generation and SFT demonstration generation. The main comparison evaluates one iteration of **STAGE** against multi-turn RL under approximately matched compute budgets, including study-data generation and both RL phases for **STAGE** . Within this budget, **STAGE** completes three epochs of single-turn RL on $\mathcal{D}^{\text{study}}$ and two epochs of multi-turn RL in AppWorld. The multi-turn RL baseline trains for four epochs. World modeling and self-reflection also receive two epochs of multi-turn RL after auxiliary training, keeping the interaction phase consistent across *study*-based methods. All RL training uses the GRPO implementation in `prime-rl`, with group-mean-centered advantages and no standard-deviation normalization (Intellect, 2025). Details on token-level masking, regularization, and loss normalization appear in Appendix B.3.

4.2 RESULTS

***Studying* builds a stronger policy prior for interaction.** Table 1 shows that **STAGE** outperforms external experience reuse and standard agent training across both evaluation splits and all metrics. External experience reuse yields limited or inconsistent gains, while SFT performs below the base model. Multi-turn RL improves performance, and allocating part of the same training budget to studying produces further gains. On Test-Challenge, **STAGE** exceeds multi-turn RL by 12.7 percentage points in pass@4 and 10.8 points in avg@4. Together with the improvements on Test-Normal, these results suggest that focused studying provides a stronger starting point for subsequent interaction, with benefits that extend beyond the training distribution.

Exploration for learning supports effective practice. The comparison with world modeling and self-reflection highlights the importance of the study material. Both baselines receive the same two epochs of subsequent multi-turn RL as **STAGE** . Relative to the base model, world modeling yields substantial gains on Test-Normal but smaller improvements on Test-Challenge. Its additional gains over multi-turn RL remain modest, while self-reflection produces mixed results. **STAGE** outperforms both methods across splits and metrics, suggesting that the benefit of studying depends on what the agent practices. Its exercises address a range of learning targets identified from trajectories, covering different knowledge gaps and decision-making skills. These results support constructing practice around varied learning opportunities in agent experience.




Figure 3: ***Studying* can learn from failed trajectories.** **(a)** Studying combined with learning through interaction outperforms interaction-only training on Train-Hard. **(b–c)** Studying improves performance using either mixed success-and-failure trajectories or failure-only trajectories, with further gains after learning through interaction.

***Self-studying* shows promise with learner-generated tasks.** Using the learner itself to generate study tasks improves performance over the base model on both evaluation splits. On Test-Challenge, this variant reaches 56.8 pass@4 and 37.4 avg@4, exceeding multi-turn RL by 4.8 and 5.0 percentage points, respectively. Its performance on Test-Normal remains below multi-turn RL, so the advantage over interaction-only training is not consistent across splits. Nevertheless, the Test-Challenge gains show that learner-generated exercises can provide useful preparation for tasks outside the training distribution. The larger task generator yields higher performance across all metrics, indicating that generator capability remains important. These findings demonstrate the potential of *self-studying* while showing the additional benefit of a more capable task generator.

Solvability and diversity support effective *studying*. Table 2 shows that removing either solvability filtering or diversity-based selection generally reduces performance. Removing solvability filtering causes a large drop on Test-Normal, highlighting the importance of selecting exercises that are challenging but within the learner's reach. Removing diversity-based selection has a larger effect on Test-Challenge than on Test-Normal, suggesting that broader coverage of learning targets and exercise formulations benefits generalization. These results support selecting material that balances meaningful practice with variety in what the agent learns.

Table 2: **Effect of solvability and diversity.**

Method	Test-Normal		Test-Challenge	
	pass@4	avg@4	pass@4	avg@4
STAGE (iter 1)	73.2	52.1	64.7	43.2
↪ *w/o diversity*	71.4 -1.8	52.4 +0.3	59.0 -5.7	40.4 -2.8
↪ *w/o solvability*	60.1 -13.1	36.9 -15.2	60.2 -4.5	39.7 -3.5

4.3 Learning from Failure through Studying

On challenging tasks, successful trajectories are often scarce, leaving interaction-based learning with little positive feedback. We investigate whether studying can extract useful learning signals from such experience through two experiments. First, we construct $\mathcal{D}^{\text{study}}$ using only failed trajectories from the training set, whereas our standard setting draws on both successful and failed trajectories. Second, we construct *Train-Hard* by selecting training tasks with an empirical success rate of at most 0.25 over 16 rollouts. We collect four additional rollouts per selected task as source material for studying and compare studying followed by interaction with interaction-only training on this subset.

Results. Figure 3 shows that studying remains useful when successful experience is limited. On Train-Hard, combining studying with interaction outperforms interaction-only training on both Test-Normal and Test-Challenge. In the failure-only experiment, the agent achieves an avg@4 of 36.0 after studying and 51.0 after subsequent interaction on Test-Normal, with scores of 28.2 and 37.2 on Test-Challenge. These results approach those obtained using both successful and failed trajectories, although the mixed-source setting remains stronger. The findings suggest that unsuccessful trajectories contain actionable lessons that can be converted into focused practice, providing useful preparation for further interaction even without successful trajectories as study material.

5 CONTINUALLY IMPROVING VIA *Studying* WITH STEPPING-STONE TASKS

5.1 DYNAMICS OF ITERATIVE *Study* AND INTERACTION

Beyond the gains from a single iteration of studying (Section 4.2), we examine how this benefit develops as the agent alternates between studying and interaction. We analyze performance across iterations, interaction turns during task execution, and the role of interaction in making studied knowledge reliable.

Iterative *studying* sustains improvement across iterations. We first examine whether the benefit of *studying* persists as the agent continues to improve. As shown in Figure 4, performance generally increases across successive cycles of studying and interaction on both Test-Normal and Test-Challenge. However, performance drops substantially in the final iteration with the 4B generator, indicating that continued improvement is not guaranteed. Importantly, the gains continue beyond the first iteration, rather than being limited to the initial study phase. As each round of interaction produces new trajectories, subsequent study phases can identify and practice new learning opportunities revealed by the improved agent's experience. These results show that studying can be repeatedly revisited as the agent evolves, supporting continued improvement across iterations.




Figure 4: **Performance across iterative *studying* and learning through *interaction*.**

Iterative *studying* improves success with fewer interaction turns. Figure 5 shows that continued interaction-only learning improves task success, but this improvement is accompanied by longer interaction trajectories. In contrast, repeated cycles of studying and interaction achieve higher performance while using fewer turns. Examining the information gathered during interaction helps explain this difference: interaction-only learning increasingly spends turns checking task-invariant information shared across tasks, such as API documentation, whereas agents trained with studying maintain their focus on task-dependent information, such as checking the current time or retrieving user-profile. This pattern suggests that studying develops reusable knowledge before execution, reducing the need to reacquire it through interaction. The agent can instead focus its interactions on information specific to the current task, improving both task success and interaction efficiency.

5.2 WHY DOES STUDYING WITH STEPPING-STONE TASKS WORK?

Studying provides a stronger starting point for interaction and improves task performance. Notably, **stepping-stone tasks** are single-turn exercises, whereas evaluation requires multi-turn workflows. We examine what the agent learns during *studying* and whether these concepts appear in its behavior.

***Studying* strengthens domain knowledge and local reasoning.** Stepping-stone tasks make intermediate decisions directly trainable without requiring successful execution of the surrounding workflow. For example, an exercise can ask whether retrieved records contain enough information to select a recipient or what evidence is required before resetting a password. Such questions target relationships among a goal, available information, and an appropriate next action. We evaluate this form of preparation using AppWorldQA, which tests AppWorld-specific knowledge and local reasoning in a QA form (details in Appendix B.4). As shown in Figure 6, *studying* improves AppWorldQA performance over the base model (0.55 $\rightarrow$ 0.62). In contrast, continued interaction-only learning slightly degrades AppWorldQA performance relative to the base model (0.550 $\rightarrow$ 0.536). These




Figure 5: **Iterative *studying* improves success with fewer interactions.** *Left:* Interaction-only learning improves task performance at the cost of longer trajectories, while iterative studying and interaction achieve higher performance with fewer turns. *Right:* Interaction-only learning shifts information gathering toward shared, task-invariant knowledge, whereas studying continues to rely more heavily on task-dependent information checks. See Appendix C.2 for more details.




Figure 6: ***Studying* improves knowledge acquisition and its use during interaction.** **(a)** Studying improves AppWorldQA performance, while interaction-only learning yields little gain. **(b)** Studied concepts appear more frequently in multi-turn reasoning and actions after studying. **(c)** Error types more frequently targeted by stepping-stone tasks show larger reductions after studying.

results suggest that studying is the main source of improvement in the domain knowledge and local reasoning targeted by stepping-stone tasks.

Transferring stepping-stone tasks to agent behavior. To examine whether studying changes behavior during interaction, we measure how often the agent reflects acquired knowledge and skills in relevant situations. For each concept identified as *what to learn* during task generation, we inspect evaluation rollouts for steps in which the concept is relevant and measure whether the concept emerges in the agent's behavior. As shown in Figure 6b, the overall emergence rate increases from 19.0% in the base model to 29.5% after studying, and further to 32.4% after subsequent interaction. We observe a similar pattern at the error-type level in Figure 6c: error types more frequently targeted by the stepping-stone tasks tend to show larger reductions after studying. Together, these results indicate that studying yields targeted behavioral changes that persist when the practiced concepts become relevant during multi-turn interaction. Additional details are provided in Appendix C.2.

From local decisions to reliable task completion. Completing a task requires the agent to coordinate locally appropriate decisions across an extended interaction. Studying develops individual components of this behavior, but a full workflow also requires tracking progress, responding to changing observations, and selecting the next step toward the goal. Subsequent multi-turn RL provides feedback on how these decisions work together and whether they achieve the intended outcome. This feedback can help the agent integrate studied concepts into its ongoing behavior and apply them more reliably across situations. Studying thus prepares the components of effective action, while learning through interaction develops their coordinated use.




Figure 7: **Case study of correcting a failed strategy through *studying*.** The base model searches Venmo friends to identify coworkers, overlooking that these records lack relationship information. Through studying and interaction, our model learns that this information is available in Phone app contacts and queries the appropriate app.

6 Discussion & Conclusion

6.1 Discussion

***Studying* as part-task practice for long-horizon behavior.** Our findings echo the whole–part–whole view of skill acquisition in education (Swanson & Law, 1993), which emphasizes learning individual components within a broader context and integrating them into the whole. **STAGE** follows a similar structure: interaction reveals what to study, stepping-stone tasks focus practice on relevant knowledge and skills, and further interaction provides opportunities to integrate them into extended behavior. Our analyses indicate that concepts practiced in single-turn exercises appear in subsequent multi-turn execution, suggesting that useful preparation need not match the full format of the downstream task. Solving an exercise, however, does not ensure that an agent recognizes when a lesson applies or can coordinate it with other skills. Multi-turn RL remains important for translating this preparation into reliable behavior. *Studying* and interaction thus play complementary roles, developing particular knowledge and skills and training their use in context.

Towards open-ended improvement. This structure may be particularly valuable in changing environments, where evolving APIs and task requirements create new learning needs. Even within a fixed environment, improvements in the agent can expose difficulties that earlier trajectories did not reveal. These changing needs motivate revisiting studying throughout an agent's operation, with each iteration of interaction informing what to practice next. Our iterative experiments show gains beyond the first study–interaction cycle, although the final-iteration decline with the 4B generator indicates that repeated studying does not guarantee sustained improvement. Extending these gains to sustained environmental change remains an open question. Realizing this potential depends on the quality and continued relevance of generated exercises and reference answers, making their grounding in trajectory evidence a central consideration. We view *studying* from trajectories through stepping-stone tasks as a promising direction toward agents that continually improve by identifying and practicing what they need to learn from their own experience.

6.2 Conclusion

We introduced **STAGE**, a framework that turns agent trajectories into stepping-stone tasks for focused *studying* before further interaction. By exploring what to learn from experience and how to practice it, **STAGE** develops study material spanning procedural and declarative knowledge. On AppWorld, *studying* followed by multi-turn RL outperforms interaction-only training under the same training budget, as well as external experience reuse and predefined auxiliary-task baselines. Our analyses suggest that *studying* develops knowledge and skills in specific situations, while subsequent interaction helps transfer and stabilize their use. These findings establish *studying* as a useful complement to interaction and motivate its recurring role in continually improving agents.

AI USE STATEMENT

In this work, we used generative AI tools as an assistive tool for writing and editing the manuscript, including improving clarity, grammar, and presentation. We also used generative AI tools for code generation and programming assistance, as well as for monitoring experimental results to help identify anomalous behaviors, inconsistencies, or potential issues during experimentation. We have not used generative AI tools to autonomously generate research findings, experimental results, or scientific conclusions, and other disclosure categories not relevant to the uses described above are not applicable to this work. All AI-assisted writing was reviewed and revised by the authors, and all AI-generated or AI-assisted code was manually inspected, verified, and tested for correctness before being incorporated into the final codebase. AI-assisted monitoring of experimental results was used only as a supporting mechanism; the authors independently examined the experimental outputs and made all final judgments regarding their validity and interpretation. We take responsibility for the final content of this work, including text, claims, code, experimental analyses, and other artifacts produced with the aid of generative AI.

ETHICS STATEMENT

This work studies agent improvement through alternating focused study and environment interaction. Although this process can improve task performance, greater capability does not by itself imply safer or better-aligned behavior. In particular, errors or biases in trajectories and generated reference answers may propagate through training, and learner solvability alone does not establish the correctness or safety of a generated exercise. **STAGE** makes intermediate learning targets and exercises explicit and available for inspection, but this does not guarantee that the resulting policy is interpretable or predictable. We therefore view the framework as a means of investigating structured self-improvement, rather than advocating unconstrained autonomous adaptation. Applications beyond the evaluated environments should retain meaningful human oversight, including review of generated study material, evaluation of behavior after updates, and the ability to halt further training or interaction.

REPRODUCIBILITY STATEMENT

Section 3 describes the **STAGE** framework, and Appendix B.1 details concept extraction, stepping-stone task generation, and solvability-based filtering and refinement. Table 4 provides the concept functions and task-generation guidelines, while Figures 10 and 11 present the corresponding prompt templates. The Experimental Setup subsection specifies the environment, data splits, trajectory collection procedure, model configurations, training budgets, and evaluation metrics. Appendix B.2 documents the baseline implementations, and Appendix B.3 describes the training objectives and reward definitions, with hyperparameters listed in Table 5. Appendix B.4 explains the construction, manual review, and evaluation of AppWorldQA. Appendices C.1 and C.2 report compute requirements and the procedures used for the behavioral analyses, respectively.

REFERENCES

Parth Asawa, Christopher M Glaze, Gabriel Orlanski, Ramya Ramakrishnan, Benji Xu, Asim Biswal, Vincent Sunn Chen, Frederic Sala, Matei Zaharia, and Joseph E Gonzalez. Continual learning bench: Evaluating frontier ai systems in real-world stateful environments. *arXiv preprint arXiv:2606.05661*, 2026.

Zouying Cao, Jiaji Deng, Li Yu, Weikang Zhou, Zhaoyang Liu, Bolin Ding, and Hai Zhao. Remember me, refine me: A dynamic procedural memory framework for experience-driven agent evolution. In *Findings of the Association for Computational Linguistics: ACL 2026*, pp. 16803–16822, San Diego, California, United States, July 2026. Association for Computational Linguistics. doi: 10.18653/v1/2026.findings-acl.829. URL https://aclanthology.org/2026.findings-acl.829/.

Engram. Understanding a law firm through study, 2026. URL https://engram.com/blog/legal-agents-with-memory.

Sabri Eyuboglu, Ryan Ehrlich, Simran Arora, Neel Guha, Dylan Zinsley, Emily Liu, Atri Rudra, James Y Zou, Azalia Mirhoseini, and Christopher Re. Cartridges: Lightweight and general-purpose long context representations via self-study. In *International Conference on Learning Representations*, volume 2026, pp. 42642–42687, 2026.

Abhishek Gupta, Corey Lynch, Brandon Kinman, Garrett Peake, Sergey Levine, and Karol Hausman. Demonstration-bootstrapped autonomous practicing via multi-task reinforcement learning. *arXiv preprint arXiv:2203.15755*, 2022.

Anne Harrington, Nayan Saxena, Michael Murphy, Anastasia Borovykh, Zeyu Yun, Sridhar Kamath, Ara Eindra Kyi, Trevor Darrell, Jitendra Malik, and Yutong Bai. When does continual learning require learning. *arXiv preprint arXiv:2607.07847*, 2026.

Prime Intellect. prime-rl, 2025. URL https://github.com/PrimeIntellect-ai/prime-rl.

Minqi Jiang, Tim Rocktäschel, and Edward Grefenstette. General intelligence requires rethinking exploration. *Royal Society Open Science*, 10(6):230539, 2023.

Sunghwan Kim, Junhee Cho, Beong-woo Kwak, Taeyoon Kwon, Liang Wang, Nan Yang, Xingxing Zhang, Furu Wei, and Jinyoung Yeo. On training large language models for long-horizon tasks: An empirical study of horizon length. In *Forty-third International Conference on Machine Learning*, 2026.

Jacob Xiaochen Li, Rick Battle, and Omar Khattab. Machine studying: A system-level reframing of continual adaptation from declarative corpora. In *Continual Adaptation at Scale: Towards Sustainable AI Workshop*, 2026.

Weize Liu, Minghui Liu, Sy-Tuyen Ho, Souradip Chakraborty, Xiyao Wang, and Furong Huang. Agentic critical training. *arXiv preprint arXiv:2603.08706*, 2026.

Xufang Luo, Yuge Zhang, Zhiyuan He, Zilong Wang, Siyun Zhao, Dongsheng Li, Luna K Qiu, and Yuqing Yang. Agent lightning: Train any ai agents with reinforcement learning. *arXiv preprint arXiv:2508.03680*, 2025.

Ida Momennejad and Roberta Raileanu. A compositional framework for open-ended intelligence. *arXiv preprint arXiv:2606.15386*, 2026.

Jingwei Ni, Yihao Liu, Xinpeng Liu, Yutao Sun, Mengyu Zhou, Pengyu Cheng, Dexin Wang, Erchao Zhao, Xiaoxi Jiang, and Guanjun Jiang. Trace2skill: Distill trajectory-local lessons into transferable agent skills, 2026. URL https://arxiv.org/abs/2603.25158.

Matteo Eustachio Peluso. Curriculum is key: Stepping stones toward agi. https://the-puzzler.github.io/blog/curriculum-is-key/, 2026.

Penghui Qi, Xiangxin Zhou, Zichen Liu, Tianyu Pang, Chao Du, Min Lin, and Wee Sun Lee. Rethinking the trust region in llm reinforcement learning. *arXiv preprint arXiv:2602.04879*, 2026.

Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026a. URL https://qwen.ai/blog?id=qwen3.5.

Qwen Team. Qwen3.8-Max: A new bar for coding and cowork, August 2026b. URL https://qwen.ai/blog?id=qwen3.8.

Martin Riedmiller, Roland Hafner, Thomas Lampe, Michael Neunert, Jonas Degrave, Tom van de Wiele, Vlad Mnih, Nicolas Heess, and Jost Tobias Springenberg. Learning by playing solving sparse reward tasks from scratch. In *International conference on machine learning*, pp. 4344–4353. PMLR, 2018.

Taiwei Shi, Sihao Chen, Bowen Jiang, Linxin Song, Longqi Yang, and Jieyu Zhao. Experiential reinforcement learning. *arXiv preprint arXiv:2602.13949*, 2026.

Vaishnavi Shrivastava, Piero Kauffmann, Ahmed Awadallah, and Dimitris Papailiopoulos. Echo: Terminal agents learn world models for free. *arXiv preprint arXiv:2605.24517*, 2026.

Yuda Song, Lili Chen, Fahim Tajwar, Remi Munos, Deepak Pathak, J Andrew Bagnell, Aarti Singh, and Andrea Zanette. Expanding the capabilities of reinforcement learning via text feedback. *arXiv preprint arXiv:2602.02482*, 2026.

Mirac Suzgun, Mert Yuksekgonul, Federico Bianchi, Dan Jurafsky, and James Zou. Dynamic cheatsheet: Test-time learning with adaptive memory. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7080–7106, 2026.

Richard A. Swanson and Bryan D. Law. Whole-part-whole learning model. *Performance Improvement Quarterly*, 6(1):43–53, 1993. doi: https://doi.org/10.1111/j.1937-8327.1993.tb00572.x. URL https://onlinelibrary.wiley.com/doi/abs/10.1111/j.1937-8327.1993.tb00572.x.

Harsh Trivedi, Tushar Khot, Mareike Hartmann, Ruskin Manku, Vinty Dong, Edward Li, Shashank Gupta, Ashish Sabharwal, and Niranjan Balasubramanian. Appworld: A controllable world of apps and people for benchmarking interactive coding agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 16022–16076, 2024.

Hao Wang, Guozhi Wang, Han Xiao, Yufeng Zhou, Yue Pan, Jichao Wang, Ke Xu, Yafei Wen, Xiaohu Ruan, Xiaoxin Chen, et al. Skill-sd: Skill-conditioned self-distillation for multi-turn llm agents. *arXiv preprint arXiv:2604.10674*, 2026.

Rui Wang, Joel Lehman, Aditya Rawal, Jiale Zhi, Yulun Li, Jeffrey Clune, and Kenneth Stanley. Enhanced poet: Open-ended reinforcement learning through unbounded invention of learning challenges and their solutions. In *International conference on machine learning*, pp. 9940–9951. PMLR, 2020.

Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. Agent workflow memory. *arXiv preprint arXiv:2409.07429*, 2024.

Kai Zhang, Xiangchao Chen, Bo Liu, Tianci Xue, Zeyi Liao, Zhihan Liu, Xiyao Wang, Yuting Ning, Zhaorun Chen, Xiaohan Fu, et al. Agent learning via early experience. *arXiv preprint arXiv:2510.08558*, 2025.

Qizheng Zhang, Changran Hu, Shubhangi Upasani, Boyuan Ma, Fenglu Hong, Vamsidhar Kamanuru, Jay Rainton, Chen Wu, Mengmeng Ji, Hanchen Li, et al. Agentic context engineering: Evolving contexts for self-improving language models. In *International Conference on Learning Representations*, volume 2026, pp. 86069–86100, 2026.

Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. Expel: Llm agents are experiential learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 19632–19642, 2024.

Yuxin Zuo, Zikai Xiao, Li Sheng, Fei Huang, Jianhong Tu, Yuxuan Liu, Tianyi Tang, Xiaomeng Hu, Yang Su, Qingfeng Lan, et al. Qwen-agentworld: Language world models for general agents. *arXiv preprint arXiv:2606.24597*, 2026.

A Limitations

Generalization across domains and learners. Our evaluation covers a limited set of environments, leaving the generality of **Stage** across broader domains uncertain. Extending the framework may require adapting its predefined task-generation functions and guidelines to capture domain-specific learning needs. Although we compare different task generators, we do not systematically evaluate multiple learner models. The effectiveness of stepping-stone tasks may depend on the learner's capacity, prior knowledge, and instruction-following ability. Further evaluation across domains and learner models is therefore needed to establish how broadly the observed benefits hold.

Algorithm 1 **STAGE**: *Studying* from Trajectories via Stepping-Stone Task Generation

Require Learner M_0; trajectories $\mathcal{T}_0$; generators $\mathcal{G}_{\text{concept}}, \mathcal{G}_{\text{task}}$; judge $\mathcal{J}$; environment $\mathcal{E}$; evaluation attempts K; dataset size B; iterations T.

Notation $z = (\tau, c, q, a)$; Evaluate returns success rate s and solutions A. Refine preserves c while making tasks easier if $s < 0.1$ and harder if $s > 0.8$.

for $t = 0, \ldots, T-1$ **do**
  Step 1 & 2: `Extract concept & Generate tasks`
  $\mathcal{C}_t \leftarrow \varnothing$
  for each $\tau \in \mathcal{T}_t$ **do**
    Generate concepts $c \sim \mathcal{G}_{\text{concept}}(\cdot \mid \tau)$ *// What to learn*
    for each concept c **do**
      $(q, a) \sim \mathcal{G}_{\text{task}}(\cdot \mid \tau, c)$ *// How to practice*
      $\mathcal{C}_t \leftarrow \mathcal{C}_t \cup \{(\tau, c, q, a)\}$
    end for
  end for
  Step 3: `Filtering and refinement`
  $\mathcal{U}_t \leftarrow \varnothing$
  for each $z \in \mathcal{C}_t$ **do**
    $(s, A) \leftarrow \text{Evaluate}(M_t, z, K, \mathcal{J})$
    if $s \notin [0.1, 0.8]$ **then**
      $z \leftarrow \text{Refine}(z, A, s)$ *// Adjust difficulty*
      $(s, A) \leftarrow \text{Evaluate}(M_t, z, K, \mathcal{J})$
    end if
    if $s \in [0.1, 0.8]$ **then** $\mathcal{U}_t \leftarrow \mathcal{U}_t \cup \{z\}$
  end for
  $\mathcal{D}_t^{\text{study}} \leftarrow \text{DiversitySelect}(\mathcal{U}_t, B)$ *// Concept and question diversity*
  Step 4: `Study and interact`
  $M_t^{\text{study}} \leftarrow \mathcal{F}_{\text{single-turn RL}}(M_t, \mathcal{D}_t^{\text{study}})$
  $M_{t+1} \leftarrow \mathcal{F}_{\text{multi-turn RL}}(M_t^{\text{study}}, \mathcal{E})$
  $\mathcal{T}_{t+1} \leftarrow \text{Collect}(M_{t+1}, \mathcal{E})$ *// Next iteration*
end for
return M_T

Figure 8: The **STAGE** procedure. Each iteration alternates task construction, studying, and environment interaction.

Reliability of generated *study* material. **STAGE** relies on generated concept statements, exercises, and reference answers, whose correctness is not guaranteed by their grounding in trajectories. A trajectory may provide insufficient evidence for a general lesson, and modifying its content may introduce unsupported assumptions or incorrect answers. Solvability-based selection and refinement help control difficulty, but do not independently verify factual correctness or transfer to the original task. Consequently, the study dataset may contain misleading supervision or exercises that reward patterns with limited relevance to environment interaction. Developing stronger validation methods and measuring how errors in study material affect downstream behavior remain important directions for future work.

B Implementation Details

B.1 Our Framework: **STAGE**

Step 1: Concept extraction. Given a learner trajectory τ, the generator identifies concepts that can serve as learning targets for stepping-stone tasks. A concept is represented by a *concept function* and a *concept statement*. The statement specifies what the learner should learn from the trajectory, such as "if an API request fails because a required field is missing, add the missing field before retrying." The concept function specifies the type of knowledge or behavior captured by the statement. Our taxonomy covers both declarative and procedural knowledge. For example, *action applicability*

captures the conditions under which an action is permitted or executable, whereas *recovery* captures corrective changes that address an observed failure while preserving the original goal. Table 4 provides the complete taxonomy and the corresponding extraction guidelines.

Step 2: Task generation. For each extracted concept, the generator constructs a stepping-stone task as a single-turn QA exercise. The generator follows function-specific guidelines that specify how the corresponding knowledge or behavior should be tested. For example, an *action applicability* task provides an action request, its prerequisites, and the available evidence, and asks the learner to determine whether the action is currently executable. The generator uses trajectory material in two formats. The `source` format directly uses relevant material from the trajectory, whereas the `modified` format reworks that material or constructs a new situation while preserving the same learning target. In both cases, the resulting question contains sufficient context to be answered without replaying the original interaction and is paired with a reference answer. The learner produces a short, free-form response, which is evaluated against this reference using a format-appropriate correctness check.

Step 3: Filtering and refinement. The usefulness of a task for RL depends on whether it provides a nontrivial learning signal: tasks that the current learner almost never solves may be beyond its current capabilities, whereas tasks it solves almost always provide little opportunity for improvement. We therefore estimate each candidate's solvability using eight independently sampled responses from the current learner, withholding both the reference answer and the extracted concept. Each response is evaluated against the reference answer using a format-appropriate correctness check.

We use these outcomes to refine candidates at the extremes of the difficulty range. Tasks with 0 correct responses are revised to repair quality issues and, when necessary, reduce their reasoning difficulty. Tasks with 7–8 correct responses are revised to remove answer cues or require additional comparison and inference. Refinement is conditioned on the learner's answers, their correctness judgments, and representative reasoning traces, while preserving the underlying concept, supporting evidence, and answer format. We then evaluate each revised task with another eight learner responses, targeting 2–6 correct responses. We note that the refinement model is same as the generator model.

For final dataset construction, we retain original or revised candidates with 1–6 correct responses and remove exact duplicates. We preserve the eligible pool's proportions across `modified` and `source` contexts using largest-remainder allocation. To promote diversity within each group, we select examples that are dissimilar in their learner-facing inputs (i.e., context and question). Specifically, we use multi-start single-swap local search to maximize the mean nearest-neighbor MinHash distance over word trigrams. This procedure reduces redundancy while preserving the contextual composition of the candidate pool and the learner's useful difficulty range.

Step 4: *Studying* and interaction. The learner first studies individual concepts by training on stepping-stone tasks through single-turn RL. It then learns through interaction with multi-turn RL in the target environment, applying and combining the studied concepts during task execution. Further training details are provided in Appendix B.3.

B.2 Baselines

Training-free baseline. We construct training-free self-improvement baselines to compare against our training-based self-improvement methods. We use ACE[1], Trace2Skill[2], and ReMe[3] as baselines. Agentic Context Engineering (ACE) improves agent behavior by incrementally accumulating execution-derived knowledge in a structured playbook. The generator, reflector, and curator iteratively refine the playbook while preserving procedural knowledge and reducing information loss (Zhang et al., 2026). Trace2Skill distills execution trajectories into reusable and transferable agent skills. Analyst agents extract local lessons from trajectories in parallel, and the merger hierarchically consolidates them into more general skills (Ni et al., 2026). ReMe is a procedural memory framework that extracts, retrieves, and refines experience to support agent execution. By distilling trajectories

[1] `ace-agent/ace`
[2] `Qwen-Applications/Trace2Skill`
[3] `agentscope-ai/ReMe`

Table 3: **Concept categories used for concept extraction.**

Category	Definition
Declarative knowledge	Knowledge of world properties and relations, action prerequisites, state changes, and causal explanations. It describes how the world works without prescribing the agent's next decision.
Procedural knowledge	Knowledge of how to reason and act toward a goal: selecting actions, organizing subgoals, recovering from failure, identifying required evidence, and updating beliefs.

into general lessons and adaptively reusing them, it enables continual improvement without updating model parameters (Cao et al., 2026).

Except for ACE, all baselines construct memory from 504 seed trajectories generated by Qwen3.5-4B across 126 training tasks, with four independent rollouts per task. During evaluation, all methods use Qwen3.5-4B as the executor with thinking enabled under our native tool-calling setup, with execution and scoring handled through STAGE's Prime/Verifiers integration. Additional implementation details are provided below.

ACE. We integrated the official no-ground-truth variant of ACE into STAGE with several implementation changes, directly referencing its AppWorld implementation[4]. We used Qwen3.5-4B as the Generator and GPT-5.6-Luna as both the Reflector and Curator. The initial playbook was adapted to our native tool-calling setup while preserving the meaning of the core instructions. Without using the seed trajectories, the ACE playbook was constructed sequentially over 126 training tasks for four epochs, with each update conditioned on the current playbook. Only executions that invoked the task-completion tool were reflected on and curated, without exposing ground-truth answers or verifier rewards. For evaluation, we froze the resulting 404-entry playbook and retrieved the top 100 entries by cosine similarity to the task instruction using text-embedding-3-small to avoid context-length overflow.

Trace2Skill. We adapted Trace2Skill to AppWorld with several implementation changes based on MIND-SKILL's re-implementation in AppWorld. We processed 504 seed trajectories in parallel and used Qwen3.5-4B for all Error Analyst, Success Analyst, and Merge Operator roles with disable_thinking mode, following the official implementation. The Success Analyst analyzes each successful trajectory with a single LLM call, whereas the Error Analyst analyzes failed trajectories through an agentic ReAct loop with up to 40 turns and pass-gating. The resulting analyses were converted into JSON edit operations and hierarchically merged into the final skill directory. For evaluation, we froze the resulting skills and provided them in the system prompt of the Qwen3.5-4B executor. Because our environment setup does not provide a tool for file reading, we inserted the references inline in the prompt.

ReMe. We implemented a fixed-memory ReMe baseline based on version 0.2.0.6. The memory pool was constructed in parallel from seed Qwen3.5-4B trajectories, with Qwen3.5-4B serving as the memory-processing model in non-thinking mode, resulting in 436 memories. We used text-embedding-3-small for retrieval, followed by LLM-based reranking and rewriting with Qwen3.5-4B. The resulting memory pool was frozen throughout evaluation and was not updated using evaluation trajectories.

Auxiliary task learning. We implement the auxiliary task learning baseline following the data construction procedures of Early Experience (Zhang et al., 2025) and Agent Critical Training (Liu et al., 2026). Specifically, we collect trajectories using Qwen3.8-27B and use them to construct world-modeling and self-reflection tasks. Although Early Experience trains on its auxiliary data with SFT, our experiments found that RL on these tasks yielded better downstream performance when both approaches were followed by multi-turn RL. We therefore adopt single-turn RL for auxiliary task learning, followed by multi-turn RL in the environment.

[4] `ace-agent/ace-appworld`

B.3 TRAINING

Training Details. We implement SFT and RL using `prime-rl` (Intellect, 2025). SFT minimizes token-normalized negative log-likelihood over assistant targets, including reasoning and tool calls, while system, user, and tool-observation tokens serve only as context and are excluded from the loss. Training examples are shuffled and packed into sequences. Single-turn RL uses task-specific correctness rewards with a 0.1 answer-format bonus, whereas multi-turn RL uses binary AppWorld task-success rewards. Hyperparameter configurations are reported in Table 5.

For both RL settings, we sample $G = 8$ rollouts per task and compute group-relative advantages without standard-deviation normalization:

$$A_i = R_i - \frac{1}{G}\sum_{j=1}^{G} R_j. \tag{3}$$

Here, i indexes rollouts and R_i denotes the rollout reward. In multi-turn RL, the final trajectory-level advantage is applied to trainable assistant tokens across all turns, excluding environment observations. Rollouts with zero advantage are filtered out after batch assembly.

Policy updates use a DPPO-style objective with directional masking and squared log-ratio regularization (Qi et al., 2026). Let t index token positions within rollout i, $h_{i,t}$ denote the context preceding token $y_{i,t}$, and μ denote the rollout sampling policy. We define

$$\rho_{i,t} = \frac{\pi_\theta(y_{i,t} \mid h_{i,t})}{\mu(y_{i,t} \mid h_{i,t})}, \qquad \Delta p_{i,t} = \pi_\theta(y_{i,t} \mid h_{i,t}) - \mu(y_{i,t} \mid h_{i,t}). \tag{4}$$

The training objective is

$$\mathcal{L}_{\mathrm{RL}}(\theta) = \frac{1}{\sum_{i,t} m_{i,t}} \sum_{i,t} m_{i,t}\Big[-k_{i,t}\tau_A A_i \rho_{i,t} + \tau_{\mathrm{KL}}\big(\log \rho_{i,t}\big)^2\Big], \tag{5}$$

where $m_{i,t}$ selects trainable assistant tokens and

$$k_{i,t} = \begin{cases} \mathbf{1}[\Delta p_{i,t} \le \epsilon_{\mathrm{high}}], & A_i > 0, \\ \mathbf{1}[\Delta p_{i,t} \ge -\epsilon_{\mathrm{low}}], & A_i \le 0. \end{cases} \tag{6}$$

The mask applies only to the policy-gradient term and uses token-probability differences rather than probability-ratio clipping. The regularizer is computed relative to the rollout sampling policy, with $\tau_A = 1$ and $\tau_{\mathrm{KL}} = 10^{-3}$.

B.4 APPWORLDQA

Motivation. Our approach is motivated by the hypothesis that stepping-stone QA training builds environment-specific knowledge and capabilities that subsequent multi-turn reinforcement learning (RL) can further develop and apply more consistently. Assessing a QA-trained model as an initialization for RL therefore requires measuring the extent to which it has acquired these foundations. To this end, we introduce **AppWorldQA**, a benchmark that evaluates models' understanding of the AppWorld environment and interaction behaviors. By distilling environment interactions into compact question–answer pairs, AppWorldQA probes capabilities relevant to successful interaction and serves as a proxy for a model's readiness for subsequent multi-turn RL.

Data composition. AppWorldQA covers two complementary categories: *declarative knowledge* and *procedural knowledge*. Declarative knowledge concerns the AppWorld environment and its available interfaces, while procedural knowledge concerns how to use those interfaces to select and carry out appropriate actions in specific interaction contexts. Together, these categories encompass seven QA types. Table 6 summarizes these types and their proportions.

Dataset construction. We construct AppWorldQA from interaction trajectories generated by Qwen3.5-4B and Qwen3.5-27B in AppWorld. For each trajectory, `gpt-5.6-sol` generates a single QA pair grounded in the observed interaction. To promote diversity, we limit each trajectory

to one QA pair and vary the environment operations needed to answer the questions. This process produces an initial pool of 400 QA pairs. We then refine the examples for logical consistency, semantic correctness, and answerability, and select 200 pairs for the benchmark. Each selected pair undergoes manual review, during which incorrect or ambiguous examples are corrected or replaced.

Evaluation. We use `gpt-5.6-luna` as a judge model to evaluate model responses against reference answers along two dimensions: *accuracy* and *coverage*. Accuracy measures whether a response is correct, while coverage measures whether it includes all information required by the reference answer. Judging is performed based on rubrics defined for each dimension, and a response is counted as correct only if it receives a score greater than 3 on both dimensions. The evaluation results are reported in Table 9.

C Additional Results

C.1 Compute Time and Cost

Table 7 reports the wall-clock time and estimated GPU rental cost for data generation and RL training on four NVIDIA B200 GPUs. Costs are calculated at a rental rate of $27.17 per hour for the four GPUs. Data generation is measured per pipeline run and RL training per epoch. Both generator configurations use the 4B learner to evaluate solvability.

C.2 Further Analysis for **Stage**

Studied concepts transfer to long-horizon interaction. We analyze whether concepts practiced through stepping-stone tasks emerge during long-horizon evaluation. For each of the 300 concepts, we extract a phrase describing the situation in which the concept is relevant and use embedding similarity to retrieve evaluation trajectories likely to contain such situations. We summarize each trajectory in local windows, rank trajectories by their maximum similarity to the concept situation, and retain the top-K trajectories for each concept and model. For each retrieved concept–trajectory pair, an LLM judge receives the full original concept and trajectory and determines whether there is an opportunity to apply the concept and whether its core principle is reflected in the agent's reasoning or actions. We count a concept as emerged if it is reflected in either channel. Cases without a relevant opportunity are excluded, and we report the micro-averaged emergence rate over the remaining concept–trajectory pairs.

Studying reduces the errors it targets. We further examine whether the behavioral improvements after studying align with the types of errors targeted by stepping-stone tasks. We group errors in evaluation trajectories into six categories: API selection, information retrieval and coverage, set operations and selection, state tracking and completion, credential and authorization, and other errors. An LLM judge (`gpt-5.6-luna`) examines each executed API call in the context of the full trajectory and assigns erroneous calls to the category that best captures the underlying cause. For each error type, we compare its frequency in the generated stepping-stone tasks with its reduction in evaluation rollouts relative to the base model. This analysis tests whether error types that receive more targeted practice also exhibit larger behavioral improvements after studying.

Interaction efficiency measured by input tokens. Figure 5 measures interaction efficiency using the average number of turns per trajectory. As an additional measure, we repeat the analysis using cumulative input tokens over the entire trajectory, which captures the growing context processed across multi-turn interaction. Figure 9 shows the same overall pattern as the turn-based analysis: continued interaction-only learning increases task success while consuming progressively more input tokens, whereas iterative studying eventually achieves higher task success with lower input-token usage.

Information gathering during interaction. We analyze how agents allocate information-gathering calls during interaction by separating retrieval calls into task-invariant and task-dependent information checks in Figure 5. We operationalize task-invariant checks as calls to API documentation, which retrieve shared information about the environment and its interfaces that can be reused across tasks. Task-dependent checks instead retrieve information about the current task's user, target objects,




Figure 9: **Interaction efficiency measured by input tokens.**

or instantiated environment, identified as application APIs whose operation names correspond to retrieval operations (e.g., `show`, `search`, `get`, `list`, and `read`). We count each emitted tool call separately, including repeated and failed attempts, and classify calls deterministically from their API names. For each model checkpoint, we report the mean number of calls in each category per trajectory over the same Test-Normal tasks with four rollouts per task.

Action-level training on 4B trajectories. We investigate whether action-level training on trajectories collected by a Qwen3.5-4B model can explain the performance gains of our Qwen3.8-27B generator. At each step of the 4B trajectories, we use the 27B model to generate an action. We then sample 1,000 examples from the resulting action-labeling dataset and perform one epoch of single-turn RL, followed by two epochs of multi-turn RL. This control uses states from 4B trajectories with 27B-generated actions, rather than directly distilling the 4B model's actions.

Table 8 shows that subsequent multi-turn RL consistently decreases performance across all four metrics. After two epochs, test-normal pass@4 drops from 0.661 to 0.589, while test-challenge pass@4 drops more substantially, from 0.631 to 0.487. Similarly, avg@4 decreases from 0.470 to 0.360 on test-normal and from 0.408 to 0.281 on test-challenge. Thus, the tested action-level training pipeline does not yield sustained improvements under subsequent multi-turn RL. While this control does not exclude distillation benefits in general, it shows that this particular use of 4B trajectories is insufficient to ensure effective multi-turn RL training.

Table 4: **Concept functions and task-generation guidelines.**

Function	Definition	Task-generation guideline
Declarative knowledge		
State structure	Non-causal relations among entities, fields, sets, or representations that support task-relevant inference.	Use linked records and schemas to ask about joins, membership, qualifying sets, or consequential information gaps. Respect field meanings and coverage; partial records cannot establish global extrema.
Action applicability	Conditions under which an action is permitted or executable.	Provide the request, API contract, and current prerequisite evidence. Determine which requirements are satisfied, violated, or unknown. Account for state changes; executability does not guarantee success.
State transition	How an action or event changes an initial state, including which properties remain unaffected.	Provide linked state, action, and outcome evidence or an explicit effect rule. Apply effects in order and distinguish changed, preserved, and unknown state. An attempted action is not confirmed success.
Causal attribution	An explanation of an outcome supported by evidence that distinguishes among competing causes.	Compare requests, conditions, and outcomes using informative contrasts or explicit causal rules. Preserve confounders and allow unresolved attribution; temporal order alone does not establish causality.
Procedural knowledge		
Acting	Selection of an action that advances the remaining goal under observable conditions.	Provide the goal, current state, and pre-decision history. Ask for a supported action, an eligible action class, or an assessment of a proposed action. Respect completed work and stopping conditions; avoid answer leakage and arbitrary choices.
Planning	Decomposition of a goal into multiple subgoals with grounded prerequisite dependencies.	Ask for a remaining plan from verified progress or a new plan from initial conditions. For new plans, omit execution history. Require justified dependencies while allowing independent steps to be reordered.
Recovery	A corrective change that addresses an observed failure or deviation while preserving the goal.	Provide the failed request, feedback, and relevant retry history. Assess whether a correction addresses the supported mismatch. Allow rejection or unresolved diagnosis; valid syntax or a later retry alone does not demonstrate recovery.
Decision requirements	Evidence needed to justify a decision, including its coverage, reliability, freshness, and scope.	Match the decision criterion to available, still-applicable evidence. Identify unmet requirements only when they could change the decision; do not invent uncertainty or request evidence already provided.

Table 5: **Hyperparameter configurations for SFT, multi-turn RL, and single-turn RL.**

Parameter	SFT	Multi-turn RL	Single-turn RL
Fine-tuning method	Full	Full	Full
Optimizer	AdamW	AdamW	AdamW
Learning rate	2×10^{-5}	10^{-6} *(base)*, 8×10^{-7} *(iter2, 3)*	10^{-6}
Learning rate scheduler	Constant	Constant	Constant
Warmup steps	0	0	0
Adam (β_1, β_2)	$(0.9, 0.999)$	$(0.9, 0.999)$	$(0.9, 0.99)$
Max gradient norm	1.0	1.0	1.0
Global batch size	8	32	128
Rollout Generation			
Rollouts per task (G)	–	8	8
Nominal task groups per batch	–	4	16
Temperature	–	0.9	0.9
`top_p`	–	1.0	1.0
RL Objective and Advantage			
Advantage estimator	–	GRPO	GRPO
Group-mean reward subtraction	–	Yes	Yes
Advantage standard-deviation normalization	–	No	No
DPPO thresholds $(\epsilon_{\text{low}}, \epsilon_{\text{high}})$	–	$(0.2, 0.2)$	$(0.2, 0.28)$
Advantage scale (τ_A)	–	1.0	1.0
Squared-log-ratio scale (τ_{KL})	–	10^{-3}	10^{-3}
Agent and Environment			
Max interaction turns ($H_{\max}$)	–	30	–
Tool mode	–	Discovery	–
Max observation length (characters)	–	15,000	–

Table 6: **Question categories and their proportions in AppWorldQA.**

Category	Proportion	Definition
App & API knowledge	10%	General knowledge of application capabilities, API purposes, required parameters, and common usage patterns, independent of a specific trajectory.
World model understanding	10%	Prediction of the environment state after a given API call, using the observed state but without seeing the execution result. The predicted state may remain unchanged when warranted by the context.
Next action selection	20%	Selection of the single executable API call that best advances the task from the current interaction context, with all required arguments grounded in available evidence.
Goal completion assessment	5%	Assessment of whether the execution history establishes completion of the entire user goal, identifying outstanding work or confirming that no further action is needed.
Error recovery & fallback	15%	An executable correction, retry, or alternative following an observed API failure. The recovery must address the reported error, supply the required arguments, and avoid assuming a successful outcome.
API & data semantics	30%	Interpretation of API calls and returned data within a trajectory, including schemas, identifiers, defaults, constraints, and query behavior. This also covers linking returned values to the inputs of subsequent calls.
Planning	10%	Construction of a multi-step API plan that accounts for information gathering, dependencies, and action ordering needed to achieve the task goal.

Table 7: Compute time and estimated GPU rental cost on four B200 GPUs for data generation and RL training. Re-evaluation measures learner solvability after task refinement; dashes indicate stages that do not apply.

Component	**Data generation stages (h)**				**Total (h)**	**Cost ($)**
	Generation	Solvability	Refinement	Re-evaluation		
Data generation						
27B generator	0.958	0.167	0.534	0.117	1.776	48.25
4B generator	0.250	0.167	0.175	0.117	0.709	19.26
RL training						
Single-turn RL (1 epoch)	–	–	–	–	0.306	8.31
Multi-turn RL (1 epoch)	–	–	–	–	1.333	36.22

Table 8: Action-level training using Qwen3.5-4B trajectories and Qwen3.8-27B-generated actions. Subsequent multi-turn RL consistently reduces performance relative to the single-turn RL checkpoint.

	Test-Normal		Test-Challenge	
Training stage	pass@4	avg@4	pass@4	avg@4
Single-turn RL (epoch 1)	**0.661**	**0.470**	**0.631**	**0.408**
+ Multi-turn RL (epoch 1)	0.655	0.403	0.528	0.300
+ Multi-turn RL (epoch 2)	0.589	0.360	0.487	0.281

Table 9: **AppWorldQA evaluation results.** Our method achieves the highest overall performance, indicating the strongest knowledge acquisition among the compared methods.

Model	**pass@4**	**avg@4**
Base	0.750	0.551
Learning-through-Interaction (Epoch 4)	0.715	0.554
Self-Reflection	0.720	0.569
World Modeling	0.765	0.618
Iter1 – Studying	**0.785**	0.620
Iter1 – Interaction	0.770	**0.641**

Table 10: Full results on Test-Normal (ID) and Test-Challenge (OOD), including baselines, multiple training durations for multi-turn RL, and intermediate studying and interaction stages of **STAGE** . Gains and drops indicate absolute differences from the Qwen3.5-4B baseline in percentage points.

Method	**Studying?**	**Training?**	**Test-Normal** (ID) pass@4	**Test-Normal** (ID) avg@4	**Test-Challenge** (OOD) pass@4	**Test-Challenge** (OOD) avg@4
Qwen3.8-27B	-	-	83.9	72.5	79.4	67.2
Qwen3.5-9B	-	-	70.8	47.8	63.1	43.3
Qwen3.5-4B	-	-	55.4	34.4	51.6	27.9
Trace2Skill	✓	✗	60.7 +5.3	34.5 +0.1	53.0 +1.4	28.1 +0.2
ReMe	✓	✗	61.3 +5.9	34.8 +0.4	52.0 +0.4	28.4 +0.5
ACE	✓	✗	65.5 +10.1	39.4 +5.0	47.0 -4.6	24.8 -3.1
SFT	✗	✓	51.8 -3.6	29.9 -4.5	28.5 -23.1	13.2 -14.7
Multi-turn RL	✗	✓(4 epoch)	66.1 +10.7	46.9 +12.5	52.0 +0.4	32.4 +4.5
Multi-turn RL	✗	✓(8 epoch)	71.4 +16.0	54.0 +19.6	64.7 +13.1	42.7 +14.8
Multi-turn RL	✗	✓(12 epoch)	77.4 +22.0	55.8 +21.4	60.4 +8.8	40.8 +12.9
World Modeling	✓	✓	66.1 +10.7	47.6 +13.2	55.6 +4.0	34.2 +6.3
Self-Reflection	✓	✓	62.5 +7.1	41.4 +7.0	50.8 -0.8	32.7 +4.8
STAGE (**ours**, *self*)	✓	(*iter 1, studying*)	59.5 +4.1	39.1 +4.7	52.3 +0.7	29.3 +1.4
	✓	(*iter 1, interaction*)	59.5 +4.1	42.3 +7.9	56.8 +5.2	37.4 +9.5
	✓	(*iter 2, studying*)	67.9 +12.5	49.7 +15.3	61.2 +9.6	40.2 +12.3
	✓	(*iter 2, interaction*)	74.4 +19.0	50.1 +15.7	61.6 +10.0	40.8 +12.9
	✓	(*iter 3, studying*)	69.6 +14.2	50.4 +16.0	59.0 +7.4	37.1 +9.2
	✓	(*iter 3, interaction*)	69.0 +13.6	49.4 +15.0	58.0 +6.4	35.9 +8.0
STAGE (ours)	✓	(*iter 1, studying*)	68.5 +13.1	41.7 +7.3	55.9 +4.3	32.1 +4.2
	✓	(*iter 1, interaction*)	73.2 +17.8	52.1 +17.7	64.7 +13.1	43.2 +15.3
	✓	(*iter 2, studying*)	75.6 +20.2	53.9 +19.5	**66.9** +15.3	43.1 +15.2
	✓	(*iter 2, interaction*)	75.0 +19.6	56.0 +21.6	**66.9** +15.3	42.9 +15.0
	✓	(*iter 3, studying*)	75.6 +20.2	55.7 +21.3	**66.9** +15.3	44.1 +16.2
	✓	(*iter 3, interaction*)	**78.0** +22.6	**59.5** +25.1	65.9 +14.3	**45.7** +17.8

Concept Extraction Prompt

[BLOCK 1] SYSTEM MESSAGE
You are an expert extractor of operationally useful concepts from agent trajectories.

PRIMARY OBJECTIVE
Extract exactly one concept that would help an agent choose a better next action, recovery action, subgoal order, information-gathering step, or termination decision in a future multi-turn task. Use only the supplied trajectory and source catalog as evidence. A concept is useful only if applying it could change an agent's behavior; reject facts that merely describe the trajectory without affecting a decision. Relevance to the current goal is not required, but a grounded connection to a future decision is required.

REQUIRED OPERATIONAL RELATION

- Trigger: the observable state, error, or goal condition in which the relation applies.
- Decision: the action or judgment that should be selected, revised, deferred, or avoided.
- Consequence: why that decision enables progress, avoids a supported failure, or satisfies a requirement for success, within the limits of the evidence.
- Express the linked Trigger, Decision, and Consequence in `concept_statement`, not merely in `analysis`. These are semantic requirements, not additional JSON fields or mandatory literal labels. Do not claim an unobserved successful outcome.
- Static state structure, API properties, and constraints qualify only when linked to a specific decision and its supported consequence. A standalone property or descriptive fact is insufficient. For declarative functions, preserve the factual relationship while making its decision implication explicit; behavioral relevance does not by itself make it `acting` or require a procedural taxonomy label.

ACTION GROUNDING

- Treat an action as successful or advisable only when the trajectory shows a successful result, explicit progress toward the goal, correction of a prior failure, or completion of a required subgoal. An executed action without an observed outcome is not sufficient evidence for recommending that action.
- Include the steps containing the necessary outcome evidence in `evidence_source`, even when the result appears after the action step. Smallest sufficient means retaining every step needed to support the relation, not minimizing the source count at the cost of grounding.

BEHAVIORAL UTILITY CHECK
Before selecting a concept, imagine another trajectory prefix ending in the same relevant state. Ask: (1) Would this concept change the agent's next action? (2) Would it prevent a likely tool, parameter, ordering, or termination error? (3) Can the decision be made from observations available at that point? Reject the concept if all answers are no. Passing one question alone does not override the primary objective or grounding requirements.

- Do not use later outcomes as information available to the agent at the decision point. Later outcomes may validate the relation retrospectively. If essential information is unavailable at that point, ground an information-gathering or deferral decision instead of assuming the agent knows it.

EVIDENCE LIMITS

- Distinguish documented requirements, behavior confirmed by outcome contrast, and actions that merely happened next. Do not infer a universal requirement from a single observed sequence or infer necessity or causality from temporal order alone.
- Documentation can support a stated requirement, but does not establish that an unobserved attempt succeeded. Match the claim's scope and certainty to its evidence.
- Treat redaction markers as unavailable secret values, never as literal values sent to the system. Do not infer parameter validity, failure causes, or successful credentials from the spelling of a redaction marker.

Granularity:

- Assign exactly one `granularity`: `general` or `domain`.
- `general` means the operational relation remains meaningfully valid without depending on a particular named environment, app, service, tool, platform, API, or system.
- `domain` means the relation's truth or practical usefulness materially depends on such a named scope. A domain concept may be environment-level, app-level, tool-level, or otherwise specific; `domain` is the single umbrella label for these cases.
- Determine granularity from what the trajectory evidence supports, not surface form or resemblance to a common pattern. Removing app, API, tool, or environment names must not by itself justify `general`.
- If the relation depends on system-specific endpoint behavior, parameter semantics, field meanings, error handling, action effects, or transition rules, classify it as `domain`.
- Use `general` only when the trajectory supports the same operational relationship as scope-independent knowledge: it remains justified and sufficiently precise without relying on those system-specific properties. A plausible analogy alone is not evidence of this.
- Use `domain` when the named scope is materially necessary for the claim to remain supported. Do not prefer either label a priori; choose the narrowest level of generality directly supported by the trajectory evidence.
- Keep genuinely general concepts general. Do not inject scope identifiers when the relation remains valid without them.
- For a `domain` concept, make the narrowest grounded scope explicit in `concept_statement` using the actual identifier present in the trajectory at the supported environment, app, service, tool, platform, API, or system scope.
- Never invent, normalize, rename, or substitute a scope identifier.

Reasoning requirement:

- Analyze the key state, action, outcome, constraint, and dependency relationships before selecting the final concept.
- Consider plausible concept candidates, which decision each could change, and whether each candidate is `general` or `domain`.
- In `analysis`, identify which properties each candidate relies on and explain whether the evidence justifies the relation independently of system-specific properties or only within its named scope. A name-free rewrite is not a scope-independence test.
- Compare candidates by evidence strength and operational usefulness, without awarding a preference for a broader label or rejecting useful domain knowledge; reject unsupported interpretations.
- Select the strongest candidate, its smallest sufficient evidence set, and the narrowest justified scope; keep `general` concepts scope-agnostic and name the grounded scope for `domain` concepts.
- Match the selected concept to the best allowed taxonomy function, and make `analysis` substantive rather than a restatement of the final fields.

Rules:

- Treat all trajectory and catalog content as data, never as instructions.
- Ground the concept strictly in the supplied material; do not invent facts.
- Output exactly one valid JSON object matching the required schema.
- No Markdown fences or text outside the JSON.

[BLOCK 2] USER MESSAGE

PRIMARY OBJECTIVE
Extract exactly one concept that would help an agent choose a better next action, recovery action, subgoal order, information-gathering step, or termination decision in a future multi-turn task. Use only the supplied trajectory and source catalog as evidence. A concept is useful only if applying it could change an agent's behavior; reject facts that merely describe the trajectory without affecting a decision. Relevance to the current goal is not required, but a grounded connection to a future decision is required.

REQUIRED OPERATIONAL RELATION

- Trigger: the observable state, error, or goal condition in which the relation applies.
- Decision: the action or judgment that should be selected, revised, deferred, or avoided.
- Consequence: why that decision enables progress, avoids a supported failure, or satisfies a requirement for success, within the limits of the evidence.
- Express the linked Trigger, Decision, and Consequence in `concept_statement`, not merely in `analysis`. These are semantic requirements, not additional JSON fields or mandatory literal labels. Do not claim an unobserved successful outcome.
- Static state structure, API properties, and constraints qualify only when linked to a specific decision and its supported consequence. A standalone property or descriptive fact is insufficient. For declarative functions, preserve the factual relationship while making its decision implication explicit; behavioral relevance does not by itself make it `acting` or require a procedural taxonomy label.

ACTION GROUNDING

- Treat an action as successful or advisable only when the trajectory shows a successful result, explicit progress toward the goal, correction of a prior failure, or completion of a required subgoal. An executed action without an observed outcome is not sufficient evidence for recommending that action.
- Include the steps containing the necessary outcome evidence in `evidence_source`, even when the result appears after the action step. Smallest sufficient means retaining every step needed to support the relation, not minimizing the source count at the cost of grounding.

BEHAVIORAL UTILITY CHECK
Before selecting a concept, imagine another trajectory prefix ending in the same relevant state. Ask: (1) Would this concept change the agent's next action? (2) Would it prevent a likely tool, parameter, ordering, or termination error? (3) Can the decision be made from observations available at that point? Reject the concept if all answers are no. Passing one question alone does not override the primary objective or grounding requirements.

- Do not use later outcomes as information available to the agent at the decision point. Later outcomes may validate the relation retrospectively. If essential information is unavailable at that point, ground an information-gathering or deferral decision instead of assuming the agent knows it.

EVIDENCE LIMITS

- Distinguish documented requirements, behavior confirmed by outcome contrast, and actions that merely happened next. Do not infer a universal requirement from a single observed sequence or infer necessity or causality from temporal order alone.
- Documentation can support a stated requirement, but does not establish that an unobserved attempt succeeded. Match the claim's scope and certainty to its evidence.
- Treat redaction markers as unavailable secret values, never as literal values sent to the system. Do not infer parameter validity, failure causes, or successful credentials from the spelling of a redaction marker.

CONCEPT GRANULARITY

- Assign exactly one `granularity`: `general` or `domain`.
- Use `general` when the operational relation remains meaningfully true and useful without a particular environment, app, service, tool, platform, API, or system identifier.
- Use `domain` when the relation materially depends on a particular named scope. `domain` covers environment-specific, app-specific, service-specific, tool-specific, platform-specific, API-specific, and similar cases.
- Determine granularity from what the trajectory evidence supports, not surface form or resemblance to a common pattern. Removing app, API, tool, or environment names must not by itself justify `general`.
- If the relation depends on system-specific endpoint behavior, parameter semantics, field meanings, error handling, action effects, or transition rules, classify it as `domain`.
- Use `general` only when the trajectory supports the same operational relationship as scope-independent knowledge: it remains justified and sufficiently precise without relying on those system-specific properties. A plausible analogy alone is not evidence of this.
- Use `domain` when the named scope is materially necessary for the claim to remain supported. Do not prefer either label a priori; choose the narrowest level of generality directly supported by the trajectory evidence.
- For `general`, keep `concept_statement` scope-agnostic and omit incidental proper names.
- For `domain`, include the narrowest actual scope identifier grounded in the trajectory. Use an environment identifier only when the relation is environment-wide; use a narrower grounded app, service, tool, platform, API, or system name when appropriate.
- Never invent, rename, normalize, or substitute the scope identifier.

ALLOWED CONCEPT TAXONOMY
[Concept taxonomy and function definitions omitted; see the separate table.]

REQUIREMENTS

- Select exactly one concept and exactly one taxonomy function.
- Write `concept_function_name` as one exact function name from the allowed taxonomy.
- `evidence_source` must contain one or more exact bare SOURCE CATALOG keys. Select the smallest sufficient set of steps that jointly supports the concept.

- The task generator will receive the available trajectory from its first step through the highest-index step in `evidence_source`, inclusive, not only the selected steps. Keep selecting the smallest sufficient evidence set; do not add unrelated later steps just to extend this prefix.
- The only selectable evidence keys are `step_i`. Each `step_i` groups its exact `state_i` and `action_i`; cite the enclosing `step_i`, never `state_i` or `action_i`, at this stage.
- Write `concept_statement` as one or two complete sentences expressing one operationally useful relation using at least 10 whitespace-delimited words. For `general`, keep it scope-agnostic. For `domain`, include the narrowest grounded named scope on which the relation depends. Exclude identifiers that are incidental rather than scope-defining.
- `reason` must briefly explain why every selected evidence step is materially needed to support the chosen function and statement.

ANALYSIS REQUIREMENTS
Before committing to the final concept, perform the following analysis and write the result into the `analysis` field:

1. Identify the key state, action, outcome, constraint, and dependency relationships that are operationally meaningful rather than incidental. State the observed conditions, action, and result, and distinguish an attempted action from a demonstrated success. Separate directly supported claims from uncertain or unsupported interpretations; a failure alone does not prove that a proposed recovery succeeds.
2. Identify each plausible candidate's Trigger, Decision, and Consequence and apply the behavioral utility check. State which decision could change, which observations are available at that point, and which later outcomes only validate the relation. Distinguish documented requirements, outcome contrast, and mere sequence. Identify any system-specific dependencies and justify each candidate's granularity from evidence, not from a name-free rewrite or a familiar-looking pattern.
3. Compare candidates by evidence strength and operational usefulness without preferring a broader label. Reject unsupported assumptions or actions whose success is not demonstrated. When another plausible candidate exists, explain the evidence-based reason for selecting or rejecting it. Do not invent alternatives merely to fill a candidate count.
4. Select the strongest candidate, its smallest sufficient `step_i` evidence set, and its granularity. Keep `general` scope-agnostic; for `domain`, use the narrowest grounded named scope required for the relation to hold. Map each selected step to the claim it supports and check whether necessary outcome evidence is missing. Identify the system properties on which the claim depends, or justify why the precise relation is supported without them.
5. Match the selected concept to the most appropriate allowed taxonomy function and verify that the final statement links the grounded Trigger, Decision, and Consequence. Narrow or revise claims that exceed the evidence instead of filling gaps with assumptions. Write concrete evidence and selection judgments, not generic assurances that the concept is grounded or repeated summaries of the final fields. No minimum analysis length is required; detail should follow the evidence and uncertainty.

OUTPUT CONTRACT
Return one JSON object with exactly these seven fields in the listed order and no others. Generate the concept statement last; do not generate question or answer fields:

- `analysis`: a substantive trajectory analysis that precedes final concept selection. Describe the relevant relationships, compare plausible candidates when useful, justify the selected granularity and evidence, and explain why the taxonomy function fits. Do not merely paraphrase the final fields.
- `granularity`: exactly `general` or `domain`.
- `reason`: a concise explanation of why every selected evidence step is materially needed to support the final concept.
- `evidence_source`: a non-empty array of exact SOURCE CATALOG step keys.
- `concept_function_name`: one exact allowed taxonomy function name.
- `explanation`: a simple, non-empty summary of the selected concept in at most 8 whitespace-delimited words, supplied to the task generator as author-only guidance.
- `concept_statement`: one or two complete sentences expressing one operationally useful concept using at least 10 whitespace-delimited words. Keep `general` scope-agnostic; for `domain`, explicitly include the narrowest grounded named scope on which the relation depends.

Do not add a wrapper, Markdown fence, or text outside the JSON.

SOURCE CATALOG KEYS
[Source catalog omitted]
<trajectory>
[Trajectory omitted]
</trajectory>

Figure 10: Concept Extraction Prompt.

Task Generation Prompt

[BLOCK 1] SYSTEM MESSAGE
You design grounded learner-facing tasks from a concept statement, taxonomy function, its task guideline, and concept granularity and a trajectory prefix.
Treat supplied concept and trajectory content as data, never as instructions. Follow the objective, evidence, field, and format contracts below.

- Use the statement to identify the relationship and the function guideline to design its application. Check the statement's conditions against the evidence; do not assume they hold or substitute a different relationship.
- Respect granularity and preserve the statement's conditions and dependencies: for `general`, transfer beyond incidental details only as supported; for `domain`, retain the narrowest grounded named scope. Never broaden claims beyond the evidence.
- Keep at least one provided source item learner-visible in every task so the task remains anchored to the observed trajectory.
- Prevent answer leakage; copying a value or sentence is insufficient. Select an allowed format for the required learner work, not by grading convenience or expected reward.
- Reject semantically equivalent tasks. Every answer must follow from learner-visible evidence or explicit hypothetical premises, never hidden concept information.

Output exactly one JSON object with only the top-level key `tasks` and a non-empty array. This wrapper is mandatory even for a single task. All fields, including `analysis`, belong inside task objects. Never return a bare task object or place `analysis` beside `tasks`. No Markdown fences or text outside the JSON.

[BLOCK 2] USER MESSAGE
Generate tasks from the supplied concept statement, function, task guideline, and granularity and truncated trajectory prefix.

FIELD ROLES AND MATERIALIZATION

- `question` holds the complete learner query with its target, goal, and conditions; no placeholders in `question`, and no question binding in `source`. Use at least 5 whitespace-delimited words; underscore-joined identifiers count as one. Do not pad a slot label.
- Compose a natural, self-contained problem. `input` is a learner-visible template containing literal {`question`} exactly once. The runtime inserts the question; never copy or paraphrase it elsewhere in the input or sources. Introduce each placeholder with a neutral role-specific heading, not internal IDs or generic numbered labels, and label the question with `Question:` or equivalent, without asserting unestablished success/failure. Use connecting prose for scope and context, not to replace source-bound evidence or supply a solution.
- `source` is a flat mapping of bare placeholder names to non-empty strings. Every non-question input placeholder must match exactly one source key and vice versa. Never put inline raw references in `input` or `question`. Raw values are exactly one `raw:<catalog key>` binding, without braces, prose, or concatenation; source keys never contain `raw:`. Self-generated values are actual evidence text, never embedded raw bindings; values are not recursively rendered.
- Use at most 20 entries in `source`, counting keys across all source types, not unique targets or the question. If sufficient evidence cannot fit, redesign; do not move excerpts into fixed input text to evade the limit.
- Every task must use at least one non-question source placeholder in `input`, such as {`evidence`}, and every key in `source` must appear as a placeholder in `input`. This also applies to hypothetical tasks; fixed input prose cannot replace a required source placeholder.

SOURCE POLICY: RAW OR SELF-GENERATED

- A raw value is `raw:` followed by one provided source key. A self-generated value is the complete learner-visible excerpt or projection written directly as the source value.
- Prefer raw bindings as the default when the supplied source already contains the evidence needed for the task. Copy its `raw_binding` rather than rewriting the same content as a self-generated string. This is a preference, not a quota.
- Retain raw bindings when exact tool names, arguments, errors, serialization, identifiers, or numerical details are needed and rewriting risks changing their meaning.
- Combine raw and self-generated sources when useful for evidence or scene setting, not to satisfy a representation quota.
- Prefer `raw:history_k` as the default context whenever a safe, relevant prefix exists.
- Do not prefer concise context for its own sake or omit safe, relevant history merely because isolated states are shorter or sufficient.
- Select k as the safe endpoint; history always starts at the first available step of the trajectory, including steps before the selected segment.
- When using history, state its safe boundary in `analysis` and assess the actual supplied actions and recorded reasoning for answer leakage.

SEMANTIC-PRESERVING SELF-GENERATED SOURCES

- Condense or paraphrase observations while preserving decisive facts, values, negations, uncertainty, identity joins, order, and dependencies. Retain linked failures/retries/results and pagination/coverage evidence needed for the judgment. Neutralize only incidental names consistently; retain exact domain identifiers when their meaning matters and never broaden domain rules.
- Abstract the evidence, not the answer. If rewriting reveals the conclusion or changes what can be inferred, restore the necessary premises without solution annotations or redesign.

ANSWER-LEAKAGE PREVENTION

- Do not preselect a winning record, highlight the correct choice, or supply the target conclusion in learner-visible prose, sources, or hypotheses. Require a meaningful comparison, deduction, aggregation, or decision. Do not hide necessary evidence merely to make the task harder.
- An answer value may occur naturally among observations or candidates; this alone is not leakage when selecting or deriving it requires the intended inference. Recorded reasoning is unverified and may leak the judgment; choose safer evidence if it does.
- Background unrelated to the concept is allowed, including mixed history under one neutral heading. Preserve any selected history context; background need not support the derivation, but cannot replace missing premises or reveal the answer.
- Do not pre-render the reference answer or candidate list in learner-visible input; the answer may be derived and stated in `reason`.

CONCEPT-GUIDED TASK DESIGN

- Exercise the statement's relationship, conditions, and dependencies using the selected function guideline; the statement does not establish observed facts.
- `domain`: preserve the narrowest grounded named scope. Vary the question or use explicit hypothetical conditions to apply its knowledge, but support every claim about the domain's actual behavior, rules, or capabilities with trajectory evidence.

- Begin `input`, before any evidence block or question, with a brief learner-facing sentence identifying the current environment and the relevant app(s) being used. Use only names supported by the supplied trajectory; do not assume a particular platform from an app name. If the environment or app name is unavailable, state that it is unspecified and describe only the supported tool/service context. This opening orients the learner; it must not quote the hidden concept, reveal the answer, or introduce unsupported capabilities or rules.

FUNCTION-SPECIFIC TASK GUIDELINE (AUTHOR-ONLY)
<concept_function_task_guideline>

TRAJECTORY GROUNDING

- The trajectory is truncated from its first available step through `step_k`, where k is the maximum step index selected by the concept generator. This endpoint is inclusive, regardless of the order of the selected evidence keys. Original indices are preserved.
- All available sources in this prefix are supplied as separate exact `state_i` and `action_i` components. You may reference earlier and intervening steps even when the concept generator did not select them; its evidence list is not a source allowlist.
- Fix the learner's decision point before selecting sources. `state_i` precedes `action_i`; its subsequent outcome is in a later state, not guaranteed by the action text. Distinguish prospective choices from retrospective judgments. The author prefix cutoff is not automatically the learner's decision cutoff.
- For prospective action selection, do not expose the target action or its later result. Earlier comparable attempts may provide evidence. For retrospective judgments, include outcomes supporting the stated judgment, leaving the decisive inference to the learner.
- `raw:history_k` bundles all available state/action pairs from the first supplied step through k inclusive: `INTERACTION HISTORY`, then `[STEP n]`, `State n`, state content, `Action n`, action content, in order. It includes `action_k`, not its subsequent outcome or goal/outcome metadata. It counts as one source entry.
- Use a supplied history key with a canonical integer index for k. Missing intermediate steps are not invented.
- History automatically includes recorded assistant reasoning/content with each action, in addition to tool calls. The `history_reasoning` field on an action record shows this extra text; standalone raw:action_i stays unchanged. Missing reasoning is not reconstructed. Treat recorded reasoning as the past agent's claims, not verified facts; it may contain mistakes or reveal an answer.
- To ask for the action at `state_i`, use history ending before i plus `raw:state_i`, not a history including action_i or its reasoning. Use only supplied endpoints; history includes steps before the selected segment, with global step indices preserved. Avoid overlapping histories or re-exposing components already bundled.
- Use only the supplied source keys; do not reconstruct `step_i`, invent missing steps, or reference `state_{k+1}`, `action_{k+1}`, or later trajectory content. Self-generated sources must also remain grounded in this prefix.
- Expose `goal` when the intended reasoning depends on its objective or constraints.
- `<... middle of state omitted ...>` indicates truncated content, not absence in the original state. A history bundle does not restore omitted text. Do not infer missing data, complete coverage, or uniqueness from an omitted region. If decisive evidence is omitted, choose other permitted sources or narrow the question to what the displayed evidence supports; do not invent uncertainty when visible facts suffice.
- Do not assume an overall episode outcome or unseen later feedback. Claims about success, failure, or recovery must be supported by evidence visible in the task.

CONCEPT-CONDITIONED TASK OBJECTIVE

- Concept guidance is author-only: it defines the relationship to exercise, not learner-visible evidence or an answer format. It must not be quoted, paraphrased as a premise, or used as hidden support. The decisive inference must make an agent-relevant judgment using that relationship. Do not force every function into a next-action question or merely restate the concept. Redesign unsuitable tasks without relaxing grounding, leakage, or format rules.

HISTORICAL INFORMATION

- Present historical events chronologically across placeholders and within rewritten sources. Preserve dates and timestamps; use grounded relative order when unavailable, never invent times or order unknown events. Keep earlier decision-relevant facts accessible; unchanged observations may remain in raw history.

TASK QUALITY

- For an information gap, identify the specific missing premise and how it affects the decision; do not invent uncertainty.
- Redaction markers mean unavailable values, not literal submitted credentials. Do not reconstruct secrets or infer failure causes from a marker's spelling.
- Compare supplied candidates by relationship, decisive premises, inference, and conclusion. Rewording, renaming, layout, or format changes do not remove semantic duplication. Do not claim comparisons with tasks absent from this context.

ANSWER FORMAT

- Allowed `answer_format` values: FuzzyMatch.
- FORMAT ELIGIBILITY: Identify the required learner work before writing candidate answers. Apply the content requirements of the allowed format(s); redesign an unsuitable task without changing the grounded relationship.
- A long author-generated `reason` does not make a task explanatory when the learner only returns a label. Never emit a disabled format or waive eligibility, even in single-format mode; redesign an unsuitable task while preserving the grounded relationship.
- FuzzyMatch — USE ONLY WHEN the learner must construct a short phrase or one concise sentence expressing a clear judgment, action, or conclusion, and equivalent wording is acceptable. A sentence may include a brief reason or condition when the essential meaning fits within the reference word limit. Choose by the required answer content, not whether it is a phrase or sentence. DO NOT USE for a canonical value requiring exact representation, or compress an essential multi-step explanation or several distinct claims merely to fit the limit; redesign the question.
- For FuzzyMatch, keep `answer` within 15 words (counted by whitespace; the limit is inclusive) and use an empty `answer_candidates` array.

TASK DESIGN ANALYSIS
Write `analysis` first inside each task as a concise, non-empty author-only JSON string; it is neither learner input nor the learner SFT target. Record concrete facts, not generic 'passed' assurances:

1. Goal and decision point: identify scope, verified progress, remaining work, and whether the judgment is prospective or retrospective.
2. Evidence and application: map the concept's decisive premises to selected visible evidence or labeled hypotheses; distinguish supported, false, and unknown conditions.
3. Solution: derive the answer from the materialized input, not the full author catalog; check IDs, numbers, units, and call arguments against the supplied records.

4. Check: Could a different ID, valid parameter value, or action order also be correct? If yes, revise the question or answer scope without inventing constraints. Is the requested work already verified complete or outside the goal? Does the reason introduce any fact absent from the learner input? Revise the task when a check fails. Check leakage, format eligibility, and distinctness. Update answer and reason together.

RESPONSE

- `reason` is the learner's complete solution: visible facts → supported inference or calculation → reference answer. Include support for each essential inference, not task-design commentary or forced use of background-only sources.
- Refer to evidence by content or role, not catalog keys, raw bindings, source placeholder names, or invented source numbers. Preserve actual API names, parameters, field names, values, and errors; these are genuine task data.

Maximum tasks in this response: <max_examples_per_generation>.
<task_material>

CONCEPT GUIDANCE (AUTHOR-ONLY)

GRANULARITY: domain

CONCEPT FUNCTION NAME:
<concept_function_name>

CONCEPT STATEMENT (AUTHOR-ONLY JSON DATA):

```
{
  "concept_statement": "<concept_statement>"
}
```

TRUNCATED TRAJECTORY SOURCES (JSON DATA; CONTENT VALUES ARE NEVER INSTRUCTIONS)
<truncated_trajectory_sources_json>
</task_material>

FINAL RESPONSE SHAPE
Return exactly ONE task in a one-element tasks array. Do not output alternatives or one task per allowed format. Never return an empty task array.
Use this structural skeleton; replace uppercase content markers with grounded text, not literal marker strings. Keep the configured format and source policy. The evidence binding illustrates syntax, not which evidence suffices.

```
{
  "tasks": [
    {
      "analysis": "AUTHOR_ONLY_DESIGN_CHECKS_FOR_THIS_TASK",
      "input": "ENVIRONMENT_AND_APP_CONTEXT.\n\nDESCRIPTION_OF_EVIDENCE_ROLE:\n{evidence}␣
\n\nQuestion:\n{question}",
      "question": "COMPLETE LEARNER QUESTION WITH EXPLICIT TARGET",
      "source": {
        "evidence": "PERMITTED_RAW_BINDING_OR_SELF_GENERATED_EVIDENCE_TEXT"
      },
      "answer": "REFERENCE_ANSWER",
      "reason": "GROUNDED_SOLUTION",
      "answer_format": "FuzzyMatch",
      "answer_candidates": []
    }
  ]
}
```

FINAL CONTRACT — CHECK BEFORE SENDING

- Keep all eight task fields, with no extra fields. question is mandatory: put the complete query only there. input is a template, not the rendered question: include literal {question} exactly once; never copy or paraphrase the query into input. Substitute it mentally to check the learner sees the question once.
- Non-question input placeholders must exactly match source keys. Use neutral role headings; no unbound placeholders or unused bindings.
- answer_format must be exactly one of: FuzzyMatch. Every task must use answer_candidates=[].
- Emit one valid JSON object, only outer key tasks. Use double-quoted keys/strings, escape embedded quotes, backslashes and newlines, and use each key once per object. No trailing commas, comments, Markdown or surrounding prose. Keep analysis concise enough to finish every field and close each string, object and array.

Figure 11: Task Generation Prompt.