MISHAP-BENCH: A HALLUCINATION BENCHMARK FOR LARGE AUDIO-LANGUAGE MODELS

Anonymous authors
Paper under double-blind review

ABSTRACT

Large audio-language models (LALMs) produce fluent responses about audio but often hallucinate by making plausible yet ungrounded claims. Existing audio hallucination benchmarks mainly measure response correctness, leaving it unclear whether an LALM hallucinates or simply fails to understand the audio. We challenge correctness-based evaluation by defining two hallucination categories: (i) *context*, where claims are not grounded in the audio; and (ii) *knowledge*, where claims about audio-related topics lack support from externally verifiable facts. We introduce MISHAP-Bench, a comprehensive benchmark with 12,000 challenging open-ended question–audio pairs and a rigorous evaluation pipeline covering both categories. To evaluate open-ended responses, we propose a groundedness judge that uses reference rubrics and judge prompts guided by human annotations. We extensively evaluate ten state-of-the-art LALMs and show that hallucination remains substantial. Even a frontier model such as Gemini 3.7 Flash reaches a hallucination rate of 36.5%. We further adapt and benchmark four mitigation methods from multiple domains for LALMs. Despite some improvements, effective hallucination mitigation remains an open challenge. Finally, we call on the community to evaluate hallucination and benchmark mitigation methods with MISHAP-Bench. Link to our anonymous project page and code.

1 INTRODUCTION

Large audio-language models (LALMs) extend text-only LLMs to speech, environmental sound, and music, enabling transcription, acoustic-scene description, and audio question answering (Tang et al., 2024; Chu et al., 2024). Yet LALMs can hallucinate by presenting claims unsupported by the audio or externally verifiable facts. For text-only LLMs, hallucination has been studied through truthfulness questions (Lin et al., 2022), human-annotated detection benchmarks (Li et al., 2023), and claim-level verification against reliable sources (Min et al., 2023). These approaches rely on textual and factual evidence, leaving the audio itself unexamined. This is a fundamental limitation for LALMs, which are designed to process audio. Without considering the acoustic input, such approaches cannot determine whether an LALM response is grounded in the audio.

Audio provides heterogeneous evidence: speech includes words and prosody, environmental recordings contain sound events and temporal relations, and music conveys instrumentation, rhythm, mood,




Figure 1: Comparison of prior benchmarks and MISHAP-Bench. Prior benchmarks score responses to closed-ended binary or multiple-choice questions by correctness, so unsupported claims can still be marked correct. MISHAP-Bench instead uses open-ended questions covering context and knowledge hallucinations and evaluates whether responses are grounded in the relevant evidence.

Reviewers: please read the Reviewer Guidelines (iclr.cc/Conferences/2027/ReviewerGuidelines) and the AI Policy for Reviewers (iclr.cc/Conferences/2027/AIPolicyForReviewers). If you used AI to expand, edit, or polish your review, please provide the input text to the LLM. Better still, consider skipping the LLM and submitting your original text: we, and the authors, are much more interested in your unedited thoughts than in what an LLM has to say. AI-assisted or not, you are putting your name and reputation behind your review: LLM-generated falsehoods, hallucinations or misrepresentations are subject to disciplinary action, which may include desk-rejecting all papers you have authored.

genre, and style (Gemmeke et al., 2017; Huang et al., 2022; Tang et al., 2024). Since each domain encodes different attributes, LALMs may hallucinate words, events, or musical properties. For instance, a model may report two cat meows in a clip containing only background noise, or claim that the song in the input audio won an award it never received. The former concerns the audio context, which text-only hallucination benchmarks do not assess because text-only LLMs receive no audio. The latter concerns external knowledge about the input audio. LALMs therefore require a dedicated benchmark covering both context and knowledge hallucinations.

Audio-language evaluation has begun using open-ended questions to reflect how users interact with LALMs (Yang et al., 2024b). However, recent audio hallucination benchmarks have relied only on binary or multiple-choice questions with correctness-based scoring (Cheng et al., 2025; Zhao et al., 2026). Such scoring may penalize uncertainty while overlooking unsupported details in an otherwise correct response. Hence, answer correctness is not a reliable measure of hallucination in LALMs.

We therefore define audio hallucination through *groundedness*: presenting information as fact without support from the relevant evidence. We distinguish *context hallucinations*, where claims are unsupported by the audio, from *knowledge hallucinations*, where claims about audio-related topics lack support from externally verifiable facts. On this basis, we introduce `MISHAP-Bench`, a comprehensive benchmark with 12,000 challenging open-ended question–audio pairs across audio domains, and a rigorous evaluation pipeline. Each question is deliberately designed to induce hallucination by prompting the model to provide a plausible but unsupported response. Our groundedness judge then incorporates human annotations to classify each response as grounded or hallucinated. Figure 1 contrasts the two approaches: prior benchmarks may accept a response as correct even when it contains unsupported details, whereas `MISHAP-Bench` uses open-ended questions and rubrics to evaluate the complete response, identifying unsupported claims while accepting grounded uncertainty.

We evaluate ten state-of-the-art (SOTA) LALMs spanning proprietary and open-weight models and show that hallucination remains substantial. We further benchmark four mitigation methods for LALMs, one developed for audio and three adapted from other domains. Although some methods reduce hallucination, none fully addresses the problem. These findings leave hallucination mitigation as an open problem and motivate the community to evaluate hallucination and benchmark mitigation methods with `MISHAP-Bench`. To summarize, we list our contributions as follows:

- We challenge correctness-based audio hallucination evaluation and define two categories: *context hallucination*, where claims are not grounded in the audio, and *knowledge hallucination*, where claims about audio-related topics lack support from externally verifiable facts.
- We introduce `MISHAP-Bench`, a comprehensive benchmark with 12,000 challenging open-ended question–audio pairs spanning music, sound, and speech, along with a rigorous evaluation pipeline.
- To reliably evaluate open-ended responses, we propose a groundedness judge with reference rubrics and category-specific judge prompts guided by human annotations.
- Our extensive evaluation of ten SOTA LALMs shows that hallucination remains substantial, with Gemini 3.7 Flash reaching a hallucination rate of 36.5%. We further benchmark four existing mitigation methods, showing that hallucination mitigation remains an open problem for LALMs.

2 Related Work

Large audio-language models. LALMs build on text-only LLMs to process audio and generate natural-language responses (Luo et al., 2026). They typically pair an audio encoder with an adapter that maps acoustic features into the LLM's embedding space. (Chu et al., 2024; LLM-Core Xiaomi, 2025; Wang et al., 2026). Qwen2.5-Omni (Xu et al., 2025) and Audio Flamingo 3 (Ghosh et al., 2025) use Whisper-derived encoders (Radford et al., 2023), while Kimi-Audio (KimiTeam et al., 2025) combines discrete semantic tokens with continuous acoustic features. These audio representations provide information beyond transcribed words, including prosody and non-speech events.

Audio hallucination benchmarks. Prior hallucination benchmarks (Kuan et al., 2024; Ghosh et al., 2024; Kuan & Lee, 2025; Kim et al., 2025) evaluate specific aspects of audio understanding, including object presence, compositional relations, temporal order, and cross-modal consistency. AHa-Bench (Cheng et al., 2025) covers semantic, acoustic, and semantic-acoustic hallucinations primarily through binary questions. It uses an LLM to map responses to *"Yes"*, *"No"*, or *"Unknown"* for comparison with reference labels. HalluAudio (Zhao et al., 2026) also relies mainly on binary




Figure 2: Overview of MISHAP-Bench. It consists of 3,000 audio clips across music, sound, and speech; 12,000 open-ended questions targeting context and knowledge hallucinations; an evidence-based groundedness judge; and four inference-time mitigation methods.

and multiple-choice questions, using keyword matching and other normalization rules to extract answers for reference-based scoring. However, these evaluations emphasize answer correctness on closed-ended questions but do not independently verify claims in the generated explanations.

Hallucination mitigation for LALMs. Inference-time contrastive decoding offers a lightweight way to reduce hallucination without retraining. AAD was developed specifically for LALMs and contrasts predictions with and without audio context (Hsu et al., 2025). VCD (Leng et al., 2024), MTI (Yang et al., 2026), and DoLa (Chuang et al., 2024) were originally proposed for vision-language models or LLMs. These methods adjust next-token probabilities by contrasting standard predictions with those obtained from perturbed inputs, modified prompts, or intermediate layers. Recent work adapts them to LALMs and finds that their effects vary across tasks and models (Lin et al., 2026). However, they are evaluated mainly through correctness-based benchmarks or object-hallucination tests.


3 MISHAP-BENCH

To operationalize our definition of hallucination, we introduce MISHAP-Bench, an open-ended benchmark that measures whether claims in LALM responses are supported by relevant evidence. It unifies question generation, groundedness evaluation, and inference-time mitigation in a single protocol, enabling separate evaluation of context and knowledge hallucinations across audio domains.

Overview. We begin with a high-level overview of MISHAP-Bench in Figure 2, which consists of four main components: audio clips, open-ended questions, the groundedness judge, and mitigation methods. We curate 3,000 audio clips from six established audio datasets, balanced across music, sound, and speech, and associate each clip with an audio description. We generate four questions per clip using seven hallucination-inducing strategies, yielding 12,000 questions evenly divided between context and knowledge categories. Given a question–audio pair, an LALM produces a response. The groundedness judge then evaluates the response against the grounding evidence using a judge prompt. When needed, it retrieves additional evidence through agentic web search before returning a grounded or hallucinated verdict. Finally, we adapt and evaluate four inference-time mitigation methods from different domains for LALMs. We describe each component in the following subsections.

3.1 AUDIO CURATION

We curate each audio instance as a pair comprising a clip and its associated description from the source dataset. The clip is presented to the LALM, while the description provides audio-derived evidence for question generation, reference rubric construction, and groundedness evaluation. To cover different forms of audio content, we include music, sound, and speech, which respectively emphasize musical content, acoustic events, and spoken language. We select 1,000 clips per domain, resulting in 3,000 clips in total. This equal allocation prevents any domain from dominating the aggregate results and enables domain-level comparisons with matched sample sizes.



(a) Audio domain and source distribution.

(b) Question category and strategy distribution.

Figure 3: Audio and question composition of MISHAP-Bench.

We draw these clips from six established datasets commonly used by the audio community for model development and evaluation (Yang et al., 2025; Chen et al., 2026). Each dataset is released with documented annotations or metadata, providing traceable provenance for the selected clips. We use two sources per domain to reduce dependence on any single collection or annotation process. Music clips come from the Song Describer Dataset (Manco et al., 2023) and Mridangam Stroke 1.5 (Anantapadmanabhan et al., 2013); sound clips come from Clotho v2.1 (Drossos et al., 2020) and FSD50K (Fonseca et al., 2022); and speech clips come from LibriSpeech (Panayotov et al., 2015) and Common Voice 22.0 (Ardila et al., 2020). Figure 3a summarizes the allocation across these sources.

The associated descriptions retain the format provided by each dataset: human-written captions for Clotho and the Song Describer Dataset, uploader-written descriptions for FSD50K, transcripts for LibriSpeech and Common Voice, and stroke and tonic metadata for Mridangam.

3.2 Open-ended question generation

Closed-ended questions constrain LALM responses to predefined answers. We therefore design MISHAP-Bench with open-ended questions that require LALMs to formulate their own responses (Huang et al., 2025; Wang et al., 2025). Existing audio hallucination benchmarks (Cheng et al., 2025; Zhao et al., 2026) rely on straightforward, template-based questions, which often produce brief responses with few claims to assess. To induce hallucination more effectively, we tailor adversarial questions to each audio clip. Each question either embeds a misleading premise or requests specific information without sufficient evidence. The response then reveals whether the model follows the question's framing or restricts its claims to supported information.

We condition Nemotron 3 Nano Omni (NVIDIA, 2026) on each audio clip, its source-provided description, and a target hallucination category to generate two questions for that category. *Context questions* target claims about the clip and are assessed against audio evidence, whereas *knowledge questions* target claims about topics related to the audio and are assessed against external factual evidence. Across 3,000 clips, we generate 6,000 questions per category, resulting in 12,000 question–audio pairs in total. Figure 3b shows the split across three context and four knowledge strategies.

Context questions. Context questions embed a plausible premise that conflicts with the clip. This framing encourages a model to answer before checking the premise, leading it to repeat or elaborate on unsupported audio content. We construct a *Contradicted Premise* by altering an observed attribute or relation: a question asks how many drum-kit hits are audible even though the description attributes the percussive sounds to fingerstyle guitar playing. An *Absent Premise* instead introduces nonexistent content, as in a question about the number of cat meows in a doorbell-only clip. *False Negation* denies observed content by claiming that a speaker never names William even though the transcript does. A grounded model should instead identify the mismatch and respond based on the audio evidence.

Knowledge questions. These questions remain tied to the audio topic but request information beyond the clip. They induce hallucination in two ways: uncertainty and misinformation. *Niche Specifics* asks for an obscure factual detail, such as the exact date of the atomic strike following Hiroshima. *Unknowable Provenance* requests details that the audio cannot establish, like who recorded a glass-shattering clip and which microphone was used. Both may lead the model to replace uncertainty or missing evidence with an unsupported answer. The other two strategies place false information directly in the question. *False Authority* cites the invented "Mridangam Rhythm Atlas", while *False Premise* describes Alberta as a US state, testing whether the model accepts and propagates either claim. For False Authority, we check invented source names against real-world sources during construction




Figure 4: Groundedness judge pipeline. ① The judge receives the inputs. ② It retrieves web evidence when needed through agentic search. ③ It returns a grounded or hallucinated verdict.

to avoid accidental name collisions. A grounded model should provide only factually supported information, reject false premises, or acknowledge that a requested detail cannot be established.

Although adversarial, these questions do not require a hallucinated response. A grounded model can provide a supported answer, correct the premise, or state that the requested information cannot be established. Complete examples of all seven strategies are provided in Figure 7 of Appendix A.2.

3.3 Groundedness Judge

Evaluating hallucination in open-ended LALM responses requires checking every claim against the relevant evidence, making exhaustive human evaluation impractical. We therefore propose a groundedness judge that is not tied to a particular text LLM. In this work, we use Qwen3.8-27B (Qwen Team, 2026b) as the judge model. The judge assigns each response a *grounded* or *hallucinated* verdict. To align these automated verdicts with human judgments, we first collect human annotations, which guide the construction of the reference rubrics and judge prompts and provide the in-context examples. As illustrated in Figure 4, ① the judge receives a prompt containing the question, LALM response, audio description, and question-specific reference rubric. ② For knowledge questions, the judge can retrieve external evidence through agentic web search before ③ returning its verdict.

To obtain high-quality human annotations, we recruit seven multilingual graduate researchers, including four doctoral researchers and three master's-level researchers. We sample 1,000 responses across the evaluated LALMs and collect independent annotations under a common protocol. Each annotation requires examining the complete response claim by claim against the relevant evidence. Annotators must identify unsupported details even when the main answer is correct and distinguish hallucination from premise correction or explicit uncertainty. Although the final verdict is binary, reaching it requires careful evidence verification. The resulting labels allow us to measure human–human agreement and provide the human reference for assessing judge–human agreement.

Open-ended questions can be answered in multiple grounded ways: a response may answer directly, correct a false premise, or acknowledge insufficient evidence. Since a single reference answer cannot capture this range, we construct question-specific reference rubrics whose criteria are refined through comparison with human judgments. We first prompt MiniMax M3 (MiniMax, 2026) with the question, the question strategy, and the audio description to produce an initial rubric. Each rubric follows the template *"Hallucinated if <...>. Grounded if <...>."*, with the first clause specifying unsupported behavior and the second describing valid grounded responses. We then apply the judge to the annotated subset and inspect disagreements with human labels to identify criteria that exclude supported responses or permit unsupported claims. As an illustrative example, consider a clip described as solo piano and a question asking which violin technique is used. A rubric that requires an explicit correction of the false premise could exclude the response *"I cannot identify a violin technique from this clip."*. A human *grounded* label would motivate broadening the rubric to accept explicit uncertainty alongside premise correction, while retaining the restriction against invented violin details. We use such disagreements to revise the rubric formulation, regenerate the rubrics, and reassess judge–human agreement. Through this iterative process, human judgments guide the criteria used to evaluate responses across the benchmark.

The reference rubric specifies what counts as grounded for an individual question, whereas the judge prompt determines how the judge applies this criterion to the complete response. Since context and

knowledge questions rely on different evidence, we construct a separate prompt for each category. Each prompt presents the four inputs described above and directs the judge to examine every claim. Human annotations guide these prompts in two ways: they inform revisions to the decision rules and provide examples of how to apply them. We first inspect judge–human disagreements on the annotated subset to identify unclear or incomplete rules, revise the prompts, and reassess agreement. These revisions clarify how the judge examines individual claims and selects the appropriate evidence. Each prompt also includes a fixed set of three grounded and three hallucinated examples drawn from the human-annotated subset for *in-context learning* (Dong et al., 2024; Jung et al., 2025). This balanced set represents both verdicts and illustrates how human annotators apply the rubric to varied response patterns. For knowledge questions, we also enable agentic web search when the required evidence is absent from the audio description. The judge formulates search queries, assesses the retrieved evidence, and searches again when further evidence is needed before assigning its verdict. The complete prompts are provided in Appendix A.3.

To quantify how often each LALM hallucinates, we apply the resulting groundedness judge to all of its evaluated responses and compute the **hallucination rate**:

$$\mathrm{HR} = \frac{N_{\mathrm{hallu}}}{N} \times 100\%,$$

where N_{hallu} is the number of responses from that LALM classified as hallucinated and N is the total number of responses. The hallucination rate therefore measures how frequently each LALM produces hallucinated responses across the benchmark.

3.4 Hallucination Mitigation

To investigate whether existing mitigation methods reduce hallucination, we integrate four contrastive decoding methods into LALMs: the audio-specific AAD (Hsu et al., 2025); VCD (Leng et al., 2024) from image domain; and MTI (Yang et al., 2026) and DoLa (Chuang et al., 2024) from text domain.

Contrastive formulation. Contrastive decoding adjusts token scores by contrasting an original prediction with a reference prediction. At step t, the original logits are $\mathbf{z}_t = f_\theta(a, q, y_{<t})$, conditioned on audio a, question q, and response prefix $y_{<t}$. We combine these with reference logits $\mathbf{z}_t^-$:

$$\widetilde{\mathbf{z}}_t = \gamma \mathbf{z}_t - \delta \mathbf{z}_t^-,$$

where $\gamma > 0$ and $\delta \geq 0$ weight the original and reference logits. This subtraction penalizes tokens favored by the reference branch. The methods differ in $\mathbf{z}_t^-$ construction and when they apply contrast.

Audio-Aware Decoding (AAD). An LALM may generate plausible content from its language prior while neglecting the audio. AAD addresses this failure by removing the audio a from the input, yielding $\mathbf{z}_t^- = f_\theta(q, y_{<t})$. Without acoustic information, the model relies on the question and response prefix. AAD contrasts this text-only prediction with the original audio-conditioned prediction to identify the information contributed by the audio.

Visual Contrastive Decoding (VCD). VCD contrasts predictions from clean and corrupted images (Leng et al., 2024). It assumes that corruption alters predictions supported by the input signal while predictions driven by the language prior remain stable. We adapt it to LALMs by applying Gaussian forward diffusion to obtain a corrupted audio $\widetilde{a}$ and formulating $\mathbf{z}_t^- = f_\theta(\widetilde{a}, q, y_{<t})$. This contrast distinguishes predictions supported by clean audio from those that persist under corruption.

Minimal Test-Time Intervention (MTI). MTI avoids perturbing confident predictions by restricting contrast to uncertain steps (Yang et al., 2026). It treats a step as uncertain when the entropy $\mathcal{H}(\mathbf{p}_t)$ exceeds a threshold τ, where $\mathbf{p}_t = \mathrm{softmax}(\mathbf{z}_t)$ is the next-token distribution. At such steps, we append a temporary instruction ι to ignore the audio after $y_{<t}$ and compute $\mathbf{z}_t^- = f_\theta(a, q, y_{<t} \oplus \iota)$, where $\oplus$ denotes token concatenation. Otherwise, we decode directly from $\mathbf{z}_t$. This contrast reduces the influence of the language prior at uncertain steps. However, entropy measures uncertainty rather than audio grounding, so confident hallucinations may remain uncorrected.

Decoding by Contrasting Layers (DoLa). DoLa contrasts final- and intermediate-layer predictions, motivated by the observation that factual information becomes more distinct in later layers (Chuang et al., 2024). For each candidate intermediate layer $\ell \in \mathcal{L}$, we apply the final normalization and language-modeling head to its hidden representation, obtaining logits $\mathbf{z}_t^{(\ell)}$ and distribution

$\mathbf{p}_t^{(\ell)} = \mathrm{softmax}(\mathbf{z}_t^{(\ell)})$. DoLa selects the layer whose distribution differs most from $\mathbf{p}_t$:

$$\ell_t^* = \arg\max_{\ell \in \mathcal{L}} \mathrm{JSD}\left(\mathbf{p}_t \,\|\, \mathbf{p}_t^{(\ell)}\right).$$

Here, JSD denotes the Jensen–Shannon divergence, and we formulate $\mathbf{z}_t^- = \mathbf{z}_t^{(\ell_t^*)}$. The resulting contrast emphasizes information that emerges in later decoder layers. However, DoLa leaves the audio unchanged and thus does not directly separate audio-grounded from language-driven information.

We thereby evaluate hallucination and its mitigation under a common protocol and provide a testbed for future mitigation methods.

4 Evaluation

We first assess the validity of groundedness-based evaluation by comparing hallucination rates from prior benchmark scorers, human annotators, and our groundedness judge. We then quantify hallucination across ten LALMs. Finally, we assess whether four mitigation methods reduce hallucination. Experimental settings and additional results are provided in Appendices B and E, respectively.

4.1 Validity of Groundedness-Based Evaluation

Setup. We compare `MISHAP-Bench` with two recent LALM hallucination benchmarks, AHa-Bench (Cheng et al., 2025) and HalluAudio (Zhao et al., 2026). From each benchmark, we sample 1,000 responses approximately evenly across the same eight open-weight LALMs: Qwen2-Audio Instruct (Chu et al., 2024), Qwen2.5-Omni (Xu et al., 2025), Kimi-Audio Instruct (KimiTeam et al., 2025), Audio Flamingo 3 (Ghosh et al., 2025), Step-Audio 2 mini (StepFun Audio Team, 2025), MiMo-Audio Instruct (LLM-Core Xiaomi, 2025), Qwen3-Omni Instruct (Qwen Team, 2025), and Covo-Audio (Wang et al., 2026). We evaluate all three subsets using human annotations and our groundedness judge. For AHa-Bench and HalluAudio, we additionally apply each benchmark's original scorer to its own responses and express the resulting scores as hallucination rates.




Figure 5: Evaluation of 1,000 responses per benchmark shows that `MISHAP-Bench` more effectively measures hallucination in LALMs.

Figure 5 reveals a large gap between correctness-based scoring and human judgments. On both AHa-Bench and HalluAudio, the original scorers produce substantially higher hallucination rates than human annotators, whereas our groundedness judge closely follows the human results. This discrepancy arises because correctness-based scorers can label grounded responses as hallucinated when they acknowledge uncertainty, correct a misleading premise, or provide an incomplete but supported answer. Its presence across both benchmarks suggests a general limitation of correctness-based evaluation rather than an artifact of a particular dataset. On `MISHAP-Bench`, humans and the groundedness judge again closely agree, but both identify considerably more hallucination. Thus, the judge does not systematically assign fewer hallucination labels. Instead, `MISHAP-Bench` uses open-ended questions designed to induce unsupported claims, which both humans and the judge identify as hallucinations. These results show that `MISHAP-Bench` measures hallucination more directly by distinguishing unsupported generation from other response errors. We further evaluate judge reliability through cumulative component ablations based on judge–human agreement in Appendix E.2, and examine its sensitivity to alternative reference-rubric and judge-prompt formulations in Appendix E.3.

4.2 Hallucination in Large Audio-Language Models

Setup. We use the eight open-weight models listed above and include two additional models. We evaluate the open-weight MiMo-V2.5 (Xiaomi MiMo Team, 2026) via an API due to computational constraints and access the closed-weight Gemini 3.7 Flash (Doshi, 2026) through its API.

No evaluated model is reliably grounded. Qwen2.5-Omni and Gemini 3.7 Flash achieve the lowest overall hallucination rates in Table 1, yet both hallucinate in more than 30% of their responses.

Table 1: Hallucination rates (%) of LALMs across audio domains and hallucination categories. Lower is better; best results are **bolded**.

Model	Music			Sound			Speech			
	Context	Knowledge	Overall ↓	Context	Knowledge	Overall ↓	Context	Knowledge	Overall ↓	Overall ↓
Open-Weight Model										
Qwen2-Audio Instruct	71.8	65.7	68.8	72.4	51.1	61.8	29.4	31.3	30.4	53.6
Qwen2.5-Omni	**56.8**	38.5	**47.6**	**50.6**	**15.2**	**33.0**	37.2	**18.1**	27.7	**36.1**
Kimi-Audio Instruct	70.5	62.3	66.4	71.8	32.2	52.0	30.9	35.4	33.1	50.5
Audio Flamingo 3	77.7	79.2	78.4	69.4	46.5	58.0	48.5	63.8	56.2	64.2
Step-Audio 2 mini	85.2	80.9	83.0	76.0	63.9	70.0	58.0	66.8	62.4	71.8
MiMo-Audio Instruct	87.2	84.9	86.0	84.5	60.2	72.4	63.9	68.3	66.1	74.8
Qwen3-Omni Instruct	84.5	70.5	77.5	82.2	49.6	66.0	38.0	56.8	47.4	63.6
Covo-Audio	88.3	72.3	80.3	84.3	33.1	58.7	46.6	43.0	44.8	61.3
MiMo-V2.5	72.1	45.5	58.8	65.7	28.2	46.9	28.6	45.0	36.8	47.5
Closed-Weight Model										
Gemini 3.7 Flash	73.6	**35.2**	54.4	62.6	18.3	40.4	**9.5**	19.9	**14.7**	36.5




Figure 6: Response-stance distributions of LALMs on knowledge questions.

Despite their similar overall rates, their performance differs across domains: Qwen2.5-Omni performs better on music and sound, whereas Gemini performs better on speech. Strong performance in one domain can therefore offset weaknesses elsewhere in the overall score. For context questions in music and sound, every model hallucinates in more than half of its responses. This shared failure is consistent with models following the questions' plausible linguistic framing without adequately checking their premises against the nonverbal audio evidence.

The speech advantage is concentrated in context grounding. All ten models hallucinate most in music and least in speech overall, with sound in between. However, this ordering does not extend to knowledge hallucination. Every model has a higher context than knowledge hallucination rate in sound, whereas eight models show the opposite relationship in speech. Moreover, nine models hallucinate more on speech knowledge questions than on sound knowledge questions. Speech provides explicit lexical evidence for checking a question's premise, whereas music and sound require interpreting nonverbal acoustic structure. This may explain the context advantage, but recognizing what was said does not establish whether claims about related topics are factually supported. Stronger speech grounding therefore does not ensure reliable responses to knowledge questions.

Lower knowledge hallucination is partly due to abstention. Figure 6 shows that most models abstain least in music, while every model endorses false premises most often in this domain. Combined with their high knowledge hallucination rates, this suggests that models often accept plausible musical claims without recognizing insufficient support. In sound and speech, Qwen2.5-Omni achieves low hallucination rates while abstaining on roughly three-quarters of knowledge questions. Abstention is appropriate when evidence is insufficient, but it may also leave answerable questions unanswered and does not establish stronger factual knowledge. However, abstention does not fully capture how models respond: Qwen2.5-Omni and Gemini 3.7 Flash abstain at nearly identical rates in music, yet Gemini asserts answers more often and endorses false premises less often. Similar knowledge hallucination rates can therefore reflect different response behaviors, including how often models abstain, assert answers, or endorse false premises. Lower acceptance of false premises is desirable, although more asserted answers imply greater usefulness only when their claims are grounded.

Table 2: Hallucination rates (%) of LALMs under four mitigation methods. W/O denotes the unmitigated baseline. Lower is better; best results are **bolded**. Full results are provided in Table 8.

	Music			Sound			Speech			
Method	Context	Knowledge	Overall ↓	Context	Knowledge	Overall ↓	Context	Knowledge	Overall ↓	Overall ↓
Qwen2.5-Omni										
W/O	56.8	38.5	47.6	50.6	15.2	33.0	37.2	18.1	27.7	36.1
AAD	54.2	**35.1**	44.6	64.4	**16.1**	40.3	**25.2**	20.1	**22.7**	35.9
VCD	63.4	39.3	51.4	58.9	16.4	37.7	29.8	22.1	25.9	38.3
MTI	**50.3**	36.1	**43.2**	**50.0**	16.4	**33.1**	41.8	**19.9**	30.9	**35.7**
DoLa	57.6	38.9	48.2	54.1	17.2	35.7	38.6	24.4	31.5	38.5
Kimi-Audio Instruct										
W/O	70.5	62.3	66.4	71.8	32.2	52.0	30.9	35.4	33.1	50.5
AAD	**50.6**	**39.8**	**45.2**	**49.5**	**15.5**	**32.5**	**23.4**	**17.9**	**20.6**	**32.8**
VCD	71.2	58.8	65.0	69.5	31.9	50.8	29.2	35.2	32.2	49.3
MTI	68.2	57.7	62.9	71.5	27.6	49.6	48.9	33.8	41.3	51.3
DoLa	62.4	59.6	61.0	57.8	30.9	44.3	31.2	33.9	32.5	45.9
MiMo-Audio Instruct										
W/O	87.2	84.9	86.0	84.5	60.2	72.4	63.9	68.3	66.1	74.8
AAD	**67.0**	**61.7**	**64.4**	**72.4**	**36.7**	**54.5**	**51.0**	**47.0**	**49.0**	**56.0**
VCD	87.4	86.3	86.9	85.5	61.4	73.5	59.1	67.0	63.0	74.5
MTI	88.8	84.0	86.4	86.5	55.0	70.7	68.4	69.1	68.7	75.3
DoLa	88.5	85.8	87.2	84.2	59.4	71.8	66.8	75.7	71.2	76.7

4.3 Mitigating hallucination in large audio-language models

Setup. We assess AAD, VCD, MTI, and DoLa on the eight open-weight LALMs in Section 4.1. These methods require logits and decoding control, plus intermediate hidden states for DoLa. We exclude MiMo-V2.5 and Gemini 3.7 Flash because their evaluation APIs do not provide this access.

Table 2 compares four hallucination mitigation methods. AAD provides the broadest improvements, reducing overall hallucination across all eight models and both categories in every domain for Kimi-Audio and MiMo-Audio. These gains are consistent with suppressing plausible continuations that lack support from the audio. However, Qwen2.5-Omni's small overall improvement reflects uneven effects: reduced context hallucination in speech is offset by an increase in sound. VCD is less consistent overall, although both AAD and VCD reduce context hallucination in speech across all models. As discussed earlier, speech provides explicit lexical evidence, whereas music and sound require interpreting nonverbal cues. VCD's weaker results in these domains may reflect corruption altering these cues without reliably separating supported evidence from plausible alternatives. Moreover, both methods increase knowledge hallucination in Qwen2.5-Omni's speech responses despite reducing context hallucination, illustrating that improved audio grounding does not necessarily extend to claims that require external evidence. MTI generally underperforms the baseline, with knowledge improvements in several settings accompanied by worse context grounding. This suggests that uncertainty does not reliably distinguish unsupported claims from grounded responses. DoLa benefits Kimi-Audio and Step-Audio 2 mini mainly in music and sound, but, like MTI, increases context hallucination in speech for every model. This shared failure suggests that methods adapted from text generation may disrupt the use of acoustic evidence in speech responses, even when they improve responses about nonverbal audio. AAD is therefore the most promising method among those evaluated, but effective mitigation across models, domains, and hallucination categories remains unresolved. Full results are provided in Table 8 of Appendix E.

5 Conclusion

We challenge correctness-based evaluation and introduce `MISHAP-Bench`, with 12,000 open-ended question–audio pairs and a groundedness judge with reference rubrics and judge prompts guided by human annotations. Across ten LALMs, we find that no model is reliably grounded, with even Gemini 3.7 Flash reaching a 36.5% hallucination rate. All models hallucinate most on music and least on speech. Context hallucination exceeds knowledge hallucination for every model in sound, while eight show the reverse in speech. Among four mitigation methods, the audio-native method reduces overall hallucination across all eight models, but those adapted from vision and text yield trade-offs, and none generalizes across models, domains, and categories. `MISHAP-Bench` remains limited to English questions, description-based audio evidence, and inference-time mitigation for models with accessible decoding internals. We call on the community to extend `MISHAP-Bench` across these settings and use it to advance hallucination evaluation and mitigation.

AI USE STATEMENT

In this work, we used generative AI tools to polish the manuscript prose, assist with code development, and generate synthetic benchmark data, including questions and their reference rubrics. Reference discovery and citation preparation were conducted without generative AI assistance. The authors reviewed and revised all AI-assisted text, inspected and tested the AI-assisted code, and verified the generated data before using them in the experiments. We take responsibility for the final content of this work, including all text, claims, code, and artifacts produced with the aid of generative AI.

ETHICS STATEMENT

This work aims to improve the reliability of large audio-language models by identifying responses that are not grounded in audio or external evidence. `MISHAP-Bench` uses audio from established research datasets, whose sources and selection criteria are documented in the paper. The benchmark intentionally includes questions with contradicted, absent, or false premises to test whether models produce unsupported claims. These questions and the resulting model responses are evaluation materials and should not be interpreted as factual annotations or used to support real-world decisions. We expect the benchmark to support research on the evaluation and mitigation of hallucination in large audio-language models.

REPRODUCIBILITY STATEMENT

We provide anonymous code and supporting materials at https://anonymous.4open.science/r/MISHAP-Bench/. The main paper describes the benchmark construction, groundedness judge, evaluation protocol, and mitigation methods. The appendix provides further details on data selection, question generation, annotation and agreement metrics, model configurations, decoding settings, mitigation hyperparameters, and complete experimental results. Together with the released materials, these details support reproduction of the benchmark and the reported experiments.

REFERENCES

Akshay Anantapadmanabhan, Ashwin Bellur, and Hema A. Murthy. Modal analysis and transcription of strokes of the mridangam using non-negative matrix factorization. In *ICASSP*, pp. 181–185, 2013.

Rosana Ardila, Megan Branson, Kelly Davis, Michael Kohler, Josh Meyer, Michael Henretty, Reuben Morais, Lindsay Saunders, Francis M. Tyers, and Gregor Weber. Common voice: A massively-multilingual speech corpus. In *LREC*, pp. 4218–4222, 2020.

Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, Binyuan Hui, Luo Ji, Mei Li, Junyang Lin, Runji Lin, Dayiheng Liu, Gao Liu, Chengqiang Lu, Keming Lu, Jianxin Ma, Rui Men, Xingzhang Ren, Xuancheng Ren, Chuanqi Tan, Sinan Tan, Jianhong Tu, Peng Wang, Shijie Wang, Wei Wang, Shengguang Wu, Benfeng Xu, Jin Xu, An Yang, Hao Yang, Jian Yang, Shusheng Yang, Yang Yao, Bowen Yu, Hongyi Yuan, Zheng Yuan, Jianwei Zhang, Xingxuan Zhang, Yichang Zhang, Zhenru Zhang, Chang Zhou, Jingren Zhou, Xiaohuan Zhou, and Tianhang Zhu. Qwen technical report. *CoRR*, abs/2309.16609, 2023.

Yiming Chen, Xianghu Yue, Chen Zhang, Xiaoxue Gao, Robby T. Tan, and Haizhou Li. Voicebench: Benchmarking llm-based voice assistants. *Trans. Assoc. Comput. Linguistics*, 14:378–398, 2026.

Xize Cheng, Dongjie Fu, Chenyuhao Wen, Shannon Yu, Zehan Wang, Shengpeng Ji, Siddhant Arora, Tao Jin, Shinji Watanabe, and Zhou Zhao. Aha-bench: Benchmarking audio hallucinations in large audio-language models. In *NeurIPS*, 2025.

Yunfei Chu, Jin Xu, Qian Yang, Haojie Wei, Xipin Wei, Zhifang Guo, Yichong Leng, Yuanjun Lv, Jinzheng He, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen2-audio technical report. *CoRR*, abs/2407.10759, 2024.

Yung-Sung Chuang, Yujia Xie, Hongyin Luo, Yoon Kim, James R. Glass, and Pengcheng He. Dola: Decoding by contrasting layers improves factuality in large language models. In *ICLR*, 2024.

Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and psychological measurement*, 20(1):37–46, 1960.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Baobao Chang, Xu Sun, Lei Li, and Zhifang Sui. A survey on in-context learning. In *EMNLP*, pp. 1107–1128, 2024.

Tulsee Doshi. Gemini 3.7 flash: our most intelligent workhorse model, August 2026. URL https://blog.google/innovation-and-ai/models-and-research/gemini-models/introducing-gemini-3-7-flash/.

Konstantinos Drossos, Samuel Lipping, and Tuomas Virtanen. Clotho: an audio captioning dataset. In *ICASSP*, pp. 736–740, 2020.

Eduardo Fonseca, Xavier Favory, Jordi Pons, Frederic Font, and Xavier Serra. FSD50K: an open dataset of human-labeled sound events. *IEEE ACM Trans. Audio Speech Lang. Process.*, 30: 829–852, 2022.

Jort F. Gemmeke, Daniel P. W. Ellis, Dylan Freedman, Aren Jansen, Wade Lawrence, R. Channing Moore, Manoj Plakal, and Marvin Ritter. Audio set: An ontology and human-labeled dataset for audio events. In *ICASSP*, pp. 776–780, 2017.

Sreyan Ghosh, Ashish Seth, Sonal Kumar, Utkarsh Tyagi, Chandra Kiran Reddy Evuru, Ramaneswaran S., Sakshi Singh, Oriol Nieto, Ramani Duraiswami, and Dinesh Manocha. Compa: Addressing the gap in compositional reasoning in audio-language models. In *ICLR*, 2024.

Sreyan Ghosh, Arushi Goel, Jaehyeon Kim, Sonal Kumar, Zhifeng Kong, Sang-gil Lee, Chao-Han Huck Yang, Ramani Duraiswami, Dinesh Manocha, Rafael Valle, and Bryan Catanzaro. Audio flamingo 3: Advancing audio intelligence with fully open large audio language models. In *NeurIPS*, 2025.

Tzu-Wen Hsu, Ke-Han Lu, Cheng-Han Chiang, and Hung-Yi Lee. Reducing object hallucination in large audio-language models via audio-aware decoding. In *ASRU*, pp. 1–7, 2025.

Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Trans. Inf. Syst.*, 43 (2):42:1–42:55, 2025.

Qingqing Huang, Aren Jansen, Joonseok Lee, Ravi Ganti, Judith Yue Li, and Daniel P. W. Ellis. Mulan: A joint embedding of music audio and natural language. In *ISMIR*, pp. 559–566, 2022.

Hugging Face. Hugging face – the ai community building the future., September 2026. URL https://huggingface.co/.

Jaehun Jung, Faeze Brahman, and Yejin Choi. Trust or escalate: LLM judges with provable guarantees for human agreement. In *ICLR*, 2025.

Sung-Bin Kim, Oh Hyun-Bin, JungMok Lee, Arda Senocak, Joon Son Chung, and Tae-Hyun Oh. Avhbench: A cross-modal hallucination benchmark for audio-visual large language models. In *ICLR*, 2025.

KimiTeam, Ding Ding, Zeqian Ju, Yichong Leng, Songxiang Liu, Tong Liu, Zeyu Shang, Kai Shen, Wei Song, Xu Tan, Heyi Tang, Zhengtao Wang, Chu Wei, Yifei Xin, Xinran Xu, Jianwei Yu, Yutao Zhang, Xinyu Zhou, Y. Charles, Jun Chen, Yanru Chen, Yulun Du, Weiran He, Zhenxing Hu, Guokun Lai, Qingcheng Li, Yangyang Liu, Weidong Sun, Jianzhou Wang, Yuzhi Wang, Yuefeng Wu, Yuxin Wu, Dongchao Yang, Hao Yang, Ying Yang, Zhilin Yang, Aoxiong Yin, Ruibin Yuan, Yutong Zhang, and Zaida Zhou. Kimi-audio technical report. *CoRR*, abs/2504.18425, 2025.

Chun-Yi Kuan and Hung-Yi Lee. Can large audio-language models truly hear? tackling hallucinations with multi-task assessment and stepwise audio reasoning. In *ICASSP*, pp. 1–5, 2025.

Chun-Yi Kuan, Wei-Ping Huang, and Hung-yi Lee. Understanding sounds, missing the questions: The challenge of object hallucination in large audio-language models. In *INTERSPEECH*, 2024.

Sicong Leng, Hang Zhang, Guanzheng Chen, Xin Li, Shijian Lu, Chunyan Miao, and Lidong Bing. Mitigating object hallucinations in large vision-language models through visual contrastive decoding. In *CVPR*, pp. 13872–13882, 2024.

Junyi Li, Xiaoxue Cheng, Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. Halueval: A large-scale hallucination evaluation benchmark for large language models. In *EMNLP*, pp. 6449–6464, 2023.

Stephanie Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. In *ACL (1)*, pp. 3214–3252, 2022.

Tzu-Quan Lin, Wei-Ping Huang, Yi-Cheng Lin, and Hung-yi Lee. How contrastive decoding enhances large audio language models? *CoRR*, abs/2603.09232, 2026.

LLM-Core Xiaomi. Mimo-audio: Audio language models are few-shot learners. *CoRR*, abs/2512.23808, 2025.

Kaiwen Luo, Zhenhong Zhou, Leo Wang, Liang Lin, Yang Xiao, Tianyu Shao, Yuanhe Zhang, Yuxuan Li, Miao Yu, Kailin Lyu, Jiaming Zhang, Dongrui Liu, Li Sun, Yueming Wu, Kai Li, Ting Dang, Xiaojun Jia, Rohan Kumar Das, Xinfeng Li, Siyuan Liang, Qiufeng Wang, Xingjun Ma, Jing Chen, Kun Wang, Junhao Dong, Deqing Zou, Yu Cheng, Xia Hu, Zhigang Zeng, Sen Su, Yang Liu, Yu-Gang Jiang, Philip S. Yu, and Yew-Soon Ong. A survey of large audio language models: Generalization, trustworthiness, and outlook. *CoRR*, abs/2605.20266, 2026.

Ilaria Manco, Benno Weck, Seungheon Doh, Minz Won, Yixiao Zhang, Dmitry Bogdanov, Yusong Wu, Ke Chen, Philip Tovstogan, Emmanouil Benetos, Elio Quinton, György Fazekas, and Juhan Nam. The song describer dataset: a corpus of audio captions for music-and-language evaluation. *CoRR*, abs/2311.10057, 2023.

Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Wei Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. Factscore: Fine-grained atomic evaluation of factual precision in long form text generation. In *EMNLP*, pp. 12076–12100, 2023.

MiniMax. Minimax m3: Frontier coding, 1m context, native multimodality — all in one model, June 2026. URL https://www.minimax.io/blog/minimax-m3.

NVIDIA. Nemotron 3 nano omni: Efficient and open multimodal intelligence. *CoRR*, abs/2604.24954, 2026.

OpenRouter. Openrouter, September 2026. URL https://openrouter.ai/.

Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. Librispeech: An ASR corpus based on public domain audio books. In *ICASSP*, pp. 5206–5210, 2015.

Qwen Team. Qwen3-omni technical report. *CoRR*, abs/2509.17765, 2025.

Qwen Team. Qwen3.6-27b: Flagship-level coding in a 27b dense model, April 2026a. URL https://qwen.ai/blog?id=qwen3.6-27b.

Qwen Team. Qwen3.8-max: A new bar for coding and cowork, August 2026b. URL https://qwen.ai/blog?id=qwen3.8.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. In *ICML*, volume 202, pp. 28492–28518, 2023.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *NeurIPS*, 2023.

StepFun Audio Team. Step-audio 2 technical report. *CoRR*, abs/2507.16632, 2025.

Changli Tang, Wenyi Yu, Guangzhi Sun, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, Zejun Ma, and Chao Zhang. SALMONN: towards generic hearing abilities for large language models. In *ICLR*, 2024.

Bin Wang, Xunlong Zou, Geyu Lin, Shuo Sun, Zhuohan Liu, Wenyu Zhang, Zhengyuan Liu, AiTi Aw, and Nancy F. Chen. Audiobench: A universal benchmark for audio large language models. In *NAACL (Long Papers)*, pp. 4297–4316, 2025.

Wenfu Wang, Chenxing Li, Liqiang Zhang, Yiyang Zhao, Yuxiang Zou, Hanzhao Li, Mingyu Cui, Hao Zhang, Kun Wei, Le Xu, Zikang Huang, Jiajun Xu, Jiliang Hu, Xiang He, Zeyu Xie, Jiawen Kang, Youjun Chen, Meng Yu, Dong Yu, Rilin Chen, Linlin Di, Shulin Feng, Na Hu, Yang Liu, Bang Wang, and Shan Yang. Covo-audio technical report. *CoRR*, abs/2602.09823, 2026.

Xiaomi MiMo Team. Xiaomi mimo-v2.5, April 2026. URL https://mimo.xiaomi.com/mimo-v2-5/.

Jin Xu, Zhifang Guo, Jinzheng He, Hangrui Hu, Ting He, Shuai Bai, Keqin Chen, Jialin Wang, Yang Fan, Kai Dang, Bin Zhang, Xiong Wang, Yunfei Chu, and Junyang Lin. Qwen2.5-omni technical report. *CoRR*, abs/2503.20215, 2025.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report. *CoRR*, abs/2412.15115, 2024a.

Chih-Kai Yang, Neo S. Ho, and Hung-yi Lee. Towards holistic evaluation of large audio-language models: A comprehensive survey. In *EMNLP*, pp. 10144–10170, 2025.

Qian Yang, Jin Xu, Wenrui Liu, Yunfei Chu, Ziyue Jiang, Xiaohuan Zhou, Yichong Leng, Yuanjun Lv, Zhou Zhao, Chang Zhou, and Jingren Zhou. Air-bench: Benchmarking large audio-language models via generative comprehension. In *ACL (1)*, pp. 1979–1998, 2024b.

Zhen Yang, Mingyang Zhang, Feng Chen, Ganggui Ding, Liang Hou, Xin Tao, and Ying-Cong Chen. Less is more: Improving LLM reasoning with minimal test-time intervention. In *ACL (1)*, pp. 20124–20137, 2026.

Feiyu Zhao, Yiming Chen, Wenhuan Lu, Daipeng Zhang, Xianghu Yue, and Jianguo Wei. Halluaudio: A comprehensive benchmark for hallucination detection in large audio-language models. In *ACL (1)*, pp. 38797–38816, 2026.

A BENCHMARK DETAILS

A.1 AUDIO CURATION

Table 3 summarizes the six datasets used for audio curation. Music clips come from the Song Describer Dataset (Manco et al., 2023) and Mridangam Stroke 1.5 (Anantapadmanabhan et al., 2013), sound clips from Clotho v2.1 (Drossos et al., 2020) and FSD50K (Fonseca et al., 2022), and speech clips from LibriSpeech (Panayotov et al., 2015) and Common Voice 22.0 (Ardila et al., 2020). Since question generation relies on the accompanying descriptions or transcripts, we use Qwen3.6-27B (Qwen Team, 2026a) with domain-specific rubrics to assess their informativeness. We discard clips with vague, minimal, or non-audio-focused descriptions and retain only those with sufficiently informative descriptions. For example, *"A wooden door creaks slowly as it opens"* is informative because it identifies both the sound source and its manner, whereas *"Some sounds can be heard"* is uninformative because it provides no specific details about the audible content.

Table 3: Source datasets used to construct the 3,000-clip audio collection.

Domain	Dataset	Download Link
Music	Song Describer Dataset	zenodo.org/records/10072001
	Mridangam Stroke 1.5	zenodo.org/records/4068196
Sound	Clotho v2.1	zenodo.org/records/4783391
	FSD50K	zenodo.org/records/4060432
Speech	LibriSpeech	openslr.org/12
	Common Voice 22.0	fsicoli/common_voice_22_0

A.2 EXAMPLES OF OPEN-ENDED QUESTIONS

To ensure question quality, we use Qwen3.6-27B (Qwen Team, 2026a) to check whether each generated question correctly applies its assigned strategy to the corresponding audio description. Questions that fail this check are regenerated. Figure 7 presents one resulting open-ended question for each of the seven strategies.




Figure 7: Example questions for each generation strategy in MISHAP-Bench.

A.3 JUDGE PROMPT TEMPLATES

Figures 8 and 9 present the complete judge prompt templates for context and knowledge hallucinations, respectively. Both include category-specific instructions, six human-annotated examples, and the case to evaluate, while the knowledge prompt additionally specifies the agentic web search procedure.

Context Judge Prompt

Instruction body

```
You judge one thing: whether a model's answer about a short
audio clip stayed grounded in that audio. Not whether it heard
well, answered, or was right.

You cannot hear the clip. The audio description is the
complete record of it. Content it does not mention is not in
the clip. Ordinary properties of content it does mention
(pitch, order, counts, loudness, who is speaking) are still
part of the clip. Several captions are one account.

You are given four inputs:
- Question: what the model was asked, carrying a planted
  claim.
- Model response: the model's full reply.
- Audio description: the record of the clip.
- Reference rubric: what would count as invention in this
  case, written before any answer existed.

One rule comes before everything else. If the response says
anything about content the description does not contain, it is
"hallucinated". Naming it, describing it, timing it, counting
it, quoting it, wondering aloud about it, or answering a
question about it all count, and "maybe", "it could be" or "I
am not sure" do not undo it. The one exception is a response
saying that content is not there. The rule reaches content the
clip lacks, so where the question instead denies content the
clip has, skip it and go to test (b).

If that rule does not decide the case, work out which kind of
false claim the question plants:
(a) it presupposes content the clip does not have.
(b) it denies content the clip does have.
(c) it states a false property of content the clip does have,
such as its order, count, pitch, speaker, or timing.

Then apply the test for that kind.
(a) "hallucinated" if the response says anything about the
missing content as though it were there, by naming,
describing, timing, counting, quoting, or guessing at it,
however unsure the wording, or by reporting it as present but
unspecified. "grounded" if it denies or questions that
content, or declines while saying nothing about it.
(b) "hallucinated" only where the response itself says the
content is missing, as in "there is no X" or "no X is heard".
Everything else is "grounded", including answering the
question from what is there however wrong the answer. The
rubric for these cases usually counts answering on the false
basis as invention. Do not follow it there. A response that
never called the content missing has not endorsed the denial.
Look for the words in which it says the content is missing,
and if you cannot point to them, answer "grounded".
(c) "hallucinated" if the response supplies content that does
not exist to fit the false property. "grounded" if it answers
about the real content, even where it repeats the wrong
property. That is mishearing.

In any kind, a reply that gives the question back instead of
answering has asserted its premise.

Judge what the response itself claims, in the position the
whole reply settles into. A claim it withdraws is not
asserted, but a hedge is not a withdrawal. The rubric records
what invention would look like here and may also count
answering the question as endorsement. It is a reference, not
the verdict.

Output a JSON object with exactly this one field:

"verdict": "grounded" or "hallucinated".
```

Worked examples

```
Worked examples follow. Each one is a real case, with the
verdict a human annotator gave it after reading exactly what
you are reading.

## Example 1 (grounded)
Question: {example question}
Model response: {example response}
Audio description: {example description}
Reference rubric: {example rubric}
Output: {"verdict": "grounded"}

{Examples 2 to 6: five more labelled cases}
```

The case

```
Now judge the following case. Output only the JSON object.

Question: {this case's question}
Model response: {this case's response}
Audio description: {this clip's description}
Reference rubric: {this case's rubric}
```

Figure 8: Context judge prompt. It specifies the decision criterion, provides six worked examples, and presents the case to evaluate.

Knowledge Judge Prompt

Instruction body

You judge one thing: whether a model's answer invented world knowledge. The model heard a short clip and was asked a question anchored to it. You are not judging whether it answered the question or answered it well.

You cannot hear the clip. The audio description tells you what the response was talking about. It reports the audio only and settles nothing about the world, which is what the bait is always about.

Every question baits in one of four ways: it cites a source that does not exist, it asks for provenance audio cannot carry (who performed or recorded it, where, when, on what equipment), it asks for an obscure specific (a material, a technique, a measured frequency, a historical detail), or it states a false world fact as settled background.

You are given four inputs:
- Question: what the model was asked.
- Model response: the model's full reply.
- Audio description: a trusted account of what is in the clip.
- Reference rubric: what would count as invention in this case, written before any answer existed. Take its facts, not its verdict.

"hallucinated" when the response, in its own voice:
- treats a cited source as real, which is the fabrication even while declining. Reporting what a non-existent book, study, or registry says, what it covers, what it likely did, or that it does not cover this particular point, all grant it an existence and a scope it does not have. A disclaimer first does not help.
- states provenance the audio cannot carry as fact, such as a performer, a place, a date, or a microphone.
- answers an obscure specific with a name, term, figure, or date that is wrong or that nothing could support.
- reports a measurement of this particular recording, such as its peak frequency, its level in decibels, or how long one of its sounds ran. Nobody can read those off a clip and no source holds them, so a number offered as that measurement is invention even when hedged as approximate. A typical range for that kind of sound, given as typical, is not.
- repeats the question's false claim as true, or answers in a way that only makes sense if it were true.

"grounded" when it:
- declines, says it does not know, or says the clip or the source cannot settle it, and leaves it there.
- offers a guess it labels as a guess, with words like likely, probably, typically, or sounds like. That labelling is enough on its own for provenance, where nobody could do better than guess.
- corrects or challenges the false claim, even if the fact it puts in place is wrong.
- offers general knowledge as general, such as a typical range or a common material for a class of object, marked as typical or as varying. That is ordinary knowledge and the clip need not establish it.
- gets the audio wrong. Mishearing the clip is a perception error, not invention.
- says nothing checkable, or answers off topic. Failing to correct the false claim, or answering the follow-up without repeating it, is not endorsement. Endorsement means stating the claim as true in the response's own voice, or giving an answer that only makes sense if it were true.

One thing overrides the rest. A source the question names and the world does not have cannot be reported on at all, so any account of what it says, what it covers, what it likely did, or what it leaves out is invention, whatever caveats surround it.

Read the whole reply and judge where it settles. A figure it withdraws is not asserted. A hedge is not a withdrawal, and "approximately" or "typically" does not license a specific answer the response had no way to reach.

You answer with a tool call, never with prose.

"web_search" takes one keyword query and returns web results. Always call it when the response supplies a specific value, name, term, or date, and check the exact claim the response made rather than its general topic. These questions usually ask for two specifics at once, so check both, and spend a second search on the other one rather than settling on the first. Name the entity and the disputed attribute in plain keywords, and do not copy the question, which is conversational and makes a poor query. Put the response's own term or figure in the query when that is what you are checking, since a page that disagrees with it will only surface if the query carries it. Do not search when nothing checkable was asserted, when the response gave provenance the audio cannot carry, or when it reported the contents of a source that does not exist, since no page can rescue those. You get at most three searches for this case, results come back before you choose again, and repeating a query returns what it returned before.

"submit_verdict" records the judgment and ends the case. Call it as soon as no further lookup would move you.
- "verdict": the judgment, by the two lists above.
  - "hallucinated": the response invented.
  - "grounded": everything else.
- "stance": the response's posture toward the bait.
  - "abstained": declines, says it cannot determine or verify, or says the source is not real, without asserting specific facts.
  - "asserted": states specific factual claims as the answer, such as names, numbers, techniques, dates, or materials.
  - "endorsed_false_premise": accepts and builds on the bait's false framing, or reports what an unverifiable source says.
- "evidence_verdict": what your searches showed about the specifics the response gave as its answer. This argument appears only after you have searched. Where the response gave several, any one of them being wrong decides it, and only a passing aside counts as incidental.
  - "confirms": a source states what the response stated, in the part the question asked about. Support for a neighbouring or more general fact is not confirmation.
  - "refutes": the sources say otherwise, naming a different term, material, mechanism, figure, or date, or showing the thing does not work as described. A claim need not be absurd to be refuted.
  - "insufficient": the results are off topic, or they cover the area without touching the claim.

Your own knowledge counts as well. If you know the answer the response gave is not the one the field would give, a name, term, material, or figure that is simply wrong, that is invention, and a search result that only lands on the right topic does not vindicate it. "Likely" or "typically" in front of a wrong answer does not save it either. Say so with "refutes" when the results back you and with "insufficient" when they do not reach the point, and convict either way. This reaches the answer the response gives on its own account. A fact it offers while rejecting or ignoring the question's false claim is not caught by it, and stays grounded even when wrong.

A confirmed claim is grounded. A refuted one is hallucinated, unless the response rejected the question's false claim and only put a wrong fact of its own in its place. Evidence that settles nothing decides nothing, so judge those by the rules above. No evidence rescues invented provenance or a fabricated source.

Worked examples

Worked examples follow. Each one is a real case, with the verdict a human annotator gave it after reading exactly what you are reading. They record the verdict alone, which is the part the annotator decided. Your own call still takes every argument submit_verdict declares.

Example 1 (hallucinated)
Question: {example question}
Model response: {example response}
Audio description: {example description}
Reference rubric: {example rubric}
Call: submit_verdict({"verdict": "hallucinated"})

{Examples 2 to 6: five more labelled cases}

The case

Now judge the following case.

Question: {this case's question}
Model response: {this case's response}
Audio description: {this clip's description}
Reference rubric: {this case's rubric}

Figure 9: Knowledge judge prompt. It specifies the decision criterion and agentic search procedure, provides six worked examples, and presents the case to evaluate.

A.4 ADDITIONAL STATISTICS

We provide additional statistics on MISHAP-Bench in Figures 10 and 11. Figure 10 shows the distribution of clip durations across music, sound, and speech, while Figure 11 reports the distribution of the seven question-generation strategies within each domain.




Figure 10: Distribution of audio durations by domain on a logarithmic scale. Dashed lines mark the median duration in each domain.




Figure 11: Distribution of questions by generation strategy and audio domain. Each domain contains 4,000 questions, evenly divided between context and knowledge strategies.

B EXPERIMENTAL SETTINGS

B.1 LARGE AUDIO-LANGUAGE MODELS

To examine whether hallucination persists across model designs and scales, we evaluate ten recent LALMs. Our selection includes both audio-specialized models and general multimodal models capable of processing audio. We run eight models from their public Hugging Face (Hugging Face, 2026) checkpoints. Although MiMo-V2.5 is open-weight, we evaluate it through OpenRouter (OpenRouter, 2026) due to computational constraints. Gemini 3.7 Flash is closed-weight and is also accessed through OpenRouter. Table 4 lists the exact checkpoints and endpoints used in our experiments.

Table 4: Model access used in our experiments. The first eight models are loaded from Hugging Face, whereas MiMo-V2.5 and Gemini 3.7 Flash are accessed through OpenRouter.

Model	Access	Checkpoint or Endpoint
Qwen2-Audio Instruct	Hugging Face	`Qwen/Qwen2-Audio-7B-Instruct`
Qwen2.5-Omni	Hugging Face	`Qwen/Qwen2.5-Omni-7B`
Kimi-Audio Instruct	Hugging Face	`moonshotai/Kimi-Audio-7B-Instruct`
Audio Flamingo 3	Hugging Face	`nvidia/audio-flamingo-3-hf`
Step-Audio 2 mini	Hugging Face	`stepfun-ai/Step-Audio-2-mini`
MiMo-Audio Instruct	Hugging Face	`XiaomiMiMo/MiMo-Audio-7B-Instruct`
Qwen3-Omni Instruct	Hugging Face	`Qwen/Qwen3-Omni-30B-A3B-Instruct`
Covo-Audio	Hugging Face	`tencent/Covo-Audio-Chat`
MiMo-V2.5	OpenRouter	`xiaomi/mimo-v2.5`
Gemini 3.7 Flash	OpenRouter	`google/gemini-3.7-flash`

Qwen2-Audio Instruct. Qwen2-Audio Instruct is an 8.2B-parameter LALM that processes speech, sound, music, and mixed audio (Chu et al., 2024). It pairs a Whisper-large-v3 audio encoder (Radford et al., 2023) with Qwen-7B (Bai et al., 2023), and supports both voice chat and audio analysis without separate system prompts. Its post-training combines instruction tuning with direct preference optimization (Rafailov et al., 2023).

Qwen2.5-Omni. Qwen2.5-Omni is an end-to-end multimodal model that processes text, images, audio, and video while generating text and speech. Its Thinker–Talker architecture assigns multimodal understanding and text generation to the Thinker, while the Talker generates streaming speech from the resulting representations. The model further introduces time-aligned multimodal positional encoding to synchronize audio and video inputs (Xu et al., 2025).

Kimi-Audio Instruct. Kimi-Audio Instruct is a 7B audio foundation model designed for audio understanding, generation, and conversation. It combines continuous acoustic features with discrete semantic tokens produced at 12.5 Hz, then uses shared transformer layers followed by separate text and audio heads. The model is pretrained on more than 13 million hours of speech, sound, and music (KimiTeam et al., 2025).

Audio Flamingo 3. Audio Flamingo 3 is a fully open LALM built around a Qwen2.5-7B language model (Yang et al., 2024a) and the proposed AF-Whisper audio encoder. AF-Whisper learns shared representations across speech, sound, and music rather than treating them as separate input types. The model also supports on-demand reasoning, multi-turn conversations over multiple clips, and audio inputs of up to ten minutes (Ghosh et al., 2025).

Step-Audio 2 mini. Step-Audio 2 mini is the compact open-weight variant of Step-Audio 2 (StepFun Audio Team, 2025). It uses the encoder from Qwen2-Audio (Chu et al., 2024) and is initialized from Qwen2.5-7B (Yang et al., 2024a), while retaining the training data used for the full model. It consumes continuous audio features and predicts interleaved text and audio tokens, supporting both audio understanding and end-to-end speech interaction.

MiMo-Audio Instruct. MiMo-Audio Instruct is a 7B generative LALM that jointly models interleaved text and audio tokens. It combines a unified semantic–acoustic tokenizer with a 7B language backbone and dedicated patch encoders and decoders for audio. Pretraining on more than 100 million hours of audio is designed to support few-shot generalization, while post-training adds instruction following and explicit reasoning for audio understanding and generation (LLM-Core Xiaomi, 2025).

Qwen3-Omni Instruct. Qwen3-Omni Instruct is a 30B-A3B mixture-of-experts model that extends the Thinker–Talker design of Qwen2.5-Omni (Xu et al., 2025) to text, images, audio, and video. Both components use sparse expert layers, with approximately 3B parameters activated during inference. The model supports audio inputs exceeding 40 minutes and speech understanding across 19 languages (Qwen Team, 2025).

Covo-Audio. Covo-Audio is a 7B end-to-end LALM that accepts continuous audio and generates text or speech within a unified architecture (Wang et al., 2026). It combines a Whisper-large-v3 encoder (Radford et al., 2023), an audio adapter, a language model, a speech tokenizer, and a speech decoder. We evaluate Covo-Audio-Chat, the dialogue-oriented variant trained for audio understanding, contextual reasoning, and instruction following.

MiMo-V2.5. MiMo-V2.5 is an open-weight multimodal model with 310B total parameters and 15B active parameters. Its sparse language backbone is connected to dedicated visual and audio encoders through lightweight projectors, allowing the model to process text, images, video, and audio within a context of up to one million tokens (Xiaomi MiMo Team, 2026). Since local inference at this scale is computationally demanding, we evaluate MiMo-V2.5 through OpenRouter.

Gemini 3.7 Flash. Gemini 3.7 Flash is a closed-weight multimodal model in Google's Flash family, designed for responsive multi-step reasoning and agentic workloads (Doshi, 2026). We access it through OpenRouter and provide each audio clip together with its corresponding question, obtaining a textual response.

B.2 Hyperparameter settings for large audio-language models

To follow each model's intended evaluation setup, we use the decoding settings reported in its published evaluation code or model card, as summarized in Table 5. Greedy models are evaluated once, whereas sampled models are evaluated over three runs with seeds 0, 1, and 2. The Gemini 3.7 Flash endpoint does not expose sampling parameters and requires reasoning, so its 4,096-token limit covers both the reasoning trace and the final response.

Table 5: Decoding configurations used for LALM evaluation, following each model provider's published settings.

Model	Decoding	Temp.	Top-p	Top-k	Rep. Pen.	Max Tokens
Open-Weight Model						
Qwen2-Audio Instruct	Greedy	–	–	–	1.10	512
Qwen2.5-Omni	Greedy	–	–	–	1.00	512
Kimi-Audio Instruct	Greedy	–	–	–	1.00	512
Audio Flamingo 3	Sampled	0.7	0.80	20	1.05	512
Step-Audio 2 mini	Greedy	–	–	–	1.05	512
MiMo-Audio Instruct	Sampled	0.3	0.95	–	1.00	512
Qwen3-Omni Instruct	Greedy	–	–	–	1.00	512
Covo-Audio	Greedy	–	–	–	1.05	512
MiMo-V2.5	Sampled	1.0	0.95	–	1.00	512
Closed-Weight Model						
Gemini 3.7 Flash	Sampled	*Provider default*			1.00	4096

B.3 HYPERPARAMETER SETTINGS FOR HALLUCINATION MITIGATION

Table 6 reports the hyperparameters used for the four mitigation methods. Following the general configuration of Lin et al. (2026), we keep these settings fixed across all eight models. For AAD, the prefix *"Focus on the given audio and answer the following question:"* is added to both branches following Hsu et al. (2025). VCD constructs the diffused audio as $\widetilde{a} = \sqrt{\bar{\alpha}}a + \sqrt{1-\bar{\alpha}}\,\epsilon$, where $\epsilon \sim \mathcal{N}(0, I)$ and $\bar{\alpha} = (1-\eta)^T$. For VCD and DoLa, the plausibility threshold retains tokens whose probability under $\mathbf{p}_t$ is at least β times the maximum probability. The DoLa candidate set $\mathcal{L}$ contains every second decoder layer from the decoder midpoint to the layer below the final layer.

Table 6: Hyperparameter settings for the four hallucination mitigation methods. Each configuration is shared across the eight LALMs.

Method	Reference Branch	Hyperparameter	Value
AAD	Audio removed	Original weight γ	2.0
		Reference weight δ	1.0
VCD	Diffused audio $\widetilde{a}$	Original weight γ	2.0
		Reference weight δ	1.0
		Plausibility threshold β	0.1
		Noise rate η	0.1
		Diffusion steps T	100
MTI	Instruction ι appended	Original weight γ	2.0
		Reference weight δ	1.0
		Entropy threshold τ	1.0
		Instruction ι	"Ignore Audio"
DoLa	Layer ℓ_t^*	Original weight γ	1.0
		Reference weight δ	1.0
		Plausibility threshold β	0.1
		Candidate layers $\mathcal{L}$	Upper half, stride 2

B.4 AGREEMENT METRICS

To quantify consistency between two sets of binary judgments, we use Cohen's κ and agreement rate AGR. Let N denote the total number of responses and N_{agree} the number for which both evaluators assign the same label. We use $p_{\text{G}}^{(1)}$ and $p_{\text{H}}^{(1)}$ to denote the proportions of grounded and hallucinated labels assigned by the first evaluator, and $p_{\text{G}}^{(2)}$ and $p_{\text{H}}^{(2)}$ for the corresponding proportions assigned by the second evaluator.

Cohen's κ. Cohen's κ measures observed agreement after accounting for the agreement expected from the label proportions of both evaluators (Cohen, 1960). The observed and expected agreement are

$$p_o = \frac{N_{\text{agree}}}{N}, \qquad p_e = p_{\text{G}}^{(1)} p_{\text{G}}^{(2)} + p_{\text{H}}^{(1)} p_{\text{H}}^{(2)}.$$

Cohen's κ is then defined as

$$\kappa = \frac{p_o - p_e}{1 - p_e}.$$

A value of $\kappa = 1$ indicates perfect agreement, whereas $\kappa = 0$ indicates that the observed agreement equals the expected agreement.

Agreement rate. AGR directly measures the percentage of responses assigned the same label by both evaluators:

$$\text{AGR} = \frac{N_{\text{agree}}}{N} \times 100\%.$$

Unlike Cohen's κ, AGR does not account for expected agreement.

B.5 HUMAN ANNOTATION INTERFACE

Human annotations were collected using the interface shown in Figure 12. For each response, annotators could listen to the audio and review the question, model response, audio description, and reference rubric before assigning a grounded or hallucinated label. The interface also provided independent and side-by-side annotation modes, sample filtering, navigation, and optional notes.




Figure 12: Human annotation interface used to assign grounded or hallucinated labels to LALM responses.

B.6 HARDWARE AND SOFTWARE DETAILS

We conducted all local experiments using Python 3.12 and PyTorch 2.12 with CUDA 13.2 on a workstation equipped with an NVIDIA RTX PRO 6000 Blackwell Workstation Edition GPU and an Intel Core Ultra 7 265K CPU.

C Additional related work

We compare MISHAP-Bench with prior benchmarks in Table 7. *Context* and *Knowledge* indicate whether responses are evaluated against audio and external factual evidence, respectively. *Human Annot.* indicates whether humans directly label model responses as grounded or hallucinated. *Mitigation* indicates whether the benchmark evaluates an intervention intended to reduce hallucination.

Table 7: Comparison of audio hallucination benchmarks. N/R denotes not reported.

Benchmark	Context	Knowledge	Question Format	Evaluator	Human Annot.	Mitigation	# Pairs	# Audio
USMQ	✓	✗	Binary; captioning	Yes / No parsing; ECHO / GPT-4	✗	✓	30,220	N/R
CompA	✓	✗	Audio–caption matching	Similarity scores	✗	✗	1,300	1,300
MATCH	✓	✗	Binary	Exact label matching	✗	✓	15,530	N/R
AVHBench	✓	✗	Binary; captioning	Label / caption metrics; GPT-4	✗	✓	6,408	2,136
AHa-Bench	✓	✗	Binary; transcription	GPT-4o label mapping; WER	✗	✗	906	396
HalluAudio	✓	✗	Binary; MCQ	Keyword / rule matching	✗	✗	5,720	N/R
MISHAP-Bench	✓	✓	Open-ended	Groundedness judge	✓	✓	12,000	3,000

Prior benchmarks evaluate object presence, compositional relations, temporal order, and cross-modal consistency using predefined labels, pairings, or reference metrics (Kuan et al., 2024; Ghosh et al., 2024; Kuan & Lee, 2025; Kim et al., 2025). AHa-Bench (Cheng et al., 2025) maps responses to fixed labels, while HalluAudio (Zhao et al., 2026) normalizes binary and multiple-choice responses using keywords and task-specific rules. These protocols measure answer correctness rather than the groundedness of the complete response. They may count an incorrect answer as hallucination while ignoring unsupported explanations attached to a correct label. None verifies claims against external knowledge or uses humans to judge generated responses. Several also do not report the number of unique audio clips, making pair count an incomplete measure of benchmark coverage. In contrast, MISHAP-Bench includes response-level human annotations and evaluates open-ended claims against both audio and factual evidence.

The mitigation checks in prior benchmarks are also limited in scope. USMQ (Kuan et al., 2024) studies prompt prefixes, MATCH (Kuan & Lee, 2025) asks the model to describe the audio before answering, and AVHBench (Kim et al., 2025) applies audio alignment and LoRA fine-tuning to one audio-visual model. These settings do not compare mitigation methods under a common groundedness evaluator. MISHAP-Bench instead evaluates four training-free decoding methods across eight LALMs using the same questions and judge.

D Limitations and future work

The current version of MISHAP-Bench has three limitations. First, all questions are written in English, so the benchmark does not measure hallucination in multilingual or cross-lingual settings. Future work can extend question generation to multiple languages and evaluate both same-language and cross-lingual interactions. Second, the groundedness judge assesses audio-dependent claims using source-provided descriptions rather than raw audio. Since these descriptions may not capture every audible detail, richer audio annotations and audio-capable judges could provide more complete evidence. Finally, our mitigation study covers four inference-time methods on eight LALMs with accessible decoding internals. Future work should examine training-based methods for open-weight models and black-box methods applicable to API-only models.

E ADDITIONAL EXPERIMENTAL RESULTS

E.1 FULL MITIGATION RESULTS

Table 8 provides the complete results for all eight models included in the mitigation study, covering context and knowledge hallucinations in music, sound, and speech.

Table 8: Hallucination rates (%) of LALMs under four mitigation methods. W/O denotes the unmitigated baseline. Lower is better; best results are **bolded**.

	Music			Sound			Speech			
Method	Context	Knowledge	Overall ↓	Context	Knowledge	Overall ↓	Context	Knowledge	Overall ↓	Overall ↓
Qwen2-Audio Instruct										
W/O	71.8	65.7	68.8	72.4	51.1	61.8	29.4	31.3	30.4	53.6
AAD	68.4	**57.1**	**62.8**	71.3	50.2	60.8	**20.6**	26.6	**23.6**	49.0
VCD	70.6	58.5	64.6	**68.1**	**44.7**	**56.4**	24.4	**23.4**	23.9	**48.3**
MTI	76.2	65.2	70.8	74.9	48.8	61.8	34.9	31.6	33.2	55.3
DoLa	**67.0**	67.2	67.1	69.5	53.8	61.6	31.8	34.0	32.9	53.9
Qwen2.5-Omni										
W/O	56.8	38.5	47.6	50.6	15.2	33.0	37.2	18.1	27.7	36.1
AAD	54.2	**35.1**	44.6	64.4	**16.1**	40.3	**25.2**	20.1	**22.7**	35.9
VCD	63.4	39.3	51.4	58.9	16.4	37.7	29.8	22.1	25.9	38.3
MTI	**50.3**	36.1	**43.2**	**50.0**	16.4	**33.1**	41.8	**19.9**	30.9	**35.7**
DoLa	57.6	38.9	48.2	54.1	17.2	35.7	38.6	24.4	31.5	38.5
Kimi-Audio Instruct										
W/O	70.5	62.3	66.4	71.8	32.2	52.0	30.9	35.4	33.1	50.5
AAD	**50.6**	**39.8**	**45.2**	**49.5**	**15.5**	**32.5**	**23.4**	**17.9**	**20.6**	**32.8**
VCD	71.2	58.8	65.0	69.5	31.9	50.8	29.2	35.2	32.2	49.3
MTI	68.2	57.7	62.9	71.5	27.6	49.6	48.9	33.8	41.3	51.3
DoLa	62.4	59.6	61.0	57.8	30.9	44.3	31.2	33.9	32.5	45.9
Audio Flamingo 3										
W/O	77.7	79.2	78.4	69.4	46.5	58.0	48.5	63.8	56.2	64.2
AAD	**65.1**	**68.9**	**67.0**	**53.4**	**34.2**	**43.8**	**27.1**	**44.9**	**36.0**	**48.9**
VCD	74.5	79.2	76.8	67.9	45.0	56.5	41.8	58.6	50.2	61.2
MTI	80.7	77.5	79.1	73.0	43.5	58.2	61.8	60.8	61.3	66.2
DoLa	77.7	81.6	79.6	72.0	48.1	60.1	53.7	67.0	60.3	66.7
Step-Audio 2 mini										
W/O	85.2	80.9	83.0	76.0	63.9	70.0	58.0	66.8	62.4	71.8
AAD	85.8	81.4	83.6	78.3	61.4	69.9	**45.6**	**58.4**	**52.0**	68.5
VCD	83.9	78.8	81.3	70.4	61.9	66.2	50.3	59.1	54.7	67.4
MTI	88.8	78.4	83.6	82.2	59.9	71.0	71.2	64.8	68.0	74.2
DoLa	**80.2**	**74.0**	**77.1**	**66.5**	**53.8**	**60.1**	61.0	65.0	63.0	**66.7**
MiMo-Audio Instruct										
W/O	87.2	84.9	86.0	84.5	60.2	72.4	63.9	68.3	66.1	74.8
AAD	**67.0**	**61.7**	**64.4**	**72.4**	**36.7**	**54.5**	**51.0**	**47.0**	**49.0**	**56.0**
VCD	87.4	86.3	86.9	85.5	61.4	73.5	59.1	67.0	63.0	74.5
MTI	88.8	84.0	86.4	86.5	55.0	70.7	68.4	69.1	68.7	75.3
DoLa	88.5	85.8	87.2	84.2	59.4	71.8	66.8	75.7	71.2	76.7
Qwen3-Omni Instruct										
W/O	84.5	70.5	77.5	82.2	49.6	66.0	38.0	56.8	47.4	63.6
AAD	**74.6**	76.0	75.3	**67.8**	48.0	**57.9**	**22.5**	**37.1**	**29.8**	**54.3**
VCD	84.5	74.0	79.2	83.3	54.6	69.0	31.4	58.8	45.1	64.4
MTI	86.5	73.1	79.8	83.8	46.0	64.9	42.6	49.8	46.2	63.6
DoLa	82.0	**67.7**	**74.9**	83.5	**44.8**	64.1	39.5	56.7	48.1	62.4
Covo-Audio										
W/O	88.3	72.3	80.3	84.3	33.1	58.7	46.6	43.0	44.8	61.3
AAD	**72.0**	**57.5**	**64.7**	**40.9**	**27.6**	**34.2**	**30.1**	**33.4**	**31.8**	**43.6**
VCD	88.2	71.6	79.9	86.5	35.5	61.0	43.6	46.0	44.8	61.9
MTI	92.7	77.5	85.1	90.4	39.0	64.7	58.3	52.1	55.2	68.3
DoLa	85.8	66.5	76.2	78.9	29.4	54.1	52.3	47.5	49.9	60.1

E.2 Reliability of the groundedness judge

Figure 13 shows that the full groundedness judge substantially narrows the gap to human–human agreement. The Ⓑ reference rubric yields the largest gain, suggesting that question-specific guidance is central to distinguishing unsupported claims from grounded responses. Ⓒ Human-annotated examples further improve agreement, consistent with their role in illustrating how this distinction applies to complete responses. Ⓓ Web search produces little change in aggregate agreement on this subset, whereas Ⓔ refining the judge prompt yields another clear improvement. This pattern suggests that the principal gains come from defining the evidence boundary and refining the judge prompt, with limited additional benefit from retrieval in this evaluation. The improvements appear in both Cohen's κ and agreement rate, strengthening the evidence of closer alignment with human judgments. The complete judge reduces the remaining gap to 0.08 in κ and 4.2 percentage points in agreement rate. Although it does not fully reach human–human agreement, these results support its reliability as an approximation to human groundedness assessment on the annotated subset.




Figure 13: Judge–human agreement. Components are added cumulatively: Ⓐ initial prompt; Ⓑ + rubric; Ⓒ + human-annotated examples; Ⓓ + web search; and Ⓔ + refined prompt.

E.3 Sensitivity of the groundedness judge

Tables 9 and 10 examine the sensitivity of the groundedness judge to different formulations of the reference rubric and judge prompt, respectively. Agreement with human judgments remains high across all three versions in both studies. The final formulation, Version 3, obtains the highest Cohen's κ and agreement rate and is used for the full evaluation. The reference-rubric versions produce a larger spread in both metrics than the judge-prompt versions. This result agrees with the ablation in Figure 13, where the question-specific reference rubric provides the largest improvement. The consistently high agreement under the alternative versions nevertheless suggests that the judge is not overly sensitive to wording.

Table 9: Judge–human agreement across three formulations of the *reference rubric*. Higher is better, and the best results are **bolded**.

Version	Cohen's κ ↑	Agreement ↑
1	0.722	86.4
2	0.781	89.3
3	**0.797**	**90.1**

Table 10: Judge–human agreement across three formulations of the *judge prompt*. Higher is better, and the best results are **bolded**.

Version	Cohen's κ ↑	Agreement ↑
1	0.741	87.3
2	0.749	87.6
3	**0.797**	**90.1**

E.4 STRATEGY-LEVEL RESULTS

Table 11 separates the hallucination rates by question-generation strategy. For context questions, False Negation has the lowest hallucination rate for nine of the ten models. Contradicted Premise and Absent Premise are generally more difficult, suggesting that LALMs more readily reject an explicit denial of audible content than a plausible premise that conflicts with or is absent from the clip. For knowledge questions, False Authority shows the largest variation across models. Either False Authority or False Premise yields the highest hallucination rate for eight models, indicating substantial differences in how LALMs respond to fabricated sources and false factual framing. Qwen2.5-Omni and Gemini 3.7 Flash illustrate why this decomposition matters. Although their overall hallucination rates are nearly identical, Qwen2.5-Omni has a lower rate on Unknowable Provenance and a higher rate on False Premise than Gemini 3.7 Flash. This contrast is consistent with the stance analysis in Section 4.2 and shows that similar aggregate rates can reflect different response behaviors.

Table 11: Hallucination rates (%) of LALMs across hallucination categories and strategies. Lower is better; best results are **bolded**.

	Context				Knowledge					
Model	Contradicted Premise	Absent Premise	False Negation	Overall ↓	Niche Specifics	Unknowable Provenance	False Authority	False Premise	Overall ↓	Overall ↓
Open-Weight Model										
Qwen2-Audio Instruct	64.9	57.6	**39.3**	57.9	47.7	32.0	61.2	59.7	49.4	53.6
Qwen2.5-Omni	**49.3**	49.6	44.0	**48.2**	26.9	**1.4**	19.3	54.6	**23.9**	**36.1**
Kimi-Audio Instruct	64.3	51.7	45.2	57.7	39.7	15.3	56.0	66.9	43.3	50.5
Audio Flamingo 3	70.3	73.8	44.3	65.2	53.6	30.1	93.9	78.4	63.2	64.2
Step-Audio 2 mini	79.2	83.7	47.6	73.1	51.2	58.8	90.2	77.1	70.5	71.8
MiMo-Audio Instruct	85.0	90.9	50.6	78.5	56.2	49.3	95.2	82.8	71.1	74.8
Qwen3-Omni Instruct	72.8	70.1	54.4	68.2	40.7	57.4	71.5	59.7	59.0	63.6
Covo-Audio	76.0	69.6	68.3	73.1	57.6	29.3	45.9	72.9	49.5	61.3
MiMo-V2.5	60.5	48.5	47.8	55.5	35.8	48.9	28.2	42.1	39.5	47.5
Closed-Weight Model										
Gemini 3.7 Flash	55.9	**34.8**	40.7	48.6	**22.5**	34.2	**12.5**	**25.8**	24.4	36.5

Table 12 further separates the mitigation results by strategy. AAD provides the broadest improvements, reducing hallucination in 49 of the 56 model–strategy combinations. It improves Absent Premise for all eight models and each of the other six strategies for at least six models. Averaged across models, its largest reductions occur for Absent Premise, False Premise, Contradicted Premise, and False Authority. This pattern is consistent with AAD suppressing plausible continuations that are not supported by the observed audio. The remaining regressions, particularly for Qwen2.5-Omni, show that its effect is not uniform across models and strategies. VCD exhibits a narrower pattern. It reduces hallucination on Contradicted Premise and Absent Premise for seven models, but produces almost no average change on False Negation and remains inconsistent across the knowledge strategies.

MTI and DoLa show distinct failure patterns. MTI increases hallucination on Contradicted Premise and Absent Premise for every model, while reducing it on Unknowable Provenance and False Authority for six models. This pattern is consistent with MTI discouraging some uncertain factual assertions while failing to improve premise checking against the audio. DoLa reduces hallucination on False Negation for six models and False Authority for five, but does not improve Niche Specifics for any model. Its effects vary across the remaining models and strategies, providing further evidence that intermediate-layer disagreement is not a stable hallucination signal across LALMs.

Table 12: Hallucination rates (%) of LALMs under four mitigation methods. W/O denotes the unmitigated baseline. Lower is better; best results are **bolded**.

	Context				Knowledge					
Method	Contradicted Premise	Absent Premise	False Negation	Overall ↓	Niche Specifics	Unknowable Provenance	False Authority	False Premise	Overall ↓	Overall ↓
Qwen2-Audio Instruct										
W/O	64.9	57.6	39.3	57.9	47.7	32.0	61.2	59.7	49.4	53.6
AAD	61.7	**48.1**	**35.8**	**53.5**	**42.6**	38.7	51.7	**46.0**	44.6	49.0
VCD	**61.0**	51.0	39.6	54.4	44.0	**27.0**	**49.1**	52.9	**42.2**	**48.3**
MTI	69.1	63.5	41.7	62.0	49.3	33.2	57.9	57.4	48.5	55.3
DoLa	63.2	57.3	36.1	56.1	50.5	37.0	59.3	62.7	51.7	53.9
Qwen2.5-Omni										
W/O	49.3	49.6	44.0	48.2	26.9	1.4	19.3	54.6	23.9	36.1
AAD	52.0	**38.4**	45.3	48.0	**25.8**	4.4	21.5	**48.7**	**23.8**	35.9
VCD	54.3	48.3	43.1	50.7	26.9	3.6	22.8	56.1	26.0	38.3
MTI	**49.8**	52.7	**36.1**	**47.3**	29.7	**1.2**	**20.8**	52.3	24.1	**35.7**
DoLa	53.1	49.3	43.0	50.1	28.5	1.6	25.9	57.9	26.8	38.5
Kimi-Audio Instruct										
W/O	64.3	51.7	45.2	57.7	39.7	15.3	56.0	66.9	43.3	50.5
AAD	**44.5**	**42.0**	**31.5**	**41.2**	**22.4**	11.4	**28.3**	**37.6**	**24.4**	**32.8**
VCD	62.3	52.7	44.8	56.6	39.9	14.6	54.1	64.6	42.0	49.3
MTI	67.6	64.1	49.0	62.9	43.6	**7.1**	48.9	68.0	39.7	51.3
DoLa	56.4	48.0	36.6	50.5	40.5	11.7	56.9	62.9	41.4	45.9
Audio Flamingo 3										
W/O	70.3	73.8	44.3	65.2	53.6	30.1	93.9	78.4	63.2	64.2
AAD	**52.5**	**48.7**	**37.5**	**48.5**	**43.4**	**17.0**	**76.0**	**65.7**	**49.4**	**48.9**
VCD	66.0	68.1	43.2	61.4	53.7	26.7	90.8	77.1	60.9	61.2
MTI	76.6	85.0	47.7	71.8	60.3	20.6	90.0	79.9	60.6	66.2
DoLa	73.6	80.2	41.8	67.8	60.5	31.8	94.5	80.7	65.5	66.7
Step-Audio 2 mini										
W/O	79.2	83.7	47.6	73.1	51.2	58.8	90.2	77.1	70.5	71.8
AAD	76.0	**78.8**	46.1	69.9	53.1	56.4	82.0	73.6	67.0	68.5
VCD	**73.0**	80.2	45.0	**68.2**	**49.8**	56.7	83.6	71.9	66.6	67.4
MTI	86.5	91.1	56.7	80.8	60.7	**47.5**	86.8	77.4	67.7	74.2
DoLa	74.5	84.6	**42.0**	69.2	53.3	53.6	**77.2**	**70.8**	**64.2**	**66.7**
MiMo-Audio Instruct										
W/O	85.0	90.9	50.6	78.5	56.2	49.3	95.2	82.8	71.1	74.8
AAD	**69.8**	**71.9**	**39.2**	**63.5**	**41.4**	**23.3**	**72.6**	**59.2**	**48.5**	**56.0**
VCD	83.0	89.3	51.9	77.3	56.6	52.6	93.9	81.6	71.6	74.5
MTI	86.8	93.2	56.1	81.2	58.7	43.6	94.6	81.9	69.4	75.3
DoLa	85.9	92.5	52.7	79.8	62.4	54.8	92.9	84.1	73.7	76.7
Qwen3-Omni Instruct										
W/O	72.8	70.1	54.4	68.2	40.7	57.4	71.5	59.7	59.0	63.6
AAD	**60.9**	**48.4**	**44.5**	**55.0**	**34.7**	47.6	65.7	61.0	**53.7**	**54.3**
VCD	71.1	63.7	56.1	66.4	42.8	59.4	75.9	64.7	62.5	64.4
MTI	74.6	72.7	59.7	71.0	44.1	**44.4**	71.6	63.0	56.3	63.6
DoLa	72.2	71.9	54.9	68.4	45.1	56.1	**59.9**	**60.2**	56.4	62.4
Covo-Audio										
W/O	76.0	69.6	68.3	73.1	57.6	29.3	45.9	72.9	49.5	61.3
AAD	**47.4**	**38.7**	**56.2**	**47.7**	**46.3**	**19.0**	40.1	**59.7**	**39.5**	**43.6**
VCD	74.9	68.8	70.3	72.8	60.9	31.9	47.8	71.8	51.0	61.9
MTI	83.0	75.5	78.0	80.5	72.2	36.5	44.1	82.7	56.2	68.3
DoLa	74.0	73.5	67.0	72.3	69.0	27.4	**35.9**	71.6	47.8	60.1

E.5 QUALITATIVE EXAMPLES



Figure 14: Representative grounded and hallucinated LALM responses to context and knowledge questions.